

reledmac

Typeset scholarly editions with L^AT_EX*

Maïeul Rouquette[†]

based on the original ledmac by

Peter Wilson

Herries Press

which was based on the original edmac, tabmac and edstanza by

John Lavagnino, Dominik Wujastyk, Herbert Breger and Wayne Sullivan.

Abstract

The **reledmac** provides many tools in order to typeset scholarly editions. It is based on the **eledmac** package, which was based on the **ledmac** package, which was based on the **edmac** T_EX package.

It can be used in combination with **reledpar** in order to typeset two texts in parallel, like an original text and its translation in a modern language.

reledmac provides many tools and options. Normally, they are all documented in this file. Also provided is a help folder, “examples”. The folder contains additional examples (although not for every possible case). Examples starting with “1-” are for basic uses, those starting with “2-” are for advanced uses.

To report bugs or request a new feature, please go to ledmac GitHub page and click on “New Issue”: <https://github.com/maieul/ledmac/issues/>. You must create an account on github.com to access my page (maieul/ledmac). GitHub accounts are free for open-source users. You can post messages in English or in French (preferred).

You can subscribe to the **reledmac** mail list at:
<http://geekographie.maieul.net/146>

Contents

1 Introduction	12
1.1 Aim of the package	12
1.2 History	13
1.2.1 edmac	13
1.2.2 ledmac	14
1.2.3 eledmac	15

*This file (reledmac.dtx) has version number v2.35.1, last revised 2020/12/20.

[†]maieul at maieul dot net

1.2.4 <code>reledmac</code>	15
1.3 Bibliography	15
1.4 Acknowledgements	15
2 How the package works — the problem of the number of \LaTeX runs	15
3 Compatibility warning	16
4 Options	16
4.1 Specific features	16
4.2 Optimizing package performance	17
5 Text lines and paragraphs numbering	18
5.1 Text lines numbering	18
5.2 Paragraphs	18
5.2.1 Basics	18
5.2.2 Automatically producing <code>\pstart ... \pend</code>	19
5.2.3 Content before specific <code>\pstart</code> and after specific <code>\pend</code>	19
5.2.4 Content before every <code>\pstart</code> and after every <code>\pend</code>	20
5.2.5 Numbering paragraphs (<code>\pstart</code>)	20
5.2.6 Languages written in Right to Left	21
5.2.7 Memory limits	21
5.3 Lineation commands	21
5.3.1 Disabling lineation	21
5.3.2 Setting lineation start and step	22
5.3.3 Setting lineation reset	22
5.3.4 Setting line number margin	23
5.3.5 Other settings	23
5.4 Changing the line numbers	23
5.4.1 Sublineation	23
5.4.2 Locking lineation	24
5.4.3 Setting and changing line number	24
5.4.4 Line number style	24
5.4.5 Skipping and hiding number	25
5.5 Adding annotations to line numbers	25
5.5.1 Resetting annotation	26
5.5.2 Modifying annotation associated with a specific note	27
5.5.3 Changing the position of the annotation	27
5.5.4 Changing the macro in which annotations are wrapped	27
5.5.5 Not printing the second identical annotations	28
5.5.6 Separator between annotations	28
5.5.7 Annotations in the apparatus	28
5.6 Executing code at each line	28
5.7 Executing code at a specific line	29

6 Apparatus commands	29
6.1 Terminology	29
6.2 Critical notes	30
6.2.1 The lemma	30
6.2.2 Footnotes	30
6.2.3 Endnotes	31
6.2.4 Paragraph in critical apparatus	32
6.2.5 Change lemma and line number	33
6.2.6 Changing the names of commands for critical apparatus	33
6.3 Disambiguation of identical words in the apparatus	34
6.3.1 Basic use	34
6.3.2 Case setting	34
6.3.3 Notes about input encoding with UTF-8 processor	34
6.3.4 Notes about right-to-left texts	35
6.3.5 Use with <code>\lemma</code> command	35
6.3.6 Sameword for a group of words	37
6.3.7 Customizing	38
6.3.8 Problems with some macros	38
6.3.9 Automatic sameword annotation	39
6.4 Apparatus of manuscripts	39
6.4.1 Marking sections of text	39
6.4.2 Layout of the apparatus of manuscripts	40
6.4.3 Settings	40
6.5 Familiar notes	41
6.5.1 Basic use	41
6.5.2 Customizing mark	41
6.5.3 Separator for multiple footnotes	41
6.6 Printing the footnote mark without printing the footnote text	42
6.7 Changing series	42
6.7.1 Create a new series	42
6.7.2 Delete series	42
6.7.3 Series order	42
6.8 Position of critical and familiar footnotes	42
7 Apparatus customization	43
7.1 Introduction	43
7.2 Introduction	43
7.3 Notes arrangement in a series	44
7.4 Control number printing	45
7.4.1 Print line number only at first time	45
7.4.2 Print page number only at first time	45
7.4.3 Arbitrary text before line number	46
7.4.4 Separator for line range	46
7.4.5 Abbreviate line range	46
7.4.6 Disabling line number printing	47
7.4.7 Printing pstart number	47

7.4.8 Printing stanza number	47
7.4.9 Disabling line number printing	48
7.4.10 Options for line number annotations	48
7.4.11 Separator between line and subline numbers	48
7.4.12 Separator between page and line numbers	49
7.4.13 Space around number	49
7.4.14 Space around line symbol	49
7.4.15 Space in place of number	49
7.4.16 Boxing line number and line symbol	49
7.5 Separator between the lemma and the note	50
7.5.1 For footnotes	50
7.5.2 For endnotes	51
7.6 Font style	51
7.6.1 For line number	51
7.6.2 For the lemma	51
7.6.3 For all notes	52
7.7 Wrapping notes	52
7.7.1 Wrapping lemmas	52
7.7.2 Wrapping contents	52
7.8 Indent of notes content	52
7.9 Arbitrary code	53
7.9.1 Arbitrary code around line number	53
7.9.2 Arbitrary code at the beginning of notes	53
7.9.3 Arbitrary code before inserting note	53
7.10 Options for footnotes in columns	54
7.10.1 Alignment	54
7.10.2 Size of the columns	54
7.11 Options for paragraphed footnotes and notes grouped by line	54
7.11.1 Mark separation of notes	54
7.11.2 Ragged text	55
7.12 Options for block of notes	55
7.12.1 Grouping notes by line	55
7.12.2 Text before notes	55
7.12.3 Code before notes	55
7.12.4 Spacing	56
7.12.5 Rule	56
7.12.6 Maximum height	56
7.12.7 Width	57
7.13 Footnotes and the <code>reledpar</code> columns	57
7.14 Endnotes in one paragraph	57

9 Verse	58
9.1 Basic	58
9.2 Define stanza indents	58
9.3 Repeating stanza indents	59
9.4 Notes about the scope of the indent settings	59
9.5 Manual stanza indent	60
9.6 Stanza breaking	60
9.7 Hanging symbol	60
9.8 Long verse and page break	61
9.9 Content before/after verses	61
9.10 Numbering stanza	62
9.11 Antilabe	62
9.12 Various tools	63
9.13 Notes on empty lines	63
10 Grouping	63
11 Cross referencing	64
11.1 Basic use	64
11.2 Cross-referencing to a critical note	64
11.3 Cross-referencing which return a number in any case	64
11.3.1 Cross-referencing in order to define line number of a critical note	65
11.4 Not automatic cross-referencing	65
11.5 Normal \LaTeX cross-referencing	66
11.6 References to start and end lines	66
11.6.1 Reference to main text lines	66
11.6.2 References to lines that are commented on in the apparatus	66
11.6.3 Settings	66
11.6.4 Combining multiple references	68
11.7 Compatibility with <code>xr</code> package	69
12 Sidenotes	69
12.1 Basics	69
12.2 Setting	69
12.2.1 Width	69
12.2.2 Vertical position	70
12.2.3 Distance to the main text	70
12.2.4 Font	70
12.2.5 Separator between notes	70
13 Indexing	70
13.1 Basics	70
13.2 Use with <code>imakeidx</code> or <code>indextools</code>	70
13.3 Referring to critical notes	71
13.4 Separator between page and line numbers	71
13.5 Using <code>xindy</code>	72

13.6 Advanced setting	72
14 Glossary	73
14.1 Preamble setting	73
14.2 Commands	73
15 Tabular material	73
16 Sectioning commands	76
16.1 Sectioning commands without line numbers or critical notes	76
16.2 Sectioning commands with line numbering and critical notes	77
16.3 Optimization	78
17 Quotation environments	78
18 Page breaks	78
18.1 Control page breaking	78
18.2 Prevent page break in a long verses	78
19 Miscellaneous	79
19.1 Known and suspected limitations	79
19.1.1 Non-standard geometry	79
19.1.2 floatrow package compatibility	79
19.1.3 “No room for a new”	79
19.1.4 Marginal notes	80
19.1.5 Paragraph shape	80
19.1.6 Paragraphed footnotes	80
19.1.7 Use with other packages	81
19.2 Parallel typesetting	82
I Implementation overview	83
II Preliminaries	83
II.1 Links with original edmac	83
II.2 Package declaration	83
II.3 Package options	84
II.3.1 Options of reledpar	84
II.3.2 Options of reledmac	84
II.4 Loading packages	86
II.5 Compatibility with LuaTeX	87
II.6 Boolean flags	87
II.7 Messages	88
II.8 Gobbling	95
II.9 Wrapping content	95
II.10 Miscellaneous commands	96
II.11 Prepare reledpar	96

II.12 Booleans provided by other optional packages which are required in any case	97
III Sectioning commands	98
IV List macros	103
V Line counting	104
V.1 Choosing the system of lineation	104
V.2 Line number margin	106
V.3 Line number initialization and increment	107
V.4 Line number locking	108
V.5 Line number style	109
V.6 Line number printing	110
V.7 Line number counters and lists	111
V.8 Line number locking counter	113
V.9 Line number associated to lemma	113
V.10 Reading the line-list file	116
V.11 Commands within the line-list file	119
V.12 Writing to the line-list file	132
VI Marking text for notes	140
VI.1 <code>\edtext</code> itself	141
VI.2 Substitute lemma	148
VI.3 Substitute line numbers	149
VI.4 Lemma disambiguation	150
VII Paragraph decomposition and reassembly	157
VII.1 Boxes, counters, <code>\pstart</code> and <code>\pend</code>	157
VII.2 Processing one line	164
VII.2.1 General process	164
VII.2.2 Process for “normal” line	165
VII.2.3 Process for line containing <code>\eledsection</code> command	167
VII.2.4 Hooks	168
VII.2.5 Sidenotes and marginal line number initialization	169
VIII Line and page number computation	170
VIII.1 Continuous line numbering between parallel typesetting and normal typesetting	173
IX Line number annotation	174
X Line number printing	176
XI Pstart number printing inside	181

XII Restoring footnotes and penalties	182
XII.1 Add insertions to the vertical list	182
XII.2 Penalties	185
XII.3 Printing leftover notes	185
XII.4 Text before notes	186
XIII Critical footnotes	188
XIII.1 Fonts	188
XIII.2 Individual note options	188
XIII.3 Notes language	189
XIII.4 General survey of the way we manage notes	190
XIII.5 General setup	191
XIII.6 Footnotes arrangement	191
XIII.6.1 User level macro	191
XIII.6.2 Normal footnote	192
XIII.6.3 Paragraphed footnotes	197
XIII.6.4 Columnar footnotes	204
XIII.7 Footnote paragraph indent	211
XIII.8 Footnote hanging indent	212
XIII.9 Critical notes presentation	212
XIII.9.1 Font tools	212
XIII.9.2 Pstart number in footnote	213
XIII.9.3 Lemma printing	213
XIII.9.4 Line number printing	214
XIII.9.5 Footnote grouped by line	227
XIV Familiar footnotes	228
XIV.1 Adjacent footnotes	228
XIV.2 Regular footnotes for numbered texts	230
XIV.3 Footnote formats	232
XIV.4 Footnote arrangement	232
XIV.4.1 User level macro	232
XIV.4.2 Normal footnotes	233
XIV.4.3 Two columns footnotes	239
XIV.4.4 Three columns footnotes	241
XIV.4.5 Paragraphed footnotes	243
XIV.5 Wrapping footnote marks in hyperlink	248
XV Code common to both critical and familiar footnote in normal arrangement	249
XVI Footnotes' width for two columns	249
XVII Footnotes' order	251
XVIII Footnotes' rule	251

XIX Specific skip for first series of footnotes	251
XIX.1 Overview	251
XIX.2 User level command	252
XIX.3 Internal commands	252
XX Endnotes	254
XX.1 Internal commands	254
XX.2 User level commands	258
XX.2.1 Inserting contents to endnotes	258
XX.2.2 Printing endnotes	259
XXI Generate series of notes	268
XXI.1 Test if series is still existing	268
XXI.2 Init specific to <code>reledpar</code>	269
XXI.3 For critical footnotes	269
XXI.3.1 Options	269
XXI.3.2 Create inserts, needed to add notes in foot	271
XXI.3.3 Create commands for critical apparatus, <code>\Afootnote</code> , <code>\Bfootnote</code> etc.	271
XXI.3.4 Set standard display	274
XXI.4 For familiar footnotes	274
XXI.4.1 Options	274
XXI.4.2 Create tools for familiar footnotes (<code>\footnoteX</code>)	275
XXI.5 The endnotes	277
XXI.5.1 The auxiliary file	277
XXI.5.2 The main macro	278
XXI.5.3 Tools	278
XXI.5.4 Internal commands	279
XXI.5.5 The options	279
XXI.6 Init standards series (A,B,C,D,E)	281
XXII Setting series display	281
XXII.1 Change series order	281
XXII.2 Test series order	282
XXII.2.1 Get the first series	282
XXII.3 Series setting	282
XXII.3.1 General way of working	282
XXII.3.2 Tools to set options	283
XXII.3.3 Tools to generate options commands	284
XXII.3.4 Options for critical notes	286
XXII.3.5 Options for familiar notes	288
XXII.3.6 Options for endnotes	289
XXII.4 Hooks for a particular footnote	290
XXII.5 Alias	292

XXIII Output routine	292
XXIII.1 Extra footnotes output	293
XXIII.2 Patching standard output's commands	296
XXIV Page numbering in parallel typesetting	298
XXV Cross referencing	301
XXV.1 Compatibility with xref	317
XXVI Sidenotes	318
XXVII Minipages and such	326
XXVIII Indexing	331
XXVIII.1 Looking on package order	331
XXVIII.2 Auxiliary macros for <code>\edindex</code>	332
XXVIII.3 Code specific to <code>\edindex</code> in critical footnotes	333
XXVIII.4 Analysis of command in indexed text	334
XXVIII.5 Code for the formatted index	334
XXVIII.6 Main code	335
XXVIII.7 Hyperlink	337
XXVIII.8 "innote" and "notenumber" option of <code>indextools</code> package	340
XXIX Glossaries	340
XXX Verse	343
XXX.1 Hanging symbol management	343
XXX.2 Using & character	344
XXX.3 Code category setting	344
XXX.4 Stanza count and indent	345
XXX.5 Numbering stanza	346
XXX.6 Stanza number in note	347
XXX.7 Main work	348
XXX.8 Restore catcode and penalties	351
XXX.9 Dealing with antilabe	351
XXXI Apparatus of Manuscripts	352
XXXI.1 User level macro	352
XXXI.2 Setting macro	354
XXXI.3 Counters and lists	354
XXXI.4 Auxiliary file macros	355
XXXI.5 Action macro	356
XXXI.6 Inserting footnote	361
XXXI.7 Other	361

XXXII Arrays and tables	362
XXXII.1 Preamble: macro as environment	362
XXXII.2 Tabular environments	366
XXXII.2.1 Disabling and restoring commands	366
XXXII.2.2 Counters, boxes and lengths	370
XXXII.2.3 Tabular typesetting	373
XXXII.2.4 Environments	384
XXXIII Quotation's commands	385
XXXIV Section's title commands	386
XXXIV.1 Commands to disable some feature	386
XXXIV.2 General overview	386
XXXIV.3 <code>\beforeeledchapter</code> command	387
XXXIV.4 Auxiliary commands	387
XXXIV.5 Patching standard commands	388
XXXIV.6 Main code of <code>\eledxxx</code> commands	393
XXXIV.7 Macros written in the auxiliary file	396
XXXV Page breaking or no page breaking depending on specific lines	398
XXXVI Long verse: prevents being separated by a page break	400
XXXVII Tools for hyperref package	401
XXXVIII Compatibility with <code>eledmac</code>	401
Appendix A Things to do when changing versions	404
A.1 Migrating from <code>edmac</code> to <code>ledmac</code>	404
A.2 Migration from <code>ledmac</code> to <code>eledmac</code>	405
A.3 Migration to <code>eledmac</code> 1.5.1	406
A.4 Migration to <code>eledmac</code> 1.12.0	406
A.5 Migration to <code>eledmac</code> 17.1	407
A.6 Migration to <code>eledmac</code> 1.21.0	407
A.6.1 <code>\Xledsetnormalparstuff</code> and <code>\ledsetnormalparstuffX</code> . . .	407
A.6.2 Endnotes	407
A.7 Migration to <code>eledmac</code> 1.22.0	407
A.8 Migration to <code>eledmac</code> 1.23.0	407
A.9 Migration from <code>eledmac</code> to <code>reledmac</code>	408
A.9.1 Risk of 'no room for a new'	408
A.9.2 Multiple indices with memoir	408
A.9.3 Deprecated commands and options	408
A.9.4 <code>\renewcommand</code> replaced by <code>command</code>	409
A.9.5 Commands the names of which have been changed	409
A.9.6 Endnotes	411
A.9.7 Z Series	411
A.9.8 Internal commands	411

A.10 Migration to reledmac 2.1.0	411
A.11 Migration to reledmac 2.1.3	411
A.12 Migration to reledmac 2.3.0	411
A.13 Migration to reledmac 2.4.0	412
A.14 Migration to reledmac 2.5.0	412
A.15 Migration to reledmac 2.7.0	412
A.16 Migration to reledmac 2.7.2	412
A.17 Migration to reledmac 2.8.0	412
A.18 Migration to reledmac 2.13.1	412
A.19 Migration to reledmac 2.18.0	413
A.20 Migration to reledmac 2.21.0	413
A.21 Migration to reledmac 2.24.0	413
A.22 Migration to reledmac 2.26.0	413
A.23 Migration to reledmac 2.27.1	413
A.24 Migration to reledmac 2.30.0	413
A.25 Migration to reledmac 2.31.1	414
A.26 Migration to reledmac 2.32.7	414
A.27 Migration to reledmac 2.33.0	414
Appendix B Auxiliary softwares	414
B.1 <i>samewords</i>	414
B.2 critical-keys for <i>Emacs</i>	414
B.3 critical-marks for <i>Emacs</i>	414
B.4 Import from TEI	414
B.5 Import from TEI	414
References	416
Index	416
Change History	469

1 Introduction

1.1 Aim of the package

The `reledmac` package, together with `ℒATEX`, provides several important facilities for formatting critical editions of texts in a traditional manner. Major features include:

- automatic stepped line numbering, by page, section or paragraph;
- sub-lineation within the main series of line numbers;
- variant readings automatically keyed to line numbers;
- caters to both prose and verse;
- multiple series of footnotes and endnotes;

- block or columnar formatting of the footnotes;
- simple tabular material may be line numbered;
- indexing keyed to page and line numbers.

`reledmac` allows the scholar engaged in preparing a critical edition to focus attention wholly on the task of creating the critical text and evaluating the variant readings, text-critical notes and testimonia. \LaTeX and `reledmac` will take care of the formatting and visual correlation of all the disparate types of information.

Apart from `reledmac` there are other \LaTeX packages for typesetting critical editions. However, the aim of `reledmac` is to provide an “all in one” and flexible tool in the field of critical editions.

Any suggestions for new features are welcome.

This manual contains a general description of how to use `reledmac`, followed by the complete source code and its extensive documentation (in sections I and following, enumerated with Roman numerals). It ends with a list of actions to do when migrating from one version to other, a change history and an index to the source code.

You do not need to read the source code for this package in order to use it; we provide this code primarily for reference, and many of our comments on it repeat material that is also found in earlier sections. But no documentation, however thorough, can cover every question that comes up and many can be answered quickly by consulting the code. On a first reading, we suggest that you read only the general documentation in sections 2, unless you are particularly interested in the innards of `reledmac`.

1.2 History

1.2.1 edmac

The original version of `edmac` was `TEXTED.TEX`, written by John Lavagnino in late 1987 and early 1988 for formatting critical editions of English plays.

John passed these macros on to Dominik Wujastyk who, in September–October 1988, added the footnote paragraphing mechanism, margin swapping and other changes to suit his own purposes, making the style more like that traditionally used for classical texts in Latin and Greek (e.g., the Oxford Classical Texts series). He also wrote some extra documentation and sent the files out to several people. This version of the macros was the first to be called `edmac`.

The present version was developed in the summer of 1990, with the intent of adding necessary features, streamlining and documenting the code, and further generalizing it to make it easily adaptable to the needs of editors in different disciplines. John did most of the general reworking and documentation, with the financial assistance of the Division of the Humanities and Social Sciences, California Institute of Technology. Dominik adapted the code to the conventions of Frank Mittelbach’s `doc` option, and added some documentation, multiple-column footnotes, cross-references, and crop marks.¹ A description by John and Dominik of this version of `edmac` was published as “An overview of `edmac`: a `PLAIN` \TeX format for critical editions”, *TUGboat* 11 (1990), pp. 623–643.

¹This version of the macros was used to format the Sanskrit text in volume I of *Metarules of Pāṇinian Grammar* by Dominik Wujastyk (Groningen: Forsten, 1993).

From 1991 through 1994, the macros continued to evolve, and were tested at a number of sites. We are very grateful to all the members of the (now defunct) `edmac@mailbase.ac.uk` discussion group who helped us with smoothing out the bugs and infelicities in the macros. Ron Whitney and our anonymous reviewer at the TUG were both of great help in ironing out last-minute wrinkles, while Ron made some important suggestions which may help to make future versions of `edmac` even more efficient. Wayne Sullivan, in particular, provided several important fixes and contributions, including adapting the Mittelbach/Schöpf “New Font Selection Scheme” for use with PLAIN \TeX and `edmac`. Another project Wayne has worked on is a DVI post-processor which works with an `edmac` that has been slightly modified to output `\specials`. This combination enables you to recover to some extent the text of each line as ASCII code, facilitating the creation of concordances, an *index verborum*, etc.

As of 1994, we were pleased to be able to say that `edmac` was being used for the real-life book production of several interesting editions, such as the Latin texts of Euclid’s *Elements*,² an edition of the letters of Nicolaus Copernicus,³ Simon Bredon’s *Arithmetica*,⁴ a Latin translation by Plato of Tivoli of an Arabic astrolabe text,⁵ a Latin translation of part II of the Arabic *Algebra* by Abū Kāmil Shujā’ b. Aslam,⁶ the Latin *Rithmachia* of Werinher von Tegernsee,⁷ a middle-Dutch romance epic on the Crusades,⁸ a seventeenth-century Hungarian politico-philosophical tract,⁹ an anonymous Latin compilation from Hungary entitled *Sermones Compilati in Studio Generali Quinqe ecclesiensi in Regno Ungarie*,¹⁰ the collected letters and papers of Leibniz,¹¹ Theodosius’s *Spherics*, the German *Algorismus* of Sacrobosco, the Sanskrit text of the *Kāśikāvṛtti* of Vāmana and Jayāditya,¹² and the English texts of Thomas Middleton’s collected works.

1.2.2 ledmac

Version 1.0 of `tabmac` was released by Herbert Breger in October 1996. This added the capability for typesetting tabular material.

Version 0.01 of `edstanza` was released by Wayne Sullivan in June 1992, to help a colleague with typesetting Irish verse.

In March 2003 Peter Wilson started an attempt to port `edmac` from \TeX to LaTeX.

²Gerhard Brey used `edmac` in the production of Hubert L. L. Busard and Menso Folkerts, *Robert of Chester’s (?) Redaction of Euclid’s Elements, the so-called Adelard II Version*, 2 vols., (Basel, Boston, Berlin: Birkhäuser, 1992).

³Being prepared at the German Copernicus Research Institute, Munich.

⁴Being prepared by Menso Folkerts *et al.*, at the Institut für Geschichte der Naturwissenschaften in Munich.

⁵Richard Lorch, Gerhard Brey *et al.*, at the same Institute.

⁶Richard Lorch, “Abū Kāmil on the Pentagon and Decagon” in *Vestigia Mathematica*, ed. M. Folkerts and J. P. Hogendijk (Amsterdam, Atlanta: Rodopi, 1993).

⁷Menso Folkerts, “Die *Rithmachia* des Werinher von Tegernsee”, *ibid.*

⁸Geert H. M. Claassens, *De Middelnederlandse Kruisvaartromans*, (Amsterdam: Schipphower en Brinkman, 1993).

⁹Emil Hargittay, Csáky István: *Politica philosophiai Okoskodás-szerint való rendes életnek példája (1664–1674)* (Budapest: Argumentum Kiadó, 1992).

¹⁰Being produced, as was the previous book, by Gyula Mayer in Budapest.

¹¹Leibniz, *Sämtliche Schriften und Briefe*, series I, III, VII, being edited by Dr. H. Breger, Dr. N. Gädke and others at the Leibniz-Archiv, Niedersächsische Landesbibliothek, Hannover. (see <http://www.nlb-hannover.de/Leibniz>)

¹²Being prepared at Poona and Lausanne Universities.

The starting point was `edmac` version 3.16 as documented on 19 July 1994 (available from CTAN). In August 2003 the `tabmac` functions were added; the starting point for these being version 1.0 of October 1996. The `edstanza` (v0.01) functions were added in February 2004. Sidenotes and regular footnotes in numbered text were added in April 2004. This port was called `ledmac` (\LaTeX `edmac`).

Since July 2011, `ledmac` is maintained by Maïeul Rouquette. It is increasingly powerful and flexible, but it also has become increasingly divergent from the original TeX macro.

1.2.3 `eledmac`

Important changes were put in version 1.0, to make `ledmac` more easily extensible (see 7 p. 43). These changes can trigger small problems with the old customization. That is why a new name was selected: `eledmac` (extended `ledmac`).

To migrate from `ledmac` to `eledmac`, please read A.2 p. 405.

1.2.4 `reledmac`

`eledmac` has facilitated the creation of customized critical editions. However, the changes made to allow such customization were made in a non-systematic way. Many deprecated commands were kept and many technical “debts” were accumulated, hindering the future evolution of the package.

For these reasons, Maïeul Rouquette decided on a spring cleaning of the code. As some commands name were changed, the resulting compatibility was broken (a little).

A new name was selected: `reledmac` (extended renewed `eledmac`). To migrate from `eledmac` to `reledmac`, please read A.9 p. 408.

1.3 Bibliography

A collaborative list of works edited with (r)(e)ledmac is available at https://www.zotero.org/groups/209265/critical_editions_typeset_with_edmac_ledmac_eledmac_and_reledmac/. Please add your own edition made with (r)(e)ledmac.

If you write a book or an article about (r)(e)ledmac, please add it on the collaborative bibliography on <https://www.zotero.org/groups/1024519/>.

1.4 Acknowledgements

Maïeul Rouquette may thank his predecessor, and all the `reledmac` community. Especially, he may thanks all the people who checks English spell and grammar for the handbook.

2 How the package works — the problem of the number of \LaTeX runs

The `reledmac` package is a three-pass package like \LaTeX itself. Although your textual apparatus and line numbers will be printed on the first run, it takes two more compila-

tions by \LaTeX to be sure that everything is correctly placed, and one more if you typeset right-to-left text with \XeTeX . If you make any subsequent changes altering the number of lines or notes, the input file may similarly require three passes to get everything to the right place. `reledmac` will tell you that you need to make more runs when it detects changes, but it does not expend the labor to check this thoroughly. If you have problems with a line or two misnumbered at the top of a page, try running \LaTeX once or twice more.

However, the best way to be sure that one has made the right number of runs is to use some of \LaTeX 's run scripts like *latexmk*.

3 Compatibility warning

If you use other classes than `\article` or `\book`, or modify the layout with `geometry`, some settings should be made to have correct height for the blocks of notes.

Please read 7.12.6 p. 56.

If you use the \LuaTeX engine, you need \LuaTeX 1.1.0 or later. A file may mix *numbered* and *unnumbered* text.

Numbered text is printed with marginal line numbers and can include footnotes and endnotes that are referenced to those line numbers: this is how you will want to print the text that you are editing.

Unnumbered text is not printed with line numbers, and you can't use `reledmac`'s note commands with it: this is appropriate for introductions and other material added by the editor around the edited text.

4 Options

The package can be loaded with a number of global options which are listed here. There are two types of options: 1) options which provide specific features, and, 2) options which optimize the package's performance. It is advisable for you to read the relevant parts of the handbook, before reading about the first type of option (specific features), but you can look at the second type (package optimization) in your first reading of the manual.

4.1 Specific features

draft underlines lemmas in the main text.

auxdir `reledmac` generates auxiliary files. It could be useful to store them in a specific directory. You can set it using `auxdir=<folder>` option. Note the two following point:

1. \TeX is not able to create folder. You should create it yourself.
2. The option does not change the default \LaTeX auxiliary files (`.aux`, `.toc`, ...).

antilabe enable `\antilabe` feature (see 9.11 p. 62);

- eledmac-compat** help to migrate from eledmac to reledmac (see A.9.5 p. 409);
- nopenalties** must be called in some cases when using paragraphed endnotes (see ?? p. ??);
- nopbinverse** prevents page break within verse environment;
- noquotation** by default, the quotation environment is redefined within numbered text. You can disable this redefinition with `noquotation` (see 17 p. 78);
- noresetlinenumannotation** does not reset the annotations to line number at each line (see 5.5 p. 25);
- parapparatus** by default, the apparatus cannot contain paragraph breaks; this option enables paragraphing inside the apparatus;
- swcaseinsensitive** make `\sameword` command case insensitive;
- widthliketwocolumns** set the width of the text printed in a single column to be the same as the width of the text printed in two parallel columns with `reledpar`. This is useful when alternating between normal and parallel typesetting;
- xindy** and `xindy+hyperref` select `xindy` as the index processor (13.5 p. 72).

4.2 Optimizing package performance

- nocritical** disables tools for critical footnotes (`\Afootnote`, `\Bfootnote` etc.). If you do not need critical footnotes, this option lets `reledmac` run faster. It will also preserve room for other packages.
- noeledsec** disables tools for `\eledsection` and related commands (16.2 p. 77).
- noend** disables tools for endnotes (`\Aendnote`, `\Bendnote` etc.). If you do not need endnotes, this option lets `reledmac` run faster. It will also preserve room for other packages.
- nofamiliar** disables tools for familiar footnotes (`\footnoteA`, `\footnoteB` etc.). If you do not need familiar footnotes, this option lets `reledmac` run faster. It will also preserve room for other packages.
- noledgroup** `reledmac` allows use of a series of critical notes and a new series of normal notes inside `minipage` and `ledgroup` environments (see 10 p. 63). However, such features use up computer memory, at the expense of other processing needs. So if you do not need this feature, use `noledgroup` option. This should make `reledmac` faster.
- series** `reledmac` defines five levels of notes: A, B, C, D, E. Using all these levels consumes memory space and processing speed. This is why, if your work does not require the entire A–E series, you can narrow down the available number of series. For example, if you only need A and B series, call the package with `series={A,B}` option.

5 Text lines and paragraphs numbering

5.1 Text lines numbering

`\beginnumbering` Each section of numbered text must be preceded by `\beginnumbering` and followed by `\endnumbering`, as in the following example.

```
\beginnumbering
Text
\endnumbering
```

The `\beginnumbering` macro resets the line number to zero, reads an auxiliary file called `<jobname>.nn` (where `<jobname>` is the name of the main input file for this job, and `nn` is 1 for the first numbered section, 2 for the second section, and so on), and then creates a new version of this auxiliary file to collect information during this run. The first instance of `\beginnumbering` also opens a file called `<jobname>.<series>end` to receive the text of the endnotes. `\endnumbering` closes the `<jobname>.nn` file.

If the line numbering of a text is to be continuous from start to end, then the whole text will be typed between one pair of `\beginnumbering` and `\endnumbering` commands. But your text will most often contain chapter or other divisions marking sections that should be independently numbered, and these will be appropriate places to begin new numbered sections.

`reledmac` has to read and store in memory a certain amount of information about the entire section when it encounters a `\beginnumbering` command, so it speeds up the processing and reduces memory use when a text is divided into a larger number of sections (at the expense of multiplying the number of external files that are generated).

5.2 Paragraphs

5.2.1 Basics

`\pstart` Within a numbered section, each paragraph of numbered text must be marked using the `\pend` `\pstart` and `\pend` commands like this:

```
\pstart
Paragraph of text.
\pend
```

Text that appears within a numbered section but is not marked with `\pstart` and `\pend` will not be numbered.

The following example shows the proper section and paragraph markup and the kind of output that would typically be generated:

```

\beginnumbering
\pstart
This is a sample paragraph, with
lines numbered automatically.
\pend

\pstart
This paragraph too has its
lines automatically numbered.
\pend

The lines of this paragraph are
not numbered.

\pstart
And here the numbering begins
again.
\pend
\endnumbering

```

5.2.2 Automatically producing \pstart ... \pend

`\autopar` You can use `\autopar` to avoid the nuisance of this paragraph markup and still have every paragraph automatically numbered. The `\autopar` command needs to be called inside a `\beginnumbering... \endnumbering` structure, as follows:

```

\beginnumbering
\autopar

A paragraph of numbered text.

Another paragraph of numbered
text.

\endnumbering

```

`\autopar` fails, however, on paragraphs that start with a `{` or with any other command that starts a new group before it generates any text. Such paragraphs need to be started explicitly, before the new group is opened, using `\indent`, `\noindent`, or `\leavevmode`, or using `\pstart` itself.¹³

5.2.3 Content before specific \pstart and after specific \pend

Both `\pstart` and `\pend` can take an optional argument in brackets. Its content will be printed before the beginning of `\pstart` / after the end of `\pend` instead of the argument of `\AtEveryPstart` / `\AtEveryPend`.

¹³For a detailed study of the reasons for this restriction, see Barbara Beeton, “Initiation rites”, *TUGboat* 12 (1991), pp. 257–258.

Note that a `\noindent` will be automatically added before this argument, and, consequently, a `\parskip` will be inserted. You can use a second optional argument in brackets to avoid that `\noindent`.

```
\pstart[foo] % A \noindent will be inserted before foo.
\pstart[] [foo]% No \noindent before foo.
```

The second optional argument of `\pstart` / `\pend` replaces the argument of `\AtEveryPstart*` / `\AtEveryPend*`.

If you need to start a `\pstart` with brackets, or to add brackets after a `\pend`, just add a `\relax` between `\pstart ... \pend` and the brackets.

This feature is also useful when typesetting verses (see 9 p. 58) or `reledpar` (see 19.2 p. 82).

A `\noindent` is automatically added before this argument.

5.2.4 Content before every `\pstart` and after every `\pend`

`\AtEveryPstart` You can use both `\AtEveryPstart` and `\AtEveryPend`. Their arguments will be printed before every `\pstart` begins / after every `\pend` ends.
`\AtEveryPend`

Note that a `\noindent` will be inserted before the argument, and, consequently, a `\parskip`. You can use the starred version of `\AtEveryPstart` and `\AtEveryPend` to avoid the `\noindent`.

`\AtStartEveryPstart` The argument of `\AtStartEveryPstart` / `\AtEndEveryPend` will be inserted at
`\AtEndEveryPend` the beginning / the end of every `\pstart` / `\pend` in the same paragraph. For example, if you want each `\pstart` to start with a star, you can use:

```
\AtStartEveryPstart{*}
```

Instead of manually doing

```
\pstart * Real pstart content.\pend
```

5.2.5 Numbering paragraphs (`\pstart`)

`\numberpstarttrue` It is possible to insert a number at every `\pstart` command; you must use the
`\numberpstartfalse` `\numberpstarttrue` command to have it. You can stop the numbering with `\numberpstartfalse`.
`\thepstart` You can redefine the command `\thepstart` to change style. You can change the value of the `pstart` number by using *after* `\beginnumbering`:

```
\setcounter{pstart}{value}
```

On each `\beginnumbering` the numbering restarts.

`\sidepstartnumtrue` With the `\sidepstartnumtrue` command, the number of `\pstart` will be printed at the sides of the text. In this case, the line number will be not printed.

`\labelpstarttrue` With the `\labelpstarttrue` command, a `\label` added just after a `\pstart` will refer to the number of this `pstart`.

5.2.6 Languages written in Right to Left

If you use languages written right to left with Lua \TeX or Xe \TeX , you must switch text direction *before* the `\pstart` command.

5.2.7 Memory limits

This paragraph is kept for history, but the problems described below should not appear with the most recent version of \TeX .

`\pausenumbering`
`\resumenumbering` reledmac stores a lot of information about line numbers and footnotes in memory as it goes through a numbered section. But at the end of such a section, it empties its memory out, so to speak. If your text has a very long numbered section it is possible that your \TeX may reach its memory limit. There are two solutions to this.

The first solution is to get a larger \TeX with increased memory.

The second solution is to split your long section into several smaller ones. The trouble with this is that your line numbering will start again at zero with each new section. To avoid this problem, we provide `\pausenumbering` and `\resumenumbering` which are just like `\endnumbering ... \beginnumbering`, except that they arrange for your line numbering to continue across the break. Use `\pausenumbering` only between numbered paragraphs:

```
\beginnumbering
\pstart
Paragraph of text.
\pend
\pausenumbering

\resumenumbering
\pstart
Another paragraph.
\pend
\endnumbering
```

We have defined these commands as two macros, in case you find it necessary to insert text between numbered sections without disturbing the line numbering. But if you are really just using these macros to save memory, you might as well type,

```
\newcommand{\memorybreak}{\pausenumbering\resumenumbering}
```

and type `\memorybreak` between the relevant `\pend` and `\pstart`.

5.3 Lineation commands

5.3.1 Disabling lineation

`\numberlinefalse`
`\numberlinetrue` Line numbering can be disabled with `\numberlinefalse`. It can be enabled again with `\numberlinetrue`.

This feature must be used with caution.

- It should not be use if you have critical footnotes after `\numberlinefalse`.

- It could be used in the following cases:
 - You want only familiar footnotes, not critical footnotes;
 - You want only parallel typesetting (using `reledpar`) but no critical footnotes.
 - You disable, for a portion of text, line numbering
- It must not be used if:
 - You do not want to have the line number in the margins, but do want to use critical footnotes. In this case, set `\firstlinenum` to a big value, such as 100,000 (5.3.2 p. 22).
 - You want to freeze the line numbering for some line, but still keep critical footnotes. In this case, use `\startlock` (5.4.2 p. 24).

A successor to `reledmac` may disable this feature.

5.3.2 Setting lineation start and step

`\firstlinenum`
`\linenumincrement`

By default, `reledmac` numbers every 5th line. There are two counters that control this behavior: `firstlinenum` and `linenumincrement`. They can be changed using `\firstlinenum{<num>}` and `\linenumincrement{<num>}`. `\firstlinenum` specifies the first line that will have a printed number, and `\linenumincrement` is the difference between successive numbered lines. For example, to start printing numbers at the first line and to have every other line numbered:

```
\firstlinenum{1} \linenumincrement{2}
```

`\firstsublinenum`
`\sublinenumincrement`
`\linenumberlist`

There are similar commands, `\firstsublinenum{<num>}` and `\sublinenumincrement{<num>}` for controlling sub-line numbering.

You can define `\linenumberlist` to specify a non-uniform distribution of printed line numbers. For example:

```
\gdef\linenumberlist{1,2,3,5,7,11,13,17,19,23,29}
```

to have numbers printed on prime-numbered lines only. There must be no spaces within the definition which consists of comma-separated integer numbers. The numbers can be in any order but it is easier to read if you put them in numerical order. Either omitting the definition of `\linenumberlist` or following the empty definition

```
\gdef\linenumberlist{}
```

the standard numbering sequence is applied. The standard sequence is that specified by the combination of the `firstlinenum`, `linenumincrement`, `firstsublinenum` and `linenumincrement` counter values.

5.3.3 Setting lineation reset

`\lineation`

Lines can be numbered either by page, by `pstart` or by section; you specify this using the `\lineation{<arg>}` macro, where `<arg>` is either `page`, `pstart` or `section`.

You may only use this command at places where numbering is not in effect; you can't change the lineation system within a section. You can change it between sections: they don't all have to use the same lineation system. The package's standard setting is

`\lineation{section}`. If the lineation is by `pstart`, the `pstart` number will be printed before the line number in the notes.

5.3.4 Setting line number margin

`\linenummargin` The command `\linenummargin{<location>}` specifies the margin where the line (or `pstart`) numbers will be printed. The permissible values for `<location>` are `left`, `right`, `inner`, or `outer`: for example, `\linenummargin{inner}`. The package's default setting is

`\linenummargin{left}`

to typeset the numbers in the left hand margin. You can change this whenever you're not in the middle of making a paragraph.

More precisely, the value of `\linenummargin` used is the value in effect at the `\pend` of a numbered paragraph. Apart from an initial setting for `\linenummargin`, only change `\linenummargin` after a `\pend`, whereupon it will apply to all following numbered paragraphs, until changed again (changing it between a `\pstart` and `\pend` pair will apply the change to all of the current paragraph).

5.3.5 Other settings

`\leftlinenum` When a marginal line number is to be printed, there are many ways to display it. You can
`\rightlinenum` redefine `\leftlinenum` and `\rightlinenum` to change the way marginal line numbers
`\linenumsep` are printed in the left and right margins respectively; the initial versions print the number in font `\numlabfont` (described below) at a distance `\linenumsep` (initially set to one pica) from the text.

5.4 Changing the line numbers

Normally, line numbering starts at 1 for the first line of a section and increments by one for each line thereafter. There are various common modifications of this system and the commands described here allow you to put such modifications into effect.

5.4.1 Sublineation

`\startsub` You insert the `\startsub` and `\endsub` commands in your text to turn sub-lineation
`\endsub` on and off. For example, stage directions in plays are often numbered with sub-line numbers: as line 10.1, 10.2, 10.3, rather than as 11, 12, and 13. Titles and headings are sometimes numbered with sub-line numbers as well.

When sub-lineation is in effect, the line number counter is frozen and the sub-line counter advances instead. If one of these commands appears in the middle of a line, it doesn't take effect until the next line; in other words, a line is counted as a line or sub-line depending on what it started out as, even if it changes in the middle.

`\Xsublinesep` You can change the separator between the line number and the subline number ei-
`\Xsublinesepside` ther by using `\Xsublinesep` without any optional argument (7.4.11 p. 48) or by using `\Xsublinesepside`. In the second case, it will change the separator only for line numbers in the margins, not in the footnotes.

5.4.2 Locking lineation

`\startlock` The `\startlock` command, used in running text, locks the line number at its current value, until you insert `\endlock`. It can tell for itself whether you are in a patch of line or sub-line numbering. One use for line-number locking is in printing poetry: there the line numbers should be those of verse lines rather than of printed lines, even when a verse line requires several printed lines. But in this case you may use the `\stanza` mechanism, see 9 p. 58.

`\lockdisp` When line-number locking is used, several printed lines may have the same line number, and you have to specify whether you want the number attached to the first printed line or the last, or whether you just want the number printed by them all, assuming that the settings of the previous parameters requires the display of a line number for this line. You specify your preference using `\lockdisp{<arg>}`; its argument is a word, either `first`, `last`, or `all`. The package initially sets this as `\lockdisp{first}`.

5.4.3 Setting and changing line number

`\setline` In some cases you may want to modify the line numbers that are automatically calculated: if you are printing only fragments of a work but want to print line numbers appropriate to a complete version, for example. The `\setline{<num>}` and `\advanceline{<num>}` commands may be used to change the current line's number (or the sub-line number, if sub-lineation is currently on). They change both the marginal line numbers and the line numbers passed to the notes. `\setline` takes one argument, the value to which you want the line number set; it must be 0 or greater. `\advanceline` takes one argument, an amount that should be added to the current line number; it may be positive or negative.

`\setlinenum` The `\setline` and `\advanceline` macros should only be used within a `\pstart... \pend` group. The `\setlinenum{<num>}` command can be used outside such a group, for example, between a `\pend` and a `\pstart`. It sets the line number to `<num>`. It has no effect if used within a `\pstart... \pend` group.

5.4.4 Line number style

`\linenumberstyle` Line numbers are normally printed as arabic numbers. You can use `\linenumberstyle{<style>}` to change the numbering style. `<style>` must be one of:

`Alph` Uppercase letters (A ... Z).

`alph` Lowercase letters (a ... z).

`arabic` Arabic numerals (1, 2, ...)

`Roman` Uppercase Roman numerals (I, II, ...)

`roman` Lowercase Roman numerals (i, ii, ...)

Note that with the `Alph` or `alph` styles, “numbers” must be between 1 and 26 inclusive.

Similarly `\sublinenumberstyle{<style>}` can be used to change the numbering style of sub-line numbers, which is normally arabic numerals.

5.4.5 Skipping and hiding number

`\skipnumbering` When inserted into a numbered line the macro `\skipnumbering` causes the numbering of that particular line to be skipped; that is, the line number is unchanged and no line number will be printed. Note that if you use it in `\stanza`, you must call it at the beginning of the verse.

`\hidenumbering` When inserted into a numbered line, the macro `\hidenumbering` causes the number for that particular line to be hidden; namely, no line number will print. Note that if you use it in `\stanza`, you must call it at the beginning of the verse.

`\hidenumberingonleftpage` `\hidenumberingonleftpage` is like `hidenumbering`, but is applied only on left page. `\hidenumberingonrightpage` is applied on right page. They can be useful if the position of the line number is depending on the position of the page, but the position of the marginal note is fixed.

5.5 Adding annotations to line numbers

You may want to have two or more numbers associated with a line of text. Consider, for example, the following cases:

- You want to split a line of verse into two parts depending upon some stylistic / rhythmic / linguistic convention.
- You want to add the line number used by a previous edition of the work.
- You want to typeset biblical text, and use division in verse.

In such instances, you must add the second number manually, as `reledmac` can't determine a general pattern for such numbering, which depends too heavily upon the edited text.¹⁴

`\linenumannotation` To resolve this issue, `reledmac` allows you to annotate line numbers using the following command:

```
\linenumannotation{<annotation>}
```

The annotation can contain any textual value (whether number, text, or other) such as the line number from the older edition. Here are some characteristics of line number annotation:

- An annotation is associated with a line of text. It is reset with each new line of text, unless you use the `noresetlinenumannotation` option of `reledmac`.
- It is printed alongside the line number in the margin.
- It is printed following the line number in critical footnotes and endnotes.
- And of particular interest: the annotation is printed in the critical note *only* when the `\edtext` is issued after the `\linenumannotation`.

¹⁴However, you may create your own commands dealing with such patterns which will in turn call `reledmac` commands.

- If two or more annotations are called before an `\edtext`, the last one is used in associated notes.
- If an annotation is called within an `\edtext`, it is printed as an annotation for the end of the lemma.

Here is an example, supposing we are on line 1:

```
\edtext{first lemma}
\linenumannotation{A}
\edtext{second lemma}{...}
\edtext{third%
  \linenumannotation{B}
lemma}{...}
\edtext{fourth lemma}&
```

In the critical notes, the line number will be followed

- by nothing in the first lemma, as there is no annotation for this line;
- by “A” for the second lemma;
- by “A-B” for the third lemma, as it starts while annotation A is still in effect and it finishes after annotation B has already taken effect;
- by “B” for the fourth lemma.

Note that the annotation must be called before the beginning of a `\edtext` to be taken into account as a starting annotation. So:

```
\linenumannotation{A}\edtext{something...\linenumannotation{B}}{\Afootnote{foo}}
```

will use A as starting annotation, while:

```
\edtext{\linenumannotation{A}something...\linenumannotation{B}}{\Afootnote{foo}}
```

won't.

5.5.1 Resetting annotation

You can manually reset annotation using `\resetlinenumannotation{}`. Note that this macro takes no argument, but you should use empty brackets or `\in` order to avoid gobbling spaces.¹⁵

5.5.2 Modifying annotation associated with a specific note

`\lineannot` The `\linenum` (6.2.5 p. 33) macro changes the line number passed to a note. The `\lineannot` macro does the same for the annotations. It takes one argument, containing the beginning and ending annotations separated by a pipe (`|`). As with `\linenum`, if one wishes to change some specific part of the annotation, one can use

```
\lineannot{b}% to change the ending annotation
\lineannot{a}% to change the beginning annotation
\lineannot{a|b}% to change both
\lineannot{\empty}|}% to delete the beginning annotation
```

5.5.3 Changing the position of the annotation

By default, annotations are placed after line numbers in both margin and footnote.

To change this behavior, one can use one of the following commands:

- `\Xlinenumannotationposition[s]{v}` changes the position in critical footnotes with *s* for the series of footnotes to which it applies, where *s* may be a comma-separated list of series. When *s* is empty, the change applies also to annotations at the sides of the page, alongside the line number.
 - `\Xlinenumannotationpositionside{v}` changes the position at the sides of the page, alongside the line numbers.
- Note that `\Xlinenumannotationposition` without any optional argument will override this setting.
- `\Xendlinenumannotationposition[s]{v}` changes the position in critical endnotes, *s* for the series of endnotes to which it applies, where *s* may once again be a comma-separated list of series.

In each of these three commands, *v* can be `after` or `before` to indicate position with regards to the line number.

With the `\linenumannotationothersidettrue`, the annotation will appear on the margin side opposite to the line number.

You can reset the default behavior with `\linenumannotationothersidefalse`.

5.5.4 Changing the macro in which annotations are wrapped

By default, annotations are wrapped in the `\textsuperscript` macro. You can modify this using one of the following:

- `\Xwraplinenumannotation[s]{cmd}` for critical footnotes; *s* indicates the series of notes to which it applies and may be a comma-separated list of series. When *s* is empty, the change applies to the annotations in the margins also—around the line number—as well as to the annotations referenced using the `\annotationref` command of the crossref mechanism (11 p. 64).

¹⁵ As for all \TeX macro with no argument.

- `\Xwraplinenumannotation`{*<cmd>*} for annotations in the margins only.
Note that `\Xwraplinenumannotation` without any optional argument will override this setting.
- `\Xwraplinenumannotationref`{*<cmd>*} for annotations referenced using the `\annotationref` command of the crossref mechanism (11 p. 64).
Note that `\Xwraplinenumannotation` without any optional argument will override this setting.
- `\Xendwraplinenumannotation`[*<s>*]{*<cmd>*} for critical endnotes, where *<s>* indicates the series of notes to which it applies, which may be a comma-separated list.

<cmd> is a command which can take one argument; the backslash is required though.

For example, if you do not wish to have annotations in the margins, but do want to have them in bold in the critical footnotes and endnotes, you say:¹⁶

```
\makeatletter
\Xwraplinenumannotation{\textbf}
\Xendwraplinenumannotation{\textbf}
\Xwraplinenumannotationside{\@gobble}
\makeatother
```

5.5.5 Not printing the second identical annotations

If you print only line number annotation, you may get in critical notes something like 6–6, because the starting and ending annotations are the same. You can avoid that using `\Xnoidenticallinenumannotation`[*<s>*], for critical footnotes or `\Xendnoidenticallinenumannotation`[*<s>*]

```
\Xnoidenticallinenumannotation
\Xendnoidenticallinenumannotation
```

5.5.6 Separator between annotations

If there are more than one annotation in the same line, they are separated by a comma. If you want to change the separator, you can use `\setlinenumannotationsep`{*<sep>*}

```
\setlinenumannotationsep
```

5.5.7 Annotations in the apparatus

Some other options for annotations in the apparatus are described in 7.4.10 p. 48

5.6 Executing code at each line

```
\dolinehook
\doinsidelinehook
```

`reledmac` provides an advanced feature for users. The argument passed to `\dolinehook`{*<arg>*} will be executed before slicing a new line in the paragraph. The argument passed to `\doinsidelinehook`{*<arg>*} will be executed before printing a new line, when the line

¹⁶The `\@gobble` command takes one argument, and returns nothing.

number has already been fixed. In many cases, the latter is more useful than the former. The file `examples/2-line_numbers_in_header.tex` provides an example for printing the first and last line numbers of a page in the header.

5.7 Executing code at a specific line

Sometime, you want to execute a code at a precise point in the flow of your text. For example, if the current header of the page corresponds to the position inside the text, you may want to use `\markboth` (or similar) command. The main problem is that you need to execute `\markboth` when `reledmac` typesets the text, and not when it reads it, because that could create damage with vertical spacing.

`\doinsidethislinehook`

The `\doinsidethislinehook{⟨code⟩}` macro allows `⟨code⟩` to be executed when the text is typeset. The `⟨code⟩` will be executed in the line equivalent to the position of `\doinsidethislinehook` in the flow of the text.

For example, with the following code:

```
\beginnumbering
\pstart
...
1.\doinsidelinehook{\markboth{1}{1}} a
\pend
```

`\markboth{1}{1}` will be executed at the line the 1. will be typeset. The `⟨code⟩` of `\doinsidethislinehook` will be executed only at the second run of `ℒTEX`.

See the file `examples/2-subdivision-number-in-header.tex` for an example. Especially, the use of this command with `ℒTEX` counters is quite complex, but the example show you how to deal with this problem.

6 Apparatus commands

6.1 Terminology

We call “critical notes” notes which refer to both a lemma, that is a part of text, and a line number. Critical notes are subdivided in critical footnotes and critical endnotes.

We call “familiar notes” notes which refer to a footnote mark in the main text.

`reledmac` manages many series of notes of each category. A series of notes is identified by an uppercase letter. When the series letter is at the *beginning* of a command name, it refers to a critical footnote. When the series letter is at the *end* of a command name, it refers to a familiar footnote.

So:

- `\Afootnote` is a critical footnote of the series A.
- `\Bendnote` is a critical endnote of the series B.
- `\footnoteC` is a familiar footnote of the series C.

6.2 Critical notes

6.2.1 The lemma

`\edtext` Within numbered paragraphs, all footnotes and endnotes are generated by the `\edtext` macro:

```
\edtext{⟨lemma⟩}{⟨commands⟩}
```

The `⟨lemma⟩` argument is the lemma in the main text: `\edtext` both prints this as part of the text, and makes it available to the `⟨commands⟩` you specify to generate notes.

For example:

```
I am happy:
I saw my friend \edtext{Smith}{
\Afootnote{Jones C, D.}}
on Tuesday.
```

1 I am happy: I saw my friend Smith on
2 Tuesday.

1 Smith] Jones C, D.

The lemma `Smith` is printed as part of this sentence in the text, and is also made available to the footnote that specifies a variant, `Jones C, D`. The footnote macro is supplied with the line number at which the lemma appears in the main text.

The `⟨lemma⟩` may contain further `\edtext` commands. Nesting makes it possible to print an explanatory note on a long passage together with notes on variants for individual words within the passage. For example:

```
I am happy: \edtext{I saw my friend
\edtext{Smith}{\Afootnote{Jones
C, D.}} on Tuesday.}{
\Bfootnote{The date was
July 16, 1954.}
}
```

1 I am happy: I saw my friend Smith on
2 Tuesday.

1 Smith] Jones C, D.

1-2 I saw my friend Smith on Tuesday.] The
date was July 16, 1954.

However, `\edtext` cannot handle overlapping but unnested notes—for example, one note covering lines 10–15, and another covering 12–18; an `\edtext` that starts in the `⟨lemma⟩` argument of another `\edtext` must end there, too. (The `\lemma` and `\linenum` commands may be used to generate overlapping notes if necessary.)

6.2.2 Footnotes

The second argument of the `\edtext` macro, `⟨commands⟩`, may contain a series of subsidiary commands that generate various kinds of notes.

`\Afootnote` Five separate series of footnotes are maintained; each macro takes one argument like `\Afootnote{⟨text⟩}`. When all of the five are used, the A notes appear in a layer just below the main text, followed by the rest in turn, down to the E notes at the bottom. These are the main macros that you will use to construct the critical apparatus of your text.

If you need more series of critical notes, please look at 6.7.1 p. 42.

An optional argument can be added before the text of the footnote. Its value is a comma-separated list of options. The available options are:

- `fulllines` to disable `\Xtwolines` and `\Xmorethantwolines` features for this note (cf. 7.4.5 p. 46).
- `nonum` disables line numbering for this note. A horizontal blank space is added instead. You can use `\Xinplaceofnumber` to set it (7.4.15 p. 49).
- `nosep` to disable the lemma separator for this note. A horizontal blank space is added instead. You can use `\Xinplaceoflemmaseparator` to set it (7.5.1 p. 51).
- `linangesep=<c>` to change to `<c>` the separator between start line and end line for this particular note.

Example: `\Afootnote[nonum]{<text>}`.

6.2.3 Endnotes

`\Aendnote` **Inserting endnotes** The package also maintains five separate series of endnotes.
`\Bendnote` If you do not need the endnotes facility, you should use `noend` option when loading
`\Cendnote` `reledmac`.
`\Dendnote` The mechanism is similar to the one for footnotes: each macro takes one or more
`\Eendnote` optional arguments and one single argument, like:
`\Aendnote[<option>]{<text>}`.

`<option>` can contain a comma-separated list of values. Allowed values are:

- `fulllines` to disable `\Xendtwolines` and `\Xendmorethantwolines` features for this particular note (cf. 7.4.5 p. 46).
- `nonum` to disable line number for this particular note.
- `nosep` to disable the lemma separator for this particular note. A horizontal blank space is added instead. You can use `\Xendinplaceoflemmaseparator` to set it (7.5.2 p. 51).
- `linangesep=<c>` to change to `<c>` the separator between start line and end line for this particular note.

`\doendnotes` **Printing endnotes** Normally, endnotes are not printed: you must use the `\doendnotes{<s>}`, where `<s>` is the letter of the series to be printed. Put this command where you want the corresponding set of endnotes printed. In this case, all the endnotes of the `<s>` series are printed, for all numbered sections.

`\doendnotesbysection` However, you may want to print the endnotes of one given series covering the first numbered section, then the endnotes of another given series covering the first numbered section, then the endnotes of the first given series covering the second numbered section, then the endnotes of the second given series covering the second numbered section, and so forth. In this case, use `\doendnotesbysection{<s>}`. For each value of `<s>`, the first call of the command will print the notes for the first series, the second call will print the notes for the second series etc. For example, do:

```
\section{Endnotes}
```

```

\subsection{First text}
\doendnotesbysection{A}
\doendnotesbysection{B}
\subsection{Second text}
\doendnotesbysection{A}
\doendnotesbysection{B}

```

Note that by default inside endnotes no separator is used between the lemma and the content. However you can use the `\Xendlemmaseparator` macro to define one (7.5.2 p. 51).

As endnotes may be printed at any point in the document they always start with the page number where they are called.

`\toendnotes`
`\Xtoendnotes`

Code between endnotes Sometimes, it is useful to insert content between endnotes of the same series: for example to separate endnotes of different sections of the same text. In this case, you could use *inside numbered text* the command:

`\toendnotes[⟨series⟩]{⟨content⟩}` where `⟨series⟩` is a comma-separated list of the series of endnotes where `⟨content⟩` must be inserted. If `⟨series⟩` is empty, then `⟨content⟩` is inserted to all the series.

For example:

```
\toendnotes{\section{Section's title}}
```

Alternatively, you can use `\Xtoendnotes{⟨content⟩}`, where “X” must be replaced by a series letter.

Remember that the endnotes are temporarily stored in an auxiliary file. That means in general you want to write the `⟨content⟩` in the auxiliary file *without expanding it*, that is without interpreting \TeX content.

However, in some cases, you may want to write a once-expanded¹⁷ version of the `⟨content⟩`, that is the version where the commands are expanded on the first level. This can be, for example, to get a counter value. Use the starred version in this case. For example:

```
\Atoendnotes*{\string\section{Letter 1 (chap. \thechapter)}}
```

6.2.4 Paragraph in critical apparatus

By default, no paragraph can be made in the notes of the critical apparatus. You can allow it by adding the options `parapparatus` when loading the package:

```
\usepackage[parapparatus]{eledmac}
```

Note that you *cannot* use paragraphs (e.g. blank lines or `\par`) inside of notes, when they are set to paragraph arrangement!

¹⁷The expansion mechanism of \TeX is a quite complex problem, but fundamental. We have no place to explain it fully here. Read introduction to \TeX to understand well.

6.2.5 Change lemma and line number

`\lemma` If you want to change the lemma that gets passed to the notes, you can do this by using `\lemma{⟨alternative⟩}` within the second argument to `\edtext` and before the note commands. The most common use of this command is to abbreviate the lemma that's printed in the notes. For example:

```
I am happy:
\edtext{I saw my friend
\edtext{Smith}{\Afootnote{Jones
C, D.}} on Tuesday.}
{\lemma{I \dots\ Tuesday.}
\Bfootnote{The date was
July 16, 1954.}
}
```

1 I am happy: I saw my friend Smith on
2 Tuesday.

1 Smith] Jones C, D.

1-2 I ... Tuesday.] The date was July 16, 1954.

`\linenum` You can use `\linenum{⟨arg⟩}` to change the line numbers passed to the notes. `⟨arg⟩` actually consist of seven parameters: the page, line, and sub-line number for the start of the lemma; the same three numbers for the end of the lemma; and the font specifier for the lemma. As the argument to `\linenum`, you specify those seven parameters in that order, separated by vertical bars (the `|` character). I.e.

```
\linenum{⟨start page⟩|⟨s. line⟩|⟨s. sub-l.⟩|⟨end p.⟩|⟨e. l.⟩|⟨e. sub-l.⟩|⟨font⟩|}
```

However, you can retain the value computed by `reledmac` for any number by simply omitting it; and you can omit a sequence of vertical bars at the end of the argument. For example, `\linenum{|||23}` changes only the ending page number of the current lemma.

This command does not change the marginal line numbers in any way; it just changes the numbers passed to the notes. Its use comes in situations that `\edtext` has trouble dealing with for whatever reason. If you need notes for overlapping passages that aren't nested, for instance, you can use `\lemma` and `\linenum` to generate such notes despite the limitations of `\edtext`. If the `⟨lemma⟩` argument to `\edtext` is extremely long, you may run out of memory; here again you can specify a note with an abbreviated lemma using `\lemma` and `\linenum`. The numbers used in `\linenum` need not be entered manually; you can use the "x-" symbolic cross-referencing commands below (11 p. 64) to compute them automatically.

Similarly, being able to manually change the lemma's font specifier in the notes might be important if you were using multiple scripts or languages. The form of the font specifier is three separate codes separated by `/` characters, giving the family, series, and shape codes as defined within NFSS.

6.2.6 Changing the names of commands for critical apparatus

The commands for generating the apparatus have been given rather bland names, because editors in different fields have widely divergent notions of what sort of notes are required, where they should be printed, and what they should be called. But this does not mean you have to type `\Afootnote` when you would rather type something you find more meaningful, like `\variant`.

We recommend that you create a series of such aliases and use them instead of the names chosen here; all you have to do is put commands of this form at the start of your

file.¹⁸

```
\newcommandx{\variant}[2][1,usedefault]{\Afootnote[#1]{#2}}
\newcommandx{\explanatory}[2][1,usedefault]{\Bfootnote[#1]{#2}}
\newcommand{\trivial}[1]{\Aendnote{#1}}
\newcommandx{\testimonia}[2][1,usedefault]{\Cfootnote[#1]{#2}}
```

6.3 Disambiguation of identical words in the apparatus

Sometimes, the same word occurs twice (or more) in the same line. `reledmac` provides tools to disambiguate references in the critical notes. The lemma will be followed by a reference number if a given word occurs more than once in the same line.

6.3.1 Basic use

`\sameword` To use this tool, you have to mark every occurrence of the potentially ambiguous term with the `\sameword` command:

```
Lupus \sameword{aut} canis \edtext{\sameword{aut}}{\Afootnote{et}} felix
```

In this example, `aut` will be followed, in the critical note, by the exponent 2 if it is printed in the same line as the first `aut`, but it will not if it is printed in a different line. The number is printed only after the second run.

6.3.2 Case setting

By default, `\sameword` is sensitive to the case. E.g. “foo” is considered as a different word to “Foo”.

You can use the `swcaseinsensitive` when loading the package to make `\sameword` insensitive to the case, i.e. to consider “foo” as identical “Foo”.

6.3.3 Notes about input encoding with UTF-8 processor

If you use UTF-8 processor, like \XeTeX or \LuaTeX , there should not be any glitches. However, pay attention to how characters are encoded. Similar-looking characters may be represented differently in unicode numbering.

For instance, in French, “é” has two possible Unicode codepoints:

- LATIN SMALL LETTER E (U+0065) + COMBINING ACUTE ACCENT (U+0301)
- LATIN SMALL LETTER E WITH ACUTE (U+00E9)

¹⁸We use `\newcommand` and `\newcommandx` instead of classical `\let` command because the `edtabular` environments have to modify the notes definition, and we need to use the newest definition of notes. Read the handbook of `xargs` to know more about `\newcommandx`.

Which unicode number you use depends, many times, on your keyboard configuration (the computer-input system).

Inside `reledmac`, the `\sameword` command considers these two unicodes (code positions) as different characters. If you use only one unicode number consistently, the distinction will probably make no difference to how your text looks, but `\sameword` will process the text inaccurately, based on the unicode numbers. To prevent this, do the following:

- If you use \XeTeX , add this line in your preamble: `\XeTeXinputnormalization 1`.
- If you use \LuaTeX , use the `uninormalize` package of Michal Hoftich¹⁹ with the `buffer` option set to true.

With these tools, \XeTeX / \LuaTeX will dynamically normalize unicode input when reading the file. Consequently, you will have no problems with the `\sameword` command.

6.3.4 Notes about right-to-left texts

Due to some internal limits of \XeTeX , `\sameword` does not work with right-to-left text with this engine.

If you need to use `\sameword` with right-to-left text, you must use \LuaTeX .

6.3.5 Use with `\lemma` command

If you use the `\lemma` command, `reledmac` cannot know to which occurrence of `\sameword` in the first argument of `\edtext` a word marked with `\sameword` in `\lemma` should refer.

For example, in the following example:

```
some thing
  \edtext{\sameword{sw}
           and other \sameword{sw}
           and again \sameword{sw}
           it is all}%
  {\lemma{\sameword{sw} \ldots all}\Afootnote{critical note}}.%
```

`reledmac` cannot know if the “sw” in `\lemma` refers to the word after “thing”, after “other”, or after “again”.

Consequently, you must tell `reledmac` to which instance of `\sameword` you are referring in the first argument of `\edtext`:

- In the content of `\lemma`, use `\sameword` with no optional argument.
- In the first argument of `\edtext`, use `\sameword` with the optional argument `[⟨X⟩]`. `⟨X⟩` is the depth of the `\edtext` where the `\lemma` is used. So if the `\lemma` is called in a `\edtext` inside another `\edtext`, `⟨X⟩` is equal to 2. If the

¹⁹<https://github.com/michal-h21/uninormalize>.

`\lemma` is called in a `\edtext` “of first level”, $\langle X \rangle$ is equal to 1. If the lemma is called in both 1 and 2 `\edtext` depth, $\langle X \rangle$ is 1,2. If that word is referenced in the lemma of every `\edtext` depth, $\langle X \rangle$ can also be set to `inlemma`.


Note that only words that are actually referenced in a `\lemma` need the optional argument. Therefore, the first `\sameword` in the example above should have “1” as its optional argument, to be referenced correctly in the lemma.

Note also that the $\langle X \rangle$ does not refer to the level where the `\sameword` occurs, but to the level of the `\lemma` that refers to that `\sameword`. For example:

```
\edtext{some \edtext{\sameword[1]{word}}{\Afootnote{om. M}}
    and other \sameword{word}
    and again a \sameword{word}
    it is all}%
}{\lemma{some \sameword{word} \ldots all}\Afootnote{critical note}}.%
```

Here the `\sameword` occurs in an `\edtext` of level 2, but since it is referenced by `\lemma` on level 1, it has “1” in the optional argument.

In the following example figure, each framed box represents an `\edtext` level. Each number is an occurrence of `\sameword`. After a framed box, the text in superscript represents the content of `\lemma` for that `\edtext` level. The text in subscript at the right of a number represents the content of the optional argument of `\sameword`.



The `\sameword` number 3 is called in a `\lemma` related to an `\edtext` of level 2. It must be marked by “2”.

The `\sameword` number 5 is called in a `\lemma` related to `\edtext` of level 1. It must be marked by “1”.

The `\sameword` number 1 is called in two `\lemmas`: one related to a `\edtext` of level 1, the other related to `\edtext` of level 2. It must be marked by “1,2”. However, as `\lemma` is called only in level 1 and 2, “1,2” could be replaced by “inlemma”.

The `\sameword` number 2 is in the first argument of a `\edtext` of level 3, but it has no `\lemma`-command, so there is no need to mark it.

Here, the corresponding code:

```

\edtext{%
  \edtext{%
    \sameword[inlemma]{A} (1)
    \edtext{%
      \sameword{A} (2)
    }%
  }%
  {%
    \Afootnote{level~3}%
  }%
  \sameword[2]{A} (3)
}%
{%
  1      A (1) A (2) A (3) A (4) A (5)
  \lemma{%
    \sameword{A}%
    \ldots%
    \sameword{A}%
    }%
    \Afootnote{level~2}%
  }%
  \sameword{A} (4)
  \sameword[1]{A} (5)
}%
{%
  \lemma{\sameword{A}\ldots\sameword{A}}%
  \Afootnote{level~1}%
}%
}

```

6.3.6 Sameword for a group of words

Sometimes a group of words and not only a single word, occurs multiple times. In this case, you have two possibilities.

First, you can consider only the individual words, and not groups of word. For example:

```

\sameword{per} \sameword{causam}
tamen scire
\edtext{\sameword{causam}}{\Bfootnote{fnote}}
est
\edtext{\sameword{per} \sameword{causam}}{\Bfootnote{causam rei B}}
cognoscere
\edtext{\sameword{causam}}{\Bfootnote{fnote}}

```

1 per causam tamen scire causam est per causam cognoscere causam

1 causam²] fnote

1 per² causam³] causam rei B

1 causam⁴] fnote

In this case it is clear which “per causam” is meant.

However, in the case that “per causam” is the lemma of the second note, there should be only one number for that whole lemma. In this case we can mark all “per causam” groups. But as “causam” is also called as lemma in note 1 and 3, we need to use nested `\sameword` commands. Consequently, we need to use `\lemma` for the `\edtext` linked to “per causam”, as we don’t want to number each individual word.

```
\sameword{per \sameword{causam}} tamen scire
\edtext{\sameword{causam}}{\Bfootnote{fnote}} est
\edtext{\sameword[1]{per \sameword{causam}}}{\lemma{\sameword{per causam}}\Bfootnote{causam}}
\edtext{\sameword{causam}}{\Bfootnote{fnote}}
```

1 per causam tamen scire causam est per causam cognoscere causam

```
1 causam2] fnote
1 per causam2] causam rei B
1 causam4] fnote
```

6.3.7 Customizing

`\showwordrank` You can redefine the `\showwordrank` macro to change the way the number is printed. The default value is

```
\newcommand{\showwordrank}[2]{%
  #1\textsuperscript{#2}%
}
```

6.3.8 Problems with some macros

`\swnoexpands` Macros inside `\sameword` that are not fully expandable, mainly macros which manipulate font features, write on full or have optional argument, may cause problems during compilation. Custom commands inside `\sameword` may therefore result in errors saying that “Use of `\sameword` doesn’t match its definition.” To solve this, include a redefinition of your custom commands in the `\swnoexpands` macro. In order to not include any content of a macro during comparison, identify the command with `\@gobble`. For example:

```
\makeatletter
\appto{\swnoexpands}{%
  \let\somemacro\@gobble%
}
\makeatother
```

This will drop the content of `\somemacro` during comparison.

To include the content of the first and only one argument of a custom command in `\sameword` comparison, use the `\@firstofone` command. For example, this is how `\emph` is handled:

```
\makeatletter
\appto{\swnoexpands}{%
  \let\emph\@firstofone%
}
\makeatother
```

To include command which can take optional argument, use `\RenewExpandableDocumentCommand` of `\xparse`. For example, this is how `\edindex` is handled:

```
\makeatletter
\appto{\swnoexpands}{%
  \RenewExpandableDocumentCommand{\edindex}{om}{}%
}
\makeatother
```

6.3.9 Automatic sameword annotation

All potentially ambiguous apparatus entries must be annotated manually. That annotation process is laborious and includes a risk of errors. *Samewords* is a Python script that can automate this step of the process. It can be installed via the *Python Package Index*, but see <https://github.com/stenskjær/samewords> for more info and documentation. The script is still at a beta stage, so comments and questions as well as error reports are very welcome at <https://github.com/stenskjær/samewords/issues>.

Please note that the maintainer of this script is not identical with the maintainer of *reledmac*.

6.4 Apparatus of manuscripts

The critical notes mostly refer to textual variants between manuscripts which contain the text to be edited. It may so happen that the manuscripts only contain parts of the text. Depending on one's wishes, *reledmac* can generate lists of relevant manuscripts for any delimited portion of text. Such lists are referred to as “apparatuses of manuscripts”.

To produce an apparatus of manuscripts with *reledmac*, you have to insert specific commands that are used to mark the sections for which only part of the manuscripts are relevant. These commands will be processed, and **after the second T_EX run**, corresponding apparatuses of manuscripts will be inserted in the first (viz. ‘A’ series) level of footnotes.

As the insertion of this apparatus can change the page breaks, you may have to run T_EX two or more times. We strongly recommend to use tools like *latexmk* to do that.

6.4.1 Marking sections of text

`\msdata` `\msdata{⟨text⟩}` must be inserted at the point where a section for which only part of the manuscripts are relevant starts. `⟨text⟩` can be any arbitrary text, viz. a list of the manuscripts that are used for the section that starts. The command must be attached right at the point where the section starts, with no space, like so:

```
\msdata{ABC}Lorem ipsum
```

Which means that the section of text starting by “Lorem ipsum” is witnessed by manuscripts A, B and C.

`\stopmsdata`

`\stopmsdata` must be inserted at the point where the section of text previously marked by `\msdata` ends. The command must be attached right to the end of the section, with no space. As `\stopmsdata` is a \LaTeX argumentless macro, it will gobble the following space. To keep that space, you have to either append a backslash followed by a space or `{}` to `\stopmsdata`, like so:

```
\msdata{ABC}Lorem ipsum dolor
[...]
amet\stopmsdata{} \msdata{ABCD}sic transit [...]
```

Which means that the part of text containing “Lorem ipsum dolor [...] amet” is witnessed by manuscripts A, B and C, while the part of text starting “sic transit” is witnessed by manuscripts A, B, C and D.

`\stopmsdata` is also automatically inserted by `\msdata`.

Note that in most cases, any `\stopmsdata` is followed by `\msdata`. However, as these two command are usually separated by a space, it may happen that a line break be automatically inserted between them. This is why it is advised to always insert `\stopmsdata`, even if `\msdata` inserts it in case it is forgotten.

6.4.2 Layout of the apparatus of manuscripts

On every page, the apparatus of manuscripts marks the corresponding section with starting and ending line numbers. However, the following rules will be applied:

- If the section does not start on the current page, the starting line number will be the line number of the first line on the page.
- If the section does not stop on the current page, the ending line number will be the line number of the last line on the page.
- If the section neither starts nor ends on the current page, no line number will be printed. The same is true in case both `\msdata` is called at the very beginning of the page and `\endmsdata` is called at the very end of the page.

6.4.3 Settings

As the apparatus of manuscripts technically consists of first-level critical notes (‘A’ series), any setting available for critical notes can be applied (7 p. 43). However, the following *additional* commands are available.

`\setmsdataseries`

The series used by default for the apparatus of manuscripts is series A. However, you can change it with `\setmsdataseries{<series>}`.

`\setmsdatalabel`

As the apparatus of manuscripts consists of regular critical footnotes, a lemma is associated to them. By default, it is “Ms.”. You can change it using `\setmsdatalabel{<txt>}`.

`\setmsdataposition`

If you want the manuscript apparatus to be on the same level of critical footnotes as the other apparatuses, for each line, reledmac will first insert the manuscript apparatus, then the other footnotes. You can change it using:

```
\msdataposition{regular-msdata}
```

And restore the default behavior using `\msdataposition{msdata-regular}`

6.5 Familiar notes

6.5.1 Basic use

`\footnoteA``\footnoteB``\footnoteC``\footnoteD``\footnoteE`

As well as the standard \LaTeX footnotes generated via `\footnote`, the package also provides five series of additional footnotes called `\footnoteA` through `\footnoteE`. These have the familiar marker in the text, and the marked text at the foot of the page can be formatted using any of the styles described for the critical footnotes. Note that the “regular” footnotes have the series letter at the end of the macro name whereas the critical footnotes have the series letter at the start of the name.

The footnote can take a first optional argument to manually define the footnote number or footnote symbol. For example:

```
\footnoteA[22]{This footnote will be numbered 22}
```

6.5.2 Customizing mark

`\thefootnoteA``\bodyfootmarkA``\footfootmarkA`

Each series uses a set of macros for styling the marks. The mark numbering scheme of series A is defined by the `\thefootnoteA` macro; the default is:

```
\renewcommand*{\thefootnoteA}{\arabic{footnoteA}}
```

The appearance of the mark in the text is controlled by `\bodyfootmarkA` which is defined as:

```
\newcommand*{\bodyfootmarkA}{%
```

```
\hbox{\textsuperscript{\normalfont\@nameuse{@thefnmarkA}}}}
```

The command `\footfootmarkA` controls the appearance of the mark at the start of the footnote text. It is defined as:

```
\newcommand*{\footfootmarkA}{\textsuperscript{\@nameuse{@thefnmarkA}}}
```

There are similar command triples for the other series.

6.5.3 Separator for multiple footnotes

The `footmisc` package [Fai03] by Robin Fairbairns has an option whereby sequential footnote marks in the text can be separated by commas^{3,4} like so. As a convenience reledmac provides this automatically.

`\multfootsep`

`\multfootsep` is used as the separator between footnote markers. Its default definition is:

```
\providecommand*{\multfootsep}{\textsuperscript{\normalfont,}}
```

and can be changed if necessary.

6.6 Printing the footnote mark without printing the footnote text

`\footnoteXmark` `\footnoteXtext` In certain cases, you can't directly use `\footnoteX`; for example, when using `\uline` command of the `ulem` package. You need to print the footnote mark first, then call the footnote text to be inserted.

For all $\langle X \rangle$ command, `reledmac` provides a `\footnote\langle X \rangle mark` command and a `\footnote\langle X \rangle text` command, equivalent to standard \TeX 's command `\footnotemark` and `\footnotetext`. For example, to use with `\uline`, do:

```
This is \uline{a test containing\mbox{\footnoteAmark}}\footnoteAtext{A
simple footnote.}\uline{ a simple footnote.}
```

If you use `reledpar`, you can't use these two commands to print the footnote mark on one side and the footnote text on the other side.

You must use `\footnote\langle X \rangle nomk` and `\footnote\langle X \rangle mk`, defined in `reledpar` (?? p. ??)

6.7 Changing series

6.7.1 Create a new series

If you need more than five series of critical footnotes, you can create extra series, using `\newseries` command. For example, to create F and G series `\newseries{G,H}`.

6.7.2 Delete series

As the number of series which are defined increases, `reledmac` gets slower. If you do not need all of the six standard series (A–E), you can load the package with the `series` option. For example, if you need only series A and B, use:

```
\usepackage[series={A,B}]{eledmac}
```

6.7.3 Series order

The default series order is the one called with the `series` option of the package, or, if this option is not used, A, B, C, D, E. Series order determines footnotes order.

`\seriesatbegin` `\seriesatend` However in some specific cases, you need to change the series order at some point inside the document. You can use `\seriesatbegin\langle s \rangle` to pull up a given series $\langle s \rangle$ to the beginning, or `\seriesatend\langle s \rangle` to push it down to the end.

6.8 Position of critical and familiar footnotes

`\fnpos` `\mpfnpos` There is a historical incoherence in $(\text{r})(\text{e})\text{ledmac}$. The familiar footnotes are before the critical footnotes in a normal page, but after in a minipage or in a ledgroup. However, it is possible to change the relative position of both types of footnotes. If you want to have familiar footnotes after critical footnotes in a normal page, use:

```
\fnpos{critical-familiar}
```

Or, if you want a minipage or ledgroup to have critical footnotes after familiar footnotes, use:

```
\mpfnpos{familiar-critical}
```

You can also decide to alternate familiar and critical footnotes with your own order. In this case, the second argument of `\fnpos` or `\mpfnpos` is a comma-separated list of values. Each value has the following form:

$\langle series \rangle \langle type \rangle$

$\langle series \rangle$ is a series letter (A,B,C etc.), while $\langle type \rangle$ must be either “critical” or “familiar”.

For example, suppose you want to first print the familiar footnotes of the “A” series, then all the series of critical footnotes, and finally all the series of familiar footnotes, except the “A” series. In this case, use the following command:

```
\fnpos{%
  {A}{familiar},
  {A}{critical},%
  {B}{critical},%
  {C}{critical},%
  {D}{critical},%
  {E}{critical},%
  {B}{familiar},%
  {C}{familiar},%
  {D}{familiar},%
  {E}{familiar}%
}
```

Note that you must define the position of all the series of footnotes you use. If you don’t, you will have infinite runs of \LaTeX .

7 Apparatus customization

7.1 Introduction

7.2 Introduction

Some commands can be used to change the way the footnotes are displayed.²⁰ All can have an optional argument $[\langle s \rangle]$, which is the letter of the series — or a list of letters separated by comma — depending on which option is applied. If the optional argument is omitted or empty, the setting will apply to the entire series.

When a length, noted $\langle l \rangle$, is used, it can be stretchable: a plus b minus c . The final length m is calculated by \LaTeX to have: $a - c \leq m \leq a + b$. If you use some relative

²⁰In the code of `reledmac`, these commands are called “hooks”.

unit²¹, it will be relative to font size of the footnote, except for commands concerning the place kept by the notes — including blank space.

Some commands are boolean, indicating when an option is enabled. If you want to disable the option after enabling it, you must use `[false]` as the second optional argument. For example:

- `\XX[A][false]` to disable the “XX” option for the series A.
- `\XX[] [false]` to disable it for all series.

There is also name convention:

- Names prefixed by X are for setting of critical footnotes.
- Names prefixed by Xend are for setting of critical endnotes.
- Names suffixed by X are for setting of familiar footnotes.

7.3 Notes arrangement in a series

`\Xarrangement`
`\arrangementX`

By default, all footnotes are formatted as a series of separate paragraphs in one column. Three other formats are also available for notes.

Use `\Xarrangement[⟨s⟩]{⟨a⟩}` to change the arrangement of the $\langle s \rangle$ series of critical footnotes and `\arrangementX[⟨s⟩]{⟨a⟩}` to change the arrangement of the $\langle s \rangle$ series of familiar footnotes.

The value of $\langle a \rangle$ can be one of the following:

- `paragraph` formats all of the footnotes of a series as a single paragraph; if you use this arrangement, you are strongly encouraged to read 19.1.6 p. 80.
- `twocol` formats them as separate paragraphs, but in two columns;
- `threecol`, in three columns.
- `normal`, restore normal arrangement.

You should set up the page layout parameters, and in particular the `\baselineskip` of the footnotes, before you call this macro because its action depends on these; too much or too little space will be allotted for the notes on the page if these macros use the wrong values.

Note that you *cannot* use paragraphs (e.g. blank lines or `\par`) or line breaks (`\break` or `\linebreak` or `\newline` etc.) inside of notes, when they are set to `paragraph` arrangement!

The notes arrangement must be called after having defined the document geometry setting. If you must change geometry setting inside your document, do not forget to call note arrangement again.

`\hsize` has been set for the pages that use this series of notes; otherwise T_EX will try to put too many or too few of these notes on each page. If you need to change the `\hsize` within the document, call the arrangement macro again afterwards to take account of the new value.

²¹Like `em` which is the width of an “m” in a given font.

7.4 Control number printing

7.4.1 Print line number only at first time

`\Xnumberonlyfirstinline`

By default, the line number is printed inside every note. If you want to print it only the first time for a given line number (i.e., once for line 1, once for line 2, etc.), you can use `\Xnumberonlyfirstinline[⟨s⟩]`.

`\numberonlyfirstintwolines`

Suppose you have a lemma on line 2 and a lemma between line 2 and line 3. With `\Xnumberonlyfirstinline`, the second lemma is considered to be on the same line as the first lemma. But if you use both `\Xnumberonlyfirstinline[⟨s⟩]` and `\Xnumberonlyfirstintwolines[⟨s⟩]`, a distinction is made.

`\Xsymlinenum`

For setting a particular symbol in place of the line number, you can use `\Xsymlinenum[⟨s⟩]{⟨symbol⟩}` in combination with `\Xnumberonlyfirstinline[⟨s⟩]`. From the second lemma of the same line, the symbol will be used instead of the line number. Note that any command called in `⟨symbol⟩` must be robust. Use `\robustify` to robustify a non-robust command.

`\Xendnumberonlyfirstinline`

`\numberonlyfirstintwolines`

`\Xendsymlinenum`

For endnotes, `\Xendnumberonlyfirstinline`; `\Xendnumberonlyfirstintwolines` and `\Xendsymlinenum` are the equivalents of `\Xnumberonlyfirstinline`; `\Xnumberonlyfirstintwolines` and `\Xsymlinenum`.

7.4.2 Print page number only at first time

`\Xendpagenumberonlyfirst`

For endnotes, `reledmac` provides a mechanism for printing the page number only the first time it is seen. However, when a lemma spans over two pages, the line numbers are normally printed in the following pattern: starting page number - starting line number - ending page number - ending line number. It follows that what corresponds to the actual “page number” may not be self-evident. So: `\Xendpagenumberonlyfirst[⟨s⟩]` can be called to ensure that the starting page number of a lemma be not printed if it is the same as the ending page number of the preceding lemma. You can use *additionally* one (and only one) of the following commands:

- `\Xendpagenumberonlyfirstifsingle[⟨s⟩]`: the first page number of the lemma will not be printed only if the following conditions are true:
 1. The starting page number of the lemma is the same as the ending page number of the preceding lemma.
 2. The ending page number of the lemma is the same as the starting page number of the lemma.

In this case the ending page number will always be printed if it is different from the starting page number.

- `\Xendpagenumberonlyfirstintwo[⟨s⟩]`: both the starting page number and the ending page number of a lemma are not printed if they are both the same as the starting page number and the ending page number of the preceding lemma respectively.

In any case, you can use:

<code>\Xendsympagenum</code>	• <code>\Xendsympagenum[⟨series⟩]{⟨c⟩}</code> to print <code>⟨c⟩</code> when the page number is not printed.
<code>\Xendinplaceofpagenumber</code>	• <code>\Xendinplaceofpagenumber[⟨series⟩]{⟨l⟩}</code> to print a <code>⟨l⟩</code> length horizontal space in case no symbol is printed instead of the page number.

7.4.3 Arbitrary text before line number

<code>\Xtxtbeforenumber</code>	For critical notes <code>\Xtxtbeforenumber[⟨s⟩]{⟨txt⟩}</code> allows the insertion of <code>⟨txt⟩</code> before the line number only when the line number is printed, so taking into account <code>\Xnumberonlyfirstinline</code> and the like.
<code>\Xendbeforepagenumber</code>	For endnotes <code>\Xendbeforepagenumber[⟨s⟩]{⟨text⟩}</code> defines the text before the page number in endnotes. Default value is p. (“p” followed by a dot).
<code>\Xendafterpagenumber</code>	<code>\Xendafterpagenumber[⟨s⟩]{⟨text⟩}</code> defines the text after the page number in endnotes. Default value is) (open parenthesis followed by a single space).
<code>\Xendlineprefixsingle</code>	<code>\Xendlineprefixsingle[⟨s⟩]</code> defines the text before the line number in endnotes when there is only one line. Default value is empty.
<code>\Xendlineprefixmore</code>	<code>\Xendlineprefixmore[⟨s⟩]{⟨text⟩}</code> defines the text before the line number in endnotes when there is more than one line. Default value is empty. If you don’t define it, it will use the value defined by <code>\Xendlineprefixsingle</code> .

7.4.4 Separator for line range

<code>\Xlinerangeseparator</code>	By default, the separator between the begin line and the end line in a lines’ range is an en-dash in a normal font (<code>\textnormal{--}</code>). You can change it for critical footnotes with <code>\Xlinerangeseparator[⟨s⟩]{⟨text⟩}</code> , and with <code>\Xendlinerangeseparator[⟨s⟩]{⟨text⟩}</code> for critical endnotes.
<code>\Xendlinerangeseparator</code>	

7.4.5 Abbreviate line range

<code>\Xtwolines</code>	If a lemma is printed on two subsequent lines, <code>reledmac</code> will print the first and the last line numbers. Instead of this, it is also possible to print an abbreviation which stands for “line 1 and subsequent line(s)”. To achieve this, use <code>\Xtwolines[⟨s⟩]{⟨text⟩}</code> and <code>\Xmorethantwolines[⟨s⟩]{⟨text⟩}</code> . The <code>⟨text⟩</code> argument of <code>\Xtwolines</code> will be printed if the lemma is on two lines, and the <code>⟨text⟩</code> argument of <code>\Xmorethantwolines</code> will be printed if the lemma is on three or more lines. For example:
<code>\Xmorethantwolines</code>	
<pre>\Xtwolines{sq.} \Xmorethantwolines{sqq.}</pre>	

will print “1sq.” for a lemma which falls on lines 1–2 and “1sqq.” for a lemma which falls on lines 1–4.

If you use `\Xtwolines` without setting `\Xmorethantwolines`, the `⟨text⟩` argument of `\Xtwolines` will be used for lemmas which fall on three or more lines.

However, if you want to use a short form (when the lemma overlaps two lines, but not more than two), use `\Xtwolinesbutnotmore[⟨series⟩]`.

When you use lineation by page, the final page number, if different from the initial page number, will not be printed, because the final page number is included in the `\Xendtwolines` symbol.

`\Xtwolinesonlyinsamepage` However, you can force print the final page number with `\Xtwolinesonlyinsamepage[⟨series⟩]`.

You can disable `\Xtwolines` and related for a specific note by using the “[fulllines]” argument in the note macro cf. 6.2.2 p. 30.

`\Xendtwolines` For endnotes, use these macros: `\Xendtwolines`; `\Xendmoreethantwolines`;
`\Xendmoreethantwolines` `\Xendtwolinesbutnotmore`;
`\Xendtwolinesbutnotmore` `\Xendtwolinesonlyinsamepage` instead of `\Xtwolines`; `\Xmoreethantwolines`;
`\Xtwolinesbutnotmore`; `\Xtwolinesonlyinsamepage`.

7.4.6 Disabling line number printing

`\Xnonumber` You can use `\Xnonumber[⟨s⟩]` if you do not want to have no line/page/pstart number in the footnotes, nor line number annotation.
`\Xendnonumber` `\Xendnonumber[⟨s⟩]` is the same for endnotes.

7.4.7 Printing pstart number

`\Xpstart` You can use `\Xpstart[⟨s⟩]` if you want to print the pstart number in the footnote, before the line and subline number. Note that when you change the lineation system, the option is automatically switched:

- If you use lineation by pstart, the option is enabled.
- If you use lineation by section or by page, the option is disabled.

`\Xpstarteverytime` By default, the pstart number is printed only in the part of text where you have called `\numberpstarttrue`. We don’t know why you would like to print the pstart number in the notes and not in the main text. However, if you want to do it, you can call `\Xpstarteverytime[⟨s⟩]`. In this case, the pstart number will be printed every time in footnote.

`\Xonlypstart` In combination with `\Xpstart`, you can use `\Xonlypstart[⟨s⟩]` if you want to print only the pstart number in the footnote, and not the line and subline number.

`Xpstartonlyfirst` You can use `Xpstartonlyfirst[⟨s⟩]` to print the pstart number only the first time it appears in the apparatus. When using `\Xpstart`, you can use `\Xpstartseparator[⟨s⟩]{⟨text⟩}` to print `⟨text⟩` after the pstart number. Default value is empty.
`\Xpstartseparator`

7.4.8 Printing stanza number

`\Xstanza` You can use `\Xstanza[⟨s⟩]` if you want to print the stanza number in the footnote, before the line and subline number.

Of course the stanza number is printed only when you use `\numberstanza`

`\Xstanzaseparator` When using `\Xstanza`, you can use `\Xstanzaseparator[⟨s⟩]{⟨text⟩}` to print `⟨text⟩` after the stanza number. Default value is empty.

`Xstanzaonlyfirst` You can use `Xstanzaonlyfirst[⟨s⟩]` to print the stanza number only the first time it appears in the apparatus.

7.4.9 Disabling line number printing

Sometime, we want to print only the stanza or pstart number, but not the line number.

`\Xnolinenumber`
`\Xendnolinenumber`

The `\Xnolinenumber[⟨s⟩]` macro disables line number printing for critical footnotes.

The `\Xendnolinenumber` macro does the same for endnotes.

Note that contrary to `\Xnonumber` and `\Xnoendnum`, the page/pstartannotation will be printed, if required.

7.4.10 Options for line number annotations

`\Xlinenumannotationonlyfirst`

By default, the line number annotation (5.5 p. 25) is printed in every note. If you want to print it only the first time for a given annotation you can use `\Xlinenumannotationonlyfirst[⟨s⟩]`.

Note the two following points:

- If you use the `noresetlinenumannotation` option of `reledmac`, the `\Xlinenumannotationonlyfirst` won't take account of the official line number.
- The `\Xlinenumannotationonlyfirst` works for consecutive lemmas with the same annotation. That is, if you have for example a lemma with an A annotation, then a lemma with a B annotation, then a lemma with an A annotation, each lemma will have its own annotation in the apparatus.

`\Xlinenumannotationonlyfirstintwo`

Suppose you have a lemma on annotation 1 and a lemma between annotation 1 and annotation 3. With `\Xlinenumannotationonlyfirst`, the second lemma is considered to have the same annotation as the first lemma. But if you use both `\Xlinenumannotationonlyfirst[⟨s⟩]` and `\Xlinenumannotationonlyfirstintwo[⟨s⟩]`, a distinction is made.

`\Xsymlinenumannotation`

To use a particular symbol in place of the line number annotation, you can use `\Xsymlinenumannotation[⟨s⟩]{⟨symbol⟩}` in combination with `\Xlinenumannotationonlyfirst[⟨s⟩]`. From the second lemma with the same line number annotation, the symbol will be used instead of the annotation. Note that any command called in `⟨symbol⟩` must be robust. Use `\robustify` to robustify a non-robust command.

`\Xendlinenumannotationonlyfirst`

`\Xendlinenumannotationonlyfirstintwo`

`\Xendsymlinenumannotation`

`\Xnolinenumberifannotation`

`\Xendnolinenumberifannotation`

For endnotes, `\Xendlinenumannotationonlyfirst`; `\Xendlinenumannotationonlyfirstintwo` and `\Xendsymlinenumannotation` are the equivalents of

`\Xlinenumannotationonlyfirst`; `\Xlinenumannotationonlyfirstintwo` and `\Xsymlinenumannotation`. The `\Xnolinenumberifannotation` disable line number printing only for critical notes when there are some annotations to the line number.

The `\Xendnolinenumberifannotation` is the same for endnotes.

7.4.11 Separator between line and subline numbers

`\Xsublinesep`

`\Xsublinesep[⟨s⟩]{⟨txt⟩}` changes the separator between line and subline in footnotes.

Employed without optional argument, it also changes the separator in side numbering.

`\Xendsublinesep`

`\Xendsublinesep[⟨s⟩]{⟨txt⟩}` does the same thing for endnotes.

However, it does not change anything for the separator in side numbering. Use `\Xsublinesep` without optional argument or `\Xsublinesepside{<txt>}` to do it.

The default value is `\textnormal{.}`.

7.4.12 Separator between page and line numbers

`\Xpagelinesep` `\Xpagelinesep[<s>]{<txt>}` changes the separator between the page and line number in footnotes.

By default, the value defined for `\Xsublinesep` is used.

7.4.13 Space around number

`\Xbeforenumber` With `\Xbeforenumber[<s>]{<l>}`, you can add some space before the line number in a footnote. If the line number is not printed, the space is not either. The default value is 0 pt.

`\Xafternumber` With `\Xafternumber[<s>]{<l>}` you can add some space after the line number in a footnote. If the line number is not printed, neither is the space. The default value is 0.5 em.

`\Xendbeforenumber` `\Xendafternumber` and `\Xendbeforenumber` and `\Xendafternumber` are the equivalents of `\Xbeforenumber` and `\Xafternumber` for endnotes.

`\Xnonbreakableafternumber` By default, the space defined by `\Xafternumber` is breakable. With `\Xnonbreakableafternumber[<s>]` it becomes nonbreakable.

7.4.14 Space around line symbol

`\Xbeforesymmlinenum` With `\Xbeforesymmlinenum[<s>]{<l>}` you can add some space before the line symbol in a footnote. The default value is value set by `\Xbeforenumber`.

`\Xaftersymmlinenum` With `\Xaftersymmlinenum[<s>]{<l>}` you can add some space after the line symbol in a footnote. The default value is value set by `\Xafternumber`.

`\Xendbeforesymmlinenum` `\Xendaftersymmlinenum` and `\Xendbeforesymmlinenum` and `\Xendaftersymmlinenum` are the equivalents of `\Xbeforesymmlinenum` and `\Xaftersymmlinenum` for the endnotes.

7.4.15 Space in place of number

`\Xinplaceofnumber` If no number or symbolic line number is printed, you can add a space, with `\Xinplaceofnumber[<s>]{<l>}`. The default value is 1 em.

`\Xendinplaceofnumber` `\Xendinplaceofnumber[<s>]{<l>}` is the same, for critical endnotes.

7.4.16 Boxing line number and line symbol

`\Xboxlinenum` It could be useful to put the line number inside a fixed box: the content of the note will be printed after this box. You can use `\Xboxlinenum[<s>]{<l>}` to do that. To subsequently disable this feature, use `\Xboxlinenum` with length equal to 0 pt. One use of this feature is to print line number in a column, and the note in an other column:

```
\Xhangindent{1em}
\Xafternumber{0em}
```

`\Xboxlinenum{1em}`

`\Xboxsymlinenum` `\Xboxsymlinenum[⟨s⟩]{⟨l⟩}` is the same as `\Xboxlinenum` but for the line number symbol.

`\Xendboxsymlinenum` `\Xendboxsymlinenum[⟨s⟩]{⟨l⟩}` is the same as `\Xboxsymlinenum` but for endnotes.

`\Xboxlinenumalign` If you put line number in box, it will be aligned left inside the box. However, you can change it using `\Xboxlinenumalign[⟨s⟩]{⟨text⟩}` where `⟨text⟩` can be the following:

L to align left (default value);

R to align right;

C to center.

When using `\Xboxlinenum`, `reledmac` put all the line number description in the same box. That is, the same box will contain: the start line number, the dash, and either the end line number or the range symbol (like `ff.`). However, it is possible to box them in two different boxes.

- `\Xboxstartlinenum[⟨s⟩]{⟨l⟩}` will box the start line number in a box of length `⟨l⟩`. The content will be put at the right of the box.
- `\Xboxendlinenum[⟨s⟩]{⟨l⟩}` will box the dash plus the end line number or the range symbol in a box of length `⟨l⟩`. The content will be put at the left of the box.

With these two commands, it is possible to horizontally align the dash of line number when using critical notes, to obtain something like:

```
1
12-23
24ff.
```

`\Xendboxlinenum` `\Xendboxlinenum[⟨s⟩]{⟨l⟩}`, `\Xendboxlinenumalign[⟨s⟩]{⟨text⟩}`, `\Xendboxstartlinenum[⟨s⟩]{⟨l⟩}`
`\Xendboxlinenumalign` `\Xendboxendlinenum[⟨s⟩]{⟨l⟩}` are the same as, respectively, `\Xboxlinenum` and
`\Xendboxstartlinenumalign` `\Xboxlinenumalign`, `\Xboxstartlinenum`, `\Xboxendlinenum` except in endnotes.
`\Xendboxendlinenumalign`

7.5 Separator between the lemma and the note

7.5.1 For footnotes

`\Xlemmaseparator` By default, in a footnote, the separator between the lemma and the note is a right bracket (`\rbracket`)²². You can use `\Xlemmaseparator[⟨s⟩]{⟨Xlemmaseparator⟩}` to change it. The optional argument can be used to specify the series in which it is used. Note that there is a non-breakable space between the lemma and the separator, but a **breakable** space between the separator and the following text.

`\Xbeforelemmaseparator` Using `\Xbeforelemmaseparator[⟨s⟩]{⟨l⟩}` you can add some space between

²²For `polyglossia`, when the lemma is RTL, the bracket automatically switches to a left bracket.

lemma and separator. If your lemma separator is empty, this space won't be printed. The default value is 0 em.

`\Xafterlemmaseparator`

Using `\Xafterlemmaseparator[⟨s⟩]{⟨l⟩}` you can add some space between separator and note. If your lemma separator is empty, this space will not be printed. The default value is 0.5 em.

`\Xnolemmaseparator`

You can suppress the lemma separator, using `\Xnolemmaseparator[⟨s⟩]`, which is simply a alias of `\Xlemmaseparator[⟨s⟩]{}`.

`\Xinplaceoflemmaseparator`

With `\Xinplaceoflemmaseparator[⟨s⟩]{⟨l⟩}` you can add a space if no lemma separator is printed. The default value is 1 em.

7.5.2 For endnotes

`\Xendlemmaseparator`

By default, there is no separator inside endnotes between the lemma and the content of the note. You can use `\Xendlemmaseparator[⟨s⟩]{⟨Xendlemmaseparator⟩}` to change this. The optional argument can be used to specify the series in which it is used. A common value of `⟨Xendlemmaseparator⟩` is `\rbracket`.

Note that there is a non-breakable space between the lemma and the separator, but a **breakable** space between the separator and the following text.

`\Xendbeforelemmaseparator`

Using `\Xendbeforelemmaseparator[⟨s⟩]{⟨l⟩}` you can add some space between the lemma and the separator. If your lemma separator is empty, this space won't be printed. The default value is 0 em.

`\Xendafterlemmaseparator`

Using `\Xendafterlemmaseparator[⟨s⟩]{⟨l⟩}` you can add some space between the separator and the content of the note. If your lemma separator is empty, this space won't be printed. The default value is 0.5 em.

`\Xinplaceoflemmaseparator`

With `\Xinplaceoflemmaseparator[⟨s⟩]{⟨l⟩}` you can add some space if you choose to remove the lemma separator. The default value is 0.5 em.

7.6 Font style

7.6.1 For line number

`\Xnotenumfont`

`\Xnotenumfont[⟨s⟩]{⟨command⟩}` is used to change the font style for line numbers in critical footnotes ; `⟨command⟩` must be one (or more) switching command, like `\bfseries`.

`\Xendnotenumfont`

`\Xendnotenumfont[⟨s⟩]{⟨command⟩}` is used to change the font style for line numbers in critical footnotes. `⟨command⟩` must be one (or more) switching command, like `\bfseries`.

`\notenumfontX`

`\notenumfontX[⟨s⟩]{⟨command⟩}` is used to change the font style for note numbers in familiar footnotes. `⟨command⟩` must be one (or more) switching command, like `\bfseries`.

7.6.2 For the lemma

`\lemmadisablefontselection`

By default, font of the lemma in footnote is the same as font of the lemma in the main text. For example, if the lemma is in italic in the main text, it is also in italic in note. The `\Xlemmadisablefontselection[⟨s⟩]` command allows to disable it for a specific series.

`\Xendlemmadisablefontselection`

By default, font of the lemma in endnote is the same as font of the lemma in the main text. For example, if the lemma is in italic in the main text, it is also in italic in note. The command allows `\Xendlemmadisablefontselection[⟨s⟩]` to disable it for a specific series.

`\Xlemmafont`
`\Xendlemmafont`

Use `\Xlemmafont[⟨s⟩]{⟨cmd⟩}` to apply a \TeX font command to the lemma. For example, to have boldface lemma:

`\Xlemmafont{\bfseries}`

`\Xendlemmafont[⟨s⟩]{⟨cmd⟩}` is the same for endnotes.

7.6.3 For all notes

`\Xnotefontsize`

`\Xnotefontsize[⟨s⟩]{⟨command⟩}` is used to define the font size of critical footnotes of the series. The default value is `\footnotesize`. The `⟨command⟩` must not be a size in pt, but a standard \LaTeX size, like `\small`.

`\notefontsizeX`

`\notefontsizeX[⟨s⟩]{⟨command⟩}` is used to define the font size of familiar footnotes of the series. The default value is `\footnotesize`. The `⟨command⟩` must not be a size in pt, but a standard \LaTeX size, like `\small`.

`\Xendnotefontsize`

`\Xendnotefontsize[⟨s⟩]{⟨l⟩}` is used to define the font size of end critical footnotes of the series. The default value is `\footnotesize`. The `⟨command⟩` must not be a size in pt, but a standard \LaTeX size, like `\small`.

7.7 Wrapping notes

7.7.1 Wrapping lemmas

`\Xwraplemma`

`\Xwraplemma[⟨s⟩]{⟨cmd⟩}` is used to wrap, in the footnote, the lemma in a \LaTeX command. For example, with the `bidir` package, to ensure having a lemma written right to left, use `\Xwraplemma{\RL}`.

`\Xwrapendlemma`

`\Xendwraplemma[⟨s⟩]{⟨cmd⟩}` is the same for endnotes.

7.7.2 Wrapping contents

`\Xwrapcontent`

`\Xwrapcontent[⟨s⟩]{⟨cmd⟩}` is used to wrap the footnote contents — excluding the lemma — in a \LaTeX command.

For example, if the language of your note is not the same as the language of the lemma, use `\Xwrapcontent{\foreignlanguage{⟨language⟩}}` (with `babel`) or `\Xwrapcontent{\text{⟨language⟩}}` (for `babel`).

`\Xendwrapcontent`

`\Xendwrapcontent[⟨s⟩]{⟨cmd⟩}` is the same for endnotes.

`\wrapcontentX`

`\wrapcontentX[⟨s⟩]{⟨cmd⟩}` is the same for familiar footnotes.

7.8 Indent of notes content

`\Xparindent`

By default, `reledmac` does not add indentation before the paragraphs inside critical footnotes. Use `\Xparindent[⟨s⟩]` to enable indentation.

`\parindentX`

By default, `reledmac` does not add indentation before the paragraphs inside familiar

footnotes. Use `\parindentX[⟨s⟩]` to enable indentation.

`\Xhangindent` For critical notes NOT paragraphed you can define an indent with `\Xhangindent[⟨s⟩]{⟨l⟩}`, which will be applied in the second line of notes. It can help to make distinction between a new note and a break in a note. The default value is 0 pt.

`\hangindentX` For familiar notes NOT paragraphed you can define an indentation with `\hangindentX[⟨s⟩]{⟨l⟩}`, which will be applied in the second line of notes. It can help to make a distinction between a new note and a break in a note.

`\Xendhangindent` For critical endnotes NOT paragraphed you can define an indentation with `\Xendhangindent[⟨s⟩]{⟨l⟩}`, which will be applied in the second line of notes. It can help to make a distinction between a new note and a break in a note.

7.9 Arbitrary code

7.9.1 Arbitrary code around line number

`\Xendbhooklinenumber` `\Xendbhooklinenumber[⟨s⟩]{⟨code⟩}` is used to execute code before line numbers in endnotes. The code is executed before the `\Xendbeforelinenumber` space and before the `\Xendnotenumfont` font setting.

`\Xendahooklinenumber` `\Xendahooklinenumber[⟨s⟩]{⟨code⟩}` is used to execute code after line number in endnotes. The code is executed after the `\Xendafternumber` space.

`\Xendbhookinplaceofnumber` `\Xendbhookinplaceofnumber[⟨s⟩]{⟨code⟩}` is used to execute code before a space or symbol which replaces line number in endnotes. The code is executed before the `\Xendbeforesymmlinenum` space and before the `\Xendnotenumfont` font setting.

`\Xendahookinplaceofnumber` `\Xendahookinplaceofnumber[⟨s⟩]{⟨code⟩}` is used to execute code after a space or symbol which replaces line number in endnotes. The code is executed after the `\Xendaftersymmlinenum` space.

7.9.2 Arbitrary code at the beginning of notes

The three next commands add arbitrary code at the beginning of notes. As the name's space is local to the notes, you can use it to redefine some style inside the notes. For example, if you don't want the `pstart` number to be in bold, use:

```
\Xbhooknote{\renewcommand{\thepstart}{\arabic{pstart}.}}
```

`\Xbhooknote` `\Xbhooknote[⟨s⟩]{⟨code⟩}` is to be used at the beginning of each critical footnote.
`\bhooknoteX` `\bhooknoteX[⟨s⟩]{⟨code⟩}` is to be used at the beginning of each familiar footnote.
`\Xendbhooknote` `\Xendbhooknote[⟨s⟩]{⟨code⟩}` is to be used at the beginning of each endnote.

7.9.3 Arbitrary code before inserting note

`\Xbeforeinserting` `\Xbeforeinserting[⟨s⟩]{⟨code⟩}` and `\beforeinsertingX[⟨s⟩]{⟨code⟩}` are very technical commands.

They allow one to add any arbitrary code just before the footnotes are added in the list of footnotes. The main use is to insert text direction code. For example, if you edit right-to-left text with `bidl`, but want your critical footnote be left-to-right, use

`\Xbeforeinserting\LTR`. You should also use `\Xwraplemma` to ensure your lemmas are right-to-left in a left-to-right paragraph (7.7.1 p. 52).

Note that the changes are local to the footnote.

7.10 Options for footnotes in columns

7.10.1 Alignment

`\Xcolalign` By default, text in footnotes of two or three columns are flush left and without hyphenation. However, you can change this with `\Xcolalign[⟨s⟩]{⟨code⟩}` for critical footnotes, and `\colalignX[⟨s⟩]{⟨code⟩}` for familiar footnotes.

`<code>` must be one of the following command:

`\justifying` to have text justified, as usual with \TeX . You can also let `<code>` empty.

`\raggedright` to have text left aligned, but *without hyphenation*. That is the default `reledmac` setting.

`\RaggedRight` to have text left aligned *with hyphenation* (requires `ragged2e`).

`\raggedleft` to have text right aligned, but *without hyphenation*.

`\RaggedLeft` to have text right aligned *with hyphenation* (requires `ragged2e`).

`\centering` to have text centered, but *without hyphenation*.

`\Centering` to have text centered *with hyphenation* (requires `ragged2e`).

7.10.2 Size of the columns

For the following four macros, be careful that the columns are made from right to left.

`\Xhsizetwocol` `\Xhsizetwocol[⟨s⟩]{⟨l⟩}` is used to change width of a column when critical notes are displaying in two columns. Default value is `.45 \hspace`.

`\Xhsizethreecol` `\Xhsizethreecol[⟨s⟩]{⟨l⟩}` is used to change width of a column when critical notes are displaying in three columns. Default value is `.3 \hspace`.

`\hsizetwocolX` `\hsizetwocolX[⟨s⟩]{⟨l⟩}` is used to change width of a column when familiar notes are displaying in two columns. Default value is `.45 \hspace`.

`\hsizethreecolX` `\hsizethreecolX[⟨s⟩]{⟨l⟩}` is used to change width of a column when familiar notes are displaying in three columns. Default value is `.3 \hspace`.

7.11 Options for paragraphed footnotes and notes grouped by line

7.11.1 Mark separation of notes

`\Xafternote` You can add some horizontal space after a note by using `\Xafternote[⟨s⟩]{⟨l⟩}` (for critical footnotes) or `\afternoteX[⟨s⟩]{⟨l⟩}` (for familiar footnotes). The default value is `1em plus.4em minus.4em`.

`\Xparafootsep` For paragraphed footnotes (see below), you can choose the separator between each
`\parafootsepX`

note by using `\Xparafootsep[⟨s⟩]{⟨text⟩}` for critical notes and `\parafootsepX` for familiar notes. A common separator is the double pipe (`||`), which you can set by using `\Xparafootsep{\parallel}`.

Note that if the symbol defined by `\Xsymlinenum` must be used at the beginning of a note, the `\Xparafootsep` / `\parafootsepX` is not used before this note.

7.11.2 Ragged text

`\Xragged` Text in paragraphed critical notes is justified, but you can use `\Xragged[⟨s⟩]{L}` if you want it to be ragged left (i.e., right justified), or `\Xragged[⟨s⟩]{R}` if you want it to be ragged right (i.e., left justified).

`\raggedX` Text in paragraphed footnotes is justified, but you can use `\raggedX[⟨s⟩]{L}` if you want it to be ragged left, or `\raggedX[⟨s⟩]{R}` if you want it to be ragged right.

7.12 Options for block of notes

7.12.1 Grouping notes by line

`\Xgroupbyline` If you do not use `\Xarrangement{paragraph}`, you may want to group all the critical footnotes related to the same line in the same paragraph. In this case, use `\Xgroupbyline[⟨series⟩]`.

In many cases, you might like to use it in combination with `\Xnumberonlyfirstinline` (7.4.1 p. 45).

`\groupbylineseparetwolines` Note that the `\Xafternote` and `\Xparafootsep` settings are used to determine space and content between footnotes (7.11 p. 54). Suppose you have two notes on line 1 which overlap lines 1 and 2. This last note will be printed, if you use `\Xgroupbyline` in the same group as the previous one. In the case you want that note to be distinct, you must use both `\Xgroupbyline` and `\Xgroupbylineseparetwolines[⟨s⟩]`.

In many cases, you might like to use it in combination with `\Xnumberonlyfirstintwolines` (7.4.1 p. 45).

7.12.2 Text before notes

`\Xtxtbeforenotes` You can add text before critical footnotes with `\Xtxtbeforenotes[⟨s⟩]{⟨text⟩}`.

`\txtbeforenotesX` You can add text before familiar footnotes with `\txtbeforenotesX[⟨s⟩]{⟨text⟩}`.

`\Xendtxtbeforenotes` You can add text before endnotes with `\Xendtxtbeforenotes[⟨s⟩]{⟨text⟩}`. The text will be typeset only if there are endnotes.

`\Xtxtbeforenotesonlyonce` By default, such texts are inserted at the beginning of the groups of notes on each page. You can add `\Xtxtbeforenotesonlyonce` (for critical footnotes) and `\txtbeforenotesonlyonceX` (for familiar footnotes) to insert them only the first time notes are typeset.

7.12.3 Code before notes

`\Xbhookgroup` While `\Xtxtbeforenotes` is for typesetting text before notes, `\Xbhookgroup[⟨s⟩]{⟨code⟩}` and `\bhookgroupX[⟨s⟩]{⟨code⟩}` (for critical and familiar respectively) are for executing code before a group of notes, between the rules and the printing of the notes.

7.12.4 Spacing

`\Xbeforenotes` You can change the vertical space before the rule of the critical notes with `\Xbeforenotes[⟨s⟩]{⟨l⟩}`. The default value is 1.2em plus .6em minus .6em.

Be careful, the standard L^AT_EX footnote rule used by `reledmac` decreases by 3pt. This 3pt decrease is not changed by this command.

`\beforenotesX` You can change the vertical space printed before the rule of the familiar notes with `\beforenotesX[⟨s⟩]{⟨l⟩}`. The default value is 1.2em plus .6em minus .6em.

Be careful, the standard L^AT_EX footnote rule, which is used by `reledmac`, decreases 3pt. These 3pt are not changed by this command.

`\Xprenotes` You can set the space before the first series of critical notes printed on each page and set a different amount of space for each subsequent series on the page. You can do it with `\Xprenotes{⟨l⟩}`. The default value is 0pt. You can disable this feature by setting the length to 0pt.

`\prenotesX` You can set the space before the first printed (in a page) series of familiar notes to be different from the space before other series. The default value is 0pt. You can do this with `\prenotesX{⟨l⟩}`. You can disable this feature by setting the length to 0pt.

7.12.5 Rule

`\Xafterrule` You can change the vertical space printed after the rule of the critical notes with `\Xafterrule[⟨s⟩]{⟨l⟩}`. The default value is 0pt.

Be careful, the standard L^AT_EX footnote rule, which is used by `reledmac`, adds 2.6pt. These 2.6pt are not changed by this command.

`\afterruleX` You can change the vertical space printed after the rule of the familiar notes with `\afterruleX[⟨s⟩]{⟨l⟩}`. The default value is 0pt.

Be careful, the standard L^AT_EX footnote rule, which is used by `reledmac`, adds 2.6pt. These 2.6pt are not changed by this command.

7.12.6 Maximum height

`\Xmaxhnotes` By default, one series of critical notes can take up to 80% of `\vsize`, before being broken to the next page. If you want to change the size use `\Xmaxhnotes[⟨s⟩]{⟨l⟩}`. Be careful: the length must be fixed (no stretch), and is relative to the the current font. For example, if you want the note to take, at most, 33% of the text height, do `\Xmaxhnotes{.33\textheight}`.

`\maxhnotesX` `\maxhnotesX[⟨s⟩]{⟨l⟩}` is the same as previous, but for familiar footnotes.

Note that in many cases, you should call these commands in the begin of the document, because the `\vsize` in the preamble is not the same as `\vsize` after the preamble. That why we recommend to you to add in your preamble

```
\AtBeginDocument{
  \maxhnotesX{0.8\textheight}
  \Xmaxhnotes{0.8\textheight}
}
```


Be careful with the two previous commands. Actually, for technical purposes, one paragraphed note is considered as one block. Consequently, it cannot be broken between two pages, even if you used these commands. The debug is in the *todolist*.

7.12.7 Width

`\Xwidth` `\Xwidth[⟨s⟩]{⟨l⟩}` sets the total width of critical footnotes. `\widthX[⟨s⟩]{⟨l⟩}` does the same for familiar footnotes.

`⟨l⟩` can be a length expression, parsable with `\dimexpr`. For example:

```
\Xwidth{\columnwidth+\marginparsep+\ledrsnotewidth}
\widthX{\columnwidth+\marginparsep+\ledrsnotewidth}
```

Note that changes the width of the block of notes. If you want to change the width of each column when typesetting notes in columns, use `\Xhsizetwocol`, `\Xhsizethreecol`, `\hsizetwocolX`, `\hsizethreecolX`, see 7.10.2 p. 54.

7.13 Footnotes and the *reledpar* columns

`\Xnoteswidthliketwocolumns` If you use `reledpar \columns` macro, you can call:

`\noteswidthliketwocolumnsX`

- `\Xnoteswidthliketwocolumns[⟨s⟩]` to create critical notes with a two-column size width.
- `\noteswidthliketwocolumnsX[⟨s⟩]` to create familiar notes with a two-column size width.

7.14 Endnotes in one paragraph

`\Xendparagraph` By default, any new endnote starts a new paragraph. Use `\Xendparagraph[⟨s⟩]` to have all end notes of one given series set in one paragraph.

`\Xendafternote` You can add some space after a endnote series by using `\Xendafternote[⟨s⟩]{⟨l⟩}`. The default value is `1em plus.4em minus.4em`.

`\Xendsep` You can choose the separator between each note by `\Xendsep[⟨s⟩]{⟨text⟩}`. A common separator is the double pipe (`||`), which you can set by using `\Xendsep{${\parallel}$}`.

8 Fonts

One of the most important features of the appearance of the notes, and indeed of your whole document, will be the fonts used. We will first describe the commands that give you control over the use of fonts in the different structural elements of the document, especially within the notes, and then in subsequent sections specify how these commands are used.

`\numlabfont` Line numbers for the main text are usually printed in a smaller font in the margin. The `\numlabfont` macro is provided as a standard name for that font: it is initially defined as

`\newcommand{\numlabfont}{\normalfont\scriptsize}`

You might wish to use a different font if, for example, you preferred to have these line numbers printed using old-style numerals.

`\select@lemmafont`

We will briefly discuss `\select@lemmafont` here because it is important to know about it now, although it is not one of the macros you would expect to change in the course of a simple job. Hence it is “protected” by having the `@`-sign in its name.

When you use the `\edtext` macro to mark a word in your text as a lemma, that word will normally be printed again in your apparatus. If the word in the text happens to be in a font such as italic or bold you would probably expect it to appear in the apparatus in the same font. This becomes an absolute necessity if the font is actually a different script, such as Arabic or Cyrillic. `\select@lemmafont` does the work of decoding `reledmac`’s data about the fonts used to print the lemma in the main text and calling up those fonts for printing the lemma in the note.

`\select@lemmafont` is a macro that takes one long argument—the cluster of line numbers passed to the note commands. This cluster ends with a code indicating what fonts were in use at the start of the lemma. `\select@lemmafont` selects the appropriate font for the note using that font specifier.

`reledmac` uses `\select@lemmafont` in a standard footnote format macro called `\normalfootfmt`. The footnote formats for each of the layers A to E are `\let` equal to `\normalfootfmt`. So all the layers of the footnotes are formatted in the same way.

9 Verse

9.1 Basic

`\stanza`
`\&`

Use `\stanza` at the start of a stanza. Each line in a stanza is ended by an ampersand (`&`), and the stanza itself is ended by putting `\&` at the end of the last line.

If you need to add brackets directly after `\stanza`, `&` or `\&`, add `\norelax`. Otherwise, the brackets will be interpreted as delimitation of an optional argument (cf. 9.9 p. 61)

9.2 Define stanza indents

`\stanzaindentbase`
`\setstanzaindent`

Lines within a stanza may be indented. The indents are integer multiples of the length `\stanzaindentbase`, whose default value is 20pt.

In order to use the stanza macros, **one must set the indentation values**. First the value of `\stanzaindentbase` should be set, unless the default value 20pt is desired. Every stanza line indentation is a multiple of this.

To specify these multiples one invokes, for example
`\setstanzaindent{3,1,2,1,2}`.

The numerical entries must be whole numbers, 0 or greater, separated by commas without embedded spaces. The first entry gives the hanging indentation to be used if the stanza line requires more than one print line.

If it is known that each stanza line will fit in one print line, then this first entry should be 0; \TeX does less work in this case, but no harm ensues if the hanging indentation is not 0 but is never used.

If you want the hanging verse to be flush right, you can use `\sethanginsymbol:` see p. 9.7 p. 60.

Enumeration is by stanza lines, not by print lines. In the above example the lines are indented one unit, two units, one unit, two units, with 3 units of hanging indentation in case a stanza line is too long to fit on one print line.

9.3 Repeating stanza indents

Since version 0.13, if the indentation is repeated every n verses of the stanza, you can define only the n first indentations, and indicate that they are repeated, defining the value of the `stanzaindentsrepetition` counter at n . For example:

```
\setstanzaindents{5,1,0}
\setcounter{stanzaindentsrepetition}{2}
```

is like

```
\setstanzaindents{5,1,0,1,0,1,0,1,0,1,0}
```

Be careful: the feature is changed in eledmac 1.5.1. See A.3 p. 406.

If you don't use the `stanzaindentsrepetition` counter, make sure you have at least one more numerical entry in `\setstanzavalues` than the number of lines in the stanza.

If you want to disable this feature again, just put the counter to 0:

```
\setcounter{stanzaindentsrepetition}{0}
```

The macro makes no restriction on the number of lines in a stanza.

Sometime, it is useful to repeat the indents only after some lines of verse. You can set the counter `startstanzaindentsrepetition` to do that. Its default value is 1, that means the repetition starts with line of verse number 1.

For example, you may want to have no indent for the first line, and all other lines been indented by 1. So do

```
\setstanzaindents{1,0,1}
\setcounter{stanzaindentsrepetition}{1}
\setcounter{startstanzaindentsrepetition}{2}
```

9.4 Notes about the scope of the indent settings

Stanza indentation values (and penalty values) obey \TeX 's grouping conventions, so if one stanza among several has a different structure, its indentations (penalties) may be set within a group; the prior values will be restored when the group ends.

9.5 Manual stanza indent

`\stanzaindent` You can set the indent of some specific verse by calling `\stanzaindent{⟨value⟩}` at the beginning of the verse, before any other character. In this case, the indent defined by `\setstanzaindent` for this verse is skipped, and `{⟨value⟩}` is used instead.

If you use the mechanism of indent repetition, the next verse will be printed as it should be even if the current verse would have its normal indent value. In other words, using `\stanzaindent` in a verse does not shift the indent repetition.

However, if you want to shift the indent repetition, so the next verse has the indent normally used for the current verse, use `\stanzaindent*` instead of `\stanzaindent`.

9.6 Stanza breaking

`\setstanzapenalties` When the stanzas run over several pages, it is often desirable that page breaks should arise between certain lines in the stanza, so a facility for including penalties after stanza lines is provided. If you are satisfied with the page breaks, you need not set the penalty values.

The command

```
\setstanzapenalties{1,5000,10100,5000,0}
```

results in a penalty of 5000 being placed after the first and third lines of the stanza, and a penalty of -100 after the second.

The first entry “1” is a control value. If it is zero, then no penalties are passed on to \TeX , which is the default. Values between 0 and 10000 are penalty values; values between 10001 and 20000 have 10000 subtracted and the result is given as a negative penalty. The mechanism used for indentations and penalties requires unsigned values less than 32768. No penalty is placed after the last line, so the final ,0 in the example above could be omitted. A penalty of 10000 will prevent a page break; such a penalty is included automatically where there is stanza hanging indentation. A penalty of -10000 (corresponding to the entry value 20000 in this context) forces a page break. Values in between act as suggestions as to the desirability of a page break at a given line. There is a subtle interaction between penalties and *glue*, so it may take some adjustment of skips and penalties to achieve the best results.

9.7 Hanging symbol

It is possible to insert a symbol in each line of hanging verse, as in French typography; for example, the opening bracket “[”. To insert it in `reledmac`, use macro `\sethangingsymbol{⟨h⟩}` with this code. In the example of French typography, do

`\sethangingsymbol`

```
\sethangingsymbol{[,]}
```

You can also use it to force hanging verse to be flush right:

```
\sethangingsymbol{\protect\hfill}
```

9.8 Long verse and page break

If you want to prevent page breaks inside long verses, use the option `nopbinverse` when loading package, or use `\lednopbinversetrue`. Read 18.2 p. 78 for further details.

9.9 Content before/after verses

It is possible to add content, like a subtitle or a spacing, before or after verse:

- The `\stanza` command can take an optional argument (in brackets). Its content will be printed before the stanza. A `\noindent` is inserted before the content of first optional argument. If you don't want this `\noindent`, you can use the second optional argument (also in brackets):

```
\stanza[foo] % \noindent is inserted before foo.
\stanza[] [foo] % There is no \noindent inserted before foo.
```

`\AtEveryStanza`

- Use `\AtEveryStanza{⟨arg⟩}` to automatically add content before stanzas (not in the same paragraph).

Note that a `\noindent` will be inserted before the argument, and, consequently, a `\parskip`. You can use the starred version of `\AtEveryStanza` to avoid this `\noindent`.

`\AtStartEveryStanza`

- Use `\AtStartEveryStanza` to automatically add content at the beginning of stanzas (in the same paragraph).

- `&` can be replaced by `\newverse` with two optional arguments (in brackets). The first will be printed after the current verse, the second before the next verse.

A `\noindent` is automatically inserted before the contents of these optional arguments.

Use a third and fourth optional argument to not add these `\noindents` (to add content respectively after the current verse / before the next verse).

- Use `\AtEveryPend{⟨arg⟩}` to automatically add content after verses (including the final one) and `\AtEveryPstart{⟨arg⟩}` to automatically add content before verses (including the first one).

- `\&` can take an optional argument (in brackets). Its content will be printed after the stanza.

`\AtEveryStopStanza`

- Use `\AtEveryStopStanza` to automatically add content after the end of stanzas (not in the same paragraph).

Note that a `\noindent` will be inserted before the argument, and, consequently, a `\parskip`. You can use the starred version of `\AtEveryStopStanza` to avoid this `\noindent`.

`\BeforeEveryStopStanza`

- Use `\BeforeEveryStopStanza` to automatically add content at the end of stanzas (in the same paragraph).

9.10 Numbering stanza

`\numberstanzatrue` If you want to automatically number stanzas, use `\numberstanzatrue`. In this case, the line number will restart at each `\stanza`.

`\numberstanzafalse` If you want to disable this feature again, use `\numberstanzafalse`. You can use this feature in combination with `\Xstanza` (7.4.8 p. 47).

`thestanza` You can redefine `\thestanza` to change the aspect of stanza number. Default value is:

```
\renewcommand{\thestanza}{%
\textbf{\arabic{stanza}}%
}
```

You can change the value of the `stanza` counter with the usual commands of \TeX .

`\stanzanumwrapper` You can redefine `\stanzanumwrapper` in order to modify the way the stanza number is inserted in the flow of text. Default value is:

```
\newcommand{\stanzanumwrapper}[1]{%
\flagstanza{#1}%
}
```

`\antilabe`

9.11 Antilabe

In dramatic text, it may happen that a line of verse is split between two speakers. That's called "antilabe". In this case, the typesetting of the second half must start at the horizontal position where the typesetting of the first half stops.

Reledmac provides tools to cope with this problem, but you must enable them with the `antilabe` option when loading package, as these tools are quite resource consuming.

The `\antilabe{<name>}` must be called at the beginning of the second half of the line of verse.

Its `<name>` argument is the name of the speaker. Because of the way \TeX expand argument, you can use one the following syntax:

- `\antilabe{<name>}`, if you typeset the character name;
- `\antilabe\command`, if the character name is defined in a command, like with the `thalie` package;
- `\antilabe{}`, if you do not type the character name.

See the file `examples/2-antilabe.tex` for an example of use.

`\beforeantilabe` You can execute any arbitrary code before or after `\antilabe` macro just with a redefinition of `\beforeantilabe` or `\afterantilabe`. For example, to add more space, just do:

`\afterantilabe`

```
\renewcommand{\afterantilabe}{\hspace{1em}}
```

9.12 Various tools

`\ampersand` If you need to print an & symbol in a stanza, use the `\ampersand` macro, not `\&` as this will end the stanza.

`\flagstanza` Putting `\flagstanza[⟨len⟩]{⟨text⟩}` at the start of a line in a stanza (or elsewhere) will typeset `⟨text⟩` at a distance `⟨len⟩` before the line. The default `⟨len⟩` is `\stanzaindentbase`.

9.13 Notes on empty lines

Since v2.3.0 of `reledmac`, empty lines when typesetting verses no longer produce new paragraphs, and consequently, do not insert vertical spaces. Use optional argument of `\stanza` or `\newverse` to insert vertical space (9.9 p. 61).

10 Grouping

In a `minipage` environment \TeX changes `\footnote` numbering from arabic to alphabetic and puts the footnotes at the end of the `minipage`.

`minipage` You can put numbered text with critical footnotes in a `minipage` and the footnotes are set at the end of the `minipage`.

You can also put familiar footnotes (see section 6.5) in a `minipage` but unlike with `\footnote` the numbering scheme is unaltered.

`ledgroup` Minipages, of course, are not broken across pages. Footnotes in a `ledgroup` environment are typeset at the end of the environment, as with minipages, but the environment includes normal page breaks. The environment makes no change to the `textwidth` so it appears as normal text; it just might be that footnotes appear in the middle of a page, with text above and below.

`ledgroupsize` The `ledgroupsize` environment is similar to `ledgroup` except that you must specify a width for the environment, as with a `minipage`.
`\begin{ledgroupsize}[⟨pos⟩]{⟨width⟩}`.

The required `⟨width⟩` argument is the text width for the environment. The optional `⟨pos⟩` argument is for positioning numbered text within the normal `textwidth`. It may be one of the characters:

l (left) numbered text is flush left with respect to the normal `textwidth`. This is the default.

c (center) numbered text is in the center of the `textwidth`.

r (right) numbered text is flush right with respect to the normal `textwidth`.

Note that normal text, footnotes, and so forth are all flush left.

`\begin{ledgroupsize}{\textwidth}` is effectively the same as `\begin{ledgroup}`

11 Cross referencing

The package provides a simple cross-referencing facility that allows you to mark places in the text with labels, and generate page and line number references to those places elsewhere using those labels.

11.1 Basic use

`\edlabel` First you place a label in the text using the command `\edlabel{<lab>}`. `<lab>` can be almost anything you like, including letters, numbers, punctuation, or a combination—anything but spaces; you might type `\edlabel{toves-3}`, for example.²³

`\edpageref` Elsewhere in the text, either before or after the `\edlabel`, you can refer to its location with `\edpageref{<lab>}`, `\edlineref{<lab>}`, `\edsublineref{<lab>}`, `\pstartref{<lab>}` or `\annotationref{<lab>}`, that will produce, respectively, the page, line, sub-line, pstart, the annotation, on which the `\edlabel{<lab>}` command occurred.

`\edlineref`

`\sublineref`

`\pstartref`

`\annotationref`

Note that the `\edlineref` command insert the side flag after the line number.

An `\edlabel` command may appear in the main text, or in the first argument of `\edtext`, but not in the apparatus itself. But `\edpageref`, `\edlineref`, `\sublineref`, `\pstartref` commands can also be used in the apparatus to refer to `\edlabels` in the text.

The `\edlabel` command works by writing macros to `ℒTEX.aux` file. You will need to process your document through `ℒTEX` twice in order for the references to be resolved.

You will be warned if you use `\edlabel{foo}` and `foo` has been used as a label before. The `ref` commands will return references to the last place in the file marked with this label. You will also be warned if a reference is made to an undefined label. (This will also happen the first time you process a document after adding a new `\edlabel` command: the auxiliary file will not have been updated yet.)

11.2 Cross-referencing to a critical note

If you want to refer to a word which is a lemma word, the `\edlabel` command should be in the first argument of `\edtext` command.

If you want to refer to the content of a `\Xfootnote`, the line and subline number printed will be the start line.

If you want to refer to starting and ending lines, you should use `\appref` and related tools (11.6.2 p. 66).

11.3 Cross-referencing which return a number in any case

`\xpageref` However, there are situations in which you will want `reledmac` to return a number without displaying any warning messages about undefined labels or the like: if you want to use the reference in a context where `ℒTEX` is looking for a number, such a warning

`\xlineref`

`\xsublineref`

`\xpstartref`

`\xannotationref`

²³More precisely, you should stick to characters in the `TEX` categories of “letter” and “other”.

will lead to a complaint that the number is missing. This is the case for references used within the argument to `\linenum`, for example (see 6.2.5 p. 33).

For this situation, `reledmac` supplies variants of the reference commands, with the `x` prefix: `\xpageref`, `\xlineref`, `\xsublineref`, `\xpstartref` and `\xannotationref`. They have the following limitations:

- They will not tell you if the label is undefined.
- They must be preceded in the file by at least one of the four other cross-reference commands—e.g., a `\edlabel{foo}` command, even if you never refer to that label—since those commands can all do the necessary processing of the `.aux` file, and the `\x...` ones cannot.
- When `hyperref` is loaded, the `hyperref` link will not be added. (Indeed, it is not a limitation, but a feature.)
- With `reledpar`, the `\xlineref` does not insert the right side flag, in order to obtain a line number. Use `\xflagref` to obtain the side flag, depending on your flag.

11.3.1 Cross-referencing in order to define line number of a critical note

`\xxref`

The `\xxref{<lab1>}{<lab2>}` command generates a reference to a sequence of lines, for use in the second argument of `\edtext`. It takes two arguments, both of which are labels: e.g., `\xxref{mouse}{elephant}`.

It automatically calls `\linenum` (6.2.5 p. 33) and `\lineannot` (5.5.2 p. 27) and sets the beginning page, line, subline numbers and line annotations to those of the place where `\edlabel{mouse}` was placed, and the ending ones to those where `\edlabel{elephant}` occurs.

For example, one might use the following:

```
\beginnumbering

\pstart
\edlabel{Queritur}Queritur utrum metaphysica sit scientia una.
\pend

\pstart
\edtext{Et videtur quod non\edlabel{non}.}{\xxref{Queritur}{non}\lemma{queritur \dots{}} non}\Afootnote{
\pend

\endnumbering
```

11.4 Not automatic cross-referencing

`\edmakelabel`

Sometimes the `\edlabel` command cannot be used to specify exactly the page and line desired—for example, if you want to refer to a page and line number in another volume of

your edition. In such cases, you can use the `\edmakelabel{<lab>}{<numbers>}` macro so that you can “roll your own” label.

For example, if you type `\edmakelabel{elephant}{10|25|0}` you will create a new label, and a later call to `\edpageref{elephant}` would print “10” and `\lineref{elephant}` would print “25”. The sub-line number here is zero. It is usually best to collect your `\edmakelabel` statements near the top of your document, so that you can see them at a glance.

11.5 Normal \LaTeX cross-referencing

`\label` The normal `\label`, `\ref` and `\pageref` macros may be used within numbered text,
`\ref` and operate in the familiar fashion.
`\pageref`

11.6 References to start and end lines

11.6.1 Reference to main text lines

Many times, you may want to make a cross-reference to a passage that is defined by a start line and an end line. `reledmac` provides specific tools for this scenario.

`\edlabelS` Use `\edlabelS{<label>}` to mark the start line of the passage.
`\edlabelE` Use `\edlabelE{<label>}` to mark the end the end line of the passage. These two
commands just create two labels which are named `<label>:start` and `<label>:end`.
`\edlabelSE` Use `\edlabelSE{<label>}` to mark just one location in the text. Contrary to a clas-
sical `\edlabel`, the `<label>` could be use with `\Seref` and `\Serefwithpage`.
`\Seref` The main utility is to use them with three other commands. `\Seref{<label>}` will
make a cross-reference printed as a reference in critical footnotes.
`\Serefwithpage` `\Serefwithpage` will make a cross-reference printed as a reference in critical end-
notes.
`\Serefonlypage` `\Serefonlypage` will make a cross-reference printed only with page number.

11.6.2 References to lines that are commented on in the apparatus

You may want to make a cross-reference to a passage that is referred to by `\edtext`. `reledmac` provides specific tools for this scenario.

`\applabel` If you use `\applabel{<label>}` inside the second argument of a `\edtext`, `reledmac`
will add a `\edlabel` at the beginning and end of the marked passage. The label at the
beginning of the passage will have the title `<label>:start`, while the label at the end
will have the title `<label>:end`.
If you use `\linenum` (6.2.5 p. 33) to refer to these labels, `reledmac` will use your line
settings to refer to the passage.
`\appref` You can also use `\appref{<label>}` and `\apprefwithpage{<label>}` to refer to these
`\apprefwithpage` lines. The first one will print the lines as they are printed in the critical footnotes, while
the second will print the lines as they are printed in endnotes.

11.6.3 Settings

`\setapprefprefixsingle` **Specific to these tools** If you use `\apprefprefixsingle{<prefix>}`, `<prefix>` will be
`\setapprefprefixmore`

printed before the line numbers of a \appref-reference. If you use \apprefprefixmore{<prefix>}, <prefix> will be printed before the line numbers, if you refer to more than one line.

For example, you may use:

```
\setapprefprefixsingle{line~}
\setapprefprefixmore{lines~}
```

Note that if you do not use \setapprefprefixmore, the argument of \setapprefprefixsingle will be used in any case.

\setSerefprefixsingle and \setSerefprefixmore are similar for \Seref command.

Use \setSerefonlypageprefixsingle{<prefix>} to set the page prefix for \Serefonlypage when there is only one page. Use \setSerefonlypageprefixmore{<prefix>} to set it when there is more than one page. For example:

```
\setSerefonlypageprefixsingle{p.~}
\setSerefonlypageprefixmore{pp.~}
```

Note that if you do not use \setSerefonlypageprefixmore, the value of \setSerefonlypageprefixsingle is used instead.

Also note that \setSerefonlypageprefixsingle is only a shortcut for \XendbeforepagenumberSerefonly (see 11.6.3 p. 67). So if you use \Xendbeforepagenumber without any optional argument, it will override this setting.

Linked to setting of critical footnotes and endnotes Some commands which set the appearance of line numbers in critical footnotes also set the appearance of line numbers in \appref and \Seref if called *without the optional series argument*.

These commands are the following:

- \Xlineflag (for reledpar), enabled by default.
- \Xlinerangeseparator
- \Xmorethantwolines
- \Xsublinesep
- \Xtwolines
- \Xtwolinesbutnotmore
- \Xtwolinesonlyinsamepage
- \Xlinenumannotationposition
- \Xwraplinenumannotation
- \Xnoidenticallinenumannotation

If you want to make settings specific to `\appref` or `\Seref`, just call them with an optional argument containing a comma-separated list of command names (for example `\appref,Seref`) or with a suffix equal to the command name (for example `\appref`).

The same principle is available for `\apprefwithpage`, `\Serefwithpage` and `\Serefonlypage` with the following commands:

- `\Xendafterpagenumber` (not for `\Serefonlypage`)
- `\Xendbeforepagenumber`
- `\Xendlineflag` (for `reledpar`), enabled by default.
- `\Xendlineprefixmore`
- `\Xendlineprefixsingle`
- `\Xendlinerangeseparator`
- `\Xendmorethantwolines`
- `\Xendsublinesep`
- `\Xendtwolines`
- `\Xendtwolinesbutnotmore`
- `\Xendtwolinesonlyinsamepage`
- `\Xendlinenumannotationposition`
- `\Xendwraplinenumannotation`
- `\Xemdnoidenticallinenumannotation`

For one specific command When calling `\appref` and `\Seref`, you can use as a first optional argument, in brackets (`[]`), any optional argument which can be used for critical footnotes (6.2.2 p. 30).

When calling `\apprefwithpage`, `\Serefwithpage` or `\Serefonlypage` you can use as a first optional argument, in brackets (`[]`), any optional argument which can be used for critical endnotes (6.2.3 p. 31).

11.6.4 Combining multiple references

When combining multiple cross references into a list, it is possible to prevent prefixes reappearing by adding an optional argument to `\appref` and `\Seref`. The available options are:

- `noprefix` to remove any prefix set by `\setapprefprefixsingle` or the equivalent for a single reference;
- `prefixmore` to force the plural version of a prefix.

For example, a reference to “lines 65–66, 72, and 75” might use `\Seref[prefixmore]{ref1}`, `\Seref` to achieve this result.

11.7 Compatibility with xr package

The `\externaldocument` command of the `\xr` package allows making cross-references from an external document, with the standard \TeX commands `\label` and `\ref` (and related).

To use it with the `reledmac` cross-reference commands (i.e. `\edlabel` and related), you must do the following:

1. Load the `xr` package.
2. Load the `reledmac` package.
3. Use the `\externaldocument` document command.

12 Sidenotes

12.1 Basics

The `\marginpar` command does not work in numbered text. Instead, the package provides for non-floating sidenotes in either margin.

`\ledinnernote` `\ledinnernote{⟨text⟩}` will put `⟨text⟩` into the inner margin level with where the command was issued. Similarly, `\ledouternote{⟨text⟩}` puts `⟨text⟩` in the outer margin.

`\ledleftnote` `\ledsidenote{⟨text⟩}` will put `⟨text⟩` into the margin specified by the current setting of `\sidenotemargin{⟨location⟩}`. The permissible value for `⟨location⟩` is one out of the list `left`, `right`, `inner`, or `outer`, for example `\sidenotemargin{outer}`.
`\ledrightnote` The package's default setting is
`\ledsidenote` `\sidenotemargin{right}`
`\sidenotemargin`

to typeset `\ledsidenotes` in the right hand margin. This is the opposite of the default margin for line numbers. The style for a `\ledsidenote` follows that for a `\ledleftnote` or a `\ledrightnote` depending on the margin it is put in.

If two note commands for the same side are called in the same line, they will be appended and separated by a comma.

The notes will appear only after the second \TeX run. If the note positions change in your `.tex` file, you need two runs to get the correction position in the output file. You are strongly encouraged to use tools like *latexmk*, to be sure to get the correct number of runs.

12.2 Setting

12.2.1 Width

`\ledlsnotewidth` The left sidenote text is put into a box of width `\ledlsnotewidth` and the right
`\ledrsnotewidth` text into a box of width `\ledrsnotewidth`. These are initially set to the value of `\marginparwidth`.

12.2.2 Vertical position

`\rightnoteupfalse` By default, sidenotes are placed to align with the last line of the note to which it refers.
`\leftnoteupfalse` If you want they to be placed to align with the first line of the note to which it refers, use `\leftnoteupfalse` (for left note) and/or `\rightnoteupfalse` (for right note).

12.2.3 Distance to the main text

`\ledlsnotesep` The texts are put a distance `\ledlsnotesep` (or `\ledrsnotesep`) into the left (or right) margin. These lengths are initially set to the value of `\linenumsep`.
`\ledrsnotesep`

12.2.4 Font

`\ledlsnotefontsetup` These macros specify how the sidenote texts are to be typeset. The initial definitions are:
`\ledrsnotefontsetup`

```
\newcommand*{\ledlsnotefontsetup}{\raggedleft\footnotesize}% left
\newcommand*{\ledrsnotefontsetup}{\raggedright\footnotesize}% right
```

These can of course be changed to suit.

12.2.5 Separator between notes

`\setsidenotesep` If you have two or more sidenotes for the same line, they are separated by a comma. But if you want to change this separator, you can use `\setsidenotesep{<sep>}`.

13 Indexing

13.1 Basics

`\edindex` \TeX provides the `\index{<item>}` command for specifying that `<item>` and the current page number should be added to the raw index (`idx`) file. The `\edindex{<item>}` macro can be used in numbered text to specify that `<item>` and the current page & line number should be added to the raw index file.

Note that the file `.idx` will contain the right reference only after the third run, because of the internal indexing mechanism of `reledmac`. That means you must first run (Xe/Lua) \TeX three times, then run `makeindex`, and then finally run (Xe/Lua) \TeX again, in order to get an index with the right page numbers.

Also note that using `\edtext` in familiar footnotes refers to the line where the footnotes are called

13.2 Use with `imakeidx` or `indextools`

If the `imakeidx` or `indextools` package is used then the macro takes an optional argument, which is the name of a raw index file. For example `\edindex[line]{item}` will use `line.idx` as the raw file instead of `\jobname.idx`.

The minimal version of `imakeidx` package to be used is the version 1.3a uploaded on CTAN on 2013/07/11.

Be careful with the order of package loading and index declaration. You must use this order:

1. Load `imakeidx` or `indextools`.
2. Load `reledmac`.
3. Declare the index with the macro `\makeindex` of `imakeidx` and `indextools`.

13.3 Referring to critical notes

If you want to refer to a word inside an `\edtext{<lemma>}{<app>}` command, `\edindex` should be defined inside the first argument, e.g.,

```
The \edtext{creature\edindex{elephant} was quite
unafraid}{\Afootnote{Of the mouse, that is.}}
```

If you add `\edindex` inside some `\Xfootnote` command, it will refer to that note, and a suffix *n* will be appended to the reference.

You can redefine the way the reference is made using:

`\Xinnotemark`
`\innotemarkX`

- `\Xinnotemark[<series>]{<definition>}` for critical notes;
- `\innotemarkX[<series>]{<definition>}` for familiar notes;

In the `<definition>` argument, you can use the following codes:

- `#1`, which stands for footnote series;
- `##1`, which stands for reference (ie. page+line)

For example:

```
\Xinnotemark{##1\textsuperscript{#1}}
```

13.4 Separator between page and line numbers

`\pagelinesep`

The page & line number combination is written as `page\pagelinesep line`, where the default definition is `\newcommand{\pagelinesep}{-}` so that an item on page 3, line 5 will be noted as being at 3-5. You can renew `\pagelinesep` to get a different separator.

- is the default separator used by the `MAKEINDEX` program.

You can reconfigure it, this example defines a colon as separator:

```
\renewcommand{\pagelinesep}{:}
```

However, you also have to configure your `.ist` index style file. For example, if you use `:` as separator²⁴.

```
page_compositor ":"
```

Read the MAKEINDEX program's handbook about the `.ist` file.

13.5 Using xindy

Should you decide to use `xindy` instead of `makeindex` to transform your `.idx` files into `.ind` files, you must use some specific configuration file (`.xdy`) so that `xindy` can understand `eledmac` reference syntax of which the scheme is:

```
pagenumber-linenummer
```

An example of such a file is provided in the “examples” folder. Read the `xindy` handbook to learn how to use it.²⁵

This file also provides, with an explanation, the settings that are needed to put `reledmac` lines numbers in parenthesis, in order to make a better distinction between line numbers and page ranges.

In any case, you must load `reledmac` with the `xindy` option, in order to generate a `.xdy` file which is specific to your document. This file is needed by the `.xdy` example file which is in the “examples” folder. Its default name is `reledmac-markup-attr.xdy`, but you can change it by using your own as an argument of the `xindy+hyperref` option.

If you choose to use both `xindy` and the `hyperref` package, you must do three more things:

1. Use `xindy+hyperref` option when loading the `reledmac` package. When you run (Xe/Lua) \TeX with this option, a `.xdy` configuration file will be generated with all the settings needed to allow internal hyperlinking in each index entry which is created by `\edindex`.
2. Use `hyperindex=false` option when loading `hyperref`.
3. Uncomment — by removing the semicolons at the beginning of the relevant lines — some lines in the `<code>.xdy</code>` file provided in the “examples” folder in order to restore internal links in the index to be used by the standard `index` command.²⁶

13.6 Advanced setting

`\edindexlab` The `\edindex` process uses a `\label` and `\ref` mechanism to get the correct line number. It automatically generates labels of the form `\label{\edindexlab N}`, where `N` is a number, and the default definition of `\edindexlab` is:

```
\newcommand*{\edindexlab}{\&}
```

²⁴For further detail, you can read <http://tex.stackexchange.com/a/32783/7712>.

²⁵Or, for people who read French, read <http://geekographie.maieul.net/174>.

²⁶These are the recommended lines to provide the best possible compatibility between `hyperref` and `xindy`, even without using `reledmac`.

in the hopes that this will not be used by any other labels (`\edindex`'s labels are like `\label{${\&27}`). You can change `\edindexlab` to something else if you need to.

14 Glossary

`reledmac` provides mechanism to make glossaries with the `glossaries` package, referring not to the page, but to the page and line.

14.1 Preamble setting

The standard compositor between page and line number in `reledmac` is a dash, while `glossaries` uses, by default, a dot. Consequently, you must:

- Or set `.glossaries`:
`\glsSetCompositor{-}`
- Or set `reledmac`:
`\renewcommand{\pagelinesep}{.}`
 In this case, the above will have consequences for your use of `\edindex` and you should set your `.ist` file (13.4 p. 71).

14.2 Commands

The `\gls`, `\Gls`, and related commands of `glossaries` packages have a prefixed version with `ed`, which refers to the page line. The argument are the same as for the standard commands. So for example:

`\edgls[<options>]{<label>}[<insert>]`

15 Tabular material

\TeX 's normal `tabular` and `array` environments cannot be used where line numbering is being done; more precisely, they can be used but with odd results, so don't use them. However, `reledmac` provides some simple tabulation environments that can be line numbered. The environments can also be used in normal unnumbered text.

There are six environments; the `edarray*` environments are for math and `edtabular*` for text entries. The final `l`, `c`, or `r` in the environment names indicate that the entries will be flushleft (`l`), centered (`c`) or flushright (`r`). There is no means of specifying different formats for each column, nor for specifying a fixed width for a column. The environments are centered with respect to the surrounding text.

```

\begin{edtabularc}
1 & 2 & 3 \\
a & bb & ccc \\
AAA & BB & C
\end{edtabularc}

```

1	2	3
a	bb	ccc
AAA	BB	C

Entries in the environments are the same as for the normal `array` and `tabular` environments but there must be no ending `\\` at the end of the last row. *There must be*


```

v                & wptz & x & y & vb \\
g                & nnn & \edrowfill{3}{5}{\upbracefill} & & \\
\edrowfill{1}{3}{\downbracefill} & & & pq & dgh \\
k                & & & l & co & ghweropjklmnbvcxys \\
1                & 2 & 3 & \edrowfill{4}{5}{\hrulefill} & \\
\end{tabularr}

```

1	2	3	4	5
Q		fd	h	qwertziohg
v	wptz	x	y	vb
g	nnn	$\underbrace{\hspace{10em}}$		
	$\underbrace{\hspace{10em}}$		pq	dgh
k		l	co	ghweropjklmnbvcxys
1	2	3	$\underline{\hspace{10em}}$	

You can also define your own “fill”. For example:

```

\newcommand*{\upbracketfill}{%
  \vrule height 4pt depth 0pt\hrulefill\vrule height 4pt depth 0pt}

```

is a fill like `\upbracefill` except it has the appearance of a (horizontal) bracket instead of a brace. It can be used like this:

```

\begin{edarrayc}
1 & 2 & & & 3 & 4 & \\
a & & \edrowfill{2}{3}{\upbracketfill} & & d & \\
A & B & & & C & D & \\
\end{edarrayc}

```

1	2	3	4
a	\lrcorner		d
A	B	C	D

`\edatleft` `\edatleft[$\langle math \rangle$]{ $\langle symbol \rangle$ }{ $\langle halfheight \rangle$ }` typesets the math $\langle symbol \rangle$ as $\left\{\langle symbol \rangle\right\}$ with the optional $\langle math \rangle$ centered before it. The $\langle symbol \rangle$ is twice $\langle halfheight \rangle$ tall. The `\edatright` macro is similar and it typesets $\right\{\langle symbol \rangle\}$ with $\langle math \rangle$ centered after it.

```

\begin{edarrayc}
& 1 & 2 & 3 & & \\
& 4 & 5 & 6 & & \\
\edatleft[left =]{\{\}}{1.5\baselineskip}
& 7 & 8 & 9 & & \\
\edatright[= right]{\}}{1.5\baselineskip}
\end{edarrayc}

```

$$left = \begin{pmatrix} 1 & 2 & 3 \\ 4 & 5 & 6 \\ 7 & 8 & 9 \end{pmatrix} = right$$

`\edbeforetab` `\edbeforetab{<text>}{<entry>}`, where `<entry>` is an entry in the leftmost column, typesets `<text>` left justified before the `<entry>`. Similarly `\edaftertab{<entry>}{<text>}`, where `<entry>` is an entry in the rightmost column, typesets `<text>` right justified after the `<entry>`.

For example:

```
\begin{edarrayl}
      A & 1 & 2 & 3 & \\\
\edbeforetab{Before}{B} & 1 & 3 & 6 & \\\
      C & 1 & 4 & & \edaftertab{8}{After} \\\
      D & 1 & 5 & 0 & \\
\end{edarrayl}
```

	$\begin{matrix} A & 1 & 2 & 3 \\ B & 1 & 3 & 6 \\ C & 1 & 4 & 8 \\ D & 1 & 5 & 0 \end{matrix}$		After
Before			

`\edvertline` The macro `\edvertline{<height>}` draws a vertical line `<height>` high (contrast this with `\edatright` where the size argument is half the desired height).

`\edvertdots`

```
\begin{edarrayr}
a & b & C & d & & \\\
v & w & x & y & & \\\
m & n & o & p & & \\\
k & & L & cvb & & \edvertline{4pc}
\end{edarrayr}
```

a	b	C	d	
v	w	x	y	
m	n	o	p	
k		L	cvb	

The `\edvertdots` macro is similar to `\edvertline` except that it produces a vertical dotted instead of a solid line.

16 Sectioning commands

16.1 Sectioning commands without line numbers or critical notes

The standard sectioning commands (`\chapter`, `\section` etc.) can be used inside numbered text. In this case, you must call them as an optional argument of `\pstart` (5.2.3

p. 19):

```
\pstart[\section{section}]
Pstart content.
\pend
```

The line which contains them will not be numbered, and you cannot add critical notes inside.

16.2 Sectioning commands with line numbering and critical notes

You have to use the following commands:

- `\eledchapter[\langle text \rangle]{\langle critical text \rangle}`,
- `\eledchapter*`,
- `\eledsection[\langle text \rangle]{\langle critical text \rangle}`,
- `\eledsection*`,
- `\eledsubsection[\langle text \rangle]{\langle critical text \rangle}`,
- `\eledsubsection*`,
- `\eledsubsubsection[\langle text \rangle]{\langle critical text \rangle}`,
- `\eledsubsubsection*`.

These are equivalent to the \LaTeX commands. Each individual command must be called alone in a `\pstart... \pend`:

```
\pstart
\eledsection*{xxxx\ledsidenote{section}}
\pend
\pstart
\eledsubsection*{xxxx\ledsidenote{sub}}
\pend
\pstart
normal text
\pend
```

After the first run, you will see only the text. This is normal. After the second run, you will see the formatting. Finally, with the third run, you will see the table of contents.

For technical reasons, the page break before `\eledchapter` cannot be added automatically. You have to insert it manually via `\beforeeledchapter`, which must be called outside of a numbered section.

16.3 Optimization

If you are not going to have any `\eledxxx` commands, then load `reledmac` with `noeledsec` option. That will suppress the generation of unneeded `.eledsec` files, save memory, and make `reledmac` run faster.

17 Quotation environments

The quotation and quote environments can be used so that the same definition/note appears both inside and outside a numbered section. The typographical consequences will resemble the outside numbered sections, based on the styles of the *book* class. However, if you use a package that redefines these environments, these redefinitions won't be available inside the numbered section. You must open any quotation environments inside a `\pstart ... \pend` block, not outside. A quotation environment **MUST NOT** be opened immediately after a `\pstart` and **MUST NOT** be closed immediately before a `\pend`.

In some cases, you do not want these environments to be redefined in numbered sections. You can load the package with the option `noquotation` to prevent this redefinition.

18 Page breaks

18.1 Control page breaking

`reledmac` and `reledpar` break pages automatically. However, you may sometimes want to either force page breaks, or prevent them. The packages provide two macros:

`\ledpb`
`\lednopb`

- `\ledpb` adds a page break.
- `\lednopb` prevents a page break, by adding one line to the current page if needed.

These commands have effect only at the second run.

These two commands take effect at the beginning of line in which they are called. For example, if you call `\ledpb` at l. 444, then l. 443 will be at p. *n*, and l. 444 at p. *n* + 1. However, you can change the behavior and decide they will have effect after the end of the line, adding `\ledpbsetting{after}` at the beginning of your file (better: in your preamble). With the previous example, l. 444 will be on p. *n* and l. 445 will be on p. *n* + 1.

`\ledpbsetting`

If you are using `reledpar` to typeset parallel pages, you must use `\lednopb` on both sides in the two corresponding lines. This is especially important when you are using stanzas; otherwise, the pages will be out of sync.

18.2 Prevent page break in a long verses

`\lednopbinversetrue`

You can also decide to prevent page breaks between two lines of a long verse. To do this, use `nopbinverse` when loading package, or add `\lednopbinversetrue` in the beginning of your file (better: in your preamble).

This feature works only with verse of 2 lines and no more. It works on the third run, or on the fourth run if using `reledpar`. By default, when a long verse runs between two pages, a page break will be placed at the beginning of the verse. However, if you have added `\ledpbsetting{after}`, the page break will be placed at the end of the long verse and the page containing the long verse will have one extra line.

19 Miscellaneous

`\extensionchars` When the package assembles the name of the auxiliary file for a section, it prefixes `\extensionchars` to the section number. This is initially defined to be empty, but you can add some characters to help distinguish these files if you like; what you use is likely to be system-dependent. If, for example, you said `\renewcommand{\extensionchars}{!}`, then you would get temporary files called `jobname. !1`, `jobname. !2`, etc.

`\ifledfinal` The package can take options. The `final` option, which is the default is for final typesetting; this sets `\ifledfinal` to TRUE. The other option, `draft`, may be useful during earlier stages and sets `\ifledfinal` to FALSE.

`\showlemma` The lemma within the text is printed via `\showlemma{lemma}`. Normally, or with the `final` option, the definition of `\showlemma` is:

```
\newcommand*{\showlemma}[1]{#1}
```

so it just produces its argument. With the `draft` option it is defined as

```
\newcommand*{\showlemma}[1]{\textbf{#1}}
```

so that its argument is bold, which may make it easier to check that all lemmas have been treated.

If you would prefer some other style, you could put something like this in the preamble:

```
\ifledfinal\else
  \renewcommand{\showlemma}[1]{\textbf{#1}}% or simply ...[1]{#1}
\fi
```

19.1 Known and suspected limitations

19.1.1 Non-standard geometry

If you use classes other than `article` or `book`, or if you use the `geometry` package, you should use `maxhnotesX` and/or `\Xmaxhnotes` as explained in 7.12.6 p. 56 in order to prevent footnotes from overlapping the bottom margin.

19.1.2 floatrow package compatibility

The `floatrow` package must be loaded before the `reledmac`.

19.1.3 “No room for a new”

Sometimes, especially when using `reledmac` with other packages, you could obtain warning messages such ‘no room for a new count’ or ‘no room for a new write’.

In order to prevent such problems, the first thing is to use the options to optimize `reledmac`. For example, if you need only two series of notes, use the `series={A,B}` option. Read 16.3 p. 78 in order to know which are the available options.

However, if with these options you still have such messages, here are some tricks.

'no room for a new count' is often caused by `biblatex` being used at the same time. Load `reledmac` (and `reledpar`) *before* `biblatex`.

'no room for a new write' can be caused by multiple indexes. In this case, use `indextools` of `imakeidx` with the `splitindex` option, in order to obtain only one `.idx` file. If that does not solve your problem, you can use `morewrites` package. That should solve the problem, but \LaTeX will be slower.

If after reading and applying these advices you have still problem, contact us with a minimal working example.

19.1.4 Marginal notes

In general, `reledmac`'s system for adding marginal line numbers breaks anything that makes direct use of the \LaTeX insert system, which includes `marginpars`, footnotes and floats.

However, you can use both `\footnote` and the familiar footnote series notes in numbered text. A `\marginpar` in numbered text will throw away its contents and send a warning message to the terminal and log file, but will do no harm.

19.1.5 Paragraph shape

`\parshape` cannot be used within numbered text, except in a very restricted way.

`\ballast` \LaTeX is a three-pass system, but even after a document has been processed three times, there are some tricky situations in which the page breaks decided by \TeX never settle down. At each successive run, `reledmac` may oscillate between two different sets of page decisions. To stop this happening, should it arise, Wayne Sullivan suggested the inclusion of the quantity `\ballast`. The amount of `\ballast` will be subtracted from the penalties which apply to the page breaks calculated on the *previous* run through \TeX , thus reinforcing these breaks. So if you find your page breaks oscillating, insert `\setcounter{ballast}{100}`

or some such figure, and with any luck the page breaks will settle down. Luckily, this problem does not crop up at all often.

19.1.6 Paragraphed footnotes

The restriction on explicit line-breaking in paragraphed footnotes, mentioned on 7.3 p. 44, and described in more detail on XIII.6.3 p. 200, really is a nuisance if that is something you need to do. There are some possible solutions, described by Michael Downes, but this area remains unsatisfactory.

If you use more than one series of paragraphed notes, it may happen, in some particular cases, that only the footnote rule, with no accompanying footnotes, be printed. In this case use `reledmac` package option `nopenalties` which should solve the problem,

but also may produce widow or orphan lines. For the time being, we have no solution of this problem.

`\footfudgefiddle`

For paragraphed footnotes \TeX has to estimate the amount of space required. If it underestimates this then the notes may get too long and run off the bottom of the text block. `\footfudgefiddle` can be increased from its default 64 (say, to 68) to increase the estimate. You have to use `\renewcommand` for this, like:

```
\renewcommand{\footfudgefiddle}{68}
```

Note that you must call it *before* `\Xarrangement{paragraph}` or `\arrangementX{paragraph}`.

Any settings to “geometry” must be made before `\Xarrangement` / `\arrangementX`.

Finally, in many cases you should use `\Xmaxhnotes` and / or `\maxhnotesX` (7.12.6 p. 56), in order to define the maximum height relative to `\textheight` and not to `\vsize`, because the `\vsize` value is not the same inside and outside of the preamble.

19.1.7 Use with other packages

Because of `reledmac`’s complexity, it may not play well with other packages. In particular `reledmac` is sensitive to commands in the arguments to the `\edtext` and `*footnote` macros (this is discussed in more detail in section VI, and in particular the discussion about `\no@expands` and `\morenoexpands`). You will have to see what works or doesn’t work in your particular case.

`\morenoexpands`

You can define the macro `\morenoexpands` to modify macros that you call within `\edtext`. Because of the way `reledmac` numbers the lines the arguments to `\edtext` can be processed more than once and in some cases a macro should only be processed once. One example is the `\colorbox` macro from the `color` package, which you might use like this:

```
... \edtext{\colorbox{mycolor}{lemma}}{\Afootnote{... \colorbox{...}}}
```

If you actually try this²⁷ you will find \TeX whinging “Missing { inserted”, and then things start to fall apart. The trick in this case is to specify either:

```
\newcommand{\morenoexpands}{\let\colorbox=0}
```

or

```
\makeatletter
\newcommand{\morenoexpands}{\let\colorbox\@secondoftwo}
\makeatother
```

(`\@secondoftwo` is an internal \TeX macro that takes two arguments and throws away the first one.) The first incantation lets color show in both the main text and footnotes whereas the second one shows color in the main text but kills it in the lemma and footnotes. On the other hand if you use `\textcolor` instead, like

```
... \edtext{\textcolor{mycolor}{lemma}}{\Afootnote{... \textcolor{...}}}
```

²⁷Reported by Dirk-Jan Dekker in the CTT thread “Incompatibility of ‘color’ package” on 2003/08/28.

there is no need to fiddle with `\morenoexpands` as the color will naturally be displayed in both the text and footnotes. To kill the color in the lemma and footnotes, though, you can do:

```
\makeatletter
\newcommand{\morenoexpands}{\let\textcolor\@secondoftwo}
\makeatother
```

It took Peter Wilson a little while to discover all this. If you run into this sort of problem you may have to spend some time experimenting before hitting on a solution.

If you want to use the option *bottom* of the `footmisc` package, you must load this package *before* the `reledmac` package.

19.2 Parallel typesetting

Peter Wilson has developed the `ledpar` package as an extension to `ledmac` specifically for parallel typesetting of critical texts. This also cooperates with the `babel` / `polyglossia` packages for typesetting in multiple languages. `reledpar` is the successor of the primitive `ledpar` package.

Peter Wilson also developed the `ledarab` package for handling parallel Arabic text in critical editions. However, this package is not maintained by Maïeul Rouquette. You should use the capabilities of a modern TeX processor, like Xe(La)TeX

I Implementation overview

We present the `reledmac` code in roughly the order in which it is used during a run of \TeX . The order is *exactly* that in which it is read when you load the `reledmac` package, because the same file is used to generate this manual and to generate the \LaTeX package file.

Most of what follows consists of macro definitions, but there are some commands that are executed immediately—especially at the start of the code. The documentation generally describes the code from the point of view of what happens when the macros are executed, though. As each macro is introduced, its name is printed in the margin.

After package options, we begin with the commands you use to start and stop line numbering in a section of text (Section II). Next comes the machinery for writing and reading the auxiliary file for each section that helps us count lines, and for creating list macros encoding the information from that file (Section V); this auxiliary file will be read at the start of each section, to create those list macros, and a new version of the file will be started to collect information from the body of the section.

Next are commands for marking sections of the text for footnotes (Section VI), followed by the macros that take each paragraph apart, attach the line numbers and insertions, and send the result to the vertical list (Section VII). The footnote commands (Section XIII) and output routine (Section XXIII) finish the main part of the processing; cross-referencing (Section XXV) and endnotes (Section XX) complete the story.

In what follows, macros with an `@` in their name are more internal to the workings of `reledmac` than those made up just of ordinary letters, just as in `PLAIN \TeX` (see *The TeXbook*, p. 344). You are meant to be able to make free with ordinary macros, but the “`@`” ones should be treated with more respect, and changed only if you are pretty sure of what you are doing.

II Preliminaries

II.1 Links with original `edmac`

Generally, these are the modifications to the original. `edmac` code:

- Replace as many `\def`’s by `\newcommand`’s as possible to avoid overwriting \LaTeX macros.
- Replace user-level \TeX counts by \LaTeX counters.
- Use the \LaTeX font handling mechanisms.
- Use \LaTeX messaging and file facilities.

II.2 Package declaration

Announce the name and version of the package, which is targetted for `LaTeX2e`.

```

1 %<*code>
2 \NeedsTeXFormat{LaTeX2e}
3 \ProvidesPackage{reledmac}[2020/12/20 v2.35.1 typesetting critical editions]
4 %

```

II.3 Package options

`\ifparledgroup` Use this to remember which option is used, set and execute the options with `final` as the default. We use `xkeyval` in order to manage options with argument.

```

\ifsameparallelpagenumber
\ifprevpgnotnumbered
\ifledfinal
\ifnocritical@
\if@noeled@sec
\ifnoend@

```

II.3.1 Options of `reledpar`

Here, we define some booleans specific to `reledpar` options, but which have consequences on `reledmac` internal commands.

```

\ifnofamiliar@
\ifnoledgroup@
\ifparapparatus@
\ifnoquotation@
\iflednopbinverse
\ifwidthliketwocolumns
\ifxindy@

```

II.3.2 Options of `reledmac`

```

\ifxindyhyperref@
\ifeledmaccompat@
\ifnoresetlinenumannotation@
\ifantilabe@
11 \DeclareOptionX{series}[A,B,C,D,E]{\xdef\default@series{#1}}
12 \ExecuteOptionsX{series}%
13
14 \newif\if@noeled@sec%
15 \DeclareOptionX{noeledsec}{\@noeled@sectrue}
16
17 \newif\ifnocritical@%
18 \DeclareOptionX{nocritical}{\nocritical@true}%
19
20 \newif\ifnofamiliar@%
21 \DeclareOptionX{nofamiliar}{\nofamiliar@true}%
22
23 \newif\ifnoledgroup@%
24 \DeclareOptionX{noledgroup}{\noledgroup@true}%
25
26 \newif\ifnoend@%
27 \DeclareOptionX{noend}{%
28   \let\l@dend@open\@gobble%
29   \let\l@dend@close\relax%
30   \global\let\l@dend@stuff=\relax%
31   \noend@true%
32 }%

```

```

33 \newif\ifnoquotation@
34 \DeclareOptionX{noquotation}{\noquotation@true}
35
36 \newif\ifledfinal
37 \DeclareOptionX{final}{\ledfinaltrue}
38 \DeclareOptionX{draft}{\ledfinalfalse}
39 \ExecuteOptionsX{final}
40
41 \newif\ifparapparatus@
42 \DeclareOptionX{parapparatus}{\parapparatus@true}
43
44 \newif\iflednopbinverse
45 \DeclareOptionX{nopbinverse}{\lednopbinversetrue}
46
47 \newif\ifwidthliketwocolumns%
48 \DeclareOptionX{widthliketwocolumns}{\widthliketwocolumnstrue}%
49
50 \newif\ifcontinuousnumberingwithcolumns
51 \DeclareOptionX{continuousnumberingwithcolumns}{\
52   continuousnumberingwithcolumnstrue}%
53
54 \newif\ifxindy@
55 \DeclareOptionX{xindy}[eledmac-markup-attr.xdy]{%
56   \AtBeginDocument{\immediate\openout\eledmac@xindy@out=#1}%
57   \newwrite\eledmac@xindy@out%
58   \xindy@true%
59   \gdef\eledmacmarkuplocdepth{:depth 1}%
60   \AtEndDocument{\immediate\closeout\eledmac@xindy@out}%
61 }%
62
63 \newif\ifxindyhyperref@
64 \DeclareOptionX{xindy+hyperref}{%
65   \xindyhyperref@true%
66 }%
67
68 \newif\ifeledmaccompat@%
69 \DeclareOptionX{eledmac-compat}{%
70   \eledmaccompat@true%
71 }%
72 \DeclareOptionX{nopenalties}{%
73   \AtBeginDocument{\let\add@penalties\relax}%
74 }
75 \def\l@auxdir{}%
76 \DeclareOptionX{auxdir}{%
77   \xdef\l@auxdir{#1}%
78 }%
79
80 \newif\ifsw@caseinsensitive%
81 \DeclareOptionX{swcaseinsensitive}{%

```

```

82 \sw@caseinsensitivetrue%
83 }%
84 \newif\ifnoresetlinenumannotation@
85 \DeclareOptionX{noresetlinenumannotation}{%
86   \noresetlinenumannotation@true%
87 }%
88 \newif\ifantilabe@%
89 \DeclareOptionX{antilabe}{%
90   \antilabe@true%
91 }%
92 %

```

We use the starred form of `\ProcessOptionsX` which executes options in the order listed in the source file: class options, then listed package options, so a package option can override a class option with the same name. This was suggested by Dan Luecking in the `ctt` thread *Class/package option processing*, on 27 February 2004.

```

93 \ProcessOptionsX*\relax
94
95 %

```

II.4 Loading packages

Loading package `xargs` to declare commands with optional arguments. Loading package `xparse` to declare fully expandable commands with optional argument. Ideally, we should use only `xparse` and not `xargs`. For historical reasons, we use both. `Etoolbox` is also used to make code clearer - for example, in dynamic command names (which can replace `\csname` etc.). Use suffix to declare commands with a starred version, `xstring` to work with strings, `ifluatex` and `ifxetex` to test if `LuaTeX` or `XgTeX` is running, and `ragged2e` to manage ragged justification for paragraphed notes.

```

96 \RequirePackage{xargs}
97 \RequirePackage{xparse}[2017/03/07]%
98 \RequirePackage{etoolbox}
99 \@ifl@t@r\fmtversion{2015/10/01}
100 {\ifboolexpr{not test{\@ifl@t@r\fmtversion{2016/03/31}}} or (test{\
101   ifdefstring{\fmtversion}{2016/03/31}} and test {\ifnumless{\patch@level
102     }{3}})}}%
103   {\PackageWarning{reledmac}{You are using a LaTeX version older than
104     2016/03/31 patch 3.%
105     \MessageBreak You are strongly encouraged to use a newer version.}}%
106   {}%
107 }%
108 {\RequirePackage{etex}%
109   \csname reserveinserts\endcsname{32}%
110 }%
111 \RequirePackage{suffix}
112 \RequirePackage{xstring}
113 \RequirePackage{ifluatex}
114 \RequirePackage{ragged2e}

```

```

112 \RequirePackage{ifxetex}%
113 %

```

II.5 Compatibility with LuaTeX

Here, we enable some primitives for LuaTeX.

```

114 \ifx\directlua\undefined\else%
115   \directlua{tex.enableprimitives("",{"texdir","pardir","bodydir"})}
116 \fi
117 \ifluatex%
118   \ifnum\luatexversion<110%
119     \PackageWarning{reledmac}{You need to use LuaTeX 1.1.0 or higher}{\@ehc}
120   }%
121   \fi%
122 \fi%
123 %

```

II.6 Boolean flags

`\ifl@dmemoir` Define a flag for if the memoir class has been used.

```

123 \newif\ifl@dmemoir
124 \@ifclassloaded{memoir}{\l@dmemoirtrue}{\l@dmemoirfalse}
125
126 %

```

`\if@ledgroup` Flag set to true inside a ledgroup environment.

```

127 \newif\if@ledgroup%
128 %

```

`\ifl@imakeidx` Define a flag for if the imakeidx package has been used.

```

129 \newif\ifl@imakeidx
130 \@ifpackageloaded{imakeidx}{\l@imakeidxtrue}{\l@imakeidxfalse}%False is the default value
131 %

```

`\ifl@indextools` Define a flag for if the indextools package has been used.

```

132 \newif\ifl@indextools%
133 \@ifpackageloaded{indextools}{%
134   \l@indextoolstrue%
135   \l@imakeidxtrue%
136   \let\imki@wrindexentry\indtl@wrindexentry%
137 }{}%
138 %

```

False is the default value. We consider `indextools` as a variant of `imakeidx`. That is why we set `\ifl@imakeidx` to true. We also let `\imki@wrindexentry` to `\indtl@wrindexentry`.

`\ifl@footmisc` Define a flag if the `footmisc` package has been loaded.

```
139 \newif\ifl@footmisc
140 \ifpackageloaded{footmisc}{\l@footmisctrue}{}%False is the default value
141 %
```

`\if@RTL` The `\if@RTL` is defined by the `bidi` package, which is sometimes loaded by *polyglossia*. But we define it as well if the `bidi` package is not loaded.

```
142 \ifdef{\if@RTL}{\newif\if@RTL}
143 %
```

`\if@firstlineofpage` `\if@firstlineofpage` is set to TRUE at the first line of every page. `\if@firstlineofpageR` is for the right side.

```
144 \newif\if@firstlineofpage%
145 \newif\if@firstlineofpageR%
146 %
```

II.7 Messages

All the messages are grouped here as macros. This saves \TeX 's memory when the same message is repeated and also lets them be edited easily.

`\reledmac@warning` Write a warning message.

```
147 \newcommand{\reledmac@warning}[1]{\PackageWarning{reledmac}{#1}}
148 %
```

`\reledmac@error` Write an error message.

```
149 \newcommand{\reledmac@error}[2]{\PackageError{reledmac}{#1}{#2}}
150 %
```

```
\led@err@NumberingStarted51 \newcommand*\led@err@NumberingStarted{%
```

```
\led@err@NumberingNotStarted52 \reledmac@error{Numbering has already been started}{\@ehc}}
```

```
\led@err@NumberingShouldHaveStarted53 \newcommand*\led@err@NumberingNotStarted{%
```

```
154 \reledmac@error{Numbering was not started}{\@ehc}}
```

```
155 \newcommand*\led@err@NumberingShouldHaveStarted{%
```

```
156 \reledmac@error{Numbering should already have been started}{\@ehc}}
```

```
157 %
```



```

\led@err@samewordRTL 58 \newcommand*{\led@err@samewordRTL}{%
159 \reledmac@error{You can't use \string\sameword \MessageBreak with XeLaTeX
\MessageBreak when typesetting RTL text.\MessageBreak Please use LuaTeX
instead.}\@ehc}%
160 }%
161 %

\led@err@edtextoutsidestart 62 \newcommand*{\led@err@edtextoutsidestart}{%
\led@err@PstartInEdtext 63 \reledmac@error{\string\edtext\space outside numbered paragraph (\pstart\
\led@err@PendInEdtext space ... \space\pend)}{\@ehc}}%
164
165 \newcommand{\led@err@PstartInEdtext}[1]{%
166 \reledmac@error{\string\pstart\space in \string\edtext\space #1 argument
}\@ehc}%
167 }%
168
169 \newcommand{\led@err@PendInEdtext}[1]{%
170 \reledmac@error{\string\pend\space in \string\edtext\space #1 argument}{\
@ehc}%
171 }%
172 %

\led@mess@NotesChanged 73 \newcommand*{\led@mess@NotesChanged}{%
174 \typeout{\reledmac reminder: }%
175 \typeout{ The number of the footnotes in this section
176 has changed since the last run.}%
177 \typeout{ You will need to run LaTeX two more times
178 before the footnote placement}%
179 \typeout{ and line numbering in this section are
180 correct.}}
181 %

\led@mess@SectionContinued 82 \newcommand*{\led@mess@SectionContinued}[1]{%
183 \message{Section #1 (continuing the previous section)}}
184 %

\led@err@LineationInNumbered 85 \newcommand*{\led@err@LineationInNumbered}{%
186 \reledmac@error{You can't use \string\lineation\space within
187 a numbered section}{\@ehc}}
188 %

\led@warn@BadLineation 89 \newcommand*{\led@warn@BadLineation}{%
\led@warn@BadLinenummargin 90 \reledmac@warning{Bad \string\lineation\space argument}}
\led@warn@BadLockdisp 91 \newcommand*{\led@warn@BadLinenummargin}{%
\led@warn@BadSubblockdisp

```

```

192 \reledmac@warning{Bad \string\linenummargin\space argument}}
193 \newcommand*{\led@warn@BadLockdisp}{%
194 \reledmac@warning{Bad \string\lockdisp\space argument}}
195 \newcommand*{\led@warn@BadSublockdisp}{%
196 \reledmac@warning{Bad \string\sublockdisp\space argument}}
197 %

```

```

\led@warn@NoFile98 \newcommand*{\led@warn@NoFile}[1]{%
199 \reledmac@warning{File `#1' not found}}
200 %

```

```

\led@warn@LineFileObsolete01 \newcommand*{\led@warn@Obsolete}[1]{%
202 \reledmac@warning{Line-list file #1 was obsolete. We have not read it.
Please run LaTeX again.}}
203 %

```

```

\led@warn@BadAdvancelineSubline04 \newcommand*{\led@warn@BadAdvancelineSubline}{%
\led@warn@BadAdvancelineLine05 \reledmac@warning{\string\advanceline\space produced a sub-line
206 number less than zero.}}
207 \newcommand*{\led@warn@BadAdvancelineLine}{%
208 \reledmac@warning{\string\advanceline\space produced a line
209 number less than zero.}}
210 %

```

```

\led@warn@BadSetline11 \newcommand*{\led@warn@BadSetline}{%
\led@warn@BadSetlinenum12 \reledmac@warning{Bad \string\setline\space argument}}
213 \newcommand*{\led@warn@BadSetlinenum}{%
214 \reledmac@warning{Bad \string\setlinenum\space argument}}
215 %

```

```

\led@err@PstartNotNumbered16 \newcommand*{\led@err@PstartNotNumbered}{%
\led@err@PstartInPstart17 \reledmac@error{\string\pstart\space must be used within a
\led@err@PendNotNumbered18 numbered section %
\led@err@PendNoPstart19 (\string\beginnumbering\space ...\space\string\
\led@err@AutoparNotNumbered endnumbering)}{\@ehc}}%
\led@err@NumberingWithoutPstart20 \newcommand*{\led@err@PstartInPstart}{%
221 \reledmac@error{\string\pstart\space encountered while another
222 \string\pstart\space was in effect}{\@ehc}}
223 \newcommand*{\led@err@PendNotNumbered}{%
224 \reledmac@error{\string\pend\space must be used within a
225 numbered section}{\@ehc}}
226 \newcommand*{\led@err@PendNoPstart}{%
227 \reledmac@error{\string\pend\space must follow a \string\pstart}{\@ehc}}
228 \newcommand*{\led@err@AutoparNotNumbered}{%

```

```

229 \reledmac@error{\string\autopar\space must be used within a
230         numbered section}{\@ehc}}
231 \newcommand*{\led@err@NumberingWithoutPstart}{%
232 \reledmac@error{\string\beginnumbering...\string\endnumbering\space
without \string\pstart}{\@ehc}}%
233 %

```

```

\led@warn@BadAction34 \newcommand*{\led@warn@BadAction}{%
235 \reledmac@warning{Bad action code, value \next@action.}}
236 %

```

```

\led@warn@DuplicateLabel237 \newcommand*{\led@warn@DuplicateLabel}[1]{%
ppLabelOutSecondArgEdtext238 \reledmac@warning{Duplicate definition of label `#1'\@gobble}%
\led@warn@RefUndefined239 \@latex@warning@no@line{Label `#1' multiply defined}%
\led@warn@RefUndefined240 }%
241 \newcommand*{\led@warn@AppLabelOutSecondArgEdtext}[1]{%
242 \reledmac@warning{\string\apptoc\space outside of the second argument
of an \string\edtext\space `#1' on page \thepage.}}%
243 \newcommand*{\led@warn@RefUndefined}[1]{%
244 \G@refundefinedtrue%
245 \reledmac@warning{Reference `#1' on page \thepage\space undefined.%
246         Using `000'.}%
247 \@latex@warning{Reference `#1' undefined\on@line}%
248 }%
249 \newcommand*{\led@warn@pairRefUndefined}[1]{%
250 \G@refundefinedtrue%
251 \reledmac@warning{Reference `#1:start' and/or `#1:end' on page \thepage\
space undefined.
252         Using `??'.}%
253 \@latex@warning{Reference `#1:start' and/or `#1:end' undefined\on@line}%
254 }
255 %

```

```

\led@warn@NoMarginpars56 \newcommand*{\led@warn@NoMarginpars}{%
257 \reledmac@warning{You can't use \string\marginpar\space in numbered text
}}
258 %

```

```

\led@warn@BadHookSeries59 \newcommand{\led@warn@BadHookSeries}[2]{%
260 \reledmac@warning{Bad series #1 for #2 hook. Skipped.}%
261 }%
262 %

```

```

\led@warn@BadSidenotemargin63 \newcommand*{\led@warn@BadSidenotemargin}{%
264 \reledmac@warning{Bad \string\sidenotemargin\space argument}}
265 %

```

```
\led@warn@NoIndexFile266 \newcommand*{\led@warn@NoIndexFile}[1]{%
267   \reledmac@warning{Undefined index file #1}}
268   %
```

```
\led@warn@SeriesStillExist269 \newcommand{\led@warn@SeriesStillExist}[1]{%
270   \reledmac@warning{Series #1 is still existing !}}%
271  }%
272   %
```

```
\led@err@BadAction273 \newcommand*{\led@err@StanzaIndentNotDefined}{%
274   \reledmac@error{You have not defined the indentation for the line \number
\stanza@count}{\@ehc}}%
275   %
```

```
\led@err@ManySidenotes276 \newcommand{\led@err@ManySidenotes}{%
\led@err@ManyLeftnotes277   \ifledRcol{%
\led@err@ManyRightnotes278     \reledmac@warning{\itemcount@space sidenotes on line \the\line@numR\
space p. \the\page@numR}%
279     \else%
280     \reledmac@warning{\itemcount@space sidenotes on line \the\line@num\
space p. \the\page@num}%
281     \fi%
282   }%
283   \newcommand{\led@err@ManyLeftnotes}{%
284     \ifledRcol{%
285       \reledmac@warning{\itemcount@space leftnotes on line \the\line@numR\
space p. \the\page@numR}%
286       \else%
287       \reledmac@warning{\itemcount@space leftnotes on line \the\line@num\
space p. \the\page@num}%
288       \fi%
289     }%
290   \newcommand{\led@err@ManyRightnotes}{%
291     \ifledRcol{%
292       \reledmac@warning{\itemcount@space rightnotes on line \the\line@numR\
space p. \the\page@numR}%
293       \else%
294       \reledmac@warning{\itemcount@space rightnotes on line \the\line@num\
space p. \the\page@num}%
295       \fi%
296     }%
297     %
```

```
\led@err@TooManyColumns298 \newcommand*{\led@err@TooManyColumns}{%
\led@err@UnequalColumns299   \reledmac@error{Too many columns}{\@ehc}}
\led@err@LowStartColumn
\led@err@HighEndColumn
\led@err@ReverseColumns
```

```

300 \newcommand*\led@err@UnequalColumns}{%
301   \reledmac@error{Number of columns is not equal to the number
302     in the previous row (or \protect\\ \space forgotten?)}{\@ehc}}
303 \newcommand*\led@err@LowStartColumn}{%
304   \reledmac@error{Start column is too low}{\@ehc}}
305 \newcommand*\led@err@HighEndColumn}{%
306   \reledmac@error{End column is too high}{\@ehc}}
307 \newcommand*\led@err@ReverseColumns}{%
308   \reledmac@error{Start column is greater than end column}{\@ehc}}
309 %

```

```

endnotes@outsidenumbering10 \newcommand\led@err@toendnotes@outsidenumbering}{%
311   \reledmac@error{\string\toendnotes\space and related commands must be
    called inside a numbered text (\string\beginnumbering\space ... \space\
    string\endnumbering)}{\@ehc}%
312 }%
313 %

```

```

err@EdtextWithoutFootnote14 \newcommand\led@err@EdtextWithoutFootnote}{%
315   \reledmac@error{edtext without Xfootnote. Check syntax}{\@ehc}%
316 }%
317 %

```

```

tnoteNotInSecondArgEdtext18 \newcommand\led@err@FootnoteNotInSecondArgEdtext}[1]{%
319   \reledmac@error{#1 footnote outside of the second argument of an edtext.
    Check syntax}{\@ehc}%
320 }%
321 %

```

```

error@PackageAfterEledmac22 \newcommand\led@error@PackageAfterEledmac}[1]{%
323   \reledmac@error{#1 must be loaded before reledmac}{\@ehc}%
324 }%
325 %

```

```

error@fail@patch@@makecol26 \newcommand\led@error@fail@patch@@makecol}{%
327   \reledmac@error{Fail to patch \string\@makecol\space command}{\@ehc}%
328 }%
329 %

```

```

ror@fail@patch@@reinserts30 \newcommand\led@error@fail@patch@@reinserts}{%
331   \reledmac@error{Fail to patch \string\@reinserts\space command}{\@ehc}%
332 }%
333 %

```

```

\led@error@fail@patch@@doclearpage34 \newcommand{\led@error@fail@patch@@doclearpage}{%
335 \reledmac@error{Fail to patch \string\@doclearpage\space command}{\@ehc}%
336 }%
337 %

\led@error@fail@patch@@iiiminipage38 \newcommand{\led@error@fail@patch@@iiiminipage}{%
339 \reledmac@error{Fail to patch \string\@iiiminipage\space command}{\@ehc}%
340 }%
341 %

\led@error@fail@patch@endminipage42 \newcommand{\led@error@fail@patch@endminipage}{%
343 \reledmac@error{Failed to patch the \string\endminipage\space command}{\@ehc}%
344 }%
345 %

\led@error@fail@patch@endminipage46 \newcommand{\led@error@fail@patch@makeindex}{%
347 \reledmac@error{Failed to patch the \string\makeindex\space command}{\@ehc}%
348 }%
349 %

\led@error@fail@patch@setcounter50 \newcommand{\led@error@fail@patch@setcounter}{%
351 \reledmac@error{Failed to patch the \string\setcounter\space command}{\@ehc}%
352 }%
353 %

\led@error@fail@patch@addtocounter54 \newcommand{\led@error@fail@patch@addtocounter}{%
355 \reledmac@error{Failed to patch the \string\addtocounter\space command}{\@ehc}%
356 }%
357 %

358 \newcommand{\led@error@fail@patch@stepcounter}{%
359 \reledmac@error{Failed to patch the \string\stepcounter\space command}{\@ehc}%
360 }%
361 %

\led@warn@edinde@outsidenumbering62 \newcommand{\led@warn@edinde@outsidenumbering}{%
363 \reledmac@warning{\string\edindex\space called outside of \string\beginnumbering\space ... \space \string\endnumbering. \MessageBreak Automatically switched to \string\index.}%
364 }%
365 %

```

```

warning@hsizeX@deprecated 366 \newcommand{\led@warning@hsizeX@deprecated}{%
367 \reledmac@warning{\string\hsizeX\space command deprecated, use \string\
widthX\space instead.}%
368 }%
369 %

```

```

warning@Xhsize@deprecated 370 \newcommand{\led@warning@Xhsize@deprecated}{%
371 \reledmac@warning{\string\Xhsize\space command deprecated, use \string\
Xwidth\space instead.}%
372 }%
373 %

```

```

warning@msdatawithoutstop 374 \newcommand{\led@warning@msdatawithoutstop}{%
375 \reledmac@warning{\string\msdata\space without corresponding \string\
stopmsdata}%
376 }%
377 %

```

```

ning@preXnotes@deprecated 378 \newcommand{\led@warning@preXnotes@deprecated}{%
379 \reledmac@warning@preXnotes@deprecated%
380 }%
381 %

```

II.8 Gobbling

Here, we define some commands which gobble their arguments.

```

\@gobblethree 382 \providecommand*\@gobblethree}[3]{}
\@gobblefour 383 \providecommand*\@gobblefour}[4]{}
\@gobbleseven 384 \providecommand*\@gobbleseven}[7]{}
385 %

```

II.9 Wrapping content

```

\l@wrap@ifnotemptybox
\l@wrap@cs@ifnotemptybox

```

The `\l@wrap@ifnotemptybox` macro wraps its second argument in the command passed as the first argument, but only if the second argument does not produce an empty box. That is useful for example when we need to wrap something on a `\textsuperscript`.

Indeed `ab` does not produce the same typographical result as `ab`.²⁸ The `\l@wrap@cs@ifnotemptybox` does the same, but take as argument a control sequence name, so without backslash.

²⁸Compare the distance between letters in the first case (`ab`) and in the second one (`ab`).

```

386 \newcommand{\l@wrap@ifnotemptybox}[2]{%
387   \setbox0=\hbox{#2}%
388   \ifdim\wd0=\z@ \else%
389     #1{#2}%
390   \fi%
391 }%
392 \newcommand{\l@wrapcs@ifnotemptybox}[2]{%
393   \l@wrap@ifnotemptybox{\csname #1\endcsname}{#2}%
394 }%
395 %

```

II.10 Miscellaneous commands

`\showlemma` `\showlemma{<lemma>}` typesets the lemma text in the body. It depends on the option.

```

396 \ifledfinal
397   \newcommand*{\showlemma}[1]{#1}
398 \else
399   \newcommand*{\showlemma}[1]{\textbf{#1}}%
400 \fi
401
402 %

```

`\linenumberlist` The code for the `\linenumberlist` mechanism was given to Peter Wilson by Wayne Sullivan on 2004/02/11.

Initialize it as `\empty`.

```

403 \let\linenumberlist=\empty
404
405 %

```

`\@l@tempcnta` In imitation of \TeX , we create a couple of scratch counters.

`\@l@tempcntb` \TeX already defines `\@tempcnta` and `\@tempcntb` but Peter Wilson found in the past that it can be dangerous to use these (for example one of the AMS packages did something nasty to the `ccaption` package's use of one of these).

```

406 \newcount\@l@tempcnta \newcount\@l@tempcntb
407 %

```

II.11 Prepare reledpar

`\ifl@dpairing` In preparation for the `reledpar` package, these are related to the “right” text of parallel
`\ifl@dpaging` texts (when `\ifl@dpairing` is TRUE). They are explained in the `reledpar` manual.
`\ifl@dprintingpages`
`\ifl@dprintingcolumns` `\newif\ifl@dpairing`
`\ifpst@rtedL` `\newif\ifl@dpaging%`
`\l@dnumpstartsL` `\newif\ifl@dprintingpages%`


```
411 \newif\ifl@dprintingcolumns%
412 \newif\ifpst@rtedL
413 \newcount\l@dnumpstartsL
414 %
```

`\ifledRcol` `\ifledRcol` is set to true in the Rightside environnement. It must be not confused with `\ifledRcol@` which is set to true when a right line is processed, in `\Pages` or `\Columns`.

```
415 \newif\ifledRcol
416 \newif\ifledRcol@
417 %
```

`\ifnumberingR` The `\ifnumberingR` flag is set to true if we're within a right text numbered section.

```
418 \newif\ifnumberingR
419 %
```

`\ifafterendnumberingR` The `\ifafterendnumberingR` boolean is set to TRUE at `\endnumberingR` and to FALSE at next `\beginnumberingR` or real `\beginnumbering` (not `\resumenummering`). It is mainly used for the `continuousnumberingwithcolumns`, to avoid incrementing right column line counters after a `\endnumberingR`.

```
420 \newif\ifafterendnumberingR%
421 %
```

The `\ifXnote@` macro is set to true when we are typesetting a critical footnote.

```
422 \newif\ifXnote@%
423 %
```

II.12 Booleans provided by other optional packages which are required in any case

`\ifindtl@innote` `\ifindtl@innote` and `\ifindtl@notenumber` are required even if `indextools` is not used.

```
424 \providebool{indtl@innote}%
425 \providebool{indtl@notenumber}%
426 %
```

`ifinstanzaL` `ifinstanzaR` These boolean tests are switched by the `\stanza` command, using either the left or right side.

```
427 \newif\ifinstanzaL%
428 \newif\ifinstanzaR%
429 %
```

`ifinastanzaL` These boolean tests are switched by the `astanza` environment, using either the left
`ifinastanzaR` or right side.

```
430 \newif\ifinastanzaL%
431 \newif\ifinastanzaR%
432 %
```

III Sectioning commands

`\section@num` You use `\beginnumbering` and `\endnumbering` to begin and end a line-numbered section of the text; the pair of commands may be used as many times as you like within one document to start and end multiple, separately line-numbered sections. \TeX will maintain and display a “section number” as a count named `\section@num` that counts how many `\beginnumbering` and `\resumenumbering` commands have appeared; it need not be related to the logical divisions of your text.

`\extensionchars` Each section will read and write an associated “line-list file”, containing information used to do the numbering; the file will be called `\jobname.nn`, where `nn` is the section number. However, you may direct that an extra string be added before the `nn` in that filename, in order to distinguish these temporary files from others: that string is called `\extensionchars`. Initially it’s empty, since different operating systems have greatly varying ideas about what characters are permitted in file names. So `\renewcommand{\extensionchars}{-}` gives temporary files called `jobname.-1`, `jobname.-2`, etc.

```
433 \newcount\section@num
434 \section@num=0
435 \let\extensionchars=\empty
436 %
```

`\ifnumbering` The `\ifnumbering` flag is set to true if we are within a numbered section (that is,
`\numberingtrue` between `\beginnumbering` and `\endnumbering`). You can use `\ifnumbering` in your
`\numberingfalse` own code to check whether you are in a numbered section, but do not change the flag’s value.

```
437 \newif\ifnumbering
438 %
```

`\beginnumbering` `\beginnumbering` begins a section of numbered text. When it is executed we increment
`\initnumbering@reg` the section number, initialize our counters, send a message to your terminal, and call macros to start the lineation machinery and endnote files.

The initializations here are trickier than they look. `\line@list@stuff` will use all of the counters that are zeroed here when it assembles the line-list and other lists of information about the lineation. But it will do all of this locally and within a group, and when it is done the lists will remain but the counters will return to zero. Those same counters will then be used as we process the text of this section, but the assignments will be made globally. These initializations actually apply to both uses, though in all

other respects there should be no direct interaction between the use of these counters and variables in the two processing steps. For parallel processing:

- zero \l@dnumpstartsL — the number of chunks to be processed.
- set \ifpst@rtedL to FALSE.

```

439 \newcommand*{\beginnumbering}{%
440   \ifnumbering
441     \led@err@NumberingStarted
442   \endnumbering
443 \fi
444 \global\numberingtrue
445 \global\afterendnumberingRfalse%
446 \global\advance\section@num \@ne
447 \initnumbering@reg
448 \message{Section \the\section@num }%
449 \line@list@stuff{\jobname.\extensionchars\the\section@num}%
450 \ifcontinuousnumberingwithcolumns%
451   \unless\ifafterendnumberingR%
452     \unless\ifl@dpairing%
453       \ledRcoltrue%
454       \global\advance\section@numR \@ne%
455       \message{Section \the\section@numR R (continuousnumbering)}%
456       \line@list@stuffR{\jobname.\extensionchars\the\section@numR R}%
457       \ledRcolfalse%
458     \fi%
459   \fi%
460 \fi%
461 \l@dend@stuff
462 \setcounter{pstart}{1}
463 \ifl@dpairing
464   \global\l@dnumpstartsL \z@
465   \global\pst@rtedLfalse
466 %

```

The tools for section's title commands are called:

- Define an empty list of pstart number where sectioning commands are called.
- Input auxiliary file with the description of section titles.
- Open the same auxiliary file to write in.

```

467 \else
468   \begingroup
469   \global\@afterindenttrue%In order to reestablish normal feature if the \
  begingroup was not here
470   \initnumbering@quote
471   \ifwidthliketwocolumns%
472     \setwidthliketwocolumns%

```

```

473     \csuse{setpositionliketwocolumns@\columns@position}%
474     \fi%
475 \fi
476 \gdef\eled@sections@@{}%
477 \if@noeled@sec\else%
478     \makeatletter%
479     \InputIfFileExists%
480         {\l@auxdir\jobname.eledsec\the\section@num}%
481         {}%
482         {\led@warn@NoFile{\l@auxdir\jobname.eledsec\the\section@num}}%
483     \makeatother%
484     \immediate\openout\eled@sectioning@out=\l@auxdir\jobname.eledsec\the\
section@num\relax%
485     \fi%
486 }
487 \newcommand*\initnumbering@reg{%
488     \global\pst@rtedLfalse
489     \global\l@dnumpstartsL \z@
490     \global\absline@num \z@
491     \gdef\normal@page@break{}
492     \gdef\l@prev@pb{}
493     \gdef\l@prev@nopb{}
494     \global\line@num \z@
495     \global\subline@num \z@
496     \global\@lock \z@
497     \global\sub@lock \z@
498     \global\sublines@false
499     \global\let\next@page@num=\relax
500     \global\let\this@section@next@page@num=\relax%
501     \global\let\sub@change=\relax
502     \global\last@page@num=-10000%
503     \ifdefined\line@numR%
504         \line@numR=\z@%
505         \last@page@numR=\z@%
506     \fi%
507     \resetprevline@
508     \resetprevpage@num
509     \global\stopmsdata@inserted@true%
510     \global\let\@msdata@list\relax%
511     \global\csundef{\@msdata@\add@msd@c @data}%
512 }
513
514 %

```

`\endnumbering` `\endnumbering` must follow the last text for a numbered section. It takes care of notifying you when changes have been noted in the input that require running the file through again to move everything to the right place. We define it using `\def` and not `\newcommand` because \TeX does not allow defining command whose name starts by “end” except if we are currently creating an environment, which is not the case here.

```

515 \def\endnumbering{%
516   \ifnumbering
517     \global\numberingfalse
518     \normal@pars
519     \ifnum\l@dnumstartsL=0%
520       \led@err@NumberingWithoutPstart%
521     \fi%
522 %

```

For the continuousnumberingwithcolumn options, we need to store a global value for the next \endnumbering. We don't modify this counter globally, because that creates problem for nested \edtext.

```

523   \global\page@num=\this@section@page@num%
524   \global\last@page@num=\this@section@last@page@num%
525   \global\let\next@page@num\this@section@next@page@num%
526   \ifl@dpairing
527     \global\pst@rtedLfalse
528   \else
529     \ifx\insertlines@list\empty\else
530       \global\noteschanged@true
531     \fi
532     \ifx\line@list\empty\else
533       \global\noteschanged@true
534     \fi
535   \fi
536   \ifnoteschanged@
537     \led@mess@NotesChanged
538   \fi
539   \else
540     \led@err@NumberingNotStarted
541   \fi
542   \autoparfalse
543   \if@noeled@sec\else%
544     \immediate\closeout\eled@sectioning@out%
545   \fi%
546   \ifl@dpairing\else
547     \global\l@dnumstartsL=\z%
548   \endgroup
549 \fi
550 }
551 %

```

`\pausenumbering` The `\pausenumbering` macro is just the same as `\endnumbering`, but with the `\ifnumbering` flag set to true, to show that numbering continues across the gap.²⁹ The `\ifresumenumbering@start` `\pausenumbering@page@num` counter stores the `\this@section@next@page@num` when the `\pause@numbering` is called.

```

552 \newcount\pausenumbering@page@num%

```

²⁹Peter Wilson's thanks to Wayne Sullivan, who suggested the idea behind these macros.

```

553 \newcommand{\pausenumbering}{%
554   \ifx\this@section@next@page@num\relax%
555     \global\pausenumbering@page@num=0%
556   \else%
557     \global\pausenumbering@page@num=\this@section@next@page@num%
558   \fi%
559   \ifautopar\global\autopar@pausettrue\fi%
560   \endnumbering\global\numberingtrue}
561 %

```

The `\resumenumbering` macro is a bit more involved, but not much. It does most of the same things as `\beginnumbering`, but without resetting the various counters. Note that no check is made by `\resumenumbering` to ensure that `\pausenumbering` was actually invoked. The boolean `\ifresumenumbering@start` is set to true. That allows us to avoid resetting the line number at the first line of `\resumenumbering` if the lineation is by page. This boolean is set to false after the first action.

```

562 \newif\ifresumenumbering@start%
563 \newcommand*{\resumenumbering}{%
564   \ifnumbering
565     \ifautopar@pause\autopar\fi
566     \global\pst@rtedLtrue
567     \global\advance\section@num \@ne
568     \global\resumenumbering@starttrue%
569     \led@mess@SectionContinued{\the\section@num}%
570     \set@continuousnumberingforL%
571     \line@list@stuff{\jobname.\extensionchars\the\section@num}%
572     \ifcontinuousnumberingwithcolumns%
573       \unless\ifafterendnumberingR%
574         \unless\ifl@dpairing%
575           \ledRcoltrue%
576           \global\advance\section@numR \@ne%
577           \message{Section \the\section@numR R (continuoousnumbering)}%
578           \line@list@stuffR{\jobname.\extensionchars\the\section@numR R}%
579           \ledRcolfalse%
580         \fi%
581       \fi%
582     \fi%
583     \l@dend@stuff
584     \ifl@dpairing\else%
585       \begingroup%
586       \initnumbering@quote%
587       \ifwidthliketwocolumns%
588         \setwidthliketwocolumns%
589         \csuse{setpositionliketwocolumns@\columns@position}%
590       \fi%
591     \fi%
592   \else
593     \led@err@NumberingShouldHaveStarted
594   \endnumbering

```

```

595 \beginnumbering
596 \fi}
597
598
599 %

```

`\set@continuousnumberingforL` `\set@continuousnumberingforl` sets `pstart` counters at a `\beginnumbering` or a `\resumenumbering` in order to have continuous numbering with single column text.

```

600 \newcommand{\set@continuousnumberingforL}{%
601 \ifcontinuousnumberingwithcolumns%
602 \ifl@dpairing%
603 \unless\ifl@dpaging%
604 \global\c@pstartL=\c@pstart%
605 \fi%
606 \fi%
607 \fi%
608 }%
609 %

```

IV List macros

We will make heavy use of lists of information, which will be built up and taken apart by the following macros; they are adapted from *The TeXbook*, pp. 378–379, which discusses their use in more detail.

These macros consume a large amount of the run-time of this code. We intend to replace them in a future version, and in anticipation of doing so have defined their interface in such a way that it is not sensitive to details of the underlying code.

The historical list tools of `ledmac` are kept, because in many cause there are more useful than `etoolbox`’s lists. They allows to get and delete the first element of a list in one operation. They also expands the items add to the list.

However, `etoolbox`’s lists are more useful to loop on them. Consequently, depending on what we need, we use one or other.

It could be nice to unify them to the \LaTeX 3 list, however such migration would take quite time with some risk of error, for a gain which will be minor.

`\list@create` The `\list@create` macro creates a new list. This macro does not do anything beyond initializing an empty list macro.

```

610 \newcommand*{\list@create}[1]{%
611 \global\let#1=\empty%
612 }%
613 %

```

`\list@clear` The `\list@clear` macro just initializes a list to the empty list; it is no different from `\list@create` in its effect, but it is in its semantic .

```

614 \newcommand*{\list@clear}[1]{%
615   \global\let#1=\empty%
616 }
617 %

```

\xright@appenditem \xright@appenditem expands an item and appends it to the right end of a list macro.
\led@toksa We want the expansion because we will often be using this to store the current value
\led@toksb of a counter. \xright@appenditem creates global control sequences, like \xdef, and
 uses two temporary token-list registers, \@toksa and \@toksb.

```

618 \newtoks\led@toksa \newtoks\led@toksb
619 \global\led@toksa={\}
620 \long\def\xright@appenditem#1\to#2{%
621   \global\led@toksb=\expandafter{#2}%
622   \xdef#2{\the\led@toksb\the\led@toksa\expandafter{#1}}%
623   \global\led@toksb={}}
624 %

```

\xleft@appenditem \xleft@appenditem expands an item and appends it to the left end of a list macro; it
 is otherwise identical to \xright@appenditem.

```

625 \long\def\xleft@appenditem#1\to#2{%
626   \global\led@toksb=\expandafter{#2}%
627   \xdef#2{\the\led@toksa\expandafter{#1}\the\led@toksb}%
628   \global\led@toksb={}}
629 %

```

\gl@p The \gl@p macro removes the leftmost item from a list and places it in a control sequence. You type \gl@p\l\to\z (where \l is the list macro, and \z receives the left item). \l is assumed nonempty: use \ifx\l\empty to test for an empty \l. The control sequences created by \gl@p are all global.

```

630 \def\gl@p#1\to#2{\expandafter\gl@poff#1\gl@poff#1#2}
631 \long\def\gl@poff\#1#2\gl@poff#3#4{\gdef#4{#1}\gdef#3{#2}}
632
633 %

```

V Line counting

V.1 Choosing the system of lineation

Line number can be reset at each section (default) ; at each page ; at each pstart. Here we define internal codes for these systems and the macros.

The \ifbypage@ and \ifbypstart@ flag specify the current lineation system:

```

\ifbypstart@
\byppstart@true
\byppstart@false
  \ifbypage@
    \bypage@true
    \bypage@false

```

- line-of-page: byppstart@ = false and bypage@ = true.
- line-of-pstart: byppstart@ = true and bypage@ = false.

reledmac will use the line-of-section system unless instructed otherwise.

```
634 \newif\ifbypage@
635 \newif\ifbypstart@
636 %
```

The \ifbypage@R and \ifbypstart@R flag specify the current lineation for right side in case of using reledpar. They are now defined because they are used in some specific code. reledpar will use the line-of-section system unless instructed otherwise.

```
\ifbypage@R37 \newif\ifbypage@R
\ifbypstart@R38 \newif\ifbypstart@R
639 %
```

\lineation \lineation{<word>} is the macro you use to select the lineation system. Its argument is a string: either page, section or pstart.

```
640 \newcommand*{\lineation}[1]{%
641 %
```

We can't change the lineation system inside numbering section.

```
642 \ifnumbering
643 \led@err@LineationInNumbered
644 \else
645 %
```

If the argument is page.

```
646 \def\@tempa{#1}\def\@tempb{page}%
647 \ifx\@tempa\@tempb
648 \global\bypage@true
649 \global\bypstart@false
650 \unless\ifnocritical@%
651 \Xpstart[] [false]%
652 \fi%
653 %
```

If the argument is pstart.

```
654 \else
655 \def\@tempb{pstart}%
656 \ifx\@tempa\@tempb
657 \global\bypage@false
658 \global\bypstart@true
659 \unless\ifnocritical@%
660 \Xpstart%
661 \fi%
662 %
```

And finally, if the argument is section (default).

```

663     \else
664         \def\@tempb{section}
665         \ifx\@tempa\@tempb
666             \global\bypage@false
667             \global\bystart@false
668             \unless\ifnocritical@%
669                 \Xpstart[] [false]%
670             \fi%
671 %

```

In other case, it is an error.

```

672     \else
673         \led@warn@BadLineation
674     \fi
675 \fi
676 \fi
677 \fi}}
678 %

```

V.2 Line number margin

`\linenummargin` `\linenummargin{<word>}` specify which margin line numbers are in; it takes one argument, a string, which value can be left ; right; inner or outer.

`\line@margin` The selection is recorded in the count `\line@margin`: 0 for left, 1 for right, 2 for outer, and 3 for inner.

`\l@dgetline@margin`

```

679 \newcount\line@margin%
680 \newcount\line@margin@columns%Only for parallel typesetting
681 \line@margin@columns=\m@ne%
682
683 \newcommand*{\linenummargin}[1]{%
684     \l@dgetline@margin{#1}%
685     \ifnum\@l@dttempcntb>\m@ne
686         \ifledRcol
687             \global\line@marginR=\@l@dttempcntb
688             \led@warn@setting@in@rightside{\linenummargin}%
689         \else
690             \global\line@margin=\@l@dttempcntb
691         \fi
692     \fi}}
693
694 \newcommand*{\l@dgetline@margin}[1]{%
695     \def\@tempa{#1}\def\@tempb{left}%
696     \ifx\@tempa\@tempb
697         \@l@dttempcntb \z@
698     \else
699         \def\@tempb{right}%
700         \ifx\@tempa\@tempb
701             \@l@dttempcntb \@ne

```

```

702 \else
703 \def\@tempb{outer}%
704 \ifx\@tempa\@tempb
705 \l@dttempcntb \tw@
706 \else
707 \def\@tempb{inner}%
708 \ifx\@tempa\@tempb
709 \l@dttempcntb \thr@@
710 \else
711 \led@warn@BadLinenummargin
712 \l@dttempcntb \m@ne
713 \fi
714 \fi
715 \fi
716 \fi}
717
718 %

```

V.3 Line number initialization and increment

`\c@firstlinenum` The following counters tell `reledmac` which lines should be printed with line numbers. `firstlinenum` is the number of the first line in each section that gets a number; `linenumincrement` is the difference between successive numbered lines. The initial values of these counters produce labels on lines 5, 10, 15, etc. `linenumincrement` must be at least 1.

```

719 \newcounter{firstlinenum}
720 \setcounter{firstlinenum}{5}
721 \newcounter{linenumincrement}
722 \setcounter{linenumincrement}{5}
723 %

```

`\c@firstsublinenum` The following parameters are just like `firstlinenum` and `linenumincrement`, but for sub-line numbers. `sublinenumincrement` must be at least 1.

```

724 \newcounter{firstsublinenum}
725 \setcounter{firstsublinenum}{5}
726 \newcounter{sublinenumincrement}
727 \setcounter{sublinenumincrement}{5}
728
729 %

```

`\firstlinenum` These macros can be used to set the corresponding counters.

```

\linenumincrement
\firstsublinenum
\sublinenumincrement
730 \newcommand*{\firstlinenum}[1]{%
731 \ifledRcol%
732 \setcounter{firstlinenumR}{#1}%
733 \led@warn@setting@in@rightside{\firstlinenum}%
734

```

```

735 \else%
736 \setcounter{firstlinenum}{#1}%
737 \fi%
738 }
739 \newcommand*\linenumincrement}[1]{%
740 \ifledRcol%
741 \setcounter{linenumincrementR}{#1}%
742 \led@warn@setting@in@rightside{\linenumincrement}%
743 \else%
744 \setcounter{linenumincrement}{#1}%
745 \fi%
746 }
747 \newcommand*\firstsublinenum}[1]{%
748 \ifledRcol%
749 \setcounter{firstsublinenumR}{#1}%
750 \led@warn@setting@in@rightside{\firstsublinenum}%
751 \else%
752 \setcounter{firstsublinenum}{#1}%
753 \fi%
754 }
755 \newcommand*\sublinenumincrement}[1]{%
756 \ifledRcol%
757 \setcounter{sublinenumincrementR}{#1}%
758 \led@warn@setting@in@rightside{\sublinenumincrement}%
759 \else%
760 \setcounter{sublinenumincrement}{#1}%
761 \fi%
762 }
763 %
764 %

```

V.4 Line number locking

`\lockdisp` When line locking is being used, the `\lockdisp{⟨word⟩}` macro specifies whether a line number—if one is due to appear—should be printed on the first printed line or on the last, or by all of them. Its argument is a word, either `first`, `last`, or `all`. Initially, it is set to `first`.

`\lock@disp` encodes the selection: 0 for first, 1 for last, 2 for all.

```

765 \newcount\lock@disp
766 \newcommand*\lockdisp}[1]{%
767 \l@getlock@disp{#1}%
768 \ifnum\l@dttempcntb>\m@ne
769 \global\lock@disp=\l@dttempcntb
770 \else
771 \led@warn@BadLockdisp
772 \fi}}
773 \newcommand*\l@getlock@disp}[1]{
774 \def\@tempa{#1}\def\@tempb{first}%

```

```

775 \ifx\@tempa\@tempb
776 \l@dttempcntb \z@
777 \else
778 \def\@tempb{last}%
779 \ifx\@tempa\@tempb
780 \l@dttempcntb \@ne
781 \else
782 \def\@tempb{all}%
783 \ifx\@tempa\@tempb
784 \l@dttempcntb \tw@
785 \else
786 \l@dttempcntb \m@ne
787 \fi
788 \fi
789 \fi}
790
791 %

```

`\sublockdisp` The same questions about where to print the line number apply to sub-lines, and these are the analogous macros for dealing with the problem.

```

792 \newcount\sublock@disp
793 \newcommand{\sublockdisp}[1]{\%
794 \l@dgetlock@disp{#1}%
795 \ifnum\l@dttempcntb>\m@ne
796 \global\sublock@disp=\l@dttempcntb
797 \else
798 \led@warn@BadSublockdisp
799 \fi}}
800
801 %

```

V.5 Line number style

`\linenumberstyle` We provide a mechanism for using different representations of the line numbers, not just the normal arabic.

`\linenumrep`

`\linenumr@p`

`\sublinenumberstyle`

`\sublinenumrep`

`\sublinenumr@p`

NOTE: In v0.7 `\linenumrep` and `\sublinenumrep` replaced the internal `\linenumr@p` and `\sublinenumr@p`.

`\linenumberstyle` and `\sublinenumberstyle` are user level macros for setting the number representation (`\linenumrep` and `\sublinenumrep`) for line and sub-line numbers.

```

802 \newcommand*{\linenumberstyle}[1]{\%
803 \def\linenumrep##1{\@nameuse{@#1}{##1}}}
804 \newcommand*{\sublinenumberstyle}[1]{\%
805 \def\sublinenumrep##1{\@nameuse{@#1}{##1}}}
806 %

```

Initialise the number styles to arabic.

```

807 \linenumberstyle{arabic}
808 \let\linenumr@p\linenumrep
809 \sublinenumberstyle{arabic}
810 \let\sublinenumr@p\sublinenumrep
811
812 %

```

V.6 Line number printing

`\leftlinenum` `\rightlinenum` and `\rightlinenum` are the macros that are called to print marginal line numbers on a page, for left- and right-hand margins respectively. They are made easy to access and change, since you may want to change the styling in some way. These standard versions illustrate the general sort of thing that will be needed; they are based on the `\leftheadline` macro in *The TeXbook*, p. 416.

Whatever these macros output gets printed in a box that will be put into the appropriate margin without any space between it and the line of text. You will generally want a kern between a line number and the text, and `\linenumsep` is provided as a standard way of storing its size. Line numbers are usually printed in a smaller font, and `\numlabfont` is provided as a standard name for that font. When called, these macros will be executed within a group, so font changes and the like will remain local.

`\ledlinenum` typesets the line (and subline) number.

The original `\numlabfont` specification is equivalent to the \TeX `\scriptsize` for a 10pt document.

```

813 \newlength{\linenumsep}
814 \setlength{\linenumsep}{1pc}
815 \newcommand*{\numlabfont}{\normalfont\scriptsize}
816 \newcommand*{\ledlinenum}{%
817   \bgroup%
818   \ifluatex%
819     \texdir TLT%
820   \fi%
821   \numlabfont%
822   \unless\iflinenumannotationotherside%
823     \ifdefstring{\Xlinenumannotationposition@side}{before}{%
824       \l@wrap@ifnotemptybox{\Xwraplinenumannotation@side}{%
825         \csuse{annot@the\absline@num @the\section@num}%
826       }%
827     }%
828   \fi%
829   \linenumrep{\line@num}%
830   \ifsublines@
831     \ifnum\subline@num>0\relax
832       \unskip%
833       \Xsublinesep@side%
834       \sublinenumrep{\subline@num}%
835     \fi
836   \fi%

```

```

837 \unless\iflinenumannotationotherside%
838 \ifdefstring{\Xlinenumannotationposition@side}{after}{%
839 \l@wrap@ifnotemptybox{\Xwraplinenumannotation@side}{%
840 \csuse{annot@the\absline@num @the\section@num}%
841 }%
842 }%
843 \fi%
844 \egroup%
845 }%
846
847 \newcommand*{\leftlinenum}{%
848 \ledlinenum%
849 \kern\linenumsep%
850 }%
851 \newcommand*{\rightlinenum}{%
852 \kern\linenumsep%
853 \ledlinenum%
854 }%
855
856 %

```

`\leftlinenumannotation` The `\leftlinenumannotation` and `\rightlinenumannotation` prints the line number annotation; when user-defined it must be printed on the side opposite the main line number.

```

857 \newcommand*{\leftlinenumannotation}{%
858 \l@wrap@ifnotemptybox{\Xwraplinenumannotation@side}{%
859 \csuse{annot@the\absline@num @the\section@num}%
860 }%
861 \kern\linenumsep%
862 }%
863 \newcommand*{\rightlinenumannotation}{%
864 \kern\linenumsep%
865 \l@wrap@ifnotemptybox{\Xwraplinenumannotation@side}{%
866 \csuse{annot@the\absline@num @the\section@num}%
867 }%
868 }%
869 %

```

V.7 Line number counters and lists

Footnote references using line numbers rather than symbols can't be generated in one pass, because we do not know the line numbers till we ship out the pages. It would be possible if footnotes were never keyed to more than one line; but some footnotes gloss passages that may run for several lines, and they must be tied to the first line of the passage glossed. And even one-line passages require two passes if we want line-per-page numbering rather than line-per-section numbering.

So we run \LaTeX over the text several times, and each time save information about page and line numbers in a “line-list file” to be used during the next pass. At the start of

each section—whenever `\beginnumbering` is executed—the line-list file for that section is read, and the information from it is encoded into a few list macros.

We need first to define the different line numbers that are involved in these macros, and the associated counters.

`\line@num` The count `\line@num` stores the line number that is used in marginal line numbering and in notes: counting either by section, page or pstart, depending on your choice for this section. This may be qualified by `\subline@num`.

```
870 \newcount\line@num
871 %
```

`\subline@num` The count `\subline@num` stores a sub-line number that qualifies `\line@num`. For example, line 10 might have sub-line numbers 1, 2 and 3, which might be printed as lines 10.1, 10.2, 10.3.

```
872 \newcount\subline@num
873 %
```

`\ifsublines@` We maintain an associated flag, `\ifsublines@`, to tell us whether we’re within a sub-line range or not.

`\sublines@true` You may wonder why we do not just use the value of `\subline@num` to determine this—treating anything greater than 0 as an indication that sub-lineation is on. We need a separate flag because sub-lineation can be used together with line-number locking in odd ways: several pieces of a logical line might be interrupted by pieces of sub-lineated text, and those sub-line numbers should not return to zero until the next change in the major line number. This is common in the typesetting of English Renaissance verse drama, in which stage directions are given sub-line numbers: a single line of verse may be interrupted by several stage directions.

`\sublines@false`

```
874 \newif\ifsublines@
875 %
```

`\absline@num` The count `\absline@num` stores the absolute number of lines since the start of the section: that is, the number we have actually printed, no matter what numbers we attached to them. This value is never printed on an output page, though `\line@num` will often be equal to it. It is used internally to keep track of where notes are to appear and where new pages start: using this value rather than `\line@num` is a lot simpler, because it does not depend on the lineation system in use.

```
876 \newcount\absline@num
877 %
```

We will call `\absline@num` numbers “absolute” numbers, and `\line@num` and `\subline@num` numbers “visible” numbers.

V.8 Line number locking counter

`\@lock` The counts `\@lock` and `\sub@lock` tell us the state of line-number and sub-line-number locking. 0 means we are not within a locked set of lines; 1 means we are at the first line in the set; 2, at some intermediate line; and 3, at the last line.

```
876 \newcount\@lock
879 \newcount\sub@lock
880 %
```

V.9 Line number associated to lemma

`\line@list` Now we can define the list of macros which will be created from the line-list file. We will maintain the following lists:

- `\line@list`: the page and line numbers for every lemma marked by `\edtext`. There are seven pieces of information, separated by vertical bars:
 1. the starting page,
 2. line, and
 3. sub-line numbers, followed by the
 4. ending page,
 5. line, and
 6. sub-line numbers, and then the
 7. font specifier for the lemma.

These line numbers are all visible numbers. The font specifier is a set of four codes for font encoding, family, series, and shape, separated by / characters. Thus a lemma that started on page 23, line 35 and went on until page 24, line 3 (with no sub-line numbering), and was typeset in a normal roman font would have a line list entry like this:

```
23|35|0|24|3|0|OT1/cm/r/n.
```

There is one item in this list for every lemma marked by `\edtext`, even if there are several notes to that lemma, or no notes at all. `\edtext` reads the data in this list, making it available for use in the text of notes.

- `\insertlines@list`: the line numbers of lines that have footnotes or other insertions. These are the absolute numbers where the corresponding lemmas begin. This list contains one entry for every footnote in the section; one lemma may contribute no footnotes or many footnotes. This list is used by `\add@inserts` within `\do@line`, to tell it where to insert notes.
- `\actionlines@list`: a list of absolute line numbers at which we are to perform special actions; these actions are specified by the `\actions@list` list defined below.
- `\actions@list`: action codes corresponding to the line numbers in `\actionlines@list`. These codes tell `reledmac` what action it is supposed to take at each of these lines. One action, the page-start action, is generated behind the scenes by `reledmac`

itself; the others, for specifying sub-lineation, line-number locking, and line-number alteration, are generated only by explicit commands in your input file. The page-start and line-number-alteration actions require arguments, to specify the new values for the page or line numbers; instead of storing those arguments in another list, we have chosen the action-code values so that they can encode both the action and the argument in these cases. Action codes greater than -1000 are page-start actions, and the code value is the page number; action codes less than -5000 specify line numbers, and the code value is a transformed version of the line number; action codes between these two values specify other actions which require no argument.

Here is the full list of action codes and their meanings:

Any number greater than -1000 is a page-start action: the line number associated with it is the first line on a page, and the action number is the page number. (The cutoff of -1000 is chosen because negative page-number values are used by some macro packages; we assume that page-number values less than -1000 are not common.) Page-start action codes are added to the list by the `\page@action` macro, which is (indirectly) triggered by the workings of the `\page@start` macro; that macro should always be called in the output routine, just before the page contents are assembled. `Eledmac` calls it in `\pagecontents`.

The action code -1001 specifies the start of sub-lineation: meaning that, starting with the next line, we should be advancing `\subline@num` at each start-of-line command, rather than `\line@num`.

The action code -1002 specifies the end of sub-lineation. At the next start-of-line, we should clear the sub-line counter and start advancing the line number. The action codes for starting and ending sub-lineation are added to the list by the `\sub@action` macro, as called to implement the `\startsub` and `\endsub` macros.

The action code -1003 specifies the start of line number locking. After the number for the current line is computed, it will remain at that value through the next line that has an action code to end locking.

The action code -1004 specifies the end of line number locking.

The action code -1005 specifies the start of sub-line number locking. After the number for the current sub-line is computed, it will remain at that value through the next sub-line that has an action code to end locking.

The action code -1006 specifies the end of sub-line number locking.

The four action codes for line and sub-line number locking are added to the list by the `\do@lockon` and `\do@lockoff` macros, as called to implement the `\startlock` and `\endlock` macros.

An action code of -5000 or less sets the current visible line number (either the line number or the sub-line number, whichever is currently being advanced) to a specific positive value. The value of the code is $-(5000 + n)$, where n is the value (always ≥ 0) assigned to the current line number. Action codes of this type are added to the list by the `\set@line@action` macro, as called to implement

the `\advanceline` and `\setline` macros: this action only occurs when the user has specified some change to the line numbers using those macros. Normally `reledmac` computes the visible line numbers from the absolute line numbers with reference to the other action codes and the settings they invoke; it does not require an entry in the action-code list for every line.

- `\annot@list` stores line number annotations for the start and the end lines of each `\edtext`, as `\line@list` does for line numbers. We don't store that in the same list as line numbers as `\Xprintlines` already have height arguments, and a `TeX` macro can take at most nine arguments.

Here are the commands to create these lists:

```
881 \list@create{\line@list}
882 \list@create{\insertlines@list}
883 \list@create{\actionlines@list}
884 \list@create{\actions@list}
885 \list@create{\annot@list}%
886 %
```

```
\page@num We will need some counts while we read the line-list, for the page number and the ending
\endpage@num page, line, and sub-line numbers. Some of these will be used again later on, when we
\endline@num are acting on the data in our list macros.
\endsubline@num
887 \newcount\page@num
888 \newcount\endpage@num
889 \newcount\endline@num
890 \newcount\endsubline@num
891 %
```

`\this@section@page@num` The `\this@section@page@num` stores the page number on which a numbering section ends.

```
892 \newcount\this@section@page@num%
893 %
```

```
\ifnoteschanged@ If the number of the footnotes in a section is different from what it was during the last
\noteschanged@true run, or if this is the very first time you've run  $\TeX$ , on this file, the information from
\noteschanged@false the line-list used to place the notes will be wrong, and some notes will probably be
misplaced. When this happens, we prefer to give a single error message for the whole
section rather than messages at every point where we notice the problem, because we do
not really know where in the section notes were added or removed, and the solution in
any case is simply to run  $\TeX$  two more times; there is no fix needed to the document.
The \ifnoteschanged@ flag is set if such a change in the number of notes is discovered
at any point.
```

```
894 \newif\ifnoteschanged@
895 %
```

`\resetprevline@` Inside the apparatus, at each note, the line number is stored in a macro called `\prevlineX`, where X is the letter of the current series. This macro is called when using `\Xnumberonlyfirstinline`. This macro must be reset at the same time as the line number. The `\resetprevline@` does this resetting for every series.

```

\resetprevline@ \newcommand*{\resetprevline@}{%
897   \def\do##1{\global\csundef{prevline##1}}%
898   \dolistloop{\@series}%
899 }
900 %

```

`\resetprevpage@num` Inside the apparatus, at each note, the page number is stored in a macro called `\prevpageX@num`, where X is the letter of the current series. This macro is called when using `\Xparafootsep` or `\parafootsepX`. This macro must be reset at the beginning of each numbered section. The `\resetprevpage@` command resets this macro for every series.

```

\resetprevpage@ \newcommand*{\resetprevpage@num}{%
901   \def\do##1{%
902     \ifcsdef{prevpage##1@num}{%
903       \global\csname prevpage##1@num\endcsname=\z@%
904       \global\csname prevpage##1@numR\endcsname=\z@%
905     }%
906     {}%
907   }%
908   \ifcsdef{##1prevpage@num}{%
909     \global\csname ##1prevpage@num\endcsname=\z@%
910     \global\csname ##1prevpage@numR\endcsname=\z@%
911   }%
912   {}%
913 }%
914 \dolistloop{\@series}%
915 }
916 %

```

V.10 Reading the line-list file

`\read@linelist` `\read@linelist{<file>}` is the control sequence that is called by `\beginnumbering` (via `\line@list@stuff`) to open and process a line-list file; its argument is the name of the file. First, it clear all previous line's list.

```

917 \newread\@inputcheck
918 \newcommand*{\read@linelist}[1]{%
919   \ifledRcol%
920     \list@clearing@regR%
921   \else%
922     \list@clearing@reg%
923   \fi%
924 %

```

When using `reledpar`, make sure that the `\maxlinesinpar@list` is empty (otherwise things will be thrown out of kilter if there is any old stuff still hanging in there).

```
925 \list@clear{\maxlinesinpar@list}
926 %
```

Now get the file and interpret it. When the file is there we start a new group and make some special definitions we will need to process it. It is a sequence of \TeX commands, but they require a few special settings. We make `[` and `]` become grouping characters: they are used that way in the line-list file, because we need to write them out one at a time rather than in balanced pairs, and it is easier to just use something other than real braces. `@` must become a letter, since this is run in the ordinary \LaTeX context. We ignore carriage returns, since if we are in horizontal mode they can get interpreted as spaces to be printed.

Our line, page, and line-locking counters were already zeroed by `\line@list@stuff` if this is being called from within `\beginnumbering`; sub-lineation will be turned off as well in that case. On the other hand, if this is being called from `\resumenumbering`, those things should still have the values they had when `\pausenumbering` was executed.

If the file is not there, we print an informative message.

Now, after these preliminaries, we start interpreting the file.

```
927 \get@linelistfile{#1}%
928 \@stopmsd%Security if last \endms{} is forgotten
929 \unless\ifledRcol%Get the last line of the last page
930 \csnumgdef{@lastabsline@forpage@the\page@num}{\the\absline@num}%
931 \csnumgdef{@lastline@forpage@the\page@num}{\the\line@num}%
932 \csnumgdef{@lastsubline@forpage@the\page@num}{\the\subline@num}%
933 \else%
934 \csnumgdef{@lastabsline@forpageR@the\page@numR}{\the\absline@numR}%
935 \csnumgdef{@lastline@forpageR@the\page@numR}{\the\line@numR}%
936 \csnumgdef{@lastsubline@forpageR@the\page@numR}{\the\subline@numR}%
937 \fi%
938 \endgroup
939 %
```

When the reading is done, we are all through with the line-list file. All the information we needed from it will now be encoded in our list macros.

Finally, we initialize the `\next@actionline` and `\next@action` macros, which specify where and what the next action to be taken is.

```
940 \ifledRcol
941 \global\page@numR=\m@ne
942 \ifx\actionlines@listR\empty
943 \gdef\next@actionlineR{1000000}%
944 \else
945 \glp\actionlines@listR\to\next@actionlineR
946 \glp\actions@listR\to\next@actionR
947 \fi
948 \else
```

```

949 \global\page@num=\m@ne
950 \ifx\actionlines@list\empty
951   \gdef\next@actionline{1000000}%
952 \else
953   \gl@p\actionlines@list\to\next@actionline
954   \gl@p\actions@list\to\next@action
955 \fi
956 \fi
957 }
958 %

```

`\list@clearing@reg` Clears the lists for `\read@linelist`

```

959 \newcommand*\list@clearing@reg{%
960   \list@clear{\line@list}%
961   \list@clear{\insertlines@list}%
962   \list@clear{\actionlines@list}%
963   \list@clear{\actions@list}%
964   \list@clear{\linesinpar@listL}%
965   \list@clear{\linesonpage@listL}%
966 }%
967 %

```

`\get@linelistfile` `reledmac` can take advantage of the \TeX “safe file input” macros to get the line-list file.

```

968 \newcommand*\get@linelistfile}[1]{%
969   \InputIfFileExists{\l@auxdir#1}{%
970     \global\noteschanged@false
971     \begingroup
972       \catcode`\[=1 \catcode`\]=2
973       \makeatletter \catcode`\~M=9}{%
974     \led@warn@NoFile{\l@auxdir#1}%
975     \global\noteschanged@true
976     \begingroup}%
977 }
978
979 %

```

This version of `\read@linelist` creates list macros containing data for the entire section, so they could get rather large. It would be no more difficult to read the line-list file incrementally rather than all at once: we could read, at the start of each paragraph, only the commands relating to that paragraph. But this would require that we have two line-lists open at once, one for reading, one for writing, and on systems without version numbers we would have to do some file renaming outside of \TeX for that to work. We have retained this slower approach to avoid that sort of hacking about, but have provided the `\pausenumbering` and `\resumenumbering` macros to help you if you run into macro memory limitations (see 5.2.7 p. 21 above).

V.11 Commands within the line-list file

This section defines the commands that can appear within a line-list file. They all have very short names because we are likely to be writing very large numbers of them out. One macro, `\@nl`, is especially short, since it will be written to the line-list file once for every line of text in a numbered section. (Another of these commands, `\@lab`, will be introduced in a later section, among the cross-referencing commands it is associated with.)

When these commands modify the various page and line counters, they deliberately do not use `\global`. This is because we want them to affect only the counter values within the current group when nested calls of `\@ref` occur. (The code assumes throughout that the value of `\globaldefs` is zero.)

The macros with `action` in their names contain all the code that modifies the action-code list: again, this is so that they can be turned off easily for nested calls of `\@ref`.

`\line@list@version` The `\line@list@version` check if the line-list file does not refer to the older commands of `reledmac`. In this case, we stop reading the line-list file. Consequently, `\line@list@version` must be the first line of a line-number file.

```

980 \newcommand{\line@list@version}[1]{%
981   \IfStrEq{#1}{\this@line@list@version}%
982   {}%
983   {\ifledRcol%
984     \led@warn@Obsolete{\jobname.\extensionchars\the\section@num}%
985     \else%
986     \led@warn@Obsolete{\jobname.\extensionchars\the\section@num}%
987     \fi%
988     \endinput%
989   }%
990 }%
991 %

```

`\@nl` `\@nl` does everything related to the start of a new line of numbered text.

`\@nl@reg` In order to get the `\setlinenum` to work Peter Wilson had to slip in some new code at the start of the macro, to get the timing of the actions correct. The problem was that his original naive implementation of `\setlinenum` had a unfortunate tendency to change the number of the last line of the *preceding* paragraph. The new code is sort of based on the page number handling and `\setline`. It seems that a lot of fiddling with the line number internals is required.

In November 2004 in order to accurately determine page numbers Peter Wilson added these to the macro. It is now:

```
\@nl{<page counter number>}{<printed page number>}
```

We do not (yet) use the printed number (i.e., the `\thepage`) but it may come in handy later. The macro `\@page` checks if a new page has started.

Exactly what `\@nl` does depends on whether right text is being processed. That's why many code is defined in `\@nl@reg` or `\nl@regR`.

```

993 \newcommand*{\@nl}[2]{%
994   \@page{#1}%
995   \ifledRcol%
996     \@nl@regR%
997   \else%
998     \@nl@reg%
999   \fi%
1000 }
1001 \newcommand*{\@nl@reg}{%
1002   \ifx\l@dchset@num\relax \else
1003     \advance\absline@num \@ne
1004     \csgdef{\l@dchset@num@the\absline@num}{}%To remember this line have
been marked by a \setlinenum
1005     \set@line@action
1006     \let\l@dchset@num=\relax
1007     \advance\absline@num \m@ne
1008     \advance\line@num \m@ne
1009   \fi
1010 }%

```

First increment the absolute line-number, and perform deferred actions relating to page starts and sub-lines.

```

1011 \reset@current@annot%
1012 \advance\absline@num \@ne
1013   \ifx\next@page@num\relax \else
1014     \page@action
1015     \let\next@page@num=\relax
1016   \fi
1017   \ifx\sub@change\relax \else
1018     \ifnum\sub@change>\z@
1019       \sublines@true
1020     \else
1021       \sublines@false
1022     \fi
1023     \sub@action
1024     \let\sub@change=\relax
1025   \fi
1026 }%

```

Fix the lock counters, if necessary. A value of 1 is advanced to 2; 3 advances to 0; other values are unchanged.

```

1027   \ifcase\@lock
1028     \or
1029       \@lock \tw@
1030     \or \or
1031       \@lock \z@
1032     \fi
1033   \ifcase\sub@lock
1034     \or

```



```

1035         \sub@lock \tw@
1036     \or \or
1037         \sub@lock \z@
1038 \fi
1039 %

```

Now advance the visible line number, unless it has been locked.

```

1040 \ifsublines@
1041     \ifnum\sub@lock<\tw@
1042         \advance\subline@num \@ne
1043     \fi
1044 \else
1045     \ifnum\@lock<\tw@
1046         \advance\line@num \@ne \subline@num \z@
1047     \fi
1048 \fi}
1049 %
1050 %

```

`\last@page@num` `\@page` determines whether or not a new page has been started, based on the page values held by `\@nl`.

```

\this@section@last@page@num
\@page
1051 \newcount\last@page@num
1052 \last@page@num=-10000
1053
1054 \newcount\this@section@last@page@num%
1055 \this@section@last@page@num=-10000%
1056
1057 \newcommand*{\@page}[1]{%
1058 \ifledRcol
1059     \ifnum #1=\last@page@numR
1060 \else
1061     \csnumgdef{@lastabsline@forpageR@the\page@numR}{\the\absline@numR}%
1062     \csnumgdef{@lastline@forpageR@the\page@numR}{\the\line@numR}%
1063     \csnumgdef{@lastsubline@forpageR@the\page@numR}{\the\subline@numR}%
1064     \ifbypage@R
1065         \ifx\ldchset@num\relax%Not resetting if preceded by a \setlinenum
1066             \ifboolexpr{%
1067                 bool{resumenumberingR@start}%
1068                 and test {\ifnumequal{\last@page@numR}{-10000}}%
1069             }%
1070             {}%
1071             {%
1072                 \line@numR \z@%
1073                 \subline@numR \z@%
1074                 \global\csdef{reset@lineR\the\numexpr\absline@numR+1\relax @\
the\section@numR}{}%
1075             }%
1076         \fi%
1077     \fi

```

```

1078 \page@numR=#1%
1079 \global\this@section@page@numR=#1%
1080 \last@page@numR=#1%
1081 \global\this@section@last@page@numR=#1%
1082 \def\next@page@numR{#1}%
1083 \gdef\this@section@next@page@numR{#1}%
1084 \fi
1085 \else
1086 \ifnum #1=\last@page@num
1087 \else
1088 \csnumgdef{lastabsline@forpage@the\page@num}{the\absline@num}%
1089 \csnumgdef{lastline@forpage@the\page@num}{the\line@num}%
1090 \csnumgdef{lastsubline@forpage@the\page@num}{the\subline@num}%
1091 \ifbypage@
1092 \ifx\l@dcchset@num\relax%Not resetting if preceded by a \setlinenum
1093 \line@num \z@%
1094 \subline@num \z@%
1095 \global\csdef{reset@line\the\numexpr\absline@num+1\relax @the\
section@num}{}%
1096 \fi%
1097 \fi
1098 \page@num=#1%
1099 \global\this@section@page@num=#1%
1100 \last@page@num=#1%
1101 \global\this@section@last@page@num=#1%
1102 \def\next@page@num{#1}%
1103 %

```

And we set a flag that tells \@n1 that a new page number is to be set, because other associated actions shouldn't occur until the next line-start occurs.

```

1104 \gdef\this@section@next@page@num{#1}%
1105 \listxadd{normal@page@break}{the\absline@num}
1106 \fi
1107 \fi}
1108 %

```

\@pend These do not do anything at this point, but will have been added to the auxiliary file(s) if the reledpar package has been used. They are just here to stop reledmac from moaning if the reledpar is used for one run and then not for the following one.

```

\@lopL
\@lopR
1109 \newcommand*{\@pend}[1]{}
1110 \newcommand*{\@pendR}[1]{}
1111 \newcommand*{\@lopL}[1]{}
1112 \newcommand*{\@lopR}[1]{}
1113
1114 %

```

\sub@on The \sub@on and \sub@off macros turn sub-lineation on and off: but not directly, since such changes do not really take effect until the next line of text. Instead they set a flag that notifies \@n1 of the necessary action.

```

1115 \newcommand*{\sub@on}{\ifsublines@
1116     \let\sub@change=\relax
1117     \else
1118     \def\sub@change{1}%
1119     \fi}
1120 \newcommand*{\sub@off}{\ifsublines@
1121     \def\sub@change{-1}%
1122     \else
1123     \let\sub@change=\relax
1124     \fi}
1125
1126 %

```

\@adv The `\@adv{<num>}` macro advances the current visible line number by the amount specified as its argument. This is used to implement `\advanceLine`.

```

1127
1128 \newcommand*{\@adv}[1]{%
1129     \ifsublines@
1130     \ifledRcol
1131         \advance\subline@numR by #1\relax
1132         \ifnum\subline@numR<\z@
1133             \led@warn@BadAdvancelineSubline
1134             \subline@numR \z@
1135         \fi
1136     \else
1137         \advance\subline@num by #1\relax
1138         \ifnum\subline@num<\z@
1139             \led@warn@BadAdvancelineSubline
1140             \subline@num \z@
1141         \fi
1142     \fi
1143 \else
1144     \ifledRcol
1145         \advance\line@numR by #1\relax
1146         \ifnum\line@numR<\z@
1147             \led@warn@BadAdvancelineLine
1148             \line@numR \z@
1149         \fi
1150     \else
1151         \advance\line@num by #1\relax
1152         \ifnum\line@num<\z@
1153             \led@warn@BadAdvancelineLine
1154             \line@num \z@
1155         \fi
1156     \fi
1157 \fi
1158 \set@line@action}
1159
1160 %

```

\@set The `\@set{<num>}` macro sets the current visible line number to the value specified as its argument. This is used to implement `\setline`.

```

1161
1162 \newcommand*{\@set}[1]{%
1163   \ifledRcol
1164     \ifsublines@
1165       \subline@numR=#1\relax
1166     \else
1167       \line@numR=#1\relax
1168     \fi
1169     \set@line@action
1170   \else
1171     \ifsublines@
1172       \subline@num=#1\relax
1173     \else
1174       \line@num=#1\relax
1175     \fi
1176     \set@line@action
1177   \fi}
1178
1179 %

```

\l@d@set The `\l@d@set{<num>}` macro sets the line number for the next `\pstart` to the value specified as its argument. This is used to implement `\setlinenum`.

\l@dchset@num `\l@dchset@num` is a flag to the `\@nl?` macro. If it is not `\relax` then a linenum change is to be done.

```

1180
1181 \newcommand*{\l@d@set}[1]{%
1182   \ifledRcol
1183     \line@numR=#1\relax
1184     \advance\line@numR \@ne
1185     \def\l@dchset@num{#1}
1186   \else
1187     \line@num=#1\relax
1188     \advance\line@num \@ne
1189     \def\l@dchset@num{#1}
1190   \fi}
1191 \let\l@dchset@num\relax
1192
1193 %

```

\page@action `\page@action` adds an entry to the action-code list to change the page number.

```

1194
1195 \newcommand*{\page@action}{%
1196   \ifledRcol
1197     \xright@appenditem{\the\absline@numR}\to\actionlines@listR
1198     \xright@appenditem{\next@page@numR}\to\actions@listR

```

```

1199 \else
1200 \xright@appenditem{\the\absline@num}\to\actionlines@list
1201 \xright@appenditem{\next@page@num}\to\actions@list
1202 \fi}
1203 %

```

\set@line@action \set@line@action adds an entry to the action-code list to change the visible line number.

```

1204
1205 \newcommand*{\set@line@action}{%
1206 \ifledRcol
1207 \xright@appenditem{\the\absline@numR}\to\actionlines@listR
1208 \ifsublines@
1209 \@l@tempcnta=-\subline@numR
1210 \else
1211 \@l@tempcnta=-\line@numR
1212 \fi
1213 \advance\@l@tempcnta by -5000\relax
1214 \xright@appenditem{\the\@l@tempcnta}\to\actions@listR
1215 \else
1216 \xright@appenditem{\the\absline@num}\to\actionlines@list
1217 \ifsublines@
1218 \@l@tempcnta=-\subline@num
1219 \else
1220 \@l@tempcnta=-\line@num
1221 \fi
1222 \advance\@l@tempcnta by -5000\relax
1223 \xright@appenditem{\the\@l@tempcnta}\to\actions@list
1224 \fi}
1225 %

```

\sub@action \sub@action adds an entry to the action-code list to turn sub-lineation on or off, according to the current value of the \ifsublines@ flag.

```

1226
1227 \newcommand*{\sub@action}{%
1228 \ifledRcol
1229 \xright@appenditem{\the\absline@numR}\to\actionlines@listR
1230 \ifsublines@
1231 \xright@appenditem{-1001}\to\actions@listR
1232 \else
1233 \xright@appenditem{-1002}\to\actions@listR
1234 \fi
1235 \else
1236 \xright@appenditem{\the\absline@num}\to\actionlines@list
1237 \ifsublines@
1238 \xright@appenditem{-1001}\to\actions@list
1239 \else
1240 \xright@appenditem{-1002}\to\actions@list

```

```

1241 \fi
1242 \fi}
1243 %

```

`\lock@on` `\lock@on` adds an entry to the action-code list to turn line number locking on. The current setting of the sub-lineation flag tells us whether this applies to line numbers or sub-line numbers.

Adding commands to the action list is slow, and it is very often the case that a lock-on command is immediately followed by a lock-off command in the line-list file, and therefore really does nothing. We use a look-ahead scheme here to detect such pairs, and add nothing to the line-list in those cases.

```

1244 \newcommand*{\lock@on}{\futurelet\next\do@lockon}
1245
1246 \newcommand*{\do@lockon}{%
1247   \ifx\next\lock@off
1248     \global\let\lock@off=\skip@lockoff
1249   \else
1250     \ifledRcol
1251       \do@lockonR
1252     \else
1253       \do@lockonL
1254     \fi
1255   \fi}
1256
1257
1258 \newcommand*{\do@lockonL}{%
1259   \xright@appenditem{\the\absline@num}\to\actionlines@list
1260   \ifsublines@
1261     \xright@appenditem{-1005}\to\actions@list
1262     \ifnum\sub@lock=\z@
1263       \sub@lock \@ne
1264     \else
1265       \ifnum\sub@lock=\thr@@
1266         \sub@lock \@ne
1267       \fi
1268     \fi
1269   \else
1270     \xright@appenditem{-1003}\to\actions@list
1271     \ifnum\@lock=\z@
1272       \@lock \@ne
1273     \else
1274       \ifnum\@lock=\thr@@
1275         \@lock \@ne
1276       \fi
1277     \fi
1278   \fi}
1279 %
1280 %

```

`\lock@off` `\lock@off` adds an entry to the action-code list to turn line number locking off.

```

1281 \do@lockoff
1282 \do@lockoffL
1283 \skip@lockoff
1284 \newcommand*{\do@lockoffL}{%
1285   \xright@appenditem{\the\absline@num}\to\actionlines@list
1286   \ifsublines@
1287     \xright@appenditem{-1006}\to\actions@list
1288     \ifnum\sub@lock=\tw@
1289       \sub@lock \thr@@
1290     \else
1291       \sub@lock \z@
1292     \fi
1293   \else
1294     \xright@appenditem{-1004}\to\actions@list
1295     \ifnum\@lock=\tw@
1296       \@lock \thr@@
1297     \else
1298       \@lock \z@
1299     \fi
1300   \fi}
1301 \newcommand*{\do@lockoff}{%
1302   \reset@current@annot%
1303   \ifledRcol
1304     \do@lockoffR
1305   \else
1306     \do@lockoffL
1307   \fi}
1308 \newcommand*{\skip@lockoff}{\global\let\lock@off=\do@lockoff}
1309 \global\let\lock@off=\do@lockoff
1310 %
1311 %

```

`\n@num` These macros implement the `\skipnumbering` command. They use action code 1007.

```

1310 \newcommand*{\n@num}{%
1311   \ifledRcol%
1312     \xright@appenditem{\the\absline@numR}\to\actionlines@listR
1313     \xright@appenditem{-1007}\to\actions@listR
1314   \else%
1315     \xright@appenditem{\the\absline@num}\to\actionlines@list%
1316     \xright@appenditem{-1007}\to\actions@list%
1317   \fi%
1318 }%
1319 %
1320 %

```

`\n@num@stanza` This macro implements the `\skipnumbering` for stanza command. It uses action code 1008.

```

\ifl@dhiddenumber
\hidenumbering
\hidenumberingonleftpage
\hidenumberingonrightpage
\hidenumberingonrightpage
\newif\ifl@dhiddenumber
\newcommand*{\hidenumbering}{%
\ifledRcol%
\write\linenum@outR{\string\hide@num}%
\else%
\write\linenum@out{\string\hide@num}%
\fi%
}%
\newcommand*{\hide@num}{%
\ifledRcol%
\xright@appenditem{\the\absline@numR}\to\actionlines@listR%
\xright@appenditem{-1009}\to\actions@listR%
\else%
\xright@appenditem{\the\absline@num}\to\actionlines@listR%
\xright@appenditem{-1009}\to\actions@listR%
\fi%
}
\newcommand*{\hidenumberingonleftpage}{%
\ifledRcol%
\write\linenum@outR{\string\hide@num@left}%
\else%
\write\linenum@out{\string\hide@num@left}%
\fi%
}%
\newcommand*{\hide@num@left}{%
\ifledRcol%
\ifodd\page@numR\else%
\xright@appenditem{\the\absline@numR}\to\actionlines@listR%
\xright@appenditem{-1009}\to\actions@listR%
\fi%
\else%
\ifodd\page@num\else%
\xright@appenditem{\the\absline@num}\to\actionlines@listR%
\xright@appenditem{-1009}\to\actions@listR%
\fi%
\fi%
}

```



```

1366 \fi%
1367 \fi%
1368 }%
1369
1370 \newcommand*{\hidenumberingonrightpage}{%
1371 \ifledRcol%
1372 \write\linenum@outR{\string\hide@num@right}%
1373 \else%
1374 \write\linenum@out{\string\hide@num@right}%
1375 \fi%
1376 }%
1377
1378 \newcommand*{\hide@num@right}{%
1379 \ifledRcol%
1380 \ifodd\page@numR%
1381 \xright@appenditem{\the\absline@numR}\to\actionlines@listR%
1382 \xright@appenditem{-1009}\to\actions@listR%
1383 \fi%
1384 \else%
1385 \ifodd\page@num%
1386 \xright@appenditem{\the\absline@num}\to\actionlines@list%%
1387 \xright@appenditem{-1009}\to\actions@list%
1388 \fi%
1389 \fi%
1390 }%
1391
1392 %

```

\@ref \@ref marks the start of a passage, for creation of a footnote reference. It takes two arguments:

- #1, the number of entries to add to \insertlines@list for this reference. This value, here and within \edtext, which computes it and writes it to the line-list file, will be stored in the count \insert@count.

```

1393 \newcount\insert@count
1394 %

```

- #2, a sequence of other line-list-file commands, executed to determine the ending line-number. (This may also include other \@ref commands, corresponding to uses of \edtext within the first argument of another instance of \edtext.)

\dummy@ref When nesting of \@ref commands does occur, it is necessary to temporarily redefine \@ref within \@ref, so that we are only doing one of these at a time.

```

1395 \newcommand*{\dummy@ref}[2]{#2}
1396 %

```

\@ref@reg The first thing \@ref (i.e. \@ref@reg) itself does is to add the specified number of items to the \insertlines@list list.

```

1397 \newcommand*{\@ref}[2]{%
1398   \ifledRcol%
1399     \@ref@regR{#1}{#2}%
1400   \else%
1401     \@ref@reg{#1}{#2}%
1402   \fi%
1403 }%
1404 \newcommand*{\@ref@reg}[2]{%
1405   \global\insert@count=#1\relax
1406   \global\advance\@edtext@level by 1%
1407   \loop\ifnum\insert@count>\z@
1408     \xright@appenditem{\the\absline@num}\to\insertlines@list
1409     \global\advance\insert@count \m@ne
1410   \repeat
1411   %

```

Next, process the second argument to determine the page and line numbers for the end of this lemma. We temporarily equate \@ref to a different macro that just executes its argument, so that nested \@ref commands are just skipped this time. Some other macros need to be temporarily redefined to suppress their action.

```

1412 \begingroup
1413   \let\@ref=\dummy@ref
1414   \let\@lopL\@gobble
1415   \let\page@action=\relax
1416   \let\sub@action=\relax
1417   \let\set@line@action=\relax
1418   \let\@lab=\relax
1419   \let\@lemma=\relax%
1420   \let\@sw\@gobblethree%
1421   \let\store@annot@to@absline\@gobble%
1422   #2
1423   \global\endpage@num=\page@num
1424   \global\endline@num=\line@num
1425   \global\endsubline@num=\subline@num
1426   \global\let\endcurrent@annot=\current@annot%
1427 \endgroup
1428 %

```

Now store all the information about the location of the lemma's start and end in \line@list.

```

1429 \xright@appenditem%
1430   {\the\page@num|\the\line@num|%
1431     \ifsublines@ \the\subline@num \else 0\fi%
1432     \the\endpage@num|\the\endline@num|%
1433     \ifsublines@ \the\endsubline@num \else 0\fi}\to\line@list
1434 \xright@appenditem%
1435   {\current@annot|\endcurrent@annot}\to\annot@list%
1436 %

```

And now, call \@ref@reg@parsearg, which can be also called by \@ref@later

```

1437 \@ref@reg@parse{#2}%
1438 %
Decrease edtext level counter.
1439 \global\advance\@edtext@level by -1%
1440 }
1441 %

```

\@ref@reg@parse The \@ref@reg@parsearg command parses the second argument of a \@ref or the unique argument of \@ref@later written in the auxiliary fill.

First, create a list which stores every second argument of each \@sw in this lemma, at this level. Also set the boolean about the use of lemma in this edtext level to false.

```

1442 \newcommand{\@ref@reg@parse}[1]{%
1443   \expandafter\list@create\expandafter{\csname sw@list@edtext@tmp@\the\
1444   \@edtext@level\endcsname}%
1445   \providebool{lemmacommand@\the\@edtext@level}%
1446   \boolfalse{lemmacommand@\the\@edtext@level}%
1447   %

```

Execute the second argument of \@ref again, to perform for real all the commands within it.

```

1447   #1%
1448 %

```

Now, we store the list of \@sw of this current \edtext as an element of the global list of list of \@sw for a \edtext depth.

```

1449 \ifnum\@edtext@level>0%
1450   \def\create@this@edtext@level{\expandafter\list@create\expandafter{\
1451   \csname sw@list@edtext@\the\@edtext@level\endcsname}}%
1452   \ifcsundef{sw@list@edtext@\the\@edtext@level}\create@this@edtext@level
1453   \fi}%
1454   \letcs{\@tmp}{sw@list@edtext@\the\@edtext@level}%
1455   \letcs{\@tmpp}{sw@list@edtext@tmp@\the\@edtext@level}%
1456   \xright@appenditem{\expandonce\@tmpp}\to\@tmp%
1457   \global\cslet{sw@list@edtext@\the\@edtext@level}{\@tmp}%
1458   \fi%
1459 %
1460 }
1461 %

```

\@ref@reg@later This macro is stored in the auxiliary file when using \edtextlater. It is used only to get the correct value for the \sameword tools.

```

1461 \newcommand{\@ref@later}[1]{%
1462   \global\advance\@edtext@level by \@ne%
1463   \ifledRcol%

```

```

1464 \@ref@reg@parseR{#1}%
1465 \else%
1466 \@ref@reg@parse{#1}%
1467 \fi%
1468 \global\advance\@edtext@level by -\@ne%
1469 }%
1470 %

```

V.12 Writing to the line-list file

We have now defined all the counters, lists, and commands involved in reading the line-list file at the start of a section. Now we will cover the commands that `reledmac` uses within the text of a section to write commands out to the line-list.

`\linenum@out` The file will be opened on output stream `\linenum@out`.

```

1471 \newwrite\linenum@out
1472 %

```

`\iffirst@linenum@out` Once any file is opened on this stream, we keep it open forever, or else switch to another file that we keep open. The reason is that we want the output routine to write the page number for every page to this file; otherwise we would have to write it at the start of every line. But it is not very easy for the output routine to tell whether an output stream is open or not. There is no way to test the status of a particular output stream directly, and the asynchronous nature of output routines makes the status hard to determine by other means.

We can manage pretty well by means of the `\iffirst@linenum@out` flag; its inelegant name suggests the nature of the problem that made its creation necessary. It is set to be `true` before any `\linenum@out` file is opened. When such a file is opened for the first time, it is done using `\immediate`, so that it will at once be safe for the output routine to write to it; we then set this flag to `false`.

```

1473 \newif\iffirst@linenum@out
1474 \iffirst@linenum@out>true
1475 %

```

`\this@line@list@version` The commands allowed in the line-list file and their arguments can change between two versions of `reledmac`. The `\this@line@list@version` command is upgraded when it happens. It is written in the file list. If we process a line-list file which used an older version, that means the commands used inside are deprecated, and we can't use them.

```

1476 \newcommand{\this@line@list@version}{8}%
1477 %

```

`\line@list@stuff` The `\line@list@stuff{<file>}` macro, which is called by `\beginnumbering`, performs all the line-list operations needed at the start of a section. Its argument is the name of the line-list file.

```

1478 \let\next@line@list@stuff\relax%
1479 \newcommand*{\line@list@stuff}[1]{%
1480 %

```

First, define a toggle set to true when we are not in the first run.

```

1481 \global\newtoggle{notfirstrun@#1}%
1482 \IfFileExists{\l@auxdir#1}%
1483   {\global\toggletrue{notfirstrun@#1}}%
1484   {\global\togglefalse{notfirstrun@#1}}%
1485 %

```

A internal hook (not used yet).

```

1486 \next@line@list@stuff%
1487 \global\let\next@line@list@stuff\relax%
1488 %

```

Use the commands of the previous section to interpret the line-list file from the last run.

```

1489 \read@linelist{#1}%
1490 %

```

Now close the current output line-list file, if any, and open a new one. The first time we open a line-list file for output, we do it using `\immediate`, and clear the `\iffirst@linenum@out@` flag. `reledmac` and `reledpar` can fill the `\next@line@list@stuff` hook between a `\endnumbering` (associated with numbered file n) and a `\beginnumbering` (associated with numbered file $n + 1$). It allows adding content to the numbered file $n + 1$ and not n .

```

1491 \iffirst@linenum@out@
1492   \global\first@linenum@out@false%
1493   \immediate\openout\linenum@out=\l@auxdir#1\relax%
1494   \immediate\write\linenum@out{\string\line@list@version{\
this@line@list@version}}%
1495   \ifl@dpaging%
1496     \immediate\write\linenum@out{\string\@par@sync@option{\
@par@this@sync@option}}%
1497   \fi%
1498   \else
1499 %

```

If we get here, then this is not the first line-list we have seen, so we do not open or close the files immediately.

```

1500   \if@minipage%
1501     \leavevmode%
1502   \fi%
1503   \closeout\linenum@out%
1504   \openout\linenum@out=\l@auxdir#1\relax%
1505   \write\linenum@out{\string\line@list@version{\this@line@list@version}}
1506 %
1507   \ifl@dpaging%

```

```

1507 \write\linenum@out{\string\@par@sync@option{\@par@this@sync@option}}
1508 %
1509 \fi%
1510 \fi%
1511 }%
1512 %

```

`\new@line` The `\new@line` macro sends the `\@nl` command to the line-list file, to mark the start of a new text line, and its page number. It writes the two forms of the page number:

- Raw form (`\the\c@page`, which can be used for numeric tests).
- Formatted form (for example, in Roman).

Actually, only the first form is used by `\@nl`. If we use the `\sameparallelpagnumber` option of `reledpar`, we must write not the real page number (i.e. page counter, defined in standard \TeX) but the printed page number (i.e. `par@page` counter, defined only on `reledmac`).

- For the raw form, we use `\the\c@page@page` macro, because the `{par@page}` counter is increased for each page.
- For the formatted version, `\thepage` is patched through `\par@patch@thepage`. So we have nothing to change.

```

1513 \newcommand*{\new@line}{%
1514 \ifnumberline%
1515 \IfStrEq{\led@pb@setting}{after}%
1516 {\xifinlist{\the\absline@num}{\l@prev@nopb}%
1517 {\xifinlist{\the\absline@num}{\normal@page@break}%
1518 {\numgdef{\@next@page}{\c@par@page+\@one}%
1519 \write\linenum@out{\string\@nl[\@next@page][\@next@page]}}%
1520 }%
1521 {\write\linenum@out{\string\@nl[\the\@this@c@page][\thepage]}}%
1522 }%
1523 {\write\linenum@out{\string\@nl[\the\@this@c@page][\thepage]}}}%
1524 {}%
1525 \IfStrEq{\led@pb@setting}{before}%
1526 {\numdef{\next@absline}{\the\absline@num+\@one}%
1527 \xifinlist{\next@absline}{\l@prev@nopb}%
1528 {\xifinlist{\the\absline@num}{\normal@page@break}%
1529 {\numgdef{\nc@page}{\c@par@page+\@one}%
1530 \write\linenum@out{\string\@nl[\nc@page][\nc@page]}}%
1531 }%
1532 {\write\linenum@out{\string\@nl[\the\@this@c@page][\thepage]}}%
1533 }%
1534 {\write\linenum@out{\string\@nl[\the\@this@c@page][\thepage]}}}%
1535 }%
1536 {}%

```

```

1537 \IfStrEqCase{\led@pb@setting}%
1538 {%
1539 {before}{\relax}%
1540 {after}{\relax}%
1541 }[%
1542 \write\linenum@out{\string\@nl[\the\@this@c@page][\thepage]]}%
1543 ]%
1544 \fi%
1545 }
1546
1547 \newcount\@this@c@page%%
1548 \newcommand{\set@this@c@page}{%
1549 \ifboolexpr{%
1550 bool{sameparallelpagenumber}%
1551 or bool{prevpgnotnumbered}%
1552 }%
1553 {\global\@this@c@page=\c@par@page}%
1554 {\global\@this@c@page=\c@page}%
1555 }%
1556 %

```

\if@noneed@Footnote \if@noneed@Footnote is a boolean to check if we have to print a error message when a \edtext is called without any critical notes.

\flag@start We enclose a lemma marked by \edtext in \flag@start and \flag@end: these send the \@ref command to the line-list file. \edtext is responsible for setting the value of \insert@count appropriately; it actually gets done by the various footnote macros.

\flag@end

```

1557 \newif\if@noneed@Footnote%
1558
1559 \newcommand*{\flag@start}{%
1560 \ifledRcol%
1561 \edef\next{\write\linenum@outR{%
1562 \string\@ref[\the\insert@countR] []}}%
1563 \next%
1564 \ifnum\insert@countR<1%
1565 \if@noneed@Footnote\else%
1566 \led@err@EdtextWithoutFootnote%
1567 \fi%
1568 \fi%
1569 \else%
1570 \edef\next{\write\linenum@out{%
1571 \string\@ref[\the\insert@count] []}}%
1572 \next%
1573 \ifnum\insert@count<1%
1574 \if@noneed@Footnote\else%
1575 \led@err@EdtextWithoutFootnote%
1576 \fi%
1577 \fi%
1578 \fi}%

```

```

1579
1580 \newcommand*{\flag@end}{%
1581   \ifledRcol%
1582     \write\linenum@outR{}}%
1583   \else%
1584     \write\linenum@out{}}%
1585   \fi}%
1586
1587
1588 %

```

`\flag@start@RTL` With Xe_{La}TeX, there is a problem when using RTL: the writing of a command in the numbered auxiliary files (.1, .2 etc) is reversed when the first argument of `\edtext` is typeset in one line, but it is **not** reversed when this first argument is typeset in two lines or more.³⁰

To solve this problem, we use a crossref mechanism. At the first run, we put a label, but we do not write any `\@ref` command. When the value of the label can be tested, that is after three runs, we're doing:

- If the first argument of `\edtext` is typeset on only one line, we first call `\flag@end`, at the point we normally call `\flag@start`, at the beginning of the content of the first argument, and we call `\flag@end` at the point we normally call `\flag@start`, at the end of the content of the first argument.
- If the first argument of `\edtext` is typeset on only two lines, we use the normal order.

This system is a workaround for the problem of order when writing in auxiliary files.

The `\flag@start@RTL` and `\flag@end@RTL` macro put the label, do the test and call the right commands.

```

1589 \newcommand{\flag@start@RTL}{%
1590   \edlabel{edtext:start:\csuse{thisedtext@the\@edtext@level}}%
1591   \IfStrEq{\xabslineref{edtext:start:\csuse{thisedtext@the\@edtext@level}}}{%
1592     {000}}%
1593     {}%
1594     {%
1595       \ifnumequal%
1596         {\xabslineref{edtext:start:\csuse{thisedtext@the\@edtext@level}}}{%
1597         {\xabslineref{edtext:end:\csuse{thisedtext@the\@edtext@level}}}%
1598         {\flag@end}%
1599         {\flag@start}}%
1600     }%
1601 }%

```

³⁰This problem is caused by the way Xe_{La}TeX manages right-to-left typesetting. David Carlisle explains it on <http://tex.stackexchange.com/a/333373/7712> and provides a potential solution, using `\vadjust`. However in some cases this adds spurious vertical spaces in `reledmac`. That is why we are using the solution explained below.


```

1602 \newcommand{\flag@end@RTL}{%
1603   \edlabel{edtext:end:\csuse{thisedtext@the\@edtext@level}}}%
1604   \IfStrEq{\xabslineref{edtext:start:\csuse{thisedtext@the\@edtext@level
1605 }}}%
1606     {000}%
1607     {}%
1608     {%
1609     \ifnumequal%
1610       {\xabslineref{edtext:start:\csuse{thisedtext@the\@edtext@level}}}%
1611       {\xabslineref{edtext:end:\csuse{thisedtext@the\@edtext@level}}}%
1612       {\flag@start}%
1613       {\flag@end}%
1614     }%
1615   }%
1616   %

```

`\flag@start@later` `\flag@start@later` and `\flag@end@later`: these send the `\@ref@later` to the line-list file command to the line-list file

```

1617 \newcommand*{\flag@start@later}{%
1618   \ifledRcol%
1619     \write\linenum@outR{\string\@ref@later []}%
1620   \else%
1621     \write\linenum@out{\string\@ref@later []}%
1622   \fi%
1623 }%
1624 \newcommand{\flag@end@later}{%
1625   \ifledRcol%
1626     \write\linenum@outR{[]}%
1627   \else%
1628     \write\linenum@out{[]}%
1629   \fi%
1630 }
1631 %

```

`\startsub` `\startsub` and `\endsub` turn sub-lineation on and off, by writing appropriate instructions to the line-list file. When sub-lineation is in effect, the line number counter is frozen and the sub-line counter advances instead. If one of these commands appears in the middle of a line, it does not take effect until the next line; in other words, a line is counted as a line or sub-line depending on what it started out as, even if that changes in the middle.

We tinker with `\lastskip` because a command of either sort really needs to be attached to the last word preceding the change, not the first word that follows the change. This is because sub-lineation will often turn on and off in mid-line—stage directions, for example, often are mixed with dialogue in that way—and when a line is mixed we want to label it using the system that was in effect at its start. But when sub-lineation begins at the very start of a line we have a problem, if we don't put in this code.

```

1632
1633
1634 \newcommand*{\startsub}{\dimen0\lastskip
1635 \ifdim\dimen0>Opt \unskip \fi
1636 \ifledRcol \write\linenum@outR{\string\sub@on}%
1637 \else \write\linenum@out{\string\sub@on}%
1638 \fi
1639 \ifdim\dimen0>Opt \hskip\dimen0 \fi}
1640 \def\endsub{\dimen0\lastskip
1641 \ifdim\dimen0>Opt \unskip \fi
1642 \ifledRcol \write\linenum@outR{\string\sub@off}%
1643 \else \write\linenum@out{\string\sub@off}%
1644 \fi
1645 \ifdim\dimen0>Opt \hskip\dimen0 \fi}
1646
1647 %

```

\advanceline You can use `\advanceline{<num>}` in running text to advance the current visible line-number by a specified value, positive or negative.

```

1648 \newcommand*{\advanceline}[1]{\leavevmode%
1649 \ifledRcol \write\linenum@outR{\string\@adv[#1]}%
1650 \else \write\linenum@out{\string\@adv[#1]}%
1651 \fi%
1652 }
1653 %

```

\setline You can use `\setline{<num>}` in running text (i.e., within `\pstart... \pend`) to set the current visible line-number to a specified positive value.

```

1654
1655 \newcommand*{\setline}[1]{%
1656 \leavevmode%
1657 \ifnum#1<\z@
1658 \led@warn@BadSetline%
1659 \else%
1660 \ifledRcol%
1661 \write\linenum@outR{\string\@set[#1]}%
1662 \else%
1663 \write\linenum@out{\string\@set[#1]}%
1664 \fi%
1665 \fi%
1666 }%
1667
1668 %

```

\setlinenum You can use `\setlinenum{<num>}` before a `\pstart` to set the visible line-number to a specified positive value. It writes a `\l@d@set` command to the line-list file.

```

1669
1670 \newcommand*{\setlinenum}[1]{%
1671   \ifnum#1<\z@%
1672     \led@warn@BadSetlinenum%
1673   \else%
1674     \ifledRcol%
1675       \write\linenum@outR{\string\l@d@set[#1]}%
1676     \else%
1677       \write\linenum@out{\string\l@d@set[#1]}%
1678     \fi%
1679   \fi%
1680 }%
1681
1682 %

```

\startlock You can use `\startlock` or `\endlock` in running text to start or end line number locking at the current line. They decide whether line numbers or sub-line numbers are affected, depending on the current state of the sub-lineation flags.

\endlock

```

1683
1684 \newcommand*{\startlock}{%
1685   \ifledRcol \write\linenum@outR{\string\lock@on}%
1686   \else      \write\linenum@out{\string\lock@on}%
1687   \fi}
1688 \def\endlock{%
1689   \ifledRcol \write\linenum@outR{\string\lock@off}%
1690   \else      \write\linenum@out{\string\lock@off}%
1691   \fi}
1692 %

```

\ifl@dskipnumber In numbered text `\skipnumbering` will suspend the numbering for that particular line.

\ifl@dskipversenumber

\l@dskipnumbertrue

\l@dskipnumberfalse

\skipnumbering

```

1693 \newif\ifl@dskipnumber
1694 \newif\ifl@dskipversenumber%
1695 \newcommand*{\skipnumbering}{%
1696   \leavevmode%
1697   \ifledRcol%
1698     \ifinstanza%
1699       \write\linenum@outR{\string\n@num@stanza}%
1700     \else%
1701       \write\linenum@outR{\string\n@num}%
1702     \fi%
1703     \advanceline{-1}%
1704   \else%
1705     \ifinstanza%
1706       \write\linenum@out{\string\n@num@stanza}%
1707     \else%
1708       \write\linenum@out{\string\n@num}%
1709     \fi%

```

```

1710 \advance\line{-1}%
1711 \fi%
1712 }%
1713
1714 %

```

VI Marking text for notes

The `\edtext` macro is used to create all footnotes and endnotes, as well as to print the portion of the main text to which a given note or notes is keyed. The idea is to have that lemma appear only once in the `.tex` file: all instances of it in the main text and in the notes are copied from that one appearance.

The `\edtext` macro takes two arguments.

```
\edtext{#1}{#2}
```

- `#1` is the piece of the main text being glossed; it gets added to the main text, and is also used as a lemma for notes to it.
- `#2` is a series of subsidiary macros that generate various kinds of notes.

The `\edtext` macro may be used (somewhat) recursively; that is, `\edtext` may be used within its own first argument. The code would be much simpler without this feature, but nested notes will commonly be necessary: it is quite likely that we will have an explanatory note for a long passage and notes on variants for individual words within that passage. The situation we can't handle is overlapping notes that are not nested: for example, one note covering lines 10–15, and another covering 12–18. You can handle such cases by using the `\lemma` and `\linenum` macros within `#2`: they alter the copy of the lemma and the line numbers that are passed to the notes, and hence allow you to overcome any limitations of this system, albeit with extra effort.

The recursive operation of `\edtext` will fail if you try to use a copy that is called something other than `\edtext`. In order to handle recursion, `\edtext` needs to redefine its own definition temporarily at one point, and that does not work if the macro you are calling is not actually named `\edtext`. There is no problem as long as `\edtext` is not invoked in the first argument. If you want to call `\edtext` something else, it is best to create instead a macro that expands to an invocation of `\edtext`, rather than copying `\edtext` and giving it a new name; otherwise you will need to add an appropriate definition for your new macro to `\morenoexpands`.

Side-effects of our line-numbering code make it impossible to use the usual footnote macros directly within a paragraph whose lines are numbered (see comments to `\do@line`, VII.2.1 p. 164). Instead, the appropriate note-generating command is appended to the list macro `\inserts@list`, and when `\pend` completes the paragraph it inserts all the notes at the proper places.

Note that we do not provide previous-note information, although it is often wanted; your own macros must handle that. We cannot do it correctly without keeping track of what kind of notes have gone past: it is not just a matter of remembering the line

numbers associated with the previous invocation of `\edtext`, because that might have been for a different kind of note. It is preferable for your footnote macros to store and recall this kind of information if they need it.

VI.1 `\edtext itself`

The various note-generating macros might want to request that commands be executed not at once, but in close connection with the start or end of the lemma. For example, footnote numbers in the text should be connected to the end of the lemma; or, instead of a single macro to create a note listing variants, you might want to use several macros in series to create individual variants, which would each add information to a private macro or token register, which in turn would be formatted and output when all of #2 for the lemma has been read.

`\end@lemmas` To accomodate this, we provide a list macro to which macros may add commands that should subsequently be executed at the end of the lemma when that lemma is added to the text of the paragraph. A macro should add its contribution to `\end@lemmas` by using `\xleft@appenditem`. (Anything that needs to be done at the *start* of the lemma may be handled using `\aftergroup`, since the commands specified within `\edtext`'s second argument are executed within a group that ends just before the lemma is added to the main text.)

`\end@lemmas` is intended for the few things that need to be associated with the end of the lemma, like footnote numbers. Such numbers are not implemented in the current version, and indeed no use is currently made of `\end@lemmas` or of the `\aftergroup` trick. The general approach would be to define a macro to be used within the second argument of `\edtext` that would add the appropriate command to `\end@lemmas`.

Commands that are added to this list should always take care not to do anything that adds possible line-breaks to the output; otherwise line numbering could be thrown off.

```
1715 \list@create{\end@lemmas}
1716 %
```

`\dummy@edtext` We now need to define a number of macros that allow us to weed out nested instances of `\edtext`, and other problematic macros, from our lemma. This is similar to what we did in reading the line-list file using `\dummy@ref` and various redefinitions—and that is because nested `\edtexts` macros create nested `\@ref` entries in the line-list file.

```
1717 \newcommand{\dummy@edtext}[2]{#1}
1718 %
```

`\dummy@edtext@showlemma` Some time, we want to obtain only the first argument of `\edtext`, while also wrapping it in `\showlemma`. For example, when printing a `\eledsection`.

```
1719 \newcommand{\dummy@edtext@showlemma}[2]{\showlemma{#1}}%
1720 %
```

We are going to need another macro that takes one argument and ignores it entirely. This is supplied by the \TeX `\@gobble{<arg>}`.

`\no@expands`
`\morenoexpands`

We need to turn off macro expansion for certain sorts of macros we are likely to see within the lemma and within the notes.

The first class is font-changing macros. We suppress expansion for them by letting them become equal to zero.³¹ This is done because we want to pass into our notes the generic commands to change to roman or whatever, and not their expansions that will ask for a particular style at a specified size. The notes may well be in a smaller font, so the command should be expanded later, when the note’s environment is in effect.

A second sort to turn off includes a few of the accent macros. Most are not a problem: an accent that is expanded to an `\accent` command may be harder to read but it works just the same. The ones that cause problems are: those that use alignments— \TeX seems to get confused about the difference between alignment parameters and macro parameters; those that use temporary control sequences; and those that look carefully at what the current font is.

(The `\copyright` macro defined in `PLAIN \TeX` has this sort of problem as well, but is not used enough to bother with. That macro, and any other that causes trouble, will get by all right if you put a `\protect` in front of it in your file.)

We also need to eliminate all `reledmac` macros like `\edlabel` and `\setline` that write things to auxiliary files: that writing should be done only once. And we make `\edtext` itself, if it appears within its own argument, do nothing but copy its first argument.

Finally, we execute `\morenoexpands`. The version of `\morenoexpands` defined here does nothing; but you may define a version of your own when you need to add more expansion suppressions as needed with your macros. That makes it possible to make such additions without needing to copy or modify the standard `reledmac` code. If you define your own `\morenoexpands`, you must be very careful about spaces: if the macro adds any spaces to the text when it runs, extra space will appear in the main text when `\edtext` is used.

The `\new@series` command also adds `\let\footnote<X>\@gobble` to the end of the `\no@expands` macro for the series $\langle X \rangle$.

(A related problem, not addressed by these two macros, is that of characters whose category code are changed by any of the macros used in the arguments to `\edtext`. Since the category codes are set when the arguments are scanned, macros that depend on changing them will not work. We have most often encountered this with characters that are made “active” within text in some, but not all, of the languages used within the document. One way around the problem, if it takes this form, is to ensure that those characters are *always* active. Within languages that make no special use of them, their associated control sequences should simply return the proper character. A simpler solution is to avoid active characters, using `Lua \TeX` or `Xy \TeX` .)

```
1721 \newcommand*{\no@expands}{%
1722   \let\select@lemmafont=0%
1723   \let\startsub=\relax   \let\endsub=\relax
1724   \let\startlock=\relax  \let\endlock=\relax
1725   \let\edlabel=\@gobble
```

³¹Since “control sequences equivalent to characters are not expandable”—*The TeXbook*, answer to Exercise 20.14.

```

1726 \let\setline=\@gobble \let\advanceline=\@gobble
1727 \let\sameword\sameword@inedtext%
1728 \let\edtext=dummy@edtext
1729 \let\edindex\dummy@edindex%
1730 \l@dtabnoexpands
1731 \l@noexpands@edgl%
1732 \let\linenumannotation=\@gobble%
1733 \morenoexpands}
1734 \let\morenoexpands=\relax
1735
1736 %

```

\@tag Now, we define an empty `\@tag` command. It will be redefine by `\edtext`: its value is the first argument. It will be used by the `\Xfootnote` commands.

```

1737 \newcommand{\@tag}{}
1738 %

```

\@edtext@level This counter is increased by 1 at each level of `\edtext`.

```

1739 \newcount\@edtext@level%
1740 \@edtext@level=0%
1741 %

```

\if@edtext@secondarg@ This boolean is set to TRUE before reading the second argument of a `\edtext`. It is tested on some macro which must be executed only inside a second argument.

```

1742 \newif\if@edtext@secondarg%
1743 %

```

\theedtext The `edtext` counter is increased at each `\edtext` command. It is used to add to insert hyperlinks between a notes and the lemma.

```

1744 \newcounter{edtext}
1745 \renewcommand{\theedtext}{edtxt@the\c@edtext}%
1746 %

```

\edtext When executed, `\edtext` first ensures that we are in horizontal mode.

```

1747 \newcommand{\edtext}[2]{\leavevmode%
1748 %

```

Then, check if we are in a numbered paragraph (`\pstart... \pend`)..

```

1749 \ifnumberedpar%
1750 %

```

Check the content of the arguments, to be certain there is no forbidden command inside.

```

1751 \@check@edtext@args{#1}{#2}%
1752 %

```

We increment the `\@edtext@level` TeX counter to know in which level of `\edtext` we are.

```
1753 \global\advance\@edtext@level by 1%
1754 %
```

We also increase the `edtext` L^AT_EX counter to insert a hypertarget if the `hyperref` package is loaded, and also works with `\edtext` on right-to-left typesetting with X_YL^AT_EX.

We store the value for the current level in a global macro. So we have one macro by level of `\edtext`. That is required, because `\edtext` can contain `\edtext`.

```
1755 \stepcounter{edtext}%
1756 \csxdef{thisedtext@the\@edtext@level}{\theedtext}%
1757 %
```

By default, we do not use `\lemma`

```
1758 \global\@lemmacommand@false%
1759 %
```

```
1760 \begingroup%
1761 %
```

We get the next series of `samewords` data in the list of `samewords` data for the current `edtext` level. We push them inside `\sw@inthisedtext`.

```
1762 \ifledRcol%
1763 \ifcsvoid{sw@list@edtextR@the\@edtext@level}%
1764 {\global\let\sw@inthisedtext\empty}%
1765 {\expandafter\glp\csname sw@list@edtextR@the\@edtext@level\endcsname\to\sw@inthisedtext}%
1766 \else%
1767 \ifcsvoid{sw@list@edtext@the\@edtext@level}%
1768 {\global\let\sw@inthisedtext\empty}%
1769 {\expandafter\glp\csname sw@list@edtext@the\@edtext@level\endcsname\to\sw@inthisedtext}%
1770 \fi%
1771 %
```

`\@tag` Our normal lemma is just argument #1; but that argument could have further invocations of `\edtext` within it. We get a copy of the lemma without any `\edtext` macros within it by temporarily redefining `\edtext` to just copy its first argument and ignore the other, and then expand #1 into `\@tag`, our lemma.

This is done within a group that starts here, in order to get the original `\edtext` restored; within this group we have also turned off the expansion of those control sequences commonly found within text that can cause trouble for us.

```
1772 \global\renewcommand{\@tag}{%
1773 \no@expands #1%
1774 }%
1775 %
```


`\l@d@nums` Prepare more data for the benefit of note-generating macros: the line references and font specifier for this lemma go to `\l@d@nums`.

```
1776 \set@line%
1777 %
```

`\insert@count` will be altered by the note-generating macros: it counts the number of deferred footnotes or other insertions generated by this instance of `\edtext`. If we are in a right column (`reledpar`), we use `\insert@countR` instead of `\insert@count`.

```
1778 \ifledRcol \global\insert@countR \z@%
1779 \else \global\insert@count \z@ \fi%
1780 %
```

Now process the note-generating macros in argument #2 (i.e., `\Afootnote`, `\lemma`, etc.). `\ignorespaces` is here to skip over any spaces that might appear at the start of #2; otherwise they wind up in the main text. Footnote and other macros that are used within #2 should all end with `\ignorespaces` as well, to skip any spaces between macros when several are used in series.

```
1781 \@edtext@secondarg@true%
1782 \ignorespaces #2\relax%
1783 \@edtext@secondarg@false%
1784 %
```

With Xe_{La}TeX, you must track whether the language reads left to right (English) or right to left (Arabic). `reledmac` defines an `\if@RTL` boolean test is not already defined.

```
1785 \if@RTL%
1786 \flag@start@RTL%
1787 \else%
1788 \flag@start%
1789 \fi%
1790 %
```

We write in the numbered file whether the current `\edtext` has a `\lemma` in the the second argument.

```
1791 \if@lemmacommand@%
1792 \ifledRcol%
1793 \write\linenum@outR{\string\@lemma}%
1794 \else%
1795 \write\linenum@out{\string\@lemma}%
1796 \fi%
1797 \fi%
1798 %
```

Finally, we are ready to admit the first argument into the current paragraph.

It is important that we generate and output all the notes for this chunk of text *before* putting the text into the paragraph: notes that are referenced by line number should generally be tied to the start of the passage they gloss, not the end. That should all be done within the expansion of #2 above, or in `\aftergroup` commands within that expansion.

```

1799 \endgroup%
1800 \ifdef{\hypertarget}%
1801 {%
1802 \Hy@raisedlink@left{\hypertarget{\csuse{thisedtext@the\
@edtext@level}:start}{}}%
1803 \showlemma{#1}%
1804 \Hy@raisedlink{\hypertarget{\csuse{thisedtext@the\@edtext@level}:
end}{}}%
1805 }%
1806 {%
1807 \showlemma{#1}%
1808 }%
1809 %

```

Finally, we add any insertions that are associated with the *end* of the lemma. Footnotes that are identified by symbols rather than by where the lemma begins in the main text need to be done here, and not above.

```

1810 \ifx\end@lemmas\empty \else%
1811 \glp\end@lemmas\to\x@lemma%
1812 \x@lemma%
1813 \global\let\x@lemma=\relax%
1814 \fi%
1815 \if@RTL%
1816 \flag@end@RTL%
1817 \else%
1818 \flag@end%
1819 \fi%
1820 %

```

We switch some flags to false.

- The one that checks having footnotes inside a `\edtext`.
- The one that says we are inside a `\edtext`. In fact, it is not a flag, but a counter which is increased to 1 in each level of `\edtext`.
- The one that says we are inside a `\@lemma`.

```

1821 \global\@noneed@Footnotefalse%
1822 \global\advance\@edtext@level by -1%
1823 \global\@lemmacommand@false%
1824 %

```

We also reset `\@beforeinsertofthisedtext`

```

1825 \global\let\@beforeinsertofthisedtext\relax%
1826 %

```

If we are outside of a numbered paragraph, we send an error message and print the first argument.

```

1827 \else%
1828 \showlemma{#1} (\textbf{\textsc{Edtext outside numbered paragraph}})\
1829 \led@err@edtextoutsidestart%
1830 \fi%
1831 }%
1832 %
1833 %

```

`\@check@edtext@args` A macro which just checks the arguments of the `\edtext` and let know if there is some probleme, like, for example, `\pstart` inside.

```

1834 \newcommand{\@check@edtext@args}[2]{%
1835 \begingroup%
1836 \noexpandarg%
1837 \IfSubStr{#1}{\pstart}{\led@err@PstartInEdtext{first}}{}%
1838 \IfSubStr{#1}{\pend}{\led@err@PendInEdtext{first}}{}%
1839 \IfSubStr{#2}{\pstart}{\led@err@PstartInEdtext{second}}{}%
1840 \IfSubStr{#2}{\pend}{\led@err@PendInEdtext{second}}{}%
1841 \endgroup%
1842 }%
1843 %
1844 %

```

`\@beforeinsertofthisedtext` `\@beforeinsertofthisedtext` is an internal macro. `reledmac` or `reledpar` can add in this macro any content required to be executed before doing any `\insert` related to a `\edtext`. Its content is `\let` equal to `\relax` at the end of every `\edtext`.

```

1845 \let\@beforeinsertofthisedtext\relax
1846 %

```

`\ifnumberline` The `\ifnumberline` option can be set to `FALSE` to disable line numbering.

```

1847 \newif\ifnumberline
1848 \numberlinetrue
1849 %

```

`\set@line` The `\set@line` macro is called by `\edtext` to put the line-reference field and font specifier for the current block of text into `\l@d@nums`.

One instance of `\edtext` may generate several notes, or it may generate none — it is legitimate for argument #2 to `\edtext` to be empty. But `\flag@start` and `\flag@end` induce the generation of a single entry in `\line@list` during the next run, and it is vital to also remove one and only one `\line@list` entry here.

If no more lines are listed in `\line@list`, something is wrong — probably just some change in the input. We set all the numbers to zeros, following an old publishing convention for numerical references that have not yet been resolved.

```

1850 \newcommand*{\set@line}{%
1851 \ifledRcol

```

```

1852 \ifx\line@listR\empty
1853 \global\noteschanged@true
1854 \xdef\l@d@nums{000|000|000|000|000|000|\edfont@info}%
1855 \else
1856 \gl@p\line@listR\to\@tempb
1857 \xdef\l@d@nums{\@tempb|\edfont@info}%
1858 \global\let\@tempb=\undefined
1859 \fi
1860 \ifx\annot@listR\empty%
1861 \xdef\l@current@annotR{||}%
1862 \else%
1863 \gl@p\annot@listR\to\@tempb%
1864 \xdef\l@current@annotR{\@tempb}%
1865 \global\let\@tempb=\undefined%
1866 \fi%
1867 \else
1868 \ifx\line@list\empty
1869 \global\noteschanged@true
1870 \xdef\l@d@nums{000|000|000|000|000|000|\edfont@info}%
1871 \else
1872 \gl@p\line@list\to\@tempb
1873 \xdef\l@d@nums{\@tempb|\edfont@info}%
1874 \global\let\@tempb=\undefined
1875 \fi
1876 \ifx\annot@list\empty%
1877 \xdef\l@current@annot{||}%
1878 \else%
1879 \gl@p\annot@list\to\@tempb%
1880 \xdef\l@current@annot{\@tempb}%
1881 \global\let\@tempb=\undefined%
1882 \fi%
1883 \fi}
1884
1885 %

```

`\edfont@info` The macro `\edfont@info` returns coded information about the current font.

```

1886 \newcommand*{\edfont@info}{\f@encoding/\f@family/\f@series/\f@shape}
1887
1888 %

```

VI.2 Substitute lemma

`\lemma` The `\lemma{<text>}` macro allows you to change the lemma that is passed on to the notes. Read about `\@tag` in normal `\edtext` macro for more details about `\sw@list@inedtext` and `\no@expands` (VI.1 p. 144).

```

1889 \newcommand*{\lemma}[1]{%
1890 \global\@lemmacommand@true%

```

```

1891 \global\renewcommand{\@tag}{%
1892 \no@expands #1%
1893 }%
1894 \ignorespaces%
1895 }%
1896 %

```

\@lemma The \@lemma is written in the numbered file to set which \edtext has an \lemma as second argument.

```

1897 \newcommand{\@lemma}{%
1898 \booltrue{lemmacommand@the\@edtext@level}%
1899 }%
1900 %

```

\if@lemmacommand@ This boolean is set to TRUE inside a \edtext (or \critext) when a \lemma command is called. That is useful for some commands which can have a different behavior if the lemma in the note is different from the lemma in the main text.

```

1901 \newif\if@lemmacommand@%
1902 %

```

VI.3 Substitute line numbers

\linenum The \linenum macro can change any or all of the page and line numbers that are passed on to the notes.

As argument \linenum takes a set of seven parameters separated by vertical bars, in the format used internally for \l@d@nums (see V.9 p. 113): the starting page, line, and sub-line numbers, followed by the ending page, line, and sub-line numbers, and then the font specifier for the lemma. However, you can omit any parameters you do not want to change, and you can omit a string of vertical bars at the end of the argument. Hence \linenum{18|4|0|18|7|1|0} is an invocation that changes all the parameters, but \linenum{|3} only changes the starting line number, and leaves the rest unaltered.

We use \ as an internal separator for the macro parameters.

```

1903 \newcommand*{\linenum}[1]{%
1904 \xdef\@tempa{#1||||||\noexpand\\\l@d@nums}%
1905 \global\let\l@d@nums=\empty
1906 \expandafter\line@set\@tempa\\\ignorespaces}
1907 %

```

\line@set \linenum calls \line@set to do the actual work; it looks at the first number in the argument to \linenum, sets the corresponding value in \l@d@nums, and then calls itself to process the next number in the \linenum argument, if there are more numbers in \l@d@nums to process.

```

1908 \def\line@set#1|#2|#3|#4\\{%
1909 \gdef\@tempb{#1}%

```

```

1910 \ifx\@tempb\empty
1911 \l@d@add{#3}%
1912 \else
1913 \l@d@add{#1}%
1914 \fi
1915 \gdef\@tempb{#4}%
1916 \ifx\@tempb\empty\else
1917 \l@d@add{|\line@set#2\|#4\}%
1918 \fi}
1919 %

```

`\l@d@add` `\line@set` uses `\l@d@add` to tack numbers or vertical bars onto the right hand end of `\l@d@nums`.

```

1920 \newcommand{\l@d@add}[1]{\xdef\l@d@nums{\l@d@nums#1}}
1921
1922 %

```

`\lineannot` Last but not least, `\lineannot` allows us to substitute line number annotation. It is different from `\linenum` for backward compatibility with older versions of `reledmac`. It calls `\lineannot@set` to determine whether we must change only one annotation or two, or none.

`\lineannot@set`

```

1923 \newcommand*{\lineannot}[1]{%
1924 \lineannot@set#1|}%
1925 }%
1926 \def\lineannot@set#1|#2|{%
1927 \expandafter\parse@annot#1|#2|}%
1928 \IfStrEq{#1}{}%
1929 {\let\@tempa\annot@start}%
1930 {\def\@tempa{#1}}}%
1931 \IfStrEq{#2}{}%
1932 {\let\@tempb\annot@start}%
1933 {\def\@tempb{#2}}}%
1934 \xdef\l@current@annot{\@tempa|\@tempb}%
1935 }%
1936 %

```

VI.4 Lemma disambiguation

The mechanism which counts the occurrence of a same word in a same line is quite complex, because, when \LaTeX reads a command between a `\pstart` and a `\pend`, it does not know yet which are the line numbers.

The general mechanism is the following:

- **At the first run**, each `\sameword` command increments an `etoolbox` counter the name of which contains the argument of the `\sameword` commands.

- Then this counter associated with the argument of `\sameword` is stored with the `\@sw` command in the auxiliary file of the current `reledmac` section (the `.1`, `.2...` file).
- **When this auxiliary file is read at the second run**, different operations are achieved:

1. Get the rank of each `\sameword` in a line (relative rank) from the rank of each `\sameword` in all the numbered section (absolute rank):

- For each paired `\sameword` argument and absolute line number, a counter is defined. Its value corresponds to the number of times `\sameword{⟨argument⟩}` is called from the beginning of the lineation to the end of the current line. We also store the same data for the preceding absolute line number, if it does not have `\sameword{⟨argument⟩}`.
- For each `\sameword` having the same argument, we subtract from its absolute rank the number stored for the paired `\sameword` argument and previous absolute line number. Consequently, we obtain the relative rank.
- See the following example which explains how, for same `\sameword`, absolute ranks are transformed to relative ranks.

```
At line 1:
absolute rank 1 becomes relative rank 1-0 = 1
1 is stored for this \sameword and line 1
At line 2:
absolute rank 2 becomes relative rank 2-1 = 1
absolute rank 3 becomes relative rank 3-1 = 2
3 is stored for this \sameword and line 2
At line 3:
no \sameword for this line.
3 is stored for this \sameword and line 3
At line 4:
absolute rank 4 becomes relative rank 4-3 = 1
4 is stored for this \sameword and line 4
```

2. Create lists of lists of `\sameword` by depth of `\edtext`. That is: create a list for `\edtexts` of level 1, a list for `\edtexts` of level 2, a list for `\edtexts` of level 3 etc. For each `\edtext` in these lists, we store all of the relative ranks of `\sameword` which are called as lemma information. That is: 1) either called in the first argument of `\sameword`, or, 2) called in the `\lemma` macro of the second argument of `\sameword` AND marked by the optional argument of `\sameword` in first argument of `\edtext`.

For example, suppose a line with nested `\edtexts` which contains some word marked by `\sameword` and having the following relative rank:

bar¹ foo¹ foo² bar² foo³ (A)(B) foo⁴ bar³ (C) foo⁵ (D) bar⁴ (E)

In this example, all lemma information for `\edtext` is framed. The text in parenthesis is the content of critical notes associated to the preceding frame. As you can see, we have two levels of `\edtext`.

The list for `\edtexts` of level 1 is $\{\{1, 2, 2, 3, 4, 3\}, \{5, 4\}\}$.

The list for `\edtexts` of level 2 is $\{\{1, 2, 2, 3\}, \{5\}\}$.

As you can see, the mandatory argument of `\sameword` does not matter: we store the rank informations for every word potentially ambiguous.

- At the second run, when a critical notes is called, we associate it to the next item of the list associated to its `\edtext` level. So, in the previous example:
 - Critical notes (A) and (B) are associated with $\{1, 2, 2, 3\}$.
 - Critical note (C) is associated with $\{1, 2, 2, 3, 4, 3\}$.
 - Critical note (D) is associated with $\{5\}$.
 - Critical note (E) is associated with $\{5, 4\}$.
- At the second run, when a critical note is printed:
 - The `\sameword` command is let `\sameword@inedtext`.
 - At each call of this `\sameword@inedtext`, we step to the next element of the list associated to the note. Let it be r .
 - For the word marked by `\sameword`, we calculate how many time it is called in its line. To do it:
 - * We get the absolute line number of the current `\sameword`. This absolute line number was stored with a list of relative ranks for the current `\edtext`. That means, in the previous example, that if the absolute line number of `\edtext` was 1, that critical notes (A) and (B) were not associated with $\{1, 2, 2, 3\}$ but with $\{(1, 1), (2, 1), (2, 1), (3, 1)\}$. Such a method of knowing the absolute line number associated to a `\sameword` is required because a `\edtext` can overlap many lines, but `\sameword` can't get it.
 - * When reading the auxiliary file, we get the value associated to the pair composed by the current marked word and the current absolute line number. To this value, we subtract the value associated to the pair composed by the current marked word and the previous absolute line number. Let the result be n .
 - If $n > 1$, that means the current word appears more than once in its line. In this case, we call `\showwordrank` with the word as the first argument and r as the second argument. If the word is called only once, we just print it.

After theory, implementation. First, getting a sanitized form of the argument of `\sameword`


```
\get@sw@txt 37 \newcommand{\get@sw@txt}[1]{%
1938 \begingroup%
1939 \swnoexpands%
1940 %.
```

Using case sensibility option.

```
1941 \ifsw@caseinsensitive%
1942 \def\tmpa##1{\lowercase{##1}}%
1943 \else%
1944 \def\tmpa##1{##1}%
1945 \fi%
1946 %
```

And now, define \sw@txt.

```
1947 \tmpa{\protected@xdef\sw@txt{##1}}%
1948 \endgroup%
1949 }%
1950 %
```

Allow some macros inside \sameword. We use \RenewExpandableDocumentCommand to get expandable command with optional argument. Cf. <https://tex.stackexchange.com/a/384783/7712>.

```
\sw@noexpand 51 \newcommand{\swnoexpands}{%
1952 \let\sameword\l@secondmandarg% Allow to have nested \sameword
1953 \let\emph\@firstofone%
1954 \let\textit\@firstofone%
1955 \let\textbf\@firstofone%
1956 \let\textsc\@firstofone%
1957 \let\framebox\@firstofone%
1958 \let\edtext\dummy@edtext%
1959 \RenewExpandableDocumentCommand{\edindex}{om}{}%
1960 \ifdefined\index%
1961 \RenewExpandableDocumentCommand{\index}{om}{}%
1962 \fi%
1963 \let\selectlanguage\@gobble%
1964 \let\foreignlanguage\@secondoftwo%
1965 \ifdefined\lpg@loaded%
1966 \renewcommand\do[1]{%
1967 \expandafter\RenewExpandableDocumentCommand\expandafter{\csname
text##1\endcsname}{om}{###2}}%
1968 }%
1969 \expandafter\docsvlist\expandafter{\lpg@loaded}%
1970 \fi%
1971 }%
1972 %
```

`\sameword` The high level macro \sameword, used by the editor.

```

1973 \newcommandx{\sameword}[2][1,usedefault]{%
1974     \ifxetex%
1975     \if@RTL%
1976     \led@err@samewordRTL%
1977     \fi%
1978     \fi%
1979     \leavevmode%
1980     \get@sw@txt{#2}%
1981 %

```

Now, the real code. First, increment the counter corresponding to the argument.

```

1982 \unless\ifledRcol%
1983     \csnumgdef{sw@sw@txt}{\csuse{sw@sw@txt}+\@ne}%
1984 %

```

Then, write its value to the numbered file.

```

1985 \protected@write\linenum@out{}{\string\@sw{sw@txt}{\csuse{sw@sw@txt}
1986 }}{#1}}%

```

Do the same thing if we are in the right column.

```

1987 \else%
1988     \csnumgdef{sw@sw@txt}{\csuse{sw@sw@txt}+\@ne}%
1989     \protected@write\linenum@outR{}{\string\@sw{sw@txt}{\csuse{sw@sw@txt}
1990 }}{#1}}%
1991 \fi%

```

And print the word.

```

1992 #2%
1993 }%
1994 %

```

A flag set to true if a \@sw relative rank must be added to the list of ranks for a specific \edtext.

```

\if@addsw%5 \newif\if@addsw%
1996 %

```

\@sw The command printed in the auxiliary files.

```

1997 \newcommand{\@sw}[3]{%
1998     \get@sw@txt{#1}%
1999     \unless\ifledRcol%
2000 %

```

First, define a counter which store the second argument as value for a each paired absolute line number/first argument

```

2001 \csxdef{sw@sw@txt @\the\absline@num @\the\section@num}{#2}%
2002 %

```

If such argument was not defined for the preceding line, define it.

```

2003 \numdef{\prev@line}{\the\absline@num-1}%
2004 \ifcsundef{sw@sw@txt @\prev@line @\the\section@num}{%
2005   \csnumgdef{sw@sw@txt @\prev@line @\the\section@num}{#2-1}%
2006   }{}%
2007 %

```

Then, calculate the position of the word in the line.

```

2008 \numdef{\the@sw}{#2-\csuse{sw@sw@txt @\prev@line @\the\section@num}}%
2009 %

```

And do the same thing for the right side.

```

2010 \else%
2011   \csxdef{sw@sw@txt @\the\absline@numR @\the\section@numR @R}{#2}%
2012   \numdef{\prev@line}{\the\absline@numR-1}%
2013   \ifcsundef{sw@sw@txt @\prev@line @\the\section@numR @R}{%
2014     \csnumgdef{sw@sw@txt @\prev@line @\the\section@numR @R}{#2-1}%
2015     }{}%
2016   \numdef{\the@sw}{#2-\csuse{sw@sw@txt @\prev@line @\the\section@numR @R}}%
2017   \fi%
2018 %

```

And now, add it to the list of \@sw for the current edtext, in all depth.

```

2019 \@tempcnta=\@edtext@level
2020 \@whilenum{\@tempcnta>0}\do{%
2021   \ifcsdef{sw@list@edtext@tmp@\the\@tempcnta}%
2022     {%
2023       \@addswfalse%
2024       \notbool{lemmacommand@\the\@tempcnta}%
2025       {\@addswtrue}%
2026       {\IfStrEq{#3}{inlemma}%
2027         {\@addswtrue}%
2028         {%
2029           \def\do##1{%
2030             \ifnumequal{##1}{\the\@tempcnta}%
2031               {\@addswtrue\listbreak}%
2032             }%
2033           }%
2034           \docsvlist{#3}%
2035         }%
2036       }%
2037     \if@addsw%
2038       \letcs{\@tmp}{sw@list@edtext@tmp@\the\@tempcnta}%
2039       \ifledRcol%
2040         \xright@appenditem{\the@sw}{\the\absline@numR}}\to\@tmp%

```

```

2041         \else%
2042             \xright@appenditem{{\the@sw}{\the\absline@num}}\to\@tmp%
2043         \fi%
2044         \cslet{sw@list@edtext@tmp@\the\@tempcnta}{\@tmp}%
2045     \fi%
2046 }%
2047 {}%
2048 \advance\@tempcnta by -1%
2049 }%
2050 }%
2051 %

```

`\sameword@inedtext` The command called when `\sameword` is called in a `\edtext`.

```

2052 \newcommandx{\sameword@inedtext}[2][1,usedefault]{%
2053     \get@sw@txt{#2}%
2054     \unless\ifledRcol@%
2055 %

```

Just a precaution.

```

2056     \ifx\sw@list@inedtext\empty%
2057         \def\the@sw{999}%
2058         \def\this@absline{-99}%
2059     \else%
2060 %

```

But in many cases, at this step, we should have some content in the list `\sw@list@inedtext`, which contains the reference for `\edtext`.

```

2061     \glp\sw@list@inedtext\to\@tmp%
2062     \edef\the@sw{\expandafter\@firstoftwo\@tmp}%
2063     \edef\this@absline{\expandafter\@secondoftwo\@tmp}%
2064     \fi%
2065 %

```

First, calculate the number of occurrences of the word in the current line

```

2066     \ifcsdef{sw@\sw@txt @\this@absline @\the\section@num}{%
2067         \numdef{\prev@line}{\this@absline-1}%
2068         \numdef{\sw@atthisline}{\csuse{sw@\sw@txt @\this@absline @\the\
section@num}-\csuse{sw@\sw@txt @\prev@line @\the\section@num}}%
2069     }%
2070     {\numdef{\sw@atthisline}{0}}%
2071 %

```

Finally, print the rank, but only if there is more than one occurrence of the word in the current line.

```

2072     \ifnumgreater{\sw@atthisline}{1}%
2073         {\showwordrank{#2}{\the@sw}}%
2074         {#2}%
2075 %

```

And the same for right side.

```

2076 \else%
2077 \ifx\sw@list@inedtext\empty%
2078 \def\the@sw{999}%
2079 \def\this@absline{-99}%
2080 \else%
2081 \gl@p\sw@list@inedtext\to\@tmp%
2082 \edef\the@sw{\expandafter\@firstoftwo\@tmp}%
2083 \edef\this@absline{\expandafter\@secondoftwo\@tmp}%
2084 \fi%
2085 \ifcsdef{sw@\sw@txt @\this@absline @\the\section@numR @R}{%
2086 \numdef{\prev@line}{\this@absline-1}%
2087 \numdef{\sw@atthisline}{\csuse{sw@\sw@txt @\this@absline @\the\
section@numR @R}-\csuse{sw@\sw@txt @\prev@line @\the\section@numR @R}}%
2088 }%
2089 {\numdef{\sw@atthisline}{0}}%
2090 \ifnumgreater{\sw@atthisline}{1}%
2091 {\showwordrank{#2}{\the@sw}}%
2092 {#2}%
2093 \fi%
2094 }%
2095 %

```

`\showwordrank` Finally, the way the rank will be printed.

```

2096 \newcommand{\showwordrank}[2]{%
2097 #1\textsuperscript{#2}%
2098 }%
2099 %

```

VII Paragraph decomposition and reassembly

In order to be able to count the lines of text and affix line numbers, we add an extra stage of processing for each paragraph. We send the paragraph into a box register, rather than straight onto the vertical list, and when the paragraph ends we slice the paragraph into its component lines; to each line we add any notes or line numbers, add a command to write to the line-list, and then at last send the line to the vertical list. This section contains all the code for this processing.

VII.1 Boxes, counters, `\pstart` and `\pend`

`\raw@text` Here are numbers and flags that are used internally in the course of the paragraph decomposition.

`\ifnumberedpar@` When we first form the paragraph, it goes into a box register, `\raw@text`, instead of onto the current vertical list. The `\ifnumberedpar@` flag will be true while a paragraph is being processed in that way. `\num@lines` will store the number of lines in the paragraph when it is complete. When we chop it up into lines, each line in turn goes

`\numberedpar@true`

`\numberedpar@false`

`\num@lines`

`\one@line`

`\par@line`

into the `\one@line` register, and `\par@line` will be the number of that line within the paragraph.

```

2100 \newbox\raw@text
2101 \newif\ifnumberedpar@
2102 \newcount\num@lines
2103 \newbox\one@line
2104 \newcount\par@line
2105 %

```

`\pstarts@typeset@L` The `\pstarts@typeset@L` counts the number of LEFT `\pstart` typeset. A left `\pstart` can be a `\pstart` typeset in normal mode, or `\pstart` typeset in left column or page in parallel mode (`withreledpar`). In the first case, its value is increased at every `\pstart` command. In the second case, its value is increased in `\Columns` or `\Pages` when we prepare to typeset a left `\pstart`. The `\pstarts@read@L` counts the number of LEFT `\pstart` read. A left `\pstart` can be a `\pstart` typeset in normal mode, or `\pstart` typeset in left column or page in parallel mode (`withreledpar`). In the first case, its value is increased at every `\pstart` command. In the second case, its value is increased at every `\pstarL`.

```

2106 \newcount\pstarts@typeset@L%
2107 \newcount\pstarts@read@L%
2108 %

```

`\pstart` `\pstart` starts the paragraph by clearing the `\inserts@list` list and other relevant variables, and then arranges for the subsequent text to go into the `\raw@text` box.
`\AtEveryPstart` `\pstart` needs to appear at the start of every paragraph that is to be numbered; the
`\AtStartEveryPstart` `\autopar` command below may be used to insert these commands automatically.
`\numberpstarttrue`
`\numberpstartfalse`

Beware: everything that occurs between `\pstart` and `\pend` is happening within a group; definitions must be global if you want them to survive past the end of the paragraph.
`\labelpstarttrue`
`\labelpstartfalse`

```

\thepstart
\if@every@pstart@star@
2109 \newcommand{\AtStartEveryPstart}[1]{%
2110   \ifstrempy{#1}%
2111   {\gdef\@at@start@every@pstart{}}%
2112   {\gdef\@at@start@every@pstart{#1}}%
2113 }%
2114 \def\@at@start@every@pstart{}%
2115
2116 \newif\if@every@pstart@star@%
2117 \newcommand{\AtEveryPstart}[1]{%
2118   \ifstrempy{#1}%
2119   {\gdef\@at@every@pstart{}}%
2120   {\gdef\@at@every@pstart{\noindent#1}}%
2121   \global\@at@every@pstart@star@false%
2122 }%
2123 \WithSuffix\newcommand\AtEveryPstart*[1]{%
2124   \ifstrempy{#1}%
2125

```

```

2126     {\gdef\at@every@pstart{}}%
2127     {\gdef\at@every@pstart{#1}}%
2128     \global\at@every@pstart@star@true%
2129 }%
2130 \def\at@every@pstart{}%
2131
2132 \newcounter{pstart}
2133 \renewcommand{\the pstart}{\bfseries\@arabic\c@pstart}. }
2134 \newif\ifnumberpstart
2135 \numberpstartfalse
2136 \newif\iflabelpstart
2137 \labelpstartfalse
2138 \newcommandx*\pstart}[2][1,2,usedefault]{%
2139     \normal@pars%
2140     \ifboolexpr{%
2141         test {\ifstrempy{#1}}%
2142         and test {\ifstrempy{#2}}%
2143     }%
2144     {\at@every@pstart}%
2145     {%
2146         \ifstrempy{#1}{\noindent#1}%
2147         \ifstrempy{#2}{\#2}%
2148     }%
2149     \ifautopar%
2150         \autopar%
2151     \fi%
2152     \ifluatex%
2153         \edef\l@luatextextdir@L{\the\textdir}%
2154     \fi%
2155     \@nobreaktrue%
2156     \ifnumbering \else%
2157         \led@err@PstartNotNumbered%
2158         \beginnumbering%
2159     \fi%
2160     \ifnumberedpar@%
2161         \led@err@PstartInPstart%
2162         \pend%
2163     \fi%
2164     \list@clear{\inserts@list}%
2165     \global\let\next@insert=\empty%
2166     \begingroup\normal@pars%
2167     \global\advance \l@dnumpstartsL\@ne
2168     \global\advance \pstarts@typeset@L\@ne%
2169     \global\advance \pstarts@read@L\@ne%
2170     \global\setbox\raw@text=\vbox\bgroup%
2171     \if@nobreak%
2172         \if@afterindent\else%
2173             \noindent%
2174             \global\@afterindenttrue%
2175         \fi%

```

```

2176 \fi%
2177 \ifboolexpr{%
2178   bool{autopar}%
2179   and bool{by@autopar}%
2180 }%
2181 {}%
2182 {%
2183   \ifnumberpstart%
2184   \ifinstanza\else%
2185   \ifsidepstartnum\else%
2186   \thepstart%
2187   \fi%
2188   \fi%
2189   \fi%
2190 }%
2191 \numberedpar@true%
2192 \iflabelpstart%
2193   \protected@edef\@currentlabel{\p@pstart\thepstart}%
2194 \fi%
2195 \l@dzeroopenalties%
2196 \@at@start@every@pstart%
2197 \global\by@autoparfalse%
2198 \ignorespaces%because not automatically ignored if an optional argument
is used (classical TeX behavior for space after commands)
2199 }
2200 %

```

\pend \pend must be used to end a numbered paragraph.

```

2201 \newcommandx*\pend{2}[1,2,usedefault]{\ifnumbering \else%
2202   \led@err@PendNotNumbered%
2203   \fi%
2204   \global\l@dskipversenumberfalse%
2205   \ifnumberedpar@ \else%
2206   \led@err@PendNoPstart%
2207   \fi%
2208 %

```

We set all the usual interline penalties to zero and then immediately call `\endgraf` to end the paragraph; this ensures that there will be no large interline penalties to prevent us from slicing the paragraph into pieces. These penalties revert to the values that you set when the group for the `\vbox` ends. Then we call `\do@line` to slice a line off the top of the paragraph, add a line number and footnotes, and restore it to the page; we keep doing this until there are not any more lines left.

```

2209 \l@dzeroopenalties%
2210 \@at@end@every@pend%
2211 \endgraf\global\num@lines=\prevgraf\egroup%
2212 \global\par@line=0%
2213 \get@firsthalf@antilabe@wd%
2214 %

```


Output the lines.

```
2215 \loop\ifvbox\raw@text%
2216 \do@line%
2217 \repeat%
2218 %
```

Deal with any leftover notes, and then end the group that was begun in the `\pstart`.

```
2219 \flush@notes%
2220 \endgroup%
2221 \ignorespaces%
2222 %
```

Increase `pstart` counter.

```
2223 \ifnumberpstart%
2224 \global\pstartnumtrue%
2225 \fi%
2226 \addtocounter{pstart}{1}%
2227 \ifcontinuousnumberingwithcolumns%
2228 \addtocounter{pstartL}{1}%
2229 \addtocounter{pstartR}{1}%
2230 \fi%
2231 %
```

Print the optional arguments of `\pend` or the content printed after every `\pend`

```
2232 \normal@pars%
2233 \ifboolexpr{%
2234 test {\ifstrempy{#1}}%
2235 and test {\ifstrempy{#2}}%
2236 }%
2237 {\at@every@pend}%
2238 {%
2239 \ifstrempy{#1}{\noindent#1}%
2240 \ifstrempy{#2}{\#2}%
2241 }%
2242 %
```

Restore standard “nobreak” and “autopar” settings. Normally, `\if@nobreak` is true only immediately after a sectioning command (see `latex.ltx` file). As a `\pstart... \pend` structure can’t contain any sectioning command, we set `\if@nobreak` to false.

```
2243 \@nobreakfalse%
2244 \ifautopar%
2245 \autopar%
2246 \fi%
2247 %
```

At the very end, we check if the lineation is made by `\pstart`. In this case, we reset the line number, using `\setlinenum`, as we are, technically, already out of `\pstart\pend` structure.

```

2248 \ifbypstart{%
2249     \begingroup%
2250     \unless\ifinstanza%
2251     \let\leavevmode\relax%
2252     \setlinenum{0}%
2253     \fi%
2254     \endgroup%
2255     \resetprevline@%
2256     \fi%
2257 }
2258 %

```

Here, two macros to insert content after every `\pend`, between numbered line. `\AtEveryPend` is the user macro, `\at@every@pend` is macro set by it.

```

\AtEveryPend59
\at@every@pend60
\ifat@every@pend@star@61 \newif\ifat@every@pend@star@%
2262 \newcommand{\AtEveryPend}[1]{%
2263     \ifstrepty{#1}%
2264     {\gdef\at@every@pend{}}%
2265     {\gdef\at@every@pend{\noindent#1}}%
2266     \global\at@every@pend@star@false%
2267 }%
2268 \WithSuffix\newcommand\AtEveryPend*[1]{%
2269     \ifstrepty{#1}%
2270     {\gdef\at@every@pend{}}%
2271     {\gdef\at@every@pend{#1}}%
2272     \global\at@every@pend@star@true%
2273 }%
2274 \xdef\at@every@pend{}%
2275
2276 %

```

\AtEndEveryPend Here a macro to insert automatically any content at the end of `\pend`, in numbered lines.

```

2277 \newcommand{\AtEndEveryPend}[1]{%
2278     \ifstrepty{#1}%
2279     {\xdef\@at@end@every@pend{}}%
2280     {\gdef\@at@end@every@pend{#1}}%
2281 }%
2282 \def\@at@end@every@pend{}%
2283 %

```

\l@dzero penalties A macro to zero penalties for `\pend` or `\pstart`.

```

2284 \newcommand*{\l@dzero penalties}{%
2285     \brokenpenalty \z@ \clubpenalty \z@
2286     \displaywidowpenalty \z@ \interlinepenalty \z@ \predisplaypenalty \z@

```

```

2287 \postdisplaypenalty \z@ \widowpenalty \z@}
2288
2289 %

```

`\autopar` In most cases it is only an annoyance to have to label the paragraphs to be numbered with `\pstart` and `\pend`. `\autopar` will do that automatically, allowing you to start a paragraph with its first word and no other preliminaries, and to end it with a blank line or a `\par` command. The command should be issued within a group, after `\beginnumbering` has been used to start the numbering; all paragraphs within the group will be affected.

A few situations can cause problems. One is a paragraph that begins with a begin-group character or command: `\pstart` will not get invoked until after such a group beginning is processed; as a result the character that ends the group will be mistaken for the end of the `\vbox` that `\pstart` creates, and the rest of the paragraph will not be numbered. Such paragraphs need to be started explicitly using `\indent`, `\noindent`, or `\leavevmode` — or `\pstart`, since you can still include your own `\pstart` and `\pend` commands even with `\autopar` on.

Prematurely ending the group within which `\autopar` is in effect will cause a similar problem. You must either leave a blank line or use `\par` to end the last paragraph before you end the group.

The functioning of this macro is more tricky than the usual `\everypar`: we do not want anything to go onto the vertical list at all, so we have to end the paragraph, erase any evidence that it ever existed, and start it again using `\pstart`. We remove the paragraph-indentation box using `\lastbox` and save the width, and then skip backwards over the `\parskip` that has been added for this paragraph. Then we start again with `\pstart`, restoring the indentation that we saved, and locally change `\par` so that it will do our `\pend` for us.

The boolean `\ifautopar` is set to TRUE while `\autopar` is enabled, and the `\ifby@autopar` is set to TRUE at each `\pstart` automatically called by the `\autopar` feature. A manual `\pstart` will have a `\ifby@autopar` set to FALSE.

```

2290 \newif\ifautopar
2291 \newif\ifby@autopar%
2292 \newcommand*{\autopar}{
2293   \ifledRcol
2294     \ifnumberingR \else
2295       \led@err@AutoparNotNumbered
2296       \beginnumberingR
2297       \fi
2298     \else
2299       \ifnumbering \else
2300         \led@err@AutoparNotNumbered
2301         \beginnumbering
2302         \fi
2303       \fi
2304       \autopartrue
2305       \everypar{\setbox0=\lastbox
2306                 \endgraf \vskip-\parskip

```

```

2307 \global\by@autopartrue%
2308 \pstart \noindent \kern\wd0%
2309 \ifnumberpstart%
2310 \ifinstanza\else%
2311 \thepstart%
2312 \fi%
2313 \fi%
2314 \let\par=\pend}%
2315 \ignorespaces}
2316 %

```

\normal@pars We also define a macro which we can rely on to turn off the \autopar definitions at various important places, if they are in force. We will want to do this within a footnotes, for example.

```

2317 \newcommand*{\normal@pars}{\everypar{}\let\par\endgraf}
2318
2319 %

```

\ifautopar@pause We define a boolean test switched to true at the beginning of the \pausenumbering command if the autopar is enabled. This boolean will be tested at the beginning of \resumenumbering to continue the autopar if needed.

```

2320 \newif\ifautopar@pause
2321 %

```

VII.2 Processing one line

VII.2.1 General process

\do@line The \do@line macro is called by \pend to do all the processing for a single line of text. The **\l@dunhbox@line** macro only \unhboxes one line, but packages like \microtype can override it as required.

```

2322 \newcommand*{\l@dunhbox@line}[1]{\unhbox #1}
2323 \newcommand*{\do@line}{%
2324 {\vbadness=10000
2325 \splittopskip=\z@
2326 \do@linehook
2327 \l@demtyd@ta
2328 \global\setbox\one@line=\vsplit\raw@text to\baselineskip}%
2329 \unvbox\one@line \global\setbox\one@line=\lastbox
2330 \getline@num
2331 \IfStrEq{\led@pb@setting}{before}{\led@check@pb\led@check@nopb}{%}
2332 \ifnum\@lock>\@ne
2333 \inserthangingsymboltrue
2334 \else
2335 \inserthangingsymbolfalse
2336 \fi

```

```

2337 \check@pb@in@verse
2338 \ifl@dhidenumber%
2339 \global\l@dhidenumberfalse%
2340 \f@x@l@cks%
2341 \else%
2342 \affixline@num%
2343 \fi%
2344 %

```

Depending whether a sectioning command is called at this pstart or not we print sectioning command or normal line,

```

2345 \xifinlist{\the\pstarts@typeset@L}{\eled@sections@@}%
2346 {\print@eledsection}%
2347 {\print@line}%
2348 \IfStrEq{\led@pb@setting}{after}{\led@check@pb\led@check@nopb}{%}
2349 }%
2350 %

```

VII.2.2 Process for “normal” line

\print@line \print@line is for normal line, i. e. line without sectioning command.

```

2351 \def\print@line{
2352 %

```

Insert the pstart number inside, if we are in the first line of a pstart.

```

2353 \affixpstart@num%
2354 %

```

The line will be boxed, to have the good width.

```

2355 \hb@xt@ \linewidth{%
2356 %

```

User hooks.

```

2357 \do@insidelinehook%
2358 \csuse{insidethis@the\absline@num @the\section@num}%
2359 \global\csundef{insidethis@the\absline@num @the\section@num}%
2360 %

```

Left line number

```

2361 \l@dld@ta%
2362 %

```

Prepare text to be inserted before notes.

```

2363 \if@firstlineofpage%
2364 \set@Xtxtbeforenotes%
2365 \set@txtbeforenotesX%
2366 \global\@firstlineofpagefalse%
2367 \fi%
2368 %

```

Insert footnotes made of manuscripts data and critical footnotes.

```

2369 \ifdefstring{\ms@data@position}{msdata-regular}{%
2370 \insert@msdata%
2371 \add@inserts%
2372 \add@Xgroupbyline%
2373 }{%
2374 \add@inserts%
2375 \add@Xgroupbyline%
2376 \insert@msdata%
2377 }%
2378 %

```

Insert marginal notes.

```

2379 \affixside@note%
2380 %

```

Print left notes.

```

2381 \l@dlsn@te
2382 %

```

Boxes the line, writes information about new line in the numbered file.

```

2383 {\ledllfill\hb@xt@ \wd\one@line{%
2384 \new@line%
2385 %

```

If we use the continuousnumberingwithcolumns, we increase right line number.

```

2386 \continuousnumberingwithcolumns@sync@linenumber@singletext%
2387 %

```

If we use Lua \LaTeX then restore the direction.

```

2388 \ifluatex%
2389 \texdir\l@luatextextdir@L%
2390 \fi%
2391 %

```

Insert, if needed, the hanging symbol.

```

2392 \inserthangingsymbol%
2393 %

```

And so, print the line.

```

2394 \l@dunhbox@line{\one@line}}%
2395 %

```

Right line number

```

2396 \ledrlfill\l@drd@ta%
2397 %

```

Print right notes.

```

2398         \l@drsn@te%
2399     }}%
2400 %

```

And reinsert penalties (for page breaking)...

```

2401     \add@penalties%
2402 }
2403 %

```

VII.2.3 Process for line containing \eledsection command

\print@eledsection \print@eledsection to print sectioning command with line number. It sets the correct spacing, depending whether a sectioning command was called at previous \pstart, calls the sectioning command, prints the normal line outside of the paper, to be able to have critical footnotes. Because of how this prints, a vertical spacing correction is added.

```

2404 \def\print@eledsection{%
2405     \disable@edindex%
2406     \if@firstlineofpage%
2407         \set@Xtxtbeforenotes%
2408         \set@txtbeforenotesX%
2409         \global\@firstlineofpagefalse%
2410     \fi%
2411     \ifdefstring{\ms@data@position}{msdata-regular}{%
2412         \insert@msdata%
2413         \add@inserts%
2414         \add@Xgroupbyline%
2415     }{%
2416         \add@inserts%
2417         \add@Xgroupbyline%
2418         \insert@msdata%
2419     }%
2420     \affixside@note%
2421     \numdef{\temp@}{\pstarts@typeset@L-1}%
2422     \xifinlist{\temp@}{\eled@sections@}{\@nbreaktrue}{\@nbreakfalse}%
2423     \@eled@sectioningtrue%
2424     \csuse{eled@sectioning@the\pstarts@typeset@L}%
2425     \@eled@sectioningfalse%
2426     \global\csundef{eled@sectioning@the\pstarts@typeset@L}%
2427     \if@RTL%
2428         \hspace{-3\paperwidth}%
2429     {\hbox{\l@dunhbox@line{\one@line}} \new@line}%
2430     \else%
2431         \hspace{3\paperwidth}%
2432     {\new@line \hbox{\l@dunhbox@line{\one@line}}}%
2433     \fi%
2434     \vskip-\baselineskip%
2435     \continuousnumberingwithcolumns@sync@linenumber@singletext%
2436     \restore@edindex%

```

```
2437 }
2438 %
```

VII.2.4 Hooks

`\do@linehook` Two hooks into `\do@line`. The first is called at the beginning of `\do@line`, the second
`\do@insidelinehook` is called in the line box. The second can, for example, have a `\markboth` command
inside, the first can not.

```
2439 \newcommand*\do@linehook{}
2440 \newcommand*\do@insidelinehook{}
2441 %
```

`\dolinehook` These high level commands just redefine the low level commands. They have to be used
`\doinsidelinehook` be user, without `\makeatletter`.

```
2442 \newcommand*\dolinehook[1]{\gdef\do@linehook{#1}}%
2443 \newcommand*\doinsidelinehook[1]{\gdef\do@insidelinehook{#1}}%
2444
2445 %
```

`\doinsidethislinehook` The `\doinsidethislinehook` can be called directly in the main flood of a text. It will
`\@insidethisline` define a hook executed at a specific line, determined by the position of the command in
the flood of the text.

```
2446 \newcommand{\doinsidethislinehook}[1]{%
2447   \leavevmode%In case it begins with a \pstart, ensure the \@insidethisline
    is written after \@nl
2448   \ifledRcol%
2449     \write\linenum@outR{\string\@insidethisline[\unexpanded{#1}]}%
2450   \else%
2451     \write\linenum@out{\string\@insidethisline[\unexpanded{#1}]}%
2452   \fi%
2453 }%
2454 %
```

The auxiliary files command just store the information to be executed when typesetting the specific line.

```
2455 \newcommand{\@insidethisline}[1]{%
2456   \ifledRcol%
2457     \csgappto{insidethisR@the\absline@numR @the\section@numR}{#1}%
2458   \else%
2459     \csgappto{insidethis@the\absline@num @the\section@num}{#1}%
2460   \fi%
2461 }%
2462 %
```


VII.2.5 Sidenotes and marginal line number initialization

`\l@emptyd@ta` Nulls the `\. . .d@ta`, which may later hold line numbers. Similarly for `\l@dcsnotetext`,
`\l@dld@ta` `\l@dcsnotetext@l`, `\l@dcsnotetext@r` for the texts of the sidenotes, left and right
`\l@drd@ta` notes.
`\l@dcsnotetext`
`\l@dcsnotetext@l`
`\l@dcsnotetext@r`

```

2463 \newcommand*{\l@emptyd@ta}{%
2464   \gdef\l@dld@ta{}%
2465   \gdef\l@drd@ta{}%
2466   \gdef\l@dcsnotetext@l{}%
2467   \gdef\l@dcsnotetext@r{}%
2468   \gdef\l@dcsnotetext{}%
2469
2470 %

```

`\l@dlsn@te` Zero width boxes of the left and right sidenotes, together with their kerns, and, eventu-
`\l@drsn@te` ally, with additional space if we are in parallel columns typesetting.

```

2471 \newcommand{\l@dlsn@te}{%
2472   \ifboolexpr{%
2473     bool {l@dprintingcolumns}%
2474     and bool {ledRcol}%
2475   }{% If we are on a right column
2476     \@tempdima=\@morespace@leftnote@rightcolumn%
2477   }{%
2478     \@tempdima=\z@%
2479   }%
2480   \hb@xt@ \z@{\hss\box\l@dlp@rbox\kern\ledlsnotesep\hskip\@tempdima}%
2481 }%
2482 \newcommand{\l@drsn@te}{%
2483   \ifboolexpr{%
2484     bool {l@dprintingcolumns}%
2485     and not bool {ledRcol}%
2486   }{% If we are on a left column
2487     \@tempdima=\@morespace@rightnote@leftcolumn%
2488   }{%
2489     \@tempdima=\z@%
2490   }%
2491   \hb@xt@ \z@{\hskip\@tempdima\kern\ledrsnotesep\box\l@drp@rbox\hss}%
2492 }%
2493
2494 %

```

`\ledllfill` These macros are called at the left (`\ledllfill`) and the right (`\ledrlfill`) of each
`\ledrlfill` numbered line. The initial definitions correspond to the original code for `\do@line`.

```

2495 \newcommand*{\ledllfill}{\hfil}
2496 \newcommand*{\ledrlfill}{\hfil}
2497
2498 %

```

VIII Line and page number computation

`\getline@num` The `\getline@num` macro determines the page and line numbers for the line we are about to send to the vertical list.

```

2499 \newcommand*{\getline@num}{%
2500   \global\advance\absline@num \@ne%
2501   \do@actions
2502   \do@ballast
2503   \ifnumberline
2504     \ifsublines@
2505       \ifnum\sub@lock<\tw@
2506         \global\advance\subline@num \@ne
2507       \fi
2508     \else
2509       \ifnum\@lock<\tw@
2510         \global\advance\line@num \@ne
2511         \global\subline@num \z@
2512       \fi
2513     \fi
2514   \fi
2515 }
2516 %

```

`\do@ballast` The real work in the macro above is done in `\do@actions`, but before we plunge into that, let's get `\do@ballast` out of the way. This macro looks to see if there is an action to be performed on the *next* line, and if it is going to be a page break action, `\do@ballast` decreases the count `\ballast@count` counter by the amount of ballast. This means, in practice, that when `\add@penalties` assigns penalties at this point, \TeX will be given extra encouragement to break the page here (see XII.2 p. 185).

`\ballast@count` First we set up the required counters; they are initially set to zero, and will remain so
`\c@ballast` unless you type `\setcounter{ballast}{\langle some figure \rangle}` in your document.

```

2517 \newcount\ballast@count
2518 \newcounter{ballast}
2519 \setcounter{ballast}{0}
2520 %

```

And here is `\do@ballast` itself. It advances `\absline@num` within the protection of a group to make its check for what happens on the next line.

```

2521 \newcommand*{\do@ballast}{\global\ballast@count \z@
2522   \begingroup
2523     \advance\absline@num \@ne
2524     \ifnum\next@actionline=\absline@num
2525       \ifnum\next@action>-1001\relax
2526         \global\advance\ballast@count by -\c@ballast
2527       \fi
2528     \fi

```

```

2529 \endgroup}
2530 %

```

`\do@actions` The `\do@actions` macro looks at the list of actions to take at particular absolute line numbers, and does everything that is specified for the current line.

`\do@actions@next`

It may call itself recursively, and to do this efficiently (using \TeX 's optimization for tail recursion), we define a control-sequence called `\do@actions@next` that is always the last thing that `\do@actions` does. If there could be more actions to process for this line, `\do@actions@next` is set equal to `\do@actions`; otherwise it is just `\relax`.

```

2531 \newcommand*{\do@actions}{%
2532   \global\let\do@actions@next=\relax
2533   \ifnum\absline@num<\next@actionline\else
2534   %

```

First, page number changes, which will generally be the most common actions. If we are restarting lineation on each page, this is where it happens.

```

2535   \ifnum\next@action>-1001
2536     \global\page@num=\next@action
2537     \ifresumenumbering@start%
2538       \setbox0=\hbox{}%Required to get the correct page number, when the
\resumenumbering is just after a \newpage
2539       \ifnum\pausenumbering@page@num<\page@num%
2540         \global\resumenumbering@startfalse%
2541       \fi%
2542     \fi%
2543     \ifboolexpr{%
2544       bool{resumenumbering@start}%
2545       and test {\ifdimgreater{\pagedepth}{\z@}}%
2546     }%
2547     {}%
2548     {\global\@firstlineofpagetrue}%
2549     \ifcsdef{reset@line\the\absline@num @\the\section@num}%
2550     {%
2551       \global\line@num=\z@%
2552       \global\subline@num=\z@%
2553       \resetprevline@%
2554     }%
2555     {}%
2556     \global\resumenumbering@startfalse%
2557     \add@msdata@firstlineofpage%
2558   %

```

Next, we handle commands that change the line-number values. (We subtract 5001 rather than 5000 here because the line number is going to be incremented automatically in `\getline@num`.)

```

2559   \else
2560     \ifnum\next@action<-4999
2561       \@l@tempcnta=-\next@action

```

```

2562     \advance\@l@dttempcnta by -5001
2563     \ifsublines@
2564         \global\subline@num=\@l@dttempcnta
2565     \else
2566         \global\line@num=\@l@dttempcnta
2567     \fi
2568 %

```

We rescale the value in \@l@dttempcnta so that we can use a case statement.

```

2569     \else
2570         \@l@dttempcnta=-\next@action
2571         \advance\@l@dttempcnta by -1000
2572         \do@actions@fixedcode
2573     \fi
2574 \fi
2575 %

```

Now we get information about the next action off the list, and then set \do@actions@next so that we will call ourselves recursively: the next action might also be for this line.

There is no warning if we find \actionlines@list empty, since that will always happen near the end of the section.

```

2576     \ifx\actionlines@list\empty
2577         \gdef\next@actionline{1000000}%
2578     \else
2579         \gl@p\actionlines@list\to\next@actionline
2580         \gl@p\actions@list\to\next@action
2581         \global\let\do@actions@next=\do@actions
2582     \fi
2583 \fi
2584 %

```

Make the recursive call, if necessary.

```

2585 \do@actions@next}
2586
2587 %

```

`\do@actions@fixedcode` This macro handles the fixed codes for \do@actions. It is one big case statement.

```

2588 \newcommand*{\do@actions@fixedcode}{%
2589     \ifcase\@l@dttempcnta
2590     \or%                % 1001 = starting sublineation
2591         \global\sublines@true
2592     \or%                % 1002 = ending sublineation
2593         \global\sublines@false
2594     \or%                % 1003 = starting locking number
2595         \global\@lock=\@one
2596     \or%                % 1004 = ending locking number
2597         \ifnum\@lock=\two@
2598             \global\@lock=\thr@@

```

```

2599 \else
2600 \global\@lock=\z@
2601 \fi
2602 \or% % 1005 = starting locking subnumber
2603 \global\sub@lock=\@ne
2604 \or% % 1006 = ending locking subnumber
2605 \ifnum\sub@lock=\tw@
2606 \global\sub@lock=\thr@@
2607 \else
2608 \global\sub@lock=\z@
2609 \fi
2610 \or% % 1007 = skipping numbering
2611 \l@dskipnumbertrue
2612 \or% % 1008 = skipping numbering in stanza
2613 \l@dskipversenumbertrue%
2614 \or% % 1009 = hiding number
2615 \l@dhiddenumbertrue
2616 \or% % 1010 = inserting msdata
2617 \add@msdata%
2618 \else
2619 \led@warn@BadAction
2620 \fi}
2621
2622
2623 %

```

VIII.1 Continuous line numbering between parallel typesetting and normal typesetting

`\sync@linenumber@singletext` The `\continuousnumberingwithcolumns` option allows to alternate between single text and two parallel texts, keeping the same line numbers when switching from one layout to the other. The lines counter for the text in a single column and for the text in the left column in parallel typesetting is the same. But the lines counter for the text in the same column is not the same.

When typesetting single column text, if the option is enabled, we need to “simulate” typesetting right line, in order to keep the two counters synchronized. That is the aim of the

`\continuousnumberingwithcolumns@sync@linenumber@singletext` macro.

```

2624 \newcommand{\continuousnumberingwithcolumns@sync@linenumber@singletext}{%
2625 \ifcontinuousnumberingwithcolumns%
2626 \unless\ifafterendnumberingR%
2627 \new@lineR%
2628 \xappto\next@line@list@stuffR{%
2629 \unexpanded{\global\line@numR=}\the\line@num%
2630 }%
2631 \fi%

```

```

2632 \fi%
2633 }%
2634 %

```

IX Line number annotation

The `\linenumannotation` allows users to add manual annotations to line numbers, for example to refer to line numbers from an older edition.

That implies that annotations be added

- in marginal line numbers. This feature is implemented by associating annotations with the absolute line numbers when reading the auxiliary numbered files (.1, .2 etc.).
- in critical footnotes. This feature is implemented by associating start / end line number annotations with each `\edtext` when reading the auxiliary numbered files.
- to crossref commands which refer to line numbers (to be completed when I will have resolved this issue).

`\linenumannotation` First, the user-level commands, which only write commands to the numbered files, storing the annotation.

`\resetlinenumannotation`

```

2635 \newcommand{\linenumannotation}[1]{%
2636   \leavevmode%In case it begins with a \pstart, ensure the \@annot is
written after \@nl
2637   \ifledRcol%
2638     \write\linenum@outR{\string\@annot[#1]}%
2639   \else%
2640     \write\linenum@out{\string\@annot[#1]}%
2641   \fi%
2642 }%
2643
2644 \newcommand{\resetlinenumannotation}[0]{%
2645   \leavevmode%In case it begins with a \pstart, ensure the \@resetannot is
written after \@nl
2646   \ifledRcol%
2647     \write\linenum@outR{\string\@resetannot}%
2648   \else%
2649     \write\linenum@out{\string\@resetannot}%
2650   \fi%
2651 }%
2652
2653 %

```

`\Xlinenumannotationposition@side`

The `\Xlinenumannotationposition@side` macro, to determine the position of line number annotations in lines printed in the side, relative to the line number position. The default value is “after”, but it can be changed to “before”, using the `\Xlinenumannotationposition` macro.

```

2654 \def\Xlinenumannotationposition@side{after}%
2655 %

```

`\xwraplinenumannotation@ref` The `\xwraplinenumannotation@ref` macro is applied to line annotations in crossref.
`\xwraplinenumannotation@side` The `\xwraplinenumannotation@side` macro is applied to line annotation in sides.
 They must be modified by users using `\xwraplinenumannotation`. By default, they call `\textsuperscript`.

We also define toggle `Xnoidenticallinenumannotation@ref` and `Xnoidenticallinenumannotation@ref`

```

2656 \def\xwraplinenumannotation@ref{\textsuperscript}%
2657 \def\xwraplinenumannotation@side{\textsuperscript}%
2658 \newtoggle{Xnoidenticallinenumannotation@ref}%
2659 \newtoggle{Xnoidenticallinenumannotation@side}%
2660 %

```

`\iflinenumannotationotherside` The `\iflinenumannotationotherside` boolean allows to print the annotation on the side opposite the line number.

```

2661 \newif\iflinenumannotationotherside%
2662 %

```

`\@annot` Then, the numbered files command `\@annot`, which

`\store@annot@to@absline`

- associates the annotation to the absolute lines number.
- stores the current annotation in a macro to be used by the `\@ref@reg` macro, which manages all things related to `\edtext` in numbered files. As we don't want to store it multiple times in the event of nested `\edtext`, we use an auxiliary macro, `\store@annot@to@absline`, which is set to `\gobble` when we parse nested `\edtext` in numbered auxiliary files.

```

2663 \newcommand{\@annot}[1]{%
2664   \store@annot@to@absline{#1}%
2665   \def\current@annot{#1}%
2666 }%
2667 \newcommand{\store@annot@to@absline}[1]{%
2668   \ifledRcol%
2669     \ifcsdef{annotR@the\absline@numR @the\section@numR}{%
2670       \csgappto{annotR@the\absline@numR @the\section@numR}{\
2671         @linenumannotationsep#1}%
2672       \csgdef{annotR@the\absline@numR @the\section@numR}{#1}%
2673     }%
2674   \else%
2675     \ifcsdef{annot@the\absline@num @the\section@num}{%
2676       \csgappto{annot@the\absline@num @the\section@num}{\
2677         @linenumannotationsep#1}%
2678       \csgdef{annot@the\absline@num @the\section@num}{#1}%

```

```

2679 }%
2680 \fi%
2681 }%
2682 %

```

`\current@annot` By default, there is no annotation to a line number, so we store an empty `\current@annot`

```

2683 \let\current@annot=\empty%
2684 %

```

`\reset@current@annot` `\reset@current@annot` is called at each `\@n1` in numbered auxiliary files. It resets the annotation of line numbers at each line.

`\@resetannot`

The `\@resetannot` macro is written in the auxiliary files with `\resetlinenumannotation` macro. It resets the annotation.

```

2685 \newcommand{\reset@current@annot}{%
2686   \unless\ifnoresetlinenumannotation@
2687     \let\current@annot\empty%
2688   \fi
2689 }%
2690 \newcommand{\@resetannot}{%
2691   \let\current@annot\empty%
2692 }%
2693 %

```

`\parse@annot` In the `\annot@list` list, each individual `\edtext` is associated with a starting and an ending line number annotation, which is stored this way: `start annotation|end annotation`. The `\parse@annot` reads the format and defines two global macros.

```

2694 \def\parse@annot#1|#2|{%
2695   \gdef\annot@start{#1}%
2696   \gdef\annot@end{#2}%
2697 }%
2698 %

```

`\setlinenumannotationsep` The separator between the annotations and the way to redefine it.

`\@linenumannotationsep`

```

2699 \newcommand{\setlinenumannotationsep}[1]{\gdef\@linenumannotationsep{#1}}%
2700 \def\@linenumannotationsep{, }%
2701 %

```

X Line number printing

`\affixline@num` `\affixline@num` just puts a left line number into `\l@dld@ta` or a right line number into `\l@drd@ta` as required.

To determine whether we need to affix a line number to this line, we compute the following:

$$n = \text{int}((\text{linenum} - \text{firstlinenum}) / \text{linenumincrement})$$

$$m = \text{firstlinenum} + (n \times \text{linenumincrement})$$

(where *int* truncates a real number to an integer). *m* will be equal to *linenum* only if we are to paste a number on here. However, the formula breaks down for the first line to number (and any before that), so we check that case separately: if `\line@num ≤ \firstlinenum`, we compare the two directly instead of making these calculations.

We compute, in the scratch counter `\@l@tempcnta`, the number of the next line that should be printed with a number (*m* in the above discussion), and move the current line number into the counter `\@l@tempcntb` for comparison.

First, the case when we are within a sub-line range.

```
2702 \newcommand*{\affixline@num}{%
2703 %
```

No number is attached if `\ifl@dskipnumber` is TRUE (and then it is set to its normal FALSE value). No number is attached if `\ifnumberline` is FALSE (the normal value is TRUE).

```
2704 \ifledgroupnotesL@else
2705 \ifnumberline
2706 \ifl@dskipnumber
2707 \global\l@dskipnumberfalse
2708 \else
2709 \ifsublines@
2710 \l@tempcntb=\subline@num
2711 \ifnum\subline@num>\c@firstsublinenum
2712 \l@tempcnta=\subline@num
2713 \advance\l@tempcnta by-\c@firstsublinenum
2714 \divide\l@tempcnta by\c@sublinenumincrement
2715 \multiply\l@tempcnta by\c@sublinenumincrement
2716 \advance\l@tempcnta by\c@firstsublinenum
2717 \else
2718 \l@tempcnta=\c@firstsublinenum
2719 \fi
2720 %
```

That takes care of computing the values for comparison, but if line number locking is in effect we have to make a further check. If this check fails, then we disable the line-number display by setting the counters to arbitrary but unequal values.

```
2721 \ch@cksub@l@ck
2722 %
```

Now the line number case, which works the same way.

```
2723 \else
2724 \l@tempcntb=\line@num
2725 %
```

Check on the `\linenumberlist` If it is `\empty` use the standard algorithm.

```

2726 \ifx\linenumberlist\empty
2727 \ifnum\line@num>\c@firstlinenum
2728 \l@dttempcnta=\line@num
2729 \advance\l@dttempcnta by-\c@firstlinenum
2730 \divide\l@dttempcnta by\c@linenumincrement
2731 \multiply\l@dttempcnta by\c@linenumincrement
2732 \advance\l@dttempcnta by\c@firstlinenum
2733 \else
2734 \l@dttempcnta=\c@firstlinenum
2735 \fi
2736 \else
2737 %

```

The `\linenumberlist` was not `\empty`, so here is Wayne's numbering mechanism. This takes place in \TeX 's mouth.

```

2738 \l@dttempcnta=\line@num
2739 \edef\rem@inder{\linenumberlist,\number\line@num,}%
2740 \edef\sc@n@list{\def\noexpand\sc@n@list
2741 ###1,\number\l@dttempcnta,###2|{\def\noexpand\rem@inder
2742 {####2}}}%
2743 \sc@n@list\expandafter\sc@n@list\rem@inder|}%
2744 \ifx\rem@inder\empty%
2745 \advance\l@dttempcnta\@ne
2746 \fi
2747 %

```

A locking check for lines, just like the version for sub-line numbers above.

```

2748 \ch@ck@l@ck
2749 \fi
2750 %

```

The following tests are true if we need to print a line number.

```

2751 \ifnum\l@dttempcnta=\l@dttempcntb
2752 \ifl@dskipversenumber\else
2753 %

```

If we got here, we are going to print a line number; so now we need to calculate a number that will tell us which side of the page will get the line number. We start from `\line@margin`, which asks for one side always if it is less than 2; and then if the side does depend on the page number, we simply add the page number to this side code—because the values of `\line@margin` have been devised so that this produces a number that is even for left-margin numbers and odd for right-margin numbers.

For \LaTeX we have to consider two column documents as well. In this case Peter Wilson thought we need to put the numbers at the outside of the column — the left of the first column and the right of the second. Do the `twocolumn` stuff before going on with the original code.

`\l@dld@ta` A left line number is stored in `\l@dld@ta` and a right one in `\l@drd@ta`.
`\l@drd@ta`

```

2754         \if@twocolumn
2755             \if@firstcolumn
2756                 \gdef\l@dld@ta{\llap{\leftlinenum}}}%
2757                 \iflinenumannotationotherside%
2758                     \gdef\l@drd@ta{\rlap{\rightlinenumannotation}}}%
2759                 \fi%
2760             \else
2761                 \gdef\l@drd@ta{\rlap{\rightlinenum}}}%
2762                 \iflinenumannotationotherside%
2763                     \gdef\l@dld@ta{\llap{\leftlinenumannotation}}}%
2764                 \fi%
2765             \fi
2766         \else
2767             \ifboolexpr{bool {l@dprintingcolumns} and test {\
ifnumgreater{\line@margin@columns}{\m@ne}}}%
2768                 {\@l@tempcntb=\line@margin@columns}%
2769                 {\@l@tempcntb=\line@margin}%
2770                 \ifnum\@l@tempcntb>\@ne
2771                     \advance\@l@tempcntb \page@num
2772                 \fi
2773                 \ifboolexpr{%
2774                     bool {l@dprintingcolumns}%
2775                     and (%
2776                         (test {\ifdefstring{\linenum@OnlyPages@ForColumns}{left
2777
2778                             and test {\ifnumodd{\page@num}}}%
2779                             )%
2780                             or%
2781                             (test {\ifdefstring{\linenum@OnlyPages@ForColumns}{right
2782
2783                             and not test {\ifnumodd{\page@num}}}%
2784                             )%
2785                         )%
2786                     )%
2787                     {\%
2788                         \ifodd\@l@tempcntb%
2789                             \gdef\l@drd@ta{\rlap{\rightlinenum}}}%
2790                             \iflinenumannotationotherside%
2791                             \gdef\l@dld@ta{\llap{\leftlinenumannotation}}}%
2792                             \fi%
2793                         \else%
2794                             \gdef\l@dld@ta{\llap{\leftlinenum}}}%
2795                             \iflinenumannotationotherside%
2796                             \gdef\l@drd@ta{\rlap{\rightlinenumannotation}}}%
2797                             \fi%
2798                         \fi%
2799                     }%
2800                 \fi

```

```
2801 \fi
2802 %
```

Now fix the lock counters, if necessary. A value of 1 is advanced to 2; 3 advances to 0; other values are unchanged.

```
2803 \f@x@l@cks
2804 \fi
2805 \fi
2806 \fi
2807 }
2808
2809 %
```

`\ch@cksub@l@ck` These macros handle line number locking for `\affixline@num`. `\ch@cksub@l@ck`
`\ch@ck@l@ck` checks subline locking. If it fails, then we disable the line-number display by setting the
`\f@x@l@cks` counters to arbitrary but unequal values.

```
2810 \newcommand*{\ch@cksub@l@ck}{%
2811 \ifcase\sub@lock
2812 \or
2813 \ifnum\sublock@disp=\@ne
2814 \@l@tempcntb=\z@ \@l@tempcnta=\@ne
2815 \fi
2816 \or
2817 \ifnum\sublock@disp=\tw@ \else
2818 \@l@tempcntb=\z@ \@l@tempcnta=\@ne
2819 \fi
2820 \or
2821 \ifnum\sublock@disp=\z@
2822 \@l@tempcntb=\z@ \@l@tempcnta=\@ne
2823 \fi
2824 \fi}
2825 %
```

Similarly for line numbers.

```
2826 \newcommand*{\ch@ck@l@ck}{%
2827 \ifcase\@lock
2828 \or
2829 \ifnum\lock@disp=\@ne
2830 \@l@tempcntb=\z@ \@l@tempcnta=\@ne
2831 \fi
2832 \or
2833 \ifnum\lock@disp=\tw@ \else
2834 \@l@tempcntb=\z@ \@l@tempcnta=\@ne
2835 \fi
2836 \or
2837 \ifnum\lock@disp=\z@
2838 \@l@tempcntb=\z@ \@l@tempcnta=\@ne
2839 \fi
```

```

2840 \fi}
2841 %

Fix the lock counters. A value of 1 is advanced to 2; 3 advances to 0; other values are
unchanged.

2842 \newcommand*{\fix@locks}{%
2843 \ifcase\@lock
2844 \or
2845 \global\@lock=\tw@
2846 \or \or
2847 \global\@lock=\z@
2848 \fi
2849 \ifcase\sub@lock
2850 \or
2851 \global\sub@lock=\tw@
2852 \or \or
2853 \global\sub@lock=\z@
2854 \fi}
2855 %
2856 %

```

XI Pstart number printing inside

Inside, the printing of the pstart number runs like the printing of the line number. There are only a few differences:

- The pstarts counter is upgraded in the `\pend` command. Consequently, the `\affixpstart@num` command has not to upgrade it, unlike the `\affixline@num` which upgrades the lines counter.
- To print the pstart number only at the beginning of a pstart, and not in every line, a boolean test is made. The `\pstartnum` boolean is set to TRUE at every `\pend`. It is tried in the `\leftpstartnum` and `\rightpstartnum` commands. After the try, it is set to FALSE.

```

\leftpstartnum57
\rightpstartnum58 \newif\ifsidepstartnum
\ifsidepstartnum59 \newcommand*{\affixpstart@num}{%
2860 \ifsidepstartnum
2861 \if@twocolumn
2862 \if@firstcolumn
2863 \gdef\l@dld@ta{\llap{\leftpstartnum}}}%
2864 \else
2865 \gdef\l@drd@ta{\rlap{\rightpstartnum}}}%
2866 \fi
2867 \else
2868 \l@dttempcntb=\line@margin%
2869 \ifnum\l@dttempcntb>\@ne

```

```

2870         \advance\l@dttempcntb \page@num
2871         \fi
2872         \ifodd\l@dttempcntb
2873             \gdef\l@drd@ta{\rlap{\rightpstartnum}}}%
2874         \else
2875             \gdef\l@dld@ta{\llap{\leftpstartnum}}}%
2876         \fi
2877     \fi
2878 \fi
2879
2880 }
2881 %
2882
2883 \newif\ifpstartnum
2884 \pstartnumtrue
2885 \newcommand*{\leftpstartnum}{
2886     \ifpstartnum\thepstart
2887     \kern\linenumsep\fi
2888     \global\pstartnumfalse
2889 }
2890 \newcommand*{\rightpstartnum}{
2891     \ifpstartnum
2892     \kern\linenumsep
2893     \thepstart
2894     \fi
2895     \global\pstartnumfalse
2896 }
2897 %

```

XII Restoring footnotes and penalties

Because of the paragraph decomposition process in order to number line, `reledmac` must hack the standard way \TeX works in order to manage insertion of footnotes, both critical and familiar.

We need to call the `\insert` commands not when the content of `\pstart... \pend` is read by \TeX by when each individual line is typeset.

Consequently, when reading the content of `\pstart... \pend`, we store the insertion (footnotes) in an specific `reledmac`'s list, and we restore them to the vertical list when printing each individual line.

XII.1 Add insertions to the vertical list

`\inserts@list` `\inserts@list` is the list macro that contains the inserts that we save up for one paragraph.

```

2898 \list@create{\inserts@list}
2899 %

```

`\add@inserts` `\add@inserts` is the penultimate macro used by `\do@line`; it takes insertions saved in a list macro and sends them onto the vertical list.

It may call itself recursively, and to do this efficiently (using \TeX 's optimization for tail recursion), we define a control-sequence called `\add@inserts@next` that is always the last thing that `\add@inserts` does. If there could be more inserts to process for this line, `\add@inserts@next` is set equal to `\add@inserts`; otherwise it is just `\relax`.

```
2900 \newcommand*{\add@inserts}{%
2901   \global\let\add@inserts@next=\relax
2902   %
```

If `\inserts@list` is empty, there are not any more notes or insertions for this paragraph, and we need not waste our time.

```
2903   \ifx\inserts@list\empty \else
2904   %
```

The `\next@insert` macro records the number of the line that receives the next footnote or other insert; it is empty when we start out, and just after we have affixed a note or insert.

```
2905   \ifx\next@insert\empty
2906     \ifx\insertlines@list\empty
2907       \global\noteschanged@true
2908       \gdef\next@insert{100000}%
2909     \else
2910       \gl@p\insertlines@list\to\next@insert
2911     \fi
2912   \fi
2913   %
```

If the next insert's for this line, tack it on (and then erase the contents of the insert macro, as it could be quite large). In that case, we also set `\add@inserts@next` so that we will call ourself recursively: there might be another insert for this same line.

```
2914   \ifnum\next@insert=\absline@num
2915     \gl@p\inserts@list\to\@insert
2916     \@insert
2917     \global\let\@insert=\undefined
2918     \global\let\next@insert=\empty
2919     \global\let\add@inserts@next=\add@inserts
2920   \fi
2921 \fi
2922 %
```

Make the recursive call, if necessary.

```
2923 \add@inserts@next}
2924
2925 %
```

`\add@Xgroupbyline` If you use `\Xgroupbyline`, the insertion of the critical footnotes are not made immediately in `\add@inserts`, but the content to be inserted is stored, in order to be inserted later in one block. This insertion in one block is made by `\add@Xgroupbyline`.

```

2926 \newcommand{\add@Xgroupbyline}{%
2927   \unless\ifnocritical%
2928     \def\do##1{%Looping on the series
2929       \let\olddo\do%Save the old \do macro, that is this macro itself!
2930       \def\do####1{%Looping on the ##1@forinserting command
2931         \ifcsdef{##1@forinserting@####1}{%
2932           \X@beforeinsertion{##1}%
2933           \if@ledgroup%
2934             \global\setbox\@nameuse{mp##1footins}=\vbox%
2935           \else%
2936             \insert\csname ##1footins\endcsname%
2937           \fi%
2938           {%
2939             \Xsetparindent{##1}%
2940             \ifcsdef{Xhsize\csuse{series@display##1}@##1}%
2941               {\hspace \csuse{Xhsize\csuse{series@display##1}@##1}}%
2942             }%
2943             \if@ledgroup%
2944               \unvbox\@nameuse{mp##1footins}%
2945             \fi%
2946             \X@atbegininsertion{##1}%
2947             \ifcsstring{series@display##1}{normal}%
2948               {%
2949                 \Xledsetnormalparstuff{##1}%
2950                 \rule\z@\splittopskip%
2951               }%
2952             {%
2953               \csuse{##1@forinserting@####1}%
2954               \strut\par%
2955             }%
2956             \global\csundef{##1@forinserting@####1}%
2957           }%
2958         }%
2959       }%
2960       \ifcsdef{##1@forinserting}{%
2961         \dolistcsloop{##1@forinserting}%
2962       }{%
2963         \global\csundef{##1@forinserting}%
2964         \let\do\olddo%Restore old do
2965       }%
2966     \dolistloop{\@series}%
2967   \fi%
2968 }%
2969
2970
2971 %

```


XII.2 Penalties

\add@penalties `\add@penalties` is the last macro used by `\do@line`. It adds up the club, widow, and interline penalties, and puts a single penalty of the appropriate size back into the paragraph; these penalties get removed by the `\vsplit` operation. `\displaywidowpenalty` and `\brokenpenalty` are not restored, since we have no easy way to find out where we should insert them.

In this code, `\num@lines` is the number of lines in the whole paragraph, and `\par@line` is the line we are working on at the moment. The count `\@l@tempcnta` is used to calculate and accumulate the penalty; it is initially set to the value of `\ballast@count`, which has been worked out in `\do@ballast` above (VIII p. 170). Finally, the penalty is checked to see that it does not go below -10000 .

```

2972 \newcommand*{\add@penalties}{\@l@tempcnta=\ballast@count
2973   \ifnum\num@lines>\@ne
2974     \global\advance\par@line \@ne
2975     \ifnum\par@line=\@ne
2976       \advance\@l@tempcnta \clubpenalty
2977     \fi
2978     \@l@tempcntb=\par@line \advance\@l@tempcntb \@ne
2979     \ifnum\@l@tempcntb=\num@lines
2980       \advance\@l@tempcnta \widowpenalty
2981     \fi
2982     \ifnum\par@line<\num@lines
2983       \advance\@l@tempcnta \interlinepenalty
2984     \fi
2985   \fi
2986   \ifnum\@l@tempcnta=\z@
2987     \relax
2988   \else
2989     \ifnum\@l@tempcnta>-10000
2990       \penalty\@l@tempcnta
2991     \else
2992       \penalty -10000
2993     \fi
2994   \fi}
2995
2996 %

```

XII.3 Printing leftover notes

\flush@notes The `\flush@notes` macro is called after the entire paragraph has been sliced up and sent on to the vertical list. If the number of notes to this paragraph has increased since the previous run of \TeX , then there can be leftover notes that have not yet been printed. An appropriate error message will be printed elsewhere; but it is best to go ahead and print these notes somewhere, even if it is not in quite the right place. What we do is dump them all out here, so that they should be printed on the same page as the last line of the paragraph. We can hope that is not too far from the proper location, to which they

will move on the next run. For the first run, we do not flush the notes, as that means all the notes will be added at the end of numbered section, and so, very far of the expected position

```

2997 \newcommand*{\flush@notes}{%
2998   \iftoggle{notfirstrun@jobname.\extensionchars\the\section@num}{%
2999     \@xloop%
3000     \ifx\inserts@list\empty \else%
3001       \gl@p\inserts@list\to\@insert%
3002       \@insert%
3003       \global\let\@insert=\undefined%
3004     \repeat%
3005   }{}%
3006 }%
3007
3008
3009 %

```

\@xloop \@xloop is a variant of the PLAIN T_EX \loop macro, useful when it's hard to construct a positive test using the T_EX \if commands—as in \flush@notes above. One types \@xloop ... \if ... \else ... \repeat, and the action following \else is repeated as long as the \if test fails. (This macro will work wherever the PLAIN T_EX \loop is used, too, so we could just call it \loop; but it seems preferable not to change the definitions of any of the standard macros.)

This variant of \loop was introduced by Alois Kabelschacht in *TUGboat* **8** (1987), pp. 184–5.

```

3010 \def\@xloop#1\repeat{%
3011   \def\body{#1\expandafter\body\fi}%
3012   \body}
3013
3014 %

```

XII.4 Text before notes

\set@Xtxtbeforenotes The \set@Xtxtbeforenotes macro resets the Xtxtbeforenotes@⟨series⟩@typeset boolean to false. Just before the first note of the ⟨series⟩ in a page, the \Xtextbeforenotes will be inserted.

```

3015 \newcommand{\set@Xtxtbeforenotes}{%
3016   \unless\ifnocritical@%
3017     \def\do##1{%
3018       \nottoggle{Xtxtbeforenotesonlyonce@##1}{%
3019         \global\togglefalse{Xtxtbeforenotes@##1@typeset}%
3020       }{}%
3021     }%
3022     \dolistloop{\@series}%
3023   \fi%
3024 }%
3025 %

```

`\set@txtbeforenotesX` The `\set@txtbeforenotesX` does the same for the `\textbeforenotesX`.

```

3026 \newcommand{\set@txtbeforenotesX}{%
3027   \unless\ifnofamiliar{%
3028     \def\do##1{%
3029       \nottoggle{txtbeforenotesonlyonceX@##1}{%
3030         \global\togglefalse{txtbeforenotesX@##1@typeset}%
3031       }{%
3032         }%
3033       \dolistloop{\@series}%
3034     }%
3035   }%
3036   %

```

`\insert@Xtxtbeforenotes` `\insert@Xtxtbeforenotes{<series>}`, called when inserting a familiar footnote, will insert the text before the note if it is not already inserted. For paragraphed footnotes, it will insert it as a component of the first footnote. For other types of footnotes, it will insert it as a regular footnote.

`\insert@txtbeforenotesX` is the same for familiar footnotes.

```

3037 \newcommand{\insert@Xtxtbeforenotes}[1]{%
3038   \nottoggle{Xtxtbeforenotes@#1@typeset}{%
3039     \global\toggletrue{Xtxtbeforenotes@#1@typeset}%
3040     \ifcsvoid{Xtxtbeforenotes@#1}{%
3041       \ifcsstring{series@display#1}{paragraph}%
3042       {\noindent\csuse{Xtxtbeforenotes@#1}}%
3043       {\expandafter\insert\csname#1footins\endcsname%
3044         \bgroup%
3045           \noindent%
3046           \ifcsdef{\csuse{series@display#1}@begin@insert}{%
3047             \csuse{\csuse{series@display#1}@begin@insert}{#1}%
3048           }{%
3049             \strut\csuse{Xnotefontsize@#1}%
3050             \csuse{Xtxtbeforenotes@#1}%
3051           }%
3052         \egroup%
3053       }%
3054     }%
3055   }%
3056 }%
3057
3058 \newcommand{\insert@txtbeforenotesX}[1]{%
3059   \nottoggle{txtbeforenotesX@#1@typeset}{%
3060     \global\toggletrue{txtbeforenotesX@#1@typeset}%
3061     \ifcsvoid{txtbeforenotesX@#1}{%
3062       \ifcsstring{series@display#1}{paragraph}%
3063       {\noindent\csuse{txtbeforenotesX@#1}}%
3064       {\expandafter\insert\csname#1footins\endcsname%
3065         \bgroup%

```

```

3067 \noindent%
3068 \ifcsdef{\csuse{series@displayX#1}@begin@insert}{%
3069 \csuse{\csuse{series@displayX#1}@begin@insert}{#1}%
3070 }{}%
3071 \strut\csuse{notefontsizeX@#1}\csuse{txtbeforenotesX@#1}%
3072 \egroup%
3073 }%
3074 }%
3075 }%
3076 {}%
3077 }%
3078
3079
3080 %

```

XIII Critical footnotes

The footnote macros are adapted from those in PLAIN T_EX, but they differ in these respects: the outer-level commands must add other commands to a list macro rather than doing insertions immediately; there are many separate levels of the footnotes, not just one; and there are options to reformat footnotes into paragraphs or into multiple columns.

XIII.1 Fonts

Before getting into the details of formatting the notes, we set up some font macros. It is the notes that present the greatest challenge for our font-handling mechanism, because we need to be able to take fragments of our main text and print them in different forms: it is common to reduce the size, for example, without otherwise changing the fonts used.

`\select@lemmafont` `\select@lemmafont` is provided to set the right font for the lemma in a note. This macro extracts the font specifier from the line and page number cluster, and issues the associated font-changing command, so that the lemma is printed in its original font.

```

3081 \def\select@lemmafont#1|#2|#3|#4|#5|#6|#7|{\select@lemmafont#7|}
3082 \def\select@lemmafont#1/#2/#3/#4|%
3083 {\fontencoding{#1}\fontfamily{#2}\fontseries{#3}\fontshape{#4}%
3084 \selectfont}
3085
3086 %

```

XIII.2 Individual note options

`\footnoteoptions@` The `\footnoteoption@[\langle side \rangle]{\langle options \rangle}{\langle value \rangle}` changes the value of on options of Xfootnote, to switch between true and false.

```

3087 \newcommand*{\footnoteoptions@}[3]{%
3088   \def\do##1{%
3089     \ifstrequal{#1}{L}{% On the left side
3090       \xright@appenditem{\noexpand\setkeys[mac]{#3footnoteoption}{\
unexpanded{##1}}}{\to\inserts@list%
3091         \global\advance\insert@count \@ne% Increment the left insert
counter.
3092       }%
3093       {%
3094         \xright@appenditem{\noexpand\setkeys[mac]{#3footnoteoption}{\
unexpanded{##1}}}{\to\inserts@listR%
3095         \global\advance\insert@countR \@ne% Increment the right insert
counter insert.
3096       }%
3097     }%
3098     \notblank{#2}{\docsvlist{#2}}}% Parsing all options
3099 }
3100 %

```

XIII.3 Notes language

`\footnotelang@lua` `\footnotelang@lua` is called to remember the information about the direction of a lemma when `LuaTeX` is used.

```

3101 \newcommandx*{\footnotelang@lua}[1][1=L,usedefault]{%
3102   \ifstrequal{#1}{L}{%
3103     \xright@appenditem{\csxdef{footnote@luatextextdir}{\the\textdir}}{\to\
inserts@list%Know the dir of lemma
3104     \global\advance\insert@count \@ne%
3105     \xright@appenditem{\csxdef{footnote@luatexpardir}{\the\pardir}}{\to\
inserts@list%Know the dir of lemma
3106     \global\advance\insert@count \@ne%
3107   }%
3108   {%
3109     \xright@appenditem{\csxdef{footnote@luatextextdir}{\the\textdir}}{\to\
inserts@listR%Know the dir of lemma
3110     \global\advance\insert@countR \@ne%
3111     \xright@appenditem{\csxdef{footnote@luatexpardir}{\the\pardir}}{\to\
inserts@listR%Know the dir of lemma
3112     \global\advance\insert@countR \@ne%
3113   }%
3114 }
3115 %

```

`\footnotelang@poly` `\footnotelang@poly` is called to remember the information about the language of a lemma when `polyglossia` is used.

```

3116 \newcommandx*{\footnotelang@poly}[1][1=L,usedefault]{%
3117   \ifstrequal{#1}{L}{%

```

```

3118 \ifRTL%
3119 \xright@appenditem{{\csxdef{footnote@dir}{@RTLtrue}}}\to\
inserts@list%Know the language used in the lemma
3120 \global\advance\insert@count \@ne%
3121 \else
3122 \xright@appenditem{{\csxdef{footnote@dir}{@RTLfalse}}}\to\
inserts@list%Know the language of lemma
3123 \global\advance\insert@count \@ne%
3124 \fi%
3125 \xright@appenditem{{\csxdef{footnote@lang}{\expandonce\language}}}\
to\inserts@list%Know the language of lemma
3126 \global\advance\insert@count \@ne%
3127 }%
3128 {%
3129 \ifRTL
3130 \xright@appenditem{{\csxdef{footnote@dir}{@RTLtrue}}}\to\
inserts@listR%Know the language of lemma
3131 \global\advance\insert@countR \@ne%
3132 \else
3133 \xright@appenditem{{\csxdef{footnote@dir}{@RTLfalse}}}\to\
inserts@listR%Know the language of lemma
3134 \global\advance\insert@countR \@ne%
3135 \fi
3136 \xright@appenditem{{\csxdef{footnote@lang}{\expandonce\language}}}\
to\inserts@listR%Know the language of lemma
3137 \global\advance\insert@countR \@ne%
3138 }%
3139 }
3140 %

```

XIII.4 General survey of the way we manage notes

The processing of each note is done by four principal macros: the `\vfootnote` macro takes the text of the footnote and does the `\insert`; it calls on the `\footfmt` macro to select the right fonts, print the line number and lemma, and do any other formatting needed for that individual note. Within the output routine, the two other macros, `\footstart` and `\footgroup`, are called; the first prints extra vertical space and a footnote rule, if desired; the second does any reformatting of the whole set of the footnotes in this series for this page—such as paragraphing or division into columns—and then sends them to the page.

These four macros, and the other macros and parameters shown here, are distinguished by the “series letter” that indicates which set of the footnotes we are dealing with—A, B, C, D, or E. The series letter always precedes the string foot in macro and parameter names. Hence, for the A series, the four macros are called `\vAfootnote`, `\Afootfmt`, `\Afootstart`, and `\Afootgroup`.

These macros are changed depending on the footnote arrangement: “normal”, “paragraphed”, “two columns” or “three columns”.

XIII.5 General setup

`\footsplitskips` Some setup code that is common for a variety of the footnotes. The setup is for:

- `\interlinepenalty`.
- `\splittopskip` (skip before last part of notes that flow from one page to another).
- `\splitmaxdepth`.
- `\floatingpenalty`, that is penalty values being added when a long note flows from one page to another. Here, we let it to 0 when we process parallel pages in `eledpar`, in order to allow notes to flow from left to right pages and *vice-versa*. Otherwise, we let it to `\@MM`, which is the standard \TeX `\floatingpenalty`.

```

3141 \newcommand*{\footsplitskips}{%
3142   \interlinepenalty=\interfootnotelinepenalty
3143   \unless\ifl@printingpages%
3144     \floatingpenalty=\@MM%
3145   \fi%
3146   \splittopskip=\ht\strutbox \splitmaxdepth=\dp\strutbox
3147   \leftskip=\z@skip \rightskip=\z@skip}
3148 %
3149 %

```

`\normalfootnoterule` `\normalfootnoterule` is a standard footnote-rule macro, for use by a `footstart` macro: just the same as the `PLAIN` \TeX footnote rule.

```

3150 \let\normalfootnoterule=\footnoterule
3151 %

```

XIII.6 Footnotes arrangement

XIII.6.1 User level macro

`\Xarrangement` `\Xarrangement[⟨s⟩]{⟨arrangement⟩}` The command calls, for each series, a specific command which set many counters and commands in order to define specific arrangement.

```

3152 \newcommandx{\Xarrangement}[2][1,usedefault]{%
3153   \def\do##1{%
3154     \csname Xarrangement@#2\endcsname{##1}%
3155   }%
3156   \ifstrempy{#1}%
3157     {%
3158       \dolistloop{\@series}%
3159     }%
3160     {
3161       \docsvlist{#1}%
3162     }%
3163   }%
3164   %

```

XIII.6.2 Normal footnote

`\Xarrangement@normal` We can now define all the parameters for the series of footnotes; initially they use the “normal” footnote formatting.

What we want to do here is to insert something like the following for each footnote series. (This is an example, not part of the actual `reledmac` code.)

```
\skip\Afootins=12pt plus5pt minus5pt
\count\Afootins=1000
\dimen\Afootins=0.8\vsiz
\let\vAfootnote=\normalvfootnote \let\Afootfmt=\normalfootfmt
\let\Afootstart=\normalfootstart \let\Afootgroup=\normalfootgroup
\let\Afootnoterule=\normalfootnoterule
```

(Read *The TeXbook* in order to understand what are the counter, skip and dimen associated to an insertion.)

Instead of repeating ourselves, we define a `\Xarrangement@normal` macro that makes all these assignments for us, for any given series letter. This command is called when people use `\Xarrangement[⟨series⟩]{normal}`

Now we set up the `\Xarrangement@normal` macro itself. It takes one argument: the footnote series letter.

```
3165 \newcommand*{\Xarrangement@normal}[1]{%
3166   \csgdef{series@display#1}{normal}
3167   \expandafter\let\csname #1footstart\endcsname=\normalfootstart
3168   \expandafter\let\csname v#1footnote\endcsname=\normalvfootnote
3169   \expandafter\let\csname #1footfmt\endcsname=\normalfootfmt
3170   \expandafter\let\csname #1footgroup\endcsname=\normalfootgroup
3171   \expandafter\let\csname #1footnoterule\endcsname=%
3172                               \normalfootnoterule
3173   \count\csname #1footins\endcsname=1000
3174   \dimen\csname #1footins\endcsname=\csuse{Xmaxhnotes@#1}
3175   \skip\csname #1footins\endcsname=\csuse{Xbeforenotes@#1}%
3176   \advance\skip\csname #1footins\endcsname by\csuse{Xafterrule@#1}%
3177   %
```

The `reledpar` provides tools in order to confine notes to one side. The mechanism is explained in the `reledpar`’s handbook. For now, just retain we need to store default value of the counter associated to the notes \TeX ’s inserts.

```
3178   \csxdef{default@#1footins}{1000}%Use this to confine the notes to one
3179   side only
3179   %
```

Now do the setup for minipage footnotes. We use as much as possible of the normal setup as we can (so the notes will have a similar layout).

```
3180   \ifnoledgroup@else%
3181     \expandafter\let\csname mpv#1footnote\endcsname=\mpnormalvfootnote
3182     \expandafter\let\csname mp#1footgroup\endcsname=\mpnormalfootgroup
3183     \count\csname mp#1footins\endcsname=1000
```



```

3184 \dimen\csname mp#1footins\endcsname=\csuse{Xmaxhnotes@#1}
3185 \skip\csname mp#1footins\endcsname=\csuse{Xbeforenotes@#1}%
3186 \advance\skip\csname mp#1footins\endcsname by\csuse{Xafterrule@#1}%
3187 \fi
3188 }
3189
3190 %

```

\normalvfootnote We now begin a series of commands that do “normal” footnote formatting: a format much like that implemented in PLAIN T_EX, in which each footnote is a separate paragraph.

\normalvfootnote takes the series letter as #1 and the entire text of the footnote is #2. It does the \insert for this note, calling on the \footfmt macro for this note series to format the text of the note.

```

3191 \notbool{parapparatus@}{\newcommand*}{\newcommand}{\normalvfootnote}[2]{%
3192 \iftoggle{Xgroupbyline@#1}{%In the case we use \Xgroupbyline, the
insertion is done later, in \add@Xgroupbyline.
3193 \prepare@Xgroupbyline{#1}{#2}{\normalvfootnote@inserted}%
3194 }{%In the case we don't use \Xgroupbyline, the insertion is made directly
3195 \X@beforeinsertion{#1}%
3196 \insert\csname #1footins\endcsname{%
3197 \X@atbegininsertion{#1}%
3198 \normalvfootnote@inserted{#1}{#2}%
3199 }%
3200 }%
3201 }%
3202 %

```

\normalvfootnote@inserted The \normalvfootnote@inserted macro is expanded to the content to be added to a \insert for normal critical footnote.

```

3203 \notbool{parapparatus@}{\newcommand*}{\newcommand}{\normalvfootnote@inserted}[2]{%
3204 \nottoggle{Xgroupbyline@#1}{\noindent}{\csuse{Xhooknote@#1}%
3205 \csuse{Xnotefontsize@#1}%
3206 \iftoggle{Xgroupbyline@#1}{\strut}{}}%
3207 \footssplitsskips
3208 \ifl@dpairing\ifl@dpadding\else%
3209 \setXnoteswidthliketwocolumns@{#1}%
3210 \fi\fi%
3211 \setXnotespositionliketwocolumns@{#1}%
3212 \spaceskip=\z@skip \xspaceskip=\z@skip%
3213 \csname #1footfmt\endcsname #2{#1}%
3214 }%
3215 %

```

\X@beforeinsertion₁₆ \newcommand{\X@beforeinsertion}[1]{%

```

3217 \if@ledgroup\else%
3218 \insert@Xtxtbeforenotes{#1}%
3219 \fi%
3220 \csuse{Xbeforeinserting@#1}%
3221 }%
3222 %

```

```

\beforeinsertion@X23 \newcommand{\beforeinsertion@X}[1]{%
3224 \if@ledgroup\else%
3225 \insert@txtbeforenotesX{#1}%
3226 \fi%
3227 \csuse{beforeinsertingX@#1}%
3228 }%
3229 %

```

```

\X@atbegininsertion30 \newcommand{\X@atbegininsertion}[1]{%
3231 \hsize=\expandafter\dimexpr\csuse{Xwidth@#1}\relax%
3232 }%
3233 %

```

And somewhat different versions of `\normalvfootnote` and `\normalvfootnote@inserted` for minipages.

```

\mpnormalvfootnote34 \notbool{parapparatus@}{\newcommand*}{\newcommand}{\mpnormalvfootnote}[2]{%
3235 \iftoggle{Xgroupbyline@#1}{%
3236 \prepare@Xgroupbyline{#1}{#2}{\mpnormalvfootnote@inserted}%
3237 }%
3238 {%
3239 \global\setbox\@nameuse{mp#1footins}%
3240 \vbox{%
3241 \unvbox\@nameuse{mp#1footins}%
3242 \mpnormalvfootnote@inserted{#1}{#2}%
3243 }%
3244 }%
3245 }%
3246 %
3247 %

```

```

\mpnormalvfootnote@inserted48 \newcommand{\mpnormalvfootnote@inserted}[2]{%
3249 \noindent\csuse{Xbhooknote@#1}%
3250 \csuse{Xnotefontsize@#1}%
3251 \hsize\columnwidth%
3252 \@parboxrestore%
3253 \color@begingroup%
3254 \csname #1footfmt\endcsname #2{#1}\color@endgroup%
3255 }%
3256 %

```

`\normalfootfmt` `\normalfootfmt` is a “normal” macro to take the footnote line and page number information (see V.9 p. 113), and the desired text, and output what’s to be printed. Argument #1 contains the line and page number information and lemma font specifier; #2 is the lemma; #3 is the note’s text; #4 is the note’s series. This version is very rudimentary—it uses `\printlines` to print just the range of line numbers, followed by a square bracket, the lemma, and the note text.

```

3257 \notbool{parapparatus@}{\newcommand*}{\newcommand}{\normalfootfmt}[4]{%
3258   \xstorelineinfo{#1}{#4}%
3259   \nottoggle{Xgroupbyline@#4}{\xledsetnormalparstuff{#4}}{}%
3260   \xsethangindent{#4}%
3261   \nottoggle{Xgroupbyline@#4}{\rule{z@}{\splittopskip}}{}%
3262   {\printlinefootnote{#1}{#4}}%
3263   \print@lemma{#1}{#2}{#4}%
3264   \csuse{Xwrapcontent@#4}{#3}%
3265   \nottoggle{Xgroupbyline@#4}{\strut\par}{}%
3266 }%
3267 %

```

`\normalfootstart` `\normalfootstart` is a standard footnote-starting macro, called in the output routine whenever there are footnotes of this series to be printed: it skips a bit and then draws a rule.

Any `\footstart` macro must put onto the page something that takes up space exactly equal to the `\skipXfootins` value for the associated series of notes. \TeX makes page computations based on that `\skip` value, and the output pages will suffer from spacing problems if what you add takes up a different amount of space.

But if the skip `\Xprenotes@` is greater than 0 pt, it is used instead of `\skip\footins` for the first printed series in one page.

The `\leftskip` and `\rightskip` values are both zeroed here. Similarly, these skips are cancelled in the `\vfootnote` macros for the various types of notes. Strictly speaking, this is necessary only if you are using paragraphed footnotes, but we have put it here and in the other `\vfootnote` macros too so that the behavior of `reledmac` in this respect is general across all footnote types. What this means is that any `\leftskip` and `\rightskip` you specify applies to the main text, but not the footnotes. The footnotes continue to be of width `\hsize`.

```

3268 \newcommand*{\normalfootstart}[1]{%
3269 %

```

The first series of notes printed in a page can have a specific skip before it. In order to insert this specific skip without overlap the bottom margin of the page, Maïeul Rouquette have defined an algorithm explained in XIX p. 251. Here is part of this algorithm, when the block of notes are ready to be printed.

```

3270 \ifdimequal{0pt}{\Xprenotes@}{}%
3271   {%
3272     \iftoggle{Xprenotes@}{%
3273       \togglefalse{Xprenotes@}%
3274       \skip\csname #1footins\endcsname=%

```

```

3275         \glueexpr\csuse{Xprenotes@}+\csuse{Xafterrule@#1}\relax%
3276     }%
3277     {}%
3278 }%
3279 \vskip\skip\csname #1footins\endcsname%
3280 %

```

And now, the problem of left and right skip for notes. Especially when using one feature of `reledpar` which allows to have the footnotes horizontal size as the size of columns printed by `\Columns`. Read XVI p. 249 for the general description of the problem.

```

3281 \leftskipOpt \rightskipOpt
3282 \ifl@dpairing\else%
3283     \hsize=\old@hsize%
3284 \fi%
3285 \setXnoteswidthliketwocolumns@{#1}%
3286 \setXnotespositionliketwocolumns@{#1}%
3287 %

```

And now, print the footnote's rule to finish the footnote's introduction.

```

3288 \print@Xfootnoterule{#1}%
3289 }%
3290 %

```

`\normalfootgroup` `\normalfootgroup` is a standard footnote-grouping macro: it sends the contents of the footnote-insert box to the output page without alteration.

```

3291 \newcommand*{\normalfootgroup}[1]{%
3292     \csuse{Xhookgroup@#1}%
3293     \unvbox\csname #1footins\endcsname%
3294     \hsize=\old@hsize%
3295 }%
3296 %
3297 %

```

`\mpnormalfootgroup` A somewhat different version for minipages. Note that, in this case, we do not make distinctions between the `\Xfootgroup` and `\Xfootstarts` macros.

```

3298 \unless\ifnoledgroup@
3299 \newcommand*{\mpnormalfootgroup}[1]{%
3300     \vskip\skip\@nameuse{mp#1footins}
3301     \ifl@dpairing\ifparledgroup%
3302         \leavevmode\marks\parledgroup@{begin}%
3303         \marks\parledgroup@series{#1}%
3304         \marks\parledgroup@type{Xfootnote}%
3305     \fi\fi\normalcolor%
3306     \ifparledgroup%
3307         \ifl@dpairing%
3308         \else%
3309             \setXnoteswidthliketwocolumns@{#1}%

```

```

3310 \setXnotespositionliketwocolumns@{#1}%
3311 \print@Xfootnoterule{#1}%
3312 \fi%
3313 \else%
3314 \setXnoteswidthliketwocolumns@{#1}%
3315 \setXnotespositionliketwocolumns@{#1}%
3316 \print@Xfootnoterule{#1}%
3317 \fi%
3318 \setlength{\parindent}{0pt}
3319 \csuse{Xhookgroup@#1}%
3320 \unvbox\csname mp#1footins\endcsname}}
3321 \fi
3322 %

```

XIII.6.3 Paragraphed footnotes

The paragraphed-footnote option reformats all the footnotes of one series for a page into a single paragraph; this is especially appropriate when the notes are numerous and brief. The code is based on *The TeXbook*, pp. 398–400, with alterations for our environment. This algorithm uses a considerable amount of save-stack space: a T_EX of ordinary size may not be able to handle more than about 100 notes of this kind on a page.

`\Xarrangement@paragraph` The `\Xarrangement@paragraph` macro sets up everything for one series of the footnotes so that they will be paragraphed; it takes the series letter as argument. We include the setting of `\count\footins` to 1000 for the footnote series just in case user is switching to paragraphed footnotes after having columnar ones, since they change this value (see below).

The argument of `\Xarrangement@footparagraph` is the letter denoting the series of notes to be paragraphed.

```

3323 \newcommand*{\Xarrangement@paragraph}[1]{%
3324 \csgdef{series@display#1}{paragraph}
3325 \expandafter\let\csname #1footstart\endcsname=\parafootstart
3326 \expandafter\let\csname v#1footnote\endcsname=\paravfootnote
3327 \expandafter\let\csname #1footfmt\endcsname=\parafootfmt
3328 \expandafter\let\csname #1footgroup\endcsname=\parafootgroup
3329 \count\csname #1footins\endcsname=1000
3330 \csxdef{default@#1footins}{1000}%Use this to confine the notes to one
side only
3331 \dimen\csname #1footins\endcsname=\csuse{Xmaxhnotes@#1}
3332 \skip\csname #1footins\endcsname=\csuse{Xbeforenotes@#1}%
3333 \advance\skip\csname #1footins\endcsname by\csuse{Xafterrule@#1}%
3334 \para@footsetup{#1}
3335 %

```

And the extra setup for minipages.

```

3336 \ifnoledgroup\else
3337 \expandafter\let\csname mpv#1footnote\endcsname=\mpparavfootnote
3338 \expandafter\let\csname mp#1footgroup\endcsname=\mpparafootgroup

```

```

3339 \count\csname mp#1footins\endcsname=1000
3340 \dimen\csname mp#1footins\endcsname=\csuse{Xmaxhnotes@#1}
3341 \skip\csname mp#1footins\endcsname=\csuse{Xbeforenotes@#1}%
3342 \advance\skip\csname mp#1footins\endcsname by\csuse{Xafterrule@#1}%
3343 \fi
3344 }
3345 %

```

\footfudgefiddle For paragraphed footnotes \TeX has to estimate the amount of space required. If it underestimates this then the notes may get too long and run off the bottom of the text block. `\footfudgefiddle` can be increased from its default 64 (say, to 70) to increase the estimate.

```

3346 \providecommand{\footfudgefiddle}{64}
3347 %

```

\para@footsetup `\footparagraph` calls the `\para@footsetup` macro to calculate a special fudge factor, which is the ratio of the `\baselineskip` to the `\hsize`. We assume that the proper value of `\baselineskip` for the footnotes (normally 9 pt) has been set already. The argument of the macro is again the note series letter.

Peter Wilson thinks that `\columnwidth` should be used here for \LaTeX not `\hsize`. Peter Wilson have also included `\footfudgefiddle`.

```

3348 \newcommand*{\para@footsetup}[1]{\csuse{Xhookgroup@#1}\csuse{
Xnotefontsize@#1}
3349 \setXnoteswidthliketwocolumns@{#1}%
3350 \ifcsempy{Xwidth@#1}%
3351 {}%
3352 {\columnwidth=\expandafter\dimexpr\csuse{Xwidth@#1}\relax}%
3353 \dimen0=\baselineskip
3354 \multiply\dimen0 by 1024
3355 \divide \dimen0 by \columnwidth \multiply\dimen0 by \footfudgefiddle\
relax
3356 \csxdef{#1footfudgefactor}{%
3357 \expandafter\strip@pt\dimen0 }}
3358
3359 %

```

`\strip@pt` strip the characters pt from a dimen value.

\parafootstart `\parafootstart` is the same as `\normalfootstart`, but we give it again to ensure that `\rightskip` and `\leftskip` are zeroed (this needs to be done before `\para@footgroup` in the output routine). The size of paragraphed notes is calculated using a fudge factor which in turn is based on `\hsize`. So the paragraph of notes needs to be that wide.

The argument of the macro is again the note series letter.

```

3360 \newcommand*{\parafootstart}[1]{%
3361 \rightskip=0pt \leftskip=0pt%

```

```

3362 \Xsetparindent{#1}%
3363 \ifdimequal{0pt}{\Xprenotes@}{}%
3364 {%
3365   \iftoggle{Xprenotes@}{%
3366     \togglefalse{Xprenotes@}%
3367     \skip\csname #1footins\endcsname=%
3368     \glueexpr\csuse{Xprenotes@}+\csuse{Xafterrule@#1}\relax%
3369   }%
3370 }%
3371 }%
3372 \vskip\skip\csname #1footins\endcsname%
3373 \setXnoteswidthliketwocolumns@{#1}%
3374 \setXnotespositionliketwocolumns@{#1}%
3375 \print@Xfootnoterule{#1}%
3376 \let\old@bidi@RTL@everypar\bidi@RTL@everypar%
3377 \let\bidi@RTL@everypar\@empty%
3378 \noindent\leavevmode%
3379 \let\bidi@RTL@everypar\old@bidi@RTL@everypar%
3380 }%
3381 %

```

\paravfootnote `\paravfootnote` is a version of the `\vfootnote` command that is used for paragraphed notes. It gets appended to the `\inserts@list` list by an outer-level footnote command like `\Afootnote`. The first argument is the note series letter; the second is the full text of the printed note itself, including line numbers, lemmata, and footnote text.

The initial model for this insertion is, of course, the `\insert\footins` definition in *The TeXbook*, p. 398. There, the footnotes are first collected up in `hboxes`, and these `hboxes` are later unpacked and stuck together into a paragraph.

However, Michael Downes has pointed out that because text in `hboxes` gets typeset in restricted horizontal mode, there are some undesirable side-effects if you later want to break such text across lines. In restricted horizontal mode, where \TeX does not expect to have to break lines, it does not insert certain items like `\discretionary`s. If you later unbox these `hboxes` and stick them together, as the *TeXbook* macros do to make these footnotes, you lose the ability to hyphenate after an explicit hyphen. This can lead to overfull `hboxes` when you would not expect to find them, and to the uninitiated it might be very hard to see why the problem had arisen.³²

Wayne Sullivan pointed out to us another subtle problem that arises from the same cause: \TeX also leaves the `\language` whatsit nodes out of the horizontal list.³³ So changes from one language to another will not invoke the proper hyphenation rules in such footnotes. Since critical editions often do deal with several languages, especially in a footnotes, we really ought to get this bit of code right.

To get around these problems, Wayne suggested emendations to the *TeXbook* versions of these macros which are broadly the same as those described by Michael: the central idea (also suggested by Donald Knuth in a letter to Michael) is to avoid collecting the text in an `hbox` in the first place, but instead to collect it in a `\vbox` whose width

³²Michael Downes, “Line Breaking in `\unhboxed` Text”, *TUGboat* **11** (1990), pp. 605–612.

³³See *The TeXbook*, p. 455 (editions after January 1990).

is (virtually) infinite. The text is therefore typeset in unrestricted horizontal mode, as a paragraph consisting of a single long line. Later, there is an extra level of unboxing to be done: we have to unpack the `\vbox`, as well as the `hboxes` inside it, but that is not too hard. For details, we refer you to Michael's article, where the issues are clearly explained.³⁴ Michael's unboxing macro is called `\Xunvvh`: `unvbox`, extract the last line, and `unhbox` it.

Doing things this way has an important consequence: as Michael pointed out, you really can't put an explicit line-break into a note built in a `\vbox` the way we are doing.³⁵ In other words, be very careful not to use `\break`, or `\penalty-10000`, or any equivalent inside your para-footnote. If you do, most of the note will probably disappear. You *are* allowed to make strong suggestions; in fact `\penalty-9999` will be quite okay. Just do not make the break mandatory. We have not applied any of Michael's solutions here, since we feel that the problem is exiguous, and `reledmac` is quite baroque enough already. If you think you are having this problem, look up Michael's solutions.

One more thing; we set `\leftskip` and `\rightskip` to zero. This has the effect of neutralizing any such skips which may apply to the main text (cf. XIII.6.2 p. 195 above). We need to do this, since `\footfudgefactor` is calculated on the assumption that the notes are `\hsize` wide.

So, finally, here is the modified foot-paragraph code, which sets the footnote in vertical mode so that language and discretionary nodes are included.

```

3382 \newcommand*{\paravfootnote}[2]{%
3383   \csuse{Xbeforeinserting@#1}%
3384   \insert\csname #1footins\endcsname
3385   \bgroup
3386     \csuse{Xnotefontsize@#1}
3387     \footplitskips
3388     \setbox0=\vbox{\hsize=\maxdimen%
3389       \let\@RTL@everypar\@empty%
3390       \insert@Xtxtbeforenotes{#1}%
3391       \noindent\csuse{Xhooknote@#1}%
3392       \csname #1footfmt\endcsname #2{#1}}%
3393     \setbox0=\hbox{\Xunvvh{0}{#1}}%
3394     \dp0=0pt
3395     \ht0=\csname #1footfudgefactor\endcsname\wd0
3396   %

```

Here we produce the contents of the footnote from box 0, and add a penalty of 0 between boxes in this insert.

```

3397   \if@RTL\noindent \leavevmode\fi\box0%
3398   \penalty0
3399   \egroup}
3400
3401 %

```

³⁴Wayne supplied his own macros to do this, but since they were almost identical to Michael's, Peter Wilson have used the latter's `\Xunvvh` macro since it is publicly documented.

³⁵"Line Breaking", p. 610.

The final penalty of 0 was added here at Wayne’s suggestion to avoid a weird page-breaking problem, which occurs on those occasions when \TeX attempts to split foot paragraphs. After trying out such a split (see *The TeXbook*, p. 124), \TeX inserts a penalty of -10000 here, which nearly always forces the break at the end of the whole footnote paragraph (since individual notes can’t be split) even when this leads to an overfull vbox. The change above results in a penalty of 0 instead which allows, but does not force, such breaks. This penalty of 0 is later removed, after page breaks have been decided, by the `\unpenalty` macro in `\makehboxofhboxes`. So it does not affect how the footnote paragraphs are typeset (the notes still have a penalty of -10 between them, which is added by `\parafootfmt`).

`\mpparavfootnote` This version is for minipages.

```

3402 \newcommand*{\mpparavfootnote}[2]{%
3403   \global\setbox\@nameuse{mp#1footins}\vbox{%
3404     \unvbox\@nameuse{mp#1footins}%
3405     \csuse{Xnotefontsize@#1}
3406     \footsplitskips
3407     \setbox0=\vbox{\hsize=\maxdimen%
3408       \let\bidir@RTL@everypar\@empty%
3409       \insert@Xtxtbeforenotes{#1}%
3410       \noindent\color@begingroup%
3411       \csuse{Xhooknote@#1}%
3412       \csname #1footfmt\endcsname #2{#1}\color@endgroup}%
3413     \setbox0=\hbox{\Xunvxh{0}{#1}}%
3414     \dp0=\z@
3415     \ht0=\csname #1footfudgefactor\endcsname\wd0
3416     \box0
3417     \penalty0
3418   }}
3419
3420 %

```

`\Xunvxh` Here is (modified) Michael’s definition of `\unvxh`, used above. Michael’s macro also takes care to remove some unwanted penalties and glue that \TeX automatically attaches to the end of paragraphs. When \TeX finishes a paragraph, it throws away any remaining glue, and then tacks on the following items: a `\penalty` of 10000, a `\parfillskip` and a `\rightskip` (*The TeXbook*, pp. 99–100). `\unvxh` cancels these unwanted paragraph-final items using `\unskip` and `\unpenalty`.

```

3421 \newcommand*{\Xunvxh}[2]{%
3422   \setbox0=\vbox{\unvbox#1%
3423     \global\setbox1=\lastbox}%
3424   \unhbox1
3425   \unskip           % remove \rightskip,
3426   \unskip           % remove \parfillskip,
3427   \unpenalty        % remove \penalty of 10000,
3428   \hskip\csuse{Xafternote@#2}\relax}% add the glue to go between the notes
3429
3430 %

```

`\parafootfmt` `\parafootfmt` is `\normalfootfmt` adapted to do the special stuff needed for paragraphed notes — leaving out the `\endgraf` at the end, sticking in special penalties and kern and leaving out the `\footstrut`. The first argument is the line and page number information, the second is the lemma, the third is the text of the footnote, and the fourth is the series (optional, for backward compatibility).

```

3431 \newcommand*{\parafootfmt}[4]{%
3432   \Xstorelineinfo{#1}{#4}%
3433   \Xinsertparafootsep{#4}%
3434   \ledsetnormalparstuff@common%
3435   \printlinefootnote{#1}{#4}%
3436   \print@lemma{#1}{#2}{#4}%
3437   \csuse{Xwrapcontent@#4}{#3}%
3438   \penalty-10 }
3439 %

```

Note that in the above definition, the penalty of -10 encourages a line break between notes, so that notes have a slight tendency to begin on new lines. The `\Xinsertparafootsep` command is used to insert the `\Xparafootsep@series` between each note in the *same* page.

`\parafootgroup` This footgroup code is modelled on the macros in *The TeXbook*, p. 399. The only difference is the `\unpenalty` in `\makehboxofhboxes`, which is there to remove the penalty of 0 which was added to the end of each footnote by `\paravfootnote`.

The call to `\Xnotefontsize@s` is to ensure that the correct `\baselineskip` for the footnotes is used. The argument is the note series letter.

```

3440 \newcommand*{\parafootgroup}[1]{%
3441   \hsize=\expandafter\dimexpr\csuse{Xwidth@#1}\relax%
3442   \unvbox\csname #1footins\endcsname
3443   \ifcsstring{Xragged@#1}{L}{\RaggedLeft}{}%
3444   \ifcsstring{Xragged@#1}{R}{\RaggedRight}{}%
3445   \makehboxofhboxes
3446   \setbox0=\hbox{\unhbox0 \removehboxes}%
3447   \csuse{Xhookgroup@#1}%
3448   \csuse{Xnotefontsize@#1}%
3449   \unhbox0\par%
3450   \global\hsize=\old@hsize%
3451   }%
3452 %
3453 %

```

`\mpparafootgroup` The minipage version.

```

3454 \newcommand*{\mpparafootgroup}[1]{%
3455   \setXnoteswidthliketwocolumns@{#1}%
3456   \vskip\skip\@nameuse{mp#1footins}
3457   \ifl@dpairing\ifparledgroup%
3458     \leavevmode\marks\parledgroup@{begin}%
3459     \marks\parledgroup@series{#1}%

```

```

3460 \marks\parledgroup@type{Xfootnote}%
3461 \fi\fi\normalcolor
3462 \ifparledgroup%
3463 \ifl@dpairing%
3464 \else%
3465 \setXnoteswidthliketwocolumns@{#1}%
3466 \setXnotespositionliketwocolumns@{#1}%
3467 \print@Xfootnoterule{#1}%
3468 \fi%
3469 \else%
3470 \setXnoteswidthliketwocolumns@{#1}%
3471 \setXnotespositionliketwocolumns@{#1}%
3472 \print@Xfootnoterule{#1}%
3473 \fi%
3474 \unvbox\csname mp#1footins\endcsname
3475 \ifcsstring{Xragged@#1}{L}{\RaggedLeft}{}%
3476 \ifcsstring{Xragged@#1}{R}{\RaggedRight}{}%
3477 \makehboxofhboxes
3478 \setbox0=\hbox{\unhbox0 \removehboxes}%
3479 \csuse{Xbhookgroup@#1}%
3480 \csuse{Xnotefontsize@#1}%
3481 \Xsetparindent{#1}%
3482 \unhbox0\par}}
3483
3484 %

```

And finally, the two macros which are required to transform the long horizontal box stored in the insert' box to a printable text.

```

\makehboxofhboxes85 \newcommand*{\makehboxofhboxes}{\setbox0=\hbox{}}%
\removehboxes86 \loop
3487 \unpenalty
3488 \setbox2=\lastbox
3489 \ifhbox2
3490 \setbox0=\hbox{\box2\unhbox0}%
3491 \repeat}
3492
3493 \newcommand*{\removehboxes}{\setbox0=\lastbox
3494 \ifhbox0{\removehboxes}\unhbox0 \fi}
3495
3496 %

```

Insertion of the footnotes separator The command `\Xinsertparafootsep{<series>}` must be called at the beginning of `\parafootftm`.

```

\prevpage@num97 \newcommand{\Xinsertparafootsep}[1]{%
\Xinsertparafootsep98 \ifledRcol@%
3499 \ifnumequal{\csuse{#1prevpage@numR}}{\page@numR}%

```

```

3500     {\ifcsdef{prevline#1}% Be sur \prevline#1 exists.
3501       {\ifcsequal{prevline#1}{lineinfo@}%
3502         {\ifcempty{Xsymlinenum@#1}{\csuse{Xparafootsep@#1}}{}}%
3503         {\csuse{Xparafootsep@#1}}%
3504       }%
3505       {\csuse{Xparafootsep@#1}}%
3506     }%
3507     {}%
3508     \global\csname #1prevpage@numR\endcsname=\page@numR%
3509   \else%
3510     \ifnumequal{\csuse{#1prevpage@num}}{\page@num}%
3511       {\ifcsdef{prevline#1}% Be sur \prevline#1 exists.
3512         {\ifcsequal{prevline#1}{lineinfo@}%
3513           {\ifcempty{Xsymlinenum@#1}{\csuse{Xparafootsep@#1}}{}}%
3514           {\csuse{Xparafootsep@#1}}%
3515         }%
3516         {\csuse{Xparafootsep@#1}}%
3517       }%
3518       {}%
3519       \global\csname #1prevpage@num\endcsname=\page@num%
3520     \fi%
3521   }
3522   %

```

XIII.6.4 Columnar footnotes

Common tools

`\rigidbalance` We will now define macros for three-column notes and two-column notes. Both sets of macros will use `\rigidbalance`, which splits a box (#1) into a number (#2) of columns, each with a space (#3) between the top baseline and the top of the `\vbox`. The `\rigidbalance` macro is taken from *The TeXbook*, p. 397, with a slight change to the syntax of the arguments so that they do not depend on white space. Note also the extra unboxing in `\splitoff`, which allows the new `\vbox` to have its natural height as it goes into the alignment.

The \LaTeX `\line` macro has no relationship to the TeX `\line`. The \LaTeX equivalent is `\@@line`.

We do not call directly `\rigidbalance`, but we call `\Xrigidbalance` for critical notes and `\rigidbalanceX` for familiar notes. Both of them call `\rigidbalance`.

```

3523 \newcount\@k \newdimen\@h
3524 \newcommand*{\Xrigidbalance}[3]{%
3525   \hsize=\expandafter\dimexpr\csuse{Xwidth@}\currentseries\relax%
3526   \rigidbalance{#1}{#2}{#3}%
3527 }%
3528
3529 \newcommand*{\rigidbalanceX}[3]{%
3530   \hsize=\expandafter\dimexpr\csuse{widthX@}\currentseries\relax%
3531   \rigidbalance{#1}{#2}{#3}%

```

```

3532 }%
3533
3534 \newcommand*{\rigidbalance}[3]{%
3535   \setbox0=\box#1 \@k=#2 \@h=#3%
3536   \@@line{\splittopskip=\@h \vbadness=\@M \hfilneg
3537   \valign{##\vfil\cr\dosplits}}}}
3538
3539 \newcommand*{\dosplits}{\ifnum\@k>0 \noalign{\hfil}\splitoff
3540   \global\advance\@k-1\cr\dosplits\fi}
3541
3542 \newcommand*{\splitoff}{\dimen0=\ht0
3543   \divide\dimen0 by\@k \advance\dimen0 by\@h
3544   \setbox2 \vsplit0 to \dimen0
3545   \unvbox2 }
3546
3547 %

```

Three columns

```

\Xarrangement@threecol 48 \newcommand*{\Xarrangement@threecol}[1]{%
3549   \csgdef{series@display#1}{threecol}
3550   \expandafter\let\csname v#1footnote\endcsname=\threecolvfootnote
3551   \expandafter\let\csname #1footfmt\endcsname=\threecolfootfmt
3552   \expandafter\let\csname #1footgroup\endcsname=\threecolfootgroup
3553   \dimen\csname #1footins\endcsname=\csuse{Xmaxhnotes@#1}%
3554   \skip\csname #1footins\endcsname=\csuse{Xbeforenotes@#1}%
3555   \advance\skip\csname #1footins\endcsname by\csuse{Xafterrule@#1}%
3556   \threecolfootsetup{#1}
3557   %

```

The additional setup for minipages.

```

3558   \ifnoledgroup@else
3559     \expandafter\let\csname mpv#1footnote\endcsname=\mpnormalvfootnote
3560     \expandafter\let\csname mp#1footgroup\endcsname=\mpthreecolfootgroup
3561     \skip\csname mp#1footins\endcsname=\csuse{Xbeforenotes@#1}%
3562     \advance\skip\csname mp#1footins\endcsname by\csuse{Xafterrule@#1}%
3563     \mpthreecolfootsetup{#1}
3564   \fi
3565 }
3566
3567 %

```

The `\footstart` and `\footnoterule` macros for these notes assume the normal values (XIII.6.2 p. 195 above).

`\threecolfootsetup` The `\threecolfootsetup` macro calculates and sets some numbers for three-column footnotes.

We set the `\count` of the foot insert to 333. Each footnote can be thought of as contributing only one third of its height to the page, since the footnote insertion has

been made as a long narrow column, which then gets trisected by the `\rigidbalance` routine (inside `\threecolfootgroup`). These new, shorter columns are saved in a box, and then that box is *put back* into the footnote insert, replacing the original collection of the footnotes. This new box is, therefore, only about a third of the height of the original one.

The `\dimen` value for this note series has to change in the inverse way: it needs to be three times the actual limit on the amount of space these notes are allowed to fill on the page, because when \TeX is accumulating material for the page and checking that limit, it does not apply the `\count` scaling.

```

3568 \newcommand*{\threecolfootsetup}[1]{%
3569   \count\csname #1footins\endcsname 333
3570   \csxdef{default@#1footins}{333}%Use this to confine the notes to one
side only
3571   \multiply\dimen\csname #1footins\endcsname \thr@@}
3572   %

```

`\mpthreecolfootsetup` The setup for minipages.

```

3573 \newcommand*{\mpthreecolfootsetup}[1]{%
3574   \count\csname mp#1footins\endcsname 333
3575   \multiply\dimen\csname mp#1footins\endcsname \thr@@}
3576   %
3577   %

```

`\threecolvfootnote` `\threecolvfootnote` This is the `\vfootnote` command for three-column notes. However, most of the code is deported on `\threecolvfootnote@inserted`. The call to `\Xnotefontsize@<s>` ensures that the `\splittopskip` and `\splitmaxdepth` take their values from the right `\strutbox`: the one used in a footnotes. Note especially the importance of temporarily reducing the `\hsize` to 0.3 of its normal value. This determines the widths of the individual columns. So if the normal `\hsize` is (say) 10 cm, then each column will be $0.3 \times 10 = 3$ cm wide, leaving a gap of 1 cm spread equally between columns (i.e., .5 cm between each).

The arguments are #1 the note series letter and #1 the full text of the note (including numbers, lemma and text).

```

3578 \notbool{parapparatus@}\newcommand*{\newcommand}{\threecolvfootnote}[2]{%
3579   \iftoggle{Xgroupbyline@#1}{%
3580     \prepare@Xgroupbyline{#1}{#2}{\threecolvfootnote@inserted}%
3581   }%
3582   {%
3583     \let\bid@RTL@everypar\relax%
3584     \X@beforeinsertion{#1}%
3585     \insert\csname #1footins\endcsname{%
3586       \threecolvfootnote@inserted{#1}{#2}%
3587     }%
3588   }%
3589   %
3590   %

```

```

\threecol@begin@insert \notbool{parapparatus@}{\newcommand*}{\newcommand}{\
threecol@begin@insert}[2]{%
3592 \hspace=\expandafter\dimexpr\csuse{Xwidth@#1}\relax%
3593 \noindent\csuse{Xhooknote@#1}%
3594 \csuse{Xnotefontsize@#1}%
3595 \footssplitsskip%
3596 \csname #1footfmt\endcsname #2{#1}%
3597 }%
3598 %

```

\threecolfootfmt \threecolfootfmt is the command that formats one note. The arguments are #1 the line numbers, #2 the lemma and #4 the text of the -footnote command #4 optional (for backward compatibility): the series.

```

3599 \notbool{parapparatus@}{\newcommand*}{\newcommand}{\threecolfootfmt}[4]{%
3600 \Xstorelineinfo{#1}{#4}%
3601 \threecol@begin@insert{#4}%
3602 \hspace{\parindent}%
3603 \printlinefootnote{#1}{#4}%
3604 \print@lemma{#1}{#2}{#4}%
3605 \csuse{Xwrapcontent@#4}{#3}%
3606 \nottoggle{Xgroupbyline@#4}%
3607 {\strut\par\allowbreak}%
3608 }%
3609 }%
3610 %

```

\threecol@begin@insert The \threecol@begin@insert contains code used at the beginning of any \insert for critical footnotes in three columns. It is used both by \threecolfootfmt and by \insert@Xtxtbeforenotes.

```

3611 \newcommand{\threecol@begin@insert}[1]{%
3612 \normal@pars%
3613 \nottoggle{Xgroupbyline@#1}%
3614 {\hspace \csuse{Xhsizethreecol@#1}}%
3615 }%
3616 \Xsetparindent{#1}%
3617 \tolerance=5000%
3618 \Xsethangindent{#1}%
3619 \@tempdima=\parindent%
3620 \csuse{Xcolalign@#1}%
3621 \parindent=\@tempdima%
3622 \strut%
3623 }%
3624 %

```

\threecolfootgroup And here is the footgroup macro that is called within the output routine to regroup the notes into three columns. Once again, the call to \Xnotefontsize@<s> is there to ensure that it is the right \splittopskip—the one used in footnotes—which is used to provide

the third argument for `\rigidbalance`. This third argument (`\@h`) is the `topskip` for the box containing the text of the footnotes, and does the job of making sure the top lines of the columns line up horizontally. In *The TeXbook*, p. 398, Donald Knuth suggests retrieving the output of `\rigidbalance`, putting it back into the insertion box, and then printing the box. Here, we just print the `\line` which comes out of `\rigidbalance` directly, without any re-boxing.

```

3625 \newcommand*{\threecolfootgroup}[1]{%
3626   \begingroup%
3627   \csuse{Xbhookgroup@#1}%
3628   \csuse{Xnotefontsize@#1}%
3629   \par%
3630   \splittopskip=\ht\strutbox%
3631   \expandafter%
3632   \Xrigidbalance\csname #1footins\endcsname \thr@@ \splittopskip%
3633   \endgroup%
3634 }%
3635 %

```

`\mpthreecolfootgroup` The setup for minipages.

```

3636 \newcommand*{\mpthreecolfootgroup}[1]{%
3637   \vskip\skip\@nameuse{mp#1footins}
3638   \ifl@dpairing\ifparledgroup%
3639     \leavevmode\marks\parledgroup@{begin}%
3640     \marks\parledgroup@series{#1}%
3641     \marks\parledgroup@type{Xfootnote}%
3642   \fi\fi\normalcolor
3643   \ifparledgroup%
3644     \ifl@dpairing%
3645     \else%
3646       \setXnoteswidthliketwocolumns@{#1}%
3647       \setXnotespositionliketwocolumns@{#1}%
3648       \print@Xfootnoterule{#1}%
3649     \fi%
3650   \else%
3651     \setXnoteswidthliketwocolumns@{#1}%
3652     \setXnotespositionliketwocolumns@{#1}%
3653     \print@Xfootnoterule{#1}%
3654   \fi%
3655   \csuse{Xbhookgroup@#1}\par%
3656   \splittopskip=\ht\strutbox
3657   \expandafter
3658   \Xrigidbalance\csname mp#1footins\endcsname \thr@@ \splittopskip}}
3659
3660 %

```

Two columns


```

\Xarrangement@twocol 3661 \newcommand*{\Xarrangement@twocol}[1]{%
3662 \csgdef{series@display#1}{twocol}
3663 \expandafter\let\csname v#1footnote\endcsname=\twocolvfootnote
3664 \expandafter\let\csname #1footfmt\endcsname=\twocolfootfmt
3665 \expandafter\let\csname #1footgroup\endcsname=\twocolfootgroup
3666 \dimen\csname #1footins\endcsname=\csuse{Xmaxhnotes@#1}%
3667 \skip\csname #1footins\endcsname=\csuse{Xbeforenotes@#1}%
3668 \advance\skip\csname #1footins\endcsname by\csuse{Xafterrule@#1}%
3669 \twocolfootsetup{#1}
3670 %

```

The additional setup for minipages.

```

3671 \ifnoledgroup@else
3672 \expandafter\let\csname mpv#1footnote\endcsname=\mpnormalvfootnote
3673 \expandafter\let\csname mp#1footgroup\endcsname=\mptwocolfootgroup
3674 \skip\csname mp#1footins\endcsname=\csuse{Xbeforenotes@#1}%
3675 \advance\skip\csname mp#1footins\endcsname by\csuse{Xafterrule@#1}%
3676 \mptwocolfootsetup{#1}
3677 \fi
3678 }
3679 %
3680 %

```

Here is a series of macros which are very similar to their three-column counterparts. In this case, each note is assumed to contribute only a half a line of text. And the notes are set in columns giving a gap between them of one tenth of the `\hsiz`.

```

\twocolfootsetup 3681 \newcommand*{\twocolfootsetup}[1]{%
\twocolvfootnote 3682 \count\csname #1footins\endcsname 500
\twocolvfootnote@inserted 3683 \csxdef{default@#1footins}{500}%
\twocolfootfmt 3684 \multiply\dimen\csname #1footins\endcsname \tw@
\twocolfootgroup 3685 %

```

```

3686 \notbool{parapparatus@}{\newcommand*{\newcommand}{\twocolvfootnote}[2]{%
3687 \iftoggle{Xgroupbyline@#1}{%
3688 \prepare@Xgroupbyline{#1}{#2}{\twocolvfootnote@inserted}%
3689 }{%
3690 \let\bidir@RTL@everypar\relax%
3691 \X@beforeinsertion{#1}%
3692 \insert\csname #1footins\endcsname{%
3693 \twocolvfootnote@inserted{#1}{#2}%
3694 }%
3695 }%
3696 }%
3697 \notbool{parapparatus@}{\newcommand*{\newcommand}{\twocolvfootnote@inserted}[2]{%
3698 \hsiz=\expandafter\dimexpr\csuse{Xwidth@#1}\relax%
3699 \noindent\csuse{Xhooknote@#1}%
3700 \csuse{Xnotefontsize@#1}%

```

```

3701 \footsplitskips%
3702 \csname #1footfmt\endcsname #2{#1}%
3703 }%
3704 %

3705 \notbool{parapparatus@}{\newcommand*}{\newcommand}{\twocolfootfmt}[4]{% 4th
arg is optional, for backward compatibility
3706 \Xstorelineinfo{#1}{#4}%
3707 \twocol@begin@insert{#4}%
3708 \hspace{\parindent}%
3709 \printlinefootnote{#1}{#4}%
3710 \print@lemma{#1}{#2}{#4}%
3711 \csuse{Xwrapcontent@#4}{#3}%
3712 \nottoggle{Xgroupbyline@#4}%
3713 {\strut\par\allowbreak}%
3714 }%
3715 }%
3716 %

3717 \newcommand{\twocol@begin@insert}[1]{%
3718 \normal@pars%
3719 \nottoggle{Xgroupbyline@#1}%
3720 {\hspace \csuse{Xhsizetwocol@#1}}%
3721 }%
3722 \Xsetparindent{#1}%
3723 \tolerance=5000%
3724 \Xsethangindent{#1}%
3725 \@tempdima=\parindent%
3726 \csuse{Xcolalign@#1}%
3727 \parindent=\@tempdima%
3728 \strut%
3729 }%
3730 %
3731 \newcommand*{\twocolfootgroup}[1]{%
3732 \begin@group%
3733 \csuse{Xbhookgroup@#1}%
3734 \csuse{Xnotefontsize@#1}%
3735 \par%
3736 \splittopskip=\ht\strutbox%
3737 \expandafter%
3738 \Xrigidbalance\csname #1footins\endcsname \tw@ \splittopskip%
3739 \endgroup%
3740 }%
3741 %
3742 %

```

`\mptwocolfootsetup` The versions for minipages.

`\mptwocolfootgroup`

```

3743 \newcommand*{\mptwocolfootsetup}[1]{%
3744 \count\csname mp#1footins\endcsname 500

```

```

3745 \multiply\dimen\csname mp#1footins\endcsname \tw@}
3746 %

3747 \newcommand*\mptwocolfootgroup}[1]{%
3748 \vskip\skip\@nameuse{mp#1footins}
3749 \ifl@dpairing\ifparledgroup%
3750 \leavevmode\marks\parledgroup@{begin}%
3751 \marks\parledgroup@series{#1}%
3752 \marks\parledgroup@type{Xfootnote}%
3753 \fi\fi\normalcolor
3754 \ifparledgroup%
3755 \ifl@dpairing%
3756 \else%
3757 \setXnoteswidthliketwocolumns@{#1}%
3758 \setXnotespositionliketwocolumns@{#1}%
3759 \print@Xfootnoterule{#1}%
3760 \fi%
3761 \else%
3762 \setXnoteswidthliketwocolumns@{#1}%
3763 \setXnotespositionliketwocolumns@{#1}%
3764 \print@Xfootnoterule{#1}%
3765 \fi%
3766 \csuse{Xbhookgroup@#1}\par%
3767 \splittopskip=\ht\strutbox
3768 \expandafter
3769 \Xrigidbalance\csname mp#1footins\endcsname \tw@ \splittopskip}}
3770
3771 %

```

XIII.7 Footnote paragraph indent

\Xsetparindent These two commands set the paragraph indentation of the footnotes, depending on the
\setparindentX settings of the user.

```

3772 \newcommand{\Xsetparindent}[1]{%
3773 \nottoggle{Xparindent@#1}{%
3774 \parindent=\z@%
3775 }%
3776 {%
3777 \ifdef{\parindent@beforestanza}{\parindent=\parindent@beforestanza}{}%
3778 }%
3779 }%
3780 \newcommand{\setparindentX}[1]{%
3781 \nottoggle{parindentX@#1}{%
3782 \parindent=\z@%
3783 }%
3784 {%
3785 \ifdef{\parindent@beforestanza}{\parindent=\parindent@beforestanza}{}%
3786 }%

```

```

3787 }%
3788 %

```

XIII.8 Footnote hanging indent

`\Xsethangindent` `\Xsethangindent` sets the hangindent for a critical footnote, while `\sethangindentX` does it for a familiar footnote.

```

3789 \newcommand{\Xsethangindent}[1]{%
3790   \if@RTL%
3791     \hangindent=-\csuse{Xhangindent@#1}%
3792     \everypar{\hangindent=-\csuse{Xhangindent@#1}}%
3793   \else%
3794     \hangindent=\csuse{Xhangindent@#1}%
3795     \everypar{\hangindent=\csuse{Xhangindent@#1}}%
3796   \fi%
3797 }%
3798 \newcommand{\sethangindentX}[1]{%
3799   \if@RTL%
3800     \hangindent=-\csuse{hangindentX@#1}%
3801     \everypar{\hangindent=-\csuse{hangindentX@#1}}%
3802   \else%
3803     \hangindent=\csuse{hangindentX@#1}%
3804     \everypar{\hangindent=\csuse{hangindentX@#1}}%
3805   \fi%
3806 }%
3807 %

```

XIII.9 Critical notes presentation

Here, we define some commons macro which are used in order to print a critical notes, that is a note with 1) line number 2) lemma 3) lemma separator 4) text associated to the lemma.

XIII.9.1 Font tools

`\endashchar` `\fullstop` `\rbracket` The fonts that are used for printing notes might not have the character mapping we expect: for example, the Computer Modern font that contains old-style numerals does not contain an en-dash or square brackets, and its period and comma are in odd locations. To allow use of the standard footnote macros with such fonts, we use the following macros for certain characters.

The `\endashchar` macro is simply an en-dash from the normal font and is immune to changes in the surrounding font. The same goes for the full stop. These two are used in `\printlines`. The right bracket macro is the same again; it crops up in `\normalfootfmt` and the other footnote macros for controlling the format of the footnotes.

Note that these commands are not directly called by `reledmac`, but are enclosed as default value of specific hooks. Consequently, people should not redefine them, but use

instead the `\Xlinerangeseparator`, `\Xendlinerangeseparator`, `\Xsublinesep`, `\Xendsublinesep` and `\Xlemmaseparator` macros.

With `polyglossia`, each critical note has a `\footnote@lang` which shows the language of the lemma, and which can be used to switch the bracket from right to left.

```

3808 \def\endashchar{\textnormal{--}}
3809
3810 \newcommand*\fullstop{\textnormal{.}}
3811 \def\Xsublinesep@side{\fullstop}
3812
3813 \newcommand*\rbracket{\textnormal{%
3814   \csuse{text}\csuse{footnote@lang}}}%
3815   \ifluatex%
3816   \ifdefstring{footnote@luatextextdir}{TRT}{\thinspace[]{\thinspace
3817   }}%
3818   \else%
3819   \thinspace]%
3820   \fi}%
3821 }
3822
3823 %

```

XIII.9.2 Pstart number in footnote

`\printpstart` The `\printpstart` macro prints the pstart number for a note.

```

3824 \newcommand{\printpstart}[0]{%
3825   \ifboolexpr{bool{l@dpairing} or bool{l@dprintingpages} or bool{
3826   l@dprintingcolumns}}{%
3827     \ifledRcol%
3828     \thepstartR%
3829     \else%
3830     \thepstartL%
3831     \fi%
3832   }{%
3833     \thepstart%
3834   }%
3835 }

```

XIII.9.3 Lemma printing

`\print@lemma` `\print@lemma` is called inside critical footnotes to print the lemma and the lemma separator (#1: line number and font information, #2: lemma, #3: series).

```

3836 %
3837 \newcommand{\print@lemma}[3]{%
3838   \bgroup%
3839   \nottoggle{Xlemmadisablefontselection@#3}%

```

```

3840     {\select@lemmafont#1|}%
3841     }%
3842     \bgroup%
3843     \csuse{Xlemmafont@#3}%Deprecated
3844     \csuse{Xwraplemma@#3}{#2}%
3845     \egroup%
3846     \egroup%
3847     \iftoggle{nosep@}{%
3848     \hskip\csuse{Xinplaceoflemmaseparator@#3}%
3849     \relax%
3850     }%
3851     {\ifcempty{Xlemmaseparator@#3}%
3852     {%
3853     \hskip\csuse{Xinplaceoflemmaseparator@#3}%
3854     \relax%
3855     }%
3856     {%
3857     \nobreak%
3858     \hskip\csuse{Xbeforelemmaseparator@#3}%
3859     \csuse{Xlemmaseparator@#3}%
3860     \hskip\csuse{Xafterlemmaseparator@#3}%
3861     \relax%
3862     }%
3863     }%
3864     }%
3865     %

```

XIII.9.4 Line number printing

\Xstorelineinfo The `\Xstorelineinfo` macro is used to store some data about line number of the current critical footnote, data which will be reused later for the `\Xnumberonlyfirstinline` and related setting.

#1 footnote specification for the current footnote; #2 footnote series.

```

3866 \newcommand{\Xstorelineinfo}[2]{%
3867   \l@dp@rsefootspec#1|}%
3868   \iftoggle{Xnumberonlyfirstintwolines@#2}{%
3869     \xdef\lineinfo@{\l@dparsedstartline - \l@dparsedstartsub - \
3870     l@dparsedendline - \l@dparsedendsub}%
3871     }%
3872     {%
3873     \xdef\lineinfo@{\l@dparsedstartline - \l@dparsedstartsub}%
3874     }%
3875     %

```

\printlinefootnote The `\printlinefootnote` macro is called in each `\<type>footfmt` command. It controls whether the line number is printed or not, according to the series options. Its first

argument is the information about lines; its second is the series of the footnote. The printing of the line number is shared in `\printlinefootnotenumbers`.

```

3876 \newcommand{\printlinefootnote}[2]{%
3877   \xdef\@currentseries{#2}%
3878   \iftoggle{nonum@}{%Try if the line number must printed for this specific
not (by default, yes)
3879   \hspace{\csuse{Xinplaceofnumber@#2}}%
3880   }%
3881   {%
3882     {%
3883       \iftoggle{Xnonumber@#2}%Try if the line number must printed (by
default, yes)
3884       {%
3885         \hspace{\csuse{Xinplaceofnumber@#2}}%
3886         }%
3887         {%
3888           {\iftoggle{Xnumberonlyfirstinline@#2}% If for this series the
line number must be printed only in the first time.
3889             {%
3890               \ifcsdef{prevline#2}%
3891               {%Be sure the \prevline exists.
3892               \ifcsequal{prevline#2}{\lineinfo@}%Try it
3893               {%
3894                 \ifcsequal{Xsymlinenumber@#2}%
3895                 {%
3896                   \hspace{\csuse{Xinplaceofnumber@#2}}%
3897                   }%
3898                   {\printsymlinefootnotearea{#2}}%
3899                   }%
3900                   {%
3901                     \printlinefootnotearea{#1}{#2}%
3902                     }%
3903                   }%
3904                   {%
3905                     \printlinefootnotearea{#1}{#2}%
3906                     }%
3907                   }%
3908                   {%
3909                     \printlinefootnotearea{#1}{#2}%
3910                     }%
3911                     \csxdef{prevline#2}{\lineinfo@}%
3912                     }%
3913                   }%
3914                   }%
3915                   }%
3916   }
3917   %

```

`\printsymlinefootnotearea` This macro prints the space before the line symbol, changes the font, when prints the

line symbol and the space after it.

```

3918 \newcommand{\printsymlinefootnotearea}[1]{%
3919   \hspace{\csuse{Xbeforesymmlinenumber@#1}}%
3920   \csuse{Xnotenumfont@#1}%
3921   \ifdimequal{\csuse{Xboxsymmlinenumber@#1}}{\z@}%
3922     {\csuse{Xsymmlinenumber@#1}}%
3923     {\hbox to \csuse{Xboxsymmlinenumber@#1}%
3924       {\csuse{Xsymmlinenumber@#1}\hfill}%
3925     }%
3926   \hspace{\csuse{Xaftersymmlinenumber@#1}}%
3927 }%
3928 %

```

\printlinefootnotearea This macro prints the space before the line number, changes the font, then prints the line number and the space after it. It is called by `\printlinefootnote` depending on the options about repeating line numbers. The first argument is line information, the second is the notes series (A, B, C, etc.)

```

3929 \newcommand{\printlinefootnotearea}[2]{%
3930   \printXbeforenumber{#2}%
3931   \csuse{Xnotenumfont@#2}%
3932   \boxfootnotenumbers{#1}{#2}%
3933   \printXafternumber{#2}%
3934 }%
3935 %

```

\boxfootnotenumbers Depending on the user settings, this macro will box line numbers (or not). The first argument is line information, the second is the notes series (A, B, C, etc.) The previous `\printlinefootnotearea` calls it.

```

3936 \newcommand{\boxfootnotenumbers}[2]{%
3937   \ifdimequal{\csuse{Xboxlinenumber@#2}}{\Opt}{%
3938     \printlinefootnotenumbers{#1}{#2}%
3939   }%
3940   {%
3941     \hbox to \csuse{Xboxlinenumber@#2}%
3942     {%
3943       \IfSubStr{RC}{\csuse{Xboxlinenumberalign@#2}}{\hfill}{}%
3944       \printlinefootnotenumbers{#1}{#2}%
3945       \IfSubStr{LC}{\csuse{Xboxlinenumberalign@#2}}{\hfill}{}%
3946     }%
3947   }%
3948 }%
3949 %

```

\printlinefootnotenumbers This macro prints, if needed, the pstart number and the line number. The first argument is line information, the second is the notes series (A, B, C, etc.) The previous `\boxlinefootnote` calls it.


```

3950 \newcommand{\printlinefootnotenumbers}[2]{%
3951   \get@pstartcounter%
3952   \ifboolexpr{%
3953     (togl{Xpstart@#2} and bool{numberpstart})%
3954     or togl{Xpstarteverytime@#2}%
3955     and not (%
3956       togl{Xpstartonlyfirst@#2}%
3957       and test {\ifnumequal{\csuse{Xprevpstart@#2}}{\current@pstart}}%
3958     )%
3959   }%
3960   {%
3961     \printpstart%
3962     \csuse{Xpstartseparator@#2}%
3963   }{}%
3964   \global\cslet{Xprevpstart@#2}{\current@pstart}%
3965   \get@stanzacounter%
3966   \ifboolexpr{%
3967     togl{Xstanza@#2}%
3968     and bool {numberstanza}%
3969     and not (%
3970       togl{Xpstartonlyfirst@#2}%
3971       and test {\ifnumequal{\csuse{Xprevstanza@#2}}{\current@stanza}}%
3972     )%
3973   }{%
3974     \printstanza%
3975     \csuse{Xstanzaseparator@#2}%
3976   }{}%
3977   \global\cslet{Xprevstanza@#2}{\current@stanza}%
3978   \iftoggle{Xonlypstart@#2}{%
3979     \csuse{Xtxtbeforenumber@#2}%
3980     \printlines#1|\ifledRcol@{\@Rlineflag\fi}}%
3981   }%
3982   %

```

`\get@pstartcounter` A single macro to get the current pstart counter.

```

3983 \newcommand{\get@pstartcounter}[0]{%
3984   \ifboolexpr{bool{l@dprintingpages} or bool{l@dprintingcolumns}}%
3985   {%
3986     \ifledRcol%
3987       \global\numdef\current@pstart{\the\c@pstartR}%
3988     \else%
3989       \global\numdef\current@pstart{\the\c@pstartL}%
3990     \fi%
3991   }%
3992   {%
3993     \global\numdef\current@pstart{\the\c@pstart}%
3994   }%
3995   }%
3996   %

```

`\get@stanzacounter` The same to get the current stanza counter.

```

3997 \newcommand{\get@stanzacounter}[0]{%
3998   \ifbool{bool{!@dprintingpages}} or bool{!@dprintingcolumns}}%
3999   {%
4000     \ifl@Rcol%
4001       \global\numdef\current@stanza{\the\c@stanzaR}%
4002     \else%
4003       \global\numdef\current@stanza{\the\c@stanzaL}%
4004     \fi%
4005   }%
4006   {%
4007     \global\numdef\current@stanza{\the\c@stanza}%
4008   }%
4009 }%
4010 %

```

`\printXbeforenumber` This macro prints a space (before the line number) in footnote. It is called by `\printlinefootnotearea`. Its only argument is the note series (A, B, C, etc.)

```

4011 \newcommand{\printXbeforenumber}[1]{%
4012   \hspace{\csuse{Xbeforenumber@#1}}%
4013 }%
4014 %

```

`\printXafternumber` This macro prints the space, adding eventually a `\nobreak`, after the line number, in footnote. It is called by `\printlinefootnotearea`. Its only argument is the series

```

4015 \newcommand{\printXafternumber}[1]{%
4016   \iftoggle{Xnonbreakableafternumber@#1}{\nobreak}{}%
4017   \hspace{\csuse{Xafternumber@#1}}%
4018 }%
4019 %

```

If we have decided to print the line number in a specific notes, the `\printlines` macro prints the line numbers for a note—which, in the general case, is a rather complicated task. The seven parameters of the argument are the line numbers as stored in `\l@d@nums`, in the form described on V.9 p. 113: the starting page, line, and sub-line numbers, followed by the ending page, line, and sub-line numbers, and then the font specifier for the lemma.

edmac’ creator have defined six boolean in order to know which component of line number description we have to print:

- `\ifl@d@pnum` for page numbers;
- `\ifl@d@ssub` for starting sub-line;
- `\ifl@d@elin` for ending line;
- `\ifl@d@esl` for ending sub-line; and

- `\ifl@d@dash` for the dash between the starting and ending groups.

There was no boolean for the line number because it was always printed.

Maïeul Rouquette has added:

- `\ifl@d@Xtwolines` and `\ifl@d@Xmorethantwolines` to print a symbol which stands for “and subsequent” when there are two, three or more lines;
- `\@annot@start@print` and `\@annot@end@print` which define annotations associated with the starting and ending line numbers in critical footnotes;
- `\ifl@d@Xlinenumber`, which value depends on the configuration of `\Xnolinenumber` and `\Xnolinenumberifannotation`.

```

\ifl@d@pnum20 \newif\ifl@d@pnum
\ifl@d@ssub21 \newif\ifl@d@ssub
\ifl@d@elin22 \newif\ifl@d@elin
\ifl@d@esl23 \newif\ifl@d@esl
\ifl@d@dash24 \newif\ifl@d@dash
\ifl@d@Xtwolines25 \newif\ifl@d@Xtwolines%
\ifl@d@Xmorethantwolines26 \newif\ifl@d@Xmorethantwolines%
\ifl@d@Xlinenumber27 \let\@annot@start@print\relax%
\@annot@start@print28 \let\@annot@end@print\relax%
\@annot@end@print29 \newif\ifl@d@Xlinenumber%
30 %

\l@dp@rsefootsspec \l@dp@rsefootsspec{<spec>}{<lemma>}{<text>} parses a footnote specification. <lemma>
\l@dp@rsefootsspec and <text> are the lemma and text respectively. <spec> is the line and page num-
\l@dp@rsefootsspec ber and lemma font specifier in \l@d@n@ums style format. The real work is done by
\l@dp@rsefootsspec \l@dp@rsefootsspec which defines macros holding the numeric values. In many cases,
\l@dp@rsefootsspec this last command is called directly. Just a reminder of the arguments:
\l@dp@rsefootsspec \printlines #1 | #2 | #3 | #4 | #5 | #6 | #7
\l@dp@rsefootsspec \printlines start-page | line | subline | end-page | line | subline | fontflag
\l@dp@rsefootsspec \l@dp@rsefootsspec
4031 \newcommand*{\l@dp@rsefootsspec}[3]{\l@dp@rsefootsspec#1|}
4032 \def\l@dp@rsefootsspec#1|#2|#3|#4|#5|#6|#7|{%
4033 \gdef\l@dp@rsefootsspec#1|{%
4034 \gdef\l@dp@rsefootsspec#2|{%
4035 \gdef\l@dp@rsefootsspec#3|{%
4036 \gdef\l@dp@rsefootsspec#4|{%
4037 \gdef\l@dp@rsefootsspec#5|{%
4038 \gdef\l@dp@rsefootsspec#6|{%
4039 }
4040 %

```

Initialise the several number value macros.

```

4041 \def\l@dp@rsefootsspec{0}%
4042 \def\l@dp@rsefootsspec{0}%
4043 \def\l@dp@rsefootsspec{0}%

```

```

4044 \def\l@dparsedendpage{0}%
4045 \def\l@dparsedendline{0}%
4046 \def\l@dparsedendsub{0}%
4047
4048 %

```

\setprintlines The macro `\setprintlines` does the work of deciding what numbers should be printed. Its arguments are the same as the first 6 of `\printlines`.

```

4049 \newcommand*{\setprintlines}[6]{%
4050   \let\@annot@start@print\relax%
4051   \let\@annot@end@print\relax%
4052   \l@d@pnumfalse%
4053   \l@d@dashfalse%
4054   \l@d@elinfalse%
4055 %

```

Should we print the line number? It depends on hooks and annotations.

```

4056   \l@d@Xlinenumbertrue%
4057   \ifboolexpr{togl{Xnolinenumber@\@currentseries}%
4058     or (%
4059       togl{Xnolinenumberifannotation@\@currentseries}%
4060       and not test{\ifdefvoid{\annot@start}}}%
4061       and not test{\ifdefvoid{\annot@end}}}%
4062     )%
4063   }{%
4064     \l@d@Xlinenumberfalse%
4065   }{%
4066 %

```

We print the page numbers only if: 1) we are doing the lineation by page, and 2) the ending page number is different from the starting page number.

```

4067   \ifbypage@
4068     \ifnum#4=#1 \else
4069       \l@d@pnumtrue
4070       \l@d@dashtrue
4071     \fi
4072   \fi
4073 %

```

We print the ending line number if:

1. we print the ending page number;
2. or the ending line number is different from the starting line number and we didn't disable the line number printing

If either of these conditions is true, we also print the annotation linked to the ending line number annotations.

```

4074 \ifbool{expr}{%
4075   bool{!@d@pnum}%
4076   or {%
4077     not test{\ifnumequal{#2}{#5}}%
4078     and bool{!@d@Xlinenumber}%
4079   }%
4080 }{%
4081   \l@d@elintrue%
4082   \l@d@dashtrue%
4083   \unless\ifx\relax\annot@end%
4084     \def\@annot@end@print{%
4085       \l@wrapcs@ifnotemptybox{Xwraplinenumannotation@\@currentseries}{\
annot@end}%
4086     }%
4087     \fi%
4088   }%
4089 }%

```

We define the starting line number annotation as a merge of the starting annotation and ending annotation if we don't print the ending line number. Otherwise, it is only the starting annotation.

```

4090 \ifl@d@elin%
4091   \def\@annot@start@print{%
4092     \l@wrapcs@ifnotemptybox{Xwraplinenumannotation@\@currentseries}{\
annot@start}%
4093   }%
4094   \else%
4095     \ifx\annot@start\annot@end%
4096       \unless\ifx\@annot@start\relax%
4097         \def\@annot@start@print{%
4098           \l@wrapcs@ifnotemptybox{Xwraplinenumannotation@\@currentseries}{\
annot@start}%
4099         }%
4100         \fi%
4101       \else%
4102         \ifx\@annot@end@print\relax%
4103           \def\@annot@start@print{%
4104             \l@wrapcs@ifnotemptybox{Xwraplinenumannotation@\@currentseries}{%
4105               \ifx\annot@start\empty\else%
4106                 \annot@start%
4107                 \ifdefined\linerangesep%
4108                   \linerangesep%
4109                 \else%
4110                   \csuse{Xlinerangeseparator@\@currentseries}%
4111                 \fi%
4112               \fi%
4113             \annot@end%
4114           }%
4115         }%
4116       \else%

```

```

4117         \let\@annot@start@print\@annot@end@print%
4118         \let\@annot@end@print\relax%
4119         \fi%
4120     \fi%
4121 \fi%
4122 %

```

We print the starting sub-line if it is nonzero.

```

4123 \l@d@ssubfalse
4124 \ifnum#3=0 \else
4125     \l@d@ssubtrue
4126 \fi
4127 %

```

We print the ending sub-line if it is nonzero and: (1) it is different from the starting sub-line number, or (2) the ending line number is being printed.

```

4128 \l@d@eslfalse
4129 \ifnum#6=0 \else
4130     \ifnum#6=#3
4131         \ifl@d@elin \l@d@esltrue \else \l@d@eslfalse \fi
4132     \else
4133         \l@d@esltrue
4134         \l@d@dashtrue
4135     \fi
4136 \fi%
4137 %

```

However, if the `\Xtwolines` is set for the current series, we do not print the last line number.

```

4138 \ifl@d@dash%
4139     \ifboolexpr{togl{fulllines@} or test{\ifcempty{Xtwolines@}\@currentseries}}}%
4140     {}%
4141     {%
4142     \setistwofollowinglines{#1}{#2}{#4}{#5}%
4143     \ifboolexpr{%
4144         (%
4145             togl {Xtwolinesbutnotmore@\@currentseries}%
4146             and not%
4147             (%
4148                 bool {istwofollowinglines@}%
4149             )%
4150         )%
4151         or%
4152         (%
4153             (not test{\ifnumequal{#1}{#4}})%
4154             and togl{Xtwolinesonlyinsamepage@\@currentseries}%
4155         )%
4156     }%

```

```

4157     {}%
4158     {%
4159     \l@d@dashfalse%
4160     \l@d@Xtwolinestrue%
4161     \l@d@elinfalse%
4162     \l@d@eslfalse%
4163     \ifcseempty{Xmorethantwolines@ \@currentseries}%
4164     {}%
4165     {\ifistwofollowinglines@ \else%
4166     \l@d@Xmorethantwolinestrue%
4167     \fi%
4168     }%
4169     }%
4170   }%
4171 \fi%
4172 %

```

If the `\Xnoidenticallinenumannotation` is set for this series, we check if the ending annotation is identical to the starting. If true, we don't print the ending annotation

```

4173 \iftoggle{Xnoidenticallinenumannotation@ \@currentseries}{%
4174 \ifx\annot@start\annot@end%
4175 \let\annot@end@print\relax%
4176 \ifboolexpr{%Do not print the dash if we do not print the line number
4177 test {\ifdefempty{\linenumrep}}}%
4178 or not bool {\l@d@Xlinenumber}%
4179 }{%
4180 \l@d@dashfalse%
4181 }{%
4182 \fi%
4183 }{%
4184 %

```

Finally, we check for `\Xlinenumannotationonlyfirst` and `\Xlinenumannotationonlyfirstintwo`, and we redefine, if required, `\annot@start@print` and `\annot@end@print`. We also store the current line number annotations.

```

4185 \iftoggle{Xlinenumannotationonlyfirst@ \@currentseries}{%
4186 \ifboolexpr{%
4187 (%
4188 togl{Xlinenumannotationonlyfirstintwo@ \@currentseries}%
4189 and test{\ifcsequal{annot@start}{prevannot@start@ \@currentseries}}}%
4190 and test{\ifcsequal{annot@end}{prevannot@end@ \@currentseries}}}%
4191 )%
4192 or%
4193 (%
4194 not togl{Xlinenumannotationonlyfirstintwo@ \@currentseries}%
4195 test{\ifcsequal{annot@start}{prevannot@start@ \@currentseries}}}%
4196 )%
4197 }{%
4198 \def\annot@start@print{%

```

```

4199 \l@wrapcs@ifnotemptybox{Xwraplinenumannotation@ \@currentseries}{\
csuse{Xsymlinenumannotation@ \@currentseries}}}%
4200 }%
4201 \let\@annot@end@print\relax%
4202 \ifboolexpr{%Do not print the dash if we do not print the line number
4203 test {\ifdefempty{\linenumrep}}}%
4204 or not bool {l@d@Xlinenumber}}%
4205 }{%
4206 \l@d@dashedfalse%
4207 }{}%
4208 }{}%
4209 \global\cslet{prevannot@start@ \@currentseries}{\annot@start}%
4210 \global\cslet{prevannot@end@ \@currentseries}{\annot@end}%
4211 }%
4212 {}%
4213 %

End of \setprintlines.

4214 }%
4215 %

```

`\setistwofollowinglines` The `\ifistwofollowinglines` boolean, used by the `\Xtwolines` and related setting, is set to true by `\setistwofollowinglines`. This command takes the following arguments:

- #1 First page number.
- #2 First line number.
- #3 Last page number.
- #4 Last line number.

If $\#3 - \#2 = 1$, then that means the two lines are subsequent, and consequently `\ifistwofollowinglines` is set to true. However, if we use lineation by page, two given lines can be subsequent if:

- The first line number is equal to the last line number of the first page.
- The last line number is equal to 1.
- $\#3 - \#1$ is equal to 1.

```

4216 \newif\ifistwofollowinglines@%
4217 \newcommand{\setistwofollowinglines}[4]{%
4218 \ifcsdef{lastlinenumberon#1}%
4219 {\numdef{\tmp}{\csuse{lastlinenumberon#1}}}%
4220 {\numdef{\tmp}{0}}}%
4221 \istwofollowinglines@false%
4222 \ifnumequal{\#4-\#2}{1}%

```



```

4223 {\istwofollowinglines@true}%
4224 {\ifbypage%
4225   \ifnumequal{#3-#1}{1}%
4226   {%
4227     \ifnumequal{#2}{\tmp}%
4228     {\ifnumequal{#4}{1}{\istwofollowinglines@true}{}}%
4229     {}}%
4230   }%
4231   {%
4232   \fi%
4233   }%
4234 }%
4235 %

```

`\printlines` So, we have decided which part of line number sets will be printed depending on these values. Now we are ready to print them. If the lineation is by pstart, we print the pstart. Arguments are 1) start page number 2) start line number 3) start subline number 4) end page number 5) end line number 6) end subline number 7) font specification 8) side flag

```

4236 \def\printlines#1|#2|#3|#4|#5|#6|#7|#8|{%
4237   \begingroup%
4238   %

```

Decide which part of line number components we will print.

```

4239   \setprintlines{#1}{#2}{#3}{#4}{#5}{#6}%
4240   %

```

One subtlety left here is when to print a period between numbers. But the only instance in which this is tricky is for the ending sub-line number: it could come after the starting sub-line number (in which case we want only the dash) or after an ending line number (in which case we need to insert a period). So, first, print the start line number.

```

4241   \ifdimequal{\csuse{Xboxstartlinenum@\@currentseries}}{0pt}%
4242   {\bgroup}%
4243   {\leavevmode\hbox to \csuse{Xboxstartlinenum@\@currentseries}\bgroup\
4244   hfill}%
4245   \ifcsstring{Xlinenumannotationposition@\@currentseries}{before}%
4246   {\@annot@start@print}%
4247   {%
4248     \ifl@d@pnum%
4249     \wrap@edcrossref{\@this@crossref@start}{#1}%
4250     \ifl@d@Xlinenum%
4251     \csuse{Xpagelinesep@\@currentseries}%
4252     \fi%
4253     \ifl@d@Xlinenum%
4254     \wrap@edcrossref{\@this@crossref@start}{%
4255       \linenumrep{#2}%
4256       \iftoggle{Xlineflag@\@currentseries}{#8}{}}%
4257     }%

```

```

4258 \ifl@d@ssub%
4259 \csuse{Xsublinesep@ \@currentseries}%
4260 \wrap@edcrossref{\@this@crossref@start}{\sublinenumrep{#3}}%
4261 \fi%
4262 \fi%
4263 \ifcsstring{Xlinenumannotationposition@ \@currentseries}{after}%
4264 {\@annot@start@print}%
4265 {}%
4266 \egroup%
4267 %

```

Then print the dash + end line number, or the range symbol.

```

4268 \ifdimequal{\csuse{Xboxendlinenum@ \@currentseries}}{0pt}%
4269 {\bgroup}%
4270 {\hbox to \csuse{Xboxendlinenum@ \@currentseries}\bgroup}%
4271 \ifl@d@Xtwolines%
4272 \ifl@d@Xlinenum%
4273 \ifl@d@Xmorethantwolines%
4274 \csuse{Xmorethantwolines@ \@currentseries}%
4275 \else%
4276 \csuse{Xtwolines@ \@currentseries}%
4277 \fi%
4278 \fi%
4279 \else%
4280 \ifl@d@dash%
4281 \ifdefined\linerrangesep%
4282 \linerrangesep%
4283 \else%
4284 \csuse{Xlinerrangeseparator@ \@currentseries}%
4285 \fi%
4286 \fi%
4287 \ifcsstring{Xlinenumannotationposition@ \@currentseries}{before}%
4288 {\@annot@end@print}%
4289 {}%
4290 \ifl@d@pnum%
4291 \wrap@edcrossref{\@this@crossref@end}{#4}%
4292 \csuse{Xpagelinesep@ \@currentseries}%
4293 \fi%
4294 \ifl@d@Xlinenum%
4295 \ifl@d@elin%
4296 \wrap@edcrossref{\@this@crossref@end}{%
4297 \linenumrep{#5}%
4298 \iftoggle{Xlineflag@ \@currentseries}{#8}{}%
4299 }%
4300 \fi%
4301 \ifl@d@esl%
4302 \ifl@d@elin%
4303 \csuse{Xsublinesep@ \@currentseries}%
4304 \fi%
4305 \wrap@edcrossref{\@this@crossref@end}{\sublinenumrep{#6}}%

```

```

4306     \fi%
4307     \fi%
4308     \ifcsstring{Xlinenumannotationposition@{@currentseries}{after}}%
4309         {\@annot@end@print}%
4310     }%
4311     \fi%
4312     \ifdimequal{\csuse{Xboxendlinenum@{@currentseries}}}{0pt}%
4313     {}%
4314     {\hfill}%Prevent underfull hbox
4315     \egroup%
4316     \endgroup%
4317 }%
4318 %

```

XIII.9.5 Footnote grouped by line

`\prepare@Xgroupbyline` `\prepare@Xgroupbyline` is a macro called on the `\metaXXXvfootnote` if `\Xgroupbyline` is set to true, instead of calling `\insert` directly. #1 The series
#2 The content of the footnote, which is also the line number indication
#3 This macro, which prepares the contents of the insertion

```

4319 \newcommand{\prepare@Xgroupbyline}[3]{%
4320     \iftoggle{Xgroupbylineseparatetwolines@#1}{%
4321         \l@dparsfootspec#2%
4322         \ifcsdef{#1@forinserting@{\l@dparsedendpage-\l@dparsedendline-\l@dparsedendsub}}%
4323             {%
4324                 \csgappto{#1@forinserting@{\l@dparsedendpage-\l@dparsedendline-\l@dparsedendsub}}{%
4325                     \hskip\csuse{Xafternote@#1}\relax%
4326                 }%
4327             }%
4328         }%
4329         \add@hooktoggle@specific@to@cs{#1@forinserting@{\l@dparsedendpage-\l@dparsedendline-\l@dparsedendsub}}%
4330         \add@hookarg@specific@to@cs{#1@forinserting@{\l@dparsedendpage-\l@dparsedendline-\l@dparsedendsub}}%
4331         \csxappto%
4332             {#1@forinserting@{\l@dparsedendpage-\l@dparsedendline-\l@dparsedendsub}}%
4333         {%
4334             \keep@this@crossref@forinserting%
4335             \unexpanded{%
4336                 \ifcseempty{Xsymlinenum@#1}%
4337                 {\csuse{Xparafootsep@#1}}%
4338                 {}%
4339                 #3{#1}{#2}%
4340             }%

```

```

4341 }%
4342 \listcsxadd{#1@forinserting}{\l@dparsedendpage-\l@dparsedendline-\
l@dparsedendsub}%
4343 }{%
4344 \ifcsdef{#1@forinserting@all}{%
4345 \csgappto%
4346 {#1@forinserting@all}%
4347 {\hskip\csuse{Xafternote@#1}\relax}%
4348 }{%
4349 \add@hooktoggle@specific@to@cs{#1@forinserting@all}%
4350 \add@hookarg@specific@to@cs{#1@forinserting@all}%
4351 \csxappto%
4352 {#1@forinserting@all}%
4353 {%
4354 \keep@this@crossref@forinserting%
4355 \unexpanded{%
4356 \ifcsemt{Xsymlinenum@#1}%
4357 {\csuse{Xparafootsep@#1}}%
4358 }%
4359 #3{#1}{#2}%
4360 }%
4361 }%
4362 }%
4363 \listcsgadd{#1@forinserting}{all}%
4364 }%
4365 %

```

`\keep@this@crossref@forinserting` `\keep@this@crossref@forinserting` is called by `\prepare@Xgroupbyline`. It just ensures that `\@this@crossref@start` and `\this@crossref@end` value are kept in memory.

```

4366 \newcommand{\keep@this@crossref@forinserting}{%
4367 \unexpanded{\gdef\@this@crossref@start}{\@this@crossref@start}%
4368 \unexpanded{\gdef\@this@crossref@end}{\@this@crossref@end}%
4369 }%
4370 %

```

XIV Familiar footnotes

XIV.1 Adjacent footnotes

The original edmac provided users with five series of critical footnotes (`\Afootnote` `\Bfootnote` `\Cfootnote` `\Dfootnote` `\Efootnote`), and \TeX provides a single numbered footnote. The `reledmac` package uses the edmac mechanism to provide six series of numbered footnotes.

First, though, the `footmisc` package has an option whereby two or more consecutive footnotes have their marks separated by commas. This seemed to Peter Wilson such a useful ability that it was provided automatically by `eledmac`.

Maïeul Rouquette has maintained this feature in `reledmac`, despite he thought that is not directly in relationship with the aim of `reledmac`.

`\multiplefootnotemarker` These macros may have been defined by the `memoir` class, are provided by the `footmisc` package and perhaps by other footnote packages. That is why we use `\providecommand` and not `\newcommand`.

```
4371 \providecommand*\multiplefootnotemarker{3sp}
4372 \providecommand*\multfootsep{\textsuperscript{\normalfont,}}
4373
4374 %
```

`\m@mmf@prepare` A pair of self-cancelling kerns. This may have been defined in the `memoir` class.

```
4375 \providecommand*\m@mmf@prepare{%
4376   \kern-\multiplefootnotemarker
4377   \kern\multiplefootnotemarker\relax}
4378 %
```

`\m@mmf@check` This may have been defined in the `memoir` class. If it recognises the last kern as `\multiplefootnotemarker` it typesets `\multfootsep`.

```
4379 \providecommand*\m@mmf@check{%
4380   \ifdim\lastkern=\multiplefootnotemarker\relax
4381     \edef\@x@sf{\the\spacefactor}%
4382     \unkern
4383     \multfootsep
4384     \spacefactor\@x@sf\relax
4385   \fi}
4386
4387 %
```

We have to modify `\@footnotetext` and `\@footnotemark`. However, if `memoir` is used the modifications have already been made.

```
4388 \@ifclassloaded{memoir}{\%
4389 %
```

`\@footnotetext` Add `\m@mmf@prepare` at the end of `\@footnotetext`.

```
4390 \apptocmd{\@footnotetext}{\m@mmf@prepare}{\%}{\%}
4391 %
```

`\@footnotemark` Modify `\@footnotemark` to cater for adjacent footnotes.

```
4392
4393 \patchcmd{\@footnotemark}
4394   {\nobreak}
4395   {\m@mmf@check
```

```

4396 \nobreak
4397 }
4398 {}{}
4399 \patchcmd{\@footnotemark}
4400 {\@makefnmark}
4401 {\@makefnmark
4402 \m@mmf@prepare
4403 }
4404 {}{}
4405 %

```

Finished the modifications for the non-memoir case.

```

4406 }
4407
4408 %

```

XIV.2 Regular footnotes for numbered texts

`\l@doldold@footnotetext` In order to enable the regular `\footnotes` in numbered text we have to play around
`\@footnotetext` with its `\@footnotetext`, using different forms for when in numbered or regular text.

```

4409 \pretocmd{\@footnotetext}{%
4410 \ifnumberedpar@
4411 \edtext{}\l@dbfnote{#1}}%
4412 \else
4413 {}{}
4414 \apptocmd{\@footnotetext}{\fi}{}{}%
4415 %

```

`\l@dbfnote` `\l@dbfnote` adds the footnote to the insert list, and `\vl@dbfnote` calls the original
`\vl@dbfnote` `\@footnotetext`. We also patch `\footnote` in order to get the correct footnote
`\vl@dbfnote` numbers when typesetting parallel texts. This is moved into a `\get@fnmark` command.
`\footnote`
`\get@fnmark`
`\get@thisfootnote`

```

4416 \patchcmd%
4417 {\footnote}%
4418 {\stepcounter\@mpfn}%
4419 {%
4420 \ifboolexpr{bool{l@dpairing} or bool{l@dprintingpages} or bool{
4421 l@dprintingcolumns}}{%
4422 \global\advance\footnote@reading by \@ne%
4423 \get@thisfootnote%
4424 \get@fnmark{\thisc@footnote}%
4425 \ifcsdef{footnotereading\the\footnote@reading=typeset}%
4426 {\setcounter{\@mpfn}{\csuse{footnotereading\the\footnote@reading=
typeset}}}%

```

```

4427     {\setcounter{\@mpfn}{\footnote@reading}}}%
4428   }{%
4429     \stepcounter{\@mpfn}%
4430   }%
4431 }%
4432 {}
4433 {}
4434
4435 \newcommand{\get@thisfootnote}{%
4436   \ifbool{pr{bool{l@dpairing} or bool{l@dprintingpages} or bool{
4437     l@dprintingcolumns}}}%
4438     \protected@xdef\thisc@footnote{\the\footnote@reading}%
4439   }{%
4440     \protected@xdef\thisc@footnote{\the\c@footnote}%
4441   }%
4442 }%
4443 \newcommand{\l@dbfnote}[1]{%
4444   \get@thisfootnote%
4445   \gdef\@tag{#1\relax}%
4446   \ifl@Rcol%
4447     \xright@appenditem{%
4448       \ifdefined\Hy@footnote@currentHref%
4449         \noexpand\def\noexpand\Hy@footnote@currentHref{\
4450           Hy@footnote@currentHref}%
4451       \fi%
4452       \noexpand\vl@dbfnote{\expandonce\@tag}\thisc@footnote}%
4453     }%
4454     \to\inserts@listR
4455     \global\advance\insert@countR \@ne%
4456   \else%
4457     \xright@appenditem{%
4458       \ifdefined\Hy@footnote@currentHref%
4459         \noexpand\def\noexpand\Hy@footnote@currentHref{\
4460           Hy@footnote@currentHref}%
4461       \fi%
4462       \noexpand\vl@dbfnote{\expandonce\@tag}\thisc@footnote}%
4463     }%
4464     \to\inserts@list
4465     \global\advance\insert@count \@ne%
4466   \fi
4467   \ignorespaces%
4468 }%
4469 \newcommand{\get@fnmark}[1]{%
4470   \ifbool{pr{bool{l@dpairing} or bool{l@dprintingpages} or bool{
4471     l@dprintingcolumns}}}%
4472     {%

```

```

4473 \immediate\write\@mainaux{%
4474 \csgdef{footnotereading#1=typeset}{\the\c@footnote@typeset}%
4475 }%
4476 \def\@thefnmark{\thefootnote}%
4477 }%
4478 {%
4479 \setcounter{footnote}{#1}%
4480 \def\@thefnmark{\thefootnote}%
4481 }%
4482 }%
4483
4484 \newcommand{\vl@dbfnote}[2]{%
4485 \get@fnmark{#2}%
4486 \@footnotetext{#1}%
4487 }%
4488 %

```

XIV.3 Footnote formats

Some of the code for the various formats is remarkably similar to that in section ??.

The following macros generally set things up for the “standard” footnote format.

`\prebodyfootmark` Two convenience macros for use by `\...@footnotemark...` macros.
`\postbodyfootmark`

```

4489 \newcommand*{\prebodyfootmark}{%
4490 \leavevmode
4491 \ifhmode
4492 \edef\x@sf{\the\spacefactor}%
4493 \m@mmf@check
4494 \nobreak
4495 \fi}
4496 \newcommand{\postbodyfootmark}{%
4497 \m@mmf@prepare
4498 \ifhmode\spacefactor\x@sf\fi\relax}
4499
4500 %

```

XIV.4 Footnote arrangement

XIV.4.1 User level macro

`\arrangementX` `\arrangementX[⟨s⟩]{⟨arrangement⟩}` command calls, for each series, a specific command which set many counters and commands in order to define specific arrangement.

```

4501 \newcommandx{\arrangementX}[2][1,usedefault]{%
4502 \def\do##1{%
4503 \csname arrangementX@#2\endcsname{##1}%
4504 }%
4505 \ifstrempy{#1}%

```



```

4506 {%
4507 \dolistloop{\@series}%
4508 }%
4509 {
4510 \docsvlist{#1}%
4511 }%
4512 }%
4513 %

```

XIV.4.2 Normal footnotes

`\normal@footnotemarkX` `\normal@footnotemarkX{<series>}` sets up the typesetting of the marker at the point where the footnote is called for.

```

4514 \newcommand*{\normal@footnotemarkX}[1]{%
4515 \prebodyfootmark
4516 \wrapped@bodyfootmarkX{#1}%
4517 \postbodyfootmark}
4518
4519 %

```

`\normalbodyfootmarkX` The `\normalbodyfootmarkX{<series>}` really typesets the in-text marker. The style is the normal superscript.

```

4520 \newcommand*{\normalbodyfootmarkX}[1]{%
4521 \hbox{\textsuperscript{\normalfont\@nameuse{@thefnmark#1}}}}
4522 %

```

`\normalvfootnoteX` `\normalvfootnoteX{<series>}{<text>}` does the `\insert` for the `<series>` and calls the series' `\footfmt...` to format the `<text>`.

```

4523 \notbool{parapparatus@}{\newcommand*{\newcommand}{\normalvfootnoteX}[2]{%
4524 \beforeinsertion@X{#1}%
4525 \insert\@nameuse{footins#1}\bgroup
4526 \fontseries{\seriesdefault}%
4527 \fontshape{\shapedefault}%
4528 \hspace=\expandafter\dimexpr\csuse{widthX@#1}\relax%
4529 \noindent\csuse{bhooknoteX@#1}%
4530 \csuse{notefontsizeX@#1}%
4531 \footsplitskips
4532 \ifl@dpairing\ifl@dpaging\else%
4533 \setnoteswidthliketwocolumnsX@{#1}%
4534 \fi\fi%
4535 \setnotesXpositionliketwocolumns@{#1}%
4536 \spaceskip=\z@skip \xspaceskip=\z@skip
4537 \csuse{\csuse{footnote@dir}}\@nameuse{footfmt#1}{#1}{#2}\egroup}
4538
4539 %

```

`\mpnormalvfootnoteX` The minipage version.

```

4540 \newcommand*{\mpnormalvfootnoteX}[3]{%
4541   \get@thisfootnoteX{#1}%
4542   \get@fnmarkX{#1}{\thisc@footnote}{#3}%
4543   \ifstrempy{#3}{%
4544     \edef\this@footnoteX@reading{\the\c@name footnote#1@reading\endc@name}%
4545   }{%
4546     \edef\this@footnoteX@reading{###3}%
4547   }%
4548   \global\setbox\@nameuse{mpfootins#1}\vbox{%
4549     \unvbox\@nameuse{mpfootins#1}
4550     \noindent\c@use{bhooknoteX@#1}%
4551     \c@use{notefontsizeX@#1}%
4552     \hsize\columnwidth
4553     \@parboxrestore
4554     \color@begingroup
4555     \@nameuse{footfmt#1}{#1}{#2}\color@endgroup}}
4556
4557 %

```

`\normalfootfmtX` `\normalfootfmtX{<series>}{<text>}` typesets the footnote text, prepended by the marker.

```

4558 \notbool{parapparatus@}{\newcommand*}{\newcommand*}{\normalfootfmtX}[2]{%
4559   \ifluatex%
4560     \texdir\footnote@luatextextdir%
4561     \pardir\footnote@luatexpardir%
4562   \fi%
4563   \protected@edef\@currentlabel{%
4564     \@nameuse{@thefnmark#1}%
4565   }%
4566   \ledsetnormalparstuffX{#1}%
4567   \sethangindentX{#1}%
4568   \rule{z@}{splittopskip}%
4569   {\c@use{notenunfontX@#1}\wrapped@footfootmarkX{#1}}%
4570   \c@use{wrapcontentX@#1}{#2}%
4571   \strut\par}}
4572
4573 %

```

`\normalfootfootmarkX` `\normalfootfootmarkX{<series>}` is called by `\normalfootfmtX` to typeset the footnote marker in the footer before the footnote text.

```

4574 \newcommand*{\normalfootfootmarkX}[1]{%
4575   \textsuperscript{\@nameuse{@thefnmark#1}}}
4576
4577 %

```

`\normalfootstartX` `\normalfootstartX{<series>}` is the `<series>` footnote starting macro used in the output routine.

```

4578 \newcommand*{\normalfootstartX}[1]{%
4579   \ifdimequal{Opt}{\prenotesX@}{}%
4580   {%
4581     \iftoggle{prenotesX@}{%
4582       \togglefalse{prenotesX@}%
4583       \skip\csname footins#1\endcsname=%
4584       \glueexpr\csuse{prenotesX@}+\csuse{afterruleX@#1}\relax%
4585     }%
4586   }%
4587 }%
4588 \vskip\skip\csname footins#1\endcsname%
4589 \leftskip=\z@
4590 \rightskip=\z@
4591 \ifl@dpairing\else%
4592   \hsize=\old@hsize%
4593 \fi%
4594 \setnoteswidthliketwocolumnsX@{#1}%
4595 \setnotesXpositionliketwocolumns@{#1}%
4596 \print@footnoterule{#1}%
4597 }%
4598
4599 %

```

\normalfootnoteruleX The rule drawn before the footnote series group.

```

4600 \let\normalfootnoteruleX=\footnoterule
4601
4602 %

```

\normalfootgroupX `\normalfootgroupX{<series>}` sends the contents of the `<series>` insert box to the output page without alteration.

```

4603 \newcommand*{\normalfootgroupX}[1]{%
4604   \csuse{bhookgroupX@#1}%
4605   \unvbox\@nameuse{footins#1}%
4606   \hsize=\old@hsize%
4607 }%
4608
4609 %

```

\mpnormalfootgroupX The minipage version.

```

4610 \newcommand*{\mpnormalfootgroupX}[1]{%
4611   \vskip\skip\@nameuse{mpfootins#1}
4612   \ifl@dpairing\ifparledgroup%
4613     \leavevmode\marks\parledgroup@{begin}%
4614     \marks\parledgroup@series{#1}%
4615     \marks\parledgroup@type{footnoteX}%
4616   \fi\fi\normalcolor
4617   \ifparledgroup%

```

```

4618 \ifl@dpairing%
4619 \else%
4620 \setnoteswidthliketwocolumnsX@{#1}%
4621 \setnotesXpositionliketwocolumns@{#1}%
4622 \print@footnoteXrule{#1}%
4623 \fi%
4624 \else%
4625 \setnoteswidthliketwocolumnsX@{#1}%
4626 \setnotesXpositionliketwocolumns@{#1}%
4627 \print@footnoteXrule{#1}%
4628 \fi%
4629 \csuse{bhookgroupX@#1}%
4630 \unvbox\@nameuse{mpfootins#1}}
4631
4632 %

```

\normalbfnoteX #1 = footnote series, #2 = footnote content, #3 manual footnote number

```

4633
4634 \newcommand{\normalbfnoteX}[3]{%
4635 \get@thisfootnoteX{#1}%
4636 \ifledRcol%
4637 \ifluatex
4638 \footnotelang@lua[R]%
4639 \fi
4640 \@ifundefined{xpg@main@language}%if polyglossia
4641 {}%
4642 {\footnotelang@poly[R]}%
4643 \xright@appenditem{%
4644 \noexpand\led@set@index@fornote{#1}%
4645 \noexpand\prepare@edindex@fornote{\led@nums}%
4646 \unexpanded{\gdef\@currentnotetype{familiar}}%
4647 \unexpanded{\def\this@footnoteX@reading{\the\csname footnote#1
@reading\endcsname}%
4648 \noexpand\vbfnoteX{#1}{#2}{\thisc@footnote}{#3}%
4649 \noexpand\led@reinit@index@fornote%
4650 \unexpanded{\advance\@edindex@fornote@m@ne}%
4651 }%
4652 \to\inserts@listR
4653 \global\advance\insert@countR \@ne%
4654 \else%
4655 \ifluatex
4656 \footnotelang@lua%
4657 \fi
4658 \@ifundefined{xpg@main@language}%if polyglossia
4659 {}%
4660 {\footnotelang@poly}%
4661 \xright@appenditem{%
4662 \noexpand\led@set@index@fornote{#1}%
4663 \noexpand\prepare@edindex@fornote{\led@nums}%

```

```

4664 \unexpanded{\gdef\@currentnotetype{familiar}}}%
4665 \unexpanded{\def\this@footnoteX@reading{\the\csname footnote#1
@reading\endcsname}%
4666 \noexpand\vbfnoteX{#1}{#2}{\thisc@footnote}{#3}%
4667 \noexpand\led@reinit@index@fornote%
4668 \unexpanded{\advance\@edindex@fornote@m@ne}%
4669 }%
4670 \to\inserts@list
4671 \global\advance\insert@count \@ne%
4672 \fi
4673 \ignorespaces}
4674
4675 %

```

\get@thisfootnoteX The macro `\get@thisfootnote` command just saves the footnote number in the `\thisfootnote` macro, depending on the use of pairing environments.

```

4676 \newcommand{\get@thisfootnoteX}[1]{%
4677 \ifboolexpr{bool{l@dpairing} or bool{l@dprintingpages} or bool{
l@dprintingcolumns}}{%
4678 \protected@xdef\thisc@footnote{\the\csname footnote#1@reading\
endcsname}%
4679 }{%
4680 \protected@xdef\thisc@footnote{\the\csname c@footnote#1\endcsname}%
4681 }%
4682 }%
4683 %

```

\vbfnoteX This command calls the correct footnote-inserting commands. #1 footnote series, #2 footnote content, #3 footnote counter, #4 manual footnote mark

```

4684 \newcommand{\vbfnoteX}[4]{%
4685 \get@fnmarkX{#1}{#3}{#4}\relax%
4686 \@nameuse{regvfootnote#1}{#1}{#2}%
4687 }%
4688 %

```

\get@fnmarkX This command gets the correct footnote number when typesetting parallel texts. #1 footnote series, #2 footnote counter, #3 manual footnote number

```

4689 \newcommand{\get@fnmarkX}[3]{%
4690 \ifstrempy{#3}{%
4691 \ifboolexpr{bool{l@dpairing} or bool{l@dprintingpages} or bool{
l@dprintingcolumns}}{%
4692 {%
4693 \stepcounter{footnote#1@typeset}%
4694 \setcounter{footnote#1}{\value{footnote#1@typeset}}%
4695 \@namedef{@thefnmark#1}{\csuse{thefootnote#1}}%
4696 \immediate\write\@mainaux{%

```

```

4697 \csgdef{footnote#1reading#2=typeset}{\the\csname c@footnote#1
@typeset\endcsname}%
4698 }%
4699 }%
4700 {%
4701 \setcounter{footnote#1}{#2}%
4702 \namedef{@thefnmark#1}{\csuse{thefootnote#1}}%
4703 }%
4704 }%
4705 {%
4706 \csdef{@thefnmark#1}{#3}%
4707 }%
4708 }%
4709 %
4710 %

```

\vnumfootnoteX #1 footnote series, #2 footnote content, #3 manual footnote mark

```

4711 \newcommand{\vnumfootnoteX}[3]{%
4712 \ifnumberedpar@
4713 \edtext{}{\normalbfnoteX{#1}{#2}{#3}}%
4714 \else
4715 \def\this@footnoteX@reading{\the\csname footnote#1@reading\endcsname}%
4716 \get@thisfootnoteX{#1}%
4717 \get@fnmarkX{#1}{\expandonce\thisc@footnote}{#3}%
4718 \@nameuse{regvfootnote#1}{#1}{#2}%
4719 \fi}
4720 %
4721 %

```

arrangementX@normal \arrangementX@normal{<series>} initialises the settings for the <series> footnotes. This should always be called for each series.

```

4722 \newcommand*{\arrangementX@normal}[1]{%
4723 \csgdef{series@displayX#1}{normal}
4724 \expandafter\let\csname footstart#1\endcsname=\normalfootstartX
4725 \@namedef{@footnotemark#1}{\normal@footnotemarkX{#1}}
4726 \@namedef{bodyfootmark#1}{\normalbodyfootmarkX{#1}}
4727 \expandafter\let\csname regvfootnote#1\endcsname=\normalvfootnoteX
4728 \expandafter\let\csname vfootnote#1\endcsname=\vnumfootnoteX
4729 \expandafter\let\csname footfmt#1\endcsname=\normalfootfmtX
4730 \@namedef{footfootmark#1}{\normalfootfootmarkX{#1}}
4731 \expandafter\let\csname footgroup#1\endcsname=\normalfootgroupX
4732 \expandafter\let\csname footnoterule#1\endcsname=\normalfootnoteruleX
4733 \count\csname footins#1\endcsname=1000
4734 \csxdef{default@footins#1}{1000}%Use to have note only for one side
4735 \dimen\csname footins#1\endcsname=\csuse{maxhnotesX@#1}
4736 \skip\csname footins#1\endcsname=\csuse{beforenotesX@#1}%
4737 \advance\skip\csname footins#1\endcsname by\csuse{afterruleX@#1}%
4738 %

```

Additions for minipages.

```

4739 \ifnoledgroup@else%
4740 \expandafter\let\csname mpvfootnote#1\endcsname=\mpnormalvfootnoteX
4741 \expandafter\let\csname mpfootgroup#1\endcsname=\mpnormalfootgroupX
4742 \count\csname mpfootins#1\endcsname=1000
4743 \dimen\csname mpfootins#1\endcsname=\csuse{maxhnotesX@#1}
4744 \skip\csname mpfootins#1\endcsname=\csuse{beforenotesX@#1}%
4745 \advance\skip\csname mpfootins#1\endcsname by\csuse{afterruleX@#1}%
4746 \fi
4747 }
4748
4749 %

```

XIV.4.3 Two columns footnotes

The following macros set footnotes in two columns. It is assumed that the length of each footnote is less than the column width.

```

\arrangementX@twocol 50 \newcommand*\arrangementX@twocol}[1]{%
4751 \csgdef{series@displayX#1}{twocol}
4752 \expandafter\let\csname regvfootnote#1\endcsname=\twocolvfootnoteX
4753 \expandafter\let\csname footfmt#1\endcsname=\twocolfootfmtX
4754 \expandafter\let\csname footgroup#1\endcsname=\twocolfootgroupX
4755 \dimen\csname footins#1\endcsname=\csuse{maxhnotesX@#1}%
4756 \skip\csname footins#1\endcsname=\csuse{beforenotesX@#1}%
4757 \advance\skip\csname footins#1\endcsname by \csuse{afterruleX@#1}\relax%
4758 \twocolfootsetupX{#1}
4759 \ifnoledgroup@else%
4760 \expandafter\let\csname mpvfootnote#1\endcsname=\mpnormalvfootnoteX
4761 \expandafter\let\csname mpfootgroup#1\endcsname=\mptwocolfootgroupX
4762 \skip\csname mpfootins#1\endcsname=\csuse{beforenotesX@#1}%
4763 \advance\skip\csname mpfootins#1\endcsname by\csuse{afterruleX@#1}
4764 \mptwocolfootsetupX{#1}
4765 \fi%
4766 }
4767
4768 %

```

```

\twocolfootsetupX \twocolfootsetupX{<series>}
\mptwocolfootsetupX
4769 \newcommand*\twocolfootsetupX}[1]{%
4770 \count\csname footins#1\endcsname 500
4771 \csxdef{default@footins#1}{500}%Use this to confine the notes to one
side only
4772 \multiply\dimen\csname footins#1\endcsname by \tw@}
4773 \newcommand*\mptwocolfootsetupX}[1]{%
4774 \count\csname mpfootins#1\endcsname 500
4775 \multiply\dimen\csname mpfootins#1\endcsname by \tw@}

```

```

4776
4777 %

\twocolvfootnoteX \twocolvfootnoteX{<series>}

4778 \notbool{parapparatus@}{\newcommand*}{\newcommand}{\twocolvfootnoteX}[2]{%
4779 \beforeinsertion@X{#1}%
4780 \let\bid@RTL@everypar\relax%
4781 \insert\csname footins#1\endcsname\bgroup%
4782 \hsize=\expandafter\dimexpr\csuse{widthX@#1}\relax%
4783 \noindent\csuse{bhooknoteX@#1}%
4784 \csuse{notefontsizeX@#1}%
4785 \footsplittopskip%
4786 \spaceskip=\z@skip \xspaceskip=\z@skip%
4787 \@nameuse{footfmt#1}{#1}{#2}\egroup}
4788
4789 %

```

```

\twocolfootfmtX \twocolfootfmtX{<series>}

4790 \notbool{parapparatus@}{\newcommand*}{\newcommand}{\twocolfootfmtX}[2]{%
4791 \protected@edef\@currentlabel{%
4792 \@nameuse{@thefnmark#1}%
4793 }%
4794 \normal@pars%
4795 \sethangindentX{#1}%
4796 \hsize \csuse{hsizetwocolX@#1}%
4797 \setparindentX{#1}%
4798 \tolerance=5000\relax%
4799 \par%
4800 \@tempdima=\parindent%
4801 \csuse{colalignX@#1}%
4802 \parindent=\@tempdima%
4803 {\hspace{\parindent}%
4804 \csuse{notenumfontX@#1}\wrapped@footfootmarkX{#1}\strut%
4805 \csuse{wrapcontentX@#1}{#2}%
4806 \strut\par}%
4807 \allowbreak%
4808 }%
4809
4810 %

```

```

\twocolfootgroupX \twocolfootgroupX{<series>}
\mptwocolfootgroupX
4811 \newcommand*{\twocolfootgroupX}[1]{\csuse{bhookgroupX@#1}\csuse{
notefontsizeX@#1}
4812 \splittopskip=\ht\strutbox
4813 \expandafter
4814 \rigidbalanceX\csname footins#1\endcsname \tw@ \splittopskip}}
4815

```



```

4816 \newcommand*{\mptwocolfootgroupX}[1]{%
4817   \vskip\skip\@nameuse{mpfootins#1}
4818   \ifl@dpairing\ifparledgroup%
4819     \leavevmode\marks\parledgroup@{begin}%
4820     \marks\parledgroup@series{#1}%
4821     \marks\parledgroup@type{footnoteX}%
4822   \fi\fi\normalcolor
4823   \ifparledgroup%
4824     \ifl@dpairing%
4825     \else%
4826       \setnoteswidthliketwocolumnsX@{#1}%
4827       \setnotesXpositionliketwocolumns@{#1}%
4828       \print@footnoteXrule{#1}%
4829     \fi%
4830   \else%
4831     \setnoteswidthliketwocolumnsX@{#1}%
4832     \setnotesXpositionliketwocolumns@{#1}%
4833     \print@footnoteXrule{#1}%
4834   \fi%
4835   \csuse{bhookgroupX@#1}%
4836   \splittopskip=\ht\strutbox
4837   \expandafter
4838   \rigidbalanceX\csname mpfootins#1\endcsname \tw@ \splittopskip}}
4839
4840 %

```

XIV.4.4 Three columns footnotes

The following macros set footnotes in three columns. It is assumed that the length of each footnote is less than the column width.

```

\arrangementX@threecol 4841 \newcommand*{\arrangementX@threecol}[1]{%
4842   \csgdef{series@displayX#1}{threecol}
4843   \expandafter\let\csname regvfootnote#1\endcsname=\threecolvfootnoteX
4844   \expandafter\let\csname footfmt#1\endcsname=\threecolfootfmtX
4845   \expandafter\let\csname footgroup#1\endcsname=\threecolfootgroupX
4846   \dimen\csname footins#1\endcsname=\csuse{maxhnotesX@#1}%
4847   \skip\csname footins#1\endcsname=\csuse{beforenotesX@#1}%
4848   \advance\skip\csname footins#1\endcsname by \csuse{afterruleX@#1}\relax%
4849   \threecolfootsetupX{#1}
4850   \ifnoledgroup\else%
4851     \expandafter\let\csname mpvfootnote#1\endcsname=\mpnormalvfootnoteX
4852     \expandafter\let\csname mpfootgroup#1\endcsname=\mpthreecolfootgroupX
4853     \skip\csname mpfootins#1\endcsname=\csuse{beforenotesX@#1}%
4854     \advance\skip\csname mpfootins#1\endcsname by \csuse{afterruleX@#1}
4855     \mpthreecolfootsetupX{#1}
4856   \fi%
4857 }
4858

```

```

4859 %

\threecolfootsetupX \threecolfootsetupX{<series>}
\mpthreecolfootsetupX
4860 \newcommand*{\threecolfootsetupX}[1]{%
4861   \count\csname footins#1\endcsname 333
4862   \csxdef{default@footins#1}{333}%Use this to confine the notes to one
side only
4863   \multiply\dimen\csname footins#1\endcsname by \thr@@
4864   \newcommand*{\mpthreecolfootsetupX}[1]{%
4865     \count\csname mpfootins#1\endcsname 333
4866     \multiply\dimen\csname mpfootins#1\endcsname by \thr@@
4867
4868 %

\threecolvfootnoteX \threecolvfootnoteX{<series>}{<text>}

4869 \notbool{parapparatus@}{\newcommand*}{\newcommand}{\threecolvfootnoteX}[2]{
%
4870   \let\bidir@RTL@everypar\relax%
4871   \beforeinsertion@X{#1}%
4872   \insert\csname footins#1\endcsname\bgroup%
4873     \hsize=\expandafter\dimexpr\csuse{widthX@#1}\relax%
4874     \noindent\csuse{hooknoteX@#1}%
4875     \csuse{notefontsizeX@#1}%
4876     \footplitskips%
4877     \@nameuse{footfmt#1}{#1}{#2}\egroup
4878
4879 %

\threecolfootfmtX \threecolfootfmtX{<series>}

4880 \notbool{parapparatus@}{\newcommand*}{\newcommand}{\threecolfootfmtX}[2]{%
4881   \protected@edef\@currentlabel{%
4882     \@nameuse{thefnmark#1}%
4883   }%
4884   \sethangindentX{#1}%
4885   \normal@pars%
4886   \hsize \csuse{hsizethreecolX@#1}%
4887   \setparindentX{#1}%
4888   \tolerance=5000\relax%
4889   \@tempdima=\parindent%
4890   \csuse{colalignX@#1}%
4891   \parindent=\@tempdima%
4892   {\hspace{\parindent}%
4893     \csuse{notenumfontX@#1}\wrapped@footfootmarkX{#1}\strut%
4894     \csuse{wrapcontentX@#1}{#2}%
4895     \strut\par}\allowbreak
4896
4897 %

```

```

\threecolfootgroupX \threecolfootgroupX{<series>}
\mpthreecolfootgroupX
4898 \newcommand*{\threecolfootgroupX}[1]{\csuse{bhookgroupX@#1}\csuse{
notefontsizeX@#1}
4899 \splittopskip=\ht\strutbox
4900 \expandafter
4901 \rigidbalanceX\csname footins#1\endcsname \thr@@ \splittopskip}}
4902
4903 \newcommand*{\mpthreecolfootgroupX}[1]{\%
4904 \vskip\skip\@nameuse{mpfootins#1}
4905 \ifl@dpairing\ifparledgroup
4906 \leavevmode\marks\parledgroup@{begin}%
4907 \marks\parledgroup@series{#1}%
4908 \marks\parledgroup@type{footnoteX}%
4909 \fi\fi\normalcolor
4910 \ifparledgroup%
4911 \ifl@dpairing%
4912 \else%
4913 \setnoteswidthliketwocolumnsX@{#1}%
4914 \setnotesXpositionliketwocolumns@{#1}%
4915 \print@footnoteXrule{#1}%
4916 \fi%
4917 \else%
4918 \setnoteswidthliketwocolumnsX@{#1}%
4919 \setnotesXpositionliketwocolumns@{#1}%
4920 \print@footnoteXrule{#1}%
4921 \fi%
4922 \csuse{bhookgroupX@#1}%
4923 \splittopskip=\ht\strutbox
4924 \expandafter
4925 \rigidbalanceX\csname mpfootins#1\endcsname \thr@@ \splittopskip}}
4926
4927 \%

```

XIV.4.5 Paragraphed footnotes

The following macros set footnotes as one paragraph.

```

\arrangementX@paragraph \footparagraphX{<series>}
4928 \newcommand*{\arrangementX@paragraph}[1]{\%
4929 \csgdef{series@displayX#1}{paragraph}%
4930 \expandafter\let\csname footstart#1\endcsname=\parafootstartX
4931 \expandafter\let\csname regvfootnote#1\endcsname=\para@vfootnoteX
4932 \expandafter\let\csname footfmt#1\endcsname=\parafootfmtX
4933 \expandafter\let\csname footgroup#1\endcsname=\para@footgroupX
4934 \expandafter\let\csname footnoterule#1\endcsname=\normalfootnoteruleX
4935 \count\csname footins#1\endcsname=1000
4936 \csxdef{default@footins#1}{1000}%Use this to confine the notes to one
side only

```

```

4937 \dimen\csname footins#1\endcsname=\csuse{maxhnotesX@#1}
4938 \skip\csname footins#1\endcsname=\csuse{beforenotesX@#1}%
4939 \advance\skip\csname footins#1\endcsname by\csuse{afterruleX@#1}%
4940 \para@footsetupX{#1}
4941 \ifnoledgroup@else
4942   \expandafter\let\csname mpvfootnote#1\endcsname=\mppara@vfootnoteX
4943   \expandafter\let\csname mpfootgroup#1\endcsname=\mppara@footgroupX
4944   \count\csname mpfootins#1\endcsname=1000
4945   \dimen\csname mpfootins#1\endcsname=\csuse{maxhnotesX@#1}
4946   \skip\csname mpfootins#1\endcsname=\csuse{beforenotesX@#1}%
4947   \advance\skip\csname mpfootins#1\endcsname by\csuse{afterruleX@#1}%
4948 \fi
4949 }
4950
4951 %

```

`\para@footsetupX` `\para@footsetupX{<series>}`

```

4952 \newcommand*{\para@footsetupX}[1]{\csuse{bhookgroupX@#1}\csuse{
notefontsizeX@#1}
4953 \setnoteswidthliketwocolumnsX@{#1}%
4954 \ifcsempy{widthX@#1}%
4955   {}%
4956   {\columnwidth=\expandafter\dimexpr\csuse{widthX@#1}\relax}%
4957 \dimen0=\baselineskip
4958 \multiply\dimen0 by 1024
4959 \divide\dimen0 by \columnwidth \multiply\dimen0 by \footfudgefiddle\relax
4960 %
4961 \expandafter
4962 \xdef\csname footfudgefactor#1\endcsname{%
\expandafter\strip@pt\dimen0 }}
4963
4964 %

```

`\parafootstartX` `\parafootstartX{<series>}`

```

4965 \newcommand*{\parafootstartX}[1]{%
4966   \ifdimequal{Opt}{\prenotesX@}{}%
4967   {%
4968     \iftoggle{prenotesX@}{%
4969       \togglefalse{prenotesX@}%
4970       \skip\csname footins#1\endcsname=%
4971       \glueexpr\csuse{prenotesX@}+\csuse{afterruleX@#1}\relax%
4972     }%
4973   }%
4974 }%
4975 \leftskip=\z@
4976 \rightskip=\z@
4977 \setparindentX{#1}%
4978 \vskip\skip\@nameuse{footins#1}%

```

```

4979 \setnoteswidthliketwocolumnsX@{#1}%
4980 \setnotesXpositionliketwocolumns@{#1}%
4981 \print@footnoteXrule{#1}%
4982 }
4983
4984 %

```

`\para@vfootnoteX` `\para@vfootnoteX{<series>}{<text>}`

`\mppara@vfootnoteX`

```

4985 \newcommand*{\para@vfootnoteX}[2]{%
4986 \csuse{beforeinsertingX@#1}%
4987 \insert\csname footins#1\endcsname%
4988 \bgroup
4989 \csuse{notefontsizeX@#1}
4990 \footsplitskips
4991 \setbox0=\vbox{\hsize=\maxdimen%
4992 \let\bid@RTL@everypar\@empty%
4993 \insert@txtbeforenotesX{#1}%
4994 \noindent\csuse{bhooknoteX@#1}%
4995 \@nameuse{footfmt#1}{#1}{#2}}%
4996 \setbox0=\hbox{\unvxhX{0}{#1}}%
4997 \dp0=\z@
4998 \ht0=\csname footfudgefactor#1\endcsname\wd0
4999 \box0
5000 \penalty0
5001 \egroup}
5002 \newcommand*{\mppara@vfootnoteX}[3]{%
5003 \get@thisfootnoteX{#1}%
5004 \get@fnmarkX{#1}{\thisc@footnote}{#3}%
5005 \edef\this@footnoteX@reading{\the\csname footnote#1@reading\endcsname}%
5006 \global\setbox\@nameuse{mpfootins#1}\vbox{%
5007 \unvbox\@nameuse{mpfootins#1}
5008 \csuse{notefontsizeX@#1}
5009 \footsplitskips
5010 \setbox0=\vbox{\hsize=\maxdimen%
5011 \let\bid@RTL@everypar\@empty%
5012 \noindent\color@begingroup%
5013 \csuse{bhooknoteX@#1}%
5014 \@nameuse{footfmt#1}{#1}{#2}\color@endgroup}%
5015 \setbox0=\hbox{\unvxhX{0}{#1}}%
5016 \dp0=\z@
5017 \ht0=\csname footfudgefactor#1\endcsname\wd0
5018 \box0
5019 \penalty0}}
5020
5021 %

```

`\unvxhX` `\newcommand*{\unvxhX}[2]{% 2th is optional for retro-compatibility`

```

5023 \setbox0=\vbox{\unvbox#1%

```

```

5024 \global\setbox1=\lastbox}%
5025 \unhbox1
5026 \unskip           % remove \rightskip,
5027 \unskip           % remove \parfillskip,
5028 \unpenalty        % remove \penalty of 10000,
5029 \hskip\csuse{afternoteX@#2}%
5030 \relax}% but add the glue to go between the notes
5031
5032 %

```

`\parafootfmtX` `\parafootfmtX{<series>}`

```

5033 \newcommand*{\parafootfmtX}[2]{%
5034   \protected@edef\@currentlabel{%
5035     \@nameuse{@thefnmark#1}%
5036   }%
5037   \insertparafootsepX{#1}%
5038   \ledsetnormalparstuff@common%
5039   {\csuse{notenumfontX@#1}%
5040    \csuse{notenumfontX@#1}%
5041    \wrapped@footfootmarkX{#1}%
5042    \strut%
5043    \csuse{wrapcontentX@#1}{#2}%
5044    \penalty-10}}
5045
5046 %

```

`\para@footgroupX` `\para@footgroupX{<series>}`
`\mppara@footgroupX`

```

5047 \newcommand*{\para@footgroupX}[1]{%
5048   \hsize=\expandafter\dimexpr\csuse{widthX@#1}\relax%
5049   \unvbox\csname footins#1\endcsname
5050   \ifcsstring{raggedX@#1}{L}{\RaggedLeft}{}%
5051   \ifcsstring{raggedX@#1}{R}{\RaggedRight}{}%
5052   \makehboxofhboxes
5053   \setbox0=\hbox{\unhbox0 \removehboxes}%
5054   \csuse{bhookgroupX@#1}
5055   \csuse{notefontsizeX@#1}
5056   \unhbox0\par}
5057
5058 \newcommand*{\mppara@footgroupX}[1]{%
5059   \setnoteswidthliketwocolumnsX@{#1}%
5060   \vskip\skip\@nameuse{mpfootins#1}
5061   \ifl@dpairing\ifparledgroup
5062     \leavevmode%
5063     \leavevmode\marks\parledgroup@{begin}%
5064     \marks\parledgroup@series{#1}%
5065     \marks\parledgroup@type{footnoteX}%
5066     \fi\fi\normalcolor
5067     \ifparledgroup%

```

```

5068 \ifl@dpairing%
5069 \else%
5070 \setnoteswidthliketwocolumnsX@{#1}%
5071 \setnotesXpositionliketwocolumns@{#1}%
5072 \print@footnoteXrule{#1}%
5073 \fi%
5074 \else%
5075 \setnoteswidthliketwocolumnsX@{#1}%
5076 \setnotesXpositionliketwocolumns@{#1}%
5077 \print@footnoteXrule{#1}%
5078 \fi%
5079 \unvbox\csname mpfootins#1\endcsname
5080 \ifcsstring{raggedX@#1}{L}{\RaggedLeft}{}%
5081 \ifcsstring{raggedX@#1}{R}{\RaggedRight}{}%
5082 \makehboxofhboxes
5083 \setbox0=\hbox{\unhbox0 \removehboxes}%
5084 \csuse{bhookgroupX@#1}%
5085 \csuse{notefontsizeX@#1}%
5086 \setparindentX{#1}%
5087 \unhbox0\par}}
5088
5089 %

```

Insertion of the footnotes separator The command `\insertparafootsepX{<series>}` must be called at the beginning of `\parafootftmX`.

```

\insertparafootsepX%0 \newcommand{\insertparafootsepX}[1]{%
5091 \ifl@Rcol@%
5092 \ifnumequal{\csuse{prevpage#1@numR}}{\page@numR}%
5093 {\csuse{parafootsepX@#1}}%
5094 {}%
5095 \global\csname prevpage#1@numR\endcsname=\page@numR%
5096 \else%
5097 \ifnumbering%
5098 \ifnumequal{\csuse{prevpage#1@num}}{\page@num}%
5099 {\csuse{parafootsepX@#1}}%
5100 {}%
5101 \global\csname prevpage#1@num\endcsname=\page@num%
5102 \else%We can't use directly the page counter, see https://tex.
stackexchange.com/a/239457/7712
5103 \global\expandafter\advance\csname footnote#1@parafootsepX\endcsname
by 1%
5104 \edef\@tmpa{parafootsepX@#1@the\csname footnote#1@parafootsepX\
endcsname}%
5105 \expandafter\edlabel\expandafter{\@tmpa}%
5106 \edef\@tmpb{\expandafter\xpagerref\expandafter{\@tmpa}}%
5107 \IfStrEq{\csuse{prevpage#1@num@outnumbering}}{\@tmpb}%
5108 {\csuse{parafootsepX@#1}}%
5109 {}%

```

```

5110 \global\cslet{prevpage#1@num@outnumbering}{\@tmpb}%
5111 \fi%
5112 \fi%
5113 }
5114 %

```

XIV.5 Wrapping footnote marks in hyperlink

`\wrapped@footfootmarkX` `\wrapped@footfootmarkX` prints the footnote mark of the footpage, wrapped in `hyperref` package's commands, if needed.

```

5115 \newcommand{\wrapped@footfootmarkX}[1]{%
5116 \ifdefined\hypertarget%
5117 \hyperlink%
5118   {@bodyfootmark#1@\this@footnoteX@reading}%
5119   {@nameuse{footfootmark#1}}%
5120 \Hy@raisedlink{%
5121 \hypertarget%
5122   {@footnotemark#1@\this@footnoteX@reading}%
5123   {}}%
5124 }%
5125 \else%
5126 \@nameuse{footfootmark#1}%
5127 \fi%
5128 }%
5129 %

```

`\wrapped@bodyfootmarkX` `\wrapped@bodyfootmarkX` prints the footnote mark of the text body, wrapped in `hyperref` package's commands, if needed.

```

5130 \newcommand{\wrapped@bodyfootmarkX}[1]{%
5131 \ifdefined\hypertarget%
5132 \hyperlink%
5133   {@footnotemark#1@\expandafter\the\csname footnote#1@reading\
5134   endcsname}%
5135   {@nameuse{bodyfootmark#1}}%
5136 \Hy@raisedlink{%
5137 \hypertarget%
5138   {@bodyfootmark#1@\expandafter\the\csname footnote#1@reading\
5139   endcsname}%
5140   {}}%
5141 }%
5142 \else%
5143 \@nameuse{bodyfootmark#1}%
5144 \fi%
5145 }%
5146 %

```


XV Code common to both critical and familiar footnote in normal arrangement

`\par` should always be redefined to `\endgraf` within the format macro (this is what `\normal@pars` does), to override tricky material in the main text to get the lines numbered automatically (as set up by `\autopar`, for example).

In the case of footnote arranged in a “normal” way, we also must set some setting for paragraph indent and text direction when using Lua \TeX .

That why we have defined `\ledsetnormalparstuff@common` in order to make this setting for both familiar and critical notes. This command is called by command to make specific setting to critical or familiar footnote.

```

\ledsetnormalparstuff@common 45 \newcommand*{\ledsetnormalparstuff@common}{%
\Xledsetnormalparstuff 46 \ifluatex%
\ledsetnormalparstuffX 47 \ifdefstring{\footnote@luatextextdir}{TLT}{}%
5148 {\textdir\footnote@luatextextdir}%
5149 \pardir\footnote@luatexpardir%
5150 \fi%
5151 \csuse{\csuse{footnote@dir}}%
5152 \normal@pars%
5153 \parfillskip \z@ \@plus 1fil}%
5154
5155 \newcommand*{\Xledsetnormalparstuff}[1]{%
5156 \ledsetnormalparstuff@common%
5157 \Xsetparindent{#1}%
5158 \iftoggle{Xparindent@#1}{\hspace{\parindent}}{}%
5159 }%
5160
5161 \newcommand*{\ledsetnormalparstuffX}[1]{%
5162 \ledsetnormalparstuff@common%
5163 \setparindentX{#1}%
5164 \iftoggle{parindentX@#1}{\hspace{\parindent}}{}%
5165 }%
5166 %

```

XVI Footnotes’ width for two columns

We define here some commands which make sense only with `reledpar`, but must be called when defining notes parameters. These commands change the width of block notes to allow them to have the same size than two parallel columns.

`\old@hsize` These two commands are called at the beginning of critical or familiar notes groups. They set, if the option is enabled, the `\hsize`. They are also called at the on the setup for paragraphed notes.

```

5167
5168 \newdimen\old@hsize%

```

```

5169 \AtBeginDocument{\old@hsize=\hsize}%
5170
5171 \newcommand{\setXnoteswidthliketwocolumns@}[1]{%
5172   \global\let\hsize@fornote=\hsize%
5173   \global\old@hsize=\hsize%
5174   \let\old@columnwidth=\columnwidth%
5175   \iftoggle{Xnoteswidthliketwocolumns@#1}%
5176     {%
5177       \setwidthliketwocolumns%
5178       \global\let\hsize@fornote=\hsize%
5179     }%
5180     {}%
5181   \let\hsize=\hsize@fornote%
5182   \let\columnwidth=\old@columnwidth%
5183 }%
5184
5185 \newcommand{\setnoteswidthliketwocolumnsX@}[1]{%
5186   \global\let\hsize@fornote=\hsize%
5187   \global\old@hsize=\hsize%
5188   \let\old@columnwidth=\columnwidth%
5189   \iftoggle{noteswidthliketwocolumnsX@#1}%
5190     {%
5191       \setwidthliketwocolumns%
5192       \global\let\hsize@fornote=\hsize%
5193     }%
5194     {}%
5195   \let\hsize=\hsize@fornote%
5196   \let\columnwidth=\old@columnwidth%
5197 }%
5198
5199 %

```

`\setXnotespositionliketwocolumns@`
`\setnotesXpositionliketwocolumns@`

These two commands set the position of the critical / familiar footnotes, depending on the hooks `Xnoteswidthliketwocolumns` and `noteswidthliketwocolumnsX`. They call commands which are defined only in `reledpar`, because this feature has no sense without `reledpar`.

```

5200 \newcommand{\setXnotespositionliketwocolumns@}[1]{%
5201   \iftoggle{Xnoteswidthliketwocolumns@#1}{%
5202     \csuse{setnotespositionliketwocolumns@\columns@position}%
5203   }{}%
5204 }%
5205
5206 \newcommand{\setnotesXpositionliketwocolumns@}[1]{%
5207   \iftoggle{noteswidthliketwocolumnsX@#1}{%
5208     \csuse{setnotespositionliketwocolumns@\columns@position}%
5209   }{}%
5210 }%
5211
5212 %

```

XVII Footnotes' order

`\fnpos` The `\fnpos` and `\mpfnpos` simply place their arguments in `\@fnpos` and `\@mpfnpos`, which will be used later in the output routine.

```

\@fnpos
5213 \def\@fnpos{familiar-critical}
\@mpfnpos
5214 \def\@mpfnpos{critical-familiar}
5215 \newcommand{\fnpos}[1]{\xdef\@fnpos{#1}}
5216 \newcommand{\mpfnpos}[1]{\xdef\@mpfnpos{#1}}
5217 %

```

XVIII Footnotes' rule

Because the footnotes' rules can be shifted to the right when footnotes are set like two columns, we do not print them directly, but we put them in a `\vbox`.

```

\print@Xfootnoterule18 \newcommand{\print@Xfootnoterule}[1]{%
\print@footnoterule19 \vskip-\csuse{Xafterterrule@#1}%Because count in \dimen\csuse{#1footins}
5220 \nointerlineskip%
5221 \moveleft-\leftskip\vbox{\csuse{#1footnoterule}}%
5222 \nointerlineskip%
5223 \vskip\csuse{Xafterterrule@#1}%
5224 }%
5225
5226 \newcommand{\print@footnoterule}[1]{%
5227 \vskip-\csuse{afterterruleX@#1}%Because count in \dimen\csuse{footins#1}
5228 \nointerlineskip%
5229 \moveleft-\leftskip\vbox{\csuse{footnoterule#1}}%
5230 \nointerlineskip%
5231 \vskip\csuse{afterterruleX@#1}%
5232 }%
5233
5234 %

```

XIX Specific skip for first series of footnotes

XIX.1 Overview

`\Xbeforenotes` inserts a specific skip for the first series of notes in a page. As we can't know in advance which series will be the first, we call `\prepare@Xprenotes` before inserting any critical notes in order to prevent page number overlapping.

1. If it is the first note of the current page, it changes the footnote skip for the series to the value specified to `\Xbeforenotes`. It also keeps the series of the note as the first one of the current page.
2. If it is not the first note of the current page:

- If the current series is printed after the series kept as the first of the current page, then nothing happens.
- If the current series is printed before the series kept as the first of the current page, then it changes the footnote skip of the current series to the value normally used by the series which was marked as the first of the page. It also keeps the current series as the new first one of the current page.

For example, suppose the series order is A,B. We call first a `\Bfootnote` and a `\Afootnote`. The only skips used are, finally, the skip specific to the first series of the page, and the skip for the B series. If we have not called `\Afootnote`, the only skip used is the skip specific to the first series of the page.

That is perfect.

The series skip and the first series of the current page are reset before the footnotes are printed. Then, the footstart macros manage the problem of the first series of the page.

After the rule, the space which is defined by `\Xafterrule` does not depend on whether the series is the first one of the page or not. So we use its normal value for each series.

And now, implementation !

XIX.2 User level command

`\Xprenotes@` If user redefines `\Xprenotes@`, via `\Xprenotes` to a value greater than 0 pt, this skip will be added before first series notes instead of the notes skip.

```

5235 \newtoggle{Xprenotes@}%
5236 \toggletrue{Xprenotes@}%
5237 \newcommand{\Xprenotes@}{Opt}%
5238 \newcommand*{\Xprenotes}[1]{\renewcommand{\Xprenotes@}{#1}}%
5239 \newcommand{\preXnotes}[1]{\led@warning@preXnotes@deprecated\Xprenotes{#1}}
    %For compatibility
5240 %

```

The same, but for familiar footnotes.

```

\Xprenotes 41 \newtoggle{prenotesX@}
\Xprenotes@ 42 \toggletrue{prenotesX@}
5243 \newcommand{\prenotesX@}{Opt}
5244 \newcommand*{\prenotesX}[1]{\renewcommand{\prenotesX@}{#1}}
5245 %

```

XIX.3 Internal commands

```

firstXseries@ 46 \gdef\firstXseries@{}
prepare@Xprenotes 47 \newcommand{\prepare@Xprenotes}[1]{%
5248   \ifdimequal{Opt}{\Xprenotes@}%

```

```

5249 {}%
5250 {%
5251   \IfStrEq{\firstXseries@}{}{-%
5252     \global\skip\csuse{#1footins}=\Xprenotes@%
5253     \global\advance\skip\csname #1footins\endcsname by\csuse{Xafterrule@
#1}%
5254     \gdef\firstXseries@{#1}%
5255   }%
5256   {%
5257     \ifseriesbefore{#1}{\firstXseries@}%
5258     {%
5259       \global\skip\csuse{#1footins}=\csuse{Xbeforenotes@\firstXseries@}%
5260       \global\advance\skip\csname #1footins\endcsname by\csuse{Xafterrule@
#1}%
5261       \gdef\firstXseries@{#1}%
5262     }%
5263     {%
5264     }%
5265   }%
5266 }
5267 %

```

The same thing is required for familiar notes and \prenotesX.

```

firstseriesX@68 \gdef\firstseriesX@{}
prepare@prenotesX69 \newcommand{\prepare@prenotesX}[1]{%
5270   \ifdimequal{0pt}{\prenotesX@}%
5271   }%
5272   {%
5273     \IfStrEq{\firstseriesX@}{}{-%
5274       \global\skip\csuse{footins#1}=\prenotesX@%
5275       \global\advance\skip\csname footins#1\endcsname by\csuse{afterruleX@
#1}%
5276       \gdef\firstseriesX@{#1}%
5277     }%
5278     {%
5279       \ifseriesbefore{#1}{\firstseriesX@}%
5280       {%
5281         \global\skip\csuse{footins#1}=\csuse{beforenotesX@\firstseriesX@}%
5282         \global\advance\skip\csname footins#1\endcsname by\csuse{afterruleX@
#1}%
5283         \gdef\firstXseries@{#1}%
5284       }%
5285       {%
5286       }%
5287     }%
5288   }
5289 %

```

XX Endnotes

First, check the noend option.

```
5290 \ifbool{noend@}{}{%Used instead of \ifnoend@ to prevent expansion problem
5291 %
```

XX.1 Internal commands

`\l@dend@open` `\l@dend@close` `\l@dend@open` and `\l@dend@close` are the macros that are used to open and close the endnote file. Note that all our writing to this file is `\immediate`: all page and line numbers for the endnotes are generated by the same mechanism we use for the footnotes, so that there is no need to defer any writing to catch information from the output routine. The argument of these two command is the series letter.

```
5292 \newcommand{\l@dend@open}[1]{%
5293   \global\booltrue{l@dend@#1}%
5294   \expandafter\immediate%
5295   \expandafter\openout%
5296   \csname l@d@#1end\endcsname%
5297   =\l@auxdir\jobname.#1end\relax%
5298 }%
5299 \newcommand{\l@dend@close}[1]{%
5300   \global\boolfalse{l@dend@#1}%
5301   \expandafter\immediate%
5302   \expandafter\closeout\csname l@d@#1end\endcsname%
5303 }%
5304
5305 %
```

`\l@dend@stuff` `\l@dend@stuff` is used by `\beginnumbering` to do everything that is necessary for the endnotes at the start of each section: it opens the `\l@d@end` file, if necessary, and writes the section number to the endnote file.

```
5306 \newcommand{\l@dend@stuff}{%
5307   \def\do##1{%
5308     \ifbool{l@dend@##1}{}%
5309     {\l@dend@open{##1}}%
5310     \expandafter\immediate\expandafter\write\csname l@d@##1end\endcsname{\
string\l@d@section{\the\section@num}\@percentchar}%
5311   }%
5312   \dolistloop{@series}%
5313 }%
5314
5315 %
```

`\endprint` The `\endprint` here is nearly identical in its functioning to `\normalfootfmt`.
`\l@d@section` The endnote file also contains `\l@d@section` commands, which supply the section numbers from the main text; standard `reledmac` does nothing with this information,

but it is there if you want to write custom macros to do something with it. Arguments are:

Ar-

- #1 Line numbers and font selection.
- #2 Lemma.
- #3 Note content.
- #4 Series.
- #5 Optional argument of `\Xendnote`.
- #6 Side (L or R).
- #7 Label for cross-referencing.

```

5316 \global\newboolean\parapparatus@{\long}\def\endprint#1#2#3#4#5#6#7{
5317 \iftoggle{Xendfirstnote@#4}{%
5318   \global\togglefalse{Xendfirstnote@#4}%
5319   \csuse{Xendtxtbeforenotes@#4}%
5320 }}%
5321 \csuse{Xendbhooknote@#4}%
5322 \csuse{Xendnotefontsize@#4}%
5323 \hangindent=\csuse{Xendhangindent@#4}%
5324 \Xendstorelineinfo{#1}{#4}%
5325 \ifXendinsertsep%
5326   \hskip\csuse{Xendafternote@#4}\relax%
5327   \ifcsdef{preendlines@#4}%
5328     {\ifcsequal{preendlines@#4}{lineinfo@}%
5329       {\ifcsequal{Xendsymnum@#4}{\csuse{Xendsep@#4}}{}}%
5330       {\csuse{Xendsep@#4}}%
5331     }%
5332     {\csuse{Xendsep@#4}}%
5333 \else%
5334   \iftoggle{Xendparagraph@#4}%
5335     {\global\Xendinsertsep@true}%
5336     {}%
5337 \fi%
5338 \xdef\@currentseries{#4}%
5339 \def\do##1{%
5340   \setkeys{mac}{truefootnoteoption}{##1}%
5341 }%
5342 \notblank{#5}{\docsvlist{#5}}}%
5343 \IfStrEq{#6}{R}{\ledRcol@true}{}%
5344 \def\@this@crossref@start{#7:start}%
5345 \def\@this@crossref@end{#7:end}%
5346 \printlineendnote{#1}{#4}%
5347 \IfStrEq{#6}{R}{\ledRcol@false}{}%
5348 \nottoggle{Xendlemmadisablefontselection@#4}%
5349   {\select@lemmafont#1}%

```

```

5350 {}%
5351 \bgroup%
5352 \csuse{Xendlemmafont@#4}%
5353 \csuse{Xendwraplemma@#4}{#2}%
5354 \egroup%
5355 \ifbool{expr}%
5356 togl {nosep@}%
5357 or test{\ifcsemt{Xendlemmaseparator@#4}}%
5358 }%
5359 {\hskip\csuse{Xendinplaceoflemmaseparator@#4}\relax}%
5360 {\nobreak%
5361 \hskip\csuse{Xendbeforelemmaseparator@#4}%
5362 \csuse{Xendlemmaseparator@#4}%
5363 \hskip\csuse{Xendafterlemmaseparator@#4}%
5364 \relax%
5365 }%
5366 \csuse{Xendwrapcontent@#4}{#3}%
5367 \nottoggle{Xendparagraph@#4}{\par}{}%
5368 \def\do##1{%
5369 \setkeys[mac]{falsefootnoteoption}{##1}%
5370 }%
5371 \notblank{#5}{\docsvlist{#5}}{}%
5372 }}%
5373
5374 \let\l@d@section=\@gobble
5375
5376 %

```

\Xendstorelineinfo The `\Xendstorelineinfo` macro is used to store some data about line number of the current critical endnote, data which will be reused later for the `\Xnumberonlyfirstinline` and related setting.

#1 endnote specification for the current endnote; #2 endnote series.

```

5377 \newcommand{\Xendstorelineinfo}[2]{%
5378 \l@dp@rsefootspec#1|}%
5379 \iftoggle{Xendnumberonlyfirstintwolines@#2}{%
5380 \xdef\lineinfo@{\l@dparsedstartpage - \l@dparsedstartline - \
5381 \l@dparsedstartsub - \l@dparsedendpage - \l@dparsedendline - \
5382 \l@dparsedendsub}%
5383 }%
5384 {\xdef\lineinfo@{\l@dparsedstartpage - \l@dparsedstartline - \
5385 \l@dparsedstartsub}%
5386 }%
5387 }%
5388 %

```

\printlineendnote This macro controls, in endnote, whether the line number is printed or not, according to the series options. Its first argument is the information about lines; its second is the series of the footnote.


```

5387 \newcommand{\printlineendnote}[2]{%
5388   \ifbool{expr{%
5389     togl {nonum@}%
5390     or togl {Xendnonumber@#2}%
5391   }}%
5392   {\hspace{\csuse{Xendinplaceofnumber@#2}}}%
5393   {%
5394     \iftoggle{Xendnumberonlyfirstinline@#2}%
5395     {\ifcsdef{prevendline#2}%
5396       {\ifcsequal{prevendline#2}{lineinfo@}%
5397         {%
5398           \csuse{Xendbhookinplaceofnumber@#2}%
5399           \ifcsequal{Xendsymmlinenumber@#2}%
5400             {\hspace{\csuse{Xendinplaceofnumber@#2}}}%
5401             {\printsymlineendnotearea{#2}}}%
5402           \csuse{Xendahookinplaceofnumber@#2}%
5403           }%
5404             {\printlineendnotearea{#1}{#2}}}%
5405             {\printlineendnotearea{#1}{#2}}}%
5406           }%
5407             {\printlineendnotearea{#1}{#2}}}%We keep every time line
5408   \csxdef{prevendline#2}{\lineinfo@}%
5409   }%
5410 }%
5411 %

```

```

\printsymlineendnotearea \newcommand{\printsymlineendnotearea}[1]{%
5413   \hspace{\csuse{Xendbeforemlinenumber@#1}}%
5414   \csuse{Xendnotenumfont@#1}%
5415   \ifdimequal{\csuse{Xendboxsymmlinenumber@#1}}{\z@}%
5416     {\csuse{Xendsymmlinenumber@#1}}%
5417     {\hbox to \csuse{Xendboxsymmlinenumber@#1}%
5418       {\csuse{Xendsymmlinenumber@#1}\hfill}%
5419     }%
5420   \hspace{\csuse{Xendaftersymmlinenumber@#1}}%
5421 }%
5422 %

```

\printlineendnotearea This macro prints the space before the line number, changes the font, then prints the line number and the space after it. It is called by `\endprint` depending on the options about repeating line numbers. The first argument is line information, the second is the notes series (A, B, C, etc.)

```

5423 \newcommand{\printlineendnotearea}[2]{%
5424   \csuse{Xendbhooklinenumber@#2}%
5425   \hspace{\csuse{Xendbeforenumber@#2}}%
5426   \bgroup%
5427   \csuse{Xendnotenumfont@#2}%
5428   \ifdimequal{\csuse{Xendboxlinenumber@#2}}{\Opt}%

```

```

5429     {\printendlines#1||\ifledRcol@\@Rlineflag\fi}%
5430     {\leavevmode%
5431     \hbox to \csuse{Xendboxlinenum@#2}%
5432     {%
5433     \IfSubStr{RC}{\csuse{Xendboxlinenumalign@#2}}{\hfill}}}%
5434     \printendlines#1||\ifledRcol@\@Rlineflag\fi%
5435     \IfSubStr{LC}{\csuse{Xendboxlinenumalign@#2}}{\hfill}}}%
5436     }%
5437 \egroup%
5438 \hspace{\csuse{Xendafternumber@#2}}%
5439 \csuse{Xendahooklinenum@#2}%
5440 }%
5441 %

```

XX.2 User level commands

XX.2.1 Inserting contents to endnotes

The `\Xendnotes` commands are defined above, when defining apparatus commands by series. Here, we define only `\toendnotes` command not specific to a series, in order to insert arbitrary code. The regular version writes an unexpanded argument, while the regular version writes a once-expanded argument.

```

\toendnotes*42 \newcommandx{\toendnotes}[2][1,usedefault]{%
\toendnotes*43 \ifboolexpr{bool{numbering} or bool{numberingR}}{%
5444 \def\do##1{%
5445 \expandafter\immediate\expandafter\write\csname l@d@##1end\endcsname%
5446 {\unexpanded{#2}\@percentchar}%
5447 }%
5448 \ifstrempy{#1}%
5449 {\dolistloop{\@series}}%
5450 {\docsvlist{#1}}%
5451 }\led@err@toendnotes@outsidenumbering}%
5452 }%
5453 \WithSuffix\newcommandx\toendnotes*[2][1,usedefault]{%
5454 \ifboolexpr{bool{numbering} or bool{numberingR}}{%
5455 \def\do##1{%
5456 \expandafter\immediate\expandafter\write\csname l@d@##1end\endcsname%
5457 {#2\@percentchar}%
5458 }%
5459 \ifstrempy{#1}%
5460 {\dolistloop{\@series}}%
5461 {\docsvlist{#1}}%
5462 }\led@err@toendnotes@outsidenumbering}%
5463 }%
5464 %

```

XX.2.2 Printing endnotes

`\doendnotes` `\doendnotes` is the command you use to print one series of endnotes; it takes one argument: the series letter of the note series you want to print. `\Xendinsertsep@` is set to true at the first note of the series, and to false at the last one.

```

5465 \newif\ifXendinsertsep@%
5466 \newcommand*{\doendnotes}[1]{%
5467   \l@dend@close{#1}%
5468   \begingroup
5469     \csxdef{prevpagenum@#1}{}%
5470     \csxdef{prevpagerange@#1}{}%
5471     \global\toggletrue{Xendfirstnote@#1}%
5472     \makeatletter
5473     \expandafter\let\csname #1end\endcsname=\endprint
5474     \input\l@auxdir\jobname.#1end%
5475     \global\Xendinsertsep@false%
5476   \endgroup}
5477 %

```

`\doendnotesbysection` `\doendnotesbysection` is a variant of the previous macro. While `\doendnotes` print endnotes for all of numbered sections `\doendnotesbysection` print the endnotes for the first numbered section at its first call for a series, then for the second section at its second call for the same series, then for the third section at its third call for the same series, and so on.

```

5478 \newcommand*{\doendnotesbysection}[1]{%
5479   \l@dend@close{#1}%
5480   \csxdef{prevpagenum@#1}{}%
5481   \csxdef{prevpagerange@#1}{}%
5482   \global\expandafter\advance\csname #1end@bysection\endcsname by 1%
5483   \begingroup%
5484     \makeatletter%
5485     \def\l@d@section##1{%
5486       \global\toggletrue{Xendfirstnote@#1}%
5487       \ifnumequal{##1}{\csname #1end@bysection\endcsname}%
5488         {\cslet{#1end}{\endprint}}%
5489         {\cslet{#1end}{\@gobbleseven}}%
5490     }%
5491     \input\l@auxdir\jobname.#1end%
5492     \global\Xendinsertsep@false%
5493   \endgroup%
5494 }%
5495 %

```

We close now the conditional period, which depends on `\ifnoend@`, because the following commands can be used by other commands than those specific to endnotes.

```

5496 }%
5497 %

```

The `\printendlines` macro is similar to `\printlines` but is for printing endnotes rather than footnotes.

The principal difference between foot- and endnotes is that footnotes are printed on the page where they are specified but endnotes are printed at a different point in the document. We need an indication of the source of an endnote; `\setprintendlines` provides this by always printing the page number. The coding is slightly simpler than `\setprintlines`.

from the starting page number.

```
\setprintendlines% \newif\ifl@d@Xendlinenumber%
\ifl@d@Xendlinenumber% \newcommand*{\setprintendlines}[6]{%
5500 \let\@annot@start@print\relax%
5501 \let\@annot@end@print\relax%
5502 \l@d@pnumfalse%
5503 \l@d@dashfalse%
5504 \l@d@elinfalse%
5505 %
```

Should we print the line number? It depends on hooks and annotations.

```
5506 \l@d@Xendlinenumbertrue%
5507 \ifboolexpr{togl{Xendnolinenumber@\@currentseries}}%
5508 or (%
5509 togl{Xendnolinenumberifannotation@\@currentseries}}%
5510 and not test{\ifdefvoid{\annot@start}}%
5511 and not test{\ifdefvoid{\annot@end}}%
5512 )%
5513 }{%
5514 \l@d@Xendlinenumberfalse%
5515 }{}%
5516 %
```

We print the second page number only if the ending page number is different

```
5517 \ifnum#4=#1 \else
5518 \l@d@pnumtrue
5519 \l@d@dashtrue
5520 \fi
5521 %
```

We print the ending line number if:

1. we print the ending page number;
2. or the ending line is different from the starting line number and we didn't disable the line number printing.

If either of these conditions is true, we also print the annotation linked to the ending line number annotations.

```
5522 \ifboolexpr{%
5523 bool{\l@d@pnum}}%
```

```

5524     or not test{\ifnumequal{#2}{#5}}}%
5525     and bool{!@d@Xendlinenum}%
5526   }{%
5527     \!d@elintrue%
5528     \!d@dashtrue%
5529     \!d@elintrue
5530     \!d@dashtrue
5531     \unless\ifx\relax\annot@end%
5532     \def\@annot@end@print{%
5533       \!@wrapcs@ifnotemptybox{Xendwraplinenumannotation@\@currentseries
5534 }{\@annot@end}%
5535   }%
5536   \fi%
5537 }%
5538 %

```

We define the starting line number annotation as a merge of the starting annotation and ending annotation if we don't print the ending line number. Otherwise, it is only the starting annotation.

```

5539 \if!d@elin%
5540   \def\@annot@start@print{%
5541     \!@wrapcs@ifnotemptybox{Xendwraplinenumannotation@\@currentseries}{\
5542   \annot@start}%
5543   }%
5544   \else%
5545     \ifx\annot@start\annot@end%
5546       \unless\ifx\@annot@start\relax%
5547       \def\@annot@start@print{%
5548         \!@wrapcs@ifnotemptybox{Xendwraplinenumannotation@\@currentseries
5549 }{\@annot@start}%
5550       }%
5551       \fi%
5552     \else%
5553       \ifx\@annot@end@print\relax%
5554       \def\@annot@start@print{%
5555         \!@wrapcs@ifnotemptybox{Xendwraplinenumannotation@\@currentseries
5556 }{%
5557         \ifx\annot@start\empty\else%
5558           \annot@start%
5559           \ifdefined\linerrangesep%
5560             \linerrangesep%
5561           \else%
5562             \csuse{Xendlinerrangeseparator@\@currentseries}%
5563           \fi%
5564         \fi%
5565         \annot@end%
5566       }%
5567       \else%

```

```

5566         \let\@annot@start@print\@annot@end@print%
5567         \let\@annot@end@print\relax%
5568         \fi%
5569     \fi%
5570 \fi%
5571 %

```

We print the starting sub-line if it is nonzero.

```

5572 \l@d@ssubfalse
5573 \ifnum#3=0 \else
5574     \l@d@ssubtrue
5575 \fi
5576 %

```

We print the ending sub-line if it is nonzero and: (1) it is different from the starting sub-line number, or (2) the ending line number is being printed.

```

5577 \l@d@eslfalse
5578 \ifnum#6=0 \else
5579     \ifnum#6=#3
5580         \ifl@d@elin \l@d@esltrue \else \l@d@eslfalse \fi
5581     \else
5582         \l@d@esltrue
5583         \l@d@dashtrue
5584     \fi
5585 \fi%
5586 %
5587 \ifl@d@dash%
5588     \ifboolexpr{togl{fulllines@} or test{\ifcsemt{Xendtwolines@}\@currentseries}}}%
5589     {%
5590     {%
5591         \setistwofollowinglines{#1}{#2}{#4}{#5}%
5592         \ifboolexpr{%
5593             (%
5594                 togl {Xendtwolinesbutnotmore@\@currentseries}%
5595                 and not%
5596                 (%
5597                     bool {istwofollowinglines@}%
5598                 )%
5599             )%
5600         or%
5601         (%
5602             (not test{\ifnumequal{#1}{#4}})%
5603             and togl{Xendtwolinesonlyinsamepage@\@currentseries}%
5604         )%
5605         }%
5606     }%
5607     {%
5608         \l@d@dashfalse%

```

```

5609         \l@d@Xtwolinestrue%
5610         \l@d@elinfalse%
5611         \l@d@eslfalse%
5612         \ifcsempy{Xendmoreethantwolines@ \@currentseries}%
5613         {%
5614         {\ifistwofollowinglines@ \else%
5615         \l@d@Xmoreethantwolinstrue%
5616         \fi%
5617         }%
5618         }%
5619     }%
5620 \fi%
5621 %

```

If the `\Xendnoidenticallinenumannotation` is set for this series, we check if the ending annotation is identical to the starting. If true, we don't print the ending annotation

```

5622 \iftoggle{Xendnoidenticallinenumannotation@ \@currentseries}{%
5623 \ifx\annot@start\annot@end%
5624 \let\annot@end@print\relax%
5625 \ifboolexpr{%Do not print the dash if we do not print the line number
5626 test{\ifdefempty{\linenumrep}}}%
5627 or not bool {l@d@Xendlinenum}%
5628 }{%
5629 \l@d@dashfalse%
5630 }{%
5631 \fi%
5632 }{%
5633 %

```

Finally, we check for `\Xendlinenumannotationonlyfirst` and `\Xendlinenumannotationonlyfirstintwo`, and we redefine, if required, `\annot@start@print` and `\annot@end@print`. We also store the current line number annotations.

```

5634 \iftoggle{Xendlinenumannotationonlyfirst@ \@currentseries}{%
5635 \ifboolexpr{%
5636 (%
5637 togl{Xendlinenumannotationonlyfirstintwo@ \@currentseries}%
5638 and test{\ifcsequal{annot@start}{prevannot@start@ \@currentseries}}%
5639 and test{\ifcsequal{annot@end}{prevannot@end@ \@currentseries}}%
5640 )%
5641 or%
5642 (%
5643 not togl{Xendlinenumannotationonlyfirstintwo@ \@currentseries}%
5644 test{\ifcsequal{annot@start}{prevannot@start@ \@currentseries}}%
5645 )%
5646 }{%
5647 \def\annot@start@print{%
5648 \l@wrapcs@ifnotemptybox{Xendwraplinenumannotation@ \@currentseries
}{\csuse{Xendsymmlinenumannotation@ \@currentseries}}%

```

```

5649 }%
5650 \let\annot@end@print\relax%
5651 \ifboolexpr{%Do not print the dash if do not print the line number
5652   test{\ifdefempty{\linenumrep}}}%
5653   or not bool {l@d@Xendlinenumber}%
5654 }{%
5655   \l@d@dashfalse%
5656 }{}%
5657 }{}%
5658 \global\cslet{prevannot@start@\@currentseries}{\annot@start}%
5659 \global\cslet{prevannot@end@\@currentseries}{\annot@end}%
5660 }%
5661 {}%
5662 %

```

End of \setprintendlines.

```

5663 }%
5664 %

```

\printendlines Now we are ready to print it all.

```

5665 \def\printendlines#1|#2|#3|#4|#5|#6|#7|#8|{%
5666   \begingroup
5667   \setprintendlines{#1}{#2}{#3}{#4}{#5}{#6}%
5668   %

```

The only subtlety left here is when to print a period between numbers. But the only instance in which this is tricky is for the ending sub-line number: it could be coming after the starting sub-line number (in which case we want only the dash) or after an ending line number (in which case we need to insert a period).

So, first, start the starting line box, if needed.

```

5669 \ifdimequal{\csuse{Xendboxstartlinenum@\@currentseries}}{0pt}%
5670 {\bgroup}%
5671 {\leavevmode\hbox to \csuse{Xendboxstartlinenum@\@currentseries}\bgroup
5672 \hfill}%
5673 %

```

Then, print the starting page number-

```

5673 \ifboolexpr{%
5674   (%
5675     test{\ifcsstring{prevpagenum@\@currentseries}{#1}}%
5676     and not%
5677     (togl{Xendpagenumberonlyfirstifsingle@\@currentseries} and bool{
5678   l@d@pnum})%
5679   )%
5680   or%
5681   (%
5682     test {\ifcsstring{prevpagerange@\@currentseries}{#1-#4}}%
5683   )%

```



```

5683 }%
5684 {%
5685 \ifcempty{Xendsympagenum@\@currentseries}%
5686 {\hspace{\csuse{Xendinplaceofpagenumber@\@currentseries}}}%
5687 {\csuse{Xendsympagenum@\@currentseries}}%
5688 }%
5689 {%
5690 \wrap@edcrossref{\@this@crossref@start}{\printnpnum{#1}}%
5691 }%
5692 %

```

Then, determine what must be printed before the start line.

```

5693 \ifl@d@dash%
5694 \ifl@d@pnum%
5695 \csuse{Xendlineprefixsingle@\@currentseries}%
5696 \else%
5697 \ifcempty{Xendlineprefixmore@\@currentseries}%
5698 {\csuse{Xendlineprefixsingle@\@currentseries}}%
5699 {\csuse{Xendlineprefixmore@\@currentseries}}%
5700 \fi%
5701 \else%
5702 \csuse{Xendlineprefixsingle@\@currentseries}%
5703 \fi%
5704 %

```

Then print the starting line, followed, if needed, by the side flag and the starting sub line number, then the line number annotation.

```

5705 \ifcsstring{Xendlinenumannotationposition@\@currentseries}{before}%
5706 {\@annot@start@print}%
5707 {}%
5708 \ifl@d@Xendlinenum%
5709 \wrap@edcrossref{\@this@crossref@start}{%
5710 \ifl@d@Rcol%
5711 \linenumrepR{#2}%
5712 \else%
5713 \linenumrep{#2}%
5714 \fi%
5715 }%
5716 \fi%
5717 \iftoggle{Xendlineflag@\@currentseries}{\ifl@d@Rcol@\@Rlineflag\fi}{}%
5718 \ifl@d@Xendlinenum%
5719 \ifl@d@ssub%
5720 \csuse{Xendsublinesep@\@currentseries}%
5721 \wrap@edcrossref{\@this@crossref@start}{%
5722 \ifl@d@Rcol%
5723 \sublinenumrepR{#3}%
5724 \else%
5725 \sublinenumrep{#3}%
5726 \fi%
5727 }%

```

```

5728 \fi%
5729 \fi%
5730 \ifcsstring{Xendlinenumannotationposition@\@currentseries}{after}%
5731 {\@annot@start@print}%
5732 {}%
5733 %

```

Close the box.

```

5734 \egroup%
5735 %

```

Open the box for the ending line number.

```

5736 \ifdimequal{\csuse{Xendboxendlinenum@\@currentseries}}{Opt}%
5737 {\bgroup}%
5738 {\hbox to \csuse{Xendboxendlinenum@\@currentseries}\bgroup}%
5739 %

```

Print the dash + the ending line number, or the line number range symbol.

```

5740 \ifl@d@Xtwolines%
5741 \ifl@d@Xendlinenum%
5742 \ifl@d@Xmorethantwolines%
5743 \csuse{Xendmorethantwolines@\@currentseries}%
5744 \else%
5745 \csuse{Xendtwolines@\@currentseries}%
5746 \fi%
5747 \fi%
5748 \else%
5749 \ifl@d@dash%
5750 \ifdefined\linrangesep%
5751 \linrangesep%
5752 \else%
5753 \csuse{Xendlinrangeseparator@\@currentseries}%
5754 \fi%
5755 \fi%
5756 %

```

Print the ending page number.

```

5757 \ifl@d@pnum%
5758 \ifcsstring{prevpagerange@\@currentseries}{#1-#4}%
5759 {%
5760 \ifcempty{Xendsympagenum@\@currentseries}%
5761 {\hspace{\csuse{Xendinplaceofpagenumber@\@currentseries}}}%
5762 {\csuse{Xendsympagenum@\@currentseries}}%
5763 }%
5764 {%
5765 \wrap@edcrossref{\@this@crossref@end}{\printpnum{#4}}%
5766 }%
5767 \fi%
5768 %

```

Print the ending line number, with, if needed, the line prefix, and followed by the side flag, the subline number, and line number annotation.

```

5769 \ifcsstring{Xendlinenumannotationposition@\@currentseries}{before}%
5770 {\@annot@end@print}%
5771 }%
5772 \ifl@d@Xendlinenumber%
5773 \ifl@d@elin%
5774 \ifl@d@pnum\csuse{Xendlineprefixsingle@\@currentseries}\fi%
5775 \wrap@edcrossref{\@this@crossref@end}{%
5776 \ifledRcol%
5777 \linenumrepR{#5}%
5778 \else%
5779 \linenumrep{#5}%
5780 \fi%
5781 }%
5782 \iftoggle{Xendlineflag@\@currentseries}{\ifledRcol@\@Rlineflag\fi
5783 }{}%
5784 \fi%
5785 \ifl@d@esl%
5786 \ifl@d@elin%
5787 \csuse{Xendsublinesep@\@currentseries}%
5788 \fi%
5789 \wrap@edcrossref{\@this@crossref@end}{%
5790 \ifledRcol%
5791 \sublinenumrepR{#6}%
5792 \else%
5793 \sublinenumrep{#6}%
5794 \fi%
5795 }%
5796 \fi%
5797 \ifcsstring{Xendlinenumannotationposition@\@currentseries}{after}%
5798 {\@annot@end@print}%
5799 }%
5800 \fi%
5801 %

```

Close the ending line box.

```

5802 \ifdimequal{\csuse{Xendboxendlinenum@\@currentseries}}{0pt}%
5803 {}%
5804 {\hfill}%Prevent underfull hbox
5805 \egroup%
5806 %

```

And, finally, save, if needed, the current page number for the Xendpagenumberonlyfirst hooks.

```

5807 \iftoggle{Xendpagenumberonlyfirst@\@currentseries}%
5808 {\iftoggle{Xendpagenumberonlyfirstintwo@\@currentseries}%
5809 {\csxdef{prevpagerange@\@currentseries}{#1-#4}}%

```

```

5810     {\csxdef{prevpagenum@\@currentseries}{#4}}%
5811     }%
5812     {}%
5813 %

```

Now, the end of `\printendlines` macro.

```

5814     \endgroup%
5815 }%
5816
5817 %

```

`\printnpnum` A macro to print a page number in an endnote. Should not be override anymore

```

5818 \newcommand*{\printnpnum}[1]{\csuse{Xendbeforepagenumber@\@currentseries
5819 }#1\csuse{Xendafterpagenumber@\@currentseries}}
5820 %

```

XXI Generate series of notes

In this section, X means the name of the series (A, B etc.)

`\series` `\series` creates one more new series. It is a public command, which just loops on the private command `\newseries@`.

```

5821 \newcommand{\newseries}[1]{%
5822     \def\do##1{\newseries@{##1}}%
5823     \docsvlist{#1}
5824 }
5825 %

```

`\@series` The `\series@` macro is an etoolbox list, which contains the name of all series.

```

5826 \newcommand{\@series}{}
5827 %

```

The command `\newseries@\series` creates a new series of the footnote.

```

\newseries@28 \newcommand{\newseries@}[1]{
5829 %

```

XXI.1 Test if series is still existing

```

5830     \xifinlist{#1}{\@series}{\led@warn@SeriesStillExist{#1}}%
5831     {%
5832 %

```

XXI.2 Init specific to reledpar

When calling `\newseries@` after having loaded `reledpar`, we need to load specific setting.

```
5833 \ifdefined\newseries@par%
5834 \newseries@par{#1}%
5835 \fi%
5836 %
```

XXI.3 For critical footnotes

Critical footnotes are those which start with letters. We look for the `\nocritical` option of `reledmac`.

```
5837 \unless\ifnocritical@
5838 %
```

XXI.3.1 Options

```
5839 \newtoggle{Xlineflag@#1}
5840 \newtoggle{Xparindent@#1}
5841 \newtoggle{Xlemmadisablefontselection@#1}
5842 \csgdef{Xwrapcontent@#1}{}%
5843 \csgdef{Xbeforeinserting@#1}{}%
5844 \csgdef{Xhangindent@#1}{Opt}%
5845 \csgdef{Xragged@#1}{}%
5846 \csgdef{Xhsizetwocol@#1}{0.45 \hsize}%
5847 \csgdef{Xhsizethreecol@#1}{.3 \hsize}%
5848 \csgdef{Xcolalign@#1}{\raggedright}%
5849 \csgdef{Xnotenumfont@#1}{\normalfont}%
5850 \csgdef{Xnotefontsize@#1}{\footnotesize}%
5851 \csgdef{Xbhooknote@#1}{}%
5852 \csgdef{Xbhookgroup@#1}{}%
5853
5854 \csgdef{Xboxlinenum@#1}{Opt}%
5855 \csgdef{Xboxlinenumalign@#1}{L}%
5856
5857 \csgdef{Xboxstartlinenum@#1}{Opt}%
5858 \csgdef{Xboxendlinenum@#1}{Opt}%
5859
5860 \csgdef{Xboxsymlinenum@#1}{Opt}%
5861 \newtoggle{Xgroupbyline@#1}%
5862 \newtoggle{Xgroupbylineseparetwolines@#1}%
5863
5864 \newtoggle{Xnumberonlyfirstinline@#1}%
5865 \newtoggle{Xnumberonlyfirstintwolines@#1}%
5866
5867 \newtoggle{Xlinenumannotationonlyfirst@#1}%
```

```

5868 \newtoggle{Xlinenumannotationonlyfirstintwo@#1}%
5869
5870 \csgdef{Xtwolines@#1}{}%
5871 \csgdef{Xmorethantwolines@#1}{}%
5872 \csgdef{Xsublinesep@#1}{\fullstop}%
5873 \csgdef{Xpagelinesep@#1}{\csname Xsublinesep@#1\endcsname}%for
backward compatibility, call Xsublinesep@#1
5874 \newtoggle{Xtwolinesbutnotmore@#1}%
5875 \newtoggle{Xtwolinesonlyinsamepage@#1}%
5876 \newtoggle{Xonlypstart@#1}%
5877 \newtoggle{Xpstarteverytime@#1}%
5878
5879 \newtoggle{Xpstart@#1}%
5880 \newtoggle{Xpstartonlyfirst@#1}%
5881 \csdef{Xprevpstart@#1}{0}%Not a hook, but a tool for the hook
Xpstartonlyfirst
5882 \csgdef{Xpstartseparator@#1}{}%
5883
5884 \newtoggle{Xstanza@#1}%
5885 \newtoggle{Xstanzaonlyfirst@#1}%
5886 \csdef{Xprevstanza@#1}{0}%Not a hook, but a tool for the hook
Xstanzaonlyfirst
5887
5888 \csgdef{Xstanzaseparator@#1}{}%
5889
5890 \csgdef{Xsymlinenum@#1}{}%
5891 \csgdef{Xsymlinenumannotation@#1}{}%
5892
5893 \newtoggle{Xnonumber@#1}%
5894 \newtoggle{Xnolinenum@#1}%
5895 \newtoggle{Xnolinenumifannotation@#1}%
5896 \csgdef{Xbeforenumber@#1}{Opt}%
5897 \csgdef{Xtxtbeforenumber@#1}{}%
5898 \csgdef{Xafternumber@#1}{0.5em}%
5899 \newtoggle{Xnonbreakableafternumber@#1}%
5900 \csgdef{Xbeforesymlinenum@#1}{\csuse{Xbeforenumber@#1}}%
5901 \csgdef{Xaftersymlinenum@#1}{\csuse{Xafternumber@#1}}%
5902 \csgdef{Xinplaceofnumber@#1}{1em}%
5903 \global\cslet{Xlemmaseparator@#1}{\rbracket}%
5904 \csgdef{Xbeforelemmaseparator@#1}{0em}%
5905 \csgdef{Xafterlemmaseparator@#1}{0.5em}%
5906 \csgdef{Xinplaceoflemmaseparator@#1}{1em}%
5907 \csgdef{Xbeforenotes@#1}{1.2em \@plus .6em \@minus .6em}%
5908 \csgdef{Xafterrule@#1}{Opt}%
5909
5910 \csgdef{Xtxtbeforenotes@#1}{%
5911 \newtoggle{Xtxtbeforenotes@#1@typeset}}%Not directly used by user,
but internal
5912 \newtoggle{Xtxtbeforenotesonlyonce@#1}%
5913

```

```

5914 \csgdef{Xmaxhnotes@#1}{0.8\vsizel}
5915 \newtoggle{Xnoteswidthliketwocolumns@#1}%
5916 \csgdef{Xparafootsep@#1}{}%
5917 \csgdef{Xafternote@#1}{1em plus.4em minus.4em}
5918 \csgdef{Xlinrangeseparator@#1}{\endashchar}%
5919
5920 \csgdef{Xlemmafont@#1}{}%
5921 \csgdef{Xwraplemma@#1}{%
5922 \csgdef{Xwidth@#1}{\hsizel}%
5923 \csgdef{Xwraplinenumannotation@#1}{\textsuperscript}%
5924 \csgdef{Xlinenumannotationposition@#1}{after}%
5925 \expandafter\csgdef{Xinnotemark@#1}##1{\ledinnotemark{##1}}%
5926 \newtoggle{Xnoidenticallinenumannotation@#1}%
5927 %

```

XXI.3.2 Create inserts, needed to add notes in foot

As regards inserts, see chapter 15 of *The TeXbook* by D. Knuth.

```

5928 \expandafter\newinsert\csname #1footins\endcsname%
5929 \unless\ifnoledgroup%
5930 \expandafter\newinsert\csname mp#1footins\endcsname%
5931 \fi%
5932 %

```

XXI.3.3 Create commands for critical apparatus, \Afootnote, \Bfootnote etc.

Note the double # in command: it is because command it is made inside another command.

```

5933 \global\newbool{parapparatus@}{\expandafter\newcommand\expandafter
5934 *}{\expandafter\newcommand}\csname #1footnote\endcsname[2] []{%
5935 \ifedtext@secondarg%
5936 \ifledRcol%
5937 \ifcsstring{Xonlyside@#1}{L}{\
5938 led@error@note@called@onrightside{#1footnote}}}%
5939 \else%
5940 \ifcsstring{Xonlyside@#1}{R}{\
5941 led@error@note@called@onleftside{#1footnote}}}%
5942 \fi%
5943 \begingroup%
5944 \newcommand{\content}{##2}%
5945 \ifnumberedpar%
5946 \ifledRcol%
5947 \ifluatex%
5948 \footnotelang@lua[R]%
5949 \fi%
5950 \@ifundefined{xpg@main@language}%if polyglossia
5951 {}%
5952 {\footnotelang@poly[R]}%
5953 \footnoteoptions@{R}{##1}{true}%

```

```

5951 \xright@appenditem{%
5952 \ifbool{indtl@innote}%
5953 {\unexpanded{\let\index\nindex}}%
5954 {}%
5955 \ifbool{indtl@notenumber}%
5956 {\unexpanded{\let\index\nindex}}%There is no note
number... so
5957 {}%
5958 \noexpand\Xnote@true%
5959 \unexpanded{\gdef\@currentnotetype{critical}}%
5960 \noexpand\prepare@Xprenotes{#1}%
5961 \noexpand\prepare@edindex@fornote{\l@d@nums}%
5962 \unexpanded{\def\sw@list@inedtext}{\expandafter\
unexpanded\expandafter{\sw@inthisedtext}}%The value of the \sw@inthisedtext
of current \edtext will be pushed to \sw@list@inedtext when the notes are
expanded.
5963 \noexpand\setcounter{stanzaR}{\the\c@stanzaR}%Save
stanzaR counter for footnote
5964 \unexpanded{\def\@this@crossref@start}{\theedtext:
start}%
5965 \unexpanded{\def\@this@crossref@end}{\theedtext:end}%
5966 \expandonce{\@beforeinsertofthisedtext}% Internal for
now, no reason to make it public
5967 \noexpand\parse@annot\l@current@annotR|%
5968 \noexpand\csuse{v#1footnote}{#1}%
5969 {\l@d@nums}{\expandonce\@tag}{\expandonce\content}}
%
5970 \noexpand\Xnote@false%
5971 \unexpanded{\advance\@edindex@fornote@m@one}%
5972 \ifbool{indtl@innote}%
5973 {\unexpanded{\let\index\orig@index}}%
5974 {}%
5975 \ifbool{indtl@notenumber}%
5976 {\unexpanded{\let\index\orig@index}}%
5977 {}%
5978 }\to\inserts@listR
5979 \footnoteoptions@{R}{##1}{false}%
5980 \global\advance\insert@countR \@one%
5981 \else%
5982 \ifluatex%
5983 \footnotelang@lua%
5984 \fi%
5985 \ifundefined{xpg@main@language}%if polyglossia
5986 {}%
5987 {\footnotelang@poly}%
5988 \footnoteoptions@{L}{##1}{true}%
5989 \xright@appenditem{%
5990 \ifbool{indtl@innote}%
5991 {\unexpanded{\let\index\nindex}}%
5992 {}%

```



```

5993         \ifbool{indtl@notenumber}%
5994             {\unexpanded{\let\index\nindex}}%There is no note
number... so
5995         {}%
5996         \noexpand\Xnote@true%
5997         \unexpanded{\gdef\@currentnotetype{critical}}%
5998         \noexpand\prepare@Xprenotes{#1}%
5999         \noexpand\prepare@edindex@fornote{\l@d@nums}%
6000         \unexpanded{\def\sw@list@inedtext}{\expandafter\
unexpanded\expandafter{\sw@inthisedtext}}%The value of the \sw@inthisedtext
of current edtext will be pushed to \sw@list@inedtext when the notes are
expanded.
6001         \ifl@dpairing%
6002             \noexpand\setcounter{stanzaL}{\the\c@stanzaL}%Save
stanzaR counter for footnote
6003         \fi%
6004         \unexpanded{\def\@this@crossref@start}{\theedtext:
start}%
6005         \unexpanded{\def\@this@crossref@end}{\theedtext:end}%
6006         \expandonce{\@beforeinsertofthisedtext}%Internal for
now, no reason to make it public
6007         \noexpand\parse@annot\l@current@annot|%
6008         \noexpand\csuse{v#1footnote}%
6009             {#1}%
6010             {{\l@d@nums}{\expandonce\@tag}{\expandonce\content
}}%
6011         \noexpand\Xnote@false%
6012         \unexpanded{\advance\@edindex@fornote@m@ne}%
6013         \ifbool{indtl@innote}%
6014             {\unexpanded{\let\index\orig@@index}}%
6015             {}%
6016         \ifbool{indtl@notenumber}%
6017             {\unexpanded{\let\index\orig@@index}}%
6018             {}%
6019         }\to\inserts@list
6020         \global\advance\insert@count \@ne%
6021         \footnoteoptions@{L}{#1}{false}%
6022     \fi
6023 \else
6024     \csuse{v#1footnote}{#1}{{0|0|0|0|0|0|0|0}{#1}}%
6025 \fi%
6026 \endgroup%
6027 \else%
6028     \led@err@FootnoteNotInSecondArgEdtext{#1}%
6029 \fi%
6030 \ignorespaces%
6031 }
6032 %

```

Create counter used to determine on which page the previous note was called.

```

6033 \expandafter\newcount\csname #1prevpage@num\endcsname%
6034 \expandafter\newcount\csname #1prevpage@numR\endcsname%
6035 %

```

We need to be able to modify reledmac's footnote macros and restore their

```

6036 \global\csletcs{#1@@footnote}{#1footnote}
6037 %

```

XXI.3.4 Set standard display

```

6038 \Xarrangement@normal{#1}%
6039 %

```

End of for critical footnotes.

```

6040 \fi
6041 %

```

XXI.4 For familiar footnotes

Familiar footnotes are those which end with letters. We look for the `nofamiliar` option of reledmac.

```

6042 \unless\ifnofamiliar@
6043 %

```

XXI.4.1 Options

```

6044 \newtoggle{parindentX@#1}
6045 \csgdef{wrapcontentX@#1}{}%
6046 \csgdef{hangindentX@#1}{Opt}%
6047 \csgdef{beforeinsertingX@#1}{}%
6048 \csgdef{raggedX@#1}{}%
6049 \csgdef{hsizetwocolX@#1}{0.45 \hsize}%
6050 \csgdef{hsizethreecolX@#1}{.3 \hsize}%
6051 \csgdef{colalignX@#1}{\raggedright}%
6052 \csgdef{notenumfontX@#1}{\normalfont}%
6053 \csgdef{notefontsizeX@#1}{\footnotesize}%
6054 \csgdef{bhooknoteX@#1}{}%
6055 \csgdef{bhookgroupX@#1}{}%
6056 \csgdef{afterruleX@#1}{Opt}
6057 \csgdef{beforenotesX@#1}{1.2em \@plus .6em \@minus .6em}
6058 \csgdef{maxhnotesX@#1}{0.8\vsizex}%
6059 \newtoggle{noteswidthliketwocolumnsX@#1}%
6060 \csgdef{parafootsepX@#1}{}%
6061 \csgdef{afternoteX@#1}{1em plus.4em minus.4em}
6062 \csgdef{widthX@#1}{\hsizex}%
6063 \expandafter\csgdef\innotemarkX@#1##1{\ledinnotemark{##1}}%
6064 \csgdef{txtbeforenotesX@#1}{}%

```

```

6065 \newtoggle{txtbeforenotesX@#1@typeset}%Not directly used by user,
but internal
6066 \newtoggle{txtbeforenotesonlyonceX@#1}%
6067 % End of for familiar footnotes.
6068 % \subsubsection{Create inserts, needed to add notes in foot}
6069 % As regards inserts, see chapter 15 of the TeXBook by D. Knuth.
6070 % \begin{macrocode}
6071 \expandafter\newinsert\csname footins#1\endcsname%
6072 \unless\ifnoledgroup%
6073 \expandafter\newinsert\csname mpfootins#1\endcsname%
6074 \fi%
6075 %

```

XXI.4.2 Create tools for familiar footnotes (\footnoteX)

First, create the \footnoteX command. Note the double # in command: it is because a command is called inside another command.

```

6076 \global\expandafter\newcommand\csname footnote#1\endcsname[2][]{%
6077 \begingroup%
6078 \prepare@prenotesX{#1}%
6079 \newcommand{\content}{#2}%
6080 %
6081 %

```

If we are using the \csquotes package, we reset the quotation level.

```

6082 \ifdefined\csq@qllevel%
6083 \csq@qllevel=0\relax%
6084 \fi%
6085 %

```

If we prepare parallel typesetting, we cannot just increase the footnote counter. Read reledpar's handbook about that (V.1.2 p. 55). If we have a manual footnote mark, use it.

```

6086 \global\expandafter\advance\csname footnote#1@reading\
endcsname by \@ne%
6087 \ifstrempy{#1}{%
6088 \ifboolexpr{bool{l@dpairing} or bool{l@dprintingpages} or
bool{l@dprintingcolumns}}{%
6089 \ifcsdef{footnote#1@reading\the\csname footnote#1@reading
\endcsname=typeset}%
6090 {\setcounter{footnote#1}{\csuse{footnote#1@reading\the\
csname footnote#1@reading\endcsname=typeset}}}%
6091 {\setcounter{footnote#1}{\the\csname footnote#1@reading\
endcsname}}}%
6092 }{%
6093 \stepcounter{footnote#1}%
6094 }%
6095 }{%
6096 %

```

We also have to check consistency with `\onlysideX` setting.

```

6097         \ifledRcol%
6098         \ifcsstring{onlysideX@#1}{L}{\
led@error@note@called@onrightside{footnote#1}}{}%
6099         \else%
6100         \ifcsstring{onlysideX@#1}{R}{\
led@error@note@called@onleftside{footnote#1}}{}%
6101         \fi%
6102 %

```

And now, the feature not depending on whether we prepare parallel typesetting

```

6103         \ifstrempy{##1}%
6104         {\protected@csxdef{@thefnmark#1}{\csuse{thefootnote#1}}}%
6105         {\protected@csxdef{@thefnmark#1}{##1}}%
6106         \nottoggle{nomk@}%Nomk is set to true when using \
footnoteXnomk with \parpackage
6107         {\csuse{@footnotemark#1}}%
6108         {}%
6109         \ifluatex%
6110         \xdef\footnote@luatextextdir{\the\textdir}%
6111         \xdef\footnote@luatexpardir{\the\pardir}%
6112         \fi%
6113         \if@ledgroup%
6114         \led@set@index@fornote{#1}%
6115         \fi%
6116         \csuse{vfootnote#1}{#1}{\expandonce\content}{##1}\
m@mmf@prepare%
6117         \ifbool{indtl@innote}%
6118         {\let\index\orig@@index}%
6119         {}%
6120         \ifbool{indtl@notenumber}%
6121         {\let\index\orig@@index}%
6122         {}%
6123         \endgroup%
6124     }
6125 %

```

Then define the counters. The \LaTeX counter `footnoteX` is the only one manipulated by the user. This is the one which is printed. The \TeX counter `\footnoteX@reading` is increased at each footnote. It is used for hyperlinks, for using `hyperlink` package, and for getting the correct footnote number when using parallel typesetting (V.1.2 p. 55).

```

6126         \newcounter{footnote#1}
6127         \global\expandafter\renewcommand\csname thefootnote#1\endcsname{\
arabic{footnote#1}}
6128         \expandafter\newcount\csname footnote#1@reading\endcsname%
6129 %

```

Create counter used to determine on which page the previous note was called.

```

6130         \expandafter\newcount\csname prevpage#1@num\endcsname%

```

```

6131 \expandafter\newcount\csname prevpage#1@numR\endcsname%
6132 \expandafter\newcount\csname footnote#1@parafootsepX\endcsname%For
the case we use \parafootsepX outside of numbered section
6133 %

Add \let\footnoteX\@gobble to \no@expands.

6134 \expandafter\gappto\expandafter\no@expands\expandafter{\expandafter\
let\csname footnote#1\endcsname\@gobble}%
6135 %

And now, define \footnoteXmark and \footnoteXtext, equivalent to classical \footnotemark
and \footnotetext.

6136 \expandafter\newcommand\csname footnote#1mark\endcsname[1] [] {%
6137 \begingroup%
6138 \prepare@prenotesX{#1}%
6139 \ifstrepty{##1}{%
6140 \stepcounter{footnote#1}%
6141 }{%
6142 \setcounter{footnote#1}{##1}%
6143 }%
6144 \protected@csxdef{@thefnmark#1}{\csuse{thefootnote#1}}%
6145 \csuse{@footnotemark#1}%
6146 \m@mmf@prepare%
6147 \endgroup%
6148 }%
6149 \expandafter\newcommand\csname footnote#1text\endcsname[2] [] {%
6150 \begingroup%
6151 \csuse{vfootnote#1}{#1}{\expandonce{##2}}{##1}%
6152 \endgroup%
6153 }%
6154 %

Do not forget to initialize the series.

6155 \arrangementX@normal{#1}%
6156 \fi
6157 %

```

XXI.5 The endnotes

Endnotes are commands like `\Xendnote`, where `X` is a series letter. First, we check for the `noend` options.

```

6158 \unless\ifnoend@
6159 %

```

XXI.5.1 The auxiliary file

`\l@d@Xend` Endnotes of all varieties are saved up in a file, one by series, typically named `\jobname`. `Xend`.
`\ifl@dend@X` `\l@d@end` is the output stream number for this file, and `\ifl@dend@X` is a flag that is
`\l@dend@Xtrue` true when the file is open.
`\l@dend@Xfalse`

```

6160 \expandafter\newwrite\csname l@d@#1end\endcsname%
6161 \expandafter\newif\csname ifl@dend@#1\endcsname%
6162 %

```

XXI.5.2 The main macro

The `\Xendnote` macro functions to write one endnote to the `.Xend` file. We change `\newlinechar` so that in the file every space becomes the start of a new line; this generally ensures that a long note does not exceed restrictions on the length of lines in files.

```

6163
6164 \global\expandafter\newcommand\csname #1endnote\endcsname[2][1,
usedefault]{%
6165 \bgroup%
6166 \newlinechar='40%
6167 \global\@noneed@Footnotetrue%
6168 \newcommand{\content}{##2}%
6169 \stepcounter{labidx}%
6170 \expandafter\immediate\expandafter\write\csname l@d@#1end\
endcsname{%
6171 \unexpanded{\def\sw@list@inedtext}%
6172 {\expandafter\unexpanded\expandafter{\sw@inthisedtext}}%
6173 \@percentchar\space%Explicit space, to add a linebreak in the
output file
6174 \noexpand\parse@annot\l@current@annot|\@percentchar\space%
6175 \expandafter\string\csname #1end\endcsname%
6176 {\ifnumberedpar@l@d@nums\fi}%
6177 {\ifnumberedpar@\expandonce\@tag\fi}%
6178 {\expandonce\content}%
6179 {\#1}%
6180 {\unexpanded{##1}}%
6181 {\ifledRcol R\else L\fi}%
6182 {\theedtext}%
6183 \@percentchar%
6184 }%
6185 \egroup%
6186 \ignorespaces%
6187 }%
6188 %

```

XXI.5.3 Tools

The `\Xtoendnotes` command inserts any arbitrary content into the endnote file. It is an alias of the more generalist `\addtoendnotes`

```

6189
6190 \global\expandafter\newcommand\csname #1toendnotes\endcsname[1]{%
6191 \toendnotes[#1]{##1}%

```

```

6192 }%
6193
6194 \expandafter\WithSuffix\expandafter\newcommand\csname #1toendnotes\
endcsname*[1]{%
6195     \toendnotes*[#1]{##1}%
6196 }%
6197
6198 %

```

XXI.5.4 Internal commands

\Xendnote commands called \Xend commands on to the endnote file; these are analogous to the various footfmt commands above, and they take the same arguments. When we process this file, we want to pick out the notes of one series and ignore all the rest. To do that, we equate the end command for the series we want to \endprint, and leave the rest equated to \@gobbleseven, which just skips over its seven arguments.

```

6199
6200 \global\cslet{#1end}{\@gobbleseven}
6201 %

```

We need to store the number of times \doendnotesbysection is called for one series.

```

6202 \global\expandafter\newcount\csname #1end@bysection\endcsname%
6203 %

```

XXI.5.5 The options

```

6204 \csgdef{Xendwraplemma@#1}{%
6205 \csgdef{Xendwrapcontent@#1}{}%
6206 \csgdef{Xendtwolines@#1}{}%
6207 \csgdef{Xendmoreethantwolines@#1}{}%
6208 \newtoggle{Xendtwolinesbutnotmore@#1}{}%
6209 \newtoggle{Xendtwolinesonlyinsamepage@#1}{}%
6210 \newtoggle{Xendlemmadisablefontselection@#1}%
6211 \csgdef{Xendnotenumfont@#1}{\normalfont}%
6212 \csgdef{Xendnotefontsize@#1}{\footnotesize}%
6213 \csgdef{Xendbhooknote@#1}{}%
6214
6215 \csgdef{Xendsublinesep@#1}{\fullstop}%
6216
6217 \csgdef{Xendbeforenumber@#1}{0pt}
6218 \csgdef{Xendafternumber@#1}{0.5em}
6219
6220 \csgdef{Xendboxlinenum@#1}{0pt}%
6221 \csgdef{Xendboxlinenumalign@#1}{L}%
6222
6223 \csgdef{Xendboxstartlinenum@#1}{0pt}%
6224 \csgdef{Xendboxendlinenum@#1}{0pt}%

```

```

6225 \csgdef{Xendlemmaseparator@#1}{}%
6226 \csgdef{Xendbeforelemmaseparator@#1}{0em}%
6227 \csgdef{Xendafterlemmaseparator@#1}{0.5em}%
6228 \csgdef{Xendinplaceoflemmaseparator@#1}{0.5em}%
6229
6230
6231 \newtoggle{Xendparagraph@#1}%
6232 \csgdef{Xendafternote@#1}{1em plus.4em minus.4em}%
6233 \csgdef{Xendsep@#1}{}%
6234
6235 \csgdef{Xendinplaceofnumber@#1}{Opt}%
6236 \newtoggle{Xendnonumber@#1}%
6237 \newtoggle{Xendnolinenum@#1}%
6238 \newtoggle{Xendnolinenumifannotation@#1}%
6239
6240 \csgdef{Xendhangindent@#1}{Opt}%
6241
6242 \newtoggle{Xendnumberonlyfirstinline@#1}%
6243 \newtoggle{Xendnumberonlyfirstintwolines@#1}%
6244
6245 \newtoggle{Xendlinenumannotationonlyfirst@#1}%
6246 \newtoggle{Xendlinenumannotationonlyfirstintwo@#1}%
6247
6248 \csgdef{Xendbeforesymlinenum@#1}{\csuse{Xendbeforenumber@#1}}%
6249 \csgdef{Xendaftersymlinenum@#1}{\csuse{Xendafternumber@#1}}%
6250
6251 \csgdef{Xendsymlinenum@#1}{}%
6252 \csgdef{Xendsymlinenumannotation@#1}{}%
6253
6254 \csgdef{Xendboxsymlinenum@#1}{Opt}%
6255
6256 \csgdef{Xendbhooklinenum@#1}{}%
6257 \csgdef{Xendehooklinenum@#1}{}%
6258 \csgdef{Xendbhookinplaceofnumber@#1}{}%
6259 \csgdef{Xendehookinplaceofnumber@#1}{}%
6260
6261 \csgdef{Xendlinerangeseparator@#1}{\endashchar}%
6262
6263 \csgdef{Xendbeforepagenumber@#1}{p.}%
6264 \csgdef{Xendafterpagenumber@#1}{) }%
6265 \csgdef{Xendlineprefixsingle@#1}{}%
6266 \csgdef{Xendlineprefixmore@#1}{}%
6267
6268 \newtoggle{Xendlineflag@#1}
6269
6270 \csgdef{Xendlemmafont@#1}{}%
6271
6272 \csgdef{Xendlinenumannotationposition@#1}{after}%
6273 \csgdef{Xendwraplinenumannotation@#1}{\textsuperscript}%
6274 \newtoggle{Xendnoidenticallinenumannotation@#1}%

```



```

6275 \newtoggle{Xendpagenumberonlyfirst@#1}%
6276 \newtoggle{Xendpagenumberonlyfirstifsingle@#1}%
6277 \newtoggle{Xendpagenumberonlyfirstintwo@#1}%
6278 \csgdef{Xendsympagenum@#1}{}%
6279 \csgdef{Xendinplaceofpagenumber@#1}{Opt}%
6280
6281 \csgdef{Xendtxtbeforenotes@#1}{}%
6282 \newtoggle{Xendfirstnote@#1}%Not a hook, but used to apply
6283 Xendtxtbeforenotes
6284
6285 %

```

End of endnotes declaration

```

6286 \fi%
6287 %

```

Dump series in \@series

```

6288 \listxadd{\@series}{#1}
6289 }
6290 }% End of \newseries
6291 %

```

XXI.6 Init standards series (A,B,C,D,E)

```

6292 \expandafter\newseries\expandafter{\default@series}
6293 %

```

XXII Setting series display

XXII.1 Change series order

\seriesatbegin `\seriesatbegin{<s>}` changes the order of series, to put the series `<s>` at the beginning of the list. The series can be the result of a command.

```

6294 \newcommand{\seriesatbegin}[1]{%
6295   \StrDel{\@series}{#1}[\@series]%
6296   \edef\@new{}%
6297   \listxadd{\@new}{#1}%
6298   \listxadd{\@new}{\@series}%
6299   \xdef\@series{\@new}%
6300 }
6301 %

```

\seriesatend And `\seriesatend` moves the series to the end of the list.

```

6302 \newcommand{\seriesatend}[1]{%
6303   \StrDel{\@series}{#1}[\@series]%
6304   \edef\@new{

```

```

6305 \listeadadd{\@new}{\@series}%
6306 \listeadadd{\@new}{#1}%
6307 \xdef\@series{\@new}%
6308 }
6309 %

```

XXII.2 Test series order

\ifseriesbefore `\ifseriesbefore{<seriesA>}{<seriesB>}{<true>}{<false>}` expands to `<true>` if `<seriesA>` is printed before `<seriesB>`, or to `<false>` otherwise.

```

6310 \newcommand{\ifseriesbefore}[4]{%
6311 \StrPosition{\@series}{#1}[\@first]%
6312 \StrPosition{\@series}{#2}[\@second]%
6313 \ifnumgreater{\@second}{\@first}{#3}{#4}%
6314 }
6315 %

```

XXII.2.1 Get the first series

In some specific case, we need to know the first series of the list of series.

```

\@getfirstseries16 \newcommand{\@getfirstseries}{%
6317 \ifdefempty{\@series}%
6318 {\xdef\@firstseries{}}%
6319 {\StrChar{\@series}{1}[\@firstseries]}%
6320 }%
6321 %

```

XXII.3 Series setting

XXII.3.1 General way of working

The setting's command (like `\numberonlyfirstinline`), also called “hooks” can be divided in two categories: those which require a string values and those which require a boolean value. The first category includes those which require a length value, because we store the length's expression send by user and we evaluate it only in the commands which requires to know the setting. The second category require boolean value only when it is set to FALSE. Otherwise, we understand the insinuated value is TRUE.

For each “hook” command, we store the value in commands (first category) or a `etoolbox`'s toggle (second category) which names are in the form `\<hook>@<series>`. For example, when calling `\twolines{<sq>}`, we store `sq` in commands `\twolines@A`, `\twolines@B`, `\twolines@C`...for each series defined for use with `reledmac`, or, if the `[<series>]` optional argument was send, for each series of this argument.

These values are tested in some specific places, scattered throughout the code, depending on their effects. The default values are defined by the `\newseries@` command.

In order to prevent code duplication, we have created some generic commands. Some of them change the value of any hook send as argument. Some other, getting a hook name, generate the user level commands.

XXII.3.2 Tools to set options

`\settoggle@series` `\settoggle@series{<series>}{<toggle>}{<value>}` is a generic command to switch toggles for some series. The arguments are:

- #1 (mandatory): the series for which the hooks should be set. If empty, all the series will be affected.
- #2 (mandatory): the name of the hook.
- #3 (mandatory): the new value of toggle (true or false).
- #4 (optional): if equal to `reload`, reload the footnote setting (call again `\Xarrangement` or `\arrangementX` or ... depending on the footnote display).
- #5 (optional): if not empty, and if #1 is empty, change the hook setting for pseudo-series, as `appref`.

```

6322 \newcommandx{\settoggle@series}[5][4,5,usedefault]{%
6323   \def\do##1{%
6324     \ifcsdef{etb@tgl@#2@##1}{%
6325       \global\settoggle{#2@##1}{#3}%
6326     }{%
6327       \led@warn@BadHookSeries{##1}{#2}%
6328     }%
6329     \ifstrequal{#4}{critical}{
6330       \csuse{Xarrangement@}\csuse{series@display##1}{##1}%
6331     }{
6332       \ifstrequal{#4}{familiar}{%
6333         \csuse{arrangementX@}\csuse{series@displayX##1}{##1}%
6334       }{%
6335       }%
6336       \ifstreempty{#1}{%
6337         \dolistloop{\@series}%
6338         \ifstreempty{#5}{%
6339           \docsvlist{#5}%
6340         }
6341       }%
6342       {%
6343         \docsvlist{#1}%
6344       }%
6345     }
6346   }%

```

`\setcommand@series` `\setcommand@series{<series>}{<command>}{<value>}` is a generic command to store a hook's value into commands specific to some series. The arguments are:

- #1 (mandatory): the series for which the hooks should be set. If empty, all the series will be affected.
- #2 (mandatory): the name of the hook.
- #3 (mandatory): the new value of the hook/command.
- #4 (optional): if equal to `reload`, reload the footnote setting (call `\footnormal` or `\footparagraph` or ... depending on the footnote display).
- #5 (optional): if not empty, and if #1 is empty, change the hook setting for pseudo-series, as `appref`.
- #6 (optional): the number of arguments of the hook.

```

6347 \newcommandx{\setcommand@series}[6][4,5,6=0,usedefault]{%
6348   \def\do##1{
6349     \ifcsdef{#2@##1}{%
6350       \expandafter\global\expandafter\renewcommand\csname#2@##1\endcsname
6351       [#6]{#3}%
6352     }{%
6353       \led@warn@BadHookSeries{##1}{#2}%
6354     }%
6355     \ifstrequal{#4}{critical}{%
6356       \csuse{Xarrangement@}\csuse{series@display##1}}{##1}%
6357     }{}
6358     \ifstrequal{#4}{familiar}{%
6359       \csuse{arrangementX@}\csuse{series@displayX##1}}{##1}%
6360     }{}%
6361   }%
6362   \ifstreempty{#1}{%
6363     \dolistloop{\@series}%
6364     \ifstreempty{#5}{}%
6365     \docsvlist{#5}
6366   }%
6367   {%
6368     \docsvlist{#1}%
6369   }%
6370 }%
6371 %

```

XXII.3.3 Tools to generate options commands

`\newhookcommand@series` `\newhookcommand@series` `\command` names is a generic command to add new commands for hooks, like `\Xhsizetwocol`. The first argument is the name of the hook, the second a comma-separated list of pseudo-series where the hook can be used, like `appref` in the case of `\Xtwolines`. The second argument is also used to create commands named `\<hookname><pseudoserries>`, like `\Xtwolinesappref`. The third argument

```

6372 \newcommandx{\newhookcommand@series}[3][2,3=0,usedefault]{%
6373   \global\expandafter\newcommand\expandafter*\csname #1\endcsname[2][]{%
6374     \setcommand@series{##1}{#1}{##2}[][#2][#3]%
6375   }%
6376   \ifstrempy{#2}{-}{%
6377     \def\do##1{%
6378       \global\expandafter\newcommand\expandafter*\csname #1##1\endcsname
6379       [1]{%
6380         \csuse{#1}[##1]{####1}%
6381       }%
6382     }%
6383   }%
6384 }
6385 %

```

\newhooktoggle@series \newhooktoggle@series\command names is a generic command to add new commands for a new toggle hook, like \Xnumberonlyfirstinline. The second argument is also used to create commands named \<hookname><pseudoserries>, like \Xtwolinesbutnotmoreappref.

```

6386 \newcommandx{\newhooktoggle@series}[2][2,usedefault]{%
6387   \global\expandafter\newcommandx\expandafter*\csname #1\endcsname[2][1,2={
6388     true},usedefault]{%
6389     \settoggle@series{##1}{#1}{##2}[][#2]%
6390   }%
6391   \ifstrempy{#2}{-}{%
6392     \def\do##1{%
6393       \global\expandafter\newcommand\expandafter*\csname #1##1\endcsname{%
6394         \csuse{#1}[##1]%
6395       }%
6396     }%
6397   }%
6398 }
6399 %

```

\newhooktoggle@series@reload \newhookcommand@toggle@reload does the same thing as \newhooktoggle@series but the commands created by this macro also reload the series arrangement, depending on the type of notes

```

6400 \newcommand{\newhooktoggle@series@reload}[2]{%
6401   \global\expandafter\newcommandx\expandafter*\csname #1\endcsname[2][1,2={
6402     true},usedefault]{%
6403     \settoggle@series{##1}{#1}{##2}[#2]%
6404   }%
6405 }

```

`\newhookcommand@series@reload` `\newhookcommand@series@reload` does the same thing as `\newhookcommand@series` but the commands created by this macro also reload the series' arrangement.

```

6406 \newcommand{\newhookcommand@series@reload}[2]{%
6407   \global\expandafter\newcommand\expandafter*\csname #1\endcsname[2][]{%
6408     \setcommand@series{##1}{#1}{##2}[#2]%
6409   }%
6410 }
6411 %

```

XXII.3.4 Options for critical notes

Before generating the commands that are used to set the critical notes, such as `\Xnumberonlyfirstinline`, `\Xlemmaseparator` and the like, we check the `nocritical` option.

```

6412 \unless\ifnocritical@
6413   \newhookcommand@series{Xwrapcontent}%
6414   \newhookcommand@series{Xbeforeinserting}%
6415   \newhookcommand@series{Xlemmafont}%
6416   \newhookcommand@series{Xwraplemma}%
6417   \newhooktoggle@series{Xparindent}
6418   \newhookcommand@series{Xhangindent}
6419   \newhookcommand@series{Xragged}
6420   \newhookcommand@series{Xhsizetwocol}
6421   \newhookcommand@series{Xhsizethreecol}
6422   \newhookcommand@series{Xcolalign}%
6423   \newhookcommand@series{Xnotenumfont}
6424   \newhookcommand@series{Xbhooknote}
6425   \newhookcommand@series@reload{Xbhookgroup}{critical}
6426   \newhookcommand@series{Xboxsymlinenum}%
6427   \newhookcommand@series{Xsymlinenum}
6428   \newhookcommand@series{Xsymlinenumannotation}%
6429   \newhookcommand@series{Xbeforenumber}
6430   \newhookcommand@series{Xtxtbeforenumber}
6431   \newhookcommand@series{Xafternumber}
6432   \newhookcommand@series{Xbeforesymlinenum}
6433   \newhookcommand@series{Xaftersymlinenum}
6434   \newhookcommand@series{Xinplaceofnumber}
6435   \newhookcommand@series{Xlemmaseparator}
6436   \newhookcommand@series{Xbeforelemmaseparator}
6437   \newhookcommand@series{Xafterlemmaseparator}
6438   \newhookcommand@series{Xinplaceoflemmaseparator}
6439   \newhookcommand@series{Xtxtbeforenotes}
6440   \newhooktoggle@series{Xtxtbeforenotesonlyonce}%
6441   \newhookcommand@series@reload{Xafterrule}{critical}
6442   \newhooktoggle@series{Xnumberonlyfirstinline}
6443   \newhooktoggle@series{Xnumberonlyfirstintwolines}
6444   \newhooktoggle@series{Xlinenumannotationonlyfirst}%
6445   \newhooktoggle@series{Xlinenumannotationonlyfirstintwo}%

```

```

6446 \newhooktoggle@series{Xgroupbyline}%
6447 \newhooktoggle@series{Xgroupbylineseparetwolines}%
6448 \newhooktoggle@series{Xnonumber}
6449 \newhooktoggle@series{Xnolinenumber}%
6450 \newhooktoggle@series{Xnolinenumberifannotation}%
6451
6452 \newhooktoggle@series{Xpstart}
6453 \newhooktoggle@series{Xpstartonlyfirst}%
6454 \newhooktoggle@series{Xpstarteverytime}%
6455 \newhookcommand@series{Xpstartseparator}%
6456
6457 \newhooktoggle@series{Xstanza}%
6458 \newhooktoggle@series{Xstanzaonlyfirst}%
6459 \newhookcommand@series{Xstanzaseparator}%
6460
6461 \newhooktoggle@series{Xonlypstart}
6462 \newhooktoggle@series{Xnonbreakableafternumber}
6463 \newhooktoggle@series{Xlemmadisablefontselection}
6464 \newhookcommand@series@reload{Xmaxhnotes}{critical}
6465 \newhookcommand@series@reload{Xbeforenotes}{critical}
6466 \newhooktoggle@series@reload{Xnoteswidthliketwocolumns}{critical}%
6467 \newhookcommand@series@reload{Xnotefontsize}{critical}
6468
6469 \newhookcommand@series{Xboxlinenum}%
6470 \newhookcommand@series{Xboxlinenumalign}%
6471
6472 \newhookcommand@series{Xboxstartlinenum}%
6473 \newhookcommand@series{Xboxendlinenum}%
6474
6475 \newhookcommand@series{Xafternote}%
6476 \newhookcommand@series{Xparafootsep}
6477 \newhookcommand@series@reload{Xwidth}{critical}%
6478
6479 \newhookcommand@series{Xinnotemark}{[] [1]}%
6480
6481 \ifundef{\Xhsize}%
6482 {%
6483   \newcommandx{\Xhsize}[2][1,usedefault]{%
6484     \led@warning@Xhsize@deprecated%
6485     \Xwidth[#1]{#2}%
6486   }%
6487 }%
6488 {}%
6489 \fi
6490 %

```

Now, hooks for critical notes which also apply to crossreferencing and line numbering at the sides of the page.

```

6491 \newhooktoggle@series{Xlineflag}[appref,SEref]
6492 \newhookcommand@series{Xtwolines}[appref,SEref]

```

```

6493 \newhookcommand@series{Xmorethantwolines}[appref,SEref]
6494 \newhookcommand@series{Xsublinesep}[appref,SEref,side]%
6495 \newhookcommand@series{Xpagelinesep}[appref,SEref,side]%
6496 \newhooktoggle@series{Xtwolinesbutnotmore}[appref,SEref]
6497 \newhooktoggle@series{Xtwolinesonlyinsamepage}[appref,SEref]
6498 \newhookcommand@series{Xlinrangeseparator}[appref,SEref]
6499 \newhookcommand@series{Xlinenumannotationposition}[side,appref,SEref]%
6500 \newhookcommand@series{Xwraplinenumannotation}[side,ref,appref,SEref]%
6501 \newhooktoggle@series{Xnoidenticallinenumannotation}[side,ref,appref,SEref]
6502 %

```

XXII.3.5 Options for familiar notes

Before generating the optional commands for familiar notes, we check the `\nofamiliar` option.

```

6503 \unless\ifnofamiliar@
6504   \newhookcommand@series{wrapcontentX}%
6505   \newhookcommand@series{beforeinsertingX}%
6506   \newhooktoggle@series{parindentX}
6507   \newhookcommand@series{hangindentX}
6508   \newhookcommand@series{raggedX}
6509   \newhookcommand@series{hsize twocolX}
6510   \newhookcommand@series{hsize threecolX}
6511   \newhookcommand@series{colalignX}%
6512   \newhookcommand@series{notenumfontX}
6513   \newhookcommand@series{bhooknoteX}
6514   \newhookcommand@series@reload{bhookgroupX}{familiar}
6515   \newhookcommand@series@reload{beforenotesX}{familiar}
6516   \newhookcommand@series@reload{maxhnotesX}{familiar}
6517   \newhooktoggle@series@reload{noteswidthliketwocolumnsX}{familiar}%
6518   \newhookcommand@series@reload{afterruleX}{familiar}
6519   \newhookcommand@series@reload{notefontsizeX}{familiar}
6520   \newhookcommand@series{afternoteX}
6521   \newhookcommand@series{parafootsepX}
6522   \newhookcommand@series{txtbeforenotesX}%
6523   \newhooktoggle@series{txtbeforenotesonlyonceX}%
6524   \newhookcommand@series@reload{widthX}{familiar}%
6525   \newhookcommand@series{innotemarkX}[] [1]%
6526
6527   \ifundef{\hsizeX}%
6528     {%
6529       \newcommandx{\hsizeX}[2] [1,usedefault]{%
6530         \led@warning@hsizeX@deprecated%
6531         \widthX[#1]{#2}%
6532       }%
6533     }%
6534   {}%
6535 \fi

```


6536 %

XXII.3.6 Options for endnotes

Before generating the commands that are used to set the endnotes, such as `\Xnumberonlyfirstinline`, `\Xlemmaseparator+` and the like, we check the `noend` option.

```

6537 \unless\ifnoend@
6538   \newhookcommand@series{Xendwraplemma}
6539   \newhookcommand@series{Xendwrapcontent}
6540   \newhookcommand@series{Xendnotenumfont}
6541   \newhookcommand@series{Xendlemmafont}%
6542   \newhookcommand@series{Xendbhooknote}
6543
6544   \newhookcommand@series{Xendboxlinenum}%
6545   \newhookcommand@series{Xendboxlinenumalign}%
6546
6547   \newhookcommand@series{Xendboxstartlinenum}%
6548   \newhookcommand@series{Xendboxendlinenum}%
6549
6550   \newhookcommand@series{Xendnotefontsize}
6551   \newhooktoggle@series{Xendlemmadisablefontselection}
6552   \newhookcommand@series{Xendlemmaseparator}
6553   \newhookcommand@series{Xendbeforelemmaseparator}
6554   \newhookcommand@series{Xendafterlemmaseparator}
6555   \newhookcommand@series{Xendinplaceoflemmaseparator}
6556
6557   \newhookcommand@series{Xendbeforenumber}%
6558   \newhookcommand@series{Xendafternumber}%
6559
6560   \newhooktoggle@series{Xendparagraph}
6561   \newhookcommand@series{Xendafternote}
6562   \newhookcommand@series{Xendsep}
6563
6564   \newhookcommand@series{Xendinplaceofnumber}%
6565   \newhooktoggle@series{Xendnonumber}%
6566   \newhooktoggle@series{Xendnolinenum}%
6567   \newhooktoggle@series{Xendnolinenumifannotation}%
6568
6569   \newhooktoggle@series{Xendnumberonlyfirstinline}%
6570   \newhooktoggle@series{Xendnumberonlyfirstintwolines}%
6571
6572   \newhooktoggle@series{Xendlinenumannotationonlyfirst}%
6573   \newhooktoggle@series{Xendlinenumannotationonlyfirstintwo}%
6574
6575   \newhookcommand@series{Xendsymmlinenum}%
6576   \newhookcommand@series{Xendbeforesymmlinenum}%
6577   \newhookcommand@series{Xendaftersymmlinenum}%
6578   \newhookcommand@series{Xendboxsymmlinenum}%
6579

```

```

6580 \newhookcommand@series{Xendsymlinenumannotation}%
6581
6582 \newhookcommand@series{Xendbhooklinenumber}%
6583 \newhookcommand@series{Xendahooklinenumber}%
6584 \newhookcommand@series{Xendbhookinplaceofnumber}%
6585 \newhookcommand@series{Xendahookinplaceofnumber}%
6586
6587 \newhookcommand@series{Xendhangindent}%
6588
6589 \newhooktoggle@series{Xendpagenumberonlyfirst}%
6590 \newhooktoggle@series{Xendpagenumberonlyfirstifsingle}%
6591 \newhooktoggle@series{Xendpagenumberonlyfirstintwo}%
6592 \newhookcommand@series{Xendsympagenum}%
6593 \newhookcommand@series{Xendinplaceofpagenumber}%
6594
6595 \newhookcommand@series{Xendtxtbeforenotes}%
6596
6597 \fi
6598 \newhooktoggle@series{Xendlineflag}[apprefwithpage,SErefwithpage]
6599 \newhookcommand@series{Xendtwwlines}[apprefwithpage,SErefwithpage]
6600 \newhookcommand@series{Xendmoreethantwwlines}[apprefwithpage,SErefwithpage]
6601 \newhooktoggle@series{Xendtwwlinesbutnotmore}[apprefwithpage,SErefwithpage]
6602 \newhooktoggle@series{Xendtwwlinesonlyinsamepage}[apprefwithpage,
SErefwithpage]
6603 \newhookcommand@series{Xendlinerangeseparator}[apprefwithpage,SErefwithpage
]
6604 \newhookcommand@series{Xendbeforepagenumber}[apprefwithpage,SErefwithpage,
SErefonlypage]
6605 \newhookcommand@series{Xendafterpagenumber}[apprefwithpage,SErefwithpage]
6606 \newhookcommand@series{Xendlineprefixsingle}[apprefwithpage,SErefwithpage]
6607 \newhookcommand@series{Xendlineprefixmore}[apprefwithpage,SErefwithpage]
6608 \newhookcommand@series{Xendsublinesep}[apprefwithpage,SErefwithpage]
6609
6610 \newhookcommand@series{Xendlinenumannotationposition}[apprefwithpage,
SErefwithpage]%
6611 \newhookcommand@series{Xendwraplinenumannotation}[apprefwithpage,
SErefwithpage]%
6612 \newhooktoggle@series{Xendnoidenticallylinenumannotation}[apprefwithpage,
SErefwithpage]%
6613 %

```

XXII.4 Hooks for a particular footnote

`\newhooktoggle@specific` `\newhooktoggle@specific` is a generic command to create boolean hook specific to a note.

```

6614 \newcommand{\newhooktoggle@specific}[1]{%
6615   \newtoggle{#1}%
6616   \listgadd{\hooktoggle@specific}{#1}%

```

```

6617 \define@key[mac]{truefootnoteoption}{#1}[]{\global\settoggle{#1@}{true}}%
    When enabling footnote option
6618 \define@key[mac]{falsefootnoteoption}{#1}[]{\global\settoggle{#1@}{false
    }}
6619 }
6620 %

```

`\newhookarg@specific` `\newhookarg@specific` is a generic command to create argumen hook specific to a note.

```

6621 \newcommand{\newhookarg@specific}[1]{%
6622 \listgadd{\hookarg@specific}{#1}%
6623 \define@key[mac]{truefootnoteoption}{#1}{\csgdef{#1@}{##1}}%When enabling
    footnote option
6624 \define@key[mac]{falsefootnoteoption}{#1}{\global\csundef{#1@}}%When
    disabling footnote option
6625 }
6626 %

```

`\hooktoggle@specific` `\hooktoggle@specific` The `\add@hooktoggle@specific@to@cs` macro stores to a macro all the current values of hook toggle specific to a command. It is useful for the `\Xgroupbyline` option, which does not immediately add notes to the inserts list. It uses the `\hooktoggle@specific` list.

```

6627 \def\hooktoggle@specific{%
6628 \newcommand{\add@hooktoggle@specific@to@cs}[1]{%
6629 \def\do##1{%
6630 \iftoggle{##1@}{%
6631 \ifcsdef{#1}{%
6632 \csgappto{#1}{\toggletrue{##1@}}%
6633 }{%
6634 \csgdef{#1}{\toggletrue{##1@}}%
6635 }%
6636 }{%
6637 \ifcsdef{#1}{%
6638 \csgappto{#1}{\togglefalse{##1@}}%
6639 }{%
6640 \csgdef{#1}{\togglefalse{##1@}}%
6641 }%
6642 }%
6643 }%
6644 \dolistloop{\hooktoggle@specific}%
6645 }%
6646 %

```

`\hookarg@specific` `\hookarg@specific` The same, but for optional argument of critical footnotes with assigned value.

```

6647 \def\hookarg@specific{%
6648 \newcommand{\add@hookarg@specific@to@cs}[1]{%
6649 \def\do##1{%

```

```

6650 \ifcsvoid{##1@}{%
6651 \ifcsdef{#1}{%
6652 \csxappto{#1}{%
6653 \noexpand\csdef%
6654 {##1@}{\csname##1@\endcsname}%
6655 }%
6656 }{%
6657 \csxdef{#1}{%
6658 \noexpand\csdef%
6659 {##1@}{\csname##1@\endcsname}%
6660 }%
6661 }%
6662 }%
6663 }%
6664 \dolistloop{\hookarg@specific}%
6665 }%
6666 %

```

And now, we define some hooks specific to a note.

```

6667 \newhooktoggle@specific{fulllines}%
6668 \newhooktoggle@specific{nonum}
6669 \newhooktoggle@specific{nosep}
6670 \newhooktoggle@specific{noprefix}%
6671 \newhooktoggle@specific{prefixmore}%
6672 \newhookarg@specific{linrangesep}
6673 %

```

linrangesep@ \linrangesep@ is defined by the option `linrangesep` of critical notes to change temporarily the line range separator for a specific line. As we have to define it before typesetting the line and undefine it after, we use the family of `xkeyval` package's key.

```

6674 %

```

\nomk@ \nomk@ toggle is used by `reledpar` to remove the footnote mark in the text when using `\footnoteXmk`. Read `reledpar` handbook.

```

6675 \newtoggle{nomk@}%
6676 %

```

XXII.5 Alias

\Xnolemmaseparator \Xnolemmaseparator[*<series>*] is just an alias for `\Xlemmaseparator[<series>]{}`.

```

6677 \newcommandx*{\Xnolemmaseparator}[1][1]{\Xlemmaseparator[#1]{}}
6678 %

```

XXIII Output routine

Now we begin the output routine and associated things.

XXIII.1 Extra footnotes output

With luck we might only have to change `\@makecol` and `\@reinserts` of \LaTeX 's kernel. Since `reledmac`, we use `etoolbox`'s patching commands instead of overriding. It should provides better compatibility with other package which modify these commands

`\l@ddoxtrafeet` `\l@ddoxtrafeet` is the code extending `\@makecol` to cater for the extra `reledmac` feet. We have two categories of extra footnotes. By default, we order the footnote inserts so that the regular footnotes of \LaTeX are first, then familiar familiar footnotes and finally the critical footnotes.

```

6679 \newcommand*{\l@ddoxtrafeet}{%
6680   \IfStrEq{familiar-critical}{\@fnpos}
6681     {\do@feetX\do@Xfeet}%
6682   {%
6683     \IfStrEq{critical-familiar}{\@fnpos}%
6684       {\do@Xfeet\do@feetX}%
6685     {%
6686       \setbox\@outputbox \vbox{%
6687         \unvbox\@outputbox%
6688         \do@feet@custom@order}{\@fnpos}%
6689       }%
6690     }%
6691   }%
6692 }%
6693 %
6694 %

```

`\do@feet@custom@order` `\do@feet@custom@order` is called when `\@fnpos` is neither “familiar-critical”, nor “critical-familiar”, that is, when the order is more complex. In this case, people must define the order for all footnote series. If they don't, \LaTeX could perform an infinite run.

```

6695 \newcommand{\do@feet@custom@order}[2]{%
6696   \def\do##1{%
6697     \edef\@notesseries{\@firstoftwo##1}%
6698     \edef\@notetype{\@secondoftwo##1}%
6699     \ifdefstring{\@notetype}{critical}%
6700       {\csuse{#1append@Xnotes}{\@notesseries}}%
6701       {\ifdefstring{\@notetype}{familiar}%
6702         {\csuse{#1append@notesX}{\@notesseries}}%
6703       }%
6704     }%
6705   }%
6706   \expandafter\docsvlist\expandafter{#2}%
6707 }%
6708 %

```

`\do@Xfeet` `\do@Xfeet` is the code extending `\@makecol` to cater to the extra critical feet.

```

6709 \newcommand*{\do@Xfeet}{%

```

```

6710 \setbox\@outputbox \vbox{%
6711 \unvbox\@outputbox
6712 \@opXfeet}}
6713 %

```

`\@opXfeet` The extra critical feet to be added to the output. . A macro which appends critical notes to the output's routine, also adding vertical space before notes

```

\append@Xnotes
\print@Xnotes
6714 \newcommand{\append@Xnotes}[1]{%
6715 \ifvoid\csuse{#1footins}\else%
6716 \global\skip\csuse{#1footins}=\csuse{Xbeforenotes@#1}%
6717 \global\advance\skip\csuse{#1footins} by\csuse{Xafterterrule@#1}%
6718 \print@Xnotes{#1}%
6719 \fi%
6720 }%
6721 %

```

The normal way to add one series, `\print@Xnotes`, is replaced by `reledpar` when using `\Pages`.

```

6722 \newcommand\print@Xnotes[1]{%
6723 \xdef\@currentseries{#1}%
6724 \csuse{#1footstart}{#1}%
6725 \csuse{#1footgroup}{#1}%
6726 }%
6727 %

```

We print all series of notes by looping on them. We check before printing them that they are not voided.

```

6728 \newcommand*{\@opXfeet}{%
6729 \unless\ifnocritical@%
6730 \gdef\firstXseries@{}%
6731 \def\do##1{%
6732 \append@Xnotes{##1}%
6733 }%
6734 \dolistloop{\@series}%
6735 \fi%
6736 }%
6737 %

```

`\l@ddodoreintrafeet` `\l@ddodoreintrafeet` is the code catering for the extra footnotes within `\@reinserts`. We use the same category and ordering as in `\l@ddoxtrafeet`.

```

6738 \newcommand*{\l@ddodoreintrafeet}{%
6739 \IfStrEq{familiar-critical}{\@fnpos}
6740 {\@doreinfeetX\X@doreinfeet}%
6741 {%
6742 \IfStrEq{critical-familiar}{\@fnpos}%
6743 {\X@doreinfeet\@doreinfeetX}%
6744 {\@doreinfeetX\X@doreinfeet}%

```

```

6745 }%
6746 }
6747
6748 %

```

`\X@doreinfeet` `\X@doreinfeet` is the code for catering for the extra critical footnotes within `\@reinserts`.

```

6749 \newcommand*\X@doreinfeet{%
6750   \unless\ifnocritical@%
6751   \def\do##1{%
6752     \ifvoid\csuse{##1footins}\else%
6753     \insert\csuse{##1footins}{\unvbox\csuse{##1footins}}%
6754     \fi}%
6755   \dolistloop{\@series}
6756   \fi%
6757 }
6758
6759 %

```

`\print@notesX` We have to add all the new kinds of familiar footnotes to the output routine. A macro
`\append@notesX` which appends the familiar footnotes of one series onto the output routine, also adding
`\do@feetX` vertical skip before notes.

```

\@doreinfeetX
6760 \newcommand*\append@notesX[1]{%
6761   \ifvoid\csuse{footins#1}\else%
6762   \global\skip\csuse{footins#1}=\csuse{beforenotesX@#1}%
6763   \global\advance\skip\csuse{footins#1} by\csuse{afterruleX@#1}%
6764   \print@notesX{#1}%
6765   \fi%
6766 }%
6767 %

```

The normal way to print one series of notes. `\print@Xnotes` is replaced by `reledpar` when using `\Pages`.

```

6768 \newcommand\print@notesX[1]{%
6769   \xdef\@currentseries{#1}%
6770   \csuse{footstart#1}{#1}%
6771   \csuse{footgroup#1}{#1}%
6772 }%
6773 %

```

We print all the series of notes by looping over them. We check before printing them that they are not voided.

```

6774 \newcommand*\do@feetX{%
6775   \unless\ifnofamiliar@%
6776   \gdef\firstseriesX@{}%
6777   \setbox\@outputbox \vbox{%
6778     \unvbox\@outputbox%
6779     \def\do##1{%

```

```

6780     \append@notesX{##1}%
6781   }%
6782   \dolistloop{\@series}}%
6783 \fi%
6784 }%
6785
6786 \newcommand{\@doreinfeetX}{%
6787   \unless\ifnofamiliar@%
6788     \def\do##1{%
6789       \ifvoid\csuse{footins##1}\else
6790         \insert%
6791           \csuse{footins##1}
6792           {\unvbox\csuse{footins##1}}%
6793       \fi%
6794     }%
6795     \dolistloop{\@series}%
6796   \fi%
6797 }%
6798
6799 %

```

XXIII.2 Patching standard output's commands

The memoir class does not use the “standard” versions of `\@makecol` and `\@reinserts`, due to its sidebar insert. We had better add that code if memoir is used. (It can be awkward dealing with `\if` code within `\if` code, so don't use `\ifl@dmemoir` here.)

```

6800 \@ifclassloaded{memoir}{%
6801   %
6802   memoir is loaded so we use memoir's built in hooks.
6803   \g@addto@macro{\m@mmdoextrafeet}{\l@dddoextrafeet}%
6804   \g@addto@macro{\m@mmdodoreinextrafeet}{\l@ddodoreinextrafeet}%
6805 }{%
6806   %

```

memoir has not been loaded, so patch `\@makecol` and `\@reinserts`. If the fancyhdr package < version 3.8 has been loaded, we patch the `\latex@makecol` command, because this package redefines the standard `\@makecol` in the preamble to call `\latex@makecol`, which has been `\let` to `\@makecol`. If this package is not loaded, we directly patch `\@makecol`. If the fancyhdr package \geq version 3.8, we also directly patch `\@makecol`, because fancyhdr does its own patch `\AtBeginDocument`.

```

6806   \ifboolexpr{%
6807     test{\@ifpackageloaded{fancyhdr}}%
6808     and test {\ifdef{\latex@makecol}}%
6809   }{%
6810     \patchcmd%
6811       {\latex@makecol}%

```



```

6812     {\xdef\@freelist{\@freelist\@midlist}}}%
6813     {\xdef\@freelist{\@freelist\@midlist}\l@ddoxtrafeet}%
6814     }%
6815     {\led@error@fail@patch@@makecol}%
6816   }{%
6817   \patchcmd%
6818     {\@makecol}%
6819     {\xdef\@freelist{\@freelist\@midlist}}}%
6820     {\xdef\@freelist{\@freelist\@midlist}\l@ddoxtrafeet}%
6821     }%
6822     {\led@error@fail@patch@@makecol}%
6823   }%
6824
6825   \patchcmd%
6826     {\@reinserts}%
6827     {\ifvbox}%
6828     {\l@ddodoreinextrafeet\ifvbox}%
6829     }{%
6830     {\led@error@fail@patch@@reinserts}%
6831   }
6832
6833   %

```

It turns out that `\@doclearpage` also needs modifying.

`\if@led@nofoot` We have to check if there are any leftover feet.

```

6834   \newif\if@led@nofoot
6835
6836   %

```

```

6837   \@ifclassloaded{memoir}{%
6838     %

```

If the memoir class is loaded, we hook into its modified `\@doclearpage`.

```

\@mem@extranofeet 39 \g@addto@macro{\@mem@extranofeet}{%%
6840   \def\do#1{%
6841     \unless\ifnocritical@%
6842       \ifvoid\csuse{#1footins}\else\@mem@nofootfalse\fi%
6843     \fi%
6844     \unless\ifnofamiliar@%
6845       \ifvoid\csuse{footins#1}\else\@mem@nofootfalse\fi%
6846     \fi%
6847   }
6848   \dolistloop{\@series}%
6849 }%
6850 }{%
6851   %

```

As memoir is not loaded we have patch \@doclearpage.

```

\@led@testifnofoot\newcommand*{\@led@testifnofoot}{%
\@doclearpage    \@led@nofoottrue%
6854             \ifvoid\footins\else%
6855                 \@led@nofootfalse%
6856             \fi%
6857             \def\do##1{%
6858                 \unless\ifnocritical@%
6859                     \ifvoid\csuse{###1footins}\else%
6860                         \@led@nofootfalse%
6861                     \fi%
6862                 \fi%
6863                 \unless\ifnofamiliar@%
6864                     \ifvoid\csuse{footins##1}\else%
6865                         \@led@nofootfalse%
6866                     \fi%
6867                 \fi%
6868             }%
6869             \dolistloop{\@series}%
6870         }%
6871
6872     \pretocmd%
6873     {\@doclearpage}%
6874     {\@led@testifnofoot}%
6875     {}%
6876     {\led@error@fail@patch@@doclearpage}%
6877
6878     \patchcmd%
6879     {\@doclearpage}%
6880     {\ifvoid\footins}%
6881     {\if@led@nofoot}%
6882     {}%
6883     {\led@error@fail@patch@@doclearpage}%
6884
6885 }
6886
6887 %

```

XXIV Page numbering in parallel typesetting

The `reledpar` package has two options which change the way page numbering works. We need to implement these options on `reledmac` and not on `reledpar` because they have some consequences for the `reledmac` auxiliary files (numbered file; see V.12 p. 134). The `sameparallelpag number` option allows the same page number on both left and right side. The `prevpgnotnumbered` option allows an empty (not numbered) right-side page before \Pages.

We cannot implement these two options by changing the value of the page counter, since its value is used by many \LaTeX features to determine whether a page is left (even numbered) or right (odd numbered). Consequently, we have to do it by patching `\thepage`, in order to use the value of the `par@page` counter instead of the value of the page counter.

This counter will be increased in a patched version of \LaTeX 's `\@outputpage` macro, as is the page counter in this macro. However, this increase will take account of the options.

`\par@patch@thepage` `\par@patch@thepage` patches `\thepage` in order to use the value of `par@page` counter and not the value of `page`. It must be called after any redefinition of `\thepage`. That is why we insert it at the end of the \LaTeX macro `\pagenumbering`, which is called by some `\xxxmatter` commands. In cases when we are using the memoir class, we insert it at the end of `\@mempnum`. When using `\pagenumbering`, we also need to reset the `par@page` counter. Consequently, we put `\par@patch@thepage` and counter reset in `\par@patch@pagenumbering`. We also call `\par@patch@thepage` at the beginning of the document.

```

6888
6889 \newcommand{\par@patch@thepage}{%
6890   \ifboolexpr{%
6891     bool{sameparallelpagenumber}%
6892     or bool{prevpgnotnumbered}%
6893   }%
6894   {%
6895     \patchcmd{\thepage}%
6896       {page}{par@page}%
6897       {}%
6898       {\led@error@fail@patch@thepage}%
6899   }{}%
6900 }%
6901
6902 \newcommand{\par@patch@pagenumbering}{%
6903   \setcounter{par@page}{1}%
6904   \par@patch@thepage%
6905 }%
6906
6907 \ifldmemoir%
6908   \apptocmd{\@mempnum}%
6909     {\par@patch@pagenumbering}%
6910     {}%
6911     {\led@error@fail@patch@mempnum}%
6912
6913 \else%
6914   \apptocmd{\pagenumbering}%
6915     {\par@patch@pagenumbering}%
6916     {}%
6917     {\led@error@fail@patch@pagenumbering}%
6918 \fi%
```

```

6919 \AtBeginDocument{\par@patch@thepage}%
6920 %
6921 %

```

\@outputpage As its name says, \@outputpage is a \TeX macro called in the output routine. It is this macro which increases the page counter. We patch it in order to increase, conditionally, the par@page counter, and to set correctly the page number sent to the auxiliary files (.1, .2, etc.).

```

6922 \AtBeginDocument{%
6923   \set@this@c@page%
6924   \apptocmd{\@outputpage}{%
6925     \ifsameparallelpagelength%
6926       \ifl@dprintingpages%
6927         \ifodd@c@page\else%
6928           \stepcounter{par@page}%
6929         \fi%
6930       \else%
6931         \stepcounter{par@page}%
6932       \fi%
6933     \else%
6934       \stepcounter{par@page}%
6935     \fi%
6936   }%
6937   {}%
6938   {\led@error@fail@patch@@outputpage}%
6939 }%
6940 \catcode`\# =12%
6941 \AtBeginDocument{%
6942   \apptocmd{\setcounter}{%
6943     \IfStrEq{#1}{page}{\set@this@c@page}{}%
6944   }%
6945   {}%
6946   {\led@error@fail@patch@setcounter}%
6947   \apptocmd{\addtocounter}{%
6948     \IfStrEq{#1}{page}{\set@this@c@page}{}%
6949   }%
6950   {}%
6951   {\led@error@fail@patch@addtocounter}%
6952   \ifpackage{calc}{%
6953     \apptocmd{\stepcounter}{%Because calc.sty does not use addtocounter in
stepcounter
6954       \IfStrEq{#1}{page}{\set@this@c@page}{}%
6955     }%
6956     {}%
6957     {\led@error@fail@patch@steptocounter}%
6958   }{}%
6959 }%
6960 \catcode`\# =6%
6961 %

```

`\thepar@page` The par@page counter.

```
6962 \newcounter{par@page}%
6963 \setcounter{par@page}{1}%
6964 %
```

XXV Cross referencing

You can mark a place in the text using a command of the form `\edlabel{<foo>}`, and later refer to it using the label `<foo>` by typing `\edpageref{<foo>}`, or `\lineref{<foo>}` or `\sublineref{<foo>}` or `\pstartref`. These reference commands will produce, respectively, the page, line sub-line and pstart on which the `\edlabel{<foo>}` command occurred.

The reference macros warn you if a reference is made to an undefined label. If `<foo>` has been used as a label before, the `\edlabel{<foo>}` command will issue a complaint; subsequent `\edpageref` and `\edlineref` commands will refer to the latest occurrence of `\edlabel{<foo>}`.

`\labelref@list` Set up a new list, `\labelref@list`, to hold the page, line and sub-line numbers for each label.

```
6965 \list@create{\labelref@list}
6966 %
```

`\zz@@@` Two convenience macros to zero three / four labeling counters in one go.

```
\zz@@@
6967 \newcommand*\zz@@@{000|000|000}% Set three counters to zero in one go
6968 \newcommand*\zz@@@{000|000|000|000}% Set four counters to zero in one go
6969
6970 %
```

`\edlabel` The `\edlabel` command first writes a `@lab` macro to the `\linenum@out` file. It then checks to see that the `\labelref@list` actually has something in it (if not, it creates a dummy entry), and pops the next value for the current label, storing it in `\label@refs`. Finally it defines the label to be `\empty` so that any future check will turn up the fact that it has been used.³⁶

This version of the original edmac `\label` uses `\@bsphack` and `\@esphack` to eliminate extra space problems and also use the \TeX write methods for the `.aux` file.

Jesse Billett³⁷ found that the original code could be off by several pages. This version, hopefully cures that, and also allows for non-arabic page numbering.

```
6971 \newcommand*\edlabel}[1]{%
6972 \leavevmode%
6973 \@bsphack%
```

³⁶The remaining macros in this section were kindly revised by Wayne Sullivan, who substantially improved their efficiency and flexibility.

³⁷(jdb43@cam.ac.uk) via the ctt thread “ledmac cross referencing”, 25 August 2003.

```

6974 \ifboolexpr{bool{ledRcol} or bool{ledRcol@}}{%
6975   \ifXnote@%
6976     \protected@write\@auxout{%
6977       {\string\l@dmake@labelsR\space\thepage|\l@dparsedstartline|\
l@dparsedstartsub|\annot@start|\the\c@pstartR|{#1}}}%
6978     \ifdef{\hypertarget}%
6979       {\Hy@raisedlink{\hypertarget{#1}{}}}%
6980       {}%
6981     \else%
6982       \write\linenum@outR{\string\@lab}%
6983       \ifx\labelref@listR\empty%
6984         \xdef\label@refs{\zz@@@}%
6985       \else%
6986         \gl@p\labelref@listR\to\label@refs%
6987       \fi%
6988       \ifvmode%
6989         \advancelabel@refs%
6990       \fi%
6991 %

```

Use code from the kernel `\label` command to write the correct page number. Also define an `hypertarget` if `hyperref` package is loaded.

```

6992   \protected@write\@auxout{%
6993     {\string\l@dmake@labelsR\space\thepage|\label@refs|\the\c@pstartR
|{#1}}}%
6994   \ifdef{\hypertarget}%
6995     {\Hy@raisedlink{\hypertarget{#1}{}}}%
6996     {}%
6997   \fi%
6998 }{%
6999   \ifXnote@%
7000     \ifl@dpairing%pstart or pstartL?
7001     \protected@write\@auxout{%
7002       {\string\l@dmake@labelsR\space\thepage|\l@dparsedstartline|\
l@dparsedstartsub|\annot@start|\the\c@pstartL|{#1}}}%
7003       \ifdef{\hypertarget}%
7004         {\Hy@raisedlink{\hypertarget{#1}{}}}%
7005         {}%
7006       \else%
7007         \protected@write\@auxout{%
7008           {\string\l@dmake@labelsR\space\thepage|\l@dparsedstartline|\
l@dparsedstartsub|\annot@start|\the\c@pstart|{#1}}}%
7009           \ifdef{\hypertarget}%
7010             {\Hy@raisedlink{\hypertarget{#1}{}}}%
7011             {}%
7012           \fi%
7013         \else%
7014           \write\linenum@out{\string\@lab}%
7015           \ifx\labelref@list\empty%
7016             \xdef\label@refs{\zz@@@}%

```

```

7017 \else%
7018 \gl@p\labelref@list\to\label@refs%
7019 \fi%
7020 \ifvmode%
7021 \advancelabel@refs%
7022 \fi%
7023 \ifl@dpairing%Pstart or PstartL?
7024 \protected@write\@auxout{}%
7025 {\string\l@dmake@labels\space\thepage|\label@refs|\the\c@pstartL
|{#1}}%
7026 \ifdef{\hypertarget}%
7027 {\Hy@raisedlink{\hypertarget{#1}{}}}%
7028 {}%
7029 \else%
7030 \protected@write\@auxout{}%
7031 {\string\l@dmake@labels\space\thepage|\label@refs|\the\c@pstart
|{#1}}%
7032 \ifdef{\hypertarget}%
7033 {\Hy@raisedlink{\hypertarget{#1}{}}}%
7034 {}%
7035 \fi%
7036 \fi%
7037 }%
7038 \@esphack}%
7039 %
7040 %

```

`\advancelabel@refs` In cases where `\edlabel` is the first element in a paragraph, we have a problem with line counts, because line counts change only at the first horizontal box of the paragraph. Hence, we need to test `\edlabel` if it occurs at the start of a paragraph. To do so, we use `\ifvmode`. If the test is true, we must advance by one unit the amount of text we write into the `.aux` file. We do so with the `\advancelabel@refs` command.

```

7041 \newcounter{line}%
7042 \newcounter{subline}%
7043 \newcounter{absline}%
7044 \newcommand{\advancelabel@refs}{%
7045 \setcounter{line}{\expandafter\labelrefsparseline\label@refs}%
7046 \stepcounter{line}%
7047 \setcounter{absline}{\expandafter\labelrefsparseabsline\label@refs}%
7048 \stepcounter{absline}%
7049 \ifsublines@%
7050 \setcounter{subline}{\expandafter\labelrefsparsesubline\label@refs}%
7051 %
7052 \stepcounter{subline}{1}%
7053 \def\label@refs{\theline|\thesubline|\theabsline}%
7054 \else%
7055 \def\label@refs{\theline|0|\theabsline}%
7056 \fi%
}

```

```

7057 \def\labelrefsparseline#1|#2|#3{#1}%
7058 \def\labelrefsparsesubline#1|#2|#3{#2}%
7059 \def\labelrefsparseabsline#1|#2|#3{#3}%
7060 %

```

\l@dmake@labels The `\l@dmake@labels` macro gets executed when the labels file is read. For each label it defines a macro, whose name is made up partly from the label you supplied, that contains the page, line and sub-line numbers. But first it checks to see whether the label has already been used (and complains if it has).

The initial use of `\newcommand` is to catch if `\l@dmake@labels` has been previously defined (by a class or package).

#1 page number, #2 line number, #3 sub-line number, #4 absolute line number, #5 line number annotation, #6 pstart number, #7 label.

```

7061 \newcommand*{\l@dmake@labels}{%
7062 \def\l@dmake@labels#1|#2|#3|#4|#5|#6|#7{%
7063   \expandafter\ifx\csname the@label\csuse{XR@prefix}#7\endcsname%
7064   \relax%
7065   \else%
7066     \led@warn@DuplicateLabel{\csuse{XR@prefix}#7}%
7067   \fi
7068   \global\providetoggle{label@#7@ledRcol}%False is the default value of
this toggle, which tells us whether a label is linked to the right or left
side
7069   \csgdef{the@label\csuse{XR@prefix}#7}{#1|#2|#3|#4|#5|#6|\relax}%
7070   \ignorespaces}
7071 %
7072 %

```

TeX reads the aux file at both the beginning and end of the document, so we have to switch off duplicate label checking after the first time the file is read.

```

7073 \AtBeginDocument{%
7074   \def\l@dmake@labels#1|#2|#3|#4|#5|#6|#7{%
7075   }
7076 %
7077 %

```

\@lab The `\@lab` command, which appears in the `\linenum@out` file, appends the current value of page, line, sub-line, and absolute line to the `\labelref@list`. These values are defined by the earlier `\@page`, `\@nl`, and the `\sub@on` and `\sub@off` commands appearing in the `\linenum@out` file.

TeX uses the page counter for page numbers. However, it appears that this is not the right place to grab the page number. That task is now done in the `\edlabel` macro. This version of `\@lab` appends just the current line and sub-line numbers to `\labelref@list`.

```

7078 %
7079 \newcommand*{\@lab}{%

```



```

7080 \ifledRcol
7081 \xright@appenditem{\linenumr@p{\line@numR}}|{%
7082 \ifsublines@ \sublinenumr@p{\subline@numR}\else 0\fi|{%
7083 \the\absline@numR|{%
7084 \current@annot%
7085 }%
7086 \to\labelref@listR
7087 \else
7088 \xright@appenditem{%
7089 \linenumr@p{\line@num}}|{%
7090 \ifsublines@ \sublinenumr@p{\subline@num}\else 0\fi|{%
7091 \the\absline@num|{%
7092 \current@annot%
7093 }%
7094 \to\labelref@list
7095 \fi}
7096 %

```

`\apptlabel` `\apptlabel`, if called in `\edtext` will insert automatically both a starting and an ending label for the current edtext lines.

```

7097 \newcommand*{\apptlabel}[1]{%
7098 \if@edtext@secondarg@%
7099 %

```

Label should not be already defined.

```

7100 \ifcsundef{the@label#1}{%
7101 \csdef{the@label#1}{\apptlabel}%
7102 }%
7103 {%
7104 \led@warn@DuplicateLabel{#1 (\apptlabel)}%
7105 }%
7106 %

```

Parse the `\edtext` line numbers and annotations.

```

7107 \expandafter\l@dp@rsefootspec\l@d@nums|{%
7108 \expandafter\parse@annot\l@current@annot|{%
7109 %

```

Use the \TeX standard hack for label.

```

7110 \@bsphack%
7111 %

```

And now, write the data in the auxiliary file.

```

7112 \ifledRcol%
7113 \protected@write\@auxout{}{%
7114 {\string\l@dmake@labelsR\space\l@d@p@rsestartpage|\l@d@p@rsestartline|\l@d@p@rsestartsub|\l@annot@start|\the\c@pstartR|{#1:
start}}}%

```

```

7115     \ifdef{\hypertarget}%
7116         {\Hy@raisedlink{\hypertarget{#1:start}}{}}%
7117         {}%
7118     \protected@write\@auxout{%
7119         {\string\l@dmake@labelsR\space\l@dparsedendpage|\l@dparsedendline
7120         ||\l@dparsedendsub||\annot@end|\the\c@pstartR|{#1:end}}}%
7121     \else%
7122     \ifl@dpairing%pstart or pstartL?
7123     \protected@write\@auxout{%
7124         {\string\l@dmake@labels\space\l@dparsedstartpage|\
7125         l@dparsedstartline|\l@dparsedstartsub||\annot@start|\the\c@pstartL|{#1:
7126         start}}}%
7127     \ifdef{\hypertarget}%
7128         {\Hy@raisedlink{\hypertarget{#1:start}}{}}%
7129         {}%
7130     \protected@write\@auxout{%
7131         {\string\l@dmake@labels\space\l@dparsedendpage|\
7132         l@dparsedendline|\l@dparsedendsub||\annot@end|\the\c@pstartL|{#1:end}}}%
7133     \else%
7134     \protected@write\@auxout{%
7135         {\string\l@dmake@labels\space\l@dparsedstartpage|\
7136         l@dparsedstartline|\l@dparsedstartsub||\annot@start|\the\c@pstartL|{#1:start
7137         }}}%
7138     \fi%
7139     \fi%
7140     %

```

Use the \TeX standard hack for label.

```

7140     \esphack%
7141     %

```

Warning if `\applabel` is called outside of `\edtext`.

```

7142     \else%
7143         \led@warn@AppLabelOutSecondArgEdtext{#1}%
7144     \fi%
7145     %

```

End of `\applabel`

```

7146 }%
7147 %

```

`\edlabelS` `\edlabelS` and `\edlabelE` are just used to mark the beginning and the end of a passage.
`\edlabelE`
`\edlabelSE`

```

7148 \newcommand{\edlabelS}[1]{%
7149   \edlabel{#1:start}%
7150 }
7151 \newcommand{\edlabelE}[1]{%
7152   \edlabel{#1:end}%
7153 }
7154 \newcommand{\edlabelSE}[1]{%
7155   \edlabelS{#1}%
7156   \edlabelE{#1}%
7157 }
7158 %

```

\wrap@edcrossref \wrap@edcrossref is called around all reledmac crossref commands, except those which start with x. It adds the hyperlink.

```

7159 \newrobustcmd{\wrap@edcrossref}[2]{%
7160   \ifdef{\hyperlink}%
7161     {\hyperlink{#1}{#2}}%
7162     {#2}%
7163 }
7164 %

```

\edpageref If the specified label exists, \edpageref gives its page number.

\xpageref For this reference command, as for the other two, a special version with prefix x is provided for use in places where the command is to be scanned as a number, as in \linenum. These special versions have two limitations: they do not print error messages if the reference is unknown, and they can't appear as the first label or reference command in the file; you must ensure that a \edlabel or a normal reference command appears first, or these x-commands will always return zeros.

TeX already defines a \pageref, so changing the name to \edpageref.

```

7165 \newcommand*{\edpageref}[1]{\l@dref@undefined{#1}\wrap@edcrossref{#1}{\l@dgetref@num{1}{#1}}}
7166 \newcommand*{\xpageref}[1]{\l@dgetref@num{1}{#1}}
7167
7168 %

```

\edlineref If the specified label exists, \lineref gives its line number.

\xlineref

```

7169 \newcommand*{\edlineref}[1]{%
7170   \l@dref@undefined{#1}%
7171   \wrap@edcrossref{#1}{%
7172     \providetoggle{label@#1@ledRcol}%Required for the first run, when the
label has not yet been parsed on the .aux file
7173     \iftoggle{label@#1@ledRcol}%
7174       {\linenumrepR{\l@dgetref@num{2}{#1}}}%
7175       {\linenumrep{\l@dgetref@num{2}{#1}}}%
7176     \xflagref{#1}%
7177   }%

```

```

7178 }%
7179 \newcommand*{\xlineref}[1]{\l@getref@num{2}{#1}}%
7180
7181 %

```

\sublineref If the specified label exists, \sublineref gives its sub-line number.

```

\sublineref
7182 \newcommand*{\sublineref}[1]{%
7183   \l@dref@undefined{#1}%
7184   \wrap@edcrossref{#1}{%
7185     \providetoggle{label@#1@ledRcol}%Required for the first run, when the
label has not yet been parsed on the .aux file
7186     \iftoggle{label@#1@ledRcol}%
7187       {\sublinenumrepR{\l@getref@num{3}{#1}}}%
7188       {\sublinenumrep{\l@getref@num{3}{#1}}}%
7189   }%
7190 }%
7191 \newcommand*{\xsublineref}[1]{\l@getref@num{3}{#1}}
7192
7193 %

```

\xabslineref If the specified label exists, \xabslineref gives its absolute line number. This is generally used only by reledmac internal macros.

```

7194 \newcommand*{\xabslineref}[1]{\l@getref@num{4}{#1}}%
7195 %

```

\annotationref If the specified label exists, \edannotationref gives the line number annotation with which it is associated.

```

\annotationref
7196 \newcommand*{\annotationref}[1]{%
7197   \l@dref@undefined{#1}%
7198   \wrap@edcrossref{#1}{%
7199     \l@wrap@ifnotemptybox{\Xwraplinenumannotation@ref}{%
7200       \l@getref@num{5}{#1}%
7201     }%
7202   }%
7203 }%
7204 \newcommand*{\xannotationref}[1]{%
7205   \l@getref@num{5}{#1}%
7206 }%
7207 %

```

\pstartref If the specified label exists, \pstartref gives its pstart number.

```

\pstartref
7208 \newcommand*{\pstartref}[1]{\l@dref@undefined{#1}\wrap@edcrossref{#1}{\l@getref@num{6}{#1}}}%
7209 \newcommand*{\xpstartref}[1]{\l@getref@num{6}{#1}}%
7210
7211 %

```

\xflagref \xflagref finds the side flag of any ref defined with \edlabel.

```
7212 \newcommand*\xflagref}[1]{\l@getref@num{7}{#1}}%
7213 %
```

The next three macros are used by the referencing commands above, and do the job of extracting the right numbers from the label macro that contains the page, line, and sub-line number.

\l@dref@undefined The \l@dref@undefined macro is called when you refer to a label with the normal referencing macros. Its argument is a label, and it just checks that the label has been defined.

```
7214 \newcommand*\l@dref@undefined}[1]{%
7215   \expandafter\ifx\csname the@label#1\endcsname\relax
7216     \led@warn@RefUndefined{#1}%
7217   \fi}
7218 %
7219 %
```

\l@dgetref@num Next, \l@dgetref@num fetches the number we want. It has two arguments: the first is simply a digit, specifying whether to fetch a page (1), line (2), sub-line (3), (4) pstart number or (5) side flag. (This switching is done by calling \l@dlabel@parse.) The second argument is the label-macro, which because of the \@lab macro above is defined to be a string of the type 123|456|789.

```
7220 \newcommand*\l@dgetref@num}[2]{%
7221   \expandafter
7222   \ifx\csname the@label#2\endcsname \relax
7223     000%
7224   \else
7225     \expandafter\expandafter\expandafter
7226     \l@dlabel@parse\csname the@label#2\endcsname|#1%
7227   \fi}
7228 %
7229 %
```

\l@dlabel@parse Notice that we slipped another | delimiter into the penultimate line of \l@dgetref@num, to keep the “switch-number” separate from the reference numbers. This | is used as another parameter delimiter by \l@dlabel@parse, which extracts the appropriate number from its first argument. The |-delimited arguments consist of the expanded label-macro (three reference numbers), followed by the switch-number (1, 2, 3, 4, 5, 6) which defines which of the former seven numbers to extract. (It was given earlier as the first argument of \l@dgetref@num.)

```
7230 \newcommand*\l@dlabel@parse#{%
7231   \def\l@dlabel@parse#1|#2|#3|#4|#5|#6|#7|#8{%
7232     \ifcase #8%
7233     \or #1%
```

```

7234 \or #2%
7235 \or #3%
7236 \or #4%
7237 \or #5%
7238 \or #6%
7239 \or #7%
7240 \fi}
7241 %

```

\xxref The `\xxref` command takes two arguments, both of which are labels, e.g., `\xxref{mouse}{elephant}`. It first does some checking to make sure that the labels do exist (if one does not, those numbers are set to zero). Then it calls `\linenum` and sets the beginning page, line, and sub-line numbers to those of the place where `\label{mouse}` was placed, and the ending numbers to those at `{elephant}`. The point of this is to be able to manufacture footnote line references to passages which cannot be specified in the normal way as the first argument to `\edtext` for one reason or another. Using `\xxref` in the second argument of `\edtext` lets you set things up at least semi-automatically.

```

7242 \newcommand*{\xxref}[2]{%
7243   {%
7244     \expandafter\ifx\csname the@label#1\endcsname\relax%
7245       \let\@tempa\zz@@@%
7246       \def\@tempc{%
7247         \else%
7248         \def\@tempa{%
7249           \l@getref@num{1}{#1}|%
7250           \l@getref@num{2}{#1}|%
7251           \l@getref@num{3}{#1}%
7252         }%
7253         \edef\@tempc{%
7254           \l@getref@num{5}{#1}%
7255         }%
7256       \fi%
7257     \expandafter\ifx\csname the@label#2\endcsname\relax%
7258       \let\@tempb\zz@@@%
7259       \def\@tempd{%
7260         \else%
7261         \def\@tempb{%
7262           \l@getref@num{1}{#2}|%
7263           \l@getref@num{2}{#2}|%
7264           \l@getref@num{3}{#2}%
7265         }%
7266         \edef\@tempd{%
7267           \l@getref@num{5}{#2}%
7268         }%
7269       \fi%
7270     \global\appto\@beforeinsertofthisedtext{%
7271       \def\@this@crossref@start{#1}%
7272     }%

```

```

7273 \global\appto\@beforeinsertofthisedtext{%
7274 \def\@this@crossref@end{#2}%
7275 }%
7276 \linenum{\@tempa|\@tempb}%
7277 \edef\@tempe{\@tempc|\@tempd}%
7278 \expandafter\lineannot\expandafter{\@tempe}%
7279 }%
7280 }%
7281
7282
7283 %

```

`\appref` `\SEref`, `\apprefwithpage`, `\SErefwithpage` and `\SEonlypage` print cross-ref to some start / end lines defined by specific commands. It prints the lines as they should be printed in the apparatus (critical notes for not suffixed versions, endnotes for suffixed versions).

Here we define hooks similar to some those related to critical footnotes or endnotes.

So, first declare the default value of the hooks for the pseudo-series. Also declare the internal toggle which are switch by `reledmac`.

```

7284 \def\Xtwolines@appref{%
7285 \def\Xtwolines@SEref{%
7286
7287 \def\Xmorethantwolines@appref{%
7288 \def\Xmorethantwolines@SEref{%
7289
7290 \def\Xlinerangeseparator@appref{\endashchar}%
7291 \def\Xlinerangeseparator@SEref{\endashchar}%
7292
7293 \def\Xsublinesep@appref{\fullstop}%
7294 \def\Xsublinesep@SEref{\fullstop}%
7295
7296 \def\Xpagelinesep@appref{\fullstop}%
7297 \def\Xpagelinesep@SEref{\fullstop}%
7298
7299
7300 \newtoggle{Xtwolinesbutnotmore@appref}%
7301 \newtoggle{Xtwolinesbutnotmore@SEref}%
7302
7303 \newtoggle{Xtwolinesonlyinsamepage@appref}%
7304
7305 \newtoggle{Xtwolinesonlyinsamepage@SEref}%
7306
7307 \newtoggle{Xlineflag@appref}%
7308 \toggletrue{Xlineflag@appref}%Here exception
7309 \newtoggle{Xlineflag@SEref}%
7310 \toggletrue{Xlineflag@SEref}%%Here exception
7311
7312 \newtoggle{Xlinenumannotationonlyfirst@SEref}%Never changed, just for the
test in \setprintlines

```

```

7313 \newtoggle{Xlinenumannotationonlyfirst@appref}%Idem
7314 \newtoggle{Xnolinenumber@SEref}%Idem
7315 \newtoggle{Xnolinenumber@appref}%Idem
7316 \newtoggle{Xnolinenumberifannotation@SEref}%Idem
7317 \newtoggle{Xnolinenumberifannotation@appref}%Idem
7318
7319
7320 \def\Xlinenumannotationposition@appref{after}%
7321 \def\Xlinenumannotationposition@SEref{after}%
7322
7323 \def\Xwraplinenumannotation@appref{\textsuperscript}%
7324 \def\Xwraplinenumannotation@SEref{\textsuperscript}%
7325 \newtoggle{Xnoidenticallinenumannotation@appref}%
7326 \newtoggle{Xnoidenticallinenumannotation@SEref}%
7327
7328 \def\Xendtwolines@apprefwithpage{}%
7329 \def\Xendtwolines@SErefwithpage{}%
7330
7331 \def\Xendmorethantwolines@apprefwithpage{}%
7332 \def\Xendmorethantwolines@SErefwithpage{}%
7333
7334 \def\Xendlinerangeseparator@apprefwithpage{\endashchar}%
7335 \def\Xendlinerangeseparator@SErefwithpage{\endashchar}%
7336 \def\Xendlinerangeseparator@SErefonlypage{\endashchar}%
7337
7338 \def\Xendbeforepagenumber@apprefwithpage{p.}%
7339 \def\Xendbeforepagenumber@SErefwithpage{p.}%
7340 \def\Xendbeforepagenumber@SEonlypage{p.}%
7341
7342 \def\Xendafterpagenumber@apprefwithpage{} }%
7343 \def\Xendafterpagenumber@SErefwithpage{} }%
7344
7345
7346 \def\Xendlineprefixsingle@apprefwithpage{}%
7347 \def\Xendlineprefixsingle@SErefwithpage{}%
7348
7349 \def\Xendlineprefixmore@apprefwithpage{}%
7350 \def\Xendlineprefixmore@SErefwithpage{}%
7351
7352 \newtoggle{Xendtwolinesbutnotmore@apprefwithpage}%
7353 \newtoggle{Xendtwolinesbutnotmore@SErefwithpage}%
7354
7355 \def\Xendsublinesep@apprefwithpage{\fullstop}%
7356 \def\Xendsublinesep@SErefwithpage{\fullstop}%
7357
7358 \newtoggle{Xendtwolinesonlyinsamepage@apprefwithpage}%
7359 \newtoggle{Xendtwolinesonlyinsamepage@SErefwithpage}%
7360
7361 \newtoggle{Xendlineflag@apprefwithpage}
7362 \toggletrue{Xendlineflag@apprefwithpage}%Here, exception

```



```

7363 \newtoggle{Xendlineflag@SErefwithpage}
7364 \toggletrue{Xendlineflag@SErefwithpage}%Here, exception
7365
7366
7367 \def\Xendlinenumannotationposition@apprefwithpage{after}%
7368 \def\Xendlinenumannotationposition@SErefwithpage{after}%
7369
7370 \def\Xendlinenumannotationposition@apprefwithpage{after}%
7371 \def\Xendlinenumannotationposition@apprefwithpage@SErefwithpage{after}%
7372
7373 \def\Xendwraplinenumannotation@apprefwithpage{\textsuperscript}%
7374 \def\Xendwraplinenumannotation@SErefwithpage{\textsuperscript}%
7375
7376 \newtoggle{Xendnoidenticallinenumannotation@apprefwithpage}%
7377 \newtoggle{Xendnoidenticallinenumannotation@SErefwithpage}%
7378
7379
7380 \newtoggle{Xendnolinenum@SErefwithpage}%Never changed, only for test in
\setprintendlines
7381 \newtoggle{Xendnolinenum@apprefwithpage}%Idem
7382 \newtoggle{Xendnolinenum@ifannotation@SErefwithpage}%Idem
7383 \newtoggle{Xendnolinenum@ifannotation@apprefwithpage}%Idem
7384
7385 %

```

Note that some of these hooks are declared but no user command can change their values. Such hooks are not pertinent for appref and apprefwithpage pseudo-series, but their values are nonetheless tested in some macros.

```

7386
7387 \newtoggle{Xendlinenumannotationonlyfirst@SEref}%Never changed, just for
the test in \setprintendlines
7388 \newtoggle{Xendlinenumannotationonlyfirst@SErefwithpage}%Idem
7389 \newtoggle{Xendlinenumannotationonlyfirst@appref}%Idem
7390 \newtoggle{Xendlinenumannotationonlyfirst@apprefwithpage}%Idem
7391
7392 \gdef\Xboxstartlinenum@appref{Opt}
7393 \gdef\Xboxstartlinenum@SEref{Opt}
7394
7395 \gdef\Xboxendlinenum@appref{Opt}
7396 \gdef\Xboxendlinenum@SEref{Opt}
7397
7398 \gdef\Xendboxstartlinenum@apprefwithpage{Opt}
7399 \gdef\Xendboxstartlinenum@SErefwithpage{Opt}
7400
7401 \gdef\Xendboxendlinenum@apprefwithpage{Opt}
7402 \gdef\Xendboxendlinenum@SErefwithpage{Opt}
7403
7404 \newtoggle{Xendpagenumberonlyfirst@apprefwithpage}
7405 \newtoggle{Xendpagenumberonlyfirst@SErefwithpage}
7406

```

```

7407 \newtoggle{Xendpagenumberonlyfirstifsingle@apprefwithpage}
7408 \newtoggle{Xendpagenumberonlyfirstifsingle@Serefwithpage}
7409
7410 \newtoggle{Xendpagenumberonlyfirstintwo@apprefwithpage}
7411 \newtoggle{Xendpagenumberonlyfirstintwo@Serefwithpage}
7412
7413 \gdef\Xendsympagenum@apprefwithpage{}
7414 \gdef\Xendsympagenum@Serefwithpage{}
7415
7416 \gdef\Xendinplaceofpagenumber@apprefwithpage{}
7417 \gdef\Xendinplaceofpagenumber@Serefwithpage{}
7418
7419 %

```

Now, declare the default values of \@apprefprefixsingle and \@apprefprefixmore, \@Serefprefix, \@Serefprefixmore and the commands which defines them.

```

7420 \newcommand\@apprefprefixsingle{}%
7421 \newcommand\@Serefprefixsingle{}%
7422
7423 \newcommand\@apprefprefixmore{}%
7424 \newcommand\@Serefprefixmore{}%
7425
7426 \newcommand{\setapprefprefixsingle}[1]{%
7427   \gdef\@apprefprefixsingle{#1}%
7428 }
7429 \newcommand{\setSerefprefixsingle}[1]{%
7430   \gdef\@Serefprefixsingle{#1}%
7431 }
7432
7433 \newcommand{\setapprefprefixmore}[1]{%
7434   \gdef\@apprefprefixmore{#1}%
7435 }
7436 \newcommand{\setSerefprefixmore}[1]{%
7437   \gdef\@Serefprefixmore{#1}%
7438 }
7439
7440 %

```

And not \setSerefonlypageprefixsingle and \setSerefonlypageprefixmore.

```

7441 \newcommand{\setSerefonlypageprefixsingle}[1]{%
7442   \gdef\Serefonlypage@prefixsingle{#1}%
7443 }%
7444 \newcommand{\setSerefonlypageprefixmore}[1]{%
7445   \gdef\Serefonlypage@prefixmore{#1}%
7446 }%
7447 %

```

And now, the main commands: \appref, \apprefwithpage, \Seref and \Serefwithpage. These commands call \reformatted@ and \reformattedwithpage, which calls \printlines

and `\printendlines`. That is why we have previously declared all hooks values tested inside these last commands.

```

7448
7449 \newcommandx{\appref}[2][1,usedefault]{\reformatted@{#1}{#2}{appref}}
7450 \newcommandx{\SEref}[2][1,usedefault]{\reformatted@{#1}{#2}{SEref}}
7451
7452 \newcommandx{\apprefwithpage}[2][1,usedefault]{\reformattedwithpage@
7453 {#1}{#2}{appref}}
7454 \newcommandx{\SErefwithpage}[2][1,usedefault]{\reformattedwithpage@
7455 {#1}{#2}{SEref}}
7456
7457 \newcommand{\reformatted@}[3]{%
7458   \def\do##1{%
7459     \setkeys[mac]{truefootnoteoption}{##1}%
7460   }%
7461   \notblank{#1}{\docsvlist{#1}}{%
7462     \xdef\@currentseries{#3}%
7463     \iftoggle{noprefix@}{%
7464       {%
7465         \ifcsemt{#3}prefixmore}%
7466         {\@apprefprefixsingle}%
7467       }%
7468       \IfEq{\xlineref{#2:start}}{\xlineref{#2:end}}{%
7469         {\iftoggle{prefixmore@}%
7470          {\csuse{#3}prefixmore}}%
7471          {\csuse{#3}prefixsingle}}%
7472       }%
7473       {\csuse{#3}prefixmore}}%
7474     }%
7475   }%
7476   \ifboolexpr{%
7477     test{\ifcsundef{the@label#2:start}}%
7478     or test{\ifcsundef{the@label#2:end}}%
7479   }%
7480   {\led@warn@pairRefUndefined{#2}\nfss@text{\reset@font\bfseries ??}}%
7481   {%
7482     \def\@this@crossref@start{#2:start}%
7483     \def\@this@crossref@end{#2:end}%
7484     \xdef\annot@start{\xannotationref{#2:start}}%
7485     \xdef\annot@end{\xannotationref{#2:end}}%
7486     \printlines\xpageref{#2:start}|\xlineref{#2:start}|\xsublineref{#2:
start}|\xpageref{#2:end}|\xlineref{#2:end}|\xsublineref{#2:end}|\relax|\
xflagref{#2:start}|\%
7487   }%
7488   \def\do##1{%
7489     \setkeys[mac]{falsefootnoteoption}{##1}%

```

```

7490 }%
7491 \notblank{#1}{\docsvlist{#1}}{}%
7492 }%
7493
7494 \newcommand{\reformattedwithpage@}[3]{%
7495   \def\do##1{%
7496     \setkeys[mac]{truefootnoteoption}{##1}%
7497   }%
7498   \notblank{#1}{\docsvlist{#1}}{}%
7499   \xdef\@currentseries{#3withpage}%
7500   \ifboolexpr{%
7501     test{\ifcsundef{the@label#2:start}}%
7502     or test{\ifcsundef{the@label#2:end}}%
7503   }%
7504   {\led@warn@pairRefUndefined{#2}\nfss@text{\reset@font\bfseries ??}}%
7505   {%
7506     \def\@this@crossref@start{#2:start}%
7507     \def\@this@crossref@end{#2:end}%
7508     \xdef\annot@start{\xannotationref{#2:start}}%
7509     \xdef\annot@end{\xannotationref{#2:end}}%
7510     \printendlines\xpageref{#2:start}|\xlineref{#2:start}|\xsublineref{#2:
start}|\xpageref{#2:end}|\xlineref{#2:end}|\xsublineref{#2:end}|\relax\
xflagref{#2:start}}%
7511   }%
7512   \def\do##1{%
7513     \setkeys[mac]{falsefootnoteoption}{##1}%
7514   }%
7515   \notblank{#1}{\docsvlist{#1}}{}%
7516 }%
7517
7518 \newcommand{\reformattedonlypage@}[3]{%
7519   \def\do##1{%
7520     \setkeys[mac]{truefootnoteoption}{##1}%
7521   }%
7522   \notblank{#1}{\docsvlist{#1}}{}%
7523   \xdef\@currentseries{#3onlypage}%
7524   \ifboolexpr{%
7525     test{\ifcsundef{the@label#2:start}}%
7526     or test{\ifcsundef{the@label#2:end}}%
7527   }%
7528   {\led@warn@pairRefUndefined{#2}\nfss@text{\reset@font\bfseries ??}}%
7529   {\ifnumequal{\xpageref{#2:end}}{\xpageref{#2:start}}%
7530     {%
7531       \ifcsvoid{#3onlypage@prefixsingle}%
7532       {}%
7533       {\csletcs{Xendbeforepagenumber@#3onlypage}{#3onlypage@prefixsingle
}}%
7534       \printnpnum{%
7535         \wrap@edcrossref{#2:start}{\xpageref{#2:start}}%
7536       }%

```

```

7537 }%
7538 {%
7539   \ifcsvoid{#3onlypage@prefixmore}%
7540   {%
7541     {\csletcs{Xendbeforepagenumber@#3onlypage}{#3onlypage@prefixmore}}%
7542     \ifdefined\linangesep%
7543       \printnpnum{%
7544         \wrap@edcrossref{#2:start}{\xpageref{#2:start}}%
7545         \linangesep%
7546         \wrap@edcrossref{#2:end}{\xpageref{#2:end}}%
7547       }%
7548     \else%
7549       \printnpnum{%
7550         \wrap@edcrossref{#2:start}{\xpageref{#2:start}}%
7551         \csuse{Xendlinangeseparator@%currentseries}%
7552         \wrap@edcrossref{#2:end}{\xpageref{#2:end}}%
7553       }%
7554     \fi%
7555   }%
7556 }%
7557 \def\do##1{%
7558   \setkeys[mac]{falsefootnoteoption}{##1}%
7559 }%
7560 \notblank{#1}{\docsvlist{#1}}{%
7561 }%
7562 %

```

\edmakelabel Sometimes the `\edlabel` command cannot be used to specify exactly the page and line desired; you can use the `\edmakelabel` macro make your own label. For example, if you insert `\edmakelabel{elephant}{10|25|0}` you will have created a new label, and a later call to `\edpageref{elephant}` would print “10” and `\lineref{elephant}` would print “25”. The sub-line number here is zero. `\edmakelabel` takes a label, followed by a page and a line number(s) as arguments. \TeX defines a `\makelabel` macro which is used in lists. Peter Wilson has changed the name to `\edmakelabel`.

```

7563 \newcommand*{\edmakelabel}[2]{\expandafter\def\csname the@label#1\
7564   endcsname{#2}}
7565 %

```

(If you are only going to refer to such a label using `\xxref`, then you can omit entries in the same way as with `\linenum` (see VI.3 p. 149 and V.9 p. 113), since `\xxref` makes a call to `\linenum` in order to do its work.)

XXV.1 Compatibility with xref

Here, we provide compatibility with the `xref` to enable `reledmac`’s cross-referencing to external documents. We assume that the user loads `xref` *before* `reledmac`, but uses `\externaldocument` *after* loading `reledmac`.

`\XR@test` First, we patch the `xr` macro `\XR@test`, which is called on every line of the external `.aux` file, in order to also call macros specific to `reledmac`.

```
7566 \pretocmd{\XR@test}%
7567   {\XR@test@mac+++#1#2#3#4+++}%
7568   {}%
7569   {}%
7570 %
```

`\XR@test@mac` The `\XR@test@mac` takes the full content of a line of the external `.aux` files, with the three final dots added by `xr`.

```
7571 \long\def\xR@test@mac+++#1+++{\XR@test@mac@test#1}
7572 %
```

`\XR@test@mac@test` And finally, `\XR@test@mac@test` does the job. This code is based on the `\XR@test` macro of the `xr` package. However, note that the `\XR@prefix` is not called here, but it is integrated directly in `\l@dmake@labels` and `\l@dmake@labelsR`.

```
7573 \long\def\xR@test@mac@test#1#2...{%The triple dots (NOT \ldots) are because
of the line 22 of xr.sty v5.02 1994/05/28
7574   \ifx#1\l@dmake@labels%
7575     \l@dmake@labels#2%
7576   \else
7577     \ifx#1\l@dmake@labelsR%
7578       \l@dmake@labelsR #2%
7579     \fi%
7580   \fi%
7581 }%
7582 %
```

XXVI Sidenotes

Regular `\marginpars` do not work inside numbered text — they do not produce any note but do put an extra unnumbered blank line into the text.

`\@xympar` Changing `\@xympar` a little at least ensures that `\marginpars` in numbered text do not disturb the flow.

```
7583 \pretocmd{\@xympar}%
7584   {\ifnumberedpar@
7585     \led@warn@NoMarginpars
7586     \@esphack
7587   \else}%
7588   {}%
7589   {}%
7590
7591 \apptocmd{\@xympar}%
7592   {\fi}%
```

```

7593 {}
7594 {}
7595
7596 %

```

We provide sidenotes as replacement for `\marginpar` in numbered text.

`\sidenote@margin` These are the sidenote equivalents to `\line@margin` and `\linenummargin` for specifying which margin. The default is the right margin (opposite to the default for line numbers). `\l@dgetsidenote@margin` returns the number associated to sidenote margin:

left: 0

right: 1

outer: 2

inner: 3

```

7597 \newcount\sidenote@margin
7598 \newcommand*{\sidenotemargin}[1]{\%
7599   \l@dgetsidenote@margin{#1}%
7600   \ifnum\@l@tempcntb>\m@ne
7601     \ifledRcol
7602       \global\sidenote@marginR=\@l@tempcntb
7603     \else
7604       \global\sidenote@margin=\@l@tempcntb
7605     \fi
7606   \fi}}
7607 \newcommand*{\l@dgetsidenote@margin}[1]{\%
7608   \def\@tempa{#1}\def\@tempb{left}%
7609   \ifx\@tempa\@tempb
7610     \@l@tempcntb \z@
7611   \else
7612     \def\@tempb{right}%
7613     \ifx\@tempa\@tempb
7614       \@l@tempcntb \@ne
7615     \else
7616       \def\@tempb{outer}%
7617       \ifx\@tempa\@tempb
7618         \@l@tempcntb \tw@
7619       \else
7620         \def\@tempb{inner}%
7621         \ifx\@tempa\@tempb
7622           \@l@tempcntb \thr@@
7623         \else
7624           \led@warn@BadSidenotemargin
7625           \@l@tempcntb \m@ne
7626         \fi

```

```

7627     \fi
7628     \fi
7629     \fi}
7630 \sidenotemargin{right}
7631
7632 %

```

`\l@dlp@rbox` We need two boxes to store sidenote texts.

```

\l@drp@rbox
7633 \newbox\l@dlp@rbox
7634 \newbox\l@drp@rbox
7635
7636 %

```

`\ledlsnotewidth` These specify the width of the left/right boxes (initialised to `\marginparwidth`), their distance from the text (initialised to `\linenumsep`), and the fonts used.

```

\ledrsnotewidth
\ledlsnotesep
7637 \newdimen\ledlsnotewidth \ledlsnotewidth=\marginparwidth
\ledrsnotesep
7638 \newdimen\ledrsnotewidth \ledrsnotewidth=\marginparwidth
\ledlsnotefontsetup
7639 \newdimen\ledlsnotesep \ledlsnotesep=\linenumsep
\ledrsnotefontsetup
7640 \newdimen\ledrsnotesep \ledrsnotesep=\linenumsep
7641 \newcommand*{\ledlsnotefontsetup}{\raggedleft\footnotesize}
7642 \newcommand*{\ledrsnotefontsetup}{\raggedright\footnotesize}
7643
7644 %

```

`\ledleftnote` `\ledleftnote`, `\ledrightnote`, `\ledinnernote`, `\ledouternote` are the user commands for left, right, inner and outer sidenotes. The two last ones are just alias for the two first ones, depending on the page number. `\ledsidenote{<text>}` is the command for a moveable sidenote.

```

\ledsidenote
7645 \newcommand*{\ledleftnote}[1]{\edtext{}{\l@dlsnote{#1}}}
7646 \newcommand*{\ledrightnote}[1]{\edtext{}{\l@drsnote{#1}}}
7647 \newcommand*{\ledsidenote}[1]{\edtext{}{\l@dcsnote{#1}}}%
7648 \newcommand*{\ledinnernote}[1]{\edtext{}{\l@disnote{#1}}}%
7649 \newcommand*{\ledouternote}[1]{\edtext{}{\l@dosnote{#1}}}%
7650 %

```

`\l@dlsnote` . The “footnotes” for left, right, and moveable sidenotes. The whole scheme is reminiscent of the critical footnotes code.

```

\l@drsnote
\l@dcsnote
7651 \newif\ifrighnoteup
\l@desnote
7652 \righnoteuptrue
\l@disnote
7653
7654 \newcommand*{\l@dlsnote}[1]{%
7655     \begingroup%
7656     \newcommand{\content}{#1}%
7657     \ifnumberedpar@
7658     \ifledRcol%
7659     \xright@appenditem{\noexpand\l@dlsnote{\expandonce\content}}%

```



```

7660         \to\inserts@listR
7661     \global\advance\insert@countR \@ne%
7662 \else%
7663     \xright@appenditem{\noexpand\vl@dlsnote{\expandonce\content}}}%
7664         \to\inserts@list
7665     \global\advance\insert@count \@ne%
7666 \fi
7667 \fi%
7668 \ignorespaces%
7669 \endgroup%
7670 }%
7671
7672 \newcommand*{\l@drsnote}[1]{%
7673     \begingroup%
7674     \newcommand{\content}{#1}%
7675     \ifnumberedpar@
7676     \ifledRcol%
7677         \xright@appenditem{\noexpand\vl@drsnote{\expandonce\content}}}%
7678             \to\inserts@listR
7679         \global\advance\insert@countR \@ne%
7680     \else%
7681         \xright@appenditem{\noexpand\vl@drsnote{\expandonce\content}}}%
7682             \to\inserts@list
7683         \global\advance\insert@count \@ne%
7684     \fi
7685     \fi\ignorespaces%
7686 \endgroup%
7687 }%
7688
7689 \newcommand*{\l@dcsnote}[1]{%
7690     \begingroup%
7691     \newcommand{\content}{#1}%
7692     \ifnumberedpar@
7693     \ifledRcol%
7694         \xright@appenditem{\noexpand\vl@dcsnote{\expandonce\content}}}%
7695             \to\inserts@listR
7696         \global\advance\insert@countR \@ne%
7697     \else%
7698         \xright@appenditem{\noexpand\vl@dcsnote{\expandonce\content}}}%
7699             \to\inserts@list
7700         \global\advance\insert@count \@ne%
7701     \fi
7702     \fi\ignorespaces%
7703 \endgroup%
7704 }%
7705
7706 \newcommand*{\l@disnote}[1]{%
7707     \begingroup%
7708     \newcommand{\content}{#1}%
7709     \ifnumberedpar@

```

```

7710 \ifledRcol%
7711 \xright@appenditem{\noexpand\vl@disnote{\expandonce\content}}}%
7712 \to\inserts@listR%
7713 \global\advance\insert@countR \@ne%
7714 \else%
7715 \xright@appenditem{\noexpand\vl@disnote{\expandonce\content}}}%
7716 \to\inserts@list%
7717 \global\advance\insert@count \@ne%
7718 \fi%
7719 \fi\ignorespaces%
7720 \endgroup%
7721 }%
7722
7723 \newcommand*{\l@dosnote}[1]{%
7724 \begingroup%
7725 \newcommand{\content}{#1}%
7726 \ifnumberedpar%
7727 \ifledRcol%
7728 \xright@appenditem{\noexpand\vl@dosnote{\expandonce\content}}}%
7729 \to\inserts@listR%
7730 \global\advance\insert@countR \@ne%
7731 \else%
7732 \xright@appenditem{\noexpand\vl@dosnote{\expandonce\content}}}%
7733 \to\inserts@list%
7734 \global\advance\insert@count \@ne%
7735 \fi%
7736 \fi\ignorespaces%
7737 \endgroup%
7738 }%
7739
7740 %

```

\vl@dlsnote Put the left/right text into boxes, but just save the moveable text. **\l@dcsnotetext**, **\vl@drsnote** **\l@dcsnotetext@l** and **\l@dcsnotetext@r** are etoolbox's lists which will store the content of sidenotes. We store the content in lists, because we need to loop later on them, in case many sidenote co-exist for the same line. That is there some special test **\vl@disnote** to do, in order to:

- Store the content of **\ledsidenote** to **\l@dcsnotetext** in any cases.
- Store the content of **\rightsidenote** to:
 - **\l@dcsnotetext** if **\ledsidenote** is to be put on right.
 - **\l@dcsnotetext@r** if **\ledsidenote** is to be put on left.
- Store the content of **\leftsidenote** to:
 - **\l@dcsnotetext** if **\ledsidenote** is to be put on left.
 - **\l@dcsnotetext@l** if **\ledsidenote** is to be put on right.

`\vl@disnote` and `\vl@dosnote` just call `\vl@dlsnote` or `\vl@drsnote`, depending on the page.

```

7741 \newcommand*{\vl@dlsnote}[1]{%
7742   \ifledRcol{%
7743     \@l@tempcntb=\sidenote@marginR%
7744     \ifnum\@l@tempcntb>\@ne%
7745       \advance\@l@tempcntb by\page@numR%
7746     \fi%
7747   \else%
7748     \@l@tempcntb=\sidenote@margin%
7749     \ifnum\@l@tempcntb>\@ne%
7750       \advance\@l@tempcntb by\page@num%
7751     \fi%
7752   \fi%
7753   \ifodd\@l@tempcntb%
7754     \listgadd{\l@dcsnotetext@l}{#1}%
7755   \else%
7756     \listgadd{\l@dcsnotetext}{#1}%
7757   \fi
7758 }
7759 \newcommand*{\vl@drsnote}[1]{%
7760   \ifledRcol{%
7761     \@l@tempcntb=\sidenote@marginR%
7762     \ifnum\@l@tempcntb>\@ne%
7763       \advance\@l@tempcntb by\page@numR%
7764     \fi%
7765   \else%
7766     \@l@tempcntb=\sidenote@margin%
7767     \ifnum\@l@tempcntb>\@ne%
7768       \advance\@l@tempcntb by\page@num%
7769     \fi%
7770   \fi%
7771   \ifodd\@l@tempcntb%
7772     \listgadd{\l@dcsnotetext}{#1}%
7773   \else%
7774     \listgadd{\l@dcsnotetext@r}{#1}%
7775   \fi%
7776 }
7777 \newcommand*{\vl@dcsnote}[1]{\listgadd{\l@dcsnotetext}{#1}}
7778
7779 \newcommand{\vl@disnote}[1]{%
7780   \ifledRcol{%
7781     \@tempcnta=\page@numR%
7782   \else%
7783     \@tempcnta=\page@num%
7784   \fi%
7785   \ifodd\@tempcnta% ODD => right page => inner side = left side
7786     \vl@dlsnote{#1}%
7787   \else%

```

```

7788 \vl@drsnote{#1}%
7789 \fi%
7790 }%
7791
7792 \newcommand{\vl@dosnote}[1]{%
7793 \ifledRcol%
7794 \@tempcnta=\page@numR%
7795 \else%
7796 \@tempcnta=\page@num%
7797 \fi%
7798 \ifodd\@tempcnta% ODD => right page => outer side = right side
7799 \vl@drsnote{#1}%
7800 \else%
7801 \vl@dlsnote{#1}%
7802 \fi%
7803 }%
7804
7805 %

```

`\setl@dlp@rbox` `\setl@dlprbox{<lednums>}{<tag>}{<text>}` puts `<text>` into the `\l@dlp@rbox` box. And similarly for the right side box. It is these boxes that finally get displayed in the margins.

```

7806 \newcommand*{\setl@dlp@rbox}[1]{%
7807 \begingroup%
7808 \parindent\z@\hsize=\ledlsnotewidth%
7809 \ledlsnotefontsetup%We kept it outside of the vbox, because can affect
the ragging
7810 \global\setbox\l@dlp@rbox%
7811 \ifleftnoteup%
7812 =\vbox to\z@{\{\ledlsnotefontsetup\vss #1\}}%We put \
ledlsnotefontsetup inside footnote because required for color command. Note
the {} to keep setting local.
7813 \else%
7814 =\vbox to 0.70\baselineskip{\{\ledlsnotefontsetup\strut#1\vss\}}%
7815 \fi%
7816 \endgroup%
7817 }
7818
7819 \newcommand*{\setl@drp@rbox}[1]{%
7820 \begingroup%
7821 \parindent\z@\hsize=\ledrsnotewidth%
7822 \ledrsnotefontsetup%We kept it outside of the vbox, because can affect
the ragging
7823 \global\setbox\l@drp@rbox%
7824 \ifrightrightnoteup%
7825 =\vbox to\z@{\{\ledrsnotefontsetup\vss#1\}}%We put \ledrsnotefontsetup
inside footnote because required for color command. Note the {} to keep
setting local.
7826 \else%

```

```

7827     =\vbox to0.7\baselineskip{{\ledrsnotefontsetup\strut#1\vss}}}%
7828     \fi%
7829     \endgroup%
7830 }%
7831 \newif\ifleftnoteup
7832 \leftnoteuptrue
7833 %

```

\@sidenoteseq This macro is used to separate sidenotes of the same line.

```

7834 \newcommand{\setsidenoteseq}[1]{\gdef\@sidenoteseq{#1}}
7835 \newcommand{\@sidenoteseq}{, }
7836 %

```

\affixside@note This macro puts any moveable sidenote text into the left or right sidenote box, depending on which margin it is meant to go in. It's a very much stripped down version of `\affixline@num`.

Before do it, we concatenate all moveable sidenotes of the line, using `\@sidenoteseq` as separator. It is the result that we put on the sidenote.

```

7837 \newcommand*{\affixside@note}{%
7838     \prepare@edindex@for@note{\the\page@num|\the\line@num|\the\subline@num|\
7839     the\page@num|\the\line@num|\the\subline@num|}%
7840     \def\sidenotecontent@{}%
7841     \numgdef{\itemcount@}{0}%
7842     \def\do##1{%
7843         \ifnumequal{\itemcount@}{0}%
7844             {%
7845                 \appto\sidenotecontent@{##1}}% Not print not separator before
7846                 the 1st note
7847                 \appto\sidenotecontent@{\@sidenoteseq ##1}%
7848             }%
7849             \numgdef{\itemcount@}{\itemcount@+\@ne}%
7850     }%
7851     \dolistloop{\l@dcnotesetext}%
7852     \ifnumgreater{\itemcount@}{1}{\led@err@ManySidenotes}{}%
7853 %

```

And we do the same for left and right notes (not movable).

```

7852 \gdef\@templ@d{%
7853 \gdef\@templ@n{\l@dcnotesetext\l@dcnotesetext@l\l@dcnotesetext@r}%
7854 \ifx\@templ@d\@templ@n \else%
7855     \if@twocolumn%
7856         \if@firstcolumn%
7857             \setl@dlp@rbox{##1}{\sidenotecontent@}%
7858         \else%
7859             \setl@drp@rbox{\sidenotecontent@}%
7860         \fi%
7861     \else%

```

```

7862 \l@dtempcntb=\sidenote@margin%
7863 \ifnum\l@dtempcntb>\@ne%
7864 \advance\l@dtempcntb by\page@num%
7865 \fi%
7866 \ifodd\l@dtempcntb%
7867 \setl@drp@rbox{\sidenotecontent@}%
7868 \gdef\sidenotecontent@{}%
7869 \numgdef\itemcount@{0}%
7870 \dolistloop{\l@dcsnotetext@l}%
7871 \ifnumgreater\itemcount@{1}{\led@err@ManyLeftnotes}{}%
7872 \setl@dlp@rbox{\sidenotecontent@}%
7873 \else%
7874 \setl@dlp@rbox{\sidenotecontent@}%
7875 \gdef\sidenotecontent@{}%
7876 \numgdef\itemcount@{0}%
7877 \dolistloop{\l@dcsnotetext@r}%
7878 \ifnumgreater\itemcount@{1}{\led@err@ManyRightnotes}{}%
7879 \setl@drp@rbox{\sidenotecontent@}%
7880 \fi%
7881 \fi%
7882 \fi%
7883 \advance\@edindex@fornote@m@ne%
7884 }
7885 %

```

XXVII Minipages and such

We can put footnotes into minipages. The preparatory code has been set up earlier, all that remains is to ensure that it is available inside a minipage box. This requires some alteration to the kernel code, specifically the `\@iiminipage` and `\endminipage` macros. We will arrange this so that additional series can be easily added.

`\l@dfeetbeginmini` These will be the hooks in `\@iiminipage` and `\endminipage`.
`\l@dfeetendmini` They can be extended to handle other things if necessary.

```

7886 \ifnoledgroup@else%
7887 \newcommand*{\l@dfeetbeginmini}{\@ledgrouptrue\l@dedbeginmini\l@dfambeginmini}
7888 \newcommand*{\l@dfeetendmini}{%
7889 \IfStrEq{critical-familiar}{\@mpfnpos}%
7890 {\l@dedendmini\l@dfamendmini}%
7891 {%
7892 \IfStrEq{familiar-critical}{\@mpfnpos}%
7893 {\l@dfamendmini\l@dedendmini}%
7894 {\do@feet@custom@order{mp@}{\@mpfnpos}}}%
7895 }%
7896 }%
7897 %

```

`\l@dedbeginmini` These handle the initiation and closure of critical footnotes in a minipage environment.

`\l@dedendmini`

`\mp@append@Xnotes`

```

7898 \newcommand*\l@dedbeginmini}{%
7899   \unless\ifnocritical{%
7900     \def\do##1{%
7901       \csletcs{v##1footnote}{mpv##1footnote}%
7902     }%
7903     \dolistloop{\@series}%
7904   \fi%
7905 }
7906 \newcommand*\l@dedendmini}{%
7907   \unless\ifnocritical{%
7908     \ifl@dpairing%
7909       \ifledRcol%
7910         \flush@notesR%
7911       \else%
7912         \flush@notes%
7913       \fi%
7914     \fi
7915     \def\do##1{%
7916       \mp@append@Xnotes{##1}%
7917     }%
7918     \dolistloop{\@series}%
7919   \fi%
7920 }%
7921 \newcommand{\mp@append@Xnotes}[1]{%
7922   \ifvoid\csuse{mp#1footins}\else%
7923     \ifl@dpairing%
7924       \ifparledgroup%
7925         \ifledRcol%
7926           \dingdef{\parledgroup@beforenotesR}{\parledgroup@beforenotesR+\skip
\@nameuse{mp#1footins}}%
7927         \else%
7928           \dingdef{\parledgroup@beforenotesL}{\parledgroup@beforenotesL+\
skip\@nameuse{mp#1footins}}%
7929         \fi%
7930       \fi%
7931     \fi%
7932     \ifcsstring{series@display#1}{paragraph}{\}%
7933     \setbox\@nameuse{mp#1footins}=\vbox{%
7934       \csuse{Xnotefontsize@#1}%
7935       \ifcsdef{Xhsize}\csuse{series@display#1}@#1{%
7936         \hsize\csuse{Xhsize}\csuse{series@display#1}@#1}%
7937       }{\}%
7938       \noindent\csuse{Xtxtbeforenotes@#1}%
7939       \unvbox\@nameuse{mp#1footins}%
7940       \@parboxrestore%
7941     }%
7942   }%
7943   \csuse{mp#1footgroup}{#1}%

```

```

7944 \fi%
7945 }%
7946 %

```

`\l@dfambeginmini` These handle the initiation and closure of familiar footnotes in a minipage environment.

```

\l@dfamendmini
\mp@append@notesX
7947 \newcommand*{\l@dfambeginmini}{%
7948 \unless\ifnofamiliar{%
7949 \def\do##1{\csletcs{vfootnote##1}{mpvfootnote##1}}%
7950 \dolistloop{\@series}%
7951 \fi%
7952 }%
7953
7954 \newcommand*{\l@dfamendmini}{%
7955 \unless\ifnofamiliar{%
7956 \def\do##1{%
7957 \mp@append@notesX{##1}%
7958 }%
7959 \dolistloop{\@series}%
7960 \fi%
7961 }%
7962 \newcommand{\mp@append@notesX}[1]{%
7963 \ifvoid\csuse{mpfootins#1}\else%
7964 \ifcsstring{series@displayX#1}{paragraph}{%}{%
7965 \setbox\@nameuse{mpfootins#1}=\vbox{%
7966 \csuse{notefontsizeX#1}%
7967 \ifcsdef{hsize\csuse{series@display#1}X#1}{%
7968 \hsize\csuse{hsize\csuse{series@display#1}X#1}%
7969 }{}%
7970 \noindent\csuse{txtbeforenotesX#1}%
7971 \unvbox\@nameuse{mpfootins#1}%
7972 \@parboxrestore%
7973 }%
7974 }%
7975 \csuse{mpfootgroup#1}{#1}%
7976 \fi%
7977 }%
7978 %

```

`\@iiiminipage` This is our extended form of the kernel `\@iiiminipage` defined in `ltboxes.dtx`.

```

7979 \patchcmd%
7980 {\@iiiminipage}%
7981 {\let\@footnotetext\@mpfootnotetext}%
7982 {\let\@footnotetext\@mpfootnotetext\l@dfambeginmini}%
7983 {}%
7984 {\led@error@fail@patch@\@iiiminipage}%
7985 %

```

`\endminipage` This is our extended form of the kernel `\endminipage` defined in `ltboxes.dtx`.


```

7986 \patchcmd%
7987   {\endminipage}%
7988   {\footnoterule}%
7989   {\footnoterule\l@advance@parledgroup@beforenormalnotes}%
7990   {}%
7991   {\led@error@fail@patch@endminipage}
7992
7993 \patchcmd%
7994   {\endminipage}%
7995   {\@minipagefalse}%
7996   {\l@dfeetendmini\@minipagefalse}%
7997   {}%
7998   {\led@error@fail@patch@endminipage}
7999
8000 %

```

`\l@dunboxmpfoot` `\@ldunboxmpfoot` insert normal footnotes for ledgroup.
`edgroup@beforenormalnotes`

```

8001 \newcommand*{\l@dunboxmpfoot}{%
8002   \vskip\skip\@mpfootins
8003   \normalcolor
8004   \footnoterule
8005   \l@advance@parledgroup@beforenormalnotes
8006   \unvbox\@mpfootins%
8007 }
8008 %

```

When using parallel ledgroup, we need to store the vertical space added before footnote, in order to compensate them between left and right pages.

```

8009 \newcommand{\l@advance@parledgroup@beforenormalnotes}{%
8010   \ifparledgroup
8011     \ifl@dpairing
8012       \ifledRcol
8013         \dimgdef{\parledgroup@beforenotesR}{\parledgroup@beforenotesR+
8014 skip\@mpfootins}
8015       \else
8016         \dimgdef{\parledgroup@beforenotesL}{\parledgroup@beforenotesL+
8017 skip\@mpfootins}
8018       \fi
8019     \fi
8020   }
8021 %

```

`ledgroup` This environment puts footnotes at the end, even if that happens to be in the middle of a page, or crossing a page boundary. It is a sort of unboxed, fixed width minipage.

```

8021

```

```

8022 \newenvironment{ledgroup}{%
8023   \resetprevpage@num%
8024   \def\@mpfn{mpfootnote}\def\thempfn{\thempfootnote}\c@mpfootnote\z@%
8025   \let\@footnotetext\@mpfootnotetext
8026   \l@dfetbeginmini%
8027 }{%
8028   \par
8029   \unskip
8030   \ifvoid\@mpfootins\else
8031     \l@dunboxmpfoot
8032   \fi
8033   \l@dfetendmini%
8034   \@ledgroupfalse%
8035 }
8036
8037
8038 %

```

`\ledgroupsize` `\begin{ledgroupsize}[\langle pos \rangle]{\langle width \rangle}`

This environment puts footnotes at the end, even if that happens to be in the middle of a page, or crossing a page boundary. It is a sort of unboxed, variable `\langle width \rangle` minipage. The optional `\langle pos \rangle` controls the sideways position of numbered text.

```

8039 \newenvironment{ledgroupsize}[2][1]{%
8040 %

```

Set the various text measures.

```

8041 \hspace #2\relax
8042 %

```

Initialize fills for centering.

```

8043 \let\ledllfill\hfil
8044 \let\ledrlfill\hfil
8045 \def\@tempa{#1}\def\@tempb{1}%
8046 %

```

Left adjusted numbered lines

```

8047 \ifx\@tempa\@tempb
8048 \let\ledllfill\relax
8049 \else
8050 \def\@tempb{r}%
8051 \ifx\@tempa\@tempb
8052 %

```

Right adjusted numbered lines

```

8053 \let\ledrlfill\relax
8054 \fi
8055 \fi
8056 %

```

Set up the footnoting.

```

8057 \def\@mpfn{mpfootnote}\def\thempfn{\thempfootnote}\c@mpfootnote\z@
8058 \let\@footnotetext\@mpfootnotetext
8059 \l@dfeetbeginmini%
8060 }{f%
8061 \par
8062 \unskip
8063 \ifvoid\@mpfootins\else
8064 \l@dunboxmpfoot
8065 \fi
8066 \l@dfeetendmini%
8067 }
8068
8069 %

```

Close the \ifnoledgroup@\else.

```

8070 \fi%
8071 %

```

\ifledgroupnotesL@ These boolean tests check if we are in the notes of a ledgroup. If we are, we do not
\ifledgroupnotesR@ number the lines. It could be useful for parallel ledgroup of reledpar.

```

8072 \newif\ifledgroupnotesL@
8073 \newif\ifledgroupnotesR@
8074 %

```

XXVIII Indexing

Here is some code for indexing using page and line numbers.

XXVIII.1 Looking on package order

First, ensure that imakeidx or indextools is loaded *before* eledmac.

```

8075 \AtBeginDocument{%
8076 \unless\ifl@imakeidx%
8077 \@ifpackageloaded{imakeidx}{\led@error@PackageAfterEledmac{imakeidx}}{}
8078 %
8079 \fi%
8080 \unless\ifl@indextools%
8081 \@ifpackageloaded{indextools}{\led@error@PackageAfterEledmac{indextools}}{}
8082 %
8083 \fi%
8084 \unless\ifl@footmisc%
8085 \@ifpackageloaded{footmisc}{\led@error@PackageAfterEledmac{footmisc}}{}
8086 %
8087 \fi%
8088 }
8089 %

```

XXVIII.2 Auxiliary macros for `\edindex`

`\pagelinesep` In order to get a correct line number we have to use the label/ref mechanism. These
`\edindexlab` macros are for that.

```
\c@labidx
8087 \newcommand{\pagelinesep}{-}
8088 \newcommand{\edindexlab}{$&}
8089 \newcounter{labidx}
8090 \setcounter{labidx}{0}
8091
8092 %
```

`\doedindexlabel` This macro sets an `\edlabel`.

```
8093 \newcommand{\doedindexlabel}{%
8094   \stepcounter{labidx}%
8095   \edlabel{\edindexlab\thelabidx}%
8096 }
8097
8098 %
```

`\thepageline` This macro makes up the page/line number combo from the label/ref. The associated counter is never directly used, but it is required in order to not have any error message with `\edgls`.

```
8099 \newcounter{pageline}%
8100 \renewcommand{\thepageline}{%
8101   \thepage%
8102   \pagelinesep%
8103   \xlineref{\edindexlab\thelabidx}%
8104 }
8105 %
```

`\thestartpageline` These macros make up the page/line start/end number when the `\edindex` command
`\theendpageline` is called in critical notes.

```
8106 \newcommand{\thestartpageline}{%
8107   \l@dparsedstartpage%
8108   \pagelinesep%
8109   \l@dparsedstartline%
8110 }
8111 \newcommand{\theendpageline}{%
8112   \l@dparsedendpage%
8113   \pagelinesep%
8114   \l@dparsedendline%
8115 }
8116 %
```

XXVIII.3 Code specific to \edindex in critical footnotes

`\@edindex@fornote@` This counter is incremented at the beginning of each note (either a footnote or a side-note), and decremented at the end of each note. If its value is greater than 0, that means we are inside a note.

```
8117 \newcount\@edindex@fornote@
8118 %
```

`\prepare@edindex@fornote` This macro is called at the beginning of each critical note. It switches some parameters, to allow index referring to this note, with reference to page and line number. It also defines `\@ledinnote@command` which will be printed as an encapsulating command after the |.

```
8119 \newcommand{\prepare@edindex@fornote}[1]{%
8120   \l@dp@rsefootspec#1|}%
8121   \advance\@edindex@fornote@\@ne%
8122 }
8123 %
```

`\edindex@ledinnote@command` The `\get@edindex@ledinnote@command` macro defines a `\@ledinnote@command` command which is added as an attribute (text inserted after |) of the next index entry.

Consequently, we write the definition of the location reference attribute in the .xdy file.

```
8124 \newcommand{\get@edindex@ledinnote@command}{%
8125   \ifxindy@%
8126     \gdef\@ledinnote@command{%
8127       ledinnote\thelabidx%
8128     }%
8129     \ifxindyhyperref@%
8130       \immediate\write\eledmac@xindy@out{%
8131         (define-attributes ("ledinnote\thelabidx"))^^J
8132         \space\space(markup-locref^^J
8133         \eledmacmarkuplocrefdepth^^J
8134         :open "\string\ledinnote[\edindexlab\thelabidx]{\@index@command
8135         }\@currentseries}{\@currentnotetype}{^^J
8136         :close "}"^^J
8137         :attr "ledinnote\thelabidx"^^J
8138       )
8139     }%
8140   \else%
8141     \immediate\write\eledmac@xindy@out{%
8142       (define-attributes ("ledinnote\thelabidx"))^^J
8143       \space\space(markup-locref^^J
8144       \eledmacmarkuplocrefdepth^^J
8145       :open "\string\ledinnote{\@index@command}{\@currentseries}{\
8146       \@currentnotetype}{^^J
8147       :close "}"^^J
8148       :attr "ledinnote\thelabidx"^^J
8149     }
```

```

8147     )
8148     }%
8149     \fi%
8150 %

```

If we do not use xindy option, `\@ledinnote@command` will produce something like `ledinnote{formattingcommand}`.

```

8151     \else%
8152     \gdef\@ledinnote@command{%
8153         ledinnote[\edindexlab\thelabidx]{\@index@command}{\@currentseries}{\@currentnotetype}%
8154     }%
8155     \fi%
8156 }
8157 %

```

XXVIII.4 Analysis of command in indexed text

`\get@index@command` This macro is used to analyze if a text to be indexed has a command after a |.

```

8158 \def\get@index@command#1|#2+{%
8159     \gdef\@index@txt{#1}%
8160     \gdef\@index@command{#2}%
8161     \xdef\@index@parenthesis{}%
8162     \IfBeginWith{\@index@command}{({}%
8163         \StrGobbleLeft{\@index@command}{1}[\@index@command@]%
8164         \global\let\@index@command\@index@command@%
8165         \xdef\@index@parenthesis{({}%
8166     }{}%
8167     \IfBeginWith{\@index@command}{})}%
8168         \StrGobbleLeft{\@index@command}{1}[\@index@command@]%
8169         \global\let\@index@command\@index@command@%
8170         \xdef\@index@parenthesis{)})}%
8171     }{}%
8172 }
8173 %

```

XXVIII.5 Code for the formatted index

`\ledinnote` These macros are used to specify that an index reference points to a note. Arguments of `\ledinnote` are:

- #1 (optional): the label for the hyperlink;
- #2: command applied to the number;
- #3: the note series;
- #4: the type of note (critical/familiar).

- #5: the number itself.

```

8174 \newcommandx{\ledinnote}[5][1,usedefault]{%
8175   \IfStrEq{#4}{critical}{%
8176     \def\tmp{Xinnotemark}%
8177   }{%
8178     \def\tmp{innotemarkX}%
8179   }%
8180   \ifboolexpr{%
8181     test{\ifdefequal{\iftrue}{\ifHy@hyperindex}}%
8182     or%
8183     bool {xindyhyperref@}%
8184   }%
8185   {%
8186     \csuse{#2}{\hyperlink{#1}{\csuse{\tmp @#3}{#5}}}%
8187   }%
8188   {%
8189     \csuse{#2}{\csuse{\tmp @#3}{#5}}%
8190   }%
8191 }%
8192 \newcommand{\ledinnotemark}[1]{#1\emph{n}}%
8193 %

```

XXVIII.6 Main code

Eledmac and ledmac were using the specific indexing tools of the memoir in order to allow multiple index. However, eledmac used imakeidx or indextools tools when one these two package was loaded. This system forced to maintained a double code, which was not very useful. Since reledmac, we use only the imakeidx or indextools tools.

The memoir class provides more flexible indexing than the standard classes. We need different code if the memoir class is being used, except if imakeidx or indextools is used.

`\edindex` Write the index information to the idx file.

```

\@wredindex
\dummy@edindex
8194 \newcommandx{\@wredindex}[2][1=\expandonce\jobname,usedefault]{%#1 = the
index name, #2 = the text
8195   \begingroup%
8196     \let\emph\@firstofone%
8197     \let\textbf\@firstofone%
8198     \let\textit\@firstofone%
8199     \let\textmd\@firstofone%
8200     \let\textnormal\@firstofone%
8201     \let\textrm\@firstofone%
8202     \let\textsc\@firstofone%
8203     \let\textsf\@firstofone%
8204     \let\textsl\@firstofone%
8205     \let\texttt\@firstofone%

```

```

8206 \let\textup\@firstofone%
8207 \xdef\@tmp{#2}%To be used in IfSubStr instead of #2 directly. Avoid
some expansion bugs (for example with \edindex{textsc{something}})
8208 \endgroup%
8209 \ifl@imakeidx%
8210 \ifnum\@edindex@fornote@>\z@%
8211 \IfSubStr[1]{\@tmp}{|}{\get@index@command#2+}{\get@index@command#2|+}
%
8212 \get@edindex@ledinnote@command%
8213 \expandafter\imki@wrindexentry{#1}{\@index@txt|(\@ledinnote@command
}{\thestartpageline}%
8214 \expandafter\imki@wrindexentry{#1}{\@index@txt|)\@ledinnote@command
}{\theendpageline}%
8215 \else%
8216 \get@edindex@hyperref{#2}%
8217 \imki@wrindexentry{#1}{\@index@txt\@edindex@hyperref}{\thepageline}%
8218 \fi%
8219 \else%
8220 \ifnum\@edindex@fornote@>\z@%
8221 \IfSubStr[1]{\@tmp}{|}{\get@index@command#2+}{\get@index@command#2|+}
%
8222 \get@edindex@ledinnote@command%
8223 \expandafter\protected@write\@indexfile{}%
8224 {\string\indexentry{\@index@txt|(\@ledinnote@command}{\thestartpageline}
}%
8225 \expandafter\protected@write\@indexfile{}%
8226 {\string\indexentry{\@index@txt|)\@ledinnote@command}{\theendpageline}
}%
8227 }%
8228 \else%
8229 \protected@write\@indexfile{}%
8230 {\string\indexentry{#2}{\thepageline}
}%
8231 \fi%
8232 \fi%
8233 \endgroup
8234 \esphack%
8235 }
8236 %

```

Need to add the definition of `\edindex` to `\makeindex`, and initialise `\edindex` to do nothing.

```

8239 \pretocmd{\makeindex}{%
8240 \def\edindex{%
8241 \ifboolexpr{bool{numbering} or bool{numberingR} or bool{
l@dprintingpages} or bool{l@dprintingcolumns}}{%
8242 \bsphack%
8243 \doedindexlabel%
8244 \begingroup%
8245 \@sanitize%
8246 \@wredindex%

```



```

8247 }%
8248 {%
8249   \led@warn@edinde@outsidenumbering%
8250   \index%
8251 }%
8252 }%
8253 }%
8254 {}%
8255 {\led@error@fail@patch@makeindex}%
8256 \newcommand{\edindex}[1]{\@bsphack\@esphack}
8257 \newcommand{\dummy@edindex}[2][1=\expandonce\jobname,usedefault]{}%
8258 \newcommand{\disable@edindex}{\let\old@edindex\edindex\let\edindex\
dummy@edindex}%
8259 \newcommand{\restore@edindex}{\let\edindex\old@edindex}%
8260 %

```

XXVIII.7 Hyperlink

\hyperlinkformat `\hyperlinkformat` command is to be used to have both a internal hyperlink and a format, when indexing.

```

8261 \newcommand{\hyperlinkformat}[3]{%
8262   \ifstrempy{#1}%
8263   {\hyperlink{#2}{#3}}%
8264   {\csuse{#1}{\hyperlink{#2}{#3}}}%
8265 }%
8266 %

```

\hyperlinkR `\hyperlinkR` command is to be used to create a internal hyperlink and `\ledRflag`, when indexing.

```

8267 \newcommand{\hyperlinkR}[2]{%
8268   \hyperlink{#1}{#2\@Rlineflag}%
8269 }%
8270 %
8271 %

```

\hyperlinkformatR `\hyperlinkformatR` command is to be used to create a internal hyperlink, a format and a `\@Rlineflag`, when indexing.

```

8272 \newcommand{\hyperlinkformatR}[3]{%
8273   \hyperlinkformat{#1}{#2}{#3\@Rlineflag}%
8274 }%
8275 %
8276 %

```

\get@edindex@hyperref `\get@edindex@hyperref` is to be used to define the `\@edindex@hyperref` macro, which, in index, links to the point where the index was called (with `hyperref`).

```

8277 \newcommand{\get@edindex@hyperref}[1]{%
8278 %

```

We have to disable temporary spaces to work through a xstring bug (or feature?)

```

8279 \edef\temp@{%
8280 \catcode`\ =9 %space need for catcode
8281 \detokenize{#1}%For active character in unicode
8282 \catcode`\ =10 % space need for catcode
8283 }%
8284 %

```

Now, we define \@edindex@hyperref if the hyperindex of hyperref is enabled.

```

8285 \ifdefequal{\iftrue}{\ifHy@hyperindex}{%
8286 \IfSubStr{\temp@}{|}%
8287 {\get@index@command#1+%
8288 \ifledRcol%
8289 \gdef\@edindex@hyperref{| \@index@parenthesis %space kept
8290 hyperlinkformatR{\@index@command}%
8291 {\edindexlab\thelabidx}}%
8292 \else%
8293 \gdef\@edindex@hyperref{| \@index@parenthesis %space kept
8294 hyperlinkformat{\@index@command}%
8295 {\edindexlab\thelabidx}}%
8296 \fi%
8297 }%
8298 {\get@index@command#1|+%
8299 \ifledRcol%
8300 \gdef\@edindex@hyperref{|hyperlinkR{\edindexlab\thelabidx}}%
8301 \else%
8302 \gdef\@edindex@hyperref{|hyperlink{\edindexlab\thelabidx}}%
8303 \fi%
8304 }%
8305 }%
8306 %

```

```

8307 % If we use both xindy and hyperref, first get the \protect\cs{
index@command} command.
8308 % Then define \protect\cs{@edindex@hyperref} in the form \verb+eledmacXXX+
8309 % \begin{macrocode}
8310 {\ifxindyhyperref%
8311 \IfSubStr{\temp@}{|}%
8312 {\get@index@command#1+%
8313 {\get@index@command#1|+%
8314 \gdef\@edindex@hyperref{|eledmac\thelabidx}%
8315 %

```

If we start a reference range by a opening parenthesis, store the \thelabidx for the current \edindex, then define \@edindex@hyperref in the form | (eledmac\thelabidx.

```

8316 \IfStrEq{\@index@parenthesis}{(}%

```

```

8317     {%
8318     \csxdef{xindyparenthesis@\@index@txt}{\thelabidx}%
8319     \gdef\@edindex@hyperref{|\(eledmac\thelabidx}%
8320     }%
8321     {%
8322     %

```

This `\thelabidx` will be called back at the closing parenthesis, to have the same number in `\@edindex@hyperref` command that we had at the opening parenthesis. `\@edindex@hyperref` start by a closing parenthesis, then followed by `eledmacXXX` where `XXX` is the `\thelabidx` of the opening `\edindex`.

```

8323     \IfStrEq{\@index@parenthesis}{})}%
8324     {%
8325     \xdef\@edindex@hyperref{|\)eledmac\csuse{xindyparenthesis@\@index@txt}}}%
8326     \global\csundef{xindyparenthesis@\@index@txt}%
8327     }%
8328     %

```

Write in the `.xdy` file the attributes of the location.

```

8329     {%
8330     \immediate\write\eledmac@xindy@out{%
8331     (define-attributes ("eledmac\thelabidx"))^^J
8332     \space\space(markup-locoref^^J
8333     \eledmacmarkuplocorefdepth^^J
8334     :open "\string\hyperlink%
8335     \ifledRcol R\fi%
8336     {\edindexlab\thelabidx}%
8337     {\ifdefempty{\@index@command}%
8338     {}%
8339     {\@backslashchar\@index@command}%
8340     {"^^J
8341     :close "})"^^J
8342     :attr "eledmac\thelabidx"^^J
8343     )
8344     }%
8345     }%
8346     %

```

And now, in any other case.

```

8347     \else%
8348     \gdef\@index@txt{#1}%
8349     \gdef\@edindex@hyperref{}%
8350     \fi%
8351     }%
8352 }
8353 %

```

XXVIII.8 “innote” and “notenumber” option of indextols package

`\led@set@index@fornote` The `\led@set@index@fornote` is called when a familiar footnote is inserted — and not when it is read — and changes the `\index` command depending on the option of the `indextools` package. Its only argument is the note series.

```

8354 \newcommand{\led@set@index@fornote}[1]{%
8355   \ifbool{indtl@innote}%
8356     {\let\index\nindex}%
8357     {}%
8358   \ifbool{indtl@notenumber}%
8359     {%
8360       \renewcommand{\index}[2][\indtl@jobname]{%
8361         \orig@@index[##1]{%
8362           ##2|innotenumber{\this@footnoteX@reading}%
8363         }%
8364       }%
8365     }%
8366     {}%
8367   }%
8368   %

```

`\led@reinit@index@fornote` The `\led@reinit@index@fornote` just reset the default value of `\index`.

```

8369 \newcommand{\led@reinit@index@fornote}{%
8370   \ifbool{indtl@innote}%
8371     {\let\index\orig@@index}%
8372     {}%
8373   \ifbool{indtl@notenumber}%
8374     {\let\index\orig@@index}%
8375     {}%
8376   }%
8377   %

```

XXIX Glossaries

Here, we define the `\gls`-like commands prefixed by `ed`, only if the package `glossaries` is loaded.

```

8378 \AtBeginDocument{%
8379   \ifpackageloaded{glossaries}{%
8380     %

```

First those which arguments are `[<options>]{<label>}[<insert>]`.

```

8381   \gdef\edglsomo{}%
8382   \listgadd{\edglsomo}{gls}%
8383   \listgadd{\edglsomo}{Gls}%
8384   \listgadd{\edglsomo}{GLS}%

```

```

8385 \listgadd{\edglsomo}{glspl}%
8386 \listgadd{\edglsomo}{Glspl}%
8387 \listgadd{\edglsomo}{GLSpl}%
8388 \listgadd{\edglsomo}{glstext}%
8389 \listgadd{\edglsomo}{Glstext}%
8390 \listgadd{\edglsomo}{GLStext}%
8391 \listgadd{\edglsomo}{Glsfirst}%
8392 \listgadd{\edglsomo}{GLSfirst}%
8393 \listgadd{\edglsomo}{glsplural}%
8394 \listgadd{\edglsomo}{Glsplural}%
8395 \listgadd{\edglsomo}{GLSplural}%
8396 \listgadd{\edglsomo}{glsfirstplural}%
8397 \listgadd{\edglsomo}{Glsfirstplural}%
8398 \listgadd{\edglsomo}{GLSfirstplural}%
8399 \listgadd{\edglsomo}{glsname}%
8400 \listgadd{\edglsomo}{Glsname}%
8401 \listgadd{\edglsomo}{GLSname}%
8402 \listgadd{\edglsomo}{glssymbol}%
8403 \listgadd{\edglsomo}{Glsymbol}%
8404 \listgadd{\edglsomo}{GLSsymbol}%
8405 \listgadd{\edglsomo}{glsdesc}%
8406 \listgadd{\edglsomo}{GLSdesc}%
8407 \listgadd{\edglsomo}{GLSdesc}%
8408 \listgadd{\edglsomo}{glsuseri}%
8409 \listgadd{\edglsomo}{Glsuseri}%
8410 \listgadd{\edglsomo}{GLSuseri}%
8411 \listgadd{\edglsomo}{glsuserii}%
8412 \listgadd{\edglsomo}{Glsuserii}%
8413 \listgadd{\edglsomo}{GLSuserii}%
8414 \listgadd{\edglsomo}{glsuseriii}%
8415 \listgadd{\edglsomo}{Glsuseriii}%
8416 \listgadd{\edglsomo}{GLSuseriii}%
8417 \listgadd{\edglsomo}{glsuseriv}%
8418 \listgadd{\edglsomo}{Glsuseriv}%
8419 \listgadd{\edglsomo}{GLSuseriv}%
8420 \listgadd{\edglsomo}{glsuserv}%
8421 \listgadd{\edglsomo}{Glsuserv}%
8422 \listgadd{\edglsomo}{GLSuserv}%
8423 \listgadd{\edglsomo}{glsuservi}%
8424 \listgadd{\edglsomo}{Glsuservi}%
8425 \listgadd{\edglsomo}{GLSuservi}%
8426 \renewcommand{\do}[1]{%
8427 \expandafter\DeclareRobustCommand\csname ed#1\endcsname[3][1,3,
usedefault]{%
8428 \doedindexlabel%
8429 \ifdef{\hypertarget}{%
8430 \Hy@raisedlink@left{\hypertarget{pageline.\thepageline}}}%
8431 }{}%
8432 \csname#1\endcsname[counter=pageline,##1]{##2}[##3]%
8433 }%

```

```

8434 \expandafter\WithSuffix\expandafter\DeclareRobustCommand\csname ed
#1\endcsname*[3][1,3,usedefault]{%
8435 \doedindexlabel%
8436 \ifdef{\hypertarget}{%
8437 \Hy@raisedlink@left{\hypertarget{pageline.\thepageline}}}%
8438 }{}%
8439 \csname#1\endcsname*[counter=pageline,##1]{##2}{##3}%
8440 }%
8441 }%
8442 \dolistloop{\edglsomo}%
8443 %

```

Then those which arguments are [*options*]{*label*}{*link text*}.

```

8444 \gdef\edglsomm{%
8445 \listgadd\edglsomm{glsdisp}%
8446 \listgadd\edglsomm{glslink}%
8447 \renewcommand{\do}[1]{%
8448 \expandafter\DeclareRobustCommand\csname ed#1\endcsname[3][1,
usedefault]{%
8449 \doedindexlabel%
8450 \ifdef{\hypertarget}{%
8451 \Hy@raisedlink@left{\hypertarget{pageline.\thepageline}}}%
8452 }{}%
8453 \csname#1\endcsname[counter=pageline,##1]{##2}{##3}%
8454 }%
8455 \expandafter\WithSuffix\expandafter\DeclareRobustCommand\csname ed
#1\endcsname*[3][1,usedefault]{%
8456 \doedindexlabel%
8457 \ifdef{\hypertarget}{%
8458 \Hy@raisedlink@left{\hypertarget{pageline.\thepageline}}}%
8459 }{}%
8460 \csname#1\endcsname*[counter=pageline,##1]{##2}{##3}%
8461 }%
8462 }%
8463 \dolistloop{\edglsomm}%
8464 %

```

Then those which arguments are [*options*]{*label*}.

```

8465 \gdef\edglsom{%
8466 \listgadd\edglsom{glsadd}%
8467 \renewcommand{\do}[1]{%
8468 \expandafter\DeclareRobustCommand\csname ed#1\endcsname[2][1,
usedefault]{%
8469 \doedindexlabel%
8470 \ifdef{\hypertarget}{%
8471 \Hy@raisedlink@left{\hypertarget{pageline.\thepageline}}}%
8472 }{}%
8473 \csname#1\endcsname[counter=pageline,##1]{##2}%
8474 }%

```

```

8475 \expandafter\WithSuffix\expandafter\DeclareRobustCommand\csname ed
#1\endcsname*[2][1,usedefault]{%
8476 \doedindexlabel%
8477 \ifdef{\hypertarget}{%
8478 \Hy@raisedlink@left{\hypertarget{pageline.\thepageline}}}%
8479 }{}%
8480 \csname#1\endcsname*[counter=pageline,##1]{##2}%
8481 }%
8482 }%
8483 \dolistloop{\edglsom}%
8484 %

```

`\l@noexpands@edgl` is a macro to avoid expanding glossaries macros in `\edtext` first argument. It is called by `\no@expands`. Its definition is made dynamically.

```

\l@noexpands@edgl 85 \def\l@noexpands@edgl{%
8486 \renewcommand\do[1]{%
8487 \xappto\l@noexpands@edgl{%
8488 \noexpand\RenewDocumentCommand\csname ed#1\endcsname{omos}{}%
8489 }%
8490 }%
8491 \dolistloop{\edglsomo}%
8492 \renewcommand\do[1]{%
8493 \xappto\l@noexpands@edgl{%
8494 \noexpand\RenewDocumentCommand\csname ed#1\endcsname{omms}{}%
8495 }%
8496 }%
8497 \dolistloop{\edglsomm}%
8498 \renewcommand\do[1]{%
8499 \xappto\l@noexpands@edgl{%
8500 \noexpand\RenewDocumentCommand\csname ed#1\endcsname{oms}{}%
8501 }%
8502 }%
8503 \dolistloop{\edglsom}%
8504 }{\let\l@noexpands@edgl\relax}%
8505 }%
8506 %

```

XXX Verse

The original code is principally Wayne Sullivan's code from `edstanza`. However, the code has been many time modified by Maïeul Rouquette in order to obtain new features and improved compatibility with `reledpar`.

XXX.1 Hanging symbol management

`\@hangingsymbol` The macro `\@hangingsymbol` is used to insert a symbol on each hanging of verses. It is set by user level macro `\sethangingsymbol`.
`\ifinstanza`

For example, in French typography, the symbol is “[”. We obtain it by means of the following code:

```
\sethangingsymbol{[,}
```

The `\ifinstanza` boolean is used to ensure that we are in a stanza part.

```
8507 \def\@hangingsymbol{}
8508 \newcommand*{\sethangingsymbol}[1]{%
8509   \gdef\@hangingsymbol{#1}%
8510 }%
8511 \newif\ifinstanza
8512 %
```

`\inserthangingsymbol` The boolean `\ifinserthangingsymbol` is set to TRUE when `\@lock` is greater than 1, i.e. when we are not in the first line of a verse. The switch of `\ifinserthangingsymbol` is made in `\do@line` before the printing of line but after the line number calculation.

```
8513 \newif\ifinserthangingsymbol
8514 \newcommand{\inserthangingsymbol}{%
8515   \ifinserthangingsymbol%
8516     \ifinstanza%
8517       \@hangingsymbol%
8518     \fi%
8519 \fi%
8520 }
8521 %
```

XXX.2 Using & character

`\ampersand` Within a stanza the `\&` macro is going to be usurped. We need an alias in case an `&` needs to be typeset in a stanza. Define it rather than letting it in case some other package has already defined it.

```
8522 \newcommand*{\ampersand}{\char`\&}
8523
8524 %
```

XXX.3 Code category setting

`\stanza@count` Before we can define the main macros we need to save and reset some category codes.
`\stanzaindentbase` To save the current values we use `\next` and `\body` from the `\loop` macro.

```
8525 \chardef\body=\catcode`\@
8526 \catcode`\@=11
8527 \chardef\next=\catcode`\&
8528 \catcode`\&=\active
8529
8530 %
```


XXX.4 Stanza count and indent

A count register is allocated for counting lines in a stanza; also allocated is a dimension register which is used to specify the base value for line indentation; all stanza indentations are multiples of this value. The default value of `\stanzaindentbase` is 20pt.

```
8531 \newcount\stanza@count
8532 \newlength{\stanzaindentbase}
8533 \setlength{\stanzaindentbase}{20pt}
8534
8535 %
```

`\strip@szacnt` The indentations of stanza lines are non-negative integer multiples of the unit called
`\setstanzavalues` `\stanzaindentbase`. To make it easier for the user to specify these numbers, some list macros are defined. These take numerical values in a list separated by commas and assign the values to special control sequences using `\mathchardef`. Though this does limit the range from 0 to 32767, it should suffice for most applications, including *penalties*, which will be discussed below.

```
8536 \def\strip@szacnt#1,#2|{\def\@tempb{#1}\def\@tempa{#2|}}
8537 \newcommand*\setstanzavalues[2]{\def\@tempa{#2,,|}%
8538   \stanza@count\z@
8539   \def\next{\expandafter\strip@szacnt\@tempa
8540     \ifx\@tempb\empty\let\next\relax\else
8541       \expandafter\mathchardef\csname #1\@number\stanza@count
8542       \@endcsname\@tempb\relax
8543       \advance\stanza@count\@ne\fi\next}%
8544   \next}
8545
8546 %
```

`\setstanzaindents` In the original edmac, `\setstanzavalues{sza}{⟨...⟩}` had to be called to set the in-
`\setstanzapenalties` dents, and similarly `\setstanzavalues{szp}{⟨...⟩}`. to set the penalties. `\setstanzaindents` and `\setstanzapenalties` macros are a convenience to give the user one less thing to worry about (misspelling the first argument).

```
8547 \newcommand*\setstanzaindents[1]{\setstanzavalues{sza}{#1}}
8548 \newcommand*\setstanzapenalties[1]{\setstanzavalues{szp}{#1}}
8549 %
8550 %
```

`\managestanza@modulo` Since the `stanzaindentrepetition` counter can be used when the indentation is repeated every n verses.

The `startstanzaindentrepetition` counter tells in which line of verse the repetition of indent starts.

The `\managestanza@modulo` macro modifies the counter `stanza@modulo`. The command adds 1 to `stanza@modulo`, but if `stanza@modulo` is equal to the `stanzaindentrepetition` counter, the command restarts it.

```

8551 \newcounter{stanzaindentrepetition}
8552 \newcounter{startstanzaindentrepetition}%
8553 \setcounter{startstanzaindentrepetition}{1}%
8554 \newcount\stanza@modulo
8555
8556 \newcommand*{\managestanza@modulo}[0]{%
8557     \advance\stanza@modulo\@ne%
8558     \ifnum\stanza@modulo>\value{stanzaindentrepetition}%
8559         \stanza@modulo\@ne%
8560     \fi%
8561 }
8562 %

```

\stanzaindent The macro `\stanzaindent`, when called at the beginning of a verse, changes the indentation normally defined for this verse by `\setstanzaindent`. The starred version **\stanzaindent*** skips the current verse for the repetition of stanza indent.

```

8563 \newcommand{\stanzaindent}[1]{%
8564     \hspace{\dimexpr#1\stanzaindentbase-\parindent\relax}%
8565     \ignorespaces%
8566 }%
8567 \WithSuffix\newcommand\stanzaindent*[1]{%
8568     \stanzaindent{#1}%
8569     \global\advance\stanza@modulo-\@ne%
8570     \ifnum\stanza@modulo=0%
8571         \global\stanza@modulo=\value{stanzaindentrepetition}%
8572     \fi%
8573     \ignorespaces%
8574 }%
8575 %

```

XXX.5 Numbering stanza

Here, macro for numbering stanza. First, the stanza counter.

```

\thestanza 76 \newcounter{stanza}
8577 \renewcommand{\thestanza}{%
8578     \textbf{\arabic{stanza}}%
8579 }
8580 %

```

\ifnumberstanza Then, macro to activate automatically numbering of stanza.

```

8581 \newif\ifnumberstanza%
8582 %

```

\@insertstanzanumber Now, macro called at the first line of of verse of a stanza.

```

8583 \newcommand{\@insertstanzanumber}[0]{%
8584   \ifnumberstanza%
8585     \ifl@dpairing%
8586       \ifledRcol%
8587         \stanzanumwrapper{\thestanzaR}%
8588       \else%
8589         \stanzanumwrapper{\thestanzaL}%
8590       \fi%
8591     \else%
8592       \stanzanumwrapper{\thestanza}%
8593     \fi%
8594     \setline{1}%
8595   \fi%
8596 }%
8597 %

```

\@advancestanzanumber Also a command to advance the counter of stanza.

```

8598 \newcommand{\@advancestanzanumber}[0]{%
8599   \ifnumberstanza%
8600     \ifl@dpairing%
8601       \ifledRcol%
8602         \addtocounter{stanzaR}{1}%
8603       \else%
8604         \addtocounter{stanzaL}{1}%
8605       \fi%
8606     \else%
8607       \addtocounter{stanza}{1}%
8608     \fi%
8609   \fi%
8610 }%
8611 %

```

\stanzanumwrapper And finally, the wrapper for stanza number

```

8612 \newcommand{\stanzanumwrapper}[1]{%
8613   \flagstanza{#1}%
8614 }%
8615 %

```

XXX.6 Stanza number in note

Here, the command called when printing stanza number in notes.

```

8616 \newcommand{\printstanza}[0]{%
8617   \ifbool{expr{bool{l@dpairing} or bool{l@dprintingpages} or bool{
8618     l@dprintingcolumns}}}{%
8619     \ifledRcol%
8619       \thestanzaR%

```

```

8620     \else%
8621         \thestanzaL%
8622     \fi%
8623 }{%
8624     \thestanza%
8625 }%
8626 }
8627 %

```

XXX.7 Main work

`\stanza@line` Now we arrive at the main works. `\stanza@line` sets the indentation for the line and starts a numbered paragraph—each line is treated as a paragraph. `\stanza@hang` sets the hanging indentation to be used if the stanza line requires more than one print line.

`\stanza@indent` If it is known that each stanza line will fit on one print line, it is advisable to set the hanging indentation to zero. `\sza@penalty` places the specified penalty following each stanza line. By default, this facility is turned off so that no penalty is included. However, the user may initiate these penalties to indicate good and bad places in the stanza for page breaking.

```

8628 \newcommand{\stanza@line}[2][1,2,usedefault]{%
8629     \stanza@indent%
8630     \pstart[#1][#2]\stanza@hang\ignorespaces%
8631 }%
8632 \newcommand{\stanza@indent}{%
8633     \ifboolexpr{%
8634         test {\ifnumequal{\value{stanzaindentrepetition}}{0}}%
8635         or%
8636         test {\ifnumless{\number\stanza@count}{\value{
8637 startstanzaindentrepetition}}}%
8638     }{%
8639         \ifcsdef{sza@\number\stanza@count @}{%
8640             {%
8641                 \parindent=\csname sza@\number\stanza@count @\endcsname\
8642 stanzaindentbase%
8643             }%
8644         }{%
8645             \ifcsdef{sza@\number\stanza@modulo @}{%
8646                 \parindent=\csname sza@%
8647 \the\numexpr%
8648 \stanza@modulo%
8649 - 1%
8650 + \value{startstanzaindentrepetition}%
8651 \relax%
8652 @\endcsname\stanzaindentbase%
8653 \managestanza@modulo%
8654             }%

```

```

8655     {%
8656     \led@err@StanzaIndentNotDefined%
8657     }%
8658 }%
8659 }%
8660 \xdef\stanza@hang{\noexpand\leavevmode\noexpand\startlock
8661     \hangindent\expandafter
8662     \noexpand\csname sza@0@\endcsname\stanzaindentbase
8663     \hangafter\@ne}
8664 \def\sza@penalty{\count@\csname szp@\number\stanza@count @\endcsname
8665     \ifnum\count@>@M\advance\count@-@M\penalty-\else
8666     \penalty\fi\count@}
8667 %

```

\@startstanza Now we have the components of the \stanza macro, which appears at the start of a
 \stanza group of lines. This macro initializes the count and checks to see if hanging indentation
 \@stopstanza and penalties are to be included. Hanging indentation suspends the line count, so that
 \AtEveryStopStanza the enumeration is by verse line rather than by print line. If the print line count is desired,
 \AtEveryStanza invoke \let\startlock\relax and do the same for \endlock. Here and above we
 \AtStartEveryStanza have used \xdef to make the stored macros take up a bit less space, but it also makes
 \BeforeEveryStopStanza them more obscure to the reader. Lines of the stanza are delimited by ampersands &.
 \newverse The last line of the stanza must end with \&.

```

8668 \xdef\@startstanza[#1][#2]{%
8669     \noexpand\instanzatrue\expandafter
8670     \begingroup%
8671     \catcode`\noexpand\&\active%
8672     \unexpanded{\newdimen\parindent@beforestanza%
8673     \parindent@beforestanza=\parindent}%Keep in memory the standard \
parindent
8674     \global\stanza@count\@ne\stanza@modulo\@ne
8675     \noexpand\ifnum\expandafter\noexpand\csname sza@0@\endcsname=\z@%
8676     \def\noexpand\stanza@hang{\unexpanded{\leavevmode\null}}}%
8677     \let\noexpand\endlock\relax%
8678     \noexpand\else%
8679     \interlinepenalty%
8680     \@M\rightskip\z@ plus 1fil\relax%
8681     \noexpand\fi%
8682     \noexpand\ifnum\expandafter\noexpand\csname szp@0@\endcsname=\z@%
8683     \let\noexpand\sza@penalty%
8684     \relax\noexpand\fi%
8685     \def\noexpand&{%
8686         \noexpand\newverse[] []}%
8687     \def\noexpand\&{\noexpand\@stopstanza}%
8688     \noexpand\@advancestanzanumber%
8689     \noexpand\stanza@line[#1][#2]%
8690     \noexpand\@insertstanzanumber%
8691     \let\par\relax\ignorespaces%No paragraph in verses
8692 }

```

```

8693
8694 \newcommandx{\stanza}[2][1,2,usedefault]{%
8695   \ifboolexpr{%
8696     not test{\ifdefvoid{\at@every@stanza}}%
8697     and test{\ifstrempy{#1}}%
8698     and test{\ifstrempy{#2}}}%
8699     {\@startstanza[][\at@every@stanza]\at@start@every@stanza}%
8700     {\@startstanza[#1][#2]\at@start@every@stanza}%
8701   }%
8702
8703 \newcommandx{\@stopstanza}[2][1,2,usedefault]{%
8704   \unskip%
8705   \endlock%
8706   \ifboolexpr{%
8707     not test{\ifdefvoid{\at@every@stop@stanza}}%
8708     and test{\ifstrempy{#1}}%
8709     and test{\ifstrempy{#2}}}%
8710     {\before@every@stop@stanza\pend[][\at@every@stop@stanza]}%
8711     {\before@every@stop@stanza\pend[#1][#2]}%
8712   \endgroup%
8713   \instanzafalse%
8714   \global\undef\parindent@beforestanza%
8715 }
8716
8717 \newcommand{\AtEveryStopStanza}[1]{%
8718   \ifstrempy{#1}%
8719     {\gdef\at@every@stop@stanza{}}%
8720     {\gdef\at@every@stop@stanza{\noindent#1}}%
8721   }%
8722 \WithSuffix\newcommand\AtEveryStopStanza*[1]{%
8723   \ifstrempy{#1}%
8724     {\gdef\at@every@stop@stanza{}}%
8725     {\gdef\at@every@stop@stanza{#1}}%
8726   }%
8727 \def\at@every@stop@stanza{}%
8728
8729 \newcommand{\AtEveryStanza}[1]{%
8730   \ifstrempy{#1}%
8731     {\gdef\at@every@stanza{}}%
8732     {\gdef\at@every@stanza{\noindent#1}}%
8733   }%
8734 \WithSuffix\newcommand\AtEveryStanza*[1]{%
8735   \ifstrempy{#1}%
8736     {\gdef\at@every@stanza{}}%
8737     {\gdef\at@every@stanza{#1}}%
8738   }%
8739
8740
8741
8742 \newcommand{\AtStartEveryStanza}[1]{%

```

```

8743 \ifstrempy{#1}%
8744   {\gdef\at@start@every@stanza{}}}%
8745   {\gdef\at@start@every@stanza{#1}}}%
8746 }%
8747 \def\at@start@every@stanza{}%
8748
8749 \newcommand{\BeforeEveryStopStanza}[1]{%
8750   \ifstrempy{#1}%
8751     {\gdef\before@every@stop@stanza{}}}%
8752     {\gdef\before@every@stop@stanza{#1}}}%
8753 }%
8754 \def\before@every@stop@stanza{}%
8755
8756 \newcommand*{\newverse}[4][1,2,3,4,usedefault]{%
8757   \unskip%
8758   \endlock\pend[#1][#3]\sza@penalty\global%
8759   \advance\stanza@count\@ne\stanza@line[#2][#4]%
8760 }
8761
8762 %

```

\flagstanza Use `\flagstanza[len]{text}` at the start of a line to put *text* a distance *len* before the start of the line. The default for *len* is `\stanzaindentbase`.

```

8763 \newcommand*{\flagstanza}[2][\stanzaindentbase]{%
8764   \hskip -#1\llap{#2}\hskip #1\ignorespaces}
8765
8766 %

```

XXX.8 Restore catcode and penalties

The ampersand & is used to mark the end of each stanza line, except the last, which is marked with `\&`. This means that `\halign` may not be used directly within a stanza line. This does not affect macros involving alignments defined outside `\stanza \&`. Since these macros usurp the control sequence `\&`, the replacement `\ampersand` is defined to be used if this symbol is needed in a stanza. Also we reset the modified category codes and initialize the penalty default.

```

8767 \catcode`\&=\next
8768 \catcode`\@=\body
8769 \setstanzavalues{szp}{0}
8770
8771 %

```

XXX.9 Dealing with antilabe

\firsthalf@antilabe@wd If the `antilabe` option is enabled, after having vboxed the content of `\pstart...pend`
get@firsthalf@antilabe@wd structure, we get the width of the last line of the `\pend`.
\antilabe

```

8772 \ifantilabe@%
8773   \newdimen\firsthalf@antilabe@wd%
8774   \newcommand\get@firsthalf@antilabe@wd{%
8775     \ifboolexpr{bool {istanza} or bool {inastanzaL} or bool {inastanzaR}}{
%
8776       \vbadness=10000%
8777       \splittopskip=\z@%
8778       \ifl@dpairing%
8779         \ifledRcol%
8780           \setbox0=\copy\csname l@dRcolrawbox\the\l@dnumpstartsR\endcsname%
8781         \else%
8782           \setbox0=\copy\csname l@dLcolrawbox\the\l@dnumpstartsL\endcsname%
8783         \fi%
8784       \else%
8785         \setbox0=\copy\raw@text%
8786       \fi%
8787       \dimen0=\dimexpr\ht0+\dp0-\baselineskip\relax%
8788       \ifdim\dimen0>0pt%
8789         \setbox1=\vsplit0 to \dimen0%
8790       \fi%
8791       \setbox0=\vbox{\unvbox0\global\setbox1=\lastbox}%
8792       \setbox1=\hbox{\noindent\unhbox1}%
8793       \global\firsthalf@antilabe@wd=\wd1%
8794     }{}%
8795   }%
8796   \def\beforeantilabe{}%
8797   \def\afterantilabe{}%
8798   \newcommand{\antilabe}[1]{%
8799     \beforeantilabe\hbox to\firsthalf@antilabe@wd{#1\hfill}\afterantilabe%
8800   }%
8801 \else%
8802   \let\get@firsthalf@antilabe@wd\relax%
8803 \fi%
8804 %

```

XXXI Apparatus of Manuscripts

XXXI.1 User level macro

\msdata The user level `\msdata` command only writes the manuscripts data in a numbered auxiliary file. There are two associated etoolbox counters.

```

\msdata@cR
\msdata@cR
8805 \def\msdata@c{}%
8806 \def\msdata@cR{}%
8807 \newcommand{\msdata}[1]{%
8808   \leavevmode%
8809   \unless\ifstopmsdata@inserted%
8810     \stopmsdata%
8811     \led@warning@msdatawithoutstop%

```



```

8812 \fi%
8813 \global\stopmsdata@inserted@false%
8814 \unless\ifledRcol%
8815   \numgdef{\msdata@c}{\msdata@c+1}%
8816   \ifdef{\hypertarget}{%
8817     \edlabel{\msdata@c:start:msdata}%
8818   }{}%
8819   \protected@write\linenum@out{}{%
8820     \string\@msd{#1}%
8821   }%
8822 \else%
8823   \numgdef{\msdata@cR}{\msdata@cR+1}%
8824   \ifdef{\hypertarget}{%
8825     \edlabel{\msdata@cR:start:msdata}%
8826   }{}%
8827   \protected@write\linenum@outR{}{%
8828     \string\@msd{#1}%
8829   }%
8830 \fi%
8831 }%
8832 %

```

\stopmsdata The user level `\stopmsdata` command only writes information about the end of manuscripts data in numbered auxiliary file.

```

8833 \newcommand{\stopmsdata}[0]{%
8834   \leavevmode%
8835   \unless\ifledRcol%
8836     \protected@write\linenum@out{}{%
8837       \string\@stopmsd%
8838     }%
8839     \ifdef{\hypertarget}{%
8840       \edlabel{\msdata@c:end:msdata}%
8841     }{}%
8842   \else%
8843     \protected@write\linenum@outR{}{%
8844       \string\@stopmsd%
8845     }%
8846     \ifdef{\hypertarget}{%
8847       \edlabel{\msdata@cR:end:msdata}%
8848     }{}%
8849   \fi%
8850   \global\stopmsdata@inserted@true%
8851 }%
8852 %

```

\ifstopmsdata@inserted@ The `\ifstopmsdata@inserted@` boolean is set to TRUE at every `\stopmsdata` and reset to FALSE at all `\msdata`. It also set to TRUE at every `\beginnumbering`. It is used to automatically insert `\stopmsdata` if forgotten before `\msdata`

```

8853 \newif\ifstopmsdata@inserted@%
8854 %

```

XXXI.2 Setting macro

Setting macros for the manuscripts apparatus tools is very easy: they just save their argument in an internal macro.

\setmsdataseries In which series of notes will be printed the apparatus of manuscripts?

```

8855 \newcommand{\setmsdataseries}[1]{%
8856   \gdef\@msdata@series{#1}%
8857 }%
8858 \def\@msdata@series{A}%
8859 %

```

\setmsdataposition The label for the manuscripts data.

```

8860 \def\ms@data@position{msdata-regular}%
8861 \newcommand{\setmsdataposition}[1]{%
8862   \gdef\ms@data@position{#1}%
8863 }%
8864 %

```

\setmsdatalabel The label for the manuscripts data.

```

8865 \def\ms@data@label{Ms.}%
8866 \newcommand{\setmsdatalabel}[1]{%
8867   \gdef\ms@data@label{#1}%
8868 }%
8869 %

```

XXXI.3 Counters and lists

\@msd@c \@msd@c is a counter incremented at each \@msd read in auxiliary file.

```

8870 \numdef{\@msd@c}{0}
8871 \numdef{\@msd@cR}{0}
8872 %

```

\add@msd@ \add@msd@ is a counter incremented at each \add@msddata, that is at each time we prepare the insertion of manuscripts data footnote.

```

8873 \numdef{\add@msd@c}{0}%
8874 \numdef{\add@msd@cR}{0}%
8875 %

```

\@msdata@list The \@msdata@list will contain, for each line, the lists of command to be executed to insert the manuscripts apparatus. It will be filled on \add@msdata and looped on \insert@msdata, then emptied.

```

8876 \def\@msdata@list{%
8877 %

```

XXXI.4 Auxiliary file macros

\@msd The \@msd macro is written in the auxiliary file. It just defines three macros by \@msdata macro, which allow us to know the manuscripts data, the line number and the absolute line number where it was called

It also stores the action code 1010 in the list of actions by line.

```

8878 \newcommand{\@msd}[1]{%
8879 \unless\ifledRcol%
8880 \global\newdef{\@msd@c}{\@msd@c+\@ne}%
8881 \csgdef{\@msdata@\@msd@c @data}{#1}%
8882 \csxdef{\@msdata@\@msd@c @linenumber}{\the\line@num}%
8883 \csxdef{\@msdata@\@msd@c @sublinenumber}{\the\subline@num}%
8884 \csxdef{\@msdata@\@msd@c @abslinenumber}{\the\absline@num}%
8885 \xright@appenditem{\the\absline@num}\to\actionlines@list%
8886 \xright@appenditem{-1010}\to\actions@list%
8887 \else%
8888 \global\newdef{\@msd@cR}{\@msd@cR+\@ne}%
8889 \csgdef{\@msdata@\@msd@cR @dataR}{#1}%
8890 \csxdef{\@msdata@\@msd@cR @linenumberR}{\the\line@numR}%
8891 \csxdef{\@msdata@\@msd@cR @sublinenumberR}{\the\subline@numR}%
8892 \csxdef{\@msdata@\@msd@cR @abslinenumberR}{\the\absline@numR}%
8893 \xright@appenditem{\the\absline@numR}\to\actionlines@listR%
8894 \xright@appenditem{-1010}\to\actions@listR%
8895 \fi%
8896 }%
8897 %

```

\@stopmsd Inserted in the auxiliary file by \@stopmsd, the \@stopmsd macro will store in two commands the line number and the absolute line number on which it is called.

```

8898 \newcommand{\@stopmsd}[0]{%
8899 \unless\ifledRcol%
8900 \ifcsundef{\@msdata@\@msd@c @stoplinenumber}{%
8901 \csxdef{\@msdata@\@msd@c @stopabslinenumber}{\the\absline@num}%
8902 \csxdef{\@msdata@\@msd@c @stoplinenumber}{\the\line@num}%
8903 \csxdef{\@msdata@\@msd@c @stopsublinenumber}{\the\subline@num}%
8904 }}%
8905 \else%
8906 \ifcsundef{\@msdata@\@msd@cR @stoplinenumberR}{%
8907 \csxdef{\@msdata@\@msd@cR @stopabslinenumberR}{\the\absline@numR}%
8908 \csxdef{\@msdata@\@msd@cR @stoplinenumberR}{\the\line@numR}%
8909 \csxdef{\@msdata@\@msd@cR @stopsublinenumberR}{\the\subline@numR}%
8910 }%
8911 }%
8912 \fi%

```

8913 }%
8914 %

XXXI.5 Action macro

`\add@msdata` `\add@msdata` is executed on each line when action code 1010 is seen. It will not insert immediately the manuscript data footnote, as action code are executed before the line be typeset, and, consequently, could be on the previous page. So it just stores the manuscript data footnote to `\@msdata@list`.

```
8915 \newcommand{\add@msdata}{%
8916   \bgroup%
8917   \normalfont%
8918   \unless\ifledRcol{%
8919     \numgdef{\add@msd@c}{\add@msd@c+\@ne}%
8920     \ifcsdef{@msdata@\add@msd@c @data}{%
8921       \letcs{@data}{@msdata@\add@msd@c @data}%
8922       \edef\l@d@nums{%
8923         000|% Start page = we don't print it
8924         \csuse{@msdata@\add@msd@c @linenumber}|% Start line number
8925         \csuse{@msdata@\add@msd@c @sublinenumber}|% Start subline number
8926         000|% End page number, we don't print it
8927         \ifnumless{\csuse{@msdata@\add@msd@c @stopabslinenumber}}{\csuse{
@lastabsline@forpage@\the\page@num}}}%
8928         {\csuse{@msdata@\add@msd@c @stoplinenumber}}}%End line number if
in the same page
8929         {\csuse{@lastline@forpage@\the\page@num}}}%Otherwise, last
number of the page
8930         |%
8931         \ifnumless{\csuse{@msdata@\add@msd@c @stopabslinenumber}}{\csuse{
@lastabsline@forpage@\the\page@num}}}%
8932         {\csuse{@msdata@\add@msd@c @stopsublinenumber}}}%End subline
number if in the same page
8933         {\csuse{@lastsubline@forpage@\the\page@num}}}%Otherwise, last
subnumber of the page
8934         |%
8935         \edefont@info%Font
8936       }%
8937       \@msd@options@fullpagefalse%
8938       \if@firstlineofpage%Try if the data are for the full page. If yes
, will add options to the list.
8939       \unless\if@msdata@insertedfrompreviouspage%
8940       \ifnumless{\csuse{@lastabsline@forpage@\the\page@num}}{\csuse{
@msdata@\add@msd@c @stopabslinenumber}+\@ne}%
8941       {%
8942       \numdef{@tmp}{\add@msd@c+\@ne}%
8943       \ifcsdef{@msdata@\@tmp @abslinenumber}%
8944       {\ifnumequal{\csuse{@msdata@\@tmp @abslinenumber}}{\csuse{
@lastabsline@forpage@\the\page@num}}}%
```

```

8945         {}%
8946         {\@msd@options@fullpagetrue}%
8947     }%
8948     {\@msd@options@fullpagetrue}%
8949 }%
8950 {}%
8951 \fi%
8952 \fi%
8953 \listxadd{\@msdata@list}{%
8954     \@msd@options@iffullpage%
8955     \ifluatex%
8956         \csxdef{footnote@luatextextdir}{\the\textdir}%
8957         \csxdef{footnote@luatexpardir}{\the\pardir}%
8958     \fi%
8959     \csdef{@this@crossref@start}{\add@msd@c:start:msdata}%
8960     \csdef{@this@crossref@end}{\add@msd@c:end:msdata}%
8961     \unexpanded{%
8962         \def\annot@start{}%
8963         \def\annot@end{}%
8964     }%
8965     \noexpand\csuse{v\@msdata@series footnote}{\@msdata@series}{\{
expandonce\l@d@nums}{\ms@data@label}{\expandonce\data}}%
8966     \reset@msd@options@iffullpage%
8967 }%
8968 }%
8969 {}%
8970 \else%
8971     \numgdef{\add@msd@cR}{\add@msd@cR+\@ne}%
8972     \ifcsdef{@msdata@\add@msd@cR @dataR}{%
8973         \letcs{@data}{\@msdata@\add@msd@cR @dataR}%
8974         \edef\l@d@nums{%
8975             000| % Start page = we don't print it
8976             \csuse{@msdata@\add@msd@cR @linenumberR}| % Start line number
8977             \csuse{@msdata@\add@msd@cR @sublinenumberR}| % Start subline
number, for now, not used
8978             000| % End page number, we don't print it
8979             \ifnumless{\csuse{@msdata@\add@msd@cR @stopabslinenumberR}}{\
csuse{@lastline@forpageR@the\page@numR}}{%
8980                 {\csuse{@msdata@\add@msd@cR @stoplinenumberR}}}%End line number
if in the same page
8981                 {\csuse{@lastline@forpageR@the\page@numR}}}%Otherwise, last
number of the page
8982             |%
8983             \ifnumless{\csuse{@msdata@\add@msd@cR @stopabslinenumberR}}{\
csuse{@lastline@forpageR@the\page@numR}}{%
8984                 {\csuse{@msdata@\add@msd@cR @stopsublinenumberR}}}%End subline
number if in the same page
8985                 {\csuse{@lastsubline@forpageR@the\page@numR}}}%Otherwise, last
number of the page
8986             000| % End sub line number, for now, not used

```

```

8987 \edfont@info%Font
8988 }%
8989 \@msd@options@fullpagefalse%
8990 \if@firstlineofpageR%
8991 \unless\if@msdata@insertedfrompreviouspage%
8992 \ifnumless{\csuse{@lastabsline@forpageR@the\page@numR}}{\
csuse{@msdata@add@msd@c @stopabslinenumberR}+\@one}%
8993 {%
8994 \numdef{\@tmp}{\add@msd@cR+\@one}%
8995 \ifcsdef{@msdata@\@tmp @abslinenumberR}%
8996 {\ifnumequal{\csuse{@msdata@\@tmp @abslinenumberR}}{\csuse{
@lastabsline@forpageR@the\page@numR}}}%
8997 }%
8998 {\@msd@options@fullpagetrue}%
8999 }%
9000 {\@msd@options@fullpagetrue}%
9001 }%
9002 {}%
9003 \fi%
9004 \fi%
9005 \listxadd{\@msdata@list}{%
9006 \@msd@options@iffullpage%
9007 \ifluatex%
9008 \csxdef{footnote@luatextextdir}{\the\textdir}%
9009 \csxdef{footnote@luatexpardir}{\the\pardir}%
9010 \fi%
9011 \csdef{@this@crossref@start}{\add@msd@cR:start:msdata}%
9012 \csdef{@this@crossref@end}{\add@msd@cR:end:msdata}%
9013 \unexpanded{%
9014 \def\annot@start{}}%
9015 \def\annot@end{}}%
9016 }%
9017 \noexpand\csuse{v\@msdata@series footnote}{\@msdata@series}{\
expandonce\ld@nums}{\ms@data@label}{\expandonce\data}}%
9018 \reset@msd@options@iffullpage%
9019 }%
9020 }%
9021 {}%
9022 \fi%
9023 \egroup%
9024 }%
9025 %

```

`\if@msdata@insertedfrompreviouspage` The `\if@msdata@insertedfrompreviouspage` boolean is set to TRUE if `reledmac` automatically inserts data from previous page in the first line of a page.

```

9026 \newif\if@msdata@insertedfrompreviouspage%
9027 %

```

`\add@msdata@firstlineofpage` `\add@msdata@firstlineofpage` is called at the first line of every page. It inserts manuscript data which start on one of the previous pages and continue on this page.

```

9028 \newcommand{\add@msdata@firstlineofpage}{%
9029   \bgroup%
9030   \normalfont%
9031   \unless\ifledRcol{%
9032     \ifcsdef{@msdata@\add@msd@c @data}{%
9033       \ifnumless{\the\absline@num-\@ne}{\csuse{@msdata@\add@msd@c
@stopabslinenumber}}}%
9034       {%
9035         \global\@msdata@insertedfrompreviouspagetrue%
9036         \letcs{\@data}{@msdata@\add@msd@c @data}%
9037         \edef\l@d@nums{%
9038           000}% Start page = we don't print it
9039           \numexpr\the\line@num+\@ne\relax}% Start line number = first line
of the page. As \add@msdata@firstlineofpage is called before line number
has been incremented, we increment it for printing
9040           000}% Start subline number, for now, not used
9041           000}% End page number, we don't print it
9042           \ifnumless{\csuse{@msdata@\add@msd@c @stopabslinenumber}}{\csuse{
@lastabsline@forpage@\the\page@num}}}%
9043           {\csuse{@msdata@\add@msd@c @stoplinenumber}}}%End line number if
in the same page
9044           {\csuse{@lastline@forpage@\the\page@num}}}%Otherwise, last
number of the page
9045           |%
9046           000}% End sub line number, for now, not used
9047           \edefont@info%Font
9048           }%
9049           \@msd@options@fullpagefalse%
9050           \ifnumless{\csuse{@lastabsline@forpage@\the\page@num}}{\csuse{
@msdata@\add@msd@c @stopabslinenumber}+\@ne}%We will test if the ms data is
for the full page
9051           {%
9052             \numdef{\@tmp}{\add@msd@c+\@ne}%
9053             \ifcsdef{@msdata@\@tmp @abslinenumber}%
9054             {\ifnumequal{\csuse{@msdata@\@tmp @abslinenumber}}{\csuse{
@lastabsline@forpage@\the\page@num}}}%
9055             {}%
9056             {\@msd@options@fullpagetrue}%
9057             }%
9058             {\@msd@options@fullpagetrue}%
9059             }%
9060             {}%
9061             \listxadd{\@msdata@list}{%
9062               \@msd@options@iffullpage%
9063               \ifluatex%
9064                 \csxdef{footnote@luatextextdir}{\the\textdir}%
9065                 \csxdef{footnote@luatexpardir}{\the\pardir}%

```

```

9066 \fi%
9067 \csdef{@this@crossref@start}{\add@msd@c:start:msdata}%
9068 \csdef{@this@crossref@end}{\add@msd@c:end:msdata}%
9069 \unexpanded{%
9070 \def\annot@start{}%
9071 \def\annot@end{}%
9072 }%
9073 \noexpand\csuse{v\@msdata@series footnote}{\@msdata@series}{\@
expandonce\l@d@nums}{\ms@data@label}{\expandonce\data}}%
9074 \reset@msd@options@iffullpage%
9075 }%
9076 }%
9077 {\global\@msdata@insertedfrompreviouspagefalse}%
9078 }{}%
9079 \else%
9080 \ifcsdef{@msdata@\add@msd@cR @dataR}{%
9081 \ifnumless{\the\absline@numR-\@one}{\csuse{@msdata@\add@msd@cR
@stopabslinenumberR}}%
9082 {%
9083 \global\@msdata@insertedfrompreviouspagetrue%
9084 \letcs{\@data}{\@msdata@\add@msd@cR @dataR}%
9085 \edef\l@d@nums{%
9086 000}% Start page = we don't print it
9087 \numexpr\the\line@numR+\@one\relax}% Start line number = first
line of the page. As \add@msdata@firstlineofpage is called before line
number has been incremented, we increment it for printing
9088 000}% Start subline number, for now, not used
9089 000}% End page number, we don't print it
9090 \ifnumless{\csuse{@msdata@\add@msd@cR @stopabslinenumberR}}{\@
csuse{@lastline@forpageR@\the\page@numR}}%
9091 {\csuse{@msdata@\add@msd@cR @stoplinenumberR}}%End line number
if in the same page
9092 {\csuse{@lastline@forpageR@\the\page@numR}}%Otherwise, last
number of the page
9093 |%
9094 000}% End sub line number, for now, not used
9095 \edef@info{Font
9096 }%
9097 \@msd@options@fullpagefalse%
9098 \ifnumless{\csuse{@lastabsline@forpageR@\the\page@numR}}{\csuse{
@msdata@\add@msd@cR @stopabslinenumberR}+\@one}%
9099 {%
9100 \numdef{\@tmp}{\add@msd@cR+\@one}%
9101 \ifcsdef{@msdata@\@tmp @abslinenumberR}%
9102 {\ifnumequal{\csuse{@msdata@\@tmp @abslinenumberR}}{\csuse{
@lastabsline@forpageR@\the\page@numR}}%
9103 }%
9104 {\@msd@options@fullpagetrue}%
9105 }%
9106 {\@msd@options@fullpagetrue}%

```



```

9107     }%
9108     {}%
9109     \listxadd{\@msdata@list}{%
9110         \@msd@options@iffullpage%
9111         \ifluatex%
9112             \csxdef{footnote@luatextextdir}{\the\textdir}%
9113             \csxdef{footnote@luatexpardir}{\the\pardir}%
9114         \fi%
9115         \csdef{@this@crossref@start}{\add@msd@cR:start:msdata}%
9116         \csdef{@this@crossref@end}{\add@msd@cR:end:msdata}%
9117         \unexpanded{%
9118             \def\annot@start{}%
9119             \def\annot@end{}%
9120         }%
9121         \noexpand\csuse{v\@msdata@series footnote}{\@msdata@series}{\{
expandonce\l@d@nums}{\ms@data@label}{\expandonce\@data}}}%
9122         \reset@msd@options@iffullpage%
9123     }%
9124 }%
9125 {\global\@msdata@insertedfrompreviouspagefalse}%
9126 }{}%
9127 \fi%
9128 \egroup%
9129 }%
9130 %

```

XXXI.6 Inserting footnote

Just before inserting standard insert (familiar and critical footnotes, sidenotes), we call `\insert@msdata` to insert manuscripts data's footnotes.

```

\insert@msdata 31 \newcommand{\insert@msdata}{%
9132     \def\do##1{##1}%
9133     \dolistloop{\@msdata@list}%
9134     \global\let\@msdata@list\relax%
9135 }%
9136 %

```

XXXI.7 Other

`\@msd@options@iffullpage` `\@msd@options@iffullpage` sets some options if the manuscripts data are for all the page. `\reset@msd@options@iffullpage` resets them after the footnote. `\if@msd@options@fullpage` is switch to true in `add@msdata@firstlineofpage` if these option must be inserted.

```

9137 \newif\if@msd@options@fullpage%
9138 \newcommand{\@msd@options@iffullpage}[0]{%
9139     \if@msd@options@fullpage%
9140         \noexpand\toggletrue{nonum@}%

```

```

9141 \ifdefvoid{\ms@data@label}%
9142     {\noexpand\toggletrue{nosep@}}}%
9143     }%
9144 \fi%
9145 }%
9146 \newcommand{\reset@msd@options@iffullpage}[0]{%
9147     \noexpand\togglefalse{nonum@}%
9148     \noexpand\togglefalse{nosep@}%
9149 }%
9150 %

```

XXXII Arrays and tables

XXXII.1 Preamble: macro as environment

The following is borrowed, and renamed, from the `amsmath` package. See also the CTT thread “`eeq` and `amstex`”, 1995/08/31, started by Keith Reckdahl and ended definitively by David M. Jones.

Several of the `[math]` macros scan their body twice. This means we must collect all text in the body of an environment form before calling the macro.

`\@emptytoks` This is actually defined in the `amsgen` package.

```

9151 \newtoks\@emptytoks
9152
9153 %

```

The rest is from `amsmath`.

`\l@denvbody` A token register to contain the body.

```

9154 \newtoks\l@denvbody
9155
9156 %

```

`\addtol@denvbody` `\addtol@denvbody{arg}` adds `arg` to the token register `\l@denvbody`.

```

9157 \newcommand{\addtol@denvbody}[1]{%
9158     \global\l@denvbody\expandafter{\the\l@denvbody#1}}
9159 %

```

`\if@edtabular` A boolean set to true inside a `reledmac`’ tabular environment.

```

9160 \newif\if@edtabular%
9161 %

```

`\l@dcollect@body` The macro `\l@dcollect@body` starts the scan for the `\end{env}` command of the current environment. It takes a macro name as argument. This macro is supposed to take the whole body of the environment as its argument. For example, given `cenv#1{...}` as a macro that processes #1, then the environment form, `\begin{env}` would call `\l@dcollect@body\cenv`.

```

9162 \newcommand{\l@dcollect@body}[1]{%
9163   \ifmode\else%
9164     \\\%Ensure that we do not have spurious indentation at the very first
line, caused by some text before.
9165   \fi%
9166   \l@denvbody{\expandafter#1\expandafter{\the\l@denvbody}}%
9167   \edef\processl@denvbody{\the\l@denvbody\noexpand\end{\@currenvir}}%
9168   \l@denvbody\@emptytoks \def\l@dbegin@stack{b}%
9169   \begingroup
9170     \edtabulartrue%
9171     \expandafter\let\csname\@currenvir\endcsname\l@dcollect@@body
9172     \edef\processl@denvbody{\expandafter\noexpand\csname\@currenvir\endcsname}%
9173     \processl@denvbody%
9174   }%
9175
9176 %

```

`\l@dpush@begins` When adding a piece of the current environment's contents to `\l@denvbody`, we scan it to check for additional `\begin` tokens, and add a "b" to the stack for any that we find.

```

9177 \def\l@dpush@begins#1\begin#2{%
9178   \ifx\end#2\else b\expandafter\l@dpush@begins\fi}
9179
9180 %

```

`\l@dcollect@@body` `\l@dcollect@@body` takes two arguments: the first will consist of all text up to the next `\end` command, and the second will be the `\end` command's argument. If there are any extra `\begin` commands in the body text, a marker is pushed onto a stack by the `\l@dpush@begins` function. Empty state for this stack means we have reached the `\end` that matches our original `\begin`. Otherwise we need to include the `\end` and its argument in the material we are adding to the environment body accumulator.

```

9181 \def\l@dcollect@@body#1\end#2{%
9182   \edef\l@dbegin@stack{\l@dpush@begins#1\begin\end
9183     \expandafter\@gobble\l@dbegin@stack}%
9184   \ifx\@empty\l@dbegin@stack
9185     \endgroup
9186     \@checkend{#2}%
9187     \addtol@denvbody{#1}%
9188   \else
9189     \addtol@denvbody{#1\end{#2}}%
9190   \fi
9191   \processl@denvbody % A little tricky! Note the grouping

```

9192 }
 9193
 9194 %

There was a question on CTT about how to use `\collect@body` for a macro taking an argument. The following is part of that thread.

From: Heiko Oberdiek <oberdiek@uni-freiburg.de>
 Newsgroups: comp.text.tex
 Subject: Re: Using `\collect@body` with commands that take >1 argument
 Date: Fri, 08 Aug 2003 09:03:20 +0200

eed132@psu.edu (Evan) wrote:
 > I'm trying to make a new Latex environment that acts like the
 > `\colorbox` command that is part of the color package. I looked through
 > the FAQ and ran across this bit about using the `\collect@body` command
 > that is part of AMSLaTeX:
 > <http://www.tex.ac.uk/cgi-bin/texfaq2html?label=cmdasenv>
 >
 > It almost works. If I do something like the following:
 > `\newcommand{\redbox}[1]{\colorbox{red}{#1}}`
 >
 > `\makeatletter`
 > `\newenvironment{redbox}{\collect@body \redbox}{}`

You will get an error message: Command `\redbox` already defined.
 Thus you must rename either the command `\redbox` or the environment name.

```
> \begin{coloredbox}{blue}
>   Yadda yadda yadda... this is on a blue background...
> \end{coloredbox}
> and can't figure out how to make the \collect@body take this.

> \collect@body \colorbox{red}
> \collect@body {\colorbox{red}}
```

The argument of `\collect@body` has to be one token exactly.

```
\documentclass{article}
\usepackage{color}
\usepackage{amsmath}

\newcommand{\redbox}[1]{\colorbox{red}{#1}}
\makeatletter
\newenvironment{coloredbox}[1]{%
  \def\next@{\colorbox{#1}}%
  \collect@body\next@
}{}
```

```

% ignore spaces at begin and end of environment
\newenvironment{coloredboxII}[1]{%
  \def\next@{\mycoloredbox{#1}}%
  \collect@body\next@
}{%}
\newcommand{\mycoloredbox}[2]{%
  \colorbox{#1}{\ignorespaces#2\unskip}%
}

% support of optional color model argument
\newcommand\coloredboxIII\endcsname{}
\def\coloredboxIII#1#2{%
  \@coloredboxIII{#1}%
}
\def\@coloredboxIII#1#2{%
  \def\next@{\mycoloredboxIII{#1}{#2}}%
  \collect@body\next@
}
\newcommand{\mycoloredboxIII}[3]{%
  \colorbox{#1}{#2}{\ignorespaces#3\unskip}%
}

\makeatother

\begin{document}
  Black text before
  \begin{coloredbox}{blue}
    Hello World
  \end{coloredbox}
  Black text after

  Black text before
  \begin{coloredboxII}{blue}
    Hello World
  \end{coloredboxII}
  Black text after

  Black text before
  \begin{coloredboxIII}[rgb]{0,0,1}
    Hello World
  \end{coloredboxIII}
  Black text after

\end{document}

Yours sincerely
  Heiko <oberdiek@uni-freiburg.de>

```

XXXII.2 Tabular environments

This is based on the work by Herbert Breger in developing `tabmac.tex`.

The original `tabmac.tex` file was void of comments or any explanatory text other than the above notice. The algorithm is Breger's. Peter Wilson have made some cosmetic changes to the original code and reimplemented some things so they are more LaTeX-like. All the commentary are from Peter Wilson, as are any mistake or errors.

However, Maïeul Rouquette has modified code in order to add new features of `eledmac` and `reledmac`.

XXXII.2.1 Disabling and restoring commands

`\l@dtabnoexpands` More no expansion for critical and familiar footnotes in tabular environment.

```

9195 \newcommand*{\l@dtabnoexpands}{%
9196   \let\rtab=0%
9197   \let\ctab=0%
9198   \let\ltab=0%
9199   \let\rtabtext=0%
9200   \let\ltabtext=0%
9201   \let\ctabtext=0%
9202   \let\edbeforetab=0%
9203   \let\edaftertab=0%
9204   \let\edatleft=0%
9205   \let\edatright=0%
9206   \let\edvertline=0%
9207   \let\edvertdots=0%
9208   \let\edrowfill=0%
9209 }
9210
9211 %

```

`\disable@familiarnotes` Macros to disable and restore familiar notes, to prevent them from printing multiple times in `edtabularx` and `edarrayx` environments.

```

9212 \newcommand{\disable@familiarnotes}{%
9213   \unless\ifnofamiliar%
9214     \def\do##1{%
9215       \csletcs{footnote@##1}{footnote##1}%
9216       \expandafter\renewcommand \csname footnote##1\endcsname[1]{%
9217         \protected@csxdef{@thefnmark##1}{\csuse{thefootnote##1}}%
9218         \csuse{@footnotemark##1}%
9219       }%
9220     }%
9221     \dolistloop{\@series}%
9222     \fi%
9223   }%
9224 \newcommand{\restore@familiarnotes}{%
9225   \unless\ifnofamiliar%
9226     \def\do##1{%

```

```

9227 \csletcs{footnote##1}{footnote@@##1}%
9228 }%
9229 \dolistloop{\@series}%
9230 \fi%
9231 }%
9232 %
9233 %

```

`\disable@sidenotes` The same for sidenotes.

```

\restore@sidenotes
9234 \newcommand{\disable@sidenotes}{%
9235 \let\@@ledrightnote\ledrightnote%
9236 \let\@@ledleftnote\ledleftnote%
9237 \let\@@ledsidenote\ledsidenote%
9238 \let\ledrightnote@gobble%
9239 \let\ledleftnote@gobble%
9240 \let\ledsidenote@gobble%
9241 }%
9242 \newcommand{\restore@sidenotes}{%
9243 \let\ledrightnote\@@ledrightnote%
9244 \let\ledleftnote\@@ledleftnote%
9245 \let\ledsidenote\@@ledsidenote%
9246 }%
9247 %

```

`\disable@endnotes` The same for endnotes.

```

\restore@endnotes
9248 \newcommand{\disable@endnotes}{%
9249 \unless\ifnoend%
9250 \def\do##1{%
9251 \csletcs{##1@endnote}{##1endnote}%
9252 \expandafter\renewcommand \csname ##1endnote\endcsname[1]{}%
9253 }%
9254 \dolistloop{\@series}%
9255 \fi%
9256 }%
9257 \newcommand{\restore@endnotes}{%
9258 \unless\ifnofamiliar%
9259 \def\do##1{%
9260 \csletcs{##1endnote}{##1@endnote}%
9261 }%
9262 \dolistloop{\@series}%
9263 \fi%
9264 }%
9265 %

```

`\disable@notes` Disable/restore side, familiar and end notes.

```

\restore@notes
9266 \newcommand{\disable@notes}{%
9267 \disable@sidenotes%

```

```

9268 \disable@famiarnotes%
9269 \disable@endnotes%
9270 }%
9271 \newcommand{\restore@notes}{%
9272 \restore@sidenotes%
9273 \restore@famiarnotes%
9274 \restore@endnotes%
9275 }%
9276 %

```

\EDTEXT We need to be able to modify the `\edtext` macros and also restore their original definitions.

\xedtext

```

9277 \let\EDTEXT=\edtext
9278 \newcommand{\xedtext}[2]{\EDTEXT{#1}{#2}}
9279 %

```

\EDLABEL We need to be able to modify and restore the `\edlabel` macro.

\xedlabel

```

9280 \let\EDLABEL=\edlabel
9281 \newcommand*{\xedlabel}[1]{\EDLABEL{#1}}
9282 %

```

\xedindex Macros supporting modification and restoration of `\edindex`.

\nulledindex

```

9283 \AtBeginDocument{\let\xedindex\edindex}%
9284 \newcommand{\nulledindex}[2][\jobname]{\@bsphack\@esphack}
9285
9286 %

```

\@line@num Macro supporting restoration of `\linenum`.

```

9287 \let\@line@num=\linenum
9288 %

```

\l@dgobbleoptarg `\l@dgobbleoptarg[⟨arg⟩]{⟨arg⟩}` replaces these two arguments (first is optional) by `\relax`.

```

9289 \newcommand*{\l@dgobbleoptarg}[2][\relax]%
9290
9291 %

```

\l@secondmandarg `\l@secondoptarg[⟨arg⟩]{⟨arg⟩}` gobble the first (optional) argument, and expand to the second (mandatory) argument.

```

9292 \NewExpandableDocumentCommand{\l@secondmandarg}{om}{#2}%
9293 %

```



```

\Relax9294 \let\Relax=\relax
\NEXT9295 \let\NEXT=\next
9296
9297 %

```

\l@dmodforedtext Modify and restore various macros for when \edtext is used.

```

\l@drestoreforedtext9298 \newcommand{\l@dmodforedtext}{%
9299 \let\edtext\relax
9300 \def\do##1{\global\csletcs{##1footnote}{\l@dgobbleoptarg}}%
9301 \dolistloop{\@series}%
9302 \let\edindex\nulledindex
9303 \let\linenum\@gobble}
9304 \newcommand{\l@drestoreforedtext}{%
9305 \def\do##1{\global\csletcs{##1footnote}{##1@footnote}}
9306 \dolistloop{\@series}%
9307 \let\edindex\xedindex}
9308 %

```

\l@dnullfills Nullify and restore some column fillers, etc.

```

\l@drestorefills9309 \newcommand{\l@dnullfills}{%
9310 \def\edlabel##1{%
9311 \def\edrowfill##1##2##3{%
9312 }
9313 \newcommand{\l@drestorefills}{%
9314 \def\edrowfill##1##2##3{\@EDROWFILL@{##1}{##2}{##3}}%
9315 }
9316
9317 %

```

\letsforverteilen Gathers some lets and other code that is common to the *verteilen* macros.

```

9318 \newcommand{\letsforverteilen}{%
9319 \let\edtext\xedtext
9320 \let\edindex\xedindex
9321 \def\do##1{\global\csletcs{##1footnote}{##1@footnote}}
9322 \dolistloop{\@series}%
9323 \let\linenum\@line@num
9324 \hilfe\skip=\l@dcolwidth%
9325 \advance\hilfe\skip by -\wd\hilfebox
9326 \def\edlabel##1{\xedlabel{##1}}
9327
9328 %

```

\disablel@dtabfeet Declarations for using or using \edtext inside tabulars. The default at this point is for
\enablel@dtabfeet \edtext.

```

9329 \newcommand\disablel@dtabfeet{\l@dmodforedtext}%
9330 \newcommand\enablel@dtabfeet{\l@drestoreforedtext}%
9331 %

```

XXXII.2.2 Counters, boxes and lengths

`\l@dampcount` `\l@dampcount` is a counter for the & column dividers and `\l@dcolcount` is a counter for the columns.

```
9332 \newcount\l@dampcount
9333 \l@dampcount=1\relax
9334 \newcount\l@dcolcount
9335 \l@dcolcount=0\relax
9336
9337 %
```

`\hilfsbox` Some (temporary) helper items.

```
\hilfsskip
9338 \newbox\hilfsbox
\Hilfsbox
9339 \newskip\hilfsskip
\hilfscount
9340 \newbox\Hilfsbox
9341 \newcount\hilfscount
9342
9343 %
```

30 columns should be adequate (compared to the original 60). These are the column widths. (Originally these were German spelled numbers e.g., `\eins`, `\zwei`, etc).

```
9344 \newdimen\dcoli
9345 \newdimen\dcolii
9346 \newdimen\dcoliii
9347 \newdimen\dcoliv
9348 \newdimen\dcolv
9349 \newdimen\dcolvi
9350 \newdimen\dcolvii
9351 \newdimen\dcolviii
9352 \newdimen\dcolix
9353 \newdimen\dcolx
9354 \newdimen\dcolxi
9355 \newdimen\dcolxii
9356 \newdimen\dcolxiii
9357 \newdimen\dcolxiv
9358 \newdimen\dcolxv
9359 \newdimen\dcolxvi
9360 \newdimen\dcolxvii
9361 \newdimen\dcolxviii
9362 \newdimen\dcolxix
9363 \newdimen\dcolxx
9364 \newdimen\dcolxxi
9365 \newdimen\dcolxxii
9366 \newdimen\dcolxxiii
9367 \newdimen\dcolxxiv
9368 \newdimen\dcolxxv
9369 \newdimen\dcolxxvi
9370 \newdimen\dcolxxvii
```

```

9371 \newdimen\dcollxxviii
9372 \newdimen\dcollxxix
9373 \newdimen\dcollxxx
9374 \newdimen\dcollerr    % added for error handling
9375
9376 %

```

\l@dcollwidth This is a cunning way of storing the columnwidths indexed by the column number \l@dcollcount, like an array. (was \Dimenzuordnung)

```

9377 \newcommand{\l@dcollwidth}{\ifcase \the\l@dcollcount \dcoli %???
9378 \or \dcoli \or \dcolii \or \dcoliii
9379 \or \dcoliv \or \dcolv \or \dcolvi
9380 \or \dcolvii \or \dcolviii \or \dcolix \or \dcolx
9381 \or \dcolxi \or \dcolxii \or \dcolxiii
9382 \or \dcolxiv \or \dcolxv \or \dcolxvi
9383 \or \dcolxvii \or \dcolxviii \or \dcolxix \or \dcolxx
9384 \or \dcolxxi \or \dcolxxii \or \dcolxxiii
9385 \or \dcolxxiv \or \dcolxxv \or \dcolxxvi
9386 \or \dcolxxvii \or \dcolxxviii \or \dcolxxix \or \dcolxxx
9387 \else \dcollerr \fi}
9388
9389 %

```

\step1@dcollcount This increments the column counter, and issues an error message if it is too large.

```

9390 \newcommand*{\step1@dcollcount}{\advance\l@dcollcount\@ne
9391 \ifnum\l@dcollcount>30\relax
9392 \led@err@TooManyColumns
9393 \fi}
9394
9395 %

```

\l@dsetmaxcolwidth Sets the column width to the maximum value seen so far.

```

9396 \newcommand{\l@dsetmaxcolwidth}{%
9397 \ifdim\l@dcollwidth < \wd\hilfsbox
9398 \l@dcollwidth = \wd\hilfsbox
9399 \else \relax \fi}
9400
9401 %

```

\measuremcell Measure (recursively) the width required for a math cell.

```

9402 \def\measuremcell #1&{%
9403 \ifx #1\ \ifnum\l@dcollcount=0\let\NEXT\relax%
9404 \else\l@dcheckcols%
9405 \l@dcollcount=0%
9406 \let\NEXT\measuremcell%
9407 \fi%

```

```

9408 \else\setbox\hilfsbox=\hbox{$\displaystyle{#1}$}%
9409 \step1@dcolcount%
9410 \l@dsetmaxcolwidth%
9411 \let\NEXT\measuremcell%
9412 \fi\NEXT}
9413
9414 %

```

\measuretcell Measure (recursively) the width required for a text cell.

```

9415 \def\measuretcell #1{%
9416 \ifx #1\ \ifnum\l@dcolcount=0\let\NEXT\relax%
9417 \else\l@dcheckcols%
9418 \l@dcolcount=0%
9419 \let\NEXT\measuretcell%
9420 \fi%
9421 \else\setbox\hilfsbox=\hbox{#1}%
9422 \step1@dcolcount%
9423 \l@dsetmaxcolwidth%
9424 \let\NEXT\measuretcell%
9425 \fi\NEXT}
9426
9427 %

```

\measuremrow Measure (recursively) the width required for a math row.

```

9428 \def\measuremrow #1{%
9429 \ifx #1\let\NEXT\relax%
9430 \else\measuremcell #1\&\&\&%
9431 \let\NEXT\measuremrow%
9432 \fi\NEXT}
9433 %

```

\measuretrow Measure (recursively) the width required for a text row.

```

9434 \def\measuretrow #1{%
9435 \ifx #1\let\NEXT\relax%
9436 \else\measuretcell #1\&\&\&%
9437 \let\NEXT\measuretrow%
9438 \fi\NEXT}
9439
9440 %

```

\edtabcolsep The length \edtabcolsep controls the distance between columns.

```

9441 \newskip\edtabcolsep
9442 \global\edtabcolsep=10pt
9443
9444 %

```

```
\variab45 \newcommand{\variab}{\relax}
```

```
9446
9447 %
```

\l@dccheckcols Check that the number of columns is consistent.

```
9448 \newcommand*{\l@dccheckcols}{%
9449   \ifnum\l@dcolcount=1\relax
9450   \else
9451     \ifnum\l@dampcount=1\relax
9452     \else
9453       \ifnum\l@dcolcount=\l@dampcount\relax
9454       \else
9455         \l@d@err@UnequalColumns
9456       \fi
9457     \fi
9458     \l@dampcount=\l@dcolcount
9459   \fi}
9460
9461 %
```

\edfilldimen A length.

```
9462 \newdimen\edfilldimen
9463 \edfilldimen=0pt
9464
9465 %
```

\c@addcolcount A counter to hold the number of a column. We use a roman number so that we can grab the column dimension from `\dcol`. We do not use the `\roman` \TeX command, because some packages, like `babel` can override it in some specific cases (Greek, for example).

\theadcolcount

```
9466 \newcounter{addcolcount}
9467 \renewcommand{\theadcolcount}{\romannumeral \c@addcolcount}
9468 %
```

XXXII.2.3 Tabular typesetting

\setmcellright Typeset (recursively) cells of display math right justified.

```
9469 \def\setmcellright #1{\def\edlabel##1}%
9470   \let\edindex\nulledindex
9471   \ifx #1\ \ifnum\l@dcolcount=0%\removelastskip
9472     \let\Next\relax%
9473   \else\l@dcolcount=0%
9474     \let\Next=\setmcellright%
9475   \fi%
9476 \else%
9477   \disablel@dtabfeet%
```

```

9478 \stepl@dc colcount%
9479 \disable@notes%
9480 \setbox\hilfsbox=\hbox{$\displaystyle{#1}$}%
9481 \restore@notes%
9482 \letsforverteilen%
9483 \hskip\hilfsskip$\displaystyle{#1}$%
9484 \hskip\edtabcolsep%
9485 \let\Next=\setmcelllright%
9486 \fi\Next}
9487
9488 %

```

\settcellright Typeset (recursively) cells of text right justified.

```

9489 \def\settcellright #1&{\def\edlabel##1{}}%
9490 \let\edindex\nulledindex
9491 \ifx #1\\ \ifnum\l@dc colcount=0%\removelastskip
9492 \let\Next\relax%
9493 \else\l@dc colcount=0%
9494 \let\Next=\settcellright%
9495 \fi%
9496 \else%
9497 \disablel@dtabfeet%
9498 \stepl@dc colcount%
9499 \disable@notes%
9500 \setbox\hilfsbox=\hbox{#1}%
9501 \restore@notes%
9502 \letsforverteilen%
9503 \hskip\hilfsskip#1%
9504 \hskip\edtabcolsep%
9505 \let\Next=\settcellright%
9506 \fi\Next}
9507 %

```

\setmcellleft Typeset (recursively) cells of display math left justified.

```

9508 \def\setmcellleft #1&{\def\edlabel##1{}}%
9509 \let\edindex\nulledindex
9510 \ifx #1\\ \ifnum\l@dc colcount=0 \let\Next\relax%
9511 \else\l@dc colcount=0%
9512 \let\Next=\setmcellleft%
9513 \fi%
9514 \else \disablel@dtabfeet%
9515 \stepl@dc colcount%
9516 \disable@notes%
9517 \setbox\hilfsbox=\hbox{$\displaystyle{#1}$}%
9518 \restore@notes%
9519 \letsforverteilen%
9520 $\displaystyle{#1}$\hskip\hilfsskip\hskip\edtabcolsep%
9521 \let\Next=\setmcellleft%

```

```

9522 \fi\Next}
9523
9524 %

```

\settcclleft Typeset (recursively) cells of text left justified.

```

9525 \def\settcclleft #1&{\def\edlabel##1{}}%
9526 \let\edindex\nulledindex
9527 \ifx #1\\ \ifnum\l@dc@colcount=0 \let\Next\relax%
9528 \else\l@dc@colcount=0%
9529 \let\Next=\settcclleft%
9530 \fi%
9531 \else \disablel@dtabfeet%
9532 \stepl@dc@colcount%
9533 \disable@notes%
9534 \setbox\hilfsbox=\hbox{#1}%
9535 \restore@notes%
9536 \letsforverteilen%
9537 #1\hskip\hilfe@skip\hskip\edtabcolsep%
9538 \let\Next=\settcclleft%
9539 \fi\Next}
9540 %

```

\setmcellcenter Typeset (recursively) cells of display math centered.

```

9541 \def\setmcellcenter #1&{\def\edlabel##1{}}%
9542 \let\edindex\nulledindex
9543 \ifx #1\\ \ifnum\l@dc@colcount=0\let\Next\relax%
9544 \else\l@dc@colcount=0%
9545 \let\Next=\setmcellcenter%
9546 \fi%
9547 \else \disablel@dtabfeet%
9548 \stepl@dc@colcount%
9549 \disable@notes%
9550 \setbox\hilfsbox=\hbox{$\displaystyle{#1}$}%
9551 \restore@notes%
9552 \letsforverteilen%
9553 \hskip 0.5\hilfe@skip$\displaystyle{#1}$\hskip0.5\hilfe@skip%
9554 \hskip\edtabcolsep%
9555 \let\Next=\setmcellcenter%
9556 \fi\Next}
9557
9558 %

```

\settcclcenter Typeset (recursively) cells of text centered.

```

9559 \def\settcclcenter #1&{\def\edlabel##1{}}%
9560 \let\edindex\nulledindex
9561 \ifx #1\\ \ifnum\l@dc@colcount=0 \let\Next\relax%
9562 \else\l@dc@colcount=0%

```

```

9563             \let\Next=\settcellcenter%
9564             \fi%
9565     \else    \disablel@dtabfeet%
9566             \stepl@dcolcount%
9567             \disable@notes%
9568             \setbox\hilfsbox=\hbox{#1}%
9569             \restore@notes%
9570             \letsforverteilen%
9571             \hskip 0.5\hilfsskip #1\hskip 0.5\hilfsskip%
9572             \hskip\edtabcolsep%
9573             \let\Next=\settcellcenter%
9574     \fi\Next}
9575
9576 %

```

```

\NEXT77 \let\NEXT=\relax

```

```

9578
9579 %

```

\setmrowright Typeset (recursively) rows of right justified math.

```

9580 \def\setmrowright #1\{%
9581     \ifx #1& \let\NEXT\relax
9582     \else \centerline{\setmcellright #1&\\&\\&}
9583     \let\NEXT=\setmrowright
9584     \fi\NEXT}
9585 %

```

\settroright Typeset (recursively) rows of right justified text.

```

9586 \def\settroright #1\{%
9587     \ifx #1& \let\NEXT\relax
9588     \else \centerline{\settcellright #1&\\&\\&}
9589     \let\NEXT=\settroright
9590     \fi\NEXT}
9591
9592 %

```

\setmrowleft Typeset (recursively) rows of left justified math.

```

9593 \def\setmrowleft #1\{%
9594     \ifx #1&\let\NEXT\relax
9595     \else \centerline{\setmcellleft #1&\\&\\&}
9596     \let\NEXT=\setmrowleft
9597     \fi\NEXT}
9598 %

```

\settrorleft Typeset (recursively) rows of left justified text.


```

9599 \def\settrorleft #1\{f%
9600   \ifx #1& \let\NEXT\relax
9601   \else \centerline{\settcclleft #1&\&\&\&}
9602   \let\NEXT=\settrorleft
9603   \fi\NEXT}
9604
9605 %

```

\setmrowcenter Typeset (recursively) rows of centered math.

```

9606 \def\setmrowcenter #1\{f%
9607   \ifx #1& \let\NEXT\relax%
9608   \else \centerline{\setmcclcenter #1&\&\&\&}
9609   \let\NEXT=\setmrowcenter
9610   \fi\NEXT}
9611 %

```

\settrorcenter Typeset (recursively) rows of centered text.

```

9612 \def\settrorcenter #1\{f%
9613   \ifx #1& \let\NEXT\relax
9614   \else \centerline{\settcclcenter #1&\&\&\&}
9615   \let\NEXT=\settrorcenter
9616   \fi\NEXT}
9617
9618 %

```

```

\newcommand{\nullsetzen}19 \newcommand{\nullsetzen}{f%
9620   \step1@dcolcount%
9621   \l@dcolwidth=0pt%
9622   \ifnum\l@dcolcount=30\let\NEXT\relax%
9623   \l@dcolcount=0\relax
9624   \else\let\NEXT\nullsetzen%
9625   \fi\NEXT}
9626
9627 %

```

\edatleft `\edatleft[$\langle math \rangle\{\langle symbol \rangle\}\{\langle len \rangle\}$]. Left $\langle symbol \rangle$, $2\langle len \rangle$ high with prepended $\langle math \rangle$ vertically centered.`

```

9628 \newcommand{\edatleft}[3][\@empty]{f%
9629   \ifx#1\@empty
9630     \vbox to 10pt{\vss\hbox{\$left#2\vrule width0pt height #3
9631       depth 0pt \right. \$hss}\vfil}
9632   \else
9633     \vbox to 4pt{\vss\hbox{\$#1left#2\vrule width0pt height #3
9634       depth 0pt \right. \$}\vfil}
9635   \fi}
9636 %

```

\edatright `\edatright[$\langle math \rangle$]{ $\langle symbol \rangle$ }{ $\langle len \rangle$ }`. Right $\langle symbol \rangle$, $2\langle len \rangle$ high with appended $\langle math \rangle$ vertically centered.

```

9637 \newcommand{\edatright}[3][\@empty]{%
9638   \ifx#1\@empty
9639     \vbox to 10pt{\vss\hbox{$\left.\vrule width0pt height #3
9640       depth 0pt \right#2 $\hss}\vfil}
9641   \else
9642     \vbox to 4pt{\vss\hbox{$\left.\vrule width0pt height #3
9643       depth 0pt \right#2 #1 $\vfil}
9644   \fi}
9645
9646 %

```

\edvertline `\edvertline{ $\langle len \rangle$ }` vertical line $\langle len \rangle$ high.

```

9647 \newcommand{\edvertline}[1]{\vbox to 8pt{\vss\hbox{\vrule height #1}\vfil}}
9648
9649 %

```

\edvertdots `\edvertdots{ $\langle len \rangle$ }` vertical dotted line $\langle len \rangle$ high.

```

9650 \newcommand{\edvertdots}[1]{\vbox to 1pt{\vss\vbox to #1%
9651   {\cleaders\hbox{$\math\hbox{.}\vbox to 0.5em{ }$\vfil}}}
9652
9653 %

```

\l@dtabaddcols `\l@dtabaddcols{ $\langle startcol \rangle$ }{ $\langle endcol \rangle$ }` adds the widths of the columns $\langle startcol \rangle$ through $\langle endcol \rangle$ to `\edfilldimen`. It is a \LaTeX style reimplementaion of the original `\@add@`.

```

9654 \newcommand{\l@dtabaddcols}[2]{%
9655   \l@dcheckstartend{#1}{#2}%
9656   \ifl@dstartendok
9657     \setcounter{addcolcount}{#1}%
9658     \@whilenum \value{addcolcount}<#2\relax \do
9659     {\advance\edfilldimen by \the\csname dcol\theaddcolcount\endcsname
9660     \advance\edfilldimen by \edtabcolsep
9661     \stepcounter{addcolcount}}%
9662     \advance\edfilldimen by \the\csname dcol\theaddcolcount\endcsname
9663   \fi
9664 }
9665
9666 %

```

\ifl@dstartendok `\l@dcheckstartend{ $\langle startcol \rangle$ }{ $\langle endcol \rangle$ }` checks that the values of $\langle startcol \rangle$ and $\langle endcol \rangle$ are sensible. If they are then `\ifl@dstartendok` is set TRUE, otherwise it is set FALSE.

```

9667 \newif\ifl@dstartendok
9668 \newcommand{\l@dcheckstartend}[2]{%

```

```

9669 \l@dstartendoktrue
9670 \ifnum #1<\@ne
9671   \l@dstartendokfalse
9672   \led@err@LowStartColumn
9673 \fi
9674 \ifnum #2>30\relax
9675   \l@dstartendokfalse
9676   \led@err@HighEndColumn
9677 \fi
9678 \ifnum #1>#2\relax
9679   \l@dstartendokfalse
9680   \led@err@ReverseColumns
9681 \fi
9682 }
9683
9684 %

```

\edrowfill **\edrowfill{<startcol>}{<endcol>}** fill fills columns *<startcol>* to *<endcol>* inclusive with *<fill>* (e.g. `\hrulefill`, `\upbracefill`). This is a \LaTeX style reimplementation and generalization of the original `\waklam`, `\Waklam`, `\waklamec`, `\wastricht` and `\wapunktel` macros.

```

9685 \newcommand*{\edrowfill}[3]{%
9686   \l@dtabaddcols{#1}{#2}%
9687   \hb@xt@ \the\l@dcowidth{\hb@xt@ \the\edfilldimen{#3}\hss}}
9688 \let\@edrowfill=\edrowfill
9689 \def\@EDROWFILL@#1#2#3{\@edrowfill@{#1}{#2}{#3}}
9690
9691 %

```

\edbeforetab The macro `\edbeforetab{<text>}{<math>}` puts *<text>* at the left margin before array cell entry *<math>*. Conversely, the macro `\edaftertab{<math>}{<text>}` puts *<text>* at the right margin after array cell entry *<math>*. `\edbeforetab` should be in the first column and `\edaftertab` in the last column. The following macros support these.

\leftltab `\leftltab{<text>}` for `\edbeforetab` in `\ltab`.

```

9692 \newcommand{\leftltab}[1]{%
9693   \hb@xt@\z@{\vbox{\edtabindent%
9694     \moveleft\Hilfsskip\hbox{\ #1}}\hss}}
9695
9696 %

```

\leftrtab `\leftrtab{<text>}{<math>}` for `\edbeforetab` in `\rtab`.

```

9697 \newcommand{\leftrtab}[2]{%
9698   #2\hb@xt@\z@{\vbox{\edtabindent%
9699     \advance\Hilfsskip by\dcoli%
9700     \moveleft\Hilfsskip\hbox{\ #1}}\hss}}
9701
9702 %

```

`\leftctab` `\leftctab{<text>}{<math>}` for `\edbeforetab` in `\ctab`.

```

9703 \newcommand{\leftctab}[2]{%
9704     \hb@xt@#2{\vbox{\edtabindent\l@dcolcount=\l@dampcount%
9705     \advance\Hilfsskip by 0.5\dcoli%
9706     \setbox\hilfsbox=\hbox{\def\edlabel##1{}%
9707     \disablel@dtabfeet$\displaystyle{#2}$}%
9708     \advance\Hilfsskip by -0.5\wd\hilfsbox%
9709     \moveleft\Hilfsskip\hbox{\ #1}}\hss}%
9710     #2}
9711
9712 %

```

`\rightctab` `\rightctab{<math>}{<text>}` for `\edaftertab` in `\ctab`.

```

9713 \newcommand{\rightctab}[2]{%
9714     \setbox\hilfsbox=\hbox{\def\edlabel##1{}%
9715     \disablel@dtabfeet#2}\l@dampcount=\l@dcolcount%
9716     #1\hb@xt@#2{\vbox{\edtabindent\l@dcolcount=\l@dampcount%
9717     \advance\Hilfsskip by 0.5\l@dcolwidth%
9718     \advance\Hilfsskip by -\wd\hilfsbox%
9719     \setbox\hilfsbox=\hbox{\def\edlabel##1{}%
9720     \disablel@dtabfeet$\displaystyle{#1}$}%
9721     \advance\Hilfsskip by -0.5\wd\hilfsbox%
9722     \advance\Hilfsskip by \edtabcolsep%
9723     \moveright\Hilfsskip\hbox{ #2}}\hss}%
9724     }
9725
9726 %

```

`\rightltab` `\rightltab{<math>}{<text>}` for `\edaftertab` in `\ltab`.

```

9727 \newcommand{\rightltab}[2]{%
9728     \setbox\hilfsbox=\hbox{\def\edlabel##1{}%
9729     \disablel@dtabfeet#2}\l@dampcount=\l@dcolcount%
9730     #1\hb@xt@#2{\vbox{\edtabindent\l@dcolcount=\l@dampcount%
9731     \advance\Hilfsskip by\l@dcolwidth%
9732     \advance\Hilfsskip by-\wd\hilfsbox%
9733     \setbox\hilfsbox=\hbox{\def\edlabel##1{}%
9734     \disablel@dtabfeet$\displaystyle{#1}$}%
9735     \advance\Hilfsskip by-\wd\hilfsbox%
9736     \advance\Hilfsskip by\edtabcolsep%
9737     \moveright\Hilfsskip\hbox{ #2}}\hss}%
9738     }
9739
9740 %

```

`\rightrtab` `\rightrtab{<math>}{<text>}` for `\edaftertab` in `\rtab`.

```

9741 \newcommand{\rightrtab}[2]{%

```

```

9742 \setbox\hilfsbox=\hbox{\def\edlabel##1}{%
9743 \disablel@dtabfeet#2}%
9744 #1\hb@xt@#2{\vbox{\edtabindent%
9745 \advance\Hilfsskip by-\wd\hilfsbox%
9746 \advance\Hilfsskip by\edtabcolsep%
9747 \moveright\Hilfsskip\hbox{ #2}}\hss}%
9748 }
9749
9750 %

```

\rtab `\rtab{<body>}` typesets `<body>` as an array with the entries right justified.
\edbeforetab The process is first to measure the `<body>` to get the column widths, and then in a
\edaftertab second pass to typeset the body.

```

9751 \newcommand{\rtab}[1]{%
9752 \l@dnnullfills
9753 \def\edbeforetab##1##2{\lefttab{##1}{##2}}%
9754 \def\edaftertab##1##2{\righttab{##1}{##2}}%
9755 \measurebody{#1}%
9756 \l@drestorefills
9757 \variab
9758 \setmrowright #1\&\&\&%
9759 \enablel@dtabfeet}
9760
9761 %

```

\measurebody `\measurebody{<body>}` measures the array `<body>`.

```

9762 \newcommand{\measurebody}[1]{%
9763 \disablel@dtabfeet%
9764 \l@dcolcount=0%
9765 \nullsetzen%
9766 \l@dcolcount=0
9767 \measuremrow #1\&\&\&%
9768 \global\l@dampcount=1}
9769
9770 %

```

\rtabtext `\rtabtext{<body>}` typesets `<body>` as a tabular with the entries right justified.

```

9771 \newcommand{\rtabtext}[1]{%
9772 \l@dnnullfills
9773 \measurebody{#1}%
9774 \l@drestorefills
9775 \variab
9776 \setthrowright #1\&\&\&%
9777 \enablel@dtabfeet}
9778
9779 %

```

`\measuretbody` `\measuretbody{<body>}` measures the tabular <body>.

```

9780 \newcommand{\measuretbody}[1]{%
9781   \disable@notes%
9782   \disablel@dtabfeet%
9783   \l@dcolcount=0%
9784   \nullsetzen%
9785   \l@dcolcount=0
9786   \measuretrrow #1\\&\\%
9787   \restore@notes%
9788   \global\l@dampcount=1}
9789
9790 %

```

`\ltab` Array with entries left justified.

```

\edbeforetab
\edaftertab \newcommand{\ltab}[1]{%
9791   \l@dnullfills
9792   \def\edbeforetab##1##2{\leftltab{##1}{##2}}%
9793   \def\edaftertab##1##2{\rightltab{##1}{##2}}%
9794   \measuretbody{#1}%
9795   \l@drestorefills
9796   \variab
9797   \setmrowleft #1\\&\\%
9798   \enablel@dtabfeet}
9799
9800 %
9801

```

`\ltabtext` Tabular with entries left justified.

```

9802 \newcommand{\ltabtext}[1]{%
9803   \l@dnullfills
9804   \measuretbody{#1}%
9805   \l@drestorefills
9806   \variab
9807   \settrrowleft #1\\&\\%
9808   \enablel@dtabfeet}
9809
9810 %

```

`\ctab` Array with centered entries.

```

\edbeforetab
\edaftertab \newcommand{\ctab}[1]{%
9811   \l@dnullfills
9812   \def\edbeforetab##1##2{\leftctab{##1}{##2}}%
9813   \def\edaftertab##1##2{\rightctab{##1}{##2}}%
9814   \measuretbody{#1}%
9815   \l@drestorefills
9816   \variab
9817   \setmrowcenter #1\\&\\%
9818

```

```

9819 \enablel@dtabfeet}
9820
9821 %

```

\ctabtext Tabular with entries centered.

```

9822 \newcommand{\ctabtext}[1]{%
9823 \l@dnnullfills
9824 \measuretbody{#1}%
9825 \l@drestorefills
9826 \variab
9827 \settrrowcenter #1\\&\\%
9828 \enablel@dtabfeet}
9829
9830 %

```

```

\spreadtext31 \newcommand{\spreadtext}[1]{%\l@dcolcount=\l@dampcount%
9832 \hb@xt@ \the\l@dcolwidth{\hbox{#1}\hss}}
9833 %

```

```

\spreadmath34 \newcommand{\spreadmath}[1]{%
9835 \hb@xt@ \the\l@dcolwidth{\hbox{$\displaystyle{#1}$}\hss}}
9836
9837 %

```

\HILFSskip More helpers.

```

\Hilfsskip
9838 \newskip\HILFSskip
9839 \newskip\Hilfsskip
9840
9841 %

```

```

\EDTABINDENT42 \newcommand{\EDTABINDENT}{%
9843 \ifnum\l@dcolcount=30\let\NEXT\relax\l@dcolcount=0%
9844 \else\step\l@dcolcount%
9845 \advance\Hilfsskip by\l@dcolwidth%
9846 \ifdim\l@dcolwidth=0pt\advance\hilfscount\@ne
9847 \else\advance\Hilfsskip by \the\hilfscount\edtabcolsep%
9848 \hilfscount=1\fi%
9849 \let\NEXT=\EDTABINDENT%
9850 \fi\NEXT}%
9851 %

```

\edtabindent (was \tabindent)

```

9852 \newcommand{\edtabindent}{%
9853     \l@dcolumncount=0\relax
9854     \Hilfsskip=0pt%
9855     \hilfscount=1\relax
9856     \EDTABINDENT%
9857     \hilfsskip=\hsize%
9858     \advance\hilfsskip -\Hilfsskip%
9859     \Hilfsskip=0.5\hilfsskip%
9860 }%
9861
9862 %

```

\EDTAB (was \TAB)

```

9863 \def\EDTAB #1|#2|{%
9864     \setbox\tabhilfbox=\hbox{$\displaystyle{#1}$}%
9865     \setbox\tabHilfbox=\hbox{$\displaystyle{#2}$}%
9866     \advance\tabelskip -\wd\tabhilfbox%
9867     \advance\tabelskip -\wd\tabHilfbox%
9868     \unhbox\tabhilfbox\hskip\tabelskip%
9869     \unhbox\tabHilfbox}%
9870
9871 %

```

\EDTABtext (was \TABtext)

```

9872 \def\EDTABtext #1|#2|{%
9873     \setbox\tabhilfbox=\hbox{#1}%
9874     \setbox\tabHilfbox=\hbox{#2}%
9875     \advance\tabelskip -\wd\tabhilfbox%
9876     \advance\tabelskip -\wd\tabHilfbox%
9877     \unhbox\tabhilfbox\hskip\tabelskip%
9878     \unhbox\tabHilfbox}%
9879 %

```

\tabhilfbox Further helpers.

```

9880 \newbox\tabhilfbox
9881 \newbox\tabHilfbox
9882
9883 %

```

XXXII.2.4 Environments

edarrayl edarrayc edarrayr The environment forms for \ltab, \ctab and \rtab.

```

9884 \newenvironment{edarrayl}{\l@dcollect@body\ltab}{\}
9885 \newenvironment{edarrayc}{\l@dcollect@body\ctab}{\}
9886 \newenvironment{edarrayr}{\l@dcollect@body\rtab}{\}
9887
9888 %

```


edtabularl edtabularc edtabularr The environment forms for \ltabtext, \ctabtext and \rtabtext.

```

9889 \newenvironment{edtabularl}{\l@dcollect@body\ltabtext}{\}
9890 \newenvironment{edtabularc}{\l@dcollect@body\ctabtext}{\}
9891 \newenvironment{edtabularr}{\l@dcollect@body\rtabtext}{\}
9892
9893 %

```

XXXIII Quotation's commands

`\initnumbering@quote` This macro, called at the beginning of any numbered section, locally redefines the quotation and quote environments, in order to allow their use inside of numbered sections.

```

\quotation \initnumbering@quote defines quotation environment.
\endquotation
\quote
\endquote
9894 \newcommand{\initnumbering@quote}{\}
9895 \ifnoquotation@else
9896 \renewcommand{\quotation}{\par\leavevmode%
9897 \parindent=1.5em%
9898 \skipnumbering%
9899 \ifautopar%
9900 \vskip-\parskip%
9901 \else%
9902 \vskip\topsep%
9903 \fi%
9904 \global\leftskip=\leftmargin%
9905 \global\rightskip=\leftmargin%
9906 }
9907 \renewcommand{\endquotation}{\par%
9908 \global\leftskip=0pt%
9909 \global\rightskip=0pt%
9910 \leavevmode%
9911 \skipnumbering%
9912 \ifautopar%
9913 \vskip-\parskip%
9914 \else%
9915 \vskip\topsep%
9916 \fi%
9917 }
9918 \renewcommand{\quote}{\par\leavevmode%
9919 \parindent=0pt%
9920 \skipnumbering%
9921 \ifautopar%
9922 \vskip-\parskip%
9923 \else%
9924 \vskip\topsep%
9925 \fi%

```

```

9926             \global\leftskip=\leftmargin%
9927             \global\rightskip=\leftmargin%
9928         }
9929         \renewcommand{\endquote}{\par%
9930             \global\leftskip=0pt%
9931             \global\rightskip=0pt%
9932             \leavevmode%
9933             \skipnumbering%
9934             \ifautopar%
9935                 \vskip-\parskip%
9936             \else%
9937                 \vskip\topsep%
9938             \fi%
9939         }
9940     \fi
9941 }
9942 %

```

XXXIV Section's title commands

XXXIV.1 Commands to disable some feature

`\ledsectnotoc` The `\ledsectnotoc` only disables the `\addcontentsline` macro.

```

9943 \newcommand{\ledsectnotoc}{\let\addcontentsline\@gobblethree}
9944 %

```

`\ledsectnomark` The `\ledsectnomark` only disables the `\chaptermark`, `\sectionmark` and `\subsectionmark` macros.

```

9945 \newcommand{\ledsectnomark}{%
9946     \let\chaptermark\@gobble%
9947     \let\sectionmark\@gobble%
9948     \let\subsectionmark\@gobble%
9949 }
9950 %

```

XXXIV.2 General overview

The system of `\eledxxxx` commands to section text work like this:

1. When one of these commands is called, `reledmac` writes to an auxiliary files:
 - The section level.
 - The section title.
 - The side (when `reledpar` is used).
 - The `pstart` where the command is called.

- If we have starred version or not.
2. `reledmac` adds the title of the section to `pstart`, as normal content. This is to enable critical notes.
 3. When \TeX is run a other time, this file is read. That:
 - Adds the `pstart` number to a list of `pstarts` where a sectioning command is used.
 - Defines a command, the name of which contains the `pstart` number, and which calls the normal \TeX sectioning command.
 4. This last command is called when the `pstart` is effectively printed.

XXXIV.3 `\beforeeledchapter` command

We do not define commands for `\eledsection` and related if the `noeledsec` option is loaded. We use `etoolbox` tests and not the `\ifxxx...\else...\fi` structure to prevent problem of expansions with command after the `\ifxxx` which contains `\fi`. As we patch command inside this test, we need to change the category code of `#` character *before* `\notbool` statement, because the second argument is read with the standard `catcode` (read *The TeXbook* to understand when the `catcode`'s change has effect).

```
9951 \catcode`\#=12
9952 \notbool{@noeled@sec}{%
9953 %
```

`\beforeeledchapter` For technical reasons, not yet solved, page-breaking before chapters can't be made automatically by `eledmac`. Users have to use `\beforeeledchapter`.

```
9954 \ifl@dmemoir
9955   \newcommand\beforeeledchapter{%
9956   \clearforchapter%
9957 }
9958 \else
9959   \newcommand\beforeeledchapter{%
9960   \if@openright%
9961     \cleardoublepage%
9962   \else%
9963     \clearpage%
9964   \fi%
9965 }
9966 \fi
9967 %
```

XXXIV.4 Auxiliary commands

`\print@leftmargin@eledsection` `\print@rightmargin@eledsection` are added by `reledmac` inside the code of sectioning command, in order to affix lines numbers. They include tests for RTL languages.

```

9968 \def\print@rightmargin@eledsection{%
9969   \if@eled@sectioning%
9970     \begingroup%
9971     \if@RTL%
9972       \let\llap\rlap%
9973       \let\leftlinenum\rightlinenum%
9974       \let\leftlinenumR\rightlinenumR%
9975       \let\l@drd@ta\l@dld@ta%
9976       \let\l@drsn@te\l@dlsn@te%
9977     \fi%
9978     \hfill\l@drd@ta \csuse{LR}{\l@drsn@te}%
9979     \endgroup%
9980   \fi%
9981 }%
9982
9983 \def\print@leftmargin@eledsection{%
9984   \if@eled@sectioning%
9985     \leavevmode%
9986     \begingroup%
9987     \if@RTL%
9988       \let\rlap\llap%
9989       \let\rightlinenum\leftlinenum%
9990       \let\rightlinenumR\leftlinenumR%
9991       \let\l@dld@ta\l@drd@ta%
9992       \let\l@dlsn@te\l@drsn@te%
9993     \fi%
9994     \l@dld@ta\csuse{LR}{\l@dlsn@te}%
9995     \endgroup%
9996   \fi%
9997 }%
9998
9999 %

```

XXXIV.5 Patching standard commands

`\M@ssect`
`\@mem@old@ssect`
`\@makechapterhead`
`\@makechapterhead`
`\@makeschapterhead`
`\@ssect`
`\@ssect`

We have to patch L^AT_EX, book and memoir sectioning commands in order to:

- Disable `\edtext` inside.
- Disable page breaking (for `\chapter`).
- Add line numbers and sidenotes.

Unfortunately, Maïeul Rouquette was not able to try if memoir is loaded. That is why `eledmac` tries to define for both standard class and memoir class.

```

10000 \AtBeginDocument{%
10001
10002
10003 \pretocmd{\M@ssect}

```

```

10004 {\let\old@edtext=\edtext%
10005 \let\edtext=\dummy@edtext@showlemma%
10006 }
10007 {}
10008 {}
10009
10010 \apptocmd{\M@sect}
10011 {\let\edtext=\old@edtext}
10012 {}
10013 {}
10014
10015 \patchcmd{\M@sect}
10016 { #9}
10017 { #9%
10018 \print@rightmargin@eledsection%
10019 }
10020 {}
10021 {}
10022
10023 \patchcmd{\M@sect}
10024 {\hskip #3\relax}
10025 {\hskip #3\relax%
10026 \print@leftmargin@eledsection%
10027 }
10028 {}
10029 {}
10030
10031 \patchcmd{\@mem@old@ssect}
10032 {#5}
10033 {#5%
10034 \print@leftmargin@eledsection%
10035 }
10036 {}
10037 {}
10038
10039 \patchcmd{\@mem@old@ssect}
10040 {\hskip #1}
10041 {\hskip #1%
10042 \print@rightmargin@eledsection%
10043 }
10044 {}
10045 {}
10046
10047
10048
10049 \patchcmd{\scr@startchapter}{\if@openright\cleardoublepage\else\clearpage\fi}{%
10050 \if@eled@sectioning\else%
10051 \ifl@dprintingpages\else%
10052 \if@openright\cleardoublepage\else\clearpage\fi}%No clearpage inside a

```

```

\Pages: will keep critical notes from printing on the title page. Here for
scrbook.
10053   \fi%
10054   \fi%
10055   }
10056   {}
10057   {}
10058
10059 \patchcmd{\@makechapterhead}
10060   {#1}
10061   {\print@leftmargin@eledsection%
10062     #1%
10063     \print@rightmargin@eledsection%
10064   }
10065   {}
10066   {}
10067
10068 \patchcmd{\@makechapterhead}% For BIDI
10069   {\if@RTL\raggedleft\else\raggedright\fi}%
10070   {\if@eled@sectioning\else%
10071     \if@RTL\raggedleft\else\raggedright\fi%
10072   \fi%
10073   }%
10074   {}%
10075   {}%
10076
10077 \patchcmd{\@makeschapterhead}
10078   {#1}
10079   {\print@leftmargin@eledsection%
10080     #1%
10081     \print@rightmargin@eledsection%
10082   }
10083   {}
10084   {}
10085
10086 \pretocmd{\@sect}
10087   {\let\old@edtext=\edtext
10088     \let\edtext=\dummy@edtext@showlemma%
10089   }
10090   {}
10091   {}
10092
10093 \apptocmd{\@sect}
10094   {\let\edtext=\old@edtext}
10095   {}
10096   {}
10097
10098 \pretocmd{\@ssect}
10099   {\let\old@edtext=\edtext%
10100   \let\edtext=\dummy@edtext@showlemma%

```

```

10101 }
10102 {}
10103 {}
10104
10105 \apptocmd{\@ssect}
10106   {\let\edtext=\old@edtext}
10107   {}
10108   {}
10109
10110 %

```

hyperref also redefines \@sect. That is why, when manipulating arguments, we patch \@sect and the same only if hyperref is not used. If it is, we patch the \NR commands.

```

10111 \@ifpackageloaded{nameref}{
10112
10113   \patchcmd{\NR@sect}
10114     {#8}
10115     {#8%
10116       \print@rightmargin@eledsection%
10117     }
10118     {}
10119     {}
10120
10121   \patchcmd{\NR@sect}
10122     {\hskip #3\relax}
10123     {\hskip #3\relax%
10124       \print@leftmargin@eledsection%
10125     }
10126     {}
10127     {}
10128
10129   \patchcmd{\NR@ssect}
10130     {#5}
10131     {#5%
10132       \print@rightmargin@eledsection%
10133     }
10134     {}
10135     {}
10136
10137   \patchcmd{\NR@ssect}
10138     {\hskip #1}
10139     {\hskip #1%
10140       \print@leftmargin@eledsection%
10141     }
10142     {}
10143     {}
10144   }%
10145   {
10146     \patchcmd{\@sect}
10147       {#8}

```

```

10148     {#8%
10149     \print@rightmargin@eledsection%
10150     }
10151     {}
10152     {}
10153
10154     \patchcmd{\@sect}
10155     {\hskip #3\relax}
10156     {\hskip #3\relax%
10157     \print@leftmargin@eledsection%
10158     }
10159     {}
10160     {}
10161
10162     \patchcmd{\@ssect}
10163     {#5}
10164     {#5%
10165     \print@rightmargin@eledsection%
10166     }
10167     {}
10168     {}
10169
10170     \patchcmd{\@ssect}
10171     {\hskip #1}
10172     {\hskip #1%
10173     \print@leftmargin@eledsection%
10174     }
10175     {}
10176     {}
10177     }%
10178 }%
10179 %

```

Close the `\notbool{@noeled@sec}` statement. Also, we have finished patching the commands, using `#` with a catcode equal to 12, so we are restoring the normal catcode for `#`.

```

10180 {}}%
10181 \protect\catcode`\#=6 %Space NEEDS by \catcode
10182 %

```

\chapter We patch the `\chapter` command even if the `noeledsec` option is called, because we can use `\chapter` in the optional argument of a `\pstart` in parallel typesetting.

```

10183 \AtBeginDocument{%
10184 \patchcmd{\chapter}{\clearforchapter}{%
10185 \if@eled@sectioning\else%
10186 \ifl@dprintingpages\else%
10187 \clearforchapter%
10188 \fi%
10189 \fi%

```



```

10190 }%
10191 {}%
10192 {}%
10193
10194 \patchcmd{\chapter}{\if@openright\cleardoublepage\else\clearpage\fi}{%
10195   \if@eled@sectioning\else%
10196     \ifl@printingpages%
10197       \endgraf%
10198     \else%
10199       \if@openright\cleardoublepage\else\clearpage\fi%No clearpage inside a
    \Pages: will keep critical notes from printing on the title page. Here for
    classical classes
    \fi%
10200   \fi%
10201 }%
10202 {}%
10203 {}%
10204 {}%
10205 }%
10206 %

```

\if@eled@sectioning The boolean \if@eled@sectioning is set to true when a sectioning command is called by a \eledxxx command, and set to false after. It is used to enable/disable line number printing.

```

10207 \newif\if@eled@sectioning%
10208 %

```

We reopen a new \notbool{@noeled@sec} statement, as we will define the \elesection commands.

```

10209 \notbool{@noeled@sec}{%
10210 %

```

XXXIV.6 Main code of \eledxxx commands

\eled@sectioning@out \eled@sectioning@out is the output file, to dump the pstarts where a sectioning command is used.

```

10211 \newwrite\eled@sectioning@out
10212 %

```

\eledchapter And now, the user sectioning commands, which write to the file, and also add content as a “normal” line.

```

\eledsection
\eledsubsection
10213 \newcommand{\eledchapter}[2][{}]{%
\eledsubsubsection
10214   \disable@familiarnotes%
\eledchapter*
10215   #2%
\eledsection*
10216   \restore@familiarnotes%
\eledsubsection*
10217   \ifledRcol%
\eledsubsubsection*

```

```

10218 \immediate\write\eled@sectioningR@out{%
10219 \string\eled@chapter{#1}{\unexpanded{#2}}{\the\l@dumpstartsR}{R}
10220 }%
10221 \else%
10222 \immediate\write\eled@sectioning@out{%
10223 \string\eled@chapter{#1}{\unexpanded{#2}}{\the\pstarts@read@L}{R}%
10224 }%
10225 \fi%
10226 }
10227
10228 \newcommand{\eledsection}[2][{}]{%
10229 \disable@familiarnotes%
10230 #2%
10231 \restore@familiarnotes%
10232 \ifledRcol%
10233 \immediate\write\eled@sectioningR@out{%
10234 \string\eled@section{#1}{\unexpanded{#2}}{\the\l@dumpstartsR}{R}
10235 }%
10236 \else%
10237 \immediate\write\eled@sectioning@out{%
10238 \string\eled@section{#1}{\unexpanded{#2}}{\the\pstarts@read@L}{R}%
10239 }%
10240 \fi%
10241 }
10242
10243 \newcommand{\eledsubsection}[2][{}]{%
10244 \disable@familiarnotes%
10245 #2%
10246 \restore@familiarnotes%
10247 \ifledRcol%
10248 \immediate\write\eled@sectioningR@out{%
10249 \string\eled@subsection{#1}{\unexpanded{#2}}{\the\l@dumpstartsR}{R}
10250 }%
10251 \else%
10252 \immediate\write\eled@sectioning@out{%
10253 \string\eled@subsection{#1}{\unexpanded{#2}}{\the\pstarts@read@L}{R}%
10254 }%
10255 \fi%
10256 }
10257 \newcommand{\eledsubsubsection}[2][{}]{%
10258 \disable@familiarnotes%
10259 #2%
10260 \restore@familiarnotes%
10261 \ifledRcol%
10262 \immediate\write\eled@sectioningR@out{%
10263 \string\eled@subsubsection{#1}{\unexpanded{#2}}{\the\l@dumpstartsR}
10264 }{R}
10265 }%

```

```

10265 \else%
10266 \immediate\write\eled@sectioning@out{%
10267 \string\eled@subsubsection{#1}{\unexpanded{#2}}{\the\pstarts@read@L
10268 }{}{}}%
10269 \fi%
10270 }
10271
10272
10273 \WithSuffix\newcommand\eledchapter*[2][]{%
10274 \disable@familiarnotes%
10275 #2%
10276 \restore@familiarnotes%
10277 \ifledRcol%
10278 \immediate\write\eled@sectioningR@out{%
10279 \string\eled@chapter{#1}{\unexpanded{#2}}{\the\l@dnumpstartsR}{*}{R}
10280 }%
10281 \else%
10282 \immediate\write\eled@sectioning@out{%
10283 \string\eled@chapter{#1}{\unexpanded{#2}}{\the\pstarts@read@L}{*}{}}%
10284 }%
10285 \fi%
10286 }
10287
10288 \WithSuffix\newcommand\eledsection*[2][]{%
10289 \disable@familiarnotes%
10290 #2%
10291 \restore@familiarnotes%
10292 \ifledRcol%
10293 \immediate\write\eled@sectioningR@out{%
10294 \string\eled@section{#1}{\unexpanded{#2}}{\the\l@dnumpstartsR}{*}{R}
10295 }%
10296 \else%
10297 \immediate\write\eled@sectioning@out{%
10298 \string\eled@section{#1}{\unexpanded{#2}}{\the\pstarts@read@L}{*}{}}%
10299 }%
10300 \fi%
10301 }
10302
10303 \WithSuffix\newcommand\eledsubsection*[2][]{%
10304 \disable@familiarnotes%
10305 #2%
10306 \restore@familiarnotes%
10307 \ifledRcol%
10308 \immediate\write\eled@sectioningR@out{%
10309 \string\eled@subsection{#1}{\unexpanded{#2}}{\the\l@dnumpstartsR}{*}{
10310 R}
10311 }%
10312 \else%
10313 \immediate\write\eled@sectioning@out{%

```

```

10313 \string\eled@subsection{#1}{\unexpanded{#2}}{\the\pstarts@read@L
10314 }{*}{}%
10315 }%
10316 \fi%
10317 }
10318 \WithSuffix\newcommand\eledsubsubsection*[2] [] {%
10319 \disable@familiarnotes%
10320 #2%
10321 \restore@familiarnotes%
10322 \ifledRcol%
10323 \immediate\write\eled@sectioningR@out{%
10324 \string\eled@subsubsection{#1}{\unexpanded{#2}}{\the\l@dumpstartsR
10325 }{*}{R}
10326 }%
10327 \else%
10328 \immediate\write\eled@sectioning@out{%
10329 \string\eled@subsubsection{#1}{\unexpanded{#2}}{\the\pstarts@read@L
10330 }{*}{}%
10331 }%
10332 \fi%
10333 }
10334 %

```

XXXIV.7 Macros written in the auxiliary file

`\eled@chapter`
`\eled@section`
`\eled@subsection`
`\eled@subsubsection`

The sectioning macros, called in the auxiliary file. They have five arguments:

1. Optional arguments of \LaTeX sectioning command.
2. Mandatory arguments of \LaTeX sectioning command.
3. Pstart number.
4. Side: R if right, nothing if left.
5. Starred or not.

```

10333 \def\eled@chapter#1#2#3#4#5{%
10334 \ifstrempy{#4}%
10335 {%
10336 \ifstrempy{#1}%
10337 {%
10338 \csgdef{eled@sectioning@#3#5}{\let\edtext=\dummy@edtext@showlemma\
chapter{#2}}%
10339 \csgdef{eled@sectmark@#3#5}{\let\edtext=\dummy@edtext}\chaptermark
10340 {#2}}%
10341 }%Need for \pairs, because of using parbox.
10342 }%

```

```

10342 \csgdef{eled@sectioning@#3#5}{\let\edtext=\dummy@edtext@showlemma\
chapter[#1]{#2}}%
10343 \csgdef{eled@sectmark@#3#5}{\let\edtext=\dummy@edtext{}\chaptermark
{#2}}%Need for \pairs, because of using parbox.
10344 }%
10345 }%
10346 {%
10347 \ifstrempy{#1}%
10348 {\csgdef{eled@sectioning@#3#5}{\let\edtext=\dummy@edtext@showlemma\
chapter*{#2}}}%
10349 {\csgdef{eled@sectioning@#3#5}{\let\edtext=\dummy@edtext@showlemma\
chapter*{#1}{#2}}}%Bug in LaTeX!
10350 }%
10351 \listcsgadd{eled@sections#5@@}{#3}%
10352 }
10353 \def\eled@section#1#2#3#4#5{%
10354 \ifstrempy{#4}%
10355 {\ifstrempy{#1}%
10356 {%
10357 \csgdef{eled@sectioning@#3#5}{\section{#2}}%
10358 \csgdef{eled@sectmark@#3#5}{\let\edtext=\dummy@edtext{}\sectionmark
{#2}}%Need for \pairs, because of using parbox.
10359 }%
10360 {%
10361 \csgdef{eled@sectioning@#3#5}{\section[#1]{#2}}%
10362 \csgdef{eled@sectmark@#3#5}{\let\edtext=\dummy@edtext{}\sectionmark
{#1}}%Need for \pairs, because of using parbox.
10363 }%
10364 }%
10365 {\ifstrempy{#1}%
10366 {\csgdef{eled@sectioning@#3#5}{\section*{#2}}}%
10367 {\csgdef{eled@sectioning@#3#5}{\section*{#1}{#2}}}%Bug in LaTeX!
10368 }
10369 \listcsgadd{eled@sections#5@@}{#3}%
10370 }
10371 \def\eled@subsection#1#2#3#4#5{%
10372 \ifstrempy{#4}%
10373 {\ifstrempy{#1}%
10374 {%
10375 \csgdef{eled@sectioning@#3#5}{\subsection{#2}}%
10376 \csgdef{eled@sectmark@#3#5}{\let\edtext=\dummy@edtext{}\csuse{
subsectionmark}{#2}}%Need for \pairs, because of using parbox. \csuse in
case of \subsectionmark is not defined (book)
10377 }%
10378 {%
10379 \csgdef{eled@sectioning@#3#5}{\subsection[#1]{#2}}%
10380 \csgdef{eled@sectmark@#3#5}{\let\edtext=\dummy@edtext{}\csuse{
subsectionmark}{#1}}%Need for \pairs, because of using parbox. \csuse in
case of \subsectionmark is not defined (book)
10381 }%

```

```

10382 }%
10383 {\ifstrepty{#1}%
10384   {\csgdef{eled@sectioning@#3#5}{\subsection*{#2}}}%
10385   {\csgdef{eled@sectioning@#3#5}{\subsection*{#1}{#2}}}%Bug in LaTeX!
10386 }
10387 \listcsgadd{eled@sections#5@@}{#3}%
10388 }
10389 \def\eled@subsubsection#1#2#3#4#5{%
10390   \ifstrepty{#4}%
10391     {\ifstrepty{#1}%
10392       {\csgdef{eled@sectioning@#3#5}{\subsubsection{#2}}}%
10393       {\csgdef{eled@sectioning@#3#5}{\subsubsection{#1}{#2}}}%
10394     }%
10395     {\ifstrepty{#1}%
10396       {\csgdef{eled@sectioning@#3#5}{\subsubsection*{#2}}}%
10397       {\csgdef{eled@sectioning@#3#5}{\subsubsection*{#1}{#2}}}%Bug in
LaTeX!
10398     }
10399     \listcsgadd{eled@sections#5@@}{#3}%
10400   }
10401
10402 %

```

End of the conditional test about noeledsec option.

```

10403 }{}
10404 %

```

XXXV Page breaking or no page breaking depending on specific lines

By default, page breaks are automatic. However, the user can define lines which will force page breaks, or prevent page breaks around one specific line. On the first run, the line-list file records the line number of where the page break is being changed (either forced, or prevented). On the next run, page breaks occur either before or after this line, depending on how the user sets the command. The default setting is after the line.

\normal@page@break \normal@page@break is an etoolbox list which contains the absolute line number of the last line, for each page.

```

10405 \def\normal@page@break{}
10406 %

```

\prev@pb The \l@prev@pb macro is a etoolbox list, which contains the lines in which page breaks occur (before or after). The \l@prev@nopb macro is a etoolbox list, which contains the lines with NO page break before or after.

```

10407 \def\l@prev@pb{}
10408 \def\l@prev@nopb{}
10409 %

```

\ledpb The `\ledpb` macro writes the call to `\led@pb` in line-list file. The `\ledpbnum` macro writes the call to `\led@pbnum` in line-list file. The `\lednopb` macro writes the call to `\led@nopb` in line-list file. The `\lednopbnum` macro writes the call to `\led@nopbnum` in line-list file.

```

10410 \newcommand{\ledpb}{\write\linenum@out{\string\led@pb}}
10411 \newcommand{\ledpbnum}[1]{\write\linenum@out{\string\led@pbnum{#1}}}
10412 \newcommand{\lednopb}{\write\linenum@out{\string\led@nopb}}
10413 \newcommand{\lednopbnum}[1]{\write\linenum@out{\string\led@nopbnum{#1}}}
10414 %

```

\led@pb The `\led@pb` adds the absolute line number in the `\prev@pb` list. The `\led@pbnum` adds the argument in the `\prev@pb` list. The `\led@nopb` adds the absolute line number in the `\prev@nopb` list. The `\led@nopbnum` adds the argument in the `\prev@nopb` list.

```

10415 \newcommand{\led@pb}{\listxadd{\l@prev@pb}{\the\absline@num}}
10416 \newcommand{\led@pbnum}[1]{\listxadd{\l@prev@pb}{#1}}
10417 \newcommand{\led@nopb}{\listxadd{\l@prev@nopb}{\the\absline@num}}
10418 \newcommand{\led@nopbnum}[1]{\listxadd{\l@prev@nopb}{#1}}
10419 %

```

\ledpbsetting The `\ledpbsetting` macro only changes the value of `\led@pb@macro`, for which the default value is `before`.

```

10420 \def\led@pb@setting{before}
10421 \newcommand{\ledpbsetting}[1]{\gdef\led@pb@setting{#1}}
10422 %

```

\led@check@pb The `\led@check@pb` and `\led@check@nopb` are called before or after each line. They check if a page break must occur, depending on the current line and on the content of `\l@pb`.

```

10423 \newcommand{\led@check@pb}{\xifinlist{\the\absline@num}{\l@prev@pb}{\pagebreak[4]}}
10424 \newcommand{\led@check@nopb}{%
10425   \IfStrEq{\led@pb@setting}{before}{%
10426     \xifinlist{\the\absline@num}{\l@prev@nopb}{%
10427       {\numdef{\abs@prevline}{\the\absline@num-1}}%
10428       \xifinlist{\abs@prevline}{\normal@page@break}{%
10429         {\nopagebreak[4]\enlargethispage{\baselineskip}}%
10430       }%
10431     }%
10432   }%
10433 }%
10434 \IfStrEq{\led@pb@setting}{after}{%

```

```

10435 \xifinlist{\the\absline@num}{\l@prev@nopb}{%
10436 \xifinlist{\the\absline@num}{\normal@page@break}%
10437 {\nopagebreak[4]\enlargethispage{\baselineskip}}%
10438 {}%
10439 }%
10440 {}%
10441 {}%
10442 {}%
10443 }
10444 %

```

XXXVI Long verse: prevents being separated by a page break

\iflednopbinverse The `\lednopbinverse` boolean is set to false by default. If set to true, `reledmac` will automatically prevent page breaks inside verse. The declaration is made at the beginning of the file, because it is used as a package option.

\check@pb@in@verse The `\check@pb@in@verse` checks if a verse is broken in two page. If true, it adds:

- The absolute line number of the first line of the verse -1 in the `\led@pb` list, if the page break must occur before the verse.
- The absolute line number of the first line of the verse -1 in the `\led@nopb` list, if the page break must occur after the verse.

```

10445 \newcommand{\check@pb@in@verse}{%
10446 \ifinstanza\iflednopbinverse\ifinserthangingsymbol% Using stanzas and
enabling page breaks in verse control, while on a hanging verse.
10447 \ifnum\page@num=\last@page@num\else%If we have change page
10448 \IfStrEq{\led@pb@setting}{before}{%
10449 \numgdef{\abs@line@verse}{\the\absline@num-1}%
10450 \ledpbnum{\abs@line@verse}%
10451 }{}%
10452 \IfStrEq{\led@pb@setting}{after}{%
10453 \numgdef{\abs@line@verse}{\the\absline@num-1}%
10454 \lednopbnum{\abs@line@verse}%
10455 }{}%
10456 \fi%
10457 \fi\fi\fi%
10458 }
10459 %

```


XXXVII Tools for hyperref package

`\Hy@raisedlink@left` The hyperref package provides a `\Hy@raisedlink` command, to be used to add an anchor to the top of a line and not to the bottom of it.³⁸

However, this command disrupts the line breaking mechanism when it is called before any word. This is why `reledmac` defines `\Hy@raisedlink@left` that is called to the left of words, at the beginning of `\edtext` or inside the `\edlabel` commands.³⁹

```

10460 \def\Hy@raisedlink@left#1{%
10461   \ifvmode
10462     #1%
10463   \else
10464     \Hy@SaveSpaceFactor
10465     \llap{\smash{%
10466       \begingroup
10467         \let\HyperRaiseLinkLength\@tempdima
10468         \setlength\HyperRaiseLinkLength\HyperRaiseLinkDefault
10469         \HyperRaiseLinkHook
10470       \expandafter\endgroup
10471       \expandafter\raise\the\HyperRaiseLinkLength\hbox{%
10472         \Hy@RestoreSpaceFactor
10473         #1%
10474         \Hy@SaveSpaceFactor
10475       }%
10476     }}%
10477     \Hy@RestoreSpaceFactor
10478     \penalty\@M\hskip\z@\relax
10479   \fi
10480 }
10481 %

```

XXXVIII Compatibility with eledmac

Here, we define some commands for the `eledmac-compat` option.

```

10482 \ifeledmaccompat%
10483
10484   \newcommand{\footnormalX}[1]{\arrangementX[#1]{normal}}%
10485   \newcommand{\footparagraphX}[1]{\arrangementX[#1]{paragraph}}%
10486   \newcommand{\foottwocolX}[1]{\arrangementX[#1]{twocol}}%
10487   \newcommand{\footthreecolX}[1]{\XarrangementX[#1]{threecol}}%
10488
10489   \unless\ifnocritical@
10490     \newcommand{\footnormal}[1]{\Xarrangement[#1]{normal}}%
10491     \newcommand{\footparagraph}[1]{\Xarrangement[#1]{paragraph}}%

```

³⁸<http://tex.stackexchange.com/a/17138/7712>.

³⁹The code is inspired by an answer given by @unbonpetit. Thanks to him. <http://texnique.fr:80/osqa/questions/781/hyraisedlink-perturbe-la-maniere-dont-se-fait-la-coupure-de-ligne/801>.

```

10492 \newcommand{\foottwocol}[1]{\Xarrangement[#1]{twocol}}%
10493 \newcommand{\footthreecol}[1]{\Xarrangement[#1]{threecol}}%
10494 \let\hsizetwocol\Xhsizetwocol
10495 \let\hsizethreecol\Xhsizethreecol
10496 \let\bhookXnote\Xbhooknote
10497 \let\boxsymlinenum\Xboxsymlinenum
10498 \let\symlinenum\Xsymlinenum
10499 \let\beforenumberinfootnote\Xbeforenumber
10500 \let\afternumberinfootnote\Xafternumber
10501 \let\beforeXsymlinenum\Xbeforesymlinenum
10502 \let\afterXsymlinenum\Xaftersymlinenum
10503 \let\inplaceofnumber\Xinplaceofnumber
10504 \let\Xlemmaseparator\lemmaseparator
10505 \let\afterlemmaseparator\Xafterlemmaseparator
10506 \let\beforelemmaseparator\Xbeforelemmaseparator
10507 \let\inplaceoflemmaseparator\Xinplaceoflemmaseparator
10508 \let\txbeforeXnotes\Xtxbeforenotes
10509 \let\afterXrule\Xafterrule
10510 \let\numberonlyfirstinline\Xnumberonlyfirstinline
10511 \let\numberonlyfirstintwlines\Xnumberonlyfirstintwlines
10512 \let\nonumberinfootnote\Xnonumberinfootnote
10513 \let\pstartinfootnote\Xpstart
10514 \let\pstartinfootnoteeverytime\Xpstarteverytime
10515 \let\onlyXpstart\Xonlypstart
10516 \let\Xnonumberinfootnote\Xnonumber
10517 \let\nonbreakableafternumber\Xnonbreakableafternumber
10518 \let\maxhXnotes\Xmaxhnotes
10519 \let\beforeXnotes\Xbeforenotes
10520 \let\boxlinenum\Xboxlinenum
10521 \let\boxlinenumalign\Xboxlinenumalign
10522 \let\boxstartlinenum\Xboxstartlinenum
10523 \let\boxendlinenum\Xboxendlinenum
10524 \let\twolines\Xtwolines
10525 \let\morethantwolines\Xmorethantwolines
10526 \let\twolinesbutnotmore\Xtwolinesbutnotmore
10527 \let\twolinesonlyinsamepage\Xtwolinesonlyinsamepage
10528 \fi
10529
10530 \unless\ifnofamiliar@
10531 \let\notesXwidthliketwocolumns\noteswidthliketwocolumnsX
10532 \fi
10533 \newcommandx{\parafootsep}[2][1,usedefault]{%
10534 \Xparafootsep[#1]{#2}%
10535 \parafootsepX[#1]{#2}
10536 }%
10537
10538 \newcommandx{\afternote}[2][1,usedefault]{%
10539 \Xafternote[#1]{#2}%
10540 \afternoteX[#1]{#2}%
10541 }%

```

```

10542 \unless\ifnoend@
10543 \let\XendXtwolines\Xendtwolines
10544 \let\XendXmorethantwolines\Xendmorethantwolines
10545 \let\hookXendnote\Xendhooknote
10546 \let\boxXendlinenum\Xendboxlinenum%
10547 \let\boxXendlinenumalign\Xendboxlinenumalign%
10548 \let\boxXendstartlinenum\Xendboxstartlinenum%
10549 \let\boxXendendlinenum\Xendboxendlinenum%
10550 \let\XendXlemmaseparator\Xendlemmaseparator
10551 \let\XendXbeforelemmaseparator\Xendbeforelemmaseparator
10552 \let\XendXafterlemmaseparator\Xendafterlemmaseparator
10553 \let\XendXinplaceoflemmaseparator\Xendinplaceoflemmaseparator
10554 \fi
10555
10556 \AtBeginDocument{%
10557 \ifdef\lineref{}\let\lineref\edlineref}%
10558 }%
10559
10560
10561 \fi%
10562 %
10563 %

```

</code>

Appendix A Things to do when changing versions

A.1 Migrating from edmac to ledmac

If you have never used edmac, ignore this section. If you have used edmac and are starting on a completely new document, ignore this section. Only read this section if you are converting an original edmac document to use ledmac.

The package still provides the original `\text` command, but it is (a) deprecated, and (b) its name has been changed⁴⁰ to `\critext`; use the `\edtext` macro instead. However, if you do use `\critext` (the new name for `\text`), the following is a reminder.

`\critext` Within numbered paragraphs, footnotes and endnotes are generated by forms of the `\critext` macro:

```
\critext{⟨lemma⟩}⟨commands⟩/
```

The `⟨lemma⟩` argument is the lemma in the main text: `\critext` both prints this as part of the text, and makes it available to the `⟨commands⟩` you specify to generate notes. The `/` at the end terminates the command; it is part of the macro's definition so that spaces after the macro will be treated as significant.

For example:

<pre>I saw my friend \critext{Smith} \Afootnote{Jones C, D.}/ on Tuesday.</pre>	<pre>1 I saw my friend 2 Smith on Tuesday. 2 Smith] Jones C, D.</pre>
---	---

The lemma Smith is printed as part of this sentence in the text, and is also made available to the footnote that specifies a variant, Jones C, D. The footnote macro is supplied with the line number at which the lemma appears in the main text.

The `⟨lemma⟩` may contain further `\critext` commands. Nesting makes it possible to print an explanatory note on a long passage together with notes on variants for individual words within the passage. For example:

<pre>\critext{I saw my friend \critext{Smith}{\Afootnote{Jones C, D.}/ on Tuesday.} \Bfootnote{The date was July 16, 1954.} /</pre>	<pre>1 I saw my friend 2 Smith on Tuesday. 2 Smith] Jones C, D. 1-2 I saw my friend Smith on Tuesday.] The date was July 16, 1954.</pre>
---	--

However, `\critext` cannot handle overlapping but unnested notes—for example, one note covering lines 10–15, and another covering 12–18; a `\critext` that starts in the `⟨lemma⟩` argument of another `\critext` must end there, too. (The `\lemma` and `\linenum` commands may be used to generate overlapping notes if necessary.)

The second argument of the `\critext` macro, `⟨commands⟩`, is the same as the second argument to the `\edtext` macro.

It is possible to define aliases for `\critext`, which can be easier to type. You can make a single character substitute for `\critext` by saying this:

```
\catcode'\<=\active
```

⁴⁰A name like `\text` is likely to be defined by other \TeX packages (it certainly is by the AMS packages) and it seems sensible to try and avoid clashes with other definitions.

```
\let<=\critext
```

Then you might say `<{Smith}\variant{Jones}/`. This of course destroys the ability to use `<` in any new macro definitions, so long as it remains in effect; hence it should be used with care.

Changing the character at the end of the command requires more work:

```
\catcode'\<=\active
\def\xtext#1#2>{\critext{#1}{#2}/}
\let<=\xtext
```

This allows you to say `<{Smith}\Afootnote{Jones}>`.

Aliases for `\critext` of the first kind shown here also can't be nested—that is, you can't use the alias in the text that forms the first argument to `\critext`. (See VI p. 140 to find out why.) Aliases of the second kind may be nested without any problem.

If you really have to use `\critext` in any of the tabular or array environments, then `\edtext` must not be used in the same environment. If you use `\critext` in one of these environments then you have to issue the declaration `\usingcritext` beforehand. The declaration `\usingedtext` must be issued to revert to the default assumption that `\edtext` will be used.

A.2 Migration from ledmac to eledmac

In `eledmac`, some changes were made in the code to allow easy customization. This may cause problems for people who have already made their own. The next sections explain how to handle this.

If you have created your own series using `\addfootins` and `\addfootinsX`, you must use instead the `\newseries` command (see 6.7.1 p. 42), and remove any `\Xfootnote` command.

If you have customized the `\XXXXXfmt` command, please check whether you can achieve the same by the commands documented for display options (7 p. 43) or `\Xfootnote` options (6.2.2 p. 30). Otherwise please add a new ticket on Github to request a new function for doing this.⁴¹

If for some reason you do not want to make the modifications to use the new functions of `eledmac`, you can continue using your own `\XXXXXfmt` command, but you must replace:

```
\renewcommand*{XXXXfmt}[3]
```

with

```
\renewcommandx*{XXXXfmt}[4][4=Z]
```

⁴¹<https://github.com/maieul/ledmac/issues>

If you do not make that, you will get a spurious [X], where X is series letter.

If you used a `\protect` command inside a `\footnote` command inside a numbered section, you must change the `\protect` to `\noexpand`. Otherwise the command after the `\protect` will be discarded.

A.3 Migration to eledmac 1.5.1

The version 1.5.1 corrects a bug in `stanzaindentrepetition` (cf. 9.3 p. 59). This bug had two consequences:

1. `stanzaindentrepetition` did not work when its value was greater than 2.
2. `stanzaindentrepetition` worked wrong when its value was equal to 2.

So, if you used `stanzaindentrepetition` with a value equal to 2, you had to change your `\setstanzaindent`. Explanation:

```
\setcounter{stanzaindentrepetition}{2}
\setstanzaindent{5,1,0}
```

This code, in versions prior to 1.5.1, made the first line have an indentation of 0, the second line of 1, the third verse of 0, the fourth verse of 1 and so forth.

But this code should have instead achieved quite the contrary: the first line would have an indentation of 1, the second line of 0, the third line of 1, the fourth line of 0 and so forth.

So version 1.5.1 corrected this bug. If you want to keep the former presentation, you must change:

```
\setcounter{stanzaindentrepetition}{2}
\setstanzaindent{5,1,0}
```

to:

```
\setcounter{stanzaindentrepetition}{2}
\setstanzaindent{5,0,1}
```

A.4 Migration to eledmac 1.12.0

The migration to eledmac 1.12.0 is easy:

- You must first delete all the auxiliary files, then compile your document three times as usual.
- If you have modified `\l@reg`, which is not advisable, you must rename it to `\@nl@reg`.

There is an additional problem. If you have put text into brackets just after `\pstart` or `\pend`, this text will be considered to be an optional argument of `\pstart` or `\pend` (see 5.2.3 p. 19). If so, add a `\relax` between `\pstart`/`\pend` and the first bracket.

The version 1.12.0 also introduce a better way to handle sectional divisions inside numbered text. Please read 16.2 p. 77.

A.5 Migration to eledmac 17.1

This version changes the default setting of `\Xpstart`. Henceforth, `pstart` numbers will be printed in footnotes within the section of text where you have called `\numberpstarttrue`.

We do not see any reason to print them in the other sections. However, if you want to print the `\pstart` numbers in every footnote, whatever the section, without having to use `\numberpstarttrue`, you can use `\Xpstarteverytime`.

A.6 Migration to eledmac 1.21.0

A.6.1 `\Xledsetnormalparstuff` and `\ledsetnormalparstuffX`

The `\ledsetnormalparstuff` has been split into two different commands:

- `\Xledsetnormalparstuff` for critical notes;
- `\ledsetnormalparstuffX` for familiar notes.

Both commands can take an optional argument which is the series letter. If you have redefined `\ledsetnormalparstuff` or any of the commands which call them, you must change them accordingly.

A.6.2 Endnotes

In any case, delete the `.end` file before the next run.

The previous version of Eledmac had a bug: there were two spaces between the starting page number and the starting line number, but only one space between the ending page number and the ending line number.

As a matter of fact, a spurious space was added after the first `\printnpnum`. This spurious space has been deleted. However, if you want to keep the previous spurious space, you may load the package with the `oldprintnpnumspace` option.

If you have redefined `\endprint`, you must:

- Contact us and ask for the feature that required your hack, in order to avoid such a hack in the future.
- Use the new fifth argument.
- Add `\xdef\@currentseries{#4}` at the beginning of your own command.

A.7 Migration to eledmac 1.22.0

The `\ledinnote` command now takes a first optional argument, which is the label for the hyperreference. If you have redefined it, change your redefinition, and check whether you can avoid this redefinition by only redefining `\ledinnotemark`.

A.8 Migration to eledmac 1.23.0

You must delete the numbered auxiliary files before compiling with the new version of eledmac.

A.9 Migration from eledmac to reledmac

There are many changes in reledmac which require the user to make modifications.

A.9.1 Risk of ‘no room for a new’

The risk to obtain a ‘no room for a new something’ error is greater in reledmac than it is in eledmac. See 19.1.3 p. 79 in order to know how to limit it.

A.9.2 Multiple indices with memoir

Eledmac and ledmac used the specific indexing tools of the memoir class designed to produce multiple indices. However, eledmac could also use imakeidx or indextools tools independently of the memoir class. This system forced to maintain redundant code. Since reledmac, we use only the imakeidx or indextools tools.

Consequently: Users of memoir are invited to use indextool or imakeidx to produce multiple indices.

A.9.3 Deprecated commands and options

The table of deprecated commands and their alternatives follows. Note that the way some commands must be used may have changed. Please read the handbook.

<i>Deprecated command</i>	<i>Replaced with</i>
<code>\addfootins</code>	<code>\newseries</code>
<code>\addfootinsX</code>	<code>\newseries</code>
<code>\critext</code>	<code>\edtext</code>
<code>\falseverse</code>	<code>\newverse</code>
<code>\interparanoteglue</code>	<code>\Xafternote</code> and <code>\afternoteX</code>
<code>\ledchapter</code>	<code>\eledchapter</code>
<code>\ledsection</code>	<code>\eledsection</code>
<code>\ledsetnormalparstuff</code>	<code>\Xledsetnormalparstuff</code> and <code>\ledsetnormalparstuffX</code>
<code>\ledsubsection</code>	<code>\eledsubsection</code>
<code>\ledsubsubsection</code>	<code>\eledsubsubsection</code>
<code>\noeledsec</code>	Package option <code>noeledsec</code>
<code>\noendnotes</code>	Package option <code>noendnotes</code>
<code>\pageparbreak</code>	<code>\ledpb</code>

The `ledsecnolinenumber` option has been removed, because it was related to deprecated commands.

The `oldprintnpnumspace` option has been removed too, because it was related to a historical bug. The `\usingedtext` and `\usingcritext` commands are also deprecated.

A.9.4 `\renewcommand` replaced by command

Many uses of `\renewcommand` have been replaced with uses of specific commands. Please read handbook about specific commands.

<i>Deprecated <code>\renewcommand</code></i>	<i>Replaced with</i>
<code>\@led@extranofeet</code>	<code>\newseries</code>
<code>\apprefprefixmore</code>	<code>\setapprefprefixmore</code>
<code>\apprefprefixsingle</code>	<code>\setapprefprefixsingle</code>
<code>\endstanzaextra</code>	Optional argument of <code>\&</code>
<code>\hangingsymbol</code>	<code>\sethangingsymbol</code>
<code>\ledfootinsdim</code>	<code>\Xmaxhnotes</code> and <code>\maxhnotesX</code>
<code>\parafootftmsep</code>	<code>\Xparafootsep</code> and <code>\parafootsepX</code>
<code>\notenumfont</code>	<code>\Xnotenumfont</code> , <code>\Xendnotenumfont</code> and <code>\notenumfontX</code>
<code>\notefontsetup</code>	<code>\Xnotefontsize</code> , <code>\Xendnotefontsize</code> and <code>\notefontsizeX</code>
<code>\sidenotesep</code>	<code>\setsidenotsep</code>
<code>\startstanzahook</code>	Optional argument of <code>\stanza</code>
<code>\symplinenum</code>	<code>\Xsymplinenum</code>

A.9.5 Commands the names of which have been changed

In order to help the migration from eledmac to reledmac, you may load reledmac with `eledmac-compat` option. However, it is advised not to, and to change the command names themselves instead. In many cases, you use only a few of them, except the `\footparagraph` command.

<i>Old command</i>	<i>New command</i>
<code>\footparagraph</code>	<code>\Xarrangement</code>
<code>\footnormal</code>	<code>\Xarrangement</code>
<code>\foottwocol</code>	<code>\Xarrangement</code>
<code>\footthreecol</code>	<code>\Xarrangement</code>
<code>\footparagraphX</code>	<code>\arrangementX</code>
<code>\footnormalX</code>	<code>\arrangementX</code>
<code>\foottwocolX</code>	<code>\arrangementX</code>
<code>\footthreecolX</code>	<code>\arrangementX</code>
<code>\afterlemmaseparator</code>	<code>\Xafterlemmaseparator</code>
<code>\afternote</code>	<code>\Xafternote</code> and <code>\afternoteX</code>
<code>\afternumberinfootnote</code>	<code>\Xafternumber</code>
<code>\afterXrule</code>	<code>\Xafterrule</code>
<code>\afterXsymplinenum</code>	<code>\Xaftersymplinenum</code>
<code>\beforelemmaseparator</code>	<code>\Xbeforelemmaseparator</code>
<code>\beforenumberinfootnote</code>	<code>\Xbeforenumber</code>
<code>\beforeXnotes</code>	<code>\Xbeforenotes</code>
<code>\beforeXsymplinenum</code>	<code>\Xbeforesymplinenum</code>

<i>Old command</i>	<i>New command</i>
<code>\bhookXnote</code>	<code>\Xbhookendnote</code>
<code>\bhookXnote</code>	<code>\Xbhooknote</code>
<code>\boxendlinenum</code>	<code>\Xboxendlinenum</code>
<code>\boxlinenum</code>	<code>\Xboxlinenum</code>
<code>\boxlinenumalign</code>	<code>\Xboxlinenumalign</code>
<code>\boxstartlinenum</code>	<code>\Xboxstartlinenum</code>
<code>\boxsymlinenum</code>	<code>\Xboxsymlinenum</code>
<code>\boxXendlinenum</code>	<code>\Xendboxlinenum</code>
<code>\boxXendlinenumalign</code>	<code>\Xendboxlinenumalign</code>
<code>\boxXendstartlinenum</code>	<code>\boxXendstartlinenum</code>
<code>\letboxXendendlinenum</code>	<code>\Xendletboxendlinenum</code>
<code>\hsizetwocol</code>	<code>\Xhsizetwocol</code>
<code>\hsizethreecol</code>	<code>\Xhsizethreecol</code>
<code>\inplaceoflemmaseparator</code>	<code>\Xinplaceoflemmaseparator</code>
<code>\inplaceofnumber</code>	<code>\Xinplaceofnumber</code>
<code>\lemmaseparator</code>	<code>\Xlemmaseparator</code>
<code>\maxhXnotes</code>	<code>\Xmaxhnotes</code>
<code>\morethantwolines</code>	<code>\Xmorethantwolines</code>
<code>\nonumberinfootnote</code>	<code>\Xnonumber</code>
<code>\notesXwidthliketwocolumns</code>	<code>\noteswidthliketwocolumnsX</code>
<code>\noXlemmaseparator</code>	<code>\Xnolemmaseparator</code>
<code>\numberonlyfirstinline</code>	<code>\Xnumberonlyfirstinline</code>
<code>\numberonlyfirstintwolines</code>	<code>\Xnumberonlyfirstintwolines</code>
<code>\nonbreakableafternumber</code>	<code>\Xnonbreakableafternumber</code>
<code>\onlyXpstart</code>	<code>\Xonlypstart</code>
<code>\parafootsep</code>	<code>\Xparafootsep</code> and <code>\parafootsepX</code>
<code>\pstartinfootnote</code>	<code>\Xpstart</code>
<code>\pstartinfootnoteeverytime</code>	<code>\Xpstarteverytime</code>
<code>\symlinenum</code>	<code>\Xsymlinenum</code>
<code>\twolines</code>	<code>\Xtwolines</code>
<code>\twolinesbutnotmore</code>	<code>\Xtwolinesbutnotmore</code>
<code>\twolinesonlyinsamepage</code>	<code>\Xtwolinesonlyinsamepage</code>
<code>\txtbeforeXnotes</code>	<code>\Xtxtbeforenotes</code>
<code>\XendXafterlemmaseparator</code>	<code>\Xendafterlemmaseparator</code>
<code>\XendXbeforelemmaseparator</code>	<code>\Xendbeforelemmaseparator</code>
<code>\XendXinplaceoflemmaseparator</code>	<code>\Xendinplaceoflemmaseparator</code>
<code>\XendXlemmaseparator</code>	<code>\Xendlemmaseparator</code>
<code>\XendXmorethantwolines</code>	<code>\Xendmorethantwolines</code>
<code>\XendXtwolines</code>	<code>\Xendtwolines</code>
<code>\Xnonumberinfootnote</code>	<code>\Xnonumber</code>
<code>\lineref</code>	<code>\edlineref</code>

A.9.6 Endnotes

With *reledmac*, there is now one auxiliary file for each endnotes set (.Aend, .Bend, .Cend etc.). If you have overridden `\doendnotes` (which you should not have done) you must adapt your code.

A.9.7 Z Series

The ‘Z’ series of notes has been removed. Only five series are provided now by default: A, B, C, D, E.

A.9.8 Internal commands

Users who have overridden internal commands, which is wrong, must adapt according to the following. Or better, they should not override any of such commands and use *reledmac* options instead.

- If you have modified `\Xfootfmt`, note that the fourth argument is now mandatory.
- `\unvxh` has been replaced with `\Xunvxh` and `\unvxhX` with two mandatory arguments.

A.10 Migration to *reledmac* 2.1.0

Reledmac 2.1.0 fix some bugs when using `\Xbhooknote` and `\bhooknoteX` not in order to execute code at the beginning of each notes, but to insert content of at the beginning of each notes.

People who use these commands to do it, which is not the original idea, must change the following:

1. Horizontal space is no longer automatically added after the content of the `\Xbhooknote/\bhooknoteX` argument. You must include it manually. So instead of `\Xbhooknote{content}`, use `\Xbhooknote{content }.`
2. Indent is no longer automatically added before the content of the `\Xbhooknote/\bhooknoteX` argument. If you want to keep it, add `\indent` to the argument of `\Xbhooknote/\bhooknoteX`.

A.11 Migration to *reledmac* 2.1.3

Reledmac 2.1.3 fix an historical bug, (style in *ledmac* 0.7!) which doubled the space before the rules of paragraphed familiar footnotes. Consequently, if you use paragraphed familiar footnotes, you should maybe adapt it, playing with `\beforenotesX`.

A.12 Migration to *reledmac* 2.3.0

Before *reledmac* 2.3.0, for typesetting verse, any empty line was considered a paragraph inside verses. Counting empty lines this created breaking verse, hanging verses, and also added spurious vertical spaces. Version 2.3.0 disables paragraph in stanza. If you want vertical space, use the optional argument of `\stanza` or `\endverse`.

A.13 Migration to reledmac 2.4.0

It is not mandatory, but strongly recommended, to change any `\renewcommand{\endashchar}{\langle...\rangle}` to the use of `\Xlinerangeseparator` or `/` and `\Xendlinerangeseparator` (7.4.4 p. 46).

A.14 Migration to reledmac 2.5.0

It is strongly recommended to stop redefining `\printnpnum` and to use the hooks documented in 7.4.3 p. 46.

`\xlineref` does not print anymore the side flag (R for right side), because it is incompatible with numerical test. Use `\xflagref` to obtain it.

The `\printlines` and `\printendlines` commands take now an eighth argument, which is the side flag. It is strongly recommended to NEVER redefine these two commands and to use the setting commands instead (or to ask for new setting commands if the actual does not answer to your needs). However, if you have done it, just change your redefinition to have a new argument.

It is strongly recommended to stop redefining `\fullstop` and to use `\Xsublinesep` instead.

A.15 Migration to reledmac 2.7.0

`\Serefonlypage` (introduced in reledmac 2.5.0) added an parenthesis after the page number. This was just an error, linked to a bad imitation of `\Serefwithpage`. That has been deleted. And so, the `\XendafterpagenumberSerefonlypage` to set it was also deleted.

`\rigidbalance` is split to two new commands: `\Xrigidbalance` for critical footnotes and `\rigidbalanceX` for familiar footnotes. If you have redefined it — but why should you have ?—, you should split your single redefinition in two redefinitions.

A.16 Migration to reledmac 2.7.2

`\Xhsize` is already defined in the `floatrow` package. It becomes `\Xwidth`, and, consequently, `\hsizeX` becomes `\widthX`.

The ancient names are temporarily maintained as aliases.

A.17 Migration to reledmac 2.8.0

Reledmac 2.8.0 fix spurious indents for paragraphed critical and familiar footnotes in `ledgroup` and `minipage`. You can re-establish the indent with `\Xparindent` and `\parindentX`.

A.18 Migration to reledmac 2.13.1

Reledmac 2.5.0 added a bug, which makes the right flag to be printed on the right side of critical footnotes, even if not explicitly requested by using `\Xlineflag`.

Version 2.13.1 solves this issue. Please use `\Xlineflag` if you want to add the right flag.

A.19 Migration to reledmac 2.18.0

After updating reledmac, and before any new compilation, you need to clean your `.aux` files, if you use `\edlabel` or related.

A.20 Migration to reledmac 2.21.0

Previously, there was a bug, which meant that the description in the handbook was incorrect. If you wrote

```
The \edtext{creature\edindex{elephant} was quite
    unafraid}{\Afootnote{Of the mouse, that is.}}
```

“elephant” was indexed in the main text and in the critical footnotes. With the new version of reledmac, it is indexed only in main text. If you also want to index it in critical footnotes, do

```
The \edtext{creature\edindex{elephant} was quite
    unafraid}{\Afootnote{\edindex{elephant}Of the mouse, that is.}}
```

A.21 Migration to reledmac 2.24.0

When using `\labelpstarttrue`, a spurious space^a was introduced after the pstart number (only for normal typesetting, not while typesetting in parallel). The new version of the package has deleted this spurious space. If you consider that it was NOT a spurious space, you should add it manually in your definition of `\thepstart`.

A.22 Migration to reledmac 2.26.0

You must delete your `.aux` file after having upgraded to this new version of reledmac.

A.23 Migration to reledmac 2.27.1

This release fixes spurious space in `\hidenumbering`. If you considered this spurious space as normal, you must insert it manually using.

```
xx\hidenumbering\ xx
```

To get the space after `xx`.

A.24 Migration to reledmac 2.30.0

If you have multiple annotations for the same line, these are now separated with a comma in the margin. You can use `\setlinenumannotationsep` to change the separator.

A.25 Migration to reledmac 2.31.1

If you use `\Xgroupbyline`, the indentation of the notes has been deleted, in order to have the same behavior as for normal critical notes.

Use `\Xparindent` to restore indentation.

A.26 Migration to reledmac 2.32.7

For paragraphed familiar footnotes, the separator between notes was `\Xparafootsep` instead of `\parafootsepX`. This release fixes this bug. You may adapt your settings.

A.27 Migration to reledmac 2.33.0

You should not redefine anymore `\ledinnotemark`, but use instead `\innotemarkX` and `\Xinnotemark`.

If you have personal script which parses for `\ledinnote` or if you redefine `\ledinnote` (but normally, you should not), this macro have new arguments. Look at the code for more details.

Appendix B Auxiliary softwares

This appendix lists some software and tools related to `reledmac` that may be useful.

B.1 *samewords*

The *samewords* program (Michael Stenskjær Christensen) automatically adds `\sameword` commands (6.3 p. 34) into a `.tex` file.

<https://samewords.readthedocs.io/en/latest/>

B.2 critical-keys for *Emacs*

The *Emacs* editor has a package to help inserting `reledmac`'s commands (Juan Manuel Macías Chaín).

<https://gitlab.com/maciaschain/critical-keys>

B.3 critical-marks for *Emacs*

A set of functions for *Emacs* that run in the export process from Org Mode to LaTeX and replace a series of simple textual marks with the basic `reledmac`'s commands (Juan Manuel Macías Chaín) <https://gitlab.com/maciaschain/critical-marks>

B.4 Import from TEI

B.5 Import from TEI

There are multiple tools to convert from XML-TEI to *reledmac*. Here is a non exhaustive-list:

- <http://ciham-digital.huma-num.fr/teicat/>
- https://github.com/fizzbucket/tei_transformer
- <https://github.com/TEIC/Stylesheets>
- <http://lombardpress.org/print/>
- <https://github.com/Jean-Baptiste-Camps/TEItoLaTeX>

Please, tell us if you know of other tools.

References

- [Bre96] Herbert Breger. `tabmac`. October 1996. (Available from CTAN in `macros/plain/contrib/tabmac`)
- [Bur01] John Burt. “Typesetting critical editions of poetry”. *TUGboat*, **22**, 4, pp 353–361, December 2001. (Code available from CTAN in `macros/latex/contrib/poemscol`)
- [Eck03] Matthias Eckermann. *The Parallel-Package*. April 2003. (Available from CTAN in `macros/latex/contrib/parallel`)
- [Fai03] Robin Fairbairns. *footmisc—a portmanteau package for customising footnotes in L^AT_EX*. February 2003. (Available from CTAN in `macros/latex/contrib/footmisc`)
- [LW90] John Lavagnino and Dominik Wujastyk. “An overview of edmac: a PLAIN TeX format for critical editions”. *TUGboat*, **11**, 4, pp. 623–643, November 1990. (Code available from CTAN in `macros/plain/contrib/edmac`)
- [Lüc03] Uwe Lück. “ednotes—critical edition typesetting with LaTeX”. *TUGboat*, **24**, 2, pp. 224–236, 2003. (Code available from CTAN in `macros/latex/contrib/ednotes`)
- [Sul92] Wayne G. Sullivan. *The file edstanza.doc*. June 1992. (Available from CTAN in `macros/plain/contrib/edmac`)
- [Wil02] Peter Wilson. *The memoir class for configurable typesetting*. November 2002. (Available from CTAN in `macros/latex/contrib/memoir`)
- [Wil04] Peter Wilson and Maïeul Rouquette. *Parallel typesetting for critical editions: the eledpar package*. December 2004. (Available from CTAN in `macros/latex/contrib/ledmmac`)

Index

Symbols

<code>\&</code>	58
<code>\@EDROWFILL@</code>	1
<code>\@adv</code>	1
<code>\@advancestanzanumber</code>	1
<code>\@annot</code>	1
<code>\@annot@end@print</code>	1
<code>\@annot@start@print</code>	1
<code>\@beforeinsertofthisedtext</code>	1
<code>\@check@edtext@args</code>	1
<code>\@doclearpage</code>	1
<code>\@doreinfeetX</code>	1

<code>\@edindex@fornote@</code>	1
<code>\@edindex@hyperref</code>	1
<code>\@edrowfill@</code>	1
<code>\@edtext@level</code>	1
<code>\@emptytoks</code>	1
<code>\@fnpos</code>	1
<code>\@footnotemark</code>	1
<code>\@footnotetext</code>	1
<code>\@getfirstseries</code>	1
<code>\@gobblefour</code>	1
<code>\@gobbleseven</code>	1
<code>\@gobblethree</code>	1
<code>\@h</code>	1
<code>\@changingsymbol</code>	1
<code>\@iiiminipage</code>	1
<code>\@insertstanzanumber</code>	1
<code>\@insidethisline</code>	1
<code>\@k</code>	1
<code>\@l@dttempcnta</code>	1
<code>\@l@dttempcntb</code>	1
<code>\@lab</code>	1
<code>\@led@testifnofoot</code>	1
<code>\@lemma</code>	1
<code>\@line@#num</code>	1
<code>\@linenumannotationsep</code>	1
<code>\@lock</code>	1
<code>\@lopL</code>	1
<code>\@lopR</code>	1
<code>\@makechapterhead</code>	1
<code>\@makeschapterhead</code>	1
<code>\@mem@extranofeet</code>	1
<code>\@mem@old@ssect</code>	1
<code>\@mpfnpos</code>	1
<code>\@msd</code>	1
<code>\@msd@c</code>	1
<code>\@msd@options@iffullpage</code>	1
<code>\@msdata@list</code>	1
<code>\@nl</code>	1
<code>\@nl@reg</code>	1
<code>\@opXfeet</code>	1
<code>\@outputpage</code>	1
<code>\@page</code>	1
<code>\@pend</code>	1
<code>\@pendR</code>	1
<code>\@ref</code>	1
<code>\@ref@reg</code>	1
<code>\@ref@reg@parse</code>	1
<code>\@resetannot</code>	1
<code>\@sect</code>	1
<code>\@series</code>	1

\@set	1
\@sidenoteseq	1
\@ssect	1
\@startstanza	1
\@stopmsd	1
\@stopstanza	1
\@sw	1
\@tag	1
\@wredindex	1
\@xloop	1
\@xympar	1
CLASSarticle	79
CLASSbook	79, 388
CLASSmemoir	229, 296–299, 335, 388, 408, 476, 480
CLASSscrbook	480
COMMAND*footnote	81
COMMAND\...\@footnotemark...	232
COMMAND\...d@ta	169
COMMAND\<hook	
@<series	282
COMMAND\<hookname	
<pseudoserries	284, 285
COMMAND\<type	
footfmt	214
COMMAND\@@line	204
COMMAND\@MM	191, 477
COMMAND\@Rlineflag	337, 477
COMMAND\@SErefprefix	314
COMMAND\@SErefprefixmore	314
COMMAND\@add@	378
COMMAND\@adv	123
COMMAND\@annot	175
COMMAND\@annot@end@print	219
COMMAND\@annot@start@print	219, 223, 263
COMMAND\@apprefprefixmore	314
COMMAND\@apprefprefixsingle	314
COMMAND\@beforeinsertofthisedtext	146, 147
COMMAND\@bsphack	301
COMMAND\@doclearpage	297, 298, 470, 480
COMMAND\@doreinfeetX	480
COMMAND\@dprintingcolumns	477
COMMAND\@edindex@hyperref	337–339
COMMAND\@edtext@level	144
COMMAND\@esphack	301
COMMAND\@firstofone	38
COMMAND\@fnpos	251, 293
COMMAND\@footnotemark	229, 470, 480
COMMAND\@footnotetext	229, 230, 470
COMMAND\@gobble	28, 38, 141, 142, 175, 277
COMMAND\@gobblefive	479

COMMAND\@gobblefour	476
COMMAND\@gobbleseven	279
COMMAND\@gobblethree	469
COMMAND\@h	208
COMMAND\@hangingsymbol	343
COMMAND\@iiiminipage	326, 328, 469, 480
COMMAND\@iiiminpage	326
COMMAND\@l	474
COMMAND\@l@tempcnta	172, 177, 185
COMMAND\@l@tempcntb	177
COMMAND\@l@reg	474
COMMAND\@lab	119, 301, 304, 309, 469
COMMAND\@ldunboxmpfoot	329
COMMAND\@led@extranofeet	409
COMMAND\@ledinnote@command	333, 334
COMMAND\@lemma	146, 149
COMMAND\@lock	113, 344
COMMAND\@lopL	470
COMMAND\@lopR	470
COMMAND\@makecol	293, 296, 480
COMMAND\@mempnum	299
COMMAND\@mpfnpos	251
COMMAND\@msd	354, 355
COMMAND\@msd@c	354
COMMAND\@msd@options@iffullpage	361
COMMAND\@msdata@list	354, 356
COMMAND\@nl	119, 121, 122, 124, 134, 176, 304, 469, 470
COMMAND\@nl@reg	119, 406, 470, 474
COMMAND\@opXfeet	470
COMMAND\@opfeetX	480
COMMAND\@opxtrafeeti	480
COMMAND\@outputpage	299, 300
COMMAND\@page	119, 121, 304
COMMAND\@pend	470
COMMAND\@pendR	470
COMMAND\@ref	119, 129–131, 135, 136, 141
COMMAND\@ref@later	130, 131, 137
COMMAND\@ref@reg	129, 175, 470
COMMAND\@ref@reg@parsearg	130, 131
COMMAND\@reinserts	293–296, 480
COMMAND\@resetannot	176
COMMAND\@secondoftwo	81
COMMAND\@sect	391
COMMAND\@series	281
COMMAND\@set	124
COMMAND\@sidenotesep	325
COMMAND\@stopmsd	355
COMMAND\@sw	131, 151, 154, 155
COMMAND\@tag	143, 144, 148
COMMAND\@tempcnta	96

COMMAND\@tempcntb	96
COMMAND\@this@crossref@start	228
COMMAND\@toksa	104
COMMAND\@toksb	104
COMMAND\@xloop	186
COMMAND\@xympar	318, 480
COMMAND\Aendnote	17, 31
COMMAND\Afootfmt	190
COMMAND\Afootgroup	190
COMMAND\Afootnote	9, 17, 29–31, 33, 145, 199, 228, 252, 271, 479
COMMAND\Afootstart	190
COMMAND\AtBeginDocument	296
COMMAND\AtEndEveryPend	20, 486
COMMAND\AtEveryPend	19, 20, 61, 162, 476, 478, 480, 486
COMMAND\AtEveryPend*	20
COMMAND\AtEveryPstart	19, 20, 61, 476, 478, 480, 483, 486
COMMAND\AtEveryPstart*	20
COMMAND\AtEveryStanza	61, 484, 486
COMMAND\AtEveryStopStanza	61, 484, 486
COMMAND\AtStartEveryPstart	20, 486
COMMAND\AtStartEveryStanza	61, 486
COMMAND\BeforeEveryStopStanza	61, 486
COMMAND\Bendnote	17, 29
COMMAND\Bfootnote	9, 17, 228, 252, 271
COMMAND\Centering	54
COMMAND\Cfootnote	228
COMMAND\Columns	97, 158, 196
COMMAND\Dfootnote	228
COMMAND\Efootnote	228
COMMAND\Gls	73
COMMAND\Hy@raisedlink	401
COMMAND\Hy@raisedlink@left	401
COMMAND\LTR	54
COMMAND\NR	391
COMMAND\Pages	97, 158, 294, 295, 298
COMMAND\ProcessOptionsX	86
COMMAND\RL	52
COMMAND\RaggedLeft	54
COMMAND\RaggedRight	54
COMMAND\RenewExpandableDocumentCommand	39, 153
COMMAND\SEonlypage	311, 482
COMMAND\SEref	66–68, 311, 314, 483, 485, 489
COMMAND\SErefonlypage	66–68, 412, 482
COMMAND\SErefwithpage	66, 68, 311, 314, 412, 482, 484, 490
COMMAND\Stanza	475
COMMAND\Waklam	379
COMMAND\X@doreinfeet	295, 480
COMMAND\XR@prefix	318
COMMAND\XR@test	318
COMMAND\XR@test@mac	318

COMMAND\XR@test@mac@test	318
COMMAND\XXXXXXfmt	405
COMMAND\XXXXXfmt	405
COMMAND\Xafterenumber	49
COMMAND\Xafterlemmaseparator	51, 409
COMMAND\Xafternote	54, 55, 408, 409
COMMAND\Xafternumber	49, 409
COMMAND\Xafterrule	56, 252, 409, 475, 478
COMMAND\Xaftersymlinenum	49, 409
COMMAND\Xarrangement	44, 55, 81, 191, 192, 283, 409
COMMAND\Xarrangement@footparagraph	197
COMMAND\Xarrangement@normal	192
COMMAND\Xarrangement@paragraph	197
COMMAND\Xbeforeinserting	53, 54
COMMAND\Xbeforelemmaseparator	50, 409
COMMAND\Xbeforenotes	56, 251, 409, 475, 478
COMMAND\Xbeforenumber	49, 409
COMMAND\Xbeforesymlinenum	49, 409
COMMAND\Xbhookendnote	410
COMMAND\Xbhookgroup	55, 482, 483
COMMAND\Xbhooknote	53, 410, 411, 480, 481
COMMAND\Xboxendlinenum	50, 410, 479
COMMAND\Xboxlinenum	49, 50, 410
COMMAND\Xboxlinenumalign	50, 410, 479
COMMAND\Xboxstartlinenum	50, 410, 479
COMMAND\Xboxsymlinenum	50, 410
COMMAND\Xcolalign	54, 478
COMMAND\Xdo@feet	480, 485
COMMAND\Xemdnoidenticallinenumannotation	68
COMMAND\Xend	279
COMMAND\XendXafterlemmaseparator	410
COMMAND\XendXbeforelemmaseparator	410
COMMAND\XendXinplaceoflemmaseparator	410
COMMAND\XendXlemmaseparator	410
COMMAND\XendXmorethantwolines	410
COMMAND\XendXtwolines	410
COMMAND\Xendafterenumber	49, 481
COMMAND\Xendafterlemmaseparator	51, 410
COMMAND\Xendafternote	57, 483
COMMAND\Xendafternumber	53
COMMAND\Xendafterpagenumbe	484
COMMAND\Xendafterpagenumber	46, 68
COMMAND\XendafterpagenumberSErefonlypage	412
COMMAND\Xendaftersymlinenum	49, 53, 481
COMMAND\Xendahookinplaceofnumber	53, 481
COMMAND\Xendahooklinenumber	53, 481
COMMAND\Xendbeforelemmaseparator	51, 410
COMMAND\Xendbeforelinenumber	53
COMMAND\Xendbeforenumber	49, 481
COMMAND\Xendbeforepagenumber	46, 67, 68

COMMAND\XendbeforepagenumberSereonlypage	67
COMMAND\Xendbeforesymlinenum	49, 53, 481
COMMAND\Xendbhookinplaceofnumber	53, 481
COMMAND\Xendbhooklinenum	53, 481
COMMAND\Xendbhooknote	53
COMMAND\Xendboxendlinenum	50, 479
COMMAND\Xendboxlinenum	50, 410, 477
COMMAND\Xendboxlinenumalign	50, 410, 479
COMMAND\Xendboxstartlinenum	50, 479
COMMAND\Xendboxsymlinenum	50, 481
COMMAND\Xendhangindent	53, 481, 483
COMMAND\Xendinplaceoflemmaseparator	31, 51, 410
COMMAND\Xendinplaceofnumber	49, 480
COMMAND\Xendinplaceofpagenumber	46, 485
COMMAND\Xendinsertsep@	259
COMMAND\Xendlemmadisablefontselection	52
COMMAND\Xendlemmafont	52, 482
COMMAND\Xendlemmaseparator	32, 51, 410
COMMAND\Xendletboxendlinenum	410
COMMAND\Xendlineflag	68
COMMAND\Xendlinenumannotationonlyfirst	48, 263, 489
COMMAND\Xendlinenumannotationonlyfirstintwo	48, 263, 489
COMMAND\Xendlinenumannotationposition	27, 68
COMMAND\Xendlineprefixmore	46, 68
COMMAND\Xendlineprefixsingle	46, 68
COMMAND\Xendlinerangeseparator	46, 68, 213, 412, 481
COMMAND\Xendmorethantwolines	31, 47, 68, 410, 478, 479
COMMAND\Xendnoidenticallinenumannotation	28, 263, 488
COMMAND\Xendnolinenum	48, 490
COMMAND\Xendnolinenumifannotation	48, 490
COMMAND\Xendnonumber	47, 480
COMMAND\Xendnote	255, 277–279, 478
COMMAND\Xendnotefontsize	52, 409
COMMAND\Xendnotenunfont	51, 53, 409
COMMAND\Xendnotes	258
COMMAND\Xendnumberonlyfirstinline	45, 481
COMMAND\Xendnumberonlyfirstintwolines	45, 481
COMMAND\Xendpagenumberonlyfirst	45, 485
COMMAND\Xendpagenumberonlyfirstifsingle	45, 485
COMMAND\Xendpagenumberonlyfirstintwo	45, 485
COMMAND\Xendparagraph	57, 475
COMMAND\Xendsep	57, 489
COMMAND\Xendstorelineinfo	256
COMMAND\Xendsublinesep	48, 68, 213
COMMAND\Xendsymlinenum	45, 481, 489
COMMAND\Xendsymlinenumannotation	48, 489
COMMAND\Xendsympagenum	46, 485
COMMAND\Xendtwolines	31, 47, 68, 410, 478, 479
COMMAND\Xendtwolinesbutnotmore	47, 68, 478, 479
COMMAND\Xendtwolinesonlyinsamepage	47, 68, 478, 479

COMMAND\Xendtxtbeforenotes	55, 487
COMMAND\Xendwrapcontent	52, 484
COMMAND\Xendwraplemma	52, 484
COMMAND\Xendwraplinenumannotation	28, 68
COMMAND\Xfootfmt	411
COMMAND\Xfootgroup	196
COMMAND\Xfootins	195
COMMAND\Xfootnote	64, 71, 143, 405, 472, 476–478, 482, 484
COMMAND\Xfootstarts	196
COMMAND\Xgroupbyline	55, 183, 227, 291, 414, 487–489
COMMAND\Xgroupbylines	485
COMMAND\Xgroupbylineseparetwolines	55
COMMAND\Xhangindent	53, 481, 489
COMMAND\Xhsizethreecol	412, 482, 483
COMMAND\Xhsizetwocol	54, 57, 410
COMMAND\Xinnotemark	54, 57, 284, 410
COMMAND\Xinplaceoflemmaseparator	71, 414, 490
COMMAND\Xinplaceofnumber	31, 51, 410
COMMAND\Xinsertparafootsep	31, 49, 410, 477, 479
COMMAND\Xledsetnormalparstuff	202, 203
COMMAND\Xlemmadisablefontselection	407, 408, 478
COMMAND\Xlemmafont	51
COMMAND\Xlemmaseparator	52, 482
COMMAND\Xlineflag	50, 51, 213, 286, 289, 292, 410
COMMAND\Xlinenumannotationonlyfirst	67, 412, 413, 484
COMMAND\Xlinenumannotationonlyfirstintwo	48, 223, 489
COMMAND\Xlinenumannotationposition	48, 223, 489
COMMAND\Xlinenumannotationposition@side	27, 67, 174
COMMAND\Xlinenumannotationpositionside	174
COMMAND\Xlinangeseparator	27
COMMAND\Xmaxhnotes	46, 67, 213, 412, 481
COMMAND\Xmorethantwolines	56, 79, 81, 409, 410, 475, 477
COMMAND\Xnoendnum	31, 46, 47, 67, 410, 477
COMMAND\Xnoidenticallylinenumannotation	48
COMMAND\Xnoindent	28, 67, 223, 488
COMMAND\Xnolemmaseparator	481
COMMAND\Xnolinenumber	51, 292, 410
COMMAND\Xnolinenumberifannotation	48, 219, 490
COMMAND\Xnonbreakableafternumber	48, 219, 490
COMMAND\Xnonumber	49, 410, 473
COMMAND\Xnonumberinfootnote	47, 48, 410
COMMAND\Xnotefontsize	410
COMMAND\Xnotefontsize@⟨s⟩	52, 409
COMMAND\Xnotenumfont	202, 206, 207
COMMAND\Xnoteswidthliketwocolumns	51, 409
COMMAND\Xnumberonlyfirstinline	57, 476
COMMAND\Xnumberonlyfirstintwolines	45, 46, 55, 116, 214, 256, 285, 286, 289, 410, 472, 477, 486
COMMAND\Xonlypstart	45, 55, 410, 472, 486
COMMAND\Xpagelinesep	47, 410, 472, 477
	49, 485

COMMAND\Xparafootsep	55, 116, 409, 410, 414, 484, 486, 487
COMMAND\Xparafootsep@series	202
COMMAND\Xparindent	52, 412, 414, 478, 481, 483, 489
COMMAND\Xprenotes	56, 252, 484
COMMAND\Xprenotes@	195, 252, 472
COMMAND\Xprintlines	115
COMMAND\Xpstart	47, 407, 410, 472, 477
COMMAND\Xpstarteverytime	47, 407, 410, 477
COMMAND\Xpstartonlyfirst	47, 490
COMMAND\Xpstartseparator	47, 490
COMMAND\Xragged	55
COMMAND\Xrigidbalance	204, 412, 482
COMMAND\Xsethangindent	212
COMMAND\Xstanza	47, 62
COMMAND\Xstanzaonlyfirst	47, 490
COMMAND\Xstanzaseparator	47
COMMAND\Xstorelineinfo	214
COMMAND\Xsublinesep	23, 48, 49, 67, 213, 412
COMMAND\Xsublinesepside	23, 49
COMMAND\Xsymlinenum	45, 55, 409, 410, 479, 486
COMMAND\Xsymlinenumannotation	48, 489
COMMAND\Xtextbeforenotes	186
COMMAND\Xtoendnotes	32, 278
COMMAND\Xtwolines	31, 46, 47, 67, 222, 224, 284, 410, 477
COMMAND\Xtwolinesappref	284
COMMAND\Xtwolinesbutnotmore	46, 47, 67, 410, 478
COMMAND\Xtwolinesbutnotmoreappref	285
COMMAND\Xtwolinesonlyinsamepage	47, 67, 410, 478
COMMAND\Xtxtbeforenotes	55, 410, 484, 485, 487
COMMAND\Xtxtbeforenotesonlyonce	55, 487
COMMAND\Xtxtbeforenumber	46
COMMAND\Xunvxh	200, 411
COMMAND\Xwidth	57, 412, 483
COMMAND\Xwrapcontent	52, 484
COMMAND\Xwraplemma	52, 54, 484
COMMAND\Xwraplinenumannotation	27, 28, 67, 175
COMMAND\Xwraplinenumannotation@ref	175
COMMAND\Xwraplinenumannotation@side	175
COMMAND\Xwraplinenumannotationref	28
COMMAND\Xwraplinenumannotationside	28
COMMAND\&	409
COMMAND\absline@num	112, 170
COMMAND\accent	142
COMMAND\actionlines@list	113, 172
COMMAND\actions@list	113
COMMAND\add@Xgroupbyline	183
COMMAND\add@hooktoggle@specific@to@cs	291
COMMAND\add@inserts	113, 183
COMMAND\add@inserts@next	183
COMMAND\add@msd@	354

COMMAND\add@msdata	354, 356
COMMAND\add@msdata@firstlineofpage	359
COMMAND\add@msddata	354
COMMAND\add@penalties	170, 185
COMMAND\addcontentsline	386
COMMAND\addfootins	405, 408
COMMAND\addfootinsX	405, 408
COMMAND\addtoendnotes	278
COMMAND\advancelabel@refs	303
COMMAND\advanceline	24, 115, 123, 138, 480
COMMAND\affixline@num	176, 180, 181, 325, 470
COMMAND\affixpstart@num	181
COMMAND\afterXrule	409
COMMAND\afterXsymlinenum	409
COMMAND\afterantilabe	62
COMMAND\aftergroup	141, 145
COMMAND\afterlemmaseparator	409
COMMAND\afternote	409
COMMAND\afternoteX	54, 408, 409
COMMAND\afternumberinfootnote	409
COMMAND\afterruleX	56, 475, 478
COMMAND\annot@end@print	223, 263
COMMAND\annot@list	115, 176
COMMAND\annotationref	27, 28, 64
COMMAND\antilabe	16, 62, 490
COMMAND\applabel	66, 305, 306, 478, 484
COMMAND\appref	64, 66–68, 311, 314, 482, 483, 489
COMMAND\apprefprefixmore	67, 409
COMMAND\apprefprefixsingle	66, 409
COMMAND\apprefwithpage	66, 68, 311, 314, 479, 482, 490
COMMAND\arrangementX	44, 81, 232, 283, 409
COMMAND\arrangementX@normal	238
COMMAND\article	16
COMMAND\at@every@pend	162
COMMAND\autopar	19, 158, 163, 164, 249, 471, 473, 474, 478, 488
COMMAND\ballast	80
COMMAND\ballast@count	170, 185
COMMAND\baselineskip	44, 198, 202
COMMAND\beforeXnotes	409
COMMAND\beforeXsymlinenum	409
COMMAND\beforeantilabe	62
COMMAND\beforeeledchapter	11, 77, 387
COMMAND\beforeinsertingX	53
COMMAND\beforelemmaseparator	409
COMMAND\beforenotesX	56, 411, 474, 475, 478
COMMAND\beforenumberinfootnote	409
COMMAND\begin	363
COMMAND\beginnumbering	18– 21, 97, 98, 102, 103, 112, 116, 117, 132, 133, 163, 254, 353, 472, 475, 479, 480, 485, 486
COMMAND\beginnumberingR	97

COMMAND\bf	472
COMMAND\bfseries	51, 472
COMMAND\bhookXnote	410
COMMAND\bhookgroupX	55, 482
COMMAND\bhooknoteX	53, 411, 480, 481
COMMAND\body	344
COMMAND\bodyfootmarkA	41
COMMAND\book	16
COMMAND\boxXendlinenum	410
COMMAND\boxXendlinenumalign	410
COMMAND\boxXendstartlinenum	410
COMMAND\boxendlinenum	410
COMMAND\boxlinefootnote	216
COMMAND\boxlinenum	410
COMMAND\boxlinenumalign	410
COMMAND\boxstartlinenum	410
COMMAND\boxsymlinenum	410
COMMAND\break	44, 200
COMMAND\brokenpenalty	185
COMMAND\c@page	134
COMMAND\c@page@page	134
COMMAND\centering	54
COMMAND\ch@ck@l@ck	470
COMMAND\ch@cksub@l@ck	180, 470
COMMAND\chapter	76, 388, 392, 475, 478, 480, 484
COMMAND\chaptermark	386
COMMAND\check@pb@in@verse	400
COMMAND\colalignX	54, 478
COMMAND\collect@body	364
COMMAND\color	484
COMMAND\colorbox	81
COMMAND\columns	57
COMMAND\columnwidth	198, 476
COMMAND\command names	284, 285
COMMAND\continuousnumberingwithcolumns@sync@linenumber@singletext	173
COMMAND\copyright	142
COMMAND\correct@Xfootins@box	477
COMMAND\correct@footinsX@box	477
COMMAND\count	205, 206
COMMAND\critex	471
COMMAND\critext	149, 404, 405, 408
COMMAND\curname	86
COMMAND\csquotes	275
COMMAND\ctab	380, 384
COMMAND\ctabtext	385
COMMAND\current@annot	176
COMMAND\dcoll	373
COMMAND\def	83, 100
COMMAND\dimen	206
COMMAND\dimexpr	57

COMMAND\discretionary	199
COMMAND\displaywidowpenalty	185
COMMAND\do@Xfeet	293, 470, 480, 485
COMMAND\do@actions	170–172, 470
COMMAND\do@actions@fixedcode	470
COMMAND\do@actions@next	171, 172
COMMAND\do@ballast	170, 185
COMMAND\do@feet@custom@order	293
COMMAND\do@insidelinehook	473
COMMAND\do@line	113, 140, 160, 164, 168, 169, 183, 185, 344, 470, 471, 473, 475
COMMAND\do@linehook	470
COMMAND\do@lockoff	114
COMMAND\do@lockon	114
COMMAND\dodoreintrafeet	469
COMMAND\doendnotes	31, 259, 411, 479, 486
COMMAND\doendnotesbysection	31, 259, 279, 479, 486
COMMAND\doennotes	486
COMMAND\doinsidelinehook	28, 475
COMMAND\doinsidethislinehook	29, 168, 488
COMMAND\dolinehook	28, 475
COMMAND\doreintrafeeti	480
COMMAND\doreintrafeetii	480
COMMAND\doxtrafeet	469
COMMAND\doxtrafeeti	480
COMMAND\doxtrafeetii	480
COMMAND\dummy@ref	141
COMMAND\edaftertab	76, 379, 380
COMMAND\edannotationref	308
COMMAND\edatleft	75, 377
COMMAND\edatright	75, 76, 378
COMMAND\edbforetab	76, 379, 380
COMMAND\edfilldimen	378
COMMAND\edfont@info	148
COMMAND\edgls	73, 332
COMMAND\edgls...	483
COMMAND\edglsadd	486
COMMAND\edindex	39, 71–73, 332, 333, 336, 338, 339, 368, 473, 475, 477, 480, 481, 485–487, 489
COMMAND\edindexlab	72, 73
COMMAND\edlabel	64–
66, 69, 142, 301, 303, 304, 307, 309, 317, 332, 368, 401, 413, 469, 472–474, 477, 482, 487	
COMMAND\edlabelE	66, 306
COMMAND\edlabelS	66, 306
COMMAND\edlabelSE	66
COMMAND\edlineref	64, 301, 410, 477, 479, 482, 486
COMMAND\edmakelabel	66, 317
COMMAND\edpageref	64, 301, 307, 317
COMMAND\edrowfill	379
COMMAND\edsublineref	64
COMMAND\edtabcolsep	372

COMMAND\edtext	7, 25, 26, 30, 33, 35, 36, 38, 58, 64–66, 70, 71, 74, 81, 101, 113, 115, 129, 131, 135, 136, 140–149, 151, 152, 154, 156, 174– 176, 305, 306, 310, 343, 368, 369, 388, 401, 404, 405, 408, 469, 471, 473, 475–479, 485–489
COMMAND\edtext@level	479
COMMAND\edtextlater	131
COMMAND\edvertdots	76, 378
COMMAND\edvertline	76, 378
COMMAND\elechapter	77
COMMAND\eled@sectioning@out	393
COMMAND\eledchapter	77, 408, 475, 480
COMMAND\eledchapter*	77
COMMAND\eledmac@error	469
COMMAND\eledsection	7, 17, 77, 141, 167, 387, 408, 477, 486, 488, 489
COMMAND\eledsection*	77
COMMAND\eledsubsection	77, 408
COMMAND\eledsubsection*	77
COMMAND\eledsubsubsection	77, 408
COMMAND\eledsubsubsection*	77
COMMAND\eledxxx	11, 78, 393, 475
COMMAND\eledxxxx	386
COMMAND\elsection	393
COMMAND\else	331, 387
COMMAND\emph	38
COMMAND\empty	96, 177, 178, 301
COMMAND\end	363
COMMAND\end@lemmas	141
COMMAND\endashchar	212
COMMAND\endgraf	160, 202, 249
COMMAND\endlock	24, 114, 139, 349
COMMAND\endminipage	326, 328, 469, 480
COMMAND\endmsdata	40
COMMAND\endnotes	478, 482
COMMAND\endnumbering	18, 19, 21, 98, 100, 101, 133, 470, 479, 485, 486
COMMAND\endnumberingR	97
COMMAND\endprint	254, 257, 279, 407
COMMAND\endstanzaextra	409
COMMAND\endsub	23, 114, 137
COMMAND\endverse	411
COMMAND\everypar	163
COMMAND\extensionchars	79, 98
COMMAND\externaldocument	69, 317
COMMAND\fx@x@l@cks	470
COMMAND>falseverse	408, 473, 475
COMMAND\fi	387
COMMAND\firstlinenum	22, 177, 471
COMMAND\firstsublinenum	22, 471
COMMAND\flag@end	135, 136, 147, 475
COMMAND\flag@end@RTL	136
COMMAND\flag@end@later	137
COMMAND\flag@start	135, 136, 147, 475, 476

COMMAND\flag@start@RTL	136
COMMAND\flag@start@later	137
COMMAND\flagstanza	63
COMMAND\floatingpenalty	191, 477
COMMAND\flush@notes	185, 186
COMMAND\fnpos	43, 251, 474, 485
COMMAND\footfmt	190, 193
COMMAND\footfmt...	233
COMMAND\footfootmarkA	41
COMMAND\footfudgefactor	200
COMMAND\footfudgefiddle	81, 198, 469
COMMAND\footgroup	190
COMMAND\footins	195
COMMAND\footnormal	284, 409, 469
COMMAND\footnormalX	409
COMMAND\footnote	41, 80, 228–230, 406, 470
COMMAND\footnote@lang	213
COMMAND\footnoteA	17, 41
COMMAND\footnoteB	17
COMMAND\footnoteC	29
COMMAND\footnoteE	41
COMMAND\footnoteX	9, 42, 275, 277, 485
COMMAND\footnoteX@reading	276
COMMAND\footnoteXmark	277, 486, 489
COMMAND\footnoteXmk	292
COMMAND\footnoteXtext	277, 486, 489
COMMAND\footnote⟨X⟩	142
COMMAND\footnote⟨X⟩mark	42
COMMAND\footnote⟨X⟩mk	42
COMMAND\footnote⟨X⟩nomk	42
COMMAND\footnote⟨X⟩text	42
COMMAND\footnotelang@lua	189
COMMAND\footnotelang@poly	189
COMMAND\footnotemark	42, 277
COMMAND\footnoteoption@	188, 481
COMMAND\footnoterule	205
COMMAND\footnotesize	52
COMMAND\footnotetext	42, 277
COMMAND\footparagraph	198, 284, 409, 475
COMMAND\footparagraphX	243, 409, 475
COMMAND\footsplitskips	470, 477
COMMAND\footstart	190, 195, 205
COMMAND\footstrut	202
COMMAND\footthreecol	409
COMMAND\footthreecolX	409, 478
COMMAND\foottwocol	409
COMMAND\foottwocolX	409, 478
COMMAND\foreignlanguage	52
COMMAND\fullstop	412
COMMAND\get@edindex@hyperref	337

COMMAND\get@edindex@ledinnote@command	333
COMMAND\get@fnmark	230
COMMAND\get@index@command	474
COMMAND\get@linelistfile	470
COMMAND\get@thisfootnote	237
COMMAND\getline@num	170, 171
COMMAND\gl@p	104
COMMAND\global	119
COMMAND\globaldefs	119
COMMAND\gls	73, 340
COMMAND\hangindentX	53, 478, 481, 489
COMMAND\hangingsymbol	409, 471
COMMAND\hbox	199
COMMAND\hfill	473
COMMAND\hidenumbering	25, 128, 413, 478, 488, 490
COMMAND\hidenumberingonleftpage	25, 128, 484
COMMAND\hidenumberingonrightpage	25, 128, 484
COMMAND\hline	74
COMMAND\hooktoggle@specific	291
COMMAND\hrulefill	379
COMMAND\hsize	44, 195, 198, 200, 206, 209, 249, 470, 476
COMMAND\hsizeX	412, 482, 483
COMMAND\hsizethreecol	410
COMMAND\hsizethreecolX	54, 57
COMMAND\hsizetwocol	410
COMMAND\hsizetwocolX	54, 57
COMMAND\hyperlinkR	337
COMMAND\hyperlinkformat	337
COMMAND\hyperlinkformatR	337
COMMAND\if@RTL	88, 145
COMMAND\if@edtext@	476, 479
COMMAND\if@eled@sectioning	393
COMMAND\if@firstlineofpage	88
COMMAND\if@firstlineofpageR	88
COMMAND\if@msd@options@fullpage	361
COMMAND\if@msdata@insertedfrompreviouspage	358
COMMAND\if@nobreak	161
COMMAND\if@noneed@Footnote	135
COMMAND\ifXnote@	97
COMMAND\ifafterendnumberingR	97
COMMAND\ifautopar	163
COMMAND\ifby@autopar	163
COMMAND\ifbypage@	104
COMMAND\ifbypage@R	105
COMMAND\ifbypstart@	104
COMMAND\ifbypstart@R	105
COMMAND\iffirst@linenum@out@	132, 133
COMMAND\ifindtl@innote	97
COMMAND\ifindtl@notenumber	97
COMMAND\ifinserthangingsymbol	344

COMMAND\ifinstanza	344
COMMAND\ifistwofollowinglines	224
COMMAND\ifl@d@Xlinenumber	219
COMMAND\ifl@d@Xmorethantwolines	219, 477
COMMAND\ifl@d@Xtwolines	219
COMMAND\ifl@d@dash	219
COMMAND\ifl@d@elin	218
COMMAND\ifl@d@esl	218
COMMAND\ifl@d@pnum	218
COMMAND\ifl@d@ssub	218
COMMAND\ifl@dend@X	277
COMMAND\ifl@dmemoir	469
COMMAND\ifl@dpaging	476
COMMAND\ifl@dpairing	96, 471
COMMAND\ifl@dprintingpages	477
COMMAND\ifl@dskipnumber	177
COMMAND\ifl@dstartendok	378
COMMAND\ifl@imakeidx	88
COMMAND\ifledRcol	97, 471
COMMAND\ifledRcol@	97, 475
COMMAND\iflemmacommand@	476
COMMAND\iflinenumannotationotherside	175
COMMAND\ifnoend@	259
COMMAND\ifnoledgroup@	331
COMMAND\ifnoteschanged@	115
COMMAND\ifnumberedpar@	157
COMMAND\ifnumbering	98, 101
COMMAND\ifnumberingR	97, 471
COMMAND\ifnumberline	147, 177
COMMAND\ifpst@rted	471
COMMAND\ifpst@rtedL	99
COMMAND\ifresumenummering@start	102
COMMAND\ifseriesbefore	282
COMMAND\ifstopmsdata@inserted@	353
COMMAND\ifsublines@	112, 125
COMMAND\iftrue	479
COMMAND\ifvmode	303
COMMAND\ifxxx	387
COMMAND\ignorespaces	145
COMMAND\imki@wrindexentry	88
COMMAND\immediate	132, 133, 254
COMMAND\indent	19, 163, 411
COMMAND\index	340, 485
COMMAND\indtl@wrindexentry	88
COMMAND\initnumbering@quote	385, 480
COMMAND\initnumbering@reg	470
COMMAND\initnumbering@sectcmd	480
COMMAND\innotemarkX	71, 414, 490
COMMAND\inplaceoflemmaseparator	410
COMMAND\inplaceofnumber	410

COMMAND\insert	147, 182, 190, 193, 207, 227, 233
COMMAND\insert@Xtxtbeforenotes	187, 207
COMMAND\insert@count	129, 135, 145
COMMAND\insert@countR	145
COMMAND\insert@msdata	354, 361
COMMAND\insert@txtbeforenotesX	187
COMMAND\inserthangingsymbol	473
COMMAND\insertlines@list	113, 129
COMMAND\insertparafootsepX	247
COMMAND\inserts@list	140, 158, 182, 183, 199
COMMAND\interAfootnotelinepenalty	471
COMMAND\interfootnotelinepenalty	471
COMMAND\interlinepenalty	191
COMMAND\interparanoteglue	408
COMMAND\justifying	54
COMMAND\keep@this@crossref@forinserting	228
COMMAND\l@advance@parledegroupp@beforenormalnotes	480
COMMAND\l@d@@wrindexhyp	476
COMMAND\l@d@add	150
COMMAND\l@d@end	254, 277
COMMAND\l@d@nums	145, 147, 149, 150, 218, 219
COMMAND\l@d@section	254
COMMAND\l@d@set	124, 138
COMMAND\l@dampcount	370
COMMAND\l@dbfnote	230, 470
COMMAND\l@dcheckstartend	378
COMMAND\l@dchset@num	124
COMMAND\l@dcolcount	370, 371
COMMAND\l@dcollect@@body	363
COMMAND\l@dcollect@body	363
COMMAND\l@dcsnote	475
COMMAND\l@dcsnotetext	169, 322
COMMAND\l@dcsnotetext@l	169, 322
COMMAND\l@dcsnotetext@r	169, 322
COMMAND\l@ddodoreinxtrafeet	294, 469
COMMAND\l@ddoxtrafeet	293, 294, 469
COMMAND\l@demptyd@ta	470
COMMAND\l@dend@close	254
COMMAND\l@dend@open	254
COMMAND\l@dend@stuff	254
COMMAND\l@denvbody	363
COMMAND\l@dfeetbeginmini	469
COMMAND\l@dfeetendmini	469
COMMAND\l@dgetline@margin	471
COMMAND\l@dgetlock@disp	471
COMMAND\l@dgetref@num	309
COMMAND\l@dgetsidenote@margin	319, 471
COMMAND\l@dgobbeloptarg	476
COMMAND\l@dgobblearg	476
COMMAND\l@dgobbleoptarg	368

COMMAND\l@dlabel@parse	309
COMMAND\l@dld@ta	176, 178
COMMAND\l@dlp@rbox	324
COMMAND\l@dlsn@te	471
COMMAND\l@dlsnote	475
COMMAND\l@dmake@labels	304, 318
COMMAND\l@dmake@labelsR	318
COMMAND\l@dnumptartsL	99, 471
COMMAND\l@dp@rsefootsspec	219
COMMAND\l@dparsefootsspec	219
COMMAND\l@dpush@begins	363
COMMAND\l@drd@ta	176, 178
COMMAND\l@dref@undefined	309
COMMAND\l@drsn@te	471
COMMAND\l@drsnote	475
COMMAND\l@dtabaddcols	378
COMMAND\l@dtabnoexpands	469
COMMAND\l@dumboxmpfoot	480
COMMAND\l@dunboxmpfoot	470
COMMAND\l@dunhbox@line	164
COMMAND\l@dzeropenalties	471, 476
COMMAND\l@noexpands@edgl	343
COMMAND\l@pb	399
COMMAND\l@prev@nopb	398
COMMAND\l@prev@pb	398
COMMAND\l@reg	406
COMMAND\l@secondoptarg	368
COMMAND\l@wrap@ifnotemptybox	95
COMMAND\label	20, 66, 69, 72, 73, 301, 302, 310
COMMAND\label@refs	301
COMMAND\labelstarttrue	20, 413, 472, 487
COMMAND\labelref@list	301, 304
COMMAND\language	199
COMMAND\lastbox	163
COMMAND\lastskip	137
COMMAND\latex@makecol	296
COMMAND\leavevmode	19, 163
COMMAND\led@check@nopb	399
COMMAND\led@check@pb	399
COMMAND\led@nopb	399, 400
COMMAND\led@nopbnum	399
COMMAND\led@pb	399, 400
COMMAND\led@pb@macro	399
COMMAND\led@pbnum	399
COMMAND\led@reinit@index@fornote	340
COMMAND\led@set@index@fornote	340
COMMAND\ledRflag	337
COMMAND\ledchapter	408, 472
COMMAND\ledfootinsdim	409
COMMAND\ledinnernote	69, 320, 475, 484

COMMAND\ledinnote	334, 407, 414, 479
COMMAND\ledinnotemark	407, 414, 478, 490
COMMAND\ledleftnote	69, 320
COMMAND\ledlinenum	110, 471
COMMAND\ledllfill	169
COMMAND\ledlsnotefontsetup	484
COMMAND\ledlsnotesep	70
COMMAND\ledlsnotewidth	69
COMMAND\lednopb	78, 399
COMMAND\lednopbinverse	400
COMMAND\lednopbinversetrue	61, 78
COMMAND\lednopbnum	399
COMMAND\ledouternote	69, 320, 475, 484
COMMAND\ledpb	78, 399, 408
COMMAND\ledpbnum	399
COMMAND\ledpbsetting	79, 399, 481
COMMAND\ledrightnote	69, 320
COMMAND\ledrsnotefontsetup	484
COMMAND\ledrsnotesep	70
COMMAND\ledrsnotewidth	69
COMMAND\ledsection	408
COMMAND\ledsectnomark	386
COMMAND\ledsectnotoc	386
COMMAND\ledsetnormalparstuff	407, 408, 478
COMMAND\ledsetnormalparstuff@common	249
COMMAND\ledsetnormalparstuffX	407, 408, 478
COMMAND\ledsidenote	69, 320, 322
COMMAND\ledsubsection	408
COMMAND\ledsubsubsection	408
COMMAND\ledxxx	475
COMMAND\left	75
COMMAND\leftctab	380
COMMAND\leftheadline	110
COMMAND\leftlinenum	23, 110, 469, 471
COMMAND\leftlinenumannotation	111
COMMAND\leftltab	379
COMMAND\leftnoteupfalse	70
COMMAND\leftpstartnum	181
COMMAND\leftftab	379
COMMAND\leftsidenote	322
COMMAND\leftskip	195, 198, 200
COMMAND\lemma	3, 30, 33, 35, 36, 38, 140, 144, 145, 148, 149, 151, 404, 471, 472, 479, 480, 482
COMMAND\lemmaseparator	410
COMMAND\let	34, 58, 142, 147, 277, 296, 349, 469
COMMAND\letboxXendendlinenum	410
COMMAND\line	204, 208
COMMAND\line@list	113, 115, 130, 147
COMMAND\line@list@stuff	98, 116, 117, 132, 469, 471
COMMAND\line@list@version	119
COMMAND\line@margin	106, 178, 319

COMMAND\line@num	112, 114, 177, 469
COMMAND\line@set	149, 150
COMMAND\lineannot	27, 65, 150
COMMAND\lineannot@set	150
COMMAND\lineation	22, 105, 487–489
COMMAND\linebreak	44
COMMAND\lineneation	483
COMMAND\linenum	27, 30, 33, 65, 66, 140, 149, 150, 307, 310, 317, 404
COMMAND\linenum@out	132, 301, 304
COMMAND\linenumannotation	25, 174, 487, 488
COMMAND\linenumannotationothersidefalse	27
COMMAND\linenumannotationothersidettrue	27, 490
COMMAND\linenumberlist	22, 96, 177, 178, 469
COMMAND\linenumberstyle	24, 109, 469, 486
COMMAND\linenumincrement	22, 471
COMMAND\linenummargin	23, 106, 319
COMMAND\linenumr@p	109, 469, 471
COMMAND\linenumrep	109, 471
COMMAND\linenumsep	23, 70, 110, 320
COMMAND\linrangesep@	292
COMMAND\lineref	301, 307, 317, 410, 477
COMMAND\list@clear	103
COMMAND\list@clearing@reg	471
COMMAND\list@create	103
COMMAND\lock@disp	108
COMMAND\lock@off	127
COMMAND\lock@on	126
COMMAND\lockdisp	24, 108
COMMAND\loop	186, 344
COMMAND\ltab	379, 380, 384
COMMAND\ltabtext	385
COMMAND\m@mmf@prepare	229
COMMAND\mainmatter	487, 488
COMMAND\makeatletter	168
COMMAND\makehboxoffhboxes	201, 202
COMMAND\makeindex	71, 336
COMMAND\makelabel	317
COMMAND\managestanza@modulo	345
COMMAND\marginpar	69, 80, 318, 319, 470
COMMAND\marginparwidth	69, 320
COMMAND\markboth	29, 168
COMMAND\mathchardef	345
COMMAND\maxhXnotes	410
COMMAND\maxhnotesX	56, 81, 409, 474, 475, 477, 478
COMMAND\maxlinesinpar@list	117
COMMAND\measurembdy	381
COMMAND\measuretbody	382
COMMAND\memorybreak	21
COMMAND\metaXXXvfootnote	227
COMMAND\microtype	164

COMMAND\morenoexpands	81, 82, 140, 142
COMMAND\morethantwolines	410
COMMAND\mpfnpos	43, 251, 474, 485
COMMAND\mpnormalfootgroup	469
COMMAND\mpnormalvfootnote	470
COMMAND\msdata	39, 40, 352, 353, 355, 486, 488
COMMAND\msdataposition	41
COMMAND\multfootsep	41, 229
COMMAND\multiplefootnotemarker	229
COMMAND\musixtex	474
COMMAND\n@num	471, 478
COMMAND\n@num@ref	478
COMMAND\new@line	134, 470
COMMAND\new@series	142
COMMAND\newcommand	34, 83, 100, 229, 304
COMMAND\newcommandx	34
COMMAND\newhookarg@specific	291
COMMAND\newhookcommand@series	284, 286, 478, 490
COMMAND\newhookcommand@series@reload	286
COMMAND\newhookcommand@toggle@reload	285, 476
COMMAND\newhooktoggle@series	285, 478
COMMAND\newhooktoggle@specific	290
COMMAND\newif	478
COMMAND\newline	44
COMMAND\newlinechar	278
COMMAND\newseries	42, 405, 408, 409
COMMAND\newseries@	268, 269, 282
COMMAND\newverse	61, 63, 408, 475, 486
COMMAND\next	344
COMMAND\next@action	117
COMMAND\next@actionline	117
COMMAND\next@insert	183
COMMAND\next@line@list@stuff	133, 487
COMMAND\nl@regR	119
COMMAND\no@expands	81, 142, 148, 277, 343, 469
COMMAND\noXlemmaseparator	410
COMMAND\nobreak	218
COMMAND\nocritical	269
COMMAND\noledsec	408
COMMAND\noendnotes	408
COMMAND\noexpand	406
COMMAND\nofamiliar	288
COMMAND\noindent	19, 20, 61, 163, 481
COMMAND\noindentX	481
COMMAND\nomk@	292
COMMAND\nonbreakableafternumber	410
COMMAND\nonnumberinfootnote	410
COMMAND\norelax	58
COMMAND\normal@footnotemarkX	233
COMMAND\normal@page@break	398

COMMAND\normal@pars	249
COMMAND\normalbfnoteX	471
COMMAND\normalbodyfootmarkX	233
COMMAND\normalfont	485
COMMAND\normalfootfmt	58, 195, 202, 212, 254, 484
COMMAND\normalfootfmtX	234
COMMAND\normalfootfootmarkX	234
COMMAND\normalfootgroup	196
COMMAND\normalfootgroupX	235
COMMAND\normalfootnoterule	191
COMMAND\normalfootstart	195, 198
COMMAND\normalfootstartX	234
COMMAND\normalvfootnote	193, 194
COMMAND\normalvfootnote@inserted	193, 194
COMMAND\normalvfootnoteX	233
COMMAND\notbool	387
COMMAND\notfontsetup	409
COMMAND\notfontsizeX	52, 409
COMMAND\notenumfont	409
COMMAND\notenumfontX	51, 409
COMMAND\notesXwidthliketwocolumns	410
COMMAND\noteswidthliketwocolumnsX	57, 410, 476, 478
COMMAND\num@lines	157, 185
COMMAND\numberlinefalse	21, 488
COMMAND\numberlinetrue	21, 488
COMMAND\numberonlyfirstinline	282, 410
COMMAND\numberonlyfirstintwolines	410
COMMAND\numberpstartfalse	20
COMMAND\numberpstarttrue	20, 47, 407, 471, 480, 486, 488
COMMAND\numberstanza	47
COMMAND\numberstanzafalse	62
COMMAND\numberstanzatrue	62
COMMAND\numlabfont	23, 57, 110
COMMAND\none@line	158
COMMAND\nonehalfspacing	481
COMMAND\nonlyXpstart	410
COMMAND\nonlysideX	276
COMMAND\page@action	114, 124
COMMAND\page@start	114, 471
COMMAND\pagecontents	114
COMMAND\pagenumbering	299
COMMAND\pageparbreak	408
COMMAND\pageref	66, 307
COMMAND\par	32, 44, 163, 249
COMMAND\par@line	158, 185
COMMAND\par@patch@pagenumbering	299
COMMAND\par@patch@thepage	134, 299
COMMAND\para@footgroup	198
COMMAND\para@footgroupX	246
COMMAND\para@footsetup	198, 469

COMMAND\para@footsetupX	244, 469, 476
COMMAND\para@vfootnoteX	245
COMMAND\parafootfmt	201, 202, 484
COMMAND\parafootfmtX	246
COMMAND\parafootftm	203
COMMAND\parafootftmX	247
COMMAND\parafootftmsep	409
COMMAND\parafootsep	410, 474, 479
COMMAND\parafootsepX	55, 116, 409, 410, 414, 484, 489, 490
COMMAND\parafootstart	198
COMMAND\parafootstartX	244
COMMAND\paravfootnote	199, 202
COMMAND\parfillskip	201
COMMAND\parindent	481
COMMAND\parindentX	53, 412, 481, 483, 489
COMMAND\parse@annot	176
COMMAND\parshape	80
COMMAND\parskip	20, 61, 163
COMMAND\pause@numbering	101
COMMAND\pausenumbering	21, 101, 102, 117, 118, 164, 474, 476, 483
COMMAND\pausenumbering@page@num	101
COMMAND\penalty	201
COMMAND\pend	2, 7, 18–21, 23, 24, 77, 78, 138, 140, 143, 150, 157, 158, 160–164, 181, 182, 351, 406, 474, 475, 484–487
COMMAND\preXnotes	478, 484
COMMAND\prenotesX	56, 253, 478
COMMAND\prepare@Xgroupbyline	227, 228
COMMAND\prepare@Xprenotes	251
COMMAND\prev@nopb	399
COMMAND\prev@pb	399
COMMAND\prevlineX	116
COMMAND\prevpageX@num	116
COMMAND\print@Xfootnoterule	478
COMMAND\print@Xnotes	294, 295
COMMAND\print@Xnotes@forpages	477
COMMAND\print@eledsection	167
COMMAND\print@footnoteXrule	478
COMMAND\print@leftmargin@eledsection	387
COMMAND\print@lemma	213
COMMAND\print@line	165
COMMAND\print@notesX@forpages	477
COMMAND\print@rightmargin@eledsection	387
COMMAND\printendlines	260, 268, 315, 412, 469, 471
COMMAND\printlinefootnote	214, 216, 477
COMMAND\printlinefootnotearea	216, 218, 477
COMMAND\printlinefootnotenumbers	215
COMMAND\printlines	195, 212, 218, 220, 260, 314, 412, 469, 471, 477, 482
COMMAND\printnpnum	407, 412
COMMAND\printpstart	213
COMMAND\protect	142, 406

COMMAND\providecommand	229, 469
COMMAND\pstarL	158
COMMAND\pstart	2, 7, 18–21, 23, 24, 76–78, 124, 138, 143, 147, 150, 157, 158, 161–163, 167, 182, 351, 392, 406, 407, 471–473, 475, 476, 478–480, 483–490
COMMAND\pstartinfootnote	410
COMMAND\pstartinfootnoteeverytime	410
COMMAND\pstartnum	181
COMMAND\pstartref	64, 301, 308, 474, 486
COMMAND\pstarts	471, 472
COMMAND\pstarts@readL	158
COMMAND\pstarts@typeset@L	158
COMMAND\raggedX	55
COMMAND\raggedleft	54
COMMAND\raggedright	54
COMMAND\raw@text	157, 158
COMMAND\rbracket	50, 51
COMMAND\read@linelist	116, 118
COMMAND\ref	66, 69, 72
COMMAND\reformatted@	314
COMMAND\reformattedwithpage	314
COMMAND\relax	20, 124, 147, 171, 183, 349, 368, 406
COMMAND\renewcommand	81, 409, 412
COMMAND\reset@current@annot	176
COMMAND\reset@msd@options@iffullpage	361
COMMAND\resetlinenumannotation	26, 176
COMMAND\resetprevline@	116
COMMAND\resetprevpage@	116
COMMAND\resumenumbering	21, 97, 98, 102, 103, 117, 118, 164, 471, 475, 476, 483
COMMAND\right	75
COMMAND\rightctab	380
COMMAND\rightlinenum	23, 110, 469, 471
COMMAND\rightlinenumannotation	111
COMMAND\rightltab	380
COMMAND\rightnoteupfalse	70
COMMAND\rightrtab	380
COMMAND\right sidenote	322
COMMAND\rightskip	195, 198, 200, 201
COMMAND\rightstartnum	181
COMMAND\rigidbalance	204, 206, 208, 412, 482
COMMAND\rigidbalanceX	204, 412, 482
COMMAND\robustify	45, 48
COMMAND\roman	373, 482
COMMAND\rtab	379–381, 384
COMMAND\rtabtext	381, 385
COMMAND\sameparalletpagenumber	134
COMMAND\sameword	17, 34–36, 38, 131, 150–153, 156, 414, 477, 479, 481, 484, 487, 489
COMMAND\sameword@inedtext	152
COMMAND\saweword	151
COMMAND\scriptsize	110
COMMAND\section	76, 471, 485

COMMAND\section@num	98
COMMAND\sectionmark	386
COMMAND\select@lemmafont	58, 188
COMMAND\series	268
COMMAND\series@	268
COMMAND\seriesatbegin	42, 281, 478
COMMAND\seriesatend	42, 281, 478
COMMAND\set@Xtxtbeforenotes	186
COMMAND\set@continuousnumberingforl	103
COMMAND\set@line	147
COMMAND\set@line@action	114, 125
COMMAND\set@txtbeforenotesX	187
COMMAND\setSErefonlypageprefixmore	67, 314, 483, 486
COMMAND\setSErefonlypageprefixsingle	67, 314, 483, 486
COMMAND\setSErefprefixmore	67
COMMAND\setSErefprefixsingle	67
COMMAND\setapprefprefixmore	67, 409
COMMAND\setapprefprefixsingle	67, 68, 409, 482
COMMAND\setcommand@series	283
COMMAND\sethangindentX	212
COMMAND\sethangingsymbol	60, 343, 409, 481
COMMAND\sethanginsymbol	59
COMMAND\setistwofollowinglines	224
COMMAND\setl@dlprbox	324
COMMAND\setline	24, 115, 119, 124, 138, 142, 480
COMMAND\setlinenum	24, 119, 124, 138, 161, 469, 487
COMMAND\setlinenumannotationsep	28, 413, 488
COMMAND\setmsdatalabel	40
COMMAND\setmsdataposition	486
COMMAND\setmsdataseries	40
COMMAND\setprintendlines	260, 264, 471
COMMAND\setprintlines	220, 224, 260, 471
COMMAND\setsidenotesep	70
COMMAND\setsidenotsep	409
COMMAND\setstanzaindent	346
COMMAND\setstanzaindents	60, 345, 406, 490
COMMAND\setstanzapenalties	345
COMMAND\setstanzavalues	345
COMMAND\settoggle@series	283, 472, 476
COMMAND\showlemma	141, 469, 470
COMMAND\showwordrank	38, 152
COMMAND\sidenote@margin	470
COMMAND\sidenotemargin	69, 470, 475
COMMAND\sidenotesep	409
COMMAND\sidepstartnumtrue	20
COMMAND\skip	195
COMMAND\skipnumbering	25, 127, 139, 471, 478, 479
COMMAND\skipnumbering@reg	478
COMMAND\small	52
COMMAND\somemacro	38

COMMAND\special	14
COMMAND\splitmaxdepth	191, 206
COMMAND\splitoff	204
COMMAND\splittopskip	191, 206, 207
COMMAND\stanza	24, 25, 61–63, 97, 349, 409, 411, 481, 486
COMMAND\stanza@hang	348
COMMAND\stanza@line	348
COMMAND\stanzaindent	60, 346, 477
COMMAND\stanzaindent*	60
COMMAND\stanzaindentbase	345
COMMAND\stanzanumwrapper	62
COMMAND\startlock	22, 24, 114, 139, 349
COMMAND\startstanzahook	409
COMMAND\startsub	23, 114, 137
COMMAND\stopmsd	355
COMMAND\stopmsdata	40, 353
COMMAND\store@annot@to@absline	175
COMMAND\strip@pt	198
COMMAND\strutbox	206
COMMAND\sub@action	114, 125
COMMAND\sub@lock	113
COMMAND\sub@off	122, 304
COMMAND\sub@on	122, 304
COMMAND\subline@num	112, 114
COMMAND\sublinenum@rep	469
COMMAND\sublinenumberstyle	24, 109, 469
COMMAND\sublinenumincrement	22
COMMAND\sublinenumr@p	109, 469, 471
COMMAND\sublinenumrep	109, 471
COMMAND\sublineref	64, 301, 308
COMMAND\subsectionmark	386
COMMAND\sw@inthisedtext	144
COMMAND\sw@list@inedtext	148, 156
COMMAND\sw@txt	153
COMMAND\swnoexpands	38, 487
COMMAND\symlinenum	410
COMMAND\symplinenum	409
COMMAND\sza@penalty	348
COMMAND>tag	477
COMMAND\text	404
COMMAND\text<language>	52
COMMAND\textbeforenotesX	187
COMMAND\textcolor	81
COMMAND\textheight	81
COMMAND\textsuperscript	27, 95, 175
COMMAND\the	134, 469
COMMAND\thefootnoteA	41
COMMAND\thefootnoteX	473
COMMAND\thelabidx	338, 339
COMMAND\thepage	119, 134, 299

COMMAND\thepstart	20, 413
COMMAND\thepstartL	472
COMMAND\thepstartR	472
COMMAND\thestanza	62
COMMAND\this@crossref@end	228
COMMAND\this@line@list@version	132
COMMAND\this@section@next@page@num	101
COMMAND\this@section@page@num	115
COMMAND\thisfootnote	237
COMMAND\threecol@begin@insert	207
COMMAND\threecolfootfmt	207, 484
COMMAND\threecolfootfmtX	242
COMMAND\threecolfootgroup	206
COMMAND\threecolfootgroupX	243
COMMAND\threecolfootsetup	205
COMMAND\threecolfootsetupX	242
COMMAND\threecolvfootnote	206
COMMAND\threecolvfootnote@inserted	206
COMMAND\threecolvfootnoteX	242
COMMAND\toendnotes	32, 258, 484
COMMAND\twocolfootfmt	484
COMMAND\twocolfootfmtX	240
COMMAND\twocolfootgroupX	240
COMMAND\twocolfootsetupX	239
COMMAND\twocolvfootnoteX	240
COMMAND\twolines	282, 410
COMMAND\twolines@A	282
COMMAND\twolines@B	282
COMMAND\twolines@C	282
COMMAND\twolinesbutnotmore	410
COMMAND\twolinesonlyinsamepage	410
COMMAND\txbeforeXnotes	410
COMMAND\txbeforenotesX	55, 487
COMMAND\txbeforenotesonlyonceX	55, 487
COMMAND\uline	42
COMMAND\unhbox	164, 199
COMMAND\unpenalty	201, 202
COMMAND\unskip	201
COMMAND\unvxh	201, 411
COMMAND\unvxhX	411
COMMAND\upbracefill	379
COMMAND\usingcritext	405, 408
COMMAND\usingdtext	405, 408
COMMAND\VAfootnote	190
COMMAND\vadjust	136
COMMAND\variant	33
COMMAND\ vbox	160, 163, 199, 200, 204, 251
COMMAND\vfootnote	190, 195, 199, 206
COMMAND\vl@dbfnote	230, 470
COMMAND\vl@disnote	323

COMMAND\vl@dlsnote	323
COMMAND\vl@dosnote	323
COMMAND\vl@drsnote	323
COMMAND\vnumfootnoteX	471
COMMAND\vsizer	56, 81
COMMAND\vsplit	185
COMMAND\waklam	379
COMMAND\waklamec	379
COMMAND\wapunktel	379
COMMAND\wastricht	379
COMMAND\widthX	57, 412, 483
COMMAND\wrap@edcrossref	307, 476
COMMAND\wrapcontentX	52, 484
COMMAND\wrapped@bodyfootmarkX	248
COMMAND\wrapped@footfootmarkX	248
COMMAND\x...	65
COMMAND\xabslineref	308
COMMAND\xannotationref	65
COMMAND\xdef	104, 349
COMMAND\xflagref	65, 309, 412, 482
COMMAND\xleft@appenditem	104, 141
COMMAND\xlineref	65, 412, 482
COMMAND\xpageref	65
COMMAND\xparse	39
COMMAND\xpstartref	65, 474, 487
COMMAND\xr	69
COMMAND\xright@appenditem	104
COMMAND\xsublineref	65
COMMAND\xxref	65, 310, 317, 474, 477, 484
COMMAND\xxxmatter	299
ENVIRONMENTastanza	98, 482
ENVIRONMENTedarrayc	384
ENVIRONMENTedarrayl	384
ENVIRONMENTedarrayr	384
ENVIRONMENTedtabular	489
ENVIRONMENTedtabularc	385
ENVIRONMENTedtabularl	385
ENVIRONMENTedtabularr	385
ENVIRONMENTledgroup	87, 329, 412, 482
ENVIRONMENTledgroupsize	330
PACKAGE(r)(e)ledmac	42
PACKAGEEledmac	114, 335, 407, 408, 477, 478
PACKAGEEledpar	478
PACKAGEEtoolbox	86
PACKAGEParallel	416
PACKAGEReledmac	62, 411, 412
PACKAGEamsgen	362
PACKAGEamsmath	362
PACKAGEbabel	52, 82, 373, 482
PACKAGEbiblatex	80

PACKAGEbidi	52, 53, 88, 481, 489
PACKAGEcalc	490
PACKAGEcaption	96
PACKAGEcolor	81
PACKAGEcsquotes	486
PACKAGEedmac	1, 6, 11, 13–15, 83, 218, 228, 301, 345, 404, 416, 469
PACKAGEedstanza	1, 14, 15, 343
PACKAGEeledmac	1, 11, 15, 17, 72, 228, 331, 335, 366, 388, 401, 405, 407–409, 473, 475, 477
PACKAGEeledpar	191, 416, 471, 475–477
PACKAGEetex	481
PACKAGEetoolbox	103, 150, 268, 282, 293, 322, 387, 398
PACKAGEfancyhdr	296, 485
PACKAGEfloatrow	79, 412
PACKAGEfootmisc	41, 82, 88, 228, 229, 416, 485
PACKAGEgeometry	16
PACKAGEglossaries	73, 340, 482
PACKAGEhandout	476
PACKAGEhyperlink	276
PACKAGEhyperref	65, 144, 248, 302, 337, 338, 391, 401, 474–476, 483, 486, 489, 490
PACKAGEifluatex	86
PACKAGEifxetex	86
PACKAGEimakeidx	70, 71, 80, 87, 88, 331, 335, 408, 473–475, 477
PACKAGEindextols	340
PACKAGEindextool	408
PACKAGEindextools	70, 71, 80, 87, 88, 97, 331, 335, 340, 408, 477, 482, 485
PACKAGEledarab	82
PACKAGEledmac	1, 11, 14, 15, 82, 103, 335, 404, 405, 408, 411
PACKAGEledpar	82
PACKAGEMemoir	87, 335, 408, 416, 475, 480
PACKAGEMorewrites	80
PACKAGEMusixtex	475
PACKAGEperpage	482
PACKAGEpolyglossia	50, 82, 189, 213, 482, 489
PACKAGEragged2e	54, 86
PACKAGEreledmac	1, 2, 6, 11–13, 15–18, 21, 22, 25, 28, 29, 31, 33–35, 39, 41–43, 45, 46, 48, 50, 52, 54, 56, 58, 60, 63–66, 69–73, 78–84, 105, 107, 113, 115, 118, 119, 122, 132–134, 142, 145, 147, 150, 151, 182, 192, 195, 200, 212, 228, 229, 254, 269, 274, 282, 293, 298, 307, 308, 311, 317, 318, 335, 358, 362, 366, 386, 387, 400, 401, 408, 409, 411–414, 480, 483, 485
PACKAGEreledpar	1, 4, 6, 9, 17, 20, 22, 42, 57, 65, 67, 68, 78–80, 82, 84, 96, 105, 117, 122, 133, 134, 145, 147, 158, 192, 196, 249, 250, 269, 275, 292, 294, 295, 298, 331, 343, 386, 481, 482, 484, 485, 487, 488
PACKAGESuffix	86
PACKAGETabmac	1, 14, 15, 416
PACKAGEthalié	62
PACKAGEulem	42
PACKAGEuninormalize	35
PACKAGExargs	34, 86
PACKAGExkeyval	84, 292
PACKAGExparse	86, 488
PACKAGEX	5, 69, 318, 483

PACKAGExref	317
PACKAGExstring	86, 338

A

\absline@num	1
Abu Kamil Shuja' b. Aslam	14
\actionlines@list	1
\actions@list	1
\add@hookarg@specific@to@cs	1
\add@hooktoggle@specific@to@cs	1
\add@inserts	1
\add@inserts@next	1
\add@msd@	1
\add@msdata	1
\add@msdata@firstlineofpage	1
\add@penalties	1
\add@Xgroupbyline	1
\addtol@denvbody	1
Adelard II	14
\advancelabel@refs	1
\advanceline	1, 24
\Aendnote	31
\affixline@num	1
\affixpstart@num	1
\affixside@note	1
\Afootnote	30
\afterantilabe	62
\afternoteX	54
\afterruleX	56
\ampersand	1, 63
\annot@list	1
\annotationref	1, 64
\antilabe	1, 62
\append@notesX	1
\append@Xnotes	1
\applabel	1, 66
\appref	1, 66
\apprefwithpage	1, 66
\arrangementX	1, 44
\arrangementX@normal	1
\arrangementX@paragraph	1
\arrangementX@threecol	1
\arrangementX@twocol	1
\at@every@pend	1
\AtEndEveryPend	1, 20
\AtEveryPend	1, 20
\AtEveryPstart	1, 20
\AtEveryStanza	1, 61
\AtEveryStopStanza	1, 61
\AtStartEveryPstart	1, 20

\AtStartEveryStanza	1, 61
\autopar	1, 19

B

\ballast	80
\ballast@count	1
Beeton, Barbara Ann Neuhaus Friend	19
\beforeantilabe	62
\beforeeledchapter	1
\BeforeEveryStopStanza	1, 61
\beforeinsertingX	53
\beforeinsertion@X	1
\beforenotesX	56
\beginnumbering	1, 18
\Bendnote	31
\Bfootnote	30
\bhookgroupX	55
\bhooknoteX	53
\bodyfootmarkA	41
\boxfootnotenumbers	1
Bredon, Simon	14
Breger, Herbert	14, 366
Brey, Gerhard	14
Busard, Hubert L. L.	14
\bypage@false	1
\bypage@true	1
\bypstart@false	1
\bypstart@true	1

C

\c@addcolcount	1
\c@ballast	1
\c@firstlinenum	1
\c@firstsublinenum	1
\c@labidx	1
\c@linenumincrement	1
\c@sublinenumincrement	1
\Cendnote	31
\Cfootnote	30
\ch@ck@l@ck	1
\ch@cksub@l@ck	1
\chapter	1
\check@pb@in@verse	1
Chester, Robert of	14
Claassens, Geert H. M.	14
\colalignX	54
\continuousnumberingwithcolumns@sync@linenumber@singletext	1
Copernicus, Nicolaus	14
\critext	404
\ctab	1

<code>\ctabtext</code>	1
<code>\current@annot</code>	1

D

Dekker, Dirk-Jan	81
<code>\Dendnote</code>	31
<code>\Dfootnote</code>	30
<code>\disable@endnotes</code>	1
<code>\disable@familiarnotes</code>	1
<code>\disable@notes</code>	1
<code>\disable@sidenotes</code>	1
<code>\disablel@dtabfeet</code>	1
<code>\do@actions</code>	1
<code>\do@actions@fixedcode</code>	1
<code>\do@actions@next</code>	1
<code>\do@ballast</code>	1
<code>\do@feet@custom@order</code>	1
<code>\do@feetX</code>	1
<code>\do@insidelinehook</code>	1
<code>\do@line</code>	1
<code>\do@linehook</code>	1
<code>\do@lockoff</code>	1
<code>\do@lockoffL</code>	1
<code>\do@lockon</code>	1
<code>\do@lockonL</code>	1
<code>\do@Xfeet</code>	1
<code>\doedindexlabel</code>	1
<code>\doendnotes</code>	1, 31
<code>\doendnotesbysection</code>	1, 31
<code>\doinsidelinehook</code>	1, 28
<code>\doinsidethislinehook</code>	1, 29
<code>\dolinehook</code>	1, 28
<code>\dosplits</code>	1
Downes, Michael	80, 199, 201
<code>\dummy@edindex</code>	1
<code>\dummy@edtext</code>	1
<code>\dummy@edtext@showlemma</code>	1
<code>\dummy@ref</code>	1

E

<code>\edaftertab</code>	1, 76, 379
<code>edarrayc</code> (environment)	73
<code>edarrayl</code> (environment)	73
<code>edarrayr</code> (environment)	73
<code>\edatleft</code>	1, 75
<code>\edatright</code>	1, 75
<code>\edbeforetab</code>	1, 76, 379
<code>\edfilldimen</code>	1
<code>\edfont@info</code>	1
<code>\edindex</code>	1, 70

<code>\edindexlab</code>	1, 72
<code>\EDLABEL</code>	1
<code>\edlabel</code>	1, 64
<code>\edlabelE</code>	1, 66
<code>\edlabels</code>	1, 66
<code>\edlabelSE</code>	1, 66
<code>\edlineref</code>	1, 64
<code>\edmakelabel</code>	1, 65
<code>\edpageref</code>	1, 64
<code>\edrowfill</code>	1, 74
<code>\EDTAB</code>	1
<code>\edtabcolsep</code>	1, 74
<code>\EDTABINDENT</code>	1
<code>\edtabindent</code>	1
<code>\EDTABtext</code>	1
<code>edtabularc (environment)</code>	73
<code>edtabularl (environment)</code>	73
<code>edtabularr (environment)</code>	73
<code>\EDTEXT</code>	1
<code>\edtext</code>	1, 30
<code>\edvertdots</code>	1, 76
<code>\edvertline</code>	1, 76
<code>\Eendnote</code>	31
<code>\Efootnote</code>	30
<code>\eled@chapter</code>	1
<code>\eled@section</code>	1
<code>\eled@sectioning@out</code>	1
<code>\eled@subsection</code>	1
<code>\eled@subsubsection</code>	1
<code>\eledchapter</code>	1
<code>\eledchapter*</code>	1
<code>\eledsection</code>	1
<code>\eledsection*</code>	1
<code>\eledsubsection</code>	1
<code>\eledsubsection*</code>	1
<code>\eledsubsubsection</code>	1
<code>\eledsubsubsection*</code>	1
<code>\enablel@dtabfeet</code>	1
<code>\end@lemmas</code>	1
<code>\endashchar</code>	1
<code>\endline@num</code>	1
<code>\endlock</code>	1, 24
<code>\endminipage</code>	1
<code>\endnumbering</code>	1, 18
<code>\endpage@num</code>	1
<code>\endprint</code>	1
<code>\endquotation</code>	1
<code>\endquote</code>	1
<code>\endsub</code>	1, 23
<code>\endsubline@num</code>	1

environments:	
edarrayc	73
edarrayl	73
edarrayr	73
edtabularc	73
edtabularl	73
edtabularr	73
ledgroup	63
ledgroupsize	63
minipage	63
Euclid	14
\extensionchars	<u>1</u> , 79

F

\f@x@l@cks	<u>1</u>
Fairbairns, Robin	41
\first@linenum@out@false	<u>1</u>
\first@linenum@out@true	<u>1</u>
\firsthalf@antilabe@wd	<u>1</u>
\firstlinenum	<u>1</u> , 22
\firstseriesX@	<u>1</u>
\firstsublinenum	<u>1</u> , 22
\firstXseries@	<u>1</u>
\flag@end	<u>1</u>
\flag@end@later	<u>1</u>
\flag@end@RTL	<u>1</u>
\flag@start	<u>1</u>
\flag@start@later	<u>1</u>
\flag@start@RTL	<u>1</u>
\flagstanza	<u>1</u> , 63
\flush@notes	<u>1</u>
\fnpos	<u>1</u> , 42
Folkerts, Menso	14
\footfootmarkA	41
\footfudgefiddle	<u>1</u> , 81
\footnote	<u>1</u>
\footnoteA	41
\footnoteB	41
\footnoteC	41
\footnoteD	41
\footnoteE	41
\footnotelang@lua	<u>1</u>
\footnotelang@poly	<u>1</u>
\footnoteoptions@	<u>1</u>
\footnoteXmark	42
\footnoteXtext	42
\footsplitskips	<u>1</u>
\fullstop	<u>1</u>

G

Gädeke, Nora	14
\get@edindex@hyperref	1
\get@edindex@ledinnote@command	1
\get@firsthalf@antilabe@wd	1
\get@fnmark	1
\get@fnmarkX	1
\get@index@command	1
\get@linelistfile	1
\get@pstartcounter	1
\get@stanzacounter	1
\get@sw@txt	1
\get@thisfootnote	1
\get@thisfootnoteX	1
\getline@num	1
\gl@p	1

H

\h@num	1
\hangindentX	53
\hidenumbering	1, 25
\hidenumberingonleftpage	1, 25
\hidenumberingonrightpage	1
\Hilfsbox	1
\hilfsbox	1
\hilfscount	1
\HILFSskip	1
\Hilfsskip	1
\hilfsskip	1
\hookarg@specific	1
\hooktoggle@specific	1
\hsizethreecolX	54
\hsizetwocolX	54
\Hy@raisedlink@left	1
\hyperlinkformat	1
\hyperlinkformatR	1
\hyperlinkR	1

I

\if@addsw	1
\if@edtabular	1
\if@edtext@secondarg@	1
\if@eled@sectioning	1
\if@firstlineofpage	1
\if@led@nofoot	1
\if@ledgroup	1
\if@lemmacommand@	1
\if@msdata@insertedfrompreviouspage	1
\if@noeled@sec	1
\if@noneed@Footnote	1

<code>\if@RTL</code>	1
<code>\ifafterendnumberingR</code>	1
<code>\ifantilabe@</code>	1
<code>\ifat@every@pend@star@</code>	1
<code>\ifat@every@pstart@star@</code>	1
<code>\ifautopar@pause</code>	1
<code>\ifbypage@</code>	1
<code>\ifbypage@R</code>	1
<code>\ifbypstart@</code>	1
<code>\ifbypstart@R</code>	1
<code>\ifeledmaccompat@</code>	1
<code>\iffirst@linenum@out@</code>	1
<code>\ifinastanzaL</code>	1
<code>\ifinastanzaR</code>	1
<code>\ifindtl@innote</code>	1
<code>\ifindtl@notenumber</code>	1
<code>\ifinserthangingsymbol</code>	1
<code>\ifinstanza</code>	1
<code>\ifinstanzaL</code>	1
<code>\ifinstanzaR</code>	1
<code>\ifl@d@dash</code>	1
<code>\ifl@d@elin</code>	1
<code>\ifl@d@esl</code>	1
<code>\ifl@d@pnum</code>	1
<code>\ifl@d@ssub</code>	1
<code>\ifl@d@Xendlinenumber</code>	1
<code>\ifl@d@Xlinenumber</code>	1
<code>\ifl@d@Xmorethantwolines</code>	1
<code>\ifl@d@Xtwolines</code>	1
<code>\ifl@dend@X</code>	1
<code>\ifl@dhidenumber</code>	1
<code>\ifl@dmemoir</code>	1
<code>\ifl@dpaging</code>	1
<code>\ifl@dpairing</code>	1
<code>\ifl@dprintingcolumns</code>	1
<code>\ifl@dprintingpages</code>	1
<code>\ifl@dskipnumber</code>	1
<code>\ifl@dskipversenumber</code>	1
<code>\ifl@dstartendok</code>	1
<code>\ifl@footmisc</code>	1
<code>\ifl@imakeidx</code>	1
<code>\ifl@indextools</code>	1
<code>\ifledfinal</code>	1, 79
<code>\ifledgroupnotesL@</code>	1
<code>\ifledgroupnotesR@</code>	1
<code>\iflednopbinverse</code>	1
<code>\ifledRcol</code>	1
<code>\ifledRcol@</code>	1
<code>\iflinenumannotationotherside</code>	1
<code>\ifnocritical@</code>	1

<code>\ifnoend@</code>	1
<code>\ifnofamiliar@</code>	1
<code>\ifnoledgroup@</code>	1
<code>\ifnoquotation@</code>	1
<code>\ifnoresetlinenumannotation@</code>	1
<code>\ifnoteschanged@</code>	1
<code>\ifnumberedpar@</code>	1
<code>\ifnumbering</code>	1
<code>\ifnumberingR</code>	1
<code>\ifnumberline</code>	1
<code>\ifnumberstanza</code>	1
<code>\ifparapparatus@</code>	1
<code>\ifparledgroup</code>	1
<code>\ifprevpgnotnumbered</code>	1
<code>\ifpst@rtedL</code>	1
<code>\ifresumenumbering@start</code>	1
<code>\ifsameparallelpagenummer</code>	1
<code>\ifseriesbefore</code>	1
<code>\ifsidepstartnum</code>	1
<code>\ifstopmsdata@inserted@</code>	1
<code>\ifsublines@</code>	1
<code>\ifwidthliketwocolumns</code>	1
<code>\ifXendinsertsep@</code>	1
<code>\ifxindy@</code>	1
<code>\ifxindyhyperref@</code>	1
<code>\initnumbering@quote</code>	1
<code>\initnumbering@reg</code>	1
<code>\innotemarkX</code>	71
<code>\insert@count</code>	0, 1
<code>\insert@msdata</code>	1
<code>\insert@txtbeforenotesX</code>	1
<code>\insert@Xtxtbeforenotes</code>	1
<code>\inserthangingymbol</code>	1
<code>\insertlines@list</code>	1
<code>\insertparafootsepX</code>	1
<code>\inserts@list</code>	1

J

Jayaditya	14
-----------------	----

K

Kabelschacht, Alois	186
<code>\keep@this@crossref@forinserting</code>	1

L

<code>\l@advance@parledgroup@beforenormalnotes</code>	1
<code>\l@d@add</code>	1
<code>\l@d@nums</code>	1
<code>\l@d@section</code>	1
<code>\l@d@set</code>	1

<code>\ld@Xend</code>	1
<code>\ldampcount</code>	1
<code>\ldbfnote</code>	1
<code>\ldcheckcols</code>	1
<code>\ldcheckstartend</code>	1
<code>\ldchset@num</code>	1
<code>\ldcolcount</code>	1
<code>\ldcollect@body</code>	1
<code>\ldcollect@body</code>	1
<code>\ldcolwidth</code>	1
<code>\ldcsnote</code>	1
<code>\ldcsnotetext</code>	1
<code>\ldcsnotetext@l</code>	1
<code>\ldcsnotetext@r</code>	1
<code>\lddodoreinextrafeet</code>	1
<code>\lddoextrafeet</code>	1
<code>\lddedbeginmini</code>	1
<code>\lddedendmini</code>	1
<code>\ldemptyd@ta</code>	1
<code>\ldend@close</code>	1
<code>\ldend@open</code>	1
<code>\ldend@stuff</code>	1
<code>\ldend@Xfalse</code>	1
<code>\ldend@Xtrue</code>	1
<code>\ldenvbody</code>	1
<code>\ldesnote</code>	1
<code>\ldfambeginmini</code>	1
<code>\ldfamendmini</code>	1
<code>\ldfeetbeginmini</code>	1
<code>\ldfeetendmini</code>	1
<code>\ldgetline@margin</code>	1
<code>\ldgetlock@disp</code>	1
<code>\ldgetref@num</code>	1
<code>\ldgetsidenote@margin</code>	1
<code>\ldgobbleoptarg</code>	1
<code>\ldisnote</code>	1
<code>\ldlabel@parse</code>	1
<code>\ldld@ta</code>	1
<code>\ldlp@rbox</code>	1
<code>\ldlsn@te</code>	1
<code>\ldlsnote</code>	1
<code>\ldmake@labels</code>	1
<code>\ldmodforedtext</code>	1
<code>\ldnullfills</code>	1
<code>\ldnumpstartsL</code>	1
<code>\ldoldold@footnotetext</code>	1
<code>\ldp@rsefootspec</code>	1
<code>\ldparsedendline</code>	1
<code>\ldparsedendpage</code>	1
<code>\ldparsedendsub</code>	1

<code>\l@dparsedstartline</code>	1
<code>\l@dparsedstartpage</code>	1
<code>\l@dparsedstartsub</code>	1
<code>\l@dparsefootspec</code>	1
<code>\l@dpush@begins</code>	1
<code>\l@drd@ta</code>	1
<code>\l@dref@undefined</code>	1
<code>\l@drestorefills</code>	1
<code>\l@drestoreforedtext</code>	1
<code>\l@drp@rbox</code>	1
<code>\l@drsn@te</code>	1
<code>\l@drsnote</code>	1
<code>\l@dsetmaxcolwidth</code>	1
<code>\l@dskipnumberfalse</code>	1
<code>\l@dskipnumbertrue</code>	1
<code>\l@dtabaddcols</code>	1
<code>\l@dtabnoexpands</code>	1
<code>\l@dunboxmpfoot</code>	1
<code>\l@dunhbox@line</code>	1
<code>\l@dzeropenalties</code>	1
<code>\l@noexpands@edgl</code>	1
<code>\l@secondmandarg</code>	1
<code>\l@wrap@ifnotemptybox</code>	1
<code>\l@wrapcs@ifnotemptybox</code>	1
<code>\label</code>	66
<code>\labelstartfalse</code>	1
<code>\labelstarttrue</code>	1, 20
<code>\labelref@list</code>	1
<code>\labelrefsparseline</code>	1
<code>\labelrefsparsesubline</code>	1
<code>\last@page@num</code>	1
Lavagnino, John	13
<code>\led@check@nopb</code>	1
<code>\led@check@pb</code>	1
<code>\led@err@AutoparNotNumbered</code>	1
<code>\led@err@BadAction</code>	1
<code>\led@err@edtextoutsidepstart</code>	1
<code>\led@err@EdtextWithoutFootnote</code>	1
<code>\led@err@FootnoteNotInSecondArgEdtext</code>	1
<code>\led@err@HighEndColumn</code>	1
<code>\led@err@LineationInNumbered</code>	1
<code>\led@err@LowStartColumn</code>	1
<code>\led@err@ManyLeftnotes</code>	1
<code>\led@err@ManyRightnotes</code>	1
<code>\led@err@ManySidenotes</code>	1
<code>\led@err@NumberingNotStarted</code>	1
<code>\led@err@NumberingShouldHaveStarted</code>	1
<code>\led@err@NumberingStarted</code>	1
<code>\led@err@NumberingWithoutPstart</code>	1
<code>\led@err@PendInEdtext</code>	1

\led@err@PendNoPstart	1
\led@err@PendNotNumbered	1
\led@err@PstartInEdtext	1
\led@err@PstartInPstart	1
\led@err@PstartNotNumbered	1
\led@err@ReverseColumns	1
\led@err@samewordRTL	1
\led@err@toendnotes@outsidenumbering	1
\led@err@TooManyColumns	1
\led@err@UnequalColumns	1
\led@error@fail@patch@@doclearpage	1
\led@error@fail@patch@@iiiminipage	1
\led@error@fail@patch@@makecol	1
\led@error@fail@patch@@reinserts	1
\led@error@fail@patch@addtocounter	1
\led@error@fail@patch@endminipage	1
\led@error@fail@patch@setcounter	1
\led@error@PackageAfterEledmac	1
\led@mess@NotesChanged	1
\led@mess@SectionContinued	1
\led@nopb	1
\led@nopbnum	1
\led@pb	1
\led@pb@setting	1
\led@pbnum	1
\led@reinit@index@fornote	1
\led@set@index@fornote	1
\led@toksa	1
\led@toksb	1
\led@warn@AppLabelOutSecondArgEdtext	1
\led@warn@BadAction	1
\led@warn@BadAdvancelineLine	1
\led@warn@BadAdvancelineSubline	1
\led@warn@BadHookSeries	1
\led@warn@BadLineation	1
\led@warn@BadLinenummargin	1
\led@warn@BadLockdisp	1
\led@warn@BadSetline	1
\led@warn@BadSetlinenum	1
\led@warn@BadSidenotemargin	1
\led@warn@BadSublockdisp	1
\led@warn@DuplicateLabel	1
\led@warn@edinde@outsidenumbering	1
\led@warn@LineFileObsolete	1
\led@warn@NoFile	1
\led@warn@NoIndexFile	1
\led@warn@NoMarginpars	1
\led@warn@RefUndefined	1
\led@warn@SeriesStillExist	1
\led@warning@hsizeX@deprecated	1

<code>\led@warning@msdatawithoutstop</code>	1
<code>\led@warning@preXnotes@deprecated</code>	1
<code>\led@warning@Xhsize@deprecated</code>	1
<code>ledgroup (environment)</code>	63
<code>ledgroupsize (environment)</code>	63
<code>\ledinnernote</code>	1, 69
<code>\ledinnote</code>	1
<code>\ledinnotemark</code>	1
<code>\ledleftnote</code>	1, 69
<code>\ledlinenum</code>	1
<code>\ledllfill</code>	1
<code>\ledlsnotefontsetup</code>	1, 70
<code>\ledlsnotesep</code>	1, 70
<code>\ledlsnotewidth</code>	1, 69
<code>\lednopb</code>	1, 78
<code>\lednopbinversetrue</code>	78
<code>\lednopbnum</code>	1
<code>\ledouternote</code>	1, 69
<code>\ledpb</code>	1, 78
<code>\ledpbnum</code>	1
<code>\ledpbsetting</code>	1, 78
<code>\ledrightnote</code>	1, 69
<code>\ledrlfill</code>	1
<code>\ledrsnotefontsetup</code>	1, 70
<code>\ledrsnotesep</code>	1, 70
<code>\ledrsnotewidth</code>	1, 69
<code>\ledsectnomark</code>	1
<code>\ledsectnotoc</code>	1
<code>\ledsetnormalparstuff@common</code>	1
<code>\ledsetnormalparstuffX</code>	1
<code>\ledsidenote</code>	1, 69
<code>\leftctab</code>	1
<code>\leftlinenum</code>	1, 23
<code>\leftlinenumannotation</code>	1
<code>\leftltab</code>	1
<code>\leftnoteupfalse</code>	70
<code>\leftpstartnum</code>	1
<code>\leftrtab</code>	1
<code>Leibniz</code>	14
<code>\lemma</code>	1, 33
<code>\letsforverteilen</code>	1
<code>\line@list</code>	1
<code>\line@list@stuff</code>	1
<code>\line@list@version</code>	1
<code>\line@margin</code>	1
<code>\line@num</code>	1
<code>\line@set</code>	1
<code>\lineannot</code>	1, 27
<code>\lineannot@set</code>	1
<code>\lineation</code>	1, 22

<code>\linenum</code>	1, 33
<code>\linenum@out</code>	1
<code>\linenumannotation</code>	1, 25
<code>\linenumannotationothersidettrue</code>	27
<code>\linenumberlist</code>	1, 22
<code>\linenumberstyle</code>	1, 24
<code>\linenumincrement</code>	1, 22
<code>\linenummargin</code>	1, 23
<code>\linenumr@p</code>	1
<code>\linenumrep</code>	1
<code>\linenumsep</code>	1, 23
<code>\linerangesep@</code>	1
<code>\list@clear</code>	1
<code>\list@clearing@reg</code>	1
<code>\list@create</code>	1
<code>\lock@disp</code>	1
<code>\lock@off</code>	1
<code>\lock@on</code>	1
<code>\lockdisp</code>	1, 24
Lorch, Richard	14
<code>\ltab</code>	1
<code>\ltabtext</code>	1
Luecking, Dan	86

M

<code>\m@mmf@check</code>	1
<code>\m@mmf@prepare</code>	1
<code>\M@sect</code>	1
<code>\makehboxofhboxes</code>	1
<code>\managestanza@modulo</code>	1
<code>\maxhnotesX</code>	56
Mayer, Gyula	14
<code>\measurembody</code>	1
<code>\measuremcell</code>	1
<code>\measuremrow</code>	1
<code>\measuretbody</code>	1
<code>\measuretcell</code>	1
<code>\measuretrow</code>	1
Middleton, Thomas	14, 112
<code>minipage</code> (environment)	63
Mittelbach, Frank	13, 14
<code>\morenoexpands</code>	1, 81
<code>\mp@append@notesX</code>	1
<code>\mp@append@Xnotes</code>	1
<code>\mpfnpos</code>	1, 42
<code>\mpnormalfootgroup</code>	1
<code>\mpnormalfootgroupX</code>	1
<code>\mpnormalvfootnote</code>	1
<code>\mpnormalvfootnote@inserted</code>	1
<code>\mpnormalvfootnoteX</code>	1

\mppara@footgroupX	1
\mppara@vfootnoteX	1
\mpparafootgroup	1
\mpparavfootnote	1
\mpthreecolfootgroup	1
\mpthreecolfootgroupX	1
\mpthreecolfootsetup	1
\mpthreecolfootsetupX	1
\mptwocolfootgroup	1
\mptwocolfootgroupX	1
\mptwocolfootsetup	1
\mptwocolfootsetupX	1
\msdata	1, 39
\msdata@c	1
\msdata@cR	1
\multfootsep	1, 41
\multiplefootnotemarker	1

N

\n@num	1
\n@num@stanza	1
\new@line	1
\newhookarg@specific	1
\newhookcommand@series	1
\newhookcommand@series@reload	1
\newhooktoggle@series	1
\newhooktoggle@series@reload	1
\newhooktoggle@specific	1
\newseries@	1
\newverse	1
\NEXT	1
\next@line@list@stuff	1
\no@expands	1
\nomk@	1
\normal@footnotemarkX	1
\normal@page@break	1
\normal@pars	1
\normalbfnoteX	1
\normalbodyfootmarkX	1
\normalfootfmt	1
\normalfootfmtX	1
\normalfootfootmarkX	1
\normalfootgroup	1
\normalfootgroupX	1
\normalfootnoterule	1
\normalfootnoteruleX	1
\normalfootstart	1
\normalfootstartX	1
\normalvfootnote	1
\normalvfootnote@inserted	1

<code>\normalvfootnoteX</code>	1
<code>\notefontsizeX</code>	52
<code>\notenumfontX</code>	51
<code>\noteschanged@false</code>	1
<code>\noteschanged@true</code>	1
<code>\noteswidthliketwocolumnsX</code>	57
<code>\nulledindex</code>	1
<code>\nullsetzen</code>	1
<code>\num@lines</code>	1
<code>\numberedpar@false</code>	1
<code>\numberedpar@true</code>	1
<code>\numberingfalse</code>	1
<code>\numberingtrue</code>	1
<code>\numberlinefalse</code>	21
<code>\numberlinetrue</code>	21
<code>\numberpstartfalse</code>	1, 20
<code>\numberpstarttrue</code>	1, 20
<code>\numberstanzafalse</code>	62
<code>\numberstanzatrue</code>	62
<code>\numlabfont</code>	1, 57

O

<code>\old@hsize</code>	1
<code>\one@line</code>	1
<code>optionafter</code>	27
<code>optionantilabe</code>	62, 351
<code>optionauxdir</code>	16, 484
<code>optionbefore</code>	27
<code>optioncontinuousnumberingwithcolumns</code>	97, 166, 173, 483, 488
<code>optiondraft</code>	79
<code>optionfinal</code>	79
<code>optioninnnote</code>	482
<code>optioninnote</code>	482
<code>optionlinrangesep</code>	292
<code>optionminus</code>	483
<code>optionnocritical</code>	480, 482
<code>optionnoeledsec</code>	78, 392, 484
<code>optionnoend</code>	482
<code>optionnofamiliar</code>	480, 488
<code>optionnopenalties</code>	80, 484
<code>optionnoprefix</code>	68, 489
<code>optionnoresetlinenumannotation</code>	25, 48, 488
<code>optionnotenumber</code>	482, 485
<code>optionplus</code>	483
<code>optionprefixmore</code>	68, 489
<code>optionsameparallelpagenummer</code>	488
<code>optionswcaseinsensitive</code>	34, 487

P

<code>\page@action</code>	1
---------------------------	---

<code>\page@num</code>	1
<code>\pagelinesep</code>	1, 71
<code>\pageref</code>	66
<code>\par@line</code>	1
<code>\par@patch@pagenumbering</code>	1
<code>\par@patch@thepage</code>	1
<code>\para@footgroupX</code>	1
<code>\para@footsetup</code>	1
<code>\para@footsetupX</code>	1
<code>\para@vfootnoteX</code>	1
<code>\parafootfmt</code>	1
<code>\parafootfmtX</code>	1
<code>\parafootgroup</code>	1
<code>\parafootsepX</code>	54
<code>\parafootstart</code>	1
<code>\parafootstartX</code>	1
<code>\paravfootnote</code>	1
<code>\parindentX</code>	52
<code>\parse@annot</code>	1
<code>\pausenumbering</code>	1, 21
<code>\pausenumbering@page@num</code>	1
<code>\pend</code>	1, 18
Plato of Tivoli	14
<code>\postbodyfootmark</code>	1
<code>\prebodyfootmark</code>	1
<code>\prenotesX</code>	56
<code>\prepare@edindex@fornote</code>	1
<code>\prepare@prenotesX</code>	1
<code>\prepare@Xgroupbyline</code>	1
<code>\prepare@Xprenotes</code>	1
<code>\prev@nopb</code>	1
<code>\prev@pb</code>	1
<code>\prevpage@num</code>	1
<code>\print@eledsection</code>	1
<code>\print@footnoteXrule</code>	1
<code>\print@leftmargin@eledsection</code>	1
<code>\print@lemma</code>	1
<code>\print@line</code>	1
<code>\print@notesX</code>	1
<code>\print@rightmargin@eledsection</code>	1
<code>\print@Xfootnoterule</code>	1
<code>\print@Xnotes</code>	1
<code>\printendlines</code>	1
<code>\printlineendnote</code>	1
<code>\printlineendnotearea</code>	1
<code>\printlinefootnote</code>	1
<code>\printlinefootnotearea</code>	1
<code>\printlinefootnotennumbers</code>	1
<code>\printlines</code>	1
<code>\printnpnum</code>	1

\printpstart	1
\printsymlineendnotearea	1
\printsymlinefootnotearea	1
\printXafternumber	1
\printXbeforenumber	1
\pstart	1, 18
\pstarteref	1
\pstartnum	1
\pstartref	64
\pstarts@read@L	1
\pstarts@typeset@L	1

Q

\quotation	1
\quote	1

R

\raggedX	55
\raw@text	1
\rbracket	1
\read@linelist	1
\ref	66
\ref@reg@later	1
\Relax	1
\reledmac@error	1
\reledmac@warning	1
\removehboxes	1
\reset@current@annot	1
\reset@msd@options@iffullpage	1
\resetlinenumannotation	1
\resetprevline@	1, 116
\resetprevpage@	1
\resetprevpage@num	116
\restore@endnotes	1
\restore@familiarnotes	1
\restore@notes	1
\restore@sidenotes	1
\resumenumbering	1, 21
\rightctab	1
\rightlinenum	1, 23
\rightlinenumannotation	1
\rightltab	1
\rightnoteupfalse	70
\rightrtab	1
\rightstartnum	1
\rigidbalance	1
\rigidbalanceX	1
\rtab	1
\rtabtext	1

S

Sacrobosco	14
\sameword	<u>1</u> , 34
\sameword@inedtext	<u>1</u>
Schöpf, Rainer	14
\section@num	<u>1</u>
\select@lemmafnt	<u>1</u>
\select@lemmafnt	<u>1</u> , 58
\Seref	<u>1</u> , 66
\Serefnonlypage	66
\Serefwithpage	<u>1</u> , 66
\series	<u>1</u>
\seriesatbegin	<u>1</u> , 42
\seriesatend	<u>1</u> , 42
\set@continuousnumberingforL	<u>1</u>
\set@line	<u>1</u>
\set@line@action	<u>1</u>
\set@this@c@page	<u>1</u>
\set@txtbeforenotesX	<u>1</u>
\set@Xtxtbeforenotes	<u>1</u>
\setapprefprefixmore	66
\setapprefprefixsingle	66
\setcommand@series	<u>1</u>
\sethangindentX	<u>1</u>
\sethangingsymbol	<u>1</u> , 60
\setistwofollowinglines	<u>1</u>
\setl@dlp@rbox	<u>1</u>
\setl@drpr@box	<u>1</u>
\setline	<u>1</u> , 24
\setlinenum	<u>1</u> , 24
\setlinenumannotationsep	<u>1</u> , 28
\setmcellcenter	<u>1</u>
\setmcellleft	<u>1</u>
\setmcellright	<u>1</u>
\setmrowcenter	<u>1</u>
\setmrowleft	<u>1</u>
\setmrowright	<u>1</u>
\setmsdatalabel	<u>1</u> , 40
\setmsdataposition	<u>1</u> , 41
\setmsdataseries	<u>1</u> , 40
\setnoteswidthliketwocolumnsX@	<u>1</u>
\setnotesXpositionliketwocolumns@	<u>1</u>
\setparindentX	<u>1</u>
\setprintendlines	<u>1</u>
\setprintlines	<u>1</u>
\setSerefnonlypageprefixmore	67
\setSerefnonlypageprefixsingle	67
\setSerefprefixmore	67
\setSerefprefixsingle	67
\setsidenotessep	70

<code>\setstanzaindents</code>	1, 58
<code>\setstanzapenalties</code>	1, 60
<code>\setstanzavalues</code>	1
<code>\settcellcenter</code>	1
<code>\settcellleft</code>	1
<code>\settcellright</code>	1
<code>\settoggle@series</code>	1
<code>\setthrowcenter</code>	1
<code>\setthrowleft</code>	1
<code>\setthrowright</code>	1
<code>\setXnotespositionliketwocolumns@</code>	1
<code>\setXnoteswidthliketwocolumns@</code>	1
<code>\showlemma</code>	1, 79
<code>\showwordrank</code>	1, 38
<code>\sidenote@margin</code>	1
<code>\sidenotemargin</code>	1, 69
<code>\sidepstartnumtrue</code>	20
<code>\skip@lockoff</code>	1
<code>\skipnumbering</code>	1, 25
<code>\splitoff</code>	1
<code>\spreadmath</code>	1, 74
<code>\spreadtext</code>	1, 74
<code>\stanza</code>	1, 58
<code>\stanza@count</code>	1
<code>\stanza@hang</code>	1
<code>\stanza@indent</code>	1
<code>\stanza@line</code>	1
<code>\stanzaindent</code>	1, 60
<code>\stanzaindent*</code>	1, 60
<code>\stanzaindentbase</code>	1, 58
<code>\stanzanumwrapper</code>	1, 62
<code>\startlock</code>	1, 24
<code>\startsub</code>	1, 23
<code>\stepl@dcolcount</code>	1
<code>\stopmsdata</code>	1, 40
<code>\store@cannot@to@absline</code>	1
<code>\strip@szacnt</code>	1
<code>\sub@action</code>	1
<code>\sub@lock</code>	1
<code>\sub@off</code>	1
<code>\sub@on</code>	1
<code>\subline@num</code>	1
<code>\sublinenumberstyle</code>	1, 24
<code>\sublinenumincrement</code>	1, 22
<code>\sublinenumr@p</code>	1
<code>\sublinenumrep</code>	1
<code>\sublineref</code>	1, 64
<code>\sublines@false</code>	1
<code>\sublines@true</code>	1
<code>\sublock@disp</code>	1

\subblockdisp	1
Sullivan, Wayne	14, 80, 96, 101, 199, 201, 301, 343
\sw@noexpand	1
\swnoexpands	38
\sza@penalty	1

T

\tabHilfbox	1
\tabhilfbox	1
\theadcolcount	1
\theadtext	1
\theendpageline	1
\thefootnoteA	41
Theodosius	14
\thepageline	1
\thepar@page	1
\thepstart	1, 20
\thestanza	1, 62
\thestartpageline	1
\this@line@list@version	1
\this@section@last@page@num	1
\this@section@page@num	1
\threecol@begin@insert	1
\threecolfootfmt	1
\threecolfootfmtX	1
\threecolfootgroup	1
\threecolfootgroupX	1
\threecolfootsetup	1
\threecolfootsetupX	1
\threecolvfootnote	1
\threecolvfootnote@inserted	1
\threecolvfootnoteX	1
\toendnotes	1, 32
\toendnotes*	1
\twocolfootfmt	1
\twocolfootfmtX	1
\twocolfootgroup	1
\twocolfootgroupX	1
\twocolfootsetup	1
\twocolfootsetupX	1
\twocolvfootnote	1
\twocolvfootnote@inserted	1
\twocolvfootnoteX	1
\txtbeforenotesonlyonceX	55
\txtbeforenotesX	55

U

\unvxhX	1
---------------	---

V

Vamana	14
\variab	<u>1</u>
\vbfnoteX	<u>1</u>
\vl@dbfnote	<u>1</u>
\vl@dcsnote	<u>1</u>
\vl@disnote	<u>1</u>
\vl@dlsnote	<u>1</u>
\vl@dosnote	<u>1</u>
\vl@drsnote	<u>1</u>
\vnumfootnoteX	<u>1</u>

W

Whitney, Ron	14
\widthX	57
\wrap@edcrossref	<u>1</u>
\wrapcontentX	52
\wrapped@bodyfootmarkX	<u>1</u>
\wrapped@footfootmarkX	<u>1</u>
Wujastyk, Dominik	13

X

\X@atbegininsertion	<u>1</u>
\X@beforeinsertion	<u>1</u>
\X@doreinfeet	<u>1</u>
\xabslineref	<u>1</u>
\Xafterlemmaseparator	51
\Xafternote	54
\Xafternumber	49
\Xafterrule	56
\Xaftersymlinenum	49
\xannotationref	<u>1</u> , 64
\Xarrangement	<u>1</u> , 44
\Xarrangement@normal	<u>1</u>
\Xarrangement@paragraph	<u>1</u>
\Xarrangement@threecol	<u>1</u>
\Xarrangement@twocol	<u>1</u>
\Xbeforeinserting	53
\Xbeforelemmaseparator	50
\Xbeforenotes	56
\Xbeforenumber	49
\Xbeforesymlinenum	49
\Xbhookgroup	55
\Xbhooknote	53
\Xboxlinenum	49
\Xboxlinenumalign	50
\Xboxsymlinenum	50
\Xcolalign	54
\xedindex	<u>1</u>
\xedlabel	<u>1</u>

\xeditext	1
\Xendafterlemmaseparator	51
\Xendafternote	57
\Xendafterpagenumber	46
\Xendaftersymlinenum	49
\Xendaftrenumber	49
\Xendahookinplaceofnumber	53
\Xendahooklinenum	53
\Xendbeforelemmaseparator	51
\Xendbeforenumber	49
\Xendbeforepagenumber	46
\Xendbeforesymlinenum	49
\Xendbhookinplaceofnumber	53
\Xendbhooklinenum	53
\Xendbhooknote	53
\Xendboxendlinenumalign	50
\Xendboxlinenum	50
\Xendboxlinenumalign	50
\Xendboxstartlinenumalign	50
\Xendboxsymlinenum	50
\Xendhangindent	53
\Xendinplaceoflemmaseparator	51
\Xendinplaceofnumber	49
\Xendinplaceofpagenumber	46
\Xendlemmadisablefontselection	52
\Xendlemmafont	52
\Xendlemmaseparator	51
\Xendlinenumannotationonlyfirst	48
\Xendlinenumannotationonlyfirstintwo	48
\Xendlinenumannotationposition	27
\Xendlineprefixmore	46
\Xendlineprefixsingle	46
\Xendlinerangeseparator	46
\Xendmorethantwolines	47
\Xendnoidenticallinenumannotation	28
\Xendnolinenum	48
\Xendnolinenumifannotation	48
\Xendnonumber	47
\Xendnotefontsize	52
\Xendnotenumfont	51
\Xendnumberonlyfirstinline	45
\Xendnumberonlyfirstintwolines	45
\Xendpagenumberonlyfirst	45
\Xendparagraph	57
\Xendsep	57
\Xendstorelineinfo	1
\Xendsublinesep	48
\Xendsymlinenum	45
\Xendsymlinenumannotation	48
\Xendsympagenum	46

\Xendtwolines	47
\Xendtwolinesbutnotmore	47
\Xendtxtbeforenotes	55
\Xendwrapcontent	52
\xflagref	<u>1</u>
\Xgroupbyline	55
\Xgroupbylineseparetwolines	55
\Xhangindent	53
\Xhsizethreecol	54
\Xhsizetwocol	54
\Xinnotemark	71
\Xinplaceoflemmaseparator	51
\Xinplaceofnumber	49
\Xinsertparafootsep	<u>1</u>
\Xledsetnormalparstuff	<u>1</u>
\xleft@appenditem	<u>1</u>
\Xlemmadisablefontselection	51
\Xlemmafont	52
\Xlemmaseparator	50
\Xlinenumannotationonlyfirst	48
\Xlinenumannotationonlyfirstintwo	48
\Xlinenumannotationposition	27
\Xlinenumannotationposition@side	<u>1</u>
\Xlinenumannotationpositionside	27
\Xlinrangeseparator	46
\xlineref	<u>1</u> , 64
\Xmaxhnotes	56
\Xmorethantwolines	46
\Xnoidenticallinenumannotation	28
\Xnolemmaseparator	<u>1</u> , 51
\Xnolinenum	48
\Xnolinenumifannotation	48
\Xnonbreakableafternumber	49
\Xnonumber	47
\Xnotefontsize	52
\Xnotenumfont	51
\Xnoteswidthliketwocolumns	57
\Xnumberonlyfirstinline	45
\Xnumberonlyfirstintwolines	45
\Xonlypstart	47
\Xpagelinesep	49
\xpageref	<u>1</u> , 64
\Xparafootsep	54
\Xparindent	52
\Xprenotes	<u>1</u> , 56
\Xprenotes@	<u>1</u>
\Xpstart	47
\Xpstarteverytime	47
\Xpstartonlyfirst	47
\xpstartref	<u>1</u> , 64

\Xpstartseparator	47
\XR@test	<u>1</u>
\XR@test@mac	<u>1</u>
\XR@test@mac@test	<u>1</u>
\Xragged	55
\xright@appenditem	<u>1</u>
\Xrigidbalance	<u>1</u>
\Xsethangindent	<u>1</u>
\Xsetparindent	<u>1</u>
\Xstanza	47
\Xstanzaonlyfirst	47
\Xstanzaseparator	47
\Xstorelineinfo	<u>1</u>
\xsublineref	<u>1</u> , 64
\Xsublinesep	23, 48
\Xsublinesep side	23
\Xsymlinenum	45
\Xsymlinenumannotation	48
\Xtoendnotes	32
\Xtwolines	46
\Xtwolinesonlyinsamepage	47
\Xtxtbeforenotes	55
\Xtxtbeforenotesonlyonce	55
\Xtxtbeforenumber	46
\Xunvxh	<u>1</u>
\Xwidth	57
\Xwrapcontent	52
\Xwrapendlemma	52
\Xwraplemma	52
\Xwraplinenumannotation@ref	<u>1</u>
\Xwraplinenumannotation@side	<u>1</u>
\xxref	<u>1</u> , 65
Z	
\zz@@@	<u>1</u>
\zz@@@@	<u>1</u>

Change History

v0.1.0.	
General: First public release	1
v0.2.0.	
\ifl@dmemoir: Added \ifl@dmemoir for memoir class having been used	87
\morenoexpands: Added \l@dtabnoexpands to \no@expands	142
\reledmac@error: Added \eledmac@error and replaced error messages	88
General: Added tabmac code, and extended indexing	1
v0.2.1.	
\@lab: Removed page setting from \@lab	304
\edlabel: Tweaked \edlabel to get correct page numbers	301
\l@ddodoreintrafeet: Renamed \dodoreintrafeet to \l@ddodoreintrafeet	294
\l@ddoxtrafeet: Renamed \doxtrafeet to \l@ddoxtrafeet	293
\morenoexpands: Removed some \lets from \no@expands. These were in edmac but Peter Wilson feels that they should not have been as they disabled page/line refs in a footnotes	142
General: Added text about normal labeling	66
Bug fixes and match with mempatch v1.8	1
Major changes to insert code when memoir is loaded	296
v0.2.2.	
\footfudgefiddle: Added \footfudgefiddle	198
\next@line@list@stuff: Added initial write of page number in \line@list@stuff	133
\para@footsetup: Added \footfudgefiddle to \para@footsetup	198
\para@footsetupX: Added \footfudgefiddle to \para@footsetupX	244
General: Improved paragraph footnotes	1
New Dekker example	1
Used \providecommand for \@gobblethree to avoid clash with the amsfonts package	95
v0.3.0.	
\@lab: Replaced \the\line@num by \linenumr@p\line@num in \@lab, and similar for sub-lines	304
\@n@reg: Added a bunch of code to \@n@ for handling \setlinenum	119
\ledlinenum: Added \linenumr@p and \sublinenumr@p to \leftlinenum and \rightlinenum	110
\linenumberlist: Added \linenumberlist mechanism	96
\printendlines: Added \linenumr@p and \sublinenumr@p to \printendlines	264
\printlines: Added \linenumr@p and \sublinenumr@p to \printlines	226
\sublinenumr@p: Added \linenumberstyle and \sublinenumberstyle	109
General: Includes edstanza and more	1
v0.3.1.	
General: Not released. Added remarks about the parallel package	1
v0.4.0.	
\@iiiminipage: Modified kernel \@iiiminipage and \endminipage to cater for critical footnotes	328
\Xarrangement@normal: Added minpage footnote setup to \footnormal	192
\edtext: Added \showlemma to \edtext	143
\l@dfeetendmini: Added \l@dfeetbeginmini, \l@dfeetendmini and all their supporting code	326
\mpnormalfootgroup: Added \mpnormalfootgroup	196

\mpnormalvfootnote: Added \mpnormalvfootnote	194
\showlemma: Added \showlemma	96
General: Added final/draft options	84
Added ledgroup environment	329
Added ledgroupsize environment	330
Added minipage, etc., support	1
v0.4.1.	
\doXfeet: Changed \doXfeet code for easier extensions	293
\edindex: Let eledmac take advantage of memoir's indexing	335
\printXnotes: Added \opXfeet	294
General: Added code for changing \doclearpage	297
Not released. Minor editorial improvements and code tweaks	1
Only change \@footnotetext and \@footnotemark if memoir not used	229
v0.5.0.	
\@footnotetext: Enabled regular \footnote in numbered text	230
\@xympar: Eliminated \marginpar disturbance	318
General: Added left and right sidenotes	319
Added sidenotes, familiar footnotes in numbered text	1
v0.5.1.	
\affixline@num: Changed \affixline@num to cater for sidenotes	177
\l@getsidenote@margin: Added \sidenotemargin and \sidenote@margin	319
General: Added moveable sidenote	319
Fixed right line numbers killed in v0.5	1
Only change \hsize in ledgroupsize environment otherwise page number can be in wrong place	330
v0.6.0.	
\@lopR: Added \@pend, \@pendR, \@lopL and \@lopR in anticipation of parallel processing	122
\@nl@reg: Extended \@nl to include the page number	119
\get@thisfootnote: Changed \l@dbfnote and \v1@dbfnote as originals could give incorrect markers in the footnotes	230
\set@this@page: Extended \new@line to output page numbers	134
General: Fixed long paragraphs looping	1
Fixed minor typos	1
Prepared for eledpar package	1
v0.7.0.	
\@nl@reg: Added \@nl@reg	119
\@ref@reg: Added \@ref@reg	129
\affixline@num: Added skipnumering to \affixline@num	177
\do@actions@fixedcode: Added \do@actions@fixedcode	172
\do@actions@next: Added number skipping to \do@actions	171
\do@insidelinehook: Added \do@linehook for use in \do@line	168
\endnumbering: Changed \endnumbering for eledpar	100
\fx@l@cks: Added \ch@cksub@l@ck, \ch@ck@l@ck and \fx@l@cks	180
\footsplitskips: Added \footsplitskips for use in many footnote styles	191
\get@linelistfile: Added \get@linelistfile	118
\initnumbering@reg: Added \initnumbering@reg	99
\l@advance@parledgroup@beforenormalnotes: Added \l@dunboxmpfoot containing some common code	329
\l@dcsnotetext@r: Added \l@emptyd@ta	169

\l@dgetline@margin: Added \l@dgetline@margin	106
\l@dgetlock@disp: Added \l@dgetlock@disp	108
\l@dgetsidenote@margin: Added \l@dgetsidenote@margin	319
\l@dnumpstartsL: Added \l@dnumpstartsL, \ifl@dpairing and \ifpst@rted for/from eledpar	96
\l@drsn@te: Added \l@dlsn@te and \l@drsn@te for use in \do@line	169
\l@dzeropenalties: Added \l@dzeropenalties	162
\ledlinenum: Added \ledlinenum for use by \leftlinenum and \rightlinenum	110
\list@clearing@reg: Added \list@clearing@reg	118
\n@num: Added \n@num	127
\next@line@list@stuff: Deleted \page@start from \line@list@stuff	133
\normalbfnoteX: Removed extraneous space from \normalbfnoteX	236
\pausenumbering@page@num: Changed \resumenumbering for eledpar	102
\setprintlines: Added \setprintlines for use by \printlines	220
\skipnumbering: Added \skipnumbering and supports	139
\sublinenumincrement: Added \firstlinenum, \linenumincrement, \firstsublinenum and \linenumincrement	107
\sublinenumr@p: Using \linenumrep instead of \linenumr@p	109
Using \sublinenumrep instead of \sublinenumr@p	109
\vnumfootnoteX: Removed extraneous space from \vnumfootnoteX	238
General: Added \setprintendlines for use by \printendlines	260
eledmac having been available for 2 years, deleted the commented out original edmac texts	1
Maïeul Rouquette new maintainer	1
Made macros of all messages	88
Replaced all \interAfootnotelinepenalty, etc., by just \interfootnotelinepenalty	1
Tidying up for eledpar and ledarab packages	1
v0.8.0.	
General: Bug on endnotes fixed: in a // text, all endnotes will print and be placed at the ends of columns ()	1
v0.8.1.	
General: Bug on \edtext ; \critex ; \lemma fixed: we can now us non-switching commands	1
v0.9.0.	
General: No more ledpatch. All patches are now in the main file.	1
v0.9.1.	
General: Fix some bugs linked to integrating ledpatch on the main file.	1
v0.10.0.	
General: Corrections to \section and other titles in numbered sections	1
v0.11.0.	
General: Makes it possible to add a symbol on each verse's hanging, as in French typography. Redefines the command \hangingsymbol to define the character.	1
v0.12.0.	
\l@dnumpstartsL: Added \ifledRcol and \ifnumberingR for/from eledpar	96
General: For compatibility with eledpar, possibility to use \autopar on the right side.	1
Possibility to number \pstart.	20
Possibility to number the pstart with the commands \numberpstarttrue.	1
v0.12.1.	
General: Do not number \pstarts of stanza.	1

The numbering of <code>\pstarts</code> restarts on each <code>\beginnumbering</code> .	1
v0.13.0.	
<code>\managestanza@modulo</code> : New <code>stanzaindentsrepetition</code> counter to repeat stanza indents every n verses.	345
General: New <code>stanzaindentsrepetition</code> counter to repeat stanza indents every n verses.	59
New <code>stanzaindentsrepetition</code> counter: to repeat stanza indents every n verses.	1
v0.13.1.	
General: <code>\thepstartL</code> and <code>\thepstartR</code> use now <code>\bfseries</code> and not <code>\bf</code> , which is deprecated and makes conflicts with <code>memoir</code> class.	1
v0.14.0.	
<code>\edlabel</code> : Tweaked <code>\edlabel</code> to get correct line number if the command is first element of a paragraph.	301
General: Tweaked <code>\edlabel</code> to get correct line number if the command is first element of a paragraph.	1
v0.15.0.	
<code>\affixline@num</code> : Line numbering can be disabled.	177
<code>\ifinserthangingsymbol</code> : New management of <code>hangingsymbol</code> insertion, preventing undesirable insertions.	344
<code>\printlines</code> : Line numbering can be reset at each <code>pstart</code> .	225
General: Line numbering can be reset at each <code>pstart</code> .	104
Possibility to print <code>\pstart</code> number at the sides of the text.	20
v0.17.0.	
<code>\ifinserthangingsymbol</code> : New new management of <code>hangingsymbol</code> insertion, preventing undesirable insertions.	344
v1.0.0.	
<code>\morenoexpands</code> : Change to be compatible with new features	142
General: <code>\lemma</code> can contain commands.	33
Debug in lineation command	22
New generic commands to customize footnote display.	43, 282
Options <code>nonum</code> and <code>nosep</code> in <code>\Xfootnote</code> .	30
Options of <code>\Xfootnotes</code> .	188
Possibility to have commands in sidenotes.	69
Some compatibility break with <code>eledmac</code> . Change of name: <code>eledmac</code> .	1
v1.0.1.	
General: Correction on <code>\Xnumberonlyfirstinline</code> with lineation by <code>pstart</code> or by page.	45
v1.1.0.	
<code>\Xprenotes</code> : New skip <code>\Xprenotes@</code>	252
<code>\settoggle@series</code> : <code>\settoggle@series</code> switch the global value of the toggle, not only the local value.	283
General: Add <code>\labelpstarttrue</code> .	20
Add <code>\Xnumberonlyfirstintwolines</code>	45
Add <code>\Xpstart</code> and <code>\Xonlypstart</code>	47
New hook to add arbitrary code at the beginning of the notes	53
New options for block of notes.	55
New package option: <code>parapparatus</code> .	1
New tools to change order of series	281
Sectioning commands.	76
v1.2.0.	
<code>\Xprenotes</code> : Debug in familiar footnotes (bug introduced by v1.1).	252
<code>\endquote</code> : Compatibility of <code>\ledchapter</code> with the <i>memoir</i> class.	385

v1.3.0.		
\endquote:	<i>Quotation</i> and quote environment inside numbered sections.	385
v1.4.0.		
\edtext:	Compatibility of \edtext with the right-to-left direction (with Polyglossia).	143
\ledsetnormalparstuffX:	Direction of footnotes with polyglossia.	249
\newseries@:	Remembers the language of the lemma, in order to create a correct direction for the footnote separator.	271
\rbracket:	Switch the right bracket to a left bracket when the lemma is RTL (needs polyglossia or LuaTeX).	213
General:	Compatibility with LuaTeX of RTL notes.	1
v1.4.1.		
\affixside@note:	Remove spurious spaces.	325
\endquote:	New option <i>noquotation</i>	385
\get@thisfootnote:	Compatibility of standard footnotes with eledmac when these footnotes contain any commands.	230
\labelrefsparsesubline:	Fix a bug with \edlabel.	303
v1.4.2.		
General:	Debug with some special classes.	1
v1.4.3.		
General:	Add \Xnonbreakableafternumber.	49
Spurious space after familiar footnotes.	1
v1.4.4.		
General:	Label inside familiar footnotes.	1
v1.4.5.		
General:	Bug with komasscript + eledpar + chapter.	1
v1.4.6.		
General:	Bug with memoir class introduced by 1.4.5.	1
v1.4.7.		
\endquote:	Compatibility of sectioning commands with \autopar.	385
v1.4.8.		
General:	Corrects a bug with parallel texts introduced by 1.1.	1
v1.4.9.		
\normalbfnoteX:	Allow to redefine \thefootnoteX with alph when some packages are loaded.	236
v1.5.0.		
\do@insidelinehook:	Added \do@insidelinehook for use in \do@line	168
\edindex:	Compatibility with imakeidx package, and possibility to use multiple index with \edindex.	335
General:	Correct indexing when the call is made in critical notes.	331
v1.5.1.		
\managestanza@modulo:	Correct stanzaindentsrepetition counter	345
\normalvfootnoteX:	Fix a bug with normal familiar footnotes when mixing RTL and LTR text.	233
v1.6.0.		
\newverse:	Add \falseverse macro.	349
v1.6.1.		
\AtStartEveryPstart:	Spurious space in \pstart.	158
\ifinserthangingsymbol:	Hang verse is now not automatically flush right.	344
\l@dunhbox@line:	Move the call to \inserthangingsymbol to allow use \hfill inside.	164

\pend: Spurious space in \pend.	160
General: Corrects a false hanging verse when a verse is exactly the length of a line.	1
v1.7.0.	
General: New features for managing page breaks.	78
v1.8.0.	
\endquote: Correction of sectioning commands in parallel texts.	385
\get@index@command: Debug \get@index@command and compatibility with hyperref package.	334
\newhookcommand@series@reload: Debug \beforenotesX and \maxnotesX which did not work.	286
\prevpage@num: Correct \parafootsep when using with ledgroup.	203
General: Compatibility with parledgroup option of eledpar package.	1
If imakeidx and hyperref are loaded, adds hyperref in the index.	331
v1.8.1.	
General: Debug endnotes when more than one series is used (change the position where tools for endnotes are defined).	254
v1.8.2.	
General: Debug compatibility problem with hebrew option of babel package.	1
v1.8.3.	
General: Fix spurious spaces added by v1.7.0.	1
v1.8.5.	
General: Debug indexing in right column, with eledpar.	331
v1.9.0.	
\l@ddoxtrafeet: Add \fnpos to choice the order of footnotes.	293
\l@dfeetendmini: Add \mpfnpos to choice the order of footnotes in minipage / ledgroup.	326
v1.10.0.	
\endquote: Correction of sectioning commands in parallel texts.	385
General: Add \pstartref and \xpstartref to refer to a pstart number (extension of \edlabel).	1
v1.10.1.	
General: Compatibility with cleveref.	1
v1.10.2.	
General: Compatibility of stanza with v1.8a of babel-greek.	1
v1.10.3.	
General: Debug of cross-referencing.	1
v1.10.4.	
General: Debug of critical notes in edtabular environment.	1
v1.10.5.	
General: Debug of \pausenumbering.	1
Debug of \xxref.	1
v1.10.6.	
General: Debug of interaction between \autopar and \pausenumbering.	1
v1.11.0.	
General: Add hooks to disable the font selection for lemma in footnote.	51
v1.11.1.	
General: Correct a bug when a critical note starts with plus or minus.	1
v1.12.0.	
\@nl@reg: To ensure compatibility with \musixtex, \@l becomes \@1. Consequently, \@1@reg becomes \@nl@reg.	119

\AtStartEveryPstart: New optional argument for \pstart, to execute code before it.	158
\edindex: Use correctly default index when imakeidx is loaded.	335
\endquote: \ledxxx sectioning commands are deprecated and replaced by \eledxxx commands.	385
\initnumbering@reg: \beginnumbering is defined only on eledmac, not on eledpar.	99
\l@dgetsidenote@margin: \sidenotemargin is now directly defined in eledmac to be able to manage eledpar.	319
\l@disnote: \l@dlsnote, \l@drsnote and \l@dcnote defined only one time, in eledmac, including needs for eledpar case.	320
\l@dnumbstartsL: Add \ifledRcol@ for eledpar	96
\l@dunhbox@line: \do@line is split in more little commands.	165
\newhookcommand@series@reload: Debug \beforenotesX and \maxhnotesX which did not work when called after \footparagraphX.	286
Debug \Xbeforenotes and \Xmaxhnotes which did not work when called after \footparagraph.	286
\pend: New optional argument for \pend, to execute code after it.	160
\stanza: &can have an optional argument: content to be printed after.	349
\Stanza can have an optional argument: content to be printed before.	349
Add \newverse macro, \falseverse deprecated.	349
General: Add \ledinnernote and \ledouternote commands.	69
Add \Xendparagraph and related settings.	57
Add hyperlink to crossref (needs hyperref package).	64
Compatibility with musixtex.	1
Debug eledmac sectioning command after using \resumenumbering.	1
Ensure that imakeidx is loaded <i>before</i> eledmac	331
New hooks: \Xafterrule and \afterruleX	56
New options for ragged-paragraph notes	55
New sectioning commands.	76
Optional arguments for \pstart and \pend.	19
v1.12.1.	
\wrap@edcrossref: Fix spurious spaces.	307
v1.12.2.	
\l@dunhbox@line: Fix a bug with critical notes at the tops of pages (added by v12.0.0)	164
v1.12.3.	
\flag@end: \flag@start and \flag@end are now defined only one time for eledmac and eledpar	135
\flag@start send a error message when a \edtext is done without insert (note)	135
\reledmac@error: Replaced error messages	88
General: Add macros for new messages since v0.7	88
Correct bug with side and familiar notes in tabular environments.	1
Debug \eledxxx with some paper size	1
Debug \ledinnernote and \ledouternote commands in the top of pages.	69
Debug left and right notes (bugs added by 1.12.0)	1
Underline lemma in \eledxxx when using draft mode.	1
v1.12.4.	
General: Debug spurious page breaks before \chapter (bug added in 1.12.0)	1
v1.12.5.	
\@edindex@hyperref: Debug \edindex when hyperref is not loaded	337
\@ssect: Debug \eledchapter in parallel with memoir	388
\doinsidelinehook: Added \dolinehook and \doinsidelinehook	168

\endnumbering: Allow to mix parallel columns and normal text when using	
\pausenumbering	100
\l@dgobbleoptarg: \l@dgobblearg becomes \l@dgobbeloptyarg	368
\l@drestoreforedtext: Debug optional arguments of \Xfootnote in tabular context	369
\pausenumbering@page@num: Debug \resumenumbering	102
v1.12.7.	
\wrap@edcrossref: \wrap@edcrossref is now robust	307
v1.12.8.	
\flag@end: \flag@start do not send a error message when a \edtext is done without insert (note) but have a endnote	135
v1.13.0.	
\newhooktoggle@series@reload: Add \newhookcommand@toggle@reload	285
\para@footsetupX: In \para@footsetupX, use \columnwidth instead of \hsize	244
\settoggle@series: \settoggle@series can take an optional arguments to reload series setup.	283
General: Add \Xnoteswidthliketwocolumns and \noteswidthliketwocolumnsX	57
Added widthliketwocolumns option	84
v1.13.1.	
\ifat@every@pstart@star@: Add \l@dzeropenalties in \pstart	158
General: Coming back of page and line breaking penalties's management, deleted by error in v0.17.	1
Debug quotation environment inside of a \pstart preceded by a sectioning command.	1
v1.13.2.	
\l@dnumpstartsL: Add \ifl@dpaging for eledpar	96
General: Fix a bug with normal footnotes, added by v1.13.0.	1
v1.13.3.	
General: Fix extra spaces with paragraphed footnotes, added by v1.13.0.	1
v1.13.4.	
General: Fix a bug with index when memoir class is used without hyperref	1
v1.14.0.	
\edindex: Let eledmac take advantage of imakeidx even when memoir class is used	335
General: Debug spurious characters before endnotes.	254
Delete previous override of \l@d@@wrindexhyp at the beginning of a document when hyperref is not loaded.	339
Move gobbling command	95
Provide \@gobblefour	95
v1.14.1.	
\@ssect: Debug sectioning commands when using both handout and hyperref package.	391
v1.14.2.	
\@ssect: Debug \edtext after starred sectioning commands when using memoir class.	388
v1.15.0.	
\@edtext@level: New boolean \if@edtext@.	143
\arrangementX@paragraph: Correct bug with paragraphed familiar footnotes setting.	243
\endsub: Restore subline feature (disabled by mistake in v1.8.0).	137
\if@lemmacommand@: New boolean \iflemmacommand@.	149
General: Fix a bug with footnotes layout when using some options of the geometry package (bug add by v1.13.0).	1
New commands \AtEveryPstart and \AtEveryPend.	20
New tools to prevent ambiguous references in lemma	34

v1.15.1.	
\next@line@list@stuff:	Revert modification of 1.5.2 which makes bug with numbering. Leave vertical mode to solve spurious space before minipage.
	133
v1.16.0.	
General:	\edtext is now defined only in eledmac, not in eledpar. Debug wrong numbering when using \sameword + eledpar + \tag command.
	143
Compatibility of standard footnotes with some biblatex styles.
	1
New \stanzaindent command.
	1
v1.16.1.	
\xlineref:	\lineref is not defined if defined by some other package, like lineno. Eledmac provides \edlineref instead.
	307
v1.17.0.	
\edtext:	Error message when calling \edtext outside of a numbered paragraph. . . .
	143
v1.18.0.	
\@edindex@hyperref:	Fix spurious space with \edindex when using imakeidx/indextools + hyperref.
	337
\edlabel:	\edlabel is now defined only one time for both eledmac and eledpar
	301
\l@d@section:	Option parapparatus works for endnotes.
	255
\l@dnumpstartsl:	Add \ifl@dprintingpages and \@dprintingcolumns for eledpar
	96
\print@line:	Compatibility with Lua \TeX RTL languages.
	165
\printlinefootnote:	Code refactoring in \printlinefootnote: the printing of the numbers are factorized in \printlinefootnotearea
	215
\printpstart:	Debug \Xpstart with parallel pages and columns (eledpar)
	213
General:	Add \Xpstarteverytime
	47
Compatibility with Lua \TeX RTL languages.
	1
Debug \Xonlypstart when using \Xnumberonlyfirstinline and the current line number differs from the previous.
	47
v1.19.0.	
\footplitskips:	\footplitskips doesn't set \floatingpenalty to \@MM when processing parallel pages.
	191
\xxref:	\xxref works also with right side numbers, when \@Rlineflag is not empty. . . .
	310
General:	\Xmaxhnotes and \maxhnotesX work now for both two-columns and three-columns setting.
	1
Compatibility with eledpar v1.13.0.
	1
v1.19.1.	
General:	Call \correct@footinsX@box and \correct@Xfootins@box directly in \print@notesX@forpages and \print@Xnotes@forpages, that is in eledpar. . . .
	1
v1.20.0.	
\printlines:	Added \ifl@d@Xmorethantwolines and \ifl@d@Xmorethantwolines to \printlines
	226
\stanza:	& and \& can be preceded by spaces.
	349
\xxref:	Debug \xxref when not loading eledpar (Fix a bug added in 1.19.0).
	310
General:	Add \Xendboxlinenum
	50
Add \Xtwolines and \Xmorethantwolines hooks
	46
Add series option.
	1
Correct \Xinplaceofnumber hook.
	1
Explicit error message when calling \Xfootnote outside of \edtext.
	1
Fix a bug with line number typesetting direction when using \eledsection and similar commands for RTL texts with Lua \TeX
	1

Fix issues with RTL text in notes when using Lua \TeX .	1
Options fulllines in \backslash Xfootnote.	30
The \backslash newifs are not followed by boolean values set to false, because it is the \TeX default setting.	1
v1.21.0.	
\backslash @edindex@hyperref: Look at the hyperindex option of hyperref before inserting hyperref	337
\backslash l@d@section: \backslash endnotes take five arguments.	255
\backslash ledinnotemark: Add \backslash ledinnotemark.	334
\backslash ledsetnormalparstuffX: \backslash ledsetnormalparstuff is deprecated and becomes \backslash ledsetnormalparstuffX and \backslash Xledsetnormalparstuff.	249
\backslash n@num: \backslash n@num@ref deleted	127
\backslash n@num defined only one time for both Eledmac and Eledpar	127
\backslash newhookcommand@series: \backslash newhookcommand@series can take an optional argument.	284
\backslash newhooktoggle@series: \backslash newhooktoggle@series can take an optional argument.	285
\backslash print@footnoterule: Code refactoring: the spaces after the footnote rules are directly managed in \backslash print@Xfootnoterule and \backslash print@footnoterule	251
\backslash seriesatend: Fix spurious space in \backslash seriesatend	281
\backslash skipnumbering: \backslash skipnumbering defined only one time for both Eledmac and Eledpar.	139
Correct \backslash skipnumbering for stanza.	139
Delete \backslash skipnumbering@reg.	139
General: \backslash AtEveryPstart and \backslash AtEveryPend are now compatible with \backslash autopar	1
\backslash Xafterrule and \backslash afterruleX features no longer create problems of overflowing at the bottom of the page.	1
\backslash chapter inside optional argument of \backslash pstart works when typesetting parallel pages	1
\backslash preXnotes and \backslash prenotesX features no longer create problems of overflowing at the bottom of the page.	1
\backslash seriesatbegin and \backslash seriesatbegin more efficient	281
Add \backslash applabel and related	66
Add \backslash beforenotesX and \backslash Xbeforenotes features for notes set in two and three column.	1
Add \backslash hidenummering	25
Add \backslash Xcolalign and \backslash colalignX hooks	54
Add \backslash Xendtwolines, \backslash Xendmoreethantwolines, \backslash Xendtwolinesbutnotmore and \backslash Xendtwolinesonlyinsamepage.	47
Add \backslash Xparindent and \backslash hangindentX	52
Add \backslash Xtwolinesbutnotmore and \backslash Xtwolinesonlyinsamepage.	1
Add nocritical, noend, nofamiliar and noledgroup options.	1
Add noeledsec package option	1
Debug \backslash beforenotesX \backslash maxhnotesX \backslash noteswidthliketwocolumnsX and \backslash afterruleX with footnotes set in two and three columns.	1
Fix a bug when a \backslash Xfootnote follows a \backslash Xendnote in the second argument of \backslash edtext (bug added in eledmac 1.0.0).	1
Fix a bug with \backslash maxhnotesX when using \backslash foottwocolX or \backslash foottwocolX.	1
Fix a bug with space between columns with notes in two columns (bug added in v1.13.0).	1

Fix spurious space after first page number in <code>\doendnotes</code> . <code>oldprintnpnumspace</code> option allows to come back to previous setting	1
<code>parapparatus</code> option works now with familiar footnotes.	1
Provide <code>\@gobblefive</code>	95
v1.22.0.	
<code>\ledinnote</code> : <code>\ledinnote</code> takes a first optional argument, which is the label for hyperlinks.	334
General: Add <code>\doendnotesbysection</code> command.	31
Add option for lemma separator inside endnotes	51
Adds hyperlink for references to notes in indices.	1
Fix conflict between <code>noend</code> package option and <code>edtabularx</code> environments	1
Provides support for <code>xindy</code>	1
Standardize endnotes handbook.	31
When using <code>hyperref</code> package, internal links in index or with <code>\edlineref</code> are now targeted to the top and not longer to the bottom of the lines they refer to.	1
v1.22.1.	
<code>\prevpage@num</code> : Correct double symbol when using both <code>\parafootsep</code> and <code>\Xsymlinenum</code>	203
General: Fix a bug (added on v1.22.0) with <code>\Xinplaceofnumber</code> hook.	1
v1.23.0.	
<code>\@edtext@level</code> : The boolean <code>\if@edtext@</code> becomes the counter <code>\edtext@level</code>	143
<code>\Serefwithpage</code> : Debug <code>\Xendtwolines</code> , <code>\Xendmoreethantwolines</code> , <code>\Xendtwolinesbutnotmore</code> and <code>\Xendtwolinesonlyinsamepage</code> when using <code>\apprefwithpage</code>	314
<code>\lemma</code> : Fix spurious space after <code>\lemma</code> command	148
<code>\newsseries@</code> : Prevent spurious spaces when <code>\Afootnote</code> and similar commands are followed by spaces (bug added on 1.0.0).	271
<code>\sameword</code> : In order to allow use of <code>\sameword</code> with <code>inputenc</code> , we detokenize its mandatory argument before using it in control sequence names.	153
General: Add <code>\Xboxlinenumalign</code> and <code>\Xendboxlinenumalign</code>	50
Add <code>\Xboxstartlinenum</code> , <code>\Xendboxstartlinenum</code> , <code>\Xboxendlinenum</code> , <code>\Xendboxendlinenum</code>	50
Allow use of <code>\sameword</code> with <code>inputenc</code> managing of UTF-8.	1
Compatibility between <code>nofamiliar/nocriticals</code> option and <code>minipage/ledgroup</code>	1
Error message when using <code>\beginnumbering</code> ... <code>\endnumbering</code> without <code>\pstart</code>	1
Fix a bug with <code>\sameword</code> when the lemma overlaps multiple line.	34
Fix a bug with <code>\sameword</code> when the same lemma is used for multiple notes or for nested <code>\edtexts</code>	34
Fix a bug with <code>\skipnumbering</code> called immediately after a <code>\pstart</code>	1
Fix error of <code>\iftrue</code> not closed.	1
Fix spurious space with <code>\skipnumbering</code> (bug added on v1.21.0).	1
New tools to ensure the line-list file uses the right version of commands when upgrading the <code>eledmac</code> version.	1
Optional argument of <code>\sameword</code> can be a comma-separated list of <code>\edtext</code> depth.	34
v1.23.1.	
General: Fix a bug with <code>\lemma</code> command in the right side.	1
v1.23.2.	
General: Compatibility with \LaTeX 's release 2015.	1

v1.24.0.	
General: We can reinitialize <code>\AtEveryPstart</code> and <code>\AtEveryPend</code> providing to it an empty argument.	1
v1.24.1.	
General: <code>\lemma</code> is disabled when using <code>nocritical</code> option.	1
v1.24.2.	
General: Fix incompatibility between <code>nofamiliar</code> option and <code>memoir</code> package.	1
v1.24.3.	
General: Restore marginal numbers and notes with sectioning command (bug introduced in v1.21.0)	1
v1.24.4.	
General: Fix spurious space with <code>\edindex</code> when using <code>xindy+hyperref</code> option.	1
v1.24.5.	
General: Fix a bug of indent, when a added in 1.1.0, when a <code>\beginnumbering</code> immediately follow a sectioning command.	1
v2.0.0.	
<code>\@iiiminipage</code> : Patch <code>\@iiiminipage</code> instead of redefining it.	328
<code>\@xympar</code> : Patching <code>\@xympar</code> instead of redefining it	318
<code>\endminipage</code> : Patch <code>\endminipage</code> instead of redefining it.	328
<code>\initnumbering@quote</code> : <code>\initnumbering@sectcmd</code> becomes <code>\initnumbering@quote</code>	385
<code>\l@advance@parledgroup@beforenormalnotes</code> : Some code of <code>\l@dumboxmpfoot</code> moved to <code>\l@advance@parledegroupp@beforenormalnotes</code>	329
<code>\newseries@</code> : One endnotes file by series.	277
General: <code>\@makecol</code> , <code>\@reinserts</code> and <code>\@doclearpage</code> are patched instead of begin redefined	296
<code>\doxtrafeeti</code> becomes <code>\Xdo@feet</code> ; <code>\doxtrafeetii</code> becomes <code>\do@Xfeet</code> ; <code>\@opxtrafeeti</code> becomes <code>\@opfeetX</code> ; <code>\doreinxtrafeetii</code> becomes <code>\X@doreinfeet</code> ; <code>\doreinxtrafeeti</code> becomes <code>\@doreinfeetX</code>	296
Add <code>\Xendinplaceofnumber</code> hook.	1
Add <code>\Xendnonumber</code> hook.	1
Add <code>nonum</code> option for endnotes.	1
Fix a bug when printing only one series of endnotes, but wanted to keep endnotes for other series.	1
In order to have a more consistent name's convention, many names has been changed.	1
Many \TeX 's output macros are now patched and not override.	1
Package's name becomes <code>reledmac</code>	1
Patch <code>\@footnotemark</code> instead of redefine it	229
Suppress indexing command specific to <code>memoir</code>	335
v2.0.1.	
General: Fix a bug in <code>eledmac-compat</code> option	1
Fix incompatibility between optional argument of <code>\pstart</code> and <code>\numberpstarttrue</code>	1
v2.1.0.	
General: Fix a bug with <code>\advanceline</code> at the beginning of a <code>\pstart</code>	1
Fix a bug with <code>\chapter</code> in optional argument of <code>\pstart</code> in parallel typesetting with <code>scrbook</code>	1
Fix a bug with <code>\eledchapter</code> in parallel typesetting with <code>scrbook</code>	1
Fix a bug with <code>\setline</code> at the beginning of a <code>\pstart</code>	1
Fix spacing bug with <code>\Xhooknote</code> and <code>\hooknoteX</code> when using them to insert text and not to execute code.	1

New tools to number stanzas	1
v2.1.1.	
General: Fix a bug with <code>\ledpbsetting{before}</code>	1
v2.1.2.	
General: Fix a bug with lineation by <code>pstart</code> and <code>tabular</code> environments (added in 2.1.0).	1
v2.1.3.	
<code>\ledsetnormalparstuffX</code> : Replaced <code>\noindent</code> with <code>\parindent</code> set to 0pt.	249
General: <code>\Xhangindent</code> and <code>\hangindentX</code> work now with all the paragraphs in the note.	1
<code>\Xnoindent</code> and <code>\noindentX</code> work now again (broken in 2.0.0).	1
Change some internal code in order to provide compatibility with \TeX release of october 2015	1
Fix a bug which inserted double space before paragraphed familiar notes.	1
Fix a bug with <code>\edindex</code> when using not-Latin characters without UTF-8 engines	1
v2.2.0.	
General: Fix a bug with combination of <code>\onehalfspacing</code> and two columns and three columns notes typeset.	1
Fix a bug with some setting command and optimization option.	1
Fix spurious space with paragraphed critical notes when using $\text{Lua}\TeX$	1
Increase line list version number to ensure compatibility with new options of <code>reledpar</code> package.	1
New setting tools for endnotes: <code>\Xendnumberonlyfirstinline</code> , <code>\Xendnumberonlyfirstintwolines</code> , <code>\Xendsymmlinenumber</code> , <code>\Xendbeforenumber</code> , <code>\Xendafterenumber</code> , <code>\Xendbeforemsymmlinenumber</code> , <code>\Xendaftersymmlinenumber</code> , <code>\Xendboxsymmlinenumber</code> , <code>\Xendhangindent</code> , <code>\Xendbhooklinenumber</code> , <code>\Xendahooklinenumber</code> , <code>\Xendbhookinplaceofnumber</code> , <code>\Xendahookinplaceofnumber</code>	1
v2.2.1.	
General: Compatibility with TeXformat 2015/10/01.	1
v2.2.2.	
General: Fix a bug in <code>\sethangingsymbol</code>	1
Fix a bug with old version of <code>etex</code>	1
v2.3.0.	
General: Disable empty lines as paragraph in stanza.	1
Fix incompatibility of paragraphed footnotes with <code>bidi</code> v17.9 and following.	1
Warning message when using some setting commands inside <code>rightside</code> environment (deprecated behavior)	1
v2.3.1.	
General: Fix spurious space when using optional argument of <code>\stanza</code> (introduced in v2.3.0).	1
v2.4.0.	
<code>\footnoteoptions@</code> : First argument of <code>\footnoteoption@</code> is now mandatory, not optional.	188
General: <code>\Xbhooknote</code> and <code>\bhooknoteX</code> work with notes in columns.	1
Fix a bug of <code>\parindentX</code> and <code>\Xparindent</code> with two columns and three columns notes.	1
Fix a bug with <code>\sameword</code> in right side.	1
Fix spurious space in two columns and three columns notes.	1
Fix spurious space when using optional argument of <code>stanza</code> (introduced in v2.3.0).	1
New hooks: <code>\Xlinerrangeseparator</code> and <code>\Xendlinerrangeseparator</code>	46

Option <code>linrangesep</code> for critical footnotes and endnotes.	46
v2.4.1.	
General: Fix a bug with <code>\appref</code> and <code>\apprefwithpage</code> (introduced in v2.4.0).	1
Fix a bug with tabular environments when using <code>babel</code> or <code>polyglossia</code> languages that override \LaTeX <code>\roman</code> command, like Greek language.	1
Fix a bug with tabular environments when using <code>babel</code> or <code>polyglossia</code> languages that override \LaTeX <code>\roman</code> command, like Greek.	1
v2.5.0.	
<code>\Serefwithpage</code> : Debug <code>\setapprefprefixsingle</code>	314
<code>\edlabel</code> : Fix a bug when calling <code>\edlabel</code> in a footnotes of the right side	301
<code>\l@d@section</code> : <code>\endnotes</code> take six arguments.	255
<code>\printlines</code> : <code>\printlines</code> takes an eighth argument: the line flag	225
<code>\xlineref</code> : <code>\xlineref</code> does not include anymore the side flag. Use <code>\xflagref</code> to get it. Not that <code>\edlineref</code> still contains the flag.	307
General: <code>\apprefwithpage</code> and <code>\appref</code> print double quotation mark when the label was not defined.	1
<code>\apprefwithpage</code> and <code>\appref</code> work with right side crossref.	1
<code>\apprefwithpage</code> works also when <code>noend</code> option is enabled.	1
<code>\appref</code> and <code>\apprefwithpage</code> can take <code>linrangesep</code> optional argument.	1
<code>\edlabel</code> works now in \LaTeX footnote.	1
<code>\lemma</code> can be used even when the <code>nocritical</code> is enabled.	1
Compatibility with new hook and tools of <code>reledpar</code> 2.6.0.	1
Fix spurious vertical space in <code>astanza</code> environment (<code>reledpar</code>)	1
Log now states “There were undefined references” when using wrong references in <code>\edlineref</code> or <code>edpageref</code>	1
New hooks to customize page and line number appearance in endnotes.	1
New hooks: <code>\Xhookgroup</code> and <code>\hookgroupX</code>	1
New tools to easily make cross-reference to a passage defined by a start and an end line	66
v2.6.0.	
General: Adds compatibility with <code>innnote</code> and <code>notenumber</code> options of <code>indextools</code> package.	1
Fix a bug with footnote counter in <code>ledgroup</code> (added in v2.5.0).	1
Fix bug, introduced in v2.5.0, with footnote numbering in parallel typesetting when using <code>perpage</code> package.	1
v2.7.0.	
<code>\@k</code> : <code>\rigidbalance</code> is split in <code>\Xrigidbalance</code> and <code>\rigidbalanceX</code>	204
<code>\l@d@section</code> : <code>\endnotes</code> take seven arguments.	255
General: Add dash as default page range separator for <code>\SEonlypage</code>	1
Debug <code>\Serefonlypage</code> when referring to only one page.	1
Delete parenthesis after <code>\Serefonlypage</code>	1
Fix (again) bugs with footnote numbering in parallel typesetting while using <code>ledgroup</code> environments (bug added in v2.5.0).	1
Fix a bug with <code>\Serefwithpage</code>	1
Fix bugs in compatibility with <code>innote</code> and <code>notenumber</code> options of <code>indextools</code> package, when indexing outside of a <code>ledgroup</code>	1
New commands to make glossaries connected to page and linenumber with the <code>glossaries</code> package	1
New hooks: <code>\Xhsize</code> and <code>\hsizeX</code>	57
New hooks: <code>\Xlemmfont</code> and <code>\xendlemmfont</code>	52

New setting commands: <code>\setSErefonlypageprefixsingle</code> and <code>\setSErefonlypageprefixmore</code>	1
Warning for duplicate and undefined labels are parsable by latexmk	1
Warning for duplicate labels does not send any more a false line and page number	1
When using <code>hyperref</code> package, add link in familiar footnotes between the footnote marks in the text and the footnote marks in the footnote	1
When using <code>hyperref</code> package, add links for <code>\SEref</code> and related, <code>\appref</code> and related.	1
When using <code>hyperref</code> package, add links from critical footnotes and critical endnotes to the line of text they refers	1
v2.7.1.	
General: Debug <code>\Xhookgroup</code> hooks executed on columnar footnotes (moved to a larger group, to take effect).	1
v2.7.2.	
General: <code>\Xhsize</code> and <code>\hsizeX</code> become <code>\Xwidth</code> and <code>\widthX</code>	57
Fix problem of hyphenation when using <code>hyperref</code> package (added in v2.7.0).	1
v2.8.0.	
<code>\l@d@section: \Xendhangindent</code> and <code>\Xendafternote</code> can take values which are relative to the font size of the endnote.	255
General: <code>reledmac</code> cross-referencing can take advantage of <code>xr</code> package.	1
More <code>\edgls...</code> commands.	1
No indentation for paragraphed notes in <code>ledgroup</code> . Can be changed with <code>\Xparindent</code> and <code>\parindentX</code> .	1
v2.8.1.	
General: Warnings for undefined labels are really parsable by latexmk	1
v2.8.2.	
General: Fix a bug concerning indent in a paragraph immediately following a sectioning command (bug NOT fixed on <code>reledpar</code>)	1
Fix a bug with <code>\AtEveryPstart</code> added in version 2.0.0.	1
Fix a bug with vertical space after the between-sectioning command as optional argument of a <code>\pstart</code> and <code>\pstart</code> content	1
v2.9.0.	
General: Allow continuing line numbering between normal text and parallel text, using <code>\pausenumbering</code> and <code>\resumenumbering</code> and the <code>continuousnumberingwithcolumns</code> option.	1
Fix a bug when using <code>\lineneation{page}</code> and <code>\pausenumbering... \resumenumbering</code> .	1
Fix a bug with three- and two-column footnote setting (added in v2.4.0).	1
Fix spurious space inside three-column familiar footnote.	1
Write correct metadata in numbered files when using <code>\pausenumbering... \resumenumbering</code> .	1
v2.9.1.	
General: Fix a bug when notes start with plus or minus.	1
v2.9.2.	
General: Fix a bug with <code>hyperref</code> package when a lemma starts with plus or “minus” (bug introduced in v. 2.7.0).	1
v2.9.3.	
General: Fix a bug with line number position and reset added by v. 2.9.0	1

v2.10.0.	
\print@lemma: Code refactoring between \parafootfmt, \twocolfootfmt, \threecolfootfmt and \normalfootfmt.	213
General: Add \AtEveryStanza and \AtEveryStopStanza.	1
Fix a bug in \ledlsnotefontsetup and \ledrsnotefontsetup which could not handle \color command properly.	1
More specific error messages.	1
New hooks: \Xwrapcontent, \Xendwrapcontent and \wrapcontentX.	52
New hooks: \Xwraplemma and \Xendwraplemma	52
v2.10.1.	
General: Add nopenalties option.	1
Fix a bug introduced in v. 1.4: not paragraphed critical footnotes could prevent marginal line number from being displayed	1
v2.11.0.	
\do@actions@fixedcode: Add action 1010	172
General: Add new tools to produce an apparatus of manuscripts	1
Fix a bug in \Xparafootsep in parallel typesetting	1
Make \parafootsepX work	1
Prevent \Xtxtbeforenotes hook from causing notes to go beyond the bottom margin	1
v2.12.0.	
General: \preXnotes becomes \Xprenotes (naming convention)	1
Add \hidenumberingonleftpage and \hidenumberingonrightpage	1
Add \toendnotes and related.	1
Add auxdir option.	1
Fix a bug in critical and familiar footnotes when using uppercase letters with accent mark	1
Fix a bug when using \chapter in optional argument of \pstart in parallel typesetting in combination with the noeledsec option.	1
Fix a bug with \ledinnernote and \ledouternote in parallel typesetting	1
Fix a bug with familiar footnote number in optional argument of \pstart or \pend in parallel typesetting	1
Fix spurious vertical space in \chapter when used as optional argument of \pstart in parallel typesetting.	1
Make endnote compatible with \sameword mechanism	1
More accurate message to control the position of \Xfootnote and \applabel in the \LaTeX code	1
v2.13.0.	
General: Version 2.13.0 never existed.	1
v2.13.1.	
General: In critical footnotes, the right side flag is printed only if requested explicitly with \Xlineflag (bug added in v. 2.5.0).	1
v2.13.2.	
General: Fix a bug added in v. 11.2 which could make parallel typesetting not work.	1
v2.13.3.	
General: Makes \Xendafterpagenumbe affecting \Serefwithpage	1
v2.14.0.	
General: Hyperref with the line number inside critical footnotes is correct when using \xxref	1
Some internal changes for new features of reledpar.	1

v2.14.1.	
General: Fix a bug when using <code>\footnoteX</code> in the first argument of <code>\edtext</code> .	1
v2.14.1a.	
General: Fix problematic typos in the handbook.	1
v2.15.0.	
General: Add “byline” arrangement.	1
Fix <code>\Xtxtbeforenotes</code> in <code>ledgroup</code> .	1
v2.15.1.	
General: Fix <code>\edindex</code> in tabular environments.	1
v2.15.2.	
General: Fix a bug with <code>fancyhdr</code> package 3.8 and later.	1
v2.15.3.	
General: Fix a bug with <code>\section</code> in optional argument of <code>\pstart</code> and empty line before <code>\pend</code> (bug added in v2.8.2).	1
Simplification of the sectioning command code.	1
v2.16.0.	
General: <code>\Xdo@feet</code> becomes <code>\do@Xfeet</code>	296
Add <code>\Xendpagenumberonlyfirst</code> , <code>\Xendpagenumberonlyfirstifsingle</code> , <code>\Xendpagenumberonlyfirstintwo</code> , <code>\Xendinplaceofpagenumber</code> and <code>\Xendsympagenum</code> hooks.	1
Add <code>\Xpagelinesep</code> hook.	49
Compatibility with new features of <code>reledpar</code>	1
Deleted dead code.	1
Display a warning message if using a version of \TeX that is too old.	1
Fix a bug with <code>\Xgroupbylines</code> for notes in two columns	1
Fix a bug with <code>\Xtxtbeforenotes</code> for notes in three or two columns	1
Fix a bug with <code>notenumber</code> option of <code>indextools</code> package when indexing texts in familiar footnotes.	1
Fix potential bug when using <code>\edindex</code> in critical footnotes.	1
More explicit error message in case the stanza indentation is not defined.	296
New options for <code>\fnpos</code> and <code>\mpfnpos</code> to set a customized order for familiar and critical footnotes.	1
When <code>\edindex</code> is called outside of a <code>\beginnumbering... \endnumbering</code> structure, it is automatically switched to <code>\index</code> , with a warning message.	1
When indexing texts in familiar footnotes with <code>\edtext</code> , refer to the line number where the footnote is called.	1
When indexing texts in sidenotes with <code>\edtext</code> , refer to the line number where the sidenote is called.	1
v2.16.1.	
General: Fix a bug with redefinition of the style of the footnote number (bug added in v2.12.0)	1
v2.16.2.	
General: Error message if <code>footmisc</code> is loaded after <code>reledmac</code> .	1
Fix a bug introduced by v2.16.1 when using non-expandable control sequence, like <code>\normalfont</code> , in the footnote number style.	1
v2.16.3.	
General: Fix a bug with <code>\Seref</code> (bug added in v2.7.0).	1
v2.16.4.	
General: Fix a bug with vertical space before sectioning command in optional argument of <code>\pstart</code> (bug added in v2.15.3).	1

v2.16.5.	
General: Fix potential spurious spaces in endnotes.	1
v2.16.6.	
General: Fix a bug with the line number style in <code>\doenotes</code> when referring to right side line in parallel typesetting.	1
Take into account <code>\linenumberstyle</code> when using <code>\edlineref</code>	1
v2.16.7.	
General: Fix a bug with <code>\msdata</code> when using multiple <code>\beginnumbering... \endnumbering</code>	1
Fix a bug with <code>\numberpstarttrue</code> when using multiple <code>\beginnumbering... \endnumbering</code>	1
v2.16.8.	
General: Fix a bug with <code>\edindex</code> in footnotes in parallel typesetting.	1
v2.17.0.	
General: Add <code>\edglsadd</code> command.	1
Add <code>\setmsdataposition</code> setting.	1
v2.17.1.	
General: Fix spurious space in paragraphed footnotes when using <code>Lua\TeX</code> without using Right-To-Left text.	1
v2.17.2.	
General: Change log message when numbered files still don't exist, in order to improve compatibility with <code>latexmk</code>	1
v2.17.3.	
General: Fix a bug with <code>\doendnotesbysection</code> and <code>\doendnotes</code>	1
v2.17.4.	
General: Fix a bug with <code>\setSErefonlypageprefixsingle</code> and <code>\setSErefonlypageprefixmore</code>	1
v2.17.5.	
General: Fix a bug with <code>\pstartref</code> when referring to the left side in parallel typesetting.	1
v2.18.0.	
General: Fix a bug when using a <code>\edtext</code> in two lines or more in right-to-left typesetting with <code>X\TeX</code>	1
Fix a bug when using both <code>\Xnumberonlyfirstintwolines</code> or <code>\Xnumberonlyfirstinline</code> and <code>\Xparafootsep</code> and <code>\Xsymlinenum</code>	1
v2.18.1.	
General: Fix a bug when using <code>\msdata</code> with <code>Lua\TeX</code> or with the <code>hyperref</code> package.	1
v2.19.0.	
General: Add <code>\footnoteXmark</code> and <code>\footnoteXtext</code> commands.	1
Add better compatibility with the <code>csquotes</code> package when using familiar footnotes.	1
Fix a bug with paragraph indent after sectioning command.	1
v2.20.0.	
General: Add <code>\AtStartEveryStanza</code> , <code>\BeforeEveryStopStanza</code> , <code>\AtEndEveryPend</code> , <code>\AtStartEveryPstart</code>	1
Add second optional argument to <code>\pstart</code> , <code>\pend</code> and <code>\stanza</code>	1
Add starred version of <code>\AtEveryPstart</code> , <code>\AtEveryPend</code> , <code>\AtEveryStanza</code> and <code>\AtEveryStopStanza</code>	1
Add third and fourth optional argument to <code>\newverse</code>	1
Fix a bug when using familiar footnotes in <code>\eledsection</code> and related.	1
Reset font specification at the beginning of familiar footnotes.	1

v2.21.0.	
General: Add the possibility of nested <code>\sameword</code> commands.	1
Fix a bug when using formatting command in the argument of <code>\edindex</code> inside <code>\edtext</code>	1
Now, as explained in the handbook, a <code>\edindex</code> inside <code>\edtext</code> only creates an index reference to the main text, and not to the critical footnote.	1
v2.22.0.	
General: Add <code>\txtbeforenotesonlyonceX</code> and <code>\Xtxtbeforenotesonlyonce</code> hooks. .	1
Add <code>\txtbeforenotesX</code> hook.	1
Fix a bug added in v2.16.0 when using <code>\Xtxtbeforenotes</code> with paragraphed or normal footnotes.	1
Fix a bug with three and two columns critical footnotes, broken in v. 2.17.6.	1
v2.22.1.	
General: Compatibility with new version of <code>reledpar</code>	1
Fix a bug with some commands inside <code>\sameword</code>	1
v2.22.2.	
General: Do not print footnotes at the first run.	1
v2.23.0.	
General: Add <code>swcaseinsensitive</code> option	1
Optimisation of the code added on v2.22.2 to not print footnotes at the first run.	1
v2.24.0.	
<code>\next@line@list@stuff</code> : Add <code>\next@line@list@stuff</code> internal hook.	132
General: Add <code>\swnoexpands</code> macro to avoid problems with not fully expandable macro inside <code>\sameword</code>	1
Fix a bug with <code>\edlabel</code> at the beginning of a <code>\pstart</code>	1
Fix spurious space with <code>\labelpstarttrue</code>	1
When a <code>\setlinenum</code> is used, it is stronger than the <code>\lineation{page}</code> setting.	1
v2.24.1.	
General: Compatibility with <code>reledpar 2.20.2</code>	1
v2.24.2.	
General: Fix bug between tabular environments and endnotes	1
v2.25.0.	
General: Add <code>\Xendtxtbeforenotes</code> hook	1
v2.26.0.	
General: Add a mechanism for annotation of stanza line numbering	1
Fix bug in <code>\xpstartref</code>	1
v2.26.1.	
General: Fix bug with <code>\linenumannotation</code>	1
v2.26.10.	
General: Add error message when insertion a <code>\pstart</code> or <code>\pend</code> inside <code>\edtext</code> arguments	1
Really fix bug with page number in footnote after <code>\mainmatter</code> (bug introduced in v2.26.7)	1
v2.26.11.	
General: Allow to use <code>\edtext</code> inside <code>\sameword</code>	1
v2.26.12.	
General: Precise minimal version of <code>xparse</code> package required.	1
v2.26.2.	
General: Fix bug with <code>\linenumannotation</code> in parallel typesetting	1
Fix bug with <code>\Xgroupbyline</code> and <code>\Xparafootsep</code>	1

Fix bug with <code>\Xgroupbyline</code> and optional argument of critical footnotes.	1
Fix bug with <code>\Xgroupbyline</code> for the series after the first one.	1
v2.26.3.	
General: Fix bug added by v2.26.0 with notes in parallel typesetting	1
v2.26.4.	
General: Fix bug when using <code>\numberpstarttrue</code> and alternating between manual <code>\pstart</code> and automatic <code>\pstart</code> produced by <code>\autopar</code>	1
v2.26.5.	
General: Check that users have a enough recent version of <code>xparse</code>	1
Fix bug when using <code>\eledsection</code> with the <code>continuousnumberingwithcolumns</code> of <code>reledpar</code>	1
Fix bug with <code>continuousnumberingwithcolumns</code>	1
Fix bug with using <code>\eledsection</code> and related when alternate normal typesetting and parallel typesetting	1
v2.26.6.	
General: Fix bug with <code>\lineation</code> by page and nexted <code>\edtext</code> between two pages (added in v. 2.24.0)	1
v2.26.7.	
General: Fix page number in footnote and endnotes when using <code>sameparallelpagenumber</code> option of <code>reledpar</code> and typesetting critical text in single mode after critical text in double page mode	1
v2.26.8.	
General: Fix bug in some specific cases, introduced by v.2.27.7	1
v2.26.9.	
General: Fix bug with critical footnotes line number when alternating between <code>\numberlinefalse</code> and <code>\numberlinetrue</code>	1
Fix bug with page number in footnote after <code>\mainmatter</code> (bug introduced in v2.26.7)	1
Workaround with a bug of <code>TeX2018/04/01</code> patch level 3 to generate the .sty file from a .ins file	1
v2.27.0.	
General: Add <code>\doinsidethislinehook</code>	1
v2.27.1.	
General: Fix spurious space in <code>\hidenumbering</code>	1
v2.28.0.	
General: Familiar footnotes can take an optional argument to manually define the footnote mark.	1
v2.28.1.	
General: Fix bug with the alignment of the columns of two and three columns critical footnotes.	1
v2.29.0.	
General: Add <code>noresetlinenumannotation</code>	1
Fix bug with <code>\linenumannotation</code> and <code>nofamiliar</code> option.	1
Fix little bug with <code>\msdata</code>	1
Really reset line number annotation at each line	1
v2.30.0.	
General: Add <code>\Xnoidenticallinenumannotation</code> and <code>\Xendnoidenticallinenumannotation</code> hooks	1
Add separator between line number annotations in margin. Add <code>\setlinenumannotationsep</code>	1

v2.31.0.	
General: Add <code>noprefix</code> and <code>prefixmore</code> to <code>\appref</code> and <code>\Seref</code> .	1
v2.31.1.	
General: Fix bug in vertical spacing with <code>\Xgroupbyline</code> .	1
Fix bug with <code>\Xgroupbyline</code> , which could produce spurious blank lines.	1
Fix bug with <code>\Xhangindent</code> and <code>\hangindentX</code> for right-to-left texts.	1
Fix bug with indentation with <code>\Xgroupbyline</code> .	1
Fix bug with multiple footnote layer and <code>\Xgroupbyline</code> .	1
Fix incompatibility between <code>\Xgroupbyline</code> and <code>hyperref</code> package.	1
Fix incompatibility between <code>\Xgroupbyline</code> and optional argument of critical footnotes.	1
v2.31.2.	
General: Fix bug with familiar footnote containing non-default font (introduced with v. 2.20.0).	1
v2.31.3.	
General: Fix bug with paragraphed footnote in RTL context.	1
v2.32.0.	
General: Add <code>\Xlinenumannotationonlyfirst</code> , <code>\Xlinenumannotationonlyfirstintwo</code> , <code>\Xsymlinenumannotation</code> , <code>\Xendlinenumannotationonlyfirst</code> , <code>\Xendlinenumannotationonlyfirstintwo</code> and <code>\Xendsymlinenumannotation</code> .	1
v2.32.1.	
General: Do not print <code>\Xendsep</code> if we print <code>\Xendsymlinenum</code> .	1
When using <code>\parindentX</code> or <code>\Xparindent</code> and stanza, use the normal indentation in the footnote, not the verse indentation.	1
v2.32.2.	
General: Fix spurious vertical space in familiar footnotes with Lua \TeX .	1
v2.32.3.	
General: Fix bug with critical footnotes when typesetting Arabic text with <code>polyglossia</code> .	1
v2.32.4.	
General: <code>\footnoteXmark</code> and <code>\footnoteXtext</code> can now have an optional argument, setting the footnote number.	1
Fix bug <code>\footnoteXmark</code> and <code>\footnoteXtext</code> .	1
Fix bug when using <code>\Xgroupbyline</code> and twocol arrangement.	1
Fix bug with three and two columns footnotes when using <code>bid</code> .	1
v2.32.5.	
General: Fix bug with <code>\edindex</code> inside <code>\eledsection</code> and related.	1
Fix bug with macro inside <code>\sameword</code> with no- $\mathcal{X}\TeX$ engines.	1
Fix bug with page number in index with <code>\edindex</code> when indexing a critical notes.	1
v2.32.6.	
General: Add <code>hyperref</code> link when inserting glossary entries.	1
Fix bug with glossary entries inside the first argument of <code>\edtext</code> .	1
v2.32.7.	
General: Fix bug with <code>\lineation{pstart}</code> and <code>\edtext</code> in the very first line of a <code>\pstart</code> .	1
Fix bug with <code>\parafootsepX</code> .	1
Fix spurious spaces at the very first line of <code>edtabular</code> environments.	1
v2.32.8.	
General: Add subline number in manuscript apparatus.	1

v2.33.0.	
\ledinnotemark: \ledinnotemark redefinition is deprecated, use \Xinnotemark and \innotemarkX instead.	334
\newhookcommand@series: \newhookcommand@series can take an second optional argument (third argument).	284
General: Add \Xinnotemark and \innotemarkX hooks.	1
Add antilabe feature.	1
Add startstanzaindentsrepetition feature.	1
v2.33.1.	
General: Fix a spacing bug when the argument of \antilabe contains more than one word.	1
v2.34.0.	
General: Add \Xpstartonlyfirst and \Xstanzaonlyfirst.	1
Add \Xpstartseparator.	1
v2.34.1.	
General: Fix bug with page number when using stanazindentsrepetition, bug introduced in v2.33.0.	1
v2.34.2.	
General: Fix bug with tabular environment, in some specific use case, added in v2.32.7. . .	1
v2.34.3.	
General: Fix bug with \parafootsepX when the footnotes are called outside of a numbered section.	1
Fix incompatibility between lineation by \pstart and (a)stanza.	1
Make commands like \hidenumbering working at the very beginning of a verse when the first argument of \setstanzaindents is equal to 0.	1
v2.34.4.	
General: Fix bugs with \parafootsepX outside of numbered section.	1
Fix some bugs with lineation by page, when a numbered section starts at the very beginning of page.	1
v2.34.5.	
General: Fix incompatibility between \apprefwithpage / \SErefwithpage and line number annotation mechanism.	1
v2.34.6.	
General: Fix incompatibility with calc package (added with v2.34.4).	1
v2.34.7.	
General: Fix bug with \parafootsepX in some circumstances (added with v2.34.4). . . .	1
v2.35.0.	
General: Add \linenumannotationothersidettrue.	1
Add new hooks: \Xnolinenumber, \Xendnolinenumber, \Xnolinenumberifannotation, \Xendnolinenumberifannotation.	1
v2.35.1.	
General: Fix a bug when printing ending page number in endnotes and using the hyperref package.	1