

The L^AT_EX keyfloat Package

v2.05 — 2021/06/11

© 2016–2021 Brian Dunn
bd@BDTechConcepts.com

Provides a key/value interface for generating floats.

Abstract

The `keyfloat` package provides a key/value user interface for quickly creating figures with a single image each, figures with arbitrary contents, tables, subfloats, rows of floats, floats located [H]ere, floats in the [M]argin, and floats with text [W]rapped around them.

Key/value combinations may specify a caption and label, a width proportional to `\linewidth`, a fixed width and/or height, rotation, scaling, a tight or loose frame, an `\arraystretch`, a continued float, additional supplemental text, and an artist/author's name with automatic index entry. When used with the `tocdata` package, the name also appears in the List of Figures.

Floats may be moved into or rearranged inside a multi-row environment or subfloats, and are typeset to fit within the given number of columns, continuing to additional rows as necessary. Nested sub-rows may be used to generate layouts such as two small figures placed vertically next to one larger figure.

As an example, a typical command to include a figure with a framed image of half `\linewidth` could be:

```
\keyfig*[hbp]{f,lw=.5,c={A caption},l={fig:label}}{image}
```



`keyfloat` uses the `caption`, `subcaption`, `newfloat` or `float`, and `wrapfig` packages, and cannot be used with the `subfig`, `subfigure`, `subfloat`, `floatrow`, or `floatflt` packages.

License:

This work may be distributed and/or modified under the conditions of the LaTeX Project Public License, either version 1.3 of this license or (at your option) any later version. The latest version of this license is in <http://www.latex-project.org/lppl.txt> and version 1.3 or later is part of all distributions of LaTeX version 2005/12/01 or later.

Contents

1	Introduction	6
1.1	A problem with floats	6
1.2	The keyfloat package	6
1.3	Features	7
2	Using the keyfloat package	9
2.1	Loading keyfloat and related packages	9
2.2	Macros and environments	10
2.3	Keys and values	12
2.4	Other settings	16
2.5	Examples	17
2.5.1	Single floats	17
2.5.2	Groups of floats	28
2.5.3	Subfloats	30
2.5.4	Continued floats	32
2.5.5	Continued subfloats	33
2.5.6	Margin floats	34
2.5.7	Wrapped floats	36
2.5.8	Custom frames	41
2.5.9	Artist's name	43
2.6	Customization	45
2.6.1	Custom frames	45
2.6.2	Distance between floats and rows	45
2.6.3	Formatting the captions	46
3	Code	47
3.1	Older packages	47
3.2	Prohibited packages	47
3.3	Required packages	48
3.4	In-line figures and tables	49
3.5	Row counting and control	50
3.6	Float key handling	50
3.7	Nesting control	57
3.8	Subfloat key handling	57
3.9	Computing image width	61
3.10	Framing and rotation	62

3.11	A graphics image from a file	64
3.12	Printing the caption	65
3.13	Defaults for a new float	70
3.14	Row start/end processing	71
3.15	Key environment helper macros	71
3.16	The \KFLT@keyflt macro	82
3.17	The \keyflt macro	82
3.18	The keyfloat environment	83
3.19	The keyfigure environment	84
3.20	The \keyfig macro	84
3.21	The \keyfigbox macro	84
3.22	The \keyparbox macro	85
3.23	The \keytab macro	86
3.24	The keytable environment	86
3.25	A row of floats	86
3.26	Subfloats	91
3.27	Margin floats	97
3.28	Wrapped floats	98

Change History and Index 100

List of Examples

1	Figure with an image from a file	17
2	Figure with arbitrary contents	17
3	Figure environment with arbitrary contents	18
4	Table macro	18
5	Table environment with arbitrary contents	19
6	Figure with many options selected	20
7	Using \linewidth	21
8	Using frames	22
9	Using rotation with boxes	23
10	Located [H]ere	24
11	Unnumbered float	25
12	Unnumbered float with a LOF entry	25
13	An unnumbered in-text image	26
14	A box without a caption.	27
15	Groups of figures — keyfloats environment	28

16	Subfigures — keysubfigs environment	30
17	Subtables [H] — keysubtabs environment	31
18	Continued figure	32
19	Continued subfloats	33
20	The marginfigure environment	34
21	The margintable environment	34
22	Using \keyfig[M]	35
23	Using keytable[M] and an offset	35
24	Using \keyfig[W] and \keytab[W]	36
25	Using \keyfigbox[W] and \keyparbox[W]	37
26	Using \keyfigure[W] and \keytable[W]	38
27	Using keywrap with a \keyfig	39
28	Using wrap width ww and wlw	40
29	Custom frames with mdframed	41
30	Custom shadows with fancybox	42
31	Artist's name — image	43
32	Artist's name — arbitrary contents	43
33	Subfloats with an artist	44

List of Figures

1	A \keyfig with an image	17
2	A \keyfigbox	17
3	A keyfigure environment	18
4	A figure with options	20
5	Half of \linewidth	21
6	Loosely-framed figure	22
7	Tightly-framed figure	22
8	A keyfig [H]	24
	Starred short caption	25
9	Next to a \keyparbox	27
10	First in a group	29
11	Third in a group	29
12	Fourth in a group	29
13	Fifth in a group	29
14	Sixth in a group	29
15	Subfigures	30
16	Figure to be continued	32
16	...continued	32
17	A set of figures	33
17	...continued	33
18	A marginfigure	34
19	A \keyfig[M]	35
20	A \keyfig[W]	36
21	A \keyfigbox[W]	37

22	A \keyfigure[W]	38
23	Keywrap with \keyfig	39
24	A \keyfig[W] with wlw	40
25	A \keyfig[W] with ww	40
26	Custom-framed image	41
27	Custom loosely-framed box	41
28	Custom shadow	42
29	Custom loosely-framed shadow	42
30	Artist's name — image	<i>First Last</i> 43
31	Artist's name — arbitrary contents	<i>Last</i> 43
32	Artist's collection	<i>First Last</i> 44

List of Tables

1	Keys and values — part I	13
1	Keys and values — part II	14
2	Caption-related key combinations	15
3	Key wp: Wrapped float placement options	15
4	A \keytab table	18
5	A keytable environment	19
6	Loosely-framed table	22
7	Tightly-framed table	22
8	Table, rotated	23
9	A table [H]	24
10	Seventh in a group	29
11	Subtables [H]	31
12	A margintable	34
13	A keytable[M]	35
14	A \keytab[W]	36
15	A keytable[W]	38

1 Introduction

The `keyfloat` package simplifies the creation of \LaTeX floats, while still allowing a large number of useful features.

1.1 A problem with floats

When including a figure with a graphics image into a document, the user typically enters something such as:

```
\begin{figure}
\centering
\includegraphics[width=3in]{filename}
\caption{A Figure}
\label{fig:somelabel}
\end{figure}
```

When doing that often enough, it makes sense to factor the common code:

```
\onefigure[3in]{filename}{A Figure}{fig:somelabel}
```

Expanding the capability of `\onefigure` via `xparse` can lead to the general case of:

```
\onefigure*[loc](width){filename}(add'l text)[shortcap]{caption}*[label]
```

Attempting to add additional features such as frames and continued floats hits the limit of nine parameters for a \TeX macro, requiring that new features use some kind of change-state macros instead. Attempting to support rows of floats or subfloats only makes things more complicated still.

A key/value system solves the problem of adding more features, does not require much additional typing, is a more self-documenting syntax, and allows a shared syntax with subfloats and groups of floats as well. Thus, the `keyfloat` package.

1.2 The `keyfloat` package

Using `keyfloat`, the previous example becomes:

```
\keyfig{w=3in,c=A figure,l=fig:somelabel}{filename}
```

The `\onefigure` general case becomes:

```
\keyfig*[loc]{w=width,t={add'l text},sc=shortcap,cstar=caption,
l=label}{filename}
```


1.3 Features

The macros and environments provided by **keyfloat** include:

\keyfig: A figure with an image.

\keytab: A table.

\keyflt: An arbitrary float type macro.

\keyfigbox: A figure with arbitrary contents.

\keyparbox: A “figure” without a caption, useful to place uncaptioned text inside a group,

keyfigure: A figure environment.

keytable: A table environment.

keyfloat: An arbitrary float type environment.

keyfloats: A group of rows and columns of floats.

keysubfigs: A figure containing a group of rows and columns of subfigures.

keysubtabs: A table containing a group of rows and columns of subtables.

keysubfloats: A float of arbitrary type containing a group of rows and columns of subfloats.

keywrap: Wraps a keyfloat around an environment of text. Usable inside a list.

marginfigure: A figure environment placed into the margin.¹

marginable: A table environment placed in the margin.

Additional features include:

- Rows and columns of floats may be generated by placing them inside a **keyfloats** environment.
- Subfloats may be generated by placing them inside a **keysubfigs** or **keysubtabs** environment.
- Dynamic layout: The number of columns is specified. Extra floats are placed onto additional rows as needed, with the final row adjusted to compensate for leftovers.


¹**marginfigure** and **marginable**: The environments provided by the **tufte-book** class are used if loaded, otherwise **keyfloat** provides its own versions.

- Floats may be placed [H]ere.
- Floats may be placed in the [M]argin.
- Floats may be placed with text [W]rapped around them.
- Floats may be starred to span two columns.
- Continued floats may be used to repeat the previous float number.
- A figure may contain an image, with additional sizing, rotation, and a frame.
- Tables may be stretched. (`\arraystretch`)
- Boxes of arbitrary contents may be assigned a width and framed.
- Floats may be moved into and out of the grouping environments as needed.
- An artist/author's name may be added to a figure and the index.
- If the `tocdata` package is loaded (use v0.12+), the name is also added to the LOF.
- Additional descriptive text may be added as well.
- Frames may be customized.

examples A large number of examples are provided, each showing L^AT_EX source and the resulting float.

index A customized index is included at the back of the documentation.

margin tags Blue margin tags are used to help quickly find information, and often indicate the destination of index entries.

 **warnings** Several warnings are noted in the text. Watch out for these special cases.

problems See the “troubleshooting” section of the index for help with specific problems which may occur.

2 Using the keyfloat package

2.1 Loading keyfloat and related packages

keyfloat is loaded with the usual command:

```
\usepackage{keyfloat}
```

Pkg tocdato If you wish to have artists' names appear in the list of figures, as provided by the tocdato package, load tocdato, optionally followed by either tocloft or titletoc, then keyfloat:

Pkg tocloft
Pkg titletoc

```
\usepackage{tocdata}  
\usepackage{titletoc}% or titletoc, or neither  
\usepackage{keyfloat}
```

Pkg float To use custom float types with the float package:

```
\usepackage{float}  
\newfloat{diagram}{htb}{lod}
```

Pkg newfloat To use custom float types with the newfloat package:

```
\usepackage{newfloat}  
\DeclareFloatingEnvironment[  
  fileext={lod},  
  listname={List of Diagrams},  
  name={Diagram},  
{diagram}
```

Pkg caption For the caption package, to have table captions appear above the tables, and to use custom float types:

```
\usepackage[tableposition=top]{caption}  
\captionsetup[diagram]{  
  style=default, justification=centering,  
  margin=0pt, parskip=0pt, skip=1ex,  
  labelfont={small,bf}, textfont={small,bf}  
}
```

Pkg cleveref To use custom float and subfloat types with cleveref:

```
\usepackage{cleveref}  
\crefname{diagram}{diagram}{diagrams}  
\crefname{subdiagram}{subdiagram}{subdiagrams}
```


2.2 Macros and environments

<code>\keyfig</code>	<code>* [\langle loc \rangle] {\langle keys/values \rangle} {\langle image filename \rangle}</code> A macro to generate a figure with an image from a file.
<code>\keytab</code>	<code>* [\langle loc \rangle] {\langle keys/values \rangle} {\langle tabular contents \rangle}</code> A macro to generate a table with tabular contents. Usually use the <code>keytable</code> environment instead.
<code>\keyflt</code>	<code>* [\langle loc \rangle] {\langle float type \rangle} {\langle keys/values \rangle} {\langle contents \rangle}</code> A macro to generate an arbitrary float type with its contents.
<code>\keyfigbox</code>	<code>* [\langle loc \rangle] {\langle keys/values \rangle} {\langle box contents \rangle}</code> A macro to generate a figure with arbitrary paragraph contents. See example 2.
<code>\keyparbox</code>	<code>* [\langle loc \rangle] {\langle keys/values \rangle} {\langle box contents \rangle}</code> A macro to generate a figure with arbitrary paragraph contents, but no number or caption. This is equal to a <code>\keyfigbox</code> with <code>cstar={}</code> . Mostly useful to add supplemental information inside a row of floats or subfloats. See example 14.
Env <code>keyfigure</code>	<code>* [\langle loc \rangle] {\langle keys/values \rangle}</code> An environment to generate a figure with arbitrary contents. Useful for multi-paragraph contents. See example 3.
Env <code>keytable</code>	<code>* [\langle loc \rangle] {\langle keys/values \rangle}</code> An environment to generate a table with arbitrary contents. Useful for larger tables. See example 5.
Env <code>keyfloat</code>	<code>* [\langle loc \rangle] {\langle float type \rangle} {\langle keys/values \rangle}</code> An environment to generate an arbitrary float type with its contents. Useful for multi-paragraph contents.

The above macros and environments may be used by themselves, or inside the following `keyfloats`, `keysubfigs`, or `keysubtabs` environments.

Env <code>keyfloats</code>	<code>* [\langle loc \rangle] {\langle num columns \rangle}</code> A group of figures or tables typeset in rows. May be nested, [H], [W], or [M]. See example 15.
Env <code>keysubfigs</code>	<code>* [\langle loc \rangle] {\langle numcols \rangle} {\langle keys \rangle}</code> A group of subfigures typeset in rows. May <i>not</i> be nested. May be [H], [W], or [M]. See example 16.

-
- Env `keysubtabs` * [`\loc`] {`\numcols`} {`\keys`}
- A group of subtables typeset in rows. May *not* be nested. May be [H], [W], or [M]. See example 17.
- Env `keysubfloats` * [`\loc`] {`\float type`} {`\numcols`} {`\keys`}
- A group of subfloats typeset in rows. May *not* be nested. May be [H], [W], or [M].
- Env `keywrap` {`\width of keyfloat`} {`\keyfloat`}
- Displays a keyfloat next to an environment of text. Two minipages are used side-by-side, which allows its use inside a list item where [W] will not work, but extra empty vertical space will appear if the keyfloat and the text are of unequal vertical size. `\keyfloat` may be any of `\keyfig`, `keyfigure`, `keyfloats`, `keysubfigs`, etc., each with its proper arguments. See example 27.
- ⚠ **empty space**
- Env `marginfigure` [`\offset`]
- A figure placed into the margin, with an optional vertical offset. `\keyfloat` uses the version provided by the `tufte-book` class if available, or provides its own version otherwise. See example 20.
- Env `marginable` [`\offset`]
- A table placed into the margin, with an optional vertical offset. `\keyfloat` uses the version provided by the `tufte-book` class if available, or provides its own version otherwise. See example 21.
-
- Arg * The star option create floats which span both columns in a two-column document.
- Arg [H] The [H] location forces a figure to be “Here”, in the form of a minipage instead of a float. A caption, label, etc. may still be assigned.
- Arg [M] The [M] location places the float into the margin. When the `tufte-book` class is used, its `marginfigure` and `marginable` environments are used, otherwise `keyfloat` provides and uses its own versions of the same environments. See examples 22 and 23.
- Arg [W] The [W] location wraps text around the float. Use this just before the start of a paragraph with contents large enough to wrap around the float. Do not use this inside a list environment. Select placement with the `wp` key; see the `wrapfig` package documentation for more information. Use `w` or `lw` to set the width of the item/image contained inside the wrap area. By default the caption will also be contained in this width. To use a larger width for the overall container and caption, set `w` or `lw` for the size of the image, and also use `ww` or `wlw` for a larger size for the caption. Watch the log for warnings from
- Pkg `wrapfig`
- ⚠ **wrapfig warnings**
- Arg [`\loc`] The star and [`\loc`] options are ignored for floats inside a `keyfloats`, `keysubfigs`, or `keysubtabs` environment. Note that these container environments may have their own star and [`\loc`] options.

2.3 Keys and values

Table 1 shows the key/value combinations which are allowed. In most cases these may be used in any order and any combination, except for the following:

subfloat keys The keys labeled "Sub" may be used for the `keysubfigs` and `keysubtabs` environments, which group a number of subfloats together under one master float. The master float has its own caption, label, and text, and each subfloat inside the group likewise has its own set of keys.

keyfloats keys `keyfloats` does not accept any keys at all.

The “artist” keys `ap`, `af`, `al`, and `as` are only used by figures.

The `stretch` key increases space between tabular elements.

The rest of the macros and environments accept all of the keys, as they each create an individual float or subfloat, and each may have its own assigned dimensions and frame.

short/long caption combinations Table 2 shows the combinations of the caption-related keys `c`, `cstar`, and `sc`, and how they control the caption numbering and entries in the `LOF/LOT`.

wrapped float placement Table 3 shows the wrapped-float placement options for the `wp` key for floats placed `[W]`.

Table 1: Keys and values — part I

Key	Sub ^a	Description	Example
c	•	An unstarred caption. If empty, creates a figure with a number but no caption.	c={A caption}
cstar	•	A starred caption. Creates a float without a number. If empty, creates a figure with no number or caption.	cstar={No Num}
sc	•	The short caption for the LOF/LOT, even if cstar.	sc={Short cap}
cont	•	Continued float?	cont
l	•	The label. Enclose in braces if a comma is included. Ignored in unnumbered floats.	l=fig:alabel
ap, aup	•	Artist/author's prefix, such as "Mr." ^b	ap=Mr.
af, auf	•	Artist/author's first name. ^b	af=First
al, aul	•	Artist/author's last name. ^b	al=Last
as, aus	•	Artist/author's suffix, such as ~III. ^b	al=~III
t	•	Additional text. May include paragraphs. Enclose in braces if a comma is included. May need \protect before macro calls. Fully-justified alignment.	t={Paragraphs}
tc	•	Additional text, aligned to the center.	tc={Paragraphs}
tl	•	Additional text, aligned to the left.	tl={Paragraphs}
tr	•	Additional text, aligned to the right.	tr={Paragraphs}

^a: All the keys in Part I may be used with the keysubfigs, keysubtabs, and keysubfloats environments.

^b: Artist / author keys: al is an artist's last name, aul is an author's last name, etc. Artists names are printed centered, authors are flush right. A fixed-width non-breakable space is placed between parts of names, except that the optional suffix is connected directly to the last name, allowing "as={, Title}", for example.

... continued

Table 1: Keys and values — part II

Key	Sub ^c	Description	Example
lw	—	Set the width to a fraction of <code>\linewidth</code> . Cancels <code>w</code> . If a non-image float, sets the width of the text box. For wrapped objects, may be used with <code>wlw</code> for a smaller item with a larger caption.	<code>lw=.5</code>
w	—	Set the actual width. Cancels <code>lw</code> . If a non-image float, sets the width of the text box. For wrapped objects, may be used with <code>ww</code> for a smaller item with a larger caption.	<code>w=2in</code>
h	—	Set the actual height, images only.	<code>w=2in</code>
s	—	Set the image scale, images only.	<code>s=3</code>
r	—	Set the rotation angle; counter-clockwise degrees.	<code>r=90</code>
f	—	Selects a loose frame with the current <code>\fboxsep</code> . Only rotated with <code>\keyfig</code> .	<code>f</code>
ft	—	Selects a tight frame with no <code>\fboxsep</code> . Useful for photographs, or diagrams which already have some margin built in.	<code>ft</code>
stretch	—	Sets <code>\arraystretch</code> inside the float.	<code>stretch=1.5</code>
mo	—	Sets the vertical offset for a margin float.	<code>mo=-1.2ex</code>
wn	—	Sets the number of lines for a wrapped float.	<code>wn=2</code>
wp	—	Sets the wrap placement for a wrapped float. The default is 0, which places the wrapped float at the outside edge of the text. See table 3.	<code>wp=I</code>
wo	—	Sets the wrap overhang for a wrapped float.	<code>wo=8em</code>
wlw	—	Sets the total width of the wrapped item to a fraction of <code>\linewidth</code> . May be more than the <code>w</code> or <code>lw</code> width.	<code>wlw=.6</code>
ww	—	Sets the total width of the wrapped item. May be more than the <code>w</code> or <code>lw</code> width.	<code>ww=2in</code>
va	—	Sets the vertical alignment of the outermost minipage container for the keyfloat. Defaults to 'c'.	<code>va=t</code>

^c None of the keys in Part II are used in the `keysubfigs`, `keysubtabs`, and `keysubfloats` environments.

Table 2: Caption-related key combinations

Keys in Use			Type of	
c	cstar	sc	Caption ^a	LOF/LOT ^b
•	—	—	Numbered	Caption
•	—	•	Numbered	Short Caption
—	•	—	Unnumbered	None
—	•	•	Unnumbered	Short Caption
—	cstar={}	Ignored	None	None

^a: Caption: Shows whether the float will be numbered, unnumbered, or have no caption.

^b: LOF/LOT: Shows whether the regular or short caption will appear in the List of Figures or List of Tables, or if there will be no listing.

Table 3: Key wp: Wrapped float placement options

Key	Location
r R	to the right of the text body
l L	to the left of the text body
i I	to the inside margin
o O	to the outside margin

The un-capitalized key attempts to place the float “here”, and the capitalized key allows L^AT_EX to try to find the best location. The default is 0.

2.4 Other settings

`\KFLTtightframe` $\{\langle contents \rangle\}$ Frames the contents without separation.

`\KFLTlooseframe` $\{\langle contents \rangle\}$ Frames the contents with separation.

These may be used to re-define how contents are framed. The default is a simple `\fbox`.

Len `\KFLTtightframewidth` Combined width of the frame and separation for each of tight and loose frames. These settings should be adjusted when changing the frame width and/or separation. The value should be equivalent to `\fboxwidth` plus `\fboxsep`.

Len `\KFLTlooseframewidth`

Len `\KFLTimageboxwidth` The computed width of the image. Useful to enclose an `mdframed` environment to restrict its width. See example [29](#).

An image.

Figure 1: A \keyfig with an image

Some text. More text.

Another paragraph.

Figure 2: A \keyfigbox

2.5 Examples

2.5.1 Single floats

Example 1: Figure with an image from a file

Code:

```
\keyfig{c=A \cs{keyfig} with an image,l=fig:simple}{image}
```

Result:

Figure 1

natural size

This float (fig. 1) is shown at its natural size because no width or height modifiers were specified. When used alone like this, a regular float is created.

Example 2: Figure with arbitrary contents

Code:

```
\keyfigbox{f,c={A \cs{keyfigbox}},l=fig:figbox}
  {Some text. More text. \par Another paragraph.}
```

Result:

Figure 2

default width

The \keyfigbox creates a figure with a box of arbitrary contents, instead of an image from a file. Its default width is the full \linewidth, unless w or lw keys are used.

Arbitrary contents may go here.

Including multiple paragraphs.

Figure 3: A keyfigure environment

Table 4: A \keytab table

A	B
C	D

Example 3: Figure environment with arbitrary contents

Code:

```
\begin{keyfigure}{f,c={A \env{keyfigure} environment},
  l=fig:environment}
Arbitrary contents may go here.
```

```
Including multiple paragraphs.
\end{keyfigure}
```

Result:

Figure 3

The keyfigure environment is preferred over the \keyfigbox macro when multiple lines of contents are to be included.

Example 4: Table macro

Code:

```
\keytab{c=A \cs{keytab} table,l=tab:simpletable}{\testtable}
```

Result:

Table 4

Do not try to use tables which overflow the page.

For anything other than a simple table, use the keytable environment. See example 5.

[large tables](#) For large tables, use the longtable or supertabular packages.

Table 5: A keytable environment

Arbitrary contents may go here. ^{<i>a</i>}	
A	B
C	D
^{<i>a</i>} A footnote.	

Example 5: Table environment with arbitrary contents*Code:*

```

\begin{keytable}{f,c={A \env{keytable} environment},
  l=tab:environment}
Arbitrary contents may go here.\footnote{A footnote.}

\testtable
\end{keytable}

```

*Result:***Table 5**

The keytable environment is preferred over the `\keytab` macro since most tables are multi-line creations.

`\keytab` centers the table, but `keytable` does not. Add `\centering` if desired.



Additional text. Multiple paragraphs may be used. The entire text is enclosed in braces because a comma is included. Alignment may be set by using tags `tc`, `tl`, or `tr` instead of `t`

Figure 4: A figure with many options

Example 6: Figure with many options selected

Code:

```
\keyfig{
  w=2in,ft,r=15,
  c=A figure with many options,
  sc=A figure with options,
  t={Additional text. Multiple paragraphs may be used.
    The entire text is enclosed in braces because a comma
    is included. Alignment may be set by using
    tags \optn{tc}, \optn{tl}, or \optn{tr}
    instead of \optn{t}},
  l=fig:options
}{image}
```

Result:

Figure 4

Width is fixed at 2 in, a tight frame is specified (`\fboxsep` of 0 pt), a short caption appears in the List of Figures, and the additional text is using the default fully-justified alignment.

Since fig. 4 is a float, it may appear on the following page.



Figure 5: Half of `\linewidth`

Example 7: Using `\linewidth`

Code:

```
\keyfig{lw=.5,c=Half of \cs{linewidth},l=fig:linewidth}{image}
```


Result:

Figure 5

`\linewidth` Figure 5 is half of `\linewidth` in size. When the `lw` key is used inside a `keyfloats` or `keysubfigs` environment, the `\linewidth` will be proportional to the sub-box for each element. When used alone, such as here, the `\linewidth` is the full width of the text on this page.

`lw` and `w` are not used at the same time. If both `lw` and `w` are specified, the last one cancels any previous ones.

Table 8: Table, rotated



(Framed to show box width.)

Example 9: Using rotation with boxes

Code:

```
\keytab{f,w=.8in,c={Table, rotated},
  r=70,l=tab:rotated,
  tc=(Framed to show box width.))
{\testwidetable}
```

Result:

Table 8

- rotated whitespace Unless a width is given, a box is the full \linewidth. When rotated, this extra horizontal space is rotated into extra vertical space. To avoid this extra space, set a w or lw to be
- ⚠ box width wide enough for the table or other contents, but not much wider. When this box is rotated, it will not take much more vertical space than necessary.
- frame rotation Unlike an image, the frame of a box does not rotate with its contents.

Example 10: Located [H]ere

Code:

```
\keytab[H]{c={A table [H]},l=tab:here}{\testtable}  
\keyfig[H]{f,w=1in,c={A keyfig [H]},l=fig:here}{image}
```

Result:


Table 9, Figure 8


Table 9: A table [H]

A	B
C	D



Figure 8: A keyfig [H]

 **Out of sequence** Table 9 and Figure 8 are to be placed “[H]ere”, and therefore may appear out-of-sequence with surrounding figures. Place a \clearpage before or after to re-sync, if necessary.



Starred caption with a short caption.


Example 11: Unnumbered float

Code:

```
\keyfig[H]{f,cstar={A starred caption}}{image}
```

Result:

See fig: “A starred caption”.



A starred caption

A starred caption creates a float without a number, and without an entry in the List of Figures unless there is a non-empty short caption. (See the next example.)



No label

Labels cannot be used when there is no number for a float.

Example 12: Unnumbered float with a LOF entry

Code:

```
\keyfig{
  f,cstar={Starred caption with a short caption.},
  sc={Starred short caption}
}{image}
```

Result:

See fig: “Starred caption with a short caption”.

A starred caption with a non-empty short caption creates an unnumbered entry in the List of Figures.

Example 13: An unnumbered in-text image

Code:

```
\keyfig[H]{f,cstar={},  
  tc={Optional text which is not a caption.}  
}{image2}
```

Result:

See fig: “Optional text which is not a caption.”



Optional text which is not a caption.

By using [H] and cstar={}, the image is placed inline without a number or LOF entry.

Also see example 14.

Some contents.

A `\keyparbox` with no number or label.

An image.

Figure 9: Next to a `\keyparbox`

Example 14: A box without a caption.

Code:

```
\begin{keyfloats}{2}
\keyparbox{
  f,lw=.5,
  tc={A \cs{keyparbox} with no number or label.}
}{Some contents.}
\keyfig{c=Next to a \cs{keyparbox},l=fig:nexttoparbox}{image}
\end{keyfloats}
\keyparbox[H]{f,lw=.5}{A \cs{keyparbox} [H], outside the row.}
```

Result:

Figure 9, and the box to its left.

A `\keyparbox` [H], outside the row.

A `\keyparbox` is a `\keyfigbox` with `cstar={}`, and is mostly useful as an information box inside a row or a set of subfloats.

2.5.2 Groups of floats

Example 15: Groups of figures — keyfloats environment

Code:


```
\begin{keyfloats}{2}
\keyfig{lw=1,f,c={First in a group},
  l=fig:firstinrow,tl={\cs{raggedright} text}
}{image}
\keyparbox{}{\centering A \cs{keyparbox} describing something.
  \par With several paragraphs.}
\begin{keyfloats}{2}
\keyfig{lw=1,c={Third in a group},
  l=fig:thirdinarow}{image}
\keyfig{lw=1,c={Fourth in a group}}{image2}
\keyfig{lw=1,c={Fifth in a group}}{image}
\keyfig{lw=1,c={Sixth in a group},
  l=fig:sixthinrow}{image2}
\end{keyfloats}
\keytab{c={Seventh in a group},l=tab:seventhinrow}{\testwidetable}
\end{keyfloats}
```


Result:

Figure 10 to Table 10

Figure 10 to table 10 are in a keyfloats environment. Furthermore, Figures 11 to 14 are in an additional nested keyfloats environment, forming a small box of floats inside the larger group.

The keyfloats environment takes an argument for the number of columns. Additional floats are automatically placed on following rows. Changing the number of columns will cause the floats to automatically readjust as necessary. Leftovers will be centered on the last row.

 **\linewidth** Note that \linewidth is adjusted for each row and nested row, so the lw key will need to be changed if a float is moved to a different nesting level.

 **image too large** Fixed-width or fixed-height floats may be too large to fit if they are moved into a group. It is the user's responsibility to adjust w, h, or lw as necessary.

Keyfloats may be located [H], [M], or located [W] set with half the line width:

```
\begin{keyfloats}[H]{2}...
```

Keyfloats may be starred to span both columns in a two-column format:

```
\begin{keyfloats}*{2}...
```




\raggedright text

Figure 10: First in a group

A \keyparbox describing something.
With several paragraphs.




Figure 11: Third in a group

Figure 12: Fourth in a group




Figure 13: Fifth in a group

Figure 14: Sixth in a group

Table 10: Seventh in a group

A	B	C
D	E	F




Figure 15: Subfigures

2.5.3 Subfloats

Example 16: Subfigures — keysubfigs environment

Code:

```
\begin{keysubfigs}{3}{c=Subfigures,l=fig:subfigs}
\keyfig{lw=1,f,c={First subfigure},
  l=fig:firstsubfig,t=Some text}{image}
\keyfig{lw=1,f,r=90,c={Second subfigure},
  l=fig:secondsubfig,
  t=Lots of lots of lots of lots of text.}
  {image2}
\begin{keyfloats}{1}
\keyfig{lw=1,f,c={Third subfigure},l=fig:thirdsubfig}{image}
\keytab{c={Fourth subfigure},l=fig:fourthsubfig}{\testtable}
\keyfig{lw=.5,f,c={Fifth subfigure},l=fig:fifthsubfig}{image}
\end{keyfloats}
\end{keysubfigs}
```

Result:

Figure 15

Figures 15a to 15e are in the fig. 15 keysubfigs environment. The keysubtabs environment is similar. Mixed types have the type of their container, as shown with fig. 15d.

Subfloats are associated floats (a, b, ...) collected together into one common float (the enclosing `keysubfigs` or `keysubtabs` environment). The enclosing float can have its own caption (call “Sub-Figures” in the example), which appears in the LOF/LOT, and also a label. Each subfloat can have its own caption and label as well, but the subcaption does not appear in the LOF/LOT.

- ⚠ **mixed subfloats** All subfloats are forced to have the same type as its containing float. A table inside a figure will be labeled as a figure, for example. This avoids miss-labeling as each subfloat must clearly be identified as a child of its containing float.
- ⚠ **nested subfloats** `keysubfigs` and `keysubtabs` may not be used inside the `keyfloats` environment, and cannot be nested inside each other. (No subfloat 12aa, 12ab, 12ba, etc.)
- n **nested keyfloats** The `keyfloats` environment may be used inside `keysubfigs` or `keysubtabs` to gather subfloats together, such as the three right-most figures in fig. 15.

Subfloats may be located [H], [M], or located [W] set with half the line width:

```
\begin{keysubfigs}[H]{3}{key/vals ...}
```

Subfloats may be starred to span both columns in a two-column format:

```
\begin{keysubfigs}*{2}{key/vals ...}
```

Example 17: Subtables [H] — `keysubtabs` environment

Code:

```
\begin{keysubtabs}[H]{2}{c=Subtables [H],l=tab:subtabs}
\keytab{c={First subtable},l=fig:firstsubtab}{\testtable}
\keytab{c={Second subtable},l=fig:secondsubtab}{\testwidetable}
\end{keysubtabs}
```

Result:

Table 11

Table 11: Subtables [H]

a: First subtable

A	B
C	D

b: Second subtable

A	B	C
D	E	F

An image.

Figure 16: Figure to be continued



Figure 16: ...continued

2.5.4 Continued floats

The cont key may be used to generate a “continued” float. The continued float receives the same number as the previous float, and it is assumed that they are the same float, except that they are separated for some reason such as size on the page.

The label may be placed in a continued float, and will still receive the same float number as the prior non-continued float.

Example 18: Continued figure

Code:

```
\begin{keyfloats}{2}
\keyfig{,c=Figure to be continued}{image}
\keyfig{c={\dots continued},cont,l=fig:firstcontinued}{image2}
\end{keyfloats}
```

Result:

Figure 16

An image.

a: First of a set

An image.

b: Second of a set

Figure 17: A set of figuresAnother
image

c: Third of a set

Another
image

d: Fourth of a set

Figure 17: ...continued

2.5.5 Continued subfloats

The keysubfigs and keysubtabs environments may also be given the cont key. The containing environment's float receives the same number as the previous float (presumably another subfloat container).

Example 19: Continued subfloats

Code:

```
\begin{keysubfigs}{2}{c={A set of figures},l=fig:continuedfigures}
\keyfig{c={First of a set},l=fig:contfirst}{image}
\keyfig{c={Second of a set},l=fig:contsecond}{image}
\end{keysubfigs}
\begin{keysubfigs}{2}{c={\dots continued},cont}
\keyfig{c={Third of a set},l=fig:contthird}{image2}
\keyfig{c={Fourth of a set},l=fig:contfourth}{image2}
\end{keysubfigs}
```

*Result:**Figure 17*

2.5.6 Margin floats

When a keyfloat is located [M], it will be placed in the margin.

Cls tufte-book

When the tufte-book class is used, its marginfigure or margintable environments will be used, otherwise keyfloat provides environments of the same name and uses those instead.

An image.

Some text added by hand.

Figure 18: A marginfigure

Example 20: The marginfigure environment

Code:

```
\begin{marginfigure}
\centering
\includegraphics[width=.75\linewidth]{image}

Some text added by hand.
\caption{A \env{marginfigure}}
\label{fig:marginfigure}
\end{marginfigure}
```

Result:

Figure 18

Example 21: The margintable environment

A	B	C
D	E	F

Table 12: A margintable

Code:

```
\begin{margintable}
\centering
\testwidetable
\caption{A \env{margintable}}
\label{fig:margintable}
\end{margintable}
```

Result:

Table 12

Example 22: Using \keyfig[M]

Code:

```
\keyfig[M]{c={A \cs{keyfig}\optn{[M]}},l=fig:keyfigm,ft,
t=Additional text.
Text text text text text text.

More paragraphs.
}{image2}
```

Result:

Figure 19

Example 23: Using keytable[M] and an offset

Code:

```
\begin{keytable}[M]{c={A \env{keytable}\optn{[M]}},
l=tab:keytablem,mo=-.9in}
\centering
\testwidetable
\end{keytable}
```


Result:

Table 13

A negative offset was used to shift the table upwards to the top of the example.

To set the minimum-allowed distance between \marginpars and margin floats:

```
\setlength{\marginparpush}{3ex}
```



Additional text. Text text text text text text.

More paragraphs.

Figure 19: A \keyfig[M]

Table 13: A keytable[M]

A	B	C
D	E	F

2.5.7 Wrapped floats

Example 24: Using \keyfig[W] and \keytab[W]


Code:

```
\keyfig[W]{c={A \cs{keyfig}\optn{[W]}},
  l=fig:keyfigw,ft,lw=.4,wp=I, wo=8em, wn=12,
  t={.4\cs{linewidth} wide, placed \optn{I}.}
}{image2}
\blindtext

\keytab[W]{c={A \cs{keytab}\optn{[W]}},l=tab:keytabw,w=.75in,
}{\testtable}
\blindtext
```

Result:

Figure 20 and table 14



.4\linewidth wide, placed I.

Figure 20: A \keyfig[W]

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Etiam lobortis facilisis sem. Nullam nec mi et neque pharetra sollicitudin. Praesent imperdiet mi nec ante. Donec ullamcorper, felis non sodales commodo, lectus velit ultrices augue, a dignissim nibh lectus placerat pede. Vivamus nunc nunc, molestie ut, ultricies vel, semper in, velit. Ut porttitor. Praesent in sapien. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Duis fringilla tristique neque. Sed interdum libero ut metus. Pellentesque placerat. Nam rutrum augue a leo. Morbi sed elit sit amet ante lobortis sollicitudin. Praesent blandit blandit mauris. Praesent lectus tellus, aliquet aliquam, luctus a, egestas a, turpis. Mauris lacinia lorem sit amet ipsum. Nunc quis urna dictum turpis accumsan semper.

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Etiam lobortis facilisis sem. Nullam nec mi et neque pharetra sollicitudin. Praesent imperdiet mi nec ante. Donec ullamcorper, felis non sodales commodo, lectus velit ultrices augue, a dignissim nibh lectus placerat pede. Vivamus nunc nunc, molestie ut, ultricies vel, semper in, velit. Ut porttitor. Praesent in sapien. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Duis fringilla tristique neque. Sed interdum libero ut metus. Pellentesque placerat. Nam rutrum augue a leo. Morbi sed elit sit amet ante lobortis sollicitudin. Praesent blandit blandit mauris. Praesent lectus tellus, aliquet aliquam, luctus a, egestas a, turpis. Mauris lacinia lorem sit amet ipsum. Nunc quis urna dictum turpis accumsan semper.

Table 14: A \keytab[W]

A	B
C	D

Example 25: Using `\keyfigbox[W]` and `\keyparbox[W]`*Code:*

```

\keyfigbox[W]{c={A \cs{keyfigbox}\optn{[W]}},
  l=fig:keyfigboxw,f,lw=.25,wp=I, wn=7,
  t=Text text text text text text text text
}{The contents.}
\blindtext

\keyparbox[W]{w=1in}{A \cs{keyparbox}[W] and some more text.}
\blindtext

```

*Result:**Figure 21 and the `\keyparbox`.*

The contents.

Text text text text text text
text text text

Figure 21: A `\keyfigbox[W]`

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Etiam lobortis facilisis sem. Nullam nec mi et neque pharetra sollicitudin. Praesent imperdiet mi nec ante. Donec ullamcorper, felis non sodales commodo, lectus velit ultrices augue, a dignissim nibh lectus placerat pede. Vivamus nunc nunc, molestie ut, ultricies vel, semper in, velit. Ut porttitor. Praesent in sapien. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Duis fringilla tristique neque. Sed interdum libero ut metus. Pellentesque placerat. Nam rutrum augue a leo. Morbi sed elit sit amet ante lobortis sollicitudin. Praesent blandit blandit mauris. Praesent lectus tellus, aliquet aliquam, luctus a, egestas a, turpis. Mauris lacinia lorem sit amet ipsum. Nunc quis urna dictum turpis accumsan semper.

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Etiam lobortis facilisis sem. Nullam nec mi et neque pharetra sollicitudin. Praesent imperdiet mi nec ante. Donec ullamcorper, felis non sodales commodo, lectus velit ultrices augue, a dignissim nibh lectus placerat pede. Vivamus nunc nunc, molestie ut, ultricies vel, semper in, velit. Ut porttitor. Praesent in sapien. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Duis fringilla tristique neque. Sed interdum libero ut metus. Pellentesque placerat. Nam rutrum augue a leo. Morbi sed elit sit amet ante lobortis sollicitudin. Praesent blandit blandit mauris. Praesent lectus tellus, aliquet aliquam, luctus a, egestas a, turpis. Mauris lacinia lorem sit amet ipsum. Nunc quis urna dictum turpis accumsan semper.

A
`\keyparbox[W]`
 and some more
 text.

Example 26: Using \keyfigure[W] and \keytable[W]

```
Code:

\begin{keyfigure}[W]{c={A \cs{keyfigure}\optn{[W]}},
  l=fig:keyfigurew,f,w=1.5in, wo=4em,wn=5}
This is a keyfigure.
\end{keyfigure}
\blindtext

\begin{keytable}[W]{c={A \env{keytable}\optn{[W]}},
  l=tab:keytablew,w=2in,wp=L,
  tc=Placed \optn{L} and 2in wide.}
\centering
\testwidetable
\end{keytable}
\blindtext
```

Result:
Figure 22 and table 15

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Etiam lobortis facilisis sem. Nullam nec mi et neque pharetra sollicitudin. Praesent imperdiet mi nec ante. Donec ullamcorper, felis non sodales commodo, lectus velit ultrices augue, a dignissim nibh lectus placerat pede. Vivamus nunc nunc, molestie ut, ultricies vel, semper in, velit. Ut porttitor. Praesent in sapien. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Duis fringilla tristique neque. Sed interdum libero ut metus. Pellentesque placerat. Nam rutrum augue a leo. Morbi sed elit sit amet ante lobortis sollicitudin. Praesent blandit blandit mauris. Praesent lectus tellus, aliquet aliquam, luctus a, egestas a, turpis. Mauris lacinia lorem sit amet ipsum. Nunc quis urna dictum turpis accumsan semper.

This is a keyfigure.

Figure 22: A \keyfigure[W]

Table 15: A keytable[W]

A	B	C
D	E	F

Placed L and 2in wide.

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Etiam lobortis facilisis sem. Nullam nec mi et neque pharetra sollicitudin. Praesent imperdiet mi nec ante. Donec ullamcorper, felis non sodales commodo, lectus velit ultrices augue, a dignissim nibh lectus placerat pede. Vivamus nunc nunc, molestie ut, ultricies vel,

semper in, velit. Ut porttitor. Praesent in sapien. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Duis fringilla tristique neque. Sed interdum libero ut metus. Pellentesque placerat. Nam rutrum augue a leo. Morbi sed elit sit amet ante lobortis sollicitudin. Praesent blandit blandit mauris. Praesent lectus tellus, aliquet aliquam, luctus a, egestas a, turpis. Mauris lacinia lorem sit amet ipsum. Nunc quis urna dictum turpis accumsan semper.

Example 27: Using keywrap with a \keyfig*Code:*

```

\begin{itemize}
\item First item.
    Several lines of text text text text text
    text text text text text text text text.
\item \begin{keywrap}{.3\linewidth}{\keyfig{%
    lw=1,c={Keywrap with \cs{keyfig}},l=fig:keywrapfig%
}}{image}}
    Second item.
    Several lines of text text text text text
    text text text text text text text text
    text text text text text text text.

    These paragraphs are inside the \texttt{keywrap}.
    A vertical gap appears below if the text is not enough to
    fill the space next to the \cs{keyfig}.
\end{keywrap}
    Outside the \env{wrapfig},\margintag{notes}\
    but still in the second item.
    There is no elegant way to place only part of a paragraph
    inside a \env{keywrap}, and attempting to do so requires
    manually removing the vertical paragraph skip.
\item Third item.
\end{itemize}

```

*Result:**Figure 23*

- First item. Several lines of text text text text text text text text text text text text.
 - Second item. Several lines of text text text text text text text text text text text text text text.
- These paragraphs are inside the keywrap. A vertical gap appears below if the text is not enough to fill the space next to the \keyfig.
- Outside the wrapfig, but still in the second item. There is no elegant way to place only part of a paragraph inside a keywrap, and attempting to do so requires manually removing the vertical paragraph skip.
- Third item.

An image.**Figure 23: Keywrap with \keyfig**

notes

Example 28: Using wrap width `ww` and `wlw`*Code:*

```

\keyfig[W]{c={A \cs{keyfig}\optn{[W] with \optn{wlw}}},
  l=fig:keyfigwlw,ft,lw=.15,wlw=.4,wp=I,
  t={.15\cs{linewidth} wide, in a .4\cs{linewidth} box.}
}{image2}
\blindtext[1]

\keyfig[W]{c={A \cs{keyfig}\optn{[W] with \optn{ww}}},
  l=fig:keyfigww,ft,w=1cm,ww=3cm,wp=I,
  t={1cm wide, in a 3cm box.}
}{image2}
\blindtext[1]

```

*Result:**Figures 24 and 25**.15\linewidth wide, in a .4\linewidth box.***Figure 24: A `\keyfig[W]` with `wlw`**

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Duis fringilla tristique neque. Sed interdum libero ut metus. Pellentesque placerat. Nam rutrum augue a leo. Morbi sed elit sit amet ante lobortis sollicitudin. Praesent blandit blandit mauris. Praesent lectus tellus, aliquet aliquam, luctus a, egestas a, turpis. Mauris lacinia lorem sit amet ipsum. Nunc quis urna dictum turpis accumsan semper.

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Etiam lobortis facilisis sem. Nullam nec mi et neque pharetra sollicitudin. Praesent imperdiet mi nec ante. Donec ullamcorper, felis non sodales commodo, lectus velit ultrices augue, a dignissim nibh lectus placerat pede. Vivamus nunc nunc, molestie ut, ultricies vel, semper in, velit. Ut porttitor. Praesent in sapien.

*1cm wide, in a 3cm box.***Figure 25: A `\keyfig[W]` with `ww`**

libero ut metus. Pellentesque placerat. Nam rutrum augue a leo. Morbi sed elit sit amet ante lobortis sollicitudin. Praesent blandit blandit mauris. Praesent lectus tellus, aliquet aliquam, luctus a, egestas a, turpis. Mauris lacinia lorem sit amet ipsum. Nunc quis urna dictum turpis accumsan semper.

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Etiam lobortis facilisis sem. Nullam nec mi et neque pharetra sollicitudin. Praesent imperdiet mi nec ante. Donec ullamcorper, felis non sodales commodo, lectus velit ultrices augue, a dignissim nibh lectus placerat pede. Vivamus nunc nunc, molestie ut, ultricies vel, semper in, velit. Ut porttitor. Praesent in sapien. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Duis fringilla tristique neque. Sed interdum



Figure 26: Custom-framed image

Figure 27: Custom loosely-framed box

2.5.8 Custom frames

Example 29: Custom frames with mdframed

Code:

```
\renewcommand{\KFLTtightframe}[1]{%
\begin{minipage}{\KFLTimageboxwidth}
\begin{mdtightframe}%
#1
\end{mdtightframe}%
\end{minipage}
}
\setlength{\KFLTtightframewidth}{1pt}

\renewcommand{\KFLTlooseframe}[1]{%
\begin{mdlooseframe}[leftmargin=1.5in,rightmargin=1.5in]%
#1
\end{mdlooseframe}%
}
\setlength{\KFLTlooseframewidth}{4pt}

\keyfig{ft,c=Custom-framed image,l=fig:customframe,r=90}{image}
\keyfigbox{f,c=Custom loosely-framed box,
l=fig:customlooseframe}{A loosely-framed box.}
```

Result:

Figures 26 and 27

⚠ Pkg mdframed
mdframed width

Example 29 shows custom frames created with the `mdframed` package along with `tikz`. Note that `mdframed` uses the full `\linewidth` even if the left/right margins are explicitly set, which causes extra vertical space when rotated. Because of this, the framed object is enclosed inside a minipage whose width is precomputed based on the object itself, then set in `\KFLTimageboxwidth`. Any shadow may fall outside this




Figure 28: Custom shadow




Figure 29: Custom loosely-framed shadow

box.

See section 2.6.1 for more details.

Example 30: Custom shadows with fancybox

Code:

```
\renewcommand{\KFLTtightframe}[1]{%
\setlength{\fboxrule}{.4pt}
\setlength{\fboxsep}{0pt}
\setlength{\shadowsize}{2pt}
\shadowbox{#1}%
}
\setlength{\KFLTtightframewidth}{0.4pt}

\renewcommand{\KFLTlooseframe}[1]{%
\setlength{\fboxrule}{.4pt}
\setlength{\fboxsep}{3pt}
\setlength{\shadowsize}{2pt}
\shadowbox{#1}%
}
\setlength{\KFLTlooseframewidth}{3.4pt}


\keyfig{ft,c=Custom shadow,l=fig:customshadow}{image}
\keyfigbox{f,c=Custom loosely-framed shadow,lw=.5,
l=fig:customlooseshadow}{A loosely-framed shadow box.}
```

Result:


Figures 28 and 29

Pkg fancybox Example 30 shows custom shadow frames created with the fancybox package. This combination respects lw and w.

See section 2.6.1 for more details.



MR. FIRST LAST III

*About the illustration.***Figure 30: Artist's name — image**


MR. LAST

Figure 31: Artist's name — arbitrary contents

2.5.9 Artist's name

Example 31: Artist's name — image*Code:*

```
\keyfig{ft,ap=Mr.,af=First,al=Last,as={~III},
tc={\textit{About the illustration.}},
c=Artist's name --- image,l=fig:artist}{image}
```

*Result:**Figure 30*

Example 32: Artist's name — arbitrary contents*Code:*

```
\tdartistright
\begin{keyfigure}{f,ap=Mr.,al=Last,
c=Artist's name --- arbitrary contents,l=fig:artistpar}
\centering Some text, a quotation, a TikZ\ diagram ---
anything not an image file.
\end{keyfigure}
\tdartistcenter
```

*Result:**Figure 31*

The artist's name and optional prefix/suffix are printed below the figure, and an index entry is made for the name in (Last, First) format, or (Last) if there is no first name. If the `tocdata` package is loaded, the artist's name is also added to the List of Figures, and the `tocdata \tdname...` macros may be used to align the name.

An image.

a: Artist's First Work



Commentary about the work.

b: Artist's Second Work

PREFIX FIRST LAST, SUFFIX

Some fully-justified text just for illustrative purposes, in case you have use for long explanations. This text may be the full \linewidth in size.

Multiple paragraphs of text are allowed.

Figure 32: Artist's collection

Example 33: Subfloats with an artist

Code:

```
\begin{keysubfigs}{2}{
  c=Artist's collection, l=fig:artistcollection,
  t={Some fully-justified text just for illustrative purposes,
    in case you have use for long explanations.
    This text may be the full \cs{linewidth} in size. \par
    Multiple paragraphs of text are allowed.},
  ap=Prefix,af=First,al=Last,as={, Suffix}
}
  \keyfig{c=Artist's First Work}{image}
  \keyfig{c=Artist's Second Work,
    tc={Commentary about the work.}}{image2}
\end{keysubfigs}
```

Result:

Figure 32

A group of figures may be placed into a subfloat container, which may have its own artist keys and additional text. Furthermore, each subfloat inside the collection may also have its own artist tags and additional text.

2.6 Customization

2.6.1 Custom frames

There are two user-redefinable framing macros:

`\KFLTtightframe` and `\KFLTlooseframe`

A float's contents are placed into a box, which is passed to either of these two macros depending on the key `f` or `tf`.

Each macro takes one argument and frames it.

Each macro has a associated L^AT_EX lengths:

`\KFLTtightframewidth` and `\KFLTlooseframewidth`

These lengths must be redefined to the expected total frame width, equal to the frame thickness plus separation.

The default definitions are:

```
\newcommand{\KFLTtightframe}[1]{%
  \setlength{\fboxsep}{0pt}%
  \setlength{\fboxrule}{.4pt}%
  \fbox{#1}%
}
\setlength{\KFLTtightframewidth}{.4pt}

\newcommand{\KFLTlooseframe}[1]{%
  \setlength{\fboxsep}{3pt}%
  \setlength{\fboxrule}{.4pt}%
  \fbox{#1}%
}
\setlength{\KFLTlooseframewidth}{3.4pt}
```

See example 29 for an example created with the `mdframed` package, and example 30 for an example created with the `fancybox` package.

2.6.2 Distance between floats and rows

rows too close/far To spread out the distance between floats and/or rows of floats on a busy page, the following settings may be changed. The settings used in this documentation are:

```
\setlength{\floatsep}{5ex plus 1ex minus 1ex}
\setlength{\dblfloatsep}{5ex plus 1ex minus 1ex}
```


2.6.3 Formatting the captions

To modify the typesetting of the captions, see the `caption` package. The settings used in this documentation are:

```
% default applied to margin floats:
\captionsetup{labelfont={small,bf},textfont={small,bf}}

\captionsetup[figure]{
  style=default, justification=centering,
  margin=0pt, parskip=0pt, skip=2ex,
  labelfont={small,bf},textfont={small,bf}
}

\captionsetup[table]{
  style=default, justification=centering,
  margin=0pt, parskip=0pt, skip=1ex,
  labelfont={small,bf},textfont={small,bf}
}

\captionsetup[subfigure]{
  style=default, justification=centering,
  margin=0pt, parskip=0pt, skip=2ex,
  labelfont={small},textfont={small}
}

\captionsetup[subtable]{
  style=default, justification=centering,
  margin=0pt, parskip=0pt, skip=1ex,
  labelfont={small},textfont={small}
}
```


3 Code

3.1 Older packages

Ensure that tocdata, if loaded, is new enough:

```

1 \@ifpackageloaded{tocdata}{
2   \@ifpackagelater{tocdata}{2019/03/21}{}{
3     \PackageError{keyfloat}
4       {%
5         The tocdata package is out of date.\MessageBreak
6         Update to tocdata v2.02 2019/03/21 or later.\MessageBreak
7         to use use this version of keyfloat%
8       }
9     {%
10      Please update the tocdata package. It's worth it!%
11    }
12  }
13 }{}

```

3.2 Prohibited packages

Prohibits the use of a certain other packages.

`\KFLT@prohibitpackage` $\{\langle packagename \rangle\}$

```

14 \newcommand*{\KFLT@prohibitpackage}[2]{%
15 \@ifpackageloaded{#1}
16 {
17   \PackageError{keyfloat}
18   {%
19     The keyfloat package conflicts with the #1.\MessageBreak
20     package. Remove #1 to use keyfloat.\MessageBreak
21     Alternative(s):.\MessageBreak
22     \space\space#2%
23   }
24   {%
25     Keyfloat uses the caption, subcaption, newfloat, and wrapfig packages.%
26   }
27 }{}
28 }

```

`\KFLT@prohibitpackage` $\{\langle packagename \rangle\}$

Prohibits the use of another package, both now and also `\AtBeginDocument`.

```
29 \newcommand*\KFLT@prohibitpackage}[2]{
30   \KFLT@prohibitpackage{#1}{#2}
31   \AtBeginDocument{\KFLT@prohibitpackage{#1}{#2}}
32 }
```

The list of prohibited packages:

```
33 \KFLT@prohibitpackage{floatrow}{caption and subcaption}
34 \KFLT@prohibitpackage{subfig}{subcaption}
35 \KFLT@prohibitpackage{subfigure}{subcaption}
36 \KFLT@prohibitpackage{subfloat}{subcaption}
37 \KFLT@prohibitpackage{floatflt}{wrapfig}
```

3.3 Required packages

Pkg etoolbox v2.6 or later for `\BeforeBeginEnvironment`, `\AfterEndEnvironment`

```
38 \RequirePackage{etoolbox}[2011/01/03]%
```

Pkg xparse Argument processing:

```
39 \RequirePackage{xparse}
```

Pkg keyval Key processing:

```
40 \RequirePackage{xkeyval}
```

Pkg graphicx For `\includegraphics` and `rotating`:

```
41 \RequirePackage{graphicx}
```

Pkg caption Handles all caption-related functions:

```
42 \RequirePackage{caption}[2010/10/31]% v3.2 to support \phantomcaption
```

Pkg subcaption Derived from `caption`, used to handle subfloats:

```
43 \RequirePackage{subcaption}
```

Pkg calc Used to compute box width minus frame sep and width.

```
44 \RequirePackage{calc}
```


Pkg rotating Provides rotation via the turn environment:

```
45 \RequirePackage{rotating}
```

Pkg placeins Provides

to process existing floats before adding new ones.

```
46 \RequirePackage{placeins}
```

Pkg wrapfig Provides figure wrapping code.

```
47 \RequirePackage{wrapfig}
```

Pkg gettitlestring Used by `hyperref` and `nameref`.

Expand names used in titles:

```
48 \PassOptionsToPackage{expand}{gettitlestring}
```

Rows of floats are created by a simple `minipage` environment, instead of relying on a preexisting package. This proved to be advantageous when support was added for multiple rows in one environment.

3.4 In-line figures and tables

These macros are commonly used by others.

Env tablehere Place a table exactly [H].

```
49 \ProvideDocumentEnvironment{tablehere}{}
50 {%
51   \vskip\intextsep\noindent%
52   \minipage{\linewidth}%
53   \def\capttype{table}%
54   \normalcolor\reset@font\normalsize%
55 }%
56 {\endminipage\vskip\intextsep}%
```

Env figurehere Place a figure exactly [H].

```
57 \ProvideDocumentEnvironment{figurehere}{}
58 {%
59   \vskip\intextsep\noindent%
60   \minipage{\linewidth}%
```



```

61 \def\@capttype{figure}%
62 \normalcolor\reset@font\normalsize%
63 }%
64 {\endminipage\vskip\intextsep}%

```

3.5 Row counting and control

Used to count position and wrap at end of each row.

Ctrl KFLT@numcols Columns per row.

```
65 \newcounter{KFLT@numcols}
```

Ctrl KFLT@thiscol Column currently processing. 0 if not yet in a keyfloats or subfloat.

```
66 \newcounter{KFLT@thiscol}
```

Len \KFLT@rowboxwidth How wide is each box in the row.

```
67 \newlength{\KFLT@rowboxwidth}
```

3.6 Float key handling

Bool KFLT@cont Continued float?

```
68 \newboolean{KFLT@cont}
```

Key [main] cont Continued float?

```
69 \define@key{KFLT@keys}{cont}[true]{\setboolean{KFLT@cont}{#1}}
```

\KFLT@c Caption storage

```
70 \newcommand{\KFLT@c}{}%
```

Bool KFLT@cstar Starred caption?

```
71 \newboolean{KFLT@cstar}
```

Key [main] c Caption

```

72 \define@key{KFLT@keys}{c}{%
73 \renewcommand{\KFLT@c}{#1}\setboolean{KFLT@cstar}{false}%
74 }

```


Key [main] cstar Caption starred?

```
75 \define@key{KFLT@keys}{cstar}{%
76   \renewcommand{\KFLT@c}{#1}\setboolean{KFLT@cstar}{true}%
77 }
```

Key [main] sc Short caption

```
78 \define@key{KFLT@keys}{sc}{%
79   \renewcommand{\KFLT@sc}{#1}%
80   \setboolean{KFLT@scgiven}{true}%
81 }
```

\KFLT@sc Short caption storage

```
82 \newcommand{\KFLT@sc}{}%
```

Bool KFLT@scgiven Was a short caption given?

```
83 \newboolean{KFLT@scgiven}
```

\KFLT@type Float type: “figure”, “table”

```
84 \newcommand*\KFLT@type{}
```

Key [main] 1 Label

```
85 \define@key{KFLT@keys}{1}{\renewcommand{\KFLT@1}{#1}}
```

\KFLT@1 Label storage

```
86 \newcommand*\KFLT@1{}
```

For the artist/author keys:

Key [main] ap Artist prefix

```
87 \define@key{KFLT@keys}{ap}{\renewcommand{\KFLT@ap}{#1}}
```

\KFLT@ap Storage for artist prefix

```
88 \newcommand*\KFLT@ap{}
```


Key [main] af Artist first name

89 \define@key{KFLT@keys}{af}{\renewcommand{\KFLT@af}{#1}}

\KFLT@af Storage for artist first name

90 \newcommand*{\KFLT@af}{}

Key [main] al Artist last name

91 \define@key{KFLT@keys}{al}{\renewcommand{\KFLT@al}{#1}}

\KFLT@al Storage for artist last name

92 \newcommand*{\KFLT@al}{}

Key [main] as Artist suffix

93 \define@key{KFLT@keys}{as}{\renewcommand{\KFLT@as}{#1}}

\KFLT@as Storage for artist suffix

94 \newcommand*{\KFLT@as}{}

Key [main] aup Author prefix

95 \define@key{KFLT@keys}{aup}{\renewcommand{\KFLT@aup}{#1}}

\KFLT@aup Storage for author prefix

96 \newcommand*{\KFLT@aup}{}

Key [main] auf Author first name

97 \define@key{KFLT@keys}{auf}{\renewcommand{\KFLT@auf}{#1}}

\KFLT@auf Storage for author first name

98 \newcommand*{\KFLT@auf}{}

Key [main] aul Author last name

99 \define@key{KFLT@keys}{aul}{\renewcommand{\KFLT@aul}{#1}}

\KFLT@a1 Storage for author last name

100 \newcommand*{\KFLT@a1}{}

Key [main] aus Author suffix

101 \define@key{KFLT@keys}{aus}{\renewcommand{\KFLT@aus}{#1}}

\KFLT@aus Storage for author suffix

102 \newcommand*{\KFLT@aus}{}

\KFLT@textalign Storage for text alignment.

Used for the additional text in the float.

103 \newcommand*{\KFLT@textalign}{}

\KFLT@t Additional text storage

Used for the additional text in the float.

104 \newcommand{\KFLT@t}{}

Create replacement macros in case tocddata is not loaded:

```
105 \providecommand{\tdartisttextjustify}{}
106 \providecommand{\tdartisttextcenter}{}
107 \providecommand{\tdartisttextleft}{}
108 \providecommand{\tdartisttextright}{}
109 \providecommand{\tdauthortextjustify}{}
110 \providecommand{\tdauthortextcenter}{}
111 \providecommand{\tdauthortextleft}{}
112 \providecommand{\tdauthortextright}{}
113 \providecommand{\tdartistjustify}{}
114 \providecommand{\tdartistcenter}{}
115 \providecommand{\tdartistleft}{}
116 \providecommand{\tdartistright}{}
117 \providecommand{\tdauthorjustify}{}
118 \providecommand{\tdauthorcenter}{}
119 \providecommand{\tdauthorleft}{}
120 \providecommand{\tdauthorright}{} 
```

Key [main] t Additional text, justified alignment.


```

121 \define@key{KFLT@keys}{t}{%
122   \renewcommand{\KFLT@t}{#1}%
123   \renewcommand{\KFLT@textalign}{}%
124 }

```

Key [main] tc Additional text, centered alignment.

```

125 \define@key{KFLT@keys}{tc}{%
126   \renewcommand{\KFLT@t}{#1}%
127   \renewcommand{\KFLT@textalign}{\centering}%
128 }

```

Key [main] tr Additional text, aligned to the right.

```

129 \define@key{KFLT@keys}{tr}{%
130   \renewcommand{\KFLT@t}{#1}%
131   \renewcommand{\KFLT@textalign}{\raggedleft}%
132 }

```

Key [main] tl Additional text, aligned to the left.

```

133 \define@key{KFLT@keys}{tl}{%
134   \renewcommand{\KFLT@t}{#1}%
135   \renewcommand{\KFLT@textalign}{\raggedright}%
136 }

```

Key [main] lw Fraction of \linewidth

```

137 \define@key{KFLT@keys}{lw}{%
138   \renewcommand{\KFLT@lw}{#1}%
139   \setlength{\KFLT@w}{0pt}%
140 }

```

\KFLT@lw Fraction of linewidth storage: “.5”

```

141 \newcommand*{\KFLT@lw}{}

```

Key [main] w Fixed width

```

142 \define@key{KFLT@keys}{w}{%
143   \setlength{\KFLT@w}{#1}%
144   \renewcommand{\KFLT@lw}{}%
145 }

```

\KFLT@w Width storage: “3cm”

```

146 \newlength{\KFLT@w}

```


Key [main] h Fixed height

```
147 \define@key{KFLT@keys}{h}{\setlength{KFLT@h}{#1}}
```

\KFLT@h Height storage: “2in”

```
148 \newlength{KFLT@h}
```

Key [main] s Scale

```
149 \define@key{KFLT@keys}{s}{\renewcommand{KFLT@s}{#1}}
```

\KFLT@s Scale storage: “3”

```
150 \newcommand*{KFLT@s}{1}
```

Key [main] r Angle. 90 is counter-clockwise 90 degrees.

```
151 \define@key{KFLT@keys}{r}{\renewcommand{KFLT@r}{#1}}
```

\KFLT@r Angle storage: “90”

```
152 \newcommand*{KFLT@r}{0}
```

Key [main] f Frame the image with \KFLTlooseframe.

```
153 \define@key{KFLT@keys}{f}[true]{\setboolean{KFLT@f}{#1}}
```

Bool KFLT@f Frame the image?

```
154 \newboolean{KFLT@f}
```

Key [main] ft Tightly frame the image using \KFLTtightframe. This is useful for photographs, or diagrams which already have built-in margins.

```
155 \define@key{KFLT@keys}{ft}[true]{\setboolean{KFLT@ft}{#1}}
```

Bool KFLT@ft Tightly frame the image?

```
156 \newboolean{KFLT@ft}
```

Key [main] stretch Set \arraystretch inside the table environment.

```
157 \define@key{KFLT@keys}{stretch}{\renewcommand{KFLT@stretch}{#1}}
```


\KFLT@stretch Storage for \arraystretch.

```
158 \newcommand*{\KFLT@stretch}{1}
```

Key [main] mo Set vertical offset for a margin float.

```
159 \define@key{KFLT@keys}{mo}{\setlength{\KFLT@mo}{#1}}
```

\KFLT@mo Storage for the vertical margin offset.

```
160 \newlength{\KFLT@mo}
```

Key [main] wn Set wrap number of narrow lines for a wrapped float.

```
161 \define@key{KFLT@keys}{wn}{\renewcommand{\KFLT@wn}{#1}}
```

\KFLT@wn Storage for the wrap placement.

```
162 \newcommand{\KFLT@wn}{} 
```

Key [main] wp Set wrap placement for a wrapped float.

See table 3 on page 15.

```
163 \define@key{KFLT@keys}{wp}{\renewcommand{\KFLT@wp}{#1}}
```

\KFLT@wp Storage for the wrap placement.

```
164 \newcommand{\KFLT@wp}{0}
```

Key [main] wo Set wrap overhang for a wrapped float.

```
165 \define@key{KFLT@keys}{wo}{\renewcommand{\KFLT@wo}{#1}}
```

\KFLT@wo Storage for the wrap placement.

```
166 \newcommand{\KFLT@wo}{\wrapoverhang}
```

Key [main] wlw Wrapped figure, fraction of \linewidth

```
167 \define@key{KFLT@keys}{wlw}{%
168   \renewcommand{\KFLT@wlw}{#1}%
169   \setlength{\KFLT@ww}{0pt}%
170 }
```


`\KFLT@w1w` Wrapped figure, fraction of linewidth storage: “.5”

```
171 \newcommand*{\KFLT@w1w}{}%
```

Key [main] `ww` Wrapped figure, fixed width

```
172 \define@key{KFLT@keys}{ww}{%
173   \setlength{\KFLT@ww}{#1}%
174   \renewcommand{\KFLT@w1w}{}}%
175 }
```

`\KFLT@ww` Wrapped figure, width storage: “3cm”

```
176 \newlength{\KFLT@ww}
```

Key [main] `va` Set vertical alignment of the outermost minipage container.

```
177 \define@key{KFLT@keys}{va}{\renewcommand{\KFLT@va}{#1}}
```

`\KFLT@va` Storage for the vertical alignment.

```
178 \newcommand{\KFLT@va}{c}
```

3.7 Nesting control

Ctrl `KFLT@keyfloatdepth` Depth inside a keyfigs environment

```
179 \newcounter{KFLT@keyfloatdepth}
180 \setcounter{KFLT@keyfloatdepth}{0}
```

Bool `KFLT@inkeysubfloats` Inside a keysubfigs environment?

```
181 \newboolean{KFLT@inkeysubfloats}
182 \setboolean{KFLT@inkeysubfloats}{false}
```

3.8 Subfloat key handling

These keys are for the container holding a collection of subfigures.

Bool `KFLT@subgrpcont` Continued float?

```
183 \newboolean{KFLT@subgrpcont}{}%
```


Key [subfloat container] cont Continued float

```
184 \define@key{KFLT@subgrpkeys}{cont}[true]{%
185   \setboolean{KFLT@subgrpcont}{#1}%
186 }
```

\KFLT@subgrpc Sub-caption storage

```
187 \newcommand{\KFLT@subgrpc}{{}}
```

Bool KFLT@subgrpcstart Sub-caption starred?

```
188 \newboolean{KFLT@subgrpcstar}
```

Key [subfloat container] c Caption

```
189 \define@key{KFLT@subgrpkeys}{c}{%
190   \renewcommand{\KFLT@subgrpc}{#1}\setboolean{KFLT@subgrpcstar}{false}%
191 }
```

Key [subfloat container] cstar Starred caption?

```
192 \define@key{KFLT@subgrpkeys}{cstar}{%
193   \renewcommand{\KFLT@subgrpc}{#1}\setboolean{KFLT@subgrpcstar}{true}%
194 }
```

Key [subfloat container] sc Short caption

```
195 \define@key{KFLT@subgrpkeys}{sc}{%
196   \renewcommand{\KFLT@subgrpsc}{#1}%
197   \setboolean{KFLT@subgrpscgiven}{true}%
198 }
```

\KFLT@subgrpsc Sub-shortcaption storage

```
199 \newcommand{\KFLT@subgrpsc}{{}}
```

Bool KFLT@subgrpscgiven Sub-shortcaption was given?

```
200 \newboolean{KFLT@subgrpscgiven}
```

\KFLT@subgrptype Subfloats collection type storage: “figure”, “table”

```
201 \newcommand*\KFLT@subgrptype{{}}
```


Key [subfloat container] 1 Label

```
202 \define@key{KFLT@subgrpkeys}{l}{\renewcommand{\KFLT@subgrpl}{#1}}
203 \newcommand*{\KFLT@subgrpl}{{}}
```

\KFLT@subgrptextalign Storage for text alignment.

Used for the additional text in the float.

```
204 \newcommand*{\KFLT@subgrptextalign}{{}}
```

\KFLT@subgrpt Additional text storage

Used for the additional text in the float.

```
205 \newcommand{\KFLT@subgrpt}{{}}
```

Key [subfloat container] t Additional text — full justification

```
206 \define@key{KFLT@subgrpkeys}{t}{%
207   \renewcommand{\KFLT@subgrpt}{#1}%
208   \renewcommand{\KFLT@subgrptextalign}{}%
209 }
```

Key [subfloat container] tc Additional text — center justification

```
210 \define@key{KFLT@subgrpkeys}{tc}{%
211   \renewcommand{\KFLT@subgrpt}{#1}%
212   \renewcommand{\KFLT@subgrptextalign}{\centering}%
213 }
```

Key [subfloat container] tl Additional text — aligned left

```
214 \define@key{KFLT@subgrpkeys}{tl}{%
215   \renewcommand{\KFLT@subgrpt}{#1}%
216   \renewcommand{\KFLT@subgrptextalign}{\raggedright}%
217 }
```

Key [subfloat container] tr Additional text — aligned right

```
218 \define@key{KFLT@subgrpkeys}{tr}{%
219   \renewcommand{\KFLT@subgrpt}{#1}%
220   \renewcommand{\KFLT@subgrptextalign}{\raggedleft}%
221 }
```

For the tocdata package:

Key [subfloat container]	ap	Artist prefix	222 \define@key{KFLT@subgrpkeys}{ap}{\renewcommand{\KFLT@subgrpap}{#1}}
	\KFLT@subgrpap	Storage for artist prefix	223 \newcommand*{\KFLT@subgrpap}{{}}
Key [subfloat container]	af	Artist first name	224 \define@key{KFLT@subgrpkeys}{af}{\renewcommand{\KFLT@subgrpaf}{#1}}
	\KFLT@subgrpaf	Storage for artist first name	225 \newcommand*{\KFLT@subgrpaf}{{}}
Key [subfloat container]	al	Artist last name	226 \define@key{KFLT@subgrpkeys}{al}{\renewcommand{\KFLT@subgrp al}{#1}}
	\KFLT@subgrp al	Storage for artist last name	227 \newcommand*{\KFLT@subgrp al}{{}}
Key [subfloat container]	as	Artist suffix	228 \define@key{KFLT@subgrpkeys}{as}{\renewcommand{\KFLT@subgrp as}{#1}}
	\KFLT@subgrp as	Storage for artist suffix	229 \newcommand*{\KFLT@subgrp as}{{}}
Key [subfloat container]	aup	Author prefix	230 \define@key{KFLT@subgrpkeys}{aup}{\renewcommand{\KFLT@subgrp aup}{#1}}
	\KFLT@subgrp aup	Storage for author prefix	231 \newcommand*{\KFLT@subgrp aup}{{}}
Key [subfloat container]	auf	Author first name	232 \define@key{KFLT@subgrpkeys}{auf}{\renewcommand{\KFLT@subgrp auf}{#1}}

\KFLT@subgrpaufl Storage for author first name

233 \newcommand*{\KFLT@subgrpaufl}{}

Key [subfloat container] au1 Author last name

234 \define@key{KFLT@subgrpkeys}{au1}{\renewcommand{\KFLT@subgrpau1}{#1}}

\KFLT@subgrpau1 Storage for author last name

235 \newcommand*{\KFLT@subgrpau1}{}

Key [subfloat container] aus Author suffix

236 \define@key{KFLT@subgrpkeys}{aus}{\renewcommand{\KFLT@subgrpau1}{#1}}

\KFLT@subgrpau1 Storage for author suffix

237 \newcommand*{\KFLT@subgrpau1}{}

3.9 Computing image width

Len \KFLT@imagewidth Computed width of the image

238 \newlength{\KFLT@imagewidth}

Len \KFLT@boxwidth Computed width of the container box

239 \newlength{\KFLT@boxwidth}

Len \KFLT@wrapwidth Computed width of the wrapped figure

240 \newlength{\KFLT@wrapwidth}

\KFLT@findwidths Figure out how wide to make an image and its container

241 \newcommand*{\KFLT@findwidths}{%

Default to a box of full \linewidth minus the potential frame:

242 \ifbool{KFLT@ft}% tight frame?

243 {\setlength{\KFLT@boxwidth}{\linewidth - 2\KFLT@tightframewidth}}%

244 {% not tight frame


```

245      \ifbool{KFLT@f}% loose frame?
246      {\setlength{KFLT@boxwidth}{\linewidth - 2\KFLTlooseframewidth}}%
247       {\setlength{KFLT@boxwidth}{\linewidth}}% no frame
248      }% not tight frame

```

Several width options exist. First see if width was given:

```

249      \ifdimgreater{KFLT@w}{0pt}%

```

Width was given:

```

250      {\setlength{KFLT@imagewidth}{KFLT@w}}%
251      {% width not given

```

Use full `\linewidth` or only a fraction:

```

252      \ifcempty{KFLT@lw}%
253      {\setlength{KFLT@imagewidth}{KFLT@boxwidth}}%
254      {\setlength{KFLT@imagewidth}{KFLT@lwKFLT@boxwidth}}%
255      }% width not given

```

The wrap width is the same as the image width, unless specified:

```

256      \ifdimgreater{KFLT@ww}{0pt}%

```

Width was given:

```

257      {%
258      \setlength{KFLT@wrapwidth}{KFLT@ww}}%
259      {% width not given

```

If `wlw`, use a fraction of line width, else if none given use the same as the image width.

```

260      \ifcempty{KFLT@wlw}%
261      {%
262      \setlength{KFLT@wrapwidth}{KFLT@imagewidth}}%
263      {%
264      \setlength{KFLT@wrapwidth}{KFLT@wlwKFLT@boxwidth}}%
265      }% width not given
266 }

```

3.10 Framing and rotation

A user-redefinable macro and length to tightly frame the contents.

`\KFLTtightframe` may be redefined to a macro which frames its contents. `\KFLTtightframewidth` should be redefined to the total width of the new frame and its separation.

`\KFLTtightframe` $\{\langle contents \rangle\}$

```
267 \newcommand{\KFLTtightframe}[1]{%
268   \setlength{\fboxsep}{0pt}%
269   \setlength{\fboxrule}{.4pt}%
270   \fbox{#1}%
271 }
272
```

Len `\KFLTtightframewidth` Must be set to the combined width of the tight frame and separation used by `\KFLTtightframe`.

```
273 \newlength{\KFLTtightframewidth}
274 \setlength{\KFLTtightframewidth}{.4pt}
```

`\KFLTlooseframe` $\{\langle contents \rangle\}$

A user-redefinable macro and length to loosely frame the contents.

`\KFLTlooseframe` may be redefined to a macro which frames its contents. `\KFLTlooseframewidth` should be redefine to the total width of the new frame and its separation.

```
275 \newcommand{\KFLTlooseframe}[1]{%
276   \setlength{\fboxsep}{3pt}%
277   \setlength{\fboxrule}{.4pt}%
278   \fbox{#1}%
279 }
```

Len `\KFLTlooseframewidth` Must be set to the combined width of the loose frame and separation used by `\KFLTlooseframe`.

```
280 \newlength{\KFLTlooseframewidth}
281 \setlength{\KFLTlooseframewidth}{3.4pt}
```

`\KFLT@frame` $\{\langle contents \rangle\}$

Frames the contents according to the `f` key. To be nested for further processing.

```
282 \newcommand{\KFLT@frame}[1]
283 {%
284   \ifbool{KFLT@ft}%
285     {\KFLTtightframe{#1}}%
286     {% not tightframe
287       \ifbool{KFLT@f}%
288         {\KFLTlooseframe{#1}}%
289         {#1}% no frame
```



```

290      }% not looseframe
291 }

```

KFLT@findenvboxwidth Figures the width of the contents of \KFLT@envbox plus the frame:

```

292 \newcommand{\KFLT@findenvboxwidth}{%
293   \settowidth{\KFLTimageboxwidth}{\usebox{\KFLT@envbox}}%
294   \ifbool{KFLT@ft}%
295     {\addtolength{\KFLTimageboxwidth}{2\KFLTtightframewidth}}%
296     {% not tightframe
297       \ifbool{KFLT@f}%
298         {\addtolength{\KFLTimageboxwidth}{2\KFLTlooseframewidth}}%
299         {}}% no frame
300   }% not looseframe
301 }

```

3.11 A graphics image from a file

\KFLT@onefigureimage {*<filename>*}

Create an image with size, frame, and turn.

```

302 \NewDocumentCommand{\KFLT@onefigureimage}{m}%
303 {%

```

Several possible combinations of linewidth, width, and height are available, and each is treated separately. Scaling and width/height are done first, then framing, then rotation.

```

304   \begin{lrbox}{\KFLT@envbox}%

```

Handle the lw key. If lw is used, width and height are ignored.

```

305   \ifdefempty{\KFLT@lw}%
306   {% not linewidth

```

Handle the w key, which may be used along with the h key:

```

307       \ifdimgreater{\KFLT@w}{0pt}%
308       {% width is given
309       \ifdimgreater{\KFLT@h}{0pt}%

```

Width and height are both given:

```

310       {% w and h

```



```

311          \includegraphics%
312          [scale=\KFLT@s,%
313          width=\KFLT@imagewidth,height=\KFLT@h]{#1}%
314      }% w and h

```

Only width:

```

315      {% only w
316          \includegraphics%
317          [scale=\KFLT@s,width=\KFLT@imagewidth]{#1}%
318      }% only w
319      }% width is given

```

Width was not given, so maybe handle h alone:

```

320      {% width is not given
321          \ifdimgreater{\KFLT@h}{0pt}%

```

h was given:

```

322          {\includegraphics[scale=\KFLT@s,height=\KFLT@h]{#1}}%

```

If none were given, use the image's natural size:

```

323          {\includegraphics[scale=\KFLT@s]{#1}}%
324      }% width is not given
325      }% not linewidth
326      {% linewidth given
327          \includegraphics[scale=\KFLT@s,width=\KFLT@imagewidth]{#1}%
328      }%
329      \end{lrbox}%
330      \unskip%
331      \KFLT@findenvboxwidth%
332      \begin{turn}{\KFLT@r}%
333      \KFLT@frame{\usebox{\KFLT@envbox}}%
334      \unskip%
335      \end{turn}%
336 }

```

3.12 Printing the caption

```
\KFLT@dosimplecaption {<star?>} {<short cap or -NO VALUE->} {<caption>}
```

Calls `\caption` depending on several combinations of star and short captions being given.

```
337 \NewDocumentCommand{\KFLT@dosimplecaption}{m m m}
```



```

338 {%
339   \unskip%
340   \IfBooleanTF{#1}% star?
341     {\IfValueTF{#2}{\caption*{#2}{#3}}{\caption*{#3}}}%
342     {\IfValueTF{#2}{\caption{#2}{#3}}{\caption{#3}}}%
343 }

```

There are two versions of \KFLT@docaption, depending on whether tocdata is loaded.

```

344 \ifpackage{tocdata}
345 {% tocdata loaded

```

```

\KFLT@docaption 1: artist/author {\langle 2: empty or "u" \rangle} {\langle 3: star? \rangle} {\langle 4: short caption \rangle} {\langle 5: caption \rangle} {\langle 6:
empty or "subgrp" \rangle}

```

```

346 \newcommand*\KFLT@docaption}[6]{%

```

(tocdata does not expand its text argument before checking for empty.)

```

347 \addvspace{\smallskipamount}%
348 \ifcseempty{KFLT@#6t}{%
349   \IfBooleanTF{#3}%
350   {%
351     \csuse{caption#1}*{#4}{#5}%
352     [%
353       [\csuse{KFLT@#6a#2p}]%
354       {\csuse{KFLT@#6a#2f}}%
355       {\csuse{KFLT@#6a#2l}}%
356       [\csuse{KFLT@#6a#2s}]%
357     ]}%
358     \csuse{caption#1}[#4]{#5}%
359     [%
360       [\csuse{KFLT@#6a#2p}]%
361       {\csuse{KFLT@#6a#2f}}%
362       {\csuse{KFLT@#6a#2l}}%
363       [\csuse{KFLT@#6a#2s}]%
364     ]}%
365 }{%
366   \ifcsstring{KFLT@#6textalign}{\csuse{td#1textjustify}}{%
367     \ifcsstring{KFLT@#6textalign}{\centering}{\csuse{td#1textcenter}}{%
368       \ifcsstring{KFLT@#6textalign}{\raggedleft}{\csuse{td#1textright}}{%
369         \ifcsstring{KFLT@#6textalign}{\raggedright}{\csuse{td#1textleft}}{%
370           \IfBooleanTF{#3}%
371           {%
372             \csuse{caption#1}*{#4}{#5}%
373             [%
374               [\csuse{KFLT@#6t}]%
375               [\csuse{KFLT@#6a#2p}]%
376               {\csuse{KFLT@#6a#2f}}%

```



```

376         {\csuse{KFLT@#6a#2l}}%
377         [\csuse{KFLT@#6a#2s}]%
378     }{%
379         \csuse{caption#1}[\#4]{\#5}%
380         [\csuse{KFLT@#6t}]%
381         [\csuse{KFLT@#6a#2p}]%
382         {\csuse{KFLT@#6a#2f}}%
383         {\csuse{KFLT@#6a#2l}}%
384         [\csuse{KFLT@#6a#2s}]%
385     }%
386 }%
387 }

```

`\KFLT@docaption` * [*2:short caption*] {*3:caption*} {*4: empty or “subgrp”*}

Depending on whether the `tocdata` package is present, and an artist is specified, use either `\caption` or `\captionartist`.

The fourth argument is `{}` if a regular float, or `subgrp` if `keysubfigs` or `keysubtabs`.

See Table 2 for the possible combinations of the caption-related keys: `c`, `cstar`, and `sc`.

With `tocdata`:

```

388 \NewDocumentCommand{\KFLT@docaption}{s o m m}
389 {%

```

Is the last name empty? Assume no artist if so.

```

390     \ifcempty{KFLT@#4al}%
391     {% figure w/o artist
392         \ifcempty{KFLT@#4aul}%
393         {% figure w/o artist or author

```

A figure without an artist or author uses the simple caption.

```

394         \KFLT@dosimplecaption{\#1}{\#2}{\#3}%
395     }% figure w/o artist or author

```

A figure with an author uses the `tocdata \captionauthor` macro, which also creates an index entry.

```

396     {% figure w/ author
397         \KFLT@docaption{author}{u}{\#1}{\#2}{\#3}{\#4}%
398     }% figure w/ author
399 }% figure w/o artist
400 {% figure with an artist

```


A figure with an artist uses the `tocdata \captionartist` macro, which also creates an index entry.

```
401      \KFLT@docaption{artist}{\#1}{\#2}{\#3}{\#4}%
402    }% figure with an artist
403 }% KFLT@tocdata
404 }% tocdata loaded
405 {% no tocdata
```

Without `tocdata`:

```
\KFLT@docaption * [\langle 2:short caption \rangle] {\langle 3:caption \rangle} {\langle 4: empty or “subgrp” \rangle}
```

```
406 \NewDocumentCommand{\KFLT@docaption}{s o m m}
407 {%
```

If `tocdata` is not loaded, use a simple caption.

```
408      \KFLT@dosimplecaption{\#1}{\#2}{\#3}%
```

Create an index entry depending on whether there is a last, first name:

```
409      \ifcempty{KFLT@#4a1}%
410      {%
411        \ifcempty{KFLT@#4a1}%
412        {}%
413        {% yes author
414          \ifcempty{KFLT@#4auf}%
415          {\index{\csuse{KFLT@#4a1}}}%
416          {\index{\csuse{KFLT@#4a1}, \csuse{KFLT@#4auf}}}%
417        }% yes author
418      }% no artist
419      {% yes artist
420        \ifcempty{KFLT@#4af}%
421        {\index{\csuse{KFLT@#4a1}}}%
422        {\index{\csuse{KFLT@#4a1}, \csuse{KFLT@#4af}}}%
423      }% yes artist
424 }% KFLT@docaption
425 }% no tocdata
```

```
\KFLT@caption {\langle empty or “subgrp” \rangle}
```

Caption-creation logic.

The argument is `{}` if a regular float, or `subgrp` if `keysubfigs` or `keysubtabs`.

See Table 2 for the possible combinations of the caption-related keys: c, cstar, and sc.

```
426 \newcommand{\KFLT@caption}[1]{%
```

A starred caption is printed but not numbered.

```
427 \ifbool{KFLT@#1cstar}% starred caption?
```

This is a starred caption:

```
428 {%starred caption
```

A key given as cstar={} yields a float with no caption at all.

```
429 \ifcempty{KFLT@#1c}% cstar={}?  
430 {}%
```

Non-empty starred caption might have a LOF entry if it has a short caption sc key:

```
431 {% non-empty starred caption  
432 \ifcempty{KFLT@#1sc}%
```

No sc short caption, but there is a cstar, so no LOF entry:

```
433 {}%
```

Both cstar and sc were given, so add a LOF entry:

```
434 {% non-empty cstar and sc:  
435 \edef\KFLT@listtype{\csuse{KFLT@#1type}}%  
436 \addcontentsline{\csuse{ext@KFLT@listtype}}%  
437 {\csuse{KFLT@#1type}}{\KFLT@sc}%  
438}% non-empty cstar and sc
```

cstar was given, so create an unnumbered caption:

```
439 \KFLT@docaption*{\csuse{KFLT@#1c}}{#1}%  
440}%  
441}% starred caption
```

Unstarred caption c was given, so number this float:

```
442 {% unstarred caption  
443 \ifcempty{KFLT@#1sc}%  
444 {% no short cap  
445 \KFLT@docaption{\csuse{KFLT@#1c}}{#1}%
```



```

446      }% no short cap
447      {% short cap
448          \KFLT@docaption[\csuse{KFLT@#1sc}]%
449          {\csuse{KFLT@#1c}}{#1}%
450      }% short cap

```

Optional label:

```

451      \ifcsemt{KFLT@#1l}%
452      {}%
453      {\label{\csuse{KFLT@#1l}}}%
454      }% unstarred caption
455 }

```

3.13 Defaults for a new float

\KFLT@defaults Defaults all settings before reading the keys.

```

456 \newcommand*\KFLT@defaults{%
457     \setboolean{KFLT@cont}{false}%
458     \renewcommand{\KFLT@c}{}%
459     \setboolean{KFLT@cstar}{false}%
460     \renewcommand{\KFLT@sc}{}%
461     \setboolean{KFLT@scgiven}{false}%
462     \renewcommand{\KFLT@type}{figure}%
463     \renewcommand{\KFLT@l}{}%
464     \renewcommand{\KFLT@ap}{}%
465     \renewcommand{\KFLT@af}{}%
466     \renewcommand{\KFLT@a1}{}%
467     \renewcommand{\KFLT@as}{}%
468     \renewcommand{\KFLT@aup}{}%
469     \renewcommand{\KFLT@aupf}{}%
470     \renewcommand{\KFLT@a1l}{}%
471     \renewcommand{\KFLT@aus}{}%
472     \renewcommand{\KFLT@t}{}%
473     \renewcommand{\KFLT@textalign}{}%
474     \renewcommand{\KFLT@lw}{}%
475     \setlength{\KFLT@w}{0pt}%
476     \setlength{\KFLT@h}{0pt}%
477     \renewcommand{\KFLT@s}{1}%
478     \renewcommand{\KFLT@r}{0}%
479     \setboolean{KFLT@f}{false}%
480     \setboolean{KFLT@ft}{false}%
481     \renewcommand{\KFLT@stretch}{1}%
482     \setlength{\KFLT@mo}{-1.2ex}%
483     \renewcommand{\KFLT@wn}{}%
484     \renewcommand{\KFLT@wp}{0}%
485     \renewcommand{\KFLT@wo}{\wrapoverhang}%

```



```

486 \renewcommand{\KFLT@w1w}{}%
487 \setlength{\KFLT@ww}{0pt}%
488 \renewcommand{\KFLT@va}{c}%
489 }

```

3.14 Row start/end processing

`\KFLT@maybestartfloatrow` Counts rows

After ending a preexisting row, move to the next row. The use of `\defcounter` makes this counter change local.

```

490 \newcommand*\KFLT@maybestartfloatrow{%
491   \KFLT@maybeendfloatrow%
492   \defcounter{KFLT@thiscol}{\value{KFLT@thiscol}+1}%
493 }

```

`\KFLT@maybeendfloatrow` Counts rows

Adds vertical space then resets to allow the start of a new row. The use of `\defcounter` makes this counter change local.

```

494 \newcommand*\KFLT@maybeendfloatrow{%
495   \ifnumless{\value{KFLT@thiscol}}{\value{KFLT@numcols}}%
496   {}% thiscol < numcols
497   {% >=
498     \par%
499     \addvspace{.75\floatsep}%
500     \defcounter{KFLT@thiscol}{0}%
501   }%
502 }%

```

3.15 Key environment helper macros

`\KFLT@trackrows` Tracks and spaces rows and columns.

```

503 \newcommand{\KFLT@trackrows}%
504 {%

```

If are nested inside a keyfloats or a subfloat:

```

505   \ifboolexpr{%
506     test {\ifnumgreater{\value{KFLT@keyfloatdepth}}{0}} or%
507     bool{KFLT@inkeysubfloats}%
508   }%
509   {% nested

```


Tracks row start and end:

```
510      \KFLT@maybestartfloatrow%
```

Possibly fill space between columns:

```
511      \ifnumgreater{\value{KFLT@thiscol}}{1}%
512          {\hfill}%
513          {}%
514      }% nested
515      {}% not nested
516 }
```

`\KFLT@addtext` {*empty or “subgrp”*}

Adds optional additional text.

The argument is {} if a regular float, or subgrp if keysubfigs or keysubtabs.

```
517 \newcommand{\KFLT@addtext}[1]
518 {%
```

Is there text to add?

```
519     \ifcempty{KFLT@#1t}%
520     {}% no text
521     {% text to add
522         {% local
```

Add some space, then create a full-width minipage to contain the text:

```
523     \addvspace{\smallskipamount}%
524     \begin{minipage}{\linewidth}%
```

Inside this minipage, temporarily prevent underfull \hbox warnings:

```
525     \hbadness=10000\relax%
```

Set the alignment and some text parameters:

```
526     \csuse{KFLT@#1textalign}%
527     \footnotesize%
528     \setlength{\parskip}{1.5ex}%
529     \setlength{\parindent}{0em}%
```

Typeset the actual text:

```
530     \csuse{KFLT@#1t}%
```


Close it all out with a little more space:

```
531      \end{minipage}%
532      \par\addvspace{2ex}%
533      }% local
534  }% text to add
535 }
```

`\KFLT@optionalname` $\{\langle name \rangle\}$

Adds optional artist's name and the following space.

```
536 \newcommand{\KFLT@optionalname}[1]
537 {%
538     \ifblank{#1}%
539     {}%
540     {#1~}%
541 }
```

`\KFLT@addartisttext` $\{\langle empty \text{ or "subgrp"} \rangle\}$

Adds optional additional text.

The argument is `{}` if a regular float, or `subgrp` if `keysubfigs` or `keysubtabs`.

One of two versions is used, depending on whether the `tocdata` package is available.

If `tocdata` is loaded and this float has an artist or author, then the float's artist's information and optional text will be printed elsewhere by `\KFLT@caption`. Otherwise, the text is printed here.

Two versions, depending on whether `tocdata` is loaded:

```
542 \@ifpackageloaded{tocdata}
543 {% tocdata loaded
```

If `tocdata` is loaded:

```
544 \newcommand{\KFLT@addartisttext}[1]
545 {%
```

Only add text if is a figure without an artist or author name. If an artist or author is given, the name and text will be added by `tocdata`.

```
546     \ifcempty{KFLT@#1al}% artist last name
547     {%
548         \ifcempty{KFLT@#1aul}% author last name
549         {\KFLT@addtext{#1}}
```



```

550          {}%
551      }%
552      {}% fig w/ artist: text will be added by \captionartist in \KFLT@caption
553 }% KFLT@addartisttext
554 }% tocdata loaded

```

If `tocdata` is not loaded, the name and text are added here:

```

555 {% tocdata not loaded

```

Factored from `\KFLT@addartisttext`

```

556 \newcommand*{\KFLT@addartisttext}[3]{%

```

Add space and create the name inside a full-width minipage:

```

557      \addvspace{\medskipamount}%
558      \begin{minipage}{\linewidth}%

```

Inside this minipage, temporarily prevent underfull `\hbox` warnings:

```

559      \hbadness=10000\relax%

```

Text alignment is #3, and depends on artist or author:

```

560      #3%

```

#1 is empty or 'subgrp'

#2 is empty for artist, 'u' for author:

```

561      \footnotesize\textsc{%
562          \KFLT@optionalname{\csuse{KFLT@#1a#2p}}}%
563          \KFLT@optionalname{\csuse{KFLT@#1a#2f}}}%
564          \csuse{KFLT@#1a#2l}%
565          \csuse{KFLT@#1a#2s}%
566      }%
567      \end{minipage}%
568      \par\addvspace{2ex}%
569 }
570
571 \newcommand{\KFLT@addartisttext}[1]
572 {%

```

Only use the artist information if a last name is given:

```

573      \ifcempty{KFLT@#1al}%
574      {% artist last name not given
575          \ifcempty{KFLT@#1aul}%

```



```

576      {}% author last name not given
577      {% author last name given
578          \KFLT@addartisttext{#1}{u}{\raggedleft}%
579      }% author last name given
580  }% artist last name not given
581  {% artist last name given
582      \KFLT@addartisttext{#1}{}{\centering}%
583  }%

```

Any additional text follows the artist's name:

```

584      \KFLT@addtext{#1}%
585 }% KFLT@addartisttext
586 }% tocdata not loaded

```

Len \KFLTimageboxwidth The computed width of the object.

This may be used as the width parameter of a minipage to encase the object.

```

587 \newlength{\KFLTimageboxwidth}

```

Env KFLT@boxinner Typeset the contents in a width which depends on the keys.

```

588 \newsavebox{\KFLT@envbox}
589
590 \NewDocumentEnvironment{KFLT@boxinner}{}
591 {% keyboxinner

```

(Possibly) frame the contents of an lrbox:

```

592      \begin{lrbox}{\KFLT@envbox}%

```

Rotate the contents:

```

593      \turn{\KFLT@r}%

```

Box the contents in the width computed by \KFLT@findwidths:

```

594      \minipage{\KFLT@imagewidth}%

```

Spacing inside the box. Also default to regular justified text alignment.

```

595      \setlength{\parskip}{2ex}%
596      \renewcommand{\arraystretch}{\KFLT@stretch}%
597 }% keyboxinner

```


End of the environment:

```
598 {% endkeyboxinner
599   \endminipage%
```

End the rotated box:

```
600   \endturn%
```

Possibly frame:

```
601   \end{lrbox}%
602   \KFLT@frame{\usebox{\KFLT@envbox}}}%
603   \par%
604}% endkeyboxinner
```

`\KFLT@boxkeys` $\{\langle keys \rangle\} \{\langle float type \rangle\}$

Default the options, adjust for a table, then parse the keys:

```
605 \NewDocumentCommand{\KFLT@boxkeys}{+m m}
606 {%
607   \KFLT@defaults%
608   \renewcommand{\KFLT@type}{#2}%
609   \setkeys{KFLT@keys}{#1}%
610 }
```

Bool `KFLT@captionistop` Saves the value of `\caption@position`, which may become unreliable if using KOMAScript and

```
\captionsetup[table]{position=above}
```

```
611 \newbool{KFLT@captionistop}
```

`\KFLT@LWR@hook@boxouter` Used by `lwarp`.

```
612 \newcommand*{\KFLT@LWR@hook@boxouter}{}%
```

Env `KFLT@boxouter` $\{\langle star? \rangle\} \{\langle loc \rangle\}$

Boxes the contents of figures and floats.

Not used by subfigures.

```
613 \NewDocumentEnvironment{KFLT@boxouter}{m m}
614 {% boxouter
```


The keyfigure and keytable environments handle the contents in one of three possible ways, depending on whether it is called alone, inside a keyfloats environment, or inside a keysubfigs or keysubtabs environment.

Start the new subfigure or subtable, of the given width:

```
615 \ifbool{KFLT@inkeysubfloats}%
616 {\csuse{sub\KFLT@type}{\KFLT@rowboxwidth}}% subfloat
```

If keyfloats, place the contents inside a minipage:

```
617 {% not subfloat:
618 \ifnumgreater{\value{KFLT@keyfloatdepth}}{0}%
619 {% keyfloats
620 \ifbool{KFLT@keywrap}%
621 {\minipage[t]{\KFLT@rowboxwidth}}%
622 {\minipage[\KFLT@va]{\KFLT@rowboxwidth}}%
623 \captionsetup{type=\KFLT@type}%
624 }% keyfloats
625 {% not keyfloats
```

A hook for lwarp to set \linewidth, etc.

```
626 \KFLT@LWR@hook@boxouter%
```

Not a subfloat or keyfloats, so create a single float.

See if inside a keywrap. If so, force [H] and vertical align top.

```
627 \ifbool{KFLT@keywrap}%
628 {%
629 \par\addvspace{\baselineskip}%
630 \noindent%
631 \minipage[t]{\linewidth}%
632 \captionsetup{type=\KFLT@type}%
633 }%
634 {% not a keywrap
```

See if the float should [W]rap:

```
635 \ifstrequal{#2}{W}%
```

Place [W], so create a wrapfloat using the wrapfig package:

```
636 {% [W]
```

Temporarily figure out \KFLT@imagewidth, and make the wrapped figure environment

as wide as the desired image size plus frame:

```
637             \KFLT@findwidths%
```

Expand the arguments for `wrapfig`:

```
638             \edef\next{%
639                 \noexpand\wrapfloat%
640                 {\KFLT@type}[\KFLT@wn]{\KFLT@wp}[\KFLT@wo]%
641                 {\KFLT@wrapwidth+2\KFLTlooseframewidth}%
642             }%
643             \next%

644             \minipage{\KFLT@wrapwidth+2\KFLTlooseframewidth}%

```

Inside this minipage, temporarily prevent underfull `\hbox` warnings:

```
645             \hbadness=10000\relax%

646             \normalcolor\reset@font\normalsize%

```

Change the interior image to the discovered fixed width.

```
647             \renewcommand{\KFLT@lw}{}%
648             \renewcommand{\KFLT@w}{\KFLT@imagewidth}%
649             \renewcommand{\KFLT@wlw}{}%
650             \renewcommand{\KFLT@ww}{\0pt}%
651             }% [W]
652             {% not [W]

```

See if the float should be positioned in the `[M]`argin:

```
653             \ifstrequal{#2}{M}%

```

Place `[M]`, so create a marginfloat:

```
654             {% [M]
655                 \KFLT@marginfloat[\KFLT@mo]{\KFLT@type}%
656             }% [M]
657             {% not [M]

```

See if the float should be positioned `[H]`ere:

```
658             \ifstrequal{#2}{H}%

```

Place `[H]`, so create an inline minipage:


```

659             {% [H]
660                 \vskip\intextsep%
661                 \noindent\minipage[\KFLT@va]{\linewidth}%
662                 \normalcolor\reset@font\normalsize%
663                 \captionsetup{type=\KFLT@type}%
664             }% [H]

```

Not [H], so create a float: For a starred float, make a two-column table in a two-col format.

```

665             {% not [H]
666                 \IfBooleanTF{#1}%
667                     {\csuse{\KFLT@type*}[\#2]}%
668                     {\csuse{\KFLT@type}[\#2]}%
669             }% not [H]
670         }% not [M]
671     }% not [W]
672 }% not keywrap
673 }% not keyfloats
674 }% not subfloat

```

Handle a continued float. Ignored if in a subfloat.

```

675     \ifbool{\KFLT@cont}{\ContinuedFloat}{}%

```

Figure out image and parbox widths for the contents:

```

676     \KFLT@findwidths%

```

Place the caption above the contents depending on caption position option:

```

677     \caption@iftop{\booltrue{\KFLT@captionistop}}{\boolfalse{\KFLT@captionistop}}%
678     \ifbool{\KFLT@captionistop}{\KFLT@caption{}}{}%

```

Typeset the contents:

```

679     \center\unskip%
680 }% boxouter

```

End of the KFLT@boxouter environment:

```

681 {% endboxouter
682     \endcenter\unskip%
683     \addvspace{\smallskipamount}%

```

Optionally print artist's name and additional text:

```

684     \KFLT@addartisttext{}%

```


Place the caption below the contents depending on caption position option:

```
685 \ifbool{KFLT@captionistop}{\KFLT@caption{}}%
```

If are inside keysubtabs, end the subtable:

```
686 \ifbool{KFLT@inkeysubfloats}%
687 {%
688   \csuse{endsub\KFLT@type}%
689 }% subfloat
690 {% not subfloat
691   \ifnumgreater{\value{KFLT@keyfloatdepth}}{0}% keyfloats?
692   {%

693     \endminipage%
694   }% keyfloats
695   {% not keyfloats
```

Not subfloat or keyfloats, so is an individual float.

Close the minipage or float:

See if in a keywrap:

```
696 \ifbool{KFLT@keywrap}{%
697   \endminipage%
698   \par\addvspace{\baselineskip}%
699 }%
700 {% not keywrap
```

See if the float should [W]rap:

```
701 \ifstrequal{#2}{W}%
```

Place [W], so close the wrap float:

```
702 {% [W]
703   \endminipage%
704   \endwrapfloat%
705 }% [W]
706 {% not[W]
```

See if the float should be positioned in the [M]argin:

```
707 \ifstrequal{#2}{M}%
```

[M], so close the marginfloat:


```

708             {% [M]
709             \endKFLT@marginfloat%
710             }% [M]

```

[H] or float:

```

711             {% not [M]
712             \ifstrequal{#2}{H}%
713             {%
714             \endminipage% [H]
715             \vskip\intextsep%
716             }%
717             {% not [H]
718             \IfBooleanTF{#1}% starred float?
719             {\csuse{end\KFLT@type*}}%
720             {\csuse{end\KFLT@type}}%
721             }% not [H]
722             }% not [M]
723             }% not [W]
724             }% not keywrap
725             }% not keyfloats
726             }% not subfloat
727 }% endkeyboxouter

```

\KFLT@ignorespaces {*<commandname>*} Only do command if not nested inside something.

```

728 \newcommand*\KFLT@ignorespaces[1]{%
729   \ifboolexpr{%
730     test {\ifnumgreater{\value{KFLT@keyfloatdepth}}{0}} or%
731     bool{KFLT@inkeysubfloats}%
732   }{\csuse{#1}}%
733 }

```

\KFLT@ignorespaces Only \ignorespaces if not nested inside something.

```

734 \newcommand*\KFLT@ignorespaces{%
735   \KFLT@ignorespaces{ignorespaces}%
736 }

```

\KFLT@envignorespaces Only \ignorespaces if not nested inside something.

```

737 \newcommand*\KFLT@envignorespaces{%
738   \KFLT@ignorespaces{ignorespacesafterend}%
739 }

```


3.16 The `\KFLT@keyflt` macro

`\KFLT@keyflt` $\{\langle 1:star \rangle\} \{\langle 2:loc \rangle\} \{\langle 3:type \rangle\} \{\langle 4:keys/values \rangle\} \{\langle 5:contents \rangle\}$

A lower-level macro to generate a float with its contents. This is used by `\keyfig` and `\keyflt`.

```

740 \NewDocumentCommand{\KFLT@keyflt}{m m m +m +m}
741 {%

742     \ifcsdef{ftype@#3}{}{%

743         \PackageError{keyfloat}%
744         {%
745             \protect\keyflt: Invalid float type.\MessageBreak%
746             \protect\keyflt*[\loc]{type}{keys/values}{contents}\MessageBreak%
747             Also, \protect\keyflt\space is not an environment
748         }%
749         {%
750             Check argument order and float type.
751         }%
752     }%
753     \KFLT@ignorespaces%
754     \KFLT@trackrows%
755     \KFLT@boxkeys{#4}{#3}%
756     \begingroup%
757     \KFLT@boxouter{#1}{#2}%
758     #5%
759     \endKFLT@boxouter%
760     \endgroup%
761     \KFLT@ignorespaces%
762 }
```

3.17 The `\keyflt` macro

`\keyflt` $* [\langle loc \rangle] \{\langle type \rangle\} \{\langle keys/values \rangle\} \{\langle contents \rangle\}$

A user-level macro to generate a float with its contents centered inside an inner box. This may be used by itself, or inside a `keyfloats` or `keysubtabs` environment.

```

763 \NewDocumentCommand{\keyflt}{s O{tbp} m +m +m}
764 {%
765     \KFLT@keyflt{#1}{#2}{#3}{#4}{%
766         \KFLT@boxinner%
767         \centering%
768         #5%
```



```

769      \endKFLT@boxinner%
770    }%
771 }

```

`\endkeyflt` Generates an error in case the user tried to use `\keyflt` as an environment.

```

772 \def\endkeyflt{%
773   \PackageError{keyfloat}
774   {%
775     \protect\end{keyflt}:\MessageBreak
776     \protect\keyflt\space is a macro, not an environment.\MessageBreak
777     Perhaps you want the keyfloat environment instead%
778   }
779   {%
780     Use \protect\begin{keyfloat} ... \protect\end{keyfloat}.
781   }
782 }

```

3.18 The keyfloat environment

`\KFLT@keyfloatstart` $\{\langle star? \rangle\} \{\langle loc \rangle\} \{\langle float type \rangle\} \{\langle keys/values \rangle\}$

```

783 \newcommand{\KFLT@keyfloatstart}[4]{%
784   \KFLT@envignorespaces%
785   \KFLT@boxkeys{#4}{#3}%
786   \KFLT@boxouter{#1}{#2}%
787   \KFLT@boxinner%
788 }

```

`\KFLT@keyfloatend`

```

789 \newcommand{\KFLT@keyfloatend}{%
790   \endKFLT@boxinner%
791   \endKFLT@boxouter%
792   \KFLT@envignorespaces%
793 }

```

Env `keyfloat` $* [\langle loc \rangle] \{\langle float type \rangle\} \{\langle keys/values \rangle\}$

```

794 \NewDocumentEnvironment{keyfloat}{s O{tbp} m +m}
795 {%
796   \KFLT@keyfloatstart{#1}{#2}{#3}{#4}%
797 }%
798 {%
799   \KFLT@keyfloatend%
800 }

```


Before keyfloat Extra code to track rows outside of the keyfloat environment, before it starts. This is done to allow nesting without losing track of the prior level.

```
801 \BeforeBeginEnvironment{keyfloat}{%
802     \KFLT@trackrows%
803 }
```

3.19 The keyfigure environment

Env keyfigure * [*<loc>*] {*<keys/values>*}

```
804 \NewDocumentEnvironment{keyfigure}{s O{tbp} +m}
805 {%
806     \KFLT@keyfloatstart{#1}{#2}{figure}{#3}%
807 }%
808 {%
809     \KFLT@keyfloatend%
810 }
```

Before keyfigure Extra code to track rows outside of the keyfigure environment, before it starts. This is done to allow nesting without losing track of the prior level.

```
811 \BeforeBeginEnvironment{keyfigure}{%
812     \KFLT@trackrows%
813 }
```

3.20 The \keyfig macro

\keyfig * [*<2:loc>*] {*<3:keys/values>*} {*<4:image filename>*}

A user-level macro to generate a figure with an image. This may be used by itself, or inside a keyfloats or keysubfigs environment.

```
814 \NewDocumentCommand{\keyfig}{s O{tbp} +m m}
815 {%
816     \KFLT@keyflt{#1}{#2}{figure}{#3}{%
817         \KFLT@onefigureimage{#4}%
818     }%
819 }
```

3.21 The \keyfigbox macro

\keyfigbox * [*<loc>*] {*<keys/values>*} {*<box contents>*}

A user-level macro to generate a figure with arbitrary paragraph contents. This may be used by itself, or inside a `keyfloats` or `keysubtabs` environment.

```

820 \NewDocumentCommand{\keyfigbox}{s O{tbp} +m +m}
821 {%
822   \KFLT@ignorespaces%
823   \KFLT@trackrows%
824   \KFLT@boxkeys{#3}{figure}%
825   \begingroup%
826   \KFLT@boxouter{#1}{#2}%
827   \KFLT@boxinner%
828   #4%
829   \endKFLT@boxinner%
830   \endKFLT@boxouter%
831   \endgroup%
832   \KFLT@ignorespaces%
833 }

```

3.22 The `\keyparbox` macro

`\keyparbox` * [*loc*] {*keys/values*} {*box contents*}

A user-level macro to generate a figure with arbitrary paragraph contents, but no number or caption. This is equal to a `\keyfigbox` with `cstar={}`. This may be used by itself, or inside a `keyfloats` or `keysubtabs` environment.

```

834 \NewDocumentCommand{\keyparbox}{s O{tbp} +m +m}
835 {%
836   \KFLT@ignorespaces%
837   \KFLT@trackrows%
838   \KFLT@boxkeys{#3}{figure}%

```

Force `cstar={}`:

```

839   \renewcommand{\KFLT@c}{}%
840   \setboolean{KFLT@cstar}{true}%

```

Continue like `\figbox`:

```

841   \begingroup%
842   \KFLT@boxouter{#1}{#2}%
843   \KFLT@boxinner%
844   #4%
845   \endKFLT@boxinner%
846   \endKFLT@boxouter%
847   \endgroup%

```



```

848 \KFLT@ignorespaces%
849 }

```

3.23 The \keytab macro

`\keytab` * [*loc*] {*keys/values*} {*tabular contents*}

A user-level macro to generate a table with tabular contents. This may be used by itself, or inside a keyfloats or keysubtabs environment.

```

850 \NewDocumentCommand{\keytab}{s O{tbp} +m +m}
851 {%
852 \IfBooleanTF{#1}{%
853 \keyflt*{#2}{table}{#3}{#4}%
854 }{%
855 \keyflt[#{#2}{table}{#3}{#4}%
856 }%
857 }

```

3.24 The keytable environment

Env `keytable` * [*loc*] {*keys/values*}

```

858 \NewDocumentEnvironment{keytable}{s O{tbp} +m}
859 {%
860 \KFLT@keyfloatstart{#1}{#2}{table}{#3}%
861 }%
862 {%
863 \KFLT@keyfloatend%
864 }

```

Before `keytable` Extra code to track rows outside of the keytable environment, before it starts. This is done to allow nesting without losing track of the prior level.

```

865 \BeforeBeginEnvironment{keytable}{%
866 \KFLT@trackrows%
867 }

```

3.25 A row of floats

`\KFLT@nonest` Error message if tried to nest subfloats.


```

868 \newcommand*{\KFLT@nonest}{%
869   \ifboolexpr{%
870     test {\ifnumgreater{\value{KFLT@keyfloatdepth}}{0}} or
871     bool {KFLT@inkeysubfloats}%
872   }%
873   {%
874     \PackageError{keyfloat}%
875     {%
876       Cannot nest keysubfigs or keysubtabs.\MessageBreak%
877       (Not in outer par mode.)%
878     }%
879     {%
880       The subcaption package do not support nested environments,\MessageBreak
881       so the keyfloat package cannot place a\MessageBreak
882       keysubfigs or keysubtabs environment inside another,\MessageBreak
883       or inside a keyfloats.%
884     }%
885   }%
886   {}}%
887 }

```

\KFLT@LWR@hook@keyfloats Used by `lwarp`.

```

888 \newcommand*{\KFLT@LWR@hook@keyfloats}{}%

```

KFLT@LWR@hook@keyfloatsminipage Modified by `lwarp`.

```

889 \newenvironment*{KFLT@LWR@hook@keyfloatsminipage}[1]
890   {\noindent\minipage{#1}}
891   {\endminipage}%

```

Env keyfloats * [*loc*] {*num columns*}

User-level macro to create rows of figures/tables. Wrapping occurs after the number of specified columns. `keyfloats` environments may be nested to create a vertical set of figures next to a single larger figure, for example.

Place `\keyfig`, `\keyfigbox`, and `\keytab` commands inside the `keyfloats` environment.

Note that `lw` linewidth keys may need to be adjusted inside a `keyfloats`, `keysubfigs`, or `keysubtabs`, since `\linewidth` changes depending on the number of columns. Likewise, manually-selected `w` width and `h` tags may need to be adjusted to prevent overflow.

```

892 \NewDocumentEnvironment{keyfloats}{s O{tbp} m}
893 {%

```



```
894 \KFLT@envignorespaces%
```

A hook for `lwarp` to set `\linewidth`, etc.

```
895 \KFLT@LWR@hook@keyfloats%
```

Track the depth:

```
896 \addtocounter{KFLT@keyfloatdepth}{1}%
```

If [H], nested, subfloats, or keywrap, use a minipage instead of a float:

```
897 \ifbool{expr{%
898     test {\ifstrequal{#2}{H}} or
899     test {\ifnumgreater{\value{KFLT@keyfloatdepth}}{1}} or
900     bool {KFLT@inkeysubfloats} or
901     bool {KFLT@keywrap}%
902 }%
```

Create an inline minipage:

```
903 {% [H] or nested
```

If nested, use different spacing as was computed in the outer nesting level:

```
904 \ifbool{expr{%
905     test {\ifnumgreater{\value{KFLT@keyfloatdepth}}{1}} or
906     bool {KFLT@inkeysubfloats}
907 }%
908 {%
909     \KFLT@LWR@hook@keyfloatsminipage{\KFLT@rowboxwidth}%
910 }%
911 {%
912     \vskip\intextsep%
913     \KFLT@LWR@hook@keyfloatsminipage{\linewidth}%
914 }%
```

Reset font and color:

```
915 \normalcolor\reset@font\normalsize%
```

If inside subfloats, generate subfigures by default:

```
916 \ifbool{KFLT@inkeysubfloats}%
917 {%
918     {\captionsetup*{type=figure}}%
919 }% [H] or nested
```


Isn't [H] or nested

```
920   {% See if [W]:
921       \ifstrequal{#2}{W}
922       {% [W]:
```

[W]:

```
923       \wrapfloat{figure}{0}{.5\linewidth}%
924       \minipage{\linewidth}%
```

Inside this minipage, temporarily prevent underfull \hbox warnings:

```
925       \hbadness=10000\relax%

926       \normalcolor\reset@font\normalsize%
927   }%
928   {% not [H]:
929       \ifstrequal{#2}{M}%
930       {% [M]:
```

[M]:

```
931       \KFLT@marginfloat{figure}%
932   }%
```

A normal figure:

```
933   {% figure
934   \IfBooleanTF{#1}% starred figure, two-col figure in a two-col format
935       {\begin{figure*}[#2]}%
936       {\begin{figure}[#2]}%
937   }% figure
938   {% not [H]
939   }%
```

Compute the width of each entry:

```
940   \ifboolexpr{%
941       test {\ifnumgreater{\value{KFLT@keyfloatdepth}}{1}} or
942       bool {KFLT@inkeysubfloats}
943   }%
```

Nested or subfloats:

```
944   {\setlength{\KFLT@rowboxwidth}{.9\KFLT@rowboxwidth/\real{#3}}}%
```


Keyfloats:

```
945      {\setlength{\KFLT@rowboxwidth}{.9\linewidth/\real{#3}}}%
```

Center the contents:

```
946      \centering%
```

Count columns using \defcounter for a local effect:

```
947      \defcounter{KFLT@numcols}{#3}%
948      \defcounter{KFLT@thiscol}{0}%
949}% starting keyfloats environment
```

When ending a keyfloats environment:

```
950}% ending keyfloats environment
```

[H] or rows/subfigs? Close a minipage:

```
951      \ifboolexpr{%
952          test {\ifstrequal{#2}{H}} or
953          test {\ifnumgreater{\value{KFLT@keyfloatdepth}}{1}} or
954          bool {KFLT@inkeysubfloats} or
955          bool {KFLT@keywrap}
956      }%
957      {% was [H], etc.
958          \endKFLT@LWR@hook@keyfloatsminipage%
959      }%
959}%      \end{minipage}%
```

Spacing if nested or not:

```
960      \ifboolexpr{
961          test {\ifnumgreater{\value{KFLT@keyfloatdepth}}{0}} or
962          bool {KFLT@keywrap}
963      }%
964      {% not nested
965          \vskip\intextsep%
966      }%
967      }% was [H], etc.
```

Not [H]:

```
968      {% not [H], etc.
969          \ifstrequal{#2}{W}%
970      }% [W]:
```


[W]:

```

971         \endminipage%
972         \endwrapfloat%
973     }%
974     {%
975         \ifstrequal{#2}{M}%
976         {% [M]:

```

[M]:

```

977         \endKFLT@marginfloat%
978     }%
979     {% figure

```

A figure:

```

980         \IfBooleanTF{#1}% starred figure?
981         {\end{figure*}}{\end{figure}}%
982     }%
983 }%
984 }% not [H], etc.

```

Unnest the environment:

```

985     \addtocounter{KFLT@keyfloatdepth}{-1}%
986     \KFLT@envignorespaces%
987 }

```

Before keyfloats Extra code to track rows outside of the keyfloats environment, before it starts. This is done to allow nesting without losing track of the prior level.

```

988 \BeforeBeginEnvironment{keyfloats}{%
989     \KFLT@trackrows%
990 }

```

3.26 Subfloats

\KFLT@subgrpdefaults Sets defaults before reading the keys.

```

991 \newcommand*{\KFLT@subgrpdefaults}{%
992     \setboolean{KFLT@subgrpcont}{false}%
993     \renewcommand{\KFLT@subgrpc}{}%
994     \setboolean{KFLT@subgrpcstar}{false}%
995     \renewcommand{\KFLT@subgrpsc}{}%
996     \setboolean{KFLT@subgrpscgiven}{false}%

```



```

997 \renewcommand{\KFLT@subgrptype}{figure}%
998 \renewcommand{\KFLT@subgrpl}{}%
999 \renewcommand{\KFLT@subgrpap}{}%
1000 \renewcommand{\KFLT@subgrpaf}{}%
1001 \renewcommand{\KFLT@subgrpap1}{}%
1002 \renewcommand{\KFLT@subgrpas}{}%
1003 \renewcommand{\KFLT@subgrpapup}{}%
1004 \renewcommand{\KFLT@subgrpapuf}{}%
1005 \renewcommand{\KFLT@subgrpaul}{}%
1006 \renewcommand{\KFLT@subgrpasup}{}%
1007 \renewcommand{\KFLT@subgrpt}{}%
1008 \renewcommand{\KFLT@subgrptextalign}{}%
1009 }

```

Bool KFLT@subcaptionistop Saves the value of \caption@position, which may become unreliable if using KOMAScript and

```
\captionsetup[table]{position=above}
```

```
1010 \newbool{KFLT@subcaptionistop}
```

\KFLT@subfloats {<starred?>} {<loc>} {<cols>} {<keys/values>}

Start a subfloat environment

```

1011 \NewDocumentCommand{\KFLT@subfloats}{m m m +m}
1012 {%
1013 \KFLT@envignorespaces%

```

Parse the key-value combinations:

```
1014 \setkeys{KFLT@subgrpkeys}{#4}%
```

Nest the environment:

```
1015 \setboolean{KFLT@inkeysubfloats}{true}%
```

Figure out the width of each subfloat. If starred, use the full-page \textwidth, else use \linewidth. .9 is used to leave a little room between columns.

```

1016 \IfBooleanTF{#1}%
1017 {\setlength{\KFLT@rowboxwidth}{.9\textwidth/\real{#3}}}%
1018 {\setlength{\KFLT@rowboxwidth}{.9\linewidth/\real{#3}}}%

```

If [H], or in a keywrap, create an inline minipage:

```
1019 \ifboolexpr{%
```



```

1020      test {\ifstrequal{#2}{H}} or
1021      bool {KFLT@keywrap}
1022    }%
1023    {%
1024      \vskip\intextsep\noindent\begin{minipage}{\linewidth}%
1025      \normalcolor\reset@font\normalsize%
1026    }%

```

Not [H]:

```

1027    {%
1028      \ifstrequal{#2}{W}%
1029      {% [W]

```

[W]:

```

1030      \wrapfloat{KFLT@subgrptype}{0}{.5\linewidth}%
1031      \setlength{KFLT@rowboxwidth}{.5KFLT@rowboxwidth}%
1032      \minipage{\linewidth}%

```

Inside this minipage, temporarily prevent underfull \hbox warnings:

```

1033      \hbadness=10000\relax%

1034      \normalcolor\reset@font\normalsize%
1035    }%
1036    {% not [H]:
1037      \ifstrequal{#2}{M}%
1038      {% [M]:

```

[M]:

```

1039      KFLT@marginfloat{KFLT@subgrptype}%
1040      \setlength{KFLT@rowboxwidth}{.9\marginparwidth/\real{#3}}%
1041    }% [M]
1042    {% subfloat

```

A subfloat:

```

1043      \IfBooleanTF{#1}%
1044      {\begin{KFLT@subgrptype*}[#2]}%
1045      {\begin{KFLT@subgrptype}[#2]}%
1046    }%
1047    {% not [H]
1048  }%

```

Set the caption type:

1049 \captionsetup*{type=\KFLT@subgrptype}%

Process continued floats:

1050 \ifbool{KFLT@subgrpcont}%
 1051 {\ContinuedFloat}%
 1052 {}}%

Center the contents:

1053 \center\unskip%

Place the caption above the contents depending on caption position option:

1054 \caption@iftop{\booltrue{KFLT@subcaptionistop}}{\boolfalse{KFLT@subcaptionistop}}%
 1055 \ifbool{KFLT@subcaptionistop}{\KFLT@caption{subgrp}}{}}%

Not yet started a row of subfloats. The use of \defcounter makes these changes local.

1056 \defcounter{KFLT@numcols}{#3}%
 1057 \defcounter{KFLT@thiscol}{0}%

Creat a group for the subfloats. Necessary in case they change \tdartisttextcenter, etc.

1058 \begingroup%
 1059 }

\KFLT@endsubfloats {\starred?} {\loc}

Ends a subfloat environment.

1060 \newcommand*{\KFLT@endsubfloats}[2]{%

End the group containing the subfloats:

1061 \endgroup%
 1062 \unskip%
 1063 \endcenter%

A little extra space at the bottom:

1064 \par\addvspace{\bigskipamount}%

Optionally print artist's name and additional text:

1065 \KFLT@addartisttext{subgrp}%

Place the caption below the contents depending on caption position option:

```
1066 \ifbool{KFLT@subcaptionistop}{\KFLT@caption{subgrp}}%
```

End the float or minipage:

```
1067 \ifboolexpr{%
1068     test {\ifstrequal{#2}{H}} or
1069     bool{KFLT@keywrap}
1070 }%
1071 {\end{minipage}\vskip\intextsep}% was [H]
1072 {% not [H]:
1073     \ifstrequal{#2}{W}%
1074     {% [W]

1075         \endminipage%
1076         \endwrapfloat%
1077     }%
1078     {% not [W]:
1079         \ifstrequal{#2}{M}%
1080         {% [M]:

1081             \endKFLT@marginfloat%
1082             }% [M]
1083             {% subfloat
1084                 \IfBooleanTF{#1}% starred?
1085                 {\end{KFLT@subgrptype*}}%
1086                 {\end{KFLT@subgrptype}}%
1087             }%
1088             }% not [W]
1089             }% not [H]
```

Unnest the environment:

```
1090 \setboolean{KFLT@inkeysubfloats}{false}%
1091 \KFLT@envignorespaces%
1092 }
```

\KFLT@LWR@hook@keysubfloats Used by `lwarp`.

```
1093 \newcommand*{\KFLT@LWR@hook@keysubfloats}{{}
```

Env KFLT@keysubfloats { $\langle star? \rangle$ } { $\langle loc \rangle$ } { $\langle float type \rangle$ } { $\langle numcols \rangle$ } { $\langle keys/values \rangle$ }

A group of subfigures typeset in rows.


```

1094 \NewDocumentEnvironment{KFLT@keysubfloats}{m m m m +m}
1095 {%

```

Error if trying to nest environments:

```

1096 \KFLT@nonest%

```

A hook for `lwarp` to set `\linewidth`, etc.

```

1097 \KFLT@LWR@hook@keysubfloats%

```

Default the options:

```

1098 \KFLT@subgrpdefaults%

```

Default to figure float type:

```

1099 \renewcommand{\KFLT@subgrptype}{#3}%

```

Start of the environment:

```

1100 \KFLT@subfloats{#1}{#2}{#4}{#5}%
1101}% the start of the environment

```

end of the environment:

```

1102 {%
1103 \KFLT@endsubfloats{#1}{#2}%
1104 }

```

Env keysubfloats * [*loc*] {*float type*} {*numcols*} {*keys/values*}

A group of subfloats typeset in rows.

```

1105 \NewDocumentEnvironment{keysubfloats}{s O{tbp} m m +m}
1106 {%
1107 \KFLT@keysubfloats{#1}{#2}{#3}{#4}{#5}%
1108 }{%
1109 \endKFLT@keysubfloats%
1110 }

```

Env keysubfigs * [*loc*] {*numcols*} {*keys/values*}

A group of subfigures typeset in rows.

```

1111 \NewDocumentEnvironment{keysubfigs}{s O{tbp} m +m}

```



```

1112 {%
1113   \KFLT@keysubfloats{#1}{#2}{figure}{#3}{#4}%
1114 }{%
1115   \endKFLT@keysubfloats%
1116 }

```

Env keysubtabs * [*<loc>*] {*<numcols>*} {*<keys/values>*}

A group of subtables typeset in rows.

```

1117 \NewDocumentEnvironment{keysubtabs}{s O{tbp} m +m}
1118 {%
1119   \KFLT@keysubfloats{#1}{#2}{table}{#3}{#4}%
1120 }{%
1121   \endKFLT@keysubfloats%
1122 }

```

3.27 Margin floats

Env KFLT@marginfloat [*<offset>*] {*<type>*}

```

1123 \newsavebox{\KFLT@marginfloatbox}
1124
1125 \NewDocumentEnvironment{KFLT@marginfloat}{O{-1.2ex} m}
1126 {% start
1127   \FloatBarrier% keep floats in order
1128   \KFLT@envignorespaces%
1129   \begin{lrbox}{\KFLT@marginfloatbox}%
1130   \begin{minipage}{\marginparwidth}%
1131   \captionsetup{type=#2}%
1132   \hbox{}\vspace*{#1}%
1133   \noindent%
1134   \normalcolor\reset@font\normalsize%
1135 }% start
1136 {% end
1137   \end{minipage}%
1138   \end{lrbox}%
1139   \marginpar{\usebox{\KFLT@marginfloatbox}}%
1140   \KFLT@envignorespaces%
1141 }% end

```

Provided in case `tufte-book` is not loaded:

Env marginfigure [*<offset>*]


```

1142 \ProvideDocumentEnvironment{marginfigure}{0{-1.2ex}}
1143   {\begin{KFLT@marginfloat}[#1]{figure}}
1144   {\end{KFLT@marginfloat}}

```

Env margintable [*<offset>*]

```

1145 \ProvideDocumentEnvironment{margintable}{0{-1.2ex}}
1146   {\begin{KFLT@marginfloat}[#1]{table}}
1147   {\end{KFLT@marginfloat}}

```

3.28 Wrapped floats

Bool KFLT@keywrap Tells the next keyfloat to wrap around some text.

```

1148 \newboolean{KFLT@keywrap}
1149 \boolfalse{KFLT@keywrap}

```

Len \KFLT@keywrapwidth The width of the object to be wrapped beside the text.

```

1150 \newlength{\KFLT@keywrapwidth}

```

Len \KFLT@keywrapparskip The \parskip outside of the keywrap.

```

1151 \newlength{\KFLT@keywrapparskip}

```

Len \KFLT@keywrapparindent The \parindent outside of the keywrap.

```

1152 \newlength{\KFLT@keywrapparindent}

```

Env keywrap {*<width>*}{*<keyfloat>*}

The main text is placed in a minipage to the left, and the wrapped content is later placed in another minipage to the right.

```

1153 \DeclareDocumentEnvironment{keywrap}{m +m}%
1154 {%
1155   \par\noindent%
1156   \setlength{\KFLT@keywrapwidth}{\linewidth}%
1157   \addtolength{\KFLT@keywrapwidth}{-#1}%
1158   \addtolength{\KFLT@keywrapwidth}{-2em}%
1159   \minipage[t]{\KFLT@keywrapwidth}%
1160 %
1161   \setlength{\parskip}{\KFLT@keywrapparskip}%
1162   \setlength{\parindent}{\KFLT@keywrapparindent}%
1163   \booltrue{KFLT@keywrap}%

```



```
1164 }
1165 {%
1166     \par%
1167     \endminipage%
1168     \hfill%
1169     \begin{minipage}[t]{#1}%
1170     \booltrue{KFLT@keywrap}%
1171     \normalcolor\reset@font\normalsize%
```

Inside this minipage, temporarily prevent underfull \hbox warnings:

```
1172     \hbadness=10000\relax%

1173     #2%
1174     \par%
1175     \unskip\vspace{\smallskipamount}%
1176     \end{minipage}%
1177     \par%
1178 }
1179
1180 \BeforeBeginEnvironment{keywrap}{%
1181     \setlength{KFLT@keywrapparskip}{\parskip}%
1182     \setlength{KFLT@keywrapparindent}{\parindent}%
1183 }
```


Change History and Index

Change History

v0.10		KFLT@boxouter: Adjustments for	
General: 2016/12/01 Initial ver.	1	keywrap.	76
v0.11		Handle vertical alignment key va.	76
\KFLT@addtext: Improved paragraph		v1.00	
handling.	72	General: 2019/01/11	1
General: 2016/12/02	1	Docs PDF bookmark	
v0.12		improvements.	1
\keyfigbox: Group around contents.	85	Removed xifthen dependency.	48
\keyflt: Group around contents.	82	Removed spurious spaces.	1
\keyparbox: Group around contents.	85	Source formatting improvements.	1
General: 2016/12/09	1	v2.00	
Adapts to older version of tocdata.	53	\KFLT@@docaption: Factored.	66
Added mo key.	56	\KFLT@ignorespaces: Added.	81
Added wp key.	56	\KFLT@caption: Generalized for float	
Docs: Improved index.	1	type.	69
Docs: Loading keyfloat.	1	\KFLT@docaption: Added support for	
Docs: Margin float examples.	34	authors.	68
Docs: Wrapped float examples.	36	\KFLT@envignorespaces: Added.	81
marginfigure: Added.	97	\KFLT@ignorespaces: Added.	81
marginfigure: Added.	98	\KFLT@keyfloatend: Factored.	83
KFLT@boxouter: [M] and [W] floats.	76	\KFLT@keyfloatstart: Factored.	83
v0.13		\KFLT@keyflt: Added.	82
\KFLT@subfloats: Fix: Subfloat type		\KFLT@onefigureimage: Filename in	
selection.	92	arg instead of \KFLT@i.	64
General: 2017/01/18	1	\KFLT@prohibitpackage: Improved	
\KFLTimageboxwidth: Added.	75	package conflict detection.	48
Docs: Other Settings.	1	\endkeyflt: Added.	83
Fix: Expands names in references.	49	\keyfig: Factored.	84
v0.14		\keyflt: Added.	82
\KFLT@docaption: Fix: No index entry		\keytab: Factored.	86
if no artist given.	67	General: 2019/03/21	1
General: 2017/02/09	1	Added custom float types.	1
v0.15		Added float authors.	1
\KFLT@subfloats: Adjustments for		Adjustments for tocdata v2.00.	53
keywrap.	92	keyfloat: Added.	83
General: 2017/05/12	1	KFLT@boxouter: Added custom float	
Added vertical alignment key va.	57	types.	78, 80
keyfloats: Adjustments for keywrap.	87		
keywrap: Added.	98		

v2.01		\KFLT@addtext: Avoid underfull	
\KFLT@endsubfloats: Added		\hbox warning.	72
keysubfloats [M].	95	\KFLT@findwidths: Added ww and	
Added keysubfloats [W].	95	w1w.	62
Fix: Positions with KOMAScript.	95	\KFLT@keyflt: Work with float.	82
Improved vertical space.	95	\KFLT@subfloats: Avoid underfull	
\KFLT@subfloats: Added		\hbox warning.	93
keysubfloats [M].	93	General: 2021/05/27	1
Added keysubfloats [W].	93	Added ww and w1w.	56, 57, 61
Fix: Font and color.	92	Work with float.	48
Fix: Positions with KOMAScript.	94	keyfloats: Avoid underfull \hbox	
Improved vertical space.	92	warning.	89
General: 2019/09/23	1	keywrap: Avoid underfull \hbox	
tablehere: Fix: Font and color.	49	warning.	99
Improved vertical space.	49	KFLT@boxouter: Added ww and w1w.	78
keyfloats: Added keyfloats [M].	89, 91	Avoid underfull \hbox warning.	78
Added keyfloats [W].	89, 91	v2.03	
Fix: Font and color.	88	General: 2021/05/28	1
Improved vertical space.	88, 90	Fixed \hbadness w/ \relax.	1
keywrap: Fix: \noindent.	98	v2.04	
Fix: Font and color.	98	General: 2021/06/08	1
KFLT@boxouter: Fix: Font and color.	78	Added wn key.	56
Fix: Positions with KOMAScript.	79, 80	Added wo key.	56
Improved vertical space.	78, 81	KFLT@boxouter: Added wn and wo.	78
KFLT@marginfloat: Fix: Font and		v2.05	
color.	97	General: 2021/06/11	1
figurehere: Fix: Font and color.	49	Docs: Fixed r key.	12
Improved vertical space.	49	Docs: Fixed braces for multi-word	
v2.02		values.	12
\KFLT@addartisttext: Avoid		KFLT@boxouter: No longer patch	
underfull \hbox warning.	74	wrapfig for expansion.	78

Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in *roman* refer to the code lines where the entry is used.

Symbols	[loc] (argument)	<i>11</i>
* (argument)		<i>11</i>
\linewidth		<i>21</i>
subfloats		<i>28</i>
with rotation		<i>23</i>
[H] (argument)		<i>11</i>
[M] (argument)		<i>11</i>
[W] (argument)		<i>11</i>
	A	
	af (key) [main]	<i>52</i>
	af (key) [subfloat container]	<i>60</i>
	al (key) [main]	<i>52</i>
	al (key) [subfloat container]	<i>60</i>
	ap (key) [main]	<i>51</i>
	ap (key) [subfloat container]	<i>60</i>

\KFLT@as	94	\KFLT@prohibitpackage	29
\KFLT@auf	98	\KFLT@r	152
\KFLT@aup	96	\KFLT@rowboxwidth (length)	50
\KFLT@aus	102	\KFLT@s	150
KFLT@boxinner (environment)	588	\KFLT@sc	82
\KFLT@boxkeys	605	KFLT@scgiven (boolean)	51
KFLT@boxouter (environment)	613	\KFLT@stretch	158
\KFLT@boxwidth (length)	61	KFLT@subcaptionistop (boolean)	92
\KFLT@c	70	\KFLT@subfloats	1011
\KFLT@caption	426	\KFLT@subgrpaf	225
KFLT@captionistop (boolean)	76	\KFLT@subgrpap	227
KFLT@cont (boolean)	50	\KFLT@subgrpap	223
KFLT@ecstar (boolean)	50	\KFLT@subgrpas	229
\KFLT@defaults	456	\KFLT@subgrpapuf	233
\KFLT@docaption	388, 406	\KFLT@subgrpaul	235
\KFLT@dosimplecaption	337	\KFLT@subgrpapup	231
\KFLT@endsubfloats	1060	\KFLT@subgrpapup	237
\KFLT@envignorespaces	737	\KFLT@subgrpc	187
KFLT@f (boolean)	55	KFLT@subgrpcont (boolean)	57
\KFLT@findenvboxwidth	292	KFLT@subgrpcont (boolean)	58
\KFLT@findwidths	241	\KFLT@subgrpdefaults	991
\KFLT@frame	282	\KFLT@subgrpdesc	199
KFLT@ft (boolean)	55	KFLT@subgrpdescgiven (boolean)	58
\KFLT@h	148	\KFLT@subgrpt	205
\KFLT@ignorespaces	734	\KFLT@subgrptextalign	204
\KFLT@imagewidth (length)	61	\KFLT@subgrptype	201
KFLT@inkeysubfloats (boolean)	57	\KFLT@t	104
KFLT@keyfloatdepth (counter)	57	\KFLT@textalign	103
\KFLT@keyfloatend	789	KFLT@thiscol (counter)	50
\KFLT@keyfloatstart	783	\KFLT@trackrows	503
\KFLT@keyflt	740	\KFLT@type	84
KFLT@keysubfloats (environment)	1094	\KFLT@va	178
\KFLT@keywrapparindent (length)	98	\KFLT@w	146
\KFLT@keywrapparskip (length)	98	\KFLT@wlv	171
\KFLT@keywrapwidth (length)	98	\KFLT@wn	162
\KFLT@l	86	\KFLT@wo	166
\KFLT@lw	141	\KFLT@wp	164
\KFLT@LWR@hook@boxouter	612	\KFLT@wrapwidth (length)	61
\KFLT@LWR@hook@keyfloats	888	\KFLT@ww	176
KFLT@LWR@hook@keyfloatsminipage (environment)	889	\KFLT@imageboxwidth (length)	16, 75
\KFLT@LWR@hook@keysubfloats	1093	\KFLT@looseframe	16, 275
KFLT@marginfloat (environment)	1123	\KFLT@looseframewidth (length)	16, 63
\KFLT@maybeendfloatrow	494	\KFLT@tightframe	16, 267
\KFLT@maybeendfloatrow	490	\KFLT@tightframewidth (length)	16, 63
\KFLT@mo	160		
\KFLT@nonest	868		
KFLT@numcols (counter)	50		
\KFLT@onefigureimage	302		
\KFLT@optionalname	536		

L	
l (key) [main]	51
l (key) [subfloat container]	59
Last,	43
Last, First	43, 44

length:		mo (key) [main]	56
\KFLT@boxwidth	61		
\KFLT@imagewidth	61	N	
\KFLT@keywrapparindent	98	newfloat (package)	9
\KFLT@keywrapparskip	98	P	
\KFLT@keywrapwidth	98	package:	
\KFLT@rowboxwidth	50	calc	48
\KFLT@wrapwidth	61	caption	9, 48
\KFLTimageboxwidth	16, 75	cleveref	9
\KFLTlooseframewidth	16, 63	etoolbox	48
\KFLTtightframewidth	16, 63	fancybox	42
lw (key) [main]	54	float	9
		getttitlestring	49
M		graphicx	48
[main]:		keyval	48
af (key)	52	mdframed	41
al (key)	52	newfloat	9
ap (key)	51	placeins	49
as (key)	52	rotating	49
auf (key)	52	subcaption	48
aul (key)	52	titletoc	9
aup (key)	52	tocdata	9
aus (key)	53	tocloft	9
c (key)	50	wrapfig	11, 49
cont (key)	50	xparse	48
cstar (key)	51	placeins (package)	49
f (key)	55		
ft (key)	55	R	
h (key)	55	r (key) [main]	55
l (key)	51	rotate	
lw (key)	54	box width and vertical space	23
mo (key)	56	rotating (package)	49
r (key)	55		
s (key)	55	S	
sc (key)	51	s (key) [main]	55
stretch (key)	55	sc (key) [main]	51
t (key)	53	sc (key) [subfloat container]	58
tc (key)	54	stretch (key) [main]	55
tl (key)	54	subcaption (package)	48
tr (key)	54	subfloat	
va (key)	57	\linewidth	21, 28
w (key)	54	distance between	45
wlw (key)	56	keys	12
wn (key)	56	nested	31
wo (key)	56	[subfloat container]:	
wp (key)	56	af (key)	60
ww (key)	57	al (key)	60
marginfigure (environment)	11, 1142	ap (key)	60
marginable (environment)	11, 1145	as (key)	60
mdframed (package)	41		

auf (key)	60	image too large	28
aul (key)	61	large tables	18
aup (key)	60	mdframed	42
aus (key)	61	missing label	25
c (key)	58	mixed subfloats	31
cont (key)	58	nested subfloats	31
cstar (key)	58	rotating	
l (key)	59	extra space	23, 42
sc (key)	58	frame	23
t (key)	59	rows too close or far	45
		tufte-book (class)	34
T			
t (key) [main]	53	V	
t (key) [subfloat container]	59	va (key) [main]	57
tablehere (environment)	49	W	
tables		w (key) [main]	54
large	18	wlw (key) [main]	56
tc (key) [main]	54	wn (key) [main]	56
titletoc (package)	9	wo (key) [main]	56
tl (key) [main]	54	wp (key) [main]	56
tocdata (package)	9	wrapfig (package)	11, 49
tocloft (package)	9	wrapped float placement	15
tr (key) [main]	54	ww (key) [main]	57
troubleshooting		X	
\linewidth	28	xparse (package)	48
caption format	46		
float out of sequence	24		