

The HEP-PAPER package*

Publications in high energy physics

Jan Hajer[†]

Department of Physics, University of Basel, Klingelbergstraße 82, 4056 Basel, Switzerland

2021/06/01

Abstract

The HEP-PAPER package aims to provide a single style file containing most configurations and macros necessary to write appealing publications in High Energy Physics. Instead of reinventing the wheel by introducing newly created macros HEP-PAPER preferably loads third party packages as long as they are lightweight enough.

Contents

1	Introduction	2
1.1	Options	2
1.1.1	Deactivation	2
1.1.2	Compatibility	3
1.1.3	Reactivation	3
2	Macros and environments	3
2.1	Title page	4
2.2	Text	4
2.2.1	References and footnotes	5
2.2.2	Acronyms	5
2.3	Math	6
2.3.1	Physics	7
2.4	Floats	8
2.5	Bibliography	9
3	Conclusion	9

*This document corresponds to HEP-PAPER v1.7.

[†]jan.hajer@uclouvain.be

1 Introduction

For usual publications it is enough to load additionally to the `article` class without optional arguments only the HEP-PAPER package [1].

```
\documentclass{article}
\usepackage{hep-paper}
```

The most notable changes after loading the HEP-PAPER package is the change of some L^AT_EX defaults. The paper and font sizes are set to A4 and 11 pt, respectively. Additionally, the paper geometry is adjusted using the GEOMETRY package [2]. Furthermore, the font is changed to latin modern using the CFR-LM package [3] with MICROTYPE [4] optimizations. Finally, portable document format (PDF) hyperlinks are implemented with the HYPERREF package [5]. If only subset of the functionality is needed one of the smaller style files HEP-TITLE, HEP-ACRONYMS, and HEP-BIBLIOGRAPHY containing only the macros relevant to sections 2.1, 2.2.2, and 2.5, respectively.

hep-title

hep-bibliography

hep-acronyms

1.1 Options

- paper** The `paper=<format>` option loads the specified paper format. The possible *<formats>* are: `a0`, `a1`, `a2`, `a3`, `a4`, `a5`, `a6`, `b0`, `b1`, `b2`, `b3`, `b4`, `b5`, `b6`, `c0`, `c1`, `c2`, `c3`, `c4`, `c5`, `c6`, `ansia`, `ansib`, `ansic`, `ansid`, `ansie`, `letter`, `executive`, `legal`. The default is `a4`.
- font** The `font=<size>` option loads the specified font size. The possible *<sizes>* are: `8pt`, `9pt`, `10pt`, `11pt`, `12pt`, `14pt`, `17pt`, `20pt`. The default is `11pt`.
- lang** The `lang=<name>` option switches the document language to one of the values provided by the BABEL package [6]. The default is `british`.
- sansserif** The `sansserif` option switches the document including math to sans serif font shape.
- oldstyle** The `oldstyle` option activates the use of oldstyle text- (123) in favour of lining- (123) figures in text mode.
- parskip** The `parskip` option changes how paragraphs are separated from each other using the PARSKIP package [7]. The L^AT_EX default is separation via indentation the `parskip` option switches to separation via vertical space.¹
- symbols** The `symbols=<family>` set the family of the symbol fonts. `symbols=ams` loads the two $\mathcal{A}\mathcal{M}\mathcal{S}$ fonts [8] and the BM bold fonts. The default `symbols=true` replaces additionally the blackboard font with the D_SFONT [9]. `symbols=minion` switches the symbol fonts to the Adobe MinionPro companion font from the M_NSYMBOL package [10]. `symbols=false` deactivates loading any additional symbol fonts.

1.1.1 Deactivation

The HEP-PAPER package loads few bigger packages which have a large impact on the document. The deactivation options can prevent such and other adjustments.

¹ Although the `parskip` option is used for this document, it is recommended only for very few document types such as technical manuals or answers to referees.

<code>defaults</code>	The <code>defaults</code> option prevents the adjustment of the page geometry and the font size set by the document class.
<code>title</code>	The <code>title=false</code> option deactivates the title page adjustments.
<code>bibliography</code>	The <code>bibliography=<key></code> option prevents the automatic loading of the BIBLATEX package [11] if <code><key>=false</code> . Otherwise the <code><key></code> is passed as <code>style</code> string to the BIBLATEX package.
<code>glossaries</code>	The <code>glossaries=false</code> option deactivates acronyms and the use of the GLOSSARIES package [12].
<code>references</code>	The <code>references=false</code> option prevents the CLEVEREF package [13] from being loaded and deactivates further redefinitions of reference macros.

1.1.2 Compatibility

The compatibility options activate the compatibility mode for certain classes and packages used for publications in high energy physics. They are mostly suitable combinations of options described in the previous section. If HEP-PAPER is able to detect the presence of such a class or package, *i.e.* if it is loaded before the HEP-PAPER package, the compatibility mode is activated automatically.

<code>beamer</code>	The <code>beamer</code> option activates the BEAMER [14] compatibility mode.
<code>jhep</code>	The <code>jhep</code> option activates the JHEP [15] compatibility mode.
<code>jcap</code>	The <code>jcap</code> option activates the JCAP [16] compatibility mode.
<code>revtex</code>	The <code>revtex</code> option activates the REVTeX [17] compatibility mode.
<code>pos</code>	The <code>pos</code> option activates the PoS compatibility mode.
<code>springer</code>	The <code>springer</code> option activates the compatibility mode the <code>svjour</code> class [18].

1.1.3 Reactivation

The HEP-PAPER package deactivates unrecommended macros, which can be reactivated manually.

<code>manualplacement</code>	The <code>manualplacement</code> option reactivates manual float placement.
<code>eqnarray</code>	The <code>eqnarray</code> option reactivates the deprecated <code>eqnarray</code> environment.

2 Macros and environments

<code>twocolumn</code>	If the global <code>twocolumn</code> option is present the page geometry is changed to cover almost the entire page. Additionally the <code>abstract*</code> environment is defined that generates a one column abstract and takes care of placing the title information.
<code>abstract*</code>	

2.1 Title page

`\series` The `\series{<series>}` macro is defined using the TITLING package [19].

`\title` The PDF meta information is set according to the `\title{<text>}` and `\author {<text>}` information.

`\subtitle` The `\subtitle{<subtitle>}` macro is defined.

`\editor` In order to facilitate multiple authors with different affiliations the AUTHBLK package [20] is loaded. The following lines add *e.g.* two authors with different affiliations

`\author`

`\affiliation` `\author[1]{Author one \email{email one}}`
`\affiliation[1]{Affiliation one}`

`\email` `\author[2]{Author two \email{email two}}`
`\affiliation[1,2]{Affiliation two}`

`\preprint` The `\preprint{<numer>}` macro places a pre-print number in the upper right corner of the title page.

`abstract` The `abstract` environment is adjusted to not start with an indentation.

`\titlefont` Various title font macros are defined, allowing to change the appearance of the

`\subtitlefont` `\maketitle` output.

`\authorfont`

2.2 Text

`\affiliationfont`

Hyphenation is provided by the BABEL package [6] and quotation commands are provided by the CSQUOTES package [21]. The latter package provides the convenient macros `\enquote{<text>}` and `\MakeOuterQuote{<text>}` allowing to leave the choice of quotation marks to L^AT_EX and use " instead of the pair “ and ”, respectively.

`\preprintfont`

`\enquote`

`\MakeOuterQuote`

`\eg` The FOREIGN package [22] defines macros such as `\eg`, `\ie`, `\cf`, and `\vs` which are typeset as *e.g.*, *i.e.*, *cf.*, and *vs.*

`\vs`

`\no`

The `\no{<number>}` macro is typeset as № 123.

`\software` The `\software[<version>]{<name>}` macro is typeset as HEP-PAPER v1.7.

`\online`

The `\online{<url>}{<text>}` macro combines the features of the `\href{<url>}{<text>}` [5] and the `\url{<text>}` [23] macros, resulting in *e.g.* `ctan.org/pkg/hep-paper`.

`inlinelist` The `inlinelist` and `enumdescript` environments are defined using the ENUMITEM package [24].

`enumdescript`

The three main points are

`\begin{inlinelist}`

`\item one`

`\item two`

`\item three`

`\end{inlinelist}`

The three main points are i) one, ii) two, and iii) three.

<code>\begin{enumdescript}[label=\Roman*]</code>	I) First one
<code>\item{First} one</code>	II) Second two
<code>\item{Second} two</code>	III) Third three
<code>\item{Third} three</code>	
<code>\end{enumdescript}</code>	
<code>\textsc</code>	A bold versions SMALL CAPS and a sans serif version of SMALL CAPS based on the computer modern font [25] is provided, the latter using the <code>SANSMATHFONTS</code> package [26].
<code>\underline</code>	The <code>\underline</code> macro is redefined to allow line-breaks using the <code>ULEM</code> package [27].
<code>\overline</code>	The <code>\overline</code> macro is extended to also <u>overline</u> text outside of math environments.
<code>\useparskip</code>	If the <code>parskip</code> option is activated the <code>\useparindent</code> macro switches to the usual parindent mode, while the <code>\useparskip</code> macro switches to the <code>parskip</code> mode.
<code>\useparindent</code>	

2.2.1 References and footnotes

`\cref` References are extended with the `CLEVEREF` package [13], which allows to *e.g.* just type `\cref{<key>}` in order to write ‘figure 1’. Furthermore, the `CLEVEREF` package allows to reference multiple objects within one `\cref{<key1,key2>}`.

`\cite` Citations are adjusted to not start on a new line in order to avoid the repeated use of `~\cite{<key>}`.

`\ref` References are also adjusted to not start on a new line.

`\eqref` Footnotes are adjusted to swallow white space before the footnote mark and at the beginning of the footnote text.

`\subref`

`\footnote`

2.2.2 Acronyms

`\acronym` The `\acronym{<*>[<typeset abbreviation>]{<abbreviation>}{<*>}{<definition>}[<plural definition>]}` macro generates the singular `\<abbreviation>` and plural `\<abbreviation>s` macros. The first star prevents the addition of an ‘s’ to the abbreviation plural. The second star restores the `TeX` default of swallowing subsequent white space. The long form is only shown at the first appearance of these macros, later appearances generate the abbreviation with a hyperlink to the long form. The long form is never used in math mode. Capitalization at the beginning of paragraphs and sentences is (mostly) ensured. The `\shortacronym` and `\longacronym` macros are drop-in replacements of the `\acronym` macro showing only the short or long form of their acronym. The first use form of the acronym can be enforced by resetting the acronym counter with `\resetacronym{<key>}`. If the acronym counter equals one at the end of the document the short form of the acronym is not introduced. Placing a `\dummyacronym{<key>}` at the end of the document ensures that the short form is introduced.

2.3 Math

<code>\mathbf</code>	The <code>MATHTOOLS</code> [28] and <code>AMSSYMB</code> [8] packages are loaded. They in turn load the <code>AMS-LATEX</code> <code>AMSMATH</code> [29] and <code>AMSFONTS</code> [8] packages. Bold math, via <code>\mathbf</code> is improved by the <code>BM</code> package [30], <i>i.e.</i> ($Ab\Gamma\delta\mathbf{Ab}\Gamma\delta$). Macros switching to <code>bfseries</code>
<code>\text</code>	such as <code>\section{<text>}</code> are ensured to also typeset math in bold. The <code>\text{<text>}</code>
<code>\mathsf</code>	macro makes it possible to write text within math mode, <i>i.e.</i> ($Ab\Gamma\delta\mathbf{Ab}\Gamma\delta$). The math sans serif alphabet is redefined to be italic sans serif if the main text is serif
<code>\mathscr</code>	and italic serif if the main text is sans serif, <i>i.e.</i> ($Ab\Gamma\delta\mathbf{Ab}\Gamma\delta$). The <code>\mathcal</code> font <i>i.e.</i> ($ABCD$) is accompanied by the <code>\mathscr</code> font <i>i.e.</i> ($\mathcal{ABC}\mathcal{D}$). The <code>\mathbb</code> font is
<code>\mathbf</code>	improved by the <code>DOUBLESTROKE</code> package [9] and adjusted depending on the <code>sansserif</code> option <i>i.e.</i> ($\mathbb{1}$). Finally, the <code>\mathfrak</code> font is also available <i>i.e.</i> ($\mathfrak{A}\mathfrak{B}\mathfrak{1}\mathfrak{2}$). Details about the font handling in <code>TEX</code> can be found in reference [31].
<code>\mathfrak</code>	
<code>\nicefrac</code>	The <code>\frac{<number>}{<number>}</code> macro is accompanied by <code>\nicefrac{<number>}{<number>}</code>
<code>\flatfrac</code>	<code>\flatfrac{<number>}{<number>}</code> , <code>\textfrac{<number>}{<number>}</code> , and <code>\flatfrac{<number>}{<number>}</code>
<code>\textfrac</code>	leading to $\frac{1}{2}$, $\frac{1}{2}$, $\frac{1}{2}$, and $\frac{1}{2}$. Diagonal matrix <code>\diag</code> and signum <code>\sgn</code> operators are defined.
<code>\diag</code>	The <code>\mathdef{<name>}[<arguments>]{<code>}</code> macro (re-)defines macros only within
<code>\sgn</code>	math mode without changing the text mode definition.
<code>\mathdef</code>	The imaginary unit <code>i</code> and the differential <code>d</code> are defined using this functionality.
<code>\i</code>	For longer paper it can be useful to re-number the equation in accordance with the
<code>\d</code>	section numbering <code>\numberwithin{equation}{section}</code> . In order to further reduce
<code>\numberwithin</code>	the size the of equation counter it can be useful to wrap <code>align</code> environments with
<code>subequations</code>	multiple rows in a <code>subequations</code> environment. Both macros are provided by the <code>AMSMATH</code> package.
<code>eqnarray</code>	The depreciated <code>eqnarray</code> environment is undefined as long this behaviour is not prevented by the <code>eqnarray</code> package option. The <code>split</code> , <code>multline</code> , <code>align</code> , <code>multlined</code> , <code>aligned</code> , <code>alignedat</code> , and <code>cases</code> environments of the <code>AMSMATH</code> and <code>MATHTOOLS</code> packages should be used instead.
<code>equation</code>	Use the <code>equation</code> environment for short equations.
	<pre>\begin{equation} left = right \ . \end{equation}</pre> <div style="display: flex; align-items: center; justify-content: center;"> <div style="border: 1px solid black; padding: 2px 10px;">left</div> <div style="margin: 0 10px;">=</div> <div style="border: 1px solid black; padding: 2px 10px;">right</div> <div style="margin-left: 10px;">.</div> <div style="margin-left: 20px;">(1)</div> </div>
<code>multline</code>	Use the <code>multline</code> environment for longer equations.
	<pre>\begin{multline} left = right 1 \ . + right 2 \ . \end{multline}</pre> <div style="display: flex; align-items: center; justify-content: center;"> <div style="border: 1px solid black; padding: 2px 10px;">left</div> <div style="margin: 0 10px;">=</div> <div style="border: 1px solid black; padding: 2px 10px;">right 1</div> <div style="margin-left: 10px;">.</div> <div style="margin-left: 20px;">(2)</div> </div> <div style="display: flex; align-items: center; justify-content: center; margin-top: 10px;"> <div style="border: 1px solid black; padding: 2px 10px; margin-left: 10px;">+ right 2</div> </div>
<code>split</code>	Use the <code>split</code> sub environment for equations in which multiple equal signs should be aligned.

$$\begin{aligned}
&\backslash\text{begin}\{\text{equation}\} \backslash\text{begin}\{\text{split}\} \\
&\quad \text{left} \&= \text{right 1} \backslash\backslash \\
&\quad \&= \text{right 2} \backslash . \\
&\backslash\text{end}\{\text{split}\} \backslash\text{end}\{\text{equation}\}
\end{aligned}
\qquad
\begin{array}{c}
\boxed{\text{left}} = \boxed{\text{right 1}} \\
= \boxed{\text{right 2}} .
\end{array}
\quad (3)$$

align Use the **align** environment for the vertical alignment and horizontal distribution of multiple equations.

$$\begin{aligned}
&\backslash\text{begin}\{\text{subequations}\} \backslash\text{begin}\{\text{align}\} \\
&\quad \text{left} \&= \text{right} \backslash , \& \\
&\quad \text{left} \&= \text{right} \backslash , \backslash \\
&\quad \text{left} \&= \text{right} \backslash , \& \\
&\quad \text{left} \&= \text{right} \backslash . \\
&\backslash\text{end}\{\text{align}\} \backslash\text{end}\{\text{subequations}\}
\end{aligned}
\qquad
\begin{array}{c}
\boxed{\text{left}} = \boxed{\text{right}} , \quad \boxed{\text{left}} = \boxed{\text{right}} , \quad (4a) \\
\boxed{\text{left}} = \boxed{\text{right}} , \quad \boxed{\text{left}} = \boxed{\text{right}} . \quad (4b)
\end{array}$$

aligned Use the **aligned** environment within a **equation** environment if the aligned equations should be labeled with a single equation number.

multlined Use the **multlined** environment if either **split** or **align** contain very long lines.

$$\begin{aligned}
&\backslash\text{begin}\{\text{equation}\} \backslash\text{begin}\{\text{split}\} \\
&\quad \text{left} \&= \text{right 1} \backslash\backslash \&= \\
&\quad \backslash\text{begin}\{\text{multlined}\}[t] \\
&\quad \quad \text{right 2} \backslash\backslash + \text{right 3} \backslash . \\
&\quad \backslash\text{end}\{\text{multlined}\} \\
&\backslash\text{end}\{\text{split}\} \backslash\text{end}\{\text{equation}\}
\end{aligned}
\qquad
\begin{array}{c}
\boxed{\text{left}} = \boxed{\text{right 1}} \\
= \boxed{\text{right 2}} \\
\boxed{+ \text{right 3}} .
\end{array}
\quad (5)$$

alignat Use the **alignat** environment together with the **\mathllap** macro for the alignment of multiple equations with vastly different lengths.

$$\begin{aligned}
&\backslash\text{begin}\{\text{subequations}\} \\
&\backslash\text{begin}\{\text{alignat}\}[2] \\
&\quad \text{left} \&= \text{long right} \&\& \backslash , \backslash \\
&\quad \text{le. 2} \&= \text{ri. 2} \backslash , \& \\
&\quad \mathllap{\text{le. 3} = \text{ri. 3}} \& \backslash . \\
&\backslash\text{end}\{\text{alignat}\} \\
&\backslash\text{end}\{\text{subequations}\}
\end{aligned}
\qquad
\begin{array}{c}
\boxed{\text{left}} = \boxed{\text{long right}} , \quad (6a) \\
\boxed{\text{le. 2}} = \boxed{\text{ri. 2}} , \quad \boxed{\text{le. 3}} = \boxed{\text{ri. 3}} . \quad (6b)
\end{array}$$

As a rule of thumb if you have to use **\notag**, **\nonumber**, or perform manual spacing via **\quad** you are probably using the wrong environment.

2.3.1 Physics

\unit The correct spacing for units, *cf.* equation (7), is provided by the macro **\unit[⟨value⟩]{⟨unit⟩}** from the **UNITS** package [32] which can also be used in text mode. The macro **\inv[⟨power⟩]{⟨text⟩}** allows to avoid math mode also for inverse units such as 5 fb^{-1} typeset via **\unit[5]{\inv{fb}}**.

Greek letters are adjusted to always be italic and upright in math and text mode, respectively, using the **FIXMATH** [33] and **ALPHABETA** [34] packages. This allows differentiations like

$$\sigma = 5\text{ fb} , \qquad \text{at } 5\sigma \text{ C.L.} , \qquad \mu = 5\text{ cm} , \qquad l = 5\mu\text{m} , \qquad (7)$$

`\begin{panels}{2}`

`code`

`\panel`

`\begin{tabular}...\end{tabular}`

`\end{panels}`

(a) Code for this panel environment.

		one		two	
		b		c	
a		b		c	
		b		c	

(b) The `booktabs` and `multirow` features.

Table 1: Example use of the `panels` environment in Panel (a) and the features from the `BOOKTABS` and `MULTIROW` packages in Panel (b).

and *e.g.* to distinguish gauge ν and mass ν eigenstates in models with massive neutrinos. Note that `\mathrm` and therefore `\unit` transform italic Greek character to seemingly random upright characters, this can be avoided by using `\unit{\text{\mu m}`. Additionally, Greek letters can also be directly typed using Unicode.

`\ev` The `PHYSICS` package [35] provides additional macros such as

$$\langle \phi \rangle, \quad \frac{\partial^n f}{\partial x^n}, \quad [A, B], \quad \mathcal{O}(x^2), \quad x|_0^\infty, \quad \det(M). \quad (8)$$

`\order` The `\cancel{\langle characters \rangle}` macro from the `CANCEL` package [36] and the `\slashed{\langle character \rangle}` macro from the `SLASHED` package [37] allow to `cancel` math and use the Dirac slash notation *i.e.* $\cancel{\phi}$, respectively.

`\overlefttrightarrow` A better looking over left right arrow is defined *i.e.* $\overleftrightarrow{\partial}$.

2.4 Floats

`figure` Automatic float placement is adjusted to place a single float at the top of pages and
`table` to reduce the number of float pages, using the `LATEX` macros.

`\setcounter{bottomnumber}{0}` no floats at the bottom of a page (default 1)
`\setcounter{topnumber}{1}` a single float at the top of a page (default 2)
`\setcounter{dbltopnumber}{1}` same for full widths floats in two-column mode
`\renewcommand{\textfraction}{.1}` large floats are allowed (default 0.2)
`\renewcommand{\topfraction}{.9}` (default 0.7)
`\renewcommand{\dbltopfraction}{.9}` (default 0.7)
`\renewcommand{\floatpagefraction}{.8}` float pages must be full (default 0.5)

`\raggedright` Additionally, manual float placement is deactivated but can be reactivated using the `manualplacement` package option. It is however recommended to archive the desired design by adjusting above macros. The most useful float placement is usually archived by placing the float *in front* of the paragraph it is referenced in first. The float environments have been adjusted to center their content. The usual behaviour can be reactivated using `\raggedright`.

`panels` The `panels` environment makes use of the `SUBCAPTION` package [38]. It provides
`\panel` sub-floats and takes as mandatory argument either the number of sub-floats (default 2) or the width of the first sub-float as fraction of the `\linewidth`. Within

the `\begin{panels}[\langle vertical alignment \rangle]{\langle width \rangle}` environment the `\panel` macro initiates a new sub-float. In the case that the width of the first sub-float has been given as an optional argument to the `panels` environment the `\panel{\langle width \rangle}` macro takes the width of the next sub-float as mandatory argument. The example code is presented in table 1a.

<code>tabular</code>	The <code>BOOKTABS</code> [39] and <code>MULTIROW</code> [40] packages are loaded enabling publication quality tabulars such as in table 1b.
<code>\graphic</code> <code>\graphics</code>	The <code>GRAPHICX</code> package [41] is loaded and the <code>\graphic[\langle width \rangle]{\langle figure \rangle}</code> macro is defined, which is a wrapper for the <code>\includegraphics{\langle figure \rangle}</code> macro and takes the figure width as fraction of the <code>\linewidth</code> as optional argument (default 1). If the graphics are located in a sub-folder its path can be indicated by <code>\graphics{\langle subfolder \rangle}</code> .

2.5 Bibliography

<code>\bibliography</code> <code>\printbibliography</code>	The <code>BIBLATEX</code> package [11] is loaded for bibliography management. The user has to add the line <code>\bibliography{\langle my.bib \rangle}</code> to the preamble of the document and <code>\printbibliography</code> at the end of the document. The bibliography is generated by <code>BIBER</code> [42]. <code>biblatex</code> is extended to be able to cope with the <code>collaboration</code> and <code>reportNumber</code> fields provided by <code>inspirehep.net</code> and a bug in the volume number is fixed. Additionally, the PubMed IDs are recognized and <code>ctan.org</code> , <code>github.com</code> , <code>gitlab.com</code> , <code>bitbucket.org</code> , <code>launchpad.net</code> , <code>sourceforge.net</code> , and <code>hepforge.org</code> are valid eprinttypes. Errata can be included using the <code>related</code> feature.
<code>erratum</code>	

```

\article{key1,
    ...,
    relatedtype="erratum",
    related="key2",
}
\article{key2,
    ...,
}

```

3 Conclusion

The `HEP-PAPER` package provides a matching selection of preloaded packages and additional macros enabling the user to focus on the content instead of the layout by reducing the amount of manual tasks. The majority of the loaded packages are fairly lightweight, the others can be deactivated with package options.

<code>arxiv-collector</code>	<code>arxiv.org</code> [43] requires the setup dependent <code>bbl</code> files instead of the original <code>bib</code> files, which causes trouble if the local \LaTeX version differs from the one used by arXiv. The <code>ARXIV-COLLECTOR</code> python script [44] alleviates this problem by collecting all files necessary for publication on arXiv (including figures).
------------------------------	---

References

- [1] J. Hajer. ‘The `hep-paper` package: Publications in high energy physics’ (2019). CTAN: `hep-paper`. DOI: 10.5281/zenodo.3606436. GitHub: `janhajer/hep-paper`.
- [2] D. Carlisle and H. Umeki. ‘The `geometry` package: Flexible and complete interface to document dimensions’ (1996). CTAN: `geometry`. GitHub: `davidcarlisle/geometry`.
- [3] C. F. Rees. ‘The `cfr-lm` package: Enhanced support for the Latin Modern fonts’ (2008). CTAN: `cfr-lm`.
- [4] R. Schlicht. ‘The `microtype` package: Subliminal refinements towards typographical perfection’ (2004). CTAN: `microtype`.
- [5] *L^AT_EX3 Project*. ‘Hypertext marks in L^AT_EX: a manual for `hyperref`: Extensive support for hypertext in L^AT_EX’ (1995). CTAN: `hyperref`. GitHub: `latex3/hyperref`.
- [6] J. Braams, J. Bezos, and et al. ‘Babel Localization and internationalization: Multilingual support for Plain T_EX or L^AT_EX’ (1989). CTAN: `babel`. GitHub: `latex3/babel`.
- [7] R. Fairbairns, F. Mittelbach, and H. Partl. ‘The `parskip` package: Layout with zero `\parindent`, non-zero `\parskip`’ (1989). CTAN: `parskip`. GitHub: `FrankMittelbach/fmitex`.
- [8] *American Mathematical Society*. ‘The `amsfonts` package: T_EX fonts from the American Mathematical Society’ (1995). CTAN: `amsfonts`. URL: `ams.org/tex/amsfonts`.
- [9] O. Kummer. ‘The `doublestroke` font: Typeset mathematical double stroke symbols’ (1995). CTAN: `doublestroke`.
- [10] A. Blumensath. ‘The `MnSymbol` package: Mathematical symbol font for Adobe MinionPro’ (2005). CTAN: `MnSymbol`.
- [11] P. Lehman, J. Wright, A. Boruvka, and P. Kime. ‘The `biblatex` Package: Sophisticated Bibliographies in L^AT_EX’ (2006). CTAN: `biblatex`. GitHub: `plk/biblatex`.
- [12] N. Talbot. ‘The `glossaries` package: Create glossaries and lists of acronyms’ (2007). CTAN: `glossaries`.
- [13] T. Cubitt. ‘The `cleveref` package: Intelligent cross-referencing’ (2006). CTAN: `cleveref`. URL: `dr-qubit.org/cleveref`.
- [14] T. Tantau, J. Wright, and V. Miletic. ‘The `beamer` class: A L^AT_EX class for producing presentations and slides’ (2003). CTAN: `beamer`. GitHub: `josephwright/beamer`.
- [15] *SISSA Medialab*. ‘The JHEP package’ (1997). URL: `jhep.sissa.it/jhep/help/JHEP_TeXclass.jsp`.
- [16] *SISSA Medialab*. ‘The JCAP package’ (2002). URL: `jcap.sissa.it/jcap/help/JCAP_TeXclass.jsp`.
- [17] *American Physical Society*. ‘The REV_TE_X class: Styles for various Physics Journals’ (1999). CTAN: `revtex`. URL: `journals.aps.org/revtex`.

- [18] *Springer Verlag*. ‘The `svjour` package: Macros for Springer journals’ (1997). CTAN: `springer`.
- [19] P. R. Wilson. ‘The `titling` package: Control over the typesetting of the `\maketitle` command’ (2000). CTAN: `titling`.
- [20] P. W. Daly. ‘A \LaTeX Package to Prepare Author and Affiliation Blocks: Support for footnote style author/affiliation’ (2001). CTAN: `authblk`.
- [21] P. Lehman and J. Wright. ‘The `csquotes` Package: Context sensitive quotation facilities’ (2003). CTAN: `csquotes`.
- [22] P. G. Ratcliffe. ‘The `foreign` package for $\LaTeX 2_{\epsilon}$: Systematic treatment of “foreign” words in documents’ (2012). CTAN: `foreign`.
- [23] D. Arseneau. ‘The `url` package: Verbatim with URL-sensitive line breaks’ (1996). CTAN: `url`.
- [24] J. Bezos. ‘Customizing lists with the `enumitem` package: Control layout of itemize, enumerate, description’ (2003). CTAN: `enumitem`. URL: texnia.com/enumitem.html. GitHub: [jbezos/enumitem](https://github.com/jbezos/enumitem).
- [25] *Donald E. Knuth*. ‘Computer Modern fonts’ (1986). CTAN: `cm`.
- [26] A. Barton. ‘The `sansmathfonts` package: Correct placement of accents in sans-serif maths’ (2013). CTAN: `sansmathfonts`.
- [27] D. Arseneau. ‘The `ulem` package: Package for underlining’ (1989). CTAN: `ulem`.
- [28] L. Madsen, M. Høgholm, W. Robertson, and J. Wright. ‘The `mathtools` package: Mathematical tools to use with `amsmath`’ (2004). CTAN: `mathtools`.
- [29] *\LaTeX Team*. ‘The `amsmath` package: AMS mathematical facilities for \LaTeX ’ (1994). CTAN: `amsmath`. URL: ams.org/tex/amslatex.
- [30] *\LaTeX Team*. ‘The `bm` package: Access bold symbols in maths mode’ (1993). CTAN: `bm`.
- [31] *\LaTeX Team*. ‘ $\LaTeX 2_{\epsilon}$ font selection: Documentation of \LaTeX font commands’ (1995). CTAN: `fntguide`.
- [32] A. Reichert. ‘The `units` and `nicefrac` packages: Typeset units’ (1998). CTAN: `units`.
- [33] W. Schmidt. ‘The `fixmath` package for $\LaTeX 2_{\epsilon}$: Make maths comply with ISO 31-0:1992 to ISO 31-13:1992’ (2000). CTAN: `fixmath`.
- [34] G. Milde. ‘The `alphabet` package: LICR macros and encoding definition files for Greek’ (2013). CTAN: `greek-fontenc`.
- [35] S. C. de la Barrera. ‘The `physics` package: Macros supporting the Mathematics of Physics’ (2012). CTAN: `physics`.
- [36] D. Arseneau. ‘The `cancel` package: Place lines through maths formulae’ (2013). CTAN: `cancel`.
- [37] D. Carlisle. ‘The `slashed` package: Put a slash through characters’ (1987). CTAN: `slashed`.
- [38] A. Sommerfeldt. ‘The `subcaption` package: Support for sub-captions’ (2007). CTAN: `subcaption`. GitLab: [axelsommerfeldt/caption](https://gitlab.com/axelsommerfeldt/caption).
- [39] D. Els and S. Fear. ‘The `booktabs` package: Publication quality tables in \LaTeX ’ (1995). CTAN: `booktabs`.

- [40] P. van Oostrum and J. Leichter. ‘The `multirow`, `bigstrut` and `bigdelim` packages: Create tabular cells spanning multiple rows’ (1994). CTAN: `multirow`.
- [41] D. Carlisle and S. Rahtz. ‘Packages in the “graphics” bundle: Enhanced support for graphics’ (1994). CTAN: `graphicx`.
- [42] F. Charette and P. Kime. ‘biber: Backend processor for Bib \LaTeX ’ (2009). GitHub: `plk/biber`. sourceforge: `biblatex-biber`.
- [43] *arXiv Team*. ‘arXiv: free distribution service and an open archive for scholarly articles’ (1991). URL: `arxiv.org`.
- [44] D. Sutherland. ‘`arxiv-collector`: A little Python script to collect \LaTeX sources for upload to the arXiv’ (2018). GitHub: `dougalsutherland/arxiv-collector`.