Lwarp

LaTeX HTML5

The lwarp package

LaTeX to HTML

v0.899 — 2021/06/29

© 2016–2021 Brian Dunn
bd@BDTechConcepts.com

Abstract

The lwarp package converts LaTeX to HTML by using LaTeX to process the user's document and directly generate HTML tags. External utility programs are only used for the final conversion of text and images. Math may be represented by SVG images or MathJax. More than 500 LaTeX packages and classes are supported, of which more than 90 also support MathJax.

Documents may be produced by DVI or PDF LaTeX, LuaLaTeX, XeLaTeX; by several CJK engines, classes, and packages; or by customized systems such as perltex and pythontex. A *texlua* script automates compilation, index, glossary, and batch image processing, and also supports *latexmk*. Configuration is semi-automatic at the first manual compile. Support files are self-generated. Print and HTML versions of each document may coexist.

Assistance is provided for HTML import into EPUB conversion software and word processors.

Requirements include the commonly-available Poppler utilities (included with MiKTeX) and Perl. Detailed installation instructions are included for each of the major operating systems and TeX distributions.

A quick-start tutorial is provided, as well as extensive documentation for special cases, a general index, and a troubleshooting index. Automatic error testing is provided for configuration files, package load order, and image generation.

SVG math and many other generated images include LaTeX expressions in the `alt` tags. MathJax may be used with advanced equation numbering under the direct control of lwarp.

Complicated tables are supported, which copy/paste well into LibreOffice Writer.

Supported classes and packages include memoir and koma-script, cleveref, caption, mdframed, siunitx, and many popular packages for tabulars, floats, graphics, theorems, the title page, bibliography, indexing, footnotes, and editorial work, as well as a number of CJK-related classes and packages.

TeX is a self-modifying tokenized macro-expansion language. Since lwarp is written directly in LaTeX, it is able to interpret the document's meaning at a deeper level than external conversions which merely approximate TeX. HTML5 and CSS3 are leveraged to provide advanced features such as booktabs trim, multicolumns, side-by-side minipages, and JavaScript-free navigation.

For a quick-start tutorial, see section 5, Tutorial.

For a list of supported features, see table 2: Supported packages and features.

To update existing projects, see section 1: Updates.

Lwarp is still in development. Changes are likely.

License:

This work may be distributed and/or modified under the conditions of the LaTeX Project Public License, either version 1.3 of this license or (at your option) any later version. The latest version of this license is in http://www.latex-project.org/lppl.txt and version 1.3 or later is part of all distributions of LaTeX version 2005/12/01 or later.

Support TEX development

TEX and related projects:

- are mostly open-sourced and a volunteer effort;
- benefit students, academics, scientists, engineers, and businesses;
- help drive education, public and private research, and commercial activity;
- are used in the fields of mathematics, science, engineering, and humanities;
- are international in reach;
- span decades of development;
- are enduring — many older packages are still actively used and maintained;
- are largely backwards compatible;
- are portable across all the major computing platforms;
- are usable even on older computers and away from internet access;
- are continuing to maintain relevance with modern improvements;
- require no yearly subscription fees;
- and are supported by an active community of knowledgeable volunteers.

Please consider helping by joining and/or contributing to the TEX Users Group, a United States 501(c)(3) tax-exempt charitable organization. Contributions are accepted by credit card, check, or Pay Pal, via the United Way, or by USA or European bank transfer. Membership in TUG supports the development of TEXLive, the major TEX distribution.

Donations may be directed towards individual projects:

TUG Bursary Fund: Assistance for attending annual TUG meetings.
CTAN: The Comprehensive TEX Archive Network — Central storage for TEX.
TeX Development Fund: Support for specific projects.
EduTeX: Teaching and using TEX in schools and universities.
GUST e-foundry fonts: Enhanced for math and additional language groups.
LaTeX Project: Modernizing the LATEX core.
Libre Font Fund: Fonts, tools (FontForge), and distribution (the Open Font Library).
LuaTeX: Combining the pdfTEX engine and the Lua language.
MetaPost: Postscript graphics.
MacTeX: TEX for Mac.
PDF Accessibility: Modern PDF standards.
Other: Additional projects may be specified.

To make a contribution: https://www.tug.org/donate.html

For country-specific TEX users groups: http://tug.org/usergroups.html

For users of MiKTEX: https://miktex.org/donations.html

Contents

Support TEX development **2**

List of Figures **44**

List of Tables **44**

1 Updates **45**

2 Introduction **65**

2.1 Typesetting conventions 67

2.2 Supported packages and features 68

3 Alternatives **75**

3.1 internet class 75

3.2 TEX4HT 75

3.3 Translators 75

3.4 AsciiDoc and Asciidoctor 76

3.4.1 Asciidoctor-LATEX 76

3.5 Pandoc 76

3.6 Word processors 76

3.7 Commercial systems 76

3.8 Comparisons 76

4 Installation **78**

4.1 Installing the lwarp package 80

4.2 Installing the *lwarpmk* utility 81

4.2.1 Using a local copy of *lwarpmk* 83

4.3 Installing additional utilities 83

5 Tutorial **85**

5.1 Starting a new project 85

5.2 Compiling the print version with *lwarpmk* 89

5.3 Compiling the HTML version with *lwarpmk* 90

5.4 Generating the SVG images 91

5.5 Using MathJax for math 92

5.6 Changing the CSS style . . . 93
5.7 Customizing the HTML output . . . 93
5.8 Using *latexmk* . . . 94
5.9 Using XeLaTeX or LuaLaTeX . . . 95
5.10 Using DVI LaTeX . . . 95
5.11 Using a glossary . . . 96
5.11.1 gloss package . . . 96
5.11.2 glossaries package . . . 96
5.12 Cleaning auxiliary files . . . 97
5.13 Cleaning auxiliary and output files . . . 97
5.14 Cleaning the images from the <project>-images directory . . . 97
5.15 Converting PDF or EPS images to SVG . . . 97
5.16 Creating HTML from an incomplete compile . . . 97
5.17 Processing multiple projects in the same directory . . . 97
5.18 Using the *make* utility . . . 98
5.19 What next? . . . 99
6 Converting an existing document . . . 100
7 Additional details . . . 101
7.1 Localization . . . 101
7.2 Accessibility . . . 101
7.3 Shell escape . . . 103
7.4 Font and UTF-8 support . . . 103
7.4.1 Indexes, glossaries, and encoding . . . 105
7.5 lwarp package loading and options . . . 106
7.6 Customizing the HTML output . . . 111
7.6.1 Example HTML file naming . . . 117
7.7 Customizing the CSS . . . 117
7.8 Assigning CSS classes and styles . . . 119
7.9 Selecting the operating system . . . 119
7.10 Selecting actions for print, HTML, or MathJax output . . . 119

7.11 Commands to be placed into the warpprint environment 120
7.12 Title page 121
7.13 HTML page meta descriptions 122
7.14 HTML homepage meta title 122
7.15 HTML page meta author 122
8 Special cases and limitations 123
8.1 Things to avoid 123
8.1.1 Invalid HTML 124
8.2 Formatting 124
8.2.1 Text formatting 124
8.2.2 Small caps 124
8.2.3 Horizontal and vertical space and rules 124
8.2.4 Text alignment 125
8.2.5 Accents 125
8.2.6 textcomp package 125
8.2.7 Superscripts and other non-math uses of math mode 125
8.2.8 Empty \item followed by a new line of text or a nested list: 125
8.2.9 Filenames and URLs in lists or footnotes 126
8.2.10 relsize package 126
8.3 Boxes and minipages 126
8.3.1 Marginpars 126
8.3.2 Save Boxes 126
8.3.3 Minipages 126
8.3.4 Side-by-side minipages 127
8.3.5 Framed minipages and other environments 127
8.3.6 fancybox package 129
8.3.7 mdframed package 130
8.3.8 tcolorbox package 130
8.4 Section names 131

8.5 Cross-references . . . 132
8.5.1 Page references . . . 132
8.5.2 cleveref and varioref packages . . . 132
8.5.3 Hyperlinks, hyperref, and url . . . 132
8.5.4 Footnotes, endnotes, and page notes . . . 133
8.5.5 xr, xr-hyper, and xcite packages . . . 134
8.6 Front and back matter . . . 134
8.6.1 Custom classes with multiple authors and affiliations . . . 134
8.6.2 Starred chapters and sections . . . 135
8.6.3 abstract package . . . 135
8.6.4 titling and authblk . . . 135
8.6.5 tocloft package . . . 135
8.6.6 appendix package . . . 136
8.6.7 pagenote package . . . 136
8.6.8 endnotes package . . . 136
8.6.9 *BibTeX* . . . 136
8.6.10 xcite package . . . 136
8.6.11 gloss package . . . 137
8.6.12 glossaries package . . . 137
8.6.13 nomencl package . . . 138
8.6.14 Indexing overview . . . 138
8.6.15 Indexing with makeidx, *makeindex*, *xindy*, *xindex*, gindex . . . 138
8.6.16 Indexing with index . . . 140
8.6.17 Indexing with splitidx . . . 141
8.6.18 Indexing with imakeidx . . . 142
8.6.19 Indexes with memoir . . . 146
8.6.20 Using a custom *makeindex* style file . . . 149
8.6.21 Using a custom *xindy* style file . . . 149
8.6.22 Using a custom *xindex* style file . . . 150
8.6.23 Additional indexing limitations . . . 151

8.6.24 Index positions, TOC, tocbibind . . . 151
8.7 Math . . . 152
8.7.1 Math in section names . . . 152
8.7.2 Rendering tradeoffs . . . 152
8.7.3 SVG option . . . 153
8.7.4 MathJax option . . . 154
8.7.5 Customizing MathJax . . . 154
8.7.6 MathJax limitations . . . 155
8.7.7 Catcode changes . . . 156
8.7.8 Complicated inline math objects . . . 156
8.7.9 Complicated display math objects . . . 157
8.7.10 Theorems . . . 157
8.7.11 ntheorem package . . . 157
8.7.12 mathtools package . . . 158
8.7.13 siunitx package . . . 158
8.7.14 units and nicefrac packages . . . 159
8.7.15 physics package . . . 159
8.8 Graphics . . . 159
8.8.1 tikz package . . . 161
8.8.2 grffile package . . . 162
8.8.3 color package . . . 162
8.8.4 xcolor package . . . 162
8.8.5 epstopdf package . . . 162
8.8.6 pstricks package . . . 162
8.8.7 pdftricks package . . . 163
8.8.8 psfrag package . . . 163
8.8.9 pstool package . . . 163
8.8.10 asymptote package . . . 164
8.8.11 overpic package . . . 164
8.8.12 Multimedia packages . . . 164

8.9 Tabbing 165
8.10 Tabular 165
8.10.1 tabular environment 165
8.10.2 multirow package 167
8.10.3 longtable package 168
8.10.4 threeparttablex package 169
8.10.5 supertabular and xtab packages 169
8.10.6 colortbl package 169
8.10.7 ctable package 170
8.10.8 bigdelim package 170
8.11 Floats 170
8.11.1 Float contents alignment 170
8.11.2 float, trivfloat, and/or algorithmicx together 170
8.11.3 caption and subcaption packages 171
8.11.4 subfig package 171
8.11.5 floatrow package 171
8.11.6 keyfloat package 172
8.12 Koma-Script classes 172
8.13 Memoir class 172
8.14 International languages 174
8.15 Miscellaneous packages 174
8.15.1 verse and memoir 174
8.15.2 newclude package 175
8.15.3 babel package 175
8.15.4 polyglossia package 175
8.15.5 todonotes and luatodonotes packages 176
8.15.6 fixme 176
8.15.7 acro package 176
8.15.8 chemfig package 176
8.15.9 chemformula package 176

8.15.10 mhchem package . . . 177
8.15.11 kotex package . . . 177
9 Compiling using custom shell commands . . . 178
9.1 Command options . . . 178
9.2 Literal character macros . . . 178
9.3 *latexmk* . . . 179
9.4 perltex package . . . 180
9.5 pythontex package . . . 180
9.6 Other packages . . . 180
9.7 *make* program . . . 181
9.8 UTF-8 locale . . . 181
10 EPUB conversion . . . 182
11 Word-processor conversion . . . 184
11.1 Activating word-processor conversion . . . 184
11.2 Additional modifications . . . 185
11.3 Recommendations . . . 187
11.4 Limitations . . . 188
12 Modifying lwarp . . . 189
12.1 Creating a development system . . . 189
12.2 Modifying a package for lwarp . . . 191
12.2.1 Adding a package to the lwarp.dtx file . . . 191
12.3 Modifying a class for lwarp . . . 192
12.4 Testing lwarp . . . 192
12.5 Modifying *lwarpmk* . . . 192
13 Troubleshooting . . . 194
13.1 lwarp package error conditions and warnings . . . 194
13.1.1 Configuration file `lwarpmk.conf` . . . 194
13.1.2 Image generation with **`lwarpmk limages`** . . . 194
13.1.3 Default bitmapped font . . . 195
13.1.4 Packages . . . 195

13.1.5 Compiling . . . 195
13.2 Using the lwarp package . . . 196
13.2.1 Debug tracing output . . . 200
13.3 Compiling the `lwarp.dtx` file . . . 200
14 Trademarks . . . 201
1 lwarp.sty . . . 202
15 Implementation . . . 202
16 Section depths and HTML headings . . . 203
17 Source code . . . 204
18 Detecting the TeX engine — *pdflatex*, *lualatex*, *xelatex* . . . 205
19 Early package requirements . . . 205
20 Package load order . . . 205
20.1 Tests of package load order . . . 206
20.2 Error for disallowed packages and classes loaded before lwarp . . . 209
20.3 Enforcing package loading after lwarp . . . 211
21 MD5 hashing . . . 222
22 pdfLaTeX T1 and UTF-8 encoding . . . 223
23 Unicode input characters . . . 223
24 Avoid a bitmapped font . . . 224
25 Upright quotes . . . 224
26 Avoid bad font combinations . . . 225
27 Miscellaneous tools . . . 225
27.1 Variables . . . 225
27.2 Lengths and units . . . 225
27.3 Counters . . . 226
27.4 Patching . . . 226
27.5 Chinese text isolation . . . 226
27.6 Inserting vertical space . . . 227
27.7 Argument selection . . . 227
27.8 Inside boxes . . . 227

27.9 Global boxes . . . 228
27.10 Converting a macro name to a cs name . . . 228
27.11 Title case . . . 229
27.12 LetLtxMacrocs . . . 229
27.13 Absorbing a star . . . 229
28 Operating-System portability . . . 229
28.1 Literal characters . . . 230
28.2 Common portability code . . . 231
28.3 Unix, Linux, and Mac OS . . . 231
28.4 MS-Windows . . . 231
29 Package options . . . 232
29.1 Additional options support . . . 236
29.2 Conditional compilation . . . 238
30 Required packages . . . 240
31 Loading packages . . . 246
32 File handles . . . 252
33 Include a file . . . 253
34 Copying a file . . . 254
35 Debugging messages . . . 254
36 Defining print and HTML versions of macros and environments . . . 255
37 HTML-conversion output modifications . . . 260
37.1 User-level controls . . . 260
37.2 Heading adjustments . . . 262
38 Remembering original formatting macros . . . 263
39 Accents . . . 265
40 Configuration files . . . 267
40.1 Decide whether to generate configuration files . . . 267
40.2 `<project>_html.tex` . . . 268
40.3 *lwarpmk* configuration files . . . 268
40.3.1 Helper macros . . . 268

40.3.2 lwarpmk.conf . . . 274
40.3.3 <project>.lwarpmkconf . . . 274
40.4 lwarp.css . . . 274
40.5 lwarp_sagebrush.css . . . 306
40.6 lwarp_formal.css . . . 311
40.7 sample_project.css . . . 315
40.8 lwarp.ist . . . 315
40.9 lwarp.xdy . . . 316
40.10 lwarp_one_limage.cmd . . . 317
40.11 lwarp_mathjax.txt . . . 317
40.12 lwarpmk.lua — lwarpmk option . . . 321
41 Stacks . . . 340
41.1 Assigning depths . . . 340
41.2 Closing actions . . . 341
41.3 Closing depths . . . 341
41.4 Pushing and popping the stack . . . 342
42 Data arrays . . . 344
43 Localizing catcodes . . . 344
44 Localizing dynamic math . . . 345
45 HTML entities . . . 346
46 HTML filename generation . . . 347
47 Homepage link . . . 350
48 Previous/next navigation links . . . 351
49 \LWRPrintStack diagnostic tool . . . 353
50 Closing stack levels . . . 353
51 PDF pages and styles . . . 354
52 HTML tags, spans, divs, elements . . . 355
52.1 Mapping LaTeX sections to HTML sections . . . 356
52.2 Hook while processing tags . . . 356
52.3 Babel-French tag modifications . . . 356

52.4 HTML output formatting . . . 357
52.5 HTML tags. . . . 358
52.6 Block tags and comments . . . 360
52.7 Div class and element class . . . 361
52.8 Single-line elements . . . 363
52.9 HTML5 semantic elements . . . 363
52.10 High-level block and inline classes . . . 363
52.11 Closing HTML tags . . . 366
53 Paragraph handling . . . 366
54 Paragraph start/stop handling . . . 370
55 Indentfirst . . . 372
56 Page headers and footers . . . 372
57 CSS . . . 373
58 MathJax script . . . 374
59 Title, HTML meta author, HTML meta description . . . 374
60 Footnotes . . . 375
60.1 Regular page footnotes . . . 376
60.2 Minipage footnotes . . . 377
60.3 Titlepage thanks . . . 377
60.4 Regular page footnote implementation . . . 377
60.5 Minipage footnote implementation . . . 380
60.6 Printing pending footnotes . . . 381
61 Marginpars . . . 382
62 Tracking internal cross references . . . 383
63 Splitting HTML files . . . 385
63.1 Sanitizing expressions for HTML . . . 390
63.2 Customizing MathJax . . . 392
64 Sectioning . . . 400
64.1 User-level starred section commands . . . 400
64.2 Book class commands. . . . 401

64.3 Sectioning support macros . . . 401
64.4 Pre- and post- sectioning names . . . 408
64.5 \section and friends . . . 409
65 Starting a new file . . . 411
66 Starting HTML output . . . 415
67 Ending HTML output . . . 418
68 Nullifying foreground/background hooks . . . 420
69 Title page . . . 421
69.1 Setting the title, etc. . . . 421
69.2 \if@titlepage . . . 422
69.3 Changes for \affiliation . . . 422
69.4 Printing the thanks . . . 423
69.5 Printing the title, etc. in HTML . . . 424
69.6 Printing the title, etc. in print form . . . 425
69.7 \maketitle for HTML output . . . 425
69.8 \published and \subtitle . . . 429
70 Abstract . . . 430
71 Quote and verse . . . 430
71.1 Attributions . . . 430
71.2 Quotes, quotations . . . 431
71.3 Verse . . . 431
71.3.1 LaTeX core verse environment . . . 432
71.3.2 verse and memoir . . . 432
72 Verbatim and tabbing . . . 433
73 Theorems . . . 436
74 Lists . . . 437
74.1 List environment . . . 438
74.2 Itemize . . . 441
74.3 Enumerate . . . 442
74.4 Description . . . 442

74.5 Patching the lists . . . 443
75 Tabular . . . 444
75.1 Limitations . . . 445
75.2 Temporary package-related macros . . . 447
75.2.1 arydshln . . . 447
75.3 Token lookahead . . . 447
75.4 Tabular variables . . . 448
75.4.1 Multicolumn variables . . . 451
75.4.2 Longtable variables . . . 452
75.4.3 Midrule variables . . . 452
75.5 Handling &, @, !, and bar . . . 452
75.5.1 Handling &. . . . 454
75.5.2 Filling an unfinished row . . . 455
75.6 Handling \\ . . . 456
75.7 Looking ahead in the column specifications . . . 457
75.8 Parsing @, >, <, !, bar columns . . . 458
75.9 Parsing 'l', 'c', or 'r' columns . . . 462
75.10 Parsing 'p', 'm', or 'b' columns . . . 462
75.11 Parsing 'w' columns . . . 463
75.12 Parsing '*' columns . . . 463
75.13 Parsing 'D' columns . . . 463
75.14 Expanding the star column specifications . . . 463
75.15 Parsing the column specifications . . . 465
75.16 colortbl and xcolor tabular color support . . . 469
75.17 Starting a new row . . . 471
75.18 Printing vertical bar tags . . . 472
75.19 Printing @ or ! tags . . . 472
75.20 Data opening tag . . . 473
75.21 Midrules . . . 475
75.22 Cell colors . . . 480

75.23 Multicolumns 484
75.23.1 Parsing multicolumns 484
75.23.2 Multicolumn factored code 487
75.23.3 Multicolumn 490
75.23.4 Longtable captions 491
75.23.5 Counting HTML tabular columns 493
75.24 Multirow if not loaded 494
75.25 Multicolumnrow 494
75.26 Utility macros inside a table 496
75.27 Special-case tabular markers 496
75.28 Checking for a new table cell 497
75.29 \mrowcell 500
75.30 \mcolrowcell 500
75.31 HTML tabular environment 500
76 Cross-references 507
76.1 Setup 507
76.2 New lwarp labels. 509
76.3 Labels 510
76.4 References 513
76.5 Hyper-references 516
77 Floats 520
77.1 Float environment 520
77.2 Float tracking 523
77.3 Caption inside a float environment 524
77.4 Caption and LOF linking and tracking 525
78 Table of Contents, LOF, LOT 528
78.1 Reading and printing the TOC 529
78.2 TOC commands 532
78.3 Side TOC 532
78.4 Low-level TOC line formatting 533

79 Index and glossary . . . 537
80 Bibliography presentation . . . 545
81 Restoring original formatting . . . 546
82 Nullifying filename formatting . . . 548
83 Math . . . 551
83.1 Limitations . . . 551
83.2 HTML `alt` tag names . . . 551
83.3 Inline and display math . . . 552
83.4 MathJax support . . . 566
83.5 Equation environment . . . 569
83.6 `\displaymathnormal` and `\displaymathother` . . . 572
83.7 AMS Math environments . . . 573
83.7.1 Support macros . . . 573
83.7.2 Environment patches . . . 574
84 Lateximages . . . 577
84.1 Description . . . 577
84.2 Support counters and macros . . . 578
84.3 Font size . . . 578
84.4 Equation numbers . . . 579
84.5 HTML `alt` tags . . . 580
84.6 `lateximage` environment . . . 580
85 `center`, `flushleft`, `flushright` . . . 587
86 Preloaded packages . . . 588
87 siunitx . . . 590
88 Graphics print-mode modifications . . . 592
88.1 General limitations . . . 592
88.2 Print-mode modifications . . . 593
89 xcolor boxes . . . 594
90 chemmacros environments . . . 597
91 cleveref . . . 597

92 Preexisting label and reference definitions . . . 598
93 picture environment . . . 598
94 Minipages and Boxes . . . 598
94.1 Computed lengths . . . 599
94.2 Virtual page size . . . 600
94.3 Footnote handling . . . 600
94.4 Minipage handling . . . 600
94.5 \parbox, \mbox, \makebox, \framebox, \fbox, \raisebox . . . 604
95 Direct formatting . . . 610
96 Skips, spaces, font sizes . . . 620
97 \phantomsection . . . 627
98 \LaTeX and other logos . . . 628
99 Starting and stopping lwarp . . . 631
100 Loading everyshi patches . . . 632
101 Loading textcomp patches . . . 632
102 Loading amsmath, amsthm patches, centernot . . . 632
103 Loading KOMA-SCRIPT class patches . . . 632
104 Loading MEMOIR class patches . . . 633
105 ut* class patches . . . 633
106 CTEX patches . . . 634
107 kotexutf patches . . . 635
108 babel and polyglossia warnings . . . 636
109 MATHJAX warnings . . . 637
2 lwarp-2in1.sty . . . 640
3 lwarp-2up.sty . . . 640
4 lwarp-a4.sty . . . 640
5 lwarp-a4wide.sty . . . 640
6 lwarp-a5comb.sty . . . 641
7 lwarp-abstract.sty . . . 641

8 lwarp-academicons.sty 643
9 lwarp-accents.sty 644
10 lwarp-accessibility.sty 645
11 lwarp-accsupp.sty 645
12 lwarp-acro.sty 646
13 lwarp-acronym.sty 648
14 lwarp-adjmulticol.sty 649
15 lwarp-addlines.sty 650
16 lwarp-afterpage.sty 651
17 lwarp-algorithm2e.sty 651
18 lwarp-algorithmicx.sty 655
19 lwarp-alltt.sty 655
20 lwarp-amscdx.sty 656
21 lwarp-amsmath.sty 657
22 lwarp-amsthm.sty 661
23 lwarp-anonchap.sty 666
24 lwarp-anysize.sty 666
25 lwarp-appendix.sty 667
26 lwarp-ar.sty 667
27 lwarp-arabicfront.sty 669
28 lwarp-array.sty 669
29 lwarp-arydshln.sty 670
30 lwarp-asymptote.sty 672
31 lwarp-atbegshi.sty 672
32 lwarp-attachfile.sty 673
33 lwarp-attachfile2.sty 674
34 lwarp-authblk.sty 676

35 lwarp-autobreak.sty 677
36 lwarp-autonum.sty 678
37 lwarp-awesomebox.sty 679
38 lwarp-axessibility.sty 680
39 lwarp-axodraw2.sty 681
40 lwarp-backnaur.sty 681
41 lwarp-backref.sty 682
42 lwarp-balance.sty 682
43 lwarp-bbding.sty 683
44 lwarp-biblatex.sty 687
45 lwarp-bibunits.sty 692
46 lwarp-bigdelim.sty 692
47 lwarp-bigfoot.sty 693
48 lwarp-bigstrut.sty 694
49 lwarp-bitpattern.sty 694
50 lwarp-blowup.sty 695
51 lwarp-bm.sty 695
52 lwarp-booklet.sty 695
53 lwarp-bookmark.sty 696
54 lwarp-booktabs.sty 696
55 lwarp-bophook.sty 698
56 lwarp-bounddvi.sty 699
57 lwarp-boxedminipage.sty 699
58 lwarp-boxedminipage2e.sty 699
59 lwarp-braket.sty 699
60 lwarp-breakurl.sty 700
61 lwarp-breqn.sty 700

62 lwarp-bsheaders.sty 702
63 lwarp-bussproofs.sty 702
64 lwarp-bxpapersize.sty 703
65 lwarp-bytefield.sty 703
66 lwarp-cancel.sty 703
67 lwarp-canoniclayout.sty 704
68 lwarp-caption.sty 704
69 lwarp-caption3.sty 706
70 lwarp-cases.sty 709
71 lwarp-ccicons.sty 709
72 lwarp-centerlastline.sty 710
73 lwarp-centernot.sty 710
74 lwarp-changebar.sty 711
75 lwarp-changelayout.sty 711
76 lwarp-changepage.sty 712
77 lwarp-changes.sty 712
78 lwarp-chappg.sty 717
79 lwarp-chapterbib.sty 717
80 lwarp-chemfig.sty 718
81 lwarp-chemformula.sty 720
82 lwarp-chemgreek.sty 725
83 lwarp-chemmacros.sty 725
191 chemmacros 725
191.1 Changes to the user's document 726
191.2 Code 726
191.3 Loading modules 726
191.4 New environments 726
191.5 Acid-base 727

191.6 Charges . . . 729
191.7 Nomenclature . . . 729
191.8 Particles . . . 731
191.9 Phases . . . 732
191.10 Mechanisms . . . 732
191.11 Newman . . . 734
191.12 Orbital . . . 735
191.13 Reactions . . . 735
191.14 Redox . . . 736
191.15 Scheme . . . 737
191.16 Spectroscopy . . . 737
191.17 Thermodynamics . . . 741

84 lwarp-chemnum.sty . . . 743
85 lwarp-chkfloat.sty . . . 744
86 lwarp-chngpage.sty . . . 744
87 lwarp-cite.sty . . . 744
88 lwarp-citeref.sty . . . 745
89 lwarp-CJK.sty . . . 745
90 lwarp-CJKutf8.sty . . . 746
91 lwarp-classicthesis.sty . . . 746
92 lwarp-cleveref.sty . . . 747
93 lwarp-clrdblpg.sty . . . 750
94 lwarp-cmbright.sty . . . 750
95 lwarp-cmdtrack.sty . . . 751
96 lwarp-colonequals.sty . . . 751
97 lwarp-color.sty . . . 752
98 lwarp-colortbl.sty . . . 752
99 lwarp-continue.sty . . . 754

100 lwarp-copyrightbox.sty 754
101 lwarp-crop.sty 755
102 lwarp-ctable.sty 755
103 lwarp-cuted.sty 758
104 lwarp-cutwin.sty 758
105 lwarp-dblfloatfix.sty 759
106 lwarp-dblfnote.sty 759
107 lwarp-dcolumn.sty 759
108 lwarp-decimal.sty 760
109 lwarp-decorule.sty 760
110 lwarp-diagbox.sty 760
111 lwarp-dingbat.sty 762
112 lwarp-DotArrow.sty 763
113 lwarp-dotlessi.sty 763
114 lwarp-dprogress.sty 764
115 lwarp-draftcopy.sty 764
116 lwarp-draftfigure.sty 764
117 lwarp-draftwatermark.sty 765
118 lwarp-drftcite.sty 765
119 lwarp-easy-todo.sty 766
120 lwarp-ebook.sty 766
121 lwarp-econometrics.sty 767
122 lwarp-ed.sty 769
123 lwarp-ellipsis.sty 770
124 lwarp-embrac.sty 770
125 lwarp-emptypage.sty 771
126 lwarp-endfloat.sty 771

127 lwarp-endheads.sty 772
128 lwarp-endnotes.sty 773
129 lwarp-engtlc.sty 774
130 lwarp-enotez.sty 778
131 lwarp-enumerate.sty 780
132 lwarp-enumitem.sty 781
133 lwarp-epigraph.sty 781
134 lwarp-epsf.sty 782
135 lwarp-epsfig.sty 782
136 lwarp-epstopdf.sty 783
137 lwarp-epstopdf-base.sty 783
138 lwarp-eqlist.sty 784
139 lwarp-eqparbox.sty 785
140 lwarp-errata.sty 786
141 lwarp-eso-pic.sty 787
142 lwarp-esvect.sty 788
143 lwarp-etoc.sty 788
144 lwarp-eurosym.sty 790
145 lwarp-everypage.sty 791
146 lwarp-everyshi.sty 791
147 lwarp-extarrows.sty 791
148 lwarp-extramarks.sty 792
149 lwarp-fancybox.sty 792
150 lwarp-fancyhdr.sty 798
151 lwarp-fancypar.sty 799
152 lwarp-fancyref.sty 800
153 lwarp-fancytabs.sty 800

154 lwarp-fancyvrb.sty 801
155 lwarp-fbox.sty 808
156 lwarp-fewerfloatpages.sty 810
157 lwarp-figcaps.sty 810
158 lwarp-figsize.sty 811
159 lwarp-fitbox.sty 811
160 lwarp-fix2col.sty 812
161 lwarp-fixmath.sty 812
162 lwarp-fixme.sty 812
163 lwarp-fixmetodonotes.sty 814
164 lwarp-flafter.sty 814
165 lwarp-flippdf.sty 814
166 lwarp-float.sty 815
167 lwarp-floatflt.sty 816
168 lwarp-floatpag.sty 817
169 lwarp-floatrow.sty 818
170 lwarp-fltrace.sty 823
171 lwarp-flushend.sty 823
172 lwarp-fnbreak.sty 823
173 lwarp-fncychap.sty 824
174 lwarp-fnlineno.sty 824
175 lwarp-fnpara.sty 825
176 lwarp-fnpos.sty 825
177 lwarp-fontawesome.sty 825
178 lwarp-fontawesome5.sty 827
179 lwarp-fontaxes.sty 827
180 lwarp-fontenc.sty 828

181 lwarp-footmisc.sty 828
182 lwarp-footnote.sty 829
183 lwarp-footnotebackref.sty 830
184 lwarp-footnotehyper.sty 830
185 lwarp-footnoterange.sty 830
186 lwarp-footnpag.sty 831
187 lwarp-foreign.sty 831
188 lwarp-forest.sty 831
189 lwarp-fouridx.sty 832
190 lwarp-fourier.sty 832
191 lwarp-framed.sty 834
192 lwarp-froufrou.sty 836
193 lwarp-ftcap.sty 837
194 lwarp-ftnright.sty 837
195 lwarp-fullminipage.sty 837
196 lwarp-fullpage.sty 837
197 lwarp-fullwidth.sty 837
198 lwarp-fvextra.sty 838
199 lwarp-fwlw.sty 841
200 lwarp-gensymb.sty 841
201 lwarp-gentombow.sty 842
202 lwarp-geometry.sty 842
203 lwarp-ghsystem.sty 843
204 lwarp-gindex.sty 843
205 lwarp-gloss.sty 844
206 lwarp-glossaries.sty 845
207 lwarp-gmeometric.sty 847

208 lwarp-graphics.sty 847

316 graphics 847

316.1 Graphics extensions 847

316.2 Length conversions and graphics options 848

316.3 Printing HTML styles 851

316.4 \includegraphics 851

316.5 Boxes 857

209 lwarp-graphicx.sty 860

210 lwarp-grffile.sty 860

211 lwarp-grid.sty 860

212 lwarp-grid-system.sty 861

213 lwarp-gridset.sty 861

214 lwarp-hang.sty 861

215 lwarp-hanging.sty 863

216 lwarp-hepunits.sty 864

217 lwarp-hhline.sty 865

218 lwarp-hhtensor.sty 866

219 lwarp-hypbmsec.sty 866

220 lwarp-hypcap.sty 866

221 lwarp-hypdestopt.sty 867

222 lwarp-hypernat.sty 867

223 lwarp-hyperref.sty 867

224 lwarp-hyperxmp.sty 877

225 lwarp-hyphenat.sty 878

226 lwarp-idxlayout.sty 879

227 lwarp-ifoddpage.sty 880

228 lwarp-imakeidx.sty 880

229 lwarp-impnattypo.sty 884

230 lwarp-index.sty 884
231 lwarp-inputtrc.sty 886
232 lwarp-intopdf.sty 886
233 lwarp-isomath.sty 887
234 lwarp-isotope.sty 887
235 lwarp-jurabib.sty 889
236 lwarp-karnaugh-map.sty 890
237 lwarp-keyfloat.sty 893
238 lwarp-keystroke.sty 899
239 lwarp-kpfonts.sty 900
240 lwarp-kpfonts-otf.sty 901
241 lwarp-layaureo.sty 903
242 lwarp-layout.sty 903
243 lwarp-layouts.sty 903
244 lwarp-leading.sty 906
245 lwarp-leftidx.sty 906
246 lwarp-letterspace.sty 907
247 lwarp-lettrine.sty 907
248 lwarp-libertinust1math.sty 908
249 lwarp-lineno.sty 914
250 lwarp-lips.sty 917
251 lwarp-listings.sty 917
252 lwarp-listliketab.sty 923
253 lwarp-lltjext.sty 924
254 lwarp-longtable.sty 925
255 lwarp-lpic.sty 928
256 lwarp-lscape.sty 928

257 lwarp-ltablex.sty 928
258 lwarp-ltcaption.sty 929
259 lwarp-ltxgrid.sty 929
260 lwarp-ltxtable.sty 929
261 lwarp-lua-check-hyphen.sty 930
262 lwarp-lua-visual-debug.sty 930
263 lwarp-luacolor.sty 930
264 lwarp-luamplib.sty 930
265 lwarp-luatexko.sty 931
266 lwarp-luatodonotes.sty 933
267 lwarp-luavlna.sty 935
268 lwarp-lyluatex.sty 935
269 lwarp-magaz.sty 937
270 lwarp-makeidx.sty 938
271 lwarp-manyfoot.sty 938
272 lwarp-marginal.sty 940
273 lwarp-marginfit.sty 940
274 lwarp-marginfix.sty 941
275 lwarp-marginnote.sty 941
276 lwarp-marvosym.sty 942
277 lwarp-mathalpha.sty 942
278 lwarp-mathastext.sty 943
279 lwarp-mathcomp.sty 944
280 lwarp-mathdesign.sty 944
281 lwarp-mathdots.sty 946
282 lwarp-mathfixs.sty 946
283 lwarp-mathpazo.sty 946

284 lwarp-mathptmx.sty 947
285 lwarp-mathspec.sty 948
286 lwarp-mathtools.sty 949
287 lwarp-mattens.sty 956
288 lwarp-maybemath.sty 957
289 lwarp-mcaption.sty 958
290 lwarp-mdframed.sty 958
398 mdframed 958
398.1 Limitations 959
398.2 Package loading 959
398.3 Patches 959
398.4 Initial setup 960
398.5 Color and length HTML conversion 960
398.6 Environment encapsulation 961
398.7 Mdframed environment 962
398.8 Titles and subtitles 963
398.9 New environments 965
291 lwarp-mdwmath.sty 967
292 lwarp-media9.sty 968
293 lwarp-memhfixc.sty 970
294 lwarp-menukeys.sty 970
295 lwarp-metalogo.sty 971
296 lwarp-metalogox.sty 971
297 lwarp-mhchem.sty 972
298 lwarp-microtype.sty 974
299 lwarp-midfloat.sty 975
300 lwarp-midpage.sty 976
301 lwarp-minibox.sty 976

302 lwarp-minitoc.sty 977
303 lwarp-minted.sty 977
304 lwarp-mismath.sty 978
305 lwarp-mleftright.sty 982
306 lwarp-morefloats.sty 982
307 lwarp-moreverb.sty 982
308 lwarp-movie15.sty 983
309 lwarp-mparhack.sty 985
310 lwarp-multibib.sty 985
311 lwarp-multicap.sty 985
312 lwarp-multicol.sty 986
313 lwarp-multicolrule.sty 987
314 lwarp-multimedia.sty 987
315 lwarp-multiobjective.sty 988
316 lwarp-multirow.sty 989
317 lwarp-multitoc.sty 993
318 lwarp-musicography.sty 993
319 lwarp-nameauth.sty 996
320 lwarp-nameref.sty 997
321 lwarp-natbib.sty 998
322 lwarp-nccfancyhdr.sty 999
323 lwarp-nccfoots.sty 999
324 lwarp-nccmath.sty 1000
325 lwarp-needspace.sty 1001
326 lwarp-newpxmath.sty 1001
327 lwarp-newtxmath.sty 1002
328 lwarp-newtxsf.sty 1003

329 lwarp-nextpage.sty 1004
330 lwarp-nfssext-cfr.sty 1005
331 lwarp-nicefrac.sty 1011
332 lwarp-niceframe.sty 1012
333 lwarp-nicematrix.sty 1012
334 lwarp-noitcrul.sty 1015
335 lwarp-nolbreaks.sty 1015
336 lwarp-nomencl.sty 1015
337 lwarp-nonfloat.sty 1016
338 lwarp-nonumonpart.sty 1016
339 lwarp-nopageno.sty 1016
340 lwarp-notes.sty 1017
341 lwarp-notespages.sty 1017
342 lwarp-nowidow.sty 1018
343 lwarp-ntheorem.sty 1018
451 ntheorem 1018
451.1 Limitations 1019
451.2 Options 1019
451.3 Remembering the theorem style 1020
451.4 HTML cross-referencing 1023
451.5 \newtheoremstyle 1023
451.6 Standard styles 1023
451.7 Additional objects 1025
451.8 Renewed standard configuration 1025
451.9 amsthm option 1026
451.10 Ending a theorem 1028
451.11 \NoEndMark 1029
451.12 List-of 1029

451.13 Symbols 1029
451.14 Cross-referencing 1030
344 **lwarp-octave.sty 1030**
345 **lwarp-orcidlink.sty 1031**
346 **lwarp-overpic.sty 1032**
347 **lwarp-pagegrid.sty 1032**
348 **lwarp-pagenote.sty 1033**
349 **lwarp-pagesel.sty 1033**
350 **lwarp-paralist.sty 1033**
351 **lwarp-parallel.sty 1034**
352 **lwarp-parcolumns.sty 1036**
353 **lwarp-parnotes.sty 1038**
354 **lwarp-parskip.sty 1039**
355 **lwarp-pbalance.sty 1039**
356 **lwarp-pbox.sty 1039**
357 **lwarp-pdfcol.sty 1040**
358 **lwarp-pdfcolfoot.sty 1040**
359 **lwarp-pdfcolmk.sty 1041**
360 **lwarp-pdfcolparallel.sty 1041**
361 **lwarp-pdfcolparcolumns.sty 1041**
362 **lwarp-pdfcomment.sty 1042**
363 **lwarp-pdfcrypt.sty 1042**
364 **lwarp-pdflscape.sty 1043**
365 **lwarp-pdfmarginpar.sty 1043**
366 **lwarp-pdfpages.sty 1043**
367 **lwarp-pdfprivacy.sty 1046**
368 **lwarp-pdfrender.sty 1046**

369 lwarp-pdfsync.sty 1046
370 lwarp-pdftricks.sty. 1046
371 lwarp-pdfx.sty. 1047
372 lwarp-perpage.sty 1047
373 lwarp-pfnote.sty 1049
374 lwarp-phfqit.sty 1049
375 lwarp-physics.sty 1049
376 lwarp-physunits.sty 1050
377 lwarp-picinpar.sty 1051
378 lwarp-pifont.sty 1053
379 lwarp-pinlabel.sty 1054
380 lwarp-placeins.sty 1054
381 lwarp-plarydshln.sty 1054
382 lwarp-plext.sty 1055
383 lwarp-plextarydshln.sty 1056
384 lwarp-plextcolortbl.sty 1056
385 lwarp-plimsoll.sty 1056
386 lwarp-prelim2e.sty. 1056
387 lwarp-prettyref.sty. 1057
388 lwarp-preview.sty 1057
389 lwarp-psfrag.sty 1057
390 lwarp-psfragx.sty 1058
391 lwarp-pst-eps.sty 1059
392 lwarp-pstool.sty 1059
393 lwarp-pstricks.sty 1060
394 lwarp-pxatbegshi.sty 1060
395 lwarp-pxeveryshi.sty 1060

396 lwarp-pxfonts.sty 1061
397 lwarp-pxftnright.sty 1061
398 lwarp-pxjahyper.sty 1061
399 lwarp-quotchap.sty 1061
400 lwarp-quoting.sty 1063
401 lwarp-ragged2e.sty 1063
402 lwarp-realscripts.sty 1064
403 lwarp-refcheck.sty 1067
404 lwarp-register.sty 1067
405 lwarp-relsize.sty 1068
406 lwarp-repeatindex.sty 1069
407 lwarp-repltext.sty 1070
408 lwarp-resizegather.sty 1071
409 lwarp-returntogrid.sty 1071
410 lwarp-rlepsf.sty 1071
411 lwarp-rmathbr.sty 1072
412 lwarp-rmpage.sty 1072
413 lwarp-romanbar.sty 1072
414 lwarp-romanbarpagenumber.sty 1072
415 lwarp-rotating.sty 1073
416 lwarp-rotfloat.sty 1073
417 lwarp-rviewport.sty 1074
418 lwarp-savetrees.sty 1075
419 lwarp-scalefnt.sty 1075
420 lwarp-scalerel.sty 1075
421 lwarp-schemata.sty 1076
422 lwarp-scrextend.sty 1076

423 lwarp-scrhack.sty 1080
424 lwarp-scrlayer.sty 1080
425 lwarp-scrlayer-notecolumn.sty 1082
426 lwarp-scrlayer-scrpage.sty 1082
427 lwarp-scrpage2.sty 1084
428 lwarp-section.sty 1085
429 lwarp-sectionbreak.sty 1085
430 lwarp-sectsty.sty 1086
431 lwarp-selectp.sty 1086
432 lwarp-semantic-markup.sty 1087
433 lwarp-seqsplit.sty 1088
434 lwarp-setspace.sty 1089
435 lwarp-shadethm.sty 1090
436 lwarp-shadow.sty 1090
437 lwarp-shapepar.sty 1090
438 lwarp-showidx.sty 1091
439 lwarp-showkeys.sty 1091
440 lwarp-showtags.sty 1091
441 lwarp-shuffle.sty 1092
442 lwarp-sidecap.sty 1093
443 lwarp-sidenotes.sty 1093
444 lwarp-simplebnf.sty 1095
445 lwarp-SIunits.sty 1096
446 lwarp-siunitx.sty 1105
447 lwarp-siunitx-v2.sty 1105
448 lwarp-skmath.sty 1120
449 lwarp-slantsc.sty 1125

450 lwarp-slashed.sty 1125
451 lwarp-soul.sty 1126
452 lwarp-soulpos.sty 1128
453 lwarp-soulutf8.sty 1128
454 lwarp-splitbib.sty 1128
455 lwarp-splitidx.sty 1129
456 lwarp-srcltx.sty 1131
457 lwarp-srctex.sty 1131
458 lwarp-stabular.sty 1131
459 lwarp-stackengine.sty 1132
460 lwarp-stackrel.sty 1134
461 lwarp-statex2.sty 1134
462 lwarp-statistics.sty 1138
463 lwarp-statmath.sty 1144
464 lwarp-steinmetz.sty 1145
465 lwarp-stfloats.sty 1146
466 lwarp-struktex.sty 1146
467 lwarp-subcaption.sty 1147
468 lwarp-subfig.sty 1147
469 lwarp-subfigure.sty 1152
470 lwarp-subsupscripts.sty 1152
471 lwarp-supertabular.sty 1154
472 lwarp-svg.sty 1155
473 lwarp-swfigure.sty 1156
474 lwarp-syntonly.sty 1156
475 lwarp-tabfigures.sty 1157
476 lwarp-tablefootnote.sty 1157

477 lwarp-tabls.sty 1157
478 lwarp-tabularx.sty 1157
479 lwarp-tabulary.sty 1158
480 lwarp-tagpdf.sty 1158
481 lwarp-tascmac.sty 1161
482 lwarp-tcolorbox.sty 1162
483 lwarp-tensor.sty 1168
484 lwarp-termcal.sty 1169
485 lwarp-textarea.sty 1170
486 lwarp-textcomp.sty 1170
487 lwarp-textfit.sty 1174
488 lwarp-textpos.sty 1174
489 lwarp-theorem.sty 1175
490 lwarp-thinsp.sty 1179
491 lwarp-thm-listof.sty 1179
492 lwarp-thm-restate.sty 1180
493 lwarp-thmbox.sty 1180
494 lwarp-thmtools.sty 1181
495 lwarp-threadcol.sty 1181
496 lwarp-threeparttable.sty 1182
497 lwarp-threeparttablex.sty 1183
498 lwarp-thumb.sty 1184
499 lwarp-thumbs.sty 1184
500 lwarp-tikz.sty 1184
501 lwarp-tikz-imagelabels.sty 1186
502 lwarp-titleps.sty 1186
503 lwarp-titleref.sty 1189

504 lwarp-titlesec.sty 1189
505 lwarp-titletoc.sty 1191
506 lwarp-titling.sty 1193
507 lwarp-tocbasic.sty 1197
508 lwarp-tocbibind.sty 1198
509 lwarp-tocdata.sty 1199
510 lwarp-tocenter.sty 1201
511 lwarp-tocloft.sty 1201
512 lwarp-tocstyle.sty 1207
513 lwarp-todo.sty 1207
514 lwarp-todonotes.sty 1208
515 lwarp-topcapt.sty 1210
516 lwarp-tram.sty 1210
517 lwarp-transparent.sty 1211
518 lwarp-trimclip.sty 1211
519 lwarp-trivfloat.sty 1212
520 lwarp-truncate.sty 1213
521 lwarp-turnthepage.sty 1213
522 lwarp-twoup.sty 1213
523 lwarp-txfonts.sty 1213
524 lwarp-txgreeks.sty 1214
525 lwarp-typearea.sty 1214
526 lwarp-typicons.sty 1215
527 lwarp-ulem.sty 1216
528 lwarp-umoline.sty 1217
529 lwarp-underscore.sty 1218
530 lwarp-unicode-math.sty 1218

531 lwarp-units.sty 1222
532 lwarp-unitsdef.sty 1223
533 lwarp-upgreek.sty 1224
534 lwarp-upref.sty 1224
535 lwarp-url.sty 1225
536 lwarp-ushort.sty 1225
537 lwarp-uspace.sty 1225
538 lwarp-varioref.sty 1226
539 lwarp-verse.sty 1226
540 lwarp-versonotes.sty 1228
541 lwarp-vertbars.sty 1228
542 lwarp-vmargin.sty 1229
543 lwarp-vowel.sty 1229
544 lwarp-vpe.sty 1230
545 lwarp-vwcol.sty 1230
546 lwarp-wallpaper.sty 1232
547 lwarp-watermark.sty 1232
548 lwarp-widetable.sty 1233
549 lwarp-widows-and-orphans.sty 1233
550 lwarp-witharrows.sty 1233
551 lwarp-wrapfig.sty 1235
552 lwarp-xbmks.sty 1236
553 lwarp-xcolor.sty 1237
661 xcolor 1237
661.1 Limitations 1237
661.2 xcolor definitions: location and timing 1237
661.3 Package loading 1239
661.4 Remembering and restoring original definitions 1239

661.5 \normalcolor . . . 1239
661.6 HTML color style . . . 1240
661.7 HTML border . . . 1241
661.8 High-level macros . . . 1241
661.9 Row colors . . . 1246

554 lwarp-xechangebar.sty . . . 1247
555 lwarp-xellipsis.sty . . . 1247
556 lwarp-xetexko.sty . . . 1248
557 lwarp-xevlna.sty . . . 1248
558 lwarp-xfakebold.sty . . . 1249
559 lwarp-xfrac.sty . . . 1249
560 lwarp-xltabular.sty . . . 1251
561 lwarp-xltxtra.sty . . . 1252
562 lwarp-xmpincl.sty . . . 1252
563 lwarp-xpiano.sty . . . 1253
564 lwarp-xpinyin.sty . . . 1253
565 lwarp-xr.sty . . . 1255
566 lwarp-xr-hyper.sty . . . 1255
567 lwarp-xtab.sty . . . 1255
568 lwarp-xunicode.sty . . . 1257
569 lwarp-xurl.sty . . . 1258
570 lwarp-xy.sty . . . 1258
571 lwarp-zhlineskip.sty . . . 1260
572 lwarp-zwpagelayout.sty . . . 1260
573 lwarp-patch-komascript.sty . . . 1261
574 lwarp-patch-memoir.sty . . . 1263

682 patch-memoir . . . 1263
682.1 Packages . . . 1265

682.2 Label handling . . . 1266
682.3 Page layout . . . 1267
682.4 Text and fonts . . . 1269
682.5 Titles . . . 1270
682.6 Abstracts . . . 1270
682.7 Docment divisions . . . 1270
682.8 Pagination and headers . . . 1273
682.9 Paragraphs and lists . . . 1274
682.10 Contents lists . . . 1275
682.11 Floats and captions . . . 1279
682.12 Footnotes and page notes . . . 1283
682.13 Decorative text . . . 1285
682.14 Poetry . . . 1285
682.15 Boxes, verbatims and files . . . 1285
682.16 Cross referencing . . . 1286
682.17 Back matter . . . 1287
682.18 Miscellaneous . . . 1288
682.19 ccaption emulation . . . 1289
682.20 Final patchwork . . . 1292

575 lwarp-common-multimedia.sty . . . 1292

576 lwarp-common-mathjax-letters.sty . . . 1297

577 lwarp-common-mathjax-newpxtxmath.sty . . . 1304

578 lwarp-common-mathjax-nonunicode.sty . . . 1309

579 lwarp-common-mathjax-overlaysymbols.sty . . . 1312

Change History . . . 1314

688 Chg Hist . . . 1314

Index of Objects . . . 1353

General Index . . . 1377

Troubleshooting Index . . . 1382

Index of Indexes **1389**

List of Figures

1 tutorial.tex listing 86

List of Tables

1 Typesetting conventions 67
2 LaTeX lwarp package — Supported features 68
3 Required software programs 79
4 Configuration files created by print version 88
5 Localization settings 101
6 Accessibiltiy settings 102
7 Lwarp package options 107
8 HTML settings 112
9 \includegraphics and file names 160
10 Literal character macros 179
11 Section HTML headings for word-processor conversion 187
12 Section depths and HTML headings 203
13 Tabular baseline 465
14 Tabular HTML column conversions 466
15 Cross-referencing data structures 508
16 Float data structures 520
17 CSS related to the sidetoc 532
18 amsthm package — CSS styling of theorems and proofs 661
19 Ntheorem package — CSS styling of theorems and proofs 1018
20 Theorem package — CSS styling of theorems and proofs 1175

1 Updates

The following is a summary of updates to lwarp, highlighting new features and any special changes which must be made due to improvements or modifications in lwarp itself.

For a detailed list of the most recent changes, see the end of the Change History on page 1352.

v0.899: Minor updates.

- *lwarpmk*: Warns if `\usepackage{lwarp}` is not detected.

packages
- graphics: Added support for `keepaspectratio`.
- keyfloat: Fix: `lw` with `h`.
- multicol: Improved css.

v0.898: Minor updates.

- Fewer underfull `\hbox` warnings.
- wrapfig: Improved integration with keyfloat.

v0.897: siunitx rollback.

docs
- Added a table of file extensions to use with `\includegraphics`. See table 9.

core
- Added tests for additional incompatible packages.

packages
- siunitx: Supports rollback to v2. Does not yet support v3.
- fixme: Improved to work if the user modifies layouts.
- float: Improved integration with newfloat, keyfloat.
- Added centerlastline, decorule, fancypar, froufrou, pbalance.
- Verified works as-is with fnpct.

v0.896: Back references, accessibility.

⚠
- Due to changes in cross referencing, execute **`lwarpmk clean`** before recompiling.
- Increased sectioning nesting stack depth. Error if overflow stack.
- Fixed footnotes at the end of the document, or inside a `description` label.
- Added an error if using braces inside `\usepackage` options.

MathJax
- Fixed footnotes in bracket display math with MathJax.

theorems
- LaTeX theorems, amsthm, ntheorem, theorem: Print theorem footnotes following theorems.

accessibility
- Added HTML `<main>` element to each page.
- Added ARIA `math` role to SVG math images, and `note` role to margin notes, footnotes, etc.

packages
- Improved citation backreferences for various packages.
- chemfig: Updated to v1.6a.
- bigdelim: Updated to v2.8.

- xetexko: Updated to v3.1.
- hyperxmp: Fix: Accept and discard additional keys.
- hyperref: Fix: Added `\*autorefname` macros.
- biblatex: Fix: Back references.
- tocloft: Fix: `\cftpagenumbersoff`, `\cftpagenumberson`.
- threeparttablex: Fix: `\TPTL@tnotex`.
- amsthm: Fix: Footnotes inside environment optional argument.
- listings: Fixed labels. Accepts but ignores escapes w/o error.
- pdflscape: Fix: Added `landscape` environment.
- Added ccicons, classicthesis, orcidlink.
- Added enotez.
- Verified support for doi, doipubmed.

v0.895: Vector packages, greatly improved MathJax for siunitx.

core
- Fixed quotes in HTML tags while using old font packages with XeLaTeX and LuaLaTeX.

MathJax
- Added `\ifblank` and `\ifstrequal` to MathJax emulation.

packages
- multirow: Allow `\par` per v2.7.
- acro: Updated to v3.5.
- fancyhdr: Updated to v4.0.
- changes: Updated to v4.0.1.
- epsfig, rotating: Now work inside `lateximage`.
- amscdx: Verified to work with SVG math. Warning added about use with MathJax.
- Added MathJax emulation for isomath, mattens, maybemath, skmath, tensor.
- Improved MathJax emulation for siunitx `\ang`, `\num`, `\SI`.
- Added epsf, impnattypo, isotope, lpic, luavlna, mdwmath, pinlabel, rlepsf, tikz-imagelabels, xevlna.
- Verified to work as-is: tensind.

v0.894: MathJax additions and improvements.

MathJax
- Improved warning message for enabling SVG graphics for select math expressions while using MathJax.
- Accept and ignore a star for `\hspace`.
- Ignores `\arabic`, `\number`, `\noalign`.

packages
- Added MathJax emulation for backnaur, colortbl, nicematrix.
- booktabs: MathJax emulation now absorbs and discards trim.
- menukeys: Updated to v1.6.1.

v0.893: Minor fixes, more packages.

MathJax
- Added MathJax emulation for `\mathnormal`.

packages
- Fixed pstricks `pspicture*`.
- Fixed tikz font macros.
- braket: Now uses the MathJax extension.
- Added esvect, fixmath, keystroke, mathastext, menukeys, picinpar, plimsoll, repltext, selectp, seqsplit, simplebnf, statistics, swfigure.
- Added MathJax emulation for mathspec.
- Verified to work as-is for apxproof, syntaxdi, venndiagram.

v0.892: minted, fvextra, MathJax `\left/\right`.

MathJax
- fourier, libertinust1math, newpxmath, newtxmath, newtxsf, unicode-math: Added MathJax `\left/\right` support for additional delimiters.

packages
- textpos: Updated to v1.10.
- xcolor: Fixed optional args for `\fcolorbox` and related.
- Added fvextra, minted.

v0.891: MathJax additions and improvements.

core
- Now displays inline `\verb` text as `\texttt`.
- Fixed alltt and verbatims with LaTeX lists.
- Now generates an error if nested each of `warpHTML`, `warpprint`, `warpMathJax` inside itself.

MathJax
- Added MathJax *textmacros* extension, allowing formatting inside `\text`.

packages
- biblatex, hyperref: Added back page references.
- fancyvrb: Fixed `BVerbatim` with a label.
- listings: Fixed MathJax with captions, improved HTML sanitation.
- babel-french: Fixed `\texorpdfstring` conflict.
- Now honors Greek package options for mathdesign, mathpazo, mathptmx, newpxmath, newtxmath.
- Improved MathJax for colonequals, mathdesign, mathdots, mathfixs, mathtools, multiobjective, nicefrac, shuffle, units.
- unicode-math: Added Greek macros, as well as macros for the first several categories listed in **`texdoc unimath-symbols`**. Improved symbol shape macros with Greek. Improved documentation.
- Added bussproofs, cmbright, fourier, kpfonts, kpfonts-otf, libertinust1math, scalerel, txgreeks.

v0.89: Additional MathJax support.

core
- Adapted to upcoming LaTeX kernel changes.
- Allows load of amsmath before lwarp.

lwarpmk
- Also removes `*.bbl` when cleaning aux files.

MathJax
- MathJax: Neutralized `\protect`, `\mathcode` and related, ligatures. Fixed nested environments.

packages
- caption: Updated for v3.5, fix for label sep.
- thmtools: Updated for v0.72. Fixed `swapnumber`, `margin`.
- Improved MathJax for centernot, mathtools, mismath, SIunits, siunitx, statmath.
- Added MathJax emulation for accents, hepunits, hhtensor, mathalpha, mathdesign, mathpazo, mathptmx, mleftright, newpxmath, newtxmath, newtxsf, pxfonts, shuffle, txfonts, upgreek, ushort.
- Verified to work as-is: authoraftertitle.

v0.88: Indexing, boxing, theorems.

- Now has programmed support for more than 500 packages and classes, of which more than 60 also support MathJax.

core
- Fixed: `\ref*`, and also added MathJax emulation.
- If starting a new paragraph, `\hrulefill` creates a `<div>` with a thin horizontal line across the page. Use instead of `\hrule`.
- Fixed: Use `\chaptername` where appropriate.
- Fixed: Inline links causing extraneous paragraphs.

lwarpmk
- Added **`lwarpmk -v`** to print the version number.

indexing
- Added the `IndexRef` option to control the display of index entries. See section 7.5.
- Added `\IndexPageSeparator` and `\IndexRangeSeparator` for custom index styles.
- Added support for gindex, *xindex*.
- Verified to work as-is with varindex.

packages
- cleveref, varioref: Fix for starred macros.
- varioref: Removed page-related text from HTML output.
- xfakebold: Updated to v0.08, using pdfrender.
- caption, scrextend: Fixed `\caption*`.
- Added fbox, shadethm, tcolorbox, termcal, thmbox, thmtools.

v0.87: MathJax, bibliography packages.

core
- Added boolean `FixSmallCaps` for fonts which render small caps as all caps.
- Fixed `\bibliography` to use the HTML version's `.bbl` file. Previously the HTML bibliography relied on the print version's `.bbl`, thus would fail if the print document had not yet been created.

MathJax
- Added `\ifstar` and `\ifnextchar` to MathJax, and removed `\DeclareIfstar`. See section 8.7.5.

⚠ Removed `\DeclareIfstar`

packages
- physics: Now supports the MathJax v3 extension.
- mathtools: Improved `\underbrakcet`, `\overbracket` for MathJax.
- nccmath: Improved `\underrel` for MathJax.

- mhchem: Now supports the MathJax v3 extension for `\ce` inside math.
- cancel: Now supports the MathJax v3 extension.
- embrac: Neutralized kerning for improved HTML conversion.
- Added citeref, drftcite, jurabib, multibib, splitbib.
- Verified to work as-is with bibtopic, collref, mciteplus.

v0.86: MathJax major updates.

core
- Fixed: Filename if named files with `*`, parens, period in section name.
- Fixed: Labels in `eqnarray`, `lateximage`.

MathJax
- Updated to MathJax v3. New repository.
- Fixed forward references for MathJax.
- Improved MathJax equation number formatting, now compatible with amsmath `\numberwithin` for chapters, sections, subsections, as well as amsmath `subequations`. See section 8.7.5.
- Added `\DeclareIfstar` to define starred TeX macros in MathJax. See section 8.7.5.
- Generates an error if `\MathJaxFilename` file does not exist.

packages
- mathtools, nccmath, physics: Added starred macros for MathJax.
- nccmath: Fixed `\nr`, `\displaybreak` for MathJax.
- xcolor: Fixed `\textcolor` with babel-french.

v0.85: fontspec

packages
- fontspec: Fixed core font change macros for world languages.

⚠ acro formats
- acro: Due to v3 changes, when defining acronym formats, use `\textbf` instead of `\bfseries`, etc.
- Fixed idxlayout, mathtools, titlesec, url.

v0.84: Previous/next page links, numerous fixes.

docs
- Added documentation of `BlockClass` and `\InlineClass` for CSS `<div>`s and `<span>`s. See section 7.8.
- Added `\LinkPrevious`, `\LinkNext` page links. See section 7.6.

⚠ home page footer changed
- Added `\FirstPageBottom`. Home page no longer shares `\PageBottom`. See section 7.6.

core
- Improved coexistence with comment, support for nested environments.
- No longer requires but still supports the caption package.
- Improved filenames and HTML titles when using special characters.

⚠
- Change: Append `-0` to section named Index previously _index to distinguish from `index.html`
- Fixed style tags for `\multicolumn`, `\multirow`.
- Fixed spacing in `tabbing`.
- Fixed `lateximage` for: `quote`, `quotation`, `verse`, `center`, `flushleft`, `flushright`, `<par>` tags, packages verbatim, alltt, epigraph.

- Fixed textcomp due to integration into LaTeX kernel.
- Fixed \itshape, etc. Adapted to LaTeX fontaxes integration.
- Fixed \@fnsymbol.
- Warns about section names with dollar-delimited math.
- Warns about a containing a float, caption, section, mdframed, or other object.
- Only warn about XeLaTeX logo and graphics if actually used \Xe.

lwarpmk
- **lwarpmk clean** also removes comment_*.cut.

packages
- scrextend, scrartcl, scrbook: Added \titlehead, \subject, \subtitle, \publishers.
- titling: Fixed \printthanks.
- memoir, abstract: Fixed for updated memoir.
- memoir: Fixed \newcomment, pagenotes, crossreferences. Fixed setting a recursive name.
- Fixed or improved: amsthm, backref, biblatex, fixme, nfssext-cfr, ntheorem, parcolumns, realscripts, rotfloat, titling.
- Added boxedminipage, renamed from boxedminipage2e per author.
- Verified to work as-is with mcite.

v0.83: memoir fixes.

packages
- memoir: Various fixes and updates.
- physunits: Updated to v1.0.4.

v0.82: MathJax notes, xpinyin improvements, various updates.

MathJax
- Improved footnotes with MathJax.
- Added MathJax emulation for endnotes, marginnote, nccfoots, pagenote, parnotes, sidenotes.

packages
- xpinyin: Added pinyin with modern HTML.
- luatexko: Added \dotemph, \ruby, \uline, etc.
- soul: Fixed \<.
- chemfig: Updated to v1.5.
- draftwatermark: Updated to v2.0.
- ulem: Fixed: \dashuline.
- amsmath: Fixed: \intertext with MathJax.
- endnotes: Fixed: Marks in print mode.
- tocvsec2, tableof: Verified to work as-is.
- Added etoc (nullified).

v0.81: MathJax speedup and additional emulations.

core
- Improved warning regarding SVG math sizing/baselines and graphics/graphicx. See section 8.7.

MathJax
- Improved MathJax emulation processing speed.
- Added MathJax emulation for accsupp, axessibiltiy, colonequals, decimal, dotlessi, econometrics, engtlc, multiobjective, physunits, SIunits, stackrel, statmath.

packages
- axessibility: Updated to 2020/01/08 version.
- gridset: Updated to v0.3.
- SIunits: Fixed for math mode.
- Added DotArrow, nolbreaks, luamplib, returntogrid, statex2, tagpdf.
- Verified to work as-is with icomma, mathpunctspace, textualicomma.

v0.80: MathJax, biblatex.

MathJax
- Added docs and warning/info messages re: avoiding slow MathJax compilation. See section 8.7.5, Customizing MathJax.
- Added MathJax emulation for accessibility, autobreak, centernot, extarrows, fouridx, gensymb, leftidx, mathcomp, mathdots, mathfixs, mismath, nccmath, noitcrul, pdfcomment, relsize, rmathbr, subsupscripts, xfrac.
- Improved MathJax emulation for unicode-math.

packages
- biblatex, url: Now create hyperlinks.
- amsmath: Fix to center starred environments.
- xcolor, graphics: Made more macros robust.
- colortbl: Fix: Rule color in a `lateximage`.
- chemmacros: Updated to v5.10.
- Added fewerfloatpages, ghsystem, hhline, mismath, nccmath.

v0.79: MathJax, nested `tabular`.

MathJax
- Added or improved MathJax emulation for amsmath, ar, arydshln, bm, bigdelim, bigstrut, booktabs, braket, mathtools, multirow, physics, siunitx, slashed, unicode-math, xfakebold.
- Warn if using certain packages not supported by MathJax.

core
- `tabular`: Now may be nested.
- `minipage`, `\parbox`, `fminipage`, `\makebox`, `\framebox`: Fix: Adjust for virtual page size.
- Uses new iftex.

packages
- graphicx: Fix: Negative angles.
- caption: Fix: `\captionlistentry` with longtable.
- multirow: Fix: Centered vertical alignment.
- siunitx: Fix: `\square`, `\cubed`.
- booktabs: Fix: memoir with `lateximage`.

- babel and polyglossia: Added troubleshooting warnings.
- fontawesome, fontawesome5: Supports text color and size.
- transparent: Fix: `lateximages`.
- epigraph: Updated to v1.5e.
- xurl: Updated to v0.08.
- subcaption: Fixed with memoir.
- floatrow: Fix: `\linewidth`. No longer require float, graphics.
- floatflt, wrapfig, niceframe: Fix: Adjust for virtual page size.
- Added widetable, witharrows, steinmetz.
- Added awesomebox, catoptions.
- Added svg, supports svg-extract.
- Added parcolumns, pdfcolparcolumns,
- Added parallel, pdfcolparallel.
- Added pdfcol, pdfcolfoot, pdfcolmk.

v0.78: Fixes for support files, `alt` tags, hyperlinks, and the 2019/10 LaTeX release.

docs
- Docs: Improved documentation regarding package options. See section 8.1.
- Fix to overwrite existing support files using new `filecontents` environment.

packages
- breqn: Previously broken by the 2019/10 LaTeX update, but now working again.
- graphics: Fix for `\includegraphics` `alt` tags.
- babel-french: Fix for hyperlinks.
- media9, movie15, multimedia: Fix for the 2019/10 LaTeX update.
- accessibility: Added.

v0.77: Updates to fix recently-broken packages.

- booktabs: Updated to v1.6180339.
- chemformula: Updated to v4.15.

v0.76: MathJax, updates for LaTeX 2019/10 release.

docs
- Docs: Expanded documentation regarding the use of multiple projects in the same directory. See section 5.17.

MathJax
- MathJax: Updated to v2.7.6.

packages
- xr: Updated to v5.05.
- xr-hyper: Updated to v6.1.
- Verified works as-is with xcite.
- acro: Updated to v2.10.

⚠ broken
- Currently broken in print mode by the 2019/10 LaTeX update, and waiting for fixes: breqn, grffile, multimedia, movie15.

v0.75: keyfloat, wrapfig

packages
- `\minipage`: Fix for `\linewidth`.
- keyfloat: Improved color control.
- wrapfig: Fix for `\linewidth`.

v0.74: Docs, SVG math, *lwarpmk*, HTML `alt` and `title` text, lyluatex

docs
- Added to the tutorial the section What next?. See section 5.19.
- Added documentation about localization options. See section 7.1.
- Added documentation about accessibility options. See section 7.2.

HTML `alt` text
⚠ changed names
- Renamed and updated HTML `alt` text macros:

Old	New
(hard coded as "image")	`\ImageAltText`
`\mathimagename`	`\MathImageAltText`
`\packagediagramname`	`\PackageDiagramAltText`

- Added `\ImageAltText` for the default HTML `alt` text for an image. See section 7.6.
- Added `\ThisAltText`, which may be used to assign a one-time HTML `alt` tag to the very next image generated by lwarp, such as a `lateximage`, `picture`, `tikzpicture`, an image generated by various chemistry or engineering packages, or an SVG math image. This macro also adds a `title` tag to a reference or hyperlink. See section 7.6.

SVG math
- Adjusted `\LateximageFontScale` default from .75 to 1.
- Fix: Font control for SVG math.

misc
- Fix: Ignores negative `\hspace`.
- Warning if `SideTOCDepth` < `FileDepth`.

lwarpmk
- *lwarpmk*: **`lwarpmk clean`** removes additional files.
- *lwarpmk*: **`lwarpmk epstopdf`** and **`lwarpmk pdftosvg`** now honor directories.

packages
- lyluatex: Split images by `system` or per `fullpage`, improved margins and scaling.
- Tested to work as-is with mathspec, unicode-math.

v0.73: `\include`, memoir, koma-script, caption, xy, datatool, music scores.

- Fix for `\include`.
- Warning for a `tabular` inside a .
- `\color`: Added HTML support for rules and frames, but not inline text. Use `\textcolor` if possible.
- Improved many HTML tags, reducing *tidy* warnings. See Change History.

packages
- memoir: Fixes for `\frontmatter*` and `\mainmatter*`. Added `\book`.
- koma-script: Fix for starred captions in the TOC.
- caption: Fix for starred captions.
- datatool: Added pie, bar, and plot charts.

- threeparttable: Added `measuredfigure`.
- intopdf: Updated to v0.2.1.
- tocdata: Updated to v2.03.
- quotchap: Updated to v1.2.
- versonotes: Updated to v0.4.
- backnaur: Now uses SVG images. Updated to v3.1.
- xy: Fix for `\xybox`, improved `xy`, also now compatible with qcircuit.
- fancyvrb: Fix for label HTML tags.
- Added stackengine.

music
- Added lyluatex. (Music scores.)
- musicography: Updated to 2019/05/28. Added support for `lateximages`.

v0.72: Font control, `\multicolumn`, xr and xr-hyper.

⚠ images
- Due to internal changes, images for inline SVG math and `lateximages` will have new hash values, and will have to be regenerated using

  Enter ⇒ **`lwarpmk cleanlimages`**

  and

  Enter ⇒ **`lwarpmk limages`**
- Docs: Color-codes package names in the table of supported packages and features, table 2, according to each package's level of support by lwarp.
- `\multicolumn`: Fix for paragraph columns.

packages
- xr, xr-hyper: Fixes for references, `\externaldocument`.
- soulutf8: Fix: Loads soul for emulation.
- boxedminipage2e: Added support for `lateximages`.
- zhlineskip: Updated to v1.0e.
- Added fontaxes, slantsc, tabfigures.
- Added nfssext-cfr, thus supporting cfr-lm and several other font packages.
- Added backnaur, hypbmsec, minibox, pdfcrypt, shapepar.

v0.71: Error handling, multimedia, `tabular`.

- `tabular`: Added support for '`*`' columns. Fix for paragraph tags.
- `quotation`: Fix for HTML tag.
- Docs: Added a section about error conditions tested by lwarp. See section 13.1.
- *lwarpmk*: If file `lwarpmk.conf` is an older version, or the incorrect operating system, displays the print command to use to recompile.

packages
- chemfig: Updated for v1.4.
- endfloat: Updated for v2.7.
- textpos: Updated for v1.9.1.

multimedia
- Added media9, movie15, multimedia.

v0.70: Error handling, MathJax, mathtools.

- Error handling for "Label(s) changed." Refuses to **`lwarpmk limages`** until recompile first.
- Fix: If Computer Modern font is used, ensures cm-super or lmodern is used.
- Fixes for `\makebox`.
- Fixes for `\parbox` inside a `<span>`.
- MathJax: Updated to v2.7.5. Loads the `autoload-all.js` extension. Added `\MathJaxFilename` to select custom scripts.

packages

- textcomp, xunicode: Fix for `\textinterrobang`.
- mhchem: Works with MathJax. See section 405.
- changes: Updated to v3.1.2.
- Added autonum, changelayout, inputtrc, mathtools, metalogox.

v0.69: Error handling, many fixes, improved keyfloat/tocdata.

- Fix for HTML corruption of `lateximage` displays.
- `\makebox`, `\framebox`: Fix for (⟨*width,height*⟩) arguments.
- `fminipage`: Honors `\minipagefullwidth`.

packages

- array, longtable: Fix for `\tabularnewline`.
- tabularx, tabulary: Fix to require the array package.
- supertabular, xtab: Fix to clear caption after use.
- graphics: Added a warning if used the `\includegraphics scale` option.
- multirow: Added an error if didn't use `\mrowcell` or `\mcolrowcell` when using `\multirow` or `\multicolumnrow`.
- keyfloat: Updated for v2.00, additional improvements.
- Added ctable, eqlist, eqparbox, ftcap, listliketab, minitoc, tocdata, topcapt.

v0.68: Error handling, tabulars, footnotes.

lwarpmk

- *lwarpmk*: Improved error handling for image generation if compile was incomplete.
- `tabular`: Fix for `\warpprintonly`.

packages

- longtable: Improved flexibility for `\endhead`, etc. Improved error reporting if `\endhead`, etc. incorrect for lwarp.
- threeparttable: Fix for caption type.
- hyperref: Fix for options with braces.
- morefloats: Fix to be loaded early for print output.
- listings: Updated for v1.7.
- Added bigfoot, fnpara, footnotebackref, manyfoot, tablefootnote, threeparttablex.
- Added layouts, niceframe, perpage, showtags.
- Prevented alg, algorithmic, pdfcprot, fncylab.

v0.67: Filename generation, symbol fonts.

docs
- Documentation fix for `<project>-images`, `<project>-images.txt`.
- Added discussion regarding section names. See section 8.4.

filenames
- Added `\FilenameNullify` and `\FilenameSimplify` for filename generation. See section 8.4.
- Core, textcomp, xunicode: Nullified additional symbols during filename generation.

packages
- color: Fix for version number warnings.
- Added academicons, bbding, dingbat, eurosym, fontawesome, fontawesome5, marvosym, pifont, typicons.
- Added changes, easyReview, fitbox, foreign, gloss, karnaugh-map, multicap, nomencl, notes, struktex, umoline, xfakebold.
- Tested to work as-is with askmaps, curves, euro, karnaughmap, tikz-karnaugh.

v0.66: xr, multiple projects, image names/directory, HTML formatting

⚠ Reset the configuration
- Due to changes in *lwarpmk*, recompile any existing project a single time using **`pdflatex filename.tex`** or similar, after which *lwarpmk* may then be used with the new configuration files.

`lateximage`
- Adds options `ImagesDirectory` and `ImagesName` to assign directory and name prefixes for `lateximage` images. The new defaults include the jobname, allowing the image directories for multiple projects to coexist.

⚠ existing projects
- To reuse existing `lateximage` directories, add lwarp options

```
\usepackage[
  ImagesDirectory={lateximages},
  ImagesName={lateximage-}
]{lwarp}
```

  If not reused, the existing `lateximages` directory and `lateximages.txt` file may be removed.

filenames
- Added `\FilenameLimit` to control the maximum length of the filenames generated by lwarp.

⚠ Possible filename changes
- Improved filename generation when special characters or macros are used in section names.

Windows
- Fix for **`lwarpmk cleanlimages`** with Windows.

floats
- Fixes for floats in the home page.

lists, table notes
- Improved CSS for definition lists, table notes.

`tabular`
- `tabular`: Fixes for `\par` in column specifier, minipage inside `tabular`.

indexing
- Indexing: Fix for a long line of multiple entries.

`minipage`
- `\minipagefullwidth`: Fix for global changes.
- Added `\UseMinipageWidths` and `\IgnoreMinipageWidths`. See section 8.3.3.

colors
- Improved `\fbox`, `\fboxBlock`, `\fminipage` to use current text color.

HTML
- Improved HTML output formatting.

docs
- Added discussion regarding invalid HTML. See section 8.1.1.

- Added discussion regarding math in section names, `\imagegraphics scale` option. See section 6.
- Added discussion regarding international languages in section names. See section 8.14.

packages
- caption: Fix for options clash.
- xr, xr-hyper: Now compatible.
- subcaption: Improved horizontal spacing.
- multicol: Fix for minipage inside `multicols`.
- multicolrule: Updated for v1.2.
- tocbasic: Minor update.
- acronym: Fix for acronym in float caption.
- kotexutf: Patch with *pdflatex* and new lwarp labels.
- extramarks, fancyhdr: Updated for v3.10.
- memoir: Added docs regarding version numbers. See section 8.13.
- zref: No longer required.
- Added ar, ed, indentfirst, nameauth, truncate.
- Verified to work as-is with changelog.
- Prevented colortab, epsf, hyper, picinpar, picins, sistyle, ucs.

v0.65: CSS layout, `alt` tags, Japanese.

page layout
- Moved the sideTOC to the left side, allowing improved CSS for margin notes.
- Improved page layout CSS.

image `alt` tags
- graphicx `\includegraphics`: Added the `alt` key to assign an `alt` tag to an image. Default is "`image`", assigned to pass validation.

duplicate HTML files
- Detects and causes an error if duplicate HTML file names are generated, caused by identical or similar sectioning names.

fixes
- Fix for `tabular*`.
- Fix for tabular border colors.
- Fixes `\quad`, `\enskip`, and figure captions to pass validation.

Japanese
- Added ltj* classes, bounddvi, gentombow, lltjext, plarydshln, plext, plextarydshln, plextcolortbl, pxatbegshi, pxeveryshi, pxftnright, pxjahyper, tascmac.
- Verified to work with plarray, plautopatch, plextarray, plextdelarray, pxgentombow, plsiunitx, pxpdfpages, pxpgfrcs, pxpgfmark.

packages
- Added support for fontspec `\textsi` and `\sishape`.
- Added multicol's `\docolaction`.
- Added embrac, footnoterange, multicolrule, versonotes.

v0.64: Koma-Script, Japanese, Chinese.

Japanese
- Added utarticle and related classes.
- Improved ujarticle and related classes.

Chinese
- Fix for biblatex with CTEX and other classes.

Koma-Script
- Fixes for scrlayer, scrlayer-scrpage.

packages
- addlines: Updated to v0.3.
- Added bsheaders, gmeometric, marginal, rmpage, scrpage2.

v0.63: mdframed, Chinese, Japanese, Korean

localization
- Added `\linkhomename`: A user-definable name for the **Home** link.
- Documented `\sidetocname`: A user-definable name for the sideTOC.

fixes
- Fix: `\LinkHome` for print output.

optimizations
- Moved package load checks to the lwarp core to reduce the number of `lwarp-*` files.

packages
- mdframed: Fix with amsthm, improved titles and font control. Improved rule widths.

Chinese
- Fixes for xeCJK.
- Added xpinyin, zhlineskip.
- Verified to work with cjkpunct, upzhkinsoku, zhspacing.

Japanese
- Verified to work with zxjatype, luatexja, luatexja-fontspec.
- Added bxjsarticle and related classes.
- Added ltjsarticle and related classes.
- Added pLaTeX, upLaTeX, ujarticle and related classes.
- Prevented utarticle and related classes.
- Prevented bxcjkatype.

Korean
- Verified to work with kotex, xetexko, luatexko.

v0.62: MiKTEX docs, HTML title, CTEX, xeCJK, bitpattern.

docs
- Docs: Setting a UTF-8 locale. See section 9.8.

MiKTEX
- MiKTEX: Docs for *MiKTeX Console* and miktex-poppler-bin.

HTML `<title>`
- HTML subpage titles: Added `\HTMLTitleBeforeSection` and `\HTMLTitleAfterSection` to select whether the HTML `<title>` displays the website name before or after the section name. See section 7.6.

fixes
- Fix for package options handling.
- Fixes for horizontal white space between `fminipage`, `fcolorminipage`, `colorboxBlock`, `fcolorboxBlock`.
- Logos: Fix for XETEX logo, improved CSS, made robust, improved search-engine optimization.
- `\\[$1]`: Additional HTML `<br>` if $1 > 0 pt.
- Fixes for `\includgraphics` filename, and with `FormatWP`.
- Fix: CSS for `\textup`.

- Fix: Added `\slshape`.

Chinese
- Added ctex package and related classes, xeCJK.
- Prevented CJK, CJKutf8 unless xeCJK, ctex are used.

packages
- chemfig: Docs for new macro `\polymerdelim`.
- asymptote: Docs for compilation.
- chngpage: Fix to load lwarp-changepage.
- algorithm2e: Fix with non-book classes.
- register: Updated to v1.8.
- nicefrac: Improved font control and CSS, honors `nice` and `ugly`.
- units: Improved font control and CSS, honors `tight` and `loose`.
- xfrac: Improved CSS.
- textcomp and xunicode: Fix conflicts with `\textcircled`.
- ulem: Improved compatibility with CJKulem, `lateximage`.
- MathJax and siunitx: Removed inoperable extension.
- Added bitpattern, pdfcomment, pdfmarginpar, tram, unitsdef, xechangebar.
- Added musicography, octave, semantic-markup.
- Added 2in1, flippdf, notespages, rviewport, twoup.

v0.61: Custom compilation, EPS-related packages, documentation, indexes.

docs
- Split index into multiple indexes.
- Improved documentation regarding font selection. See section 7.4.
- Added documentation regarding debugging options. See section 35.
- Added documentation regarding HTML entities inside program listings. See section 8.2.1.

custom compiling
- Added options to specify the shell commands to execute for **`lwarpmk print`** and **`lwarpmk html`**, allowing the use of lwarp with perltex, pythontex, etc. If not specified, these are set automatically depending on the LaTeX engine, `--shell-escape`, and lwarp options. See section 9.

⚠ changed names
- Changed macro names to match `\displaymathother`, `\displaymathnormal`:

Old	New
`\StartDynamicMath`	`\inlinemathother`
`\StopDynamicMath`	`\inlinemathnormal`

fixes
- Fix: Paragraph tags in a `tabular`.
- Fix: supertabular and xtab captions.
- Fix: DVI LaTeX `\includegraphics` EPS images.
- Fix: newfloat lists.
- Fix: CSS footnotes text align, minipage tabular and footnote margins.

packages
- Added epsfig, psfrag, psfragx, pstool.
- Added copyrightbox, pdfprivacy, thinsp, threadcol, uspace.
- Added chkfloat, cmdtrack, dprogress, lua-visual-debug, refcheck, srcltx, srctex, vpe, xbmks.

v0.60: Fixes for longtable, listings.

fixes
- longtable, etc.: Fixes for slowdown and memory management for very long tables.
- listings: Fix for HTML entities, and also when used inside a list.
- diagbox: Fix for incorrect HTML par tags.

packages
- Added 2up, booklet.
- Added bophook, draftfigure, fullminipage, grid-system, layaureo.
- Added leading, widows-and-orphans.
- Added fancytabs, thumb, thumbs.

v0.59: DVI *latex*, MathJax, asymptote, pdftricks and pstricks, epstopdf, brqen.

⚠ Reset the configuration
- Due to changes in *lwarpmk*, recompile any existing project a single time using **`pdflatex filename.tex`** or similar, after which *lwarpmk* may then be used with the new configuration files.

lwarpmk
- Added an error if `lwarpmk.conf`'s format has changed and the document must be recompiled.
- Added a warning if the `lwarpmk.conf` configuration file appears to be for the wrong operating system, in case files are transferred between systems.
- Added
  ```
  lwarpmk epstopdf <list-of-EPS-files>
  ```
  to quickly convert a document's EPS images to PDF or SVG. See section 8.8.

DVI *latex*
- Added support for DVI *latex*. See section 7.5.

latexmk
- Fix for `--shell-escape` with *latexmk*.

math
- Updated MathJax script to v2.7.4.
- Fix: MathJax chapter number removed from non-numeric tagged equations.
- Added MathJax support for nicefrac, units.
- Fix for `\[` and `\]` with `\displaymathnormal`.

images
- Fix for `\includegraphics` filename expansion.
- `\includegraphics` now works with `.pdf` and `.eps` filename extensions.

packages
- Moved amsmath out of the lwarp core.
- Fix for chemformula `\NMR`.
- Added asymptote, pdftricks, pstricks, pst-eps.
- Added breqn, SIunits.
- Added bxpapersize, canoniclayout, draftcopy, fnbreak, nccfancyhdr.
- Added accsupp, axessibility.
- Added xunicode.
- Improved and now supports epstopdf.
- Tested to work as-is: eepic, sepfootnotes.

docs
- Added information about setting up a development version of lwarp.

v0.58: Extensive improvements in indexing, glossaries. Adds PDF-inclusion packages.

⚠ Reset the configuration

- Due to changes in *lwarpmk*, recompile any existing project a single time using **`pdflatex filename.tex`** or similar, after which *lwarpmk* may then be used with the new configuration files.

lwarpmk

- *lwarpmk*: Added the `-p` option to specify the project name.

glossaries

- *lwarpmk*: Now uses *makeglossaries* for glossary generation, allowing the processing of multiple glossaries at once.
- Added lwarp option `GlossaryCmd` to specify the shell command used by **`lwarpmk printglossary`** and **`lwarpmk htmlglossary`**. Defaults to **`makeglossaries`**.

index and glossary

- Docs: Extra indexing options. See section 8.6.14.
- Added support for *makeindex*. (Previously supported only *xindy*.) Also added indexing packages listed below.
- Added lwarp options `PrintIndexCmd`, `HTMLIndexCmd`, and `LatexmkIndexCmd` to specify shell commands used by **`lwarpmk printindex`**, **`lwarpmk htmlindex`**, and *latexmk*. May be preset with the `makeindex` or `xindy` lwarp options. See section 7.5.
- Added lwarp options `makeindex` and `xindy` to set `PrintIndexCmd`, `HTMLIndexCmd`, and `LatexmkIndexCmd` to sensible values for a typical single index. See section 7.5.
- Added lwarp option `makeindexStyle` to tell *lwarpmk* to use a custom style instead of `lwarp.ist`. See section 8.6.20.
- Fix for index entries with `\see`, `\seealso`, `\emph`, `\textbf`, etc.

misc. fixes

- Replaced each `\csuse` with `\@nameuse` for improved error detection.
- Additional internal print/HTML macro selection improvements.
- Fix: `\printindex` finishes pending `\index` writes first.

packages

- Fixes for memoir: makeidx, ccaption, multiple indexes, `\specialindex`.
- Fixes for komascript: Indexing improvements.
- Added imakeidx, index, repeatindex, splitidx.
- Added attachfile, attachfile2, intopdf, pdfpages, pdfx.
- Added cases.
- Tested to work as-is: notes2bib, hvindex.

v0.57: algorithm2e, float styles, tabular packages, internal improvements.

MathJax

- Added support for MathJax equations with `\footnote`, `\footnotemark`.

math macros

- Added `\StartDefiningMath` and `\StopDefiningMath` for use when defining macros in the preamble which contain $. See section 8.7.7.

dynamic math

- Added `\inlinemathother` and `\inlinemathnormal` to delimit math expressions which depend on a variable condition such as a counter. Such expressions will not be hashed for reuse, and will be converted to SVG math images even when MathJax is enabled. See section 8.7.8.

⚠ new name

- Renamed `\EndDefiningTabulars` to `\StopDefiningTabulars`.

lateximage alt tags

- Improved localization for lateximage HTML alt tags. For SVG math images, the alt tag under some conditions will be set to \MathImageAltText, which defaults to math image. For packages, the alt tag is set using the package name followed by \PackageDiagramAltText, which defaults to diagram. Ex:

  ```
  (-xy- diagram)
  ```

  See section 7.6.

- Fix: Improved print/HTML macro selection.

misc. fixes

- Fix: \href text catcodes.
- Fix: \subref text.
- Fixes: Colored \rule and \boxframe.

packages

- float, rotfloat: Adds support for float styles ruled and boxed.
- float: Fix: Do not create \l@<type> until \listof is used.
- marginnote: Fix: Long optional argument.
- ellipsis: Adds \midwordellipsis.
- breakurl: Fix for text catcodes.
- Added algorithm2e, register, ltablex, xltabular, xellipsis, trimclip, errata, vowel, xpiano.
- Prevents glossary.
- Tested to work as-is with gauss, phonrule, piano, SIunits, tikzcodeblocks.

v0.56: Shell escape, tabular packages.

lwarpmk

- Added

  ```
  lwarpmk pdftosvg <list-of-PDF-files>
  ```

  to quickly convert a document's PDF images to SVG, for use with HTML. See section 8.8.

- Added support for --shell-escape. See section 7.3.

tabular

- Added support for array w and W columns.
- Fix: \multicolumn parameter handling.
- Added support for double \hlines, \midrules, and vertical rules.
- Added support for arydshln dashed lines with HTML tabular, but reverts to plain rules for lateximage and SVG math array.

misc. fixes

- Fix: \thinspace.
- Fix: paralist compact environments.

packages

- Added parnotes, quoting, lua-check-hyphen, tocenter, underscore.
- Added bibunits.
- Tested to work as-is with babelbib, bodegraph, fast-diagram, nicematrix, structmech.

v0.55: Various fixes.

misc fixes

- Fix: Extraneous space in file links, which also prevented *Calibre* EPUB conversions.
- Fix: Float optional argument regression.
- Fix: `\ForceHTMLTOC` with `\phantomsection`.
- Fix: Overfull boxes in `lateximages`.
- Fix: QED symbols in `lateximage`.

packages

- koma-script: Fix: Figure with `\centering`, etc.
- Added clrdblpg.

v0.54: Float `\centering`, improved image checks.

⚠ Reset the configuration

- Due to changes in *lwarpmk*, recompile any existing project a single time using **`pdflatex filename.tex`** or similar, after which *lwarpmk* may then be used with the new configuration files.

lwarpmk

- `lwarpmk limages` checks for the presence of the HTML version of the document and valid image references before attempting to create the `lateximages`.
- *lwarpmk*: Improved error message if configuration file does not exist.

BibTeX

- Added documentation for avoiding error with BibTeX and `\etalchar`. See section 8.6.9.

polyglossia

- Added documentation regarding polyglossia. See section 8.15.4.

macros in section names

- Added documentation regarding the use of macros in section names. See section 8.1.

document encoding

⚠ New and revised encoding options

- Renamed and added package options:

Old Package Option	New Package Option
`xdyFilename`	`xindyStyle`
`IndexLanguage`	`xindyLanguage`
–	`xindyCodepage`
–	`pdftotextEnc`

Use these options along with inputenc or inputenx to process documents in an encoding other than UTF-8. See section 7.4.

floats with `\centering`, etc.

- Floats now honor `\centering`, `\raggedright`, `\raggedleft`, and their ragged2e equivalents, when placed directly after:

```
\begin{floattype}
\centering
```

misc. fixes

- tikz: `\pgfpicture`, fit, align, font.
- ragged2e: `\centering` etc.
- hyperref: `\hypertarget` was creating duplicate of `\label`.
- hyperref: Active chars inside `\hyperref`, `\hyperlink`.
- hyperref: `\ref` inside `\hyperlink` caused a nested HTML link.
- glossaries: Fix when not using babel or polyglossia.
- textcomp: `\textperthousand`.

- LaTeX core `verse` environment: line spacing.

⚠
- Removed `\citetitle`, adjusted `\attribution`.

packages
- memoir: Minor update for v3.7g.
- Added inputenx, bibunits, chngpage, forest, magaz, gridset.
- Prevents loading ae, aecc, t1enc, and wasysym.

v0.53: Improved image checks.

lwarpmk
- *lwarpmk*: Added a warning about corrupted images due to the need to recompile the document one more time.
- *lwarpmk*: Added the **`lwarpmk cleanlimages`** command.
- Added documentation for **`lwarpmk cleanlimages`** and **`lwarpmk pdftohtml`**.

v0.52: Improved footnotes, SVG math.

documentation
- Improved install instructions regarding `lwarp_baseline_marker.png`.
- Added documentation regarding footnotes in section headings, and footnotes with `\VerbatimFootnotes` from fancybox, fancyvrb. See section 8.5.4.
- Added documentation regarding font selection when using XeLaTeX or LuaLaTeX with fontspec and traditional font packages. See section 7.4.

SVG math
- Fix: Limit the number of background tasks when generating `lateximages`.
- Added user-adjustable SVG math font scaling. See section 84.3.
- Added warnings if `lwarp_baseline_marker.png` is not present, or if graphicx or graphics is not loaded.
- Improved `\ensuremath` hashing expansion.
- Fix: `equation*` with `split`.
- `tabbing` now works inside a `lateximage`. Use for math in `tabbing`.

MathJax
- Fix: MathJax script was not executing in some conditions.
- Added `\CustomizeMathJax` to add custom functions. See section 8.7.

footnotes
- Fix: Footnote numbering when using `HTMLDebugComments`.
- Fix: Footnote paragraph tags.
- Fix: `FootnoteDepth` defaults to `\subsubsection`.

misc. fixes
- Fix: `\kill` in a `lateximage`.
- Fix: `\FileDepth`, misc. others, when input encoding is not `utf8`.
- Fix: `\texorpdfstring` in a section name.

packages
- hyperref emulation: Fix for #, %, &, ~, _ characters in URLs.
- fancybox, fancyvrb: Initial support for `\VerbatimFootnotes`.
- nicefrac: Added with fix for `\ensuremath`.
- graphicx: Fix for option defaults. Added v1.1a/b options.
- endfloat: Updated for v2.6.
- url: Fixes for active characters.

2 Introduction

The lwarp project aims to allow a rich LaTeX document to be converted to a reasonable HTML5 interpretation, with only minor intervention on the user's part. No attempt has been made to force LaTeX to provide for every HTML-related possibility, and HTML cannot exactly render every possible LaTeX concept. Where compromise is necessary, it is desirable to allow the print output to remain typographically rich, and compromise only in the HTML conversion.

Several "modern" features of HTML5, CSS3, and SVG are employed to allow a fairly feature-rich document without relying on the use of JavaScript. Limited testing on older browsers shows that these new features degrade gracefully.

---

lwarp is a native LaTeX package, and operates by either patching or emulating various functions. Source-level compatibility is a major goal, but occasional user intervention is required in certain cases.

As a package running directly in LaTeX, lwarp has some advantages over other methods of HTML conversion. TeX itself is still used, allowing a wider range of TeX trickery to be understood. Lua expressions are still available with LuaTeX. Entire categories of LaTeX packages work as-is when used with lwarp: definitions, file handling, utilities, internal data structures and calculations, specialized math-mode typesetting for various fields of science and engineering, and anything generating plain-text output. Blocks of PDF output may be automatically converted to SVG images while using the same font and spacing as the original print document, directly supporting Ti*k*z and `picture`. Numerous packages are easily adapted for HTML versions, either by loading and patching the originals, or by creating nullified or emulated replacements, and all without resorting to external programming. As a result, several hundred packages have already been adapted (table 2), and an uncounted number more work as-is.

Packages have been selected according to several criteria: perceived importance, popularity lists, recent CTAN updates, CTAN topics, mention in other packages, support by other HTML conversion methods, and from sample documents taken from public archives. These include some "obsolete" packages as well.[1]

Assistance is also provided for modifying the HTML output to suit the creation of EPUB documents, and for modifying the HTML output to ease import into a word processor.

---

pdflatex, *xelatex*, or *lualatex* may be used, allowing lwarp to process the usual image formats. While generating HTML output, SVG files are used in place of PDF. Other formats such as PNG and JPG are used as-is.

[1] An amazing number of decades-old packages are still in use today.

SVG images may be used for math, and are also used for `picture`, Ti*k*z, and similar environments. The SVG format has better browser and e-book support than MathML (as of this writing), while still allowing for high-quality display and printing of images (again, subject to potentially bug-ridden[2] browser support).

Furthermore, SVG images allow math to be presented with the same precise formatting as in the print version. Math is accompanied by `<alt>` tags holding the LaTeX source for the expression, allowing it to be copy/pasted into other documents.[3] Custom LaTeX macros may be used as-is in math expressions, since the math is evaluated entirely inside LaTeX. An MD5 hash is used to combine multiple instances of the same inline math expression into a single image file, which then needs to be converted to SVG only a single time.

The MathJax JavaScript display engine may be selected for math display instead of using SVG images. Subject to browser support and Internet access, MathJax allows an HTML page to display math without relying on a large number of external image files.[4] lwarp maintains LaTeX control for cross-referencing and equation numbering, and attempts to force MathJax to tag equations accordingly.

A *texlua* program called *lwarpmk* is used to process either the print or HTML version of the document. A few external utility programs are used to finish the conversion from a LaTeX-generated PDF file which happens to have HTML5 tags, to a number of HTML5 plain-text files and accompanying images.

lwarp automatically generates the extra files necessary for the HTML conversion, such as CSS and `.xdy` files, and configuration files for the utility *lwarpmk*. Also included is a parallel version of the user's source document, `<sourcename>-html.tex`, which selects HTML output and then inputs the user's own source. This process allows both the printed and HTML versions to co-exist side-by-side, each with their own auxiliary files.

When requesting packages during HTML conversion, lwarp first looks to see if it has its own modified version to use instead of the standard LaTeX version. These `lwarp-packagename.sty` files contain code used to emulate or replace functions for HTML output.

[2] Firefox has had an on-again/off-again bug for quite some time regareding printing SVGs at high resolution.

[3] There seems to be some debate as to whether MathML is actually an improvement over LaTeX for sharing math. The author has no particular opinion on the matter, except to say that in this case LaTeX is much easier to implement!

[4] One SVG image file per math expression, except that duplicate inline math expressions are combined into a single file according to the MD5 hash function of its contents. A common scientific paper can easily include several thousand files, and in one case the MD5 hash cut the number of files in half and the rendering time by 30%.

2.1 Typesetting conventions

Font weight, family, and style are used to indicate various objects:

Table 1: Typesetting conventions

package	LaTeX package.
program	Program's executable name.
`option`	Program or package option.
`filename`	File name in the operating system.
Brand Name	Proper name for a program, operating system, etc.
commands	Commands to be entered by the user.
`code`	Program code.
`\macroname`	LaTeX macro.
`environment`	LaTeX environment.
`counter`	LaTeX counter.
`boolean`	LaTeX boolean.
`<element>`	HTML element.
`attribute`	HTML attribute.
User Interface	A user-interface item.
acro	Acronym.

2.2 Supported packages and features

Table 2 lists some of the various LaTeX features and packages which may be used.

Package names are colored according to their support level:

name: Supported as-is.

name: Modifed to work with HTML output, and perhaps also as print output in SVG math or `latexmage` environments.

name: Emulated for HTML output.

name: Ignored for HTML output, but provides source-level compatibility.

MJ: Supported as-is for MathJax, subject to limitations.

MJ: Emulated for MathJax using custom macros, subject to limitations.

MJ: Ignored by MathJax, but may be used in the document source. May be converted to SVG images.

Table 2: LaTeX lwarp package — Supported features

Category	Status and supported features.
Engines:	DVI LaTeX, pdfLaTeX, XeLaTeX, LuaLaTeX, upLaTeX
Compiling:	*latexmk*, *perltex*, *pythontex*, *make*, etc.
Classes:	article, book, report, scrartcl, scrbook, scrreprt, memoir, CJK-related as listed below.
Koma-script:	scrextend, scrhack, scrlayer. Others as listed below.
Memoir:	memhfixc
Languages:	babel, cjkpunct, impnattypo, luavlna, polyglossia, xeCJK, xevlna.
Chinese:	CTeX, ctex, upzhkinsoku, xpinyin, zhlineskip, zhspacing.
Japanese:	upLaTeX, LuaTeX-ja, gentombow, lltjext, plarray, plarydshln, plautopatch, plext, plextarray, plextarydshln, plextcolortbl, plextdelarray, pxatbegshi, pxeveryshi, pxftnright, pxgentombow, pxjahyper, pxpdfpages, pxpgfrcs, pxpgfmark, tascmac, zxjatype. bxjsarticle and related, ltjsarticle and related, luatexja, luatexja-fontspec, ujarticle and related, utarticle and related.
Korean:	kotex, luatexko, xetexko.

lwarp Supported Functions — continued

Category	Status
Page layout:	2in1, 2up, a4, a4wide, a5comb, addlines, anysize, atbegshi, balance, blowup, booklet, bophook, bounddvi, bxpapersize, canoniclayout, centerlastline, changelayout, changepage, chngpage, clrdblpg, continue, draftcopy, draftfigure, draftwatermark, ebook, everyshi, fancyhdr, fancytabs, flippdf, fullminipage, fullpage, fwlw, geometry, gmeometric, grid, grid-system, gridset, layaureo, layout, layouts, leading, lscape, ltxgrid, nccfancyhdr, notespages, nowidow, pagegrid, pagesel, parallel, parcolumns, pbalance, pdfcolparallel, pdfcolparcolumns, pdfcrypt, pdflscape, pdfprivacy, preview, ragged2e, returntogrid, rmpage, scrlayer-scrpage, scrpage2, setspace, selectp, textarea, threadcol, thumb, thumbs, titleps, tocenter, turnthepage, twoup, typearea, underlin, vmargin, watermark, widows-and-orphans, zwpagelayout.
Sectioning:	Adds `FileDepth` for splitting the HTML output. Files may be numbered sequentially or named according to section name. Common short words and punctuation are removed from the filenames. anonchap, bsheaders, decorule, fncychap, froufrou, hypbmsec, indentfirst, quotchap, section, sectionbreak, secdot, sectsty, titlesec, tocvsec2.
Table of contents, figures, tables:	Supported, with hyperlinks. etoc, minitoc, multitoc, shorttoc, tableof, titletoc, tocbasic, tocbibind, tocdata, tocloft, tocstyle, tocvsec2.
Title page:	`\maketitle`, `titlepage`, authblk, authoraftertitle, titling.
Front & back matter:	abstract, appendix.
Indexing:	*makeindex*, *xindy*, and *xindex* are supported, with hyperlinks. gindex, hvindex, idxlayout, imakeidx, index, makeidx, repeatindex, splitidx, varindex, xindex.
Glossary:	gloss, glossaries and *xindy*, nomencl.
Bibliography:	babelbib, bibtopic, backref, biblatex, bibunits, chapterbib, cite, citeref, collref, drftcite, hypernat, jurabib, mcite, mciteplus, multibib, natbib, notes2bib, splitbib, showtags.

lwarp Supported Functions — continued

Category	Status
Cross-references:	bookmark, breakurl, cleveref, fancyref, hypdestopt, hyperref, perpage, prettyref, titleref, url, varioref, xcite, xr, xr-hyper, xurl, zref.
Margin notes:	marginal, marginfit, marginfix, scrlayer-notecolumn, versonotes.
Footnotes:	Adds `FootnoteDepth` to print footnotes at section breaks. MathJax emulation for `\footnote`, and also as marked in the following: bigfoot, dblfnote, endheads, endnotes[MJ], enotez[MJ], fixfoot, fnbreak, fnpara, fnpct, fnpos, footmisc, footnote, footnotebackref, footnoterange, footnpag, manyfoot, marginnote[MJ], nccfoots[MJ], pagenote[MJ], parnotes[MJ], pdfcolfoot, pfnote, sepfootnotes, sidenotes[MJ], tablefootnote.
Math:	Converted to SVG images with HTML `<alt>` tags containing the LaTeX source for the math expression. MathJax supported as an alternative. amsmath[MJ]: $\mathcal{AMS}$ environments are supported. User-defined macros are available during converson, due to native LaTeX processing.
Theorems:	Native LaTeX theorems, amsthm, apxproof, ntheorem, shadethm, theorem, thmbox, thmtools.
Additional math:	Math fonts via SVG images, accents[MJ], amscd[MJ], amscdx, autobreak[MJ], autonum, backnaur[MJ], bm[MJ], braket[MJ], breqn[MJ], bussproofs[MJ], cases[MJ], centernot[MJ], cmbright[MJ], colonequals[MJ], decimal[MJ], delarray, DotArrow[MJ], dotlessi[MJ], dotlessj[MJ], esvect[MJ], extarrows[MJ], fixmath[MJ], fouridx[MJ], fourier[MJ], guass, hhtensor[MJ], icomma[MJ], isomath[MJ], jkmath, kpfonts[MJ], kpfonts-otf[MJ], leftidx[MJ], libertinust1math[MJ], mathalpha[MJ], mathastext[MJ], mathcomp[MJ], mathdesign[MJ], mathdots[MJ], mathfixs[MJ], mathpazo[MJ], mathptmx[MJ], mathpunctspace[MJ], mathspec[MJ], mathtools[MJ], mattens[MJ], maybemath[MJ], mdwmath[MJ], mismath[MJ], mleftright[MJ], multiobjective[MJ], nccmath[MJ], nicematrix[MJ], noitcrul[MJ], newpxmath[MJ], newtxmath[MJ], newtxsf[MJ], pb-diagram, pxfonts[MJ], resizegather[MJ], rmathbr[MJ], scalerel[MJ], shuffle[MJ], skmath[MJ], stackrel[MJ], statex2[MJ], statistics, statmath[MJ], subsupscripts[MJ], tensind, tensor[MJ], textualicomma[MJ], txfonts[MJ], txgreeks[MJ], unicode-math[MJ], upgreek[MJ], ushort[MJ], witharrows[MJ], xfakebold[MJ], xy. Many others work as-is.

lwarp Supported Functions — continued

Category	Status
Display math with `\displaymathother`:	Complicated math objects in display math, such as tikz-cd, etc.
Units and fractions:	nicefrac[MJ], SIunits[MJ], siunitx[MJ], units[MJ], unitsdef, xfrac[MJ].
Floats:	Appear where declared. capt-of, caption, cutwin, dblfloatfix, endfloat, fewerfloatpages, fix2col, flafter, float, floatflt, floatrow, fltrace, ftcap, hypcap, keyfloat, morefloats, multicap, newfloat, nonfloat, picinpar, placeins, rotfloat, stfloats, subcaption, subfig, subfigure, subfloat, swfigure, topcapt, trivfloat, wrapfig.
Tabular:	`tabular` environment, array[MJ], arydshln[MJ], bigdelim[MJ], bigstrut[MJ], booktabs[MJ], colortbl[MJ], ctable, diagbox, hhline[MJ], longtable, ltablex, ltxtable, multirow[MJ], supertabular, tabularx, tabulary, threeparttable, threeparttablex, widetable, xltabular, xtab.
Graphics:	graphics and graphicx. `\includegraphics` supports `width`, `height`, `origin`, `angle`, and `scale` tags, and adds `class`. References to PDF files are changed to SVG, other image types are accepted as well. `\rotatebox` and `\scalebox` are supported as well as HTML can handle. rotating is emulated but all objects are unrotated in HTML. `picture`, tikz, and xy are converted to an SVG image. asymptote, curves, datatool, eepic, epsf, epsfig, epstopdf, figsize, fitbox, grffile, lpic, luamplib, media9, movie15, multimedia, overpic, pict2e, pinlabel, psfrag, psfragx, pst-eps, pstool, pstricks, rlepsf, rviewport, svg, svg-extract, tikz, tikz-3dplot, tikz-imagelabels, xy
xcolor:	Full package color names, any color models, and mixing. `\textcolor`, `\colorbox`, `\fcolorbox`. Enhanced for HTML compatibility.
Lists:	Standard LaTeX environments, enumerate, enumitem, eqlist, hang, listliketab, paralist.
Environments:	Standard LaTeX environments.
Paragraphs, `minipage`, `\parbox`:	Some HTML5-imposed limitations. Nested minipages are supported. eqparbox, fancypar, minibox, pbox, shapepar.

lwarp Supported Functions — continued

Category	Status
Quotations:	copyrightbox, csquotes, epigraph, quoting, verse.
Verbatim:	fancyvrb, fvextra, moreverb, shortvrb, verbatim.
Frames:	boxedminipage, boxedminipage2e, fancybox, fbox[MJ], framed, mdframed, niceframe, shadow, tcolorbox[MJ], vertbars.
Multi-columns:	adjmulticol, multicol, multicolrule, vwcol.
Margins:	fullwidth, hanging, midpage.
Line numbering:	fnlineno, lineno.
Direct formatting:	`\emph`, `\textsuperscript`, `\textbf`, etc are supported. `\bfseries`, etc. are only supported in some cases. cancel[MJ], ellipsis, embrac, enparen, hyphenat, lettrine, lips, lua-check-hyphen, luacolor, magaz, moresize, nolbreaks, normalcolor, pdfcol, pdfcolmk, pdfrender, realscripts, relsize[MJ], scalefnt, seqsplit[MJ], soul, soulpos, soulutf8, stackengine, textfit, thinsp, trimclip, truncate, ulem, umoline, underscore, uspace, xellipsis.
Acronyms:	acro, acronym.
Ordinals:	engord, fmtcount, nth.
Text ligatures:	Ligatures for symbols are supported. Ligatures for f, q, t are intentionally turned off because many simpler browsers do not display them correctly. Modern full-featured browsers re-create these ligatures on-the-fly.
Horizontal space:	HTML output for thin-unbreakable, unbreakable, `\enskip`, `\quad`, `\qquad`, `\hspace`.
Rules:	`\rule` with width, height, raise, text color.
HTML reserved characters:	`\&`, `\textless`, and `\textgreater` are converted to HTML entities.
Fonts:	Used as-is. Appear in SVG math expressions or embedded image environments. fontaxes, nfssext-cfr, slantsc, tabfigures. Tested to work as-is: Special font macros in cfr-lm and others which use nfssext-cfr. Also see the math section for math and MathJax support for math font packages.

lwarp Supported Functions — continued

Category	Status
Symbols:	Native LaTeX diacriticals, academicons, amssymb[MJ], bbding, ccicons, chemgreek, dingbat, euro, eurosym, fontawesome, fontawesome5, gensymb[MJ], latexsym[MJ], marvosym, metalogo, metalogox, pifont, textalpha, textcomp, textgreek, typicons, xunicode.
Files:	attachfile, attachfile2, hyperxmp, inputtrc, intopdf, pdfpages, pdfx, xmpincl.
Science and engineering:	algorithm2e, algorithmicx, ar[MJ], askmaps, axodraw2, bitpattern, blochsphere, bodegraph, bohr, bytefield, chemfig, chemformula, chemgreek, chemmacros, chemnum, circuitikz, econometrics[MJ], elements, engtlc[MJ], fast-diagram, ghsystem, hepnicenames, heppennames, hepunits[MJ], isotope[MJ], karnaughmap, karnaugh-map, keystroke, listings, listingsutf8, linop, menukeys, mhchem[MJ], minted, pgfgantt, phfqit, physics[MJ], physunits[MJ], plimsoll[MJ], qcircuit, register, simplebnf, simpler-wick, slashed[MJ], steinmetz[MJ], structmech, struktex, syntaxdi, tikz-karnaugh, tikzcodeblocks, venndiagram
Arts and humanities:	foreign, forest, lyluatex, musicography, nameauth, octave, phonrule, piano, schemata, semantic-markup, tikz-dependency, vowel, xpiano
Academic:	academicons, classicthesis, doi, doipubmed, orcidlink[MJ], termcal
Admonitions:	awesomebox, notes.
Editorial:	changebar, changelog, changes, easy-todo, easyReview, ed, errata, fixme, fixmetodonotes, pdfcomment[MJ], pdfmarginpar, todo, todonotes, tram, xechangebar.
Accessibility:	accessibility[MJ], accsupp[MJ], axessibility[MJ], pdfcomment[MJ], repltext[MJ], tagpdf.
Package handling:	catoptions.
Debug:	chkfloat, cmdtrack, dprogress, lua-visual-debug, refcheck, srcltx, srctex, vpe, xbmks.

lwarp Supported Functions — continued

Category	Status
Working as-is:	Various utility, calculation, file, and text-only packages, such as calc, fileerr, somedefs, trace, xspace. Also, most math-only packages, including specialized typesetting for various fields of science and engineering.

3 Alternatives

Summarized below are several other ways to convert a LaTeX or other document to HTML. Where an existing LaTeX document is to be converted to HTML, lwarp may be a good choice. For new projects with a large number of documents, it may be worth investigating the alternatives before decided which path to take.

3.1 internet class

Cls internet The closest to lwarp in design principle is the `internet` class by Andrew Stacey — an interesting project which directly produces several versions of markdown, and also HTML and EPUB. https://github.com/loopspace/latex-to-internet

3.2 TeX4ht

Prog TeX4ht http://tug.org/tex4ht/

Prog htlatex

This system uses native LaTeX processing to produce a DVI file containing special commands, and then uses additional post-processing for the HTML conversion by way of numerous configuration files. In some cases lwarp provides a better HTML conversion, and it supports a different set of packages. TeX4ht produces several other forms of output beyond HTML, including ODT and a direct path to EPUB, and is still being developed.

3.3 Translators

These systems use external programs to translate a subset of LaTeX syntax into HTML. Search for each on CTAN (http:\ctan.org).

Prog Hevea **HeVeA:** http://hevea.inria.fr/ (not on CTAN)

Prog TtH **TtH:** http://hutchinson.belmont.ma.us/tth/

Prog GELLMU **GELLMU:** http://www.albany.edu/~hammond/gellmu/

Prog LaTeXML **LaTeXML:** http://dlmf.nist.gov/LaTeXML/

Prog Plastex **PlasTeX:** https://github.com/tiarno/plastex

Prog LaTeX2HTML **LaTeX2HTML:** http://www.latex2html.org/
and http://ctan.org/pkg/latex2html.

Prog TeX2page **TeX2page:** http://ds26gte.github.io/tex2page/index.html

Finally, GladTeX may used to directly insert LaTeX math into HTML:

Prog GladTeX **GladTeX:** http://humenda.github.io/GladTeX/

3.4 AsciiDoc and Asciidoctor

AsciiDoc is one of the most capable markup languages, providing enough features to produce the typical technical-writing document with cross-references, and it writes LaTeX and HTML.

Prog AsciiDoc **Asciidoctor:** http://asciidoctor.org/ (More active.)

Prog AsciiDoctor **AsciiDoc:** http://asciidoc.org/ (The original project.)

3.4.1 Asciidoctor-LaTeX

The Asciidoctor-LaTeX project is developing additional LaTeX-related features.

Asciidoctor-LateX:
http://www.noteshare.io/book/asciidoctor-latex-manual
Prog Asciidoctor-LaTeX https://github.com/asciidoctor/asciidoctor-latex

3.5 Pandoc

Prog Pandoc A markup system which also reads and writes LaTeX and HTML.

Pandoc: http://pandoc.org/

(Watch for improvements in cross-references to figures and tables.)

3.6 Word processors

Prog Word
Prog LibreOffice
Prog OpenOffice

It should be noted that the popular word processors have advanced through the years in their abilities to represent math with a LaTeX-ish input syntax, unicode math fonts, and high-quality output, and also generate HTML with varying success. See recent developments in Microsoft ® *Word* ® and LibreOffice ™ *Writer*.

3.7 Commercial systems

Prog Adobe
Prog FrameMaker
Prog InDesign
Prog Flare
Prog Madcap

Likewise, several professional systems exist whose abilities have been advancing in the areas of typesetting, cross-referencing, and HTML generation. See Adobe ® *FrameMaker* ®, Adobe *InDesign* ®, and Madcap *Flare* ™.

3.8 Comparisons

AsciiDoc, Pandoc, and various other markup languages typically have a syntax which tries to be natural and human-readable, but the use of advanced features tends to require many combinations of special characters, resulting in a complicated mess of syntax. By

contrast, LaTeX spells things out in readable words but takes longer to type, although integrated editors exist which can provide faster entry and a graphic user interface. For those functions which are covered by the typical markup language it is arguable that LaTeX is comparably easy to learn, while LaTeX provides many more advanced features where needed, along with a large number of pre-existing packages which provide solutions to numerous common tasks.

Text-based document-markup systems share some of the advantages of LaTeX vs. a typical word processor. Documents formats are stable. The documents themselves are portable, work well with revision control, do not crash or become corrupted, and are easily generated under program control. Formatting commands are visible, cross-referencing is automatic, and editing is responsive. Search/replace with regular expressions provides a powerful tool for the manipulation of both document contents and structure. Markup systems and some commercial systems allow printed output through a LaTeX back end, yielding high-quality results especially when the LaTeX template is adjusted, but they lose the ability to use LaTeX macros and other LaTeX source-document features.

The effort required to customize the output of each markup system varies. For print output, LaTeX configuration files are usually used. For HTML output, a CSS file will be available, but additional configuration may require editing some form of control file with a different syntax, such as XML. In the case of lwarp, CSS is used, and much HTML output is adjusted through the usual LaTeX optional macro parameters, but further customization may require patching LaTeX code.

The popular word processors and professional document systems each has a large base of after-market support including pre-designed styles and templates, and often include content-management systems for topic reuse.

4 Installation

Table 3 shows the tools which are used for the LaTeX to HTML conversion. In most cases, these will be available via the standard package-installation tools.

Detailed installation instructions follow.

Table 3: Required software programs

Provided by your LaTeX distribution:

From TeXLive: http://tug.org/texlive/.

LaTeX: *pdflatex*, *xelatex*, or *lualatex*.

The lwarp package: This package.

The *lwarpmk* utility: Provided along with this package. This should be an operating-system executable in the same way that *pdflatex* or *latexmk* is. It is possible to have the lwarp package generate a local copy of *lwarpmk* called `lwarpmk.lua`. See table 4.

***luatex*:** Used by the *lwarpmk* program to simplify and automate document generation.

***xindy*:** The *xindy* program is used by lwarp to create indexes. On a MiKTeX system this may have to be acquired separately, but it is part of the regular installer as of mid 2015.

***latexmk*:** Optionally used by *lwarpmk* to compile LaTeX code. On a MiKTeX system, *Perl* may need to be installed first.

***pdfcrop*:** Used to pull images out of the LaTeX PDF.

Poppler PDF utilities:

***pdftotext*:** Used to convert PDF to text.

***pdfseparate*:** Used to pull images out of the LaTeX PDF.

***pdftocairo*:** Used to convert images to SVG.

These might be provided by your operating-system package manager, and MiKTeX provides miktex-poppler-bin-* packages.

From Poppler: poppler.freedesktop.org.

For MacOS®, see https://brew.sh/, install *Homebrew*, then

Enter ⇒ **`brew install poppler`**

For Windows, see MikTeX miktex-poppler-bin-*, or:
https://sourceforge.net/projects/poppler-win32/ and:
http://blog.alivate.com.au/poppler-windows/

***Perl*:**

This may be provided by your operating-system package manager, and may be required for some of the Poppler PDF utilities.

strawberryperl.com (recommended), perl.org

Automatically downloaded from the internet as required:

MathJax: Optionally used to display math. From: mathjax.org

4.1 Installing the lwarp package

There are several ways to install lwarp. These are listed here with the preferred methods listed first:

Pre-installed: Try entering into a command line:

Enter ⇒ **`kpsewhich lwarp.sty`**

If a path to `lwarp.sty` is shown, then lwarp is already installed and you may skip to the next section.

TEX Live: If using a TEX Live distribution, try installing via *tlmgr*:

Enter ⇒ **`tlmgr install lwarp`**

MiKTEX:

1. For newer versions of MiKTEX, install or update lwarp using the *MiKTeX Console* program.
2. For older versions of MiKTEX, to install lwarp the first time, use the *MiKTeX Package Manager (Admin)*. To update lwarp, use *MiKTeX Update (Admin)*.
3. Either way, also update the package miktex-misc, which will install and update the *lwarpmk* executable.

Operating-system package: The operating-system package manager may already have lwarp, perhaps as part of a set of TEX-related packages.

CTAN TDS archive: lwarp may be downloaded from the Comprehensive TEX Archive:

1. See http://ctan.org/pkg/lwarp for the lwarp package.
2. Download the TDS archive: `lwarp.tds.zip`
3. Find the TEX `local` directory:

   TEX Live:

   Enter ⇒ **`kpsewhich -var-value TEXMFLOCAL`**

   MiKTEX:

   In the **Settings** window, **Roots** tab, look for a local TDS root.

   This should be something like:

   ```
   /usr/local/texlive/texmf-local/
   ```

4. Unpack the archive in the TDS local directory.
5. Renew the cache:

   Enter ⇒ **`mktexlsr`**

   — or —

   Enter ⇒ **`texhash`**

   Or, for WINDOWS MiKTEX, start the program called *MiKTeX Settings (Admin)* and click on the button called **Refresh FNDB**.

CTAN `.dtx` and `.ins` files: Another form of TEX package is `.dtx` and `.ins` source files. These files are used to create the documentation and `.sty` files.

1. See http://ctan.org/pkg/lwarp for the lwarp package.
2. Download the zip archive `lwarp.zip` into your own `lwarp` directory.
3. Unpack `lwarp.zip`.
4. Locate the contents `lwarp.dtx` and `lwarp.ins`
5. Create the `.sty` files:

   Enter ⇒ **`pdflatex lwarp.ins`**
6. Create the documentation:

```
pdflatex lwarp.dtx  (several times)
makeindex -s gglo.ist -o lwarp.gls lwarp.glo
makeindex -s gind.ist lwarp.idx
pdflatex lwarp.dtx  (several times)
```

7. Copy the `.sty` files somewhere such as the TEX Live local tree found in the previous CTAN TDS section, under the subdirectory:

   `<texlocal>/tex/latex/local/lwarp`
8. Copy `lwarp_baseline_marker.png` and `lwarp_baseline_marker.eps` to the same place as the `.sty` files.
9. Copy the documentation `lwarp.pdf` to a `source` directory in the local tree, such as:

   `<texlocal>/doc/local/lwarp`
10. Renew the cache:

    Enter ⇒ **`mktexlsr`**

    — or —

    Enter ⇒ **`texhash`**

    Or, for WINDOWS MiKTEX, start the program called *MiKTeX Settings (Admin)* and click on the button called **Refresh FNDB**.
11. See section 4.2.1 to generate your local copy of *lwarpmk*.
12. Once the local version of `lwarpmk.lua` is installed, it may be made available system-wide as per section 4.2.

Project-local CTAN `.dtx` and `.ins` files: The `.dtx` and `.ins` files may be downloaded to a project directory, then compiled right there, alongside the document source files. The resultant `*.sty` and `lwarpmk.lua` files may be used as-is, so long as they are in the same directory as the document source. The files `lwarp_baseline_marker.png` and `lwarp_baseline_marker.eps` must also be copied as well. This approach is especially useful if you would like to temporarily test lwarp before deciding whether to permanently install it.

Just testing!

4.2 Installing the *lwarpmk* utility

(Note: If *lwarpmk* is not already installed, it is easiest to use a local copy instead of installing it system-wide. See section 4.2.1.)

After the lwarp package is installed, you may need to setup the *lwarpmk* utility:

1. At a command line, try executing **`lwarpmk`**. If the *lwarpmk* help message appears, then *lwarpmk* is already set up. If not, it is easiest to generate and use a local copy. See section 4.2.1.

2. For MiKTEX, try updating the miktex-misc package. This may install the *lwarpmk* executable for you.

   Otherwise, continue with the following:

3. Locate the file `lwarpmk.lua`, which should be in the `scripts` directory of the TDS tree. On a TEX Live or MiKTEX system you may use

   Enter ⇒ **`kpsewhich lwarpmk.lua`**

   (If the file is not found, you may also generate a local copy and use it instead. See section 4.2.1.)

4. Create *lwarpmk*:

   Unix: Create a symbolic link and make it executable:

   (a) Locate the TEX Live binaries:

   Enter ⇒ **`kpsewhich -var-value TEXMFROOT`**

   This will be something like:

   `/usr/local/texlive/<year>`

   The binaries are then located in the `bin/<arch>` directory under the root:

   `/usr/local/texlive/<year>/bin/<architecture>/`

   In this directory you will find programs such as *pdflatex* and *makeindex*.

   (b) In the binaries directory, create a new symbolic link from the binaries directory to `lwarpmk.lua`:

   Enter ⇒ **`ln -s <pathtolwarpmk.lua> lwarpmk`**

   (c) Make the link executable:

   Enter ⇒ **`chmod 0755 lwarpmk`**

   Windows TEX Live: Create a new `lwarpmk.exe` file:

   (a) Locate the TEX Live binaries as shown above for Unix.

   (b) In the binaries directory, make a *copy* of `runscript.exe` and call it `lwarpmk.exe` This will call the copy of `lwarpmk.lua` which is in the `scripts` directory of the distribution.

   Windows MiKTEX: Create a new `lwarpmk.bat` file:

   (a) Locate the MiKTEX binaries. These will be in a directory such as:

   `C:\Program Files\MiKTeX 2.9\miktex\bin\x64`

   In this directory you will find programs such as `pdflatex.exe` and `makeindex.exe`.

   (b) Create a new file named `lwarpmk.bat` containing:

   ```
   texlua "C:\Program Files\MiKTeX 2.9\scripts\lwarp\lwarp.texlua" %*
   ```

   This will call the copy of `lwarpmk.lua` which is in the `scripts` directory of the distribution.

4.2.1 Using a local copy of *lwarpmk*

It is also possible to use a local version of *lwarpmk*:

1. When compiling the tutorial in section 5, use the `lwarpmk` option for the lwarp package:

   ```
   \usepackage[lwarpmk]{lwarp}
   ```

2. When the tutorial is compiled with *pdflatex*, the file `lwarpmk.lua` will be generated along with the other configuration files.

3. `lwarpmk.lua` may be used for this project:

   Unix:

   (a) Make `lwarpmk.lua` executable:
   Enter ⇒ **`chmod 0755 lwarpmk.lua`**

   (b) Compile documents with
   Enter ⇒ **`./lwarpmk.lua html`**
   Enter ⇒ **`./lwarpmk.lua print`**
   etc.

   (c) It may be useful to rename or link to a version without the `.lua` suffix.

   Windows:

   Compile documents with either of the following, depending on which command shell is being used:
   Enter ⇒ **`texlua lwarpmk.lua html`**
   Enter ⇒ **`texlua lwarpmk.lua print`**
   etc.

   Or:
   Enter ⇒ **`lwarpmk html`**
   Enter ⇒ **`lwarpmk print`**
   etc.

4.3 Installing additional utilities

To test for the existence of the additional utilities:

Enter the following in a command line. If each programs' version is displayed, then that utility is already installed. See table 3 on page 79.

Enter ⇒ **`luatex --version`**
Enter ⇒ **`xindy --version`**
Enter ⇒ **`latexmk --version`**
Enter ⇒ **`perl --version`**
Enter ⇒ **`pdfcrop --version`**
Enter ⇒ **`pdftotext -v`**
Enter ⇒ **`pdfseparate --version`**
Enter ⇒ **`pdftocairo -v`**

To install *xindy*, *latexmk*, and *pdfcrop*:

The TEX utilities *xindy*, *latexmk*, and *pdfcrop* may be installed in *TexLive* with *tlmgr*, installed by *MiKTeX*, provided by your operating system's package manager, or downloaded from the *CTAN* archive:

http://ctan.org/pkg/xindy
http://ctan.org/pkg/latexmk
http://ctan.org/pkg/pdfcrop

Prog [requirement] pdftotext
Prog [requirement] pdfseparate
Prog [requirement] pdftocairo

To install the Poppler utilities to a Unix/Linux system:

The tools from the Poppler project should be provided by your operating system's package manager.

To install the Poppler utilities to a MacOS machine:

1. Install *Homebrew* from https://brew.sh/:

```
/usr/bin/ruby -e "$(curl -fsSL https://raw.githubusercontent.com/Homebrew/install/master/install)"
```
Enter

2. Install the Poppler utilities:

Enter ⇒ `brew install poppler`

To install the Poppler utilities to a Windows machine:

If using MikTeX, install a miktex-poppler-bin-* package. Otherwise:

1. See table 3 on page 79.
2. Download and extract the Poppler utilities *pdftotext*, *pdfseparate*, and *pdfseparate* to a directory, such as `Poppler`.
3. In the **Start** window, type "Path" to search for results related to Path. Or, open the control panel and search for "Path".
4. Choose **Edit the system environment variables** in the control panel.
5. Choose the **Environment Variables** button.
6. Choose the **Path** variable, then the **Edit** button.
7. Choose the **New** button to make an additional entry.
8. Enter the `bin` directory of the Poppler utilities, such as:

   `C:\Users\<myname>\Desktop\Poppler\poppler-0.5_x86\poppler-0.5\bin`

   Be sure to include `\bin`.
9. Click **Ok** when done.

Prog [requirement] perl

To install Perl to a Windows machine:

1. Download and install a version of Perl, such as Strawberry Perl, to a directory without a space in its name, such as `C:\Strawberry`.
2. Edit the **Path** as seen above for the Poppler utilities.
3. Enter the `bin` directory of the *perl* utility, such as:

   `C:\Strawberry\perl\bin`

   Be sure to include `\bin`.
4. Click **Ok** when done.

Any utilities installed by hand must be added to the PATH.

5 Tutorial

This section shows an example of how to create an lwarp document.

Need help?

See the General Index for "how-to", and the Troubleshooting Index if something doesn't work. A Troubleshooting section is also available. The Index of Objects contains automated entries for each package, macro, environment, counter, boolean, and other objects; individually and also sorted by category.

5.1 Starting a new project

1. Create a new project directory called `tutorial`.

File `tutorial.tex`

2. Inside the `tutorial` directory, create a new file called `tutorial.tex`. This may be done several ways:

   Copy from the documentation PDF:

   A listing is in fig. 1, which may be copied/pasted from the figure directly into your own editor, depending on the quality of the PDF viewer and editor, or:

   Copy from the lwarp documentation directory:

File `lwarp_tutorial.txt`

⚠ Note: `.txt` suffix!

   Another copy may be found by entering into a command line:

   Enter ⇒ **`texdoc -l lwarp_tutorial.txt`**

   This should be in the `doc/latex/lwarp/` directory along with this PDF documentation. Copy `lwarp_tutorial.txt` directly into your `tutorial` directory, renamed as `tutorial.tex`.

⚠ Bad formatting!

   When using Windows, use an editor other than Notepad, since Notepad does not accept the end-of-line from a Unix text file.

3. Compile the project:

   Enter ⇒ **`pdflatex tutorial.tex`**

   (several times)

   (*xelatex* or *lualatex* may be used as well. lwarp also supports DVI *latex* for use with `.eps` images.)

4. View the resulting `tutorial.pdf` with a PDF viewer.

A number of new files are created when `tutorial.tex` is compiled, as shown in table 4. These files are created by the `lwarp` package.

(Two of the new files are configuration files for the helper program *lwarpmk*. Whenever a print version of the document is created, the configuration files for *lwarpmk* are updated to record the operating system, LaTeX engine (*latex*, *pdflatex*, *xelatex*, or *lualatex*), the filenames of the source code and HTML output, and whether the additional helper program *latexmk* will be used to compile the document.)

Figure 1: tutorial.tex listing

Note: There are two pages!

```
% Save this as tutorial.tex for the lwarp package tutorial.

\documentclass{book}

\usepackage{iftex}

% --- LOAD FONT SELECTION AND ENCODING BEFORE LOADING LWARP ---

\ifPDFTeX
\usepackage{lmodern}            % pdflatex or dvi latex
\usepackage[T1]{fontenc}
\usepackage[utf8]{inputenc}
\else
\usepackage{fontspec}           % XeLaTeX or LuaLaTeX
\fi

% --- LWARP IS LOADED NEXT ---
\usepackage[
%   HomeHTMLFilename=index,     % Filename of the homepage.
%   HTMLFilename={node-},       % Filename prefix of other pages.
%   IndexLanguage=english,      % Language for xindy index, glossary.
%   latexmk,                    % Use latexmk to compile.
%   OSWindows,                  % Force Windows. (Usually automatic.)
%   mathjax,                    % Use MathJax to display math.
]{lwarp}
% \boolfalse{FileSectionNames}  % If false, numbers the files.

% --- LOAD PDFLATEX MATH FONTS HERE ---

% --- OTHER PACKAGES ARE LOADED AFTER LWARP ---
\usepackage{makeidx} \makeindex
\usepackage{xcolor}             % (Demonstration purposes only.)
\usepackage{hyperref,cleveref}  % LOAD THESE LAST!

% --- LATEX AND HTML CUSTOMIZATION ---
\title{The Lwarp Tutorial}
\author{Some Author}
\setcounter{tocdepth}{2}        % Include subsections in the \TOC.
\setcounter{secnumdepth}{2}     % Number down to subsections.
\setcounter{FileDepth}{1}       % Split \HTML\ files at sections
\booltrue{CombineHigherDepths}  % Combine parts/chapters/sections
\setcounter{SideTOCDepth}{1}    % Include subsections in the side\TOC
\HTMLTitle{Webpage Title}       % Overrides \title for the web page.
\HTMLAuthor{Some Author}        % Sets the HTML meta author tag.
\HTMLLanguage{en-US}            % Sets the HTML meta language.
\HTMLDescription{A description.}% Sets the HTML meta description.
\HTMLFirstPageTop{Name and \fbox{HOMEPAGE LOGO}}
\HTMLPageTop{\fbox{LOGO}}
\HTMLPageBottom{Contact Information and Copyright}
\CSSFilename{lwarp_sagebrush.css}
```

```
\begin{document}

\maketitle                      % Or titlepage/titlingpage environment.

% An article abstract would go here.

\tableofcontents                % MUST BE BEFORE THE FIRST SECTION BREAK!
\listoffigures

\chapter{First chapter}

\section{A section}

This is some text which is indexed.\index{Some text.}

\subsection{A subsection}

See \cref{fig:withtext}.

\begin{figure}\begin{center}
\fbox{\textcolor{blue!50!green}{Text in a figure.}}
\caption{A figure with text\label{fig:withtext}}
\end{center}\end{figure}

\section{Some math}

Inline math: $r = r_0 + vt - \frac{1}{2}at^2$
followed by display math:
\begin{equation}
a^2 + b^2 = c^2
\end{equation}


\begin{warpprint}   % For print output ...
\cleardoublepage    % ... a common method to place index entry into TOC.
\phantomsection
\addcontentsline{toc}{chapter}{\indexname}
\end{warpprint}
\ForceHTMLPage      % HTML index will be on its own page.
\ForceHTMLTOC       % HTML index will have its own toc entry.
\printindex

\end{document}
```

Table 4: Configuration files created by print version

tutorial.pdf: The PDF output from LaTeX. The print version of the document.

tutorial_html.tex: A small `.tex` file used to create a parallel HTML version of the document, which co-exists with usual the PDF version, and which will have its own auxiliary files. In this way, both PDF and HTML documents may co-exist side-by-side.

Auxiliary files: The usual LaTeX files `.aux`, `.log`, `.out`, `.toc`, `.lof`, `.idx`. When an HTML version of the document is created, `_html` versions of the auxiliary files will also be generated.

lwarpmk.conf: A configuration file for *lwarpmk*, which is used to automate the compilation of PDF or HTML versions of the document.

tutorial.lwarpmkconf: Another configuration file used by *lwarpmk*, which is only useful if you wish to have several projects residing in the same directory.

.css files: `lwarp.css`, `lwarp_formal.css`, `lwarp_sagebrush.css` These files are standard for lwarp, and are not meant to be modified by the user.

sample_project.css: An example of a user-customized CSS file, which may be used for project-specific changes to the lwarp defaults.

lwarp.ist: Used by lwarp while creating an index using *makeindex*. This file should not be modified by the user. A custom file may be used instead, if necessary.

lwarp.xdy: Used by lwarp while creating an index using *xindy*. This file should not be modified by the user. A custom file may be used instead, if necessary.

lwarp_one_limage.txt: For Windows only. Used to process SVG images in the background. Copied to `lwarp_one_limage.cmd` when images are generated.

lwarp_mathjax.txt: Inserted into the HTML files when MathJax is used to display math. Do not modify, see `\MathJaxFilename` instead.

comment_*.cut: Temporary files used by lwarp to conditionally process blocks of text. These files may be ignored.

When the `lwarpmk` option is given to the lwarp package:

lwarpmk.lua: A local copy of the *lwarpmk* utility.

On Unix-related operating systems this file must be made executable:

```
chmod u+x lwarpmk.lua
```

This may be useful to have to archive with a project for future use.

5.2 Compiling the print version with *lwarpmk*

The *lwarpmk* utility program is used to compile either the printed or the HTML version of the document.

`lwarpmk print` is used to recompile a printed version of the document.

⚠ Enable *lwarpmk*

1. If you have not yet done so, add `\usepackage{lwarp}` to the document, then compile the project a single time using *pdflatex*, *lualatex*, or *xelatex*. This generates the file `lwarpmk.conf`, which then allows the *lwarpmk* program to be used.

2. Re-compile the print version:

   Enter ⇒ **`lwarpmk print`**

   lwarpmk prints an introduction then checks to see if the document must be recompiled. If it seems that the files are up-to-date, then *lwarpmk* informs you of that fact and then exits.

3. Make a small change in the original document, such as adding a space character.

4. Recompile again.

   Enter ⇒ **`lwarpmk print`**

   The document is recompiled when a change is seen in the source. Several compilations may be necessary to resolve cross-references.

5. Force a recompile to occur.

   Enter ⇒ **`lwarpmk again`**

   Enter ⇒ **`lwarpmk print`**

   `lwarpmk again` updates the date code for the file, triggering a recompile the next time the document is made.[5]

6. Process the index.[6] [7]

   Enter ⇒ **`lwarpmk printindex`**

7. Recompile again to include the index.

   Enter ⇒ **`lwarpmk print`**

8. To force a single recompile when needed, even if no changes were detected:

   Enter ⇒ **`lwarpmk print1`**

Note that the HTML customization commands are ignored while making the print version.

[5] Although, when using the utility *latexmk* (introduced later), the changed date is ignored and an actual change in contents must occur to cause a recompile.

[6] The command **`lwarpmk printglossary`** is also available to process a glossary produced with the glossaries package. See section 8.6.12.

[7] Also see section 8.6.15 for index options.

5.3 Compiling the HTML version with *lwarpmk*

`lwarpmk html` is used to recompile an HTML version of the document.

⚠ Enable *lwarpmk*

1. If you have not yet done so, add `\usepackage{lwarp}` to the document, then compile the project a single time using *pdflatex*, *lualatex*, or *xelatex*. This generates the file `lwarpmk.conf`, which then allows the *lwarpmk* program to be used.

2. Compile the HTML version:

   Enter ⇒ **`lwarpmk html`**

   (a) *lwarpmk* uses LaTeX to process `tutorial_html.tex` to create `tutorial_html.pdf`.

   (b) *pdftotext* is then used to convert to the file `tutorial_html.html`. This file is a plain-text file containing HTML tags and content for the entire document.

   (c) *lwarpmk* manually splits `tutorial_html.html` into individual HTML files according to the HTML settings. For this tutorial, the result is `tutorial.html` (the home page), along with `First-chapter.html`[8], `Some-math.html`, and the document's index in `_Index.html`.[9]

3. View the HTML page in a web browser.

   Open the file `tutorial.html` in a web browser.

math

   Note that math is still displayed as its `alt` tag, which is the plain-text LaTeX source, until the images of the math expressions have been generated. Math may be displayed as SVG images or by a MathJax script, as seen in sections 5.4 and 5.5.

4. Force a recompile:

   Enter ⇒ **`lwarpmk again`**

   Enter ⇒ **`lwarpmk html`**

   Enter ⇒ **`lwarpmk print`**

5. Process the HTML index and recompile:[10][11]

   Enter ⇒ **`lwarpmk htmlindex`**

   Enter ⇒ **`lwarpmk html`**

   `_Index.html` is updated for the new LaTeX index.

6. Reload the web page to see the added index.

7. To force a single recompile when needed, even if no changes were detected:

   Enter ⇒ **`lwarpmk html1`**

[8] `First-chapter.html` also contains the first section, even though the second section is its own HTML page. This behavior is controlled by the boolean `CombineHigherDepths`.

[9] `index.html` is commonly used as a homepage, so the document index is in `_Index.html`.

[10] The command **`lwarpmk htmlglossary`** is also available to process a glossary produced with the glossaries package. See section 8.6.12.

[11] Also see section 8.6.15 for index options.

5.4 Generating the SVG images

math as SVG images

By default lwarp represents math as SVG images, with the LaTeX source included in `alt` attributes. In this way, the math is displayed as it was drawn by LaTeX, and the LaTeX source may be copied and pasted into other documents.

`picture` and Ti*k*z

lwarp uses the same mechanism for `picture` and Ti*k*z environments.

1. Create the SVG images:

   Enter ⇒ **`lwarpmk limages`**

   Enter ⇒ **`lwarpmk html`**

2. Move to the tutorial's HTML math page and reload the document in the browser.
3. The math images are displayed using the same font and formatting as the printed version.
4. Copy/paste a math expression into a text editor to see the LaTeX source.

⚠ adding/removing

When a math expression, `picture`, or Ti*k*z environment is added or removed, the SVG images must be re-created by entering **`lwarpmk limages`** to maintain the proper image-file associations. Inline SVG math may be hashed and thus not need to be recreated, but display math and objects such as Ti*k*z may move to new image numbers when the document is changed.

recompile first

Before attempting to create the SVG image files, *lwarpmk* verifies that the HTML version of the document exists and has correct internal image references.[12] If it is necessary to recompile the document's HTML version one more time, *lwarpmk* usually will inform the user with an error message, but there are some conditions which cannot be detected, so the user should watch for the LaTeX recompile warnings.

⚠ HTML instead of images

If HTML appears where an SVG image should be, recompile the document one more time to get the page numbers back in sync, then remake the images one more time.

⚠ page counter

Incorrect SVG images will also occur if the document changes the page counter:

```
\setcounter{page}{<value>}
```

The page counter must *not* be adjusted by the user.

⚠ Lots of files!

Expressing math as SVG images has the advantage of representing the math exactly as LaTeX would, but has the disadvantage of requiring an individual file for each math expression. For inline math, and some other objects, lwarp uses an MD5 hash on its LaTeX source to combine multiple instances of identical inline expressions into a single image file, but display math and other environments such as `picture` and Ti*k*z require one image file each. For a document with a large amount of math, see section 5.5 to use MathJax instead.

[12] This becomes important when dealing with a document containing thousands of images.

5.5 Using MathJax for math

math with MathJax

Math may also be represented using the MathJax JavaScript project.

1. In the tutorial's source code, uncomment the `mathjax` package option for lwarp:

   ```
   mathjax, % Use MathJax to display math.
   ```

2. Recompile

   Enter ⇒ **`lwarpmk html`**

3. Reload the math page.

⚠ MathJax requirements

MathJax requires web access unless a local copy of MathJax is available, and it also requires that JavaScript is enabled for the web page. The math is rendered by MathJax. Right-click on math to see several options for rendering, and for copying the LaTeX source.

While using MathJax has many advantages, it may not be able to represent complex expressions or spacing adjustments as well as LaTeX, and it may not support some math-related packages.

5.6 Changing the css style

For a formal CSS style, add to the preamble:

```
\usepackage{lwarp}
. . .
\CSSFilename{lwarp_formal.css}
. . .
\begin{document}
```

For a modern CSS style, `lwarp_sagebrush.css` is also provided:

```
\CSSFilename{lwarp_sagebrush.css}
```

See section 7.7 for more information about modifying the CSS styling of the document.

5.7 Customizing the HTML output

A number of settings may be made to control the HTML output, including filename generation, automatic compilation, math output, document splitting, meta data, and page headers and footers.

See section 7.6 for more information.

5.8 Using *latexmk*

latexmk is a LaTeX utility used to monitor changes in source files and recompile as needed.

1. In the tutorial's source code uncomment the `latexmk` option for the lwarp package:

   ```
   latexmk, % Use latexmk to compile.
   ```

2. Recompile the printed version of the document.

   Enter ⇒ **`lwarpmk print`**

   lwarp updates its own configuration files (`lwarpmk.conf` and `tutorial.lwarpmkconf`) whenever the printed version of the document is compiled. These configuration files remember that *lwarpmk* should use *latexmk* to compile the document.

3. Recompile the document.

   Enter ⇒ **`lwarpmk print`**

   and/or

   Enter ⇒ **`lwarpmk html`**

Changes are detected by comparing checksums rather than modification times, so `lwarpmk again` will not trigger a recompile, but *latexmk* has a much better awareness of changes than the *lwarpmk* utility does and it is likely to correctly know when to recompile. A recompile may be forced by making a small change to the source, and a single recompile may be forced with:

forced single-pass recompile

Enter ⇒ **`lwarpmk print1`**

and/or

Enter ⇒ **`lwarpmk html1`**

5.9 Using XeLaTeX or LuaLaTeX

XeLaTeX or LuaLaTeX may be used instead of LaTeX.

1. Remove the auxiliary files for the project:

   Enter ⇒ **`lwarpmk cleanall`**

2. Use *xelatex* or *lualatex* to compile the printed version a single time.

   Enter ⇒ **`xelatex tutorial.tex`**

   — *or* —

   Enter ⇒ **`lualatex tutorial.tex`**

   When the compile occurs, the configuration files for *lwarpmk* are modified to remember which TeX engine was used. XeLaTeX or LuaLaTeX will be used for future runs of *lwarpmk*.

3. To recompile the document:

   Enter ⇒ **`lwarpmk print`**

   -and-

   Enter ⇒ **`lwarpmk html`**

4. Also remember to update the indexes and recompile again:

   Enter ⇒ **`lwarpmk htmlindex`**

   Enter ⇒ **`lwarpmk html`**

   Enter ⇒ **`lwarpmk printindex`**

   Enter ⇒ **`lwarpmk print`**

5.10 Using DVI LaTeX

Traditional DVI LaTeX may also be used along with `.eps` image files. An SVG version of each image must also be provided. *lwarpmk* may be used to convert image formats.

To convert EPS files to PDF:

Enter ⇒ **`lwarpmk epstopdf *.eps`** **(or a list of files)**

To convert PDF files to SVG:

Enter ⇒ **`lwarpmk pdftosvg *.pdf`** **(or a list of files)**

⚠ bitmapped fonts See section 7.4 regarding font selection to avoid the use of bitmapped fonts.

5.11 Using a glossary

lwarp supports the gloss and glossaries packages, although this tutorial does not supply an example.

5.11.1 gloss package

See section 8.6.11.

5.11.2 glossaries package

To process the glossary for the print version:

Enter ⇒ **`lwarpmk printglossary`**

⚠ (If **`makeglossaries`** is not found, see section 8.6.12.)

To process the glossary for the HTML version:

Enter ⇒ **`lwarpmk htmlglossary`**

In each case, the document will have to be recompiled afterwards:

Enter ⇒ **`lwarpmk html1`**

Enter ⇒ **`lwarpmk html`**

Enter ⇒ **`lwarpmk print1`**

Enter ⇒ **`lwarpmk print`**

See section 8.6.12 to set options for processing glossaries.

5.12 Cleaning auxiliary files

To remove the auxiliary files `.aux`, `.toc`, `.lof`, `.lot`, `.idx`, `.ind`, `.log`, and `.gl*`, and a few others:

Enter ⇒ **`lwarpmk clean`**

5.13 Cleaning auxiliary and output files

To remove the auxiliary files, and also remove the `.pdf` and `.html` files:

Enter ⇒ **`lwarpmk cleanall`**

5.14 Cleaning the images from the <project>-images directory

The `<project>-images` directory contains SVG images automatically generated for inline and display math, tikz, etc. To remove all the images from the `<project>-images` directory:

Enter ⇒ **`lwarpmk cleanlimages`**

5.15 Converting PDF or EPS images to SVG

HTML cannot display PDF or EPS images, so any external PDF graphics images must be converted to SVG format. *pdftocairo* and *epstopdf* may be used one image at a time, but *lwarpmk* also provides a way to convert PDF or EPS images in bulk:

Enter ⇒ **`lwarpmk epstopdf *.eps`** **(or a list of files)**

Enter ⇒ **`lwarpmk pdftosvg *.pdf`** **(or a list of files)**

Be sure to always provide SVG files for HTML output.

5.16 Creating HTML from an incomplete compile

During testing it may be useful to finish the HTML conversion even when the document had errors and did not compile successfully. To attempt an HTML conversion of an incomplete document:

Enter ⇒ **`lwarpmk pdftohtml [-p project]`**

5.17 Processing multiple projects in the same directory

⚠ xr, xr-hyper, xcite

It is possible to have several projects in the same directory. *lwarpmk* has an optional parameter which is the document to compile.

To create each project:

Enter ⇒ **pdflatex project_a**

Enter ⇒ **pdflatex project_b**

Each project is given its own configuration file:

`project_a.lwarpmkconf, project_b.lwarpmkconf`

To compile each project with `lwarkmk`:

Enter ⇒ **lwarpmk print -p project_a**

Enter ⇒ **lwarpmk print -p project_b**

Enter ⇒ **lwarpmk html -p project_a**

Enter ⇒ **lwarpmk html -p project_b**

To generate each project's images:

Enter ⇒ **lwarpmk limages -p project_a**

Enter ⇒ **lwarpmk limages -p project_b**

To clean each project's images:

Enter ⇒ **lwarpmk cleanlimages -p project_a**

Enter ⇒ **lwarpmk cleanlimages -p project_b**

To clean each project's auxiliary files:

Enter ⇒ **lwarpmk cleanall -p project_a**

Enter ⇒ **lwarpmk cleanall -p project_b**

If using *bibtex*, for example, the HTML version must also be processed:

Enter ⇒ **bibtex project_a_html**

5.18 Using the *make* utility

lwarpmk has an action which may be useful for integration with the common *make* utility:

`lwarpmk pdftohtml [-p project]`

make may be used to compile the code to PDF with HTML tags (`project_html.pdf`), then *lwarpmk* may be used to convert each target to HTML files.

5.19 What next?

How do I do something? See the General Index.

Something do not work! See the Troubleshooting Index or section 13: Troubleshooting.

Package options: See section 29, Package options.

HTML and filename settings: See section 7.6, Customizing the HTML output.

Footnote placement: See section 7.6, Customizing the HTML output.

Title page, indexing, glossaries: See section 8.6, Front and back matter.

Shell escape: See section 7.3, Shell escape.

CSS customization: See section 7.7, Customizing the CSS.

MathJax customization: See section 8.7.5, Customizing MathJax.

Localization: (languages) — See section 7.1, Localization.

Accessibility: (`alt` and `title` tags) — See section 7.2, Accessibility.

Converting an existing document: See section 6, Converting an existing document.

EPUB conversion: See section 10, EPUB conversion.

Word processor conversion: See section 11, Word-processor conversion.

6 Converting an existing document

To convert an existing document for use with lwarp:

1. Arrange the document in the following order:
   (a) Declare the `\documentclass`.
   (b) Load text fonts.
   (c) Load inputenc or inputenx, fontenc, or fontspec.
   (d) Load lwarp.
   (e) Load remaining packages.
2. Modify the document:

⚠ math in section names

   (a) If using named HTML files, in section names use paren math `\(x+y\)` instead of dollar math `$x+y$`. (Dollar math works, but appears in the filename.) Or, use a short name for the TOC entry without the math, or use `\texorpdfstring` from the hyperref package:

```
\section{Some math \texorpdfstring{$1+2=3$}{three}}
```

⚠ scale

   (b) Avoid using the `\includegraphics` `scale` option. Change:

```
\includegraphics[scale=<xx>]{ . . . }
```

   to:

```
\includegraphics[width=<yy>\linewidth]{ . . . }
```

⚠ tabular

   (c) Possible changes to `tabular` environments include: `*` columns, multirow, longtable, supertabular, xtab, bigdelim. See section 8.10.1.

⚠ package options

   (d) If using braces in package options, such as with caption, see section 8.1.
   (e) Possible option clashes with memoir. See section 8.13.

⚠ indexes

   (f) If using indexes, see section 8.6.15.
   (g) If using many indexes, glossaries, `.aux` files, etc., see section 8.6.15 regarding morewrites. If morewrites is already used, be sure to add the setup with `allocate=10`.
   (h) Other changes as per Special cases and limitations, section 8.
3. Convert any PDF images to SVG. See section 8.8.
4. Manually compile the print version with *latex*, *pdflatex*, *lualatex*, or *xelatex*.
5. `lwarpmk print` to finish the print version.
6. `lwarpmk html` to create the HTML version.
7. `lwarpmk limages` to create the SVG images of any SVG math, `lateximage`, Ti*k*z, etc.

Need help?

See the General Index for "how-to", and the Troubleshooting Index if something doesn't work. A Troubleshooting section is also available. The Index of Objects contains automated entries for each package, macro, environment, counter, boolean, and other objects; individually and also sorted by category.

Table 5: Localization settings

Object names: LaTeX provides redefinable names for various objects, and lwarp adds a few more. Use `\renewcommand` to change these.

`\abstractname`: This macro is honored by lwarp.

`\linkhomename`: Displayed by the link to the homepage.

`\linkpreviousname`: Displayed by the link to the previous page

`\linknextname`: Displayed by the link to the next page.

`\sidetocname`: Displayed at the head of the sideTOC.

HTML settings: See table 8 and section 7.6 for details.

`\HTMLLanguage`: The language to declare for each web page.

`\ImageAltText`, `\MathImageAltText`, `\PackageDiagramAltText`, `\AltTextOpen`, `\AltTextClose`: The defaults used for HTML `alt` text for images. See section 7.2.

`\CSSFilename`: The name of the CSS file to use.

`\MathJaxFilename`: The name of the MathJax script to use.

Package options:

`ImagesName` and `ImagesDirectory`: These options control the filenames used by lwarp when it automatically generates images. See table 7 and section 7.5.

`xindyStyle`, `xindyLanguage`, `xindyCodepage`: When using *xindy*, these options may be set according to local use. See section 8.6.21.

`pdftotextEnc`: To adjust the encoding of *pdftotext*.

7 Additional details

7.1 Localization

Regional localization is supported by lwarp via the package options and macros shown in table 5.

7.2 Accessibility

lwarp provides several methods for improving access to the document using tools such as text-only browsers, copy/paste, text-to-speech readers, or Braille readers. lwarp can use the HTML `alt` text attribute for images, as describe below. lwarp can also use the HTML `title` attribute, which usually generates a pop-up text. lwarp can add this to a reference or hyperlink. lwarp also uses standard HTML5 elements which are pre-assigned ARIA roles for increased accessibility, and lwarp assigns the `math` role for SVG math images, and the `note` role for footnotes, end notes, margin paragraphs and notes, etc. MathJax also has provisions for improved accessibility as well. See table 6.

Table 6: Accessibiltiy settings

\ImageAltText: The default HTML `alt` text for `\includegraphics` and `lateximages`. Set with `\renewcommand`.

\includegraphics alt key: For `\includegraphics`, lwarp adds the `alt` key/value. For example:

```
\includegraphics[alt={Some text.}]{filename}
```

SVG math: For simple SVG math, lwarp places the LaTeX math expression in the `alt` text, so that the LaTeX expression may be copied and pasted to another document as plain text.

\MathImageAltText: For complicated SVG math, such as enclosed in `\InlineMathOther`/`\InlineMathNormal`, or `\DisplayMathOther`/`\DisplayMathNormal`, the HTML `alt` text will be set to `\MathImageAltText`. Set with `\renewcommand`.

MathJax: For MathJax, the accessibility tools provided by MathJax are enabled by default by lwarp's MathJax scripts.

\PackageDiagramAltText: Various packages create diagrams which lwarp converts into SVG images. These are given `alt` text set to `\PackageDiagramAltText`. Set with `\renewcommand`.

\ThisAltText: The HTML `alt` text of the next image may be set with:

```
\ThisAltText{Custom text about the image.}
<SVG math, Tikz, picture, etc.>
```

The next single image will be generated with the given text, and the following images will revert to back to their defaults.

`\ThisAltText` may also be used to assign an HTML `title` to the next reference or hyperlink.

```
\ThisAltText{Custom text about the link.}
Text ... \ref{label_name} ... text.
```

See section 7.6.

\AltTextOpen and \AltTextClose: By default, HTML `alt` text is enclosed by parentheses. This may be changed by redefining `\AltTextOpen` and `\AltTextClose`. Set with `\renewcommand`.

7.3 Shell escape

Opt --shell-escape

Some documents require the use of an external program, which is allowed when using the `--shell-escape` command-line option. When the document is first compiled manually, and also whenever the print version is recompiled, lwarp detects and remembers whether shell escape is enabled. If so, it will also be enabled when the document is recompiled with *lwarpmk*.

7.4 Font and UTF-8 support

⚠ type 3 bitmapped fonts

lwarp uses *pdftotext* to convert PDF output into UTF-8-encoded text. This process requires that UTF-8 information be embedded in the PDF file, which may prevent the use of older "type 3" bit-mapped fonts, and of older packages such as ae. The lwarp option `pdftotextEnc` may be useful in some situations. See section 7.5.

vector fonts
Computer Modern
⚠ *pdflatex*
⚠ DVI *latex*
Pkg cm-super

While using DVI *latex* or PDF *pdflatex*, if no font-related package is specified then the default Computer Modern font is used, which may be a "type 3" bit-mapped font which may not convert well to plain text. A "type 1" vector font is required.

To use the updated cm-super's type 1 fonts instead of Computer Modern, install the cm-super font package.

Pkg lmodern

To use Latin Modern instead, add

```
usepackage{lmodern}
```

to the preamble.

Pkg dejavu

Another useful option is the Deja Vu series of fonts, which have an increased coverage of language and glyphs:

```
\usepackage{dejavu}
```

latex, *pdflatex*, T1, UTF8

While using DVI *latex* or PDF *pdflatex*, lwarp automatically loads fontenc with T1 encoding. fontenc may be loaded with an additional encoding after lwarp. inputenc is automatically loaded with UTF8 encoding if if has not yet been loaded, but may also be specified with another encoding such as `latin1`. See the next section regarding index encoding.

⚠ *xelatex*, *lualatex*, fontspec

XeLaTeX and LuaLaTeX users must use the fontspec package. Do NOT use fontenc!

Place fontspec or fontenc, xunicode, and other font and UTF-8 related commands after the `\documentclass` command and before `\usepackage{lwarp}`.

⚠ package conflicts

In some cases, a package conflict may require that a font package be loaded after lwarp, which should work as well:

1. `documentclass{article/book/report}` comes first, followed by any of:
2. Font and UTF-8 related commands:
   - For XeLaTeX or LuaLaTeX:
     - fontspec and font choices

Pkg fontspec

ligatures

lwarp sets the following to turn off TeX ligatures during the generation

of HTML tags, and turn off common ligatures in regular text, since older browsers may not display them correctly and newer browsers can automatically re-create them.

```
\defaultfontfeatures[\rmfamily]{Ligatures={NoCommon,TeX}}
\defaultfontfeatures[\sffamily]{Ligatures={NoCommon,TeX}}
\defaultfontfeatures[\ttfamily]{Ligatures=NoCommon}
```

- For *pdflatex*:
  (a) `\usepackage{lmodern}`, or other font-related packages
  (b) `\usepackage[T1]{fontenc}`
  (c) `\usepackage[utf8]{inputenc}`, or `latin1`, etc. Or use inputenx.
  (d) `\usepackage{newunicodechar}` along with related definitions.
  (e) To assist with the PDF-HTML conversion:
    i. `\input glyphtounicode.tex`
    ii. `\input glyphtounicode-cmr.tex% from the pdfx package`
    iii. `\pdfgentounicode=1`
  (f) Another option to assist with the PDF-HTML conversion, such as the dotless j (`\j`):
    – `\usepackage{cmap}` — *or* —
    – `\usepackage{mmap}` — *or* —
    – `\usepackage[noTeX]{mmap}`
  (g) `\usepackage{textcomp}`

Pkg lmodern
Pkg fontenc
Pkg inputenc
Pkg inputenx
Pkg newunicodechar
File glyphtounicode.tex
⚠ dotless j
Pkg cmap
Pkg mmap
Pkg textcomp

3. `\usepackage{newtxmath}` or other math-related font packages. Many of these load amsmath, which may now be loaded before lwarp.

4. `\usepackage{lwarp}` (section 7.5) is placed after any of the above, followed by:

⚠ fontspec with monospaced fonts

5. `\setmonofont{TeX Gyre Cursor}` or similar may be required if using XeLaTeX or LuaLaTeX and fontspec along with traditional font packages such as txfonts, newtxtext, etc. This is required to turn off the monospaced font's ligatures with fontspec after loading the traditional font packages. Monospaced output ligatures must be turned off to produce the correct HTML characters.

   Any monospace font with built-in ligatures may require these ligatures to be disabled for HTML. In one example, JetBrain Mono, it is required to use

   ```
   \setmonofont{JetBrains Mono}[%
   . . .
   Contextuals=AlternateOff,
   ]
   ```

   After lwarp is loaded, the ligature may be re-enabled for print mode by using `\setmonofont` again inside a `warpprint` environment.

⚠ JetBrain Mono
⚠ HTML corrupted

6. … the rest of the preamble and the main document.

⚠ UTF-8 locale In some cases, an external program may require a UTF-8 "locale". See section 9.8.

7.4.1 Indexes, glossaries, and encoding

lwarp supports *makeindex*, *xindy*, *xindex*, and glossaries, gloss, and nomencl.

See section 8.6.14 for indexing, and section 8.6.12 for the glossaries package.

7.5 lwarp package loading and options

lwarp supports book, report, and article classes, as well as the equivalent Koma-script classes and memoir, and various CJK-related classes and packages.

Load the lwarp package immediately after the font and UTF-8 setup commands.

Package options may be set while loading lwarp, or later with

```
\lwarpsetup{⟨key=value, . . . ⟩}
```

Pkg lwarp

lwarp package options are as follows:

Opt mathsvg
Opt mathjax

mathsvg and **mathjax:** Selects SVG images or MathJax for math display. See section 8.7.

Default: mathsvg

Opt latexmk
Default: false

latexmk: Tells *lwarpmk* to use *latexmk* to recompile the document several times if necessary. Otherwise, *lwarpmk* attempts to determing for itself whether to recompile. See section 7.6.

Opt dvips
Default: false

dvips: Tells *lwarpmk* to use *dvips* and *ps2pdf* to convert DVI output to PDF.

Opt dvipdfm
Default: false

dvipdfm: Tells *lwarpmk* to use *dvipdfm* to convert DVI output to PDF.

Opt dvipdfmx
Default: false

dvipdfmx: Tells *lwarpmk* to use *dvipdfmx* to convert DVI output to PDF.

Opt HomeHTMLFilename
Default: \BaseJobname

HomeHTMLFilename:

Filename of the homepage, without the "`.html`" suffix. Defaults to the `\BaseJobname`. A common setting is:

```
HomeHTMLFilename=index
```

filename underscores

causing the homepage to be the file `index.html`. Underscores are allowed in `HomeHTMLFilename` and `HTMLFilename` options, but may need to be escaped elsewhere, such as when appearing in a list:

```
\item [\href{file\_name.pdf}{text}] \
```

See section 7.6.1 for examples of naming and numbering HTML files.

Opt HTMLFilename
Default: <empty>

HTMLFilename: A filename prefix for the rest of the HTML web pages. Useful for numbered web pages with a common prefix. May be empty. See section 7.6.1 for examples of naming and numbering HTML files.

Opt ImagesName
Default: image-

ImagesName: The prefix for the images automatically generated by lwarp for objects such as SVG math and `lateximages`.

Opt ImagesDirectory
Default: \jobname-images

ImagesDirectory: The directory for the images automatically generated by lwarp for objects such as SVG math and `lateximages`. By default, these images will appear in a

Table 7: Lwarp package options

Option	Description
mathsvg	Show math using SVG images.
mathjax	Show math using MathJax.
latexmk	Use *latexmk* for compiling documents.
dvips	Use *dvips* and *ps2pdf* to convert DVI documents.
dvipdfm	Use *dvipdfm* to convert DVI documents.
dvipdfmx	Use *dvipdfmx* to convert DVI documents.
HomeHTMLFilename	The filename of the home page.
HTMLFilename	A prefix for the filenames of the remaining web pages.
ImagesName	A prefix for the filenames of generated images.
ImagesDirectory	The directory used to hold generated images.
PrintLatexCmd	The shell commands for **lwarpmk print**.
HTMLLatexCmd	The shell commands for **lwarpmk html**.
For indexing (section 8.6.15) and glossaries (section 8.6.12):	
makeindex	Use *makeindex* to generate indices.
makeindexStyle	Set a custom style for *makeindex*.
xindy	Use *xindy* to generate indices.
xindyStyle	Set a custom style for *xindy*.
xindyLanguage	The *xindy* language option used for index generation.
xindyCodepage	The *xindy* codepage option used for index generation.
xindex	Use *xindex* to generate indices.
xindexConfig	Set a custom configuration file for *xindex*.
PrintIndexCmd	Shell commands executed by **lwarpmk printindex**.
HTMLIndexCmd	Shell commands executed by **lwarpmk htmlindex**.
LatexmkIndexCmd	Shell commands executed by *latexmk*.
IndexRef	How to format index links.
GlossaryCmd	Shell command executed by **lwarpmk printglossary** and **lwarpmk htmlglossary**.
Seldom necessary:	
OSWindows	Force compatibility with MS-Windows.
pdftotextEnc	Set the encoding for *pdftotext*.
lwarpmk	Generate a local copy of `lwarpmk.lua`.
Used internally by lwarp:	
warpprint	Generate print output, and also generate configuration files.
warpHTML	Generate HTML output.
BaseJobname	The `\jobname` to use. Set to the `\jobname` of the printed version even while generating HTML.

directory named `<jobname>-images`, and the images will be named and numbered `image-<nn>`.

Opt `PrintLatexCmd` Default: `<automatic>`

`PrintLatexCmd:` Sets the shell commands executed by **`lwarpmk print`**. If not specified, will automatically be set according to the detected LaTeX engine and the use of `--shell-escape`.

Opt `HTMLLatexCmd` Default: `<automatic>`

`HTMLLatexCmd:` Sets the shell commands executed by **`lwarpmk html`**. If not specified, will automatically be set according to the detected LaTeX engine and the use of `--shell-escape`.

Opt `makeindex` Default: `makeindex`

`makeindex:` Sets `PrintIndexCmd`, `HTMLIndexCmd`, and `LatexmkImageCmd` to use *makeindex* when generating indexes with **`lwarpmk printindex`**, **`lwarpmk htmlindex`**, or *latexmk*. If neither `makeindex` nor `xindy` is used, `makeindex` is assumed.

Opt `makeindexStyle` Default: `lwarp.ist`

`makeindexStyle:` If you wish to use a custom `.ist` file for index generation, see section 8.6.20.

Opt `xindy` Default: `makeindex`

`xindy:` Sets `PrintIndexCmd`, `HTMLIndexCmd`, and `LatexmkImageCmd` to use *xindy* when generating indexes with **`lwarpmk printindex`**, **`lwarpmk htmlindex`**, or *latexmk*.

Opt `xindyStyle` Default: `lwarp.xdy`

`xindyStyle:` If you wish to use a custom `.xdy` file for index generation, see section 8.6.21.

Opt `xindyLanguage` Default: `english`

`xindyLanguage:` If using an index or glossary, see section 29.

Opt `xindyCodepage` Default: `utf8`

`xindyCodepage:` If using an index, see section 29.

Opt `xindex` Default: `makeindex`

`xindex:` Sets `PrintIndexCmd`, `HTMLIndexCmd`, and `LatexmkImageCmd` to use *xindex* when generating indexes with **`lwarpmk printindex`**, **`lwarpmk htmlindex`**, or *latexmk*.

Opt `xindexConfig` Default: `<empty>`

`xindexConfig:` If you wish to use a custom `xindex-*.lua` file for index generation, see section 8.6.22.

Opt `PrintIndexCmd` Default: `<automatic>`

`PrintIndexCmd:` Sets the shell commands executed by **`lwarpmk printindex`**. If not specified, will be set by the selection of `makeindex` or `xindy`. May be used to specify the creation of multiple indexes. See section 8.6.15.

Examples:

```
makeindex -s lwarp.ist projectname.idx                (makeindex)
xindy -M lwarp.xdy -L english -C utf8 projectname.idx      (xindy)
```

automatic setting

The use of the `makeindex` or `xindy` options sets `PrintIndexCmd` to sensible values for each of those programs while compiling a single index. lwarp's `makeindexStyle`, `xindyStyle`, `xindyLanuage`, and `xindyCodepage` options will be used if specified.

⚠ xindy

If specifying `PrintIndexCmd` manually, be sure to assign an *xindy* language and

codepage with the -L and -C *xindy* options, as the lwarp xindyLanguage and xindyCodepage options are not used for the PrintIndexCmd option when it is set manually.

This option is stored in the configuration files lwarpmk.conf and *.lwarpmkconf, and is then passed by the **lwarpmk printindex** command to the operating system to compile the print indexes. Since the command string is parsed by TEX, written to a file, read from the file by LuaTEX, and finally passed to the operating system, any attempt at quoting will be problematic. For complicated commands, it would be best to create a shell script, and simply refer to the script with the lwarp PrintIndexCmd option.

Opt HTMLIndexCmd
Default: <automatic>

HTMLIndexCmd: Sets the shell commands executed by **lwarpmk htmlindex**. If not specified, will be set by the selection of makeindex or xindy. May be used to specify the creation of multiple indexes. See section 8.6.15.

⚠ filenames

Example settings are similar to PrintIndexCmd, but append _html to the filenames:

```
makeindex -s lwarp.ist projectname_html.idx            (makeindex)
xindy -M lwarp.xdy -L english -C utf8 projectname_html.idx  (xindy)
```

automatic setting

The use of the makeindex or xindy options sets HTMLIndexCmd to sensible values for each of those programs while compiling a single index. lwarp's makeindexStyle, xindyStyle, xindyLanuage, and xindyCodepage options will be used if specified.

⚠ xindy

If specifying HTMLIndexCmd manually, be sure to assign an *xindy* language and codepage with the -L and -C *xindy* options, as the lwarp xindyLanguage and xindyCodepage options are not used for the HTMLIndexCmd option when it is set manually.

As with PrintIndexCmd, to generate complicated indexes it may be worthwhile to use a shell script, then refer to that script with HTMLIndexCmd.

Opt LatexmkIndexCmd
Default: <automatic>

LatexmkIndexCmd: Sets the shell commands executed by *latexmk*. Unlike PrintIndexCmd and HTMLIndexCmd, LatexmkIndexCmd does not include any filenames, which will be provided instead by *latexmk*. See section 8.6.15.

Example settings are similar to PrintIndexCmd, but without a filename:

```
makeindex -s lwarp.ist                                 (makeindex)
xindy -M lwarp.xdy -L english -C utf8                      (xindy)
```

automatic setting

The use of the makeindex or xindy options sets LatexmkIndexCmd to either of the two settings show above. lwarp's makeindexStyle, xindyStyle, xindyLanuage, and xindyCodepage options will be used if specified. Unlike PrintIndexCmd and HTMLIndexCmd, *latexmk* uses either of the single-line settings of LatexmkIndexCmd shown above to compile each of multiple indexes if necessary.

⚠ xindy

If specifying LatexmkIndexCmd manually, be sure to assign an *xindy* language and codepage with the -L and -C *xindy* options, as the lwarp xindyLanguage and xindyCodepage options are not used for the LatexmkIndexCmd option when it is set manually.

Opt IndexRef
Default: cref

IndexRef: Describes how to display the index entries for HTML output. Possible values are ref, nameref, refnameref, cref, crefnameref, autoref, or a text string such

as (link) or (*) for each index entry reference. (Adding parentheses around a single character makes the link larger and easier to click on.) The default is cref, which is available even if the print document does not use cleveref, as the lwarp package relies on cleveref during HTML output. Option autoref gives the same results as cref.

\ref and \cref to starred or otherwise unknown links will display as (*) instead of ??.

⚠ ?? If using cref (the default), and if a reference appears as ?? with a non-functional link, use cleveref's \crefname to give a name to that type of label.

In general, crefnameref gives the most information, but the index can become quite verbose. Using (*) or similar yields a very compact index.

Opt GlossaryCmd
Default: **makeglossaries**

GlossaryCmd: Sets the shell command executed by **lwarpmk printglossary** and **lwarpmk htmlglossary**. The print or HTML glossary filename is appended to this command. See section 8.6.12.

Opt OSWindows

OSWindows: lwarp attempts to automatically sense WINDOWS, but it may be forced with this option. See section 7.9.

Opt pdftotextEnc
Default: UTF-8

pdftotextEnc: Used to specify the encoding used by *pdftotext* during the PDF-HTML conversion. In most situations, the default is the correct choice.

Opt lwarpmk

lwarpmk: If you wish to have lwarp generate a local copy of lwarpmk.lua for archival or local-installation purposes, compile the print version with the lwarpmk option set. See section 29.

The following options are used internally by lwarp, and usually are not used in the user's document:

Opt warpprint
Opt warpHTML

warpprint and **warpHTML:** Usually controlled by *lwarpmk*, and not set in the document. Select the warpprint option to generate print output (default), or the warpHTML option to generate HTML5 output. The default is print output, so the print version may be compiled with the usual *pdflatex*, etc. When lwarp is loaded in print mode, it creates <project>_html.tex, which sets the warpHTML option before calling the user's source code <project>.tex. In this way, <project>.tex can \usepackage{lwarp} without any options to create a printed version, while <project>_html.tex will create an HTML version.

Opt BaseJobname
Default: \jobname

BaseJobname: Not intended for the user. Used internally by lwarp when creating the *_html.tex file used to compile the HTML version. See section 29.

7.6 Customizing the HTML output

Table 8 shows several settings may be used to customize the HTML output. Watch for the correct placement of each!

⚠ Placement!

⚠ Changes! Note that if changes are made, it is best to first:

1. Clear all the HTML, PDF, and auxiliary files:
   Enter ⇒ **`lwarpmk clearall`**
2. Recompile the print version in order to recreate the configuration files for *lwarpmk*:
   Enter ⇒ **`lwarpmk print`**
3. Finally, recompile the HTML version with the new settings:
   Enter ⇒ **`lwarpmk html`**

Placed in the preamble before `\begin{document}`:

`\HTMLFirstPageTop` Default: `<empty>`

`\HTMLFirstPageTop`: {⟨*contents*⟩} A user-definable custom action applied to the top of the home page. Useful for logos, etc. `\LinkNext` may be used to link to the next web page. Defaults empty. Ignored in print output.

`\HTMLFirstPageBottom` Default: `<empty>`

`\HTMLFirstPageBottom`: {⟨*contents*⟩} A user-definable custom action applied to the bottom of the home page. Useful for logos, etc. `\LinkNext` may be used to link to the next web page. Defaults empty. Ignored in print output.

`\linkhomename` Default: `Home`

`\linkhomename`: Name of the link to the home page. Paragraphs are allowed. Redefine with `\renewcommand`.

`\linkpreviousname` Default: `Previous`

`\linkpreviousname`: Name of the link to the previous page. Paragraphs are allowed. Redefine with `\renewcommand`.

`\linknextname` Default: `Next`

`\linknextname`: Name of the link to the next page. Paragraphs are allowed. Redefine with `\renewcommand`.

Ctr `tocdepth`

`tocdepth`: Sectioning depth of the table of contents. See section 16 for a list of LaTeX stack depths.

Ctr `SideTOCDepth` Default: 1

`SideTOCDepth`: Sectioning depth of the sideTOC. Defaults to 1, causing the sideTOC to show sections but not subsections.

sideTOC

Each subpage of the website has its own small table of contents on the side (the "sideTOC"). Its depth is set by `SideTOCDepth`. This sideTOC is only shown if the browser display is wide enough. When using a narrow web browser window, "responsive web design" is used to show the sideTOC at the top of the page, as well as a link back to **Home** at the top and bottom.

It is recommended to set:

```
SideTOCDepth=FileDepth
```

or

```
SideTOCDepth=FileDepth+1
```

Table 8: HTML settings

Macro/Cntr/Bool	Loc*	Description
\linkhomename	P	Name of the link to the homepage.
\linkpreviousname	P	Name of the link to the previous page.
\linknextname	P	Name of the link to the next page.
SideTOCDepth	P	Sectioning depth of the sideTOC.
\sidetocname	P	Name of the sideTOC.
FileDepth	P	Sectioning depth of the file splits.
CombineHigherDepths	P	Combine higher section levels.
FileSectionNames	P	Use section names for file names, else use numbers.
\FilenameLimit	P	Maximum length of the generated filenames.
FootnoteDepth	P	Sectioning depth of footnotes.
\abstractname	P	The name of the abstract.
\ImageAltText	PD	\includegraphics and other images' alt tag.
\ThisAltText {⟨text⟩}	PD	Assigns an alt/title tag for the next image or link.
\MathImageAltText	PD	The SVG math image lateximage alt tag.
\PackageDiagramAltText	PD	The suffix for a package's lateximage alt tags.
\AltTextOpen	PD	Start an HTML alt tag.
\AltTextClose	PD	End an HTML alt tag.
\CSSFilename	PS	The CSS for the following files.
\MathJaxFilename	PS	The MathJax script for the following files.
\HTMLLanguage	PS	The HTML lang tag.
\HTMLTitle	PS	The homepage's <title>, overriding \title.
\HTMLTitleBeforeSection	PS	Set subpage <title>s to \HTMLTitle - sectionname
\HTMLTitleAfterSection	PS	Set subpage <title>s to sectionname - \HTMLTitle
\HTMLAuthor	PS	The HTML author meta tag, overriding \author.
\HTMLDescription	PS	The HTML description meta tag.
\HTMLFirstPageTop	P	Heading for the home page.
\HTMLFirstPageBottom	P	Footer for the home page.
\HTMLPageTop	PS	Heading for the other pages.
\HTMLPageBottom	PS	Footer for the other pages.
\IndexPageSeparator	P	Index page list separator.
\IndexRangeSeparator	P	Index page range separator.
FixSmallCaps	P	Set true if small caps rendered as all caps.
HTMLDebugComments	P	Boolean to generate HTML comments.

* **P:** Preamble, **D:** Anywhere in the document. **S:** Before a section.

⚠ inaccessible pages

If SideTOCDepth < FileDepth, web pages will be inaccessible via the sideTOC.

\sidetocname
Default: Contents

\sidetocname: Name of the sideTOC. Paragraphs are allowed. Redefine with \renewcommand.

Ctr FileDepth
Default: -5

FileDepth: Sectioning depth of file splits. Defaults to -5, causing the entire HTML website to be one single file.

- To place the entire file into one HTML page, use:
  \setcounter{FileDepth}{-5}
- To split the HTML file at \section depth, use:
  \setcounter{FileDepth}{1}
- To ensure that the HTML pages/files are accessible:
  Place a \tableofcontents somewhere before the first section break (therefore in the "home page"), and set
  tocdepth >= FileDepth

⚠

Bool CombineHigherDepths
Default: true

CombineHigherDepths: Combine a higher section with its first lower subsections, down to the FileDepth. Defaults to true. Set to false to simulate the concept of a chapter opening on its own page, for example.

The file splits are controlled by the counter FileDepth and the boolean CombineHigherDepths. Setting FileDepth to 0 splits the file at chapters, 1 at sections, etc. CombineHigherDepths controls whether to combine pages at levels higher than the chosen FileDepth, such as in this tutorial where the page which opens the chapter also contains the first section. Be careful to set tocdepth and SideTOCDepth to allow access to each page of the website. Set tocdepth and SideTOCDepth to be greater than or equal to FileDepth.

⚠ Inaccesible pages!

⚠ Lost in an old page!

When making changes to the file structure, it is possible to end up with the web browser pointing to an old file which is no longer in use. When this occurs, changes to the web site will not appear in the browser, even if reloading the page, because that page is no longer in use. It is best to return to the home page, clean the files (lwarpmk cleanall), change FileDepth and/or CombineHigherDepths, then finally recompile and renavigate to the desired page using the new file structure.

Bool FileSectionNames
Default: true

FileSectionNames: If true, web page filenames are derived from a sanitized version of the section names. If false, web pages are numbered. Either way, the HTMLFilename option is used as a prefix. See section 7.6.1 for examples of naming and numbering HTML files. The user must ensure that filenames are unique after begin sanitized. For example, math in the section name is removed before creating the filename, so the rest of the filename must be sufficiently unique to avoid name collisions.

⚠ Unique filename!

\FilenameLimit
Default: 80

\FilenameLimit: The maximum length of the filenames generated by lwarp. ".html" is added to this length. Redefine with \renewcommand.

Ctr FootnoteDepth
Default: 3

FootnoteDepth: Determines where to place pending footnotes. 3 places footnotes before each break down to the \subsubsection level. 1 places footnotes before each \section break. Any pending footnotes are also placed at the bottom of each page before each file break.

Bool FixSmallCaps
Default: false

FixSmallCaps: Set true if Small Caps are rendering in all caps ("SMALL CAPS").

May be required for some fonts (erewhon, utopia, fbb, et al.), and packages such as embrac.

Bool HTMLDebugComments
Default: false

HTMLDebugComments: Set true to generate HTML comments, such as which section or is being opened or closed.

\abstractname
Default: Abstract

\abstractname: The name of the abstract. This may also be over-written by the babel package. Defaults to "Abstract". Redefine with \renewcommand.

\IndexPageSeparator
Default: ", "

\IndexPageSeparator: Index page list separator. Adjust to match index style file. If using gindex, this is set automatically to gindex's \indexpagessep.

\IndexRangeSeparator
Default: "--"

\IndexRangeSeparator: Index page range separator. Adjust to match index style file. If using gindex, this is set automatically to gindex's \indexrangesep.

Placed before \begin{document}, or before any sectioning command which causes a file break:

\CSSFilename
Default: lwarp.css

\CSSFilename: {⟨*filename.css*⟩} Sets the CSS file to use for the following files. May be changed before each each sectioning command which would cause a file split.

The CSS styles of the web pages are set by the \CSSFilename command. If \CSSFilename is not used, a default plain style is used to mimic printed LaTeX output. lwarp_sagebrush.css is a semi-fancy colored style as shown in this tutorial. Change it to lwarp_formal.css for a more formal look, or comment out the \CSSFilename command to see the default. \CSSFilename may be used before each file break to set the CSS for individual pagess of the website.

\MathJaxFilename
Default: lwarp_mathjax.txt

\MathJaxFilename: {⟨*filename*⟩} Sets the MathJax script file to use for the following files. May be changed before each each sectioning command which would cause a file split.

The MathJax script file is copied into the head of each HTML file. This may be used to point to a local repository, add extensions, or change the script somewhere in the middle of the document. \MathJaxFilename may be used before each file break to set the script file for individual pages of the website.

\HTMLLanguage
Default: en-US

\HTMLLanguage: {⟨*langauge*⟩} The HTML file's HTML lang meta tag. Defaults to en-US.

\HTMLTitle
Default: \thetitle

\HTMLTitle: {⟨*title*⟩} Overrides \title for the HTML header's meta title. Defaults to \thetitle, which is set by \title, or empty otherwise. Unlike the author, \thetitle is set by \title even if not using the titling package.

\HTMLTitleBeforeSection
Default: \HTMLTitleBeforeSection

\HTMLTitleBeforeSection: Sets subpage <title> tags to show the website title followed by the section name.

\HTMLTitleAfterSection

\HTMLTitleAfterSection: Sets subpage <title> tags to show the section name followed by the website title.

custom <title>

To customize subpage <title>s, redefine \theHTMLTitleSection, which defaults to:

```
\def\theHTMLTitleSection{%
  \theHTMLTitle\theHTMLTitleSeparator\theHTMLSection%
}
```

\HTMLAuthor
Default: \theauthor

\HTMLAuthor: {⟨*author*⟩} The HTML header's meta author. Defaults to \theauthor, which is set by \author if using the titling package, but is empty otherwise. There are several ways to represent the author and affiliations, especially if using the authblk package, most of which do not result in a sensible \theauthor, so \HTMLAuthor is useful to create a list of authors without their affiliations.

\HTMLDescription
Default: <empty>

\HTMLDescription: {⟨*description*⟩} Sets the HTML description tag for the following files. May be changed before each each sectioning command which would cause a file split.

\HTMLPageTop
Default: <empty>

\HTMLPageTop: {⟨*contents*⟩} A user-definable custom action applied to the top of pages other than the home page. Useful for logos, etc. Defaults empty. \LinkHome may be used to place a link back to the homepage, as well as \LinkPrevious and \LinkNext. Ignored in print output.

\HTMLPageBottom
Default: <empty>

\HTMLPageBottom: {⟨*contents*⟩} A user-definable custom action applied to the bottom of pages other than the home page. Useful for authors, copyright notices, contact information, etc. Defaults empty. \LinkHome may be used to place a link back to the homepage, as well as \LinkPrevious and \LinkNext. Ignored in print output.

\LinkHome

\LinkHome: Creates a link to the home page. Usually used in \HTMLPageTop and related.

\LinkPrevious

\LinkPrevious: Creates a link to the previous HTML page, unless already at the home page. Usually used in \HTMLPageTop and related.

\LinkNext

\LinkNext: Creates a link to the next HTML page, unless already at the end. Usually used in \HTMLPageTop and related.

Placed in the home page before the first sectioning command which causes a file break:

\tableofcontents
⚠ TOC on the homepage!

\tableofcontents: Used to place a table of contents on the home page. This command must be used before the first file split, so that a way is available to navigate to other files from the homepage.

Links to each chapter/section are provided, as selected by tocdepth.

Placed in the document wherever necessary:

\ImageAltText
Default: image

\ImageAltText: Redefine with \renewcommand. \includegraphics and other images are assigned an HTML alt tag according to \ImageAltText along with \AltTextOpen and \AltTextClose. This text is visible in the browser if images are not loaded, and appears when the text is copied and pasted. The default is "image", and it may be changed according to the document's language. This may be set in the preamble, or changed as necessary inside the document, where it will affect the following \includegraphics and other images.

\ThisAltText

\ThisAltText: {⟨*text*⟩} \ThisAltText can be used to assign an HTML alt text attribute to the next image generated by a lateximage, picture, tikzpicture, or any other similar environment which generates an image, or the next SVG math expression. This tag is cleared after use. The tag is also cleared after

each MathJax expression, in case the user changes between SVG math and MathJax.

`\ThisAltText` also may be used to add an HTML `title` to a reference or hyperlink, such as a `\ref`, `\cref`, `\href`, `\url`, `\hyperref`, or `\hyperlink`. In each case, the alternative text is cleared after use.

`\MathImageAltText` Default: `math image`

`\MathImageAltText`: Redefine with `\renewcommand`. When creating an SVG math image, its HTML `alt` tag may be set to the math expression, which may be hashed for image reuse. In the case of `\ensuremath` or after `\inlinemathother`, where the contents require a unique image for each instance of the same expression, the `alt` tag is set to `\MathImageAltText`, along with `\AltTextOpen` and `\AltTextClose`, and the image is not reused.

This `alt` expression is visible in the browser if images are not loaded, and appears when the text is copied and pasted. The default is "`math image`", and it may be changed according to the document's language. This may be set in the preamble, or changed as necessary inside the document, where it will affect the following SVG math images.

`\PackageDiagramAltText` Default: `diagram`

`\PackageDiagramAltText`: Redefine with `\renewcommand`. For many packages, the output is placed inside a `lateximage` with an HTML `alt` tag set to the package name followed by `\PackageDiagramAltText`. For example:

```
(-xy- diagram)
```

This expression is visible in the browser if images are not loaded, and appears when the text is copied and pasted. The default is "diagram", and may it be changed according to the document's language. This may be set in the preamble, or changed as necessary inside the document, where it will affect the following package diagrams.

`\AltTextOpen` Default: `(`

`\AltTextOpen`: Redefine with `\renewcommand`.

`\AltTextClose` Default: `)`

`\AltTextClose`: Redefine with `\renewcommand`. HTML `alt` text is enclosed by the macros `\AltTextOpen` and `\AltTextClose`, which default to an opening and closing parenthesis.

Env `warpprint`

`warpprint`: An environment which is only used while generating print output. Place inside anything which does not apply to HTML and which may cause problems with lwarp. If lwarp knows about and emulates or supports a package then its related macros, lengths, counters, etc. probably won't have to be placed inside a `warpprint` environment, but unknown packages may cause problems which may be isolated from lwarp using this environment.

⚠ *Do not place anything else on the same line as* `\end{warpprint}`. Also do not nest `warpprint` inside itself.

Env `warpHTML`

`warpHTML`: An environment which is only included while generating HTML output. This is useful for website logos and other items which have no purpose in printed output.

⚠ *Do not place anything else on the same line as* `\end{warpHTML}`. Also do not nest `warpHTML` inside itself.

`\warpprintonly`

`\warpprintonly`: {⟨*contents*⟩} A macro version of the `warpprint` environment.

\warpHTMLonly **\warpHTMLonly:** {⟨*contents*⟩} A macro version of the warpHTML environment.

7.6.1 Example HTML file naming

Examples of ways to name or number HTML files:

Numbered HTML nodes:

Example: Homepage index.html, and node-1, node-2. [13]

```
\usepackage[
    HomeHTMLFilename=index,
    HTMLFilename={node-}
]{lwarp}
\boolfalse{FileSectionNames}
```

Named HTML sections, no prefix:

Example: index.html, and About.html, Products.html

```
\usepackage[
    HomeHTMLFilename=index,
    HTMLFilename={}
]{lwarp}
\booltrue{FileSectionNames}
```

Named HTML sections, with prefix:

Example: Homepage mywebsite.html, and additional pages such as mywebsite-About.html, mywebsite-Products, etc.

```
\usepackage[
    HomeHTMLFilename=mywebsite,
    HTMLFilename={mywebsite-}
]{lwarp}
\booltrue{FileSectionNames}
```

7.7 Customizing the CSS

\CSSFilename {⟨*filename*⟩}
Default: lwarp.css

\CSSFilename may be used to choose which .css file is used to display each page of the web site. Use \CSSFilename before \begin{document} to assign the style of the home page. If different parts of the website should have different styles, call \CSSFilename again before each section heading which creates a new file. This may be changed numerous times throughout the file, resulting in different HTML pages having different CSS files assigned:

[13] See \SetHTMLFileNumber to number in groups by chapter, for example.

```
...
\CSSFilename{myCSS.css}
\chapter{Another Chapter}
...
```

The styles provided by lwarp include:

lwarp.css: A default style if \CSSFilename is not used. This style is comparable to a plain LaTeX document. To set this style, you may use \CSSFilename{lwarp.css}, or no \CSSFilename call at all.

lwarp_formal.css: A formal style with a serif fonts and a traditional look.

lwarp_sagebrush.css: A style with muted colors, gradient backgrounds, additional borders, and rounded corners.

To see each style in use, change the \CSSFilename entry in the tutorial, lwarpmk html again, and then reload the tutorial webpage.

Custom css

A customized style may also be created. For each new project a file called sample_project.css is generated. This may be renamed to <project>.css then used by assigning \CSSFilename{<project>.css}.

⚠ Rename it!

Note that sample_project.css is overwritten whenever lwarp is loaded in print mode. It is therefore important to rename the file to something like <project>.css before using it, so that your own changes are not overwritten.

<project>.css has an entry which loads lwarp.css, and this entry may be changed to load lwarp_formal.css or lwarp_sagebrush.css if desired. Additional changes to the css may be made by making entries later in the <project>.css file.

File lwarp.css
File project.css
File sample_project.css

It is best to make a local project-specific css file such as project.css, containing only things which are different from lwarp.css. The file project.css should refer to lwarp.css as follows:

```
/* ( --- Start of project.css --- ) */
/* ( --- A sample project-specific CSS file for lwarp --- ) */

/* Uncomment one of the following: */
@import url("lwarp.css") ;
/* @import url("lwarp_formal.css") ; */
/* @import url("lwarp_sagebrush.css") ; */

/* Project-specific CSS setting follow here. */
/* . . . */

/* ( --- End of project.css --- ) */
```

Finally use \CSSFilename{<project>.css} in the document to activate the custom css.

7.8 Assigning css classes and styles

HTML CSS classes and styles may be assigned to fragments of the document.

Env BlockClass [⟨*style*⟩] {⟨*class*⟩}

An entire block of text, including paragraphs, may be assigned a CSS class and optional CSS style using the BlockClass environment. The result is placed inside a . A BlockClass may nest other BlockClasses or \InlineClasses.

\InlineClass (⟨*WP CSS style*⟩) [⟨*web CSS style*⟩] {⟨*CSS class*⟩} {⟨*text*⟩}

A section of text without paragraphs may be assinged a CSS class and optional CSS style using the \InlineClass macro. The result is placed inside a . \InlineClass may be nested, but per the HTML standard it must not contain BlockClass, nor may it contain a paragraph, nor several other objects such as HTML figures. \InlineClass also accepts a second optional parameter, enclosed inside parentheses, which assigns the style while generating output for a word processor, while ignoring the web style.

Nullified versions of BlockClass and \InlineClass are provided for the print version, so they may be used in the document without placing them inside warpHTML or \warpHTMLonly.

7.9 Selecting the operating system

Prog Unix
Prog Mac OS
Prog Linux

lwarp tries to detect which operating system is being used. UNIX / MAC OS / LINUX is the default (collectively referred to as "UNIX" in the configuration files), and MS-WINDOWS is supported as well.

Prog MS-Windows
Prog Windows

If MS-WINDOWS is not correctly detected, use the lwarp option OSWindows.

Opt OSWindows

When detected or specified, the operating-system path separator used by lwarp is modified, and the boolean usingOSWindows is set true. This boolean may be tested by the user for later use.

7.10 Selecting actions for print, HTML, or MATHJAX output

The following environments and macros are used to select actions which only apply to either traditional LaTeX print-formatted PDF generation, or to HTML generation, or to HTML with MATHJAX.

For most of built-in LaTeX and many additional packages there is user-level source code support or emulation, so no special handling will be required. For those cases which lwarp does not handle by itself, the following environments and macros may be used to isolate sections of code for print-only or HTML-only.

These environments are also useful for creating a special version of the titlepage for print and another for HTML.

Env warpHTML

Anything which is to be done only for HTML5 output is surrounded by a warpHTML environment:

```
\begin{warpHTML}
 ... something to be done only during \HTML\ generation
\end{warpHTML}
```

⚠ `\end{warpHTML}` ⚠ nesting

Do *not* place anything else on the same line as `\end{warpHTML}`. The exact phrase is used to mark the end of the environment. Do not nest `warpHTML` inside itself. `warpMathJax` may be used inside `warpHTML`.

Env `warpprint`

Anything which is to be done only for print output is surrounded by a `warpprint` environment:

```
\begin{warpprint}
 ... something to be done only during traditional \PDF\ generation
\end{warpprint}
```

⚠ `\end{warpprint}` ⚠ nesting

As above, do not place anything else on the line with `\end{warpprint}`. Do not nest `warpprint` inside itself.

Env `warpall`

Anything which is to be done for any output may be surrounded by a `warpall` environment. Doing so is optional.

```
\begin{warpall}
 ... something to be done during print \PDF\ or \HTML\ output
\end{warpall}
```

⚠ `\end{warpall}` ⚠ nesting

As above, do not place anything else on the line with `\end{warpall}`. Do not nest `warpall` inside itself.

Macros are also provided for print-only or HTML-only code:

`\warpprintonly` {⟨*actions*⟩}

Performs the given actions only when print output is being generated.

`\warpHTMLonly` {⟨*actions*⟩}

Performs the given actions only when HTML output is being generated.

Env `warpMathJax`

⚠ `\end{warpMathJax}` ⚠ nesting

Anything which is to be done only while using HTML output with MathJax is surrounded by a `warpMathJax` environment. Usually, this is `\CustomizeMathJax`, used to add emulation macros. `\end{warpMathJax}` must appear on its own line. Do not nest `warpMathJax` inside itself. `warpMathJax` may be used inside `warpHTML`.

7.11 Commands to be placed into the `warpprint` environment

Certain print-related commands should always be placed inside a `warpprint` environment, or may need other special handling. These are unrelated to HTML output, but are hard to isolate automatically. For example:

- Paragraph formatting: `\parindent` `\parskip`
- Manual page positions such as the textpos package, which is emulated but only in a limited way.
- Anything changing the page counter. lwarp requires that the page counter not be adjusted during HTML output.

Some packages require additional setup commands. Where these packages are emulated for HTML, setup commands may work for the emulated HTML output as well as for print output. See the details for each package in this document for more information.

Also see section 13: Troubleshooting.

7.12 Title page

In the preamble, place an additional block of code to set the following:

```
\title{Document Title} % One line only
\author{Author One\affiliation{Affiliation One} \and
    Author Two\affiliation{Affiliation Two} }
\date{Optional date}
```

The title is used in the meta tags in the HTML files, unless overridden by `\HTMLTitle`, and the rest are used in `\maketitle`. To use a `\subtitle` or `\published` field, see section 69.8.

`\maketitle` Use `\maketitle` just after the `\begin{document}`, as this will establish the title of the homepage. Optionally, use a `titlepage` environment instead.

Env `titlepage` The `titlepage` environment may be used to hold a custom title page. The titlepage will be set in a `<div>` class `titlepage`, and `\printtitle`, etc. may be used inside this environment.

Env `titlingpage` Another form of custom title page, where `\maketitle` is allowed, and additional information may be included as well.

`\title` {⟨*title*⟩}

⚠ HTML corrupted ⚠ newlines Avoid newlines in the `\title`; these will interfere with the file break and CSS detection. Use a `\subtitle` command instead (section 69.8). The title will appear in the document `\maketitle` as a heading `<h1>`. The HTML meta `title` tag will also have this title, unless `\HTMLTitle` is used to set the meta title to something else instead.

`\author` {⟨*author*⟩}

In `\author`, `\protect` may be needed before some formatting commands. In HTML, the author will appear in a `<div>` of class `author` in the `\maketitle`. If the titling package is used, the author will also appear in a HTML meta tag, but `\HTMLAuthor` may be necessary to create a plain list of names if `\author` had affiliations added. `\affiliation` is a new addition to lwarp.

`\date` {⟨*date*⟩}

\date works as expected. In HTML, this will appear in a class titledate.

\thanks {⟨*text*⟩}

\thanks are allowed in the titlepage fields, and will be rendered as HTML notes at the bottom of the title page.

7.13 HTML page meta descriptions

\HTMLDescription {⟨*A description of the web page.*⟩}
Default: (none)

limitations Each page of HTML output should have its own HTML meta description, which usually shows up in web search results, is limited to around 150 characters in length, and should not include the ASCII double quote character (").

placement Use \HTMLDescription just before \begin{document} to set the description of the home page, and also just before each sectioning command such as \chapter or \section where a new file will be generated, depending on FileDepth. For example, if FileDepth is 1, use \HTMLDescription just before each \section command, and that description will be placed inside the HTML page for that \section. The same descrition will be used for all following HTML files as well, until reset by a new \HTMLDescription. It is best to use a unique description for each HTML file.

disabling To disable the generation of HTML description meta tags, use:

```
\HTMLDescription{}
```

7.14 HTML homepage meta title

\HTMLTitle {⟨*title*⟩}
Default: \HTMLtitle{\thetitle}

Sets the contents of the web page <meta name="title"> element. May be set empty to cancel the meta title tag.

See section 7.6 for \HTMLTitleBeforeSection and \HTMLTitleAfterSection, used to set the title for HTML subpages.

7.15 HTML page meta author

\HTMLAuthor {⟨*author*⟩}
Default: \HTMLAuthor{\theauthor}

Sets the contents of the web page <meta name="author"> element. May be set empty to cancel the meta author tag.

\author may be used to create a list of authors and their affiliations, in several formats if using authblk, and these may not successfully parse properly into a sensible list for \theauthor. \HTMLAuthor may be used to set the meta tag to a simple list of names.

8 Special cases and limitations

Some commonly-used LaTeX expressions should be modified as follows to allow for a smooth conversion to both HTML and print-formatted outputs.

Need help?

See the General Index for "how-to", and the Troubleshooting Index if something doesn't work. A Troubleshooting section is also available. The Index of Objects contains automated entries for each package, macro, environment, counter, boolean, and other objects; individually and also sorted by category.

8.1 Things to avoid

In the document, avoid the following:

⚠ options with braces

Package options: Package options may cause problems with lwarp, especially if they include curley braces.

If selecting options with braces in `\usepackage` does not work:

```
\usepackage[font={it,small}]{caption}% does not work
```

... try instead selecting the package options before loading lwarp:

```
\PassOptionsToPackage{font={it,small}}{caption}
...
\usepackage{lwarp}
...
\usepackage{caption}
```

... or try setting package options after the package has been loaded:

```
\usepackage{caption}
\captionsetup{font={it,small}}
```

page counter: Do not adjust the page counter. If doing so is required for the print version, place the adjustment inside a `warpprint` environment.

Custom math environment macros: Do not use expressions such as `\beq` as a replacement for `\begin{equation}`.

Custom macros in section, figure, table names: Custom macros which appear in sectioning commands or float captions then appear in the `.toc`, `.lof`, and `.lot` lists, and should be made robust using `\newrobustcmd` or `\robustify` from etoolbox, xparse, etc.

When setting `FileSectionNames` to `true` to name the HTML files from the section names, the file names are created from sanitized versions of the chapter or section names, but the section names must be plain text or something which expands into plain text. Robust macros will not work at the sectioning level which is used for file names, but a robust macro or other complicated name may be used for the manditory argument of `\chapter`, `\section`, etc., if a plain-text version is also included in the optional argument:

```
\chapter[Plain Name]{\ARobustMacro{Fancy Name}}
```

8.1.1 Invalid HTML

Additionally, some objects are valid LaTeX, but invalid HTML. An example is a tabular inside `\textbf`, since HTML does not allow a table inside a span. lwarp will create the table, and the browser may support it, but the result is technically invalid.

8.2 Formatting

8.2.1 Text formatting

⚠ `\bfseries`, etc. `\textbf`, etc. are supported, but `\bfseries`, etc. work only in some situations.

⚠ HTML special chars &, <, and > have special meanings in HTML. If `\&`, `\textless`, and `\textgreater` are used, proper HTML entities will be used, but there may be HTML parsing problems if these special characters occur unescaped in program listings or other verbatim text.

program listings For program listings, the listings package is supported, and its `literate` option is used to convert &, <, and > to proper HTML entities.

verbatim The various `verbatim`-related environments do not convert &, <, and >, so care must be taken to avoid accidentally including valid HTML code inside these environments. Adding a space on either side may be sufficient.

8.2.2 Small caps

`Bool FixSmallCaps` Some fonts, such as erewhon, utopia, or fbb, and some packages such as embrac, copy/paste "Small Caps" as all caps ("SMALL CAPS"), which lwarp then reads as all caps, so the text is printed in all caps. If small caps are being rendered as all caps, set:

```
\booltrue{FixSmallCaps}
```

⚠ CJK fonts Some CJK fonts may not work if `FixSmallCaps` is set `true`.

8.2.3 Horizontal and vertical space and rules

`\hspace` `\hspace` is converted to an inline HTML span of the given width, except that `0` width is ignored, a width of `.16667em` is converted to an HTML thin breakable space (`U+2009`), and a `\fill` is converted to a `\qquad`.

`\vspace` `\vspace` is ignored for HTML.

`~` `\,` ~ and `\,` are converted to HTML entities.

`\kern` `\hskip` `\kern` and `\hskip` are entered into the HTML PDF output as-is, then interpreted by *pdftotext*, and thus usually appear as a single space.

`\rule` `\rule` is converted to an HTML rule of the same dimensions, of the currently selected text color.

\hrule
\vrule

Both \hrule and \vrule are ignored for HTML. To create a horizontal dividing rule across the page, use \hrulefill in its own paragraph.

\hrulefill

\hrulefill usually creates a one-inch rule, similar to a "fill in the blank". If it is used at the start of a new paragraph, it creates a with a thin horizontal border across the page, as would often be done with \hrule.

8.2.4 Text alignment

Use the environments center, flushright, flushleft instead of the macros \centering, \raggedright, \raggedleft.

⚠ figure & table alignment

\centering, etc. are honored in a figure or table if they are the first command inside the float:

```
\begin{table*}
\centering
\caption{A Table}
. . .
```

8.2.5 Accents

Native LaTeX accents such as \" will work, but many more kinds of accents are available when using Unicode-aware XeLaTeX and LuaLaTeX. If using accents in section names which will become file names, it is recommended to use the LaTeX accents such as \" and \v instead of Unicode accents. The LaTeX accents will have the accents stripped when creating the filenames, whereas the Unicode accents will appear in the file names, which may cause issues with some operating systems.

8.2.6 textcomp package

Pkg textcomp

Some textcomp symbols do not have Unicode equivalents, and thus are not supported.

⚠ missing symbols

Many textcomp symbols are not supported by many system/browser fonts. In the CSS try referencing fonts which are more complete, but expect to see gaps in coverage.

8.2.7 Superscripts and other non-math uses of math mode

Use ^{x} instead of ^{x}

8.2.8 Empty \item followed by a new line of text or a nested list:

lists

Use a trailing backslash: \item[label] \

8.2.9 Filenames and URLs in lists or footnotes

filename underscore

Escape underscores in the filenames:

```
\item[\href{file\_name.pdf}{text}]
```

8.2.10 relsize package

Pkg relsize

For HTML, only the inline macros are supported: `\textlarger`, `\textsmaller`, and `\textscale`. Each becomes an inline span of a modified `font-size`.

`\relsize`, `\larger`, `\smaller`, and `\relscale` are ignored.

While creating SVG math for HTML, the original definitions are temporarilty restored, and so should work as expected.

⚠ not small

The HTML browser's setting for minumum font size may limit how small the output will be displayed.

8.3 Boxes and minipages

8.3.1 Marginpars

`\marginpar` `[`⟨*left*⟩`]` `{`⟨*right*⟩`}` `\marginpar` may contains paragraphs, but in order to remain inline with the surrounding text lwarp nullifies block-related macros inside the `\marginpar`. Paragraph breaks are converted to `<br />` tags.

`\marginparBlock` `[`⟨*left*⟩`]` `{`⟨*right*⟩`}` To include block-related macros, use `\marginparBlock`, which takes the same arguments but creates a `<div>` instead of a `<span>`. A line break will occur in the text where the `\marginBlock` occurs.

8.3.2 Save Boxes

⚠ HTML corrupted

⚠ boxes

TEX boxes are placed inline and do not allow line breaks, so boxes with long contents may overflow the line during HTML conversion. lwarp uses methods which help avoid this problem.

⚠ `minipage`, `\parbox`

`\savebox` and related do not (yet) support `minipage` or `\parbox`.

8.3.3 Minipages

⚠ inline

A line of text with an inline `minipage` or `\parbox` will have the `minipage` or `\parbox` placed onto its own line, because a paragraph is a block element and cannot be made `inline-block`.

placement

`minipages` and `\parboxes` will be placed side-by-side in HTML unless you place a `\newline` between them.

side-by-side

Side-by-side minipages may be separated by \quad, \qquad, \enskip, \hspace, \hfill, or a \rule. When inside a center environment, the result is similar in print and HTML. Paragraph tags are suppressed between side-by-side minipages and these spacing commands, but not at the start or end of the paragraph.

⚠ minipage in a span

There is limited support for minipages inside an HTML . An HTML cannot appear inside a . While in a , minipages, and \parboxes, and any enclosed lists have limited HTML tags, resulting in an "inline" format, without markup except for HTML breaks. Use \newline or \par for an HTML break.

⚠ minipage size

When using minipage, \parbox, and fminipage, a virtual 6 × 9 inch text area is used for \linewidth, \textwidth, and \textheight, both for sizing the minipage, and also for its contents.

if width is \linewidth

If a minipage or \parbox is assigned a width of exactly \linewidth, in HTML it is automatically given no HTML width, thus allowed to fill the line as needed, similar to how it appears in print output.

full-width if HTML

A new macro \minipagefullwidth requests that, during HTML output, the next single minipage or \parbox be generated without an HTML width attribute, allowing it to be the full width of the display rather than the declared print-output width. This may be useful where the printed version's width makes no sense in HTML.

⚠ tabular, multicols

\UseMinipageWidths
\IgnoreMinipageWidths

Inside a tabular or multicols environment, where the width depends on the browser window, \minipagefullwidth is effectively used by default for every minipage or \parbox inside the environment. \UseMinipageWidths may be used to tell lwarp to honor the specified widths of all following minipages and \parboxes until the end of the local scope, and \IgnoreMinipageWidths may be used to tell lwarp to ignore the specified widths.

⚠ multicol

Inside a multicols, \linewidth is divided by the specified number of columns.

⚠ text alignment

Nested minipages adopt their parent's text alignment in HTML, whereas in regular LaTeX PDF output they do not. Use a flushleft or similar environment in the child minipage to force a text alignment.

8.3.4 Side-by-side minipages

Place side-by-side minipages inside a center environment, with horizontal space between them, such as \quad, \qquad, \hspace, or \hfill. The result is similar in print and HTML. Do not use space commands at the start or end of the line.

8.3.5 Framed minipages and other environments

\fbox can only be used around inline items during HTML output, but HTML cannot place a block element such as a for a minipage or a list inside of a . Several options are provided for framing an object, depending on which kind of object and which packages are loaded:

\fbox
\fboxBlock
Env fminipage

For a framed object, options include:

To remove the frame in HTML output: Place the `\fbox` command and its closing brace inside `warpprint` environments. This will nullify the frame for HTML output.

For inline text:

To frame the contents inline with some formatting losses in HTML: This is the default action of `\fbox` when enclosing a minipage. During HTML output, `\fbox` nullifies the HTML tags for `minipage`, `\parbox`, and lists. The contents are included as inline text inside the `\fbox`'s `<span>` of class `framebox`. For lists, line breaks are converted to HTML breaks. The result is a plain-text inline version of the contents, framed inline with the surrounding text, but lacking any extra HTML markup.

For inline `minipage` and lists:

To frame the contents on their own line with improved formatting in HTML: A new command `\fboxBlock` is included, intended to be a direct replacement for `\fbox` for cases where the `\fbox` surrounds a minipage, table, or list. For print output, this behaves as `\fbox`. For HTML output, the contents are placed inside an HTML `<div>` with the class `framed`, resulting in the contents being placed on their own line with a frame surrounding them. The contents preserve their HTML formatting, so lists and minipages look nicer, and valid HTML is created for a `tabular`. While an `\fbox` containing a `tabular` is valid LaTeX code, the result in HTML is problematic since a table is a `<div>` not a `<span>`, so use `\fboxBlock` around a `tabular`, or else place the `tabular` inside a `minipage`, or use `fminipage`, described next. Also see below regarding the "Misplaced alignment tab character &." error.

For display `tabular`, minipages, and lists:

To create a framed minipage in both print and HTML: A new environment `fminipage` is included. For print output, this is identical to `minipage`, except that it is also framed. For HTML output, this forms a `<div>` of class `framed`, the contents preserve their HTML formatting, and valid HTML is created for a `tabular`. Also see section 89 for a new environment `fcolorminipage`. Also see below regarding the "Misplaced alignment tab character &." error.

colored boxes and frames:

To create colored frames and boxes: See section 661 for xcolor's `\colorbox` and `\fcolorbox`, and lwarp's additional `\colorboxBlock` and `\fcolorboxBlock`.

⚠ Misplaced alignment tab character &

To frame tables or verbatim environments: Place the contents inside a `fminipage`, or perhaps a `\fboxBlock` for a `tabular`. Also, if using `\fboxblock` with `tabular`, you will have to use `\StartDefiningTabulars` before the start of the macro which uses `\fboxBlock` and the `tabular`, and `\StopDefiningTabulars` afterwards. Also see the lwarp documentation for the fancybox package.

To frame equations: See section 257 for the fancybox package.

For fancy framed minipages: See packages boxedminipage, shadow, fancybox, framed, mdframed.

Custom environments: Use a custom environment to create a sidebar, containing a `BlockClass` environment with custom CSS formatting, and `\warpprintonly{\hrule}` command:

```
\begin{BlockClass}{frameminipage}% ignored in print output
  % use \CSS\ to format div class framedminipage
\warpprintonly{\hrule} % only appears in print output
Contents
\warpprintonly{\hrule} % only appears in print output
\end{BlockClass}
```

8.3.6 fancybox package

Pkg fancybox

framed equation example

fancybox's documentation has an example FramedEqn environment which combines math, \Sbox, a minipage, and an \fbox. This combination requires that the entire environment be enclosed inside a lateximage, which is done by adding \lateximage at the very start of FramedEqn's beginning code, and \endlateximage at the very end of the ending code. Unfortunately, the HTML alt attribute is not used here.

```
\newenvironmentFramedEqn
{
\lateximage% NEW
\setlength{\fboxsep}{15pt}
. . . }{. . .
\[\fbox{\TheSbox}\]
\endlateximage% NEW
}
```

framing alternatives

\fbox works with fancybox. Also see lwarp's \fboxBlock macro and fminipage environment for alternatives to \fbox for framing environments.

framed table example

The fancybox documentation's example of a framed table using an \fbox containing a tabular does not work with lwarp, but the FramedTable environment does work if \fbox is replaced by \fboxBlock. This method does lose some HTML formatting. A better method is to enclose the table's contents inside a fminipage environment. The caption may be placed either inside or outside the fminipage:

```
\begin{table}
\begin{fminipage}{\linewidth}
\begin{tabular}{lr}
. . .
\end{tabular}
\end{fminipage}
\end{table}
```

⚠ framed verbatim

lwarp does not support the verbatim environment inside a span, box, or fancybox's \Sbox, but a verbatim may be placed inside a fminipage. The fancybox documentation's example FramedVerb may be defined as:

```
\newenvironment{FramedVerb}[1] % width
{
  \VerbatimEnvironment
  \fminipage{#1}
  \beginVerbatim
}{
  \endVerbatim
  \endfminipage
}
```

framed \VerbBox

fancybox's \VerbBox may be used inside \fbox.

indented alignment

LVerbatim, \LVerbatimInput, and \LUseVerbatim indent with horizontal space which may not line up exactly with what *pdftotext* detects. Some lines may be off slightly in their left edge.

8.3.7 mdframed package

Pkg mdframed

support Most basic functionality is supported, including frame background colors and single-border colors and thickness, title and subtitle background colors and borders and thickness, border radius, and shadow. CSS classes are created for mdframed environments and frame titles.

⚠ loading When used, lwarp loads mdframed in HTML with `framemethod=none`.

font For title font, use

```
frametitlefont=\textbf,
```

instead of

```
frametitlefont=\bfseries,
```

where `\textbf` must appear just before the comma and will receive the following text as its argument (since the text happens to be between braces in the mdframed source). Since lwarp does not support `\bfseries` and friends, only one font selection may be made at a time.

theoremtitlefont `theoremtitlefont` is not supported, since the following text is not in braces in the mdframed source.

ignored options `userdefinedwidth` and `align` are currently ignored.

css classes Environments created or encapsulated by mdframed are enclosed in a `<div>` of class `mdframed`, and also class `md<environmentname>` for new environments.

Frame titles are placed in a `<div>` of class |mdframedtitle|. Subtitles are in a `<div>` of class |mdframedsubtitle|, and likewise for subsubtitles.

8.3.8 tcolorbox package

Pkg tcolorbox

tcolorbox is emulated for HTML and MathJax, and supported as-is inside a `lateximage` or SVG math.

What has been tested to work (at least partly) includes:

- `tcolorbox`, `\tcbox`.
- Title, subtitle.
- Upper, lower parts.
- Colors and title fonts.
- Floating objects.
- Some layered box features.
- Counters, labels, references.
- listings, listingsutf8.
- `theorems`: Theorems are supported. `math`, `ams equation`, etc. are not supported. Use a `tcolorbox` with regular math inside it. `\tcboxmath` and `\tcbhighmath` are suppored in SVG math, and emulated in MathJax.

⚠ math

- Fitting features: `\tcboxfit` becomes `\tcbox` in HTML.

⚠ footnotes

- Footnote numbering does not match the printed output.
- MathJax emulation is provided for common macros.

⚠ undefined references

If using cleveref, it may be necessary to name theorems such as:

```
\crefname{tcb@cnt@mytheo}{my theorem}{my theorems}
```

8.4 Section names

If using named HTML files, by selecting `\booltrue{FileSectionNames}`, the generated filenames may be simplified by using `\FilenameSimplify` and `\FilenameNullify`:

`\FilenameSimplify` `{`⟨*text*⟩`}`

To remove common short words from the automatically-generated filenames, replacing each with a single hyphen "-", use `\FilenameSimplify`:

```
\FilenameSimplify*{-in-}
\FilenameSimplify*{A-}
```

The first example removes the word "in" in the middle of a filename, and the second example removes "A" at the start of the filename. The star forces the arguments to be detokenized, which is required for a plain-text comparison. (The unstarred form is used for a token-sensitive comparison, which is seldom required by the user.) After simplfication, repeated hyphen characters will be further simplified to a single hyphen "-". Finally, single hyphens at the start or end of the filename are removed.

`\FilenameNullify` `{`⟨*macros*⟩`}`

⚠ macros in section names

Macro names may appear in the automatically-generated file names. To remove these, create *non-robust* nullified versions of the macros, ensuring that each line ends with a percent character `%` as shown below. These are placed inside `\FilenameNullify`, which adds them to the list of macros which are nullfiied during filename generation. Low-level macros such as `\begingroup` will cause problems when nullfied. Many macros such as `\textbf` are already nullfied. lwarp also already nullifies built-in symbol and textcomp macros, including if defined by xunicode, but not all xunicode macros. See the definition of `\LWR@nullfonts` for a complete list.

```
\FilenameNullify{%
  \renewcommand*{\macroname}[1]{#1}%
  \renewcommand*{\anothermacro}{}%
}
```

⚠ duplicate filename

Avoid duplicate file names. Section names at levels which result in HTML file splits must be unique. lwarp will generate an error if a duplicate HTML filename is generated. Use the optional TOC caption entry parameter for formatting. Remember to `\protect` LaTeX commands which appear in section names and TOC captions.

⚠ math in section names

If using named HTML files, in section names use paren math `\(x+y\)` instead of dollar math `$x+y$`. (Dollar math works, but appears in the filename.) Or, use a short name for the TOC entry without the math, or use `\texorpdfstring` from the hyperref package:

```
\section{Some math \texorpdfstring{$1+2=3$}{three}}
```

8.5 Cross-references

labels
⚠ label characters

Labels with special characters may be a problem. It is best to stick with alpha-numeric, hyphen, underscore, and perhaps the colon (if not French).

\nameref
⚠ empty link

`\nameref` refers to the most recently-used section where the `\label` was defined. If no section has been defined before the `\label`, the link will be empty. Index entries also use `\nameref` and have the same limitation.

8.5.1 Page references

⚠ LaTeX page numbers

The printed page does not translate to the HTML page, so `\pageref` references are converted to parentheses containing `\pagerefPageFor`, which defaults to "see ", followed by a hyperlink to the appropriate object.

Ex:

```
\ref{sec:name} on page \pageref{sec:name}
```

in HTML becomes:

"Sec. 1.23 on page (**see** sec. 1.23)".

`\pagerefPageFor` may be redefined to "page for ", empty, etc. See page 515.

8.5.2 cleveref and varioref packages

Pkg cleveref
Pkg varioref
⚠ cleveref page numbers

cleveref and varioref are supported, but printed page numbers do not map to HTML, so a section name or a text phrase are used for `\cpageref` and `\cpagerefrange`. This phrase includes `\cpagerefFor`, which defaults to "for".

Ex:

```
\cpageref{tab:first,tab:second}
```

in html becomes:

"pages **for** table 4.1 and **for** table 4.2"

See `\cpagerefFor` at page 748 to redefine the message which is printed for page number references.

⚠ varioref types

cleveref changes the behavior of varioref in that the reference type is automatically printed if cleveref is loaded. Lwarp requires cleveref, so the HTML version will always automatically print the reference types even if the print mode does not. The simplest way to make them match is to require the cleveref package for the document.

8.5.3 Hyperlinks, hyperref, and url

Pkg hyperref
Pkg url

lwarp emulates hyperref, including the creation of active hyperlinks, but does not require that hyperref be loaded by the document.

⚠ comments between arguments

Do not place a comment with a `%` character between arguments for `\hyperref`, etc., as it is neutralized for inclusion in HTML URLs.

lwarp can also load url, but url should not be used at the same time as hyperref, since they both define the `\url` command. lwarp does not (yet) attempt to convert url links into hyperlinks during HTML output, nor does the print version of url create hyperlinks.

⚠ backref When generating HTML, lwarp's emulation of hyperref does not automatically load backref, so backref must be loaded explicitly.

8.5.4 Footnotes, endnotes, and page notes

lwarp uses native LaTeX footnote code, although with its own `\box` to avoid the LaTeX output routine. The usual functions mostly work as-is.

footnote numbering To have footnote numbers reset each time footnotes are printed:

```
\setcounter{footnoteReset}{1}
```

For bigfoot, manyfoot, or perpage:

```
\MakePerPage{footnoteX}
— or —
\MakeSortedPerPage{footnoteX}
```

The footnotes are reset when they are printed, according to section level as set by `FootnoteDepth`, which is not necessarily by HTML page. This is recommended for `\alph`, `\Alph`, or `\fnsymbol` footnotes, due to the limited number of symbols which are available.

MathJax Also for MathJax, `\footnotename` is used for a `\footnotemark` if the actual footnote number is not known. To redefine it, provide it before loading lwarp:

```
\providecommand{\footnotename}{something}
\usepackage{lwarp}
```

Similar for sidenotes. For endnotes:

```
\def\endnotename{something}% \def allows name to start with "end"
```

For the pagenote package, there is no `\pagenotename` to define, since there is no `\pagenotemark` command.

footmisc The footmisc `stable` option is emulated by lwarp.

⚠ sectioning commands When using footnotes in sectioning commands, to generate consistent results between print and HTML, use the footmisc package with the `stable` option, provide a short TOC entry, and `\protect` the `\footnote`:

```
\usepackage[stable]{footmisc}
. . .
\subsection[Subsection Name]
    {Subsection Name\protect\footnote{A footnote.}}
```

memoir with footmisc ⚠ memoir If using memoir class, with which lwarp preloads footmisc, the `stable` option must be declared before lwarp is loaded:

```
\PassOptionsToPackage{stable}{footmisc}
\usepackage{lwarp}
. . .
```

Do not use a starred sectioning command. As an alternative, it may be possible to adjust `\secnumdepth` instead.

fancybox, fancyvrb
⚠ `\VerbatimFootnotes`
⚠ sectioning or displaymath

If using fancybox or fancyvrb with `\VerbatimFootnotes`, and using footnotes in a sectioning command or display math, use `\footnotemark` and `\footnotetext`:

```
\subsection[Subsection Name]
    {Subsection Name\protect\footnotemark}
\footnotetext{A footnote with \verb+verbtim+.}
```

and likewise for equations or display math.

At present there is a bug such that paragraph closing tags are not present in footnotes when `\VerbatimFootnotes` are selected. The browser usually compensates.

pfnote
⚠ pfnote numbers

While emulating pfnote, lwarp is not able to reset HTML footnote numbers per page number to match the printed version, as HTML has no concept of page numbers. lwarp therefore uses continuous footnote numbering even for pfnote.

bigfoot, manyfoot
⚠ verbatim

Verbatim footnotes are not yet supported.

If using the bigfoot package, and possibly also manyfoot, problems may occur with counter allocation because lwarp uses many counters, and there is a difference in how counters numbered 256 and up are handled in pdfLaTeX. With bigfoot this has been known to show up as an error related to one footnote insert being forbidden inside another. Another problem showed up as a input stack error, and which of these problems occurred depended on how many counters were allocated.

As a possible solution, try creating several new counters before defining bigfoot or manyfoot footnotes, hoping to shift the problematic counter above the 256 threshold. It may instead be necessary to use XeLaTeX or LuaLaTeX instead of pdfLaTeX.

8.5.5 xr, xr-hyper, and xcite packages

See section 5.17.

8.6 Front and back matter

8.6.1 Custom classes with multiple authors and affiliations

Some classes allow multiple authors and affiliations. Often it is possible to emulate these using a standard class along with authblk:

```
%\documentclass{customclass} % for print document
\documentclass{article} % for html document

\usepackage{lwarp}
\begin{warpHTML}
\usepackage{authblk}
\let\affiliation\affil % maybe required
\end{warpHTML}
```

8.6.2 Starred chapters and sections

HTML page and TOC

The following describes \ForceHTMLPage and \ForceHTMLTOC, which may be used for endnotes, glossaries, tocbibind, bibliographies, and the index. See the following sections where applicable. Continue here if interested in the reason for adding these commands to lwarp.

Some packages use \chapter* or \section* to introduce reference material such as notes or lists, often to be placed in the back matter of a book. These starred sections are placed inline instead of on their own HTML pages, and they are not given TOC entries.

lwarp provides a method to cause a starred section to be on its own HTML page, subject to FileDepth, and also a method to cause the starred section to have its own TOC entry during HTML output.

\ForceHTMLPage

To place a starred section on its own HTML page, use \ForceHTMLPage just before the \chapter* or \section*. lwarp will create a new page for the starred sectional unit.

A starred sectional unit does not have a TOC entry unless one is placed manually. The typical method using \phantomsection and \addcontentsline works for inline text but fails when the new starred section is given its own webpage after the TOC entry is created, or when creating an EPUB where the TOC entry will point to the page before the starred section. If the starred section has its own HTML page but no correct TOC entry pointing to that page, the page will be inaccessible unless some other link is created.

⚠ inaccessible HTML page

\ForceHTMLTOC

To automatically force the HTML version of the document to have a TOC entry for a starred section, use \ForceHTMLTOC just before the \chapter* or \section*, and place \phantomsection and \addcontentsline inside a warpprint environment.

For print output, \ForceHTMLTOC and \ForceHTMLPage have no effect.

8.6.3 abstract package

Pkg abstract

⚠ missing TOC

If using the number option with file splits, be sure to place the table of contents before the abstract. The number option causes a section break which may cause a file split, which would put a table of contents out of the home page if it is after the abstract.

8.6.4 titling and authblk

Pkg titling

Pkg authblk

package support

⚠ load order

\published and \subtitle

lwarp supports the native LaTeX titling commands, and also supports the packages authblk and titling. If both are used, authblk should be loaded before titling.

If using the titling package, additional titlepage fields for \published and \subtitle may be added by using \AddSubtitlePublished in the preamble. See section 69.8.

8.6.5 tocloft package

Opt [tocloft] titles

Pkg tocloft

Pkg tocloft

⚠ tocloft & other packages

If using tocloft with tocbibind, anonchap, fncychap, or other packages which change

chapter title formatting, load tocloft with its `titles` option, which tells tocloft to use standard LaTeX commands to create the titles, allowing other packages to work with it.

8.6.6 appendix package

Pkg appendix

⚠ incorrect TOC link

During HTML conversion, the option `toc` without the option `page` results in a TOC link to whichever section was before the `appendices` environment. It is recommended to use both `toc` and also `page` at the same time.

8.6.7 pagenote package

Pkg pagenote

pagenote works as-is, but the page option is disabled.

⚠ labels

Note that labels in page notes do not appear as expected, even in the print version.

8.6.8 endnotes package

Pkg endnotes

table of contents

To place the endnotes in the TOC, use:

```
\usepackage{endnotes}
\appto\enoteheading{\addcontentsline{toc}{section}{\notesname}}
\renewcommand*{\notesname}{Endnotes} % optional
```

HTML page

To additionally have the endnotes on their own HTML page, if `FileDepth` allows:

```
\ForceHTMLPage
\theendnotes
```

⚠ `\endnotemark` numbering

If using MathJax, see section 8.5.4 regarding the use of `\endnotemark` and `\endnotetext`.

8.6.9 *BibTeX*

`\etalchar`

Displays a superscript "+" to indicate "and others".

⚠ Modify *.bib

When enough authors are cited for a source, BibTeX may use the `\etalchar` command to display a math superscript with a + character to indicate "and others". Without modification, this will result in an "Improper `\prevdepth`" error. At present, lwarp requires that `\etalchar` be replaced by a text superscript. To do so, add to the start of the `.bib` file the following:

```
@PREAMBLE{"\let\etalchar\relax \newcommand{\etalchar}[1]{\textsuperscript{#1}}"}
```

8.6.10 xcite package

See section 5.17.

8.6.11 gloss package

Pkg gloss

⚠ compiling

To process the HTML glossary:

```
bibtex <projectname>_html.gls
```

8.6.12 glossaries package

Pkg glossaries

processing glossaries

Opt GlossaryCmd

Default: makeglossaries

Opt [lwarpmk] printglossary

Opt [lwarpmk] htmlglossary

⚠ *makeglossaries* not found

lwarpmk has the commands **lwarpmk printglossary** and **lwarpmk htmlglossary**, which process the glossaries created by the glossaries package using that package's *makeglossaries* program.

The shell command to execute is set by the lwarp option GlossaryCmd, which defaults to **makeglossaries**. The print or HTML glossary filename is appended to this command.

In some situations it may be required to modify the default command, such as to add the **perl** command in front:

```
\usepackage[
   GlossaryCmd={perl makeglossaries},
] {lwarp}
```

xindy language

To set the language to use for processing glossaries with *xindy*:

```
\usepackage[
   GlossaryCmd={makeglossaries -L english},
] {lwarp}
```

Other options for *makeglossaries* may be set as well.

placement and TOC options

The glossaries may be placed in a numbered or unnumbered section, given a TOC entry, and placed inline or on their own HTML page:

Numbered section, on its own HTML page:

```
\usepackage[xindy,toc,numberedsection=nolabel]{glossaries}
. . .
\printglossaries
```

Unnumbered section, inline with the current HTML page:

```
\usepackage[xindy,toc]{glossaries}
. . .
\printglossaries
```

Unnumbered section, on its own HTML page:

```
\usepackage[xindy,toc]{glossaries}
. . .
\ForceHTMLPage
\printglossaries
```

⚠ glossary style

The default style=item option for glossaries conflicts with lwarp, so the style is forced to index instead.

⚠ number list

The page number list in the printed form would become \namerefs in HTML, which could

become a very long string if many items are referenced. For now, the number list is simply turned off.

print/HTML versions

The print and HTML versions of the glossary differ in their internal page numbers. Separate commands for generating print and HTML glossaries are used, even though the page number is currently ignored.

8.6.13 nomencl package

Pkg nomencl

To process the HTML nomenclature:

```
makeindex <project>_html.nlo -s nomencl.ist -o <project>_html.nls
```

8.6.14 Indexing overview

There are many ways to process indexes for a LaTeX document, including native LaTeX capabilities, a number of packages and classes, the possible availability of shell escape and *latexmk*, and the need to process print and HTML versions. lwarp attempts to provide easy recompilation of indexes along with the rest of the document, but the various indexing options must be set correctly. Numerous examples are given below. Some differ in minor details, so the important parts are highlighted in red, and options are in green.

Once set up properly, the entire document may be recompiled with **`lwarpmk print`** and **`lwarpmk html`**. In some cases, it will also be necessary to compile the indexes with **`lwarpmk printindex`** and **`lwarpmk htmlindex`**. A recompile may then be forced with **`lwarpmk print1`** and **`lwarpmk html1`**.

manual processing

The user may continue to process indexes manually or by shell script without the use of *lwarpmk*, but adjustments will be required to process HTML indexes as well. In general, `*.idx` and `*.ind` files will be accompanied by `*_html.idx` and `*_html.ind` files.

custom index style

If using a custom indexing style file, see sections 8.6.20 to 8.6.22.

link appearance

To control how the index links appear in the HTML output, see the `IndexRef` option in section 7.5, page 109.

source code

See section 79 for lwarp's core index and glossary code, section 338 for index, section 563 for splitidx, section 336 for imakeidx, section 616 for tocbibind, and section 682.17 for memoir's indexing patches.

8.6.15 Indexing with makeidx, *makeindex*, *xindy*, *xindex*, gindex

lwarpmk processing

The following allow the user to process indexes automatically, or using *lwarpmk*'s commands:

Enter ⇒ **`lwarpmk printindex`**

Enter ⇒ **`lwarpmk htmlindex`**

Prog makeindex **For a single index using *makeindex*:**

```
\usepackage[makeindex,latexmk] {lwarp}
```

The usual `.idx` and `.ind` files will be used, along with the new `lwarp.ist` style file. When creating the HTML index, "`_html`" is automatically appended to each of the names.

lwarpmk will use *latexmk* if specified, in which case *latexmk* will create the index automatically. Otherwise, use

Enter ⇒ **`lwarpmk printindex`**

Enter ⇒ **`lwarpmk htmlindex`**

to compile the indexes.

To use a custom configuration file, see section 8.6.20.

Prog xindy **For a single index using *xindy*:**

```
\usepackage[
    xindy,
    xindyLanguage=english,                  <optional>
    xindyCodepage=utf8,                     <optional>
    latexmk                                 <optional>
]{lwarp}
```

The usual `.idx` and `.ind` files will be used, along with the new `lwarp.xdy` style file.

lwarpmk will use *latexmk* if specified, in which case *latexmk* will create the index automatically. Otherwise, use

Enter ⇒ **`lwarpmk printindex`**

Enter ⇒ **`lwarpmk htmlindex`**

to compile the indexes.

To use a custom configuration file, see section 8.6.21.

Prog xindex **For a single index using *xindex*:**

```
\usepackage[
    xindex,
    latexmk                                 <optional>
]{lwarp}
```

The usual `.idx` and `.ind` files will be used.

lwarpmk will use *latexmk* if specified, in which case *latexmk* will create the index automatically. Otherwise, use

Enter ⇒ **`lwarpmk printindex`**

Enter ⇒ **`lwarpmk htmlindex`**

to compile the indexes.

To use a custom configuration file, see section 8.6.22.

Pkg gindex **For a single index using gindex:**

```
\usepackage[
    makeindex,
    makeindexStyle=gindex.ist,
    . . . or . . .
    makeindexStyle=gindexh.ist,
    latexmk                                    <optional>
]{lwarp}
```

The usual `.idx` and `.ind` files will be used.

lwarpmk will use *latexmk* if specified, in which case *latexmk* will create the index automatically. Otherwise, use

Enter ⇒ **`lwarpmk printindex`**

Enter ⇒ **`lwarpmk htmlindex`**

to compile the indexes.

To use a custom configuration file, copy `gindex.ist` to a new file, modify, then specify it with `MakeindexStyle` as above. lwarp will automatically adapt to gindex's `\indexpagessep` and `\indexrangesep` settings.

8.6.16 Indexing with index

Prog index

lwarp is told how to use *makeindex* using the `PrintIndexCmd` and `HTMLIndexCmd` options. The file `lwarp.ist` is specified, which generates index letter heads for print output and also allows special HTML formatting for HTML output.

For multiple indexes using *makeindex* and index:

(Assuming that the second index has file extensions `.sist` and `.sind`)

```
\usepackage[
  makeindex, latexmk,
  PrintIndexCmd={
    makeindex -s lwarp.ist <projectname>.idx ;
    makeindex -s lwarp.ist
      -o <projectname>.sind <projectname>.sidx
  },
  HTMLIndexCmd={
    makeindex -s lwarp.ist <projectname>_html.idx ;
    makeindex -s lwarp.ist
      -o <projectname>_html.sind <projectname>_html.sidx
  }
]{lwarp}
\usepackage{index}
. . .
\makeindex
\newindex{secondname}{sidx}{sind}{Second Index}
```

⚠ Windows *For Windows, replace the two ";" characters with "&".*

When creating the HTML index, "`_html`" is automatically appended to the index filenames.

Use

Enter ⇒ **lwarpmk printindex**

Enter ⇒ **lwarpmk htmlindex**

to compile the indexes.

If the latexmk option is selected for lwarp, *latexmk* will compile the document but will *not* compile the indexes. **lwarpmk printindex** and **lwarpmk htmlindex** will still be required.

8.6.17 Indexing with splitidx

Prog splitidx

lwarp is told how to use *splitindex* using the PrintIndexCmd and HTMLIndexCmd options. The file lwarp.ist is specified, which generates index letter heads for print output and also allows special HTML formatting for HTML output.

If the latexmk option is selected for lwarp, *latexmk* will compile the document but will *not* compile the indexes. **lwarpmk printindex** and **lwarpmk htmlindex** will still be required.

⚠ \thepage When using \AtWriteToIndex or \AtNextWriteToIndex, the user must not refer to \thepage during HTML output, as the concept of a page number is meaningless. Instead, do

```
\addtocounter{LWR@autoindex}{1}
\LWR@new@label{LWRindex-\arabic{LWR@autoindex}}
```

where the \index-like action occurs, and then refer to \arabic{LWR@autoindex} instead of \thepage where the reference should occur.

See section 682.17 in the lwarp-patch-memoir package for the \@@wrspindexhyp macro as an example.

For multiple indexes using *makeindex* and splitidx:

```
\usepackage[
  makeindex, latexmk,
  PrintIndexCmd={
    splitindex <projectname> -- -s lwarp.ist
  },
  HTMLIndexCmd={
    splitindex <projectname>_html -- -s lwarp.ist
  }
]{lwarp}
\usepackage{splitidx}
. . .
\makeindex
\newindex[Second Index]{secondname}
```

When creating the HTML index, "_html" is automatically appended to each of the names.

Use

Enter ⇒ **lwarpmk printindex**

Enter ⇒ **lwarpmk htmlindex**

to compile the indexes.

For multiple indexes using *xindy* and splitidx:

```
\usepackage[
  xindy, latexmk,
  PrintIndexCmd={
    splitindex -m xindy <projectname> -- -M lwarp.xdy
      -L english -C utf8                          <optional>
  },
  HTMLIndexCmd={
    splitindex -m xindy <projectname>_html -- -M lwarp.xdy
      -L english -C utf8                          <optional>
  }
]{lwarp}
\usepackage{splitidx}
. . .
\makeindex
\newindex[Second Index]{secondname}
```

When creating the HTML index, "_html" is automatically appended to each of the names.

Use

Enter ⇒ **lwarpmk printindex**

Enter ⇒ **lwarpmk htmlindex**

to compile the indexes.

8.6.18 Indexing with imakeidx

Prog imakeidx

Due to the number of methods which may be used to process multiple indexes, the options for style file and *xindy* language and codepage must be specified in one of several different ways. These are described in detail later in this section, but are summarized here.

If shell escape is used, imakeidx will automatically compile the indexes by itself. Options specifying a custom style file and *xindy* language and codepage must be specified for each `\makeindex` command using its `options=` option, which must include lwarp's special `lwarp.ist` or `lwarp.xdy` file, or a file based on them. If using a custom indexing style file, see sections 8.6.20 to 8.6.22.

The `splitindex` option is also available of shell escape is used, in which case the splitidx package and *splitindex* program will also be used.

If shell escape is not possible, *latexmk* may be used to automatically compile the indexes. The style, language, and codepage options are specified with lwarp's `makeindexStyle`,

xindyStyle, xindyLanguage, and xindyCodepage options. These are passed to *latexmk* by *lwarpmk*'s **lwarpmk printindex** and **lwarpmk htmlindex** commands.

Where shell escape and *latexmk* are not possible, *lwarpmk* may be used to manually compile the indexes. lwarp's PrintIndexCmd and HTMLIndexCmd options are used.

For a single or multiple indexes using *makeindex* and imakeidx:

The index style lwarp.ist is automatically used for HTML output. This file turns on letter headings, so it may be desirable to specify it as an option, in which case it will also be used for print output, which will help match the print and HTML output.

```
\usepackage[makeindex,latexmk] {lwarp}
\usepackage[makeindex]{imakeidx}
. . .
\makeindex[options={-s lwarp.ist}]
\makeindex[name=secondname,options={-s lwarp.ist}]
```

imakeidx will automatically compile the indexes. Shell escape is not required while using *makeindex*. latexmk may be specified, and if so it will be used for **lwarpmk print** and **lwarpmk html**, but *imakeidx* will actually create the indexes.

For a single or multiple indexes using *makeindex* and *splitindex* with imakeidx:

The index style lwarp.ist is automatically used for HTML output. This file turns on letter headings, so it may be desirable to specify it as an option, in which case it will also be used for print output, which will help match the print and HTML output.

```
\usepackage[makeindex,latexmk] {lwarp}
\usepackage[makeindex,splitindex]{imakeidx}
. . .
\makeindex[options={-s lwarp.ist}]
\makeindex[name=secondname,options={-s lwarp.ist}]
```

⚠ enable shell escape

Shell escape is required while using *splitindex*. For the first compile, use

Enter ⇒ **pdflatex --shell-escape projectname.tex**

Enter ⇒ **pdflatex --enable-write18 projectname.tex** **(MiKTeX)**

or similar with *xelatex* or *lualatex*. lwarp will remember that shell escape was used.

imakeidx will automatically execute *splitindex*, and will also use *makeindex* to compile the indexes.

latexmk may be specified, and if so it will be used for **lwarpmk print** and **lwarpmk html**, but *imakeidx* will actually create the indexes.

For multiple indexes using *xindy* and imakeidx, using shell escape:

Options may be given to imakeidx's \makeindex command. The style file lwarp.xdy is automatically used for HTML output, and is not necessary for print output since the output will be similar. If language or codepage must be set, they should be specified as options for \makeindex, since imakeidx will process the indexes.

```
\usepackage[xindy,latexmk] {lwarp}
\usepackage[xindy,splitindex]{imakeidx}
. . .
\makeindex[
  options={ -M lwarp.xdy -L english -c utf8 }
]
\makeindex[
  name=secondname,
  options={ -M lwarp.xdy -L english -c utf8 }
]
```

⚠ enable shell escape

For the first compile, use

Enter ⇒ **pdflatex --shell-escape projectname.tex**

Enter ⇒ **pdflatex --enable-write18 projectname.tex** **(MiKTeX)**

or similar with *xelatex* or *lualatex*. lwarp will remember that shell escape was used.

imakeidx will automatically execute *splitindex* if selected, and will also use *xindy* to compile the indexes.

If selected, *latexmk* will automatically recompile the entire document as necessary.

For indexes using *xindy* and *imakeidx*, without shell escape, but *with latexmk*:

lwarp's options are used, and are passed to *latexmk*.

```
\usepackage[
  xindy,
  xindyLanguage=english,                    <optional>
  xindyCodepage=utf8,                       <optional>
  latexmk,
]{lwarp}
\usepackage[xindy]{imakeidx}
. . .
\makeindex
\makeindex[name=secondname]
```

latexmk will create the indexes automatically when **lwarpmk print** and **lwarpmk html** are executed.

For indexes using *xindy* and *imakeidx*, without shell escape, and *without latexmk*:

lwarpmk must be told how to create the indexes:

```
\usepackage[
  xindy,
  PrintIndexCmd={
    xindy -M lwarp.xdy -L english -C utf8
      <projectname>.idx ;
    xindy -M lwarp.xdy -L english -C utf8
      secondname.idx
  },
  HTMLIndexCmd={
    xindy -M lwarp.xdy -L english -C utf8
      <projectname>_html.idx ;
    xindy -M lwarp.xdy -L english -C utf8
      secondname_html.idx
  }
]{lwarp}
\usepackage[xindy]{imakeidx}
. . .
\makeindex
\makeindex[name=secondname]
```

⚠ Windows *For Windows, replace the two ";" characters with "&".*

`<projectname>` is the `\jobname`: if compiling "`name.tex`", use the filenames `name.idx` and `name_html.idx`.

Use

Enter ⇒ **`lwarpmk printindex`**

Enter ⇒ **`lwarpmk htmlindex`**

to compile the indexes.

For multiple indexes using *xindex* and imakeidx, using shell escape:

xindex, *makeindex*, *imakeidx*, and *splitindex* can all work together:

```
\usepackage[%
  xindex,
  xindexConfig=-imakeidx,
  latexmk
] {lwarp}
\usepackage[makeindex,splitindex]{imakeidx}
. . .
\makeindex[%
  options={ -s lwarp.ist} }
]
\makeindex[
  name=secondname,
  options={ -s lwarp.ist} }
]
```

⚠ enable shell escape For the first compile, use:

Enter ⇒ **pdflatex --shell-escape projectname.tex**

Enter ⇒ **pdflatex --enable-write18 projectname.tex** **(MiKTeX)**

or similar with *xelatex* or *lualatex*. lwarp will remember if shell escape was used.

xindex will use *imakeidx*, and *imakeidx* will automatically execute *splitindex* if selected.

If selected, *latexmk* will automatically recompile the entire document as necessary.

8.6.19 Indexes with memoir

For a single index with memoir and *makeindex*:

```
\documentclass{memoir}
\usepackage[makeindex,latexmk]{lwarp}
. . .
\makeindex
```

The usual `.idx` and `.ind` files will be used, along with the `lwarp.ist` style file.

lwarpmk will use *latexmk* if specified, in which case *latexmk* will create the index automatically. Otherwise, use

Enter ⇒ **lwarpmk printindex**

Enter ⇒ **lwarpmk htmlindex**

to compile the indexes.

For multiple indexes with memoir and *makeindex*, using *latexmk*:

lwarp's options are used, and are passed to *latexmk*.

```
\documentclass{memoir}
\usepackage[makeindex,latexmk]{lwarp}
. . .
\makeindex
\makeindex[secondname]
```

lwarpmk will use *latexmk* to create the indexes automatically when the user executes **lwarpmk print** and **lwarpmk html**.

For multiple indexes with memoir and *makeindex*, *without* latexmk:

lwarpmk must be told how to create the indexes:

```
\documentclass{memoir}
\usepackage[
  makeindex,
  PrintIndexCmd={
    makeindex -s lwarp.ist <projectname>.idx ;
    makeindex -s lwarp.ist secondname.idx
  },
  HTMLIndexCmd={
    makeindex -s lwarp.ist <projectname>_html.idx ;
    makeindex -s lwarp.ist secondname_html.idx
  }
]{lwarp}
. . .
\makeindex
\makeindex[secondname]
```

⚠ Windows *For Windows, replace the two ";" characters with "&".*

`<projectname>` is the `\jobname`: if compiling "`name.tex`", use the filenames `name.idx` and `name_html.idx`.

Use

Enter ⇒ **`lwarpmk printindex`**

Enter ⇒ **`lwarpmk htmlindex`**

to compile the indexes.

For a single index with memoir and *xindy*:

```
\documentclass{memoir}
\usepackage[
    xindy,
    xindyLanguage=english,                    <optional>
    xindyCodepage=utf8,                       <optional>
    latexmk                                   <optional>
]{lwarp}
. . .
\xindyindex
\makeindex
```

The usual `.idx` and `.ind` files will be used, along with the `lwarp.xdy` style file.

lwarpmk will use *latexmk* if specified, in which case *latexmk* will create the index automatically. Otherwise, use

Enter ⇒ **`lwarpmk printindex`**

Enter ⇒ **`lwarpmk htmlindex`**

to compile the indexes.

For multiple indexes with memoir and *xindy*, using latexmk:

lwarp's options are used, and are passed to *latexmk*.

```
\documentclass{memoir}
\usepackage[
    xindy,
    xindyLanguage=english,                    <optional>
    xindyCodepage=utf8,                       <optional>
    latexmk
]{lwarp}
. . .
\xindyindex
\makeindex
\makeindex[secondname]
```

lwarpmk will use *latexmk* to create the indexes automatically.

For multiple indexes with memoir and *xindy*, *without* latexmk:

lwarpmk must be told how to create the indexes:

```
\documentclass{memoir}
\usepackage[
  xindy,
  PrintIndexCmd={
    xindy -M lwarp.xdy -L english -C utf8
      <projectname>.idx ;
    xindy -M lwarp.xdy -L english -C utf8
      secondname.idx
  },
  HTMLIndexCmd={
    xindy -M lwarp.xdy -L english -C utf8
      <projectname>_html.idx ;
    xindy -M lwarp.xdy -L english -C utf8
      secondname_html.idx
  }
]{lwarp}
. . .
\xindyindex
\makeindex
\makeindex[secondname]
```

⚠ Windows *For Windows, replace the four ";" characters with "&".*

`<projectname>` is the `\jobname`: if compiling "`name.tex`", use the filenames `name.idx` and `name_html.idx`.

Use

Enter ⇒ **`lwarpmk printindex`**

Enter ⇒ **`lwarpmk htmlindex`**

to compile the indexes.

8.6.20 Using a custom *makeindex* style file

Prog makeindex
File lwarp.ist

When using *makeindex*, *lwarpmk* uses the file `lwarp.ist` to process the index. This file is over-written by lwarp whenever a print version of the document is processed.

To use a custom *makeindex* style file:

1. Copy `lwarp.ist` to a new filename such as `projectname.ist`
2. Make changes to `projectname.ist`. Keep the lines which refer to `\hyperindexref`. These lines creates the hyperlinks for the HTML index. During print output `\hyperindexref` becomes a null function.
3. If changing

   ```
   delim_n -and- delim_r
   ```

   in `projectname.ist`, then in the document preamble redefine

   ```
   \IndexPageSeparator -and- \IndexRangeSeparator
   ```

   to match.

Opt makeindexStyle

4. In the document source use the `makeindexStyle` option for lwarp:

   ```
   \usepackage[
     . . . other options . . .
     makeindex,
     makeindexStyle=projectname.ist,
   ]{lwarp}
   ```

   Likewise, refer to the custom style file if using `\PrintIndexCmd`, `\HTMLIndexCmd`, or `\LatexmkIndexCmd`.
5. Recompile the print version, which causes lwarp to rewrite the `lwarpmk.conf` configuration file. This tells *lwarpmk* to use the custom `projectname.ist` file instead of `lwarp.ist`.

8.6.21 Using a custom *xindy* style file

Prog xindy
File lwarp.xdy

When using *xindy*, *lwarpmk* uses the file `lwarp.xdy` to process the index. This file is over-written by lwarp whenever a print version of the document is processed.

To use a custom *xindy* style file:

1. Copy `lwarp.xdy` to a new filename such as `projectname.xdy`
2. Make changes to `projectname.xdy`.

   Keep the lines which refer to `\hyperindexref`:

   ```
   (define-attributes (("hyperindexref")))
   (markup-locref :open "\hyperindexref{" :close "}")
   ...
   (markup-locref :open "\textit{\hyperindexref{" :close "}}" :attr "textit")
   ```

These lines create the hyperlinks for the HTML index. During print output `\hyperindexref` becomes a null function.

To create custom styles, refer to the lines for `\textbf` and `\textit`.

3. If changing any of

```
markup-locref-list :sep
markup-locclass-list :open
markup-locclass-list :sep
markup-crossref-layer-list :sep
markup-range :sep
```

in `projectname.xdy`, then in the document preamble redefine

```
\IndexPageSeparator -and- \IndexRangeSeparator
```

to match.

Opt `xindyStyle`

4. In the document source use the `xindyStyle` option for lwarp:

```
\usepackage[
  . . . other options . . .
  xindy,
  xindyStyle=projectname.xdy,
]{lwarp}
```

Likewise, refer to the custom style file if using `\PrintIndexCmd`, `\HTMLIndexCmd`, or `\LatexmkIndexCmd`.

5. Recompile the print version, which causes lwarp to rewrite the `lwarpmk.conf` configuration file. This tells *lwarpmk* to use the custom `projectname.xdy` file instead of `lwarp.xdy`.

8.6.22 Using a custom *xindex* style file

Prog `xindex`

To use a custom *xindex* style file:

⚠ filename

1. Copy `xindex-cfg.lua` to a new filename such as `xindex-projectname.lua`. The filename must start with `xindex-` and end with `.lua`.

2. Make changes to `xindex-projectname.lua`.

3. If changing

```
itemPageDelimiter -and- rangeSymbol
```

in `xindex-projectname.lua`, then in the document preamble redefine

```
\IndexPageSeparator -and- \IndexRangeSeparator
```

to match.

Opt `xindexConfig`

4. In the document source use the `xindexConfig` option for lwarp:

```
\usepackage[
  . . . other options . . .
  xindex,
  xindexConfig=projectname,    % (without xindex- or .lua)
]{lwarp}
```

Likewise, refer to the custom style file if using `\PrintIndexCmd`, `\HTMLIndexCmd`, or `\LatexmkIndexCmd`.

5. Recompile the print version, which causes lwarp to rewrite the `lwarpmk.conf` configuration file. This tells *lwarpmk* to use the custom `xindex-projectname.lua` file instead of the default `xindex-cfg.lua`.

8.6.23 Additional indexing limitations

⚠ *xindy* with hyperref

xindy and hyperref may not work well together for print output with "see", "see also", reference ranges, or stylized index references. It may be necessary to turn off hyperreferencing for indexes:

```
\usepackage[hyperindex=false]{hyperref}
```

⚠ empty index

If an HTML index is empty, it may be necessary to add the following before lwarp is loaded:

```
\usepackage{morewrites}
\morewritessetup{allocate=10}
. . .
\usepackage{lwarp}
```

makeindex custom display styles

When using *makeindex*, custom display styles are possible:

```
\begin{warpprint}
\newcommand{\notesstyle}[1]{#1nn}
\end{warpprint}

\begin{warpHTML}
\makeatletter
\newcommand{\notesstyle}[1]{\LWR@doindexentry{#1} notes }
\makeatother
\end{warpHTML}
. . .
A sentence.\index{key|notesstyle}
```

xindy custom display styles

For custom styles with *xindy*, see `lwarp.xdy` for `\textbf` and `\textit` as examples.

8.6.24 Index positions, TOC, tocbibind

placement and TOC options

An index may be placed inline with other HTML text, or on its own HTML page:

Pkg makeidx

Inline, with a manual TOC entry:

A commonly-used method to introduce an index in a LaTeX document:

```
\cleardoublepage
\phantomsection
\addcontentsline{toc}{section}{\indexname}% or chapter
\printindex
```

Pkg makeidx **On its own HTML page, with a manual TOC entry:**

```
\begin{warpprint}
\cleardoublepage
\phantomsection
\addcontentsline{toc}{section}{\indexname}% or chapter
\end{warpprint}
\ForceHTMLPage
\ForceHTMLTOC
\printindex
```

Pkg tocbibind **Inline, with an automatic TOC entry:**

The tocbibind package may be used to automatically place an entry in the TOC.

```
\usepackage[nottoc]{tocbibind}
. . .
\cleardoublepage
\phantomsection % to fix print-version index link
\printindex
```

Pkg tocbibind **On its own HTML page, with an automatic TOC entry:**

```
\usepackage[nottoc]{tocbibind}
. . .
\cleardoublepage
\phantomsection % to fix print-version index link
\ForceHTMLPage
\printindex
```

Opt [tocbibind] numindex
numbered index section

Use the tocbibind `numindex` option to generate a numbered index. Without this option, the index heading has no number.

Other packages, such as imakeidx, may also have options for including the index in the Table of Contents.

Pkg tocloft
⚠ tocloft & other packages

If using tocloft with tocbibind, anonchap, fncychap, or other packages which change chapter title formatting, load tocloft with its `titles` option, which tells tocloft to use standard LaTeX commands to create the titles, allowing other packages to work with it.

8.7 Math

8.7.1 Math in section names

⚠ math in section names

If using named HTML files, in section names use paren math `\(x+y\)` instead of dollar math `$x+y$`. (Dollar math works, but appears in the filename.) Or, use a short name for the TOC entry without the math, or use `\texorpdfstring` from the hyperref package:

```
\section{Some math \texorpdfstring{$1+2=3$}{three}}
```

8.7.2 Rendering tradeoffs

Math rendering

Math may be rendered as SVG graphics or using the MathJax JavaScript display engine.

SVG files

Rendering math as images creates a new SVG file for each expression, except that an MD5 hash is used to combine identical duplicates of the same inline math expression into a single file, which must be converted to SVG only once. Display math is still handled as individual files, since it may contain labels or references which are likely to change.

SVG inline

The SVG images are currently stored separately, but they could be encoded in-line directly into the HTML document. This may reduce the number of files and potentially speed loading the images, but slows the display of the rest of the document before the images are loaded.

PNG files

Others LaTeX-to-HTML converters have used PNG files, sometimes pre-scaled for print resolution but displayed on-screen at a scaled down size. This allows high-quality print output at the expense of larger files, but SVG files are the preferred approach for scalable graphics.

MathML

Conversion to MathML might be a better approach, among other things allowing a more compact representation of math than SVG drawings. Problems with MathML include limited browser support and some issues with the fine control of the appearance of the result. Also see section 10 regarding EPUB output with MathJax.

8.7.3 svg option

SVG math option

For SVG math, math is rendered as usual by LaTeX into the initial PDF file using the current font[14], then is captured from the PDF and converted to SVG graphics via a number of utility programs. The SVG format is a scalable-vector web format, so math may be typeset by LaTeX with its fine control and precision, then displayed or printed at any size, depending on (sometimes broken) browser support. An HTML `alt` attribute carries the LaTeX code which generated the math, allowing copy/paste of the LaTeX math expression into other documents.

SVG image font size

For the `lateximage` environment, the size of the math and text used in the SVG image may be adjusted by setting `\LateximageFontSizeName` to a font size name — *without the backslash*, which defaults to:

```
\renewcommand{\LateximageFontSizeName}{normalsize}
```

For inline SVG math, font size is instead controlled by `\LateximageFontScale`, which defaults to:

```
\newcommand*{\LateximageFontScale}{.75}
```

SVG math copy/paste

For SVG math, text copy/paste from the HTML `<alt>` tags lists the equation number or tag for single equations, along with the LaTeX code for the math expression. For AMS environments with multiple numbers in the same environment, only the first and last is copy/pasted, as a range. No tags are listed inside a starred AMS environment, although the `\tag` macro will still appear inside the LaTeX math expression.

⚠ SVG math size, baseline

SVG math sizing and baselines are improved if the graphics or graphicx package is loaded. An almost-invisible marker is placed at either end of the image to assist in cropping and computing the baseline. A warning is issued at the end of the compile if graphics or graphicx are not used.

[14] See section 667 regarding fonts and fractions.

⚠ SVG math in TEX boxes

SVG math does not work inside TEX boxes, since a \newpage is required before and after each image.

8.7.4 MathJax option

MathJax math option

Prog MathJax

The MathJax (mathjax.org) LATEX-math to HTML converter may be used to display math.

When MathJax is enabled, math is rendered twice:

1. As regular LATEX PDF output placed inside an HTML comment, allowing equation numbering and cross referencing to be almost entirely under the control of LATEX, and
2. As detokenized printed LATEX commands placed directly into the HTML output for interpretation by the MathJax display scripts. An additional script is used to pre-set the equation number format and value according to the current LATEX values, and the MathJax equation numbering system is ignored in favor of the LATEX internal system, seamlessly integrating with the rest of the HTML output, including any math appearing in non-MathJax SVG output.

8.7.5 Customizing MathJax

equation numbering

lwarp detects and adjusts MathJax equation numbering format for article and book style equations as well as amsmath \numberwithin for chapters, sections, and subsections. Custom equation number formats may be set as follows, for example:

```
\renewcommand*{\theequation}{\Alph{section}.\arabic{equation}}
\AtBeginDocument{
  \renewcommand*{\theMathJaxsection}{\Alph{section}.}
}
```

⚠ subequation

The amsmath subequations environment is supported, but only with \alpha subequation numbering.

global customizations

MathJax does not have preexisting support every possible math function. Additional MathJax function definitions may be defined in the preamble. These will be declared at the start of each HTML page, and thus will have a global effect across all HTML pages.

Examples:

```
\begin{warpMathJax}
\CustomizeMathJax{
    \newcommand{\expval}[1]{\langle#1\rangle}
    \newcommand{\abs}[1]{\lvert#1\rvert}
}
\CustomizeMathJax{\newcommand{\arcsinh}{\text{arcsinh}}}
\CustomizeMathJax{\newcommand{\arccosh}{\text{arccosh}}}
\CustomizeMathJax{\newcommand{\NN}{\mathbb{N}}}
\end{warpMathJax}
```

⚠ slow compilation

To avoid a slowdown in compile speed, use the warpMathJax environment to prevent its contents from being processed in print or SVG math output. Also, place each new definition

inside its own \CustomizeMathJax. A warning to this effect is issued if an overly-long definition is attempted.

lwarp already provides MathJax customizations for some packages.

siunitx When using siunitx, a similar process may be used to add custom units:

```
\begin{warpMathJax}
\CustomizeMathJax{\newcommand{\myunit}{\mathrm{WXYZ}}}
\CustomizeMathJax{\newcommand{\umyunit}{\mathrm{\micro\myunit}}}
\end{warpMathJax}
```

advanced control For more advanced control over dynamically creating custom definitions, see as an example the lwarp definition for \DeclarePairedDelimiterX, in section 394, mathtools.

local customizations For customizations local to the current HTML page only, macros may be defined as follows:

```
\begin{warpMathJax}
\( \newcommand{\macroname}{. . . } \)
\( \newcommand{\anothername}{. . . } \)
\end{warpMathJax}
```

To maintain compile speed, use the warpMathJax environment, and use a separate math environment for each definition.

\ifstar For MathJax, use \ifstar instead of \@ifstar:

```
\CustomizeMathJax{
  \def\myname{
    \ifstar\starredaction\unstarredaction
    % (Do not place anything after!)
  } }
```

\ifnextchar For MathJax, use \ifnextchar instead of \@ifnextchar:

```
\CustomizeMathJax{\def\myname{\ifnextchar X \found\notfound}}
```

"X" may be a single ASCII character, or a hex number inside braces, ex:

```
\CustomizeMathJax{\def\myname{\ifnextchar{0x7B}\found\notfound}}
```

Use "(" or "{0x28}" for a left parenthesis, "{0x7B}" for a left brace, "{0x7D}" for a right brace, or "{0x5C}" for a backslash.

8.7.6 MathJax limitations

MathJax limitations Limitations when using MathJax include:

Prog MathJax

⚠ \multicolumn, multirow

- MathJax does not support \multicolumn or multirow. These may be used in text tabulars or SVG math, but in MathJax math arrays they are emulated. \multicolumn only fills a single cell, resulting in a short row. \multirow simply prints its text on the first line.

⚠ footnotes

- Footnotes are emulated when used inside a MathJax expression. For an equation with a single footnote, the correct footnote number is used. For non-equations,

\footnotename is used instead, since the actual number cannot be tracked. See section 8.5.4 regarding the use of footnotes with MathJax.

⚠ references

- Inside a MathJax expression, references to equations work within the same HTML web page, but do not work when referring to an equation in a different HTML web page. Outside of a MathJax expression, in the text body, references work as expected.

lateximage

- Math appearing inside a lateximage, and therefore also inside a Ti*k*z or picture environment, is rendered as SVG math even if MathJax is used in the rest of the document.

siunitx

- For siunitx, see siunitx package, section 8.7.13.

physics

- For physics, see physics package, section 8.7.15.

tabbing

- A tabbing environment is emulated using an HTML <pre>. While MathJax is enabled inside tabbing, the browser may not correctly render the horizontal alignment of the math and text following after on the same line.

\text

- MathJax includes the *textmacros* extension, which supports various macros which are commonly used inside \text, such as \textbf and text accents. Lwarp supports this extension.

⚠ other macros and packages

- Many other math-related macros and packages are not directly supported by MathJax, including \ensuremath and occasionally-used macros such as \relax. While using MathJax, lwarp provides emulation for many of these macros, as well as for footnotes and emulation for dozens of packages (see table 2). In many cases these emulations simply ignore the package in a source-compatible way. Others produce a result which represents the meaning, even if they don't look exact. Look up each package in this document for a description of the limitations of each.

8.7.7 Catcode changes

preamble macros with math

The math shift character $ is not set for HTML output until after the preamble. Macros defined in the preamble which contain $ must be enclosed between \StartDefiningMath and \StopDefiningMath to temporarily change to the HTML meaning of $:

```
\StartDefiningMath
\newcommand{. . .}
\StopDefiningMath
```

As an alternative, use \(and \) instead of $, in which case \StartDefiningMath and \StopDefiningMath are not necessary.

If a package defines macros using $, it may be nessary to use \StartDefiningMath and \StopDefiningMath before and after loading the package.

8.7.8 Complicated inline math objects

\inlinemathnormal
\inlinemathother

changing contents

An inline math expression is usually converted to a reusable hashed SVG math image, or a MathJax expression. The hash or expression depends on the contents of the math expression. In most cases this math expression is static, such as $x+1$, so the image can be reused for multiples instances of the same expression. In some cases, the math

complicated alt tag
MathJax limitations

expression includes a counter or other object which may change between uses. Another problem is complicated contents which do not expand well in an alt tag. Yet another problem is math packages which are only partially emulated in MathJax. The macro \inlinemathother may be used before a sequence of dynamic or complicated math expressions, and \inlinemathnormal after. Doing so tells lwarp to use unhashed svg math images for those particular expressins, even if MathJax is otherwise in use. See section 44.

8.7.9 Complicated display math objects

\displaymathnormal

By default, or when selecting \displaymathnormal, MathJax math display environments print their contents as text into html for MathJax to interpret, and svg display math environments render their contents as svg images and use their contents as the alt tag of html output. To do so, the contents are loaded into a macro for reuse. In some cases, such as complicated Ti*k*z pictures, compilation will fail.

\displaymathother
MathJax unsupported
complicated alt tag

When selecting \displaymathother, it is assumed that the contents are more complicated than "pure" math. An example is an elaborate Ti*k*z picture, which will not render in MathJax and will not make sense as an html alt tag. In this mode, MathJax is turned off, math display environments become svg images, even if MathJax is selected, and the html alt tags become simple messages. The contents are internally processed as an environment instead of a macro argument, so complicated objects such as Ti*k*z pictures are more likely to compile successfully.

8.7.10 Theorems

⚠ cref reference format undefined

If the print version does not use cleveref, place all \theoremstyle and \newtheorem declarations in the preamble inside \AtEndPreamble.[15] For some theorems, it may also be required to add inside \AtEndPreamble something such as:

```
\usepackage{etoolbox} % for \ifdef, \AtEndPreamble
\AtEndPreamble{ % if not using cleveref package
  \theoremstyle{definition}
  \newtheorem{dtheorem}{Definition}
  . . .
  \ifdef{\cref}{
    \crefname{Proof}{Proof}{Proofs}
  }{}
}
```

8.7.11 ntheorem package

Pkg ntheorem

This conversion is not total. Font control is via css, and the custom LaTeX font settings are ignored.

⚠ Font control

⚠ Equation numbering

ntheorem has a bug with equation numbering in $\mathcal{AMS}$ environments when the option

[15] lwarp uses cleveref for the html conversion, and loads cleveref \AtEndPreamble, just before \AtBeginDocument. This is also before the .aux file is read.

`thref` is used. lwarp does not share this bug, so equations with `\split`, etc, are numbered correctly with lwarp's HTML output, but not with the print output. It is recommended to use cleveref instead of ntheorem's `thref` option.

8.7.12 mathtools package

Pkg `mathtools`

`showonlyrefs` is disabled, as it conflicts with cleveref, which is used by lwarp. Equation numbers may not match the print version.

⚠ equation numbering

⚠ italic correction

`mathic` is not emulated for HTML.

⚠ MathJax

If using MathJax:

- mathtools `disallowspaces` does not work for MathJax. Protect brackets which are not optional arguments, such as:

```
\begin{gathered}{}
[p]=1 . . .
\end{gathered}
```

- `showonlyrefs` does not work in MathJax, and will result in a difference in equation numbering compared to the print version.
- Due to MathJax limitations, the following do not render well: `\overbracket`, `\underbracket`, `\overbrace`, `\underbrace`, `rcases`, `drcases`, `\Aboxed`, and `\ArrowBetweenLines`.
- For the new `cases`-like environments, `\text` must be used to set the normal roman font if desired.
- `alignat` in MathJax requires math mode, but in LaTeX it doesn't. It may be required to use `warpHTML` and `warpprint` to isolate a version for each mode.
- `\DeclarePairedDelimiter` and related must be in the preamble before `\begin{document}`.

8.7.13 siunitx package

Pkg `siunitx`

siunitx v3 is not yet supported. For now, specify version 2:

⚠ v3 not yet!

```
\usepackage{siunitx}[=v2]
```

This may be also be necessary before loading other packages which also use siunitx, such as chemmacros.

fractions

Due to *pdftotext* limitations, fraction output is replaced by symbol output for `per-mode` and `quotient-mode`.

⚠ math mode required

Some units will require that the expression be placed inside math mode.

⚠ `tabular`

Tabular `S` columns are rendered as simple `c` columns, and tabular `s` columns are not supported. These may be replaced by `c` columns with each cell contained in `\num` or `\si`.

⚠ MathJax

For math mode with SVG display, the original siunitx code is used while generating the SVG image. For text mode, lwarp uses an emulation which provides a very effective HTML interpretation of siunitx. For math expressions while using MathJax, a limited emulation is used. Most functions work reasonably well, but many options cannot be emulated. Complicated parsing such as for \ang is not supported. The result usually looks fine, and otherwise is enough to get the meaning across.

Document modifications required for MathJax:

custom units

- Custom units may be added with \CustomizeMathJax. See the lwarp-siunitx code for examples.

⚠ unit spacing

- Units work better using ~ between units instead of using periods.

⚠ \square, \cubic

- To square or cube compound units, enclose the following compound units in braces:

  ```
  \cubic{\centi\meter}
  ```

  Single units do not require braces.

Also see MathJax option, section 8.7.4.

8.7.14 units and nicefrac packages

Pkg units
Pkg nicefrac

units and nicefrac work with lwarp, but MathJax does not have an extension for units or nicefrac. These packages do work with lwarp's option svgmath.

8.7.15 physics package

Pkg physics

physics works as-is for HTML with SVG math.

For MathJax, the MathJax v3 physics extension is used.

8.8 Graphics

Pkg graphics
Pkg graphicx

⚠ case sensitive

Per table 9, image filenames may be specified either with or without an extension. If an extension is given it will be used as-is, for either print or HTML output. If no extension is given, a list of possible extensions is tried, which depends on whether print or HTML is being generated. This allows a PDF file for print and a SVG file for HTML, for example. If no extension is given, the automatic search will only return lowercase extensions, even if the filename actually has an uppercase extension, and lwarp cannot get around this problem, so image file extensions must be lowercase to be seen by the HTML browser with lwarp. For example, name the image file image.pdf instead of image.PDF, but refer to it in the source as image, without an extension. For images which may be used as-is with either print or HTML, such as JPG or PNG, you may use a capitalized extension if it is specified in the source, such as image.JPG.

\includegraphics file formats

For \includegraphics with .pdf or .eps files, the user must provide a .pdf or .eps

Table 9: \includegraphics and file names

Print image file	HTML image file	Command to use
image.pdf[a]	image.svg[a]	\includegraphics{image}
image.eps[a]	image.svg[a]	\includegraphics{image}
image.jpg	—[b]	\includegraphics{image}
image.png	—[b]	\includegraphics{image}
image.JPG	—[b]	\includegraphics{image.JPG}[c]
image.PNG	—[b]	\includegraphics{image.PNG}[c]
image.jpg	image.gif	\includegraphics{image}

[a:] Must be a lowercase file extension.
[b:] The same file is used for print and HTML.
[c:] The uppercase extension must be specified.

image file for use in print mode, and also a .svg, .png, or .jpg version of the same image for use in HTML.

```
\includegraphics{filename} % print:.pdf/.eps HTML:.svg, etc.
```

For print output, lwarp will automatically choose the .pdf or .eps format if available, or some other format otherwise. For HTML, one of the other formats is used instead.

If a .pdf or .eps image is referred to with its file extension, the extension will be changed to .svg for HTML:

```
\includegraphics{filename.pdf} % uses .svg in html
\includegraphics{filename.eps} % uses .svg in html
```

Prog pdftocairo
PDF to SVG

To convert a PDF image to SVG, use the utility *pdftocairo*:

Enter ⇒ **pdftocairo -svg filename.pdf**

Prog lwarpmk pdftosvg

For a large number of images, use *lwarpmk*:

Enter ⇒ **lwarpmk pdftosvg *.pdf** **(or a list of filenames)**

Prog lwarpmk epstopdf
Prog epstopdf
epstopdf package

For EPS images converted to PDF using the package epstopdf, use

Enter ⇒ **lwarpmk pdftosvg *.PDF**

to convert to SVG images.

DVI LaTeX

When using DVI *latex*, it is necessary to convert EPS to PDF and then to SVG:

Enter ⇒ **lwarpmk epstopdf *.eps** **(or a list of filenames)**

Enter ⇒ **lwarpmk pdftosvg *.pdf** **(or a list of filenames)**

PNG and JPG — For PNG or JPGwhile using *pdflatex*, *lualatex*, or *xelatex*, the same file may be used in both print or HTML versions, and may be used with a file extension, but will also be used without the file extension if it is the only file of its base name.

GIF — GIF files may be used for HTML, but another format must also be provided for print output.

file extension priorities — If a file extension is not used, for HTML the file extension priorities are: SVG, GIF, PNG, then JPG.

⚠ graphics vs. graphicx — If using the older graphics syntax, use both optional arguments for `\includegraphics`. A single optional parameter is interpreted as the newer graphicx syntax. Note that viewports are not supported by lwarp — the entire image will be shown.

⚠ viewport

⚠ viewport units — For `\includegraphics`, avoid `px` and `%` units for width and height, or enclose them inside `warpHTML` environments. For font-proportional image sizes, use `ex` or `em`. For fixed-sized images, use `cm`, `mm`, `in`, `pt`, or `pc`. Use the keys `width=.5\linewidth`, or similar for `\textwidth` or `\textheight` to give fixed-sized images proportional to a 6 by 9 inch text area. Do not use the `scale` option, since it is not well supported by HTML browsers.

options — `\includegraphics` accepts `width` and `height`, `origin`, `rotate` and `scale`, plus new `class` and `alt` keys.

HTML class — With HTML output, `\includegraphics` accepts an optional `class=xyz` keyval combination, and if this is given then the HTML output will include that class for the image. The class is ignored for print output.

HTML `alt` tags — Likewise, the `\includegraphics alt` key adds an HTML `alt` tag to an image, and is ignored for print output. If not assigned, each image is given an `alt` tag according to `\ImageAltText`.

⚠ `scale` — Avoid using the `\includegraphics scale` option. Change:

```
\includegraphics[scale=<xx>]{ . . . }
```

to:

```
\includegraphics[width=<yy>\linewidth]{ . . . }
```

`\rotatebox` — `\rotatebox` accepts the optional `origin` key.

⚠ browser support — `\rotatebox`, `\scalebox`, and `\reflectbox` depend on modern browser support. The CSS3 standard declares that when an object is transformed the whitespace which they occupied is preserved, unlike LaTeX, so expect some ugly results for scaling and rotating.

8.8.1 tikz package

Pkg `tikz`

⚠ displaymath and matrices — If using display math with `tikzpicture` or `\tikz`, along with matrices with the & character, the document must be modified as follows:

```
\usepackage{tikz}
\tikzset{every picture/.style={ampersand replacement=\&}}
```

and each instance of & in the tikz expression must be replaced with `\&`.

8.8.2 grffile package

Pkg grffile

⚠ matching PDF and SVG

grffile is supported as-is. File types known to the browser are displayed, and unknown file types are given a link. Each PDF image for print mode should be accompanied by an SVG, PNG, or JPG version for HTML.

8.8.3 color package

Pkg color

color is superceded by xcolor, and lwarp requires several of the features of xcolor. When color is requested, xcolor is loaded as well.

8.8.4 xcolor package

Pkg xcolor

\colorboxBlock and \fcolorboxBlock

\colorboxBlock and \fcolorboxBlock are provided for increased HTML compatibility, and they are identical to \colorbox and \fcolorbox in print mode. In HTML mode they place their contents into a instead of a . These s are set to display: inline-block so adjacent \colorboxBlocks appear side-by-side in HTML, although text is placed before or after each.

Print-mode definitions for \colorboxBlock and \fcolorboxBlock are created by lwarp's core if xcolor is loaded.

background: none

\fcolorbox and \fcolorboxBlock allow a background color of none, in which case only the frame is drawn, which can be useful for HTML.

color support

Color definitions, models, and mixing are fully supported without any changes required.

colored tables

\rowcolors is supported, except that the optional argument is ignored so far.

colored text and boxes

\textcolor, \colorbox, and \fcolorbox are supported.

\color and \pagecolor

\color and \pagecolor are ignored. Use CSS or \textcolor where possible.

8.8.5 epstopdf package

Pkg epstopdf

⚠ convert to .svg

Images with an .eps extension will be converted to .pdf. The HTML output uses the .svg version, so use

Enter ⇒ **lwarpmk pdftosvg <listofPDFfiles>**

to generate .svg versions.

8.8.6 pstricks package

Pkg pstricks

⚠ use pspicture

All pstricks content should be contained inside a pspicture environment.

8.8.7 pdftricks package

Pkg pdftricks

⚠ convert image files

The pdftricks image files <jobname>-fig*.pdf must be converted to .svg, or else a missing file error will occur. The image files must also be converted again whenever they change. To convert the images:

Enter ⇒ **lwarpmk pdftosvg <jobname>-fig*.pdf**

8.8.8 psfrag package

Pkg psfrag

⚠ use psfrags

The psfrags environment is modified to use lateximage to encapsulate the image. Always use a psfrags environment to contain any local \psfrag macros and the associated \includegraphics or \epsfig calls. Outside of a psfrags environment, psfrags adjustments will not be seen by lwarp.

⚠ Tip: Use a mono-spaced font for the tags in the EPS file.

8.8.9 pstool package

Pkg pstool

\graphicspath is ignored, and the file directory must be stated.

⚠ path and filename

The filename must not have a file extension.

Use

Enter ⇒ **lwarpmk html**

followed by

Enter ⇒ **lwarpmk limages**

.

8.8.10 asymptote package

Pkg asymptote

To compile:

```
pdflatex project.tex
asy project-*.asy
pdflatex project.tex

lwarpmk print
asy project-*.asy
lwarpmk print1
lwarpmk print1

lwarpmk html
asy project_html-*.asy
lwarpmk html1
lwarpmk html1
lwarpmk limages
```

8.8.11 overpic package

Pkg overpic

⚠ scaling

The macros `\overpicfontsize` and `\overpicfontskip` are used during HTML generation. These are sent to `\fontsize` to adjust the font size for scaling differences between the print and HTML versions of the document. Renew these macros before using the `overpic` and `Overpic` environments.

8.8.12 Multimedia packages

Pkg multimedia

Pkg movie15

Pkg media9

The packages multimedia, movie15, and media9 are supported.

HTML5 <audio> and <video> objects are created for `.mp3` and `.mp4` files.

HTML5 <embed> objects are created for `http` and `ftp` links.

`\href` links are created for other media types. (Unfortunately, there is not much overlap between the file types supported for print output and the file types supported by HTML5.)

For media9, a multimedia object is inserted for each `addresource=`, as well as each `flashvars` `source=` and `src=`. This may result in duplicate objects.

Undesired objects may be nullified by placing them inside `\warpprintonly` or the `warpprint` environment.

Each HTML multimedia object includes the poster text, except for <embed> objects. For movie15, the `text` option is supported to specify the poster text.

The `width`, `height`, and `totalheight` options are supported. The HTML object is scaled according to the display width, correctly compensating for either tall or wide viewports.

Other options are ignored.

media9 \addmediapath is supported. It is assumed that the same path structure will exist for the HTML document.

HTML5 media controls are always specified for each <audio> and <video> object.

media9 slideshows are not supported.

\hyperlinkmovie, \movieref, and \mediabutton are not supported.

3D objects are not supported.

If using a YouTube™ video, use an "embedded" URL with .../embed/... instead of .../v/...

8.9 Tabbing

The tabbing environment works, except that SVG math and lateximages do not yet work inside the environment.

⚠ math in tabbing

If math is used inside tabbing, place tabbing inside a lateximage environment, which will render the entire environment as a single SVG image.

8.10 Tabular

8.10.1 tabular environment

Tabular mostly works as expected, but pay special attention to the following, especially if working with environments, macros inside tabulars, multirows, siunitx S columns, or the packages multirow, longtable, supertabular, or xtab.

Defining macros and environments:

⚠ Misplaced alignment tab character &

- When defining environments or macros which include tabular and instances of the & character, it may be necessary to make & active before the environment or macro is defined, then restore & to its default catcode after, using the following commands. These are are ignored in print mode.

```
\StartDefiningTabulars
<define macros or environments using tabular and & here>
\StopDefiningTabulars
```

⚠ floatrow

This includes before and after defining any macro which used \ttabbox from floatrow.

⚠ tabular inside another environment

- When creating a new environment which contains a tabular environment, lwarp's emulation of the tabular does not automatically resume when the containing enviroment ends, resulting in corrupted HTML rows. To fix this, use \ResumeTabular as follows. This is ignored in print mode.

```
\StartDefiningTabulars %   (& is used in a definition)
\newenvironment{outerenvironment}
{
  \tabular{cc}
  left & right \\
}
{
  \TabularMacro\ResumeTabular
  left & right \\
  \endtabular
}
\StopDefiningTabulars
```

For developers:

- To automate the use of \StartDefiningTabulars and \EndDefiningTabulars, these macros may be embedded inside an HTML environment definition to automatically change the catcode of & before absorbing the arguments. Another environment may be embedded as well.

```
% Does the work after the catcode has been changed:
\newcommand*{\LWR@HTML@subsomename}[2]{%
  . . .
  \otherenvironmentname [<args>] {<args>}  % for example
}
% Change catcode before absorbing arguments:
\newcommand*{\LWR@HTML@somename{%
  \StartDefiningTabulars
  \LWR@HTML@subsomename
}
% Change catcode again at the end:
\newcommand*{\LWR@HTML@endsomename}{%
  . . .
  \endotherenvironmentname   % for example
  \StopDefiningTabulars
}
% Combine with the existing print definition:
\LWR@formattedenv{somename}
```

Cell contents:

⚠ macro in a table

- Using a custom macro inside a tabular data cell may result in an extra HTML data cell tag, corrupting the HTML table. To avoid this, use \TabularMacro just before the macro. This is ignored in print mode.

```
\TabularMacro\somemacro & more row contents \\
```

Column specifiers:

@ and !

- Only one each of @ and ! is used at each column, and they are used in that order.

\multirow

- In \multirow cells, the print version may have extra instances of <, >, @, and ! cells on the second and later rows in the \multirow which do not appear in the HTML version.

⚠ \newcolumntype

- \newcolumntype is ignored; unknown column types are set to l.

Rules:

- Doubled `\hlines`, `\midrules`, and vertical rules are supported.

vertical rules

- Vertical rules next to either side of an `@` or `!` column are displayed on both sides of the column.

width and trim

- Width options are honored. Trim options are converted to rounded top corners. Trim corners are not rounded with `@` or `!` columns, and full-width rules ignore trim. When given an optional width, each cell is styled to create the custom border. Without an optional width, the entire row is given a class to assign the standard border.

combined rules

- If you wish to use `\cmidrule` followed by `\bottomrule`, it may be necessary to use:

```
\cmidrule{2-3} \\[-2ex]
\bottomrule
```

The optional `-2ex` is ignored in HTML, but improves the visual formatting in the print output.

⚠ `\warpprintonly`
⚠ Misplaced `\noalign`

- For `\toprule` and `\bottomrule`, when combined with a `warpprint` or `warpHTML` environment, if a "Misplaced `\noalign`" error occurs, change

```
This & That \endhead
```

to

```
\warpprintonly{This & That \endhead}
```

and likewise with the other `\end` headings. Keep the `\endfirsthead` row unchanged, as it is still relevent to HTML output.

Other:

- tabularx ignores the width, but `X` columns do produce paragraph columns or multicolumns.

`longtable` headings

- For longtable, place headings and footings which do not apply to HTML inside `\warpprintonly{}`.

⚠ S columns

- For S columns (from the siunitx package), while producing print output, anything non-numeric must be placed inside { } braces, including commands such as `\multirow`. While producing HTML output, though, anything placed inside braces is not seen by lwarp's tabular handling algorithm. To resolve this problem, make a copy of the row, with one version for print output, containing the extra braces, and another version for HTML output, without the extra braces, such as:

```
\warpprintonly{1 & 2 & {\multirow{2}{2cm}{Text}} & 3 \\}
\warpHTMLonly{1 & 2 & \multirow{2}{2cm}{Text} & 3 \\}
```

⚠ `tabular` inside a `<span>`

- In LaTeX, a `tabular` may be placed inside a `minipage`, but in HTML a `<table>` may not be inside a `<span>`. If this situation is detected, a warning is printed instructing the user to isolate the `<span>` using `\warpprintonly` or the `warpprint` environment.

8.10.2 multirow package

vposn

- Note that recent versions of multirow include a new optional vposn argument.

multirow cells

- For multirow, insert `\mrowcell` into any empty multi-row cells. This will be a null function for the print output, and is a placeholder for parsing the table for HTML output. An error is generated if this is missed.

```
. . . &  \multirow{2}{.5in}{text}  & . . .
. . . &  \mrowcell                 & . . .
```

colored cells

- The multirow documentation regarding colored cells recommends using a negative number of rows. This will not work with lwarp, so \warpprintonly and \warpHTMLonly must be used to make versions for print and HTML.

with \multicolumn

- See section 424.2 for \multicolumnrow.

⚠ \multicolumn & \multirow

lwarp does not support directly combining \multicolumn and \multirow. Use \multicolumnrow instead. To create a 2 column, 3 row cell:

```
\multicolumnrow{2}{c}[c]{3}[0]{1in}[0pt]{Text}
```

The two arguments for \multicolumn come first, followed by the five arguments for \multirow, many of which are optional, followed by the contents.

⚠ skipped cells

As per \multirow, skipped cells to the right of the \multicolumnrow statement are not included in the source code on the same line. On the following lines,

⚠ empty cells

\mcolrowcell must be used for each cell of each column and each row to be skipped. An error is generated if this is missed.

```
. . . &  \multicolumnrow{2}{c}[c]{3}[0]{1in}[0pt]{Text}  & . . .
. . . &  \mcolrowcell          &          \mcolrowcell   & . . .
. . . &  \mcolrowcell          &          \mcolrowcell   & . . .
```

⚠ MathJax

- MathJax does not support multirow, so it is emulated to only print its text on the first row. \multirow works as expected in text tabulars or SVG math.

8.10.3 longtable package

Pkg longtable

Use one of either \endhead or \endfirsthead for both print and HTML, and use a \warpprintonly macro to disable the other head phrase, and also the \endfoot and \endfirstfoot phrases. (See section 8.10.4 if using threeparttablex.)

```
\begin{longtable}{ [column specifiers] }
[ . . . ] \endfirsthead   % or \endhead, for print and HTML
\warpprintonly{          % not used in HTML
  [ . . . ] \endhead     % or \endfirsthead
  [ . . . ] \endfoot
  [ <lastfoot macros> ] \endlastfoot
}
. . .  table contents . . .
\warpHTMLonly{
  [ <lastfoot macros> ]   % HTML last footer, without \endfoot
                                                % or \endlastfoot.
}
\end{longtable}
```

⚠ Misplaced \noalign

Use the \warpprintonly macro instead of the warpprint environment. Doing so helps avoid "Misplaced \noalign." when using \begin{warpprint}.

⚠ \kill

\kill is ignored, place a \kill line inside

```
\begin{warpprint} . . .  \end{warpprint}
```

or place it inside \warpprintonly.

⚠ lateximage longtable is not supported inside a lateximage.

8.10.4 threeparttablex package

Pkg threeparttablex threeparttablex is used with longtable and booktabs as follows:

```
\begin{longtable}{ [column specifiers] }
[ . . . ] \endfirsthead   % or \endhead, for print and HTML
\warpprintonly{          % not used in HTML
  [ . . . ] \endhead     % or \endfirsthead
  [ . . . ] \endfoot
  \bottomrule \insertTableNotes \endlastfoot
}
. . .  table contents . . .
\warpHTMLonly{   % HTML last footer
  \bottomrule
  \UseMinipageWidths     % optional
  \insertTableNotes
  \endlastfoot
}
\end{longtable}
```

table width The table notes are created using a \multicolumn. By default the width is not specified to the browser, so long table notes can cause the table to be spread out horizontally. For HTML output, lwarp guesses the width of the table depending on the number of columns, then restricts its guess to a min/max range. To use this guess for the width of the table notes, use \UseMinipageWidths before \insertTableNotes. The width is then specified, and in many cases the result is an improvement in overall table layout.

8.10.5 supertabular and xtab packages

Pkg supertabular For \tablefirsthead, etc., enclose them as follows:

Pkg xtab

⚠ Misplaced alignment tab character &

```
\StartDefiningTabulars
\tablefirsthead
. . .
\StopDefiningTabulars
```

See section 8.10.1.

⚠ lateximage supertabular and xtab are not supported inside a lateximage.

8.10.6 colortbl package

Pkg colortbl Only use \rowcolor and \cellcolor at the start of a row, in that order.

⚠ row/cell color colortbl ignores the overhang arguments.

8.10.7 ctable package

⚠ Misplaced alignment tab character &

Use \StartDefiningTabulars before one or more \ctables, and \StopDefiningTabulars after. These change the meaning of the ampersand & character.

8.10.8 bigdelim package

Pkg bigdelim

⚠ use \mrowcell

\ldelim and \rdelim use \multirow, so \mrowcell must be used in the proper number of empty cells in the same column below \ldelim or \rdelim, but not in cells which are above or below the delimiter:

```
\begin{tabular}{lll}
<empty> & a & b \\
\ldelim{\{}{3}{.25in}[left ] & c & d \\
\mrowcell & e & f \\
\mrowcell & g & h \\
<empty> & i & j \\
\end{tabular}
```

<-> a b

left { c d
e f
g h

<-> i j

For MathJax, limited emulation is provided which merely prints the delimter and optional text in the first row.

8.11 Floats

8.11.1 Float contents alignment

⚠ figure & table alignment

\centering, etc. are honored in a figure or table if they are the first command inside the float:

```
\begin{table*}
\centering
\caption{A Table}
. . .
```

8.11.2 float, trivfloat, and/or algorithmicx together

Pkg float

Pkg trivfloat

Pkg algorithmicx

⚠ package conflicts

If using \newfloat, trivfloat, and/or algorithmicx together, see section 627.1.

8.11.3 caption and subcaption packages

Pkg caption
Pkg subcaption

Package options may cause problems with lwarp, especially if they include curley braces.

If selecting options with braces in \usepackage does not work:

```
\usepackage[font={it,small}]{caption}% does not work
```

... try instead selecting the package options before loading lwarp:

```
\PassOptionsToPackage{font={it,small}}{caption}
. . .
\usepackage{lwarp}
. . .
\usepackage{caption}
```

... or try setting package options after the package has been loaded:

```
\usepackage{caption}
\captionsetup{font={it,small}}
```

⚠ numbering

To ensure proper float numbering, set caption positions such as:

```
\captionsetup[figure]{position=bottom}
\captionsetup[subfigure]{position=bottom}
\captionsetup[table]{position=top}
\captionsetup[subtable]{position=top}
```

Similarly for longtable. These positions depend on where the user places the \caption command inside each float.

8.11.4 subfig package

Pkg subfig

⚠ table numbering

To have correct sub table numbers:

```
\usepackage{caption}
\captionsetup[table]{position=top}
```

⚠ lof/lotdepth

At present, the package options for lofdepth and lotdepth are not working. These counters must be set separately after the package has been loaded.

⚠ horizontal spacing

In the document source, use \hfill and \hspace* between subfigures to spread them apart horizontally. The use of other forms of whitespace may cause paragraph tags to be generated, resulting in subfigures appearing on the following lines instead of all on a single line.

8.11.5 floatrow package

Pkg floatrow

Use \StartDefiningTabulars and \StopDefiningTabulars before and after defining macros using \ttabbox with a tabular inside. See section 8.10.1.

⚠ Misplaced alignment tab character &
⚠ subfig package

When combined with the subfig package, while inside a subfloatrow \ffigbox and

\ttabbox must have the caption in the first of the two of the mandatory arguments.

⚠ \FBwidth, \FBheight

The emulation of floatrow does not support \FBwidth or \FBheight. These values are pre-set to .3\linewidth and 2in. Possible solutions include:

- Use fixed lengths. lwarp will scale the HTML lengths appropriately.
- Use warpprint and warpHTML environments to select appropriate values for each case.
- Inside a warpHTML environment, manually change \FBwidth or \FBheight before the \ffigbox or \ttabbox. Use \FBwidth or \FBheight normally afterwards; it will be used as expected in print output, and will use your custom-selected value in HTML output. This custom value will be used repeatedly, until it is manually changed to a new value.

8.11.6 keyfloat package

Pkg keyfloat

⚠ keywrap

If placing a \keyfig[H] inside a keywrap, use an absolute width for \keyfig, instead of lw-proportional widths. (The [H] option forces the use of a minipage, which internally adjusts for a virtual 6-inch wide minipage, which then corrupts the lw option.)

For wrapped figures, overhang and number of lines are ignored.

8.12 KOMA-SCRIPT classes

Cls komascript

Many features are ignored during the HTML conversion. The goal is source-level compatibility.

\captionformat, \figureformat, and \tableformat are not yet emulated.

⚠ Not fully tested!

Please send bug reports!

Some features have not yet been tested. Please contact the author with any bug reports.

8.13 MEMOIR class

Cls memoir

⚠ captions

lwarp uses caption, which causes a warning from memoir. This is normal. Adjust captions via caption, instead of memoir.

⚠ options clash

While emulating memoir, lwarp pre-loads a number of packages (section 682.1). This can cause an options clash when the user's document later loads the same packages with options. To fix this problem, specify the options before loading lwarp:

```
\documentclass{memoir}
. . .
\PassOptionsToPackage{options_list}{package_name}
. . .
\usepackage{lwarp}
. . .
\usepackage{package_name}
```

⚠ version numbers

memoir emulates a number of packages, and declares a version date for each which often does not match the date of the corresponding freestanding package. This can cause warnings about incorrect version numbers. Since lwarp is intended to support the freestanding packages, which are often newer than the date declared by memoir, it is hoped that memoir will update and change its emulated version numbers to match.

`\label(bookmark){tag}`

`\label` accepts an optional `(bookmark)` argument, but this is ignored in HTML.

⚠ `comment`

The `comment` environment is from the comment package, and thus requires that the `\begin` and `\end` each be on its own line:

```
\begin{comment}
This is a comment.
\end{comment}
```

`\newcomment`

Comments defined with `\newcomment` use memoir's defintions, and behave as expected, where the `\begin` and `\end` do have to each be on its own line.

⚠ verbatim footnotes

`\verbfootnote` is not supported.

⚠ `\newfootnoteseries`

`\newfootnoteseries`, etc. are not supported.

⚠ page notes

lwarp loads pagenote to perform memoir's pagenote functions, but there are minor differences in `\pagenotesubhead` and related macros.

page notes with cleveref

To add support for pagenotes with cleveref, add:

```
\crefname{pagenote}{page note}{page notes}
\Crefname{pagenote}{Page note}{Page notes}
```

page note `\nameref`

Note that for print mode, `\nameref` print the section name where the page notes are declared in the text, but for HTML it prints the name where the page notes are printed.

⚠ poems

Poem numbering is not supported.

⚠ `verbatim`

The `verbatim` environment does not yet support the memoir enhancements. It is currently recommended to load and use fancyvrb instead.

⚠ glossaries

The memoir glossary system is not yet supported by *lwarpmk*. The glossaries package may be used instead, but does require the glossary entries be changed from the memoir syntax to the glossaries syntax.

⚠ `framewithtitle`, `titledframe`

The custom frame commands in the memoir manual may be emulated by placing the original defintions in the preamble inside `warpprint` environments, and then providing an HTML equivalent:

```
\begin{warpHTML}
\newcommand{\FrameTitle}[2]{%
    \textbf{#2}
}

\newenvironment{framewithtitle}[2][\FrameFirst@Lab\ (cont.)]{%
    \begin{fminipage}{\linewidth}
    \textbf{#2}
    \begin{minipage}{\linewidth}
}
```

```
{\end{minipage}\end{fminipage}}

\newcommand{\TitleFrame}[2]{%
    \par
    \textbf{#1}\par
    \fboxBlock{#2}
}

\newenvironment{titledframe}[2][\FrameFirst@Lab\ (cont.)]{%
    \par
    \textbf{#2}
    \begin{fminipage}{\linewidth}
}
{\end{fminipage}}
\end{warpHTML}
```

8.14 International languages

⚠ section and file names

If using *pdflatex* with the setting `\booltrue{FileSectionNames}`, non-ASCII text in section names can result in corrupted HTML file names. *pdflatex* may be used if setting `\boolfalse{FileSectionNames}`, in which case HTML file numbers will be generated.

For correct HTML file names, use *xelatex*, *lualatex*, or dedicated document classes/engines.

(As of this writing, this warning is only relevent to the kotex package.)

8.15 Miscellaneous packages

8.15.1 verse and memoir

Pkg verse

Cls memoir

\attrib

When using verse or memoir, always place a `\\` after each line.

The documentation for the verse and memoir packages suggest defining an `\attrib` command, which may already exist in current documents, but it will only work for print output. lwarp provides `\attribution`, which works for both print and HTML output. To combine the two so that `\attrib` is used for print and `\attribution` is used for HTML:

```
\begin{warpHTML}
\let\attrib\attribution
\end{warpHTML}
```

Len \vleftskip

Len \vleftmargini

Len \HTMLvleftskip

Len \HTMLleftmargini

These lengths are used by verse and memoir to control the left margin, and they may already be set by the user for print output. New lengths `\HTMLvleftskip` and `\HTMLleftmargini` are provided to control the margins in HTML output. These new lengths may be set by the user before any `verse` environment, and persist until they are manually changed again. One reason to change `\HTMLleftmargini` is if there is a wide `\flagverse` in use, such as the word "Chorus", in which case the value of `\HTMLleftmargini` should be set to a wide enough length to contain "Chorus". The default is wide enough for a stanza number.

⚠ spacing

Horizontal spacing relies on *pdftotext*'s ability to discern the layout (`-layout` option)

⚠ verse margin

of the text in the HTML-tagged PDF output. For some settings of `\HTMLleftmargini` or `\HTMLleftskip` the horizontal alignment may not work out exactly, in which case a label may be shifted by one space. During translation to HTML, the stanza numbers are kept out of the left margin, which would have caused *pdftotext* to shift everything over.

8.15.2 newclude package

Pkg newclude

⚠ loading

newclude modifies `\label` in a non-adaptive way, so newclude must be loaded before lwarp is loaded:

```
\documentclass{article}
. . . <font setup>
\usepackage{newclude}
\usepackage[warpHTML]{lwarp}
. . .
```

8.15.3 babel package

Pkg babel

⚠ `\CaptionSeparator`

When French is used, the caption separator is changed to a dash. To restore it to a colon, the following may be placed before lwarp is loaded:

```
\renewcommand*{\CaptionSeparator}{:~}
```

punctuation spaces

⚠ customized spacing

Also when French is used, lwarp creates fixed-width space around punctuation by patching `\FBcolonspace`, `\FBthinspace`, `\FBguillspace`, `\FBmedkern`, `\FBthickkern`, `\FBtextellipsis`, and the tilde. If the user's document also changes these parameters, the user's changes should be placed inside a `warpprint` environment so that the user's changes do not affect the HTML output.

8.15.4 polyglossia package

Pkg polyglossia

lwarp uses cleveref, which has some limitations when using polyglossia, possibly resulting in the error

```
! Undefined control sequence. . . . \__hook begindocument
```

To test compatibility, add

```
\usepackage{cleveref}
```

near the end of the preamble (as the last package to be loaded), and try to compile the print version. It may be necessary to set

```
\setdefaultlanguage{english}
```

or some other language supported by cleveref, then select other languages using `\setotherlanguages`.

Once the print version works with cleveref and polyglossia, the HTML version should work as well using lwarp.

8.15.5 todonotes and luatodonotes packages

Pkg todonotes
Pkg luatodonotes

The documentation for todonotes and luatodonotes have an example with a todo inside a caption. If this example does not work it will be necessary to move the todo outside of the caption.

8.15.6 fixme

Pkg fixme

External layouts (`\fxloadlayouts`) are not supported.

⚠ external layouts

Customized layouts are overwritten by lwarp's versions `\AtBeginDocument` in order to provide the HTML conversion. If creating a new layout, see lwarp's changes to provide similar for the new layout, inside a `warpHTML` environment.

User control is provided for setting the HTML styling of the "faces". The defaults are as follows, and may be changed in the preamble after fixme is loaded:

```
\def\FXFaceInlineHTMLStyle{font-weight:bold}
\def\FXFaceEnvHTMLStyle{font-weight:bold}
\def\FXFaceSignatureHTMLStyle{font-style:italic}
\def\FXFaceTargetHTMLStyle{font-style:italic}
```

8.15.7 acro package

⚠ formats

Define acronymn formats using `\textbf` instead of `\bfseries` etc.

8.15.8 chemfig package

If using `\polymerdelim` to add delimiters to a `\chemfig`, wrap both inside a single `lateximage`:

```
\begin{lateximage}[-chemfig-~\PackageDiagramAltText]
\chemfig{. . . }
\polymerdelim[. . . ]{. . . }
\end{lateximage}
```

8.15.9 chemformula package

⚠ chemformula with MathJax

chemformula works best without MathJax. If MathJax is used, `\displaymathother` must be used before `array`, and then `\displaymathnormal` may be used after. (The chemformula package adapts to `array`, but does not know about MathJax, and MathJax does not know about chemformula.)

While using MathJax, `\displaymathother` may also be used for other forms of display and inline math which contain chemformula expressions.

8.15.10 mhchem package

See section 405.

8.15.11 kotex package

Pkg kotex See section 8.14 regarding *pdflatex* and Korean section names.

⚠ Korean section names

9 Compiling using custom shell commands

lwarp and *lwarpmk* try to make it easy to process print and HTML compilation tasks in most situations. Depending on the operating system, command-line options, TEX engine, and lwarp options, the commands **`lwarpmk print`** and **`lwarpmk html`** are automatically set up to correctly recompile the project. These actions may be overridden using lwarp options, thus allowing the use of packages such as perltex and pythontex.

9.1 Command options

Opt `PrintLatexCmd`
Opt `HTMLLatexCmd`

The lwarp options `PrintLatexCmd` and `HTMLLatexCmd` are used to set customized commands to be executed by **`lwarpmk print`** and **`lwarpmk html`**.

`PrintLatexCmd` should be set to shell commands which take `project.tex` and generate `project.pdf`.

`HTMLLatexCmd` should be set to take `project_html.tex` and generate `project_html.pdf`. *lwarpmk* will then take `project_html.pdf` and automatically convert it and generate `project.html`.

9.2 Literal character macros

The lwarp package options are parsed by TEX, and so some characters require the use of a special macro to represent them. See table 10. `\LWRopquote` and `\LWRopseq` may be used to increase operating-system portability. `\jobname` must have `_html` appended for processing HTML. `\space` may be necessary between other macros.

⚠ macro not found

To use these macros, either kvoptions-patch must be loaded before lwarp:

```
\usepackage{kvoptions-patch}
\usepackage[
    PrintLatexCmd={ ... } ,
    HTMLLatexCmd={ ... }
]{lwarp}
```

Table 10: Literal character macros

Character	Macro	Comment
%	\LWRpercent	
$	\LWRdollar	
&	\LWRamp	
%	\LWRhash	
\	\LWRbackslash	
' or "	\LWRopquote	Depends on the operating system.
& or &&	\LWRopseq	Depends on the operating system.
(space)	\space	Forces an extra space.
(jobname)	\jobname	Without file extension.

or \lwarpsetup must be used to set PrintLatexCmd and HTMLLatexCmd:

```
\usepackage[...]{lwarp}
\lwarpsetup{
  PrintLatexCmd=
      {
          latex tm \LWRopseq
          dvips -o tm-pics.ps tm.dvi \LWRopseq
          ps2pdf tm-pics.ps \LWRopseq
          pdflatex tm.tex
      } ,
  HTMLLatexCmd=
      {
          latex tm_html \LWRopseq
          dvips -o tm_html-pics.ps tm_html.dvi \LWRopseq
          ps2pdf tm_html-pics.ps \LWRopseq
          pdflatex tm_html.tex
      }
}
```

9.3 *latexmk*

Prog latexmk If *latexmk* is used for a project, it may be easiest to continue using it.

latexmk project.tex would create project.pdf as normal.

latexmk project_html.tex would create project_html.pdf, then

lwarpmk pdftohtml project_html.pdf would take project_html.pdf and convert it to project.html.

Pkg sagetex *latexmk* may simplify the use of packages such as sagetex.

9.4 perltex package

Pkg perltex The lwarp package option settings to use perltex would be similar to:

```
\usepackage[
  . . .
  PrintLatexCmd={perltex -latex=pdflatex project.tex} ,
  HTMLLatexCmd={perltex -latex=pdflatex project_html.tex} ,
  . . .
]{lwarp}
```

⚠ "impure" math Place perltex math expressions between `\displaymathother` and `\displaymathnormal`, or `\inlinemathother` and `\inlinemathnormal`. See section 8.7.9.

9.5 pythontex package

Pkg pythontex An example using pythontex:

```
\usepackage[
  . . .
  PrintLatexCmd={
    pdflatex project.tex \LWRopseq
    pythontex project \LWRopseq
    pdflatex project.tex
  } ,
  HTMLLatexCmd={
    pdflatex project_html.tex \LWRopseq
    pythontex project_html \LWRopseq
    pdflatex project_html.tex
  } ,
  . . .
]{lwarp}
```

Another possibility is to use *latexmk*, placing the **`latexmk . . .`** commands in the `PrintLatexCmd` and `HTMLLatexCmd` options. While using these options, the lwarp option `latexmk` would not be used.

⚠ "impure" math
⚠ HTML look-alike

No attempt has yet been made to make pythontex robust with HTML output. Some math objects must be surrounded by `\displaymathother` … `\displaymathnormal`, or `\inlinemathother` … `\inlinemathnormal`. Displays of code may have to be enclosed inside a `lateximage` environment to prevent <, > and similar from being interpreted by the browser as HTML entities.

9.6 Other packages

Pkg sympytex
Pkg rterface

Other packages such as sympytex and rterface would be set up similar to pythontex, and the same warnings would apply.

9.7 *make* program

Prog make

To use lwarp with the *make* program, have the `makefile` take `project.tex` and generate the print version `project.pdf`, as normal. `\usepackage{lwarp}` must be used, and it generates `lwarpmk.conf` when the print version is created.

To generate HTML, first have `project_html.tex` be compiled to generate `project_html.pdf`. This must be in PDF format. Finally, have `project_html.pdf` be converted to HTML using **`lwarpmk pdftohtml project_html.pdf`**, and convert SVG math with **`lwarpmk limages`**.

9.8 UTF-8 locale

⚠ UTF-8 locale

lwarpmk uses the *texlua* program, which sets the "locale" to "C", including for external operating-system calls such as when executing **`lwarpmk html`**. In some cases, an external program called from the user's document may require the use of a UTF-8 "locale". For UNIX-related operating systems, it may be required to use lwarp's custom compilation options to add a locale change:

```
\usepackage{lwarp}[
  PrintLatexCmd={
    env LC_CTYPE=en_US.UTF-8
      xelatex -shell-escape project.tex
  }
  HTMLLatexCmd={
    env LC_CTYPE=en_US.UTF-8
      xelatex -shell-escape project_html.tex
  }
]
```

Pkg ditaa

The only example seen so far where this is required is the ditaa package, where the locale change allows the use of UTF-8 with XeLaTeX and ditaa. To use LuaLaTeX instead, the locale change would have to be made inside the ditaa package where its calls the *ditaa* program.

10 EPUB conversion

lwarp does not produce EPUB documents, but it may be told to modify its HTML output to greatly assist in the conversion. An external program may then be used to finish the conversion to EPUB.

<meta> author

To assign the author's name for regular lwarp HTML files, and also for the EPUB, use `\HTMLAuthor {⟨name⟩}`. This assigns the name to the `<meta>` author element. It may be set empty, and it defaults to `\theauthor`.

A special boolean is provided to simplify the process of converting lwarp HTML output to EPUB:

`FormatEPUB`

Bool `FormatEPUB`
Default: `false`

`FormatEPUB` changes HTML output for easy EPUB conversion via an external program. Removes per-file headers, footers, and nav. Adds footnotes per chapter/section.

To help convert lwarp HTML output to EPUB, add

```
\booltrue{FormatEPUB}
```

to the project's source preamble after `\usepackage{lwarp}`. The EPUB version of the document cannot co-exist with the regular HTML version, so

Enter ⇒ **`lwarpmk cleanall`**

Enter ⇒ **`lwarpmk html`**

Enter ⇒ **`lwarpmk limages`**

to recompile with the `FormatEPUB` boolean turned on. Several changes are then made to the HTML output:

- Headers, footers, and navigation are removed at file splits.
- Any accumulated footnotes are printed at the bottom of each section.

Calibre

The resulting files will be ready to be loaded into an EPUB conversion program, such as the open-source program *Calibre* (`https://calibre-ebook.com/`).

⚠ search order

The EPUB conversion program must know what order the files are included. For lwarp projects, set the EPUB conversion software to do a breadth-first search of the files. For *Calibre*, this option is found in

Preferences → Plugins → File type plugins → HTML to Zip

⚠ encoding

Check the box Add linked files in breadth first order. Set the document encoding as `utf-8`, which is what lwarp generates for HTML, even if the original printed document uses some other encoding.

⚠ section breaks

The EPUB-conversion program must also know where the section breaks are located. For a list of lwarp's section headings, see table 12. For example, an `article` class document would break at `\section`, which is mapped to HTML heading level <h4>, whereas a book class document would break at `\chapter`, which is HTML heading level <h3>. For *Calibre*, this option is found in

> **Preferences → Conversion (Common Options) → Structure Detection → Detect chapters at (XPath expression)**

Select the "magic wand" to the right of this entry box, and set the first entry

> **Match HTML tags with tag name:**

to "h4". (Or "h3" for document classes with `\chapters`.) The Detect chapters at field should then show

> **//h:h4** — or — **//h:h3**

This option is also available on the main tool bar at the Convert books button.

Once these settings have been made, the lwarp-generated HTML files may be loaded by *Calibre*, and then converted to an EPUB.

MathJax support

MathJax may be used in EPUB documents. Some e-readers include MathJax, but any given reader may or may not have a recent version, and may or may not include extensions such as support for siunitx.

lwarp adds some modifications to MathML to support equations numbered by chapter. These modifications may not be compatible with the e-reader's version of MathJax, so lwarp requests that a known version be loaded instead. In some cases chapter numbering of equations still doesn't work.

Until math support in EPUB documents is improved, it is recommended to use SVG images instead of MathJax, especially for equations numbered by chapter, or where siunitx support is important.

11 Word-processor conversion

lwarp may be told to modify its HTML output to make it easier to import the HTML document into a word processor. At the time of this writing, it seems that LibreOffice works best at preserving table layout, but it still has some limitations, such as an inability to automatically assign figure and table frames and captions according to user-selected HTML classes. lwarp provides some assistance in locating these frame boundaries, as shown below.

11.1 Activating word-processor conversion

A special boolean is provided to simplify the process of converting lwarp HTML output to EPUB:

`FormatWP`

Bool `FormatWP`
Default: `false`

Changes HTML output for easier conversion by a word processor. Removes headers and nav, prints footnotes per section, and also forces single-file output and turns off HTML debug comments. Additionally, honors the booleans `WPMarkFloats`, `WPMarkMinipages`, `WPMarkTOC`, and `WPMarkLOFT`.

To help modify lwarp HTML output for easier import to a word processor, add

```
\booltrue{FormatWP}
```

to the project's source preamble after lwarp is loaded. The following changes are then made to the HTML output:

formatting adjustments

- If using a class without chapters, `\section` and lower are shifted up in level for the HTML heading tags. The CSS has not been changed, so the section heading formats will not match the normal HTML output, but when imported to *LibreOffice Writer* the higher section headings will import as **Heading 1** for the title, **Heading 2** for `\section`, etc.
- Headers, footers, and navigation are removed at file splits.
- Any accumulated footnotes are printed at the bottom of each section.
- Forces single-file output.
- Turns off HTML debugging comments. These are comments appearing inside the HTML code, marking the opening/closing of sections and `<div>`s, but they are no longer useful when the document has been imported into a word processor.
- An additional `<div>` with an `id` encapsulates each float and minipage, which on import into *LibreOffice Writer* causes a thin frame to appear around the text block for each.
- Float captions are given an explicit italic formatting.

- Tabular rule borders are made explicit for *LibreOffice Writer*. LibreOffice displays a light border around each cell while editing, even those which have no border when printed, and lwarp also uses a light border for thin rules, so it will be best to judge the results using the print preview instead of while editing in LibreOffice.
- `\includegraphics` and SVG math width and height are made explicit for LibreOffice.
- `\hspace` is approximated by a number of `\quad`s, and rules are approximated by a number of underscores.
- Explicit HTML styles are given to:
  - `\textsc`, etc.
  - `\underline`, soul and ulem markup.
  - `center`, `flushleft`, `flushright`.
  - `\marginpar`, keyfloat, sidenotes, floatflt, and wrapfig.
  - fancybox `\shadowbox`, etc.
  - The LaTeX and TeX logos.
- Honors several booleans:

  WPMarkFloats: Marks the begin and end of floats.

  WPMarkMinipages: Marks the begin and end of minipages.

  WPMarkTOC: Marks the location of the Table of Contents.

  WPMarkLOFT: Marks the locations of the List of Figures/Tables.

  WPMarkMath: Prints LaTeX math instead of using images.

  WPTitleHeading: Adjusts title and section headings.

  Several of these may be used to add markers to the HTML text which help determine where to adjust the word processor document after import.

11.2 Additional modifications

`WPMarkFloats`

Bool `WPMarkFloats`
Default: `false`

Adds

```
=== begin table ===
. . .
=== end ===
```

or

```
=== begin figure ===
. . .
=== end ===
```

around floats while formatting for word processors. This helps identify boundaries of floats to be manually converted to word-processor frames and captions.

WPMarkMinipages

Bool WPMarkMinipages
Default: false

Adds

```
=== begin minipage ===
. . .
=== end minipage ===
```

around minipages while formatting for word processors. This helps identify boundaries of minipages to be manually converted to word-processor frames.

WPMarkTOC

Bool WPMarkTOC
Default: true

While formatting for word processors, adds

```
=== table of contents ===
```

where the Table of Contents would have been. This helps identify where to insert the actual TOC.

If set `false`*, the actual* TOC *is printed instead.*

WPMarkLOFT

Bool WPMarkLOFT
Default: false

While formatting for word processors, adds

```
=== list of figures ===    and/or
=== list of tables ===
```

where each of these lists would have been. This helps identify where to insert the actual lists.

If set `false`*, the actual lists are printed instead.*

WPMarkMath

siunitx
Bool WPMarkMath
Default: false
Prog TeXMaths

While formatting for word processors, prints math as LaTeX code instead of creating SVG images or MathJax. This is useful for cut/paste into the *LibreOffice Writer TeXMaths* extension.

When using the siunitx package, enter

```
\usepackage{siunitx}
```

in the *TeXMaths* preamble. Equation numbering is problematic for $\mathcal{AMS}$ math environments.

WPTitleHeading

Table 11: Section HTML headings for word-processor conversion

	HTML headings*			
	With \chapter		Without \chapter	
	WPTitleHeading		WPTitleHeading	
Section	true	false	true	false
Title	<h1>	plain	<h1>	plain
\book				
\part	<h2>	<h1>	<h2>	<h1>
\chapter	<h3>	<h2>	—	—
\section	<h4>	<h3>	<h3>	<h2>
\subsection	<h5>	<h4>	<h4>	<h3>
\paragraph	<h6>	<h5>	<h5>	<h4>
\subparagraph		<h6>	<h6>	<h5>

* For default depths when not FormatWP, see table 12 on page 203.

Bool WPTitleHeading
Default: false
section headings

While formatting for word processors, true sets the document title to <h1>, which is expected for HTML documents, but also causes the lower-level section headings to start at **Heading 2** when imported into LibreOffice. Set to false to cause the title to be plain text, and the section headings to begin at **Heading 1**.

See table 11 on page 187.

11.3 Recommendations

TOC, LOF, LOT

For use with *LibreOffice Writer*, it is recommended to:

1. Set \booltrue{FormatWP}
2. Set \booltrue{WPMarkTOC} and \boolfalse{WPMarkLOFT}
3. Use lwarp to generate the HTML document.
4. Copy/paste from the HTML document into an empty *LibreOffice Writer* document.
5. Manually insert a LibreOffice TOC in the LibreOffice document.
6. Manually add frames around each float, adding a caption which is cut/pasted from each float's simulated caption.
7. Manually create cross references.

This process yields a document with an actual LibreOffice Table of Contents, but a simulated List of Figures and List of Tables.

siunitx For siunitx, remember to adjust the preamble as mentioned above.

LO view border options LibreOffice has options in the **View** menu to turn on/off the display of thin borders around table cells and text objects.

11.4 Limitations

Floats and captions are not explicitly converted to LibreOffice floats with their own captions. Floats are surrounded by a thin frame in the LibreOffice editor, and may be marked with `WPMarkFloats`, but are not given a proper LibreOffice object frame. Captions are given an explicit italic formatting, but not a proper LibreOffice paragraph style.

Cross references are not actual LibreOffice linked cross references.

The List of Figures and List of Tables are not linked. The pasted pseudo LOF and LOT match the numbering of the LaTeX and HTML versions.

Equation numbering is not automatic, but the equation numbers in SVG math will match the LaTeX and HTML output. SVG math is recommended when using the $\mathcal{AMS}$ environments, which may have multiple numbered equations per object.

As of when last checked, LibreOffice ignores the following:

- Minipage alignment.
- Tabular cell vertical alignment.
- Image rotation and scaling.
- Rounded border corners, which are also used by:
  - `\textcircled`
  - booktabs trim
- `\hspace` and rules, also used by algorithmic.
- Coloring of text decorations, used by soul and ulem.
- Overline text decoration, used by romanbar.

LibreOffice also has limitations with frames and backgrounds:

- Multiple lines in an object are framed individually instead of as a whole.
- Nested frames are not handled correctly.
- Images inside boxes are not framed correctly.
- Spans with background colors and frames are not displayed correctly.

12 Modifying lwarp

locating something

To quickly find the source for a package in `lwarp.dtx`, search for `*packagename`, such as `*siunitx`.

Likewise, to quickly find the source for a file in `lwarp.dtx`, search for `*filename`, such as `*lwarp.css`.

Purely text-based packages probably will work as-is when generating HTML.

Look to existing code for ideas on how to expand into new code.

image of TEX output

An environment may be converted to a `lateximage` then displayed with an image of the resulting LaTeX output. See section 93 for an example of the `picture` environment.

css classes

To create a custom HTML block or inline CSS class, see section 52.10.

print/HTML macros

To create print and HTML versions of the same macro or environment, see section 36.

⚠ TEX boxes

Any TeX boxes must be undone, as SVG math or `lateximages` require `\newpage`, which will not work in a TeX box.

12.1 Creating a development system

The following creates a local development system for lwarp on a TeXLive system in a UNIX-like environment. Doing so allows anything requesting lwarp to use the development version instead of whichever version is installed in TeXLive.

Create a development directory:

Place into this directory `lwarp.dtx` and `lwarp.ins`.

To create `lwarp.sty`, execute

Enter ⇒ **`pdflatex lwarp.ins`**

which creates `lwarp.sty` and several hundred additional `lwarp-*.sty` files for the various packages which are supported.

To create the initial documentation `lwarp.pdf`, execute

Enter ⇒ **`pdflatex lwarp.dtx`**

To make the development files visible to other projects:

Create the directory

`/usr/local/texlive/texmf-local/tex/latex/local/lwarp`

Inside this directory, create the file `update`, containing:

```
rm lwarp-*.sty
ln -s /path_to_dev_directory/lwarp*.sty .
ln -s /path_to_dev_directory/lwarp_baseline_marker.png .
ln -s /path_to_dev_directory/lwarp_baseline_marker.eps .
mktexlsr
```

Run ./update now, and whenever a new lwarp-* package is added.

To make the development version of *lwarpmk* visible to other projects:

```
cd /opt
ln -s /usr/local/texlive/texmf-local/bin/x86_64-linux texbin_local
cd texbin_local
ln -s ../../scripts/lwarp/lwarpmk.lua lwarpmk
cd /usr/local/texlive/texmf-local/scripts/
mkdir lwarp
cd lwarp
ln -s /path_to_dev_directory/lwarpmk.lua lwarpmk
```

Verify that the correct version is found with

Enter ⇒ **`which lwarpmk`**

To make the local versions visible to the shell:

Paths must be set by the shell startup, such as in `.bashrc` and `.cshrc`:

In `.bashrc`:

```
PATH=/opt/texbin_local:/opt/texbin:$PATH
```

In `.cshrc`:

```
setenv PATH ${HOME}/bin:/opt/texbin_local:/opt/texbin:${PATH}
```

To fully compile the lwarp documentation and indexes:

```
pdflatex lwarp.ins
pdflatex lwarp.dtx
pdflatex lwarp.dtx                              <if necessary>
makeindex -s gglo.ist -o lwarp.gls lwarp.glo      <indexes>
splitindex lwarp.idx - -s gind.ist
pdflatex lwarp.dtx
pdflatex lwarp.dtx                              <if necessary>
makeindex -s gglo.ist -o lwarp.gls lwarp.glo      <indexes>
splitindex lwarp.idx - -s gind.ist                  <again>
pdflatex lwarp.dtx
pdflatex lwarp.dtx                              <if necessary>
```

(The second round of index processing is required to fully resolve the final Index of Indexes.)

To make it easier to update the documentation after a minor change, it is useful to create a command script called `make_index`, containing:

```
makeindex -s gglo.ist -o lwarp.gls lwarp.glo
splitindex lwarp.idx -- -s gind.ist
```

⚠ references

Note that Index of Indexes and the cross-references to the indexes may not be correct until the above has been accomplished.

12.2 Modifying a package for lwarp

If a class loads additional packages, it will be required to modify the class for lwarp, since lwarp must be loaded before most other packages.

To work with lwarp, a class must first set up anything which replicates the functions of the basic LaTeX classes, load any required fonts, then load lwarp, then finally load and adjust any other required packages.

When creating HTML, lwarp redefines the `\usepackage` and `\RequirePackage` macros such that it first looks to see if a `lwarp-<packagename>.sty` version exists. If so, the lwarp version is used instead. This modular system allows users to create their own versions of packages for lwarp to use for HTML, simply by creating a new package with a `lwarp-` prefix. If placed in the local directory along with the source code, it will be seen by that project alone. If placed alongside the other `lwarp-` packages where TeX can see it, then the user's new package will be seen by any documents using lwarp. (Remember `mktexlsr` or `texhash`.)

An `lwarp-<packagename>.sty` package is only used during HTML generation. Its purpose is to pretend to be the original package, while modify anything necessary to create a successful HTML conversion. For many packages it is sufficient to simply provide nullified macros, lengths, counters, etc. for anything which the original package does, while passing the raw text on to be typeset. See the pre-existing `lwarp-` packages for examples.

Anything the user might expect of the original package must be replaced or emulated by the new `lwarp-` package, including package options, user-adjustable counters, lengths, and booleans, and conditional behaviors. In many of these packages, most of the new definitions have a "local" prefix according to the package name, and `@` characters inside the name, which hides these names from the user. In most cases these macros will not need to be emulated for HTML output. Only the "user-facing" macros need to be nullified or emulated.

Each `lwarp-*` package should first call either of:

```
\LWR@ProvidesPackageDrop
  — or —
\LWR@ProvidesPackagePass
```

If "`Drop`"ped, the original print-version package is ignored, and only the `lwarp-` version is used. Use this where the original print version is useless for HTML. If "`Pass`"ed, the original package is loaded first, with the user-supplied options, then the `lwarp-` version continues loading as well. See section 451 (ntheorem) for an example of selectively disabling user options for a package. Use this when HTML output only requires some modifications of the original package. For a case where the original package is usable without changes, there is no need to create a `lwarp-` version.

12.2.1 Adding a package to the lwarp.dtx file

When adding a package to `lwarp.dtx` for permanent inclusing in lwarp, provide the `lwarp-<packagename>` code in `lwarp.dtx`, add its entry into `lwarp.ins`, and also remember to add

```
\LWR@loadafter{<packagename>}
```

to `lwarp.dtx` in section 20.1. This causes lwarp to stop with an error if packagename is loaded before lwarp. Finally, add an entry in table 2, Supported packages and features, and also the Updates section.

12.3 Modifying a class for lwarp

If a class loads additional packages, it will be required to modify the class for lwarp, since lwarp must be loaded before most other packages.

To work with lwarp, a class must first set up anything which replicates the functions of the basic LaTeX classes, load any required fonts, then load lwarp, then finally load and adjust any other required packages.

12.4 Testing lwarp

When changes have been made, test the print output before testing the HTML. The print output compiles faster, and any errors in the printed version will be easier to figure out than the HTML version.

Remember that the configuration files are only rewritten when compiling the printed version of the document.

When changing the source to *lwarpmk* or a CSS file in `lwarp.dtx`:

1. Change the source in `lwarp.dtx`.
2. `pdflatex lwarp.ins`
3. `pdflatex lwarp.dtx`
4. If modifying *lwarpmk* the new version should now be active.
5. If modifying CSS files:
   (a) For the document, `lwarpmk print` to update the CSS files in the project.
   (b) Reload the HTML document to see the effect of the new CSS files.

Sometimes it is worth checking the `<project>_html.pdf` file, which is the PDF containing HTML tags. Also, `<project>_html.html` has the text conversion of these tags, before the file is split into individual HTML files.

It is also worth checking the browser's tools for verifying the correctness of HTML and CSS code.

12.5 Modifying *lwarpmk*

Prog `lwarpmk`
File `lwarpmk.lua`

In most installations, `lwarpmk.lua` is an executable file located somewhere the operating

system knows about, and it is called by typing **lwarpmk** into a terminal.

A project-local copy of `lwarpmk.lua` may be generated, modified, and then used to compile documents:

1. Add the `lwarpmk` option to the lwarp package.
2. Recompile the printed version of the document. The `lwarpmk` option causes lwarp to create a local copy of `lwarpmk.lua`
3. The `lwarpmk` option may now be removed from the lwarp package.
4. Copy and rename `lwarpmk.lua` to a new file such as `mymake.lua`.
5. Modify `mymake.lua` as desired.
6. If necessary, make `mymake.lua` executable.
7. Use `mymake.lua` instead of `lwarpmk.lua`.

13 Troubleshooting

13.1 lwarp package error conditions and warnings

lwarp tests for a number of error conditions and prints appropriate warnings. The following is a summary of these conditions.

13.1.1 Configuration file `lwarpmk.conf`

File does not exist: The configuration file must exist for lwarpmk.

Incorrect `Unix`/`Windows` selection: The operating system which was detected by lwarp. So far only `Unix` and `Windows` are supported.

Incorrect delimiter characters. Older versions of *lwarpmk* used a different delimiter.

Source name is set to `lwarp`: lwarp has recently been recompiled in this directory, which overwrote the project's configuration files. This also occurs if *lwarpmk* is executed in lwarp's source directory.

Incorrect operating system: The configuratio file was set for a different operating system, perhaps due to sharing in a collaborative project.

Outdated configuration files: lwarp has been updated since this projects was last compiled. If there appears to be a valid print command in the file, lwarpmk displays this to instruct the user how to recompile the print version, which then updates the configuration files.

The designated source file does not exist: For whatever reason…

Unknown engine: lwarp cannot determing which engine is being used. Supported are DVI LaTeX, PDF LaTeX, XeLaTeX, LuaLaTeX, and upLaTeX.

13.1.2 Image generation with `lwarpmk limages`

"Wait a moment for the images to complete before reloading page.":

Images are generated by background tasks. If the document is reloaded before these tasks are complete, some images may not yet be generated. *lwarpmk* tries to wait for background tasks to complete before exiting.

HTML version does not exist: Images are extracted from the HTML version, which must be compiled before images are generated.

`*-images.txt` does not exist: This file tells which images to extract from the HTML file. If the file does not exist, it may be that no SVG math or `latexi`mages were used. If so, **`lwarpmk limages`** is not necessary.

Cross references are not correct: The document must have up-to-date cross references to locate the images to extract. A number of conditions may cause incorrect cross references.

"WARNING: Images will be incorrect.": An image reference was not found. Recompile.

`lwarpmk epstopdf *` or `lwarpmk pdftosvg *`: Errors if filenames are not found.

13.1.3 Default bitmapped font

lwarp requires the use of a vector font. If lwarp detects that the document uses the default Computer Modern font, and the cm-super package is not installed, it is assumed that the font is bitmapped. An error is generated, along with the recommendation to install cm-super or use lmodern.

13.1.4 Packages

Loaded before lwarp: Some packages and classes must be loaded before lwarp. These include input and font encoding, morewrites and newclude, and a number of CJK-related packages and classes.

Loaded after lwarp: Most packages which are modified by lwarp must be loaded after lwarp.

Loaded never: Some packages do not work with lwarp. An error is generated, along with a list of alternatives to consider.

Specific packages: Some packages enforce a specific load order vs. certain other packages.

Patching error: lwarp tries to patch some packages using xpatch. If the original package has been updated more recently than lwarp, a patch may not work. It may be necessary to use an older version of the package until lwarp is updated.

longtable: lwarp's longtable package issues detailed error messages regarding the use of the table headers and footers.

polyglossia: If used, an informative message is printed to instruct the user to be sure to set a language, without which an error will occur.

babel or polyglossia: An informative message is printed to note that not all langauges are supported by cleveref.

13.1.5 Compiling

`SideTOCDepth` < `FileDepth`: A warning is displayed if these counters are set such that the sideToc will not be able to access all pages of the website.

Filenames: lwarp may generate file names from section names. While doing so, the filenames are simplified, and special characters and math are removed. If this process generates a duplicate filename, and error is generated, describing the filename and which section name generated it. A warning is issued if dollar-delimited math is used. Parenthesis-delimited math is recommended instead.

⚠ HTML corrupted **Multirow:** When `\multirow` or `\multicolrow` are used, `\mrowcell` or `\mcolrowcell` must be placed in the appropriate cells to avoid corrupted HTML output.

(width,height) missing a comma: `\makebox` and `\framebox` can accept a parenthesis-delimited width and height, which must be separated by a comma.

"Load graphicx or graphics for improved SVG math baselines.": SVG math sizing and baselines are improved if either of these packages are used.

"Load graphicx or graphics for improved XeTeX logo.": If these packages are loaded, the XeLaTeX logo can use the reversed "E".

"It is recommended to use `[width=xx\linewidth]` instead of `[scale=yy]` ": Browser support of `scale` does not have the same effect as in LaTeX.

13.2 Using the lwarp package

The following address problems which may occur, and possible solutions to each.

Also see:
Section 7.11: Commands to be placed into the `warpprint` environment
Section 8: Special cases and limitations

⚠ HTML corrupted **Text is not converting correctly / corrupted HTML tags:**

- Font-related UTF-8 information must be embedded in the PDF file. See section 7.4 regarding bitmapped vs. vector fonts.
- See section 8.2.1 regarding HTML entities and the characters &, <, and >.

⚠ dotlessj **Dotless j (`\j`):** See section 7.4 regarding cmap, mmap.

Undefined HTML settings:

- See the warning regarding the placement of the HTML settings at section 7.6.

Tabular problems: See section 8.10.1.

Obscure error messages:

Print first: Be sure that a print version of the document compiles and that your document's LaTeX code is correct, before attempting to generate an HTML version.

⚠ `warpHTML`, `warpprint`, `warpMathJax`, `warpall` **`\end{warpHTML}, \end{warpprint}, \end{warpall}, \end{warpMathJax}:** Each of these must be without any other characters on the same line.

"`Runaway argument? File ended while scanning use of \next`: Don't use `warpHTML`, `warpprint`, `warpall`, or `warpMathJax` inside itself.

Options clash: If using memoir, see section 8.13.

"Missing `\begin{document}`.": Some packages require that their options be specified before lwarp is loaded, or via the package's setup macro, especially if these options include the use of braces. See section 8.1.

"No room for a new \write.": Before `\usepackage{lwarp}`, add:

```
\usepackage{morewrites}
\morewritessetup{allocate=10}
```

"! TeX capacity exceeded, sorry [text input levels=15].": Packages were nested too many levels deep. Locate the file `texmf.cnf` for your distribution, and add the line

```
max_in_open = 30
```

"Missing $ inserted.": If using a filename or URL in a footnote or `\item`, escape underscores with `\_`.

"Label(s) may have changed. Rerun to get cross-references right.":

This warning may repeat endlessly if a math expression is used in a caption. Simple math expressions such as $X=1$ may be replaced with

```
\textit{X}\,=\,1
```

"Temporary page! LaTeX was unable to guess the total number of pages ...": Harmless. Recompile the document one more time.

"Leaders not followed by proper glue":
This can be caused by a missing `l@<floattype>` or `l@<sectiontype>` definition. See lwarp's definitions for examples.

"Improper \prevdepth": `lateximages` and SVG math require `\newpage`, which cannot work inside TEX boxes or `\ensuremath`. Anything using `\newsavebox`, `\newbox`, `lrbox`, `\savebox`, `\hbox`, `\vbox`, `\usebox`, `\sbox`, etc., must be modified to work without box commands.

If you find something using `\ensuremath`, have it temporarily set:

```
\LetLtxMacro\@ensuredmath\LWR@origensuredmath
```

inside a group first.

`LWR@texboxdepth`

As a stop-gap measure, you may wish to try incrementing the counter `LWR@texboxdepth` before the problematic macro, and then decrementing it after. Doing so tells lwarp to avoid using a `\newpage` inside the macro, which may avoid this error.

⚠ macros in section, table, figure names

Also, custom macros which appear inside a section, figure, or table name should be made robust since they appear inside the `.toc`, `.lof`, or `.lot` files. Use `\newrobustcmd` or `\robustify` from etoolbox, xparse, etc.

⚠ BibTeX

If using BibTeX, see section 8.6.9.

⚠ polyglossia

"! Undefined control sequence. . . . __hook begindocument":
See section 8.15.4 if using polyglossia.

⚠ custom macros for environments

"\begin{equation} ended by \end{document}": Do not use custom macros such as `\beq` and `\eeq` to replace

```
\begin{equation}
. . .
\end{equation}
```

⚠ `\LWR@formatted`

"Misplaced \omit": If using `\LWR@formatted` to define new macros for print and HTML modes, see section 36 regarding `\LWR@expandableformatted`.

"Token not allowed in a PDF string": This hyperref warning appears while creating the print-mode document, not HTML. A low-level macro is being used in a section name which appears in the PDF bookmarks. hyperref removes this macro from the bookmark, and warns of doing so. To avoid this warning, use `\pdfstringdefDisableCommands` in the preamble to define simplified replacement macros for each, or use `\texorpdfstring` in the `\section` or related macro to declare what to use for the TEX text, v.s. the PDF bookmark. See the hyperref manual.

⚠ quote character

"Command \textquoteright invalid in math mode": This can occur when the document source has math containing the slanted quote ' character, instead of using the upright quote ' character.

⚠ "impure" math objects

Complicated objects inside math: Some objects, such as Ti*k*z, may not compile in lwarp's normal math emulation. Insert

`\displaymathother` — *or* — `\inlinemathother`

before the math, and then

`\displaymathnormal` — *or* — `\inlinemathnormal`

when displaying "normal" math. See section 8.7.9.

Slow compliation of math objects: Complicated math objects can also cause problems with `alt` tags, resulting in very slow compilation, large `alt` tags, and possible crashes. Use `\inlinemathother` ... `\inlinemathnormal` or `\displaymathother` ... `\displaymathnormal` around the math expression.

⚠ MathJax

Incorrect MathJax: Some objects do not convert to MathJax. Use `\displaymathother` before these objects, then `\displaymathnormal` to return to "normal" display math. See section 8.7.9.

Missing sections: See section 7.6 regarding the `FileDepth` and `SideTOCDepth` counters, and the use of `\tableofcontents` in the home page.

Misnumbered footnotes from section headings: See section 8.5.4.

Missing HTML files:

- See the warning regarding changes to the HTML settings at section 7.6.
- Ensure that the filenames are unique after math and short words are removed. See `FileSectionNames` at section 7.6.

Missing / incorrect cross-references:

- Use `lwarpmk again` followed by `lwarpmk html` or `lwarpmk print` to compile the document one more time.

labels

⚠ label characters

`\nameref`

⚠ empty link

- Labels with special characters may be a problem. It is best to stick with alphanumeric, hyphen, underscore, and perhaps the colon (if not French).

  `\nameref` refers to the most recently-used section where the `\label` was defined. If no section has been defined before the `\label`, the link will be empty. Index entries also use `\nameref` and have the same limitation.

⚠ cleveref page numbers

- cleveref and varioref are supported, but printed page numbers do not map to HTML, so a section name or a text phrase are used for `\cpageref` and `\cpagerefrange`. This phrase includes `\cpagerefFor`, which defaults to "for".

Ex:
```
\cpageref{tab:first,tab:second}
```
in html becomes:
"pages **for** table 4.1 and **for** table 4.2"
See `\cpagerefFor` at page 748 to redefine the message which is printed for page number references.

BibTeX errors with `\etalchar`: See section 8.6.9.

Malformed URLs: Do not use the `%` character between arguments of `\hyperref`, etc., as this character is among those which is neutralized for inclusion in HTML URLs.

Em-dashes or En-dashes in listing captions and titles:

Use XeLaTeX or LuaLaTeX.

Floats out of sequence:

Mixed "Here" and floating: Floats [H]ere and regular floats may become out of order. `\clearpage` if necessary.

Caption setup: With `\captionsetup` set the positions for the captions `above` or `below` to match their use in the source code.

Images are appearing in strange places:

- Enter **`lwarpmk limages`** to refresh the `lateximage` images.

SVG images:

⚠ adding/removing

When a math expression, `picture`, or Ti*k*z environment is added or removed, the SVG images must be re-created by entering **`lwarpmk limages`** to maintain the proper image-file associations. Inline SVG math may be hashed and thus not need to be recreated, but display math and objects such as Ti*k*z may move to new image numbers when the document is changed.

recompile first

Before attempting to create the SVG image files, *lwarpmk* verifies that the HTML version of the document exists and has correct internal image references.[16] If it is necessary to recompile the document's HTML version one more time, *lwarpmk* usually will inform the user with an error message, but there are some conditions which cannot be detected, so the user should watch for the LaTeX recompile warnings.

⚠ HTML instead of images

If HTML appears where an SVG image should be, recompile the document one more time to get the page numbers back in sync, then remake the images one more time.

⚠ page counter

Incorrect SVG images will also occur if the document changes the page counter:

```
\setcounter{page}{<value>}
```

The page counter must *not* be adjusted by the user.

⚠ Lots of files!

Expressing math as SVG images has the advantage of representing the math exactly as LaTeX would, but has the disadvantage of requiring an individual file for each math expression. For inline math, and some other objects, lwarp uses an MD5 hash on its LaTeX source to combine multiple instances of identical inline expressions into a single image file, but display math and other environments such as `picture` and Ti*k*z require one image file each. For a document with a large amount of math, see section 5.5 to use MathJax instead.

[16] This becomes important when dealing with a document containing thousands of images.

Plain-looking document:

- The document's CSS stylesheet may not be available, or may be linked incorrectly. Verify any `\CSSFilename` statements point to a valid CSS file.

⚠ HTML corrupted **Broken fragments of HTML:**

- Check the PDF file used to create HTML to see if the tags overflowed the margin. (This is why such large page size and margins are used.)

Changes do not seem to be taking effect:

- Be sure to `lwarpmk clean`, recompile, then start by reloading the home page. You may have been looking at an older version of the document. If you changed a section name, you may have been looking at the file for the old name.
- See the warning regarding changes to the HTML settings at section 7.6.
- Verify that the proper CSS is actually being used.
- The browser may compensate for some subtle changes, such as automatically generating ligatures, reflowing text, etc.

Un-matched conditional compiles:

- Verify the proper `begin`/`end` of `warpprint`, `warpHTML`, and `warpall` environments.

13.2.1 Debug tracing output

`\tracinglwarp` When `\tracinglwarp` is used, lwarp will add extra tracing messages to the `.log` file. The last several messages may help track down errors.

Place `\tracinglwarp` just after `\usepackage{lwarp}` to activate tracing.

13.3 Compiling the `lwarp.dtx` file

`lwarp_tutorial.tex`: Copy or link `lwarp_tutorial.txt` from the TDS doc directory to the `source` directory, or wherever you wish to compile the documentation. This file is included verbatim in the documentation, but is in the doc directory so that it may be found by *texdoc* and copied by the user.

Illogical error messages caused by an out-of-sync `lwarp.sty` file:

1. Delete the `lwarp.sty` file.
2. Enter **`pdflatex lwarp.ins`** to generate a new `lwarp.sty` file.
3. Enter **`pdflatex lwarp.dtx`** to recompile the `lwarp.pdf` documentation.

Un-nested environments:

Be sure to properly nest:

- `\begin{macrocode}` and `\end{macrocode}`
- `\begin{macro}` and `\end{macro}`
- `\begin{environment}` and `\end{environment}`

14 Trademarks

- TEX is a trademark of American Mathematical Society.
- Adobe® and Adobe *Framemaker*® are either registered trademarks or trademarks of Adobe Systems Incorporated in the United States and/or other countries.
- Linux® is the registered trademark of Linus Torvalds in the U.S. and other countries.
- Mac OS® is a trademark of Apple Inc.
- MadCap Flare™ is the property of MadCap Software, Inc.
- MathJax is copyright 2009 and later. The MathJax Consortium is a joint venture of the American Mathematical Society (AMS) and the Society for Industrial and Applied Mathematics (SIAM) to advance mathematical and scientific content on the web.
- Microsoft®, Encarta, MSN, and Windows® are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.
- UNIX® is a registered trademark of The Open Group.
- YouTube™ is trademark of Google LLC.

File 1 **lwarp.sty**

15 Implementation

This package is perhaps best described as a large collection of smaller individual technical challenges, in many cases solved through a number of ~~crude hacks~~ clever tricks. Reference sources are given for many of the solutions, and a quick internet search will provide additional possibilities.

Judgement calls were made, and are often commented. Improvements are possible. The author is open to ideas and suggestions.

Packages were patched for re-use where they provided significant functionality. Examples include xcolor with its color models and conversion to HTML color output, and siunitx which provides many number and unit-formatting options, almost all of which are available in pure-text form, and thus easily used by *pdftotext*.

Packages were emulated where their primary purpose was visual formatting which is not relevent to HTML output. For example, packages related to sectioning are already patched by numerous other packages, creating a difficult number of combinations to try to support, and yet in HTML output all of the formatting is thrown away, so these packages are merely emulated.

Packages with graphical output are allowed as-is, but must be nested inside a `lateximage` environment to preserve the graphics.

Testing has primarily been done with the Iceweasel/Firefox browser.

Table 12: Section depths and HTML headings

Section	LaTeX depth	HTML headings *
Title of the entire website		`<h1>`
(none)	-5	new for this package
book	-2	`<div class = "book">`
part	-1	`<h2>`
chapter	0	`<h3>`
section	1	`<h4>`
subsection	2	`<h5>`
subsubsection	3	`<h6>`
paragraph	4	`<span class = "paragraph">`
subparagraph	5	`<span class = "subparagraph">`
listitem	7	new for this package, used for list items

* If `FormatWP` is true, section headings may be adjusted, depending on `WPTitleHeading`. See table 11 on page 187.

16 Section depths and HTML headings

Stacks are created to track depth inside the LaTeX document structure. This depth is translated to HTML headings as shown in table 12. "Depth" here is not depth in the traditional computer-science stack-usage sense, but rather a representation of the nesting depth inside the LaTeX document structure.

When starting a new section, the program first must close out any existing sections and lists of a deeper level to keep the HTML tags nested correctly.

Support for the memoir package will require the addition of a book level, which may push the HTML headings down a step, and also cause `subsubsection` to become a `<div>` due to a limit of six HTML headings.

It is possible to use HTML5 `<section>` and `<h1>` for all levels, but this may not be well-recognized by older browsers.

Fixed levels for parts and chapters allow the CSS to remain fixed as well.

17 Source code

This is where the documented source code for lwarp begins, continuing through the following sections all the way to the change log and index at the end of this document.

The following sections document the actual implementation of the lwarp package.

line numbers The small numbers at the left end of a line refer to line numbers in the `lwarp.sty` file.

subjects Blue-colored tags in the left margin aid in quickly identifying the subject of each paragraph.

objects Black-colored tags in the left marign are used to identify programming objects such as files, packages, environments, booleans, and counters. Items without a tag are command macros. Each of these also appears in the index as individual entries, and are also listed together under “files”, “packages”, “environments”, “booleans”, and “counters”.

index entries

⚠ warnings Special warnings are marked with a warning icon.

for HTML output: Green-colored tags in the left margin show which sections of source code apply to the generation of HTML, print, or both forms of output.

for PRINT output:

for HTML & PRINT:

— lwarp source code begins on the following page —

18 Detecting the TEX engine — *pdflatex*, *lualatex*, *xelatex*

See: http://tex.stackexchange.com/a/47579.

Detects XeTeX and LuaLaTeX:

```
\RequirePackage{iftex}[2019/11/07]
\RequirePackage{ifpdf}
\RequirePackage{ifptex}

\newif\ifxetexorluatex

\ifXeTeX
    \xetexorluatextrue
\else
    \ifLuaTeX
        \xetexorluatextrue
    \else
        \xetexorluatexfalse
    \fi
\fi
```

19 Early package requirements

Pkg etoolbox Provides `\ifbool` and other functions.

Pkg xpatch Patches macros with optional arguments.

```
\RequirePackage{etoolbox}[2011/01/03]% v2.6 for \BeforeBeginEnvironment, etc.
\RequirePackage{xpatch}
```

Pkg ifplatform Provides `\ifwindows` to try to automatically detect Windows OS.

```
\RequirePackage{ifplatform}% sense op-system platform
```

Pkg letltxmacro

```
\RequirePackage{letltxmacro}
```

20 Package load order

Several packages must never be used with lwarp, others should only be loaded before lwarp, and others should only be loaded after. The lwarp core checks most of these cases. In some `lwarp-*` packages, `\LWR@loadbefore` is used to trigger an error if they are loaded after lwarp, while additional code provides necessary patches for when they are loaded before.

Packages which must be loaded after lwarp are enfoced by a large number of \LWR@loadafter statements, below. Some packages are emulated by memoir, and so these are tested by \LWR@notmemoirloadafter, which does not cause an error if memoir is used.

\LWR@checkloadfilename is used to check each filename to see if it must never be loaded, or must always be loaded before lwarp.

20.1 Tests of package load order

\LWR@loadafter {⟨*packagename*⟩} Error if this package was loaded before lwarp.

```
\newcommand*{\LWR@loadafter}[1]{%
\@ifpackageloaded{#1}
{
    \PackageError{lwarp}
        {%
            Package #1,\MessageBreak
            or one which uses #1,\MessageBreak
            must be loaded after Lwarp.\MessageBreak
            Enter 'H' for possible solutions%
        }
        {%
            Move ``\protect\usepackage{#1}'' after
            ``\protect\usepackage{lwarp}''.\MessageBreak
            Package #1 may also be loaded by something else,\MessageBreak
            which must also be moved after Lwarp.%
        }
}
{\relax}
}
```

\LWR@notmemoirloadafter {⟨*packagename*⟩} Error if not memoir class and this package was loaded before lwarp.

memoir emulates many packages, and pretends that they have already been loaded.

```
\@ifclassloaded{memoir}
{\newcommand*{\LWR@notmemoirloadafter}[1]{}}
{\LetLtxMacro\LWR@notmemoirloadafter\LWR@loadafter}
```

\LWR@notltjloadafter {⟨*packagename*⟩} Error if not a ltjs* class and this package was loaded before lwarp.

```
\LetLtxMacro\LWR@notltjloadafter\LWR@loadafter

\@ifclassloaded{ltjarticle}{\renewcommand*{\LWR@notltjloadafter}[1]{}}{}
\@ifclassloaded{ltjbook}{\renewcommand*{\LWR@notltjloadafter}[1]{}}{}
\@ifclassloaded{ltjreport}{\renewcommand*{\LWR@notltjloadafter}[1]{}}{}
\@ifclassloaded{ltjsarticle}{\renewcommand*{\LWR@notltjloadafter}[1]{}}{}
\@ifclassloaded{ltjsbook}{\renewcommand*{\LWR@notltjloadafter}[1]{}}{}
\@ifclassloaded{ltjsreport}{\renewcommand*{\LWR@notltjloadafter}[1]{}}{}
\@ifclassloaded{ltjspf}{\renewcommand*{\LWR@notltjloadafter}[1]{}}{}
\@ifclassloaded{ltjskiyou}{\renewcommand*{\LWR@notltjloadafter}[1]{}}{}
\@ifclassloaded{ltjtarticle}{\renewcommand*{\LWR@notltjloadafter}[1]{}}{}
```

```
\@ifclassloaded{ltjtbook}{\renewcommand*{\LWR@notltjloadafter}[1]{}}{}
\@ifclassloaded{ltjtreport}{\renewcommand*{\LWR@notltjloadafter}[1]{}}{}
```

`\LWR@loadbefore` {⟨*packagename*⟩} Error if this package is loaded after lwarp.

```
\newcommand*{\LWR@loadbefore}[1]{%
\@ifpackageloaded{#1}
{\relax}
{
    \PackageError{lwarp}
    {%
        Package #1 must be loaded before lwarp.\MessageBreak
        Enter 'H' for possible solutions%
    }
    {Move ``\protect\usepackage{#1}'' before ``\protect\usepackage{lwarp}''.}
}
}
```

`\LWR@checkloadbefore` {⟨*packagename*⟩}

Given `\LWR@tempone` is the package name to compare to, if package names match, error if it is loaded after lwarp.

```
\newcommand*{\LWR@checkloadbefore}[1]{%
    \ifdefstring{\LWR@tempone}{#1}{%
        \LWR@loadbefore{#1}%
    }{}%
}
```

`\LWR@loadnever` {⟨*badpackagename*⟩} {⟨*replacementpkgnames*⟩}

The first packages is not supported, so tell the user to use the second instead. Factored from `\LWR@checkloadnever` and `\LWR@earlyloadnever`.

```
\newcommand*{\LWR@loadnever}[2]{%
\PackageError{lwarp}
{%
    Package #1 is not yet supported\MessageBreak
    by lwarp's HTML conversion%
    \ifblank{#2}{}{%
        .\MessageBreak
        Package(s)\MessageBreak
        \space\space#2\MessageBreak
        may be useful instead%
    }%
}
{%
    Package #1 might conflict with lwarp in some way,\MessageBreak
    or is superceded by another package.%
    \ifblank{#2}{}{%
        \MessageBreak
        For possible alternatives, see package(s) #2.%
    }%
```

```
}
}
```

`\LWR@afterloadnever` {⟨*badpackagename*⟩} {⟨*replacementpkgnames*⟩}

Given: `\LWR@tempone` is set to the package name being tested against, if this package name is the bad packagename, suggest the replacements instead. This is used when loading packages after lwarp.

```
\newcommand*{\LWR@afterloadnever}[2]{%
    \ifdefstring{\LWR@tempone}{#1}{%
        \LWR@loadnever{#1}{#2}%
    }{}%
}
```

`\LWR@earlyloadnever` {⟨*badpackagename*⟩} {⟨*replacementpkgname*⟩}

The first package is not supported, so tell the user to use the second instead. This version checks immediately for packages which may have been loaded before lwarp.

```
\newcommand*{\LWR@earlyloadnever}[2]{%
    \@ifpackageloaded{#1}{%
        \LWR@loadnever{#1}{#2}%
    }{}%
}
```

`\LWR@earlyclassloadnever` {⟨*badclassname*⟩} {⟨*replacementclassname*⟩}

The first class is not supported, so tell the user to use the second instead. This version checks immediately for classes which may have been loaded before lwarp.

```
\newcommand*{\LWR@earlyclassloadnever}[2]{%
\@ifclassloaded{#1}{%
\PackageError{lwarp}
{%
    Class #1 is not supported\MessageBreak
    by lwarp's HTML conversion%
    \ifblank{#2}{}{%
        .\MessageBreak
        Class(es) #2 may be useful instead%
    }%
}
{%
    Class #1 might conflict with lwarp in some way,\MessageBreak
    or is superceded by another class.%
    \ifblank{#2}{}{%
        \MessageBreak
        For a possible alternative, see class(es) #2.%
    }%
}
}{\relax}%
}
```

20.2 Error for disallowed packages and classes loaded before lwarp

\LWR@checkloadnevers Checks against a list of incompatible packages.

```
\newcommand*{\LWR@checkloadnevers}{
\LWR@checkloadnever{ae}{cm-super, lmodern}
\LWR@checkloadnever{aecompl}{cm-super, lmodern}
\LWR@checkloadnever{aecc}{cm-super, lmodern}
\LWR@checkloadnever{alg}{algorithm2e, algorithmicx}
\LWR@checkloadnever{algorithmic}{algorithm2e, algorithmicx}
\LWR@checkloadnever{bitfield}{bytefield}
```

bxcjkatype is based on CJK:

```
\LWR@checkloadnever{bxcjkjatype}{upLaTeX, bxjsarticle, ujarticle, utarticle}
```

```
\LWR@checkloadnever{caption2}{caption}
% \LWR@checkloadnever{ccaption}{caption}% might be preloaded by memoir
\LWR@checkloadnever{colortab}{colortbl}
\LWR@checkloadnever{csvtools}{datatool}
\LWR@checkloadnever{doublespace}{setspace}
\LWR@checkloadnever{fancyheadings}{fancyhdr}
\LWR@checkloadnever{fncylab}{cleveref}
\LWR@checkloadnever{formula}{siunitx}
\LWR@checkloadnever{glossary}{glossaries}
```

hangul is not in TeXLive, and is not tested:

```
\LWR@checkloadnever{hangul}{kotex, xetexko, luatexko}
```

```
\LWR@checkloadnever{hyper}{hyperref}
\LWR@checkloadnever{libgreek}{libertinust1math, newtx}
\LWR@checkloadnever{newthm}{ntheorem}
\LWR@checkloadnever{pdfcprot}{microtype}
\LWR@checkloadnever{picins}{floatflt, wrapfig}
\LWR@checkloadnever{rplain}{fancyhdr}
\LWR@checkloadnever{si}{siunitx}
\LWR@checkloadnever{sistyle}{siunitx}
\LWR@checkloadnever{slashbox}{diagbox}
\LWR@checkloadnever{statex}{statex2}
\LWR@checkloadnever{t1enc}{fontenc, inputenc, inputenx}
\LWR@checkloadnever{ucs}{inputenc, inputencx}
\LWR@checkloadnever{wasysym}{textcomp, amssymb, amsfonts, mnsymbol, fdsymbol}
```

The following may one day be supported by lwarp:

```
% \LWR@checkloadnever{adjustbox}{}% req'd for menukeys
\LWR@checkloadnever{animate}{}
\LWR@checkloadnever{auto-pst-pdf}{}
\LWR@checkloadnever{auto-pst-pdf-lua}{}
\LWR@checkloadnever{algorithms}{}
\LWR@checkloadnever{arraycols}{}
\LWR@checkloadnever{beamer}{}
```

```
\LWR@checkloadnever{bidi}{}
\LWR@checkloadnever{cals}{}
\LWR@checkloadnever{cellspace}{}
\LWR@checkloadnever{cgloss4e}{}
\LWR@checkloadnever{colophon}{}
\LWR@checkloadnever{cooltooltips}{}
\LWR@checkloadnever{covington}{}
\LWR@checkloadnever{crbox}{}
\LWR@checkloadnever{decision-table}{}
\LWR@checkloadnever{dvgloss}{}
\LWR@checkloadnever{ednotes}{}
\LWR@checkloadnever{edfnotes}{}
\LWR@checkloadnever{eledform}{}
\LWR@checkloadnever{eledmac}{}
\LWR@checkloadnever{embedfile}{}
\LWR@checkloadnever{endnotes-hy}{endnotes}
\LWR@checkloadnever{expex}{}
\LWR@checkloadnever{fancytooltips}{}
\LWR@checkloadnever{fixocgx}{}
\LWR@checkloadnever{flowfram}{}
\LWR@checkloadnever{gb4e}{}
\LWR@checkloadnever{gmverse}{}
\LWR@checkloadnever{graphbox}{}
\LWR@checkloadnever{graphicxbox}{}
\LWR@checkloadnever{hvfloat}{}
\LWR@checkloadnever{inline-images}{}
\LWR@checkloadnever{isorot}{rotating}
\LWR@checkloadnever{ledmac}{}
\LWR@checkloadnever{linguex}{}
\LWR@checkloadnever{longdiv}{}
\LWR@checkloadnever{longfigure}{}
\LWR@checkloadnever{longtabu}{}
\LWR@checkloadnever{mdwenv}{}
\LWR@checkloadnever{mdwlist}{}
\LWR@checkloadnever{mdwtab}{}
\LWR@checkloadnever{navigator}{}
\LWR@checkloadnever{nccpic}{}
\LWR@checkloadnever{nccsect}{}
\LWR@checkloadnever{newvbtm}{}
\LWR@checkloadnever{ocg-p}{}
\LWR@checkloadnever{ocgtools}{}
\LWR@checkloadnever{ocgx}{}
\LWR@checkloadnever{ocgx2}{}
\LWR@checkloadnever{parrun}{}
\LWR@checkloadnever{poemscol}{}
\LWR@checkloadnever{poetry}{}
\LWR@checkloadnever{program}{}
\LWR@checkloadnever{proofread}{}
\LWR@checkloadnever{pst-pdf}{}
\LWR@checkloadnever{refstyle}{}
\LWR@checkloadnever{robustindex}{}
\LWR@checkloadnever{robustglossary}{}
\LWR@checkloadnever{semioneside}{}
\LWR@checkloadnever{slemph}{}
\LWR@checkloadnever{snotez}{sidenotes}
```

```
\LWR@checkloadnever{spacingtricks}{}
\LWR@checkloadnever{sverb}{verbatim, fancyvrb}
\LWR@checkloadnever{syntax}{}
\LWR@checkloadnever{tablists}{}
\LWR@checkloadnever{tabto}{}
\LWR@checkloadnever{tabu}{}
\LWR@checkloadnever{tabularht}{}
\LWR@checkloadnever{tabularkv}{}
\LWR@checkloadnever{thumby}{}
\LWR@checkloadnever{titles}{}
\LWR@checkloadnever{typehtml}{}
\LWR@checkloadnever{unicode-bidi}{}
\LWR@checkloadnever{vcell}{}
\LWR@checkloadnever{xhfill}{}
}
```

`\LWR@checkloadnever` {⟨*badpackagename*⟩} {⟨*replacementpkgname*⟩}

The first package is not supported, so tell the user to use the second instead.

When lwarp is first loaded, this is set to `\LWR@earlyloadnever` to check for incompatible packages which were loaded before lwarp. After lwarp is loaded, this is changed to `\LWR@afterloadnever` to check for incompatible packages during `\usepackage`.

```
\LetLtxMacro\LWR@checkloadnever\LWR@earlyloadnever
```

Now check for incompatible packages which have been loaded before lwarp:

```
\LWR@checkloadnevers
```

The older CJK and CJKutf8 only work with xeCJK:

```
\@ifpackageloaded{xeCJK}{}{
    \LWR@checkloadnever{CJK}{ctex, xeCJK}
    \LWR@checkloadnever{CJKutf8}{ctex, xeCJK}
}
```

Some classes do not work with lwarp:

```
\LWR@earlyclassloadnever{jarticle}{ujarticle}
\LWR@earlyclassloadnever{jbook}{ujbook}
\LWR@earlyclassloadnever{jreport}{ujreport}
\LWR@earlyclassloadnever{tarticle}{utarticle}
\LWR@earlyclassloadnever{tbook}{utbook}
\LWR@earlyclassloadnever{treport}{utreport}
\LWR@earlyclassloadnever{novel}{}
\LWR@earlyclassloadnever{powerdot}{}
```

20.3 Enforcing package loading after lwarp

Packages which should only be loaded after lwarp are tested here to trip an error of they have already been loaded.

The following packages must be loaded after lwarp:

```
\LWR@loadafter{2in1}
\LWR@loadafter{2up}
\LWR@loadafter{a4}
\LWR@loadafter{a4wide}
\LWR@loadafter{a5comb}
\LWR@notmemoirloadafter{abstract}
\LWR@loadafter{academicons}
\LWR@loadafter{accents}
\LWR@loadafter{accessibility}
\LWR@loadafter{accsupp}
\LWR@loadafter{acro}
\LWR@loadafter{acronym}
\LWR@loadafter{adjmulticol}
\LWR@loadafter{addlines}
\LWR@loadafter{afterpage}
\LWR@loadafter{algorithm2e}
\LWR@loadafter{algorithmicx}
\LWR@loadafter{alltt}
\LWR@loadafter{amscdx}
% \LWR@loadafter{amsmath}% may be preloaded
% \LWR@loadafter{amsthm}% may be preloaded
\LWR@loadafter{anonchap}
\LWR@loadafter{anysize}
\LWR@notmemoirloadafter{appendix}
\LWR@loadafter{ar}
\LWR@loadafter{arabicfront}
\LWR@notmemoirloadafter{array}
\LWR@loadafter{arydshln}
\LWR@loadafter{asymptote}
% \LWR@loadafter{atbegshi}% now in LaTeX core, also used by morewrites
\LWR@loadafter{attachfile}
\LWR@loadafter{attachfile2}
\LWR@loadafter{authblk}
\LWR@loadafter{authoraftertitle}% Supported as-is, but must be loaded after.
\LWR@loadafter{autobreak}
\LWR@loadafter{autonum}
\LWR@loadafter{awesomebox}
\LWR@loadafter{axessibility}
\LWR@loadafter{axodraw2}
\LWR@loadafter{backnaur}
\LWR@loadafter{backref}
\LWR@loadafter{balance}
\LWR@loadafter{bbding}
\LWR@loadafter{bigdelim}
\LWR@loadafter{bigfoot}
\LWR@loadafter{bigstrut}
\LWR@loadafter{bitpattern}
\LWR@loadafter{blowup}
\LWR@loadafter{bm}
\LWR@loadafter{booklet}
\LWR@loadafter{bookmark}
\LWR@notmemoirloadafter{booktabs}
\LWR@loadafter{bophook}
```

```
\LWR@loadafter{bounddvi}
\LWR@loadafter{boxedminipage}
\LWR@loadafter{boxedminipage2e}
\LWR@loadafter{braket}
\LWR@loadafter{breakurl}
\LWR@loadafter{breqn}
\LWR@loadafter{bsheaders}
\LWR@loadafter{bussproofs}
\LWR@loadafter{bxpapersize}
\LWR@loadafter{bytefield}
\LWR@loadafter{ccicons}
\LWR@loadafter{cancel}
\LWR@loadafter{canoniclayout}
\LWR@loadafter{caption}
\LWR@loadafter{caption2}
\LWR@loadafter{caption3}
\LWR@loadafter{cases}
% catoptions is supported by the lwarp core
% \LWR@loadafter{ccaption}% may be preloaded by memoir
\LWR@loadafter{centerlastline}
% \LWR@loadafter{centernot}% may be preloaded by newtx
\LWR@loadafter{changebar}
\LWR@loadafter{changelayout}
\LWR@notmemoirloadafter{changepage}
\LWR@loadafter{changes}
\LWR@loadafter{chappg}
\LWR@loadafter{chapterbib}
\LWR@loadafter{chemfig}
\LWR@loadafter{chemformula}
\LWR@loadafter{chemgreek}
\LWR@loadafter{chemmacros}
\LWR@loadafter{chemnum}
\LWR@loadafter{chkfloat}
\LWR@notmemoirloadafter{chngpage}
\LWR@loadafter{cite}
\LWR@loadafter{citeref}
\LWR@loadafter{classicthesis}
\LWR@loadafter{cleveref}
% cmbright may be preloaded
\LWR@loadafter{cmdtrack}
\LWR@loadafter{colonequals}
\LWR@loadafter{color}
\LWR@loadafter{colortbl}
\LWR@loadafter{continue}
\LWR@loadafter{copyrightbox}
\LWR@notmemoirloadafter{crop}
% ctex must be loaded before lwarp
\LWR@loadafter{ctable}
\LWR@loadafter{cuted}
\LWR@loadafter{cutwin}
\LWR@loadafter{dblfloatfix}
\LWR@loadafter{dblfnote}
\LWR@notmemoirloadafter{dcolumn}
\LWR@loadafter{decimal}
\LWR@loadafter{decorule}
```

```
\LWR@loadafter{diagbox}
\LWR@loadafter{dingbat}
\LWR@loadafter{DotArrow}
\LWR@loadafter{dotlessi}
\LWR@loadafter{dprogress}
\LWR@loadafter{draftcopy}
\LWR@loadafter{draftfigure}
\LWR@loadafter{draftwatermark}
\LWR@loadafter{drftcite}
\LWR@loadafter{easy-todo}
\LWR@loadafter{ebook}
\LWR@loadafter{econometrics}
\LWR@loadafter{ed}
\LWR@loadafter{ellipsis}
\LWR@loadafter{embrac}
\LWR@loadafter{emptypage}
\LWR@loadafter{endfloat}
\LWR@loadafter{endheads}
\LWR@loadafter{endnotes}
\LWR@loadafter{engtlc}
\LWR@loadafter{enotez}
\LWR@notmemoirloadafter{enumerate}
\LWR@loadafter{enumitem}
\LWR@notmemoirloadafter{epigraph}
\LWR@loadafter{epsf}
\LWR@loadafter{epsfig}
\LWR@loadafter{epstopdf}
\LWR@loadafter{epstopdf-base}
\LWR@loadafter{eqlist}
\LWR@loadafter{eqparbox}
\LWR@loadafter{errata}
\LWR@loadafter{eso-pic}
\LWR@loadafter{esvect}
\LWR@loadafter{etoc}
\LWR@loadafter{eurosym}
\LWR@loadafter{everypage}
% \LWR@loadafter{everyshi}% now in LaTeX core
\LWR@loadafter{extarrows}
\LWR@loadafter{extramarks}
\LWR@loadafter{fancybox}
\LWR@loadafter{fancyhdr}
\LWR@loadafter{fancypar}
\LWR@loadafter{fancyref}
\LWR@loadafter{fancytabs}
\LWR@loadafter{fancyvrb}
\LWR@loadafter{fbox}
\LWR@loadafter{fewerfloatpages}
\LWR@loadafter{figcaps}
\LWR@loadafter{figsize}
\LWR@loadafter{fitbox}
\LWR@loadafter{fix2col}
\LWR@loadafter{fixmath}
\LWR@loadafter{fixme}
\LWR@loadafter{fixmetodonotes}
\LWR@loadafter{flafter}
```

```
\LWR@loadafter{flippdf}
\LWR@loadafter{float}
\LWR@loadafter{floatflt}
\LWR@loadafter{floatpag}
\LWR@loadafter{floatrow}
\LWR@loadafter{fltrace}
\LWR@loadafter{flushend}
\LWR@loadafter{fnbreak}
\LWR@loadafter{fncychap}
\LWR@loadafter{fnlineno}
\LWR@loadafter{fnpara}
\LWR@loadafter{fnpos}
\LWR@loadafter{fontawesome}
\LWR@loadafter{fontawesome5}
% fontenc must be loaded before lwarp
% fontspec must be loaded before lwarp
\LWR@loadafter{footmisc}
\LWR@loadafter{footnote}
\LWR@loadafter{footnotebackref}
\LWR@loadafter{footnotehyper}
\LWR@loadafter{footnoterange}
\LWR@loadafter{footnpag}
\LWR@loadafter{foreign}
\LWR@loadafter{forest}
\LWR@loadafter{fouridx}
% fourier may be loaded before lwarp
\LWR@loadafter{framed}
\LWR@loadafter{froufrou}
\LWR@loadafter{ftcap}
\LWR@loadafter{ftnright}
\LWR@loadafter{fullminipage}
\LWR@loadafter{fullpage}
\LWR@loadafter{fullwidth}
\LWR@loadafter{fvextra}
\LWR@loadafter{fwlw}
\LWR@loadafter{gensymb}
\LWR@loadafter{gentombow}
% geometry is always loaded by lwarp, and lwarp-geometry is AtBeginDocument
\LWR@loadafter{ghsystem}
\LWR@loadafter{gindex}
\LWR@loadafter{glossaries}
\LWR@loadafter{gmeometric}
% \LWR@loadafter{graphics}% pre-loaded by xunicode
% \LWR@loadafter{graphicx}% pre-loaded by xunicode
\LWR@loadafter{gloss}
\LWR@loadafter{glossary}
\LWR@loadafter{grffile}
\LWR@loadafter{grid}
\LWR@loadafter{grid-system}
\LWR@loadafter{gridset}
\LWR@loadafter{hang}
\LWR@loadafter{hanging}
\LWR@loadafter{hepunits}
\LWR@loadafter{hhline}
\LWR@loadafter{hhtensor}
```

```
\LWR@loadafter{hypbmsec}
\LWR@loadafter{hypcap}
\LWR@loadafter{hypdestopt}
\LWR@loadafter{hypernat}
\LWR@loadafter{hyperref}
\LWR@loadafter{hyperxmp}
\LWR@loadafter{hyphenat}
\LWR@loadafter{idxlayout}
\LWR@loadafter{ifoddpage}
\LWR@loadafter{imakeidx}
\LWR@loadafter{impnattypo}
\LWR@notmemoirloadafter{index}
% inputenc must be loaded before lwarp
% inputenx must be loaded before lwarp
% inputtrc may be loaded before lwarp
\LWR@loadafter{intopdf}
\LWR@loadafter{isomath}
\LWR@loadafter{isotope}
\LWR@loadafter{jurabib}
\LWR@loadafter{karnaugh-map}
\LWR@loadafter{keyfloat}
\LWR@loadafter{keystroke}
% kpfonts may be loaded before lwarp
% kpfonts-otf may be loaded before lwarp
\LWR@loadafter{layaureo}
\LWR@loadafter{layout}
\LWR@loadafter{layouts}
\LWR@loadafter{leading}
\LWR@loadafter{leftidx}
\LWR@loadafter{letterspace}
\LWR@loadafter{lettrine}
% libertinust1math may be loaded before lwarp
\LWR@loadafter{lineno}
\LWR@loadafter{lips}
\LWR@loadafter{listings}
\LWR@loadafter{listliketab}
\LWR@loadafter{longtable}
\LWR@loadafter{lpic}
\LWR@loadafter{lscape}
\LWR@loadafter{ltablex}
\LWR@loadafter{ltcaption}
\LWR@loadafter{ltxgrid}
\LWR@loadafter{ltxtable}
\LWR@loadafter{lua-check-hyphen}
\LWR@loadafter{lua-visual-debug}
\LWR@loadafter{luacolor}
\LWR@loadafter{luamplib}
\LWR@loadafter{luatodonotes}
\LWR@loadafter{luavlna}
\LWR@loadafter{lyluatex}
\LWR@loadafter{magaz}
\LWR@notmemoirloadafter{makeidx}
\LWR@loadafter{manyfoot}
\LWR@loadafter{marginfit}
\LWR@loadafter{marginfix}
```

```
\LWR@loadafter{marginnote}
\LWR@loadafter{marvosym}
% mathalpha may be loaded before lwarp
\LWR@loadafter{mathastext}
\LWR@loadafter{mathcomp}
\LWR@loadafter{mathdesign}
\LWR@loadafter{mathdots}
\LWR@loadafter{mathfixs}
\LWR@loadafter{mathpazo}
\LWR@loadafter{mathptmx}
\LWR@loadafter{mathspec}
\LWR@loadafter{mathtools}
\LWR@loadafter{mattens}
\LWR@loadafter{maybemath}
\LWR@loadafter{mcaption}
\LWR@loadafter{mdframed}
\LWR@loadafter{mdwmath}
\LWR@loadafter{media9}
\LWR@loadafter{memhfixc}
\LWR@loadafter{menukeys}
\LWR@loadafter{metalogo}
\LWR@loadafter{metalogox}
\LWR@loadafter{mhchem}
\LWR@loadafter{microtype}
\LWR@loadafter{midfloat}
\LWR@loadafter{midpage}
\LWR@loadafter{minibox}
\LWR@loadafter{minitoc}
\LWR@loadafter{minted}
\LWR@loadafter{mismath}
\LWR@loadafter{mleftright}
% morefloats must be allowed early for print mode
\LWR@notmemoirloadafter{moreverb}
% morewrites must be loaded before lwarp
\LWR@notmemoirloadafter{movie15}
\LWR@notmemoirloadafter{mparhack}
\LWR@loadafter{multibib}
\LWR@loadafter{multicap}
%\LWR@loadafter{multicol}% loaded by ltxdoc
\LWR@loadafter{multicolrule}
\LWR@loadafter{multimedia}
\LWR@loadafter{multiobjective}
\LWR@loadafter{multirow}
\LWR@loadafter{multitoc}
\LWR@loadafter{musicography}
\LWR@loadafter{nameauth}
\LWR@loadafter{nameref}
\LWR@loadafter{natbib}
\LWR@notmemoirloadafter{nccfancyhdr}
\LWR@loadafter{nccfoots}
\LWR@loadafter{nccmath}
\LWR@notmemoirloadafter{needspace}
% newclude must be loaded before lwarp
% newpxmath may be preloaded
% newtxmath may be loaded before lwarp
```

```
% newtxsf may be loaded before lwarp
% newunicodechar must be loaded before lwarp
\LWR@notmemoirloadafter{nextpage}
\LWR@loadafter{nicefrac}
\LWR@loadafter{niceframe}
\LWR@loadafter{nicematrix}
\LWR@loadafter{noitcrul}
\LWR@loadafter{nolbreaks}
\LWR@loadafter{nomencl}
\LWR@loadafter{nonfloat}
\LWR@loadafter{nonumonpart}
\LWR@loadafter{nopageno}
\LWR@loadafter{notes}
\LWR@loadafter{notespages}
\LWR@loadafter{nowidow}
\LWR@loadafter{ntheorem}
\LWR@loadafter{octave}
\LWR@loadafter{orcidlink}
\LWR@loadafter{overpic}
\LWR@loadafter{pagegrid}
\LWR@notmemoirloadafter{pagenote}
\LWR@loadafter{pagesel}
\LWR@loadafter{paralist}
\LWR@loadafter{parallel}
\LWR@loadafter{parcolumns}
\LWR@loadafter{parnotes}
\LWR@notmemoirloadafter{parskip}
\LWR@loadafter{pbalance}
\LWR@loadafter{pbox}
\LWR@loadafter{pdfcol}
\LWR@loadafter{pdfcolfoot}
\LWR@loadafter{pdfcolmk}
\LWR@loadafter{pdfcolparallel}
\LWR@loadafter{pdfcolparcolumns}
\LWR@loadafter{pdfcomment}
\LWR@loadafter{pdfcrypt}
\LWR@loadafter{pdflscape}
\LWR@loadafter{pdfmarginpar}
\LWR@loadafter{pdfpages}
\LWR@loadafter{pdfprivacy}
\LWR@loadafter{pdfrender}
\LWR@loadafter{pdfsync}
\LWR@loadafter{pdftricks}
\LWR@loadafter{pdfx}
\LWR@loadafter{perpage}
\LWR@loadafter{pfnote}
\LWR@loadafter{phfqit}
\LWR@loadafter{physics}
\LWR@loadafter{physunits}
\LWR@loadafter{picinpar}
\LWR@loadafter{pifont}
\LWR@loadafter{pinlabel}
\LWR@loadafter{placeins}
\LWR@loadafter{plarray}
\LWR@loadafter{plarydshln}
```

```
\LWR@loadafter{plextarray}
\LWR@loadafter{plextarydshln}
\LWR@loadafter{plcolortbl}
\LWR@loadafter{plextdelarray}
\LWR@loadafter{plimsoll}
\LWR@loadafter{prelim2e}
\LWR@loadafter{prettyref}
\LWR@loadafter{preview}
\LWR@loadafter{psfrag}
\LWR@loadafter{psfragx}
\LWR@loadafter{pst-eps}
\LWR@loadafter{pstool}
\LWR@loadafter{pstricks}
% \LWR@loadafter{pxatbegshi}% may be used by morewrites
\LWR@loadafter{pxeveryshi}
% \LWR@loadafter{pxfonts}% may be loaded before lwarp
\LWR@loadafter{pxftnright}
\LWR@loadafter{pxjahyper}
\LWR@loadafter{quotchap}
\LWR@loadafter{quoting}
\LWR@loadafter{ragged2e}
\LWR@loadafter{realscripts}
\LWR@loadafter{refcheck}
\LWR@loadafter{register}
\LWR@loadafter{relsize}
\LWR@loadafter{repeatindex}
\LWR@loadafter{resizegather}
\LWR@loadafter{returntogrid}
\LWR@loadafter{rlepsf}
\LWR@loadafter{rmathbr}
\LWR@loadafter{rmpage}
\LWR@loadafter{romanbar}
\LWR@loadafter{romanbarpagenumber}
\LWR@loadafter{rotating}
\LWR@loadafter{rotfloat}
\LWR@loadafter{rviewport}
\LWR@loadafter{savetrees}
% scalefnt is loaded by babel-french
\LWR@loadafter{scalerel}
\LWR@loadafter{schemata}
\LWR@loadafter{scrextend}
\LWR@loadafter{scrhack}
\LWR@loadafter{scrlayer}
\LWR@loadafter{scrlayer-notecolumn}
\LWR@loadafter{scrlayer-scrpage}
\LWR@loadafter{scrpage2}
\LWR@loadafter{section}
\LWR@loadafter{sectionbreak}
\LWR@loadafter{sectsty}
\LWR@loadafter{selectp}
\LWR@loadafter{semantic-markup}
\LWR@notmemoirloadafter{setspace}
\LWR@loadafter{shadow}
\LWR@loadafter{shapepar}
\LWR@notmemoirloadafter{showidx}
```

```
\LWR@loadafter{showkeys}
\LWR@loadafter{showtags}
\LWR@loadafter{shuffle}
\LWR@loadafter{sidecap}
\LWR@loadafter{sidenotes}
\LWR@loadafter{simplebnf}
\LWR@loadafter{SIunits}
\LWR@loadafter{siunitx}
\LWR@loadafter{siunitx-v2}
\LWR@loadafter{skmath}
\LWR@loadafter{slantsc}
\LWR@loadafter{slashed}
\LWR@loadafter{soul}
\LWR@loadafter{soulpos}
\LWR@loadafter{soulutf8}
\LWR@loadafter{splitbib}
\LWR@loadafter{splitidx}
\LWR@loadafter{srcltx}
\LWR@loadafter{srctex}
\LWR@loadafter{stabular}
\LWR@loadafter{stackengine}
\LWR@loadafter{stackrel}
\LWR@loadafter{statex2}
\LWR@loadafter{statistics}
\LWR@loadafter{statmath}
\LWR@loadafter{steinmetz}
\LWR@notltjloadafter{stfloats}
\LWR@loadafter{struktex}
\LWR@loadafter{subcaption}
\LWR@loadafter{subfig}
\LWR@loadafter{subfigure}
\LWR@loadafter{subsupscripts}
\LWR@loadafter{supertabular}
\LWR@loadafter{svg}
\LWR@loadafter{swfigure}
\LWR@loadafter{syntonly}
\LWR@loadafter{t1inc}
\LWR@loadafter{tabfigures}
\LWR@loadafter{tabls}
\LWR@loadafter{tablefootnote}
\LWR@notmemoirloadafter{tabularx}
\LWR@loadafter{tabulary}
\LWR@loadafter{tagpdf}
\LWR@loadafter{tascmac}
\LWR@loadafter{tcolorbox}
\LWR@loadafter{tensor}
\LWR@loadafter{termcal}
\LWR@loadafter{textarea}
% \LWR@loadafter{textcomp}% maybe before lwarp with font packages
\LWR@loadafter{textfit}
\LWR@loadafter{textpos}
\LWR@loadafter{theorem}
\LWR@loadafter{thinsp}
\LWR@loadafter{thm-listof}
\LWR@loadafter{thm-restate}
```

```
\LWR@loadafter{thmbox}
\LWR@loadafter{thmtools}
\LWR@loadafter{threadcol}
\LWR@loadafter{threeparttable}
\LWR@loadafter{threeparttablex}
\LWR@loadafter{thumb}
\LWR@loadafter{thumbs}
\LWR@loadafter{tikz}
\LWR@loadafter{tikz-imagelabels}
\LWR@loadafter{titleps}
\LWR@loadafter{titlesec}
\LWR@loadafter{titletoc}
\LWR@notmemoirloadafter{titling}
% \LWR@loadafter{tocbasic}% preloaded by koma-script classes
\LWR@notmemoirloadafter{tocbibind}
\LWR@loadafter{tocdata}
\LWR@loadafter{tocenter}
\LWR@notmemoirloadafter{tocloft}
\LWR@loadafter{tocstyle}
\LWR@loadafter{todo}
\LWR@loadafter{todonotes}
\LWR@loadafter{topcapt}
\LWR@loadafter{tram}
\LWR@loadafter{transparent}
\LWR@loadafter{trimclip}
\LWR@loadafter{trivfloat}
\LWR@loadafter{truncate}
\LWR@loadafter{turnthepage}
\LWR@loadafter{twoup}
% \LWR@loadafter{txfonts}% may be loaded before lwarp
% txgreeks may be loaded before lwarp

% \LWR@loadafter{typearea}% preloaded by koma-script classes
\LWR@loadafter{typicons}
% \LWR@loadafter{ulem}% preloaded by ctexart and related classes
\LWR@loadafter{umoline}
\LWR@loadafter{underscore}
% unicode-math may be loaded before lwarp
\LWR@loadafter{units}
\LWR@loadafter{unitsdef}
\LWR@loadafter{upgreek}
\LWR@loadafter{upref}
\LWR@loadafter{url}
\LWR@loadafter{ushort}
\LWR@loadafter{uspace}
\LWR@loadafter{varioref}
\LWR@notmemoirloadafter{verse}
\LWR@loadafter{versonotes}
\LWR@loadafter{vertbars}
\LWR@loadafter{vmargin}
\LWR@loadafter{vowel}
\LWR@loadafter{vpe}
\LWR@loadafter{vwcol}
\LWR@loadafter{wallpaper}
\LWR@loadafter{watermark}
```

```
\LWR@loadafter{widetable}
\LWR@loadafter{widows-and-orphans}
\LWR@loadafter{witharrows}
\LWR@loadafter{wrapfig}
\LWR@loadafter{xbmks}
\LWR@loadafter{xcolor}
\LWR@loadafter{xechangebar}
\LWR@loadafter{xellipsis}
% xetexko must be loaded before lwarp
\LWR@loadafter{xevlna}
\LWR@loadafter{xfakebold}
\LWR@loadafter{xfrac}
\LWR@loadafter{xltabular}
\LWR@loadafter{xltxtra}
\LWR@loadafter{xmpincl}
\LWR@loadafter{xpiano}
\LWR@loadafter{xpinyin}
\LWR@loadafter{xr}
\LWR@loadafter{xr-hyper}
\LWR@loadafter{xtab}
% xunicode must be loaded before lwarp
\LWR@loadafter{xurl}
\LWR@loadafter{xy}
\LWR@loadafter{zwpagelayout}
```

21 MD5 hashing

The MD5 hash is used for `lateximage` filenames for SVG math.

```
\newcommand{\LWR@mdfive}[1]{%
    \PackageError{lwarp}
        {No MD5 macro was found}
        {%
            Lwarp must find the macros \protect\pdfmdfivesum\space
            or \protect\mdfivesum.%
        }
}
```

The default for pdfLaTeX, DVILaTeX, upLaTeX, etc:

```
\let\LWR@mdfive\pdfmdfivesum
```

For LuaLaTeX:

```
\ifLuaTeX
\RequirePackage{pdftexcmds}
\let\LWR@mdfive\pdf@mdfivesum
\fi
```

For XeLaTeX:

```
\ifXeTeX
```

```
\@ifundefined{pdffivesum}{}
    {\let\LWR@mdfive\pdfmdfivesum}
\@ifundefined{mdfivesum}{}
    {\let\LWR@mdfive\mdfivesum}
\fi
```

22 pdfLaTeX T1 and UTF-8 encoding

When using pdfLaTeX, lwarp requires T1 font encoding, and recommends UTF-8 input encoding.

If some other input encoding is already defined, lwarp will try to use it instead, and hope for the best.

XeLaTeX and LuaLaTeX are both UTF-8 by nature.

`\LWR@pdfencoding` Sets T1, and also utf8 if not already set.

```
\newcommand*{\LWR@pdfencoding}{%
    \RequirePackage[T1]{fontenc}

    \@ifpackageloaded{inputenc}{}{
        \@ifpackageloaded{inputenx}{}{
            \RequirePackage[utf8]{inputenc}
        }
    }
}
```

```
\ifPDFTeX% pdflatex or dvi latex
    \LWR@pdfencoding
\fi

\ifpTeX
    \LWR@pdfencoding
\fi
```

23 Unicode input characters

for HTML & PRINT: If using *pdflatex*, convert a minimal set of Unicode characters. Additional characters may be defined by the user, as needed.

A commonly-used multiply symbol is declared to be `\texttimes`.

The first arguments of `\newunicodechar` below are text ligatures in the source code, even though they are not printed in the following listing.

```
\ifpTeX
\else
\RequirePackage{newunicodechar}

```

```
\newunicodechar{×}{\texttimes}

\ifPDFTeX% pdflatex or dvi latex
\newunicodechar{ff}{ff}% Here, the first arguments are ligatures.
\newunicodechar{fi}{fi}
\newunicodechar{fl}{fl}
\newunicodechar{ffi}{ffi}
\newunicodechar{ffl}{ffl}
\newunicodechar{–}{---}
\newunicodechar{–}{--}
\fi

\fi
```

24 Avoid a bitmapped font

If DVI or PDF LaTeX, and if the default Computer Modern is the selected font family, ensure that cm-super or lmodern is used to provide a vector font.

```
\ifxetexorluatex
\else
    \ifdefstring{\f@family}{cmr}{
        \IfFileExists{type1ec.sty}% found in cm-super
        {}
        {% cm-super not installed
            \IfFileExists{lmodern.sty}{
                \PackageInfo{lwarp}{cm-super not installed, loading lmodern}
                \RequirePackage{lmodern}
            }{
                \PackageError{lwarp}
                {%
                    Lwarp requires a vector font.\MessageBreak
                   Install and load cm-super, lmodern, or another\MessageBreak
                    Type-1 vector font before loading lwarp.\MessageBreak
                    Enter 'H' for possible solutions%
                }
                {%
                    Install cm-super or lmodern.\MessageBreak
                    If lmodern, load it before lwarp:\MessageBreak
                        \space\space\protect\usepackage{lmodern}\MessageBreak
                        \space\space\protect\usepackage{lwarp}%
                }
            }
        }% cm-super not installed
    }{}% f@family
\fi
```

25 Upright quotes

In pdfTeX, preserve upright quotes in verbatim text. upquote also loads textcomp.

```
\ifPDFTeX
\RequirePackage{upquote}
\fi

\ifpTeX
    \RequirePackage{upquote}
\fi
```

26 Avoid bad font combinations

For XeLaTeX and LuaLaTeX, certain font combinations cause problems with lwarp.

libertinus-otf has special handling for `\textquotedbl`. Search for `\LWR@orig@textquotedbl`.

```
\ifxetexorluatex
    \AtBeginDocument{
        \@ifpackageloaded{kpfonts}{
            \PackageError{lwarp}
                {%
                    When using XeLaTeX or LuaLaTeX,\MessageBreak
                    use kpfonts-otf instead of kpfonts%
                }
                {%
                    Replace: \protect\usepackage{kpfonts}\MessageBreak
                    with: \protect\usepackage{kpfonts-otf}
                }
        }{}
    }
\fi
```

27 Miscellaneous tools

27.1 Variables

```
\newlength{\LWR@templengthone}
\newlength{\LWR@templengthtwo}
\newlength{\LWR@templengththree}
\newcounter{LWR@tempcountone}
```

27.2 Lengths and units

`\LWR@providelength` `{⟨\lengthname⟩}` Provides the length if it isn't defined yet.

Used to provide source compatibility for lengths which will be ignored, but might or might not be already provided by other packages.

```
\newcommand*\LWR@providelength[1]{%
    \ifdeflength{#1}{}{\newlength{#1}}%
}
```

\LWR@convertto {⟨*dest unit*⟩} {⟨*length*⟩}

Prints a length in the given units, without printing the unit itself.

```
\newcommand*{\LWR@convertto}[2]{\strip@pt\dimexpr #2*65536/\number\dimexpr 1#1}
```

\LWR@printpercentlength {⟨*smaller*⟩} {⟨*larger*⟩}

Prints a percent ratio of the two lengths.

```
\newcommand*{\LWR@printpercentlength}[2]{%
    \setcounter{LWR@tempcountone}{100*\ratio{#1}{#2}}%
    \arabic{LWR@tempcountone}%
}
```

27.3 Counters

\defaddtocounter {⟨*name*⟩} {⟨*value*⟩}

Locally add to a counter.

```
\providecommand*{\defaddtocounter}[2]{%
    \defcounter{#1}{\value{#1}+#2}%
}
```

27.4 Patching

\LWR@patcherror {⟨*packagename*⟩} {⟨*macroname*⟩}

Prints an error if could not patch a macro.

```
\newcommand*{\LWR@patcherror}[2]{%
    \PackageError{lwarp}%
        {%
            Unable to patch package #1,\MessageBreak
            macro \LWRbackslash #2.\MessageBreak
            Lwarp or #1 may need to be updated%
        }%
        {Please contact the maintainer of the Lwarp package.}%
}
```

27.5 Chinese text isolation

\LWR@isolate {⟨*text*⟩} Isolates Chinese characters from the surrounding text. This is required to avoid extra spaces on either side of the Chinese characters, especially when written to a file.

```
\newcommand{\LWR@isolate}[1]{#1}%

\@ifpackageloaded{ctexpatch}{
```

```
    \renewcommand{\LWR@isolate}[1]{\null#1\null}%
}{}

\@ifpackageloaded{xeCJK}{
    \renewcommand{\LWR@isolate}[1]{\null#1\null}%
}{}
```

`\LWR@disablepinyin` Disable xpinyin during file, sideTOC, and footnote generation. Set by xpinyin.

```
\newcommand*{\LWR@disablepinyin}{}
```

27.6 Inserting vertical space

`\LWR@forceemptyline` Extra vertical space in the HTML output. Use after `\LWR@stoppars`.

```
\newcommand*{\LWR@forceemptyline}{%
    \LWR@origrule{0pt}{1\baselineskip}%
    \LWR@orignewline%
}
```

27.7 Argument selection

`\LWR@firstoffive` {⟨*first*⟩} {⟨*second*⟩} {⟨*third*⟩} {⟨*fourth*⟩} {⟨*fifth*⟩}

`\LWR@secondoffive` {⟨*first*⟩} {⟨*second*⟩} {⟨*third*⟩} {⟨*fourth*⟩} {⟨*fifth*⟩}

`\LWR@thirdoffive` {⟨*first*⟩} {⟨*second*⟩} {⟨*third*⟩} {⟨*fourth*⟩} {⟨*fifth*⟩}

`\LWR@fourthoffive` {⟨*first*⟩} {⟨*second*⟩} {⟨*third*⟩} {⟨*fourth*⟩} {⟨*fifth*⟩}

`\LWR@fifthoffive` {⟨*first*⟩} {⟨*second*⟩} {⟨*third*⟩} {⟨*fourth*⟩} {⟨*fifth*⟩}

Expands to the nth of the five arguments. Used for extra cross referencing.

```
\long\def\LWR@firstoffive#1#2#3#4#5{#1}
\long\def\LWR@secondoffive#1#2#3#4#5{#2}
\long\def\LWR@thirdoffive#1#2#3#4#5{#3}
\long\def\LWR@fourthoffive#1#2#3#4#5{#4}
\long\def\LWR@fifthoffive#1#2#3#4#5{#5}
```

27.8 Inside boxes

Greater than zero if currently inside a TEX box, thus should not use `\LWR@orignewpage`. See section 13.2.

```
\newcounter{LWR@texboxdepth}
\setcounter{LWR@texboxdepth}{0}
```

\LWR@maybe@orignewpage Only do \LWR@orignewpage if not inside a TEX box.

```
\newcommand*{\LWR@maybe@orignewpage}{%
    \LWR@traceinfo{LWR@maybe@orignewpage}%
    \ifnumgreater{\value{LWR@texboxdepth}}{0}
        {}%
        {\LWR@orignewpage}%
    \LWR@traceinfo{LWR@maybe@orignewpage done}%
}
```

27.9 Global boxes

\LWR@gsavebox {⟨*macroname*⟩} {⟨*contents*⟩}

From https://tex.stackexchange.com/questions/288702/savebox-forgets-its-content-across-columns-inside-align

```
\DeclareRobustCommand\LWR@gsavebox[1]{%
  \@ifnextchar(%)
    {\LWR@@gsavepicbox#1}{\@ifnextchar[{\LWR@@gsavebox#1}{\LWR@gsbox#1}}}%
\long\def\LWR@gsbox#1#2{\global\setbox#1\hbox{%
  \color@setgroup#2\color@endgroup}}
\def\LWR@@gsavebox#1[#2]{%
  \@ifnextchar [{\LWR@@igsavebox#1[#2]}{\LWR@@igsavebox#1[#2][c]}}
\long\def\LWR@@igsavebox#1[#2][#3]#4{%
  \LWR@gsbox#1{\@imakebox[#2][#3]{#4}}}
\def\LWR@@gsavepicbox#1(#2,#3){%
  \@ifnextchar[%]
    {\LWR@@igsavepicbox#1(#2,#3)}{\LWR@@igsavepicbox#1(#2,#3)[]}}
\long\def\LWR@@igsavepicbox#1(#2,#3)[#4]#5{%
  \LWR@gsbox#1{\@imakepicbox(#2,#3)[#4]{#5}}}
```

Env LWR@glrbox {⟨*macroname*⟩}

```
\def\LWR@glrbox#1{%
  \edef\reserved@a{%
    \endgroup
    \global\setbox#1\hbox{%
      \begingroup\aftergroup}%
        \def\noexpand\@currenvir{\@currenvir}%
        \def\noexpand\@currenvline{\on@line}}%
  \reserved@a
    \@endpefalse
    \color@setgroup
      \ignorespaces}
\let\LWR@endglrbox\LWR@endlrbox
```

27.10 Converting a macro name to a cs name

\macrotocsname {⟨*macro name with backslash*⟩}

Results in the macro name without the leading backslash.

Ref: https://tex.stackexchange.com/questions/42318/removing-a-backslash-from-a-character-sequence

```
\newcommand*{\macrotocsname}[1]{%
  \ifcat\relax\noexpand#1%
    \expandafter\expandafter\expandafter\@gobble\expandafter\string
  \fi
  #1%
}
```

27.11 Title case

\LWRtexttitlecase

```
\ExplSyntaxOn
\newcommand*{\LWRtexttitlecase}[1]{%
    \text_titlecase:n{#1}%
}
\ExplSyntaxOff
```

27.12 LetLtxMacrocs

\LWR@LetLtxMacrocs {⟨*newcsname*⟩} {⟨*oldcsname*⟩}

\LetLtxMacro with cs names.

```
\newcommand*{\LWR@LetLtxMacrocs}[2]{%
    \expandafter\LetLtxMacro\csname #1\expandafter\endcsname%
    \csname#2\endcsname%
}
```

27.13 Absorbing a star

\LWR@absorbstar {⟨*csname*⟩}

Modifies a macro to aborb a star. Used for cleveref, since hyperref is emulated, so the starred macros are not created by cleveref.

```
\newcommand*{\LWR@absorbstar}[1]{%
    \LWR@LetLtxMacrocs{LWR@origns@#1}{#1}%
    \csdef{#1}{\@ifstar{\csuse{LWR@origns@#1}}{\csuse{LWR@origns@#1}}}
    \expandafter\robustify\csname #1\endcsname
}
```

28 Operating-System portability

Prog Unix
Prog Mac OS
Prog Linux

lwarp tries to detect which operating system is being used. Unix / Mac OS / Linux is the

default (collectively referred to as "Unix" in the configuration files), and MS-Windows is supported as well.

Prog MS-Windows

If MS-Windows is not correctly detected, use the lwarp option OSWindows.

Prog Windows

Opt OSWindows

When detected or specified, the operating-system path separator used by lwarp is modified, and the boolean usingOSWindows is set true. This boolean may be tested by the user for later use.

28.1 Literal characters

Literal characters to be used in PrintLatexCmd and HTMLLatexCmd. These are defined without @ to easily allow their inclusion in the user's document.

The literal % character:

```
\let\LWRpercent\@percentchar
```

The literal $ character:

```
\catcode`\$=12
\def\LWRdollar{$}
\catcode`\$=3
```

The literal & character:

```
\catcode`\&=12
\def\LWRamp{&}
\catcode`\&=4
```

The literal \ character. The ampersand is temporarily set to the escape character during the definition of the backslash macro.

```
\catcode`\&=0
&catcode`&\=12
&def&LWRbackslash{\}
&catcode`&\=0
\catcode`\&=4
```

The literal { character. The ampersand is temporarily set to the begin group character during the definition of the leftbrace macro.

```
\catcode`\&=1
\catcode`\{=12
\def\LWRleftbrace&{}
\catcode`\{=1
\catcode`\&=4
```

The literal } character. The ampersand is temporarily set to the end group character during the definition of the leftbrace macro.

```
\catcode`\&=2
\catcode`\}=12
```

```
\def\LWRrightbrace{}&
\catcode`\}=2
\catcode`\&=4
```

The literal # character:

```
\catcode`\#=12
\def\LWRhash{#}
\catcode`\#=6
```

\LWRopquote The operating system's quote mark, Unix default. For Windows, see \LWR@setOSWindows, below.

```
\def\LWRopquote{'}
```

\LWRopseq The operating system's sequential execution command, Unix default. For Windows, see \LWR@setOSWindows, below.

```
\def\LWRopseq{\space\LWRamp\LWRamp\space\space}
```

28.2 Common portability code

Bool usingOSWindows Set if the OSWindows option is used, or if Windows is automatically detected.

```
\newbool{usingOSWindows}
\boolfalse{usingOSWindows}
```

28.3 Unix, Linux, and Mac OS

\OSPathSymbol Symbol used to separate directories in a path.

```
\newcommand*{\OSPathSymbol}{/}
```

28.4 MS-Windows

For MS-Windows:

\LWR@setOSWindows Set defaults for the MS-Windows operating system. lwarp attempts to auto-detect the operatings system, and the OSWindows option may also be used to force MS-Windows compatibility.

```
\newcommand*{\LWR@setOSWindows}
{
\booltrue{usingOSWindows}
\renewcommand*{\OSPathSymbol}{\@backslashchar}
\def\LWRopquote{"}
\def\LWRopseq{\space\LWRamp\space\space}
}
```

Test for windows during compile. The user may also specify `OSWindows` package option in case this test fails.

```
\ifwindows
\LWR@setOSWindows
\fi
```

29 Package options

Pkg `kvoptions` Allows key/value package options.

```
\RequirePackage{kvoptions}
\SetupKeyvalOptions{family=LWR,prefix=LWR@}
```

`\lwarpsetup` A user interface to set the keys:

```
\newcommand{\lwarpsetup}[1]{\setkeys{LWR}{#1}}
```

Bool `warpingprint`
Bool `warpingHTML`
Bool `mathjax`
Bool `LWR@origmathjax`

Set to true/false depending on the package option selections for print/HTML/EPUB output and mathsvg/mathjax.

`LWR@origmathjax` remembers the original setting to be restored by `\displaymathnormal`.

```
\newbool{warpingprint}
\newbool{warpingHTML}
\newbool{mathjax}
\newbool{LWR@origmathjax}
```

defaults The default is print output, and SVG math if the user chose HTML output.

```
\booltrue{warpingprint}%
\boolfalse{warpingHTML}%
\boolfalse{mathjax}%
```

Opt `warpprint` If the `warpprint` option is given, boolean `warpingprint` is true and boolean `warpingHTML` is false, and may be used for `\ifbool` tests.

```
\DeclareVoidOption{warpprint}{%
    \PackageInfo{lwarp}{Using option 'warpprint'}
    \booltrue{warpingprint}%
    \boolfalse{warpingHTML}%
}
```

Opt `warpHTML` Anything in the `warpHTML` environment will be generated for HTML output only.

Opt `warpHTML` If the `warpHTML` option is given, boolean `warpingHTML` is true and boolean `warpingprint` is false, and may be used for `\ifbool` tests.

```
\DeclareVoidOption{warpHTML}{%
    \PackageInfo{lwarp}{Using option 'warpHTML'}%
    \booltrue{warpingHTML}%
    \boolfalse{warpingprint}%
}
```

Opt mathsvg

Option mathsvg selects SVG math display: If the mathsvg option is given, boolean mathjax is false, and may be used for \ifbool tests.

```
\DeclareVoidOption{mathsvg}{%
    \PackageInfo{lwarp}{Using option 'mathsvg'}
    \boolfalse{mathjax}%
    \boolfalse{LWR@origmathjax}%

}
```

Opt mathjax

Option mathjax selects MathJax math display: If the mathjax option is given, boolean mathjax is true, may be used for \ifbool tests.

```
\DeclareVoidOption{mathjax}{%
    \PackageInfo{lwarp}{Using option 'mathjax'}
    \booltrue{mathjax}%
    \booltrue{LWR@origmathjax}%

}
```

Opt BaseJobname
Default: \jobname

Option BaseJobname sets the \BaseJobname for this document.

This is the \jobname of the printed version, even if currently compiling the HTML version. I.e. this is the \jobname without _html appended. This is used to set \HomeHTMLFilename if the user did not provide one.

```
\DeclareStringOption[\jobname]{BaseJobname}
```

Opt ImagesDirectory
Default: \jobname-images

Option ImagesDirectory sets the name of the directory to use for the lateximage images.

```
\DeclareStringOption[\BaseJobname-images]{ImagesDirectory}
```

Opt ImagesName
Default: image-

Option ImagesName sets the prefix to use for the lateximage images.

```
\DeclareStringOption[image-]{ImagesName}
```

Opt makeindexStyle
Default: lwarp.ist

Selects a custom .ist file. A customized file should be based on lwarp.ist. See section 8.6.20.

```
\DeclareStringOption[lwarp.ist]{makeindexStyle}
```

Opt xindyStyle
Default: lwarp.xdy

Selects a custom .xdy file. A customized file should be based on lwarp.xdy. See section 8.6.21.

```
\DeclareStringOption[lwarp.xdy]{xindyStyle}
```

Opt `xindyLanguage`
Default: `english`

Sets the *xindy* language to be assigned in *lwarpmk*'s configuration files. This is then used by *lwarpmk* while processing the index and glossary.

```
\DeclareStringOption[english]{xindyLanguage}
```

Opt `xindyCodepage`
Default: `utf8`

Sets the *xindy* codepage to be assigned in *lwarpmk*'s configuration files. This is then used by *lwarpmk* while processing the index.

```
\DeclareStringOption[utf8]{xindyCodepage}
```

Opt `xindexConfig`
Default: `<empty>`

Selects a custom `xindex-*.lua` file. A customized file should be based on `xindex-cfg.lua`. See section 8.6.22.

```
\DeclareStringOption[]{xindexConfig}
```

Opt `pdftotextEnc`
Default: `UTF-8`

The option `pdftotextEnc` sets the encoding used by *pdftotext*. This is passed to *pdftotext* using its `-enc` option, and is used when converting LaTeX PDF output with HTML tags into a plain-text file with HTML tags.

```
\DeclareStringOption[UTF-8]{pdftotextEnc}
```

Opt `lwarpmk`

Tells lwarp to generate a local copy of *lwarpmk* called `lwarpmk.lua`. Useful for archiving for future use. This file may be made executable and acts just like *lwarpmk*.

If `lwarpmk` option, creates a local copy of `lwarpmk.lua`:

```
\newbool{LWR@creatinglwarpmk}
\boolfalse{LWR@creatinglwarpmk}

\DeclareVoidOption{lwarpmk}{
    \PackageInfo{lwarp}{Using option 'lwarpmk'}
    \booltrue{LWR@creatinglwarpmk}
}
```

Opt `OSWindows`

Tells lwarp to use MS-Windows compatibility. Auto-detection of the operating system is attempted, and this option is only necessary if the auto-detection fails. See the automatically-generated `lwarpmk.conf` file to find out whether the operating system was detected correctly.

```
\DeclareVoidOption{OSWindows}{
    \PackageInfo{lwarp}{Using option 'OSWindows'}
    \LWR@setOSWindows
}
```

Opt `HomeHTMLFilename`
Default: `\BaseJobname`

The filename of the homepage. The default is the jobname. This option is stored into `\LWR@HomeHTMLFilename`, and later transferred into `\HomeHTMLFilename` for internal use.

```
\DeclareStringOption[]{HomeHTMLFilename}
```

Opt `HTMLFilename`
Default: `<empty>`

The filename prefix of web pages after the homepage. The default is empty, no prefix. This

option is stored into \LWR@HTMLFilename, and later transferred into \HTMLFilename for internal use.

```
\DeclareStringOption[]{HTMLFilename}
```

Opt PrintLatexCmd
Default: <automatic>

The shell commands to use to compile the print document.

```
\DeclareStringOption[]{PrintLatexCmd}
```

Opt HTMLLatexCmd
Default: <automatic>

The shell commands to use to compile the HTML document.

```
\DeclareStringOption[]{HTMLLatexCmd}
```

Opt PrintIndexCmd
Default: <empty>

The shell commands to use to compile the print indexes.

```
\DeclareStringOption[]{PrintIndexCmd}
```

Opt HTMLIndexCmd
Default: <empty>

The shell commands to use to compile the HTML indexes.

```
\DeclareStringOption[]{HTMLIndexCmd}
```

Opt LatexmkIndexCmd
Default: <empty>

The shell commands to by used by *latexmk* to compile the print indexes. Unlike PrintIndexCmd and HTMLIndexCmd, LatexmkIndexCmd does not include the filename, which will be provided by *latexmk*.

```
\DeclareStringOption[]{LatexmkIndexCmd}
```

Opt makeindex

Tells lwarp to use *makeindex* for index generation. When lwarpmk.conf and *.lwarpmkconf are generated, PrintIndexCmd and HTMLIndexCmd will be set for *makeindex* with a single index file.

```
\DeclareBoolOption[false]{makeindex}
```

Opt xindy

Tells lwarp to use *xindy* for index generation. When lwarpmk.conf and *.lwarpmkconf are generated, PrintIndexCmd and HTMLIndexCmd will be set for *xindy* with a single index file.

```
\DeclareBoolOption[false]{xindy}
```

Opt xindex

Tells lwarp to use *xindex* for index generation. When lwarpmk.conf and *.lwarpmkconf are generated, PrintIndexCmd and HTMLIndexCmd will be set for *xindex* with a single index file.

```
\DeclareBoolOption[false]{xindex}
```

Opt IndexRef
Default: cref

Tells lwarp how to display the index entries in HTMLoutput. See section 7.5.

```
\DeclareStringOption[cref]{IndexRef}
```

Opt GlossaryCmd
Default: makeglossaries

The shell command to use to compile the glossary. The print or HTML version of the glossary filename will be appended to this command.

```
\DeclareStringOption[makeglossaries]{GlossaryCmd}
```

Opt latexmk Option latexmk tells *lwarpmk* to use *latexmk* when compiling documents.

```
\DeclareBoolOption[false]{latexmk}
```

Opt dvips Option dvips tells *lwarpmk* to use *dvips* when compiling DVI *latex* documents.

```
\DeclareBoolOption[false]{dvips}
```

Opt dvipdfm Option dvipdfm tells *lwarpmk* to use *dvipdfm* when compiling DVI *latex* documents.

```
\DeclareBoolOption[false]{dvipdfm}
```

Opt dvipdfmx Option dvipdfmx tells *lwarpmk* to use *dvipdfmx* when compiling DVI *latex* documents.

```
\DeclareBoolOption[false]{dvipdfmx}
```

Execute options Execute the package options, with the defaults which have been set just above:

```
\ProcessKeyvalOptions*\relax
```

29.1 Additional options support

Assign the \BaseJobname if the user hasn't provided one:

```
\providecommand*{\BaseJobname}{\LWR@BaseJobname}
```

Defaults unless already over-ridden by the user:

```
\ifcsempty{LWR@HomeHTMLFilename}{
    \newcommand*{\HomeHTMLFilename}{\BaseJobname}
}{
    \csedef{HomeHTMLFilename}{\LWR@HomeHTMLFilename}
}

\csedef{HTMLFilename}{\LWR@HTMLFilename}
```

Special handling for underscores in labels and filenames.

\LWR@sanitized The sanitized version of what was given to \LWR@sanitize. Characters are set to their detokenized versions. Required for underscores in labels and filenames.

```
\newcommand*{\LWR@sanitized}{}
```

\LWR@sanitize {⟨*text*⟩}

Sanitizes the text and returns the result in \LWR@sanitized.

```
\newcommand*{\LWR@sanitize}[1]{%
\edef\LWR@sanitized{#1}%
\edef\LWR@sanitized{\detokenize\expandafter{\LWR@sanitized}}%
}
```

Sanitize some string options to neutralize underscores.

```
\LWR@sanitize{\LWR@BaseJobname}
\edef\LWR@BaseJobname{\LWR@sanitized}

\LWR@sanitize{\LWR@ImagesDirectory}
\edef\LWR@ImagesDirectory{\LWR@sanitized}

\LWR@sanitize{\LWR@ImagesName}
\edef\LWR@ImagesName{\LWR@sanitized}
```

\LWR@PrintIndexCmd and \LWR@HTMLIndexCmd are tested to see if they are empty. If so, they are set to a reasonable defaults for a single index using *makeindex*, then possibly set to defaults for *xindy* if the lwarp xindy option was selected, then likewise for *xindex* if the xindex option was selected.

```
\ifdefempty{\LWR@PrintIndexCmd}{
    \renewcommand{\LWR@PrintIndexCmd}{%
        makeindex  -s \LWR@makeindexStyle \space  \jobname.idx%
    }
    \ifbool{LWR@xindy}{
        \renewcommand{\LWR@PrintIndexCmd}{%
            xindy
            -M \LWR@xindyStyle \space
            -L \LWR@xindyLanguage \space
            -C \LWR@xindyCodepage \space
            \jobname.idx%
        }
    }{}
    \ifbool{LWR@xindex}{
        \ifdefvoid{\LWR@xindexConfig}{
            \renewcommand{\LWR@PrintIndexCmd}{%
                xindex
                \jobname.idx%
            }
        }{
            \renewcommand{\LWR@PrintIndexCmd}{%
                xindex
                -c \LWR@xindexConfig \space
                \jobname.idx%
            }
        }
    }{}
}{}

\ifdefempty{\LWR@HTMLIndexCmd}{
    \renewcommand{\LWR@HTMLIndexCmd}{%
        makeindex  -s \LWR@makeindexStyle \space  \jobname_html.idx%
    }
    \ifbool{LWR@xindy}{
        \renewcommand{\LWR@HTMLIndexCmd}{%
            xindy
            -M \LWR@xindyStyle \space
            -L \LWR@xindyLanguage \space
            -C \LWR@xindyCodepage \space
```

```
            \jobname_html.idx%
        }
    }{}
    \ifbool{LWR@xindex}{
        \ifdefvoid{\LWR@xindexConfig}{
            \renewcommand{\LWR@HTMLIndexCmd}{%
                xindex
                \jobname_html.idx%
            }
        }{
            \renewcommand{\LWR@HTMLIndexCmd}{%
                xindex
                -c \LWR@xindexConfig \space
                \jobname_html.idx%
            }
        }
    }{}
}{}

\ifdefempty{\LWR@LatexmkIndexCmd}{
    \renewcommand{\LWR@LatexmkIndexCmd}{%
        makeindex  -s \LWR@makeindexStyle%
    }
    \ifbool{LWR@xindy}{
        \renewcommand{\LWR@LatexmkIndexCmd}{%
            xindy
            -M \LWR@xindyStyle \space
            -L \LWR@xindyLanguage \space
            -C \LWR@xindyCodepage%
        }
    }{}
    \ifbool{LWR@xindex}{
        \ifdefvoid{\LWR@xindexConfig}{
            \renewcommand{\LWR@LatexmkIndexCmd}{%
                xindex
            }
        }{
            \renewcommand{\LWR@LatexmkIndexCmd}{%
                xindex
                -c \LWR@xindexConfig
            }
        }
    }{}
}{}
```

29.2 Conditional compilation

`\warpprintonly` {⟨*contents*⟩}

Only process the contents if producing printed output.

```
\newcommand{\warpprintonly}[1]{\ifbool{warpingprint}{#1}{}}
```

`\warpHTMLonly` {⟨*contents*⟩}

Only process the contents if producing HTML output.

```
\newcommand{\warpHTMLonly}[1]{\ifbool{warpingHTML}{#1}{}}
```

Pkg comment Provides conditional code blocks.

Attempts to use versions or verbatim fail in some cases, and do not provide much of a speed benefit even when they do work.

```
\RequirePackage{comment}
```

\LWR@includecomment {⟨*env name*⟩} {⟨*partial filename*⟩}

\LWR@excludecomment {⟨*env name*⟩} {⟨*partial filename*⟩}

Use many comment cut files to avoid collision in case the user uses the comment package. Each filename is "comment_#2.cut". Based on the comment package.

```
\def\LWR@includecomment
 #1#2{\message{Lwarp: Including comment '#1'}%
    \csarg\def{After#1Comment}{%
        \CloseAndInputCutFile%
        \csundef{LWR@#1commentused}%
    }
    \csarg\def{#1}{%
        \endgroup
        \ifcsdef{LWR@#1commentused}{
            \PackageError{lwarp}%
                {Nested #1 environment}%
                {%
                    Environment #1 cannot be nested.\MessageBreak
                    This can happen when a package is loaded
                    from inside a\MessageBreak
                    #1 environment.%
                }%
        }{\relax}
        \csdef{LWR@#1commentused}{}
        \message{Including '#1' comment.}%
        \def\CommentCutFile{comment_#2.cut}
        \SetUpCutFile
        \ProcessComment{#1}
    }%
    \CommentEndDef{#1}
}

\def\LWR@excludecomment
 #1#2{\message{Lwarp: Excluding comment '#1'}%
    \csarg\def{#1}{
        \endgroup
        \message{Excluding '#1' comment.}%
        \begingroup
           \def\CommentCutFile{comment_#2.cut}
            \def\ProcessCutFile{}%
           \def\ThisComment####1{}%
```

```
            \ProcessComment{#1}
    }%
    \csarg\def{After#1Comment}{\CloseAndInputCutFile \endgroup}
    \CommentEndDef{#1}}
```

Env `warpall` Anything in the `warpall` environment will be generated for print or HTML outputs.

```
\LWR@includecomment{warpall}{all}
```

Env `warpHTML` For HTML output:

```
\ifbool{warpingHTML}
    {\LWR@includecomment{warpHTML}{html}}
    {\LWR@excludecomment{warpHTML}{html}}
```

Env `warpprint` Anything in the `warpprint` environment will be generated for print output only.

```
\ifbool{warpingprint}
    {\LWR@includecomment{warpprint}{print}}
    {\LWR@excludecomment{warpprint}{print}}
```

Env `warpMathJax` Only if MathJax is being used along with HTML.

```
\begin{warpprint}
\LWR@excludecomment{warpMathJax}{mathjax}
\end{warpprint}

\begin{warpHTML}
\ifbool{mathjax}
    {\LWR@includecomment{warpMathJax}{mathjax}}
    {\LWR@excludecomment{warpMathJax}{mathjax}}
\end{warpHTML}
```

Env `LWRcreatelwarpmk` Optionally generate a local copy of *lwarpmk*. Default to no.

```
\ifbool{LWR@creatinglwarpmk}
    {\LWR@includecomment{LWRcreatelwarpmk}{lwarpmk}}
    {\LWR@excludecomment{LWRcreatelwarpmk}{lwarpmk}}
```

30 Required packages

These packages are automatically loaded by lwarp when generating HTML output. Some of them are also automatically loaded when generating print output, but some are not.

for HTML output:

```
\begin{warpHTML}
```

Pkg `fontspec` Load fontspec if necessary:

```
\ifxetexorluatex
```

```
\@ifpackageloaded{fontspec}{}{
    \usepackage[no-math]{fontspec}
}
```

The monospaced font is used for HTML tags, so turn off its TeX ligatures and common ligatures:

```
\defaultfontfeatures[\rmfamily]{Ligatures={NoCommon,TeX}}
\defaultfontfeatures[\sffamily]{Ligatures={NoCommon,TeX}}
\defaultfontfeatures[\ttfamily]{Ligatures=NoCommon}
\else
```

pdflatex only: Only pre-loaded if *pdflatex* is being used.

Pkg microtype

ligatures Older browsers don't display ligatures. Turn off letter ligatures, keeping LaTeX dash and quote ligatures, which may fail on older browers but at least won't corrupt written words.

```
\RequirePackage {microtype}

\microtypesetup{
    protrusion=false,
    expansion=false,
    tracking=false,
    kerning=false,
    spacing=false}
%    \begin{macrocode}
%
% Disable ligatures for typewriter fonts.
% The comma was causing issues with \brand{MathJax} and \cs{,} followed by a comma.
% Ligatures for f, q, t, etc used to be disabled for non-typewriter fonts, but
% are now allowed.
% \changes{v0.89}{2020/08/01}{Disable typewriter ligatures.}
% ^^A \DisableLigatures[{,},f,q,t,T,Q]{encoding = *,family = *}% previous
%    \begin{macrocode}
\DisableLigatures{encoding = *,family = tt*}

\fi

\end{warpHTML}
```

Pkg geometry Tactics to avoid unwanted page breaks and margin overflow:

- Uses a very long and wide page to minimize page breaks and margin overflow.
- Uses a scriptsize font.
- Uses extra space at the margin to avoid HTML tag overflow off the page.
- Forces a new PDF page before some environments.
- Forces line break between major pieces of long tags.

for HTML output:

```
\begin{warpHTML}
```

If geometry has not yet been loaded, use the preexising page and text sizes to be preserved for later reuse. These will be replaced by lwarp `\AtBeginDocument` with a very large page size to reduce HTML tag overflow off the page.

```
\@ifpackageloaded{geometry}
{}{
    \RequirePackage[
        reset,
        paperwidth=\paperwidth,
        paperheight=\paperheight,
        textwidth=\textwidth,
        textheight=\textheight,
        left=\oddsidemargin,
        top=\topmargin,
        marginparsep=\marginparsep,
        marginparwidth=\marginparwidth,
    ]{geometry}
}
```

Remember the original definitions for later reuse. If the geometry package is loaded by the user, lwarp-geometry will nullify the user-level originals.

```
\LetLtxMacro\LWR@origgeometry\geometry
\LetLtxMacro\LWR@orignewgeometry\newgeometry
\LetLtxMacro\LWR@origrestoregeometry\restoregeometry
\LetLtxMacro\LWR@origsavegeometry\savegeometry
\LetLtxMacro\LWR@origloadgeometry\loadgeometry
```

Bool `LWR@allowanothergeometry`

geometry may be loaded by the user before lwarp, after lwarp, or not at all. If before lwarp, it will have already been loaded by now and its page layout has already been saved. If geometry is loaded after lwarp, its layout will be set at that time and the user macros nullified. `\AtEndPreamble` this layout will be saved. If the user never loads geometry, lwarp-geometry will be loaded `\AtBeginDocument`, but it should not change the page layout set here. This is controlled by the boolean `LWR@allowanothergeometry`. Geometry may be adjusted throughout the preamble until `\AtEndPreamble`, when this boolean is set `false`.

```
\newbool{LWR@allowanothergeometry}
\booltrue{LWR@allowanothergeometry}
```

Use `\AtEndPreamble` to avoid class and option conflict by changing settings after other packages load, instead of using geometry package options:

```
\AtEndPreamble{
```

Whatever geometry choices the user has made in the preamble, either before or after lwarp was loaded, are now saved for possible temporary reuse, such as by lyluatex.

See the lwarp-geometry section for what happens if geometry is loaded after lwarp.

```
\LWR@origsavegeometry{LWR@usergeometry}
```

The user's paper size is saved for later reuse, such as by the pdfpages or parallel packages.

```
\newlength{\LWR@userspaperwidth}
\setlength{\LWR@userspaperwidth}{\paperwidth}

\newlength{\LWR@userspaperheight}
\setlength{\LWR@userspaperheight}{\paperheight}

\newlength{\LWR@usersmarginparwidth}
\setlength{\LWR@usersmarginparwidth}{\marginparwidth}

\newlength{\LWR@userstextwidth}
\setlength{\LWR@userstextwidth}{\textwidth}

\newlength{\LWR@userstextheight}
\setlength{\LWR@userstextwidth}{\textheight}
```

For lwarp, use a very large page and margins to help avoid letting HTML tags run off the edge:

```
\LWR@origgeometry{
    reset,
    paperheight=190in,
    paperwidth=20in,
    left=2in,
    right=6in,
    top=1in,
    bottom=1in,
    heightrounded,%
}
```

The lwarp page geometry is saved for future restore:

```
\LWR@origsavegeometry{LWR@lwarpgeometry}
```

No longer adjust the page layout when lwarp-geometry is loaded `\AtBeginDocument`:

```
\boolfalse{LWR@allowanothergeometry}%
```

ltjsbook and other classes can print vertically, and require these to be reset by lwarp:

```
\setlength{\textheight}{0.8\paperheight}
\setlength{\textwidth}{0.7\paperwidth}

\@twosidefalse
\@mparswitchfalse
}% \AtEndPreamble

\end{warpHTML}
```

for HTML & PRINT:

```
\begin{warpall}
```

Pkg xparse

LaTeX3 command argument parsing

```
\RequirePackage{xparse}
```

Pkg calc

```
\RequirePackage{calc}
```

```
\end{warpall}
```

for HTML output:

```
\begin{warpHTML}
```

Pkg expl3

LaTeX3 programming

```
\RequirePackage{expl3}
```

Pkg gettitlestring

Used to emulate `\nameref`.

```
\RequirePackage{gettitlestring}
```

Pkg everyhook

everyhook is used to patch paragraph handling.

```
\@ifundefined{bxjs@everypar}{}{\let\everypar\bxjs@everypar}

\RequirePackage{everyhook}
\end{warpHTML}
```

for HTML & PRINT:

```
\begin{warpall}
```

Pkg filecontents

Used to write helper files while creating the print version.

Recent versions of LaTeX (as of Fall 2019) now include the functionality of the filecontents package, but with a new optional argument used to specify whether to force the overwriting of an existing file. If an older LaTeX kernel is used, the original filecontents package is used, but it is patched to throw away the new optional argument.

```
\@ifundefined{filec@ntents@opt}{% older kernel, discard optional args

    \RequirePackage{filecontents}

    \LetLtxMacro\LWR@orig@filec@ntents\filec@ntents

    \@ifpackagelater{filecontents}{2011/10/08}
    {
```

For a newer version of the filecontents package, simply discard the optional argument.

```
        \renewcommand*{\filec@ntents}[1][]{\LWR@orig@filec@ntents}
    }
    {% patch older package for morewrites
```

For an older version of filecontents, discard the optional argument, and also patch to work with morewrites, per https://tex.stackexchange.com/questions/312830/does-morewrites-not-support-filecontents-and-can-i-write-body-of-environment-us/312910

```
        \newwrite\fcwrite
        \renewcommand*{\filec@ntents}[1][]{%
            \def\chardef##1\write{\let\reserved@c\fcwrite}%
            \LWR@orig@filec@ntents%
        }
    }

}% older kernel
{% newer kernel
```

For a newer kernel with a `filecontents` environment which accepts the optional `overwrite` argument, use the environment as-is.

```
}% newer kernel, filecontents env accepts optional args, do not load package

\end{warpall}
```

for HTML output:

```
\begin{warpHTML}
```

Pkg xifthen

```
\RequirePackage{xifthen}
```

Pkg verbatim

```
\RequirePackage{verbatim}
```

Pkg refcount

Provides `\setcounterref`, `\setcounterpageref`, etc.

```
\RequirePackage{refcount}
```

Pkg newfloat

```
\RequirePackage{newfloat}

\end{warpHTML}
```

for HTML & PRINT:

```
\begin{warpall}
```

Pkg xstring

There was a short-term bug in xstring regarding `\IfInteger` which affected lwarp's index

⚠ index generation. The updated version is requested here.

```
\RequirePackage{xstring}[2019/02/01]
```

Pkg environ Used to encapsulate math environments for re-use in HTML <alt> text.

```
\RequirePackage{environ}
```

```
\end{warpall}
```

for HTML output:

```
\begin{warpHTML}
```

Pkg printlen Used to convert lengths for image width/height options.

```
\RequirePackage{printlen}
```

\LWR@printlength {⟨*length*⟩}

Prints a length using a locally-controlled unit and space. Rounding is used unless the length is small.

```
\newrobustcmd*{\LWR@printlength}[1]{%
    \begingroup%
    \uselengthunit{PT}%
    \renewcommand*{\unitspace}{}%
    \ifdimless{#1}{10pt}{%
        \printlength{#1}%
    }{%
        \rndprintlength{#1}%
    }%
    \endgroup%
}
```

```
\end{warpHTML}
```

for PRINT output:

```
\begin{warpprint}
```

Pkg varwidth Used for print-mode lateximage.

```
\RequirePackage{varwidth}
```

```
\end{warpprint}
```

31 Loading packages

\RequirePackage and \usepackage are modified to error-check for certain packages, and for HTML they load the lwarp- version if it exists.

for HTML & PRINT:

```
\begin{warpall}
```

Remember the original \RequirePackage:

```
\LetLtxMacro\LWR@origRequirePackage\RequirePackage
\LetLtxMacro\LWR@origRequirePackageWithOptions\RequirePackageWithOptions
```

\LWR@requirepackagenames Stores the list of required package names.

```
\newcommand*{\LWR@requirepackagenames}{}
```

\LWR@parsedrequirepackagenames Stores the parsed list of required package names after spaces are removed and lwarp- is prepended.

```
\newcommand*{\LWR@parsedrequirepackagenames}{}
```

\LWR@nullifycomment Remove the preexisting comment environment. Certain packages define it for their own use.

```
\newcommand*{\LWR@nullifycomment}{%
    \PackageInfo{lwarp}%
       {Nullifying the comment environment before loading \LWR@strresulttwo,}%
    \let\comment\relax%
    \let\endcomment\relax%
}
```

\LWR@findword [⟨*1: separator*⟩] {⟨*2: list*⟩} {⟨*3: index*⟩} [⟨*4: destination*⟩]

Note that argument 4 is passed directly to \StrBetween.

```
\newcommand*\LWR@findword[3][,]{%
    \StrBetween[#3,\numexpr#3+1]{#1#2#1}{#1}{#1}%
}
```

\LWR@checkloadnever {⟨*bad package name*⟩} {⟨*replacement package names*⟩}

From now on, check for incompatible packages loaded via \usepackage, instead of packages loaded before lwarp:

```
\LetLtxMacro\LWR@checkloadnever\LWR@afterloadnever
```

\LWR@checkloadfilename {⟨*filename*⟩} Checks if this filename should be loaded after lwarp, or never at all.

```
\newcommand*{\LWR@checkloadfilename}[1]{%
```

Remember the package name to compare with, to be used by \LWR@checkloadnever and \LWR@checkloadbefore.

```
    \edef\LWR@tempone{#1}%
```

Check against the list of packages which should never be loaded:

```
    \LWR@checkloadnevers
```

The following should only be loaded before lwarp:

```
    \LWR@checkloadbefore{ctex}
    \LWR@checkloadbefore{fontspec}
    \LWR@checkloadbefore{inputenc}
    \LWR@checkloadbefore{inputenx}
    \LWR@checkloadbefore{nfssext-cfr}
    \LWR@checkloadbefore{fontaxes}
    \LWR@checkloadbefore{kotex}
    \LWR@checkloadbefore{kpfonts}% textcomp option clash
    \LWR@checkloadbefore{luatexja}
    \LWR@checkloadbefore{luatexja-fontspec}
    \LWR@checkloadbefore{luatexko}
    \LWR@checkloadbefore{morewrites}
    \LWR@checkloadbefore{newclude}
    \LWR@checkloadbefore{newunicodechar}
    \LWR@checkloadbefore{plext}
    \LWR@checkloadbefore{xeCJK}
    \LWR@checkloadbefore{xetexko}
    \LWR@checkloadbefore{zxjatype}
}
```

`\LWR@lookforpackagename` {⟨*index*⟩}

If HTML, and if this is an lwarp-supported package name, re-direct it to the lwarp version by renaming it `lwarp-` followed by the original name.

Looks `index` deep into the list of package names, `\LWR@requirepackagenames`, and builds `\LWR@parsedrequirepackagenames` which is the modified list of names.

```
\newcommand*{\LWR@lookforpackagename}[1]{%
```

Find the `index`'th package name from the list:

```
\LWR@findword{\LWR@requirepackagenames}{#1}[\LWR@strresult]%
```

Remove blanks. The original name with blanks is in `LWR@strresult` and the final name with no blanks goes into `LWR@strresulttwo`.

```
\StrSubstitute[100]{\LWR@strresult}{ }{}[\LWR@strresulttwo]%
```

See if the package name was found:

```
\IfStrEq{\LWR@strresulttwo}{}%
{}% no filename
{% yes filename was found
```

Possible adjustments before loading the package. Maybe nullify the `comment` environment if the new package will be redefining it for a new purpose.

```
    \ifdefstring{\LWR@strresulttwo}{easyReview}{\LWR@nullifycomment}{}%
    \ifdefstring{\LWR@strresulttwo}{changes}{\LWR@nullifycomment}{}%
```

If HTML, check if the package should be loaded before lwarp, or never at all:

```
    \ifbool{warpingHTML}{\LWR@checkloadfilename{\LWR@strresulttwo}}{}%
```

If HTML, and if found, and if an lwarp-equivalent name exists, use `lwarp-*` instead.

```
    \ifboolexpr{
        bool{warpingHTML} and
        test{\IfFileExists{lwarp-\LWR@strresulttwo.sty}}
    }%
    {% lwarp-* file found
        \ifdefvoid{\LWR@parsedrequirepackagenames}{%
            \edef\LWR@parsedrequirepackagenames{lwarp-\LWR@strresulttwo}%
        }{%
            \edef\LWR@parsedrequirepackagenames{%
                \LWR@parsedrequirepackagenames,lwarp-\LWR@strresulttwo%
            }%
        }%
    }%
    {%
```

Otherwise, use the current package name.

```
        \ifdefvoid{\LWR@parsedrequirepackagenames}{%
            \edef\LWR@parsedrequirepackagenames{\LWR@strresulttwo}%
        }{%
            \edef\LWR@parsedrequirepackagenames{%
                \LWR@parsedrequirepackagenames,\LWR@strresulttwo%
            }%
        }%
    }% no lwarp-* file
}% yes filename
}
```

`\RequirePackage` `[`⟨*1: options*⟩`]` `{`⟨*2: package names*⟩`}` `[`⟨*3: version*⟩`]`

For each of many package names in a comma-separated list, if an lwarp version of a package exists, select it instead of the LaTeX version.

```
\RenewDocumentCommand{\RequirePackage}{o m o}{%
```

Redirect up to twenty names:[17]

```
\renewcommand*{\LWR@requirepackagenames}{#2}%
\renewcommand*{\LWR@parsedrequirepackagenames}{}%
\LWR@lookforpackagename{1}%
\LWR@lookforpackagename{2}%
\LWR@lookforpackagename{3}%
\LWR@lookforpackagename{4}%
\LWR@lookforpackagename{5}%
\LWR@lookforpackagename{6}%
\LWR@lookforpackagename{7}%
\LWR@lookforpackagename{8}%
\LWR@lookforpackagename{9}%
\LWR@lookforpackagename{10}%
```

[17] This was originally nine names, but then I came across a package which used twelve...

```
\LWR@lookforpackagename{11}%
\LWR@lookforpackagename{12}%
\LWR@lookforpackagename{13}%
\LWR@lookforpackagename{14}%
\LWR@lookforpackagename{15}%
\LWR@lookforpackagename{16}%
\LWR@lookforpackagename{17}%
\LWR@lookforpackagename{18}%
\LWR@lookforpackagename{19}%
\LWR@lookforpackagename{20}%
```

Error if braces are used in optional argument. This can cause an error, so tell how to avoid.

```
\IfSubStr{\detokenize\expandafter{#1}}{\LWRleftbrace}%
    {%
        \PackageError{lwarp}{%
            You used:\MessageBreak
            \protect\usepackage[#1]{#2}\MessageBreak
            Braces in the package options will fail with Lwarp.\MessageBreak
            Instead, use:\MessageBreak
            \protect\PassOptionsToPackage{#1}{#2}\MessageBreak
            \protect\usepackage{#2}\MessageBreak
            near the line number given below.\MessageBreak
            Enter 'h' for more info%
        }%
        {%
            See the Lwarp manual troubleshooting index entry for\MessageBreak
            ``package, options with braces''%
        }%
    }%
    {}% no brace
```

\RequirePackage depending on the options and version:

```
\IfValueTF{#1}%
{% options given
    \IfValueTF{#3}% version given?
        {\LWR@origRequirePackage[#1]{\LWR@parsedrequirepackagenames}[#3]}%
        {\LWR@origRequirePackage[#1]{\LWR@parsedrequirepackagenames}}%
}%
{% no options given
    \IfValueTF{#3}% version given?
        {\LWR@origRequirePackage{\LWR@parsedrequirepackagenames}[#3]}%
        {\LWR@origRequirePackage{\LWR@parsedrequirepackagenames}}%
}%
}
\LetLtxMacro\usepackage\RequirePackage
\@onlypreamble\RequirePackage
\@onlypreamble\usepackage

\end{warpall}
```

for HTML output:

```
\begin{warpHTML}
```

\LWR@ProvidesPackagePass {⟨*pkgname*⟩} [⟨*version*⟩]

Uses the original package, including options.

```
\NewDocumentCommand{\LWR@ProvidesPackagePass}{m o}{
    \PackageInfo{lwarp}{%
        Using package ‘#1’,\MessageBreak
        and adding lwarp modifications, including options,\MessageBreak%
    }%
    \IfValueTF{#2}%
        {\ProvidesPackage{lwarp-#1}[#2]}%
        {\ProvidesPackage{lwarp-#1}}%
    \DeclareOption*{%
        \PassOptionsToPackage{\CurrentOption}{#1}%
    }%
    \ProcessOptions\relax%
```

If using catoptions, an error occurs if a package is loaded with an option then loaded again with no options. lwarp does this if a package is preloaded then later patched. To avoid an error while using catoptions, if a package has already been loaded, it is loaded again with its original options.

```
    \@ifpackageloaded{#1}{%
        \edef\LWR@tempone{\csuse{opt@#1.sty}}%
        \IfValueTF{#2}%
            {%
                \expandafter\LWR@origRequirePackage%
                    \expandafter[\LWR@tempone]{#1}[#2]%
            }%
            {%
                \expandafter\LWR@origRequirePackage%
                    \expandafter[\LWR@tempone]{#1}%
            }%
    }{%
        \IfValueTF{#2}%
            {\LWR@origRequirePackage{#1}[#2]}%
            {\LWR@origRequirePackage{#1}}%
    }%
```

In some cases, the following seems to be required to avoid an “unknown option” error, such as when loading xcolor with options.

```
    \DeclareOption*{}%
    \ProcessOptions\relax%
}
```

\LWR@ProvidesPackageDropA {⟨*name*⟩} {⟨*date or -NoValue-*⟩}

Declares the package. Factored for reuse.

```
\newcommand*{\LWR@ProvidesPackageDropA}[2]{%
    \PackageInfo{lwarp}{%
        Replacing package ‘#1’ with the lwarp version,\MessageBreak
        and discarding options,%
```

```
    }%
    \IfValueTF{#2}
    {\ProvidesPackage{lwarp-#1}[#2]}
    {\ProvidesPackage{lwarp-#1}}
}
```

\LWR@ProvidesPackageDropB Nullifies then processes the options.

Seems to be required when options contain curly braces, which were causing "`Missing \begin{document}`".

```
\newcommand*{\LWR@ProvidesPackageDropB}{%
% \ProcessOptions\relax% original LaTeX code
\let\ds@\@empty%         from the original \ProcessOptions
\edef\@curroptions{}%    lwarp modification to \ProcessOptions
\@process@ptions\relax%  from the original \ProcessOptions
}
```

\LWR@ProvidesPackageDrop {⟨*pkgname*⟩} [⟨*version*⟩]

Ignores the original package and uses lwarp's version instead. Drops/discards all options.

```
\NewDocumentCommand{\LWR@ProvidesPackageDrop}{m o}{
```

Declare the package:

```
\LWR@ProvidesPackageDropA{#1}{#2}
```

Ignore all options:

```
\DeclareOption*{}
```

Process the options:

```
\LWR@ProvidesPackageDropB
}
```

```
\end{warpHTML}
```

32 File handles

Defines file handles for writes.

for HTML & PRINT:

```
\begin{warpall}
```

\LWR@quickfile For quick temporary use only. This is reused in several places.

```
\newwrite\LWR@quickfile%
```

```
\end{warpall}
```

for HTML output:
```
\begin{warpHTML}
```

`\LWR@lateximagesfile` For `<project>-images.txt`:

```
\newwrite\LWR@lateximagesfile
\end{warpHTML}
```

33 Include a file

During HTML output, `\include{<filename>}` causes the following to occur:

1. lwarp creates `<filename>_html_inc.tex` whose contents are:
   `\input <filename>.tex`
2. `<filename>_html_inc.tex` is then `\included` instead of `<filename>.tex`.
3. `<filename>_html_inc.aux` is automatically generated and used by LaTeX.

for HTML output:
```
\begin{warpHTML}
```

`\@include` {⟨*filename*⟩} Modified to load `_html_inc` files.

(Below, `\clearpage` caused missing text, and was changed to `\newpage`.)

```
\def\@include#1 {%
\immediate\openout\LWR@quickfile #1_html_inc.tex% lwarp
\immediate\write\LWR@quickfile{\string\input{#1.tex}}% lwarp
\immediate\closeout\LWR@quickfile% lwarp
\LWR@maybe@orignewpage% changed from clearpage
\if@filesw
    \immediate\write\@mainaux{\string\@input{#1_html_inc.aux}}% changed
\fi
\@tempswatrue
\if@partsw
    \@tempswafalse
    \edef\reserved@b{#1}%
    \@for\reserved@a:=\@partlist\do
    {\ifx\reserved@a\reserved@b\@tempswatrue\fi}%
\fi
\if@tempswa
    \let\@auxout\@partaux
    \if@filesw
        \immediate\openout\@partaux #1_html_inc.aux % changed
        \immediate\write\@partaux{\relax}%
    \fi
    \@input@{#1_html_inc.tex}% changed
    \LWR@maybe@orignewpage% changed from clearpage
    \@writeckpt{#1}%
    \if@filesw
```

```
        \immediate\closeout\@partaux
    \fi
\else
    \deadcycles\z@
    \@nameuse{cp@#1}%
\fi
\let\@auxout\@mainaux%
}
```

```
\end{warpHTML}
```

34 Copying a file

for HTML output:

```
\begin{warpHTML}
```

`\LWR@copyfile` {⟨*source filename*⟩} {⟨*destination filename*⟩}

Used to copy the `.toc` file to `.sidetoc` to re-print the TOC in the sideTOC navigation pane.

```
\newwrite\LWR@copyoutfile   % open the file to write to
\newread\LWR@copyinfile     % open the file to read from

\newcommand*{\LWR@copyfile}[2]{%
    \LWR@traceinfo{LWR@copyfile: copying #1 to #2}

    \immediate\openout\LWR@copyoutfile=#2
    \openin\LWR@copyinfile=#1
    \begingroup\endlinechar=-1
    \makeatletter

    \LWR@traceinfo{LWR@copyfile: about to loop}

    \loop\unless\ifeof\LWR@copyinfile
        \LWR@traceinfo{LWR@copyfile: one line}
     \read\LWR@copyinfile to\LWR@fileline  % Read one line and store it into \LWR@fileline
%   \LWR@fileline\par                   % print the content into the pdf
% print the content:
     \immediate\write\LWR@copyoutfile{\unexpanded\expandafter{\LWR@fileline}}%
    \repeat
    \immediate\closeout\LWR@copyoutfile
    \LWR@traceinfo{LWR@copyfile: done}
    \endgroup
}
```

```
\end{warpHTML}
```

35 Debugging messages

HTML comments To have the HTML output include additional HTML comments, such as which is

closing, use

```
\booltrue{HTMLDebugComments}
```

debugging information To have debug information written to the log, use

```
\tracinglwarp
```

for HTML & PRINT:

```
\begin{warpall}
```

Bool LWR@tracinglwarp True if tracing is turned on.

```
\newbool{LWR@tracinglwarp}
```

\tracinglwarp Turns on the debug tracing messages.

```
\newcommand{\tracinglwarp}{\booltrue{LWR@tracinglwarp}}
```

\LWR@traceinfo {⟨*text*⟩} If tracing is turned on, writes the text to the .log file.

```
\newcommand{\LWR@traceinfo}[1]{%
\ifbool{LWR@tracinglwarp}%
{%
    \typeout{*** lwarp: #1}%
}%
{}%
}
```

Bool HTMLDebugComments Add comments in HTML about closing s, sections, etc.
Default: false

```
\newbool{HTMLDebugComments}
\boolfalse{HTMLDebugComments}
```

If \tracinglwarp, show where preamble hooks occur:

```
\AfterEndPreamble{
\LWR@traceinfo{AfterEndPreamble}
}

\AtBeginDocument{
\LWR@traceinfo{AtBeginDocument}
}

\end{warpall}
```

36 Defining print and HTML versions of macros and environments

The following refers to defining objects inside lwarp, and is not for the user's document.

Many macros and environments must be provided as both print and HTML versions.

While generating the print version of a document, the original macros as defined by LaTeX and its packages are used as-is.

While generating the HTML version of a document, the original macro or environment is redefined to call a new HTML version or a copy of the original print version. The new HTML versions of macros and environments are used most of the time. Copies of the print versions are used inside a `latexmage` environment, which draws and remembers an image of the printed output, and also several other places.

The general structure for providing print and HTML versions of a macro or environment is as follows:

For a preexisting macro, not defined with xparse: An HTML version is provided with a special name, inside a `warpHTML` environment, then `\LWR@formatted` is used to redefine and patch various macros:

```
\begin{warpHTML}
\newcommand{\LWR@HTML@name}{...}% may also use xparse

\LWR@formatted{name}
\end{warpHTML}
```

`\LWR@formatted{name}` copies the original print version, then redefines `\name` to use either the print or HTML version depending on which mode lwarp is using. xparse may be used to define the new HTML version, even if the original did not use xparse. expl3 syntax may be used as well.

For a preexisiting environment, not defined with xparse: The process is similar. Note the use of `\LWR@formattedenv` instead of `\LWR@formatted`.

```
\begin{warpHTML}
\newenvironment{LWR@HTML@name}{...}% may also use xparse

\LWR@formattedenv{name}
\end{warpHTML}
```

If the original used xparse: A copy must be made using a new name:

```
\begin{warpHTML}
\NewDocumentCommand{\LWR@print@name}{..}{..}% copy the original

\NewDocumentCommand{\LWR@HTML@name}{..}{..}% or use \newcommand

\LWR@formatted{name}
\end{warpHTML}
```

Similar for an environment, using `\LWR@formattedenv`. (`\LWR@formatted` and `\LWR@formattedenv` use `\LetLtxMacro` to copy the original print definiton, which may not work with macros and environments created by xparse, so the print version must be manually recreated in the lwarp source.)

For a new macro or environment, not using xparse for the print version:

```
\begin{warpall}
\newcommand{\name}{...}% NOT xparse!
\end{warpall}

\begin{warpHTML}
\newcommand{\LWR@HTML@name}{...}% may use xparse for HTML

\LWR@formatted{name}
\end{warpHTML}
```

Similar for an environment. The plain `\name` or environment `name` is used for the printed version, and is placed inside `warpall`. xparse may be used for the `\LWR@HTML@<name>` version. expl3 syntax may be used for the print and HTML versions.

For a new macro or environment, using xparse: It is possible to use xparse for an entirely new macro or environment by defining the `\LWR@print@<name>` version with xparse, along with `\name` defined without xparse to refer directly to the `\LWR@print` version:

```
\begin{warpall}
\NewDocumentCommand{\LWR@print@name}{...} {...}%      -or-
\NewDocumentEnvironment{\LWR@print@name}{...} {...} {...}

% Simply a call to \LWR@print@name:
\newcommand{\name}{\LWR@print@name}%        -or-
\newenvironment{name}{\LWR@print@name}{\endLWR@print@name}
\end{warpall}

\begin{warpHTML}
\NewDocumentCommand{\LWR@HTML@name}{...} {...}%      -or-
\NewDocumentEnvironment{\LWR@HTML@name}{...} {...} {...}

\LWR@formatted{name}%    -or-
\LWR@formattedenv{name}
\end{warpHTML}
```

In general, `\LWR@formatted` or `\LWR@formattedenv` are placed inside a `warpHTML` environment, and while producing an HTML document they do the following:

- Macros are modified:
  1. The pre-existing print version `\name` is saved as `\LWR@print@<name>`, unless `\LWR@print@<name>` is already defined.
  2. The original `\name` is redefined to call either the print or HTML version depending on which format is in use at the moment, as set by `\LWR@formatting`, which is defined as either "`print`" or "`HTML`".
- When lwarp is producing a print document, the original definitions are used, as well as any new definitions defined in `warpall` above.

- When lwarp is generating HTML output, \LWR@formatting is set to "HTML", and \name is directed to \LWR@HTML@<name>.
- When lwarp is generating HTML output but enters a lateximage environment, or for some other reason needs to draw images using the original print definitions, \LWR@formatting is changed to "print" and \name is then redirected to \LWR@print@<name>, which was the original \name.

Since arguments are not handled by the new \name, any star and other arguments are processed by the print or HTML version.

Expandable versions are also provided as well. These usually are necessary for anything which could appear inside a tabular, without which a "Misplaced \omit" error may occur.

⚠ Misplaced \omit error

\LWR@expandableformatted
\LWR@expandableformattedenv

(Older versions of lwarp used \LetLtxMacro for everything, but this could fail when using macros defined by xparse. This older system is still in use for many definitions.)

for HTML output:

```
\begin{warpHTML}
```

\LWR@formatting Remembers if selected print/HTML formatting.

Used while \LWR@restoreorigformatting, such as in an lateximage. May be set to either "print" or "HTML".

```
\newcommand*{\LWR@formatting}{HTML}
```

\LWR@formatted@checkname {⟨*name*⟩}

```
\newcommand*{\LWR@formatted@checkname}[1]{%
    \ifcsundef{LWR@HTML@#1}{%
        \PackageError{lwarp}
        {%
            \protect\LWR@HTML@#1 is not defined%
        }
        {Perhaps it is misspelled.}
    }{\relax}%
}
```

\LWR@formatted@checkendname {⟨*name*⟩}

```
\newcommand*{\LWR@formatted@checkendname}[1]{%
    \ifcsundef{endLWR@HTML@#1}{%
        \PackageError{lwarp}
        {%
            \protect\endLWR@HTML@#1 is not defined%
        }
        {Perhaps it is misspelled.}
    }{\relax}%
}
```

`\LWR@formatted` {⟨*macroname*⟩} No backslash in the macro name.

If not yet defined, defines `\LWR@print@<name>` as the original print-mode `\<name>`. Also redefines `\<name>` to use `\LWR@<format>@<name>`, where <format> is set by `\LWR@formatting`, and is `print` or `HTML`.

```
\newcommand*{\LWR@formatted}[1]{%
    \LWR@formatted@checkname{#1}%
    \ifcsundef{LWR@print@#1}{%
        \expandafter\LetLtxMacro\csname LWR@print@#1\expandafter\endcsname%
            \csname#1\endcsname%
    }{}%
    \ifcsundef{#1}{%
        \expandafter\newrobustcmd\csname #1\endcsname{%
            \@nameuse{LWR@\LWR@formatting @#1}%
        }%
    }{%
        \expandafter\renewrobustcmd\csname #1\endcsname{%
            \@nameuse{LWR@\LWR@formatting @#1}%
        }%
    }%
}
```

`\LWR@expandableformatted` {⟨*macroname*⟩} No backslash in the macro name.

An expandable version of `\LWR@formatted`.

```
\newcommand*{\LWR@expandableformatted}[1]{%
    \LWR@formatted@checkname{#1}%
    \ifcsundef{LWR@print@#1}{%
        \expandafter\LetLtxMacro\csname LWR@print@#1\expandafter\endcsname%
            \csname#1\endcsname%
    }{}%
    \ifcsundef{#1}{%
        \expandafter\newcommand\csname #1\endcsname{%
            \@nameuse{LWR@\LWR@formatting @#1}%
        }%
    }{%
        \expandafter\renewcommand\csname #1\endcsname{%
            \@nameuse{LWR@\LWR@formatting @#1}%
        }%
    }%
}
```

`\LWR@formattedenv` {⟨*environmentname*⟩}

If not yet defined, defines the environment `LWR@print@<name>` as the original print-mode `<name>`. Also redefines the environment `<name>` to use environment `LWR@<format>@<name>`, where <format> is set by `\LWR@formatting`, and is `print` or `HTML`.

```
\newcommand*{\LWR@formattedenv}[1]{%
    \LWR@formatted@checkname{#1}%
    \LWR@formatted@checkendname{#1}%
    \ifcsundef{LWR@print@#1}{%
```

```
        \expandafter\LetLtxMacro\csname LWR@print@#1\expandafter\endcsname%
            \csname#1\endcsname%
        \csletcs{endLWR@print@#1}{end#1}%
    }{}%
    \DeclareDocumentEnvironment{#1}{}%
    {%
        \@nameuse{LWR@\LWR@formatting @#1}%
    }%
    {%
        \@nameuse{endLWR@\LWR@formatting @#1}%
    }%
}
```

`\LWR@expandableformattedenv` {⟨*environmentname*⟩}

An expandable version of `LWR@formattedenv`.

```
\newcommand*{\LWR@expandableformattedenv}[1]{%
    \LWR@formatted@checkname{#1}%
    \LWR@formatted@checkendname{#1}%
    \ifcsundef{LWR@print@#1}{%
        \expandafter\LetLtxMacro\csname LWR@print@#1\expandafter\endcsname%
            \csname#1\endcsname%
        \csletcs{endLWR@print@#1}{end#1}%
    }{}%
    \DeclareExpandableDocumentEnvironment{#1}{}%
    {%
        \@nameuse{LWR@\LWR@formatting @#1}%
    }%
    {%
        \@nameuse{endLWR@\LWR@formatting @#1}%
    }%
}
```

```
\end{warpHTML}
```

37 HTML-conversion output modifications

These booleans modify the HTML output in various ways to improve conversion to EPUB or word processor imports.

for HTML & PRINT:

```
\begin{warpall}
```

37.1 User-level controls

Bool `FormatEPUB`
Default: `false`

Changes HTML output for easy EPUB conversion via an external program. Removes per-file headers, footers, and nav. Adds footnotes per chapter/section.

```
\newbool{FormatEPUB}
\boolfalse{FormatEPUB}
```

Bool FormatWP
Default: false

Changes HTML output for easier conversion by a word processor. Removes headers and nav, prints footnotes per section, and also forces single-file output and turns off HTML debug comments.

```
\newbool{FormatWP}
\boolfalse{FormatWP}
```

Bool WPMarkFloats
Default: false

Adds

```
=== begin table ===
. . .
=== end ===
```

or

```
=== begin figure ===
. . .
=== end ===
```

around floats while formatting for word processors. This helps identify boundaries of floats to be manually converted to word-processor frames and captions. [18]

```
\newbool{WPMarkFloats}
\boolfalse{WPMarkFloats}
```

Bool WPMarkMinipages
Default: false

Adds

```
=== begin minipage ===
. . .
=== end minipage ===
```

around minipages while formatting for word processors. This helps identify boundaries of minipages to be manually converted to word-processor frames.

```
\newbool{WPMarkMinipages}
\boolfalse{WPMarkMinipages}
```

Bool WPMarkTOC
Default: true

While formatting for word processors, adds

```
=== table of contents ===
```

where the Table of Contents would have been. This helps identify where to insert the actual TOC.

If set `false`*, the actual* TOC *is printed instead.*

```
\newbool{WPMarkTOC}
\booltrue{WPMarkTOC}
```

Bool WPMarkLOFT
Default: false

While formatting for word processors, adds

```
=== list of figures ===    and/or
=== list of tables ===
```

[18] Perhaps some day word processors will have HTML import options for identifying `<figure>` and caption tags for figures and tables.

where each of these lists would have been. This helps identify where to insert the actual lists.

If set `false`*, the actual lists are printed instead.*

```
\newbool{WPMarkLOFT}
\boolfalse{WPMarkLOFT}
```

Bool `WPMarkMath` Default: `false`

While formatting for word processors, prints math as LaTeX code instead of creating SVG images or MathJax. This is useful for cut/paste into the *LibreOffice Writer TeXMaths* extension.

```
\newbool{WPMarkMath}
\boolfalse{WPMarkMath}
```

Bool `WPTitleHeading` Default: `false`

While formatting for word processors, `true` sets the document title to <h1>, which is expected for HTML documents, but also causes the lower-level section headings to start at **Heading 2** when imported into LibreOffice. Set to `false` to cause the title to be plain text, and the section headings to begin at **Heading 1**.

See table 11 on page 187.

```
\newbool{WPTitleHeading}
\boolfalse{WPTitleHeading}
```

```
\end{warpall}
```

37.2 Heading adjustments

If formatting the HTML for a word processor, adjust heading levels.

If `WPTitleHeading` is true, adjust so that `part` is **Heading 1**.

If `WPTitleHeading` is false, use <h1> for the title, and set `part` to **Heading 2**.

for HTML output:

```
\begin{warpHTML}
```

```
\AtBeginDocument{
\ifbool{FormatWP}{
\@ifundefined{chapter}{
\ifbool{WPTitleHeading}{% part and section starting at h2
\renewcommand*{\LWR@tagtitle}{h1}
\renewcommand*{\LWR@tagtitleend}{/h1}
\renewcommand*{\LWR@tagpart}{h2}
\renewcommand*{\LWR@tagpartend}{/h2}
\renewcommand*{\LWR@tagsection}{h3}
\renewcommand*{\LWR@tagsectionend}{/h3}
\renewcommand*{\LWR@tagsubsection}{h4}
\renewcommand*{\LWR@tagsubsectionend}{/h4}
\renewcommand*{\LWR@tagsubsubsection}{h5}
\renewcommand*{\LWR@tagsubsubsectionend}{/h5}
\renewcommand*{\LWR@tagparagraph}{h6}
\renewcommand*{\LWR@tagparagraphend}{/h6}
```

```
\renewcommand*{\LWR@tagsubparagraph}{span class=\textquotedbl{}subparagraph\textquotedbl}
\renewcommand*{\LWR@tagsubparagraphend}{/span}
}% WPTitleHeading
{% not WPTitleHeading, part and section starting at h1
\renewcommand*{\LWR@tagtitle}{div class=\textquotedbl{}title\textquotedbl}
\renewcommand*{\LWR@tagtitleend}{/div}
\renewcommand*{\LWR@tagpart}{h1}
\renewcommand*{\LWR@tagpartend}{/h1}
\renewcommand*{\LWR@tagsection}{h2}
\renewcommand*{\LWR@tagsectionend}{/h2}
\renewcommand*{\LWR@tagsubsection}{h3}
\renewcommand*{\LWR@tagsubsectionend}{/h3}
\renewcommand*{\LWR@tagsubsubsection}{h4}
\renewcommand*{\LWR@tagsubsubsectionend}{/h4}
\renewcommand*{\LWR@tagparagraph}{h5}
\renewcommand*{\LWR@tagparagraphend}{/h5}
\renewcommand*{\LWR@tagsubparagraph}{h6}
\renewcommand*{\LWR@tagsubparagraphend}{/h6}
}% not WPTitleHeading
}% chapter undefined
{% chapter defined
\ifbool{WPTitleHeading}{}
{% not WPTitleHeading, part and chapter starting at h1
\renewcommand*{\LWR@tagtitle}{div class=\textquotedbl{}title\textquotedbl}
\renewcommand*{\LWR@tagtitleend}{/div}
\renewcommand*{\LWR@tagpart}{h1}
\renewcommand*{\LWR@tagpartend}{/h1}
\renewcommand*{\LWR@tagchapter}{h2}
\renewcommand*{\LWR@tagchapterend}{/h2}
\renewcommand*{\LWR@tagsection}{h3}
\renewcommand*{\LWR@tagsectionend}{/h3}
\renewcommand*{\LWR@tagsubsection}{h4}
\renewcommand*{\LWR@tagsubsectionend}{/h4}
\renewcommand*{\LWR@tagsubsubsection}{h5}
\renewcommand*{\LWR@tagsubsubsectionend}{/h5}
\renewcommand*{\LWR@tagparagraph}{h6}
\renewcommand*{\LWR@tagparagraphend}{/h6}
\renewcommand*{\LWR@tagsubparagraph}{span class=\textquotedbl{}subparagraph\textquotedbl}
\renewcommand*{\LWR@tagsubparagraphend}{/span}
}% not WPTitleHeading
}% chapter defined
}{}% FormatWP
}% AtBeginDocument

\end{warpHTML}
```

38 Remembering original formatting macros

for HTML output:

```
\begin{warpHTML}
```

Remember original definitions of formatting commands. Will be changed to HTML commands for most uses. Will be temporarily restored to original meaning inside any latexmage environment. Also nullify unused commands.

Some packages redefine \#, which is used to generate HTML, so the original must be remembered here.

```
\chardef\LWR@origpound=‘\#

\let\LWR@origcomma\,
\let\LWR@origthinspace\thinspace
\let\LWR@orignegthinspace\negthinspace
\let\LWR@origtilde~
\let\LWR@origenskip\enskip
\let\LWR@origquad\quad
\let\LWR@origqquad\qquad
\let\LWR@orighfil\hfil
\let\LWR@orighss\hss
\let\LWR@origllap\llap
\let\LWR@origrlap\rlap
\let\LWR@orighfilneg\hfilneg
\let\LWR@orighspace\hspace

\let\LWR@origrule\rule

\let\LWR@origmedskip\medskip
\let\LWR@origbigskip\bigskip

\let\LWR@origtextellipsis\textellipsis

\let\LWR@origvdots\vdots
```

libertinus-otf has too much kerning for \textquotedbl, causing an extra space.

```
\LetLtxMacro\LWR@orig@@textquotedbl\textquotedbl
\LetLtxMacro\LWR@orig@textquotedbl\LWR@orig@@textquotedbl

\AtEndPreamble{
\@ifpackageloaded{libertinus-otf}{
    \renewcommand{\LWR@orig@textquotedbl}{\LWR@orig@@textquotedbl\kern-.15em}
    \LetLtxMacro\textquotedbl\LWR@orig@textquotedbl
}{}
}

\LetLtxMacro\LWR@origttfamily\ttfamily

\LetLtxMacro\LWR@origem\em

\LetLtxMacro\LWR@orignormalfont\normalfont

\let\LWR@origonecolumn\onecolumn

\let\LWR@origsp\sp
\let\LWR@origsb\sb

\LetLtxMacro\LWR@origunderline\underline

\let\LWR@orignewpage\newpage
```

```
\let\LWR@origpagestyle\pagestyle
\let\LWR@origthispagestyle\thispagestyle
\LetLtxMacro\LWR@origpagenumbering\pagenumbering

\let\LWR@orignewline\newline

\AtBeginDocument{% in case packages change definition
\let\LWR@orig@trivlist\@trivlist
\let\LWR@origtrivlist\trivlist
\let\LWR@origendtrivlist\endtrivlist
\LetLtxMacro\LWR@origitem\item
\LetLtxMacro\LWR@origitemize\itemize
\LetLtxMacro\LWR@endorigitemize\enditemize
\LetLtxMacro\LWR@origenumerate\enumerate
\LetLtxMacro\LWR@endorigenumerate\endenumerate
\LetLtxMacro\LWR@origdescription\description
\LetLtxMacro\LWR@endorigdescription\enddescription
\let\LWR@orig@mklab\@mklab
\let\LWR@origmakelabel\makelabel
\let\LWR@orig@donoparitem\@donoparitem
\LetLtxMacro\LWR@orig@item\@item
\let\LWR@orig@nbitem\@nbitem
}

\let\LWR@origpar\par

\LetLtxMacro\LWR@origfootnote\footnote
\let\LWR@orig@mpfootnotetext\@mpfootnotetext


\AtBeginDocument{% in case packages change definition
\LetLtxMacro\LWR@orighline\hline%
\LetLtxMacro\LWR@origcline\cline%
}

\end{warpHTML}
```

39 Accents

Native LaTeX accents such as \" will work, but many more kinds of accents are available when using Unicode-aware XeLaTeX and LuaLaTeX. If using accents in section names which will become file names, it is recommended to use the LaTeX accents such as \" and \v instead of Unicode accents. The LaTeX accents will have the accents stripped when creating the filenames, whereas the Unicode accents will appear in the file names, which may cause issues with some operating systems.

for HTML output:

```
\begin{warpHTML}
```

Without `\AtBeginDocument`, `\t` was being re-defined somewhere.

```
\AtBeginDocument{
```

The following are restored for print when inside a `lateximage`.

For Unicode engines, only `\t` needs to be redefined:

```
\LetLtxMacro\LWR@origtie\t
```

For pdfLaTeX, additional work is required:

```
\ifPDFTeX% pdflatex or dvi latex
\LetLtxMacro\LWR@origgraveaccent\‘
\LetLtxMacro\LWR@origacuteaccent\’
\LetLtxMacro\LWR@origcircumflexaccent\^
\LetLtxMacro\LWR@origtildeaccent\~
\LetLtxMacro\LWR@origmacronaccent\=
\LetLtxMacro\LWR@origbreve\u
\LetLtxMacro\LWR@origdotaccent\.
\LetLtxMacro\LWR@origdiaeresisaccent\"
\LetLtxMacro\LWR@origdoubleacuteaccent\H
\LetLtxMacro\LWR@origcaronaccent\v
\LetLtxMacro\LWR@origdotbelowaccent\d
\LetLtxMacro\LWR@origcedillaaccent\c
\LetLtxMacro\LWR@origmacronbelowaccent\b
```

The HTML redefinitions follow.

For pdfLaTeX, Unicode diacritical marks are used:

```
\renewcommand*{\‘}[1]{#1\HTMLunicode{0300}}
\renewcommand*{\’}[1]{#1\HTMLunicode{0301}}
\renewcommand*{\^}[1]{#1\HTMLunicode{0302}}
\renewcommand*{\~}[1]{#1\HTMLunicode{0303}}
\renewcommand*{\=}[1]{#1\HTMLunicode{0304}}
\renewcommand*{\u}[1]{#1\HTMLunicode{0306}}
\renewcommand*{\.}[1]{#1\HTMLunicode{0307}}
\renewcommand*{\"}[1]{#1\HTMLunicode{0308}}
\renewcommand*{\H}[1]{#1\HTMLunicode{030B}}
\renewcommand*{\v}[1]{#1\HTMLunicode{030C}}
\renewcommand*{\d}[1]{#1\HTMLunicode{0323}}
\renewcommand*{\c}[1]{#1\HTMLunicode{0327}}
\renewcommand*{\b}[1]{#1\HTMLunicode{0331}}
\fi
```

For all engines, a Unicode diacritical tie is used:

```
\def\LWR@t#1#2{#1\HTMLunicode{0361}#2}
\renewcommand*{\t}[1]{\LWR@t#1}
```

`\LWR@restoreorigaccents` Called from `\restoreoriginalformatting` when a `lateximage` is begun.

```
\ifPDFTeX% pdflatex or dvi latex
\newcommand*{\LWR@restoreorigaccents}{%
    \LetLtxMacro\‘\LWR@origgraveaccent%
    \LetLtxMacro\’\LWR@origacuteaccent%
    \LetLtxMacro\^\LWR@origcircumflexaccent%
    \LetLtxMacro\~\LWR@origtildeaccent%
```

```
    \LetLtxMacro\=\LWR@origmacronaccent%
    \LetLtxMacro\u\LWR@origbreve%
    \LetLtxMacro\.\LWR@origdotaccent%
    \LetLtxMacro\"\LWR@origdiaeresisaccent%
    \LetLtxMacro\H\LWR@origdoubleacuteaccent%
    \LetLtxMacro\v\LWR@origcaronaccent%
    \LetLtxMacro\t\LWR@origtie%
    \LetLtxMacro\d\LWR@origdotbelowaccent%
    \LetLtxMacro\c\LWR@origcedillaaccent%
    \LetLtxMacro\b\LWR@origmacronbelowaccent%
}%
\else% XeLaTeX, LuaLaTeX:
\newcommand*{\LWR@restoreorigaccents}{%
    \LetLtxMacro\t\LWR@origtie%
}%
\fi%
}% AtBeginDocument

\end{warpHTML}
```

40 Configuration files

40.1 Decide whether to generate configuration files

Configuration files are only written if processing the print version of the document, and not processing a pstool image. pstool uses an additional compile for each image using the original document's preamble, which includes lwarp, so the lwarp configuration files are turned off if `-pstool` is part of the `\jobname`.

Default to no configuration files:

```
\LWR@excludecomment{LWRwriteconf}{writeconf}
```

Generate configuration files if print mode and not `-pstool`:

for PRINT output:

```
\begin{warpprint}
\fullexpandarg%
\IfSubStr*{\jobname}{-pstool}
    {
        \PackageInfo{lwarp}{%
            Jobname with -pstool is found.\MessageBreak
            Not generating lwarp configuration files,%
        }
    }
    {
        \PackageInfo{lwarp}{Generating lwarp configuration files,}%
        \LWR@includecomment{LWRwriteconf}{writeconf}
    }
\end{warpprint}
```

40.2 <project>_html.tex

File *_html.tex Used to allow an HTML version of the document to exist alongside the print version.

Config file:
```
\begin{LWRwriteconf}
\immediate\openout\LWR@quickfile=\jobname_html.tex
\immediate\write\LWR@quickfile{%
\detokenize{\PassOptionsToPackage}%
{warpHTML,BaseJobname=\jobname}{lwarp}%
}
\immediate\write\LWR@quickfile{%
\detokenize{\input}\string{\jobname.tex\string }%
}
\immediate\closeout\LWR@quickfile
\end{LWRwriteconf}
```

40.3 *lwarpmk* configuration files

Config file:
```
\begin{LWRwriteconf}
```

\LWR@lwarpconfversion The version number of the configuration file, allowing *lwarpmk* to detect an obsolete configuration file format. Incremented by one each time the configuration file format changes. (This is NOT the same as the lwarp version number.)

```
\newcommand*{\LWR@lwarpconfversion}{2}% also in lwarpmk.lua
```

40.3.1 Helper macros

\LWR@shellescapecmd The LaTeX compile option for shell escape, if used.

```
\ifshellescape
    \def\LWR@shellescapecmd{--shell-escape }
\else
    \def\LWR@shellescapecmd{}
\fi
```

\LWR@compilecmd {⟨*engine*⟩} {⟨*suffix*⟩}

Used to form the basic compilation command for a document, adding the optional shell escape.

Engine is *pdflatex*, etc. Suffix is empty or _html

```
\newcommand*{\LWR@compilecmd}[2]{%
    #1 \LWR@shellescapecmd \jobname#2%
}
```

\LWR@addcompilecmd {⟨*cmd*⟩} {⟨*suffix*⟩}

Adds to the compilation command.

Cmd is ***dvipdfmx***, etc. Suffix is empty or `_html`

```
\newcommand*{\LWR@addcompilecmd}[2]{%
    \LWRopseq
    #1 \jobname#2%
}
```

`\LWR@unknownengine` Error message if not sure which LaTeX engine is being used.

```
\newcommand*{\LWR@unknownengine}{%
    \PackageError{lwarp}%
        {Unknown LaTeX engine}%
        {%
            Lwarp only knows about pdflatex, DVI latex,
            xelatex, lualatex, and upLateX.%
        }%
}
```

`\LWR@latexmkvar` {⟨*varname*⟩} {⟨*value*⟩}

Adds a ***latexmk*** variable assignment.

```
\newcommand*{\LWR@latexmkvar}[2]{%
    -e
    \LWRopquote%
    \LWRdollar #1=q/#2/%
    \LWRopquote
}
```

`\LWR@latexmkcmd` {⟨***latexmk*** *options*⟩}

Sets a call to ***latexmk*** with the given options, possibly adding `--shell-escape`, and also adding the indexing program.

```
\newcommand*{\LWR@latexmkcmd}[1]{%
    latexmk  \space \LWR@shellescapecmd \space  #1 \space
    -recorder \space
    \LWR@latexmkvar{makeindex}{\LWR@LatexmkIndexCmd}%
}
```

`\LWR@latexmkdvipdfm` {⟨***dvipdfm*** *or* ***dvipdfmx***⟩}

Adds the options settings for ***dvipdfm*** or ***dvipdfmx***.

```
\newcommand*{\LWR@latexmkdvipdfm}[1]{%
    -pdfdvi \space
    \LWR@latexmkvar{dvipdf}{%
        #1
        \@percentchar O
        -o \@percentchar D
        \@percentchar S%
    }
}
```

\LWR@compileuplatex Sets compile options for upLaTeX with ujarticle or related classes.

```
\newcommand*{\LWR@compileuplatex}{
    \def\LWR@tempprintlatexcmd{%
        \LWR@compilecmd{uplatex}{}
        \LWR@addcompilecmd{dvipdfmx}{}
    }
    \def\LWR@tempHTMLlatexcmd{%
        \LWR@compilecmd{uplatex}{_html}
        \LWR@addcompilecmd{dvipdfmx}{_html}
    }
}
```

\LWR@PrintLatexCmd
\LWR@HTMLLatexCmd
If not set by the user, the following sets the command to use to compile the source to PDF form.

If using *latexmk*, a complicated string is created, eventually resulting in something such as:

For *xelatex* with `--shell-escape`:

```
[[latexmk   -xelatex   --shell-escape  -recorder
    -e '$makeindex = q/makeindex -s lwarp.ist/'  <jobname>_html]]
```

For *dvipdfmx*:

```
[[latexmk   -pdfdvi  -e '$dvipdf=q/dvipdfmx %O -o %D %S/'
    -recorder
    -e '$makeindex=q/makeindex -s lwarp.ist/'   <jobname>_html]]
```

For the following, temporary values are computed, but the permanent values are only set if the originals were not assigned by the user.

```
\ifbool{LWR@latexmk}{
```

For *latexmk* with *pdflatex* or *lualatex*:

```
    \ifpdf
```

For *latexmk* with *pdflatex*:

```
        \ifPDFTeX
            \def\LWR@latexcmd{\LWR@latexmkcmd{-pdf -dvi- -ps-}}
        \else
```

For *latexmk* with *lualatex*:

```
            \ifLuaTeX
                \def\LWR@latexcmd{\LWR@latexmkcmd{-lualatex}}
```

```
            \else
                \LWR@unknownengine
            \fi
        \fi
    \else% \ifpdf
```

For *latexmk* with *xelatex* or DVI *latex*:

```
        \ifXeTeX
```

For *latexmk* with *xelatex*:

```
            \def\LWR@latexcmd{\LWR@latexmkcmd{-xelatex}}
        \else% \ifXeTeX
```

For *latexmk* with DVI *latex*:

```
            \ifbool{LWR@dvipdfm}{
                \def\LWR@latexcmd{%
                    \LWR@latexmkcmd{%
                        \LWR@latexmkdvipdfm{dvipdfm}%
                    }
                }
            }{
                \ifbool{LWR@dvipdfmx}{
                    \def\LWR@latexcmd{%
                        \LWR@latexmkcmd{%
                            \LWR@latexmkdvipdfm{dvipdfmx}%
                        }
                    }
                }{
                    \def\LWR@latexcmd{\LWR@latexmkcmd{-pdfps}}
                }
            }
        \fi
    \fi% \ifpdf
```

The final assignment if *latexmk*:

```
    \def\LWR@tempprintlatexcmd{\LWR@latexcmd \space \jobname}
    \def\LWR@tempHTMLlatexcmd{\LWR@latexcmd \space \jobname_html}
}% latexmk
```

Without *latexmk*, the compiling command is simply the compiler name and the optional shell escape:

```
{% not latexmk
    \ifpdf
```

For *pdflatex* or *lualatex*:

```
        \ifPDFTeX
```

For *pdflatex*:

```
            \def\LWR@tempprintlatexcmd{\LWR@compilecmd{pdflatex}{}}
            \def\LWR@tempHTMLlatexcmd{\LWR@compilecmd{pdflatex}{_html}}
        \else
            \ifLuaTeX
```

For *lualatex*:

```
                \def\LWR@tempprintlatexcmd{\LWR@compilecmd{lualatex}{}}
                \def\LWR@tempHTMLlatexcmd{\LWR@compilecmd{lualatex}{_html}}
            \else
                \LWR@unknownengine
            \fi
        \fi
    \else% \ifpdf
```

For DVI *latex* or *xelatex*:

```
        \ifXeTeX
```

For *xelatex*:

```
            \def\LWR@tempprintlatexcmd{\LWR@compilecmd{xelatex}{}}
            \def\LWR@tempHTMLlatexcmd{\LWR@compilecmd{xelatex}{_html}}
        \else
```

For DVI *latex*. Default to *dvips*, unless told to use *dvipdfm* or *dvipdfmx*:

```
            \ifbool{LWR@dvipdfm}{
```

For DVI *latex* with *dvipdfm*:

```
                \def\LWR@tempprintlatexcmd{%
                    \LWR@compilecmd{latex}{}
                    \LWR@addcompilecmd{dvipdfm}{}
                }
                \def\LWR@tempHTMLlatexcmd{%
                    \LWR@compilecmd{latex}{_html}
                    \LWR@addcompilecmd{dvipdfm}{_html}
                }
            }{
                \ifbool{LWR@dvipdfmx}{
```

For DVI *latex* with *dvipdfmx*:

```
                    \def\LWR@tempprintlatexcmd{%
                        \LWR@compilecmd{latex}{}
                        \LWR@addcompilecmd{dvipdfmx}{}
                    }
                    \def\LWR@tempHTMLlatexcmd{%
                        \LWR@compilecmd{latex}{_html}
                        \LWR@addcompilecmd{dvipdfmx}{_html}
                    }
                }{% dvips
```

For DVI *latex* with *dvips* and *ps2pdf*:

```
                    \def\LWR@tempprintlatexcmd{%
                        \LWR@compilecmd{latex}{}
                        \LWR@addcompilecmd{dvips}{}
                        \LWR@addcompilecmd{ps2pdf}{}.ps
                    }
                    \def\LWR@tempHTMLlatexcmd{%
                        \LWR@compilecmd{latex}{_html}
                        \LWR@addcompilecmd{dvips}{_html}
                        \LWR@addcompilecmd{ps2pdf}{_html}.ps
                    }
                }
            }
        \fi% \ifXeTeX
    \fi% \ifpdf
}% latexmk
```

For ujarticle, utarticle, and related, using upLaTeX and *dvipdfmx*:

```
\@ifclassloaded{ujarticle}{\LWR@compileuplatex}{}
\@ifclassloaded{ujbook}{\LWR@compileuplatex}{}
\@ifclassloaded{ujreport}{\LWR@compileuplatex}{}
\@ifclassloaded{utarticle}{\LWR@compileuplatex}{}
\@ifclassloaded{utbook}{\LWR@compileuplatex}{}
\@ifclassloaded{utreport}{\LWR@compileuplatex}{}
```

Only make the setting permanent if the original was empty:

```
\ifdefempty{\LWR@PrintLatexCmd}{
    \def\LWR@PrintLatexCmd{\LWR@tempprintlatexcmd}
}{}
\ifdefempty{\LWR@HTMLLatexCmd}{
    \def\LWR@HTMLLatexCmd{\LWR@tempHTMLlatexcmd}
}{}
```

`\LWR@writeconf` {⟨*filename*⟩}

Common code for each of `lwarpmk.conf` and `<project>.lwarpmkconf`. Each entry is a variable name, the equal sign, and a quoted string inside `[[` and `]]`, which are *lua*'s long quote characters, allowing the use of single and double quotes inside.

```
\newcommand{\LWR@writeconf}[1]{
\ifcsdef{LWR@quickfile}{}{\newwrite{\LWR@quickfile}}
\immediate\openout\LWR@quickfile=#1
\immediate\write\LWR@quickfile{confversion = [[\LWR@lwarpconfversion]]}
\ifbool{usingOSWindows}{
    \immediate\write\LWR@quickfile{opsystem = [[Windows]]}
}{
    \immediate\write\LWR@quickfile{opsystem = [[Unix]]}
}
\immediate\write\LWR@quickfile{sourcename = [[\jobname]]}
\immediate\write\LWR@quickfile{homehtmlfilename = [[\HomeHTMLFilename]]}
\immediate\write\LWR@quickfile{htmlfilename = [[\HTMLFilename]]}
```

```
\immediate\write\LWR@quickfile{imagesdirectory = [[\LWR@ImagesDirectory]]}
\immediate\write\LWR@quickfile{imagesname = [[\LWR@ImagesName]]}
\immediate\write\LWR@quickfile{latexmk = [[\ifbool{LWR@latexmk}{true}{false}]]}
\immediate\write\LWR@quickfile{printlatexcmd = [[\LWR@PrintLatexCmd]]}
\immediate\write\LWR@quickfile{HTMLlatexcmd = [[\LWR@HTMLLatexCmd]]}
\immediate\write\LWR@quickfile{printindexcmd = [[\LWR@PrintIndexCmd]]}
\immediate\write\LWR@quickfile{HTMLindexcmd = [[\LWR@HTMLIndexCmd]]}
\immediate\write\LWR@quickfile{latexmkindexcmd = [[\LWR@LatexmkIndexCmd]]}
\immediate\write\LWR@quickfile{glossarycmd = [[\LWR@GlossaryCmd]]}
\immediate\write\LWR@quickfile{pdftotextenc = [[\LWR@pdftotextEnc]]}
\immediate\closeout\LWR@quickfile
}

\end{LWRwriteconf}
```

40.3.2 `lwarpmk.conf`

File `lwarpmk.conf`

`lwarpmk.conf` is automatically (re-)created by the lwarp package when executing
`pdflatex <project.tex>`,
or similar for *xelatex* or *lualatex*, in print-document generation mode, which is the default unless the `warpHTML` option is given. `lwarpmk.conf` is then used by the utility *lwarpmk*.

Config file:

```
\begin{LWRwriteconf}

\AtBeginDocument{\LWR@writeconf{lwarpmk.conf}}

\end{LWRwriteconf}
```

40.3.3 `<project>.lwarpmkconf`

File `project.lwarpmkconf`

A project-specific configuration file for *lwarpmk*.

The `makeindex` and `xindy` options have already been handled for `lwarp.conf`.

Config file:

```
\begin{LWRwriteconf}

\AtBeginDocument{\LWR@writeconf{\jobname.lwarpmkconf}}

\end{LWRwriteconf}
```

40.4 `lwarp.css`

File `lwarp.css`

This is the base css layer used by lwarp.

This must be present both when compiling the project and also when distributing the HTML files.

Config file:

```
\begin{LWRwriteconf}
\begin{filecontents*}[overwrite]{lwarp.css}
/*
```

```
  CSS stylesheet for the LaTeX Lwarp package
  Copyright 2016-2021 Brian Dunn — BD Tech Concepts LLC
*/


/* a fix for older browsers: */
header, section, footer, aside, nav, main,
    article, figure { display: block; }


A:link {color:#000080 ; text-decoration: none ; }
A:visited {color:#800000 ; }
A:hover {color:#000080 ; text-decoration: underline ;}
A:active {color:#800000 ; }

a.tocbook {display: inline-block ; margin-left: 0em ;
    font-weight: bold ; margin-top: 1ex ; margin-bottom: 1ex ; }
a.tocpart {display: inline-block ; margin-left: 0em ;
    font-weight: bold ;}
a.tocchapter {display: inline-block ; margin-left: 0em ;
    font-weight: bold ;}
a.tocsection {display: inline-block ; margin-left: 1em ;
    text-indent: -.5em ; font-weight: bold ; }
a.tocsubsection {display: inline-block ; margin-left: 2em ;
    text-indent: -.5em ; }
a.tocsubsubsection {display: inline-block ; margin-left: 3em ;
    text-indent: -.5em ; }
a.tocparagraph {display: inline-block ; margin-left: 4em ;
    text-indent: -.5em ; }
a.tocsubparagraph {display: inline-block ; margin-left: 5em ;
    text-indent: -.5em ; }
a.tocfigure {margin-left: 0em}
a.tocsubfigure {margin-left: 2em}
a.toctable {margin-left: 0em}
a.tocsubtable {margin-left: 2em}
a.toctheorem {margin-left: 0em}
a.toclstlisting {margin-left: 0em}

body {
    font-family: "DejaVu Serif", "Bitstream Vera Serif",
        "Lucida Bright", Georgia, serif;
    background: #FAF7F4 ;
    color: black ;
    margin:0em ;
    padding:0em ;
    font-size: 100% ;
    line-height: 1.2 ;
}

p {margin: 1.5ex 0em 1.5ex 0em ;}
table p {margin: .5ex 0em .5ex 0em ;}

/* Holds a section number */
span.sectionnumber { margin-right: 0em }

```

```
/* Inserted in front of index lines */
span.indexitem {margin-left: 0em}
span.indexsubitem {margin-left: 2em}
span.indexsubsubitem {margin-left: 4em}
div.indexheading {margin-top: 2ex ; font-weight: bold}

div.hidden, span.hidden { display: none ; }

kbd, span.texttt, p span.texttt {
    font-family: "DejaVu Mono", "Bitstream Vera Mono", "Lucida Console",
        "Nimbus Mono L", "Liberation Mono", "FreeMono", "Andale Mono",
        "Courier New", monospace;
    font-size: 100% ;
}

pre { padding: 3pt ; }

span.strong, span.textbf, div.strong, div.textbf { font-weight: bold; }

span.textit, div.textit { font-style: italic; }

span.textmd, div.textmd { font-weight: normal; }

span.textup, div.textup {
    font-style: normal;
    font-variant: normal;
    font-variant-numeric: normal ;
}

span.textsc, div.textsc {
    font-variant: small-caps;
    font-variant-numeric: oldstyle-nums ;
}

span.textulc, div.textulc {
    font-variant: normal ;
    font-variant-numeric: normal ;
}

span.textsl, div.textsl { font-style: oblique; }

span.textrm, div.textrm {
    font-family: "DejaVu Serif", "Bitstream Vera Serif",
    "Lucida Bright", Georgia, serif;
}

span.textsf, div.textsf {
     font-family: "DejaVu Sans", "Bitstream Vera Sans",
        Geneva, Verdana, sans-serif ;
}

/* nfssext-cfr lining figures */
span.textln, div.textln {
    font-variant-numeric: lining-nums ;
}
```

```
2335
2336 /* nfssext-cfr proportional figures */
2337 span.textp, div.textp {
2338     font-variant-numeric: proportional-nums ;
2339 }
2340
2341 /* nfssext-cfr tabular figures */
2342 span.textt, div.textt {
2343     font-variant-numeric: tabular-nums ;
2344 }
2345
2346 /* nfssext-cfr font weights */
2347 span.textdb, div.textdb {
2348     font-weight: 500 ;
2349 }
2350
2351 span.textsb, div.textsb {
2352     font-weight: 600 ;
2353 }
2354
2355 span.texteb, div.texteb {
2356     font-weight: 800 ;
2357 }
2358
2359 span.textub, div.textub {
2360     font-weight: 900 ;
2361 }
2362
2363 span.textlg, div.textlg {
2364     font-weight: 300 ;
2365 }
2366
2367 span.textel, div.textel {
2368     font-weight: 200 ;
2369 }
2370
2371 span.textul, div.textul {
2372     font-weight: 100 ;
2373 }
2374
2375
2376
2377 span.textcircled { border: 1px solid black ; border-radius: 1ex ; }
2378
2379 span.underline {
2380     text-decoration: underline ;
2381     text-decoration-skip: auto ;
2382 }
2383
2384 span.overline {
2385     text-decoration: overline ;
2386     text-decoration-skip: auto ;
2387 }
2388
2389 div.hrule { border-top: 1px solid silver }
```

```
2390
2391
2392 /* for vertical text: */
2393 div.verticalrl { writing-mode: vertical-rl }
2394 div.horizontaltb { writing-mode: horizontal-tb }
2395
2396
2397 /* for diagbox */
2398 div.diagboxtitleN { border-bottom: 1px solid gray }
2399 div.diagboxtitleS { border-top: 1px solid gray }
2400
2401 div.diagboxE {
2402     padding-left: 2em ;
2403     text-align: right ;
2404 }
2405
2406 div.diagboxW {
2407     padding-right: 2em ;
2408     text-align: left ;
2409 }
2410
2411
2412
2413 /* For realscripts */
2414 .supsubscript {
2415     display: inline-block;
2416     text-align:left ;
2417 }
2418
2419 .supsubscript sup,
2420 .supsubscript sub {
2421     position: relative;
2422     display: block;
2423     font-size: .7em;
2424     line-height: 1;
2425 }
2426
2427 .supsubscript sup {
2428     top: .3em;
2429 }
2430
2431 .supsubscript sub {
2432     top: .3em;
2433 }
2434
2435 div.attribution p {
2436     text-align: right ;
2437     font-size: 80%
2438 }
2439
2440 span.poemtitle {
2441   font-size: 120% ; font-weight: bold;
2442 }
2443
2444 pre.tabbing {
```

```
    font-family: "Linux Libertine Mono O", "Lucida Console",
        "Droid Sans Mono", "DejaVu Mono", "Bitstream Vera Mono",
        "Liberation Mono", "FreeMono", "Andale Mono",
        "Nimbus Mono L", "Courier New", monospace;
}

blockquote {
    display: block ;
    margin-left: 2em ;
    margin-right: 2em ;
}

/* quotchap is for the quotchap package */
div.quotchap {
    display: block ;
    font-style: oblique ;
    overflow-x: auto ;
    margin-left: 2em ;
    margin-right: 2em ;
}

blockquote p, div.quotchap p {
    line-height: 1.5;
    text-align: left ;
    font-size: .85em ;
}

/* qauthor is for the quotchap package */
div.qauthor {
  display: block ;
  text-align: right ;
  margin-left: auto ;
  margin-right: 2em ;
  font-size: 80% ;
  font-variant: small-caps;
}

div.qauthor p {
  text-align: right ;
}

div.epigraph, div.dictum {
  line-height: 1.2;
    text-align: left ;
    padding: 3ex 1em 0ex 1em ;
/*     margin: 3ex auto 3ex auto ; */ /* Epigraph centered */
    margin: 3ex 1em 3ex auto ; /* Epigraph to the right */
/*    margin: 3ex 1em 3ex 1em ; */ /* Epigraph to the left */
    font-size: .85em ;
    max-width: 27em ;
}

div.epigraphsource, div.dictumauthor {
    text-align:right ;
    margin-left:auto ;
```

```
/*     max-width: 50% ; */
    border-top: 1px solid #A0A0A0 ;
    padding-bottom: 3ex ;
    line-height: 1.2;
}

div.epigraph p, div.dictum p { padding: .5ex ; margin: 0ex ;}
div.epigraphsource p, div.dictumauthor p { padding: .5ex 0ex 0ex 0ex ; margin: 0ex ;}
div.dictumauthor { font-style:italic }


/* copyrightbox package: */
div.copyrightbox { margin: .5ex .5em }
div.copyrightbox p {margin: 0px .5em ; padding: 0px}
div.copyrightboxnote {text-align: left ; font-size: 60%}


/* lettrine package: */
span.lettrine { font-size: 4ex ; float: left ; }
span.lettrinetext { font-variant: small-caps ; }

/* ulem, soul, umoline packages: */
span.uline {
    text-decoration: underline ;
    text-decoration-skip: auto ;
}

span.uuline {
    text-decoration: underline ;
    text-decoration-skip: auto ;
    text-decoration-style: double ;
}

span.uwave {
    text-decoration: underline ;
    text-decoration-skip: auto ;
    text-decoration-style: wavy ;
}

span.sout {
    text-decoration: line-through ;
}

span.oline {
    text-decoration: overline ;
    text-decoration-skip: auto ;
}

span.xout {
    text-decoration: line-through ;
}

span.dashuline {
    text-decoration: underline ;
    text-decoration-skip: auto ;
```

```
    text-decoration-style: dashed ;
}

span.dotuline {
    text-decoration: underline ;
    text-decoration-skip: auto ;
    text-decoration-style: dotted ;
}

span.letterspacing { letter-spacing: .2ex ; }

span.capsspacing {
    font-variant: small-caps ;
    letter-spacing: .1ex ;
}

span.highlight { background: #F8E800 ; }


/* keystroke package: */
span.keystroke {
    border-style: outset ;
    padding: 0pt .5em 0pt .5em ;
}


html body {
  margin: 0 ;
  line-height: 1.2;
}


body div {
  margin: 0ex;
}


div.book, h1, h2, h3, h4, h5, h6, span.paragraph, span.subparagraph
{
    font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
        "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
        "Liberation Serif", "Nimbus Roman No 9 L",  "FreeSerif", Times,
        "Times New Roman", serif;
    font-style: normal ;
    font-weight: bold ;
    text-align: left ;
}

h1 {    /* title of the entire website, used on each page */
    text-align: center ;
    font-size: 2.5em ;
    padding: .4ex 0em 0ex 0em ;
}

div.book {
```

```
    text-align: center ;
    font-size: 2.325em ;
    padding: .4ex 0em 0ex 0em ;
}

h2 { font-size: 2.25em }
h3 { font-size: 2em }
h4 { font-size: 1.75em }
h5 { font-size: 1.5em }
h6 { font-size: 1.25em }
span.paragraph {font-size: 1em ; font-variant: normal ;
    margin-right: 1em ; }
span.subparagraph {font-size: 1em ; font-variant: normal ;
    margin-right: 1em ;  }

div.minisec {
    font-family: "DejaVu Sans", "Bitstream Vera Sans",
        Geneva, Verdana, sans-serif ;
    font-style: normal ;
    font-weight: bold ;
    text-align: left ;
}

h1 {
  margin: 0ex 0em 0ex 0em ;
  line-height: 1.3;
  text-align: center ;
}

h2 {
  margin: 1ex 0em 1ex 0em ;
  line-height: 1.3;
  text-align: center ;
}

h3 {
  margin: 3ex 0em 1ex 0em ;
  line-height: 1.3;
}

h4 {
  margin: 3ex 0em 1ex 0em ;
  line-height: 1.3;
}

h5 {
  margin: 3ex 0em 1ex 0em ;
  line-height: 1.3;
}

h6 {
  margin: 3ex 0em 1ex 0em ;
  line-height: 1.3;
}

```

```
2665
2666 div.titlepage {
2667   text-align: center ;
2668 }
2669
2670 .footnotes {
2671     text-align: left ;
2672     font-size: .85em ;
2673     margin: 3ex 2em 0ex 2em ;
2674     border-top: 1px solid silver ;
2675 }
2676
2677 .marginpar, .marginparblock {
2678     max-width: 50%;
2679     float: right ;
2680     clear: both ;
2681     text-align: left ;
2682     margin: 1ex 0.5em 1ex 1em ;
2683     padding: 1ex 0.5em 1ex 0.5em ;
2684     font-size: 85% ;
2685     border-top: 1px solid silver ;
2686     border-bottom: 1px solid silver ;
2687     overflow-x: auto ;
2688 }
2689
2690 .marginpar br { margin-bottom: 2ex ; }
2691
2692 div.marginblock, div.marginparblock {
2693     max-width:50%;
2694     min-width: 10em; /* room for caption */
2695     float:right;
2696     text-align:left;
2697     margin: 1ex 0.5em 1ex 1em ;
2698     padding: 1ex 0.5em 1ex 0.5em ;
2699     overflow-x: auto;
2700 }
2701
2702 div.marginblock div.minipage,
2703 div.marginparblock div.minipage {
2704     display: inline-block ;
2705     margin: 0pt auto 0pt auto ;
2706 }
2707
2708 div.marginblock div.minipage p ,
2709 div.marginparblock div.minipage p
2710     { font-size: 85%}
2711
2712 div.marginblock br ,
2713 div.marginparblock br
2714     { margin-bottom: 2ex ; }
2715
2716 main.bodycontainer {
2717     float: left ;
2718     width: 80% ;
2719 }
```

```
2720
2721 div.bodywithoutsidetoc main.bodycontainer {
2722     float: none ;
2723     width: 100% ;
2724 }
2725
2726 section.textbody div.footnotes{
2727     margin: 3ex 2em .5ex 2em ;
2728     border-bottom: 2px solid silver ;
2729 }
2730
2731 .footnoteheader {
2732     border-top: 2px solid silver ;
2733     margin-top: 3ex ;
2734     padding-top: 1ex ;
2735     font-weight: bold ;
2736 }
2737
2738 .mpfootnotes {
2739     text-align: left ;
2740     font-size: .85em ;
2741     margin-left: 1em ;
2742     border-top: 1px solid silver ;
2743 }
2744
2745 /* Remove footnote top border in the title page. */
2746 div.titlepage div.mpfootnotes {
2747     border-top: none ;
2748 }
2749
2750
2751
2752 ul, ol {
2753   margin: 1ex 1em 1ex 0em;
2754   line-height: 1.2;
2755 }
2756
2757 body dir, body menu {
2758   margin: 3ex 1em 3ex 0em;
2759   line-height: 1.2;
2760 }
2761
2762 li { margin: 0ex 0em 1ex 0em; }
2763
2764 html {
2765   margin: 0;
2766   padding: 0;
2767 }
2768
2769 .programlisting {
2770   font-family: "DejaVu Mono", "Bitstream Vera Mono", "Lucida Console",
2771         "Nimbus Mono L", "Liberation Mono", "FreeMono", "Andale Mono",
2772         "Courier New", monospace;
2773   margin: 1ex 0ex 1ex 0ex ;
2774   padding: .5ex 0pt .5ex 0pt ;
```

```
  overflow-x: auto;
}

section.textbody>pre.programlisting {
border-top: 1px solid silver ;
border-bottom: 1px solid silver ;
}


div.displaymath {
    text-align: center ;
}

div.displaymathnumbered {
    text-align: right ;
    margin-left: 5% ;
    margin-right: 5% ;
    min-width: 2.5in ;
}

@media all and (min-width: 400px) {
    div.displaymathnumbered {
        margin-left: 10% ;
        margin-right: 10% ;
    }
}

@media all and (min-width: 800px) {
    div.displaymathnumbered {
        margin-right: 20% ;
    }
}

@media all and (min-width: 1200px) {
    div.displaymathnumbered {
        margin-right: 30% ;
    }
}


.inlineprogramlisting {
  font-family: "DejaVu Mono", "Bitstream Vera Mono", "Lucida Console",
        "Nimbus Mono L", "Liberation Mono", "FreeMono", "Andale Mono",
        "Courier New", monospace;
  overflow-x: auto;
}

span.listinglabel {
    display: inline-block ;
    font-size: 70% ;
    width: 4em ;
    text-align: right ;
    margin-right: 2em ;
}

```

```
div.abstract {
  margin: 2em 5% 2em 5% ;
  padding: 1ex 1em 1ex 1em ;
/*  font-weight: bold ; */
  font-size: 90% ;
    text-align: left ;
}

div.abstract dl {line-height:1.5;}
div.abstract dt {color:#304070;}

div.abstracttitle{
    font-family: "URW Classico", Optima, "Linux Biolinum O",
        "Linux Libertine O", "Liberation Serif", "Nimbus Roman No 9 L",
        "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
    font-weight:bold;
    font-size:1.25em;
    text-align: center ;
}

span.abstractrunintitle{
    font-family: "URW Classico", Optima, "Linux Biolinum O",
        "Linux Libertine O", "Liberation Serif", "Nimbus Roman No 9 L",
        "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
    font-weight:bold;
}


.verbatim {
    overflow-x: auto ;
}

.alltt {
    overflow-x: auto ;
}


.bverbatim {
    margin: 1ex 0pt 1ex 0pt ;
    padding: .5ex 0pt .5ex 0pt ;
    overflow-x: auto ;
}

.lverbatim {
    margin: 1ex 0pt 1ex 0pt ;
    padding: .5ex 0pt .5ex 0pt ;
    overflow-x: auto ;
}

.fancyvrb {
    font-size:.85em ;
    margin: 3ex 0pt 3ex 0pt
}

.fancyvrblabel {
```

```
    font-size: .85em ;
    text-align: center ;
    font-weight: bold ;
    margin-top: 1ex ;
    margin-bottom: 1ex ;
}


.verse {
    font-family: "Linux Libertine Mono O", "Lucida Console",
        "Droid Sans Mono", "DejaVu Mono", "Bitstream Vera Mono",
        "Liberation Mono", "FreeMono", "Andale Mono",
        "Nimbus Mono L", "Courier New", monospace;
    margin-left: 1em ;
}


div.singlespace { line-height: 1.2 ; }
div.onehalfspace { line-height: 1.5 ; }
div.doublespace { line-height: 2 ; }


/* Word processor format output: */
div.wpfigure { border: 1px solid red ; margin: .5ex ; padding: .5ex ; }
div.wptable { border: 1px solid blue ; margin: .5ex ; padding: .5ex ; }
div.wpminipage { border: 1px solid green ; margin: .5ex ; padding: .5ex ;}




/* Minipage environments, vertically aligned to top, center, bottom: */
.minipage, .fminipage, .fcolorminipage {
    /* display: inline-block ; */
        /* Mini pages which follow each other will be tiled. */
    text-align:left;
    margin: .25em .25em .25em .25em;
    padding: .25em .25em .25em .25em;
    display: inline-flex;
    flex-direction: column ;
    overflow: auto;
}

.inlineminipage {
    display: inline-block ;
    text-align: left
}

/* Paragraphs in the flexbox did not collapse their margins. */
/* Have not yet researched this. */
.minipage p {margin: .75ex 0em .75ex 0em ;}

.fboxBlock .minipage, .colorbox .minipage, .colorboxBlock .minipage,
.fcolorbox .minipage, .fcolorboxBlock .minipage
    {border: none ; background: none;}

```

```
.fbox, .fboxBlock { border: 1px solid black ; }

.fbox, .fboxBlock, .fcolorbox, .fcolorboxBlock, .colorbox, .colorboxBlock,
.fminipage, .fcolorminipage
    {display: inline-block}

.shadowbox, .shabox {
   border: 1px solid black;
    box-shadow: 3px 3px 3px #808080 ;
     border-radius: 0px ;
    padding: .4ex .3em .4ex .3em ;
    margin: 0pt .3ex 0pt .3ex ;
  display: inline-block ;
}

.doublebox {
   border: 3px double black;
     border-radius: 0px ;
    padding: .4ex .3em .4ex .3em ;
    margin: 0pt .3ex 0pt .3ex ;
  display: inline-block ;
}

.ovalbox, .Ovalbox {
   border: 1px solid black;
     border-radius: 1ex ;
    padding: .4ex .3em .4ex .3em ;
    margin: 0pt .3ex 0pt .3ex ;
  display: inline-block ;
}

.Ovalbox { border-width: 2px ; }

.framebox {
   border: 1px solid black;
     border-radius: 0px ;
    padding: .3ex .2em 0ex .2em ;
    margin: 0pt .1ex 0pt .1ex ;
  display: inline-block ;
}


/* mdframed, tcolorbox, shadebox packages */
.mdframed, .tcolorbox, .shadebox {
    padding: 0ex ;
    margin: 2ex 0em 2ex 0em ;
    border: 1px solid black ;
}

.tcolorbox {
    border-radius: 10pt ;
    margin: 2ex 1em 2ex 1em ;
}

.mdframed p, .tcolorbox p { padding: 0ex .5em 0ex .5em ; }
```

```
2995
2996 .mdframed dl, .tcolorbox dl { padding: 1ex .5em 0ex .5em ; }
2997
2998 .mdframedtitle, .tcolorboxtitle {
2999     padding: .5ex 0pt 0pt 0pt ;
3000     border-radius: 10pt 10pt 0pt 0pt ;
3001     display: block ;
3002     margin-bottom: 1ex ;
3003     border-bottom: 1px solid silver ;
3004 }
3005
3006 .tcolorboxsubtitle .tcolorbox {
3007     margin: 2ex 0em 2ex 0em ;
3008     border-radius: 0pt ;
3009 }
3010
3011 .mdframedsubtitle {
3012     display: block ;
3013 }
3014
3015 .mdframedsubsubtitle {
3016     display: block ;
3017 }
3018
3019 .mdtheorem {
3020     padding: 0ex .5em 0ex .5em ;
3021     margin: 3ex 5% 3ex 5% ;
3022 }
3023
3024
3025 /* framed package */
3026 .framed, pre.boxedverbatim, fcolorbox {
3027     margin: 3ex 0em 3ex 0em ;
3028    border: 1px solid black;
3029      border-radius: 0px ;
3030     padding: .3ex 1em 0ex 1em ;
3031   display: block ;
3032 }
3033
3034 .shaded {
3035     margin: 3ex 0em 3ex 0em ;
3036     padding: .3ex 1em .3ex 1em ;
3037     display: block ;
3038 }
3039
3040 .snugframed {
3041     margin: 3ex 0em 3ex 0em ;
3042    border: 1px solid black;
3043      border-radius: 0px ;
3044   display: block ;
3045 }
3046
3047 .framedleftbar {
3048     margin: 3ex 0em 3ex 0em ;
3049    border-left: 3pt solid black;
```

```
     border-radius: 0px ;
    padding: .3ex .2em .3ex 1em ;
  display: block ;
}

.framedtitle {
    margin: 0em ;
    padding: 0em ;
    font-size: 130%
}

.framedtitle p { padding: .3em }


/* For the niceframe package: */

div.niceframe, div.curlyframe, div.artdecoframe, div.generalframe {
    padding: 1ex ;
    margin: 2ex auto ;
    border-radius: 2ex ;
}

div.niceframe {
    border: 6px groove black ;
}

div.curlyframe {
    border-left: 3px dotted black ;
    border-right: 3px dotted black ;
    border-radius: 6ex ;
}

div.artdecoframe {
    border-left: 10px double black ;
    border-right: 10px double black ;
    border-radius: 6ex ;
}

div.generalframe {
    border: 6px groove black ;
}



dl {
  margin: 1ex 2em 1ex 0em;
  line-height: 1.3;
}

dl dt {
    display: block ;
    float:left ;
    font-weight: bold;
    padding-right: 1em ;
}
```

```
3105
3106 dl dd { display: block ; }
3107
3108 dl dd:after { content: "" ; display: block ; clear: both }
3109
3110 dl dd p { margin-top: 0em; }
3111
3112 dd ul, dd ol, dd dl {
3113     clear: both ;
3114 /*    padding-top: 1ex ; */
3115 }
3116
3117
3118 nav {
3119     font-family: "URW Classico", Optima, "Linux Biolinum O",
3120         "DejaVu Sans", "Bitstream Vera Sans",
3121         Geneva, Verdana, sans-serif ;
3122     margin-bottom: 4ex ;
3123 }
3124
3125 nav p {
3126     line-height: 1.2 ;
3127     margin-top:.5ex ;
3128     margin-bottom:.5ex;
3129     font-size: .9em ;
3130 }
3131
3132
3133
3134 img, img.hyperimage, img.borderimage {
3135     max-width: 600px;
3136     border: 1px solid silver;
3137     box-shadow: 3px 3px 3px #808080 ;
3138     padding: .5% ;
3139     margin: .5% ;
3140     background: none ;
3141 }
3142
3143 img.inlineimage{
3144     padding: 0px ;
3145     box-shadow: none ;
3146     border: none ;
3147     background: none ;
3148     margin: 0px ;
3149     display: inline-block ;
3150     border-radius: 0px ;
3151 }
3152
3153 img.logoimage{
3154     max-width: 300px ;
3155     box-shadow: 3px 3px 3px #808080 ;
3156     border: 1px solid black ;
3157     background:none ;
3158     padding:0 ;
3159     margin:.5ex ;
```

```
    border-radius: 10px ;
}


.section {
/*
    To have each section float relative to each other:
*/
/*
    display: block ;
    float: left ;
    position: relative ;
    background: white ;
    border: 1px solid silver ;
    padding: .5em ;
*/
    margin: 0ex .5em 0ex .5em ;
    padding: 0 ;
}


figure {
    margin: 5ex auto 5ex auto ;
    padding: 1ex 1em 1ex 1em ;
    overflow-x: auto ;
}


/* To automatically center images in figures: */
/*
figure img.inlineimage {
    margin: 0ex auto 0ex auto ;
    display: block ;
}
*/

/* To automatically center minipages in figures: */
/*
figure div.minipage, figure div.minipage div.minipage {
    margin: 1ex auto 1ex auto ;
    display: block ;
}
*/

figure figure { margin: 0pt }

figure div.minipage p { font-size: 85% ; }

figure.subfigure, figure.subtable  {
    display: inline-block ; margin: 3ex 1em 3ex 1em ;
}

div.figurecaption .minipage { margin:0 ; padding: 0 }

div.minipage figure { border: none ; box-shadow: none ; }
```

```
div.minipage figure.table { margin: 0ex }
div.minipage div.footnotes { margin: 1ex 2em 0ex 2em }

div.floatrow { text-align: center; }

div.floatrow figure { display: inline-block ; margin: 1ex 2% ; }

div.floatfoot { font-size: .85em ;
    border-top: 1px solid silver ; line-height: 1.2 ; }

div.figurecaption , .lstlistingtitle {
    font-size: .85em ;
    text-align: center ;
    font-weight: bold ;
    margin-top: 1ex ;
    margin-bottom: 1ex ;
}

figure.subfigure div.figurecaption, figure.subtable div.figurecaption  {
    border-bottom: none ; background: none ;
}

div.nonfloatcaption {
    margin: 1ex auto 1ex auto ;
    font-size: .85em ;
    text-align: center ;
    font-weight: bold ;
}

/* For a \RawCaption inside a minipage inside a figure's floatrow: */
figure div.floatrow div.minipage div.figurecaption {
    border: none ;
    background: none ;
}


/* For packages such as float, rotfloat, and algorithm2e: */

figure.boxed, figure.boxruled {
    border: 1px solid black ;
}

figure.ruled {
    border-top: 1px solid black ;
    border-bottom: 1px solid black ;
    border-left: 0px ;
    border-right: 0px ;
    border-radius: 0px ;
    background: none ;
    box-shadow: none ;
}

figure.ruled div.figurecaption, figure.boxruled div.figurecaption {
    border-top: 1px solid silver ;
    border-bottom: 1px solid silver ;
```

```
}


table {
    margin: 1ex auto 1ex auto ;
    border-collapse: separate ;
    border-spacing: 0px ;
    line-height: 1.3 ;
    }

table > tbody > tr.hline > td {border-top: 1px solid #808080 ; margin-top: 0ex ;
    margin-bottom: 0ex ; } /* for \hline */

tr.tbrule td {border-top: 1px solid black ; margin-top: 0ex ;
    margin-bottom: 0ex ; } /* for \toprule, \bottomrule */

td {padding: .5ex .5em .5ex .5em ;}

table td.tdl { text-align: left ; vertical-align: middle ; }
table td.tdc { text-align: center ; vertical-align: middle ; }
table td.tdat { text-align: center ; vertical-align: middle ; padding: 0px ; margin: 0px ; }
table td.tdbang { text-align: center ; vertical-align: middle ; }
table td.tdr { text-align: right ; vertical-align: middle ; }
table td.tdp { text-align: left ; vertical-align: bottom ; }
table td.tdm { text-align: left ; vertical-align: middle ; }
table td.tdb { text-align: left ; vertical-align: top ; }
table td.tdP { text-align: center ; vertical-align: bottom ; }
table td.tdM { text-align: center ; vertical-align: middle ; }
table td.tdB { text-align: center ; vertical-align: top ; }

table td.tvertbarl { border-left: 1px solid black }
table td.tvertbarldouble { border-left: 4px double black }
table td.tvertbarr { border-right: 1px solid black }
table td.tvertbarrdouble { border-right: 4px double black }

table td.tvertbarldash { border-left: 1px dashed black }
table td.tvertbarldoubledash { border-left: 2px dashed black }
table td.tvertbarrdash { border-right: 1px dashed black }
table td.tvertbarrdoubledash { border-right: 2px dashed black }


/* for cmidrules: */
table td.tdrule {
    border-top: 1px solid #A0A0A0 ;
}

table td.tdrulel {
    border-top-left-radius:.5em ;
    border-top: 1px solid #A0A0A0 ;
}

table td.tdruler {
    border-top-right-radius:.5em ;
    border-top: 1px solid #A0A0A0 ;
}
```

```
3325
3326 table td.tdrulelr {
3327     border-top-left-radius:.5em ;
3328     border-top-right-radius:.5em ;
3329     border-top: 1px solid #A0A0A0 ;
3330 }
3331
3332
3333 /* Margins of paragraphs inside table cells: */
3334 td.tdp p , td.tdprule p , td.tdP p , td.tdPrule p { padding-top: 1ex ;
3335     padding-bottom: 1ex ; margin: 0ex ; }
3336 td.tdm p , td.tmbrule p , td.tdM p , td.tdMrule p { padding-top: 1ex ;
3337     padding-bottom: 1ex ; margin: 0ex ; }
3338 td.tdb p , td.tdbrule p , td.tdB p , td.tdBrule p { padding-top: 1ex ;
3339     padding-bottom: 1ex ; margin: 0ex ; }
3340
3341 td.tdp , td.tdprule , td.tdP , td.tdPrule
3342     { padding: 0ex .5em 0ex .5em ; }
3343 td.tdm , td.tdmrule , td.tdM , td.tdMrule
3344     { padding: 0ex .5em 0ex .5em ; }
3345 td.tdb , td.tdbrule , td.tdB , td.tdBrule
3346     { padding: 0ex .5em 0ex .5em ; }
3347
3348
3349 /* table notes: */
3350 .tnotes {
3351     margin: 0ex 5% 1ex 5% ;
3352     padding: 0.5ex 1em 0.5ex 1em;
3353     font-size:.80em;
3354     text-align: left ;
3355 }
3356
3357 .minipage .tnotes {
3358     margin: 0pt ;
3359     padding: 0pt ;
3360 }
3361
3362 .tnotes dl dt p {margin-bottom:0px;}
3363
3364 .tnoteitemheader {margin-right: 1em;}
3365
3366
3367 /* for colortbl and cell color */
3368 div.cellcolor {
3369     width: 100% ;
3370     padding: .5ex .5em .5ex .5em ;
3371     margin: -.5ex -.5em -.5ex -.5em ;
3372 }
3373
3374
3375 /* for lyluatex */
3376 span.lyluatex {
3377     display: inline-block ;
3378 }
3379
```

```
div.lyluatex p span.lateximagesource img {
    display: block ;
    margin-top: 3ex ;
    margin-bottom: 3ex ;
}


/* for bigdelim */
.ldelim, .rdelim { font-size: 200% }


/* center, flushleft, flushright environments */
div.center{text-align:center;}
div.center table {margin-left:auto;margin-right:auto;}
div.flushleft{text-align:left;}
div.flushleft table {margin-left:0em ; margin-right:auto;}
div.flushright{text-align:right;}
div.flushright table {margin-left:auto ; margin-right: 0em ;}


/* Fancybox */
div.Btrivlist table tr td {
    padding: .2ex 0em ;
}


/* program listing callouts: */
span.callout {
     font-family: "DejaVu Sans", "Bitstream Vera Sans",
        Geneva, Verdana, sans-serif ;
    border-radius: .5em;
    background-color:black;
    color:white;
    padding:0px .25em 0px .25em;
    margin: 0 ;
    font-weight: bold;
    font-size:.72em ;
}

div.programlisting pre.verbatim span.callout{
    font-size: .85em ;
}

span.verbatim {
    font-family: "DejaVu Mono", "Bitstream Vera Mono", "Lucida Console",
        "Nimbus Mono L", "Liberation Mono", "FreeMono", "Andale Mono",
        "Courier New", monospace;
}



div.titlehead
{
    text-align: left ;
    font-style: normal ;
```

```
3435     font-weight: normal ;
3436     font-style: normal ;
3437     font-size: .8em ;
3438     margin: 1ex 0em 1ex 0em ;
3439 }
3440
3441 div.subject
3442 {
3443     text-align: center ;
3444     font-style: normal ;
3445     font-weight: bold ;
3446     font-style: normal ;
3447     font-size: .8em ;
3448     margin: 1ex 0em 1ex 0em ;
3449 }
3450
3451 div.published
3452 {
3453     text-align: center ;
3454     font-variant: normal ;
3455     font-style: italic ;
3456     font-size: 1em ;
3457     margin: 1ex 0em 1ex 0em ;
3458 }
3459
3460 div.subtitle
3461 {
3462     text-align: center ;
3463     font-variant: normal ;
3464     font-style: italic ;
3465     font-size: 1.25em ;
3466     margin: 1ex 0em 1ex 0em ;
3467 }
3468
3469 div.subtitle p { margin: 1ex ; }
3470
3471 div.author
3472 {
3473     font-variant: normal ;
3474     font-style: normal ;
3475     font-size: 1em ;
3476     margin: 1ex 0em 1ex 0em ;
3477 }
3478
3479 div.oneauthor {
3480     display: inline-block ;
3481     margin: 0ex 1em 0ex 1em ;
3482 }
3483
3484 /*
3485 div.author table {
3486     margin: 1ex auto 0ex auto ;
3487     background: none ;
3488 }
3489
```

```
div.author table tbody tr td { padding: .25ex ; }
*/

span.affiliation {font-size: .85em ; font-variant: small-caps; }

div.titledate {
    text-align: center ;
    font-size: .85em ;
    font-style: italic;
    margin: 1ex 0em 1ex 0em ;
}


nav.topnavigation{
    text-align: left ;
    padding: 0.5ex 1em 0.5ex 1em ;
/*     margin: 2ex 0em 3ex 0em ; */
    margin: 0 ;
    border-bottom: 1px solid silver ;
    border-top: 1px solid silver ;
    clear:both ;
}

nav.botnavigation{
    text-align: left ;
    padding: 0.5ex 1em 0.5ex 1em ;
/*     margin: 3ex 0em 2ex 0em ; */
    margin: 0 ;
    border-top: 1px solid silver ;
    border-bottom: 1px solid silver ;
    clear:both ;
}


header {
    line-height: 1.2 ;
    font-size: 1em ;
    border-bottom: 1px solid silver ;
    margin: 0px ;
    padding: 2ex 1em 2ex 1em ;
    text-align:left ;
}


footer {
    font-size: .85em ;
    line-height: 1.2 ;
    margin-top: 1ex ;
    border-top: 1px solid silver ;
    padding: 2ex 1em 2ex 1em ;
    clear:both ;
    text-align:left ;
}

```

```
/* for \LinkHome, \LinkPrevious, and \LinkNext: */
a.linkhome { font-weight:bold ; font-size: 1em ;}


div.lateximagesource { padding: 0px ; margin: 0px ; display: none; }

img.lateximage{
    padding: 0pt ;
    margin: 0pt ;
    box-shadow: none ;
    border: none ;
    background: none ;
    max-width: 100% ;
    border-radius: 0ex ;
    border: none ;
}


div.sidetoccontainer {
    font-family: "DejaVu Serif", "Bitstream Vera Serif",
        "Lucida Bright", Georgia, serif;
    float: left ;
    width: 19%; /* room for border-right next to 80% main */
    margin: 0pt 0em 3ex 0pt ;
    border-right: 1px solid silver;
    border-bottom: 1px solid silver;
    background: #FAF7F4 ;
    font-size:.9em ;
    border-radius: 0px 0px 20px 0px ;
}

div.sidetoccontents {
    overflow-y: auto ;
    width: 100% ;
    text-align: left ;
}


nav.sidetoc p {line-height:1.2 ; margin: 1ex .5em 1ex .5em ;
    text-indent: 0 ; }

nav.sidetoc p a {color:black ; font-size: .7em ;}

div.sidetoctitle {font-size: 1.2em; font-weight:bold; text-align:center;
    border-bottom: 1px solid silver ;    }

nav.sidetoc a:hover {text-decoration: underline ; }



section.textbody { margin: 0ex 1em 0ex 1em ;}


div.multicolsheading { -webkit-column-span: all;
    -moz-column-span: all; column-span: all; }
```

```
div.multicols {
    -webkit-columns: 3 auto ;
    -moz-columns: 3 auto ;
    columns: 3 auto ;
}
div.multicols p {margin-top: 0ex}


/* Used for xfrac and nicefrac: */
span.numerator {
    font-size: 60% ;
    vertical-align: .4em ;
}

span.denominator {
    font-size: 60%
}


/* Used for algorithm2e: */
div.alg2evline{
    margin-left: 1em ;
    padding-left: 1em ;
    border-left: 1px solid black ;
    border-radius: 0px 0px 0px 1ex ;
}

div.alg2evsline{
    margin-left: 1em ;
    padding-left: 1em ;
    border-left: 1px solid black ;
}

div.alg2enoline{
    margin-left: 1em ;
    padding-left: 1em ;
}

span.alg2elinenumber{
    margin-right: .5em ;
    font-size: 50% ;
    color: red ;
}


/* Used for algorithmicx: */
span.floatright { float: right ; }


/* keyfloat and tocdata: */
.floatnotes {
    margin: 0ex 5% 0ex 5% ;
    padding: 0ex 1em 0ex 1em ;
    font-size:.80em ;
    text-align: left ;
```

```
}

.authorartist{
    display:block ;
    font-size:.70em ;
    font-style: italic;
}

nav .authorartist{ display:inline; }


/* Native LaTeX theorems: */

.theoremcontents {
    font-style: italic; margin-top: 3ex ; margin-bottom: 3ex ;
}

.theoremlabel {
    font-style: normal; font-weight: bold ; margin-right: .5em ;
}


/* theorem, amsthm, and ntheorem packages */

span.theoremheader,
span.theoremheaderplain,
span.theoremheaderdefinition,
span.theoremheaderbreak,
span.theoremheadermarginbreak,
span.theoremheaderchangebreak,
span.theoremheaderchange,
span.theoremheadermargin
{
    font-style:normal ; font-weight: bold ; margin-right: 1em ;
}

span.amsthmnameplain,
span.amsthmnamedefinition,
span.amsthmnumberplain,
span.amsthmnumberdefinition
{
    font-style:normal ; font-weight: bold ;
}


span.amsthmnameremark,
span.amsthmnumberremark
{font-style:italic ; font-weight: normal ; }


span.amsthmnoteplain,
span.amsthmnotedefinition
{font-style:normal ;}
```

```
3710
3711
3712 span.theoremheaderremark,
3713 span.theoremheaderproof,
3714 span.amsthmproofname
3715 {font-style:italic ; font-weight: normal ; margin-right: 1em ; }
3716
3717 span.theoremheadersc
3718 {
3719     font-style:normal ;
3720     font-variant: small-caps ;
3721     font-weight: normal ;
3722     margin-right: 1em ;
3723 }
3724
3725 .theoremendmark {float:right}
3726
3727 div.amsthmbodyplain, div.theorembodyplain, div.theorembodynonumberplain,
3728 div.theorembodybreak, div.theorembodynonumberbreak,
3729 div.theorembodymarginbreak,
3730 div.theorembodychangebreak,
3731 div.theorembodychange,
3732 div.theorembodymargin
3733 {
3734     font-style:italic;
3735     margin-top: 3ex ; margin-bottom: 3ex ;
3736 }
3737
3738 div.theorembodydefinition, div.theorembodyremark, div.theorembodyproof,
3739 div.theorembodyplainupright, nonumberplainuprightsc,
3740 div.amsthmbodydefinition, div.amsthmbodyremark,
3741 div.amsthmproof
3742 {
3743     font-style: normal ;
3744     margin-top: 3ex ; margin-bottom: 3ex ;
3745 }
3746
3747 span.amsthmnoteremark {}
3748
3749
3750 /* thmbox */
3751
3752 .thmbox {
3753     font-style: italic; margin-top: 3ex ; margin-bottom: 3ex ;
3754     border: 1px solid gray ;
3755     padding: 1ex ;
3756 }
3757
3758 .thmboxtitle {
3759     font-style: normal; font-weight: bold ; margin-right: .5em ;
3760     border-bottom: 1px solid gray ;
3761 }
3762
3763 span.thmboxproofname, span.thmboxexamplename {
3764     font-weight: bold ;
```

```
}

div.thmboxproof, div.thmboxexample {
    font-size: 0.85em ;
    margin: 2ex ;
}

div.thmboxleftbar {
    border-left: 2px solid black ;
    padding-left: 1em ;
}



/* For the backnaur package: */
div.backnaur {
    display: block ;
    margin: 2ex 2em 2ex 2em ;
}

div.backnaur p {
    margin: .25ex 0ex .25ex 0ex ;
}

div.backnaurprod {
    display: inline-block ;
    min-width: 8em ;
    text-align:right ;
}

div.backnaurdesc {
    display: inline-block ;
}


/* For the notes package: */
div.notesimportantnote, div.noteswarningnote, div.notesinformationnote {
    clear: both ;
    margin: 2ex 2em 2ex 2em ;
    border: 1px solid silver ;
}

div.notesicon {
    float:left ;
    display: inline-block ;
    background: gold ;
    padding: 0ex 1em 0ex 1em ;
    margin-right: 1em ;
    font-weight: bold ;
}

div.notescontents { font-style: italic }


/* nolbreaks package: */
```

```
span.nolbreaks { white-space: nowrap ; }


/*
For CSS LaTeX and related logos:
Based on spacing demonstrated by the metafont package.

The subscripts are shrunk instead of lowered below the baseline,
to avoid browser rendering errors with the line height in lists, etc.
*/

.latexlogofont {
    font-family: "Linux Libertine O", "Nimbus Roman No 9 L",
        "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
    font-variant: normal ;
}

.latexlogo {
    font-family: "Linux Libertine O", "Nimbus Roman No 9 L",
        "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
}

.latexlogosup {
  text-transform: uppercase;
  letter-spacing: .03em ;
  font-size: 0.7em;
  vertical-align: 0.25em;
  margin-left: -0.4em;
  margin-right: -0.15em;
}

.latexlogosub {
  text-transform: uppercase;
/*  vertical-align: -0.27ex; */
  margin-left: -0.08em;
  margin-right: -0.07em;
/*  font-size: 1em; */
    font-size: .7em ;
}

.latexlogotwoe {
  text-transform: none ;
  font-variant-numeric: oldstyle-nums ;
}

.latexlogotwoesub {
  font-style:italic ;
/*  vertical-align: -0.27ex; */
  margin-left: -0.11em;
  margin-right: -0.1em;
/*  font-size: 1em; */
    font-size: .7em ;
}

.xelatexlogo {
```

```
    font-family: "Linux Libertine O", "Nimbus Roman No 9 L",
        "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
    letter-spacing: .03em ;
}

.xelatexlogosub {
/*  vertical-align: -0.27ex; */
  margin-left: -0.0667em;
  margin-right: -.05em;
/*  font-size: 1em; */
    font-size: .7em ;
  letter-spacing: .03em ;
}

.amslogo {
    font-family: "TeXGyreChorus","URW Chancery L",
        "Apple Chancery","ITC Zapf Chancery","Monotype Corsiva",
        "Linux Libertine O", "Nimbus Roman No 9 L",  "FreeSerif",
        "Hoefler Text", Times, "Times New Roman", serif ;
    font-style: italic ;
}

.lyxlogo {
    font-family: "URW Classico", Optima, "Linux Biolinum O",
        "DejaVu Sans", "Bitstream Vera Sans", Geneva,
        Verdana, sans-serif ;
}


/* Only display top and bottom navigation if a small screen: */
/* Hide the sidetoc if a small screen: */
nav.topnavigation { display:none; }
nav.botnavigation { display:none; }

/* Only display the sidetoc's webpage title if a small screen */
span.sidetocthetitle { display: none }

@media screen and (max-width: 100em) {
    div.multicols {
        -webkit-columns: 2 auto ;
        -moz-columns: 2 auto ;
        columns: 2 auto ;
    }
}

@media screen and (max-width: 50em) {
    div.sidetoccontainer {
        float: none ;
        width: 100% ;
        padding: 0 ;
        border-radius: 0 ;
        border-bottom: 1px solid black ;
        border-top: 1px solid black ;
        box-shadow: none ;
    }
```

```
    span.sidetocthetitle { display: inline }
    nav.topnavigation { display:block }
    nav.botnavigation { display:block }
    main.bodycontainer { width: 100% }
    .marginpar {
        max-width: 100%;
        float: none;
        display:block ;
        margin: 1ex 1em 1ex 1em ;
    }
    div.multicols {
        -webkit-columns: 1 auto ;
        -moz-columns: 1 auto ;
        columns: 1 auto ;
    }
}

@media print {
    body {
        font-family: "Linux Libertine O",
        "DejaVu Serif", "Bitstream Vera Serif",
        "Liberation Serif", "Nimbus Roman No 9 L",
        "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
    }
    div.sidetoccontainer { display:none; }
    nav.topnavigation { display: none; }
    nav.botnavigation { display: none; }
    main.bodycontainer { width: 100% }
}

@media handheld {
    div.sidetoccontainer { display:none; }
    nav.topnavigation { display:block }
    nav.botnavigation { display:block }
    main.bodycontainer { width: 100% }
}

@media projection {
    div.sidetoccontainer { display:none; }
    nav.topnavigation { display:block }
    nav.botnavigation { display:block }
    main.bodycontainer { width: 100% }
}
\end{filecontents*}
% \end{Verbatim}% for syntax highlighting
\end{LWRwriteconf}
```

40.5 lwarp_sagebrush.css

File lwarp_sagebrush.css An optional CSS which may be used for a semi-modern appearance.

If used, this must be present both when compiling the project and also when distributing the HTML files.

Config file:

```
\begin{LWRwriteconf}
\begin{filecontents*}[overwrite]{lwarp_sagebrush.css}
@import url("lwarp.css") ;


A:link {color:#105030 ; text-decoration: none ; }
A:visited {color:#705030 ; text-shadow:1px 1px 2px #a0a0a0;}
A:hover {color:#006000 ; text-decoration: underline ; text-shadow:0px 0px 2px #a0a0a0;}
A:active {color:#00C000 ; text-shadow:1px 1px 2px #a0a0a0;}


div.book, h1, h2, h3, h4, h5, h6, span.paragraph, span.subparagraph
{
    font-family: "URW Classico", Optima, "Linux Biolinum O",
        "Linux Libertine O", "Liberation Serif",
        "Nimbus Roman No 9 L",  "FreeSerif",
        "Hoefler Text", Times, "Times New Roman", serif;
    font-variant: small-caps ;
    font-weight: normal ;
    color: #304070 ;
    text-shadow: 2px 2px 3px #808080;
}

h1 {    /* title of the entire website, used on each page */
    font-variant: small-caps ;
    color: #304070 ;
    text-shadow: 2px 2px 3px #808080;
    background-color: #F7F7F0 ;
    background-image: linear-gradient(to bottom, #F7F7F0, #C0C0C4);
}

h1 {
  border-bottom: 1px solid #304070;
/*  border-top: 2px solid #304070; */
}

h2 {
  border-bottom: 1px solid #304070;
/*  border-top: 2px solid #304070; */
    background-color: #F7F7F0 ;
    background-image: linear-gradient(to bottom, #F7F7F0, #DAD0C0);
}


div.abstract {
    background: #f5f5eb ;
    background-image: linear-gradient(to bottom, #f5f5eb, #C8C8B8);

  border: 1px solid silver;
    border-radius: 1em ;
}

div.abstract dl {line-height:1.5;}
div.abstract dt {color:#304070;}
```

```
4032
4033 div.abstracttitle{
4034     font-family: "URW Classico", Optima, "Linux Biolinum O",
4035         "Linux Libertine O", "Liberation Serif", "Nimbus Roman No 9 L",
4036         "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
4037     font-weight:bold;
4038     font-variant: small-caps ;
4039     font-size:1.5em;
4040     border-bottom: 1px solid silver ;
4041     color: #304070 ;
4042     text-align: center ;
4043     text-shadow: 1px 1px 2px #808080;
4044 }
4045
4046 span.abstractrunintitle{
4047     font-family: "URW Classico", Optima, "Linux Biolinum O",
4048         "Linux Libertine O", "Liberation Serif", "Nimbus Roman No 9 L",
4049         "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
4050     font-weight:bold;
4051 }
4052
4053
4054 div.epigraph, div.dictum {
4055     background: #f5f5eb ;
4056     background-image: linear-gradient(to bottom, #f5f5eb, #C8C8B8);
4057
4058     border: 1px solid silver ;
4059     border-radius: 1ex ;
4060     box-shadow: 3px 3px 3px #808080 ;
4061 }
4062
4063
4064 .example {
4065     background-color: #f5f5eb ;
4066     background-image: linear-gradient(to bottom, #f5f5eb, #C8C8B8);
4067
4068 }
4069
4070 div.exampletitle{
4071     font-family: "URW Classico", Optima, "Linux Biolinum O",
4072         "Linux Libertine O", "Liberation Serif", "Nimbus Roman No 9 L",
4073         "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
4074     font-weight:bold;
4075     font-variant: small-caps ;
4076     border-bottom: 1px solid silver ;
4077     color: #304070 ;
4078     text-align: center ;
4079     text-shadow: 1px 1px 2px #808080;
4080 }
4081
4082
4083 .sidebar {
4084     background-color: #f5f5eb ;
4085     background-image: linear-gradient(to bottom, #f5f5eb, #C8C8B8);
4086
```

```
}

div.sidebartitle{
    font-family: "URW Classico", Optima, "Linux Biolinum O",
        "Linux Libertine O", "Liberation Serif", "Nimbus Roman No 9 L",
        "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
    font-weight:bold;
    font-variant: small-caps ;
    border-bottom: 1px solid silver ;
    color: #304070 ;
    text-align: center ;
    text-shadow: 1px 1px 2px #808080;
}


.fancyvrblabel {
    font-family: "URW Classico", Optima, "Linux Biolinum O",
        "Linux Libertine O", "Liberation Serif", "Nimbus Roman No 9 L",
        "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
    font-weight:bold;
    font-variant: small-caps ;
    font-size: 1.5em ;
    color: #304070 ;
    text-align: center ;
    text-shadow: 1px 1px 2px #808080;
}

div.minipage {
    background-color: #eeeee7 ;
    border: 1px solid silver ;
    border-radius: 1ex ;
}

table div.minipage { background: none ; border: none ; }

div.framebox div.minipage {border:none ; background:none}

section.textbody > div.minipage {
    box-shadow: 3px 3px 3px #808080 ;
}

div.fboxBlock div.minipage { box-shadow: none ; }

.framed .minipage , .framedleftbar .minipage {
    border: none ;
    background: none ;
    padding: 0ex ;
    margin: 0ex ;
}

figure.figure .minipage, div.figurecaption .minipage { border: none; }

div.marginblock div.minipage ,
div.marginparblock div.minipage
    { border: none; }
```

```
4142
4143 figure , div.marginblock {
4144     background-color: #eeeee7 ;
4145     border: 1px solid silver ;
4146     border-radius: 1ex ;
4147     box-shadow: 3px 3px 3px #808080 ;
4148 }
4149
4150 figure figure {
4151     border: 1px solid silver ;
4152     margin: 0em ;
4153     box-shadow: none ;
4154 }
4155
4156 /*
4157 div.figurecaption {
4158     border-top: 1px solid silver ;
4159     border-bottom: 1px solid silver ;
4160     background-color: #e8e8e8 ;
4161 }
4162 */
4163
4164
4165 div.table {
4166     box-shadow: 3px 3px 3px #808080 ;
4167 }
4168
4169 /*
4170 .tnotes {
4171     background: #e8e8e8;
4172     border: 1px solid silver;
4173 }
4174 */
4175
4176
4177 nav.topnavigation{
4178     background-color: #b0b8b0 ;
4179     background-image: linear-gradient(to bottom,#e0e0e0,#b0b8b0) ;
4180 }
4181
4182 nav.botnavigation{
4183     background-color: #b0b8b0 ;
4184     background-image: linear-gradient(to top,#e0e0e0,#b0b8b0) ;
4185 }
4186
4187
4188
4189 header{
4190     background-color: #F7F7F0 ;
4191     background-image: linear-gradient(to top, #F7F7F0, #b0b8b0);
4192 }
4193
4194 footer{
4195     background-color: #F7F7F0 ;
4196     background-image: linear-gradient(to bottom, #F7F7F0, #b0b8b0);
```

```
}


div.sidetoccontainer {
    background-color: #F7F7F0 ;
    background-image: linear-gradient(to bottom, #F7F7F0, #C0C0C0);
    box-shadow: 3px 3px 3px #808080 ;
    }

div.sidetoctitle {color: #304070 ; }

nav.sidetoc a:hover {
    color:#006000 ;
    text-decoration: none ;
    text-shadow:0px 0px 2px #a0a0a0;
}


@media screen and (max-width: 45em) {
    div.sidetoccontainer { border-radius: 0 ; }
}


\end{filecontents*}
% \end{Verbatim}% for syntax highlighting
\end{LWRwriteconf}
```

40.6 lwarp_formal.css

File lwarp_formal.css An optional css which may be used for a more formal appearance.

If used, this must be present both when compiling the project and also when distributing the HTML files.

Config file:

```
\begin{LWRwriteconf}
\begin{filecontents*}[overwrite]{lwarp_formal.css}
@import url("lwarp.css") ;


A:link {color:#802020 ; text-decoration:none; }
A:visited {color:#802020 ; text-shadow:none ;}
A:hover {color:#400000 ; text-shadow:none ;}
A:active {color:#C00000 ; text-shadow:none ;}


body {
    font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
        "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
        "Liberation Serif", "Nimbus Roman No 9 L",  "FreeSerif", Times,
        "Times New Roman", serif;
    background: #fffcf5;
}
```

```
4243
4244 span.textrm {
4245     font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
4246         "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
4247         "Liberation Serif", "Nimbus Roman No 9 L",  "FreeSerif", Times,
4248         "Times New Roman", serif;
4249 }
4250
4251 span.textsf {
4252      font-family: "DejaVu Sans", "Bitstream Vera Sans",
4253         Geneva, Verdana, sans-serif ;
4254 }
4255
4256
4257
4258 div.book, h1, h2, h3, h4, h5, h6, span.paragraph, span.subparagraph
4259 {
4260     font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
4261         "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
4262         "Liberation Serif", "Nimbus Roman No 9 L",  "FreeSerif", Times,
4263         "Times New Roman", serif;
4264     color: #800000 ;
4265     text-shadow: none ;
4266 }
4267
4268 h1, h2 {
4269     background-color: #fffcf5 ;
4270     background-image: none ;
4271     border-bottom: 1px solid #808080;
4272 /*    border-top: 2px solid #808080; */
4273 }
4274
4275 div.abstracttitle {
4276     font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
4277         "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
4278         "Liberation Serif", "Nimbus Roman No 9 L",  "FreeSerif", Times,
4279         "Times New Roman", serif;
4280     color: black ;
4281     text-shadow: none ;
4282 }
4283
4284 span.abstractrunintitle {
4285     font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
4286         "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
4287         "Liberation Serif", "Nimbus Roman No 9 L",  "FreeSerif", Times,
4288         "Times New Roman", serif;
4289     color: black ;
4290     text-shadow: none ;
4291 }
4292
4293 div.abstract { font-size: 100% }
4294
4295 .sidebar {
4296     background: #fffcf5;
4297     background-image: none ;
```

```
  margin: 2em 5% 2em 5%;
  padding: 0.5em 1em;
  border: none ;
  border-top : 1px solid silver;
  border-bottom : 1px solid silver;
  font-size: 90% ;
}

div.sidebartitle{
    font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
        "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
        "Liberation Serif", "Nimbus Roman No 9 L",  "FreeSerif", Times,
        "Times New Roman", serif;
    color: #800000 ;
    text-shadow: none ;
    border: none ;
}

.example {
    background: #fffcf5;
    background-image: none ;
  margin: 2em 5% 2em 5%;
  padding: 0.5em 1em;
  border: none ;
  border-top : 1px solid silver;
  border-bottom : 1px solid silver;
}

div.exampletitle{
    font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
        "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
        "Liberation Serif", "Nimbus Roman No 9 L",  "FreeSerif", Times,
        "Times New Roman", serif;
    color: #800000 ;
    text-shadow: none ;
    border: none ;
}

div.fancyvrblabel{
    font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
        "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
        "Liberation Serif", "Nimbus Roman No 9 L",  "FreeSerif", Times,
        "Times New Roman", serif;
    color: #800000 ;
    text-shadow: none ;
    border: none ;
}



figure {
    margin: 5ex 5% 5ex 5% ;
    padding: 1ex 1em 1ex 1em ;
    background-color: #fffcf5 ;
    overflow-x: auto ;
```

```
4353     border: none ;
4354 /*     border-top: 1px solid silver; */
4355 /*     border-bottom: 1px solid silver; */
4356 }
4357
4358
4359 div.figurecaption , .lstlisting {
4360     border: none ;
4361 /*     border-top: 1px solid silver ; */
4362 /*     border-bottom: 1px solid silver ; */
4363     background-color: #fffcf5 ;
4364 }
4365
4366 .tnotes {
4367     background: #fffcf5 ;
4368     border-top: 1px solid silver ;
4369     border-bottom: 1px solid silver ;
4370 }
4371
4372 .theorem {
4373         background: none ;
4374 }
4375
4376 .minipage {
4377     background-color: #fffcf5 ;
4378     border: none ;
4379 }
4380
4381 div.floatrow figure { border: none ; }
4382
4383 figure figure { border: none ; }
4384
4385
4386 nav.toc, nav.lof, nav.lot, nav.lol {
4387     font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
4388         "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
4389         "Liberation Serif", "Nimbus Roman No 9 L",  "FreeSerif", Times,
4390         "Times New Roman", serif;
4391 }
4392
4393 div.sidetoccontainer {
4394     font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
4395         "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
4396         "Liberation Serif", "Nimbus Roman No 9 L",  "FreeSerif", Times,
4397         "Times New Roman", serif;
4398     background-image: linear-gradient(to bottom, #fffcf5, #C0C0C0);
4399 }
4400
4401 div.sidetoctitle{
4402     color: #800000 ;
4403 }
4404
4405 header{
4406     background-color: #e0e0e0 ;
4407     background-image: linear-gradient(to top, #fffcf5, #b0b0b0);
```

```
    text-align:center ;
}

footer{
    background-color: #e0e0e0 ;
    background-image: linear-gradient(to bottom, #fffcf5, #b0b0b0);
    padding: 2ex 1em 2ex 1em ;
    text-align:left ;
}

nav.botnavigation {
    background: #dedcd5 ;
    border-top: 1px solid black ;
}
\end{filecontents*}
% \end{Verbatim}% for syntax highlighting
\end{LWRwriteconf}
```

40.7 sample_project.css

File sample_project.css The project-specific css file. Use with \CSSFilename.

If used, this must be present both when compiling the project and also when distributing the HTML files.

Config file:

```
\begin{LWRwriteconf}
\begin{filecontents*}[overwrite]{sample_project.css}
/* ( --- Start of project.css --- ) */
/* ( --- A sample project-specific CSS file for lwarp --- ) */

/* Uncomment one of the following: */
@import url("lwarp.css") ;
/* @import url("lwarp_formal.css") ; */
/* @import url("lwarp_sagebrush.css") ; */

/* Project-specific CSS setting follow here. */
/* . . . */

/* ( --- End of project.css --- ) */
\end{filecontents*}
% \end{Verbatim}% for syntax highlighting
\end{LWRwriteconf}
```

40.8 lwarp.ist

File lwarp.ist Used to modify the index for lwarp.

This must be present when compiling the project, but does not need to be present when distributing the resulting HTML files.

The page compositor line is for memoir's \specialindex.

Config file:

```
\begin{LWRwriteconf}
```

```
\begin{filecontents*}[overwrite]{lwarp.ist}
preamble
"\\begin{theindex}
  \\providecommand*\\lettergroupDefault[1]{}
  \\providecommand*\\lettergroup[1]{%
      \\par\\textbf{#1}\\par
      \\nopagebreak
  }
"
headings_flag 1
heading_prefix "
  \\lettergroup{"
heading_suffix "}"
delim_0 ", \\hyperindexref{"
delim_1 ", \\hyperindexref{"
delim_2 ", \\hyperindexref{"
delim_n "}, \\hyperindexref{"
delim_r "} -- \\hyperindexref{"
delim_t "}"
page_compositor "."
\end{filecontents*}
% \end{Verbatim}% for syntax highlighting
\end{LWRwriteconf}
```

40.9 `lwarp.xdy`

File `lwarp.xdy` Used to modify the index for lwarp.

This must be present when compiling the project, but does not need to be present when distributing the resulting HTML files.

See:
https://tex.stackexchange.com/questions/80300/how-can-i-convince-hyperref-and-xindy-to-play-together-nicely

Config file:

```
\begin{LWRwriteconf}
\begin{filecontents*}[overwrite]{lwarp.xdy}
(require "tex/inputenc/latin.xdy")
(merge-rule "\\PS *" "Postscript")
(require "texindy.xdy")
(require "page-ranges.xdy")
(require "book-order.xdy")
(define-location-class "arabic-page-numbers"
    ("arabic-numbers") :min-range-length 1)
(require "makeindex.xdy")
(define-attributes (("hyperindexref")))
(markup-locref :open "\hyperindexref{" :close "}")
(markup-locref :open "\hyperindexref{" :close "}" :attr "hyperpage")
(markup-locref :open "\textbf{\hyperindexref{" :close "}}" :attr "textbf")
(markup-locref :open "\textit{\hyperindexref{" :close "}}" :attr "textit")
(define-location-class-order ("roman-page-numbers"
                  "arabic-page-numbers"
                  "alpha-page-numbers"
                  "Roman-page-numbers"
```

```
                    "Alpha-page-numbers"
                    "see"
                    "seealso"))
\end{filecontents*}
% \end{Verbatim}% for syntax highlighting
\end{LWRwriteconf}
```

40.10 lwarp_one_limage.cmd

File lwarp_one_limage.cmd

Used by lwarp to help make lateximages when using Windows.

This must be present when compiling the project, but does not need to be present when distributing the resulting html files.

The arguments are each of the three fields from <project>-images.txt, and also the base name of the source file.

MiKTeX does not allow file lwarp_one_limage.cmd to be created directly by *lwarpmk*, so lwarp_one_limage.txt is created instead, then copied to lwarp_one_limage.cmd by *lwarpmk*. This occurs each time *lwarpmk* used to create lateximages.

Config file:

```
\begin{LWRwriteconf}
\immediate\openout\LWR@quickfile=lwarp_one_limage.txt
\immediate\write\LWR@quickfile{%
    pdfseparate -f \LWRpercent 1 -l \LWRpercent 1 \LWRpercent 4_html.pdf %
   \LWR@ImagesDirectory\OSPathSymbol lateximagetemp-\LWRpercent\LWRpercent d.pdf%
}
\immediate\write\LWR@quickfile{%
   pdfcrop --hires  \LWR@ImagesDirectory\OSPathSymbol lateximagetemp-\LWRpercent 1.pdf %
    \LWR@ImagesDirectory\OSPathSymbol\LWRpercent 3.pdf%
}
\immediate\write\LWR@quickfile{%
   pdftocairo -svg -noshrink  \LWR@ImagesDirectory\OSPathSymbol\LWRpercent 3.pdf %
    \LWR@ImagesDirectory\OSPathSymbol\LWRpercent 3.svg%
}
\immediate\write\LWR@quickfile{%
    del \LWR@ImagesDirectory\OSPathSymbol\LWRpercent 3.pdf%
}
\immediate\write\LWR@quickfile{%
    del \LWR@ImagesDirectory\OSPathSymbol lateximagetemp-\LWRpercent 1.pdf%
}
\immediate\write\LWR@quickfile{exit}
\immediate\closeout\LWR@quickfile
\end{LWRwriteconf}
```

40.11 lwarp_mathjax.txt

(*Emulates or patches code by* Davide P. Cervone.)

File lwarp_mathjax.txt

The default MathJax script used by lwarp when using MathJax. A recent version of MathJax is used, as served by the recommended repository. Adjustments are made to allow LaTeX to control the equation tags and provide for starred macros.

\MathJaxFilename determines which script file is copied into the HTML pages, and defaults to lwarp_mathjax.txt. The script files must be present when compiling the project, but do not need to be present when distributing the resulting HTML files.

custom script

To generate a custom script, such as to use a local repository, copy lwarp_mathjax.txt to a new file, make changes while keeping lwarp's adjustments for equation numbering and starred macros, and use \MathJaxFilename to select the new filename.

Config file:

```
\begin{LWRwriteconf}
\begin{filecontents*}[overwrite]{lwarp_mathjax.txt}
<script>
// Lwarp MathJax emulation code
//
// Based on code by Davide P. Cervone.
// Equation numbering: https://github.com/mathjax/MathJax/issues/2427
// Starred and ifnextchar macros: https://github.com/mathjax/MathJax/issues/2428
// \left, \right delimiters: https://github.com/mathjax/MathJax/issues/2535
//
// Modified by Brian Dunn to adjust equation numbering and add subequations.
//
// LaTeX can use \seteqnumber{subequations?}{section}{number} before each equation.
// subequations? is 0 usually, 1 if inside subequations.
// section is a string printed as-is, or empty.
// number is auto-incremented by MathJax between equations.
//
MathJax = {
  subequations: "0",
  section: "",
  loader: {
    load: ['[tex]/tagformat', '[tex]/textmacros'],
  },
  startup: {
    ready() {
      //  These would be replaced by import commands if you wanted to make
      //  a proper extension.
      const Configuration = MathJax._.input.tex.Configuration.Configuration;
      const CommandMap = MathJax._.input.tex.SymbolMap.CommandMap;
      const Macro = MathJax._.input.tex.Symbol.Macro;
      const TexError = MathJax._.input.tex.TexError.default;
      const ParseUtil = MathJax._.input.tex.ParseUtil.default;
      const expandable = MathJax._.util.Options.expandable;

      //  Insert the replacement string into the TeX string, and check
      //  that there haven't been too many maxro substitutions (prevents
      //  infinite loops).
      const useArgument = (parser, text) => {
     parser.string = ParseUtil.addArgs(parser, text, parser.string.slice(parser.i));
        parser.i = 0;
        if (++parser.macroCount > parser.configuration.options.maxMacros) {
          throw new TexError('MaxMacroSub1',
          'MathJax maximum macro substitution count exceeded; ' +
          'is there a recursive macro call?');
        }
      }

```

```
4561      //  Create the command map for:
4562      //    \ifstar, \ifnextchar, \ifblank, \ifstrequal, \seteqnumber
4563      new CommandMap('Lwarp-macros', {
4564        ifstar: 'IfstarFunction',
4565        ifnextchar: 'IfnextcharFunction',
4566        ifblank: 'IfblankFunction',
4567        ifstrequal: 'IfstrequalFunction',
4568        seteqnumber: 'SeteqnumberFunction'
4569      }, {
4570        //  This function implements an ifstar macro.
4571        IfstarFunction(parser, name) {
4572          const resultstar = parser.GetArgument(name);
4573          const resultnostar = parser.GetArgument(name);
4574         const star = parser.GetStar();                // true if there is a *
4575          useArgument(parser, star ? resultstar : resultnostar);
4576        },
4577
4578        //  This function implements an ifnextchar macro.
4579        IfnextcharFunction(parser, name) {
4580          let whichchar = parser.GetArgument(name);
4581          if (whichchar.match(/^(?:0x[0-9A-F]+|[0-9]+)$/i)) {
4582            // $ syntax highlighting
4583            whichchar = String.fromCodePoint(parseInt(whichchar));
4584          }
4585          const resultnextchar = parser.GetArgument(name);
4586          const resultnotnextchar = parser.GetArgument(name);
4587          const gotchar = (parser.GetNext() === whichchar);
4588          useArgument(parser, gotchar ? resultnextchar : resultnotnextchar);
4589        },
4590
4591        // This function implements an ifblank macro.
4592        IfblankFunction(parser, name) {
4593          const blankarg = parser.GetArgument(name);
4594          const resultblank = parser.GetArgument(name);
4595          const resultnotblank = parser.GetArgument(name);
4596          const isblank = (blankarg.trim() == "");
4597          useArgument(parser, isblank ? resultblank : resultnotblank);
4598        },
4599
4600        // This function implements an ifstrequal macro.
4601        IfstrequalFunction(parser, name) {
4602          const strequalfirst = parser.GetArgument(name);
4603          const strequalsecond = parser.GetArgument(name);
4604          const resultequal = parser.GetArgument(name);
4605          const resultnotequal = parser.GetArgument(name);
4606          const isequal = (strequalfirst == strequalsecond);
4607          useArgument(parser, isequal ? resultequal : resultnotequal);
4608        },
4609
4610        //  This function modifies the equation numbers.
4611        SeteqnumberFunction(parser, name) {
4612            //  Get the macro parameters
4613           const star = parser.GetStar();               // true if there is a *
4614        const optBrackets = parser.GetBrackets(name);  // contents of optional brackets
4615        const newsubequations = parser.GetArgument(name);  // the subequations argument
```

```
4616        const neweqsection = parser.GetArgument(name);  // the eq section argument
4617        const neweqnumber = parser.GetArgument(name);   // the eq number argument
4618        MathJax.config.subequations=newsubequations ;   // a string with boolean meaning
4619        MathJax.config.section=neweqsection ;        // a string with numeric meaning
4620            parser.tags.counter = parser.tags.allCounter = neweqnumber ;
4621        }
4622
4623      });
4624
4625      //  Create the Lwarp-macros package
4626      Configuration.create('Lwarp-macros', {
4627        handler: {macro: ['Lwarp-macros']}
4628      });
4629
4630      MathJax.startup.defaultReady();
4631
4632      // For forward references:
4633      MathJax.startup.input[0].preFilters.add(({math}) => {
4634        if (math.inputData.recompile){
4635          MathJax.config.subequations = math.inputData.recompile.subequations;
4636            MathJax.config.section = math.inputData.recompile.section;
4637        }
4638      });
4639      MathJax.startup.input[0].postFilters.add(({math}) => {
4640        if (math.inputData.recompile){
4641          math.inputData.recompile.subequations = MathJax.config.subequations;
4642            math.inputData.recompile.section = MathJax.config.section;
4643        }
4644      });
4645
4646        // For \left, \right with unicode-math:
4647        const {DelimiterMap} = MathJax._.input.tex.SymbolMap;
4648        const {Symbol} = MathJax._.input.tex.Symbol;
4649        const {MapHandler} = MathJax._.input.tex.MapHandler;
4650        const delimiter = MapHandler.getMap('delimiter');
4651        delimiter.add('\\lBrack', new Symbol('\\lBrack', '\u27E6'));
4652        delimiter.add('\\rBrack', new Symbol('\\rBrack', '\u27E7'));
4653        delimiter.add('\\lAngle', new Symbol('\\lAngle', '\u27EA'));
4654        delimiter.add('\\rAngle', new Symbol('\\rAngle', '\u27EB'));
4655        delimiter.add('\\lbrbrak', new Symbol('\\lbrbrak', '\u2772'));
4656        delimiter.add('\\rbrbrak', new Symbol('\\rbrbrak', '\u2773'));
4657        delimiter.add('\\lbag', new Symbol('\\lbag', '\u27C5'));
4658        delimiter.add('\\rbag', new Symbol('\\rbag', '\u27C6'));
4659      delimiter.add('\\llparenthesis', new Symbol('\\llparenthesis', '\u2987'));
4660      delimiter.add('\\rrparenthesis', new Symbol('\\rrparenthesis', '\u2988'));
4661        delimiter.add('\\llangle', new Symbol('\\llangle', '\u2989'));
4662        delimiter.add('\\rrangle', new Symbol('\\rrangle', '\u298A'));
4663        delimiter.add('\\Lbrbrak', new Symbol('\\Lbrbrak', '\u27EC'));
4664        delimiter.add('\\Rbrbrak', new Symbol('\\Rbrbrak', '\u27ED'));
4665        delimiter.add('\\lBrace', new Symbol('\\lBrace', '\u2983'));
4666        delimiter.add('\\rBrace', new Symbol('\\rBrace', '\u2984'));
4667        delimiter.add('\\lParen', new Symbol('\\lParen', '\u2985'));
4668        delimiter.add('\\rParen', new Symbol('\\rParen', '\u2986'));
4669        delimiter.add('\\lbrackubar', new Symbol('\\lbrackubar', '\u298B'));
4670        delimiter.add('\\rbrackubar', new Symbol('\\rbrackubar', '\u298C'));
```

```
      delimiter.add('\\lbrackultick', new Symbol('\\lbrackultick', '\u298D'));
      delimiter.add('\\rbracklrtick', new Symbol('\\rbracklrtick', '\u298E'));
      delimiter.add('\\lbracklltick', new Symbol('\\lbracklltick', '\u298F'));
      delimiter.add('\\rbrackurtick', new Symbol('\\rbrackurtick', '\u2990'));
       delimiter.add('\\langledot', new Symbol('\\langledot', '\u2991'));
       delimiter.add('\\rangledot', new Symbol('\\rangledot', '\u2992'));
       delimiter.add('\\lparenless', new Symbol('\\lparenless', '\u2993'));
       delimiter.add('\\rparengtr', new Symbol('\\rparengtr', '\u2994'));
       delimiter.add('\\Lparengtr', new Symbol('\\Lparengtr', '\u2995'));
       delimiter.add('\\Rparenless', new Symbol('\\Rparenless', '\u2996'));
       delimiter.add('\\lblkbrbrak', new Symbol('\\lblkbrbrak', '\u2997'));
       delimiter.add('\\rblkbrbrak', new Symbol('\\rblkbrbrak', '\u2998'));
       delimiter.add('\\lvzigzag', new Symbol('\\lvzigzag', '\u29D8'));
       delimiter.add('\\rvzigzag', new Symbol('\\rvzigzag', '\u29D9'));
       delimiter.add('\\Lvzigzag', new Symbol('\\Lvzigzag', '\u29DA'));
       delimiter.add('\\Rvzigzag', new Symbol('\\Rvzigzag', '\u29DB'));
       delimiter.add('\\lcurvyangle', new Symbol('\\lcurvyangle', '\u29FC'));
       delimiter.add('\\rcurvyangle', new Symbol('\\rcurvyangle', '\u29FD'));
       delimiter.add('\\Vvert', new Symbol('\\Vvert', '\u2980'));
    }   // ready
  },    // startup

  tex: {
    packages: {'[+]': ['tagformat', 'Lwarp-macros', 'textmacros']},
    tags: "ams",
        tagformat: {
            number: function (n) {
                if(MathJax.config.subequations==0)
                    return(MathJax.config.section + n);
                else
                   return(MathJax.config.section + String.fromCharCode(96+n));
            },
        },
  }
}
</script>

<script
    id="MathJax-script"
    src="https://cdn.jsdelivr.net/npm/mathjax@3/es5/tex-chtml.js"
></script>
\end{filecontents*}
% \end{Verbatim}% for syntax highlighting
\end{LWRwriteconf}
```

40.12 `lwarpmk.lua` — `lwarpmk` option

Opt `lwarpmk` Creates a local copy of *lwarpmk*.

Prog `lwarpmk` Command-line utility to process lwarp files and images.

parallel processing `latexi`mages and SVG math images are generated using multiple processes in parallel. For Unix and Linux, every 32 images the `wait` command is issued to wait for the previous

batch of images to finish processing before starting a new batch. For Windows, every 32 images one task is dispatched with

```
START /B /WAIT /BELOWNORMAL
```

which causes the operating system to wait until this lesser-priority tasks finishes, hopefully also waiting for the normal priority tasks which were already in progress to also complete. Afterwards, the next batch of images is started.

The following is only generated if the `lwarpmk` option was given to lwarp.

```
\begin{LWRcreatelwarpmk}

\begin{filecontents*}[overwrite]{lwarpmk.lua}
#!/usr/bin/env texlua

-- Copyright 2016-2021 Brian Dunn


printversion = "v0.899"
requiredconfversion = "2" -- also at *lwarpmk.conf

function printhelp ()
print ("lwarpmk: Use lwarpmk -h or lwarpmk --help for help.") ;
end


function printusage ()
--
-- Print the usage of the lwarpmk command:
--
print ( [[

lwarpmk print [-p project]: Compile the print version if necessary.
lwarpmk print1 [-p project]: Forced single compile of the print version.
lwarpmk printindex [-p project]: Process print indexes.
lwarpmk printglossary [-p project]: Process the glossary for the print version.
lwarpmk html [-p project]: Compile the HTML version if necessary.
lwarpmk html1 [-p project]: Forced single compile of the HTML version.
lwarpmk htmlindex [-p project]: Process HTML indexes.
lwarpmk htmlglossary [-p project]: Process the glossary for the html version.
lwarpmk again [-p project]: Touch the source code to trigger recompiles.
lwarpmk limages [-p project]: Process the "lateximages" created by lwarp.sty.
lwarpmk pdftohtml [-p project]:
    For use with latexmk or a Makefile:
    Converts project_html.pdf to project_html.html and individual HTML files.
    Finishes the HTML conversion even if there was a compile error.
lwarpmk pdftosvg <list of file names>: Converts each PDF file to SVG.
lwarpmk epstopdf <list of file names>: Converts each EPS file to PDF.
lwarpmk clean [-p project]: Remove *.aux, *.toc, *.lof/t,
    *.idx, *.ind, *.bbl, *.log, *_html_inc.*, .gl*,
    *_html.pdf, *_html.html, *_html.sidetoc
lwarpmk cleanall [-p project]: Remove auxiliary files, project.pdf, *.html
lwarpmk cleanlimages: Removes all images from the "lateximages" directory.
lwarpmk -v: Print the version number.
lwarpmk -h: Print this help message.
```

```
lwarpmk --help: Print this help message.

]] )
-- printconf ()
end


function splitfilename ( pathandfilename )
--
-- Separates out the path and extension from a filename.
-- Returns path, filename with extension, and extension.
-- Ex: thispath, thisfilename, thisextension = splitfilename ("path/to/filename.ext")
--
-- https://www.fhug.org.uk/wiki/wiki/doku.php?id=plugins:code_snippets:
--      split_filename_in_to_path_filename_and_extension
--
    if lfs.attributes(pathandfilename,"mode") == "directory" then
      local strPath = pathandfilename:gsub("[\\/]$","") -- $ (syntax highlighting)
        return strPath.."\\","",""
    end
    pathandfilename = pathandfilename.."."
    return pathandfilename:match("^(.-)([^\\/]-)%.([^\\/%.]-)%.?$")
end


function splitfile (destfile,sourcefile)
--
-- Split one large sourcefile into a number of files,
-- starting with destfile.
-- The file is split at each occurance of <!--|Start file|newfilename|*
-- If lwarp is in use, sets usinglwarp.
--
usinglwarp = false ;
print ("lwarpmk: Splitting " .. sourcefile .. " into " .. destfile) ;
local sfile = io.open(sourcefile)
io.output(destfile)
for line in sfile:lines() do
i,j,copen,cstart,newfilename = string.find (line,"(.*)|(.*)|(.*)|") ;
if ( (i~= nil) and (copen == "<!--") and (cstart == "Start file")) then
    -- split the file
    io.output(newfilename) ;
else
if ( (i~= nil) and (copen == "<!--") and (cstart == "Using lwarp")) then
    -- verified the use of \usepackage{lwarp}
    usinglwarp = true ;
else
    -- not a splitpoint
    io.write (line .. "\n") ;
end end
end -- do
io.close(sfile)
if ( usinglwarp == false ) then
    print ("lwarpmk: ===")
    print ("lwarpmk: \\usepackage{lwarp} was not detected.")
    print ("lwarpmk: The HTML output will not be correct.")
```

```
4814     print ("lwarpmk: Ensured that \\usepackage{lwarp} is enabled,")
4815     print ("lwarpmk: then lwarpmk print and lwarpmk HTML again.")
4816     print ("lwarpmk: ===")
4817 end
4818 end -- function
4819
4820
4821 function cvalueerror ( line, linenum , cvalue )
4822 --
4823 -- Incorrect value, so print an error and exit.
4824 --
4825     print ("lwarpmk: ===")
4826     print ("lwarpmk: " .. linenum .. " : " .. line ) ;
4827     print (
4828         "lwarpmk: incorrect variable value \"" .. cvalue ..
4829         "\" in lwarpmk.conf.\n"
4830     ) ;
4831     print ("lwarpmk: ===")
4832 --    printconf () ;
4833     os.exit(1) ;
4834 end
4835
4836
4837 function printhowtorecompile ()
4838 -- Tells the user how to recompile to regenerate the configuration files.
4839   print ("lwarpmk: The configuration files lwarpmk.conf and "..sourcename..".lwarpmkconf" )
4840     print ("lwarpmk:   must be updated.  To do so, recompile" )
4841     print ("lwarpmk:   " , sourcename..".tex" )
4842     if ( printlatexcmd == "" ) then
4843         print ("lwarpmk:   using xe/lua/pdflatex," )
4844     else
4845         print ("lwarpmk:   using the command:")
4846         print ("lwarpmk:   " , printlatexcmd )
4847     end
4848     print ("lwarpmk:   then use lwarpmk again.")
4849 end -- printhowtorecompile
4850
4851
4852 function ignoreconf ()
4853 -- Global argument index
4854 argindex = 2
4855 end
4856
4857 function loadconf ()
4858 --
4859 -- Load settings from the project's "lwarpmk.conf" file:
4860 --
4861 -- Default configuration filename:
4862 local conffile = "lwarpmk.conf"
4863 local confroot = "lwarpmk"
4864 -- Global argument index
4865 argindex = 2
4866 -- Optional configuration filename:
4867 if ( arg[argindex] == "-p" ) then
4868     argindex = argindex + 1
```

```
    confroot = arg[argindex]
    conffile = confroot..".lwarpmkconf"
    argindex = argindex + 1
end
-- Additional defaults:
confversion = "0"
opsystem = "Unix"
imagesdirectory = "lateximages"
imagesname = "image-"
latexmk = "false"
printlatexcmd = ""
HTMLlatexcmd = ""
printindexcmd = ""
HTMLindexcmd = ""
latexmkindexcmd = ""
-- to be removed:
-- indexprog = "makeindex"
-- makeindexstyle = "lwarp.ist"
-- xindylanguage = "english"
-- xindycodepage = "utf8"
-- xindystyle = "lwarp.xdy"
-- pdftotextenc = "UTF-8"
glossarycmd = "makeglossaries"
-- Verify the file exists:
if (lfs.attributes(conffile,"mode")==nil) then
    -- file not exists
    print ("lwarpmk: ===")
    print ("lwarpmk: File \"" .. conffile .."\" does not exist.")
    print ("lwarpmk: Move to the project's source directory,")
    print ("lwarpmk: recompile using pdflatex, xelatex, or lualatex,")
    print ("lwarpmk: then try using lwarpmk again.")
    if ( arg[argindex] ~= nil ) then
        print (
            "lwarpmk: (\"" .. confroot ..
            "\" does not appear to be a project name.)"
        )
    end
    print ("lwarpmk: ===")
    printhelp () ;
    os.exit(1) -- exit the entire lwarpmk script
else -- file exists
-- Read the file:
print ("lwarpmk: Reading " .. conffile ..".")
local cfile = io.open(conffile)
-- Scan each line, parsing each line as: name = [[string]]
local linenum = 0
for line in cfile:lines() do -- scan lines
linenum = linenum + 1
i,j,cvarname,cvalue = string.find (line,"([%w-_]*)%s*=%s*%[%[([^%]]*)%]%]") ;
-- Error if incorrect enclosing characters:
if ( i == nil ) then
    print ("lwarpmk: ===")
    print ("lwarpmk: " ..  linenum .. " : " .. line ) ;
    print ("lwarpmk: Incorrect entry in " .. conffile ..".\n" ) ;
    print ("lwarpmk: ===")
```

```
--    printconf () ;
    os.exit(1) ;
end -- nil
if ( cvarname == "confversion" ) then
    confversion = cvalue
elseif ( cvarname == "opsystem" ) then
    -- Verify choice of opsystem:
    if ( (cvalue == "Unix") or (cvalue == "Windows") ) then
        opsystem = cvalue
    else
        cvalueerror ( line, linenum , cvalue )
    end
elseif ( cvarname == "sourcename" ) then sourcename = cvalue
elseif ( cvarname == "homehtmlfilename" ) then homehtmlfilename = cvalue
elseif ( cvarname == "htmlfilename" ) then htmlfilename = cvalue
elseif ( cvarname == "imagesdirectory" ) then imagesdirectory = cvalue
elseif ( cvarname == "imagesname" ) then imagesname = cvalue
elseif ( cvarname == "latexmk" ) then latexmk = cvalue
elseif ( cvarname == "printlatexcmd" ) then printlatexcmd = cvalue
elseif ( cvarname == "HTMLlatexcmd" ) then HTMLlatexcmd = cvalue
elseif ( cvarname == "printindexcmd" ) then printindexcmd = cvalue
elseif ( cvarname == "HTMLindexcmd" ) then HTMLindexcmd = cvalue
elseif ( cvarname == "latexmkindexcmd" ) then latexmkindexcmd = cvalue
elseif ( cvarname == "glossarycmd" ) then glossarycmd = cvalue
elseif ( cvarname == "pdftotextenc" ) then pdftotextenc = cvalue
else
    print ("lwarpmk: ===")
    print ("lwarpmk: " .. linenum .. " : " .. line ) ;
    print (
        "lwarpmk: Incorrect variable name \"" .. cvarname .. "\" in " ..
        conffile ..".\n"
    ) ;
    print ("lwarpmk: ===")
--    printconf () ;
os.exit(1) ;
end -- cvarname
end -- do scan lines
io.close(cfile)
end -- file exists
-- Error if sourcename is "lwarp".
-- This could happen if a local copy of lwarp has recently been recompiled.
if sourcename=="lwarp" then
    print ("lwarpmk: ===")
   print ("lwarpmk: lwarp.sty has recently been recompiled in this directory,")
   print ("lwarpmk: and \"lwarpmk.conf\" is no longer set for your own project.")
    print ("lwarpmk:   (Perhaps you are not in your project's directory?)")
    print ("lwarpmk: In your project directory, recompile your project")
    print ("lwarpmk: using pdf/lua/xelatex <projectname>.")
  print ("lwarpmk: After a recompile, \"lwarpmk.conf\" will be set for your project,")
    print ("lwarpmk: and you may again use lwarpmk.")
    print ("lwarpmk: ===")
    os.exit(1)
end -- sourcename of "lwarp"
-- Select some operating-system commands:
if opsystem=="Unix" then  -- For Unix / Linux / Mac OS:
```

```
4979     rmname = "rm"
4980     mvname = "mv"
4981     cpname = "cp"
4982     touchnamepre = "touch"
4983     touchnamepost = ""
4984     newtouchname = "touch"
4985     dirslash = "/"
4986     opquote= "\'"
4987     cmdgroupopenname = " ( "
4988     cmdgroupclosename = " ) "
4989     seqname = " && "
4990     bgname = " &"
4991 elseif opsystem=="Windows" then -- For Windows
4992     rmname = "DEL"
4993     mvname = "MOVE"
4994     cpname = "COPY"
4995     touchnamepre = "COPY /b"
4996     touchnamepost = "+,,"
4997     newtouchname = "echo empty >"
4998     dirslash = "\\"
4999     opquote= "\""
5000     cmdgroupopenname = ""
5001     cmdgroupclosename = ""
5002     seqname = " & "
5003     bgname = ""
5004 else
5005     print ("lwarpmk: ===")
5006     print ("lwarpmk: Select Unix or Windows for opsystem." )
5007     print ("lwarpmk: ===")
5008     os.exit(1)
5009 end --- for Windows
5010 -- Warning if the operating system does not appear to be correct,
5011 -- in case files were transferred to another system.
5012 if ( (package.config:sub(1,1)) ~= dirslash ) then
5013     print ("lwarpmk: ===")
5014    print ("lwarpmk: It appears that lwarpmk.conf is for a different operating system." )
5015     printhowtorecompile ()
5016     print ("lwarpmk: ===")
5017     os.exit(1)
5018 end
5019 -- Error if the configuration file's version is not current:
5020 if ( confversion ~= requiredconfversion ) then
5021     print ("lwarpmk: ===")
5022     printhowtorecompile ()
5023     print ("lwarpmk: ===")
5024     os.exit(1)
5025 end
5026 end -- loadconf
5027
5028
5029 function executecheckerror ( executecommands , errormessage )
5030 --
5031 -- Execute an operating system call,
5032 -- and maybe exit with an error message.
5033 --
```

```
local err
err = os.execute ( executecommands )
if ( err ~= 0 ) then
    print ("lwarpmk: ===")
    print ("lwarpmk: " .. errormessage )
    print ("lwarpmk: ===")
    os.exit(1)
end
end -- executecheckerror


function refreshdate ()
os.execute(touchnamepre .. " " .. sourcename .. ".tex " .. touchnamepost)
end



function reruntoget (filesource)
--
-- Scan the LaTeX log file for the phrase "Rerun to get",
-- indicating that the file should be compiled again.
-- Return true if found.
--
local fsource = io.open(filesource)
for line in fsource:lines() do
if ( string.find(line,"Rerun to get") ~= nil ) then
    io.close(fsource)
    return true
end -- if
end -- do
io.close(fsource)
return false
end



function onetime (latexcmd, fsuffix)
--
-- Compile one time, return true if should compile again.
-- fsuffix is "" for print, "_html" for HTML output.
--
print("lwarpmk: Compiling with: " .. latexcmd)
executecheckerror (
    latexcmd ,
    "Compile error."
)
return (reruntoget(sourcename .. fsuffix .. ".log") ) ;
end


function manytimes (latexcmd, fsuffix)
--
-- Compile up to five times.
-- fsuffix is "" for print, "_html" for HTML output
--
```

```
5089 if onetime(latexcmd, fsuffix) == true then
5090 if onetime(latexcmd, fsuffix) == true then
5091 if onetime(latexcmd, fsuffix) == true then
5092 if onetime(latexcmd, fsuffix) == true then
5093 if onetime(latexcmd, fsuffix) == true then
5094 end end end end end
5095 end
5096
5097
5098 function verifyfileexists (filename)
5099 --
5100 -- Exit if the given file does not exist.
5101 --
5102 if (lfs.attributes ( filename , "modification" ) == nil ) then
5103     print ("lwarpmk: ===")
5104     print ("lwarpmk: " .. filename .. " not found." ) ;
5105     print ("lwarpmk: ===")
5106     os.exit (1) ;
5107 end
5108 end
5109
5110
5111
5112 function pdftohtml ()
5113 --
5114 -- Convert <project>_html.pdf into HTML files:
5115 --
5116 -- Convert to text:
5117 print ("lwarpmk: Converting " .. sourcename
5118     .."_html.pdf to " .. sourcename .. "_html.html")
5119 os.execute("pdftotext  -enc " .. pdftotextenc .. "  -nopgbrk  -layout "
5120     .. sourcename .. "_html.pdf " .. sourcename .. "_html.html")
5121 -- Split the result into individual HTML files:
5122 splitfile (homehtmlfilename .. ".html" , sourcename .. "_html.html")
5123 end
5124
5125
5126 function removeaux ()
5127 --
5128 -- Remove auxiliary files:
5129 -- All .aux files are removed since there may be many bbl*.aux files.
5130 -- Also removes sourcename_html.pdf, sourcename_html.html,
5131 -- and sourcename_html.sidetoc, plus comment_*.cut.
5132 --
5133 os.execute ( rmname .. " *.aux " ..
5134     sourcename ..".toc " .. sourcename .. "_html.toc " ..
5135     sourcename ..".lof " .. sourcename .. "_html.lof " ..
5136     sourcename ..".lot " .. sourcename .. "_html.lot " ..
5137     sourcename ..".bbl " .. sourcename .. "_html.bbl " ..
5138     " *.idx " ..
5139     " *.ind " ..
5140     sourcename ..".ps " .. sourcename .."_html.ps " ..
5141     sourcename ..".log " .. sourcename .. "_html.log " ..
5142     sourcename ..".gl* " .. sourcename .. "_html.gl* " ..
5143     sourcename .. "_html.pdf " ..
```

```
5144     sourcename .. "_html.html " ..
5145     sourcename .. "_html.sidetoc " ..
5146     " *_html_inc.* " ..
5147     " comment_*.cut"
5148     )
5149 end
5150
5151 function checkhtmlpdfexists ()
5152 --
5153 -- Error if the HTML document does not exist.
5154 -- The lateximages are drawn from the HTML PDF version of the document,
5155 -- so "lwarpmk html" must be done before "lwarpmk limages".
5156 --
5157 local htmlpdffile = io.open(sourcename .. "_html.pdf", "r")
5158 if ( htmlpdffile == nil ) then
5159     print ("")
5160     print ("lwarpmk: ===")
5161     print ("lwarpmk: The HTML version of the document does not exist.")
5162     print ("lwarpmk: Enter \"lwarpmk html\" to compile the HTML version.")
5163     print ("lwarpmk: ===")
5164     os.exit(1)
5165 end
5166 io.close (htmlpdffile)
5167 end -- checkhtmlpdfexists
5168
5169
5170 function warnlimages ()
5171 --
5172 -- Warning of a missing <sourcename>-images.txt file:
5173     print ("lwarpmk: ===")
5174     print ("lwarpmk: \"" .. sourcename .. "-images.txt\" does not exist.")
5175     print ("lwarpmk: Your project does not use SVG math or other lateximages,")
5176     print ("lwarpmk: or the file has been deleted somehow.")
5177     print ("lwarpmk: Use \"lwarpmk html1\" to recompile your project")
5178     print ("lwarpmk: and recreate \"" .. sourcename .. "-images.txt\".")
5179    print ("lwarpmk: If your project does not use SVG math or other lateximages,")
5180    print ("lwarpmk: then \"" .. sourcename .. "-images.txt\" will never exist, and")
5181     print ("lwarpmk: \"lwarpmk limages\" will not be necessary.")
5182     print ("lwarpmk: ===")
5183 end -- warnlimages
5184
5185
5186 function warnlimagesrecompile ()
5187 -- Warning if must recompile before creating limages:
5188     print ("")
5189     print ("lwarpmk: ===")
5190     print ("lwarpmk: Cross-references are not yet correct.")
5191    print ("lwarpmk: The document must be recompiled before creating the lateximages.")
5192    print ("lwarpmk: Enter \"lwarpmk html1\" again, then try \"lwarpmk limages\" again.")
5193     print ("lwarpmk: ===")
5194 end --warnlimagesrecompile
5195
5196
5197 function checklimages ()
5198 --
```

```
-- Check <sourcename>.txt to see if need to recompile first.
-- If any entry has a page number of zero, then there were incorrect images.
--
print ("lwarpmk: Checking for a valid " .. sourcename .. "-images.txt file.")
local limagesfile = io.open(sourcename .. "-images.txt", "r")
if ( limagesfile == nil ) then
    warnlimages ()
    os.exit(1)
end
-- Track warning to recompile if find a page 0
local pagezerowarning = false
-- Scan <sourcename>.txt
for line in limagesfile:lines() do
    -- lwimgpage is the page number in the PDF which has the image
    -- lwimghash is true if this filename is a hash
    -- lwimgname is the lateximage filename root to assign for the image
    i,j,lwimgpage,lwimghash,lwimgname = string.find (line,"|(.*)|(.*)|(.*)|")
    -- For each entry:
    if ( (i~=nil) ) then
        -- If the page number is 0, image references are incorrect
        --  and must recompile the soure document:
        if ( lwimgpage == "0" ) then
            pagezerowarning = true
        end
    end -- if i~=nil
end -- do
-- The last line should be |end|end|end|.
-- If not, the compile must have aborted, and the images are incomplete.
if ( lwimgpage ~= "end" ) then
    warnlimagesrecompile()
    os.exit(1) ;
end
if ( pagezerowarning ) then
    warnlimagesrecompile()
    os.exit(1) ;
end -- pagezerowarning
end -- checklimages


function createuniximage ( lwimgfullname )
--
-- Create one lateximage for Unix / Linux / Mac OS.
--
executecheckerror (
    cmdgroupopenname ..
    "pdfseparate -f " .. lwimgpage .. " -l " .. lwimgpage .. " " ..
        sourcename .."_html.pdf " ..
        imagesdirectory .. dirslash .."lateximagetemp-%d" .. ".pdf" ..
        seqname ..
    -- Crop the image:
    "pdfcrop  --hires  " .. imagesdirectory .. dirslash .. "lateximagetemp-" ..
        lwimgpage .. ".pdf " ..
        imagesdirectory .. dirslash .. lwimgname .. ".pdf" ..
        seqname ..
    -- Convert the image to svg:
```

```
5254    "pdftocairo -svg -noshrink " .. imagesdirectory .. dirslash .. lwimgname .. ".pdf " ..
5255         imagesdirectory .. dirslash .. lwimgname ..".svg" ..
5256         seqname ..
5257      -- Remove the temporary files:
5258    rmname .. " " .. imagesdirectory .. dirslash .. lwimgname .. ".pdf" .. seqname ..
5259    rmname .. " " .. imagesdirectory .. dirslash .. "lateximagetemp-" .. lwimgpage .. ".pdf" ..
5260     cmdgroupclosename .. " >/dev/null " .. bgname
5261     ,
5262     "File error trying to convert " .. lwimgfullname
5263 )
5264 -- Every 32 images, wait for completion at below normal priority,
5265 --  allowing other image tasks to catch up.
5266 numimageprocesses = numimageprocesses + 1
5267 if ( numimageprocesses > 32 ) then
5268     numimageprocesses = 0
5269     print ( "lwarpmk: waiting" )
5270     executecheckerror ( "wait" , "File error trying to wait.")
5271 end
5272 end -- createuniximage
5273
5274
5275 function createwindowsimage ( lwimgfullname )
5276 --
5277 -- Create one lateximage for Windows.
5278 --
5279 -- Every 32 images, wait for completion at below normal priority,
5280 --  allowing other image tasks to catch up.
5281 numimageprocesses = numimageprocesses + 1
5282 if ( numimageprocesses > 32 ) then
5283     numimageprocesses = 0
5284     thiswaitcommand = "/WAIT /BELOWNORMAL"
5285     print ( "lwarpmk: waiting" )
5286 else
5287     thiswaitcommand = ""
5288 end
5289 -- Execute the image generation command
5290 executecheckerror (
5291     "start /B " .. thiswaitcommand .. " \"\" lwarp_one_limage " ..
5292     lwimgpage .. " " ..
5293     lwimghash .. " " ..
5294     lwimgname .. " " ..
5295     sourcename .. " <nul >nul"
5296     ,
5297     "File error trying to create image."
5298 )
5299 end -- createwindowsimage
5300
5301
5302 function createonelateximage ( line )
5303 --
5304 -- Given the next line of <sourcename>.txt, convert a single image.
5305 --
5306 -- lwimgpage is the page number in the PDF which has the image
5307 -- lwimghash is true if this filename is a hash
5308 -- lwimgname is the lateximage filename root to assign for the image
```

```
i,j,lwimgpage,lwimghash,lwimgname = string.find (line,"|(.*)|(.*)|(.*)|")
-- For each entry:
if ( (i~=nil) ) then
    -- Skip if the page number is 0:
    if ( lwimgpage == "0" ) then
        pagezerowarning = true
    -- Skip if the page number is "end":
    else if ( lwimgpage == "end" ) then
    else
        -- Skip is this image is hashed and already exists:
       local lwimgfullname = imagesdirectory .. dirslash .. lwimgname .. ".svg"
        if (
            (lwimghash ~= "true") or
            (lfs.attributes(lwimgfullname,"mode")==nil) -- file not exists
        )
        then -- not hashed or not exists:
            -- Print the name of the file being generated:
            print ( "lwarpmk: " .. lwimgname )
          -- Touch/create the dest so that only once instance tries to build it:
            executecheckerror (
                newtouchname .. " " .. lwimgfullname ,
                "File error trying to touch " .. lwimgfullname
            )
            -- Separate out the image into its own single-page pdf:
            if opsystem=="Unix" then
                createuniximage (lwimgfullname)
            elseif opsystem=="Windows" then
                createwindowsimage (lwimgfullname)
            end
        end -- not hashed or not exists
    end -- not page "end"
    end -- not page 0
end -- not nil
end -- createonelateximage


function createlateximages ()
--
-- Create lateximages based on <sourcename>-images.txt:
--
-- See if the document must be recompiled first:
checklimages ()
-- See if the HTML version exists:
checkhtmlpdfexists ()
-- Attempt to create the lateximages:
print ("lwarpmk: Creating lateximages.")
local limagesfile = io.open(sourcename .. "-images.txt", "r")
if ( limagesfile == nil ) then
    warnlimages ()
    os.exit(1)
end
-- Create the lateximages directory, ignore error if already exists
err = os.execute("mkdir " .. imagesdirectory)
-- For Windows, create lwarp_one_limage.cmd from lwarp_one_limage.txt:
if opsystem=="Windows" then
```

```
5364     executecheckerror (
5365         cpname .. " lwarp_one_limage.txt lwarp_one_limage.cmd" ,
5366        "File error trying to copy lwarp_one_limage.txt to lwarp_one_limage.cmd"
5367     )
5368 end -- create lwarp_one_limage.cmd
5369 -- Track the number of parallel processes
5370 numimageprocesses = 0
5371 -- Track warning to recompile if find a page 0
5372 pagezerowarning = false
5373 -- Scan <sourcename>.txt
5374 for line in limagesfile:lines() do
5375     createonelateximage ( line )
5376 end -- do
5377 io.close(limagesfile)
5378 print ( "lwarpmk limages: ===")
5379 print ( "lwarpmk limages: Wait a moment for the images to complete" )
5380 print ( "lwarpmk limages:   before reloading the page." )
5381 print ( "lwarpmk limages: ===")
5382 print ( "lwarpmk limages: Done." )
5383 if ( pagezerowarning == true ) then
5384     print ( "lwarpmk limages: WARNING: Images will be incorrect." )
5385     print ( "lwarpmk limages:   Enter \"lwarpmk cleanlimages\", then" )
5386     print ( "lwarpmk limages:   recompile the document one more time, then" )
5387     print ( "lwarpmk limages:   repeat \"lwarpmk images\" again." )
5388 end -- pagezerowarning
5389 end -- function
5390
5391
5392 function convertepstopdf ()
5393 --
5394 -- Converts EPS files to PDF files.
5395 -- The filenames are arg[argindex] and up.
5396 -- arg[1] is the command "epstopdf".
5397 --
5398 ignoreconf ()
5399 for i = argindex , #arg do
5400     if (lfs.attributes(arg[i],"mode")==nil) then
5401         print ("lwarpmk: File \"" .. arg[i] .. "\" does not exist.")
5402     else
5403         print ("lwarpmk: Converting \"" .. arg[i] .. "\"")
5404         thispath, thisfilename, thisextension = splitfilename(arg[i])
5405         if ( thispath == nil ) then
5406             os.execute ( "epstopdf " .. arg[i] )
5407         else
5408             os.execute (
5409                 "epstopdf " ..
5410                 thispath .. thisfilename .. "." .. thisextension .. " " ..
5411                 thispath .. thisfilename .. ".pdf"
5412             )
5413         end
5414     end -- if
5415 end -- do
5416 end --function
5417
5418
```

```
function convertpdftosvg ()
--
-- Converts PDF files to SVG files.
-- The filenames are arg[argindex] and up.
-- arg[1] is the command "pdftosvg".
--
ignoreconf ()
for i = argindex , #arg do
    if (lfs.attributes(arg[i],"mode")==nil) then
        print ("lwarpmk: File \"" .. arg[i] .. "\" does not exist.")
    else
        print ("lwarpmk: Converting \"" .. arg[i] .. "\"")
        thispath, thisfilename, thisextension = splitfilename(arg[i])
        if ( thispath == nil ) then
            os.execute ( "pdftocairo -svg " .. arg[i] )
        else
            os.execute (
                "pdftocairo -svg " ..
                thispath .. thisfilename .. "." .. thisextension .. " " ..
                thispath .. thisfilename .. ".svg"
            )
        end
    end -- if
end -- do
end --function


-- Force an update and conclude processing:
function updateanddone ()
print ("lwarpmk: Forcing an update of " .. sourcename ..".tex.")
refreshdate ()
print ("lwarpmk: " .. sourcename ..".tex is ready to be recompiled.")
print ("lwarpmk: Done.")
end -- function


-- Start of the main code: --


-- lwarpmk --version :

if (arg[1] == "--version") then
print ( "lwarpmk: " .. printversion )

else -- not --version


-- print intro:

print ("lwarpmk: " .. printversion .. "  Automated make for the LaTeX Lwarp package.")


-- lwarpmk print:

if arg[1] == "print" then
```

```
loadconf ()
if ( latexmk == "true" ) then
    print ("lwarpmk: Compiling with: " .. printlatexcmd)
    executecheckerror (
        printlatexcmd ,
        "Compile error."
    )
    print ("lwarpmk: Done.")
else -- not latexmk
    verifyfileexists (sourcename .. ".tex") ;
    -- See if up to date:
    if (
        ( lfs.attributes ( sourcename .. ".pdf" , "modification" ) == nil ) or
        (
            lfs.attributes ( sourcename .. ".tex" , "modification" ) >
            lfs.attributes ( sourcename .. ".pdf" , "modification" )
        )
    ) then
        -- Recompile if not yet up to date:
        manytimes(printlatexcmd, "")
        print ("lwarpmk: Done.") ;
    else
        print ("lwarpmk: " .. sourcename .. ".pdf is up to date.") ;
    end
end -- not latexmk


-- lwarpmk print1:

elseif arg[1] == "print1" then
    loadconf ()
    verifyfileexists (sourcename .. ".tex") ;
    onetime(printlatexcmd, "")
    print ("lwarpmk: Done.") ;


-- lwarpmk printindex:
-- Compile the index then touch the source
-- to trigger a recompile of the document:

elseif arg[1] == "printindex" then
loadconf ()
os.execute ( printindexcmd )
print ("lwarpmk: -------")
updateanddone ()


-- lwarpmk printglossary:
-- Compile the glossary then touch the source
-- to trigger a recompile of the document:

elseif arg[1] == "printglossary" then
loadconf ()
print ("lwarpmk: Processing the glossary.")

```

```
os.execute(glossarycmd .. " " .. sourcename)
updateanddone ()


-- lwarpmk html:

elseif arg[1] == "html" then
loadconf ()
if ( latexmk == "true" ) then
    print ("lwarpmk: Compiling with: " .. HTMLlatexcmd)
    executecheckerror (
        HTMLlatexcmd ,
        "Compile error."
    )
    pdftohtml ()
    print ("lwarpmk: Done.")
else -- not latexmk
    verifyfileexists ( sourcename .. ".tex" ) ;
    -- See if exists and is up to date:
    if (
      ( lfs.attributes ( homehtmlfilename .. ".html" , "modification" ) == nil ) or
        (
            lfs.attributes ( sourcename .. ".tex" , "modification" ) >
            lfs.attributes ( homehtmlfilename .. ".html" , "modification" )
        )
    ) then
        -- Recompile if not yet up to date:
        manytimes(HTMLlatexcmd, "_html")
        pdftohtml ()
        print ("lwarpmk: Done.")
    else
        print ("lwarpmk: " .. homehtmlfilename .. ".html is up to date.")
    end
end -- not latexmk


-- lwarpmk html1:

elseif arg[1] == "html1" then
    loadconf ()
    verifyfileexists ( sourcename .. ".tex" ) ;
    onetime(HTMLlatexcmd, "_html")
    pdftohtml ()
    print ("lwarpmk: Done.")


-- lwarpmk pdftohtml:
elseif arg[1] == "pdftohtml" then
    loadconf ()
    pdftohtml ()


-- lwarpmk htmlindex:
-- Compile the index then touch the source
-- to trigger a recompile of the document:
```

```
5584
5585 elseif arg[1] == "htmlindex" then
5586 loadconf ()
5587 os.execute ( HTMLindexcmd )
5588 print ("lwarpmk: -------")
5589 updateanddone ()
5590
5591
5592 -- lwarpmk htmlglossary:
5593 -- Compile the glossary then touch the source
5594 -- to trigger a recompile of the document.
5595 -- The <sourcename>.xdy file is created by the glossaries package.
5596
5597 elseif arg[1] == "htmlglossary" then
5598 loadconf ()
5599 print ("lwarpmk: Processing the glossary.")
5600 os.execute(glossarycmd .. " " .. sourcename .. "_html")
5601 updateanddone ()
5602
5603
5604 -- lwarpmk limages:
5605 -- Scan the <sourcename>.txt file to create lateximages.
5606
5607 elseif arg[1] == "limages" then
5608 loadconf ()
5609 print ("lwarpmk: Processing images.")
5610 createlateximages ()
5611 print ("lwarpmk: Done.")
5612
5613
5614 -- lwarpmk again:
5615 -- Touch the source to trigger a recompile.
5616
5617 elseif arg[1] == "again" then
5618 loadconf ()
5619 updateanddone ()
5620
5621
5622 -- lwarpmk clean:
5623 -- Remove project.aux, .toc, .lof, .lot, .log, *.idx, *.ind, *_html_inc.*, .gl*
5624
5625 elseif arg[1] == "clean" then
5626 loadconf ()
5627 removeaux ()
5628 print ("lwarpmk: Done.")
5629
5630
5631 -- lwarpmk cleanall
5632 -- Remove project.aux, .toc, .lof, .lot, .log, *.idx, *.ind, *_html_inc.*, .gl*
5633 --    and also project.pdf, project.dvi, *.html
5634
5635 elseif arg[1] == "cleanall" then
5636 loadconf ()
5637 removeaux ()
5638 os.execute ( rmname .. " " ..
```

```
    sourcename .. ".pdf " .. sourcename .. "_html.pdf " ..
    sourcename .. ".dvi " .. sourcename .. "_html.dvi " ..
    "*.html"
    )
print ("lwarpmk: Done.")


-- lwarpmk cleanlimages
-- Remove images from the imagesdirectory.

elseif arg[1] == "cleanlimages" then
loadconf ()
os.execute ( rmname .. " " .. imagesdirectory .. dirslash .. "*" )
print ("lwarpmk: Done.")

-- lwarpmk epstopdf <list of file names>
-- Convert EPS files to PDF using epstopdf
elseif arg[1] == "epstopdf" then
convertepstopdf ()
print ("lwarpmk: Done.")


-- lwarpmk pdftosvg <list of file names>
-- Convert PDF files to SVG using pdftocairo
elseif arg[1] == "pdftosvg" then
convertpdftosvg ()
print ("lwarpmk: Done.")


-- lwarpmk with no argument :

elseif (arg[1] == nil) then
printhelp ()


-- lwarpmk -v:

elseif (arg[1] == "-v" ) then
-- The version number has already been printed
-- by the lwarpmk intro.

-- lwarpmk -h or lwarpmk --help :

elseif (arg[1] == "-h" ) or (arg[1] == "--help") then
printusage ()


-- Unknown command:

else
printhelp ()
print ("\nlwarpmk: ****** Unknown command \""..arg[1].."\". ******\n")
end

end -- not --version
```

```
\end{filecontents*}
% \end{Verbatim}% for syntax highlighting

\end{LWRcreatelwarpmk}
```

41 Stacks

for HTML output:

```
\begin{warpHTML}
```

Stacks are used to remember how to close sections and list items. Before a new section is started, previously nested sections and items must be closed out (un-nested) in proper order. Note that starting a new section may close several levels of previously nested items at the same time. For example, starting a new `\section` would close any currently open subsection, subsubsection, and paragraph. General environments are not nested on the stack since they have their own close mechanism. List environments are nested, and items inside those environments are nested one level deeper still. List environments may be nested inside other list environments, and list items are nested inside list environments as well. Thus, the stack may have items which are not necessarily in order, since a description may contain an enumerate, for example. Depths to be recorded in `\LWR@closedepthone`, etc.

41.1 Assigning depths

initial depths for empty stack entries:

```
\newcommand*{\LWR@depthnone}{-5}
```

All sectioning depths are deeper than `LWR@depthfinished`:

```
\newcommand*{\LWR@depthfinished}{-4}
\newcommand*{\LWR@depthbook}{-2}
\newcommand*{\LWR@depthpart}{-1}
\newcommand*{\LWR@depthchapter}{0}
\newcommand*{\LWR@depthsection}{1}
\newcommand*{\LWR@depthsubsection}{2}
\newcommand*{\LWR@depthsubsubsection}{3}
\newcommand*{\LWR@depthparagraph}{4}
\newcommand*{\LWR@depthsubparagraph}{5}
```

Used by `\itemize`, `\enumerate`, `\description`:

```
\newcommand*{\LWR@depthlist}{6}
```

Used by `\item`:

```
\newcommand*{\LWR@depthlistitem}{7}
\let\LWR@depthdescitem\LWR@depthlistitem
```

41.2 Closing actions

A stack to record the action to take to close each nesting level: Add more levels of stack if necessary for a very deeply nested document, adding to \pushclose and \popclose as well.

```
\newcommand*{\LWR@closeone}{}% top of the stack
\newcommand*{\LWR@closetwo}{}
\newcommand*{\LWR@closethree}{}
\newcommand*{\LWR@closefour}{}
\newcommand*{\LWR@closefive}{}
\newcommand*{\LWR@closesix}{}
\newcommand*{\LWR@closeseven}{}
\newcommand*{\LWR@closeeight}{}
\newcommand*{\LWR@closenine}{}
\newcommand*{\LWR@closeten}{}
\newcommand*{\LWR@closeeleven}{}
\newcommand*{\LWR@closetwelve}{}
\newcommand*{\LWR@closethirteen}{}
\newcommand*{\LWR@closefourteen}{}
\newcommand*{\LWR@closefifteen}{}
\newcommand*{\LWR@closesixteen}{}
\newcommand*{\LWR@closeseventeen}{}
\newcommand*{\LWR@closeeighteen}{}
\newcommand*{\LWR@closenineteen}{}
```

41.3 Closing depths

A stack to record the depth of each level:

⚠ Note that nested LaTeX structures may push depths which are non-sequential.

Ex:

```
\begin{itemize}
   \item{A}
   \begin{description}
      \item{B}
   \end{description}
\end{itemize}
```

```
\newcommand*{\LWR@closedepthone}{\LWR@depthnone}% top of the stack
\newcommand*{\LWR@closedepthtwo}{\LWR@depthnone}
\newcommand*{\LWR@closedepththree}{\LWR@depthnone}
\newcommand*{\LWR@closedepthfour}{\LWR@depthnone}
\newcommand*{\LWR@closedepthfive}{\LWR@depthnone}
\newcommand*{\LWR@closedepthsix}{\LWR@depthnone}
\newcommand*{\LWR@closedepthseven}{\LWR@depthnone}
\newcommand*{\LWR@closedeptheight}{\LWR@depthnone}
\newcommand*{\LWR@closedepthnine}{\LWR@depthnone}
\newcommand*{\LWR@closedepthten}{\LWR@depthnone}
```

```
\newcommand*{\LWR@closedepththeleven}{\LWR@depthnone}
\newcommand*{\LWR@closedepththirteen}{\LWR@depthnone}
\newcommand*{\LWR@closedepthfourteen}{\LWR@depthnone}
\newcommand*{\LWR@closedepthfifteen}{\LWR@depthnone}
\newcommand*{\LWR@closedepthsixteen}{\LWR@depthnone}
\newcommand*{\LWR@closedepthseventeen}{\LWR@depthnone}
\newcommand*{\LWR@closedepthtwelve}{\LWR@depthnone}
\newcommand*{\LWR@closedepthnineteen}{\LWR@depthnone}
```

41.4 Pushing and popping the stack

`\LWR@pushclose` {⟨*sectiontype*⟩}

Pushes one return action and its LaTeX depth onto the stacks.

```
\NewDocumentCommand{\LWR@pushclose}{m}
{%
\global\let\LWR@closenineteen\LWR@closeeighteen%
\global\let\LWR@closeeighteen\LWR@closeseventeen%
\global\let\LWR@closeseventeen\LWR@closesixteen%
\global\let\LWR@closesixteen\LWR@closefifteen%
\global\let\LWR@closefifteen\LWR@closefourteen%
\global\let\LWR@closefourteen\LWR@closethirteen%
\global\let\LWR@closethirteen\LWR@closetwelve%
\global\let\LWR@closetwelve\LWR@closeeleven%
\global\let\LWR@closeeleven\LWR@closeten%
\global\let\LWR@closeten\LWR@closenine%
\global\let\LWR@closenine\LWR@closeeight%
\global\let\LWR@closeeight\LWR@closeseven%
\global\let\LWR@closeseven\LWR@closesix%
\global\let\LWR@closesix\LWR@closefive%
\global\let\LWR@closefive\LWR@closefour%
\global\let\LWR@closefour\LWR@closethree%
\global\let\LWR@closethree\LWR@closetwo%
\global\let\LWR@closetwo\LWR@closeone%
\global\csletcs{LWR@closeone}{LWR@printclose#1}%
\global\let\LWR@closedepthnineteen\LWR@closedepteighteen%
\global\let\LWR@closedepteighteen\LWR@closedepthseventeen%
\global\let\LWR@closedepthseventeen\LWR@closedepthsixteen%
\global\let\LWR@closedepthsixteen\LWR@closedepthfifteen%
\global\let\LWR@closedepthfifteen\LWR@closedepthfourteen%
\global\let\LWR@closedepthfourteen\LWR@closedepththirteen%
\global\let\LWR@closedepththirteen\LWR@closedepthtwelve%
\global\let\LWR@closedepthtwelve\LWR@closedepthteleven%
\global\let\LWR@closedepthteleven\LWR@closedepthten%
\global\let\LWR@closedepthten\LWR@closedepthnine%
\global\let\LWR@closedepthnine\LWR@closedepteight%
\global\let\LWR@closedepteight\LWR@closedepthseven%
\global\let\LWR@closedepthseven\LWR@closedepthsix%
\global\let\LWR@closedepthsix\LWR@closedepthfive%
\global\let\LWR@closedepthfive\LWR@closedepthfour%
\global\let\LWR@closedepthfour\LWR@closedepththree%
\global\let\LWR@closedepththree\LWR@closedepthtwo%
```

```
\global\let\LWR@closedepthtwo\LWR@closedepthone%
\global\csletcs{LWR@closedepthone}{LWR@depth#1}%
```

Error if the deepest depth is no longer \LWR@depthnone, which means that it somehow has been nested too deeply, or things are not being unnested correctly.

```
\ifdefstring{\LWR@closedepthnineteen}{\LWR@depthnone}%
    {}%
    {%
        \PackageError{lwarp}%
            {The document is nested too deeply for Lwarp}%
            {PLEASE inform the Lwarp maintainer!}%
    }%
}
```

\LWR@popclose Pops one action and its depth off the stacks.

```
\newcommand*{\LWR@popclose}
{%
\global\let\LWR@closeone\LWR@closetwo%
\global\let\LWR@closetwo\LWR@closethree%
\global\let\LWR@closethree\LWR@closefour%
\global\let\LWR@closefour\LWR@closefive%
\global\let\LWR@closefive\LWR@closesix%
\global\let\LWR@closesix\LWR@closeseven%
\global\let\LWR@closeseven\LWR@closeeight%
\global\let\LWR@closeeight\LWR@closenine%
\global\let\LWR@closenine\LWR@closeten%
\global\let\LWR@closeten\LWR@closeeleven%
\global\let\LWR@closeeleven\LWR@closetwelve%
\global\let\LWR@closetwelve\LWR@closethirteen%
\global\let\LWR@closethirteen\LWR@closefourteen%
\global\let\LWR@closefourteen\LWR@closefifteen%
\global\let\LWR@closefifteen\LWR@closesixteen%
\global\let\LWR@closesixteen\LWR@closeseventeen%
\global\let\LWR@closeseventeen\LWR@closeeighteen%
\global\let\LWR@closeeighteen\LWR@closenineteen%
\global\let\LWR@closedepthone\LWR@closedepthtwo%
\global\let\LWR@closedepthtwo\LWR@closedepththree%
\global\let\LWR@closedepththree\LWR@closedepthfour%
\global\let\LWR@closedepthfour\LWR@closedepthfive%
\global\let\LWR@closedepthfive\LWR@closedepthsix%
\global\let\LWR@closedepthsix\LWR@closedepthseven%
\global\let\LWR@closedepthseven\LWR@closedeptheight%
\global\let\LWR@closedeptheight\LWR@closedepthnine%
\global\let\LWR@closedepthnine\LWR@closedepthten%
\global\let\LWR@closedepthten\LWR@closedeptheleven%
\global\let\LWR@closedeptheleven\LWR@closedepthtwelve%
\global\let\LWR@closedepthtwelve\LWR@closedepththirteen%
\global\let\LWR@closedepththirteen\LWR@closedepthfourteen%
\global\let\LWR@closedepthfourteen\LWR@closedepthfifteen%
\global\let\LWR@closedepthfifteen\LWR@closedepthsixteen%
\global\let\LWR@closedepthsixteen\LWR@closedepthseventeen%
\global\let\LWR@closedepthseventeen\LWR@closedeptheighteen%
\global\let\LWR@closedeptheighteen\LWR@closedepthnineteen%
```

```
}
\end{warpHTML}
```

42 Data arrays

These macros are similar to the arrayjobx package, except that `\LWR@setexparray`'s argument is expanded only once when assigned.

`name` has no backslash, `index` can be a number or a text name, and an empty `value` must be `\relax` instead of empty.

To assign an empty value:

```
\LWR@setexparray{name}{index}{}
```

for HTML output:

```
\begin{warpHTML}
```

`\LWR@setexparray` {⟨*name*⟩} {⟨*index*⟩} {⟨*contents*⟩}

```
\NewDocumentCommand{\LWR@setexparray}{m m m}{%
    \let\LWR@temp@par\par%
    \let\par\relax%
    \edef\LWR@thisexparrayname{#1#2}%
    \ifstrempty{#3}%
        {\csdef{\LWR@thisexparrayname}{}}%
        {\csedef{\LWR@thisexparrayname}{#3}}%
    \let\par\LWR@temp@par%
}
```

`\LWR@getexparray` {⟨*name*⟩} {⟨*index*⟩}

```
\newcommand*{\LWR@getexparray}[2]{%
    \@nameuse{#1#2}%
}
```

```
\end{warpHTML}
```

43 Localizing catcodes

for HTML & PRINT:

```
\begin{warpall}
```

⚠ Misplaced alignment tab character &

Place `\StartDefiningTabulars` and `\StopDefiningTabulars` before and after defining macros or environments which include the tabular & character in their definitions.

The catcode of & must be changed before the definitions begin, and must be restored afterwards. Doing so avoids the error

```
Misplaced alignment tab character &.
```

\StartDefiningTabulars Place before defining something with & in it.

```
\newcommand{\StartDefiningTabulars}{%
    \LWR@traceinfo{StartDefiningTabulars}%
    \warpHTMLonly{\catcode`\&=\active}%
}
```

\StopDefiningTabulars Place after defining something with & in it.

```
\newcommand{\StopDefiningTabulars}{%
    \LWR@traceinfo{StopDefiningTabulars}%
    \warpHTMLonly{\catcode`\&=4}%
}
```

Bool LWR@mathmacro True if currently defining math macros. Used to disable SVG math hashing and MathJax math contents while defining a macro using inline math. Begin a macro, it is not guaranteed that the contents are static, and so the image must be unique. The contents also almost certainly will not be parsed correctly by MathJax.

```
\newbool{LWR@mathmacro}
\boolfalse{LWR@mathmacro}
```

\StartDefiningMath Place before defining something with $ in it.

```
\newcommand{\StartDefiningMath}{%
    \LWR@traceinfo{StartDefiningMath}%
    \warpHTMLonly{\catcode`\$=\active}%
}
```

\StopDefiningMath Place after defining something with $ in it.

```
\newcommand{\StopDefiningMath}{%
    \LWR@traceinfo{StopDefiningMath}%
    \warpHTMLonly{\catcode`\$=3}% math shift
}
```

```
\end{warpall}
```

44 Localizing dynamic math

Inline SVG math usually uses a hash of its contents to generate `latexi`mages which are reusable for multiple instances with the same contents. If the contents may change for each use, such as depending on the current value of a counter, then `\inlinemathother` must be used before the inline math expression, and `\inlinemathnormal` must be used after.

For MathJax, the inline math expression is usually printed for MathJax to interpret. When marked as dynamic math, the following inline math expression will be displayed as an unhashed inline SVG image instead.

For existing code and packages, it may be possible to patch macros after they have been defined, using the xpatch package, which is pre-loaded by lwarp:

```
\xpatchcmd{\macroname}
    {$math expression$}
    {\inlinemathother$math expression$\inlinemathnormal}
    {}
    {\typeout{Error patching macroname.}}
```

for HTML & PRINT:

```
\begin{warpall}
```

Bool `LWR@dynamicmath` Default: `false`

True to mark inline math which is dynamic in nature, thus should not be hashed for reuse.

```
\newbool{LWR@dynamicmath}
\boolfalse{LWR@dynamicmath}
```

`\inlinemathother` Place before using $ … $ or \(… \) if the contents of the math are not static, depending on counters or dynamic macros.

```
\newcommand{\inlinemathother}{%
\LWR@traceinfo{inlinemathother}%
\booltrue{LWR@dynamicmath}%
}
```

`\inlinemathnormal` Place after using $ … $ or \(… \) with dynamic contents.

```
\newcommand{\inlinemathnormal}{%
\LWR@traceinfo{inlinemathnormal}%
\boolfalse{LWR@dynamicmath}%
}
```

```
\end{warpall}
```

45 HTML entities

for HTML output:

```
\begin{warpHTML}
```

HTML Unicode entities:

```
\let\LWR@origampersand\&
```

`\HTMLentity` {⟨*entitytag*⟩}

```
\newcommand*{\HTMLentity}[1]{%
% \LWR@traceinfo{HTMLentity \detokenize{#1}}%
\begingroup%
\LWR@hook@processingtags%
```

```
\LWR@origampersand#1;%
\endgroup%
% \LWR@traceinfo{HTMLentity done}%
}
```

\HTMLunicode {⟨*hex_unicode*⟩}

```
\newcommand*{\HTMLunicode}[1]{\HTMLentity{\LWR@origpound{}x#1}}
```

\&

```
\renewrobustcmd*{\&}{\HTMLentity{amp}}
```

\textless

```
\let\LWR@origtextless\textless
\renewrobustcmd*{\textless}{\HTMLentity{lt}}
```

\textgreater

```
\let\LWR@origtextgreater\textgreater
\renewrobustcmd*{\textgreater}{\HTMLentity{gt}}

\end{warpHTML}
```

46 HTML filename generation

The filename of the homepage is set to \HomeHTMLFilename.html. The filenames of additional sections start with \HTMLFilename, to which is appended a section number or a simplified section name, depending on FileSectionNames.

for HTML & PRINT:

```
\begin{warpall}
```

\BaseJobname The \jobname of the printed version, even if currently compiling the HTML version. I.e. this is the \jobname without _html appended. This is used to set \HomeHTMLFilename if the user did not provide one.

```
\providecommand*{\BaseJobname}{\jobname}
```

\HTMLFilename The prefix for all generated HTML files other than the home page, defaulting to empty. See section 7.6.1.

```
\providecommand*{\HTMLFilename}{}
```

\HomeHTMLFilename The filename of the home page, defaulting to the \BaseJobname. See section 7.6.1.

```
\providecommand*{\HomeHTMLFilename}{\BaseJobname}
```

`\SetHTMLFileNumber` {⟨*number*⟩}

Sets the file number for the next file to be generated. 0 is the home page. Use just before the next sectioning command, and set it to one less than the desired number of the next section. May be used to generate numbered groups of nodes such as 100+ for one chapter, 200+ for another chapter, etc.

```
\newcommand*{\SetHTMLFileNumber}[1]{%
    \setcounter{LWR@htmlfilenumber}{#1}%
}
```

Bool `FileSectionNames` Selects how to create HTML file names.

Defaults to use section names in the filenames.

```
\newbool{FileSectionNames}
\booltrue{FileSectionNames}
```

```
\end{warpall}
```

for HTML output:

```
\begin{warpHTML}
```

Updated each time a new HTML file is begun. Used to provide HTML previous/next web page links.

```
\newcounter{LWR@HTMLpagenum}
\setcounter{LWR@HTMLpagenum}{0}
```

Ctr `LWR@htmlseqfilenumber` A sequential count of the number of each HTML file as it is being created. Number 0 is the home page. Unlike `\LWR@htmlfilenumber`, this one is known to increment by one for each file. This is used to generate previous /next links for each web page, via labels called `\BaseJobname-autofile-*`, and the last page is also labelled `\BaseJobname-autofile-last`.

```
\newcounter{LWR@htmlseqfilenumber}
\setcounter{LWR@htmlseqfilenumber}{0}
```

Bool `LWR@setseqfilelabel` At each new HTML file, this is false until a sectional unit is used, at which point this is set true and a label is placed. In this way, the previous/next labels will point to a named section.

```
\newbool{LWR@setseqfilelabel}
\setbool{LWR@setseqfilelabel}{false}
```

Ctr `LWR@htmlfilenumber` Records the number of each HTML file as it is being created. Number 0 is the home page. This might not be sequential, as the user may use `\SetHTMLFileNumber` to create groups of numbered nodes.

```
\newcounter{LWR@htmlfilenumber}
\setcounter{LWR@htmlfilenumber}{0}
```

`\LWR@htmlsectionfilename` {⟨*htmlfilenumber or name*⟩}

Prints the filename for a given section: `\HTMLFilename{}filenumber/name.html`

```
\newcommand*{\LWR@htmlsectionfilename}[1]{%
\LWR@traceinfo{LWR@htmlsectionfilename A !\detokenize{#1}!}%
\begingroup%
```

Disable CJK xpinyin while generating file names.

```
\LWR@disablepinyin%
```

Section 0 or empty is given the home filename. The filename must be detokenized for underscores.

```
% \LWR@traceinfo{about to assign temp}%
\LWR@sanitize{#1}%
\LWR@traceinfo{about to compare with ??}%
\ifdefstring{\LWR@sanitized}{??}
    {\LWR@traceinfo{found ??}}%
    {\LWR@traceinfo{not found ??}}%
\LWR@traceinfo{about to compare with zero or empty}%
\ifboolexpr{
    test {\ifdefstring{\LWR@sanitized}{0}} or
    test {\ifdefstring{\LWR@sanitized}{}} or
    test {\ifdefstring{\LWR@sanitized}{??}}
}
{%
    \LWR@traceinfo{LWR@htmlsectionfilename B \HomeHTMLFilename.html}%
    \HomeHTMLFilename.html%
}%
```

For a LaTeX section named “Index” or “index” without a prefix, create a filename with a trailing `-0` to avoid colliding with the HTML filename `index.html`:

```
{%
    \LWR@traceinfo{LWR@htmlsectionfilename C \LWR@sanitized}%
    \ifboolexpr{
            test{\ifdefvoid{\HTMLFilename}} and
            (
                test{\ifdefstring{\LWR@sanitized}{Index}} or
                test{\ifdefstring{\LWR@sanitized}{index}}
            )
    }%
    {%
        \LWR@traceinfo{Adding a zero to the index filename.}%
        \LWR@sanitized-0.html%
    }%
```

Otherwise, create a filename with the chosen prefix:

```
    {%
        \HTMLFilename\LWR@isolate{\LWR@sanitized}.html%
    }%
}%
\LWR@traceinfo{LWR@htmlsectionfilename Z}%
\endgroup%
```

```
}
```

`\LWR@htmlrefsectionfilename` {⟨*label*⟩}

Prints the filename for the given label

```
\newcommand*{\LWR@htmlrefsectionfilename}[1]{%
    \LWR@traceinfo{LWR@htmlrefsectionfilename: !\detokenize{#1}!}%
```

`\LWR@nullfonts` to allow math in a section name.

```
    \begingroup%
    \LWR@nullfonts%
    \LWR@htmlsectionfilename{\LWR@htmlfileref{#1}}%
    \endgroup%
    \LWR@traceinfo{LWR@htmlrefsectionfilename: done}%
}
```

```
\end{warpHTML}
```

47 Homepage link

for HTML & PRINT:

```
\begin{warpall}
```

`\linkhomename` Holds the default name for the home link.

```
\newcommand{\linkhomename}{Home}
```

```
\end{warpall}
```

for HTML output:

```
\begin{warpHTML}
```

`\LinkHome` May be used wherever you wish to place a link back to the homepage. The filename must be detokenized for underscores.

```
\newcommand*{\LinkHome}{%
    \LWR@subhyperrefclass{\HomeHTMLFilename.html}{\linkhomename}{linkhome}%
}
```

```
\end{warpHTML}
```

for PRINT output:

```
\begin{warpprint}
```

`\LinkHome` May be used wherever you wish to place a link back to the homepage. For print output, if hyperref is available a hyperlink to the first page is used, named by `\linkhomename`. If hyperref is not available, a pageref is used instead.

`\BaseJobname` is included in the link label in case multiple documents are cross-referenced.

```
\AtBeginDocument{
\@ifundefined{hyperref}{
    \newcommand*{\LinkHome}{%
        \linkhomename\ --- page \pageref{\BaseJobname-page-LWRfirstpage}%
    }
}{
    \newcommand*{\LinkHome}{%
        \hyperref[\BaseJobname-page-LWRfirstpage]{\linkhomename}%
    }
}
}

\AfterEndPreamble{\label{\BaseJobname-page-LWRfirstpage}}

\end{warpprint}
```

for HTML output:

```
\begin{warpHTML}
```

`\LWR@topnavigation` Creates a link to the homepage at the top of the page for use when the window is too narrow for the sideTOC.

```
\newcommand*{\LWR@topnavigation}{%
    \LWR@htmlelementclassline{nav}{topnavigation}{\LinkHome}
}
```

`\LWR@botnavigation` Creates a link to the homepage at the bottom of the page for use when the window is too narrow for the sideTOC.

```
\newcommand*{\LWR@botnavigation}{%
    \LWR@htmlelementclassline{nav}{botnavigation}{\LinkHome}
}

\end{warpHTML}
```

48 Previous/next navigation links

for HTML & PRINT:

```
\begin{warpall}
```

`\linkpreviousname` What to call the link to the previous web page.

```
\newcommand*{\linkpreviousname}{Previous}
```

`\linknextname` What to call the link to the next web page.

```
\newcommand*{\linknextname}{Next}

\end{warpall}
```

for PRINT output:

```
\begin{warpprint}
```

\LinkPrevious Creates a link to the previous web page if there is one.

```
\newcommand*{\LinkPrevious}{}
```

\LinkNext Creates a link to the next web page if there is one.

```
\newcommand*{\LinkNext}{}
```

```
\end{warpprint}
```

for HTML output:

```
\begin{warpHTML}
```

\LinkPrevious Creates a link to the previous web page if there is one.

The links refer to the LaTeX labels \Basejobname-autofile-*

```
\newcommand*{\LinkPrevious}{%
    \ifnumless{\value{LWR@htmlseqfilenumber}}{1}{}{%
        \setcounter{LWR@tempcountone}{\value{LWR@htmlseqfilenumber}-1}%
        \LWR@subhyperrefclass{%
            \LWR@htmlrefsectionfilename{%
                \BaseJobname-autofile-\arabic{LWR@tempcountone}%
            }%
        }{\linkpreviousname}{linkhome}%
    }%
}
```

\LinkNext Creates a link to the next web page if there is one.

The links refer to the LaTeX labels \Basejobname-autofile-*
and the last is the label \Basejobname-autofile-last

```
\newcommand*{\LinkNext}{%
    \ifcsdef{r@\BaseJobname-autofile-last@lwarp}{%
        \edef\LWR@tempone{%
        \LWR@htmlfileref{\BaseJobname-autofile-\arabic{LWR@htmlseqfilenumber}}%
        }%
        \edef\LWR@temptwo{%
            \LWR@htmlfileref{\BaseJobname-autofile-last}%
        }%
        \ifdefequal{\LWR@tempone}{\LWR@temptwo}{}{%
            \setcounter{LWR@tempcountone}{\value{LWR@htmlseqfilenumber}+1}%
            \LWR@subhyperrefclass{%
                \LWR@htmlrefsectionfilename{%
                    \BaseJobname-autofile-\arabic{LWR@tempcountone}%
                }%
            }{\linknextname}{linkhome}%
        }%
    }{}%
}
```

```
\end{warpHTML}
```

49 \LWRPrintStack diagnostic tool

⚠ Diagnostics tool: Prints the LaTeX nesting depth values for the stack levels. \LWR@startpars is used before printing the stack, so that \LWRPrintStack may be called from anywhere in the normal text flow.

for HTML output:

```
\begin{warpHTML}
```

\LWRPrintStack Prints the closedepth stack.

```
\newcommand*{\LWR@subprintstack}{
\LWR@closedepthone\ \LWR@closedepththwo\ \LWR@closedepththree\
\LWR@closedepthfour\ \LWR@closedepthfive\ \LWR@closedepthsix\
\LWR@closedepthseven\ \LWR@closedepthheight\ \LWR@closedepthnine\
\LWR@closedepthten\ \LWR@closedepthheleven\ \LWR@closedepthtwelve\
\LWR@closedepththirteen\ \LWR@closedepthfourteen\ \LWR@closedepthfifteen\
\LWR@closedepthsixteen\ \LWR@closedepthseventeen\ \LWR@closedepthheighteen\
\LWR@closedepthnineteen\
}

\newcommand*{\LWRPrintStack}{
\LWR@startpars
\LWR@subprintstack
}

\end{warpHTML}
```

for PRINT output:

```
\begin{warpprint}

\newcommand*{\LWRPrintStack}{}

\end{warpprint}
```

50 Closing stack levels

for HTML output:

```
\begin{warpHTML}
```

Close one nested level:

```
\newcommand*{\LWR@closeoneprevious}{%

\LWR@closeone

\LWR@popclose
}
```

\LWR@closeprevious {⟨*sectintype*⟩} Close everything up to the given depth:

```
\newcommand*{\LWR@closeprevious}[1]{
```

```
\LWR@traceinfo{%
    LWR@closeprevious to depth \csuse{LWR@depth#1}, %
    depths are \LWR@subprintstack%
}%
```

Close any pending paragraph:

```
\LWR@stoppars%
```

Close anything nested deeper than the desired depth. First close anything deeper, then at most one of the same level.

```
\whileboolexpr{test{\ifnumcomp{\LWR@closedepthone}{>}{\csuse{LWR@depth#1}}}}%
{%
    \LWR@traceinfo{LWR@closeprevious: closing out depth \LWR@closedepthone}%
    \LWR@closeoneprevious%
}%
\ifboolexpr{test{\ifnumcomp{\LWR@closedepthone}{=}{\csuse{LWR@depth#1}}}}%
{%
    \LWR@traceinfo{LWR@closeprevious: closing out depth \LWR@closedepthone}%
    \LWR@closeoneprevious%
}{}%
\LWR@traceinfo{LWR@closeprevious: done, depths are \LWR@subprintstack}%
}
```

```
\end{warpHTML}
```

51 PDF pages and styles

for HTML output:

```
\begin{warpHTML}
```

`\LWR@forcenewpage` New PDF page a before major environment.

This is used just before major environments, such as `verse`. Reduces the chance of an environment overflowing the HTML PDF output page.

```
\newcommand{\LWR@forcenewpage}{%
\LWR@traceinfo{LWR@forcenewpage}%
\ifinner\else%
    \LWR@traceinfo{LWR@forcenewpage A}%
    \LWR@stoppars%
    \LWR@traceinfo{LWR@forcenewpage B}%
    \LWR@maybe@orignewpage%
    \LWR@traceinfo{LWR@forcenewpage C}%
    \LWR@startpars%
\fi%
\LWR@traceinfo{LWR@forcenewpage done}%
}
```

`\pagestyle`, etc. are nullified for HTML output.

\pagestyle {⟨*style*⟩}

```
\renewcommand*{\pagestyle}[1]{}
```

\thispagestyle {⟨*style*⟩}

```
\renewcommand*{\thispagestyle}[1]{}
```

\markboth {⟨*left*⟩} {⟨*right*⟩}

```
\renewcommand*{\markboth}[2]{}
```

\markright {⟨*right*⟩}

```
\renewcommand*{\markright}[1]{}
```

\raggedbottom

```
\renewcommand*{\raggedbottom}{}
```

\flushbottom

```
\renewcommand*{\flushbottom}{}
```

\sloppy

```
\renewcommand*{\sloppy}{}
```

\fussy

```
\renewcommand*{\fussy}{}
```

\pagenumbering * {⟨*commands*⟩}

```
\RenewDocumentCommand{\pagenumbering}{s m}{}
\end{warpHTML}
```

52 HTML tags, spans, divs, elements

for HTML output:

```
\begin{warpHTML}
```

52.1 Mapping LaTeX sections to HTML sections

```
\newcommand*{\LWR@tagtitle}{h1}
\newcommand*{\LWR@tagtitleend}{/h1}
\newcommand*{\LWR@tagbook}{div class=\textquotedbl{}book\textquotedbl}
\newcommand*{\LWR@tagbookend}{/div}
\newcommand*{\LWR@tagpart}{h2}
\newcommand*{\LWR@tagpartend}{/h2}
\newcommand*{\LWR@tagchapter}{h3}
\newcommand*{\LWR@tagchapterend}{/h3}
\newcommand*{\LWR@tagsection}{h4}
\newcommand*{\LWR@tagsectionend}{/h4}
\newcommand*{\LWR@tagsubsection}{h5}
\newcommand*{\LWR@tagsubsectionend}{/h5}
\newcommand*{\LWR@tagsubsubsection}{h6}
\newcommand*{\LWR@tagsubsubsectionend}{/h6}
\newcommand*{\LWR@tagparagraph}{span class=\textquotedbl{}paragraph\textquotedbl}
\newcommand*{\LWR@tagparagraphend}{/span}
\newcommand*{\LWR@tagsubparagraph}{span class=\textquotedbl{}subparagraph\textquotedbl}
\newcommand*{\LWR@tagsubparagraphend}{/span}

\newcommand*{\LWR@tagregularparagraph}{p}
```

52.2 Hook while processing tags

This is used to disable special text processing while processing HTML tags. Special processing includes that done by babel-french, luavina, xevlna.

`\LWR@hook@processingtags` Disable special text processing while generating tags. Replaces `\LWR@FBcancel` in most places.

```
\newcommand*{\LWR@hook@processingtags}{}
```

52.3 Babel-French tag modifications

Adjust babel-french for HTML spaces. So far, this only works for *pdflatex* and *xelatex*.

(*Emulates or patches code by* Daniel Flipo.)

```
\providecommand*{\LWR@FBcancel}{}

\AtBeginDocument{%
```

In some circumstances, `\NoAutoSpacing` may be defined when `\frenchbsetup` is not.

```
\@ifundefined{NoAutoSpacing}%
    {}%
    {%
        \LetLtxMacro\LWR@FBcancel\NoAutoSpacing%
        \appto{\LWR@hook@processingtags}{\LWR@FBcancel}%
    }%
```

```
\@ifundefined{frenchbsetup}%
{}%
{%
    \frenchbsetup{FrenchFootnotes=false}%

%
    \renewrobustcmd*{\FBcolonspace}{%
        \begingroup%
        \LWR@hook@processingtags%
        \LWR@origampersand{}nbsp;%
        \endgroup%
    }%
    \renewrobustcmd*{\FBthinspace}{%
        \begingroup%
        \LWR@hook@processingtags%
        \LWR@origampersand\LWR@origpound{}x202f;% \,
        \endgroup%
    }%
    \renewrobustcmd*{\FBguillspace}{%
        \begingroup%
        \LWR@hook@processingtags%
        \LWR@origampersand{}nbsp;% ~,  for \og xyz \fg{}
        \endgroup%
    }%
    \DeclareDocumentCommand{\FBmedkern}{}{%
        \begingroup%
        \LWR@hook@processingtags%
        \LWR@origampersand\LWR@origpound{}x202f;% \,
        \endgroup%
    }%
    \DeclareDocumentCommand{\FBthickkern}{}{%
        \begingroup%
        \LWR@hook@processingtags%
        \LWR@origampersand{}nbsp;% ~
        \endgroup%
    }%
    \renewrobustcmd*{~}{\HTMLentity{nbsp}}% was overwritten by babel-french
    \ifFBunicode%
    \else%
        \DeclareTextSymbol{\FBtextellipsis}{LY1}{133}%
        \DeclareTextCommandDefault{\FBtextellipsis}{\textellipsis\xspace}%
    \fi%
}%
}
```

52.4 HTML output formatting

Helps format the output HTML code for human readability.

`\LWR@indentHTML` Newline and indent the output HTML code.

```
\newcommand*{\LWR@indentHTML}{%
```

```
    \LWR@orignewline\LWR@origrule{2em}{0pt}%
}
```

`\LWR@indentHTMLtwo` Newline and indent the output HTML code.

```
\newcommand*{\LWR@indentHTMLtwo}{%
    \LWR@orignewline\LWR@origrule{4em}{0pt}%
}
```

52.5 HTML tags

`\LWR@htmltagc` {⟨*tag*⟩} Break ligatures and use upright apostrophes in HTML tags.

`\protect` is in case the tag appears in TOC, LOF, LOT.

```
\newcommand*{\LWR@htmltagc}[1]{%
\LWR@traceinfo{LWR@htmltagc !\detokenize{#1}!}%
\begingroup%
\LWR@hook@processingtags%
\ifmmode\else\protect\LWR@print@normalfont\protect\LWR@origttfamily\fi%
\protect\LWR@origtextless%
\LWR@isolate{#1}%
\protect\LWR@origtextgreater%
\endgroup%
}
```

`\LWR@spanwarnformat` {⟨*object*⟩}

Warns if the given object is used inside a span.

```
\newcommand*{\LWR@spanwarnformat}[1]{%
    \ifnumcomp{\value{LWR@spandepth}}{>}{0}{%
        \PackageWarning{lwarp}{%
            A #1 is being used inside a span.\MessageBreak
            Formatting may be lost,%
        }%
    }{}%
}
```

`\LWR@spanwarninvalid` {⟨*object*⟩}

Warns if the given object is used inside a span.

```
\newcommand*{\LWR@spanwarninvalid}[1]{%
    \ifnumcomp{\value{LWR@spandepth}}{>}{0}{%
        \PackageWarning{lwarp}{%
            A #1 is being used inside a span.\MessageBreak
            This generates invalid HTML,%
        }%
    }{}%
}
```

Env LWR@nestspan Disable minipage, \parbox, and HTML s inside a .

⚠ \begin{LWR@nestspan} must follow the opening tag to allow a paragraph to start if the span is at the beginning of a new paragraph.

⚠ \end{LWR@nestspan} must follow the or a <p> may appear inside the span.

```
\newcommand*{\LWR@nestspanitem}{%
\if@newlist\else{\LWR@htmltagc{br /}}\fi%
\LWR@origitem%
}

\newenvironment*{LWR@nestspan}
{%
\LWR@traceinfo{LWR@nestspan starting}%
\ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
{%
    \LWR@traceinfo{LWR@nestspan: inside a lateximage}%
}%
{% not in a lateximage
    \LWR@traceinfo{LWR@nestspan: NOT inside a lateximage}%
    \addtocounter{LWR@spandepth}{1}%
```

Nullify several objects inside the span:

```
    \RenewDocumentEnvironment{minipage}{O{t} o O{t} m}%
        {\LWR@spanwarnformat{minipage or \protect\parbox}}%
        {}%
    \RenewDocumentEnvironment{BlockClass}{o m}%
        {\LWR@spanwarnformat{multi-paragraph object}}%
        {}%
    \RenewDocumentEnvironment{LWR@BlockClassWP}{m m D(){} m}%
        {\LWR@spanwarnformat{multi-paragraph object}}%
        {}%
    \renewcommand{\BlockClassSingle}[2]{%
        {\LWR@spanwarnformat{multi-paragraph object}}%
        ##2%
    }%
    \renewcommand{\LWR@forcenewpage}{}%
    \renewcommand{\LWR@liststart}{%
        \let\item\LWR@nestspanitem%
    }%
    \renewcommand{\LWR@listend}{\LWR@htmltagc{br /}\LWR@htmltagc{br /}}%
    \renewenvironment{quote}{\LWR@htmltagc{br /}}{\LWR@htmltagc{br /}}%
    \renewenvironment{quotation}{\LWR@htmltagc{br /}}{\LWR@htmltagc{br /}}%
}% not in a lateximage
\LWR@traceinfo{LWR@nestspan starting: done}%
}% starting env
{% ending env
\LWR@traceinfo{LWR@nestspan ending}%
\ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
{}%
{\addtocounter{LWR@spandepth}{-1}}%
\LWR@traceinfo{LWR@nestspan ending: done}%
}
```

```
6257
6258 \AfterEndEnvironment{LWR@nestspan}{\global\let\par\LWR@closeparagraph}
```

`\LWR@htmlspan` {⟨*tag*⟩} {⟨*text*⟩}

⚠ `\LWR@spandepth` is used to ensure that paragraph tags are not generated inside a span. The exact sequence of when to add and subtract the counter is important to correctly handle the paragraph tags before and after the span.

```
6259 \NewDocumentCommand{\LWR@htmlspan}{m +m}{%
6260 \LWR@ensuredoingapar%
6261 \LWR@htmltagc{#1}%
6262 \begin{LWR@nestspan}%
6263 #2%
6264 \LWR@htmltagc{/#1}%
6265 \end{LWR@nestspan}%
6266 }
```

`\LWR@htmlspanclass` [⟨*style*⟩] (⟨*ARIA role*⟩) {⟨*class*⟩} {⟨*text*⟩}

```
6267 \NewDocumentCommand{\LWR@htmlspanclass}{o D(){} m +m}{%
6268     \LWR@traceinfo{LWR@htmlspanclass |#1|#2|#3|}%
6269     \LWR@ensuredoingapar%
6270     \ifblank{#2}%
6271         {\LWR@subhtmlelementclass{span}[#1]{#3}}%
6272         {\LWR@subhtmlelementclass{span}[#1](#2){#3}}%
6273     \begin{LWR@nestspan}%
6274     #4%
6275     \LWR@htmltagc{/span}%
6276     \LWR@traceinfo{LWR@htmlspanclass done}%
6277     \end{LWR@nestspan}%
6278 }
```

`\LWR@htmltag` {⟨*tag*⟩}

Print an HTML tag: <tag>

```
6279 \newcommand*{\LWR@htmltag}[1]{%
6280 % \LWR@traceinfo{LWR@htmltagb !\detokenize{#1}!}%
6281 \LWR@htmltagc{#1}%
6282 % \LWR@traceinfo{LWR@htmltagb: done}%
6283 }
```

52.6 Block tags and comments

In the following, `\origttfamily` breaks ligatures, which may not be used for HTML codes:

`\LWR@htmlopencomment`
`\LWR@htmlclosecomment`

```
6284 \newcommand*{\LWR@htmlopencomment}{%
6285 {%
```

```
% \LWR@traceinfo{LWR@htmlopencomment}%
\begingroup%
\LWR@hook@processingtags%
\ifmmode\else\protect\LWR@print@normalfont\protect\LWR@origttfamily\fi%
\LWR@print@mbox{\LWR@origtextless{}!-\/-}%
\endgroup%
}%
}

\newcommand*{\LWR@htmlclosecomment}{%
{%
% \LWR@traceinfo{LWR@htmlclosecomment}%
\begingroup%
\LWR@hook@processingtags%
\ifmmode\else\protect\LWR@print@normalfont\protect\LWR@origttfamily\fi%
\LWR@print@mbox{-\/-\LWR@origtextgreater}%
\endgroup%
}%
}
```

`\LWR@htmlcomment` {⟨*comment*⟩}

```
\newcommand{\LWR@htmlcomment}[1]{%
\ifmmode%
\else%
    \LWR@htmlopencomment{}%
    {%
        \LWR@print@normalfont%
        \LWR@origttfamily% break ligatures
        #1%
    }%
    \LWR@htmlclosecomment{}%
\fi%
}
```

`\LWR@htmlblockcomment` {⟨*comment*⟩}

```
\newcommand{\LWR@htmlblockcomment}[1]
{\LWR@stoppars\LWR@htmlcomment{#1}\LWR@startpars}
```

`\LWR@htmlblocktag` {⟨*tag*⟩} print a stand-alone HTML tag

```
\newcommand*{\LWR@htmlblocktag}[1]{%
\LWR@stoppars%
\LWR@htmltag{#1}%
\LWR@startpars%
}
```

52.7 Div class and element class

`\LWR@subhtmlelementclass` {⟨*element*⟩} [⟨*style*⟩] (⟨*ARIA role*⟩) {⟨*class*⟩}

Factored and reused in several places.

The trailing spaces allow more places for a line break.

The use of \textquotedbl instead of " provides improved compatibility with xeCJK.

```
\NewDocumentCommand{\LWR@subhtmlelementclass}{m O{} D(){} m}{%
\LWR@traceinfo{LWR@subhtmlelementclass !#1!#2!#3!#4!}%
\ifblank{#2}%
{% empty style
    \LWR@htmltag{%
        #1%
        \ifblank{#3}{}{ role=\textquotedbl#3\textquotedbl}% spaces
        \ifblank{#4}{}{ class=\textquotedbl#4\textquotedbl}% spaces
    }%
}%
{% non-empty style
    \LWR@htmltag{%
        #1\LWR@indentHTML%
        \ifblank{#3}{}{role=\textquotedbl#3\textquotedbl\LWR@indentHTML}%
        \ifblank{#4}{}{class=\textquotedbl#4\textquotedbl\LWR@indentHTML}%
        style=\textquotedbl#2\textquotedbl\LWR@orignewline%
    }%
}%
\LWR@traceinfo{LWR@subhtmlelementclass done}%
}
```

\LWR@htmlelementclass {⟨*element*⟩} [⟨*style*⟩] {⟨*class*⟩}

```
\NewDocumentCommand{\LWR@htmlelementclass}{m o D(){} m}{%
    \LWR@stoppars%
    \LWR@forceemptyline%
    \ifblank{#3}%
        {\LWR@subhtmlelementclass{#1}[#2]{#4}}%
        {\LWR@subhtmlelementclass{#1}[#2](#3){#4}}%
    \LWR@startpars%
}
```

\LWR@htmlelementclassend {⟨*element*⟩} {⟨*class*⟩}

```
\newcommand*{\LWR@htmlelementclassend}[2]{%
    \LWR@stoppars%
    \LWR@htmltag{/#1}%
    \ifbool{HTMLDebugComments}{%
        \LWR@htmlcomment{End of #1 ‘‘#2’’}%
    }{}%
    \LWR@startpars%
}
```

\LWR@htmldivclass [⟨*style*⟩] (⟨*ARIA role*⟩) {⟨*class*⟩}

```
\NewDocumentCommand{\LWR@htmldivclass}{o D(){} m}{%
    \ifblank{#2}
```

```
        {\LWR@htmlelementclass{div}[#1]{#3}}%
        {\LWR@htmlelementclass{div}[#1](#2){#3}}%
}
```

`\LWR@htmldivclassend` {⟨*class*⟩}

```
\newcommand*{\LWR@htmldivclassend}[1]{%
    \LWR@htmlelementclassend{div}{#1}%
}
```

52.8 Single-line elements

A single-line element, without a paragraph tag for the line of text:

`\LWR@htmlelementclassline` {⟨*element*⟩} [⟨*style*⟩] {⟨*class*⟩} {⟨*text*⟩}

```
\NewDocumentCommand{\LWR@htmlelementclassline}{m o m +m}{%
\LWR@stoppars
\LWR@forceemptyline%
\LWR@subhtmlelementclass{#1}[#2]{#3}%
#4%
\LWR@htmltag{/#1}
\LWR@startpars
}
```

52.9 HTML5 semantic elements

`\LWR@htmlelement` {⟨*element*⟩}

```
\newcommand*{\LWR@htmlelement}[1]{%
\LWR@htmlblocktag{#1}
}
```

`\LWR@htmlelementend` {⟨*element*⟩}

```
\newcommand*{\LWR@htmlelementend}[1]{%
\LWR@stoppars
\LWR@htmltag{/#1}
\LWR@startpars
}

\end{warpHTML}
```

52.10 High-level block and inline classes

These are high-level commands which allow the creation of arbitrary block or inline sections which may be formatted with CSS.

Nullified versions are provided for print mode.

For other direct-formatting commands, see section 95.

Env `BlockClass` `[`⟨*style*⟩`]` `(`⟨*ARIA role*⟩`)` `{`⟨*class*⟩`}` High-level interface for classes.

Ex: `\begin{BlockClass}{class}` text `\end{BlockClass}`

for PRINT output:

```
\begin{warpprint}
\NewDocumentEnvironment{BlockClass}{o D(){} m}{}{}
\end{warpprint}
```

for HTML output:

```
\begin{warpHTML}

\NewDocumentEnvironment{LWR@print@BlockClass}{o D(){} m}{}{}%

\NewDocumentEnvironment{LWR@HTML@BlockClass}{o D(){} m}%
    {\LWR@htmldivclass[#1](#2){#3}}%
    {\LWR@htmldivclassend{#3}}

\LWR@formattedenv{BlockClass}
\end{warpHTML}
```

`\BlockClassSingle` `{`⟨*class*⟩`}` `{`⟨*text*⟩`}` A single-line , without a paragraph tag for the line of text.

for HTML & PRINT:

```
\begin{warpall}
\newcommand{\BlockClassSingle}[2]{#2}
\end{warpall}
```

for HTML output:

```
\begin{warpHTML}
\newcommand{\LWR@HTML@BlockClassSingle}[2]{%
    \LWR@htmlelementclassline{div}{#1}{#2}%
}

\LWR@formatted{BlockClassSingle}
\end{warpHTML}
```

`\InlineClass` `(`⟨*WP style*⟩`)` `[`⟨*style*⟩`]` `{`⟨*class*⟩`}` `{`⟨*text*⟩`}`

High-level interface for inline span classes.

`(`⟨*WP style*⟩`)` is css styling to add when formatting for a word processor import.

`[`⟨*style*⟩`]` is the css styling to add when not formatting for a word processor.

for PRINT output:

```
\begin{warpprint}
\NewDocumentCommand{\InlineClass}{D{(}{)}{} o m +m}{#4}%
\end{warpprint}
```

for HTML output:

```
\begin{warpHTML}
\NewDocumentCommand{\LWR@print@InlineClass}{D{(}{)}{} o m +m}{#4}%

\NewDocumentCommand{\LWR@HTML@InlineClass}{D{(}{)}{} o m +m}{%
```

```
\LWR@traceinfo{LWR@HTML@InlineClass #3}%
\ifbool{FormatWP}{%
    \LWR@traceinfo{LWR@HTML@InlineClass: FormatWP}%
    \LWR@htmlspanclass[#1]{#3}{#4}%
}{%
    \LWR@traceinfo{LWR@HTML@InlineClass: not FormatWP}%
    \LWR@htmlspanclass[#2]{#3}{#4}%
}%
\LWR@traceinfo{LWR@HTML@InlineClass: done}%
}

\LWR@formatted{InlineClass}
\end{warpHTML}
```

Env `LWR@BlockClassWP` {⟨*WPstyle*⟩} {⟨*HTMLstyle*⟩} (⟨*ARIA role*⟩) {⟨*class*⟩} Low-level interface for classes with an automatic float ID. These are often used when `\ifbool{FormatWP}`.

The use of `\textquotedbl` instead of " provides improved compatibility with XeCJK.

for PRINT output:

```
\begin{warpprint}
\NewDocumentEnvironment{LWR@BlockClassWP}{m m D(){} m}{}{}
\end{warpprint}
```

for HTML output:

```
\begin{warpHTML}
\NewDocumentEnvironment{LWR@print@LWR@BlockClassWP}{m m D(){} m}{}{}%

\NewDocumentEnvironment{LWR@HTML@LWR@BlockClassWP}{m m D(){} m}%
{%
\LWR@stoppars%
\ifbool{FormatWP}%
{%
    \addtocounter{LWR@thisautoidWP}{1}%

    \LWR@htmltag{%
        div class=\textquotedbl#4\textquotedbl\ % space
        id=\textquotedbl%
            \LWR@print@mbox{autoidWP-\arabic{LWR@thisautoidWP}}%
        \textquotedbl%
        \ifblank{#3}{}{ role=\textquotedbl#3\textquotedbl}%
        \ifblank{#1}{}{ style=\textquotedbl#1\textquotedbl}%
    }%
}% FormatWP
{% not FormatWP
    \LWR@htmltag{%
        div class=\textquotedbl#4\textquotedbl%
        \ifblank{#3}{}{ role=\textquotedbl#3\textquotedbl}%
        \ifblank{#2}{}{ style=\textquotedbl#2\textquotedbl}%
    }%
}% not FormatWP
\LWR@startpars%
}
{\LWR@htmldivclassend{#4}}

\LWR@formattedenv{LWR@BlockClassWP}
\end{warpHTML}
```

52.11 Closing HTML tags

for HTML output:

```
\begin{warpHTML}
```

Sections H1, H2, etc. do not need a closing HTML tag, but we add a comment for readability:

```
\newcommand*{\LWR@printclosebook}
    {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing book}}{}}
\newcommand*{\LWR@printclosepart}
    {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing part}}{}}
\newcommand*{\LWR@printclosechapter}
    {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing chapter}}{}}
\newcommand*{\LWR@printclosesection}
    {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing section}}{}}
\newcommand*{\LWR@printclosesubsection}
    {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing subsection}}{}}
\newcommand*{\LWR@printclosesubsubsection}
    {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing subsubsection}}{}}
\newcommand*{\LWR@printcloseparagraph}
    {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing paragraph}}{}}
\newcommand*{\LWR@printclosesubparagraph}
    {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing subparagraph}}{}}
```

Lists require closing HTML tags:

```
\newcommand*{\LWR@printcloselistitem}
    {\LWR@htmltag{/li}}
\newcommand*{\LWR@printclosedescitem}
    {\LWR@htmltag{/dd}}
\newcommand*{\LWR@printcloseitemize}
    {\LWR@htmltag{/ul}}
\newcommand*{\LWR@printcloseenumerate}
    {\LWR@htmltag{/ol}}
\newcommand*{\LWR@printclosedescription}
    {\LWR@htmltag{/dl}}

\end{warpHTML}
```

53 Paragraph handling

These commands generate the HTML paragraph tags when allowed and required.

Paragraph tags are or are not allowed depending on many conditions. Section 54 has high-level commands which allow paragraph-tag generation to start/stop. Even when allowed (`\LWR@doingstartpars`), tags are not generated until a LaTeX paragraph is being used (`\LWR@doingapar`). `LWR@lateximagedepth` is used to prevent nesting tags inside a `lateximage`. `LWR@spandepth` is used to prevent nesting paragraph tags inside a paragraph, which became important inside `\fbox` commands and other spans.

for HTML output:

```
\begin{warpHTML}
```

Ctr `LWR@spandepth` Do not create paragraph tags inside of an HTML span.

```
\newcounter{LWR@spandepth}
\setcounter{LWR@spandepth}{0}
```

Bool LWR@doingstartpars Tells whether paragraphs may be generated.

```
\newbool{LWR@doingstartpars}
\boolfalse{LWR@doingstartpars}
```

Bool LWR@doingapar Tells whether have actually generated and are currently processing paragraph text.

```
\newbool{LWR@doingapar}
\global\boolfalse{LWR@doingapar}
```

\LWR@ensuredoingapar If are about to print something visible, and if allowed to start a new paragraph, ensure that are LWR@doingapar, so that paragraph tags are placed:

```
\newcommand*{\LWR@ensuredoingapar}{%
\ifbool{LWR@doingstartpars}%
{\global\booltrue{LWR@doingapar}}%
{}%
}
```

\PN@parnotes@auto Redefined by parnotes to print paragraph notes at the end of each paragraph.

```
\def\PN@parnotes@auto{}%
```

\LWR@openparagraph

```
\newcommand*{\LWR@openparagraph}
{%
```

See if paragraph handling is enabled:

```
\ifbool{LWR@doingstartpars}%
{% handling pars
```

See if have already started a lateximage or a . If so, do not generate nested paragraph tags.

```
    \ifboolexpr{
        test {\ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}} or
        test {\ifnumcomp{\value{LWR@spandepth}}{>}{0}}
    }% nested par tags?
```

If so: Do nothing if already started a lateximage page. Cannot nest a lateximage. Also do nothing if already inside a . Do not nest paragraph tags inside a .

```
    {}% no nested par tags
```

Else: No lateximage or has been started yet, so it's OK to generate paragraph tags.

```
    {% yes nest par tags
```

If parnotes is used, paragraph notes are inserted before starting the next paragraph:

```
        \PN@parnotes@auto%
```

The opening paragraph tag:

```
        \LWR@htmltagc{\LWR@tagregularparagraph}\LWR@orignewline%
```

Now have started a paragraph.

```
        \global\booltrue{LWR@doingapar}%
```

At the endof each paragraph, generate closing tag and do regular /par stuff. (Attempting to use the everyhook cr hook for \LWR@closeparagraph does not work well.)

```
        \let\par\LWR@closeparagraph%
    }% end of yes nest par tags
}% end of handling pars
{}% not handling pars
}
```

\LWR@closeparagraph@br Add an HTML break if in a span, and not in a lateximage, and not in tabular metadata. Factored from \LWR@closeparagraph.

```
\newcommand*{\LWR@closeparagraph@br}
{%
    \ifboolexpr{
        test {\ifnumcomp{\value{LWR@spandepth}}{>}{0}} and
        test {\ifnumcomp{\value{LWR@lateximagedepth}}{=}{0}} and
        not bool {LWR@intabularmetadata}
    }%
        {\unskip\LWR@htmltagc{br /}}%
        {}%
}
```

\LWR@closeparagraph

```
\newcommand*{\LWR@closeparagraph}
{%
% \LWR@traceinfo{LWR@closeparagraph}%
```

See if paragraph handling is enabled:

```
\ifbool{LWR@doingapar}%
```

If currently in paragraph mode:

```
{% handling pars
```

See if already started a lateximage or a :

```
    \ifboolexpr{
        test {\ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}} or
```

```
        test {\ifnumcomp{\value{LWR@spandepth}}{>}{0}}
    }%
```

Add a parbreak if in a span, not in a lateximage, and not in table metadata.

```
    {% no nested par tags
        \LWR@closeparagraph@br%
    }% no nested par tags
```

If have not already started a `lateximage` or a :

```
    {% yes nest par tags
```

Print a closing tag and some extra vertical space.

(The fill seems to be required to force the caption package to create flush left caption text in the HTML.)

```
        \@hspacer{\fill}% \hspace*{\fill}
        \leavevmode\LWR@orignewline%
        \LWR@htmltagc{/\LWR@tagregularparagraph}%
```

No longer doing a paragraph:

```
        \global\boolfalse{LWR@doingapar}%
```

Disable the special `minipage` & `\hspace` interaction until a new minipage is found:

```
        \global\boolfalse{LWR@minipagethispar}%
```

If parnotes is used, paragraph notes are inserted after ending the previous paragraph:

```
        \PN@parnotes@auto%
    }% end of yes nest par tags
}% end of handling pars
```

Add a parbreak if in a span, not in a lateximage, and not in table metadata.

```
{% not handling pars
    \LWR@closeparagraph@br%
}% not handling pars
```

In most cases, finish with a LaTeX `\par`, but in the case of paragraphs between lines in a tabular fetch the next token instead:

```
\ifboolexpr{%
    not bool {LWR@doingapar} and
    test {\ifnumcomp{\value{LWR@tabulardepth}}{>}{0}} and
    test {
        \ifnumcomp{\value{LWR@tabulardepth}}{=}{\value{LWR@tabularpardepth}}
    } and
    bool {LWR@intabularmetadata} and
    not bool {LWR@tableparcell} and
    test {\ifnumcomp{\value{LWR@lateximagedepth}}{=}{0}}
```

```
}%
{%
    \LWR@getmynexttoken%
}{%
    \LWR@origpar%
}%
}
```

```
\end{warpHTML}
```

54 Paragraph start/stop handling

These commands allow/disallow the generation of HTML paragraph tags.

Section 53 has the commands which actually generate the tags.

The everyhook package is used to generate the opening paragraph tags. The closing tags are generated by \par.

for HTML output:

```
\begin{warpHTML}
```

\LWR@startpars

Begin handling HTML paragraphs. This allows an HTML paragraph to start, but one has not yet begun.

```
\newcommand*{\LWR@startpars}%
{%
% \LWR@traceinfo{LWR@startpars}%
```

Ignore if inside a lateximage or :

```
\ifboolexpr{
    test {\ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}} or
    test {\ifnumcomp{\value{LWR@spandepth}}{>}{0}}
}%
{}%
{%
```

See if currently handling HTML paragraphs:

```
    \ifbool{LWR@doingstartpars}%
```

If already in paragraph mode, do nothing.

```
    {}%
```

If not currently in paragraph mode:

```
    {%
```

At the start of each paragraph, generate an opening tag:

```
        \PushPreHook{par}{\LWR@openparagraph}%
```

At the end of each paragraph, generate closing tag then do regular /par actions:

```
        \let\par\LWR@closeparagraph

    }% an intentionally blank line
```

Are now handling paragraphs, but have not yet actually started one:

```
    \global\setbool{LWR@doingstartpars}{true}%
```

No <par> tag yet to undo:

```
    \global\boolfalse{LWR@doingapar}%
}% nestspan
% \LWR@traceinfo{LWR@startpars: done}%
}
```

\LWR@stoppars Stop handling HTML paragraphs. Any currently open HTML paragraph is closed, and no more will be opened.

```
\newcommand*{\LWR@stoppars}%
{%
```

Ignore if inside a lateximage or :

```
\ifboolexpr{
    test {\ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}} or
    test {\ifnumcomp{\value{LWR@spandepth}}{>}{0}}
}%
{}%
{%
```

See if currently handling HTML paragraphs:

```
    \ifbool{LWR@doingapar}%
```

if currently in an HTML paragraph:

```
    {%
```

Print a closing tag:

```
        \leavevmode\LWR@orignewline%
        \LWR@htmltagc{/\LWR@tagregularparagraph}%
        \LWR@orignewline%
```

No longer have an open HTML paragraph:

```
        \global\boolfalse{LWR@doingapar}%
```

Disable the special minipage & \hspace interaction until a new minipage is found:

```
        \global\boolfalse{LWR@minipagethispar}
    }%
```

If was not in an HTML paragraph:

```
    {}%
```

See if currently allowing HTML paragraphs:

```
    \ifbool{LWR@doingstartpars}%
```

If so: clear the par hook to no longer catch paragraphs:

```
        {\ClearPreHook{par}}%
```

Else: Do nothing:

```
        {}%
```

No longer in paragraph mode:

```
    \global\setbool{LWR@doingstartpars}{false}%
```

No <p> tag to undo:

```
    \global\boolfalse{LWR@doingapar}%
}% nestspan
}

\end{warpHTML}
```

55 Indentfirst

Pkg indentfirst indentfirst redefines `\@afterindentfalse` to be `\@afterindenttrue`. This is reversed `\AtBeginDocument` here.

for HTML output:

```
\begin{warpHTML}

\AtBeginDocument{
    \def\@afterindentfalse{\let\if@afterindent\iffalse}
    \@afterindentfalse
}
\let\LWR@afterindent@syntaxhighlight\fi% syntax highlighting

\end{warpHTML}
```

56 Page headers and footers

for HTML & PRINT:

```
\begin{warpall}
```

In the following, catcode is manually changed back and forth without groups, since new macros are being defined which must not be contained within the groups.

```
\newcommand{\LWR@firstpagetop}{} % for the home page alone
\newcommand{\LWR@firstpagebottom}{} % for the home page alone
\newcommand{\LWR@pagetop}{} % for all other pages
\newcommand{\LWR@pagebottom}{}
```

`\HTMLFirstPageTop` {⟨*text and logos*⟩}

```
\newcommand{\HTMLFirstPageTop}[1]{%
    \renewcommand{\LWR@firstpagetop}{#1}%
}
```

`\HTMLFirstPageBottom` {⟨*text and logos*⟩}

```
\newcommand{\HTMLFirstPageBottom}[1]{%
    \renewcommand{\LWR@firstpagebottom}{#1}%
}
```

`\HTMLPageTop` {⟨*text and logos*⟩}

```
\newcommand{\HTMLPageTop}[1]{%
    \renewcommand{\LWR@pagetop}{#1}%
}
```

`\HTMLPageBottom` {⟨*text and logos*⟩}

```
\newcommand{\HTMLPageBottom}[1]{%
    \renewcommand{\LWR@pagebottom}{#1}%
}

\end{warpall}
```

57 CSS

for HTML output:

```
\begin{warpHTML}
```

`\LWR@currentcss` The CSS filename to use. This may be changed mid-document using `\CSSFilename`, allowing different CSS files to be used for different sections of the document.

```
\newcommand*{\LWR@currentcss}{lwarp.css}
```

`\CSSFilename` {⟨*new-css-filename.css*⟩} Assigns the CSS file to be used by the following HTML pages.

```
\newcommand*{\CSSFilename}[1]{%
\renewcommand*{\LWR@currentcss}{#1}%
```

```
\@onelevel@sanitize\LWR@currentcss%
}

\end{warpHTML}
```

for PRINT output:

```
\begin{warpprint}
\newcommand*{\CSSFilename}[1]{}
\end{warpprint}
```

58 MathJax script

for HTML output:

```
\begin{warpHTML}
```

Default: `lwarp_mathjax.txt`

`\LWR@mathjaxfilename` The MathJax script filename to use. This file is copied into the head of each HTML page. This may be changed mid-document using `\MathJaxFilename`, allowing the use of a custom MathJax script, such as for a local repository, or different MathJax script files to be used for different sections of the document.

```
\newcommand*{\LWR@mathjaxfilename}{lwarp_mathjax.txt}
```

`\MathJaxFilename` {⟨*filename*⟩} Assigns the MathJax script file to be used by the following HTML pages.

```
\newcommand*{\MathJaxFilename}[1]{%
    \renewcommand*{\LWR@mathjaxfilename}{#1}%
    \@onelevel@sanitize\LWR@mathjaxfilename%
}

\end{warpHTML}
```

for PRINT output:

```
\begin{warpprint}
\newcommand*{\MathJaxFilename}[1]{}
\end{warpprint}
```

59 Title, HTML meta author, HTML meta description

for HTML output:

```
\begin{warpHTML}
```

`\title` {⟨*title*⟩} Modified to remember `\thetitle`, which is used to set the HTML page titles.

```
\let\LWR@origtitle\title

\renewcommand*{\title}[1]{%
    \LWR@origtitle{#1}%
    \begingroup%
        \renewcommand{\thanks}[1]{}%
        \protected@xdef\thetitle{#1}%
    \endgroup%
}
```

```
\end{warpHTML}
```

for HTML & PRINT:

```
\begin{warpall}
```

`\HTMLTitle` {⟨*Titlename*⟩} The Title to place into an HTML meta tag. The default is to use the document `\title`'s setting.

```
\providecommand{\thetitle}{\BaseJobname}

\newcommand{\theHTMLTitle}{\thetitle}

\newcommand{\HTMLTitle}[1]{\renewcommand{\theHTMLTitle}{#1}}
```

`\HTMLAuthor` {⟨*authorname*⟩} The author to place into an HTML meta tag. If none given, the default is `\theauthor`, which is empty unless the titling package is used.

```
\providecommand{\theauthor}{}

\newcommand{\theHTMLAuthor}{\theauthor}

\newcommand{\HTMLAuthor}[1]{\renewcommand{\theHTMLAuthor}{#1}}
```

This is placed inside an HTML meta tag at the start of each file. This may be changed mid-document using `\HTMLDescription`, allowing different HTML descriptions to be used for different sections of the document.

⚠ HTML author Do not use double quotes, and do not exceed 150 characters.

`\HTMLDescription` {⟨*New HTML meta description.*⟩} Assigns the HTML file's description meta tag.

```
\newcommand{\LWR@currentHTMLDescription}{}

\newcommand{\HTMLDescription}[1]{%
\renewcommand{\LWR@currentHTMLDescription}{#1}
}

\end{warpall}
```

60 Footnotes

lwarp uses native LaTeX footnote code, although with its own `\box` to avoid the LaTeX output routine. The usual functions mostly work as-is.

footnote numbering To have footnote numbers reset each time footnotes are printed:

```
\setcounter{footnoteReset}{1}
```

For bigfoot, manyfoot, or perpage:

```
\MakePerPage{footnoteX}
— or —
\MakeSortedPerPage{footnoteX}
```

The footnotes are reset when they are printed, according to section level as set by `FootnoteDepth`, which is not necessarily by HTML page. This is recommended for `\alph`, `\Alph`, or `\fnsymbol` footnotes, due to the limited number of symbols which are available.

MathJax

Also for MathJax, `\footnotename` is used for a `\footnotemark` if the actual footnote number is not known. To redefine it, provide it before loading lwarp:

```
\providecommand{\footnotename}{something}
\usepackage{lwarp}
```

Similar for sidenotes. For endnotes:

```
\def\endnotename{something}% \def allows name to start with "end"
```

For the pagenote package, there is no `\pagenotename` to define, since there is no `\pagenotemark` command.

footmisc

The footmisc `stable` option is emulated by lwarp.

⚠ sectioning commands

When using footnotes in sectioning commands, to generate consistent results between print and HTML, use the footmisc package with the `stable` option, provide a short TOC entry, and `\protect` the `\footnote`:

```
\usepackage[stable]{footmisc}
. . .
\subsection[Subsection Name]
    {Subsection Name\protect\footnote{A footnote.}}
```

memoir with footmisc

⚠ memoir

If using memoir class, with which lwarp preloads footmisc, the `stable` option must be declared before lwarp is loaded:

```
\PassOptionsToPackage{stable}{footmisc}
\usepackage{lwarp}
. . .
```

Do not use a starred sectioning command. As an alternative, it may be possible to adjust `\secnumdepth` instead.

Several kinds of footnotes are used: in a regular page, in a minipage, or as thanks in the titlepage. Each of these is handle differently.

60.1 Regular page footnotes

In HTML documents, footnotes are placed at the bottom of the web page or the section, depending on `FootnoteDepth`, using the LaTeX box `\LWR@footnotebox`. Using this instead of the original `\footins` box avoids having footnotes be printed by the output routine, since footnotes should be printed per HTML page instead of per PDF page.

See section 60.4 for the implementation.

60.2 Minipage footnotes

See section 60.5 for how minipage footnotes are gathered. See section 94.4 for how minipage footnotes are placed into the document.

60.3 Titlepage thanks

See section 69.7 for titlepage footnotes.

60.4 Regular page footnote implementation

for HTML & PRINT:

```
6696 \begin{warpall}
```

Ctr `FootnoteDepth`
Default: 3

Determines how deeply to place footnotes in the HTML files, similar to `tocdepth`. The default of 3 places footnotes before each `\subsubsection` or higher. See table 12 for a table of LaTeX section headings.

```
6697 \newcounter{FootnoteDepth}
6698 \setcounter{FootnoteDepth}{3}
```

Ctr `footnoteReset`
Default: `0`

If non-zero, the `footnote` counter is reset to this value each time the footnotes are printed, as controlled by `FootnoteDepth`. For the manyfoot and bigfoot packages, additional counters such as `footnote<suffix>Reset` will be defined as well. These counters may be set non-zero by the user, and are also set if the perpage's `\MakePerPage` or `\MakeSortedPerPage` macros are used for the `footnote` or `footnote<suffix>` counters.

(The name is not capitalized because it is made from the counter's name with "Reset" appended.)

```
6699 \newcounter{footnoteReset}
6700 \setcounter{footnoteReset}{0}
```

```
6701 \end{warpall}
```

for HTML output:

```
6702 \begin{warpHTML}
```

`\LWR@footnotebox`

Patch LaTeX footnotes to use a new `\box` instead of an insert for lwarp footnotes. This avoids having the original `\footins` appear at the bottom of a `lateximage`, which is on its own new page.

```
6703 \newbox\LWR@footnotebox
```

Much of the following has unneeded print-mode formatting removed.

`\@makefntext` {⟨*text*⟩}

```
6704 \long\def\@makefntext#1{\textsuperscript{\@thefnmark}~#1}
```

\@makefnmark

```
\def\@makefnmark{%
    \textsuperscript{\@thefnmark}%
}
```

Footnotes may be in regular text, in which case paragraphs are tagged, or in a table data cell or lateximage, in which case paragraph tags must be added manually.

In a lateximage during HTML output, the lateximage is placed inside a print-mode minipage, but the footnotes are broken out by:

```
\def\@mpfn{footnote}
\def\thempfn{\thefootnote}
\let\@footnotetext\LWR@footnotetext
```

\LWR@@footnotetext {⟨*text*⟩} {⟨*footnote box name*⟩}

Factored to allow multiple footnote boxes for manyfoot.

```
\long\def\LWR@@footnotetext#1#2{%
\LWR@traceinfo{LWR@footnotetext}%
```

Perhaps generate an autopage in the text to link a citation backreference closer to its usage.

```
\LWR@newautopagelabel{page}%
```

Locally disable auto page labels inside the footnote text. Footnotes are accumulated in the current page before finally being placed in a potentially later page, so the aotopages would be incorrect.

```
\begingroup%
\let\LWR@newautopagelabel\LWR@null@newautopagelabel%
```

Take the existing footnote box and add the new content:

```
\global\setbox\csname #2\endcsname=\vbox{%
    \unvbox\csname #2\endcsname%
```

Remember the footnote number for \ref:

```
    \protected@edef\@currentlabel{%
        \csname p@footnote\endcsname\@thefnmark%
    }% @currentlabel
```

Open a group:

```
    \color@begingroup%
```

Disable CJK xpinyin while generating footnotes.

```
    \LWR@disablepinyin%
```

Use HTML superscripts in the footnote even when the main text is inside a `lateximage`, because the footnote will be in HTML:

```
    \renewrobustcmd{\textsuperscript}[1]{\LWR@htmlspan{sup}{##1}}%
```

Use paragraph tags if in a tabular data cell or a `lateximage`:

```
    \ifthenelse{%
        \boolean{LWR@doingstartpars} \AND%
        \cnttest{\value{LWR@lateximagedepth}}{=}{0}%
    }%
        {}%
        {\LWR@htmltagc{\LWR@tagregularparagraph}\LWR@orignewline}%
```

Append the footnote to the list:

```
    \@makefntext{#1}%
```

Closing paragraph tag:

```
    \ifthenelse{%
        \boolean{LWR@doingstartpars} \AND%
        \cnttest{\value{LWR@lateximagedepth}}{=}{0}%
    }%
        {\par}%
        {%
            \LWR@htmltagc{/\LWR@tagregularparagraph}%
            \LWR@orignewline%
        }%
```

Close the group:

```
    \color@endgroup%
}% vbox
\endgroup%
```

Paragraph handling:

```
\LWR@ensuredoingapar%
}%
```

`\LWR@footnotetext` {⟨*text*⟩}

```
\long\def\LWR@footnotetext#1{\LWR@@footnotetext{#1}{LWR@footnotebox}}%
```

`\@footnotetext` {⟨*text*⟩}

```
\LetLtxMacro\@footnotetext\LWR@footnotetext
```

60.5 Minipage footnote implementation

Patch LaTeX minipage footnotes to use a new \box instead of an insert for lwarp minipage footnotes. This avoids having the original \@mpfootins appear at the bottom of a lateximage, which is on its own new page.

```
\newbox\LWR@mpfootnotes
```

\@mpfootnotetext {⟨*text*⟩}

```
\long\def\@mpfootnotetext#1{%
\LWR@traceinfo{@mpfootnotetext}%
\global\setbox\LWR@mpfootnotes\vbox{%
    \unvbox\LWR@mpfootnotes%
    \reset@font\footnotesize%
    \hsize\columnwidth%
    \@parboxrestore%
    \protected@edef\@currentlabel%
        {\csname p@mpfootnote\endcsname\@thefnmark}%
    \color@begingroup%
```

Use paragraph tags if in a tabular data cell or a lateximage:

```
    \ifthenelse{%
        \boolean{LWR@doingstartpars} \AND%
        \cnttest{\value{LWR@lateximagedepth}}{=}{0}%
    }%
        {}%
        {\LWR@htmltagc{\LWR@tagregularparagraph}\LWR@orignewline}%

    \@makefntext{%
        \ignorespaces#1%
    }%
```

Don't add the closing paragraph tag if are inside a lateximage:

```
    \ifthenelse{\cnttest{\value{LWR@lateximagedepth}}{>}{0}}%
        {}%
        {%
            \leavevmode\LWR@orignewline%
            \LWR@htmltagc{/\LWR@tagregularparagraph}%
            \LWR@origpar%
        }%
    \color@endgroup%
}% vbox
```

Paragraph handling:

```
\LWR@ensuredoingapar%
\LWR@traceinfo{@mpfootnotetext: done}%
}
```

\thempfootnote Redefined to remove the \itshape, which caused an obscure compiling error in some situations.

```
\AtBeginDocument{
    \def\thempfootnote{\@alph\c@mpfootnote}
}
```

60.6 Printing pending footnotes

\LWR@@printpendingfootnotes {⟨*footnote counter name*⟩}

```
\newcommand*{\LWR@@printpendingfootnotes}[1]{%
\expandafter\ifvoid\csname LWR@#1box\endcsname\else
    \LWR@forcenewpage
    \begin{BlockClass}(note){footnotes}%
```

Create a new autopage in case citation back references occur inside the footnotes:

```
    \LWR@newautopagelabel{page}%

    \null
    \unvbox\csuse{LWR@#1box}
    \setbox\csuse{LWR@#1box}=\vbox{}
    \end{BlockClass}
    \ifltxcounter{#1Reset}{%
        \ifnumgreater{\value{#1Reset}}{0}{%
            \setcounter{#1}{\value{#1Reset}}%
            \addtocounter{#1}{-1}%
        }{}%
    }{}%
\fi
}
```

\LWR@printpendingfootnotes Enclose the footnotes in a class, print, then clear. For manynotes, new footnotes may be added via \appto.

```
\newcommand*{\LWR@printpendingfootnotes}{%
    \LWR@@printpendingfootnotes{footnote}%
}
```

\LWR@maybeprintpendingfootnotes {⟨*depth*⟩} Used to print footnotes before sections only if formatting for an EPUB or word processor:

```
\newcommand*{\LWR@maybeprintpendingfootnotes}[1]{%
\ifboolexpr{
    not test{\ifnumcomp{#1}{>}{\value{FootnoteDepth}}} or
    bool{FormatEPUB} or
    bool{FormatWP}
}%
{\LWR@printpendingfootnotes}%
{}%
}
```

\LWR@printpendingmpfootnotes Enclose the minipage footnotes in a class, print, then clear.

```
\newcommand*{\LWR@printpendingmpfootnotes}{%
\ifvoid\LWR@mpfootnotes\else
    \LWR@forcenewpage
    \begin{BlockClass}(note){footnotes}%
    \null
    \unvbox\LWR@mpfootnotes
    \setbox\LWR@mpfootnotes=\vbox{}
    \end{BlockClass}
\fi
}
```

```
\end{warpHTML}
```

61 Marginpars

\marginpar [⟨*left*⟩] {⟨*right*⟩} \marginpar may contains paragraphs, but in order to remain inline with the surrounding text lwarp nullifies block-related macros inside the \marginpar. Paragraph breaks are converted to <br /> tags.

\marginparBlock [⟨*left*⟩] {⟨*right*⟩} To include block-related macros, use \marginparBlock, which takes the same arguments but creates a instead of a . A line break will occur in the text where the \marginBlock occurs.

for HTML output:

```
\begin{warpHTML}
```

\marginpar [⟨*left*⟩] {⟨*right*⟩}

```
\renewcommand{\marginpar}[2][]{%
\ifbool{FormatWP}%
{%
\begin{LWR@BlockClassWP}{width:2in; float:right; margin:10pt}{}(note){marginblock}%
#2
\end{LWR@BlockClassWP}%
}%
{%
    \LWR@htmlspanclass(note){marginpar}{#2}%
}%
}
```

\marginparBlock [⟨*left*⟩] {⟨*right*⟩}

For use when the marginpar will be more than one paragraph, and/or contains more than simple text.

HTML version.

```
\newcommand{\marginparBlock}[2][]{%
\LWR@stoppars%
\ifbool{FormatWP}%
```

```
{%
  \begin{LWR@BlockClassWP}{width:2in; float:right; margin:10pt}{}(note){marginblock}%
    #2
    \end{LWR@BlockClassWP}
}{%
  \begin{BlockClass}[width:2in; float:right; margin:10pt](note){marginparblock}%
    #2
    \end{BlockClass}
}%
\LWR@startpars%
}
```

\reversemarginpar

```
\renewcommand*{\reversemarginpar}{}
```

\normalmarginpar

```
\renewcommand*{\normalmarginpar}{}
```

```
\end{warpHTML}
```

for PRINT output:

```
\begin{warpprint}
```

\marginparBlock `[`⟨*left*⟩`]` `{`⟨*right*⟩`}`

For use when the marginpar will be more than one paragraph, and/or contains more than simple text.

Print version.

```
\LetLtxMacro\marginparBlock\marginpar
```

```
\end{warpprint}
```

62 Tracking internal cross references

Cross references are generated using the PDF file's page number during LaTeX compilation. Internal labels are generated which include these page numbers in the label.

File *_html.aux

A new entry in the *_html.aux file is used to help cross-references:

```
\newlabel{autopage-<nnn>}{{<x>}{<y>}}
```

Ctr LWR@currentautosecpage

Records the page number when the section was created. (If a math expression is included in the section name, and SVG math is used, the corresponding `latexmage` will cause the page number to change by the time the following autosec label is created, thus the initial page number is recorded here.) `LWR@currentautosecfloatpage` is updated more often than `LWR@currentautosecpage`.

```
\newcounter{LWR@currentautosecpage}
\setcounter{LWR@currentautosecpage}{1}
```

Ctr LWR@currentautosecfloatpage

The HTML output's PDF page number at the start of a new HTML file, section, or float. Updated more often than LWR@currentautosecpage, such as when a new float occurs. Used only for table of contents, list of figures, list of tables, but not for general cross references such as \label, citation backlinks, etc.

\LWRsetnextfloat is written with this and the autoid by the modified \addcontentsline just before each float's entry.

```
\newcounter{LWR@currentautosecfloatpage}
\setcounter{LWR@currentautosecfloatpage}{1}
```

Ctr LWR@previousautopagelabel

Remembers which autopage label was most recently generated. Used to avoid duplicates.

```
\newcounter{LWR@previousautopagelabel}
\setcounter{LWR@previousautopagelabel}{-1}
```

\LWR@newautopagelabel {⟨*pagenumber counter*⟩}

\BaseJobname is added to the label in case xr or xr-hyper are used.

```
\newcommand*{\LWR@newautopagelabel}[1]{%
```

No action if this autopage label has already been defined:

```
\ifnumequal{\value{LWR@previousautopagelabel}}{\value{page}}%
    {}%
```

If the PDF page has changed, create a label using the desired counter.

If the counter is LWR@currentautosecpage, that was the page number when the section generation began, but the current PDF page may be different by now if the section name had an SVG image, such as SVG math. To allow the cross-reference to point just after the section heading, the label must be made after the section heading is complete, which may have generated a new PDF page. Thus, the label is made with the given counter, which may be the PDF page number where the section heading began, then if the PDF page number has changed, another label is made for the current page number.

```
    {%
        \label{\BaseJobname-autopage-\csuse{the#1}}%
```

If there are intervening pages, such as an SVG image, define another label for the new page:

```
        \ifnumequal{\value{#1}}{\value{page}}%
            {}%
            {\label{\BaseJobname-autopage-\csuse{thepage}}}%
```

Remember the latest autopage label:

```
        \setcounter{LWR@previousautopagelabel}{\value{page}}%
    }%
}
```

\LWR@null@newautopagelabel {⟨*pagenumber counter*⟩}

Inside a footnote, the page numbers will be incorrect, so this is nullified.

```
\newcommand*{\LWR@null@newautopagelabel}[1]{}
```

63 Splitting HTML files

- Files are split according to FileDepth and CombineHigherDepths.
- Filenames are sanitized by \LWR@filenamenoblanks.
- \LWR@newhtmlfile finishes an HTML page, adds a comment to tell where and how to split the file, then starts a new HTML page.

for HTML & PRINT:

```
\begin{warpall}
```

Ctr FileDepth {⟨*section depth*⟩} determines how deeply to break into new HTML files, similar to tocdepth. The default of -5 produces one large HTML file.

```
\newcounter{FileDepth}
\setcounter{FileDepth}{-5}
```

Bool CombineHigherDepths Combile higher-level sections together into one file?

```
\newbool{CombineHigherDepths}
\booltrue{CombineHigherDepths}
```

\FilenameLimit Maximum length of the generated filenames.

```
\newcommand*{\FilenameLimit}{80}
```

```
\end{warpall}
```

for HTML output:

```
\begin{warpHTML}
```

\LWR@thisfilename The currently-active filename or number. At first, this is the homepage.

```
\AtBeginDocument{
\ifbool{FileSectionNames}%
    {\newcommand*{\LWR@thisfilename}{\HomeHTMLFilename}}
    {\newcommand*{\LWR@thisfilename}{0}}
}
```

\LWR@thisnewfilename The filename being sanitized.

```
\newcommand*{\LWR@thisnewfilename}{}
```

\LWR@simplifyname * {⟨*expression*⟩} Simplify \LWR@thisnewfilename.

If starred, detokenizes the input expression. If found, changes the expression to a single detokenized dash.

```
\NewDocumentCommand{\LWR@simplifyname}{s m}{%
\IfBooleanTF{#1}{%
    \StrSubstitute{\LWR@thisnewfilename}%
        {\detokenize{#2}}%
        {\detokenize{-}}[\LWR@thisnewfilename]%
}{%
    \StrSubstitute{\LWR@thisnewfilename}%
        {#2}%
        {\detokenize{-}}[\LWR@thisnewfilename]%
}
}
```

\LWR@simplifycustom User-defined filename simplifications. Redefine with \newcommand.

```
\newcommand*{\LWR@simplifycustom}{}
```

\FilenameSimplify * {⟨*phrase*⟩} Assign a user-defined filename simplification. Appends to \LWR@simplifycustom.

```
\NewDocumentCommand{\FilenameSimplify}{s m}{%
\IfBooleanTF{#1}{%
    \appto{\LWR@simplifycustom}{%
        \LWR@simplifyname*{#2}%
    }%
}{%
    \appto{\LWR@simplifycustom}{%
        \LWR@simplifyname{#2}%
    }%
}%
}
```

\LWR@avoiddupfilenames Instructions for how to avoid duplicate filenames. This is used in a warning in \LWR@filenamenoblanks, and in an error in \LWR@newhtmlfile.

```
\newcommand*{\LWR@avoiddupfilenames}{%
    To avoid duplicate filenames, use the optional\MessageBreak
    short Table of Contents entry:\MessageBreak
    \space\space\protect\section[Unique name, no math]{Name with math}%
        \MessageBreak
    or use \protect\texorpdfstring, from the hyperref package:\MessageBreak
    \space\space%
        \protect\section{\MessageBreak
            \space\space\space\space\protect\texorpdfstring\MessageBreak
                \space\space\space\space\space\space%
                {Name with math}{Unique name, no math}\MessageBreak
        \space\space}
}
```

\LWR@filenamenoblanks {⟨*filename*⟩}

Convert blanks into dashes, removes short words, store result in \LWR@thisfilename.

Also see \LWR@nullfonts for nullified macros.

```
\newcommand*{\LWR@filenamenoblanks}[1]{%
\begingroup
```

Locally temporarily disable direct-formatting commands, not used in filenames:

```
\LWR@nullfonts%
\renewcommand*{\LWR@htmltagc}[1]{}%

\edef\LWR@thisnewfilename{#1}%
```

Replaces common macros with hyphens. (\& is done by \LWR@nullfonts.)

```
\RenewDocumentCommand{\LWR@subsingledollar}{s m m m}{}%
\LWR@simplifyname{\_}
\LWR@simplifyname{\#}
\LWR@simplifyname{\textbackslash}
\LWR@simplifyname{\protect}
\LWR@simplifyname{\ }
\LWR@simplifyname{\textless}
\LWR@simplifyname{\textgreater}

\edef\LWR@thisnewfilename{\detokenize\expandafter{\LWR@thisnewfilename}}%
```

Warn if there is dollar math in the section name:

```
\ifbool{FileSectionNames}{%
    \IfSubStr{\LWR@thisnewfilename}{\LWRdollar}{%
        \PackageWarning{lwarp}
        {%
            This section name:\MessageBreak
            \space\space``\detokenize\expandafter{#1}''\MessageBreak
            at the line number listed below,\MessageBreak
            is using $dollar-delimited math$,
            which generates\MessageBreak
            complicated file names.  It is better to use\MessageBreak
            \space\space%
              \protect\section{Name with \protect\(parenthesis math\protect\)}%
                 \MessageBreak
            The math then will be removed from the file name.\MessageBreak
            \MessageBreak
            \LWR@avoiddupfilenames%
            \MessageBreak
            This section is found before or%
        }
    }{}%
}{}
```

```
\LWR@traceinfo{LWR@filenamenoblanks edef: !\LWR@thisnewfilename!}%
\fullexpandarg%
```

Convert spaces into hyphens:

```
\LWR@simplifyname*{ }
```

Convert punctutation into hyphens:

```
\LWR@simplifyname*{*}
\LWR@simplifyname*{(}
\LWR@simplifyname*{)}
\LWR@simplifyname*{.}
\LWR@simplifyname*{!}
\LWR@simplifyname*{,}
\LWR@simplifyname*{'}
\LWR@simplifyname*{+}
\LWR@simplifyname*{/}
\LWR@simplifyname*{:}
\LWR@simplifyname*{;}
\LWR@simplifyname*{=}
\LWR@simplifyname*{?}
\LWR@simplifyname*{@}
\LWR@simplifyname*{^}
\LWR@simplifyname*{&}
\LWR@simplifyname*{"}
\LWR@simplifyname*{<}
\LWR@simplifyname*{>}
```

```
\LWR@simplifyname{\LWRbackslash}
```

Braces are removed entirely to avoid extra dashes in the result.

```
\StrSubstitute{\LWR@thisnewfilename}%
    {\LWRleftbrace}{}[\LWR@thisnewfilename]%
\StrSubstitute{\LWR@thisnewfilename}%
    {\LWRrightbrace}{}[\LWR@thisnewfilename]%
```

```
\LWR@simplifyname{\LWRpercent}
\LWR@simplifyname{\LWRdollar}
```

```
\LWR@simplifyname*{|}
\LWR@simplifyname*{^}
\LWR@simplifyname*{~}
\LWR@simplifyname*{[}
\LWR@simplifyname*{]}
\LWR@simplifyname*{`}
```

Convert short words:

```
\LWR@simplifyname*{-s-}
\LWR@simplifyname*{-S-}
\LWR@simplifyname*{-a-}
```

```
\LWR@simplifyname*{-A-}
\LWR@simplifyname*{-an-}
\LWR@simplifyname*{-AN-}
\LWR@simplifyname*{-to-}
\LWR@simplifyname*{-TO-}
\LWR@simplifyname*{-by-}
\LWR@simplifyname*{-BY-}
\LWR@simplifyname*{-of-}
\LWR@simplifyname*{-OF-}
\LWR@simplifyname*{-and-}
\LWR@simplifyname*{-AND-}
\LWR@simplifyname*{-for-}
\LWR@simplifyname*{-FOR-}
\LWR@simplifyname*{-the-}
\LWR@simplifyname*{-THE-}
```

Convert custom words:

```
\LWR@simplifycustom%
```

If pdfLaTeX and not `utf8` encoding, don't try to convert emdash, endash:

```
\ifPDFTeX% pdflatex or dvi latex
\ifdefstring{\inputencodingname}{utf8}{%
    \LWR@simplifyname*{—}
%     emdash
    \LWR@simplifyname*{–}
%     endash
}{}%
\else% not PDFTeX
    \LWR@simplifyname*{—}
    \LWR@simplifyname*{–}
\fi%
```

Convert multiple hyphens:

```
\LWR@simplifyname*{-----}
\LWR@simplifyname*{----}
\LWR@simplifyname*{---}
\LWR@simplifyname*{--}
```

If starts with a dash, remove the leading dash:

```
\IfBeginWith{\LWR@thisnewfilename}{\detokenize{-}}{%
    \StrGobbleLeft{\LWR@thisnewfilename}{1}[\LWR@thisnewfilename]%
}{}%
```

If ends with a dash, remove the trailing dash:

```
\IfEndWith{\LWR@thisnewfilename}{\detokenize{-}}{%
    \StrGobbleRight{\LWR@thisnewfilename}{1}[\LWR@thisnewfilename]%
}{}%
```

Limits the length of the filename:

```
\StrLeft{\LWR@thisnewfilename}{\FilenameLimit}[\LWR@thisnewfilename]%
```

Return the global result:

```
\global\let\LWR@thisfilename\LWR@thisnewfilename%
\endgroup%
\LWR@traceinfo{LWR@filenamenoblanks: result is \LWR@thisfilename}%
}
```

63.1 Sanitizing expressions for HTML

Math expressions are converted to `latexmlmath`, and some math environments may contain &, <, or >, which should not be allowed inside an HTML `<alt>` tag, so must convert them to HTML entities.

`\LWR@replacestrings` {⟨*search*⟩} {⟨*replace*⟩}

Replaces strings inside `\tmpb`.

Modified from the original, by Petr Olsak, from the opmac package.

```
\bgroup
\catcode`!=3 \catcode`?=3

\long\gdef\LWR@replacestrings@addto#1#2{%
    \expandafter\def\expandafter#1\expandafter{#1#2}%
}

\gdef\LWR@replacestrings#1#2{%
    \long\def\LWR@replacestringsA##1#1{\def\tmpb{##1}\LWR@replacestringsB}%
   \long\def\LWR@replacestringsB##1#1{%
        \ifx!##1\relax \else\LWR@replacestrings@addto\tmpb{#2##1}%
        \expandafter\LWR@replacestringsB\fi%
    }%                                      improved version <May 2016> inspired
  \expandafter\LWR@replacestringsA\tmpb?#1!#1% from pysyntax.tex by Petr Krajnik
    \long\def\LWR@replacestringsA##1?{%
        \def\tmpb{##1}%
    }\expandafter\LWR@replacestringsA\tmpb%
}
\egroup
```

`Bool` `LWR@MathJax@silentquotes` If true, double quotes (\" and ") are removed (used for mathspec). This unfortunately includes double quotes used inside `\text` with MathJax. If false, double quotes are escaped.

```
\newbool{LWR@MathJax@silentquotes}
\boolfalse{LWR@MathJax@silentquotes}
```

`\LWR@subHTMLsanitize` `\LWR@strresult` must first be set by `\LWR@HTMLsanitize`, `\LWR@HTMLsanitizeexpand`, or `\CustomizeMathJax`.

```
\catcode`\#=12
\catcode`\&=12
\newcommand{\LWR@subHTMLsanitize}{%
```

The &, <, and > may be interpreted by the browser:

```
    \edef\tmpb{\detokenize\expandafter{\LWR@strresult}}%
    \LWR@replacestrings{&}{&amp;}%
    \LWR@replacestrings{<}{&lt;}%
    \LWR@replacestrings{>}{&gt;}%
```

The quotes occasionally causes problems. For mathspec, also allow neutralization of \" and the " character.

```
    \ifbool{LWR@MathJax@silentquotes}
        {%
            \expandafter\LWR@replacestrings\expandafter{\LWRbackslash"}{}%
            \LWR@replacestrings{"}{}%
        }%
        {\LWR@replacestrings{"}{&quot;}}%
    \LWR@replacestrings{'}{&apos;}%
    \LWR@replacestrings{`}{&grave;}%
```

MathJax allows expressions to be defined with \newcommand. These expressions would appear with ## for each argument, and each must be changed to a single #. This must be done after all the above changes. Attempting another conversion after this causes an error upon further expansion.

```
    \LWR@replacestrings{##}{#}%
    \edef\LWR@strresult{\detokenize\expandafter{\tmpb}}%
}
\catcode`\#=6
\catcode`\&=4
```

`\LWR@HTMLsanitize` {⟨*text*⟩}

```
\newrobustcmd{\LWR@HTMLsanitize}[1]{%
```

Cancel French babel character handling, and fully expand the strings:

```
    \begingroup%
    \LWR@hook@processingtags%
    \edef\LWR@strresult{\detokenize{#1}}%
    \LWR@subHTMLsanitize%
    \LWR@strresult%
    \endgroup%
}
```

`\LWR@HTMLsanitizeexpand` {⟨*text*⟩}

This version expands the argument before sanitizing it. This is only used for adding math to MathJax expressions or `lateximage` `alt` tags.

```
\edef\LWR@beginspaceleftbrace{begin \LWRleftbrace}
\edef\LWR@beginspaceleftbrace{\detokenize\expandafter{\LWR@beginspaceleftbrace}}
\edef\LWR@beginleftbrace{begin\LWRleftbrace}
\edef\LWR@beginleftbrace{\detokenize\expandafter{\LWR@beginleftbrace}}

\edef\LWR@endspacerightbrace{end \LWRrightbrace}
\edef\LWR@endspacerightbrace{\detokenize\expandafter{\LWR@endspacerightbrace}}
\edef\LWR@endrightbrace{end\LWRrightbrace}
\edef\LWR@endrightbrace{\detokenize\expandafter{\LWR@endrightbrace}}

\newrobustcmd{\LWR@HTMLsanitizeexpand}[1]{%
```

Cancel French babel character handling, and fully expand the strings:

```
    \begingroup%
    \LWR@hook@processingtags%
```

The difference between this and `\LWR@HTMLsanitize` (without "expand") is the following `\expandafter`:

```
    \edef\LWR@strresult{\detokenize\expandafter{#1}}%
```

The math expression may includes spaces between tokens, but MathJax does not want a space between `\begin` or `\end` and the following brace. This space is removed here.

```
    \protect\StrSubstitute{\LWR@strresult}%
        {\LWR@beginspaceleftbrace}{\LWR@beginleftbrace}[\LWR@strresult]%
    \protect\StrSubstitute{\LWR@strresult}%
        {\LWR@endspacerightbrace}{\LWR@endrightbrace}[\LWR@strresult]%

    \LWR@subHTMLsanitize%
    \LWR@strresult%
    \endgroup%
}
```

63.2 Customizing MathJax

`\LWR@customizedMathJax` Additional MathJax definitions to be added to the start of each HTML page.

```
\newcommand*{\LWR@customizedMathJax}{}
```

Bool `LWR@warnedcustomizemathjax` Used to issue only one warning about using a `\CustomizeMathJax` per macro.

```
\newbool{LWR@warnedcustomizemathjax}
\boolfalse{LWR@warnedcustomizemathjax}
```

`\LWR@subcustomizedmathjax` {⟨*macro definition*⟩}

```
\newcommand*{\LWR@subcustomizedmathjax}[1]{%
    \begingroup%
    \LWR@hook@processingtags%
```

```
    \edef\LWR@strresult{\detokenize{#1}}%
    \LWR@subHTMLsanitize%
    \xdef\LWR@customizedMathJax{%
        \LWR@customizedMathJax%
            \LWR@strresult%
    }%
    \endgroup%
}
\@onlypreamble\LWR@subcustomizedmathjax
```

`\CustomizeMathJax` {⟨*macro definition*⟩}

A warning is issued if a very long argument is given.

```
\newcommand*{\CustomizeMathJax}[1]{%
    \ifbool{LWR@warnedcustomizemathjax}{}{%
        \StrLen{\detokenize{#1}}[\LWR@tempone]%
        \ifnumgreater{\LWR@tempone}{350}{%
            \AtEndDocument{%
                \PackageWarningNoLine{lwarp}{%
                  To ensure faster MathJax compilation, place each\MessageBreak
                custom macro in its own \protect\CustomizeMathJax.\MessageBreak
                 See the Lwarp documentation regarding customizing\MessageBreak
                    MathJax%
                }%
            }%
            \booltrue{LWR@warnedcustomizemathjax}%
        }{}%
    }%
    \appto\LWR@customizedMathJax{\LWRbackslash(}%
    \LWR@subcustomizedmathjax{#1}%
    \appto\LWR@customizedMathJax{\LWRbackslash)\par}%
}
\@onlypreamble\CustomizeMathJax
```

`\LWR@infoprocessingmathjax` {⟨*package name*⟩}

```
\newcommand*{\LWR@infoprocessingmathjax}[1]{%
\typeout{---}
\typeout{Package lwarp: Processing MathJax customizations for #1.}
\typeout{\space\space This may take a moment.}
\typeout{---}
}
```

defaults Default customizations:

In the MathJax code, footnotes are only referenced. For equations, they are also generated in the HTML when the LaTeX math is generated inside the HTML comment. For other math environments, the `\footnotemark`/`\footnotetext` method must be used. See section 8.5.4 ⚠ `\footnotemark` regarding `\footnotemark`.

For footnotes, `\footnotename` is used in most cases, however for `equation` the footnote is picked up from LaTeXin `\LWR@doendequation`.

First, \footnotename for MathJax is copied from LaTeX.

```
\providecommand{\footnotename}{footnote}

% due to warpMathJax:
\end{warpHTML}

\begin{warpMathJax}
\xdef\LWR@customizedMathJax{\LWR@customizedMathJax%
    \LWRbackslash(%
    \LWRbackslash{}newcommand%
    \{\LWRbackslash{}footnotename\}%
    \{\footnotename\}%
    \LWRbackslash)\par%
}
\end{warpMathJax}
```

\LWRfootnote is set per equation if a footnote is detected in the equation's math expression, otherwise it defaults to \footnotename.

```
\begin{warpMathJax}
\CustomizeMathJax{\def\LWRfootnote{1}}
\CustomizeMathJax{\newcommand{\footnote}[2][\LWRfootnote]{{}^{\mathrm{#1}}}}
\CustomizeMathJax{\newcommand{\footnotemark}[1][\LWRfootnote]{{}^{\mathrm{#1}}}}
```

\hspace is modified to accept and ignore a star:

```
\CustomizeMathJax{\let\LWRorighspace\hspace}
\CustomizeMathJax{\renewcommand{\hspace}{\ifstar\LWRorighspace\LWRorighspace}}
```

Various other customizations:

```
\CustomizeMathJax{\newcommand{\mathnormal}[1]{{#1}}}
\CustomizeMathJax{\newcommand\ensuremath[1]{#1}}
\CustomizeMathJax{% absorb two optional arguments
    \newcommand{\LWRframebox}[2][]{\fbox{#2}}
    \newcommand{\framebox}[1][]{\LWRframebox}
}
\CustomizeMathJax{\newcommand{\setlength}[2]{}}
\CustomizeMathJax{\newcommand{\addtolength}[2]{}}
\CustomizeMathJax{\newcommand{\setcounter}[2]{}}
\CustomizeMathJax{\newcommand{\addtocounter}[2]{}}
\CustomizeMathJax{\newcommand{\arabic}[1]{}}
\CustomizeMathJax{\newcommand{\number}[1]{}}
\CustomizeMathJax{\newcommand{\noalign}[1]{\text{#1}\notag \\}}
\CustomizeMathJax{\newcommand{\cline}[1]{}}
\CustomizeMathJax{\newcommand{\directlua}[1]{\text{(directlua)}}}
\CustomizeMathJax{\newcommand{\luatexdirectlua}[1]{\text{(directlua)}}}
```

\protect, \mathchar, and \delimiter are silently discarded; and \mathcode and \delcode are ignored.

```
\CustomizeMathJax{\newcommand{\protect}{}}
\CustomizeMathJax{\def\LWRabsorbnumber#1 {}}
\CustomizeMathJax{\def\LWRabsorbquotenumber"#1 {}}
```

```
\CustomizeMathJax{\newcommand{\LWRabsorboption}[1][]{}}
\CustomizeMathJax{\newcommand{\LWRabsorbtwooptions}[1][]{\LWRabsorboption}}
\CustomizeMathJax{\def\mathchar{\ifnextchar"\LWRabsorbquotenumber\LWRabsorbnumber}}
\CustomizeMathJax{\def\mathcode#1={\mathchar}}
\CustomizeMathJax{\let\delcode\mathcode}
\CustomizeMathJax{\let\delimiter\mathchar}
\end{warpMathJax}

\begin{warpHTML}% due to warpMathJax
```

`\LWR@customizeMathJax` Prints MathJax commands to the HTML output.

```
\newcommand{\LWR@customizeMathJax}{%
\ifbool{mathjax}{

\LWR@stoppars
\LWR@htmlcomment{MathJax customizations:}

\begin{BlockClass}{hidden}
\LWR@stoppars
```

Avoid ligatures while printing MathJax customizations:

```
{
    \LWR@print@ttfamily
    \LWR@customizedMathJax
}
\LWR@startpars
\end{BlockClass}

\LWR@startpars
}{}
}

\end{warpHTML}
```

for PRINT output:

```
\begin{warpprint}
```

`\CustomizeMathJax` The print-mode version:

```
\newcommand*{\CustomizeMathJax}[1]{}
```

`\FilenameSimplify` `*` {⟨*expression*⟩}

```
\NewDocumentCommand{\FilenameSimplify}{s m}{}

\end{warpprint}
```

for HTML output:

```
\begin{warpHTML}
```

`\LWR@createfooter` If specified, create the first or later web page footer.

```
\newcommand*{\LWR@createfooter}{%
    \ifnumless{\value{LWR@htmlseqfilenumber}}{1}{%
        \ifdefempty{\LWR@firstpagebottom}{}{%
            \LWR@htmlelement{footer}

            \LWR@firstpagebottom

            \LWR@htmlelementend{footer}
        }%
    }{%
        \ifdefempty{\LWR@pagebottom}{}{%
            \LWR@htmlelement{footer}

            \LWR@pagebottom

            \LWR@htmlelementend{footer}
        }%
    }%
}
```

`\LWR@newhtmlfile` {⟨*section name*⟩}

Finishes the current HTML page with footnotes, footer, navigation, then starts a new HTML page with an HTML comment telling where to split the page and what the new filename and CSS are, then adds navigation, side TOC, header, and starts the text body.

```
\newcommand*{\LWR@newhtmlfile}[1]{
\LWR@traceinfo{LWR@newhtmlfile}
```

At the bottom of the ending file:

```
\LWR@htmlelementclassend{section}{textbody}
\LWR@htmlelementclassend{main}{bodycontainer}
\LWR@htmlelementclassend{div}{bodyandsidetoc}

\LWR@printpendingfootnotes

```

No footer between files if EPUB:

```
\ifbool{FormatEPUB}{}{\LWR@createfooter}
```

No bottom navigation if are finishing the home page or formatting for EPUB or a word-processor.

```
\ifthenelse{\boolean{FormatEPUB}\OR\boolean{FormatWP}}
    {}
    {\ifnumcomp{\value{LWR@htmlfilenumber}}{>}{0}{\LWR@botnavigation}{}}
```

End of this HTML file:

```
\LWR@stoppars
\LWR@htmltag{/body}\LWR@orignewline
\LWR@htmltag{/html}\LWR@orignewline
```

```
\LWR@traceinfo{LWR@newhtmlfile: about to LWR@orignewpage}
\LWR@maybe@orignewpage

\addtocounter{LWR@htmlfilenumber}{1}%
\addtocounter{LWR@htmlseqfilenumber}{1}%
```

If using a filename based on section name, create a version without blanks. The filename without blanks will be placed into `\LWR@thisfilename`. Duplicates will be detected using MD5 hashes.

If not using a filename, the file number will be used instead.

```
\ifbool{FileSectionNames}%
{%
```

Convert the section name to a filename with blanks and common words removed. The resulting filename is in `\LWR@thisfilename`.

```
    \LWR@filenamenoblanks{#1}%
```

Create a macro name from the MD5 hash of the file name, to detect duplicates:

```
    \edef\LWR@hashedname{\LWR@mdfive{\LWR@thisfilename}}%
```

If the macro name is not yet defined, this filename is unique.

```
    \ifcsundef{LWR@filename\LWR@hashedname}{%
```

If the filename is unique, create a macro using the hashed name, to be used to test for additional duplicates in the future.

```
        \csdef{LWR@filename\LWR@hashedname}{}%
    }{%
```

If the filename is not unique, create an error.

```
        \PackageError{lwarp}%
            {%
                The section name:\MessageBreak
                ``#1'',\MessageBreak
                at the line number listed below,\MessageBreak
                generates the filename\MessageBreak
                ``\LWR@thisfilename'',\MessageBreak
                which appears to be a duplicate.  There is a\MessageBreak
               previous section with an identical or similar name.\MessageBreak
                While generating file names, Lwarp sanitizes math,\MessageBreak
                most symbols, and a few common short words,\MessageBreak
                and this may cause a conflict.\MessageBreak
                Enter 'H' for possible solutions%
            }%
            {%
                \LWR@avoiddupfilenames%
            }%
```

```
    }%
}%
```

If using file numbers instead of names, the name is set to the next file number.

```
{\renewcommand*{\LWR@thisfilename}{\arabic{LWR@htmlfilenumber}}}
```

Include an HTML comment to instruct lwarpmk where to split the files apart. Uses pipe-separated fields for `split_html.gawk`. Uses monospaced font with ligatures disabled for everything except the title.

```
\LWR@traceinfo{LWR@newhtmlfile: about to print start file}%
```

`\LWR@nullfonts` to allow math in a section name.

```
\begingroup%
\LWR@nullfonts%
\LWR@htmlblockcomment{%
|Start file|%
\LWR@htmlsectionfilename{\LWR@thisfilename}|%
}
\endgroup%
```

At the top of the starting file:

```
\LWR@stoppars

```

Start a new file with the given section name:

```
\LWR@filestart[#1]

```

Track the PDF page numbers of the HTML output. This is updated more frequently than `LWR@currentautosecpage`.

```
\setcounter{LWR@currentautosecfloatpage}{\value{page}}%
\LWR@newautopagelabel{LWR@currentautosecfloatpage}%
```

No navigation between files if formatting for an EPUB or word processor:

```
\ifthenelse{\boolean{FormatEPUB}\OR\boolean{FormatWP}}
    {}
    {\LWR@topnavigation}

```

No header if between files if formatting for an EPUB or word processor:

```
\ifthenelse{\boolean{FormatEPUB}\OR\boolean{FormatWP}}
    {}
    {

        \ifdefempty{\LWR@pagetop}{}{
```

```
            \LWR@htmlelement{header}

            \LWR@pagetop

            \LWR@htmlelementend{header}
        }
    }

```

The container for the sidetoc and text body:

```
\LWR@htmlelementclass{div}{bodyandsidetoc}
```

No sideTOC if formatting for an EPUB or word processor:

```
\ifthenelse{\boolean{FormatEPUB}\OR\boolean{FormatWP}}
    {}
    {\LWR@sidetoc}

```

Start of the <textbody>:

```
\LWR@htmlelementclass{main}{bodycontainer}
\LWR@htmlelementclass{section}{textbody}
```

Not yet found a new section in this file. Once one is found, a label will be placed for previous/next links.

```
\boolfalse{LWR@setseqfilelabel}
```

Print title only if there is one. Skip if formatting for an EPUB or word processor:

```
\ifthenelse{\boolean{FormatEPUB}\OR\boolean{FormatWP}}%
    {}%
    {%
        \ifcsvoid{thetitle}{}{%
            \LWR@printthetitle%
        }%
    }%
```

Keep paragraph tags disabled for now:

```
\LWR@stoppars

```

If using MATHJAX, print the customizations here.

```
\LWR@customizeMathJax

\LWR@traceinfo{LWR@newhtmlfile: done}
}

\end{warpHTML}
```

64 Sectioning

Sectioning and cross-references have been emulated from scratch, rather than try to patch several layers of existing LaTeX code and packages. Formatting is handled by CSS, so the emulated code has much less work to do than the print versions.

Unicode

⚠ accents in filenames

Section names and the resulting filenames with accented characters are partially supported, depending on the ability of *pdflatex* to generate characters and *pdftotext* to read them. If extra symbols appear in the text, it may be that *pdflatex* is actually producing a symbol over or under a character, resulting in *pdftotext* picking up the accent symbol separately.

XeLaTeX and LuaLaTeX directly support accented section and file names, but it may be necessary to use LaTeX accents instead of native Unicode accents. LaTeX accents will have the accents stripped when creating file names, whereas using Unicode accents will create filenames which include accents, which may cause issues with some operating systems.

for HTML output:

```
\begin{warpHTML}
```

64.1 User-level starred section commands

`\ForceHTMLPage`

For HTML output, forces the next section to be on its own HTML page, if `FileDepth` allows, even if starred. For use with `\printindex` and others which generate a starred section which should be on its own HTML page. Also see `\ForceHTMLTOC`.

For print output, no effect.

```
\newbool{LWR@forcinghtmlpage}
\boolfalse{LWR@forcinghtmlpage}

\newcommand*{\ForceHTMLPage}{%
\global\booltrue{LWR@forcinghtmlpage}%
}
```

`\ForceHTMLTOC`

For HTML output, forces the next section to have a TOC entry, even if starred. For use with `\printindex` and others which generate a starred section which should be in the TOC so that it may be accessed via HTML. Not necessary if used with tocbibind. Also see `\ForceHTMLPage`.

For print output, no effect.

```
\newbool{LWR@forcinghtmltoc}
\boolfalse{LWR@forcinghtmltoc}

\newcommand*{\ForceHTMLTOC}{%
\global\booltrue{LWR@forcinghtmltoc}%
}

\end{warpHTML}
```

for PRINT output:

```
\begin{warpprint}
\newcommand*{\ForceHTMLPage}{}
```

```
\newcommand*{\ForceHTMLTOC}{}
\end{warpprint}
```

for HTML output:

```
\begin{warpHTML}
```

64.2 Book class commands

`\mainmatter` Declare the main matter section of the document. Does not reset the page number, which must be consecutive arabic numbers for the HTML conversion.

```
\newbool{LWR@mainmatter}
\DeclareDocumentCommand{\mainmatter}{}{%
\booltrue{LWR@mainmatter}%
}
```

`\frontmatter` Declare the front matter section of the document, using arabic numbering for the internal numbering. Does not reset the page number.

```
\DeclareDocumentCommand{\frontmatter}{}{%
\boolfalse{LWR@mainmatter}%
}
```

`\backmatter` Declare the back matter section of the document. Does not reset the page number.

```
\DeclareDocumentCommand{\backmatter}{}{%
\boolfalse{LWR@mainmatter}
}
```

64.3 Sectioning support macros

`\LWR@sectionumber` {⟨*section type*⟩}

Typeset a section number and its trailing space with CSS formatting:

```
\newcommand*{\LWR@sectionnumber}[1]{%
\InlineClass{sectionnumber}{#1}%
}
```

`autosec` A tag used by the TOC and index.

`\LWR@createautosec` {⟨*section type*⟩}

Create an autosection tag.

The use of `\textquotedbl` instead of " provides improved compatibility with xeCJK.

```
\newcommand*{\LWR@createautosec}[1]{%
\LWR@htmltag{%
    #1 % space
```

```
7368     id=\textquotedbl\LWR@print@mbox{autosec-\arabic{page}}\textquotedbl%
7369 }%
7370 }
```

`\LWR@pushoneclose` {⟨*sectiontype*⟩} Stacks the new sectioning level's closing tag, to be used when this section is closed some time later.

⚠ `\LWR@stoppars` must be executed first.

```
7371 \NewDocumentCommand{\LWR@pushoneclose}{m}{%
7372 \LWR@traceinfo{LWR@pushoneclose #1}%
7373     \LWR@pushclose{#1}%
7374 }
```

`\LWR@startnewdepth` {⟨*sectiontype*⟩}

Closes currently stacked tags of a lesser level, then opens the new nesting level by saving this new sectioning level's closing tag for later use.

⚠ `\LWR@stoppars` must be executed first.

```
7375 \NewDocumentCommand{\LWR@startnewdepth}{m}{%
```

Close any stacked sections up to this new one.

```
7376 \LWR@closeprevious{#1}%
```

Push a new section depth:

```
7377 \LWR@pushoneclose{#1}%
7378 }
```

Ctr `LWR@prevFileDepth` Remembers the previous `LWR@FileDepth`.

Initialized to a deep level so that any section will trigger a new HTML page after the home page.

```
7379 \newcounter{LWR@prevFileDepth}
7380 \setcounter{LWR@prevFileDepth}{\LWR@depthsubparagraph}
```

`\@seccntformat` {⟨*sectiontype*⟩}

```
7381 \def\@seccntformat#1{\csname the#1\endcsname\quad}
```

`\simplechapterdelim` Used by tocbibind and anonchap.

```
7382 \newcommand*{\simplechapterdelim}{}
```

`\@chapcntformat` {⟨*sectiontype*⟩}

`\let` to `\@seccntformat` by default, but may be redefined by `\simplechapter` and `\restorechapter` from tocbibind or anonchap.

```
\let\@chapcntformat\@seccntformat
```

`\@partcntformat` {⟨*sectiontype*⟩}

`\let` to `\@seccntformat` by default, but may be redefined by ctex.

```
\let\@partcntformat\@seccntformat
```

`\@partnameformat` Prints "Part" for part sections.

Nullified by ctex.

```
\newcommand*{\@partnameformat}{\LWR@isolate{\partname}~}%
```

`\LWR@printchaptername` Print `\chaptername` in most cases, but this is nullified for ctexbook, komascript, ujt* classes.

```
\newcommand*{\LWR@printchaptername}{%
    \ifdefvoid{\chaptername}{}{\chaptername~}%
}
```

`\LWR@section` * [⟨*TOC name*⟩] {⟨*name*⟩} {⟨*sectiontype*⟩}

The common actions for the high-level sectioning commands.

```
\DeclareDocumentCommand{\LWR@section}{m m m m}{%
\IfValueTF{#2}%
    {\LWR@traceinfo{LWR@section: starting #4 #2}}%
    {\LWR@traceinfo{LWR@section: starting #4 #3}}%
```

Warn if starting a section inside a :

```
    \LWR@spanwarninvalid{section}%
```

```
\LWR@maybeprintpendingfootnotes{\csuse{LWR@depth#4}}%
\LWR@stoppars%
\LWR@startnewdepth{#4}%
```

Cancel special `minipage` horizontal space interaction:

```
\global\boolfalse{LWR@minipagethispar}%
```

Start a new HTML file unless starred, and if is a shallow sectioning depth.

Exception: Also start a new HTML file for `\part*`, for appendix.

Generate a new LaTeX page so that TOC and index page number points to the section:

```
\LWR@traceinfo{LWR@section: testing whether to start a new HTML file}%
```

```
\IfBooleanT{#1}{\LWR@traceinfo{LWR@section: starred}}%
\ifbool{LWR@forcinghtmlpage}{\LWR@traceinfo{LWR@section: forcinghtmlpage}}{}%
\ifthenelse{%
    \(%
        \(\NOT\equal{#1}{\BooleanTrue}\)\OR%
        \(\cnttest{\@nameuse{LWR@depth#4}}{=}{\LWR@depthpart}\)\OR%
        \(\boolean{LWR@forcinghtmlpage}\)%
    \)%
    \AND%
    \cnttest{\@nameuse{LWR@depth#4}}{<=}{\value{FileDepth}}%
    \AND%
    \(%
        \NOT\boolean{CombineHigherDepths}\OR%
        \cnttest{\@nameuse{LWR@depth#4}}{<=}{\value{LWR@prevFileDepth}}%
    \)%
    \AND%

    \(% phantomsection
        \NOT\isempty{#3}%
        \OR%
        \(\NOT\equal{#1}{\BooleanTrue}\)%
    \)%
}%
```

If so: start a new HTML file:

```
{% new file
    \LWR@traceinfo{LWR@section: new HTML file}%
```

See if there was an optional TOC name entry:

```
    \IfNoValueTF{#2}%
```

If no optional entry

```
        {\LWR@newhtmlfile{#3}}%
```

If yes an optional entry

```
        {\LWR@newhtmlfile{#2}}%
}% new file
```

Else: No new HTML file:

```
{% not new file
```

Generate a new LaTeX page so that TOC and index page number points to the section:

```
    \LWR@traceinfo{LWR@section: not a new HTML file, about to LWR@orignewpage}%
    \LWR@maybe@orignewpage%
}% not new file

```

Remember this section's name for `\nameref`:

```
\IfValueT{#3}{%
    \LWR@traceinfo{LWR@section: about to LWR@setlatestname}%
    \IfValueTF{#2}{\LWR@setlatestname{#2}}{\LWR@setlatestname{#3}}%
}%
```

Print an opening comment with the level and the name; ex: "section" "Introduction" Footnotes may be used in section names, which would also appear in the HTML section opening comments, so the short TOC entry is used if possible, and a limited opening comment is made if the sectional unit is starred.

```
\ifbool{HTMLDebugComments}{%
    \begingroup%
    \LWR@nullfonts%
    \IfBooleanTF{#1}% starred
    {\LWR@htmlcomment{Opening #4*}}%
    {%
        \IfNoValueTF{#2}% short TOC
            {\LWR@htmlcomment{Opening #4 ``#3''}}%
            {\LWR@htmlcomment{Opening #4 ``#2''}}%
    }\LWR@orignewline%
    \endgroup%
}{}
```

For inline sections paragraph and subparagraph, start a new paragraph now:

```
\ifthenelse{%
    \cnttest{\@nameuse{LWR@depth#4}}{>=}{\LWR@depthparagraph}%
}%
    {\LWR@startpars}%
    {}%
```

Create the opening tag with an autosec:

```
\LWR@traceinfo{LWR@section: about to LWR@createautosec}%
\LWR@createautosec{\@nameuse{LWR@tag#4}}%

\setcounter{LWR@currentautosecpage}{\value{page}}%
```

Check if starred:

```
\IfBooleanTF{#1}%
{%
    \LWR@traceinfo{LWR@section: starred}%
```

Starred, but also forcing a TOC entry, so add unnumbered TOC name or regular name:

```
    \ifbool{LWR@forcinghtmltoc}%
    {%
        \addcontentsline{toc}{#4}{%
            \IfValueTF{#2}{\LWR@isolate{#2}}{\LWR@isolate{#3}}%
        }%
    }%
    {}%
}% starred
```

Not starred, so step counter and add to TOC:

```
{% not starred
```

Only add a numbered TOC entry if section number is not too deep:

```
    \ifthenelse{%
        \cnttest{\@nameuse{LWR@depth#4}}{<=}{\value{secnumdepth}}%
    }%
    {% if secnumdepth
```

If in the main matter, step the counter and add the TOC entry. For `article` class, lwarp assumes that all is mainmatter.

```
        \LWR@traceinfo{LWR@section: about to test main matter}%
        \ifbool{LWR@mainmatter}%
        {%
            \LWR@traceinfo{LWR@section: yes mainmatter}%
            \refstepcounter{#4}%
```

Add main matter numbered TOC entry with the TOC name or the regular name:

```
            \LWR@traceinfo{LWR@section: about to addcontentsline}%
            \addcontentsline{toc}{#4}%
            {%
                \protect\numberline{%
                    \@nameuse{pre#4name}%
                    \@nameuse{the#4}%
                    \@nameuse{post#4name}%
                }%
                {%
                    \ignorespaces%
              \IfValueTF{#2}{\LWR@isolate{#2}}{\LWR@isolate{#3}}\protect\relax%
                }%
            }%
            \LWR@traceinfo{LWR@section: finished addcontentsline}%
        }% end of if main matter
```

If not main matter, add unnumbered TOC name or regular name:

```
        {% not main matter
            \LWR@traceinfo{LWR@section: no main matter}%
            \addcontentsline{toc}{#4}{%
                \IfValueTF{#2}{\LWR@isolate{#2}}{\LWR@isolate{#3}}%
            }%
        }% end of not main matter
    }% end of secnumdepth
```

Deeper than secnumdepth, so add an unnumbered TOC entry:

```
    {%
        \addcontentsline{toc}{#4}{%
            \IfValueTF{#2}{\LWR@isolate{#2}}{\LWR@isolate{#3}}%
        }%
    }%
```

For part, print “Part”:

```
    \ifbool{LWR@mainmatter}%
    {%
        \ifthenelse{%
            \(\cnttest{\@nameuse{LWR@depth#4}}{<=}%
                {\value{secnumdepth}}\) \AND%
            \(\cnttest{\@nameuse{LWR@depth#4}}{=}{\LWR@depthpart}\)%
        }%
            {\@partnameformat}%
            {}%
```

Print the section number:

```
        \LWR@traceinfo{LWR@section: about to print section number}%
        \ifthenelse{%
            \cnttest{\@nameuse{LWR@depth#4}}{<=}{\value{secnumdepth}}%
        }%
            {%
                \ifstrequal{#4}{part}%
                {\protect\LWR@sectionnumber{\@partcntformat{#4}}}%
                {%
                    \ifstrequal{#4}{chapter}%
                        {%

                            \LWR@printchaptername%
                            \protect\LWR@sectionnumber{\@chapcntformat{#4}}%
                        }%
                        {\protect\LWR@sectionnumber{\@seccntformat{#4}}}%
                }%
            }%
            {}%
        \LWR@traceinfo{LWR@section: finished print section number}%
    }{}%
}% not starred
```

Print the section name:

```
\LWR@traceinfo{LWR@section: about to print the section name}%
\LWR@isolate{#3}%
```

Close the heading tag, such as /H2:

```
\LWR@traceinfo{LWR@section: about to close the heading tag}%
\LWR@htmltag{\@nameuse{LWR@tag#4end}}%
\LWR@orignewline%
```

Generate a LaTeX label.

Track the PDF page numbers of the HTML output. A new autopage label may be generated for `LWR@currentautosecpage` for the start of the section, and also for the current page if it is different due to an SVG image in the section name. Also, the final page after the section has been created is updated in `LWR@currentautosecfloatpage`.

```
\LWR@traceinfo{LWR@section: about to create the LaTeX label}%
\setcounter{LWR@currentautosecfloatpage}{\value{page}}%
\LWR@newautopagelabel{LWR@currentautosecpage}\LWR@orignewline%
```

If this is the first section found in this file, create a label for prevous/next links:

```
\ifbool{LWR@setseqfilelabel}{}{%
    \label{\BaseJobname-autofile-\arabic{LWR@htmlseqfilenumber}}%
    \booltrue{LWR@setseqfilelabel}%
}%
```

Start paragraph handing unless is an inline paragraph or subparagraph:

```
\ifthenelse{%
    \cnttest{\@nameuse{LWR@depth#4}}{<}{\LWR@depthparagraph}%
}%
    {\LWR@startpars}%
    {}%
```

If not starred, remember the previous depth to possibly trigger a new HTML page.

HOWEVER, allow a `\part*` to start a new HTML page. This is used by appendix.

A starred section does not trigger a new HTML page at the beginning of this macro, so it should not affect it here at the end either. This became an issue when a `\listoftables` was tested in the middle of the document. The `\chapter*` for the list was not allowing a new HTML page for the section following it while `CombineHigherDepths` was true.

```
\ifthenelse{%
    \NOT\equal{#1}{\BooleanTrue}\OR%
    \cnttest{\@nameuse{LWR@depth#4}}{=}{\LWR@depthpart}%
}%
    {% not starred
        \setcounter{LWR@prevFileDepth}{\@nameuse{LWR@depth#4}}%
    }% not starred
    {}%
```

Reset to defaults if not a phantomsection:

```
\ifstrempty{#3}%
    {}%
    {%
        \global\boolfalse{LWR@forcinghtmlpage}%
        \global\boolfalse{LWR@forcinghtmltoc}%
    }%
%
\LWR@traceinfo{LWR@section: done}%
}
```

64.4 Pre- and post- sectioning names

`\prebookname` `\postbookname` Usually null, but is used by uj* and ut* Japanese classes.

```
\providecommand*{\prebookname}{}
\providecommand*{\postbookname}{}
```

`\prepartname` `\postpartname` Usually null, but is used by uj* and ut* Japanese classes.

```
\providecommand*{\prepartname}{}
\providecommand*{\postpartname}{}
```

`\prechaptername` `\postchaptername` Usually null, but is used by uj* and ut* Japanese classes.

```
\providecommand*{\prechaptername}{}
\providecommand*{\postchaptername}{}
```

`\presectionname` `\postsectionname` Always null, but provided here for algorithmic simplicity in `\LWR@section`.

```
\providecommand*{\presectionname}{}
\let\postsectionname\presectionname

\let\presubsectionname\presectionname
\let\postsubsectionname\postsectionname

\let\presubsubsectionname\presectionname
\let\postsubsubsectionname\postsectionname

\let\preparagraphname\presectionname
\let\postparagraphname\postsectionname

\let\presubparagraphname\presectionname
\let\postsubparagraphname\postsectionname
```

64.5 `\section` and friends

For memoir, a second optional argument is allowed.

For hypbmsec, a second optional argument or either parenthesis argument is allowed.

Each of these additional arguments are for headers or PDF bookmarks, and are ignored for HTML output.

`\part` `*` `(`⟨*2:PDF name*⟩`)` `[`⟨*3:TOC name*⟩`]` `[`⟨*4:PDF name*⟩`]` `(`⟨*5:PDF name*⟩`)` `{`⟨*6:name*⟩`}`

```
\newcommand{\part@preamble}{}% for koma-script

\DeclareDocumentCommand{\part}{s d() o o d() m}{%
    \LWR@section{#1}{#3}{#6}{part}%

    \part@preamble% for koma-script
    \renewcommand{\part@preamble}{}%
}
```

\chapter * (⟨2:PDF name⟩) [⟨3:TOC name⟩] [⟨4:PDF name⟩] (⟨5:PDF name⟩) {⟨6:name⟩}

```
\let\@printcites\relax% for quotchap package

\newcommand{\chapter@preamble}{}% for koma-script

\@ifundefined{chapter}
{}
{%
    \DeclareDocumentCommand{\chapter}{s d() o o d() m}{%
        \LWR@section{#1}{#3}{#6}{chapter}%

        \@printcites% for quotchap package

        \chapter@preamble% for koma-script
        \renewcommand{\chapter@preamble}{}%
    }
}
```

\section * (⟨2:PDF name⟩) [⟨3:TOC name⟩] [⟨4:PDF name⟩] (⟨5:PDF name⟩) {⟨6:name⟩}

```
\DeclareDocumentCommand{\section}{s d() o o d() m}{%
    \LWR@section{#1}{#3}{#6}{section}%
}
```

\subsection * (⟨2:PDF name⟩) [⟨3:TOC name⟩] [⟨4:PDF name⟩] (⟨5:PDF name⟩) {⟨6:name⟩}

```
\DeclareDocumentCommand{\subsection}{s d() o o d() m}{%
    \LWR@section{#1}{#3}{#6}{subsection}%
}
```

\subsubsection * (⟨2:PDF name⟩) [⟨3:TOC name⟩] [⟨4:PDF name⟩] (⟨5:PDF name⟩) {⟨6:name⟩}

```
\DeclareDocumentCommand{\subsubsection}{s d() o o d() m}{%
    \LWR@section{#1}{#3}{#6}{subsubsection}%
}
```

\paragraph * (⟨2:PDF name⟩) [⟨3:TOC name⟩] [⟨4:PDF name⟩] (⟨5:PDF name⟩) {⟨6:name⟩}

```
\DeclareDocumentCommand{\paragraph}{s d() o o d() m}{%
    \LWR@section{#1}{#3}{#6}{paragraph}%
}
```

\subparagraph * (⟨2:PDF name⟩) [⟨3:TOC name⟩] [⟨4:PDF name⟩] (⟨5:PDF name⟩) {⟨6:name⟩}

```
\DeclareDocumentCommand{\subparagraph}{s d() o o d() m}{%
    \LWR@section{#1}{#3}{#6}{subparagraph}%
}

\end{warpHTML}
```

65 Starting a new file

for HTML & PRINT:

```
\begin{warpall}
```

\HTMLLanguage Default language for the HTML lang tag.

```
\newcommand*{\LWR@currentHTMLLanguage}{en-US}

\newcommand*{\HTMLLanguage}[1]{%
    \renewcommand*{\LWR@currentHTMLLanguage}{#1}%
}
```

\theHTMLTitleSeparator May be used inside \theHTMLTitleSection to separate the website's overall HTML title and the particular page's section name.

```
\ifPDFTeX% pdflatex or dvi latex
    \ifdefstring{\inputencodingname}{utf8}{%
        \newcommand*{\theHTMLTitleSeparator}{ —\ }% EMdash
    }{%
        \newcommand*{\theHTMLTitleSeparator}{ -\ }% hyphen
    }%
\else%
    \ifpTeX
        \newcommand*{\theHTMLTitleSeparator}{ -\ }% hyphen
    \else
        \newcommand*{\theHTMLTitleSeparator}{ —\ }% EMdash
    \fi%
\fi%
```

\HTMLTitleBeforeSection Sets the HTML page's meta title tag to show the website title before the section name.

```
\newcommand*{\HTMLTitleBeforeSection}{%
    \def\theHTMLTitleSection{%
        \theHTMLTitle\theHTMLTitleSeparator\theHTMLSection%
    }%
}
```

\HTMLTitleAfterSection Sets the HTML page's meta title tag to show the section name before the website title.

```
\newcommand*{\HTMLTitleAfterSection}{%
    \def\theHTMLTitleSection{%
        \theHTMLSection\theHTMLTitleSeparator\theHTMLTitle%
    }%
}
```

\theHTMLTitleSection Forms the HTML page's meta title tag. The default is to show the website title before the section name.

```
\HTMLTitleBeforeSection
```

\theHTMLSection The section name is passed to \LWR@filestart, which then sets \theHTMLSection for use inside \theHTMLTitleSection to create an HTML meta title tag.

```
\newcommand*{\theHTMLSection}{}

\end{warpall}

for HTML output: \begin{warpHTML}
```

\LWR@filestart [⟨*section name*⟩] Creates the opening HTML tags.

```
\newcommand*{\LWR@filestart}[1][]{%
\LWR@traceinfo{LWR@filestart !#1!}%
```

Locally temporarily disable direct-formatting commands:

```
\begingroup%
\LWR@nullfonts%
```

Save the section name for use while creating the HTML meta title tag:

```
\edef\theHTMLSection{#1}%
```

Remove extra material:

```
\StrSubstitute{\theHTMLSection}{\protect}{\detokenize{-}}[\theHTMLSection]
\StrSubstitute{\theHTMLSection}{\detokenize{-----}}{\detokenize{-}}[\theHTMLSection]
\StrSubstitute{\theHTMLSection}{\detokenize{----}}{\detokenize{-}}[\theHTMLSection]
\StrSubstitute{\theHTMLSection}{\detokenize{---}}{\detokenize{-}}[\theHTMLSection]
\StrSubstitute{\theHTMLSection}{\detokenize{--}}{\detokenize{-}}[\theHTMLSection]
```

If starts with a dash, remove the leading dash:

```
\IfBeginWith{\theHTMLSection}{\detokenize{-}}{%
    \StrGobbleLeft{\theHTMLSection}{1}[\theHTMLSection]%
}{}%
```

Create the page's HTML header:

```
\LWR@htmltag{!DOCTYPE html}\LWR@orignewline
```

The language is user-adjustable:

NOTE: \LWR@orig@textquotedbl is used here because \textquotedbl is nullified by \LWR@nullfonts while starting the new file.

```
\LWR@htmltag{%
   html lang=\LWR@orig@textquotedbl\LWR@currentHTMLLanguage\LWR@orig@textquotedbl%
}\LWR@orignewline
```

Start of the meta data:

```
\LWR@htmltag{head}\LWR@orignewline
```

Charset is fixed at UTF-8:

```
\LWR@htmltag{%
    meta charset=\LWR@orig@textquotedbl{}UTF-8\LWR@orig@textquotedbl\ /%
}\LWR@orignewline
```

Author:

```
\ifthenelse{\equal{\theHTMLAuthor}{}}%
    {}%
    {%
        \LWR@htmltag{%
        meta name=\LWR@orig@textquotedbl{}author\LWR@orig@textquotedbl\ % space
         content=\LWR@orig@textquotedbl\theHTMLAuthor\LWR@orig@textquotedbl\ /%
        }\LWR@orignewline%
    }%
```

lwarp is the generator:

```
\LWR@htmltag{%
    meta % space
    name=\LWR@orig@textquotedbl{}generator\LWR@orig@textquotedbl\ % space
   content=\LWR@orig@textquotedbl{}LaTeX Lwarp package\LWR@orig@textquotedbl\ /%
}\LWR@orignewline%
```

If there is a description, add it now:

```
\ifdefempty{\LWR@currentHTMLDescription}{}{%
    \LWR@htmltag{%
      meta name=\LWR@orig@textquotedbl{}description\LWR@orig@textquotedbl\ % space
      content=\LWR@orig@textquotedbl\LWR@currentHTMLDescription\LWR@orig@textquotedbl\ /%
    }\LWR@orignewline
}%
```

Mobile-friendly viewport:

```
\LWR@htmltag{%
    meta % space
    name=\LWR@orig@textquotedbl{}viewport\LWR@orig@textquotedbl\ % space
   content=\LWR@orig@textquotedbl{}width=device-width, initial-scale=1.0\LWR@orig@textquotedbl\ /%
}\LWR@orignewline
```

IE patch:

```
\LWR@htmltag{!-\/-[if lt IE 9]}\LWR@orignewline
\LWR@htmltag{%
    script % space
    src=\LWR@orig@textquotedbl{}%
        http://html5shiv.googlecode.com/svn/trunk/html5.js%
    \LWR@orig@textquotedbl%
}%
\LWR@htmltag{/script}\LWR@orignewline
\LWR@htmltag{![endif]-\/-}\LWR@orignewline
```

The page's title, if there is one. A section name is also added if given.

```
\ifthenelse{\equal{\theHTMLTitle}{}}%
    {}%
    {%
        \LWR@htmltag{title}%
        \ifdefempty{\theHTMLSection}%
            {\theHTMLTitle}%
            {\theHTMLTitleSection}%
        \LWR@htmltag{/title}\LWR@orignewline%
    }%
```

The page's stylesheet:

```
\LWR@htmltag{%
    link % space
    rel=\LWR@orig@textquotedbl{}stylesheet\LWR@orig@textquotedbl\ % space
    type=\LWR@orig@textquotedbl{}text/css\LWR@orig@textquotedbl\ % space
    href=\LWR@orig@textquotedbl\LWR@currentcss\LWR@orig@textquotedbl\ /%
}%
\LWR@orignewline
```

Optional MathJax support. The HTML tags must be turned off during the verbatim input, and the paragraph handling which was turned on at the end of verbatim input must be immediately turned off again.

```
\ifbool{mathjax}%
{%
    \begingroup%
    \LWR@restoreoriglists%
    \boolfalse{LWR@verbtags}%

        \IfFileExists{\LWR@mathjaxfilename}%
            {\verbatiminput{\LWR@mathjaxfilename}}%
            {%
                \PackageError{lwarp}%
                    {%
                     \protect\MathJaxFilename\space specified the file\MessageBreak
                           \space\space\LWR@mathjaxfilename\MessageBreak
                           which does not exist%
                    }%
                {Specify an existing file, or remove \protect\MathJaxFilename.}%
            }%

    \booltrue{LWR@verbtags}%
    \endgroup%
    \LWR@stoppars%
}% end of mathjax
{}%
```

End of the header:

```
\LWR@htmltag{/head}\LWR@orignewline
```

Start of the body:

```
\LWR@htmltag{body}\LWR@orignewline
\endgroup
\LWR@traceinfo{LWR@filestart: done}
}

\end{warpHTML}
```

66 Starting HTML output

for HTML output:

```
\begin{warpHTML}
```

`\LWR@LwarpStart` Executed at the beginning of the entire document.

The use of `\textquotedbl` instead of " improves compatibility with xeCJK.

```
\catcode`\$=\active
\newcommand*{\LWR@LwarpStart}
{%
\LWR@traceinfo{LWR@lwarpStart}
```

If formatting for a word processor, force filedepth to single-file only, force HTML debug comments off.

```
\ifbool{FormatWP}{%
    \setcounter{FileDepth}{-5}%
    \boolfalse{HTMLDebugComments}%
}{}
```

Expand and detokenize `\HomeHTMLFilename` and `\HTMLFilename`:

```
\edef\LWR@strresult{\HomeHTMLFilename}
\edef\HomeHTMLFilename{\detokenize\expandafter{\LWR@strresult}}
\edef\LWR@strresult{\HTMLFilename}
\edef\HTMLFilename{\detokenize\expandafter{\LWR@strresult}}
```

Force onecolumn and empty page style:

```
\LWR@origonecolumn%
\LWR@origpagestyle{empty}%
```

No black box for overfull lines:

```
\overfullrule=0pt
```

Reduce chance of line overflow when HTML tags are added:

```
\LWR@print@footnotesize%
```

In PDF output, don't allow line breaks to interfere with HTML tags:

```
\LWR@print@raggedright%
\LetLtxMacro{\\}{\LWR@endofline}%
```

Spread the lines for *pdftotext* to read them well:

```
\linespread{1.3}%
```

For *pdftotext* to reliably identify paragraph splits:

```
\setlength{\parindent}{0pt}
\setlength{\parskip}{2ex}
```

For the `lateximage` record file:

```
\immediate\openout\LWR@lateximagesfile=\BaseJobname-images.txt
```

Removes space around the caption in the HTML:

```
\setlength{\belowcaptionskip}{0ex}
\setlength{\abovecaptionskip}{0ex}
```

Redefine the plain page style to be empty when used by index pages:

```
\renewcommand{\ps@plain}{}
```

Plug in some new actions. This is done just before the document start so that they won't be over-written by some other package.

Float captions:

```
\let\LWR@origcaption\caption
```

Not yet started any paragraph handling:

```
\global\boolfalse{LWR@doingapar}
\global\boolfalse{LWR@doingstartpars}
```

Document and page settings:

```
\mainmatter
\LWR@origpagenumbering{arabic}
```

Start a new HTML file and a header:

```
\LWR@traceinfo{LWR@lwarpStart: Starting new file.}
\LWR@filestart
```

Tell *lwarpmk* that the lwarp package is in use. This allows *lwarpmk* to warn if `usepackage{lwarp}` was somehow disabled.

```
\begingroup%
\LWR@nullfonts%
```

```
\LWR@htmlblockcomment{%
|Using lwarp|%
\LWR@htmlsectionfilename{\LWR@thisfilename}|%
}
\endgroup%
```

```
\LWR@traceinfo{LWR@lwarpStart: Generating first header.}
\ifdefempty{\LWR@firstpagetop}{}{%
    \LWR@htmltag{header}\LWR@orignewline
    \LWR@startpars
    \LWR@firstpagetop
    \LWR@stoppars
    \LWR@htmltag{/header}\LWR@orignewline
}%
```

```
\LWR@htmlelementclass{div}{bodywithoutsidetoc}
\LWR@htmlelementclass{main}{bodycontainer}
\LWR@traceinfo{LWR@lwarpStart: Generating textbody.}
\LWR@htmlelementclass{section}{textbody}
```

Create a label for previous/next links, and remember it has been done:

```
\booltrue{LWR@setseqfilelabel}%
\label{\BaseJobname-autofile-\arabic{LWR@htmlseqfilenumber}}
```

Patch the `itemize`, `enumerate`, and `description` environments and `\item`. This works with the native LaTeX environments, as well as those provided by enumitem, enumerate, and paralist.

```
\LWR@patchlists
```

Ensure that math mode is active to call lwarp's patches:

```
\catcode`\$=\active
```

Required for `\nameref` to work with SVG math:

```
\immediate\write\@mainaux{\catcode`\string$\active}%
\LetLtxMacro\LWR@syntaxhighlightone$% balance for editor syntax highlighting
```

Allow HTML paragraphs to begin:

```
\LWR@startpars
```

If using MathJax, disable `\ensuremath` by printing a nullified definition at the start of each file, and add further customizations:

```
\ifbool{mathjax}{
    \typeout{---}
    \typeout{Package lwarp:}
    \typeout{Processing MathJax customizations for the first HTML page.}
    \typeout{Later HTML pages will take the same amount of time.}
   \typeout{If this takes too long, see the Lwarp manual regarding customizing MathJax.}
```

```
}{}

\LWR@customizeMathJax

\ifbool{mathjax}{
    \typeout{Done.}
    \typeout{---}
}{}
```

First autopage label in case a figure occurs early before the first section: A new autopage label may be generated for `LWR@currentautosecpage` for the start of the section, and also for the current page if it is different due to an SVG image in the section name. Also, the final page after the section has been created is updated in `LWR@currentautosecfloatpage`.

```
\setcounter{LWR@currentautosecfloatpage}{\value{page}}%
\LWR@newautopagelabel{LWR@currentautosecpage}%

\LWR@traceinfo{LWR@lwarpStart: done}
}
\catcode`\$=3% math shift until lwarp starts

\end{warpHTML}
```

67 Ending HTML output

for HTML output:

```
\begin{warpHTML}
```

`\LWR@requesttoc` {⟨*boolean*⟩} {⟨*suffix*⟩} Requests that a TOC, LOF, or LOTbe generated.

```
\newcommand*{\LWR@requesttoc}[2]{%
\ifbool{#1}
{
    \expandafter\newwrite\@nameuse{tf@#2}
    \immediate\openout \@nameuse{tf@#2} \jobname.#2\relax
}{}
}
```

`\LWR@LwarpEnd` Final stop of all HTML output:

```
\newcommand*{\LWR@LwarpEnd}
{
\LWR@stoppars
\LWR@closeprevious{finished}
```

At the bottom of the ending file:

Print any pending footnotes:

```
\LWR@printpendingfootnotes
```

Close the textbody:

```
\label{\BaseJobname-autofile-last}
\LWR@htmlelementclassend{section}{textbody}
\LWR@htmlelementclassend{main}{bodycontainer}
\LWR@htmlelementclassend{div}{bodyandsidetoc}
```

Create the footer if not EPUB

```
\ifbool{FormatEPUB}{}{\LWR@createfooter}
```

No bottom navigation if are finishing the home page, or if formatting for an EPUB or word processor.

Presumably has a table-of-contents.

```
\ifthenelse{\boolean{FormatEPUB}\OR\boolean{FormatWP}}
    {}
    {
        \ifnumcomp{\value{LWR@htmlfilenumber}}{>}{0}{\LWR@botnavigation}{}
    }
```

```
\LWR@stoppars% final stop of all paragraphs
```

Finish the HTML file:

```
\LWR@htmltag{/body}\LWR@orignewline
\LWR@htmltag{/html}\LWR@orignewline
```

Seems to be required sometimes:

```
\LWR@maybe@orignewpage
}
```

`\enddocument` If labels have not changed, mark successful completion of the `lateximages.txt` file. Executed as everything is being shut down.

For the newer kernel hooks, see **`texdoc lthooks-doc`** and **`texdoc ltshipout-doc`**.

```
\ifdef{\AddToHook}{% newer kernel
    \AddToHook{enddocument/info}{%
       \if@filesw
       \ifx \@multiplelabels \relax
         \if@tempswa
```

This is where warnings of duplicate labels would appear.

```
         \else
```

No duplicate labels, so safe to create images.

```
            \immediate\write\LWR@lateximagesfile{%
                |end|end|end|%
            }%
```

```
         \fi
       \fi\fi
    }
}% newer kernel
{% older kernel
    \xpatchcmd{\enddocument}
        {%
            \if@tempswa
            \@latex@warning@no@line{Label(s) may have changed.
            Rerun to get cross-references right}%
            \fi
        }
        {%
            \if@tempswa
                \@latex@warning@no@line{Label(s) may have changed.
                Rerun to get cross-references right}%
            \else
```

No duplicate labels, so safe to create images.

```
                \immediate\write\LWR@lateximagesfile{%
                    |end|end|end|%
                }%
            \fi
        }
        {}
        {
            \AtEndDocument{
                \PackageWarningNoLine{lwarp}
                {%
                    Could not patch \protect\enddocument.\MessageBreak
                If labels have changed, be sure to recompile before\MessageBreak
                    creating lateximages with\MessageBreak
                    \space\space lwarpmk limages,\MessageBreak
                    or the images may be corrupt%
                }
            }
        }
}% older kernel
```

68 Nullifying foreground/background hooks

See **texdoc lthooks-doc** and **textdoc ltshipout-doc**.

```
\ifdef{\RemoveFromHook}{
    \AfterEndPreamble{
        \IfHookEmptyTF{shipout/background}{}{
            \PackageInfo{lwarp}{Removing background hook}
            \RemoveFromHook{shipout/background}[*]
        }
        \IfHookEmptyTF{shipout/foreground}{}{
            \PackageInfo{lwarp}{Removing foreground hook}
            \RemoveFromHook{shipout/foreground}[*]
```

```
7918          }
7919      }
7920 }{}

7921 \end{warpHTML}
```

69 Title page

package support
load order

lwarp supports the native LaTeX titling commands, and also supports the packages authblk and titling. If both are used, authblk should be loaded before titling.

\published and \subtitle

If using the titling package, additional titlepage fields for \published and \subtitle may be added by using \AddSubtitlePublished in the preamble. See section 69.8.

affiliation

lwarp provides for the \author macro an additional \affiliation macro to provide an affiliation and other additional information for each author in the title page. The affiliation information is removed when using titlingpage's \theauthor in the main text.

reusing titlepage information

The titling package maintains the definitions of \thetitle, \theauthor, etc., after the title has been typeset. These commands are to be used to refer to the document's title and author, etc., in the main text. These definitions have the \thanks and \affiliation removed, and for \author the \and is replaced to generate a simple inline list of authors separated by commas. Note: \theauthor does not work well with authblk unless the traditional LaTeX syntax is used.

\theauthor, authblk

custom titlepages

\printtitle, \printauthor, etc., are provided for use inside a custom titlepage or titlingpage environment, and these retain the \thanks and \affiliation.

\printthanks

\printthanks has been added to force the printing of thanks inside a titlingpage environment when \maketitle is not used.

\thanks

Inside a \titlepage or \titlingpage environment, use \thanks instead of \footnote for acknowledgements, etc.

69.1 Setting the title, etc.

The following provide setting commands for both HTML and print outputs.

\author
\and

{⟨*author*⟩} While using \maketitle and print mode, the author is treated as a single-column tabular and the \and feature finishes the current tabular then starts a new one for the next author. Each author thus is placed into its own tabular, and an affiliation may be placed on its own line such as

```
\author{Name \\ Affiliation \and Second Name \\ Second Affiliation}
```

For HTML, the entire author block is placed inside a of class author, and each individual author is inside a of class oneauthor.

\@title
\@author
\@date

\@title, \@author, and \@date store the values as originally assigned, including any \thanks, \and, or \affiliation. These are low-level macros intended to be used by other macros only inside a titlepage or titlingpage, and are used by \maketitle. The

author is printed inside a single-column tabular, which becomes multiple single-column tabulars if multiples authors are included. For HTML, these tabulars become side-by-side s of class oneauthor, all of which are combined into one of class author.

\printtitle
\printauthor
\printdate

\printtitle, etc. are user-level macros intended to be used in custom titlepage or titlingpage environments in cases where \maketitle is not desired. These commands preserve the \thanks, etc., and should not be used in the main text.

\thetitle
\theauthor
\thedate
\HTMLPageBottom

\thetitle, \theauthor, and \thedate are available if titling has been loaded, and are sanitized user-level versions from which have been removed the \thanks and \affiliation, and \and is changed for inline text usage. The author is printed inline without \affiliation or \thanks, with \and placing commas between multiple authors. Thus, these commands are to be used in the main text whenever the user wishes to refer to the document's title and such. One practical use for this is to place the authors at the bottom of each HTML page, such as:

```
\HTMLPageBottom{
  \begin{center}\textcopyright~20xx \theauthor\end{center}
}
```

⚠ \theauthor, authblk

\theauthor does not work well if authblk is used. If \theauthor is important, it is recommended to use the standard LaTeX syntax for \author, optionally with lwarp's \affiliation macro as well.

⚠ affiliations

After \maketitle has completed, \theauthor retains the definition of the author, but \and is changed to become a comma and a space, intending to print the authors names separated by spaces. This fails when affiliations are included on their own table rows.

\affiliation

A solution, provide here, is to define a macro \affiliation which, during \maketitle, starts a new row and adds the affiliation, but after \maketitle is finished \affiliation is re-defined to discard its argument, thus printing only the author names when \author is later used inline.

69.2 \if@titlepage

for HTML & PRINT:

```
\begin{warpall}
```

\if@titlepage

Some classes do not provide \if@titlepage. In this case, provide it and force it false.

```
\ifcsvoid{@titlepagefalse}{
    \newif\if@titlepage
    \@titlepagefalse
}{}
```

```
\end{warpall}
```

69.3 Changes for \affiliation

\affiliation {⟨*text*⟩}

Adds the affiliation to the author for use in \maketitle.

Inside titlepage, this macro prints its argument. Outside, it is null.

for HTML & PRINT:

```
\begin{warpall}
\providerobustcmd{\affiliation}[1]{}
\end{warpall}
```

for PRINT output:

```
\begin{warpprint}

\AtBeginEnvironment{titlepage}{
\renewrobustcmd{\affiliation}[1]{\\ \textsc{\small#1}}
}

\AtBeginDocument{
\@ifpackageloaded{titling}{
\AtBeginEnvironment{titlingpage}{
\renewrobustcmd{\affiliation}[1]{\\ \textsc{\small#1}}
}
}{}% titling loaded
}% AtBeginDocument

\end{warpprint}
```

for HTML output:

```
\begin{warpHTML}
```

Env titlepage Sets up a of class titlepage. Provided even for memoir class, since it is used by \maketitle.

```
\DeclareDocumentEnvironment{titlepage}{}
{
\renewrobustcmd{\affiliation}[1]{\\ \InlineClass{affiliation}{##1}}
\LWR@printpendingfootnotes
\LWR@forcenewpage
\BlockClass{titlepage}
}
{
\endBlockClass
\LWR@printpendingfootnotes
}

\end{warpHTML}
```

69.4 Printing the thanks

\printthanks Forces the \thanks to be printed. This is necessary in a titlingpage environment when \maketitle was not used.

for PRINT output:

```
\begin{warpprint}
\newcommand*{\printthanks}{\@thanks}
\end{warpprint}
```

for HTML output:
```
\begin{warpHTML}
\newcommand*{\printthanks}{\LWR@stoppars\@thanks\LWR@startpars}
\end{warpHTML}
```

69.5 Printing the title, etc. in HTML

The following are for printing the title, etc. in a `titlepage` or a `titlingpage` in HTML:

for HTML output:
```
\begin{warpHTML}
```

`\printtitle`

```
\newcommand*{\printtitle}
{%
    \LWR@stoppars%
    \LWR@htmltag{\LWR@tagtitle}%
    \@title%
    \LWR@htmltag{\LWR@tagtitleend}%
    \LWR@startpars%
}
```

`\LWR@printthetitle` A private version which prints the title without footnotes, used to title each HTML page.

```
\newcommand*{\LWR@printthetitle}
{%
    \LWR@stoppars%
    \LWR@htmltag{\LWR@tagtitle}%
    \thetitle%
    \LWR@htmltag{\LWR@tagtitleend}%
    \LWR@startpars%
}
```

`\printauthor` HTML version.

```
\newcommand*{\printauthor}{
```

The entire author block is contained in a `<div>` named `author`:

```
\begin{BlockClass}{author}
```

`\and` finishes one author and starts the next:

```
\renewcommand{\and}{%
\end{BlockClass}
\begin{BlockClass}{oneauthor}
}
```

Individual authors are contained in a `<div>` named `oneauthor`:

```
\begin{BlockClass}{oneauthor}
\@author
```

```
\end{BlockClass}
\end{BlockClass}
}
```

\printdate

```
\newcommand*{\printdate}{%
\begin{BlockClass}{titledate}
\@date
\end{BlockClass}
}

\end{warpHTML}
```

69.6 Printing the title, etc. in print form

The following are for printing the title, etc. in a `titlepage` or a `titlingpage` in print form:

for PRINT output:

```
\begin{warpprint}
```

\printtitle

```
\newcommand*{\printtitle}{{\Huge\@title}}
```

\printauthor Print mode.

```
\newcommand*{\printauthor}
    {{\large\begin{tabular}[t]{c}\@author\end{tabular}}}
```

\printdate

```
\newcommand*{\printdate}{{\small\textit{\@date}}}

\end{warpprint}
```

69.7 `\maketitle` for HTML output

An HTML `<div>` of class `titlepage` is used.

`\thanks` are a form of footnotes used in the title page. See section 60 for other kinds of footnotes.

See `\thanksmarkseries{series}`, below, to set the style of the footnote marks.

for HTML output:

```
\begin{warpHTML}
```

```
\@ifclassloaded{memoir}
{
\newcommand{\LWR@setfootnoteseries}{%
    \renewcommand\thefootnote{\@arabic\c@footnote}%
}
}{% not memoir
\if@titlepage
\newcommand{\LWR@setfootnoteseries}{%
    \renewcommand\thefootnote{\@arabic\c@footnote}%
}
\else
\newcommand{\LWR@setfootnoteseries}{%
    \renewcommand\thefootnote{\@fnsymbol\c@footnote}%
}
\fi
}% not memoir
```

`\LWR@maketitlesetup` Patches `\thanks` macros.

```
\newcommand*{\LWR@maketitlesetup}{%
```

Redefine the footnote mark:

```
\LWR@setfootnoteseries%
\def\@makefnmark{%
    \textsuperscript{\thefootnote}%
}
```

`\thefootnote` ⇒ `\nameuse{arabic}{footnote}`, or
`\thefootnote` ⇒ `\nameuse{fnsymbol}{footnote}`

Redefine the footnote text:

```
\long\def\@makefntext##1{%
```

Make the footnote mark and some extra horizontal space for the tags:

```
\textsuperscript{\@thefnmark}~%
```

`\makethanksmark` ⇒ `\thanksfootmark` ⇒ `\tamark` ⇒ `\@thefnmark` ⇒ `\itshape` a (or similar)

Print the text:

```
##1%
}%
}
```

`\@fnsymbol` {⟨*counter*⟩}

Re-defined to use an HTML entity for the double vertical bar symbol. The original definition used `\|` which was not being seen by *pdftotext*.

```
\def\LWR@HTML@@fnsymbol#1{%
    \ifcase#1\or *\or
    \HTMLentity{dagger}\or
    \HTMLentity{Dagger}\or
    \HTMLentity{sect}\or
    \HTMLentity{para}\or
    \HTMLunicode{2016}\or
    **\or
    \HTMLentity{dagger}\HTMLentity{dagger} \or
    \HTMLentity{Dagger}\HTMLentity{Dagger} \else
    \@ctrerr\fi%
}
\LWR@formatted{@fnsymbol}
```

`\maketitle` HTML mode. Creates an HTML titlepage div and typesets the title, etc.

Code from the titling package is adapted, simplified, and modified for HTML output.

```
\renewcommand*{\maketitle}{%
```

An HTML titlepage is used for all classes.

```
\begin{titlepage}
```

Set up special patches:

```
\LWR@maketitlesetup
```

Typeset the title, etc:

```
\@maketitle
```

Immediately generate any `\thanks` footnotes:

```
\LWR@stoppars\@thanks\LWR@startpars
```

Close the HTML titlepage div and cleanup:

```
\end{titlepage}
\setcounter{footnote}{0}%
\global\let\thanks\relax
\global\let\maketitle\relax
\global\let\@maketitle\relax
\global\let\@thanks\@empty
\global\let\@author\@empty
\global\let\@date\@empty
\global\let\@title\@empty
\global\let\title\relax
\global\let\author\relax
\global\let\date\relax
\global\let\and\relax
```

```
}
```

`\@maketitle` HTML mode. Typesets the title, etc.:

```
\DeclareDocumentCommand{\@maketitle}{}{%
    \LWR@stoppars%
    \LWR@htmltag{\LWR@tagtitle}%
    \@title%
    \LWR@htmltag{\LWR@tagtitleend}%
    \LWR@startpars%
    \begin{BlockClass}{author}%
```

For IEEEtran class:

```
    \renewcommand*{\cr}{}%
    \renewcommand*{\crcr}{}%
    \renewcommand*{\noalign}{}%

        \renewcommand{\and}{%
            \end{BlockClass}%
            \begin{BlockClass}{oneauthor}%
        }%
        \begin{BlockClass}{oneauthor}%
            \@author%
        \end{BlockClass}%
    \end{BlockClass}%
    \begin{BlockClass}{titledate}%
    \@date%
    \end{BlockClass}%
}
```

`\LWR@titlingmaketitle` `\maketitle` for use inside an HTML `titlingpage` environment.

```
\newcommand*{\LWR@titlingmaketitle}{%
```

Keep pending footnotes out of the title block:

```
\LWR@stoppars\@thanks\LWR@startpars
```

Set up special patches:

```
\LWR@maketitlesetup
```

Typeset the title, etc:

```
\@maketitle
```

Immediately generate any `\thanks` footnotes:

```
\LWR@stoppars\@thanks\LWR@startpars
}

\end{warpHTML}
```

69.8 \published and \subtitle

\subtitle and \published

To add \subtitle and \published to the titlepage, load the titling package and use \AddSubtitlePublished in the preamble.

The default lwarp.css has definitions for the published and subtitle classes.

If titling is loaded, \AddSubtitlePublished creates a number of additional macros, and also assigns some of the titling hooks. If titling is not loaded, \AddSubtitlePublished creates null macros.

⚠ titling hooks

Do not use \AddSubtitlePublished if the user has patched the titling hooks for some other reason. Portions are marked \warpprintonly to reduce extra tags in HTML. Similarly, BlockClass has no effect in print mode. Thus, the following may be marked warpall.

for HTML & PRINT:

```
\begin{warpall}
```

\AddSubtitlePublished

Adds \published and \subtitle, and related.

```
\newcommand*{\AddSubtitlePublished}{%
\@ifpackageloaded{titling}{% yes titling package
    \newcommand{\@published}{}%
    \newcommand{\published}[1]{\gdef\@published{##1}}%
    \renewcommand*{\maketitlehooka}{\printpublished}%
    \newcommand*{\printpublished}{%
        \warpprintonly{\begin{center}\unskip}%
        \begin{BlockClass}{published}%
        \warpprintonly{\large\itshape}%
        \@published%
        \end{BlockClass}%
        \warpprintonly{\end{center}}%
    }%
    \newcommand{\@subtitle}{}%
    \newcommand{\subtitle}[1]{\gdef\@subtitle{##1}}%
    \renewcommand*{\maketitlehookb}{\printsubtitle}%
    \newcommand*{\printsubtitle}{%
        \warpprintonly{\begin{center}\unskip}%
        \begin{BlockClass}{subtitle}%
        \warpprintonly{\Large\itshape}%
        \@subtitle%
        \end{BlockClass}%
        \warpprintonly{\end{center}}%
    }%
}% yes titling package
{% no titling package

    \def\@published{}%
    \DeclareDocumentCommand{\published}{m}{\gdef\@published{##1}}%
    \DeclareDocumentCommand{\printpublished}{}{}%
    \def\@subtitle{}%
    \DeclareDocumentCommand{\subtitle}{m}{\gdef\@subtitle{##1}}%
    \DeclareDocumentCommand{\printsubtitle}{}{}%
}% no titling package
}% \AddSubtitlePublished
```

```
\end{warpall}
```

70 Abstract

The following code replaces the LaTeX default, and will itself be replaced later if the abstract package is loaded.

for HTML output:

```
\begin{warpHTML}
```

`\abstractname` User-redefinable title for the abstract.

Also over-written by the babel package.

```
\providecommand*{\abstractname}{Abstract}
```

Some classes allow an optional name, so it is allowed here.

Env `abstract`

```
\DeclareDocumentEnvironment{abstract}{O{\abstractname}}
{
    \LWR@forcenewpage
    \BlockClass{abstract}
    \BlockClassSingle{abstracttitle}{#1}
}
{
    \endBlockClass
}
```

```
\end{warpHTML}
```

71 Quote and verse

71.1 Attributions

`\attribution` {⟨*name*⟩}

For use with quote, quotation, verse:

Ex: `"A quotation." \attribution{\textsc{Author Name}\\\textsl{Book Title}}`

for HTML & PRINT:

```
\begin{warpall}
\newcommand{\attribution}[1]{
    \begin{flushright}
    \unskip
    #1
    \end{flushright}%
}
\end{warpall}
```

for HTML output:

```
\begin{warpHTML}
\newcommand{\LWR@HTML@attribution}[1]{%
    \LWR@stoppars%
    \begin{BlockClass}{attribution}
    #1
    \end{BlockClass}
    \LWR@startpars%
}
\LWR@formatted{attribution}
\end{warpHTML}
```

71.2 Quotes, quotations

for HTML output:

```
\begin{warpHTML}
```

Env quote

```
\newenvironment*{LWR@HTML@quote}
{
    \LWR@forcenewpage
    \LWR@htmlblocktag{blockquote}
}
{\LWR@htmlblocktag{/blockquote}}

\LWR@formattedenv{quote}
```

Env quotation

```
\newenvironment*{LWR@HTML@quotation}
{
    \LWR@forcenewpage
    \LWR@htmlblocktag{blockquote}
}
{\LWR@htmlblocktag{/blockquote}}

\LWR@formattedenv{quotation}

\end{warpHTML}
```

71.3 Verse

When using verse or memoir, always place a \\ after each line.

\attrib The documentation for the verse and memoir packages suggest defining an \attrib command, which may already exist in current documents, but it will only work for print output. lwarp provides \attribution, which works for both print and HTML output. To combine the two so that \attrib is used for print and \attribution is used for HTML:

```
\begin{warpHTML}
\let\attrib\attribution
\end{warpHTML}
```

Len \vleftskip
Len \vleftmargini
Len \HTMLvleftskip
Len \HTMLleftmargini

These lengths are used by verse and memoir to control the left margin, and they may already be set by the user for print output. New lengths \HTMLvleftskip and \HTMLleftmargini are provided to control the margins in HTML output. These new lengths may be set by the user before any verse environment, and persist until they are manually changed again. One reason to change \HTMLleftmargini is if there is a wide \flagverse in use, such as the word "Chorus", in which case the value of \HTMLleftmargini should be set to a wide enough length to contain "Chorus". The default is wide enough for a stanza number.

⚠ spacing

Horizontal spacing relies on *pdftotext*'s ability to discern the layout (-layout option) of the text in the HTML-tagged PDF output. For some settings of \HTMLleftmargini or \HTMLleftskip the horizontal alignment may not work out exactly, in which case a label may be shifted by one space. During translation to HTML, the stanza numbers are kept out of the left margin, which would have caused *pdftotext* to shift everything over.

⚠ verse margin

71.3.1 LaTeX core verse environment

for HTML output:

```
\begin{warpHTML}
```

Env verse

```
\newenvironment{LWR@HTML@verse}
               {\let\\\newline% lwarp
                \list{}{\itemsep      \z@
                        \itemindent   -1.5em%
                        \listparindent\itemindent
                        \rightmargin  \leftmargin
                        \advance\leftmargin 1.5em}%
                \item\relax}
               {\endlist}

\LWR@formattedenv{verse}

\end{warpHTML}
```

for HTML & PRINT:

```
\begin{warpall}
```

71.3.2 verse and memoir

The following lengths are used by verse and memoir. They may be set in either print or HTML output, but are only used in HTML. This allows the user to set \vleftskip and \leftmargini for print output, and optionally select different values for HTML.

Len \HTMLvleftskip

Sets \vleftskip inside a verse environment in HTML.

```
\newlength{\HTMLvleftskip}
\setlength{\HTMLvleftskip}{1em}
```

Len \HTMLleftmargini

Sets \leftmargini inside a verse environment in HTML.

```
\newlength{\HTMLleftmargini}
\setlength{\HTMLleftmargini}{4.5em}

\end{warpall}
```

72 Verbatim and tabbing

for HTML & PRINT:

```
\begin{warpall}
```

Len `\VerbatimHTMLWidth` Width to use in HTML `Verbatim` environment.

This width is used when placing line numbers to the right. Ignored during print output.

```
\newlength{\VerbatimHTMLWidth}
\setlength{\VerbatimHTMLWidth}{4in}
\end{warpall}
```

for HTML output:

```
\begin{warpHTML}
```

Bool `LWR@verbtags` Used to temporarily turn off verbatim tags while doing `\verbatiminput` in the HTML head.

```
\newbool{LWR@verbtags}
\booltrue{LWR@verbtags}
```

`\verb` Patched to encapsulate the verbatim text inside span with a class of `texttt`.

```
\LetLtxMacro\LWR@orig@verb@egroup\verb@egroup

\def\LWR@verb@egroup@endspan{%
    \LWR@orig@verb@egroup%
    \LWR@htmltag{/span}%
    \endgroup%
}

\xpretocmd{\verb}
    {%
        \begingroup%
        \LWR@htmltag{span class=\textquotedbl{}texttt\textquotedbl}%
        \let\verb@egroup\LWR@verb@egroup@endspan%
    }
    {}
    {\LWR@patcherror{LaTeX}{verb}}
```

`\LWR@atbeginverbatim` `[`⟨*1: style*⟩`]` `{`⟨*2: class*⟩`}`

Encloses a verbatim environment with the given CSS class.

The use of `\textquotedbl` instead of " improves compatibility with xeCJK.

```
\newcommand*{\LWR@atbeginverbatim}[2][]
{%
```

Stop generating HTML paragraph tags:

```
\LWR@stoppars%
```

Avoid excessive space between lines:

```
\setlength{\parskip}{0ex}%
\setlength{\topsep}{0pt}%
\setlength{\partopsep}{0pt}%
```

Inside the verbatim, temporarily prevent underfull \hbox warnings.

```
            \hbadness=10000\relax%
```

Create a new pre of the given class. The tags may temporarily be turned off for internal use, such as loading the MathJax script.

```
\ifbool{LWR@verbtags}{%
    \LWR@htmltag{pre class=\textquotedbl#2\textquotedbl%
        \ifthenelse{\equal{#1}{}}{}{ style=\textquotedbl#1\textquotedbl}%
    }%
    \par%
}{}%
```

Use a mono-spaced font to preserve horizontal positioning. If horizontal alignment is important for the user, use a mono-spaced font in the CSS for the verse class.

```
\begingroup%
```

```
\LWR@print@normalfont%
\LWR@origttfamily%
\LWR@print@scriptsize%
```

Since inside a <pre>, restore the original list processing:

```
\LWR@restoreoriglists%
```

Turn off babel-french extra space before punctuation:

```
\LWR@hook@processingtags%
```

Do not produce HTML tags for \hspace inside a verse par. Restore plain LaTeX \hspace functionality:

```
\LWR@select@print@hspace%
}
```

\LWR@afterendverbatim Finishes enclosing a verbatim environment.

```
\newcommand*{\LWR@afterendverbatim}{%
\endgroup%
\par%
```

At the end of the environment, close the pre:

```
\ifbool{LWR@verbtags}{%
    \noindent\LWR@htmltag{/pre}\par% pre
}{}%
```

Resume regular paragraph handling:

```
\LWR@startpars%
}
```

`\verbatiminput` {⟨*filename*⟩}

Patch `\verbatiminput` to add HTML tags:

```
\newcommand{\LWR@HTML@verbatim@input}[2]{%
    \ifbool{LWR@verbtags}{\LWR@forcenewpage}{}%
    \LWR@atbeginverbatim{Verbatim}%
    \LWR@print@verbatim@input{#1}{#2}%
    \LWR@afterendverbatim%
}

\LWR@formatted{verbatim@input}
```

Env `verbatim`

```
\AfterEndPreamble{
\LWR@traceinfo{Patching verbatim.}
\AtBeginEnvironment{verbatim}{%
    \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
        {}%
        {%
            \LWR@forcenewpage%
            \LWR@atbeginverbatim{verbatim}%
        }%
}
\AfterEndEnvironment{verbatim}{%
    \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
        {}%
        {%
            \LWR@afterendverbatim%
        }%
}
}
```

Env `tabbing` The `tabbing` environment works, except that SVG math and `latexmages` do not yet work inside the environment.

⚠ math in `tabbing` If math is used inside `tabbing`, place `tabbing` inside a `latexmage` environment, which will render the entire environment as a single SVG image.

```
\newcommand*{\LWR@HTML@tabbing}{%
    \LWR@forcenewpage%
```

```
    \LWR@atbeginverbatim{tabbing}%
    \let\enskip\LWR@origenskip%
    \let\quad\LWR@origquad%
    \let\qquad\LWR@origqquad%
    \let~\LWR@origtilde%
    \let\,\LWR@origcomma%
    \let\thinspace\LWR@origthinspace%
    \let\negthinspace\LWR@orignegthinspace%
    \LWR@print@tabbing%
}

\newcommand*{\LWR@HTML@endtabbing}{%
    \LWR@print@endtabbing%
    \LWR@afterendverbatim%
}

\LWR@formatted{tabbing}
\LWR@formatted{endtabbing}

\end{warpHTML}
```

73 Theorems

`\newtheorem` `{`⟨*text*⟩`}` `[`⟨*counter*⟩`]` — *or* — `[`⟨*oldname*⟩`]` `{`⟨*text*⟩`}`

A few minor changes are made to supply HTML tags.

- The entire theorem is placed into a `<div>` of class `theoremcontents`.
- The label for each theorem is placed inside a `<span>` of class `theoremlabel`.
- The contents are placed inside a `<div>` of class theoremcontents.

for HTML output:

```
\begin{warpHTML}
```

`\@begintheorem` `{`⟨*name*⟩`}` `{`⟨*number*⟩`}`

```
\renewcommand{\@begintheorem}[2]{%
\LWR@forcenewpage

    \LWR@printpendingfootnotes%                    lwarp

\BlockClass{theoremcontents}
\trivlist
\item[\InlineClass{theoremlabel}{#1\ #2\ }]\itshape
}
```

`\@opargbegintheorem` `{`⟨*name*⟩`}` `{`⟨*number*⟩`}` `{`⟨*oparg*⟩`}`

LaTeX defines this, but amsthm \relaxes it, so it will not be defined if amsthm is loaded before lwarp.

```
\ifundef{\@opargbegintheorem}{}{
    \renewcommand{\@opargbegintheorem}[3]{%
        \LWR@forcenewpage
        \BlockClass{theoremcontents}
        \trivlist
        \item[\InlineClass{theoremlabel}{#1\ #2\ (#3)\ }]\itshape
    }
}
```

\@endtheorem

```
\renewcommand*{\@endtheorem}{%
\endtrivlist

    \LWR@printpendingfootnotes%                    lwarp

\endBlockClass% theoremcontents
}

\end{warpHTML}
```

74 Lists

The environments itemize, enumerate, and description are patched when lwarp is started. These patches support the standard LaTeX environments, as well as those of enumerate, enumitem, and paralist, and at least the French version of babel. Additional patches are done on a package-specific basis.

The LaTeX source for itemize and enumerate are found in source2e, but the source for description is found in article.cls, etc.

empty item

To have an empty item,use \mbox{} or a trailing backslash. This forces a new line in print output, matching the new line which will appear in HTML output. Ex:

```
begin{itemize}
item \mbox{}
    \begin{itemize}
...
    \end{itemize}
item \
    \begin{itemize}
  ...
    \end{itemize}
```

\makelabel

While inside a list environment, lwarp nullifies a number of TeX horizontal skip and fill

commands, allowing the user to define \makelabel for print mode while HTML mode ignores those commands.

⚠ label font When defining \makelabel in a list environment, use \textbf etc. instead of \bfseries.

74.1 List environment

for HTML output:

```
\begin{warpHTML}
```

\LWR@printcloselist May be locally redefined by enumerate or description.

```
\newcommand*{\LWR@printcloselist}{\LWR@printcloseitemize}
```

\LWR@printopenlist May be locally redefined by enumerate or description.

```
\newcommand*{\LWR@printopenlist}{%
   ul style=\textquotedbl\LWR@print@mbox{list-style-type:none}\textquotedbl{}%
}
```

\@mklab Removes PDF spacing.

```
\AtBeginDocument{
\def\@mklab#1{%
%     \hfil %
    #1}
\let\makelabel\@mklab
}
```

\@donoparitem Modified for HTML output by replacing TEX boxes with plain text. Also removes PDF spacing.

```
\def\@donoparitem{%
  \@noparitemfalse
%   \global\setbox\@labels\hbox{\hskip -\leftmargin
%                                \unhbox\@labels
%                                 \hskip \leftmargin}%
%   \if@minipage\else
%     \@tempskipa\lastskip
%     \vskip -\lastskip
%     \advance\@tempskipa\@outerparskip
%     \advance\@tempskipa -\parskip
%     \vskip\@tempskipa
%   \fi
}
```

\@item Modified for HTML output by replacing TEX boxes with plain text. Also removes PDF spacing.

```
\def\LWR@HTML@item[#1]{%
\LWR@traceinfo{@item}%
```

```
  \if@noparitem
    \@donoparitem
  \else
%     \if@inlabel
%       \indent
        \par
%     \fi
    \ifhmode
%       \unskip\unskip
        \par
    \fi
    \if@newlist
      \if@nobreak
        \@nbitem
      \else
%         \addpenalty\@beginparpenalty
%         \addvspace\@topsep
%         \addvspace{-\parskip}%
      \fi
    \else
%       \addpenalty\@itempenalty
%       \addvspace\itemsep
    \fi
    \global\@inlabeltrue
  \fi
%   \everypar{%
    \@minipagefalse
    \global\@newlistfalse

%     \if@inlabel
%       \global\@inlabelfalse

%       {\setbox\z@\lastbox
%        \ifvoid\z@
%          \kern-\itemindent
%        \fi}%

%       \box\@labels
%       \penalty\z@
%     \fi

%     \if@nobreak
%       \@nobreakfalse
%       \clubpenalty \@M
%     \else
%       \clubpenalty \@clubpenalty
%       \everypar{}%
%     \fi}%

  \if@noitemarg
    \@noitemargfalse
    \if@nmbrlist

      \refstepcounter\@listctr
    \fi
```

```
  \fi

    \makelabel{#1} % extra space
%   \sbox\@tempboxa{\makelabel{#1}%
%   \global\setbox\@labels\hbox{%
%     \unhbox\@labels
%     \hskip \itemindent
%     \hskip -\labelwidth
%     \hskip -\labelsep
%     \ifdim \wd\@tempboxa >\labelwidth
%       \box\@tempboxa

%     \else
%       \hbox to\labelwidth {\unhbox\@tempboxa}%
%     \fi
%     \hskip \labelsep}%
  \ignorespaces%
}
```

\@nbitem

```
\def\@nbitem{%
%   \@tempskipa\@outerparskip
%   \advance\@tempskipa -\parskip
%   \addvspace\@tempskipa
}
```

\LWR@listitem [⟨*label*⟩]

Handles \item inside a list, itemize, or enumerate.

See \LWR@openparagraph where extra \hspace is used to leave room for the label while inside a list during paragraph construction.

```
\newcommand*{\LWR@listitem}{%
\LWR@stoppars%
\LWR@startnewdepth{listitem}%
\LWR@htmltag{li}%
\LWR@startpars%
\LWR@origitem%
}
```

\LWR@nulllistfills Nullifies various TEX fill commands, in case they are used inside \makelabel. Problems are caused when these are nullified all the time.

```
\newcommand*{\LWR@nulllistfills}{%
\renewcommand*{\hss}{}%
\renewcommand*{\llap}[1]{##1}%
\renewcommand*{\rlap}[1]{##1}%
\renewcommand*{\hfil}{}%
\renewcommand*{\hfilneg}{}%
\renewcommand*{\hfill}{}%
}
```

Env `list` {⟨*label*⟩} {⟨*commands*⟩}

```
\newcommand*{\LWR@liststart}{%
\LWR@traceinfo{LWR@liststart}%
\LWR@stoppars%
\LWR@pushoneclose{list}%
\LWR@htmltag{\LWR@printopenlist}\LWR@orignewline%
\LWR@startpars%
\setlength{\topsep}{0pt}%
\setlength{\partopsep}{0pt}%
\setlength{\itemsep}{0pt}%
\setlength{\parsep}{0pt}%
\setlength{\leftmargin}{0pt}%
\setlength{\rightmargin}{0pt}%
\setlength{\listparindent}{0pt}%
\setlength{\itemindent}{0pt}%
\setlength{\labelsep}{1em}%
\LWR@nulllistfills%
}

\newcommand*{\LWR@listend}{%
\LWR@traceinfo{LWR@listend}%
\LWR@stoppars%
\LWR@closeprevious{list}%
\LWR@startpars%
}
```

74.2 Itemize

`\LWR@itemizeitem` [⟨*label*⟩]

Handles `\item` inside an itemize or enumerate.

See `\LWR@openparagraph` where extra `\hspace` is used to leave room for the label while inside a list during paragraph construction.

```
\newcommand*{\LWR@itemizeitem}{%
\LWR@stoppars%
\LWR@startnewdepth{listitem}%
\LWR@htmltag{li}%
\LWR@startpars%
\LWR@origitem%
}
```

Env `itemize` [⟨*options*⟩]

```
\newcommand*{\LWR@itemizestart}{%
\renewcommand*{\LWR@printcloselist}{\LWR@printcloseitemize}
\renewcommand*{\LWR@printopenlist}{%
   ul style=\textquotedbl\LWR@print@mbox{list-style-type:none}\textquotedbl{}%
}
\let\item\LWR@itemizeitem%
\LWR@nulllistfills%
}
```

74.3 Enumerate

An HTML unordered list is used with customized LaTeX-generated labels.

Env `enumerate` [⟨*options*⟩]

```
\newcommand*{\LWR@enumeratestart}{%
\renewcommand*{\LWR@printcloselist}{\LWR@printcloseitemize}
\renewcommand*{\LWR@printopenlist}{%
   ul style=\textquotedbl\LWR@print@mbox{list-style-type:none}\textquotedbl{}%
}
\let\item\LWR@itemizeitem%
\LWR@nulllistfills%
}
```

74.4 Description

`\LWR@descitem` [⟨*label*⟩] Handles an `\item` inside a description.

```
\newcommand*{\LWR@descitem}[1][]%
{%
\LWR@stoppars%
\LWR@setlatestname{#1}%
\LWR@startnewdepth{descitem}%
```

While creating the label, encase it inside tags and disable `\hspace`, which is used by the standard classes to add space to the labels.

```
\begingroup%
\let\LWR@orig@desc@makelabel\makelabel
\renewcommand*{\makelabel}[1]{%
    \LWR@htmltag{dt}%
    \LWR@orig@desc@makelabel{#1}%
    \LWR@htmltag{/dt}%
}
\LWR@select@html@nohspace%
\LWR@origitem[#1]%
\endgroup%
\LWR@orignewline%
\LWR@htmltag{dd}%
\LWR@startpars%
}
```

Env `description` [⟨*options*⟩]

Footnotes are modified to correctly parse optional arguments.

```
\newcommand*{\LWR@descriptionstart}{%
    \renewcommand*{\LWR@printcloselist}{\LWR@printclosedescription}
    \renewcommand*{\LWR@printopenlist}{dl}
    \let\item\LWR@descitem%
    \LWR@nulllistfills%
```

Footnotes are redefined to process optional arguments inside the `description` label. A `\footnote` is dropped, as it is in print mode. Using the optional arguments does not work in print mode, but for some reason they must be accepted as done here to work correctly even without the optional arguments.

```
    \renewcommand{\footnote}[2][]{%
        \ifblank{##1}%
        {%
            \stepcounter\@mpfn
            \protected@xdef\@thefnmark{\thempfn}%
            \@footnotemark%\@footnotetext
        }%
        {%
            \begingroup
            \csname c@\@mpfn\endcsname ##1\relax
            \unrestored@protected@xdef\@thefnmark{\thempfn}%
            \endgroup
            \@footnotemark%\@footnotetext
        }%
    }%
    %
    \renewcommand{\footnotemark}[1][]{%
        \ifblank{##1}%
        {%
            \stepcounter{footnote}%
            \protected@xdef\@thefnmark{\thefootnote}%
            \@footnotemark%
        }%
        {%
            \begingroup%
            \c@footnote ##1\relax%
            \unrestored@protected@xdef\@thefnmark{\thefootnote}%
            \endgroup%
            \@footnotemark%
        }%
    }%
}
```

74.5 Patching the lists

`\LWR@patchlists` Patches list environments.

`\LWR@patchlists` remembers `\item` as defined by whatever packages have been loaded, then patches the `itemize`, `enumerate`, and `description` environments and `\item`. This works with the native LaTeX environments, as well as those provided by enumitem, enumerate, and paralist.

```
\newcommand*{\LWR@patchlists}{%
    \LetLtxMacro\item\LWR@listitem%
    \LetLtxMacro\@item\LWR@HTML@item%
    \renewcommand*{\@trivlist}{%
        \LWR@traceinfo{@trivlist start}%
        \LWR@liststart%
```

```
        \LWR@orig@trivlist%
        \LWR@traceinfo{@trivlist done}%
    }%
    \renewcommand*{\trivlist}{%
        \LWR@traceinfo{trivlist}%
        \LWR@origtrivlist%
    }%
    \renewcommand*{\endtrivlist}{%
        \LWR@traceinfo{endtrivlist start}%
        \LWR@origendtrivlist\LWR@listend%
        \LWR@traceinfo{endtrivlist done}%
    }%
    \renewcommand*{\itemize}{%
        \LWR@itemizestart\LWR@origitemize%
    }%
    \renewcommand*{\enumerate}{%
        \LWR@enumeratestart\LWR@origenumerate%
    }%
    \renewcommand*{\description}{%
        \LWR@descriptionstart\LWR@origdescription%
    }%
}
```

`\LWR@restoreoriglists` Restores the original `trivlist` environment.

```
\newcommand*{\LWR@restoreoriglists}{%
    \LWR@traceinfo{LWR@restoreoriglists}%
    \LetLtxMacro\item\LWR@origitem%
    \LetLtxMacro\@item\LWR@orig@item%
    \let\@trivlist\LWR@orig@trivlist%
    \let\trivlist\LWR@origtrivlist%
    \let\endtrivlist\LWR@origendtrivlist%
    \LetLtxMacro\itemize\LWR@origitemize%
    \LetLtxMacro\enditemize\LWR@endorigitemize%
    \LetLtxMacro\enumerate\LWR@origenumerate%
    \LetLtxMacro\endenumerate\LWR@endorigenumerate%
    \LetLtxMacro\description\LWR@origdescription%
    \LetLtxMacro\enddescription\LWR@endorigdescription%
    \let\@mklab\LWR@orig@mklab%
    \let\makelabel\LWR@origmakelabel%
    \let\@donoparitem\LWR@orig@donoparitem%
    \let\@nbitem\LWR@orig@nbitem%
}

\end{warpHTML}
```

75 Tabular

This is arguably the most complicated part of the entire package. Numerous tricks are employed to handle the syntax of the LaTeX core and the various tabular-related packages.

75.1 Limitations

Tabular mostly works as expected, but pay special attention to the following, especially if working with environments, macros inside tabulars, multirows, siunitx S columns, or the packages multirow, longtable, supertabular, or xtab.

Defining macros and environments:

⚠ Misplaced alignment tab character &

- When defining environments or macros which include `tabular` and instances of the & character, it may be necessary to make & active before the environment or macro is defined, then restore & to its default catcode after, using the following commands. These are are ignored in print mode.

```
\StartDefiningTabulars
<define macros or environments using tabular and & here>
\StopDefiningTabulars
```

⚠ floatrow

This includes before and after defining any macro which used `\ttabbox` from floatrow.

⚠ `tabular` inside another environment

- When creating a new environment which contains a `tabular` environment, lwarp's emulation of the tabular does not automatically resume when the containing enviroment ends, resulting in corrupted HTML rows. To fix this, use `\ResumeTabular` as follows. This is ignored in print mode.

```
\StartDefiningTabulars %   (& is used in a definition)
\newenvironment{outerenvironment}
{
  \tabular{cc}
  left & right \\
}
{
  \TabularMacro\ResumeTabular
  left & right \\
  \endtabular
}
\StopDefiningTabulars
```

For developers:

- To automate the use of `\StartDefiningTabulars` and `\EndDefiningTabulars`, these macros may be embedded inside an HTML environment definition to automatically change the catcode of & before absorbing the arguments. Another environment may be embedded as well.

```
% Does the work after the catcode has been changed:
\newcommand*{\LWR@HTML@subsomename}[2]{%
  . . .
  \otherenvironmentname [<args>] {<args>}  % for example
}
% Change catcode before absorbing arguments:
\newcommand*{\LWR@HTML@somename{%
  \StartDefiningTabulars
  \LWR@HTML@subsomename
}
% Change catcode again at the end:
\newcommand*{\LWR@HTML@endsomename}{%
  . . .
  \endotherenvironmentname   % for example
  \StopDefiningTabulars
}
% Combine with the existing print definition:
\LWR@formattedenv{somename}
```

Cell contents:

⚠ macro in a table

- Using a custom macro inside a tabular data cell may result in an extra HTML data cell tag, corrupting the HTML table. To avoid this, use `\TabularMacro` just before the macro. This is ignored in print mode.

```
\TabularMacro\somemacro & more row contents \\
```

Column specifiers:

`@` and `!`

- Only one each of `@` and `!` is used at each column, and they are used in that order.

`\multirow`

- In `\multirow` cells, the print version may have extra instances of <, >, `@`, and `!` cells on the second and later rows in the `\multirow` which do not appear in the HTML version.

⚠ `\newcolumntype`

- `\newcolumntype` is ignored; unknown column types are set to `l`.

Rules:

- Doubled `\hlines`, `\midrules`, and vertical rules are supported.

vertical rules

- Vertical rules next to either side of an `@` or `!` column are displayed on both sides of the column.

width and trim

- Width options are honored. Trim options are converted to rounded top corners. Trim corners are not rounded with `@` or `!` columns, and full-width rules ignore trim. When given an optional width, each cell is styled to create the custom border. Without an optional width, the entire row is given a class to assign the standard border.

combined rules

- If you wish to use `\cmidrule` followed by `\bottomrule`, it may be necessary to use:

```
\cmidrule{2-3} \\[-2ex]
\bottomrule
```

The optional `-2ex` is ignored in HTML, but improves the visual formatting in the print output.

⚠ \warpprintonly
⚠ Misplaced \noalign

- For \toprule and \bottomrule, when combined with a warpprint or warpHTML environment, if a "Misplaced \noalign" error occurs, change

  ```
  This & That \endhead
  ```

  to

  ```
  \warpprintonly{This & That \endhead}
  ```

  and likewise with the other \end headings. Keep the \endfirsthead row unchanged, as it is still relevent to HTML output.

Other:

- tabularx ignores the width, but X columns do produce paragraph columns or multicolumns.

longtable headings

- For longtable, place headings and footings which do not apply to HTML inside \warpprintonly{}.

⚠ S columns

- For S columns (from the siunitx package), while producing print output, anything non-numeric must be placed inside { } braces, including commands such as \multirow. While producing HTML output, though, anything placed inside braces is not seen by lwarp's tabular handling algorithm. To resolve this problem, make a copy of the row, with one version for print output, containing the extra braces, and another version for HTML output, without the extra braces, such as:

  ```
  \warpprintonly{1 & 2 & {\multirow{2}{2cm}{Text}} & 3 \\}
  \warpHTMLonly{1 & 2 & \multirow{2}{2cm}{Text} & 3 \\}
  ```

⚠ tabular inside a

- In LaTeX, a tabular may be placed inside a minipage, but in HTML a <table> may not be inside a . If this situation is detected, a warning is printed instructing the user to isolate the using \warpprintonly or the warpprint environment.

for HTML output:

```
\begin{warpHTML}
```

75.2 Temporary package-related macros

These macros are temporary placeholders for macros defined by various packages. If the relevent package is not loaded, these placeholders are used instead.

75.2.1 arydshln

Emualated by the original LaTeX non-dashed versions.

```
\LetLtxMacro\hdashline\hline
\LetLtxMacro\cdashline\cline
\LetLtxMacro\firsthdashline\hline
\LetLtxMacro\lasthdashline\hline
```

75.3 Token lookahead

Used by \LWR@futurenonspacelet to look at the next token.

\LWR@mynexttoken

```
\newcommand\LWR@mynexttoken\relax
```

\futurelet copies the next token then executes a function to analyze it.

\LWR@futurenonspacelet does the same, but ignores intervening white space

Based on the booktabs style:

\LWR@futurenonspacelet

```
\def\LWR@futurenonspacelet#1{\def\LWR@cs{#1}%
\afterassignment\LWR@fnslone\let\nexttoken= }

\def\LWR@fnslone{\expandafter\futurelet\LWR@cs\LWR@fnsltwo}

\def\LWR@fnsltwo{%
\expandafter\ifx\LWR@cs\@sptoken\let\next=\LWR@fnslthree%
\else\let\next=\nexttoken\fi\next}

\def\LWR@fnslthree{\afterassignment\LWR@fnslone\let\next= }
```

\LWR@getmynexttoken Looks ahead and copies the next token into \LWR@mynexttoken.

```
\newcommand*{\LWR@getmynexttoken}{%
    \LWR@traceinfo{LWR@getmynexttoken}%
% nothing must follow this next line
    \LWR@futurenonspacelet\LWR@mynexttoken\LWR@tabledatacolumntag
}
```

75.4 Tabular variables

In order to support nested tabulars, each of these is used locally. For local counters, etoolbox's \defcounter and lwarp's new \defaddtocounter are used.

Bool LWR@startedrow True if should print a row tag before this column.

```
\newbool{LWR@startedrow}
\boolfalse{LWR@startedrow}
```

Bool LWR@tabularcelladded True if have added a data cell for this position.

```
\newbool{LWR@tabularcelladded}
\boolfalse{LWR@tabularcelladded}
```

Ctr LWR@hlines Number of \hlines or \midrules above the next row.

```
\newcounter{LWR@hlines}
```

Ctr LWR@hdashedlines Number of arydshln dashed lines above the next row.

```
\newcounter{LWR@hdashedlines}
```

Bool LWR@doingtbrule — True if the next row will have a top/bottom rule above it.

```
\newbool{LWR@doingtbrule}
\boolfalse{LWR@doingtbrule}
```

Bool LWR@doingcmidrule — True if the next row will have a cmidrule above it.

This is used by \LWR@tabularfinishrow to force a final empty row to create the border for the \cmidrule.

```
\newbool{LWR@doingcmidrule}
\boolfalse{LWR@doingcmidrule}
```

Bool LWR@tableparcell — True if are handling a paragraph inside a table cell, so must close the paragraph tag before moving on.

```
\newbool{LWR@tableparcell}
```

Bool LWR@skippingmrowcell — True if are doing an empty \multirow cell, and thus there is no data tag to close.

```
\newbool{LWR@skippingmrowcell}
```

Bool LWR@skippingmcolrowcell — True if are doing an empty \multicolumnrow cell, and thus there is no data tag to close, and do not print @ and ! columns.

```
\newbool{LWR@skippingmcolrowcell}
```

Bool LWR@usedmultirow — Used to error if used \multirow or \multicolumnrow without using \mrowcell or \mcolrowcell.

```
\newbool{LWR@usedmultirow}
```

Bool LWR@foundmrowcell — Used to error if used \multirow or \multicolumnrow without using \mrowcell or \mcolrowcell.

```
\newbool{LWR@foundmrowcell}
```

Bool LWR@skipatbang — True if just finished a \multicolumn so should not create the trailing @ or ! columns table data cells.

```
\newbool{LWR@skipatbang}
```

Bool LWR@emptyatbang — True if finishing a row and should print empty @ or ! column table data cells.

```
\newbool{LWR@emptyatbang}
```

Bool LWR@intabularmetadata — True if are in a tabular but not in a data cell. Used to prevent extra HTML breaks if not inside table data.

```
\newbool{LWR@intabularmetadata}
\boolfalse{LWR@intabularmetadata}
```

Bool LWR@exitingtabular — When \end is found, turns off the next opening data tag.

```
\newbool{LWR@exitingtabular}
```

Bool LWR@tabularmutemods Mutes HTML output for @, !, < and >.

This is used while printing the final row to generate \bottomrules.

```
\newbool{LWR@tabularmutemods}
```

Bool LWR@validtablecol True if found a valid table column type.

```
\newbool{LWR@validtablecol}
```

Bool LWR@opttablecol True if found a table column optional argument.

```
\newbool{LWR@opttablecol}
```

Used to add a style to a table data cell:

```
\newbool{LWR@tdhavecellstyle}
```

Ctr LWR@tabularDepth Tracks whether & is being used inside a tabular.

```
\newcounter{LWR@tabulardepth}
\setcounter{LWR@tabulardepth}{0}
```

Ctr LWR@tabularpardepth Tracks whether should look ahead at the next token when encountering a \par while processing tabular contents.

When LWR@tabularpardepth is deeper than LWR@tabulardepth then lwarp has started looking at the contents of the tabular, and thus any \pars encountered must be followed by another token lookahead.

```
\newcounter{LWR@tabularpardepth}
\setcounter{LWR@tabularpardepth}{0}
```

```
\newcommand*{\LWR@colsresult}{}%temp storage for column format results
\newcommand*{\LWR@pposition}{}
\newcommand*{\LWR@pleft}{}
\newcommand*{\LWR@pright}{}
```

LWR@tablecolspec Holds the parsed column specification, of total width LWR@tabletotalLaTeXcols, not counting @ and ! columns.

Will contain a string such as llrrccpc, exactly one letter per LaTeX table column, without @, !, >, <, or the vertical bar.

\LWR@strresult Holds the result of Str functions.

```
\providecommand*{\LWR@strresult}{}
\providecommand*{\LWR@strresulttwo}{}
```

\LWR@origcolspec Holds the original column specs given to tabular.

```
\newcommand*{\LWR@origcolspec}{}
```

Ctr LWR@tablecolspecwidth — Holds the number of tokens in the table columns specification.

This is includes one for each @, !, <, > column, and also one for each of the parameters of p, @, !, <, > columns, and three for each D column.

(This is not the total # of LaTeX columns in the table.)

```
\newcounter{LWR@tablecolspecwidth}
```

Ctr LWR@tablecolspecindex — While parsing the LaTeX table column specification, starts at 1 and is incremented per token of the specification.

```
\newcounter{LWR@tablecolspecindex}
```

Ctr LWR@tableLaTeXcolindex — While producing the table, resets to 1 at the start of the table and also at each end of line, and is incremented by 1 by each ampersand.

```
\newcounter{LWR@tableLaTeXcolindex}
```

Ctr LWR@tabletotalLaTeXcols — While parsing a table column specification, begins at 0 and increments by 1 per LaTeX table column. Eventually holds the final number of LaTeX table columns in each row, not counting @ and ! columns. (In HTML, @ and ! cells become their own columns, but are not included in LWR@tabletotalLaTeXcols.)

```
\newcounter{LWR@tabletotalLaTeXcols}
```

Ctr LWR@tabletotalLaTeXcolsnext — Holds the next LaTeX table column index while parsing, equal to one more than LWR@tabletotalLaTeXcols.

```
\newcounter{LWR@tabletotalLaTeXcolsnext}
```

LWR@colatspec — A data array of specifications for @ columns. The leftmost's index is leftedge, the others are counter values. See section 42.

LWR@colbangspec — A data array of specifications for ! columns. The leftmost's index is leftedge, the others are counter values. See section 42.

LWR@colbeforespec — A data array of specifications for > columns.

LWR@colafterspec — A data array of specifications for < columns.

LWR@colbarspec — A data array of specifications for vertical rules.

Ctr LWR@cellcolordepth — Counts how many cell color s were added to the current tabular data cell.

```
\newcounter{LWR@cellcolordepth}
```

75.4.1 Multicolumn variables

```
\newcounter{LWR@tablemulticolswidth}
```

Indexes into the multicolumn specification:

```
\newcounter{LWR@tablemulticolspos}
```

Remembers multicolumn vertical rules if found in the column spec.

```
\newcounter{LWR@mcolvertbarsl}
\newcounter{LWR@mcolvertbarsr}
\newcounter{LWR@mcolvertbarsldash}
\newcounter{LWR@mcolvertbarsrdash}
\newbool{LWR@mcolvertbaronleft}
```

75.4.2 Longtable variables

Bool `LWR@starredlongtable` Per the caption package, step the counter if `longtable*`.

```
\newbool{LWR@starredlongtable}
\boolfalse{LWR@starredlongtable}
```

75.4.3 Midrule variables

Ctr `LWR@midrulecounter` Indexes across the `LWR@midrules` and `LWR@trim<l/r>rules` data arrays.

```
\newcounter{LWR@midrulecounter}
```

75.5 Handling &, @, !, and bar

For technical discussion regarding problems redefining \&, See:
http://tex.stackexchange.com/questions/11638/where-do-i-find-futurelets-nasty-behaviour-documented/11860#11860

`\LWR@instertatbangcols`

```
\newcommand*{\LWR@insertatbangcols}{%
    \ifbool{LWR@skipatbang}%
    {}%
    {%
        \LWR@printatbang{at}{\arabic{LWR@tableLaTeXcolindex}}%
        \LWR@printatbang{bang}{\arabic{LWR@tableLaTeXcolindex}}%
    }%
}
```

`\LWR@closetabledatacell` If `LWR@skippingmrowcell` or `LWR@skippingmcolrowcell` then there is no data tag to close. Otherwise, close any paragraphs, then close the data tag.

```
\newcommand*{\LWR@closetabledatacell}{%
    \booltrue{LWR@intabularmetadata}%
    \ifbool{LWR@exitingtabular}%
    {%

        \LWR@stoppars%
```

```
    }%
    {% not exiting tabular
      \ifboolexpr{bool{LWR@skippingmrowcell} or bool{LWR@skippingmcolrowcell}}%
        {%

            \LWR@stoppars%
```

If not skipping a `\multicolumnrow` cell, insert the `@` and `!` columns after this non-existant column.

```
            \ifbool{LWR@skippingmcolrowcell}%
                {}%
                {\LWR@insertatbangcols}%
        }%
        {% not skippingmrowcell
```

Insert any `<` then any `@` and `!` column contents, unless muted for the `\bottomrule` or a `\multicolumn`:

```
            \unskip%
            \ifboolexpr{%
                bool{LWR@tabularmutemods} or
                bool{LWR@skipatbang} or
                bool{LWR@emptyatbang}
            }%
                {}%
                {%
                    \LWR@getexparray{LWR@colafterspec}%
                        {\arabic{LWR@tableLaTeXcolindex}}%
                }%
```

Close paragraphs:

```
            \LWR@stoppars%
            \boolfalse{LWR@tableparcell}%
```

Close the table data cell.

Close any color `<div>`s.

```
          \whileboolexpr{test {\ifnumcomp{\value{LWR@cellcolordepth}}{>}{0}}}{%
                \LWR@htmltag{/div}\LWR@orignewline%
                \defaddtocounter{LWR@cellcolordepth}{-1}%
            }%
```

Skip the `@` and `!` cells if are closing a multicolumn cell.

```
            \leavevmode\unskip\LWR@htmltag{/td}\LWR@orignewline%
            \global\booltrue{LWR@tabularcelladded}%
            \LWR@insertatbangcols%
        }% not skipping mrowcell
    }% not exiting tabular
    \boolfalse{LWR@skippingmrowcell}%
    \boolfalse{LWR@skippingmcolrowcell}%
    \boolfalse{LWR@skipatbang}%
```

Color control. Column is set by >{} for each cell, so it must be cleared here.

```
    \def\LWR@cellHTMLcolor{}%
    \def\LWR@columnHTMLcolor{}%
    \defcounter{LWR@cellcolordepth}{0}%
}
```

When not used inside a tabular, & performs its original function as recorded here (with catcode 4).

```
\let\LWR@origampmacro&
```

```
\end{warpHTML}
```

75.5.1 Handling &

for HTML output:

```
\begin{warpHTML}
```

& Will behave depending on whether it is being used inside tabular.

& is redefined to test whether it is inside a tabular environment, in which case it performs special processing for HTML conversion. If not, it behaves normally.

```
\newcommand*{\LWR@tabularampersand}{%
    \LWR@traceinfo{LWR@tabularampersand}%
    \ifnumcomp{\value{LWR@tabulardepth}}{>}{0}%
    {%
```

If not skipping a multirow cell, close the current data cell.

```
        \unskip%
        \LWR@closetabledatacell%
```

Move to the next column.

```
        \defaddtocounter{LWR@tableLaTeXcolindex}{1}%
```

Have not yet added data in this column:

```
        \global\boolfalse{LWR@tabularcelladded}%
```

Look at the next token to decide multi or single column data tag.

```
        \LWR@getmynexttoken%
    }%
```

If not inside a tabular, performs the original action:

```
    {%
        \LWR@origampmacro%
    }%
}
```

& is left with its original catcode for now.

tikz package seems to require & be left alone until after tikz has been loaded. Also, cleveref uses the ampersand in one of its options.

& is made active inside a `tabular`.

& is left alone when in math alignments.

75.5.2 Filling an unfinished row

`\LWR@tabularfinishrow` Adds empty table cells if necessary to finish the row.

At the end of the table, if any bottom rules are requested then an empty row must be generated to form the borders which show the rules.

```
\newcommand*{\LWR@tabularfinishrow}{%
```

If not exiting the tabular, or doing a rule, or have already started a row, finish this row:

```
    \ifboolexpr{%
        not bool {LWR@exitingtabular} or%
        bool{LWR@doingtbrule} or%
        bool{LWR@doingcmidrule} or%
        test{\ifnumcomp{\value{LWR@hlines}}{>}{0}} or%
        test{\ifnumcomp{\value{LWR@hdashedlines}}{>}{0}} or%
        bool{LWR@startedrow}%
    }{%
```

To temporarily turn off `LWR@exitingtabular` so that table data tags will still be generated:

If generating a final row for the `\bottomrule` borders, turn off the `@`, `!`, <, and > column output:

```
    \ifbool{LWR@exitingtabular}{%
        \booltrue{LWR@tabularmutemods}%
    }{%
        \boolfalse{LWR@tabularmutemods}%
    }%
```

Locally reenable the table data tags until finished with the final row:

```
    \boolfalse{LWR@exitingtabular}%
```

Generate table data tags and ampersands until the right edge:

```
    \whileboolexpr{%
        test {
            \ifnumcomp{\value{LWR@tableLaTeXcolindex}}{<}
                {\value{LWR@tabletotalLaTeXcols}}
        } or %
        (%
            bool{LWR@intabularmetadata} and%
```

```
            not bool{LWR@tabularcelladded} and%
            test {
                \ifnumcomp{\value{LWR@tableLaTeXcolindex}}{=}
                    {\value{LWR@tabletotalLaTeXcols}}
            }%
        )%
    }%
    {%
        \LWR@tabledatasinglecolumntag%
```

The following is essentially `\LWR@tabularampersand` with `LWR@emptyatbang` added to empty the following cells:

```
        \LWR@closetabledatacell%
        \defaddtocounter{LWR@tableLaTeXcolindex}{1}%
        \global\boolfalse{LWR@tabularcelladded}%
        \booltrue{LWR@emptyatbang}%
```

Starts the next cell:

```
        \ifnumcomp{\value{LWR@tableLaTeXcolindex}}{<}
                {\value{LWR@tabletotalLaTeXcols}}%
            {\LWR@getmynexttoken}%
            {}%
    }%
```

Reenable the original `LWR@exitingtabular` to close the entire table:

```
    \ifbool{LWR@tabularmutemods}{%
        \booltrue{LWR@exitingtabular}%
    }{%
        \boolfalse{LWR@exitingtabular}%
    }%
    \boolfalse{LWR@tabularmutemods}%

    \boolfalse{LWR@emptyatbang}%
    }{}% ifboolexpr
}
```

75.6 Handling \\

Inside tabular, `\\` is redefined to `\LWR@tabularendofline`

Throws away options `\\[dim]` or `\\*`

`\LWR@tabularendofline`

```
\NewDocumentCommand{\LWR@tabularendofline}{s o}{%
```

Finish the row:

```
    \ifnumcomp{\value{LWR@tableLaTeXcolindex}}{<}
```

```
            {\value{LWR@tabletotalLaTeXcols}}%
        {\LWR@tabularfinishrow}%
        {\LWR@closetabledatacell}%
    \LWR@htmltag{/tr}\LWR@orignewline%
```

xcolor row color support:

```
    \@rowc@lors%
```

No longer inside a data cell:

```
    \booltrue{LWR@intabularmetadata}%
```

Not yet started a table row:

```
    \boolfalse{LWR@startedrow}%
```

Additional setup:

```
    \defcounter{LWR@hlines}{0}%
    \defcounter{LWR@hdashedlines}{0}%
    \boolfalse{LWR@doingtbrule}%
    \boolfalse{LWR@doingcmidrule}%
    \LWR@clearmidrules%

    \def\LWR@rowHTMLcolor{}%
```

Start at first column:

```
    \defcounter{LWR@tableLaTeXcolindex}{1}%
```

Have not yet added data in this column:

```
    \global\boolfalse{LWR@tabularcelladded}%
```

Allow TEX to flush the pending paragraph. Not doing so causes a slowdown for very large tables.

```
    \LWR@stoppars%
    \LWR@origpar%
```

Look at the next token to decide between single column data tag or a special case:

```
    \LWR@getmynexttoken%
}
```

75.7 Looking ahead in the column specifications

`\LWR@columnspeclookahead` {⟨*offset*⟩}

Looks `offset` tokens ahead in the column specification, setting `\LWR@strresulttwo`.

The w column alignment will be seen as a single unit such as {c}.

```
\newcommand*{\LWR@columnspeclookahead}[1]{%
    \setcounter{LWR@tempcountone}{\value{LWR@tablecolspecindex}}%
    \addtocounter{LWR@tempcountone}{#1}%
    \fullexpandarg%
    \StrChar{\LWR@origcolspec}{\arabic{LWR@tempcountone}}[\LWR@strresulttwo]%
```

Get the contents of the first group in \LWR@strresulttwo:

```
        \exploregroups%
        \StrChar{\LWR@strresulttwo}{1}[\LWR@strresulttwo]%
        \noexploregroups%
}
```

75.8 Parsing @, >, <, !, bar columns

Holds the parsed argument for @, >, <, or ! columns:

```
\newcommand*{\LWR@colparameter}{}
```

\LWR@parseatcolumn Handles @{text} columns.

```
\newcommand*{\LWR@parseatcolumn}{%
```

Move to the next token after the '@':

```
    \LWR@traceinfo{at column}%
    \defaddtocounter{LWR@tablecolspecindex}{1}%
```

Read the next token into \LWR@colparameter, expanding once:

```
    \LWR@traceinfo{about to read the next token:}%
    \expandarg%
    \StrChar{\LWR@origcolspec}%
        {\arabic{LWR@tablecolspecindex}}[\LWR@colparameter]%
    \fullexpandarg%
```

Store the result into a data array, expanding once out of \LWR@colparameter:

```
    \LWR@traceinfo{have now read the next token}%
    \ifnumcomp{\value{LWR@tabletotalLaTeXcols}}{=}{0}%
    {% left edge of the table:
        \LWR@traceinfo{at the left edge}%
        \LWR@setexparray{LWR@colatspec}%
            {leftedge}%
            {\expandafter\@firstofone\LWR@colparameter}%
        \LWR@traceinfo{at the left edge: %
            \LWR@getexparray{LWR@colatspec}{leftedge}}%
    }%
    {% not at the left edge:
        \LWR@traceinfo{not at the left edge}%
```

```
        \LWR@setexparray{LWR@colatspec}%
            {\arabic{LWR@tabletotalLaTeXcols}}%
            {\expandafter\@firstofone\LWR@colparameter}%
        \LWR@traceinfo{at \arabic{LWR@tabletotalLaTeXcols}%
        : % space
        \LWR@getexparray{LWR@colatspec}{\arabic{LWR@tabletotalLaTeXcols}}}%
    }%
    \let\LWR@colparameter\relax%
    \booltrue{LWR@validtablecol}%
}
```

`\LWR@parsebangcolumn` Handles `!{text}` columns.

```
\newcommand*{\LWR@parsebangcolumn}{%
```

Move to the next token after the '!':

```
    \LWR@traceinfo{bang column}%
    \defaddtocounter{LWR@tablecolspecindex}{1}%
```

Read the next token into `\LWR@colparameter`, expanding once:

```
    \LWR@traceinfo{about to read the next token:}%
    \expandarg%
    \StrChar{\LWR@origcolspec}%
        {\arabic{LWR@tablecolspecindex}}[\LWR@colparameter]%
    \fullexpandarg%
```

Store the result into a data array, expanding once out of `\LWR@colparameter`:

```
    \LWR@traceinfo{have now read the next token}%
    \ifnumcomp{\value{LWR@tabletotalLaTeXcols}}{=}{0}%
    {% left edge of the table:
        \LWR@traceinfo{at the left edge}%
        \LWR@setexparray{LWR@colbangspec}%
            {leftedge}%
            {\expandafter\@firstofone\LWR@colparameter}%
    }%
    {% not at the left edge:
        \LWR@traceinfo{not at the left edge}%
        \LWR@setexparray{LWR@colbangspec}%
            {\arabic{LWR@tabletotalLaTeXcols}}%
            {\expandafter\@firstofone\LWR@colparameter}%
      \LWR@traceinfo{bang \arabic{LWR@tabletotalLaTeXcols}: \LWR@colparameter!}%
    }%
    \let\LWR@colparameter\relax%
    \booltrue{LWR@validtablecol}%
}
```

`\LWR@parsebeforecolumn` Handles `>{text}` columns.

```
\newcommand*{\LWR@parsebeforecolumn}{%
```

Move to the next token after the '>':

```
    \defaddtocounter{LWR@tablecolspecindex}{1}%
```

Read the next token, expanding once into `\LWR@colparameter`:

```
    \expandarg%
    \StrChar{\LWR@origcolspec}%
        {\arabic{LWR@tablecolspecindex}}[\LWR@colparameter]%
    \fullexpandarg%
```

Store the result into a data array, expanding once out of `\LWR@colparameter`:

```
    \LWR@setexparray{LWR@colbeforespec}%
        {\arabic{LWR@tabletotalLaTeXcolsnext}}%
        {\expandafter\@firstofone\LWR@colparameter}%
    \let\LWR@colparameter\relax%
    \booltrue{LWR@validtablecol}%
}
```

`\LWR@parseaftercolumn` Handles `<{text}` columns.

```
\newcommand*{\LWR@parseaftercolumn}{%
```

Move to the next token after the '<':

```
    \defaddtocounter{LWR@tablecolspecindex}{1}%
```

Read the next token, expanding once into `\LWR@colparameter`:

```
    \expandarg%
    \StrChar{\LWR@origcolspec}%
        {\arabic{LWR@tablecolspecindex}}[\LWR@colparameter]%
    \fullexpandarg%
```

Store the result into a data array, expanding once out of `\LWR@colparameter`:

```
    \LWR@setexparray{LWR@colafterspec}%
        {\arabic{LWR@tabletotalLaTeXcols}}%
        {\expandafter\@firstofone\LWR@colparameter}%
    \let\LWR@colparameter\relax%
    \booltrue{LWR@validtablecol}%
}
```

`\LWR@parsebarcolumn` Handles vertical rules.

```
\newcommand*{\LWR@parsebarcolumn}{%
    \LWR@traceinfo{LWR@parsebarcolumn}%
```

Remember the bar at this position:

```
    \ifnumcomp{\value{LWR@tabletotalLaTeXcols}}{=}{0}%
    {% left edge of the table:
```

```
        \edef\LWR@tempone{\LWR@getexparray{LWR@colbarspec}{leftedge}}%
        \ifdefstring{\LWR@tempone}{tvertbarl}%
        {\LWR@setexparray{LWR@colbarspec}{leftedge}{tvertbarldouble}}%
        {\LWR@setexparray{LWR@colbarspec}{leftedge}{tvertbarl}}%
    }%
    {% not at the left edge:
        \edef\LWR@tempone{%
           \LWR@getexparray{LWR@colbarspec}{\arabic{LWR@tabletotalLaTeXcols}}%
        }%
        \ifdefstring{\LWR@tempone}{tvertbarr}%
        {%
            \LWR@setexparray{LWR@colbarspec}%
                {\arabic{LWR@tabletotalLaTeXcols}}{tvertbarrdouble}%
        }%
        {%
            \LWR@setexparray{LWR@colbarspec}%
                {\arabic{LWR@tabletotalLaTeXcols}}{tvertbarr}%
        }%
    }%
    \booltrue{LWR@validtablecol}%
}
```

`\LWR@parsecoloncolumn` Handles vertical rules.

```
\newcommand*{\LWR@parsecoloncolumn}{%
    \LWR@traceinfo{LWR@parsecoloncolumn}%
```

Remember the bar at this position:

```
    \ifnumcomp{\value{LWR@tabletotalLaTeXcols}}{=}{0}%
    {% left edge of the table:
        \edef\LWR@tempone{\LWR@getexparray{LWR@colbarspec}{leftedge}}%
        \ifdefstring{\LWR@tempone}{tvertbarldash}%
        {\LWR@setexparray{LWR@colbarspec}{leftedge}{tvertbarldoubledash}}%
        {\LWR@setexparray{LWR@colbarspec}{leftedge}{tvertbarldash}}%
    }%
    {% not at the left edge:
        \edef\LWR@tempone{%
           \LWR@getexparray{LWR@colbarspec}{\arabic{LWR@tabletotalLaTeXcols}}%
        }%
        \ifdefstring{\LWR@tempone}{tvertbarrdash}%
        {\LWR@setexparray{LWR@colbarspec}%
            {\arabic{LWR@tabletotalLaTeXcols}}{tvertbarrdoubledash}}%
        {\LWR@setexparray{LWR@colbarspec}%
            {\arabic{LWR@tabletotalLaTeXcols}}{tvertbarrdash}}%
    }%
    \booltrue{LWR@validtablecol}%
}
```

`\LWR@parsesemicoloncolumn` Handles vertical rules.

```
\newcommand*{\LWR@parsesemicoloncolumn}{%
```

Treat ; as a : column:

```
    \LWR@parsecoloncolumn%
```

Skip the following width token:

```
    \defaddtocounter{LWR@tablecolspecindex}{1}%
}
```

75.9 Parsing 'l', 'c', or 'r' columns

`\LWR@parsenormalcolumn` {⟨*thiscolumn*⟩}

Add to the accumulated column specs, advance counters, and pre-clear another column of at, before, and after specs.

```
\newcommand*{\LWR@parsenormalcolumn}[1]{%
    \defaddtocounter{LWR@tabletotalLaTeXcols}{1}%
    \defaddtocounter{LWR@tabletotalLaTeXcolsnext}{1}%

    \LWR@setexparray{LWR@tablecolspec}{\arabic{LWR@tabletotalLaTeXcols}}{#1}%

    \LWR@traceinfo{normal column \arabic{LWR@tabletotalLaTeXcols}: #1}%
    \LWR@setexparray{LWR@colatspec}{\arabic{LWR@tabletotalLaTeXcolsnext}}{}%
    \LWR@setexparray{LWR@colbangspec}{\arabic{LWR@tabletotalLaTeXcolsnext}}{}%
   \LWR@setexparray{LWR@colbeforespec}{\arabic{LWR@tabletotalLaTeXcolsnext}}{}%
   \LWR@setexparray{LWR@colafterspec}{\arabic{LWR@tabletotalLaTeXcolsnext}}{}%
    \LWR@setexparray{LWR@colbarspec}{\arabic{LWR@tabletotalLaTeXcolsnext}}{}%
    \booltrue{LWR@validtablecol}%
}
```

75.10 Parsing 'p', 'm', or 'b' columns

`\LWR@parsepcolumn` {⟨*thiscolumn*⟩} The width will be ignored.

```
\newcommand*{\LWR@parsepcolumn}[1]{%
```

Converts to the given column type:

```
    \LWR@parsenormalcolumn{#1}%
```

Skips the following width token:

```
    \defaddtocounter{LWR@tablecolspecindex}{1}%
}
```

75.11 Parsing ‘w’ columns

\LWR@parsewcolumn The width will be ignored.

```
\newcommand*{\LWR@parsewcolumn}{%
    \LWR@columnspeclookahead{1}%
    \expandafter\LWR@parsenormalcolumn\expandafter{\LWR@strresulttwo}%
```

Skips the following width and alignment tokens:

```
    \defaddtocounter{LWR@tablecolspecindex}{2}%
}
```

75.12 Parsing ’*’ columns

\LWR@parsestarcolumn Star columns should already have been expanded, so this should never be used.

```
\newcommand*{\LWR@parsestarcolumn}{%
    \defaddtocounter{LWR@tablecolspecindex}{2}%
}
```

75.13 Parsing ‘D’ columns

From the dcolumn package.

\LWR@parseDcolumn {⟨*thiscolumn*⟩} The three parameters will be ignored.

```
\newcommand*{\LWR@parseDcolumn}[1]{%
```

Converts to the given column type.

```
    \LWR@parsenormalcolumn{#1}%
```

Skips the following three parameters.

```
    \defaddtocounter{LWR@tablecolspecindex}{3}%
}
```

75.14 Expanding the star column specifications

Ctr LWR@starcount Internal count for duplicating star columns.

```
\newcount\LWR@starcount
```

\LWR@expcolspec Temporary storage used to build the expanded column specifier.

```
\newcommand*{\LWR@expcolspec}{}
```

Ctr LWR@splitstarindex Indexes into the column specifiers.

```
\newcounter{LWR@splitstarindex}
```

Ctr LWR@splitstarcopies Number of copies.

```
\newcounter{LWR@splitstarcopies}
```

\LWR@splitstarcontents Contents to duplicate.

```
\newcommand*{\LWR@splitstarcontents}{}
```

\expandcolspec Expands \LWR@origcolspec for star columns.

```
\newcommand*{\expandcolspec}{%
```

Find the position of any star token.

```
    \StrPosition{\LWR@origcolspec}{*}[\LWR@tempone]%
```

Expand until no stars are found:

```
    \whileboolexpr{ test {\ifnumgreater{\LWR@tempone}{0}}}%
    {%
```

Begin with any characters to the left of the star.

```
        \setcounter{LWR@splitstarindex}{\LWR@tempone}%
        \addtocounter{LWR@splitstarindex}{-1}%
      \StrLeft{\LWR@origcolspec}{\value{LWR@splitstarindex}}[\LWR@expcolspec]%
```

Move past the star to remember its number of copies.

```
        \addtocounter{LWR@splitstarindex}{2}%
        \StrChar{\LWR@origcolspec}{\value{LWR@splitstarindex}}[\LWR@tempone]%
       \setcounter{LWR@splitstarcopies}{\expandafter\@firstofone\LWR@tempone}%
```

Move past the number of copies and remember the contents.

```
        \addtocounter{LWR@splitstarindex}{1}%
     \StrChar{\LWR@origcolspec}{\value{LWR@splitstarindex}}[\LWR@splitstarcontents]%
```

For each copy, append the contents.

```
        \ifnumgreater{\value{LWR@splitstarcopies}}{0}%
        {%
            \LWR@starcount=\value{LWR@splitstarcopies}%
            \loop
                \appto\LWR@expcolspec{%
```

(Remove the enclosing braces.)

```
                    \expandafter\@firstofone\LWR@splitstarcontents%
```

Table 13: Tabular baseline

l	p	m	b	r
			bot	
		mid	bot	
l	par	mid	bot	r
	par	mid		
	par			

```
8976                }%
8977                \advance \LWR@starcount -1
8978            \ifnum \LWR@starcount>0 \repeat
8979        }{}%
```

Remove any token to the left, and append the rightmost remainding tokens.

```
8980      \StrGobbleLeft{\LWR@origcolspec}{\value{LWR@splitstarindex}}[\colspecremainder]%
8981        \appto{\LWR@expcolspec}{\colspecremainder}%
```

Remember the final result.

```
8982        \edef\LWR@origcolspec{\LWR@expcolspec}%
```

See if more stars exist.

```
8983        \StrPosition{\LWR@origcolspec}{*}[\LWR@tempone]%
8984    }%
8985 }
```

75.15 Parsing the column specifications

⚠ tabular baselines

HTML CSS cannot exactly match the LaTeX concept of a baseline for a table row. Table 13 shows the LaTeX results for various vertical-alignment choices, with the baseline of the first column drawn across all the columns for comparison. See the p column specification in table 14 for details.

Table 14 describes how each kind of column is converted to HTML.

`\LWR@parsetablecols` {⟨*colspecs*⟩}

Scans the column specification left to right.

Builds `\LWR@tablecolspec` with the final specification, one LaTeX column per entry. The final number of LaTeX columns in each row is stored in `LWR@tabletotalLaTeXcols`, which is the number of & and \\ in each line, but which does not include @, !, <, > specifications in the count.

```
8986 \newcommand*{\LWR@parsetablecols}[1]{%
8987     \LWR@traceinfo{LWR@parsetablecols}%
```

Table 14: Tabular HTML column conversions

l, r, c: Converted to table cells without paragraph tags.
Uses CSS `vertical-align:middle` so that top or bottom-aligned cells may go above or below this cell.

p: Converted to table cells with paragraph tags. Ref: Table 13, LaTeX places the top line of a parbox aligned with the rest of the text line, so CSS `vertical-align:bottom` is used to have the HTML result appear with the paragraph extending below the L, R, C cells at the middle, if possible. This may be confusing as a P cell may not top-align with an L,R,C cell in the HTML conversion, especially in the presence of a B cell, and two P cells side-by-side will be aligned at the bottom instead of the top. Some adjustment of the CSS may be desired, changing `td.tdp`, `td.tdP`, `td.tdprule`, and `td.tdPrule` to `vertical-align: middle`. Another possibility is to change L,R,C, and P to `vertical-align: top` and not worry about the alignment of B and M cells or trying to approximate LaTeX baselines.

m: With paragraph tags, CSS `vertical-align:middle`.

b: With paragraph tags, CSS `vertical-align:top` so that the bottom of the text is closest to the middle of the text line.

P, M, B: Horizontally-centered versions.

S: Converted to 'r'. Ignores optional argument. From the siunitx package.

D: Converted to 'c'. From the dcolumn package.

@, !, >, <: One each, in that order.

|: Vertical rule.

Unknown: Converted to 'l'.

`\newcolumn`: Currently treated as unknown.

Remember the original supplied column spec:

```
\renewcommand*{\LWR@origcolspec}{#1}%
```

Remove spaces:

```
\expandarg%
\StrSubstitute{\LWR@origcolspec}{ }{}[\LWR@origcolspec]%
```

Expand any star columns:

```
\expandcolspec%
```

The parsed column spec data array, `LWR@tablecolspec`, will be overwritten with new values.

Total number of columns found so far. Also pre-initialize the first several columns of specs:

```
\defcounter{LWR@tabletotalLaTeXcols}{0}%
\defcounter{LWR@tabletotalLaTeXcolsnext}{1}%
\LWR@setexparray{LWR@colatspec}{leftedge}{}%
\LWR@setexparray{LWR@colatspec}{1}{}%
\LWR@setexparray{LWR@colatspec}{2}{}%
\LWR@setexparray{LWR@colatspec}{3}{}%
\LWR@setexparray{LWR@colbangspec}{leftedge}{}%
\LWR@setexparray{LWR@colbangspec}{1}{}%
\LWR@setexparray{LWR@colbangspec}{2}{}%
\LWR@setexparray{LWR@colbangspec}{3}{}%
\LWR@setexparray{LWR@colbeforespec}{1}{}%
\LWR@setexparray{LWR@colbeforespec}{2}{}%
\LWR@setexparray{LWR@colbeforespec}{3}{}%
\LWR@setexparray{LWR@colafterspec}{1}{}%
\LWR@setexparray{LWR@colafterspec}{2}{}%
\LWR@setexparray{LWR@colafterspec}{3}{}%
\LWR@setexparray{LWR@colbarspec}{leftedge}{}%
\LWR@setexparray{LWR@colbarspec}{1}{}%
\LWR@setexparray{LWR@colbarspec}{2}{}%
\LWR@setexparray{LWR@colbarspec}{3}{}%
```

Starting at the first column specification:

```
\defcounter{LWR@tablecolspecindex}{1}%
```

Place the colspecs string length into `\LWR@strresult`, and remember the number of characters in the column specification:

```
\expandarg%
\StrLen{\LWR@origcolspec}[\LWR@strresult]%
\fullexpandarg%
\LWR@traceinfo{original column spec length: \LWR@strresult}%
\defcounter{LWR@tablecolspecwidth}{\LWR@strresult}%
```

Haven't seen any optional arguments so far

```
\boolfalse{LWR@opttablecol}%
```

Scan through the column specifications:

```
    \whileboolexpr{%
        not test{%
            \ifnumcomp{\value{LWR@tablecolspecindex}}{>}%
                {\value{LWR@tablecolspecwidth}}%
        }%
    }%
    {%
```

Place the next single-character column type into `\LWR@strresult`:

```
    \expandarg%
   \StrChar{\LWR@origcolspec}{\arabic{LWR@tablecolspecindex}}[\LWR@strresult]%
    \LWR@traceinfo{position \arabic{LWR@tablecolspecindex}: \LWR@strresult}%
    \fullexpandarg%
```

Not yet found a valid column type:

```
    \boolfalse{LWR@validtablecol}%
```

Skip over any optional arguments, such as siunitx `S` column:

```
    \IfStrEq{\LWR@strresult}{[}{\booltrue{LWR@opttablecol}}{}%
```

Throw away anything found inside the optional argument:

```
    \ifbool{LWR@opttablecol}%
    {}% inside an optional argument
    {% not an optional tabular argument
```

Not inside an optional argument, so consider the column type:

```
    \IfStrEq{\LWR@strresult}{l}{\LWR@parsenormalcolumn{l}}{}%
    \IfStrEq{\LWR@strresult}{c}{\LWR@parsenormalcolumn{c}}{}%
    \IfStrEq{\LWR@strresult}{r}{\LWR@parsenormalcolumn{r}}{}%
    \IfStrEq{\LWR@strresult}{L}{\LWR@parsenormalcolumn{l}}{}%
    \IfStrEq{\LWR@strresult}{C}{\LWR@parsenormalcolumn{c}}{}%
    \IfStrEq{\LWR@strresult}{R}{\LWR@parsenormalcolumn{r}}{}%
    \IfStrEq{\LWR@strresult}{J}{\LWR@parsenormalcolumn{l}}{}%

    \IfStrEq{\LWR@strresult}{S}{\LWR@parsenormalcolumn{c}}{}%
    \IfStrEq{\LWR@strresult}{s}{\LWR@parsenormalcolumn{c}}{}%

    \IfStrEq{\LWR@strresult}{\detokenize{@}}{\LWR@parseatcolumn}{}%
    \IfStrEq{\LWR@strresult}{!}{\LWR@parsebangcolumn}{}%
    \IfStrEq{\LWR@strresult}{>}{\LWR@parsebeforecolumn}{}%
    \IfStrEq{\LWR@strresult}{<}{\LWR@parseaftercolumn}{}%
    \IfStrEq{\LWR@strresult}{|}{\LWR@parsebarcolumn}{}%
    \IfStrEq{\LWR@strresult}{:}{\LWR@parsecoloncolumn}{}%
    \IfStrEq{\LWR@strresult}{;}{\LWR@parsesemicoloncolumn}{}%

    \IfStrEq{\LWR@strresult}{p}{\LWR@parsepcolumn{p}}{}%
    \IfStrEq{\LWR@strresult}{m}{\LWR@parsepcolumn{m}}{}%
    \IfStrEq{\LWR@strresult}{b}{\LWR@parsepcolumn{b}}{}%
```

```
    \IfStrEq{\LWR@strresult}{w}{\LWR@parsewcolumn}{}%
    \IfStrEq{\LWR@strresult}{W}{\LWR@parsewcolumn}{}%
```

A star column:

```
    \IfStrEq{\LWR@strresult}{*}{\LWR@parsestarcolumn}{}%
```

From the dcolumn package:

```
    \IfStrEq{\LWR@strresult}{D}{\LWR@parseDcolumn{c}}{}%
```

From the tabularx package. X column has no parameter, but will be given paragraph tags.

```
    \IfStrEq{\LWR@strresult}{X}{\LWR@parsenormalcolumn{X}}{}%
```

Many people define centered versions "P", "M", and "B":

```
\newcolumntype{P}[1]{>{\centering\arraybackslash}p{#1}}
```

```
    \IfStrEq{\LWR@strresult}{P}{\LWR@parsepcolumn{P}}{}%
    \IfStrEq{\LWR@strresult}{M}{\LWR@parsepcolumn{M}}{}%
    \IfStrEq{\LWR@strresult}{B}{\LWR@parsepcolumn{B}}{}%
```

If this column was an invalid column type, convert it to an `l` column:

```
    \ifbool{LWR@validtablecol}{}{%
        \LWR@traceinfo{invalid column type: \LWR@strresult}%
        \LWR@parsenormalcolumn{l}%
    }%
    }% not an optional column argument
```

If read the closing bracket, no longer inside the optional argument:

```
    \IfStrEq{\LWR@strresult}{]}{\boolfalse{LWR@opttablecol}}{}%
```

Move to the next character:

```
    \defaddtocounter{LWR@tablecolspecindex}{1}%
    }% whiledo
}%
```

75.16 colortbl and xcolor tabular color support

These macros provide a minimal emulation of some colortbl macros which might appear between table cells. If colortbl is loaded, these macros will be replaced with functional versions.

For each of the HTML colors below, the text for the HTML color is set if requested, but the macro is empty if none has been set.

`\rownum` Reserve a counter register.

```
\@ifundefined{rownum}{\newcount\rownum}{}
```

`\@rowcolors` Emulated in case xcolor is not used.

```
\newcommand*{\@rowcolors}{}
```

`\@rowc@lors` Emulated in case xcolor is not used.

```
\newcommand*{\@rowc@lors}{}
```

`\LWR@xcolorrowHTMLcolor` Emulated xcolor row color.

```
\newcommand*{\LWR@xcolorrowHTMLcolor}{}
```

`\LWR@columnHTMLcolor` HTMLstyle code for the column color.

```
\def\LWR@columnHTMLcolor{}
```

`\LWR@rowHTMLcolor` HTMLstyle code for the row color.

```
\def\LWR@rowHTMLcolor{}
```

`\LWR@cellHTMLcolor` HTMLstyle code for the cell color.

```
\def\LWR@cellHTMLcolor{}
```

`\LWR@ruleHTMLcolor` HTMLstyle code for the rule color.

```
\newcommand*{\LWR@ruleHTMLcolor}{}
```

`\rowcolor` `[`⟨*model*⟩`]` `{`⟨*color*⟩`}` `[`⟨*left overhang*⟩`]` `[`⟨*right overhang*⟩`]` Print version. The HTML version is in lwarp-colortbl. Used before starting a tabular data cell, thus `\LWR@getmynexttoken`.

```
\newcommand*{\rowcolor}{\LWR@getmynexttoken}%
```

`\arrayrulecolor` `[`⟨*model*⟩`]` `{`⟨*color*⟩`}`

`\arrayrulecolornexttoken` `[`⟨*model*⟩`]` `{`⟨*color*⟩`}`

Print versions for use outside and inside a `tabular`:

```
\newcommand{\arrayrulecolor}[2][named]{}
\newcommand{\arrayrulecolornexttoken}[2][named]{\LWR@getmynexttoken}
```

`\doublerulesepcolor` `[`⟨*model*⟩`]` `{`⟨*color*⟩`}`

\doublerulesepcolornexttoken [⟨*model*⟩] {⟨*color*⟩}

Print versions for use inside and outside a `tabular`:

```
\newcommand{\doublerulesepcolor}[2][named]{}
\newcommand{\doublerulesepcolornexttoken}[2][named]{\LWR@getmynexttoken}
```

75.17 Starting a new row

\LWR@maybenewtablerow If have not yet started a new table row, begin one now. Creates a new row tag, adding a class for `hline` or `tbrule` if necessary.

```
\newcommand*{\LWR@maybenewtablerow}
{%
    \ifbool{LWR@startedrow}%
    {}% started the row
    {% not started the row
```

Remember that now have started the row:

```
        \booltrue{LWR@startedrow}%
```

Create the row tag, with a class if necessary.

```
        \booltrue{LWR@intabularmetadata}%
        \ifboolexpr{%
            test{\ifnumcomp{\value{LWR@hlines}}{>}{0}} or%
            test{\ifnumcomp{\value{LWR@hdashedlines}}{>}{0}}%
        }%
        {%
            \LWR@htmltag{tr class=\textquotedbl{}hline\textquotedbl }%
            \LWR@orignewline%
        }%
        {% not doing hline
            \ifbool{LWR@doingtbrule}%
            {%
                \ifdefvoid{\LWR@ruleHTMLcolor}{%
                    \LWR@htmltag{tr class=\textquotedbl{}tbrule\textquotedbl}%
                }{%
                    \LWR@htmltag{%
                        tr class=\textquotedbl{}tbrule\textquotedbl\ % space
                        style=\textquotedbl{}border-top: 1px solid % space
                            \LWR@origpound\LWR@ruleHTMLcolor \textquotedbl{}%
                    }%
                }%
                \LWR@orignewline%
            }%
            {\LWR@htmltag{tr}\LWR@orignewline}%
        }% end of not doing hline
    }% end of not started the row
}
```

75.18 Printing vertical bar tags

\LWR@printbartag {⟨*index*⟩}

Adds to a tabular data cell an HTML class name for a left/right vertical bar.

```
\newcommand*{\LWR@printbartag}[1]{%
    \LWR@traceinfo{LWR@printbartag !#1!}%
    \ifboolexpr{bool{LWR@tabularmutemods} or bool{LWR@emptyatbang}}%
    {}% muting or empty
    {% not muting
        \edef\LWR@tempone{\LWR@getexparray{LWR@colbarspec}{#1}}%
        \ifdefempty{\LWR@tempone}{}{ \LWR@tempone}%
    }% not muting
    \LWR@traceinfo{LWR@printbartag done}%
}
```

75.19 Printing @ or ! tags

\LWR@printatbang {⟨*at — or — bang*⟩} {⟨*index*⟩}

```
\newcommand*{\LWR@printatbang}[2]{%
```

Fetch the column at or bang spec:

```
    \xdef\LWR@atbangspec{\LWR@getexparray{LWR@col#1spec}{#2}}%
    \LWR@traceinfo{atbang: #2 !\LWR@atbangspec!}%
```

Only generate if is not empty;

```
    \ifdefempty{\LWR@atbangspec}%
    {}%
    {% not empty
        \LWR@htmltag{%
            td class=\textquotedbl{}td#1%
            \LWR@subaddcmidruletrim{}{}%
            \LWR@printbartag{#2}%
            \textquotedbl{}%
            \LWR@tdstartstyles%
            \LWR@addcmidrulewidth%
            \LWR@addcdashline%
            \LWR@addtabularrulecolors%
            \LWR@tdendstyles%
        }%
```

Create an empty cell if muting for the \bottomrule:

```
        \ifboolexpr{bool{LWR@tabularmutemods} or bool{LWR@emptyatbang}}%
        {}%
        {\LWR@atbangspec}%
%
        \LWR@htmltag{/td}\LWR@orignewline%
```

```
        \global\booltrue{LWR@tabularcelladded}%
    }% not empty
}%
```

\LWR@addleftmostbartag

```
\newcommand*{\LWR@addleftmostbartag}{%
    \ifnumcomp{\value{LWR@tableLaTeXcolindex}}{=}{1}{%
        \LWR@printbartag{leftedge}%
    }{}%
}
```

\LWR@tabularleftedge

```
\newcommand*{\LWR@tabularleftedge}{%
    \ifnumcomp{\value{LWR@tableLaTeXcolindex}}{=}{1}%
    {%
        \LWR@printatbang{at}{leftedge}%
        \LWR@printatbang{bang}{leftedge}%
    }% left edge
    {}% not left edge
}
```

75.20 Data opening tag

\LWR@thiscolspec Temporary storage.

```
\newcommand*{\LWR@thiscolspec}{}
```

\LWR@tabledatasinglecolumntag Print a table data opening tag with style for alignment and color.

```
\newcommand*{\LWR@tabledatasinglecolumntag}%
{%
    \LWR@traceinfo{LWR@tabledatasinglecolumntag}%
    \LWR@maybenewtablerow%
```

Don't start a new paragraph tag if have already started one:

```
    \ifbool{LWR@intabularmetadata}%
    {%
```

If have found the end of tabular command, do not create the next data cell:

```
        \ifbool{LWR@exitingtabular}{}%
        {% not exiting tabular
```

Print the `@` and `!` contents before first column:

```
            \LWR@tabularleftedge%
```

Fetch the current column's alignment character into `\LWR@strresult`:

```
          \xdef\LWR@strresult{%
        \LWR@getexparray{LWR@tablecolspec}{\arabic{LWR@tableLaTeXcolindex}}%
          }%
```

Print the start of a new table data cell:

```
        \LWR@traceinfo{LWR@tabledatasinglecolumntag: about to print td tag}%
          \LWR@htmltag{%
              td class=\textquotedbl{}td%
```

Append this column's spec:

```
              \LWR@strresult%
```

If this column has a cmidrule, add "rule" to the end of the HTML class tag. Also add vertical bar tags.

```
              \LWR@addcmidruletrim%
              \LWR@addleftmostbartag%
              \LWR@printbartag{\arabic{LWR@tableLaTeXcolindex}}%
              \textquotedbl{}%
```

Add styles for rules, alignment:

```
              \LWR@tdstartstyles%
              \LWR@addcmidrulewidth%
              \LWR@addcdashline%


              \xdef\LWR@thiscolspec{%
                  \LWR@getexparray{LWR@tablecolspec}%
                      {\arabic{LWR@tableLaTeXcolindex}}%
              }%
              \LWR@addformatwpalignment{\LWR@thiscolspec}%
```

Add styles for cell and rule colors:

```
              \LWR@addtabularrowcolor%
              \LWR@addtabularrulecolors%


              \LWR@tdendstyles%
          }% HTML td
        \LWR@traceinfo{LWR@tabledatasinglecolumntag: done printing td tag}%
```

If this is a p, m, b, or X column, allow paragraphs:

```
          \ifboolexpr{%
              test{ \ifdefstring{\LWR@strresult}{p} } or
              test{ \ifdefstring{\LWR@strresult}{m} } or
              test{ \ifdefstring{\LWR@strresult}{b} } or
              test{ \ifdefstring{\LWR@strresult}{P} } or
              test{ \ifdefstring{\LWR@strresult}{M} } or
```

```
                test{ \ifdefstring{\LWR@strresult}{B} } or
                test{ \ifdefstring{\LWR@strresult}{X} }
            }%
            {% allow pars
           \LWR@traceinfo{LWR@tabledatasinglecolumntag: about to LWR@startpars}%
                \booltrue{LWR@tableparcell}%
                \LWR@startpars%
           \LWR@traceinfo{LWR@tabledatasinglecolumntag: done with LWR@startpars}%
            }% allow pars
            {}% no pars
```

Print the > contents unless muted for the `\bottomrule`:

```
            \ifboolexpr{bool{LWR@tabularmutemods} or bool{LWR@emptyatbang}}%
            {}%
            {%
           \LWR@getexparray{LWR@colbeforespec}{\arabic{LWR@tableLaTeXcolindex}}%
            }%
            \boolfalse{LWR@intabularmetadata}%
        }% not exiting tabular
    }{}% in tabular metadata
    \LWR@traceinfo{LWR@tabledatasinglecolumntag: done}%
}%
```

75.21 Midrules

`LWR@midrules` `LWR@midrules` is a data array (section 42) of columns each containing a non-zero width if a midrule should be created for this column.

`LWR@trimlrules` `LWR@trimlrules` is a data array (section 42) of columns containing `l` if a midrule should be left trimmed for each column.

`LWR@trimrrules` `LWR@trimrrules` is a data array (section 42) of columns containing `r` if a midrule should be right trimmed for each column.

`LWR@cdashlines` `LWR@cdashlines` is a data array (section 42) of columns each containing a `Y` if an arydshln package "cdashed line" should be created for this column.

Len `\LWR@heavyrulewidth` The default width of the rule.

```
\newlength{\LWR@heavyrulewidth}
\setlength{\LWR@heavyrulewidth}{.08em}
```

Len `\LWR@lightrulewidth` The default width of the rule.

```
\newlength{\LWR@lightrulewidth}
\setlength{\LWR@lightrulewidth}{.05em}
```

Len `\LWR@cmidrulewidth` The default width of the rule.

```
\newlength{\LWR@cmidrulewidth}
\setlength{\LWR@cmidrulewidth}{.03em}
```

Len `\LWR@thiscmidrulewidth` The width of the next rule, defaulting to `\LWR@cmidrulewidth`.

If not \LWR@cmidrulewidth, a style will be used to generate the custom width.

Assigned from the LWR@midrules array.

```
\newlength{\LWR@thiscmidrulewidth}
\setlength{\LWR@thiscmidrulewidth}{\LWR@cmidrulewidth}
```

\LWR@clearmidrules Start new midrules. Called at beginning of tabular and also at \\.

Clears all LWR@midrules and LWR@trimrules markers for this line.

```
\newcommand*{\LWR@clearmidrules}
{%
    \defcounter{LWR@midrulecounter}{1}%
    \whileboolexpr{%
        not test{%
            \ifnumcomp{\value{LWR@midrulecounter}}{>}%
                {\value{LWR@tabletotalLaTeXcols}}%
        }%
    }%
    {%
        \LWR@setexparray{LWR@midrules}{\arabic{LWR@midrulecounter}}{0pt}%
        \setlength{\LWR@thiscmidrulewidth}{\LWR@cmidrulewidth}%
        \LWR@setexparray{LWR@trimlrules}{\arabic{LWR@midrulecounter}}{}%
        \LWR@setexparray{LWR@trimrrules}{\arabic{LWR@midrulecounter}}{}%
        \LWR@setexparray{LWR@cdashlines}{\arabic{LWR@midrulecounter}}{N}%
        \defaddtocounter{LWR@midrulecounter}{1}%
    }%
}
```

\LWR@subcmidrule {⟨*width*⟩} {⟨*trim*⟩} {⟨*leftcolumn*⟩} {⟨*rightcolumn*⟩}

Marks LWR@midrules data array elements to be non-zero widths from left to right columns. Also marks trimming for the L and/or R columns.

LWR@doingcmidrule is set to force an empty row at the end of the tabular to create the rule.

```
\newcommand*{\LWR@subcmidrule}[4]{%
    \defcounter{LWR@midrulecounter}{#3}%
    \whileboolexpr{%
        not test {%
            \ifnumcomp{\value{LWR@midrulecounter}}{>}{#4}%
        }%
    }%
    {%
        \LWR@setexparray{LWR@midrules}{\arabic{LWR@midrulecounter}}{#1}%
        \defaddtocounter{LWR@midrulecounter}{1}%
    }% whiledo
    \IfSubStr{#2}{l}{\LWR@setexparray{LWR@trimlrules}{#3}{l}}{}%
    \IfSubStr{#2}{r}{\LWR@setexparray{LWR@trimrrules}{#4}{r}}{}%
    \booltrue{LWR@doingcmidrule}%
}
```

\LWR@docmidrule [⟨*width*⟩] (⟨*trim*⟩) {⟨*leftcolumn-rightcolumn*⟩}

Marks LWR@midrules array elements to be a non-zero width from left to right columns. Also marks trimming for the L and/or R columns.

```
\NewDocumentCommand{\LWR@docmidrule}
    {O{\LWR@cmidrulewidth} D(){} >{\SplitArgument{1}{-}}m}
    {\LWR@subcmidrule{#1}{#2}#3}
```

\LWR@subcdashline {⟨*leftcolumn*⟩} {⟨*rightcolumn*⟩}

Marks LWR@cdashlines data array elements to be Y from left to right columns.

LWR@doingcmidrule is set to force an empty row at the end of the tabular to create the rule.

```
\newcommand*{\LWR@subcdashline}[2]{%
    \defcounter{LWR@midrulecounter}{#1}%
    \whileboolexpr{%
        not test {%
            \ifnumcomp{\value{LWR@midrulecounter}}{>}{#2}%
        }%
    }%
    {%
        \LWR@setexparray{LWR@cdashlines}{\arabic{LWR@midrulecounter}}{Y}%
        \defaddtocounter{LWR@midrulecounter}{1}%
    }% whiledo
    \booltrue{LWR@doingcmidrule}%
}
```

\LWR@docdashline {⟨*leftcolumn-rightcolumn*⟩}

Marks LWR@cdashlines data array elements to be Y from left to right columns.

```
\NewDocumentCommand{\LWR@docdashline}
    {>{\SplitArgument{1}{-}}m}%
    {%
        \LWR@subcdashline#1%
    }
```

\LWR@tdstartstyles Begins possibly adding a table data cell style.

```
\newcommand*{\LWR@tdstartstyles}{\boolfalse{LWR@tdhavecellstyle}}
```

\LWR@tdaddstyle Starts adding a table data cell style.

```
\newcommand*{\LWR@tdaddstyle}{%
    \ifbool{LWR@tdhavecellstyle}%
        {; }%
        { style=\textquotedbl}%
    \booltrue{LWR@tdhavecellstyle}%
}
```

\LWR@tdendstyles Finishes possibly adding a table data cell style. Prints the closing quote.

```
\newcommand*{\LWR@tdendstyles}{%
    \ifbool{LWR@tdhavecellstyle}%
        {%
            \textquotedbl%
            \boolfalse{LWR@tdhavecellstyle}%
        }{}%
}
```

\LWR@subaddcmidruletrim {⟨*lefttrim*⟩} {⟨*righttrim*⟩} Adds a \cmidrule with optional trim.

```
\newcommand*{\LWR@subaddcmidruletrim}[2]{%
    \setlength{\LWR@templengthone}{%
            \LWR@getexparray{LWR@midrules}{\arabic{LWR@tableLaTeXcolindex}}%
    }%
    \ifdimcomp{\LWR@templengthone}{>}{0pt}%
        {%
```

Print the class with left and right trim letters appended:

```
            \LWR@origtilde tdrule#1#2%
```

Remember the width of the rule:

```
            \setlength{\LWR@thiscmidrulewidth}{\LWR@templengthone}%
        }%
        {%
            \setlength{\LWR@thiscmidrulewidth}{0pt}%
        }%
}
```

\LWR@addcmidruletrim Adds left or right trim to a \cmidrule.

```
\newcommand*{\LWR@addcmidruletrim}{%
    \LWR@subaddcmidruletrim%
        {\LWR@getexparray{LWR@trimlrules}{\arabic{LWR@tableLaTeXcolindex}}}%
        {\LWR@getexparray{LWR@trimrrules}{\arabic{LWR@tableLaTeXcolindex}}}%
}
```

\LWR@addrulewidth {⟨*thiswidth*⟩} {⟨*defaultwidth*⟩}

If not default width, add a custom style with width and color depending on thiswidth.

Must be placed between \LWR@tdstartstyles and \LWR@tdendstyles.

```
\newcommand{\LWR@addrulewidth}[2]{%
```

Only add a custom width if thiswidth is different than the defaultwidth, or if a color is being used:

```
    \ifboolexpr{%
```

```
        test{\ifdimcomp{#1}{=}{0pt}} or
        (
            ( test{\ifdimcomp{#1}{=}{#2}} and not bool{FormatWP} )
            and ( test {\ifdefvoid{\LWR@ruleHTMLcolor}} )
        )
    }%
    {}% default width and color
    {% custom width and/or color
```

Ensure that the width is wide enough to display in the browser:

```
        \LWR@forceminwidth{#1}%
```

Begin adding another style:

```
        \LWR@tdaddstyle%
```

The style itself:

```
        border-top:\LWR@printlength{\LWR@atleastonept} solid % space
```

If default gray, the darkness of the color depends on the thickness of the rule:

```
        \ifdefvoid{\LWR@ruleHTMLcolor}{%
            \ifdimcomp{#1}{<}{\LWR@lightrulewidth}%
            {\LWR@origpound{}A0A0A0}%
            {% lightrule or heaver
                \ifdimcomp{#1}{<}{\LWR@heavyrulewidth}%
                {\LWR@origpound{}808080}%
                {black}%
            }% lightrule or heavier
        }{%
            \LWR@origpound\LWR@ruleHTMLcolor%
        }%
    }% custom width and/or color
}
```

\LWR@addcmidrulewidth Adds a `style` for the rule width.

Must be placed between `\LWR@tdstartstyles` and `\LWR@tdendstyles`.

```
\newcommand{\LWR@addcmidrulewidth}{%
    \LWR@addrulewidth{\LWR@thiscmidrulewidth}{\LWR@cmidrulewidth}%
}
```

\LWR@addcdashline Must be placed between `\LWR@tdstartstyles` and `\LWR@tdendstyles`.

```
\newcommand{\LWR@addcdashline}{%
    \edef\LWR@tempone{%
        \LWR@getexparray{LWR@cdashlines}{\arabic{LWR@tableLaTeXcolindex}}%
    }%
    \ifdefstring{\LWR@tempone}{Y}{%
        \LWR@tdaddstyle%
        border-top: 1pt dashed %
```

```
        \ifdefvoid{\LWR@ruleHTMLcolor}%
            {black}%
            {\LWR@origpound\LWR@ruleHTMLcolor}%
    }{}%
}
```

`\LWR@WPcell` {⟨*text-align*⟩} {⟨*vertical-align*⟩}

```
\newcommand*{\LWR@WPcell}[2]{%
    \LWR@tdaddstyle%
    \LWR@print@mbox{text-align:#1}; \LWR@print@mbox{vertical-align:#2}%
}
```

`\LWR@addformatwpalignment` If `FormatWP`, adds a `style` for the alignment.

Must be placed between `\LWR@tdstartstyles` and `\LWR@tdendstyles`.

```
\newcommand*{\LWR@addformatwpalignment}[1]{%
    \ifbool{FormatWP}{%
        \IfSubStr{#1}{l}{\LWR@WPcell{left}{middle}}{}%
        \IfSubStr{#1}{c}{\LWR@WPcell{center}{middle}}{}%
        \IfSubStr{#1}{r}{\LWR@WPcell{right}{middle}}{}%
        \IfSubStr{#1}{p}{\LWR@WPcell{left}{bottom}}{}%
        \IfSubStr{#1}{m}{\LWR@WPcell{left}{middle}}{}%
        \IfSubStr{#1}{b}{\LWR@WPcell{left}{top}}{}%
        \IfSubStr{#1}{P}{\LWR@WPcell{center}{bottom}}{}%
        \IfSubStr{#1}{M}{\LWR@WPcell{center}{middle}}{}%
        \IfSubStr{#1}{B}{\LWR@WPcell{center}{top}}{}%
    }{}%
}
```

75.22 Cell colors

`\LWR@addtabularrowcolor` Adds a cell's row color style, if needed.

No color is added for the final row of empty cells which finishes each `tabular`.

```
\newcommand*{\LWR@addtabularrowcolor}{%
    \ifbool{LWR@tabularmutemods}{}{%
        \ifdefvoid{\LWR@rowHTMLcolor}{%
            \ifdefvoid{\LWR@xcolorrowHTMLcolor}{}%
            {% xcolor row color
                \LWR@tdaddstyle%
                background:\LWR@origpound\LWR@xcolorrowHTMLcolor%
            }%
        }%
        {% explicit row color
            \LWR@tdaddstyle%
            background:\LWR@origpound\LWR@rowHTMLcolor%
        }%
    }%
}
```

\LWR@addtabularhrulecolor Adds a cell's horizontal rule color style, if needed.

```
\newcommand*{\LWR@addtabularhrulecolor}{%
```

If either form of horizontal rule is requested:

```
    \ifboolexpr{%
        test{\ifnumcomp{\value{LWR@hlines}}{>}{0}} or%
        test{\ifnumcomp{\value{LWR@hdashedlines}}{>}{0}} or%
        bool{LWR@doingtbrule}%
    }{%
```

If there is a no custom color:

```
        \ifdefvoid{\LWR@ruleHTMLcolor}%
        {%
            \ifnumcomp{\value{LWR@hlines}}{>}{1}%
            {%
                \LWR@tdaddstyle%
                border-top: 4px double%
            }{% else
            \ifnumcomp{\value{LWR@hdashedlines}}{>}{1}%
            {%
                \LWR@tdaddstyle%
                border-top: 2px dashed%
            }{% else
            \ifnumcomp{\value{LWR@hdashedlines}}{=}{1}%
            {%
                \LWR@tdaddstyle%
                border-top: 1px dashed%
            }{}}}%
```

If no color and not doubled or dashed, then add nothing, since a simpler rule is the default.

```
        }%
```

If there is a custom color:

```
        {%
            \ifnumcomp{\value{LWR@hlines}}{>}{1}%
            {%
                \LWR@tdaddstyle%
                border-top: 4px double \LWR@origpound\LWR@ruleHTMLcolor%
            }{% else
            \ifnumcomp{\value{LWR@hdashedlines}}{>}{1}%
            {%
                \LWR@tdaddstyle%
                border-top: 2px dashed \LWR@origpound\LWR@ruleHTMLcolor%
            }{% else
            \ifnumcomp{\value{LWR@hdashedlines}}{=}{1}%
            {%
                \LWR@tdaddstyle%
                border-top: 1px dashed \LWR@origpound\LWR@ruleHTMLcolor%
            }{% else
                \LWR@tdaddstyle%
```

```
                border-top: 1px solid \LWR@origpound\LWR@ruleHTMLcolor%
            }}}%
        }%
    }{}%
}
```

`\LWR@addtabularrulecolors` Adds a cell's rule color styles, if needed.

No color is added for the final row of empty cells which finishes each `tabular`.

```
\newcommand*{\LWR@addtabularrulecolors}{%
```

Custom horizonal rule color:

```
    \LWR@addtabularhrulecolor%
```

No vertical rules if finishing the `tabular` with a row of empty cells:

```
    \ifbool{LWR@tabularmutemods}{}{%
```

If at the leftmost cell, possibly add a leftmost vertical rule:

```
        \ifnumequal{\value{LWR@tableLaTeXcolindex}}{1}{%
```

Fetch the left edge's vertical bar specification:

```
            \edef\LWR@tempone{\LWR@getexparray{LWR@colbarspec}{leftedge}}%
```

Add a custom style if a vertical bar was requested:

```
            \ifdefstring{\LWR@tempone}{tvertbarl}{%
                    \LWR@tdaddstyle%
                    border-left: 1px solid % space
                        \LWR@vertruleHTMLcolor%
            }{}%
            \ifdefstring{\LWR@tempone}{tvertbarldouble}{%
                    \LWR@tdaddstyle%
                    border-left: 4px double % space
                        \LWR@vertruleHTMLcolor%
            }{}%
            \ifdefstring{\LWR@tempone}{tvertbarldash}{%
                    \LWR@tdaddstyle%
                    border-left: 1px dashed % space
                        \LWR@vertruleHTMLcolor%
            }{}%
            \ifdefstring{\LWR@tempone}{tvertbarldoubledash}{%
                    \LWR@tdaddstyle%
                    border-left: 2px dashed % space
                        \LWR@vertruleHTMLcolor%
            }{}%
        }{}%
```

Possibly add a right vertical rule for this cell:

```
        \edef\LWR@tempone{%
            \LWR@getexparray{LWR@colbarspec}{\arabic{LWR@tableLaTeXcolindex}}%
        }%
        \ifdefstring{\LWR@tempone}{tvertbarr}{%
```

Add a custom style if a vertical bar was requested:

```
                \LWR@tdaddstyle%
                border-right: 1px solid \LWR@vertruleHTMLcolor%
        }{}%
        \ifdefstring{\LWR@tempone}{tvertbarrdouble}{%
                \LWR@tdaddstyle%
                border-right: 4px double \LWR@vertruleHTMLcolor%
        }{}%
        \ifdefstring{\LWR@tempone}{tvertbarrdash}{%
                \LWR@tdaddstyle%
                border-right: 1px dashed \LWR@vertruleHTMLcolor%
        }{}%
        \ifdefstring{\LWR@tempone}{tvertbarrdoubledash}{%
                \LWR@tdaddstyle%
                border-right: 2px dashed \LWR@vertruleHTMLcolor%
        }{}%
    }%
}
```

`\LWR@subaddtabularcellcolor` {⟨*HTML color*⟩}

```
\newcommand*{\LWR@subaddtabularcellcolor}[1]{%
    \LWR@htmltag{div class=\textquotedbl{}cellcolor\textquotedbl\ % space
        style=\textquotedbl{}%
        background:\LWR@origpound{}{}#1 %
        \textquotedbl\ %
    }% space
    \defaddtocounter{LWR@cellcolordepth}{1}%
}
```

`\LWR@addtabularcellcolor` Adds a cell color style, if needed.

```
\newcommand*{\LWR@addtabularcellcolor}{%
    \ifdefvoid{\LWR@cellHTMLcolor}%
    {%
        \ifdefvoid{\LWR@rowHTMLcolor}%
        {%
            \ifdefvoid{\LWR@xcolorrowHTMLcolor}%
            {%
                \ifdefvoid{\LWR@columnHTMLcolor}%
                {}%
                {\LWR@subaddtabularcellcolor{\LWR@columnHTMLcolor}}%
            }%
            {\LWR@subaddtabularcellcolor{\LWR@xcolorrowHTMLcolor}}%
        }%
        {\LWR@subaddtabularcellcolor{\LWR@rowHTMLcolor}}%
    }%
    {\LWR@subaddtabularcellcolor{\LWR@cellHTMLcolor}}%
}
```

75.23 Multicolumns

75.23.1 Parsing multicolumns

\LWR@printmccoltype {⟨*colspec*⟩} Print any valid column type found. Does not print `@`, `!`, `>`, or `<` columns or their associated tokens.

This is printed as part of the table data tag's `class`.

```
\newcommand*{\LWR@printmccoltype}[1]{%
    \LWR@traceinfo{lwr@printmccoltype -#1-}%
```

Get one token of the column spec:

```
    \StrChar{#1}{\arabic{LWR@tablemulticolspos}}[\LWR@strresult]%
```

Add to the HTML tag depending on which column type is found:

```
    \IfStrEq{\LWR@strresult}{l}{l}{}%
    \IfStrEq{\LWR@strresult}{c}{c}{}%
    \IfStrEq{\LWR@strresult}{r}{r}{}%
    \IfStrEq{\LWR@strresult}{p}{p}{}%
    \IfStrEq{\LWR@strresult}{m}{m}{}%
    \IfStrEq{\LWR@strresult}{b}{b}{}%
    \IfStrEq{\LWR@strresult}{P}{P}{}%
    \IfStrEq{\LWR@strresult}{M}{M}{}%
    \IfStrEq{\LWR@strresult}{B}{B}{}%

    \IfStrEq{\LWR@strresult}{w}{w}{}%
    \IfStrEq{\LWR@strresult}{W}{W}{}%

    \IfStrEq{\LWR@strresult}{S}{c}{}%
    \IfStrEq{\LWR@strresult}{s}{c}{}%

    \IfStrEq{\LWR@strresult}{X}{p}{}%

    \IfStrEq{\LWR@strresult}{|}%
    {%
        \ifbool{LWR@mcolvertbaronleft}%
            {\defaddtocounter{LWR@mcolvertbarsl}{1}}% left edge
            {\defaddtocounter{LWR@mcolvertbarsr}{1}}% not left edge
    }%
    {%
        \IfStrEq{\LWR@strresult}{:}%
        {%
            \ifbool{LWR@mcolvertbaronleft}%
                {\defaddtocounter{LWR@mcolvertbarsldash}{1}}% left edge
                {\defaddtocounter{LWR@mcolvertbarsrdash}{1}}% not left edge
        }%
        {%
            \IfStrEq{\LWR@strresult}{;}%
            {%
                \ifbool{LWR@mcolvertbaronleft}%
```

```
                    {\defaddtocounter{LWR@mcolvertbarsldash}{1}}% left edge
                   {\defaddtocounter{LWR@mcolvertbarsrdash}{1}}% not left edge
            }%
            {\boolfalse{LWR@mcolvertbaronleft}}%
        }%
    }%
    \LWR@traceinfo{lwr@printmccoltype done}%
}
```

`\LWR@multicolpartext` {⟨*num parameters*⟩} Print the data with paragraph tags, advance to bypass the given number of parameters.

```
\newcommand*{\LWR@multicolpartext}[1]{%
    \LWR@startpars%
    \LWR@multicoltext%
    \defaddtocounter{LWR@tablemulticolspos}{#1}%
    \LWR@stoppars%
}
```

`\LWR@multicolother` {⟨*colspec*⟩} For `@`, `!`, `>`, `<`, print the next token without paragraph tags:

```
\newcommand*{\LWR@multicolother}[1]{%
    \defaddtocounter{LWR@tablemulticolspos}{1}%
    \StrChar{#1}{\arabic{LWR@tablemulticolspos}}[\LWR@strresult]%
    \LWR@strresult%
```

A valid column data type was found:

```
    \booltrue{LWR@validtablecol}%
}
```

`\LWR@multicolskip` Nothing to print for this column type.

```
\newcommand*{\LWR@multicolskip}{%
```

A valid column data type was found:

```
    \booltrue{LWR@validtablecol}%
}
```

`\LWR@printmccoldata` {⟨*colspec*⟩} Print the data for any valid column type found.

```
\newcommand*{\LWR@printmccoldata}[1]{%
    \LWR@traceinfo{lwr@printmccoldata -#1}%
```

Not yet found a valid column type:

```
    \boolfalse{LWR@validtablecol}%
```

Get one token of the column spec, into a local copy in case nested.

```
    \StrChar{#1}{\arabic{LWR@tablemulticolspos}}[\LWR@strresult]%
    \edef\LWR@printmccoldatatoken{\LWR@strresult}%
```

Print the text depending on which column type is found. Also handles `@`, `>`, `<` as it comes to them.

```
    \IfStrEq{\LWR@printmccoldatatoken}{l}{\LWR@multicoltext}{}%
    \IfStrEq{\LWR@printmccoldatatoken}{c}{\LWR@multicoltext}{}%
    \IfStrEq{\LWR@printmccoldatatoken}{r}{\LWR@multicoltext}{}%
    \IfStrEq{\LWR@printmccoldatatoken}{D}{%
        \defaddtocounter{LWR@tablemulticolspos}{3}% skip parameters
        \LWR@multicoltext%
    }{}%

    \IfStrEq{\LWR@printmccoldatatoken}{p}{\LWR@multicolpartext{2}}{}%
    \IfStrEq{\LWR@printmccoldatatoken}{m}{\LWR@multicolpartext{2}}{}%
    \IfStrEq{\LWR@printmccoldatatoken}{b}{\LWR@multicolpartext{2}}{}%
    \IfStrEq{\LWR@printmccoldatatoken}{P}{\LWR@multicolpartext{2}}{}%
    \IfStrEq{\LWR@printmccoldatatoken}{M}{\LWR@multicolpartext{2}}{}%
    \IfStrEq{\LWR@printmccoldatatoken}{B}{\LWR@multicolpartext{2}}{}%

    \IfStrEq{\LWR@printmccoldatatoken}{w}{\LWR@multicolpartext{3}}{}%
    \IfStrEq{\LWR@printmccoldatatoken}{W}{\LWR@multicolpartext{3}}{}%

    \IfStrEq{\LWR@printmccoldatatoken}{S}{\LWR@multicoltext}{}%
    \IfStrEq{\LWR@printmccoldatatoken}{s}{\LWR@multicoltext}{}%

    \IfStrEq{\LWR@printmccoldatatoken}{X}{\LWR@multicolpartext{1}}{}%
    \IfStrEq{\LWR@printmccoldatatoken}{|}{\LWR@multicolskip}{}%
    \IfStrEq{\LWR@printmccoldatatoken}{:}{\LWR@multicolskip}{}%
    \IfStrEq{\LWR@printmccoldatatoken}{;}{%
        \LWR@multicolskip%
        \defaddtocounter{LWR@tablemulticolspos}{1}% skip parameter
    }{}%
   \IfStrEq{\LWR@printmccoldatatoken}{\detokenize{@}}{\LWR@multicolother{#1}}{}%
   \IfStrEq{\LWR@printmccoldatatoken}{\detokenize{!}}{\LWR@multicolother{#1}}{}%
   \IfStrEq{\LWR@printmccoldatatoken}{\detokenize{>}}{\LWR@multicolother{#1}}{}%
   \IfStrEq{\LWR@printmccoldatatoken}{\detokenize{<}}{\LWR@multicolother{#1}}{}%
```

If an invalid column type:

```
    \ifbool{LWR@validtablecol}{}{\LWR@multicoltext{}}%
```

Tracing:

```
    \LWR@traceinfo{lwr@printmccoldata done}%
}
```

`\parsemulticolumnalignment` {⟨*1: colspec*⟩} {⟨*2: printresults*⟩}

Scan the multicolumn specification and execute the printfunction for each entry.

Note that the spec for a `p{spec}` column, or `@`, `>`, `<`, is a token list which will NOT match `l`, `c`, `r`, or `p`.

```
\newcommand*{\LWR@parsemulticolumnalignment}[2]{%
```

```
    \defcounter{LWR@tablemulticolspos}{1}%
    \StrLen{#1}[\LWR@strresult]%
    \defcounter{LWR@tablemulticolswidth}{\LWR@strresult}%
```

Scan across the tokens in the column spec:

```
    \whileboolexpr{%
        not test {%
            \ifnumcomp{\value{LWR@tablemulticolspos}}{>}%
                {\value{LWR@tablemulticolswidth}}%
        }%
    }%
    {%
```

Execute the assigned print function for each token in the column spec:

```
        #2{#1}%
```

Move to the next token in the column spec:

```
        \defaddtocounter{LWR@tablemulticolspos}{1}%
    }%
}
```

75.23.2 Multicolumn factored code

`\LWR@addmulticolvertrulecolor`

```
\newcommand*{\LWR@addmulticolvertrulecolor}{%
```

No vertical rules if finishing the `tabular` with a row of empty cells:

```
    \ifbool{LWR@tabularmutemods}{}{%
```

Left side:

```
        \ifnumcomp{\value{LWR@mcolvertbarsl}}{=}{1}{%
            \LWR@tdaddstyle%
            border-left: 1px solid \LWR@vertruleHTMLcolor%
        }{}%
        \ifnumcomp{\value{LWR@mcolvertbarsl}}{>}{1}{%
            \LWR@tdaddstyle%
            border-left: 4px double \LWR@vertruleHTMLcolor%
        }{}%
        \ifnumcomp{\value{LWR@mcolvertbarsldash}}{=}{1}{%
            \LWR@tdaddstyle%
            border-left: 1px dashed \LWR@vertruleHTMLcolor%
        }{}%
        \ifnumcomp{\value{LWR@mcolvertbarsldash}}{>}{1}{%
            \LWR@tdaddstyle%
            border-left: 2px dashed \LWR@vertruleHTMLcolor%
        }{}%
```

Right side:

```
        \ifnumcomp{\value{LWR@mcolvertbarsr}}{=}{1}{%
            \LWR@tdaddstyle%
            border-right: 1px solid \LWR@vertruleHTMLcolor%
        }{}%
        \ifnumcomp{\value{LWR@mcolvertbarsr}}{>}{1}{%
            \LWR@tdaddstyle%
            border-right: 4px double \LWR@vertruleHTMLcolor%
        }{}%
        \ifnumcomp{\value{LWR@mcolvertbarsrdash}}{=}{1}{%
            \LWR@tdaddstyle%
            border-right: 1px dashed \LWR@vertruleHTMLcolor%
        }{}%
        \ifnumcomp{\value{LWR@mcolvertbarsrdash}}{>}{1}{%
            \LWR@tdaddstyle%
            border-right: 2px dashed \LWR@vertruleHTMLcolor%
        }{}%
    }%
}

\newcommand{\LWR@multicoltext}{}
```

To find multicolumn right trim:

```
\newcounter{LWR@lastmulticolumn}
```

`\LWR@domulticolumn` `[`⟨*1: vpos*⟩`]` `[`⟨*2: #rows*⟩`]` {⟨*3: numLaTeXcols*⟩} {⟨*4: numHTMLcols*⟩} {⟨*5: colspec*⟩} {⟨*6: text*⟩}

```
\NewDocumentCommand{\LWR@domulticolumn}{o o m m m +m}{%
    \LWR@traceinfo{LWR@domulticolumn -#1- -#2- -#4- -#5-}%
```

Remember the text to be inserted, and remember that a valid column type was found:

```
    \renewcommand{\LWR@multicoltext}{%
        #6%
        \booltrue{LWR@validtablecol}%
    }%
```

Compute the rightmost column to be included. This is used to create the right trim.

```
    \defcounter{LWR@lastmulticolumn}{\value{LWR@tableLaTeXcolindex}}%
    \defaddtocounter{LWR@lastmulticolumn}{#3}%
    \defaddtocounter{LWR@lastmulticolumn}{-1}%
```

Row processing:

```
    \LWR@maybenewtablerow%
```

Begin the opening table data tag:

```
    \LWR@htmltag{%
        td colspan=\textquotedbl#4\textquotedbl\ %
```

```
        \IfValueT{#2}{ % rows?
            rowspan=\textquotedbl#2\textquotedbl\ %
        }%

        class=\textquotedbl{}td%
```

Print the column type and vertical bars:

```
        \defcounter{LWR@mcolvertbarsl}{0}%
        \defcounter{LWR@mcolvertbarsr}{0}%
        \defcounter{LWR@mcolvertbarsldash}{0}%
        \defcounter{LWR@mcolvertbarsrdash}{0}%
        \booltrue{LWR@mcolvertbaronleft}%
        \LWR@parsemulticolumnalignment{#5}{\LWR@printmccoltype}%
```

If this column has a cmidrule, add "rule" to the end of the HTML class tag.

If this position had a "Y" then add "rule" for a horizontal rule:

```
        \LWR@subaddcmidruletrim%
            {%
                \LWR@getexparray{LWR@trimlrules}%
                    {\arabic{LWR@tableLaTeXcolindex}}%
            }%
            {%
                \LWR@getexparray{LWR@trimrrules}%
                    {\arabic{LWR@lastmulticolumn}}%
            }%
```

Also add vertical bar class.

```
        \ifnumcomp{\value{LWR@mcolvertbarsl}}{=}{1}{ tvertbarl}{}%
        \ifnumcomp{\value{LWR@mcolvertbarsl}}{>}{1}{ tvertbarldouble}{}%
        \ifnumcomp{\value{LWR@mcolvertbarsr}}{=}{1}{ tvertbarr}{}%
        \ifnumcomp{\value{LWR@mcolvertbarsr}}{>}{1}{ tvertbarrdouble}{}%
        \ifnumcomp{\value{LWR@mcolvertbarsldash}}{=}{1}{ tvertbarldash}{}%
        \ifnumcomp{\value{LWR@mcolvertbarsldash}}{>}{1}%
            { tvertbarldoubledash}{}%
        \ifnumcomp{\value{LWR@mcolvertbarsrdash}}{=}{1}{ tvertbarrdash}{}%
        \ifnumcomp{\value{LWR@mcolvertbarsrdash}}{>}{1}%
            { tvertbarrdoubledash}{}%
```

Close the class tag's opening quote:

```
        \textquotedbl{}%

        \LWR@tdstartstyles%
```

Style for vertical position:

```
        \IfValueT{#1}{% vpos?
            \ifstrequal{#1}{b}%
                {%
                    \LWR@tdaddstyle%
```

```
                    \LWR@print@mbox{vertical-align:bottom}%
                }{}%
            \ifstrequal{#1}{t}%
                {%
                    \LWR@tdaddstyle%
                    \LWR@print@mbox{vertical-align:top}%
                }{}%
        }% vpos?
```

Style for row colors:

```
        \LWR@addtabularrowcolor%
```

Other styles:

```
        \LWR@addcmidrulewidth%
        \LWR@addcdashline%
        \LWR@addtabularhrulecolor%
        \LWR@addmulticolvertrulecolor%
        \LWR@addformatwpalignment{#5}%
        \LWR@tdendstyles%
    }% end of the opening table data tag
    \boolfalse{LWR@intabularmetadata}%
    \LWR@parsemulticolumnalignment{#5}{\LWR@printmccoldata}%
}
```

75.23.3 Multicolumn

`\LWR@htmlmulticolumn` {⟨*numcols*⟩} {⟨*alignment*⟩} {⟨*text*⟩}

```
\NewDocumentCommand{\LWR@htmlmulticolumn}{m m +m}%
{%
```

Figure out how many extra HTML columns to add for `@` and `!` columns:

```
    \LWR@tabularhtmlcolumns{\arabic{LWR@tableLaTeXcolindex}}{#1}%
```

Create the multicolumn tag:

```
    \LWR@domulticolumn{#1}{\arabic{LWR@tabhtmlcoltotal}}{#2}{#3}%
```

Move to the next LaTeX column:

```
    \defaddtocounter{LWR@tableLaTeXcolindex}{#1}%
    \defaddtocounter{LWR@tableLaTeXcolindex}{-1}%
```

Skip any trailing `@` or `!` columns for this cell:

```
    \booltrue{LWR@skipatbang}%
}
```

75.23.4 Longtable captions

longtable captions use `\multicolumn`.

Per the caption package. User-redefinable float type.

```
\providecommand*{\LTcaptype}{table}
```

`\LWR@longtabledatacaptiontag` * [⟨*toc entry*⟩] {⟨*caption*⟩}

```
\NewDocumentCommand{\LWR@longtabledatacaptiontag}{s o +m}
{%
```

Remember the latest name for `\nameref`:

```
    \IfValueTF{#2}{% optional given?
        \ifblank{#2}% optional empty?
        {\LWR@setlatestname{#3}}% empty
        {\LWR@setlatestname{#2}}% given and non-empty
    }% optional given
    {\LWR@setlatestname{#3}}% no optional
```

Create a multicolumn across all the columns:

Figure out how many extra HTML columns to add for `@` and `!` columns found between the first and the last column:

```
    \LWR@tabularhtmlcolumns{1}{\arabic{LWR@tabletotalLaTeXcols}}%
```

Create the multicolumn tag:

```
    \LWR@domulticolumn{\arabic{LWR@tabletotalLaTeXcols}}%
        {\arabic{LWR@tabhtmlcoltotal}}%
        {P}%
    {% \LWR@domulticolumn
    \IfBooleanTF{#1}% star?
```

Star version, show a caption but do not make a LOT entry:

```
    {% yes star
        \LWR@figcaption%
        \LWR@isolate{#3}%
        \endLWR@figcaption%
    }%
    {% No star:
```

Not the star version:

Don't step the counter if `\caption[]{A caption.}`

```
        \ifbool{LWR@starredlongtable}%
        {%
            \ifblank{#2}% TOC entry
            {}%
```

```
            {%
                \refstepcounter{\LTcaptype}%
                \protected@edef\@currentlabel{%
                    \@nameuse{p@\LTcaptype}\@nameuse{the\LTcaptype}%
                }%
            }%
        }{}%
```

Create an HTML caption. Afterwards, maybe make a LOT entry.

```
        \LWR@figcaption%
        \LWR@isolate{\@nameuse{fnum@\LTcaptype}}%
        \CaptionSeparator%
        \LWR@isolate{#3}%
        \endLWR@figcaption%
```

See if an optional caption was given:

```
        \ifblank{#2}% TOC entry empty
```

if the optional caption was given, but empty, do not form a TOC entry

```
        {}%
```

If the optional caption was given, but might only be `[]`:

```
        {% TOC entry not empty
            \IfNoValueTF{#2}% No TOC entry?
```

The optional caption is `[]`:

```
            {% No TOC entry
                \addcontentsline%
                {\@nameuse{ext@\LTcaptype}}%
                {\LTcaptype}%
                {%
                    \protect\numberline%
              {\LWR@isolate{\@nameuse{p@\LTcaptype}}\@nameuse{the\LTcaptype}}%
                    {\ignorespaces \LWR@isolate{#3}\protect\relax}%
                }%
            }% end of No TOC entry
```

The optional caption has text enclosed:

```
            {% yes TOC entry
                \addcontentsline%
                {\@nameuse{ext@\LTcaptype}}%
                {\LTcaptype}%
                {%
                    \protect\numberline%
              {\LWR@isolate{\@nameuse{p@\LTcaptype}}\@nameuse{the\LTcaptype}}%
                    {\ignorespaces \LWR@isolate{#2}\protect\relax}%
                }%
            }% end of yes TOC entry
        }% end of TOC entry not empty
```

```
    }% end of no star
```

Skip any trailing `@` or `!` columns for this cell:

```
    \booltrue{LWR@skipatbang}%
    }% end of \LWR@domulticolumn
    \defaddtocounter{LWR@tableLaTeXcolindex}{\value{LWR@tabletotalLaTeXcols}}%
    \defaddtocounter{LWR@tableLaTeXcolindex}{-1}

}
```

75.23.5 Counting HTML tabular columns

The LaTeX specification for a table includes a number of columns separated by the `&` character. These columns differ in content from line to line. Additional virtual columns may be specified by the special `@` and `!` columns. These columns are identical from line to line, but may be skipped during a multicolumn cell.

For HTML output, `@` and `!` columns are placed into their own tabular columns. Thus, a LaTeX `\multicolumn` command may span several additional `@` and `!` columns in HTML output. These additional columns must be added to the total number of columns spanned by an HTML multi-column data cell.

```
\newcounter{LWR@tabhtmlcolindex}
\newcounter{LWR@tabhtmlcolend}
\newcounter{LWR@tabhtmlcoltotal}
```

`\LWR@subtabularhtmlcolumns` {⟨*index*⟩}

Factored from `\LWr@tabularhtmlcolumns`, which follows.

```
\newcommand*{\LWR@subtabularhtmlcolumns}[1]{%
```

Temporarily define a macro equal to the `@` specification for this column:

```
    \edef\LWR@atbangspec{\LWR@getexparray{LWR@colatspec}{#1}}%
```

If the `@` specification is not empty, add to the count:

```
    \ifdefempty{\LWR@atbangspec}%
        {}%
        {\defaddtocounter{LWR@tabhtmlcoltotal}{1}}%
```

Likewise for the `!` columns:

```
    \edef\LWR@atbangspec{\LWR@getexparray{LWR@colbangspec}{#1}}%
    \ifdefempty{\LWR@atbangspec}%
        {}%
        {\defaddtocounter{LWR@tabhtmlcoltotal}{1}}%
}
```

`\LWR@tabularhtmlcolumns` {⟨*starting LaTeX column*⟩} {⟨*number LaTeX columns*⟩}

Compute the total number of HTML columns being spanned, considering the starting LaTeX table column and the number of LaTeX tabular columns being spanned. Any `@` and `!` columns within this span are included in the total count. The resulting number of HTML columns is returned in the counter `LWR@tabhtmlcoltotal`.

```
\newcommand*{\LWR@tabularhtmlcolumns}[2]{%
```

Count the starting index, compute ending index, and begin with the count being the LaTeX span, to which additional `@` and `!` columns may be added:

```
    \defcounter{LWR@tabhtmlcolindex}{#1}%
    \defcounter{LWR@tabhtmlcoltotal}{#2}%
    \defcounter{LWR@tabhtmlcolend}{#1}%
    \defaddtocounter{LWR@tabhtmlcolend}{#2}%
```

If at the left edge, add the at/bang columns for the left edge:

```
    \ifnumcomp{\value{LWR@tabhtmlcolindex}}{=}{1}{%
        \LWR@subtabularhtmlcolumns{leftedge}%
    }{}%
```

Walk across the LaTeX columns looking for `@` and `!` columns:

```
    \whileboolexpr{%
        test {%
        \ifnumcomp{\value{LWR@tabhtmlcolindex}}{<}{\value{LWR@tabhtmlcolend}}%
        }%
    }%
    {%
        \LWR@subtabularhtmlcolumns{\arabic{LWR@tabhtmlcolindex}}%
        \defaddtocounter{LWR@tabhtmlcolindex}{1}%
    }% whiledo
}
```

```
\end{warpHTML}
```

75.24 Multirow if not loaded

A default defintion in case multirow is not loaded. This is used during table parsing.

```
\begin{warpHTML}
\newcommand{\multirow}[2][c]{}
\end{warpHTML}
```

75.25 Multicolumnrow

A print-mode version is defined here, and is also used during HTML output while inside a `latexmage`.

See section 424 for the HTML versions.

for HTML & PRINT:

```
\begin{warpall}
```

\multicolumnrow {⟨*1:cols*⟩} {⟨*2:halign*⟩} [⟨*3:vpos*⟩] {⟨*4:numrows*⟩} [⟨*5:bigstruts*⟩] {⟨*6:width*⟩} [⟨*7:fixup*⟩] {⟨*8:text*⟩}

For discussion of the use of \DeclareExpandableDocumentCommand, see:
https://tex.stackexchange.com/questions/168434/problem-with-abbreviation-of-multirow-and-multicolumn-latex

\AtBeginDocument to adjust after the user may have loaded multirow, which requires several tests to determine which version is loaded and thus which options are available.

```
\AtBeginDocument{
```

\@ifundefined{@xmultirow} determines if multirow was never loaded.

Null action if not loaded:

```
\@ifundefined{@xmultirow}
{
\DeclareExpandableDocumentCommand{\LWR@print@multicolumnrow}%
    {+m +m +O{c} +m +O{0} +m +O{0pt} +m}%
    {}%
}% no version of multirow was loaded
{% \@xmultirow defined, so some version of multirow was loaded
```

\@ifpackageloaded{multirow} determines if v2.0 or later of multirow was used, which included the \ProvidesPackage macro.

The print version:

```
\@ifpackageloaded{multirow}{% v2.0 or newer
\@ifpackagelater{multirow}{2016/09/01}% 2016/09/27 for v2.0
{% v2.0+:
\DeclareExpandableDocumentCommand{\LWR@print@multicolumnrow}%
    {+m +m +O{c} +m +O{0} +m +O{0pt} +m}%
    {\multicolumn{#1}{#2}{\@xmultirow[#3]{#4}[#5]{#6}[#7]{#8}}}%
}
{% loaded but older, probably not executed:
\DeclareExpandableDocumentCommand{\LWR@print@multicolumnrow}%
    {+m +m +O{c} +m +O{0} +m +O{0pt} +m}%
    {\multicolumn{#1}{#2}{\@xmultirow{#4}[#5]{#6}[#7]{#8}}}%
}
}% packageloaded{multirow}
```

If not \@ifpackageloaded{multirow} but \@xmultirow is defined, then this must be v1.6 or earlier, which did not \ProvidesPackage{multirow}, and did not have the vposn option.

```
{% v1.6 or older did not \ProvidePackage
\DeclareExpandableDocumentCommand{\LWR@print@multicolumnrow}%
    {+m +m +O{c} +m +O{0} +m +O{0pt} +m}%
    {\multicolumn{#1}{#2}{\@xmultirow{#4}[#5]{#6}[#7]{#8}}}%
}

}% \@ifundefined{@xmultirow}

```

```
\providecommand*{\multicolumnrow}{\LWR@print@multicolumnrow}

}% AtBeginDocument

\end{warpall}
```

75.26 Utility macros inside a table

for HTML output:

```
\begin{warpHTML}
```

Used to prevent opening a tabular data cell if the following token is one which does not create tabular data:

```
\newcommand*{\LWR@donothing}{}
```

In case array is not loaded:

```
\let\firsthline\relax
\let\lasthline\relax
\newcommand*{\firsthline}{}
\newcommand*{\lasthline}{}
```

In case bigdelim is not loaded:

```
\newcommand*{\ldelim}{}
\newcommand*{\rdelim}{}

\end{warpHTML}
```

75.27 Special-case tabular markers

for HTML & PRINT:

```
\begin{warpall}
```

`\TabularMacro` Place this just before inserting a custom macro in a table data cell. Doing so tells lwarp not to automatcally start a new HTML table data cell yet. See section 8.10.1.

```
\newcommand*{\TabularMacro}{}

\end{warpall}
```

`\ResumeTabular` Used to resume tabular entries after resuming an environment.

⚠ `tabular` inside another environment

When creating a new environment which contains a `tabular` environment, lwarp's emulation of the tabular does not automatically resume when the containing enviroment ends, resulting in corrupted HTML rows. To fix this, use `\ResumeTabular` as follows. This is ignored in print mode.

```
\StartDefiningTabulars %   (& is used in a definition)
\newenvironment{outerenvironment}
{
  \tabular{cc}
  left & right \\
}
{
  \TabularMacro\ResumeTabular
  left & right \\
  \endtabular
}
\StopDefiningTabulars
```

for HTML output:

```
\begin{warpHTML}

\newcommand*{\ResumeTabular}{%
    \boolfalse{LWR@exitingtabular}%
    \boolfalse{LWR@tabularmutemods}%
    \LWR@getmynexttoken%
}

\end{warpHTML}
```

for PRINT output:

```
\begin{warpprint}

\newcommand*{\ResumeTabular}{}

\end{warpprint}
```

75.28 Checking for a new table cell

for HTML output:

```
\begin{warpHTML}
```

`\LWR@tabledatacolumntag`

Open a new HTML table cell unless the next token is for a macro which does not create data, such as `\hline`, `\toprule`, etc:

```
\newcommand*{\LWR@tabledatacolumntag}%
{%
    \LWR@traceinfo{LWR@tabledatacolumntag}%
```

`\show\LWR@mynexttoken` to see what tokens to look for

If not any of the below, start a new table cell:

```
    \global\let\LWR@mynextaction\LWR@tabledatasinglecolumntag%
```

If exiting the tabular:

```
    \ifdefequal{\LWR@mynexttoken}{\end}%
        {\booltrue{LWR@exitingtabular}}{}%
```

longtable can have a caption in a cell

```
    \ifdefequal{\LWR@mynexttoken}{\caption}%
        {\global\let\LWR@mynextaction\LWR@donothing}{}%
```

Look for other things which would not start a table cell:

```
    \ifdefequal{\LWR@mynexttoken}{\multicolumn}%
        {\global\let\LWR@mynextaction\LWR@donothing}{}%
    \ifdefequal{\LWR@mynexttoken}{\multirow}%
        {\global\let\LWR@mynextaction\LWR@donothing}{}%
    \ifdefequal{\LWR@mynexttoken}{\multicolumnrow}%
        {\global\let\LWR@mynextaction\LWR@donothing}{}%
    \ifdefequal{\LWR@mynexttoken}{\noalign}%
        {\global\let\LWR@mynextaction\LWR@donothing}{}%
```

If an \mrowcell, this is a cell to be skipped over:

```
    \ifdefequal{\LWR@mynexttoken}{\mrowcell}%
        {\global\let\LWR@mynextaction\LWR@donothing}{}%
```

If an \mcolrowcell, this is a cell to be skipped over:

```
    \ifdefequal{\LWR@mynexttoken}{\mcolrowcell}%
        {\global\let\LWR@mynextaction\LWR@donothing}{}%

    \ifdefequal{\LWR@mynexttoken}{\TabularMacro}%
        {\global\let\LWR@mynextaction\LWR@donothing}{}%

    \ifdefequal{\LWR@mynexttoken}{\hline}%
        {\global\let\LWR@mynextaction\LWR@donothing}{}%

    \ifdefequal{\LWR@mynexttoken}{\firsthline}%
        {\global\let\LWR@mynextaction\LWR@donothing}{}%

    \ifdefequal{\LWR@mynexttoken}{\lasthline}%
        {\global\let\LWR@mynextaction\LWR@donothing}{}%

    \ifdefequal{\LWR@mynexttoken}{\toprule}%
        {\global\let\LWR@mynextaction\LWR@donothing}{}%

    \ifdefequal{\LWR@mynexttoken}{\midrule}%
        {\global\let\LWR@mynextaction\LWR@donothing}{}%

    \ifdefequal{\LWR@mynexttoken}{\cmidrule}%
        {\global\let\LWR@mynextaction\LWR@donothing}{}%


    \ifdefequal{\LWR@mynexttoken}{\morecmidrules}%
        {\global\let\LWR@mynextaction\LWR@donothing}{}%

    \ifdefequal{\LWR@mynexttoken}{\specialrule}%
        {\global\let\LWR@mynextaction\LWR@donothing}{}%
```

```
    \ifdefequal{\LWR@mynexttoken}{\cline}%
        {\global\let\LWR@mynextaction\LWR@donothing}{}%

    \ifdefequal{\LWR@mynexttoken}{\bottomrule}%
        {\global\let\LWR@mynextaction\LWR@donothing}{}%

    \ifdefequal{\LWR@mynexttoken}{\hhline}%
        {\global\let\LWR@mynextaction\LWR@donothing}{}%

    \ifdefequal{\LWR@mynexttoken}{\rowcolor}%
        {\global\let\LWR@mynextaction\LWR@donothing}{}%

    \ifdefequal{\LWR@mynexttoken}{\arrayrulecolor}%
        {\global\let\LWR@mynextaction\LWR@donothing}{}%

    \ifdefequal{\LWR@mynexttoken}{\doublerulesepcolor}%
        {\global\let\LWR@mynextaction\LWR@donothing}{}%

    \ifdefequal{\LWR@mynexttoken}{\warpprintonly}%
        {\global\let\LWR@mynextaction\LWR@donothing}{}%

    \ifdefequal{\LWR@mynexttoken}{\warpHTMLonly}%
        {\global\let\LWR@mynextaction\LWR@donothing}{}%

    \ifdefequal{\LWR@mynexttoken}{\ldelim}%
        {\global\let\LWR@mynextaction\LWR@donothing}{}%

    \ifdefequal{\LWR@mynexttoken}{\rdelim}%
        {\global\let\LWR@mynextaction\LWR@donothing}{}%
```

For arydshln:

```
    \ifdefequal{\LWR@mynexttoken}{\hdashline}%
        {\global\let\LWR@mynextaction\LWR@donothing}{}%

    \ifdefequal{\LWR@mynexttoken}{\cdashline}%
        {\global\let\LWR@mynextaction\LWR@donothing}{}%

    \ifdefequal{\LWR@mynexttoken}{\firsthdashline}%
        {\global\let\LWR@mynextaction\LWR@donothing}{}%

    \ifdefequal{\LWR@mynexttoken}{\lasthdashline}%
        {\global\let\LWR@mynextaction\LWR@donothing}{}%
```

Ignore an empty line between rows:

```
    \ifdefequal{\LWR@mynexttoken}{\par}%
        {\global\let\LWR@mynextaction\LWR@donothing}{}%
```

No action for an \end token.

Add similar to the above for any other non-data tokens which might appear in the table.

Start the new table cell if was not any of the above:

```
    \LWR@traceinfo{LWR@tabledatacolumntag: about to do mynext}%
    \LWR@mynextaction%
    \LWR@traceinfo{LWR@tabledatacolumntag: done}%
}
```

```
\end{warpHTML}
```

75.29 \mrowcell

for HTML & PRINT:

```
\begin{warpall}
```

\mrowcell
⚠ multirow cells

The user must insert \mrowcell into any \multirow cells which must be skipped. This command has no action during print output.

```
\newcommand*{\mrowcell}{}
```

```
\end{warpall}
```

75.30 \mcolrowcell

for HTML & PRINT:

```
\begin{warpall}
```

\mcolrowcell
⚠ multirow cells

The user must insert \mcolrowcell into any \multicolumnrow cells which must be skipped. This command has no action during print output.

```
\newcommand*{\mcolrowcell}{}
```

```
\end{warpall}
```

75.31 HTML tabular environment

for HTML output:

```
\begin{warpHTML}
```

These are default defininitions in case booktabs is not loaded, and are not expected to used, but must exist as placeholders. memoir may have already loaded booktabs.

```
\providecommand*{\toprule}[1][]{\hline}
\providecommand*{\midrule}[1][]{\hline}
\providecommand*{\cmidrule}{\cline}
\providecommand*{\bottomrule}[1][]{\hline}
\providecommand*{\addlinespace}[1][]{}
\providecommand*{\morecmidrules}{}
\providecommand*{\specialrule}[3]{\hline}
```

`\noalign` {⟨*text*⟩} Redefined for use inside `tabular`.

```
\LetLtxMacro\LWR@orignoalign\noalign

\newcommand{\LWR@tabularnoalign}[1]{%
    \advance\rownum\m@ne%
    \LetLtxMacro\LWR@save@xcolorrowHTMLcolor\LWR@xcolorrowHTMLcolor%
    \renewcommand*{\LWR@xcolorrowHTMLcolor}{}%
    \multicolumn{\value{LWR@tabletotalLaTeXcols}}{l}{#1} \\
    \LetLtxMacro\LWR@xcolorrowHTMLcolor\LWR@save@xcolorrowHTMLcolor%
    % \@rowc@lors%
    \LWR@getmynexttoken%
}
```

`\LWR@HTMLhline` The definition of `\hline` depends on whether tabls has been loaded. If so, optional space below the line may be specified, but will be ignored.

```
\AtBeginDocument{

\@ifpackageloaded{lwarp-tabls}
{
    \newcommand*{\LWR@HTMLhline}[1][]{%
        \ifbool{FormatWP}%
            {\LWR@docmidrule{1-\arabic{LWR@tabletotalLaTeXcols}}}%
            {\defaddtocounter{LWR@hlines}{1}}%
        \LWR@getmynexttoken}%
}
{
    \newcommand*{\LWR@HTMLhline}{%
        \ifbool{FormatWP}%
            {\LWR@docmidrule{1-\arabic{LWR@tabletotalLaTeXcols}}}%
            {\defaddtocounter{LWR@hlines}{1}}%
        \LWR@getmynexttoken}%
}

}% AtBeginDocument
```

`\LWR@HTMLcline` {⟨*columns*⟩}

```
\NewDocumentCommand{\LWR@HTMLcline}{m}%
    {\LWR@docmidrule{#1}\LWR@getmynexttoken}%
```

`\LWR@tabular@warpprintonly` {⟨*contents*⟩}

Only process the contents if producing printed output. Modified inside a `tabular` to grab the next token.

```
\newcommand{\LWR@tabular@warpprintonly}[1]{%
    \ifbool{warpingprint}{#1}{}%
    \LWR@getmynexttoken%
}
```

\LWR@nullifyNoAutoSpacing For babel-french, turn off auto spacing at the start of the tabular, then nullify the autospacing commands inside the tabular, since they were not compatible with the tabular parsing code for each cell, which uses xstring.

```
\AtBeginDocument{
\@ifundefined{NoAutoSpacing}%
{% no babel-french
    \newcommand*{\LWR@nullifyNoAutoSpacing}{}
}% no babel-french
{% yes babel-french
    \newcommand*{\LWR@nullifyNoAutoSpacing}{%
        \NoAutoSpacing%
        \renewcommand*{\NoAutoSpacing}{}%
        \renewcommand*{\LWR@FBcancel}{}%
    }
}% yes babel-french
}% AtBeginDocument
```

Env tabular <direction> [⟨*vertposition*⟩] {⟨*colspecs*⟩}

The <direction> is from plext for Japanese documents, and is ignored.

```
\StartDefiningTabulars

\NewDocumentCommand{\LWR@HTML@@tabular}{d<> o m}
{%
    \LWR@traceinfo{LWR@HTML@@tabular started}%
```

⚠ <table> inside In LaTeX, a tabular may be placed inside a minipage, but in HTML a <table> may not be inside a . Since there may be several nested s, with an unknown number of other objects between, it is hard to undo all these s before the <table> then redo them after. The broswer probably compensates for this situation, but formatting may be lost inside the <table> because several things are neutralized inside a . Furthermore, in the HTML output, the entire <table> is placed on a single line of HTML code, since the line breaking commands are neutralized inside a . Since this is such a sloppy situation, a warning is issued here instructing the user to please isolate the to print-only.

```
    \LWR@spanwarnformat{tabular}%
    \addtocounter{LWR@tabulardepth}{1}%
```

Not yet started a table row:

```
    \boolfalse{LWR@startedrow}%
```

Not yet doing any rules:

```
    \defcounter{LWR@hlines}{0}%
    \defcounter{LWR@hdashedlines}{0}%
    \boolfalse{LWR@doingtbrule}%
    \boolfalse{LWR@doingcmidrule}%
```

For babel-french, turn off auto spacing one time, then nullify the autospacing commands since were not compatible with the tabular parsing code.

```
\LWR@nullifyNoAutoSpacing%
```

Have not yet found the end of tabular command. Unmute the `@` and `!` columns.

```
\boolfalse{LWR@exitingtabular}%
\boolfalse{LWR@tabularmutemods}%
```

Error if failed to use `\mrowcell` or `\mcolrowcell` when needed.

```
\boolfalse{LWR@usedmultirow}%
\boolfalse{LWR@foundmrowcell}%

\renewcommand*{\LWR@multicoltext}{}%
```

Create the `table` tag:

```
\booltrue{LWR@intabularmetadata}%
\LWR@traceinfo{LWR@@tabular: About to LWR@forecenewpage.}%
\LWR@forcenewpage
\LWR@htmlblocktag{table}%
```

Parse the table columns:

```
\LWR@parsetablecols{#3}%
```

Table col spec is: `\LWR@tablecolspec` which is a string of `llccrr`, etc.

Do not place the table inside a paragraph:

```
\LWR@stoppars%
```

Track column #:

```
\defcounter{LWR@tableLaTeXcolindex}{1}%
```

Have not yet added data in this column:

```
\global\boolfalse{LWR@tabularcelladded}%
```

Start looking for midrules:

```
\LWR@clearmidrules%
```

`\\` becomes a macro to end the table row:

```
\LetLtxMacro{\\}{\LWR@tabularendofline}%
```

`\warpprintonly` inside a `tabular` must grab the next token.

```
\LetLtxMacro\warpprintonly\LWR@tabular@warpprintonly%
```

The following adjust for colortbl.

```
\LetLtxMacro\arrayrulecolor\arrayrulecolornexttoken%
\LetLtxMacro\doublerulesepcolor\doublerulesepcolornexttoken%
\def\LWR@columnHTMLcolor{}%
\def\LWR@rowHTMLcolor{}%
\def\LWR@cellHTMLcolor{}%
\@rowcolors%
```

The vertical rules are set to the color active at the start of the tabular. `\arrayrulecolor` will then affect horizontal rules inside the tabular, but not the vertical rules.

```
\ifdefvoid{\LWR@ruleHTMLcolor}%
    {\edef\LWR@vertruleHTMLcolor{black}}%
    {\edef\LWR@vertruleHTMLcolor{\LWR@origpound\LWR@ruleHTMLcolor}}%
```

Tracking the depth of cell color s:

```
\defcounter{LWR@cellcolordepth}{0}%
```

The following may appear before a data cell is created, so after doing their actions, we look ahead with `\LWR@getmynextoken` to see if the next token might create a new data cell:

The optional parameter for `\hline` supports the tabls package.

```
\LWR@traceinfo{LWR@@HTML@tabular: redefining macros}%
\LetLtxMacro\noalign\LWR@tabularnoalign%
\LetLtxMacro\hline\LWR@HTMLhline%
\LetLtxMacro\cline\LWR@HTMLcline%

\DeclareDocumentCommand{\hdashline}{o}{%
    \ifbool{FormatWP}%
        {\LWR@docdashline{1-\arabic{LWR@tabletotalLaTeXcols}}}%
        {\defaddtocounter{LWR@hdashedlines}{1}}%
    \LWR@getmynexttoken%
}%

\DeclareDocumentCommand{\cdashline}{m}{%
    \LWR@docdashline{##1}\LWR@getmynexttoken%
}%

\DeclareDocumentCommand{\firsthdashline}{o}{%
    \ifbool{FormatWP}%
        {\LWR@docdashline{1-\arabic{LWR@tabletotalLaTeXcols}}}%
        {\defaddtocounter{LWR@hdashedlines}{1}}%
    \LWR@getmynexttoken%
}%

\DeclareDocumentCommand{\lasthdashline}{o}{%
    \ifbool{FormatWP}%
        {\LWR@docdashline{1-\arabic{LWR@tabletotalLaTeXcols}}}%
        {\defaddtocounter{LWR@hdashedlines}{1}}%
    \LWR@getmynexttoken%
}%
```

The following create data cells and will have no more data in this cell, so we do not want to look ahead for a possible data cell, so do not want to use \LWR@getmynexttoken.

```
    \renewcommand{\multicolumn}{\LWR@htmlmulticolumn}%
    \renewcommand*{\mrowcell}{%
        \LWR@maybenewtablerow%
        \LWR@tabularleftedge%
        \booltrue{LWR@skippingmrowcell}%
        \booltrue{LWR@foundmrowcell}%
    }%
    \renewcommand*{\mcolrowcell}{%
        \LWR@maybenewtablerow%
        \booltrue{LWR@skippingmcolrowcell}%
        \booltrue{LWR@foundmrowcell}%
    }%
    \LetLtxMacro\caption\LWR@longtabledatacaptiontag%
```

Reset for new processing:

```
    \boolfalse{LWR@tableparcell}%
    \boolfalse{LWR@skippingmrowcell}%
    \boolfalse{LWR@skippingmcolrowcell}%
    \boolfalse{LWR@skipatbang}%
    \boolfalse{LWR@emptyatbang}%
```

Set & for its special meaning inside the tabular:

```
    \StartDefiningTabulars%
    \protected\gdef&{\LWR@tabularampersand}%
```

Locally force any minipages to be fullwidth, until the end of the tabular:

```
    \booltrue{LWR@forceminipagefullwidth}%
```

Nest one level deeper of tabular paragraph handling:

```
    \addtocounter{LWR@tabularpardepth}{1}%
```

Look ahead for a possible table data cell:

```
    \LWR@traceinfo{LWR@@HTML@tabular: about to LWR@getmynexttoken}%
    \LWR@getmynexttoken%
}%
```

Ending the environment:

```
\newcommand*{\LWR@HTML@endtabular}
{%
    \LWR@traceinfo{LWR@HTML@endtabular}%
```

Unnest one level of tabular paragraph handling:

```
    \addtocounter{LWR@tabularpardepth}{-1}%
    \ifboolexpr{%
```

```
        test {%
            \ifnumcomp{\value{LWR@tableLaTeXcolindex}}{<}%
                {\value{LWR@tabletotalLaTeXcols}}
        } or %
        (%
            bool{LWR@intabularmetadata} and%
            not bool{LWR@tabularcelladded} and%
            test {%
                \ifnumcomp{\value{LWR@tableLaTeXcolindex}}{=}%
                    {\value{LWR@tabletotalLaTeXcols}}%
            }%
        )%
    }%
    {%
        \LWR@tabularfinishrow%
    }%
    {%
        \LWR@closetabledatacell%
    }%
    \LWR@htmlblocktag{/tr}%
```

xcolor row color support:

```
    \@rowc@lors%
```

```
    \LWR@htmlblocktag{/table}%
    \boolfalse{LWR@intabularmetadata}%
```

Unnest one level of tabular:

```
    \addtocounter{LWR@tabulardepth}{-1}%
```

Restore & to its usual meaning:

```
    \ifnumequal{\value{LWR@tabulardepth}}{0}{%
        \protected\gdef&{\LWR@origampmacro}%
        \StopDefiningTabulars%
    }{}%
```

Error if used `\multirow` or `\multicolumnrow` without using `\mrowcell` or `\mcolrowcell`.

```
    \ifbool{LWR@usedmultirow}{%
        \ifbool{LWR@foundmrowcell}%
            {\relax}%
            {%
                \PackageError{lwarp}%
                {%
             When using \protect\multirow, \protect\multicolumnrow,\MessageBreak
                    or the bigdelim package,\MessageBreak
             place \protect\mrowcell\space or \protect\mcolrowcell\MessageBreak
                    in empty cells which are to be skipped.\MessageBreak
                    See the Lwarp package documentation:\MessageBreak
                    "Special cases and limitations" -> "Tabular"
                }%
```

```
                {%
                    See the Lwarp package documentation:\MessageBreak
                    "Special cases and limitations" -> "Tabular".
                }%
            }%
    }{}%

    \LWR@traceinfo{LWR@HTML@endtabular finished}%
}

\csletcs{LWR@HTML@endtabular*}{LWR@HTML@endtabular}

\StopDefiningTabulars
```

siunitx may redefine `tabular`, so set the following later:

```
\AtBeginDocument{
    \LetLtxMacro\LWR@origendtabular\endtabular
    \csletcs{LWR@origendtabular*}{endtabular*}
    \LWR@formatted{@tabular}
    \LWR@formatted{endtabular}
    \LWR@formatted{endtabular*}
}

\end{warpHTML}
```

76 Cross-references

Sections commands have been emulated from scratch, so the cross-referencing commands are custom-written for them. Emulating both avoids several layers of patches.

File `*_html.aux` A new entry in `*_html.aux` is used to remember section name, file, and lateximage depth and number for each label:

```
\newlabel{<labelname>@lwarp}{{<section name>}{<filename>}
                                    {<limagedepth>}{<limagenumber>}}
```

Table 15 shows the data structures related to cross-referencing.

for HTML output:

```
\begin{warpHTML}
```

76.1 Setup

`\@currentlabelname` To remember the most recently defined section name, description, or caption, for `\nameref`.

```
\def\@currentlabelname{\linkhomename}%
```

`\LWR@stripperiod` {⟨*text*⟩} [⟨.⟩]

Table 15: Cross-referencing data structures

Original LaTeX: (print and HTML)

\refstepcounter: Steps the couunter and sets `\@currentlabel`.

\@currentlabel: `\p@<ctr>\the<ctr>` Updated by `\refstepcounter`.

\label: Writes to the `.aux` file:
`\newlabel{<label>}{{\@currentlabel}{\thepage}}`

\newlabel: When the `.aux` file is read, sets `\r@<label>`.

\r@<label>: Set to: `{{\@currentlabel}{\thepage}}`

\ref: Returns the first part of `\r@<label>`.

\pageref: Returns the second part of `\r@<label>`.

Added by lwarp: (HTML only)

\label: Adds HTML tags (section 76.3), and another `.aux` entry (section 76.2). If memoir is used, its `\@mem@old@label` points to lwarp's version, and cleveref patches.

\newlabel: Unchanged. When the `.aux` file is read, sets `\r@<label>@lwarp`.

\r@<label>@lwarp: Set to `{{section_name}{file_name}{depth}{number}}`:

\LWR@nameref: The section or object name for this label.

\LWR@currentautosecpageref: The `LWR@currentautosecpage` for this label.

\LWR@htmlfileref: The filenumber or name for this label.

\LWR@lateximagedepthref: The `lateximagedepth` for this label.

\LWR@lateximagenumberref: The `lateximagenumber` for this label.

\nameref: Emualted from hyperref for lwarp. See section 76.4.

\ref and \nameref: Adds HTML tags. See section 76.4.

Added by amsmath: (print and HTML)

\label: Execution is delayed until the math environment is completed.

\ltx@label: LaTeX `\label`, (HTML: patched by lwarp,) later patched by cleveref.

Added by cleveref: (print and HTML)

\refstepcounter: Added: sets `\cref@currentlabel`.

\cref@currentlabel: (`<type>=<ctr>` unless an alias is used):
`[<type>][\arabic{<ctr>}][<parent ctrs>]{\p@<ctr>\the<ctr>}` Also see section 60.4 for use with footnotes.

\label: Writes to the `.aux` file:
`\newlabel{<label>@cref}{{\cref@currentlabel}{\thepage}}`

\newlabel: Unchanged. When the `.aux` file is read, sets `\r@<label>@cref`.

\r@<label>@cref: Set to: `{{\cref@currentlabel}{\thepage}}`

Utility functions: See `\cref@getlabel`, `\cref@gettype`, `\cref@getcounter`, `\cref@getprefix`.

Cross-referencing names: `\crefname` and `\Crefname` assign human-readable names for references to this counter type.

Additionally patched by lwarp: (HTML only)

\cref, etc.: Modified for lwarp. See section 200.

\label inside math: See section 83.7.1.

Footnotes: See `\noteentry` in section 60.4.

Removes a trailing period.

```
\def\LWR@stripperiod#1.\ltx@empty#2\@nil{#1}%
```

`\LWR@setlatestname` {⟨*object name*⟩}

Removes `\label`, strips any final period, and remembers the result.

```
\newcommand*{\LWR@setlatestname}[1]{%
```

Remove `\label` and other commands from the name, the strip any final period. See gettitlestring.

```
    \GetTitleStringExpand{#1}%
    \edef\@currentlabelname{\detokenize\expandafter{\GetTitleStringResult}}%
    \edef\@currentlabelname{%
        \expandafter\LWR@stripperiod\@currentlabelname%
        \ltx@empty.\ltx@empty\@nil%
    }%
}
```

76.2 New lwarp labels.

File `*_html.aux` A new entry in `*_html.aux` is used to remember section name, file, and latexmage depth and number for each label:

```
\newlabel{<labelname>@lwarp}{{<section name>}{<filename>}
                                    {<limagedepth>}{<limagenumber>}}
```

See:
http://tex.stackexchange.com/questions/57194/extract-section-number-from-equation-reference

`\LWR@setref` {⟨*args list*⟩} {⟨*selector*⟩} {⟨*label*⟩}

`\@setref` without the `\null` (`\hbox`), and without the warning messages. Each caused problems with lwarp references. The regular reference will cause the warning.

```
\def\LWR@setref#1#2#3{%
  \ifx#1\relax%
    ??%
  \else%
   \expandafter#2#1%
  \fi}
```

`\LWR@nameref` {⟨*label*⟩} Returns the section name for this label:

```
\newcommand*{\LWR@nameref}[1]{%
    \expandafter\LWR@setref\csname r@#1@lwarp\endcsname\LWR@firstoffive{#1}%
}
```

\LWR@currentautosecpageref {⟨*label*⟩} Returns the LWR@currentautosecpage for this label:

```
\newcommand*{\LWR@currentautosecpageref}[1]{%
    \expandafter\LWR@setref\csname r@#1@lwarp\endcsname\LWR@secondoffive{#1}%
}
```

\LWR@htmlfileref {⟨*label*⟩} Returns the file number or name for this label:

```
\newcommand*{\LWR@htmlfileref}[1]{%
    \expandafter\LWR@setref\csname r@#1@lwarp\endcsname\LWR@thirdoffive{#1}%
}
```

\LWR@lateximagedepthref {⟨*label*⟩} Returns the lateximagedepth for this label:

```
\newcommand*{\LWR@lateximagedepthref}[1]{%
    \expandafter\LWR@setref\csname r@#1@lwarp\endcsname\LWR@fourthoffive{#1}%
}
```

\LWR@lateximagenumberref {⟨*label*⟩} Returns the lateximagenumber for this label:

```
\newcommand*{\LWR@lateximagenumberref}[1]{%
    \expandafter\LWR@setref\csname r@#1@lwarp\endcsname\LWR@fifthoffive{#1}%
}
```

\LWR@write@lwarplabel {⟨*label*⟩} Sanitize the name and then creates the label:

```
\newcommand*{\LWR@write@lwarplabel}[1]{%
    \LWR@traceinfo{LWR@write@lwarplabel !#1!}%
    \LWR@setlatestname{\@currentlabelname}%
        \@bsphack%
        \protected@write\@auxout{}%
            {%
                \string\newlabel{#1@lwarp}{%
                    {\@currentlabelname}%
                    {\theLWR@currentautosecpage}%
                    {%
                        \ifbool{FileSectionNames}%
                            {\LWR@thisfilename}%
                            {\arabic{LWR@htmlfilenumber}}%
                    }%
                    {\arabic{LWR@lateximagedepth}}%
                    {\arabic{LWR@lateximagenumber}}%
                }%
            }%
        \@esphack%
}
```

76.3 Labels

\LWR@label@subcreatetag Creates the tag from \LWR@sanitized.

```
\newcommand*{\LWR@label@subcreatetag}{%
  \LWR@htmltag{a \LWR@print@mbox{id=\textquotedbl\LWR@sanitized\textquotedbl}}%
   \LWR@htmltag{/a}%
}
```

`\LWR@label@inmathcomment`

```
\newcommand*{\LWR@label@inmathcomment}{%
    \ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
    {%
```

The combined LaTeX & HTML label is printed in a `\mbox` field:

```
        \mbox{%
```

Shift the label over to the right side of the environment to avoid over-printing the math:

```
        \ifdef{\totwidth@}{\ifbool{LWR@amsmultline}{}{\hspace*{\totwidth@}}}{}%
```

Temporarily end the HTML comment, insert the LaTeX & HTML label, then resume the HTML comment. `\@firstofone` is required to remove extra braces introduced by the amsmath package.)

```
            \LWR@htmlclosecomment%
            \LWR@label@subcreatetag%
            \LWR@htmlopencomment%
        }% mbox
    }% mathjax
    {%
        \LWR@label@subcreatetag%
    }%
}
```

`\LWR@label@createtag` {⟨*label*⟩} Creates an HTML id tag.

Used by `\LWR@new@label` and `\hyperdef`.

`\detokenize` is used to allow underscores in the labels.

```
\newcommand*{\LWR@label@createtag}[1]{%
    \LWR@traceinfo{LWR@label@createtag !#1!}%
```

Create an HTML id tag unless are inside a lateximage, since it would appear in the image:

```
    \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
    {}%
    {% not lateximage
```

If not doing a lateximage, create an HTML ID tag.

```
        \LWR@sanitize{#1}%
        \ifbool{LWR@insidemathcomment}%
        {% inside HTML math comment
```

```
            \LWR@label@inmathcomment%
        }% inside HTML math comment
        {% not inside HTML math comment
            \ifbool{LWR@doingstartpars}%
            {% pars allowed
                \ifbool{LWR@doingapar}%
                {% par started
                    \LWR@label@subcreatetag%
                }% par started
                {% par not started
                    \LWR@stoppars%
                    \LWR@label@subcreatetag%
                    \LWR@startpars%
                }% par not started
            }% pars allowed
            {% pars not allowed
                    \LWR@label@subcreatetag%
            }% pars not allowed
        }% not inside HTML math comment
    }% not lateximage
}
```

`\LWR@new@label` {⟨*label*⟩}

`\label` during HTML output when not in SVG math mode, removing extra spaces around the label, as done by a regular LaTeX `\label`.

The is also used during a `lateximage`, including SVG math, since the special label handling is required, but `\LWR@label@createtag` does not generate HTML tags inside a `lateximage`.

If memoir is used, it's `\@mem@old@label` is pointed here.

clevereref later encases this to add its own cross-referencing, and also patches memoir.

```
\newcommand*{\LWR@new@label}[1]{%
    \LWR@traceinfo{LWR@new@label: starting}%
    \LWR@traceinfo{LWR@new@label: !#1!}%
% \@bsphack%
```

Create a traditional LaTeX label, as modified by cleveref:

```
    \LWR@orig@label{#1}%
```

Create a special label which holds the section number, section name, `LWR@htmlfilenumber`, `LWR@lateximagedepth`, and `LWR@lateximagenumber`:

```
    \LWR@traceinfo{%
        LWR@new@label: filesectionnames is %
        \ifbool{FileSectionNames}{true}{false}%
    }%
    \LWR@traceinfo{%
        LWR@new@label: LWR@thisfilename is !\LWR@thisfilename!%
    }%
    \LWR@traceinfo{%
        LWR@new@label: LWR@htmlfilenumber is \arabic{LWR@htmlfilenumber}%
```

```
    }%
    \LWR@write@lwarplabel{#1}%
    \LWR@label@createtag{#1}%
    % \@esphack%
    \LWR@traceinfo{LWR@new@label: done}%
}
```

76.4 References

\LWR@addlinktitle

```
\newcommand*{\LWR@addlinktitle}{%
    \ifdefvoid{\LWR@ThisAltText}{}{ % space
        title=\textquotedbl\LWR@ThisAltText\textquotedbl\ % space
        \gdef\LWR@ThisAltText{}%
    }%
}
```

\LWR@startref {⟨*label*⟩} (Common code for \ref and \nameref.)

Open an HTML tag reference to a filename, # character, and a label.

```
\newcommand*{\LWR@startref}[1]
{%
    \LWR@sanitize{#1}%
    \LWR@traceinfo{LWR@startref A: !#1!}%
```

Create the filename part of the link:

```
    \LWR@htmltag{a href=\textquotedbl%
    \LWR@traceinfo{LWR@startref B}%
    \LWR@print@mbox{\LWR@htmlrefsectionfilename{#1}}%
    \LWR@traceinfo{LWR@startref C}%
    \LWR@origpound%
```

Create the destination id:

See if LWR@lateximagedepth is unknown:

```
    \LWR@traceinfo{LWR@startref D: !#1!}%
    \ifcsundef{r@#1@lwarp}%
```

"??" if LWR@lateximagedepth is unknown, so create a link with an unknown destination:

```
    {%
        \LWR@traceinfo{LWR@startref D0: ??}%
        ??%
    }%
```

If LWR@lateximagedepth is known. Use a lateximage if the depth is greater than zero, or a regular link otherwise:

```
    {%
        \ifthenelse{\cnttest{\LWR@lateximagedepthref{#1}}{>}{0}}%
            {%
                lateximage-\BaseJobname-\LWR@lateximagenumberref{#1}%
            }%
            {%
                \LWR@traceinfo{LWR@startref D3}%
```

`\detokenize` is used to allow underscores in the labels:

```
                \LWR@print@mbox{\LWR@sanitized}%
            }%
    }%
    \LWR@traceinfo{LWR@startref E}%
```

Closing quote:

```
    \textquotedbl%
```

Maybe add a title:

```
    \LWR@addlinktitle%
    }%
    \LWR@traceinfo{LWR@startref F}%
}
```

`\LWR@subnewref` {⟨*label*⟩} {⟨*label or sub@label*⟩}

Factored for the subfig package. Uses the original label for the hyper-reference, but prints its own text, such as "1(b)".

```
\NewDocumentCommand{\LWR@subnewref}{m m}{%
    \LWR@traceinfo{LWR@subnewref #1 #2}%
    \LWR@startref{#1}%
    \LWR@print@ref{#2}%
    \LWR@htmltag{/a}%
}
```

`\ref` * {⟨*label*⟩} `\ref` is redefined to `\LWR@HTML@ref`, except inside the text part of a `\hyperref`, where it is redefined to `\LWR@ref@ignorestar`.

`\LWR@HTML@ref` * {⟨*label*⟩} Create an internal document reference link, or without a link if starred per hyperref.

hyperref defines a starred version. Since hyperref is only emulated, the starred version is defined here for print mode, in case `\ref` is used inside SVG math:

```
\LWR@absorbstar{ref}%
```

The HTML version:

```
\NewDocumentCommand{\LWR@HTML@ref}{s m}{%
    \LWR@traceinfo{LWR@HTML@ref !#2!}%
    \IfBooleanTF{#1}%
        {\LWR@print@ref{#2}}%
        {\LWR@subnewref{#2}{#2}}%
}

\LWR@formatted{ref}
```

\LWR@refwithsection

```
\NewDocumentCommand{\LWR@refwithsection}{s m}{%
    \LWR@traceinfo{LWR@refwithsection !#2!}%
    \IfBooleanTF{#1}%
       {\LWR@print@ref{\BaseJobname-autopage-\LWR@currentautosecpageref{#2}}}%
        {%
            \LWR@startref{#2}%
         \LWR@print@ref{\BaseJobname-autopage-\LWR@currentautosecpageref{#2}}%
            \LWR@htmltag{/a}%
        }%
}
```

For MathJax:

```
\CustomizeMathJax{\let\LWRref\ref}
\CustomizeMathJax{\renewcommand{\ref}{\ifstar\LWRref\LWRref}}
```

\pagerefPageFor Text for page references.

```
\newcommand*{\pagerefPageFor}{see }
```

\pageref * {⟨*label*⟩} Create an internal document reference, or just the unlinked number if starred, per hyperref.

```
\NewDocumentCommand{\LWR@new@pageref}{s m}{%
    \IfBooleanTF{#1}%
        {(\pagerefPageFor\LWR@print@ref{#2})}%
        {(\cpageref{#2})}%
}
```

\nameref {⟨*label*⟩}

```
\newrobustcmd*{\nameref}[1]{%
    \LWR@traceinfo{nameref}%
    \LWR@startref{#1}%
    \LWR@traceinfo{nameref B}%
    \LWR@nameref{#1}%
    \LWR@traceinfo{nameref C}%
    \LWR@htmltag{/a}%
    \LWR@traceinfo{nameref: done}%
}
```

`\Nameref` {⟨*label*⟩} In print, adds the page number. In HTML, does not.

```
\LetLtxMacro\Nameref\nameref
```

76.5 Hyper-references

⚠ Note that the code currently only sanitizes the underscore character. Additional characters should be rendered inert as well. See the `hyperref.sty` definition of `\gdef\hyper@normalise` for an example.

Pkg hyperref

⚠ Do not tell other packages that hyperref is emulated. Some packages patch various commands if hyperref is present, which will probably break something, and the emulation already handles whatever may be emulated anyhow.

```
% DO NOT TELL OTHER PACKAGES TO ASSUME HYPERREF, lest they attempt to patch it:
% \EmulatesPackage{hyperref}[2015/08/01]% Disabled.  Do not do this.
```

Emulates hyperref:

`\@currentHref` Added to support backref.

```
\AtBeginDocument{
    \def\@currentHref{\BaseJobname-autopage-\theLWR@previousautopagelabel}%
}
```

`\LWR@linkcatcodes` Sets catcodes before processing macros which have hyperlinks as arguments.

```
\newcommand*{\LWR@linkcatcodes}{%
    \catcode`\#=12%
    \catcode`\%=12%
    \catcode`\&=12%
    \catcode`\~=12%
    \catcode`\_=12%
```

For babel-french:

```
    \LWR@hook@processingtags%
}
```

`\LWR@linkmediacatcodes` Sets catcodes before processing macros which have hyperlinks as arguments. Modified for multimedia links.

```
\newcommand*{\LWR@linkmediacatcodes}{%
    \catcode`\#=12%
    \catcode`\%=12%
%   \catcode`\&=12% left alone for splitting flash variables
    \catcode`\~=12%
    \catcode`\_=12%
```

For babel-french:

```
    \LWR@hook@processingtags%
}
```

`\LWR@subhyperref` {⟨*URL*⟩}

Starts a link for `\LWR@hrefb`. A group must have been opened first, with nullified catcodes. The text name is printed afterwards, after the group is closed and catcodes restored.

```
\NewDocumentCommand{\LWR@subhyperref}{m}{%
    \LWR@traceinfo{LWR@subhyperref !#1!}%
    \LWR@sanitize{#1}%
    \LWR@htmltag{%
        a href=\textquotedbl\LWR@sanitized\textquotedbl\ % space
        \LWR@addlinktitle % space
        target=\textquotedbl\_{}blank\textquotedbl\ % space
    }%
}
```

`\LWR@subhyperreftext` {⟨*text*⟩}

Finishes the hyperref for `\LWR@hrefb`. Catcodes must have been restored already. To be used after `\LWR@subhyperref`, and after its group has been closed.

```
\newcommand{\LWR@subhyperreftext}[1]{%
    #1%
    \LWR@htmltag{/a}%
    \LWR@ensuredoingapar%
}
```

`\LWR@subhyperrefclass` {⟨*URL*⟩} {⟨*text*⟩} {⟨*htmlclass*⟩}

```
\NewDocumentCommand{\LWR@subhyperrefclass}{m +m m}{%
    \LWR@htmltag{%
        a % space
      href=\textquotedbl\begingroup\@sanitize#1\endgroup\textquotedbl\ % space
        class=\textquotedbl#3\textquotedbl\ % space
        \LWR@addlinktitle % space
    }\LWR@orignewline%
    #2%
    \LWR@htmltag{/a}%
    \LWR@ensuredoingapar%
}
```

`\LWR@href` [⟨*options*⟩] {⟨*URL*⟩} {⟨*text*⟩}

Create a link with accompanying text:

```
\DeclareDocumentCommand{\LWR@hrefb}{O{} m}{%
    \LWR@ensuredoingapar%
    \LWR@subhyperref{#2}%
    \endgroup% restore catcodes
```

```
    \LWR@subhyperreftext%
}

\newrobustcmd*{\LWR@href}{%
    \begingroup%
    \LWR@linkcatcodes%
    \LWR@hrefb%
}
```

`\LWR@nolinkurl` {⟨*URL*⟩}

Print the name of the link without creating the link:

```
\newcommand*{\LWR@nolinkurlb}[1]{%
    \LWR@ensuredoingapar%
    \def\LWR@templink{#1}%
    \@onelevel@sanitize\LWR@templink%
    \LWR@templink%
    \endgroup%
}

\newrobustcmd*{\LWR@nolinkurl}{%
    \begingroup%
    \LWR@linkcatcodes%
    \LWR@nolinkurlb%
}
```

`\LWR@url` {⟨*URL*⟩}

Create a link whose text name is the address of the link.

The url package may redefine `\url`, so it is `\let` to `\LWR@urlahere` and also redefined by lwarp-url.

```
\DeclareDocumentCommand{\LWR@urlb}{m}{%
    \LWR@ensuredoingapar%
    \def\LWR@templink{#1}%
    \@onelevel@sanitize\LWR@templink%
    \LWR@href{\LWR@templink}{\LWR@templink}%
    \endgroup%
}

\newrobustcmd*{\LWR@url}{%
    \begingroup%
    \LWR@linkcatcodes%
    \LWR@urlb%
}
```

`\LWR@subinlineimage` {⟨*1:* <alt> *tag*⟩} {⟨*2: class*⟩} {⟨*3: filename*⟩} {⟨*4: extension*⟩} {⟨*5:* CSS *style*⟩} {⟨*6:* ARIA *role*⟩}

Factored from `lateximage`.

```
\newcommand*{\LWR@subinlineimage}[6]{%
```

```
    \ifblank{#6}%
        {\renewcommand*{\LWR@tempone}{}}
        {\renewcommand*{\LWR@tempone}{role="#6"\LWR@indentHTML}}
    \ifblank{#1}%
    {%
        \LWR@htmltag{img \LWR@indentHTML
            src=\textquotedbl#3.#4\textquotedbl \LWR@indentHTML
            alt=\textquotedbl#3\textquotedbl \LWR@indentHTML
            \LWR@tempone
            style=\textquotedbl#5\textquotedbl \LWR@indentHTML
            class=\textquotedbl#2\textquotedbl \LWR@orignewline
        }%
    }%
    {%
        \LWR@htmltag{img \LWR@indentHTML
            src=\textquotedbl#3.#4\textquotedbl \LWR@indentHTML
            alt=\textquotedbl#1\textquotedbl \LWR@indentHTML
            \LWR@tempone
            style=\textquotedbl#5\textquotedbl \LWR@indentHTML
            class=\textquotedbl#2\textquotedbl \LWR@orignewline
        }%
    }%
}

\end{warpHTML}
```

Table 16: Float data structures

For each <type> of float (figure, table, etc.) there exists the following:
counter <type>: A counter called <type>, such as `figure`, `table`.
\<type>name: Name. `\figurename` prints "Figure", etc.
\ext@<type>: File extension. `\ext@figure` prints "lof", etc.
\fps@<type>: Placement.
\the<type>: Number. `\thetable` prints the number of the table, etc.
\p@<type>: Parent's number. Prints the number of the [within] figure, etc.
\fnum@<type>: Prints the figure number for the caption. `\<type>name \the<type>`, "Figure 123".
\<type>: Starts the float environment. `\figure` or `\begin{figure}`
\end<type>: Ends the float environment. `\endfigure` or `\end{figure}`
\tf@<ext>: The LaTeX file identifier for the output file.
LWR@have<type>: A boolean remembering whether a `\listof` was requested for a float of this type.
File with extension lo<f,t,a-z>: An output file containing the commands to build the `\listof<type>` "table-of-contents" structure.
Cross-referencing names: For cleveref's `\cref` and related, `\crefname` and `\Crefname` assign human-readable names for references to this float type.

77 Floats

Floats are supported, although partially through emulation.

Table 16 shows the data structure associated with each <type> of float.

77.1 Float environment

for HTML output:
```
\begin{warpHTML}
```

`\LWR@floatbegin` `{`⟨*type*⟩`}` `[`⟨*placement*⟩`]` Begins a `\newfloat` environment.

```
\NewDocumentCommand{\LWR@floatbegin}{m o}{%
```

Warn if starting a float inside a :

```
    \LWR@spanwarninvalid{float}%
```

```
    \ifbool{FormatWP}{\newline}{}%
    \LWR@stoppars%
```

There is a new float, so increment the unique float counter:

```
    \addtocounter{LWR@thisautoid}{1}%
    \booltrue{LWR@freezethisautoid}%

    \begingroup%
```

Settings while inside the environment:

```
    \LWR@print@raggedright%
```

Open an HTML `figure` tag. The figure is assigned a `class` equal to its type, and another class according to the float package style, if used. Note that `\csuse` returns an empty string if `\LWR@floatstyle@<type>` is not defined.

```
    \LWR@htmltag{%
        figure id=\textquotedbl%
            \LWR@print@mbox{autoid-\arabic{LWR@thisautoid}}%
        \textquotedbl\ % space
        class=\textquotedbl#1 \@nameuse{LWR@floatstyle@#1}\textquotedbl%
    }%
    \ifbool{FormatWP}{%
        \LWR@orignewline%
        \LWR@BlockClassWP{}{}{wp#1}%
    }{}%
```

Update the caption type:

```
    \renewcommand*{\@captype}{#1}%
```

Mark the float for a word processor conversion:

```
    \LWR@startpars%
    \ifboolexpr{bool{FormatWP} and bool{WPMarkFloats}}{%

    === begin #1 ===

    }{}%
```

After each `\LWR@floatbegin`, look for `\centering`, etc next, using `\LWR@floatalignment`.

```
}
```

For koma-script. The following does not work for tables.

```
\AtBeginDocument{

\@ifpackageloaded{tocbasic}{

\appto\figure@atbegin{%
```

```
    \LWR@futurenonspacelet\LWR@mynexttoken\LWR@floatalignment%
}

}{}% tocbasic

}% AtBeginDocument
```

\@xfloat
\@xdlbfloat

Support packages which create floats directly.

Look for \centering, etc using \LWR@floatalignment.

```
\AtBeginDocument{
    \def\@xfloat #1[#2]{%
        \LWR@floatbegin{#1}[#2]
        \LWR@futurenonspacelet\LWR@mynexttoken\LWR@floatalignment%
    }
    \def\@xdblfloat #1[#2]{%
        \LWR@floatbegin{#1}[#2]
        \LWR@futurenonspacelet\LWR@mynexttoken\LWR@floatalignment%
    }
}
```

\LWR@floatend

Ends a \newfloat environment.

```
\newcommand*{\LWR@floatend}{%
```

If saw a \centering, finish the center environment:

```
    \LWR@endfloatalignment%
```

Mark the float end for a word processor conversion:

```
    \ifboolexpr{bool{FormatWP} and bool{WPMarkFloats}}{%

    === end ===

    }{}%
    \LWR@stoppars%
```

Close an HTML figure tag:

```
    \ifbool{FormatWP}{\endLWR@BlockClassWP}{}%
    \LWR@htmlelementend{figure}%
    \endgroup%
    \boolfalse{LWR@freezethisautoid}%
    \LWR@startpars%
    \ifbool{FormatWP}{\newline}{}%
}
```

\end@float
\end@dlbfloat

Support packages which create floats directly.

```
\AtBeginDocument{
    \let\end@float\LWR@floatend
```

```
    \let\end@dblfloat\LWR@floatend
}
```

77.2 Float tracking

Ctr `LWR@thisautoid` A sequential counter for all floats and theorems. This is used to identify the float or theorem then reference it from the List of Figures and List of Tables.

```
\newcounter{LWR@thisautoid}
```

Ctr `LWR@thisautoidWP` A sequential counter for all word processor conversion s. This is used to convince LibreOffice to form a frame around this element.

```
\newcounter{LWR@thisautoidWP}
```

Bool `LWR@freezethisautoid` Prevents multiple increments of `\LWR@thisautoid` inside a float.

```
\newbool{LWR@freezethisautoid}
\boolfalse{LWR@freezethisautoid}
```

`\LWR@forcenewautoidanchor` Adds a new <autoid> anchor.

```
\newcommand*{\LWR@forcenewautoidanchor}{%
    \addtocounter{LWR@thisautoid}{1}%
    \ifbool{LWR@doingapar}%
    {%
        \LWR@htmltag{a id=\textquotedbl%
            \LWR@print@mbox{autoid-\arabic{LWR@thisautoid}}%
            \textquotedbl\ }% space
        \LWR@htmltag{/a }%
    }%
    {%
        \LWR@stoppars%
        \LWR@htmltag{a id=\textquotedbl%
            \LWR@print@mbox{autoid-\arabic{LWR@thisautoid}}%
        \textquotedbl\ }% space
        \LWR@htmltag{/a }%
        \LWR@startpars%
    }%
}
```

`\LWR@newautoidanchor` Sometimes adds a new <autoid> anchor.

```
\newcommand*{\LWR@newautoidanchor}{%
    \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
        {}%
        {\ifbool{LWR@freezethisautoid}{}{\LWR@forcenewautoidanchor}}%
}
```

`\@captype` Remembers which float type is in use.

```
\newcommand*{\@captype}{}
```

\LWR@floatalignmentname Set to center, flushleft, or flushright if saw \centering, \raggedright, or \raggedleft.

```
\newcommand*{\LWR@floatalignmentname}{}
```

\LWR@floatalignment If sees a \centering, \raggedleft, or \raggedright, creates a center, flushright, or flushleft environment.

```
\newcommand*{\LWR@floatalignment}{%
    \ifdefstrequal{\LWR@mynexttoken}{\centering}{%
        \center%
        \renewcommand*{\LWR@floatalignmentname}{center}%
    }{}%
    \ifdefstrequal{\LWR@mynexttoken}{\raggedright}{%
        \flushleft%
        \renewcommand*{\LWR@floatalignmentname}{flushleft}%
    }{}%
    \ifdefstrequal{\LWR@mynexttoken}{\raggedleft}{%
        \flushright%
        \renewcommand*{\LWR@floatalignmentname}{flushright}%
    }{}%
}
```

\LWR@endfloatalignment Closes an environment from \LWR@floatalignment.

```
\newcommand*{\LWR@endfloatalignment}{%
    \ifdefvoid{\LWR@floatalignmentname}%
        {}%
        {\@nameuse{end\LWR@floatalignmentname}}%
    \renewcommand*{\LWR@floatalignmentname}{}%
}
```

77.3 Caption inside a float environment

\CaptionSeparator How to separate the float number and the caption text, if not defined by the user. In most cases, caption's settings are used instead.

```
\AtBeginDocument{\providecommand*{\CaptionSeparator}{:~}}
```

\@caption {⟨*posn*⟩} [⟨*name*⟩] {⟨*long name*⟩}

\@makecaption {⟨*name and num*⟩} {⟨*text*⟩}

Prints the float type and number, the caption separator, and the caption text.

\@caption is provided here in case caption is not loaded, and is based on the nameref package.

```
\AtBeginDocument{
    \@ifpackageloaded{caption}{}{
        \let\LWR@orig@caption\@caption%
        \long\def\@caption#1[#2]{%
```

Warn if using a caption inside a :

```
            \LWR@spanwarnformat{caption}%

            \LWR@setlatestname{#2}%
            \LWR@orig@caption{#1}[{#2}]% also takes third argument
        }%

        \renewcommand{\@makecaption}[2]{%
            \LWR@traceinfo{@makecaption}%
            \caption@begin{\@captype}%
            \LWR@isolate{#1}%
            \edef\LWR@tempone{#1}%
            \ifdefvoid{\LWR@tempone}{}{\CaptionSeparator}%
            \LWR@isolate{#2}%
            \caption@end%
            \LWR@traceinfo{@makecaption: done}%
        }%
    }
}
```

77.4 Caption and LOF linking and tracking

When a new HTML file is marked in the LaTeX PDF file, or at the start of a new section, the LaTeX PDF page number at that point is stored in `LWR@currentautosecfloatpage`, (and the associated filename is remembered by the special LaTeX labels). This page number is used to generate an `autopage` HTML `<id>` in the HTML output at the start of the new HTML file or section. Meanwhile, there is a float counter used to generate an HTML `autoid` `<id>` at the start of the float itself in the HTML file. The `autopage` and `autoid` values to use for each float are written to the `.lof`, etc. files just before each float's entry. These values are used by `\l@figure`, etc. to create the HTML links in the List of Figures, etc.

Ctr `LWR@nextautoid` Tracks `autoid` for floats. Tracks `autopage` for floats.

Ctr `LWR@nextautopage` These are updated per float as the `.lof`, `.lot` file is read.

```
\newcounter{LWR@nextautoid}
\newcounter{LWR@nextautopage}
```

`\LWRsetnextfloat` {⟨*autopage*⟩} {⟨*float autoid*⟩}

File `*_html.lof` This is written to the `*_html.lof` or `*_html.lot` file just before each float's usual entry.

File `*_html.lot` The `autopage` and the float's `autoid` are remembered for `\l@figure` to use when creating the HTML links.

```
\newcommand*{\LWRsetnextfloat}[2]{%
    \setcounter{LWR@nextautopage}{#1}%
    \setcounter{LWR@nextautoid}{#2}%
}
```

Env LWR@figcaption An HTML <figcaption> is not allowed in places where LaTeX does allow a figure caption, such as inside a longtable where the tabular has already started, or inside a center environment. Therefore, a of class figurecaption is used instead.

```
\newenvironment*{LWR@figcaption}
    {%
        \ifbool{FormatWP}{%
            \BlockClass[font-style:italic]{figurecaption}%
        }{%
            \BlockClass{figurecaption}%
        }%
```

Inside the caption, temporarily prevent underfull \hbox warnings, such as when the caption contains a math SVG image.

```
            \hbadness=10000\relax%

    }%
    {\endBlockClass}
```

\LWR@HTML@caption@begin {⟨*type*⟩}

Low-level code to create HTML tags for captions.

The print versions are from the caption package, if loaded.

```
\newcommand*{\LWR@HTML@caption@begin}[1]
{%
    \LWR@traceinfo{LWR@HTML@caption@begin}%
```

Keep par and minipage changes local:

```
    \begingroup%
```

No need for a minipage or \parbox inside the caption:

```
    \RenewDocumentEnvironment{minipage}{O{t} o O{t} m}{}{}%
    \RenewDocumentCommand{\parbox}{O{t} O{} O{t} m +m}{##5}%
```

Enclose the original caption code inside an HTML tag:

```
    \LWR@figcaption%
    \LWR@traceinfo{LWR@HTML@caption@begin: about to LWR@origcaption@begin}%
    \LWR@print@caption@begin{#1}%
    \LWR@traceinfo{LWR@HTML@caption@begin: done}%
}
```

\LWR@HTML@caption@end Low-level patches to create HTML tags for captions.

```
\newcommand*{\LWR@HTML@caption@end}
{%
    \LWR@traceinfo{LWR@HTML@caption@end}%
    \LWR@print@caption@end%
```

Closing tag:

```
    \endLWR@figcaption%
    \endgroup%
    % \leavevmode% avoid bad space factor (0) error
    \LWR@traceinfo{LWR@HTML@caption@end: done}%
}
```

`\caption@begin` `\caption@end` Low-level patches to create HTML tags for captions. These are assigned `\AtBeginDocument` so that other packages which modify captions will have already been loaded before saving the print-mode version.

Print versions are provided here in case caption is not loaded.

```
\AtBeginDocument{
    \providecommand{\caption@begin}[1]{}
    \LWR@formatted{caption@begin}

    \providecommand{\caption@end}{}
    \LWR@formatted{caption@end}
}
```

`\captionlistentry` Tracks the float number for this caption used outside a float. Patched to create an HTML anchor.

```
\AtBeginDocument{%
\@ifpackageloaded{caption}{
    \let\LWR@origcaptionlistentry\captionlistentry

    \renewcommand*{\captionlistentry}{%
        \LWR@ensuredoingapar%
        \LWR@origcaptionlistentry%
    }


    \def\LWR@LTcaptionlistentry{%
        \LWR@ensuredoingapar%
        \LWR@forcenewautoidanchor%
        \bgroup%
        \@ifstar{\egroup\LWR@LT@captionlistentry}% gobble *
            {\egroup\LWR@LT@captionlistentry}%
    }%

    \def\LWR@LT@captionlistentry#1{%
        \caption@listentry\@firstoftwo[\LTcaptype]{#1}%
    }%
}% caption loaded
{% caption not loaded
    \newcommand{\captionlistentry}[2][]{}%
    \newcommand{\LWR@LT@captionlistentry}[2][]{}%
}
}% AtBeginDocument
```

\addcontentsline Patched to write the autopage and autoid before each float's entry. No changes if writing .toc For a theorem, automatically defines \ext@<type> as needed, to mimic and reuse the float mechanism.

f

```
\let\LWR@origaddcontentsline\addcontentsline

\renewcommand*{\addcontentsline}[3]{%
    \ifstrequal{#1}{toc}{}{% not TOC

    \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
        {}%
        {\LWR@newautoidanchor}%

        \ifcsvoid{ext@#2}{\csdef{ext@#2}{#1}}{}%

        \addtocontents{\@nameuse{ext@#2}}{%
            \protect\LWRsetnextfloat%
            {\arabic{LWR@currentautosecfloatpage}}%
            {\arabic{LWR@thisautoid}}%
        }%
    }% not TOC
    \LWR@origaddcontentsline{#1}{#2}{#3}%
}
```

Pkg capt-of Pkg caption Either package provides \captionof, which is later patched at the beginning of the document.

\captionof Patched to handle paragraph tags.

```
\RequirePackage{capt-of}

\AtBeginDocument{
    \let\LWR@origcaptionof\captionof

    \renewcommand*{\captionof}{%
        \LWR@stoppars%
        \LWR@origcaptionof%
    }
}% AtBeginDocument

\end{warpHTML}
```

78 Table of Contents, LOF, LOT

This section controls the generation of the TOC, LOF, and LOT.

The .toc, .lof, and .lot files are named by the source code \jobname.

In HTML, the printed tables are placed inside a of class toc, lof, or lot.

A “sidetoc” is provided which prints a subset of the TOC on the side of each page other than the homepage.

The regular LaTeX infrastructure is used for TOC, along with some patches to generate HTML output.

for HTML output:
```
\begin{warpHTML}
```

78.1 Reading and printing the TOC

`\LWR@myshorttoc` {⟨*toc/lof/lot/sidetoc*⟩}

Reads in and prints the TOC/LOF/LOT at the current position. While doing so, makes the `@` character into a normal letter to allow formatting commands in the section names.

Unlike in regular LaTeX, the file is not reset after being read, since the sideTOC may be referred to again in each HTML page.

```
\newcommand*{\LWR@myshorttoc}[1]{%
    \LWR@traceinfo{LWR@myshorttoc: #1}%
    \LWR@ensuredoingapar%
```

Only if the file exists:

```
    \IfFileExists{\jobname.#1}{%
        \LWR@traceinfo{LWR@myshorttoc: loading}%
```

⚠ Many of the commands in the file will have `@` characters in them, so `@` must be made a regular letter.

```
        \begingroup%
        \makeatletter%
```

Disable CJK xpinyin while generating the sideTOC.

```
        \LWR@disablepinyin%
```

Read in the TOC file:

```
        \@input{\jobname.#1}%
        \endgroup%
    }%
    {}%
    \LWR@traceinfo{LWR@myshorttoc: done}%
}
```

`\LWR@subtableofcontents` {⟨*toc/lof/lot*⟩} {⟨*sectionstarname*⟩}

Places a TOC/LOF/LOT at the current position.

```
\NewDocumentCommand{\LWR@subtableofcontents}{m m}{%
```

Closes previous levels:

```
    \@ifundefined{chapter}%
        {\LWR@closeprevious{section}}%
        {\LWR@closeprevious{chapter}}%
```

Prints any pending footnotes so that they appear above the potentially large TOC:

```
    \LWR@printpendingfootnotes%
```

Place the list into its own chapter (if defined) or section:

```
    \@ifundefined{chapter}{\section*{#2}}{\chapter*{#2}}%
```

Create a new HTML nav containing the TOC/LOF/LOT:

```
    \LWR@htmlelementclass{nav}{#1}%
```

Create the actual list:

```
    \LWR@myshorttoc{#1}%
```

Close the nav:

```
    \LWR@htmlelementclassend{nav}{#1}%
}
```

`\@starttoc` {⟨*ext*⟩}

Patch `\@starttoc` to encapsulate the TOC inside HTML tags:

```
\let\LWR@orig@starttoc\@starttoc

\renewcommand{\@starttoc}[1]{
    \LWR@htmlelementclass{nav}{#1}%
    \LWR@orig@starttoc{#1}%
    \LWR@htmlelementclassend{nav}{#1}%
}
```

Bool `LWR@copiedsidetoc` Used to only copy the TOC file to the sidetoc a single time.

(listings and perhaps other packages would re-use `\tableofcontents` for their own purposes, causing the sidetoc to be copied more than once, and thus end up empty.)

```
\newbool{LWR@copiedsidetoc}
\boolfalse{LWR@copiedsidetoc}
```

`\tableofcontents` Patch `\tableofcontents`, etc. to print footnotes first. newfloat uses `\listoffigures` for all future float types.

```
\AtBeginDocument{

\let\LWR@origtableofcontents\tableofcontents
```

```
10760
10761 \renewcommand*{\tableofcontents}{%
```

Do not print the table of contents if formatting for a word processor, which will presumably auto-generate its own updated table of contents:

```
10762     \ifboolexpr{bool{FormatWP} and bool{WPMarkTOC}}{
10763
10764     === table of contents ===
10765
10766     }
10767     {
```

Copy the `.toc` file to `.sidetoc` for printing the sideTOC. The original `.toc` file is renewed when `\tableofcontents` is finished.

```
10768         \ifbool{LWR@copiedsidetoc}{}{%
10769             \LWR@copyfile{\jobname.toc}{\jobname.sidetoc}%
10770             \booltrue{LWR@copiedsidetoc}%
10771         }%
10772         \LWR@printpendingfootnotes
10773         \LWR@origtableofcontents
10774     }
10775 }% \tableofcontents
10776
10777 }% AtBeginDocument
```

`\listoffigures`

```
10778 \let\LWR@origlistoffigures\listoffigures
10779
10780 \renewcommand*{\listoffigures}{
10781     \ifboolexpr{bool{FormatWP} and bool{WPMarkLOFT}}{
10782
10783     === list of figures ===
10784
10785     }
10786     {
10787         \LWR@printpendingfootnotes
10788         \LWR@origlistoffigures
10789     }
10790 }
```

`\listoftables`

```
10791 \let\LWR@origlistoftables\listoftables
10792
10793 \renewcommand*{\listoftables}{
10794     \ifboolexpr{bool{FormatWP} and bool{WPMarkLOFT}}{
10795
10796     === list of tables ===
10797
10798     }
10799     {
```

```
        \LWR@printpendingfootnotes
        \LWR@origlistoftables
    }
}
```

78.2 TOC commands

`\LWR@listof` {⟨*type*⟩} {⟨*title*⟩}

Emulate the `\listof` command from the float package (section 274). Used to create lists of custom float types. Also used to redefine the standard LaTeX `\listoffigures` and `\listoftables` commands, and in tocloft and memoir.

```
\NewDocumentCommand{\LWR@listof}{m +m}{%
    \@ifundefined{l@#1}{%
       \csdef{l@#1}##1##2{\hypertocfloat{1}{#1}{\@nameuse{ext@#1}}{##1}{##2}}%
    }{}%
    \LWR@subtableofcontents{\@nameuse{ext@#1}}{#2}%
    \expandafter\newwrite\csname tf@\csname ext@#1\endcsname\endcsname%
    \immediate\openout \csname tf@\csname ext@#1\endcsname\endcsname%
        \jobname.\@nameuse{ext@#1}\relax%
}
```

78.3 Side TOC

The "side TOC" is a table-of-contents positioned to the side.

It may be renamed by redefining `\sidetocname`, and may contain paragraphs.

Per table 17, CSS may be used to format the sideTOC.

Table 17: CSS related to the sideTOC

`div.sidetoccontainer`: The entire sideTOC.

`div.sidetoctitle`: The title.

`div.sidetoccontents`: The table of contents.

```
\end{warpHTML}
```

for HTML & PRINT:

```
\begin{warpall}
```

Ctr `SideTOCDepth` Controls how deep the side-TOC gets. Use a standard LaTeX section level similar to `tocdepth`. Warn if parts of the website may be inaccessible.

```
\newcounter{SideTOCDepth}
\setcounter{SideTOCDepth}{1}

\AtEndDocument{%
    \ifnumcomp{\value{SideTOCDepth}}{<}{\value{FileDepth}}{
        \PackageWarningNoLine{lwarp}
```

```
        {%
            SideTOCDepth is less than FileDepth,\MessageBreak
            so some website pages may be inaccessible%
        }
    }{}
}
```

\sidetocname Holds the default name for the sideTOC.

```
\newcommand{\sidetocname}{Contents}
```

```
\end{warpall}
```

for HTML output:

```
\begin{warpHTML}
```

\LWR@sidetoc Creates the actual side-TOC.

```
\newcommand*{\LWR@sidetoc}{%
    \LWR@forcenewpage
    \LWR@stoppars

```

The entire sideTOC is placed into a nav of class sidetoc.

```
    \LWR@htmlelementclass{div}{sidetoccontainer}
    \LWR@htmlelementclass{nav}{sidetoc}

    \setcounter{tocdepth}{\value{SideTOCDepth}}

```

The title is placed into a of class sidetoctitle, and may contain paragraphs.

```
    \begin{BlockClass}{sidetoctitle}
    \ifcsvoid{thetitle}{}{\InlineClass{sidetocthetitle}{\thetitle}\par}
    \sidetocname
    \end{BlockClass}
```

The table of contents is placed into a of class sidetoccontents.

```
    \begin{BlockClass}{sidetoccontents}
    \LinkHome

    \LWR@myshorttoc{sidetoc}
    \end{BlockClass}
    \LWR@htmlelementclassend{nav}{sidetoc}
    \LWR@htmlelementclassend{div}{sidetoccontainer}
}
```

78.4 Low-level TOC line formatting

\numberline {⟨*number*⟩}

(Called from each line in the .aux, .lof files.)

Record this section number for further use:

```
\newcommand*{\LWR@numberline}[1]{%
    \LWR@sectionnumber{#1}\quad%
}

\LetLtxMacro\numberline\LWR@numberline
```

\LWR@maybetocdata Replaced by tocdata. Adds author name.

```
\newcommand*{\LWR@maybetocdata}{}
```

\hypertoc {⟨*1: depth*⟩} {⟨*2: type*⟩} {⟨*3: name*⟩} {⟨*4: page*⟩}

Called by \l@section, etc. to create a hyperlink to a section.

The autopage label is always created just after the section opens.

#1 is depth

#2 is section, subsection, etc.

#3 the text of the caption

#4 page number

```
\NewDocumentCommand{\hypertoc}{m m +m m}{%
    \LWR@traceinfo{hypertoc !#1!#2!#3!#4!}%
```

Respond to tocdepth:

```
    \ifnumcomp{#1}{>}{\value{tocdepth}}%
        {}%
        {%
            \LWR@startpars%
```

Create an HTML link to <filename>#autosec-(page), with the name, of the given HTML class.

\BaseJobname is added to the label in case xr or xr-hyper are used.

```
            \LWR@subhyperrefclass{%
                \LWR@htmlrefsectionfilename{\BaseJobname-autopage-#4}%
                    \LWR@origpound\LWR@print@mbox{autosec-#4}%
            }{#3}{toc#2}%

            \LWR@maybetocdata%

            \LWR@stoppars%
        }%
    \LWR@traceinfo{hypertoc done}%
}
```

Ctr `lofdepth` TOC depth for figures.

```
\@ifclassloaded{memoir}{}{
    \newcounter{lofdepth}
    \setcounter{lofdepth}{1}
}
```

Ctr `lotdepth` TOC depth for tables.

```
\@ifclassloaded{memoir}{}{
    \newcounter{lotdepth}
    \setcounter{lotdepth}{1}
}
```

`\hypertocfloat` {⟨*1: depth*⟩} {⟨*2: type*⟩} {⟨*3: ext of parent*⟩} {⟨*4: caption*⟩} {⟨*5: page*⟩}

#1 is depth

#2 is `figure`, `table`, etc.

#3 is `lof`, `lot`, of the parent.

#4 the text of the caption

#5 page number

```
\newcommand{\hypertocfloat}[5]{%
```

If some float-creation package has not yet defined the float type's `lofdepth` counter, etc, define it here:

```
    \@ifundefined{c@#3depth}{%
        \newcounter{#3depth}%
        \setcounter{#3depth}{1}%
    }{}%
```

Respond to `lofdepth`, etc.:

```
    \LWR@traceinfo{hypertocfloat depth is #1 #3depth is \arabic{#3depth}}%
    \ifthenelse{\cnttest{#1}{<=}{\arabic{#3depth}}}%
        {%
            \LWR@startpars%
```

Create an HTML link to filename#autoid-(float number), with text of the caption, of the given HTML class.

`\BaseJobname` is added to the label in case xr or xr-hyper are used.

```
            \LWR@subhyperrefclass{%
            \LWR@htmlrefsectionfilename{%
                \BaseJobname-autopage-\arabic{LWR@nextautopage}%
            }%
            \LWR@origpound\LWR@print@mbox{autoid-\arabic{LWR@nextautoid}}}%
            {#4}{toc#2}%
```

```
            \LWR@maybetocdata%

            \LWR@stoppars%
        }%
        {}%
}
```

Automatically called by \contentsline:

\l@book {⟨*name*⟩} {⟨*page*⟩}

Uses \DeclareDocumentCommand in case the class does not happen to have a \book.

```
\DeclareDocumentCommand{\l@book}{m m}{\hypertoc{-2}{book}{#1}{#2}}
```

\l@part {⟨*name*⟩} {⟨*page*⟩}

Uses \DeclareDocumentCommand in case the class does not happen to have a \part.

```
\DeclareDocumentCommand{\l@part}{m m}{\hypertoc{-1}{part}{#1}{#2}}
```

\l@chapter {⟨*name*⟩} {⟨*page*⟩}

Uses \DeclareDocumentCommand in case the class does not happen to have a \chapter.

```
\@ifundefined{chapter}
{}
{
\DeclareDocumentCommand{\l@chapter}{m m}
    {\hypertoc{0}{chapter}{#1}{#2}}
}
```

\l@section {⟨*name*⟩} {⟨*page*⟩}

```
\renewcommand{\l@section}[2]{\hypertoc{1}{section}{#1}{#2}}
```

\l@subsection {⟨*name*⟩} {⟨*page*⟩}

```
\renewcommand{\l@subsection}[2]{\hypertoc{2}{subsection}{#1}{#2}}
```

\l@subsubsection {⟨*name*⟩} {⟨*page*⟩}

```
\renewcommand{\l@subsubsection}[2]{\hypertoc{3}{subsubsection}{#1}{#2}}
```

\l@paragraph {⟨*name*⟩} {⟨*page*⟩}

```
\renewcommand{\l@paragraph}[2]{\hypertoc{4}{paragraph}{#1}{#2}}
```

\l@subparagraph {⟨*name*⟩} {⟨*page*⟩}

```
\renewcommand{\l@subparagraph}[2]{\hypertoc{5}{subparagraph}{#1}{#2}}
```

\l@figure {⟨*name*⟩} {⟨*page*⟩}

```
\renewcommand{\l@figure}[2]{\hypertocfloat{1}{figure}{lof}{#1}{#2}}
```

\l@table {⟨*name*⟩} {⟨*page*⟩}

```
\renewcommand{\l@table}[2]{\hypertocfloat{1}{table}{lot}{#1}{#2}}
```

```
\end{warpHTML}
```

79 Index and glossary

See:
http://tex.stackexchange.com/questions/187038/how-to-mention-section-number-in-index-created-by-imakeidx

Index links are tracked by the counter LWR@autoindex. This counter is used to create a label for each index entry, and a reference to this label for each entry in the index listing. This method allows each index entry to link directly to its exact position in the document.

for HTML output:

```
\begin{warpHTML}
```

```
\newcounter{LWR@autoindex}
\setcounter{LWR@autoindex}{0}

\newcounter{LWR@autoglossary}
\setcounter{LWR@autoglossary}{0}
```

\IndexPageSeparator
\IndexRangeSeparator

User-adjustable delimiters for page and range separators in the *.ind files.

```
\newcommand*{\IndexPageSeparator}{, }
\newcommand*{\IndexRangeSeparator}{--}
```

Env theindex

```
\@ifundefined{chapter}
    {\newcommand*{\LWR@indexsection}[1]{\section*{#1}}}
    {\newcommand*{\LWR@indexsection}[1]{\chapter*{#1}}}


\AtBeginDocument{

\renewenvironment*{theindex}{%
    \LWR@indexsection{\indexname}%
    \let\item\LWR@indexitem%
    \let\subitem\LWR@indexsubitem%
    \let\subsubitem\LWR@indexsubsubitem%
}{}

}% AtBeginDocument
```

`\LWR@indexitem` `[`⟨*index key*⟩`]` The optional argument is added to support repeatindex.

```
\newcommand{\LWR@indexitem}[1][\@empty]{

    \InlineClass{indexitem}{\LWR@htmlcomment{}}#1%
}
```

`\LWR@indexsubitem`

```
\newcommand{\LWR@indexsubitem}{

    \InlineClass{indexsubitem}{\LWR@htmlcomment{}}%
}
```

`\LWR@indexsubsubitem`

```
\newcommand{\LWR@indexsubsubitem}{

    \InlineClass{indexsubsubitem}{\LWR@htmlcomment{}}%
}
```

`\LWR@xindex@modifyentry` {⟨*indexing term*⟩}

If using *xindex*, modifies the pipe character to become `\hyperindexformat`. The indexing term is split into two argument at the pipe, then fed to `\LWR@xindex@modifyentrysub`.

```
\NewDocumentCommand{\LWR@xindex@modifyentry}{>{\SplitArgument{1}{|}}m}
    {\LWR@xindex@modifyentrysub#1}
```

Handle left and right parenthesis range argument, or add a `hyperindexformat` clause.

```
\newcommand*{\LWR@xindex@modifyentrysub}[2]{%
    \edef\LWR@tempone{#1}%
    \edef\LWR@temptwo{#2}%
    \IfValueTF{#2}{%
        \ifx#2(%
            \appto\LWR@tempone{|(}%
        \else%
            \ifx#2)%
                \appto\LWR@tempone{|)}%
            \else%
                \appto\LWR@tempone{%
                    |hyperindexformat\LWRleftbrace%
                    \LWRbackslash#2%
                    \LWRrightbrace%
                }%
            \fi%
        \fi%
    }%
    {}%
}
```

`\@wrindex` {⟨*indexing term*⟩} Redefined to write the `LWR@autoindex` counter instead of page.

If using *xindex*, the first line is a comment including a special phrase which tricks *xindex* into thinking that hyperref was used.

```
\newbool{LWR@xindex@tricked}
\boolfalse{LWR@xindex@tricked}

\def\LWR@wrindex#1{%
    \ifbool{LWR@xindex}{%
        \ifbool{LWR@xindex@tricked}{}{%
            \protected@write\@indexfile{}%
            {%
                \LWRpercent\space hyperpage\LWRrightbrace%
                \LWRpercent\space trick xindex to assume hyperref%
            }%
            \global\booltrue{LWR@xindex@tricked}%
        }%
        \LWR@xindex@modifyentry{#1}%
    }{%
        \def\LWR@tempone{#1}%
    }%
    \addtocounter{LWR@autoindex}{1}%
    \label{LWRindex-\arabic{LWR@autoindex}}%
    \protected@write\@indexfile{}%
    {\string\indexentry{\LWR@tempone}{\arabic{LWR@autoindex}}}%
    \endgroup%
    \@esphack%
}

\AtBeginDocument{
\let\@wrindex\LWR@wrindex
}
```

`\@wrglossary` {⟨*term*⟩} Redefined to write the `LWR@autoglossary` counter instead of page.

```
\def\@wrglossary#1{%
    \addtocounter{LWR@autoglossary}{1}%
    \LWR@new@label{LWRglossary-\theLWR@autoglossary}%
    \protected@write\@glossaryfile{}%
    {\string\glossaryentry{#1}{\theLWR@autoglossary}}%
    \endgroup%
    \@esphack%
}
```

`\LWR@indexnameref@anonref` {⟨*LWR@autoindex*⟩}

Displays a reference link where there no `\ref` available.

```
\newcommand*{\LWR@indexnameref@anonref}[1]{%
    \LWR@startref{LWRindex-#1}%
    (*)%
    \LWR@htmltag{/a}%
}
```

`\LWR@indexnameref@ref` {⟨*LWR@autoindex*⟩}

Creates \ref-style index references. To avoid an unwanted space if there is nothing to reference, the reference is checked first.

```
\newcommand*{\LWR@indexnameref@ref}[1]{%
    \edef\LWR@thisref{\csuse{r@LWRindex-#1}}%
    \ifdefvoid{\LWR@thisref}{}{%
        \edef\LWR@thisref{\expandafter\@firstoftwo\LWR@thisref}%
        \ifdefvoid{\LWR@thisref}%
            {\LWR@indexnameref@anonref{#1}}%
            {\ref{LWRindex-#1}}%
    }%
}
```

\LWR@indexnameref@refnameref {⟨*LWR@autoindex*⟩}

Creates \ref-style index references. To avoid an unwanted space if there is nothing to reference, the reference is checked first. For links to starred or ?? objects, only the name is used.

```
\newcommand*{\LWR@indexnameref@refnameref}[1]{%
    \edef\LWR@thisref{\csuse{r@LWRindex-#1}}%
    \ifdefvoid{\LWR@thisref}{}{%
        \edef\LWR@thisref{\expandafter\@firstoftwo\LWR@thisref}%
        \ifdefvoid{\LWR@thisref}{}{%
            \ifdefstring{\LWR@thisref}{(*)}%
                {}%
                {\ref{LWRindex-#1} }% space
        }%
    }%
    \nameref{LWRindex-#1}%
}
```

\LWR@indexnameref@cref {⟨*LWR@autoindex*⟩}

Creates \cref-style index references. If no numbered reference is available, a \nameref is used instead. If the reference is ??, which will be changed by \LWR@indexnameref to become (*), then the link is changed to show (*).

```
\newcommand*{\LWR@indexnameref@cref}[1]{%
    \edef\LWR@thisref{\csuse{r@LWRindex-#1}}%
    \ifdefvoid{\LWR@thisref}{%
        \nameref{LWRindex-#1}%
    }{%
        \edef\LWR@thisref{\expandafter\@firstoftwo\LWR@thisref}%
        \ifdefvoid{\LWR@thisref}{%
            \nameref{LWRindex-#1}%
        }{%
            \ifdefstring{\LWR@thisref}{(*)}{%
                \LWR@indexnameref@anonref{#1}%
            }{%
                \cref{LWRindex-#1}%
            }%
        }%
    }%
```

```
}
```

`\LWR@indexnameref@crefnameref` {⟨*LWR@autoindex*⟩}

Creates `\cref`-style index references. If no numbered reference is available, a `\nameref` is used instead. If the reference is ??, which will be changed by `\LWR@indexnameref` to become `(*)`, then the link is changed to show only the name.

```
\newcommand*{\LWR@indexnameref@crefnameref}[1]{%
    \edef\LWR@thisref{\csuse{r@LWRindex-#1}}%
    \ifdefvoid{\LWR@thisref}%
        {}%
        {%
            \edef\LWR@thisref{\expandafter\@firstoftwo\LWR@thisref}%
            \ifdefvoid{\LWR@thisref}%
                {}%
                {%
                    \ifdefstring{\LWR@thisref}{(*)}%
                        {}%
                        {\cref{LWRindex-#1}} % space
                }%
        }%
    \nameref{LWRindex-#1}%
}
```

`\LWR@indexnameref` {⟨*LWR@autoindex*⟩}

Creates a hyperlink based on the given entry's autoindex.

```
\newcommand*{\LWR@indexnameref}[1]{%
    {% group
```

Temporarily redefine caption's `\caption@xref` because it was printing ?? in the indexes, and also causing error on expansion:

```
        \ifdef{\caption@xref}{%
            \renewcommand*{\caption@xref}[2]{(*)}%
        }{}%

        \ifdefstring{\LWR@IndexRef}{ref}{%
            \LWR@indexnameref@ref{#1}%
        }{%
        \ifdefstring{\LWR@IndexRef}{nameref}{%
            \nameref{LWRindex-#1}%
        }{%
        \ifdefstring{\LWR@IndexRef}{refnameref}{%
            \LWR@indexnameref@refnameref{#1}%
        }{%
        \ifdefstring{\LWR@IndexRef}{cref}{%
            \LWR@indexnameref@cref{#1}%
        }{%
        \ifdefstring{\LWR@IndexRef}{crefnameref}{%
            \LWR@indexnameref@crefnameref{#1}%
        }{%
```

```
        \ifdefstring{\LWR@IndexRef}{autoref}{%
            \LWR@indexnameref@cref{#1}%
        }{% text string
            \LWR@startref{LWRindex-#1}%
            \LWR@IndexRef%
            \LWR@htmltag{/a}%
        }}}}}}%
    }% group
}
```

`\LWR@doindexentrysubsub` {⟨*range start: LWR@autoindex, or macros.*⟩} {⟨*range end or blank*⟩}

Creates a hyperlink, or handles `\see`, `\textbf`, etc.

```
\newrobustcmd{\LWR@doindexentrysubsub}[2]{%
    \IfInteger{#1}%
        {\LWR@indexnameref{#1}}%
        {#1}%
    \IfValueT{#2}{%
        \IndexRangeSeparator%
        \IfInteger{#2}%
            {\LWR@indexnameref{#2}}%
            {#2}%
    }%
}
```

`\LWR@doindexentrysub` {⟨*range delimiter*⟩} {⟨*LWR@autoindex or macros, possible a range*⟩}

```
\NewDocumentCommand{\LWR@doindexentrysub}{m >{\SplitArgument{1}{#1}}m}
    {\LWR@doindexentrysubsub#2}
```

`\LWR@doindexentry` {⟨*LWR@autoindex or macros, possible a range*⟩}

```
\newcommand*{\LWR@doindexentry}[1]{%
    \relax% required
    \expandafter\LWR@doindexentrysub\expandafter{\IndexRangeSeparator}{#1}%
}
```

`\LWR@hyperindexrefnullified` Handles macros commonly seen inside an `\index` entry. Each macro is redefined to create and format a link to its entry.

⚠ index formatting To handle additional macros:

```
\appto\LWR@hyperindexrefnullified{...}
```

```
\newcommand{\LWR@hyperindexrefnullified}{%
    \renewrobustcmd{\emph}[1]{\LWR@HTML@emph{\LWR@doindexentry{##1}}}%
    \renewrobustcmd{\textbf}[1]{\LWR@HTML@textbf{\LWR@doindexentry{##1}}}%
    \renewrobustcmd{\texteb}[1]{\LWR@HTML@texteb{\LWR@doindexentry{##1}}}%
    \renewrobustcmd{\textlg}[1]{\LWR@HTML@textlg{\LWR@doindexentry{##1}}}%
    \renewrobustcmd{\textrm}[1]{\LWR@HTML@textrm{\LWR@doindexentry{##1}}}%
    \renewrobustcmd{\textsf}[1]{\LWR@HTML@textsf{\LWR@doindexentry{##1}}}%
    \renewrobustcmd{\texttt}[1]{\LWR@HTML@texttt{\LWR@doindexentry{##1}}}%
```

```
    \renewrobustcmd{\textup}[1]{\LWR@HTML@textup{\LWR@doindexentry{##1}}}%
    \renewrobustcmd{\textsc}[1]{\LWR@HTML@textsc{\LWR@doindexentry{##1}}}%
    \renewrobustcmd{\textulc}[1]{\LWR@HTML@textulc{\LWR@doindexentry{##1}}}%
    \renewrobustcmd{\textsi}[1]{\LWR@HTML@textsi{\LWR@doindexentry{##1}}}%
    \renewrobustcmd{\textit}[1]{\LWR@HTML@textit{\LWR@doindexentry{##1}}}%
    \renewrobustcmd{\textsl}[1]{\LWR@HTML@textsl{\LWR@doindexentry{##1}}}%
}
```

`\hyperindexref` {⟨*list of LWR@autoindex, commas, and ranges*⟩}

`\hyperindexref{LWR@autoindex}` is inserted into `*.ind` by the ***makeindex*** style file `lwarp.ist` or the ***xindy*** style file `lwarp.xdy`. For ***xindex***, `\hyperpage` is inserted, which is `\let` to `\hyperindexref`. For ***gindex***, `\addindexitem` and related are inserted, which are defined to use `\hyperindexref`.

The argument is split at commas, and also for ranges, then passed to `\LWR@hyperindexrefsub`.

```
\newcommand*{\hyperindexref}[1]{%
    \relax% required
    \expandafter\LWR@hyperindexref@comma\expandafter{\IndexPageSeparator}{#1}%
}
```

`\LWR@hyperindexref@comma` {⟨*separator*⟩} {⟨*list of args*⟩}

The list is split at commas, and passed to `\LWR@hyperindexref@@comma`.

```
\NewDocumentCommand{\LWR@hyperindexref@comma}
    {m >{\SplitList{#1}} m}
    {%
```

Used to place the separtor between each entry, but not before the first.

```
        \def\LWR@hyperindexref@thiscomma{}%
        \def\LWR@hyperindexref@nextcomma{#1}%
```

Each comma-delimited entry is now passed individually to `\LWR@hyperindexref@@comma`.

```
        \ProcessList{#2}\LWR@hyperindexref@@comma%
    }
```

`\LWR@hyperindexref@@comma` {⟨*arg, perhaps with a range*⟩}

A comma separator is placed if not the first item, then the range is parsed.

```
\newcommand*{\LWR@hyperindexref@@comma}[1]{%
    \LWR@hyperindexref@thiscomma%
    \renewcommand{\LWR@hyperindexref@thiscomma}{\LWR@hyperindexref@nextcomma}%
   \expandafter\LWR@hyperindexref@range\expandafter{\IndexRangeSeparator}{#1}%
}
```

`\LWR@hyperindexref@range` {⟨*range delimiter*⟩} {⟨*arg*⟩}

```
\NewDocumentCommand{\LWR@hyperindexref@range}
    {m >{\SplitArgument{1}{#1}} m}
    {\LWR@hyperindexrefsub#2}
```

`\LWR@hyperindexrefsub` {⟨*range start: LWR@autoindex*⟩} {⟨*range end, or* -NoValue-⟩}

Handles the start and end of a range, if applicable.

```
\newcommand*{\LWR@hyperindexrefsub}[2]{%
    \LWR@hyperindexrefsubtwo{#1}%
    \IfValueT{#2}{%
        \IndexRangeSeparator%
        \LWR@hyperindexrefsubtwo{#2}%
    }%
}
```

`\LWR@hyperindexrefsubtwo` {⟨*LWR@autoindex*⟩}

```
\newcommand*{\LWR@hyperindexrefsubtwo}[1]{%
```

In long index lines with numerous entries, *makeindex* can insert a newline before the page number, resulting in an extra space before the first digit. If the first character is a space, remove it first.

```
    \edef\LWR@tempone{#1}%
    \IfBeginWith{\LWR@tempone}{ }{%
        \StrGobbleLeft{\LWR@tempone}{1}[\LWR@tempone]%
    }{}%
```

If a numeric entry, create a link. If not numeric, such as `\see`, use the entry as-is. `\emph`, `\textit`, etc. have been redefined above to create and format the entry.

```
    \IfInteger{\LWR@tempone}%
        {\LWR@indexnameref{\LWR@tempone}}%
        {%
            \begingroup%
            \LWR@hyperindexrefnullified%
            #1%
            \endgroup%
        }%
}
```

`\hyperpage` Emulate hyperref.

```
\LetLtxMacro\hyperpage\hyperindexref
```

`\nohyperpage` Emulate hyperref.

```
\def\nohyperpage#1{}
```

`\hyperindexformat` Emulate hyperref.

```
\def\hyperindexformat#1#2{%
    #1{\hyperpage{#2}}%
}%

\end{warpHTML}
```

for PRINT output: A null command for print mode, in case hyperref was not used:

```
\begin{warpprint}
\newcommand{\hyperindexref}[1]{#1}
\end{warpprint}
```

for HTML & PRINT: For the glossaries package, try to prevent an error where `\glo@name` was not found:

```
\begin{warpall}
\providecommand{\glo@name}{}
\end{warpall}
```

80 Bibliography presentation

for HTML output:

```
\begin{warpHTML}
```

`\bibliography` {⟨*filenames*⟩} At one time this was modified to read `\BaseJobname.bbl`, which meant the HTML version could not resolve until the print version was also present. This also confused multibib. It has been reverted to the original to use `\jobname.bbl`.

`\@biblabel` {⟨*text-refnumber*⟩}

```
\renewcommand{\@biblabel}[1]{[#1]\quad}
```

Env `thebibliography` To emphasize document titles in the bibliography, the following redefines `\em` inside `thebibliography` to gather everything until the next closing brace, then display these tokens with `\textit`.

Adapted from `embracedef.sty`, *which is by* Takayuki YATO*:*
https://gist.github.com/zr-tex8r/b72555e3e7ad2f0a37f1

```
\AtBeginDocument{

\AtBeginEnvironment{thebibliography}{

\providecommand*{\LWR@newem}[1]{\textit{#1}}

\renewrobustcmd{\em}{%
  \begingroup
    \gdef\LWR@em@after{\LWR@em@finish\LWR@newem}%
    \afterassignment\LWR@em@after
    \toks@\bgroup
}

```

```
\def\LWR@em@finish#1{%
    \xdef\LWR@em@after{\noexpand#1{\the\toks@}}%
  \endgroup
  \LWR@em@after\egroup
}

}% \AtBeginEnvironment{thebibliography}

}% \AtBeginDocument

\end{warpHTML}
```

81 Restoring original formatting

for HTML output:

```
\begin{warpHTML}
```

`\LWR@restoreMathJaxformatting`

A few macros (ref: tcolorbox) must be treated separately while printing the HTML comment for a MathJax expression. These are set here, to which other functions may be appended.

```
\newcommand*{\LWR@restoreMathJaxformatting}{}
```

`\LWR@restoreorigformatting`

Used to temporarily restore the print-mode meaning of a number of formatting, graphics, and symbols-related macros while generating SVG math or a `lateximage`.

Must be used inside a group.

Sets `\LWR@formatting` to `print` until the end of the group.

A number of packages will `\appto` additional actions to this macro.

Various packages add to this macro using `\appto`.

```
\newcommand*{\LWR@restoreorigformatting}{%
    \LWR@traceinfo{LWR@restoreorigformatting}%
```

Numerous macros change their print/HTML meaning depending on `\LWR@formatting`:

```
    \renewcommand*{\LWR@formatting}{print}%
    \linespread{1}%

    \let\par\LWR@origpar%

    \LWR@select@print@hspace%

    \LetLtxMacro\hfil\LWR@orighfil%
    \let\hss\LWR@orighss%
    \let\llap\LWR@origllap%
    \let\rlap\LWR@origrlap%
    \let\hfilneg\LWR@orighfilneg%
```

```
    \let\,\LWR@origcomma% disable HTML short unbreakable space
    \let\thinspace\LWR@origthinspace% disable HTML short unbreakable space
  \let\negthinspace\LWR@orignegthinspace% disable HTML negative short unbreakable space
    \let\textellipsis\LWR@origtextellipsis%

    \let\vdots\LWR@origvdots%

    \let\textless\LWR@origtextless%
    \let\textgreater\LWR@origtextgreater%

    \let\&\LWR@origampersand%

    \LetLtxMacro\em\LWR@origem%
    \LetLtxMacro\normalfont\LWR@orignormalfont%
    \let\sp\LWR@origsp%
    \let\sb\LWR@origsb%
    \LetLtxMacro\underline\LWR@origunderline%
    \let~\LWR@origtilde%
    \let\enskip\LWR@origenskip%
    \let\quad\LWR@origquad%
    \let\qquad\LWR@origqquad%
```

`\endtabular` must be restored to its original, instead of relying on lwarp's `\LWR@formatted` mechanism:

```
    \LetLtxMacro\endtabular\LWR@origendtabular%
    \csletcs{endtabular*}{LWR@origendtabular*}%

    \LetLtxMacro\noalign\LWR@orignoalign%
    \LetLtxMacro\hline\LWR@orighline%

    \let\newline\LWR@orignewline%
    \LetLtxMacro\includegraphics\LWR@origincludegraphics%

    \LetLtxMacro\@ensuredmath\LWR@origensuredmath%

    \let\math\LWR@orig@math%
    \let\endmath\LWR@orig@endmath%
    \let\displaymath\LWR@orig@displaymath%
    \let\enddisplaymath\LWR@orig@enddisplaymath%
%
    \LWR@restoreorigaccents%
    \LWR@restoreoriglists%
%
    \LWR@hook@processingtags%
```

To enable MathJax-specific nullification, used for tcolorbox:

```
    \ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
        {\LWR@restoreMathJaxformatting}%
        {}%
}
```

```
\end{warpHTML}
```

82 Nullifying filename formatting

The following are used to nullify certain macros and environments while converting section names to file names.

for HTML output:

```
\begin{warpHTML}
```

Also commonly used are `\@empty`, `\@gobble`, and `\@firstofone`.

```
\newcommand*{\LWR@dash}{-}
```

`\LWR@nullfonts` Removes formatting during filename operations, file references, and HTML comments.

⚠ Use only inside a group.

The following are *not* made robust, since they must be expanded to their nullified versions.

```
\catcode`\$=\active% redefining $ below
\catcode`\_=12% redefining \_ below
\newcommand*{\LWR@nullfonts}{%
```

Various built-in symbols.

```
    \renewcommand*{\$}{-}%
    \renewcommand*{\%}{-}%
    \renewcommand*{\_}{-}%
    \renewcommand*{\}}{-}%
    \renewcommand*{\{}{-}%
    \renewcommand*{\&}{-}% used to be 'and'
    \renewcommand*{\#}{-}%
    \renewcommand*{\,}{-}%
    \renewcommand*{~}{-}%
%
% accents:
    \renewcommand*{\`}[1]{##1}%
    \renewcommand*{\'}[1]{##1}%
    \renewcommand*{\^}[1]{##1}%
    \renewcommand*{\~}[1]{##1}%
    \renewcommand*{\=}[1]{##1}%
    \renewcommand*{\u}[1]{##1}%
    \renewcommand*{\.}[1]{##1}%
    \renewcommand*{\"}[1]{##1}%
    \renewcommand*{\H}[1]{##1}%
    \renewcommand*{\v}[1]{##1}%
    \renewcommand*{\d}[1]{##1}%
    \renewcommand*{\c}[1]{##1}%
    \renewcommand*{\b}[1]{##1}%
    \renewcommand*{\t}[1]{##1}%
%
    \let\newline\LWR@dash%
```

```
    \let\textasciicircum\LWR@dash%
    \let\textasciitilde\LWR@dash%
    \let\textasteriskcentered\LWR@dash%
    \let\textbackslash\LWR@dash%
    \let\textbar\LWR@dash%
    \let\textbardbl\LWR@dash%
    \let\textbigcircle\LWR@dash%
    \let\textbraceleft\LWR@dash%
    \let\textbraceright\LWR@dash%
    \let\textbullet\LWR@dash%
    \let\textcopyright\LWR@dash%
    \let\textdagger\LWR@dash%
    \let\textdaggerdbl\LWR@dash%
    \let\textdollar\LWR@dash%
    \let\textellipsis\LWR@dash%
    \let\textemdash\LWR@dash%
    \let\textendash\LWR@dash%
    \let\textexclamdown\LWR@dash%
    \let\textgreater\LWR@dash%
    \let\textless\LWR@dash%
    \let\textordfeminine\LWR@dash%
    \let\textordmasculine\LWR@dash%
    \let\textparagraph\LWR@dash%
    \let\textperiodcentered\LWR@dash%
    \let\textpertenthousand\LWR@dash%
    \let\textperthousand\LWR@dash%
    \let\textquestiondown\LWR@dash%
    \let\textquotedblleft\LWR@dash%
    \let\textquotedblright\LWR@dash%
    \let\textquoteleft\LWR@dash%
    \let\textquoteright\LWR@dash%
    \let\textregistered\LWR@dash%
    \let\textsection\LWR@dash%
    \let\textsterling\LWR@dash%
    \let\texttrademark\LWR@dash%
    \let\textunderscore\LWR@dash%
    \let\textvisiblespace\LWR@dash%
    \let\copyright\LWR@dash%
    \let\dag\LWR@dash%
    \let\ddag\LWR@dash%
    \let\dots\LWR@dash%
    \let\P\LWR@dash%
    \let\pounds\LWR@dash%
    \let\S\LWR@dash%
%
    \renewcommand*{\aa}{a}%
    \renewcommand*{\AA}{A}%
    \renewcommand*{\AE}{AE}%
    \renewcommand*{\ae}{ae}%
    \renewcommand*{\dh}{d}%
    \renewcommand*{\DH}{D}%
    \renewcommand*{\DJ}{D}%
    \renewcommand*{\dj}{d}%
    \renewcommand*{\IJ}{IJ}%
    \renewcommand*{\ij}{ij}%
```

```
    \renewcommand*{\L}{L}%
    \renewcommand*{\l}{l}%
    \renewcommand*{\NG}{NG}%
    \renewcommand*{\ng}{ng}%
    \renewcommand*{\O}{O}%
    \renewcommand*{\o}{o}%
    \renewcommand*{\oe}{oe}%
    \renewcommand*{\OE}{OE}%
    \renewcommand*{\ss}{ss}%
    \renewcommand*{\SS}{SS}%
    \renewcommand*{\th}{th}%
    \renewcommand*{\TH}{TH}%
%
    \let\guillemotleft\@empty%
    \let\guilsinglleft\@empty%
    \let\quotedblbase\@empty%
    \let\textquotedbl\@empty%
    \let\guillemotright\@empty%
    \let\guilsinglright\@empty%
    \let\quotesinglbase\@empty%

    \renewcommand*{\HTMLunicode}[1]{}%
    \renewcommand*{\HTMLentity}[1]{}%

    \renewcommand{\textsuperscript}[1]{##1}%
    \renewcommand{\textsubscript}[1]{##1}%


    \renewcommand{\underline}[1]{##1}%


    \RenewDocumentCommand{\hspace}{s m}{}%


    \RenewDocumentCommand{\LWR@htmlspanclass}{o D(){} m +m}{{##4}}%
    \DeclareExpandableDocumentCommand{\InlineClass}{D{(){}}{} o m +m}{{##4}}%
```

Nullify math macros.

```
    \def\(##1\){}%
    \def\[##1\]{}%
    \RenewDocumentCommand{\LWR@subsingledollar}{s m m m}{}%
```

Nullify logos:

```
    \renewcommand*{\TeX}{TeX}%
    \renewcommand*{\LaTeX}{LaTeX}%
    \renewcommand*{\LaTeXe}{LaTeX2e}%
    \renewcommand*{\LuaTeX}{LuaTeX}%
    \renewcommand*{\LuaLaTeX}{LuaLaTeX}%
    \renewcommand*{\XeTeX}{XeTeX}%
    \renewcommand*{\XeLaTeX}{XeLaTeX}%
    \renewcommand*{\ConTeXt}{ConTeXt}%
    \renewcommand*{\BibTeX}{BibTeX}%
    \renewcommand*{\MakeIndex}{MakeIndex}%
    \renewcommand*{\AmS}{AmS}%
```

```
    \renewcommand*{\MiKTeX}{MiKTeX}%
    \renewcommand*{\LyX}{LyX}%
```

Use the simpler form with `\texorpdfstring`:

```
    \def\texorpdfstring{\expandafter\@secondoftwo}%
}
\catcode`\$=3%
\catcode`\_=8%
```

`\FilenameNullify` {⟨*redefinitions*⟩}

Adds more nullifying definitions for filename generation.

```
\newcommand*{\FilenameNullify}[1]{%
    \appto{\LWR@nullfonts}{#1}%
}
```

```
\end{warpHTML}
```

83 Math

83.1 Limitations

See Math, section 8.7.

83.2 HTML `alt` tag names

Redefinable names for the HTML `alt` tags, for translation according to the reader's native language.

for HTML & PRINT:

```
\begin{warpall}
```

`\AltTextOpen` The opening part of HTML `alt` tag for an image. The default is a left parenthesis.
Default: (

```
\newcommand*{\AltTextOpen}{(}
```

`\AltTextClose` The closing part of HTML `alt` tag for an image. The default is a right parenthesis.
Default: (

```
\newcommand*{\AltTextClose}{)}
```

`\ImageAltText` The HTML `alt` tag for an image.
Default: image

```
\newcommand*{\ImageAltText}{image}
```

\MathImageAltText — The HTML `alt` tag for an SVG math image.
Default: "math image"

```
\newcommand*{\MathImageAltText}{math image}
```

\LWR@ThisAltText — The HTML `alt` tag for the next image. Cleared after use, and also after each `lateximage`, `\LWR@subsingledollar`, and each use of MathJax.

```
\newcommand*{\LWR@ThisAltText}{}
```

\ThisAltText {⟨*text*⟩}

Assigns the HTML `alt` tag for the next image generated by lwarp, such as a `lateximage`, `picture`, or SVG math.

```
\newcommand*{\ThisAltText}[1]{%
    \renewcommand{\LWR@ThisAltText}{#1}%
}
```

\PackageDiagramAltText — Appended to the `lateximage` HTML `alt` tag for the images generated by many packages.
Default: "diagram"

```
\newcommand*{\PackageDiagramAltText}{diagram}
```

```
\end{warpall}
```

83.3 Inline and display math

for HTML output:

```
\begin{warpHTML}
```

Ctr LWR@externalfilecnt — Counter for the external files which are generated and then referenced from the HTML:

```
\newcounter{LWR@externalfilecnt}
```

Bool LWR@indisplaymathimage — True if processing display math for SVG output. Inside a `lateximage`, display math is only set to print-mode output if `LWR@indisplaymathimage` is false. Used to avoid nullifying display math before it has been completed.

```
\newbool{LWR@indisplaymathimage}
```

Bool LWR@insidemathcomment — True while inside an HTML comment which is displaying a math environment. Used to undo the comment for a moment while creating a `\label`, so that the label's HTML tags will be seen by HTML.

```
\newbool{LWR@insidemathcomment}
\boolfalse{LWR@insidemathcomment}
```

Bool LWR@xfakebold — True if xfakebold `\setBold` is in use.

```
\newbool{LWR@xfakebold}
\boolfalse{LWR@xfakebold}
```

\LWR@orig@setBold Redefined by lwarp-xfakebold.

```
\newcommand*{\LWR@orig@setBold}{}
```

\LWR@orig@unsetBold Redefined by lwarp-xfakebold.

```
\newcommand*{\LWR@orig@unsetBold}{}
```

\LWR@applyxfakebold Redefined by lwarp-xfakebold.

```
\newcommand*{\LWR@applyxfakebold}{}
```

\LWR@setcurrentfont Sets the actual LaTeX font to that which was selected for HTML output. Ex: In HTML mode, \bfseries sets \LWR@f@series to "bf". This sets the PDF output here for use inside a lateximage.

```
\newcommand*{\LWR@setcurrentfont}{%
    \LWR@traceinfo{Using font family \LWR@f@family}%
    \@nameuse{LWR@print@\LWR@f@family family}%
    \LWR@traceinfo{Using font series \LWR@f@series}%
    \@nameuse{LWR@print@\LWR@f@series series}%
    \LWR@traceinfo{Using font shape \LWR@f@shape}%
    \@nameuse{LWR@print@\LWR@f@shape shape}%
    \LWR@traceinfo{Using font caps shape \LWR@f@shapecaps}%
    \@nameuse{LWR@print@\LWR@f@shapecaps shape}%
}
```

\$ Plain dollar signs appearing in the HTML output may be interpreted by MathJax to be math shifts. For a plain text dollar \$, use an HTML entity to avoid it being interpreted by MathJax, unless are inside a lateximage, in which case it will not be seen by MathJax.

```
\let\LWR@origtextdollar\$

\renewcommand*{\$}{%
    \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
    {\LWR@origtextdollar}%
    {\HTMLunicode{00024}}%
}
```

File lwarp_baseline_marker.png
File lwarp_baseline_marker.eps

A marker to be used to help *pdfcrop* identify the inline math baseline and width. If either graphicx or graphics is loaded, this marker is placed at the lower left and lower right corners of the inline math. *pdfcrop* is then able to identify the width of the image, and also the height of an image such as a horizontal dash which does not otherwise touch the baseline.

A marker with alpha or opacity of 0% is not registered by *pdfcrop*, so the marker is a small square block of 1% alpha, which seems to work while still being effectively invisible in the final SVG image.

If graphicx is loaded, this marker is sized as a tiny 1 sp square. If graphics is loaded, this marker is used at its default size of around .25 pt. If neither graphics package is loaded, the marker is replaced by a 10 sp horizontal space, and there is no assistance for determining

baseline or width of the inline math image. The best results are obtained when using graphicx.

\LWR@addbaselinemarker Places a small marker in an SVG inline image. If graphics or graphicx are loaded, the marker is a mostly transparent image. If neither is loaded, no marker is used.

```
\AtBeginDocument{

\ifpdf
    \newcommand*{\LWR@baselinename}{lwarp_baseline_marker.png}
\else
    \ifXeTeX
        \newcommand*{\LWR@baselinename}{lwarp_baseline_marker.png}
    \else
        \newcommand*{\LWR@baselinename}{lwarp_baseline_marker.eps}
    \fi
\fi

\IfFileExists{\LWR@baselinename}%
{
    \@ifpackageloaded{graphicx}{
        \newcommand*{\LWR@addbaselinemarker}{%
            \LWR@origincludegraphics{\LWR@baselinename}%
        }
    }{
        \@ifpackageloaded{graphics}{
            \newcommand*{\LWR@addbaselinemarker}{%
                \LWR@origincludegraphics{\LWR@baselinename}%
            }
        }{
            \newcommand*{\LWR@addbaselinemarker}{%
                \global\booltrue{LWR@warnbaselinemarker}%
            }
            \AtEndDocument{
                \ifbool{LWR@warnbaselinemarker}{
                    \PackageWarningNoLine{lwarp}{%
                        Load graphicx or graphics for improved\MessageBreak
                        SVG math sizing and baselines%
                    }
                }{}
            }
        }
    }
}{% lwarp_baseline_marker.png or .eps is not present
    \newcommand*{\LWR@addbaselinemarker}{%
        \global\booltrue{LWR@warnbaselinemarker}%
    }
    \AtEndDocument{
        \ifbool{LWR@warnbaselinemarker}{
            \PackageWarningNoLine{lwarp}{%
                File \LWR@baselinename\space is not installed\MessageBreak
                alongside the lwarp-*.sty files, so\MessageBreak
                SVG math sizing and baselines may not be accurate}
        }{}
    }
```

```
}

}% AtBeginDocument
```

Bool LWR@warnbaselinemarker

True if the math baseline marker was ever called for, but graphics or graphicx were not loaded.

```
\newbool{LWR@warnbaselinemarker}
\boolfalse{LWR@warnbaselinemarker}
```

Bool LWR@unknownmathsize

If Ti*k*z or other objects are used inside math mode, the resulting image may exceed the TEX box, resulting in an incorrect measurement of the size of the resulting image. If this is so, the HTML styles for image size and depth will be neutralized.

```
\newbool{LWR@unknownmathsize}
```

\LWR@singledollarmeasure {⟨*math expression*⟩}

Measures the size of the image of the math expression.

(In some circumstances SVG math is used even if MATHJAX is preferred.)

SVG math: \LWR@origensuredmath is part of argument #4.

SVG math \ensuremath: \LWR@origensuredmath is part of argument #4.

SVG dynamic math: \LWR@origensuredmath is part of argument #4.

MATHJAX: Argument #4 is the contents of the math expression without \LWR@origensuredmath. This case is handled above.

MATHJAX \ensuremath: \LWR@origensuredmath is part of argument #4.

MATHJAX dynamic math: Argument #4 is the contents of the math expression without \LWR@origensuredmath, so \LWR@origensuredmath is added below.

\ifmmode: Included "just in case".

Factored from \LWR@subsingledollarsvg.

```
\newcommand*{\LWR@singledollarmeasure}[1]{%
    \begingroup%
```

Temporarily disable formatting while measuring the image parameters:

```
    \LWR@restoreorigformatting%
    \RenewDocumentEnvironment{lateximage}{s o s o o d()}{}{}% inside group
    \LWR@print@normalsize%
```

Temporarily set font for the HTML PDF output:

```
    \LWR@setcurrentfont%
```

`lateximagedepth` must be nested to avoid generating paragraph tags. $\mathcal{AMS}$ math modifies the `\text` macro such that `\addtocounter` does not always occur as expected. Lower-level code is used instead.

```
    \global\advance\c@LWR@lateximagedepth 1\relax%
```

Typeset the math in a box. While doing so, some macros or environments may set `LWR@unknownmathsize`, in which case this will be used to cancel the HTML styles being generated here.

```
    \boolfalse{LWR@unknownmathsize}%
    \ifmmode%
        \global\sbox{\LWR@singledollarbox}{#1}%
    \else%
        \ifbool{LWR@dynamicmath}{%
            \ifbool{mathjax}{%
                \global\sbox{\LWR@singledollarbox}%
                    {\LWR@origensuredmath{#1}}%
            }{%
                \global\sbox{\LWR@singledollarbox}{#1}%
            }%
        }{%
            \global\sbox{\LWR@singledollarbox}{#1}%
        }%
    \fi%
```

Add a small and almost transparent marker at the depth of the image.

A math minus sign has the same depth as a plus, even though it does not draw anything below the baseline. This means that *pdfcrop* would crop the image without depth. The marker below the baseline is seen by *pdfcrop* and preserves the depth.

```
    \global\sbox{\LWR@singledollarbox}{%
        \usebox{\LWR@singledollarbox}%
        \raisebox{-\dp\LWR@singledollarbox}{%
            \LWR@addbaselinemarker%
        }%
    }%
```

More low-level code to undo the counter change.

```
    \global\advance\c@LWR@lateximagedepth -1\relax% Due to AmS \text macro.
```

Measure the depth:

```
    \setlength{\LWR@singledollardepth}{%
        \LateximageFontScale\dp\LWR@singledollarbox%
    }%
```

Make the length a global change:

```
    \global\LWR@singledollardepth=\LWR@singledollardepth%
```

Likewise for width:

```
    \setlength{\LWR@singledollarwidth}{%
        \LateximageFontScale\wd\LWR@singledollarbox%
    }%
    \global\LWR@singledollarwidth=\LWR@singledollarwidth%
```

Likewise for total height:

```
    \setlength{\LWR@singledollarheight}{%
        \LateximageFontScale\ht\LWR@singledollarbox%
    }%
    \addtolength{\LWR@singledollarheight}{%
        \LateximageFontScale\dp\LWR@singledollarbox%
    }%
    \global\LWR@singledollarheight=\LWR@singledollarheight%

    \endgroup%
}
```

`\LWR@subsingledollarsvg` * {⟨*2: alt text*⟩} {⟨*3: add'l hashing*⟩} {⟨*4: math expression*⟩}

For inline math. Uses SVG math. The image is measured and ajusted to the baseline of the HTML output, and placed inside a `lateximage`.

(In some circumstances SVG math is used even if MathJax is preferred.)

Factored from `\LWR@subsingledollar`.

```
\newcommand*{\LWR@subsingledollarsvg}[4]{%
```

Measure the depth, width, and height of the math image:

```
    \LWR@singledollarmeasure{#4}%
```

Set a style for the the height or width. The `em` unit is used so that the math scales according to the user's selected font size.

Start with the greater of the width or the height, biased towards the width:

```
    \ifdimgreater{\LWR@singledollarwidth}{.7\LWR@singledollarheight}{%
        \def\LWR@singledollarstyle{%
            width:\LWR@convertto{em}{\the\LWR@singledollarwidth} em%
        }%
    }{%
        \def\LWR@singledollarstyle{%
            height:\LWR@convertto{em}{\the\LWR@singledollarheight} em%
        }%
    }%
```

If a very narrow width, use the height.

```
    \ifdimless{\LWR@singledollarwidth}{.2em}%
    {%
        \def\LWR@singledollarstyle{%
            height:\LWR@convertto{em}{\the\LWR@singledollarheight} em%
```

```
        }%
    }%
    {}%
```

If very wide and short, use the width:

```
    \ifdimless{\LWR@singledollarheight}{.2em}%
    {%
        \def\LWR@singledollarstyle{%
            width:\LWR@convertto{em}{\the\LWR@singledollarwidth} em%
        }%
    }%
    {}%
```

If there is significant text depth, add the depth to the style.

```
    \ifdimgreater{\LWR@singledollardepth}{0.05ex}{%
        \def\LWR@singledollardepthstyle{%
            \ ; % extra space
            \LWR@print@mbox{%
            vertical-align:-\LWR@convertto{em}{\the\LWR@singledollardepth} em%
            } % extra space
        }%
    }{%
        \def\LWR@singledollardepthstyle{}%
    }%
```

If using certain Ti*k*z actions inside math, the resulting image may exceed the TEX boundaries, so the HTML size styles may be incorrect, and must be neutralized.

```
    \ifbool{LWR@unknownmathsize}{%
        \def\LWR@singledollarstyle{}%
        \def\LWR@singledollardepthstyle{}%
    }{}%
```

Create the `lateximage` using the alternate tag and the computed size and depth. The star causes `lateximage` to use an MD5 hash as the filename. When hashing, also include the current font and color in the hash.

```
    \ifbool{LWR@dynamicmath}{%
        \LWR@traceinfo{subsingledollar: dynamic}%
        \begin{lateximage}% no hashing
            [\MathImageAltText]% alt tag
            []% no add'l hashing
            [\LWR@singledollarstyle \LWR@singledollardepthstyle]% CSS
            (math)% ARIA
    }{% not dynamic math
        \LWR@traceinfo{subsingledollar: static}%
        \IfValueTF{#1}{% #1 True
            \LWR@findcurrenttextcolor% sets \LWR@tempcolor
```

Support for xfakebold:

```
            \ifbool{LWR@xfakebold}%
                {\def\LWR@tempone{Y}}%
```

```
                {\def\LWR@tempone{N}}%

            \begin{lateximage}*% use hashing
                [#2]% alt
                *% do not add open/closing braces
                [% addl' hashing
                    #3%
                    FM\LWR@f@family%
                    SR\LWR@f@series%
                    SH\LWR@f@shape%
                    SHC\LWR@f@shapecaps%
                    CL\LWR@tempcolor%
                    FB\LWR@tempone% xfakebold
                ]%
                [\LWR@singledollarstyle \LWR@singledollardepthstyle]% CSS
                (math)% ARIA
        }{% #1 False
            \begin{lateximage}% no hashing
                [#2]% alt
                []% no add'l hashing
                [\LWR@singledollarstyle \LWR@singledollardepthstyle]% CSS
                (math)% ARIA
        }%
    }% not dynamic math
```

Place small and almost transparent markers on the baseline at the left and right edges of the image. These markers are seen by ***pdfcrop***, and force vertically-centered objects such as a dash to be raised off the baseline in the cropped image, and also force the total width and left/right margins to be correct. (Except that in some fonts a character may exceed the bounding box, and thus may appear wider than expected when converted to an image.)

```
    \LWR@addbaselinemarker%
```

Support for xfakebold:

```
    \LWR@applyxfakebold%
```

Typeset the contents:

```
    \usebox{\LWR@singledollarbox}%
```

The closing baseline marker:

```
    \LWR@addbaselinemarker%

    \end{lateximage}%
%
}
```

`\LWR@subsingledollar` `*` `{`⟨*2: alt text*⟩`}` `{`⟨*3: add'l hashing*⟩`}` `{`⟨*4: math expression*⟩`}`

For inline math. Uses MathJax, or for SVG math the image is measured and ajusted to the baseline of the HTML output, and placed inside a `lateximage`.

SVG math: `\LWR@origensuredmath` is part of argument #4.

SVG math `\ensuremath`: `\LWR@origensuredmath` is part of argument #4.

SVG dynamic math: `\LWR@origensuredmath` is part of argument #4.

MathJax: Argument #4 is the contents of the math expression without `\LWR@origensuredmath`. This case is handled above.

MathJax `\ensuremath`: `\LWR@origensuredmath` is part of argument #4.

MathJax dynamic math: Argument #4 is the contents of the math expression without `\LWR@origensuredmath`, so `\LWR@origensuredmath` is added below.

image filename hashing

If starred, a hashed filename is used.If so, the hash is based on the `alt` tag and also the additional hashing argument.

This may be used to provide an expression with a simple `alt` tag but also enough additional information to provide a unique hash.

An example is when the expression is a complicated TeX expression, which would not copy/paste well. A simplified tag may be used, while the complicated expression is duplicated in the additional hashing argument.

Another example is when the expression is simple, but the image depends on options. These options may be decoded into text form and included in the additional hashing argument in order to make the hash unique according to the set of options, even if the simple `alt` tag is still the same.

```
\newlength{\LWR@singledollarwidth}
\newlength{\LWR@singledollarheight}
\newlength{\LWR@singledollardepth}

\newsavebox{\LWR@singledollarbox}

\NewDocumentCommand{\LWR@subsingledollar}{s m m m}{%
    \LWR@traceinfo{LWR@subsingledollar}%

    \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
    {%
        \LWR@traceinfo{LWR@subsingledollar: already in a lateximage}%
            #4% contents
    }%
    {% not in a lateximage
        \begingroup%
```

Support for xfakebold:

```
        \LWR@applyxfakebold%
```

MathJax cannot parse the often complicated TeX expressions which appear in the various uses of `\ensuredmath`. `\ensuremath` forces the `alt` tag to "`(math image)`", as translated according to `\MathImageAltText`. If this is the case, force the use of a `lateximage` even if MathJax. Likewise for siunitx if `parse-numbers=false`.

If MathJax, or if formatting math for a word processor, and not `\ensuredmath`, and not a dynamic math expression, print the math expression:

```
        \ifboolexpr{%
            (
                bool{mathjax} or
                ( bool{FormatWP} and bool{WPMarkMath} )
            ) and
            ( not test {
                    \ifstrequal {#2}% from \ensuredmath
                        {\AltTextOpen\MathImageAltText\AltTextClose}
                }
            ) and
            ( not bool{LWR@dynamicmath} )
        }%
```

For MathJax, print the math between `\(` and `\)`:

```
        {%
            \LWR@traceinfo{LWR@subsingledollar: Mathjax}%
            {%
                \textbackslash(%
                {%
```

`\ifmmode` to avoid error about `\ttfamily` inside math mode in the case of nested math, ex. equation with tcolorbox with math.

```
                    \ifmmode\else\LWR@print@ttfamily\fi%
                    \LWR@HTMLsanitize{#4}%
                }%
                \textbackslash)%
            }%
        }% mathjax
```

For SVG, print the math inside a `lateximage`, with an `<alt>` tag of the LaTeX code, and a CSS style to control the baseline adjustment.

```
        {% not mathjax
            \LWR@traceinfo{%
             LWR@subsingledollar: NOT mathjax, or is ensuremath, or is dynamic%
            }%
            \LWR@subsingledollarsvg{#1}{#2}{#3}{#4}%
        }% not mathjax
        \endgroup%
    }% not in a lateximage
```

Clear the single-use `alt` text:

```
    \gdef\LWR@ThisAltText{}%
    \LWR@traceinfo{LWR@subsingledollar: done}%
}

\LetLtxMacro\LWR@origdollar$
\LetLtxMacro\LWR@secondorigdollar$% balance for editor syntax highlighting
```

```
\LetLtxMacro\LWR@origopenparen\(
\LetLtxMacro\LWR@origcloseparen\)
\LetLtxMacro\LWR@origopenbracket\[
\LetLtxMacro\LWR@origclosebracket\]
```

$ $$ Redefine the dollar sign to place math inside a `lateximage`, or use MathJax:

```
\begingroup
\catcode`\$=\active%
\protected\gdef${\@ifnextchar$\LWR@doubledollar\LWR@singledollar}%
```

Used by chemformula to escape single-dollar math:

```
\protected\gdef\LWR@newsingledollar{\@ifnextchar$\LWR@doubledollar\LWR@singledollar}%
```

\LWR@doubledollar Redefine the double dollar sign to place math inside a `lateximage`, or use MathJax:

```
\protected\gdef\LWR@doubledollar$#1$${%
```

If MathJax or formatting for a word processor, print the LaTeX expression:

```
\ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
```

For MathJax, print the math between `\[` and `\]`:

```
{

    \IfSubStr{\detokenize\expandafter{#1}}{\detokenize{note}}{%
```

The equation is printed to the PDF output inside HTML comment tags. This allows labels and footnotes to be accepted and processed. The `math` environment is selected here, and `\LWR@hidelatexequation` will use the original print-mode meaning of `math`.

```
        \LWR@hidelatexequation{math}{#1}%

        \InlineClass{hidden}{\LWR@syncnotenumbers}%
        \textbackslash[%
        {\LWR@print@ttfamily\LWR@HTMLsanitize{#1}}%
        \textbackslash]
        \InlineClass{hidden}{\LWR@syncnotenames}%
    }{%
        \textbackslash[%
        {\LWR@print@ttfamily\LWR@HTMLsanitize{#1}}%
        \textbackslash]
    }%

}% mathjax
```

For SVG, print the math inside a `lateximage`, with an `<alt>` tag of the LaTeX code:

```
{% not mathjax
    \begin{BlockClass}{displaymath}%
    \LWR@newautoidanchor%
```

```
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}%
    [%
        \textbackslash{[} % extra space
        \LWR@HTMLsanitize{#1} % extra space
        \textbackslash{]}%
    ]%
    *% do not add open/closing braces
    (math)% ARIA
```

Support for xfakebold:

```
    \LWR@applyxfakebold%

    \LWR@origdollar\LWR@origdollar#1\LWR@origdollar\LWR@origdollar%
    \end{lateximage}%
    \end{BlockClass}%
}% not mathjax
```

Clear the single-use `alt` text:

```
\gdef\LWR@ThisAltText{}%
}%
```

`\LWR@singledollar` {⟨*alt text*⟩} {⟨*math expression*⟩}

```
\protected\gdef\LWR@singledollar#1${%
\ifbool{mathjax}{%
    \LWR@subsingledollar*%
    {% alt tag
        \textbackslash( %
        \LWR@HTMLsanitize{#1} % extra space
        \textbackslash)%
    }%
    {singledollar}% add'l hashing
    {#1}% contents
}{% not mathjax
    \LWR@subsingledollar*%
    {% alt tag
        \textbackslash( %
        \LWR@HTMLsanitize{#1} % extra space
        \textbackslash)%
    }%
    {singledollar}% add'l hashing
    {\LWR@origensuredmath{#1}}% contents
}% not mathjax
```

Clear the single-use `alt` text:

```
\gdef\LWR@ThisAltText{}%
}
```

`\(` `\[` Redefine to the above dollar macros.

```
\AtBeginDocument{
    \protected\gdef\(#1\){$#1$}
    \protected\gdef\[#1\]{$$#1$$}
}

\endgroup% active $
```

```
\AtBeginDocument{
\LetLtxMacro\LWR@openbracketnormal\[
\LetLtxMacro\LWR@closebracketnormal\]
}
```

`\@ensuredmath` {⟨*expression*⟩}

If MathJax, a `lateximage` is used, since `\ensuremath` is often used for complex TEX expressions which MathJax may not render. If SVG math, a hashed file is used with a simple `alt` tag, but additional hashing provided by the contents.

```
\LetLtxMacro\LWR@origensuredmath\@ensuredmath

\renewcommand{\@ensuredmath}[1]{%
    \ifbool{mathjax}{%
        \LWR@subsingledollar*{\AltTextOpen\MathImageAltText\AltTextClose}%
        {%
            \protect\LWR@HTMLsanitize{\detokenize\expandafter{#1}}%
        }%
        {%
            \relax%
            \LWR@origensuredmath{#1}%
        }%
    }{% SVG math
```

If already inside a `lateximage` in math mode, continue as-is.

```
        \ifmmode%
            \LWR@origensuredmath{#1}%
        \else%
```

Create an inline math `lateximage` with a simple `alt` tag and additional hashing according to the contents.

```
            \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
                {\LWR@origensuredmath{#1}}%
                {%
                    \LWR@subsingledollar*%
                        {\AltTextOpen\MathImageAltText\AltTextClose}%
                     {\protect\LWR@HTMLsanitize{\detokenize\expandafter{#1}}}%
                        {\LWR@origensuredmath{#1}}%
                }%
        \fi%
    }%
```

Clear the single-use `alt` text:

```
    \gdef\LWR@ThisAltText{}%
}
```

Remember then remove the old `math` and `displaymath` environments:

```
\let\LWR@orig@math\math
\let\LWR@orig@endmath\endmath

\let\LWR@orig@displaymath\displaymath
\let\LWR@orig@enddisplaymath\enddisplaymath

\let\math\relax
\let\endmath\relax

\let\displaymath\relax
\let\enddisplaymath\relax
```

Env `math` Set math mode then typeset the body of what was between the begin/end. See the environ package for `\BODY`.

```
\NewEnviron{math}{\expandafter\(\BODY\)}
```

Env `LWR@displaymathnormal` Set math mode then typeset the body of what was between the begin/end. See the environ package for `\BODY`.

```
\NewEnviron{LWR@displaymathnormal}{\expandafter\[\BODY\]\@ignoretrue}
```

Set the default displaymath to the normal version:

```
\LetLtxMacro\displaymath\LWR@displaymathnormal%
\LetLtxMacro\enddisplaymath\endLWR@displaymathnormal%
```

Env `LWR@displaymathother` A version of `displaymath` which can handle complicated objects, but does not supply MathJax or HTML `alt` tags.

```
\newenvironment{LWR@displaymathother}
{%
    \begin{BlockClass}{displaymath}%
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}[\MathImageAltText](math)% [alt](ARIA)
    \LWR@origdollar\LWR@origdollar%
}
{%
    \LWR@origdollar\LWR@origdollar%
    \end{lateximage}%
    \end{BlockClass}%
}
```

Env `LWR@equationother` A version of `displaymath` which can handle complicated objects, but does not supply MathJax or HTML `alt` tags.

```
\newenvironment{LWR@equationother}
{%
    \begin{BlockClass}{displaymathnumbered}%
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}[\MathImageAltText](math)% [alt](ARIA)
    \LWR@orig@equation%
}
{%
    \LWR@orig@endequation%
    \end{lateximage}%
    \end{BlockClass}%
}
```

83.4 MathJax support

Ctr `LWR@nextequation` Used to add one to compute the next equation number.

```
\newcounter{LWR@nextequation}
```

Determing how to set MathJax section and equation numbers. Adjusts for various kinds of `\theequation` to determine `\theMathJaxsection` and `\theMathJaxequation`.

```
\newcommand\LWR@article@theequation{\@arabic\c@equation}

\newcommand\LWR@book@theequation
  {\ifnum \c@chapter>\z@ \thechapter.\fi \@arabic\c@equation}


\newcommand\LWR@chapter@theequation{\thechapter.\arabic{equation}}
\newcommand\LWR@section@thequation{\thesection.\arabic{equation}}
\newcommand\LWR@subsection@thequation{\thesubsection.\arabic{equation}}

\AtBeginDocument{
    % default per article class:
    \newcommand*{\theMathJaxsubequations}{0}
    \newcommand*{\theMathJaxsection}{}
    \newcommand*{\theMathJaxequation}{\arabic{equation}}

    \ifdefstrequal{\theequation}{\LWR@article@theequation}
    {}{
    \ifdefstrequal{\theequation}{\LWR@book@theequation}{
      \renewcommand*{\theMathJaxsection}{\ifnum \c@chapter>\z@ \thechapter.\fi}
    }{
    \ifdefstrequal{\theequation}{\LWR@subsection@thequation}{
        \renewcommand*{\theMathJaxsection}{\thesubsection{}.}
    }{
    \ifdefstrequal{\theequation}{\LWR@section@thequation}{
        \renewcommand*{\theMathJaxsection}{\thesection{}.}
    }{
    \ifdefstrequal{\theequation}{\LWR@chapter@theequation}{
        \renewcommand*{\theMathJaxsection}{\thechapter{}.}
    }{% unknown format
        \PackageWarningNoLine{lwarp}
```

```
        {%
            Unknown equation tag format for \protect\theequation.\MessageBreak
            Article-style equation numbering will be used%
        }
    }}}}}
}
```

`\LWR@syncmathjax` Sets the MathJax equation format and number for the following equations.

These MathJax commands are printed inside "`\(`" and "`\)`" characters. They are printed to HTML output, not interpreted by LaTeX.

```
\newcommand*{\LWR@syncmathjax}{%
```

Tell MathJax that the next equation number is the current LaTeX equation number.

Before each equation, lwarp inserts into the HTML code:

```
\seteqnumber{subequations?}{section}{number}
```

`subequations?` is `0` usually, `1` if inside amsmath `subequations`.

`section` is a string printed as-is, or empty.

`number` is auto-incremented by MathJax between equations.

Place the MathJax command inside "`\(`" and "`\)`" characters, to be printed to HTML, not interpreted by LaTeX.

```
        \LWR@stoppars%
        \InlineClass{hidden}{
            \textbackslash(%
            \textbackslash{}seteqnumber%
            \{\theMathJaxsubequations\}%
            \{\theMathJaxsection\}%
            \{\theMathJaxequation\}%
            \textbackslash)%
        }
        \LWR@startpars%
}
```

`\LWR@hidelatexequation` {⟨*environment*⟩} {⟨*contents*⟩}

Creates the LaTeX version of the equation inside an HTML comment.

```
\NewDocumentCommand{\LWR@hidelatexequation}{m +m}{%
```

Stop HTML paragraph handling and open an HTML comment:

```
    \LWR@stoppars
    \LWR@htmlopencomment

```

Start the LaTeX math environment inside the HTML comment:

```
    \begingroup
    \@nameuse{LWR@orig@#1}
```

While in the math environment, restore various commands to their LaTeX meanings.

```
    \LWR@restoreorigformatting
    \booltrue{LWR@insidemathcomment}
```

Temporarily prevent underfull \hbox warnings.

```
    \hbadness=10000\relax%
```

See \LWR@htmlmathlabel in section 83.7.1.

Print the contents of the equation:

```
    #2
```

End the LaTeX math environment inside the HTML comment:

```
    \@nameuse{LWR@orig@end#1}
    \endgroup

```

Close the HTML comment and resume HTML paragraph handling:

```
    \LWR@htmlclosecomment
    \boolfalse{LWR@insidemathcomment}
    \LWR@startpars
}
```

\LWR@addmathjax {⟨*environment*⟩} {⟨*contents*⟩}

Given the name of a math environment and its contents, create a MathJax instance. The contents are printed to HTML output, not interpreted by LaTeX.

```
\NewDocumentCommand{\LWR@addmathjax}{m +m}{%
```

Enclose the MathJax environment inside printed "\(" and "\)" characters.

```
    \LWR@origtilde\LWR@orignewline
```

Print the environment name and contents, sanitizing for HTML special characters.

```
    {%
        \LWR@print@ttfamily%
        \textbackslash{}begin\{#1\}
        \LWR@orignewline%
        \LWR@HTMLsanitizeexpand{\detokenize\expandafter{#2}}%
        \LWR@orignewline%
        \textbackslash{}end\{#1\}
    }%
```

```
    \LWR@orignewline
}
```

83.5 Equation environment

Remember existing `equation` environment, after redefined by amsmath, if loaded.

```
\AtBeginDocument{
    \let\LWR@orig@equation\equation
    \let\LWR@orig@endequation\endequation
    \csletcs{LWR@orig@equation*}{equation*}
    \csletcs{LWR@orig@endequation*}{endequation*}
}
```

`\LWR@doequation` {⟨*env contents*⟩} {⟨*env name*⟩}

For SVG math output, the contents are typeset using the original `equation` inside a `lateximage`, along with an `<alt>` tag containing a detokenized copy of the LaTeX source for the math.

For MathJax output, the contents are typeset in an original `equation` environment placed inside a HTML comment, with special processing for `\label`s. The contents are also printed to the HTML output for processing by the MathJax script.

```
\newcommand*{\LWR@doequation}[2]{%

```

If `mathjax` or `FormatWP`, print the LaTeX expression:

```
    \ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
```

MathJax output:

```
    {
```

Print commands to syncronize MathJax's equation number and format to the current LaTeX chapter/section and equation number:

```
        \LWR@syncmathjax%
```

Print the LaTeX math inside an HTML comment:

```
        \LWR@hidelatexequation{#2}{#1}
    }
```

SVG output: Create the `lateximage` along with an HTML `<alt>` tag having an equation number, the LaTeX equation environment commands, and the contents of the environment's `\BODY`.

```
    {% not mathjax
```

Begin the lateximage with an <alt> tag containing the math source:

```
        \ifstrequal{#2}{equation*}{%
            \begin{BlockClass}{displaymath}%
        }{%
            \begin{BlockClass}{displaymathnumbered}%
        }%
        \LWR@newautoidanchor%
        \booltrue{LWR@indisplaymathimage}%
        \begin{lateximage}[%
            \ifstrequal{#2}{equation*}{%
                \ifdefequal{\LWR@equationtag}{\theequation}{%
    %                                       no tag was given
                }{%
                    (\LWR@equationtag) % tag was given
                }%
            }{%
                (\LWR@equationtag) % automatic numbering
            }%
            \textbackslash{begin\{#2\}} % extra space
            \LWR@HTMLsanitizeexpand{\detokenize\expandafter{#1}} % extra space
            \textbackslash{end\{#2\}}%
        ]*(math)% alt tag, ARIA
```

Support for xfakebold:

```
        \LWR@applyxfakebold%
```

Create the actual LaTeX-formatted equation inside the lateximage using the contents of the environment.

```
        \@nameuse{LWR@orig@#2}%
        #1% contents collected by \collect@body
        \@nameuse{LWR@orig@end#2}%
        \end{lateximage}%
        \end{BlockClass}%
    }% not mathjax
```

Clear the single-use alt text:

```
    \gdef\LWR@ThisAltText{}%
}
```

After the environment, if MathJax, print the math to the HTML output for MathJax processing. If a footnote is used, sync the footnote counter before, then unsync after for non-equation environments, as defined next.

```
\newcommand*{\LWR@doendequation}[1]{%
    \ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
    {%
        \IfSubStr{\detokenize\expandafter{\BODY}}{\detokenize{note}}{%
            \InlineClass{hidden}{\LWR@syncnotenumbers}%
            \LWR@addmathjax{#1}{\BODY}%
            \InlineClass{hidden}{\LWR@syncnotenames}%
        }{%
```

```
            \LWR@addmathjax{#1}{\BODY}%
        }%
    }{}%
```

Clear the single-use `alt` text:

```
    \gdef\LWR@ThisAltText{}%
}
```

The following are used to syncronize footnote marks and related to MathJax if `*note*` is used inside the MathJax expression. The counter is read from LaTeX then defined into MathJax for use during the following equation. After the equation, the MathJax value is returned to the text from `\footnotename`. Other notes may be added by appending to `\LWR@syncnotenumbers` and `\LWR@syncnotenames`.

`\LWR@synconenotenumber` {⟨*MathJax variable*⟩} {⟨*mark*⟩}

```
\newcommand*{\LWR@synconenotenumber}[2]{%
    \textbackslash(
    \textbackslash{}def\textbackslash{}#1\{#2\}
    \textbackslash)
}
```

`\LWR@syncnotenumbers` Assignments to make.

```
\newcommand*{\LWR@syncnotenumbers}{\LWR@synconenotenumber{LWRfootnote}{\thefootnote}}
```

`\LWR@synconenotename` {⟨*MathJax variable*⟩} {⟨*text*⟩}

```
\newcommand*{\LWR@synconenotename}[2]{%
    \textbackslash(
    \textbackslash{}def\textbackslash{}#1name\{#2\}
    \textbackslash)
}
```

`\LWR@syncnotenames` Assignments to make.

```
\newcommand*{\LWR@syncnotenames}{\LWR@synconenotename{LWRfootnote}{\footnotename}}
```

Remove existing `equation` environment:

```
\AtBeginDocument{
    \let\equation\relax
    \let\endequation\relax
    \csletcs{equation*}{relax}
    \csletcs{endequation*}{relax}
}
```

Env `equation` The new `equation` environment is created with `\NewEnviron` (from the environ package), which stores the contents of its environment in a macro called `\BODY`.

```
\AtBeginDocument{
    \NewEnviron{equation}%
        {\LWR@doequation{\BODY}{equation}}%
        [\LWR@doendequation{equation}]

    \LetLtxMacro\LWR@equationnormal\equation
    \LetLtxMacro\endLWR@equationnormal\endequation
}% AtBeginDocument
```

Env `equation*`

```
\AtBeginDocument{
    \NewEnviron{equation*}%
        {\LWR@doequation{\BODY}{equation*}}%
        [\LWR@doendequation{equation*}]

    \csletcs{LWR@equationnormalstar}{equation*}
    \csletcs{LWR@endequationnormalstar}{endequation*}
}% AtBeginDocument
```

Remember the "less" version of `equation`, which uses MathJax and `alt` tags, but does not support complicated contents such as some Ti*k*z expressions.

```
\AtBeginDocument{
    \LetLtxMacro\LWR@equationless\equation
    \LetLtxMacro\endLWR@equationless\endequation
    \csletcs{LWR@equationlessstar}{equation*}
    \csletcs{LWR@endequationlessstar}{endequation*}
}
```

83.6 `\displaymathnormal` and `\displaymathother`

`\displaymathnormal` By default, or when selecting `\displaymathnormal`, MathJax math display environments print their contents as text into HTML for MathJax to interpret, and SVG display math environments render their contents as SVG images and use their contents as the `alt` tag of HTML output. To do so, the contents are loaded into a macro for reuse. In some cases, such as complicated Ti*k*z pictures, compilation will fail.

`\displaymathother` MathJax unsupported complicated `alt` tag When selecting `\displaymathother`, it is assumed that the contents are more complicated than "pure" math. An example is an elaborate Ti*k*z picture, which will not render in MathJax and will not make sense as an HTML `alt` tag. In this mode, MathJax is turned off, math display environments become SVG images, even if MathJax is selected, and the HTML `alt` tags become simple messages. The contents are internally processed as an environment instead of a macro argument, so complicated objects such as Ti*k*z pictures are more likely to compile successfully.

`\displaymathnormal` simple math objects Use when display math environments have simple math which is to sent to MathJax or included in HTML `alt` tags.

```
\newcommand*{\displaymathnormal}{%
    \ifbool{LWR@origmathjax}{\booltrue{mathjax}}{\boolfalse{mathjax}}%
```

```
    \LetLtxMacro\[\LWR@openbracketnormal%
    \LetLtxMacro\]\LWR@closebracketnormal%
    \LetLtxMacro\displaymath\LWR@displaymathnormal%
    \LetLtxMacro\enddisplaymath\endLWR@displaymathnormal%
    \LetLtxMacro\equation\LWR@equationnormal%
    \LetLtxMacro\endequation\endLWR@equationnormal%
    \csletcs{equation*}{LWR@equationnormalstar}%
    \csletcs{endequation*}{LWR@endequationnormalstar}%
}
```

`\displaymathother` complicated math objects

Use when display math environments have complicated objects which will not work with MathJax or should not be included in HTML `alt` tags. Complicated contents are more likely to compile correctly.

```
\newcommand*{\displaymathother}{%
    \boolfalse{mathjax}%
    \LetLtxMacro\displaymath\LWR@displaymathother%
    \LetLtxMacro\enddisplaymath\endLWR@displaymathother%
    \LetLtxMacro\[\LWR@displaymathother%
    \LetLtxMacro\]\endLWR@displaymathother%
    \LetLtxMacro\equation\LWR@equationother%
    \LetLtxMacro\endequation\endLWR@equationother%
    \csletcs{equation*}{displaymath}%
    \csletcs{endequation*}{enddisplaymath}%
}
```

```
\end{warpHTML}
```

for PRINT output:

```
\begin{warpprint}
```

Print-mode versions:

```
\newcommand*{\displaymathnormal}{}
\newcommand*{\displaymathother}{}
```

```
\end{warpprint}
```

for HTML output:

```
\begin{warpHTML}
```

83.7 AMS Math environments

83.7.1 Support macros

Bool `LWR@amsmultline` True if processing a multline environment.

To compensate for `multline`-spefific code, `LWR@amsmultline` is used to add extra horizontal space in `\LWR@htmlmathlabel` if is used in an amsmath environment which is not a `multline` environment and not an `equation`.

```
\newbool{LWR@amsmultline}
\boolfalse{LWR@amsmultline}
```

\LWR@beginhideamsmath Starts hiding LaTeX math inside an HTML comment.

```
\newcommand*{\LWR@beginhideamsmath}{
    \LWR@stoppars
    \LWR@origtilde\LWR@orignewline
    \LWR@htmlopencomment

    \begingroup
    \LWR@restoreorigformatting
```

Temporarily prevent underfull \hbox warnings.

```
    \hbadness=10000\relax%

    \booltrue{LWR@insidemathcomment}
}
```

\LWR@endhideamsmath Ends hiding LaTeX math inside an HTML comment.

```
\newcommand*{\LWR@endhideamsmath}{
    \endgroup

    \LWR@htmlclosecomment
    \boolfalse{LWR@insidemathcomment}
    \LWR@orignewline
    \LWR@startpars
}
```

83.7.2 Environment patches

The amsmath environments already collect their contents in \@envbody for further processing. eqnarray is not an $\mathcal{AMS}$ package, and thus requires special handling.

For SVG math: Each envrionment is encapsulated inside a `latexmage` environment, along with a special optional argument of \LWR@amsmathbody or \LWR@amsmathbodynumbered telling `latexmage` to use as the HTML <alt> tag the environment's contents which were automatically captured by the $\mathcal{AMS}$ environment.

For MathJax: Each environment is syched with LaTeX's equation numbers, typeset with LaTeX inside an HTML comment, then printed to HTML output for MathJax to process.

Env eqnarray This environmnet is not an $\mathcal{AMS}$ environment and thus its body is not automatically captured, so the environ package is used to capture the environment into \BODY.

```
\let\LWR@origeqnarray\eqnarray
\let\LWR@origendeqnarray\endeqnarray
```

To remember whether the starred environment was used, and thus whether to number the equations:

```
\newbool{LWR@numbereqnarray}
\booltrue{LWR@numbereqnarray}
```

Common code used by `eqnarray` and `Beqnarray` (from fancybox):

```
\newcommand{\LWR@eqnarrayfactor}{%
```

If `mathjax` or `FormatWP`, print the LaTeX expression:

```
    \ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
    {%
```

If MathJax, the environment contents (the `\BODY`) are executed in a HTML comment to trigger the correct equation number increment (if not starred), then are included verbatim in the output for MathJax to interpret:

```
        \LWR@syncmathjax%
        \boolfalse{LWR@amsmultline}%
        \ifbool{LWR@numbereqnarray}%
        {%
```

If numbering the equations, execute a copy inside an HTML comment block:

```
            \LWR@beginhideamsmath%
            \LWR@origeqnarray%
            \BODY%
            \LWR@origendeqnarray%
            \LWR@endhideamsmath%
```

Then print the (sanitized) contents to the output for MathJax to interpret:

```
            \LWR@addmathjax{eqnarray}{\BODY}%
        }%
        {% not LWR@numbereqnarray
```

If not numbering equations, just create the contents for MathJax:

```
            \LWR@addmathjax{eqnarray*}{\BODY}%
        }% LWR@numbereqnarray
    }% mathjax
    {% not mathjax
        \ifbool{LWR@numbereqnarray}%
        {%
```

For numbered SVG equations, first create a `lateximage` with an `alt` attribute containing sanitized copy of the source code:

```
            \begin{BlockClass}{displaymathnumbered}%
            \LWR@newautoidanchor%
            \booltrue{LWR@indisplaymathimage}%
        \begin{lateximage}[(\LWR@startingequationtag\textendash\LWR@equationtag)%
                \LWR@addmathjax{eqnarray}{\BODY}]*(math)%
```

Support for xfakebold:

```
            \LWR@applyxfakebold%
```

Create the image contents using an actual eqnarray:

```
            \LWR@origeqnarray%
            \BODY%
            \LWR@origendeqnarray%
            \end{lateximage}%
            \end{BlockClass}%
        }%
        {% not LWR@numbereqnarray
```

If not numbered, do the same, but an extra \nonumber seems to be required:

```
            \begin{BlockClass}{displaymath}%
            \LWR@newautoidanchor%
            \booltrue{LWR@indisplaymathimage}%
            \begin{lateximage}[\LWR@addmathjax{eqnarray*}{\BODY}]*(math)%
```

Support for xfakebold:

```
            \LWR@applyxfakebold%

            \def\@eqncr{\nonumber\@seqncr}
            \csuse{LWR@origeqnarray}%
            \BODY%
            \nonumber\csuse{LWR@origendeqnarray}%
            \end{lateximage}%
            \end{BlockClass}%
        }% LWR@numbereqnarray
    }% not mathjax
```

Default to number equations in the future:

```
    \booltrue{LWR@numbereqnarray}%
```

Clear the single-use alt text:

```
    \gdef\LWR@ThisAltText{}%
}
```

eqnarray itself is made with a blank line before and after to force it to be on its own line:

```
\RenewEnviron{eqnarray}
{%

\LWR@eqnarrayfactor

}
```

The starred version is patched to turn off the numbering:

```
\csgpreto{eqnarray*}{\boolfalse{LWR@numbereqnarray}}

\end{warpHTML}
```

84 Lateximages

84.1 Description

Env `lateximage` A `lateximage` is a piece of the document which is typeset in LaTeX then included in the HTML output as an image. This is used for math if SVG math is chosen, and also for the `picture`, `tikzpicture`, and other environments.

Before typesetting the `lateximage` a large number of formatting, graphics, and symbols-related macros are temporarily restored to their print-mode meaning by `\LWR@restoreorigformatting`. (See section 81.)

A `lateximage` is typeset on its own PDF page inside an HTML comment which starts on the preceeding page and ends on following page, and instructions are written to `lateximage.txt` for *lwarpmk* to extract the `lateximage` from the page of the PDF file then generate an accompanying `.svg` file image file. Meanwhile, instructions to show this image are placed into the HTML file after the comment.

An HTML `<span>` is created to hold both the HTML comment, which will have the *pdftotext* conversion, and also the link to the final `.svg` image.

A LaTeX label is used to remember which PDF page has the image. A label is used because footnotes, endnotes, and pagenotes may cause the image to appear at a later time. The label is declared along with the image, and so it correctly remembers where the image finally ended up.

HTML `alt` tag The HTML `alt` tag is set to the LaTeX source for SVG math, some chemistry expressions, and perhaps some other expressions which make sense for text copy/paste. In some other cases, the `alt` tag is set according to the package name.

When creating an SVG math image, its HTML `alt` tag may be set to the math expression, which may be hashed for image reuse. In the case of `\ensuremath` or after `\inlinemathother`, where the contents require a unique image for each instance of the same expression, the `alt` tag is set to `\MathImageAltText`, along with `\AltTextOpen` and `\AltTextClose`, and the image is not reused.

This `alt` expression is visible in the browser if images are not loaded, and appears when the text is copied and pasted. The default is "`math image`", and it may be changed according to the document's language. This may be set in the preamble, or changed as necessary inside the document, where it will affect the following SVG math images.

For many packages, the output is placed inside a `lateximage` with an HTML `alt` tag set to the package name followed by `\PackageDiagramAltText`. For example:

```
(-xy- diagram)
```

This expression is visible in the browser if images are not loaded, and appears when the text is copied and pasted. The default is "diagram", and may it be changed according to the document's language. This may be set in the preamble, or changed as necessary inside the document, where it will affect the following package diagrams.

SVG image font size For the `lateximage` environment, the size of the math and text used in the SVG image

may be adjusted by setting \LateximageFontSizeName to a font size name — *without the backslash*, which defaults to:

```
\renewcommand{\LateximageFontSizeName}{normalsize}
```

For inline SVG math, font size is instead controlled by \LateximageFontScale, which defaults to:

```
\newcommand*{\LateximageFontScale}{.75}
```

84.2 Support counters and macros

for HTML output:

```
\begin{warpHTML}
```

Ctr LWR@lateximagenumber

Sequence the images.

```
\newcounter{LWR@lateximagenumber}
\setcounter{LWR@lateximagenumber}{0}
```

Ctr LWR@lateximagedepth

Do not create \lateximage inside of \lateximage.

```
\newcounter{LWR@lateximagedepth}
\setcounter{LWR@lateximagedepth}{0}
```

A few utility macros to write special characters:

```
\edef\LWR@hashmark{\string#} % for use in \write
\edef\LWR@percent{\@percentchar} % for use in \write
```

Ctr LWR@LIpage

Used to reference the PDF page number of a lateximage to be written into <project>-images.txt.

```
\newcounter{LWR@LIpage}
```

```
\end{warpHTML}
```

84.3 Font size

for HTML & PRINT:

```
\begin{warpall}
```

\LateximageFontSizeName

Declares how large to write text in \lateximages. The .svg file text size should blend well with the surrounding HTML text size.

⚠ no backslash

Do not include the leading backslash in the name.

```
\newcommand*{\LateximageFontSizeName}{normalsize}
```

\LateximageFontScale

Declares how large to scale inline SVG math images. The .svg file text size should blend well with the surrounding HTML text size. The default is 1, but it may be redefined as needed depending on the HTML font.

```
\newcommand*{\LateximageFontScale}{1}
```

```
\end{warpall}
```

84.4 Equation numbers

for HTML output:

```
\begin{warpHTML}
```

Ctr `LWR@startingequation`

For use with `lateximage` and multi-line numbered equations. Remembers the next equation number so that it may be printed in the alt tag.

```
\newcounter{LWR@startingequation}

\@ifundefined{chapter}
{
\renewcommand{\theLWR@startingequation}{%
    \arabic{LWR@startingequation}%
}
}
{% chapter defined
\renewcommand{\theLWR@startingequation}{%
    \ifnumcomp{\value{chapter}}{>}{0}{\arabic{chapter}.}{}%
    \arabic{LWR@startingequation}%
}
}
```

Bool `LWR@isstartingequation`

True for the first equation tag, false for later tags in the same environment.

```
\newbool{LWR@isstartingequation}
```

`\LWR@startingequationtag`

Prints the starting equation number or tag.

```
\let\LWR@startingequationtag\theLWR@startingequation
```

`\LWR@equationtag`

Prints the ending equation number or tag.

This is reset by `lateximage`, may be temporarily overwritten by `\tag` calling `\LWR@remembertag`.

```
\newcommand*{\LWR@equationtag}{}
```

Only if svg math, patch `\tag` after packages have loaded, in case someone else modified `\tag`.

```
\AtBeginDocument{

\ifbool{mathjax}{}{% not mathjax
```

`\LWR@remembertag` {⟨*tag*⟩}

For use inside the math environments while using svg math. Sets `\theLWR@startingequation` and `\theequation` to the given tag.

```
\NewDocumentCommand{\LWR@remembertag}{m}{%
    \ifbool{LWR@isstartingequation}%
    {%
        \global\boolfalse{LWR@isstartingequation}%
        \xdef\LWR@startingequationtag{#1}%
    }{}%
    \xdef\LWR@equationtag{#1}%
}%

}% not mathjax
}% AtBeginDocument
```

84.5 HTML alt tags

\LWR@amsmathbody {⟨*envname*⟩} For use inside the optional argument to a lateximage to add the contents of a AMS math environment to the <alt> tag.

```
\newcommand*{\LWR@amsmathbody}[1]
{%
    \textbackslash\{begin\}\{#1\} % extra space
    \LWR@HTMLsanitizeexpand{\detokenize\expandafter{\the\@envbody}}%
    \textbackslash\{end\}\{#1\}%
}
```

\LWR@amsmathbodynumbered {⟨*envname*⟩} For use inside the optional argument to a lateximage to add the contents of a AMS math environment to the alt tag, prefixed by the equation numbers.

```
\newcommand*{\LWR@amsmathbodynumbered}[1]
{%
    \ifnumcomp{\value{LWR@startingequation}}{=}{\value{equation}}%
        {(\LWR@equationtag)}%
        {(\LWR@startingequationtag\textendash\LWR@equationtag)} % extra space
    \LWR@amsmathbody{#1} % extra space
}
```

84.6 lateximage environment

\LWR@lateximage@oneimageb {⟨*1: alt text*⟩} {⟨*2: filename*⟩} {⟨*3: CSS style*⟩} {⟨*4: ARIA role*⟩} Creates the image for the lateximage.

```
\newcommand{\LWR@lateximage@oneimageb}[4]{%
    \LWR@subinlineimage{#1}{lateximage}%
    {%
        \LWR@print@mbox{%
            \LWR@ImagesDirectory\OSPathSymbol%
            #2%
        }%
    }{svg}{#3}{#4}%
}
```

\LWR@lateximage@oneimage {⟨*1: alt text*⟩} {⟨*2: filename*⟩} {⟨*3: CSS style*⟩} {⟨*4: delimit?*⟩} {⟨*5: ARIA role*⟩}

Creates an image for the `lateximage`, whose `alt` text depends on the circumstances.

```
\newcommand{\LWR@lateximage@oneimage}[5]{%
    \ifdefvoid{\LWR@ThisAltText}{%
        \IfBooleanTF{#4}{%
            \LWR@lateximage@oneimageb{#1}{#2}{#3}{#5}%
        }{%
            \LWR@lateximage@oneimageb%
                {\AltTextOpen#1\AltTextClose}%
                {#2}{#3}{#5}%
        }%
    }{%
        \LWR@lateximage@oneimageb%
            {\AltTextOpen\LWR@ThisAltText\AltTextClose}%
            {#2}{#3}{#5}%
    }%
}
```

Env `lateximage` * [⟨*2:* `<alt>` *tag*⟩] * [⟨*4: add'l hashing*⟩] [⟨*5: CSS style*⟩] (⟨*6: ARIA role*⟩)

Typesets the contents and then renders the result as an SVG file. Star #1 causes the image to be hashed for reuse. Star #3 causes the `alt` tag to not include `\AltTextOpen` and `\AltTextClose`, for use with math expressions.

The optional `<alt>` tag is included in the HTML code for use with copy/paste.

image filename hashing

If starred, a hashed filename is used.If so, the hash is based on the `alt` tag and also the additional hashing argument.

This may be used to provide an expression with a simple `alt` tag but also enough additional information to provide a unique hash.

An example is when the expression is a complicated TEX expression, which would not copy/paste well. A simplified tag may be used, while the complicated expression is duplicated in the additional hashing argument.

Another example is when the expression is simple, but the image depends on options. These options may be decoded into text form and included in the additional hashing argument in order to make the hash unique according to the set of options, even if the simple `alt` tag is still the same.

File `*_html.aux`

A new label is placed into the file `*_html.aux`:

```
\newlabel{LWRlateximage-<BaseJobname>-<number>}{{<x>}{<y>}}
```

This is used to find the image in the PDF file, according to its name.

File `*-images.txt`

A list of images to generate is created in `<jobname>-images.txt`. Each line has three pipe-delimited fields, containing the PDF page number from `<jobname>_html.pdf`, where the image is located, a boolean indicating whether the image is hashed, and the filename of the image. The last line has "end" in each field, and is used to detect an incomplete compile.

```
\catcode`\$=\active%

\NewDocumentEnvironment{lateximage}{s O{\ImageAltText} s O{} O{} D(){}}%
{%
\LWR@traceinfo{lateximage: starting on \jobname.pdf page \arabic{page}}%
\LWR@traceinfo{lateximage: entering depth is \arabic{LWR@lateximagedepth}}%
```

Nested lateximages remain one large lateximage:

```
\ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
```

If nesting inside an already-existing lateximage, simply record one more level. $\mathcal{AMS}$ packages redefine \addtocounter to do nothing if inside a \text, so lower-level TEX macros are used for tracking nested lateximages.

```
{%
%     \addtocounter{LWR@lateximagedepth}{1}%
    \global\advance\c@LWR@lateximagedepth 1\relax% Due to AmS \text macro.
}%
```

Otherwise, this is the outer-most lateximage:

```
{% start of outer-most lateximage
```

Remember the next equation number to be allocated, in case it must be printed in a multi-equation environment:

```
    \LWR@traceinfo{lateximage: starting outer-most lateximage}%
    \setcounter{LWR@startingequation}{\value{equation}}%
    \addtocounter{LWR@startingequation}{1}%
    \booltrue{LWR@isstartingequation}%
    \let\LWR@startingequationtag\theLWR@startingequation%
```

The default equation tag, unless overwritten by \tag:

```
    \let\LWR@equationtag\theequation%
```

Starting a new lateximage:

```
    \addtocounter{LWR@lateximagenumber}{1}%
   \LWR@traceinfo{lateximage: LWR@lateximagenumber is \arabic{LWR@lateximagenumber}}%
```

While inside a lateximage, locally do not use mathjax:

```
    \boolfalse{mathjax}%
```

Be sure that are doing a paragraph:

```
    \LWR@ensuredoingapar%
```

Inside the lateximage, temporarily prevent underfull \hbox warnings.

```
            \hbadness=10000\relax%
```

Next file:

```
    \addtocounter{LWR@externalfilecnt}{1}%
  \LWR@traceinfo{lateximage: LWR@externalfilecnt is \arabic{LWR@externalfilecnt}}%
```

Figure out what the next page number will be. `\setcounterpageref` assigns `LWR@LIpage` to the page number for the reference `LWRlateximage-BaseJobname-XXX`:

```
    \setcounterpageref{LWR@LIpage}{%
        LWRlateximage-\BaseJobname-\arabic{LWR@lateximagenumber}%
    }%
    \LWR@traceinfo{lateximage: LWR@LIpage is \arabic{LWR@LIpage}}%
```

Create an HTML span which will hold the comment which contains the ***pdftotext*** translation of the image's page, and also will hold the link to the `.svg` file:

```
    \LWR@htmltag{span\LWR@indentHTML%
        id=\textquotedbl{}%
            lateximage-\BaseJobname-\arabic{LWR@lateximagenumber}%
            \textquotedbl\LWR@indentHTML
        class=\textquotedbl{}lateximagesource\textquotedbl\LWR@orignewline
    }%
```

Write instructions to the `<ImagesDirectory>.txt` file:

```
    \LWR@traceinfo{lateximage: about to write to \BaseJobname-images.txt}%
    \IfBooleanTF{#1}% starred
    {% hash
```

Compute and save the hashed file name for later use:

```
        \ifdefvoid{\LWR@ThisAltText}{%
            \IfBooleanTF{#3}{%
                \edef\LWR@hashedname{%
                    \LWR@mdfive{\detokenize\expandafter{#2}-!-#4}%
                }%
            }{%
                \edef\LWR@hashedname{%
              \LWR@mdfive{\detokenize\expandafter{\AltTextOpen#2\AltTextClose}-!-#4}%
                }%
            }%
        }{%
            \edef\LWR@hashedname{%
           \LWR@mdfive{\detokenize\expandafter{\AltTextOpen\LWR@ThisAltText\AltTextClose}-!-#4}%
            }%
        }%
        \LWR@traceinfo{lateximage: hash is \LWR@hashedname}%
```

Write the page, hashing, and hashed name:

```
        \immediate\write\LWR@lateximagesfile{%
            |\arabic{LWR@LIpage}|true|\LWR@hashedname|%
        }%
    }% hash
    {% no hash
```

No hash, so write the page, no hashing, and the image number:

```
        \LWR@traceinfo{lateximage: hash false}%
        \immediate\write\LWR@lateximagesfile{%
        |\arabic{LWR@LIpage}|false|\LWR@ImagesName\arabic{LWR@externalfilecnt}|%
        }%
    }% no hash
```

Place an open comment tag. This will hide any traces of the lateximage PDF page which were picked up by *pdftotext*.

```
    \LWR@traceinfo{lateximage: about to create open comment}%
    \LWR@htmlopencomment%
```

One level deeper. At this outer-most `lateximage`, it is known that this is not being used inside an $\mathcal{AMS}$ `\text`, since the outer-most level will never be in math mode.

```
     \addtocounter{LWR@lateximagedepth}{1}%
```

Start the new PDF page:

```
    \LWR@traceinfo{lateximage: about to create a new page}%
    \LWR@maybe@orignewpage%
```

If the current page is larger, typeset the image in a "standard" width page and font size:

```
    \LWR@traceinfo{lateximage: about to create minipage}%
    \ifdimless{\linewidth}{6in}{%
        \LWR@print@minipage{\linewidth}%
    }{%
        \LWR@print@minipage{6in}%
    }%
    \@nameuse{LWR@print@\LateximageFontSizeName}%
```

Temporarily restore formatting to its PDF definitions: Do not produce HTML tags for \hspace, etc. inside a lateximage.

```
    \LWR@traceinfo{lateximage: about to temporarily restore formatting}%
    \LWR@restoreorigformatting%
```

Use full-page footnotes instead of minipage footnotes. These become HTML footnotes.

```
    \def\@mpfn{footnote}%
    \def\thempfn{\thefootnote}%
    \LetLtxMacro\@footnotetext\LWR@footnotetext%
```

Create the `LWRlateximage<number>` label:

```
    \LWR@traceinfo{lateximage: about to create label}%
    \LWR@orig@label{LWRlateximage-\BaseJobname-\arabic{LWR@lateximagenumber}}%
    \LWR@traceinfo{lateximage: finished creating the label}%
```

Adjust the rule color to match HTML:

```
    \ifdefvoid{\LWR@ruleHTMLcolor}{}{%
        \LWR@print@arrayrulecolor[HTML]{\LWR@ruleHTMLcolor}%
    }%
```

Enable print-mode math functions:

```
    \LetLtxMacro$\LWR@origdollar%
    \catcode`\$=3% math shift
    \LetLtxMacro\(\LWR@origopenparen%
    \LetLtxMacro\)\LWR@origcloseparen%
```

Only enable print-mode display math if are not already inside display math:

```
    \ifbool{LWR@indisplaymathimage}{}{% not in display math
        \LetLtxMacro\[\LWR@origopenbracket%
        \LetLtxMacro\]\LWR@origclosebracket%
        \let\equation\LWR@orig@equation%
        \let\endequation\LWR@orig@endequation%
        \csletcs{equation*}{LWR@orig@equation*}%
        \csletcs{endequation*}{LWR@orig@endequation*}%
    }% not in display math
```

For chemformula:

```
    \LetLtxMacro\LWR@newsingledollar$%
    \LetLtxMacro\LWR@newsingledollar$% syntax highlighting
```

```
}% end of outer-most lateximage
\LWR@traceinfo{lateximage: finished start of environment}%
}% end of \begin{lateximage}
```

\endlateximage When the lateximage environment closes:

```
{% start of \end{lateximage}
\LWR@traceinfo{lateximage: starting end of lateximage}%
```

Nested more than one deep?

```
\LWR@traceinfo{lateximage: internal depth was \arabic{LWR@lateximagedepth}}%
\ifnumcomp{\value{LWR@lateximagedepth}}{>}{1}%
```

If nesting inside an already existing lateximage, simply record one less level. Uses a lower-level TEX macro due to $\mathcal{AMS}$ \text change of \addtocounter.

```
{%
    \LWR@traceinfo{lateximage: unnesting}%
    \global\advance\c@LWR@lateximagedepth -1\relax%
}%
```

If this is the outer-most lateximage:

```
{% end of outer-most lateximage
```

Finish the lateximage minipage and start a new PDF page:

```
\LWR@traceinfo{lateximage: ending outer-most lateximage}%
    \endLWR@print@minipage%
    \LWR@maybe@orignewpage%
```

Close the HTML comment which encapsulated any traces of the lateximage picked up by *pdftotext*:

```
    \LWR@print@vspace*{.5\baselineskip}%
    \LWR@htmlclosecomment%
    \LWR@traceinfo{lateximage: The page after the image is \arabic{page}}%
```

Create a link to the lateximage, allowing its natural height:

```
    \IfBooleanTF{#1}% starred
    {% hash
        \LWR@lateximage@oneimage{#2}{\LWR@hashedname}{#5}{#3}{#6}%
    }% hash
    {% no hash
     \LWR@lateximage@oneimage{#2}{\LWR@ImagesName\theLWR@externalfilecnt}{#5}{#3}{#6}%
    }% no hash
```

Be sure that are doing a paragraph:

```
    \LWR@ensuredoingapar%
```

Close the HTML span which has the *pdftotext* comment and also the link to the `.svg` image:

```
    \LWR@htmltag{/span}%
    \ifbool{HTMLDebugComments}{%
        \LWR@htmlcomment{End of lateximage}%
    }{}%
```

Undo one lateximage level. This is not inside an $\mathcal{AMS}$ `\text`, so regular `\addtocounter` may be used here.

```
    \addtocounter{LWR@lateximagedepth}{-1}%
```

Clear the single-use `alt` text:

```
    \gdef\LWR@ThisAltText{}%
}% end of outer-most lateximage
\LWR@traceinfo{lateximage: exiting depth is \arabic{LWR@lateximagedepth}}%
\LWR@traceinfo{lateximage: done}%
}%
\catcode`\$=3% math shift
\end{warpHTML}
```

for PRINT output:

```
\begin{warpprint}
```

Env `lateximage` * [⟨<alt> *tag*⟩] * [⟨*add'l hashing*⟩] [⟨*CSS style*⟩]

varwidth is used to create a box of the natural width of its contents.

```
\NewDocumentEnvironment{lateximage}{s o s o o d()}
    {\begin{varwidth}[b]{\linewidth}}
    {\end{varwidth}}

\end{warpprint}
```

85 center, flushleft, flushright

for HTML output:

```
\begin{warpHTML}
```

Env center Replace center functionality with css tags. In a , these macros are nullified, but extra % are used to remove spurrious spaces here as well.

```
\newenvironment*{LWR@HTML@center}
{%
    \LWR@forcenewpage%
    \ifbool{FormatWP}%
        {\BlockClass[\LWR@print@mbox{text-align:center}]{center}}%
        {\BlockClass{center}}%
}
{\endBlockClass}

\LWR@formattedenv{center}
```

Env flushright

```
\newenvironment*{LWR@HTML@flushright}
{%
    \LWR@forcenewpage%
    \ifbool{FormatWP}%
        {\BlockClass[\LWR@print@mbox{text-align:right}]{flushright}}%
        {\BlockClass{flushright}}%
}
{\endBlockClass}

\LWR@formattedenv{flushright}
```

Env flushleft

```
\newenvironment*{LWR@HTML@flushleft}
{%
    \LWR@forcenewpage%
    \ifbool{FormatWP}%
        {\BlockClass[\LWR@print@mbox{text-align:left}]{flushleft}}%
        {\BlockClass{flushleft}}%
}
{\endBlockClass}

\LWR@formattedenv{flushleft}
```

\centering, \raggedleft, and \raggedright usually have no effect on the HTML output, but they may be used to compare with the next token to identify their use at the start of a float. See \LWR@floatalignment.

\centering

```
\newcommand*{\LWR@HTML@centering}{%
    \ifbool{HTMLDebugComments}{%
        \LWR@htmlcomment{centering}%
    }{}%
}
\LWR@formatted{centering}
```

\raggedleft

```
\newcommand*{\LWR@HTML@raggedleft}{%
    \ifbool{HTMLDebugComments}{%
        \LWR@htmlcomment{raggedleft}%
    }{}%
}
\LWR@formatted{raggedleft}
```

\raggedright

```
\newcommand*{\LWR@HTML@raggedright}{%
    \ifbool{HTMLDebugComments}{%
        \LWR@htmlcomment{raggedright}%
    }{}%
}
\LWR@formatted{raggedright}
```

\leftline {⟨*text*⟩}

```
\renewcommand{\leftline}[1]{\begin{flushleft}#1\end{flushleft}}
```

\centerline {⟨*text*⟩}

```
\renewcommand{\centerline}[1]{\begin{center}#1\end{center}}
```

\rightline {⟨*text*⟩}

```
\renewcommand{\rightline}[1]{\begin{flushright}#1\end{flushright}}
```

```
\end{warpHTML}
```

86 Preloaded packages

for HTML output:

```
\begin{warpHTML}
```

If the given package was loaded before or by lwarp, load the lwarp version as well.

`\LWR@PreloadedPackage` {⟨*packagename*⟩}

```
\newcommand*{\LWR@PreloadedPackage}[1]{%
    \@ifpackageloaded{#1}%
        {%
            \AtBeginDocument{
                \LWR@origRequirePackage{lwarp-#1}%
            }
        }%
        {}%
}
```

If inputtrc was loaded before lwarp, as is usually done, explicitly load the lwarp patches now:

```
\LWR@PreloadedPackage{inputtrc}
```

If textcomp was loaded before lwarp, perhaps as part of the font-related packages, explicitly load the lwarp patches now:

```
\LWR@PreloadedPackage{textcomp}
```

If xunicode was loaded before lwarp, perhaps as part of the font-related packages, explicitly load the lwarp patches now:

```
\LWR@PreloadedPackage{xunicode}
```

If graphics or graphicx were loaded before lwarp, perhaps by xunicode, explicitly load the lwarp patches now:

```
\LWR@PreloadedPackage{graphics}
\LWR@PreloadedPackage{graphicx}
```

scalefnt may have been preloaded by babel

```
\LWR@PreloadedPackage{scalefnt}
```

fontaxes must be preloaded so that lwarp may patch it for HTML.

```
\LWR@PreloadedPackage{fontaxes}
```

Various font packages which may be loaded before lwarp:

```
\LWR@PreloadedPackage{cmbright}
\LWR@PreloadedPackage{fourier}
\LWR@PreloadedPackage{kpfonts}
\LWR@PreloadedPackage{kpfonts-otf}
\LWR@PreloadedPackage{libertinust1math}
\LWR@PreloadedPackage{pxfonts}
\LWR@PreloadedPackage{txfonts}
\LWR@PreloadedPackage{txgreeks}
```

```
\LWR@PreloadedPackage{newpxmath}
\LWR@PreloadedPackage{newtxmath}
\LWR@PreloadedPackage{newtxsf}
\LWR@PreloadedPackage{mathalpha}
\LWR@PreloadedPackage{unicode-math}
```

nfssext-cfr may be preloaded by cfm-lm or related font packages.

```
\LWR@PreloadedPackage{nfssext-cfr}
```

ulem may be preloaded by ctex, ctexart, and related classes.

```
\LWR@PreloadedPackage{ulem}
```

```
\LWR@PreloadedPackage{xetexko}
```

geometry is preloaded by lwarp, and perhaps by various classes.

```
\LWR@PreloadedPackage{geometry}
```

plext is preloaded by some CJK classes.

```
\LWR@PreloadedPackage{plext}
```

stfloats is preloaded by ltj* classes.

```
\LWR@PreloadedPackage{stfloats}
```

lltjext is preloaded by ltj* classes.

```
\LWR@PreloadedPackage{lltjext}
```

luatexko must be loaded before lwarp.

```
\LWR@PreloadedPackage{luatexko}
```

```
\end{warpHTML}
```

87 siunitx

Pkg siunitx The lwarp core passes a few options to siunitx.

⚠ v3 not yet! siunitx v3 is not yet supported. For now, specify version 2:

```
\usepackage{siunitx}[=v2]
```

This may be also be necessary before loading other packages which also use siunitx, such as chemmacros.

fractions Due to *pdftotext* limitations, fraction output is replaced by symbol output for `per-mode` and `quotient-mode`.

⚠ math mode required

Some units will require that the expression be placed inside math mode.

⚠ tabular

Tabular `S` columns are rendered as simple `c` columns, and tabular `s` columns are not supported. These may be replaced by `c` columns with each cell contained in `\num` or `\si`.

⚠ MathJax

For math mode with SVG display, the original siunitx code is used while generating the SVG image. For text mode, lwarp uses an emulation which provides a very effective HTML interpretation of siunitx. For math expressions while using MathJax, a limited emulation is used. Most functions work reasonably well, but many options cannot be emulated. Complicated parsing such as for `\ang` is not supported. The result usually looks fine, and otherwise is enough to get the meaning across.

Document modifications required for MathJax:

custom units

- Custom units may be added with `\CustomizeMathJax`. See the lwarp-siunitx code for examples.

⚠ unit spacing

- Units work better using ~ between units instead of using periods.

⚠ `\square`, `\cubic`

- To square or cube compound units, enclose the following compound units in braces:

  ```
  \cubic{\centi\meter}
  ```

  Single units do not require braces.

Also see MathJax option, section 8.7.4.

for HTML output:

```
\begin{warpHTML}
```

Options for siunitx:

```
\newrobustcmd{\LWR@siunitx@textcelsius}{\HTMLentity{deg}C}
\newrobustcmd{\LWR@siunitx@textdegree}{\HTMLentity{deg}}
\newrobustcmd{\LWR@siunitx@textprime}{\HTMLunicode{2032}}
\newrobustcmd{\LWR@siunitx@textdblprime}{\HTMLunicode{2033}}
\newrobustcmd{\LWR@siunitx@textplanckbar}{\text{\textit{\HTMLunicode{210F}}}}

\appto\LWR@restoreorigformatting{%
\renewrobustcmd{\LWR@siunitx@textcelsius}{\text{\ensuremath{^\circ}C}}%
\renewrobustcmd{\LWR@siunitx@textdegree}{\text{\ensuremath{^\circ}}}%
\renewrobustcmd{\LWR@siunitx@textprime}{\text{\ensuremath{^\prime}}}%
\renewrobustcmd{\LWR@siunitx@textdblprime}{\text{\ensuremath{^{\prime\prime}}}}%
\renewrobustcmd{\LWR@siunitx@textplanckbar}{\text{\ensuremath{\hbar}}}%
}

\PassOptionsToPackage{
    detect-mode=true,
    per-mode=symbol,% fraction is not seen by pdftotext
    text-celsius = {\LWR@siunitx@textcelsius},
    text-degree = {\LWR@siunitx@textdegree},
    text-arcminute = {\LWR@siunitx@textprime} ,
    text-arcsecond = {\LWR@siunitx@textdblprime} ,
}{siunitx-v2}

\end{warpHTML}
```

88 Graphics print-mode modifications

88.1 General limitations

⚠ case sensitive

Per table 9, image filenames may be specified either with or without an extension. If an extension is given it will be used as-is, for either print or HTML output. If no extension is given, a list of possible extensions is tried, which depends on whether print or HTML is being generated. This allows a PDF file for print and a SVG file for HTML, for example. If no extension is given, the automatic search will only return lowercase extensions, even if the filename actually has an uppercase extension, and lwarp cannot get around this problem, so image file extensions must be lowercase to be seen by the HTML browser with lwarp. For example, name the image file `image.pdf` instead of `image.PDF`, but refer to it in the source as `image`, without an extension. For images which may be used as-is with either print or HTML, such as JPG or PNG, you may use a capitalized extension if it is specified in the source, such as `image.JPG`.

`\includegraphics` file formats

For `\includegraphics` with `.pdf` or `.eps` files, the user must provide a `.pdf` or `.eps` image file for use in print mode, and also a `.svg`, `.png`, or `.jpg` version of the same image for use in HTML.

```
\includegraphics{filename} % print:.pdf/.eps HTML:.svg, etc.
```

For print output, lwarp will automatically choose the `.pdf` or `.eps` format if available, or some other format otherwise. For HTML, one of the other formats is used instead.

If a `.pdf` or `.eps` image is referred to with its file extension, the extension will be changed to `.svg` for HTML:

```
\includegraphics{filename.pdf} % uses .svg in html
\includegraphics{filename.eps} % uses .svg in html
```

Prog `pdftocairo`

PDF to SVG

To convert a PDF image to SVG, use the utility *pdftocairo*:

Enter ⇒ **`pdftocairo -svg filename.pdf`**

Prog `lwarpmk pdftosvg`

For a large number of images, use *lwarpmk*:

Enter ⇒ **`lwarpmk pdftosvg *.pdf`** **(or a list of filenames)**

Prog `lwarpmk epstopdf`

Prog `epstopdf`

epstopdf package

For EPS images converted to PDF using the package epstopdf, use

Enter ⇒ **`lwarpmk pdftosvg *.PDF`**

to convert to SVG images.

DVI LaTeX

When using DVI *latex*, it is necessary to convert EPS to PDF and then to SVG:

Enter ⇒ **`lwarpmk epstopdf *.eps`** **(or a list of filenames)**

Enter ⇒ **`lwarpmk pdftosvg *.pdf`** **(or a list of filenames)**

PNG and JPG

For PNG or JPGwhile using *pdflatex*, *lualatex*, or *xelatex*, the same file may be used in both print or HTML versions, and may be used with a file extension, but will also be used without the file extension if it is the only file of its base name.

GIF — GIF files may be used for HTML, but another format must also be provided for print output.

file extension priorities — If a file extension is not used, for HTML the file extension priorities are: SVG, GIF, PNG, then JPG.

⚠ graphics vs. graphicx — If using the older graphics syntax, use both optional arguments for `\includegraphics`. A single optional parameter is interpreted as the newer graphicx syntax. Note that viewports are not supported by lwarp — the entire image will be shown.

⚠ viewport

⚠ viewport units — For `\includegraphics`, avoid `px` and `%` units for width and height, or enclose them inside `warpHTML` environments. For font-proportional image sizes, use `ex` or `em`. For fixed-sized images, use `cm`, `mm`, `in`, `pt`, or `pc`. Use the keys `width=.5\linewidth`, or similar for `\textwidth` or `\textheight` to give fixed-sized images proportional to a 6 by 9 inch text area. Do not use the `scale` option, since it is not well supported by HTML browsers.

options — `\includegraphics` accepts `width` and `height`, `origin`, `rotate` and `scale`, plus new `class` and `alt` keys.

HTML class — With HTML output, `\includegraphics` accepts an optional `class=xyz` keyval combination, and if this is given then the HTML output will include that class for the image. The class is ignored for print output.

HTML `alt` tags — Likewise, the `\includegraphics alt` key adds an HTML `alt` tag to an image, and is ignored for print output. If not assigned, each image is given an `alt` tag according to `\ImageAltText`.

⚠ `scale` — Avoid using the `\includegraphics scale` option. Change:

```
\includegraphics[scale=<xx>]{ . . . }
```

to:

```
\includegraphics[width=<yy>\linewidth]{ . . . }
```

`\rotatebox` — `\rotatebox` accepts the optional `origin` key.

⚠ browser support — `\rotatebox`, `\scalebox`, and `\reflectbox` depend on modern browser support. The CSS3 standard declares that when an object is transformed the whitespace which they occupied is preserved, unlike LaTeX, so expect some ugly results for scaling and rotating.

88.2 Print-mode modifications

for PRINT output: For print output, accept and then discard the new `class` key:

```
\begin{warpprint}
\define@key{Gin}{class}{}
\define@key{Gin}{alt}{}
```

Print-mode additions for the overpic package. See section 454 for the HTML version.

```
\AtBeginDocument{
\@ifpackageloaded{overpic}{
\newcommand*{\overpicfontsize}{12}
\newcommand*{\overpicfontskip}{14}
```

```
}{}
}
\end{warpprint}
```

89 xcolor boxes

Pkg xcolor

A few new definitions are provided for enhanced HTML colored boxes, and \fcolorbox is slightly modified. Print-mode version are also provided.

Print-mode versions of new xcolor defintions. These are defined inside warpall because they are also used for HTML while inside a lateximage. They are defined \AtBeginDocument so that the xcolor originals may first be loaded and saved for reuse.

The framed versions are modified to allow a background color of none, in which case only the frame is drawn, allowing the background page color to show.

for HTML & PRINT:

```
\begin{warpall}
```

After xparse may have been loaded ...

```
\AtBeginDocument{
```

... and *only* if xcolor was loaded:

```
\@ifpackageloaded{xcolor}{
\LWR@traceinfo{patching xcolor}
```

The print version:

\colorboxBlock

\colorboxBlock is the same as \colorbox:

```
\LetLtxMacro\colorboxBlock\colorbox
```

The original definition is reused by the new versions:

```
\LetLtxMacro\LWR@orig@print@fcolorbox\fcolorbox
```

\fcolorbox [⟨*framemodel*⟩] {⟨*framecolor*⟩} [⟨*boxmodel*⟩] {⟨*boxcolor*⟩} {⟨*text*⟩}

In print mode, \fcolorbox is modified to accept a background color of none.

(\fcolorbox is particular about its optional arguments, thus the elaborate combinations of \ifthenelse.)

```
\newsavebox{\LWR@colorminipagebox}

\NewDocumentCommand{\LWR@print@fcolorbox}{o m o m +m}{%
\LWR@traceinfo{LWR@print@fcolorbox #2 #4}%
```

Pre-load the contents into an LR box so that they can be used inside a \fcolorbox:

```
\begin{lrbox}{\LWR@colorminipagebox}%
#5%
\end{lrbox}%
```

Sort out the various optional arguments and the background color of none. In each case, the LRbox is placed inside a \fcolorbox.

The current color is remembered, then set to the frame, then the current color is used for the contents.

```
\ifstrequal{#4}{none}%
{% #4 none
    \LWR@traceinfo{background is none}%
    {% scope the \colorlet
        \colorlet{LWR@currentcolor}{.}%
        \color{#2}%
        \fbox{%
            \color{LWR@currentcolor}%
            \usebox{\LWR@colorminipagebox}%
        }% fbox
    }% colorlet
}% #4 none
{% #4 not none
\LWR@traceinfo{background not none}%
\IfValueTF{#1}%
{%
    \IfValueTF{#3}%
   {\LWR@orig@print@fcolorbox[#1]{#2}[#3]{#4}{\usebox{\LWR@colorminipagebox}}}%
    {\LWR@orig@print@fcolorbox[#1]{#2}{#4}{\usebox{\LWR@colorminipagebox}}}%
}%
{% no value #1
    \IfValueTF{#3}%
    {\LWR@orig@print@fcolorbox{#2}[#3]{#4}{\usebox{\LWR@colorminipagebox}}}%
    {\LWR@orig@print@fcolorbox{#2}{#4}{\usebox{\LWR@colorminipagebox}}}%
}% no value #1
}% #4 not none
\LWR@traceinfo{LWR@print@fcolorbox done}%
}
```

```
\renewrobustcmd*{\fcolorbox}{\LWR@print@fcolorbox}%
```

\fcolorboxBlock [⟨*framemodel*⟩] {⟨*framecolor*⟩} [⟨*boxmodel*⟩] {⟨*boxcolor*⟩} {⟨*text*⟩}

In print mode, \fcolorboxBlock is the same as \fcolorbox.

```
\newcommand*{\LWR@print@fcolorboxBlock}{\LWR@print@fcolorbox}
```

```
\newrobustcmd*{\fcolorboxBlock}{\LWR@print@fcolorboxBlock}
```

Env fcolorminipage [⟨*1:framemodel*⟩] {⟨*2:framecolor*⟩} [⟨*3:boxmodel*⟩] {⟨*4:boxcolor*⟩} [⟨*5:align*⟩] [⟨*6:height*⟩] [⟨*7:inner-align*⟩] {⟨*8:width*⟩}

In print mode, becomes a \fcolorbox containing a minipage:

```
\NewDocumentEnvironment{LWR@print@fcolorminipage}{o m o m O{c} O{} o m}
{%
\LWR@traceinfo{*** fcolorminipage: #2 #4 #8}%
```

Pre-load the contents into an LR box so that they can be used inside a `\fcolorbox`:

```
\begin{lrbox}{\LWR@colorminipagebox}%
```

If inner alignment is not given, use the outer alignment instead:

```
\IfValueTF{#7}%
{\begin{minipage}[#5][#6][#7]{#8}}%
{\begin{minipage}[#5][#6][#5]{#8}}%
}%
{%
\end{minipage}%
\end{lrbox}%
\LWR@traceinfo{*** starting end fcolorminipage #1 #2 #3 #4 #8}%
```

Sort out the various optional arguments and the background color of none. In each case, the LRbox is placed inside a `\fcolorbox`.

The current color is remembered, then set to the frame, then the current color is used for the contents.

```
\ifstrequal{#4}{none}%
{% #4 none
    {% scope the \colorlet
        \colorlet{LWR@currentcolor}{.}%
        \color{#2}%
        \fbox{%
            \color{LWR@currentcolor}%
            \usebox{\LWR@colorminipagebox}%
        }% fbox
    }% colorlet
}% #4 none
{% #4 not none
    \IfValueTF{#1}%
    {%
    \IfValueTF{#3}%
   {\LWR@orig@print@fcolorbox[#1]{#2}[#3]{#4}{\usebox{\LWR@colorminipagebox}}}%
    {\LWR@orig@print@fcolorbox[#1]{#2}{#4}{\usebox{\LWR@colorminipagebox}}}%
    }%
    {% no value #1
    \IfValueTF{#3}%
    {\LWR@orig@print@fcolorbox{#2}[#3]{#4}{\usebox{\LWR@colorminipagebox}}}%
    {\LWR@orig@print@fcolorbox{#2}{#4}{\usebox{\LWR@colorminipagebox}}}%
    }% no value #1
}% #4 not none
\LWR@traceinfo{*** finished end fcolorminipage}%
}

\NewDocumentEnvironment{fcolorminipage}{}
    {\LWR@print@fcolorminipage}
    {\endLWR@print@fcolorminipage}
```

```
\LWR@traceinfo{xcolor patches done}
}{}% xcolor loaded
}% AtBeginDocument

\end{warpall}
```

90 chemmacros environments

\makepolymerdelims and redox reactions must be enclosed in a lateximage during HTML output. These environments are provided here in print mode, and in the chemmacros code in HTML mode, as a high-level semantic syntax which automatically embeds the contents in a lateximage with an appropriate alt tag.

for PRINT output:

```
\begin{warpprint}

\AtBeginDocument{
\@ifpackageloaded{chemmacros}{
```

Env polymerdelims

```
\DeclareDocumentEnvironment{polymerdelims}{}
    {}{}
```

Env redoxreaction {⟨*space above*⟩} {⟨*space below*⟩}

For print output, extra space is include above and below the image, and a lateximage is not necessary. This extra space must be enforced, even inside a float, so zero-width rules are used.

For the HTML version, see section 191.4.

```
\DeclareDocumentEnvironment{redoxreaction}{m m}
    {\rule{0pt}{#1}}{\rule[-#2]{0pt}{#2}}

}{}% chemmacros
}% AtBeginDocument

\end{warpprint}
```

91 cleveref

loading order

cleveref and lwarp-cleveref with its associated macro patches are automatically preloaded at the end of the preamble via \AtEndPreamble and \AfterEndPreamble. This is done because the HTML conversion requires cleveref. The user's document may not require cleveref, thus the user may never explicitly load it, so during HTML output lwarp loads it last. If the user's document preamble uses cleveref options, or functions such as \crefname, then cleveref may be loaded in the user's preamble near the end, and lwarp's additional loading of cleveref will have no effect.

`\AtEndPreable` forces cleveref to be loaded last, if it has not yet been loaded by the user.

for HTML output:

```
\begin{warpHTML}

\AtEndPreamble{
    \RequirePackage{cleveref}
}

\end{warpHTML}
```

92 Preexisting label and reference definitions

Remember and patch some label-related defintions. These will be further encased and patched by other packages later.

`\label` and `\pageref` do NOT change their behavior according to print or HTML output, and thus do not use the `\LWR@formatted` system.

for HTML output:

```
\begin{warpHTML}

\LetLtxMacro\LWR@orig@label\label% includes memoir, before cleveref
\LetLtxMacro\label\LWR@new@label

\LetLtxMacro\LWR@orig@pageref\pageref
\LetLtxMacro\pageref\LWR@new@pageref

\end{warpHTML}
```

93 `picture` environment

Env `picture` The `picture` environment is enclosed inside a `\lateximage`.

for HTML output:

```
\begin{warpHTML}
```

Env `picture`

```
\BeforeBeginEnvironment{picture}{\begin{lateximage}[picture]}

\AfterEndEnvironment{picture}{\end{lateximage}}
```

```
\end{warpHTML}
```

94 Minipages and Boxes

A css flexbox is used for minipages and parboxes, allowing external and internal vertical positioning.

⚠ inline — A line of text with an inline `minipage` or `\parbox` will have the `minipage` or `\parbox` placed onto its own line, because a paragraph is a block element and cannot be made `inline-block`.

placement — `minipages` and `\parboxes` will be placed side-by-side in HTML unless you place a `\newline` between them.

side-by-side — Side-by-side `minipages` may be separated by `\quad`, `\qquad`, `\enskip`, `\hspace`, `\hfill`, or a `\rule`. When inside a `center` environment, the result is similar in print and HTML. Paragraph tags are suppressed between side-by-side `minipages` and these spacing commands, but not at the start or end of the paragraph.

⚠ minipage in a span — There is limited support for `minipages` inside an HTML . An HTML cannot appear inside a . While in a , `minipages`, and `\parboxes`, and any enclosed lists have limited HTML tags, resulting in an "inline" format, without markup except for HTML breaks. Use `\newline` or `\par` for an HTML break.

⚠ minipage size — When using `minipage`, `\parbox`, and `fminipage`, a virtual 6×9 inch text area is used for `\linewidth`, `\textwidth`, and `\textheight`, both for sizing the minipage, and also for its contents.

if width is `\linewidth` — If a `minipage` or `\parbox` is assigned a width of exactly `\linewidth`, in HTML it is automatically given no HTML width, thus allowed to fill the line as needed, similar to how it appears in print output.

full-width if HTML — A new macro `\minipagefullwidth` requests that, during HTML output, the next single `minipage` or `\parbox` be generated without an HTML `width` attribute, allowing it to be the full width of the display rather than the declared print-output width. This may be useful where the printed version's width makes no sense in HTML.

⚠ `tabular`, `multicols`

`\UseMinipageWidths`
`\IgnoreMinipageWidths` — Inside a `tabular` or `multicols` environment, where the width depends on the browser window, `\minipagefullwidth` is effectively used by default for every `minipage` or `\parbox` inside the environment. `\UseMinipageWidths` may be used to tell lwarp to honor the specified widths of all following `minipages` and `\parboxes` until the end of the local scope, and `\IgnoreMinipageWidths` may be used to tell lwarp to ignore the specified widths.

⚠ multicol — Inside a `multicols`, `\linewidth` is divided by the specified number of columns.

⚠ text alignment — Nested `minipages` adopt their parent's text alignment in HTML, whereas in regular LaTeX PDF output they do not. Use a `flushleft` or similar environment in the child `minipage` to force a text alignment.

for HTML output:
```
\begin{warpHTML}
```

94.1 Computed lengths

Len `\LWR@minipagewidth` — Used to convert the width into printable units.

```
\newlength{\LWR@minipagewidth}
```

Len `\LWR@minipageheight` — Used to convert the height into printable units.

```
\newlength{\LWR@minipageheight}
```

94.2 Virtual page size

Ctr LWR@virtualpagedepth Used to only reset the line width at the outermost minipage.

```
\newcounter{LWR@virtualpagedepth}
\setcounter{LWR@virtualpagedepth}{0}
```

Env LWR@setvirtualpage * [⟨*columns*⟩]

If not nesting a minipage, adjust \linewidth, \textwidth, and \textheight for a virtual 6×9 page, and start on a new PDF page to help prevent page overflows.

If starred, force a new page in the PDF before generating more HTML. This may be done to reduce the chance of page overflow when starting a new minipage.

The optional number of columns defaults to 1.

```
\NewDocumentEnvironment{LWR@setvirtualpage}{s O{1}}{%
    \ifnumequal{\value{LWR@virtualpagedepth}}{0}{%
        \IfBooleanT{#1}{\LWR@maybe@orignewpage}%
        \setlength{\linewidth}{6in/#2}%
        \setlength{\textwidth}{6in}%
        \setlength{\textheight}{9in}%
    }{}%
    \addtocounter{LWR@virtualpagedepth}{1}%
}
{\addtocounter{LWR@virtualpagedepth}{-1}}
```

94.3 Footnote handling

Also see section 60 for other forms of footnotes. Minipage footnotes are gathered in section 60.5, and then placed into the document in section 94.4.

94.4 Minipage handling

Bool LWR@minipagefullwidth Should the next minipage have no HTML width?

```
\newbool{LWR@minipagefullwidth}
\boolfalse{LWR@minipagefullwidth}
```

Bool LWR@forceminipagefullwidth Should the next minipage have no HTML width? Used to force full width for all minipages in an environment such as tabular or multicols, where the actual width depends on the browser width. Controlled by \useminipagewidths and \ignoreminipagewidths.

```
\newbool{LWR@forceminipagefullwidth}
\boolfalse{LWR@forceminipagefullwidth}
```

\minipagefullwidth Requests that the next minipage have no width tag in HTML:

for HTML output:

```
\newcommand*{\minipagefullwidth}{\global\booltrue{LWR@minipagefullwidth}}
```

\UseMinipageWidths Locally requests that minipage widths be honored.

```
\newcommand*{\UseMinipageWidths}{\boolfalse{LWR@forceminipagefullwidth}}
```

\IgnoreMinipageWidths Locally requests that minipage widths be ignored.

```
\newcommand*{\IgnoreMinipageWidths}{\booltrue{LWR@forceminipagefullwidth}}
\end{warpHTML}
```

for PRINT output:

```
\begin{warpprint}
\newcommand*{\minipagefullwidth}{}
\newcommand*{\UseMinipageWidths}{}
\newcommand*{\IgnoreMinipageWidths}{}
\end{warpprint}
```

for HTML output:

```
\begin{warpHTML}
```

Bool LWR@minipagethispar Has a minipage been seen this paragraph? If true, prevents paragraph tags around horizontal space between minipages.

```
\newbool{LWR@minipagethispar}
\boolfalse{LWR@minipagethispar}
```

Env minipage [⟨*vert position*⟩] [⟨*height*⟩] [⟨*inner vert position*⟩] {⟨*width*⟩}

The vertical positions may be 'c', 't', or 'b'. The inner position may also be 's'.

When using \linewidth, \textwidth, or \textheight, these are scaled proportionally to a 6×9 inch text area.

```
\NewDocumentEnvironment{LWR@HTML@sub@minipage}{m m m m}
{%
\LWR@traceinfo{minipage}%
```

Start an environment, in which width and height is computed based on a virtual page size instead of the extra-large PDF page used during HTML tag generation.

```
\begin{LWR@setvirtualpage}*%
```

Save the requested width now that \linewidth, etc. are adjusted to virtual size.

```
\setlength{\LWR@minipagewidth}{#4}%
\ifnumequal{\value{LWR@virtualpagedepth}}{1}{%
    \addtolength{\LWR@minipagewidth}{3em}% room for frames
}{}%
\LWR@traceinfo{computed width is \LWR@printlength{\LWR@minipagewidth}}%
```

Compute height:

```
\setlength{\LWR@minipageheight}{\textheight}% default unless specified
\ifblank{#2}{}{\setlength{\LWR@minipageheight}{#2}}%
```

LaTeX wants to start a paragraph for the virtual minipage, then start a paragraph again for the contents of the minipage, so cancel the paragraph tag handling until the minipage has begun.

```
\ifbool{FormatWP}{\newline}{}%
\LWR@stoppars%
```

If `FormatWP`, add a text frame:

```
\ifbool{FormatWP}{%

\addtocounter{LWR@thisautoidWP}{1}%
\LWR@htmltag{%
    div id=\textquotedbl%
        \LWR@print@mbox{autoidWP-\arabic{LWR@thisautoidWP}}%
    \textquotedbl\ % space
    class=\textquotedbl{}wpminipage\textquotedbl%
}%

}{}%
```

Create the tag with optional alignment style:

```
\LWR@traceinfo{minipage: creating div class}%
\LWR@htmltag{div class=\textquotedbl{}minipage\textquotedbl\ style=\textquotedbl%
\ifthenelse{\equal{#1}{t}}{\LWR@print@mbox{vertical-align:bottom} ; }{}%
\ifthenelse{\equal{#1}{c}}{\LWR@print@mbox{vertical-align:middle} ; }{}%
\ifthenelse{\equal{#1}{b}}{\LWR@print@mbox{vertical-align:top} ; }{}%
\ifthenelse{\equal{#3}{t}}{\LWR@print@mbox{justify-content:flex-start} ; }{}%
\ifthenelse{\equal{#3}{c}}{\LWR@print@mbox{justify-content:center} ; }{}%
\ifthenelse{\equal{#3}{b}}{\LWR@print@mbox{justify-content:flex-end} ; }{}%
\ifthenelse{\equal{#3}{s}}{\LWR@print@mbox{justify-content:space-between} ; }{}%
```

Print the width and optional height styles:

```
\LWR@traceinfo{minipage: about to print the width of \LWR@printlength{\LWR@minipagewidth}}%
\ifbool{LWR@minipagefullwidth}%
{\global\boolfalse{LWR@minipagefullwidth}}%
{%
    \ifbool{LWR@forceminipagefullwidth}%
        {}%
        {%
            \ifdimequal{#4}{\linewidth}%
                {}%
                {width:\LWR@printlength{\LWR@minipagewidth} ; }%
        }%
}%
\LWR@traceinfo{minipage: about to print the height}%
\ifblank{#2}{}{height:\LWR@printlength{\LWR@minipageheight} ; }%
\textquotedbl%
}%
```

Finish with an empty line to start the contents on a new line.

```

```

```
% The preceding empty line is required.
```

Set the user-accessible line and text width and height values inside the virtual minipage. These do not affect the actual size of the PDF output, but are used by any reference to `\linewidth`, etc. inside the virtual minipage being created here. `\LWR@minipagewidth` was the original then padded by 3em, which is restored here. This is done instead of settings back to #4, in case #4 was `\linewidth`, which was changed to 6in above.

```
\ifnumequal{\value{LWR@virtualpagedepth}}{1}{%
    \addtolength{\LWR@minipagewidth}{-3em}% undo frame padding
}{}%
\setlength{\linewidth}{\LWR@minipagewidth}%
```

`\raggedright` cancels hyphenation, which will be done by HTML instead.

```
\LWR@print@raggedright%
```

```
    \LWR@newautopagelabel{page}%
```

Set minipage footnotes:

```
\def\@mpfn{mpfootnote}%
\def\thempfn{\thempfootnote}\c@mpfootnote\z@%
\let\@footnotetext\@mpfootnotetext%
```

Resume paragraph tag handling for the contents of the minipage:

```
\LWR@startpars%
\ifboolexpr{bool{FormatWP} and bool{WPMarkMinipages}}{%

=== begin minipage ===

}{}%
\LWR@traceinfo{minipage: finished starting the minipage}%
}% finished \minipage
{% \endminipage
```

Print pending minipage footnotes:

```
\LWR@printpendingmpfootnotes%
```

End the environment with closing tag:

```
\ifboolexpr{bool{FormatWP} and bool{WPMarkMinipages}}{%

=== end minipage ===

}{}%
\LWR@stoppars%

\ifbool{FormatWP}{%

\LWR@htmlelementend{div}%

```

```
}{}%
\LWR@htmldivclassend{minipage}%

\end{LWR@setvirtualpage}%
\LWR@startpars%
\ifbool{FormatWP}{\newline}{}%
```

Prevent paragraph tags around horizontal white space until the start of the next paragraph:

```
\global\booltrue{LWR@minipagethispar}%
\LWR@traceinfo{LWR@minipage: done}%
}

\NewDocumentEnvironment{LWR@HTML@minipage}{O{t} O{} O{t} m}
    {\LWR@HTML@sub@minipage{#1}{#2}{#3}{#4}}
    {\endLWR@HTML@sub@minipage}

\LWR@formattedenv{minipage}
```

94.5 \parbox, \mbox, \makebox, \framebox, \fbox, \raisebox

for HTML output:

\parbox [⟨*pos*⟩] [⟨*height*⟩] [⟨*inner-pos*⟩] {⟨*width*⟩} {⟨*text*⟩}

A parbox uses the minipage code:

```
\NewDocumentCommand{\LWR@HTML@parbox}{O{t} O{} O{t} m +m}
{
\LWR@traceinfo{parbox of width #4}%
\begin{minipage}[#1][#2][#3]{#4}%
#5
\end{minipage}%
}

\LWR@formatted{parbox}
```

\mbox {⟨*text*⟩} Nullified for HTML.

```
\newcommand*{\LWR@HTML@mbox}[1]{{#1}}

\LWR@formatted{mbox}
```

\LWR@@makebox@paren {⟨*width*⟩} , {⟨*height*⟩}

Adds to the style in \LWR@temptwo.

```
\NewDocumentCommand{\LWR@@makebox@paren}{m m}{%
\IfValueTF{#2}{%
    \setlength{\LWR@tempwidth}{#1\unitlength}%
    \setlength{\LWR@tempheight}{#2\unitlength}%
    \appto{\LWR@temptwo}{%
        \LWR@print@mbox{width:\LWR@printlength{\LWR@tempwidth}} ; % space
```

```
        \LWR@print@mbox{height:\LWR@printlength{\LWR@tempheight}} ; % space
    }%
}{%
    \PackageError{lwarp}%
        {(width,height) is missing a comma ',' character}%
        {\protect\makebox\space and \protect\framebox\space accept
            a size in the format (width,height).}%
}%
}
```

`\LWR@@makebox@align` {⟨*alignment character*⟩}

Adds to the style in `\LWR@temptwo`.

```
\newcommand*{\LWR@@makebox@align}[1]{%
    \def\LWR@align{center}%
    \ifstrequal{#1}{l}{\def\LWR@align{left}}{}%
    \ifstrequal{#1}{r}{\def\LWR@align{right}}{}%
    \ifstrequal{#1}{s}{\def\LWR@align{justify}}{}%
    \appto{\LWR@temptwo}{%
        \LWR@print@mbox{text-align:\LWR@align} ; %
    }%
}
```

`\makebox` (⟨*width,height*⟩) [⟨*width*⟩] [⟨*pos*⟩] {⟨*text*⟩}

```
\NewDocumentCommand{\LWR@HTML@makebox}{>{\SplitArgument{1}{,}}d() o o +m}{%
```

Build the style depending on arguments:

```
    \begin{LWR@setvirtualpage}%
        \def\LWR@temptwo{}%
        \IfValueTF{#1}%
        {% (width,height) ..
            \LWR@@makebox@paren #1%
            \IfValueT{#2}%
            {% (width,height) [posn]
                \LWR@@makebox@align{#2}%
            }%
        }%
        {% [width]
            \IfValueT{#2}% [width]
            {%
                \setlength{\LWR@tempwidth}{#2}%
                \ifdimgreater{\LWR@tempwidth}{0pt}{%
                    \appto{\LWR@temptwo}{%
                        width:\LWR@printlength{\LWR@tempwidth} ; % space
                    }%
                }{}%
            }%
        }%
        \IfValueT{#3}%
        {% [width] [posn]
            \LWR@@makebox@align{#3}%
```

```
        }%
        \InlineClass[%
            \LWR@print@mbox{display:inline-block} ; %
            \LWR@temptwo%
        ]%
        {makebox}%
        {#4}%
    \end{LWR@setvirtualpage}%
}
\LWR@formatted{makebox}
```

`\framebox` `(`⟨*width,height*⟩`)` `[`⟨*width*⟩`]` `[`⟨*pos*⟩`]` `{`⟨*text*⟩`}`

```
\NewDocumentCommand{\LWR@HTML@framebox}{d() o o +m}{%
    \fbox{\makebox(#1)[#2][#3]{#4}}%
}

\LWR@formatted{framebox}
```

`\LWR@forceminwidth` `{`⟨*legth*⟩`}`

Sets `\LWR@atleastonept` to be at least 1pt.

```
\newlength{\LWR@atleastonept}

\newcommand*{\LWR@forceminwidth}[1]{%
\setlength{\LWR@atleastonept}{#1}%
\ifthenelse{%
    \lengthtest{\LWR@atleastonept>0pt}\AND%
    \lengthtest{\LWR@atleastonept<1pt}%
}%
    {\setlength{\LWR@atleastonept}{1pt}}%
    {}%
}
```

`\LWR@fboxstyle` Prints the HTML attributes for a black border and padding.

`\LWR@forceminwidth` must be used first in order to set the border width.

```
\newcommand*{\LWR@fboxstyle}{%
\LWR@findcurrenttextcolor%
\LWR@traceinfo{LWR@fboxstyle B}%
border:\LWR@printlength{\LWR@atleastonept} solid \LWR@origpound\LWR@tempcolor ; %
padding:\LWR@printlength{\fboxsep} ; %
color:\LWR@origpound\LWR@tempcolor%
}
```

`\fbox` `{`⟨*text*⟩`}`

Creates a framed inline span enclosing the text.

Create a new HTML version, but don't use it until after xcolor may have loaded:

```
\newcommand{\LWR@HTML@fbox}[1]{%
\LWR@traceinfo{HTML fbox}%
\LWR@forceminwidth{\fboxrule}%
\LWR@traceinfo{HTML fbox B}%
\InlineClass[%
    \LWR@print@mbox{display:inline-block} ; %
    \LWR@fboxstyle%
]{fbox}{#1}%
\LWR@traceinfo{HTML fbox: done}%
}
```

xcolor `\lets` things to `\fbox` when it is loaded, and this must remain even for HTML output while in a `lateximage`, so `\fbox` is not modified until `\AtBeginDocument`:

```
\AtBeginDocument{\LWR@formatted{fbox}}
```

`\fboxBlock` {⟨*text*⟩} Creates a framed HTML `<div>` of the text.

First, a print-mode version. This is newly defined for print mode, so it is defined inside `warpall`.

for HTML & PRINT:

```
\end{warpHTML}
\begin{warpall}
\let\fboxBlock\fbox
\end{warpall}

\begin{warpHTML}
```

for HTML output: Next, an HTML version:

```
\newcommand{\LWR@HTML@fboxBlock}[1]{%
\LWR@forceminwidth{\fboxrule}%
\LWR@stoppars%
\begin{BlockClass}[%
\LWR@fboxstyle%
]{fboxBlock}
#1
\end{BlockClass}
\LWR@startpars%
}

\LWR@formatted{fboxBlock}

\end{warpHTML}
```

Env `fminipage` [⟨*align*⟩] [⟨*height*⟩] [⟨*align*⟩] {⟨*width*⟩}

Creates a framed HTML `<div>` around its contents.

for HTML & PRINT: Print version:

```
\begin{warpall}

\newsavebox{\LWR@fminipagebox}

```

```
\NewDocumentEnvironment{LWR@print@fminipage}{O{t} o O{t} m}
{%
```

An outer minipage will be used for vertical alignment. An inner minipage will be framed with \fbox.

If the optional inner alignment is not given, use the outer instead:

```
\IfValueTF{#3}%
{\def\LWR@thisalign{#3}}
{\def\LWR@thisalign{#1}}%
```

Form the outer minipage depending on whether a height was given. Make the outer minipage larger to compensate for the frame.

```
\IfValueTF{#2}%
{\minipage[#1][#2+2\fboxsep+2\fboxrule][\LWR@thisalign]{#4+2\fboxsep+2\fboxrule}}%
{\minipage[#1]{#4+2\fboxsep+2\fboxrule}}%
```

Capture the contents of the environment:

```
\begin{lrbox}{\LWR@fminipagebox}%
```

Nest the contents inside an inner minipage of the desired size:

```
\IfValueTF{#2}%
{\minipage[#1][#2][\LWR@thisalign]{#4}}%
{\minipage[#1]{#4}}%
}
{%
```

Close the inner minipage and the LR box with the contents:

```
\endminipage%
\end{lrbox}%
```

Create a frame around the contents of the environment:

```
\fbox{\usebox{\LWR@fminipagebox}}%
```

The entire thing is placed inside the outer minipage:

```
\endminipage%
}

\LetLtxMacro\fminipage\LWR@print@fminipage
\LetLtxMacro\endfminipage\endLWR@print@fminipage
% \newenvironment{fminipage}{\LWR@print@fminipage}{\endLWR@print@fminipage}

\end{warpall}
```

HTML version:

for HTML output:

```
\begin{warpHTML}
```

```
12855
12856 \NewDocumentEnvironment{LWR@HTML@fminipage}{O{t} o O{t} m}
12857 {%
12858 \LWR@traceinfo{fminipage #1 #2 #3 #4}%
```

Locally change to the virtual page size before processing the requested sizes:

```
12859 \begin{LWR@setvirtualpage}*%
12860 \setlength{\LWR@tempwidth}{#4}%
12861 \IfValueT{#2}{\setlength{\LWR@tempheight}{#2}}%
```

Use a rule of at least one pixel in width:

```
12862 \LWR@forceminwidth{\fboxrule}%


12863 \LWR@stoppars%


12864 \begin{BlockClass}[%
12865 \LWR@fboxstyle ; %
12866 \IfValueT{#2}{height:\LWR@printlength{\LWR@tempheight} ; }%
12867 \ifbool{LWR@minipagefullwidth}%
12868 {\global\boolfalse{LWR@minipagefullwidth}}%
12869 {%
12870     \ifbool{LWR@forceminipagefullwidth}%
12871         {}%
12872         {%
12873             \ifdimequal{\LWR@tempwidth}{\linewidth}%
12874                 {}%
12875                 {width:\LWR@printlength{\LWR@tempwidth} ; }%
12876         }%
12877 }%
12878 ]{fminipage}%
12879 }
12880 {%
12881 \end{BlockClass}%
12882 \end{LWR@setvirtualpage}%
```

Prevent paragraph tags around horizontal white space until the start of the next paragraph:

```
12883 \global\booltrue{LWR@minipagethispar}%
12884 \LWR@traceinfo{fminipage done}%
12885 }
12886
12887 \LWR@formattedenv{fminipage}
```

`\raisebox` {⟨*raiselen*⟩} [⟨*height*⟩] [⟨*depth*⟩] {⟨*text*⟩}

```
12888 \NewDocumentCommand{\LWR@HTML@raisebox}{m o o m}{%
12889 #4%
12890 }
12891
12892 \LWR@formatted{raisebox}
```

```
\end{warpHTML}
```

95 Direct formatting

⚠ \bfseries, etc. \textbf, etc. are supported, but \bfseries, etc. work only in some situations.

⚠ HTML special chars &, <, and > have special meanings in HTML. If \&, \textless, and \textgreater are used, proper HTML entities will be used, but there may be HTML parsing problems if these special characters occur unescaped in program listings or other verbatim text.

program listings For program listings, the listings package is supported, and its literate option is used to convert &, <, and > to proper HTML entities.

verbatim The various verbatim-related environments do not convert &, <, and >, so care must be taken to avoid accidentally including valid HTML code inside these environments. Adding a space on either side may be sufficient.

For high-level block and inline custom CSS classes, see section 52.10.

for HTML & PRINT:

```
\begin{warpall}
```

Bool FixSmallCaps User may set FixSmallCaps to true if small caps are being incorrectly rendered as all caps.

```
\newbool{FixSmallCaps}
\boolfalse{FixSmallCaps}
```

```
\end{warpall}
```

for HTML output:

```
\begin{warpHTML}
```

\emph {⟨*text*⟩}

```
\DeclareRobustCommand{\LWR@HTML@emph}[1]{%
    {%
        \LWR@HTML@itshape%
        \LWR@htmlspan{em}{#1}%
    }%
}

\LWR@formatted{emph}
```

\textmd {⟨*text*⟩}

```
\DeclareRobustCommand{\LWR@HTML@textmd}[1]{%
    {%
        \LWR@HTML@mdseries%
        \InlineClass(font-weight:normal){textmd}{#1}%
    }%
}

\LWR@formatted{textmd}
```

\textbf {⟨*text*⟩}

```
\DeclareRobustCommand{\LWR@HTML@textbf}[1]{%
    {%
        \LWR@HTML@bfseries%
        \LWR@htmlspan{b}{#1}%
    }%
}

\LWR@formatted{textbf}
```

\texteb {⟨*text*⟩} From nfssext-cfr.

```
\DeclareRobustCommand{\LWR@HTML@texteb}[1]{%
    {%
        \LWR@HTML@ebweight%
        \InlineClass{texteb}{#1}%
    }%
}

\LWR@formatted{texteb}
```

\textlg {⟨*text*⟩} From nfssext-cfr.

```
\DeclareRobustCommand{\LWR@HTML@textlg}[1]{%
    {%
        \LWR@HTML@lgweight%
        \InlineClass{textlg}{#1}%
    }%
}

\LWR@formatted{textlg}
```

\textrm {⟨*text*⟩}

```
\DeclareRobustCommand{\LWR@HTML@textrm}[1]{%
    {%
        \LWR@HTML@rmfamily%
        \InlineClass(font-family:serif){textrm}{#1}%
    }%
}

\LWR@formatted{textrm}
```

\textsf {⟨*text*⟩}

```
\DeclareRobustCommand{\LWR@HTML@textsf}[1]{%
    {%
        \LWR@HTML@sffamily%
        \InlineClass(font-family:sans){textsf}{#1}%
    }%
}

\LWR@formatted{textsf}
```

\texttt {⟨*text*⟩}

```
\DeclareRobustCommand{\LWR@HTML@texttt}[1]{%
    {%
        \LWR@HTML@ttfamily%
        \LWR@htmlspan{kbd}{#1}%
    }%
}

\LWR@formatted{texttt}
```

\textup {⟨*text*⟩}

```
\DeclareRobustCommand{\LWR@HTML@textup}[1]{%
    {%
        \LWR@HTML@upshape%
        \InlineClass(font-style:normal){textup}{#1}%
    }%
}

\LWR@formatted{textup}
```

\textit {⟨*text*⟩}

```
\DeclareRobustCommand{\LWR@HTML@textit}[1]{%
    {%
        \LWR@HTML@itshape%
        \LWR@htmlspan{i}{#1}%
    }%
}

\LWR@formatted{textit}
```

\textsc {⟨*text*⟩}

```
\DeclareRobustCommand{\LWR@HTML@textsc}[1]{%
    {%
        \LWR@HTML@scshape%
        \InlineClass{textsc}{#1}%
    }%
}

\LWR@formatted{textsc}
```

\textulc {⟨*text*⟩} From fontaxes.

```
\DeclareRobustCommand{\LWR@HTML@textulc}[1]{%
    {%
        \LWR@HTML@ulcshape%
        \InlineClass{textulc}{#1}%
    }%
}

\LWR@formatted{textulc}
```

\textsi {⟨*text*⟩}

```
\@ifundefined{textsi}{
    \LetLtxMacro\LWR@print@textsi\LWR@print@textsc
}{}

\DeclareRobustCommand{\LWR@HTML@textsi}[1]{%
    {%
        \LWR@HTML@sishape%
        \textsc{\textit{#1}}%
%         \InlineClass(
%             font-style: italic;
%             font-variant: small-caps ;
%             font-variant-numeric: oldstyle-nums ;
%         ){textsi}{#1}%
    }%
}

\LWR@formatted{textsi}
```

\textsl {⟨*text*⟩}

```
\DeclareRobustCommand{\LWR@HTML@textsl}[1]{%
    {%
        \slshape%
        \InlineClass(font-style:oblique){textsl}{#1}%
    }%
}

\LWR@formatted{textsl}
```

\textssc {⟨*text*⟩}

```
\newrobustcmd{\LWR@HTML@textssc}[1]{\textsc{#1}}
\LWR@formatted{textssc}
```

\textnormal {⟨*text*⟩}

```
\DeclareRobustCommand{\LWR@HTML@textnormal}[1]{\textmd{\textrm{\textup{#1}}}}

\LWR@formatted{textnormal}

\FilenameNullify{%
    \LetLtxMacro\emph\@firstofone%
    \LetLtxMacro\textmd\@firstofone%
    \LetLtxMacro\textbf\@firstofone%
    \LetLtxMacro\texteb\@firstofone%
    \LetLtxMacro\textlg\@firstofone%
    \LetLtxMacro\textrm\@firstofone%
    \LetLtxMacro\textsf\@firstofone%
    \LetLtxMacro\texttt\@firstofone%
    \LetLtxMacro\textup\@firstofone%
    \LetLtxMacro\textit\@firstofone%
```

```
    \LetLtxMacro\textsc\@firstofone%
    \LetLtxMacro\textulc\@firstofone%
    \LetLtxMacro\textsi\@firstofone%
    \LetLtxMacro\textsl\@firstofone%
    \LetLtxMacro\textssc\@firstofone%
    \LetLtxMacro\textnormal\@firstofone%
}
```

Remembers the current font family, series, and shape. fontaxes support is integrated here.

```
\newcommand*{\LWR@f@family}{rm}
\newcommand*{\LWR@f@series}{md}
\newcommand*{\LWR@f@shape}{up}
\newcommand*{\LWR@f@shapecaps}{ulc}
```

`\LWR@textcurrentfont` {⟨*text*⟩}

Prints the text with the current font choices. Avoids nesting repeated font selections.

```
\newcounter{LWR@textcurrentfontdepth}
\setcounter{LWR@textcurrentfontdepth}{0}

\newcommand*{\LWR@textcurrentfont}[1]{%
    \ifnumcomp{\value{LWR@textcurrentfontdepth}}{>}{0}%
        {%
            \addtocounter{LWR@textcurrentfontdepth}{1}%
            #1%
            \addtocounter{LWR@textcurrentfontdepth}{-1}%
        }%
        {%
            \addtocounter{LWR@textcurrentfontdepth}{1}%
            \InlineClass{%
                    text\LWR@f@family\LWR@origtilde{}%
                    text\LWR@f@series\LWR@origtilde{}%
                    text\LWR@f@shape\LWR@origtilde{}%
                    text\LWR@f@shapecaps%
                }%
                {#1}%
            \addtocounter{LWR@textcurrentfontdepth}{-1}%
        }%
}
```

Env `LWR@blocktextcurrentfont` Prints the contents with the current font choices.

```
\newenvironment*{LWR@blocktextcurrentfont}{%
\LWR@stoppars%
\BlockClass{%
        text\LWR@f@family\LWR@origtilde{}%
        text\LWR@f@series\LWR@origtilde{}%
        text\LWR@f@shape\LWR@origtilde{}%
        text\LWR@f@shapecaps%
    }%
}{\endBlockClass\LWR@startpars}
```

\mdseries

```
\newrobustcmd*{\LWR@HTML@mdseries}{%
    \LWR@print@mdseries%
    \renewcommand*{\LWR@f@series}{md}%
}
\LWR@formatted{mdseries}
```

\bfseries

```
\newrobustcmd*{\LWR@HTML@bfseries}{%
    \LWR@print@bfseries%
    \renewcommand*{\LWR@f@series}{bf}%
}
\LWR@formatted{bfseries}
```

\ebweight From nfssext-cfr.

```
\newrobustcmd*{\LWR@HTML@ebweight}{%
    \LWR@print@ebweight%
    \renewcommand*{\LWR@f@series}{eb}%
}
\LWR@formatted{ebweight}
```

\lgweight From nfssext-cfr.

```
\newrobustcmd*{\LWR@HTML@lgweight}{%
    \LWR@print@lgweight%
    \renewcommand*{\LWR@f@series}{lg}%
}
\LWR@formatted{lgweight}
```

\rmfamily

```
\newrobustcmd*{\LWR@HTML@rmfamily}{%
    \LWR@print@rmfamily%
    \renewcommand*{\LWR@f@family}{rm}%
}
\LWR@formatted{rmfamily}
```

\sffamily

```
\newrobustcmd*{\LWR@HTML@sffamily}{%
    \LWR@print@sffamily%
    \renewcommand*{\LWR@f@family}{sf}%
}
\LWR@formatted{sffamily}
```

\ttfamily

```
\newrobustcmd*{\LWR@HTML@ttfamily}{%
```

```
    \LWR@print@ttfamily%
    \renewcommand*{\LWR@f@family}{tt}%
}
\LWR@formatted{ttfamily}
```

The following use `\AtBeginDocument` due to the LaTeX core `\reinstall@nfss@defs`, which redefines these `\AtBeginDocument`. See **texdoc source2e**.

\upshape

```
\newrobustcmd*{\LWR@HTML@upshape}{%
    \LWR@print@upshape%
    \renewcommand*{\LWR@f@shape}{up}%
}
\AtBeginDocument{\LWR@formatted{upshape}}
```

\itshape

```
\newrobustcmd*{\LWR@HTML@itshape}{%
    \LWR@print@itshape%
    \renewcommand*{\LWR@f@shape}{it}%
}
\AtBeginDocument{\LWR@formatted{itshape}}
```

\scshape Note: `\LWR@print@scshape` is not used here since some fonts, such as erewhon, copy/paste as all-caps.

```
\newrobustcmd*{\LWR@HTML@scshape}{%
    \ifbool{FixSmallCaps}{}{%
        \LWR@print@scshape%
    }%
    \renewcommand*{\LWR@f@shapecaps}{sc}%
}
\AtBeginDocument{\LWR@formatted{scshape}}
```

\ulcshape From fontaxes.

```
\@ifundefined{ulcshape}{
    \LetLtxMacro\ulcshape\upshape
}{}
\newrobustcmd*{\LWR@HTML@ulcshape}{%
    \LWR@print@ulcshape%
    \renewcommand*{\LWR@f@shapecaps}{ulc}%
}
\AtBeginDocument{\LWR@formatted{ulcshape}}
```

\sishape

```
\@ifundefined{sishape}{
    \LetLtxMacro\sishape\scshape
}{}
```

```
\newrobustcmd*{\LWR@HTML@sishape}{%
    \ifbool{FixSmallCaps}{}{%
        \LWR@print@sishape%
    }%
    \renewcommand*{\LWR@f@shape}{it}
    \renewcommand*{\LWR@f@shapecaps}{sc}%
}
\AtBeginDocument{\LWR@formatted{sishape}}
```

\slshape

```
\newrobustcmd*{\LWR@HTML@slshape}{%
    \LWR@print@slshape%
    \renewcommand*{\LWR@f@shape}{sl}%
}
\AtBeginDocument{\LWR@formatted{slshape}}
```

\sscshape

```
\newrobustcmd{\LWR@HTML@sscshape}{\LWR@HTML@scshape}
\AtBeginDocument{\LWR@formatted{sscshape}}
```

\normalfont

```
\newrobustcmd*{\LWR@HTML@normalfont}{\rmfamily\mdseries\upshape\ulcshape}
\LWR@formatted{normalfont}

\FilenameNullify{%
    \LetLtxMacro\rmfamily\@empty%
    \LetLtxMacro\sffamily\@empty%
    \LetLtxMacro\ttfamily\@empty%
    \LetLtxMacro\bfseries\@empty%
    \LetLtxMacro\ebweight\@empty%
    \LetLtxMacro\lgweight\@empty%
    \LetLtxMacro\mdseries\@empty%
    \LetLtxMacro\upshape\@empty%
    \LetLtxMacro\slshape\@empty%
    \LetLtxMacro\sishape\@empty%
    \LetLtxMacro\scshape\@empty%
    \LetLtxMacro\itshape\@empty%
    \LetLtxMacro\ulcshape\@empty%
    \LetLtxMacro\sscshape\@empty%
    \LetLtxMacro\normalfont\@empty%
}
```

\sp {⟨*text*⟩}

For siunitx. Must work in math mode.

```
\renewcommand{\sp}[1]{\text{<sup>#1</sup>}{}}
```

\sb {⟨*text*⟩}

For siunitx. Must work in math mode.

```
\renewcommand{\sb}[1]{\text{<sub>#1</sub>}{}}
```

`\textsuperscript` {⟨*text*⟩}

```
\newrobustcmd{\LWR@HTML@textsuperscript}[1]{\LWR@htmlspan{sup}{#1}}
\LWR@formatted{textsuperscript}
```

`\@textsuperscript` {⟨*text*⟩}

```
\newcommand{\LWR@HTML@@textsuperscript}[1]{\LWR@htmlspan{sup}{#1}}
\LWR@formatted{@textsuperscript}
```

`\textsubscript` {⟨*text*⟩}

```
    \newrobustcmd{\LWR@HTML@textsubscript}[1]{\LWR@htmlspan{sub}{#1}}
    \LWR@formatted{textsubscript}
```

`\@textsubscript` {⟨*text*⟩}

```
    \newcommand{\LWR@HTML@@textsubscript}[1]{\LWR@htmlspan{sub}{#1}}
    \LWR@formatted{@textsubscript}
```

`\up` {⟨*text*⟩} Prints superscript.

This is `\let` at the beginning of the document in case some other package has changed the definition.

```
\AtBeginDocument{\let\up\textsuperscript}
```

`\fup` {⟨*text*⟩} Prints superscript.

Supports fmtcount package.

This is `\let` at the beginning of the document in case some other package has changed the definition.

```
\AtBeginDocument{\let\fup\textsuperscript}
```

`\underline` {⟨*text*⟩}

```
\renewcommand{\underline}[1]{%
    \InlineClass%
        (text-decoration:underline; text-decoration-skip: auto)%
        {underline}{#1}%
}
```

`\LWR@overline` {⟨*text*⟩}

```
\newcommand{\LWR@overline}[1]{%
    \InlineClass%
        (text-decoration:overline; text-decoration-skip: auto)%
        {overline}{#1}%
}
```

`\LWR@currenttextcolor` The color to use for text and `\rule`, defaulting to black:

```
\newcommand*{\LWR@currenttextcolor}{black}
```

`\LWR@tempcolor` `\LWR@tempcolortwo` The color converted to HTML colorspace.

```
\newcommand*{\LWR@tempcolor}{}
\newcommand*{\LWR@tempcolortwo}{}
```

`\LWR@findcurrenttextcolor` Sets `\LWR@tempcolor` to the current color.

```
\newcommand*{\LWR@findcurrenttextcolor}{%
    \renewcommand{\LWR@tempcolor}{000000}%
}
```

`\LWR@textcurrentcolor` {⟨*text*⟩} Like `\textcolor` but uses the current `\color` instead.

```
\NewDocumentCommand{\LWR@textcurrentcolor}{m}{%
    \renewcommand*{\LWR@currenttextcolor}{black}%
    #1%
}
```

```
\end{warpHTML}
```

for PRINT output:

```
\begin{warpprint}
```

`\LWR@textcurrentfont` {⟨*text*⟩}

Prints the text with the current font choices.

```
\newcommand*{\LWR@textcurrentfont}[1]{#1}
```

Env `LWR@blocktextcurrentfont` Prints the contents with the current font choices.

```
\newenvironment*{LWR@blocktextcurrentfont}{}{}
```

`\FilenameNullify` {⟨*macros to nullify*⟩}

```
\newcommand*{\FilenameNullify}[1]{}
```

```
\end{warpprint}
```

96 Skips, spaces, font sizes

for HTML output:

```
\begin{warpHTML}
```

`\,` and `\thinspace` may be redefined by other packages, so are redefined `\AtBeginDocument` here.

Direct-formatting space commands become HTML entities:

```
\AtBeginDocument{
\renewrobustcmd*{\,}{\HTMLunicode{202f}} % HTML thin non-breakable space
\renewrobustcmd*{\thinspace}{\HTMLunicode{202f}}   % HTML thin non-breakable space
\renewrobustcmd*{\negthinspace}{\HTMLunicode{202f}}   % HTML thin non-breakable space
\renewrobustcmd*{~}{\HTMLentity{nbsp}}
\renewrobustcmd*{\textellipsis}{\HTMLunicode{2026}}
\renewrobustcmd*{\vdots}{\HTMLunicode{22EE}}
}
```

Direct-formatting font sizes are remembered for future use:

```
\newcommand*{\LWR@font@size}{normalsize}

\newrobustcmd*{\LWR@HTML@normalsize}{\renewcommand*{\LWR@font@size}{normalsize}}
\LWR@formatted{normalsize}

\newrobustcmd*{\LWR@HTML@small}{\renewcommand*{\LWR@font@size}{small}}
\LWR@formatted{small}

\newrobustcmd*{\LWR@HTML@footnotesize}{\renewcommand*{\LWR@font@size}{footnotesize}}
\LWR@formatted{footnotesize}

\newrobustcmd*{\LWR@HTML@scriptsize}{\renewcommand*{\LWR@font@size}{scriptsize}}
\LWR@formatted{scriptsize}

\newrobustcmd*{\LWR@HTML@tiny}{\renewcommand*{\LWR@font@size}{tiny}}
\LWR@formatted{tiny}

\newrobustcmd*{\LWR@HTML@large}{\renewcommand*{\LWR@font@size}{large}}
\LWR@formatted{large}

\newrobustcmd*{\LWR@HTML@Large}{\renewcommand*{\LWR@font@size}{Large}}
\LWR@formatted{Large}

\newrobustcmd*{\LWR@HTML@LARGE}{\renewcommand*{\LWR@font@size}{LARGE}}
\LWR@formatted{LARGE}

\newrobustcmd*{\LWR@HTML@huge}{\renewcommand*{\LWR@font@size}{huge}}
\LWR@formatted{huge}

\newrobustcmd*{\LWR@HTML@Huge}{\renewcommand*{\LWR@font@size}{Huge}}
\LWR@formatted{Huge}


\DeclareDocumentCommand{\onecolumn}{}{}
```

```
13254
13255 \DeclareDocumentCommand{\twocolumn}{O{}}{
13256
13257 #1
13258
13259 }
```

\hfill

```
13260 \newcommand*{\LWR@HTML@hfill}{\qquad}
13261 \LWR@formatted{hfill}
```

\hrulefill

```
13262 \newcommand*{\LWR@HTML@hrulefill}{%
13263     \ifbool{LWR@doingapar}%
13264         {\rule{1in}{1pt}}%
13265         {%
13266             \LWR@findcurrenttextcolor%
13267             \ifdefstring{\LWR@tempcolor}{000000}%
13268             {%
13269                 \begin{BlockClass}{hrule}%
13270                 \end{BlockClass}%
13271             }%
13272             {%
13273                 \begin{BlockClass}[%
13274                     border-top: 1px solid \LWR@origpound\LWR@tempcolor % space
13275                 ]{hrule}%
13276                 \end{BlockClass}%
13277             }%
13278         }%
13279 }%
13280 \LWR@formatted{hrulefill}
```

\dotfill

```
13281 \newcommand*{\LWR@HTML@dotfill}{\dots}
13282 \LWR@formatted{dotfill}
```

\newpage

```
13283 \renewcommand*{\newpage}{
13284
13285 }
```

\newline Uses the HTML <br /> element.

```
13286 \newrobustcmd*{\LWR@newlinebr}{\unskip\LWR@htmltag{br /}\LWR@orignewline}%
13287 \LetLtxMacro\newline\LWR@newlinebr
```

\\ Redefined to \LWR@endofline or \LWR@tabularendofline.

\LWR@endofline * [⟨*len*⟩]

\\ is assigned to \LWR@endofline at \LWR@LwarpStart.

Inside tabular, \\ is temporarily changed to \LWR@tabularendofline.

```
\LetLtxMacro\LWR@origendofline\\
\NewDocumentCommand{\LWR@endofline}{s O{0pt}}
{%
\newline%

\setlength{\LWR@templengthone}{#2}%
\ifdimgreater{\LWR@templengthone}{0pt}{\newline}{}%
}
```

\LWR@minipagestartpars Minipages are often placed side-by-side inside figures, with a bit of horizontal space to separate them. Since HTML does not allow a to be inside a p, paragraphs must be turned off during the generation of the minipage, then turned on after the minipage is complete. When this occurs between side-by-side minipages, lwarp correctly suppresses the paragraph tags between the minipages, unless some other text is between the minipages. Such text forms its own paragraph, resulting in text after a minipage to be on its own line. Since people often place small horizontal space between minipages, it is desirable to maintain this space if possible. lwarp tries to do this by remembering that a minipage has been seen, in which case paragraph tags are suppressed around \hspace, \enskip, \quad, and \qquad until the end of the paragraph, when the closing p tag is created.

\hspace
\enskip
\quad
\qquad

When a minipage is seen, the boolean LWR@minipagethispar is set, telling the following horizontal whitespace commands to try to suppress their surrounding paragraph tags. LWR@minipagethispar is cleared at the next end of paragraph, when the HTML paragraph closing tag is generated.

Placed just before \hspace, \quad, or \qquad's HTML output.

```
\newcommand*{\LWR@minipagestartpars}{%
    \ifbool{LWR@minipagethispar}{\LWR@startpars}{}%
}
```

\LWR@minipagestoppars Placed just after \hspace, \quad, or \qquad's HTML output.

```
\newcommand*{\LWR@minipagestoppars}{%
    \ifbool{LWR@minipagethispar}{\LWR@stoppars}{}%
}
```

\quad Handles special minipage & horizontal space interactions. Uses 2003 EM SPACE to pass validation.

```
\renewrobustcmd*{\quad}{%
    \LWR@minipagestoppars%
    \HTMLunicode{2003}%
    \LWR@minipagestartpars%
}
```

\qquad Handles special minipage & horizontal space interactions.

```
\renewrobustcmd*{\qquad}{\quad\quad}
```

\enskip Handles special minipage & horizontal space interactions.

```
\renewrobustcmd*{\enskip}{%
    \LWR@minipagestoppars%
    \HTMLunicode{2002}%
    \LWR@minipagestartpars%
}
```

Len \LWR@tempwidth Used to compute span width, height, raise for \hspace and \rule:

Len \LWR@tempheight

Len \LWR@tempraise

```
\newlength{\LWR@tempwidth}
\newlength{\LWR@tempheight}
\newlength{\LWR@tempraise}
```

\LWR@select@html@hspace * {⟨*length*⟩} * {⟨*length*⟩}

\hspace

Handles special minipage & horizontal space interactions.

Prints a span of a given width. Ignores the optional star.

\hspace{\fill} is converted to \hspace{2em}, equal to \qquad.

```
\newcommand{\LWR@select@html@hspace}{%
\RenewDocumentCommand{\hspace}{s m}{%
\setlength{\LWR@tempwidth}{##2}%
```

If \fill, change to \qquad:

```
\ifnum\gluestretchorder\LWR@tempwidth>0%
\setlength{\LWR@tempwidth}{2em}%
\fi%
```

Only if the width is greater than zero:

```
\ifdimcomp{\LWR@tempwidth}{>}{0pt}{%
```

If had a minipage this paragraph, try to inline the white space without generating paragraph tags:

```
    \LWR@minipagestoppars%
```

Support the HTML thin wrappable space:

```
    \ifdimcomp{\LWR@tempwidth}{=}{.16667em}%
    {%
        \HTMLunicode{2009}% thin breakable space
    }%
```

Print the span with the converted width. Not rounded.

```
    {%
        \LWR@htmltagc{%
        span style=\textquotedbl{}width:\LWR@printlength{\LWR@tempwidth}; % extra space
                display:inline-block\textquotedbl%
        }%
```

If formatting for a word processor, approximate with a number of \quads, in case a span of a given width is not supported:

```
        \ifbool{FormatWP}{%
            \setlength{\LWR@templengthone}{\LWR@tempwidth}%
            \whiledo{\lengthtest{\LWR@templengthone>1em}}{%
                \quad%
                \addtolength{\LWR@templengthone}{-1em}%
            }%
        }%
```

If NOT formatting for a word processor, include an empty comment to avoid an empty span:

```
        {\LWR@htmlcomment{}}%
```

Close the span:

```
        \LWR@htmltagc{/span}%
    }%
```

If had a minipage this paragraph, try to inline the white space without generating paragraph tags:

```
    \LWR@minipagestartpars%
}{}% width greater than 0
}%
}
```

\LWR@select@html@nohspace * {⟨*length*⟩}
\hspace

Used to disable \hspace while creating description \items.

```
\newcommand{\LWR@select@html@nohspace}{%
    \RenewDocumentCommand{\hspace}{s m}{}%
}
```

\LWR@select@print@hspace

```
\newcommand*{\LWR@select@print@hspace}{%
    \renewrobustcmd\hspace{\@ifstar\@hspacer\@hspace}%
}
```

\hspace * {⟨*length*⟩}

Handles special minipage & horizontal space interactions.

```
\LWR@select@html@hspace
```

`\LWR@vspace` * {⟨*length*⟩} Nullified vspace.

```
\NewDocumentCommand{\LWR@HTML@vspace}{s m}{}

\LWR@formatted{vspace}
```

`\linebreak` [⟨*num*⟩] Inserts an HTML br tag.

```
\renewcommand*{\linebreak}[1][]{\newline}
```

`\nolinebreak` [⟨*num*⟩]

```
\renewcommand*{\nolinebreak}[1][]{}
```

`\pagebreak` [⟨*num*⟩] Starts a new paragraph.

```
\renewcommand*{\pagebreak}[1][]{

}
```

`\nopagebreak` [⟨*num*⟩]

```
\renewcommand*{\nopagebreak}[1][]{}
```

`\enlargethispage` * {⟨*len*⟩}

```
\RenewDocumentCommand{\enlargethispage}{s m}{}
```

`\clearpage`
`\cleardoublepage`

```
\renewcommand*{\clearpage}{}
\renewcommand*{\cleardoublepage}{}
```

`\rule` [⟨*raise*⟩] {⟨*width*⟩} {⟨*height*⟩}

Handles special minipage & horizontal space interactions.

Creates a span of a given width and height. Ignores the optional star.

`\fill` is zero-width, so `\hspace{\fill}` is ignored.

```
\newcommand*{\LWR@HTML@rule}[3][]{%
```

The width is copied into a temporary LaTeX length, from which comparisons and conversions may be made:

```
\setlength{\LWR@tempwidth}{#2}%
```

If it's zero-width then skip the entire rule:

```
\ifthenelse{\lengthtest{\LWR@tempwidth=0pt}}%
{}% zero- width
{% non-zero width
```

If it's non-zero width, set a minimal thickness so that it more reliably shows in the browser:

```
    \ifthenelse{%
        \lengthtest{\LWR@tempwidth>0pt}\AND%
        \lengthtest{\LWR@tempwidth<1pt}%
    }%
        {\setlength{\LWR@tempwidth}{1pt}}%
        {}%
```

Likewise with height:

```
    \setlength{\LWR@tempheight}{#3}%
    \ifthenelse{%
        \lengthtest{\LWR@tempheight>0pt}\AND%
        \lengthtest{\LWR@tempheight<1pt}%
    }%
        {\setlength{\LWR@tempheight}{1pt}}%
        {}%
```

If had a minipage this paragraph, try to inline the rule without generating paragraph tags:

```
    \LWR@minipagestoppars%
```

Print the span with the converted width and height. The width and height are NOT rounded, since a height of less than 1pt is quite common in LaTeX code.

```
    \LWR@findcurrenttextcolor%
    \LWR@htmltagc{%
    span\LWR@indentHTML%
    style=\textquotedbl%
```

The HTML background color is used to draw the filled rule according to the LaTeX foreground color set by `\textcolor`.

```
    \ifbool{FormatWP}{}{background:\LWR@currenttextcolor ; }%
```

The width and height are printed, converted to PT:

```
    width:\LWR@printlength{\LWR@tempwidth} ; %
    height:\LWR@printlength{\LWR@tempheight} ; %
```

The raise height is converted to a CSS transform. The `*2` raise multiplier is to approximately match HTML output's X height. Conversion to a LaTeX length allows a typical LaTeX expression to be used as an argument for the raise, whereas printing the raise argument directly to HTML output without conversion to a LaTeX length limits the allowable syntax. To do: A superior method would compute a ratio of LaTeX ex height, then print that to HTML with an ex unit.

```
    \ifblank{#1}%
    {}%
```

```
    {%
        \setlength{\LWR@tempraise}{0pt-#1}%
        \setlength{\LWR@tempraise}{\LWR@tempraise*2}%
        \LWR@indentHTML%
        -ms-transform: translate(0pt,\LWR@printlength{\LWR@tempraise}); %
        \LWR@indentHTML%
        -webkit-transform: translate(0pt,\LWR@printlength{\LWR@tempraise}); %
        \LWR@indentHTML%
        transform: translate(0pt,\LWR@printlength{\LWR@tempraise}); %
        \LWR@indentHTML%
    }%
```

Display inline-block to place the span inline with the text:

```
    display:inline-block;\textquotedbl\LWR@orignewline%
    }%
```

If formatting for a word processor, approximate with a number of underscores, in case a span of a given width is not supported:

```
        \ifbool{FormatWP}{%
            \setlength{\LWR@templengthone}{\LWR@tempwidth}%
            \whiledo{\lengthtest{\LWR@templengthone>1em}}{%
                \_{}%
                \addtolength{\LWR@templengthone}{-1em}%
            }%
        }%
```

If NOT formatting for a word processor, add a comment to avoid an empty :

```
        {\LWR@htmlcomment{}}%
```

Close the span:

```
    \LWR@htmltagc{/span}%
```

If had a minipage this paragraph, try to inline the white space without generating paragraph tags:

```
    \LWR@minipagestartpars%
}% non-zero width
}

\LWR@formatted{rule}

\end{warpHTML}
```

97 \phantomsection

for HTML output:

```
\begin{warpHTML}
```

\LWR@phantomsection Emulate the hyperref \phantomsection command, often used to insert the bibliography into the table of contents. Ignores \ForceHTMLTOC.

```
\newrobustcmd*{\LWR@phantomsection}{%
    \begingroup%
    \boolfalse{LWR@forcinghtmltoc}%
    \section*{}%
    \endgroup%
}
```

```
\end{warpHTML}
```

98 \LaTeX and other logos

Logos for HTML and print modes:

Some of these logos may be redefined in a later package, so after loading other packages, and at the beginning of the document, their definitions are finally set by \LWR@formatted.

For CSS conversions, see:
http://edward.oconnor.cx/2007/08/tex-poshlet
http://nitens.org/taraborelli/texlogo
and the spacing described in the metafont package documentation.

for HTML & PRINT:

```
\begin{warpall}
\newbool{LWR@warnXe}
\boolfalse{LWR@warnXe}

\newrobustcmd*{\Xe}
    {%
        X\hspace{-.1667em}\raisebox{-.5ex}{E}%
        \global\booltrue{LWR@warnXe}%
    }

\AtBeginDocument{
    \@ifpackageloaded{graphics}{
        \@ifpackageloaded{metalogo}{}{
            \renewrobustcmd*{\Xe}
                {X\hspace{-.1667em}\raisebox{-.5ex}{\reflectbox{E}}}
        }
    }{}
}

\AtEndDocument{
    \ifbool{LWR@warnXe}{
        \PackageWarningNoLine{lwarp}{Load graphicx or graphics
            for improved XeTeX logo}
    }{}
}

\providerobustcmd*{\XeTeX}{\mbox{\Xe\hspace{-.125em}\TeX}}
\providerobustcmd*{\XeLaTeX}{\mbox{\Xe\hspace{-.125em}\LaTeX}}
\providerobustcmd*{\AmS}{%
```

```
    \leavevmode\hbox{$\mathcal A\kern-.2em\lower.376ex%
    \hbox{$\mathcal M$}\kern-.2em\mathcal S$}%
}
\newrobustcmd*{\LyX}{\textsf{LyX}}
\providerobustcmd*{\LuaTeX}{\mbox{Lua\TeX}}
\providerobustcmd*{\LuaLaTeX}{\mbox{Lua\LaTeX}}
\providerobustcmd*{\BibTeX}{\mbox{B\textsc{ib}\TeX}}
\providerobustcmd*{\MakeIndex}{\mbox{\textit{MakeIndex}}}
\providerobustcmd*{\ConTeXt}{\mbox{Con\TeX{}t}}
\providerobustcmd*{\MiKTeX}{\mbox{MiK\TeX}}
\end{warpall}
```

for HTML output:

```
\begin{warpHTML}
```

The print-mode versions of the following may be changed by metalogo, so their print formatting is recorded `\AtBeginDocument`.

`\TeX` TEX

`latexlogo` is a css class used to properly typeset the E and A in LATEX and friends.

`latexlogofont` is a css class used to select the font for the rest of the logo in LATEX, LuaTEX, ConTEXt, etc.

```
\newrobustcmd*{\LWR@HTML@TeX}
{%
    \InlineClass{latexlogofont}%
    {%
        \InlineClass{latexlogo}%
        {%
            T%
            \InlineClass{latexlogosub}{e}%
            X%
        }%
    }%
}
\AtBeginDocument{\LWR@formatted{TeX}}% may have been patched by metalogo
```

`\LaTeX` LATEX, LATEX 2_ε
`\LaTeXe`

```
\newrobustcmd*{\LWR@HTML@LaTeX}
{%
    \InlineClass{latexlogofont}%
    {%
        \InlineClass{latexlogo}%
        {%
            L%
            \InlineClass{latexlogosup}{a}%
            T%
            \InlineClass{latexlogosub}{e}%
            X%
        }%
    }%
}
```

```
13497
13498 \AtBeginDocument{\LWR@formatted{LaTeX}}% may have been patched by metalogo
13499
13500
13501 \newrobustcmd*{\LWR@HTML@LaTeXe}
13502 {%
13503     \LaTeX%
13504     \InlineClass{latexlogofont}{%
13505         \InlineClass{latexlogotwoe}{%
13506             2%
13507             \InlineClass{latexlogotwoesub}{\HTMLunicode{03B5}}%
13508         }%
13509     }%
13510 }
13511 \AtBeginDocument{\LWR@formatted{LaTeXe}}% may have been patched by metalogo
```

\LuaTeX \LuaLaTeX

LuaTeX, LuaLaTeX

```
13512 \newrobustcmd*{\LWR@HTML@LuaTeX}{\InlineClass{latexlogofont}{Lua}\TeX}
13513 \AtBeginDocument{\LWR@formatted{LuaTeX}}% may have been patched by metalogo
13514
13515 \newrobustcmd*{\LWR@HTML@LuaLaTeX}{\InlineClass{latexlogofont}{Lua}\LaTeX}
13516 \AtBeginDocument{\LWR@formatted{LuaLaTeX}}% may have been patched by metalogo
```

\XeTeX \XeLaTeX

XeTeX, XeLaTeX

xetexlogo is a css class which aligns the backwards E in XeTeX and spaces TeX appropriately.

xelatexlogo is a css class which aligns the backwards E in XeLaTeX and spaces LaTeX appropriately.

```
13517 \newrobustcmd*{\LWR@HTML@Xe}
13518     {%
13519         X%
13520         \InlineClass{xelatexlogosub}{\HTMLunicode{18e}}%
13521     }
13522 \AtBeginDocument{\LWR@formatted{Xe}}% may have been patched by metalogo
13523
13524 \newrobustcmd*{\LWR@HTML@XeTeX}{\InlineClass{xelatexlogo}{\Xe}\TeX}
13525 \AtBeginDocument{\LWR@formatted{XeTeX}}% may have been patched by metalogo
13526
13527 \newrobustcmd*{\LWR@HTML@XeLaTeX}{\InlineClass{xelatexlogo}{\Xe}\LaTeX}
13528 \AtBeginDocument{\LWR@formatted{XeLaTeX}}% may have been patched by metalogo
```

\ConTeXt

ConTeXt

```
13529 \newrobustcmd*{\LWR@HTML@ConTeXt}{%
13530     \InlineClass{latexlogofont}{Con}\TeX{}%
13531     \InlineClass{latexlogofont}{t}%
13532 }
13533 \LWR@formatted{ConTeXt}
```

\BibTeX BibTeX, *MakeIndex*
\MakeIndex

```
\newrobustcmd*{\LWR@HTML@BibTeX}
    {\InlineClass{latexlogofont}{B\textsc{ib}}\TeX}
\LWR@formatted{BibTeX}

\newrobustcmd*{\LWR@HTML@MakeIndex}
    {\InlineClass{latexlogofont}{\textit{MakeIndex}}}
\LWR@formatted{MakeIndex}
```

\AmS $\mathcal{AMS}$

amslogo is a CSS class used for the $\mathcal{AMS}$ logo.

```
\AtBeginDocument{%
\newrobustcmd*{\LWR@HTML@AmS}
{%
    \InlineClass{amslogo}{%
        \textit{%
            A%
            \InlineClass{latexlogosub}{M}%
            S%
        }%
    }%
}%
\LWR@formatted{AmS}
}
```

\MiKTeX MiKTeX

```
\newrobustcmd*{\LWR@HTML@MiKTeX}{\InlineClass{latexlogofont}{MiK}\TeX}
\LWR@formatted{MiKTeX}
```

\LyX LyX

lyxlogo is a CSS class used for the LyX logo.

```
\newrobustcmd*{\LWR@HTML@LyX}{\InlineClass{lyxlogo}{LyX}}
\LWR@formatted{LyX}

\end{warpHTML}
```

99 Starting and stopping lwarp

for HTML output:

```
\begin{warpHTML}
```

\LWR@LwarpStart
\LWR@LwarpEnd

Automatically sets up the HTML-related actions for the start and end of the document.

```
\AfterEndPreamble{\LWR@LwarpStart}
\AtEndDocument{\LWR@LwarpEnd}

\end{warpHTML}
```

100 Loading everyshi patches

everyshi is emulated by the LaTeX core, so its patches are loaded here. `\AtBeginDocument` is used in case an older verison of LaTeX is used.

for HTML output:
```
\begin{warpHTML}
\AtBeginDocument{
    \@ifpackageloaded{everyshi}{
        \RequirePackage{lwarp-everyshi}
    }{}
}
\end{warpHTML}
```

101 Loading textcomp patches

textcomp has now been integrated into the LaTeX core, so its patches are loaded now.

for HTML output:
```
\begin{warpHTML}
\RequirePackage{lwarp-textcomp}
\end{warpHTML}
```

102 Loading amsmath, amsthm patches, centernot

amsmath, amsthm, and centernot may have been preloaded, such as by newtx, so their patches are loaded now.

for HTML output:
```
\begin{warpHTML}
\@ifpackageloaded{amsthm}{
    \RequirePackage{lwarp-amsthm}
}{}

\@ifpackageloaded{amsmath}{
    \RequirePackage{lwarp-amsmath}
}{}
```

amsthm may load centernot, so centernot must be checked second.

```
\@ifpackageloaded{centernot}{
    \RequirePackage{lwarp-centernot}
}{}
\end{warpHTML}
```

103 Loading Koma-script class patches

Load patches to koma-script.

for HTML output:
```
\begin{warpHTML}
```

```
\@ifclassloaded{scrbook}{\RequirePackage{lwarp-patch-komascript}}{}
\@ifclassloaded{scrartcl}{\RequirePackage{lwarp-patch-komascript}}{}
\@ifclassloaded{scrreprt}{\RequirePackage{lwarp-patch-komascript}}{}

\end{warpHTML}
```

104 Loading Memoir class patches

Load patches to memoir.

for PRINT output:

```
\begin{warpprint}
\@ifclassloaded{memoir}{\LWR@origRequirePackage{xcolor}}{}
\end{warpprint}
```

for HTML output:

```
\begin{warpHTML}
\@ifclassloaded{memoir}{\RequirePackage{lwarp-patch-memoir}}{}
\end{warpHTML}
```

105 ut* class patches

Load patches to uj* and ut* classes, as well as ltj* classes.

for HTML output:

```
\begin{warpHTML}

\newcommand*{\LWR@patchujtclasses}{
```

uj/t does not use \partname

```
    \def\@partnameformat{}

    \def\@partcntformat##1{%
        \prepartname%
        \csname the##1\endcsname%
        \postpartname%
        \quad%
    }
    \@ifundefined{chapter}{}{
        \def\@chapcntformat##1{%
            \prechaptername%
            \csname the##1\endcsname%
            \postchaptername%
            \quad%
        }
    }
    \renewcommand*{\LWR@printchaptername}{}
```

Use decimal points instead of centered dots:

```
    \renewcommand{\thepart}{\@Roman\c@part}
```

```
    \@ifundefined{chapter}{
        \renewcommand{\thesection}{\@arabic\c@section}
    }{
        \renewcommand{\thechapter}{\@arabic\c@chapter}
        \renewcommand{\thesection}{\thechapter.\@arabic\c@section}
    }
    \renewcommand{\thesubsection}{\thesection.\@arabic\c@subsection}
    \renewcommand{\thesubsubsection}{%
    \thesubsection.\@arabic\c@subsubsection}
    \renewcommand{\theparagraph}{%
    \thesubsubsection.\@arabic\c@paragraph}
    \renewcommand{\thesubparagraph}{%
    \theparagraph.\@arabic\c@subparagraph}
    \@ifundefined{chapter}{
        \renewcommand{\thefigure}{\@arabic\c@figure}
        \renewcommand{\thetable}{\@arabic\c@table}
    }{
        \renewcommand{\thefigure}{%
        \ifnum\c@chapter>\z@\thechapter.\fi\@arabic\c@figure}
        \renewcommand{\thetable}{%
        \ifnum\c@chapter>\z@\thechapter.\fi\@arabic\c@table}
    }
}

\@ifclassloaded{ujarticle}{\LWR@patchujtclasses}{}
\@ifclassloaded{ujbook}{\LWR@patchujtclasses}{}
\@ifclassloaded{ujreport}{\LWR@patchujtclasses}{}
\@ifclassloaded{utarticle}{\LWR@patchujtclasses}{}
\@ifclassloaded{utbook}{\LWR@patchujtclasses}{}
\@ifclassloaded{utreport}{\LWR@patchujtclasses}{}
\@ifclassloaded{ltjarticle}{\LWR@patchujtclasses}{}
\@ifclassloaded{ltjbook}{\LWR@patchujtclasses}{}
\@ifclassloaded{ltjreport}{\LWR@patchujtclasses}{}
\@ifclassloaded{ltjsarticle}{\LWR@patchujtclasses}{}
\@ifclassloaded{ltjsbook}{\LWR@patchujtclasses}{}
\@ifclassloaded{ltjsreport}{\LWR@patchujtclasses}{}
\@ifclassloaded{ltjskiyou}{\LWR@patchujtclasses}{}
\@ifclassloaded{ltjspf}{\LWR@patchujtclasses}{}
\@ifclassloaded{ltjtarticle}{\LWR@patchujtclasses}{}
\@ifclassloaded{ltjtbook}{\LWR@patchujtclasses}{}
\@ifclassloaded{ltjtreport}{\LWR@patchujtclasses}{}

\end{warpHTML}
```

106 CTEX patches

Patches for ctex and related classes, which are loaded before lwarp.

All CTEX classes and the ctex package seem to load ctexpatch, so its presence is used to decide whether to have lwarp patch CTEX.

for HTML output:

```
\begin{warpHTML}
```

`\AtBeginDocument` in case the user set `FileSectionNames` in the preamble.

```
\AtBeginDocument{
    \@ifpackageloaded{ctexpatch}{%
        \def\@partcntformat#1{%
            \LWR@isolate{\CTEX@partname}~%
            \CTEX@part@aftername%
        }%

        \def\@partnameformat{}

        \def\@chapcntformat#1{%
            \LWR@isolate{\CTEX@chaptername}~%
            \CTEX@chapter@aftername%
        }%

        \renewcommand*{\LWR@printchaptername}{}
    }{}
}
```

```
\end{warpHTML}
```

107 kotexutf patches

Patch for kotexutf, which is loaded before lwarp.

kotexutf's `\@setref` was conflicting with lwarp's cross references.

for HTML output:

```
\begin{warpHTML}
```

If kotexutf's version of `\@setref` is detected, it is reverted to the original.

```
\AtBeginDocument{
\@ifpackageloaded{kotexutf}{%
    \def\LWR@kotexutf@setref#1#2#3{%
        \@setref@dhucs@orig{#1}{#2}{#3}%
      \ifx#1\relax\else
        \bgroup
        \dhucs@make@cjkchar@null
        \edef\@temp{\expandafter#2#1}\global\josatoks\expandafter{\@temp}%
        \egroup
      \fi%
    }%

    \ifdefequal{\@setref}{\LWR@kotexutf@setref}{
        \let\@setref\@setref@dhucs@orig
    }{}
}{}
}
```

```
\end{warpHTML}
```

108 babel and polyglossia warnings

lwarp prints a message instructing the user how to avoid the following error.

(These are not \PackageWarnings because there may not be a problem.)

lwarp uses cleveref, which has some limitations when using polyglossia, possibly resulting in the error

```
! Undefined control sequence. . . . \__hook begindocument
```

To test compatibility, add

```
\usepackage{cleveref}
```

near the end of the preamble (as the last package to be loaded), and try to compile the print version. It may be necessary to set

```
\setdefaultlanguage{english}
```

or some other language supported by cleveref, then select other languages using \setotherlanguages.

Once the print version works with cleveref and polyglossia, the HTML version should work as well using lwarp.

for HTML output:

```
\begin{warpHTML}
\AtBeginDocument{

\@ifpackageloaded{polyglossia}{
    \PackageWarningNoLine{lwarp}
    {%
        Polyglossia has been loaded.  Lwarp also uses cleveref.\MessageBreak
        See the cleveref documentation regarding\MessageBreak
        polyglossia support.  Some languages are not supported%
    }
    \typeout{---}
    \typeout{Package lwarp:}
    \typeout{If the error}
    \typeout{\space\space``! Undefined control sequence.
        \space ... \space \protect\__hook begindocument''}
    \typeout{occurs here, use the polyglossia macro:}
    \typeout{\space\space\protect\setmainlanguage\protect{...\protect}}
    \typeout{---}
}{
    \@ifpackageloaded{babel}{
        \PackageWarningNoLine{lwarp}
        {%
            Babel has been loaded.  Lwarp also uses cleveref.\MessageBreak
            See the cleveref documentation regarding\MessageBreak
            babel support.  Some languages are not supported%
        }
    }{}
}

```

```
}
\end{warpHTML}
```

109 MathJax warnings

\LWR@mathjaxwarn {⟨*packagename*⟩} {⟨*More text.*⟩}

To be done \AtBeginDocument.

```
\newcommand*{\LWR@mathjaxwarn}[2]{%
    \@ifpackageloaded{lwarp-#1}{%
        \ifblank{#2}{%
            \PackageWarningNoLine{lwarp}
                {%
                   Lwarp provides emulation for MathJax when used\MessageBreak
                    with the #1 package%
                }
        }{%
            \PackageWarningNoLine{lwarp}
                {%
                   Lwarp provides emulation for MathJax when used\MessageBreak
                    with the #1 package.\MessageBreak
                    #2%
                }
        }%
    }{}%
}

% \begin{macro}{\LWR@nomathjaxwarn} \marg{packagename} \marg{More text.}
%
% To be done \cs{AtBeginDocument}.
%
% \changes{v0.894}{2020/12/22}{Warn if using packages not supported by \brand{MathJax}.}
% \changes{v0.895}{2021/01/08}{Improved \brand{MathJax} warning.}
%    \begin{macrocode}
\newcommand*{\LWR@nomathjaxwarn}[2]{%
    \@ifpackageloaded{lwarp-#1}{%
        \ifblank{#2}{%
            \PackageWarningNoLine{lwarp}
                {%
                   Lwarp does not provide MathJax support for #1.\MessageBreak
                    Use SVG math by removing the Lwarp mathjax option%
                }
        }{%
            \PackageWarningNoLine{lwarp}
                {%
                   Lwarp does not provide MathJax support for #1.\MessageBreak
                    #2%
                }
        }%
    }{}%
}
```

\LWR@forceSVGmessage {⟨*packagename*⟩}

```
\newcommand*{\LWR@forceSVGmessage}[1]{%
    SVG math output may be enabled for select math\MessageBreak
    expressions to preserve #1 visual\MessageBreak
    features for those particular expressions.\MessageBreak
    Before the chosen inline math, use \protect\inlinemathother\MessageBreak
    to begin using SVG math, and \protect\inlinemathnormal\MessageBreak
    afterward to resume using MathJax math.\MessageBreak
    Before display math, use \protect\displaymathother\MessageBreak
    to begin using SVG math, and use \protect\displaymathnormal\MessageBreak
    after to resume using MathJax for the following math.\MessageBreak
    Or, use SVG math for all expressions by removing\MessageBreak
    the mathjax option for the lwarp package%
}
```

If MathJax is being used, issue a warning for certain packages.

```
\AtBeginDocument{
    \ifbool{mathjax}{
        \LWR@nomathjaxwarn{aligned-overset}{}
        \LWR@nomathjaxwarn{amscdx}
            {\LWR@forceSVGmessage{amscdx}}
        \LWR@mathjaxwarn{arydshln}
            {In a math array, do not use the optional argument\MessageBreak
            for \protect\cdashline.\space\space
            Furthermore, \protect\cline\space is not\MessageBreak
            supported by MathJax}
        \LWR@nomathjaxwarn{autoaligne}{}
        \LWR@mathjaxwarn{autonum}
            {MathJax does not support equation+.\MessageBreak
            You may use the warpprint and warpHTML\MessageBreak
            environments to isolate the package load\MessageBreak
            and the equation+ environments}
        \LWR@mathjaxwarn{bigdelim}
            {Delimiters appear only of the first line}
        \LWR@nomathjaxwarn{boldtensors}{}
        \LWR@mathjaxwarn{booktabs}
            {\protect\cmidrule\space is not displayed}
        \LWR@mathjaxwarn{breqn}
            {Each environment becomes an SVG image}
        \LWR@mathjaxwarn{colortbl}
            {Colors are ignored in MathJax.\MessageBreak
            (Text mode tabular does support colortbl.)\MessageBreak
            \LWR@forceSVGmessage{colortbl}}
        \LWR@mathjaxwarn{delarray}
            {\LWR@forceSVGmessage{delarray}}
        \LWR@nomathjaxwarn{gauss}
            {\LWR@forceSVGmessage{gauss}}
        \LWR@mathjaxwarn{hhline}
            {A simple \protect\hline\space is used}
        \LWR@mathjaxwarn{isomath}
        {Some of the symbol font macros such as \protect\mathsfbfit\MessageBreak
               do not use a sans font because MathJax does not yet\MessageBreak
                 have sans Greek.  Tensors may look like vectors%
```

```
            }
        \LWR@nomathjaxwarn{jkmath}
            {\LWR@forceSVGmessage{jkmath}}
        \LWR@mathjaxwarn{libertinust1math}
        {Some of the symbol font macros such as \protect\mathsfbfit\MessageBreak
               do not use a sans font because MathJax does not yet\MessageBreak
                 have sans Greek.  Tensors may look like vectors%
            }
        \LWR@mathjaxwarn{mathtools}
            {See the Lwarp manual regarding the disallowspaces\MessageBreak
            and showonlyrefs options, the alignat environment,\MessageBreak
            and \protect\DeclarePairedDelimiter\space and related%
            }
        \LWR@mathjaxwarn{mathspec}
            {Double quotes are removed, even inside \protect\text}
        \LWR@mathjaxwarn{multirow}
            {Multirow works as expected in text mode, but\MessageBreak
            limited emulation is provided for MathJax math.\MessageBreak
            \protect\multirow\space ignores all arguments except\MessageBreak
            the text}
        \LWR@mathjaxwarn{nicematrix}
            {Keys/values are ignored in MathJax.\MessageBreak
            \protect\Cdots, etc. do not span multiple cells.\MessageBreak
            AutoNiceMatrix, etc. are not supported for MathJax.\MessageBreak
            \LWR@forceSVGmessage{nicematrix}%
            }
        \LWR@nomathjaxwarn{pb-diagram}
            {\LWR@forceSVGmessage{pb-diagram}}
%         \LWR@mathjaxwarn{physics}
% %             {The third-party extension is not used.\MessageBreak
%             {The MathJax v3 extension is used.\MessageBreak
%             See the Lwarp manual for details}
        \LWR@nomathjaxwarn{tensind}{}
        \LWR@mathjaxwarn{unicode-math}
            {Do not use embedded Unicode characters.\MessageBreak
            (Not all characters are encoded correctly.)\MessageBreak
            Some symbol fonts are not supported by MathJax,\MessageBreak
            and are only approximated.\MessageBreak
        Greek macros such as \protect\alpha\space respond to the math-style\MessageBreak
            option.  Latin symbols does not, per MathJax\MessageBreak
           limitations, unless placed inside \protect\symbit\space or similar}
        \LWR@nomathjaxwarn{unitsdef}{}
        \LWR@mathjaxwarn{witharrows}
            {Arrows can only point to the next line.\MessageBreak
            Text is only placed on a single line}
        \LWR@nomathjaxwarn{xy}
          {In text, xy works as-is.  SVG images will be generated.\MessageBreak
            \LWR@forceSVGmessage{xy}}
    }{}
}
```

File 2 **lwarp-2in1.sty**

§ 110 Package 2in1

Pkg 2in1 2in1 is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{2in1}
```

File 3 **lwarp-2up.sty**

§ 111 Package 2up

Pkg 2up 2up is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{2up}[2010/05/15]

\def\source#1#2#3{}
\def\target#1#2#3{}
\def\targetlayout#1{}
\newdimen\pageseplength
\newdimen\pagesepwidth
\newdimen\pagesepoffset
\def\twoupemptypage{}
\def\twoupclearpage{}
\def\twoupeject{}
\def\twouparticle{}
\def\twoupplain{}
\def\twouplegaltarget{}
\def\twouplandscape{}
\def\TwoupWrites{}
```

File 4 **lwarp-a4.sty**

§ 112 Package a4

Pkg a4 a4 is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{a4}[2004/04/15]

\newcommand*{\WideMargins}{}
```

File 5 **lwarp-a4wide.sty**

§ 113 Package a4wide

Pkg a4wide a4wide is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{a4wide}[1994/08/30]
```

File 6 **lwarp-a5comb.sty**

§ 114 Package a5comb

Pkg a5comb a5comb is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{a5comb}
```

File 7 **lwarp-abstract.sty**

§ 115 Package abstract

(*Emulates or patches code by* Peter Wilson.)

Pkg abstract abstract is supported and patched by lwarp.

⚠ missing toc If using the number option with file splits, be sure to place the table of contents before the abstract. The number option causes a section break which may cause a file split, which would put a table of contents out of the home page if it is after the abstract.

for HTML output: memoir provides an abstract environment even though it is not an article or report class. Meanwhile, lwarp loads book to emulate memoir, but book does not have an abstract environment, so when the abstract package is loaded for emulation there is no pre-existing abstract to redefine, which would cause an error. Thus, a null abstract is provide here:

```
\ProvideDocumentEnvironment{abstract}{}{}{}
```

Accept all options for lwarp-abstract:

```
\LWR@ProvidesPackagePass{abstract}[2009/06/08]

\AtBeginDocument{
\BeforeBeginEnvironment{abstract}{
\LWR@forcenewpage
\BlockClass{abstract}
}
\AfterEndEnvironment{abstract}{\endBlockClass}
}

\renewcommand{\@bsrunintitle}{%
\hspace*{\abstitleskip}%
{\abstractnamefont%
\InlineClass{abstractrunintitle}{\abstractname}%
\@bslabeldelim}%
}
```

```
\@ifclassloaded{memoir}
{
  \renewenvironment{abstract}{%
% %     \titlepage
%     \null\vfil
%     \@beginparpenalty\@lowpenalty
  \setup@bstract
    \if@bsrunin
    \else
%       \if@bsstyle
%         \abstitlestyle{\BlockClassSingle{abstracttitle}{\abstractname}}
%       \else
        \ifnumber@bs
          \num@bs
        \else
          \begin{\absnamepos}%
  \abstractnamefont \BlockClassSingle{abstracttitle}{\abstractname}
%             \@endparpenalty\@M
          \end\absnamepos%
       \vspace{\abstitleskip}%
        \fi
%       \fi
%       \vspace{\abstitleskip}%
    \fi
    \put@bsintoc%
    \begin{@bstr@ctlist}\if@bsrunin\@bsrunintitle\fi\abstracttextfont}%
    {\par\end{@bstr@ctlist}%\vfil\null%\endtitlepage
    }
}{% not memoir
\if@titlepage
  \renewenvironment{abstract}{%
%     \titlepage
    \null\vfil
    \@beginparpenalty\@lowpenalty
    \if@bsrunin
    \else
      \if@bsstyle
        \abstitlestyle{\BlockClassSingle{abstracttitle}{\abstractname}}
      \else
        \ifnumber@bs
          \num@bs
        \else
          \begin{\absnamepos}%
  \abstractnamefont \BlockClassSingle{abstracttitle}{\abstractname}
            \@endparpenalty\@M
          \end\absnamepos%
%%        \vspace{\abstitleskip}%
        \fi
      \fi
      \vspace{\abstitleskip}%
    \fi
    \put@bsintoc%
    \begin{@bstr@ctlist}\if@bsrunin\@bsrunintitle\fi\abstracttextfont}%
    {\par\end{@bstr@ctlist}\vfil\null%\endtitlepage
    }
```

```
\else
  \renewenvironment{abstract}{%
    \if@bsrunin
    \else
      \if@bsstyle
        \abstitlestyle{\BlockClassSingle{abstracttitle}{\abstractname}}
      \else
        \ifnumber@bs
          \num@bs
        \else
\begin{\absnamepos}%
\abstractnamefont\BlockClassSingle{abstracttitle}{\abstractname}%
\end\absnamepos%
%%        \vspace{\abstitleskip}%
        \fi
      \fi
      \vspace{\abstitleskip}%
    \fi
    \put@bsintoc%
    \begin{@bstr@ctlist}\if@bsrunin\@bsrunintitle\fi\abstracttextfont}%
    {\par\end{@bstr@ctlist}}
\fi
}% not memoir
```

File 8 **lwarp-academicons.sty**

§ 116 Package

academicons

(*Emulates or patches code by* Diogo A. B. Fernandes.)

Pkg academicons

academicons is patched for use by lwarp.

If \aiicon is used, the name of the icon is used in the alt tag. Otherwise, for each of the individual icon macros, a generic alt tag is used.

for HTML output:

```
\LWR@ProvidesPackagePass{academicons}[2018/06/27]

\LetLtxMacro\LWR@orig@symbol\symbol

\let\LWR@academicons@orig@AI\AI

\newcommand*{\LWR@academicons@symbol}[1]{%
    \begin{lateximage}*[academicon][academicons#1]%
    \begingroup%
    \LWR@academicons@orig@AI%
    \LWR@orig@symbol{#1}%
    \endgroup%
    \end{lateximage}%
}

\renewcommand*{\AI}{%
    \LetLtxMacro\symbol\LWR@academicons@symbol%
}
```

```
\renewcommand*{\aiicon}[1]
{%
    \begin{lateximage}*[#1 icon][academicons#1]%
    \AI\csname aiicon@#1\endcsname%
    \end{lateximage}%
}
```

File 9 **lwarp-accents.sty**

§ 117 Package

accents

(*Emulates or patches code by* Javier Bezos.)

Pkg accents accents is used as-is for SVG math, and is emulated for MathJax.

for HTML output:

```
\LWR@ProvidesPackagePass{accents}[2006/05/12]
```

For MathJax:

```
\begin{warpMathJax}
\LWR@infoprocessingmathjax{accents}

\CustomizeMathJax{\newcommand{\ring}[1]{\mathring{#1}}}
\CustomizeMathJax{\newcommand{\accentset}[2]{\overset{#1{}}{#2}}}
```

As of this writing, MathJax v3 does not yet support groups for macros, so for \underaccent, the originals are remembered here, then they are temporarily redefined and used inside \underaccent, then restored to their originals. \LARGE gives a reasonable size, and \raise is used to adjust vertically without introducing extra line space.

```
\CustomizeMathJax{\let\LWRgrave\grave}
\CustomizeMathJax{\let\LWRacute\acute}
\CustomizeMathJax{\let\LWRcheck\check}
\CustomizeMathJax{\let\LWRbreve\breve}
\CustomizeMathJax{\let\LWRbar\bar}
\CustomizeMathJax{\let\LWRhat\hat}
\CustomizeMathJax{\let\LWRdot\dot}
\CustomizeMathJax{\let\LWRtilde\tilde}
\CustomizeMathJax{\let\LWRddot\ddot}
\CustomizeMathJax{\let\LWRvec\vec}
\CustomizeMathJax{\let\LWRwidetilde\widetilde}

\CustomizeMathJax{\newcommand{\underaccent}[2]{%
    {%
    \renewcommand{\grave}[1]{{\LARGE\LWRgrave{##1}}}%
    \renewcommand{\acute}[1]{{\LARGE\LWRacute{##1}}}%
    \renewcommand{\check}[1]{{\LARGE\LWRcheck{##1}}}%
    \renewcommand{\breve}[1]{{\LARGE\LWRbreve{##1}}}%
    \renewcommand{\bar}[1]{{\LARGE\LWRbar{##1}}}%
    \renewcommand{\hat}[1]{{\LARGE\LWRhat{##1}}}%
    \renewcommand{\dot}[1]{{\LARGE\LWRdot{##1}}}%
```

```
    \renewcommand{\tilde}[1]{{\LARGE\LWRtilde{##1}}}%
    \renewcommand{\ddot}[1]{{\LARGE\LWRddot{##1}}}%
    \renewcommand{\vec}[1]{{\LARGE\LWRvec{##1}}}%
    \renewcommand{\widetilde}[1]{{\LARGE\LWRwidetilde{\hphantom{#2}}}}%
    \underset{\raise 2pt {#1{}}}{#2}%
    \let\grave\LWRgrave%
    \let\acute\LWRacute%
    \let\check\LWRcheck%
    \let\breve\LWRbreve%
    \let\bar\LWRbar%
    \let\hat\LWRhat%
    \let\dot\LWRdot%
    \let\tilde\LWRtilde%
    \let\ddot\LWRddot%
    \let\vec\LWRvec%
    \let\widetilde\LWRwidetilde%
    }%
}}

\CustomizeMathJax{\newcommand{\undertilde}[1]{%
    \underset{\raise 3pt {\widetilde{\hphantom{#1}}}}{#1}%
}}
\end{warpMathJax}
```

File 10 **lwarp-accessibility.sty**

§ 118 Package accessibility

Pkg accessibility accessibility is emulated.

for HTML output: Discard all options for lwarp-accessibility:

```
\LWR@ProvidesPackageDrop{accessibility}[2019/10/14]

\newcommand{\alt}[1]{\ThisAltText{#1}}
\newcommand{\newhref}[3]{\ThisAltText{#2}\LWR@href{#1}{#3}}%
\providecommand{\thead}[1]{\textbf{#1}}
```

For MathJax:

```
\begin{warpMathJax}
\CustomizeMathJax{\newcommand{\alt}[1]{}}
\CustomizeMathJax{\newcommand{\thead}[1]{\text{\textbf{#1}}}}
\end{warpMathJax}
```

File 11 **lwarp-accsupp.sty**

§ 119 Package accsupp

Pkg accsupp accsupp is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{accsupp}[2018/03/28]

\newcommand*{\BeginAccSupp}[1]{}
\newcommand*{\EndAccSupp}[1]{}
```

For MathJax:

```
\begin{warpMathJax}
\CustomizeMathJax{\newcommand{\BeginAccSupp}[1]{}}
\CustomizeMathJax{\newcommand{\EndAccSupp}[1]{}}
\end{warpMathJax}
```

File 12 **lwarp-acro.sty**

§ 120 Package

acro

(*Emulates or patches code by* Clemens Niederberger.)

Pkg acro acro is patched for use by lwarp.

⚠ formats Define acronymn formats using `\textbf` instead of `\bfseries` etc.

for HTML output:

```
\LWR@ProvidesPackagePass{acro}[2019/10/12]
```

`\DeclareAcronym` is used in the preamble, where lwarp has not yet made the dollar active, so temporarily enable lwarp math catcode just for this definition:

```
\ExplSyntaxOn
\NewDocumentCommand \LWR@DeclareAcronym {mm}
{
    \acro_declare_acronym:nn {#1} {#2}
    \catcode`\$=3% lwarp
}
\ExplSyntaxOff

\RenewDocumentCommand{\DeclareAcronym}{}{
    \catcode`\$=\active% lwarp
    \LWR@DeclareAcronym
}
```

Replace dot fill with simple dots:

```
\ExplSyntaxOn
\cs_new_protected:Npn \LWR@HTML@acro_dot_fill: {\dots\space}
\LWR@formatted{acro_dot_fill:}
\ExplSyntaxOff
```

Modified to activate the current font:

```
\ExplSyntaxOn
\@ifpackagelater{acro}{2020/04/29}%
{}% v3 or later
```

```
{% before v3
\@ifpackagelater{acro}{2019/09/23}%
{% v2.10 or later
\cs_gset_protected:Npn \__acro_typeset:nn #1#2
  {
    \mode_if_horizontal:F { \leavevmode }
    \group_begin:
      \use:x
        {
          \bool_if:cTF {l__acro_custom_#1_format_bool}
            { \exp_not:v {l__acro_custom_#1_format_tl} }
            { \exp_not:v {l__acro_#1_format_tl} }
            {\exp_not:N\LWR@textcurrentfont{#2}}%   lwarp
        }
    \group_end:
  }

\cs_gset_protected:Npn \__acro_ending_format:nn #1#2
  {
    \bool_if:NTF \l__acro_include_endings_format_bool
      {
        \str_case:nn {#1}
          {
            {long}
            {
              \bool_if:NTF \l__acro_custom_long_format_bool
                { \l__acro_custom_long_format_tl }
                {
                  \bool_if:NTF \l__acro_first_instance_bool
                    { \l__acro_first_long_format_tl }
                    { \l__acro_long_format_tl }
                }
            }
            {short}
            {
              \bool_if:NTF \l__acro_custom_short_format_bool
                { \l__acro_custom_short_format_tl }
                { \l__acro_short_format_tl }
            }
            {alt}
            {
              \bool_if:NTF \l__acro_custom_alt_format_bool
                { \l__acro_custom_alt_format_tl }
                { \l__acro_alt_format_tl }
            }
          }
      }
      { \use:n }
      {\exp_not:N\LWR@textcurrentfont{#2}}% lwarp
  }
}% v2.10 or later
{% before v2.10
\cs_gset_protected:Npn \acro_write_short:nn #1#2
  {
    \mode_if_horizontal:F { \leavevmode }
```

```
    \group_begin:
      \bool_if:NTF \l__acro_custom_format_bool
        { \l__acro_custom_format_tl }
        { \l__acro_short_format_tl }
      {\LWR@textcurrentfont{#2}}% lwarp
    \group_end:
  }

\cs_gset_protected:Npn \acro_write_alt:nn #1#2
  {
    \mode_if_horizontal:F { \leavevmode }
    \group_begin:
      \bool_if:NTF \l__acro_custom_format_bool
        { \l__acro_custom_format_tl }
        { \l__acro_alt_format_tl }
      {\LWR@textcurrentfont{#2}}% lwarp
    \group_end:
  }

\cs_gset_protected:Npn \acro_write_long:nn #1#2
  {
    \mode_if_horizontal:F { \leavevmode }
    \group_begin:
      \bool_if:NTF \l__acro_custom_long_format_bool
        { \l__acro_custom_long_format_tl }
        { \use:n }
      {
        \use:x
          {
            \exp_not:n {#1}
            {
              \bool_if:NTF \l__acro_first_upper_bool
                { \exp_not:N \__acro_first_upper_case:n { \exp_not:n {
                    \LWR@textcurrentfont{#2}% lwarp
                } } }
                { \exp_not:n {\LWR@textcurrentfont{#2}} }% lwarp
            }
          }
      }
    \group_end:
  }
}% before v2.10
}% before v3
\ExplSyntaxOff
```

File 13 **lwarp-acronym.sty**

§ 121 Package

acronym

(*Emulates or patches code by* Tobias Oetiker.)

Pkg acronym acronym is patched for use by lwarp.

⚠ multiply-defined labels `\acresetall` does not work with cleveref, causing multiply-defined labels. lwarp patches

acronym for HTML, but not for print mode.

for HTML output:

```
\LWR@ProvidesPackagePass{acronym}[2015/03/21]
```

Uses \textit instead of \itshape:

```
\renewcommand{\acfia}[1]{%
  {\textit{\AC@acl{#1}}} (\ifAC@starred\acs*{#1}\else\acs{#1}\fi)}
```

Removes the mbox to allow math inside:

```
\renewcommand*\AC@acs[1]{%
%     \mbox{
 \expandafter\AC@get\csname fn@#1\endcsname\@firstoftwo{#1}}
% }
```

Fix for acronym labels in the captions of floats.

```
\renewcommand{\@starttoc}[1]{
\LWR@htmlelementclass{nav}{#1}
\LetLtxMacro\@verridelabel\@gobble
\LWR@orig@starttoc{#1}
\LWR@htmlelementclassend{nav}{#1}
}
```

Modified for cleveref and lwarp:

```
\renewcommand*\AC@und@newl@bel[3]{%
    \@ifundefined{#1@#3}%
    {%
        \global\expandafter\let\csname#2@#3\endcsname\@nnil
        \global\expandafter\let\csname#2@#3@lwarp\endcsname\@nnil% lwarp
        \global\expandafter\let\csname#2@#3@cref\endcsname\@nnil% lwarp
    }%
    {%
        \global\expandafter\let\csname#1@#3\endcsname\relax
        \global\expandafter\let\csname#1@#3@lwarp\endcsname\relax% lwarp
        \global\expandafter\let\csname#1@#3@cref\endcsname\relax% lwarp
    }%
}%
```

File 14 **lwarp-adjmulticol.sty**

§ 122 Package adjmulticol

(*Emulates or patches code by* Boris Veytsman.)

Pkg adjmulticol

adjmulticol is emulated.

Emulation similar to multicols is used, with adjusted margins. If the number of columns is specified as 1, it is set so, but if two or greater are used, lwarp allows a variable number of columns up to three.

for HTML output:

```
\LWR@ProvidesPackageDrop{adjmulticol}[2012/01/20]
\RequirePackage{multicol}
```

adjmulticols * {⟨*numcols*⟩} {⟨*left margi*⟩} {⟨*right margin*⟩}

```
\NewDocumentEnvironment{adjmulticols}{s m m m}
{%
```

Compute the margins, and limit to positive only:

```
\setlength{\LWR@templengthone}{#3}%
\ifdimcomp{\LWR@templengthone}{<}{0pt}{\setlength{\LWR@templengthone}{0pt}}{}%
\setlength{\LWR@templengthtwo}{#4}
\ifdimcomp{\LWR@templengthtwo}{<}{0pt}{\setlength{\LWR@templengthtwo}{0pt}}{}%
```

If one column is specified, use a of class singlecolumn, else use multicols:

```
\newcommand*{\LWR@mcolstype}{multicols}%
\ifnumcomp{#2}{=}{1}{\renewcommand*{\LWR@mcolstype}{singlecolumn}}{}%
```

Help avoid page overflow:

```
\LWR@forcenewpage%
```

Create the with the given margin and class:

```
\BlockClass[%
    \LWR@print@mbox{margin-left:\LWR@printlength{\LWR@templengthone}} ; %
    \LWR@print@mbox{margin-right:\LWR@printlength{\LWR@templengthtwo}}%
]{\LWR@mcolstype}%
}
{\endBlockClass}
```

File 15 **lwarp-addlines.sty**

§ 123 Package

addlines

(*Emulates or patches code by* Will Robertson.)

Pkg addlines addlines is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{addlines}[2018/12/05]
\newcommand\addlines{\@ifstar\addlines@a\addlines@a}
\newcommand\addlines@a[1][1]{}
\let\addline\addlines
\newcommand\removelines{\@ifstar\removelines@a\removelines@a}
\newcommand\removelines@a[1][1]{}
\let\removeline\removelines
\newcommand\squeezepage[1][0]{}
```

File 16 **lwarp-afterpage.sty**

§ 124 Package afterpage

(*Emulates or patches code by* David Carlisle.)

Pkg afterpage afterpage is emulated.

for HTML output: Discard all options for lwarp-afterpage:

```
\LWR@ProvidesPackageDrop{afterpage}[2014/10/28]
\newcommand{\afterpage}[1]{#1}
```

File 17 **lwarp-algorithm2e.sty**

§ 125 Package algorithm2e

(*Emulates or patches code by* Christophe Fiorio.)

Pkg algorithm2e algorithm2e is patched for use by lwarp.

For print output, captions are placed according to package options, but for HTML output captions are placed where used. Therefore, to have captions appear at the top of the algorithms for both print and HTML, place each captions at the top of each algorithm.

for HTML output:

```
\LWR@ProvidesPackagePass{algorithm2e}[2017/07/18]
```

For the list-of entries:

```
\renewcommand{\l@algocf}[2]{\hypertocfloat{1}{algocf}{loa}{#1}{#2}}
```

Select the lwarp float style according to the algorithm2e style:

```
\newcommand*{\LWR@floatstyle@algocf}{ruled}

\ifdefstring{\algocf@style}{boxed}{%
\renewcommand*{\LWR@floatstyle@algocf}{boxed}
}{}

\ifdefstring{\algocf@style}{boxruled}{%
\renewcommand*{\LWR@floatstyle@algocf}{boxruled}
}{}

\ifdefstring{\algocf@style}{plain}{%
\renewcommand*{\LWR@floatstyle@algocf}{plain}
}{}
```

Paragraph handling to allow line numbers under certain conditions:

```
\newbool{LWR@algocf@dopars}
\booltrue{LWR@algocf@dopars}

\renewcommand{\algocf@everypar}{%
\ifbool{LWR@algocf@dopars}{%
    \ifbool{LWR@doingstartpars}{%
        \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
            {}%
            {%
                \algocf@everyparnl\algocf@everyparhanging%
            }%
    }{}%
}{}%
}
```

lwarp caption handling:

```
\renewcommand{\algocf@makecaption}[2]{%
\LWR@HTML@caption@begin{algocf}%
\LWR@isolate{\algocf@captiontext{#1}{#2}}%
\LWR@HTML@caption@end%
}
```

Print any caption where it is declared:

```
\renewcommand{\algocf@makecaption@plain}[2]{%
    \LWR@HTML@caption@begin{algocf}%
    \LWR@isolate{\algocf@captiontext{#1}{#2}}%
    \LWR@HTML@caption@end%
}

\renewcommand{\algocf@makecaption@boxed}[2]{%
    \LWR@HTML@caption@begin{algocf}%
    \LWR@isolate{\algocf@captiontext{#1}{#2}}%
    \LWR@HTML@caption@end%
}

\renewcommand{\algocf@makecaption@ruled}[2]{%
    \LWR@HTML@caption@begin{algocf}%
    \LWR@isolate{\algocf@captiontext{#1}{#2}}%
    \LWR@HTML@caption@end%
}
```

Turn off line numbering while making the caption:

```
\long\def\algocf@latexcaption#1[#2]#3{% original definition of caption
\boolfalse{LWR@algocf@dopars}%  lwarp
  \par%
  \addcontentsline{\csname ext@#1\endcsname}{#1}%
 {\protect\numberline{\csname the#1\endcsname}{\ignorespaces \LWR@isolate{#2}}}%
  \begingroup%
  \@parboxrestore%
  \if@minipage%
```

```
    \@setminipage%
  \fi%
  \normalsize%
  \@makecaption{\csname fnum@#1\endcsname}{\ignorespaces #3}\par%
  \endgroup%
\booltrue{LWR@algocf@dopars}%   lwarp
}
```

Line numbers are printed in a of class alg2elinenumber:

```
\renewcommand{\algocf@printnl}[1]{%
    \InlineClass{alg2elinenumber}{\NlSty{#1}}~%
}%
```

While initializing an algorithm environment, locally declare the style of a regular figure to be the same as the algorithm style, in case the figure option was used.

```
\preto\@algocf@init{%
  \edef\LWR@floatstyle@figure{\LWR@floatstyle@algocf}%
}
```

For lwarp, the algorithm is not assembled inside a box, since lateximages would not work, so the captions are printed where declared.

```
\renewcommand{\@algocf@start}{%
    \let\@mathsemicolon=\;\def\;{\ifmmode\@mathsemicolon\else\@endalgoln\fi}%
%     \raggedright%
    \AlFnt{}%
    \booltrue{LWR@algocf@dopars}% lwarp
}

\renewcommand{\@algocf@finish}{%
    \boolfalse{LWR@algocf@dopars}% lwarp
    \lineskip\normallineskip\setlength{\skiptotal}{\@defaultskiptotal}%
    \let\;=\@mathsemicolon%
    \let\]=\@emathdisplay%
}
```

Use an HTML break:

```
\renewcommand{\BlankLine}{%
\LWR@stoppars%
\LWR@htmltagc{br /}%
\LWR@startpars%
}
```

Simplified for HTML. The paragraph handling must be preserved.

```
\renewcommand{\SetKwInOut}[2]{%
  \algocf@newcommand{#1}[1]{%
    \ifthenelse{\boolean{algocf@hanginginout}}%
        {\relax}%
        {\algocf@seteveryparhanging{\relax}}%
    \ifthenelse{\boolean{algocf@inoutnumbered}}%
        {\relax}%
```

```
        {\algocf@seteveryparnl{\relax}}%
    {%
            \KwSty{#2\algocf@typo:}%
        ~##1\par%
    }%
    \algocf@linesnumbered% reset the numbering of the lines
    \ifthenelse{\boolean{algocf@hanginginout}}%
        {\relax}%
        {\algocf@reseteveryparhanging}%
  }%
}%

\renewcommand{\ResetInOut}[1]{}%
```

Each of the following creates a of a given class, and turns off line numbering while creating the tags:

```
\renewcommand{\algocf@Vline}[1]{%
    \boolfalse{LWR@algocf@dopars}%
    \begin{BlockClass}{alg2evline}
    \booltrue{LWR@algocf@dopars}%
    #1
    \boolfalse{LWR@algocf@dopars}%
    \end{BlockClass}
    \booltrue{LWR@algocf@dopars}%
}

\renewcommand{\algocf@Vsline}[1]{%
    \boolfalse{LWR@algocf@dopars}%
    \begin{BlockClass}{alg2evsline}
    \booltrue{LWR@algocf@dopars}%
    #1
    \boolfalse{LWR@algocf@dopars}%
    \end{BlockClass}
    \booltrue{LWR@algocf@dopars}%
}

\renewcommand{\algocf@Noline}[1]{%
    \boolfalse{LWR@algocf@dopars}%
    \begin{BlockClass}{alg2enoline}
    \booltrue{LWR@algocf@dopars}%
    #1
    \boolfalse{LWR@algocf@dopars}%
    \end{BlockClass}
    \booltrue{LWR@algocf@dopars}%
}
```

The [H] environment is converted to a regular float, which in HTML is placed where declared. Reusing the regular float allows the [H] version to reuse the ruled and boxed options.

```
\LetLtxMacro\algocf@Here\algocf
\LetLtxMacro\endalgocf@Here\endalgocf
```

File 18 **lwarp-algorithmicx.sty**

§ 126 Package

algorithmicx

(*Emulates or patches code by* Szász János.)

Pkg algorithmicx algorithmicx is supported with minor adjustments.

for HTML output:

```
\LWR@ProvidesPackagePass{algorithmicx}[2005/04/27]
```

Inside the algorithmic environment, level indenting is converted to a of the required length, and comments are placed inside a which is floated right.

⚠ package conflicts If using \newfloat, trivfloat, and/or algorithmicx together, see section 627.1.

```
\AtBeginEnvironment{algorithmic}{%
%
\let\origALG@doentity\ALG@doentity%
%
\renewcommand*{\ALG@doentity}{%
\origALG@doentity%
\LWR@htmltagc{%
    span style=\textquotedbl{}%
        width:\LWR@printlength{\ALG@thistlm}; display:inline-block;%
    \textquotedbl%
}%
\ifbool{FormatWP}{%
\setlength{\LWR@templengthone}{\the\ALG@thistlm}%
\whiledo{\lengthtest{\LWR@templengthone>1em}}{%
\quad%
\addtolength{\LWR@templengthone}{-1em}%
}%
}{}%
\LWR@htmltagc{/span}%
}%

\let\LWR@origComment\Comment%

\renewcommand{\Comment}[1]{%
    \InlineClass{floatright}{\LWR@origComment{#1}}%
}%
}

\renewcommand\algorithmiccomment[1]{%
\hfill\HTMLunicode{25B7} #1% white right triangle
}%
```

File 19 **lwarp-alltt.sty**

§ 127 Package alltt

(*Emulates or patches code by* Johannes Braams.)

Pkg alltt alltt is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{alltt}[1997/06/16]

\AfterEndPreamble{
\LWR@traceinfo{Patching alltt.}

\AtBeginEnvironment{alltt}{%
    \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
        {}%
        {%
            \LWR@forcenewpage
```

Vertical spacing changes if inside a list.

```
            \LWR@atbeginverbatim{alltt}%
        }%
}

\AfterEndEnvironment{alltt}{%
    \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
        {}%
        {%
```

Vertical spacing changes if inside a list.

```
            \LWR@afterendverbatim%
        }%
}

}
```

File 20 **lwarp-amscdx.sty**

§ 128 Package amscdx

(*Emulates or patches code by* Martin Vermeer.)

Pkg amscdx amscdx is used as-is for SVG math.

⚠ MathJax For MathJax, a warning notes that the CD environment must be enclosed between \displaymathother and \displaymathnormal.

for HTML output:

```
\LWR@ProvidesPackagePass{amscdx}[2019/07/02]

\begin{warpMathJax}
\CustomizeMathJax{%
    \renewenvironment{CD}
```

```
    {\text{(Use \unicode{x005C}displaymathother before the CD enviroment.) \quad}}
    {\quad \text{(Use \unicode{x005C}displaymathnormal after the CD enviroment.)}}
}

\CustomizeMathJax{\newcommand{\CDfattrue}{}}
\CustomizeMathJax{\newcommand{\CDfatfalse}{}}
\CustomizeMathJax{\newcommand{\CDashtrue}{}}
\CustomizeMathJax{\newcommand{\CDashfalse}{}}
\CustomizeMathJax{\newcommand{\CDlor}[1]{}}
\end{warpMathJax}
```

File 21 **lwarp-amsmath.sty**

§ 129 Package

amsmath

(*Emulates or patches code by* American Mathematical Society, LaTeX3 Project.)

Pkg amsmath amsmath is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{amsmath}[2017/09/02]
```

\dotso An HTML text-mode version.

```
\newcommand*{\LWR@HTML@dotso}{\textellipsis\ }
\LWR@formatted{dotso}
```

Patches to allow \eqref inside a caption:

```
\def\maketag@@@#1{\text{#1}}
\def\tagform@#1{\maketag@@@{(\ignorespaces#1\unskip)}}
```

Patches for $\mathcal{AMS}$ math \tag macro to remember the first tag:

```
\ifbool{mathjax}{}{% not mathjax

\LetLtxMacro\LWR@origmake@df@tag@@\make@df@tag@@
\LetLtxMacro\LWR@origmake@df@tag@@@\make@df@tag@@@

\renewcommand*{\make@df@tag@@}[1]{%
\LWR@remembertag{#1}%
\LWR@origmake@df@tag@@{#1}%
}

\renewcommand*{\make@df@tag@@@}[1]{%
\LWR@remembertag{#1}%
\LWR@origmake@df@tag@@@{#1}%
}

}% not mathjax
```

For nesting $\mathcal{AMS}$ environments:

```
\newcounter{LWR@amsmathdepth}
\setcounter{LWR@amsmathdepth}{0}
```

The following $\mathcal{AMS}$ environments are patched in-place:

`\LWR@amsmathenv@@before` * {⟨*environment name*⟩}

* if the environment was starred.

Embeds the environment inside a `lateximage`.

```
\NewDocumentCommand{\LWR@amsmathenv@@before}{s m}{%
    \IfBooleanTF{#1}{
        \begin{BlockClass}{displaymath}
    }{
        \begin{BlockClass}{displaymathnumbered}
    }
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}[\LWR@amsmathbodynumbered{#2}]*%
    \LWR@applyxfakebold%
}
```

`\LWR@amsmathenv@before` * {⟨*environment name*⟩}

* if the environment was starred.

Embeds the environment with MathJax or a `lateximage`.

```
\NewDocumentCommand{\LWR@amsmathenv@before}{s m}{%
    \ifnumequal{\value{LWR@amsmathdepth}}{0}{%
        \LWR@stoppars%
       \ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
        {
            \LWR@syncmathjax
            \boolfalse{LWR@amsmultline}
            \ifstrequal{#2}{multline}{\booltrue{LWR@amsmultline}}{}
            \ifstrequal{#2}{multline*}{\booltrue{LWR@amsmultline}}{}
```

⚠ autonum's "+" environments are not supported by MathJax.

```
            \LWR@beginhideamsmath
        }
        {
            \IfBooleanTF{#1}{
                \LWR@amsmathenv@@before*{#2}
            }{
                \LWR@amsmathenv@@before{#2}
            }
        }
    }{}
    \addtocounter{LWR@amsmathdepth}{1}
}
```

`\LWR@amsmathenv@@after`

Embeds the environment inside a `lateximage`.

```
\newcommand*{\LWR@amsmathenv@@after}{%
```

```
    \end{lateximage}\end{BlockClass}\LWR@startpars%
}
```

\LWR@amsmathenv@after * {⟨*environment name*⟩}

* if the environment was starred. Ignored here, only used for a consistent syntax.

Embeds the environment with MathJax or a `lateximage`.

```
\NewDocumentCommand{\LWR@amsmathenv@after}{s m}{%
    \ifnumequal{\value{LWR@amsmathdepth}}{1}{%
        \ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
        {
            \LWR@endhideamsmath
            \boolfalse{LWR@amsmultline}
            \LWR@addmathjax{#2}{\the\@envbody}
        }
        {\LWR@amsmathenv@@after}
```

Clear the single-use `alt` text:

```
        \gdef\LWR@ThisAltText{}%
    }{}
    \addtocounter{LWR@amsmathdepth}{-1}
}
```

Env multline

```
\BeforeBeginEnvironment{multline}{\LWR@amsmathenv@before{multline}}

\AfterEndEnvironment{multline}{\LWR@amsmathenv@after{multline}}
```

Env multline*

```
\BeforeBeginEnvironment{multline*}{\LWR@amsmathenv@before*{multline*}}

\AfterEndEnvironment{multline*}{\LWR@amsmathenv@after*{multline*}}

```

Env gather

```
\BeforeBeginEnvironment{gather}{\LWR@amsmathenv@before{gather}}

\AfterEndEnvironment{gather}{\LWR@amsmathenv@after{gather}}
```

Env gather*

```
\BeforeBeginEnvironment{gather*}{\LWR@amsmathenv@before*{gather*}}

\AfterEndEnvironment{gather*}{\LWR@amsmathenv@after*{gather*}}
```

Env align

```
\BeforeBeginEnvironment{align}{\LWR@amsmathenv@before{align}}
```

```
86
87 \AfterEndEnvironment{align}{\LWR@amsmathenv@after{align}}
```

Env align*

```
88 \BeforeBeginEnvironment{align*}{\LWR@amsmathenv@before*{align*}}
89
90 \AfterEndEnvironment{align*}{\LWR@amsmathenv@after*{align*}}
```

Env flalign

```
91 \BeforeBeginEnvironment{flalign}{\LWR@amsmathenv@before{flalign}}
92
93 \AfterEndEnvironment{flalign}{\LWR@amsmathenv@after{flalign}}
```

Env flalign*

```
94 \BeforeBeginEnvironment{flalign*}{\LWR@amsmathenv@before*{flalign*}}
95
96 \AfterEndEnvironment{flalign*}{\LWR@amsmathenv@after*{flalign*}}
```

Env alignat

```
97 \BeforeBeginEnvironment{alignat}{\LWR@amsmathenv@before{alignat}}
98
99 \AfterEndEnvironment{alignat}{\LWR@amsmathenv@after{alignat}}
```

Env alignat*

```
100 \BeforeBeginEnvironment{alignat*}{\LWR@amsmathenv@before*{alignat*}}
101
102 \AfterEndEnvironment{alignat*}{\LWR@amsmathenv@after*{alignat*}}
```

```
103 \AtBeginEnvironment{subequations}{
104     \renewcommand*{\theMathJaxsubequations}{1}
105     \renewcommand*{\theMathJaxsection}{\theparentequation}
106     \renewcommand*{\theMathJaxequation}{\arabic{equation}}
107 }
```

For MathJax:

```
108 \begin{warpMathJax}
109 \CustomizeMathJax{\newcommand{\intertext}[1]{\text{#1}\notag \\}}
110 \CustomizeMathJax{\let\Hat\hat}
111 \CustomizeMathJax{\let\Check\check}
112 \CustomizeMathJax{\let\Tilde\tilde}
113 \CustomizeMathJax{\let\Acute\acute}
114 \CustomizeMathJax{\let\Grave\grave}
115 \CustomizeMathJax{\let\Dot\dot}
116 \CustomizeMathJax{\let\Ddot\ddot}
117 \CustomizeMathJax{\let\Breve\breve}
```

```
\CustomizeMathJax{\let\Bar\bar}
\CustomizeMathJax{\let\Vec\vec}
\end{warpMathJax}
```

File 22 **lwarp-amsthm.sty**

§ 130 Package

amsthm

(*Emulates or patches code by* Publications Technical Group — American Mathematical Society.)

The original source code is located in amsclass.dtx, and printed in amsclass.pdf.

Pkg amsthm amsthm is patched for use by lwarp.

Table 18: amsthm package — css styling of theorems and proofs

Theorem: of class amsthmbody<theoremstyle>

Theorem Name: of class amsthmname<theoremtyle>

Theorem Number: of class amsthmnumber<theoremstyle>

Theorem Note: of class amsthmnote<theoremstyle>

Proof: of class amsthmproof

Proof Name: of class amsthmproofname

where <theoremstyle> is plain, definition, etc.

for HTML output: amsthm must be loaded before mdframed:

```
\@ifpackageloaded{mdframed}{
    \PackageError{lwarp}
    {%
        Package mdframed must be loaded after package amsthm.\MessageBreak
        Enter 'H' for solutions%
    }
    {%
        Move ``\protect\usepackage{amsthm}'' before
        ``\protect\usepackage{mdframed}''.\MessageBreak
        Package amsthm may be loaded by something else,\MessageBreak
        which must also be moved before mdframed.%
    }
}
{\relax}
```

Necessary for \text, used by \openbox, etc., below:

```
\RequirePackage{amsmath}
```

```
\LWR@ProvidesPackagePass{amsthm}[2017/10/31]
```

Storage for the style being used for new theorems:

```
\newcommand{\LWR@newtheoremstyle}{plain}
```

Patched to remember the style being used for new theorems:

```
\renewcommand{\theoremstyle}[1]{%
  \@ifundefined{th@#1}{%
    \PackageWarning{amsthm}{Unknown theoremstyle `#1'}%
    \thm@style{plain}%
    \renewcommand{\LWR@newtheoremstyle}{plain}% lwarp
  }{%
    \thm@style{#1}%
    \renewcommand{\LWR@newtheoremstyle}{#1}% lwarp
  }%
}
```

Patched to remember the style for this theorem type:

```
\def\@xnthm#1#2{%
  \csedef{LWR@thmstyle#2}{\LWR@newtheoremstyle}% lwarp
  \let\@tempa\relax
  \@xp\@ifdefinable\csname #2\endcsname{%
    \global\@xp\let\csname end#2\endcsname\@endtheorem
    \ifx *#1% unnumbered, need to get one more mandatory arg
      \edef\@tempa##1{%
        \gdef\@xp\@nx\csname#2\endcsname{%
          \@nx\@thm{\@xp\@nx\csname th@\the\thm@style\endcsname}%
            {}{##1}}}%
    \else % numbered theorem, need to check for optional arg
      \def\@tempa{\@oparg{\@ynthm{#2}}[]}%
    \fi
    \AtBeginEnvironment{#2}{%
        \edef\LWR@thisthmstyle{\@nameuse{LWR@thmstyle#2}}%
    }%          lwarp
  }%
  \@tempa%
}
```

Patched to enclose with css:

```
\newcommand{\LWR@haveamsthmname}{
    \renewcommand{\thmname}[1]{%
        \InlineClass{amsthmname\LWR@thisthmstyle}{##1}%
    }
}

\newcommand{\LWR@haveamsthmnumber}{
    \renewcommand{\thmnumber}[1]{%
        \InlineClass{amsthmnumber\LWR@thisthmstyle}{##1}%
    }
}

\newcommand{\LWR@haveamsthmnote}{
    \renewcommand{\thmnote}[1]{%
```

```
        \InlineClass{amsthmnote\LWR@thisthmstyle}{##1}%
    }
}

\LWR@haveamsthmname
\LWR@haveamsthmnumber
\LWR@haveamsthmnote
```

Patched for css:

```
\def\@begintheorem#1#2[#3]{%

    \GetTitleString{#3}%                                    lwarp
    \let\@currentlabelname\GetTitleStringResult%            lwarp
    \item[%

    \LWR@newautopagelabel{page}%

%   \deferred@thm@head{
%     \the\thm@headfont \thm@indent
    \@ifempty{#1}{\let\thmname\@gobble}{\LWR@haveamsthmname}%       lwarp
    \@ifempty{#2}{\let\thmnumber\@gobble}{\LWR@haveamsthmnumber}%   lwarp
    \@ifempty{#3}{\let\thmnote\@gobble}{\LWR@haveamsthmnote}%       lwarp
    \thm@swap\swappedhead\thmhead{#1}{#2}{#3}%
    \the\thm@headpunct % space
    \thmheadnl % possibly a newline.
    \hskip\thm@headsep
%   }%
    ]%
  \ignorespaces}
```

Patched for css:

```
\def\@thm#1#2#3{%
  \ifhmode\unskip\unskip\par\fi
  \normalfont
  \LWR@forcenewpage%                            lwarp

  \LWR@printpendingfootnotes%                   lwarp

  \BlockClass{amsthmbody\LWR@thisthmstyle}%     lwarp
```

Footnotes are redefined to work correctly inside the option brackets for a theorem environment.

```
    \renewcommand{\footnote}[1][]{%
        \ifblank{##1}%
        {%
            \stepcounter\@mpfn
            \protected@xdef\@thefnmark{\thempfn}%
            \@footnotemark\@footnotetext
        }%
        {%
```

```
            \begingroup
            \csname c@\@mpfn\endcsname ##1\relax
            \unrestored@protected@xdef\@thefnmark{\thempfn}%
            \endgroup
            \@footnotemark\@footnotetext
        }%
    }%
%
    \renewcommand{\footnotemark}[1][]{%
        \ifblank{##1}%
        {%
            \stepcounter{footnote}%
            \protected@xdef\@thefnmark{\thefootnote}%
            \@footnotemark%
        }%
        {%
            \begingroup%
            \c@footnote ##1\relax%
            \unrestored@protected@xdef\@thefnmark{\thefootnote}%
            \endgroup%
            \@footnotemark%
        }%
    }%
%
  \trivlist
  \let\thmheadnl\relax
  \let\thm@swap\@gobble
  \thm@notefont{\fontseries\mddefault\upshape}%
  \thm@headpunct{.}% add period after heading
  \thm@headsep 5\p@ plus\p@ minus\p@\relax
  \thm@space@setup
  #1% style overrides
  \@topsep \thm@preskip               % used by thm head
  \@topsepadd \thm@postskip           % used by \@endparenv
  \def\@tempa{#2}\ifx\@empty\@tempa
    \def\@tempa{\@oparg{\@begintheorem{#3}{}}[]}%
  \else
    \refstepcounter{#2}%
    \def\@tempa{\@oparg{\@begintheorem{#3}{\csname the#2\endcsname}}[]}%
  \fi
  \@tempa%
}
```

cleveref patches `\@thm` to do `\cref@thmoptarg` if an optional argument is given. lwarp then patches `\cref@thmoptarg` `\AtBeginDocument`.

```
\AtBeginDocument{%
\def\cref@thmoptarg[#1]#2#3#4{%
    \ifhmode\unskip\unskip\par\fi%
    \normalfont%
    \LWR@forcenewpage%                          lwarp
    \LWR@printpendingfootnotes%                   lwarp
    \BlockClass{amsthmbody\LWR@thisthmstyle}%   lwarp
```

```
    \trivlist%
    \let\thmheadnl\relax%
    \let\thm@swap\@gobble%
    \thm@notefont{\fontseries\mddefault\upshape}%
    \thm@headpunct{.}% add period after heading
    \thm@headsep 5\p@ plus\p@ minus\p@\relax%
    \thm@space@setup%
    #2% style overrides
    \@topsep \thm@preskip               % used by thm head
    \@topsepadd \thm@postskip           % used by \@endparenv
    \def\@tempa{#3}\ifx\@empty\@tempa%
        \def\@tempa{\@oparg{\@begintheorem{#4}{}}[]}%
    \else%
        \refstepcounter[#1]{#3}%  <<< cleveref modification
        \def\@tempa{\@oparg{\@begintheorem{#4}{\csname the#3\endcsname}}[]}%
    \fi%
    \@tempa
}%
}% AtBeginDocument

\def\@endtheorem{%
    \endtrivlist%

  \LWR@printpendingfootnotes%                  lwarp

    \endBlockClass%
    \@endpefalse%
}
```

Proof QED symbol:

```
\AtBeginDocument{
\@ifundefined{LWR@orig@openbox}{
\LetLtxMacro\LWR@orig@openbox\openbox
\LetLtxMacro\LWR@orig@blacksquare\blacksquare
\LetLtxMacro\LWR@orig@Box\Box

\def\openbox{\text{\HTMLunicode{25A1}}}% UTF-8 white box
\def\blacksquare{\text{\HTMLunicode{220E}}}% UTF-8 end-of-proof
\def\Box{\text{\HTMLunicode{25A1}}}% UTF-8 white box

\appto\LWR@restoreorigformatting{%
    \LetLtxMacro\openbox\LWR@orig@openbox%
    \LetLtxMacro\blacksquare\LWR@orig@blacksquare%
    \LetLtxMacro\Box\LWR@orig@Box%
}% appto
}{}% @ifundefined
}% AtBeginDocument
```

Patched for css:

```
\renewenvironment{proof}[1][\proofname]{\par
  \LWR@forcenewpage% lwarp
```

```
\LWR@printpendingfootnotes%                    lwarp

  \BlockClass{amsthmproof}% lwarp
  \LWR@newautopagelabel{page}%
\pushQED{\qed}%
\normalfont \topsep6\p@\@plus6\p@\relax
\trivlist
\item[
      \InlineClass{amsthmproofname}{#1\@addpunct{.}}]\ignorespaces% changes
}{%
\InlineClass{theoremendmark}{\popQED}\endtrivlist%

\LWR@printpendingfootnotes%                    lwarp

\endBlockClass% lwarp
\@endpefalse
}
```

File 23 **lwarp-anonchap.sty**

§ 131 Package

anonchap

(*Emulates or patches code by* Peter Wilson.)

Pkg anonchap anonchap is emulated.

Pkg tocloft

⚠ tocloft & other packages

If using tocloft with tocbibind, anonchap, fncychap, or other packages which change chapter title formatting, load tocloft with its `titles` option, which tells tocloft to use standard LaTeX commands to create the titles, allowing other packages to work with it.

The code is shared by tocbibind.

for HTML output:

```
\LWR@ProvidesPackageDrop{anonchap}[2009/08/03]

\newcommand{\simplechapter}[1][\@empty]{%
    \def\@chapcntformat##1{%
        #1~\csname the##1\endcsname\simplechapterdelim\quad%
    }%
}

\newcommand{\restorechapter}{%
\let\@chapcntformat\@seccntformat%
}
```

File 24 **lwarp-anysize.sty**

§ 132 Package

anysize

(*Emulates or patches code by* Michael Salzenberg, Thomas Esser.)

Pkg anysize anysize is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{anysize}[1994/08/13]

\def\papersize#1#2{}
\def\marginsize#1#2#3#4{}
```

File 25 **lwarp-appendix.sty**

§ 133 Package

appendix

(*Emulates or patches code by* Peter Wilson.)

Pkg appendix appendix is patched for use by lwarp.

⚠ incorrect TOC link During HTML conversion, the option `toc` without the option `page` results in a TOC link to whichever section was before the `appendices` environment. It is recommended to use both `toc` and also `page` at the same time.

for HTML output:

```
\LWR@ProvidesPackagePass{appendix}[2009/09/02]

\renewcommand*{\@chap@pppage}{%
\part*{\appendixpagename}
 \if@dotoc@pp
 \addappheadtotoc
 \fi
}

\renewcommand*{\@sec@pppage}{%
\part*{\appendixpagename}
 \if@dotoc@pp
 \addappheadtotoc
 \fi
}
```

File 26 **lwarp-ar.sty**

§ 134 Package

ar

(*Emulates or patches code by* Agostino De Marco.)

Pkg ar ar is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{ar}[2012/01/23]
```

Measure and print the width of the supplied glyph.

```
\newlength{\LWR@ar@width}

\newcommand*{\LWR@ar@printwidth}[1]{%
```

```
    \setlength{\LWR@ar@width}{\widthof{#1}}%
    width:%
    \LWR@convertto{em}{\the\LWR@ar@width}em%
}
```

The HTML version of \AR:

```
\newrobustcmd*{\LWR@HTML@AR}{%
```

Start a hashed `lateximage`, additionally hashed by the font series, with a width depending on the given glyph:

```
    \begin{lateximage}*[AR][\LWR@f@series][\LWR@ar@printwidth{\LWR@print@AR}]%
```

For text mode, set the font series according to the HTML font series:

```
    \ifmmode\else\csuse{LWR@orig\LWR@f@series series}\fi%
```

Print the original glyph using the newly set font series:

```
    \LWR@print@AR%
```

Done.

```
    \end{lateximage}%
}
```

Combine the print and HTML versions:

```
\LWR@formatted{AR}

\newrobustcmd*{\LWR@HTML@ARb}{%
    \begin{lateximage}*[AR][b][\LWR@ar@printwidth{\LWR@print@ARb}]%
    \LWR@print@ARb%
    \end{lateximage}%
}
\LWR@formatted{ARb}

\newrobustcmd*{\LWR@HTML@ARss}{%
   \begin{lateximage}*[ARss][\LWR@f@series][\LWR@ar@printwidth{\LWR@print@ARss}]%
    \ifmmode\else\csuse{LWR@orig\LWR@f@series series}\fi%
    \LWR@print@ARss%
    \end{lateximage}%
}
\LWR@formatted{ARss}

\newrobustcmd*{\LWR@HTML@ARssb}{%
    \begin{lateximage}*[AR][ssb][\LWR@ar@printwidth{\LWR@print@ARssb}]%
    \LWR@print@ARssb%
    \end{lateximage}%
}
\LWR@formatted{ARssb}

\newrobustcmd*{\LWR@HTML@ARtt}{%
```

```
    \begin{lateximage}*[AR][tt][\LWR@ar@printwidth{\LWR@print@ARtt}]%
    \LWR@print@ARtt%
    \end{lateximage}%
}
\LWR@formatted{ARtt}
```

For MathJax:

```
\begin{warpMathJax}
\CustomizeMathJax{\newcommand{\AR}{\mathit{A\!\!R}}}
\CustomizeMathJax{\newcommand{\ARb}{\boldsymbol{A\!\!R}}}
\end{warpMathJax}
```

File 27 **lwarp-arabicfront.sty**

§ 135 Package arabicfront

Pkg arabicfront arabicfront is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{arabicfront}[2006/09/03]
```

File 28 **lwarp-array.sty**

§ 136 Package array

Pkg array array is used as-is for print output, and emulated for HTML.

plarray and plextarray do not affect `\firsthline` or `\lasthline`, and so are not affected by the following.

for HTML output: Remove the default nullfied macros:

```
\let\firsthline\relax
\let\lasthline\relax

\LWR@ProvidesPackagePass{array}[2018/12/30]

\newcommand*{\LWR@HTML@firsthline}{\LWR@HTMLhline}%
\LWR@expandableformatted{firsthline}

\newcommand*{\LWR@HTML@lasthline}{\LWR@HTMLhline}%
\LWR@expandableformatted{lasthline}


\providecommand*{\LWR@HTML@tabularnewline}{\LWR@tabularendofline}
\LWR@formatted{tabularnewline}
```

For MathJax:

```
\CustomizeMathJax{
    \newcommand{\multicolumn}[3]{#3}% only uses one cell
}
```

File 29 **lwarp-arydshln.sty**

§ 137 Package

arydshln

(*Emulates or patches code by* Hiroshi Nakashima.)

Pkg arydshln

arydshln heavily patches tabular code, so the actual package is not used. arydshln is emulated for HTML `tabular`, and reverts to solid rules for SVG math `array` and `tabular` in a `lateximage`.

CSS is not able to display a double-dashed border, so a single-dashed rule is displayed as a single-dashed border, and a double-dashed rule is displayed as a thicker single-dashed border.

For MathJax, limited emulation is provided for math mode.

for HTML output:

array is required to allow `\newcolumn` below.

```
\RequirePackage{array}
```

```
\LWR@ProvidesPackageDrop{arydshln}[2018/09/26]
```

Ignored, but included for source compatibility:

```
\newdimen\dashlinedash \dashlinedash4pt %
\newdimen\dashlinegap \dashlinegap4pt %
\let\hdashlinewidth\dashlinedash
\let\hdashlinegap\dashlinegap

\def\ADLnullwide{}
\def\ADLsomewide{}
\def\ADLnullwidehline{}
\def\ADLsomewidehline{}

\def\ADLactivate{}
\def\ADLinactivate{}
\newcommand*{\ADLdrawingmode}[1]{}
\newcommand*{\ADLnoshorthanded}{}
\newcommand*{\dashgapcolor}[2][]{}
\newcommand*{\nodashgapcolor}{}
```

In a `lateximage`, revert to solid vertical rules:

```
\appto\LWR@restoreorigformatting{%
\newcolumntype{:}{|}%
\newcolumntype{;}[1]{|}%
\LetLtxMacro\hdashline\hline%
}
```

Some of these macros are already defined as temporary placeholders in the lwarp core, so they must be redefined here.

The emulated defaults also work for an emulated print mode inside a `lateximage`:

```
\def\hdashline{
%     \adl@hdashline\adl@ihdashline
    \adl@hdashline\adl@inactivehdl
}
\def\adl@hdashline#1{\noalign{\ifnum0=`}\fi
%         \ifadl@zwhrule \vskip-\arrayrulewidth
%         \else
%             \adl@hline\adl@connect\arrayrulewidth
                \hrule \@height \arrayrulewidth% lwarp
%         \fi
        \@ifnextchar[%]
                    {#1}%
                    {#1[%
%                         \dashlinedash/\dashlinegap
                       1pt/1pt
                    ]}}
% \def\adl@ihdashline[#1/#2]{\ifnum0=`{\fi}%
%         \multispan{\adl@columns}\unskip \adl@hcline\z@[#1/#2]%
%         \noalign{\ifnum0=`}\fi
%         \futurelet\@tempa\adl@xhline}
\def\adl@inactivehdl[#1/#2]{
%         \ifadl@zwhrule \vskip-\arrayrulewidth \fi
        \hrule\@height\arrayrulewidth
        \futurelet\@tempa\adl@xhline}
\def\adl@xhline{\ifx\@tempa\hline \adl@ixhline\fi
        \ifx\@tempa\hdashline \adl@ixhline\fi
        \ifnum0=`{\fi}}
\def\adl@ixhline{\vskip\doublerulesep \adl@hline\relax\doublerulesep}
\def\adl@hline#1#2{%
% \@tempcnta#2
%         \global\advance\adl@totalheight\@tempcnta
%         \xdef\adl@rowsL{\adl@rowsL
%                 (#1/\number\@tempcnta);}%
%         \xdef\adl@rowsR{\adl@rowsR
%                 (#1/\number\@tempcnta);}
}

\def\cdashline#1{\noalign{\ifnum0=`}\fi
        \@ifnextchar[%]
%                       {\adl@cdline[#1]}%
%                       {\adl@cdline[#1][\dashlinedash/\dashlinegap]}
                      {\adl@inactivecdl[#1]}%
                      {\adl@inactivecdl[#1][\dashlinedash/\dashlinegap]}
}

\def\adl@inactivecdl[#1-#2][#3]{\ifnum0=`{\fi}\cline{#1-#2}}


\begin{warpMathJax}
\CustomizeMathJax{\newcommand{\firsthdashline}[1][]{\hdashline}}
\CustomizeMathJax{\let\lasthdashline\firsthdashline}
\CustomizeMathJax{\let\cdashline\cline}
\end{warpMathJax}
```

File 30 **lwarp-asymptote.sty**

§ 138 Package asymptote

(*Emulates or patches code by* Andy Hammerlindl, John Bowman, Tom Prince.)

Pkg asymptote asymptote is patched for use by lwarp.

To compile:

```
pdflatex project.tex
asy project-*.asy
pdflatex project.tex

lwarpmk print
asy project-*.asy
lwarpmk print1
lwarpmk print1

lwarpmk html
asy project_html-*.asy
lwarpmk html1
lwarpmk html1
lwarpmk limages
```

for HTML output:

```
\LWR@ProvidesPackagePass{asymptote}[2016/11/26]

\BeforeBeginEnvironment{asy}{%
    \begin{lateximage}[-asymptote-~\PackageDiagramAltText]%
}
\AfterEndEnvironment{asy}{\end{lateximage}}

\xpatchcmd{\asyinclude}
    {\begingroup}
    {\begin{lateximage}[-asymptote-~\PackageDiagramAltText]}
    {}
    {\LWR@patcherror{asymptote}{asyinclude-begingroup}}

\xpatchcmd{\asyinclude}
    {\endgroup}
    {\end{lateximage}}
    {}
    {\LWR@patcherror{asymptote}{asyinclude-endgroup}}
```

File 31 **lwarp-atbegshi.sty**

§ 139 Package atbegshi

(*Emulates or patches code by* Heiko Oberdiek.)

Pkg atbegshi atbegshi is ignored.

for HTML output: Discard all options for lwarp-atbegshi:

```
\LWR@ProvidesPackageDrop{atbegshi}[2011/10/05]

\let\AtBeginShipout\relax
\let\AtBeginShipoutNext\relax
\let\AtBeginShipoutFirst\relax
\let\AtBeginShipoutDiscard\relax
\let\AtBeginShipoutInit\relax
\let\AtBeginShipoutAddToBox\relax
\let\AtBeginShipoutAddToBoxForeground\relax
\let\AtBeginShipoutUpperLeft\relax
\let\AtBeginShipoutUpperLeftForeground\relax
\let\AtBeginShipoutOriginalShipout\relax

\newcommand*{\AtBeginShipout}[1]{}
\newbox\AtBeginShipoutBox
\newcommand*{\AtBeginShipoutNext}[1]{}
\newcommand*{\AtBeginShipoutFirst}[1]{}
\newcommand*{\AtBeginShipoutDiscard}{}
\newcommand*{\AtBeginShipoutInit}{}
\newcommand*{\AtBeginShipoutAddToBox}[1]{}
\newcommand*{\AtBeginShipoutAddToBoxForeground}[1]{}
\newcommand*{\AtBeginShipoutUpperLeft}[1]{}
\newcommand*{\AtBeginShipoutUpperLeftForeground}[1]{}
\newcommand*{\AtBeginShipoutOriginalShipout}[1]{}
\def\AtBeginShipoutBoxWidth{0pt}
\def\AtBeginShipoutBoxHeight{0pt}
\def\AtBeginShipoutBoxDepth{0pt}
```

File 32 **lwarp-attachfile.sty**

§ 140 Package

attachfile

(*Emulates or patches code by* Scott Pakin.)

Pkg attachfile attachfile is patched for use by lwarp.

⚠ Metadata is ignored for now.

for HTML output:

```
\LWR@ProvidesPackagePass{attachfile}[2016/09/18]
```

Encloses each icon:

```
\newenvironment*{LWR@attachfile@icon}
{
    \begin{lateximage}*%
        [-attachfile-]%
        [%
            \detokenize\expandafter{\atfi@icon@icon}-%
            \detokenize\expandafter{\atfi@color@rgb}%
```

```
        ]%
}
{
    \end{lateximage}
}
```

Each icon is enclosed inside a LWR@attachfile@icon environment:

```
\xpretocmd{\atfi@acroGraph}{\LWR@attachfile@icon}{}{}
\xapptocmd{\atfi@acroGraph}{\endLWR@attachfile@icon}{}{}

\xpretocmd{\atfi@acroPaperclip}{\LWR@attachfile@icon}{}{}
\xapptocmd{\atfi@acroPaperclip}{\endLWR@attachfile@icon}{}{}

\xpretocmd{\atfi@acroPushPin}{\LWR@attachfile@icon}{}{}
\xapptocmd{\atfi@acroPushPin}{\endLWR@attachfile@icon}{}{}

\xpretocmd{\atfi@acroTag}{\LWR@attachfile@icon}{}{}
\xapptocmd{\atfi@acroTag}{\endLWR@attachfile@icon}{}{}
```

Disable PDF file embedding:

```
\DeclareRobustCommand{\atfi@embedfile}[1]{}
```

The displayed output for an \attachfile reference:

```
\newcommand*{\LWR@attachfile@appearance}{}

\DeclareRobustCommand{\atfi@set@appearance}[1]{%
    \def\LWR@attachfile@appearance{#1}%
}
```

A file annotation becomes a reference:

```
\DeclareRobustCommand{\atfi@insert@file@annot}[1]{%
    \LWR@href{#1}{\LWR@attachfile@appearance}%
}
```

File 33 **lwarp-attachfile2.sty**

§ 141 Package

attachfile2

(*Emulates or patches code by* Heiko Oberdiek.)

Pkg attachfile2 attachfile2 is patched for use by lwarp.

⚠ Metadata is ignored for now.

for HTML output:

```
\LWR@ProvidesPackagePass{attachfile2}[2016/05/16]
```

Adds memory of the selected color:

```
\def\LWR@attachfiletwo@color{}%

\define@key{AtFi}{color}{%
    \def\LWR@attachfiletwo@color{#1}%   lwarp
  \HyColor@AttachfileColor{#1}%
          \atfi@color@tex\atfi@color@inline\atfi@color@annot
          {attachfile2}{color}%
}
```

Encloses each icon:

```
\newenvironment*{LWR@attachfile@icon}
{
    \begin{lateximage}*%
        [-attachfile-]%
        [%
            \detokenize\expandafter{\atfi@icon@icon}-%
            \detokenize\expandafter{\LWR@attachfiletwo@color}%
        ]%
}
{
    \end{lateximage}
}
```

Each icon is enclosed inside a `LWR@attachfile@icon` environment:

```
\xpretocmd{\atfi@acroGraph}{\LWR@attachfile@icon}{}{}
\xapptocmd{\atfi@acroGraph}{\endLWR@attachfile@icon}{}{}

\xpretocmd{\atfi@acroPaperclip}{\LWR@attachfile@icon}{}{}
\xapptocmd{\atfi@acroPaperclip}{\endLWR@attachfile@icon}{}{}

\xpretocmd{\atfi@acroPushPin}{\LWR@attachfile@icon}{}{}
\xapptocmd{\atfi@acroPushPin}{\endLWR@attachfile@icon}{}{}

\xpretocmd{\atfi@acroTag}{\LWR@attachfile@icon}{}{}
\xapptocmd{\atfi@acroTag}{\endLWR@attachfile@icon}{}{}
```

Disable PDF file embedding:

```
\DeclareRobustCommand{\atfi@embedfile}[1]{}
```

The displayed output for an `\attachfile` reference:

```
\newcommand*{\LWR@attachfile@appearance}{}

\def\atfi@set@appearance@icon{%
    \atfi@set@appearance{\csname atfi@acro\atfi@icon@icon\endcsname}%
}

\DeclareRobustCommand{\atfi@set@appearance}[1]{%
    \def\LWR@attachfile@appearance{#1}%
}
```

A file annotation becomes a reference:

```
\DeclareRobustCommand{\atfi@insert@file@annot}[1]{%
    \LWR@href{#1}{\LWR@attachfile@appearance}%
}
```

Modified for text color:

```
\DeclareRobustCommand{\notextattachfile}[2][]{%
  \begingroup
    \atfi@setup{#1}%
    \ifatfi@print
      \leavevmode
      \begingroup
        \HyColor@UseColor\atfi@color@tex
        \LWR@textcurrentcolor{#2}%      lwarp
% \strut
      \endgroup
%     \else
%       \sbox\ltx@zero{#2\strut}%
%       \makebox[\wd0]{}%
    \fi
  \endgroup
}
```

Modified to draw the icon:

```
\DeclareRobustCommand{\noattachfile}[1][]{%
  \begingroup
    \atfi@setup{#1}%
    \atfi@set@appearance@icon
    \ifatfi@print
        \LWR@attachfile@appearance%     lwarp
%       \expandafter
%       \atfi@refxform\csname atfi@appobj@\atfi@icon@icon\endcsname
%     \else
%       \makebox[\atfi@appearancewidth]{}%
    \fi
  \endgroup
}
```

File 34 **lwarp-authblk.sty**

§ 142 Package

authblk

(*Emulates or patches code by* Patrick W. Daly.)

Pkg authblk authblk is patched for HTML.

package support ⚠ load order lwarp supports the native LaTeX titling commands, and also supports the packages authblk and titling. If both are used, authblk should be loaded before titling.

\published and \subtitle If using the titling package, additional titlepage fields for \published and \subtitle may

be added by using \AddSubtitlePublished in the preamble. See section 69.8.

(*Emulates or patches code by* Patrick W. Daly.)

for HTML output: Require that authblk be loaded before titling:

```
\@ifpackageloaded{titling}{
    \PackageError{lwarp-authblk}
        {Package authblk must be loaded before titling}
        {%
            Titling appends authblk's author macro,
            so authblk must be loaded first.%
        }
}
{\relax}
```

Load authblk:

```
\LWR@ProvidesPackagePass{authblk}[2001/02/27]
```

Patch to add a class for the affiliation:

```
\LetLtxMacro\LWRAB@affil\affil

\renewcommand{\affil}[2][]{%
\LWRAB@affil[#1]{\protect\InlineClass{affiliation}{#2}}
}
```

Create an HTML break for an \authorcr:

```
\renewcommand*{\authorcr}{\protect\LWR@newlinebr}
```

File 35 **lwarp-autobreak.sty**

§ 143 Package

autobreak

(*Emulates or patches code by* Takahiro Ueda.)

Pkg autobreak autobreak is used as-is for SVG math, and nullified for MathJax.

for HTML output:

```
\LWR@ProvidesPackagePass{autobreak}[2017/02/23]
```

For MathJax. The modified align environment is used for SVG math, but is reverted to its original for MathJax. (Extraneous commas were appearing in the result.)

```
\begin{warpMathJax}
\renewenvironment{autobreak}{\newcommand{\MoveEqLeft}[1]{}}{}
\let\start@align\@autobreak@oldstart@align
\let\endalign\@autobreak@oldendalign
\CustomizeMathJax{\newenvironment{autobreak}{}{}}
\CustomizeMathJax{\newcommand{\MoveEqLeft}[1][]{}}
\CustomizeMathJax{\newcommand{\everybeforeautobreak}[1]{}}
\CustomizeMathJax{\newcommand{\everyafterautobreak}[1]{}}
\end{warpMathJax}
```

File 36 **lwarp-autonum.sty**

§ 144 Package

autonum

Pkg autonum autonum is ignored.

⚠ numbering All equations are numbered in HTML output.

MathJax does not support the "+" environments.

for HTML output:

```
\LWR@ProvidesPackageDrop{autonum}[2015/01/18]

\RequirePackage{amsmath}


\newenvironment{equation+}{\equation}{\endequation}


\newenvironment{gather+}{\gather}{\endgather}

\BeforeBeginEnvironment{gather+}{\LWR@amsmathenv@@before{gather+}}

\AfterEndEnvironment{gather+}{\LWR@amsmathenv@@after}


\newenvironment{multline+}{\multline}{\endmultline}

\BeforeBeginEnvironment{multline+}{\LWR@amsmathenv@@before{multline+}}

\AfterEndEnvironment{multline+}{\LWR@amsmathenv@@after}


\newenvironment{flalign+}{\flalign}{\endflalign}

\BeforeBeginEnvironment{flalign+}{\LWR@amsmathenv@@before{flaline+}}

\AfterEndEnvironment{flalign+}{\LWR@amsmathenv@@after}


\newenvironment{align+}{\align}{\endalign}

\BeforeBeginEnvironment{align+}{\LWR@amsmathenv@@before{aline+}}

\AfterEndEnvironment{align+}{\LWR@amsmathenv@@after}


\newenvironment{alignat+}{\alignat}{\endalignat}

\BeforeBeginEnvironment{alignat+}{\LWR@amsmathenv@@before{alineat+}}

\AfterEndEnvironment{alignat+}{\LWR@amsmathenv@@after}

```

```
42
43 \newenvironment{split+}{\split}{\endsplit}
```

File 37 **lwarp-awesomebox.sty**

§ 145 Package awesomebox

(*Emulates or patches code by* Étienne Deparis.)

Pkg awesomebox awesomebox is patched for use by lwarp.

for HTML output:

```
1 \LWR@ProvidesPackagePass{awesomebox}[2019/07/27]

2 \newcommand*{\LWR@awesomebox@boxborders}{}%
3 \newcommand*{\LWR@awesomebox@contentsborders}{}%
4
5 \newcommand*{\LWR@awesomebox@ruleborders}{%
6     border-top: 1px solid black ;
7     border-bottom: 1px solid black%
8 }
9
10 % \awesomebox[1:vrulecolor][2:hrule][3:title]{4:vrulewidth}{5:icon}{6:iconcolor}{7:content}
11 \RenewDocumentCommand \awesomebox { O{abvrulecolor} O{} o m m m +m }{%
12     \begin{awesomeblock}[#1][#2][#3]{#4}{#5}{#6}
13     #7
14     \end{awesomeblock}
15 }
16
17 % \begin{awesomeblock}[1:vrulecolor][2:hrule][3:title]{4:vrulewidth}{5:icon}{6:iconcolor}
18 % <contents>
19 % \end{awesomeblock}
20 \RenewDocumentEnvironment{awesomeblock}{ O{abvrulecolor} O{} o m m m }
21 {%
22     \LWR@forceminwidth{#4}%
23     \convertcolorspec{named}{#1}{HTML}\LWR@tempcolor%
24     \renewcommand*{\LWR@awesomebox@boxborders}{}%
25     \renewcommand*{\LWR@awesomebox@contentsborders}{}%
26     \ifdefstrequal{\abShortLine}{#2}{%
27       \renewcommand*{\LWR@awesomebox@contentsborders}{\LWR@awesomebox@ruleborders}%
28     }{}%
29     \ifdefstrequal{\abLongLine}{#2}{%
30       \renewcommand*{\LWR@awesomebox@boxborders}{\LWR@awesomebox@ruleborders}%
31     }{}%
32     \begin{BlockClass}[\LWR@awesomebox@boxborders]{awesomebox}
33     \begin{BlockClass}[%
34         margin-left: 2\% ;
35         vertical-align: top
36     ]{minipage}
37         \color{#6}\Huge #5
38     \end{BlockClass}
39     \begin{BlockClass}[%
40         width:75\% ;
41         vertical-align: top ;
```

```
        padding-left: 1em ;
        \LWR@awesomebox@contentsborders ;
        border-left: \LWR@printlength{\LWR@atleastonept} %
            solid \LWR@origpound\LWR@tempcolor%
    ]{minipage}
        \IfValueTF{#3}{#3\newline}{}
}
{%
    \end{BlockClass}
    \end{BlockClass}
}
```

File 38 **lwarp-axessibility.sty**

§ 146 Package

axessibility

Pkg axessibility

axessibility is ignored.

for HTML output:

```
\PackageInfo{lwarp}{Using the lwarp version of package ‘axessibility’.}%
\ProvidesPackage{lwarp-axessibility}% no date is declared by the original

\newif\iftagpdfopt

\DeclareOption{accsupp}{
  \tagpdfoptfalse
}

\DeclareOption{tagpdf}{
  \tagpdfopttrue
}

\ProcessOptions\relax

\iftagpdfopt
    \RequirePackage{tagpdf}
\else
    \RequirePackage{accsupp}
\fi

\long\def\wrap#1{}
\long\def\wrapml#1{}
\long\def\wrapmlstar#1{}
\long\def\wrapmlalt#1{}
```

For MathJax. These usually will not be needed.

```
\begin{warpMathJax}
\CustomizeMathJax{\newcommand{\wrap}[1]{}}
\CustomizeMathJax{\newcommand{\wrapml}[1]{}}
\CustomizeMathJax{\newcommand{\wrapmlstar}[1]{}}
\CustomizeMathJax{\newcommand{\wrapmlalt}[1]{}}
\end{warpMathJax}
```

File 39 **lwarp-axodraw2.sty**

§ 147 Package axodraw2

(*Emulates or patches code by* John C. Collins, J.A.M. Vermaseren.)

Pkg axodraw2 axodraw2 is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{axodraw2}[2018/02/15]

\BeforeBeginEnvironment{axopicture}{%
    \begin{lateximage}[-axopicture-~\PackageDiagramAltText]%
}

\AfterEndEnvironment{axopicture}{\end{lateximage}}
```

File 40 **lwarp-backnaur.sty**

§ 148 Package backnaur

(*Emulates or patches code by* Adrian P. Robson.)

Pkg backnaur backnaur is patched for use by lwarp, and emulated for MathJax.

for HTML output:

```
\LWR@ProvidesPackagePass{backnaur}[2019/06/18]

\renewenvironment{bnf}{\eqnarray}{\endeqnarray}
\renewenvironment{bnf*}{\csuse{eqnarray*}}{\csuse{endeqnarray*}}
```

For MathJax:

```
\begin{warpMathJax}
\CustomizeMathJax{\newcommand{\bnfpn}[1]{\langle \text{\textrm{#1}} \rangle}}
\CustomizeMathJax{\newcommand{\bnfor}{\; \mid \;}}
\CustomizeMathJax{\newcommand{\bnfsp}{\;}}
\@ifpackagewith{backnaur}{perp}{
    \CustomizeMathJax{\newcommand{\bnfes}{\perp}}
}{
    \@ifpackagewith{backnaur}{epsilon}{
        \CustomizeMathJax{\newcommand{\bnfes}{\epsilon}}
    }{
        \CustomizeMathJax{\newcommand{\bnfes}{\lambda}}
    }
}
\@ifpackagewith{backnaur}{tsrm}{
    \CustomizeMathJax{\newcommand{\bnfts}[1]{\text{#1}}}
}{
    \CustomizeMathJax{\newcommand{\bnfts}[1]{\text{\texttt{#1}}}}
}
```

```
\CustomizeMathJax{\newcommand{\bnftd}[1]{\text{\textit{#1}}}}
\CustomizeMathJax{\newcommand{\bnfsk}{\dots}}
\@ifpackagewith{backnaur}{altpo}{
    \CustomizeMathJax{\newcommand{\bnfpo}{::=}}
}{
    \CustomizeMathJax{\newcommand{\bnfpo}{\models}}
}
\CustomizeMathJax{\newcommand{\bnfprod}{\ifstar{\LWRbnfprodnn}{\LWRbnfprodyn}}}
\CustomizeMathJax{\newcommand{\LWRbnfprodyn}[2]{\bnfpn{#1} & \bnfpo & #2}}
\CustomizeMathJax{\newcommand{\LWRbnfprodnn}[2]{\nonumber \bnfpn{#1} & \bnfpo & #2}}
\CustomizeMathJax{\newcommand{\bnfmore}{\ifstar{\LWRbnfmorenn}{\LWRbnfmoreyn}}}
\CustomizeMathJax{\newcommand{\LWRbnfmoreyn}[1]{ &  & #1}}
\CustomizeMathJax{\newcommand{\LWRbnfmorenn}[1]{\nonumber &  & #1}}
\end{warpMathJax}
```

File 41 **lwarp-backref.sty**

§ 149 Package backref

(*Emulates or patches code by* David Carlisle and Sebastian Rahtz.)

Pkg backref backref is patched for use by lwarp.

⚠ loading Note that backref must be explicitly loaded, and is not automatically loaded by hyperref when generating HTML output.

for HTML output:

```
\LWR@ProvidesPackagePass{backref}[2016/05/21]
```

Force the hyperref option:

```
\def\backref{}

\long\def\hyper@section@backref#1#2#3{%
    \LWR@refwithsection{#3}%
}

\let\backrefxxx\hyper@section@backref
```

File 42 **lwarp-balance.sty**

§ 150 Package balance

(*Emulates or patches code by* Patrick W. Daly.)

Pkg balance balance is ignored.

for HTML output: Discard all options for lwarp-balance:

```
\LWR@ProvidesPackageDrop{balance}[1999/02/23]

\newcommand*{\balance}{}
\newcommand*{\nobalance}{}
```

File 43 **lwarp-bbding.sty**

§ 151 Package

bbding

(*Emulates or patches code by* Karel Horak, Peter Møller Neergaard.)

Pkg bbding bbding is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{bbding}[1999/04/15]

\newcommand*{\LWR@bbdingsymbol}[2]{\HTMLunicode{#2}}

\newcommand{\LWR@HTML@ScissorRightBrokenBottom}{\LWR@bbdingsymbol{000}   {2701}}
\newcommand{\LWR@HTML@ScissorRight}{\LWR@bbdingsymbol{001}               {2702}}
\newcommand{\LWR@HTML@ScissorRightBrokenTop}{\LWR@bbdingsymbol{002}     {2703}}
\newcommand{\LWR@HTML@ScissorLeftBrokenBottom}{\LWR@bbdingsymbol{003}   {2701}}
\newcommand{\LWR@HTML@ScissorLeft}{\LWR@bbdingsymbol{004}                {2702}}
\newcommand{\LWR@HTML@ScissorLeftBrokenTop}{\LWR@bbdingsymbol{005}      {2703}}
\newcommand{\LWR@HTML@ScissorHollowRight}{\LWR@bbdingsymbol{006}        {2704}}
\newcommand{\LWR@HTML@ScissorHollowLeft}{\LWR@bbdingsymbol{007}         {2704}}
\newcommand{\LWR@HTML@Phone}{\LWR@bbdingsymbol{010}                     {260E}}
\newcommand{\LWR@HTML@PhoneHandset}{\LWR@bbdingsymbol{011}              {2706}}
\newcommand{\LWR@HTML@Tape}{\LWR@bbdingsymbol{012}                      {2707}}
\newcommand{\LWR@HTML@Plane}{\LWR@bbdingsymbol{013}                     {2708}}
\newcommand{\LWR@HTML@Envelope}{\LWR@bbdingsymbol{014}                  {2709}}
\newcommand{\LWR@HTML@HandCuffRight}{\LWR@bbdingsymbol{015}             {261B}}
\newcommand{\LWR@HTML@HandCuffLeft}{\LWR@bbdingsymbol{016}              {261A}}
\newcommand{\LWR@HTML@HandCuffRightUp}{\LWR@bbdingsymbol{017}           {261D}}
\newcommand{\LWR@HTML@HandCuffLeftUp}{\LWR@bbdingsymbol{020}            {261F}}
\newcommand{\LWR@HTML@HandRight}{\LWR@bbdingsymbol{021}                 {261E}}
\newcommand{\LWR@HTML@HandLeft}{\LWR@bbdingsymbol{022}                  {261C}}
\newcommand{\LWR@HTML@HandRightUp}{\LWR@bbdingsymbol{023}               {261D}}
\newcommand{\LWR@HTML@HandLeftUp}{\LWR@bbdingsymbol{024}                {261F}}
\newcommand{\LWR@HTML@Peace}{\LWR@bbdingsymbol{025}                     {270C}}
\newcommand{\LWR@HTML@HandPencilLeft}{\LWR@bbdingsymbol{026}            {270D}}
\newcommand{\LWR@HTML@PencilRight}{\LWR@bbdingsymbol{027}               {270F}}
\newcommand{\LWR@HTML@PencilLeft}{\LWR@bbdingsymbol{030}                {270F}}
\newcommand{\LWR@HTML@PencilRightUp}{\LWR@bbdingsymbol{031}             {2710}}
\newcommand{\LWR@HTML@PencilLeftUp}{\LWR@bbdingsymbol{032}              {2710}}
\newcommand{\LWR@HTML@PencilRightDown}{\LWR@bbdingsymbol{033}           {270E}}
\newcommand{\LWR@HTML@PencilLeftDown}{\LWR@bbdingsymbol{034}            {270E}}
\newcommand{\LWR@HTML@NibRight}{\LWR@bbdingsymbol{035}                  {2711}}
\newcommand{\LWR@HTML@NibLeft}{\LWR@bbdingsymbol{036}                   {2711}}
\newcommand{\LWR@HTML@NibSolidRight}{\LWR@bbdingsymbol{037}             {2712}}
\newcommand{\LWR@HTML@NibSolidLeft}{\LWR@bbdingsymbol{040}              {2712}}
\newcommand{\LWR@HTML@Checkmark}{\LWR@bbdingsymbol{041}                 {2713}}
\newcommand{\LWR@HTML@CheckmarkBold}{\LWR@bbdingsymbol{042}             {2714}}
\newcommand{\LWR@HTML@XSolid}{\LWR@bbdingsymbol{043}                    {2715}}
\newcommand{\LWR@HTML@XSolidBold}{\LWR@bbdingsymbol{044}                {2716}}
\newcommand{\LWR@HTML@XSolidBrush}{\LWR@bbdingsymbol{045}               {2717}}
\newcommand{\LWR@HTML@PlusOutline}{\LWR@bbdingsymbol{046}               {2719}}
\newcommand{\LWR@HTML@Plus}{\LWR@bbdingsymbol{047}                      {271A}}
```

```
\newcommand{\LWR@HTML@PlusCenterOpen}{\LWR@bbdingsymbol{050}           {271C}}
\newcommand{\LWR@HTML@PlusThinCenterOpen}{\LWR@bbdingsymbol{051}       {271B}}
\newcommand{\LWR@HTML@Cross}{\LWR@bbdingsymbol{052}                    {271D}}
\newcommand{\LWR@HTML@CrossOpenShadow}{\LWR@bbdingsymbol{053}          {271E}}
\newcommand{\LWR@HTML@CrossOutline}{\LWR@bbdingsymbol{054}             {271F}}
\newcommand{\LWR@HTML@CrossBoldOutline}{\LWR@bbdingsymbol{055}         {271F}}
\newcommand{\LWR@HTML@CrossMaltese}{\LWR@bbdingsymbol{056}             {2720}}
\newcommand{\LWR@HTML@DavidStarSolid}{\LWR@bbdingsymbol{057}           {2721}}
\newcommand{\LWR@HTML@DavidStar}{\LWR@bbdingsymbol{060}                {2721}}
\newcommand{\LWR@HTML@FourAsterisk}{\LWR@bbdingsymbol{061}             {2722}}
\newcommand{\LWR@HTML@JackStar}{\LWR@bbdingsymbol{062}                 {2723}}
\newcommand{\LWR@HTML@JackStarBold}{\LWR@bbdingsymbol{063}             {2724}}
\newcommand{\LWR@HTML@CrossClowerTips}{\LWR@bbdingsymbol{064}          {2725}}
\newcommand{\LWR@HTML@FourStar}{\LWR@bbdingsymbol{065}                 {2726}}
\newcommand{\LWR@HTML@FourStarOpen}{\LWR@bbdingsymbol{066}             {2727}}
\newcommand{\LWR@HTML@FiveStarLines}{\LWR@bbdingsymbol{067}            {2729}}
\newcommand{\LWR@HTML@FiveStar}{\LWR@bbdingsymbol{070}                 {2605}}
\newcommand{\LWR@HTML@FiveStarOpen}{\LWR@bbdingsymbol{071}             {2729}}
\newcommand{\LWR@HTML@FiveStarOpenCircled}{\LWR@bbdingsymbol{072}      {272A}}
\newcommand{\LWR@HTML@FiveStarCenterOpen}{\LWR@bbdingsymbol{073}       {272B}}
\newcommand{\LWR@HTML@FiveStarOpenDotted}{\LWR@bbdingsymbol{074}       {272C}}
\newcommand{\LWR@HTML@FiveStarOutline}{\LWR@bbdingsymbol{075}          {272D}}
\newcommand{\LWR@HTML@FiveStarOutlineHeavy}{\LWR@bbdingsymbol{076}     {272E}}
\newcommand{\LWR@HTML@FiveStarConvex}{\LWR@bbdingsymbol{077}           {272F}}
\newcommand{\LWR@HTML@FiveStarShadow}{\LWR@bbdingsymbol{100}           {2730}}
\newcommand{\LWR@HTML@AsteriskBold}{\LWR@bbdingsymbol{101}             {2731}}
\newcommand{\LWR@HTML@AsteriskCenterOpen}{\LWR@bbdingsymbol{102}       {2732}}
\newcommand{\LWR@HTML@AsteriskThin}{\LWR@bbdingsymbol{103}             {273B}}
\newcommand{\LWR@HTML@AsteriskThinCenterOpen}{\LWR@bbdingsymbol{104}    {273C}}
\newcommand{\LWR@HTML@EightStarTaper}{\LWR@bbdingsymbol{105}           {2733}}
\newcommand{\LWR@HTML@EightStarConvex}{\LWR@bbdingsymbol{106}          {2735}}
\newcommand{\LWR@HTML@SixStar}{\LWR@bbdingsymbol{107}                  {2736}}
\newcommand{\LWR@HTML@EightStar}{\LWR@bbdingsymbol{110}                {2737}}
\newcommand{\LWR@HTML@EightStarBold}{\LWR@bbdingsymbol{111}            {2738}}
\newcommand{\LWR@HTML@TwelweStar}{\LWR@bbdingsymbol{112}               {2739}}
\newcommand{\LWR@HTML@SixteenStarLight}{\LWR@bbdingsymbol{113}         {273A}}
\newcommand{\LWR@HTML@SixFlowerPetalRemoved}{\LWR@bbdingsymbol{114}    {273B}}
\newcommand{\LWR@HTML@SixFlowerOpenCenter}{\LWR@bbdingsymbol{115}      {273C}}
\newcommand{\LWR@HTML@Asterisk}{\LWR@bbdingsymbol{116}                 {273D}}
\newcommand{\LWR@HTML@SixFlowerAlternate}{\LWR@bbdingsymbol{117}       {273E}}
\newcommand{\LWR@HTML@FiveFlowerPetal}{\LWR@bbdingsymbol{120}          {273F}}
\newcommand{\LWR@HTML@SixFlowerPetalDotted}{\LWR@bbdingsymbol{121}     {2740}}
\newcommand{\LWR@HTML@FiveFlowerOpen}{\LWR@bbdingsymbol{122}           {2740}}
\newcommand{\LWR@HTML@EightFlowerPetal}{\LWR@bbdingsymbol{123}         {2741}}
\newcommand{\LWR@HTML@SunshineOpenCircled}{\LWR@bbdingsymbol{124}      {2742}}
\newcommand{\LWR@HTML@SixFlowerAltPetal}{\LWR@bbdingsymbol{125}        {2743}}
\newcommand{\LWR@HTML@FourClowerOpen}{\LWR@bbdingsymbol{126}           {273F}}
\newcommand{\LWR@HTML@FourClowerSolid}{\LWR@bbdingsymbol{127}          {273F}}
\newcommand{\LWR@HTML@AsteriskRoundedEnds}{\LWR@bbdingsymbol{130}      {2749}}
\newcommand{\LWR@HTML@EightFlowerPetalRemoved}{\LWR@bbdingsymbol{131}   {274A}}
\newcommand{\LWR@HTML@EightAsterisk}{\LWR@bbdingsymbol{132}            {274B}}
\newcommand{\LWR@HTML@SixFlowerRemovedOpenPetal}{\LWR@bbdingsymbol{133}  {2740}}
\newcommand{\LWR@HTML@SparkleBold}{\LWR@bbdingsymbol{134}              {2748}}
\newcommand{\LWR@HTML@Sparkle}{\LWR@bbdingsymbol{135}                  {2747}}
\newcommand{\LWR@HTML@SnowflakeChevron}{\LWR@bbdingsymbol{136}         {2744}}
```

```
\newcommand{\LWR@HTML@SnowflakeChevronBold}{\LWR@bbdingsymbol{137}     {2746}}
\newcommand{\LWR@HTML@Snowflake}{\LWR@bbdingsymbol{140}                 {2744}}
\newcommand{\LWR@HTML@CircleSolid}{\LWR@bbdingsymbol{141}               {25CF}}
\newcommand{\LWR@HTML@Ellipse}{\LWR@bbdingsymbol{142}                   {274D}}
\newcommand{\LWR@HTML@EllipseSolid}{\LWR@bbdingsymbol{143}              {25CF}}
\newcommand{\LWR@HTML@CircleShadow}{\LWR@bbdingsymbol{144}              {274D}}
\newcommand{\LWR@HTML@EllipseShadow}{\LWR@bbdingsymbol{145}             {274D}}
\newcommand{\LWR@HTML@Square}{\LWR@bbdingsymbol{146}                    {25A1}}
\newcommand{\LWR@HTML@SquareSolid}{\LWR@bbdingsymbol{147}               {25A0}}
\newcommand{\LWR@HTML@SquareShadowBottomRight}{\LWR@bbdingsymbol{150}   {2751}}
\newcommand{\LWR@HTML@SquareShadowTopRight}{\LWR@bbdingsymbol{151}      {2752}}
\newcommand{\LWR@HTML@SquareShadowTopLeft}{\LWR@bbdingsymbol{152}       {2752}}
\newcommand{\LWR@HTML@SquareCastShadowBottomRight}{\LWR@bbdingsymbol{153} {2751}}
\newcommand{\LWR@HTML@SquareCastShadowTopRight}{\LWR@bbdingsymbol{154}   {2752}}
\newcommand{\LWR@HTML@SquareCastShadowTopLeft}{\LWR@bbdingsymbol{155}    {2752}}
\newcommand{\LWR@HTML@TriangleUp}{\LWR@bbdingsymbol{156}                 {25B2}}
\newcommand{\LWR@HTML@TriangleDown}{\LWR@bbdingsymbol{157}               {25BC}}
\newcommand{\LWR@HTML@DiamondSolid}{\LWR@bbdingsymbol{160}               {25C6}}
\newcommand{\LWR@HTML@OrnamentDiamondSolid}{\LWR@bbdingsymbol{161}      {2756}}
\newcommand{\LWR@HTML@HalfCircleRight}{\LWR@bbdingsymbol{162}           {25D7}}
\newcommand{\LWR@HTML@HalfCircleLeft}{\LWR@bbdingsymbol{163}            {25D6}}
\newcommand{\LWR@HTML@RectangleThin}{\LWR@bbdingsymbol{164}             {2758}}
\newcommand{\LWR@HTML@Rectangle}{\LWR@bbdingsymbol{165}                 {2759}}
\newcommand{\LWR@HTML@RectangleBold}{\LWR@bbdingsymbol{166}             {275A}}
\newcommand{\LWR@HTML@ArrowBoldRightStrobe}{\LWR@bbdingsymbol{167}      {27A0}}
\newcommand{\LWR@HTML@ArrowBoldUpRight}{\LWR@bbdingsymbol{170}          {27A6}}
\newcommand{\LWR@HTML@ArrowBoldDownRight}{\LWR@bbdingsymbol{171}        {27A5}}
\newcommand{\LWR@HTML@ArrowBoldRightShort}{\LWR@bbdingsymbol{172}       {27A7}}
\newcommand{\LWR@HTML@ArrowBoldRightCircled}{\LWR@bbdingsymbol{173}     {27B2}}


\LWR@formatted{ScissorRightBrokenBottom}
\LWR@formatted{ScissorRight}
\LWR@formatted{ScissorRightBrokenTop}
\LWR@formatted{ScissorLeftBrokenBottom}
\LWR@formatted{ScissorLeft}
\LWR@formatted{ScissorLeftBrokenTop}
\LWR@formatted{ScissorHollowRight}
\LWR@formatted{ScissorHollowLeft}
\LWR@formatted{Phone}
\LWR@formatted{PhoneHandset}
\LWR@formatted{Tape}
\LWR@formatted{Plane}
\LWR@formatted{Envelope}
\LWR@formatted{HandCuffRight}
\LWR@formatted{HandCuffLeft}
\LWR@formatted{HandCuffRightUp}
\LWR@formatted{HandCuffLeftUp}
\LWR@formatted{HandRight}
\LWR@formatted{HandLeft}
\LWR@formatted{HandRightUp}
\LWR@formatted{HandLeftUp}
\LWR@formatted{Peace}
\LWR@formatted{HandPencilLeft}
\LWR@formatted{PencilRight}
```

```
\LWR@formatted{PencilLeft}
\LWR@formatted{PencilRightUp}
\LWR@formatted{PencilLeftUp}
\LWR@formatted{PencilRightDown}
\LWR@formatted{PencilLeftDown}
\LWR@formatted{NibRight}
\LWR@formatted{NibLeft}
\LWR@formatted{NibSolidRight}
\LWR@formatted{NibSolidLeft}
\LWR@formatted{Checkmark}
\LWR@formatted{CheckmarkBold}
\LWR@formatted{XSolid}
\LWR@formatted{XSolidBold}
\LWR@formatted{XSolidBrush}
\LWR@formatted{PlusOutline}
\LWR@formatted{Plus}
\LWR@formatted{PlusCenterOpen}
\LWR@formatted{PlusThinCenterOpen}
\LWR@formatted{Cross}
\LWR@formatted{CrossOpenShadow}
\LWR@formatted{CrossOutline}
\LWR@formatted{CrossBoldOutline}
\LWR@formatted{CrossMaltese}
\LWR@formatted{DavidStarSolid}
\LWR@formatted{DavidStar}
\LWR@formatted{FourAsterisk}
\LWR@formatted{JackStar}
\LWR@formatted{JackStarBold}
\LWR@formatted{CrossClowerTips}
\LWR@formatted{FourStar}
\LWR@formatted{FourStarOpen}
\LWR@formatted{FiveStarLines}
\LWR@formatted{FiveStar}
\LWR@formatted{FiveStarOpen}
\LWR@formatted{FiveStarOpenCircled}
\LWR@formatted{FiveStarCenterOpen}
\LWR@formatted{FiveStarOpenDotted}
\LWR@formatted{FiveStarOutline}
\LWR@formatted{FiveStarOutlineHeavy}
\LWR@formatted{FiveStarConvex}
\LWR@formatted{FiveStarShadow}
\LWR@formatted{AsteriskBold}
\LWR@formatted{AsteriskCenterOpen}
\LWR@formatted{AsteriskThin}
\LWR@formatted{AsteriskThinCenterOpen}
\LWR@formatted{EightStarTaper}
\LWR@formatted{EightStarConvex}
\LWR@formatted{SixStar}
\LWR@formatted{EightStar}
\LWR@formatted{EightStarBold}
\LWR@formatted{TwelweStar}
\LWR@formatted{SixteenStarLight}
\LWR@formatted{SixFlowerPetalRemoved}
\LWR@formatted{SixFlowerOpenCenter}
\LWR@formatted{Asterisk}
```

```
\LWR@formatted{SixFlowerAlternate}
\LWR@formatted{FiveFlowerPetal}
\LWR@formatted{SixFlowerPetalDotted}
\LWR@formatted{FiveFlowerOpen}
\LWR@formatted{EightFlowerPetal}
\LWR@formatted{SunshineOpenCircled}
\LWR@formatted{SixFlowerAltPetal}
\LWR@formatted{FourClowerOpen}
\LWR@formatted{FourClowerSolid}
\LWR@formatted{AsteriskRoundedEnds}
\LWR@formatted{EightFlowerPetalRemoved}
\LWR@formatted{EightAsterisk}
\LWR@formatted{SixFlowerRemovedOpenPetal}
\LWR@formatted{SparkleBold}
\LWR@formatted{Sparkle}
\LWR@formatted{SnowflakeChevron}
\LWR@formatted{SnowflakeChevronBold}
\LWR@formatted{Snowflake}
\LWR@formatted{CircleSolid}
\LWR@formatted{Ellipse}
\LWR@formatted{EllipseSolid}
\LWR@formatted{CircleShadow}
\LWR@formatted{EllipseShadow}
\LWR@formatted{Square}
\LWR@formatted{SquareSolid}
\LWR@formatted{SquareShadowBottomRight}
\LWR@formatted{SquareShadowTopRight}
\LWR@formatted{SquareShadowTopLeft}
\LWR@formatted{SquareCastShadowBottomRight}
\LWR@formatted{SquareCastShadowTopRight}
\LWR@formatted{SquareCastShadowTopLeft}
\LWR@formatted{TriangleUp}
\LWR@formatted{TriangleDown}
\LWR@formatted{DiamondSolid}
\LWR@formatted{OrnamentDiamondSolid}
\LWR@formatted{HalfCircleRight}
\LWR@formatted{HalfCircleLeft}
\LWR@formatted{RectangleThin}
\LWR@formatted{Rectangle}
\LWR@formatted{RectangleBold}
\LWR@formatted{ArrowBoldRightStrobe}
\LWR@formatted{ArrowBoldUpRight}
\LWR@formatted{ArrowBoldDownRight}
\LWR@formatted{ArrowBoldRightShort}
\LWR@formatted{ArrowBoldRightCircled}
```

File 44 **lwarp-biblatex.sty**

§ 152 Package biblatex

(*Emulates or patches code by* Philipp Lehman.)

Pkg biblatex When biblatex is used, modifications from newfloat may have to be undone.

for HTML output:

1. lwarp uses newfloat.
2. For classes with chapters which newfloat does not know about, such as CTEX-related classes, newfloat may modify `\addtocontents`.
3. biblatex, though, wants to patch `\addtocontents`, which causes an error if `\addtocontents` has been changed.
4. Therefore, `\addtocontents` is restored to its original here, since biblatex is about to be loaded.
5. This means that the newfloat's `chapterlistsgaps` option may no longer work.

```
\ifdef{\newfloat@addtocontents@ORI}{
    \let\addtocontents\newfloat@addtocontents@ORI
}{}
```

hyperref emulation is loaded `\AtBeginDocument` to avoid an options clash.

```
\AtBeginDocument{\RequirePackage{hyperref}}

\LWR@ProvidesPackagePass{biblatex}[2018/03/04]
```

The following create hyperlinks to the references. The original code to use hyperref is recreated here, because hyperref is emulated.

```
\AfterPreamble{

\let\blx@anchors\@empty
\protected\def\blx@anchor{%
    \xifinlist{\the\c@refsection @\abx@field@entrykey}{\blx@anchors}
        {}
        {\listxadd\blx@anchors{\the\c@refsection @\abx@field@entrykey}%
        \hypertarget{cite.\the\c@refsection @\abx@field@entrykey}{}}}

\protected\def\blx@imc@bibhyperref{%
    \@ifnextchar[%]
      {\blx@bibhyperref}
      {\blx@bibhyperref[\abx@field@entrykey]}}%

\long\def\blx@bibhyperref[#1]#2{%
%        \blx@sfsave
        \hyperlink{cite.\the\c@refsection @#1}{%
%             \blx@sfrest
         #2%
%        \blx@sfsave
        }%
% \blx@sfrest%
}%% \def\blx@nohyperref[#1]#2{#2}%

\protected\long\def\blx@imc@bibhyperlink#1#2{%
%        \blx@sfsave
        \hyperlink{cite.\the\c@refsection:#1}{%
%          \blx@sfrest
         #2%
```

```
%         \blx@sfsave
         }%
%          \blx@sfrest%
}%

\protected\long\def\blx@imc@bibhypertarget#1#2{%
%         \blx@sfsave%
         \hypertarget{cite.\the\c@refsection:#1}{%
%          \blx@sfrest
          #2%
%         \blx@sfsave%
         }%
%          \blx@sfrest%
}

\let\blx@imc@ifhyperref\@firstoftwo
```

Ensure that an autopage reference is current where each `\cite` is used, although this is nullified inside footnotes since they now use a LaTeX box.

```
\xpretocmd{\blx@citecmdinit}
    {\LWR@newautopagelabel{page}}%
    {}
    {\LWR@patcherror{biblatex}{blx@citecmdinit}}
```

Ensure that an autopage reference is current for each backref. If the citation is in a footnote, the backref will point to whatever preceeded the footnotes.

```
\xpatchcmd{\blx@addbackref@i}
    {\thepage}
    {\theLWR@previousautopagelabel}% ref to the most recent object
    {}
    {\LWR@patcherror{biblatex}{blx@addbackref@i A}}

\xpatchcmd{\blx@addbackref@i}
    {\c@page}
    {\c@LWR@previousautopagelabel}% refto the most recent object
    {}
    {\LWR@patcherror{biblatex}{blx@addbackref@i B}}
```

The following patches are for back page references.

```
\DeclareListFormat{pageref}{%
  \ifnumless{\abx@pagerefstyle}{0}
    {\usebibmacro{list:plain}%
     \ifhyperref
       {%
%             \hyperlink{page.#1}{#1}%
            \LWR@refwithsection{\BaseJobname-autopage-#1}%  lwarp
       }
       {#1}}
    {\ifnumequal{\value{listcount}}{1}
       {\usebibmacro{pageref:init}}
       {}%
     \usebibmacro{pageref:comp}{#1}%
```

```
    \ifnumequal{\value{listcount}}{\value{liststop}}
      {\usebibmacro{pageref:dump}}
      {}}}

\renewbibmacro*{pageref:comp}[1]{%
  \numdef\abx@range@prev{\abx@range@prev+1}%
  \ifinteger{#1}
    {\def\abx@range@num{#1}%
     \def\abx@range@this{1}%
     \ifnumequal{\abx@range@this}{\abx@range@last}
       {}
       {\def\abx@range@prev{-1}}}
    {\ifrmnum{#1}
       {\numdef\abx@range@num{\rmntonum{#1}}%
        \def\abx@range@this{2}%
        \ifnumequal{\abx@range@this}{\abx@range@last}
          {}
          {\def\abx@range@prev{-1}}}
       {\undef\abx@range@num
        \def\abx@range@this{0}%
        \def\abx@range@prev{-1}}%
  \ifdef\abx@range@num
    {\ifnumequal{\abx@range@num}{\abx@range@prev}
       {\def\abx@range@hold{#1}%
        \numdef\abx@range@diff{\abx@range@diff+1}}
       {\usebibmacro{pageref:dump}%
        \ifnumgreater{\abx@range@last}{-1}
          {\printdelim{multilistdelim}}
          {}%
        \ifhyperref
%           {\hyperlink{page.#1}{#1}}
          {\LWR@refwithsection{\BaseJobname-autopage-#1}}%  lwarp
          {#1}}%
     \edef\abx@range@prev{\abx@range@num}}
    {\usebibmacro{pageref:dump}%
     \ifnumgreater{\abx@range@last}{-1}
       {\printdelim{multilistdelim}}
       {}%
     \ifhyperref
%        {\hyperlink{page.#1}{#1}}
       {\LWR@refwithsection{\BaseJobname-autopage-#1}}%  lwarp
       {#1}%
     \def\abx@range@prev{-1}}%
  \edef\abx@range@last{\abx@range@this}}

\renewbibmacro*{pageref:dump}{%
  \ifnumgreater{\abx@range@diff}{0}
    {\ifcase\abx@pagerefstyle\relax % two
       \bibrangedash
       \ifhyperref
%          {\hyperlink{page.\abx@range@hold}{\abx@range@hold}}
         {\LWR@refwithsection{\BaseJobname-autopage-\abx@range@hold}}%  lwarp
         {\abx@range@hold}%
     \or % three
       \ifnumless{\abx@range@diff}{2}
```

```
135         {\printdelim{multilistdelim}}
136         {\bibrangedash}%
137       \ifhyperref
138 %         {\hyperlink{page.\abx@range@hold}{\abx@range@hold}}
139         {\LWR@refwithsection{\BaseJobname-autopage-\abx@range@hold}}%  lwarp
140         {\abx@range@hold}%
141     \or % two+
142       \ifnumless{\abx@range@diff}{2}
143         {\sqspace
144          \ifhyperref
145 %           {\hyperlink{page.\abx@range@hold}{\bibstring{sequens}}}
146          {\LWR@refwithsection{\BaseJobname-autopage-\abx@range@hold}}%  lwarp
147            {\bibstring{sequens}}}
148         {\bibrangedash
149          \ifhyperref
150 %           {\hyperlink{page.\abx@range@hold}{\abx@range@hold}}
151          {\LWR@refwithsection{\BaseJobname-autopage-\abx@range@hold}}%  lwarp
152            {\abx@range@hold}}%
153     \or % three+
154       \ifnumless{\abx@range@diff}{2}
155         {\sqspace
156          \ifhyperref
157 %           {\hyperlink{page.\abx@range@hold}{\bibstring{sequens}}}
158          {\LWR@refwithsection{\BaseJobname-autopage-\abx@range@hold}}%  lwarp
159            {\bibstring{sequens}}}
160         {\ifnumless{\abx@range@diff}{3}
161           {\sqspace
162            \ifhyperref
163 %             {\hyperlink{page.\abx@range@hold}{\bibstring{sequentes}}}
164           {\LWR@refwithsection{\BaseJobname-autopage-\abx@range@hold}}% lwarp
165              {\bibstring{sequentes}}}
166            {\bibrangedash
167             \ifhyperref
168 %             {\hyperlink{page.\abx@range@hold}{\abx@range@hold}}
169           {\LWR@refwithsection{\BaseJobname-autopage-\abx@range@hold}}% lwarp
170              {\abx@range@hold}}}%
171     \else % all+
172       \ifnumless{\abx@range@diff}{2}
173         {\sqspace
174          \ifhyperref
175 %           {\hyperlink{page.\abx@range@hold}{\bibstring{sequens}}}
176          {\LWR@refwithsection{\BaseJobname-autopage-\abx@range@hold}}%  lwarp
177            {\bibstring{sequens}}}
178         {\sqspace
179          \ifhyperref
180 %           {\hyperlink{page.\abx@range@hold}{\bibstring{sequentes}}}
181          {\LWR@refwithsection{\BaseJobname-autopage-\abx@range@hold}}%  lwarp
182            {\bibstring{sequentes}}}%
183     \fi
184     \def\abx@range@diff{0}}
185    {}}
186
187 }% \AfterPreamble
```

File 45 **lwarp-bibunits.sty**

§ 153 Package

bibunits

(*Emulates or patches code by* Thorsten Hansen.)

Pkg bibunits bibunits is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{bibunits}[2004/05/12]
\def\bu@bibdata{\BaseJobname}
```

File 46 **lwarp-bigdelim.sty**

§ 154 Package

bigdelim

(*Emulates or patches code by* Piet van Oostrum, Øystein Bache, Jerry Leichter.)

Pkg bigdelim bigdelim is used as-is for print or `lateximage`, and patched for HTML.

The delimiters are displayed in HTML by printing the delimiter, the text, and a thick border across the side of the `\multirow` which indicates the actual height of the delimiter. The delimiter character is given a `<span>` class of `ldelim` or `rdelim`, and the default CSS sets this to `font-size:200%`

⚠ use \mrowcell `\ldelim` and `\rdelim` use `\multirow`, so `\mrowcell` must be used in the proper number of empty cells in the same column below `\ldelim` or `\rdelim`, but not in cells which are above or below the delimiter:

```
\begin{tabular}{lll}
<empty> & a & b \\
\ldelim{\{}{3}{.25in}[left ] & c & d \\
\mrowcell & e & f \\
\mrowcell & g & h \\
<empty> & i & j \\
\end{tabular}
```

<-> a b

left { c d
e f
g h

<-> i j

For MathJax, limited emulation is provided which merely prints the delimter and optional text in the first row.

for HTML output: First, remove the temporary definitions of `\ldelim` and `\rdelim`, which were previously defined for tabular scanning in case bigdelim was not loaded:

```
\let\ldelim\relax
\let\rdelim\relax
```

Next, load the package's new definitions:

```
\LWR@ProvidesPackagePass{bigdelim}[2021/03/15]
```

`\ldelim` {⟨*1:delimiter*⟩} {⟨*2:#rows*⟩} [⟨*3: vmove*⟩] {⟨*4:width*⟩} [⟨*5:text*⟩]
`\rdelim`

```
\NewDocumentCommand{\LWR@HTML@ldelim}{m m o m O{}}{%
\renewcommand{\LWR@multirowborder}{right}%
\multirow{#2}{#4}{#5 \InlineClass{ldelim}{#1}}%
}

\LWR@formatted{ldelim}

\NewDocumentCommand{\LWR@HTML@rdelim}{m m o m O{}}{%
\renewcommand{\LWR@multirowborder}{left}%
\multirow{#2}{#4}{\InlineClass{rdelim}{#1} #5}%
}

\LWR@formatted{rdelim}
```

Limited emulation for MathJax. The delimiter is printed on the first row, along with any optional text.

```
\begin{warpMathJax}
% \ldelim ( {n}{width}[text]
\CustomizeMathJax{\newcommand{\LWRldelimtwo}[1][]{\text{#1}~\LWRbigdelim}}
\CustomizeMathJax{\newcommand{\LWRldelimone}[2][]{\LWRldelimtwo}}
\CustomizeMathJax{\def\ldelim#1#2{\def\LWRbigdelim{#1}\LWRldelimone}}
% \rdelim ) {n}{width}[text]
\CustomizeMathJax{\newcommand{\LWRrdelimtwo}[1][]{\LWRbigdelim~\text{#1}}}
\CustomizeMathJax{\newcommand{\LWRrdelimone}[2][]{\LWRrdelimtwo}}
\CustomizeMathJax{\def\rdelim#1#2{\def\LWRbigdelim{#1}\LWRrdelimone}}
\end{warpMathJax}
```

File 47 **lwarp-bigfoot.sty**

§ 155 Package

bigfoot

Pkg bigfoot bigfoot is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{bigfoot}[2015/08/30]

\RequirePackage{manyfoot}
\RequirePackage{perpage}

\def\RestyleFootnote#1#2{}
```

```
\def\FootnoteSpecific#1{}
\def\DefineFootnoteStack#1{}
\def\PushFootnoteMark#1{}
\def\PopFootnoteMark#1{}
\def\hfootfraction{0.9}
\def\vtypefraction{0.7}
\def\FootnoteMinimum{1sp}
\def\FootnoteMainMinimum{0pt}
\newcount\bigfoottolerance
\bigfoottolerance=100
\providecommand\footnotecarryratio{2}
```

File 48 **lwarp-bigstrut.sty**

§ 156 Package

bigstrut

(*Emulates or patches code by* Piet van Oostrum, Øystein Bache, Jerry Leichter.)

Pkg bigstrut bigstrut is used as-is for print or `lateximage`, and patched for HTML.

for HTML output:

```
\LWR@ProvidesPackagePass{bigstrut}[2018/08/03]

\LetLtxMacro\LWR@origbigstrut\bigstrut

\renewcommand\bigstrut[1][x]{}

\appto\LWR@restoreorigformatting{%
\LetLtxMacro\bigstrut\LWR@origbigstrut%
}


\begin{warpMathJax}
\CustomizeMathJax{\newcommand{\bigstrut}[1][]{}}
\end{warpMathJax}
```

File 49 **lwarp-bitpattern.sty**

§ 157 Package

bitpattern

(*Emulates or patches code by* Jean-Marc Bourguet.)

Pkg bitpattern bitpattern is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{bitpattern}[2015/12/11]

\xpatchcmd{\bitpattern}
    {\begingroup}
    {\begin{lateximage}[-bitpattern-~\PackageDiagramAltText]}
    {}
    {\LWR@patcherror{bitpattern}{bitpattern}}
```

```
7
8 \xpatchcmd{\bp@Done}
9     {\endgroup}
10    {\end{lateximage}}
11    {}
12    {\LWR@patcherror{bitpattern}{bp@Done}}
```

File 50 **lwarp-blowup.sty**

§ 158 Package

blowup

Pkg blowup

blowup is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{blowup}[2018/01/02]

2 \newcommand*\blowUp[1]{}
```

File 51 **lwarp-bm.sty**

§ 159 Package

bm

(*Emulates or patches code by* David Carlisle, Frank Mittelbach.)

Pkg bm

bm is patched for use by lwarp.

for HTML output:

```
1 \LWR@ProvidesPackagePass{bm}[2019/07/24]
```

\DeclareBoldMathCommand must only be used in the preamble, since it adds to the MathJax setup code.

```
2 \begin{warpMathJax}
3 \LetLtxMacro\LWR@orig@DeclareBoldMathCommand\DeclareBoldMathCommand
4
5 \renewcommand\DeclareBoldMathCommand[3][bold]{%
6     \LWR@orig@DeclareBoldMathCommand[#1]{#2}{#3}%
7     \CustomizeMathJax{\newcommand{#2}{\boldsymbol{#3}}}%
8 }
9
10 \@onlypreamble\DeclareBoldMathCommand
11
12 \CustomizeMathJax{\newcommand{\bm}[1]{\boldsymbol{#1}}}
13 \end{warpMathJax}
```

File 52 **lwarp-booklet.sty**

§ 160 Package

booklet

(*Emulates or patches code by* Peter Wilson.)

Pkg booklet booklet is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{booklet}[2009/09/02]

\newdimen\pageseplength
\newdimen\pagesepwidth
\newdimen\pagesepoffset
\newif\ifsidebyside     \sidebysidetrue
\newif\ifuselandscape   \uselandscapefalse
\newif\ifprintoption    \printoptionfalse
\newcommand*{\pagespersignature}[1]{}
\def\magstepminus#1{}
\newcommand*{\target}[3]{}
\newcommand*{\source}[3]{}
\newcommand*{\setpdftargetpages}{}
\newcommand*{\setdvipstargetpages}{}
\newcommand*{\targettopbottom}{}
\newcommand*{\twoupemptypage}{}
\newcommand*{\twoupclearpage}{}
\newcommand*{\checkforlandscape}{}
```

File 53 **lwarp-bookmark.sty**

§ 161 Package bookmark

(*Emulates or patches code by* Heiko Oberdiek.)

Pkg bookmark bookmark is ignored.

for HTML output: Discard all options for lwarp-bookmark:

```
\LWR@ProvidesPackageDrop{bookmark}[2016/05/17]

\newcommand*{\bookmarksetup}[1]{}
\newcommand*{\bookmarksetupnext}[1]{}
\newcommand*{\bookmark}[2][]{}
\newcommand*{\bookmarkdefinestyle}[2]{}
\newcommand*{\bookmarkget}[1]{}
\newcommand{\BookmarkAtEnd}[1]{}
```

File 54 **lwarp-booktabs.sty**

§ 162 Package booktabs

(*Emulates or patches code by* Simon Fear.)

Pkg booktabs booktabs is emulated during HTML output, and used as-is during print output and inside an HTML `lateximage`.

⚠ `\cmidrule` For MathJax, emulation is provided in math mode, but `\cmidrule` trim must not be used.

for HTML output:

If booktabs has already been loaded before lwarp, such as by memoir, use it as-is. If not, the lwarp core will have placed some dummy macros which should be removed before loading the actual booktabs definitions.

```
\@ifpackageloaded{booktabs}{}{
    \LetLtxMacro\toprule\relax
    \LetLtxMacro\midrule\relax
    \LetLtxMacro\cmidrule\cline
    \LetLtxMacro\bottomrule\relax
    \LetLtxMacro\addlinespace\relax
    \LetLtxMacro\morecmidrules\relax
    \LetLtxMacro\specialrule\relax
}
```

Next, load the booktabs package:

```
\LWR@ProvidesPackagePass{booktabs}[2019/10/08]
```

Adjust to work even if xltabular is loaded:

```
% \def\LWR@HTML@@BLTrule{\@BTnormal}
%
% \LWR@formatted{@BLTrule}
\LetLtxMacro\@BLTrule\@BTnormal


\DeclareDocumentCommand{\LWR@HTML@toprule}{o d()}%
    {%
        \IfValueTF{#1}%
            {\LWR@docmidrule[#1](){1-\arabic{LWR@tabletotalLaTeXcols}}}%
            {%
                \ifbool{FormatWP}%
                {\LWR@docmidrule[#1](){1-\arabic{LWR@tabletotalLaTeXcols}}}%
                {\booltrue{LWR@doingtbrule}}%
            }%
    \LWR@getmynexttoken}

\LWR@expandableformatted{toprule}

\DeclareDocumentCommand{\LWR@HTML@midrule}{o d()}%
    {%
        \IfValueTF{#1}%
            {\LWR@docmidrule[#1](){1-\arabic{LWR@tabletotalLaTeXcols}}}%
            {%
                \ifbool{FormatWP}%
                {\LWR@docmidrule[#1](){1-\arabic{LWR@tabletotalLaTeXcols}}}%
                {\defaddtocounter{LWR@hlines}{1}}%
            }%
    \LWR@getmynexttoken}

\LWR@expandableformatted{midrule}

\DeclareDocumentCommand{\LWR@HTML@cmidrule}{O{\LWR@cmidrulewidth} d() m}{%
    \LWR@docmidrule[#1](#2){#3}%
    \LWR@getmynexttoken%
}%
```

```
\LWR@expandableformatted{cmidrule}

\DeclareDocumentCommand{\LWR@HTML@bottomrule}{o d()}{%
    \IfValueTF{#1}%
        {\LWR@docmidrule[#1]()}{1-\arabic{LWR@tabletotalLaTeXcols}}}%
        {%
            \ifbool{FormatWP}%
            {\LWR@docmidrule[#1]()}{1-\arabic{LWR@tabletotalLaTeXcols}}}%
            {\booltrue{LWR@doingtbrule}}%
        }%
    \LWR@getmynexttoken%
}%

\LWR@expandableformatted{bottomrule}

\DeclareDocumentCommand{\LWR@HTML@addlinespace}{o}{}%

\LWR@expandableformatted{addlinespace}

\DeclareDocumentCommand{\LWR@HTML@morecmidrules}{}{}%

\LWR@expandableformatted{morecmidrules}

\DeclareDocumentCommand{\LWR@HTML@specialrule}{m m m d()}%
  {\LWR@docmidrule[#1]()}{1-\arabic{LWR@tabletotalLaTeXcols}}\LWR@getmynexttoken}%

\LWR@expandableformatted{specialrule}
```

For MathJax:

```
\begin{warpMathJax}
\CustomizeMathJax{\newcommand{\toprule}[1][]{\hline}}
\CustomizeMathJax{\let\midrule\toprule}
\CustomizeMathJax{\let\bottomrule\toprule}
\CustomizeMathJax{\def\LWRbooktabscmidruleparen(#1)#2{}}
\CustomizeMathJax{\newcommand{\LWRbooktabscmidrulenoparen}[1]{}}
\CustomizeMathJax{\newcommand{\cmidrule}[1][]{%
    \ifnextchar(\LWRbooktabscmidruleparen\LWRbooktabscmidrulenoparen%
}}
\CustomizeMathJax{\newcommand{\morecmidrules}{}}
\CustomizeMathJax{\newcommand{\specialrule}[3]{\hline}}
\CustomizeMathJax{\newcommand{\addlinespace}[1][]{}}
\end{warpMathJax}
```

File 55 **lwarp-bophook.sty**

§ 163 Package

bophook

Pkg bophook bophook is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{bophook}[2001/03/29]
```

```
\newcommand*{\AtBeginPage}[1]{}
\newcommand*{\PageLayout}[1]{}
```

File 56 **lwarp-bounddvi.sty**

§ 164 Package

bounddvi

Pkg bounddvi bounddvi is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{bounddvi}[2016/12/28]
```

File 57 **lwarp-boxedminipage.sty**

§ 165 Package

boxedminipage

(*Emulates or patches code by* Scott Pakin.)

Pkg boxedminipage boxedminipage is emulated for HTML, and used as-is for `latexi`mages.

for HTML output:

```
\LWR@ProvidesPackagePass{boxedminipage}[2020/04/19]

\newenvironment{LWR@HTML@boxedminipage}{%
    \LWR@stoppars%
    \begin{BlockClass}{framebox}%
    \minipage%
}
{%
    \endminipage%
    \end{BlockClass}%
    \LWR@startpars%
}
\LWR@formattedenv{boxedminipage}
```

File 58 **lwarp-boxedminipage2e.sty**

§ 166 Package

boxedminipage2e

(*Emulates or patches code by* Scott Pakin.)

Pkg boxedminipage2e boxedminipage2e has been renamed boxedminipage by the author.

for HTML output: Automatically loads boxedminipage:

```
\LWR@ProvidesPackagePass{boxedminipage2e}
```

File 59 **lwarp-braket.sty**

§ 167 Package braket

(*Emulates or patches code by* Donald Arseneau.)

Pkg braket braket works as-is for HTML with SVG math. For MathJax, the MathJax extension is used.

for HTML output:

```
\LWR@ProvidesPackagePass{braket}% No date is provided by the file.

\begin{warpMathJax}
    \CustomizeMathJax{\require{braket}}
\end{warpMathJax}
```

File 60 **lwarp-breakurl.sty**

§ 168 Package breakurl

(*Emulates or patches code by* Vilar Camara Neto.)

Pkg breakurl breakurl is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{breakurl}[2013/04/10]

\LetLtxMacro\burl\LWR@url

\NewDocumentCommand{\LWR@burlaltb}{O{} +m m}{%
    \LWR@ensuredoingapar%
    \LWR@subhyperref{#2}%
    \LWR@subhyperreftext{#3}%
    \endgroup% restore catcodes
}

\newrobustcmd*{\burlalt}{%
    \begingroup%
    \LWR@linkcatcodes%
    \LWR@burlaltb%
}

\LetLtxMacro\urlalt\burlalt
```

File 61 **lwarp-breqn.sty**

§ 169 Package breqn

(*Emulates or patches code by* Michael J. Downes, Morten Høgholm.)

Pkg breqn breqn is patched for use by lwarp.

⚠ darray darray is not supported, and in fact does not work in the print version either.

While using MathJax, breqn objects are converted to SVG images.

for HTML output:

```
\LWR@ProvidesPackagePass{breqn}[2017/01/27]
```

```
\setkeys{breqn}{spread={5pt}}

\def\eqnumside{R}
% \def\eqnumplace{T}

\BeforeBeginEnvironment{dmath}{
    \begin{BlockClass}{displaymathnumbered}
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}[-breqn dmath- \MathImageAltText]
}

\AfterEndEnvironment{dmath}{
    \end{lateximage}\end{BlockClass}
}

\BeforeBeginEnvironment{dmath*}{
    \begin{BlockClass}{displaymath}
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}[-breqn dmath*- \MathImageAltText]
}

\AfterEndEnvironment{dmath*}{
    \end{lateximage}\end{BlockClass}
}

\BeforeBeginEnvironment{dseries}{
    \begin{BlockClass}{displaymathnumbered}
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}[-breqn dseries- \MathImageAltText]
}

\AfterEndEnvironment{dseries}{
    \end{lateximage}\end{BlockClass}
}

\BeforeBeginEnvironment{dseries*}{
    \begin{BlockClass}{displaymath}
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}[-breqn dseries*- \MathImageAltText]
}

\AfterEndEnvironment{dseries*}{
    \end{lateximage}\end{BlockClass}
}

\BeforeBeginEnvironment{dgroup}{
    \begin{BlockClass}{displaymath}
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}[-breqn dgroup- \MathImageAltText]
}
```

```
57
58 \AfterEndEnvironment{dgroup}{
59     \end{lateximage}\end{BlockClass}
60 }
61
62 \BeforeBeginEnvironment{dgroup*}{
63     \begin{BlockClass}{displaymath}
64     \LWR@newautoidanchor%
65     \booltrue{LWR@indisplaymathimage}%
66     \begin{lateximage}[-breqn dgroup*- \MathImageAltText]
67 }
68
69 \AfterEndEnvironment{dgroup*}{
70     \end{lateximage}\end{BlockClass}
71 }
```

File 62 **lwarp-bsheaders.sty**

§ 170 Package

bsheaders

Pkg bsheaders

bsheaders is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{bsheaders}[1997/10/06]
```

File 63 **lwarp-bussproofs.sty**

§ 171 Package

bussproofs

(*Emulates or patches code by* Samuel R. Buss.)

Pkg bussproofs

bussproofs is used as-is for HTML, and emulated by MathJax's extension.

⚠ \DisplayProof

If not using MathJax, inline proofs with \DisplayMath must be placed inside a math expression.

If using MathJax, only the prooftree environment may be used, not \DisplayProof.

for HTML output:

```
1 \LWR@ProvidesPackagePass{bussproofs}% no date in file

2 \ifbool{mathjax}{
3     \CustomizeMathJax{\require{bussproofs}}
4
5     \NewEnviron{LWR@HTML@prooftree}%
6         {\LWR@doequation{\BODY}{prooftree}}%
7         [\LWR@doendequation{prooftree}]
8     \LWR@formattedenv{prooftree}
9 }{% SVG HTML
10    \BeforeBeginEnvironment{prooftree}{%
11        \begin{lateximage}[-bussproofs-~\PackageDiagramAltText]%
12    }
```

```
    \AfterEndEnvironment{prooftree}{\end{lateximage}}
}
```

File 64 **lwarp-bxpapersize.sty**

§ 172 Package

bxpapersize

Pkg bxpapersize bxpapersize is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{bxpapersize}[2017/10/08]

\providecommand*\papersizesetup{\bxpapersizesetup}
\newcommand*\bxpapersizesetup[1]{}
```

File 65 **lwarp-bytefield.sty**

§ 173 Package

bytefield

(*Emulates or patches code by* Scott Pakin.)

Pkg bytefield bytefield is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{bytefield}[2017/09/15]

\BeforeBeginEnvironment{bytefield}{%
    \begin{lateximage}[-bytefield-~\PackageDiagramAltText]%
}

\AfterEndEnvironment{bytefield}{\end{lateximage}}
```

File 66 **lwarp-cancel.sty**

§ 174 Package

cancel

Pkg cancel cancel is used as-is for SVG math, and emulated for HTML text output.

for HTML output:

```
\LWR@origRequirePackage{lwarp-xcolor}% for \convertcolorspec
\LWR@ProvidesPackagePass{cancel}[2013/04/12]
```

\cancelto is math-only, so is used as-is.

```
\LetLtxMacro\LWR@origcancel\cancel
\LetLtxMacro\LWR@origbcancel\bcancel
\LetLtxMacro\LWR@origxcancel\xcancel

\appto\LWR@restoreorigformatting{%
\LetLtxMacro\cancel\LWR@origcancel%
```

```
\LetLtxMacro\bcancel\LWR@origbcancel%
\LetLtxMacro\xcancel\LWR@origxcancel%
}
```

\LWR@cancelcolor {⟨*text*⟩} {⟨*color*⟩} {⟨*class*⟩} {⟨*colorstyle*⟩} {⟨*FormatWPstyle*⟩}

Add colors if not empty:

```
\newcommand{\LWR@cancelcolor}[5]{%
\ifcsempty{#2}%
{\InlineClass(#5){#3}{#1}}%
{\LWR@htmlspanclass[#5;#4:\LWR@origpound\LWR@tempcolor]{#3}{#1}}%
}
```

\cancel {⟨*text*⟩}

```
\DeclareRobustCommand{\cancel}[1]{%
\begingroup%
\CancelColor%
\LWR@findcurrenttextcolor%
\color{black}%
\LWR@cancelcolor{#1}{LWR@tempcolor}{sout}{text-decoration-color}%
    {text-decoration:line-through}%
\endgroup%
}

\LetLtxMacro\bcancel\cancel
\LetLtxMacro\xcancel\cancel
```

For MathJax:

```
\begin{warpMathJax}
\PackageWarningNoLine{lwarp, cancel}{The MathJax v3 extension will be used}
\CustomizeMathJax{\require{cancel}}
\end{warpMathJax}
```

File 67 **lwarp-canoniclayout.sty**

§ 175 Package

canoniclayout

Pkg canoniclayout canoniclayout is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{canoniclayout}[2011/11/05]

\newcommand*{\currentfontletters}{}
\newcommand*{\charactersperpage}{}
```

File 68 **lwarp-caption.sty**

§ 176 Package

caption

(*Emulates or patches code by* Axel Sommerfeldt.)

Pkg caption

caption is patched for use by lwarp.

for HTML output:

```
\typeout{---}
\typeout{Packages lwarp and caption:}
\typeout{If a ‘‘Missing \protect\begin\protect{document\protect}’’ error occurs here,}
\typeout{try using: \space \protect\usepackage\protect{caption\protect}\space%
    \protect\captionsetup{options}}
\typeout{instead of: \protect\usepackage[options]\protect{caption\protect}.}
\typeout{---}

\LWR@ProvidesPackagePass{caption}[2020/10/26]

\long\def\caption@iibox@#1#2#3#4{%
%   \setbox\@tempboxa\hbox{#4}%
  \caption@iiibox{#1}{#2}{#3}%
%         [\wd\@tempboxa]%
        []%                             lwarp
        [\captionbox@hj@default]%
%         {\unhbox\@tempboxa}%
        {{#4}}%                         lwarp
}

\long\def\caption@iiiibox#1#2#3#4#5[#6][#7]#8{%
  \begingroup
  #1*% set \caption@position
  \caption@iftop{%
    \endgroup

    \minipagefullwidth%                 lwarp
    \parbox[t]{\linewidth}{%
      #1\relax
      \caption@setposition t%
%       #2%
            {\caption#4{#5}}%
%       \captionbox@hrule
%       \csname caption@hj@#7\endcsname
      #8%
    }%
  }{%
    \endgroup

%     \parbox[b]{#6}{%
    \minipagefullwidth%                 lwarp
    \parbox[b]{\linewidth}{%            lwarp
      #1\relax
      \caption@setposition b%
%       \csname caption@hj@#7\endcsname
      #8%
%       \captionbox@hrule
%       #3
            {\caption#4{#5}}%
    }%
  }%
}
```

\caption@makecaption

```
\long\def\caption@makecaption#1#2{%
%   \caption@make@above
  \caption@@make{#1}{#2}%
%   \caption@make@below
}

\AtBeginDocument{
    \let\@makecaption\caption@makecaption
}
```

Appended to look ahead to the next token for \centering, etc:

```
\AtBeginDocument{
\xapptocmd{\@xfloat}
    {\LWR@futurenonspacelet\LWR@mynexttoken\LWR@floatalignment}
    {}
    {\LWR@patcherror{caption}{@xfloat}}

\xapptocmd{\@xdblfloat}
    {\LWR@futurenonspacelet\LWR@mynexttoken\LWR@floatalignment}
    {}
    {\LWR@patcherror{caption}{@xdblfloat}}
}
```

Updates for late patches for scrextend:

```
\caption@AtBeginDocument{
\@ifpackageloaded{lwarp-scrextend}{
    \LetLtxMacro\captionbelow\caption
    \LetLtxMacro\captionabove\caption
    \LetLtxMacro\captionofbelow\captionof
    \LetLtxMacro\captionofabove\captionof
}{}
}
```

File 69 **lwarp-caption3.sty**

§ 177 Package

caption3

(*Emulates or patches code by* Axel Sommerfeldt.)

Pkg caption3 caption3 is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{caption3}[2020/10/21]
```

\caption@@@make {⟨*caption label*⟩} {⟨*caption text*⟩}

```
\@ifpackagelater{caption3}{2020/08/23}{
\renewcommand\caption@@@make[2]{%
\LWR@traceinfo{caption@@@make}%
```

```
    \LWR@stoppars%                                lwarp
%   \sbox\@tempboxa{#1}%
%   \ifdim\wd\@tempboxa=\z@
%     \caption@set{labelseparator}{none}%
%   \fi
  \caption@ifempty{#2}{%
    \caption@set{labelseparator}{none}%
    \caption@set{textformat}{simple}%
  }%
  \caption@labelseparator % defines \caption@iflabelfont,
%       \caption@labelsep and \caption@labelsep@name
%       (the latter is needed by \caption@fmt)
%
%   \@setpar{\@@par\caption@@par}\caption@@par
  \caption@applyfont
```

\caption@fmt with plain format is defined as {#1#2#3\par}:

```
%   \caption@fmt
    {\ifcaption@star\else
       \begingroup
         \captionlabelfont
         \LWR@isolate{#1}%                        lwarp
       \endgroup
     \fi}%
    {\ifcaption@star\else
       \begingroup
         \caption@iflabelfont\captionlabelfont
         \relax\caption@labelsep
       \endgroup
     \fi}%
    {{\captiontextfont
        \let\\\newline%                           lwarp
%
      \caption@textstart
%       \caption@ifstrut
%         {\vrule\@height\ht\strutbox\@width\z@}%
%         {}%
%       \nobreak\hskip\z@skip % enable hyphenation
      \LWR@isolate{\caption@textformat{#2}}%    lwarp
%       \caption@ifstrut
%         {\ifhmode\@finalstrut\strutbox\fi}%
%         {}%
      \caption@textend}}%
    \LWR@startpars%                               lwarp
\LWR@traceinfo{caption@@@make done}%
}
}% later than 2020/08/23
{% earlier than 2020/08/23
\renewcommand\caption@@@make[2]{%
\LWR@traceinfo{caption@@@make}%
```

```
    \LWR@stoppars%                                lwarp
%   \sbox\@tempboxa{#1}%
%   \ifdim\wd\@tempboxa=\z@
%     \let\caption@lsep\relax
%   \fi
  \caption@ifempty{#2}{%
    \let\caption@lsep\@empty
    \let\caption@tfmt\@firstofone
  }%
%   \@setpar{\@@par\caption@@par}\caption@@par
  \caption@applyfont
```

`\caption@fmt` with `plain` format is defined as `{#1#2#3\par}`:

```
%     \caption@fmt
    {\ifcaption@star\else
       \begingroup
        \captionlabelfont
         \LWR@isolate{#1}%                        lwarp
       \endgroup
     \fi}%
    {\ifcaption@star\else
       \begingroup
         \caption@iflf\captionlabelfont
         \relax
        \caption@lsep
       \endgroup
     \fi}%
    {{%
        \captiontextfont
        \let\\\newline%                           lwarp
%       \caption@ifstrut
%         {\vrule\@height\ht\strutbox\@width\z@}%
%         {}%
%       \nobreak\hskip\z@skip % enable hyphenation
        \LWR@isolate{\caption@tfmt{#2}}%          lwarp
%       \caption@ifstrut
%         {\ifhmode\@finalstrut\strutbox\fi}%
%         {}%
      }}%
    \LWR@startpars%                                lwarp
\LWR@traceinfo{caption@@@make done}%
}
}% earlier than 2020/08/23
```

`\caption@@make@` {⟨⟩} {⟨⟩}

```
\renewcommand{\caption@@make@}[2]{%
  \caption@stepthecounter%
  \caption@beginhook%
      \caption@@@make{#1}{#2}%
  \caption@endhook%
}

\DeclareCaptionBox{none}{#2}
\DeclareCaptionBox{parbox}{%
```

```
    #2%
}

\DeclareCaptionBox{colorbox}{%
    #2%
}
```

File 70 **lwarp-cases.sty**

§ 178 Package cases

(*Emulates or patches code by* Donald Arseneau.)

Pkg cases cases is patched for use by lwarp.

While using MathJax, cases objects are converted to svg math images.

for HTML output:

```
\LWR@ProvidesPackagePass{cases}[2002/05/02]

\BeforeBeginEnvironment{numcases}{
    \begin{BlockClass}{displaymathnumbered}
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}[-cases- \MathImageAltText]
}

\AfterEndEnvironment{numcases}{
    \end{lateximage}\end{BlockClass}
}

\BeforeBeginEnvironment{subnumcases}{
    \begin{BlockClass}{displaymathnumbered}
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}[-cases- \MathImageAltText]
}

\AfterEndEnvironment{subnumcases}{
    \end{lateximage}\end{BlockClass}
}
```

File 71 **lwarp-ccicons.sty**

§ 179 Package ccicons

(*Emulates or patches code by* Michael Ummels.)

Pkg ccicons ccicons is used as svg images for html.

for HTML output: Discard all options for lwarp-ccicons:

```
\LWR@ProvidesPackagePass{ccicons}[2017/10/30]
```

```
\newcommand{\LWR@ccicons}[2]{%
    {\begin{lateximage}*[#1]\ccicons@font\char#2\end{lateximage}}
}
\renewcommand{\ccicons@logo}{\LWR@ccicons{ccLogo}{0}}
\renewcommand{\ccicons@by}{\LWR@ccicons{ccAttribution}{1}}
\renewcommand{\ccicons@sa}{\LWR@ccicons{ccShareAlike}{2}}
\renewcommand{\ccicons@nd}{\LWR@ccicons{ccNoDerivatives}{3}}
\renewcommand{\ccicons@nc}{\LWR@ccicons{ccNonCommercial}{4}}
\renewcommand{\ccicons@nceu}{\LWR@ccicons{ccNonCommercialEU}{5}}
\renewcommand{\ccicons@ncjp}{\LWR@ccicons{ccNonCommercialJP}{6}}
\renewcommand{\ccicons@pd}{\LWR@ccicons{ccPublicDomain}{7}}
\renewcommand{\ccicons@zero}{\LWR@ccicons{ccZero}{8}}
\renewcommand{\ccicons@sampling}{\LWR@ccicons{ccSampling}{9}}
\renewcommand{\ccicons@share}{\LWR@ccicons{ccShare}{10}}
\renewcommand{\ccicons@remix}{\LWR@ccicons{ccRemix}{11}}
\renewcommand{\ccicons@copy}{\LWR@ccicons{ccCopy}{12}}
\renewcommand{\ccicons@pdalt}{\LWR@ccicons{ccPublicDomainAlt}{13}}
```

File 72 **lwarp-centerlastline.sty**

§ 180 Package centerlastline

Pkg centerlastline centerlastline is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{centerlastline}[2020/10/12]

\providecommand{\centerlastline}{}
\def\endcenterlastline{\par}
```

File 73 **lwarp-centernot.sty**

§ 181 Package centernot

(*Emulates or patches code by* Heiko Oberdiek.)

Pkg centernot centernot is used as-is for SVG math, and emulated for MathJax.

for HTML output:

```
\LWR@ProvidesPackagePass{centernot}[2016/05/16]
```

Based on https://github.com/mathjax/MathJax/issues/2107 with \textstyle removed to work with sub/super scripts.

```
\LWR@origRequirePackage{lwarp-common-mathjax-overlaysymbols}

\begin{warpMathJax}
\CustomizeMathJax{\newcommand{\centernot}[1]{%
    \LWRoverlaysymbols{\unicode{x2215}}{#1}
}}
\end{warpMathJax}
```

File 74 **lwarp-changebar.sty**

§ 182 Package changebar

Pkg changebar changebar is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{changebar}[2018/03/09]

\newcommand*{\cbstart}{}
\newcommand*{\cbend}{}
\newenvironment*{\changebar}{}{}
\newcommand*{\cbdelete}{}
\newcommand*{\nochnagebars}{}
\newcommand*{\cbcolor}[1]{}
\newlength{\changebarwidth}
\newlength{\deletebarwidth}
\newlength{\changebarsep}
\newcounter{changebargrey}
```

File 75 **lwarp-changelayout.sty**

§ 183 Package changelayout

(*Emulates or patches code by* Ahmed Musa.)

Pkg changelayout changelayout is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{changelayout}[2009/10/07]

\renewrobustcmd\cpl@backtodefaults{}

\renewrobustcmd\cpl@checkifoddpage{%
  \cpl@oddpagefalse%
}

\renewrobustcmd\changepagelayout[1]{%
  \setkeys[KV]{changelay}{#1}%
}

\renewrobustcmd{\changetextlayout}[1]{\changepagelayout{#1}}

\renewrobustcmd\adjustpagelayout[1]{%
  \setkeys[KV@X]{changelay}{#1}%
}

\renewrobustcmd{\adjusttextlayout}[1]{\adjustpagelayout{#1}}

\renewrobustcmd\adjusttextwidth[1]{%
  \setkeys[KV]{changelay}{#1}%
```

```
  \begin{BlockClass}[color:\LWR@colorstyle{named}{\cpl@textcolor}]{changelayout}
      \color{\cpl@textcolor}%
      \cpl@content
   \end{BlockClass}
}
```

File 76 **lwarp-changepage.sty**

§ 184 Package

changepage

(*Emulates or patches code by* Peter Wilson.)

Pkg changepage changepage is ignored.

for HTML output: Discard all options for lwarp-changepage:

```
\LWR@ProvidesPackageDrop{changepage}[2009/10/20]

\newif\ifoddpage
\DeclareRobustCommand{\checkoddpage}{\oddpagetrue}
\DeclareRobustCommand{\changetext}[5]{}
\DeclareRobustCommand{\changepage}[9]{}

\@ifundefined{adjustwidth}{
\newenvironment{adjustwidth}[2]{}{}
\newenvironment{adjustwidth*}[2]{}{}
}{
\renewenvironment{adjustwidth}[2]{}{}
\renewenvironment{adjustwidth*}[2]{}{}
}

\DeclareDocumentCommand{\strictpagecheck}{}{}
\DeclareDocumentCommand{\easypagecheck}{}{}
```

File 77 **lwarp-changes.sty**

§ 185 Package

changes

(*Emulates or patches code by* Ekkart Kleinod.)

Pkg changes changes is patched for use by lwarp.

⚠ \comment Use commandnameprefix=ifneeded to avoid a conflict with the \comment command when using lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{changes}[2021/02/14]
```

\BaseJobname is added to the label in case xr or xr-hyper are used.

```
\renewcommand{\ChangesListline}[4]{%
```

```
    \IfIsInList{#1}{\Changes@loc@show}{%
        \LWR@startpars%
        #2: #3 \qquad
        \nameref{\BaseJobname-autopage-#4}%
        \LWR@stoppars%
    }{}%
}

\renewcommand{\listofchanges}[1][\@empty]{%
\setkeys{Changes@loc}{#1}%
\ifbool{Changes@optiondraft}%
{%
\IfIsInList{\Changes@loc@style}{list|summary|compactsummary}%
{}%
{%
\PackageWarning{changes}{Wrong style for list of changes: '\Changes@loc@style', using 'list' instead.}%
\def\Changes@loc@style{}%
}%
\IfIsEmpty{\Changes@loc@style}%
{\def\Changes@loc@style{list}}%
{}%
\IfStrEq{\Changes@loc@show}{all}%
{\def\Changes@loc@show{added|deleted|replaced|highlight|comment}}%
{}%
\IfIsInList{\Changes@loc@show}{added|deleted|replaced|highlight|comment}%
{}%
{%
\PackageWarning{changes}{Wrong show-value for list of changes: '\Changes@loc@show', using 'all' instead.}
\def\Changes@loc@show{}%
}%
\IfIsEmpty{\Changes@loc@show}%
{\def\Changes@loc@show{added|deleted|replaced|highlight|comment}}%
{}%
\IfIsEmpty{\Changes@loc@title}%
{%
\IfStrEq{\Changes@loc@style}{list}%
{\def\Changes@heading{\listofchangesname}}{}%
\IfStrEq{\Changes@loc@style}{summary}%
{\def\Changes@heading{\summaryofchangesname}}{}%
\IfStrEq{\Changes@loc@style}{compactsummary}%
{\def\Changes@heading{\compactsummaryofchangesname}}{}%
}%
{\def\Changes@heading{\Changes@loc@title}}%
\section*{\Changes@heading}
\IfIsInList{\Changes@loc@style}{list}%
{%
\IfFileExists{\jobname.\Changes@locextension}%
{%
\newread\Changes@InFile%
\openin\Changes@InFile=\jobname.\Changes@locextension%
\loop\unless\ifeof\Changes@InFile%
\read\Changes@InFile to \Changes@Line%
\ifeof\Changes@InFile\else%
\Changes@Line%
\fi
```

```
\repeat
\closein\Changes@InFile%
}{%
\emph{\changesnoloc}%
\PackageWarning{changes}{LaTeX rerun needed for list of changes}%
}%
}{}%
\IfIsInList{\Changes@loc@style}{summary|compactsummary}%
{%
\IfFileExists{\jobname.\Changes@socextension}%
{%
\newread\Changes@InFile%
\openin\Changes@InFile = \jobname.\Changes@socextension%
\loop\unless\ifeof\Changes@InFile%
\read\Changes@InFile to \Changes@Line%
\ifeof\Changes@InFile\else%
\expandafter\changes@chopline\Changes@Line\\%
\textbf{%
\IfIsColored%
{\color{\Changes@Incolor}}%
{}%
\IfIsAnonymous{\Changes@Inid}%
{%
    \LWR@textcurrentcolor{%     lwarp
        \changesauthorname: \changesanonymousname%
    }%  lwarp
}%
{%
    \LWR@textcurrentcolor{%     lwarp
\changesauthorname: \Changes@Inid%
    }%  lwarp
\IfIsEmpty{\Changes@Inname}%
{}%
{ %
    \LWR@textcurrentcolor{%     lwarp
(\Changes@Inname)%
    }%  lwarp
}%
}%
}\\%
\numdef{\Changes@InSum}{0}%
\renewcommand*{\do}[1]{%
\numdef{\Changes@InSum}{\Changes@InSum + \csuse{Changes@In########1}}%
}%
\expandafter\dopsvlist\expandafter{\Changes@loc@show}%
\ifnumcomp{\Changes@InSum}{=}{0}%
{%
% \parbox{\Changes@summary@width}{% lwarp
    \changesnochanges%
% }%    lwarp
% \\[1ex]%    lwarp
    \par%   \lwarp
}%
{%
\numdef{\Changes@InCount}{0}%
```

```
\renewcommand*{\do}[1]{%
\numdef{\Changes@InCount}{\Changes@InCount + \csuse{Changes@In########1}}%
\ifboolexpr{%
not test {\IfStrEq{\Changes@loc@style}{compactsummary}} or%
test {\ifnumgreater{\csuse{Changes@In########1}}{0}}%
}%
{%
% \parbox{\Changes@summary@width}{%  lwarp
\csuse{changes########1name}~%
% \let\cleaders\leaders\dotfill~%   lwarp
\dotfill~%   \lwarp
\csuse{Changes@In########1}%
% }%    lwarp
% \ifnumless{\Changes@InCount}{\Changes@InSum}%     lwarp
{\\}%
% {\\[1ex]}%    lwarp
}%
{}%
}%
\expandafter\dopsvlist\expandafter{\Changes@loc@show}%
    \par%   lwarp
}%
\fi%
\repeat
\closein\Changes@InFile%
}{%
\emph{\changesnosoc}%
\PackageWarning{changes}{LaTeX rerun needed for summary of changes}%
}%
}{}%
}{}%
}


\renewcommand{\Changes@Markup@comment}[3]{%
\IfStrEq{\Changes@optioncommentmarkup}{todo}%
{%
\IfIsColored%
{\colorlet{Changes@todocolor}{authorcolor}}%
{\colorlet{Changes@todocolor}{black}}%
\todo[color=Changes@todocolor!10, bordercolor=Changes@todocolor, linecolor=Changes@todocolor!70, nolist
}{}%
\IfStrEq{\Changes@optioncommentmarkup}{margin}%
{%
\marginpar{%
\IfIsColored%
{\leavevmode\color{authorcolor}}%
{}%
    \LWR@textcurrentcolor{%     lwarp
\textbf{[\IfIsAnonymous{#2}{}{#3~}\arabic{Changes@commentCount#2}]:} #1%
    }%  lwarp
}%
}{}%
\IfStrEq{\Changes@optioncommentmarkup}{footnote}%
{%
```

```
\footnote{%
    \LWR@textcurrentcolor{%     lwarp
\textbf{[\IfIsAnonymous{#2}{}{#3~}\arabic{Changes@commentCount#2}]:} #1%
    }%  lwarp
}%
}{}%
\IfStrEq{\Changes@optioncommentmarkup}{uwave}%
{%
{%
\IfIsColored%
{\color{authorcolor}}%
{}%
\allowbreak%
\uwave{%
\textbf{[\IfIsAnonymous{#2}{}{#3~}\arabic{Changes@commentCount#2}]:} #1%
}%
}%
}{}%
}

\renewrobustcmd{\Changes@output}[7]{%
\ifbool{Changes@optiondraft}%
{%
\Changes@check@author{#2}%
\Changes@set@color{#2}%
{%
\IfIsInList{#1}{added|deleted|replaced|highlight}%
{%
\IfIsEmpty{#5}%
{%
\IfIsAuthorEmptyAtPosition{#2}{left}%
{}%
{{%
\IfIsColored%
{\color{authorcolor}}%
{}%
    \LWR@textcurrentcolor{%     lwarp
\Changes@Markup@author{\Changes@output@author{#2}{left}}%
    }%  lwarp
}}%
}{}%
{%
\IfStrEq{#1}{highlight}%
{}{%
\IfIsColored%
{\color{authorcolor}}%
{}%
}%
    \LWR@textcurrentcolor{%     lwarp
\IfStrEq{#1}{added}{\Changes@Markup@added{#3}}{}%
\IfStrEq{#1}{deleted}{\Changes@Markup@deleted{#4}}{}%
\IfStrEq{#1}{replaced}{{\Changes@Markup@added{#3}}\allowbreak\Changes@Markup@deleted{#4}}{}%
\IfStrEq{#1}{highlight}{\Changes@Markup@highlight{#3}}{}%
    }%  lwarp
}%
```

```
\IfIsEmpty{#5}%
{%
\IfIsAuthorEmptyAtPosition{#2}{right}%
{}%
{{%
\IfIsColored%
{\color{authorcolor}}%
{}%
    \LWR@textcurrentcolor{%     lwarp
\Changes@Markup@author{\Changes@output@author{#2}{right}}%
    }%  lwarp
}}%
}{}%
\stepcounter{Changes@#1Count#2}%
}{}%
\IfIsEmpty{#5}%
{}%
{%
\stepcounter{Changes@commentCount#2}%
\Changes@set@commentcount{#2}%
\Changes@Markup@comment%
{#5}%
{#2}%
{\Changes@output@author{#2}{left}\Changes@output@author{#2}{right}}%
}%
}%
\IfIsEmpty{#2}%
{\def\Changes@locid{}}%
{\def\Changes@locid{~(#2)}}%
\addtocontents{\Changes@locextension}{\protect\ChangesListline{#1}{#6\Changes@locid}{#7}{\thepage}}%
}%
{%
\IfIsEmpty{#3}%
{\@bsphack\@esphack}%
{#3}%
}%
}
```

File 78 **lwarp-chappg.sty**

§ 186 Package

chappg

(*Emulates or patches code by* Robin Fairbairns.)

Pkg chappg chappg is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{chappg}[2006/05/09]

\renewcommand{\pagenumbering}[2][]{}
\providecommand{\chappgsep}{--}
```

File 79 **lwarp-chapterbib.sty**

§ 187 Package chapterbib

(*Emulates or patches code by* Donald Arseneau.)

Pkg chapterbib chapterbib is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{chapterbib}[2010/09/18]

\xdef\@savedjobname{\BaseJobname}
\let\@currentipfile\@savedjobname
```

File 80 **lwarp-chemfig.sty**

§ 188 Package chemfig

(*Emulates or patches code by* Christian Tellechea.)

Pkg chemfig chemfig is patched for use by lwarp.

If using `\polymerdelim` to add delimiters to a `\chemfig`, wrap both inside a single `lateximage`:

```
\begin{lateximage}[-chemfig-~\PackageDiagramAltText]
\chemfig{. . . }
\polymerdelim[. . . ]{. . . }
\end{lateximage}
```

The images are not hashed because they depend on external settings which may be changed at any time, and are unlikely to be reused inline anyhow.

for HTML output:

```
\LWR@ProvidesPackagePass{chemfig}[2021/02/28]

\catcode`\_=11

\@ifpackagelater{chemfig}{2020/03/05}
{
    \xpretocmd\charge{\begin{lateximage}[-chemfig-~\PackageDiagramAltText]}
        {}{\LWR@patcherror{chemfig}{charge}}
    \xpretocmd\Charge{\begin{lateximage}[-chemfig-~\PackageDiagramAltText]}
        {}{\LWR@patcherror{chemfig}{Charge}}
    \xapptocmd\charge_c{\end{lateximage}}
        {}{\LWR@patcherror{chemfig}{charge_c}}
}{}

\@ifpackagelater{chemfig}{2019/04/18}%
{% 2019/04/18 or newer

    \xpretocmd{\CF_chemfiga}
        {\begin{lateximage}[-chemfig-~\PackageDiagramAltText]}
        {}{\LWR@patcherror{chemfig}{CF_chemfiga}}

    \xpatchcmd{\CF_chemfigb}
```

```
        {\let\CF_flipstate\CF_zero}
        {\end{lateximage}\let\CF_flipstate\CF_zero}
        {}{\LWR@patcherror{chemfig}{CF_chemfigb}}

    \GlobalLetLtxMacro\LWR@chemfig@origCF_lewisc\CF_lewisc
    \gdef\CF_lewisc#1,#2\_nil{%
    \begin{lateximage}[-chemfig-~\PackageDiagramAltText]%
    \LWR@chemfig@origCF_lewisc#1,#2\_nil
    \end{lateximage}
    }

    \gpreto{\schemestart}{%
        \begin{lateximage}[-chemfig-~\PackageDiagramAltText]%
    }
    \gappto{\CF_schemestop}{\end{lateximage}}

}% 2019/04/18 or newer
{% older than 2019/04/18

    \LetLtxMacro\LWR@chemfig@origchemfig\chemfig

    \DeclareDocumentCommand\chemfig{s O{} O{} m}{%
        \begin{lateximage}[-chemfig-~\PackageDiagramAltText]%
        \IfBooleanTF{#1}{%
            \LWR@chemfig@origchemfig*[#2][#3]{#4}%
        }{%
            \LWR@chemfig@origchemfig[#2][#3]{#4}%
        }
        \end{lateximage}%
    }

    \LetLtxMacro\LWR@chemfig@origCF@lewis@b\CF@lewis@b

    \def\CF@lewis@b#1#2{%
    \begin{lateximage}[-chemfig-~\PackageDiagramAltText]%
    \LWR@chemfig@origCF@lewis@b{#1}{#2}%
    \end{lateximage}%
    }

    \preto{\schemestart}{%
        \begin{lateximage}[-chemfig-~\PackageDiagramAltText]%
    }
    \appto{\CF@schemestop}{\end{lateximage}}

}% older than 2019/04/18

\catcode`\_=8%



\LetLtxMacro\LWR@chemfig@origchemleft\chemleft

\def\chemleft#1#2\chemright#3{%
\begin{lateximage}[-chemfig-~\PackageDiagramAltText]%
\LWR@chemfig@origchemleft#1#2\chemright#3%
```

```
\end{lateximage}%
}

\LetLtxMacro\LWR@chemfig@origchemup\chemup

\def\chemup#1#2\chemdown#3{%
\begin{lateximage}[-chemfig-~\PackageDiagramAltText]%
\LWR@chemfig@origchemup#1#2\chemdown#3%
\end{lateximage}%
}
```

File 81 **lwarp-chemformula.sty**

§ 189 Package

chemformula

(*Emulates or patches code by* Clemens Niederberger.)

Pkg chemformula

chemformula is patched for use by lwarp.

The SVG images are hashed according to contents and local options. Global options are assumed to be constant document-wide.

⚠ chemformula with MathJax

chemformula works best without MathJax. If MathJax is used, `\displaymathother` must be used before `array`, and then `\displaymathnormal` may be used after. (The chemformula package adapts to `array`, but does not know about MathJax, and MathJax does not know about chemformula.)

While using MathJax, `\displaymathother` may also be used for other forms of display and inline math which contain chemformula expressions.

for HTML output:

```
\LWR@ProvidesPackagePass{chemformula}[2019/10/13]

\ExplSyntaxOn
```

`\ch`

Enclose in an inline SVG image or MathJax. The `alt` tag is is the contents of the `\ch` expression. The filename is hashed, and also has additional hashing information based on the local options.

```
\RenewDocumentCommand \ch { O{}m }
 {%
```

To work inside `align` with `\displaymathother`, a simple version must be used to work with chemformula's adaptation to `align`.

```
    \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%  lwarp
    {
        \chemformula_ch:nn {#1} {#2}%   original
    }
```

If used as the outer level, must temporarily ensure MathJax is disabled:

```
    {
        \begingroup%
        \boolfalse{mathjax}%
```

An inline image is used, adjusted for the baseline:

```
        \LWR@subsingledollar*{% lwarp
            \textbackslash{}ch\{\LWR@HTMLsanitize{#2}\}% alt text
        }{%
         \protect\LWR@HTMLsanitize{\detokenize\expandafter{#1}}% add'l hashing
        }%
        {%
            \chemformula_ch:nn {#1} {#2}%   original
        }%
        \endgroup%
    }
  }
```

\chcpd Similar to \ch.

```
\@ifpackagelater{chemformula}{2019/10/13}{
\cs_gset_protected:Npn \chemformula_chcpd:nn #1#2
  {
    \begingroup%
    \boolfalse{mathjax}%
    \LWR@subsingledollar*{% lwarp
        \textbackslash{}chcpd\{\LWR@HTMLsanitize{#2}\}%
    }{%
        \protect\LWR@HTMLsanitize{\detokenize\expandafter{#1}}%
    }{% original
    \group_begin:
      \tl_if_blank:nF {#2}
        {
          \keys_set:nn {chemformula} {#1}
          \__chemformula_save_catcodes:
          \__chemformula_sanitize:Nn
            \l__chemformula_chemformula_tmpa_tl
            {#2}
          \__chemformula_input_compound_no_check:NV
            \l__chemformula_compound_tl
            \l__chemformula_chemformula_tmpa_tl
          \__chemformula_prepare_output:NV
            \l__chemformula_compound_tl
            \l__chemformula_catcodes_tl
          \chemformula_write:V \l__chemformula_compound_tl
        }
    \group_end:
    }
    \endgroup
  }
}% later than 2019/10/13
{% earlier than 2019/10/13
\cs_gset_protected:Npn \chemformula_chcpd:nn #1#2
  {
    \begingroup%
    \boolfalse{mathjax}%
    \LWR@subsingledollar*{% lwarp
        \textbackslash{}chcpd\{\LWR@HTMLsanitize{#2}\}%
    }{%
        \protect\LWR@HTMLsanitize{\detokenize\expandafter{#1}}%
```

```
    }{% original
    \group_begin:
      \tl_if_blank:nF {#2}
        {
          \keys_set:nn {chemformula} {#1}
          \__chemformula_save_catcodes:
          \__chemformula_sanitize:Nn
            \l__chemformula_chemformula_tmpa_tl
            {#2}
          \__chemformula_input_compound_no_check:NV
            \l__chemformula_compound_tl
            \l__chemformula_chemformula_tmpa_tl
          \__chemformula_prepare_output:N \l__chemformula_compound_tl
          \chemformula_write:V \l__chemformula_compound_tl
        }
    \group_end:
    }
    \endgroup
  }
}% earlier than 2019/10/13
```

\charrow If standalone, appears in a regular lateximage.

```
\RenewDocumentCommand \charrow { mO{}O{} }
{
    \begin{lateximage}[-chemformula- charrow]
    \group_begin:
      \__chemformula_draw_arrow:nnn {#1} {#2} {#3}
    \group_end:
    \end{lateximage}
}
```

\chname If standalone, appears in a regular lateximage, hashed according to contents.

```
\RenewDocumentCommand \chname { R(){}R(){} }
  {
    \begin{lateximage}*[%
        \textbackslash{}chname(\LWR@HTMLsanitize{#1})(\LWR@HTMLsanitize{#2})
    ]*%
        \chemformula_chwritebelow:nn {#1} {#2}
    \end{lateximage}
  }
```

\chlewis Placed inline, hashed according to contents and options.

```
\RenewDocumentCommand \chlewis { O{}mm }
  {
    \begingroup%
    \boolfalse{mathjax}%
    \LWR@subsingledollar*{\textbackslash{}chlewis\{#2\}\{#3\}}%
    {
        \protect\LWR@HTMLsanitize{\detokenize\expandafter{#1}}%
    }{
        \chemformula_lewis:nnn {#1} {#2} {#3}
    }
```

```
    \endgroup%
}
```

lwarp redefines the $ character, so special handling is required to escape math expressions inside \ch.

This boolean tracks a new kind of escaped math:

```
\bool_new:N       \l__chemformula_first_last_LWRdollar_bool
```

\chemformula_input_escape_math

Adds additional escaping for the new dollar definition:

```
\cs_gset_protected:Npn \__chemformula_input_escape_math:n #1
 {
   \__chemformula_first_last_math:n {#1}
   \bool_if:NT \l__chemformula_first_last_dollar_bool
     {
       \bool_set_true:N \l__chemformula_first_last_math_bool
       \__chemformula_read_escape_dollar:w #1 \q_nil
     }
   \bool_if:NT \l__chemformula_first_last_mathbraces_bool
     {
       \bool_set_true:N \l__chemformula_first_last_math_bool
       \__chemformula_read_escape_mathbraces:w #1 \q_nil
     }
```

Added by lwarp:

```
   \bool_if:NT \l__chemformula_first_last_LWRdollar_bool%      lwarp
     {                                                         lwarp
       \bool_set_true:N \l__chemformula_first_last_math_bool%  lwarp
       \__chemformula_read_escape_LWRdollar:w #1 \q_nil%       lwarp
     }                                                         lwarp
 }
```

\chemformula_read_escape_LWRdollar

The following parses the contents inside the new dollars.

lwarp keeps the dollar as its original math shift until the document starts. While chemmacros is being patched, the dollar must temporarily be set to its new meaning during the following definition.

```
\begingroup
\catcode`\$=\active

\cs_new_protected:Npn \__chemformula_read_escape_LWRdollar:w $#1$ \q_nil
{
    \__chemformula_read_escape_math:n {#1}
}

\endgroup
```

\chemformula_bool_set_if_first_last

The following looks at the first and last tokens for delimiters to escape math inside \ch. The original definition is modified to look for the control sequences which are used by the new meaning of $.

```
\cs_new_protected:Npn \__chemformula_bool_cs_set_if_first_last:NnNN #1#2#3#4
  {
    \int_zero:N \l__chemformula_tmpa_int
    \int_zero:N \l__chemformula_tmpb_int
    \int_set:Nn \l__chemformula_tmpa_int { \tl_count:n {#2} }
    \tl_map_inline:nn {#2}
      {
        \int_incr:N \l__chemformula_tmpb_int
        \int_compare:nT { \l__chemformula_tmpb_int = 1 }
          {
```

At the start, the cs_ version compares control sequences:

```
            \ifdefstrequal{##1}{#3}% lwarp
                {
                    \bool_set_true:N #1
                }% lwarp
                {}
          }
```

At the end, compare more control sequences:

```
        \int_compare:nT { \l__chemformula_tmpb_int = \l__chemformula_tmpa_int }
          {
            \ifdefstrequal{##1}{#4}
                {}
                {
                    \bool_set_false:N #1
                }
          }
      }
  }
```

\chemformula_first_last_math

Modified to check for the new meaning of $ at first/last:

```
\cs_gset_protected:Npn \__chemformula_first_last_math:n #1
  {
    \bool_set_false:N \l__chemformula_first_last_math_bool
    \bool_set_false:N \l__chemformula_first_last_dollar_bool
    \bool_set_false:N \l__chemformula_first_last_LWRdollar_bool%    lwarp
    \bool_set_false:N \l__chemformula_first_last_mathbraces_bool
    \__chemformula_bool_set_if_first_last:Nnnn
      \l__chemformula_first_last_dollar_bool
      {#1}
      { $ } { $ }
    \bool_if:NF \l__chemformula_first_last_dollar_bool
      {
        \__chemformula_bool_set_if_first_last:Nnnn
          \l__chemformula_first_last_mathbraces_bool
```

```
          {#1}
          { \( } { \) }
```

Added by lwarp:

```
          \bool_if:NF \l__chemformula_first_last_mathbraces_bool%   lwarp
            {
                \__chemformula_bool_cs_set_if_first_last:NnNN
                \l__chemformula_first_last_LWRdollar_bool
                {#1}
                { \LWR@newsingledollar } { \LWR@newsingledollar }
            }%  lwarp
      }
  }

\ExplSyntaxOff
```

File 82 **lwarp-chemgreek.sty**

§ 190 Package

chemgreek

(*Emulates or patches code by* Clemens Niederberger.)

Pkg chemgreek chemgreek is patched for use by lwarp.

Greek symbols
⚠ package selection To use text-mode symbols, use packages textalpha or textgreek. Using the other packages supported by chemgreek will result in math-mode greek characters, which will result in SVG images being used. These images will be hashed.

⚠ XeLaTeX, LuaLaTeX If using XeLaTeX or LuaLaTeX, select the fontspec mapping:

```
\selectchemgreekmapping{fontspec}
```

for HTML output:

```
\LWR@ProvidesPackagePass{chemgreek}[2020/01/16]

\ExplSyntaxOn

\cs_gset_protected:Npn \chemgreek_text:n #1
  { { \text {#1} } }

\appto\LWR@restoreorigformatting{%
\cs_set_protected:Npn \chemgreek_text:n #1%
  { \ensuremath { \text {#1} } }%
}

\ExplSyntaxOff
```

File 83 **lwarp-chemmacros.sty**

§ 191 Package

chemmacros

(*Emulates or patches code by* Clemens Niederberger.)

Pkg chemmacros chemmacros is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{chemmacros}[2017/08/28]
```

SVG file hashing assumes that the relevent options are constant for the entire document.

§ 191.1 Changes to the user's document

⚠ \makepolymerdelims When using \makepolymerdelims, enclose the entire expression inside a polymerdelims environment, such as (from the chemmacros manual):

```
\begin{polymerdelims}
\chemfig{-[@{op,.75}]CH_2-CH(-[6]Cl)-[@{cl,0.25}]}
\makepolymerdelims{5pt}[27pt]{op}{cl}
\end{polymerdelims}
```

⚠ redox reactions Redox reactions must be enclosed inside a redoxreaction environment. For print output, extra space must be included above and/or below the result, so they are declared as arguments to the environment, instead of being manually entered as per the chemmacros manual. For HTML output, the extra space is ignored and a lateximage is used instead.

```
\begin{redoxreaction}{7mm}{7mm}
\OX{a,Na} $\rightarrow$ \OX{b,Na}\pch\redox(a,b){oxidation}
\end{redoxreaction}
```

§ 191.2 Code

§ 191.3 Loading modules

Patching chemmacros modules must be done \AtBeginDocument, since modules are invoked by the user in the preamble, and each patch is only done if the module is loaded.

```
\ExplSyntaxOn

\newcommand{\@ifchemmacrosmoduleloaded}[1]{%
\@ifl@aded{\c__chemmacros_module_extension_tl}{\c__chemmacros_module_prefix_tl.#1}%
}

\ExplSyntaxOff
```

§ 191.4 New environments

\makepolymerdelims and redox reactions must be enclosed in a lateximage during HTML output. These environments are provided here in HTML mode, and in the lwarp core in print mode, as a high-level semantic syntax which automatically embeds the contents in a lateximage with an appropriate alt tag.

Env polymerdelims

```
\DeclareDocumentEnvironment{polymerdelims}{}
{\begin{lateximage}[-chemmacros- polymer]}
{\end{lateximage}}
```

Env redoxreaction {⟨*space above*⟩} {⟨*space below*⟩}

For HTML output, the above and below space is ignored, and a `lateximage` is used instead. For the print output version, see section 90.

```
\DeclareDocumentEnvironment{redoxreaction}{m m}
{\begin{lateximage}[-chemmacros- redoxreaction]}
{\end{lateximage}}

\ExplSyntaxOn
```

§ 191.5 Acid-base

```
\AtBeginDocument{
\@ifchemmacrosmoduleloaded{acid-base}{
\PackageInfo{lwarp}{Patching~chemmacros~module~acid-base}

\cs_gset_protected:Npn \chemmacros_p:n #1
  {
    \begingroup
    \boolfalse{mathjax}
    \LWR@subsingledollar*{
        \textbackslash{}p\{\LWR@HTMLsanitize{#1}\}
    }{
        chemmacrosp\protect\LWR@HTMLsanitize{\detokenize\expandafter{#1}}%
    }{
    \group_begin:
      \mbox
        {
          \chemmacros_p_style:n {p}
          \ensuremath {#1}
        }
    \group_end:
    }
    \endgroup
  }

\RenewDocumentCommand \pH  {} {
    \begingroup
    \boolfalse{mathjax}
    \LWR@subsingledollar*{\textbackslash{}pH}{chemmacros}{
        \chemmacros_p:n { \chemmacros_chemformula:n {H} }
    }
    \endgroup
}

\RenewDocumentCommand \pOH {} {
    \begingroup
    \boolfalse{mathjax}
    \LWR@subsingledollar*{\textbackslash{}pOH}{chemmacros}{
        \chemmacros_p:n { \chemmacros_chemformula:n {OH} }
    }
    \endgroup
}

```

```
\RenewDocumentCommand \pKa {O{}}
  {
    \begingroup
    \boolfalse{mathjax}
    \LWR@subsingledollar*{\textbackslash{}pKa{[}#1{]}}{chemmacros #1}{
        \chemmacros_p:n
        {
            \Ka \ifblank {#1} {}
            { {} \c_math_subscript_token { \chemmacros_bold:n {#1} } }
        }
    }
    \endgroup
  }

\RenewDocumentCommand \pKb {O{}}
  {
    \begingroup
    \boolfalse{mathjax}
    \LWR@subsingledollar*{\textbackslash{}pKb{[}#1{]}}{chemmacros #1}{
        \chemmacros_p:n
        {
            \Kb \ifblank {#1} {}
            { {} \c_math_subscript_token { \chemmacros_bold:n {#1} } }
        }
    }
    \endgroup
  }

\LetLtxMacro\LWR@chemmacros@origKa\Ka
\renewcommand*{\Ka}{%
    \begingroup
    \boolfalse{mathjax}
    \LWR@subsingledollar*{\textbackslash{}Ka}{chemmacros}{%
        \LWR@chemmacros@origKa%
    }%
    \endgroup
}

\LetLtxMacro\LWR@chemmacros@origKb\Kb
\renewcommand*{\Kb}{%
    \begingroup
    \boolfalse{mathjax}
    \LWR@subsingledollar*{\textbackslash{}Kb}{chemmacros}{%
        \LWR@chemmacros@origKb%
    }%
    \endgroup
}

\LetLtxMacro\LWR@chemmacros@origKw\Kw
\renewcommand*{\Kw}{%
    \begingroup
    \boolfalse{mathjax}
    \LWR@subsingledollar*{\textbackslash{}Kw}{chemmacros}{
        \LWR@chemmacros@origKw
    }
```

```
    \endgroup
}

}{}% \@ifchemmacrosmoduleloaded
}% AtBeginDocument
```

§ 191.6 Charges

```
\AtBeginDocument{
\@ifchemmacrosmoduleloaded{charges}{
\PackageInfo{lwarp}{Patching~chemmacros~module~charges}

\cs_gset_protected:Npn \fplus  {
    \begingroup
    \boolfalse{mathjax}
    \LWR@subsingledollar*{\textbackslash{}fplus}{chemmacros}
    { \LWR@origensuredmath{\chemformula_fplus:}  }
    \endgroup
}
\cs_gset_protected:Npn \fminus {
    \begingroup
    \boolfalse{mathjax}
    \LWR@subsingledollar*{\textbackslash{}fminus}{chemmacros}
    { \LWR@origensuredmath{\chemformula_fminus:} }
    \endgroup
}

}{}% \@ifchemmacrosmoduleloaded
}% AtBeginDocument
```

§ 191.7 Nomenclature

```
\AtBeginDocument{
\@ifchemmacrosmoduleloaded{nomenclature}{
\PackageInfo{lwarp}{Patching~chemmacros~module~nomenclature}

\cs_gset_protected:Npn \chemmacros_charge:n #1
  {
    \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}
    {\chemmacros_chemformula:n { {}^{#1} }}
    {
        \ifmmode
            {\chemmacros_chemformula:n { {}^{#1} }}
        \else
            { \textsuperscript{\ensuremath{#1}} }
        \fi
    }
  }


\LetLtxMacro\LWR@chemmacros@origchemprime\chemprime

\protected\def\chemprime { \HTMLunicode{2032} }

\appto\LWR@restoreorigformatting{%
```

```
\LetLtxMacro\chemprime\LWR@chemmacros@origchemprime%
}

\ChemCompatibilityFrom{5.8}
\cs_gset_protected:Npn \__chemmacros_cip:n #1
  {
    \tl_set:Nn \l__chemmacros_tmpa_tl {#1}
    \int_step_inline:nnnn {0} {1} {9}
      {
        \tl_replace_all:Nnn \l__chemmacros_tmpa_tl
          {##1}
          { { \l__chemmacros_cip_number_tl ##1} }
      }
    {
        \l__chemmacros_cip_inner_tl
        \LWR@textcurrentcolor{\LWR@textcurrentfont{% lwarp
            \l__chemmacros_tmpa_tl
        }}% lwarp
    }
  }
\EndChemCompatibility

\RenewDocumentCommand \Sconf { O{S} } {
\begin{lateximage}[\textbackslash{}Sconf{[}#1{]}]*
    \chemmacros_sconf:n {#1}
\end{lateximage}
}

\RenewDocumentCommand \Rconf { O{R} } {
\begin{lateximage}[\textbackslash{}Rconf{[}#1{]}]*
    \chemmacros_rconf:n {#1}
\end{lateximage}
}

\cs_gset_protected:Npn \chemmacros_hapto:n #1
  {
    \begingroup
    \boolfalse{mathjax}
    \LWR@subsingledollar*{\textbackslash{}hapto\{#1\}}{chemmacros}{
        \chemmacros_coordination_symbol:nnnn
        { \l__chemmacros_coord_use_hyphen_bool }
        {
            \chemmacros_if_compatibility:nnTF {>} {5.7}
            { \c_true_bool }
            { \c_false_bool }
        }
        { \chemeta }
        {#1}
    }
    \endgroup
  }

\cs_gset_protected:Npn \chemmacros_dento:n #1
  {
    \begingroup
    \boolfalse{mathjax}
```

```
    \LWR@subsingledollar*{\textbackslash{}dento\{#1\}}{chemmacros}{
        \chemmacros_coordination_symbol:nnnn
        { \l__chemmacros_coord_use_hyphen_bool }
        {
            \chemmacros_if_compatibility:nnTF {>} {5.7}
            { \c_true_bool }
            { \c_false_bool }
        }
        { \chemkappa }
        {#1}
    }
    \endgroup
  }

\cs_gset_protected:Npn \chemmacros_bridge:n #1
  {
    \begingroup
    \boolfalse{mathjax}
    \LWR@subsingledollar*{\textbackslash{}bridge\{#1\}}{chemmacros}{
        \chemmacros_coordination_symbol:nnnn
        { \l__chemmacros_coord_use_hyphen_bool }
        { \l__chemmacros_bridge_super_bool }
        { \chemmu }
        {#1}
    }
    \endgroup
  }
}{}% \@ifchemmacrosmoduleloaded
}% AtBeginDocument
```

§ 191.8 Particles

```
\AtBeginDocument{
\@ifchemmacrosmoduleloaded{particles}{
\PackageInfo{lwarp}{Patching~chemmacros~module~particles}

\cs_gset_protected:Npn \chemmacros_declare_nucleophile:Nn #1#2
  {
    \cs_set_protected:cpn {__chemmacros_ \chemmacros_remove_backslash:N #1:}
      {
        \bool_if:NTF \l__chemmacros_nucleophile_elpair_bool
          {
            \chemmacros_elpair:n { #2 }
            \chemmacros_if_compatibility:nnT {>=} {5.3}
              { \skip_horizontal:N \l__chemmacros_nucleophile_dim }
            \chemmacros_chemformula:n { {}^{-} }
          }
          { \chemmacros_chemformula:n { #2^{-} } }
      }
    \DeclareDocumentCommand #1 {o}
      {%
        \begin{lateximage}%
        \group_begin:%
          \IfNoValueF {##1}%
            { \chemmacros_set_keys:nn {particles} {##1} }%
          \use:c {__chemmacros_ \chemmacros_remove_backslash:N #1:}%
```

```
        \group_end:%
        \end{lateximage}%
      }
  }

\RenewChemNucleophile \Nuc {Nu}
\RenewChemNucleophile \ba  {ba}

}{}% \@ifchemmacrosmoduleloaded
}% AtBeginDocument
```

§ 191.9 Phases

```
\AtBeginDocument{
\@ifchemmacrosmoduleloaded{phases}{
\PackageInfo{lwarp}{Patching~chemmacros~module~phases}

\cs_undefine:N \chemmacros_phase:n
\cs_new_protected:Npn \chemmacros_phase:n #1
  {

    \mode_leave_vertical:

    \bool_if:NTF \l__chemmacros_phases_sub_bool
      {
        \ifnumequal{\value{LWR@lateximagedepth}}{0}
        {
            \textsubscript{ (#1) }
        }
        {
            \chemformula_subscript:n { (#1) }
        }
      }
      {
        \skip_horizontal:N \l__chemmacros_phases_space_dim
        \chemmacros_text:n { (#1) }
      }
  }

}{}% \@ifchemmacrosmoduleloaded
}% AtBeginDocument
```

§ 191.10 Mechanisms

```
\AtBeginDocument{
\@ifchemmacrosmoduleloaded{mechanisms}{
\PackageInfo{lwarp}{Patching~chemmacros~module~mechanisms}

\chemmacros_define_keys:nn {textmechanisms}
  {
    type      .choice: ,
    type /    .code:n    =
      {
        \__chemmacros_set_mechanisms:nnn { S }
          {
```

```
            \textsubscript{N}
        }
        { }
    } ,
  type / 1  .code:n    =
    {
      \__chemmacros_set_mechanisms:nnn { S }
        {
            \textsubscript{N}
          1
        }
        { }
    } ,
  type / 2  .code:n    =
    {
      \__chemmacros_set_mechanisms:nnn { S }
        {
            \textsubscript{N}
          2
        }
        { }
    } ,
  type / se .code:n    =
    {
      \__chemmacros_set_mechanisms:nnn { S }
        {
            \textsubscript{E}
        }
        { }
    } ,
  type / 1e .code:n    =
    {
      \__chemmacros_set_mechanisms:nnn { S }
        {
            \textsubscript{E}
          1
        }
        { }
    } ,
  type / 2e .code:n    =
    {
      \__chemmacros_set_mechanisms:nnn { S }
        {
            \textsubscript{E}
          2
        }
        { }
    } ,
  type / ar .code:n    =
    {
      \__chemmacros_set_mechanisms:nnn { S }
        {
            \textsubscript{E}
        }
        { Ar - }
```

```
      } ,
    type / e  .code:n    =
      { \__chemmacros_set_mechanisms:nnn { E } { } { } } ,
    type / e1 .code:n    =
      { \__chemmacros_set_mechanisms:nnn { E } { 1 } { } } ,
    type / e2 .code:n    =
      { \__chemmacros_set_mechanisms:nnn { E } { 2 } { } } ,
    type / cb .code:n    =
      {
        \__chemmacros_set_mechanisms:nnn { E }
          {
            1
              \textsubscript{cb}
          }
          { }
      } ,
    type      .default:n =
  }

\cs_gset_protected:Npn \chemmacros_mechanisms:n #1
  {
    \tl_if_blank:nTF {#1}
      { \chemmacros_set_keys:nn {textmechanisms} { type } }
      { \chemmacros_set_keys:nn {textmechanisms} { type = #1 } }
    \mbox
      {
        \tl_use:N \l__chemmacros_mechanisms_ar_tl
        \tl_use:N \l__chemmacros_mechanisms_type_tl
        \tl_use:N \l__chemmacros_mechanisms_mol_tl
      }
  }

\appto\LWR@restoreorigformatting{%
\cs_set_protected:Npn \chemmacros_mechanisms:n #1%
  {%
    \tl_if_blank:nTF {#1}%
      { \chemmacros_set_keys:nn {mechanisms} { type } }%
      { \chemmacros_set_keys:nn {mechanisms} { type = #1 } }%
    \mbox%
      {%
        \tl_use:N \l__chemmacros_mechanisms_ar_tl%
        \tl_use:N \l__chemmacros_mechanisms_type_tl%
        \tl_use:N \l__chemmacros_mechanisms_mol_tl%
      }%
  }%
}

}{}% \@ifchemmacrosmoduleloaded
}% AtBeginDocument
```

§ 191.11 Newman

```
\AtBeginDocument{
\@ifchemmacrosmoduleloaded{newman}{
\PackageInfo{lwarp}{Patching~chemmacros~module~newman}

```

```
\RenewDocumentCommand \newman {od()m}%
  {
    \IfValueTF{#2}
    {\begin{lateximage}[\textbackslash{}newman(#2)\{#3\}]*}
    {\begin{lateximage}[\textbackslash{}newman\{#3\}]*}
    \group_begin:
      \IfNoValueF  {#1} { \chemmacros_set_keys:nn {newman} {#1} }
      \IfNoValueTF {#2}
        { \chemmacros_newman:nn {  } {#3} }
        { \chemmacros_newman:nn {#2} {#3} }
    \group_end:
    \end{lateximage}
  }%

}{}% \@ifchemmacrosmoduleloaded
}% AtBeginDocument
```

§ 191.12 Orbital

```
\AtBeginDocument{
\@ifchemmacrosmoduleloaded{orbital}{
\PackageInfo{lwarp}{Patching~chemmacros~module~orbital}

\RenewDocumentCommand \orbital {om}
  {
    \IfValueTF{#1}
    {
        \begin{lateximage}[%
            \textbackslash{}orbital{[}\LWR@HTMLsanitize{#1}{]}\{#2\}%
        ]*[][margin-left: 1em ; margin-right: 1em]
    }
    {
        \begin{lateximage}[%
            \textbackslash{}orbital\{#2\}%
        ]*[][margin-left: 1em ; margin-right: 1em]
    }
    \group_begin:
      \chemmacros_set_keys:nn {orbital/type} {#2}
      \IfNoValueTF {#1}
        { \chemmacros_orbital:n {  } }
        { \chemmacros_orbital:n {#1} }
    \group_end:
    \end{lateximage}
  }

}{}% \@ifchemmacrosmoduleloaded
}% AtBeginDocument
```

§ 191.13 Reactions

\chemmacros_declare_reaction_env {⟨*chem*⟩} {⟨*math*⟩} {⟨*args number*⟩} {⟨*argument list ([#2]{#3}...)*⟩}

```
\AtBeginDocument{
\@ifchemmacrosmoduleloaded{reactions}{
\PackageInfo{lwarp}{Patching~chemmacros~module~reactions}
```

```
\cs_gset_protected:Npn \chemmacros_declare_reaction_env:nnnn #1#2#3#4
  {
   \exp_args:Nnx \DeclareDocumentEnvironment {#1} { O{} \prg_replicate:nn {#3+0} {m} }
      {
        \boolfalse{mathjax}%                          lwarp
        \ifdefvoid{\LWR@ThisAltText}{%                lwarp
            \ThisAltText{-chemmacros-~reaction}%      lwarp
        }{}%                                          lwarp
        \chemmacros_add_reaction_description:n {##1}
        \__chemmacros_begin_reaction:
        \chemmacros_reaction_read:nnw {#2} {#4}
      }
      {
        \__chemmacros_end_reaction:
        \gdef\LWR@ThisAltText{}%                      lwarp
      }
  }
\cs_generate_variant:Nn \chemmacros_declare_reaction_env:nnnn {nnnV}

\RenewChemReaction {reaction}   {equation}
\RenewChemReaction {reaction*}  {equation*}
\RenewChemReaction {reactions}  {align}
\RenewChemReaction {reactions*} {align*}

}{}% \@ifchemmacrosmoduleloaded
}% AtBeginDocument
```

§ 191.14 Redox

```
\AtBeginDocument{
\@ifchemmacrosmoduleloaded{redox}{
\PackageInfo{lwarp}{Patching~chemmacros~module~redox}

\NewDocumentCommand \LWR@chemmacros@ox { s m >{\SplitArgument{1}{,}}m }
  {
    \IfBooleanTF {#1}
      { \chemmacros_ox:nnnn {#1} {#2} #3 }
      { \chemmacros_ox:nnnn {  } {#2} #3 }
  }

\RenewDocumentCommand \ox { s O{} m }
  {
    \begingroup
    \boolfalse{mathjax}
    \IfBooleanTF {#1}
      {
        \LWR@subsingledollar*{% yes hash
            \textbackslash{}ox*\{\LWR@HTMLsanitize{#3}\}% alt
        }{%
            star \protect\LWR@HTMLsanitize{\detokenize\expandafter{#2}}%
        }{%
            \LWR@chemmacros@ox* {#2} {#3}% contents
        }%
      }
      {
```

```
        \LWR@subsingledollar*{% yes hash
            \textbackslash{}ox*\{\LWR@HTMLsanitize{#3}\}% alt
        }{%
            \protect\LWR@HTMLsanitize{\detokenize\expandafter{#2}}%
        }{%
            \LWR@chemmacros@ox {#2} {#3}% contents
        }%
      }
    \endgroup
  }

}{}% \@ifchemmacrosmoduleloaded
}% AtBeginDocument
```

§ 191.15 Scheme

Fix for chemmacros as of v5.8b, when using newfloat and babel:

```
\AtBeginDocument{
\@ifchemmacrosmoduleloaded{scheme}{
\PackageInfo{lwarp}{Patching~chemmacros~module~scheme}

\ifdefstring{\schemename}{los}{
\SetupFloatingEnvironment{scheme}{
name = \chemmacros_translate:n {scheme-name}
}
}{}

}{}% \@ifchemmacrosmoduleloaded
}% AtBeginDocument
```

§ 191.16 Spectroscopy

```
\AtBeginDocument{
\@ifchemmacrosmoduleloaded{spectroscopy}{
\PackageInfo{lwarp}{Patching~chemmacros~module~spectroscopy}

\ChemCompatibilityTo{5.8}
\cs_gset_protected:Npn \__chemmacros_nmr_base:nn #1#2
  {
    \tl_if_blank:VF \g__chemmacros_nmr_element_coupled_tl
      {
        \tl_put_left:Nn \g__chemmacros_nmr_element_coupled_tl { \{ }
        \tl_put_right:Nn \g__chemmacros_nmr_element_coupled_tl { \} }
      }
    \tl_put_left:Nn \g__chemmacros_nmr_element_coupled_tl {#2}
%     \chemmacros_chemformula:n { ^{#1} }
    \textsuperscript{#1}
    \bool_if:NTF \l__chemmacros_nmr_parse_bool
      { \chemformula_ch:nV {} \g__chemmacros_nmr_element_coupled_tl }
      { \chemmacros_chemformula:V \g__chemmacros_nmr_element_coupled_tl }
    \tl_use:N \l__chemmacros_nmr_element_method_connector_tl
    \tl_use:N \l__chemmacros_nmr_method_tl
  }
\EndChemCompatibility
```

```
\ChemCompatibilityFrom{5.8}
\cs_gset_protected:Npn \__chemmacros_nmr_base:nn #1#2
  {
    \group_begin:
      \tl_use:N \l__chemmacros_nmr_base_format_tl
      \tl_if_blank:VF \g__chemmacros_nmr_element_coupled_tl
        {
          \tl_put_left:Nn \g__chemmacros_nmr_element_coupled_tl { \{ }
          \tl_put_right:Nn \g__chemmacros_nmr_element_coupled_tl { \} }
        }
      \tl_put_left:Nn \g__chemmacros_nmr_element_coupled_tl {#2}
%       \chemmacros_chemformula:n { ^{#1} }
      \textsuperscript{#1}
      \tl_if_blank:VF \g__chemmacros_nmr_element_coupled_tl
        {
          \bool_if:NTF \l__chemmacros_nmr_parse_bool
            { \chemformula_ch:nV {} \g__chemmacros_nmr_element_coupled_tl }
            { \chemmacros_chemformula:V \g__chemmacros_nmr_element_coupled_tl }
        }
      \tl_use:N \l__chemmacros_nmr_element_method_connector_tl
      \tl_use:N \l__chemmacros_nmr_method_tl
    \group_end:
  }
\EndChemCompatibility


\cs_gset_protected:Npn \chemmacros_nmr_position:n #1
  {
    \chemmacros_chemformula:x
      {
        \exp_not:V \g__chemmacros_nmr_element_tl
        \bool_if:NF \l__chemmacros_nmr_position_side_bool
          {
            \tl_if_eq:NnTF \l__chemmacros_nmr_position_tl {^}% lwarp
            { \textsuperscript{\exp_not:n { {#1} }} }% lwarp
            { \textsubscript{\exp_not:n { {#1} }} }% lwarp
%             \exp_not:V \l__chemmacros_nmr_position_tl
%             \exp_not:n { {#1} }
          }
      }
    \bool_if:NT \l__chemmacros_nmr_position_side_bool
      {
        \tl_use:N \l__chemmacros_nmr_position_tl
        \__chemmacros_nmr_position:n {#1}
      }
  }

\cs_gset_protected:Npn \__chemmacros_nmr_coupling:w (#1;#2)
  {
    \tl_set:Nn \l__chemmacros_nmr_coupling_bonds_tl
      {
        \l__chemmacros_nmr_coupling_bonds_pre_tl
        #1
        \l__chemmacros_nmr_coupling_bonds_post_tl
      }
```

```
    \bool_if:NTF \l__chemmacros_nmr_coupling_nuclei_sub_bool
      {
        \tl_set:Nn \l__chemmacros_nmr_coupling_nuclei_tl
          {
% \c_math_subscript_token
            \textsubscript% lwarp
              {
                \l__chemmacros_nmr_coupling_nuclei_pre_tl
                \chemmacros_chemformula:n {#2}
                \l__chemmacros_nmr_coupling_nuclei_post_tl
              }
          }
      }
      {
        \tl_set:Nn \l__chemmacros_nmr_coupling_nuclei_tl
          {
            \l__chemmacros_nmr_coupling_nuclei_pre_tl
            \chemmacros_chemformula:n {#2}
            \l__chemmacros_nmr_coupling_nuclei_post_tl
          }
      }
    \__chemmacros_nmr_coupling_aux_i:w
  }
\AfterEndPreamble{% After \AtBeginDocument
% \NMR{<num>,<elem>}(<num>,<unit>)[<solvent>] ALL arguments are optional
% \NMR* same but without ": $\delta$" at end
\cs_gset_protected:Npn \chemmacros_nmr:nnnn #1#2#3#4
    {
    \bool_if:NT \l__chemmacros_nmr_list_bool { \item \scan_stop: }
    \group_begin:

        \mode_leave_vertical:

        \bool_set_false:N \l__chemmacros_nmr_frequency_bool
        \bool_set_false:N \l__chemmacros_nmr_solvent_bool
        \tl_if_empty:nF {#3}
        { \bool_set_true:N \l__chemmacros_nmr_frequency_bool }
        \tl_if_empty:nF {#4}
        { \bool_set_true:N \l__chemmacros_nmr_solvent_bool }
        \bool_if:nT
        {
            \l__chemmacros_nmr_frequency_bool
            ||
            \l__chemmacros_nmr_solvent_bool
        }
        { \bool_set_true:N \l__chemmacros_nmr_delimiters_bool }
        \bool_if:nT
        {
            \l__chemmacros_nmr_frequency_bool
            &&
            \l__chemmacros_nmr_solvent_bool
        }
        { \bool_set_true:N \l__chemmacros_nmr_comma_bool }
        \tl_if_empty:nTF {#2}
        {
            \__chemmacros_nmr_nucleus:VV
```

```
            \l__chemmacros_nmr_isotope_default_tl
            \l__chemmacros_nmr_element_default_tl
        }
        { \__chemmacros_nmr_nucleus:w #2 \q_stop }
        \mode_if_math:TF
        {
            \text
            {
                \group_begin:
                \tl_use:N \l__chemmacros_nmr_format_tl
\LWR@textcurrentcolor{\LWR@textcurrentfont{% lwarp
                \__chemmacros_nmr_base:VV
                    \g__chemmacros_nmr_isotope_tl
                    \g__chemmacros_nmr_element_tl
                \bool_if:NT \l__chemmacros_nmr_delimiters_bool
                    { ~ ( }
                \bool_if:NT \l__chemmacros_nmr_frequency_bool
                    { \__chemmacros_nmr_frequency:n {#3} }
                \bool_if:NT \l__chemmacros_nmr_comma_bool
                    { , ~ }
                \bool_if:NT \l__chemmacros_nmr_solvent_bool
                    { \chemmacros_chemformula:n {#4} }
                \bool_if:NT \l__chemmacros_nmr_delimiters_bool
                    { ) }
                \tl_if_blank:nT {#1} {:~}
}}% lwarp
                \group_end:
            }
            \tl_if_blank:nT {#1}
            {
                \delta
                \text { \l__chemmacros_nmr_delta_tl }
                \bool_if:NT \l__chemmacros_nmr_use_equal_bool {=}
            }
        }
        {
            \group_begin:
            \tl_use:N \l__chemmacros_nmr_format_tl
\LWR@textcurrentcolor{\LWR@textcurrentfont{% lwarp
            \__chemmacros_nmr_base:VV
                \g__chemmacros_nmr_isotope_tl
                \g__chemmacros_nmr_element_tl
            \bool_if:NT \l__chemmacros_nmr_delimiters_bool
                {~(}
            \bool_if:NT \l__chemmacros_nmr_frequency_bool
                { \__chemmacros_nmr_frequency:n {#3} }
            \bool_if:NT \l__chemmacros_nmr_comma_bool
                {,~}
            \bool_if:NT \l__chemmacros_nmr_solvent_bool
                {
                \bool_if:NTF \l__chemmacros_nmr_parse_bool

%                   { \chemformula_ch:nn { } {#4} }%  original
                  {\ch{#4}}%  lwarp
                  {#4}
```

```
                }
            \bool_if:NT \l__chemmacros_nmr_delimiters_bool
                {)}
}}% lwarp
            \tl_if_blank:nT {#1} {:}
            \group_end:
            \tl_if_blank:nT {#1}
            {
                \tl_use:N \c_space_tl
                \c_math_toggle_token
                \delta
                \c_math_toggle_token
                \l__chemmacros_nmr_delta_tl
                \bool_if:NT \l__chemmacros_nmr_use_equal_bool {~=}
            }
        }
    \group_end:
    }
}% AfterEndPremble


\RenewDocumentCommand \chemmacros_data:w { smo }
  {
    \bool_if:NT \l__chemmacros_nmr_list_bool { \item }
      {
%         \tl_use:N \l__chemmacros_nmr_format_tl #2
        \tl_use:N \l__chemmacros_nmr_format_tl
        \LWR@textcurrentcolor{\LWR@textcurrentfont{% lwarp
            #2
            \IfNoValueF {#3} { ~ ( #3 ) }
         \IfBooleanT {#1} { \bool_if:NT \l__chemmacros_nmr_use_equal_bool { : } }
        }}% lwarp
      }
    \IfBooleanF {#1} { \bool_if:NT \l__chemmacros_nmr_use_equal_bool { ~ = } }
  }

}{}% \@ifchemmacrosmoduleloaded
}% AtBeginDocument
```

§ 191.17 Thermodynamics

```
\AtBeginDocument{
\@ifchemmacrosmoduleloaded{thermodynamics}{
\PackageInfo{lwarp}{Patching~chemmacros~module~thermodynamics}

\cs_gset_protected:Npn \chemmacros_state:nn #1#2
  {
    \group_begin:
      \boolfalse{mathjax}
      \chemmacros_set_keys:nn {thermodynamics} {#1}
        \LWR@subsingledollar*{% yes hashing
            \textbackslash{}state\{\LWR@HTMLsanitize{#2}\}% alt
        }{%
            chemmacros_state% add'l hashing
            #1% options
            LSP \tl_use:N \l__chemmacros_state_sp_left_tl% super/subscripts
```

```
            LSB \tl_use:N \l__chemmacros_state_sb_left_tl
            RSP \tl_use:N \l__chemmacros_state_sp_right_tl
            RSB \tl_use:N \l__chemmacros_state_sb_right_tl
        }
        {
         \LWR@origensuredmath{
          \chemmacros_text:V \l__chemmacros_state_pre_tl
          \c_math_superscript_token
            { \chemmacros_text:V \l__chemmacros_state_sp_left_tl }
```

Only add the subscripts if they are being used. This avoids causing an incorrect depth, as the empty subscript will be measured by TEX but cropped out by *pdfcrop*.

```
          \tl_if_empty:NTF \l__chemmacros_state_sb_left_tl
          {}
          {
            \c_math_subscript_token
            { \chemmacros_text:V \l__chemmacros_state_sb_left_tl }
          }
          #2
          \c_math_superscript_token
            { \chemmacros_text:V \l__chemmacros_state_sp_right_tl }
          \tl_if_empty:NTF \l__chemmacros_state_sb_right_tl
          {}
          {
            \c_math_subscript_token
            { \chemmacros_text:V \l__chemmacros_state_sb_right_tl }
          }
          \chemmacros_text:V \l__chemmacros_state_post_tl
         }
        }
    \group_end:
  }
\cs_generate_variant:Nn \chemmacros_state:nn { nV }

\cs_gset_protected:Npn \chemmacros_declare_state:Nn #1#2
  {
    \chemmacros_define_keys:xn
      {thermodynamics/\chemmacros_remove_backslash:N #1}
      {
        pre              .meta:nn = {chemmacros/thermodynamics} { pre = ##1 } ,
        post             .meta:nn = {chemmacros/thermodynamics} { post = ##1 } ,
      superscript-left  .meta:nn = {chemmacros/thermodynamics} { superscript-left = ##1 } ,
      superscript-right .meta:nn = {chemmacros/thermodynamics} { superscript-right = ##1 } ,
        superscript       .meta:n  = { superscript-right = ##1 } ,
      subscript-left   .meta:nn = {chemmacros/thermodynamics} { subscript-left = ##1 } ,
      subscript-right  .meta:nn = {chemmacros/thermodynamics} { subscript-right = ##1 } ,
        subscript         .meta:n     = { subscript-left = ##1 } ,
        subscript-pos     .choices:nn =
          { left , right }
          { \tl_set_eq:NN \l__chemmacros_state_sb_pos_tl \l_keys_choice_tl } ,
        symbol            .tl_set:N = \l__chemmacros_state_symbol_tl ,
        unit              .tl_set:N = \l__chemmacros_state_unit_tl
       }
    \DeclareDocumentCommand #1 { sO{}D(){}m }
```

```
    {
      \group_begin:
        \chemmacros_set_keys:xn
          {thermodynamics/\chemmacros_remove_backslash:N #1}
          {#2}
        \tl_if_blank:nF {##3}
          {
            \chemmacros_set_keys:nx {thermodynamics}
             { subscript-\l__chemmacros_state_sb_pos_tl = \exp_not:n {##3} }
          }
            \chemmacros_state:nV {##2} \l__chemmacros_state_symbol_tl
           \chemmacros_set_keys_groups:nnn {thermodynamics} {variables} {##2}
          \IfBooleanF {##1} {  = ~ \SI {##4} { \l__chemmacros_state_unit_tl } }
      \group_end:
    }
}
```

The pre-existing macros are redefined with the new definition:

```
\RenewChemState \enthalpy { symbol = H , unit = \kilo\joule\per\mole }
\RenewChemState \entropy  { symbol = S , unit = \joule\per\kelvin\per\mole , pre = }
\RenewChemState \gibbs    { symbol = G , unit = \kilo\joule\per\mole }

}{}% \@ifchemmacrosmoduleloaded
}% AtBeginDocument

\ExplSyntaxOff
```

File 84 **lwarp-chemnum.sty**

§ 192 Package

chemnum

(*Emulates or patches code by* Clemens Niederberger.)

Pkg chemnum chemnum is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{chemnum}[2016/04/14]

\ExplSyntaxOn

\cs_gset_protected:Npn \chemnum_compound_write:n #1
 {
   \chemnum_get_compound_property:nn {#1} {pre-main-label-code}
   \group_begin:
     \bool_if:NTF \l__chemnum_compound_local_bool
       { \l__chemnum_local_label_format_tl }
       { \chemnum_get_compound_property:nn {#1} {label-format} }
     {
       \LWR@textcurrentfont{
           \chemnum_get_compound_property:nn {#1} {counter-representation}
       }
     }
   \group_end:
```

```
    \chemnum_get_compound_property:nn {#1} {post-main-label-code}
  }

\cs_gset_protected:Npn \chemnum_subcompound_write:nn #1#2
  {
    \group_begin:
      \bool_if:NTF \l__chemnum_compound_local_bool
        { \l__chemnum_local_label_format_tl }
        { \chemnum_get_compound_property:nn {#1} {label-format} }
      {
        \LWR@textcurrentfont{
            \chemnum_get_subcompound_property:nnn {#1} {#2}
            {counter-representation}
        }
      }
    \group_end:
  }

\ExplSyntaxOff
```

File 85 **lwarp-chkfloat.sty**

§ 193 Package chkfloat

Pkg chkfloat chkfloat is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{chkfloat}[2012/08/19]
```

File 86 **lwarp-chngpage.sty**

§ 194 Package chngpage

(*Emulates or patches code by* Peter Wilson.)

Pkg chngpage chngpage is ignored.

for HTML output: Discard all options for lwarp-chngpage:

```
\LWR@ProvidesPackageDrop{chngpage}[2009/10/20]
\LWR@origRequirePackage{lwarp-changepage}
```

File 87 **lwarp-cite.sty**

§ 195 Package cite

(*Emulates or patches code by* Donald Arseneau.)

Pkg cite cite is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{cite}[2015/02/27]
```

For the [super] option, the \kern must be removed:

```
\def\LWRCT@biblabel#1{\@citess{#1}\kern-\labelsep\,}

\ifdefstrequal{\@biblabel}{\LWRCT@biblabel}
{
    \def\@biblabel#1{\@citess{#1}}
}{}
```

For the [super] option, \textsuperscript is used instead of math superscript:

```
\def\@citess#1{\textsuperscript{#1}}

\DeclareDocumentCommand\citepunct{}{,\,\relax}
```

File 88 **lwarp-citeref.sty**

§ 196 Package citeref

(*Emulates or patches code by* Björn Briel.)

Pkg citeref citeref is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{citeref}[1999/27/05]

\def\@cprwrite#1={%
    \write\@auxout{\string\citepageref{#1}{\theLWR@previousautopagelabel}}%
}

\def\citepageref#1#2{%
    \xdef\cpr@testa{\@nameuse{cpr@last@#1}}%letzte Zitatstelle
    \xdef\cpr@testb{#2}% Seite dieser Zitatstelle
    \ifx\cpr@testa\cpr@testb%
        \relax% Konsekutive identische Seitenangaben weglassen
    \else%
        \@namexdef{cpr@last@#1}{#2}%
        \@ifundefined{cpr@#1}%
        {\@namexdef{cpr@#1}{\LWR@refwithsection{\BaseJobname-autopage-#2}}}%  lwarp
            {%      lwarp
                \@namexdef{cpr@#1}{\@nameuse{cpr@#1}, % space
                \LWR@refwithsection{\BaseJobname-autopage-#2}}%
            }%
    \fi
    }
```

File 89 **lwarp-CJK.sty**

§ 197 Package CJK

Pkg CJK CJK does not work with lwarp unless called from ctex.

for HTML output:

```
\@ifpackageloaded{xeCJK}{}{
    \LWR@loadnever{CJK}{ctex, xeCJK}
}

\LWR@ProvidesPackagePass{CJK}[2015/04/18]
```

File 90 **lwarp-CJKutf8.sty**

§ 198 Package

CJKutf8

Pkg CJKutf8 CJKutf8 does not work with lwarp unless called from ctex.

for HTML output:

```
\@ifpackageloaded{xeCJK}{}{
    \LWR@loadnever{CJKutf8}{ctex, xeCJK}
}

\LWR@ProvidesPackagePass{CJKutf8}[2015/04/18]
```

File 91 **lwarp-classicthesis.sty**

§ 199 Package

classicthesis

(*Emulates or patches code by* André Miede and Ivo Pletikosić.)

Pkg classicthesis classicthesis is emulated.

for HTML output: Discard all options for lwarp-classicthesis:

```
\LWR@ProvidesPackageDrop{classicthesis}[2018/06/03]

\RequirePackage{scrlayer-scrpage} % provides headers and footers (KOMA Script)
\RequirePackage{scrtime} % time access
\PassOptionsToPackage{titles}{tocloft}
\RequirePackage{textcase} % for \MakeTextUppercase
\RequirePackage[newparttoc]{titlesec} % newparttoc to write \part to .toc with \numberline
\RequirePackage{tocloft}
\PassOptionsToPackage{headinclude,footinclude}{typearea} % for classes other than KOMA
\RequirePackage{typearea}
\PassOptionsToPackage{marginal}{footmisc}% marginal flushmargin
\RequirePackage{footmisc}%
\RequirePackage{prelim2e}
\RequirePackage{remreset}%

\DeclareRobustCommand{\spacedallcaps}[1]{\textsc{\MakeTextUppercase{#1}}}
\DeclareRobustCommand{\spacedlowsmallcaps}[1]{\textsc{\MakeTextLowercase{#1}}}
\newcommand{\ctparttext}[1]{}
\newcommand{\tocEntry}[1]{}
\DeclareRobustCommand*{\deactivateaddvspace}{}%
\newlength{\beforebibskip}
```

File 92 **lwarp-cleveref.sty**

§ 200 Package

cleveref

(*Emulates or patches code by* Toby Cubitt.)

Pkg cleveref

cleveref is patched for HTML, and limited MathJax emulation is added.

⚠ cleveref page numbers

cleveref and varioref are supported, but printed page numbers do not map to HTML, so a section name or a text phrase are used for \cpageref and \cpagerefrange. This phrase includes \cpagerefFor, which defaults to "for".

Ex:

```
    \cpageref{tab:first,tab:second}
in html becomes:
```
"pages **for** table 4.1 and **for** table 4.2"

See \cpagerefFor at page 748 to redefine the message which is printed for page number references.

Table 15 on page 508 shows the data structure of the label/reference system as revised by lwarp and cleveref.

⚠ multiple labels

For MathJax, each references is printed as an \eqref, without cleveref's description text. Page references are also printed as simple \eqrefs. Multiple labels in a single \cref will print as (???) in MathJax.

for HTML output:

```
\LWR@ProvidesPackagePass{cleveref}[2018/03/27]
```

The following patches are applied. Print-mode versions are not required since they all come down to \ref eventually, and \ref has a print-mode version.

\@@@setcref {⟨*kindofref*⟩} {⟨*label*⟩}

\@templabel becomes the section number.

```
\def\LWR@orig@@@setcref#1#2{\cref@getlabel{#2}{\@templabel}#1{\@templabel}{}{}}%

\ifdefequal{\@@setcref}{\LWR@orig@@@setcref}{% before v0.21
    \renewcommand*{\@@setcref}[2]{#1{\ref{#2}}{}{}}
}{
    \ifdefequal{\@@@setcref}{\LWR@orig@@@setcref}{% as of v0.21
        \renewcommand*{\@@@setcref}[2]{%
            #1{\ref{#2}}{}{}}
    }{
        \PackageWarningNoLine{lwarp-cleveref}{
            Unknown version of cleveref.
            \protect\cref\space will fail.
        }%
    }
}
```

\@@@setcrefrange {⟨*text*⟩} {⟨*label*⟩} {⟨*label*⟩}

```
\def\LWR@orig@@@setcrefrange#1#2#3{%
  \cref@getlabel{#2}{\@labela}%
  \cref@getlabel{#3}{\@labelb}%
  #1{\@labela}{\@labelb}{}{}{}{}}%

\ifdefequal{\@@setcrefrange}{\LWR@orig@@@setcrefrange}{
    \renewcommand{\@@setcrefrange}[3]{%
        #1{\ref{#2}}{\ref{#3}}{}{}{}{}%
    }
}{
    \ifdefequal{\@@@setcrefrange}{\LWR@orig@@@setcrefrange}{
        \renewcommand{\@@@setcrefrange}[3]{%
            #1{\ref{#2}}{\ref{#3}}{}{}{}{}%
        }
    }{
        \PackageWarningNoLine{lwarp-cleveref}{
            Unknown version of cleveref.
            \protect\crefrange\space will fail.
        }
    }
}
```

\cpagerefFor Redefinable word between “page(s)” and the page numbers.

```
\newcommand*{\cpagerefFor}{for}
```

\@@@setcpageref {⟨*typeofref*⟩} {⟨*label*⟩}, where typeofref is “page” or “pages”

```
\def\LWR@orig@@setcpageref#1#2{% before v0.21
  \cref@getpageref{#2}{\@temppage}#1{\@temppage}{}{}}%

\def\LWR@orig@@@setcpageref#1#2{% as of v0.21
  \cpageref@getlabel{#2}{\@temppage}#1{\@temppage}{}{}}%

\ifdefequal{\@@setcpageref}{\LWR@orig@@setcpageref}{
    \renewcommand*{\@@setcpageref}[2]{%
        #1{\cpagerefFor\ \cref{#2}}{}{}%
    }
}{
    \ifdefequal{\@@@setcpageref}{\LWR@orig@@@setcpageref}{
        \renewcommand*{\@@@setcpageref}[2]{%
            #1{\cpagerefFor\ \cref{#2}}{}{}%
        }
    }
    {
        \PackageWarningNoLine{lwarp-cleveref}{
            Unknown version of cleveref.
            \protect\cpageref\space will fail.
        }
    }
}
```

```
\def\LWR@orig@@setcpagerefrange#1#2#3{% before v0.21
  \cref@getpageref{#2}{\@pagea}%
  \cref@getpageref{#3}{\@pageb}%
  #1{\@pagea}{\@pageb}{}{}{}{}}%

\def\LWR@orig@@@setcpagerefrange#1#2#3{% as of v0.21
  \cpageref@getlabel{#2}{\@pagea}%
  \cpageref@getlabel{#3}{\@pageb}%
  #1{\@pagea}{\@pageb}{}{}{}{}}%

\ifdefequal{\@@setcpagerefrange}{\LWR@orig@@setcpagerefrange}{
    \renewcommand*{\@@setcpagerefrange}[3]{%
        #1{\cpagerefFor\ \cref{#2}}{\cref{#3}}{}{}{}{}%
    }
}{
    \ifdefequal{\@@@setcpagerefrange}{\LWR@orig@@@setcpagerefrange}{
        \renewcommand*{\@@@setcpagerefrange}[3]{%
            #1{\cpagerefFor\ \cref{#2}}{\cref{#3}}{}{}{}{}%
        }
    }
    {
        \PackageWarningNoLine{lwarp-cleveref}{
            Unknown version of cleveref.
            \protect\cpagerefrange\space will fail.
        }
    }
}
```

If hyperref is loaded, cleveref defines starred versions of the following, but since hyperref is only emulated, starred versions are defined here:

```
\LWR@absorbstar{cref}
\LWR@absorbstar{Cref}
\LWR@absorbstar{crefrange}
\LWR@absorbstar{Crefrange}
\LWR@absorbstar{cpageref}
\LWR@absorbstar{Cpageref}
\LWR@absorbstar{cpagerefrange}
\LWR@absorbstar{Cpagerefrange}
\LWR@absorbstar{labelcref}
\LWR@absorbstar{labelcpageref}
```

If hyperref is loaded, cleveref also defines starred versions of varioref macros, so they are defined here.

```
\@ifpackageloaded{varioref}{
    \LWR@absorbstar{vref}
    \LWR@absorbstar{Vref}
    \LWR@absorbstar{vrefrange}
    \LWR@absorbstar{Vrefrange}
    \LWR@absorbstar{fullref}
    \LWR@absorbstar{Fullref}
}{}% varioref


\@ifclassloaded{memoir}{
```

```
\AtBeginDocument{
\def\sf@memsub@label(#1)#2{%
  \protected@edef\mem@currentlabelname{#1}%
  \sf@@memsub@label{#2}}
}{}

\@ifpackageloaded{subfig}{
\def\sf@sub@label(#1)#2{%
  \ifhyperrefloaded
    \protected@edef\@currentlabelname{%
      \expandafter\strip@period #1\relax.\relax\@@@}%
  \fi
  \sf@@sub@label{#2}}
}{}
```

File 93 **lwarp-clrdblpg.sty**

§ 201 Package clrdblpg

Pkg clrdblpg clrdblpg is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{clrdblpg}[2018/04/21]
```

File 94 **lwarp-cmbright.sty**

§ 202 Package cmbright

(*Emulates or patches code by* Walter Schmidt.)

Pkg cmbright cmbright is used as-is for SVG math, and is emulated for MathJax.

⚠ limitations The MathJax emulation ignores all package options, except `slantedGreek` is honored, and `\mathbold` is available.

The dedicated macros for upright Greek letters do work correctly.

SVG math should appear the same as the printed output.

for HTML output:

```
\LWR@ProvidesPackagePass{cmbright}[2005/04/13]

\LWR@infoprocessingmathjax{cmbright}

\LWR@origRequirePackage{lwarp-common-mathjax-letters}

\begin{warpMathJax}

\@ifpackagewith{cmbright}{slantedGreek}
{
    \LWR@mathjax@addgreek@u@it*{}{}
```

```
}
{}

\LWR@mathjax@addgreek@u@up*{up}{}

\CustomizeMathJax{\newcommand{\mathbold}[1]{\boldsymbol{#1}}}

\end{warpMathJax}
```

File 95 **lwarp-cmdtrack.sty**

§ 203 Package cmdtrack

Pkg cmdtrack cmdtrack is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{cmdtrack}[2012/12/18]

\newcommand{\untrack}[1]{}
```

File 96 **lwarp-colonequals.sty**

§ 204 Package colonequals

(*Emulates or patches code by* Heiko Oberdiek.)

Pkg colonequals colonequals is used as-is for SVG math, and is emulated for MathJax.

Since Unicode symbols are not available for each of the following, only two are used for the single and double colons, and the other symbols are derived in a consistent manner. Occasional negative space is added as well. This may need to be undone for some fonts.

for HTML output:

```
\LWR@ProvidesPackagePass{colonequals}[2016/05/16]

\begin{warpMathJax}
\LWR@infoprocessingmathjax{colonequals}

\CustomizeMathJax{\newcommand{\ratio}{\mathrel{\unicode{x2236}}}}
\CustomizeMathJax{\newcommand{\coloncolon}{\mathrel{\unicode{x2237}}}}
\CustomizeMathJax{\newcommand{\colonequals}{\mathrel{\unicode{x2236}\!=}}}
\CustomizeMathJax{\newcommand{\coloncolonequals}{\mathrel{\unicode{x2237}\!=}}}
\CustomizeMathJax{\newcommand{\equalscolon}{\mathrel{=\!\unicode{x2236}}}}
\CustomizeMathJax{\newcommand{\equalscoloncolon}{\mathrel{=\!\unicode{x2237}}}}
\CustomizeMathJax{\newcommand{\colonminus}{\mathrel{\unicode{x2236}-}}}
\CustomizeMathJax{\newcommand{\coloncolonminus}{\mathrel{\unicode{x2237}-}}}
\CustomizeMathJax{\newcommand{\minuscolon}{\mathrel{-\unicode{x2236}}}}
\CustomizeMathJax{\newcommand{\minuscoloncolon}{\mathrel{-\unicode{x2237}}}}
\CustomizeMathJax{\newcommand{\colonapprox}{\mathrel{\unicode{x2236}\!\approx}}}
\CustomizeMathJax{\newcommand{\coloncolonapprox}{\mathrel{\unicode{x2237}\!\approx}}}
\CustomizeMathJax{\newcommand{\approxcolon}{\mathrel{\approx\!\unicode{x2236}}}}
\CustomizeMathJax{\newcommand{\approxcoloncolon}{\mathrel{\approx\!\unicode{x2237}}}}
```

```
\CustomizeMathJax{\newcommand{\colonsim}{\mathrel{\unicode{x2236}\!\sim}}}
\CustomizeMathJax{\newcommand{\coloncolonsim}{\mathrel{\unicode{x2237}\!\sim}}}
\CustomizeMathJax{\newcommand{\simcolon}{\mathrel{\sim\!\unicode{x2236}}}}
\CustomizeMathJax{\newcommand{\simcoloncolon}{\mathrel{\sim\!\unicode{x2237}}}}
\end{warpMathJax}
```

File 97 **lwarp-color.sty**

§ 205 Package

color

Pkg color Allowed but ignored. xcolor is then required as well.

color is superceded by xcolor, and lwarp requires several of the features of xcolor. When color is requested, xcolor is loaded as well.

for HTML output:

```
\LWR@ProvidesPackageDrop{color}[2016/07/10]
\RequirePackage{xcolor}
```

File 98 **lwarp-colortbl.sty**

§ 206 Package

colortbl

Pkg colortbl colortbl is used as-is for print output, and emulated for HTML.

⚠ row/cell color Only use \rowcolor and \cellcolor at the start of a row, in that order.

colortbl ignores the overhang arguments.

for HTML output: A placeholder definition is forgotten first:

```
\let\rowcolor\relax

\LWR@ProvidesPackagePass{colortbl}[2018/12/12]
```

The following \LWR@HTML versions are used inside an HTML tabular.

\columncolor [⟨*model*⟩] {⟨*color*⟩} [⟨*left overhang*⟩] [⟨*right overhang*⟩]

\LWR@getmynexttoken is not used here because \columncolor is not used inside the data area of the tabular.

```
\NewDocumentCommand{\LWR@HTML@columncolor}{O{named} m o o}{%
    \convertcolorspec{#1}{#2}{HTML}\LWR@columnHTMLcolor%
    \LWR@addtabularcellcolor%
}

\AtBeginDocument{\LWR@formatted{columncolor}}
```

\LWR@getmynexttoken is used for \rowcolor because it is used inside the data area of the tabular.

\rowcolor [⟨*model*⟩] {⟨*color*⟩} [⟨*left overhang*⟩] [⟨*right overhang*⟩]

```
\NewDocumentCommand{\LWR@HTML@rowcolor}{O{named} m o o}{%
    \convertcolorspec{#1}{#2}{HTML}\LWR@rowHTMLcolor%
    \LWR@getmynexttoken%
}

\AtBeginDocument{\LWR@expandableformatted{rowcolor}}
```

\cellcolor [⟨*model*⟩] {⟨*color*⟩} [⟨*left overhang*⟩] [⟨*right overhang*⟩]

```
\NewDocumentCommand{\LWR@HTML@cellcolor}{O{named} m o o}{%
    \convertcolorspec{#1}{#2}{HTML}\LWR@cellHTMLcolor%
    \LWR@addtabularcellcolor%
}

\AtBeginDocument{\LWR@formatted{cellcolor}}
```

\arrayrulecolor [⟨*model*⟩] {⟨*color*⟩}

The HTML version for use outside a `tabular`. Inside a `tabular`, `\LWR@HTML@arrayrulecolornexttoken` is used instead.

```
\newcommand{\LWR@HTML@arrayrulecolor}[2][named]{%
    \convertcolorspec{#1}{#2}{HTML}\LWR@ruleHTMLcolor%
}

\AtBeginDocument{\LWR@expandableformatted{arrayrulecolor}}
```

\LWR@arrayrulecolornexttoken [⟨*model*⟩] {⟨*color*⟩}

The HTML version for use inside a `tabular`.

```
\newcommand{\LWR@HTML@arrayrulecolornexttoken}[2][named]{%
    \convertcolorspec{#1}{#2}{HTML}\LWR@ruleHTMLcolor%
    \LWR@getmynexttoken%
}

\AtBeginDocument{\LWR@expandableformatted{arrayrulecolornexttoken}}
```

\doublerulesepcolor [⟨*model*⟩] {⟨*color*⟩}

The version for use outside a `tabular`.

```
\newcommand{\LWR@HTML@doublerulesepcolor}[2][named]{}

\AtBeginDocument{\LWR@expandableformatted{doublerulesepcolor}}
```

\LWR@doublerulesepcolornexttoken [⟨*model*⟩] {⟨*color*⟩}

The version for use inside a `tabular`.

```
\newcommand{\LWR@HTML@doublerulesepcolornexttoken}[2][named]{\LWR@getmynexttoken}

\AtBeginDocument{\LWR@expandableformatted{doublerulesepcolornexttoken}}
```

For MathJax, colors are discarded.

```
\begin{warpMathJax}
\CustomizeMathJax{\newcommand{\columncolor}[2][]{\LWRabsorbtwooptions}}
\CustomizeMathJax{\let\rowcolor\columncolor}
\CustomizeMathJax{\let\cellcolor\columncolor}
\end{warpMathJax}
```

File 99 **lwarp-continue.sty**

§ 207 Package continue

Pkg continue continue is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{continue}}[2018/12/09]

\newcommand*{\flagcont}{}
\newcommand*{\flagend}{}
\newcommand*{\flagword}{}
\newcommand*{\preflagword}{}
\newcommand*{\postflagword}{}
\newlength\contsep
\newlength\contdrop
```

File 100 **lwarp-copyrightbox.sty**

§ 208 Package copyrightbox

(*Emulates or patches code by* Thomas Fischer, Ives van der Flaas.)

Pkg copyrightbox copyrightbox is emulated for use by lwarp.

The entire copyright box is placed inside a of class copyrightbox.

The contents are placed inside a of class copyrightboxcontents.

The copyright notice is placed inside a of class copyrightboxnote.

for HTML output:

```
\LWR@ProvidesPackageDrop{copyrightbox}[2011/11/27]

\newcommand{\copyrightbox}[3][r]{%
\begin{BlockClass}[
    display: inline-flex;
    flex-direction: column ;
]{copyrightbox}
\begin{BlockClass}{copyrightboxcontents}
#2
\end{BlockClass}
\begin{BlockClass}{copyrightboxnote}
#3
\end{BlockClass}
```

```
\end{BlockClass}
}

\newcommand{\CRB@setcopyrightfont}{}
\newcommand{\CRB@setcopyrightparagraphstyle}{}
```

File 101 **lwarp-crop.sty**

§ 209 Package

crop

(*Emulates or patches code by* Melchior FRANZ.)

Pkg crop crop is ignored.

for HTML output: Discard all options for lwarp-crop:

```
\LWR@ProvidesPackageDrop{crop}[2003/05/20]

\newcommand*{\crop}[1][]{}
\newcommand*{\cropdef}[6][]{}
```

File 102 **lwarp-ctable.sty**

§ 210 Package

ctable

(*Emulates or patches code by* Wybo Dekker.)

Pkg ctable ctable is patched for use by lwarp.

⚠ Misplaced alignment tab character &

Use `\StartDefiningTabulars` before one or more `\ctables`, and `\StopDefiningTabulars` after. These change the meaning of the ampersand & character.

for HTML output:

```
\LWR@ProvidesPackagePass{ctable}[2015/10/17]
```

The following is in the original:

```
\newcommand{\LWR@HTML@ctable}[4][]{%
   \let\@CTtaborfig  \@dfltCTtaborfig
   \let\@CTalign     \@dfltCTalign
   \let\@CTsideways  \@dfltCTsideways
   \let\@CTcontinued \empty
   \let\@CTpos       \@dfltCTpos
   \let\@CTcaption   \empty
   \let\@CTcap       \undefined
   \let\@CTlabel     \empty
   \let\@CTbotcap    \@dfltCTbotcap
   \let\@CTstarred   \@dfltCTstarred
   \let\@CTsuper     \@dfltCTsuper
   \let\@CTnotespar  \@dfltCTnotespar
   \let\@CTdoinside  \@dfltCTdoinside
   \let\@CTbgopacity \@dfltCTbgopacity
```

```
\@CTframerule     \@dfltCTframerule
\@CTcaptionskip   \@dfltCTcaptionskip
\@CTframesep      \@dfltCTframesep
\@CTwidth         \@dfltCTwidth
\@CTmaxwidth      \@dfltCTmaxwidth
\@CTmincapwidth   \@dfltCTmincapwidth
\@CTfooterwidth   \@dfltCTfooterwidth
\def\@CTfgactual {@dfltCTframefg}%
\def\@CTbgactual {@dfltCTframebg}%
\def\@CTbeg      {\begin{\@CTsideways\@CTtaborfig\@CTstarred}}%
\def\@CTbegin    {\@CTbeg}%
\def\@CTend      {\end{\@CTsideways\@CTtaborfig\@CTstarred}}%
\setkeys{CT}{#1}%
\ifx\@CTcap\undefined\let\@CTcap\@CTcaption\fi
\ifx\@CTcap\empty
  \if@CTcaptionloaded\else
    \PackageWarningNoLine{lwarp-ctable}{\MessageBreak
       An empty cap= option prevents lot/loc entry only\MessageBreak
       if the caption package is loaded!}
  \fi
\fi
\if@CTinmemoir\else
   \ifx\@CTbotcap\undefined
      \PackageError{lwarp-ctable}{\MessageBreak
         You can, currently, use the sidecap option only with\MessageBreak
         memoir documents. Use topcap or botcap only}
         {}
   \fi
\fi
\ifdim\@CTwidth=0pt\else
   \ifdim\@CTmaxwidth=0pt\else
      \PackageError{lwarp-ctable}{\MessageBreak
        You may not use the width and maxwidth options together\MessageBreak
         Use either width or maxwidth}
         {}
   \fi
\fi
\ifx\@CTpos\empty
   \ifx\@CTsideways\empty\else
   \PackageError{lwarp-ctable}{\MessageBreak
      You may not use the pos and sideways options together\MessageBreak
      Rotated tables and figures are always typeset on a separate page}
     {}
   \fi
\fi
\ifx\@CTcaption\empty
   \ifx\@CTlabel\empty\else
      \PackageError{lwarp-ctable}{\MessageBreak
         You may not label a captionless table\MessageBreak
         Such a label can't be referenced}
         {}
   \fi
\fi
```

Some of the original, regarding computing the width of `\CT@t`, is removed here.

```
  \@CTbegin
     \ifx\@CTcontinued\empty\else\addtocounter{\@CTtaborfig}{-1}\fi
     \@CTalign
```

lwarp's patches begin here:

```
   \begin{center}
       \setlength{\fboxrule}{\@CTframerule}
       \setlength{\fboxsep}{\@CTframesep}
       \LWR@forceminwidth{\fboxrule}%  lwarp
       \convertcolorspec{named}{\@CTbgactual}{HTML}\LWR@tempcolor% lwarp
       \begin{BlockClass}[%                            lwarp
           border:
               \LWR@printlength{\LWR@atleastonept}
               solid
               \LWR@colorstyle{named}{\@CTfgactual} ; %
           padding:\LWR@printlength{\fboxsep} ; %
           \ifdefstring{\LWR@tempcolor}{FFFFFF}{}{%
               background: \LWR@colorstyle{named}{\@CTbgactual} ; %
           }%
       ]{fminipage}%       lwarp
        \ifx\@CTbotcap\@CTfalse\@CTCaption\vskip\@CTcaptionskip\fi
        \ifx\@CTbotcap\undefined%
            \begin{sidecaption}[\@CTcap]{\@CTcaption}[\@CTlabel]
        \fi
        \@CTdoinside
        \begin{tabularx}{\linewidth}{#2}%      lwarp
           #4%
        \end{tabularx}%                    lwarp
        \def\@CTfootnotes{#3}%
        \ifx#3\empty\else{% append footnotes, if any
           \begin{BlockClass}{tnotes}%     lwarp
           #3
           \end{BlockClass}%               lwarp
        }
        \fi
        \ifx\@CTbotcap\undefined\end{sidecaption}\fi
        \ifx\@CTbotcap\@CTtrue\vskip\@CTcaptionskip\@CTCaption\fi
       \end{BlockClass}
    \end{center}
   \@CTend
}
\LWR@formatted{ctable}
```

Required to properly detect the toprule:

```
\LetLtxMacro\FL\toprule
```

Table notes are redefined for HTML:

```
\newcommand{\LWR@HTML@tmark}[1][a]{%
   \textsuperscript{\textrm{\textit{#1}}}
}
```

```
\LWR@formatted{tmark}

\newcommand{\LWR@HTML@tnote}[2][a]{%
    \tmark[#1]\,#2\par
}
\LWR@formatted{tnote}
```

File 103 **lwarp-cuted.sty**

§ 211 Package cuted

(*Emulates or patches code by* Sigitas Tolušis.)

Pkg cuted cuted is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{cuted}[2012/10/04]

\newenvironment{strip}{}{}
\newskip\stripsep
\def\oldcolsbreak#1{}
```

File 104 **lwarp-cutwin.sty**

§ 212 Package cutwin

(*Emulates or patches code by* Peter Wilson and Alan Hoenig.)

Pkg cutwin cutwin is emulated.

for HTML output: Discard all options for lwarp-cutwin:

```
\LWR@ProvidesPackageDrop{cutwin}[2010/09/29]

\newcommand*{\opencutleft}{}
\newcommand*{\opencutright}{}
\newcommand*{\opencutcenter}{}
\newcommand*{\cutfuzz}{}

\newenvironment{cutout}[4]
{\marginpar{\windowpagestuff}}
{}

\newcommand*{\windowpagestuff}{}

\newcommand*{\pageinwindow}{%
% \begin{minipage}{.3\linewidth}
\windowpagestuff
% \end{minipage}
}

\newenvironment{shapedcutout}[3]
```

```
{\marginpar{\picinwindow}}
{}

\newcommand*{\putstuffinpic}{}

\newcommand*{\picinwindow}{%
\begin{picture}(0,0)
\putstuffinpic
\end{picture}}
```

File 105 **lwarp-dblfloatfix.sty**

§ 213 Package dblfloatfix

Pkg dblfloatfix dblfloatfix is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{dblfloatfix}[2012/12/31]
```

File 106 **lwarp-dblfnote.sty**

§ 214 Package dblfnote

(*Emulates or patches code by* Hiroshi Nakashima.)

Pkg dblfnote dblfnote is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{dblfnote}[1999/07/14]

\newcounter{DFNsloppiness}
\newdimen\DFNcolumnsep
\newdimen\DFNcolumnwidth
\def\DFNallowcbreak{}
\def\DFNinhibitcbreak{}
\def\DFNtrysingle{}
\def\DFNalwaysdouble{}
\def\DFNruleboth{}
\def\DFNruleleft{}
```

File 107 **lwarp-dcolumn.sty**

§ 215 Package dcolumn

Pkg dcolumn dcolumn is emulated by the lwarp core.

```
\LWR@ProvidesPackageDrop{dcolumn}[2014/10/28]
```

File 108 **lwarp-decimal.sty**

§ 216 Package decimal

(*Emulates or patches code by* A. Syropoulos and R. W. D. Nickalls.)

Pkg decimal decimal works as-is for SVG math, and is emulated for MathJax.

for HTML output:

```
\LWR@ProvidesPackagePass{decimal}[2011/06/03]

\begin{warpMathJax}
\CustomizeMathJax{\def\.{\mbox{.}}}
\end{warpMathJax}
```

File 109 **lwarp-decorule.sty**

§ 217 Package decorule

(*Emulates or patches code by* Peter Flynn.)

Pkg decorule decorule is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{decorule}[2020/04/01]

\xpretocmd{\decorule}
    {\begin{lateximage}*[decorule]}
    {}
    {\LWR@patcherror{decorule}{decorule A}}

\xapptocmd{\decorule}
    {\end{lateximage}}
    {}
    {\LWR@patcherror{decorule}{decorule B}}
```

File 110 **lwarp-diagbox.sty**

§ 218 Package diagbox

(*Emulates or patches code by* Leo Liu.)

Pkg diagbox diagbox is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{diagbox}[2016/12/28]
```

To restore print-mode inside a `lateximage`:

```
\LetLtxMacro\LWR@origdiagbox@double\diagbox@double
\LetLtxMacro\LWR@origdiagbox@triple\diagbox@triple

\appto\LWR@restoreorigformatting{%
\LetLtxMacro\diagbox@double\LWR@origdiagbox@double%
\LetLtxMacro\diagbox@triple\LWR@origdiagbox@triple%
}
```

`\LWR@diagbox@AB` {⟨*E/W*⟩} {⟨*A*⟩} {⟨*E/W*⟩} {⟨*B*⟩}

```
\newcommand{\LWR@diagbox@AB}[4]{
\begingroup%
\LetLtxMacro\\\newline%
\BlockClassSingle{diagbox#1}{#2}%
\BlockClassSingle{diagbox#3}{#4}%
\endgroup%
\LWR@stoppars%
}
```

`\LWR@diagboxNW` {⟨*A*⟩} {⟨*B*⟩}

```
\newcommand{\LWR@diagboxNW}[2]{%
\LWR@diagbox@AB{E}{#2}{W}{#1}%
}
```

Likewise for NE, SW, SE:

```
\newcommand{\LWR@diagboxNE}[2]{%
\LWR@diagbox@AB{W}{#1}{E}{#2}%
}

\let\LWR@diagboxSW\LWR@diagboxNE
\let\LWR@diagboxSE\LWR@diagboxNW
```

`\diagbox@double` {⟨*keys*⟩} {⟨*A*⟩} {⟨*B*⟩}

```
\def\diagbox@double#1#2#3{%
\setkeys{diagbox}{dir=NW,#1}%
\@nameuse{LWR@diagbox\diagbox@dir}{#2}{#3}%
}
```

`\LWR@diagboxTNW` {⟨*title*⟩} {⟨*A*⟩} {⟨*B*⟩}

```
\newcommand{\LWR@diagboxTNW}[3]{%
\BlockClassSingle{diagboxtitleN}{#1}
\LWR@diagboxNW{#2}{#3}
}
```

Likewise for NE, SW, SE:

```
\newcommand{\LWR@diagboxTNE}[3]{%
\BlockClassSingle{diagboxtitleN}{#1}
\LWR@diagboxNE{#2}{#3}
}
```

```
38
39 \newcommand{\LWR@diagboxTSW}[3]{%
40 \LWR@diagboxSW{#2}{#3}
41 \BlockClassSingle{diagboxtitleS}{#1}
42 \LWR@stoppars%
43 }
44
45 \newcommand{\LWR@diagboxTSE}[3]{%
46 \LWR@diagboxSE{#2}{#3}
47 \BlockClassSingle{diagboxtitleS}{#1}
48 \LWR@stoppars%
49 }
```

\diagbox@triple {⟨*keys*⟩} {⟨*A*⟩} {⟨*T*⟩} {⟨*B*⟩}

```
50 \def\diagbox@triple#1#2#3#4{%
51 \setkeys{diagbox}{dir=NW,#1}%
52 \@nameuse{LWR@diagboxT\diagbox@dir}{#3}{#2}{#4}%
53 }
```

File 111 **lwarp-dingbat.sty**

§ 219 Package

dingbat

(*Emulates or patches code by* Scott Pakin.)

Pkg dingbat dingbat is patched for use by lwarp.

for HTML output:

```
1 \LWR@ProvidesPackagePass{dingbat}[2001/04/27]

2 \newcommand*{\LWR@dingbatsymbol}[1]{\HTMLunicode{#1}}
3
4 \newcommand{\LWR@HTML@rightpointright}{\LWR@dingbatsymbol{261E}}
5 \newcommand{\LWR@HTML@leftpointright}{\LWR@dingbatsymbol{261E}}
6 \newcommand{\LWR@HTML@leftthumbsdown}{\LWR@dingbatsymbol{1F44E}}
7 \newcommand{\LWR@HTML@leftthumbsup}{\LWR@dingbatsymbol{1F44D}}
8 \newcommand{\LWR@HTML@rightpointleft}{\LWR@dingbatsymbol{261C}}
9 \newcommand{\LWR@HTML@rightthumbsdown}{\LWR@dingbatsymbol{1F44E}}
10 \newcommand{\LWR@HTML@rightthumbsup}{\LWR@dingbatsymbol{1F44D}}
11 \newcommand{\LWR@HTML@squarewithdots}{\LWR@dingbatsymbol{25C7}}
12 \newcommand{\LWR@HTML@filledsquarewithdots}{\LWR@dingbatsymbol{25C6}}
13 \newcommand{\LWR@HTML@Sborder}{\LWR@dingbatsymbol{271A}}
14 \newcommand{\LWR@HTML@Zborder}{\LWR@dingbatsymbol{274B}}
15 \newcommand{\LWR@HTML@largepencil}{\LWR@dingbatsymbol{270E}}
16 \newcommand{\LWR@HTML@anchor}{\LWR@dingbatsymbol{2693}}
17 \newcommand{\LWR@HTML@carriagereturn}{\LWR@dingbatsymbol{23CE}}
18 \newcommand{\LWR@HTML@checkmark}{\LWR@dingbatsymbol{2713}}
19 \newcommand{\LWR@HTML@eye}{\LWR@dingbatsymbol{1F441}}
20 \newcommand{\LWR@HTML@satellitedish}{\LWR@dingbatsymbol{1F4E1}}
21 \newcommand{\LWR@HTML@smallpencil}{\LWR@dingbatsymbol{270E}}
22
23 \LWR@formatted{rightpointright}
24 \LWR@formatted{leftpointright}
```

```
\LWR@formatted{leftthumbsdown}
\LWR@formatted{leftthumbsup}
\LWR@formatted{rightpointleft}
\LWR@formatted{rightthumbsdown}
\LWR@formatted{rightthumbsup}
\LWR@formatted{squarewithdots}
\LWR@formatted{filledsquarewithdots}
\LWR@formatted{Sborder}
\LWR@formatted{Zborder}
\LWR@formatted{largepencil}
\LWR@formatted{anchor}
\LWR@formatted{carriagereturn}
\LWR@formatted{checkmark}
\LWR@formatted{eye}
\LWR@formatted{satellitedish}
\LWR@formatted{smallpencil}
```

File 112 **lwarp-DotArrow.sty**

§ 220 Package

DotArrow

(*Emulates or patches code by* Sven Schneider.)

Pkg DotArrow DotArrow is patched for use by lwarp, and emulated for MathJax.

for HTML output:

```
\LWR@ProvidesPackagePass{DotArrow}[2007/02/12]
```

The width must be recomputed each time, depending on print or HTML output.

```
\xpretocmd{\dotarrow}{\settowidth{\oneWidth}{\onePartX}}{}{}

\begin{warpMathJax}
\CustomizeMathJax{\newcommand{\dotarrow}[1]{\stackrel{#1}{\unicode{x21E2}}}}
\end{warpMathJax}
```

File 113 **lwarp-dotlessi.sty**

§ 221 Package

dotlessi

(*Emulates or patches code by* Javier Bezos.)

Pkg dotlessi dotlessi is used as-is for SVG math, and is emulated for MathJax.

⚠ HTML \dotlessj Use \usepackage{cmap} if \dotlessj does not appear in HTML in text mode. See section 7.4.

⚠ not bold For MathJax, use \boldsymbol instead of \mathbf.

for HTML output:

```
\LWR@ProvidesPackagePass{dotlessi}[1999/10/12]
```

For MathJax:

```
\begin{warpMathJax}
\CustomizeMathJax{\let\dotlessi\imath}
\CustomizeMathJax{\let\dotlessj\jmath}
\end{warpMathJax}
```

File 114 **lwarp-dprogress.sty**

§ 222 Package

dprogress

Pkg dprogress

dprogress is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{dprogress}[2008/02/21]
```

File 115 **lwarp-draftcopy.sty**

§ 223 Package

draftcopy

Pkg draftcopy

draftcopy is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{draftcopy}[2002/02/25]

\newcommand{\draftcopyVersion}[1]{}
\newcommand{\draftcopySetGrey}[1]{}
\newcommand{\draftcopySetScale}[1]{}
\newcommand{\draftcopySetScaleFactor}[1]{}
\newcommand{\draftcopyFirstPage}[1]{}
\newcommand{\draftcopyLastPage}[1]{}
\newcommand{\draftcopyName}[2]{}
\newcommand{\draftcopyPageTransform}[1]{}
\newcommand{\draftcopyBottomTransform}[1]{}
\newcommand{\draftcopyPageX}[1]{}
\newcommand{\draftcopyPageY}[1]{}
\newcommand{\draftcopyBottomX}[1]{}
\newcommand{\draftcopyBottomY}[1]{}
```

File 116 **lwarp-draftfigure.sty**

§ 224 Package

draftfigure

Pkg draftfigure

draftfigure is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{draftfigure}[2017/07/19]
\RequirePackage{xkeyval}
```

```
\define@key{draftfigure}{code}{}
\define@key{draftfigure}{noframe}[true]{}
\define@key{draftfigure}{filename}[true]{}
\define@key{draftfigure}{content}[]{}
\define@key{draftfigure}{style}[normal]{}
\define@key{draftfigure}{position}[left]{}
\define@key{draftfigure}{size}[normal]{}
\newcommand\setdf[1]{\setkeys{draftfigure}{#1}}
```

File 117 **lwarp-draftwatermark.sty**

§ 225 Package draftwatermark

(*Emulates or patches code by* Sergio Callegari.)

Pkg draftwatermark draftwatermark is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{draftwatermark}[2020/03/14]

\newcommand{\DraftwatermarkOptions}[1]{}
\newcommand{\DraftwatermarkStdMark}{}
\newcommand{\SetWatermarkAngle}[1]{}
\newcommand{\SetWatermarkColor}[1]{}
\newcommand{\SetWatermarkLightness}[1]{}
\newcommand{\SetWatermarkFontSize}[1]{}
\newcommand{\SetWatermarkScale}[1]{}
\newcommand{\SetWatermarkHorCenter}[1]{}
\newcommand{\SetWatermarkVertCenter}[1]{}
\newcommand{\SetWatermarkText}[1]{}
```

File 118 **lwarp-drftcite.sty**

§ 226 Package drftcite

(*Emulates or patches code by* Donald Arseneau.)

Pkg drftcite drftcite is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{drftcite}[1995/01/23]

\def\@lbibitem[#1]#2{\global\@HighCite\z@
  \item[
    \textsuperscript{\@nameuse{DCN@#2\@extra@b@citeb}}~%     lwarp
    \@biblabel{\@ifundefined{DCN@#2\@extra@b@citeb}{\@warning
    {Reference `#2' on page \thepage\space was never cited}}{}%
%    \DC@llap{$^{\@nameuse{DCN@#2\@extra@b@citeb}}$\ \ }%%o
   \@citeverb{#2}}\hfil]\if@filesw{\def\protect##1{\string ##1\space}%
   \immediate\write\@auxout{\string\bibcite{#2}{#1}}}\fi\ignorespaces}
```

File 119 **lwarp-easy-todo.sty**

§ 227 Package

easy-todo

(*Emulates or patches code by* Juan Rada-Vilela.)

Pkg easy-todo easy-todo is patched for use by lwarp.

To remove the "P." heading for HTML:

```
\warpHTMLonly{\renewcommand{\todoindexpagetitle}{}}
```

for HTML output:

```
\LWR@ProvidesPackagePass{easy-todo}[2014/01/01]
```

\listoftodos Modified to correct buggy use of \flushright.

```
\let\LWR@easytodo@origlistoftodos\listoftodos

\renewcommand{\listoftodos}{%
\begingroup
\renewcommand{\flushright}{}
\LWR@easytodo@origlistoftodos
\endgroup
}
```

\todoii Modified to use \textcolor instead of \color.

```
\renewcommand{\todoii}[2]{%
\ifthenelse{\equal{\@todoobeyfinal}{true}}%
    {%
        \ifoptionfinal{\todoenable{false}}{\todoenable{true}}%
    }%
    {}%
\ifthenelse{\equal{\@todoenable}{true}}%
    {%
        \refstepcounter{todos}%
        \noindent{%
            \todocolor%
            \LWR@textcurrentcolor{%
                \normalfont\scriptsize{\bfseries{\thetodos.#1}}%
            }%
        }%
        \addcontentsline{lod}{todos}{\protect{\thetodos. }\LWR@isolate{#2}}%
    }%
    {}%
}
```

File 120 **lwarp-ebook.sty**

§ 228 Package ebook

(*Emulates or patches code by* Jørgen Steensgaard.)

Pkg ebook ebook is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{ebook}

\setcounter{secnumdepth}{0}
\setcounter{tocdepth}{2}

\providecommand{\pagefill}[1][0.001mm]{\noindent}

\providecommand{\ebook}{
\setcounter{secnumdepth}{0}
\setcounter{tocdepth}{2}
}
```

File 121 **lwarp-econometrics.sty**

§ 229 Package econometrics

(*Emulates or patches code by* Erik Kole.)

Pkg econometrics econometrics is used as-is for SVG math, and is emulated for MathJax.

for HTML output:

```
\LWR@ProvidesPackagePass{econometrics}% no date specified in the original

\LWR@origRequirePackage{lwarp-common-mathjax-letters}

\begin{warpMathJax}
\LWR@infoprocessingmathjax{econometrics}

\CustomizeMathJax{\newcommand{\SC}{\mathbb{C}}}
\CustomizeMathJax{\newcommand{\SN}{\mathbb{N}}}
\CustomizeMathJax{\newcommand{\SQ}{\mathbb{Q}}}
\CustomizeMathJax{\newcommand{\SR}{\mathbb{R}}}
\CustomizeMathJax{\newcommand{\SZ}{\mathbb{Z}}}

\CustomizeMathJax{\newcommand{\calA}{\mathcal{A}}}
\CustomizeMathJax{\newcommand{\calB}{\mathcal{B}}}
\CustomizeMathJax{\newcommand{\calC}{\mathcal{C}}}
\CustomizeMathJax{\newcommand{\calD}{\mathcal{D}}}
\CustomizeMathJax{\newcommand{\calE}{\mathcal{E}}}
\CustomizeMathJax{\newcommand{\calF}{\mathcal{F}}}
\CustomizeMathJax{\newcommand{\calG}{\mathcal{G}}}
\CustomizeMathJax{\newcommand{\calH}{\mathcal{H}}}
\CustomizeMathJax{\newcommand{\calI}{\mathcal{I}}}
\CustomizeMathJax{\newcommand{\calJ}{\mathcal{J}}}
\CustomizeMathJax{\newcommand{\calK}{\mathcal{K}}}
\CustomizeMathJax{\newcommand{\calL}{\mathcal{L}}}
\CustomizeMathJax{\newcommand{\calM}{\mathcal{M}}}
```

```
\CustomizeMathJax{\newcommand{\calN}{\mathcal{N}}}
\CustomizeMathJax{\newcommand{\calO}{\mathcal{O}}}
\CustomizeMathJax{\newcommand{\calP}{\mathcal{P}}}
\CustomizeMathJax{\newcommand{\calQ}{\mathcal{Q}}}
\CustomizeMathJax{\newcommand{\calR}{\mathcal{R}}}
\CustomizeMathJax{\newcommand{\calS}{\mathcal{S}}}
\CustomizeMathJax{\newcommand{\calT}{\mathcal{T}}}
\CustomizeMathJax{\newcommand{\calU}{\mathcal{U}}}
\CustomizeMathJax{\newcommand{\calV}{\mathcal{V}}}
\CustomizeMathJax{\newcommand{\calW}{\mathcal{W}}}
\CustomizeMathJax{\newcommand{\calX}{\mathcal{X}}}
\CustomizeMathJax{\newcommand{\calY}{\mathcal{Y}}}
\CustomizeMathJax{\newcommand{\calZ}{\mathcal{Z}}}

\LWR@mathjax@addlatin@u@bfit{m}% uppercase Latin, bold italic
\LWR@mathjax@addlatin@l@bfit{v}% lowercase Latin, bold italic

\LWR@mathjax@addgreek@l@bfit{v}{}% lowercase Greek bold italic
\LWR@mathjax@addgreek@u@bfit*{m}{}% uppercase Greek bold italic, capitalized macro names

\CustomizeMathJax{\newcommand{\rb}{\mathrm{b}}}
\CustomizeMathJax{\newcommand{\rB}{\mathrm{B}}}
\CustomizeMathJax{\newcommand{\rC}{\mathrm{C}}}
\CustomizeMathJax{\newcommand{\rD}{\mathrm{D}}}
\CustomizeMathJax{\newcommand{\rf}{\mathrm{f}}}
\CustomizeMathJax{\newcommand{\rF}{\mathrm{F}}}
\CustomizeMathJax{\newcommand{\rH}{\mathrm{H}}}
\CustomizeMathJax{\newcommand{\rL}{\mathrm{L}}}
\CustomizeMathJax{\newcommand{\rN}{\mathrm{N}}}
\CustomizeMathJax{\newcommand{\rt}{\mathrm{t}}}
\CustomizeMathJax{\newcommand{\rU}{\mathrm{U}}}
\CustomizeMathJax{\newcommand{\rGam}{\mathrm{Gam}}}
\CustomizeMathJax{\newcommand{\rBeta}{\mathrm{Beta}}}

\CustomizeMathJax{\newcommand{\Bin}{\mathrm{Bin}}}
\CustomizeMathJax{\newcommand{\eu}{\mathrm{e}}}
\CustomizeMathJax{\newcommand{\iu}{\mathrm{i}}}
\CustomizeMathJax{\newcommand{\LN}{\mathrm{LN}}}
\CustomizeMathJax{\newcommand{\IN}{\mathrm{IN}}}

\CustomizeMathJax{\newcommand{\Poi}{\mathrm{Poi}}}

\CustomizeMathJax{\newcommand{\ped}[1]{_\mathrm{#1}}}
\CustomizeMathJax{\newcommand{\ap}[1]{^\mathrm{#1}}}
\CustomizeMathJax{\renewcommand{\Re}{\mathrm{Re}}{\nolimits}}
\CustomizeMathJax{\renewcommand{\Im}{\mathrm{Im}}{\nolimits}}

\CustomizeMathJax{\newcommand{\deriv}[3][]{%
    \frac{\mathrm{d}^{#1}#2}{\mathrm{d}\,#3^{#1}}%
}}
\CustomizeMathJax{\newcommand{\pderiv}[3][]{%
    \frac{\partial^{#1}#2}{\partial #3^{#1}}%
}}

\CustomizeMathJax{\newcommand{\bias}{\operatorname{bias}}}
```

```
\CustomizeMathJax{\newcommand{\col}{\operatorname{col}}}
\CustomizeMathJax{\newcommand{\corr}{\operatorname{corr}}}
\CustomizeMathJax{\newcommand{\cov}{\operatorname{cov}}}
\CustomizeMathJax{\newcommand{\dg}{\operatorname{dg}}}
\CustomizeMathJax{\newcommand{\diag}{\operatorname{diag}}}
\CustomizeMathJax{\newcommand{\E}{\operatorname{E}}}
\CustomizeMathJax{\newcommand{\etr}{\operatorname{etr}}}
\CustomizeMathJax{\newcommand{\ip}{\mathrm{int}}{\nolimits}}
\CustomizeMathJax{\newcommand{\kur}{\operatorname{kur}}}
\CustomizeMathJax{\newcommand{\MSE}{\operatorname{MSE}}}
\CustomizeMathJax{\newcommand{\MSFE}{\operatorname{MSFE}}}
\CustomizeMathJax{\newcommand{\OLS}{\operatorname{OLS}}}
\CustomizeMathJax{\newcommand{\plim}{\operatorname{plim}}}
\CustomizeMathJax{\newcommand{\resid}{\operatorname{resid}}}
\CustomizeMathJax{\newcommand{\rk}{\operatorname{rk}}}
\CustomizeMathJax{\newcommand{\SE}{\operatorname{SE}}}
\CustomizeMathJax{\newcommand{\sgn}{\operatorname{sgn}}}
\CustomizeMathJax{\newcommand{\tr}{\operatorname{tr}}}
\CustomizeMathJax{\newcommand{\var}{\operatorname{var}}}
\CustomizeMathJax{\renewcommand{\vec}{\operatorname{vec}}}
\CustomizeMathJax{\newcommand{\vech}{\operatorname{vech}}}

\CustomizeMathJax{\newcommand{\distr}{\sim}}
\CustomizeMathJax{\newcommand{\adistr}{\stackrel{a}{\distr}}}
\CustomizeMathJax{\newcommand{\diff}{\Delta}}
\CustomizeMathJax{\newcommand{\fdiff}{\diff_{\rf}}}
\CustomizeMathJax{\newcommand{\bdiff}{\diff_{\rb}}}

\CustomizeMathJax{\newcommand{\eps}{\epsilon}}
\CustomizeMathJax{\newcommand{\epsi}{\varepsilon}}

\CustomizeMathJax{\newcommand{\longto}{\longrightarrow}}
\CustomizeMathJax{\newcommand{\pto}{\stackrel{p}{\longrightarrow}}}
\CustomizeMathJax{\newcommand{\dto}{\stackrel{d}{\longrightarrow}}}
\CustomizeMathJax{\newcommand{\wto}{\stackrel{w}{\longrightarrow}}}

\CustomizeMathJax{\newcommand{\Infmat}{\bm\calI}}
\CustomizeMathJax{\newcommand{\Hesmat}{\bm\calH}}
\CustomizeMathJax{\newcommand{\bcdot}{\bullet}}

\CustomizeMathJax{\newcommand{\vones}{\bm\imath}}
\CustomizeMathJax{\newcommand{\vzeros}{\boldsymbol{0}}}
\CustomizeMathJax{\newcommand{\mZeros}{\mathbf{O}}}

\CustomizeMathJax{\newcommand{\e}{\eu}}
\CustomizeMathJax{\newcommand{\mply}{\cdot}}
\CustomizeMathJax{\newcommand{\rW}{\ensuremath{\mathrm{W}}}}
\end{warpMathJax}
```

File 122 **lwarp-ed.sty**

§ 230 Package ed

(*Emulates or patches code by* Michael Kohlhase.)

Pkg ed ed is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{ed}[2012/01/29]
```

Bugs:

1. `todolist` fails with the `hide` option, as does `\edexplanation`.
2. `\edstubURI` is actually `\edstuURI`.

```
\RequirePackage{xcolor}

\renewenvironment{edstub}[2][The following blue text]
{%
    \def\@test{#1}%
    \begin{center}%
        \huge%
        \textcolor{red}{%
            #1 is only a provisional stub\\\Large
            the Office document
            \ifx\ed@stubURI\@empty{#2}\else\LWR@href{\ed@stubURI}{#2}\fi\
            contains more text\\which will be merged for the final document%
        }%
    \end{center}%
    \BlockClass[color:blue]{edstub}%
}
{\endBlockClass}
```

File 123 **lwarp-ellipsis.sty**

§ 231 Package ellipsis

(*Emulates or patches code by* Peter J. Heslin.)

Pkg ellipsis ellipsis is emulated.

```
\LWR@ProvidesPackageDrop{ellipsis}[2004/09/28]

\newcommand{\ellipsisgap}{0.1em}

\newcommand*{\midwordellipsis}{\,\textellipsis\,}
```

File 124 **lwarp-embrac.sty**

§ 232 Package embrac

(*Emulates or patches code by* Clemens Niederberger.)

Pkg embrac embrac is patched for HTML and used as-is for print.

for HTML output:

```
\LWR@ProvidesPackagePass{embrac}[2017/07/04]

\ExplSyntaxOn
\RenewDocumentCommand{\embrac_kern:n}{m}{}
\ExplSyntaxOff

\LetLtxMacro\LWR@orig@HTML@emph\LWR@HTML@emph
\RenewDocumentCommand{\LWR@HTML@emph}{s m}{\LWR@orig@HTML@emph{#2}}

\LetLtxMacro\LWR@orig@HTML@textit\LWR@HTML@textit
\RenewDocumentCommand{\LWR@HTML@textit}{s m}{\LWR@orig@HTML@textit{#2}}

\LetLtxMacro\LWR@orig@HTML@textsl\LWR@HTML@textsl
\RenewDocumentCommand{\LWR@HTML@textsl}{s m}{\LWR@orig@HTML@textsl{#2}}

\ifxetexorluatex
    \LetLtxMacro\LWR@orig@HTML@textsi\LWR@HTML@textsi
    \RenewDocumentCommand{\LWR@HTML@textsi}{s m}{%
    \LWR@orig@HTML@textsi{#2}}
\fi

\AtBeginDocument{
    \LWR@formatted{emph}
    \LWR@formatted{textit}
    \LWR@formatted{textsl}
    \ifxetexorluatex
        \LWR@formatted{textsi}
    \fi
}

\newcommand{\LWR@HTML@EmbracOff}{}
\LWR@formatted{EmbracOff}

\newcommand{\LWR@HTML@EmbracOn}{}
\LWR@formatted{EmbracOn}
```

File 125 **lwarp-emptypage.sty**

§ 233 Package emptypage

Pkg emptypage emptypage is ignored.

for HTML output: Discard all options for lwarp-emptypage:

```
\LWR@ProvidesPackageDrop{emptypage}[2010/05/30]
```

File 126 **lwarp-endfloat.sty**

§ 234 Package endfloat

Pkg endfloat endfloat is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{endfloat}[2019/04/15]

\newcommand\figureplace{}
\newcommand\tableplace{}
\newcommand\floatplace[1]{}
\newcounter{posttable}
\newcounter{postfigure}
\newcommand*{\theposttbl}{}
\newcommand*{\thepostfig}{}
\newcommand{\AtBeginFigures}[1]{}
\newcommand{\AtBeginTables}[1]{}
\newcommand{\AtBeginDelayedFloats}[1]{}
\newcommand*{\processdelayedfloats}{}
\newcommand*{\efloatseparator}{}
\def\efloattype{}
\providecommand\efloatheading[1]{}
\providecommand\efloatpreamble{}
\providecommand\efloatpostamble{}
\NewDocumentCommand{\addtodelayedfloat}{s m m}{}
\providecommand{\efloatbegin}{}
\providecommand{\efloatend}{}
\providecommand{\efloatbeginlist}{}
\providecommand{\efloatendlist}{}
```

File 127 **lwarp-endheads.sty**

§ 235 Package endheads

Pkg endheads endheads is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{endheads}[2017/04/06]

\newcommand{\changesinglepageabbrev}[1]{}
\newcommand{\changemultiplepageabbrev}[1]{}
\newcommand{\changenotesname}[1]{}
\newcommand{\changenotesheader}[1]{}
\newcommand{\changenotescontentsname}[1]{}
\newcommand{\changechapternotesline}[1]{}
\newcommand{\checknoteheaders}{}
\newif\ifnotesincontentson \notesincontentsonfalse
\newcommand{\notesincontents}{\notesincontentsontrue}
\newif\ifendnoteheaderson \endnoteheadersonfalse
\newcommand{\setupendnoteheaders}{%
    \endnoteheadersontrue%
}
\newif\iftitleinnotes \titleinnotestrue
\newcommand{\styleforchapternotebegin}{}
\newcommand{\styleforchapternoteend}{}
```

```
\newcommand{\setstyleforchapternotebegin}[1]{%
    \renewcommand{\styleforchapternotebegin}{#1}%
}
\newcommand{\setstyleforchapternoteend}[1]{%
    \renewcommand{\styleforchapternoteend}{#1}%
}
\newcommand{\resetendnotes}{}
\newif\ifnotesbychapteron \notesbychapteronfalse
\newcommand{\notesbychapter}{\notesbychapterontrue}
```

File 128 **lwarp-endnotes.sty**

§ 236 Package

endnotes

(*Emulates or patches code by* John Lavagnino.)

Pkg endnotes Patched for HTML.

table of contents To place the endnotes in the TOC, use:

```
\usepackage{endnotes}
\appto\enoteheading{\addcontentsline{toc}{section}{\notesname}}
\renewcommand*{\notesname}{Endnotes} % optional
```

HTML page To additionally have the endnotes on their own HTML page, if `FileDepth` allows:

```
\ForceHTMLPage
\theendnotes
```

⚠ `\endnotemark` numbering If using MathJax, see section 8.5.4 regarding the use of `\endnotemark` and `\endnotetext`.

for HTML output:

```
\LWR@ProvidesPackagePass{endnotes}

\def\enoteformat{%
% \rightskip\z@ \leftskip\z@ \parindent=1.8em
\leavevmode
% \llap{
\makeenmark
% }
}

\def\LWR@HTML@@makeenmark{\hbox{\LWR@htmlspan{sup}{\normalfont\theenmark}}}
\LWR@formatted{@makeenmark}

\def\makeenmark{\@makeenmark}
```

For MathJax:

```
\begin{warpMathJax}
\def\endnotename{endnote}
\appto\LWR@syncnotenumbers{\LWR@synconenotenumber{LWRendnote}{\theendnote}}
\appto\LWR@syncnotenames{\LWR@synconenotename{LWRendnote}{\endnotename}}
```

```
\CustomizeMathJax{\def\LWRendnote{1}}
\CustomizeMathJax{\newcommand{\endnote}[2][\LWRendnote]{{}^{\mathrm{#1}}}}
\CustomizeMathJax{\newcommand{\endnotemark}[1][\LWRendnote]{{}^{\mathrm{#1}}}}
\end{warpMathJax}
```

File 129 **lwarp-engtlc.sty**

§ 237 Package

engtlc

(*Emulates or patches code by* Claudio Fiandrino.)

Pkg engtlc engtlc is patched for use by lwarp. MathJax is emulated.

⚠ For MathJax, \signt, \signf, \signn, and \signz do not force letter case as they do in svg math.

for HTML output:

```
\LWR@ProvidesPackagePass{engtlc}[2012/12/18]

\newcommand{\LWR@HTML@finees}{%
    \begin{BlockClass}[text-align:right]{exerend}%
    \HTMLunicode{220E}%
    \end{BlockClass}%
}
\LWR@formatted{finees}

\newcommand{\LWR@HTML@exerend}{\finees}
\LWR@formatted{exerend}

\begin{warpMathJax}
\LWR@infoprocessingmathjax{engtlc}

\CustomizeMathJax{\newcommand{\unit}[1]{\,\mathrm{#1}}}
\CustomizeMathJax{\newcommand{\micro}{\mathrm{\unicode{x00B5}}}}
%
\CustomizeMathJax{\newcommand{\ho}{\unit{h}}}
\CustomizeMathJax{\newcommand{\s}{\unit{s}}}
\CustomizeMathJax{\newcommand{\ms}{\unit{ms}}}
\CustomizeMathJax{\newcommand{\us}{\unit{\micro s}}}
\CustomizeMathJax{\newcommand{\ns}{\unit{ns}}}
\CustomizeMathJax{\newcommand{\ps}{\unit{ps}}}
%
\CustomizeMathJax{\newcommand{\um}{\unit{\micro m}}}
\CustomizeMathJax{\newcommand{\mm}{\unit{mm}}}
\CustomizeMathJax{\newcommand{\cm}{\unit{cm}}}
\CustomizeMathJax{\newcommand{\dm}{\unit{dm}}}
\CustomizeMathJax{\newcommand{\m}{\unit{m}}}
\CustomizeMathJax{\newcommand{\km}{\unit{km}}}
%
\CustomizeMathJax{\newcommand{\MA}{\unit{MA}}}
\CustomizeMathJax{\newcommand{\kA}{\unit{kA}}}
\CustomizeMathJax{\newcommand{\A}{\unit{A}}}
\CustomizeMathJax{\newcommand{\mA}{\unit{mA}}}
\CustomizeMathJax{\newcommand{\uA}{\unit{\micro A}}}
```

```
\CustomizeMathJax{\newcommand{\nA}{\unit{nA}}}
%
\CustomizeMathJax{\newcommand{\MV}{\unit{MV}}}
\CustomizeMathJax{\newcommand{\kV}{\unit{kV }}}
\CustomizeMathJax{\newcommand{\V}{\unit{V}}}
\CustomizeMathJax{\newcommand{\mV}{\unit{mV}}}
\CustomizeMathJax{\newcommand{\uV}{\unit{\micro V}}}
%
\CustomizeMathJax{\newcommand{\mohm}{\unit{m\Omega}}}
\CustomizeMathJax{\newcommand{\ohm}{\unit{\Omega}}}
\CustomizeMathJax{\newcommand{\kohm}{\unit{k\Omega}}}
\CustomizeMathJax{\newcommand{\Mohm}{\unit{M\Omega}}}
%
\CustomizeMathJax{\newcommand{\pSi}{\unit{pS}}}
\CustomizeMathJax{\newcommand{\nSi}{\unit{nS}}}
\CustomizeMathJax{\newcommand{\uSi}{\unit{\micro S}}}
\CustomizeMathJax{\newcommand{\mSi}{\unit{mS}}}
\CustomizeMathJax{\newcommand{\Si}{\unit{S}}}
\CustomizeMathJax{\newcommand{\kSi}{\unit{kS}}}
\CustomizeMathJax{\newcommand{\MSi}{\unit{MS}}}
%
\CustomizeMathJax{\newcommand{\fFa}{\unit{fF}}}
\CustomizeMathJax{\newcommand{\pFa}{\unit{pF}}}
\CustomizeMathJax{\newcommand{\nFa}{\unit{nF}}}
\CustomizeMathJax{\newcommand{\uFa}{\unit{\micro F}}}
\CustomizeMathJax{\newcommand{\mFa}{\unit{mF}}}
\CustomizeMathJax{\newcommand{\Fa}{\unit{F}}}
%
\CustomizeMathJax{\newcommand{\fHe}{\unit{fH}}}
\CustomizeMathJax{\newcommand{\pHe}{\unit{pH}}}
\CustomizeMathJax{\newcommand{\nHe}{\unit{nH}}}
\CustomizeMathJax{\newcommand{\uHe}{\unit{\micro H}}}
\CustomizeMathJax{\newcommand{\mHe}{\unit{mH}}}
\CustomizeMathJax{\newcommand{\He}{\unit{H}}}
%
\CustomizeMathJax{\newcommand{\dB}{\unit{dB}}}
\CustomizeMathJax{\newcommand{\dBm}{\unit{dBm}}}
%
\CustomizeMathJax{\newcommand{\uW}{\unit{\micro W}}}
\CustomizeMathJax{\newcommand{\mW}{\unit{mW}}}
\CustomizeMathJax{\newcommand{\W}{\unit{W}}}
\CustomizeMathJax{\newcommand{\kW}{\unit{kW}}}
\CustomizeMathJax{\newcommand{\MW}{\unit{MW}}}
%
\CustomizeMathJax{\newcommand{\Hz}{\unit{Hz}}}
\CustomizeMathJax{\newcommand{\kHz}{\unit{kHz}}}
\CustomizeMathJax{\newcommand{\MHz}{\unit{MHz}}}
\CustomizeMathJax{\newcommand{\GHz}{\unit{GHz}}}
\CustomizeMathJax{\newcommand{\THz}{\unit{THz}}}
%
\CustomizeMathJax{\newcommand{\bit}{\unit{bit}}}
\CustomizeMathJax{\newcommand{\kbit}{\unit{Kib}}}
\CustomizeMathJax{\newcommand{\Mbit}{\unit{Mib}}}
\CustomizeMathJax{\newcommand{\Byte}{\unit{B}}}
\CustomizeMathJax{\newcommand{\kByte}{\unit{KiB}}}
```

```
\CustomizeMathJax{\newcommand{\MByte}{\unit{Mib}}}
\CustomizeMathJax{\newcommand{\GByte}{\unit{GiB}}}
\CustomizeMathJax{\newcommand{\TByte}{\unit{TiB}}}
\CustomizeMathJax{\newcommand{\bits}{\unit{bit/s}}}
\CustomizeMathJax{\newcommand{\kbits}{\unit{Kib/s}}}
\CustomizeMathJax{\newcommand{\Mbits}{\unit{Mib/s}}}
\CustomizeMathJax{\newcommand{\Bytes}{\unit{B/s}}}
\CustomizeMathJax{\newcommand{\kBytes}{\unit{KiB/s}}}
\CustomizeMathJax{\newcommand{\MBytes}{\unit{MiB/s}}}
\CustomizeMathJax{\newcommand{\GBytes}{\unit{GiB/s}}}
\CustomizeMathJax{\newcommand{\TBytes}{\unit{TiB/s}}}
\CustomizeMathJax{\newcommand{\chips}{\unit{chip/s}}}
\CustomizeMathJax{\newcommand{\kchips}{\unit{Ki\mkern2mu chip/s}}}
\CustomizeMathJax{\newcommand{\Mchips}{\unit{Mi\mkern2mu chip/s}}}
\CustomizeMathJax{\newcommand{\chipsubit}{\unit{chip/bit}}}
%
\CustomizeMathJax{\newcommand{\frecciadex}[1][0.5]{%
    \hspace{.25cm}\Longrightarrow \hspace{.25cm}}%
}
\CustomizeMathJax{\newcommand{\varianzarumore}{\frac{N_0}{2}}}
%
\CustomizeMathJax{\newcommand{\etsymbolbracearg}[2]{%
    #1\mathopen{}\left\lbrace#2\right\rbrace\mathclose{}}%
}
\CustomizeMathJax{\newcommand{\fourier}[1]{\etsymbolbracearg{\mathcal{F}}{#1}}}
\CustomizeMathJax{\newcommand{\invfourier}[1]{\etsymbolbracearg{\mathcal{F}^{-1}}{#1}}}
\CustomizeMathJax{\newcommand{\partereale}[1]{\etsymbolbracearg{\textbf{Re}}{#1}}}
\CustomizeMathJax{\newcommand{\parteimm}[1]{\etsymbolbracearg{\textbf{Im}}{#1}}}
\CustomizeMathJax{\newcommand{\Info}[1]{I\left(#1\right)}}
\CustomizeMathJax{\newcommand{\versore}[1]{\hat{#1}}}
\CustomizeMathJax{\newcommand{\vettore}[1]{\overrightarrow{#1}}}
\CustomizeMathJax{\newcommand{\coseno}[1]{\cos\left(2\pi#1t\right)}}
\CustomizeMathJax{\newcommand{\seno}[1]{\sin\left(2\pi#1t\right)}}
\CustomizeMathJax{\newcommand{\energia}[1]{\mathcal{E}_{#1}}}
\CustomizeMathJax{\newcommand{\moduloexp}[2]{\left\vert#1\right\vert^{#2}}}
\CustomizeMathJax{\newcommand{\modulo}[1]{\left\vert#1\right\vert}}
\CustomizeMathJax{\newcommand{\indB}[1]{%
    \mathopen{}\left.#1\right\vert_{\mathrm{dB}}\mathclose{}}}%
\CustomizeMathJax{\newcommand{\for}[2]{\left. #1 \right\vert_{#2}}}
\CustomizeMathJax{\newcommand{\massimo}[1]{\etsymbolbracearg{\max}{#1}}}
\CustomizeMathJax{\newcommand{\minimo}[1]{\etsymbolbracearg{\min}{#1}}}
\CustomizeMathJax{\newcommand{\valc}{3\cdot 10^8}}
\CustomizeMathJax{\newcommand{\loga}[2]{\log_{#1}#2}}
\CustomizeMathJax{\newcommand{\analitic}[1]{\mathring{#1}}}
\CustomizeMathJax{\newcommand{\diff}{\mathop{}\mathopen{\mathrm{d}}}}
\CustomizeMathJax{\newcommand{\intinf}[1]{\int_{-\infty}^{+\infty}{#1}}}
\CustomizeMathJax{\newcommand{\deltain}[1]{\delta\left(#1\right)}}
\CustomizeMathJax{\newcommand{\iu}{\mathrm{j}}}
\CustomizeMathJax{\newcommand{\ex}[1]{\mathrm{e}^{#1}}}
%
\CustomizeMathJax{\newcommand{\gammatens}{{}^{\mathrm{V}}\Gamma}}
\CustomizeMathJax{\newcommand{\gammacorr}{{}^{\mathrm{I}}\Gamma}}
\CustomizeMathJax{\newcommand{\gammatensin}[1]{{}^{\mathrm{V}}\Gamma_{\mathrm{#1}}}}
\CustomizeMathJax{\newcommand{\gammacorrin}[1]{{}^{\mathrm{I}}\Gamma_{\mathrm{#1}}}}
\CustomizeMathJax{\newcommand{\gammain}[1]{\Gamma_{\mathrm{#1}}}}
```

```
\CustomizeMathJax{\newcommand{\gammak}{{}^{\mathrm{k}}\Gamma}}
%
\CustomizeMathJax{\newcommand{\lbvt}{\lambda_0}}
\CustomizeMathJax{\newcommand{\lbg}{\lambda_g}}
\CustomizeMathJax{\newcommand{\lbgvt}{\lambda_{g_0}}}
%
\CustomizeMathJax{\newcommand{\potin}[1]{P_{\mathrm{#1}}}}
\CustomizeMathJax{\newcommand{\potdisp}[1][]{P_{\mathrm{disp}}^{#1}}}
\CustomizeMathJax{\newcommand{\potDC}[1][]{P_{\mathrm{DC}}^{#1}}}
\CustomizeMathJax{\newcommand{\potCC}[1][]{P_{\mathrm{CC}}^{#1}}}
\CustomizeMathJax{\newcommand{\potirr}[1][]{P_{\mathrm{irr}}^{#1}}}
\CustomizeMathJax{\newcommand{\potdiss}[1][]{P_{\mathrm{diss}}^{#1}}}
\CustomizeMathJax{\newcommand{\potinc}[1][]{P_{\mathrm{inc}}^{#1}}}
%
\CustomizeMathJax{\newcommand{\z}[1]{Z_{\mathrm{#1}}}}
\CustomizeMathJax{\newcommand{\znorm}[1]{z_{\mathrm{#1}}}}
\CustomizeMathJax{\newcommand{\y}[1]{Y_{\mathrm{#1}}}}
\CustomizeMathJax{\newcommand{\ynorm}[1]{y_{\mathrm{#1}}}}
\CustomizeMathJax{\newcommand{\zinf}[1][]{Z_{\infty#1}}}
\CustomizeMathJax{\newcommand{\zinfn}[1]{\zinf[#1]}}
\CustomizeMathJax{\newcommand{\yinf}[1][]{Y_{\infty#1}}}
\CustomizeMathJax{\newcommand{\yinfn}[1]{\yinf[#1]}}
\CustomizeMathJax{\newcommand{\zvt}{Z_0}}
\CustomizeMathJax{\newcommand{\yvt}{Y_0}}
%
\CustomizeMathJax{\newcommand{\campoe}{\underline{\mathcal{E}}(\underline{r},t)}}
\CustomizeMathJax{\newcommand{\campoefas}{\underline{E}(\underline{r})}}
\CustomizeMathJax{\newcommand{\campoh}{\underline{\mathcal{H}}(\underline{r},t)}}
\CustomizeMathJax{\newcommand{\campohfas}{\underline{H}(\underline{r})}}
%
\CustomizeMathJax{\newcommand{\signt}[1]{{#1}(t)}}
\CustomizeMathJax{\newcommand{\signf}[1]{{#1}(f)}}
\CustomizeMathJax{\newcommand{\signn}[1]{{#1}(n)}}
\CustomizeMathJax{\newcommand{\signz}[1]{{#1}(z)}}
%
\CustomizeMathJax{\newcommand{\prob}[1]{\mathcal{P}\left(#1\right)}}
\CustomizeMathJax{\newcommand{\valatt}[1]{\mathbb{E}\left[#1\right]}}
\CustomizeMathJax{\newcommand{\var}[1]{\mathrm{Var}\left[#1\right]}}
\CustomizeMathJax{\newcommand{\comma}{\, , \,}}
\CustomizeMathJax{\newcommand{\dato}{\,|\,}}
%
\CustomizeMathJax{\let\bfRe\partereale}
\CustomizeMathJax{\let\bfIm\parteimm}
\CustomizeMathJax{\let\noisevar\varianzarumore}
% \CustomizeMathJax{\let\exerend\finees}
\CustomizeMathJax{\let\Spimplies\frecciadex}
\CustomizeMathJax{\let\Downimplies\frecciadown}
\CustomizeMathJax{\let\unitvec\versore}
\CustomizeMathJax{\let\vector\vettore}
\CustomizeMathJax{\let\cosine\coseno}
\CustomizeMathJax{\let\sine\seno}
\CustomizeMathJax{\let\energy\energia}
\CustomizeMathJax{\let\Abs\modulo}
\CustomizeMathJax{\let\AbsPow\moduloexp}
\CustomizeMathJax{\let\Max\massimo}
```

```
\CustomizeMathJax{\let\Min\minimo}
\CustomizeMathJax{\let\clight\valc}
\CustomizeMathJax{\let\Log\loga}
\CustomizeMathJax{\let\analytic\analitic}
\CustomizeMathJax{\let\infint\intinf}
\CustomizeMathJax{\let\deltaimp\deltain}
\CustomizeMathJax{\let\Vgamma\gammatens}
\CustomizeMathJax{\let\Cgamma\gammacorr}
\CustomizeMathJax{\let\Vgammain\gammatensin}
\CustomizeMathJax{\let\Cgammain\gammacorrin}
\CustomizeMathJax{\let\Kgamma\gammak}
\CustomizeMathJax{\let\powerin\potin}
\CustomizeMathJax{\let\availpow\potdisp}
\CustomizeMathJax{\let\irrpow\potirr}
\CustomizeMathJax{\let\disspow\potdiss}
\CustomizeMathJax{\let\incpow\potinc}
\CustomizeMathJax{\let\potalim\potCC}
\CustomizeMathJax{\let\potDC\potCC}
\CustomizeMathJax{\let\Efield\campoe}
\CustomizeMathJax{\let\Hfield\campoh}
\CustomizeMathJax{\let\phasorEfield\campoefas}
\CustomizeMathJax{\let\phasorHfiled\campohfas}
\CustomizeMathJax{\let\given\dato}
\CustomizeMathJax{\let\expval\valatt}
\CustomizeMathJax{\let\rmexp\ex}
\end{warpMathJax}
```

File 130 **lwarp-enotez.sty**

§ 238 Package enotez

(*Emulates or patches code by* Clemens Niederberger.)

Pkg enotez enotez is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{enotez}[2020/12/13]
```

Hyperref is emulated by lwarp, so it is forced on for enotez:

```
\ExplSyntaxOn
\AtBeginDocument{
    \bool_set_true:N \l__enotez_hyperref_bool
    \bool_set_true:N \l__enotez_hyperfootnotes_bool
}
```

Do not move or \hbox the \hypertarget:

```
% typeset the actual mark:
% #1: id
% #2: mark
\cs_gset_protected:Npn \enotez_write_mark:nn #1#2
  {
    \bool_if:NTF \l__enotez_hyperfootnotes_bool
```

```
      {
        \enotezwritemark { \hyperlink {enz.#1} { \enmarkstyle #2 } }
        \bool_if:NT \l__enotez_hyperbackref_bool
          {
%             \box_move_up:nn {1em} {
%                 \hbox:n {
                    \hypertarget {enz.#1.backref} { }
%                 }
%             }
          }
      }
      { \enotezwritemark { \enmarkstyle #2 } }
  }
\cs_generate_variant:Nn \enotez_write_mark:nn {x}
```

Do not move or \hbox the \hypertarget:

```
\cs_gset_protected:Npn \enotez_write_list_number:n #1
  {
    \bool_if:NT \l__enotez_hyperfootnotes_bool
      {
%         \box_move_up:nn {1em} { \hbox:n {
            \hypertarget {enz.#1} { }
%         } }
      }
    \tl_use:N \l__enotez_list_number_format_tl
    \tl_if_eq:nxTF {a} { \prop_item:Nn \g__enotez_endnote_man_prop {#1} }
      {
        \bool_if:nTF
          { \l__enotez_hyperfootnotes_bool && \l__enotez_hyperbackref_bool }
          {
            \exp_args:Nnx
            \hyperlink {enz.#1.backref}
              { \exp_not:V \l__enotez_endnote_mark_tl }
          }
          { \prop_item:Nn \g__enotez_endnote_mark_prop {#1} }
      }
      {
        \bool_if:nTF
          { \l__enotez_hyperfootnotes_bool && \l__enotez_hyperbackref_bool }
          {
            \exp_args:Nnx
            \hyperlink {enz.#1.backref}
              { \exp_not:V \l__enotez_endnote_mark_tl }
          }
          { \tl_use:N \l__enotez_endnote_mark_tl }
      }
  }
```

Do not move the label to the left:

```
\DeclareTemplateCode {enotez-list} {paragraph} {1}
  {
    heading       = \enotez_list_heading:n           ,
    format        = \l__enotez_list_format_tl        ,
```

```
    number        = \enotez_list_number:n            ,
    number-format = \l__enotez_list_number_format_tl ,
    notes-sep     = \l__enotez_list_notes_sep_dim
  }
  {
    \AssignTemplateKeys
    \enotez_set_totoc:
    \enotez_list_heading:n { \l__enotez_list_name_tl }
    \enotez_list_preamble:
    \enotez_build_print_list:nnnn {#1}
      {}
      {
        \par\noindent
        \group_begin:
          \tl_use:N \l__enotez_list_format_tl
%           \hbox_overlap_left:n
%             {
              \enotez_list_number:n
                { \enotez_write_list_number:n {##1} }
              \tl_use:N \c_space_tl
%             }
          % \cs_set:cpn {@currentlabel}
          %   { \p@endnote \l__enotez_endnote_mark_tl }
          \tl_use:N \g__enotez_endnote_text_tl
          \par
          \dim_compare:nT { \l__enotez_list_notes_sep_dim != 0pt }
            { \addvspace { \l__enotez_list_notes_sep_dim } }
        \group_end:
      }
      {}
    \enotez_list_postamble:
  }

\ExplSyntaxOff
```

For MathJax:

```
\begin{warpMathJax}
\def\endnotename{endnote}
\appto\LWR@syncnotenumbers{\LWR@synconenotenumber{LWRendnote}{\theendnote}}
\appto\LWR@syncnotenames{\LWR@synconenotename{LWRendnote}{\endnotename}}
\CustomizeMathJax{\def\LWRendnote{1}}
\CustomizeMathJax{\newcommand{\endnote}[2][\LWRendnote]{{}^{\mathrm{#1}}}}
\CustomizeMathJax{\newcommand{\endnotemark}[1][\LWRendnote]{{}^{\mathrm{#1}}}}
\end{warpMathJax}
```

File 131 **lwarp-enumerate.sty**

§ 239 Package enumerate

Pkg enumerate enumerate is supported with no changes.

This package is only required because it was used in the past to drop and then emulate the package. It cannot be removed because an older version which dropped the package may still remain, for example in a local vs. distribution directory, but it is now supported directly by lwarp and thus must no longer be dropped.

for HTML output:

```
\LWR@ProvidesPackagePass{enumerate}[2015/07/23]
```

File 132 **lwarp-enumitem.sty**

§ 240 Package enumitem

(*Emulates or patches code by* Javier Bezos.)

Pkg enumitem enumitem is supported with minor adjustments.

for HTML output:

```
\LWR@ProvidesPackagePass{enumitem}[2018/11/30]
```

\newlist {⟨*name*⟩} {⟨*type*⟩} {⟨*maxdepth*⟩}
\renewlist {⟨*name*⟩} {⟨*type*⟩} {⟨*maxdepth*⟩}

For enumitem lists, new lists must have the start and end actions assigned to the new environment. Renewed lists already have their actions assigned, and thus need no changes.

```
\let\LWR@enumitem@orignewlist\newlist

\renewcommand*{\newlist}[3]{%
\LWR@enumitem@orignewlist{#1}{#2}{#3}%
\AtBeginEnvironment{#1}{\@nameuse{LWR@#2start}}%
\AtEndEnvironment{#1}{\@nameuse{LWR@#2end}}%
}

\def\DrawEnumitemLabel{}
```

File 133 **lwarp-epigraph.sty**

§ 241 Package epigraph

(*Emulates or patches code by* Peter Wilson.)

Pkg epigraph epigraph is emulated for HTML, and used as-is for print output.

Use CSS to format epigraphs.

for HTML output:

```
\LWR@ProvidesPackagePass{epigraph}[2020/01/02]
```

```
\DeclareDocumentCommand{\LWR@HTML@qitem}{m m}
{%
    \begin{BlockClass}{qitem}%
    #1%
    \LWR@stoppars%
```

```
    \ifbool{FormatWP}%
        {\begin{BlockClass}[border-top:1px solid gray]{epigraphsource}}%
        {\begin{BlockClass}{epigraphsource}}%
    #2%
    \end{BlockClass}%
    \end{BlockClass}%
}
\LWR@formatted{qitem}
```

epigraph: Added ARIA role.

```
\DeclareDocumentCommand{\LWR@HTML@epigraph}{m m}
{%
   \begin{LWR@BlockClassWP}{\LWR@print@mbox{text-align:right}}{}(note){epigraph}%
    \qitem{#1}{#2}%
    \end{LWR@BlockClassWP}%
}
\LWR@formatted{epigraph}

\DeclareDocumentEnvironment{LWR@HTML@epigraphs}{}
    {\LWR@BlockClassWP{\LWR@print@mbox{text-align:right}}{}(note){epigraph}}%
    {\endLWR@BlockClassWP}
\LWR@formattedenv{epigraphs}
```

The following cannot be used in print mode while generating HTML:

```
\renewcommand{\epigraphhead}[2][0]{#2}
\renewcommand{\dropchapter}[1]{}
\renewcommand*{\undodrop}{}
```

File 134 **lwarp-epsf.sty**

§ 242 Package

epsf

(*Emulates or patches code by* Tom Rokicki.)

Pkg epsf epsf is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{epsf}% not date given

\xpretocmd{\epsfsetgraph}
    {\begin{lateximage}}
    {}
    {\LWR@patcherror{lwarp-epsf}{epsfsetgraph-begin}}

\xapptocmd{\epsfsetgraph}
    {\end{lateximage}}
    {}
    {\LWR@patcherror{lwarp-epsf}{epsfsetgraph-end}}
```

File 135 **lwarp-epsfig.sty**

§ 243 Package

epsfig

Pkg epsfig

epsfig is emulated for use by lwarp.

⚠ Only the LaTeX2e syntax is emulated.

for HTML output:

```
\LWR@ProvidesPackagePass{epsfig}[2017/06/25]
```

A few additional keys to capture the filename:

```
\RequirePackage{graphics}

\define@key{igraph}{file}{%
    \xdef\LWR@epsfig@filename{#1}%
}

\define@key{igraph}{figure}{%
    \xdef\LWR@epsfig@filename{#1}%
}

\define@key{igraph}{prolog}{}

\define@key{igraph}{silent}[]{}
```

The captured filename is used as the argument to `\includegraphics`:

```
\newcommand{\LWR@HTML@epsfig}[1]{\includegraphics[#1]{\LWR@epsfig@filename}}
\LWR@formatted{epsfig}

\newcommand{\LWR@HTML@psfig}[1]{\includegraphics[#1]{\LWR@epsfig@filename}}
\LWR@formatted{psfig}
```

File 136 **lwarp-epstopdf.sty**

§ 244 Package

epstopdf

Pkg epstopdf

Previous versions of lwarp had a nullfied version, but now epstopdf-base is supported. lwarp-epstopdf becomes a placeholder to overwrite previous versions.

See package epstopdf-base for details.

for HTML output:

```
\LWR@ProvidesPackagePass{epstopdf}[2020-01-24]
```

File 137 **lwarp-epstopdf-base.sty**

§ 245 Package

epstopdf-base

Pkg epstopdf-base

⚠ convert to .svg

Images with an .eps extension will be converted to .pdf. The HTML output uses the .svg version, so use

Enter ⇒ **lwarpmk pdftosvg <listofPDFfiles>**

to generate .svg versions.

for HTML output:

```
\LWR@ProvidesPackagePass{epstopdf-base}[2020-01-24]
```

Redefine to remember the image filename, replacing .pdf with .svg. Use the epstopdf print version inside a lateximage.

```
\newcommand*{\LWR@HTML@ETE@OrgGin@setfile}[3]{%
    \edef\LWR@tempone{#3}%
    \StrSubstitute{\LWR@tempone}{.pdf}{.svg}[\LWR@tempone]%
    \StrSubstitute{\LWR@tempone}{.PDF}{.SVG}[\LWR@tempone]%
    \xdef\LWR@parsedfilename{\LWR@tempone}%
}

\LWR@formatted{ETE@OrgGin@setfile}
```

\includegraphics in HTML mode redefines \Gin@setfile to be \LWR@HTML@Gin@setfile, which is now redirected to epstopdf's version:

```
\renewcommand*{\LWR@HTML@Gin@setfile}[3]{%
    \ETE@Gin@setfile{#1}{#2}{#3}%
}
```

Allow .eps images to be found if a suffix is not provided:

```
\AtBeginDocument{
\DeclareGraphicsExtensions{%
    .eps,.EPS,.svg,.SVG,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG%
}
\DeclareGraphicsRule{.svg}{svg}{.svg}{}
\DeclareGraphicsRule{.SVG}{svg}{.SVG}{}
}
```

Likewise when inside a lateximage:

```
\appto\LWR@restoreorigformatting{%
\DeclareGraphicsExtensions{%
    .eps,.EPS,.pdf,.PDF,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG%
}%
}
```

File 138 **lwarp-eqlist.sty**

§ 246 Package

eqlist

Pkg eqlist

eqlist is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{eqlist}[2002/08/15]
```

```
\newenvironment{eqlist}[1][]{\description}{\enddescription}
\newenvironment{eqlist*}[1][]{\description}{\enddescription}
\newenvironment{Eqlist}[2][]{\description}{\enddescription}
\newenvironment{Eqlist*}[2][]{\description}{\enddescription}
\newcommand*{\longitem}[1][]{\item[#1]}
\newcommand*{\eqlistinit}{}
\newcommand*{\eqliststarinit}{}
\newcommand*{\eqlistinitpar}{}
\def\eqlistlabel#1{#1}
\newcommand{\eqlistauto}[1]{}
\newcommand{\eqlistnoauto}{}
```

File 139 **lwarp-eqparbox.sty**

§ 247 Package

eqparbox

(*Emulates or patches code by* Scott Pakin.)

Pkg eqparbox eqparbox is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{eqparbox}[2017/09/03]

\NewDocumentCommand{\LWR@HTML@eqparbox}{O{t} O{} O{t} m +m}{%
    {%
        \minipagefullwidth%
        \parbox[#1][#2][#3]{\linewidth}{#5}%
    }%
}
\LWR@formatted{eqparbox}

\NewDocumentCommand{\LWR@HTML@eqmakebox}{o o m}{%
    \makebox[#2]{#3}%
}
\LWR@formatted{eqmakebox}

\NewDocumentCommand{\LWR@HTML@eqframebox}{o o m}{%
    \framebox[#2]{#3}%
}
\LWR@formatted{eqframebox}

\NewDocumentEnvironment{LWR@HTML@eqminipage}{O{t} O{} O{t} m}
{%
    \begingroup%
    \minipagefullwidth%
    \minipage[#1][#2][#3]{\linewidth}%
}%
{%
    \endminipage%
    \endgroup%
}

\newcommand*{\LWR@HTML@eqboxwidth}[1]{.25\linewidth}
\LWR@formatted{eqboxwidth}
```

```
\newcommand*{\LWR@HTML@eqsetminwidth}[2]{}
\newcommand*{\LWR@HTML@eqsetmaxwidth}[2]{}

\newcommand*{\LWR@HTML@eqsetminwidthto}[2]{}
\newcommand*{\LWR@HTML@eqsetmaxwidthto}[2]{}
```

File 140 **lwarp-errata.sty**

§ 248 Package

errata

(*Emulates or patches code by* Michael Kohlhase.)

Pkg errata errata is patched for use by lwarp.

This is for v0.3 of errata. A newer version of errata with more features is under development, at which time the lwarp version will have to be updated.

for HTML output: Macros are being defined with the math dollar, so enable the HTML version during package loading:

```
\StartDefiningMath
```

Now load the package:

```
\LWR@ProvidesPackagePass{errata}[2006/11/12]
```

Patches for dynamic inline math:

```
\xpatchcmd{\erratumAdd}
    {$_a^{\arabic{erratum}}$}
%     {\inlinemathother$_a^{\arabic{erratum}}$\inlinemathnormal}
    {\textsubscript{a}\textsuperscript{\arabic{erratum}}}
    {}
    {\LWR@patcherror{erratum}{erratumAdd}}

\xpatchcmd{\erratumDelete}
    {$_d^{\arabic{erratum}}$}
%     {\inlinemathother$_d^{\arabic{erratum}}$\inlinemathnormal}
    {\textsubscript{d}\textsuperscript{\arabic{erratum}}}
    {}
    {\LWR@patcherror{erratum}{erratumDelete}}

\xpatchcmd{\erratumReplace}
    {$_r^{\arabic{erratum}}$}
%     {\inlinemathother$_r^{\arabic{erratum}}$\inlinemathnormal}
    {\textsubscript{r}\textsuperscript{\arabic{erratum}}}
    {}
    {\LWR@patcherror{erratum}{erratumReplace}}

\xpatchcmd{\erratum}
    {$_a$}
%     {\inlinemathother$_a$\inlinemathnormal}
```

```
    {\textsubscript{a}}
    {}
    {\LWR@patcherror{erratum}{erratumDelete}}

\xpatchcmd{\erratum}
    {$_d^{\@thefnmark}$}
%     {\inlinemathother$_d^{\@thefnmark}$\inlinemathnormal}
    {\textsubscript{d}\textsuperscript{\@thefnmark}}
    {}
    {\LWR@patcherror{erratum}{eDelete}}

\xpatchcmd{\erratum}
    {$_r^{\@thefnmark}$}
%     {\inlinemathother$_r^{\@thefnmark}$\inlinemathnormal}
    {\textsubscript{r}\textsuperscript{\@thefnmark}}
    {}
    {\LWR@patcherror{erratum}{eReplace}}
```

Finish the current page's errata before closing and reloading the list:

```
\preto\PrintErrata{\LWR@maybe@orignewpage}
```

No longer defining math macros with the HTML $:

```
\StopDefiningMath
```

File 141 **lwarp-eso-pic.sty**

§ 249 Package

eso-pic

(*Emulates or patches code by* Rolf Niepraschk.)

Pkg eso-pic eso-pic is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{eso-pic}[2018/04/12]

\newcommand*{\LenToUnit}{}
\newcommand{\AtPageUpperLeft}[1]{}
\newcommand{\AtPageLowerLeft}[1]{}
\newcommand{\AtPageCenter}[1]{}
\newcommand{\AtStockLowerLeft}[1]{}
\newcommand{\AtStockUpperLeft}[1]{}
\newcommand{\AtStockCenter}[1]{}
\newcommand{\AtTextUpperLeft}[1]{}
\newcommand{\AtTextLowerLeft}[1]{}
\newcommand{\AtTextCenter}[1]{}
\NewDocumentCommand{\AddToShipoutPictureBG}{s +m}{}

\newcommand{\AddToShipoutPicture}{\AddToShipoutPictureBG}
\NewDocumentCommand{\AddToShipoutPictureFG}{s +m}{}
\newcommand*{\ClearShipoutPictureBG}{}
\newcommand*{\ClearShipoutPicture}{}
```

```
\newcommand*{\ClearShipoutPictureFG}{}
\newcommand{\gridSetup}[6][]{}
```

File 142 **lwarp-esvect.sty**

§ 250 Package

esvect

(*Emulates or patches code by* Eddie Saudrais.)

Pkg esvect esvect is used as-is for SVG math, and emulated for MathJax.

for HTML output:

```
\LWR@ProvidesPackagePass{esvect}% no date given

\begin{warpMathJax}
\CustomizeMathJax{\newcommand{\LWResvectvv}[1]{\overrightarrow{#1}}}
\CustomizeMathJax{\newcommand{\LWResvectvvstar}[2]{\overrightarrow{#1}\!_{#2}}}
\CustomizeMathJax{\newcommand{\vv}{\ifstar\LWResvectvvstar\LWResvectvv}}
\end{warpMathJax}
```

File 143 **lwarp-etoc.sty**

§ 251 Package

etoc

Pkg etoc etoc is ignored. All commands are nullified.

⚠ \tableofcontents with \ref

The etoc package uses a non-standard syntax which looks ahead after a `\tableofcontents` for a following `\ref`. These `\ref`s appear in the HTML result unless they are removed. Where a `\tableofcontents` is followed by `\ref`, and perhaps also `\label` as well, enclose all of them inside `\warpprintonly`:

```
\warpprintonly{\tableofcontents \ref{toc:abc} \label{toc:def}}
```

or place all code related to a local `\tableofcontents` inside a `warpprint` environment.

⚠ home page

Be sure to keep the initial `\tableofcontents` on the home page, perhaps in its own `\warpHTMLonly` macro or `warpHTML` environment.

for HTML output:

```
\LWR@ProvidesPackageDrop{etoc}[2019/11/17]

\def\etocsetlevel#1#2{}
\def\etocskipfirstprefix{}
\let\etocthename   \@empty
\let\etocthenumber \@empty
\let\etocthepage   \@empty
\let\etocthelinkedname   \@empty
\let\etocthelinkednumber \@empty
\let\etocthelinkedpage   \@empty
\let\etocthelink   \@firstofone % prior to 1.08j its was \let to \@empty
\DeclareRobustCommand*{\etocname}  {}
\DeclareRobustCommand*{\etocnumber}{}
```

```
\DeclareRobustCommand*{\etocpage}  {}
\DeclareRobustCommand*{\etoclink}  {\@firstofone}
\DeclareRobustCommand*{\etocifnumbered}{\@firstoftwo}
\DeclareRobustCommand*{\etociffirst}{\@firstoftwo}
\DeclareRobustCommand*\etocifwasempty{\@firstoftwo}
\let\etocaftertitlehook    \@empty
\let\etocaftercontentshook \@empty
\def\etoctableofcontents{}
\newcommand*\localtableofcontents{}
\newcommand*\localtableofcontentswithrelativedepth[1]{}
\newcommand\etocsettocstyle[2]{}
\long\def\etocsetstyle#1#2#3#4#5{}
\def\etocfontminustwo {\normalfont \LARGE \bfseries}
\def\etocfontminusone {\normalfont \large \bfseries}
\def\etocfontzero     {\normalfont \large \bfseries}
\def\etocfontone      {\normalfont \normalsize \bfseries}
\def\etocfonttwo      {\normalfont \normalsize}
\def\etocfontthree    {\normalfont \footnotesize}
\def\etocsepminustwo  {4ex \@plus .5ex \@minus .5ex}
\def\etocsepminusone  {4ex \@plus .5ex \@minus .5ex}
\def\etocsepzero      {2.5ex \@plus .4ex \@minus .4ex}
\def\etocsepone       {1.5ex \@plus .3ex \@minus .3ex}
\def\etocseptwo       {.5ex \@plus .1ex \@minus .1ex}
\def\etocsepthree     {.25ex \@plus .05ex \@minus .05ex}
\def\etocbaselinespreadminustwo {1}
\def\etocbaselinespreadminusone {1}
\def\etocbaselinespreadzero     {1}
\def\etocbaselinespreadone      {1}
\def\etocbaselinespreadtwo      {1}
\def\etocbaselinespreadthree    {.9}
\def\etocminustwoleftmargin  {1.5em plus 0.5fil}
\def\etocminustworightmargin {1.5em plus -0.5fil}
\def\etocminusoneleftmargin  {1em}
\def\etocminusonerightmargin {1em}
\def\etoctoclineleaders
        {\hbox{\normalfont\normalsize\hb@xt@2ex {\hss.\hss}}}
\def\etocabbrevpagename {p.~}
\def\etocpartname       {Part}% modified 1.08b
\def\etocbookname       {Book}
\def\etocdefaultlines{}
\def\etocabovetocskip{3.5ex \@plus 1ex \@minus .2ex}
\def\etocbelowtocskip{3.5ex \@plus 1ex \@minus .2ex}
\def\etoccolumnsep{2em}
\def\etocmulticolsep{0ex}
\def\etocmulticolpretolerance{-1}
\def\etocmulticoltolerance{200}
\def\etocdefaultnbcol{2}
\def\etocinnertopsep{2ex}
\newcommand\etocmulticolstyle[2][]{}
\def\etocinnerbottomsep{3.5ex}
\def\etocinnerleftsep{2em}
\def\etocinnerrightsep{2em}
\def\etoctoprule{\hrule}
\def\etocleftrule{\vrule}
\def\etocrightrule{\vrule}
```

```
\def\etocbottomrule{\hrule}
\def\etoctoprulecolorcmd{\relax}
\def\etocbottomrulecolorcmd{\relax}
\def\etocleftrulecolorcmd{\relax}
\def\etocrightrulecolorcmd{\relax}
\newcommand*\etocruledstyle[2][]{}
\def\etocframedmphook{\relax}
\long\def\etocbkgcolorcmd{\relax}
\newcommand*\etocframedstyle[2][]{}
\def\etocmulticol{}
\def\etocruled{}
\def\etocframed{}
\def\etoclocalmulticol{}
\def\etoclocalruled{}
\def\etoclocalframed{}
\def\etocarticlestyle{}
\def\etocarticlestylenomarks{}
\def\etocbookstyle{}
\def\etocbookstylenomarks{}
\let\etocreportstyle\etocbookstyle
\let\etocreportstylenomarks\etocbookstylenomarks
\def\etocmemoirtoctotocfmt #1#2{}
\def\etocmemoirstyle{}
\def\etocscrartclstyle{}
\let\etocscrbookstyle\etocscrartclstyle
\let\etocscrreprtstyle\etocscrartclstyle
\def\etocstandarddisplaystyle{\etocarticlestyle}
\newcommand*\etocmarkboth[1]{}
\newcommand*\etocmarkbothnouc[1]{}
\newcommand\etoctocstyle[3][section]{}
\newcommand\etoctocstylewithmarks[4][section]{}
\newcommand\etoctocstylewithmarksnouc[4][section]{}
\def\etocignoretoctocdepth{}
\def\etocsettocdepth[1]{}
\def\etocdepthtag   #1#{\Etoc@depthtag }
\def\Etoc@depthtag  #1{}
\def\etocignoredepthtags {}
\def\etocobeydepthtags   {}
\def\etocsettagdepth #1#2{}
\def\invisibletableofcontents {}
\def\invisiblelocaltableofcontents{}
\def\etocsetnexttocdepth #1{}
\def\etocsetlocaltop #1#{\Etoc@set@localtop}
\def\Etoc@set@localtop #1{}
\def\etocstandardlines {}
\def\etoctoclines      {}
\let\etocaftertochook    \@empty
\let\etocbeforetitlehook \@empty
\appto\tableofcontents{\def\tableofcontents{}}
```

File 144 **lwarp-eurosym.sty**

§ 252 Package eurosym

(*Emulates or patches code by* Henrik Theiling.)

Pkg eurosym eurosym is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{eurosym}[1998/08/06]

\renewrobustcmd\officialeuro{\HTMLentity{euro}}
\let\geneuro\officialeuro
\let\geneuronarrow\officialeuro
\let\geneurowide\officialeuro
\let\euro\officialeuro
\renewrobustcmd\eurobars{}
\renewrobustcmd\eurobarsnarrow{}
\renewrobustcmd\eurobarswide{}
```

File 145 **lwarp-everypage.sty**

§ 253 Package everypage

(*Emulates or patches code by* Sergio Callegari.)

Pkg everypage everypage is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{everypage}[2007/06/20]

\newcommand*{\AddEverypageHook}[1]{}
\newcommand*{\AddThispageHook}[1]{}
```

File 146 **lwarp-everyshi.sty**

§ 254 Package everyshi

(*Emulates or patches code by* Martin Schröder.)

Pkg everyshi ignored.

for HTML output: Discard all options for lwarp-everyshi:

```
\LWR@ProvidesPackageDrop{everyshi}[2001/05/15]

\let\EveryShipout\relax
\newcommand*{\EveryShipout}[1]{}

\let\AtNextShipout\relax
\newcommand*{\AtNextShipout}[1]{}
```

File 147 **lwarp-extarrows.sty**

§ 255 Package extarrows

(*Emulates or patches code by* Huynh Ky Anh.)

Pkg extarrows extarrows is used as-is for SVG math, and emulted for MathJax.

for HTML output:

```
\LWR@ProvidesPackagePass{extarrows}[2008/05/15]

\begin{warpMathJax}
\CustomizeMathJax{\Newextarrow\xLongleftarrow{10,10}{0x21D0}}
\CustomizeMathJax{\Newextarrow\xLongrightarrow{10,10}{0x21D2}}
\CustomizeMathJax{\Newextarrow\xLongleftrightarrow{10,10}{0x21D4}}
\CustomizeMathJax{\Newextarrow\xLeftrightarrow{10,10}{0x21D4}}
\CustomizeMathJax{\Newextarrow\xlongleftrightarrow{10,10}{0x2194}}
\CustomizeMathJax{\Newextarrow\xleftrightarrow{10,10}{0x2194}}
\CustomizeMathJax{\let\xlongleftarrow\xleftarrow}
\CustomizeMathJax{\let\xlongrightarrow\xrightarrow}
\end{warpMathJax}
```

File 148 **lwarp-extramarks.sty**

§ 256 Package extramarks

(*Emulates or patches code by* Piet van Oostrum.)

Pkg extramarks extramarks is ignored.

for HTML output: Discard all options for lwarp-extramarks:

```
\LWR@ProvidesPackageDrop{extramarks}[2019/01/31]

\newcommand*{\extramarks}[2]{}
\newcommand*{\firstleftxmark}{}
\newcommand*{\lastleftxmark}{}
\newcommand*{\firstrightxmark}{}
\newcommand*{\lastrightxmark}{}
\newcommand*{\firstxmark}{}
\newcommand*{\lastxmark}{}
\newcommand*{\topxmark}{}
\newcommand*{\topleftxmark}{}
\newcommand*{\toprightxmark}{}
\newcommand*{\firstleftmark}{}
\newcommand*{\lastrightmark}{}
\newcommand*{\firstrightmark}{}
\newcommand*{\lastleftmark}{}
```

File 149 **lwarp-fancybox.sty**

§ 257 Package fancybox

(*Emulates or patches code by* Timothy Van Zandt.)

Pkg fancybox

fancybox is supported with some patches.

framed equation example

fancybox's documentation has an example FramedEqn environment which combines math, \Sbox, a minipage, and an \fbox. This combination requires that the entire environment be enclosed inside a lateximage, which is done by adding \lateximage at the very start of FramedEqn's beginning code, and \endlateximage at the very end of the ending code. Unfortunately, the HTML alt attribute is not used here.

```
\newenvironmentFramedEqn
{
\lateximage% NEW
\setlength{\fboxsep}{15pt}
. . . }{. . .
\[\fbox{\TheSbox}\]
\endlateximage% NEW
}
```

framing alternatives

\fbox works with fancybox. Also see lwarp's \fboxBlock macro and fminipage environment for alternatives to \fbox for framing environments.

framed table example

The fancybox documentation's example of a framed table using an \fbox containing a tabular does not work with lwarp, but the FramedTable environment does work if \fbox is replaced by \fboxBlock. This method does lose some HTML formatting. A better method is to enclose the table's contents inside a fminipage environment. The caption may be placed either inside or outside the fminipage:

```
\begin{table}
\begin{fminipage}{\linewidth}
\begin{tabular}{lr}
. . .
\end{tabular}
\end{fminipage}
\end{table}
```

⚠ framed verbatim

lwarp does not support the verbatim environment inside a span, box, or fancybox's \Sbox, but a verbatim may be placed inside a fminipage. The fancybox documentation's example FramedVerb may be defined as:

```
\newenvironment{FramedVerb}[1] % width
{
  \VerbatimEnvironment
  \fminipage{#1}
  \beginVerbatim
}{
  \endVerbatim
  \endfminipage
}
```

framed \VerbBox

fancybox's \VerbBox may be used inside \fbox.

indented alignment

LVerbatim, \LVerbatimInput, and \LUseVerbatim indent with horizontal space which may not line up exactly with what *pdftotext* detects. Some lines may be off slightly in their left edge.

fancybox, fancyvrb
⚠ \VerbatimFootnotes
⚠ sectioning or displaymath

If using fancybox or fancyvrb with \VerbatimFootnotes, and using footnotes in a sectioning command or display math, use \footnotemark and \footnotetext:

```
\subsection[Subsection Name]
    {Subsection Name\protect\footnotemark}
\footnotetext{A footnote with \verb+verbtim+.}
```

and likewise for equations or display math.

At present there is a bug such that paragraph closing tags are not present in footnotes when \VerbatimFootnotes are selected. The browser usually compensates.

```
\LWR@ProvidesPackagePass{fancybox}[2010/05/15]
```

After the preamble is loaded, after any patches to Verbatim:

```
\AfterEndPreamble{
\LWR@traceinfo{Patching fancybox.}
```

\VerbatimFootnotes

Patched to use the new version.

```
\def\VerbatimFootnotes{%
\let\@footnotetext\V@footnotetext%
\let\LWR@footnotetext\V@footnotetext% lwarp
}
```

\V@@footnotetext

Patches in a subset of lwarp's \LWR@footnotetext to the fancyvrb version of \V@@footnotetext.

```
\def\V@@footnotetext{%
\LWR@traceinfo{V@footnotetext}%
```

Place an autopage marker so that back references to citations inside a footnote will link closer to the footnote text, if possible.

```
\LWR@newautopagelabel{page}%
```

Take the current footnote box, then append:

```
\global\setbox\LWR@footnotebox=\vbox\bgroup%
```

Add to any current footnotes:

```
    \unvbox\LWR@footnotebox%
```

Remember the footnote number for \ref:

```
    \protected@edef\@currentlabel{%
        \csname p@footnote\endcsname\@thefnmark%
    }% @currentlabel
```

Use HTML superscripts in the footnote even inside a lateximage:

```
    \renewrobustcmd{\textsuperscript}[1]{\LWR@htmlspan{sup}{##1}}%
```

Use paragraph tags if in a tabular data cell or a lateximage:

```
    \ifthenelse{%
        \boolean{LWR@doingstartpars} \AND%
```

```
        \cnttest{\value{LWR@lateximagedepth}}{=}{0}%
    }%
        {}%
        {\LWR@htmltagc{\LWR@tagregularparagraph}\LWR@orignewline}%
```

Append the footnote to the list:

```
    \@makefntext{}%
```

The footnote text will follow after `\V@@@footnotetext` has completed.

```
  \bgroup%
  \aftergroup{\V@@@footnotetext}%
```

Do not generate autopages inside the footnotes, since they are accumulated at the moment before finally being used perhaps on a later page.

```
    \let\LWR@newautopagelabel\LWR@null@newautopagelabel%
  \ignorespaces%
}%

}% AfterEndPreamble

\renewcommand*{\@shadowbox}[1]{%
\ifbool{FormatWP}%
{\InlineClass[border:1px solid black]{shadowbox}{#1}}%
{\InlineClass{shadowbox}{#1}}%
}

\renewcommand*{\@doublebox}[1]{%
\ifbool{FormatWP}%
{\InlineClass[border:1px double black]{doublebox}{#1}}%
{\InlineClass{doublebox}{#1}}%
}

\renewcommand*{\@ovalbox}[2]{%
\ifbool{FormatWP}%
{\InlineClass[border:1px solid black; border-radius:1ex]{ovalbox}{#2}}%
{%
    \ifthenelse{\isequivalentto{#1}{\thinlines}}%
        {\InlineClass{ovalbox}{#2}}%
        {\InlineClass{Ovalbox}{#2}}%
}%
}
```

Convert minipages, parboxes, and lists into linear text using the `LWR@nestspan` environment:

```
\let\LWR@origSbox\Sbox

\def\Sbox{\LWR@origSbox\LWR@nestspan}


\let\LWR@origendSbox\endSbox

\def\endSbox{\endLWR@nestspan\LWR@origendSbox}
```

`Beqnarray` is adapted for MathJax or enclosed inside a `latexmage`:

```
\RenewEnviron{Beqnarray}
{\LWR@eqnarrayfactor}

\csgpreto{Beqnarray*}{\boolfalse{LWR@numbereqnarray}}
```

`\GenericCaption` is enclosed in an HTML block:

```
\renewcommand{\GenericCaption}[1]{%
\LWR@figcaption%
\LWR@isolate{#1}%
\endLWR@figcaption%
}
```

`Btrivlist` is enclosed in an HTML block. This is a tabular, and does not use `\item`.

`\trivlist` {⟨*l/c/r*⟩} [⟨*t/c/b*⟩]

```
\RenewDocumentEnvironment{Btrivlist}{m o}
{%
    \LWR@stoppars%
    \begin{BlockClass}{Btrivlist}%
    \tabular{#1}%
}
{%
    \endtabular%
    \end{BlockClass}%
    \LWR@startpars%
}
```

`Btrivlist` is also neutralized when used inside a span:

```
\AtBeginEnvironment{LWR@nestspan}{%
\RenewDocumentEnvironment{Btrivlist}{m o}{}{}%
}
```

lwarp's handling of `\item` is patched to accept fancybox's optional arguments:

```
\let\LWRFB@origitemizeitem\LWR@itemizeitem
\let\LWRFB@origdescitem\LWR@descitem

\RenewDocumentCommand{\LWR@itemizeitem}{d()o}{%
    \IfValueTF{#2}{%
        \LWRFB@origitemizeitem[#2]%
    }{%
        \LWRFB@origitemizeitem%
    }%
}

\RenewDocumentCommand{\LWR@descitem}{d()o}{%
    \IfValueTF{#2}{%
        \LWRFB@origdescitem[#2]~%
    }{%
```

```
        \LWRFB@origdescitem%
    }%
}

\RenewDocumentCommand{\LWR@nestspanitem}{d()}{%
\if@newlist\else{\LWR@htmltagc{br /}}\fi%
\LWR@origitem%
}
```

The various boxed lists become regular lists:

```
\renewenvironment{Bitemize}[1][]{\begin{itemize}}{\end{itemize}}
\renewenvironment{Benumerate}[1][]{\begin{enumerate}}{\end{enumerate}}
\renewenvironment{Bdescription}[1][]{\begin{description}}{\end{description}}
```

\boxput simply prints one then the other argument, side-by-side instead of above and behind:

```
\RenewDocumentCommand{\boxput}{s d() m m}{%
\IfBooleanTF{#1}{#3\quad#4}{#4\quad#3}%
}
```

Neutralized commands:

```
\RenewDocumentCommand{\fancyput}{s d() m}{}
\RenewDocumentCommand{\thisfancyput}{s d() m}{}

\RenewDocumentCommand{\fancypage}{m m}{}
\RenewDocumentCommand{\thisfancypage}{m m}{}

\def\LandScape#1{}
\def\endLandScape{}
\def\@Landscape#1#2#3{}
\def\endLandscape{}
```

Low-level patches for UseVerbatim and friends:

```
\let\LWRFB@UseVerbatim\UseVerbatim
\renewcommand*{\UseVerbatim}[1]{%
\LWR@atbeginverbatim{Verbatim}%
\LWRFB@UseVerbatim{#1}%
\LWR@afterendverbatim%
}

\let\LWRFB@LUseVerbatim\LUseVerbatim

\renewcommand*{\LUseVerbatim}[1]{%
\LWR@atbeginverbatim{LVerbatim}%
\noindent%
\LWRFB@LUseVerbatim{#1}%
\LWR@afterendverbatim%
}

```

```
\def\@BUseVerbatim[#1]#2{%
\LWR@atbeginverbatim{BVerbatim}%
\LWRFB@UseVerbatim{#2}%
\LWR@afterendverbatim%
}
```

File 150 **lwarp-fancyhdr.sty**

§ 258 Package

fancyhdr

(*Emulates or patches code by* Piet van Oostrum.)

Pkg fancyhdr fancyhdr is ignored.

for HTML output: Discard all options for lwarp-fancyhdr:

```
\LWR@ProvidesPackageDrop{fancyhdr}[2021/01/04]

\newcommand*{\fancyhead}[2][]{}
\newcommand*{\fancyfoot}[2][]{}
\newcommand*{\fancyhf}[2][]{}

\newcommand*{\lhead}[2][]{}
\newcommand*{\chead}[2][]{}
\newcommand*{\rhead}[2][]{}
\newcommand*{\lfoot}[2][]{}
\newcommand*{\cfoot}[2][]{}
\newcommand*{\rfoot}[2][]{}
\newcommand*{\headrulewidth}{}
\newcommand*{\footrulewidth}{}
\providecommand{\headruleskip}{0pt}
\providecommand{\footruleskip}{0pt}
\newcommand{\plainheadrulewidth}{0pt}
\newcommand{\plainfootrulewidth}{0pt}
\def\fancyplain#1#2{#1}
\newcommand*{\headrule}{}
\newcommand*{\footrule}{}
\newlength{\headwidth}
\newcommand*{\fancycenter}[1][1em]{}
\newcommand*{\fancyheadoffset}[2][]{}
\newcommand*{\fancyfootoffset}[2][]{}
\newcommand*{\fancyhfoffset}[2][]{}
\newcommand{\fancyheadinit}[1]{}
\newcommand{\fancyfootinit}[1]{}
\newcommand{\fancyhfinit}[1]{}
\newcommand*{\iffloatpage}[2]{#2}
\newcommand*{\ifftopfloat}[2]{#2}
\newcommand*{\iffbotfloat}[2]{#2}
\newcommand*{\iffootnote}[2]{#2}

\newcommand{\fancypagestyle}[1]{%
  \@ifnextchar[{\f@nch@pagestyle{#1}}{\f@nch@pagestyle{#1}[]}%
}
\long\def\f@nch@pagestyle#1[#2]#3{}
```

File 151 **lwarp-fancypar.sty**

§ 259 Package

fancypar

(*Emulates or patches code by* Gonzalo Medina.)

Pkg fancypar

fancypar is used as-is for print output, and emulated for HTML.

⚠ css classes

\NotebookPar and related are used as-is inside a lateximage, but for HTML these are emulated as a of class NotebookPar, etc. For HTML, the package options and the macro optional arguments are ignored. The user must provide custom CSS for each if visual effects are required. See section 7.7.

⚠ custom styles

If using a custom paragraph style, such as \MyStylePar from the documentation, use the following to generate an HTML of class MyStylePar:

```
... (existing definiton of \MyStylePar, print version) ...
\begin{warpHTML}
\AddFancyparClass{MyStyle}
\end{warpHTML}
```

\MyStylePar is then modified to emulate HTML. An optional argument is allowed, which is ignored.

for HTML output:

```
\LWR@ProvidesPackagePass{fancypar}[2019/01/18]

\begin{warpHTML}
\makeatletter

\newcommand{\LWR@fancypar}[2]{%
    \begin{BlockClass}{#1Par}
    #2
    \end{BlockClass}
}

\newcommand{\LWR@HTML@NotebookPar}[2][]{\LWR@fancypar{Notebook}{#2}}
\LWR@formatted{NotebookPar}

\newcommand{\LWR@HTML@ZebraPar}[2][]{\LWR@fancypar{Zebra}{#2}}
\LWR@formatted{ZebraPar}

\newcommand{\LWR@HTML@DashedPar}[2][]{\LWR@fancypar{Dashed}{#2}}
\LWR@formatted{DashedPar}

\newcommand{\LWR@HTML@MarkedPar}[2][]{\LWR@fancypar{Marked}{#2}}
\LWR@formatted{MarkedPar}

\newcommand{\LWR@HTML@UnderlinedPar}[2][]{\LWR@fancypar{Underlined}{#2}}
\LWR@formatted{UnderlinedPar}

```

```
\newcommand{\LWR@HTML@add@fancy@format}{}
\LWR@formatted{add@fancy@format}


\newcommand{\AddFancyparClass}[1]{%
    \expandafter\newcommand\csname LWR@HTML@#1Par\endcsname[2][]{%
        \LWR@fancypar{#1}{##2}%
    }
    \LWR@formatted{#1Par}
}

\makeatother
\end{warpHTML}
```

File 152 **lwarp-fancyref.sty**

§ 260 Package

fancyref

(*Emulates or patches code by* Axel Reichert.)

Pkg fancyref fancyref is modifed for HTML output.

for HTML output:

```
\LWR@ProvidesPackagePass{fancyref}[1999/02/03]
```

To remove the `margin` option, if `\fancyrefhook` is anything other than the `paren` option, then force it to the default instead. (Comparing to the `margin` option was not possible since lwarp has revised the meaning of `\mbox` so the comparison failed.)

```
\newcommand*{\LWRfref@parenfancyrefhook}[1]{(#1)}

\ifdefstrequal{\fancyrefhook}{\LWRfref@parenfancyrefhook}
{}{
    \renewcommand*{\fancyrefhook}[1]{#1}%
}
```

File 153 **lwarp-fancytabs.sty**

§ 261 Package

fancytabs

Pkg fancytabs fancytabs is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{fancytabs}[2016/03/29]

\newcommand{\fancytab}[3][RIGHT]{}
\newcommand{\fancytabsStyle}[1]{}
\newcommand{\fancytabsHeight}[1]{}
\newcommand{\fancytabsWidth}[1]{}
\newcommand{\fancytabsCount}[1]{}
\newcommand{\fancytabsLeftColor}[1]{}
```

```
\newcommand{\fancytabsRightColor}[1]{}
\newcommand{\fancytabsTop}[1]{}
\newcommand{\fancytabsTextVPos}[1]{}
\newcommand{\fancytabsTextHPos}[1]{}
\newcommand{\fancytabsGap}[1]{}
\newcommand{\fancytabsFloor}[1]{}
\newcommand{\fancytabsRotate}[1]{}
```

File 154 **lwarp-fancyvrb.sty**

§ 262 Package

fancyvrb

(*Emulates or patches code by* Timothy Van Zandt.)

Pkg fancyvrb

fancyvrb is supported with some patches.

HTML classes

The fancy verbatim environment is placed inside a of class fancyvrb. The label is placed inside a of class fancyvrblabel. The verbatim text itself is placed inside a of class verbatim.

fancybox, fancyvrb
⚠ \VerbatimFootnotes
⚠ sectioning or displaymath

If using fancybox or fancyvrb with \VerbatimFootnotes, and using footnotes in a sectioning command or display math, use \footnotemark and \footnotetext:

```
\subsection[Subsection Name]
    {Subsection Name\protect\footnotemark}
\footnotetext{A footnote with \verb+verbtim+.}
```

and likewise for equations or display math.

At present there is a bug such that paragraph closing tags are not present in footnotes when \VerbatimFootnotes are selected. The browser usually compensates.

```
\AtBeginDocument{\RequirePackage{xcolor}}% for \convertcolorspec

\LWR@ProvidesPackagePass{fancyvrb}[2008/02/07]
```

Initial default patch for fancyvrb:

```
\fvset{frame=none}%
```

After the preamble is loaded, after any patches to Verbatim:

```
\AfterEndPreamble{
\LWR@traceinfo{Patching fancyvrb.}
```

\VerbatimFootnotes

Patched to use the new version.

```
\def\VerbatimFootnotes{%
\let\@footnotetext\V@footnotetext%
\let\footnote\V@footnote%
\let\LWR@footnotetext\V@footnotetext% lwarp
}
```

\V@@footnotetext Patches in a subset of lwarp's \LWR@footnotetext to the fancyvrb version of \V@@footnotetext.

```
\def\V@@footnotetext{%
\LWR@traceinfo{V@footnotetext}%
```

Place an autopage marker so that back references to citations inside a footnote will link closer to the footnote text, if possible.

```
\LWR@newautopagelabel{page}%
```

Take the current footnote box, then append:

```
\global\setbox\LWR@footnotebox=\vbox\bgroup%
```

Add to any current footnotes:

```
    \unvbox\LWR@footnotebox%
```

Remember the footnote number for \ref:

```
    \protected@edef\@currentlabel{%
        \csname p@footnote\endcsname\@thefnmark%
    }% @currentlabel
```

Use HTML superscripts in the footnote even inside a lateximage:

```
    \renewrobustcmd{\textsuperscript}[1]{\LWR@htmlspan{sup}{##1}}%
```

Use paragraph tags if in a tabular data cell or a lateximage:

```
    \ifthenelse{%
        \boolean{LWR@doingstartpars} \AND%
        \cnttest{\value{LWR@lateximagedepth}}{=}{0}%
    }%
        {}%
        {\LWR@htmltagc{\LWR@tagregularparagraph}\LWR@orignewline}%
```

Append the footnote mark to the list:

```
    \@makefntext{}%
```

The footnote text will follow after \V@@@footnotetext has completed.

```
  \bgroup%
  \aftergroup{\V@@@footnotetext}%
```

Do not generate autopages inside the footnotes, since they are accumulated at the moment before finally being used perhaps on a later page.

```
    \let\LWR@newautopagelabel\LWR@null@newautopagelabel%

  \ignorespaces%
}%

\preto\FVB@Verbatim{\LWR@forcenewpage}
\preto\FVB@LVerbatim{\LWR@forcenewpage}
% \preto\FVB@BVerbatim{\LWR@forcenewpage}% Fails, so done below.
```

Simplified to remove PDF formatting:

```
\def\FV@BeginListFrame@Single{%
```

```
  \FV@SingleFrameLine{\z@}%
}

\def\FV@EndListFrame@Single{%
  \FV@SingleFrameLine{\@ne}%
}

\def\FV@BeginListFrame@Lines{%
  \FV@SingleFrameLine{\z@}%
}

\def\FV@EndListFrame@Lines{%
    \FV@SingleFrameLine{\@ne}%
}

\renewcommand*{\FV@SingleFrameSep}{}
```

Adds HTML formatting:

```
\def\FV@BUseVerbatim#1{%
    \FV@BVerbatimBegin#1\FV@BVerbatimEnd%
}
```

`\LWR@FVstyle` Holds the style of the verbatim.

```
\newcommand*{\LWR@FVstyle}{}
```

The following patches to `Verbatim` are executed at the start and end of the environment, depending on the choice of `frame`. Original code is from the fancyvrb package.

```
\newcommand*{\LWR@fvstartnone}{%
\LWR@traceinfo{fvstartnone}%
% \hbox to\z@{
\BlockClass[\LWR@FVstyle]{fancyvrb}
\LWR@stoppars
\ifx\FV@LabelPositionTopLine\relax\else
    \ifx\FV@LabelBegin\relax\else
        \FancyVerbRuleColor{\LWR@FVfindbordercolor}
        \LWR@htmltagc{%
            div class=\textquotedbl{}fancyvrblabel\textquotedbl\ % space
           style=\textquotedbl{}color: \LWR@origpound\LWR@tempcolor\textquotedbl%
        }
        \LWR@print@textrm{\FV@LabelBegin}% \textrm preserves emdash
        \LWR@htmltagc{/div}\LWR@orignewline%
    \fi
\fi
\LWR@atbeginverbatim{verbatim}%
% }%
}

\newcommand*{\LWR@fvendnone}{%
\LWR@traceinfo{fvendnone}%
% \hbox to\z@{
\LWR@afterendverbatim%
```

```
\LWR@stoppars%
\ifx\FV@LabelPositionBottomLine\relax\else
    \ifx\FV@LabelEnd\relax\else
        \FancyVerbRuleColor{\LWR@FVfindbordercolor}
        \LWR@htmltagc{%
            div class=\textquotedbl{}fancyvrblabel\textquotedbl\ % space
           style=\textquotedbl{}color: \LWR@origpound\LWR@tempcolor\textquotedbl%
        }
        \LWR@print@textrm{\FV@LabelEnd}
        \LWR@htmltagc{/div}\LWR@orignewline%
    \fi
\fi
\endBlockClass
}

\newcommand*{\LWR@fvstartsingle}{%
\LWR@traceinfo{fvstartsingle}%
\LWR@fvstartnone%
\FV@BeginListFrame@Single%
}

\newcommand*{\LWR@fvendsingle}{%
\LWR@traceinfo{fvendsingle}%
\FV@EndListFrame@Single%
\LWR@fvendnone%
}

\newcommand*{\LWR@fvstartline}{%
\LWR@traceinfo{fvstartline}%
\LWR@fvstartnone%
% \setlength{\LWR@templengthone}{\baselineskip}%
\FV@BeginListFrame@Lines%
% \setlength{\baselineskip}{\LWR@templengthone}%
% \setlength{\baselineskip}{5pt}%
}

\newcommand*{\LWR@fvendline}{%
\LWR@traceinfo{fvendline}%
\FV@EndListFrame@Lines%
\LWR@fvendnone%
}
```

The following patches select the start/left/right/end behaviors depending on `frame`. Original code is from the fancyvrb package.

```
\newcommand*{\LWR@FVfindbordercolor}{%
\FancyVerbRuleColor%
\LWR@findcurrenttextcolor%
\color{black}%
}

% border width of \FV@FrameRule
\newcommand*{\LWR@FVborderstyle}[1]{%
padding#1: \strip@pt\dimexpr \FV@FrameSep\relax\relax pt ; % space
\LWR@FVfindbordercolor\LWR@indentHTMLtwo%
```

```
132 border#1: \strip@pt\dimexpr \FV@FrameRule\relax\relax pt % space
133 solid {\FancyVerbRuleColor{\LWR@origpound\LWR@tempcolor}} ; % space
134 }
135
136 \def\FV@Frame@none{%
137 \renewcommand*{\LWR@FVstyle}{\LWR@currenttextcolorstyle}%
138 \let\FV@BeginListFrame\LWR@fvstartnone%
139 \let\FV@LeftListFrame\relax%
140 \let\FV@RightListFrame\relax%
141 \let\FV@EndListFrame\LWR@fvendnone}
142
143 \FV@Frame@none% default values
144
145 \def\FV@Frame@single{%
146 \renewcommand*{\LWR@FVstyle}{%
147     \LWR@currenttextcolorstyle\LWR@indentHTMLtwo%
148     \LWR@FVborderstyle{}%
149 }%
150 \let\FV@BeginListFrame\LWR@fvstartsingle%
151 \let\FV@LeftListFrame\FV@LeftListFrame@Single%
152 \let\FV@RightListFrame\FV@RightListFrame@Single%
153 \let\FV@EndListFrame\LWR@fvendsingle}
154
155 \def\FV@Frame@lines{%
156 \renewcommand*{\LWR@FVstyle}{%
157     \LWR@currenttextcolorstyle\LWR@indentHTMLtwo%
158     \LWR@FVborderstyle{-top}%
159     \LWR@indentHTMLtwo%
160     \LWR@FVborderstyle{-bottom}%
161 }%
162 \let\FV@BeginListFrame\LWR@fvstartline%
163 \let\FV@LeftListFrame\relax%
164 \let\FV@RightListFrame\relax%
165 \let\FV@EndListFrame\LWR@fvendline}
166
167 \def\FV@Frame@topline{%
168 \renewcommand*{\LWR@FVstyle}{%
169     \LWR@currenttextcolorstyle\LWR@indentHTMLtwo%
170     \LWR@FVborderstyle{-top}%
171 }%
172 \let\FV@BeginListFrame\LWR@fvstartline%
173 \let\FV@LeftListFrame\relax%
174 \let\FV@RightListFrame\relax%
175 \let\FV@EndListFrame\LWR@fvendnone}
176
177 \def\FV@Frame@bottomline{%
178 \renewcommand*{\LWR@FVstyle}{%
179     \LWR@currenttextcolorstyle\LWR@indentHTMLtwo%
180     \LWR@FVborderstyle{-bottom}%
181 }%
182 \let\FV@BeginListFrame\LWR@fvstartnone%
183 \let\FV@LeftListFrame\relax%
184 \let\FV@RightListFrame\relax%
185 \let\FV@EndListFrame\LWR@fvendline}
```

Seems to be required in some situations:

```
\def\FV@FrameFillLine{}%

\def\FV@Frame@leftline{%
\renewcommand*{\LWR@FVstyle}{%
    \LWR@currenttextcolorstyle\LWR@indentHTMLtwo%
    \LWR@FVborderstyle{-left}%
}%
% To define the \FV@FrameFillLine macro (from \FV@BeginListFrame)
\ifx\FancyVerbFillColor\relax%
\let\FV@FrameFillLine\relax%
\else%
\@tempdima\FV@FrameRule\relax%
\multiply\@tempdima-\tw@%
\edef\FV@FrameFillLine{%
{\noexpand\FancyVerbFillColor{\vrule\@width\number\@tempdima sp}%
\kern-\number\@tempdima sp}}%
\fi%
\let\FV@BeginListFrame\LWR@fvstartnone%
\let\FV@LeftListFrame\FV@LeftListFrame@Single%
\let\FV@RightListFrame\relax%
\let\FV@EndListFrame\LWR@fvendnone}
```

Adds the optional label to the top and bottom edges. Original code is from the fancyvrb package.

```
\def\FV@SingleFrameLine#1{%
%   \hbox to\z@{%
%     \kern\leftmargin
    \ifnum#1=\z@\relax
      \let\FV@Label\FV@LabelBegin
    \else
      \let\FV@Label\FV@LabelEnd
    \fi
    \ifx\FV@Label\relax
%       \FancyVerbRuleColor{\vrule \@width\linewidth \@height\FV@FrameRule}%
    \else
      \ifnum#1=\z@
%         \setbox\z@\hbox{\strut\enspace\FV@LabelBegin\enspace\strut}%
        \ifx\FV@LabelPositionTopLine\relax
        \else
        \fi
      \else
%         \setbox\z@\hbox{\strut\enspace\FV@LabelEnd\enspace\strut}%
        \ifx\FV@LabelPositionBottomLine\relax
        \else
        \fi
      \fi
    \fi
%     \hss
%     }
}
```

Processes each line, adding optional line numbers. Original code is from the fancyvrb package.

```
\def\FV@ListProcessLine#1{%
   \hbox to \hsize{%
%      \kern\leftmargin
       \hbox to \VerbatimHTMLWidth {%
        \ifcsvoid{FV@LeftListNumber}{}{\kern 2.5em}%
         \FV@LeftListNumber%
%        \FV@LeftListFrame
       \FancyVerbFormatLine{#1}%
       \hss%
%        \FV@RightListFrame
       \FV@RightListNumber%
     }%
       \hss% required to avoid underfull hboxes
}
}

\def\FV@ListProcessLine@i#1{%
%   \hbox{%
    \ifvoid\@labels\else
      \hbox to \z@{\kern\@totalleftmargin\box\@labels\hss}%
    \fi
    \FV@ListProcessLine{#1}%
%   }%
%   \let\FV@ProcessLine\FV@ListProcessLine@ii%
}

\def\FV@ListProcessLastLine{}
```

Env BVerbatim

```

\xpretocmd{\FV@BeginVBox}
    {%
        \LWR@forcenewpage% instead of \preto
        \LWR@atbeginverbatim{bverbatim}%
    }
    {}
    {\LWR@patcherror{fancyvrb}{FV@BeginVBox}}

\xapptocmd{\FV@EndVBox}
    {%
        \LWR@afterendverbatim%
    }
    {}
    {\LWR@patcherror{fancyvrb}{FV@EndVBox}}
```

End of the modifications to make at the end of the preamble:

```
} % \AfterEndPreamble
```

File 155 **lwarp-fbox.sty**

§ 263 Package

fbox

(*Emulates or patches code by* Herbert Voss.)

Pkg fbox fbox is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{fbox}[2020/06/22]
```

This will be `\LWR@formatted` when `\AtBeginDocument`:

```
\LetLtxMacro\LWR@HTML@fbox\fbox
```

Instead of using the original, the new version is used with all borders:

```
\renewcommand*{\orig@fbox}{\FBox@i[tblr]}
```

`\WR@fboxpkg@border` {⟨*1: top/bottom/left/right*⟩} {⟨*2: padding, or empty*⟩}

Accumulates HTML styles for border, and padding if given:

```
\newcommand*{\LWR@fboxpkg@border}[2]{%
    \appto\LWR@tempone{%
        border-#1: % space
        \LWR@printlength{\LWR@atleastonept} % space
        solid \LWR@origpound\LWR@tempcolor ;\LWR@indentHTML
    }%
    \ifblank{#2}{}{%
        \appto\LWR@tempone{%
            padding-#1: \LWR@printlength{#2} ;\LWR@indentHTML
        }%
    }%
}
```

A hack to reuse the same code for inline and blocks:

```
\newbool{LWR@fboxpkg@ispar}
\boolfalse{LWR@fboxpkg@ispar}
```

Acculumate HTML styles for left and right padding, depending on `\if@fbox@space@left`, `\if@fbox@space@right`:

```
\newcommand{\LWR@fboxpkg@lrpadding}[1]{%
    \csuse{if@fbox@space@#1}%
        \appto\LWR@tempone{%
            padding-#1: \LWR@printlength{\fbox@@sep};\LWR@indentHTML
        }
    \else%
        \appto\LWR@tempone{%
            padding-#1: 0pt;\LWR@indentHTML
```

```
        }
    \fi%
}
```

The HTML version, modified to use HTML styles and either an `\InlineClass` or `BlockClass`:

```
\newcommand{\LWR@HTML@FBox@iii}[1]{%
```

Find and set the text color, rule width, margin:

```
    \LWR@forceminwidth{\fbox@@rule}%
    \LWR@findcurrenttextcolor%
    \def\LWR@tempone{%
        color: \LWR@origpound\LWR@tempcolor ; \LWR@indentHTML
        margin: 1ex ; \LWR@indentHTML
    }%
```

Add left/right padding:

```
    \LWR@fboxpkg@lrpadding{left}%
    \LWR@fboxpkg@lrpadding{right}%
```

Per the original to decode the borders, in a new way:

```
    \ifnum\the\@tempcntb>8\relax
        \advance\@tempcntb by -8
        \LWR@fboxpkg@border{top}{\fbox@@sep}%
    \fi
    \ifnum\@tempcntb>3
        \advance\@tempcntb by -4
        \LWR@fboxpkg@border{left}{}%
    \fi
    \ifnum\@tempcntb>1
        \LWR@fboxpkg@border{right}{}%
    \fi
    \ifodd\@tempcntb
        \LWR@fboxpkg@border{bottom}{\fbox@@sep}%
    \fi
```

Generate a `BlockClass` or `\InlineClass` with the contents:

```
    \color@begingroup
    \ifbool{LWR@fboxpkg@ispar}%
        {%
            \begin{BlockClass}[\LWR@tempone]{fboxpkg}%
                #1%
            \end{BlockClass}%
        }%
        {%
            \InlineClass[\LWR@tempone]{fboxpkg}{%
                #1%
            }%
        }%
    \color@endgroup
    \boolfalse{LWR@fboxpkg@ispar}% globally
```

```
}
\LWR@formatted{FBox@iii}
```

For `\fparbox`, set the use of `BlockClass`, then reuse the above:

```
\long\def\LWR@HTML@FParBox@i[#1]#2{%
    \booltrue{LWR@fboxpkg@ispar}%
    \FBox@i[#1]{#2}
}
\LWR@formatted{FParBox@i}

\long\def\LWR@HTML@FParBox@ii#1{%
    \booltrue{LWR@fboxpkg@ispar}%
    \FBox@i[tblr]{#1}%
}
\LWR@formatted{FParBox@ii}
```

For MathJax, absorb and ignore star and optional arguments:

```
\CustomizeMathJax{\let\LWRorigfbox\fbox}
\CustomizeMathJax{\newcommand{\LWRfboxpkgtwo}[2][]{\LWRorigfbox{#2}}}
\CustomizeMathJax{\renewcommand{\fbox}{\ifstar\LWRfboxpkgtwo\LWRfboxpkgtwo}}
\CustomizeMathJax{\newcommand{\fparbox}{\fbox}}
```

File 156 **lwarp-fewerfloatpages.sty**

§ 264 Package

fewerfloatpages

Pkg fewerfloatpages fewerfloatpages is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{fewerfloatpages}[2020/02/14]

\newcommand\floatpagekeepfraction{\textfraction}
\newcounter{floatpagedeferlimit}
\newcounter{floatpagekeeplimit}
```

File 157 **lwarp-figcaps.sty**

§ 265 Package

figcaps

(*Emulates or patches code by* Patrick W. Daly.)

Pkg figcaps figcaps is ignored.

for HTML output: Discard all options for lwarp-figcaps:

```
\LWR@ProvidesPackageDrop{figcaps}[1999/02/23]

\newcommand*{\figcapson}{}
\newcommand*{\figcapsoff}{}
```

```
\newcommand*{\printfigures}{}
\newcommand*{\figmarkon}{}
\newcommand*{\figmarkoff}{}
\def\figurecapname{Figure Captions}
\def\tablepagename{Tables}
\def\figurepagename{Figures}
```

File 158 **lwarp-figsize.sty**

§ 266 Package

figsize

(*Emulates or patches code by* Anthony A. Tanbakuchi.)

Pkg figsize figsize is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{figsize}[2002/03/18]
```

Emulates a virtual 6×9 inch textsize.

```
\newlength{\figwidth}
\newlength{\figheight}

\newcommand{\SetFigLayout}[3][0]{%
\setlength{\figheight}{8in}%
\setlength{\figheight}{\figheight / #2}%
%
\setlength{\figwidth}{5.5in}%
\setlength{\figwidth}{\figwidth / #3}%
}
```

File 159 **lwarp-fitbox.sty**

§ 267 Package

fitbox

Pkg fitbox fitbox is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{fitbox}[2019/02/20]

\NewDocumentCommand{\fitbox}{s o m}{%
    \begin{BlockClass}{fitbox}
    #3
    \end{BlockClass}
}

\newcommand*{\fitboxset}[1]{}

\newdimen\fitboxnatheight
\newdimen\fitboxnatwidth

\newcommand\SetFitboxLayout[3][]{}
```

File 160 **lwarp-fix2col.sty**

§ 268 Package

fix2col

Pkg fix2col fix2col is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{fix2col}[2015/11/13]
```

File 161 **lwarp-fixmath.sty**

§ 269 Package

fixmath

(*Emulates or patches code by* Walter Schmidt.)

Pkg fixmath fixmath is used as-is for SVG math, and emulated for MathJax.

⚠ limitations MathJax does not have full font support for bold italic Greek.

for HTML output:

```
1 \LWR@ProvidesPackagePass{fixmath}[2000/04/11]

2 \LWR@origRequirePackage{lwarp-common-mathjax-letters}
3
4 \begin{warpMathJax}
5 \LWR@mathjax@addgreek@u@it*{}{}
6 \LWR@mathjax@addletter{\BooleanTrue}{up}{}{delta}{0394}
7 \LWR@mathjax@addletter{\BooleanTrue}{up}{}{omega}{03A9}
8 \CustomizeMathJax{\newcommand{\mathbold}[1]{\boldsymbol{#1}}}
9 \end{warpMathJax}
```

File 162 **lwarp-fixme.sty**

§ 270 Package

fixme

(*Emulates or patches code by* Didier Verna.)

Pkg fixme fixme is patched for use by lwarp.

⚠ external layouts External layouts (`\fxloadlayouts`) are not supported.

Customized layouts are overwritten by lwarp's versions `\AtBeginDocument` in order to provide the HTML conversion. If creating a new layout, see lwarp's changes to provide similar for the new layout, inside a `warpHTML` environment.

User control is provided for setting the HTML styling of the "faces". The defaults are as follows, and may be changed in the preamble after fixme is loaded:

```
\def\FXFaceInlineHTMLStyle{font-weight:bold}
\def\FXFaceEnvHTMLStyle{font-weight:bold}
\def\FXFaceSignatureHTMLStyle{font-style:italic}
\def\FXFaceTargetHTMLStyle{font-style:italic}
```

for HTML output:

```
\LWR@ProvidesPackagePass{fixme}[2019/01/03]
```

Restore lwarp's version of `\@wrindex`, ignoring the fixme package's `target` option:

```
\let\@wrindex\LWR@wrindex
```

Float-related macros required by lwarp:

```
\newcommand{\ext@fixme}{lox}

\renewcommand{\l@fixme}[2]{%
    \hypertocfloat{1}{fixme}{lox}%
       {\LWR@nameref{\BaseJobname-autopage-\arabic{LWR@nextautopage}} --- #1}%
        {#2}
}
```

Other modifications. Done `\AtBeginDocument` to hopefully work if the user customizes the layouts.

```
\AtBeginDocument{

\def\FXFaceInlineHTMLStyle{font-weight:bold}

\renewcommand*\FXLayoutInline[3]{ % space
    \InlineClass[\FXFaceInlineHTMLStyle]{fixmeinline}%
        {\@fxtextstd{#1}{#2}{#3}}%
}

\def\FXFaceEnvHTMLStyle{font-weight:bold}

\renewcommand*\FXEnvLayoutPlainBegin[2]{%
    \BlockClass[\FXFaceEnvHTMLStyle]{fixmebold}
    \ignorespaces#2 \fxnotename{#1}: \ignorespaces%
}

\renewcommand*\FXEnvLayoutPlainEnd[2]{\endBlockClass}

\renewcommand*\FXEnvLayoutSignatureBegin[2]{%
    \BlockClass[\FXFaceEnvHTMLStyle]{fixmebold}
    \fxnotename{#1}: \ignorespaces%
}

\renewcommand*\FXEnvLayoutSignatureEnd[2]{\@fxsignature{#2}\endBlockClass}

\def\FXFaceSignatureHTMLStyle{font-style:italic}

\DeclareRobustCommand*\@fxsignature[1]{%
    \ifthenelse{\equal{#1}{}}%
        {}%
        { -- {\InlineClass[\FXFaceSignatureHTMLStyle]{fixmesignature}{#1}}}%
```

```
}


\def\FXFaceTargetHTMLStyle{font-style:italic}

\renewcommand\FXTargetLayoutPlain[2]{%
    \InlineClass[\FXFaceTargetHTMLStyle]{fixmetarget}{#2}%
}

}% \AtBeginDocument
```

File 163 **lwarp-fixmetodonotes.sty**

§ 271 Package fixmetodonotes

(*Emulates or patches code by* Gioele Barabucci.)

Pkg fixmetodonotes fixmetodonotes is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{fixmetodonotes}[2013/04/28]

\renewcommand{\NOTES@addtolist}[2]{%
    \refstepcounter{NOTES@note}%
%   \phantomsection% REMOVED
    \addcontentsline{notes}{NOTES@note}{%
        \protect\numberline{\theNOTES@note}{{#1}: {#2}}%
    }%
}

\renewcommand{\NOTES@marker}[2]{\fbox{%
    \textcolor{#2}{% WAS \color
        \textbf{#1}}%
    }}

\renewcommand{\NOTES@colorline}[2]{%
  \bgroup%
    \ULon{\LWR@backgroundcolor{#1}{#2}}%
}
```

File 164 **lwarp-flafter.sty**

§ 272 Package flafter

Pkg flafter flafter is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{flafter}[2018/01/08]
\providecommand\fl@trace[1]{}
```

File 165 **lwarp-flippdf.sty**

§ 273 Package

flippdf

Pkg flippdf flippdf is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{flippdf}[2006/06/30]

\newcommand\FlipPDF{}
\newcommand\UnFlipPDF{}
```

File 166 **lwarp-float.sty**

§ 274 Package

float

(*Emulates or patches code by* Anselm Lingnau.)

Pkg float float is emulated.

Float styles boxed and ruled are emulated by CSS and a float class according to style.

The HTML <figure> class is set to the float type, so CSS may also be used to format the float and its caption, according to float type. Furthermore, an additional class is set to the float style: plain, plaintop, boxed, or ruled, so CSS may be used to format by float style as well. Default formatting by CSS is provided for ruled and boxed styles.

⚠ not seem to be a floating environment

Always declare a \newfloat before modifying it with \floatname, etc.

for HTML output:

```
\LWR@ProvidesPackageDrop{float}[2001/11/08]
```

\LWR@floatstyle The default float style.

```
\newcommand*{\LWR@floatstyle}{plain}
```

\newfloat {⟨*1: type*⟩} {⟨*2: placement*⟩} {⟨*3: ext*⟩} [⟨*4: within*⟩]

Emulates the \newfloat command from the float package.

"placement" is ignored.

```
\NewDocumentCommand{\newfloat}{m m m o}{%
    \IfValueTF{#4}%
        {\DeclareFloatingEnvironment[fileext=#3,within=#4]{#1}}%
        {\DeclareFloatingEnvironment[fileext=#3]{#1}}%
```

Remember the float style:

```
    \csedef{LWR@floatstyle@#1}{\LWR@floatstyle}%
```

newfloat package automatically creates the \listof command for new floats, but float does not, so remove \listof here in case it is manually created later.

```
    \cslet{listof#1s}\relax%
    \cslet{listof#1es}\relax%
```

Likesize, newfloat also creates \l@<type>, but float does not, so remove it here:

```
    \cslet{l@#1}\relax%
}
```

\floatname {⟨*type*⟩} {⟨*name*⟩}

Sets the text name of the float, such as “Figure”. Avoids trying to set a recursive name, from trivfloat.

```
\NewDocumentCommand{\floatname}{m +m}{%
    \def\LWR@tempone{#2}%
    \def\LWR@temptwo{\@nameuse{#1name}}%
    \ifdefequal{\LWR@tempone}{\LWR@temptwo}{}{%
        \SetupFloatingEnvironment{#1}{name=#2}%
    }%
}
```

\floatplacement {⟨*type*⟩} {⟨*placement*⟩}

Float placement is ignored.

```
\newcommand*{\floatplacement}[2]{%
    \SetupFloatingEnvironment{#1}{placement=#2}%
}
```

\floatstyle {⟨*style*⟩}

Remember the style for future floats:

```
\newcommand{\floatstyle}[1]{%
    \def\LWR@floatstyle{#1}%
}%
```

\restylefloat * {⟨*type*⟩}

Remember the style for this float:

```
\NewDocumentCommand{\restylefloat}{s m}{%
    \csedef{LWR@floatstyle@#2}{\LWR@floatstyle}%
}
```

\listof See section 78.2 for the \LWR@listof command in the lwarp core.

```
\newcommand{\listof}{\LWR@listof}
```

File 167 **lwarp-floatflt.sty**

§ 275 Package

floatflt

(*Emulates or patches code by* Mats Dahlgren.)

Pkg floatflt floatflt is emulated.

for HTML output:

Discard all options for lwarp-floatflt:

```
\LWR@ProvidesPackageDrop{floatflt}[1997/07/16]
```

Env `[⟨⟩]` offset {⟨*type*⟩} {⟨*width*⟩} Borrowed from the lwarp version of keyfloat:

```
\NewDocumentEnvironment{KFLTfloatflt@marginfloat}{O{-1.2ex} m m}
{%
    \begin{LWR@setvirtualpage}*%
    \ifblank{#3}{%
        \LWR@BlockClassWP{%
            float:right; %
            width: 1.5in; % reasonable dummy width for word processor
            margin:10pt%
        }{}%
        (note)%
        {marginblock}%
    }{%
        \setlength{\LWR@templengthone}{#3}%
        \LWR@BlockClassWP{%
            float:right; %
            width:\LWR@printlength{\LWR@templengthone};  % extra space
            margin:10pt%
        }{%
            width:\LWR@printlength{\LWR@templengthone}%
        }%
        (note)%
        {marginblock}%
    }%
    \renewcommand*{\@captype}{#2}%
}
{%
    \endLWR@BlockClassWP%
    \end{LWR@setvirtualpage}%
}
```

Env floatingfigure `[⟨placement⟩] {⟨width⟩}`

```
\DeclareDocumentEnvironment{floatingfigure}{o m}
  {\begin{KFLTfloatflt@marginfloat}{figure}{#2}}
  {\end{KFLTfloatflt@marginfloat}}
```

Env floatingtable `[⟨placement⟩]`

```
\DeclareDocumentEnvironment{floatingtable}{o}
  {\begin{KFLTfloatflt@marginfloat}{table}{}}
  {\end{KFLTfloatflt@marginfloat}}
```

File 168 **lwarp-floatpag.sty**

§ 276 Package

floatpag

(*Emulates or patches code by* Vytas Statulevičius and Sigitas Tolušis.)

Pkg floatpag floatpag is ignored.

for HTML output: Discard all options for lwarp-floatpag:

```
\LWR@ProvidesPackageDrop{floatpag}[2012/05/29]

\newcommand*{\floatpagestyle}[1]{}
\newcommand*{\rotfloatpagestyle}[1]{}
\newcommand*{\thisfloatpagestyle}[1]{}
```

File 169 **lwarp-floatrow.sty**

§ 277 Package

floatrow

(*Emulates or patches code by* Olga Lapko.)

Pkg floatrow floatrow is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{floatrow}[2008/08/02]
```

⚠ Misplaced alignment tab character & Use `\StartDefiningTabulars` and `\StopDefiningTabulars` before and after defining macros using `\ttabbox` with a tabular inside. See section 8.10.1.

⚠ subfig package When combined with the subfig package, while inside a `subfloatrow` `\ffigbox` and `\ttabbox` must have the caption in the first of the two of the mandatory arguments.

⚠ `\FBwidth`, `\FBheight` The emulation of floatrow does not support `\FBwidth` or `\FBheight`. These values are pre-set to `.3\linewidth` and `2in`. Possible solutions include:

- Use fixed lengths. lwarp will scale the HTML lengths appropriately.
- Use `warpprint` and `warpHTML` environments to select appropriate values for each case.
- Inside a `warpHTML` environment, manually change `\FBwidth` or `\FBheight` before the `\ffigbox` or `\ttabbox`. Use `\FBwidth` or `\FBheight` normally afterwards; it will be used as expected in print output, and will use your custom-selected value in HTML output. This custom value will be used repeatedly, until it is manually changed to a new value.

After everything has loaded, remember whether subcaption was loaded. If not, it is assumed that subfig is used instead:

```

\newbool{LWR@subcaptionloaded}

\AtBeginDocument{
\@ifpackageloaded{subcaption}
    {\booltrue{LWR@subcaptionloaded}}
    {\boolfalse{LWR@subcaptionloaded}}
}
```

\floatbox [⟨*1 preamble*⟩] {⟨*2 captype*⟩} [⟨*3 width*⟩] [⟨*4 height*⟩] [⟨*5 vert pos*⟩] {⟨*6 caption*⟩} {⟨*7 object*⟩}

Only parameters for captype, width, caption, and object are used.

`LWR@insubfloatrow` is true if inside a `subfloatrow` environment.

There are two actions, depending on the use of subcaption or subfig.

```
\NewDocumentCommand{\floatbox}{o m o o o +m +m}{%
\ifbool{LWR@subcaptionloaded}%
{% subcaption
```

For subcaption:

```
    \ifbool{LWR@insubfloatrow}%
    {% subcaption in a subfloatrow
```

`subfigure` and `subtable` environments take width as an argument.

```
        \IfValueTF{#3}%
        {\@nameuse{sub#2}{#3}}%
        {\@nameuse{sub#2}{\linewidth}}%
    }% subcaption in a subfloatrow
    {% subcaption not in subfloatrow
```

`figure` and `table` environments do not take a width argument.

```
        \@nameuse{#2}%
    }% subcaption not in subfloatrow
    #6

    #7
```

End the environments:

```
    \ifbool{LWR@insubfloatrow}%
    {\@nameuse{endsub#2}}%
    {\@nameuse{end#2}}%
}% subcaption
{% assume subfig
```

For subfig:

```
\ifbool{LWR@insubfloatrow}%
{% subfig in a subfloatrow
```

`\subfloat` is a macro, not an environment.

Package subfig's `\subfloat` command takes an optional argument which is the caption, but `\floatbox` argument `#6` contains commands to create the caption and label, not the caption itself. Thus, `\caption` is temporarily disabled to return its own argument without braces.

```
    \begingroup
    \let\caption\@firstofone
    \subfloat[#6]{#7}
    \endgroup
}% subfig in a subfloatrow
{% subfig package, but not a subfig
```

`figure` and `table` are environments:

```
\@nameuse{#2}
#6

#7
\@nameuse{end#2}
}% subfig package, but not a subfig
}% assume subfig
}
```

Not used:

```
\newcommand*{\nocapbeside}{}
\newcommand*{\capbeside}{}
\newcommand*{\captop}{}
\newlength{\FBwidth}
\setlength{\FBwidth}{.3\linewidth}
\newlength{\FBheight}
\setlength{\FBheight}{2in}
\newcommand*{\useFCwidth}{}
\newcommand{\floatsetup}[2][]{}
\newcommand{\thisfloatsetup}[1]{}
\newcommand{\clearfloatsetup}[1]{}
\newcommand*{\killfloatstyle}{}
```

\newfloatcommand {⟨*1 command*⟩} {⟨*2 captype*⟩} [⟨*3 preamble*⟩] [⟨*4 default width*⟩]

Preamble and default width are ignored.

```
\NewDocumentCommand{\newfloatcommand}{m m o o}{%
\@namedef{#1}{
\floatbox{#2}
}
}
```

\renewfloatcommand {⟨*1 command*⟩} {⟨*2 captype*⟩} [⟨*3 preamble*⟩] [⟨*4 default width*⟩]

Preamble and default width are ignored.

```
\NewDocumentCommand{\renewfloatcommand}{m m o o}{%
\@namedef{#1}{%
\floatbox{#2}
}
}
```

\ffigbox [⟨*width*⟩] [⟨*height*⟩] [⟨*vposn*⟩] {⟨*caption commands*⟩} {⟨*contents*⟩}

```
\newfloatcommand{ffigbox}{figure}[\nocapbeside][]
```

\ttabbox [⟨*width*⟩] [⟨*height*⟩] [⟨*vposn*⟩] {⟨*caption commands*⟩} {⟨*contents*⟩}

```
\newfloatcommand{ttabbox}{table}[\captop][\FBwidth]
```

\fcapside [⟨*width*⟩] [⟨*height*⟩] [⟨*vposn*⟩] {⟨*caption commands*⟩} {⟨*contents*⟩}

```
\newfloatcommand{fcapside}{figure}[\capbeside][]
```

Env floatrow [⟨*numfloats*⟩]

The row of floats is placed into a of class floatrow.

```
\newenvironment*{floatrow}[1][2]
{%
    \begin{LWR@setvirtualpage}*%
    \BlockClass{floatrow}%
}
{
    \endBlockClass%
    \end{LWR@setvirtualpage}%
}
```

Keys for \DeclareNewFloatType:

```
\newcommand*{\LWR@frowkeyplacement}{}
\newcommand*{\LWR@frowkeyname}{}
\newcommand*{\LWR@frowkeyfileext}{}
\newcommand*{\LWR@frowkeywithin}{}
\newcommand*{\LWR@frowkeycapstyle}{}

\define@key{frowkeys}{placement}{}%
\define@key{frowkeys}{name}{\renewcommand{\LWR@frowkeyname}{#1}}%
\define@key{frowkeys}{fileext}{\renewcommand{\LWR@frowkeyfileext}{#1}}%
\define@key{frowkeys}{within}{\renewcommand{\LWR@frowkeywithin}{#1}}%
\define@key{frowkeys}{relatedcapstyle}{}%
```

\DeclareNewFloatType {⟨*type*⟩} {⟨*options*⟩}

Use \listof{type}{Title} to print a list of the floats.

```
\newcommand*{\DeclareNewFloatType}[2]{%
```

Reset key values:

```
\renewcommand*{\LWR@frowkeyplacement}{}%
\renewcommand*{\LWR@frowkeyname}{}%
\renewcommand*{\LWR@frowkeyfileext}{}%
\renewcommand*{\LWR@frowkeywithin}{}%
\renewcommand*{\LWR@frowkeycapstyle}{}%
```

Read new key values:

```
\LWR@traceinfo{about to setkeys frowkeys}%
\setkeys{frowkeys}{#2}%
\LWR@traceinfo{finished setkeys frowkeys}%
```

Create a new float with optional [within]:

```
\ifthenelse{\equal{\LWR@frowkeywithin}{}}%
{%
    \DeclareFloatingEnvironment[
        placement=\LWR@frowkeyplacement,
        fileext=\LWR@frowkeyfileext
    ]{#1}%
}%
{%
```

```
    \DeclareFloatingEnvironment[
        placement=\LWR@frowkeyplacement,
        fileext=\LWR@frowkeyfileext,
        within=\LWR@frowkeywithin
    ]{#1}%
%     \LWR@traceinfo{finished newfloat #1}%
}%
```

Rename the float if a name was given:

```
\ifthenelse{\equal{\LWR@frowkeyname}{}}%
    {}%
    {%
        \SetupFloatingEnvironment{#1}{name={\LWR@frowkeyname}}%
    }%
}
```

Not used:

```
\newcommand{\buildFBBOX}[2]{}
\newcommand*{\CenterFloatBoxes}{}
\newcommand*{\TopFloatBoxes}{}
\newcommand*{\BottomFloatBoxes}{}
\newcommand*{\PlainFloatBoxes}{}

\newcommand{\capsubrowsettings}{}

\NewDocumentCommand{\RawFloats}{o o}{}
```

`\RawCaption` `{`⟨*text*⟩`}`

To be used inside a minipage or parbox.

```
\newcommand{\RawCaption}[1]{#1}
```

`\floatfoot` `{`⟨*text*⟩`}`

Places additional text inside a float, inside a css `<div>` of class `floatfoot`.

```
\NewDocumentCommand{\floatfoot}{s +m}{%
    \begin{BlockClass}{floatfoot}
    #2
    \end{BlockClass}
}
```

Used to compute `\linewidth`.

```
\newbool{LWR@insubfloatrow}
\boolfalse{LWR@insubfloatrow}
```

Env `subfloatrow` `[`⟨*num_floats*⟩`]`

```
\newenvironment*{subfloatrow}[1][2]
{
```

The row of floats is placed into a `<div>` of class `floatrow`:

```
    \LWR@forcenewpage
    \BlockClass{floatrow}
```

While inside the floatrow, `LWR@insubfloatrow` is set true, which tells `\floatbox` to use `\subfigure` or `\subtable`.

```
    \begingroup%
    \booltrue{LWR@insubfloatrow}%
}
{%
    \endgroup%
    \endBlockClass%
    \boolfalse{LWR@insubfloatrow}%
}
```

File 170 **lwarp-fltrace.sty**

§ 278 Package

fltrace

Pkg fltrace fltrace is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{fltrace}[2018/01/08]

\def\tracefloats{}
\def\tracefloatsoff{}
\def\tracefloatvals{}
```

File 171 **lwarp-flushend.sty**

§ 279 Package

flushend

(*Emulates or patches code by* Sigitas Tolušis.)

Pkg flushend flushend is ignored.

for HTML output: Discard all options for lwarp-flushend:

```
\LWR@ProvidesPackageDrop{flushend}[2017/03/27]

\newcommand*{\flushend}{}
\newcommand*{\raggedend}{}
\newcommand*{\flushcolsend}{}
\newcommand*{\raggedcolsend}{}
\newcommand*{\atColsBreak}[1]{}
\newcommand*{\atColsEnd}[1]{}
\newcommand*{\showcolsendrule}{}
```

File 172 **lwarp-fnbreak.sty**

§ 280 Package

fnbreak

Pkg fnbreak fnbreak is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{fnbreak}[2012/01/01]

\newcommand*{\fnbreakverbose}{}
\newcommand*{\fnbreaknonverbose}{}
\newcommand*{\fnbreaklabel}{}
\newcommand*{\fnbreaknolabel}{}
```

File 173 **lwarp-fncychap.sty**

§ 281 Package

fncychap

(*Emulates or patches code by* Ulf A. Lindgren.)

Pkg fncychap fncychap is ignored.

for HTML output: Discard all options for lwarp-fncychap:

```
\LWR@ProvidesPackageDrop{fncychap}[2007/07/30]

\def\mghrulefill#1{}
\def\ChNameLowerCase{}
\def\ChNameUpperCase{}
\def\ChNameAsIs{}
\def\ChTitleLowerCase{}
\def\ChTitleUpperCase{}
\def\ChTitleAsIs{}
\newcommand{\ChRuleWidth}[1]{}
\newcommand{\ChNameVar}[1]{}
\newcommand{\ChNumVar}[1]{}
\newcommand{\ChTitleVar}[1]{}
\newcommand{\TheAlphaChapter}{}
\newcommand{\DOCH}{}
\newcommand{\DOTI}[1]{}
\newcommand{\DOTIS}[1]{}
\newlength{\mylen}
\newlength{\myhi}
\newlength{\px}
\newlength{\py}
\newlength{\pyy}
\newlength{\pxx}
\newlength{\RW}
\newcommand{\FmN}[1]{#1}
\newcommand{\FmTi}[1]{#1}
```

File 174 **lwarp-fnlineno.sty**

§ 282 Package

fnlineno

Pkg fnlineno

fnlineno is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{fnlineno}[2011/01/07]
```

File 175 **lwarp-fnpara.sty**

§ 283 Package

fnpara

Pkg fnpara

fnpara is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{fnpara}
```

File 176 **lwarp-fnpos.sty**

§ 284 Package

fnpos

(*Emulates or patches code by* Hiroshi Nakashima.)

Pkg fnpos

fnpos is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{fnpos}[1999/07/14]

\newcommand*{\makeFNbottom}{}
\newcommand*{\makeFNmid}{}
\newcommand*{\makeFNbelow}{}
\newcommand*{\makeFNabove}{}
```

File 177 **lwarp-fontawesome.sty**

§ 285 Package

fontawesome

(*Emulates or patches code by* Xavier Danaux.)

Pkg fontawesome

fontawesome is patched for use by lwarp.

Hashed inline images are used, as there may not be Unicode support for all icons.

⚠ *poppler* syntax warning

If using pdfLaTeX, *poppler* may issue a syntax warning regarding parsing a ligature component. XeLaTeX or LuaLaTeX may be used to avoid this warning.

In the following, the general strategy is to intercept `\symbol` and embed it inside a `lateximage`. These changes are done inside a local group.

For pdfLaTeX, the `alt` tag includes the icon (symbol) number. For XeLaTeX and LuaLaTeX, the `alt` tag is generic.

for HTML output:

```
\LWR@ProvidesPackagePass{fontawesome}[2016/05/15]
```

```
\LetLtxMacro\LWR@orig@symbol\symbol

\ifxetexorluatex

\newfontfamily{\LWR@orig@FA}{FontAwesome}

\newcommand*{\LWR@fontawesome@xelatex@symbol}[1]{%
    \LWR@findcurrenttextcolor%
   \begin{lateximage}*[icon][fontawesomexetex#1SZ\LWR@font@size{}CL\LWR@tempcolor]%
    \csuse{\LWR@font@size}%
    \LWR@orig@FA%
    \LWR@orig@symbol{#1}%
    \end{lateximage}%
}

\RenewDocumentCommand{\FA}{}{%
    \LetLtxMacro\symbol\LWR@fontawesome@xelatex@symbol%
}

\else

\newcommand*{\LWR@fontawesome@symbolX}[2]{%
    \LWR@findcurrenttextcolor%
   \begin{lateximage}*[icon #1][fontawesome#2#1SZ\LWR@font@size{}CL\LWR@tempcolor]%
    \csuse{\LWR@font@size}%
    \fontencoding{U}\fontfamily{fontawesome#2}\selectfont%
    \LWR@orig@symbol{#1}%
    \end{lateximage}%
}

\newcommand*{\LWR@fontawesome@symbolone}[1]{%
    \LWR@fontawesome@symbolX{#1}{one}%
}

\newcommand*{\LWR@fontawesome@symboltwo}[1]{%
    \LWR@fontawesome@symbolX{#1}{two}%
}

\newcommand*{\LWR@fontawesome@symbolthree}[1]{%
    \LWR@fontawesome@symbolX{#1}{three}%
}

\renewrobustcmd\FAone{%
    \LetLtxMacro\symbol\LWR@fontawesome@symbolone%
}

\renewrobustcmd\FAtwo{%
    \LetLtxMacro\symbol\LWR@fontawesome@symboltwo%
}

\renewrobustcmd\FAthree{%
    \LetLtxMacro\symbol\LWR@fontawesome@symbolthree%
}
\fi
```

File 178 **lwarp-fontawesome5.sty**

§ 286 Package

fontawesome5

(*Emulates or patches code by* Marcel Krüger.)

Pkg fontawesome5 fontawesome5 is patched for use by lwarp.

Hashed inline images are used, as there may not be Unicode support for all icons.

The `alt` tag has the name of the icon.

for HTML output:

```
\LWR@ProvidesPackagePass{fontawesome5}[2018/07/27]

\ExplSyntaxOn
\cs_set:Nn\fontawesome_use_icon:nn{
    \LWR@findcurrenttextcolor
  \cs_if_exist:cTF{c__fontawesome_slot_#2_tl}{
    \begin{lateximage}*[#2][fontawesome5#1SZ\LWR@font@size{}CL\LWR@tempcolor]
    \csuse{\LWR@font@size}
    \exp_last_unbraced:Nv
      \__fontawesome_icon_at:nnnn
      {c__fontawesome_slot_#2_tl}
        {#1}{#2}
    \end{lateximage}
  }{
    \msg_error:nnxx{fontawesome5}{icon-not-found}{#2}{#1}
  }
}
\ExplSyntaxOff
```

File 179 **lwarp-fontaxes.sty**

§ 287 Package

fontaxes

(*Emulates or patches code by* Andreas Bühmann, Michael Ummels.)

Pkg fontaxes fontaxes is emulated for HTML, and used as-is for print output.

Functionality for small caps is in the lwarp core. Swashes and figure styles are ignored for HTML.

for HTML output:

```
\LWR@ProvidesPackagePass{fontaxes}[2014/03/23]

\ifdef{\LWR@HTML@swshape}{}{% duplicated by nfssext-cfr
    \newcommand{\LWR@HTML@swshape}{}
    \LWR@formatted{swshape}

    \newrobustcmd{\LWR@HTML@textsw}[1]{#1}
```

```
    \LWR@formatted{textsw}

    \FilenameNullify{%
        \LetLtxMacro\swshape\@empty%
        \LetLtxMacro\textsw\firstofone%
    }
}
```

File 180 **lwarp-fontenc.sty**

§ 288 Package

fontenc

Pkg fontenc

If using pdfLaTeX, lwarp used to require fontenc be loaded before lwarp, but now lwarp itself loads `\fontenc` with T1 encoding, which lwarp requires. fontenc is now allowed to be loaded with another encoding after lwarp.

lwarp-fontenc is no longer necessary, but is still provided to overwrite older versions.

for HTML output:

```
\LWR@ProvidesPackagePass{fontenc}[2017/04/05]
```

File 181 **lwarp-footmisc.sty**

§ 289 Package

footmisc

(*Emulates or patches code by* Robin Fairbairns.)

Pkg footmisc

footmisc is emulated.

lwarp incidentally happens to emulate the `stable` option.

```
\LWR@ProvidesPackageDrop{footmisc}[2011/06/06]
```

Some nullified commands:

```
\newcommand{\footnotelayout}{}
\newcommand{\setfnsymbol}[1]{}
\NewDocumentCommand{\DefineFNsymbols}{s m o m}{}

\newdimen\footnotemargin
\footnotemargin1.8em\relax

\newcommand*\hangfootparskip{0.5\baselineskip}
\newcommand*\hangfootparindent{0em}%

\let\pagefootnoterule\footnoterule
\let\mpfootnoterule\footnoterule
\def\splitfootnoterule{\kern-3\p@ \hrule \kern2.6\p@}

\providecommand*{\multiplefootnotemarker}{3sp}
\providecommand*{\multfootsep}{,}
```

Using cleveref. `\labelcref` only prints the number of the object, not its type.

```
\providecommand*{\footref}[1]{\labelcref{#1}}
```

The following work as-is:

```
\newcommand\mpfootnotemark{%
  \@ifnextchar[%
    \@xmpfootnotemark%
    {%
      \stepcounter\@mpfn%
      \protected@xdef\@thefnmark{\thempfn}%
      \@footnotemark%
    }%
}
\def\@xmpfootnotemark[#1]{%
  \begingroup%
    \csname c@\@mpfn\endcsname #1\relax%
    \unrestored@protected@xdef\@thefnmark{\thempfn}%
  \endgroup%
  \@footnotemark%
}
```

File 182 **lwarp-footnote.sty**

§ 290 Package

footnote

(*Emulates or patches code by* Mark Wooding.)

Pkg footnote footnote is used with minor patches.

for HTML output:

```
\LWR@ProvidesPackagePass{footnote}[1997/01/28]
```

Removed print-version formatting:

```
\def\fn@startnote{%
%   \@parboxrestore%
  \protected@edef\@currentlabel{\csname p@\@mpfn\endcsname\@thefnmark}%
%   \color@begingroup% *** conflicts with lwarp
}

% \let\fn@endnote\color@endgroup% *** conflicts with lwarp
\def\fn@endnote{%
\LWR@htmltagc{/\LWR@tagregularparagraph}%
\LWR@orignewline%
}
```

Removed print-version formatting:

```
\def\fn@startfntext{%
  \setbox\z@\vbox\bgroup%
    \fn@startnote%
    \ignorespaces%
```

```
}
```

Removed print-version formatting, added closing paragraph tag:

```
\def\fn@endfntext{%
    \LWR@htmltagc{/\LWR@tagregularparagraph}%
    \LWR@orignewline%
  \egroup%
  \begingroup%
    \let\@makefntext\@empty%
    \let\@finalstrut\@gobble%
    \LetLtxMacro\rule\@gobbletwo% *8* also the optional argument?
    \@footnotetext{\unvbox\z@}%
  \endgroup%
}
```

These have been redefined, so re-`\let` them again:

```
\let\endfootnote\fn@endfntext
\let\endfootnotetext\endfootnote
```

File 183 **lwarp-footnotebackref.sty**

§ 291 Package

footnotebackref

Pkg footnotebackref

footnotebackref is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{footnotebackref}[2012/07/01]
```

File 184 **lwarp-footnotehyper.sty**

§ 292 Package

footnotehyper

Pkg footnotehyper

footnotehyper is a hyperref-safe version of footnote. For lwarp, footnotehyper is emulated.

for HTML output:

Discard all options for lwarp-footnotehyper:

```
\RequirePackage{footnote}
\LWR@ProvidesPackageDrop{footnotehyper}[2018/01/23]
```

File 185 **lwarp-footnoterange.sty**

§ 293 Package

footnoterange

(*Emulates or patches code by* H.-Martin Münch.)

Pkg footnoterange

footnoterange is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{footnoterange}[2012/02/17]

\csletcs{footnoterange}{footnoterange*}
\csletcs{endfootnoterange}{endfootnoterange*}
```

File 186 **lwarp-footnpag.sty**

§ 294 Package

footnpag

Pkg footnpag footnpag is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{footnpag}
```

File 187 **lwarp-foreign.sty**

§ 295 Package

foreign

(*Emulates or patches code by* Philip G. Ratcliffe.)

Pkg foreign foreign is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{foreign}[2012/09/25]

\renewcommand\foreignabbrfont{\emph}
```

File 188 **lwarp-forest.sty**

§ 296 Package

forest

(*Emulates or patches code by* Sašo Živanović.)

Pkg forest forest is patched for use by lwarp.

⚠ \Forest* The starred version of the macro \Forest* is not supported. lwarp encases each lateximage in an environment, so the global results of the starred \Forest* are lost.

for HTML output:

```
\LWR@ProvidesPackagePass{forest}[2017/07/14]

\BeforeBeginEnvironment{forest}{%
    \begin{lateximage}[-forest-~\PackageDiagramAltText]%
}

\AfterEndEnvironment{forest}{\end{lateximage}}

\RenewDocumentCommand{\Forest}{s D(){} m}{%
  \forest@config{#2}%
  \IfBooleanTF{#1}{%
```

```
        \PackageError{lwarp-forest}%
        {\protect\Forest* is not supported}%
        {Lwarp uses an environment for images,\MessageBreak
            but \protect\Forest* cannot work in an environment.}%
        \let\forest@next\forest@env%
    }{\let\forest@next\forest@group@env}%
    \begin{lateximage}[-forest-~\PackageDiagramAltText]%     lwarp
  \forest@next{#3}%
    \end{lateximage}%               lwarp
}
```

File 189 **lwarp-fouridx.sty**

§ 297 Package fouridx

(*Emulates or patches code by* Stefan Karrmann.)

Pkg fouridx fouridx works as-is with SVG math, and is emulated for MathJax.

for HTML output:

```
\LWR@ProvidesPackagePass{fouridx}[2013/11/21]

\begin{warpMathJax}
\CustomizeMathJax{%
    \newcommand{\fourIdx}[5]{%
        \vphantom{#5}^{\hphantom{#2}#1}_{\hphantom{#1}#2}{#5}^{#3}_{#4}%
    }%
}
\end{warpMathJax}
```

File 190 **lwarp-fourier.sty**

§ 298 Package fourier

(*Emulates or patches code by* Michel Bovani.)

Pkg fourier fourier is used as-is for SVG math, and is emulated for MathJax.

⚠ limitations The MathJax emulation ignores all package options, except `sloped` and `upright` are honored for Greek characters, but MathJax cannot yet honor these for Latin characters.

The dedicated macros for upright and italic Greek letters do work correctly.

SVG math should appear the same as the printed output.

for HTML output:

```
\LWR@ProvidesPackagePass{fourier}[2020/03/03]

\LWR@infoprocessingmathjax{fourier}

\LWR@origRequirePackage{lwarp-common-mathjax-letters}

\LWR@origRequirePackage{lwarp-common-mathjax-overlaysymbols}
```

```
\begin{warpMathJax}

\@ifpackagewith{fourier}{sloped}
    {
        \LWR@mathjax@addgreek@l@up{other}{}
        \LWR@mathjax@addgreek@u@it*{other}{}
    }% sloped
    {% not sloped
        \@ifpackagewith{fourier}{upright}
            {% upright option
                \LWR@mathjax@addgreek@l@up{}{}
                \LWR@mathjax@addgreek@u@up*{}{}
                \LWR@mathjax@addgreek@l@it{other}{}
                \LWR@mathjax@addgreek@u@it*{other}{}
            }
            {% neither sloped nor upright
                \LWR@mathjax@addgreek@l@up{other}{}
                \LWR@mathjax@addgreek@u@it*{other}{}
            }
    }

\CustomizeMathJax{\newcommand{\othergreek}[1]{#1}}
\CustomizeMathJax{\let\varvarrho\varrho}
\CustomizeMathJax{\let\varvarpi\varpi}
\CustomizeMathJax{\let\othervarvarpi\othervarpi}
\CustomizeMathJax{\let\othervarvarrho\othervarrho}
\CustomizeMathJax{\let\varpartialdiff\partial}
```

`lwarp_mathjax.txt` adds `\left`/`\right` support for delimiters.

```
\CustomizeMathJax{\let\llbracket\lBrack}
\CustomizeMathJax{\let\rrbracket\rBrack}
\CustomizeMathJax{\let\dblbrackleft\lBrack}
\CustomizeMathJax{\let\dblbrackright\rBrack}

\CustomizeMathJax{\let\VERT|}

\CustomizeMathJax{\newcommand{\parallelslant}{\mathrel{\unicode{x02AFD}}}}
\CustomizeMathJax{\newcommand{\thething}{\mathord{\unicode{x1F60E}}}}
\CustomizeMathJax{\newcommand{\nparallelslant}{%
    \mathrel{\LWRoverlaysymbols{-}{\unicode{x02AFD}}}%
}}
\CustomizeMathJax{\newcommand{\xswordsup}{\mathord{\unicode{x2694}}}}
\CustomizeMathJax{\newcommand{\xswordsdown}{\mathord{\unicode{x2694}}}}% up
\CustomizeMathJax{\newcommand{\notowns}{\mathrel{\unicode{x220C}}}}

\CustomizeMathJax{\newcommand{\iintop}{\mathop{\unicode{x222C}}\limits}}
\CustomizeMathJax{\newcommand{\iiintop}{\mathop{\unicode{x222D}}\limits}}
\CustomizeMathJax{\newcommand{\oiint}{\mathop{\unicode{x222F}}\limits}}
\CustomizeMathJax{\let\oiintop\oiint}
\CustomizeMathJax{\newcommand{\oiiint}{\mathop{\unicode{x2230}}\limits}}
\CustomizeMathJax{\let\oiiintop\oiiint}
\CustomizeMathJax{\newcommand{\slashint}{\mathop{\unicode{x2A0D}}\limits}}
\CustomizeMathJax{\let\slashintop\slashint}
```

```
59
60 \CustomizeMathJax{\let\overgroup\overparen}
61 \CustomizeMathJax{\let\wideparen\overparen}
62 \CustomizeMathJax{\let\widearc\overparen}
63 \CustomizeMathJax{\let\wideOarc\overrightarrow}
64 \CustomizeMathJax{\newcommand{\widering}[1]{\stackrel{\unicode{x2218}}{\overgroup{#1}}}}
65
66 \end{warpMathJax}
```

File 191 **lwarp-framed.sty**

§ 299 Package

framed

(*Emulates or patches code by* Donald Arseneau.)

Pkg framed framed is supported and patched by lwarp.

for HTML output: Accept all options for lwarp-framed:

```
1 \LWR@ProvidesPackagePass{framed}[2011/10/22]
2 \AtBeginDocument{\RequirePackage{xcolor}}% for \convertcolorspec

3
4 \renewenvironment{framed}{%
5 \LWR@forcenewpage
6 \BlockClass{framed}%
7 }
8 {\endBlockClass}
9
10 \renewenvironment{oframed}{%
11 \LWR@forcenewpage
12 \BlockClass{framed}%
13 }
14 {\endBlockClass}
15
16
17 \renewenvironment{shaded}{%
18 \convertcolorspec{named}{shadecolor}{HTML}\LWR@tempcolor%
19 \LWR@forcenewpage
20 \BlockClass[background: \LWR@origpound\LWR@tempcolor]{shaded}%
21 }
22 {\endBlockClass}
23
24 \renewenvironment{shaded*}{%
25 \convertcolorspec{named}{shadecolor}{HTML}\LWR@tempcolor%
26 \LWR@forcenewpage
27 \BlockClass[background: \LWR@origpound\LWR@tempcolor]{shaded}%
28 }
29 {\endBlockClass}
30
31
32 \renewenvironment{leftbar}{%
33 \LWR@forcenewpage
34     \BlockClass{framedleftbar}
```

```
  \def\FrameCommand{}%
  \MakeFramed {}
}%
 {\endMakeFramed\endBlockClass}


\renewenvironment{snugshade}{%
\convertcolorspec{named}{shadecolor}{HTML}\LWR@tempcolor%
\LWR@forcenewpage
\BlockClass[background: \LWR@origpound\LWR@tempcolor]{snugframed}%
}
{\endBlockClass}

\renewenvironment{snugshade*}{%
\convertcolorspec{named}{shadecolor}{HTML}\LWR@tempcolor%
\LWR@forcenewpage
\BlockClass[background: \LWR@origpound\LWR@tempcolor]{snugframed}%
}
{\endBlockClass}

\let\oframed\framed
\let\endoframed\endframed


\RenewEnviron{titled-frame}[1]{%
\CustomFBox{#1}{}{0pt}{0pt}{0pt}{0pt}{\BODY}
}
```

\CustomFBox {⟨*toptitle*⟩} {⟨*bottitle*⟩} {⟨*thicknesstop*⟩} {⟨*bottom*⟩} {⟨*left*⟩} {⟨*right*⟩} {⟨*text contents*⟩}

```
\renewcommand{\CustomFBox}[7]{%
\convertcolorspec{named}{TFFrameColor}{HTML}\LWR@tempcolor%
\LWR@forcenewpage
\begin{BlockClass}[border: 3px solid \LWR@origpound\LWR@tempcolor]{framed}%
\ifthenelse{\isempty{#1}}{}{% not empty
    \begin{BlockClass}[background: \LWR@origpound\LWR@tempcolor]{framedtitle}%
    \textcolor{TFTitleColor}{\textbf{#1}}%
    \end{BlockClass}
}% not empty

#7

\ifthenelse{\isempty{#2}}{}{% not empty
    \convertcolorspec{named}{TFFrameColor}{HTML}\LWR@tempcolor%
    \begin{BlockClass}[background: \LWR@origpound\LWR@tempcolor]{framedtitle}%
    \textcolor{TFTitleColor}{\textbf{#2}}%
    \end{BlockClass}
}% not empty
\end{BlockClass}
}
```

\TitleBarFrame [⟨*marker*⟩] {⟨*title*⟩} {⟨*contents*⟩}

```
\renewcommand\TitleBarFrame[3][]{
```

```
\CustomFBox
    {#2}{}%
    \fboxrule\fboxrule\fboxrule\fboxrule
    {#3}%
}

\renewcommand{\TF@Title}[1]{#1}
```

MakeFramed {⟨*settings*⟩}

```
\let\MakeFramed\relax
\let\endMakeFramed\relax

\NewEnviron{MakeFramed}[1]{%
\FrameCommand{\begin{minipage}{\linewidth}\BODY\end{minipage}}%
}
```

\fb@put@frame {⟨*frame cmd no split*⟩} {⟨*frame cmd split*⟩}

```
\renewcommand*{\fb@put@frame}[2]{%
\relax%
\@tempboxa%
}
```

File 192 **lwarp-froufrou.sty**

§ 300 Package

froufrou

(*Emulates or patches code by* Nelson Lago.)

Pkg froufrou froufrou is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{froufrou}[2020/12/22]

\ExplSyntaxOn
\xpretocmd{\setfroufrou}
    {\edef\LWR@latestfroufrou{\detokenize{#1}}}
    {}
    {\LWR@patcherror{froufrou}{setfroufrou}}
\ExplSyntaxOff

\xpatchcmd{\@realfroufrou}
    {\@froufrouOrnament}
    {%
        \begin{center}
        \begin{lateximage}*[froufrou][\LWR@latestfroufrou]%
        \@froufrouOrnament%
        \end{lateximage}
        \end{center}
    }
    {}
    {\LWR@patcherror{froufrou}{@realfroufrou}}
```

File 193 **lwarp-ftcap.sty**

§ 301 Package

ftcap

Pkg ftcap ftcap is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{ftcap}
```

File 194 **lwarp-ftnright.sty**

§ 302 Package

ftnright

Pkg ftnright ftnright is ignored.

for HTML output: Discard all options for lwarp-ftnright:

```
1 \LWR@ProvidesPackageDrop{ftnright}[2014/10/28]
```

File 195 **lwarp-fullminipage.sty**

§ 303 Package

fullminipage

Pkg fullminipage fullminipage is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{fullminipage}[2014/07/06]
2 \newenvironment{fullminipage}[1][]{}{}
```

File 196 **lwarp-fullpage.sty**

§ 304 Package

fullpage

Pkg fullpage fullpage is ignored.

for HTML output: Discard all options for lwarp-fullpage:

```
1 \LWR@ProvidesPackageDrop{fullpage}[1994/06/01]
```

File 197 **lwarp-fullwidth.sty**

§ 305 Package fullwidth

(*Emulates or patches code by* Marco Daniel.)

Pkg `fullwidth` fullwidth is emulated.

A minipage is used, of no HTML width.

for HTML output:

```
\LWR@ProvidesPackageDrop{fullwidth}[2011/11/18]

\newenvironment*{fullwidth}[1][]{%
\minipagefullwidth%
\minipage{\linewidth}%
}
{%
\endminipage%
}
```

File 198 **lwarp-fvextra.sty**

§ 306 Package fvextra

(*Emulates or patches code by* Geoffrey M. Poore.)

Pkg `fvextra` fvextra is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{fvextra}[2019/02/04]
```

Ignored are `highlight`, `showtabs`, `obeytabs`, `tab`, `tabcolor`. Also ignored are all options regarding line breaking except `breaklines`, which is emulated as true.

`tabsize` is honored.

If line numbers on the right side are used along with `breaklines`, the line numbers will not be aligned.

```

\define@booleankey{FV}{obeytabs}%
%   {\let\FV@ObeyTabsInit\FV@@ObeyTabsInit}%
  {\let\FV@ObeyTabsInit\relax}
  {\let\FV@ObeyTabsInit\relax}

\define@key{FV}{tabcolor}%
 {}

\define@key{FV}{tab}{}

\define@booleankey{FV}{showtabs}%
%  {\def\FV@TabChar{\FV@TabColor{\FancyVerbTab}}}%
 {\let\FV@TabChar\relax}
 {\let\FV@TabChar\relax}

\newbool{LWR@FV@breaklines}
```

```
19
20 \define@booleankey{FV}{breaklines}%
21   {\FV@BreakLinesfalse
22     \booltrue{LWR@FV@breaklines}
23     \let\FV@ListProcessLine\FV@ListProcessLine@NoBreak}
24   {\FV@BreakLinesfalse
25     \boolfalse{LWR@FV@breaklines}
26     \let\FV@ListProcessLine\FV@ListProcessLine@NoBreak}
27 % \fvset{breaklines}
28
29 \define@key{FV}{breakanywheresymbolpre}{\def\FancyVerbBreakAnywhereSymbolPre{}}
30 \fvset{breakanywheresymbolpre={}}
31
32 \define@key{FV}{breakanywheresymbolpost}{\def\FancyVerbBreakAnywhereSymbolPost{}}
33 \fvset{breakanywheresymbolpost={}}
34
35 \define@key{FV}{breakbeforesymbolpre}{\def\FancyVerbBreakBeforeSymbolPre{}}
36 \fvset{breakbeforesymbolpre={}}
37
38 \define@key{FV}{breakbeforesymbolpost}{\def\FancyVerbBreakBeforeSymbolPost{}}
39 \fvset{breakbeforesymbolpost={}}
40
41 \define@key{FV}{breakaftersymbolpre}{\def\FancyVerbBreakAfterSymbolPre{}}
42 \fvset{breakaftersymbolpre={}}
43
44 \define@key{FV}{breakaftersymbolpost}{\def\FancyVerbBreakAfterSymbolPost{}}
45 \fvset{breakaftersymbolpost={}}
46
47 \define@key{FV}{breaksymbolleft}{\def\FancyVerbBreakSymbolLeft{}}
48
49 \define@key{FV}{breaksymbol}{\fvset{breaksymbolleft={}}}
50
51 \fvset{breaksymbolleft={}}
52
53 \define@key{FV}{breaksymbolright}{\def\FancyVerbBreakSymbolRight{}}
54 \fvset{breaksymbolright={}}
55
56 \def\FV@ListProcessLine@NoBreak#1{%
57 %   \hbox to \hsize{%
58 %     \kern\leftmargin
59 %     \hbox to \linewidth{%
60       \FV@LeftListNumber%
61       \FV@LeftListFrame%
62       \FancyVerbFormatLine{%
63         \FancyVerbHighlightLine{%
64           \FV@ObeyTabs{\FancyVerbFormatText{#1}}}}%\hss
65       \FV@RightListFrame%
66       \FV@RightListNumber%
67 %     }%
68 %     \hss}%
69 \null\par%                    lwarp
70 }
71
72
73 \newcommand*{\LWR@FV@linethensep}{%
```

```
    \ifbool{LWR@FV@breaklines}%
        {\theFancyVerbLine\kern\FV@NumberSep}%
        {\hbox to\z@{\hss\theFancyVerbLine\kern\FV@NumberSep}}%
}

\newcommand*{\LWR@FV@septhenline}{%
    \ifbool{LWR@FV@breaklines}%
        {\kern\FV@NumberSep\theFancyVerbLine}%
        {\hbox to\z@{\kern\FV@NumberSep\theFancyVerbLine\hss}}%
}

\xpatchcmd{\FV@Numbers@left}
    {\hbox to\z@{\hss\theFancyVerbLine\kern\FV@NumberSep}}
    {\LWR@FV@linethensep}
    {}
    {\LWR@patcherror{fvextra}{FV@Numbers@left A}}

\xpatchcmd{\FV@Numbers@left}
    {\hbox to\z@{\hss\theFancyVerbLine\kern\FV@NumberSep}}
    {\LWR@FV@linethensep}
    {}
    {\LWR@patcherror{fvextra}{FV@Numbers@left B}}

\xpatchcmd{\FV@Numbers@left}
    {\hbox to\z@{\hss\theFancyVerbLine\kern\FV@NumberSep}}
    {\LWR@FV@linethensep}
    {}
    {\LWR@patcherror{fvextra}{FV@Numbers@left C}}

\xpatchcmd{\FV@Numbers@right}
    {\hbox to\z@{\kern\FV@NumberSep\theFancyVerbLine\hss}}
    {\LWR@FV@septhenline}
    {}
    {\LWR@patcherror{fvextra}{FV@Numbers@right A}}

\xpatchcmd{\FV@Numbers@right}
    {\hbox to\z@{\kern\FV@NumberSep\theFancyVerbLine\hss}}
    {\LWR@FV@septhenline}
    {}
    {\LWR@patcherror{fvextra}{FV@Numbers@right B}}

\xpatchcmd{\FV@Numbers@right}
    {\hbox to\z@{\hss\theFancyVerbLine\kern\FV@NumberSep}}
    {\LWR@FV@linethensep}
    {}
    {\LWR@patcherror{fvextra}{FV@Numbers@right C}}

\xpatchcmd{\FV@Numbers@both}
    {\hbox to\z@{\hss\theFancyVerbLine\kern\FV@NumberSep}}
    {\LWR@FV@linethensep}
    {}
    {\LWR@patcherror{fvextra}{FV@Numbers@both A}}

\xpatchcmd{\FV@Numbers@both}
    {\hbox to\z@{\hss\theFancyVerbLine\kern\FV@NumberSep}}
```

```
    {\LWR@FV@linethensep}
    {}
    {\LWR@patcherror{fvextra}{FV@Numbers@both B}}

\xpatchcmd{\FV@Numbers@both}
    {\hbox to\z@{\hss\theFancyVerbLine\kern\FV@NumberSep}}
    {\LWR@FV@linethensep}
    {}
    {\LWR@patcherror{fvextra}{FV@Numbers@both C}}

\xpatchcmd{\FV@Numbers@both}
    {\hbox to\z@{\kern\FV@NumberSep\theFancyVerbLine\hss}}
    {\LWR@FV@septhenline}
    {}
    {\LWR@patcherror{fvextra}{FV@Numbers@both D}}

\xpatchcmd{\FV@Numbers@both}
    {\hbox to\z@{\kern\FV@NumberSep\theFancyVerbLine\hss}}
    {\LWR@FV@septhenline}
    {}
    {\LWR@patcherror{fvextra}{FV@Numbers@both E}}

\xpatchcmd{\FV@Numbers@both}
    {\hbox to\z@{\hss\theFancyVerbLine\kern\FV@NumberSep}}
    {\LWR@FV@linethensep}
    {}
    {\LWR@patcherror{fvextra}{FV@Numbers@both F}}
```

File 199 **lwarp-fwlw.sty**

§ 307 Package fwlw

Pkg fwlw fwlw is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{fwlw}

\newbox\FirstWordBox      \global\setbox\FirstWordBox\hbox{}
\newbox\NextWordBox       \global\setbox\NextWordBox\hbox{}
\newbox\LastWordBox       \global\setbox\LastWordBox\hbox{}
\def\ps@fwlwhead{}
\def\ps@NextWordFoot{}
```

File 200 **lwarp-gensymb.sty**

§ 308 Package gensymb

(*Emulates or patches code by* Walter Schmidt.)

Pkg gensymb gensymb works as-is for SVG math, and is emulated for MathJax.

for HTML output:

```
\LWR@ProvidesPackagePass{gensymb}[2003/07/02]
```

```
\begin{warpMathJax}
\CustomizeMathJax{\newcommand{\degree}{\mathrm{^\circ}}}
\CustomizeMathJax{\newcommand{\celsius}{\unicode{x2103}}}
\CustomizeMathJax{\newcommand{\perthousand}{\unicode{x2030}}}
\CustomizeMathJax{\newcommand{\ohm}{\mathrm{\Omega}}}
\CustomizeMathJax{\newcommand{\micro}{\mathrm{\unicode{x00B5}}}}
\end{warpMathJax}
```

File 201 **lwarp-gentombow.sty**

§ 309 Package gentombow

Pkg gentombow gentombow is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{gentombow}[2018/05/17]
```

```
\newcommand{\settombowbanner}[1]{}
\newcommand{\settombowbannerfont}[1]{}
\newcommand{\settombowwidth}[1]{}
\newcommand{\settombowbleed}[1]{}
\newcommand{\settombowcolor}[1]{}
```

File 202 **lwarp-geometry.sty**

§ 310 Package geometry

(*Emulates or patches code by* Hideo Umeki.)

Pkg geometry geometry is preloaded by lwarp, but must be nullified as seen by the user's source code.

for HTML output: Discard all options for lwarp-geometry:

```
\LWR@ProvidesPackageDropA{geometry}{2018/04/16}
```

If geometry is never loaded by the user, it will be loaded by lwarp `\AtBeginDocument`. If this is the case, the page layout should not be changed but the user macros should still be nullified.

```
\ifbool{LWR@allowanothergeometry}{%
```

Assign and set the selected geometry with `reset` prepended. `\AtEndPreamble` lwarp will save this, then set its own geometry.

```
    \edef\LWR@tempone{reset,\@ptionlist{\@currname.\@currext}}%
    \expandafter\LWR@origgeometry\expandafter{\LWR@tempone}%
}{}% LWR@allowanothergeometry
```

The user-level commands are nullified:

```
\renewcommand*{\geometry}[1]{}
```

```
\renewcommand*{\newgeometry}[1]{}
\renewcommand*{\restoregeometry}{}
\renewcommand*{\savegeometry}[1]{}
\renewcommand*{\loadgeometry}[1]{}
```

File 203 **lwarp-ghsystem.sty**

§ 311 Package

ghsystem

(*Emulates or patches code by* Clemens Niederberger.)

Pkg ghsystem ghsystem is patched for use by lwarp.

⚠ \ghspic images Images must be provided in SVG format, unless JPG is specified. It is recommended to create a local images directory, copy into it the relevent PDF ghsystem images, and then convert them with

Enter ⇒ **lwarpmk pdftosvg images/*.pdf**

for HTML output:

```
\LWR@ProvidesPackagePass{ghsystem}[2020/02/17]

\ExplSyntaxOn

\cs_set_protected:Npn \ghsystem_filler:n #1
  { \emph { \textless #1 \textgreater } }

\cs_set_protected:Npn \ghsystem_pic:n #1
  {
    \__ghsystem_includegraphics:xn
      {
%         scale = \fp_to_tl:N \l__ghsystem_picture_scale_fp
        width = 1.25cm
        \exp_not:V \l__ghsystem_picture_includegraphics_tl
      }
      { ghsystem_ #1 . \l__ghsystem_picture_type_tl }
  }

\ExplSyntaxOff
```

File 204 **lwarp-gindex.sty**

§ 312 Package

gindex

(*Emulates or patches code by* Javier Bezos.)

Pkg gindex gindex is patched for use by lwarp.

See section 8.6.15.

for HTML output:

```
\LWR@ProvidesPackagePass{gindex}[2019/10/07]
```

Set the index page and range separators. These are set `\AtBeginDocument` to allow the user to change them. They are then protected so that the lwarp core looks for the tokens instead of their expanded contents, since the `*.ind` files will contain `\indexpagessep` and `\indexrangesep` instead of their literal contents. Finally, lwarp is told of the gindex macros.

```
\AtBeginDocument{
    \robustify{\indexpagessep}
    \robustify{\indexrangesep}
    \renewcommand*{\IndexPageSeparator}{\indexpagessep}
    \renewcommand*{\IndexRangeSeparator}{\indexrangesep}
}
```

`\hyperindexref` is added:

```
\def\addindexitem#1#2{%
  \indexflushitem
  \gix@getspecial#1\indexspecial\indexspecial\@@\indexitem{\hyperindexref{#2}}}

\def\addindexsubitem#1#2{%
  \stepcounter{indexsubitems}%
  \gix@getspecial#1\indexspecial\indexspecial\@@\indexsubitem{\hyperindexref{#2}}}

\def\addindexsubsubitem#1#2{%
  \gix@getspecial#1\indexspecial\indexspecial\@@\indexsubsubitem{\hyperindexref{#2}}}
```

Uses a `<div>` of class `indexheading`:

```
\renewcommand\indexheading[1]{%
    \begin{BlockClass}{indexheading}
    \MakeUppercase{#1}%
    \end{BlockClass}
}
```

File 205 **lwarp-gloss.sty**

§ 313 Package

gloss

(*Emulates or patches code by* Jose Luis Díiaz, Javier Bezos.)

Pkg gloss gloss is patched for use by lwarp.

To process the HTML glossary:

```
bibtex <projectname>_html.gls
```

for HTML output:

```
\LWR@ProvidesPackagePass{gloss}[2002/07/26]
```

`\BaseJobname` is added to the label in case xr or xr-hyper are used.

```
\xpatchcmd{\gls@gloss@iii}
    {\thepage}
```

```
    {\theLWR@previousautopagelabel}
    {}
    {\LWR@patcherror{gloss}{gls@gloss@iii}}

\def\gls@page@i#1#2{%
  \endgroup%
  \global\@namedef{glsp@#1}{\nameref{\BaseJobname-autopage-#2}}}%
```

File 206 **lwarp-glossaries.sty**

§ 314 Package

glossaries

(*Emulates or patches code by* Nicola L.C. Talbot.)

Pkg glossaries

processing glossaries

Opt GlossaryCmd

Default: makeglossaries

Opt [lwarpmk] printglossary

Opt [lwarpmk] htmlglossary

⚠ *makeglossaries* not found

lwarpmk has the commands **lwarpmk printglossary** and **lwarpmk htmlglossary**, which process the glossaries created by the glossaries package using that package's *makeglossaries* program.

The shell command to execute is set by the lwarp option GlossaryCmd, which defaults to **makeglossaries**. The print or HTML glossary filename is appended to this command.

In some situations it may be required to modify the default command, such as to add the **perl** command in front:

```
\usepackage[
   GlossaryCmd={perl makeglossaries},
] {lwarp}
```

xindy language

To set the language to use for processing glossaries with *xindy*:

```
\usepackage[
   GlossaryCmd={makeglossaries -L english},
] {lwarp}
```

Other options for *makeglossaries* may be set as well.

placement and TOC options

The glossaries may be placed in a numbered or unnumbered section, given a TOC entry, and placed inline or on their own HTML page:

Numbered section, on its own HTML page:

```
\usepackage[xindy,toc,numberedsection=nolabel]{glossaries}
. . .
\printglossaries
```

Unnumbered section, inline with the current HTML page:

```
\usepackage[xindy,toc]{glossaries}
. . .
\printglossaries
```

Unnumbered section, on its own HTML page:

```
\usepackage[xindy,toc]{glossaries}
. . .
\ForceHTMLPage
\printglossaries
```

⚠ glossary style — The default `style=item` option for glossaries conflicts with lwarp, so the style is forced to `index` instead.

⚠ number list — The page number list in the printed form would become `\namerefs` in HTML, which could become a very long string if many items are referenced. For now, the number list is simply turned off.

print/HTML versions — The print and HTML versions of the glossary differ in their internal page numbers. Separate commands for generating print and HTML glossaries are used, even though the page number is currently ignored.

for HTML output:

```
\PassOptionsToPackage{xindy}{glossaries}

\LWR@ProvidesPackagePass{glossaries}[2018/07/23]

\setupglossaries{nonumberlist}
\setglossarystyle{index}
```

Patched to fix TOC pointing to the previous page:

```
\renewcommand*{\@p@glossarysection}[2]{%
  \glsclearpage
  \LWR@phantomsection
  \ifdefempty\@@glossarysecstar
  {%
    \csname\@@glossarysec\endcsname{#2}%
  }%
  {%
```

In the original, the TOC entry was made before the section, thus linking to the phantomsection in the printed version, but for HTML, this caused the link to point to the page before the glossaries, which could be a different HTML file. Here, the TOC entry is made after the section is created:

```
      \csname\@@glossarysec\endcsname*{#2}%
    \@gls@toc{#1}{\@@glossarysec}% Moved after the previous line.
  }%
  \@@glossaryseclabel
}
```

lwarp's sectioning commands cannot handle robust macros when splitting HTML into named filenames. glossaries uses `\translate` in sectioning names, and `\translate` is robust and cannot be expanded. The following pre-expands the translations at this moment, making use of `\translatelet`.

```
\newcommand*{\LWR@comp@glossaryname}{\translate{Glossary}}

\ifdefstrequal{\glossaryname}{\LWR@comp@glossaryname}{
    \translatelet\LWR@translatetemp{Glossary}
    \edef\glossaryname{\LWR@translatetemp}
}{}

\newcommand*{\LWR@comp@acronymname}{\translate{Acronym}}

```

```
\ifdefstrequal{\acronymname}{\LWR@comp@acronymname}{
    \translatelet\LWR@translatetemp{Acronym}
    \edef\acronymname{\LWR@translatetemp}
}{}

\newcommand*{\LWR@comp@glssymbolsgroupname}{\translate{Symbols (glossaries)}}

\ifdefstrequal{\glssymbolsgroupname}{\LWR@comp@glssymbolsgroupname}{
    \translatelet\LWR@translatetemp{Symbols (glossaries)}
    \edef\glssymbolsgroupname{\LWR@translatetemp}
}{}

\newcommand*{\LWR@comp@glsnumbersgroupname}{\translate{Numbers (glossaries)}}

\ifdefstrequal{\glsnumbersgroupname}{\LWR@comp@glsnumbersgroupname}{
    \translatelet\LWR@translatetemp{Numbers (glossaries)}
    \edef\glsnumbersgroupname{\LWR@translatetemp}
}{}
```

File 207 **lwarp-gmeometric.sty**

§ 315 Package gmeometric

Pkg gmeometric gmeometric is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{gmeometric}[2008/11/22]
\RequirePackageWithOptions{geometry}
```

File 208 **lwarp-graphics.sty**

§ 316 Package graphics

(*Emulates or patches code by* D. P. Carlisle.)

Pkg graphics graphics is emulated.

for HTML output:

```
\LWR@ProvidesPackagePass{graphics}[2020/08/30]
```

§ 316.1 Graphics extensions

\DeclareGraphicsExtensions {⟨*list*⟩}

\AtBeginDocument allow SVG files instead of PDF:

```
\AtBeginDocument{
\DeclareGraphicsExtensions{.svg,.SVG,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG}
\DeclareGraphicsRule{.svg}{svg}{.svg}{}
\DeclareGraphicsRule{.SVG}{svg}{.SVG}{}
}
```

Inside a `lateximage`, allow PDF instead of SVG:

```
\ifpdf
\appto\LWR@restoreorigformatting{%
\DeclareGraphicsExtensions{.pdf,.PDF,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG}%
}
\else% \ifpdf
        \ifXeTeX
\appto\LWR@restoreorigformatting{%
\DeclareGraphicsExtensions{.pdf,.PDF,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG}%
}
        \else
\appto\LWR@restoreorigformatting{%
\DeclareGraphicsExtensions{.eps,.EPS,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG}%
}
        \fi
\fi
```

§ 316.2 Length conversions and graphics options

⚠ whitespace

A scaled image in LaTeX by default takes only as much space on the page as it requires, but HTML browsers use as much space as the original unscaled image would have taken, with the scaled image over- or under-flowing the area.

Used to store the user's selected dimensions and HTML class.

The class defaults to "inlineimage" unless changed by a `class=xyx` option.

```
\newlength{\LWR@igwidth}
\newlength{\LWR@igheight}
\newcommand*{\LWR@igwidthstyle}{}
\newcommand*{\LWR@igheightstyle}{}
\newcommand*{\LWR@igorigin}{}
\newcommand*{\LWR@igangle}{}
\newcommand*{\LWR@igxscale}{1}
\newcommand*{\LWR@igyscale}{1}

\newbool{LWR@igkeepaspectratio}
\boolfalse{LWR@igkeepaspectratio}

\newcommand*{\LWR@igclass}{inlineimage}


\newcommand*{\LWR@igalt}{\ImageAltText}
```

Set the actions of each of the key/value combinations for `\includegraphics`. Many are ignored.

If an optional width was given, set an HTML style:

```
\define@key{igraph}{width}{%
\setlength{\LWR@igwidth}{#1}%
\ifthenelse{\lengthtest{\LWR@igwidth > 0pt}}%
{%
```

Default to use the converted fixed length given:

```
    \renewcommand*{\LWR@igwidthstyle}{width:\LWR@printlength{\LWR@igwidth}}%
```

If ex or em dimensions were given, use those instead:

```
    \IfEndWith{#1}{ex}%
    {\renewcommand*{\LWR@igwidthstyle}{width:#1}}% yes ex
    {}% not ex
    \IfEndWith{#1}{em}%
    {\renewcommand*{\LWR@igwidthstyle}{width:#1}}% yes em
    {}% not em
    \IfEndWith{#1}{\%}%
    {\renewcommand*{\LWR@igwidthstyle}{width:#1}}% yes percent
    {}% not percent
    \IfEndWith{#1}{px}%
    {\renewcommand*{\LWR@igwidthstyle}{width:#1}}% yes px
    {}% not px
}{}% end of length > 0pt
}
```

If an optional height was given, set an HTML style:

```
\define@key{igraph}{height}{%
\setlength{\LWR@igheight}{#1}%
\ifthenelse{\lengthtest{\LWR@igheight > 0pt}}%
{%
```

Default to use the converted fixed length given:

```
    \renewcommand*{\LWR@igheightstyle}{%
    height:\LWR@printlength{\LWR@igheight} % extra space
    }%
```

If ex or em dimensions were given, use those instead:

```
    \IfEndWith{#1}{ex}%
    {\renewcommand*{\LWR@igheightstyle}{height:#1}}% yes ex
    {}% not ex
    \IfEndWith{#1}{em}%
    {\renewcommand*{\LWR@igheightstyle}{height:#1}}% yes em
    {}% not em
    \IfEndWith{#1}{\%}%
    {\renewcommand*{\LWR@igheightstyle}{height:#1}}% yes percent
    {}% not percent
    \IfEndWith{#1}{px}%
    {\renewcommand*{\LWR@igheightstyle}{height:#1}}% yes px
    {}% not px
}{}% end of length > 0pt
}
```

Handle `keepaspectratio` key:

```
\define@key{igraph}{keepaspectratio}[false]{%
    \booltrue{LWR@igkeepaspectratio}%
```

```
}
```

Handle `origin` key:

```
\define@key{igraph}{origin}[c]{%
    \renewcommand*{\LWR@igorigin}{#1}%
}
```

Handle `angle` key:

```
\define@key{igraph}{angle}{\renewcommand*{\LWR@igangle}{#1}}
```

Handle `class` key:

```
\define@key{igraph}{class}{\renewcommand*{\LWR@igclass}{#1}}
```

Handle `alt` key:

```
\define@key{igraph}{alt}{\renewcommand*{\LWR@igalt}{#1}}
```

It appears that graphicx does not have separate keys for `xscale` and `yscale`. `scale` adjusts both at the same time.

```
\define@key{igraph}{scale}{%
    \ifthenelse{\equal{#1}{1}}{}{%  must expand #1
        \PackageWarning{lwarp}{%
         It is recommended to use ``[width=xx\protect\linewidth]''\MessageBreak
            instead of ``[scale=yy]'',%
        }%
    }%
    \renewcommand*{\LWR@igxscale}{#1}%
    \renewcommand*{\LWR@igyscale}{#1}%
}
```

Numerous ignored keys:

```
\define@key{igraph}{bb}{}
\define@key{igraph}{bbllx}{}
\define@key{igraph}{bblly}{}
\define@key{igraph}{bburx}{}
\define@key{igraph}{bbury}{}
\define@key{igraph}{natwidth}{}
\define@key{igraph}{natheight}{}
\define@key{igraph}{hiresbb}[true]{}
\define@key{igraph}{viewport}{}
\define@key{igraph}{trim}{}
\define@key{igraph}{totalheight}{}
\define@key{igraph}{clip}[true]{}
\define@key{igraph}{draft}[true]{}
\define@key{igraph}{type}{}
\define@key{igraph}{ext}{}
\define@key{igraph}{read}{}
\define@key{igraph}{command}{}
```

New in v1.1a:

```
\define@key{igraph}{quite}{}
\define@key{igraph}{page}{}
\define@key{igraph}{pagebox}{}
\define@key{igraph}{interpolate}[true]{}
```

New in v1.1b:

```
\define@key{igraph}{decodearray}{}
```

§ 316.3 Printing HTML styles

`\LWR@rotstyle` {⟨*prefix*⟩} {⟨*degrees*⟩}

Prints the rotate style with the given prefix.

`prefix` is `-ms-` or `-webkit-` or nothing, and is used to generate three versions of the `transform:rotate` style.

```
\newcommand*{\LWR@rotstyle}[2]{%
    \edef\LWR@tempone{#2}%
    \setcounter{LWR@tempcountone}{-1*\real{\LWR@tempone}} % space
    #1transform:rotate(\arabic{LWR@tempcountone}deg); % space
}
```

`\LWR@scalestyle` {⟨*prefix*⟩} {⟨*xscale*⟩} {⟨*yscale*⟩}

Prints the scale style with the given prefix.

`prefix` is `-ms-` or `-webkit-` or nothing, and is used to generate three versions of the `transform:scale` style.

```
\newcommand*{\LWR@scalestyle}[3]{%
    #1transform:scale(#2,#3);
}
```

§ 316.4 `\includegraphics`

`\LWR@opacity` For HTML, used only for `\includegraphics`.

`\LWR@opacity` may be set by the transparent package.

```
\def\LWR@opacity{1}
```

`\LWR@imagesizebox` Used to determine the actual image size if needed.

```
\newsavebox{\LWR@imagesizebox}
```

`\LWR@HTML@Gin@setfile` {⟨*w*⟩} {⟨*h*⟩} {⟨*filename*⟩} Sets the parsed filename for HTML output.

```
\newcommand*{\LWR@HTML@Gin@setfile}[3]{%
    \xdef\LWR@parsedfilename{#3}%
}
```

Key [Gin] `class` CSS class for the image.

Define the new class key for the print-mode version of `\includegraphics`, which is enabled inside a `lateximage`.

```
\AtBeginDocument{
\define@key{Gin}{class}{}
\define@key{Gin}{alt}{}
}
```

\LWR@replaceEPSSVG

Usually, references to EPS files become SVG files, but if the epstopdf package is being used, it automatically converts EPS to PDF, and the following must NOT be done.

```
\AtBeginDocument{
\@ifpackageloaded{epstopdf}
{
    \newcommand*{\LWR@replaceEPSSVG}{}
}{%
    \newcommand*{\LWR@replaceEPSSVG}{%
        \StrSubstitute{\LWR@tempone}{.eps}{.svg}[\LWR@tempone]%
        \StrSubstitute{\LWR@tempone}{.EPS}{.SVG}[\LWR@tempone]%
    }
}%
}
```

* [⟨*2: options*⟩] [⟨*3: options*⟩] {⟨*4: filename*⟩}

\LWR@ig@useactualimagesize

If formatting for a word processor, find and set the actual image size, without rotation, using PDF instead of SVG to find the original bounding box:

```
\newcommand*{\LWR@ig@useactualimagesize}[4]{%
    \begingroup%
    \LWR@restoreorigformatting%
    \ifpdf%
    \appto\LWR@restoreorigformatting{%
        \DeclareGraphicsExtensions{%
            .pdf,.PDF,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG%
        }%
    }%
    \else% \ifpdf
            \ifXeTeX%
    \appto\LWR@restoreorigformatting{%
        \DeclareGraphicsExtensions{%
            .pdf,.PDF,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG%
        }%
    }%
            \else%
    \appto\LWR@restoreorigformatting{%
        \DeclareGraphicsExtensions{%
            .eps,.EPS,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG%
        }%
    }%
            \fi%
    \fi% \ifpdf
```

For a word processor, do not use rotation:

```
    \ifbool{FormatWP}{\define@key{Gin}{angle}{}}{}%

    \IfBooleanTF{#1}%
```

```
    {% starred
        \IfValueTF{#3}%
        {%
            \global\sbox{\LWR@imagesizebox}{%
                \LWR@origincludegraphics*[#2][#3]{#4}%
            }%
        }%
        {%
            \IfValueTF{#2}%
            {%
                \global\sbox{\LWR@imagesizebox}{%
                    \LWR@origincludegraphics*[#2]{#4}%
                }%
            }{%
                \global\sbox{\LWR@imagesizebox}{%
                    \LWR@origincludegraphics*{#4}%
                }%
            }%
        }%
    }% starred
    {% not starred
        \IfValueTF{#3}%
        {%
            \global\sbox{\LWR@imagesizebox}{%
                \LWR@origincludegraphics[#2][#3]{#4}%
            }%
        }%
        {%
            \IfValueTF{#2}%
            {%
                \global\sbox{\LWR@imagesizebox}{%
                    \LWR@origincludegraphics[#2]{#4}%
                }%
            }{%
                \global\sbox{\LWR@imagesizebox}{%
                    \LWR@origincludegraphics{#4}%
                }%
            }%
        }%
    }% not starred
    \endgroup%
    \settowidth{\LWR@igwidth}{\usebox{\LWR@imagesizebox}}%
    \global\renewcommand*{\LWR@igwidthstyle}{%
        width:\LWR@printlength{\LWR@igwidth}%
    }%
    \settoheight{\LWR@igheight}{\usebox{\LWR@imagesizebox}}%
    \global\renewcommand*{\LWR@igheightstyle}{%
        height:\LWR@printlength{\LWR@igheight}%
    }%
}
```

`\LWR@ig@htmltag` For the HTML reference, add the graphicspath, filename, extension, alt tag, style, and class.

```
\newcommand*{\LWR@ig@htmltag}{%
```

```
    img\LWR@indentHTML%
    src=\textquotedbl%
    \detokenize\expandafter{\LWR@parsedfilename}%
    \textquotedbl\LWR@indentHTML%
```

Only include a style tag if a width, height, angle, or scale was given:

```
    \ifthenelse{
        \NOT\equal{\LWR@igwidthstyle}{} \OR
        \NOT\equal{\LWR@igheightstyle}{} \OR
        \NOT\equal{\LWR@igorigin}{} \OR
        \NOT\equal{\LWR@igangle}{} \OR
        \NOT\equal{\LWR@igxscale}{1} \OR
        \NOT\equal{\LWR@igyscale}{1}
    }%
    {%
        style=\textquotedbl\LWR@indentHTML
        \ifthenelse{\NOT\equal{\LWR@igwidthstyle}{}}%
            {\LWR@igwidthstyle;\LWR@indentHTML}{}%
        \ifthenelse{\NOT\equal{\LWR@igheightstyle}{}}%
            {\LWR@igheightstyle;\LWR@indentHTML}{}%
        \ifthenelse{\NOT\equal{\LWR@igorigin}{}}%
            {%
                transform-origin: \LWR@originnames{\LWR@igorigin};%
                \LWR@indentHTML%
            }{}%
        \ifthenelse{\NOT\equal{\LWR@igangle}{}}%
        {%
            \LWR@rotstyle{-ms-}{\LWR@igangle}\LWR@indentHTML
            \LWR@rotstyle{-webkit-}{\LWR@igangle}\LWR@indentHTML
            \LWR@rotstyle{}{\LWR@igangle }\LWR@indentHTML
        }{}%
        \ifthenelse{%
            \NOT\equal{\LWR@igxscale}{1}\OR%
            \NOT\equal{\LWR@igyscale}{1}%
        }%
        {%
            \LWR@scalestyle{-ms-}{\LWR@igxscale}{\LWR@igyscale}%
            \LWR@indentHTML
            \LWR@scalestyle{-webkit-}{\LWR@igxscale}{\LWR@igyscale}%
            \LWR@indentHTML
            \LWR@scalestyle{}{\LWR@igxscale}{\LWR@igyscale}%
            \LWR@indentHTML
        }{}%
        %
        \ifthenelse{\NOT\equal{\LWR@opacity}{1}}%
            {opacity:\LWR@opacity;\LWR@indentHTML}{}%
        %
        \textquotedbl\LWR@indentHTML%
    }{}%
```

Set the class and alt tag:

```
    class=\textquotedbl\LWR@igclass\textquotedbl\LWR@indentHTML%
   alt=\textquotedbl\AltTextOpen\LWR@igalt\AltTextClose\textquotedbl\ \LWR@orignewline%
}% end of image tags
```

\LWR@includegraphicsb * [⟨*2: options*⟩] [⟨*3: options*⟩] {⟨*4: filename*⟩}

graphics syntax is \includegraphics * [⟨*llx,lly*⟩] [⟨*urx,ury*⟩] {⟨*filename*⟩}

graphicx syntax is \includegraphics [⟨*key values*⟩] {⟨*filename*⟩}

If #3 is empty, only one optional argument was given, thus graphicx syntax.

If using \epsfig or \psfig from the epsfig package, #4 will be \LWR@epsfig@filename, which will have been set by the file or figure keys. Therefore, #4 must not be used until after the keys have been processed.

```
\NewDocumentCommand{\LWR@includegraphicsb}{s o o m}
{%
```

Start the image tag on a new line, allow PDF output word wrap:

```
    \LWR@origtilde \LWR@orignewline%
```

Temporarily compute \linewidth, \textwidth, \textheight arguments with a 6x9 inch size until the next \endgroup.

```
    \begin{LWR@setvirtualpage}%
```

For correct em sizing during the width and height conversions:

```
    \large%
```

Temporarily prevent underfull \hbox warnings.

```
            \hbadness=10000\relax%
```

Reset some defaults, possibly will be changed below if options were given:

```
    \setlength{\LWR@igwidth}{0pt}%
    \setlength{\LWR@igheight}{0pt}%
    \renewcommand*{\LWR@igwidthstyle}{}%
    \renewcommand*{\LWR@igheightstyle}{}%
    \renewcommand*{\LWR@igorigin}{}%
    \renewcommand*{\LWR@igangle}{}%
    \renewcommand*{\LWR@igxscale}{1}%
    \renewcommand*{\LWR@igyscale}{1}%
    \renewcommand*{\LWR@igclass}{inlineimage}%
    \boolfalse{LWR@igkeepaspectratio}%

    \ifdefvoid{\LWR@ThisAltText}{%
        \edef\LWR@igalt{\ImageAltText}%
    }{%
        \edef\LWR@igalt{\LWR@ThisAltText}%
    }%
```

If #3 is empty, only one optional argument was given, thus graphicx syntax:

```
    \IfValueF{#3}{%
        \IfValueTF{#2}%
            {\setkeys{igraph}{#2}}%
            {\setkeys{igraph}{}}%
    }%
```

Fully expand and detokenize the filename, changing the file extension to .svg if necessary.

Note that uppercase file extensions are detected and reported as lowercase, so lwarp can only report to the browser lowercase extensions, so all images must have lowercase file extensions.

```
    \begingroup%
    \LetLtxMacro\Gin@setfile\LWR@HTML@Gin@setfile%
    \edef\LWR@tempone{#4}%
    \StrSubstitute{\LWR@tempone}{.pdf}{.svg}[\LWR@tempone]%
    \StrSubstitute{\LWR@tempone}{.PDF}{.SVG}[\LWR@tempone]%
    \LWR@replaceEPSSVG%
    \xdef\LWR@parsedfilename{\LWR@tempone}%
    \Ginclude@graphics{\detokenize\expandafter{\LWR@tempone}}%
    \endgroup%
    \filename@parse{\LWR@parsedfilename}%
```

Remove doubled // in the directory path, from the 2020/10/01 LaTeX kernel change.

```
    \StrSubstitute{\LWR@parsedfilename}{//}{/}[\LWR@parsedfilename]%

    \LWR@traceinfo{LWR@parsedfilename is \LWR@parsedfilename}%
```

If formatting for a word processor, or if using keepaspectratio, find and set the actual image size, without rotation, using PDF instead of SVG to find the original bounding box:

```
    \ifboolexpr{
        bool {FormatWP} or
        bool {LWR@igkeepaspectratio}
    }{\LWR@ig@useactualimagesize{#1}{#2}{#3}{#4}}{}%
```

Create the HTML reference with the graphicspath, filename, extension, alt tag, style, and class:

```
    \LWR@traceinfo{LWR@includegraphicsb: about to create href}%
    \LWR@href{\LWR@parsedfilename}%
    {% start of href
        \LWR@traceinfo{LWR@includegraphicsb: about to LWR@htmltag}%
        \LWR@htmltag{\LWR@ig@htmltag}%
    }% end of href
```

Return to original page size and font size:

```
    \end{LWR@setvirtualpage}%
```

Clear the single-use alt text:

```
    \gdef\LWR@ThisAltText{}%
    \LWR@traceinfo{LWR@includegraphicsb done}%
}
```

\includegraphics [⟨*key=val*⟩] {⟨*filename*⟩}

Handles width and height, converted to fixed width and heights.

The user should always use no file suffix in the document source.

```
\AtBeginDocument{

\LWR@traceinfo{Patching includegraphics.}

\LetLtxMacro\LWR@origincludegraphics\includegraphics
```

```
\renewrobustcmd*{\includegraphics}
{%
```

This graphic should trigger an HTML paragraph even if alone, so ensure that are doing paragraph handling:

```
\LWR@traceinfo{includegraphics}%
\LWR@ensuredoingapar%
\LWR@includegraphicsb%
}% includegraphics
}% AtBeginDocument
```

§ 316.5 Boxes

`\LWR@rotboxorigin` Holds the origin key letters.

```
\newcommand*{\LWR@rotboxorigin}{}
```

`\LWR@originname` {⟨*letter*⟩}

Given one LaTeX origin key value, translate into an HTML origin word:

```
\newcommand*{\LWR@originname}[1]{%
    \ifthenelse{\equal{#1}{t}}{top}{}%
    \ifthenelse{\equal{#1}{b}}{bottom}{}%
    \ifthenelse{\equal{#1}{c}}{center}{}%
    \ifthenelse{\equal{#1}{l}}{left}{}%
    \ifthenelse{\equal{#1}{r}}{right}{}%
}
```

`\LWR@originnames` {⟨*letters*⟩}

Given one- or two-letter LaTeX origin key values, translate into HTML origin words:

```
\newcommand*{\LWR@originnames}[1]{%
\StrChar{#1}{1}[\LWR@strresult]%
\LWR@originname{\LWR@strresult}
\StrChar{#1}{2}[\LWR@strresult]%
\LWR@originname{\LWR@strresult}
}
```

Handle the `origin` key for `\rotatebox`:

```
\define@key{krotbox}{origin}{%
\renewcommand*{\LWR@rotboxorigin}{#1}%
}
```

These keys are ignored:

```
\define@key{krotbox}{x}{}
\define@key{krotbox}{y}{}
\define@key{krotbox}{units}{}
```

`\rotatebox` [⟨*keyval list*⟩] {⟨*angle*⟩} {⟨*text*⟩}

```
\AtBeginDocument{
```

The HTML version:

```
\NewDocumentCommand{\LWR@HTML@rotatebox}{O{} m +m}{%
```

Reset the origin to “none-given”:

```
\renewcommand*{\LWR@rotboxorigin}{}
```

Process the optional keys, which may set `\LWR@rotateboxorigin`:

```
\setkeys{krotbox}{#1}%
```

Select `inline-block` so that HTML will transform this span:

```
\LWR@htmltagc{%
    span\LWR@indentHTML
    style=\textquotedbl\LWR@indentHTML
    display: inline-block;\LWR@indentHTML
```

If an origin was given, translate and print the origin information:

```
    \ifthenelse{\NOT\equal{\LWR@rotboxorigin}{}}%
      {transform-origin: \LWR@originnames{\LWR@rotboxorigin};\LWR@indentHTML}%
        {}%
```

Print the rotation information:

```
    \LWR@rotstyle{-ms-}{#2}\LWR@indentHTML
    \LWR@rotstyle{-webkit-}{#2}\LWR@indentHTML
    \LWR@rotstyle{}{#2}\textquotedbl\LWR@orignewline%
}\LWR@orignewline%
```

Print the text to be rotated:

```
\begin{LWR@nestspan}%
#3%
```

Close the span:

```
\LWR@htmltagc{/span}%
\end{LWR@nestspan}%
}
```

The high-level interface:

```
\LWR@formatted{rotatebox}

}% AtBeginDocument
```

`\scalebox` {⟨*h-scale*⟩} [⟨*v-scale*⟩] {⟨*text*⟩}

```
\AtBeginDocument{
```

The HTML version:

```
\NewDocumentCommand{\LWR@HTML@scalebox}{m o m}{%
```

Select `inline-block` so that HTML will transform this span:

```
\LWR@htmltagc{%
    span\LWR@indentHTML
    style=\textquotedbl\LWR@indentHTML
    display: inline-block;\LWR@indentHTML
```

Print the scaling information:

```
    \LWR@scalestyle{-ms-}{#1}{\IfNoValueTF{#2}{#1}{#2}}\LWR@indentHTML
    \LWR@scalestyle{-webkit-}{#1}{\IfNoValueTF{#2}{#1}{#2}}\LWR@indentHTML
    \LWR@scalestyle{}{#1}{\IfNoValueTF{#2}{#1}{#2}}
    \textquotedbl\LWR@orignewline
}\LWR@orignewline%
```

Print the text to be scaled:

```
\begin{LWR@nestspan}%
#3%
```

Close the span:

```
\LWR@htmltagc{/span}%
\end{LWR@nestspan}%
}
```

The high-level interface:

```
\LWR@formatted{scalebox}

}% AtBeginDocument
```

`\reflectbox` {⟨*text*⟩}

```
\AtBeginDocument{

\newcommand{\LWR@HTML@reflectbox}[1]{%
    \scalebox{-1}[1]{#1}%
}% \reflectbox

\LWR@formatted{reflectbox}

}% AtBeginDocument
```

`\resizebox` {⟨*h-length*⟩} {⟨*v-length*⟩} {⟨*text*⟩}

Simply prints its text argument.

```
\AtBeginDocument{
```

```
408
409 \NewDocumentCommand{\LWR@HTML@resizebox}{s m m m}{%
410     #4%
411 }
412
413 \LWR@formatted{resizebox}
414
415 }% AtBeginDocument
```

File 209 **lwarp-graphicx.sty**

§ 317 Package graphicx

Pkg graphicx graphicx is emulated.

graphicx loads graphics, which also loads lwarp-graphics, which remembers the original graphics definitions for use inside a `lateximage`, and then patches them `\AtBeginDocument` for HTML output.

lwarp-graphics handles the syntax of either graphics or graphicx.

for HTML output:

```
1 \LWR@ProvidesPackagePass{graphicx}[2020/09/09]
```

File 210 **lwarp-grffile.sty**

§ 318 Package grffile

Pkg grffile

⚠ matching PDF and SVG

grffile is supported as-is. File types known to the browser are displayed, and unknown file types are given a link. Each PDF image for print mode should be accompanied by an SVG, PNG, or JPG version for HTML.

lwarp-grffile now exists as a placeholder since grffile used to be emulated by lwarp, and thus older versions of lwarp-grffile may exist and should be overwritten by this newer version.

for HTML output:

```
1 \LWR@ProvidesPackagePass{grffile}[2017/06/30]
```

File 211 **lwarp-grid.sty**

§ 319 Package grid

Pkg grid grid is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{grid}[2009/06/16]

2 \newenvironment*{gridenv}{}{}
```

File 212 **lwarp-grid-system.sty**

§ 320 Package grid-system

(*Emulates or patches code by* Marcus Bitzl.)

Pkg grid-system grid-system is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{grid-system}[2014/02/16]
```

(\ifdef is in case the older syntax is removed.)

```
\AtBeginEnvironment{Row}{\setlength{\linewidth}{6in}}

\ifdef{\endrow}{
    \AtBeginEnvironment{row}{\setlength{\linewidth}{6in}}
}{}

\renewcommand{\gridsystem@finishcell}{\hspace{\gridsystem@cellsep}}
```

File 213 **lwarp-gridset.sty**

§ 321 Package gridset

Pkg gridset gridset is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{gridset}[2020-02-12]

\newcommand*{\gridbase}{}
\newcommand*{\gridinterval}{}
\newcommand*{\SavePos}[1]{}
\ifLuaTeX
\else
\let\savepos\SavePos
\fi
\newcommand*{\vskipnextgrid}{}
\newcommand*{\thegridinfo}[1]{(thegridinfo)}
\newcommand*{\theposinfo}[1]{(theposinfo)}
\newcommand*{\theypos}[1]{(theypos)}
```

File 214 **lwarp-hang.sty**

§ 322 Package hang

(*Emulates or patches code by* Andreas Nolda.)

Pkg hang hang is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{hang}[2017/02/18]

\newlength{\hangingindent}
\setlength{\hangingindent}{1em}
\newlength{\hangingleftmargin}
\setlength{\hangingleftmargin}{0em}

\newcommand*{\LWR@findhangingleftmargin}{%
\setlength{\LWR@templengthone}{\hangingleftmargin}%
\addtolength{\LWR@templengthone}{\hangingindent}%
}

\newenvironment{hangingpar}
{
    \LWR@findhangingleftmargin%
    \BlockClass[%
        \LWR@print@mbox{margin-left:\LWR@printlength{\LWR@templengthone}} ; %
        \LWR@print@mbox{text-indent:-\LWR@printlength{\hangingindent}}%
    ]%
    {hangingpar}%
}
{\endBlockClass}

\newenvironment{hanginglist}
{%
    \renewcommand*{\LWR@printcloselist}{\LWR@printcloseitemize}%
    \renewcommand*{\LWR@printopenlist}{%
        \LWR@findhangingleftmargin%
        ul style=\textquotedbl%
            \LWR@print@mbox{list-style-type:none;} % extra space
            \LWR@print@mbox{%
                margin-left:\LWR@printlength{\LWR@templengthone}%
            } ; % extra space
            \LWR@print@mbox{%
                text-indent:-\LWR@printlength{\hangingindent}%
            }%
        \textquotedbl%
    }%
    \let\item\LWR@itemizeitem%
    \list{}{}%
}
{\endlist}

\newenvironment{compacthang}
{\hanginglist}
{\endhanginglist}

\newlength{\labeledleftmargin}
\setlength{\labeledleftmargin}{0em}

\newenvironment{labeledpar}[2]
{%
    \BlockClass[%
        \LWR@findhangingleftmargin%
```

```
        \LWR@print@mbox{margin-left:\LWR@printlength{\LWR@templengthone}} ; %
        \LWR@print@mbox{text-indent:-\LWR@printlength{\hangingindent}}%
    ]{labeledpar}#2%
}
{\endBlockClass}

\newenvironment{labeledlist}[1]
{\hanginglist}
{\endhanginglist}

\newenvironment{compactlabel}[1]
{\hanginglist}
{\endhanginglist}
```

File 215 **lwarp-hanging.sty**

§ 323 Package

hanging

Pkg hanging

hanging is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{hanging}[2009/09/02]

\@ifclassloaded{memoir}{
\let\hangpara\relax
\let\hangparas\relax
\let\endhangparas\relax
\let\hangpunct\relax
\let\endhangpunct\relax
}{}
```

\hangpara {⟨*indent*⟩} {⟨*afternum*⟩}

Use hangparas instead.

```
\newcommand*{\hangpara}[2]{}
```

Env hangparas {⟨*indent*⟩} {⟨*afternum*⟩}

```
\newenvironment*{hangparas}[2]
{%
    \BlockClass[%
        \LWR@print@mbox{margin-left:\LWR@printlength{#1}} ; %
        \LWR@print@mbox{text-indent:-\LWR@printlength{#1}}%
    ]%
    {hangingpar}%
}
{\endBlockClass}
```

Env hangpunct

```
\newenvironment*{hangpunct}
{\BlockClass{hangpunct}}
{\endBlockClass}
```

```
\newcommand{\nhpt}{.}
\newcommand{\nhlq}{‘}
\newcommand{\nhrq}{’}
```

File 216 **lwarp-hepunits.sty**

§ 324 Package

hepunits

(*Emulates or patches code by* Andy Buckley.)

Pkg hepunits hepunits is used as-is, and emulated for MathJax.

for HTML output:

```
\LWR@ProvidesPackagePass{hepunits}[2020/04/10]

\begin{warpMathJax}
\LWR@infoprocessingmathjax{hepunits}

\ifx\@HEPopt@sicmds\@yes
\CustomizeMathJax{\newcommand{\micron}{\micro\metre}}
\CustomizeMathJax{\newcommand{\mrad}{\milli\radian}}
\fi

\CustomizeMathJax{\newcommand{\gauss}{\mathrm{G}}}

\CustomizeMathJax{\newcommand{\invcmsq}{\centi\metre\tothe{-2}}}
\CustomizeMathJax{\newcommand{\invcmsqpersecond}{\invcmsq\second\tothe{-1}}}
\CustomizeMathJax{\newcommand{\invcmsqpersec}{\invcmsqpersecond}}

%% (Inverse) cross-sections
\CustomizeMathJax{\newcommand{\invbarn}{\barn\tothe{-1}}}

\ifx\@HEPopt@noprefixcmds\@empty
\CustomizeMathJax{\newcommand{\millibarn}{\milli\barn}}
\CustomizeMathJax{\newcommand{\microbarn}{\micro\barn}}
\CustomizeMathJax{\newcommand{\nanobarn}{\nano\barn}}
\CustomizeMathJax{\newcommand{\picobarn}{\pico\barn}}
\CustomizeMathJax{\newcommand{\femtobarn}{\femto\barn}}
\CustomizeMathJax{\newcommand{\attobarn}{\atto\barn}}
\CustomizeMathJax{\newcommand{\zeptobarn}{\zepto\barn}}
\CustomizeMathJax{\newcommand{\yoctobarn}{\yocto\barn}}
\CustomizeMathJax{\newcommand{\invnanobarn}{\nano\invbarn}}
\CustomizeMathJax{\newcommand{\invpicobarn}{\pico\invbarn}}
\CustomizeMathJax{\newcommand{\invfemtobarn}{\femto\invbarn}}
\CustomizeMathJax{\newcommand{\invattobarn}{\atto\invbarn}}
\CustomizeMathJax{\newcommand{\invzeptobarn}{\zepto\invbarn}}
\CustomizeMathJax{\newcommand{\invyoctobarn}{\yocto\invbarn}}
\CustomizeMathJax{\newcommand{\invnb}{\invnanobarn}}
\CustomizeMathJax{\newcommand{\invpb}{\invpicobarn}}
\CustomizeMathJax{\newcommand{\invfb}{\invfemtobarn}}
\CustomizeMathJax{\newcommand{\invab}{\invattobarn}}
\CustomizeMathJax{\newcommand{\invzb}{\invzeptobarn}}
\CustomizeMathJax{\newcommand{\invyb}{\invyoctobarn}}
\fi
```

```
41
42 \CustomizeMathJax{\newcommand{\electronvoltc}{\electronvolt\per\mathit{c}}}
43 \CustomizeMathJax{\newcommand{\electronvoltcsq}{\electronvolt\per\mathit{c}\squared}}
44 \CustomizeMathJax{\let\eVc\electronvoltc}
45 \CustomizeMathJax{\let\eVcsq\electronvoltcsq}
46
47 \ifx\@HEPopt@noprefixcmds\@empty
48 \CustomizeMathJax{\newcommand{\meV}{\milli\eV}}
49 \CustomizeMathJax{\newcommand{\keV}{\kilo\eV}}
50 \CustomizeMathJax{\newcommand{\MeV}{\mega\eV}}
51 \CustomizeMathJax{\newcommand{\GeV}{\giga\eV}}
52 \CustomizeMathJax{\newcommand{\TeV}{\tera\eV}}
53 \CustomizeMathJax{\newcommand{\meVc}{\milli\eVc}}
54 \CustomizeMathJax{\newcommand{\keVc}{\kilo\eVc}}
55 \CustomizeMathJax{\newcommand{\MeVc}{\mega\eVc}}
56 \CustomizeMathJax{\newcommand{\GeVc}{\giga\eVc}}
57 \CustomizeMathJax{\newcommand{\TeVc}{\tera\eVc}}
58 \CustomizeMathJax{\newcommand{\meVcsq}{\milli\eVcsq}}
59 \CustomizeMathJax{\newcommand{\keVcsq}{\kilo\eVcsq}}
60 \CustomizeMathJax{\newcommand{\MeVcsq}{\mega\eVcsq}}
61 \CustomizeMathJax{\newcommand{\GeVcsq}{\giga\eVcsq}}
62 \CustomizeMathJax{\newcommand{\TeVcsq}{\tera\eVcsq}}
63 \fi
64 \end{warpMathJax}
```

File 217 **lwarp-hhline.sty**

§ 325 Package

hhline

(*Emulates or patches code by* David Carlisle.)

Pkg hhline

hhline is patched for use by lwarp.

Only a rudimentary emulation is provided so far. If the argument contains any = characters, the result is a double \hline. If none, the result is a single \hline.

for HTML output:

```
1 \LWR@ProvidesPackagePass{hhline}[2014/10/28]

2 \newrobustcmd*{\LWR@HTML@hhline}[1]{%
3     \edef\LWR@tempone{\detokenize\expandafter{#1}}%
4     \IfSubStr[1]{\LWR@tempone}{=}{\hline\hline}{\hline}%
5 }
6 % ^^A or:
7 % ^^A \newrobustcmd*{\LWR@HTML@hhline}[1]{\LWR@getmynexttoken}
8
9 \AtBeginDocument{\LWR@expandableformatted{hhline}}
```

For MathJax. A simple \hline is used.

```
10 \begin{warpMathJax}
11 \CustomizeMathJax{\newcommand{\hhline}[1]{\hline}}
12 \end{warpMathJax}
```

File 218 **lwarp-hhtensor.sty**

§ 326 Package

hhtensor

(*Emulates or patches code by* Harald Harders.)

Pkg hhtensor hhtensor is used as-is, and emulated for MathJax.

for HTML output:

```
\LWR@ProvidesPackagePass{hhtensor}[2011/12/29]

\begin{warpMathJax}
\iftensor@bold
  \CustomizeMathJax{\newcommand{\vec}[1]{\boldsymbol{#1}}}
  \CustomizeMathJax{\newcommand{\matr}[1]{\boldsymbol{#1}}}
  \CustomizeMathJax{\newcommand{\tens}[2]{\boldsymbol{#1}}}
\else
  \iftensor@uline
    \CustomizeMathJax{\newcommand{\vec}[1]{\ushort{#1}}}
    \CustomizeMathJax{\newcommand{\matr}[1]{\ushortd{#1}}}
    \CustomizeMathJax{\newcommand{\tens}[2]{
        \underset{
            \raise{.5ex}{\underset{#2}{\sim}}
        }{#1}
    }}
  \else
    \CustomizeMathJax{\newcommand{\matr}[1]{\vec{\vec{#1}}}}
    \CustomizeMathJax{\newcommand{\tens}[2]{
        \underset{
            \raise{.5ex}{\underset{#2}{\sim}}
        }{#1}
    }}
  \fi
\fi
\CustomizeMathJax{\newcommand{\dcdot}{\mathrel{\cdot\mkern 0.0mu \cdot}}}
\CustomizeMathJax{\newcommand{\trans}{{}^{\mathrm{T}}}}
\end{warpMathJax}
```

File 219 **lwarp-hypbmsec.sty**

§ 327 Package

hypbmsec

Pkg hypbmsec hypbmsec is emulated by the lwarp core.

for HTML output:

```
\LWR@ProvidesPackageDrop{hypbmsec}[2016/05/16]
```

File 220 **lwarp-hypcap.sty**

§ 328 Package hypcap

Pkg hypcap hypcap is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{hypcap}[2016/05/16]

\newcommand*{\capstart}{}
\newcommand*{\hypcapspace}{}
\newcommand*{\hypcapredef}[1]{}
\newcommand*{\capstartfalse}{}
\newcommand*{\capstarttrue}{}
```

File 221 **lwarp-hypdestopt.sty**

§ 329 Package hypdestopt

Pkg hypdestopt hypdestopt is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{hypdestopt}[2016/05/21]
```

File 222 **lwarp-hypernat.sty**

§ 330 Package hypernat

Pkg hypernat hypernat is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{hypernat}[2001/07/09]
```

File 223 **lwarp-hyperref.sty**

§ 331 Package hyperref

(*Emulates or patches code by* Sebastian Rahtz, Heiko Oberdiek, The LaTeX3 Project.)

Pkg hyperref hyperref is emulated.

for HTML output:

```
% \LWR@ProvidesPackageDrop{hyperref}% not allowed
% \ProvidesPackage{lwarp-#1-#2}% not allowed
\PackageInfo{lwarp}{%
Using the lwarp HTML version of package ‘hyperref’,\MessageBreak
and discarding options except backref, pagebackref.\MessageBreak
(Not using \protect\ProvidesPackage, so that other packages\MessageBreak
do not attempt to patch lwarp’s version of ‘hyperref’.)\MessageBreak}

\SetupKeyvalOptions{family=LWR@hyperref,prefix=LWR@hyperref@}

```

```
\newcommand{\hypersetup}[1]{\setkeys{LWR@hyperref}{#1}}

\define@key{LWR@hyperref}{a4paper}[]{}
\define@key{LWR@hyperref}{a5paper}[]{}
\define@key{LWR@hyperref}{b5paper}[]{}
\define@key{LWR@hyperref}{letterpaper}[]{}
\define@key{LWR@hyperref}{legalpaper}[]{}
\define@key{LWR@hyperref}{executivepaper}[]{}
\define@key{LWR@hyperref}{implicit}[]{}
\define@key{LWR@hyperref}{draft}[]{}
\define@key{LWR@hyperref}{final}[]{}
\define@key{LWR@hyperref}{setpagesize}[]{}
\define@key{LWR@hyperref}{debug}[]{}
\define@key{LWR@hyperref}{linktocpage}[]{}
\define@key{LWR@hyperref}{linktoc}[]{}
\define@key{LWR@hyperref}{extension}[]{}
\define@key{LWR@hyperref}{verbose}[]{}
\define@key{LWR@hyperref}{typexml}[]{}
\define@key{LWR@hyperref}{raiselinks}[]{}
\define@key{LWR@hyperref}{breaklinks}[]{}
\define@key{LWR@hyperref}{localanchorname}[]{}
\define@key{LWR@hyperref}{pageanchor}[]{}
\define@key{LWR@hyperref}{plainpages}[]{}
\define@key{LWR@hyperref}{naturalnames}[]{}
\define@key{LWR@hyperref}{hypertexnames}[]{}
\define@key{LWR@hyperref}{nesting}[]{}
\define@key{LWR@hyperref}{destlabel}[]{}
\define@key{LWR@hyperref}{unicode}[]{}
\define@key{LWR@hyperref}{pdfencoding}[]{}
\define@key{LWR@hyperref}{psdextra}[]{}
\define@key{LWR@hyperref}{pdfversion}[]{}
\define@key{LWR@hyperref}{dvipdfmx-outline-open}[]{}
\define@key{LWR@hyperref}{driverfallback}[]{}
\define@key{LWR@hyperref}{customdriver}[]{}
\define@key{LWR@hyperref}{hyperfigures}[]{}
\define@key{LWR@hyperref}{hyperfootnotes}[]{}
\define@key{LWR@hyperref}{hyperindex}[]{}
\define@key{LWR@hyperref}{encap}[]{}
\define@key{LWR@hyperref}{colorlinks}[]{}
\define@key{LWR@hyperref}{ocgcolorlinks}[]{}
\define@key{LWR@hyperref}{frenchlinks}[]{}
\define@key{LWR@hyperref}{bookmarks}[]{}
\define@key{LWR@hyperref}{bookmarksopen}[]{}
\define@key{LWR@hyperref}{bookmarksdepth}[]{}
\define@key{LWR@hyperref}{bookmarksopenlevel}[]{}
\define@key{LWR@hyperref}{bookmarkstype}[]{}
\define@key{LWR@hyperref}{bookmarksnumbered}[]{}
\define@key{LWR@hyperref}{CJKbookmarks}[]{}
\define@key{LWR@hyperref}{link}[]{}
\define@key{LWR@hyperref}{anchor}[]{}
\define@key{LWR@hyperref}{cite}[]{}
\define@key{LWR@hyperref}{file}[]{}
\define@key{LWR@hyperref}{url}[]{}
\define@key{LWR@hyperref}{menu}[]{}
\define@key{LWR@hyperref}{run}[]{}
```

```
\define@key{LWR@hyperref}{linkbordercolor}[]{}
\define@key{LWR@hyperref}{anchorbordercolor}[]{}
\define@key{LWR@hyperref}{citebordercolor}[]{}
\define@key{LWR@hyperref}{filebordercolor}[]{}
\define@key{LWR@hyperref}{urlbordercolor}[]{}
\define@key{LWR@hyperref}{menubordercolor}[]{}
\define@key{LWR@hyperref}{runbordercolor}[]{}
\define@key{LWR@hyperref}{pagecolor}[]{}
\define@key{LWR@hyperref}{baseurl}[]{}
\define@key{LWR@hyperref}{linkfileprefix}[]{}
\define@key{LWR@hyperref}{pdfpagetransition}[]{}
\define@key{LWR@hyperref}{pdfpageduration}[]{}
\define@key{LWR@hyperref}{pdfpagehidden}[]{}
\define@key{LWR@hyperref}{pagebordercolor}[]{}
\define@key{LWR@hyperref}{allbordercolors}[]{}
\define@key{LWR@hyperref}{pdfhighlight}[]{}
\define@key{LWR@hyperref}{pdfborder}[]{}
\define@key{LWR@hyperref}{pdfborderstyle}[]{}
\define@key{LWR@hyperref}{pdfprintpagerange}[]{}
\define@key{LWR@hyperref}{pdfusetitle}[]{}
\define@key{LWR@hyperref}{pdftitle}[]{}
\define@key{LWR@hyperref}{pdfauthor}[]{}
\define@key{LWR@hyperref}{pdfproducer}[]{}
\define@key{LWR@hyperref}{pdfcreator}[]{}
\define@key{LWR@hyperref}{addtopdfcreator}[]{}
\define@key{LWR@hyperref}{pdfcreationdate}[]{}
\define@key{LWR@hyperref}{pdfmoddate}[]{}
\define@key{LWR@hyperref}{pdfsubject}[]{}
\define@key{LWR@hyperref}{pdfkeywords}[]{}
\define@key{LWR@hyperref}{pdftrapped}[]{}
\define@key{LWR@hyperref}{pdfinfo}[]{}
\define@key{LWR@hyperref}{pdfview}[]{}
\define@key{LWR@hyperref}{pdflinkmargin}[]{}
\define@key{LWR@hyperref}{pdfstartpage}[]{}
\define@key{LWR@hyperref}{pdfstartview}[]{}
\define@key{LWR@hyperref}{pdfremotestartview}[]{}
\define@key{LWR@hyperref}{pdfpagescrop}[]{}
\define@key{LWR@hyperref}{pdftoolbar}[]{}
\define@key{LWR@hyperref}{pdfmenubar}[]{}
\define@key{LWR@hyperref}{pdfwindowui}[]{}
\define@key{LWR@hyperref}{pdffitwindow}[]{}
\define@key{LWR@hyperref}{pdfcenterwindow}[]{}
\define@key{LWR@hyperref}{pdfdisplaydoctitle}[]{}
\define@key{LWR@hyperref}{pdfa}[]{}
\define@key{LWR@hyperref}{pdfnewwindow}[]{}
\define@key{LWR@hyperref}{pdflang}[]{}
\define@key{LWR@hyperref}{pdfpagelabels}[]{}
\define@key{LWR@hyperref}{pdfescapeform}[]{}
\define@key{LWR@hyperref}{english}[]{}
\define@key{LWR@hyperref}{UKenglish}[]{}
\define@key{LWR@hyperref}{british}[]{}
\define@key{LWR@hyperref}{USenglish}[]{}
\define@key{LWR@hyperref}{american}[]{}
\define@key{LWR@hyperref}{german}[]{}
\define@key{LWR@hyperref}{austrian}[]{}
```

```
\define@key{LWR@hyperref}{ngerman}[]{}
\define@key{LWR@hyperref}{naustrian}[]{}
\define@key{LWR@hyperref}{russian}[]{}
\define@key{LWR@hyperref}{brazil}[]{}
\define@key{LWR@hyperref}{brazilian}[]{}
\define@key{LWR@hyperref}{portuguese}[]{}
\define@key{LWR@hyperref}{spanish}[]{}
\define@key{LWR@hyperref}{catalan}[]{}
\define@key{LWR@hyperref}{afrikaans}[]{}
\define@key{LWR@hyperref}{french}[]{}
\define@key{LWR@hyperref}{frenchb}[]{}
\define@key{LWR@hyperref}{francais}[]{}
\define@key{LWR@hyperref}{acadian}[]{}
\define@key{LWR@hyperref}{canadien}[]{}
\define@key{LWR@hyperref}{italian}[]{}
\define@key{LWR@hyperref}{magyar}[]{}
\define@key{LWR@hyperref}{hungarian}[]{}
\define@key{LWR@hyperref}{greek}[]{}
\define@key{LWR@hyperref}{dutch}[]{}
\define@key{LWR@hyperref}{tex4ht}[]{}
\define@key{LWR@hyperref}{pdftex}[]{}
\define@key{LWR@hyperref}{luatex}[]{}
\define@key{LWR@hyperref}{nativepdf}[]{}
\define@key{LWR@hyperref}{dvipdfm}[]{}
\define@key{LWR@hyperref}{dvipdfmx}[]{}
\define@key{LWR@hyperref}{xetex}[]{}
\define@key{LWR@hyperref}{pdfmark}[]{}
\define@key{LWR@hyperref}{dvips}[]{}
\define@key{LWR@hyperref}{hypertex}[]{}
\define@key{LWR@hyperref}{vtex}[]{}
\define@key{LWR@hyperref}{vtexpdfmark}[]{}
\define@key{LWR@hyperref}{dviwindo}[]{}
\define@key{LWR@hyperref}{dvipsone}[]{}
\define@key{LWR@hyperref}{textures}[]{}
\define@key{LWR@hyperref}{latex2html}[]{}
\define@key{LWR@hyperref}{ps2pdf}[]{}
\define@key{LWR@hyperref}{vietnamese}[]{}
\define@key{LWR@hyperref}{vietnam}[]{}
\define@key{LWR@hyperref}{arabic}[]{}
\define@key{LWR@hyperref}{hidelinks}[]{}
\define@key{LWR@hyperref}{draft}[]{}
\define@key{LWR@hyperref}{nolinks}[]{}
\define@key{LWR@hyperref}{final}[]{}
\define@key{LWR@hyperref}{pdfa}[]{}
\define@key{LWR@hyperref}{pdfversion}[]{}
\define@key{LWR@hyperref}{typexml}[]{}
\define@key{LWR@hyperref}{tex4ht}[]{}
\define@key{LWR@hyperref}{pdftex}[]{}
\define@key{LWR@hyperref}{nativepdf}[]{}
\define@key{LWR@hyperref}{dvipdfm}[]{}
\define@key{LWR@hyperref}{dvipdfmx}[]{}
\define@key{LWR@hyperref}{dvipdfmx-outline-open}[]{}
\define@key{LWR@hyperref}{pdfmark}[]{}
\define@key{LWR@hyperref}{dvips}[]{}
\define@key{LWR@hyperref}{hypertex}[]{}
```

```
\define@key{LWR@hyperref}{vtex}[]{}
\define@key{LWR@hyperref}{vtexpdfmark}[]{}
\define@key{LWR@hyperref}{dviwindo}[]{}
\define@key{LWR@hyperref}{dvipsone}[]{}
\define@key{LWR@hyperref}{textures}[]{}
\define@key{LWR@hyperref}{latex2html}[]{}
\define@key{LWR@hyperref}{ps2pdf}[]{}
\define@key{LWR@hyperref}{xetex}[]{}
\define@key{LWR@hyperref}{driverfallback}[]{}
\define@key{LWR@hyperref}{customdriver}[]{}
\define@key{LWR@hyperref}{pdfversion}[]{}
\define@key{LWR@hyperref}{bookmarks}[]{}
\define@key{LWR@hyperref}{ocgcolorlinks}[]{}
\define@key{LWR@hyperref}{colorlinks}[]{}
\define@key{LWR@hyperref}{frenchlinks}[]{}
\define@key{LWR@hyperref}{backref}[]{}
\define@key{LWR@hyperref}{pagebackref}[]{}
\define@key{LWR@hyperref}{destlabel}[]{}
\define@key{LWR@hyperref}{pdfpagescrop}[]{}
\define@key{LWR@hyperref}{pdfpagemode}[]{}
\define@key{LWR@hyperref}{pdfnonfullscreenpagemode}[]{}
\define@key{LWR@hyperref}{pdfdirection}[]{}
\define@key{LWR@hyperref}{pdfviewarea}[]{}
\define@key{LWR@hyperref}{pdfviewclip}[]{}
\define@key{LWR@hyperref}{pdfprintarea}[]{}
\define@key{LWR@hyperref}{pdfprintclip}[]{}
\define@key{LWR@hyperref}{pdfprintscaling}[]{}
\define@key{LWR@hyperref}{pdfduplex}[]{}
\define@key{LWR@hyperref}{pdfpicktraybypdfsize}[]{}
\define@key{LWR@hyperref}{pdfprintpagerange}[]{}
\define@key{LWR@hyperref}{pdfnumcopies}[]{}
\define@key{LWR@hyperref}{pdfstartview}[]{}
\define@key{LWR@hyperref}{pdfstartpage}[]{}
\define@key{LWR@hyperref}{pdftoolbar}[]{}
\define@key{LWR@hyperref}{pdfmenubar}[]{}
\define@key{LWR@hyperref}{pdfwindowui}[]{}
\define@key{LWR@hyperref}{pdffitwindow}[]{}
\define@key{LWR@hyperref}{pdfcenterwindow}[]{}
\define@key{LWR@hyperref}{pdfdisplaydoctitle}[]{}
\define@key{LWR@hyperref}{pdfpagelayout}[]{}
\define@key{LWR@hyperref}{pdflang}[]{}
\define@key{LWR@hyperref}{baseurl}[]{}
\define@key{LWR@hyperref}{pdfusetitle}[]{}
\define@key{LWR@hyperref}{pdfpagelabels}[]{}
\define@key{LWR@hyperref}{hyperfootnotes}[]{}
\define@key{LWR@hyperref}{hyperfigures}[]{}
\define@key{LWR@hyperref}{hyperindex}[]{}
\define@key{LWR@hyperref}{encap}[]{}
\define@key{LWR@hyperref}{linkcolor}[]{}
\define@key{LWR@hyperref}{anchorcolor}[]{}
\define@key{LWR@hyperref}{citecolor}[]{}
\define@key{LWR@hyperref}{filecolor}[]{}
\define@key{LWR@hyperref}{urlcolor}[]{}
\define@key{LWR@hyperref}{menucolor}[]{}
\define@key{LWR@hyperref}{runcolor}[]{}
```

```
\define@key{LWR@hyperref}{allcolors}[]{}

\DeclareStringOption[false]{backref}[section]

\DeclareBoolOption{pagebackref}

\DeclareDefaultOption{}

\ProcessKeyvalOptions*\relax
```

Maybe load backref:

```
\ifdefstring{\LWR@hyperref@backref}{section}
    {\RequirePackage{backref}}
    {}

\ifdefstring{\LWR@hyperref@backref}{slide}
    {\RequirePackage{backref}}
    {}

\ifdefstring{\LWR@hyperref@backref}{page}
    {\RequirePackage{backref}}
    {}

\ifLWR@hyperref@pagebackref
    \RequirePackage{backref}
\fi


\LetLtxMacro\href\LWR@href
\LetLtxMacro\nolinkurl\LWR@nolinkurl
\LetLtxMacro\url\LWR@url
\LetLtxMacro\phantomsection\LWR@phantomsection


\newcommand*{\hyperbaseurl}[1]{}
```

`\hyperimage` {⟨*URL*⟩} {⟨*alt text*⟩}

Insert an image with alt text:

```
\NewDocumentCommand{\LWR@hyperimageb}{m +m}{%
    \LWR@ensuredoingapar%
    \def\LWR@templink{#1}%
    \@onelevel@sanitize\LWR@templink%
    \LWR@htmltag{%
        img src=\textquotedbl\LWR@templink\textquotedbl\ %
        alt=\textquotedbl#2\textquotedbl\ %
        class=\textquotedbl{}hyperimage\textquotedbl%
    }%
    \LWR@ensuredoingapar%
    \endgroup%
}

\newrobustcmd*{\hyperimage}{%
    \begingroup%
    \LWR@linkcatcodes%
```

```
    \LWR@hyperimageb%
}
```

`\hyperdef` {⟨*1: category*⟩} {⟨*2: name*⟩} {⟨*3: text*⟩}

Creates an HTML anchor to `category.name` with the given text.

```
\NewDocumentCommand{\LWR@hyperdefb}{m m +m}{%
    \LWR@ensuredoingapar%
    \LWR@label@createtag{#1.#2}%
    #3%
    \endgroup%
}

\newcommand*{\hyperdef}{%
    \begingroup%
    \LWR@linkcatcodes%
    \LWR@hyperdefb%
}
```

`\LWR@hyperrefb` {⟨*1: URL*⟩} {⟨*2: category*⟩} {⟨*3: name*⟩} {⟨*4: text*⟩}

Creates an HTML link to `URL#category.name` with the given text.

To avoid nested links, `\ref` is temporarily redefined to the print version.

```
\newcommand{\LWR@hyperreffinish}[1]{%
    \begingroup%
    \RenewDocumentCommand{\ref}{s m}{\LWR@print@ref{##2}}%
   #1%
    \endgroup%
    \LWR@htmltag{/a}%
}

\newcommand*{\LWR@hyperrefbb}[3]{%
    \LWR@htmltag{%
        a href=\textquotedbl%
            \detokenize\expandafter{#1}\LWR@hashmark%
            \detokenize\expandafter{#2}.\detokenize\expandafter{#3}%
        \textquotedbl%
        \LWR@addlinktitle%
    }%
    \endgroup%
    \LWR@hyperreffinish%
}

\newrobustcmd*{\LWR@hyperrefb}{%
    \begingroup%
    \LWR@linkcatcodes%
    \LWR@hyperrefbb%
}
```

`\LWR@hyperrefc` [⟨*label*⟩] {⟨*text*⟩}

Creates text as an HTML link to the LaTeX label.

```
\NewDocumentCommand{\LWR@hyperrefcb}{O{label}}{%
    \LWR@startref{#1}%
    \endgroup%
    \LWR@hyperreffinish%
}

\newcommand*{\LWR@hyperrefc}{%
    \begingroup%
    \LWR@linkcatcodes%
    \LWR@hyperrefcb%
}
```

\hyperref {⟨*1: URL*⟩} {⟨*2: category*⟩} {⟨*3: name*⟩} {⟨*4: text*⟩} — or — [⟨*1: label*⟩] {⟨*2: text*⟩}

```
\DeclareRobustCommand*{\hyperref}{%
    \LWR@ensuredoingapar%
    \@ifnextchar[\LWR@hyperrefc\LWR@hyperrefb%
}
```

\hypertarget {⟨*name*⟩} {⟨*text*⟩}

Creates an anchor to name with the given text.

```
\NewDocumentCommand{\LWR@hypertargetb}{m +m}{%
    \label{LWR-ht-#1}%
    #2%
    \endgroup%
}

\newcommand*{\hypertarget}{%
    \begingroup%
    \LWR@linkcatcodes%
    \LWR@hypertargetb%
}
```

\hyperlink {⟨*name*⟩} {⟨*text*⟩}

Creates a link to the anchor created by hypertarget, with the given link text.

Declared because also defined by memoir.

```
\DeclareDocumentCommand{\LWR@hyperlinkb}{m}{%
    \ifbool{LWR@insidemathcomment}%
        {\endgroup}%
        {\LWR@hyperrefcb[LWR-ht-#1]}%
}

\DeclareDocumentCommand{\hyperlink}{}{%
    \LWR@ensuredoingapar%
    \begingroup%
    \LWR@linkcatcodes%
    \LWR@hyperlinkb%
}
```

\autoref * {⟨*label*⟩}

For HTML, \cleveref is used instead.

```
\NewDocumentCommand{\autoref}{s m}{%
    \IfBooleanTF{#1}{\ref{#2}}{\cref{#2}}%
}
```

\autopageref {⟨*label*⟩}

For HTML, \cleveref is used instead.

```
\NewDocumentCommand{\autopageref}{s m}{%
    \IfBooleanTF{#1}{\cpageref{#2}}{\cref{#2}}%
}
```

Default names:

```
\def\equationautorefname{Equation}%
\def\footnoteautorefname{footnote}%
\def\itemautorefname{item}%
\def\figureautorefname{Figure}%
\def\tableautorefname{Table}%
\def\partautorefname{Part}%
\def\appendixautorefname{Appendix}%
\def\chapterautorefname{chapter}%
\def\sectionautorefname{section}%
\def\subsectionautorefname{subsection}%
\def\subsubsectionautorefname{subsubsection}%
\def\paragraphautorefname{paragraph}%
\def\subparagraphautorefname{subparagraph}%
\def\FancyVerbLineautorefname{line}%
\def\theoremautorefname{Theorem}%
\def\pageautorefname{page}%
```

\pdfstringdef {⟨*macroname*⟩} {⟨*TEXstring*⟩}

```
\newcommand{\pdfstringdef}[2]{}
```

\pdfbookmark [⟨*level*⟩] {⟨*text*⟩} {⟨*name*⟩}

```
\newcommand{\pdfbookmark}[3][]{}
```

\currentpdfbookmark {⟨*text*⟩} {⟨*name*⟩}

```
\newcommand{\currentpdfbookmark}[2]{}
```

\subpdfbookmark {⟨*text*⟩} {⟨*name*⟩}

```
\newcommand{\subpdfbookmark}[2]{}
```

\belowpdfbookmark {⟨*text*⟩} {⟨*name*⟩}

```
\newcommand{\belowpdfbookmark}[2]{}
```

\texorpdfstring {⟨*TEXstring*⟩} {⟨*PDFstring*⟩}

```
\let\texorpdfstring\relax
\newcommand{\texorpdfstring}[2]{#1}
```

{⟨*commands*⟩}

\pdfstringdefDisableCommands

```
\newcommand{\pdfstringdefDisableCommands}[1]{}
```

\hypercalcbp {⟨*dimen*⟩} From hyperref.

```
\def\hypercalcbp#1{%
    \strip@pt\dimexpr 0.99626401\dimexpr(#1)\relax\relax
}%
```

\Acrobatmenu {⟨*menuoption*⟩} {⟨*text*⟩}

```
\newcommand{\Acrobatmenu}[2]{}
```

\TextField [⟨*parameters*⟩] {⟨*label*⟩}

```
\DeclareRobustCommand{\TextField}[2][]{}
```

\CheckBox [⟨*parameters*⟩] {⟨*label*⟩}

```
\DeclareRobustCommand{\CheckBox}[2][]{}
```

\ChoiceMenu [⟨*parameters*⟩] {⟨*label*⟩} {⟨*choices*⟩}

```
\DeclareRobustCommand{\ChoiceMenu}[3][]{}
```

\PushButton [⟨*parameters*⟩] {⟨*label*⟩}

```
\DeclareRobustCommand{\PushButton}[2][]{}
```

\Submit [⟨*parameters*⟩] {⟨*label*⟩}

```
\DeclareRobustCommand{\Submit}[2][]{}
```

\Reset [⟨*parameters*⟩] {⟨*label*⟩}

```
\DeclareRobustCommand{\Reset}[2][]{}
```

\Gauge [⟨*parameters*⟩] {⟨*label*⟩}

```
\DeclareRobustCommand{\Gauge}[2][]{}
```

\LayoutTextField {⟨*label*⟩} {⟨*field*⟩}

```
\newcommand*{\LayoutTextField}[2]{}
```

\LayoutChoiceField {⟨*label*⟩} {⟨*field*⟩}

```
397 \newcommand*{\LayoutChoiceField}[2]{}
```

\LayoutCheckField {⟨*label*⟩} {⟨*field*⟩}

```
398 \newcommand*{\LayoutCheckField}[2]{}
```

\MakeRadioField {⟨*width*⟩} {⟨*height*⟩}

```
399 \newcommand*{\MakeRadioField}[2]{}
```

\MakeCheckField {⟨*width*⟩} {⟨*height*⟩}

```
400 \newcommand*{\MakeCheckField}[2]{}
```

\MakeTextField {⟨*width*⟩} {⟨*height*⟩}

```
401 \newcommand*{\MakeTextField}[2]{}
```

\MakeChoiceField {⟨*width*⟩} {⟨*height*⟩}

```
402 \newcommand*{\MakeChoiceField}[2]{}
```

\MakeFieldButton {⟨*text*⟩}

```
403 \newcommand{\MakeFieldButton}[1]{}
```

File 224 **lwarp-hyperxmp.sty**

§ 332 Package

hyperxmp

Pkg hyperxmp hyperxmp is ignored.

for HTML output: Discard all options for lwarp-hyperxmp:

```
1 \LWR@ProvidesPackageDrop{hyperxmp}[2018/11/27]
2
3 \define@key{LWR@hyperref}{pdfdate}[]{}
4 \define@key{LWR@hyperref}{pdfmetadate}[]{}
5 \define@key{LWR@hyperref}{pdfcopyright}[]{}
6 \define@key{LWR@hyperref}{pdftype}[]{}
7 \define@key{LWR@hyperref}{pdflicenseurl}[]{}
8 \define@key{LWR@hyperref}{pdfauthortitle}[]{}
9 \define@key{LWR@hyperref}{pdfcaptionwriter}[]{}
10 \define@key{LWR@hyperref}{pdfmetalang}[]{}
11 \define@key{LWR@hyperref}{pdfapart}[]{}
12 \define@key{LWR@hyperref}{pdfaconformance}[]{}
13 \define@key{LWR@hyperref}{pdfuapart}[]{}
14 \define@key{LWR@hyperref}{pdfxstandard}[]{}
```

```
\define@key{LWR@hyperref}{pdfsource}[]{}
\define@key{LWR@hyperref}{pdfdocumentid}[]{}
\define@key{LWR@hyperref}{pdfinstanceid}[]{}
\define@key{LWR@hyperref}{pdfversionid}[]{}
\define@key{LWR@hyperref}{pdfrendition}[]{}
\define@key{LWR@hyperref}{pdfpublication}[]{}
\define@key{LWR@hyperref}{pdfpubtype}[]{}
\define@key{LWR@hyperref}{pdfbytes}[]{}
\define@key{LWR@hyperref}{pdfnumpages}[]{}
\define@key{LWR@hyperref}{pdfissn}[]{}
\define@key{LWR@hyperref}{pdfeissn}[]{}
\define@key{LWR@hyperref}{pdfisbn}[]{}
\define@key{LWR@hyperref}{pdfbookedition}[]{}
\define@key{LWR@hyperref}{pdfpublisher}[]{}
\define@key{LWR@hyperref}{pdfvolumenum}[]{}
\define@key{LWR@hyperref}{pdfissuenum}[]{}
\define@key{LWR@hyperref}{pdfpagerange}[]{}
\define@key{LWR@hyperref}{pdfdoi}[]{}
\define@key{LWR@hyperref}{pdfurl}[]{}
\define@key{LWR@hyperref}{pdfidentifier}[]{}
\define@key{LWR@hyperref}{pdfsubtitle}[]{}
\define@key{LWR@hyperref}{pdfpubstatus}[]{}
\define@key{LWR@hyperref}{pdfcontactaddress}[]{}
\define@key{LWR@hyperref}{pdfcontactcity}[]{}
\define@key{LWR@hyperref}{pdfcontactregion}[]{}
\define@key{LWR@hyperref}{pdfcontactpostcode}[]{}
\define@key{LWR@hyperref}{pdfcontactcountry}[]{}
\define@key{LWR@hyperref}{pdfcontactphone}[]{}
\define@key{LWR@hyperref}{pdfcontactemail}[]{}
\define@key{LWR@hyperref}{pdfcontacturl}[]{}
\define@key{LWR@hyperref}{keeppdfinfo}[]{}
\define@key{LWR@hyperref}{pdfauthor}[]{}
\define@key{LWR@hyperref}{pdfkeywords}[]{}
```

File 225 **lwarp-hyphenat.sty**

§ 333 Package

hyphenat

Pkg hyphenat

hyphenat is emulated during HTML output, while the print-mode version is used inside a latexmage.

for HTML output:

```
\LWR@ProvidesPackagePass{hyphenat}[2009/09/02]

\LetLtxMacro\LWRHYNAT@origtextnhtt\textnhtt
\LetLtxMacro\LWRHYNAT@orignhttfamily\nhttfamily
\LetLtxMacro\LWRHYNAT@orignohyphens\nohyphens
\LetLtxMacro\LWRHYNAT@origbshyp\bshyp
\LetLtxMacro\LWRHYNAT@origfshyp\fshyp
\LetLtxMacro\LWRHYNAT@origdothyp\dothyp
\LetLtxMacro\LWRHYNAT@origcolonhyp\colonhyp
\LetLtxMacro\LWRHYNAT@orighyp\hyp

\LetLtxMacro\textnhtt\texttt
```

```
\LetLtxMacro\nhttfamily\ttfamily

\renewcommand{\nohyphens}[1]{#1}
\renewrobustcmd{\bshyp}{%
    \ifmmode\backslash\else\textbackslash\fi%
}
\renewrobustcmd{\fshyp}{/}
\renewrobustcmd{\dothyp}{.}
\renewrobustcmd{\colonhyp}{:}
\renewrobustcmd{\hyp}{-}

\appto\LWR@restoreorigformatting{%
\LetLtxMacro\textnhtt\LWRHYNAT@origtextnhtt%
\LetLtxMacro\nhttfamily\LWRHYNAT@orignhttfamily%
\LetLtxMacro\nohyphens\LWRHYNAT@orignohyphens%
\LetLtxMacro\bshyp\LWRHYNAT@origbshyp%
\LetLtxMacro\fshyp\LWRHYNAT@origfshyp%
\LetLtxMacro\dothyp\LWRHYNAT@origdothyp%
\LetLtxMacro\colonhyp\LWRHYNAT@origcolonhyp%
\LetLtxMacro\hyp\LWRHYNAT@orighyp%
}
```

File 226 **lwarp-idxlayout.sty**

§ 334 Package

idxlayout

(*Emulates or patches code by* Thomas Titz.)

Pkg idxlayout idxlayout is emulated.

for HTML output: Discard all options for lwarp-idxlayout:

```
\LWR@ProvidesPackageDrop{idxlayout}[2012/03/30]

\newcommand{\LWR@indexprenote}{}
```

\AtBeginDocument to help with package load order.

```
\AtBeginDocument{
    \preto\printindex{

    \LWR@maybe@orignewpage
    \LWR@startpars

    \LWR@indexprenote

    }
}

\newcommand{\setindexprenote}[1]{\renewcommand{\LWR@indexprenote}{#1}}
\newcommand*{\noindexprenote}{\renewcommand{\LWR@indexprenote}{}}

\newcommand{\idxlayout}[1]{}
```

```
\newcommand*{\indexfont}{}
\newcommand*{\indexjustific}{}
\newcommand*{\indexsubsdelim}{}
\newcommand*{\indexstheadcase}{}
```

File 227 **lwarp-ifoddpage.sty**

§ 335 Package

ifoddpage

(*Emulates or patches code by* Martin Scharrer.)

Pkg ifoddpage ifoddpage is emulated.

for HTML output: Discard all options for lwarp-ifoddpage:

```
\LWR@ProvidesPackageDrop{ifoddpage}[2016/04/23]

\newif\ifoddpage

\newif\ifoddpageoroneside

\DeclareRobustCommand{\checkoddpage}{\oddpagetrue\oddpageoronesidetrue}

\def\oddpage@page{1}

\def\@ifoddpage{%
        \expandafter\@firstoftwo
}

\def\@ifoddpageoroneside{%
        \expandafter\@firstoftwo
}
```

File 228 **lwarp-imakeidx.sty**

§ 336 Package

imakeidx

(*Emulates or patches code by* Enrico Gregorio.)

Pkg imakeidx imakeidx is patched for use by lwarp.

letter headings When using *makeindex*, to match the print and HTML output's display of index letter headings, specify the `lwarp.ist` style:

```
\makeindex[options={-s lwarp.ist}]
```

(For HTML the `lwarp.ist` style is used automatically, which displays letter headings. When using *xindy* the default style also displays letter headings.)

index setup See section 8.6.18 for how to setup *lwarpmk* to process the indexes with imakeidx, both with and without shell escape.

for HTML output:

```
\LWR@ProvidesPackagePass{imakeidx}[2016/10/15]
```

Use the new HTML suffix:

```
\catcode`\_=12%
\define@key{imki}{name}{\def\imki@name{#1_html}}
\catcode`\_=8%
```

\printindex The HTML version of \printindex:

```
\catcode`\_=12%

\renewcommand*{\printindex}[1][\imki@jobname]{%
\LWR@maybe@orignewpage%
\LWR@startpars%
\ifstrequal{#1}{\imki@jobname}{%
  \@ifundefined{#1@idxfile}{%
        \imki@error{#1}%
    }{%
        \imki@putindex{#1}%
    }%
}{%
 \@ifundefined{#1_html@idxfile}{\imki@error{#1_html}}{\imki@putindex{#1_html}}%
}%
}

\catcode`\_=8%
```

\@index The HTML version of \@index:

```
\catcode`\_=12%

\def\@index[#1]{%
    \ifstrequal{#1}{\imki@jobname}%
    {%
        \@ifundefined{#1@idxfile}%
        {%
            \PackageWarning{lwarp-imakeidx}{Undefined index file `#1'}%
            \begingroup
            \@sanitize
            \imki@nowrindex%
        }%
        {%
            \edef\@idxfile{#1}%
            \begingroup
            \@sanitize
            \@wrindex\@idxfile%
        }%
    }%
    {%
        \@ifundefined{#1_html@idxfile}%
        {%
            \PackageWarning{lwarp-imakeidx}{Undefined index file `#1_html'}%
            \begingroup
            \@sanitize
```

```
            \imki@nowrindex%
        }%
        {%
            \edef\@idxfile{#1_html}%
            \begingroup
            \@sanitize
            \@wrindex\@idxfile%
        }%
    }%
}

\catcode`\_=8%
```

\item
\subitem
\subsubitem

HTML versions of \item, etc.:

```
\appto\theindex{%
    \let\item\LWR@indexitem%
    \let\subitem\LWR@indexsubitem%
    \let\subsubitem\LWR@indexsubsubitem%
}
```

\imki@wrindexentrysplit {⟨*file*⟩} {⟨*entry*⟩} {⟨*page*⟩}
\imki@wrindexentryunique {⟨*file*⟩} {⟨*entry*⟩} {⟨*page*⟩}

While writing index entries, adds an HTML label, and writes the label's index instead of the page number:

```
\renewcommand\imki@wrindexentrysplit[3]{%
\addtocounter{LWR@autoindex}{1}%
\label{LWRindex-\arabic{LWR@autoindex}}%
  \expandafter\protected@write\csname#1@idxfile\endcsname{}%
    {\string\indexentry{#2}{\arabic{LWR@autoindex}}}%
}

\renewcommand\imki@wrindexentryunique[3]{%
\addtocounter{LWR@autoindex}{1}%
\label{LWRindex-\arabic{LWR@autoindex}}%
  \protected@write\@indexfile{}%
    {\string\indexentry[#1]{#2}{\arabic{LWR@autoindex}}}%
}

\def\imki@wrindexsplit#1#2{%
\imki@wrindexentrysplit{#1}{#2}{\thepage}%
\endgroup\imki@showidxentry{#1}{#2}%
  \@esphack%
}

\def\imki@wrindexunique#1#2{%
\imki@wrindexentryunique{#1}{#2}{\thepage}%
\endgroup\imki@showidxentry{#1}{#2}%
  \@esphack%
  }

```

\LWR@imki@setxdydefopts

Sets the *xindy* HTML options, ignoring the user's settings.

```
\newcommand*{\LWR@imki@setxdydefopts}{%
    \edef\imki@options{ \space %
        -M \space \LWR@xindyStyle\space %
        -L \space \LWR@xindyLanguage\space %
        -C \space \LWR@xindyCodepage\space %
    }%
}
```

\LWR@imki@setdefopts {⟨*user options*⟩}

Sets the HTML options, added to the user's settings, depending on whether *makeindex* or *xindy* are used.

For *makeindex*, the user's choice is ignored, and only the lwarp version is used. (Only one style at a time is possible.)

For *xindy*, multiple modules may be specified, and the lwarp version is appended.

```
\newcommand*{\LWR@imki@setdefopts}[1]{%
\ifblank{#1}{%
    \edef\imki@options{\space -s \space \LWR@makeindexStyle \space}%
    \ifdefstring{\imki@progdefault}{xindy}{\LWR@imki@setxdydefopts}{}%
    \ifdefstring{\imki@progdefault}{texindy}{\LWR@imki@setxdydefopts}{}%
    \ifdefstring{\imki@progdefault}{truexindy}{\LWR@imki@setxdydefopts}{}%
}{%
    \edef\imki@options{\space #1 \space}%
}%
}
```

\imki@makeindex Use the new HTML options:

```
\xpatchcmd{\imki@makeindex}
    {\let\imki@options\space}
    {\LWR@imki@setdefopts{}}%
    {}
    {\LWR@patcherror{imakeidx}{makeindex}}
```

Use the new HTML options.

```
\define@key{imki}{options}{\LWR@imki@setdefopts{#1}}
```

\imki@resetdefaults Use the new HTML options:

```
\xpatchcmd{\imki@resetdefaults}
    {\def\imki@options{ }}
    {\LWR@imki@setdefopts{}}
    {}
    {\LWR@patcherror{imakeidx}{resetdefaults}}
```

`theindex` was already defined `\AtBeginDocument` by the lwarp core, so it must be redefined here similarly, but patched for imakeidx:

Env theindex

```
\AtBeginDocument{
\renewenvironment*{theindex}{%
    \imki@maybeaddtotoc
     \imki@indexlevel{\indexname}
    \let\item\LWR@indexitem%
    \let\subitem\LWR@indexsubitem%
    \let\subsubitem\LWR@indexsubsubitem%
}{}
}% AtBeginDocument
```

Update to the new defaults:

```
\imki@resetdefaults
```

Update to the new patches:

`\AtBeginDocument` is because `\@wrindex` is previously defined as `\AtBeginDocument` in the lwarp core.

```
\ifimki@splitindex
  \let\imki@startidx\imki@startidxunique
  \AtBeginDocument{\let\@wrindex\imki@wrindexunique}
  \let\imki@putindex\imki@putindexunique
  \let\imki@wrindexentry\imki@wrindexentryunique
  \let\imki@startidxsplit\@undefined
  \let\imki@wrindexsplit\@undefined
  \let\imki@putindexsplit\@undefined
\else
  \let\imki@startidx\imki@startidxsplit
  \AtBeginDocument{\let\@wrindex\imki@wrindexsplit}
  \let\imki@putindex\imki@putindexsplit
  \let\imki@wrindexentry\imki@wrindexentrysplit
  \let\imki@startidxunique\@undefined
  \let\imki@wrindexunique\@undefined
  \let\imki@putindexunique\@undefined
\fi
```

File 229 **lwarp-impnattypo.sty**

§ 337 Package impnattypo

Pkg impnattypo impnattypo is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{impnattypo}[2019/03/04]
```

File 230 **lwarp-index.sty**

§ 338 Package index

(*Emulates or patches code by* David M. Jones.)

Pkg index index is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{index}[2004/01/20]
```

Use \theLWR@autoindex instead of \thepage. \@tempswatrue is used to force an immediate write to the index file instead of waiting until the end of the page.

```
\xpatchcmd{\newindex}
    {\x@newindex[thepage]}
    {%
        \@tempswatrue%
        \x@newindex[theLWR@autoindex]%
    }
    {}
    {\LWR@patcherror{index}{newindex}}

\xpatchcmd{\renewindex}
    {\x@renewindex[thepage]}
    {%
        \@tempswatrue%
        \x@renewindex[theLWR@autoindex]%
    }
    {}
    {\LWR@patcherror{index}{renewindex}}
```

Patched to set a new autoindex:

```
\xpatchcmd{\@wrindex}
    {\begingroup}
    {%
        \addtocounter{LWR@autoindex}{1}%                    lwarp
        \label{LWRindex-\arabic{LWR@autoindex}}%    lwarp
        \begingroup%
    }
    {}
    {\LWR@patcherror{index}{@wrindex}}
```

\AtBeginDocument lwarp core \lets \@wrindex to \LWR@wrindex. Since the index package has been loaded, \let to its version instead:

```
\let\LWR@index@wrindex\@wrindex

\AtBeginDocument{
\let\@wrindex\LWR@index@wrindex
}
```

Modified to add \index@prologue:

```
\AtBeginDocument{
\renewenvironment*{theindex}{%
    \LWR@indexsection{\indexname}%
    \ifx\index@prologue\@empty\else
        \index@prologue
        \bigskip
    \fi
```

```
    \let\item\LWR@indexitem%
    \let\subitem\LWR@indexsubitem%
    \let\subsubitem\LWR@indexsubsubitem%
}{}
}% AtBeginDocument
```

Disabled:

```
\def\@showidx#1{}
\let\@texttop\relax
\renewcommand*{\raggedbottom}{}
\renewcommand*{\flushbottom}{}
\renewcommand*{\markboth}[2]{}
\renewcommand*{\markright}[1]{}
```

File 231 **lwarp-inputtrc.sty**

§ 339 Package

inputtrc

(*Emulates or patches code by* Uwe Lück.)

Pkg inputtrc inputtrc is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{inputtrc}[2012/10/10]
```

Patched to remove extraneous spaces, which sometimes showed up in logos inside a `lateximage`.

```
\renewcommand*{\IT@prim@input}[1]{%
  \typeout{\IT@indent\IT@currfile INPUTTING #1}%
%% ... TODO: option to write to '.log' only.
  \xdef\IT@filestack{{\IT@currfile}\IT@filestack}%
  \xdef\IT@currfile{#1}%
  \expandafter \gdef\expandafter \IT@indent\expandafter{%
    \IT@indent \IT@indent@unit}%                lwarp
  \@@input#1%                                   lwarp
  \expandafter\IT@pop@indent\IT@indent   \@nil% lwarp
  \expandafter\IT@pop@file  \IT@filestack\@nil% lwarp
  \IT@maybe@returnmessage%% v0.2                lwarp
}
```

File 232 **lwarp-intopdf.sty**

§ 340 Package

intopdf

Pkg intopdf intopdf is emulated.

The filespec, MIME type, and description are ignored for now.

for HTML output:

```
\LWR@ProvidesPackageDrop{intopdf}[2019/05/28]
```

```
\NewDocumentCommand{\attachandlink}{o m o m m}{%
    \LWR@href{#2}{#5}%
}
```

File 233 **lwarp-isomath.sty**

§ 341 Package isomath

(*Emulates or patches code by* Günter Milde.)

Pkg isomath isomath is used as-is for SVG math, and emulated for MathJax.

⚠ MathJax sans MathJax does not provide a sans math font, so sans is typeset as roman.

for HTML output:

```
\LWR@ProvidesPackagePass{isomath}[2012/09/04]

\begin{warpMathJax}
\CustomizeMathJax{\let\mathbfit\boldsymbol}
\CustomizeMathJax{\let\mathsfbfit\mathbfit}% not sans
\CustomizeMathJax{\let\mathsfit\mathit}% not sans
\CustomizeMathJax{\let\vectorsym\mathbfit}
\CustomizeMathJax{\let\matrixsym\mathbfit}
\CustomizeMathJax{\let\tensorsym\mathsfbfit}
\CustomizeMathJax{\let\mathboldsans\mathsfbfit}
\CustomizeMathJax{\let\mathbold\mathbfit}
\CustomizeMathJax{\let\mathsans\mathrm}% not sans
\end{warpMathJax}
```

File 234 **lwarp-isotope.sty**

§ 342 Package isotope

(*Emulates or patches code by* Heiko Bauke.)

Pkg isotope isotope is patched for use by lwarp with SVG math, and emulated for MathJax.

for HTML output:

```
\LWR@ProvidesPackagePass{isotope}[2011/08/26]

\newcommand{\LWR@HTML@isotope@two}[2][]{%
    \renewcommand{\isotope@atomicnumber}{#1}%
    \edef\LWR@isotope@alttag{%
        \textbackslash(
        \textbackslash{}isotope
        [\isotope@nucleonnumber]%
        [\isotope@atomicnumber]%
        \{#2\}
        \textbackslash)%
    }%
  \ifbool{mathjax}%
    {\LWR@isotope@alttag}%
```

```
    {% SVG
        \m@th%
        \LWR@subsingledollar*%
        {% alt tag
            \LWR@isotope@alttag%
        }%
        {isotope}% add'l hashing
        {% contents
            \settowidth\@tempdimb{%
                \ensuremath{\scriptstyle\isotope@nucleonnumber}%
            }%
            \settowidth\@tempdimc{%
                \ensuremath{\scriptstyle\isotope@atomicnumber}%
            }%
            \ifdim\@tempdimb<\@tempdimc\@tempdimb=\@tempdimc\fi%
            \ensuremath{
                {}%
                ^{\makebox[\@tempdimb][r]{%
                    \ensuremath{%
                    \scriptstyle\isotope@nucleonnumber%
                    }% ensuremath
                }}%
                _{\makebox[\@tempdimb][r]{%
                    \ensuremath{%
                        \scriptstyle\isotope@atomicnumber%
                    }% ensuremath
                }}%
                \isotopestyle{#2}%
            }% ensuremath
        }% contents
    }% SVG
  \endgroup%
}%
\LWR@formatted{isotope@two}

\begin{warpMathJax}
\CustomizeMathJax{%
    \newcommand{\LWRisotopetwo}[2][]{%
        {%
            \vphantom{\mathrm{#2}}%
            {}^{\LWRisotopenucleonnumber}_{#1}%
            \mathrm{#2}%
        }%
    }%
}

\CustomizeMathJax{%
    \newcommand{\isotope}[1][]{%
        \def\LWRisotopenucleonnumber{#1}%
        \LWRisotopetwo%
    }%
}
\end{warpMathJax}
```

File 235 **lwarp-jurabib.sty**

§ 343 Package

jurabib

(*Emulates or patches code by* Jens Berger.)

Pkg jurabib jurabib is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{jurabib}[2004/01/25]

\renewrobustcmd{\jblangle}{\textless}

\renewrobustcmd{\jbrangle}{\textgreater}

\renewcommand*{\jb@biblaw@item}{%
    \hspace{0.5em}%
%     $\triangleright$
    \HTMLunicode{25B7}%     lwarp
    \hspace{0.5em}%
}

\renewrobustcmd{\jbarchsig}[2]{%
     \ifjbweareinbib
        \settowidth{\jb@subarchitemwidth}{\jbsamesubarchindent+#1}%
       \setlength{\jb@subarchentrywidth}{\textwidth-\jb@subarchitemwidth-4em}%
%      \begin{tabular}{@{}p{\jb@subarchitemwidth}@{}j{\jb@subarchentrywidth}@{}}%
           #1\ifjb@dot\unskip\unskip\unskip.\fi
%             &
            \quad%      lwarp
            \ifthenelse{\equal{#2}{}}{}{\jbarchnameformat{#2}}%
%         \end{tabular}
     \fi
}%


\xpatchcmd{\jb@do@post@item}
    {\begin{tabular}{p{\jb@biblaw@item@width}j{\jb@biblaw@entry@width}}}
    {}
    {}
    {\LWR@patcherror{jurabib}{jb@do@post@item 1}}

\xpatchcmd{\jb@do@post@item}
    {\multicolumn{2}{p{\columnwidth}}{\jb@@name}}
    {\jb@@name}
    {}
    {\LWR@patcherror{jurabib}{jb@do@post@item 2}}

\xpatchcmd{\jb@do@post@item}
    {\jb@biblaw@item & \jb@@fulltitle}
    {\jb@biblaw@item \quad \jb@@fulltitle}
    {}
    {\LWR@patcherror{jurabib}{jb@do@post@item 3}}
```

```
\xpatchcmd{\jb@do@post@item}
    {\end{tabular}}
    {}
    {}
    {\LWR@patcherror{jurabib}{jb@do@post@item 4}}

\xpatchcmd{\jb@do@post@item}
    {\begin{minipage}[t]{\bibnumberwidth}}
    {}
    {}
    {\LWR@patcherror{jurabib}{jb@do@post@item 5}}

\xpatchcmd{\jb@do@post@item}
    {\end{minipage}}
    {\quad}
    {}
    {\LWR@patcherror{jurabib}{jb@do@post@item 6}}
```

File 236 **lwarp-karnaugh-map.sty**

§ 344 Package

karnaugh-map

(*Emulates or patches code by* Mattias Jacobsson.)

Pkg karnaugh-map karnaugh-map is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{karnaugh-map}[2017/02/20]
```

This patch is needed only because lwarp changes the definition of \&, and the original uses \ifnum to compare 0 with \&. It is hard to patch this environment, so the entire thing is redefined here, with the lwarp modifications identified in comments.

```
\RenewDocumentEnvironment{karnaugh-map}{s O{4} O{4} O{1} O{$X_1X_0$} O{$X_3X_2$} O{$X_5X_4$}} {%
  \begingroup
    % store map size {[START]
      \renewcommand{\@karnaughmap@var@mapsizex@}{#2}%
      \renewcommand{\@karnaughmap@var@mapsizey@}{#3}%
      \renewcommand{\@karnaughmap@var@mapsizez@}{#4}%
    % [END]}
    % determinate if markings should be color or black and white
    \IfBooleanTF{#1}{%
      % should be black and white
      \renewcommand{\@karnaughmap@var@bw@}{1}%
    }{%
      % should be color
      \renewcommand{\@karnaughmap@var@bw@}{0}%
    }%
    %
    % find matching matrix template and alignment parameters {[START]
    \newcommand{\@karnaughmap@local@matrixtemplate@}{0}% '0' is considered as missing matrix template
      \newcommand{\@karnaughmap@local@maprealignmentx@}{0}%
      \newcommand{\@karnaughmap@local@maprealignmenty@}{0}%
```

```
\ifnum\@karnaughmap@var@mapsizex@\@karnaughmap@var@mapsizey@\@karnaughmap@var@mapsizez@=221
    \renewcommand{\@karnaughmap@local@matrixtemplate@}{%
              \&                  0 \&                  1 \& \phantom{0} \\
          0 \& |(000000)| \phantom{0} \& |(000001)| \phantom{0} \&         \\
          1 \& |(000010)| \phantom{0} \& |(000011)| \phantom{0} \&         \\
    \phantom{0}  \&                   \&                   \&          \\
    }%
  \fi
\ifnum\@karnaughmap@var@mapsizex@\@karnaughmap@var@mapsizey@\@karnaughmap@var@mapsizez@=241
    \renewcommand{\@karnaughmap@local@matrixtemplate@}{%
              \&                 0 \&                 1 \& \phantom{00} \\
         00 \& |(000000)| \phantom{0} \& |(000001)| \phantom{0} \&          \\
         01 \& |(000010)| \phantom{0} \& |(000011)| \phantom{0} \&          \\
         11 \& |(000110)| \phantom{0} \& |(000111)| \phantom{0} \&          \\
         10 \& |(000100)| \phantom{0} \& |(000101)| \phantom{0} \&          \\
    \phantom{00} \&                   \&                   \&           \\
    }%
  \fi
\ifnum\@karnaughmap@var@mapsizex@\@karnaughmap@var@mapsizey@\@karnaughmap@var@mapsizez@=421
    \renewcommand{\@karnaughmap@local@matrixtemplate@}{%
             \&               00 \&               01 \&               11 \&               10 \& \phanto
         0  \& |(000000)| \phantom{0} \& |(000001)| \phantom{0} \& |(000011)| \phantom{0} \& |(00001
         1  \& |(000100)| \phantom{0} \& |(000101)| \phantom{0} \& |(000111)| \phantom{0} \& |(00011
   \phantom{00} \&                \&                \&                \&                \&
    }%
  \fi
\ifnum\@karnaughmap@var@mapsizex@\@karnaughmap@var@mapsizey@\@karnaughmap@var@mapsizez@=441
    \renewcommand{\@karnaughmap@local@matrixtemplate@}{%
             \&               00 \&               01 \&               11 \&               10 \& \phanto
         00 \& |(000000)| \phantom{0} \& |(000001)| \phantom{0} \& |(000011)| \phantom{0} \& |(00001
         01 \& |(000100)| \phantom{0} \& |(000101)| \phantom{0} \& |(000111)| \phantom{0} \& |(00011
         11 \& |(001100)| \phantom{0} \& |(001101)| \phantom{0} \& |(001111)| \phantom{0} \& |(00111
         10 \& |(001000)| \phantom{0} \& |(001001)| \phantom{0} \& |(001011)| \phantom{0} \& |(00101
   \phantom{00} \&                \&                \&                \&                \&
    }%
  \fi
\ifnum\@karnaughmap@var@mapsizex@\@karnaughmap@var@mapsizey@\@karnaughmap@var@mapsizez@=442
    \renewcommand{\@karnaughmap@local@matrixtemplate@}{%
             \&               00 \&               01 \&               11 \&               10 \& \phanto
         00 \& |(000000)| \phantom{0} \& |(000001)| \phantom{0} \& |(000011)| \phantom{0} \& |(00001
         01 \& |(000100)| \phantom{0} \& |(000101)| \phantom{0} \& |(000111)| \phantom{0} \& |(00011
         11 \& |(001100)| \phantom{0} \& |(001101)| \phantom{0} \& |(001111)| \phantom{0} \& |(00111
         10 \& |(001000)| \phantom{0} \& |(001001)| \phantom{0} \& |(001011)| \phantom{0} \& |(00101
   \phantom{00} \&                \&                \&                \&                \&
    }%
    \renewcommand{\@karnaughmap@local@maprealignmentx@}{2.5}%
  \fi
\ifnum\@karnaughmap@var@mapsizex@\@karnaughmap@var@mapsizey@\@karnaughmap@var@mapsizez@=444
    \renewcommand{\@karnaughmap@local@matrixtemplate@}{%
             \&               00 \&               01 \&               11 \&               10 \& \phanto
         00 \& |(000000)| \phantom{0} \& |(000001)| \phantom{0} \& |(000011)| \phantom{0} \& |(00001
         01 \& |(000100)| \phantom{0} \& |(000101)| \phantom{0} \& |(000111)| \phantom{0} \& |(00011
         11 \& |(001100)| \phantom{0} \& |(001101)| \phantom{0} \& |(001111)| \phantom{0} \& |(00111
         10 \& |(001000)| \phantom{0} \& |(001001)| \phantom{0} \& |(001011)| \phantom{0} \& |(00101
   \phantom{00} \&                \&                \&                \&                \&
```

```
            00 \& |(100000)| \phantom{0} \& |(100001)| \phantom{0} \& |(100011)| \phantom{0} \& |(1000
            01 \& |(100100)| \phantom{0} \& |(100101)| \phantom{0} \& |(100111)| \phantom{0} \& |(1001
            11 \& |(101100)| \phantom{0} \& |(101101)| \phantom{0} \& |(101111)| \phantom{0} \& |(1011
            10 \& |(101000)| \phantom{0} \& |(101001)| \phantom{0} \& |(101011)| \phantom{0} \& |(1010
     \phantom{00} \&                \&                \&                \&                \&
      }%
      \renewcommand{\@karnaughmap@local@maprealignmentx@}{2.5}%
      \renewcommand{\@karnaughmap@local@maprealignmenty@}{-2.5}%
    \fi
  % [END]}
 % test if a matrix template is found or not(aka "\@karnaughmap@local@matrixtemplate@" equals to '0')
  \ifdefstring{\@karnaughmap@local@matrixtemplate@}{0}{%  lwarp
%   \ifnum0=\@karnaughmap@local@matrixtemplate@%  original
    % print error if no template could be found
    \PackageError{lwarp-karnaugh-map}{%
      Can not find a template fitting your specification
     (\@karnaughmap@var@mapsizex@\space x \@karnaughmap@var@mapsizey@\space x
      \@karnaughmap@var@mapsizez@)%
    }{%
      Existing templates have the following dimensions:
      2x2x1, 2x4x1, 4x2x1, 4x4x1, 4x4x2, and 4x4x4.
    }%
%   \fi   original
  }{\relax}%    lwarp
  \begin{tikzpicture}
    % grid
    % for all dimensions
  \draw[color=black, ultra thin] (0,0) grid (\@karnaughmap@var@mapsizex@,\@karnaughmap@var@mapsizey@);
    % when there are 2 sub maps
    \ifnum\@karnaughmap@var@mapsizez@=2
      \draw[color=black, ultra thin] (5,0) grid (9,4);
    \fi
    % when there are 4 sub maps
    \ifnum\@karnaughmap@var@mapsizez@=4
      \draw[color=black, ultra thin] (5,0) grid (9,4);
      \draw[color=black, ultra thin] (0,-5) grid (4,-1);
      \draw[color=black, ultra thin] (5,-5) grid (9,-1);
    \fi
    % labels
    % for all dimensions
  \node[above] at (\@karnaughmap@var@mapsizex@*0.5,\@karnaughmap@var@mapsizey@+0.9) {\small{#5}};
    \node[left] at (-0.9,\@karnaughmap@var@mapsizey@*0.5) {\small{#6}};
    % when there are 2 sub maps
    \ifnum\@karnaughmap@var@mapsizez@=2
      \node[above] at (7,4.9) {\small{#5}};
      % extra sub maps labels
      \node[below] at (2,-0.1) {\small{#7$=0$}};
      \node[below] at (7,-0.1) {\small{#7$=1$}};
    \fi
    % when there are 4 sub maps
    \ifnum\@karnaughmap@var@mapsizez@=4
      \node[above] at (7,4.9) {\small{#5}};
      \node[left] at (-0.9,-3) {\small{#6}};
      % extra sub maps labels
      \node[below] at (2,-0.1) {\small{#7$=00$}};
```

```
      \node[below] at (7,-0.1) {\small{#7$=01$}};
      \node[below] at (2,-5.1) {\small{#7$=10$}};
      \node[below] at (7,-5.1) {\small{#7$=11$}};
    \fi
    % data
    \matrix[
      matrix of nodes,
      ampersand replacement=\&,
      column sep={1cm,between origins},
      row sep={1cm,between origins},
  ] at (\@karnaughmap@var@mapsizex@*0.5+\@karnaughmap@local@maprealignmentx@,\@karnaughmap@var@mapsiz
      \@karnaughmap@local@matrixtemplate@%
    };
}{
  \end{tikzpicture}
\endgroup
}
```

File 237 **lwarp-keyfloat.sty**

§ 345 Package

keyfloat

(*Emulates or patches code by* Brian Dunn.)

Pkg keyfloat keyfloat is supported with a considerable amount of hacking. (It's a mashup of lwarp, keyfloat, and tocdata.)

⚠ keywrap If placing a \keyfig[H] inside a keywrap, use an absolute width for \keyfig, instead of lw-proportional widths. (The [H] option forces the use of a minipage, which internally adjusts for a virtual 6-inch wide minipage, which then corrupts the lw option.)

For wrapped figures, overhang and number of lines are ignored.

for HTML output:

```
\LWR@ProvidesPackagePass{keyfloat}[2019/09/23]

\@ifpackagelater{keyfloat}{2019/09/23}{\relax}{
    \PackageError{lwarp-keyfloat}
    {%
        The keyfloat package is out of date.\MessageBreak
        Update to keyfloat v2.01 2019/09/23 or later%
    }
    {%
        Please update the keyfloat package.  It's worth it!%
    }
}
```

After keyfloat has loaded:

```
\AtBeginDocument{


\providecommand*{\KFLT@LWR@hook@boxouter}{}
\renewcommand*{\KFLT@LWR@hook@boxouter}{%
    \ifbool{KFLT@keywrap}{%
```

```
    }{%
        \ifnumequal{\value{KFLT@keyfloatdepth}}{0}{%
            \setlength{\linewidth}{6in}%
            \setlength{\textwidth}{6in}%
            \setlength{\textheight}{9in}%
        }{}%
    }%
    \normalcolor%
}


\LetLtxMacro\KFLT@LWR@hook@keysubfloats\KFLT@LWR@hook@boxouter

\let\KFLT@LWR@hook@keyfloatsminipage\relax
\let\endKFLT@LWR@hook@keyfloatsminipage\relax
\newenvironment*{KFLT@LWR@hook@keyfloatsminipage}[1]{}{}


\LetLtxMacro\KFLT@LWR@hook@keyfloats\KFLT@LWR@hook@boxouter

\renewcommand*{\KFLT@maybeendfloatrow}{%
    \ifnumless{\value{KFLT@thiscol}}{\value{KFLT@numcols}}%
        {}% thiscol < numcols
        {% >=
            \defcounter{KFLT@thiscol}{0}%
        }%
}%

\renewcommand{\KFLT@trackrows}%
{%
```

If are nested inside a keyfloats or a subfloat:

```
    \ifboolexpr{%
        test {\ifnumgreater{\value{KFLT@keyfloatdepth}}{0}} or%
        bool{KFLT@inkeysubfloats}%
    }%
    {% nested
```

Tracks row start and end:

```
        \KFLT@maybestartfloatrow%
```

Possibly fill space between columns:

```
        \ifnumgreater{\value{KFLT@thiscol}}{1}%
            {%
%                 \hfill%
            }%
            {}%
    }% nested
    {}% not nested
}


\RenewDocumentCommand{\KFLT@onefigureimage}{m}
```

```
{%
\LWR@traceinfo{KFLT@onefigureimage}%
% \begin{lrbox}{\KFLT@envbox}%
\ifthenelse{\NOT\equal{\KFLT@lw}{}}%
    {%

        \ifdimgreater{\KFLT@h}{0pt}%
        {%
            \KFLT@frame{%
                \includegraphics%
                [%
                    scale=\KFLT@s,%
                    width=\KFLT@imagewidth,%
                    height=\KFLT@h,%
                    \KFLT@keepaspectratio,%
                ]{#1}%
            }%
        }%
        {%
            \KFLT@frame{\includegraphics%
            [scale=\KFLT@s,width=\KFLT@imagewidth]{#1}}%
        }%
    }%
    {% not linewidth
        \ifthenelse{\dimtest{\KFLT@w}{>}{0pt}}%
        {% width is given
            \ifthenelse{\dimtest{\KFLT@h}{>}{0pt}}%
            {% w and h
                \KFLT@frame{\includegraphics[%
                    scale=\KFLT@s,%
                    width=\KFLT@imagewidth,%
                    height=\KFLT@h,%
                    \KFLT@keepaspectratio,%
                ]{#1}}%
            }% w and h
            {% only w
                \KFLT@frame{\includegraphics%
                [scale=\KFLT@s,width=\KFLT@imagewidth]{#1}}%
            }% only w
        }% width is given
        {% width is not given
            \ifthenelse{\dimtest{\KFLT@h}{>}{0pt}}%
            {%
                \KFLT@frame{\includegraphics%
                [scale=\KFLT@s,height=\KFLT@h]{#1}}%
            }%
            {%
                \KFLT@frame{\includegraphics%
                [scale=\KFLT@s]{#1}}%
            }%
        }% width is not given
    }% not linewidth
% \end{lrbox}%
% \unskip%
% \KFLT@findenvboxwidth%
```

```
% \begin{turn}{\KFLT@r}%
% \KFLT@frame{\usebox{\KFLT@envbox}}%
% \unskip%
% \end{turn}%
\LWR@traceinfo{KFLT@onefigureimage: done}%
}

\RenewDocumentEnvironment{KFLT@boxinner}{}
{%
    \LWR@traceinfo{KFLT@boxinner}%
    \LWR@stoppars%
    \minipagefullwidth%
    \ifboolexpr{bool{KFLT@ft} or bool{KFLT@f}}{%
        \fminipage{\KFLT@imagewidth}%
    }{%
        \minipage{\KFLT@imagewidth}%
    }%
}
{%
    \ifboolexpr{bool{KFLT@ft} or bool{KFLT@f}}{%
        \endfminipage%
    }{%
        \endminipage%
    }%
    \LWR@startpars%
    \LWR@traceinfo{KFLT@boxinner: done}%
}

\newcommand*{\LWR@KFLT@settextalign}[1]{%
    \def\LWR@KFLT@textalign{justify}%
    \ifcsstring{KFLT@#1textalign}{\centering}%
        {\def\LWR@KFLT@textalign{center}}%
        {}%
    \ifcsstring{KFLT@#1textalign}{\raggedleft}%
        {\def\LWR@KFLT@textalign{right}}%
        {}%
    \ifcsstring{KFLT@#1textalign}{\raggedright}%
        {\def\LWR@KFLT@textalign{left}}%
        {}%
}

\renewcommand{\KFLT@addtext}[1]
{%
```

Is there text to add?

```
    \ifcsempty{KFLT@#1t}%
    {}% no text
    {% text to add
        {% local
```

Add some space, then create a to contain the text:

```
        \addvspace{\smallskipamount}%
        \LWR@KFLT@settextalign{#1}%
```

```
        \begin{BlockClass}[text-align:\LWR@KFLT@textalign]{floatnotes}%
```

Set the alignment and some text parameters:

```
%         \csuse{KFLT@#1textalign}%
%         \footnotesize%
        \setlength{\parskip}{1.5ex}%
        \setlength{\parindent}{0em}%
```

Typeset the actual text:

```
        \csuse{KFLT@#1t}%
```

Close it all out with a little more space:

```
        \end{BlockClass}%
%         \par\addvspace{2ex}%
        }% local
    }% text to add
}

\@ifpackageloaded{tocdata}
{}
{% tocdata not loaded

    \newcommand*{\LWR@KFLT@setnamealign}[1]{%
        \def\LWR@KFLT@textalign{justify}%
        \ifstrequal{#1}{\centering}%
            {\def\LWR@KFLT@textalign{center}}%
            {}%
        \ifstrequal{#1}{\raggedleft}%
            {\def\LWR@KFLT@textalign{right}}%
            {}%
        \ifstrequal{#1}{\raggedright}%
            {\def\LWR@KFLT@textalign{left}}%
            {}%
    }

    \renewcommand*{\KFLT@@addartisttext}[3]{%

```

Add space and create the name inside a :

```
%         \addvspace{\medskipamount}%
    %     \begin{minipage}{\linewidth}%
        \LWR@KFLT@setnamealign{#3}%
        \begin{BlockClass}[text-align:\LWR@KFLT@textalign]{floatnotes}%

```

Text alignment is #3, and depends on artist or author:

```
    %     #3%

```

#1 is empty or 'subgrp'
#2 is empty for artist, 'u' for author:

```
        \footnotesize\textsc{%
            \KFLT@optionalname{\csuse{KFLT@#1a#2p}}%
            \KFLT@optionalname{\csuse{KFLT@#1a#2f}}%
            \csuse{KFLT@#1a#2l}%
            \csuse{KFLT@#1a#2s}%
        }%
    %     \end{minipage}%
        \end{BlockClass}
%         \par\addvspace{2ex}%
    }

}% tocdata not loaded
```

Env KFLT@marginfloat [⟨*offset*⟩] {⟨*type*⟩}

```
\DeclareDocumentEnvironment{KFLT@marginfloat}{O{-1.2ex} m}
{%
    \uselengthunit{PT}%
    \LWR@BlockClassWP%
        {float:right; width:2in; margin:10pt}%
        {}%
        (note)%
        {marginblock}%
    \renewcommand*{\@captype}{#2}%
    \minipage{\LWR@usersmarginparwidth}%
    \setlength{\marginparwidth}{.95\LWR@usersmarginparwidth}%
}
{%
    \endminipage%
    \endLWR@BlockClassWP%
}

\DeclareDocumentEnvironment{marginfigure}{o}
    {\begin{KFLT@marginfloat}{figure}}
    {\end{KFLT@marginfloat}}

\DeclareDocumentEnvironment{margintable}{o}
    {\begin{KFLT@marginfloat}{table}}
    {\end{KFLT@marginfloat}}
```

Env keywrap {⟨*width*⟩} {⟨*keyfloat*⟩}

```
\DeclareDocumentEnvironment{keywrap}{m +m}
{%
    \begin{LWR@setvirtualpage}*
    \setlength{\LWR@templengthone}{#1}%
    \begin{LWR@BlockClassWP}%
        {%
         float:right; width:\LWR@printlength{\LWR@templengthone};  % extra space
            margin:10pt%
        }%
```

```
        {}%
        (note)%
        {marginblock}%
    \setlength{\linewidth}{.95\LWR@templengthone}%
    \booltrue{KFLT@keywrap}%
    #2%
    \end{LWR@BlockClassWP}%
    \end{LWR@setvirtualpage}%
}
{}

}% AtBeginDocument
```

File 238 **lwarp-keystroke.sty**

§ 346 Package

keystroke

(*Emulates or patches code by* Werner Fink.)

Pkg keystroke keystroke is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{keystroke}[2010/04/23]

\newcommand*{\LWR@HTML@keystroke}[1]{
    \InlineClass{keystroke}{#1}
}
\LWR@formatted{keystroke}


\newcommand*{\LWR@HTML@Return}{\keystroke{\HTMLunicode{021A9}}}
\LWR@formatted{Return}

\newcommand*{\LWR@HTML@BSpace}{\keystroke{\HTMLunicode{027FB}}}
\LWR@formatted{BSpace}

\newcommand*{\LWR@HTML@Tab}{\keystroke{|\HTMLunicode{021C6}|}}
\LWR@formatted{Tab}

\newcommand*{\LWR@HTML@UArrow}{\keystroke{\HTMLunicode{02191}}}
\LWR@formatted{UArrow}

\newcommand*{\LWR@HTML@DArrow}{\keystroke{\HTMLunicode{02193}}}
\LWR@formatted{DArrow}

\newcommand*{\LWR@HTML@LArrow}{\keystroke{\HTMLunicode{02190}}}
\LWR@formatted{LArrow}

\newcommand*{\LWR@HTML@RArrow}{\keystroke{\HTMLunicode{02192}}}
\LWR@formatted{RArrow}

% Preserves the language options:
\LetLtxMacro\LWR@HTML@Shift\Shift
\xpatchcmd{\LWR@HTML@Shift}
```

```
    {$\Uparrow$}
    {\HTMLunicode{21D1}}
    {}
    {}
\LWR@formatted{Shift}

\LetLtxMacro\LWR@HTML@PgUp\PgUp
\xpatchcmd{\LWR@HTML@PgUp}
    {$\uparrow$}
    {\HTMLunicode{2191}}
    {}
    {}
\LWR@formatted{PgUp}

\LetLtxMacro\LWR@HTML@PgDown\PgDown
\xpatchcmd{\LWR@HTML@PgDown}
    {$\downarrow$}
    {\HTMLunicode{2193}}
    {}
    {}
\LWR@formatted{PgDown}
```

File 239 **lwarp-kpfonts.sty**

§ 347 Package

kpfonts

(*Emulates or patches code by* Christophe Caignaert.)

Pkg kpfonts

kpfonts is used as-is for SVG math, and is emulated for MathJax.

⚠ limitations

The MathJax emulation honors the options uprightRoman for \D only, classicReIm, frenchstyle for Greek only, upright for Greek only, uprightgreeks, slantedGreeks, and mathcalasscript.

The dedicated macros for Greek work correctly.

SVG math should appear the same as the printed output.

for HTML output:

```
\LWR@ProvidesPackagePass{kpfonts}[2010/08/20]

\LWR@infoprocessingmathjax{kpfonts}

\LWR@origRequirePackage{lwarp-common-mathjax-newpxtxmath}

\LWR@origRequirePackage{lwarp-common-mathjax-letters}

\begin{warpMathJax}

\ifkp@calasscr
    \CustomizeMathJax{\let\LWRorigmathscr\mathscr}
    \CustomizeMathJax{\let\LWRorigmathcal\mathcal}
    \CustomizeMathJax{\let\mathscr\LWRorigmathcal}
    \CustomizeMathJax{\let\mathcal\LWRorigmathscr}
```

```
\fi

\ifkp@upgrk % lowercase
    \LWR@mathjax@addgreek@l@up{}{}
    \LWR@mathjax@addgreek@l@it{other}{}
\else
    \LWR@mathjax@addgreek@l@up{other}{}
\fi

\ifkp@slGrk
    \LWR@mathjax@addgreek@u@it*{}{}
    \LWR@mathjax@addgreek@u@up*{other}{}
    \LWR@mathjax@addgreek@u@up*{var}{}
\else
    \LWR@mathjax@addgreek@u@it*{other}{}
    \LWR@mathjax@addgreek@u@it*{var}{}
\fi

\LWR@mathjax@addgreek@u@up*{}{up}
\LWR@mathjax@addgreek@l@up{}{up}

\LWR@mathjax@addgreek@u@it*{}{sl}
\LWR@mathjax@addgreek@l@it{}{sl}

\CustomizeMathJax{\newcommand{\partialsl}{\mathord{\unicode{x1D715}}}}
\CustomizeMathJax{\let\partialup\uppartial}% not upright

\ifkp@oldReIm
\else
    \CustomizeMathJax{\renewcommand{\Re}{\mathfrak{Re}}}
    \CustomizeMathJax{\renewcommand{\Im}{\mathfrak{Im}}}
\fi

\ifkp@Dcommand
    \ifkp@upRm%
        \CustomizeMathJax{
            \def\D#1{\mathclose{\,\mathrm{d}}#1}
        }
    \else
        \CustomizeMathJax{
            \def\D#1{\mathclose{\,\mathit{d}}#1}
        }
    \fi
\fi

\CustomizeMathJax{\let\pounds\mathsterling}
\CustomizeMathJax{\let\kppounds\mathsterling}

\CustomizeMathJax{\newcommand{\mathup}[1]{\mathrm{#1}}}% never sans
\CustomizeMathJax{\let\mathupright\mathup}

\end{warpMathJax}
```

File 240 **lwarp-kpfonts-otf.sty**

§ 348 Package

kpfonts-otf

(*Emulates or patches code by* Daniel Flipo.)

Pkg kpfonts-otf

kpfonts-otf is used as-is for SVG math, and is emulated for MathJax.

⚠ limitations

The MathJax emulation honors the options `fancyReIm`, `mathcal`, `frenchstyle` for Greek only, and `mathcalasscript`.

Also see the options for unicode-math, which is loaded by kpfonts-otf.

The unicode-math dedicated macros for Greek work correctly.

⚠ `\mathversion`

The MathJax emulation does not change with the use of `\mathversion`. Whatever emulation is established at the begin of the document will remain.

SVG math should appear the same as the printed output.

for HTML output:

```
\LWR@ProvidesPackagePass{kpfonts-otf}[2020/06/20]

\LWR@infoprocessingmathjax{kpfonts-otf}

\LWR@origRequirePackage{lwarp-common-mathjax-nonunicode}

\LWR@origRequirePackage{lwarp-common-mathjax-letters}

\begin{warpMathJax}

\ifkp@calasscr
    \CustomizeMathJax{\let\mathscr\mathcal}
\else
    \CustomizeMathJax{\let\mathcal\mathscr}
\fi

\ifkp@frenchstyle
    \LWR@mathjax@addgreek@l@up{}{}
    \LWR@mathjax@addgreek@u@up*{}{}
\fi

\ifkp@oldReIm
    \CustomizeMathJax{\renewcommand{\Re}{\mathfrak{Re}}}
    \CustomizeMathJax{\renewcommand{\Im}{\mathfrak{Im}}}
\else
\fi

\ifkp@Dcommand
    \CustomizeMathJax{
        \def\D#1{\mathclose{\,\mathrm{d}}#1}
    }
\fi

\CustomizeMathJax{\let\varint\int}
\CustomizeMathJax{\let\variint\iint}
\CustomizeMathJax{\let\variiint\iiint}
\CustomizeMathJax{\let\variiiint\iiiint}
\CustomizeMathJax{\let\varidotsint\idotsint}
```

```
39
40 \CustomizeMathJax{\newcommand{\varointctrclockwise}{\mathop{\unicode{x2939}\!\!\unicode{x0222E}}}}
41 \CustomizeMathJax{\newcommand{\oiintclockwise}{\mathop{\unicode{x0222F}\!\!\unicode{x2938}}}}
42 \CustomizeMathJax{\newcommand{\oiintctrclockwise}{\mathop{\unicode{x2939}\!\!\unicode{x0222F}}}}
43 \CustomizeMathJax{\newcommand{\varoiintclockwise}{\mathop{\unicode{x0222F}\!\!\unicode{x2938}}}}
44 \CustomizeMathJax{\newcommand{\varoiintctrclockwise}{\mathop{\unicode{x2939}\!\!\unicode{x0222F}}}}
45 \CustomizeMathJax{\newcommand{\oiiintclockwise}{\mathop{\unicode{x02230}\!\!\unicode{x2938}}}}
46 \CustomizeMathJax{\newcommand{\oiiintctrclockwise}{\mathop{\unicode{x2939}\!\!\unicode{x02230}}}}
47 \CustomizeMathJax{\newcommand{\varoiiintclockwise}{\mathop{\unicode{x02230}\!\!\unicode{x2938}}}}
48 \CustomizeMathJax{\newcommand{\varoiiintctrclockwise}{\mathop{\unicode{x2939}\!\!\unicode{x02230}}}}
49 \CustomizeMathJax{\newcommand{\sqiint}{\mathop{\unicode{x2A16}\!\!\unicode{x2A16}}}}
50 \CustomizeMathJax{\newcommand{\sqiiint}{\mathop{\unicode{x2A16}\!\!\unicode{x2A16}\!\!\unicode{x2A16}}}}
51
52 \CustomizeMathJax{\let\widearc\overparen}
53 \CustomizeMathJax{\let\widearcarrow\overrightarrow}
54 \CustomizeMathJax{\let\overrightarc\overrightarrow}
55
56 \end{warpMathJax}
```

File 241 **lwarp-layaureo.sty**

§ 349 Package layaureo

Pkg layaureo layaureo is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{layaureo}[2004/09/16]
```

File 242 **lwarp-layout.sty**

§ 350 Package layout

Pkg layout layout is ignored.

for HTML output: Discard all options for lwarp-layout:

```
1 \LWR@ProvidesPackageDrop{layout}[2014/10/28]

2 \NewDocumentCommand{\layout}{s}{}
```

File 243 **lwarp-layouts.sty**

§ 351 Package layouts

Pkg layouts layouts is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{layouts}[2009/09/02]
```

```
\newif\ifoddpagelayout
  \oddpagelayouttrue
\newif\iftwocolumnlayout
  \twocolumnlayoutfalse
\newif\ifdrawmarginpars
  \drawmarginparstrue
\newif\ifdrawparameters
  \drawparameterstrue
\newif\iflistaspara
  \listasparatrue
\newif\ifruninhead
  \runinheadfalse
\newif\ifprintparameters
  \printparameterstrue
\newif\ifdrawdimensions
  \drawdimensionsfalse
\newif\ifprintheadings
  \printheadingstrue
\newcommand{\testdrawdimensions}{}
\newcommand{\testprintparameters}{}
\newcommand{\setlabelfont}[1]{}
\newcommand{\setparametertextfont}[1]{}
\newcommand{\setvaluestextsize}[1]{}
\newcommand{\setlayoutscale}[1]{}
\newcommand{\setuplayouts}{}
\newcommand{\printinunitsof}[1]{}
\newcommand{\prntlen}[1]{}
\newcommand{\trypaperwidth}[1]{}
\newcommand{\trypaperheight}[1]{}
\newcommand{\tryhoffset}[1]{}
\newcommand{\tryvoffset}[1]{}
\newcommand{\trytopmargin}[1]{}
\newcommand{\tryheadheight}[1]{}
\newcommand{\tryheadsep}[1]{}
\newcommand{\trytextheight}[1]{}
\newcommand{\tryfootskip}[1]{}
\newcommand{\tryoddsidemargin}[1]{}
\newcommand{\tryevensidemargin}[1]{}
\newcommand{\trytextwidth}[1]{}
\newcommand{\trymarginparsep}[1]{}
\newcommand{\trymarginparwidth}[1]{}
\newcommand{\trymarginparpush}[1]{}
\newcommand{\trycolumnsep}[1]{}
\newcommand{\trycolumnseprule}[1]{}
\newcommand{\setfootbox}[2]{}
\newcommand{\currentpage}{}
\newcommand{\drawpage}{(draw page)}
\newcommand{\pagediagram}{(page diagram)}
\newcommand{\pagedesign}{(page design)}
\newcommand{\pagevalues}{(page values)}
\newcommand{\trystockwidth}[1]{}
\newcommand{\trystockheight}[1]{}
\newcommand{\trytrimedge}[1]{}
\newcommand{\trytrimtop}[1]{}
\newcommand{\tryuppermargin}[1]{}
```

```
\newcommand{\tryspinemargin}[1]{}
\newcommand{\currentstock}{}
\newcommand{\drawstock}{(draw stock)}
\newcommand{\stockdiagram}{(stock diagram)}
\newcommand{\stockdesign}{(stock design)}
\newcommand{\stockvalues}{(stock values)}
\newcommand{\tryitemindent}[1]{}
\newcommand{\trylabelwidth}[1]{}
\newcommand{\trylabelsep}[1]{}
\newcommand{\tryleftmargin}[1]{}
\newcommand{\tryrightmargin}[1]{}
\newcommand{\trylistparindent}[1]{}
\newcommand{\trytopsep}[1]{}
\newcommand{\tryparskip}[1]{}
\newcommand{\trypartopsep}[1]{}
\newcommand{\tryparsep}[1]{}
\newcommand{\tryitemsep}[1]{}
\newcommand{\currentlist}{}
\newcommand{\drawlist}{(draw list)}
\newcommand{\listdiagram}{(list diagram)}
\newcommand{\listdesign}{(list design)}
\newcommand{\listvalues}{(list values)}
\newcommand{\tryfootins}[1]{}
\newcommand{\tryfootnotesep}[1]{}
\newcommand{\tryfootnotebaseline}[1]{}
\newcommand{\tryfootruleheight}[1]{}
\newcommand{\tryfootrulefrac}[1]{}
\newcommand{\currentfootnote}{}
\newcommand{\drawfootnote}{(draw footnote)}
\newcommand{\footnotediagram}{(footnote diagram)}
\newcommand{\footnotedesign}{(footnote design)}
\newcommand{\footnotevalues}{(footnote values)}
\newcommand{\tryparindent}[1]{}
\newcommand{\tryparlinewidth}[1]{}
\newcommand{\tryparbaselineskip}[1]{}
\newcommand{\currentparagraph}{}
\newcommand{\drawparagraph}{(draw paragraph)}
\newcommand{\paragraphdiagram}{(paragraph diagram)}
\newcommand{\paragraphdesign}{(paragraph design)}
\newcommand{\paragraphvalues}{(paragraph values)}
\newcommand{\trybeforeskip}[1]{}
\newcommand{\tryafterskip}[1]{}
\newcommand{\tryindent}[1]{}
\newcommand{\currentheading}{}
\newcommand{\drawheading}[1]{(draw heading)}
\newcommand{\headingdiagram}[1]{(heading diagram)}
\newcommand{\headingdesign}[1]{(heading design)}
\newcommand{\headingvalues}{(heading values)}
\newcommand{\trytextfloatsep}[1]{}
\newcommand{\tryfloatsep}[1]{}
\newcommand{\tryintextsep}[1]{}
\newcommand{\trytopfigrule}[1]{}
\newcommand{\trybotfigrule}[1]{}
\newcommand{\currentfloat}{}
\newcommand{\drawfloat}{(draw float)}
```

```
\newcommand{\floatdiagram}{(float diagram)}
\newcommand{\floatdesign}{(float design)}
\newcommand{\floatvalues}{(float values)}
\newcommand{\trytotalnumber}[1]{}
\newcommand{\trytopnumber}[1]{}
\newcommand{\trybottomnumber}[1]{}
\newcommand{\trytopfraction}[1]{}
\newcommand{\trytextfraction}[1]{}
\newcommand{\trybottomfraction}[1]{}
\newcommand{\currentfloatpage}{}
\newcommand{\drawfloatpage}{(draw floatpage)}
\newcommand{\floatpagediagram}{(floatpage diagram)}
\newcommand{\floatpagedesign}{(floatpage design)}
\newcommand{\floatpagevalues}{(floatpage values)}
\newcommand{\trytocindent}[1]{}
\newcommand{\trytocnumwidth}[1]{}
\newcommand{\trytoclinewidth}[1]{}
\newcommand{\trytocrmarg}[1]{}
\newcommand{\trytocpnumwidth}[1]{}
\newcommand{\trytocdotsep}[1]{}
\newcommand{\currenttoc}{}
\newcommand{\drawtoc}{(draw toc)}
\newcommand{\tocdiagram}{(toc diagram)}
\newcommand{\tocdesign}{(toc design)}
\newcommand{\tocvalues}{(toc values)}
\newcommand{\drawaspread}[8][0]{(a spread)}
\newcommand{\drawfontframe}[1]{(font frame)}
\newcommand{\drawfontframelabel}[1]{}
```

File 244 **lwarp-leading.sty**

§ 352 Package

leading

Pkg leading leading is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{leading}[2008/12/11]

\newcommand\leading[1]{}
```

File 245 **lwarp-leftidx.sty**

§ 353 Package

leftidx

(*Emulates or patches code by* Harald Harders.)

Pkg leftidx leftidx works as-is with SVG math, and is emulated for MathJax.

for HTML output:

```
\LWR@ProvidesPackagePass{leftidx}[2003/09/24]

\begin{warpMathJax}
```

```
\CustomizeMathJax{\newcommand{\leftidx}[3]{{\vphantom{#2}}#1#2#3}}
\CustomizeMathJax{\newcommand{\ltrans}[1]{\leftidx{^\mathrm{t}}{\!#1}{}}}
\end{warpMathJax}
```

File 246 **lwarp-letterspace.sty**

§ 354 Package

letterspace

(*Emulates or patches code by* R Schlicht.)

Pkg letterspace letterspace is a subset of microtype, which is pre-loaded by lwarp. All user options and macros are ignored and disabled.

for HTML output: Discard all options for lwarp-letterspace:

```
\LWR@ProvidesPackageDrop{letterspace}[2018/01/14]

\newcommand*\lsstyle{}
\newcommand\textls[2][]{}
\def\textls#1#{}
\newcommand*\lslig[1]{#1}
```

File 247 **lwarp-lettrine.sty**

§ 355 Package

lettrine

(*Emulates or patches code by* Daniel Flipo.)

Pkg lettrine lettrine is emulated.

for HTML output: Discard all options for lwarp-lettrine:

```
\LWR@ProvidesPackageDrop{lettrine}[2018-08-28]
```

The initial letter is in a of class `lettrine`, and the following text is in a of class `lettrinetext`. `\lettrine` [⟨*keys*⟩] {⟨*letter*⟩} {⟨*additional text*⟩}

```
\DeclareDocumentCommand{\lettrine}{o m m}{%
    \InlineClass{lettrine}{#2}\InlineClass{lettrinetext}{#3} % extra space
}

\newcounter{DefaultLines}
\setcounter{DefaultLines}{2}
\newcounter{DefaultDepth}
\newcommand*{\DefaultOptionsFile}{\relax}
\newcommand*{\DefaultLoversize}{0}
\newcommand*{\DefaultLraise}{0}
\newcommand*{\DefaultLhang}{0}
\newdimen\DefaultFindent
\setlength{\DefaultFindent}{\z@}
\newdimen\DefaultNindent
```

```
\setlength{\DefaultNindent}{0.5em}
\newdimen\DefaultSlope
\setlength{\DefaultSlope}{\z@}
\newdimen\DiscardVskip
\setlength{\DiscardVskip}{0.2\p@}
\newif\ifLettrineImage
\newif\ifLettrineOnGrid
\newif\ifLettrineRealHeight

\newcommand*{\LettrineTextFont}{\scshape}
\newcommand*{\LettrineFontHook}{}
\newcommand*{\LettrineFont}[1]{\InlineClass{lettrine}{#1}}
\newcommand*{\LettrineFontEPS}[1]{\includegraphics[height=1.5ex]{#1}}
```

File 248 **lwarp-libertinust1math.sty**

§ 356 Package

libertinust1math

(*Emulates or patches code by* Michael Sharpe.)

Pkg libertinust1math

libertinust1math is used as-is for SVG math, and is emulated for MathJax.

The MathJax emulation honors `frenchmath` for Greek but not Latin characters, and `slantedGreek`, `uprightGreek`, and `ISO` also adjust Greek characters. MathJax cannot yet honor options for adjusting Latin characters.

The dedicated macros for upright and italic Greek letters do work correctly.

Some of the symbol font macros such as `\mathsfbf` do not use a sans font because MathJax does not yet have sans Greek.

SVG math honors all font choices, and should appear the same as the printed output.

for HTML output:

```
\LWR@ProvidesPackagePass{libertinust1math}[2020/06/10]

\LWR@infoprocessingmathjax{libertinust1math}

\LWR@origRequirePackage{lwarp-common-mathjax-letters}

\begin{warpMathJax}

\iflibus@slantedG
    \LWR@mathjax@addgreek@u@it*{}{}
\else
    \LWR@mathjax@addgreek@u@up*{}{}
\fi

\LWR@mathjax@addgreek@u@it*{}{it}
\LWR@mathjax@addgreek@u@up*{up}{}
\LWR@mathjax@addgreek@u@up*{}{up}

\iflibus@frenchm
    \LWR@mathjax@addgreek@l@up{}{}
```

```
\else
    \LWR@mathjax@addgreek@l@it{}{}
\fi

\LWR@mathjax@addgreek@l@it{}{it}
\LWR@mathjax@addgreek@l@up{}{up}
\LWR@mathjax@addgreek@l@up{up}{}

\CustomizeMathJax{\let\uppartial\partial}% not upright


\CustomizeMathJax{\let\mathsfbf\mathbf}% not sans
% \CustomizeMathJax{\newcommand{\mathsfbf}[1]{%
%     \mmlToken{mi}[mathvariant="bold-sans-serif"]{#1}% not greek
% }}% not sans

% \CustomizeMathJax{\newcommand{\mathbfit}[1]{\boldsymbol{#1}}}
\CustomizeMathJax{\let\mathbfit\boldsymbol}


% \CustomizeMathJax{\newcommand{\mathsfbfit}[1]{\boldsymbol{#1}}}% not sans
\CustomizeMathJax{\let\mathsfbfit\mathbfit}% not sans
% \CustomizeMathJax{\newcommand{\mathsfbfit}[1]{%
%     \mmlToken{mi}[mathvariant="sans-serif-bold-italic"]{#1}% not greek
% }}%


\CustomizeMathJax{\let\mathsfit\mathit}% not sans
% \CustomizeMathJax{\newcommand{\mathsfit}[1]{%
%     \mmlToken{mi}[mathvariant="sans-serif-italic"]{#1}% not greek
% }}

\CustomizeMathJax{\let\vectorsym\mathbfit}
\CustomizeMathJax{\let\matrixsym\mathbfit}
\CustomizeMathJax{\let\tensorsym\mathsfbfit}
\CustomizeMathJax{\let\mathboldsans\mathsfbfit}
\CustomizeMathJax{\let\mathbold\mathbfit}
```

`lwarp_mathjax.txt` adds `\left`/`\right` support for delimiters.

```
\CustomizeMathJax{\let\dlb\lBrack}
\CustomizeMathJax{\let\drb\rBrack}

\CustomizeMathJax{\let\sqrtsign\sqrt}

\CustomizeMathJax{\let\smallintsl\smallint}
\CustomizeMathJax{\newcommand{\smalliintsl}{\mathop{\unicode{x222C}}\limits}}
\CustomizeMathJax{\newcommand{\smalliiintsl}{\mathop{\unicode{x222D}}\limits}}
\CustomizeMathJax{\newcommand{\smalliiiintsl}{\mathop{\unicode{x2A0C}}\limits}}
\CustomizeMathJax{\newcommand{\smallointsl}{\mathop{\unicode{x222E}}\limits}}
\CustomizeMathJax{\newcommand{\smalloiintsl}{\mathop{\unicode{x222F}}\limits}}

\CustomizeMathJax{\let\smallintup\smallint}
\CustomizeMathJax{\newcommand{\smalliintup}{\mathop{\unicode{x222C}}\limits}}
\CustomizeMathJax{\newcommand{\smalliiintup}{\mathop{\unicode{x222D}}\limits}}
\CustomizeMathJax{\newcommand{\smalliiiintup}{\mathop{\unicode{x2A0C}}\limits}}
```

```
\CustomizeMathJax{\newcommand{\smallointup}{\mathop{\unicode{x222E}}\limits}}
\CustomizeMathJax{\newcommand{\smalloiintup}{\mathop{\unicode{x222F}}\limits}}

\CustomizeMathJax{\let\intslop\int}
\CustomizeMathJax{\newcommand{\iintslop}{\mathop{\unicode{x222C}}\limits}}
\CustomizeMathJax{\newcommand{\iiintslop}{\mathop{\unicode{x222D}}\limits}}
\CustomizeMathJax{\newcommand{\iiiintslop}{\mathop{\unicode{x2A0C}}\limits}}
\CustomizeMathJax{\let\ointslop\oint}
\CustomizeMathJax{\newcommand{\oiintslop}{\mathop{\unicode{x222F}}\limits}}
\CustomizeMathJax{\newcommand{\oiiintslop}{\mathop{\unicode{x2230}}\limits}}

\CustomizeMathJax{\let\intupop\int}
\CustomizeMathJax{\newcommand{\iintupop}{\mathop{\unicode{x222C}}\limits}}
\CustomizeMathJax{\newcommand{\iiintupop}{\mathop{\unicode{x222D}}\limits}}
\CustomizeMathJax{\newcommand{\iiiintupop}{\mathop{\unicode{x2A0C}}\limits}}
\CustomizeMathJax{\let\ointupop\oint}
\CustomizeMathJax{\newcommand{\oiintupop}{\mathop{\unicode{x222F}}\limits}}
\CustomizeMathJax{\newcommand{\oiiintupop}{\mathop{\unicode{x2230}}\limits}}

\CustomizeMathJax{\newcommand{\smalliint}{\mathop{\unicode{x222C}}\limits}}
\CustomizeMathJax{\newcommand{\smalliiint}{\mathop{\unicode{x222D}}\limits}}
\CustomizeMathJax{\newcommand{\smalliiiint}{\mathop{\unicode{x2A0C}}\limits}}
\CustomizeMathJax{\newcommand{\smalloint}{\mathop{\unicode{x222E}}\limits}}
\CustomizeMathJax{\newcommand{\smalloiint}{\mathop{\unicode{x222F}}\limits}}

\CustomizeMathJax{\let\intop\int}
\CustomizeMathJax{\newcommand{\iintop}{\mathop{\unicode{x222C}}\limits}}
\CustomizeMathJax{\newcommand{\iiintop}{\mathop{\unicode{x222D}}\limits}}
\CustomizeMathJax{\newcommand{\iiiintop}{\mathop{\unicode{x2A0C}}\limits}}
\CustomizeMathJax{\let\ointop\oint}
\CustomizeMathJax{\newcommand{\oiintop}{\mathop{\unicode{x222F}}\limits}}
\CustomizeMathJax{\newcommand{\oiiintop}{\mathop{\unicode{x2230}}\limits}}

\CustomizeMathJax{\newcommand{\oiint}{\mathop{\unicode{x222F}}\limits}}

\CustomizeMathJax{\newcommand{\bigcupdot}{\mathop{\unicode{x2A03}}}}
\CustomizeMathJax{\newcommand{\bigsqcap}{\mathop{\unicode{x2A05}}}}
\CustomizeMathJax{\newcommand{\xsol}{\mathop{\unicode{x29F8}}}}
\CustomizeMathJax{\newcommand{\xbsol}{\mathop{\unicode{x29F9}}}}
\CustomizeMathJax{\let\prodop\prod}
\CustomizeMathJax{\let\coprodop\coprod}
\CustomizeMathJax{\let\sumop\sum}
\CustomizeMathJax{\let\bigwedgeop\bigwedge}
\CustomizeMathJax{\let\bigveeop\bigvee}
\CustomizeMathJax{\let\bigcapop\bigcap}
\CustomizeMathJax{\let\bigcupop\bigcup}
\CustomizeMathJax{\let\xsolop\xsol}
\CustomizeMathJax{\let\xbsolop\xbsol}
\CustomizeMathJax{\let\bigodotop\bigodot}
\CustomizeMathJax{\let\bigoplusop\bigoplus}
\CustomizeMathJax{\let\bigotimesop\bigotimes}
\CustomizeMathJax{\let\bigcupdotop\bigcupdot}
\CustomizeMathJax{\let\biguplusop\biguplus}
\CustomizeMathJax{\let\bigsqcapop\bigsqcap}
\CustomizeMathJax{\let\bigsqcupop\bigsqcup}
```

```
\CustomizeMathJax{\newcommand{\ovhook}[1]{\mathord{#1\unicode{x00309}}}}
\CustomizeMathJax{\newcommand{\candra}[1]{\mathord{#1\unicode{x00310}}}}
\CustomizeMathJax{\newcommand{\oturnedcomma}[1]{\mathord{#1\unicode{x00312}}}}
\CustomizeMathJax{\newcommand{\ocommatopright}[1]{\mathord{#1\unicode{x00315}}}}
\CustomizeMathJax{\newcommand{\droang}[1]{\mathord{#1\unicode{x0031A}}}}
\CustomizeMathJax{\newcommand{\leftharpoonaccent}[1]{\mathord{#1\unicode{x020D0}}}}
\CustomizeMathJax{\newcommand{\rightharpoonaccent}[1]{\mathord{#1\unicode{x020D1}}}}
\CustomizeMathJax{\newcommand{\leftarrowaccent}[1]{\mathord{#1\unicode{x020D0}}}}
\CustomizeMathJax{\let\rightarrowaccent\vec}

\CustomizeMathJax{\newcommand{\leftrightarrowaccent}[1]{\mathord{#1\unicode{x020E1}}}}
\CustomizeMathJax{\newcommand{\annuity}[1]{\mathord{#1\unicode{x020E7}}}}
\CustomizeMathJax{\newcommand{\widebridgeabove}[1]{\mathord{#1\unicode{x020E9}}}}
\CustomizeMathJax{\newcommand{\asteraccent}[1]{\mathord{#1\unicode{x020F0}}}}

% neutralized:
\CustomizeMathJax{\newcommand{\braceld}{}}
\CustomizeMathJax{\newcommand{\bracerd}{}}
\CustomizeMathJax{\newcommand{\bracelu}{}}
\CustomizeMathJax{\newcommand{\braceru}{}}
\CustomizeMathJax{\newcommand{\braceex}{}}
\CustomizeMathJax{\newcommand{\bracemu}{}}
\CustomizeMathJax{\newcommand{\bracemd}{}}
\CustomizeMathJax{\newcommand{\parenld}{}}
\CustomizeMathJax{\newcommand{\parenrd}{}}
\CustomizeMathJax{\newcommand{\parenlu}{}}
\CustomizeMathJax{\newcommand{\parenru}{}}
\CustomizeMathJax{\newcommand{\bracketld}{}}
\CustomizeMathJax{\newcommand{\bracketrd}{}}
\CustomizeMathJax{\newcommand{\bracketlu}{}}
\CustomizeMathJax{\newcommand{\bracketru}{}}
\CustomizeMathJax{\newcommand{\bracketex}{}}
\CustomizeMathJax{\newcommand{\parenex}{}}

\CustomizeMathJax{\newcommand{lhook}{~}}
\CustomizeMathJax{\newcommand{rhook}{~}}
\CustomizeMathJax{\newcommand{relbar}{-}}
\CustomizeMathJax{\newcommand{Relbar}{=}}

\CustomizeMathJax{\newcommand{\mapstochar}{\mathrel{\unicode{x21A6}}}}

\CustomizeMathJax{\newcommand{\Zbar}{\mathord{\unicode{x0001B5}}}}
\CustomizeMathJax{\newcommand{\notchar}{\mathrel{\unicode{x000AC}}}}
\CustomizeMathJax{\newcommand{\upbackepsilon}{\mathord{\unicode{x03F6}}}}
\CustomizeMathJax{\newcommand{\smblkcircle}{\mathbin{\unicode{x02022}}}}
\CustomizeMathJax{\newcommand{\enleadertwodots}{\mathord{\unicode{x02025}}}}
\CustomizeMathJax{\newcommand{\unicodeellipsis}{\mathord{\unicode{x02026}}}}
\CustomizeMathJax{\newcommand{\mathellipsis}{\mathinner{\unicode{x02026}}}}
\CustomizeMathJax{\newcommand{\dprime}{\mathord{\unicode{x02033}}}}
\CustomizeMathJax{\newcommand{\trprime}{\mathord{\unicode{x02034}}}}
\CustomizeMathJax{\newcommand{\backdprime}{\mathord{\unicode{x02036}}}}
\CustomizeMathJax{\newcommand{\backtrprime}{\mathord{\unicode{x02037}}}}
\CustomizeMathJax{\newcommand{\caretinsert}{\mathord{\unicode{x02038}}}}
\CustomizeMathJax{\newcommand{\Exclam}{\mathord{\unicode{x0203C}}}}
```

```
177
178 \CustomizeMathJax{\newcommand{\hyphenbullet}{\mathord{\unicode{x02043}}}}
179 \CustomizeMathJax{\newcommand{\fracslash}{\mathbin{\unicode{x02044}}}}
180 \CustomizeMathJax{\newcommand{\Question}{\mathord{\unicode{x02047}}}}
181 \CustomizeMathJax{\newcommand{\closure}{\mathrel{\unicode{x02050}}}}
182 \CustomizeMathJax{\newcommand{\qprime}{\mathord{\unicode{x02057}}}}
183 \CustomizeMathJax{\newcommand{\vertoverlay}{\mathrel{\unicode{x020D2}}}}
184 \CustomizeMathJax{\newcommand{\enclosecircle}{\mathord{\unicode{x020DD}}}}
185 \CustomizeMathJax{\newcommand{\enclosesquare}{\mathord{\unicode{x020DE}}}}
186 \CustomizeMathJax{\newcommand{\enclosetriangle}{\mathord{\unicode{x020E4}}}}
187 \CustomizeMathJax{\newcommand{\Eulerconst}{\mathord{\unicode{x02107}}}}
188 \CustomizeMathJax{\newcommand{\turnediota}{\mathord{\unicode{x02129}}}}
189 \CustomizeMathJax{\newcommand{\Angstrom}{\mathord{\unicode{x0212B}}}}
190
191 \CustomizeMathJax{\newcommand{\sansLturned}{\mathord{\unicode{x02142}}}}
192 \CustomizeMathJax{\newcommand{\sansLmirrored}{\mathord{\unicode{x02143}}}}
193 \CustomizeMathJax{\newcommand{\Yup}{\mathord{\unicode{x02144}}}}
194 \CustomizeMathJax{\newcommand{\upand}{\mathbin{\unicode{x0214B}}}}
195 \CustomizeMathJax{\newcommand{\increment}{\mathord{\unicode{x02206}}}}
196 \CustomizeMathJax{\newcommand{\smallin}{\mathrel{\unicode{x0220A}}}}
197 \CustomizeMathJax{\newcommand{\nni}{\mathrel{\unicode{x0220C}}}}
198
199 \CustomizeMathJax{\newcommand{\smallni}{\mathrel{\unicode{x0220D}}}}
200 \CustomizeMathJax{\newcommand{\QED}{\mathord{\unicode{x0220E}}}}
201 \CustomizeMathJax{\newcommand{\vysmwhtcircle}{\mathbin{\unicode{x02218}}}}
202 \CustomizeMathJax{\newcommand{\vysmblkcircle}{\mathbin{\unicode{x02219}}}}
203 \CustomizeMathJax{\newcommand{\rightangle}{\mathord{\unicode{x0221F}}}}
204
205 \CustomizeMathJax{\newcommand{\Colon}{\mathrel{\unicode{x02237}}}}
206 \CustomizeMathJax{\newcommand{\dotminus}{\mathbin{\unicode{x02238}}}}
207 \CustomizeMathJax{\newcommand{\dashcolon}{\mathrel{\unicode{x02239}}}}
208 \CustomizeMathJax{\newcommand{\dotsminusdots}{\mathrel{\unicode{x0223A}}}}
209 \CustomizeMathJax{\newcommand{\kernelcontraction}{\mathrel{\unicode{x0223B}}}}
210 \CustomizeMathJax{\newcommand{\invlazys}{\mathbin{\unicode{x0223E}}}}
211
212 \CustomizeMathJax{\newcommand{\sinewave}{\mathord{\unicode{x0223F}}}}
213 \CustomizeMathJax{\newcommand{\nsime}{\mathrel{\unicode{x02244}}}}
214 \CustomizeMathJax{\newcommand{\simneqq}{\mathrel{\unicode{x02246}}}}
215 \CustomizeMathJax{\newcommand{\napprox}{\mathrel{\unicode{x02249}}}}
216 \CustomizeMathJax{\newcommand{\approxident}{\mathrel{\unicode{x0224B}}}}
217 \CustomizeMathJax{\newcommand{\backcong}{\mathrel{\unicode{x0224C}}}}
218
219 \CustomizeMathJax{\newcommand{\nasymp}{\mathrel{\unicode{x0226D}}}}
220 \CustomizeMathJax{\newcommand{\nlesssim}{\mathrel{\unicode{x02274}}}}
221 \CustomizeMathJax{\newcommand{\ngtrsim}{\mathrel{\unicode{x02275}}}}
222 \CustomizeMathJax{\newcommand{\nlessgtr}{\mathrel{\unicode{x02278}}}}
223 \CustomizeMathJax{\newcommand{\ngtrless}{\mathrel{\unicode{x02279}}}}
224
225 \CustomizeMathJax{\newcommand{\nsubset}{\mathrel{\unicode{x02284}}}}
226 \CustomizeMathJax{\newcommand{\nsupset}{\mathrel{\unicode{x02285}}}}
227
228 \CustomizeMathJax{\newcommand{\cupleftarrow}{\mathbin{\unicode{x0228C}}}}
229 \CustomizeMathJax{\newcommand{\cupdot}{\mathbin{\unicode{x0228D}}}}
230 \CustomizeMathJax{\newcommand{\circledequal}{\mathbin{\unicode{x0229C}}}}
231
```

```
\CustomizeMathJax{\newcommand{\assert}{\mathrel{\unicode{x022A6}}}}
\CustomizeMathJax{\newcommand{\VDash}{\mathrel{\unicode{x022AB}}}}
\CustomizeMathJax{\newcommand{\prurel}{\mathrel{\unicode{x022B0}}}}

\CustomizeMathJax{\newcommand{\origof}{\mathrel{\unicode{x022B6}}}}
\CustomizeMathJax{\newcommand{\smallprod}{\mathop{\unicode{x0220F}}}}% not small
\CustomizeMathJax{\newcommand{\smallcoprod}{\mathop{\unicode{x02210}}}}% not small
\CustomizeMathJax{\newcommand{\smallsum}{\mathop{\unicode{x02211}}}}% not small
\CustomizeMathJax{\newcommand{\Hfraktur}{\mathord{\unicode{x1D525}}}}
\CustomizeMathJax{\newcommand{\dsol}{\mathbin{\unicode{x029F6}}}}
\CustomizeMathJax{\newcommand{\rsolbar}{\mathbin{\unicode{x029F7}}}}

\CustomizeMathJax{\newcommand{\eqless}{\mathrel{\unicode{x022DC}}}}
\CustomizeMathJax{\newcommand{\eqgtr}{\mathrel{\unicode{x022DD}}}}
\CustomizeMathJax{\newcommand{\npreccurlyeq}{\mathrel{\unicode{x022E0}}}}
\CustomizeMathJax{\newcommand{\nsucccurlyeq}{\mathrel{\unicode{x022E1}}}}
\CustomizeMathJax{\newcommand{\nsqsubseteq}{\mathrel{\unicode{x022E2}}}}
\CustomizeMathJax{\newcommand{\nsqsupseteq}{\mathrel{\unicode{x022E3}}}}
\CustomizeMathJax{\newcommand{\sqsubsetneq}{\mathrel{\unicode{x022E4}}}}
\CustomizeMathJax{\newcommand{\sqsupsetneq}{\mathrel{\unicode{x022E5}}}}
\CustomizeMathJax{\newcommand{\nvartriangleleft}{\mathrel{\unicode{x022EA}}}}
\CustomizeMathJax{\newcommand{\nvartriangleright}{\mathrel{\unicode{x022EB}}}}

\CustomizeMathJax{\newcommand{\vdotsmath}{\mathrel{\unicode{x022EE}}}}
\CustomizeMathJax{\newcommand{\unicodecdots}{\mathord{\unicode{x022EF}}}}
\CustomizeMathJax{\newcommand{\adots}{\mathrel{\unicode{x022F0}}}}
\CustomizeMathJax{\newcommand{\succneq}{\mathrel{\unicode{x02AB2}}}}
\CustomizeMathJax{\newcommand{\preceqq}{\mathrel{\unicode{x02AB3}}}}
\CustomizeMathJax{\newcommand{\succeqq}{\mathrel{\unicode{x02AB4}}}}
\CustomizeMathJax{\newcommand{\precneq}{\mathrel{\unicode{x02AB1}}}}

\CustomizeMathJax{\newcommand{\mapsfrom}{\mathrel{\unicode{x021A4}}}}

\CustomizeMathJax{\newcommand{\longmapsfrom}{\mathrel{\unicode{x027FB}}}}

\CustomizeMathJax{\newcommand{\diameter}{\mathord{\unicode{x02300}}}}
\CustomizeMathJax{\newcommand{\coloneq}{\mathrel{\unicode{x02254}}}}
\CustomizeMathJax{\newcommand{\eqcolon}{\mathrel{\unicode{x02255}}}}
\CustomizeMathJax{\newcommand{\arceq}{\mathrel{\unicode{x02258}}}}
\CustomizeMathJax{\newcommand{\wedgeq}{\mathrel{\unicode{x02259}}}}
\CustomizeMathJax{\newcommand{\veeeq}{\mathrel{\unicode{x0225A}}}}

\CustomizeMathJax{\newcommand{\stareq}{\mathrel{\unicode{x0225B}}}}
\CustomizeMathJax{\newcommand{\eqdef}{\mathrel{\unicode{x0225D}}}}
\CustomizeMathJax{\newcommand{\measeq}{\mathrel{\unicode{x0225E}}}}
\CustomizeMathJax{\newcommand{\questeq}{\mathrel{\unicode{x0225F}}}}
\CustomizeMathJax{\newcommand{\nequiv}{\mathrel{\unicode{x02262}}}}
\CustomizeMathJax{\newcommand{\Equiv}{\mathrel{\unicode{x02263}}}}

\CustomizeMathJax{\newcommand{\house}{\mathord{\unicode{x02302}}}}

\CustomizeMathJax{\newcommand{\musicalnote}{\mathord{\unicode{x0266A}}}}
\CustomizeMathJax{\newcommand{\degree}{\mathord{\unicode{x000B0}}}}
\CustomizeMathJax{\newcommand{\mathsection}{\mathord{\unicode{x000A7}}}}
\CustomizeMathJax{\newcommand{\mathparagraph}{\mathord{\unicode{x000B6}}}}
```

```
\CustomizeMathJax{\newcommand{\checkmarkmath}{\mathord{\unicode{x02713}}}}
\CustomizeMathJax{\newcommand{\invnot}{\mathord{\unicode{x02310}}}}

\CustomizeMathJax{\newcommand{\mathvisiblespace}{\mathord{\unicode{x02423}}}}
\CustomizeMathJax{\newcommand{\mdlgblksquare}{\mathord{\unicode{x025A0}}}}
\CustomizeMathJax{\newcommand{\mdlgwhtsquare}{\mathord{\unicode{x025A1}}}}

\CustomizeMathJax{\newcommand{\bigblacktriangleup}{\mathord{\unicode{x025B2}}}}
\CustomizeMathJax{\newcommand{\varbigtriangleup}{\mathord{\unicode{x025B3}}}}

\CustomizeMathJax{\newcommand{\bigblacktriangledown}{\mathord{\unicode{x025BC}}}}
\CustomizeMathJax{\newcommand{\varbigtriangledown}{\mathord{\unicode{x025BD}}}}
\CustomizeMathJax{\newcommand{\Longmapsfrom}{\mathrel{\unicode{x027FD}}}}

% bug in print font:
\CustomizeMathJax{\newcommand{\mdlgblkdiamond}{\mathord{\unicode{x025C6}}}}

\CustomizeMathJax{\newcommand{\mdlgwhtdiamond}{\mathord{\unicode{x025C7}}}}
\CustomizeMathJax{\newcommand{\Longmapsto}{\mathrel{\unicode{x027FE}}}}
\CustomizeMathJax{\newcommand{\fisheye}{\mathord{\unicode{x025C9}}}}
\CustomizeMathJax{\newcommand{\mdlgwhtlozenge}{\mathord{\unicode{x025CA}}}}
\CustomizeMathJax{\newcommand{\mdlgwhtcircle}{\mathbin{\unicode{x025CB}}}}
\CustomizeMathJax{\newcommand{\bullseye}{\mathord{\unicode{x025CE}}}}
\CustomizeMathJax{\newcommand{\mdlgblkcircle}{\mathord{\unicode{x025CF}}}}

\CustomizeMathJax{\newcommand{\Nwarrow}{\mathrel{\unicode{x021D6}}}}
\CustomizeMathJax{\newcommand{\Nearrow}{\mathrel{\unicode{x021D7}}}}
\CustomizeMathJax{\newcommand{\Searrow}{\mathrel{\unicode{x021D8}}}}
\CustomizeMathJax{\newcommand{\Swarrow}{\mathrel{\unicode{x021D9}}}}

\CustomizeMathJax{\newcommand{\Mapsfrom}{\mathord{\unicode{x02906}}}}
\CustomizeMathJax{\newcommand{\smwhtcircle}{\mathord{\unicode{x025E6}}}}
\CustomizeMathJax{\newcommand{\smwhtdiamond}{\mathbin{\unicode{x022C4}}}}
\CustomizeMathJax{\newcommand{\Mapsto}{\mathord{\unicode{x02907}}}}

\CustomizeMathJax{\let\ngets\nleftarrow}
\CustomizeMathJax{\let\nsimeq\nsime}
\CustomizeMathJax{\let\nle\nleq}
\CustomizeMathJax{\let\nge\ngeq}

\end{warpMathJax}
```

File 249 **lwarp-lineno.sty**

§ 357 Package

lineno

(*Emulates or patches code by* Stephan I. Böttcher.)

Pkg lineno lineno is partly emulated, but mostly ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{lineno}[2005/11/02]

\newcommand*\resetlinenumber[1][\@ne]{}
```

```
3
4 \def\linenumbers{%
5     \@ifnextchar[{\resetlinenumber}%]
6                 {\@ifstar{\resetlinenumber}{}}%
7     }
8
9 \newcommand*{\nolinenumbers}{}
10
11 \@namedef{linenumbers*}{\par\linenumbers*}
12 \@namedef{runninglinenumbers*}{\par\runninglinenumbers*}
13
14 \def\endlinenumbers{\par}
15 \let\endrunninglinenumbers\endlinenumbers
16 \let\endpagewiselinenumbers\endlinenumbers
17 \expandafter\let\csname endlinenumbers*\endcsname\endlinenumbers
18 \expandafter\let\csname endrunninglinenumbers*\endcsname\endlinenumbers
19 \let\endnolinenumbers\endlinenumbers
20
21 \def\pagewiselinenumbers{\linenumbers\setpagewiselinenumbers}
22
23 \def\runninglinenumbers{\setrunninglinenumbers\linenumbers}
24
25 \def\setpagewiselinenumbers{}
26
27 \def\setrunninglinenumbers{}
28
29 \def\linenomath{}%
30 \@namedef{linenomath*}{}%
31 \def\endlinenomath{}
32 \expandafter\let\csname endlinenomath*\endcsname\endlinenomath
33
34 \let\linelabel\label
35
36 \def\switchlinenumbers{\@ifstar{}{}}
37 \def\setmakelinenumbers#1{\@ifstar{}{}}
38
39 \def\leftlinenumbers{\@ifstar{}{}}
40 \def\rightlinenumbers{\@ifstar{}{}}
41
42 \newcounter{linenumber}
43 \newcount\c@pagewiselinenumber
44 \let\c@runninglinenumber\c@linenumber
45
46 \def\runningpagewiselinenumbers{}
47 \def\realpagewiselinenumbers{}
48
49
50 \NewDocumentCommand\modulolinenumbers{s o}{}
51
52 \chardef\c@linenumbermodulo=5
53 \modulolinenumbers[1]
54
55 \newcommand*\firstlinenumber[1]{}
56
57 \newcommand\internallinenumbers{}
```

```
\let\endinternallinenumbers\endlinenumbers
\@namedef{internallinenumbers*}{\internallinenumbers}
\expandafter\let\csname endinternallinenumbers*\endcsname\endlinenumbers

\newcommand*{\linenoplaceholder}[1]{% redefine per language
    (line number reference for \detokenize\expandafter{#1})
}

\newcommand*{\lineref}[2][]{\linenoplaceholder{#2}}
\newcommand*{\linerefp}[2][]{\linenoplaceholder{#2}}
\newcommand*{\linerefr}[2][]{\linenoplaceholder{#2}}

\newcommand\quotelinenumbers
   {\@ifstar\linenumbers{\@ifnextchar[\linenumbers{\linenumbers*}}}

\newdimen\linenumbersep
\newdimen\linenumberwidth
\newdimen\quotelinenumbersep

\quotelinenumbersep=\linenumbersep
\let\quotelinenumberfont\linenumberfont

\def\linenumberfont{\normalfont\tiny\sffamily}


\linenumberwidth=10pt
\linenumbersep=10pt

\def\thelinenumber{}

\def\LineNumber{}
\def\makeLineNumber{}
\def\makeLineNumberLeft{}
\def\makeLineNumberRight{}
\def\makeLineNumberOdd{}
\def\makeLineNumberEven{}
\def\makeLineNumberRunning{}


\newenvironment{numquote}     {\quote}{\endquote}
\newenvironment{numquotation} {\quotation}{\endquotation}
\newenvironment{numquote*}    {\quote}{\endquote}
\newenvironment{numquotation*}{\quotation}{\endquotation}

\newdimen\bframerule
\bframerule=\fboxrule

\newdimen\bframesep
\bframesep=\fboxsep

\newenvironment{bframe}
{%
    \LWR@forceminwidth{\bframerule}%
    \BlockClass[
        border:\LWR@printlength{\LWR@atleastonept} solid black ; %
```

```
        padding:\LWR@printlength{\bframesep}%
    ]{bframe}
}
{\endBlockClass}
```

File 250 **lwarp-lips.sty**

§ 358 Package lips

(*Emulates or patches code by* Matt Swift.)

Pkg lips lips is emulated.

```
% \LWR@ProvidesPackageDrop{lips}
\PackageInfo{lwarp}{Using the lwarp version of package ‘lips’.}%
\ProvidesPackage{lwarp-lips}[2001/08/31]

\NewDocumentCommand{\Lips}{}{\textellipsis}

\NewDocumentCommand{\BracketedLips}{}{[\textellipsis]}

\let\lips\Lips
\let\olips\lips

\DeclareOption*{}
\DeclareOption{mla}{
\let\lips\BracketedLips
}
\ProcessOptions\relax

\newcommand \LPNobreakList {}
```

File 251 **lwarp-listings.sty**

§ 359 Package listings

(*Emulates or patches code by* Carsten Heinz, Brooks Moses, Jobst Hoffmann.)

Pkg listings listings is supported with some limitations. Text formatting and escape characters are not yet supported.

```
\LWR@ProvidesPackagePass{listings}[2018/09/02]
```

Force flexible columns. Fixed columns inserts spaces in the PDF output.

```
\lst@column@flexible
```

Patches to embed listings inside pre tags:

```
\let\LWR@origlst@Init\lst@Init
```

```
\let\LWR@origlst@DeInit\lst@DeInit

\let\LWR@origlsthkEveryPar\lsthk@EveryPar

\renewcommand{\l@lstlisting}[2]{\hypertocfloat{1}{lstlisting}{lol}{#1}{#2}}
```

`\lstset` {⟨*options*⟩}

Use the listings `literate` option to replace HTML entities:

```
\def\lstset@#1{\endgroup%
%  \ifx\@empty#1%
%         \@empty%
%     \else%
        \setkeys{lst}{%
            #1%
            ,literate=%
            {<}{\HTMLentity{lt}}{4}%
            {>}{\HTMLentity{gt}}{4}%
            {'}{\HTMLentity{apos}}{6}%
            {`}{\HTMLentity{grave}}{7}%
```

The ampersand is not treated here, as the result is inconsistent spacing. It is nevertheless converted to `&` elsewhere. Sanitizing the double quote interferes with listings' conversion of visible spaces inside strings.

```
        }%
%     \fi%
}
```

`\lst@Init` {⟨*backslash-processing*⟩} Done at the start of a listing.

```
\renewcommand{\lst@Init}[1]{%
```

Perform the listings initialization:

```
\LWR@traceinfo{lst@Init}%
```

`\LWR@forcenewpage` is moved to the start to avoid a spurrious bug with paragraph handling and conditionals.

```
\lst@ifdisplaystyle%        lwarp
    \LWR@forcenewpage%      lwarp
\fi%                        lwarp
```

Escapes do not work yet, and are disabled:

```
\let\lst@ifmathescape\iffalse%      lwarp
\let\lst@DefEsc\relax%              lwarp
\def\lst@escapebegin{}%             lwarp
\def\lst@escapeend{}%               lwarp

\renewcommand*{\@captype}{lstlisting}%      lwarp
    \let\lst@aboveskip\z@\let\lst@belowskip\z@%     lwarp
    \gdef\lst@boxpos{t}%            lwarp
    \let\lst@frame\@empty%          lwarp
    \let\lst@frametshape\@empty%    lwarp
    \let\lst@framershape\@empty%    lwarp
```

```
    \let\lst@framebshape\@empty%    lwarp
    \let\lst@framelshape\@empty%    lwarp
    \lstframe@\lst@frameround ffff\relax%   lwarp
    \lst@multicols\@empty%  lwarp
    \begingroup%
```

Inside the listing, temporarily prevent underfull \hbox warnings.

```
            \hbadness=10000\relax%
    \ifx\lst@float\relax\else%
        \edef\@tempa{\noexpand\lst@beginfloat{lstlisting}[\lst@float]}%
        \expandafter\@tempa%
    \fi%
    \ifx\lst@multicols\@empty\else%
        \edef\lst@next{\noexpand\multicols{\lst@multicols}}%
        \expandafter\lst@next%
    \fi%
    \ifhmode\ifinner \lst@boxtrue \fi\fi%
    \lst@ifbox%
        \lsthk@BoxUnsafe%
        \hbox to\z@\bgroup%
             $\if t\lst@boxpos \vtop%
        \else \if b\lst@boxpos \vbox%
        \else \vcenter \fi\fi%
        \bgroup \par\noindent%
    \else%
        \lst@ifdisplaystyle%
            \lst@EveryDisplay%
            \par\penalty-50\relax%
            \vspace\lst@aboveskip%
        \fi%
    \fi%
    \normalbaselines%
    \abovecaptionskip\lst@abovecaption\relax%
    \belowcaptionskip\lst@belowcaption\relax%
    \lst@MakeCaption t%
```

Use the overall listing label instead of the line number label:

```
\LWR@traceinfo{lst@Init: defining current label !\@currentlabel!}%
    \let\LWR@listings@currentlabel\@currentlabel%           lwarp
\LWR@traceinfo{lst@Init: defining current label !\cref@currentlabel!}%
    \let\LWR@listings@cref@currentlabel\cref@currentlabel%   lwarp

\LWR@traceinfo{lst@Init: preinit and init}%
    \lsthk@PreInit \lsthk@Init%

    \let\@currentlabel\LWR@listings@currentlabel%           lwarp
    \let\cref@currentlabel\LWR@listings@cref@currentlabel%   lwarp

\LWR@traceinfo{lst@Init: M}%
    \lst@ifdisplaystyle
        \global\let\lst@ltxlabel\@empty
        \if@inlabel
            \lst@ifresetmargins
                \leavevmode
            \else
```

```
                \xdef\lst@ltxlabel{\the\everypar}%
                \lst@AddTo\lst@ltxlabel{%
                    \global\let\lst@ltxlabel\@empty
                    \everypar{\lsthk@EveryLine\lsthk@EveryPar}}%
            \fi
        \fi
        \everypar\expandafter{\lst@ltxlabel
                              \lsthk@EveryLine\lsthk@EveryPar}%
    \else
        \everypar{}
        \let\lst@NewLine\@empty
    \fi
\LWR@traceinfo{lst@Init: P}%
    \lsthk@InitVars \lsthk@InitVarsBOL
    \lst@Let{13}\lst@MProcessListing
    \let\lst@Backslash#1%
    \lst@EnterMode{\lst@Pmode}{\lst@SelectCharTable}%
    \lst@InitFinalize%
\LWR@traceinfo{lst@Init: S}%
```

Avoids extra horizontal space:

```
\def\lst@framelr{}%     lwarp
```

```
\LWR@traceinfo{lst@Init: finished origlst@Init}%
\lst@ifdisplaystyle%    lwarp
```

Creating a display.

Disable line numbers, produce the <pre>, then reenable line numbers.

```
    \LWR@traceinfo{lst@Init: About to create verbatim.}%  lwarp
    \let\lsthk@EveryPar\relax%                  lwarp

    \LWR@atbeginverbatim{programlisting}%       lwarp

    \let\lsthk@EveryPar\LWR@origlsthkEveryPar%  lwarp
\else%                                          lwarp
```

Inline, so open a :

```
    \ifbool{LWR@verbtags}{\LWR@htmltag{%        lwarp
        span class=\textquotedbl{}inlineprogramlisting\textquotedbl%    lwarp
    }}{}%                                       lwarp
\fi%                                            lwarp
\LWR@traceinfo{lst@Init: done}%
}
```

`\lst@DeInit` Done at the end of a listing.

```
\renewcommand*{\lst@DeInit}{%
\LWR@traceinfo{lst@DeInit}%
\lst@ifdisplaystyle%
```

Creating a display.

Disable line numbers, produce the </pre>, then reenable line numbers:

```
    \let\lsthk@EveryPar\relax%
    \LWR@afterendverbatim%
```

```
    \let\lsthk@EveryPar\LWR@origlsthkEveryPar%
\else%
```

Inline, so create the closing :

```
    \ifbool{LWR@verbtags}{\noindent\LWR@htmltag{/span}}{}%
\fi%
```

Final listings deinit:

```
    \lst@XPrintToken \lst@EOLUpdate
    \global\advance\lst@newlines\m@ne
    \lst@ifshowlines
        \lst@DoNewLines
    \else
        \setbox\@tempboxa\vbox{\lst@DoNewLines}%
    \fi
    \lst@ifdisplaystyle \par\removelastskip \fi
    \lsthk@ExitVars\everypar{}\lsthk@DeInit\normalbaselines\normalcolor
    \lst@MakeCaption b%
    \lst@ifbox
        \egroup $\hss \egroup
        \vrule\@width\lst@maxwidth\@height\z@\@depth\z@
    \else
        \lst@ifdisplaystyle
            \par\penalty-50\vspace\lst@belowskip
        \fi
    \fi
    \ifx\lst@multicols\@empty\else
        \def\lst@next{\global\let\@checkend\@gobble
                      \endmulticols
                      \global\let\@checkend\lst@@checkend}
        \expandafter\lst@next
    \fi
    \ifx\lst@float\relax\else
        \expandafter\lst@endfloat
    \fi
    \endgroup
\LWR@traceinfo{lst@DeInit done}%
}
```

`\lst@MakeCaption` {⟨*t/b*⟩}

This is called BOTH at the top and at the bottom of each listing.

Patched for lwarp.

```
\def\lst@MakeCaption#1{%
\LWR@traceinfo{lst@MakeCaption at #1}%
  \lst@ifdisplaystyle
\LWR@traceinfo{lst@MakeCaption: making a listings display caption}%
    \ifx #1t%
         \ifx\lst@@caption\@empty\expandafter\lst@HRefStepCounter \else
                                    \expandafter\refstepcounter
         \fi {lstlisting}%
% \LWR@traceinfo{About to assign label: !\lst@label!}%
%         \ifx\lst@label\@empty\else
% \label{\lst@label}\fi
% \LWR@traceinfo{Finished assigning the label.}%
```

```
        \let\lst@arg\lst@intname \lst@ReplaceIn\lst@arg\lst@filenamerpl
        \global\let\lst@name\lst@arg \global\let\lstname\lst@name
        \lst@ifnolol\else
            \ifx\lst@@caption\@empty
                \ifx\lst@caption\@empty
                    \ifx\lst@intname\@empty
                    \else
                        \def\lst@temp{ }%
                        \ifx\lst@intname\lst@temp \else
```

This code places a contents entry for a non-float. This would have to be modified for lwarp:

```
\LWR@traceinfo{lst@MakeCaption: addcontents lst@name: -\lst@name-}%
%                           \addcontentsline{lol}{lstlisting}{\lst@name}
                        \fi
                    \fi
                \fi
            \else
```

This would have to be modified for lwarp:

```
\LWR@traceinfo{lst@MakeCaption: addcontents lst@@caption: -\lst@@caption-}%
                  \addcontentsline{lol}{lstlisting}%
{\protect\numberline{\thelstlisting}%
{\protect\ignorespaces \LWR@isolate{\lst@@caption} \protect\relax}}%
            \fi
         \fi
     \fi
    \ifx\lst@caption\@empty\else
\LWR@traceinfo{lst@MakeCaption: lst@caption not empty-}%
        \lst@IfSubstring #1\lst@captionpos
            {\begingroup
\LWR@traceinfo{lst@MakeCaption: at the selected position}%
```

These space and box commands are not needed for HTML output:

```
%               \let\@@vskip\vskip
%               \def\vskip{\afterassignment\lst@vskip \@tempskipa}%
%               \def\lst@vskip{\nobreak\@@vskip\@tempskipa\nobreak}%
%               \par\@parboxrestore\normalsize\normalfont % \noindent (AS)
%               \ifx #1t\allowbreak \fi
             \ifx\lst@title\@empty
```

New lwarp code to create a caption:

```
                    \LWR@stoppars%      lwarp
                  \lst@makecaption\fnum@lstlisting{\ignorespaces \lst@caption}
             \else
```

New lwarp code to create a title:

```
%                  \lst@maketitle\lst@title % (AS)
\LWR@traceinfo{lst@MakeCaption: Making title: \lst@title}%
\begin{BlockClass}{lstlistingtitle}%    lwarp
\lst@maketitle\lst@title%               lwarp
\end{BlockClass}%                       lwarp
             \fi%
\LWR@traceinfo{lst@MakeCaption: About to assign label: !\lst@label!}%
        \ifx\lst@label\@empty\else%
\leavevmode% gets rid of bad space factor error
```

```
\GetTitleStringExpand{\lst@caption}%
\edef\LWR@lntemp{\GetTitleStringResult}%
\edef\@currentlabelname{\detokenize\expandafter{\LWR@lntemp}}%
\label{\lst@label}\fi%
\LWR@traceinfo{lst@MakeCaption: Finished assigning the label.}%
```

Not needed for lwarp:

```
%              \ifx #1b\allowbreak \fi
             \endgroup}{}%
    \fi
\LWR@traceinfo{lst@MakeCaption: end of making a listings display caption}%
  \else
\LWR@traceinfo{lst@MakeCaption: INLINE}%
  \fi
\LWR@traceinfo{lst@MakeCaption: done at #1}%
}

\renewcommand{\lst@maketitle}[1]{%
    \LWR@isolate{#1}%
}%

```

line numbers Patched to keep left line numbers outside of the left margin, and place right line numbers in a field `\VerbatimHTMLWidth` wide.

```
\lst@Key{numbers}{none}{%
    \let\lst@PlaceNumber\@empty
    \lstKV@SwitchCases{#1}%
    {none:\\%
     left:\def\lst@PlaceNumber{%
```

For now, lwarp places left line numbers inline. Ideally the entire line would be moved to the right, but conflicts with list indenting occurs.

```
%         \LWR@origllap{
            \LWR@orignormalfont%
            \lst@numberstyle{\thelstnumber}\kern\lst@numbersep%
%         }
    }\\%
     right:\def\lst@PlaceNumber{\LWR@origrlap{\LWR@orignormalfont
                \kern 6in \kern\lst@numbersep
                \lst@numberstyle{\thelstnumber}}}%
    }{\PackageError{lwarp-listings}{Numbers #1 unknown}\@ehc}}
```

File 252 **lwarp-listliketab.sty**

§ 360 Package

listliketab

Pkg listliketab listliketab is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{listliketab}[2005/01/09]
```

```
\newcommand*{\storestyleof}[1]{}
\newcommand*{\storeliststyle}{}
\newenvironment{listliketab}{}{}
```

File 253 **lwarp-lltjext.sty**

§ 361 Package

lltjext

(*Emulates or patches code by* The LuaTeX-ja project team.)

Pkg lltjext lltjext is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{lltjext}[2018/10/07]

\protected\def\yoko{%
  \directlua{luatexja.direction.set_list_direction(4, 'yoko')}%
}
\protected\def\tate{\yoko}
\protected\def\dtou{\yoko}
\protected\def\utod{\yoko}

\define@key[ltj]{japaram}{direction}{}

\yoko

\DeclareExpandableDocumentCommand{\rensuji}{s o m}{#3}

\DeclareDocumentCommand{\layoutfloat}{d() o m}{}

\DeclareDocumentCommand{\DeclareLayoutCaption}{m d<> d() o}{}

\LetLtxMacro\pcaption\caption

\DeclareDocumentCommand{\layoutcaption}{d<> d() o}{}

\let\captiondir\relax
\RenewDocumentEnvironment{LWR@HTML@minipage}{d<> O{t} O{} O{t} m}
    {\LWR@HTML@sub@minipage{#2}{#3}{#4}{#5}}
    {\endLWR@HTML@sub@minipage}

\RenewDocumentCommand{\LWR@HTML@parbox}{d<> O{t} O{} O{t} m +m}
{
\LWR@traceinfo{parbox of width #4}%
\begin{minipage}[#2][#3][#4]{#5}%
#6
\end{minipage}%
}

\RenewDocumentCommand{\pbox}{d<> O{0pt} O{c} m}{%
\global\booltrue{LWR@minipagefullwidth}%
\parbox{#2}{#4}%
}
```

File 254 **lwarp-longtable.sty**

§ 362 Package

longtable

(*Emulates or patches code by* David Carlisle.)

Pkg longtable longtable is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{longtable}[2014/10/28]
```

Use one of either \endhead or \endfirsthead for both print and HTML, and use a \warpprintonly macro to disable the other head phrase, and also the \endfoot and \endfirstfoot phrases. (See section 8.10.4 if using threeparttablex.)

```
\begin{longtable}{ [column specifiers] }
[ . . . ] \endfirsthead   % or \endhead, for print and HTML
\warpprintonly{          % not used in HTML
  [ . . . ] \endhead     % or \endfirsthead
  [ . . . ] \endfoot
  [ <lastfoot macros> ] \endlastfoot
}
. . .  table contents . . .
\warpHTMLonly{
  [ <lastfoot macros> ]   % HTML last footer, without \endfoot
                                                % or \endlastfoot.
}
\end{longtable}
```

⚠ Misplaced \noalign Use the \warpprintonly macro instead of the warpprint environment. Doing so helps avoid "Misplaced \noalign." when using \begin{warpprint}.

⚠ \kill \kill is ignored, place a \kill line inside

```
\begin{warpprint} . . .  \end{warpprint}
```

or place it inside \warpprintonly.

⚠ lateximage longtable is not supported inside a lateximage.

See:
http://tex.stackexchange.com/questions/43006/why-is-input-not-expandable

Used to detect more than one of \endhead and \endfirsthead in use for HTML at the same time.

```
\newbool{LWR@longtable@havehead}
\boolfalse{LWR@longtable@havehead}
```

Env longtable * [⟨*horizalignment*⟩] {⟨*colspec*⟩} Emulates the longtable environment.

Per the caption package, the starred version steps the counter per caption. The unstarred version steps the counter once at the beginning, but not at each caption.

Options [c], [l], and [r] are ignored.

```
\newenvironment{longtable*}[2][]{%
    \LWR@floatbegin{table}%
    \ifdef{\setcaptiontype}{% caption package:
        \setcaptiontype{\LTcaptype}%
        \caption@setoptions{longtable}%
        \caption@setoptions{@longtable}%
        \caption@LT@setup%
    }{% w/o caption package:
        \renewcommand*{\@captype}{\LTcaptype}%
    }%
    \booltrue{LWR@starredlongtable}%
    \boolfalse{LWR@longtable@havehead}%
    \let\captionlistentry\LWR@LTcaptionlistentry%
    \tabular{#2}%
}
{\endtabular\LWR@floatend}

\newenvironment{longtable}[2][]{%
    \LWR@floatbegin{table}%
    \ifdef{\setcaptiontype}{% caption package:
        \setcaptiontype{\LTcaptype}%
        \caption@setoptions{longtable}%
        \caption@setoptions{@longtable}%
        \caption@LT@setup%
    }{% w/o caption package:
        \renewcommand*{\@captype}{\LTcaptype}%
    }%
    \refstepcounter{\LTcaptype}%
    \boolfalse{LWR@longtable@havehead}%
    \let\captionlistentry\LWR@LTcaptionlistentry%
    \tabular{#2}%
}
{\endtabular\LWR@floatend}
```

Provided for compatibility, but ignored:

```
\newcounter{LTchunksize}
```

Error for heads which should have been in `\warpprintonly`:

```
\newcommand*{\LWR@longtable@headerror}{%
    \PackageError{lwarp-longtable}
    {For longtable:\MessageBreak
    1: Keep either one of an \protect\endhead\space or\MessageBreak
        \space\protect\endfirsthead\space phrase as-is,\MessageBreak
        \space to be used by both print and HTML.\MessageBreak
    2: Place any other \protect\end... phrases inside a\MessageBreak
        \space\protect\warpprintonly\space macro,
            to be ignored by HTML.\MessageBreak
    3: At the end of the table,\MessageBreak
```

```
        \space add a final footer for HTML\MessageBreak
        \space inside a \protect\warpHTMLonly\space macro.
            This can be\MessageBreak
        \space a copy of an \protect\endfoot\space or
            \protect\endfirstfoot\MessageBreak
        \space phrase, but without the actual \protect\endfoot\MessageBreak
        \space or \protect\endfirstfoot\space macros.\MessageBreak
        \space If using threeparttablex, add\MessageBreak
        \space \protect\insertTableNotes\space here,
            optionally with\MessageBreak
        \space \protect\UseMinipageWidths\space in front.\MessageBreak
    See the Lwarp documentation regarding\MessageBreak
    longtables and threeparttablex}
    {See the Lwarp documentation regading longtables and threeparttablex.}
}
```

Error if more than one of `\endhead` or `\endfirsthead` is outside of `warpprintonly`.

```
\newcommand*{\LWR@longtable@maybeheaderror}{%
\ifbool{LWR@longtable@havehead}%
    {\LWR@longtable@headerror}%
    {%
        \booltrue{LWR@longtable@havehead}
        \LWR@tabularendofline% throws away options //[dim] and //*
    }%
}
```

Error if more than one of these is outside of `warpprint`.

```
\def\endhead{\LWR@longtable@maybeheaderror}
\def\endfirsthead{\LWR@longtable@maybeheaderror}
```

Error if ANY of these is outside of `warpprint`.

```
\def\endfoot{\LWR@longtable@headerror}
\def\endlastfoot{\LWR@longtable@headerror}


\providecommand*{\LWR@HTML@tabularnewline}{\LWR@tabularendofline}
\LWR@formatted{tabularnewline}

\newcommand{\setlongtables}{}% Obsolete command, does nothing.
\newlength{\LTleft}
\newlength{\LTright}
\newlength{\LTpre}
\newlength{\LTpost}
\newlength{\LTcapwidth}


\LetLtxMacro\LWR@origkill\kill
\renewcommand*{\kill}{\LWR@tabularendofline}
\appto\LWR@restoreorigformatting{%
\LetLtxMacro\kill\LWR@origkill%
}
```

File 255 **lwarp-lpic.sty**

§ 363 Package

lpic

(*Emulates or patches code by* R. Matveyev.)

Pkg lpic lpic is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{lpic}[2010/12/23]

\BeforeBeginEnvironment{lpic}{%
    \begin{lateximage}[-lpic-~\PackageDiagramAltText]%
}

\AfterEndEnvironment{lpic}{\end{lateximage}}
```

File 256 **lwarp-lscape.sty**

§ 364 Package

lscape

(*Emulates or patches code by* D. P. Carlisle.)

Pkg lscape lscape is ignored.

for HTML output: Discard all options for lwarp-lscape.

```
\LWR@ProvidesPackageDrop{lscape}[2000/10/22]

\newenvironment*{landscape}{}{}
```

File 257 **lwarp-ltablex.sty**

§ 365 Package

ltablex

(*Emulates or patches code by* Anil K. Goel.)

Pkg ltablex ltablex is emulated by lwarp.

for HTML output: Relies on tabularx.

```
\RequirePackage{longtable}
\RequirePackage{tabularx}

\LWR@ProvidesPackageDrop{ltablex}[2014/08/13]

\DeclareDocumentEnvironment{tabularx}{m o m}
{\longtable{#3}}
```

```
{\endlongtable}

\DeclareDocumentEnvironment{tabularx*}{m o m}
{\longtable{#3}}
{\endlongtable}

\newcommand*{\keepXColumns}{}
\newcommand*{\convertXColumns}{}
```

File 258 **lwarp-ltcaption.sty**

§ 366 Package

ltcaption

(*Emulates or patches code by* Axel Sommerfeldt.)

Pkg ltcaption ltcaption is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{ltcaption}[2018/08/26]
```

\LTcaptype is already defined by lwarp.

longtable* is already defined by lwarp-longtable.

```
\newlength{\LTcapskip}
\newlength{\LTcapleft}
\newlength{\LTcapright}
\newcommand*{\LTcapmarginsfalse}{}
```

File 259 **lwarp-ltxgrid.sty**

§ 367 Package

ltxgrid

Pkg ltxgrid ltxgrid is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{ltxgrid}[2010/07/25]

\newcommand*{\onecolumngrid}{}
\newcommand*{\twocolumngrid}{}
\newcommand*{\removestuff}{}
\newcommand*{\addstuff}[2]{}
\newcommand*{\replacestuff}[2]{}
```

File 260 **lwarp-ltxtable.sty**

§ 368 Package

ltxtable

Pkg ltxtable ltxtable is emulated.

⚠ table numbering The print version does not seem to honor `longtable*` from the caption package, while lwarp does.

for HTML output:

```
\RequirePackage{tabularx,longtable}
\LWR@ProvidesPackageDrop{ltxtable}[1995/12/11]
```

`\LTXtable` {⟨*width*⟩} {⟨*file*⟩}

```
\newcommand*{\LTXtable}[2]{%
    \input{#2}%
}
```

File 261 **lwarp-lua-check-hyphen.sty**

§ 369 Package

lua-check-hyphen

Pkg `lua-check-hyphen` lua-check-hyphen is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{lua-check-hyphen}[2018/04/19]
```

```
\newcommand*{\LuaCheckHyphen}[1]{}
```

File 262 **lwarp-lua-visual-debug.sty**

§ 370 Package

lua-visual-debug

Pkg `lua-visual-debug` lua-visual-debug is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{lua-visual-debug}[2016/05/30]
```

File 263 **lwarp-luacolor.sty**

§ 371 Package

luacolor

Pkg `luacolor` luacolor is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{luacolor}[2016/05/16]
```

```
\newcommand{\luacolorProcessBox}[1]{}
```

File 264 **lwarp-luamplib.sty**

§ 372 Package

luamplib

(*Emulates or patches code by* Hans Hagen, Taco Hoekwater, Elie Roux, Philipp Gesang, Kim Dohyun.)

Pkg luamplib luamplib is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{luamplib}[2020/02/24]

\BeforeBeginEnvironment{mplibcode}{%
    \begin{lateximage}[-mplibcode-~\PackageDiagramAltText]%
}
\AfterEndEnvironment{mplibcode}{\end{lateximage}}
```

File 265 **lwarp-luatexko.sty**

§ 373 Package

luatexko

(*Emulates or patches code by* Dohyun Kim, Soojin Nam.)

Pkg luatexko luatexko is patched for use by lwarp.

Modern HTML is used for \dotemph, \ruby, and offset and thickness control for \uline, etc.

for HTML output:

```
\LWR@ProvidesPackagePass{luatexko}[2020/03/20]

\newcommand{\LWR@HTML@dotemph}[1]{%
%     \uline{#1}%
    \InlineClass[text-emphasis-style: dot]{dotemph}{#1}%
}
\LWR@formatted{dotemph}

\newcommand{\LWR@HTML@ruby}[2]{%
    \LWR@htmltagc{ruby}%
    \LWR@htmltagc{rb}#1\LWR@htmltagc{/rb}%
    \LWR@htmltagc{rp}(\LWR@htmltagc{/rp}%
    \LWR@htmltagc{rt}#2\LWR@htmltagc{/rt}%
    \LWR@htmltagc{rp})\LWR@htmltagc{/rp}%
    \LWR@htmltagc{/ruby}%
}
\LWR@formatted{ruby}
```

The following is modified from lwarp-ulem:

```
\NewDocumentCommand{\LWR@HTML@uline}{+m}{%
    \InlineClass%
        (text-decoration:underline; text-decoration-skip: auto)%
        [%
            text-underline-offset: \ulinedown ;
            text-decoration-thickness: \ulinewidth%
        ]%
        {uline}{\LWR@isolate{#1}}%
}
\LWR@formatted{uline}

\NewDocumentCommand{\LWR@HTML@uuline}{+m}{%
```

```
    \InlineClass%
        (%
            text-decoration:underline; text-decoration-skip: auto;%
            text-decoration-style:double%
        )%
        [%
            text-underline-offset: \ulinedown ;
            text-decoration-thickness: \ulinewidth%
        ]%
        {uuline}{\LWR@isolate{#1}}%
}
\LWR@formatted{uuline}

\NewDocumentCommand{\LWR@HTML@uwave}{+m}{%
    \InlineClass%
        (%
            text-decoration:underline; text-decoration-skip: auto;%
            text-decoration-style:wavy%
        )%
        [%
            text-underline-offset: \ulinedown ;
            text-decoration-thickness: \ulinewidth%
        ]%
        {uwave}{\LWR@isolate{#1}}%
}
\LWR@formatted{uwave}

\NewDocumentCommand{\LWR@HTML@sout}{+m}{%
    \InlineClass%
        (text-decoration:line-through)%
        [text-decoration-thickness: \ulinewidth]%
        {sout}{\LWR@isolate{#1}}%
}
\LWR@formatted{sout}

\NewDocumentCommand{\LWR@HTML@xout}{+m}{%
    \InlineClass%
        (text-decoration:line-through)%
        [text-decoration-thickness: \ulinewidth]%
        {xout}{\LWR@isolate{#1}}%
}
\LWR@formatted{xout}

\NewDocumentCommand{\LWR@HTML@dashuline}{+m}{%
    \InlineClass%
        (%
            text-decoration:underline;%
            text-decoration-skip: auto;%
            text-decoration-style:dashed%
        )%
        [%
            text-underline-offset: \ulinedown ;
            text-decoration-thickness: \ulinewidth%
        ]%
        {dashuline}{\LWR@isolate{#1}}%
```

```
}
\LWR@formatted{dashuline}

\NewDocumentCommand{\LWR@HTML@dotuline}{+m}{%
    \InlineClass%
        (%
            text-decoration:underline;%
            text-decoration-skip: auto;%
            text-decoration-style: dotted%
        )%
        [%
            text-underline-offset: \ulinedown ;
            text-decoration-thickness: \ulinewidth%
        ]%
        {dotuline}{\LWR@isolate{#1}}%
}
\LWR@formatted{dotuline}
```

File 266 **lwarp-luatodonotes.sty**

§ 374 Package

luatodonotes

(*Emulates or patches code by* Fabian Lipp.)

Pkg luatodonotes luatodonotes is emulated.

The documentation for todonotes and luatodonotes have an example with a todo inside a caption. If this example does not work it will be necessary to move the todo outside of the caption.

for HTML output:

```
\LWR@ProvidesPackagePass{luatodonotes}[2017/09/30]
```

Nullify options:

```
\@todonotes@additionalMarginEnabledfalse

\if@todonotes@disabled
\else

\newcommand{\ext@todo}{tdo}

\renewcommand{\l@todo}[2]{\hypertocfloat{1}{todo}{ldo}{#1}{#2}}


\let\LWRTODONOTES@orig@todototoc\todototoc

\renewcommand*{\todototoc}{%
\LWR@phantomsection%
\LWRTODONOTES@orig@todototoc%
}


\renewcommand{\@todonotes@drawMarginNoteWithLine}{%
```

```
\fcolorbox
    {\@todonotes@currentbordercolor}
    {\@todonotes@currentbackgroundcolor}
    {\arabic{@todonotes@numberoftodonotes}}
\marginpar{\@todonotes@drawMarginNote}
}

\renewcommand{\@todonotes@drawInlineNote}{%
\fcolorboxBlock%
    {\@todonotes@currentbordercolor}%
    {\@todonotes@currentbackgroundcolor}%
    {%
        \if@todonotes@authorgiven%
        {\@todonotes@author:\,}%
        \fi%
        \@todonotes@text%
    }%
}

\newcommand{\@todonotes@drawMarginNote}{%
    \if@todonotes@authorgiven%
        \@todonotes@author\par%
    \fi%
    \arabic{@todonotes@numberoftodonotes}: %
    \fcolorbox%
    {\@todonotes@currentbordercolor}%
    {\@todonotes@currentbackgroundcolor}%
    {%
        \@todonotes@sizecommand%
        \@todonotes@text %
    }%
}%

\renewcommand{\missingfigure}[2][]{%
\setkeys{todonotes}{#1}%
\addcontentsline{tdo}{todo}{\@todonotes@MissingFigureText: #2}%
\fcolorboxBlock%
    {\@todonotes@currentbordercolor}%
    {\@todonotes@currentfigcolor}%
    {%
        \setlength{\fboxrule}{4pt}%
        \fcolorbox{red}{white}{Missing figure} \quad #2%
    }
}

\LetLtxMacro\LWRTODONOTES@orig@todocommon\@todocommon

\RenewDocumentCommand{\@todocommon}{m m}{%
\begingroup%
\renewcommand*{\phantomsection}{}%
\LWRTODONOTES@orig@todocommon{#1}{#2}%
\endgroup%
}

\renewcommand{\@todoarea}[3][]{%
```

```
    \@todonotes@areaselectedtrue%
    \@todocommon{#1}{#2}%
    \todonotes@textmark@highlight{#3}%
    \zref@label{@todonotes@\arabic{@todonotes@numberoftodonotes}@end}%
}%


\DeclareDocumentCommand{\todonotes@textmark@highlight}{m}{%
\InlineClass[background:\LWR@origpound{}B3FFB3]{highlight}{#1}%
}

\fi% \if@todonotes@disabled
```

File 267 **lwarp-luavlna.sty**

§ 375 Package

luavlna

(*Emulates or patches code by* Michal Hoftich, Miro Hrončok.)

Pkg luavlna luavlna is patched for use by lwarp.

The package is disabled for HTML output, due to incompatibilities with lwarp's handling of math SVG images.

for HTML output:

```
\LWR@ProvidesPackagePass{luavlna}[2019/10/30]

\preventsingleoff
\LetLtxMacro\preventsingleon\preventsingleoff
```

File 268 **lwarp-lyluatex.sty**

§ 376 Package

lyluatex

(*Emulates or patches code by* Fr. Jacques Peron, Urs Liska, Br. Samuel Springuel.)

Pkg lyluatex lyluatex is patched for use by lwarp.

For the first compile, to set *lwarpmk*'s configuration, use:

```
lualatex --shell-escape <filename>
```

⚠ images After compiling the document with **lwarpmk html**, use **lwarpmk limages** to convert the Lilypond images for HTML.

The option `insert=systems` results in an image per system. Each music image "system" CSS is placed inside a `<span>` of class `lyluatex`, which defaults to `display: inline-block`.

⚠ insert=fullpage The option `insert=fullpage` results in a single image per page of printed output. Each CSS music "fullpage" image is placed inside a `<div>` of class `lyluatex`. To match the number

of measures per line with the printed version, use the geometry package to select the page geometry, or use the lyluatex options for page and staff sizes.

⚠ options To use `\linewidth` or `\textwidth` inside the package options for lyluatex, use the kvoptions-patch package first:

```
\usepackage{kvoptions-patch}
\usepackage[...,line-width-0.8\linewidth,...]{lyluatex}
```

⚠ raw-pdf If using `raw-pdf`, the resulting PDF images must be converted to SVG:

Enter ⇒ **`lwarpmk pdftosvg tmp-ly/*.pdf`**

for HTML output:

```
\LWR@origRequirePackage{luacode}

\LWR@ProvidesPackagePass{lyluatex}[2019/05/27]
```

User-redefinable `ALT` tag:

```
\newcommand*{\LyluatexImageAltText}{-lilypond-~\PackageDiagramAltText}
```

`\ly@compilescore` {⟨*Lilypond object*⟩}

```
\LetLtxMacro\LWR@orig@ly@compilescore\ly@compilescore

\renewcommand*{\ly@compilescore}[1]{%
```

A local group holds a number of changes:

```
    \begingroup%
```

The user's original geometry and font size are restored to match the print version. This allows for correct spacing in the musical score.

```
    \LWR@maybe@orignewpage%
    \LWR@origloadgeometry{LWR@usergeometry}%
    \LWR@print@normalsize%
```

A local group holds a redefined `\includegraphics` which is used by *lyluatex.lua* to insert the *Lilypond* score if `insert=systems` is used. This is now placed inside a `lateximage`, which itself is placed inside a of class `lyluatex`.

`\LWR@addbaselinemarker` preserves the left margins.

```
    \renewcommand{\includegraphics}[2][]{%
        \InlineClass{lyluatex}{%
            \begin{lateximage}[\LyluatexImageAltText]%
            \LWR@addbaselinemarker%
            \LWR@origincludegraphics{##2}%
            \end{lateximage}%
        }%
    }%
```

From the original:

```
    \ly@setunits%
    \directlua{
        ly_opts:set_option('currfiledir', [[\currfiledir]])
```

```
        ly_opts:set_option('twoside', '\ly@istwosided')
        #1
    }%
    \ly@resetunits%
    \ly@currentfonts%
```

The fullpage version is set inside an HTML :

```
    \directlua{
        if (ly.score.insert == 'fullpage') then
            tex.print{[[\string\begin{BlockClass}{lyluatex}]]}
        end
    }%
```

Generate the score:

```
    \directlua{ly.score:process()}%
```

Close the :

```
    \directlua{
        if (ly.score.insert == 'fullpage') then
            tex.print{[[\string\end{BlockClass}]]}
        end
    }%
```

Move to a new page and renew the regular page geometry:

```
    \LWR@maybe@orignewpage%
    \LWR@origrestoregeometry%
```

End of the local group.

```
    \endgroup%
}
```

In HTML the following generates an error, so is removed:

```
\xpatchcmd{\endly@bufferenv}
    {\hspace{0pt}\\}
    {}
    {}
    {\LWR@patcherror{lyluatex}{endly@bufferenv}}
```

File 269 **lwarp-magaz.sty**

§ 377 Package

magaz

Pkg magaz magaz is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{magaz}[2011/11/24]

\newcommand\FirstLine[1]{%
    \begingroup%
    \FirstLineFont{%
        \LWR@textcurrentcolor{%
            \LWR@textcurrentfont{%
```

```
                #1%
            }%
        }%
    }%
    \endgroup%
}

\providecommand\FirstLineFont{\scshape}
```

File 270 **lwarp-makeidx.sty**

§ 378 Package

makeidx

(*Emulates or patches code by* LaTeX Project Team.)

Pkg makeidx makeidx is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{makeidx}[2014/09/29]
```

\@wrindex is redefined \AtBeginDocument by the lwarp core.

\printindex

```
\preto\printindex{%
    \LWR@maybe@orignewpage%
    \LWR@startpars%
}
```

File 271 **lwarp-manyfoot.sty**

§ 379 Package

manyfoot

Pkg manyfoot manyfoot is emulated.

bigfoot, manyfoot ⚠ verbatim

Verbatim footnotes are not yet supported.

If using the bigfoot package, and possibly also manyfoot, problems may occur with counter allocation because lwarp uses many counters, and there is a difference in how counters numbered 256 and up are handled in pdfLaTeX. With bigfoot this has been known to show up as an error related to one footnote insert being forbidden inside another. Another problem showed up as a input stack error, and which of these problems occurred depended on how many counters were allocated.

As a possible solution, try creating several new counters before defining bigfoot or manyfoot footnotes, hoping to shift the problematic counter above the 256 threshold. It may instead be necessary to use XeLaTeX or LuaLaTeX instead of pdfLaTeX.

lwarp's emulation of bigfoot uses manyfoot, so some of the bigfoot enhancements are included here.

The bigfoot "default" footnote is ignored, using the lwarp version instead.

for HTML output:

```
\LWR@ProvidesPackageDrop{manyfoot}[2005/09/11]

\RequirePackage{nccfoots}

\newcommand{\extrafootnoterule}{}

\let\defaultfootnoterule\footnoterule

\newcommand*{\SelectFootnoteRule}[2][0]{}

\newcommand{\footnoterulepriority}{1}

\newcommand{\SetFootnoteHook}[1]{}
\@onlypreamble\SetFootnoteHook

\newcommand{\SplitNote}{}

\newcommand*\ExtraParaSkip[1]{}

\newcommand*{\newfootnote}[2][plain]{%
    \ifstrequal{#2}{default}{}{% not "default"
        \expandafter\newbox\csname LWR@footnote#2box\endcsname%
        \appto{\LWR@printpendingfootnotes}{%
            \LWR@@printpendingfootnotes{footnote#2}%
        }
        \long\csdef{Footnotetext#2}##1##2{%
            \NCC@makefnmark{##1}%
            \LWR@@footnotetext{##2}{LWR@footnote#2box}%
        }%
        \long\csdef{Footnotetext#2+}##1##2{%
            \NCC@makefnmark{##1}%
            \LWR@@footnotetext{##2}{LWR@footnote#2box}%
        }%
    }% not "default"
}
\@onlypreamble\newfootnote

\newcommand*{\DeclareNewFootnote}[2][plain]{%
  \@ifnextchar[%
        {\LWR@manyfoot@declare{#1}{#2}}%
        {\LWR@manyfoot@declare{#1}{#2}[arabic]}%
}

\def\LWR@manyfoot@declare#1#2[#3]{%
\ifstrequal{#2}{default}{}{% not "default"
  \newfootnote[#1]{#2}%
  \newcounter{footnote#2}%
    \newcounter{footnote#2Reset}%
    \setcounter{footnote#2Reset}{0}%
    \csdef{thefootnote#2}{%
      \expandafter\noexpand\csname @#3\endcsname%
      \expandafter\noexpand\csname c@footnote#2\endcsname%
    }%
```

For bigfoot, the footnote commands may be appended with one or two plusses or one or two minuses, which are ignored in HTML.

```
\expandafter\NewDocumentCommand\csname footnote#2\endcsname{t{+}t{+}t{-}t{-}}{%
     \stepcounter{footnote#2}%
     \protected@xdef\@thefnmark{\csname thefootnote#2\endcsname}%
     \@footnotemark%
     \csuse{Footnotetext#2}{\@thefnmark}% absorbs the footnote contents
  }%
  \csdef{footnotemark#2}{%
     \stepcounter{footnote#2}%
     \protected@xdef\@thefnmark{\csname thefootnote#2\endcsname}%
     \@footnotemark%
  }%
\expandafter\NewDocumentCommand\csname footnotetext#2\endcsname{t{+}t{+}t{-}t{-}}{%
     \protected@xdef\@thefnmark{\csname thefootnote#2\endcsname}%
     \csuse{Footnotetext#2}{\@thefnmark}% absorbs the footnote contents
  }%
  \csdef{Footnotemark#2}{%
    \Footnotemark%
  }%
  \csdef{Footnote#2}##1{%
    \Footnotemark{##1}%
    \csuse{Footnotetext#2}{##1}%
  }%
}% not "default"
}
\@onlypreamble\DeclareNewFootnote
```

File 272 **lwarp-marginal.sty**

§ 380 Package marginal

Pkg marginal

marginal is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{marginal}

\newcommand*{\showlostmarginals}{}
\newcommand*{\enlargefreelist}{}
\newcommand*{\onesidemarginals}{}
```

File 273 **lwarp-marginfit.sty**

§ 381 Package marginfit

Pkg marginfit

marginfit is ignored.

for HTML output:

Discard all options for lwarp-marginfit:

```
\LWR@ProvidesPackageDrop{marginfit}[2018/06/08]
```

File 274 **lwarp-marginfix.sty**

§ 382 Package marginfix

(*Emulates or patches code by* Stephen Hicks.)

Pkg marginfix marginfix is ignored.

for HTML output: Discard all options for lwarp-marginfix:

```
\LWR@ProvidesPackageDrop{marginfix}[2013/09/08]

\newcommand*{\marginskip}[1]{}
\newcommand*{\clearmargin}{}
\newcommand*{\softclearmargin}{}
\newcommand*{\extendmargin}[1]{}
\newcommand*{\mparshift}[1]{}
\newdimen\marginheightadjustment
\newdimen\marginposadjustment
\newcommand*{\blockmargin}[1][]{}
\newcommand*{\unblockmargin}[1][]{}
\newcommand*{\marginphantom}[2][]{}
```

File 275 **lwarp-marginnote.sty**

§ 383 Package marginnote

(*Emulates or patches code by* Markus Kohm.)

Pkg marginnote marginnote is emulated.

for HTML output: Discard all options for lwarp-marginnote:

```
\LWR@ProvidesPackageDrop{marginnote}[2018/08/09]

\NewDocumentCommand{\marginnote}{+o +m o}{\marginpar{#2}}

\newcommand*{\marginnoteleftadjust}{}
\newcommand*{\marginnoterightadjust}{}
\newcommand*{\marginnotetextwidth}{}
\let\marginnotetextwidth\textwidth
\newcommand*{\marginnotevadjust}{}
\newcommand*{\marginfont}{}
\newcommand*{\raggedleftmarginnote}{}
\newcommand*{\raggedrightmarginnote}{}

\appto\LWR@restoreorigformatting{%
    \RenewDocumentCommand{\marginnote}{+o +m o}{}
}
```

For MathJax:

```
\begin{warpMathJax}
\CustomizeMathJax{\newcommand{\LWRmarginnote}[1][]{}}
\CustomizeMathJax{\newcommand{\marginnote}[2][]{\qquad{\small\textrm{#2}}\LWRmarginnote}}
\end{warpMathJax}
```

File 276 **lwarp-marvosym.sty**

§ 384 Package marvosym

(*Emulates or patches code by* Thomas Henlich, Mojca Miklavec.)

Pkg marvosym marvosym is patched for use by lwarp.

Hashed inline images are used, as there may not be Unicode support for all icons.

for HTML output:

```
\LWR@ProvidesPackagePass{marvosym}[2011/07/20]

\renewcommand{\mvchr}[1]{%
    \begin{lateximage}*[symbol #1][marvosym #1]%
    \mvs\char#1%
    \end{lateximage}%
}

\renewcommand{\textmvs}[1]{%
    \begin{lateximage}%
    \mvs #1%
    \end{lateximage}%
}
```

File 277 **lwarp-mathalpha.sty**

§ 385 Package mathalpha

(*Emulates or patches code by* Michael Sharpe.)

Pkg mathalpha mathalpha is used as-is for SVG math, and is emulated for MathJax.

⚠ limitations The MathJax emulation ignores all package options, and some bold fonts may not be not supported by MathJax.

for HTML output:

```
\LWR@ProvidesPackagePass{mathalpha}[2019/10/05]

\begin{warpMathJax}
\CustomizeMathJax{\newcommand{\mathbbb}[1]{\boldsymbol{\mathbb{#1}}}}% not bold
\CustomizeMathJax{\newcommand{\mathbcal}[1]{\boldsymbol{\mathcal{#1}}}}
\CustomizeMathJax{\newcommand{\mathbfrak}[1]{\boldsymbol{\mathfrak{#1}}}}
\CustomizeMathJax{\newcommand{\mathbscr}[1]{\boldsymbol{\mathscr{#1}}}}% not bold
\end{warpMathJax}
```

File 278 **lwarp-mathastext.sty**

§ 386 Package

mathastext

(*Emulates or patches code by* Jean-François Burnol.)

Pkg mathastext mathastext is used as-is for SVG math, and emulated for MathJax.

for HTML output:

```
\LWR@ProvidesPackagePass{mathastext}[2019/11/16]

\LWR@origRequirePackage{lwarp-common-mathjax-letters}

\begin{warpMathJax}
\ifmst@itgreek
%     \LWR@mathjax@addgreek@l@it{}{}
\else
    \ifmst@upgreek
        \LWR@mathjax@addgreek@l@up{}{}
    \else
        \ifmst@frenchmath
            \LWR@mathjax@addgreek@l@up{}{}
        \else
            \ifmst@italic
%               \LWR@mathjax@addgreek@l@it{}{}
            \else
                \LWR@mathjax@addgreek@l@up{}{}
            \fi
        \fi
    \fi
\fi

\ifcase\mst@greek@select
    \or{\LWR@mathjax@addgreek@u@it*{}{}}
%     \or{\LWR@mathjax@addgreek@u@up*{}{}}
\fi

\CustomizeMathJax{\newcommand{\mathnormalbold}[1]{\boldsymbol{#1}}}
\CustomizeMathJax{\newcommand{\MathEulerBold}[1]{\boldsymbol{#1}}}
\CustomizeMathJax{\newcommand{\MathEuler}[1]{{#1}}}
\CustomizeMathJax{\newcommand{\MathPSymbol}[1]{{#1}}}
\CustomizeMathJax{\let\fouriervec\vec}
\CustomizeMathJax{\let\pmvec\vec}
\CustomizeMathJax{\let\inodot\imath}
\CustomizeMathJax{\let\jnodot\jmath}
\CustomizeMathJax{\let\shortiff\iff}
\CustomizeMathJax{\let\longto\longrightarrow}
\CustomizeMathJax{\newcommand{\inftypsy}{\mathord{\unicode{x221E}}}}
\CustomizeMathJax{\newcommand{\proptopsy}{\mathrel{\unicode{x221D}}}}
\CustomizeMathJax{\let\prodpsy\prod}
\CustomizeMathJax{\let\sumpsy\sum}
\CustomizeMathJax{\let\MToriginalprod\prod}
\CustomizeMathJax{\let\MToriginalsum\sum}
```

```
\CustomizeMathJax{\newcommand{\DotTriangle}{\mathord{\unicode{x2234}}}}
\end{warpMathJax}
```

File 279 **lwarp-mathcomp.sty**

§ 387 Package mathcomp

(*Emulates or patches code by* Tilmann Böß.)

Pkg mathcomp mathcomp is supported as-is for SVG math, and is emulated for MathJax.

for HTML output:

```
\LWR@ProvidesPackagePass{mathcomp}[2001/01/07]

\begin{warpMathJax}
\CustomizeMathJax{\newcommand{\tcohm}{\mathrm{\Omega}}}
\CustomizeMathJax{\newcommand{\tccelsius}{\unicode{x2103}}}
\CustomizeMathJax{\newcommand{\tcmu}{\mathrm{\unicode{x00B5}}}}
\CustomizeMathJax{\newcommand{\tcperthousand}{\unicode{x2030}}}
\CustomizeMathJax{\newcommand{\tcpertenthousand}{\unicode{x2031}}}
\CustomizeMathJax{\newcommand{\tcdegree}{\mathrm{^\circ}}}
\CustomizeMathJax{\newcommand{\tcdigitoldstyle}[1]{\oldstyle{#1}}}
\end{warpMathJax}
```

File 280 **lwarp-mathdesign.sty**

§ 388 Package mathdesign

(*Emulates or patches code by* Paul Pichaureau.)

Pkg mathdesign mathdesign is used as-is for SVG math, and is emulated for MathJax.

⚠ limitations The MathJax emulation ignores all package options except `greekuppercase` and `greeklowercase`. The dedicated macros for upright and italic greek letters work correctly, although the user may wish to swap the definitions for epsilon and phi.

SVG math should appear the same as the printed output.

for HTML output:

```
\LWR@ProvidesPackagePass{mathdesign}[2013/08/29]
```

For MathJax:

```
\LWR@origRequirePackage{lwarp-common-mathjax-letters}

\LWR@origRequirePackage{lwarp-common-mathjax-overlaysymbols}

\begin{warpMathJax}
\LWR@infoprocessingmathjax{mathdesign}
```

Default greek upright or italicized:

```
\if@MD@grupright
\LWR@mathjax@addgreek@l@up{}{}
\fi

\if@MD@GRupright
\else
\LWR@mathjax@addgreek@u@it*{}{}
\fi
```

Upright:

```
\LWR@mathjax@addgreek@l@up{}{up}
\LWR@mathjax@addgreek@u@up*{}{up}
```

Italicized:

```
\LWR@mathjax@addgreek@l@it{}{it}
\LWR@mathjax@addgreek@u@it*{}{it}
```

Adapt to mathdesign inconsistency:

```
\CustomizeMathJax{\let\digammaup\Digammaup}
\CustomizeMathJax{\renewcommand{\digammait}{\mathit{\digammaup}}}
```

Extra symbols:

```
\CustomizeMathJax{\newcommand{\smallin}{\mathrel{\unicode{x220A}}}}
\CustomizeMathJax{\newcommand{\smallowns}{\mathrel{\unicode{x220D}}}}
\CustomizeMathJax{\newcommand{\notsmallin}{\mathrel{\LWRoverlaysymbols{/}{\unicode{x220A}}}}}
\CustomizeMathJax{\newcommand{\notsmallowns}{\mathrel{\LWRoverlaysymbols{/}{\unicode{x220D}}}}}
\CustomizeMathJax{\newcommand{\rightangle}{\mathord{\unicode{x221F}}}}
```

Integrals:

```
\CustomizeMathJax{\newcommand{\intclockwise}{\mathop{\unicode{x2231}}\limits}}
\CustomizeMathJax{\newcommand{\ointclockwise}{\mathop{\unicode{x2232}}\limits}}
\CustomizeMathJax{\newcommand{\ointctrclockwise}{\mathop{\unicode{x2233}}\limits}}
\CustomizeMathJax{\newcommand{\oiint}{\mathop{\unicode{x222F}}\limits}}
\CustomizeMathJax{\newcommand{\oiiint}{\mathop{\unicode{x2230}}\limits}}
```

Math and text mode:

```
\CustomizeMathJax{\newcommand{\ddag}{\unicode{x2021}}}
\CustomizeMathJax{\newcommand{\P}{\unicode{x00B6}}}
\CustomizeMathJax{\newcommand{\copyright}{\unicode{x00A9}}}
\CustomizeMathJax{\newcommand{\dag}{\unicode{x2020}}}
\CustomizeMathJax{\newcommand{\pounds}{\unicode{x00A3}}}
```

Extra symbols:

```
\CustomizeMathJax{\newcommand{\iddots}{\mathinner{\unicode{x22F0}}}}
\CustomizeMathJax{\newcommand{\utimes}{\mathbin{\overline{\times}}}}
\CustomizeMathJax{\newcommand{\dtimes}{\mathbin{\underline{\times}}}}
\CustomizeMathJax{\newcommand{\udtimes}{\mathbin{\overline{\underline{\times}}}}}
```

```
\CustomizeMathJax{\newcommand{\leftwave}{\left\{}}
\CustomizeMathJax{\newcommand{\rightwave}{\right\}}}

\end{warpMathJax}
```

File 281 **lwarp-mathdots.sty**

§ 389 Package mathdots

(*Emulates or patches code by* Dan Luecking.)

Pkg mathdots mathdots is used as-is for SVG math, and emulated for MathJax.

for HTML output:

```
\LWR@ProvidesPackagePass{mathdots}[2014/06/11]

\begin{warpMathJax}
\CustomizeMathJax{\newcommand{\iddots}{\mathinner{\unicode{x22F0}}}}
\CustomizeMathJax{\let\fixedddots\ddots}
\CustomizeMathJax{\let\fixedvdots\vdots}
\CustomizeMathJax{\let\fixediddots\iddots}
\CustomizeMathJax{\let\originalddots\ddots}
\CustomizeMathJax{\let\originalvdots\vdots}
\CustomizeMathJax{\let\originaliddots\iddots}
\CustomizeMathJax{\let\originaldddot\dddot}
\CustomizeMathJax{\let\originalddddot\ddddot}
\end{warpMathJax}
```

File 282 **lwarp-mathfixs.sty**

§ 390 Package mathfixs

(*Emulates or patches code by* Niklas Beisert.)

Pkg mathfixs mathfixs is used as-is for SVG math, and is emulated for MathJax.

⚠ Greek letters are unchanged.

for HTML output:

```
\LWR@ProvidesPackagePass{mathfixs}[2018/12/30]

\begin{warpMathJax}
\CustomizeMathJax{\newcommand{\rfrac}[2]{\tfrac{#1}{#2}}}
\CustomizeMathJax{\newcommand{\vfrac}[2]{\mathinner{{}^{#1}\!/{}_{#2}}}}
\CustomizeMathJax{\newcommand{\ProvideMathFix}[1]{}}
\CustomizeMathJax{\newcommand{\mathbold}[1]{\boldsymbol{#1}}}
\CustomizeMathJax{\newcommand{\.}{\,}}
\end{warpMathJax}
```

File 283 **lwarp-mathpazo.sty**

§ 391 Package

mathpazo

(*Emulates or patches code by* Walter Schmidt.)

Pkg mathpazo mathpazo is used as-is for SVG math, and is emulated for MathJax.

⚠ limitations The MathJax emulation ignores all package options. The dedicated macros for upright greek letters do work correctly.

SVG math should appear the same as the printed output.

for HTML output:

```
\LWR@ProvidesPackagePass{mathpazo}[2020/03/25]
```

For MathJax:

```
\LWR@origRequirePackage{lwarp-common-mathjax-letters}

\begin{warpMathJax}
\LWR@infoprocessingmathjax{mathpazo}

\ifpazo@slGreek
\LWR@mathjax@addgreek@u@it*{}{}
\fi

\LWR@mathjax@addgreek@u@up*{up}{}

\CustomizeMathJax{\newcommand{\mathbold}[1]{\boldsymbol{#1}}}
\end{warpMathJax}
```

File 284 **lwarp-mathptmx.sty**

§ 392 Package

mathptmx

(*Emulates or patches code by* Walter Schmidt.)

Pkg mathptmx mathptmx is used as-is for SVG math, and is emulated for MathJax.

⚠ limitations The MathJax emulation ignores all package options. The dedicated macros for upright greek letters do work correctly.

SVG math should appear the same as the printed output.

for HTML output:

```
\LWR@ProvidesPackagePass{mathptmx}[2020/03/25]
```

For MathJax:

```
\LWR@origRequirePackage{lwarp-common-mathjax-letters}

\begin{warpMathJax}
\LWR@infoprocessingmathjax{mathptmx}

\@ifpackagewith{mathptmx}{slantedGreek}
    {\LWR@mathjax@addgreek@u@it*{}{}}
```

```
    {}

\LWR@mathjax@addgreek@u@up*{up}{}
\end{warpMathJax}
```

File 285 **lwarp-mathspec.sty**

§ 393 Package

mathspec

(*Emulates or patches code by* Andrew Gilbert Moschou.)

Pkg mathspec mathspec is used as-is with SVG math, and is emulated for MathJax.

⚠ quotes Double quotes (\" and the " character) are removed during MathJax emulation, but this also includes inside \text.

for HTML output:

```
\LWR@ProvidesPackagePass{mathspec}[2016/12/22]

\LWR@origRequirePackage{lwarp-common-mathjax-letters}

\begin{warpMathJax}
```

Neutralize double quotes (" and \"):

```
\booltrue{LWR@MathJax@silentquotes}
```

Sort options for out Greek emulation:

```
\AtBeginDocument{
\ifcase\eu@GreekUppercase@@value %% If Greek Uppercase Regular
    \LWR@mathjax@addgreek@u@up*{}{}
\or %% If Greek Uppercase Italic
    \LWR@mathjax@addgreek@u@it*{}{}
\or %% If Greek Uppercase Plain
    \LWR@mathjax@addgreek@u@up*{}{}
\fi
\ifcase\eu@GreekLowercase@@value %% If Greek Lowercase Regular
    \LWR@mathjax@addgreek@l@up{}{}
\or %% If Greek Lowercase Italic
    \LWR@mathjax@addgreek@l@it{}{}
\or %% If Greek Lowercase Plain
    \LWR@mathjax@addgreek@l@it{}{}
\fi
}
```

Swap definitions according the mathspec conditionals:

```
\newcommand*{\LWR@mathspec@varforms}{%
\eu@ifbooltrue{GreekLowercase}{
    \eu@ifbooltrue{exchangebetaforms}{
        \CustomizeMathJax{\let\LWRorigbeta\beta}
        \CustomizeMathJax{\let\beta\varbeta}
        \CustomizeMathJax{\let\varbeta\LWRorigbeta}
```

```
    }
    \eu@ifbooltrue{exchangeepsilonforms}{
        \CustomizeMathJax{\let\LWRorigepsilon\epsilon}
        \CustomizeMathJax{\let\epsilon\varepsilon}
        \CustomizeMathJax{\let\varepsilon\LWRorigepsilon}
    }
    \eu@ifbooltrue{exchangethetaforms}{
        \CustomizeMathJax{\let\LWRorigtheta\theta}
        \CustomizeMathJax{\let\theta\vartheta}
        \CustomizeMathJax{\let\vartheta\LWRorigtheta}
    }
    \eu@ifbooltrue{exchangekappaforms}{
        \CustomizeMathJax{\let\LWRorigkappa\kappa}
        \CustomizeMathJax{\let\kappa\varkappa}
        \CustomizeMathJax{\let\varkappa\LWRorigkappa}
    }
    \eu@ifbooltrue{exchangepiforms}{
        \CustomizeMathJax{\let\LWRorigpi\pi}
        \CustomizeMathJax{\let\pi\varpi}
        \CustomizeMathJax{\let\varpi\LWRorigpi}
    }
    \eu@ifbooltrue{exchangerhoforms}{
        \CustomizeMathJax{\let\LWRorigrho\rho}
        \CustomizeMathJax{\let\rho\varrho}
        \CustomizeMathJax{\let\varrho\LWRorigrho}
    }
    \eu@ifbooltrue{exchangephiforms}{
        \CustomizeMathJax{\let\LWRorigphi\phi}
        \CustomizeMathJax{\let\phi\varphi}
        \CustomizeMathJax{\let\varphi\LWRorigphi}
    }
}
\eu@ifbooltrue{GreekUppercase}{
    \eu@ifbooltrue{exhangeThetaforms}{
        \CustomizeMathJax{\let\LWRorigTheta\Theta}
        \CustomizeMathJax{\let\Theta\varTheta}
        \CustomizeMathJax{\let\varTheta\LWRorigTheta}
    }
}
}
```

Append new action to mathspec's `\AtBeginDocument` code:

```
\xapptocmd{\exchangeforms}
    {\AtBeginDocument{\LWR@mathspec@varforms}}
    {}
    {\LWR@patcherror{mathspec}{exchangeforms}}

\end{warpMathJax}
```

File 286 **lwarp-mathtools.sty**

§ 394 Package

mathtools

(*Emulates or patches code by* Morten Høgholm, Lars Madsen.)

Pkg mathtools

mathtools is patched for use by lwarp. Emulation macros are provided for MathJax.

⚠ equation numbering

showonlyrefs is disabled, as it conflicts with cleveref, which is used by lwarp. Equation numbers may not match the print version.

⚠ italic correction

mathic is not emulated for HTML.

⚠ MathJax

If using MathJax:

- mathtools disallowspaces does not work for MathJax. Protect brackets which are not optional arguments, such as:

```
\begin{gathered}{}
[p]=1 . . .
\end{gathered}
```

- showonlyrefs does not work in MathJax, and will result in a difference in equation numbering compared to the print version.
- Due to MathJax limitations, the following do not render well: \overbracket, \underbracket, \overbrace, \underbrace, rcases, drcases, \Aboxed, and \ArrowBetweenLines.
- For the new cases-like environments, \text must be used to set the normal roman font if desired.
- alignat in MathJax requires math mode, but in LaTeX it doesn't. It may be required to use warpHTML and warpprint to isolate a version for each mode.
- \DeclarePairedDelimiter and related must be in the preamble before \begin{document}.

for HTML output:

```
\LWR@ProvidesPackagePass{mathtools}[2018/01/08]
\RequirePackage{graphicx}
\MHInternalSyntaxOn
```

Forces showonlyrefs off because lwarp uses cleveref, which is not compatible with showonlyrefs.

```
\renewcommand*\MT_showonlyrefs_true:{%
    \PackageWarningNoLine{lwarp}
    {%
        Mathtools \space showonlyrefs \space conflicts \space
        with \space cleveref,\MessageBreak
        which \space is \space used \space by \space lwarp, \space
        so \space showonlyrefs \space is\MessageBreak
        forced \space off. \space\space
        Equation \space numbers \space may \space not \space match%
    }
```

```
    \MT_showonlyrefs_false:
}
\mathtoolsset{showonlyrefs=false}
```

Forces math italic correction off. Not patched for lwarp.

```
\renewcommand*{\MT_mathic_true:}{\MT_mathic_false:}
\mathtoolsset{mathic=false}

\MHInternalSyntaxOff
```

For MathJax:

```
\begin{warpMathJax}
\LWR@infoprocessingmathjax{mathtools}

\CustomizeMathJax{\newcommand{\mathllap}[2][]{{#1#2}}}
\CustomizeMathJax{\newcommand{\mathrlap}[2][]{{#1#2}}}
\CustomizeMathJax{\newcommand{\mathclap}[2][]{{#1#2}}}
\CustomizeMathJax{\newcommand{\mathmbox}[1]{#1}}
\CustomizeMathJax{\newcommand{\clap}[1]{#1}}
\CustomizeMathJax{\newcommand{\LWRmathmakebox}[2][]{#2}}
\CustomizeMathJax{\newcommand{\mathmakebox}[1][]{\LWRmathmakebox}}
\CustomizeMathJax{\newcommand{\cramped}[2][]{{#1#2}}}
\CustomizeMathJax{\newcommand{\crampedllap}[2][]{{#1#2}}}
\CustomizeMathJax{\newcommand{\crampedrlap}[2][]{{#1#2}}}
\CustomizeMathJax{\newcommand{\crampedclap}[2][]{{#1#2}}}
\CustomizeMathJax{\newenvironment{crampedsubarray}[1]{}{}}
\CustomizeMathJax{\newcommand{\crampedsubstack}{}}

\CustomizeMathJax{\newcommand{\smashoperator}[2][]{#2\limits}}

\CustomizeMathJax{\newcommand{\adjustlimits}{}}

\CustomizeMathJax{\newcommand{\SwapAboveDisplaySkip}{}}

\CustomizeMathJax{\require{extpfeil}}
\CustomizeMathJax{\Newextarrow\xleftrightarrow{10,10}{0x2194}}
\CustomizeMathJax{\Newextarrow\xLeftarrow{10,10}{0x21d0}}
\CustomizeMathJax{\Newextarrow\xhookleftarrow{10,10}{0x21a9}}
\CustomizeMathJax{\Newextarrow\xmapsto{10,10}{0x21a6}}
\CustomizeMathJax{\Newextarrow\xRightarrow{10,10}{0x21d2}}
\CustomizeMathJax{\Newextarrow\xLeftrightarrow{10,10}{0x21d4}}
\CustomizeMathJax{\Newextarrow\xhookrightarrow{10,10}{0x21aa}}
\CustomizeMathJax{\Newextarrow\xrightharpoondown{10,10}{0x21c1}}
\CustomizeMathJax{\Newextarrow\xleftharpoondown{10,10}{0x21bd}}
\CustomizeMathJax{\Newextarrow\xrightleftharpoons{10,10}{0x21cc}}
\CustomizeMathJax{\Newextarrow\xrightharpoonup{10,10}{0x21c0}}
\CustomizeMathJax{\Newextarrow\xleftharpoonup{10,10}{0x21bc}}
\CustomizeMathJax{\Newextarrow\xleftrightharpoons{10,10}{0x21cb}}

\CustomizeMathJax{\newcommand{\LWRdounderbracket}[3]{%
    \mathinner{\underset{#3}{\underline{\llcorner{#1}\lrcorner}}}%
```

```
}}
\CustomizeMathJax{\newcommand{\LWRunderbracket}[2][]{\LWRdounderbracket{#2}}}
\CustomizeMathJax{\newcommand{\underbracket}[1][]{\LWRunderbracket}}
\CustomizeMathJax{\newcommand{\LWRdooverbracket}[3]{%
    \mathinner{\overset{#3}{\overline{\ulcorner{#1}\urcorner}}}%
}}
\CustomizeMathJax{\newcommand{\LWRoverbracket}[2][]{\LWRdooverbracket{#2}}}
\CustomizeMathJax{\newcommand{\overbracket}[1][]{\LWRoverbracket}}

\CustomizeMathJax{\newcommand{\LaTeXunderbrace}[1]{\underbrace{#1}}}
\CustomizeMathJax{\newcommand{\LaTeXoverbrace}[1]{\overbrace{#1}}}

\CustomizeMathJax{\newenvironment{matrix*}[1][]{\begin{matrix}}{\end{matrix}}}
\CustomizeMathJax{\newenvironment{pmatrix*}[1][]{\begin{pmatrix}}{\end{pmatrix}}}
\CustomizeMathJax{\newenvironment{bmatrix*}[1][]{\begin{bmatrix}}{\end{bmatrix}}}
\CustomizeMathJax{\newenvironment{Bmatrix*}[1][]{\begin{Bmatrix}}{\end{Bmatrix}}}
\CustomizeMathJax{\newenvironment{vmatrix*}[1][]{\begin{vmatrix}}{\end{vmatrix}}}
\CustomizeMathJax{\newenvironment{Vmatrix*}[1][]{\begin{Vmatrix}}{\end{Vmatrix}}}
\CustomizeMathJax{\newenvironment{smallmatrix*}[1][]{\begin{matrix}}{\end{matrix}}}
\CustomizeMathJax{\newenvironment{psmallmatrix*}[1][]{\begin{pmatrix}}{\end{pmatrix}}}
\CustomizeMathJax{\newenvironment{bsmallmatrix*}[1][]{\begin{bmatrix}}{\end{bmatrix}}}
\CustomizeMathJax{\newenvironment{Bsmallmatrix*}[1][]{\begin{Bmatrix}}{\end{Bmatrix}}}
\CustomizeMathJax{\newenvironment{vsmallmatrix*}[1][]{\begin{vmatrix}}{\end{vmatrix}}}
\CustomizeMathJax{\newenvironment{Vsmallmatrix*}[1][]{\begin{Vmatrix}}{\end{Vmatrix}}}
\CustomizeMathJax{\newenvironment{psmallmatrix}[1][]{\begin{pmatrix}}{\end{pmatrix}}}
\CustomizeMathJax{\newenvironment{bsmallmatrix}[1][]{\begin{bmatrix}}{\end{bmatrix}}}
\CustomizeMathJax{\newenvironment{Bsmallmatrix}[1][]{\begin{Bmatrix}}{\end{Bmatrix}}}
\CustomizeMathJax{\newenvironment{vsmallmatrix}[1][]{\begin{vmatrix}}{\end{vmatrix}}}
\CustomizeMathJax{\newenvironment{Vsmallmatrix}[1][]{\begin{Vmatrix}}{\end{Vmatrix}}}


\CustomizeMathJax{\newcommand{\LWRmultlined}[1][]{\begin{multline*}}}
\CustomizeMathJax{\newenvironment{multlined}[1][]{\LWRmultlined}{\end{multline*}}}

\CustomizeMathJax{\let\LWRorigshoveleft\shoveleft}
\CustomizeMathJax{\renewcommand{\shoveleft}[1][]{\LWRorigshoveleft}}
\CustomizeMathJax{\let\LWRorigshoveright\shoveright}
\CustomizeMathJax{\renewcommand{\shoveright}[1][]{\LWRorigshoveright}}

\CustomizeMathJax{\newenvironment{dcases}{\begin{cases}}{\end{cases}}}
\CustomizeMathJax{\newenvironment{dcases*}{\begin{cases}}{\end{cases}}}
\CustomizeMathJax{\newenvironment{rcases}{\begin{cases}}{\end{cases}}}
\CustomizeMathJax{\newenvironment{rcases*}{\begin{cases}}{\end{cases}}}
\CustomizeMathJax{\newenvironment{drcases}{\begin{cases}}{\end{cases}}}
\CustomizeMathJax{\newenvironment{drcases*}{\begin{cases}}{\end{cases}}}
\CustomizeMathJax{\newenvironment{cases*}{\begin{cases}}{\end{cases}}}

\CustomizeMathJax{\newcommand{\MoveEqLeft}[1][]{}}

\CustomizeMathJax{% special parsing to handle '&' in argument
    \def\LWRAboxed#1&#2&#3!|!{\fbox{\(#1\)}&\fbox{\(#2\)}}
    \newcommand{\Aboxed}[1]{\LWRAboxed#1&&!|!}
}


\CustomizeMathJax{
```

```
   \newcommand{\LWRABLines}[1][\Updownarrow]{#1 \notag \\}% star/nostar the same
    \newcommand{\ArrowBetweenLines}{\ifstar\LWRABLines\LWRABLines}
}

\CustomizeMathJax{\newcommand{\shortintertext}[1]{\text{#1}\notag \\}}

\CustomizeMathJax{\newcommand{\vdotswithin}[1]{\hspace{.5em}\vdots}}

\CustomizeMathJax{\newcommand{\LWRshortvdotswithinstar}[1]{\vdots \hspace{.5em} & \\}}
\CustomizeMathJax{\newcommand{\LWRshortvdotswithinnostar}[1]{& \hspace{.5em}\vdots \\}}
\CustomizeMathJax{%
    \newcommand{\shortvdotswithin}%
        {\ifstar\LWRshortvdotswithinstar\LWRshortvdotswithinnostar}%
}

\CustomizeMathJax{\newcommand{\MTFlushSpaceAbove}{}}
\CustomizeMathJax{\newcommand{\MTFlushSpaceBelow}{\\}}

\LetLtxMacro\LWR@mathtools@orig@DeclarePairedDelimiter\DeclarePairedDelimiter
\renewcommand{\DeclarePairedDelimiter}[3]{
    \LWR@mathtools@orig@DeclarePairedDelimiter{#1}{#2}{#3}
% starred:
    \appto\LWR@customizedMathJax{\LWRbackslash()
    \appto\LWR@customizedMathJax{%
       \LWRbackslash{}newcommand\{\LWRbackslash\macrotocsname{#1}LWRsubstar\}%
    }%
    \appto\LWR@customizedMathJax{[2][]}%
    \appto\LWR@customizedMathJax{\{\{}%
    \LWR@subcustomizedmathjax{##1\left#2##2##1\right#3}%
    \appto\LWR@customizedMathJax{\}\}}%
    \appto\LWR@customizedMathJax{\LWRbackslash)\par}%
% not starred:
    \appto\LWR@customizedMathJax{\LWRbackslash()
    \appto\LWR@customizedMathJax{%
      \LWRbackslash{}newcommand\{\LWRbackslash\macrotocsname{#1}LWRsubnostar\}%
    }%
    \appto\LWR@customizedMathJax{[2][]}%
    \appto\LWR@customizedMathJax{\{\{}%
    \LWR@subcustomizedmathjax{##1#2##2##1#3}%
    \appto\LWR@customizedMathJax{\}\}}%
    \appto\LWR@customizedMathJax{\LWRbackslash)\par}%
% user macro:
    \appto\LWR@customizedMathJax{\LWRbackslash()
    \appto\LWR@customizedMathJax{%
        \LWRbackslash{}newcommand\{\LWRbackslash{}\macrotocsname{#1}\}%
        \{\LWRbackslash{}ifstar%
            \LWRbackslash{}\macrotocsname{#1}LWRsubstar%
            \LWRbackslash{}\macrotocsname{#1}LWRsubnostar%
        \}%
    }%
    \appto\LWR@customizedMathJax{\LWRbackslash)\par}%
}
\@onlypreamble\DeclareParedDelimiter

% (DeclarePairedDelimiterX is already defined to use \DeclarePairedDelimiterXPP.)
```

```
\LetLtxMacro\LWR@mathtools@orig@DeclarePairedDelimiterXPP\DeclarePairedDelimiterXPP
\DeclareDocumentCommand{\DeclarePairedDelimiterXPP}{m O{1} m m m m}{
    \LWR@mathtools@orig@DeclarePairedDelimiterXPP{#1}[#2]{#3}{#4}{#5}{#6}{#7}
% subsubstar, second opt arg
    \appto\LWR@customizedMathJax{\LWRbackslash()%
    \appto\LWR@customizedMathJax{%
      \LWRbackslash{}newcommand\{\LWRbackslash\macrotocsname{#1}LWRsubsubstar\}%
    }%
    \appto\LWR@customizedMathJax{[#2]}%
    \appto\LWR@customizedMathJax{\{\{\LWRbackslash{}left}%
    \LWR@subcustomizedmathjax{#3#4#7}%
    \appto\LWR@customizedMathJax{\LWRbackslash{}right}%
    \LWR@subcustomizedmathjax{#5#6}%
    \appto\LWR@customizedMathJax{\}\}}%
    \appto\LWR@customizedMathJax{\LWRbackslash)\par}%
% substar, first opt arg
    \appto\LWR@customizedMathJax{\LWRbackslash()%
    \appto\LWR@customizedMathJax{%
      \LWRbackslash{}newcommand\{\LWRbackslash\macrotocsname{#1}LWRsubstar\}[1][]%
    }%
    \appto\LWR@customizedMathJax{%
        \{
        \LWRbackslash{}def\LWRbackslash{}delimsize\{\#1\}
        \LWRbackslash\macrotocsname{#1}LWRsubsubstar
        \}%
    }%
    \appto\LWR@customizedMathJax{\LWRbackslash)\par}%
% subsubnostar, second opt arg
    \appto\LWR@customizedMathJax{\LWRbackslash()%
    \appto\LWR@customizedMathJax{%
      \LWRbackslash{}newcommand\{\LWRbackslash\macrotocsname{#1}LWRsubsubnostar\}%
    }%
    \appto\LWR@customizedMathJax{[#2]}%
    \appto\LWR@customizedMathJax{\{\{\LWRbackslash{}delimsize}%
    \LWR@subcustomizedmathjax{#3#4#7}%
    \appto\LWR@customizedMathJax{\LWRbackslash{}delimsize}%
    \LWR@subcustomizedmathjax{#5#6}%
    \appto\LWR@customizedMathJax{\}\}}%
    \appto\LWR@customizedMathJax{\LWRbackslash)\par}%
% subnostar, first opt arg
    \appto\LWR@customizedMathJax{\LWRbackslash()%
    \appto\LWR@customizedMathJax{%
      \LWRbackslash{}newcommand\{\LWRbackslash\macrotocsname{#1}LWRsubnostar\}[1][]%
    }%
    \appto\LWR@customizedMathJax{%
        \{
        \LWRbackslash{}def\LWRbackslash{}delimsize\{\#1\}
        \LWRbackslash\macrotocsname{#1}LWRsubsubnostar
        \}%
    }%
    \appto\LWR@customizedMathJax{\LWRbackslash)\par}%
% user macro:
    \appto\LWR@customizedMathJax{\LWRbackslash()
    \appto\LWR@customizedMathJax{%
```

```
        \LWRbackslash{}newcommand\{%
            \LWRbackslash{}\macrotocsname{#1}%
        \}%
            \{\LWRbackslash{}ifstar%
                \LWRbackslash{}\macrotocsname{#1}LWRsubstar%
                \LWRbackslash{}\macrotocsname{#1}LWRsubnostar%
            \}%
    }%
    \appto\LWR@customizedMathJax{\LWRbackslash)\par}%
}
\@onlypreamble\DeclareParedDelimiterXPP
\@onlypreamble\DeclareParedDelimiterX

\CustomizeMathJax{\newcommand\lparen{(}}
\CustomizeMathJax{\newcommand\rparen{)}}
\CustomizeMathJax{\newcommand{\ordinarycolon}{:}}


\CustomizeMathJax{\newcommand{\vcentcolon}{\mathrel{\unicode{x2236}}}}

\CustomizeMathJax{\newcommand\dblcolon{\mathrel{\unicode{x2237}}}}
\CustomizeMathJax{\newcommand\coloneqq{\mathrel{\unicode{x2236}\!=}}}
\CustomizeMathJax{\newcommand\Coloneqq{\mathrel{\unicode{x2237}\!=}}}
\CustomizeMathJax{\newcommand\coloneq{\mathrel{\unicode{x2236}-}}}
\CustomizeMathJax{\newcommand\Coloneq{\mathrel{\unicode{x2237}-}}}

\CustomizeMathJax{\newcommand\eqqcolon{\mathrel{=\!\unicode{x2236}}}}
\CustomizeMathJax{\newcommand\Eqqcolon{\mathrel{=\!\unicode{x2237}}}}
\CustomizeMathJax{\newcommand\eqcolon{\mathrel{-\unicode{x2236}}}}
\CustomizeMathJax{\newcommand\Eqcolon{\mathrel{-\unicode{x2237}}}}

\CustomizeMathJax{\newcommand\colonapprox{\mathrel{\unicode{x2236}\!\approx}}}
\CustomizeMathJax{\newcommand\Colonapprox{\mathrel{\unicode{x2237}\!\approx}}}
\CustomizeMathJax{\newcommand\colonsim{\mathrel{\unicode{x2236}\!\sim}}}
\CustomizeMathJax{\newcommand\Colonsim{\mathrel{\unicode{x2237}\!\sim}}}


\CustomizeMathJax{\newcommand{\nuparrow}{\mathrel{\cancel{\uparrow}}}}
\CustomizeMathJax{\newcommand{\ndownarrow}{\mathrel{\cancel{\downarrow}}}}
\CustomizeMathJax{\newcommand{\bigtimes}{\mathop{\Large\times}\limits}}

\CustomizeMathJax{\newcommand{\prescript}[3]{{}^{#1}_{#2}#3}}


\CustomizeMathJax{\newenvironment{lgathered}{\begin{gathered}}{\end{gathered}}}
\CustomizeMathJax{\newenvironment{rgathered}{\begin{gathered}}{\end{gathered}}}

\LetLtxMacro\LWR@mathtools@orig@newgathered\newgathered
\renewcommand{\newgathered}[4]{%
    \LWR@mathtools@orig@newgathered{#1}{#2}{#3}{#4}%
    \appto\LWR@customizedMathJax{\LWRbackslash(}%
    \LWR@subcustomizedmathjax{%
        \newenvironment{#1}{\begin{gathered}}{\end{gathered}}%
    }%
    \appto\LWR@customizedMathJax{\LWRbackslash)}%
}
```

```
\@onlypreamble\newgathered

\CustomizeMathJax{\newcommand{\splitfrac}[2]{{}^{#1}_{#2}}}
\CustomizeMathJax{\let\splitdfrac\splitfrac}
\end{warpMathJax}
```

File 287 **lwarp-mattens.sty**

§ 395 Package mattens

(*Emulates or patches code by* Danie Els.)

Pkg mattens mattens is used as-is for SVG math, and is emulated for MathJax.

for HTML output:

```
\LWR@ProvidesPackagePass{mattens}[2010/03/26]

\begin{warpMathJax}
\CustomizeMathJax{\newcommand{\LWRmattensnull}{}}

\CustomizeMathJax{\newcommand{\LWRmattensnostar}[2][]{%
  {#1{\LWRmattensundercmd{\LWRmattensovercmd{\LWRmattenscross{\boldsymbol{#2}}}}}}%
}}

\CustomizeMathJax{\newcommand{\LWRmattensstar}[2][]{%
    {#1{\LWRmattensundercmd{\LWRmattensovercmd{\LWRmattenscross{#2}}}}}%
}}

\CustomizeMathJax{\newcommand{\LWRmattens}{
    \ifstar\LWRmattensstar\LWRmattensnostar%
}}

\CustomizeMathJax{\newcommand{\aS}{%
    \let\LWRmattenscross\LWRmattensnull%
    \let\LWRmattensovercmd\overrightarrow%
    \let\LWRmattensundercmd\LWRmattensnull%
    \LWRmattens%
}}

\CustomizeMathJax{\newcommand{\Sa}{%
    \let\LWRmattenscross\LWRmattensnull%
    \let\LWRmattensovercmd\underrightarrow%
    \let\LWRmattensundercmd\LWRmattensnull%
    \LWRmattens%
}}

\CustomizeMathJax{\newcommand{\bS}{%
    \let\LWRmattenscross\LWRmattensnull%
    \let\LWRmattensovercmd\overline%
    \let\LWRmattensundercmd\LWRmattensnull%
    \LWRmattens%
}}

\CustomizeMathJax{\newcommand{\Sb}{%
```

```
    \let\LWRmattenscross\LWRmattensnull%
    \let\LWRmattensovercmd\underline%
    \let\LWRmattensundercmd\LWRmattensnull%
    \LWRmattens%
}}

\CustomizeMathJax{\newcommand{\aSa}{%
    \let\LWRmattenscross\LWRmattensnull%
    \let\LWRmattensovercmd\overrightarrow%
    \let\LWRmattensundercmd\underrightarrow%
    \LWRmattens%
}}

\CustomizeMathJax{\newcommand{\aSb}{%
    \let\LWRmattenscross\LWRmattensnull%
    \let\LWRmattensovercmd\overrightarrow%
    \let\LWRmattensundercmd\underline%
    \LWRmattens%
}}

\CustomizeMathJax{\newcommand{\bSa}{%
    \let\LWRmattenscross\LWRmattensnull%
    \let\LWRmattensovercmd\overline%
    \let\LWRmattensundercmd\underrightarrow%
    \LWRmattens%
}}

\CustomizeMathJax{\newcommand{\bSb}{%
    \let\LWRmattenscross\LWRmattensnull%
    \let\LWRmattensovercmd\overline%
    \let\LWRmattensundercmd\underline%
    \LWRmattens%
}}

\CustomizeMathJax{\newcommand{\aCSa}{%
    \let\LWRmattenscross\tilde%
    \let\LWRmattensovercmd\overrightarrow%
    \let\LWRmattensundercmd\underrightarrow%
    \LWRmattens%
}}

\CustomizeMathJax{\newcommand{\bCSb}{%
    \let\LWRmattenscross\tilde%
    \let\LWRmattensovercmd\overline%
    \let\LWRmattensundercmd\underline%
    \LWRmattens%
}}
\end{warpMathJax}
```

File 288 **lwarp-maybemath.sty**

§ 396 Package maybemath

(*Emulates or patches code by* Andy Buckley.)

Pkg maybemath maybemath is used as-is for SVG math, and is emulated for MathJax.

⚠ no effect MathJax is not able to detect the surrounding text font, so all maybemath macros are ignored.

for HTML output:

```
\LWR@ProvidesPackagePass{maybemath}[2005/2/22]

\begin{warpMathJax}
\CustomizeMathJax{\newcommand{\mayberm}[1]{{#1}}}
\CustomizeMathJax{\let\maybebm\mayberm}
\CustomizeMathJax{\let\maybeit\mayberm}
\CustomizeMathJax{\let\maybeitrm\mayberm}
\CustomizeMathJax{\let\maybeitsubscript\mayberm}
\CustomizeMathJax{\let\maybesf\mayberm}
\CustomizeMathJax{\let\maybebmsf\mayberm}
\end{warpMathJax}
```

File 289 **lwarp-mcaption.sty**

§ 397 Package mcaption

(*Emulates or patches code by* Stephan Hennig.)

Pkg mcaption mcaption is ignored.

for HTML output: Discard all options for lwarp-mcaption:

```
\LWR@ProvidesPackageDrop{mcaption}[2009/03/13]

\newenvironment{margincap}{}{}
\newcommand*{\margincapalign}{}
\newlength{\margincapsep}
```

File 290 **lwarp-mdframed.sty**

§ 398 Package mdframed

(*Emulates or patches code by* Marco Daniel, Elke Schubert.)

Pkg mdframed mdframed is loaded with options forced to `frame method=none`.

§ 398.1 Limitations

support Most basic functionality is supported, including frame background colors and single-border colors and thickness, title and subtitle background colors and borders and thickness, border radius, and shadow. CSS classes are created for mdframed environments and frame titles.

⚠ loading When used, lwarp loads mdframed in HTML with `framemethod=none`.

font For title font, use

```
frametitlefont=\textbf,
```

instead of

```
frametitlefont=\bfseries,
```

where `\textbf` must appear just before the comma and will receive the following text as its argument (since the text happens to be between braces in the mdframed source). Since lwarp does not support `\bfseries` and friends, only one font selection may be made at a time.

theoremtitlefont `theoremtitlefont` is not supported, since the following text is not in braces in the mdframed source.

ignored options `userdefinedwidth` and `align` are currently ignored.

css classes Environments created or encapsulated by mdframed are enclosed in a `<div>` of class `mdframed`, and also class `md<environmentname>` for new environments.

Frame titles are placed in a `<div>` of class |mdframedtitle|. Subtitles are in a `<div>` of class |mdframedsubtitle|, and likewise for subsubtitles.

Pre-existing hooks are used to patch extra functions before and after the frames.

§ 398.2 Package loading

for HTML output:

```
\RequirePackage{xcolor}% for \convertcolorspec

\LWR@ProvidesPackageDrop{mdframed}[2013/07/01]
```

Do not require Ti*k*z or pstricks:

```
\LWR@origRequirePackage[framemethod=none]{mdframed}
```

§ 398.3 Patches

Patch to remove PDF formatting and add HTML tags:

```
\AtBeginDocument{
\def\mdf@trivlist#1{%
  \edef\mdf@temp{%
%     \topsep=\the\topsep\relax%
%     \partopsep=\the\partopsep\relax%
%     \parsep=\the\parsep\relax%
  }%
%   \setlength{\topsep}{#1}%
```

```
%   \topskip\z@%
%   \partopsep\z@%
%   \parsep\z@%
%   \@nmbrlistfalse%
%   \@trivlist%
%   \labelwidth\z@%
%   \leftmargin\z@%
%   \itemindent\z@%
  \let\@itemlabel\@empty%
  \def\makelabel##1{##1}%
%   \item\relax\mdf@temp\relax%
}

\renewcommand*{\endmdf@trivlist}{%
\LWR@traceinfo{endmdf@trivlist}%
% \endtrivlist%
\LWR@listend%
}
}% AtBeginDocument
```

§ 398.4 Initial setup

To handle CSS and paragraphs, patch code at start and end of environment and contents. `\LWR@print@raggedright` helps avoid hyphenation.

```
\mdfsetup{
startcode={\LWR@mdframedstart\LWR@print@raggedright},
endcode={\LWR@mdframedend},
startinnercode={\LWR@startpars\LWR@print@raggedright},
endinnercode={\LWR@stoppars},
}
```

§ 398.5 Color and length HTML conversion

`\LWR@mdfprintcolor` {⟨*mdfcolorkey*⟩}

Given the mdframed key, print the color.

```
\newcommand*{\LWR@mdfprintcolor}[1]{%
\convertcolorspec{named}{\@nameuse{mdf@#1}}{HTML}\LWR@tempcolor%
\LWR@origpound\LWR@tempcolor
}
```

`\LWR@mdfprintlength` {⟨*mdflengthkey*⟩}

Given the mdframed key, print the length.

```
\newcommand*{\LWR@mdfprintlength}[1]{%
\LWR@forceminwidth{\@nameuse{mdf@#1@length}}%
\LWR@printlength{\LWR@atleastonept}%
}
```

§ 398.6 Environment encapsulation

\LWR@mdframedstart Actions before an mdframe starts.

Encapsulate a frame inside a of the desired class.

```
\newcommand*{\LWR@mdframedstart}{%
\LWR@traceinfo{LWR@mdframedstart start}%
```

Warn if starting a frame inside a :

```
    \LWR@spanwarninvalid{mdframe}%
```

Turn off paragraph handling during the generation of the encapsulating tags:

```
\LWR@stoppars%
```

Open a and with custom class and custom style. A BlockClass environment is not used because this is created by the mdframed startcode and endcode settings, which do not properly nest the inside the mdframed environment.

```
\LWR@htmltagc{div class=\textquotedbl%
mdframed%
\ifdefstring{\LWR@mdthisenv}{mdframed}{}{ \LWR@mdthisenv}%
\textquotedbl \LWR@orignewline
style=\textquotedbl\LWR@orignewline
```

Convert and print the background color:

```
background: \LWR@mdfprintcolor{backgroundcolor} ; \LWR@orignewline
```

Convert and print the border color and width:

```
border: \LWR@mdfprintlength{linewidth} solid
\LWR@mdfprintcolor{linecolor} ; \LWR@orignewline
```

Convert and print the border radius:

```
border-radius: \LWR@mdfprintlength{roundcorner} ; \LWR@orignewline
```

Convert and print the shadow:

```
\ifbool{mdf@shadow}{%
    box-shadow:
    \LWR@mdfprintlength{shadowsize}
    \LWR@mdfprintlength{shadowsize}
    \LWR@mdfprintlength{shadowsize}
    \LWR@mdfprintcolor{shadowcolor} ;
}
{box-shadow: none ;}
\LWR@orignewline

\textquotedbl}
% \LWR@htmldivclass{\LWR@mdthisenv}
```

mdframed environment may not work with the HTML versions of the following, so restore them to their originals while inside mdframed:

```
\LWR@select@print@hspace%
\renewcommand*{\rule}{\LWR@print@rule}
\LetLtxMacro\makebox\LWR@print@makebox%

\LWR@startpars%
\LWR@traceinfo{LWR@mdframedstart done}%
}
```

\LWR@mdframedend Actions after an mdframe ends.

After closing the , globally restore to the default environment type:

```
\newcommand*{\LWR@mdframedend}{
\LWR@traceinfo{LWR@mdframedend start}%
```

Close the custom :

```
\LWR@htmldivclassend{\LWR@mdthisenv}
```

Reset future custom class to the default:

```
\gdef\LWR@mdthisenv{mdframed}
```

Resume paragraph handling:

```
\LWR@startpars%
\LWR@traceinfo{LWR@mdframedend done}%
}
```

§ 398.7 Mdframed environment

```
\renewenvironment{mdframed}[1][]{%
 \color@begingroup%
   \mdfsetup{userdefinedwidth=\linewidth,#1}%
   \mdf@startcode%
   \mdf@preenvsetting%
   \ifdefempty{\mdf@firstframetitle}{}%
            {\let\mdf@frametitlesave\mdf@frametitle%
             \let\mdf@frametitle\mdf@firstframetitle%
            }%
   \ifvmode\nointerlineskip\fi%
        \ifdefempty{\mdf@frametitle}{}%
            {\mdfframedtitleenv{\mdf@frametitle}%
%             \mdf@@frametitle@use%
            }%
   \mdf@trivlist{\mdf@skipabove@length}%%
   \mdf@settings%
%    \mdf@lrbox{\mdf@splitbox@one}%
%    \mdf@startinnercode%
  }%
  {%
%    \mdf@@ignorelastdescenders%
   \par%
%     \unskip\ifvmode\nointerlineskip\hrule \@height\z@ \@width\hsize\fi%%
   \ifmdf@footnoteinside%
      \def\mdf@reserveda{%
        \mdf@footnoteoutput%
%         \mdf@endinnercode%
%         \endmdf@lrbox%
%         \ifdefempty{\mdf@frametitle}{}%
%             {\mdfframedtitleenv{\mdf@frametitle}\mdf@@frametitle@use}%
%         \detected@mdf@put@frame
      }%
   \else%
      \def\mdf@reserveda{%
%         \mdf@endinnercode%
```

```
%         \endmdf@lrbox%
%         \ifdefempty{\mdf@frametitle}{}%
%             {\mdfframedtitleenv{\mdf@frametitle}\mdf@@frametitle@use}%
%         \detected@mdf@put@frame%
        \mdf@footnoteoutput%
        }%
   \fi%
   \mdf@reserveda%
  \aftergroup\endmdf@trivlist%
 \color@endgroup%
 \mdf@endcode%
}
```

\mdf@footnoteoutput

```
\renewrobustcmd*\mdf@footnoteoutput{%
    \LWR@printpendingmpfootnotes%
}
```

§ 398.8 Titles and subtitles

\mdfframedtitleenv {⟨*title*⟩}

Place the title inside a of class mdframedtitle:

```
\newlength{\LWR@titleroundcorner}

\renewrobustcmd\mdfframedtitleenv[1]{%
\LWR@traceinfo{LWR@mdframedtitleenv start}%
```

Open a with a custom class and custom style:

```
\begin{BlockClass}[%
```

Convert and print the title background color:

```
background:
\LWR@mdfprintcolor{frametitlebackgroundcolor}
; \LWR@orignewline
```

Convert and print the title rule:

```
\ifbool{mdf@frametitlerule}{%
    border-bottom:
    \LWR@mdfprintlength{frametitlerulewidth}
    solid
    \LWR@mdfprintcolor{frametitlerulecolor}
    ; \LWR@orignewline
}{}%
```

Finish the custom style and the opening tag:

```
]{mdframedtitle}%
```

Print the title inside the :

```
\mdf@frametitlefont{\LWR@textcurrentfont{#1}}%
```

Close the :

```
\end{BlockClass}%
\LWR@traceinfo{LWR@mdframedtitleenv end}%
```

```
}
```

`\LWR@mdfsubtitlecommon` {⟨*sub — or — subsub*⟩} [⟨*options*⟩] {⟨*title*⟩}

Common code for `\LWR@mdfsubtitle` and `\LWR@mdfsubsubtitle`.

Encapsulate the subtitle inside a `<div>` of class `mdframedsubtitle`:

```
\NewDocumentCommand{\LWR@mdfsubtitlecommon}{m o m}
{% the following empty line is required

\LWR@traceinfo{LWR@mdframedsubtitlecommon start}%
```

Open a `<div>` with a custom `class` and custom `style`:

```
\begin{BlockClass}[%
```

Convert and print the background color:

```
background:
\LWR@mdfprintcolor{#1titlebackgroundcolor}
; \LWR@orignewline
```

Convert and print the above line:

```
\ifbool{mdf@#1titleaboveline}{%
    border-top:
    \LWR@mdfprintlength{#1titleabovelinewidth}
    solid
    \LWR@mdfprintcolor{#1titleabovelinecolor}
    ; \LWR@orignewline
}{}%
```

Convert and print the below line:

```
\ifbool{mdf@#1titlebelowline}{%
    border-bottom:
    \LWR@mdfprintlength{#1titlebelowlinewidth}
    solid
    \LWR@mdfprintcolor{#1titlebelowlinecolor}
    ; \LWR@orignewline
}{}%
```

Finish the custom style and the opening `<div>` tag:

```
]{mdframed#1title}%
```

Perform the original subtitle action:

```
\IfNoValueTF{#2}
{\@nameuse{LWR@origmdf#1title}{\csuse{mdf@#1titlefont}{\LWR@textcurrentfont{#3}}}}%
{\@nameuse{LWR@origmdf#1title}[#2]{\csuse{mdf@#1titlefont}{\LWR@textcurrentfont{#3}}}}%
```

Close the `<div>`:

```
\end{BlockClass}%
\LWR@traceinfo{LWR@mdframedsubtitlecommon end}%
}
```

`\LWR@mdfsubtitle` [⟨*options*⟩] {⟨*title*⟩}

```
\newcommand*{\LWR@mdfsubtitle}{%
```

```
\LWR@mdfsubtitlecommon{sub}%
}
\let\mdfsubtitle\LWR@mdfsubtitle
```

`\LWR@mdfsubsubtitle` `[⟨options⟩] {⟨title⟩}`

```
\newcommand*{\LWR@mdfsubsubtitle}{%
\LWR@mdfsubtitlecommon{subsub}%
}
\let\mdfsubsubtitle\LWR@mdfsubsubtitle
```

§ 398.9 New environments

`\LWR@mdthisenv` Stores the environment of the frame about to be created:

```
\newcommand*{\LWR@mdthisenv}{mdframed}
```

`\newmdenv` `[⟨options⟩] {⟨env-name⟩}`

Modified from the original to remember the environment.

```
\renewrobustcmd*\newmdenv[2][]{%
\newenvironment{#2}%
{%
\mdfsetup{#1}%
\renewcommand*{\LWR@mdthisenv}{md#2}%
\begin{mdframed}%
}
{\end{mdframed}}%
}
```

`\surroundwithmdframed` `[⟨options⟩] {⟨environment⟩}`

Modified from the original to remember the environment.

```
\renewrobustcmd*{\surroundwithmdframed}[2][]{%
\BeforeBeginEnvironment{#2}{%
\renewcommand*{\LWR@mdthisenv}{md#2}%
\begin{mdframed}[#1]}%
\AfterEndEnvironment{#2}{\end{mdframed}}%
}
```

`\mdtheorem` `[⟨mdframed-options⟩] {⟨envname⟩} [⟨numberedlike⟩] {⟨caption⟩} [⟨within⟩]`

Modified from the original to remember the environment.

```
\DeclareDocumentCommand{\mdtheorem}{ O{} m o m o }%
 {\ifcsdef{#2}%
   {\mdf@PackageWarning{Environment #2 already exits\MessageBreak}}%
   {%
    \IfNoValueTF {#3}%
     {%#3 not given -- number relationship
      \IfNoValueTF {#5}%
        {%#3+#5 not given
        \@definecounter{#2}%
        \expandafter\xdef\csname the#2\endcsname{\@thmcounter{#2}}%
        \newenvironment{#2}[1][]{%
```

```
      \refstepcounter{#2}%
      \ifstrempty{##1}%
        {\let\@temptitle\relax}%
        {%
         \def\@temptitle{\mdf@theoremseparator%
                         \mdf@theoremspace%
                         \mdf@theoremtitlefont%
                         \LWR@textcurrentfont{##1}}% lwarp
         \mdf@thm@caption{#2}{{#4}{\csname the#2\endcsname}{##1}}%
         }%
      \begin{mdframed}[#1,frametitle={\strut#4\ \csname the#2\endcsname%
                                      \@temptitle}]}%
      {\end{mdframed}}%
    \newenvironment{#2*}[1][]{%
      \ifstrempty{##1}{\let\@temptitle\relax}{\def\@temptitle{:\ ##1}}%
      \begin{mdframed}[#1,frametitle={\strut#4\@temptitle}]}%
      {\end{mdframed}}%
    }%
    {%#5 given -- reset counter
    \@definecounter{#2}\@newctr{#2}[#5]%
    \expandafter\xdef\csname the#2\endcsname{\@thmcounter{#2}}%
    \expandafter\xdef\csname the#2\endcsname{%
           \expandafter\noexpand\csname the#5\endcsname \@thmcountersep%
              \@thmcounter{#2}}%
    \newenvironment{#2}[1][]{%
      \refstepcounter{#2}%
      \ifstrempty{##1}%
        {\let\@temptitle\relax}%
        {%
         \def\@temptitle{\mdf@theoremseparator%
                         \mdf@theoremspace%
                         \mdf@theoremtitlefont%
                         \LWR@textcurrentfont{##1}}% lwarp
         \mdf@thm@caption{#2}{{#4}{\csname the#2\endcsname}{##1}}%
         }
      \begin{mdframed}[#1,frametitle={\strut#4\ \csname the#2\endcsname%
                                      \@temptitle}]}%
      {\end{mdframed}}%
    \newenvironment{#2*}[1][]{%
      \ifstrempty{##1}%
        {\let\@temptitle\relax}%
        {%
         \def\@temptitle{\mdf@theoremseparator%
                         \mdf@theoremspace%
                         \mdf@theoremtitlefont%
                         \LWR@textcurrentfont{##1}}% lwarp
         \mdf@thm@caption{#2}{{#4}{\csname the#2\endcsname}{##1}}%
         }%
      \begin{mdframed}[#1,frametitle={\strut#4\@temptitle}]}%
      {\end{mdframed}}%
    }%
  }%
  {%#3 given -- number relationship
    \global\@namedef{the#2}{\@nameuse{the#3}}%
    \newenvironment{#2}[1][]{%
```

```
          \refstepcounter{#3}%
          \ifstrempty{##1}%
            {\let\@temptitle\relax}%
            {%
             \def\@temptitle{\mdf@theoremseparator%
                             \mdf@theoremspace%
                             \mdf@theoremtitlefont%
                             \LWR@textcurrentfont{##1}}% lwarp
             \mdf@thm@caption{#2}{{#4}{\csname the#2\endcsname}{##1}}%
             }
          \begin{mdframed}[#1,frametitle={\strut#4\ \csname the#2\endcsname%
                                          \@temptitle}]}%
          {\end{mdframed}}%
        \newenvironment{#2*}[1][]{%
          \ifstrempty{##1}{\let\@temptitle\relax}{\def\@temptitle{:\ ##1}}%
          \begin{mdframed}[#1,frametitle={\strut#4\@temptitle}]}%
          {\end{mdframed}}%
     }%
    \BeforeBeginEnvironment{#2}{\renewcommand*{\LWR@mdthisenv}{md#2}}% lwarp
    \BeforeBeginEnvironment{#2*}{\renewcommand*{\LWR@mdthisenv}{md#2}}% lwarp
   }%
}
```

\newmdtheoremenv `[`⟨*1: mdframed-options*⟩`]` `{`⟨*2: envname*⟩`}` `[`⟨*3: numberedlike*⟩`]` `{`⟨*4: caption*⟩`}` `[`⟨*5: within*⟩`]`

Modified from the original to remember the environment.

```
\DeclareDocumentCommand\newmdtheoremenv{O{} m o m o }{%
 \ifboolexpr{ test {\IfNoValueTF {#3}} and test {\IfNoValueTF {#5}} }%
    {\newtheorem{#2}{#4}}%
    {%
     \IfValueT{#3}{\newtheorem{#2}[#3]{#4}}%
     \IfValueT{#5}{\newtheorem{#2}{#4}[#5]}%
    }%
 \BeforeBeginEnvironment{#2}{%
 \renewcommand*{\LWR@mdthisenv}{md#2}%
 \begin{mdframed}[#1]}%
 \AfterEndEnvironment{#2}{%
 \end{mdframed}}%
}
```

File 291 **lwarp-mdwmath.sty**

§ 399 Package mdwmath

(*Emulates or patches code by* Mark Wooding.)

Pkg mdwmath mdwmath is used as-is for SVG math, and is emulated for MathJax.

for HTML output:

```
\LWR@ProvidesPackagePass{mdwmath}[1996/04/11]

\begin{warpMathJax}
\CustomizeMathJax{\let\LWRmdwmathsqrt\sqrt}
\CustomizeMathJax{\renewcommand{\sqrt}{\ifstar\LWRmdwmathsqrt\LWRmdwmathsqrt}}
```

```
\CustomizeMathJax{\newcommand{\bitand}{\mathbin\&}}
\CustomizeMathJax{\def\bitor{\mathbin\mid}}
\CustomizeMathJax{\def\dblor{\mathbin{\mid\mid}}}
\CustomizeMathJax{\def\dbland{\mathbin{\mathrel\bitand\mathrel\bitand}}}
\end{warpMathJax}
```

File 292 **lwarp-media9.sty**

§ 400 Package

media9

Pkg media9

media9 is emulated.

The packages multimedia, movie15, and media9 are supported.

HTML5 <audio> and <video> objects are created for .mp3 and .mp4 files.

HTML5 <embed> objects are created for http and ftp links.

\href links are created for other media types. (Unfortunately, there is not much overlap between the file types supported for print output and the file types supported by HTML5.)

For media9, a multimedia object is inserted for each addresource=, as well as each flashvars source= and src=. This may result in duplicate objects.

Undesired objects may be nullified by placing them inside \warpprintonly or the warpprint environment.

Each HTML multimedia object includes the poster text, except for <embed> objects. For movie15, the text option is supported to specify the poster text.

The width, height, and totalheight options are supported. The HTML object is scaled according to the display width, correctly compensating for either tall or wide viewports.

Other options are ignored.

media9 \addmediapath is supported. It is assumed that the same path structure will exist for the HTML document.

HTML5 media controls are always specified for each <audio> and <video> object.

media9 slideshows are not supported.

\hyperlinkmovie, \movieref, and \mediabutton are not supported.

3D objects are not supported.

If using a YouTube™ video, use an "embedded" URL with .../embed/... instead of .../v/...

⚠ & in a URL

Many special characters are converted to regular catcode 12 characters for use inside a URL. & is used in the flash variables fields, which are split with xparse \SplitList, which does not seem to work with a catcode 12 divider token, so & is not converted to catcode 12, and will not work in a URL with media9. Using & in a URL in a flashvars field may also cause parsing problems with print output, as well.

for HTML output:

```
\LWR@ProvidesPackageDrop{media9}[2019/02/21]

\LWR@origRequirePackage{lwarp-common-multimedia}

\RequirePackage{xkeyval}
```

\addmediapath {⟨*path*⟩}

Supported.

```
\newcommand*{\LWR@medianine@path}{}

\newcommand*{\addmediapath}[1]{\appto\LWR@medianine@path{{#1}}}
```

The options and poster text are reused in several places.

```
\newcommand*{\LWR@medianine@postertext}{}
\newcommand*{\LWR@medianine@options}{}
```

Each addresource can generate a multimedia object.

```
\define@key{LWR@medianine}{addresource}{%
    \expandafter\LWR@multimedia\expandafter[\LWR@medianine@options]
        {\LWR@medianine@postertext}
        {#1}
}
```

Each flashvars source can generate a multimedia object.

```
\newcommand*{\LWR@medianine@flashvarsb}[1]{%
    \IfBeginWith{#1}{source=}{%
        \StrGobbleLeft{#1}{7}[\LWR@tempone]%
        \expandafter\LWR@multimedia\expandafter[\LWR@medianine@options]%
            {\LWR@medianine@postertext}%
            {\LWR@tempone}%
    }{}%
    \IfBeginWith{#1}{src=}{%
        \StrGobbleLeft{#1}{4}[\LWR@tempone]%
        \expandafter\LWR@multimedia\expandafter[\LWR@medianine@options]%
            {\LWR@medianine@postertext}%
            {\LWR@tempone}%
    }{}%
}

\NewDocumentCommand{\LWR@medianine@flashvars}{ >{\SplitList{&}} m }{%
    \ProcessList {#1}{\LWR@medianine@flashvarsb}%
}

\define@key{LWR@medianine}{flashvars}{%
    \LWR@medianine@flashvars{#1}%
}
```

\includemedia [⟨*options*⟩] {⟨*poster text*⟩} {⟨*file or* URL⟩}

```
\newcommand*{\LWR@includemediab}[3][]{%
```

```
    \let\input@path\LWR@medianine@path%
    \renewcommand*{\LWR@medianine@options}{#1}%
    \renewcommand*{\LWR@medianine@postertext}{#2}%
    \setkeys*{LWR@medianine}{#1}%
    \IfBeginWith{#3}{http}{\LWR@multimedia[#1]{#2}{#3}}{%
    \IfBeginWith{#3}{HTTP}{\LWR@multimedia[#1]{#2}{#3}}{%
    \IfBeginWith{#3}{ftp}{\LWR@multimedia[#1]{#2}{#3}}{%
    \IfBeginWith{#3}{FTP}{\LWR@multimedia[#1]{#2}{#3}}{%
    }}}}%
    \endgroup%
}

\newrobustcmd*{\includemedia}{%
    \begingroup%
    \LWR@linkmediacatcodes%
    \LWR@includemediab%
}
```

`\mediabutton` `[`⟨*options*⟩`]` `{`⟨*text*⟩`}`

Ignored.

```
\newcommand*{\mediabutton}[2][]{}
```

File 293 **lwarp-memhfixc.sty**

§ 401 Package memhfixc

Pkg memhfixc memhfixc is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{memhfixc}[2013/05/30]
```

File 294 **lwarp-menukeys.sty**

§ 402 Package menukeys

(*Emulates or patches code by* Tobias Weh.)

Pkg menukeys menukeys is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{menukeys}[2020/12/19]
```

Patch to use a `lateximage` whose `alt` text is the contents of this use of the macro. A hash on these contents allows the reuse of the image for each instance of the same contents.

```
\xpatchcmd{\tw@define@menu@macro@}
    {\@nameuse{tw@style@#4@pre}}
    {%
        \begin{lateximage}*[\detokenize{##2}]%
        \@nameuse{tw@style@#4@pre}%
    }
```

```
    {}
    {\LWR@patcherror{menukeys}{tw@define@menu@macro@}}

\xpatchcmd{\tw@define@menu@macro@}
    {\@nameuse{tw@style@#4@post}}
    {%
        \@nameuse{tw@style@#4@post}%
        \end{lateximage}%
    }
    {}
    {\LWR@patcherror{menukeys}{tw@define@menu@macro@ B}}
```

Patch the existing macros:

```
\renewmenumacro{\menu}[>]{menus}
\renewmenumacro{\directory}[/]{paths}
\renewmenumacro{\keys}[+]{roundedkeys}
```

File 295 **lwarp-metalogo.sty**

§ 403 Package metalogo

(*Emulates or patches code by* Andrew Gilbert Moschou.)

Pkg metalogo metalogo is used in print mode, and emulated in HTML.

for HTML output:

```
\LWR@ProvidesPackagePass{metalogo}[2010/05/29]

\newcommand*{\LWR@HTML@setlogokern}[2]{}
\newcommand*{\LWR@HTML@setlogodrop}[2][XeTeX]{}
\newcommand*{\LWR@HTML@setLaTeXa}[1]{}
\newcommand*{\LWR@HTML@setLaTeXee}[1]{}
\newcommand*{\LWR@HTML@seteverylogo}[1]{}
\newcommand*{\LWR@HTML@everylogo}[1]{}

\LWR@formatted{setlogokern}
\LWR@formatted{setlogodrop}
\LWR@formatted{setLaTeXa}
\LWR@formatted{setLaTeXee}
\LWR@formatted{seteverylogo}
\LWR@formatted{everylogo}
```

File 296 **lwarp-metalogox.sty**

§ 404 Package metalogox

(*Emulates or patches code by* Brian Dunn.)

Pkg metalogox metalogox is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{metalogox}[2019/01/20]
```

`\AtBeginDocument`, adjust the logo setting according to the font which is active at that moment.

```
\AtBeginDocument{
    \let\LWR@metalogox@currentformatting\LWR@formatting
    \renewcommand*{\LWR@formatting}{print}%
    \autoadjustlogos*
    \let\LWR@formatting\LWR@metalogox@currentformatting
}
```

File 297 **`lwarp-mhchem.sty`**

§ 405 Package

mhchem

(*Emulates or patches code by* Martin Hensel.)

Pkg mhchem

mhchem is patched for use by lwarp.

without MathJax

Without MathJax, mhchem expressions are converted to svg math. Inline expressions use hashed filenames to allow reuse, and assume that any mhchem options are global.

MathJax with mhchem extension

For MathJax, the mhchem extension is used if the mhchem expression is used inside a math expression:

```
$\ce{C6H5-CHO}$
```

To force the use of svg math for an expression which does not work with MathJax, place the expression between `\displaymathother` and `\displaymathnormal`:

```
\displaymathother
\[ \ce{ . . . } \]     . . .     $ \ce { . . . } $
\displaymathnormal
```

not inside math

If *not* used inside a math expression, lwarp converts standalone mhchem expressions into svg math images.

⚠ nested math

When producing html output without the MathJax mhchem extension, lwarp does not support the use of nested dollar signs in mhchem expressions.

For some examples from the mhchem manual, change as follows:

```
$\ce{NaOH(aq,$\infty$)}$            % old
$\ce{NaOH(aq,\infty)}$              % new

$\ce{Fe(CN)_{$\frac{6}{2}$}$}$      % old
$\ce{Fe(CN)_{\frac{6}{2}}}$         % new

$\ce{NO_$x$}$                       % old
$\ce{NO_x}$                         % new

$\ce{NO_${x}$}$                     % old
$\ce{NO_{x}}$                       % new
```

```
$\ce{$cis${-}[PtCl2(NH3)2]}$        % old
$\ce{\mathit{cis}{-}[PtCl2(NH3)2]}$ % new
```

for HTML output:

```
\LWR@ProvidesPackagePass{mhchem}[2018/06/22]
```

The original definition of `\ce`:

```
\LetLtxMacro\LWR@mhchem@origce\ce
```

The new definition, called from the new `\ce` after math shift is set. The starred `lateximage` uses a hashed filename for the SVG image. The `alt` tag is set to the mhchem expression.

```
\newcommand{\LWR@mhchem@HTML@ce}[1]{%
\LWR@findcurrenttextcolor% sets \LWR@tempcolor
\ifbool{LWR@xfakebold}%
    {\def\LWR@tempone{Y}}%
    {\def\LWR@tempone{N}}%
\begin{lateximage}*[\textbackslash{}ce\{\LWR@HTMLsanitize{#1}\}]*%
    [%
        FM\LWR@f@family%
        SR\LWR@f@series%
        SH\LWR@f@shape%
        SHC\LWR@f@shapecaps%
        CL\LWR@tempcolor%
        FB\LWR@tempone% xfakebold
    ]%
\LWR@setcurrentfont%
\LWR@mhchem@origce{#1}%
\end{lateximage}%
\endgroup%
\addtocounter{LWR@mhchem@cedepth}{-1}%
}
```

Only set math shift if outer depth:

```
\newcounter{LWR@mhchem@cedepth}
\setcounter{LWR@mhchem@cedepth}{0}
```

The new `\ce`. Sets math shift then continues.

```
\renewcommand{\ce}{%
\begingroup%
\ifnumequal{\value{LWR@mhchem@cedepth}}{0}{%
    \catcode`\$=3% math shift
}{}%
\addtocounter{LWR@mhchem@cedepth}{1}%
\LWR@mhchem@HTML@ce%
}
```

The original definition of `\cesplit`:

```
\LetLtxMacro\LWR@mhchem@origcesplit\cesplit
```

The new definition, called from the new \cesplit after math shift is set. The starred lateximage uses a hashed filename for the SVG image. The alt tag is set to the mhchem expression.

```
\newcommand*{\LWR@mhchem@HTML@cesplit}[2]
{%
\LWR@findcurrenttextcolor% sets \LWR@tempcolor
\ifbool{LWR@xfakebold}%
    {\def\LWR@tempone{Y}}%
    {\def\LWR@tempone{N}}%
\begin{lateximage}*[\textbackslash{}cesplit\{\LWR@HTMLsanitize{#2}\}]*%
    [%
        FM\LWR@f@family%
        SR\LWR@f@series%
        SH\LWR@f@shape%
        SHC\LWR@f@shapecaps%
        CL\LWR@tempcolor%
        FB\LWR@tempone% xfakebold
    ]%
\LWR@setcurrentfont%
\LWR@mhchem@origcesplit{#1}{#2}%
\end{lateximage}%
\endgroup%
}
```

Only set math shift if outer depth:

```
\newcounter{LWR@mhchem@cesplitdepth}
\setcounter{LWR@mhchem@cesplitdepth}{0}
```

The new \cesplit. Sets math shift then continues.

```
\renewcommand{\cesplit}{%
\begingroup%
\ifnumequal{\value{LWR@mhchem@cesplitdepth}}{0}{%
    \catcode`\$=3% math shift
}{}%
\addtocounter{LWR@mhchem@cesplitdepth}{1}%
\LWR@mhchem@HTML@cesplit%
}
```

Resore originals inside a lateximage:

```
\appto\LWR@restoreorigformatting{%
\LetLtxMacro\ce\LWR@mhchem@origce%
\LetLtxMacro\cesplit\LWR@mhchem@origcesplit%
}

\begin{warpMathJax}
\CustomizeMathJax{\require{mhchem}}
\end{warpMathJax}
```

File 298 **lwarp-microtype.sty**

§ 406 Package microtype

(*Emulates or patches code by* R Schlicht.)

Pkg microtype microtype is pre-loaded by lwarp. All user options and macros are ignored and disabled.

for HTML output: Discard all options for lwarp-microtype:

```
\LWR@ProvidesPackageDrop{microtype}[2018/01/14]

\DeclareDocumentCommand{\DeclareMicrotypeSet}{o m m}{}
\DeclareDocumentCommand{\UseMicrotypeSet}{o m}{}
\DeclareDocumentCommand{\DeclareMicrotypeSetDefault}{o m}{}
\DeclareDocumentCommand{\SetProtrusion}{o m m}{}
\DeclareDocumentCommand{\SetExpansion}{o m m}{}
\DeclareDocumentCommand{\SetTracking}{o m m}{}
\DeclareDocumentCommand{\SetExtraKerning}{o m m}{}
\DeclareDocumentCommand{\SetExtraSpacing}{o m m}{}
\DeclareDocumentCommand{\DisableLigatures}{o m}{}
\DeclareDocumentCommand{\DeclareCharacterInheritance}{o m m}{}
\DeclareDocumentCommand{\DeclareMicrotypeVariants}{m}{}
\DeclareDocumentCommand{\DeclareMicrotypeAlias}{m m}{}
\DeclareDocumentCommand{\LoadMicrotypeFile}{m}{}
\DeclareDocumentCommand{\DeclareMicrotypeBabelHook}{m m}{}
\DeclareDocumentCommand{\microtypesetup}{m}{}
\DeclareDocumentCommand{\microtypecontext}{m}{}
\DeclareDocumentCommand{\textmicrotypecontext}{m m}{#2}
\@ifpackageloaded{letterspace}{\let\MT@textls\relax}{%
\DeclareDocumentCommand{\lsstyle}{}{}
\DeclareDocumentCommand{\textls}{o +m}{}
\DeclareDocumentCommand{\lslig}{m}{#1}
}
\def\DeclareMicrotypeSet#1#{\@gobbletwo}
\def\DeclareMicrotypeVariants#1#{\@gobble}
\@onlypreamble\DeclareMicrotypeSet
\@onlypreamble\UseMicrotypeSet
\@onlypreamble\DeclareMicrotypeSetDefault
\@onlypreamble\DisableLigatures
\@onlypreamble\DeclareMicrotypeVariants
\@onlypreamble\DeclareMicrotypeBabelHook
```

File 299 **lwarp-midfloat.sty**

§ 407 Package midfloat

(*Emulates or patches code by* Sigitas Tolušis.)

Pkg midfloat midfloat is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{midfloat}[2012/05/29]

\newenvironment{strip}[1][]{}{}
\newskip\stripsep
```

File 300 **lwarp-midpage.sty**

§ 408 Package midpage

Pkg midpage midpage is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{midpage}[2009/09/03]

\newenvironment{midpage}
{\begin{BlockClass}[%
    \LWR@print@mbox{margin-top:6ex} ; \LWR@print@mbox{margin-bottom:6ex}%
]{midpage}}
{\end{BlockClass}}
```

File 301 **lwarp-minibox.sty**

§ 409 Package minibox

(*Emulates or patches code by* Will Robertson.)

Pkg minibox minibox is patched for use by lwarp.

Due to HTML limitations regarding paragraphs and s, miniboxes inline with other text will appear on their own line.

for HTML output:

```
\LWR@ProvidesPackagePass{minibox}[2013/06/21]

\ExplSyntaxOn
\newcommand\LWR@HTML@minibox[2][]{%
    \LWR@stoppars%
    \group_begin:
    \keys_set:nn {minibox} {#1}
    \bool_if:NTF \l_minibox_frame_bool
    {
        \setlength\fboxrule{\l_minibox_rule_dim}
        \setlength\fboxsep{\l_minibox_pad_dim}
        \fboxBlock{%
            \begin{tabular}[\l_minibox_tabular_valign_tl]%
              {\l_minibox_tabular_preamble_tl}
                {#2}
            \end{tabular}
        }%
    }
    {
        \begin{BlockClass}[display:inline-block]{minibox}
        \begin{tabular}[\l_minibox_tabular_valign_tl]%
          {\l_minibox_tabular_preamble_tl}
            {#2}
```

```
        \end{tabular}
        \end{BlockClass}
    }
    \group_end:
    \LWR@startpars%
}
\ExplSyntaxOff

\LWR@formatted{minibox}
```

File 302 **lwarp-minitoc.sty**

§ 410 Package

minitoc

Pkg minitoc minitoc is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{minitoc}[2018/07/12]
```

mtcoff disables minitoc.

```
\usepackage{mtcoff}
```

File 303 **lwarp-minted.sty**

§ 411 Package

minted

(*Emulates or patches code by* Geoffrey M. Poore.)

Pkg minted minted is patched for use by lwarp.

⚠ limitations mathescape and highlightlines don't work. Line numbers on the right will not be aligned. Due to *pdftotext*, extra spaces may appear in broken lines if other formatting is included.

for HTML output:

```
\LWR@ProvidesPackagePass{minted}[2017/07/19]

\xpatchcmd{\minted}
    {\setkeys{minted@opt@cmd}{#1}}
    {%
        \setkeys{minted@opt@cmd}{%
            #1,%
            mathescape=false,breaklines,texcomments=false,highlightlines={}%
        }%
    }
    {}
    {\LWR@patcherror{minted}{minted}}

\xpatchcmd{\mintinline}
    {\setkeys{minted@opt@cmd}{#1}}
    {\setkeys{minted@opt@cmd}{%
```

```
            #1,%
            mathescape=false,breaklines,texcomments=false,highlightlines={}%
        }%
    }
    {}
    {\LWR@patcherror{minted}{mintinline}}

\xpatchcmd{\mint}
    {\setkeys{minted@opt@cmd}{#1}}
    {%
        \setkeys{minted@opt@cmd}{%
            #1,%
            mathescape=false,breaklines,texcomments=false,highlightlines={}%
        }%
    }
    {}
    {\LWR@patcherror{minted}{mint}}

\xpatchcmd{\inputminted}
    {\setkeys{minted@opt@cmd}{#1}}
    {\setkeys{minted@opt@cmd}{%
            #1,%
            mathescape=false,breaklines,texcomments=false,highlightlines={}%
        }%
    }
    {}
    {\LWR@patcherror{minted}{inputminted}}
```

File 304 **lwarp-mismath.sty**

§ 412 Package

mismath

(*Emulates or patches code by* Antoine Missier.)

Pkg mismath mismath is patched for SVG math, and emulated for MathJax.

⚠ MathJax `\enumber`, `\inumber`, `\jnumber`, and `\pinumber` are ignored for MathJax, except that `\itpi` is made available as a clone of `\pi`.

For MathJax, `\boldvect` and `\arrowvect` are honored if in the preamble.

If `\boldvectcommand` is set to `\mathbf` in the preamble, it will be used for MathJax, otherwise it will default to `\mathit`. `\boldvectcommand` may also be set with `\CustomizeMathJax` in the preamble. See section 8.7.5. Note that as of this writing there is not a bold italic font across all MathJax fonts.

If `\probastyle` is set to `\mathbb` in the preamble, it will be used for MathJax, otherwise it will default to `\mathrm`. `\probastyle` may be set with `\CustomizeMathJax` in the preamble.

If `\mathset` is set to `\mathbb` in the preamble, it will be used for MathJax, otherwise it will default to `\mathbf`. `\mathset` may be set with `\CustomizeMathJax` in the preamble.

for HTML output:

```
\LWR@ProvidesPackagePass{mismath}[2019/12/27]
```

For MathJax, used in the HTML comment before the environment.

```
\ifbool{mathjax}{
    \RenewEnviron{mathcols}{%
        \preto\BODY{\begin{aligned}\displaystyle}
        \appto\BODY{\end{aligned}}
        \expandafter\(\BODY\)
    }
}% mathjax
```

For SVG math. The `lateximage` restores the original defintion of the `math` environment.

```
{% svg
    \renewenvironment{mathcols}{
        \begin{lateximage}
        \begin{math}
        \begin{aligned}\displaystyle
    }{
        \end{aligned}%
        \end{math}
        \end{lateximage}
    }
}% svg

\renewcommand{\changecol}{
    \end{aligned}   \qquad
    \begin{aligned}\displaystyle
}

\begin{warpMathJax}
\CustomizeMathJax{\newcommand{\mathup}[1]{\mathrm{#1}}}
\CustomizeMathJax{\newcommand{\e}{\mathrm{e}}}
\CustomizeMathJax{\newcommand{\i}{\mathrm{i}}}
\CustomizeMathJax{\newcommand{\j}{\mathrm{j}}}

\CustomizeMathJax{\newcommand{\boldvect}{}}
\CustomizeMathJax{\newcommand{\arrowvect}{}}
\CustomizeMathJax{\newcommand{\pinumber}[1][]{}}
\CustomizeMathJax{\newcommand{\hvect}[1]{\vec{\vphantom{h}#1}}}
\CustomizeMathJax{\newcommand{\hvec}[1]{\vec{\vphantom{t}#1}}}
\CustomizeMathJax{%
    \newcommand{\norm}[1]{\left\vert\left\vert#1\right\vert\right\vert}
}
\CustomizeMathJax{\newcommand{\di}{\mathop{}\!\mathrm{d}}}

\CustomizeMathJax{\newcommand{\P}{\operatorname{\probastyle{P}}}}
\CustomizeMathJax{\newcommand{\E}{\operatorname{\probastyle{E}}}}
\CustomizeMathJax{\newcommand{\V}{\operatorname{\probastyle{V}}}}
\CustomizeMathJax{\newcommand{\Par}{\unicode{x00B6}}}

\CustomizeMathJax{\DeclareMathOperator{\adj}{adj}}
\CustomizeMathJax{\DeclareMathOperator{\Aut}{Aut}}
\CustomizeMathJax{\DeclareMathOperator{\Conv}{Conv}}
\CustomizeMathJax{\DeclareMathOperator{\cov}{cov}}
\CustomizeMathJax{\DeclareMathOperator{\Cov}{Cov}}
```

```
\CustomizeMathJax{\newcommand{\curl}{\operatorname{\vect{\mathrm{curl}}}}}
\CustomizeMathJax{\DeclareMathOperator{\divg}{div}}
\CustomizeMathJax{\DeclareMathOperator{\End}{End}}

\CustomizeMathJax{\DeclareMathOperator{\erf}{erf}}
\CustomizeMathJax{\newcommand{\grad}{\operatorname{\vect{\mathrm{grad}}}}}
\CustomizeMathJax{\DeclareMathOperator{\id}{id}}
\CustomizeMathJax{\DeclareMathOperator{\Id}{Id}}
\CustomizeMathJax{\DeclareMathOperator{\im}{im}}
\CustomizeMathJax{\let\oldIm\Im}
\CustomizeMathJax{\renewcommand{\Im}{\operatorname{Im}}}
\CustomizeMathJax{\DeclareMathOperator{\lb}{lb}}
\CustomizeMathJax{\DeclareMathOperator{\lcm}{lcm}}

\CustomizeMathJax{\DeclareMathOperator{\rank}{rank}}
\CustomizeMathJax{\let\oldRe\Re}
\CustomizeMathJax{\renewcommand{\Re}{\operatorname{Re}}}
\CustomizeMathJax{\newcommand{\rot}{\operatorname{\vect{\mathrm{rot}}}}}
\CustomizeMathJax{\DeclareMathOperator{\sgn}{sgn}}
\CustomizeMathJax{\DeclareMathOperator{\spa}{span}}
\CustomizeMathJax{\DeclareMathOperator{\tr}{tr}}
\CustomizeMathJax{\DeclareMathOperator{\Var}{Var}}
\CustomizeMathJax{\DeclareMathOperator{\Zu}{Z}}

\CustomizeMathJax{\DeclareMathOperator{\arccot}{arccot}}
\CustomizeMathJax{\DeclareMathOperator{\sech}{sech}}
\CustomizeMathJax{\DeclareMathOperator{\csch}{csch}}
\CustomizeMathJax{\DeclareMathOperator{\arsinh}{arsinh}}
\CustomizeMathJax{\DeclareMathOperator{\arcosh}{arcosh}}
\CustomizeMathJax{\DeclareMathOperator{\artanh}{artanh}}
\CustomizeMathJax{\DeclareMathOperator{\arcoth}{arcoth}}
\CustomizeMathJax{\DeclareMathOperator{\arsech}{arsech}}
\CustomizeMathJax{\DeclareMathOperator{\arcsch}{arcsch}}

\CustomizeMathJax{\DeclareMathOperator{\bigO}{\mathcal{O}}}
\CustomizeMathJax{\DeclareMathOperator{\bigo}{O}}
\CustomizeMathJax{\DeclareMathOperator{\lito}{o}}

\CustomizeMathJax{\newcommand{\R}{\mathset{R}}}
\CustomizeMathJax{\newcommand{\C}{\mathset{C}}}
\CustomizeMathJax{\newcommand{\N}{\mathset{N}}}
\CustomizeMathJax{\newcommand{\Z}{\mathset{Z}}}
\CustomizeMathJax{\newcommand{\Q}{\mathset{Q}}}
\CustomizeMathJax{\newcommand{\F}{\mathset{F}}}
\CustomizeMathJax{\newcommand{\K}{\mathset{K}}}

\CustomizeMathJax{\newcommand{\ds}{\displaystyle}}
\CustomizeMathJax{\newcommand{\dlim}{\lim\limits}}
\CustomizeMathJax{\newcommand{\dsum}{\sum\limits}}
\CustomizeMathJax{\newcommand{\dprod}{\prod\limits}}
\CustomizeMathJax{\newcommand{\dcup}{\bigcup\limits}}
\CustomizeMathJax{\newcommand{\dcap}{\bigcap\limits}}
\CustomizeMathJax{\newcommand{\lbar}{\overline}}
\CustomizeMathJax{\newcommand{\hlbar}[1]{\overline{\vphantom{h}#1}}}
\CustomizeMathJax{\newcommand{\eqdef}{\stackrel{\mathrm{def}}{=}}}
```

```
\CustomizeMathJax{\newcommand{\unbr}{\underbrace}}
\CustomizeMathJax{\newcommand{\iif}{if and only if }}

\CustomizeMathJax{\newcommand{\mul}{\mathord{\times}}}
\CustomizeMathJax{\newcommand{\then}{\ \Longrightarrow \ \mbox{} }}
\CustomizeMathJax{\newcommand{\txt}[1]{\quad\text{#1}\quad}}
\CustomizeMathJax{\newcommand{\paren}[1]{\mathopen{\left(#1\right)}}}
\CustomizeMathJax{\newcommand{\pow}[2]{\left( #1 \right)^{\!#2}}}
\CustomizeMathJax{\newcommand{\abs}[1]{\left\vert#1\right\vert}}
\CustomizeMathJax{\newcommand{\lfrac}[2]{\frac{\:#1\:}{\:#2\:}}}

\CustomizeMathJax{\newenvironment{system}[1][l]%
    {\left\{\begin{array}{@{.15em}#1@{}}}
    {\end{array}\right.}
}

\CustomizeMathJax{\newenvironment{spmatrix}
    {\left(\begin{smallmatrix}}
    {\end{smallmatrix}\right)}
}

\CustomizeMathJax{%
    \newenvironment{mathcols}
        {\begin{aligned}\displaystyle}
        {\end{aligned}}
}
\CustomizeMathJax{\newcommand{\changecol}{\end{aligned}\qquad\begin{aligned}}}
```

User-adjustable settings, detected if in the preamble.

```
\AtBeginDocument{
\ifdef{\itpi}{
    \CustomizeMathJax{\let\itpi\pi}
}{}
\ifdefstring{\boldvectcommand}{\mathbf}{
    \CustomizeMathJax{\newcommand{\boldvectcommand}[1]{\mathbf{#1}}}
}{
    \CustomizeMathJax{\newcommand{\boldvectcommand}[1]{\boldsymbol{#1}}}
}
\ifbool{arrowvect}{
    \CustomizeMathJax{\newcommand{\vect}[1]{\overrightarrow{#1}}}
}{
    \CustomizeMathJax{\newcommand{\vect}[1]{\boldvectcommand{#1}}}
}
\ifdefstring{\probastyle}{\mathbb}{
    \CustomizeMathJax{\newcommand{\probastyle}[1]{\mathbb{#1}}}
}{
    \CustomizeMathJax{\newcommand{\probastyle}[1]{\mathrm{#1}}}
}
\ifdefstring{\mathset}{\mathbb}{
    \CustomizeMathJax{\newcommand{\mathset}[1]{\mathbb{#1}}}
}{
    \CustomizeMathJax{\newcommand{\mathset}[1]{\mathbf{#1}}}
}
}
```

```
159 \end{warpMathJax}
```

File 305 **lwarp-mleftright.sty**

§ 413 Package mleftright

(*Emulates or patches code by* Heiko Oberdiek.)

Pkg mleftright mleftright is used as-is, and is emulated for MathJax.

for HTML output:

```
1 \LWR@ProvidesPackagePass{mleftright}[2019/12/03]

2 \begin{warpMathJax}
3 \CustomizeMathJax{\newcommand{\mleft}{\left}}
4 \CustomizeMathJax{\newcommand{\mright}{\right}}
5 \CustomizeMathJax{\newcommand{\mleftright}{}}
6 \CustomizeMathJax{\newcommand{\mleftrightrestore}{}}
7 \end{warpMathJax}
```

File 306 **lwarp-morefloats.sty**

§ 414 Package morefloats

Pkg morefloats morefloats is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{morefloats}[2015/07/22]
```

File 307 **lwarp-moreverb.sty**

§ 415 Package moreverb

(*Emulates or patches code by* Robin Fairbairns.)

Pkg moreverb moreverb is supported with some patches.

```
1 \LWR@ProvidesPackagePass{moreverb}[2008/06/03]

2 \BeforeBeginEnvironment{verbatimtab}{%
3 \LWR@forcenewpage
4 \LWR@atbeginverbatim{Verbatim}%
5 }
6 \AfterEndEnvironment{verbatimtab}{%
7 \LWR@afterendverbatim%
8 }
9
10
11 \LetLtxMacro\LWRMV@orig@verbatimtabinput\@verbatimtabinput
```

```
12
13 \renewcommand{\@verbatimtabinput}[2][]{%
14 \LWR@forcenewpage
15 \LWR@atbeginverbatim{Verbatim}%
16 \LWRMV@orig@verbatimtabinput[#1]{#2}%
17 \LWR@afterendverbatim%
18 }
19
20 \BeforeBeginEnvironment{listing}{%
21 \LWR@forcenewpage
22 \LWR@atbeginverbatim{programlisting}%
23 }
24
25 \AfterEndEnvironment{listing}{%
26 \LWR@afterendverbatim%
27 }
28
29 \BeforeBeginEnvironment{listingcont}{%
30 \LWR@forcenewpage
31 \LWR@atbeginverbatim{programlisting}%
32 }
33
34 \AfterEndEnvironment{listingcont}{%
35 \LWR@afterendverbatim%
36 }

37 \LetLtxMacro\LWRMV@@listinginput\@listinginput
38
39 \renewcommand{\@listinginput}[3][]{
40 \LWR@forcenewpage
41 \LWR@atbeginverbatim{programlisting}%
42 \LWRMV@@listinginput[#1]{#2}{#3}%
43 \LWR@afterendverbatim%
44 }
45
46
47 \renewenvironment*{boxedverbatim}
48 {
49 \LWR@forcenewpage
50 \LWR@atbeginverbatim{boxedverbatim}%
51 \verbatim%
52 }
53 {
54 \endverbatim%
55 \LWR@afterendverbatim%
56 }
```

File 308 **lwarp-movie15.sty**

§ 416 Package

movie15

Pkg movie15 movie15 is emualted.

The packages multimedia, movie15, and media9 are supported.

HTML5 <audio> and <video> objects are created for .mp3 and .mp4 files.

HTML5 <embed> objects are created for http and ftp links.

\href links are created for other media types. (Unfortunately, there is not much overlap between the file types supported for print output and the file types supported by HTML5.)

For media9, a multimedia object is inserted for each addresource=, as well as each flashvars source= and src=. This may result in duplicate objects.

Undesired objects may be nullified by placing them inside \warpprintonly or the warpprint environment.

Each HTML multimedia object includes the poster text, except for <embed> objects. For movie15, the text option is supported to specify the poster text.

The width, height, and totalheight options are supported. The HTML object is scaled according to the display width, correctly compensating for either tall or wide viewports.

Other options are ignored.

media9 \addmediapath is supported. It is assumed that the same path structure will exist for the HTML document.

HTML5 media controls are always specified for each <audio> and <video> object.

media9 slideshows are not supported.

\hyperlinkmovie, \movieref, and \mediabutton are not supported.

3D objects are not supported.

If using a YouTube™ video, use an "embedded" URL with .../embed/... instead of .../v/...

for HTML output:

```
\LWR@ProvidesPackageDrop{movie15}[2012/05/16]

\LWR@origRequirePackage{lwarp-common-multimedia}

\RequirePackage{xkeyval}

\newcommand*{\LWR@moviefifteen@text}{}

\define@key{LWR@moviefifteen}{text}{\renewcommand{\LWR@moviefifteen@text}{#1}}

\newcommand*{\LWR@includemovieb}[4][]{%
    \renewcommand{\LWR@moviefifteen@text}{(multimedia)}
    \setkeys*{LWR@moviefifteen}{#1}%
    \LWR@multimediab[#1,width=#2,height=#3]{\LWR@moviefifteen@text}{#4}%
}

\newrobustcmd*{\includemovie}{%
    \begingroup%
    \LWR@linkmediacatcodes%
    \LWR@includemovieb%
}
```

```
21
22
23 \newcommand*{\movieref}[3][]{}
24
25 \LetLtxMacro\movie\LWR@multimedia
26 % \LetLtxMacro\sound\LWR@multimedia% not in media15
27
28 \newcommand{\hyperlinkmovie}[3][]{}
```

File 309 **lwarp-mparhack.sty**

§ 417 Package mparhack

Pkg mparhack mparhack is ignored.

for HTML output: Discard all options for lwarp-mparhack:

```
1 \LWR@ProvidesPackageDrop{mparhack}[2005/04/17]
```

File 310 **lwarp-multibib.sty**

§ 418 Package multibib

(*Emulates or patches code by* Thorsten Hansen.)

Pkg multibib multibib is patched for use by lwarp.

for HTML output:

```
1 \LWR@ProvidesPackagePass{multibib}[2008/12/10]

2 \xpatchcmd{\newcites}
3     {{\@suffix}}
4     {{\@suffix_html}}
5     {}
6     {\LWR@patcherror{multibib}{newcites}}
```

File 311 **lwarp-multicap.sty**

§ 419 Package multicap

Pkg multicap multicap is emualted.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{multicap}[2002/05/04]

2 \newcommand*{\mfcaption}{\captionof{figure}}
3 \newcommand*{\mtcaption}{\captionof{table}}
4 \newcounter{mcapsize}
5 \newcounter{mcapskip}
6 \newlength{\abvmcapskip}
7 \newlength{\blwmcapskip}
```

File 312 **lwarp-multicol.sty**

§ 420 Package

multicol

(*Emulates or patches code by* Frank Mittelbach.)

Pkg multicol multicol is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{multicol}[2018/12/27]
```

Multicols are converted into a 1–3 column display, browser-supported.

The optional multicols heading is placed inside a of class multicolsheading.

The content is placed inside a of class multicols.

Env multicols * {⟨*numcols*⟩} [⟨*heading*⟩]

```
\NewDocumentEnvironment{multicols}{s m o}
```

HTML class to contain everything:

```
{
    \LWR@forcenewpage
    \BlockClass{multicols}
```

Optional HTML class for the heading:

```
    \IfValueT{#3}{\begin{BlockClass}{multicolsheading}#3\end{BlockClass}}%
```

Change \linewidth to compensate for expected size:

```
    \setlength{\linewidth}{\linewidth/#2}
```

Locally force any minipages to be fullwidth:

```
    \booltrue{LWR@forceminipagefullwidth}
}
```

When done with the environment, close the :

```
{\endBlockClass}
```

Emulated null functions which are not used in HTML:

```
\newcommand*{\columnbreak}{}
\newcommand*{\RLmulticolcolumns}{}
\newcommand*{\LRmulticolcolumns}{}

\newlength{\premulticols}
\newlength{\postmulticols}
\newlength{\multicolsep}
\newlength{\multicolbaselineskip}
\newlength{\multicoltolerance}
\newlength{\multicolpretolerance}
\newcommand*{\columnseprulecolor}{\normalcolor}
```

```
\newcounter{columnbadness}
\newcounter{finalcolumnbadness}
\newcounter{collectmore}
\newcounter{unbalance}
\newlength{\multicolovershoot}
\newlength{\multicolundershoot}

\NewDocumentCommand{\docolaction}{s o m m m}{%
    \IfValueTF{#2}{#2}{#3}%
}
```

File 313 **lwarp-multicolrule.sty**

§ 421 Package multicolrule

Pkg multicolrule multicolrule is ignored.

for HTML output:

```
\RequirePackage{multicol}

\LWR@ProvidesPackageDrop{multicolrule}[2019/01/01]

\newcommand*{\SetMCRule}[1]{}
\NewDocumentCommand{\DeclareMCRulePattern}{m m}{}
```

File 314 **lwarp-multimedia.sty**

§ 422 Package multimedia

Pkg multimedia multimedia is emulated.

The packages multimedia, movie15, and media9 are supported.

HTML5 <audio> and <video> objects are created for .mp3 and .mp4 files.

HTML5 <embed> objects are created for http and ftp links.

\href links are created for other media types. (Unfortunately, there is not much overlap between the file types supported for print output and the file types supported by HTML5.)

For media9, a multimedia object is inserted for each addresource=, as well as each flashvars source= and src=. This may result in duplicate objects.

Undesired objects may be nullified by placing them inside \warpprintonly or the warpprint environment.

Each HTML multimedia object includes the poster text, except for <embed> objects. For movie15, the text option is supported to specify the poster text.

The width, height, and totalheight options are supported. The HTML object is scaled according to the display width, correctly compensating for either tall or wide viewports.

Other options are ignored.

media9 `\addmediapath` is supported. It is assumed that the same path structure will exist for the HTML document.

HTML5 media controls are always specified for each `<audio>` and `<video>` object.

media9 slideshows are not supported.

`\hyperlinkmovie`, `\movieref`, and `\mediabutton` are not supported.

3D objects are not supported.

If using a YouTube™ video, use an "embedded" URL with …`/embed/`… instead of …`/v/`…

for HTML output:

```
\LWR@ProvidesPackageDrop{multimedia}[2012/05/02]

\LWR@origRequirePackage{lwarp-common-multimedia}

\LetLtxMacro\movie\LWR@multimedia
\LetLtxMacro\sound\LWR@multimedia

\newcommand{\hyperlinkmovie}[3][]{}
```

File 315 **lwarp-multiobjective.sty**

§ 423 Package

multiobjective

(*Emulates or patches code by* Luis Martí.)

Pkg `multiobjective` multiobjective is used as-is for SVG math, and is emulated for MathJax.

for HTML output:

```
\LWR@ProvidesPackagePass{multiobjective}[2008/08/19]

\begin{warpMathJax}
\CustomizeMathJax{\newcommand{\dom}{\prec}}
\CustomizeMathJax{\newcommand{\negdom}{\not\prec}}
\CustomizeMathJax{\newcommand{\weakdom}{\preccurlyeq}}
\CustomizeMathJax{\newcommand{\negweakdom}{\not\preccurlyeq}}

\CustomizeMathJax{\newcommand{\strictdom}{\mathord{\prec}\!\!\!\mathord{\prec}}}
\CustomizeMathJax{\newcommand{\negstrictdom}{\mathord{\not\prec}\!\!\!\mathord{\prec}}}
\CustomizeMathJax{\newcommand{\multepsilondom}{\preccurlyeq_{\epsilon\cdot}}}
\CustomizeMathJax{\newcommand{\addiepsilondom}{\preccurlyeq_{\epsilon +}}}
\CustomizeMathJax{\newcommand{\better}{\triangleleft}}
\CustomizeMathJax{\def\vec#1{%
    \mathchoice%
        {{\displaystyle\boldsymbol{#1}}}%
        {{\textstyle\boldsymbol{#1}}}%
        {{\scriptstyle\boldsymbol{#1}}}%
        {{\scriptscriptstyle\boldsymbol{#1}}}%
}}

```

```
\CustomizeMathJax{\newcommand{\set}[1]{%
    \mathchoice%
        {{\displaystyle\mathcal{#1}}}%
        {{\textstyle\mathcal{#1}}}%
        {{\scriptstyle\mathcal{#1}}}%
        {{\scriptscriptstyle\mathcal{#1}}}%
}}
\CustomizeMathJax{\def\argmax{\mathop{{\mathrm{arg}}\,\max}}}
\CustomizeMathJax{\def\argmin{\mathop{{\mathrm{arg}}\,\min}
}}
\end{warpMathJax}
```

File 316 **lwarp-multirow.sty**

§ 424 Package

multirow

(*Emulates or patches code by* Piet van Oostrum, Øystein Bache, Jerry Leichter.)

Pkg multirow multirow is emulated during HTML output, and used as-is while inside a `latexmage`.

vposn

- Note that recent versions of multirow include a new optional vposn argument.

multirow cells

- For multirow, insert `\mrowcell` into any empty multi-row cells. This will be a null function for the print output, and is a placeholder for parsing the table for HTML output. An error is generated if this is missed.

```
... &  \multirow{2}{.5in}{text}  & ...
... &  \mrowcell                 & ...
```

colored cells

- The multirow documentation regarding colored cells recommends using a negative number of rows. This will not work with lwarp, so `\warpprintonly` and `\warpHTMLonly` must be used to make versions for print and HTML.

with \multicolumn

- See section 424.2 for `\multicolumrow`.

⚠ \multicolumn & \multirow

lwarp does not support directly combining `\multicolumn` and `\multirow`. Use `\multicolumnrow` instead. To create a 2 column, 3 row cell:

```
\multicolumnrow{2}{c}[c]{3}[0]{1in}[0pt]{Text}
```

The two arguments for `\multicolumn` come first, followed by the five arguments for `\multirow`, many of which are optional, followed by the contents.

⚠ skipped cells

⚠ empty cells

As per `\multirow`, skipped cells to the right of the `\multicolumnrow` statement are not included in the source code on the same line. On the following lines, `\mcolrowcell` must be used for each cell of each column and each row to be skipped. An error is generated if this is missed.

```
... &  \multicolumnrow{2}{c}[c]{3}[0]{1in}[0pt]{Text}  & ...
... &  \mcolrowcell          &          \mcolrowcell   & ...
... &  \mcolrowcell          &          \mcolrowcell   & ...
```

⚠ MathJax

- MathJax does not support multirow, so it is emulated to only print its text on the first row. `\multirow` works as expected in text `tabulars` or SVG math.

In a lateximage, the print versions are restored.

See section 75.25 for the print-mode versions.

for HTML output: Remove the placeholder macro which was used if multirow was not loaded:

```
\LetLtxMacro\multirow\relax
\LWR@ProvidesPackagePass{multirow}[2021/01/29]
```

\LWR@multirowborder Set to left or right to create a thick border for the cell, for use by bigdelim:

```
\newcommand{\LWR@multirowborder}{}
```

§ 424.1 Multirow

\LWR@multirow@par \par inside a \multirow.

```
\newcommand*{\LWR@multirow@par}{\LWR@htmltag{br /}\LWR@origpar}%
```

\multirow [⟨*vpos*⟩] {⟨*numrows*⟩} [⟨*bigstruts*⟩] {⟨*width*⟩} [⟨*fixup*⟩] {⟨*text*⟩}

```
\NewDocumentCommand{\LWR@HTML@multirow}{O{c} m o m o +m}%
{%
\LWR@traceinfo{*** LWR@HTML@multirow #1 #2 #4}%
\booltrue{LWR@usedmultirow}%
\LWR@maybenewtablerow%
\LWR@tabularleftedge%
```

Print the start of a new table data cell:

```
\LWR@htmltag{td rowspan=\textquotedbl#2\textquotedbl\ %
```

A class adds the column spec and the rule:

```
class=\textquotedbl{}td%
```

Append this column's spec:

```
\LWR@getexparray{LWR@tablecolspec}{\arabic{LWR@tableLaTeXcolindex}}%
```

If this column has a cmidrule, add "rule" to the end of the HTML class tag. Also add the vertical bar class.

```
\LWR@addcmidruletrim%
\LWR@addleftmostbartag%
\LWR@printbartag{\arabic{LWR@tableLaTeXcolindex}}%
\textquotedbl%
\LWR@tdstartstyles%
```

The vertical alignment, if given:

```
\ifstrequal{#1}{c}{\LWR@tdaddstyle\LWR@print@mbox{vertical-align:middle}}{}%
\ifstrequal{#1}{b}{\LWR@tdaddstyle\LWR@print@mbox{vertical-align:bottom}}{}%
\ifstrequal{#1}{t}{\LWR@tdaddstyle\LWR@print@mbox{vertical-align:top}}{}%
```

The left/right border, if given:

```
\ifdefvoid{\LWR@multirowborder}{}{%
    \LWR@tdaddstyle%
    \LWR@print@mbox{border-\LWR@multirowborder:} 2px dotted black ; %
    \LWR@print@mbox{padding-\LWR@multirowborder:} 2px%
}%
```

Additional style elements:

```
\LWR@addcmidrulewidth%
\LWR@addcdashline%
\LWR@addtabularrulecolors%
\LWR@tdendstyles%
}%
```

The column's < spec:

```
\LWR@getexparray{LWR@colbeforespec}{\arabic{LWR@tableLaTeXcolindex}}%
```

While printing the text, redefine \\ to generate a new line. If a nested `tabular` occurs, \\ is redefined to `\LWR@tabularendofline` at the start of the `tabular`, then `\LWR@endofline` before again printing any `\multirow` contents inside the nested `tabular`.

\par is redefined to insert an HTML break, and if `tabular` is nested, it is redefined at the start of `tabular`.

```
\begingroup%
    \LetLtxMacro{\\}{\LWR@endofline}%
    \let\par\LWR@multirow@par%
    #6%
\endgroup%
\LWR@stoppars%
\boolfalse{LWR@intabularmetadata}%
\renewcommand{\LWR@multirowborder}{}%
\LWR@traceinfo{*** LWR@HTML@multirow done}%
}%

\LWR@formatted{multirow}
```

§ 424.2 Combined multicolumn and multirow

\multicolumnrow {⟨*1:cols*⟩} {⟨*2:halign*⟩} [⟨*3:vpos*⟩] {⟨*4:numrows*⟩} [⟨*5:bigstruts*⟩] {⟨*6:width*⟩} [⟨*7:fixup*⟩] {⟨*8:text*⟩}

\@ifpackageloaded{multirow} determines if v2.0 or later of multirow was used, which included the \ProvidesPackage macro.

The HTML version follows.

\AtBeginDocument because the print version had to see if multirow was loaded before determining how to define \LWR@print@multicolumnrow.

```
\AtBeginDocument{

\NewExpandableDocumentCommand{\LWR@HTML@multicolumnrow}{m m O{} m O{} m O{} +m}{%

\booltrue{LWR@usedmultirow}%
```

Figure out how many extra HTML columns to add for @ and ! columns:

```
\LWR@tabularhtmlcolumns{\arabic{LWR@tableLaTeXcolindex}}{#1}
```

Create the multicolumn/multirow tag, temporarily redefining the end of line. (Using a group caused problems with a nested tabular.

```
\LetLtxMacro{\\}{\LWR@endofline}%
\LWR@domulticolumn[#3][#4]{#1}{\arabic{LWR@tabhtmlcoltotal}}{#2}{#8}%
\LetLtxMacro{\\}{\LWR@tabularendofline}%
```

Move to the next LaTeX column:

```
\defaddtocounter{LWR@tableLaTeXcolindex}{#1}%
\defaddtocounter{LWR@tableLaTeXcolindex}{-1}%
```

Skip any trailing @ or ! columns for this cell:

```
\booltrue{LWR@skipatbang}%
}

\LWR@expandableformatted{multicolumnrow}

}% \AtBeginDocument
```

For MathJax. Only the text is used. All other parameters are ignored.

```
\begin{warpMathJax}
% \multirow[vpos]{num}[bigstruts]{width}[vmove]{text}
\CustomizeMathJax{\newcommand{\LWRsubmultirow}[2][]{#2}}
\CustomizeMathJax{\newcommand{\LWRmultirow}[2][]{\LWRsubmultirow}}
\CustomizeMathJax{\newcommand{\multirow}[2][]{\LWRmultirow}}
%
\CustomizeMathJax{\newcommand{\mrowcell}{}}
\CustomizeMathJax{\newcommand{\mcolrowcell}{}}
```

```
\CustomizeMathJax{\newcommand{\STneed}[1]{}}
\end{warpMathJax}
```

File 317 **lwarp-multitoc.sty**

§ 425 Package

multitoc

Pkg multitoc multitoc is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{multitoc}[1999/06/08]

\newcommand{\multicolumntoc}{2}
\newcommand{\multicolumnlot}{2}
\newcommand{\multicolumnlof}{2}
\newcommand*{\immediateaddtocontents}[2]{}
```

File 318 **lwarp-musicography.sty**

§ 426 Package

musicography

(*Emulates or patches code by* Andrew A. Cashner.)

Pkg musicography musicography is patched for use by lwarp.

Images are used for the meter symbols and fingered bass, since the HTML fonts tend not to be the correct size and HTML cannot stack items. The HTML `alt` tag copies `C` and `3/2`, etc. Hashes are used for the meter images, which are then reused as necessary.

⚠ Note that browser support for musical symbols may be buggy. ALT text and copy/paste into a text editor work well.

for HTML output:

```
\LWR@ProvidesPackagePass{musicography}[2019/05/28]

\NewDocumentCommand{\LWR@HTML@musSymbol}{ O{\musFont} m m m m }{%
\begin{lateximage}%
{#1\kern#2\raisebox{#3}{#5}\kern#4}%
\end{lateximage}%
}

\LWR@formatted{musSymbol}

\NewDocumentCommand{\LWR@HTML@musStemmedNote}{ m }{%
\begin{lateximage}%
\musSymbol{0.05em}{0.5ex}{0.2em}{#1\musStem}%
\end{lateximage}%
}

\LWR@formatted{musStemmedNote}

\NewDocumentCommand{\LWR@HTML@musFlaggedNote}{ m m }{%
```

```
\begin{lateximage}%
\musSymbol{0.05em}{0.5ex}{0pt}{#1\musStem}%
\musSymbol{0pt}{0pt}{0.9em}{#2}%
\end{lateximage}%
}

\LWR@formatted{musFlaggedNote}

\NewDocumentCommand{\LWR@HTML@musDottedNote}{ m }{%
\begin{lateximage}%
#1\musDot%
\end{lateximage}%
}

\LWR@formatted{musDottedNote}

\NewDocumentCommand{\LWR@HTML@musMeter}{ m m }{%
\begin{lateximage}*[#1/#2][#1#2]*%
\musStack{#1 #2}\kern0.05em%
\end{lateximage}%
}

\LWR@formatted{musMeter}

\NewDocumentCommand{\LWR@HTML@meterCplus}{ m }{%
\begin{lateximage}*[C#1]*%
    \meterC{}\kern-0.7pt#1%
\end{lateximage}%
}

\LWR@formatted{meterCplus}

\NewDocumentCommand{\LWR@HTML@meterC}{}{%
\begin{lateximage}*[C]*%
\musSymbolMeter{\symbol{83}}%
\end{lateximage}%
}

\LWR@formatted{meterC}

\NewDocumentCommand{\LWR@HTML@meterCutC}{}{%
\begin{lateximage}*[C|]*%
\musSymbolMeter{\symbol{82}}%
\end{lateximage}%
}

\LWR@formatted{meterCutC}

\NewDocumentCommand{\LWR@HTML@meterCThreeTwo}{}{%
\begin{lateximage}*[C3/2]*%
\meterCplus{\musStack{3 2}}%
\end{lateximage}%
}

\LWR@formatted{meterCThreeTwo}
```

```
\NewDocumentCommand{\LWR@HTML@meterO}{}{\HTMLunicode{25EF}}

\LWR@formatted{meterO}

\newcommand{\LWR@null@noFig}[1][]{}%

\NewDocumentCommand{\LWR@HTML@musFig}{ m }{%
\begin{lateximage}*[%
    {% ALT text for copy/paste
        \LetLtxMacro\noFig\LWR@null@noFig%
        \LetLtxMacro\musSharp\LWR@HTML@musSharp%
        \LetLtxMacro\musDoubleSharp\LWR@HTML@musDoubleSharp%
        \LetLtxMacro\musFlat\LWR@HTML@musFlat%
        \LetLtxMacro\musDoubleFlat\LWR@HTML@musDoubleFlat%
        \LetLtxMacro\musNatural\LWR@HTML@musNatural%
        {#1}% braces here because \noFig uses []
    }%
]*%
    \musStack[\musFigFont]{#1}%
\end{lateximage}%
}

\LWR@formatted{musFig}

\NewDocumentCommand{\LWR@HTML@musFlat}       {}{\HTMLunicode{266D}}
\NewDocumentCommand{\LWR@HTML@musDoubleFlat} {}{\HTMLunicode{1D12B}}
\NewDocumentCommand{\LWR@HTML@musSharp}      {}{\HTMLunicode{266F}}
\NewDocumentCommand{\LWR@HTML@musDoubleSharp}{}{\HTMLunicode{1D12A}}
\NewDocumentCommand{\LWR@HTML@musNatural}    {}{\HTMLunicode{266E}}

\LWR@formatted{musFlat}
\LWR@formatted{musDoubleFlat}
\LWR@formatted{musSharp}
\LWR@formatted{musDoubleSharp}
\LWR@formatted{musNatural}

\NewDocumentCommand{\LWR@HTML@musWhole}         {}{\HTMLunicode{1D15D}}
\NewDocumentCommand{\LWR@HTML@musHalf}          {}{\HTMLunicode{1D15E}}
\NewDocumentCommand{\LWR@HTML@musQuarter}       {}{\HTMLunicode{1D15F}}
\NewDocumentCommand{\LWR@HTML@musEighth}        {}{\HTMLunicode{1D160}}
\NewDocumentCommand{\LWR@HTML@musSixteenth}     {}{\HTMLunicode{1D161}}
\NewDocumentCommand{\LWR@HTML@musThirtySecond}  {}{\HTMLunicode{1D162}}
\NewDocumentCommand{\LWR@HTML@musSixtyFourth}   {}{\HTMLunicode{1D163}}

\LWR@formatted{musWhole}
\LWR@formatted{musHalf}
\LWR@formatted{musQuarter}
\LWR@formatted{musEighth}
\LWR@formatted{musSixteenth}
\LWR@formatted{musThirtySecond}
\LWR@formatted{musSixtyFourth}

\NewDocumentCommand{\LWR@HTML@musWholeDotted}{}
    {\HTMLunicode{1D15D}\HTMLunicode{1D16D}}
```

```
\NewDocumentCommand{\LWR@HTML@musHalfDotted}{}
    {\HTMLunicode{1D15E}\HTMLunicode{1D16D}}
\NewDocumentCommand{\LWR@HTML@musQuarterDotted}{}
    {\HTMLunicode{1D15F}\HTMLunicode{1D16D}}
\NewDocumentCommand{\LWR@HTML@musEighthDotted}{}
    {\HTMLunicode{1D160}\HTMLunicode{1D16D}}
\NewDocumentCommand{\LWR@HTML@musSixteenthDotted}{}
    {\HTMLunicode{1D161}\HTMLunicode{1D16D}}
\NewDocumentCommand{\LWR@HTML@musThirtySecondDotted}{}
    {\HTMLunicode{1D162}\HTMLunicode{1D16D}}
\NewDocumentCommand{\LWR@HTML@musSixtyFourthDotted}{}
    {\HTMLunicode{1D163}\HTMLunicode{1D16D}}

\LWR@formatted{musWholeDotted}
\LWR@formatted{musHalfDotted}
\LWR@formatted{musQuarterDotted}
\LWR@formatted{musEighthDotted}
\LWR@formatted{musSixteenthDotted}
\LWR@formatted{musThirtySecondDotted}
\LWR@formatted{musSixtyFourthDotted}
```

File 319 **lwarp-nameauth.sty**

§ 427 Package

nameauth

(*Emulates or patches code by* Charles P. Schaum.)

Pkg nameauth nameauth is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{nameauth}[2017/03/22]
```

lwarp formatting is inserted in the following.

```
\renewcommand*\@nameauth@Hook[1]
{%
  \if@nameauth@Lock
    \@nameauth@InHooktrue%
    \protected@edef\test{#1}%
    \expandafter\@nameauth@TestDot\expandafter{\test}%
    \if@nameauth@InAKA
      \if@nameauth@AlwaysFormat
        \@nameauth@FirstFormattrue%
      \else
        \unless\if@nameauth@AKAFormat
        \@nameauth@FirstFormatfalse\fi
      \fi
      \if@nameauth@MainFormat
        \if@nameauth@FirstFormat
          \bgroup\NamesFormat{%
            \LWR@textcurrentcolor{\LWR@textcurrentfont{#1}}%    lwarp
          }\egroup%
        \else
          \bgroup\MainNameHook{%
```

```
            \LWR@textcurrentcolor{\LWR@textcurrentfont{#1}}%    lwarp
          }\egroup%
        \fi
      \else
        \if@nameauth@FirstFormat
          \bgroup\FrontNamesFormat{%
            \LWR@textcurrentcolor{\LWR@textcurrentfont{#1}}%    lwarp
          }\egroup%
        \else
          \bgroup\FrontNameHook{%
            \LWR@textcurrentcolor{\LWR@textcurrentfont{#1}}%    lwarp
          }\egroup%
        \fi
      \fi
    \else
      \if@nameauth@AlwaysFormat
        \@nameauth@FirstFormattrue%
      \fi
      \if@nameauth@MainFormat
        \if@nameauth@FirstFormat
          \bgroup\NamesFormat{%
            \LWR@textcurrentcolor{\LWR@textcurrentfont{#1}}%    lwarp
          }\egroup%
        \else
          \bgroup\MainNameHook{%
            \LWR@textcurrentcolor{\LWR@textcurrentfont{#1}}%    lwarp
          }\egroup%
        \fi
      \else
        \if@nameauth@FirstFormat
          \bgroup\FrontNamesFormat{%
            \LWR@textcurrentcolor{\LWR@textcurrentfont{#1}}%    lwarp
          }\egroup%
        \else
          \bgroup\FrontNameHook{%
            \LWR@textcurrentcolor{\LWR@textcurrentfont{#1}}%    lwarp
          }\egroup%
        \fi
      \fi
    \fi
    \@nameauth@FirstFormatfalse%
    \@nameauth@InHookfalse%
  \fi
}
```

File 320 **lwarp-nameref.sty**

§ 428 Package

nameref

Pkg nameref nameref is emulated by lwarp.

for HTML output: Discard all options for lwarp-nameref:

```
\PackageInfo{lwarp}{%
Using the lwarp HTML version of package ‘nameref’,\MessageBreak
and discarding options.\MessageBreak
(Not using \protect\ProvidesPackage, so that other packages\MessageBreak
do not attempt to patch lwarp’s version of ‘nameref’.)\MessageBreak
}
\DeclareOption*{}
\ProcessOptions\relax
```

File 321 **lwarp-natbib.sty**

§ 429 Package

natbib

(*Emulates or patches code by* Patrick W. Daly.)

Pkg natbib natbib is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{natbib}[2010/09/13]
```

Replace math < and > with `\textless` and `\textgreater`:

A macro to compare:

```
\newcommand{\LWRNB@NAT@open}{$<$}
```

To patch `\NAT@open` and `\NAT@close`

```
\newcommand{\LWRNB@patchnatbibopenclose}{
\ifdefstrequal{\NAT@open}{\LWRNB@NAT@open}
{
    \renewcommand{\NAT@open}{\textless}
    \renewcommand{\NAT@close}{\textgreater}
}{}
}
```

Do it now in case `angle` was selected as an option:

```
\LWRNB@patchnatbibopenclose
```

Also patch `\setcitestyle` to patch after settings are made:

```
\let\LWRNB@origsetcitestyle\setcitestyle

\renewcommand{\setcitestyle}[1]{%
\LWRNB@origsetcitestyle{#1}%
\LWRNB@patchnatbibopenclose%
}
```

Syncronize the autopage labels:

```
\xpretocmd{\NAT@reset@parser}
    {\LWR@newautopagelabel{page}}%
```

```
    {}
    {\LWR@patcherror{natbib}{NAT@reset@parser}}
```

File 322 **lwarp-nccfancyhdr.sty**

§ 430 Package

nccfancyhdr

(*Emulates or patches code by* Alexander I. Rozhenko.)

Pkg nccfancyhdr nccfancyhdr is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{nccfancyhdr}[2004/12/07]

\newcommand*{\headrulewidth}{}
\newcommand*{\footrulewidth}{}
\newcommand{\headstrutheight}{}
\newcommand{\footstrutheight}{}
\newcommand*{\headrule}{}
\newcommand*{\footrule}{}

\newdimen\headwidth
\newcommand*{\extendedheaders}{}
\newcommand*{\normalheaders}{}

\newcommand*{\fancyhead}[2][]{}
\newcommand*{\fancyfoot}[2][]{}
\newcommand*{\fancyhf}[2][]{}
\newcommand*{\fancypagestyle}[2]{}
\newcommand*{\lhead}[2][]{}
\newcommand*{\chead}[2][]{}
\newcommand*{\rhead}[2][]{}
\newcommand*{\lfoot}[2][]{}
\newcommand*{\cfoot}[2][]{}
\newcommand*{\rfoot}[2][]{}

\newcommand{\nouppercase}[1]{#1}

\NewDocumentCommand{\fancycenter}{o o m m m}{}

\NewDocumentCommand{\newpagestyle}{m o m}{}

\newcommand*{\iffloatpage}[2]{#2}
\newcommand*{\ifftopfloat}[2]{#2}
\newcommand*{\iffbotfloat}[2]{#2}
```

File 323 **lwarp-nccfoots.sty**

§ 431 Package

nccfoots

(*Emulates or patches code by* Alexander I. Rozhenko.)

Pkg nccfoots nccfoots is used as-is, and emulated for MathJax.

for HTML output:

```
\LWR@ProvidesPackagePass{nccfoots}[2005/02/03]
```

⚠ For MathJax. There is no way to test for an empty argument, so the mark is not automatically duplicated.

```
\begin{warpMathJax}
\CustomizeMathJax{\newcommand{\Footnotemark}[1]{{}^{\mathrm{#1}}}}
\CustomizeMathJax{\newcommand{\Footnote}[2]{\Footnotemark{#1}}}
\end{warpMathJax}
```

File 324 **lwarp-nccmath.sty**

§ 432 Package nccmath

(*Emulates or patches code by* Alexander I. Rozhenko.)

Pkg nccmath nccmath is patched for use by lwarp, and emulated for MathJax.

for HTML output:

```
\LWR@ProvidesPackagePass{nccmath}[2006/01/20]

\let\LWR@origeqnarray\eqnarray
\let\LWR@origendeqnarray\endeqnarray

\csletcs{LWR@origeqnarraystar}{eqnarray*}
\csletcs{LWR@origendeqnarraystar}{endeqnarray*}

\RenewEnviron{eqnarray}
{%

    \LWR@eqnarrayfactor

}

\RenewEnviron{eqnarray*}
{%

    \begingroup
    \csletcs{LWR@origeqnarray}{LWR@origeqnarraystar}
    \csletcs{LWR@origendeqnarray}{LWR@origendeqnarraystar}
    \boolfalse{LWR@numbereqnarray}
    \LWR@eqnarrayfactor
    \endgroup

}

\def\eqs{%
    \@ifstar\LWR@nccmath@eqsstar\LWR@nccmath@eqs%
}
\newcommand*{\LWR@nccmath@eqsstar}[2][]{\begin{eqnarray*}#2\end{eqnarray*}}
\newcommand*{\LWR@nccmath@eqs}[2][]{\begin{eqnarray}#2\end{eqnarray}}

```

```
\begin{warpMathJax}

\CustomizeMathJax{\renewcommand{\intertext}[2][]{\text{#2}\notag \\}}
\CustomizeMathJax{\newenvironment{fleqn}[1][]{}{}}
\CustomizeMathJax{\newenvironment{ceqn}{}{}}
\CustomizeMathJax{\newenvironment{darray}[2][c]{\begin{array}[#1]{#2}}{\end{array}}}
\CustomizeMathJax{\newcommand{\dmulticolumn}[3]{#3}}
```

As of v0.86, MathJax v3 does not offer *, so the unstarred version is used here.

```
\CustomizeMathJax{\newcommand{\LWRnrnostar}[1][0.5ex]{\\[#1]}}
\CustomizeMathJax{\newcommand{\nr}{\ifstar\LWRnrnostar\LWRnrnostar}}

\CustomizeMathJax{\newcommand{\mrel}[1]{\begin{aligned}#1\end{aligned}}}
\CustomizeMathJax{\newcommand{\underrel}[2]{\underset{#2}{#1}}}
\CustomizeMathJax{\newcommand{\medmath}[1]{#1}}
\CustomizeMathJax{\newcommand{\medop}[1]{#1}}
\CustomizeMathJax{\newcommand{\medint}[1]{#1}}
\CustomizeMathJax{\newcommand{\medintcorr}[1]{#1}}
\CustomizeMathJax{\newcommand{\mfrac}[2]{\frac{#1}{#2}}}
\CustomizeMathJax{\newcommand{\mbinom}[2]{\binom{#1}{#2}}}
\CustomizeMathJax{\newenvironment{mmatrix}{\begin{matrix}}{\end{matrix}}}

\CustomizeMathJax{\newcommand{\displaybreak}[1][]{}}
```

\eq, \eqs, \eqalign are created by LaTeX, not MathJax.

```
\end{warpMathJax}
```

File 325 **lwarp-needspace.sty**

§ 433 Package needspace

(*Emulates or patches code by* Peter Wilson.)

Pkg needspace needspace is ignored.

for HTML output: Discard all options for lwarp-needspace:

```
\LWR@ProvidesPackageDrop{needspace}[2010/09/12]

\DeclareDocumentCommand{\needspace}{m}{}
\DeclareDocumentCommand{\Needspace}{s m}{}
```

File 326 **lwarp-newpxmath.sty**

§ 434 Package newpxmath

(*Emulates or patches code by* Michael Sharpe.)

Pkg newpxmath newpxmath is used as-is for SVG math, and is emulated for MathJax.

⚠ limitations The MathJax emulation ignores all package options, except `slantedGreek` is honored. The dedicated macros for upright and italic Greek do work correctly.

SVG math should appear the same as the printed output.

for HTML output: The MathJax code from newtxmath is used:

```
\LWR@ProvidesPackagePass{newpxmath}[2020/01/09]

\LWR@infoprocessingmathjax{newpxmath}

\LWR@origRequirePackage{lwarp-common-mathjax-newpxtxmath}

\LWR@origRequirePackage{lwarp-common-mathjax-letters}

\begin{warpMathJax}

%   * \marg{2: prefix} \marg{3: postfix} \marg{4: i/u: italic/upright}
\LWR@mathjax@addgreek@u@up*{}{up}
\LWR@mathjax@addgreek@u@up*{up}{}
\LWR@mathjax@addgreek@l@up{up}{}
\LWR@mathjax@addgreek@l@up{}{up}
\LWR@mathjax@addgreek@u@it*{}{it}
\LWR@mathjax@addgreek@l@it{}{it}
```

Optional slanted Greek:

```
\ifpx@slantedG
    \LWR@mathjax@addgreek@u@it*{}{}
\fi

\end{warpMathJax}
```

File 327 **lwarp-newtxmath.sty**

§ 435 Package

newtxmath

(*Emulates or patches code by* Michael Sharpe.)

Pkg newtxmath newtxmath is used as-is for SVG math, and is emulated for MathJax.

⚠ limitations The MathJax emulation ignores all package options, except `slantedGreek` is honored, and except that bold italic Latin letters are not defined for MathJax if the option is not selected.

The dedicated macros for upright and italic Greek and bold italic Latin letters do work correctly.

SVG math should appear the same as the printed output.

for HTML output:

```
\LWR@ProvidesPackagePass{newtxmath}[2020/08/04]

```

```
\LWR@infoprocessingmathjax{newtxmath}

\LWR@origRequirePackage{lwarp-common-mathjax-newpxtxmath}

\LWR@origRequirePackage{lwarp-common-mathjax-letters}

\begin{warpMathJax}

%   * \marg{2: prefix} \marg{3: postfix} \marg{4: i/u: italic/upright}
\LWR@mathjax@addgreek@u@up*{}{up}
\LWR@mathjax@addgreek@u@up*{up}{}
\LWR@mathjax@addgreek@l@up{up}{}
\LWR@mathjax@addgreek@l@up{}{up}
\LWR@mathjax@addgreek@u@it*{}{it}
\LWR@mathjax@addgreek@l@it{}{it}

% only newtxmath, not newpxmath:
\LWR@mathjax@addgreek@u@it*{it}{}
\LWR@mathjax@addgreek@l@it{it}{}

% only newtxmath, not newpxmath:
\ifdef{\iftx@BI}{
    \iftx@BI
        \LWR@mathjax@addlatin@u@bfit{BI}
        \LWR@mathjax@addlatin@l@bfit{BI}
    \fi
}{}
```

Optional slanted Greek:

```
\iftx@slantedG
    \LWR@mathjax@addgreek@u@it*{}{}
\fi

\end{warpMathJax}
```

File 328 **lwarp-newtxsf.sty**

§ 436 Package

newtxsf

(*Emulates or patches code by* Michael Sharpe.)

Pkg newtxsf newtxsf is used as-is for svg math, and is emulated for MathJax.

⚠ limitations The MathJax emulation ignores all package options, except `slantedGreek` is honored. The dedicated macros for upright and italic Greek and bold italic Latin letters do work correctly.

svg math should appear the same as the printed output.

for HTML output:

```
\LWR@ProvidesPackagePass{newtxsf}[2020/05/02]

\LWR@infoprocessingmathjax{newtxsf}
```

```
\LWR@origRequirePackage{lwarp-common-mathjax-newpxtxmath}

\LWR@origRequirePackage{lwarp-common-mathjax-letters}

\begin{warpMathJax}

%   * \marg{2: prefix} \marg{3: postfix} \marg{4: i/u: italic/upright}
\LWR@mathjax@addgreek@u@up*{}{up}
\LWR@mathjax@addgreek@u@up*{up}{}
\LWR@mathjax@addgreek@l@up{up}{}
\LWR@mathjax@addgreek@l@up{}{up}
\LWR@mathjax@addgreek@u@it*{}{it}
\LWR@mathjax@addgreek@l@it{}{it}

% only newtxmath, not newpxmath:
\LWR@mathjax@addgreek@u@it*{it}{}
\LWR@mathjax@addgreek@l@it{it}{}
%
% only newtxmath, not newpxmath:
\ifdef{\iftx@BI}{
    \iftx@BI
        \LWR@mathjax@addlatin@u@bfit{BI}
        \LWR@mathjax@addlatin@l@bfit{BI}
    \fi
}{}
```

Optional slanted Greek:

```
\iftx@slantedG
    \LWR@mathjax@addgreek@u@it*{}{}
\fi

\end{warpMathJax}
```

File 329 **lwarp-nextpage.sty**

§ 437 Package

nextpage

(*Emulates or patches code by* Peter Wilson.)

Pkg nextpage nextpage is ignored.

for HTML output: Discard all options for lwarp-nextpage.

```
\LWR@ProvidesPackageDrop{nextpage}[2009/09/03]

\DeclareDocumentCommand{\cleartoevenpage}{o}{}
\DeclareDocumentCommand{\movetoevenpage}{o}{}
\DeclareDocumentCommand{\cleartooddpage}{o}{}
\DeclareDocumentCommand{\movetooddpage}{o}{}
```

File 330 **lwarp-nfssext-cfr.sty**

§ 438 Package

nfssext-cfr

(*Emulates or patches code by* Clea F. Rees.)

Pkg nfssext-cfr nfssext-cfr is emulated in HTML, and used as-is in print output.

Results depend on the browser's font.

for HTML output:

```
\LWR@ProvidesPackagePass{nfssext-cfr}[2017/03/28]
```

Macros which are present in the lwarp core are commented out here.

```
\newrobustcmd{\LWR@HTML@lnstyle}{}
\newrobustcmd{\LWR@HTML@osstyle}{\LWR@HTML@scshape}
\newrobustcmd{\LWR@HTML@instyle}{}
\newrobustcmd{\LWR@HTML@sustyle}{}
\newrobustcmd{\LWR@HTML@swstyle}{}
\newrobustcmd{\LWR@HTML@pstyle}{}
\newrobustcmd{\LWR@HTML@tistyle}{}
\newrobustcmd{\LWR@HTML@ostyle}{\LWR@HTML@scshape}
\newrobustcmd{\LWR@HTML@postyle}{\LWR@HTML@scshape}
\newrobustcmd{\LWR@HTML@ltstyle}{}
\newrobustcmd{\LWR@HTML@ofstyle}{}
\newrobustcmd{\LWR@HTML@altstyle}{}
\newrobustcmd{\LWR@HTML@regstyle}{}
\newrobustcmd{\LWR@HTML@embossstyle}{}
\newrobustcmd{\LWR@HTML@ornamentalstyle}{}
\newrobustcmd{\LWR@HTML@qtstyle}{}
\newrobustcmd{\LWR@HTML@shstyle}{}
\newrobustcmd{\LWR@HTML@swashstyle}{}
\newrobustcmd{\LWR@HTML@tmstyle}{\renewcommand*{\LWR@f@family}{tt}}
\newrobustcmd{\LWR@HTML@tvstyle}{\renewcommand*{\LWR@f@family}{tt}}
\newrobustcmd{\LWR@HTML@tstyle}{}
\newrobustcmd{\LWR@HTML@lstyle}{}
\newrobustcmd{\LWR@HTML@tlstyle}{}
\newrobustcmd{\LWR@HTML@plstyle}{}
\newrobustcmd{\LWR@HTML@tostyle}{\LWR@HTML@scshape}
% \newrobustcmd{\LWR@HTML@sishape}{}
\newrobustcmd{\LWR@HTML@olshape}{}
\newrobustcmd{\LWR@HTML@scolshape}{}
\newrobustcmd{\LWR@HTML@ushape}{}
\newrobustcmd{\LWR@HTML@scushape}{}
\newrobustcmd{\LWR@HTML@uishape}{\LWR@HTML@itshape}
\newrobustcmd{\LWR@HTML@rishape}{}
\newrobustcmd{\LWR@HTML@regwidth}{}
\newrobustcmd{\LWR@HTML@nwwidth}{}
\newrobustcmd{\LWR@HTML@cdwidth}{}
\newrobustcmd{\LWR@HTML@ecwidth}{}
\newrobustcmd{\LWR@HTML@ucwidth}{}
\newrobustcmd{\LWR@HTML@etwidth}{}
```

```
\newrobustcmd{\LWR@HTML@epwidth}{}
\newrobustcmd{\LWR@HTML@exwidth}{}
\newrobustcmd{\LWR@HTML@uxwidth}{}
\newrobustcmd{\LWR@HTML@mbweight}{\renewcommand*{\LWR@f@series}{md}}
\newrobustcmd{\LWR@HTML@dbweight}{\renewcommand*{\LWR@f@series}{db}}
\newrobustcmd{\LWR@HTML@sbweight}{\renewcommand*{\LWR@f@series}{sb}}
% \newrobustcmd{\LWR@HTML@ebweight}{\renewcommand*{\LWR@f@series}{eb}}
\newrobustcmd{\LWR@HTML@ubweight}{\renewcommand*{\LWR@f@series}{ub}}
% \newrobustcmd{\LWR@HTML@lgweight}{\renewcommand*{\LWR@f@series}{lg}}
\newrobustcmd{\LWR@HTML@elweight}{\renewcommand*{\LWR@f@series}{el}}
\newrobustcmd{\LWR@HTML@ulweight}{\renewcommand*{\LWR@f@series}{ul}}
% \newrobustcmd{\LWR@HTML@itshape}{}
% \newrobustcmd{\LWR@HTML@scshape}{}
% \newrobustcmd{\LWR@HTML@upshape}{}
\newrobustcmd{\LWR@HTML@dfshape}{}

\ifdef{\LWR@HTML@swshape}{}{% duplicated by fontaxes
    \newrobustcmd{\LWR@HTML@swshape}{}
}

\newrobustcmd{\LWR@HTML@ornament}[1]{}

\LWR@formatted{lnstyle}
\LWR@formatted{osstyle}
\LWR@formatted{instyle}
\LWR@formatted{sustyle}
\LWR@formatted{swstyle}
\LWR@formatted{pstyle}
\LWR@formatted{tistyle}
\LWR@formatted{ostyle}
\LWR@formatted{postyle}
\LWR@formatted{ltstyle}
\LWR@formatted{ofstyle}
\LWR@formatted{altstyle}
\LWR@formatted{regstyle}
\LWR@formatted{embossstyle}
\LWR@formatted{ornamentalstyle}
\LWR@formatted{qtstyle}
\LWR@formatted{shstyle}
\LWR@formatted{swashstyle}
\LWR@formatted{tmstyle}
\LWR@formatted{tvstyle}
\LWR@formatted{tstyle}
\LWR@formatted{lstyle}
\LWR@formatted{tlstyle}
\LWR@formatted{plstyle}
\LWR@formatted{tostyle}
% \LWR@formatted{sishape}
\LWR@formatted{olshape}
\LWR@formatted{scolshape}
\LWR@formatted{ushape}
\LWR@formatted{scushape}
\LWR@formatted{uishape}
\LWR@formatted{rishape}
\LWR@formatted{regwidth}
```

```
\LWR@formatted{nwwidth}
\LWR@formatted{cdwidth}
\LWR@formatted{ecwidth}
\LWR@formatted{ucwidth}
\LWR@formatted{etwidth}
\LWR@formatted{epwidth}
\LWR@formatted{exwidth}
\LWR@formatted{uxwidth}
\LWR@formatted{mbweight}
\LWR@formatted{dbweight}
\LWR@formatted{sbweight}
% \LWR@formatted{ebweight}
\LWR@formatted{ubweight}
% \LWR@formatted{lgweight}
\LWR@formatted{elweight}
\LWR@formatted{ulweight}
\LWR@formatted{itshape}% adapt to the new print version
\LWR@formatted{scshape}% adapt to the new print version
\LWR@formatted{upshape}% adapt to the new print version
\LWR@formatted{dfshape}

\ifdef{\LWR@HTML@swshape}{}{% duplicated by fontaxes
    \LWR@formatted{swshape}
}

\LWR@formatted{ornament}


\FilenameNullify{%
    \LetLtxMacro\lnstyle\@empty%
    \LetLtxMacro\osstyle\@empty%
    \LetLtxMacro\instyle\@empty%
    \LetLtxMacro\sustyle\@empty%
    \LetLtxMacro\swstyle\@empty%
    \LetLtxMacro\pstyle\@empty%
    \LetLtxMacro\tistyle\@empty%
    \LetLtxMacro\ostyle\@empty%
    \LetLtxMacro\postyle\@empty%
    \LetLtxMacro\ltstyle\@empty%
    \LetLtxMacro\ofstyle\@empty%
    \LetLtxMacro\altstyle\@empty%
    \LetLtxMacro\regstyle\@empty%
    \LetLtxMacro\embossstyle\@empty%
    \LetLtxMacro\ornamentalstyle\@empty%
    \LetLtxMacro\qtstyle\@empty%
    \LetLtxMacro\shstyle\@empty%
    \LetLtxMacro\swashstyle\@empty%
    \LetLtxMacro\tmstyle\@empty%
    \LetLtxMacro\tvstyle\@empty%
    \LetLtxMacro\tstyle\@empty%
    \LetLtxMacro\lstyle\@empty%
    \LetLtxMacro\tlstyle\@empty%
    \LetLtxMacro\plstyle\@empty%
    \LetLtxMacro\tostyle\@empty%
%   \LetLtxMacro\sishape\@empty%
    \LetLtxMacro\olshape\@empty%
```

```
    \LetLtxMacro\scolshape\@empty%
    \LetLtxMacro\ushape\@empty%
    \LetLtxMacro\scushape\@empty%
    \LetLtxMacro\uishape\@empty%
    \LetLtxMacro\rishape\@empty%
    \LetLtxMacro\regwidth\@empty%
    \LetLtxMacro\nwwidth\@empty%
    \LetLtxMacro\cdwidth\@empty%
    \LetLtxMacro\ecwidth\@empty%
    \LetLtxMacro\ucwidth\@empty%
    \LetLtxMacro\etwidth\@empty%
    \LetLtxMacro\epwidth\@empty%
    \LetLtxMacro\exwidth\@empty%
    \LetLtxMacro\uxwidth\@empty%
    \LetLtxMacro\mbweight\@empty%
    \LetLtxMacro\dbweight\@empty%
    \LetLtxMacro\sbweight\@empty%
%   \LetLtxMacro\ebweight\@empty%
    \LetLtxMacro\ubweight\@empty%
%   \LetLtxMacro\lgweight\@empty%
    \LetLtxMacro\elweight\@empty%
    \LetLtxMacro\ulweight\@empty%
%   \LetLtxMacro\itshape\@empty%
%   \LetLtxMacro\scshape\@empty%
%   \LetLtxMacro\upshape\@empty%
    \LetLtxMacro\dfshape\@empty%
    \LetLtxMacro\swshape\@empty%
    \LetLtxMacro\ornament\@gobble%
}

\newrobustcmd{\LWR@HTML@textln}[1]{\InlineClass{textln}{#1}}
\newrobustcmd{\LWR@HTML@textos}[1]{\textsc{#1}}
\newrobustcmd{\LWR@HTML@textin}[1]{#1}
\newrobustcmd{\LWR@HTML@textsu}[1]{#1}
% \newrobustcmd{\LWR@HTML@textsi}[1]{#1}
\newrobustcmd{\LWR@HTML@textdf}[1]{#1}


\ifdef{\LWR@HTML@textsw}{}{% duplicated by fontaxes
    \newrobustcmd{\LWR@HTML@textsw}[1]{#1}
    \LWR@formatted{textsw}
}

\newrobustcmd{\LWR@HTML@textti}[1]{#1}
\newrobustcmd{\LWR@HTML@textlt}[1]{#1}
\newrobustcmd{\LWR@HTML@textof}[1]{#1}
\newrobustcmd{\LWR@HTML@textalt}[1]{#1}
\newrobustcmd{\LWR@HTML@textreg}[1]{#1}
\newrobustcmd{\LWR@HTML@emboss}[1]{#1}
\newrobustcmd{\LWR@HTML@textorn}[1]{#1}
\newrobustcmd{\LWR@HTML@textqt}[1]{#1}
\newrobustcmd{\LWR@HTML@textsh}[1]{#1}
\newrobustcmd{\LWR@HTML@texttm}[1]{\texttt{#1}}
\newrobustcmd{\LWR@HTML@texttv}[1]{\texttt{#1}}
\newrobustcmd{\LWR@HTML@textl}[1]{\InlineClass{textln}{#1}}
\newrobustcmd{\LWR@HTML@texto}[1]{\textsc{#1}}
```

```
\newrobustcmd{\LWR@HTML@textp}[1]{\InlineClass{textp}{#1}}
\newrobustcmd{\LWR@HTML@textt}[1]{\InlineClass{textt}{#1}}
\newrobustcmd{\LWR@HTML@textpl}[1]{#1}
\newrobustcmd{\LWR@HTML@textpo}[1]{\textsc{#1}}
\newrobustcmd{\LWR@HTML@texttl}[1]{\InlineClass{textln}{#1}}
\newrobustcmd{\LWR@HTML@textto}[1]{\textsc{#1}}
\newrobustcmd{\LWR@HTML@textol}[1]{#1}
\newrobustcmd{\LWR@HTML@textswash}[1]{#1}
\newrobustcmd{\LWR@HTML@textu}[1]{#1}
\newrobustcmd{\LWR@HTML@textscu}[1]{#1}
\newrobustcmd{\LWR@HTML@textui}[1]{\LWR@HTML@textit{#1}}
\newrobustcmd{\LWR@HTML@textri}[1]{#1}
\newrobustcmd{\LWR@HTML@textnw}[1]{#1}
\newrobustcmd{\LWR@HTML@textcd}[1]{#1}
\newrobustcmd{\LWR@HTML@textec}[1]{#1}
\newrobustcmd{\LWR@HTML@textuc}[1]{#1}
\newrobustcmd{\LWR@HTML@textet}[1]{#1}
\newrobustcmd{\LWR@HTML@textep}[1]{#1}
\newrobustcmd{\LWR@HTML@textex}[1]{#1}
\newrobustcmd{\LWR@HTML@textux}[1]{#1}
\newrobustcmd{\LWR@HTML@textrw}[1]{#1}
\newrobustcmd{\LWR@HTML@textmb}[1]{{\LWR@HTML@mbweight\InlineClass{textmb}{#1}}}
\newrobustcmd{\LWR@HTML@textdb}[1]{{\LWR@HTML@dbweight\InlineClass{textdb}{#1}}}
\newrobustcmd{\LWR@HTML@textsb}[1]{{\LWR@HTML@sbweight\InlineClass{textsb}{#1}}}
% \newrobustcmd{\LWR@HTML@texteb}[1]}{#1}
\newrobustcmd{\LWR@HTML@textub}[1]{{\LWR@HTML@ubweight\InlineClass{textub}{#1}}}
% \newrobustcmd{\LWR@HTML@textlg}[1]}{#1}
\newrobustcmd{\LWR@HTML@textel}[1]{{\LWR@HTML@elweight\InlineClass{textel}{#1}}}
\newrobustcmd{\LWR@HTML@textul}[1]{{\LWR@HTML@ulweight\InlineClass{textul}{#1}}}

\LWR@formatted{textln}
\LWR@formatted{textos}
\LWR@formatted{textin}
\LWR@formatted{textsu}
% \LWR@formatted{textsi}
\LWR@formatted{textdf}
\LWR@formatted{textti}
\LWR@formatted{textlt}
\LWR@formatted{textof}
\LWR@formatted{textalt}
\LWR@formatted{textreg}
\LWR@formatted{emboss}
\LWR@formatted{textorn}
\LWR@formatted{textqt}
\LWR@formatted{textsh}
\LWR@formatted{texttm}
\LWR@formatted{texttv}
\LWR@formatted{textl}
\LWR@formatted{texto}
\LWR@formatted{textp}
\LWR@formatted{textt}
\LWR@formatted{textpl}
\LWR@formatted{textpo}
\LWR@formatted{texttl}
\LWR@formatted{textto}
```

```
\LWR@formatted{textol}
\LWR@formatted{textswash}
\LWR@formatted{textu}
\LWR@formatted{textscu}
\LWR@formatted{textui}
\LWR@formatted{textri}
\LWR@formatted{textnw}
\LWR@formatted{textcd}
\LWR@formatted{textec}
\LWR@formatted{textuc}
\LWR@formatted{textet}
\LWR@formatted{textep}
\LWR@formatted{textex}
\LWR@formatted{textux}
\LWR@formatted{textrw}
\LWR@formatted{textmb}
\LWR@formatted{textdb}
\LWR@formatted{textsb}
% \LWR@formatted{texteb}
\LWR@formatted{textub}
% \LWR@formatted{textlg}
\LWR@formatted{textel}
\LWR@formatted{textul}


\FilenameNullify{%
    \LetLtxMacro\textln\@firstofone%
    \LetLtxMacro\textos\@firstofone%
    \LetLtxMacro\textin\@firstofone%
    \LetLtxMacro\textsu\@firstofone%
%   \LetLtxMacro\textsi\@firstofone%
    \LetLtxMacro\textdf\@firstofone%
    \LetLtxMacro\textsw\@firstofone%
    \LetLtxMacro\textti\@firstofone%
    \LetLtxMacro\textlt\@firstofone%
    \LetLtxMacro\textof\@firstofone%
    \LetLtxMacro\textalt\@firstofone%
    \LetLtxMacro\textreg\@firstofone%
    \LetLtxMacro\emboss\@firstofone%
    \LetLtxMacro\textorn\@firstofone%
    \LetLtxMacro\textqt\@firstofone%
    \LetLtxMacro\textsh\@firstofone%
    \LetLtxMacro\texttm\@firstofone%
    \LetLtxMacro\texttv\@firstofone%
    \LetLtxMacro\textl\@firstofone%
    \LetLtxMacro\texto\@firstofone%
    \LetLtxMacro\textp\@firstofone%
    \LetLtxMacro\textt\@firstofone%
    \LetLtxMacro\textpl\@firstofone%
    \LetLtxMacro\textpo\@firstofone%
    \LetLtxMacro\texttl\@firstofone%
    \LetLtxMacro\textto\@firstofone%
    \LetLtxMacro\textol\@firstofone%
    \LetLtxMacro\textswash\@firstofone%
    \LetLtxMacro\textu\@firstofone%
```

```
    \LetLtxMacro\textscu\@firstofone%
    \LetLtxMacro\textui\@firstofone%
    \LetLtxMacro\textri\@firstofone%
    \LetLtxMacro\textnw\@firstofone%
    \LetLtxMacro\textcd\@firstofone%
    \LetLtxMacro\textec\@firstofone%
    \LetLtxMacro\textuc\@firstofone%
    \LetLtxMacro\textet\@firstofone%
    \LetLtxMacro\textep\@firstofone%
    \LetLtxMacro\textex\@firstofone%
    \LetLtxMacro\textux\@firstofone%
    \LetLtxMacro\textrw\@firstofone%
    \LetLtxMacro\textmb\@firstofone%
    \LetLtxMacro\textdb\@firstofone%
    \LetLtxMacro\textsb\@firstofone%
%   \LetLtxMacro\texteb\@firstofone%
    \LetLtxMacro\textub\@firstofone%
%   \LetLtxMacro\textlg\@firstofone%
    \LetLtxMacro\textel\@firstofone%
    \LetLtxMacro\textul\@firstofone%
}

\providecommand*{\zeroslash}{0}
\newrobustcmd*{\LWR@HTML@zeroslash}{0}
\LWR@formatted{zeroslash}
```

File 331 **lwarp-nicefrac.sty**

§ 439 Package nicefrac

(*Emulates or patches code by* Axel Reichert.)

Pkg nicefrac nicefrac is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{nicefrac}[1998/08/04]

\DeclareRobustCommand*{\LWR@HTML@@UnitsNiceFrac}[3][]{%
    {% localize font selection
        #1{%
            \LWR@textcurrentfont{%
                \InlineClass{numerator}{#2}%
                /%
                \InlineClass{denominator}{#3}%
            }%
        }%
    }%
}

\LWR@formatted{@UnitsNiceFrac}

\DeclareRobustCommand*{\LWR@HTML@@UnitsUglyFrac}[3][]{%
    {% localize font selection
        #1{\LWR@textcurrentfont{#2/#3}}%
```

```
    }%
}

\LWR@formatted{@UnitsUglyFrac}
```

For MathJax:

```
\begin{warpMathJax}
\CustomizeMathJax{\newcommand{\nicefrac}[3][]{\mathinner{{}^{#2}\!/\!_{#3}}}}
\end{warpMathJax}
```

File 332 **lwarp-niceframe.sty**

§ 440 Package niceframe

Pkg niceframe niceframe is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{niceframe}% the original date is in yyyy/dd/mm format


\newcommand{\LWR@niceframe}[3]{%
    \begin{LWR@setvirtualpage}*%
    \setlength{\LWR@templengthone}{#1}%
    \begin{BlockClass}[max-width:\LWR@printlength{\LWR@templengthone}]{#3}%
    #2
    \end{BlockClass}%
    \end{LWR@setvirtualpage}%
}

\newcommand{\niceframe}[2][\textwidth]{\LWR@niceframe{#1}{#2}{niceframe}}
\newcommand{\curlyframe}[2][\textwidth]{\LWR@niceframe{#1}{#2}{curlyframe}}
\newcommand{\artdecoframe}[2][\textwidth]{\LWR@niceframe{#1}{#2}{artdecoframe}}

\newcommand{\generalframe}[9]{\LWR@niceframe{\textwidth}{#9}{generalframe}}
```

File 333 **lwarp-nicematrix.sty**

§ 441 Package nicematrix

(*Emulates or patches code by* F. Pantigny.)

Pkg nicematrix nicematrix is used as-is for SVG math, and is emulated for MathJax.

⚠ MathJax Keys/values are ignored in MathJax. `\Cdots`, etc. do not span multiple cells. `AutoNiceMatrix`, etc. are not supported for MathJax. SVG math output preserves all nicematrix features. To force SVG output for one or more consecutive math expressions, for inline math use `\inlinemathother` and `\inlinemathnormal`, or for display math use `\displaymathother` and `\displaymathnormal`.

for HTML output:

```
\LWR@ProvidesPackagePass{nicematrix}[2020/11/23]
```

`NiceTabular` must be converted to SVG to support the various nicematrix options:

```
\begin{warpHTML}
\BeforeBeginEnvironment{NiceTabular}{%
    \begin{lateximage}[-nicematrix-~\PackageDiagramAltText]%
}
\AfterEndEnvironment{NiceTabular}{\end{lateximage}}
\BeforeBeginEnvironment{NiceTabular*}{%
    \begin{lateximage}[-nicematrix-~\PackageDiagramAltText]%
}
\AfterEndEnvironment{NiceTabular*}{\end{lateximage}}
\end{warpHTML}
```

Special handling for the optional arguments, and the lack of a delimiter:

```
\begin{warpMathJax}
\CustomizeMathJax{\newcommand{\LWRnicearrayarray}[1]{\begin{array}{#1}}}
\CustomizeMathJax{\def\LWRnicearrayarrayopt#1[#2] {\begin{array}{#1}}}

\CustomizeMathJax{%
    \newenvironment{NiceArray}[2][]%
        {\ifnextchar[{\LWRnicearrayarrayopt{#2}}{\LWRnicearrayarray{#2}}}%
        {\end{array}}%
}

\CustomizeMathJax{%
    \newcommand{\LWRnicearraywithdelimtwo}[2][]{%
        \ifnextchar[{\LWRnicearrayarrayopt{#2}}{\LWRnicearrayarray{#2}}%
    }%
}
```

General case with left/right delimiters:

```
\CustomizeMathJax{%
    \newenvironment{NiceArrayWithDelims}[2]%
        {%
            \def\LWRnicearrayrightdelim{\right#2}%
            \left#1%
            \LWRnicearraywithdelimtwo%
        }%
        {\end{array}\LWRnicearrayrightdelim}%
}
```

Instances of specific delimiters:

```
\CustomizeMathJax{%
    \newenvironment{pNiceArray}
        {\begin{NiceArrayWithDelims}{(}{)}}
        {\end{NiceArrayWithDelims}}
}

\CustomizeMathJax{%
    \newenvironment{bNiceArray}
        {\begin{NiceArrayWithDelims}{[}{]}}
        {\end{NiceArrayWithDelims}}
```

```
}

\CustomizeMathJax{%
    \newenvironment{BNiceArray}
        {\begin{NiceArrayWithDelims}{\{}{\}}}
        {\end{NiceArrayWithDelims}}
}

\CustomizeMathJax{%
    \newenvironment{vNiceArray}
        {\begin{NiceArrayWithDelims}{\vert}{\vert}}
        {\end{NiceArrayWithDelims}}
}

\CustomizeMathJax{%
    \newenvironment{VNiceArray}
        {\begin{NiceArrayWithDelims}{\Vert}{\Vert}}
        {\end{NiceArrayWithDelims}}
}
```

Ignore optional arg and use standard environments:

```
\CustomizeMathJax{\newenvironment{NiceMatrix}[1][]{\begin{matrix}}{\end{matrix}}}
\CustomizeMathJax{\newenvironment{pNiceMatrix}[1][]{\begin{pmatrix}}{\end{pmatrix}}}
\CustomizeMathJax{\newenvironment{bNiceMatrix}[1][]{\begin{bmatrix}}{\end{bmatrix}}}
\CustomizeMathJax{\newenvironment{BNiceMatrix}[1][]{\begin{Bmatrix}}{\end{Bmatrix}}}
\CustomizeMathJax{\newenvironment{vNiceMatrix}[1][]{\begin{vmatrix}}{\end{vmatrix}}}
\CustomizeMathJax{\newenvironment{VNiceMatrix}[1][]{\begin{Vmatrix}}{\end{Vmatrix}}}
```

Ignore optional argument and size. Print contents.

```
\CustomizeMathJax{\newcommand{\LWRnicematrixBlock}[1]{#1}}
\CustomizeMathJax{\def\LWRnicematrixBlockopt<#1>#2{#2}}

\CustomizeMathJax{%
   \newcommand{\Block}[2][]{\ifnextchar<\LWRnicematrixBlockopt\LWRnicematrixBlock}%
}
```

Form an approximation:

```
\CustomizeMathJax{%
    \newcommand{\diagbox}[2]{%
        \begin{array}{l}\hfill\quad#2\\\hline#1\quad\hfill\end{array}%
    }%
}
```

More approximations:

```
\CustomizeMathJax{\let\hdottedline\hdashline}

\CustomizeMathJax{\newcommand{\ldots}[1][]{\dots}}
\CustomizeMathJax{\newcommand{\Cdots}[1][]{\cdots}}
\CustomizeMathJax{\newcommand{\Vdots}[1][]{\vdots}}
\CustomizeMathJax{\newcommand{\Ddots}[1][]{\ddots}}
\CustomizeMathJax{\newcommand{\Iddots}[1][]{\mathinner{\unicode{x22F0}}}}
```

```
89
90 \CustomizeMathJax{\newcommand{\Hdotsfor}[1]{\ldots}}
91 \CustomizeMathJax{\newcommand{\Vdotsfor}[1]{\vdots}}
```

There is no way to emulate AutoNiceMatrix in MathJax.

```
92 \CustomizeMathJax{\newcommand{\AutoNiceMatrix}[2]{\text{(AutoNiceMatrix #1)}}}
93 \CustomizeMathJax{\let\pAutoNiceMatrix\AutoNiceMatrix}
94 \CustomizeMathJax{\let\bAutoNiceMatrix\AutoNiceMatrix}
95 \CustomizeMathJax{\let\BAutoNiceMatrix\AutoNiceMatrix}
96 \CustomizeMathJax{\let\vAutoNiceMatrix\AutoNiceMatrix}
97 \CustomizeMathJax{\let\VAutoNiceMatrix\AutoNiceMatrix}
98 \end{warpMathJax}
```

File 334 **lwarp-noitcrul.sty**

§ 442 Package noitcrul

(*Emulates or patches code by* Paul Ebermann.)

Pkg noitcrul noitcrul is used as-is for SVG and emulated for MathJax.

for HTML output:

```
1 \LWR@ProvidesPackagePass{noitcrul}[2006/04/11]
```

```
2 \begin{warpMathJax}
3 \CustomizeMathJax{\newcommand{\noitUnderline}[1]{\underline{#1}\!}}
4 \end{warpMathJax}
```

File 335 **lwarp-nolbreaks.sty**

§ 443 Package nolbreaks

(*Emulates or patches code by* Donald Arseneau.)

Pkg nolbreaks nolbreaks is emulated.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{nolbreaks}[2012/05/31]
```

```
2 \NewDocumentCommand{\nolbreaks}{s m}{\InlineClass{nolbreaks}{#2}}
```

File 336 **lwarp-nomencl.sty**

§ 444 Package nomencl

(*Emulates or patches code by* Boris Veytsman, Bernd Schandl, Lee Netherton, CV Radhakrishnan.)

Pkg nomencl nomencl is patched for use by lwarp.

To process the HTML nomenclature:

```
makeindex <project>_html.nlo -s nomencl.ist -o <project>_html.nls
```

for HTML output:

```
\LWR@ProvidesPackagePass{nomencl}[2005/09/22]
```

\BaseJobname is added to the label in case xr or xr-hyper are used.

```
\def\@@@nomenclature[#1]#2#3{%
 \def\@tempa{#2}\def\@tempb{#3}%
 \protected@write\@nomenclaturefile{}%
  {\string\nomenclatureentry{#1\nom@verb\@tempa @[{\nom@verb\@tempa}]%
      \begingroup\nom@verb\@tempb\protect\nomeqref{\theequation}%
        |nompageref}{\theLWR@previousautopagelabel}}%   lwarp
 \endgroup
 \@esphack}

\renewcommand*{\pagedeclaration}[1]{, \nameref{\BaseJobname-autopage-#1}}%
```

File 337 **lwarp-nonfloat.sty**

§ 445 Package nonfloat

(*Emulates or patches code by* Kai Rascher.)

Pkg nonfloat nonfloat is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{nonfloat}[1999/07/05]
```

```
\LetLtxMacro\topcaption\caption
\newcommand{\figcaption}{\def\@captype{figure}\caption}
\newcommand{\tabcaption}{\def\@captype{table}\topcaption}
\newenvironment{narrow}[2]{}{}
```

File 338 **lwarp-nonumonpart.sty**

§ 446 Package nonumonpart

Pkg nonumonpart nonumonpart is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{nonumonpart}[2011/04/15]
```

File 339 **lwarp-nopageno.sty**

§ 447 Package nopageno

Pkg nopageno nopageno is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{nopageno}[1989/01/01]
```

File 340 **lwarp-notes.sty**

§ 448 Package notes

Pkg notes notes is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{notes}[2002/10/29]

\newcommand*{\LWR@notes@onenote}[2]{%
\newenvironment{#1}
    {
        \BlockClass{notes#1}
        \begin{BlockClass}{notesicon}\textcircled{~#2~}\end{BlockClass}
        \BlockClass{notescontents}
    }
    {\endBlockClass\endBlockClass}
}

\LWR@notes@onenote{importantnote}{!}

\LWR@notes@onenote{warningnote}{--}

\LWR@notes@onenote{informationnote}{i}
```

File 341 **lwarp-notespages.sty**

§ 449 Package notespages

Pkg notespages notespages is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{notespages}[2016/08/21]

\newcommand*{\npnotesname}{}
\newcommand*{\npnotestext}{}
\newcommand*{\remainingtextheight}{}
\newdimen\remainingtextheight
\newcommand*{\notestitletext}{}
\newcommand*{\notesareatext}{}
\newcommand*{\npnpinfo}[1]{}
\newcommand*{\tracingnpmarks}{}
\newcommand*{\notespage}[1][]{}
\newcommand*{\notespages}[1][]{}
\newcommand*{\notesfill}[1][]{}
\newcommand*{\setnotespages}[1]{}
\newcommand*{\definenotesoption}[2]{}
\newcommand{\definenotesstyle}[2]{}
\newcommand{\definetitlestyle}[2]{}
\newcommand{\nppatchchapter}[1]{}
\newcommand{\npunpatchchapter}{}
```

File 342 **lwarp-nowidow.sty**

§ 450 Package nowidow

(*Emulates or patches code by* Raphaël Pinson.)

Pkg nowidow nowidow is ignored.

for HTML output: Disabling options for lwarp-nowidow.

```
\ProvidesPackage{lwarp-nowidow}[2011/09/20]
```

\nowidow [⟨*lines*⟩]

\setnowidow [⟨*lines*⟩]

```
\newcommand*{\nowidow}[1][]{}
\newcommand*{\setnowidow}[1][]{}
```

\noclub [⟨*lines*⟩]

\setnoclub [⟨*lines*⟩]

```
\newcommand*{\noclub}[1][]{}
\newcommand*{\setnoclub}[1][]{}
```

File 343 **lwarp-ntheorem.sty**

§ 451 Package ntheorem

(*Emulates or patches code by* Wolfgang May, Andreas Schedler.)

Pkg ntheorem ntheorem is patched for use by lwarp.

Table 19: Ntheorem package — css styling of theorems and proofs

Theorem: of class theorembody<theoremstyle>

Theorem Header: of class theoremheader<style>

where <theoremstyle> is plain, break, etc.

§ 451.1 Limitations

⚠ Font control

This conversion is not total. Font control is via CSS, and the custom LaTeX font settings are ignored.

⚠ Equation numbering

ntheorem has a bug with equation numbering in $\mathcal{AMS}$ environments when the option `thref` is used. lwarp does not share this bug, so equations with `\split`, etc, are numbered correctly with lwarp's HTML output, but not with the print output. It is recommended to use cleveref instead of ntheorem's `thref` option.

§ 451.2 Options

Options `amsthm` or `standard` choose which set of theorems and proofs to initialize.

⚠ Disabled options

The options `thmmarks` and `amsmath` are disabled, since they heavily modify the underlying math code. Theorem marks are emulated. The AMS-math modifications are not done.

Option `thref` is disabled because cleveref functions are used instead. `\thref` is emulated.

Option `hyperref` is disabled because lwarp emulated hyperref.

for HTML output:

Some disabled options:

```
\DeclareOption{thref}{
    \AtEndDocument{
        \PackageWarningNoLine{lwarp}{%
            Lwarp uses cleveref, which takes over ntheorem's\MessageBreak
            referencing, including
                \protect\label \space and \protect\thref.\MessageBreak
            Cleveref does not accept ntheorem's optional\MessageBreak
            argument for \protect\label, so it will appear\MessageBreak
            in the text.  It is recommended to remove the\MessageBreak
            thref option, \protect\usepackage{cleveref} instead,\MessageBreak
            and remove any trailing optional arguments for \protect\label%
        }%
    }
}


\newbool{LWR@ntheoremmarks}
\boolfalse{LWR@ntheoremmarks}

\DeclareOption{thmmarks}{
\booltrue{LWR@ntheoremmarks}
\newif\ifsetendmark\setendmarktrue
}


\newbool{LWR@ntheoremamsthm}
\boolfalse{LWR@ntheoremamsthm}

\DeclareOption{amsthm}{\booltrue{LWR@ntheoremamsthm}}


\DeclareOption{amsmath}{}
\DeclareOption{hyperref}{}
```

```
34
35 \LWR@ProvidesPackagePass{ntheorem}[2011/08/15]
```

§ 451.3 Remembering the theorem style

Storage for the style being used for new theorems.

```
36 \newcommand{\LWR@newtheoremstyle}{plain}

37 \AtBeginDocument{
38 \@ifpackageloaded{cleveref}{
39 \gdef\@thm#1#2#3{%
40   \if@thmmarks
41     \stepcounter{end\InTheoType ctr}%
42   \fi
43   \renewcommand{\InTheoType}{#1}%
44   \if@thmmarks
45     \stepcounter{curr#1ctr}%
46     \setcounter{end#1ctr}{0}%
47   \fi
48   \refstepcounter[#1]{#2}%  <<< cleveref modification
49   \theorem@prework
50    \LWR@forcenewpage% lwarp

51    \LWR@printpendingfootnotes%                   lwarp

52    \BlockClass{theorembody#1}%\LWR@thisthmstyle% lwarp
53   \trivlist % latex's \trivlist, calling latex's \@trivlist unchanged
54   \ifuse@newframeskips  % cf. latex.ltx for topsepadd: \@trivlist
55     \ifthm@inframe
56       \thm@topsep\theoreminframepreskipamount
57       \thm@topsepadd\theoreminframepostskipamount
58      \else
59       \thm@topsep\theorempreskipamount
60       \thm@topsepadd\theorempostskipamount
61      \fi
62    \else% oldframeskips
63      \thm@topsep\theorempreskipamount
64      \thm@topsepadd \theorempostskipamount
65      \ifvmode\advance\thm@topsepadd\partopsep\fi
66   \fi
67   \@topsep\thm@topsep
68   \@topsepadd\thm@topsepadd
69   \advance\linewidth -\theorem@indent
70   \advance\linewidth -\theorem@rightindent
71   \advance\@totalleftmargin \theorem@indent
72   \parshape \@ne \@totalleftmargin \linewidth
73   \@ifnextchar[{\@ythm{#1}{#2}{#3}}{\@xthm{#1}{#2}{#3}}
74 }
75 }{% not @ifpackageloaded{cleveref}
76 \gdef\@thm#1#2#3{%
77   \if@thmmarks
78     \stepcounter{end\InTheoType ctr}%
79   \fi
80   \renewcommand{\InTheoType}{#1}%
```

```
  \if@thmmarks
    \stepcounter{curr#1ctr}%
    \setcounter{end#1ctr}{0}%
  \fi
  \refstepcounter{#2}%
  \theorem@prework
   \LWR@forcenewpage% lwarp

   \LWR@printpendingfootnotes%                    lwarp

   \BlockClass{theorembody#1}%\LWR@thisthmstyle% lwarp
  \trivlist % latex's \trivlist, calling latex's \@trivlist unchanged
  \ifuse@newframeskips  % cf. latex.ltx for topsepadd: \@trivlist
    \ifthm@inframe
      \thm@topsep\theoreminframepreskipamount
      \thm@topsepadd\theoreminframepostskipamount
    \else
      \thm@topsep\theorempreskipamount
      \thm@topsepadd\theorempostskipamount
    \fi
   \else% oldframeskips
    \thm@topsep\theorempreskipamount
    \thm@topsepadd \theorempostskipamount
    \ifvmode\advance\thm@topsepadd\partopsep\fi
  \fi
  \@topsep\thm@topsep
  \@topsepadd\thm@topsepadd
  \advance\linewidth -\theorem@indent
  \advance\linewidth -\theorem@rightindent
  \advance\@totalleftmargin \theorem@indent
  \parshape \@ne \@totalleftmargin \linewidth
  \@ifnextchar[{\@ythm{#1}{#2}{#3}}{\@xthm{#1}{#2}{#3}}
}
}
}% AtBeginDocument
```

Patched to remember the style being used for new theorems:

```
\gdef\theoremstyle#1{%
  \@ifundefined{th@#1}{\@warning
         {Unknown theoremstyle `#1'. Using `plain'}%
         \theorem@style{plain}
           \renewcommand{\LWR@newtheoremstyle}{plain}% lwarp
           }%
     {
       \theorem@style{#1}
       \renewcommand{\LWR@newtheoremstyle}{#1}% lwarp
       }
}
```

Patched to remember the style for this theorem type, and set it later when the environment is started.

```

```

```
\gdef\@xnthm#1#2[#3]{%
  \ifthm@tempif
     \csedef{LWR@thmstyle#1}{\LWR@newtheoremstyle}% lwarp
     \expandafter\@ifundefined{c@#1}%
        {\@definecounter{#1}}{}%
     \@newctr{#1}[#3]%
     \expandafter\xdef\csname the#1\endcsname{%
       \expandafter\noexpand\csname the#3\endcsname \@thmcountersep
          {\noexpand\csname\the\theoremnumbering\endcsname{#1}}}%
     \expandafter\gdef\csname mkheader@#1\endcsname
       {\csname setparms@#1\endcsname
        \@thm{#1}{#1}{#2}
        }%
     \global\@namedef{end#1}{\@endtheorem}
    \AtBeginEnvironment{#1}{\edef\LWR@thisthmstyle{\@nameuse{LWR@thmstyle#1}}}% lwarp
  \fi
}

\gdef\@ynthm#1#2{%
  \ifthm@tempif
     \csedef{LWR@thmstyle#1}{\LWR@newtheoremstyle}% lwarp
     \expandafter\@ifundefined{c@#1}%
        {\@definecounter{#1}}{}%
     \expandafter\xdef\csname the#1\endcsname
        {\noexpand\csname\the\theoremnumbering\endcsname{#1}}%
     \expandafter\gdef\csname mkheader@#1\endcsname
       {\csname setparms@#1\endcsname
        \@thm{#1}{#1}{#2}
        }%
     \global\@namedef{end#1}{\@endtheorem}
    \AtBeginEnvironment{#1}{\edef\LWR@thisthmstyle{\@nameuse{LWR@thmstyle#1}}}% lwarp
  \fi
}

\gdef\@othm#1[#2]#3{%
  \@ifundefined{c@#2}{\@nocounterr{#2}}%
   {\ifthm@tempif
     \csedef{LWR@thmstyle#1}{\LWR@newtheoremstyle}% lwarp
     \global\@namedef{the#1}{\@nameuse{the#2}}%
     \expandafter\protected@xdef\csname num@addtheoremline#1\endcsname{%
               \noexpand\@num@addtheoremline{#1}{#3}}%
     \expandafter\protected@xdef\csname nonum@addtheoremline#1\endcsname{%
               \noexpand\@nonum@addtheoremline{#1}{#3}}%
    \theoremkeyword{#3}%
    \expandafter\protected@xdef\csname #1Keyword\endcsname
             {\the\theoremkeyword}%
     \expandafter\gdef\csname mkheader@#1\endcsname
       {\csname setparms@#1\endcsname
                \@thm{#1}{#2}{#3}
        }%
     \global\@namedef{end#1}{\@endtheorem}
    \AtBeginEnvironment{#1}{\edef\LWR@thisthmstyle{\@nameuse{LWR@thmstyle#1}}}% lwarp
  \fi}
}
```

§ 451.4 HTML cross-referencing

Mimics a float by incrementing the float counter and generating an HTML anchor. These are used for list-of-theorem cross-references.

```
\newcommand{\LWR@inctheorem}{%
\addtocounter{LWR@thisautoid}{1}%
\LWR@stoppars%
\LWR@htmltag{%
   a id=\textquotedbl\LWR@print@mbox{autoid-\arabic{LWR@thisautoid}}\textquotedbl%
}%
\LWR@htmltag{/a}%
\LWR@startpars%
}
```

§ 451.5 \newtheoremstyle

The following are patched for CSS.

These were in individual files `thp.sty` for plain, `thmb.sty` for margin break, etc. They are gathered together here.

Each theorem is encased in a `BlockClass` environment of class `theorembody<style>`.

Each header is encased in an `\InlineClass` of class `theoremheader<style>`.

```
\gdef\newtheoremstyle#1#2#3{%
  \expandafter\@ifundefined{th@#1}%
   {\expandafter\gdef\csname th@#1\endcsname{%
    \def\@begintheorem####1####2{%
    \LWR@inctheorem% lwarp
    #2}%
    \def\@opargbegintheorem####1####2####3{%
    \LWR@inctheorem% lwarp
    #3}%
}%
}%
{\PackageError{\basename}{Theorem style #1 already defined}\@eha}
}
```

§ 451.6 Standard styles

```
\renewtheoremstyle{plain}%
  {\item[
    \InlineClass{theoremheaderplain}{##1\ ##2\theorem@separator}]}%
  {\item[
    \InlineClass{theoremheaderplain}{##1\ ##2\ (##3)\theorem@separator}]}

\renewtheoremstyle{break}%
  {\item[
    \InlineClass{theoremheaderbreak}{##1\ ##2\theorem@separator}\newline
    ]}%
  {\item[
    \InlineClass{theoremheaderbreak}%
        {##1\ ##2\ (##3)\theorem@separator}\newline
    ]}
```

```
\renewtheoremstyle{change}%
  {\item[
    \InlineClass{theoremheaderchange}{##2\ ##1\theorem@separator}]}%
  {\item[
    \InlineClass{theoremheaderchange}{##2\ ##1\ (##3)\theorem@separator}]}

\renewtheoremstyle{changebreak}%
  {\item[
        \InlineClass{theoremheaderchangebreak}%
            {##2\ ##1\theorem@separator}\newline
    ]}%
  {\item[
        \InlineClass{theoremheaderchangebreak}%
            {##2\ ##1\ (##3)\theorem@separator}\newline
    ]}

\renewtheoremstyle{margin}%
  {\item[
        \InlineClass{theoremheadermargin}{##2 \qquad ##1\theorem@separator}
    ]}%
  {\item[
     \InlineClass{theoremheadermargin}{##2 \qquad ##1\ (##3)\theorem@separator}
    ]}

\renewtheoremstyle{marginbreak}%
  {\item[
    \InlineClass{theoremheadermarginbreak}%
        {##2 \qquad ##1\theorem@separator}\newline
    ]}%
  {\item[
    \InlineClass{theoremheadermarginbreak}%
        {##2 \qquad ##1\ (##3)\theorem@separator}\newline
    ]}

\renewtheoremstyle{nonumberplain}%
  {\item[
    \InlineClass{theoremheaderplain}{##1\theorem@separator}]}%
  {\item[
    \InlineClass{theoremheaderplain}{##1\ (##3)\theorem@separator}]}

\renewtheoremstyle{nonumberbreak}%
  {\item[
    \InlineClass{theoremheaderbreak}{##1\theorem@separator}\newline
    ]}%
  {\item[
    \InlineClass{theoremheaderbreak}{##1\ (##3)\theorem@separator}\newline
    ]}

\renewtheoremstyle{empty}%
  {\item[]}%
  {\item[
    \InlineClass{theoremheaderplain}{##3}]}

\renewtheoremstyle{emptybreak}%
```

```
  {\item[]%
  {\item[
    \InlineClass{theoremheaderplain}{##3}] \ \newline}
```

§ 451.7 Additional objects

The following manually adjust the CSS for the standard configuration objects which are not a purely plain style:

```
\ifbool{LWR@ntheoremamsthm}{}{%
```

Upright text via CSS:

```
    \newtheoremstyle{plainupright}%
    {\item[
        \InlineClass{theoremheaderplain}{##1\ ##2\theorem@separator}]}%
    {\item[
        \InlineClass{theoremheaderplain}{##1\ ##2\ (##3)\theorem@separator}]}
```

Upright text and small caps header via CSS:

```
    \newtheoremstyle{nonumberplainuprightsc}%
    {\item[
        \InlineClass{theoremheadersc}{##1\theorem@separator}]}%
    {\item[
        \InlineClass{theoremheadersc}{##1\ (##3)\theorem@separator}]}
}% not amsthm
```

§ 451.8 Renewed standard configuration

The following standard configuration is renewed using the new CSS:

```
\ifbool{LWR@ntheoremamsthm}{}{%
```

```
\ifx\thm@usestd\@undefined
\else
    \theoremnumbering{arabic}
    \theoremstyle{plain}
    \RequirePackage{latexsym}
    \theoremsymbol{\Box}
    \theorembodyfont{\itshape}
    \theoremheaderfont{\normalfont\bfseries}
    \theoremseparator{}
    \renewtheorem{Theorem}{Theorem}
    \renewtheorem{theorem}{Theorem}
    \renewtheorem{Satz}{Satz}
    \renewtheorem{satz}{Satz}
    \renewtheorem{Proposition}{Proposition}
    \renewtheorem{proposition}{Proposition}
    \renewtheorem{Lemma}{Lemma}
    \renewtheorem{lemma}{Lemma}
    \renewtheorem{Korollar}{Korollar}
    \renewtheorem{korollar}{Korollar}
    \renewtheorem{Corollary}{Corollary}
```

```
    \renewtheorem{corollary}{Corollary}

    \theoremstyle{plainupright}
    \theorembodyfont{\upshape}
    \theoremsymbol{\HTMLunicode{25A1}}% UTF-8 white box
    \renewtheorem{Example}{Example}
    \renewtheorem{example}{Example}
    \renewtheorem{Beispiel}{Beispiel}
    \renewtheorem{beispiel}{Beispiel}
    \renewtheorem{Bemerkung}{Bemerkung}
    \renewtheorem{bemerkung}{Bemerkung}
    \renewtheorem{Anmerkung}{Anmerkung}
    \renewtheorem{anmerkung}{Anmerkung}
    \renewtheorem{Remark}{Remark}
    \renewtheorem{remark}{Remark}
    \renewtheorem{Definition}{Definition}
    \renewtheorem{definition}{Definition}

    \theoremstyle{nonumberplainuprightsc}
    \theoremsymbol{\HTMLunicode{220E}}% UTF-8 end-of-proof
    \renewtheorem{Proof}{Proof}
    \renewtheorem{proof}{Proof}
    \renewtheorem{Beweis}{Beweis}
    \renewtheorem{beweis}{Beweis}
    \qedsymbol{\HTMLunicode{220E}}% UTF-8 end-of-proof

    \theoremsymbol{}
\fi
}% not amsthm
```

§ 451.9 amsthm option

Only if the amsthm option was given:

```
\ifbool{LWR@ntheoremamsthm}{

\gdef\th@plain{%
  \def\theorem@headerfont{\normalfont\bfseries}\itshape%
  \def\@begintheorem##1##2{%
        \LWR@inctheorem% lwarp
      \item[
  \InlineClass{theoremheaderplain}{##1\ ##2.}
        ]}%
  \def\@opargbegintheorem##1##2##3{%
        \LWR@inctheorem% lwarp
     \item[
  \InlineClass{theoremheaderplain}{##1\ ##2\ (##3).}
        ]}}

\gdef\th@nonumberplain{%
  \def\theorem@headerfont{\normalfont\bfseries}\itshape%
  \def\@begintheorem##1##2{%
        \LWR@inctheorem% lwarp
      \item[
  \InlineClass{theoremheaderplain}{##1.}
```

```
        ]}%
  \def\@opargbegintheorem##1##2##3{%
        \LWR@inctheorem% lwarp
     \item[
  \InlineClass{theoremheaderplain}{##1\ (##3).}
        ]}}

\gdef\th@definition{%
  \def\theorem@headerfont{\normalfont\bfseries}\normalfont%
  \def\@begintheorem##1##2{%
        \LWR@inctheorem% lwarp
      \item[
  \InlineClass{theoremheaderdefinition}{##1\ ##2.}
        ]}%
  \def\@opargbegintheorem##1##2##3{%
        \LWR@inctheorem% lwarp
     \item[
  \InlineClass{theoremheaderdefinition}{##1\ ##2\ (##3).}
        ]}}

\gdef\th@nonumberdefinition{%
  \def\theorem@headerfont{\normalfont\bfseries}\normalfont%
  \def\@begintheorem##1##2{%
        \LWR@inctheorem% lwarp
      \item[
  \InlineClass{theoremheaderdefinition}{##1.}
        ]}%
  \def\@opargbegintheorem##1##2##3{%
        \LWR@inctheorem% lwarp
     \item[
  \InlineClass{theoremheaderdefinition}{##1\ (##3).}
        ]}}

\gdef\th@remark{%
  \def\theorem@headerfont{\itshape}\normalfont%
  \def\@begintheorem##1##2{%
        \LWR@inctheorem% lwarp
      \item[
  \InlineClass{theoremheaderremark}{##1\ ##2.}
        ]}%
  \def\@opargbegintheorem##1##2##3{%
        \LWR@inctheorem% lwarp
     \item[
  \InlineClass{theoremheaderremark}{##1\ ##2\ (##3).}
        ]}}

\gdef\th@nonumberremark{%
  \def\theorem@headerfont{\itshape}\normalfont%
  \def\@begintheorem##1##2{%
        \LWR@inctheorem% lwarp
      \item[
  \InlineClass{theoremheaderremark}{##1.}
        ]}%
  \def\@opargbegintheorem##1##2##3{%
        \LWR@inctheorem% lwarp
```

```
    \item[
  \InlineClass{theoremheaderremark}{##1\ (##3).}
        ]}}

\gdef\th@proof{%
  \def\theorem@headerfont{\normalfont\bfseries}\itshape%
  \def\@begintheorem##1##2{%
        \LWR@inctheorem% lwarp
      \item[
  \InlineClass{theoremheaderproof}{##1.}
        ]}%
  \def\@opargbegintheorem##1##2##3{%
        \LWR@inctheorem% lwarp
     \item[
  \InlineClass{theoremheaderproof}{##1\ (##3).}
        ]}}



\newcounter{proof}%
\if@thmmarks
    \newcounter{currproofctr}%
    \newcounter{endproofctr}%
\fi

\gdef\proofSymbol{\openbox}

\newcommand{\proofname}{Proof}

\newenvironment{proof}[1][\proofname]{
    \th@proof
    \def\theorem@headerfont{\itshape}%
    \normalfont
    \theoremsymbol{\HTMLunicode{220E}}% UTF-8 end-of-proof
    \@thm{proof}{proof}{#1}
}%
{\@endtheorem}

}{}% amsthm option
```

§ 451.10 Ending a theorem

Patched for css:

```
\let\LWR@origendtheorem\@endtheorem
\renewcommand{\@endtheorem}{%
\ifbool{LWR@ntheoremmarks}{%
    \ifsetendmark%
    \InlineClass{theoremendmark}{\csname\InTheoType Symbol\endcsname}%
    \setendmarkfalse%
    \fi%
}{}%
\LWR@origendtheorem% also does \@endtrivlist
\ifbool{LWR@ntheoremmarks}{\global\setendmarktrue}{}%
```

```
    \LWR@printpendingfootnotes%                    lwarp

\endBlockClass%
}
```

§ 451.11 \NoEndMark

```
\gdef\NoEndMark{\global\setendmarkfalse}
```

§ 451.12 List-of

Redefined to reuse the float mechanism to add list-of-theorem links:

\thm@thmline {⟨*1: printed type*⟩} {⟨*2: #*⟩} {⟨*3: optional*⟩} {⟨*4: page*⟩}

```
\renewcommand{\thm@@thmline@noname}[4]{%
\hypertocfloat{1}{theorem}{thm}{#2 #3}{}%
}

\renewcommand{\thm@@thmline@name}[4]{%
\hypertocfloat{1}{theorem}{thm}{#1 #2 #3}{}%
}
```

This was redefined by ntheorem when loaded, so it is now redefined for lwarp:

```
\def\thm@@thmline{\thm@@thmline@name}
```

Patch for css:

```
\def\listtheorems#1{
\LWR@htmlelementclass{nav}{lothm}%
\begingroup
\c@tocdepth=-2%
\def\thm@list{#1}\thm@processlist
\endgroup
\LWR@htmlelementclassend{nav}{lothm}%
}
```

§ 451.13 Symbols

Proof QED symbol:

```
\newcommand{\qed}{\qquad\the\qedsymbol}

\AtBeginDocument{
\@ifundefined{LWR@orig@openbox}{
\LetLtxMacro\LWR@orig@openbox\openbox
\LetLtxMacro\LWR@orig@blacksquare\blacksquare
\LetLtxMacro\LWR@orig@Box\Box

\def\openbox{\text{\HTMLunicode{25A1}}}% UTF-8 white box
\def\blacksquare{\text{\HTMLunicode{220E}}}% UTF-8 end-of-proof
\def\Box{\text{\HTMLunicode{25A1}}}% UTF-8 white box

```

```
\appto\LWR@restoreorigformatting{%
\LetLtxMacro\openbox\LWR@orig@openbox%
\LetLtxMacro\blacksquare\LWR@orig@blacksquare%
\LetLtxMacro\Box\LWR@orig@Box%
}% appto
}{}% @ifundefined
}% AtBeginDocument
```

§ 451.14 Cross-referencing

`\thref {`⟨*label*⟩`}`

```
\newcommand*{\thref}[1]{\cref{#1}}%
```

File 344 **lwarp-octave.sty**

§ 452 Package octave

(*Emulates or patches code by* Andrew A. Cashner.)

Pkg octave octave is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{octave}[2017/10/31]
```

Remove the leading 1pt kern:

```
\RenewDocumentCommand{\@PrintTicks}{ m }{%
\kern-1pt%  lwarp
\@TickNum = #1%
\loop
\@Tick{}%
\advance\@TickNum by -1
\ifnum\@TickNum > 0
\repeat
}
```

Use unicode for the prime character:

```
\RenewDocumentCommand{\@Tick}{}{\HTMLunicode{2032}}
```

Catch the inline font:

```
\RenewDocumentCommand{\pitch}{ m o m }{%
\if@OctaveNumber%
{%
    \pitchfont{%
        \LWR@textcurrentfont{%  lwarp
            \MakeUppercase{#1}%
            \IfValueTF{#2}{#2}{}\textsubscript{#3}%
        }%
    }%
}%
```

```
\else%
{%
    \pitchfont{%
        \LWR@textcurrentfont{%  lwarp
            \@GetOctaveTick{#1}[#2]{#3}%
        }%
    }%
}%
\fi%
}
```

The original was hard to adapt to lwarp's handling of &.

```
\StartDefiningTabulars
\renewcommand{\octavetable}{%
\begin{tabular}{ll}
\octaveprimes \pitch{C}{0} & \octavenumbers \pitch{C}{0} \\
\octaveprimes \pitch{C}{1} & \octavenumbers \pitch{C}{1} \\
\octaveprimes \pitch{C}{2} & \octavenumbers \pitch{C}{2} \\
\octaveprimes \pitch{C}{3} & \octavenumbers \pitch{C}{3} \\
\octaveprimes \pitch{C}{4} & \octavenumbers \pitch{C}{4} \\
\octaveprimes \pitch{C}{5} & \octavenumbers \pitch{C}{5} \\
\octaveprimes \pitch{C}{6} & \octavenumbers \pitch{C}{6} \\
\octaveprimes \pitch{C}{7} & \octavenumbers \pitch{C}{7} \\
\end{tabular}
}
\StopDefiningTabulars
```

File 345 **lwarp-orcidlink.sty**

§ 453 Package

orcidlink

(*Emulates or patches code by* Leo C. Stein.)

Pkg orcidlink orcidlink is patched for use by lwarp.

for HTML output:

```
\RequirePackage{lwarp-scalerel}

\LWR@ProvidesPackagePass{orcidlink}[2020/11/21]

\renewcommand\orcidlink[1]{%
    \texorpdfstring%
        {%
            \href%
                {https://orcid.org/#1}%
                {%
                    \begin{lateximage}[orcid #1]%   lwarp
                    \mbox{%
                        \scalerel*{%
                            \begin{tikzpicture}[yscale=-1,transform shape]
                            \pic{orcidlogo};
                            \end{tikzpicture}
                        }{|}%
```

```
                    }%
                    \end{lateximage}%   lwarp
                }%
        }%
        {}%
}

\begin{warpMathJax}
\CustomizeMathJax{\newcommand{\orcidlink}[1]{}}
\end{warpMathJax}
```

File 346 **lwarp-overpic.sty**

§ 454 Package overpic

(*Emulates or patches code by* Rolf Niepraschk.)

Pkg overpic overpic is patched for use by lwarp.

⚠ scaling The macros \overpicfontsize and \overpicfontskip are used during HTML generation. These are sent to \fontsize to adjust the font size for scaling differences between the print and HTML versions of the document. Renew these macros before using the overpic and Overpic environments.

See section 88.2 for the print-mode version of \overpicfontsize and \overpicfontskip.

for HTML output:

```
\LWR@ProvidesPackagePass{overpic}[2017/10/06]

\newcommand*{\overpicfontsize}{12}
\newcommand*{\overpicfontskip}{14}

\BeforeBeginEnvironment{overpic}{%
    \begin{lateximage}%
    \fontsize{\overpicfontsize}{\overpicfontskip}%
    \selectfont%
}

\AfterEndEnvironment{overpic}{\end{lateximage}}

\BeforeBeginEnvironment{Overpic}{%
    \begin{lateximage}%
    \fontsize{\overpicfontsize}{\overpicfontskip}%
    \selectfont%
}

\AfterEndEnvironment{Overpic}{\end{lateximage}}
```

File 347 **lwarp-pagegrid.sty**

§ 455 Package pagegrid

Pkg pagegrid pagegrid is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{pagegrid}[2016/05/16]
\newcommand*{\pagegridsetup}[1]{}
```

File 348 **lwarp-pagenote.sty**

§ 456 Package pagenote

Pkg pagenote pagenote works as-is, but the page option is disabled.

⚠ labels Note that labels in page notes do not appear as expected, even in the print version.

for HTML output:

```
\DeclareOption{page}{}
\LWR@ProvidesPackagePass{pagenote}[2009/09/03]
```

For MathJax:

```
\begin{warpMathJax}
\appto\LWR@syncnotenumbers{\LWR@synconenotenumber{LWRpagenote}{\thepagenote}}
\CustomizeMathJax{\def\LWRpagenote{1}}
\CustomizeMathJax{\newcommand{\pagenote}[2][\LWRpagenote]{{}^{\mathrm{#1}}}}
\end{warpMathJax}
```

There is no \pagenotemark, so the following are not required:

```
\providecommand{\pagenotename}{pagenote}
\appto\LWR@syncnotenames{\LWR@synconenotename{LWRpagenote}{\pagenotename}}
```

File 349 **lwarp-pagesel.sty**

§ 457 Package pagesel

Pkg pagesel pagesel is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{pagesel}[2016/05/16]
```

File 350 **lwarp-paralist.sty**

§ 458 Package paralist

(*Emulates or patches code by* Bernd Schandl.)

Pkg paralist paralist is supported with minor changes.

for HTML output:

```
\LWR@ProvidesPackagePass{paralist}[2017/01/22]
```

The compact environments are identical to the regular ones:

```
\LetLtxMacro\compactitem\itemize
\LetLtxMacro\compactenum\enumerate
\LetLtxMacro\compactdesc\description
\LetLtxMacro\endcompactitem\enditemize
\LetLtxMacro\endcompactenum\endenumerate
\LetLtxMacro\endcompactdesc\enddescription
```

For the inline environments, revert `\item` to its original print-mode version:

```
\AtBeginEnvironment{inparaitem}{\LetLtxMacro\item\LWR@origitem}
\AtBeginEnvironment{inparaenum}{\LetLtxMacro\item\LWR@origitem}
\AtBeginEnvironment{inparadesc}{\LetLtxMacro\item\LWR@origitem}
```

Manual formatting of the description labels:

```
\def\paradescriptionlabel#1{{\normalfont\textbf{#1}}}
```

File 351 **lwarp-parallel.sty**

§ 459 Package

parallel

(*Emulates or patches code by* Matthias Eckermann.)

Pkg parallel parallel is emulated.

Package options are ignored. Footnotes are treated as normal lwarp footnotes.

Environment option c gives side-by-side s of class minipage, each of whose width is a percent depending on the given left and right widths, proportional to `\linewidth`.

Inside each environment, `\linewidth` and `\textwidth` are set for the print-output sizes.

for HTML output: Discard all options for lwarp-parallel:

```
\LWR@ProvidesPackageDrop{parallel}[2003/04/13]

\newcounter{LWR@parallel@Lwidth}
\newcounter{LWR@parallel@Rwidth}
\newcommand*{\LWR@parallel@border}

\newenvironment*{Parallel}[3][]%
    {%
        \LWR@printpendingfootnotes%
        \setlength{\linewidth}{\LWR@userstextwidth}%
        \setlength{\textwidth}{\LWR@userstextwidth}%
        \renewcommand*{\LWR@parallel@border}{}%
        \ifstrequal{#1}{v}%
            {%
           \renewcommand*{\LWR@parallel@border}{ ; border-left: 2px solid black}%
            }%
            {}%
```

```
        \ifblank{#2}{%
            \ifblank{#3}{% {}{}
                \setcounter{LWR@parallel@Lwidth}{45}%
                \setcounter{LWR@parallel@Rwidth}{45}%
            }% {}{}
            {% {}{x}
                \setlength{\LWR@templengthone}{\linewidth-#3}%
                \setcounter{LWR@parallel@Lwidth}{%
                    90*\ratio{\LWR@templengthone}{\linewidth}%
                }%
                \setcounter{LWR@parallel@Rwidth}{%
                    90*\ratio{#3}{\linewidth}%
                }%
            }% {}{x}
        }% #2 blank
        {% #2 non-blank
            \ifblank{#3}{% {x}{}
                \setcounter{LWR@parallel@Lwidth}{%
                    90*\ratio{#2}{\linewidth}%
                }%
                \setlength{\LWR@templengthone}{\linewidth-#2}%
                \setcounter{LWR@parallel@Rwidth}{%
                    90*\ratio{\LWR@templengthone}{\linewidth}%
                }%
            }% {x}{}
            {% {x}{x}
                \setcounter{LWR@parallel@Lwidth}{%
                    90*\ratio{#2}{\linewidth}%
                }%
                \setcounter{LWR@parallel@Rwidth}{%
                    90*\ratio{#3}{\linewidth}%
                }%
            }% {x}{x}
        }% #2 non-blank
    }
    {%
        \ParallelAtEnd%
        \renewcommand*{\ParallelAtEnd}{}%
        \LWR@printpendingfootnotes%
    }

\newcommand*{\ParallelLText}[1]{%
    \begin{BlockClass}[%
        width:\arabic{LWR@parallel@Lwidth}\% ; % space
        padding: .5ex 1\% ; % space
    ]{minipage}%
    #1%
    \end{BlockClass}%
}

\newcommand*{\ParallelRText}[1]{%
    \begin{BlockClass}[%
        width:\arabic{LWR@parallel@Rwidth}\% ; % space
        padding: .5ex 1\% ; % space
        \LWR@parallel@border%
```

```
    ]{minipage}%
    #1%
    \end{BlockClass}%
}

\newcommand*{\ParallelPar}{\LWR@printpendingfootnotes}

\newcommand*{\ParallelAtEnd}{}
```

File 352 **lwarp-parcolumns.sty**

§ 460 Package

parcolumns

(*Emulates or patches code by* Jonathan Sauer.)

Pkg parcolumns parcolumns is emulated.

rulebetween is honored. The other keys are ignored, including colwidths.

Each column is placed inside a of class minipage, each of whose width is fixed at 85% divided by the number of columns. In most cases, this results in side-by-side minipages adapting to the browser width. Inside each minipage, \linewidth, \textwidth, and \textheight are set for a virtual 6×9 inch page, with \linewidth divided by the number of columns.

for HTML output: Discard all options for lwarp-parcolumns:

```
\RequirePackage{keyval}%

\LWR@ProvidesPackageDrop{parcolumns}[2004/11/25]


\newcounter{LWR@parcolumns@numcols}
\newcounter{LWR@parcolumns@thiscol}
\newcounter{LWR@parcolumns@width}
\newbool{LWR@parcolumns@started}
\newbool{LWR@parcolumns@rule}

\define@key{LWRparcols}{colwidths}{}
\define@key{LWRparcols}{distance}{}
\define@key{LWRparcols}{rulebetween}[true]{%
    \setbool{LWR@parcolumns@rule}{#1}%
}
\define@key{LWRparcols}{nofirstindent}{}
\define@key{LWRparcols}{sloppy}{}
\define@key{LWRparcols}{sloppyspaces}{}

\newenvironment*{parcolumns}[2][]
    {%
        \begin{LWR@setvirtualpage}*[#2]%
        \setcounter{LWR@parcolumns@numcols}{#2}%
        \setcounter{LWR@parcolumns@thiscol}{1}%
        \boolfalse{LWR@parcolumns@started}%
        \boolfalse{LWR@parcolumns@rule}%
```

```
        \setcounter{LWR@parcolumns@width}{%
            85/#2
        }%
        \setkeys{LWRparcols}{#1}%
    }
    {%


        \colplacechunks%
        \end{LWR@setvirtualpage}%
    }

\newcommand{\LWR@parcolumns@onecol}[1]{%
    \ifbool{LWR@parcolumns@started}%
        {}%
        {%
            \LWR@htmldivclass{parcolumns}%
            \booltrue{LWR@parcolumns@started}%
        }%
    \ifboolexpr{%
        bool {LWR@parcolumns@rule} and
        test {%
            \ifnumgreater
                {\value{LWR@parcolumns@thiscol}}
                {1}
        }%
    }%
        {\renewcommand{\LWR@tempone}{ ; border-left: 2px solid black}}%
        {\renewcommand{\LWR@tempone}{}}%
    \begin{BlockClass}[%
        width:\arabic{LWR@parcolumns@width}\% ; % space
        padding: .5ex 1\% ; % space
        \LWR@tempone%
    ]{minipage}%
    #1%
    \end{BlockClass}%
    \addtocounter{LWR@parcolumns@thiscol}{1}%
}

\newcommand{\colchunk}[2][\value{LWR@parcolumns@thiscol}]{%
    \whileboolexpr{%
        test {%
            \ifnumcomp%
                {\value{LWR@parcolumns@thiscol}}
                {<}
                {#1}%
        }%
    }{%
        \LWR@parcolumns@onecol{}%
    }%
    \LWR@parcolumns@onecol{#2}%
}

\newcommand*{\colplacechunks}{%
    \ifbool{LWR@parcolumns@started}%
        {%
```

```
            \LWR@htmldivclassend{div}%
            \boolfalse{LWR@parcolumns@started}%
        }%
        {}%
    \setcounter{LWR@parcolumns@thiscol}{1}%
}
```

File 353 **lwarp-parnotes.sty**

§ 461 Package

parnotes

(*Emulates or patches code by* Chelsea Hughes.)

Pkg parnotes parnotes is supported with some patches.

for HTML output:

```
\LWR@ProvidesPackagePass{parnotes}[2016/08/15]

\long\def\PN@parnote@real#1#2{%
    \parnotemark{#1}%
    % Unless this is the first parnote in \PN@text, add a separator first
    \unless\ifx\PN@text\@empty\g@addto@macro\PN@text{\parnoteintercmd}\fi
    % Redefine \@currentlabel to the parnote label, so \label works
    \g@addto@macro\PN@text{%
%         \phantomsection%
        \def\@currentlabel{#1}%
        \def\cref@currentlabel{%        lwarp
            [parnotemark][\arabic{parnotemark}][]\theparnotemark%
        }%
    }%
    \g@addto@macro\PN@text{%
        \LWR@textcurrentfont{%          lwarp
            \parnotemark{#1}\nolinebreak\thinspace#2%
        }%
    }%
}

\def\PN@parnotes@real{%
    % We call \par later, so this avoids recursion with \PN@parnotes@auto
    \PN@inparnotestrue
    \unless\ifvmode\par\fi
    % Avoid page breaks between a paragraph and its parnotes
    \nopagebreak\addvspace{\parnotevskip}%
    \LWR@forcenewpage%                      lwarp
    \begin{BlockClass}(note){footnotes}%    lwarp
    {\parnotefmt{\PN@text}\par}%
    \end{BlockClass}%                       lwarp
    \global\def\PN@text{}%
    \addvspace{\parnotevskip}%
    %
    % These can be enabled or disabled by package options
    %
    \PN@disable@indent
    \PN@reset@optional
```

```
    \PN@inparnotesfalse
}

\AtBeginDocument{
    \crefname{parnotemark}{paragraph note}{paragraph notes}
    \Crefname{parnotemark}{Paragraph note}{Paragraph notes}
}
```

For MathJax:

```
\begin{warpMathJax}
\providecommand{\parnotename}{parnote}
\appto\LWR@syncnotenumbers{%
    \addtocounter{parnotemark}{-1}% specific to parnotes
    \LWR@synconenotenumber{LWRparnote}{\theparnotemark}%
    \addtocounter{parnotemark}{1}% specific to parnotes
}
\appto\LWR@syncnotenames{\LWR@synconenotename{LWRparnote}{\parnotename}}
\CustomizeMathJax{\def\LWRparnote{1}}
\CustomizeMathJax{\newcommand{\parnote}[2][\LWRparnote]{{}^{\mathrm{#1}}}}
\CustomizeMathJax{\newcommand{\parnotemark}[1][\LWRparnote]{{}^{\mathrm{#1}}}}
\end{warpMathJax}
```

File 354 **lwarp-parskip.sty**

§ 462 Package

parskip

Pkg parskip parskip is ignored.

for HTML output: Discard all options for lwarp-parskip.

```
\LWR@ProvidesPackageDrop{parskip}[2001/04/09]
```

File 355 **lwarp-pbalance.sty**

§ 463 Package

pbalance

Pkg pbalance pbalance is ignored.

for HTML output:

```
\RequirePackage{balance}

\LWR@ProvidesPackageDrop{pbalance}[2020/12/16]

\newcommand\shrinkLastPage[1]{}
```

File 356 **lwarp-pbox.sty**

§ 464 Package pbox

(*Emulates or patches code by* Simon Law.)

Pkg pbox pbox is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{pbox}[2011/12/07]

\NewDocumentCommand{\pbox}{O{t} O{} O{t} m +m}{%
\global\booltrue{LWR@minipagefullwidth}%
\parbox[#1][#2][#3]{#4}{#5}%
}

\newcommand{\settominwidth}[3][\columnwidth]{%
\settowidth{#2}{#3}%
}

\newcommand{\widthofpbox}[1]{%
\widthof{#1}%
}
```

File 357 **lwarp-pdfcol.sty**

§ 465 Package pdfcol

Pkg pdfcol pdfcol is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{pdfcol}[2018/11/01]

\ltx@newif\ifpdfcolAvailable
\pdfcolAvailablefalse

\def\pdfcolErrorNoStacks{
    \PackageInfo{lwarp-pdfcol}{Ignoring pdfcol for HTML output.}
}

\def\pdfcolInitStack#1{}%

\long\def\pdfcolIfStackExists#1#2#3{#3}%

\def\pdfcolSwitchStack#1{}%

\def\pdfcolSetCurrentColor{}%

\def\pdfcolSetCurrent#1{}%
```

File 358 **lwarp-pdfcolfoot.sty**

§ 466 Package pdfcolfoot

Pkg pdfcolfoot pdfcolfoot is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{pdfcolfoot}[2016/05/16]

\newcommand*{\pdfcolfoot@switch}{}

\newcommand*{\pdfcolfoot@current}{}
```

File 359 **lwarp-pdfcolmk.sty**

§ 467 Package

pdfcolmk

Pkg pdfcolmk pdfcolmk is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{pdfcolmk}[2016/05/16]
```

File 360 **lwarp-pdfcolparallel.sty**

§ 468 Package

pdfcolparallel

Pkg pdfcolparallel pdfcolparallel is ignored.

for HTML output:

```
\RequirePackage{keyval}%

\LWR@ProvidesPackageDropA{pdfcolparallel}{2016/05/16}
```

Pass options to parallel:

```
\DeclareOption*{%
    \PassoptionsToPackage{\CurrentOption}{parallel}%
}
```

Process the options:

```
\LWR@ProvidesPackageDropB
```

Require parallel with the given options:

```
\RequirePackage{parallel}[2003/04/13]
```

Ignore the new key:

```
\define@key{parallel}{rulebetweencolor}{}
```

File 361 **lwarp-pdfcolparcolumns.sty**

§ 469 Package

pdfcolparcolumns

Pkg pdfcolparcolumns pdfcolparcolumns is ignored.

for HTML output:

```
\LWR@ProvidesPackageDropA{pdfcolparcolumns}{2016/05/16}
```

Pass options to parcolumns:

```
\DeclareOption*{%
    \PassoptionsToPackage{\CurrentOption}{parcolumns}%
}
```

Process the options:

```
\LWR@ProvidesPackageDropB
```

Require parcolumns with the given options:

```
\RequirePackage{parcolumns}[2004/11/25]
```

Ignore the new key:

```
\define@key{LWRparcols}{rulebetweencolor}{}
```

File 362 **lwarp-pdfcomment.sty**

§ 470 Package

pdfcomment

Pkg pdfcomment

pdfcomment is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{pdfcomment}[2016/06/13]

\newenvironment{pdfsidelinecomment}[2][]{}{}
\newcommand{\pdfcomment}[2][]{}
\newcommand{\pdfmargincomment}[2][]{}
\newcommand{\pdfmarkupcomment}[3][]{#2}
\newcommand{\pdffreetextcomment}[2][]{}
\newcommand{\pdfsquarecomment}[2][]{}
\newcommand{\pdfcirclecomment}[2][]{}
\newcommand{\pdflinecomment}[2][]{}
\newcommand{\pdftooltip}[3][]{#2}
\newcommand{\pdfcommentsetup}[2][]{}
\newcommand{\listofpdfcomments}[1][]{}
\newcommand{\setliststyle}[1]{}
\newcommand{\defineliststyle}[2]{}
\newcommand{\defineavatar}[2]{}
\newcommand{\definestyle}[2]{}
```

For MathJax:

```
\begin{warpMathJax}
\CustomizeMathJax{\newcommand{\pdfmarkupcomment}[3][]{#2}}
\CustomizeMathJax{\newcommand{\pdftooltip}[3][]{#2}}
\end{warpMathJax}
```

File 363 **lwarp-pdfcrypt.sty**

§ 471 Package pdfcrypt

Pkg pdfcrypt pdfcrypt is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{pdfcrypt}[2016/05/16]

\newcommand*{\pdfcryptsetup}[1]{}
```

File 364 **lwarp-pdflscape.sty**

§ 472 Package pdflscape

Pkg pdflscape pdflscape is ignored.

for HTML output: Discard all options for lwarp-pdflscape:

```
\LWR@ProvidesPackageDrop{pdflscape}[2019/12/05]

\let\landscape\relax
\let\endlandscape\relax

\newenvironment*{landscape}{}{}
```

File 365 **lwarp-pdfmarginpar.sty**

§ 473 Package pdfmarginpar

Pkg pdfmarginpar pdfmarginpar is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{pdfmarginpar}[2011/08/05]

\newcommand{\pdfmarginpar}[2][]{}
\newcommand{\pdfmarginparset}[1]{}
```

File 366 **lwarp-pdfpages.sty**

§ 474 Package pdfpages

(*Emulates or patches code by* Andreas Matthias.)

Pkg pdfpages pdfpages is patched for use by lwarp.

Option `link` and `linkname` work:

```
\hyperlink{<filename>.pdf.<pagenubmer>}{some text}
\hyperlink{<linkname>.<pagenubmer>}{some text}
```

Options which make no sense in HTML are disabled.

for HTML output:

```
\LWR@ProvidesPackagePass{pdfpages}[2017-10-31]
```

Disable option which have no meaning for HTML output:

```
\define@key{pdfpages}{fitpaper}[false]{}
\define@key{pdfpages}{landscape}[false]{}
\define@key{pdfpages}{openright}[false]{}
\define@key{pdfpages}{signature}{}
\define@key{pdfpages}{signature*}{}
\define@key{pdfpages}{booklet}[false]{}
\define@key{pdfpages}{rotateoversize}[false]{}
\define@key{pdfpages}{doublepages}[false]{}
\define@key{pdfpages}{doublepagestwist}[false]{}
\define@key{pdfpages}{doublepagestwistodd}[false]{}
\define@key{pdfpages}{doublepagestwist*}[false]{}
\define@key{pdfpages}{doublepagestwistodd*}[false]{}
\define@key{pdfpages}{duplicatepages}[2]{}
\define@key{pdfpages}{thread}[false]{}
\define@key{pdfpages}{threadname}{}
\define@key{pdfpages}{linkfit}{}
\define@key{pdfpages}{linktodoc}[false]{}
\define@key{pdfpages}{linktodocfit}{}
\define@key{pdfpages}{linkfilename}{}
\define@key{pdfpages}{survey}[false]{}
\define@key{pdfpages}{survey-nolink}[false]{}
\define@key{pdfpages}{newwindow}[false]{}
```

Use print mode while measuring the page numbers:

```
\xpretocmd{\AM@getpagecount}{\LWR@restoreorigformatting}{}{}
```

Emulate a bit of eso-pic:

```
\newif\ifESO@texcoord

\newcommand{\ESO@HookIIBG}{}

\renewcommand{\AM@AddToShipoutPicture}{\g@addto@macro\ESO@HookIIBG}

\renewcommand{\ClearShipoutPicture}{}
```

`\LWR@esopic@newpage` At each \newpage.

```
\newcommand*{\LWR@esopic@newpage}{%
```

Is there something to draw?

```
\ifdefvoid{\ESO@HookIIBG}%
{}%
{%
```

If the `link` option was specified, add a hyper target:

```
    \ifAM@link%
```

```
        \hypertarget{\AM@linkname.\AM@page}{}%
    \fi%
```

Draw inside a picture environment of the size of a virtual page:

```
    \begingroup%
    \setlength{\unitlength}{1in}%
    \begin{picture}(8,10.5)%
    \ESO@HookIIBG%
    \end{picture}%
    \endgroup%
    \global\let\ESO@HookIIBG\@empty%
}
}
```

`\AM@output` Patched to use `\LWR@esopic@newpage`.

```
\xpatchcmd{\AM@output}
    {\newpage}
    {\LWR@esopic@newpage}
    {}
    {\LWR@patcherror{pdfpages}{AM@output-1}}

\xpatchcmd{\AM@output}
    {\newpage}
    {\LWR@esopic@newpage}
    {}
    {\LWR@patcherror{pdfpages}{AM@output-2}}

\xpatchcmd{\AM@output}
    {\newpage}
    {\LWR@esopic@newpage}
    {}
    {\LWR@patcherror{pdfpages}{AM@output-3}}
```

`\includepdf` Patched to set the user's paper size.

```
\xpretocmd{\includepdf}{%
    \begingroup%
    \setlength{\paperwidth}{\LWR@userspaperwidth}%
    \setlength{\paperheight}{\LWR@userspaperheight}%
}{}{}

\xapptocmd{\includepdf}{%
    \endgroup%
}{}{}
```

`\includepdfmerge` Patched to set the user's paper size.

```
\xpretocmd{\includepdfmerge}{%
    \begingroup%
    \setlength{\paperwidth}{\LWR@userspaperwidth}%
    \setlength{\paperheight}{\LWR@userspaperheight}%
}{}{}

\xapptocmd{\includepdfmerge}{%
```

```
    \endgroup%
}{}{}
```

\AM@hyper@begin@i Hyper links are created by \LWR@esopic@newpage, so don't create them here:

```
\renewcommand{\AM@hyper@begin@i}{}
```

File 367 **lwarp-pdfprivacy.sty**

§ 475 Package

pdfprivacy

Pkg pdfprivacy pdfprivacy is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{pdfprivacy}[2017/12/03]
```

File 368 **lwarp-pdfrender.sty**

§ 476 Package

pdfrender

Pkg pdfrender pdfrender is allowed during HTML, but it has no effect on HTML text output. pdfrender is enabled for use with xfakebold, and it is enabled during HTML so that it may be in use when an SVG math image is started. I.e. xfakebold's \setBold may be used outside of a math expression and still be detected when the math begins.

The lwarp-pdfrender package is present because it used to disable pdfrender, so this newer version is to overwrite older versions.

for HTML output:

```
\LWR@ProvidesPackagePass{pdfrender}[2019/12/29]
```

File 369 **lwarp-pdfsync.sty**

§ 477 Package

pdfsync

(*Emulates or patches code by* J. Laurens.)

Pkg pdfsync pdfsync is ignored.

for HTML output: Discard all options for lwarp-pdfsync:

```
\LWR@ProvidesPackageDrop{pdfsync}[2008/01/26]

\newcommand*{\pdfsync}{}
\newcommand*{\pdfsyncstart}{}
\newcommand*{\pdfsyncstop}{}
```

File 370 **lwarp-pdftricks.sty**

§ 478 Package

pdftricks

(*Emulates or patches code by* C. V. Radhakrishnan, C. V. Rajagopal, Antoine Chambert-Loir.)

Pkg pdftricks pdftricks is patched for use by lwarp.

⚠ convert image files The pdftricks image files `<jobname>-fig*.pdf` must be converted to `.svg`, or else a missing file error will occur. The image files must also be converted again whenever they change. To convert the images:

Enter ⇒ **`lwarpmk pdftosvg <jobname>-fig*.pdf`**

for HTML output:

```
\LWR@ProvidesPackagePass{pdftricks}[2003/08/10]
```

Reuse the print-mode images:

```
\def\PDFTfigname{\BaseJobname-fig\thepsfig}
```

If the `.pdf` images have not yet been converted to `.svg` then an error about a missing file will occur. Warn the user to convert the images.

```
\PackageWarning{lwarp-pdftricks}{
When the pdftricks images change,
remember to convert PDF images to SVG using 'lwarpmk pdftosvg *-fig.pdf',
}

\AfterEndDocument{\typeout{***}}
\AfterEndDocument{\typeout{*** Note: If pdftricks images are not found, new, or updated,}}
\AfterEndDocument{\typeout{*** \space use 'lwarpmk pdftosvg \BaseJobname-fig*.pdf'}}
\AfterEndDocument{\typeout{***}}
```

File 371 **`lwarp-pdfx.sty`**

§ 479 Package

pdfx

Pkg pdfx pdfx is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{pdfx}[2017/05/18]
```

File 372 **`lwarp-perpage.sty`**

§ 480 Package

perpage

(*Emulates or patches code by* David Kastrup.)

Pkg perpage perpage is mostly ignored, but support is added for footnote counters.

There is no page number in HTML, so most counters are not reset. If the document redefines \the<countername> to include \theperpage, it is necessary to place that redefininition inside a warpprint environment to avoid modifying the HTML defintions.

\AddAbsoluteCounter must not be inside warpprint, as the counter must be added for HTML also, although it is not incremented.

footnote numbering

To have footnote numbers reset each time footnotes are printed:

```
\setcounter{footnoteReset}{1}
```

For bigfoot, manyfoot, or perpage:

```
\MakePerPage{footnoteX}
— or —
\MakeSortedPerPage{footnoteX}
```

The footnotes are reset when they are printed, according to section level as set by FootnoteDepth, which is not necessarily by HTML page. This is recommended for \alph, \Alph, or \fnsymbol footnotes, due to the limited number of symbols which are available.

for HTML output:

```
\LWR@ProvidesPackageDrop{perpage}[2014/10/25]

\newcommand\AddAbsoluteCounter[1]
{
    \@ifundefined{c@abs#1}{%
        \expandafter\newcount\csname c@abs#1\endcsname
        \global\value{abs#1}\@ne
%         \global\expandafter\let\csname cl@abs#1\endcsname\@empty
        \expandafter\xdef\csname theabs#1\endcsname{%
%             \noexpand\number \csname c@abs#1\endcsname
        }%
%         \global\@namedef{c@pabs@#1}{\pp@cl@begin
%         \stepcounter{abs#1}%
%         \pp@cl@end}%
%         \@addtoreset{pabs@#1}{#1}
    }
    {}
}

\AddAbsoluteCounter{page}
\def\theabspage{1}

\newcommand*\MakePerPage[2][1]{%
    \ifltxcounter{#2Reset}{%
        \setcounter{#2Reset}{#1}%
    }{

}%
}

\newcommand*\MakeSorted[1]{}

\newcommand*\MakeSortedPerPage[2][1]{%
    \ifltxcounter{#2Reset}{%
        \setcounter{#2Reset}{#1}%
```

```
    }{
}%
}

\newcommand*{\theperpage}{1}
```

File 373 **lwarp-pfnote.sty**

§ 481 Package pfnote

Pkg pfnote pfnote is ignored.

pfnote ⚠ pfnote numbers While emulating pfnote, lwarp is not able to reset HTML footnote numbers per page number to match the printed version, as HTML has no concept of page numbers. lwarp therefore uses continuous footnote numbering even for pfnote.

for HTML output:

```
\LWR@ProvidesPackageDrop{pfnote}[1999/07/14]
```

File 374 **lwarp-phfqit.sty**

§ 482 Package phfqit

(*Emulates or patches code by* Philippe Faist.)

Pkg phfqit phfqit is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{phfqit}[2017/08/16]

\LetLtxMacro\LWR@origbitstring\bitstring

\renewcommand\bitstring[1]{%
\InlineClass[%
    text-decoration: overline underline ;
]{bitstring}{#1}%
% \phfqit@bitstring{#1}%
}

\appto\LWR@restoreorigformatting{%
\LetLtxMacro\bitstring\LWR@origbitstring%
}
```

File 375 **lwarp-physics.sty**

§ 483 Package physics

(*Emulates or patches code by* Sergio C. de la Barrera.)

Pkg physics physics works as-is for HTML with SVG math.

For MathJax, the MathJax v3 physics extension is used.

for HTML output:

```
\LWR@ProvidesPackagePass{physics}% No date is provided by the package.

\begin{warpMathJax}
\PackageWarningNoLine{lwarp, physics}{The MathJax v3 extension will be used}
\CustomizeMathJax{\require{physics}}
\end{warpMathJax}
```

File 376 **lwarp-physunits.sty**

§ 484 Package

physunits

(*Emulates or patches code by* Brian W. Mulligan.)

Pkg physunits physunits is supported as-is for SVG math, and is emulated for MathJax.

for HTML output:

```
\LWR@ProvidesPackagePass{physunits}[2020/03/26]

\begin{warpMathJax}
\LWR@infoprocessingmathjax{physunits}

\CustomizeMathJax{\newcommand{\micro}{\mu}}
\CustomizeMathJax{\newcommand{\V}[1][ ]{\,\mathrm{#1V}}}
\CustomizeMathJax{\newcommand{\Volt}[1][ ]{\,\mathrm{#1V}}}
\CustomizeMathJax{\newcommand{\Coulomb}[1][ ]{\,\mathrm{#1C}}}
\CustomizeMathJax{\newcommand{\esu}{\,\mathrm{esu}}}
\CustomizeMathJax{\newcommand{\Ohm}[1][ ]{\,\mathrm{#1\Omega}}}
\CustomizeMathJax{\newcommand{\Amp}[1][ ]{\,\mathrm{#1A}}}
\CustomizeMathJax{\newcommand{\Farad}[1][ ]{\,\mathrm{#1F}}}
\CustomizeMathJax{\newcommand{\Tesla}[1][ ]{\,\mathrm{#1T}}}
\CustomizeMathJax{\newcommand{\Gauss}[1][ ]{\,\mathrm{#1G}}}
\CustomizeMathJax{\newcommand{\Henry}[1][ ]{\,\mathrm{#1H}}}
\CustomizeMathJax{\newcommand{\eV}[1][ ]{\,\mathrm{#1eV}}}
\CustomizeMathJax{\newcommand{\keV}{\,\mathrm{keV}}}
\CustomizeMathJax{\newcommand{\MeV}{\,\mathrm{MeV}}}
\CustomizeMathJax{\newcommand{\J}[1][ ]{\,\mathrm{#1J}}}
\CustomizeMathJax{\newcommand{\Joule}[1][ ]{\,\mathrm{#1J}}}
\CustomizeMathJax{\newcommand{\erg}{\,\mathrm{erg}}}
\CustomizeMathJax{\newcommand{\kcal}{\,\mathrm{kcal}}}
\CustomizeMathJax{\newcommand{\Cal}{\,\mathrm{Cal}}}
\CustomizeMathJax{\newcommand{\calorie}[1][ ]{\,\mathrm{#1cal}}}
\CustomizeMathJax{\newcommand{\BTU}{\,\mathrm{BTU}}}
\CustomizeMathJax{\newcommand{\tnt}{\,\mathrm{ton\, of\, TNT}}}
\CustomizeMathJax{\newcommand{\Watt}[1][ ]{\,\mathrm{#1W}}}
\CustomizeMathJax{\newcommand{\hpi}{\,\mathrm{hp(I)}}}
\CustomizeMathJax{\newcommand{\hpm}{\,\mathrm{hp(M)}}}
\CustomizeMathJax{\newcommand{\hp}{\,\mathrm{hp}}}
\CustomizeMathJax{\newcommand{\meter}[1][ ]{\,\mathrm{#1m}}}
\CustomizeMathJax{\newcommand{\m}[1][ ]{\,\mathrm{#1m}}}
\CustomizeMathJax{\newcommand{\km}{\,\mathrm{km}}}
\CustomizeMathJax{\newcommand{\au}{\,\mathrm{au}}}
\CustomizeMathJax{\newcommand{\pc}[1][ ]{\,\mathrm{#1pc}}}
```

```
\CustomizeMathJax{\newcommand{\ly}[1][ ]{\,\mathrm{#1ly}}}
\CustomizeMathJax{\newcommand{\cm}{\,\mathrm{cm}}}
\CustomizeMathJax{\newcommand{\nm}{\,\mathrm{nm}}}
\CustomizeMathJax{\newcommand{\ft}{\,\mathrm{ft}}}
\CustomizeMathJax{\newcommand{\inch}{\,\mathrm{in}}}
\CustomizeMathJax{\newcommand{\mi}{\,\mathrm{mi}}}
\CustomizeMathJax{\newcommand{\s}[1][ ]{\,\mathrm{#1s}}}
\CustomizeMathJax{\newcommand{\Sec}[1][ ]{\,\mathrm{#1s}}}
\CustomizeMathJax{\newcommand{\Min}{\,\mathrm{min}}}
\CustomizeMathJax{\newcommand{\h}{\,\mathrm{h}}}
\CustomizeMathJax{\newcommand{\y}[1][ ]{\,\mathrm{#1y}}}
\CustomizeMathJax{\newcommand{\Day}{\,\mathrm{d}}}

\CustomizeMathJax{\newcommand{\gm}[1][ ]{\,\mathrm{#1g}}}
\CustomizeMathJax{\newcommand{\kg}{\,\mathrm{kg}}}
\CustomizeMathJax{\newcommand{\lb}{\,\mathrm{lb}}}
\CustomizeMathJax{\newcommand{\amu}{\,\mathrm{amu}}}
\CustomizeMathJax{\newcommand{\N}[1][ ]{\,\mathrm{#1N}}}
\CustomizeMathJax{\newcommand{\Newton}[1][ ]{\,\mathrm{#1N}}}
\CustomizeMathJax{\newcommand{\dyne}[1][ ]{\,\mathrm{#1dyn}}}
\CustomizeMathJax{\newcommand{\lbf}{\,\mathrm{lbf}}}
\CustomizeMathJax{\newcommand{\kmps}{\,\mathrm{km}\,\mathrm{s}^{-1}}}
\CustomizeMathJax{\newcommand{\kmph}{\,\mathrm{km}\,\mathrm{h}^{-1}}}
\CustomizeMathJax{\newcommand{\mps}[1][ ]{\,\mathrm{#1m}\,\mathrm{s}^{-1}}}
\CustomizeMathJax{\newcommand{\miph}{\,\mathrm{mi}\,\mathrm{h}^{-1}}}
\CustomizeMathJax{\newcommand{\kts}{\,\mathrm{kts}}}

\CustomizeMathJax{\newcommand{\mpss}[1][ ]{\,\mathrm{#1m}\,\mathrm{s}^{-2}}}
\CustomizeMathJax{\newcommand{\gacc}{\,\mathrm{g}}}
\CustomizeMathJax{\newcommand{\ftpss}{\,\mathrm{ft}\,\mathrm{s}^{-2}}}
\CustomizeMathJax{\newcommand{\K}[1][ ]{\,\mathrm{#1K}}}
\CustomizeMathJax{\newcommand{\Kelvin}[1][ ]{\,\mathrm{#1K}}}
\CustomizeMathJax{\newcommand{\Celcius}{\,^\circ{\mathrm{C}}}}
\CustomizeMathJax{\newcommand{\Rankine}{\,^\circ{\mathrm{R}}}}
\CustomizeMathJax{\newcommand{\Fahrenheit}{\,^\circ{\mathrm{F}}}}

\CustomizeMathJax{\newcommand{\rpm}{\,\mathrm{rev}\,\Min^{-1}}}

\CustomizeMathJax{\newcommand{\Hz}[1][ ]{\,\mathrm{#1Hz}}}
\CustomizeMathJax{\newcommand{\barP}[1][ ]{\,\mathrm{#1bar}}}
\CustomizeMathJax{\newcommand{\atm}{\,\mathrm{atm}}}
\CustomizeMathJax{\newcommand{\Pa}[1][ ]{\,\mathrm{#1Pa}}}
\CustomizeMathJax{\newcommand{\mmHg}{\,\mathrm{mmHg}}}
\CustomizeMathJax{\newcommand{\inHg}{\,\mathrm{inHg}}}
\CustomizeMathJax{\newcommand{\lbsi}{\,\mathrm{psi}}}
\CustomizeMathJax{\newcommand{\lbsf}{\,\mathrm{psf}}}
\CustomizeMathJax{\newcommand{\Ba}[1][ ]{\,\mathrm{#1Ba}}}
\CustomizeMathJax{\newcommand{\Torr}[1][ ]{\,\mathrm{#1Torr}}}
\CustomizeMathJax{\newcommand{\mol}{\,\mathrm{mol}}}
\end{warpMathJax}
```

File 377 **lwarp-picinpar.sty**

§ 485 Package

picinpar

(*Emulates or patches code by* Friedhelm Sowa.)

Pkg picinpar picinpar is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{picinpar}% No date is assigned.
```

The window is floated by a BlockClass style.

```
\long\def\LWR@HTML@window[#1,#2,#3,#4] {%
    \if #2r%
        \begin{BlockClass}[float:right](note){marginblock}%
    \else%
        \begin{BlockClass}[float:left](note){marginblock}%
    \fi%
    #3\par%
    #4%
    \end{BlockClass}%
}

\def\endLWR@HTML@window{}

\LWR@formattedenv{window}
```

The framepic and wframepic are placed inside a BlockClass of class framebox.

```
\def\LWR@HTML@framepic#1{%
    \begin{BlockClass}{framebox}
    \expandafter\box\csname #1box\endcsname%
    \end{BlockClass}
}
\LWR@formatted{framepic}

\def\LWR@HTML@wframepic#1{%
    \begin{BlockClass}{framebox}
    \expandafter\box\csname #1box\endcsname%
    \end{BlockClass}
}
\LWR@formatted{wframepic}
```

The caption is placed inside a BlockClass of class figurecaption.

```
\long\def\LWR@HTML@@makewincaption#1#2{%
\begin{BlockClass}{figurecaption}
#1: #2
\end{BlockClass}
}
\LWR@formatted{@makewincaption}
```

With HTML output, figwindow and tabwindow must not pre-decrement their counters.

```
\long\def\LWR@HTML@figwindow[#1,#2,#3,#4] {%
%       \advance\c@figure -1
```

```
     \window[#1,#2,{#3},{\def\@captype{figure}%
        \wincaption#4\par}] }

\def\endLWR@HTML@figwindow{\endwindow}

\LWR@formattedenv{figwindow}
```

For tabwindow, to change the catcode of &, \StartDefiningTabulars is used before absorbing the arguments, and \EndDefiningTabulars is used at the end of the environment.

```
\long\def\LWR@HTML@subtabwindow[#1,#2,#3,#4] {%
%      \advance\c@table -1
     \window[#1,#2,{#3},{\def\@captype{table}%
        \wincaption#4\par}] }

\newcommand*{\LWR@HTML@tabwindow}{%
    \StartDefiningTabulars%
    \LWR@HTML@subtabwindow%
}

\def\endLWR@HTML@tabwindow{%
    \endwindow%
    \StopDefiningTabulars%
}

\LWR@formattedenv{tabwindow}
```

File 378 **lwarp-pifont.sty**

§ 486 Package

pifont

(*Emulates or patches code by* Walter Schmidt.)

Pkg pifont pifont is patched for use by lwarp.

Hashed inline images are used, as there may not be Unicode support for all icons.

for HTML output:

```
\LWR@ProvidesPackagePass{pifont}[2005/04/12]

\renewcommand{\Pisymbol}[2]{%
    \begin{lateximage}*[Pisymbol][pisymbol#1#2]%
    {\Pifont{#1}\char#2}%
    \end{lateximage}%
}

\newcommand{\LWR@HTML@Pifill}[2]{
    \Pisymbol{#1}{#2} \Pisymbol{#1}{#2} \Pisymbol{#1}{#2}
}
\LWR@formatted{Pifill}

\newcommand{\LWR@HTML@Piline}[2]{%
    \par\noindent\hspace*{0.5in}
    \Pifill{#1}{#2} \Pifill{#1}{#2} \Pifill{#1}{#2}
```

```
}
\LWR@formatted{Piline}
```

File 379 **lwarp-pinlabel.sty**

§ 487 Package

pinlabel

(*Emulates or patches code by* Colin Rourke.)

Pkg pinlabel pinlabel is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{pinlabel}% no date given

\xpretocmd{\psfig}
    {\begin{lateximage}[-pinlabel-~\PackageDiagramAltText]}
    {}
    {\LWR@patcherror{pinlabel}{psfigA}}

\xapptocmd{\psfig}
    {\end{lateximage}}
    {}
    {\LWR@patcherror{pinlabel}{psfigB}}
```

File 380 **lwarp-placeins.sty**

§ 488 Package

placeins

(*Emulates or patches code by* Donald Arseneau.)

Pkg placeins placeins is ignored.

Discard all options for lwarp-placeins:

for HTML output:

```
\LWR@ProvidesPackageDrop{placeins}[2005/04/18]

\newcommand*{\FloatBarrier}{}
```

File 381 **lwarp-plarydshln.sty**

§ 489 Package

plarydshln

Pkg plarydshln plarydshln is emulated by lwarp-arydshln.

for HTML output:

```
\LWR@ProvidesPackageDrop{plarydshln}[2018/10/20]

\LWR@origRequirePackage{lwarp-arydshln}
```

File 382 **lwarp-plext.sty**

§ 490 Package

plext

Pkg plext

plext is preloaded by jtarticle and related classes.

for HTML output:

```
\LWR@loadbefore{plext}

\LWR@ProvidesPackagePass{plext}[2017/07/21]

\let\tate\relax

\DeclareExpandableDocumentCommand{\rensuji}{s o m}{#3}

% \layoutfloat(width,height)[pos]#4
\DeclareDocumentCommand{\layoutfloat}{d() o m}{}

% \DeclareLayoutCaption{type} <dir>(width)[pos1pos2]
\DeclareDocumentCommand{\DeclareLayoutCaption}{m d<> d() o}{}

\LetLtxMacro\pcaption\caption

% \layoutcaption<dir>(width)[pos]
\DeclareDocumentCommand{\layoutcaption}{d<> d() o}{}

\let\captiondir\relax
```

Add the optional <t/y> direction:

```
\RenewDocumentEnvironment{LWR@HTML@minipage}{d<> O{t} O{} O{t} m}
    {\LWR@HTML@sub@minipage{#2}{#3}{#4}{#5}}
    {\endLWR@HTML@sub@minipage}

\RenewDocumentCommand{\LWR@HTML@parbox}{d<> O{t} O{} O{t} m +m}
{
\LWR@traceinfo{parbox of width #4}%
\begin{minipage}[#2][#3][#4]{#5}%
#6
\end{minipage}%
}

% \pbox <t/y> [width] [l/r] {contents}
\RenewDocumentCommand{\pbox}{d<> O{0pt} O{c} m}{%
\global\booltrue{LWR@minipagefullwidth}%
\parbox{#2}{#4}%
}
```

picture, as modified by pext, is encapsulated by the lwarp core.

File 383 **lwarp-plextarydshln.sty**

§ 491 Package

plextarydshln

Pkg plextarydshln plextarydshln is emulated by lwarp-arydshln.

for HTML output:

```
\LWR@ProvidesPackageDrop{plextarydshln}[2018/10/20]
\LWR@origRequirePackage{lwarp-arydshln}
```

File 384 **lwarp-plextcolortbl.sty**

§ 492 Package

plextcolortbl

Pkg plextcolortbl plextcolortbl is emulated by lwarp-colortbl.

for HTML output:

```
\LWR@ProvidesPackageDrop{plextcolortbl}[2018/09/19]
\LWR@origRequirePackage{lwarp-colortbl}
```

File 385 **lwarp-plimsoll.sty**

§ 493 Package

plimsoll

(*Emulates or patches code by* Palle Jørgensen.)

Pkg plimsoll plimsoll is used as-is for SVG math, and emulated for MathJax.

The circ option is honored. For MathJax, \plimsollsans is the same as \plimsollroman.

for HTML output:

```
\LWR@ProvidesPackagePass{plimsoll}[2020/10/09]

\begin{warpMathJax}
\CustomizeMathJax{\newcommand{\plimsollroman}{\unicode{x029B5}}}

\CustomizeMathJax{\let\plimsoll\plimsollroman}
\CustomizeMathJax{\let\plimsollsans\plimsoll}

\ifdefstring{\stst}{^{\circ}}
    {\CustomizeMathJax{\newcommand{\stst}{^{\circ}}}}
    {\CustomizeMathJax{\newcommand{\stst}{^{\plimsoll}}}}
\end{warpMathJax}
```

File 386 **lwarp-prelim2e.sty**

§ 494 Package prelim2e

(*Emulates or patches code by* Martin Schröder.)

Pkg prelim2e prelim2e is ignored.

for HTML output: Discard all options for lwarp-prelim2e:

```
\LWR@ProvidesPackageDrop{prelim2e}[2009/05/29]

\newcommand{\PrelimText}{}
\newcommand{\PrelimTextStyle}{}
\newcommand{\PrelimWords}{}
```

File 387 **lwarp-prettyref.sty**

§ 495 Package prettyref

(*Emulates or patches code by* Kevin S. Ruland.)

Pkg prettyref prettyref is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{prettyref}[1998/07/09]

\newrefformat{fig}{Figure \ref{#1}}
\newrefformat{tab}{Table \ref{#1}}
```

File 388 **lwarp-preview.sty**

§ 496 Package preview

Pkg preview preview is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{preview}[2017/04/24]

\newenvironment{preview}{}{}
\newenvironment{nopreview}{}{}
\NewDocumentCommand{\PreviewMacro}{s o o +m}{}
\NewDocumentCommand{\PreviewEnvironment}{s o o +m}{}
\newcommand{\PreviewSnarfEnvironment}[2][]{}
\NewDocumentCommand{\PreviewOpen}{s o}{}
\NewDocumentCommand{\PreviewClose}{s o}{}
\let\ifPreview\iffalse% \fi for syntax highlighting
```

File 389 **lwarp-psfrag.sty**

§ 497 Package

psfrag

(*Emulates or patches code by* Michael C. Grant, David Carlisle.)

Pkg psfrag

psfrag is patched for use by lwarp.

⚠ use psfrags

The psfrags environment is modified to use lateximage to encapsulate the image. Always use a psfrags environment to contain any local \psfrag macros and the associated \includegraphics or \epsfig calls. Outside of a psfrags environment, psfrags adjustments will not be seen by lwarp.

⚠

Tip: Use a mono-spaced font for the tags in the eps file.

for HTML output:

```
\LWR@ProvidesPackagePass{psfrag}[1998/04/11]
```

A lateximage captures the modified image from the document.

```
\BeforeBeginEnvironment{psfrags}{%
    \begin{lateximage}[-psfrags-~\PackageDiagramAltText]%
}

\AfterEndEnvironment{psfrags}{\end{lateximage}}
```

File 390 **lwarp-psfragx.sty**

§ 498 Package

psfragx

(*Emulates or patches code by* Pascal Kockaert.)

Pkg psfragx

psfragx is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{psfragx}[2012/05/02]
```

A lateximage captures the modified image from the document.

```
\def\pfx@includegraphicx#1#2{%
    \begin{lateximage}[-psfragx-~\PackageDiagramAltText]%
    \mbox{\pfx@overpix{#1}{#2}\endpfx@overpix}%
    \end{lateximage}%
}

\def\@@@overpix[#1]<#2>[#3]#4{%
    \begin{lateximage}[-psfragx-~\PackageDiagramAltText]%
    \pfx@overpix{#1,ovpfgd={#2},ovpbgd={#3}}{#4}%
}

\def\endoverpix{%
    \endpfx@overpix%
    \end{lateximage}%
}
```

File 391 **lwarp-pst-eps.sty**

§ 499 Package

pst-eps

(*Emulates or patches code by* Herbert Voss.)

Pkg pst-eps pst-eps is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{pst-eps}[2005/05/20]

\renewenvironment{TeXtoEPS}{}{}
\renewcommand{\PSTtoEPS}[3][]{}
```

File 392 **lwarp-pstool.sty**

§ 500 Package

pstool

(*Emulates or patches code by* Zebb Prime, Will Robertson.)

Pkg pstool pstool is patched for use by lwarp.

\graphicspath is ignored, and the file directory must be stated.

⚠ path and filename The filename must not have a file extension.

Use

Enter ⇒ **lwarpmk html**

followed by

Enter ⇒ **lwarpmk limages**

.

for HTML output:

```
\LWR@ProvidesPackagePass{pstool}[2018/01/20]
```

Each image is placed inside a lateximage to capture the results of psfrag.

```
\renewcommand\pstool@alwaysprocess[3][]{%
    \begin{lateximage}[-pstool-~\PackageDiagramAltText]%
    \includegraphics{#2.pdf}%
    \end{lateximage}%
}
\LetLtxMacro\pstool@neverprocess\pstool@alwaysprocess
\LetLtxMacro\pstool@maybeprocess\pstool@alwaysprocess

\renewcommand\pstool@@psfragfig[4]{%
    \begin{lateximage}[-pstool-~\PackageDiagramAltText]%
```

```
12     \includegraphics{#2.pdf}%
13     \end{lateximage}%
14 }
```

File 393 **lwarp-pstricks.sty**

§ 501 Package

pstricks

(*Emulates or patches code by* Timothy Van Zandt.)

Pkg pstricks pstricks is patched for use by lwarp.

⚠ use pspicture All pstricks content should be contained inside a pspicture environment.

for HTML output:

```
1 \LWR@ProvidesPackagePass{pstricks}[2018/01/06]

2 \BeforeBeginEnvironment{pspicture}{%
3     \begin{lateximage}[pspicture]%
4 }
5 \AfterEndEnvironment{pspicture}{\end{lateximage}}
6
7 \BeforeBeginEnvironment{pspicture*}{%
8     \begin{lateximage}[pspicture]%
9 }
10 \AfterEndEnvironment{pspicture*}{\end{lateximage}}
```

File 394 **lwarp-pxatbegshi.sty**

§ 502 Package

pxatbegshi

Pkg pxatbegshi pxatbegshi is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{pxatbegshi}[2017/11/04]

2 \LWR@origRequirePackage{lwarp-atbegshi}
```

File 395 **lwarp-pxeveryshi.sty**

§ 503 Package

pxeveryshi

Pkg pxeveryshi pxeveryshi is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{pxeveryshi}[2012/05/19]

2 \LWR@origRequirePackage{lwarp-everyshi}
```

File 396 **lwarp-pxfonts.sty**

§ 504 Package pxfonts

(*Emulates or patches code by* Young Ryu.)

Pkg pxfonts pxfonts is used as-is for SVG math, and is emulated for MathJax.

for HTML output:

```
\LWR@ProvidesPackagePass{pxfonts}[2008/01/22]
```

For MathJax:

```
\LWR@origRequirePackage{lwarp-common-mathjax-letters}

\begin{warpMathJax}
\LWR@infoprocessingmathjax{pxfonts}

\LWR@mathjax@addgreek@l@up{}{up}
\end{warpMathJax}
```

File 397 **lwarp-pxftnright.sty**

§ 505 Package pxftnright

Pkg pxftnright pxftnright is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{pxftnright}[2017/02/28]

\LWR@origRequirePackage{lwarp-ftnright}
```

File 398 **lwarp-pxjahyper.sty**

§ 506 Package pxjahyper

Pkg pxjahyper pxjahyper is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{pxjahyper}[2018/07/15]
```

File 399 **lwarp-quotchap.sty**

§ 507 Package quotchap

(*Emulates or patches code by* Karsten Tinnefeld, Jan Klever.)

Pkg quotchap

quotchap is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{quotchap}[2019/07/09]

\newcommand{\@quotchap}{}
\newlength{\LWR@quotchapwidth}

\let\@printcites\relax

\newcommand*{\@iprintcites}{%
```

Place the quotes inside a of class quotchap, of the maximum selected width:

```
\begin{BlockClass}[max-width: \LWR@printlength{\LWR@quotchapwidth}]{quotchap}
%\begin{minipage}{\LWR@quotchapwidth}
\@quotchap
%\end{minipage}
\end{BlockClass}
```

Deactivate the quote printing:

```
\global\let\@printcites\relax
}

\NewEnviron{savequote}[1][\linewidth]{%
```

Remember the width, adjusted for HTML, and make the length assignment global, per:
https://tex.stackexchange.com/questions/300823/why-is-setlength-ineffective-inside-a-tabular-environment

```
\setlength{\LWR@quotchapwidth}{#1*2}%
\global\LWR@quotchapwidth=\LWR@quotchapwidth%
```

Remember the body, and activate the quote printing:

```
\global\let\@quotchap\BODY
\global\let\@printcites\@iprintcites%
}
```

The quotation author is placed inside a of class qauthor:

```
\newcommand{\qauthor}[1]{%
    \LWR@stoppars%
    \begin{BlockClass}{qauthor}%
    {#1}%
    \end{BlockClass}%
    \LWR@startpars%
}
```

Fonts are ignored. Use CSS.

```
\newcommand{\qsetcnfont}[1]{}
\providecommand*{\quotefont}{}
\providecommand*{\qauthorfont}{}
```

File 400 **lwarp-quoting.sty**

§ 508 Package quoting

(*Emulates or patches code by* Thomas Titz.)

Pkg quoting quoting is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{quoting}[2014/01/28]

\xpatchcmd{\quoting}{\quo@begintext}
    {\begin{LWR@blocktextcurrentfont}\quo@begintext}
    {}
    {\LWR@patcherror{quoting}{quoting}}

\xpatchcmd{\endquoting}{\quo@endtext}
    {\quo@endtext\end{LWR@blocktextcurrentfont}\LWR@stoppars}
    {}
    {\LWR@patcherror{quoting}{endquoting}}
```

File 401 **lwarp-ragged2e.sty**

§ 509 Package ragged2e

(*Emulates or patches code by* Martin Schröder.)

Pkg ragged2e ragged2e is emulated.

Discard all options for lwarp-ragged2e:

for HTML output:

```
\LWR@ProvidesPackageDrop{ragged2e}[2009/05/21]

\LetLtxMacro\Centering\centering
\LetLtxMacro\RaggedLeft\raggedleft
\LetLtxMacro\RaggedRight\raggedright
\newcommand*{\justifying}{}
\newlength{\CenteringLeftskip}
\newlength{\RaggedLeftLeftskip}
\newlength{\RaggedRightLeftskip}
\newlength{\CenteringRightskip}
\newlength{\RaggedLeftRightskip}
\newlength{\RaggedRightRightskip}
\newlength{\CenteringParfillskip}
\newlength{\RaggedLeftParfillskip}
\newlength{\RaggedRightParfillskip}
\newlength{\JustifyingParfillskip}
\newlength{\CenteringParindent}
\newlength{\RaggedLeftParindent}
\newlength{\RaggedRightParindent}
```

```
\newlength{\JustifyingParindent}
\newenvironment*{Center}{\center}{\endcenter}
\newenvironment*{FlushLeft}{\flushleft}{\endflushleft}
\newenvironment*{FlushRight}{\flushright}{\endflushright}
\newenvironment*{justify}{\justifying}{\endjustifying}
```

File 402 **lwarp-realscripts.sty**

§ 510 Package

realscripts

(*Emulates or patches code by* Will Robertson.)

Pkg realscripts realscripts is emulated. See `lwarp.css` for the of class supsubscript.

for HTML output:

```
\LWR@ProvidesPackagePass{realscripts}[2016/02/13]
```

The following are copied verbatim from the original, but given new names, since xparse definitions should not be `\let`.

```
\ExplSyntaxOn

\DeclareDocumentCommand \LWR@print@realsubscript {m} {
  \fontspec_if_fontspec_font:TF {
    \fontspec_if_opentype:TF
    { \fontspec_if_feature:nTF {+subs}
        { {\addfontfeature{VerticalPosition=Inferior}#1} }
        { \fontspec_if_feature:nTF {+sinf}
            { {\addfontfeature{VerticalPosition=ScientificInferior}#1} }
            { \fakesubscript{#1} }
        }
    }
    { \fontspec_if_aat_feature:nnTF {10} {2}
        { {\addfontfeature{VerticalPosition=Inferior}#1} }
        { \fakesubscript{#1} }
    }
  }
  { \fakesubscript{#1} }
}

\DeclareDocumentCommand \LWR@HTML@realsubscript {m} {
    \LWR@HTML@textsubscript{#1}
}

\LWR@formatted{realsubscript}


\DeclareDocumentCommand \LWR@print@realsuperscript {m} {
  \fontspec_if_fontspec_font:TF
  {
    \fontspec_if_opentype:TF
    { \fontspec_if_feature:nTF {+sups}
      { {\addfontfeature{VerticalPosition=Superior}#1} }
      { \fakesuperscript{#1} }
```

```
    }
    { \fontspec_if_aat_feature:nnTF {10} {1}
      { {\addfontfeature{VerticalPosition=Superior}#1} }
      { \fakesuperscript{#1} }
    }
  }
  { \fakesuperscript{#1} }
}

\DeclareDocumentCommand \LWR@HTML@realsuperscript {m} {
    \LWR@HTML@textsuperscript{#1}
}

\LWR@formatted{realsuperscript}


\DeclareDocumentCommand \LWR@print@textsubsuperscript {s O{l} mm} {
  \leavevmode
  \group_begin:
  \IfBooleanTF #1
  {
    \hbox_set:Nn \l_tmpa_box {\textsubscript*{#3}}
    \hbox_set:Nn \l_tmpb_box {\textsuperscript*{#4}}
  }
  {
    \hbox_set:Nn \l_tmpa_box {\textsubscript{#3}}
    \hbox_set:Nn \l_tmpb_box {\textsuperscript{#4}}
  }
  \hbox_set:Nn \l_tmpa_box
    { \box_move_down:nn \subsupersep {\box_use:N \l_tmpa_box} }
  \hbox_set:Nn \l_tmpb_box
    { \box_move_up:nn \subsupersep {\box_use:N \l_tmpb_box} }
  \str_case:nnF {#2}
  {
    {l}{\use_i:nnn}
    {c}{\use_ii:nnn}
    {r}{\use_iii:nnn}
  }
  {
    \PackageWarning{realscripts}{
      Unknown~alignment~option~`#2'. \MessageBreak
      One~ of~ `l',~ `c',~ `r',~ only
    }
    \use_i:nnn
  }
  {
    \hbox_overlap_right:n { \box_use:N \l_tmpa_box }
    \hbox_overlap_right:n { \box_use:N \l_tmpb_box }
    \skip_horizontal:n {
      \dim_max:nn {\box_wd:N \l_tmpa_box} {\box_wd:N \l_tmpb_box}
    }
  }
  {
    \dim_compare:nTF { \box_wd:N \l_tmpa_box > \box_wd:N \l_tmpb_box }
    {
```

```
      \skip_horizontal:n {
        0.5\box_wd:N \l_tmpa_box-0.5\box_wd:N \l_tmpb_box
      }
      \box_use:N \l_tmpb_box
      \skip_horizontal:n {
        -0.5\box_wd:N \l_tmpa_box-0.5\box_wd:N \l_tmpb_box
      }
      \box_use:N \l_tmpa_box
    }
    {
      \skip_horizontal:n {
        0.5\box_wd:N \l_tmpb_box-0.5\box_wd:N \l_tmpa_box
      }
      \box_use:N \l_tmpa_box
      \skip_horizontal:n {
        -0.5\box_wd:N \l_tmpb_box-0.5\box_wd:N \l_tmpa_box
      }
      \box_use:N \l_tmpb_box
    }
  }
  {
    \skip_horizontal:n {
      \dim_max:nn {\box_wd:N \l_tmpa_box} {\box_wd:N \l_tmpb_box}
    }
    \hbox_overlap_left:n { \box_use:N \l_tmpa_box }
    \hbox_overlap_left:n { \box_use:N \l_tmpb_box }
  }
  \group_end:
}

\ExplSyntaxOff


\newcommand*{\LWR@realscriptsalign}{}

\newcommand*{\LWR@setrealscriptsalign}[1]{%
    \renewcommand*{\LWR@realscriptsalign}{}%
    \ifthenelse{\equal{#1}{c}}{%
        \renewcommand{\LWR@realscriptsalign}{%
            \LWR@print@mbox{text-align:center} ; %
        }%
    }{}%
    \ifthenelse{\equal{#1}{r}}{%
        \renewcommand{\LWR@realscriptsalign}{%
            \LWR@print@mbox{text-align:right} ; %
        }%
    }{}%
}

\DeclareDocumentCommand \LWR@HTML@textsubsuperscript {s O{l} mm} {%
    \LWR@setrealscriptsalign{#2}%
    \InlineClass[\LWR@realscriptsalign]{supsubscript}{%
        \textsuperscript{#4}\textsubscript{#3}%
    }%
}
```

```
\LWR@formatted{textsubsuperscript}

\FilenameNullify{%
    \RenewDocumentCommand{\textsuperscript}{s m}{}%
    \RenewDocumentCommand{\textsubscript}{s m}{}%
    \renewcommand{\fakesubscript}[1]{}%
    \renewcommand{\fakesuperscript}[1]{}%
    \renewcommand{\realsubscript}[1]{}%
    \renewcommand{\realsuperscript}[1]{}%
    \renewcommand{\textsubsuperscript}[2]{}%
    \renewcommand{\textsupersubscript}[2]{}%
}
```

File 403 **lwarp-refcheck.sty**

§ 511 Package refcheck

Pkg refcheck refcheck is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{refcheck}[2013/02/14]

\def\showrefnames{}
\def\norefnames{}
\def\showcitenames{}
\def\nocitenames{}
\def\setonmsgs{}
\def\setoffmsgs{}
\def\checkunlbld{}
\def\ignoreunlbld{}
\newcommand*{\refcheckxrdoc}[2][]{}
```

File 404 **lwarp-register.sty**

§ 512 Package register

(*Emulates or patches code by* Matthew Lovell.)

Pkg register register is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{register}[2019/01/01]

\xpatchcmd{\register}
    {\centering}
    {%
        \begin{center}%
        \begin{lateximage}[-register-~\PackageDiagramAltText]%
    }
    {}
    {\LWR@patcherror{register}{register}}

```

```
\xpatchcmd{\endregister}
    {\leftskip}
    {%
        \end{lateximage}\end{center}%
        \leftskip%
    }%
    {}
    {\LWR@patcherror{register}{endregister}}

\expandafter\xapptocmd\csname register*\endcsname
    {%
        \begin{center}%
        \begin{lateximage}[-register-~\PackageDiagramAltText]%
    }
    {}
    {\LWR@patcherror{register}{register*}}

\expandafter\xpatchcmd\csname endregister*\endcsname
    {\leftskip}
    {%
        \end{lateximage}\end{center}%
        \leftskip%
    }%
    {}
    {\LWR@patcherror{register}{endregister*}}

\setlength{\regWidth}{5in}
```

File 405 **lwarp-relsize.sty**

§ 513 Package

relsize

(*Emulates or patches code by* Donald Arseneau, Bernie Cosell, Matt Swift.)

Pkg relsize relsize is patched for use by lwarp, and emulated for MathJax.

For HTML, only the inline macros are supported: \textlarger, \textsmaller, and \textscale. Each becomes an inline span of a modified font-size.

\relsize, \larger, \smaller, and \relscale are ignored.

While creating SVG math for HTML, the original definitions are temporarilty restored, and so should work as expected.

⚠ not small The HTML browser's setting for minumum font size may limit how small the output will be displayed.

for HTML output:

```
\LWR@ProvidesPackagePass{relsize}[2013/03/29]

\let\LWR@origrelsize\relsize
\LetLtxMacro\LWR@origlarger\larger
\LetLtxMacro\LWR@origsmaller\smaller
\let\LWR@relscale\relscale
```

```
\LetLtxMacro\LWR@origtextlarger\textlarger
\LetLtxMacro\LWR@origtextsmaller\textsmaller
\let\LWR@textscale\textscale

\appto\LWR@restoreorigformatting{%
\let\relsize\LWR@origrelsize%
\LetLtxMacro\larger\LWR@origlarger%
\LetLtxMacro\smaller\LWR@origsmaller%
\let\relscale\LWR@relscale%
\LetLtxMacro\textlarger\LWR@origtextlarger%
\LetLtxMacro\textsmaller\LWR@origtextsmaller%
\let\textscale\LWR@textscale%
}

\newcounter{LWR@relsizetemp}

\renewcommand*{\relsize}[1]{}
\renewcommand*{\larger}[1][]{}
\renewcommand*{\smaller}[1][]{}
\renewcommand*{\relscale}[1]{}

\renewcommand*{\textlarger}[2][1]{%
\setcounter{LWR@relsizetemp}{100+(#1*20)}%
\InlineClass[font-size:\arabic{LWR@relsizetemp}\%]{textlarger}{#2}%
}

\renewcommand*{\textsmaller}[2][1]{%
\setcounter{LWR@relsizetemp}{100-(#1*20)}%
\InlineClass[font-size:\arabic{LWR@relsizetemp}\%]{textsmaller}{#2}%
}

\renewcommand*{\textscale}[2]{%
\setcounter{LWR@relsizetemp}{100*\real{#1}}%
\InlineClass[font-size:\arabic{LWR@relsizetemp}\%]{textscale}{#2}%
}
```

For MathJax:

```
\begin{warpMathJax}
\CustomizeMathJax{\newcommand{\mathlarger}[1]{#1}}
\CustomizeMathJax{\newcommand{\mathsmaller}[1]{#1}}
\end{warpMathJax}
```

File 406 **lwarp-repeatindex.sty**

§ 514 Package

repeatindex

Pkg repeatindex repeatindex is emulated for lwarp.

⚠ style file lwarp must be used with a special style file:

```
\usepackage[makeindex,makeindexStyle={lwarp_repeatindex}]{lwarp}
```

where `lwarp_repeatindex.ist` may be copied from the following modified version of `lwarp.ist`:

```
preamble
"\\begin{theindex}
  \\providecommand*\\lettergroupDefault[1]{}
  \\providecommand*\\lettergroup[1]{%
      \\par\\textbf{#1}\\par
      \\nopagebreak
  }
"
headings_flag 1
heading_prefix "
  \\lettergroup{"
heading_suffix "}"
delim_0 "], \\hyperindexref{"
delim_1 ", \\hyperindexref{"
delim_2 ", \\hyperindexref{"
delim_n "}, \\hyperindexref{"
delim_r "} -- \\hyperindexref{"
delim_t "}"

item_0 "\n  \\item ["
```

(The modifications are the `delim_0` and `item_0` entries.)

for HTML output:

```
\LWR@ProvidesPackageDrop{repeatindex}[2001/10/13]
```

In the lwarp core, `\LWR@indexitem` is modified to accept the optional `\item` argument.

```
\RequirePackage{makeidx}
\def\entryprefix{\itshape}
\def\entrypostfix{\dots}
```

File 407 **`lwarp-repltext.sty`**

§ 515 Package

repltext

Pkg `repltext`

repltext is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{repltext}[2020/09/25]

\newcommand{\repltext}[2]{#2}
\newcommand*{\prevrepl}{}
```

For MathJax:

```
\begin{warpMathJax}
\CustomizeMathJax{\newcommand{\repltext}[2]{#2}}
\end{warpMathJax}
```

File 408 **lwarp-resizegather.sty**

§ 516 Package
# resizegather

Pkg resizegather resizegather is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{resizegather}[2016/05/16]

\newcommand*{\resizegathersetup}[1]{}
```

File 409 **lwarp-returntogrid.sty**

§ 517 Package
# returntogrid

Pkg returntogrid returntogrid is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{returntogrid}[2018/08/21]

\NewDocumentCommand\returntogrid{ O {} }{}
\NewDocumentCommand\returntogridsetup { m } {}
\NewDocumentCommand\showdebugpagegrid {} {}
```

File 410 **lwarp-rlepsf.sty**

§ 518 Package
# rlepsf

(*Emulates or patches code by* Michael Greene, Colin Rourke.)

Pkg rlepsf rlepsf is patched for use by lwarp.

⚠ Rename the style file! The file `rlepsf.tex` must be copied to `rlepsf.sty` for lwarp to detect and patch it.

for HTML output:

```
\LWR@ProvidesPackagePass{rlepsf}% No date given.

\xpretocmd{\relabelbox}
    {\begin{lateximage}}
    {}
    {\LWR@patcherror{rlepsf}{relabelbox}}

\xapptocmd{\endrelabelbox}
    {\end{lateximage}}
    {}
    {\LWR@patcherror{rlepsf}{endrelabelbox}}
```

File 411 **lwarp-rmathbr.sty**

§ 519 Package rmathbr

(*Emulates or patches code by* Denis Ryabov.)

Pkg rmathbr rmathbr is used as-is for SVG math, and emulated for MathJax.

for HTML output:

```
\LWR@ProvidesPackagePass{rmathbr}[2020/12/11]

\begin{warpMathJax}
\CustomizeMathJax{\def\*{~}}
\CustomizeMathJax{\newcommand{\cdott}{\cdot}}
\CustomizeMathJax{\newcommand{\nobr}{}}
\end{warpMathJax}
```

File 412 **lwarp-rmpage.sty**

§ 520 Package rmpage

Pkg rmpage rmpage is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{rmpage}[1997/09/29]
```

File 413 **lwarp-romanbar.sty**

§ 521 Package romanbar

(*Emulates or patches code by* H.-Martin Münch.)

Pkg romanbar romanbar is patched for use by lwarp.

An inline class with an overline and underline is used.

for HTML output:

```
\LWR@ProvidesPackagePass{romanbar}[2012/01/01]

\DeclareRobustCommand{\Roman@bar}[1]{% #1 is in Roman, i.e. MMXII
\InlineClass[%
    text-decoration: overline underline ;
]{romanbar}{#1}%
}
```

File 414 **lwarp-romanbarpagenumber.sty**

§ 522 Package romanbarpagenumber

Pkg romanbarpagenumber romanbarpagenumber is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{romanbarpagenumber}[2015/02/06]
```

File 415 **lwarp-rotating.sty**

§ 523 Package rotating

(*Emulates or patches code by* Robin Fairbairns, Sebastian Rahtz, Leonor Barroca.)

Pkg rotating rotating is emulated.

All rotations are ignored in HTML output.

for HTML output:

```
\LWR@ProvidesPackagePass{rotating}[2016/08/11]
\RequirePackage{graphicx}

\LetLtxMacro\LWR@HTML@sidewaystable\table
\let\endLWR@HTML@sidewaystable\endtable
\LWR@formattedenv{sidewaystable}

\LetLtxMacro\LWR@HTML@sidewaysfigure\figure
\let\endLWR@HTML@sidewaysfigure\endfigure
\LWR@formattedenv{sidewaysfigure}

\newenvironment*{LWR@HTML@sideways}{}{}
\LWR@formattedenv{sideways}

\newenvironment*{LWR@HTML@turn}[1]{}{}
\LWR@formattedenv{turn}

\newenvironment*{LWR@HTML@rotate}[1]{}{}
\LWR@formattedenv{rotate}

\NewDocumentCommand{\LWR@HTML@turnbox}{m +m}{#2}
\LWR@formatted{turnbox}

\let\LWR@HTML@rotcaption\caption
\LWR@formatted{rotcaption}

\let\LWR@HTML@@makerotcaption\@makecaption
\LWR@formatted{@makerotcaption}
```

File 416 **lwarp-rotfloat.sty**

§ 524 Package rotfloat

(*Emulates or patches code by* Axel Sommerfeldt.)

Pkg rotfloat rotfloat is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{rotfloat}[2004/01/04]

\RequirePackage{float}
\RequirePackage{rotating}
```

\newfloat {⟨*1: type*⟩} {⟨*2: placement*⟩} {⟨*3: ext*⟩} [⟨*4: within*⟩]

Emulates the \newfloat command from the float package. Sideways floats are \let to the same as regular floats.

"placement" is ignored.

```
\RenewDocumentCommand{\newfloat}{m m m o}{%
\IfValueTF{#4}%
{%
    \DeclareFloatingEnvironment[fileext=#3,within=#4]{#1}%
}%
{%
    \DeclareFloatingEnvironment[fileext=#3]{#1}%
}%
\csletcs{sideways#1}{#1}%
\csletcs{endsideways#1}{end#1}%
```

Remember the float style:

```
\csedef{LWR@floatstyle@#1}{\LWR@floatstyle}%
\csedef{LWR@floatstyle@sideways#1}{\LWR@floatstyle}%
```

newfloat package automatically creates the \listof command for new floats, but float does not, so remove \listof here in case it is manually created later:

```
\cslet{listof#1s}\relax%
\cslet{listof#1es}\relax%
\cslet{listofsideways#1s}\relax%
\cslet{listofsideways#1es}\relax%
}
```

File 417 **lwarp-rviewport.sty**

§ 525 Package

rviewport

Pkg rviewport rviewport is honored inside a lateximage, and otherwise ignored for HTML output.

If rviewport is important for an image, enclose the image inside a lateximage environment.

for HTML output:

```
\LWR@ProvidesPackagePass{rviewport}[2011/08/27]

\define@key{igraph}{rviewport}{}
```

File 418 **lwarp-savetrees.sty**

§ 526 Package savetrees

Pkg savetrees savetrees is ignored.

for HTML output: Discard all options for lwarp-savetrees:

```
\LWR@ProvidesPackageDrop{savetrees}[2016/04/13]
```

File 419 **lwarp-scalefnt.sty**

§ 527 Package scalefnt

(*Emulates or patches code by* D. Carlisle.)

Pkg scalefnt scalefnt is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{scalefnt}
\DeclareRobustCommand\scalefont[1]{}
```

File 420 **lwarp-scalerel.sty**

§ 528 Package scalerel

(*Emulates or patches code by* Steven B. Segletes.)

Pkg scalerel scalerel is used as-is for SVG math, and is emulated and ignored for MathJax.

for HTML output:

```
\LWR@ProvidesPackagePass{scalerel}[2016/12/29]
```

For MathJax:

```
\begin{warpMathJax}
\LWR@infoprocessingmathjax{scalerel}

\CustomizeMathJax{\newcommand{\scalerel}{\ifstar{\scalerelplain}{\scalerelplus}}}
\CustomizeMathJax{\newcommand{\scalerelplain}[3][]{#2}}
\CustomizeMathJax{\newcommand{\scalerelplus}[3][]{#2#3}}
\CustomizeMathJax{\newcommand{\stretchrel}{\ifstar{\stretchrelplain}{\stretchrelplus}}}
\CustomizeMathJax{\newcommand{\stretchrelplain}[3][]{#2}}
\CustomizeMathJax{\newcommand{\stretchrelplus}[3][]{#2#3}}
\CustomizeMathJax{\newcommand{\scaleto}[3][]{#2}}
\CustomizeMathJax{\newcommand{\stretchto}[3][]{#2}}
\CustomizeMathJax{\newcommand{\scaleleftright}[4][]{#2#3#4}}
```

```
\CustomizeMathJax{\newcommand{\stretchleftright}[4][]{#2#3#4}}
\CustomizeMathJax{\newcommand{\hstretch}[2]{#2}}
\CustomizeMathJax{\newcommand{\vstretch}[2]{#2}}
\CustomizeMathJax{\newcommand{\scaleobj}[2]{#2}}
\CustomizeMathJax{\newcommand{\ThisStyle}[1]{#1}}
\CustomizeMathJax{\newcommand{\SavedStyle}{}}
\CustomizeMathJax{\def\scriptstyleScaleFactor{.7}}
\CustomizeMathJax{\def\scriptscriptstyleScaleFactor{.5}}
\CustomizeMathJax{\newcommand{\discernmathstyle}{}}
\CustomizeMathJax{\newcommand{\ignoremathstyle}[1][T]{}}
\CustomizeMathJax{\newcommand{\Isnextbyte}[3][v]{}}
\end{warpMathJax}
```

File 421 **lwarp-schemata.sty**

§ 529 Package schemata

(*Emulates or patches code by* Charles P. Schaum.)

Pkg schemata schemata is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{schemata}[2020/11/23]

\LetLtxMacro\LWR@schemata@origschema\schema
\LetLtxMacro\LWR@schemata@origSchema\Schema

\renewcommand{\schema}[3][open]{%
    \begin{lateximage}[-schemata-~\PackageDiagramAltText]%
    \LWR@print@normalsize%
    \LWR@schemata@origschema[#1]{#2}{#3}%
    \end{lateximage}%
}

\renewcommand{\Schema}[5][open]{%
    \begin{lateximage}[-schemata-~\PackageDiagramAltText]%
    \LWR@print@normalsize%
    \LWR@schemata@origSchema[#1]{#2}{#3}{#4}{#5}%
    \end{lateximage}%
}
```

File 422 **lwarp-scrextend.sty**

§ 530 Package scrextend

Pkg scrextend scrextend is emulated.

This package may be loaded standalone, but is also loaded automatically if koma-script classes are in use. \DeclareDocumentCommand is used to overwrite the koma-script definitions.

for HTML output:

```
\LWR@ProvidesPackageDrop{scrextend}[2020/01/24]
```

```
\DeclareDocumentCommand{\setkomafont}{m m}{}
\DeclareDocumentCommand{\addkomafont}{m m}{}
\DeclareDocumentCommand{\usekomafont}{m}{}

\DeclareDocumentCommand{\usefontofkomafont}{m}{}
\DeclareDocumentCommand{\useencodingofkomafont}{m}{}
\DeclareDocumentCommand{\usesizeofkomafont}{m}{}
\DeclareDocumentCommand{\usefamilyofkomafont}{m}{}
\DeclareDocumentCommand{\useseriesofkomafont}{m}{}
\DeclareDocumentCommand{\useshapeofkomafont}{m}{}

\providecommand*{\coverpagetopmargin}{}
\providecommand*{\coverpagebottommargin}{}
\providecommand*{\coverpageleftmargin}{}
\providecommand*{\coverpagerightmargin}{}

```

Title page:

```
\AtBeginDocument{
    \let\LWR@koma@orig@maketitle\maketitle
    \DeclareDocumentCommand{\maketitle}{o}{\LWR@koma@orig@maketitle}
}

\DeclareDocumentCommand{\@maketitle}{}{%
    \ifdefvoid{\@titlehead}{}{%
        \begin{BlockClass}{titlehead}%
        \@titlehead%
        \end{BlockClass}%
    }%
    \ifdefvoid{\@subject}{}{%
        \begin{BlockClass}{subject}%
        \@subject%
        \end{BlockClass}%
    }%
    \LWR@stoppars%
    \LWR@htmltag{\LWR@tagtitle}%
    \@title%
    \LWR@htmltag{\LWR@tagtitleend}%
    \ifdefvoid{\@subtitle}{}{%
        \begin{BlockClass}{subtitle}%
        \@subtitle%
        \end{BlockClass}%
    }%
    \LWR@startpars%
    \begin{BlockClass}{author}%

    \renewcommand*{\cr}{}%
    \renewcommand*{\crcr}{}%
    \renewcommand*{\noalign}{}%

        \renewcommand{\and}{%
            \end{BlockClass}%
            \begin{BlockClass}{oneauthor}%
        }%
```

```
        \begin{BlockClass}{oneauthor}%
            \@author%
        \end{BlockClass}%
    \end{BlockClass}%
    \begin{BlockClass}{titledate}%
    \@date%
    \end{BlockClass}%
    \ifdefvoid{\@published}{}{%
        \begin{BlockClass}{published}%
        \@published%
        \end{BlockClass}%
    }%
}

\AddSubtitlePublished

\DeclareDocumentCommand{\extratitle}{m}{}
\DeclareDocumentCommand{\frontispiece}{m}{}

\def\@titlehead{}%
\DeclareDocumentCommand{\titlehead}{m}{\gdef\@titlehead{#1}}%

\def\@subject{}%
\DeclareDocumentCommand{\subject}{m}{\gdef\@subject{#1}}%

% \subtitle and \published are defined by \AddSubtitlePublished

\DeclareDocumentCommand{\publishers}{m}{\published{#1}}

\DeclareDocumentCommand{\uppertitleback}{m}{}
\DeclareDocumentCommand{\lowertitleback}{m}{}
\DeclareDocumentCommand{\dedication}{m}{}

\DeclareDocumentCommand{\ifthispageodd}{m m}{#1}

\DeclareDocumentCommand{\cleardoublepageusingstyle}{m}{}
\DeclareDocumentCommand{\cleardoubleemptypage}{}{}
\DeclareDocumentCommand{\cleardoubleplainpage}{}{}
\DeclareDocumentCommand{\cleardoublestandardpage}{}{}
\DeclareDocumentCommand{\cleardoubleoddpage}{}{}
\DeclareDocumentCommand{\cleardoubleoddpageusingstyle}{m}{}
\DeclareDocumentCommand{\cleardoubleoddemptypage}{}{}
\DeclareDocumentCommand{\cleardoubleoddplainpage}{}{}
\DeclareDocumentCommand{\cleardoubleoddstandardpage}{}{}
\DeclareDocumentCommand{\cleardoubleevenpage}{}{}
\DeclareDocumentCommand{\cleardoubleevenpageusingstyle}{m}{}
\DeclareDocumentCommand{\cleardoubleevenemptypage}{}{}
\DeclareDocumentCommand{\cleardoubleevenplainpage}{}{}
\DeclareDocumentCommand{\cleardoubleevenstandardpage}{}{}

\DeclareDocumentCommand{\multiplefootnoteseparator}{}{%
  \begingroup\let\thefootnotemark\multfootsep\@makefnmark\endgroup
}

\DeclareDocumentCommand{\multfootsep}{}{,}
```

```
\DeclareDocumentCommand{\footref}{m}{%
  \begingroup
    \unrestored@protected@xdef\@thefnmark{\ref{#1}}%
  \endgroup
  \@footnotemark
}

\DeclareDocumentCommand{\deffootnote}{o m m m}{}
\DeclareDocumentCommand{\deffootnotemark}{m}{}
\DeclareDocumentCommand{\setfootnoterule}{o m}{}
\DeclareDocumentCommand{\raggedfootnote}{}{}


\DeclareDocumentCommand{\dictum}{o m}{
\begin{LWR@BlockClassWP}{\LWR@print@mbox{text-align:right}}{}{dictum}
    #2
    \IfValueT{#1}
    {
        \LWR@stoppars%
        \ifbool{FormatWP}
     {\begin{BlockClass}[\LWR@print@mbox{border-top:} 1px solid gray]{dictumauthor}}
        {\begin{BlockClass}{dictumauthor}}
        \dictumauthorformat{#1}
        \end{BlockClass}
    }
\end{LWR@BlockClassWP}
}

\DeclareDocumentCommand{\dictumwidth}{}{}
\DeclareDocumentCommand{\dictumauthorformat}{m}{(#1)}
\DeclareDocumentCommand{\dictumrule}{}{}
\DeclareDocumentCommand{\raggeddictum}{}{}
\DeclareDocumentCommand{\raggeddictumtext}{}{}
\DeclareDocumentCommand{\raggeddictumauthor}{}{}

\DeclareDocumentEnvironment{labeling}{o m}
{%
\def\sc@septext{#1}%
\list{}{}%
\let\makelabel\labelinglabel%
}
{
\endlist
}

\DeclareDocumentCommand{\labelinglabel}{m}{%
#1 \qquad \sc@septext%
}

\let\addmargin\relax
\let\endaddmargin\relax
\cslet{addmargin*}{\relax}
\cslet{endaddmargin*}{\relax}
```

```
\NewDocumentEnvironment{addmargin}{s O{} m}
{
\LWR@stoppars%
\setlength{\LWR@templengthtwo}{#3}
\ifblank{#2}
{
    \begin{BlockClass}[
        \LWR@print@mbox{margin-left:\LWR@printlength{\LWR@templengthtwo}} ;
        \LWR@print@mbox{margin-right:\LWR@printlength{\LWR@templengthtwo}}
    ]{addmargin}
}
{
    \setlength{\LWR@templengthone}{#2}
    \begin{BlockClass}[
        \LWR@print@mbox{margin-left:\LWR@printlength{\LWR@templengthone}} ;
        \LWR@print@mbox{margin-right:\LWR@printlength{\LWR@templengthtwo}}
    ]{addmargin}
}
}
{\end{BlockClass}\LWR@startpars}
```

Ref to create a starred environment:
https://tex.stackexchange.com/questions/45401/use-the-s-star-argument-with-newdocumentenvironment

```

\ExplSyntaxOn
\cs_new:cpn {addmargin*} {\addmargin*}
\cs_new_eq:cN {endaddmargin*} \endaddmargin
\ExplSyntaxOff

\DeclareDocumentCommand{\marginline}{m}{\marginpar{#1}}
```

File 423 **lwarp-scrhack.sty**

§ 531 Package scrhack

Pkg scrhack scrhack is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{scrhack}[2018/03/30]
```

File 424 **lwarp-scrlayer.sty**

§ 532 Package scrlayer

(*Emulates or patches code by* Markus Kohm.)

Pkg scrlayer scrlayer is emulated.

⚠ Not fully tested! Please send bug reports!

for HTML output:

```
\LWR@ProvidesPackageDrop{scrlayer}[2018/03/30]

\newcommand*{\DeclareSectionNumberDepth}[2]{}
\newcommand*{\DeclareLayer}[2][]{}
\newcommand*{\DeclareNewLayer}[2][]{}
\newcommand*{\ProvideLayer}[2][]{}
\newcommand*{\RedeclareLayer}[2][]{}
\newcommand*{\ModifyLayer}[2][]{}
\newcommand*{\layerhalign}{}
\newcommand*{\layervalign}{}
\newcommand*{\layerxoffset}{}
\newcommand*{\layeryoffset}{}
\newcommand*{\layerwidth}{}
\newcommand*{\layerheight}{}
\providecommand*{\LenToUnit}[1]{\strip@pt\dimexpr#1*\p@/\unitlength}
\newcommand*{\putUL}[1]{}
\newcommand*{\putUR}[1]{}
\newcommand*{\putLL}[1]{}
\newcommand*{\putLR}[1]{}
\newcommand*{\putC}[1]{}
\newcommand*{\GetLayerContents}[1]{}
\newcommand{\IfLayerExists}[3]{#3}
\newcommand*{\DestroyLayer}[1]{}
\newcommand*{\layercontentsmeasure}{}
\newcommand*{\currentpagestyle}{}
\newcommand*{\BeforeSelectAnyPageStyle}[1]{}
\newcommand*{\AfterSelectAnyPageStyle}[1]{}
\newcommand*{\DeclarePageStyleAlias}[2]{}
\newcommand*{\DeclareNewPageStyleAlias}[2]{}
\newcommand*{\ProvidePageStyleAlias}[2]{}
\newcommand*{\RedeclarePageStyleAlias}[2]{}
\newcommand*{\DestroyPageStyleAlias}[1]{}
\newcommand*{\GetRealPageStyle}[1]{}
\newcommand*{\DeclarePageStyleByLayers}[3][]{}
\newcommand*{\DeclareNewPageStyleByLayers}[3][]{}
\newcommand*{\ProvidePageStyleByLayers}[3][]{}
\newcommand*{\RedeclarePageStyleByLayers}[3][]{}
\NewDocumentCommand{\ForEachLayerOfPageStyle}{s m m}{}
\newcommand*{\AddLayersToPageStyle}[2]{}
\newcommand*{\AddLayersAtBeginOfPageStyle}[2]{}
\newcommand*{\AddLayersAtEndOfPageStyle}[2]{}
\newcommand*{\RemoveLayersFromPageStyle}[2]{}
\newcommand*{\AddLayersToPageStyleBeforeLayer}[3]{}
\newcommand*{\AddLayersToPageStyleAfterLayer}[3]{}
\newcommand*{\UnifyLayersAtPageStyle}[1]{}
\newcommand*{\ModifyLayerPageStyleOptions}[2]{}
\newcommand*{\AddToLayerPageStyleOptions}[2]{}
\newcommand{\IfLayerPageStyleExists}[3]{#3}
\newcommand{\IfRealLayerPageStyleExists}[3]{#3}
\newcommand{\IfLayerAtPageStyle}[4]{#4}
\newcommand{\IfSomeLayerAtPageStyle}[4]{#4}
\newcommand{\IfLayersAtPageStyle}[4]{#4}
\newcommand*{\DestroyRealLayerPageStyle}[1]{}
\@ifundefined{footheight}{\newlength\footheight}{}
\DeclareDocumentCommand{\automark}{s o m}{}
```

```
\DeclareDocumentCommand{\manualmark}{}{}
\DeclareDocumentCommand{\MakeMarkcase}{m}{#1}

\newcommand{\partmarkformat}{}
\if@chapter
\newcommand{\chaptermarkformat}{}
\fi
\newcommand{\sectionmarkformat}{}
\DeclareDocumentCommand{\GenericMarkFormat}{m}{}

\newcommand*{\@mkleft}[1]{}
\newcommand*{\@mkright}[1]{}
\newcommand*{\@mkdouble}[1]{}
\newcommand*{\@mkboth}[2]{}
\newcommand*{\scrlayerInitInterface}[1][]{}
\newcommand{\scrlayerAddToInterface}[3][]{}
\newcommand{\scrlayerAddCsToInterface}[3][]{}
\newcommand{\scrlayerOnAutoRemoveInterface}[2][]{}
```

File 425 **lwarp-scrlayer-notecolumn.sty**

§ 533 Package scrlayer-notecolumn

(*Emulates or patches code by* Markus Kohm.)

Pkg scrlayer-notecolumn scrlayer-notecolumn is emulated.

⚠ Not fully tested! Please send bug reports!

for HTML output:

```
\LWR@ProvidesPackageDrop{scrlayer-notecolumn}[2018/02/02]

\newcommand*{\DeclareNoteColumn}[2][]{}
\newcommand*{\DeclareNewNoteColumn}[2][]{}
\newcommand*{\ProvideNoteColumn}[2][]{}
\newcommand*{\RedeclareNoteColumn}[2][]{}
\NewDocumentCommand{\makenote}{s o m}{\marginpar{#3}}
\newcommand*{\syncwithnotecolumn}[1][]{}
\newcommand*{\syncwithnotecolumns}[1][]{}
\newcommand*{\clearnotecolumn}[1][]{}
\newcommand*{\clearnotecolumns}[1][]{}
```

File 426 **lwarp-scrlayer-scrpage.sty**

§ 534 Package scrlayer-scrpage

(*Emulates or patches code by* Markus Kohm.)

Pkg scrlayer-scrpage scrlayer-scrpage is ignored.

⚠ Not fully tested! Please send bug reports!

for HTML output:

```
\LWR@ProvidesPackageDrop{scrlayer-scrpage}[2018/03/30]

\@ifundefined{footheight}{\newlength\footheight}{}
\NewDocumentCommand{\lehead}{s o m}{}
\NewDocumentCommand{\cehead}{s o m}{}
\NewDocumentCommand{\rehead}{s o m}{}
\NewDocumentCommand{\lohead}{s o m}{}
\NewDocumentCommand{\cohead}{s o m}{}
\NewDocumentCommand{\rohead}{s o m}{}
\NewDocumentCommand{\lefoot}{s o m}{}
\NewDocumentCommand{\cefoot}{s o m}{}
\NewDocumentCommand{\refoot}{s o m}{}
\NewDocumentCommand{\lofoot}{s o m}{}
\NewDocumentCommand{\cofoot}{s o m}{}
\NewDocumentCommand{\rofoot}{s o m}{}
\NewDocumentCommand{\ohead}{s o m}{}
\NewDocumentCommand{\chead}{s o m}{}
\NewDocumentCommand{\ihead}{s o m}{}
\NewDocumentCommand{\ofoot}{s o m}{}
\NewDocumentCommand{\cfoot}{s o m}{}
\NewDocumentCommand{\ifoot}{s o m}{}

\NewDocumentCommand{\automark}{som}{}
\newcommand*{\manualmark}{}

\DeclareDocumentCommand{\MakeMarkcase}{m}{#1}

\let\headmark\leftmark
\providecommand{\pnumfont}{\normalfont}%
\DeclareRobustCommand\pagemark{{\pnumfont{\thepage}}}%

\newcommand*{\defpairofpagestyles}[3][]{}
\newcommand*{\newpairofpagestyles}[3][]{}
\newcommand*{\renewpairofpagestyles}[3][]{}
\newcommand*{\providepairofpagestyles}[3][]{}

\newcommand*{\clearmainofpairofpagestyles}{}
\newcommand*{\clearplainofpairofpagestyles}{}
\newcommand*{\clearpairofpagestyles}{}
\newcommand*{\clearscrheadings}{}
\newcommand*{\clearscrheadfoot}{}
\newcommand*{\clearscrplain}{}

\NewDocumentCommand{\deftriplepagestyle}{m o o m m m m m m}{}
\NewDocumentCommand{\newtriplepagestyle}{m o o m m m m m m}{}
\NewDocumentCommand{\renewtriplepagestyle}{m o o m m m m m m}{}
\NewDocumentCommand{\providetriplepagestyle}{m o o m m m m m m}{}
\newcommand*{\defpagestyle}[3]{}
\newcommand*{\newpagestyle}[3]{}
\newcommand*{\providepagestyle}[3]{}
\newcommand*{\renewpagestyle}[3]{}
```

File 427 **lwarp-scrpage2.sty**

§ 535 Package

scrpage2

(*Emulates or patches code by* Markus Kohm.)

Pkg scrpage2 scrpage2 is ignored.

⚠ Not fully tested! Please send bug reports!

for HTML output:

```
\LWR@ProvidesPackageDrop{scrpage2}[2018/03/30]

\@ifundefined{footheight}{\newlength\footheight}{}
\NewDocumentCommand{\lehead}{o m}{}
\NewDocumentCommand{\cehead}{o m}{}
\NewDocumentCommand{\rehead}{o m}{}
\NewDocumentCommand{\lohead}{o m}{}
\NewDocumentCommand{\cohead}{o m}{}
\NewDocumentCommand{\rohead}{o m}{}
\NewDocumentCommand{\lefoot}{o m}{}
\NewDocumentCommand{\cefoot}{o m}{}
\NewDocumentCommand{\refoot}{o m}{}
\NewDocumentCommand{\lofoot}{o m}{}
\NewDocumentCommand{\cofoot}{o m}{}
\NewDocumentCommand{\rofoot}{o m}{}
\NewDocumentCommand{\ohead}{o m}{}
\NewDocumentCommand{\chead}{o m}{}
\NewDocumentCommand{\ihead}{o m}{}
\NewDocumentCommand{\ofoot}{o m}{}
\NewDocumentCommand{\cfoot}{o m}{}
\NewDocumentCommand{\ifoot}{o m}{}
\DeclareDocumentCommand{\automark}{o m}{}
\DeclareDocumentCommand{\manualmark}{}{}
\DeclareDocumentCommand{\MakeMarkcase}{m}{#1}
\NewDocumentCommand{\deftripstyle}{m o o m m m m m}{}
\NewDocumentCommand{\defpagestyle}{s m m m}{}
\NewDocumentCommand{\newpagestyle}{s m m m}{}
\NewDocumentCommand{\renewpagestyle}{s m m m}{}
\NewDocumentCommand{\providepagestyle}{s m m m}{}
\newcommand{\partmarkformat}{}
\if@chapter
\newcommand{\chaptermarkformat}{}
\fi
\newcommand{\sectionmarkformat}{}
\newcommand{\subsectionmarkformat}{}
\newcommand{\subsubsectionmarkformat}{}
\newcommand{\paragraphmarkformat}{}
\newcommand{\subparagraphmarkformat}{}

\newcommand*{\clearscrheadings}{}
\newcommand*{\clearscrheadfoot}{}
\newcommand*{\clearscrplain}{}
```

File 428 **lwarp-section.sty**

§ 536 Package section

Pkg section section is ignored.

(*Emulates or patches code by* Oliver Pretzel.)

for HTML output:

```
\LWR@ProvidesPackageDrop{section}

\ifx\chapter\undefined
 \def\chsize{\Large}\def\hdsize{\huge}\else
 \def\chsize{\huge}\def\hdsize{\Huge}
\fi
\let\ttsize\LARGE
\let\ausize\large
\let\dasize\large
\let\secsize\Large
\let\subsize\large
\let\hdpos\raggedright
\newcounter{hddepth}
\let\fpind\relax
\def\ttfnt{}
\def\hdfnt{}
\def\fefnt{}
\def\thfnt{}
\def\pgfnt{}
\def\hmkfnt{}
\let\mkcse\uppercase
\def\hddot{}
\def\cpdot{:}
\def\nmdot{}
\ifx\secindent\undefined
 \newdimen\secindent
 \newskip\secpreskp
 \newskip\secpstskp
 \newdimen\subindent
 \newskip\subpreskp
 \newskip\subpstskp
 \newskip\parpstskp
 \newcount\c@hddepth
\fi
```

File 429 **lwarp-sectionbreak.sty**

§ 537 Package sectionbreak

(*Emulates or patches code by* Michal Hoftich.)

Pkg sectionbreak sectionbreak is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{sectionbreak}[2018-01-03]

\renewcommand\asterism{\HTMLunicode{2042}}

\renewcommand\pre@sectionbreak{}
\renewcommand\post@sectionbreak{}

\renewcommand\print@sectionbreak[1]{%
\begin{center}
#1
\end{center}
}

```

File 430 **lwarp-sectsty.sty**

§ 538 Package

sectsty

(*Emulates or patches code by* Rowland McDonnell.)

Pkg sectsty sectsty is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{sectsty}[2002/02/25]

\newcommand*{\partfont}          [1] {}
\newcommand*{\partnumberfont}    [1] {}
\newcommand*{\parttitlefont}     [1] {}
\newcommand*{\chapterfont}       [1] {}
\newcommand*{\chapternumberfont} [1] {}
\newcommand*{\chaptertitlefont}  [1] {}
\newcommand*{\sectionfont}       [1] {}
\newcommand*{\subsectionfont}    [1] {}
\newcommand*{\subsubsectionfont} [1] {}
\newcommand*{\paragraphfont}     [1] {}
\newcommand*{\subparagraphfont}  [1] {}
\newcommand*{\minisecfont}  [1] {}
\newcommand*{\allsectionsfont}[1] {}
\newcommand{\nohang}{}
```

`\sectionrule` is only to be used in `*font` commands, thus it is ignored.

```
\newcommand*{\sectionrule}[5]{}

\def\ulemheading#1#2{}
```

File 431 **lwarp-selectp.sty**

§ 539 Package

selectp

Pkg selectp selectp is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{selectp}% no date given
\newcommand*{\outputonly}[1]{}
```

File 432 **lwarp-semantic-markup.sty**

§ 540 Package

semantic-markup

(*Emulates or patches code by* Andrew A. Cashner.)

Pkg semantic-markup semantic-markup is patched for use by lwarp.

⚠ If using the endnotes option, add \theendnotes where desired.

for HTML output:

```
\LWR@ProvidesPackagePass{semantic-markup}[2018/05/21]
```

The endnotes must be printed by the user before the end of the document, since the end is after the HTML footer, etc.

```
\ifendnotes
\RenewDocumentCommand{\SetupEndnotes}{}{%
    \let\footnote=\endnote
%     \AtEndDocument{\DoBeforeEndnotes{\EndnoteFont\theendnotes}}%
}
\fi
```

HTML unicode characters from musicography are used.

```
\RequirePackage{musicography}

\let\fl\musFlat
\let\sh\musSharp
\let\na\musNatural
```

The \musfig is placed inside a hashed image, with a simple alt tag.

```
\RequirePackage{amsmath}

\RenewDocumentCommand{\musfig}{ m m }{%
    \LWR@subsingledollar*%
        {#1/#2}% alt tag
        {musfig}% addl' hashing
        {% contents
            \LWR@origensuredmath{%
                \genfrac{}{}{0pt}{1}{\text{#1}}{\text{#2}}%
            }%
        }%
}
```

The `\meter` is taken from musicography, and becomes a hashed image with a simple `alt` tag.

```
\RenewDocumentCommand{\meter}{ m m }{%
    \musMeter{#1}{#2}%
}
```

File 433 **lwarp-seqsplit.sty**

§ 541 Package

seqsplit

(*Emulates or patches code by* Boris Veytsman.)

Pkg seqsplit seqsplit is patched for use by lwarp.

For HTML output, the results are similar to print mode, and respond to window size.

⚠ SVG math results For SVG math, the output differs from print mode in that the contents are formatted in a minipage, which is then inline with the surrounding math.

For MathJax, the contents are used as-is.

for HTML output:

```
\LWR@ProvidesPackagePass{seqsplit}[2006/08/07]
```

Special handling because lwarp uses a box for SVG math, which does not normally allow line breaks, so a print-mode `minipage` must be used to allow line breaks. The `minipage` will not be wrapped inline with any surrounding math.

```
\begin{warpHTML}
\LetLtxMacro\LWR@orig@seqsplit\seqsplit

\renewcommand*{\seqsplit}[1]{%
    \ifmmode%
        \begin{LWR@print@minipage}{6in}%
        \LWR@orig@seqsplit{#1}%
        \end{LWR@print@minipage}%
    \else%
        \InlineClass[word-wrap:break-word]{seqsplit}{\LWR@orig@seqsplit{#1}}%
    \fi
}
```

Between characters, an empty HTML comment is placed to allow a line wrap in the HTML source, without adding spaces in the output.

```
\AtBeginDocument{
    \newcommand*{\LWR@HTML@seqinsert}{%
        \LWR@htmlcomment{ }%
    }
    \LWR@formatted{seqinsert}
}
\end{warpHTML}

\begin{warpMathJax}
```

```
\CustomizeMathJax{\newcommand{\seqsplit}[1]{#1}}
\end{warpMathJax}
```

File 434 **lwarp-setspace.sty**

§ 542 Package

setspace

(*Emulates or patches code by* Robin Fairbairns.)

Pkg setspace setspace is emulated.

Discard all options for lwarp-setspace:

for HTML output:

```
\LWR@ProvidesPackageDrop{setspace}[2011/12/19]

\newcommand*{\setstretch}[1]{}
\newcommand*{\SetSinglespace}[1]{}
\newcommand*{\singlespacing}{}
\newcommand*{\onehalfspacing}{}
\newcommand*{\doublespacing}{}

\newenvironment*{singlespace}
{
\LWR@forcenewpage
\BlockClass{singlespace}
}
{\endBlockClass}

\newenvironment*{singlespace*}
{
\LWR@forcenewpage
\BlockClass{singlespace}
}
{\endBlockClass}

\newenvironment*{spacing}[1]{

}{

}

\newenvironment*{onehalfspace}
{
\LWR@forcenewpage
\BlockClass{onehalfspace}
}
{\endBlockClass}

\newenvironment*{doublespace}
{
\LWR@forcenewpage
\BlockClass{doublespace}
}
{\endBlockClass}
```

File 435 **lwarp-shadethm.sty**

§ 543 Package shadethm

(*Emulates or patches code by* Jim Hefferon.)

Pkg shadethm shadethm is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{shadethm}[1999/11/23]

\newenvironment{LWR@HTML@shadebox}
{%
    \convertcolorspec{named}{shadethmcolor}{HTML}\LWR@tempcolor%
    \convertcolorspec{named}{shaderulecolor}{HTML}\LWR@tempcolortwo%
    \begin{BlockClass}[%
        background: \LWR@origpound\LWR@tempcolor ;
        border: 1px solid \LWR@origpound\LWR@tempcolortwo ;
    ]{shadebox}
}%
{\end{BlockClass}}
\LWR@formattedenv{shadebox}
```

File 436 **lwarp-shadow.sty**

§ 544 Package shadow

(*Emulates or patches code by* Mauro Orlandini.)

Pkg shadow shadow is emulated.

for HTML output: Discard all options for lwarp-shadow:

```
\LWR@ProvidesPackageDrop{shadow}[2003/02/19]

\newdimen\sboxsep
\newdimen\sboxrule
\newdimen\sdim

\newcommand{\shabox}[1]{%
\InlineClass{shabox}{#1}%
}
```

File 437 **lwarp-shapepar.sty**

§ 545 Package shapepar

(*Emulates or patches code by* Donald Arseneau.)

Pkg shapepar shapepar is patched for use by lwarp. Shapes appear in print mode, as well as inside a `latexmage`, but are ignored for HTML.

for HTML output:

```
\LWR@ProvidesPackagePass{shapepar}[2013/03/26]

\newcommand*{\LWR@HTML@shapepar}[2][]{}
\LWR@formatted{shapepar}

\NewDocumentCommand{\LWR@HTML@cutout}{m d()}{}
\LWR@formatted{cutout}
```

File 438 **lwarp-showidx.sty**

§ 546 Package showidx

Pkg showidx showidx is ignored.

for HTML output: Discard all options for lwarp-showidx:

```
\LWR@ProvidesPackageDrop{showidx}[2014/09/29]
```

`\@wrindex` is redefined `\AtBeginDocument` by the lwarp core.

File 439 **lwarp-showkeys.sty**

§ 547 Package showkeys

(*Emulates or patches code by* David Carlisle, Morten Høgholm.)

Pkg showkeys showkeys is ignored.

for HTML output: Discard all options for lwarp-showkeys:

```
\LWR@ProvidesPackageDrop{showkeys}[2014/10/28]

\NewDocumentCommand{\showkeys}{s}{}
```

File 440 **lwarp-showtags.sty**

§ 548 Package showtags

Pkg showtags showtags is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{showtags}% no version is given

\newcommand{\thecitetag}[1]{}
```

File 441 **lwarp-shuffle.sty**

§ 549 Package

shuffle

(*Emulates or patches code by* Julian Gilbey and Antoine Lejay.)

Pkg shuffle

shuffle is emulated for SVG math, and also emulated for MathJax.

The font used for shuffle may not render correctly when converted to SVG math, so a `picture` environment drawing is used instead.

For MathJax, the Unicode character is used, and for `\cshuffle` a `\bar` is added.

for HTML output:

```
\LWR@ProvidesPackageDrop{shuffle}[2008/10/27]
\LWR@origRequirePackage{lwarp-common-mathjax-overlaysymbols}

\newcommand*{\LWR@shuffle@start}{%
    \hspace*{.2em}
    \begin{picture}(.75,0.65)
    \setlength{\unitlength}{1em}
    \put(0,0){\line(1,0){.75}}
    \put(0,0){\line(0,1){.5}}
    \put(.375,0){\line(0,1){.5}}
    \put(.75,0){\line(0,1){.5}}
}

\newcommand*{\LWR@shuffle@finish}{%
    \end{picture}
    \hspace*{.75em}
    \hspace*{.2em}
}

\newcommand*{\shuffle}{%
    \LWR@shuffle@start%
    \LWR@shuffle@finish%
}

\newcommand*{\cshuffle}{%
    \LWR@shuffle@start%
    \put(.05,.65){\line(1,0){.65}}%
    \LWR@shuffle@finish%
}


\begin{warpMathJax}
\CustomizeMathJax{\newcommand{\shuffle}{\mathbin{\unicode{0x29E2}}}}
\CustomizeMathJax{\newcommand{\cshuffle}{%
    \mathbin{\LWRoverlaysymbols{\raise{.6ex}{-}}{\unicode{0x29E2}}}%
}}
\end{warpMathJax}
```

File 442 **lwarp-sidecap.sty**

§ 550 Package sidecap

(*Emulates or patches code by* Rolf Niepraschk, Hubert Gässlein.)

Pkg sidecap sidecap is emulated.

for HTML output: Discard all options for lwarp-sidecap.

```
\LWR@ProvidesPackageDrop{sidecap}[2003/06/06]
```

See:
http://tex.stackexchange.com/questions/45401/use-the-s-star-argument-with-newdocumentenvironment
regarding the creation of starred environments with xparse.

```
\NewDocumentEnvironment{SCtable}{soo}
{\IfValueTF{#3}{\table[#3]}{\table}}
{\endtable}

\ExplSyntaxOn
\cs_new:cpn {SCtable*} {\SCtable*}
\cs_new_eq:cN {endSCtable*} \endSCtable
\ExplSyntaxOff


\NewDocumentEnvironment{SCfigure}{soo}
{\IfValueTF{#3}{\figure[#3]}{\figure}}
{\endfigure}

\ExplSyntaxOn
\cs_new:cpn {SCfigure*} {\SCfigure*}
\cs_new_eq:cN {endSCfigure*} \endSCfigure
\ExplSyntaxOff


\newenvironment*{wide}{}{}
```

File 443 **lwarp-sidenotes.sty**

§ 551 Package sidenotes

(*Emulates or patches code by* Andy Thomas, Oliver Schebaum.)

Pkg sidenotes Patched for lwarp.

for HTML output: Load the original package:

```
\LWR@ProvidesPackagePass{sidenotes}
```

The following patch sidenotes for use with lwarp.

An ARIA note role is not assigned since the caption is an important part of the figure.

\sidecaption * [⟨*entry*⟩] [⟨*offset*⟩] {⟨*text*⟩}

```
\RenewDocumentCommand \sidecaption {s o o m}
{
   \LWR@stoppars
   \begingroup
  \captionsetup{style=sidecaption}%
  \IfBooleanTF{#1}
  { % starred
   \begin{BlockClass}[border:none ; box-shadow:none]{marginblock}%
   \caption*{#4}%
   \end{BlockClass}
  }
  { % unstarred
  \IfNoValueOrEmptyTF{#2}
   {\def\@sidenotes@sidecaption@tof{#4}}
   {\def\@sidenotes@sidecaption@tof{#2}}
   \begin{BlockClass}[border:none ; box-shadow:none]{marginblock}%
   \caption[\@sidenotes@sidecaption@tof]{#4}
   \end{BlockClass}
  }
   \endgroup
   \LWR@startpars
}
```

Borrowed from the lwarp version of keyfloat:

```
\NewDocumentEnvironment{KFLTsidenotes@marginfloat}{O{-1.2ex} m}
{% start
   \LWR@BlockClassWP{float:right; width:2in; margin:10pt}{}{marginblock}%
   \renewcommand*{\@captype}{#2}%
}
{%
   \endLWR@BlockClassWP%
}

\RenewDocumentEnvironment{marginfigure}{o}
  {\begin{KFLTsidenotes@marginfloat}{figure}}
  {\end{KFLTsidenotes@marginfloat}}

\RenewDocumentEnvironment{margintable}{o}
  {\begin{KFLTsidenotes@marginfloat}{table}}
  {\end{KFLTsidenotes@marginfloat}}
```

The following were changed by sidenotes, and now are reset back to their lwarp-supported originals:

Restoring the definition from the LaTeX 2_ε `article.cls` source:

```
\renewenvironment{figure*}
               {\@dblfloat{figure}}
               {\end@dblfloat}
```

```
\renewenvironment{table*}
                 {\@dblfloat{table}}
                 {\end@dblfloat}
```

For MathJax:

⚠ Note that sidenotes does not support `\sidenote` inside math in print mode. Use `\sidenotemark` and `\sidenotetext` instead.

```
\begin{warpMathJax}
\providecommand{\sidenotename}{sidenote}
\appto\LWR@syncnotenumbers{\LWR@synconenotenumber{LWRsidenote}{\thesidenote}}
\appto\LWR@syncnotenames{\LWR@synconenotename{LWRsidenote}{\sidenotename}}
\CustomizeMathJax{\def\LWRsidenote{1}}
\CustomizeMathJax{\newcommand{\sidenotemark}[1][\LWRsidenote]{{}^{\mathrm{#1}}}}
\end{warpMathJax}
```

The following is not defined since is not allowed inside math in print mode, and also would have to be modified to parse the optional offset argument:

```
\CustomizeMathJax{\newcommand{\sidenote}[2][\LWRsidenote]{{}^{\mathrm{#1}}}}
```

File 444 **lwarp-simplebnf.sty**

§ 552 Package

simplebnf

(*Emulates or patches code by* Jay Lee.)

Pkg simplebnf simplebnf is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{simplebnf}[2020/09/01]
```

The entire object is placed inside a `lateximage` whose `alt` text is the LaTeX source BNF expression.

```
\ExplSyntaxOn

\RenewDocumentEnvironment { bnfgrammar } { +b }
 {
   %% \l__input_seq is a list of term definitions.
   \regex_split:nnN { ;; } { #1 } \l__input_seq
   \begin{center}
   \begin{lateximage}[#1]%     lwarp
     \tl_set:Nn \l__table_tl
       {
         \begin{tabular}{lcll}
       }
   \bool_set_true:N \l_tmp_first_term % Is this the first term in this grammar?
   \seq_map_inline:Nn \l__input_seq
     {
       %% \l__term_seq    - (term, rhses)...
```

```
        %% \l__term_tl     - term
        %% \l__keypairs_tl - rhses
        \regex_split:nnN { ::= } { ##1 } \l__term_seq
        \seq_pop_left:NN \l__term_seq \l__term_tl
        \seq_pop_left:NN \l__term_seq \l__keypairs_tl

        \regex_replace_once:nnN { ^\s+ } {} \l__term_tl

        \bool_if:NTF \l_tmp_first_term
          {
            \bool_set_false:N \l_tmp_first_term
          }
          {
            \tl_put_right:Nn \l__table_tl { \\ }
          }
        \tl_put_right:Nx \l__table_tl
          {
            \bnfexpr { \l__term_tl } & \g__simplebnf_defeq_tl &
          }
        %% \l__keypairs_seq - (rhs:annot | rhs)...
        \seq_set_split:NnV \l__keypairs_seq { | } \l__keypairs_tl

        \bool_set_true:N \l__first_rhs
        \seq_map_function:NN \l__keypairs_seq \simplebnf_typeset_rhs:n
      }

    \tl_put_right:Nn \l__table_tl { \end{tabular} }
    \tl_use:N \l__table_tl
    \end{lateximage}%       lwarp
    \end{center}
  }
  { }

\ExplSyntaxOff
```

File 445 **lwarp-SIunits.sty**

§ 553 Package

SIunits

(*Emulates or patches code by* Marcel Heldoorn.)

Pkg SIunits SIunits is patched for use by lwarp.

For SVG math, it is recommended to use `\unit` where possible, which combines the entire expression into a single `lateximage`, and adds the `alt` tag containing the LaTeX code, allowing for copy/paste. When units are used outside of the `\unit` macro, each unit macro will have its own `lateximage`, and each will have the `alt` tag set according to `\MathImageAltText`, which defaults to `(math image)`.

For MathJax, individual units used in text will appear as SVG images, since `\ensuremath` is used in the original defintions, and `\ensuremath` often has expressions which do not work well in MathJax, so it is always forced to an SVG image. If, however, `\unit` is used, the result is expressed with MathJax instead of an SVG image.

for HTML output:

```
\LWR@ProvidesPackagePass{SIunits}[2007/12/02]
```

Patched for copy/paste with the HTML `alt` tag:

```
\ifbool{mathjax}{
    \DeclareRobustCommand{\LWR@HTML@unit}[2]{%
        \LWR@subsingledollar*%  lwarp
        {% alt tag
            \textbackslash{}unit\{\LWR@HTMLsanitize{#1}\}%
                \{ \LWR@HTMLsanitize{#2}\}% extra space
        }%
        {SIunits}% add'l hashing
        {%
            #1\,{#2}%
        }% contents
    }
}{% not MathJax
    \DeclareRobustCommand{\LWR@HTML@unit}[2]{%
        \@inunitcommandtrue%    original
        \LWR@subsingledollar*%  lwarp
        {% alt tag
            \textbackslash{}unit\{\LWR@HTMLsanitize{#1}\}%
                \{ \LWR@HTMLsanitize{#2}\}% extra space
        }%
        {SIunits}% add'l hashing
        {%
            \LWR@origensuredmath{%  lwarp modification
                \SI@fstyle{%
                    {#1}\@qsk\period@active{#2}%
                }%  original
            }%
        }% contents
        \@inunitcommandfalse%   original
    }
}% not MathJax
\LWR@formatted{unit}
```

For MathJax:

```
\begin{warpMathJax}
\LWR@infoprocessingmathjax{SIunits}

\CustomizeMathJax{\newcommand{\one}{}}
\CustomizeMathJax{\newcommand{\meter}{\metre}}
\CustomizeMathJax{\newcommand{\deka}{\deca}}
\CustomizeMathJax{\newcommand{\dekad}{\decad}}
\CustomizeMathJax{\newcommand{\per}{/}}
\CustomizeMathJax{\newcommand{\usk}{\;}}
\CustomizeMathJax{\newcommand{\unit}[2]{#1\,{#2}}}
\CustomizeMathJax{\newcommand{\power}[2]{#1^{#2}}}

\AtBeginDocument{%
 \if@redefsquare
  \CustomizeMathJax{\renewcommand{\square}[1]{\power{#1}{2}}}
 \else
```

```
   \if@defsquaren
    \CustomizeMathJax{\newcommand{\squaren}[1]{\power{#1}{2}}}
   \else
     \CustomizeMathJax{\renewcommand{\square}[1]{\power{#1}{2}}}
   \fi %\if@defsquaren
 \fi   %\if@redefsquare
}     %\AtBeginDocument

\CustomizeMathJax{\newcommand{\squared}{^{2}}}
\CustomizeMathJax{\newcommand{\cubic}[1]{\power{#1}{3}}}
\CustomizeMathJax{\newcommand{\cubed}{^{3}}}
\CustomizeMathJax{\newcommand{\fourth}[1]{\power{#1}{4}}}
\CustomizeMathJax{\newcommand{\reciprocal}[1]{\power{#1}{-1}}}
\CustomizeMathJax{\newcommand{\rp}{\reciprocal}}
\CustomizeMathJax{\newcommand{\rpsquare}[1]{\power{#1}{-2}}}
\CustomizeMathJax{\newcommand{\rpsquared}{^{-2}}}
\CustomizeMathJax{\newcommand{\rpcubic}[1]{\power{#1}{-3}}}
\CustomizeMathJax{\newcommand{\rpcubed}{^{-3}}}
\CustomizeMathJax{\newcommand{\rpfourth}[1]{\power{#1}{-4}}}
\CustomizeMathJax{\newcommand{\yocto}{\mathrm{y}}}
\CustomizeMathJax{\newcommand{\zepto}{\mathrm{z}}}
\CustomizeMathJax{\newcommand{\atto}{\mathrm{a}}}
\CustomizeMathJax{\newcommand{\femto}{\mathrm{f}}}
\CustomizeMathJax{\newcommand{\pico}{\mathrm{p}}}
\CustomizeMathJax{\newcommand{\nano}{\mathrm{n}}}
\CustomizeMathJax{\newcommand{\micro}{\mathrm{\unicode{x00B5}}}}
\CustomizeMathJax{\newcommand{\milli}{\mathrm{m}}}
\CustomizeMathJax{\newcommand{\centi}{\mathrm{c}}}
\CustomizeMathJax{\newcommand{\deci}{\mathrm{d}}}
\CustomizeMathJax{\newcommand{\deca}{\mathrm{da}}}
\CustomizeMathJax{\newcommand{\hecto}{\mathrm{h}}}
\CustomizeMathJax{\newcommand{\kilo}{\mathrm{k}}}
\CustomizeMathJax{\newcommand{\mega}{\mathrm{M}}}
\CustomizeMathJax{\newcommand{\giga}{\mathrm{G}}}
\CustomizeMathJax{\newcommand{\tera}{\mathrm{T}}}
\CustomizeMathJax{\newcommand{\peta}{\mathrm{P}}}
\CustomizeMathJax{\newcommand{\exa}{\mathrm{E}}}
\CustomizeMathJax{\newcommand{\zetta}{\mathrm{Z}}}
\CustomizeMathJax{\newcommand{\yotta}{\mathrm{Y}}}
\CustomizeMathJax{\newcommand{\yoctod}{\power{10}{-24}}}
\CustomizeMathJax{\newcommand{\zeptod}{\power{10}{-21}}}
\CustomizeMathJax{\newcommand{\attod}{\power{10}{-18}}}
\CustomizeMathJax{\newcommand{\femtod}{\power{10}{-15}}}
\CustomizeMathJax{\newcommand{\picod}{\power{10}{-12}}}
\CustomizeMathJax{\newcommand{\nanod}{\power{10}{-9}}}
\CustomizeMathJax{\newcommand{\microd}{\power{10}{-6}}}
\CustomizeMathJax{\newcommand{\millid}{\power{10}{-3}}}
\CustomizeMathJax{\newcommand{\centid}{\power{10}{-2}}}
\CustomizeMathJax{\newcommand{\decid}{\power{10}{-1}}}
\CustomizeMathJax{\newcommand{\decad}{\power{10}{1}}}
\CustomizeMathJax{\newcommand{\hectod}{\power{10}{2}}}
\CustomizeMathJax{\newcommand{\kilod}{\power{10}{3}}}
\CustomizeMathJax{\newcommand{\megad}{\power{10}{6}}}
\CustomizeMathJax{\newcommand{\gigad}{\power{10}{9}}}
\CustomizeMathJax{\newcommand{\terad}{\power{10}{12}}}
```

```
\CustomizeMathJax{\newcommand{\petad}{\power{10}{15}}}
\CustomizeMathJax{\newcommand{\exad}{\power{10}{18}}}
\CustomizeMathJax{\newcommand{\zettad}{\power{10}{21}}}
\CustomizeMathJax{\newcommand{\yottad}{\power{10}{24}}}
\CustomizeMathJax{\newcommand{\gram}{\mathrm{g}}}
\CustomizeMathJax{\newcommand{\metre}{\mathrm{m}}}
\CustomizeMathJax{\newcommand{\kilogram}{\kilo\gram}}
\CustomizeMathJax{\newcommand{\second}{\mathrm{s}}}
\CustomizeMathJax{\newcommand{\ampere}{\mathrm{A}}}
\CustomizeMathJax{\newcommand{\kelvin}{\mathrm{K}}}
\CustomizeMathJax{\newcommand{\mole}{\mathrm{mol}}}
\CustomizeMathJax{\newcommand{\candela}{\mathrm{cd}}}
\CustomizeMathJax{\newcommand{\radian}{\mathrm{rad}}}
\CustomizeMathJax{\newcommand{\steradian}{\mathrm{sr}}}
\CustomizeMathJax{\newcommand{\hertz}{\mathrm{Hz}}}
\CustomizeMathJax{\newcommand{\newton}{\mathrm{N}}}
\CustomizeMathJax{\newcommand{\pascal}{\mathrm{Pa}}}
\CustomizeMathJax{\newcommand{\joule}{\mathrm{J}}}
\CustomizeMathJax{\newcommand{\watt}{\mathrm{W}}}
\CustomizeMathJax{\newcommand{\coulomb}{\mathrm{C}}}
\CustomizeMathJax{\newcommand{\volt}{\mathrm{V}}}
\CustomizeMathJax{\newcommand{\farad}{\mathrm{F}}}
\CustomizeMathJax{\newcommand{\ohm}{\mathrm{\Omega}}}
\CustomizeMathJax{\newcommand{\siemens}{\mathrm{S}}}
\CustomizeMathJax{\newcommand{\weber}{\mathrm{Wb}}}
\CustomizeMathJax{\newcommand{\tesla}{\mathrm{T}}}
\CustomizeMathJax{\newcommand{\henry}{\mathrm{H}}}
\CustomizeMathJax{\newcommand{\degreecelsius}{\mathrm{\unicode{x2103}}}}
\CustomizeMathJax{\newcommand{\celsius}{\degreecelsius}}
\CustomizeMathJax{\newcommand{\lumen}{\mathrm{lm}}}
\CustomizeMathJax{\newcommand{\lux}{\mathrm{lx}}}
\CustomizeMathJax{\newcommand{\becquerel}{\mathrm{Bq}}}
\CustomizeMathJax{\newcommand{\sievert}{\mathrm{Sv}}}
\CustomizeMathJax{\newcommand{\katal}{\mathrm{kat}}}

\ifdef{\radianbase}{
\CustomizeMathJax{\newcommand{\radianbase}%
        {\metre\usk\reciprocal\metre}}
\CustomizeMathJax{\newcommand{\steradianbase}%
        {\squaremetre\usk\rpsquare\metre}}
\CustomizeMathJax{\newcommand{\hertzbase}%
        {\reciprocal\second}}
\CustomizeMathJax{\newcommand{\newtonbase}%
        {\metre\usk\kilogram\usk\second\rpsquared}}
\CustomizeMathJax{\newcommand{\pascalbase}%
        {\reciprocal\metre\usk\kilogram\usk\second\rpsquared}}
\CustomizeMathJax{\newcommand{\joulebase}%
        {\squaremetre\usk\kilogram\usk\second\rpsquared}}
\CustomizeMathJax{\newcommand{\wattbase}%
        {\squaremetre\usk\kilogram\usk\rpcubic\second}}
\CustomizeMathJax{\newcommand{\coulombbase}%
        {\ampere\usk\second}}
\CustomizeMathJax{\newcommand{\voltbase}%
        {\squaremetre\usk\kilogram\usk\rpcubic\second\usk\reciprocal\ampere}}
\CustomizeMathJax{\newcommand{\faradbase}%
```

```
      {\rpsquare\metre\usk\reciprocal\kilogram\usk\fourth\second\usk\ampere\squared}}
\CustomizeMathJax{\newcommand{\ohmbase}%
        {\squaremetre\usk\kilogram\usk\rpcubic\second\usk\rpsquare\ampere}}
\CustomizeMathJax{\newcommand{\siemensbase}%
      {\rpsquare\metre\usk\reciprocal\kilogram\usk\cubic\second\usk\ampere\squared}}
\CustomizeMathJax{\newcommand{\weberbase}%
       {\squaremetre\usk\kilogram\usk\second\rpsquared\usk\reciprocal\ampere}}
\CustomizeMathJax{\newcommand{\teslabase}%
        {\kilogram\usk\second\rpsquared\usk\reciprocal\ampere}}
\CustomizeMathJax{\newcommand{\henrybase}%
        {\squaremetre\usk\kilogram\usk\second\rpsquared\usk\rpsquare\ampere}}
\CustomizeMathJax{\newcommand{\celsiusbase}%
        {\kelvin}}
\CustomizeMathJax{\newcommand{\lumenbase}%
        {\candela\usk\squaremetre\usk\rpsquare\metre}}
\CustomizeMathJax{\newcommand{\luxbase}%
        {\candela\usk\squaremetre\usk\rpfourth\metre}}
\CustomizeMathJax{\newcommand{\becquerelbase}%
        {\hertzbase}}
\CustomizeMathJax{\newcommand{\graybase}%
        {\squaremetre\usk\second\rpsquared}}
\CustomizeMathJax{\newcommand{\sievertbase}%
        {\graybase}}
\CustomizeMathJax{\newcommand{\katalbase}%
        {\rp\second\usk\mole }}
}{}

\ifdef{\derradian}{
\CustomizeMathJax{\newcommand{\derradian}%
        {\metre\usk\reciprocal\metre}}
\CustomizeMathJax{\newcommand{\dersteradian}%
        {\squaremetre\usk\rpsquare\metre}}
\CustomizeMathJax{\newcommand{\derhertz}%
        {\reciprocal\second}}
\CustomizeMathJax{\newcommand{\dernewton}%
        {\metre\usk\kilogram\usk\second\rpsquared}}
\CustomizeMathJax{\newcommand{\derpascal}%
        {\newton\usk\rpsquare\metre}}
\CustomizeMathJax{\newcommand{\derjoule}%
        {\newton\usk\metre}}
\CustomizeMathJax{\newcommand{\derwatt}%
        {\joule\usk\reciprocal\second}}
\CustomizeMathJax{\newcommand{\dercoulomb}%
        {\ampere\usk\second}}
\CustomizeMathJax{\newcommand{\dervolt}%
        {\watt\usk\reciprocal\ampere}}
\CustomizeMathJax{\newcommand{\derfarad}%
        {\coulomb\usk\reciprocal\volt}}
\CustomizeMathJax{\newcommand{\derohm}%
        {\volt\usk\reciprocal\ampere}}
\CustomizeMathJax{\newcommand{\dersiemens}%
        {\ampere\usk\reciprocal\volt}}
\CustomizeMathJax{\newcommand{\derweber}%
       {\squaremetre\usk\kilogram\usk\second\rpsquared\usk\reciprocal\ampere}}
\CustomizeMathJax{\newcommand{\dertesla}%
```

```
        {\weber\usk\rpsquare\metre}}
\CustomizeMathJax{\newcommand{\derhenry}%
        {\weber\usk\reciprocal\ampere}}
\CustomizeMathJax{\newcommand{\dercelsius}%
        {\kelvin}}
\CustomizeMathJax{\newcommand{\derlumen}%
        {\candela\usk\steradian}}
\CustomizeMathJax{\newcommand{\derlux}%
        {\lumen\usk\rpsquare\metre}}
\CustomizeMathJax{\newcommand{\derbecquerel}%
        {\derhertz}}
\CustomizeMathJax{\newcommand{\dergray}%
        {\joule\usk\reciprocal\kilogram}}
\CustomizeMathJax{\newcommand{\dersievert}%
        {\dergray}}
\CustomizeMathJax{\newcommand{\derkatal}%
        {\katalbase}}
}{}

\CustomizeMathJax{\newcommand{\minute}{\mathrm{min}}}
\CustomizeMathJax{\newcommand{\hour}{\mathrm{h}}}
\CustomizeMathJax{\newcommand{\dday}{\mathrm{d}}}
\CustomizeMathJax{\newcommand{\degree}{\mathrm{^\circ}}}
\CustomizeMathJax{\newcommand{\paminute}{^\prime}}
\CustomizeMathJax{\newcommand{\arcminute}{^\prime}}
\CustomizeMathJax{\newcommand{\pasecond}{^{\prime\prime}}}
\CustomizeMathJax{\newcommand{\arcsecond}{^{\prime\prime}}}
\CustomizeMathJax{\newcommand{\ton}{\mathrm{t}}}
\CustomizeMathJax{\newcommand{\tonne}{\mathrm{t}}}
\CustomizeMathJax{\newcommand{\liter}{\mathrm{L}}}
\CustomizeMathJax{\newcommand{\litre}{\mathrm{l}}}
\CustomizeMathJax{\newcommand{\neper}{\mathrm{Np}}}
\CustomizeMathJax{\newcommand{\bel}{\mathrm{B}}}
\CustomizeMathJax{\newcommand{\curie}{\mathrm{Ci}}}
\CustomizeMathJax{\newcommand{\rad}{\mathrm{rad}}}
\CustomizeMathJax{\newcommand{\arad}{\mathrm{rd}}}
\CustomizeMathJax{\newcommand{\rem}{\mathrm{rem}}}
\CustomizeMathJax{\newcommand{\roentgen}{\mathrm{R}}}
\CustomizeMathJax{\newcommand{\electronvolt}{\mathrm{\mathrm{eV}}}}
\CustomizeMathJax{\newcommand{\atomicmass}{\mathrm{u}}}
\CustomizeMathJax{\newcommand{\atomicmassunit}{\mathrm{u}}}
\CustomizeMathJax{\newcommand{\dalton}{\mathrm{Da}}}
\CustomizeMathJax{\newcommand{\are}{\mathrm{a}}}
\CustomizeMathJax{\newcommand{\hectare}{\mathrm{\hecto\are}}}
\CustomizeMathJax{\newcommand{\barn}{\mathrm{b}}}
\CustomizeMathJax{\newcommand{\bbar}{\mathrm{bar}}}
\CustomizeMathJax{\newcommand{\gal}{\mathrm{Gal}}}
\CustomizeMathJax{\newcommand{\angstrom}{\mathrm{\unicode{x212B}}}}
\CustomizeMathJax{\newcommand{\rperminute}{\mathrm{r}\per\minute}}
\CustomizeMathJax{\newcommand{\rpersecond}{\mathrm{r}\per\second}}
\CustomizeMathJax{\newcommand{\squaremetre}{\power{\metre}{2}}}
\CustomizeMathJax{\newcommand{\cubicmetre}{\cubic\metre}}
\CustomizeMathJax{\newcommand{\graypersecond}{\gray\per\second}}
\CustomizeMathJax{\newcommand{\graypersecondnp}{\gray\usk\reciprocal\second}}
\CustomizeMathJax{\newcommand{\metrepersquaresecond}{\metre\per\second\squared}}
```

```
\CustomizeMathJax{\newcommand{\metrepersquaresecondnp}{\metre\usk\second\rpsquared}}
\CustomizeMathJax{\newcommand{\joulepermole}{\joule\per\mole}}
\CustomizeMathJax{\newcommand{\joulepermolenp}{\joule\usk\reciprocal\mole}}
\CustomizeMathJax{\newcommand{\molepercubicmetre}{\mole\per\cubic\metre}}
\CustomizeMathJax{\newcommand{\molepercubicmetrenp}{\mole\usk\rpcubic\metre}}
\CustomizeMathJax{\newcommand{\radianpersquaresecond}{\radian\per\second\squared}}
\CustomizeMathJax{\newcommand{\radianpersquaresecondnp}{\radian\usk\second\rpsquared}}
\CustomizeMathJax{\newcommand{\kilogramsquaremetrepersecond}{%
    \kilogram\usk\squaremetre\per\second%
}}
\CustomizeMathJax{\newcommand{\kilogramsquaremetrepersecondnp}{%
    \kilogram\usk\squaremetre\usk\reciprocal\second%
}}
\CustomizeMathJax{\newcommand{\radianpersecond}{\radian\per\second}}
\CustomizeMathJax{\newcommand{\radianpersecondnp}{\radian\usk\reciprocal\second}}
\CustomizeMathJax{\newcommand{\squaremetrepercubicmetre}{\squaremetre\per\cubic\metre}}
\CustomizeMathJax{\newcommand{\squaremetrepercubicmetrenp}{%
    \squaremetre\usk\rpcubic\metre%
}}
\CustomizeMathJax{\newcommand{\katalpercubicmetre}{\katal\per\cubic\metre}}
\CustomizeMathJax{\newcommand{\katalpercubicmetrenp}{\katal\usk\rpcubic\metre}}
\CustomizeMathJax{\newcommand{\coulombpermol}{\coulomb\per\mole}}
\CustomizeMathJax{\newcommand{\coulombpermolnp}{\coulomb\usk\reciprocal\mole}}
\CustomizeMathJax{\newcommand{\amperepersquaremetre}{\ampere\per\squaremetre}}
\CustomizeMathJax{\newcommand{\amperepersquaremetrenp}{\ampere\usk\rpsquare\metre}}
\CustomizeMathJax{\newcommand{\kilogrampercubicmetre}{\kilogram\per\cubic\metre}}
\CustomizeMathJax{\newcommand{\kilogrampercubicmetrenp}{\kilogram\usk\rpcubic\metre}}
\CustomizeMathJax{\newcommand{\squaremetrepernewtonsecond}{%
    \squaremetre\per\newton\usk\second%
}}
\CustomizeMathJax{\newcommand{\squaremetrepernewtonsecondnp}{%
    \squaremetre\usk\reciprocal\newton\usk\reciprocal\second%
}}
\CustomizeMathJax{\newcommand{\pascalsecond}{\pascal\usk\second}}
\CustomizeMathJax{\newcommand{\coulombpercubicmetre}{\coulomb\per\cubic\metre}}
\CustomizeMathJax{\newcommand{\coulombpercubicmetrenp}{\coulomb\usk\rpcubic\metre}}
\CustomizeMathJax{\newcommand{\amperemetresecond}{\ampere\usk\metre\usk\second}}
\CustomizeMathJax{\newcommand{\voltpermetre}{\volt\per\metre}}
\CustomizeMathJax{\newcommand{\voltpermetrenp}{\volt\usk\reciprocal\metre}}
\CustomizeMathJax{\newcommand{\coulombpersquaremetre}{\coulomb\per\squaremetre}}
\CustomizeMathJax{\newcommand{\coulombpersquaremetrenp}{\coulomb\usk\rpsquare\metre}}
\CustomizeMathJax{\newcommand{\faradpermetre}{\farad\per\metre}}
\CustomizeMathJax{\newcommand{\faradpermetrenp}{\farad\usk\reciprocal\metre}}
\CustomizeMathJax{\newcommand{\ohmmetre}{\ohm\usk\metre}}
\CustomizeMathJax{\newcommand{\kilowatthour}{\kilo\watt\hour}}
\CustomizeMathJax{\newcommand{\wattpersquaremetre}{\watt\per\squaremetre}}
\CustomizeMathJax{\newcommand{\wattpersquaremetrenp}{\watt\usk\rpsquare\metre}}
\CustomizeMathJax{\newcommand{\joulepersquaremetre}{\joule\per\squaremetre}}
\CustomizeMathJax{\newcommand{\joulepersquaremetrenp}{\joule\usk\rpsquare\metre}}
\CustomizeMathJax{\newcommand{\newtonpercubicmetre}{\newton\per\cubic\metre}}
\CustomizeMathJax{\newcommand{\newtonpercubicmetrenp}{\newton\usk\rpcubic\metre}}
\CustomizeMathJax{\newcommand{\newtonperkilogram}{\newton\per\kilogram}}
\CustomizeMathJax{\newcommand{\newtonperkilogramnp}{\newton\usk\reciprocal\kilogram}}
\CustomizeMathJax{\newcommand{\jouleperkelvin}{\joule\per\kelvin}}
\CustomizeMathJax{\newcommand{\jouleperkelvinnp}{\joule\usk\reciprocal\kelvin}}
```

```
\CustomizeMathJax{\newcommand{\jouleperkilogram}{\joule\per\kilogram}}
\CustomizeMathJax{\newcommand{\jouleperkilogramnp}{\joule\usk\reciprocal\kilogram}}
\CustomizeMathJax{\newcommand{\coulombperkilogram}{\coulomb\per\kilogram}}
\CustomizeMathJax{\newcommand{\coulombperkilogramnp}{\coulomb\usk\reciprocal\kilogram}}
\CustomizeMathJax{\newcommand{\squaremetrepersecond}{\squaremetre\per\second}}
\CustomizeMathJax{\newcommand{\squaremetrepersecondnp}{%
    \squaremetre\usk\reciprocal\second%
}}
\CustomizeMathJax{\newcommand{\squaremetrepersquaresecond}{%
    \squaremetre\per\second\squared%
}}
\CustomizeMathJax{\newcommand{\squaremetrepersquaresecondnp}{%
    \squaremetre\usk\second\rpsquared%
}}
\CustomizeMathJax{\newcommand{\kilogrammetrepersecond}{%
    \kilogram\usk\metre\per\second%
}}
\CustomizeMathJax{\newcommand{\kilogrammetrepersecondnp}{%
    \kilogram\usk\metre\usk\reciprocal\second%
}}
\CustomizeMathJax{\newcommand{\candelapersquaremetre}{\candela\per\squaremetre}}
\CustomizeMathJax{\newcommand{\candelapersquaremetrenp}{\candela\usk\rpsquare\metre}}
\CustomizeMathJax{\newcommand{\amperepermetre}{\ampere\per\metre}}
\CustomizeMathJax{\newcommand{\amperepermetrenp}{\ampere\usk\reciprocal\metre}}
\CustomizeMathJax{\newcommand{\joulepertesla}{\joule\per\tesla}}
\CustomizeMathJax{\newcommand{\joulepertesla np}{\joule\usk\reciprocal\tesla}}
\CustomizeMathJax{\newcommand{\henrypermetre}{\henry\per\metre}}
\CustomizeMathJax{\newcommand{\henrypermetrenp}{\henry\usk\reciprocal\metre}}
\CustomizeMathJax{\newcommand{\kilogrampersecond}{\kilogram\per\second}}
\CustomizeMathJax{\newcommand{\kilogrampersecondnp}{\kilogram\usk\reciprocal\second}}
\CustomizeMathJax{\newcommand{\kilogrampersquaremetresecond}{%
    \kilogram\per\squaremetre\usk\second%
}}
\CustomizeMathJax{\newcommand{\kilogrampersquaremetresecondnp}{%
    \kilogram\usk\rpsquare\metre\usk\reciprocal\second%
}}
\CustomizeMathJax{\newcommand{\kilogrampersquaremetre}{\kilogram\per\squaremetre}}
\CustomizeMathJax{\newcommand{\kilogrampersquaremetrenp}{\kilogram\usk\rpsquare\metre}}
\CustomizeMathJax{\newcommand{\kilogrampermetre}{\kilogram\per\metre}}
\CustomizeMathJax{\newcommand{\kilogrampermetrenp}{\kilogram\usk\reciprocal\metre}}
\CustomizeMathJax{\newcommand{\joulepermolekelvin}{\joule\per\mole\usk\kelvin}}
\CustomizeMathJax{\newcommand{\joulepermolekelvinnp}{%
    \joule\usk\reciprocal\mole\usk\reciprocal\kelvin%
}}
\CustomizeMathJax{\newcommand{\kilogramperkilomole}{\kilogram\per\kilo\mole}}
\CustomizeMathJax{\newcommand{\kilogramperkilomolenp}{%
    \kilogram\usk\kilo\reciprocal\mole%
}}
\CustomizeMathJax{\newcommand{\kilogramsquaremetre}{\kilogram\usk\squaremetre}}
\CustomizeMathJax{\newcommand{\kilogramsquaremetrenp}{\kilogramsquaremetre}}
\CustomizeMathJax{\newcommand{\kilogrammetrepersquaresecond}{%
    \kilogram\usk\metre\per\second\squared%
}}
\CustomizeMathJax{\newcommand{\kilogrammetrepersquaresecondnp}{%
    \kilogram\usk\metre\usk\second\rpsquared%
```

```
}}
\CustomizeMathJax{\newcommand{\newtonpersquaremetre}{\newton\per\squaremetre}}
\CustomizeMathJax{\newcommand{\newtonpersquaremetrenp}{\newton\usk\rpsquare\metre}}
\CustomizeMathJax{\newcommand{\persquaremetresecond}{1\per\squaremetre\usk\second}}
\CustomizeMathJax{\newcommand{\persquaremetresecondnp}{%
    \rpsquare\metre\usk\reciprocal\second%
}}
\CustomizeMathJax{\newcommand{\wattperkilogram}{\watt\per\kilogram}}
\CustomizeMathJax{\newcommand{\wattperkilogramnp}{\watt\usk\reciprocal\kilogram}}
\CustomizeMathJax{\newcommand{\wattpercubicmetre}{\watt\per\cubic\metre}}
\CustomizeMathJax{\newcommand{\wattpercubicmetrenp}{\watt\usk\rpcubic\metre}}
\CustomizeMathJax{\newcommand{\wattpersquaremetresteradian}{%
    \watt\per\squaremetre\usk\steradian%
}}
\CustomizeMathJax{\newcommand{\wattpersquaremetresteradiannp}{%
    \watt\usk\rpsquare\metre\usk\rp\steradian%
}}
\CustomizeMathJax{\newcommand{\jouleperkilogramkelvin}{\joule\per\kilogram\usk\kelvin}}
\CustomizeMathJax{\newcommand{\jouleperkilogramkelvinnp}{%
    \joule\usk\reciprocal\kilogram\usk\reciprocal\kelvin%
}}
\CustomizeMathJax{\newcommand{\squaremetreperkilogram}{\squaremetre\per\kilogram}}
\CustomizeMathJax{\newcommand{\rpsquaremetreperkilogram}{%
    \squaremetre\usk\reciprocal\kilogram%
}}
\CustomizeMathJax{\newcommand{\cubicmetreperkilogram}{\cubic\metre\per\kilogram}}
\CustomizeMathJax{\newcommand{\rpcubicmetreperkilogram}{%
    \cubic\metre\usk\reciprocal\kilogram%
}}
\CustomizeMathJax{\newcommand{\newtonpermetre}{\newton\per\metre}}
\CustomizeMathJax{\newcommand{\newtonpermetrenp}{\newton\usk\reciprocal\metre}}
\CustomizeMathJax{\newcommand{\Celsius}{\unicode{x2103}}}
\CustomizeMathJax{\newcommand{\wattpermetrekelvin}{\watt\per\metre\usk\kelvin}}
\CustomizeMathJax{\newcommand{\wattpermetrekelvinnp}{%
    \watt\usk\reciprocal\metre\usk\reciprocal\kelvin%
}}
\CustomizeMathJax{\newcommand{\newtonmetre}{\newton\usk\metre}
\CustomizeMathJax{\newcommand{\newtonmetrenp}{\newtonmetre}}}
\CustomizeMathJax{\newcommand{\squaremetrepercubicsecond}{%
    \squaremetre\per\cubic\second%
}}
\CustomizeMathJax{\newcommand{\squaremetrepercubicsecondnp}{%
    \squaremetre\usk\rpcubic\second%
}}
\CustomizeMathJax{\newcommand{\metrepersecond}{\metre\per\second}}
\CustomizeMathJax{\newcommand{\metrepersecondnp}{\metre\usk\reciprocal\second}}
\CustomizeMathJax{\newcommand{\joulepercubicmetre}{\joule\per\cubicmetre}}
\CustomizeMathJax{\newcommand{\joulepercubicmetrenp}{\joule\usk\rpcubic\metre}}
\CustomizeMathJax{\newcommand{\kilogrampercubicmetrecoulomb}{%
    \kilogram\per\cubic\metre\usk\coulomb%
}}
\CustomizeMathJax{\newcommand{\kilogrampercubicmetrecoulombnp}{%
    \kilogram\usk\rpcubic\metre\usk\reciprocal\coulomb%
}}
\CustomizeMathJax{\newcommand{\cubicmetrepersecond}{\cubicmetre\per\second}}
```

```
\CustomizeMathJax{\newcommand{\rpcubicmetrepersecond}{\cubicmetre\usk\reciprocal\second}}
\CustomizeMathJax{\newcommand{\kilogrampersecondcubicmetre}{%
    \kilogram\per\second\usk\cubicmetre%
}}
\CustomizeMathJax{\newcommand{\kilogrampersecondcubicmetrenp}{%
    \kilogram\usk\reciprocal\second\usk\rpcubic\metre%
}}
\end{warpMathJax}
```

File 446 **lwarp-siunitx.sty**

§ 554 Package siunitx

(*Emulates or patches code by* Joseph Wright.)

Pkg siunitx siunitx-v2 is patched for use by lwarp, and is emulated for MathJax. Use as:

```
\usepackage{siunitx}[=v2]
```

siunitx v3 is not yet supported.

for HTML output:

```
\providecommand\DeclareRelease[3]{}
\providecommand\DeclareCurrentRelease[2]{}

\DeclareRelease{2}{2010-05-23}{lwarp-siunitx-v2.sty}
\DeclareRelease{v2}{2010-05-23}{lwarp-siunitx-v2.sty}
\DeclareCurrentRelease{}{2021-05-17}

\PackageWarningNoLine{lwarp}
    {%
        **************\MessageBreak
        Siunitx version 3 is not yet supported by Lwarp.\MessageBreak
        V2 emulation is used here.\MessageBreak
        **************
    }

\RequirePackage{xcolor}% for \convertcolorspec

% \LWR@ProvidesPackagePass{siunitx}[2021-05-21]

\RequirePackage{siunitx-v2}
```

File 447 **lwarp-siunitx-v2.sty**

§ 555 Package siunitx-v2

(*Emulates or patches code by* Joseph Wright.)

Pkg siunitx-v2 siunitx-v2 is patched for use by lwarp, and is emulated for MathJax.

⚠ v3 not yet! siunitx v3 is not yet supported. For now, specify version 2:

```
\usepackage{siunitx}[=v2]
```

This may be also be necessary before loading other packages which also use siunitx, such as chemmacros.

fractions

Due to *pdftotext* limitations, fraction output is replaced by symbol output for `per-mode` and `quotient-mode`.

⚠ math mode required

Some units will require that the expression be placed inside math mode.

⚠ `tabular`

Tabular `S` columns are rendered as simple `c` columns, and tabular `s` columns are not supported. These may be replaced by `c` columns with each cell contained in `\num` or `\si`.

⚠ MathJax

For math mode with SVG display, the original siunitx code is used while generating the SVG image. For text mode, lwarp uses an emulation which provides a very effective HTML interpretation of siunitx. For math expressions while using MathJax, a limited emulation is used. Most functions work reasonably well, but many options cannot be emulated. Complicated parsing such as for `\ang` is not supported. The result usually looks fine, and otherwise is enough to get the meaning across.

Document modifications required for MathJax:

custom units

- Custom units may be added with `\CustomizeMathJax`. See the lwarp-siunitx code for examples.

⚠ unit spacing

- Units work better using ~ between units instead of using periods.

⚠ `\square, \cubic`

- To square or cube compound units, enclose the following compound units in braces:

  ```
  \cubic{\centi\meter}
  ```

  Single units do not require braces.

Also see MathJax option, section 8.7.4.

for HTML output:

```
\RequirePackage{xcolor}% for \convertcolorspec

\LWR@ProvidesPackagePass{siunitx-v2}[2021-04-17]


\AtBeginDocument{% in case textcomp was not loaded
    \DeclareSIUnit\bohr{\textit{a}\textsubscript{0}}
    \DeclareSIUnit\clight{\textit{c}\textsubscript{0}}
    \DeclareSIUnit\elementarycharge{\textit{e}}
    \DeclareSIUnit\electronmass{\textit{m}\textsubscript{e}}
    \DeclareSIUnit\hartree{\textit{E}\textsubscript{h}}
    \DeclareSIUnit\planckbar{\LWR@siunitx@textplanckbar}
}% AtBeginDocument
```

`\@ensuredmath` is not supported inside an `\hbox`, so it must temporarily be restored to its original. Similar for `\mbox`. SVG math is created explicitly when necessary, using `\LWR@subsingledollar`.

```

\ExplSyntaxOn
%
```

Modified to set set HTML `\textcolor` if not black:

```
\cs_set_protected:Npn \__siunitx_print_aux:
  {
    \text
      {
        \__siunitx_ensure_ltr:n
          {
```

`\color@endgroup` was adding a paragraph break, so use a regular group instead.

```
%             \color@begingroup
            \begingroup% lwarp
%
            \__siunitx_print_color:
            \__siunitx_font_shape:
            \__siunitx_font_weight:
            \use:c
              {
                __siunitx_ \l__siunitx_print_type_tl _
                text \l__siunitx_font_family_tl :
              }


%             \bool_if:NTF \l__siunitx_font_math_mode_bool
%               {
%                     \__siunitx_print_math:
%               }
                {
                     \LWR@findcurrenttextcolor% lwarp
                     \ifdefstring{\LWR@tempcolor}{000000}% lwarp
                         {\__siunitx_print_text:}% lwarp
                         {% lwarp
                             \LWR@textcurrentcolor{% lwarp
                                 \__siunitx_print_text:
                             }% lwarp
                         }% lwarp
                }
%             \color@endgroup
            \endgroup% lwarp
%
          }
      }
  }

\cs_set_protected:Npn \__siunitx_set_math_fam:n #1 {
  \group_begin:
    \LetLtxMacro\@ensuredmath\LWR@origensuredmath% lwarp
    \LetLtxMacro\mbox\LWR@print@mbox% lwarp
    \hbox_set:Nn \l__siunitx_tmp_box
      {
        \ensuremath
          {
            \use:c { math #1 }
              {
                \int_const:cn { c__siunitx_math #1 _int } { \fam }
```

```
              }
          }
      }
  \group_end:
}

\cs_set_protected:Npn \__siunitx_combined_output:n #1 {
%
    \group_begin:% lwarp
    \LetLtxMacro\@ensuredmath\LWR@origensuredmath% lwarp
    \LetLtxMacro\mbox\LWR@print@mbox% lwarp
  \bool_if:NTF \l__siunitx_number_parse_bool
    {
      \tl_clear:N \l__siunitx_number_out_tl
      \bool_set_false:N \l__siunitx_number_compound_bool
      \__siunitx_number_output_parse:n {#1}
    }
    {
```

For parse-numbers=false:

```
        \__siunitx_unit_output_pre_print:
        \begingroup%    lwarp
            \boolfalse{mathjax}%    lwarp
%       \__siunitx_print:nn { number } { \ensuremath {#1} }
            \LWR@subsingledollar{% lwarp
                \textbackslash( \LWR@HTMLsanitize{#1} \textbackslash)% lwarp
            }{siunitx}{%
                \__siunitx_print:nn { number } {%
                    \LWR@origensuredmath{#1}%
                }%
            }% lwarp
        \endgroup%    lwarp
        \__siunitx_unit_output_print:
    }
   \group_end:% lwarp
%
}
```

For parse-numbers=false:

```
\cs_set_protected:Npn \__siunitx_range_numbers_aux:n #1
  {
    \bool_if:NTF \l__siunitx_number_parse_bool
      {
        \tl_clear:N \l__siunitx_number_out_tl
        \tl_clear:N \l__siunitx_number_out_saved_tl
        \bool_set_false:N \l__siunitx_number_compound_bool
        \__siunitx_number_output_parse:n {#1}
        \bool_if:NT \l__siunitx_number_compound_bool
          { \msg_error:nnx { siunitx } { multi-part-range } {#1} }
      }
      {
        \__siunitx_unit_output_pre_print:
        \begingroup%    lwarp
```

```
            \boolfalse{mathjax}%    lwarp
%           \__siunitx_print:nn { number } {#1}
                \LWR@subsingledollar{% lwarp
                  \textbackslash( \LWR@HTMLsanitize{#1} \textbackslash)% lwarp
                }{siunitx}{%
                    \__siunitx_print:nn { number } {%
                        \LWR@origensuredmath{#1}%
                    } % lwarp
                }% lwarp
        \endgroup%    lwarp
        \__siunitx_unit_output_print:
      }
  }
```

For `parse-numbers=false`:

```
\cs_set_protected:Npn \__siunitx_angle_print_direct_aux:nn #1#2 {
  \tl_if_empty:nF {#1}
    {
      \tl_set:Nn \l__siunitx_unit_tl {#2}
        \begingroup%    lwarp
            \boolfalse{mathjax}%    lwarp
%           \__siunitx_print:nn { number } {#1}
                \LWR@subsingledollar{% lwarp
                  \textbackslash( \LWR@HTMLsanitize{#1} \textbackslash)% lwarp
                }{siunitx}{%
                    \__siunitx_print:nn { number } {
                        \LWR@origensuredmath{#1}%
                    }% lwarp
                }% lwarp
        \endgroup%    lwarp
      \__siunitx_unit_output_print:
    }
}
%
```

For quotients, the fraction code is replaced by the symbol code:

```
\cs_set_protected:Npn \__siunitx_number_output_quotient_fraction: {
  \bool_set_true:N \l__siunitx_number_compound_bool
  \__siunitx_number_output_quotient_aux_i:
  \tl_set_eq:NN \l__siunitx_number_out_tl
    \l__siunitx_number_numerator_tl
  \tl_put_right:NV \l__siunitx_number_out_tl \l__siunitx_output_quotient_tl
  \tl_put_right:NV \l__siunitx_number_out_tl
    \l__siunitx_number_denominator_tl
  \__siunitx_number_output_single_aux:
}
```

For units, the fraction code is replaced by the symbol code:

```
\cs_set_protected:Npn \__siunitx_unit_format_fraction_fraction: {
  \__siunitx_unit_format_fraction_symbol_aux:
  \int_compare:nNnT { \l__siunitx_unit_denominator_int } > { 1 }
    {
```

```
      \bool_if:NT \l__siunitx_unit_denominator_bracket_bool
        {
       \tl_put_left:NV \l__siunitx_unit_denominator_tl \l__siunitx_bracket_open_tl
       \tl_put_right:NV \l__siunitx_unit_denominator_tl \l__siunitx_bracket_close_tl
        }
    }
  \tl_set_eq:NN \l__siunitx_unit_tl \l__siunitx_unit_numerator_tl
  \tl_put_right:NV \l__siunitx_unit_tl \l__siunitx_per_symbol_tl
  \tl_put_right:NV \l__siunitx_unit_tl \l__siunitx_unit_denominator_tl
}

\cs_set_protected:Npn \__siunitx_angle_print_astronomy_aux: {
  \prop_get:NnNT \l__siunitx_number_out_prop { mantissa-integer }
    \l__siunitx_tmpa_tl
    { \__siunitx_print:nV { number } \l__siunitx_tmpa_tl }
 \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}% lwarp
 {% lateximage
  \hbox_set:Nn \l__siunitx_angle_marker_box
    {
      \__siunitx_print:nn { number } { { \l__siunitx_output_decimal_tl } }
    }
  \hbox_set:Nn \l__siunitx_angle_unit_box
    {
      \__siunitx_print:nV { unit } \l__siunitx_unit_tl
      \skip_horizontal:n { -\scriptspace }
    }
  \__siunitx_angle_print_astronomy_aux:n { marker }
  \__siunitx_angle_print_astronomy_aux:n { unit }
  \hbox_set:Nn \l__siunitx_angle_marker_box
    {
      \box_use:N \l__siunitx_angle_marker_box
      \box_use:N \l__siunitx_angle_unit_box
    }
  \dim_compare:nNnTF
    { \l__siunitx_angle_marker_dim } > { \l__siunitx_angle_unit_dim }
    { \__siunitx_angle_print_astronomy_marker: }
    { \__siunitx_angle_print_astronomy_unit: }
 }% lateximage
 {% not a lateximage
      \__siunitx_print:nV { unit } \l__siunitx_unit_tl
      \__siunitx_print:nn { number } { { \l__siunitx_output_decimal_tl } }
 }% not a lateximage
  \prop_get:NnNT \l__siunitx_number_out_prop { mantissa-decimal }
    \l__siunitx_tmpa_tl
    { \__siunitx_print:nV { number } \l__siunitx_tmpa_tl }
}

\cs_set_protected:Npn \__siunitx_textsuperscript:n #1 {\textsuperscript{#1}}
```

\num [⟨*options*⟩] {⟨*value*⟩}

```
\RenewDocumentCommand \num { o m } {
  \leavevmode
  \group_begin:% lwarp
```

```
    \LetLtxMacro\@ensuredmath\LWR@origensuredmath% lwarp
    \LetLtxMacro\mbox\LWR@print@mbox% lwarp
    \bool_set_false:N \l__siunitx_font_set_bool
    \IfNoValueF {#1}
      { \keys_set:nn { siunitx } {#1} }
    \__siunitx_number_output:n {#2}
  \group_end:% lwarp
}
```

\numrange [⟨*options*⟩] {⟨*value1*⟩} {⟨*value2*⟩}

```
\RenewDocumentCommand \numrange { o m m } {
  \leavevmode
  \group_begin:% lwarp
    \LetLtxMacro\@ensuredmath\LWR@origensuredmath% lwarp
    \LetLtxMacro\mbox\LWR@print@mbox% lwarp
    \bool_set_false:N \l__siunitx_font_set_bool
    \IfNoValueF {#1}
      { \keys_set:nn { siunitx } {#1} }
    \__siunitx_range_numbers:nn {#2} {#3}
  \group_end:% lwarp
}
```

\ang {⟨*options*⟩} {⟨*angle*⟩}

```
\RenewDocumentCommand \ang { o > { \SplitArgument { 2 } { ; } } m } {
  \group_begin:% lwarp
    \LetLtxMacro\@ensuredmath\LWR@origensuredmath% lwarp
    \LetLtxMacro\mbox\LWR@print@mbox% lwarp
    \IfNoValueF {#1}
      { \keys_set:nn { siunitx } {#1} }
    \__siunitx_angle_output:nnn #2
  \group_end:% lwarp
}
```

\si {⟨*options*⟩} {⟨*unit*⟩}

```
\RenewDocumentCommand \si { o m } {
  \leavevmode
  \group_begin:% lwarp
    \LetLtxMacro\@ensuredmath\LWR@origensuredmath% lwarp
    \LetLtxMacro\mbox\LWR@print@mbox% lwarp
    \bool_set_false:N \l__siunitx_font_set_bool
    \IfNoValueTF {#1}
      { \__siunitx_unit_output:nn {#2} { } }
      {
        \keys_set:nn { siunitx } {#1}
        \__siunitx_unit_output:nn {#2} {#1}
      }
  \group_end:% lwarp
}
```

\SIrange [⟨*options*⟩] {⟨*value1*⟩} {⟨*value2*⟩} {⟨*unit*⟩}

```
\RenewDocumentCommand{\SIrange}{o m m m}
```

```
{%
  \leavevmode
  \group_begin:% lwarp
    \LetLtxMacro\@ensuredmath\LWR@origensuredmath% lwarp
    \LetLtxMacro\mbox\LWR@print@mbox% lwarp
    \bool_set_false:N \l__siunitx_font_set_bool
    \IfNoValueTF {#1}
      { \__siunitx_range_unit:nnnn {#4} { } {#2} {#3} }
      {
        \keys_set:nn { siunitx } {#1}
        \__siunitx_range_unit:nnnn {#4} {#1} {#2} {#3}
      }
  \group_end:% lwarp
}

\ExplSyntaxOff
```

For MathJax. (The following runs much faster as separate `\CusomizeMathJax` calls instead of one single call.)

```
\begin{warpMathJax}
\LWR@infoprocessingmathjax{siunitx}

\CustomizeMathJax{\newcommand{\tothe}[1]{^{#1}}}
\CustomizeMathJax{\newcommand{\raiseto}[2]{{#2}^{#1}}}
```

Used as an end marker when parsing values:

```
\CustomizeMathJax{\newcommand{\LWRsiunitxEND}{}}
```

`\ang` `[`⟨*options*⟩`]` `{`⟨*value*⟩`}`

```
\CustomizeMathJax{\def\LWRsiunitxang#1;#2;#3;#4\LWRsiunitxEND{%
    \ifblank{#1}{}{\num{#1}\degree}%
    \ifblank{#2}{}{\num{#2}^{\unicode{x2032}}}% \prime
    \ifblank{#3}{}{\num{#3}^{\unicode{x2033}}}% \dblprime
}}
\CustomizeMathJax{\newcommand{\ang}[2][]{\LWRsiunitxang#2;;;\LWRsiunitxEND}}
```

Processes scientific notation. Special handling for a mantissa which is either empty or only a minus sign.

```
\CustomizeMathJax{\newcommand{\LWRsiunitxnumscientific}[2]{%
    \ifblank{#1}%
        {}%
        {%
            \ifstrequal{#1}{-}%
                {-}%
                {\LWRsiunitxprintdecimal{#1}\times}%
        }%
    10^{\LWRsiunitxprintdecimal{#2}}
}}
```

\num handles optional powers (e, E, d, D), multiples (x), plus and minus, and period or comma decimal output.

To split the string, \def is used with parameter delimiters. When each of the following macro is used, extra delimiters are padded to the end of the arguments of each macro when used, and the final argument of each collects any extra unused delimiters.

```
\ExplSyntaxOn
\AtBeginDocument{
\ifdefstring{\l__siunitx_output_decimal_tl}{{,}}
    {% Use decimal comma
      \CustomizeMathJax{\def\LWRsiunitxprintdecimalsub#1.#2.#3\LWRsiunitxEND{%
            \mathrm{#1}%
            \ifblank{#2}
                {}%
                {,\mathrm{#2}}
        }}

        \CustomizeMathJax{\newcommand{\LWRsiunitxprintdecimal}[1]{%
            \LWRsiunitxprintdecimalsub#1...\LWRsiunitxEND%
        }}
    }
    {% Use decimal point
      \CustomizeMathJax{\def\LWRsiunitxprintdecimalsub#1,#2,#3\LWRsiunitxEND{%
            \mathrm{#1}%
            \ifblank{#2}
                {}%
                {.\mathrm{#2}}
        }}

        \CustomizeMathJax{\newcommand{\LWRsiunitxprintdecimal}[1]{%
            \LWRsiunitxprintdecimalsub#1,,,\LWRsiunitxEND%
        }}
    }
}
\ExplSyntaxOff
```

\num [⟨*options*⟩] {⟨*value*⟩}

```
\CustomizeMathJax{\def\LWRsiunitxnumplus#1+#2+#3\LWRsiunitxEND{%
    \ifblank{#2}
        {\LWRsiunitxprintdecimal{#1}}% no plus
        {%
            \ifblank{#1}%
                {\LWRsiunitxprintdecimal{#2}}% leading plus, ignore
                {% a+b
                    \LWRsiunitxprintdecimal{#1}%
                    \unicode{x02B}% plus sign
                    \LWRsiunitxprintdecimal{#2}%
                }%
        }%
}}

\CustomizeMathJax{\def\LWRsiunitxnumminus#1-#2-#3\LWRsiunitxEND{%
    \ifblank{#2}
```

```
        {\LWRsiunitxnumplus#1+++\LWRsiunitxEND}%
        {%
            \LWRsiunitxprintdecimal{#1}%
            \unicode{x02212}% mathematical minus sign
            \LWRsiunitxprintdecimal{#2}%
        }%
}}

\CustomizeMathJax{\def\LWRsiunitxnumpm#1+-#2+-#3\LWRsiunitxEND{%
    \ifblank{#2}%
        {\LWRsiunitxnumminus#1---\LWRsiunitxEND}%
        {%
            \LWRsiunitxprintdecimal{#1}%
            \unicode{x0B1}% \pm
            \LWRsiunitxprintdecimal{#2}%
        }%
}}

\CustomizeMathJax{\def\LWRsiunitxnumx#1x#2x#3x#4\LWRsiunitxEND{%
    \ifblank{#2}%
        {\LWRsiunitxnumpm#1+-+-\LWRsiunitxEND}%
        {%
            \ifblank{#3}%
                {%
                    \LWRsiunitxprintdecimal{#1}%
                    \times%
                    \LWRsiunitxprintdecimal{#2}%
                }%
                {%
                    \LWRsiunitxprintdecimal{#1}%
                    \times%
                    \LWRsiunitxprintdecimal{#2}%
                    \times%
                    \LWRsiunitxprintdecimal{#3}%
                }%
        }%
}}

\CustomizeMathJax{\def\LWRsiunitxnumD#1D#2D#3\LWRsiunitxEND{%
    \ifblank{#2}%
        {\LWRsiunitxnumx#1xxxxx\LWRsiunitxEND}%
        {\mathrm{\LWRsiunitxnumscientific{#1}{#2}}}%
}}

\CustomizeMathJax{\def\LWRsiunitxnumd#1d#2d#3\LWRsiunitxEND{%
    \ifblank{#2}%
        {\LWRsiunitxnumD#1DDD\LWRsiunitxEND}%
        {\mathrm{\LWRsiunitxnumscientific{#1}{#2}}}%
}}

\CustomizeMathJax{\def\LWRsiunitxnumE#1E#2E#3\LWRsiunitxEND{%
    \ifblank{#2}%
        {\LWRsiunitxnumd#1ddd\LWRsiunitxEND}%
        {\mathrm{\LWRsiunitxnumscientific{#1}{#2}}}%
}}
```

```
\CustomizeMathJax{\def\LWRsiunitxnume#1e#2e#3\LWRsiunitxEND{%
    \ifblank{#2}%
        {\LWRsiunitxnumE#1EEE\LWRsiunitxEND}%
        {\mathrm{\LWRsiunitxnumscientific{#1}{#2}}}%
}}

\CustomizeMathJax{\def\LWRsiunitxnumcomma#1,#2,#3\LWRsiunitxEND{%
    \ifblank{#2}
        {\LWRsiunitxnume#1eee\LWRsiunitxEND}
        {\LWRsiunitxnume#1.#2eee\LWRsiunitxEND}
}}

\CustomizeMathJax{\newcommand{\num}[2][]{\LWRsiunitxnumcomma#2,,,\LWRsiunitxEND}}
```

`\si` `[`⟨*options*⟩`]` `{`⟨*unit*⟩`}`

```
\CustomizeMathJax{\newcommand{\si}[2][]{\mathrm{#2}}}
```

`\SI` `[`⟨*options*⟩`]` `{`⟨*value*⟩`}` `[`⟨*prefix*⟩`]` `{`⟨*unit*⟩`}`

`\SI` has a second optional arg, which is parsed using `\ifnextchar`.

```
\CustomizeMathJax{\def\LWRsiunitxSIopt#1[#2]#3{%
    {#2}\num{#1}{#3}%
}}

\CustomizeMathJax{\newcommand{\LWRsiunitxSI}[2]{%
    \num{#1}\,{#2}%
}}

\CustomizeMathJax{\newcommand{\SI}[2][]{%
    \ifnextchar[%
        {\LWRsiunitxSIopt{#2}}%
        {\LWRsiunitxSI{#2}}%
}}
```

`\numlist` `[`⟨*options*⟩`]` `{`⟨*list*⟩`}`

`\numlist` should only be used in text mode. If used in MathJax, it is merely printed as input.

```
\CustomizeMathJax{\newcommand{\numlist}[2][]{\mathrm{#2}}}
```

`\numrange` `[`⟨*options*⟩`]` `{`⟨*value1*⟩`}` `{`⟨*value2*⟩`}`

`\numrange` should only be used in text mode. If used in MathJax math, an en-dash is used instead of the `range-phase`.

```
\CustomizeMathJax{\newcommand{\numrange}[3][]{\num{#2}\,\unicode{x2013}\,\num{#3}}}
```

`\SIlist` `[`⟨*options*⟩`]` `{`⟨*list*⟩`}`

`\SIlist` and `\SIrange` should only be used in text mode. If used in MathJax, a simple emulation is provided.

```
\CustomizeMathJax{\newcommand{\SIlist}[3][]{\mathrm{#2\,#3}}}
```

\SIrange [⟨*options*⟩] {⟨*value1*⟩} {⟨*value2*⟩} {⟨*unit*⟩}

```
\CustomizeMathJax{\newcommand{\SIrange}[4][]{\num{#2}\,#4\,\unicode{x2013}\,\num{#3}\,#4}}
```

\tablenum [⟨*options*⟩] {⟨*value*⟩}

```
\CustomizeMathJax{\newcommand{\tablenum}[2][]{\mathrm{#2}}}

\CustomizeMathJax{\newcommand{\ampere}{\mathrm{A}}}
\CustomizeMathJax{\newcommand{\candela}{\mathrm{cd}}}
\CustomizeMathJax{\newcommand{\kelvin}{\mathrm{K}}}
\CustomizeMathJax{\newcommand{\kilogram}{\mathrm{kg}}}
\CustomizeMathJax{\newcommand{\metre}{\mathrm{m}}}
\CustomizeMathJax{\newcommand{\mole}{\mathrm{mol}}}
\CustomizeMathJax{\newcommand{\second}{\mathrm{s}}}
%
\CustomizeMathJax{\newcommand{\becquerel}{\mathrm{Bq}}}
\CustomizeMathJax{\newcommand{\degreeCelsius}{\unicode{x2103}}}
\CustomizeMathJax{\newcommand{\coulomb}{\mathrm{C}}}
\CustomizeMathJax{\newcommand{\farad}{\mathrm{F}}}
\CustomizeMathJax{\newcommand{\gray}{\mathrm{Gy}}}
\CustomizeMathJax{\newcommand{\hertz}{\mathrm{Hz}}}
\CustomizeMathJax{\newcommand{\henry}{\mathrm{H}}}
\CustomizeMathJax{\newcommand{\joule}{\mathrm{J}}}
\CustomizeMathJax{\newcommand{\katal}{\mathrm{kat}}}
\CustomizeMathJax{\newcommand{\lumen}{\mathrm{lm}}}
\CustomizeMathJax{\newcommand{\lux}{\mathrm{lx}}}
\CustomizeMathJax{\newcommand{\newton}{\mathrm{N}}}
\CustomizeMathJax{\newcommand{\ohm}{\mathrm{\Omega}}}
\CustomizeMathJax{\newcommand{\pascal}{\mathrm{Pa}}}
\CustomizeMathJax{\newcommand{\radian}{\mathrm{rad}}}
\CustomizeMathJax{\newcommand{\siemens}{\mathrm{S}}}
\CustomizeMathJax{\newcommand{\sievert}{\mathrm{Sv}}}
\CustomizeMathJax{\newcommand{\steradian}{\mathrm{sr}}}
\CustomizeMathJax{\newcommand{\tesla}{\mathrm{T}}}
\CustomizeMathJax{\newcommand{\volt}{\mathrm{V}}}
\CustomizeMathJax{\newcommand{\watt}{\mathrm{W}}}
\CustomizeMathJax{\newcommand{\weber}{\mathrm{Wb}}}
\CustomizeMathJax{\newcommand{\day}{\mathrm{d}}}
\CustomizeMathJax{\newcommand{\degree}{\mathrm{^\circ}}}
\CustomizeMathJax{\newcommand{\hectare}{\mathrm{ha}}}
\CustomizeMathJax{\newcommand{\hour}{\mathrm{h}}}
\CustomizeMathJax{\newcommand{\litre}{\mathrm{l}}}
\CustomizeMathJax{\newcommand{\liter}{\mathrm{L}}}
\CustomizeMathJax{\newcommand{\arcminute}{^\prime}}
\CustomizeMathJax{\newcommand{\minute}{\mathrm{min}}}
\CustomizeMathJax{\newcommand{\arcsecond}{^{\prime\prime}}}
\CustomizeMathJax{\newcommand{\tonne}{\mathrm{t}}}
\CustomizeMathJax{\newcommand{\astronomicalunit}{au}}
\CustomizeMathJax{\newcommand{\atomicmassunit}{u}}
\CustomizeMathJax{\newcommand{\bohr}{\mathit{a}_0}}
\CustomizeMathJax{\newcommand{\clight}{\mathit{c}_0}}
\CustomizeMathJax{\newcommand{\dalton}{\mathrm{D}_\mathrm{a}}}
\CustomizeMathJax{\newcommand{\electronmass}{\mathit{m}_{\mathrm{e}}}}
```

```
\CustomizeMathJax{\newcommand{\electronvolt}{\mathrm{eV}}}
\CustomizeMathJax{\newcommand{\elementarycharge}{\mathit{e}}}
\CustomizeMathJax{\newcommand{\hartree}{\mathit{E}_{\mathrm{h}}}}
\CustomizeMathJax{\newcommand{\planckbar}{\mathit{\unicode{x210F}}}}
\CustomizeMathJax{\newcommand{\angstrom}{\mathrm{\unicode{x212B}}}}
\CustomizeMathJax{\let\LWRorigbar\bar}
\CustomizeMathJax{\newcommand{\bar}{\mathrm{bar}}}
\CustomizeMathJax{\newcommand{\barn}{\mathrm{b}}}
\CustomizeMathJax{\newcommand{\bel}{\mathrm{B}}}
\CustomizeMathJax{\newcommand{\decibel}{\mathrm{dB}}}
\CustomizeMathJax{\newcommand{\knot}{\mathrm{kn}}}
\CustomizeMathJax{\newcommand{\mmHg}{\mathrm{mmHg}}}
\CustomizeMathJax{\newcommand{\nauticalmile}{\mathrm{M}}}
\CustomizeMathJax{\newcommand{\neper}{\mathrm{Np}}}
%
\CustomizeMathJax{\newcommand{\yocto}{\mathrm{y}}}
\CustomizeMathJax{\newcommand{\zepto}{\mathrm{z}}}
\CustomizeMathJax{\newcommand{\atto}{\mathrm{a}}}
\CustomizeMathJax{\newcommand{\femto}{\mathrm{f}}}
\CustomizeMathJax{\newcommand{\pico}{\mathrm{p}}}
\CustomizeMathJax{\newcommand{\nano}{\mathrm{n}}}
\CustomizeMathJax{\newcommand{\micro}{\mathrm{\unicode{x00B5}}}}
\CustomizeMathJax{\newcommand{\milli}{\mathrm{m}}}
\CustomizeMathJax{\newcommand{\centi}{\mathrm{c}}}
\CustomizeMathJax{\newcommand{\deci}{\mathrm{d}}}
\CustomizeMathJax{\newcommand{\deca}{\mathrm{da}}}
\CustomizeMathJax{\newcommand{\hecto}{\mathrm{h}}}
\CustomizeMathJax{\newcommand{\kilo}{\mathrm{k}}}
\CustomizeMathJax{\newcommand{\mega}{\mathrm{M}}}
\CustomizeMathJax{\newcommand{\giga}{\mathrm{G}}}
\CustomizeMathJax{\newcommand{\tera}{\mathrm{T}}}
\CustomizeMathJax{\newcommand{\peta}{\mathrm{P}}}
\CustomizeMathJax{\newcommand{\exa}{\mathrm{E}}}
\CustomizeMathJax{\newcommand{\zetta}{\mathrm{Z}}}
\CustomizeMathJax{\newcommand{\yotta}{\mathrm{Y}}}
%
\CustomizeMathJax{\newcommand{\percent}{\mathrm{\%}}}
%
\CustomizeMathJax{\newcommand{\meter}{\mathrm{m}}}
\CustomizeMathJax{\newcommand{\metre}{\mathrm{m}}}
%
\CustomizeMathJax{\newcommand{\gram}{\mathrm{g}}}
\CustomizeMathJax{\newcommand{\kg}{\kilo\gram}}
\CustomizeMathJax{\newcommand{\of}[1]{_{\mathrm{#1}}}}
\CustomizeMathJax{\newcommand{\squared}{^2}}
\CustomizeMathJax{\newcommand{\square}[1]{\mathrm{#1}^2}}
\CustomizeMathJax{\newcommand{\cubed}{^3}}
\CustomizeMathJax{\newcommand{\cubic}[1]{\mathrm{#1}^3}}
\CustomizeMathJax{\newcommand{\per}{/}}
\CustomizeMathJax{\newcommand{\celsius}{\unicode{x2103}}}
%
\CustomizeMathJax{\newcommand{\fg}{\femto\gram}}
\CustomizeMathJax{\newcommand{\pg}{\pico\gram}}
\CustomizeMathJax{\newcommand{\ng}{\nano\gram}}
\CustomizeMathJax{\newcommand{\ug}{\micro\gram}}
```

```
\CustomizeMathJax{\newcommand{\mg}{\milli\gram}}
\CustomizeMathJax{\newcommand{\g}{\gram}}
\CustomizeMathJax{\newcommand{\kg}{\kilo\gram}}
%
\CustomizeMathJax{\newcommand{\amu}{\mathrm{u}}}
%
\CustomizeMathJax{\newcommand{\pm}{\pico\metre}}
\CustomizeMathJax{\newcommand{\nm}{\nano\metre}}
\CustomizeMathJax{\newcommand{\um}{\micro\metre}}
\CustomizeMathJax{\newcommand{\mm}{\milli\metre}}
\CustomizeMathJax{\newcommand{\cm}{\centi\metre}}
\CustomizeMathJax{\newcommand{\dm}{\deci\metre}}
\CustomizeMathJax{\newcommand{\m}{\metre}}
\CustomizeMathJax{\newcommand{\km}{\kilo\metre}}
%
\CustomizeMathJax{\newcommand{\as}{\atto\second}}
\CustomizeMathJax{\newcommand{\fs}{\femto\second}}
\CustomizeMathJax{\newcommand{\ps}{\pico\second}}
\CustomizeMathJax{\newcommand{\ns}{\nano\second}}
\CustomizeMathJax{\newcommand{\us}{\micro\second}}
\CustomizeMathJax{\newcommand{\ms}{\milli\second}}
\CustomizeMathJax{\newcommand{\s}{\second}}
%
\CustomizeMathJax{\newcommand{\fmol}{\femto\mol}}
\CustomizeMathJax{\newcommand{\pmol}{\pico\mol}}
\CustomizeMathJax{\newcommand{\nmol}{\nano\mol}}
\CustomizeMathJax{\newcommand{\umol}{\micro\mol}}
\CustomizeMathJax{\newcommand{\mmol}{\milli\mol}}
\CustomizeMathJax{\newcommand{\mol}{\mol}}
\CustomizeMathJax{\newcommand{\kmol}{\kilo\mol}}
%
\CustomizeMathJax{\newcommand{\pA}{\pico\ampere}}
\CustomizeMathJax{\newcommand{\nA}{\nano\ampere}}
\CustomizeMathJax{\newcommand{\uA}{\micro\ampere}}
\CustomizeMathJax{\newcommand{\mA}{\milli\ampere}}
\CustomizeMathJax{\newcommand{\A}{\ampere}}
\CustomizeMathJax{\newcommand{\kA}{\kilo\ampere}}
%
\CustomizeMathJax{\newcommand{\ul}{\micro\litre}}
\CustomizeMathJax{\newcommand{\ml}{\milli\litre}}
\CustomizeMathJax{\newcommand{\l}{\litre}}
\CustomizeMathJax{\newcommand{\hl}{\hecto\litre}}
\CustomizeMathJax{\newcommand{\uL}{\micro\liter}}
\CustomizeMathJax{\newcommand{\mL}{\milli\liter}}
\CustomizeMathJax{\newcommand{\L}{\liter}}
\CustomizeMathJax{\newcommand{\hL}{\hecto\liter}}
%
\CustomizeMathJax{\newcommand{\mHz}{\milli\hertz}}
\CustomizeMathJax{\newcommand{\Hz}{\hertz}}
\CustomizeMathJax{\newcommand{\kHz}{\kilo\hertz}}
\CustomizeMathJax{\newcommand{\MHz}{\mega\hertz}}
\CustomizeMathJax{\newcommand{\GHz}{\giga\hertz}}
\CustomizeMathJax{\newcommand{\THz}{\tera\hertz}}
%
\CustomizeMathJax{\newcommand{\mN}{\milli\newton}}
```

```
\CustomizeMathJax{\newcommand{\N}{\newton}}
\CustomizeMathJax{\newcommand{\kN}{\kilo\newton}}
\CustomizeMathJax{\newcommand{\MN}{\mega\newton}}
%
\CustomizeMathJax{\newcommand{\Pa}{\pascal}}
\CustomizeMathJax{\newcommand{\kPa}{\kilo\pascal}}
\CustomizeMathJax{\newcommand{\MPa}{\mega\pascal}}
\CustomizeMathJax{\newcommand{\GPa}{\giga\pascal}}
%
\CustomizeMathJax{\newcommand{\mohm}{\milli\ohm}}
\CustomizeMathJax{\newcommand{\kohm}{\kilo\ohm}}
\CustomizeMathJax{\newcommand{\Mohm}{\mega\ohm}}
%
\CustomizeMathJax{\newcommand{\pV}{\pico\volt}}
\CustomizeMathJax{\newcommand{\nV}{\nano\volt}}
\CustomizeMathJax{\newcommand{\uV}{\micro\volt}}
\CustomizeMathJax{\newcommand{\mV}{\milli\volt}}
\CustomizeMathJax{\newcommand{\V}{\volt}}
\CustomizeMathJax{\newcommand{\kV}{\kilo\volt}}
%
\CustomizeMathJax{\newcommand{\W}{\watt}}
\CustomizeMathJax{\newcommand{\uW}{\micro\watt}}
\CustomizeMathJax{\newcommand{\mW}{\milli\watt}}
\CustomizeMathJax{\newcommand{\kW}{\kilo\watt}}
\CustomizeMathJax{\newcommand{\MW}{\mega\watt}}
\CustomizeMathJax{\newcommand{\GW}{\giga\watt}}
%
\CustomizeMathJax{\newcommand{\J}{\joule}}
\CustomizeMathJax{\newcommand{\uJ}{\micro\joule}}
\CustomizeMathJax{\newcommand{\mJ}{\milli\joule}}
\CustomizeMathJax{\newcommand{\kJ}{\kilo\joule}}
%
\CustomizeMathJax{\newcommand{\eV}{\electronvolt}}
\CustomizeMathJax{\newcommand{\meV}{\milli\electronvolt}}
\CustomizeMathJax{\newcommand{\keV}{\kilo\electronvolt}}
\CustomizeMathJax{\newcommand{\MeV}{\mega\electronvolt}}
\CustomizeMathJax{\newcommand{\GeV}{\giga\electronvolt}}
\CustomizeMathJax{\newcommand{\TeV}{\tera\electronvolt}}
%
\CustomizeMathJax{\newcommand{\kWh}{\kilo\watt\hour}}
%
\CustomizeMathJax{\newcommand{\F}{\farad}}
\CustomizeMathJax{\newcommand{\fF}{\femto\farad}}
\CustomizeMathJax{\newcommand{\pF}{\pico\farad}}
%
\CustomizeMathJax{\newcommand{\K}{\mathrm{K}}}
%
\CustomizeMathJax{\newcommand{\dB}{\mathrm{dB}}}
%
\CustomizeMathJax{\newcommand{\kibi}{\mathrm{Ki}}}
\CustomizeMathJax{\newcommand{\mebi}{\mathrm{Mi}}}
\CustomizeMathJax{\newcommand{\gibi}{\mathrm{Gi}}}
\CustomizeMathJax{\newcommand{\tebi}{\mathrm{Ti}}}
\CustomizeMathJax{\newcommand{\pebi}{\mathrm{Pi}}}
\CustomizeMathJax{\newcommand{\exbi}{\mathrm{Ei}}}
```

```
\CustomizeMathJax{\newcommand{\zebi}{\mathrm{Zi}}}
\CustomizeMathJax{\newcommand{\yobi}{\mathrm{Yi}}}
\end{warpMathJax}
```

File 448 **lwarp-skmath.sty**

§ 556 Package

skmath

(*Emulates or patches code by* Simon Sigurdhsson.)

Pkg skmath skmath is used as-is for SVG math, and is emulated for MathJax.

for HTML output:

```
\LWR@ProvidesPackagePass{skmath}[2019/10/15]
```

Only defined if package option requested:

```
\begin{warpMathJax}
\ExplSyntaxOn
\bool_if:NT\g__skmath_define_common_sets_bool{
\CustomizeMathJax{\newcommand{\N}{\mathbb{N}}}
\CustomizeMathJax{\newcommand{\Z}{\mathbb{Z}}}
\CustomizeMathJax{\newcommand{\Q}{\mathbb{Q}}}
\CustomizeMathJax{\newcommand{\R}{\mathbb{R}}}
\CustomizeMathJax{\newcommand{\C}{\mathbb{C}}}
}
```

skmath is using l3keys, which does not seem to have an equivalent to `\@ifpackagewith`. To detect package options, comparisons with the following are made to see if various macros have been defined as follows:

```
\cs_gset_nopar:Npn\LWR__skmath_imaginary_unit:n#1{{#1}}
\cs_gset_nopar:Npn\LWR__skmath_natural_log_e:{{e}}
\cs_gset_nopar:Npn\LWR__skmath_integral_d:{{d}}
\cs_gset_nopar:Npn\LWR__skmath_total_derivative_d:{{d}}
```

If `notation=iso`, use upright, else italic:

```
\cs_if_eq:NNTF \__skmath_imaginary_unit:n \LWR__skmath_imaginary_unit:n
    {
        \CustomizeMathJax{\newcommand{ii}{\mathit{i}}}
        \CustomizeMathJax{\newcommand{jj}{\mathit{j}}}
    }
    {
        \CustomizeMathJax{\newcommand{ii}{\mathrm{i}}}
        \CustomizeMathJax{\newcommand{jj}{\mathrm{j}}}
    }
```

If `notation=iso`, use upright, else italic:

```
\cs_if_eq:NNTF \__skmath_natural_log_e: \LWR__skmath_natural_log_e:
    { \CustomizeMathJax{\newcommand{\ee}{\mathit{e}}} }
    { \CustomizeMathJax{\newcommand{\ee}{\mathrm{e}}} }
```

skmath uses \DeclarePairedDelimiter from mathtools for \abs and \norm, and lwarp uses this to automatically define MathJax definitions for each.

If notation=english, use slanted, else upright:

```
\cs_if_eq:NNTF \__skmath_integral_d: \LWR__skmath_integral_d:
    { \CustomizeMathJax{\newcommand{\d}{\mathit{d}}} }
    { \CustomizeMathJax{\newcommand{\d}{\mathrm{d}}} }
```

Used to parse comma and caret arguments for \pd and \td:

```
\CustomizeMathJax{\def\LWRskmathEND{}}
```

Parse the arguments with up to four commas. Argument 6 contains any leftover commas.

```
\CustomizeMathJax{\def\LWRskmathpdstarsub#1#2,#3,#4,#5,#6\LWRskmathEND{
    #1_{#2#3#4#5}%
}}

\CustomizeMathJax{\newcommand{\LWRskmathpdstar}[2]{%
    \LWRskmathpdstarsub{#1}#2,,,,\LWRskmathEND%
}}
```

Parse the arguments with up to two carets. Argument 3 contains any leftover carets. \LWRskmathpdplus is used to only place a plus sign starting after the first term. \LWRskmathpdone is used to only place a 1 digit if a second or later term does not have a power.

```
\CustomizeMathJax{\def\LWRskmathpdnumerator#1^#2^#3\LWRskmathEND{%
    \ifblank{#1}{}{
        \ifblank{#2}{\LWRskmathpdplus\LWRskmathpdone}{\LWRskmathpdplus#2}
    }
}}
```

Parse the arguments with up to two carets. Argument 3 contains any leftover carets.

```
\CustomizeMathJax{\def\LWRskmathpddenominator#1^#2^#3\LWRskmathEND{%
    \ifblank{#1}{}{%
        \ifblank{#2}%
            {\partial{#1}}%
            {\partial{#1}^{#2}}%
    }%
}}
```

Factored from \LWRskmathpdnostarsub, following:

The phrase ^{} appears to be required while parsing the carets. \LWRskmathpdplus is used to only place a plus sign starting after the first term. \LWRskmathpdone is used to only place a 1 digit if a second or later term does not have a power.

This may not be recursion-safe. (Is there really such as a thing as nested differentials?)

```
\CustomizeMathJax{\newcommand{\LWRskmathdonumerator}[5]{%
    \partial^{%
        \def\LWRskmathpdplus{}%
```

```
        \LWRskmathpdnumerator#2^{}^{}\LWRskmathEND%
        \def\LWRskmathpdplus{+}%
        \def\LWRskmathpdone{1}%
        \LWRskmathpdnumerator#3^{}^{}\LWRskmathEND%
        \LWRskmathpdnumerator#4^{}^{}\LWRskmathEND%
        \LWRskmathpdnumerator#5^{}^{}\LWRskmathEND%
    }%
    {#1}%
}}

\CustomizeMathJax{\newcommand{\LWRskmathdodenominator}[4]{%
    \LWRskmathpddenominator#1^{}^{}^{}\LWRskmathEND%
    \ifblank{#2}{}{\,}%
    \LWRskmathpddenominator#2^{}^{}^{}\LWRskmathEND%
    \ifblank{#3}{}{\,}%
    \LWRskmathpddenominator#3^{}^{}^{}\LWRskmathEND%
    \ifblank{#4}{}{\,}%
    \LWRskmathpddenominator#4^{}^{}^{}\LWRskmathEND%
}}
```

Parse the arguments with up to four commas. Argument 6 contains any leftover commas.

```
\CustomizeMathJax{\def\LWRskmathpdnostarsub#1#2,#3,#4,#5,#6\LWRskmathEND{
    \ifblank{#3}{\def\LWRskmathpdone{}}{\def\LWRskmathpdone{1}}
    \frac%
        {\LWRskmathdonumerator{#1}{#2}{#3}{#4}{#5}}%
        {\LWRskmathdodenominator{#2}{#3}{#4}{#5}}%
}}

\CustomizeMathJax{\newcommand{\LWRskmathpdnostar}[2]{%
    \LWRskmathpdnostarsub{#1}#2,,,,,,\LWRskmathEND%
}}

\CustomizeMathJax{\newcommand{\pd}{\ifstar\LWRskmathpdstar\LWRskmathpdnostar}}
```

If `notation=english` or `legacy`, use slanted, else upright:

```
\cs_if_eq:NNTF \__skmath_total_derivative_d: \LWR__skmath_total_derivative_d:
    { \CustomizeMathJax{\newcommand{\LWRskmathtd}{\mathit{d}}} }
    { \CustomizeMathJax{\newcommand{\LWRskmathtd}{\mathrm{d}}} }

\CustomizeMathJax{\def\LWRskmathtdsub#1#2^#3\LWRskmathEND{%
    \frac
        {\LWRskmathtd^{#3}{#1}}
        {\LWRskmathtd{#2}^{#3}}
}}

\CustomizeMathJax{\newcommand{\td}[2]{%
    \LWRskmathtdsub{#1}#2^{}\LWRskmathEND%
}}

\CustomizeMathJax{\newcommand{\E}[1]{%
    \operatorname{E}\left[#1\right]%
}}
```

```
\CustomizeMathJax{\let\given\mid}

\CustomizeMathJax{\newcommand{\P}[1]{%
    \operatorname{P}%
    \left(#1\right)%
}}

\CustomizeMathJax{\newcommand{\var}[1]{%
  \operatorname{Var}\left(#1\right)%
}}
\CustomizeMathJax{\newcommand{\cov}[2]{%
  \operatorname{Cov}\left(#1,#2\right)%
}}
```

Common code for \sin etc:

```
\CustomizeMathJax{\newcommand{\LWRskmathtrigtwo}[2][]{%
    \ifblank{#1}{}{^{#1}}%
    \ifblank{#2}{}{\left(#2\right)}%
}}

\CustomizeMathJax{\newcommand{\LWRskmathtrig}[1]{%
    \operatorname{#1}%
    \LWRskmathtrigtwo%
}}

\CustomizeMathJax{\renewcommand{\sin}{\LWRskmathtrig{sin}}}
\CustomizeMathJax{\renewcommand{\arcsin}{\LWRskmathtrig{arcsin}}}

\CustomizeMathJax{\renewcommand{\cos}{\LWRskmathtrig{cos}}}
\CustomizeMathJax{\renewcommand{\arccos}{\LWRskmathtrig{arccos}}}

\CustomizeMathJax{\renewcommand{\tan}{\LWRskmathtrig{tan}}}
\CustomizeMathJax{\renewcommand{\arctan}{\LWRskmathtrig{arctan}}}

\CustomizeMathJax{\renewcommand{\cot}{\LWRskmathtrig{cot}}}

\CustomizeMathJax{\renewcommand{\sinh}{\LWRskmathtrig{sinh}}}
\CustomizeMathJax{\renewcommand{\cosh}{\LWRskmathtrig{cosh}}}
\CustomizeMathJax{\renewcommand{\tanh}{\LWRskmathtrig{tanh}}}
```

Common code for \ln and \log:

```
\CustomizeMathJax{\newcommand{\LWRskmathlogtwo}[2][]{%
    \ifblank{#1}{}{_{#1}}%
    \ifblank{#2}{}{\left(#2\right)}%
}}

\CustomizeMathJax{\newcommand{\LWRskmathlog}[1]{%
    \operatorname{#1}%
    \LWRskmathlogtwo%
}}
```

```
\CustomizeMathJax{\renewcommand{\ln}{\LWRskmathlog{ln}}}
\CustomizeMathJax{\renewcommand{\log}{\LWRskmathlog{log}}}

\CustomizeMathJax{\newcommand{\LWRskmathexpparens}[1]{%
    \operatorname{exp}%
    \ifblank{#1}{}{\left(#1\right)}%
}}
```

See the skmath source for the original of the following:

```
\CustomizeMathJax{\newcommand{\LWRskmathexpnostar}[1]{%
    \mathchoice
        {\ee^{#1}}
        {\LWRskmathexpparens{#1}}
        {\LWRskmathexpparens{#1}}
        {\LWRskmathexpparens{#1}}
}}

\CustomizeMathJax{\renewcommand{\exp}{\ifstar\LWRskmathexpparens\LWRskmathexpnostar}}
```

Common code for \min etc:

```
\CustomizeMathJax{\newcommand{\LWRskmathminstar}[2][]{%
    \operatorname{\LWRskmathminname}%
    \ifblank{#1}{}{%
        _{\mathchoice{\mathclap{#1}}{#1}{#1}{#1}}
    }%
    \ifblank{#2}{}{#2}%
}}

\CustomizeMathJax{\newcommand{\LWRskmathminnostar}[2][]{%
    \ifblank{#1}%
        {\operatorname{\LWRskmathminname}}%
        {%
            \underset%
                {\mathchoice{\mathclap{#1}}{#1}{#1}{#1}}%
                {\operatorname{\LWRskmathminname}}%
        }%
    \ifblank{#2}{}{\left\{#2\right\}}%
}}
```

\LWRskmathminname seems to be recursion-safe since it is used immediately.

```
\CustomizeMathJax{\newcommand{\LWRskmathmin}[1]{%
    \def\LWRskmathminname{#1}%
    \ifstar\LWRskmathminstar\LWRskmathminnostar%
}}

\CustomizeMathJax{\renewcommand{\min}{\LWRskmathmin{min}}}
\CustomizeMathJax{\renewcommand{\argmin}{\arg\LWRskmathmin{min}}}

\CustomizeMathJax{\renewcommand{\max}{\LWRskmathmin{max}}}
\CustomizeMathJax{\renewcommand{\argmax}{\arg\LWRskmathmin{max}}}
\CustomizeMathJax{\renewcommand{\sup}{\LWRskmathmin{sup}}}
\CustomizeMathJax{\renewcommand{\inf}{\LWRskmathmin{inf}}}
```

```
\CustomizeMathJax{\let\bar\overline}

\CustomizeMathJax{\let\vec\boldsymbol}
```

Remember the original definitions:

```
\CustomizeMathJax{\let\LWRskmathRe\Re}
\CustomizeMathJax{\let\LWRskmathIm\Im}
```

Redefine depending on `notation=iso`:

```
\bool_if:NTF\g__skmath_iso_complex_parts_bool{
    \CustomizeMathJax{\renewcommand{\Re}[1]{%
        \LWRskmathRe%
        \ifblank{#1}{}{\left(#1\right)}%
    }}
    \CustomizeMathJax{\renewcommand{\Im}[1]{%
        \LWRskmathIm%
        \ifblank{#1}{}{\left(#1\right)}%
    }}
}{
    \CustomizeMathJax{\renewcommand{\Re}[1]{%
        \operatorname{Re}%
        \ifblank{#1}{}{#1}%
    }}
    \CustomizeMathJax{\renewcommand{\Im}[1]{%
        \operatorname{Im}%
        \ifblank{#1}{}{#1}%
    }}
}

\ExplSyntaxOff
\end{warpMathJax}
```

File 449 **lwarp-slantsc.sty**

§ 557 Package

slantsc

(*Emulates or patches code by* Harald Harders.)

Pkg slantsc slantsc is emulated for HTML, and used as-is for print output.

for HTML output:

```
\LWR@ProvidesPackagePass{slantsc}[2012/01/01]

\newcommand*{\LWR@HTML@noscshape}{}
\LWR@formatted{noscshape}

\FilenameNullify{%
    \LetLtxMacro\noscshape\@empty%
}
```

File 450 **lwarp-slashed.sty**

§ 558 Package slashed

(*Emulates or patches code by* David Carlisle.)

Pkg slashed slashed works as-s for HTML SVG math. For MathJax, emulation is provided.

for HTML output:

```
\LWR@ProvidesPackagePass{slashed}[1997/01/16]

\begin{warpMathJax}
\CustomizeMathJax{\newcommand{\slashed}[1]{\cancel{#1}}}
\end{warpMathJax}
```

File 451 **lwarp-soul.sty**

§ 559 Package soul

(*Emulates or patches code by* Melchior FRANZ.)

Pkg soul soul is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{soul}[2003/11/17]
\RequirePackage{xcolor}% for \convertcolorspec
```

Storage for the colors to use:

```
\newcommand*{\LWR@soululcolor}{}

\newcommand*{\LWR@soulstcolor}{}

% \definecolor{LWR@soulhlcolordefault}{HTML}{F8E800}
% \newcommand*{\LWR@soulhlcolor}{LWR@soulhlcolordefault}
\newcommand*{\LWR@soulhlcolor}{}
```

\so {⟨*text*⟩}

Basic markup with CSS:

```
\newcommand{\so}[1]{%
\InlineClass(letter-spacing:.2ex){letterspacing}{#1}%
}
```

\caps {⟨*text*⟩}

```
\newcommand{\caps}[1]{%
    \InlineClass%
        (font-variant:small-caps;letter-spacing:.1ex)%
        {capsspacing}{#1}%
}
```

\LWR@soulcolor {⟨*text*⟩} {⟨*color*⟩} {⟨*class*⟩} {⟨*colorstyle*⟩} {⟨*FormatWPstyle*⟩}

Add colors if not empty:

```
\newcommand{\LWR@soulcolor}[5]{%
\ifcsempty{#2}%
{%
    \InlineClass(#5){#3}{#1}%
}%
{%
    \convertcolorspec{named}{\@nameuse{#2}}{HTML}\LWR@tempcolor%
    \LWR@htmlspanclass[#5;#4:\LWR@origpound\LWR@tempcolor]{#3}{#1}%
}%
}

\newcommand{\ul}[1]{%
\LWR@soulcolor{#1}{LWR@soululcolor}{uline}{text-decoration-color}%
    {text-decoration:underline; text-decoration-skip: auto;}%
}

\newcommand{\st}[1]{
\LWR@soulcolor{#1}{LWR@soulstcolor}{sout}{text-decoration-color}%
    {text-decoration:line-through}%
}

\newcommand{\hl}[1]{
\LWR@soulcolor{#1}{LWR@soulhlcolor}{highlight}{background-color}%
    {background:\LWR@origpound{}F8E800}
}
```

Nullified:

```
\newcommand*{\soulaccent}[1]{}
\newcommand*{\soulregister}[2]{}
\newcommand{\sloppyword}[1]{#1}
\newcommand*{\sodef}[5]{\DeclareRobustCommand*#1[1]{\so{##1}}}
\newcommand*{\resetso}{}
\newcommand*{\capsdef}[5]{}
\newcommand*{\capsreset}{}
\newcommand*{\capssave}[1]{}
\newcommand*{\capsselect}[1]{}
\newcommand*{\setul}[2]{}
\newcommand*{\resetul}{}
\newcommand*{\setuldepth}[1]{}
\newcommand*{\setuloverlap}[1]{}
\newcommand*{\<}{}
```

Set colors:

```
\newcommand*{\setulcolor}[1]{\renewcommand{\LWR@soululcolor}{#1}}
\newcommand*{\setstcolor}[1]{\renewcommand{\LWR@soulstcolor}{#1}}
\newcommand*{\sethlcolor}[1]{\renewcommand{\LWR@soulhlcolor}{#1}}
```

Long versions of the user-level macros:

```
\let\textso\so
\let\textul\ul
\let\texthl\hl
\let\textcaps\caps
```

File 452 **lwarp-soulpos.sty**

§ 560 Package soulpos

(*Emulates or patches code by* Javier Bezos.)

Pkg soulpos soulpos is emulated.

for HTML output:

```
\RequirePackage{soul}
\RequirePackage{soulutf8}
\LWR@ProvidesPackageDrop{soulpos}[2012/02/25]

\NewDocumentCommand{\ulposdef}{m o m}{}

\newdimen\ulwidth

\newcommand\ifulstarttype[1]{%
\expandafter\@secondoftwo%
}

\newcommand\ifulendtype[1]{%
\expandafter\@secondoftwo%
}

\newcommand{\ulstarttype}{0}
\newcommand{\ulendtype}{0}
\newcommand\ulpostolerance{0}%
```

File 453 **lwarp-soulutf8.sty**

§ 561 Package soulutf8

Pkg soulutf8 soulutf8 is emulated.

lwarp's HTML output naturally supports UTF-8 encoding.

for HTML output:

```
\LWR@ProvidesPackageDrop{soulutf8}[2016/05/16]
\RequirePackage{soul}
```

File 454 **lwarp-splitbib.sty**

§ 562 Package splitbib

(*Emulates or patches code by* Nicolas Markey.)

Pkg splitbib splitbib is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{splitbib}[2005/12/22]
```

```
\def\NMSB@stylebox#1#2{%
\begin{BlockClass}[text-align:center ; border: 1px solid black]{splitbibbox}
    \csname SB\NMSB@level font\endcsname{\LWR@textcurrentfont{#1#2}}
\end{BlockClass}
}

\def\NMSB@stylebar#1#2{%
\begin{BlockClass}[%
    text-align:center ;
    border-top: 1px solid black ;
    border-bottom: 1px solid black ;
]{splitbibbar}
    \csname SB\NMSB@level font\endcsname{\LWR@textcurrentfont{#1#2}}
\end{BlockClass}
}

\def\NMSB@styledash#1#2{%
\begin{BlockClass}[%
    text-align:center ;
]{splitbibdash}
    \csname SB\NMSB@level font\endcsname{\LWR@textcurrentfont{---~#1#2~---}}
\end{BlockClass}
}

\def\NMSB@stylenone#1#2{%
    \par
}

\def\NMSB@stylesimple#1#2{%
\par
 \csname SB\NMSB@level font\endcsname{\LWR@textcurrentfont{#1#2}}
\par
}
```

File 455 **lwarp-splitidx.sty**

§ 563 Package

splitidx

(*Emulates or patches code by* Markus Kohm.)

Pkg splitidx splitidx is patched for use by lwarp.

If the latexmk option is selected for lwarp, *latexmk* will compile the document but will *not* compile the indexes. **lwarpmk printindex** and **lwarpmk htmlindex** will still be required.

⚠ \thepage When using \AtWriteToIndex or \AtNextWriteToIndex, the user must not refer to \thepage during HTML output, as the concept of a page number is meaningless. Instead, do

```
\addtocounter{LWR@autoindex}{1}
\LWR@new@label{LWRindex-\arabic{LWR@autoindex}}
```

where the \index-like action occurs, and then refer to \arabic{LWR@autoindex} instead of \thepage where the reference should occur.

See section 682.17 in the lwarp-patch-memoir package for the \@@wrspindexhyp macro as an example.

for HTML output:

```
\LWR@ProvidesPackagePass{splitidx}[2016/02/18]

\catcode`\_=12%
\xpatchcmd{\newindex}
    {\jobname-#2.idx}
    {\jobname-#2_html.idx}
    {}
    {\LWR@patcherror{splitidx}{@newindex}}
\catcode`\_=8%
```

Patched to use lwarp's automatic indexing counter instead of \thepage:

```
\renewcommand*{\@wrsindex}[2][]{%
  \ifx\relax#1\relax
    \if@splitidx
      \@wrsindex[idx]{#2}%
    \else
      \def\@tempa{#2}%
      \if@verbindex\@onelevel@sanitize\@tempa\fi
      \@wrindex{\@tempa}%
    \fi
  \else
    \def\@tempa{#2}%
    \csname index@#1@hook\endcsname
%     \expandafter\ifx\csname @@wrsindex\endcsname\relax
    \addtocounter{LWR@autoindex}{1}%                    lwarp
    \label{LWRindex-\arabic{LWR@autoindex}}%    lwarp
%       \@@@wrsindex{#1}{{\@tempa}{\thepage}}%
      \@@@wrsindex{#1}{{\@tempa}{\arabic{LWR@autoindex}}}%
%     \else
%       \def\@tempb{\@@wrsindex{#1}}%
%       \expandafter\@tempb\@tempa||\\%
%     \fi
    \endgroup
    \@esphack
  \fi
}
```

lwarp defines sectioning commands with xparse, so the below patches are done as temporary redefinitions instead of being \let.

```
\xpatchcmd{\printsubindex}
    {\let\section\subsection}
    {\renewcommand*{\section}{\subsection}}
    {}
    {\LWR@patcherror{splitidx}{printsubindex-section}}

\xpatchcmd{\printsubindex}
    {\let\chapter\section}
```

```
    {\renewcommand*{\chapter}{\section}}
    {}
    {\LWR@patcherror{splitidx}{printsubindex-chapter}}

\xpatchcmd{\printsubindex}
    {\let\@makechapterhead\section}
    {\def\@makechapterhead{\section}}
    {}
    {\LWR@patcherror{splitidx}{printsubindex-chapter}}
```

File 456 **lwarp-srcltx.sty**

§ 564 Package srcltx

Pkg srcltx srcltx is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{srcltx}[2006/11/12]

\newif\ifSRCOK \SRCOKfalse
\newcommand*\srcIncludeHook[1]{}
\newcommand*\srcInputHook[1]{}
\newcommand*\MainFile{}
\def\MainFile{\jobname.tex}
\newcommand*\CurrentInput{}
\gdef\CurrentInput{\MainFile}
\newcommand\Input{}
\let\Input\input
```

File 457 **lwarp-srctex.sty**

§ 565 Package srctex

Pkg srctex srctex is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{srctex}[2006/11/12]
\LWR@origRequirePackage{lwarp-srcltx}
```

File 458 **lwarp-stabular.sty**

§ 566 Package stabular

(*Emulates or patches code by* Sigitas Tolušis.)

Pkg stabular stabular is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{stabular}[2014/03/20]
```

Env stabular [⟨*vpos*⟩] {⟨*colspec*⟩}

```
\newenvironment{stabular}[2][c]
{
\begin{tabular}[#1]{#2}
\renewcommand{\noalign}[1]{}
}
{\end{tabular}}
```

Env stabular {⟨*width*⟩} [⟨*vpos*⟩] {⟨*colspec*⟩}

```
\NewDocumentEnvironment{stabular*}{m o m}
{
\begin{tabular}[#2]{#3}
\renewcommand{\noalign}[1]{}
}
{\end{tabular}}
```

File 459 **lwarp-stackengine.sty**

§ 567 Package

stackengine

(*Emulates or patches code by* Steven B. Segletes.)

Pkg stackengine stackengine is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{stackengine}[2017/02/13]
```

The original version is neccessary for the patched \@stack and \stackanchor, where nesting lateximages does not work:

```
\LetLtxMacro\LWR@orig@stackengine\stackengine

\renewcommand*{\stackengine}[8]{%
    \ifstrequal{#4}{O}%
        {\begin{lateximage}[\ImageAltText]}%
        {\begin{lateximage}[\ImageAltText][][vertical-align:top]}%
    \LWR@orig@stackengine{#1}{#2}{#3}{#4}{#5}{#6}{#7}{#8}%
    \end{lateximage}%
}
```

\@stack uses a lateximage with a vertical alignment:

```
\LetLtxMacro\LWR@orig@@stack\@stack

\xpatchcmd{\LWR@orig@@stack}{\stackengine}{\LWR@orig@stackengine}
    {}
    {\LWR@patcherror{stackengine}{LWR@orig@@stack}}

\renewcommand*{\@stack}[4]{%
    \ifstrequal{#3}{O}%
        {\begin{lateximage}[\ImageAltText]}%
```

```
        {\begin{lateximage}[\ImageAltText][][vertical-align:top]}%
    \LWR@orig@@stack{#1}{#2}{#3}{#4}%
    \end{lateximage}%
}
```

The lapping macros are disabled for HTML:

```
\newcommand*\LWR@HTML@@stacklap[4]{#3}
\LWR@formatted{@stacklap}
```

`\stackanchor` is patched for two instances of `\stackengine`. A `lateximage` with vertical alignment is used.

```
\xpatchcmd{\stackanchor}{\stackengine}{\LWR@orig@stackengine}
    {}
    {\LWR@patcherror{stackengine}{stackanchor patch 1}}

\xpatchcmd{\stackanchor}{\stackengine}{\LWR@orig@stackengine}
    {}
    {\LWR@patcherror{stackengine}{stackanchor patch 2}}

\xpretocmd{\stackanchor}
    {\begin{lateximage}[\ImageAltText][][vertical-align:middle]}
    {}
    {\LWR@patcherror{stackengine}{stackanchor pre}}

\xapptocmd{\stackanchor}{\end{lateximage}}
    {}
    {\LWR@patcherror{stackengine}{stackanchor app}}
```

`\Centerstack` is simply placed inside a `lateximage` with a vertical alignment:

```
\xpretocmd{\Centerstack}
    {\begin{lateximage}[\ImageAltText][][vertical-align:middle]}
    {}
    {\LWR@patcherror{stackengine}{Centerstack pre}}

\xapptocmd{\Centerstack}{\end{lateximage}}
    {}
    {\LWR@patcherror{stackengine}{Centerstack app}}
```

`\savestack` reverts to print mode while saving the box, then places it inside a `lateximage` when used:

```
\renewcommand*\savestack[2]{%
  \xdef\sv@name{\stack@macro@name{#1}}%
  \@ifundefined{\sv@name content}{%
    \expandafter\newsavebox\expandafter{\csname\sv@name content\endcsname}%
   }{}%
    \begingroup%    lwarp
    \LWR@restoreorigformatting%     lwarp
   \RenewDocumentEnvironment{lateximage}{s o s o o d()}{}{}% lwarp: inside group
  \expandafter\LWR@gsavebox\csname\sv@name content\endcsname{#2}%
  \expandafter\gdef\expandafter#1\expandafter{%
        \expandafter\begin\expandafter{lateximage\expandafter}%     lwarp
```

```
        \expandafter\usebox\expandafter%
        {\csname\sv@name content\endcsname}%
        \expandafter\end\expandafter{lateximage\expandafter}%       lwarp
    }%
    \endgroup%      lwarp
}
```

File 460 **lwarp-stackrel.sty**

§ 568 Package stackrel

(*Emulates or patches code by* Heiko Oberdiek.)

Pkg stackrel stackrel is used as-is for SVG math, and is emulated for MathJax.

for HTML output:

```
\LWR@ProvidesPackagePass{stackrel}[2016/05/16]

\begin{warpMathJax}
\CustomizeMathJax{\renewcommand{\stackrel}[3][]{%
    \mathrel{\mathop{#3}\limits_{#1}^{#2}}%
}}

\CustomizeMathJax{\newcommand{\stackbin}[3][]{%
    \mathbin{\mathop{#3}\limits_{#1}^{#2}}%
}}
\end{warpMathJax}
```

File 461 **lwarp-statex2.sty**

§ 569 Package statex2

(*Emulates or patches code by* Rodney A Sparapani.)

Pkg statex2 statex2 is patched for use by lwarp, and emulated for MathJax.

⚠ As of this version, option autobold does not appear to work for PDF output.

⚠ For MathJax, the tilde character ~ does not create \sim. Use \sim directly.

⚠ Because MathJax has limited conditional processing:

- \wrap only creates square braces, no matter what its optional arguments.
- \P, \pCau, \pN, and \pU do not handle special cases.

⚠ \and To have \and work if using \maketitle, place the following after the start of the document:

```
\newcommand*{\and}{%
    \relax\ifmmode%
```

```
            \expandafter\;\mb{\mathrm{and}}\;%
        \else%
            \expandafter\STATEXand%
        \fi%
    }
```

for HTML output:

```
\LWR@ProvidesPackagePass{statex2}[2011/09/14]

\newcommand*{\LWR@HTML@Alpha}[1][]{%
    \fcolorbox{black}{ForestGreen}{\textcolor{white}{\textsf{ALPHA}}}%
    \textbf{\textcolor{ForestGreen}{\textsf{#1}}}%
}
\LWR@formatted{Alpha}

\newcommand*{\LWR@HTML@List}[1]{%
    \textbf{\textcolor{Dandelion}{\textsf{L}\textsubscript{\textit{#1}}}}%
}
\LWR@formatted{List}

\newcommand*{\LWR@HTML@Snd}[1][]{%
    \fcolorbox{black}{Dandelion}{\textcolor{white}{\textsf{2nd}}}%
    \textbf{\textcolor{Dandelion}{\textsf{#1}}}%
}
\LWR@formatted{Snd}

\begin{warpMathJax}
\LWR@infoprocessingmathjax{statex2}

\CustomizeMathJax{\newcommand{\cpi}{\boldsymbol{\pi}}}
\CustomizeMathJax{\newcommand{\c}[1]{\boldsymbol{\mathrm{#1}}}}
\CustomizeMathJax{\newcommand{\sfsl}[1]{\mathsf#1}}%     not slanted

\if@manualbold
\CustomizeMathJax{\newcommand{\mb}[1]{#1}}
\else
\CustomizeMathJax{\newcommand{\mb}[1]{\boldsymbol{#1}}}
\fi

\CustomizeMathJax{\newcommand{\diag}{\mb{\mathrm{diag}}}}
\CustomizeMathJax{\newcommand{\blockdiag}{\mb{\mathrm{blockdiag}}}}
\CustomizeMathJax{\newcommand{\erf}{\mb{\mathrm{erf}}}}
\CustomizeMathJax{\newcommand{\logit}{\mb{\mathrm{logit}}}}
\CustomizeMathJax{\newcommand{\trace}{\mb{\mathrm{trace}}}}

\CustomizeMathJax{\newcommand{\chisq}{{\mb{\chi^2}}}}
\CustomizeMathJax{\newcommand{\deriv}[2]{\mb{\frac{\d{}}{\d{#1}}}\wrap{\mb{#2}}}}
\CustomizeMathJax{\newcommand{\derivf}[2]{\mb{\frac{\d{}}{\d{#2}}}\wrap{\mb{#1}}}}
\CustomizeMathJax{\newcommand{\e}[1]{\mb{\mathrm{e}^{#1}}}}
\CustomizeMathJax{\newcommand{\E}[2][]{\mb{\mathrm{E}}_{\mb{#1}} \wrap{\mb{#2}}}}
\CustomizeMathJax{\newcommand{\ha}{{\mb{\frac{\alpha}{2}}}}}
\CustomizeMathJax{\newcommand{\I}[2][]{%
    \mb{\mathrm{I}}_{\mb{#1}} \LWRwrapparen{\mb{#2}}%
}}
\CustomizeMathJax{\newcommand{\IBeta}[2]{%
    \mb{\frac{\Gamma[#1+#2]}{\Gamma[#1]\Gamma[#2]}}%
```

```
}}
\CustomizeMathJax{\newcommand{\If}{\;\mb{\mathrm{if}}\;}}
\CustomizeMathJax{\newcommand{\im}{\mb{\mathrm{i}}}}
\CustomizeMathJax{\newcommand{\ol}{\overline}}
\CustomizeMathJax{\newcommand{\ow}{\;\mb{\mathrm{otherwise}}\;}}
\CustomizeMathJax{\newcommand{\pderiv}[2]{%
    \mb{\frac{\partial}{\partial #1}}\wrap{\mb{#2}}%
}}
\CustomizeMathJax{\newcommand{\pderivf}[2]{%
    \mb{\frac{\partial}{\partial #2}}\wrap{\mb{#1}}%
}}
\CustomizeMathJax{\newcommand{\sd}{\mb{\sigma}}}
\CustomizeMathJax{\newcommand{\ul}{\underline}}
\CustomizeMathJax{\newcommand{\V}[2][]{\mb{\mathrm{V}}_{\mb{#1}} \wrap{\mb{#2}}}}
\CustomizeMathJax{\newcommand{\vs}{\;\mb{\mathrm{vs.}}\;}}
\CustomizeMathJax{\newcommand{\where}{\;\mb{\mathrm{where}}\;}}
\CustomizeMathJax{\newcommand{\wrap}[2][]{\left[ #2 \right]}}%         only []
\CustomizeMathJax{\newcommand{\LWRwrapparen}[1]{\left( #1 \right)}}%    lwarp

% \CustomizeMathJax{\renewcommand{~}{\mb{\sim}}}% doesn't work,
% replace <space>~<space> with <space>\sim<space>

\CustomizeMathJax{\newcommand{\iid}{\;\stackrel{\mb{\mathrm{iid}}}{\sim}\;}}
\CustomizeMathJax{\newcommand{\ind}{\;\stackrel{\mb{\mathrm{ind}}}{\sim}\;}}
\CustomizeMathJax{\newcommand{\indpr}{%
    \;\stackrel{\mb{\mathrm{ind}}}{\stackrel{\mb{\mathrm{prior}}}{\sim}}\;%
}}
\CustomizeMathJax{\newcommand{\post}{\;\stackrel{\mb{\mathrm{post}}}{\sim}\;}}
\CustomizeMathJax{\newcommand{\prior}{\;\stackrel{\mb{\mathrm{prior}}}{\sim}\;}}

\CustomizeMathJax{\let\STATEXGamma=\Gamma}
\CustomizeMathJax{\renewcommand{\Gamma}[1][]{\mb{\STATEXGamma}\LWRwrapparen{\mb{#1}}}}
%
\CustomizeMathJax{\renewcommand{\and}{\;\mb{\mathrm{and}}\;}}
%
\CustomizeMathJax{\newcommand{\H}{\mb{\mathrm{H}}}}
%
\CustomizeMathJax{\newcommand{\P}[2][]{\mb{\mathrm{P}}_{\mb{#1}}\wrap{\mb{#2}}}}
%
\CustomizeMathJax{\newcommand{\|}{\mb{\mid}}}

\CustomizeMathJax{\newcommand{\B}[1]{\mb{\mathrm{B}}\LWRwrapparen{\mb{#1}}}}
\CustomizeMathJax{\newcommand{\BB}[1]{\mb{\mathrm{BetaBin}}\LWRwrapparen{\mb{#1}}}}
\CustomizeMathJax{\newcommand{\Bin}[2]{\mb{\mathrm{Bin}}\LWRwrapparen{\mb{#1,\ #2}}}}
\CustomizeMathJax{\newcommand{\Dir}[1]{\mb{\mathrm{Dirichlet}}\LWRwrapparen{\mb{#1}}}}
\CustomizeMathJax{\newcommand{\HG}[3]{%
    \mb{\mathrm{Hypergeometric}}\LWRwrapparen{\mb{#1,\ #2,\ #3}}%
}}
\CustomizeMathJax{\newcommand{\M}[2]{%
    \mb{\mathrm{Multinomial}}\LWRwrapparen{\mb{#1,\ #2}}%
}}
\CustomizeMathJax{\newcommand{\NB}[2]{\mb{\mathrm{NegBin}}\LWRwrapparen{\mb{#1,\ #2}}}}
\CustomizeMathJax{\newcommand{\Poi}[1]{\mb{\mathrm{Poisson}}\LWRwrapparen{\mb{#1}}}}
\CustomizeMathJax{\let\Poisson=\Poi}

```

```
\CustomizeMathJax{\newcommand{\pBB}[4][x]{%
    \mb{\frac{\Gamma[#2+1]\Gamma[#3+#1]\Gamma[#2+#4-#1]\Gamma[#3+#4]}%
    {\Gamma[#1+1]\Gamma[#2-#1+1]\Gamma[#2+#3+#4]\Gamma[#3]\Gamma[#4]}%
    \I[#1]{\{0, 1,\., #2\}}, \where #3>0,\; #4>0 \and n=1, 2,\.}%
}}
\CustomizeMathJax{\newcommand{\pBin}[3][x]{%
    \mb{\binom{#2}{#1}#3^{#1}} \LWRwrapparen{\mb{{1-#3}^{#2-#1}}}%
    \mb{\I[#1]{\{0,1,\.,#2\}}, \where p \in (0, 1) \and n=1, 2,\.}%
}}
\CustomizeMathJax{\newcommand{\pPoi}[2][x]{%
    \mb{\frac{1}{#1!}#2^{#1}\e{-#2}\I[#1]{\{0, 1,\.\}}, \where #2>0}%
}}

\CustomizeMathJax{\newcommand{\Cau}[2]{\mb{\mathrm{Cauchy}}\LWRwrapparen{\mb{#1,\ #2}}}}
\CustomizeMathJax{\let\Cauchy=\Cau}
\CustomizeMathJax{\newcommand{\Chi}[2][]{%
    \chisq_{\mb{#1}}\LWRwrapparen{\mb{#2}}%
}}
\CustomizeMathJax{\let\Chisq=\Chi}
\CustomizeMathJax{\newcommand{\Bet}[2]{\mb{\mathrm{Beta}}\LWRwrapparen{\mb{#1,\ #2}}}}
\CustomizeMathJax{\let\Beta=\Bet}
\CustomizeMathJax{\newcommand{\Exp}[1]{\mb{\mathrm{Exp}}\LWRwrapparen{\mb{#1}}}}
\CustomizeMathJax{\newcommand{\F}[2]{\mb{\mathrm{F}}\LWRwrapparen{\mb{#1,\ #2}}}}
\CustomizeMathJax{\newcommand{\Gam}[2]{\mb{\mathrm{Gamma}}\LWRwrapparen{\mb{#1,\ #2}}}}
\CustomizeMathJax{\newcommand{\IC}[1]{\mb{\mathrm{\chi^{-2}}}\LWRwrapparen{\mb{#1}}}}
\CustomizeMathJax{\newcommand{\IG}[2]{%
    \mb{\mathrm{Gamma^{-1}}}\LWRwrapparen{\mb{#1,\ #2}}%
}}
\CustomizeMathJax{\newcommand{\IW}[2]{%
    \mb{\mathrm{Wishart^{-1}}}\LWRwrapparen{\mb{#1,\ #2}}%
}}
\CustomizeMathJax{\newcommand{\Log}[2]{%
\mb{\mathrm{Logistic}}\LWRwrapparen{\mb{#1,\ #2}}%
}}
\CustomizeMathJax{\newcommand{\LogN}[2]{%
    \mb{\mathrm{Log\!-\!N}}\LWRwrapparen{\mb{#1,\ #2}}%
}}
\CustomizeMathJax{\newcommand{\N}[3][]{%
    \mb{\mathrm{N}}_{\mb{#1}}\LWRwrapparen{\mb{#2,\ #3}}%
}}
\CustomizeMathJax{\newcommand{\Par}[2]{\mb{\mathrm{Pareto}}\LWRwrapparen{\mb{#1,\ #2}}}}
\CustomizeMathJax{\let\Pareto=\Par}
\CustomizeMathJax{\newcommand{\Tsq}[2]{\mb{\mathrm{T^2}}\LWRwrapparen{\mb{#1,\ #2}}}}
\CustomizeMathJax{\newcommand{\U}[1]{\mb{\mathrm{U}}\LWRwrapparen{\mb{#1}}}}
\CustomizeMathJax{\newcommand{\W}[2]{\mb{\mathrm{Wishart}}\LWRwrapparen{\mb{#1,\ #2}}}}

\CustomizeMathJax{\renewcommand{\t}[1]{\mb{\mathrm{t}}\LWRwrapparen{\mb{#1}}}}

\CustomizeMathJax{\newcommand{\pBet}[3][x]{%
    \IBeta{#2}{#3}%
    #1^{#2-1}\LWRwrapparen{1-#1}^{#3-1}\I[#1]{0,\ 1}, \where #2>0 \and #3>0%
}}
\CustomizeMathJax{\newcommand{\pCau}[3][x]{%
%     \ifthenelse{\equal{#2, #3}{0, 1}}{\frac{1}{\cpi\LWRwrapparen{1+#1}^2}}%
  {\frac{1}{#3\cpi\left\{1+\wrap{\LWRwrapparen{x-#2}/#3}^2\right\}}, \where #3>0}%
```

```
}}% no special case for 0,1
\CustomizeMathJax{\newcommand{\pChi}[2][x]{%
    \frac{2^{-#2/2}}{\Gamma[#2/2]}#1^{#2/2-1}\e{-#1/2}%
    \I[#1]{0,\infty}, \where #2>0%
}}
\CustomizeMathJax{\newcommand{\pExp}[2][x]{%
    \frac{1}{#2}\e{-#1/#2}\I[#1]{0,\infty},%
    \where #2>0%
}}
\CustomizeMathJax{\newcommand{\pGam}[3][x]{%
    \frac{#3^{#2}}{\Gamma[#2]}#1^{#2-1}\e{-#3#1}%
    \I[#1]{0,\infty}, \where #2>0 \and #3>0%
}}
\CustomizeMathJax{\newcommand{\pN}[3][x]{%
%     \ifthenelse{\equal{#2, #3}{0, 1}}%
%     {\frac{1}{\sqrt{2\cpi}}\e{-#1^2/2}}%
    {\frac{1}{\sqrt{2\cpi \cdot #3}}\e{-\LWRwrapparen{#1-#2}^2/2 \cdot #3}}%
}}% no test for 0,1, must add \cdot
\CustomizeMathJax{\newcommand{\pPar}[3][x]{%
    \frac{#3}{#2\LWRwrapparen{1+#1/#2}^{#3+1}}\I[#1]{0,\infty},%
    \where #2>0 \and #3>0%
}}
\CustomizeMathJax{\newcommand{\pU}[3][x]{%
%     \ifthenelse{\equal{#2, #3}{0, 1}}{\I[#1]{0,\ 1}}%
    {\frac{1}{#3-#2}\I[#1]{#2,\ #3}, \where #2<#3}%
}}% no special case for 0,1

\CustomizeMathJax{\newcommand{\=}[1]{\bar{#1}}}
\CustomizeMathJax{\let\^\widehat}
\CustomizeMathJax{\let\~\widetilde}
\CustomizeMathJax{\newcommand{\'}[1]{\LWRwrapparen{\mb{#1}}}}
\CustomizeMathJax{\newcommand{\b}[1]{\bar{#1}}}
\CustomizeMathJax{\newcommand{\c}[1]{\mb{\mathrm{#1}}}}
\CustomizeMathJax{\newcommand{\d}[1]{\,\mb{\mathrm{d}{#1}}}}
\CustomizeMathJax{\newcommand{\.}{\mb{\ldots}}}
\end{warpMathJax}
```

File 462 **lwarp-statistics.sty**

§ 570 Package

statistics

(*Emulates or patches code by* Julien Rivaud.)

Pkg statistics statistics is patched for use by lwarp.

⚠ \color The statistics documentation examples include the use of the \color macro. Use \textcolor instead.

⚠ math The statistics package uses math arrays, but the HTML version uses text tabulars to allow text copy/paste. If math is required, use \ensuremath or \(and \) as needed.

Pre/postline is ignored, and \hline is used instead. Each table will have an \hline above and below as a frame.

for HTML output:

```
\LWR@ProvidesPackagePass{statistics}[2019/09/29]
\ExplSyntaxOn
```

To use text `tabular` instead of math `array`. This allows text copy/paste of the results.

In the following, all changes for the Lwarp package are labelled "lwarp".

Redefined using the lwarp version of &:

```
\StartDefiningTabulars%     lwarp
\cs_set_protected_nopar:Nn \__statistics_table_make:nn {
    \int_compare:nT
            { 0 < \l__statistics_table_maxcols_int
                = \l__statistics_nbvals_int } {
        \__statistics_table_end:
        \tl_use:N \l__statistics_table_sep_tl
        \__statistics_table_start:
    }
    \int_incr:N \l__statistics_nbvals_int
    \int_incr:N \l__statistics_currange_int
    \fp_add:Nn \l__statistics_curtotal_fp { #2 }
    \__statistics_set_if_shown:N \l_tmpa_bool
    \tl_set:Nx \l_tmpa_tl {
        \exp_not:n { & \tl_set:Nn \currentcolumn } {
            \int_use:N \l__statistics_currange_int
        }
    }
    \bool_if:NTF \l_tmpa_bool {
        \tl_put_right:Nn \l_tmpa_tl
            {\__statistics_table_shown_format:n}
    }{
        \tl_put_right:Nn \l_tmpa_tl
            {\__statistics_table_hidden_format:n}
    }
    \seq_put_right:Nn \l__statistics_store_values_seq { #1 }
    \bool_if:NT \l__statistics_table_values_bool {
        \tl_put_right:Nx \l__statistics_table_values_tl {
            \exp_not:V \l_tmpa_tl {
                \exp_not:n {
                    \__statistics_table_values_format:n { #1 }
                }
            }
        }
    }
    \seq_put_right:Nx \l__statistics_store_counts_seq { \fp_eval:n {#2} }
    \bool_if:NT \l__statistics_table_counts_bool {
        \tl_put_right:Nx \l__statistics_table_counts_tl {
            \exp_not:V \l_tmpa_tl {
                \exp_not:n {
                    \__statistics_table_counts_format:n {
                        { \__statistics_table_allcounts_format:n { #2 } }
                    }
                }
            }
```

```
        }
    }
    \bool_if:NT \l__statistics_table_icc_bool {
        \tl_put_right:Nx \l__statistics_table_icc_tl {
            \exp_not:V \l_tmpa_tl {
                \exp_not:n { \__statistics_table_icc_format:n }
                {
                    \exp_not:n{ \__statistics_table_allcounts_format:n }
                        { \fp_use:N \l__statistics_curtotal_fp }
                }
            }
        }
    }
    \bool_if:NT \l__statistics_table_dcc_bool {
        \tl_put_right:Nx \l__statistics_table_dcc_tl {
            \exp_not:V \l_tmpa_tl {
                \exp_not:n { \__statistics_table_dcc_format:n }
                {
                    \exp_not:n{ \__statistics_table_allcounts_format:n }
                    {
                        \fp_eval:n {
                            \l__statistics_total_fp
                                - \l__statistics_curtotal_fp
                                + #2
                        }
                    }
                }
            }
        }
    }
    \fp_set:Nn \l__statistics_table_curICF_fp {
        round(\l__statistics_curtotal_fp
                / \l__statistics_total_fp,
              \l__statistics_table_round_int)
    }
    \bool_if:NT \l__statistics_table_frequencies_bool {
        \tl_put_right:Nx \l__statistics_table_frequencies_tl {
            \exp_not:V \l_tmpa_tl {
                \exp_not:n { \__statistics_table_frequencies_format:n }
                {
                    \exp_not:n{ \__statistics_table_allfreqs_format:n }
                    {
                        \fp_eval:n {
                            \l__statistics_table_curICF_fp
                                - \l__statistics_table_prevICF_fp
                        }
                    }
                }
            }
        }
    }
    \bool_if:NT \l__statistics_table_icf_bool {
        \tl_put_right:Nx \l__statistics_table_icf_tl {
            \exp_not:V \l_tmpa_tl {
                \exp_not:n { \__statistics_table_icf_format:n }
```

```
                {
                    \exp_not:n{ \__statistics_table_allfreqs_format:n }
                        { \fp_to_decimal:N \l__statistics_table_curICF_fp }
                }
            }
        }
    }
    \bool_if:NT \l__statistics_table_dcf_bool {
        \tl_put_right:Nx \l__statistics_table_dcf_tl {
            \exp_not:V \l_tmpa_tl {
                \exp_not:n { \__statistics_table_dcf_format:n }
                {
                    \exp_not:n{ \__statistics_table_allfreqs_format:n }
                    {
                        \fp_eval:n {
                            1 - \l__statistics_table_prevICF_fp
                        }
                    }
                }
            }
        }
    }
    \fp_set_eq:NN
        \l__statistics_table_prevICF_fp
        \l__statistics_table_curICF_fp
}
\StopDefiningTabulars%  lwarp
```

Redefined using `tabular`. Also, preline and postline do not work correctly with lwarp, which looks for certain tokens to detect `\hline`s, so `\hline` is used instead.

```
\cs_set_protected_nopar:Nn \__statistics_table_end: {
    \tl_set:Nx \l__statistics_table_preamble_tl {
%         \exp_not:n { \begin{array}[ }
        \exp_not:n {\begin{tabular}[ }%      lwarp
            \exp_not:V \l__statistics_table_valign_tl
        \exp_not:n { ] }
                { \exp_not:V \l__statistics_table_headcoltype_tl
                  \prg_replicate:nn { \l__statistics_nbvals_int }
                    { \exp_not:V \l__statistics_table_coltype_tl } }
    }
    \seq_clear:N \l__statistics_table_contents_seq
    \clist_map_inline:nn { values, counts, icc, dcc, frequencies, icf, dcf } {
        \bool_if:cT { l__statistics_table_##1_bool } {
            \seq_put_right:Nv
                    \l__statistics_table_contents_seq
                    { l__statistics_table_##1_tl }
        }
    }
%     $
    \tl_use:N \l__statistics_table_preamble_tl
        \hline%      lwarp
%         \l__statistics_table_preline_tl
        \seq_use:Nn
                \l__statistics_table_contents_seq
```

```
                { \l__statistics_table_newline_tl }
        \\
%         \l__statistics_table_postline_tl
        \hline%      lwarp
%     \end{array}$
    \end{tabular}%      lwarp
}
```

With lwarp, `\ensuremath` creates an SVG image, but its `alt` tag does not contain the text of the contents for copy/paste, since these expressions are usually not simple text. For the statistics package, copy/paste is restored by using text instead of math output.

For the leftmost column. Redefined to use text output:

```
\cs_set_protected_nopar:Nn \__statistics_table_start: {
    \int_zero:N \l__statistics_nbvals_int
    \clist_pop:NNT \l__statistics_table_maxcols_clist \l_tmpa_tl {
        \int_set:Nn \l__statistics_table_maxcols_int { \l_tmpa_tl }
    }
    \clist_map_inline:nn { values, counts, frequencies, icc, icf, dcc, dcf } {
        \tl_set:cx { l__statistics_table_##1_tl } {
%             \exp_not:N \ensuremath {
                \exp_not:N \hbox {
                    \exp_not:c { l__statistics_table_##1_name_tl }
                }
%             }
        }
    }
}
```

For the first row. Redefined to use text output:

```
\RenewDocumentCommand \__statistics_IN:w { m u{;} u{;} m } {
%     \ensuremath{ \left#1 \num{#2} \mathbin{;} \num{#3} \right#4 }
    #1 #2 ; #3 #4%      lwarp
}

\__statistics_setup:nn { table } {
%     values/format = \ensuremath{#1},
    values/format = {#1},%      lwarp
}
```

Added `\ExplSyntaxOn/Off` to avoid errors. (In once instance, a double subscript error appeared.)

```
\RenewDocumentCommand \StatsGraph { +O{} +m +O{} } {
    \group_begin:
    \int_gincr:N \g__statistics_graph_last_int
    \tl_set:Nx \l_tmpa_tl {
        \exp_not:n { g__statistics_graph_xstep_ }
        \int_use:N \g__statistics_graph_last_int
        \exp_not:n { _tl }
    }
    \tl_if_exist:cTF { \l_tmpa_tl } {
        \fp_gset:Nn \g__statistics_graph_xstep_fp
```

```
            { \tl_use:c {\l_tmpa_tl} }
    }{
        \fp_gset:Nn \g__statistics_graph_xstep_fp { \c_one_int }
    }
    \__statistics_setup:nn { graph } { #1, #3 }
    \tl_if_single:nTF { #2 } {
        \cs_if_exist:NF #2 { #2 }
        \tl_set_eq:NN \l__statistics_data_tl #2
    }{
        \tl_set:Nn \l__statistics_data_tl { #2 }
    }
    \fp_zero:N \l__statistics_graph_maxheight_fp
    \fp_set:Nn \l__statistics_graph_minvalue_fp {inf}
    \fp_set:Nn \l__statistics_graph_maxvalue_fp {-inf}
    \fp_zero:N \l__statistics_total_fp
    \int_zero:N \l__statistics_nbvals_int
    \bool_set_true:N \l__statistics_graph_allranges_bool
    \keyval_parse:NNV
            \__statistics_graph_prepare:n
            \__statistics_graph_prepare:nn
            \l__statistics_data_tl
    \tl_clear:N \l__statistics_graph_tikzdata_tl
    \tl_clear:N \l__statistics_graph_tikzinfo_tl
    \int_zero:N \l__statistics_currange_int
    \bool_if:NTF \l__statistics_graph_allranges_bool {
        \bool_if:NTF \l__statistics_graph_cumulative_bool {
\ExplSyntaxOn%     lwarp
            \__statistics_graph_dopicture_cumulative:
\ExplSyntaxOff%    lwarp
        }{
\ExplSyntaxOn%     lwarp
            \__statistics_graph_dopicture_hist:
\ExplSyntaxOff%    lwarp
        }
    }{
\ExplSyntaxOn%    lwarp
        \__statistics_graph_dopicture_comb:
\ExplSyntaxOff%    lwarp
    }
    \iow_now:Nx \@auxout {
        \exp_not:n {
            \ExplSyntaxOn
            \tl_gset:cn
        }
        {
            \exp_not:n {g__statistics_graph_xstep_}
            \int_use:N \g__statistics_graph_last_int
            \exp_not:n {_tl}
        }
        {
            \fp_to_decimal:N \g__statistics_graph_xstep_fp
        }
        \exp_not:n {
            \ExplSyntaxOff
        }
```

```
    }
    \group_end:
}

\ExplSyntaxOff
```

File 463 **lwarp-statmath.sty**

§ 571 Package statmath

(*Emulates or patches code by* Sebastian Ankargren.)

Pkg statmath statmath is used as-is for SVG math, and is emulated for MathJax.

for HTML output:

```
\LWR@ProvidesPackagePass{statmath}[2018/03/08]

\LWR@origRequirePackage{lwarp-common-mathjax-letters}

\begin{warpMathJax}
\LWR@infoprocessingmathjax{statmath}

\ifdefequal{\abcbf}{\mathbf}
    {\CustomizeMathJax{\newcommand{\abcbf}[1]{\mathbf{#1}}}}
    {\CustomizeMathJax{\newcommand{\abcbf}[1]{\boldsymbol{#1}}}}

\CustomizeMathJax{\newcommand{\greekbf}[1]{\boldsymbol{#1}}}

\CustomizeMathJax{\newcommand{\bfA}{\abcbf A}}
\CustomizeMathJax{\newcommand{\bfB}{\abcbf B}}
\CustomizeMathJax{\newcommand{\bfC}{\abcbf C}}
\CustomizeMathJax{\newcommand{\bfD}{\abcbf D}}
\CustomizeMathJax{\newcommand{\bfE}{\abcbf E}}
\CustomizeMathJax{\newcommand{\bfF}{\abcbf F}}
\CustomizeMathJax{\newcommand{\bfG}{\abcbf G}}
\CustomizeMathJax{\newcommand{\bfH}{\abcbf H}}
\CustomizeMathJax{\newcommand{\bfI}{\abcbf I}}
\CustomizeMathJax{\newcommand{\bfJ}{\abcbf J}}
\CustomizeMathJax{\newcommand{\bfK}{\abcbf K}}
\CustomizeMathJax{\newcommand{\bfL}{\abcbf L}}
\CustomizeMathJax{\newcommand{\bfM}{\abcbf M}}
\CustomizeMathJax{\newcommand{\bfN}{\abcbf N}}
\CustomizeMathJax{\newcommand{\bfO}{\abcbf O}}
\CustomizeMathJax{\newcommand{\bfP}{\abcbf P}}
\CustomizeMathJax{\newcommand{\bfQ}{\abcbf Q}}
\CustomizeMathJax{\newcommand{\bfR}{\abcbf R}}
\CustomizeMathJax{\newcommand{\bfS}{\abcbf S}}
\CustomizeMathJax{\newcommand{\bfT}{\abcbf T}}
\CustomizeMathJax{\newcommand{\bfU}{\abcbf U}}
\CustomizeMathJax{\newcommand{\bfV}{\abcbf V}}
\CustomizeMathJax{\newcommand{\bfW}{\abcbf W}}
\CustomizeMathJax{\newcommand{\bfX}{\abcbf X}}
\CustomizeMathJax{\newcommand{\bfY}{\abcbf Y}}
\CustomizeMathJax{\newcommand{\bfZ}{\abcbf Z}}
```

```
\CustomizeMathJax{\newcommand{\bfa}{\abcbf a}}
\CustomizeMathJax{\newcommand{\bfb}{\abcbf b}}
\CustomizeMathJax{\newcommand{\bfc}{\abcbf c}}
\CustomizeMathJax{\newcommand{\bfd}{\abcbf d}}
\CustomizeMathJax{\newcommand{\bfe}{\abcbf e}}
\CustomizeMathJax{\newcommand{\bff}{\abcbf f}}
\CustomizeMathJax{\newcommand{\bfg}{\abcbf g}}
\CustomizeMathJax{\newcommand{\bfh}{\abcbf h}}
\CustomizeMathJax{\newcommand{\bfi}{\abcbf i}}
\CustomizeMathJax{\newcommand{\bfj}{\abcbf j}}
\CustomizeMathJax{\newcommand{\bfk}{\abcbf k}}
\CustomizeMathJax{\newcommand{\bfl}{\abcbf l}}
\CustomizeMathJax{\newcommand{\bfm}{\abcbf m}}
\CustomizeMathJax{\newcommand{\bfn}{\abcbf n}}
\CustomizeMathJax{\newcommand{\bfo}{\abcbf o}}
\CustomizeMathJax{\newcommand{\bfp}{\abcbf p}}
\CustomizeMathJax{\newcommand{\bfq}{\abcbf q}}
\CustomizeMathJax{\newcommand{\bfr}{\abcbf r}}
\CustomizeMathJax{\newcommand{\bfs}{\abcbf s}}
\CustomizeMathJax{\newcommand{\bft}{\abcbf t}}
\CustomizeMathJax{\newcommand{\bfu}{\abcbf u}}
\CustomizeMathJax{\newcommand{\bfv}{\abcbf v}}
\CustomizeMathJax{\newcommand{\bfw}{\abcbf w}}
\CustomizeMathJax{\newcommand{\bfx}{\abcbf x}}
\CustomizeMathJax{\newcommand{\bfy}{\abcbf y}}
\CustomizeMathJax{\newcommand{\bfz}{\abcbf z}}

\LWR@mathjax@addgreek@l@bfit{bf}{}% Greek lowercase bold face italic
\LWR@mathjax@addgreek@u@bfup*{bf}{}% Greek uppercase bold face upright, cap macros.

\CustomizeMathJax{\newcommand{\bfzero}{\greekbf 0}}

\CustomizeMathJax{\DeclareMathOperator{\cov}{Cov}}
\CustomizeMathJax{\DeclareMathOperator{\E}{E}}
\CustomizeMathJax{\DeclareMathOperator{\V}{V}}
\CustomizeMathJax{\newcommand{\inas}{\overset{a.s.}{\to}}}
\CustomizeMathJax{\newcommand{\indist}{\overset{d}{\to}}}
\CustomizeMathJax{\newcommand{\inprob}{\overset{p}{\to}}}
\CustomizeMathJax{\DeclareMathOperator{\plim}{plim}}
\CustomizeMathJax{\DeclareMathOperator{\tr}{tr}}
\CustomizeMathJax{\DeclareMathOperator{\vc}{vec}}
\CustomizeMathJax{\DeclareMathOperator{\vcs}{vecs}}
\CustomizeMathJax{\DeclareMathOperator{\vch}{vech}}
\CustomizeMathJax{\DeclareMathOperator{\diag}{diag}}
\CustomizeMathJax{\DeclareMathOperator{\argmin}{arg\,min}}
\CustomizeMathJax{\DeclareMathOperator{\argmax}{arg\,max}}
\end{warpMathJax}
```

File 464 **lwarp-steinmetz.sty**

§ 572 Package

steinmetz

(*Emulates or patches code by* Enrico Gregorio.)

Pkg steinmetz steinmetz is patched for use by lwarp. Emulation is provided for MathJax

for HTML output:

```
\LWR@ProvidesPackagePass{steinmetz}[2009/06/14]

\renewcommand{\phase}[2][]{%
    \begin{lateximage}*[steinmetz\{\detokenize{#2}\}]
    \ensuremath{\underline{/#2}}
    \end{lateximage}
}

\begin{warpMathJax}
\CustomizeMathJax{\newcommand{\phase}[2][]{\underline{/#2}}}
\end{warpMathJax}
```

File 465 **lwarp-stfloats.sty**

§ 573 Package stfloats

Pkg stfloats stfloats is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{stfloats}[2017/03/27]
```

stfloats may have been preloaded by a ltj* class.

The following are provided in case they have not yet been defined:

```
\providecommand*{\fnbelowfloat}{}
\providecommand*{\fnunderfloat}{}
\providecommand*{\setbaselinefloat}{}
\providecommand*{\setbaselinefixed}{}
```

Nullified for HTML:

```
\renewcommand*{\fnbelowfloat}{}
\renewcommand*{\fnunderfloat}{}
\renewcommand*{\setbaselinefloat}{}
\renewcommand*{\setbaselinefixed}{}
```

File 466 **lwarp-struktex.sty**

§ 574 Package struktex

(*Emulates or patches code by* Jobst Hoffmann.)

Pkg struktex struktex is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{struktex}

\BeforeBeginEnvironment{struktogramm}{%
    \begin{lateximage}[-struktex-~\PackageDiagramAltText]%
```

```
}
\AfterEndEnvironment{struktogramm}{\end{lateximage}}

\newenvironment{LWR@HTML@centernss}{\begin{center}}{\end{center}}
\LWR@formattedenv{centernss}

\newcommand{\LWR@HTML@CenterNssFile}[1]{%
    \begin{center}
    \input{#1.nss}
    \end{center}
}
\LWR@formatted{CenterNssFile}

\newcommand{\LWR@HTML@centernssfile}{\LWR@HTML@CenterNssFile}
\LWR@formatted{centernssfile}
```

File 467 **lwarp-subcaption.sty**

§ 575 Package

subcaption

(*Emulates or patches code by* Axel Sommerfeldt.)

Pkg subcaption subcaption is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{subcaption}[2018/05/01]
```

Tells lwarp to ignore minipage widths inside a subfigure or subtable. In print mode the minipages are used to place the items next to each other. In HTML they are placed side-by-side automatically.

```
\xpretocmd{\subcaption@iiminipage}
    {\minipagefullwidth}
    {}
    {\LWR@patcherror{subcaption}{subcaption@iiminipage}}
```

Likewise for a \subcaptionbox:

```
\xpretocmd{\subcaptionbox}
    {\minipagefullwidth}
    {}
    {\LWR@patcherror{subcaption}{subcaptionbox}}
```

File 468 **lwarp-subfig.sty**

§ 576 Package

subfig

(*Emulates or patches code by* Steven Douglas Cochran.)

Pkg subfig subfig is supported and patched by lwarp.

⚠ table numbering To have correct sub table numbers:

```
\usepackage{caption}
\captionsetup[table]{position=top}
```

⚠ lof/lotdepth

At present, the package options for `lofdepth` and `lotdepth` are not working. These counters must be set separately after the package has been loaded.

⚠ horizontal spacing

In the document source, use `\hfill` and `\hspace*` between subfigures to spread them apart horizontally. The use of other forms of whitespace may cause paragraph tags to be generated, resulting in subfigures appearing on the following lines instead of all on a single line.

for HTML output:

Accept all options for lwarp-subfig:

```
\LWR@ProvidesPackagePass{subfig}[2005/06/28]
```

`\sf@@@subfloat` {⟨*1 type*⟩} [⟨*2 LOF entry*⟩] [⟨*3 caption*⟩] {⟨*4 contents*⟩}

The outer minipage allows side-by-side subfloats with `\hfill` between.

```
\long\def\sf@@@subfloat#1[#2][#3]#4{%
\begin{minipage}{\linewidth}% lwarp

\IfValueTF{#2}{%
    \LWR@setlatestname{#2}%
}{%
    \IfValueTF{#3}{%
        \LWR@setlatestname{#3}%
    }{}%
}%
\LWR@stoppars% lwarp
    \@ifundefined{FBsc@max}{}%
        {\FB@readaux{\let\FBsuboheight\relax}}%
    \@tempcnta=\@ne
    \if@minipage
      \@tempcnta=\z@
    \else\ifdim \lastskip=\z@ \else
      \@tempcnta=\tw@
    \fi\fi
    \ifmaincaptiontop
      \sf@top=\sf@nearskip
      \sf@bottom=\sf@farskip
    \else
      \sf@top=\sf@farskip
      \sf@bottom=\sf@nearskip
    \fi
    \leavevmode

%     \setbox\@tempboxa \hbox{#4}%
%     \@tempdima=\wd\@tempboxa
%     \@ifundefined{FBsc@max}{}%
%         {\global\advance\Xhsize-\wd\@tempboxa
%          \dimen@=\ht\@tempboxa
%          \advance\dimen@\dp\@tempboxa
%          \ifdim\dimen@>\FBso@max
%            \global\FBso@max\dimen@
%          \fi}%
```

Do not use boxes, which interfere with `lateximages`:

```
%     \vtop%
   \bgroup
%       \vbox%
      \bgroup
        \ifcase\@tempcnta
          \@minipagefalse
        \or
%           \vskip\sf@top
        \or
          \ifdim \lastskip=\z@ \else
%             \@tempskipb\sf@top\relax\@xaddvskip
          \fi
        \fi
        \sf@ifpositiontop{%
          \ifx \@empty#3\relax \else
            \sf@subcaption{#1}{#2}{#3}%
%             \vskip\sf@capskip
%             \vskip\sf@captopadj
          \fi\egroup
%           \hrule width0pt height0pt depth0pt
            \LWR@startpars% lwarp
%  \box\@tempboxa
            #4
            \LWR@stoppars% lwarp
        }{%
        \LWR@startpars% lwarp
        \@ifundefined{FBsc@max}%
            {
%  \box\@tempboxa
                #4
            }%
            {\ifx\FBsuboheight\relax
%                \box\@tempboxa
                #4
             \else
%                \vbox to \FBsuboheight{\FBafil\box\@tempboxa\FBbfil}%
                #4
             \fi}%
        \LWR@stoppars% lwarp
          \egroup
          \ifx \@empty#3\relax \else
%             \vskip\sf@capskip
%             \hrule width0pt height0pt depth0pt
            \sf@subcaption{#1}{#2}{#3}%
         \fi
        }%
%       \vskip\sf@bottom
    \egroup
    \@ifundefined{FBsc@max}{}%
        {\addtocounter{FRobj}{-1}%
         \ifnum\c@FRobj=0\else
           \subfloatrowsep
         \fi}%
    \ifmaincaptiontop\else
```

```
      \global\advance\@nameuse{c@\@captype}\m@ne
    \fi
\end{minipage}% lwarp
\LWR@startpars% lwarp
  \endgroup\ignorespaces%
}%
```

\sf@subcaption {⟨*1 type*⟩} {⟨*2 LOF entry*⟩} {⟨*3 caption*⟩}

```
\long\def\sf@subcaption#1#2#3{%
\LWR@stoppars% lwarp
  \ifx \relax#2\relax \else
    \bgroup
      \let\label=\@gobble
      \let\protect=\string
      \def\@subcaplabel{%
        \caption@lstfmt{\@nameuse{p@#1}}{\@nameuse{the#1}}}%
      \sf@updatecaptionlist{#1}{#2}{\the\value{\@captype}}{\the\value{#1}}%
    \egroup
  \fi
  \bgroup
    \ifx \relax#3\relax
      \let\captionlabelsep=\relax
    \fi
%     \setbox0\vbox{%
%        \hb@xt@\the\@tempdima{%
%
% %          \hss
% %         \parbox[t]{\the\@tempdima}{%
%           \caption@make
%               {\@nameuse{sub\@captype name}}%
%               {\@nameuse{thesub\@captype}}%
%               {#3}
% %  }%
% %             \hss
%   }
%  }%
    \@ifundefined{FBsc@max}%
%         {\box0}%
        {
%  \parbox[t]{\the\@tempdima}{%
\LWR@traceinfo{sfsubcap B1}%    lwarp
            \LWR@figcaption%    lwarp
            \caption@make
                {\@nameuse{sub\@captype name}}%
                {\@nameuse{thesub\@captype}}%
                {\LWR@isolate{#3}}%
            \endLWR@figcaption%     lwarp
\LWR@traceinfo{sfsubcap B2}%        lwarp
%  }%
        }%
        {\dimen@\ht0%
         \advance\dimen@\dp0%
         \ifdim\dimen@>\FBsc@max
           \global\FBsc@max\dimen@
```

```
        \fi
        \FB@readaux{\let\FBsubcheight\relax}%
        \ifx\FBsubcheight\relax
          \def\next{
%  \parbox[t]{\the\@tempdima}
           }%
        \else
          \def\next{
%  \parbox[t][\FBsubcheight][t]{\the\@tempdima}
           }%
        \fi
%         \vbox{%
%           \hb@xt@\the\@tempdima{%

%             \hss
%             \next{%
\LWR@traceinfo{sfsubcap C1}% lwarp
                \caption@make
                    {\@nameuse{sub\@captype name}}%
                    {\@nameuse{thesub\@captype}}%
                    {#3}
\LWR@traceinfo{sfsubcap C1}% lwarp
%  }%
%             \hss

%  }
%           }
       }%
  \egroup
\LWR@startpars% lwarp
}
```

\subfloat@label Patches for \sf@sub@label:

```
\xpretocmd{\subfloat@label}
    {\LWR@ensuredoingapar}
    {}
    {\LWR@patcherror{subfig}{subfloat@label}}
```

Patches for \subref.

\sf@subref {⟨*label*⟩}

The unstarred version uses a \ref link whose printed text comes from the sub@<label>:

```
\renewcommand{\sf@subref}[1]{%
    \LWR@subnewref{#1}{sub@#1}%
}
```

\sf@@subref {⟨*label*⟩}

The starred version uses the printed sub@<label> which is stored as if it were a page number:

```
\renewcommand{\sf@@subref}[1]{\LWR@orig@pageref{sub@#1}}
```

Defining new subfloats. The l@sub<type> for each is redefined.

\@newsubfloat [⟨*keys/values*⟩] {⟨*float name*⟩}

```
\LetLtxMacro\LWR@orig@newsubfloat\@newsubfloat

\def\@newsubfloat[#1]#2{%
\LWR@orig@newsubfloat[#1]{#2}%
\renewcommand{\l@sub#2}[2]{\hypertocfloat{2}{sub#2}{\ext@sub#2}{##1}{##2}}%
}
```

Pre-defined for figures and tables:

\l@subfigure {⟨*text*⟩} {⟨*pagenum*⟩}

```
\renewcommand{\l@subfigure}[2]{\hypertocfloat{2}{subfigure}{lof}{#1}{#2}}
```

\l@subtable {⟨*text*⟩} {⟨*pagenum*⟩}

```
\renewcommand{\l@subtable}[2]{\hypertocfloat{2}{subtable}{lot}{#1}{#2}}
```

File 469 **lwarp-subfigure.sty**

§ 577 Package

subfigure

Pkg subfigure

subfigure is emulated by subfig.

for HTML output:

```
\LWR@ProvidesPackageDrop{subfigure}[2002/03/15]
\RequirePackage{subfig}

\LetLtxMacro\subfigure\subfloat
\LetLtxMacro\subtable\subfloat
\LetLtxMacro\Subref\subref
\@ifundefined{figuretopcaptrue}{\newif\iffiguretopcap}{}
\newif\ifsubfiguretopcap
\newif\ifsubcaphang
\newif\ifsubcapcenter
\newif\ifsubcapcenterlast
\newif\ifsubcapnooneline
\newif\ifsubcapraggedright
\newskip\subfigtopskip
\newskip\subfigcapskip
\newdimen\subfigcaptopadj
\newskip\subfigbottomskip
\newdimen\subfigcapmargin
\newskip\subfiglabelskip
\newcommand*{\subcapsize}{}
\newcommand*{\subcaplabelfont}{}
\newcommand*{\subcapfont}{}
```

File 470 **lwarp-subsupscripts.sty**

§ 578 Package

subsupscripts

(*Emulates or patches code by* Riccardo Bresciani.)

Pkg subsupscripts

subsupscripts is used as-is for SVG math, and is emulated for MathJax.

for HTML output:

```
\LWR@ProvidesPackagePass{subsupscripts}[2009/10/27]
```

The larger skips are used here.

```
\begin{warpMathJax}
\CustomizeMathJax{%
    \newcommand{\fourscriptsC}[7]{%
        {}^{#2}_{#3}\hspace{#6}#1\hspace{#7}{}^{#4}_{#5}%
    }
}
\CustomizeMathJax{%
    \newcommand{\lrsubscriptsC}[5]{%
        \fourscriptsC{#1}{}{#2}{}{#3}{#4}{#5}%
    }
}
\CustomizeMathJax{%
    \newcommand{\lrsuperscriptsC}[5]{%
        \fourscriptsC{#1}{#2}{}{#3}{}{#4}{#5}%
    }
}
\CustomizeMathJax{%
    \newcommand{\fourscripts}[5]{%
        \fourscriptsC{#1}{#2}{#3}{#4}{#5}{0ex}{0ex}%
    }
}
\CustomizeMathJax{%
    \newcommand{\lrsubscripts}[3]{\fourscripts{#1}{}{#2}{}{#3}}
}
\CustomizeMathJax{%
    \newcommand{\lrsuperscripts}[3]{\fourscripts{#1}{#2}{}{#3}{}}
}
\CustomizeMathJax{%
    \newcommand{\twolscripts}[4][-.16ex]{{}^{#3}_{#4}\hspace{#1}#2}
}
\CustomizeMathJax{%
    \newcommand{\tworscripts}[4][-.07ex]{#2\hspace{#1}{}^{#3}_{#4}}
}
\CustomizeMathJax{%
    \newcommand{\lsubscript}[3][-.16ex]{\twolscripts[#1]{#2}{}{#3}}
}
\CustomizeMathJax{%
    \newcommand{\lsuperscript}[3][-.16ex]{\twolscripts[#1]{#2}{#3}{}}
}
\CustomizeMathJax{%
    \newcommand{\rsubscript}[3][-.07ex]{\tworscripts[#1]{#2}{}{#3}}
}
\CustomizeMathJax{%
    \newcommand{\rsuperscript}[3][-.07ex]{\tworscripts[#1]{#2}{#3}{}}
}
```

```
\end{warpMathJax}
```

File 471 **lwarp-supertabular.sty**

§ 579 Package

supertabular

(*Emulates or patches code by* Johannes Braams, Theo Jurriens.)

Pkg supertabular supertabular is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{supertabular}[2004/02/20]
```

⚠ Misplaced alignment tab character &

For `\tablefirsthead`, etc., enclose them as follows:

```
\StartDefiningTabulars
\tablefirsthead
. . .
\StopDefiningTabulars
```

See section 8.10.1.

⚠ lateximage supertabular and xtab are not supported inside a `lateximage`.

```
\newcommand{\LWRST@firsthead}{}

\newcommand{\tablefirsthead}[1]{%
    \long\gdef\LWRST@firsthead{#1}%
}

\newcommand{\tablehead}[1]{}
\newcommand{\tabletail}[1]{}

\newcommand{\LWRST@lasttail}{}

\newcommand{\tablelasttail}[1]{%
    \long\gdef\LWRST@lasttail{#1}%
}


\newcommand{\tablecaption}[2][]{%
    \long\gdef\LWRST@caption{%
        \ifblank{#1}%
            {\caption{#2}}%
            {\caption[#1]{#2}}%
    }%
}

\let\topcaption\tablecaption
\let\bottomcaption\tablecaption


\newcommand*{\LWRST@caption}{}

\newcommand*{\shrinkheight}[1]{}

```

```
\NewDocumentEnvironment{supertabular}{s o m}
{%
\LWR@traceinfo{supertabular}%
\begin{table}%
\LWRST@caption%
\begin{tabular}{#3}%
\TabularMacro\ifdefvoid{\LWRST@firsthead}%
{\LWR@getmynexttoken}%
{\expandafter\LWR@getmynexttoken\LWRST@firsthead}%
}%
{%
\ifdefvoid{\LWRST@lasttail}%
{}%
{%
\TabularMacro\ResumeTabular%
\LWRST@lasttail%
}%
\end{tabular}%
\end{table}%

\gdef\LWRST@caption{}%

\LWR@traceinfo{supertabular done}%
}

\NewDocumentEnvironment{mpsupertabular}{s o m}
{\minipage{\linewidth}\supertabular{#3}}
{\endsupertabular\endminipage}
```

File 472 **lwarp-svg.sty**

§ 580 Package

svg

(*Emulates or patches code by* Philip Ilten, Falk Hanisch.)

Pkg svg svg is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{svg}[2020/10/23]

\xpretocmd{\includesvg}%
    {\begin{lateximage}}%
    {}%
    {\LWR@patcherror{svg}{includesvg}}

\xapptocmd{\includesvg}%
    {\end{lateximage}}%
    {}%
    {\LWR@patcherror{svg}{includesvg}}

\xpretocmd{\includeinkscape}%
    {\begin{lateximage}}%
    {}%
```

```
    {\LWR@patcherror{svg}{includeinkscape}}

\xapptocmd{\includeinkscape}%
    {\end{lateximage}}%
    {}%
    {\LWR@patcherror{svg}{includeinkscape}}
```

File 473 **lwarp-swfigure.sty**

§ 581 Package swfigure

(*Emulates or patches code by* Claudio Beccari.)

Pkg swfigure swfigure is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{swfigure}[2020-11-10]

\NewDocumentEnvironment{DFimage}%
  {O{SW} m O{#4} m o D(){0.8} D<>{0} D||{0.25} D!!{}}%
{%
    \begin{figure}
    \centering
    \includegraphics{#2}
    \caption[#3]{#4}
    \IfValueT{#5}{\label{#5}}
    \end{figure}
}%
{}%
```

File 474 **lwarp-syntonly.sty**

§ 582 Package syntonly

(*Emulates or patches code by* Frank Mittelbach, Rainer Schöpf.)

Pkg syntonly syntonly is ignored.

for HTML output: Discard all options for lwarp-syntonly:

```
\LWR@ProvidesPackageDrop{syntonly}[2017/06/30]

\newif\ifsyntax@
\syntax@false

\newcommand*{\syntaxonly}{}

\@onlypreamble\syntaxonly

\def\nopages@{}
```

File 475 **lwarp-tabfigures.sty**

§ 583 Package

tabfigures

Pkg tabfigures tabfigures is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{tabfigures}[2012/01/24]
```

File 476 **lwarp-tablefootnote.sty**

§ 584 Package

tablefootnote

Pkg tablefootnote tablefootnote is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{tablefootnote}[2014/01/26]
```

This works because in HTML tables are no longer floats.

```
\LetLtxMacro\tablefootnote\footnote
```

File 477 **lwarp-tabls.sty**

§ 585 Package

tabls

(*Emulates or patches code by* Donald Arseneau.)

Pkg tabls tabls is emulated. `\LWR@hline` is used to handle the optional argument when tabls is loaded.

for HTML output:

```
\LWR@ProvidesPackageDrop{tabls}
```

```
\newdimen\tablinesep
\newdimen\arraylinesep
\newdimen\extrarulesep
```

File 478 **lwarp-tabularx.sty**

§ 586 Package

tabularx

(*Emulates or patches code by* David Carlisle.)

Pkg tabularx tabularx is emulated by lwarp.

for HTML output: Discard all options for lwarp-tabularx:

```
\LWR@ProvidesPackageDrop{tabularx}[2016/02/03]
\RequirePackage{array}

\DeclareDocumentEnvironment{tabularx}{m o m}
{\tabular{#3}}
{\endtabular}

\DeclareDocumentEnvironment{tabularx*}{m o m}
{\tabular{#3}}
{\endtabular}
```

File 479 **lwarp-tabulary.sty**

§ 587 Package tabulary

(*Emulates or patches code by* David Carlisle.)

Pkg tabulary tabulary is emulated by lwarp.

for HTML output: Discard all options for lwarp-tabulary.

Column types L, C, R, and J are emulated by lwarp core code.

```
\LWR@ProvidesPackageDrop{tabulary}[2014/06/11]
\RequirePackage{array}

\NewDocumentEnvironment{tabulary}{m o m}
{\tabular{#3}}
{\endtabular}

\NewDocumentEnvironment{tabulary*}{m o m}
{\tabular{#3}}
{\endtabular}

\newdimen\tymin
\newdimen\tymax
\def\tyformat{}
```

File 480 **lwarp-tagpdf.sty**

§ 588 Package tagpdf

Pkg tagpdf tagpdf is mostly ignored, but emulates alt text, for images only. (HTML only has alternate text for images.)

(If left enabled for HTML output, tagpdf errors when producing HTML, somehow due to the HTML page numbers.)

for HTML output:

```
\LWR@ProvidesPackageDrop{tagpdf}[2019/07/02]
```

```
\ExplSyntaxOn

\tl_new:N \l__uftag_mc_key_label_tl

\keys_define:nn { uftag / mc }
{
 tag .code:n = % the name (H,P,Span etc
  {},
 raw  .code:n =
  {}
   ,
 alttext .code:n      = % Alt property
  {
   \gdef\LWR@ThisAltText{\detokenize\expandafter{#1}}%
  },
  alttext-o .code:n      = % Alt property
  {
   \gdef\LWR@ThisAltText{\detokenize\expandafter{#1}}%
  },
  actualtext .code:n      = % ActualText property
  {},
  actualtext-o .code:n      = % ActualText property
  {},
 label .tl_set:N        = \l__uftag_mc_key_label_tl,
 artifact .code:n       = {},
 artifact .default:n    = {notype}
}

\keys_define:nn { uftag / struct }
{
 label .tl_set:N      = \l__uftag_struct_key_label_tl,
 stash .bool_set:N    = \l__uftag_struct_elem_stash_bool,
 tag   .code:n        = % S property
  {},
 title .code:n        = % T property
  {},
 title-o .code:n        = % T property
  {},
 alttext .code:n      = % Alt property
  {
   \gdef\LWR@ThisAltText{\detokenize\expandafter{#1}}%
  },
  alttext-o .code:n      = % Alt property
  {
   \gdef\LWR@ThisAltText{\detokenize\expandafter{#1}}%
  },
  actualtext .code:n  = % ActualText property
  {},
  actualtext-o .code:n  = % ActualText property
  {},
}

\NewDocumentCommand \tagpdfsetup { m }{}

\cs_set_eq:NN\tagpdfifluatexTF \sys_if_engine_luatex:TF
```

```
\cs_set_eq:NN\tagpdfifluatexT  \sys_if_engine_luatex:T
\cs_set_eq:NN\tagpdfifpdftexT  \sys_if_engine_pdftex:T
\cs_new:Npn \tagpdfget #1 {}
\cs_new:Npn \uftag_get:n #1 {}

\NewDocumentCommand \tagmcifinTF { m m }{}

\NewDocumentCommand \tagmcbegin { m }{\uftag_mc_begin:n {#1}\ignorespaces}
\cs_new_protected:Nn \uftag_mc_begin:n {
  \group_begin:
   \keys_set:nn { uftag / mc } {#1}
  \group_end:
}

\NewDocumentCommand \tagmcend {}{\ThisAltText{}}

\cs_new_protected:Nn \uftag_mc_end: {\ThisAltText{}}

\NewDocumentCommand \tagmcuse { m }{}

\cs_new_protected:Nn \uftag_mc_use:n {}

\NewDocumentCommand \tagstructbegin { m }{
  \uftag_struct_begin:n {#1}
}

\cs_new_protected:Nn \uftag_struct_begin:n
{
  \group_begin:
  \keys_set:nn {uftag / struct} { #1 }
  \group_end:
}

\NewDocumentCommand \tagstructend {  }{\ThisAltText{}}

\cs_new_protected:Nn \uftag_struct_end: {\ThisAltText{}}

\NewDocumentCommand \tagstructuse { m }{}

% \NewDocumentCommand\showtagpdfmcdata { O {\__uftag_get_mc_abs_cnt:} }{}
% What is the second argument?

\NewDocumentCommand\showtagpdfattributes { }{}

\sys_if_engine_luatex:T
{
  \NewDocumentCommand\pdffakespace { }
  {
   \__uftag_fakespace:
  }
}

\ExplSyntaxOff
```

File 481 **lwarp-tascmac.sty**

§ 589 Package

tascmac

Pkg tascmac tascmac is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{tascmac}[2018/03/09]

\newenvironment*{boxnote}
    {
        \BlockClass[
            padding: .5ex ;
            border: 1px solid black ;
            border-top: 1px dashed black ;
        ]{boxnote}
    }
    {\endBlockClass}

\newenvironment*{screen}[1][]
    {
        \BlockClass[
            padding: .5ex ;
            border: 1px solid gray ;
            border-radius: 8pt
        ]{boxnote}
    }
    {\endBlockClass}

\newenvironment*{itembox}[2][]
    {
        \BlockClass[
            padding: .5ex ;
            border: 1px solid gray ;
            border-radius: 8pt
        ]{boxnote}
        \InlineClass{itemboxtitle}{#2}\par
    }
    {\endBlockClass}

\newenvironment*{shadebox}
    {
        \BlockClass[
            padding: .5ex ;
            border: 1px solid black ;
            box-shadow: 3px 3px 3px \#808080 ;
        ]{boxnote}
    }
    {\endBlockClass}

\newcommand*{\mask}[2]{%
    \InlineClass[background: lightgray]{mask}{#1}%
```

```
}

\newcommand*{\maskbox}[5]{%
    \InlineClass[background: lightgray]{mask}{#5}%
}

\newcommand*{\Maskbox}[6]{%
    \InlineClass[
        background: lightgray ;
        border: #5 solid black
    ]{mask}{#6}%
}

\newcommand*{\keytop}[2][]{%
    \InlineClass[%
        padding: .2ex ;
        border: 1px solid black ;
        border-radius: .7ex ;
    ]{keytop}{#2}%
}

\def\yen{\HTMLunicode{00A5}}

\def\return{\HTMLunicode{23CE}}

\def\Return{\HTMLunicode{23CE}}

\def\ascii{ASCII Corporation}

\def\Ascii{ASCII Corporation}

\def\ASCII{ASCII Corporation}
```

File 482 **lwarp-tcolorbox.sty**

§ 590 Package

tcolorbox

(*Emulates or patches code by* Thomas F. Sturm.)

Pkg tcolorbox

tcolorbox is patched for use by lwarp.

See section 8.3.8 for limitations.

for HTML output:

```
\LWR@ProvidesPackagePass{tcolorbox}[2020/04/28]

\newbool{LWR@havetcblower}
\boolfalse{LWR@havetcblower}
```

Colors are supported via HTML styles:

```
\newcommand{\LWR@tcolorbox@findcolors}{%
    \convertcolorspec{named}{tcbcolback}{HTML}\LWR@tcbcolback
    \convertcolorspec{named}{tcbcolframe}{HTML}\LWR@tcbcolframe
```

```
    \iftcb@titlefilled%
        \convertcolorspec{named}{tcbcolbacktitle}{HTML}\LWR@tcbcolbacktitle
    \else
        \convertcolorspec{named}{tcbcolframe}{HTML}\LWR@tcbcolbacktitle
    \fi
    \convertcolorspec{named}{tcbcoltitle}{HTML}\LWR@tcbcoltitle
    \convertcolorspec{named}{tcbcolupper}{HTML}\LWR@tcbcolupper
    \convertcolorspec{named}{tcbcollower}{HTML}\LWR@tcbcollower
}

\newcommand*{\LWR@tcolorbox@titlecolorstyles}{%
    border-top: 1px solid \LWR@origpound\LWR@tcbcolframe ;
    border-bottom: 1px solid \LWR@origpound\LWR@tcbcolframe ;
    background: \LWR@origpound\LWR@tcbcolbacktitle ;
    color: \LWR@origpound\LWR@tcbcoltitle ;
}
```

The title is placed inside its own of class tcolorboxtitle.

```
\newcommand*{\LWR@showtitle@}[1]{%
    \begin{BlockClass}[
        \LWR@tcolorbox@titlecolorstyles
    ]{tcolorboxtitle}
%                     \cmdKV@LWRtcolorbox@title\par
    \kvtcb@before@title#1\kvtcb@after@title
    \end{BlockClass}
}
```

If no title, a non-breakable space is used to take some vertical space.

```
\newcommand*{\LWR@showtitle}[1]{%
    \iftcb@titlevisible
    \LWR@showtitle@{#1}
    \else
    \LWR@showtitle@{~}
    \fi
}

\newcommand*{\LWR@tcolorbox@dophantom}{%
%     \sbox\tcb@phantombox{\kvtcb@phantom}%
%     \iftcb@hasPhantom%
%         \box\tcb@phantombox%
%         \tcb@hasPhantomfalse%
%     \fi%
    \kvtcb@phantom
    \let\kvtcb@phantom\@empty%
}
```

The tcolorbox is placed inside an external of class #1, which is tcolorbox or tcolorbox inlineminipage. The upper and lower parts are placed into their own internal s of class tcolorboxupper and tcolorboxlower.

```
\newcommand*{\LWR@tcolorboxstart}[1]{
    \LWR@tcolorbox@findcolors
    \begin{BlockClass}[
```

```
        border: 1px solid \LWR@origpound\LWR@tcbcolframe ;
        background: \LWR@origpound\LWR@tcbcolback ;
    ]{#1}
    \LWR@tcolorbox@dophantom%
    \ifdefvoid{\kvtcb@title}
        {}
        {
            \LWR@showtitle{\kvtcb@title}
        }
    \begin{BlockClass}[
        color: \LWR@origpound\LWR@tcbcolupper ;
    ]{tcolorboxupper}
}
```

Floats enclose the tcolorbox.

```
\newcommand*{\LWR@tcolorbox@dostartfloat}{%
    \ifx\kvtcb@float\@empty%
%         \tcb@set@normal@unbroken@beforeafter%
    \else%
%         \edef\tcb@before@unbroken{%
%             \noexpand\tcb@float@env@begin{tcbfloat}[\kvtcb@float]%
%             \noexpand\kvtcb@everyfloat%
%         }%
%         \let\tcb@after@unbroken=\tcb@float@env@end%
        \tcb@float@env@begin{tcbfloat}[\kvtcb@float]
        \noexpand\kvtcb@everyfloat
    \fi%
}

\newcommand*{\LWR@tcolorbox@doendfloat}{%
    \ifx\kvtcb@float\@empty%
    \else%
        \tcb@float@env@end%
    \fi%
}
```

Footnotes are handled via the main footnote mechanism, and pending notes are printed before and after each tcolorbox. Footnote numbering will not match the print output.

```
\renewenvironment{tcolorbox}[1][]
    {
        \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
        {
            \PackageError{lwarp}
                {%
               Lwarp cannot process a tcolorbox inside a lateximage\MessageBreak
                    or SVG math.\MessageBreak
                    Enter 'H' for possible solutions%
                }
                {%
                    Use \protect\tcbox, \protect\tcboxmath, or
                    \protect\tcbhighmath\space instead.\MessageBreak%
                    (Inside math, you probably want to use these anyhow.)%
                }
```

```
        }{\relax}
        \LWR@printpendingfootnotes
        \tcb@layer@inc
        \tcb@apply@box@options{#1}
        \LWR@tcolorbox@dostartfloat%
%         \tcbset{title=,#1}
        \boolfalse{LWR@havetcblower}
        \LWR@tcolorboxstart{tcolorbox}
        \tcb@insert@before@upper%
    }
    {
        \ifbool{LWR@havetcblower}{%
            \tcb@insert@after@lower%
        }{%
            \tcb@insert@after@upper%
        }%
        \end{BlockClass}
        \LWR@printpendingfootnotes
        \tcb@layer@dec
        \end{BlockClass}
        \LWR@tcolorbox@doendfloat%
    }
```

For the lower part, the upper part is finished then the lower is started. `\tcblower` is only temporarily defined where appropriate, so the HTML version is defined globally via `\newcommand` instead of `\renewcommand`.

```
\newcommand{\tcblower}{
    \tcb@insert@after@upper%
    \end{BlockClass}
    \begin{BlockClass}[%
        border-top: 1px dashed \LWR@origpound\LWR@tcbcolframe ;
        color: \LWR@origpound\LWR@tcbcollower ;
    ]{tcolorboxlower}
    \tcb@insert@before@lower%
}
```

Starred and unstarred `\tcbline` are simple `\hrule`s.

```
\AtBeginDocument{
\ifdef{\tcbline}{
    \newcommand*{\LWR@sub@tcbline}{%
        \begin{BlockClass}{hrule}
        \end{BlockClass}
    }
    \newcommand{\LWR@HTML@tcbline}{\@ifstar\LWR@sub@tcbline\LWR@sub@tcbline}
    \LWR@formatted{tcbline}
}{}
}

\newcommand{\LWR@HTML@tcbox}[2][]{
    \LWR@printpendingfootnotes
    \LWR@tcolorbox@dostartfloat%
    \begingroup
    \tcb@layer@inc
```

```
    \tcb@apply@box@options{#1}
%     \tcbset{title=,#1}
    \boolfalse{LWR@havetcblower}
    \LWR@tcolorboxstart{tcolorbox inlineminipage}
    \tcb@insert@before@upper%
    #2
    \ifbool{LWR@havetcblower}{%
        \tcb@insert@after@lower%
    }{%
        \tcb@insert@after@upper%
    }%
    \end{BlockClass}
    \LWR@printpendingfootnotes
    \end{BlockClass}
    \tcb@layer@dec%
    \endgroup%
    \LWR@tcolorbox@dostartfloat%
    \global\booltrue{LWR@minipagethispar}%
}
\LWR@formatted{tcbox}

\appto\LWR@restoreMathJaxformatting{%
    \renewcommand{\tcbox}[2][]{#2}%
}
```

Patches for the subtitle, which is placed inside a of class tcolorboxsubtitle.

```
\xpatchcmd{\tcbsubtitle}
    {\begingroup}
    {\begingroup\let\kvtcb@title\relax\begin{BlockClass}{tcolorboxsubtitle}}
    {}
    {\LWR@patcherror{tcolorbox}{tcbsubtitle}}

\xpatchcmd{\tcbsubtitle}
    {\endgroup}
    {\end{BlockClass}\endgroup}
    {}
    {\LWR@patcherror{tcolorbox}{tcbsubtitleB}}
```

\tcboxfit is the same as \tcbox.

```
\AtBeginDocument{
    \ifdef{\tcboxfit}{%
        \let\LWR@HTML@tcboxfit\tcbox%
        \LWR@formatted{tcboxfit}
    }{}
}
```

\tcbtitle is patched to support the text font.

```
\LetLtxMacro\LWR@HTML@tcbtitle\tcbtitle
\xpatchcmd{\LWR@HTML@tcbtitle}
    {\kvtcb@before@title\tcbtitletext}
   {\kvtcb@before@title\LWR@textcurrentfont{\LWR@textcurrentcolor{\tcbtitletext}}}
    {}
```

```
    {\LWR@patcherror{tcolorbox}{LWR@HTML@tcbtitle}}
\LWR@formatted{tcbtitle}
```

List-of:

```
\renewcommand*\l@tcolorbox[2]{\hypertocfloat{1}{tcolorbox}{lof}{#1}{#2}}
```

Theorem limitations. An error is printed if the document uses `math`, `ams equation`, etc. `\tcboxmath` and `\tcbhighmath` are ignored for HTML.

```
\AtBeginDocument{
\pgfkeysifdefined{/tcb/libload/theorems}{

    \def\LWR@HTML@tcb@hack@amsmath{%
        \PackageError{lwarp}
            {%
                tcolorbox ``math'', ``ams equation'', and related\MessageBreak
                are not supported.\MessageBreak
                \protect\tcboxmath\space and
                \protect\tcbhighmath\space are emulated.\MessageBreak
                Enter 'H' for possible solutions%
            }
            {%
               Remove tcolorbox math-related options, and instead\MessageBreak
                use the usual math environments inside each tcolorbox.%
            }
    }
    \LWR@formatted{tcb@hack@amsmath}

    % Cause an error if using math:
    \tcbset{%
        math upper/.style={before upper*=\tcb@hack@amsmath,after upper*=$},%
        math lower/.style={before lower*=\tcb@hack@amsmath,after lower*=$},%
    }

    \appto\LWR@restoreorigformatting{%
    \tcbset{%
        math upper/.style={before upper*=$\displaystyle,after upper*=$},%
        math lower/.style={before lower*=$\displaystyle,after lower*=$},%
    }%
    }

    \newcommand{\LWR@HTML@tcboxmath}[2][]{#2}
    \LWR@formatted{tcboxmath}
    \newcommand{\LWR@HTML@tcbhighmath}[2][]{#2}
    \LWR@formatted{tcbhighmath}
    \appto\LWR@restoreMathJaxformatting{%
        \renewcommand{\tcboxmath}[2][]{#2}%
        \renewcommand{\tcbhighmath}[2][]{#2}%
    }
}{}% theorems loaded
}% AtBeginDocument
```

For MathJax:

```
\CustomizeMathJax{\newcommand{\tcbset}[1]{}}
\CustomizeMathJax{\newcommand{\tcbsetforeverylayer}[1]{}}
\CustomizeMathJax{\newcommand{\tcbox}[2][]{\boxed{\text{#2}}}}
\CustomizeMathJax{\newcommand{\tcboxfit}[2][]{\boxed{#2}}}
\CustomizeMathJax{\newcommand{\tcblower}{}}
\CustomizeMathJax{\newcommand{\tcbline}{}}
\CustomizeMathJax{\newcommand{\tcbtitle}{}}
\CustomizeMathJax{\newcommand{\tcbsubtitle[2][]{\mathrm{#2}}}}
\CustomizeMathJax{\newcommand{\tcboxmath}[2][]{\boxed{#2}}}
\CustomizeMathJax{\newcommand{\tcbhighmath}[2][]{\boxed{#2}}}
```

File 483 **lwarp-tensor.sty**

§ 591 Package

tensor

(*Emulates or patches code by* Philip G. Ratcliffe.)

Pkg tensor tensor is used as-is for SVG math, and is emulated for MathJax.

⚠ spacing Compressed spacing and left justification are not possible with MathJax.

for HTML output:

```
\LWR@ProvidesPackagePass{tensor}[2004/12/20]
```

For MathJax. Special handling is required to parse the superscript and subscript arguments.

When a superscript or subscript is seen, it is processed and then the remainder is processesed recursively.

```
\begin{warpMathJax}
\CustomizeMathJax{\def\LWRtensorindicesthreesub#1#2{{_{#2}}\LWRtensorindicesthree}}
\CustomizeMathJax{\def\LWRtensorindicesthreesup#1#2{{^{#2}}\LWRtensorindicesthree}}
```

If not a superscript nor a subscript, processing stops.

```
\CustomizeMathJax{\newcommand{\LWRtensorindicesthreenotsup}{}}
```

Check ahead for a superscript or a subscript.

```
\CustomizeMathJax{\newcommand{\LWRtensorindicesthreenotsub}{
    \ifnextchar ^ \LWRtensorindicesthreesup \LWRtensorindicesthreenotsup
}}

\CustomizeMathJax{\newcommand{\LWRtensorindicesthree}{
    \ifnextchar _ \LWRtensorindicesthreesub \LWRtensorindicesthreenotsub
}}
```

Ignore star.

```
\CustomizeMathJax{\newcommand{\LWRtensorindicestwo}{
    \ifstar\LWRtensorindicesthree\LWRtensorindicesthree
}}
```

Remove the outer brace of the argument.

```
\CustomizeMathJax{\newcommand{\indices}[1]{\LWRtensorindicestwo#1}}
```

Attempting to use \vphantom here does not work:

```
\CustomizeMathJax{\newcommand{\LWRtensortwo}[3][]{{}\indices{#1}{#2}\indices{#3}}}
```

Ignore star.

```
\CustomizeMathJax{\newcommand{\tensor}{\ifstar\LWRtensortwo\LWRtensortwo}}
```

In text mode, \nuclide is converted to an SVG image.

```
\CustomizeMathJax{%
    \newcommand{\LWRnuclidetwo}[2][]{%
        {%
            \vphantom{\mathrm{#2}}%
            {}^{\LWRtensornucleonnumber}_{#1}%
            \mathrm{#2}%
        }%
    }%
}

\CustomizeMathJax{%
    \newcommand{\nuclide}[1][]{%
        \def\LWRtensornucleonnumber{#1}%
        \LWRnuclidetwo%
    }%
}
\end{warpMathJax}
```

File 484 **lwarp-termcal.sty**

§ 592 Package

termcal

(*Emulates or patches code by* Bill Mitchell.)

Pkg termcal termcal is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{termcal}% questionable date in the .sty file
```

Nullify the @ because everything is being done in a token list.

```
\xpatchcmd{\endcalendar}
    {@{}}
    {}
    {}
    {\LWR@patcherror{termcal}{endcalendar}}
```

Remove the hbox:

```
\xpatchcmd{\ca@doaday}
    {\hbox to \hsize{\calprintdate\hfill\ifclassday\calprintclass\fi}}
    {%
        \calprintdate\hfill\ifclassday\calprintclass\fi%
    }
    {}
    {\LWR@patcherror{termcal}{ca@doaday}}
```

Change each of two ampersands to call the lwarp tabular version:

```
\xpatchcmd{\calday}
    {&}
    {\LWR@tabularampersand}
    {}
    {\LWR@patcherror{termcal}{calday}}

\xpatchcmd{\calday}
    {&}
    {\LWR@tabularampersand}
    {}
    {\LWR@patcherror{termcal}{calday B}}
```

File 485 **lwarp-textarea.sty**

§ 593 Package textarea

(*Emulates or patches code by* Alexander I. Rozhenko.)

Pkg textarea textarea is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{textarea}[2005/12/26]

\newcommand\StartFromTextArea{}
\newcommand\StartFromHeaderArea{}
\newcommand*\RestoreTextArea{}
\newcommand*\ExpandTextArea[1][*]{}
\let\NCC@restoretextarea\@empty
```

File 486 **lwarp-textcomp.sty**

§ 594 Package textcomp

(*Emulates or patches code by* Frank Mittelbach, Robin Fairbairns, Werner Lemberg.)

Pkg textcomp textcomp is patched for use by lwarp.

§ 594.1 Limitations

Some textcomp symbols do not have Unicode equivalents, and thus are not supported.

⚠ missing symbols Many textcomp symbols are not supported by many system/browser fonts. In the CSS try referencing fonts which are more complete, but expect to see gaps in coverage.

§ 594.2 Package loading

for HTML output:

```
\LWR@ProvidesPackagePass{textcomp}[2017/04/05]
```

§ 594.3 HTML symbols

For HTML, use HTML entities or direct Unicode, depending on the engine.

`\AtBeginDocument` improves support for LuaLaTeX and XeLaTeX.

§ 594.3.1 pdfLaTeX symbols

```
\AtBeginDocument{
\ifPDFTeX% pdflatex or dvi latex
\newcommand*{\LWR@HTML@textdegree}{\HTMLentity{deg}}
\newcommand*{\LWR@HTML@textcelsius}{\HTMLunicode{2103}}
\newcommand*{\LWR@HTML@textohm}{\HTMLunicode{2126}}
\newcommand*{\LWR@HTML@textmu}{\HTMLunicode{00B5}}
\newcommand*{\LWR@HTML@textlquill}{\HTMLunicode{2045}}
\newcommand*{\LWR@HTML@textrquill}{\HTMLunicode{2046}}
\newcommand*{\LWR@HTML@textcircledP}{\HTMLunicode{2117}}
\newcommand*{\LWR@HTML@texttwelveudash}{\HTMLunicode{2014}}% emdash
\newcommand*{\LWR@HTML@textthreequartersemdash}{\HTMLunicode{2014}}% emdash
\newcommand*{\LWR@HTML@textmho}{\HTMLunicode{2127}}
\newcommand*{\LWR@HTML@textnaira}{\HTMLunicode{20A6}}
\newcommand*{\LWR@HTML@textpeso}{\HTMLunicode{20B1}}
\newcommand*{\LWR@HTML@textrecipe}{\HTMLunicode{211E}}
\newcommand*{\LWR@HTML@textinterrobang}{\HTMLunicode{203D}}
\newcommand*{\LWR@HTML@textinterrobangdown}{\HTMLunicode{2E18}}
\newcommand*{\LWR@HTML@textperthousand}{\HTMLunicode{2030}}
\newcommand*{\LWR@HTML@textpertenthousand}{\HTMLunicode{2031}}
\newcommand*{\LWR@HTML@textbaht}{\HTMLunicode{0E3F}}
\newcommand*{\LWR@HTML@textdiscount}{\%}
\newcommand*{\LWR@HTML@textservicemark}{\HTMLunicode{2120}}
\else
```

§ 594.3.2 XeLaTeX and LuaLaTeX symbols

NOTE: Some of the following do not print well in the listing. Consult the .dtx or .sty file for the actual characters.

```
\newcommand*{\LWR@HTML@textdegree}{°}
\newcommand*{\LWR@HTML@textcelsius}{℃}
\newcommand*{\LWR@HTML@textohm}{Ω}
\newcommand*{\LWR@HTML@textmu}{µ}
\newcommand*{\LWR@HTML@textlquill}{⁅}
```

```
\newcommand*{\LWR@HTML@textrquill}{⁆}
\newcommand*{\LWR@HTML@textcircledP}{Ⓟ}
\newcommand*{\LWR@HTML@texttwelveudash}{–}% emdash
\newcommand*{\LWR@HTML@textthreequartersemdash}{–}% emdash
\newcommand*{\LWR@HTML@textmho}{℧}
\newcommand*{\LWR@HTML@textnaira}{₦}
\newcommand*{\LWR@HTML@textpeso}{₱}
\newcommand*{\LWR@HTML@textrecipe}{℞}
\newcommand*{\LWR@HTML@textinterrobang}{‽}
\newcommand*{\LWR@HTML@textinterrobangdown}{⸘}
\newcommand*{\LWR@HTML@textperthousand}{‰}
\newcommand*{\LWR@HTML@textpertenthousand}{‱}
\newcommand*{\LWR@HTML@textbaht}{฿}
\newcommand*{\LWR@HTML@textdiscount}{\%}
\newcommand*{\LWR@HTML@textservicemark}{℠}
\fi

\LWR@formatted{textdegree}
\LWR@formatted{textcelsius}
\LWR@formatted{textohm}
\LWR@formatted{textmu}
\LWR@formatted{textlquill}
\LWR@formatted{textrquill}
\LWR@formatted{textcircledP}
\LWR@formatted{texttwelveudash}
\LWR@formatted{textthreequartersemdash}
\LWR@formatted{textmho}
\LWR@formatted{textnaira}
\LWR@formatted{textpeso}
\LWR@formatted{textrecipe}
\LWR@formatted{textinterrobang}
\LWR@formatted{textinterrobangdown}
\LWR@formatted{textperthousand}
\LWR@formatted{textpertenthousand}
\LWR@formatted{textbaht}
\LWR@formatted{textdiscount}
\LWR@formatted{textservicemark}
```

§ 594.4 HTML diacritics

For HTML, Unicode diacritical marks are used:

```
\newcommand*{\LWR@HTML@capitalcedilla}[1]{#1\HTMLunicode{0327}}
\newcommand*{\LWR@HTML@capitalogonek}[1]{#1\HTMLunicode{0328}}
\newcommand*{\LWR@HTML@capitalgrave}[1]{#1\HTMLunicode{0300}}
\newcommand*{\LWR@HTML@capitalacute}[1]{#1\HTMLunicode{0301}}
\newcommand*{\LWR@HTML@capitalcircumflex}[1]{#1\HTMLunicode{0302}}
\newcommand*{\LWR@HTML@capitaltilde}[1]{#1\HTMLunicode{0303}}
\newcommand*{\LWR@HTML@capitaldieresis}[1]{#1\HTMLunicode{0308}}
\newcommand*{\LWR@HTML@capitalhungarumlaut}[1]{#1\HTMLunicode{30B}}
\newcommand*{\LWR@HTML@capitalring}[1]{#1\HTMLunicode{30A}}
\newcommand*{\LWR@HTML@capitalcaron}[1]{#1\HTMLunicode{30C}}
\newcommand*{\LWR@HTML@capitalbreve}[1]{#1\HTMLunicode{306}}
\newcommand*{\LWR@HTML@capitalmacron}[1]{#1\HTMLunicode{304}}
\newcommand*{\LWR@HTML@capitaldotaccent}[1]{#1\HTMLunicode{307}}
```

\textcircled becomes a span with a rounded border. \providecommand is used to avoid conflict with xunicode.

```
\providecommand*{\LWR@HTML@textcircled}[1]{%
    \InlineClass[border: 1px solid \LWR@currenttextcolor]{textcircled}{#1}%
}

\LWR@formatted{capitalcedilla}
\LWR@formatted{capitalogonek}
\LWR@formatted{capitalgrave}
\LWR@formatted{capitalacute}
\LWR@formatted{capitalcircumflex}
\LWR@formatted{capitaltilde}
\LWR@formatted{capitaldieresis}
\LWR@formatted{capitalhungarumlaut}
\LWR@formatted{capitalring}
\LWR@formatted{capitalcaron}
\LWR@formatted{capitalbreve}
\LWR@formatted{capitalmacron}
\LWR@formatted{capitaldotaccent}

\LWR@formatted{textcircled}
```

Nullify textcomp macros when generating filenames:

```
\FilenameNullify{%
    \renewcommand*{\textdegree}{}%
    \renewcommand*{\textcelsius}{}%
    \renewcommand*{\textohm}{}%
    \renewcommand*{\textmu}{}%
    \renewcommand*{\textlquill}{}%
    \renewcommand*{\textrquill}{}%
    \renewcommand*{\textcircledP}{}%
    \renewcommand*{\texttwelveudash}{}%
    \renewcommand*{\textthreequartersemdash}{}%
    \renewcommand*{\textmho}{}%
    \renewcommand*{\textnaira}{}%
    \renewcommand*{\textpeso}{}%
    \renewcommand*{\textrecipe}{}%
    \renewcommand*{\textinterrobang}{}%
    \renewcommand*{\textinterrobangdown}{}%
    \renewcommand*{\textperthousand}{}%
    \renewcommand*{\textpertenthousand}{}%
    \renewcommand*{\textbaht}{}%
    \renewcommand*{\textdiscount}{}%
    \renewcommand*{\textservicemark}{}%
    \renewcommand*{\textcircled}[1]{#1}%
    \renewcommand*{\capitalcedilla}[1]{#1}%
    \renewcommand*{\capitalogonek}[1]{#1}%
    \renewcommand*{\capitalgrave}[1]{#1}%
    \renewcommand*{\capitalacute}[1]{#1}%
    \renewcommand*{\capitalcircumflex}[1]{#1}%
    \renewcommand*{\capitaltilde}[1]{#1}%
    \renewcommand*{\capitaldieresis}[1]{#1}%
    \renewcommand*{\capitalhungarumlaut}[1]{#1}%
```

```
    \renewcommand*{\capitalring}[1]{#1}%
    \renewcommand*{\capitalcaron}[1]{#1}%
    \renewcommand*{\capitalbreve}[1]{#1}%
    \renewcommand*{\capitalmacron}[1]{#1}%
    \renewcommand*{\capitaldotaccent}[1]{#1}%
}% FilenameNullify

}% AtBeginDocument
```

File 487 **lwarp-textfit.sty**

§ 595 Package

textfit

Pkg textfit textfit is emulated.

Text is placed into a of class `textfit`. Sizes are approximated, and also limited by browser min/max font-size settings.

for HTML output:

```
\LWR@ProvidesPackageDrop{textfit}[1994/04/15]

\newsavebox{\LWR@textfitbox}

\newcommand*{\LWR@textfitscale}[2]{%
\setlength{\LWR@templengthone}{#1}%
\setlength{\LWR@templengthone}{%
    1em*\ratio{\LWR@templengthone}{\LWR@templengthtwo}%
}%
\InlineClass[font-size:\LWR@printlength{\LWR@templengthone}]{textfit}{#2}%
}

\newcommand*{\scaletowidth}[2]{%
\sbox{\LWR@textfitbox}{#2}%
\settowidth{\LWR@templengthtwo}{\usebox{\LWR@textfitbox}}%
\LWR@textfitscale{#1}{#2}%
}

\newcommand*{\scaletoheight}[2]{%
\sbox{\LWR@textfitbox}{#2}%
\settoheight{\LWR@templengthtwo}{\usebox{\LWR@textfitbox}}%
\LWR@textfitscale{#1}{#2}%
}
```

File 488 **lwarp-textpos.sty**

§ 596 Package

textpos

(*Emulates or patches code by* Norman Gray.)

Pkg textpos textpos is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{textpos}[2020/09/26]
```

```
\NewDocumentEnvironment{textblock}{m o r()}{}{}
\NewDocumentEnvironment{textblock*}{m o r()}{}{}
\newcommand*{\TPGrid}[3][]{}
\def\TPShowGrid{\@ifstar{\@TPShowGrid}{\@TPShowGrid}}
\def\@TPShowGrid#1#2{}
\NewDocumentCommand{\TPMargin}{s o}{}
\newcommand*{\textblockcolour}[1]{}
\newcommand*{\textblockrulecolour}[1]{}
\newcommand*{\textblockcolor}[1]{}
\newcommand*{\textblockrulecolor}[1]{}
\newcommand*{\tekstblokkulur}[1]{}
\newcommand*{\tekstblokrulekulur}[1]{}
\newlength{\TPHorizModule}
\newlength{\TPVertModule}
\newlength{\TPboxrulesize}
\newcommand{\textblocklabel}[1]{}
\newcommand*{\showtextsize}{}
\newcommand{\textblockorigin}[2]{}
\newcommand*{\TPoptions}[1]{}
\newcommand*{\TPReferencePosition}[1]{}
```

File 489 **lwarp-theorem.sty**

§ 597 Package theorem

(*Emulates or patches code by* Frank Mittelbach.)

Pkg theorem theorem is patched for use by lwarp.

Table 20: Theorem package — css styling of theorems and proofs

Theorem: of class theorembody<theoremstyle>

Theorem Header: of class theoremheader

where <theoremstyle> is plain, break, etc.

for HTML output:

```
\LWR@ProvidesPackagePass{theorem}[2014/10/28]
```

§ 597.1 Remembering the theorem style

Storage for the style being used for new theorems:

```
\newcommand{\LWR@newtheoremstyle}{plain}
```

Patched to remember the style being used for new theorems:

```
\gdef\theoremstyle#1{%
   \@ifundefined{th@#1}{\@warning
          {Unknown theoremstyle `#1'. Using `plain'}%
          \theorem@style{plain}%
```

```
           \renewcommand{\LWR@newtheoremstyle}{plain}% lwarp
          }%
      {%
          \theorem@style{#1}%
          \renewcommand{\LWR@newtheoremstyle}{#1}% lwarp
      }%
      \begingroup
        \csname th@\the\theorem@style \endcsname
      \endgroup}
```

Patched to remember the style for this theorem type, and set it later when the environment is started.

```
\gdef\@xnthm#1#2[#3]{%
   \expandafter\@ifdefinable\csname #1\endcsname
   {%
    \csedef{LWR@thmstyle#1}{\LWR@newtheoremstyle}% lwarp
    \@definecounter{#1}\@newctr{#1}[#3]%
    \expandafter\xdef\csname the#1\endcsname
      {\expandafter \noexpand \csname the#3\endcsname
       \@thmcountersep \@thmcounter{#1}}%
    \def\@tempa{\global\@namedef{#1}}%
    \expandafter \@tempa \expandafter{%
      \csname th@\the \theorem@style
            \expandafter \endcsname \the \theorem@bodyfont
     \@thm{#1}{#2}}%
    \global \expandafter \let \csname end#1\endcsname \@endtheorem
   \AtBeginEnvironment{#1}{\edef\LWR@thisthmstyle{\@nameuse{LWR@thmstyle#1}}}% lwarp
   }}

\gdef\@ynthm#1#2{%
    \expandafter\@ifdefinable\csname #1\endcsname
   {
    \csedef{LWR@thmstyle#1}{\LWR@newtheoremstyle}% lwarp
    \@definecounter{#1}%
    \expandafter\xdef\csname the#1\endcsname{\@thmcounter{#1}}%
    \def\@tempa{\global\@namedef{#1}}\expandafter \@tempa
     \expandafter{\csname th@\the \theorem@style \expandafter
     \endcsname \the\theorem@bodyfont \@thm{#1}{#2}}%
    \global \expandafter \let \csname end#1\endcsname \@endtheorem
   \AtBeginEnvironment{#1}{\edef\LWR@thisthmstyle{\@nameuse{LWR@thmstyle#1}}}% lwarp
   }}

\gdef\@othm#1[#2]#3{%
  \expandafter\ifx\csname c@#2\endcsname\relax
   \@nocounterr{#2}%
  \else
   \expandafter\@ifdefinable\csname #1\endcsname
   {
    \csedef{LWR@thmstyle#1}{\LWR@newtheoremstyle}% lwarp
    \expandafter \xdef \csname the#1\endcsname
     {\expandafter \noexpand \csname the#2\endcsname}%
    \def\@tempa{\global\@namedef{#1}}\expandafter \@tempa
     \expandafter{\csname th@\the \theorem@style \expandafter
     \endcsname \the\theorem@bodyfont \@thm{#2}{#3}}%
```

```
    \global \expandafter \let \csname end#1\endcsname \@endtheorem
   \AtBeginEnvironment{#1}{\edef\LWR@thisthmstyle{\@nameuse{LWR@thmstyle#1}}}% lwarp
    }%
  \fi}
```

§ 597.2 css patches

The following are patched for css.

These were in individual files `thp.sty` for plain, `thmb.sty` for margin break, etc. They are gathered together here.

Each theorem is encased in a `BlockClass` environment of class `theorembody<style>`.

Each header is encased in an `\InlineClass` of class `theoremheader`.

```
\gdef\th@plain{%
  \def\@begintheorem##1##2{%
        \item[
            \InlineClass{theoremheader}{##1\ ##2}
        ]
    }%
\def\@opargbegintheorem##1##2##3{%
   \item[
        \InlineClass{theoremheader}{##1\ ##2\ (##3)}
    ]
    }
}

\gdef\th@break{%
  \def\@begintheorem##1##2{%
    \item[
        \InlineClass{theoremheader}{##1\ ##2}\newline%
    ]
    }%
\def\@opargbegintheorem##1##2##3{%
  \item[
        \InlineClass{theoremheader}{##1\ ##2\ (##3)}\newline
    ]
    }
}

\gdef\th@marginbreak{%
  \def\@begintheorem##1##2{
    \item[
        \InlineClass{theoremheader}{##2 \qquad ##1}\newline
    ]
    }%
\def\@opargbegintheorem##1##2##3{%
    \item[
        \InlineClass{theoremheader}{##2 \qquad ##1\ %
        (##3)}\newline
    ]
    }
}

```

```
\gdef\th@changebreak{%
  \def\@begintheorem##1##2{
    \item[
        \InlineClass{theoremheader}{##2\ ##1}\newline
    ]
    }%
\def\@opargbegintheorem##1##2##3{%
    \item[
        \InlineClass{theoremheader}{ ##2\ ##1\ %
        (##3)}\newline
    ]
    }
}

\gdef\th@change{%
  \def\@begintheorem##1##2{
    \item[
        \InlineClass{theoremheader}{##2\ ##1}
    ]
    }%
\def\@opargbegintheorem##1##2##3{%
    \item[
        \InlineClass{theoremheader}{##2\ ##1\ (##3)}
    ]
    }
}

\gdef\th@margin{%
  \def\@begintheorem##1##2{
    \item[
        \InlineClass{theoremheader}{##2 \qquad ##1}
    ]
    }%
\def\@opargbegintheorem##1##2##3{%
    \item[
            \InlineClass{theoremheader}{##2 \qquad ##1\ (##3)}
    ]
    }
}
```

Patched for css:

```
\gdef\@thm#1#2{\refstepcounter{#1}%
\LWR@forcenewpage% lwarp

    \LWR@printpendingfootnotes%                   lwarp

    \BlockClass{theorembody\LWR@thisthmstyle}% lwarp
   \trivlist
   \@topsep \theorempreskipamount               % used by first \item
   \@topsepadd \theorempostskipamount           % used by \@endparenv
   \@ifnextchar [%
   {\@ythm{#1}{#2}}%
   {\@begintheorem{#2}{\csname the#1\endcsname}\ignorespaces}}

```

```
\gdef\@endtheorem{%
\endtrivlist

    \LWR@printpendingfootnotes%                    lwarp

\endBlockClass
}
```

File 490 **lwarp-thinsp.sty**

§ 598 Package

thinsp

Pkg thinsp thinsp is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{thinsp}[2016/10/02]

\AtBeginDocument{
\let\thinthinspace\relax% defined by some packages
\newcommand*{\thinthinspace}{\thinspace}
}

\newcommand*{\stretchthinspace}{\thinspace}
\newcommand*{\stretchthinthinspace}{\thinthinspace}
\newcommand*{\stretchnegthinspace}{\negthinspace}
```

File 491 **lwarp-thm-listof.sty**

§ 599 Package

thm-listof

(*Emulates or patches code by* Ulrich M. Schwarz, Yukai Chou.)

Pkg thm-listof thm-listof is part of thmtools, and is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{thm-listof}[2019/12/22]
```

For font control, see the generated HTML and use CSS per amsthm or ntheorem.

Other thm-* package may be loaded by thm-listof.

```
\@ifpackagelater{thm-listof}{2020/08/01}{% v0.72
  \def\thmtlo@newentry{%
    \csdef{l@\thmt@envname}##1##2{\hypertocfloat{1}{figure}{lof}{##1}{##2}}%
  }
}{% earlier than v0.72
    \xpatchcmd{\listoftheorems}
        {%
            \@xa\protected@edef\csname l@\thmt@envname\endcsname{%
                \@nx\@dottedtocline{1}{1.5em}{\@nx\thmt@listnumwidth}%
            }%
```

```
        }
        {%
        \csdef{l@\thmt@envname}##1##2{\hypertocfloat{1}{figure}{lof}{##1}{##2}}%
        }
        {}
        {\LWR@patcherror{thm-listof}{listoftheorems}}

    \xpatchcmd{\thmt@mklistcmd}
        {%
            \@xa\protected@edef\csname l@\thmt@envname\endcsname{%
                \@nx\@dottedtocline{1}{1.5em}{\@nx\thmt@listnumwidth}%
            }%
        }
        {%
        \csdef{l@\thmt@envname}##1##2{\hypertocfloat{1}{figure}{lof}{##1}{##2}}%
        }
        {}
        {\LWR@patcherror{thm-listof}{thmt@mklistcmd}}
}
```

File 492 **lwarp-thm-restate.sty**

§ 600 Package thm-restate

(*Emulates or patches code by* Ulrich M. Schwarz.)

Pkg thm-restate thm-restate is part of thmtools, and is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{thm-restate}[2020/08/01]

\xpatchcmd{\thmt@restatable}
    {\@ifstar}
    {\edef\LWR@thisthmstyle{#2}\@ifstar}
    {}
    {\LWR@patcherror{thm-restate}{thmt@restatable}}
```

File 493 **lwarp-thmbox.sty**

§ 601 Package thmbox

(*Emulates or patches code by* Emmanuel Beffara.)

Pkg thmbox thmbox is emulated for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{thmbox}[2005/04/24]

\renewenvironment{thmbox}[2][]%
    {%
        \begin{BlockClass}{thmbox}
        \begin{BlockClass}{thmboxtitle}
```

```
        #2
        \end{BlockClass}
    }
    {\end{BlockClass}}

\renewenvironment{proof}[1][]
    {%
        \begin{BlockClass}{thmboxproof}%
        \InlineClass{thmboxproofname}{\proofname\ #1\unskip\,:}
    }
    {%
        \qquad\HTMLunicode{220E}% end of proof symbol
        \end{BlockClass}
    }

\renewenvironment{example}[1][\examplename]%
    {%
        \begin{BlockClass}{thmboxexample}%
        \InlineClass{thmboxexamplename}{#1\,:}
    }
    {\end{BlockClass}}

\renewenvironment{leftbar}[1][]%
    {\begin{BlockClass}{thmboxleftbar}}
    {\end{BlockClass}}
```

File 494 **lwarp-thmtools.sty**

§ 602 Package

thmtools

(*Emulates or patches code by* Ulrich M. Schwarz.)

Pkg thmtools thmtools is patched for use by lwarp.

Also see thm-listof and thm-restate.

for HTML output:

```
\LWR@ProvidesPackagePass{thmtools}[2020/08/01]
```

The following patches either thm-amsthm or thm-ntheorem.

```
\def\thmt@headstyle@margin{%
    \InlineClass{amsthmnnumbertheorem}{\NUMBER}
    \
    \InlineClass{amsthmnametheorem}{\NAME}
    \InlineClass{amsthmnotetheorem}{\NOTE}
}

\let\thmt@headstyle@swapnumber\thmt@headstyle@margin
```

File 495 **lwarp-threadcol.sty**

§ 603 Package threadcol

Pkg threadcol threadcol is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{threadcol}[2013/01/06]
\newcommand{\setthreadname}[1]{}
```

File 496 **lwarp-threeparttable.sty**

§ 604 Package threeparttable

(*Emulates or patches code by* Donald Arseneau.)

Pkg threeparttable threeparttable is emulated.

Table note are contained inside a css of class tnotes. If enumitem is used, the note item labels are also individually highlighted with an additional css of class tnoteitemheader, otherwise they are plain text.

for HTML output:

```
\LWR@ProvidesPackageDrop{threeparttable}[2003/06/13]
```

Env threeparttable [⟨*alignment*⟩]

```
\newenvironment*{threeparttable}[1][b]
    {\def\@captype{table}}
    {}
```

Env tablenotes [⟨*options*⟩]

```
\newenvironment*{tablenotes}[1][]
{%
\LWR@forcenewpage
\BlockClass{tnotes}%
\description%
}
{%
\enddescription%
\endBlockClass%
}
```

\tnote {⟨*text*⟩}

```
\newcommand{\tnote}[1]{\LWR@htmlspan{sup}{#1}}
```

Env measuredfigure [⟨*alignment*⟩]

```
\newenvironment*{measuredfigure}[1][t]
    {\def\@captype{figure}}
    {}
```

File 497 **lwarp-threeparttablex.sty**

§ 605 Package

threeparttablex

Pkg threeparttablex threeparttablex is patched for use by lwarp.

threeparttablex is used with longtable and booktabs as follows:

```
\begin{longtable}{ [column specifiers] }
[ . . . ] \endfirsthead   % or \endhead, for print and HTML
\warpprintonly{          % not used in HTML
  [ . . . ] \endhead     % or \endfirsthead
  [ . . . ] \endfoot
  \bottomrule \insertTableNotes \endlastfoot
}
. . .  table contents . . .
\warpHTMLonly{   % HTML last footer
  \bottomrule
  \UseMinipageWidths     % optional
  \insertTableNotes
  \endlastfoot
}
\end{longtable}
```

table width The table notes are created using a \multicolumn. By default the width is not specified to the browser, so long table notes can cause the table to be spread out horizontally. For HTML output, lwarp guesses the width of the table depending on the number of columns, then restricts its guess to a min/max range. To use this guess for the width of the table notes, use \UseMinipageWidths before \insertTableNotes. The width is then specified, and in many cases the result is an improvement in overall table layout.

for HTML output:

```
\LWR@ProvidesPackagePass{threeparttablex}[2013/07/23]
```

The width is guessed depending on the number of columns, then limited to a min/max.

```
\renewcommand\insertTableNotes{%
    \setlength{\LWR@templengthone}{.375in*\value{LWR@tabletotalLaTeXcols}}%
    \setlength{\LWR@templengthone}{\minof{\textwidth}{\LWR@templengthone}}%
    \setlength{\LWR@templengthone}{\maxof{2.5in}{\LWR@templengthone}}%
  \multicolumn{\value{LWR@tabletotalLaTeXcols}}{c}{%
      \parbox{\LWR@templengthone}{%
        \begin{tablenotes}[\TPTL@optarg]%
          \TPTL@font%
          \TPTL@body%
        \end{tablenotes}%
      }%
  }%
}

\providecommand{\TPTL@tnotex}{}
```

```
16 \renewcommand{\TPTL@tnotex}[2]{\tnote{\nameref{#2}}}
```

File 498 **lwarp-thumb.sty**

§ 606 Package

thumb

Pkg thumb thumb is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{thumb}[1997/12/24]

2 \newcommand*{\Overviewpage}{}
3 \newlength{\thumbheight}
4 \newlength{\thumbwidth}
```

File 499 **lwarp-thumbs.sty**

§ 607 Package

thumbs

Pkg thumbs thumbs is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{thumbs}[2014/03/09]

2 \newcommand{\addthumb}[4]{}
3 \newcommand{\addtitlethumb}[5]{}
4 \newcommand{\stopthumb}{}
5 \newcommand{\continuethumb}{}
6 \newcommand{\thumbsoverview}[1]{}
7 \newcommand{\thumbsoverviewback}[1]{}
8 \newcommand{\thumbsoverviewverso}[1]{}
9 \newcommand{\thumbsoverviewdouble}[1]{}
10 \newcommand{\thumbnewcolumn}{}
11 \newcommand{\addthumbsoverviewtocontents}[2]{}
12 \newcommand{\thumbsnophantom}{}
```

File 500 **lwarp-tikz.sty**

§ 608 Package

tikz

(*Emulates or patches code by* Till Tantau.)

Pkg tikz tikz is supported.

⚠ displaymath and matrices If using display math with `tikzpicture` or `\tikz`, along with matrices with the & character, the document must be modified as follows:

```
\usepackage{tikz}
\tikzset{every picture/.style={ampersand replacement=\&}}
```

and each instance of & in the tikz expression must be replaced with \&.

Accept all options for lwarp-tikz:

```
\LWR@ProvidesPackagePass{tikz}[2015/08/07]
```

catcodes lwarp changes the catcode of $ for its own use. The Ti*k*z babel library temporarily changes catcodes back to normal for Ti*k*z's use. tikz v3.0.0 introduced the babel library which handles catcode changes. For older versions, lwarp must change $'s catcode itself.

Also see:
https://tex.stackexchange.com/questions/16199/test-if-a-package-or-package-option-is-loaded

```
\newbool{LWR@tikzbabel}

\@ifpackagelater{tikz}{2013/12/20}% Test for Tikz version v3.0.0
{\usetikzlibrary{babel}\booltrue{LWR@tikzbabel}}
{\boolfalse{LWR@tikzbabel}}
```

Env pgfpicture The \pgfpicture environment is enclosed inside a \lateximage. Enclose the low-level \pgfpicture in a lateximage. This is also used by the higher-level \tikz and tikzpicture.

```
\preto\pgfpicture{%
    \begin{lateximage}[-tikz-~\PackageDiagramAltText]%
    \ifbool{LWR@tikzbabel}% Test for Tikz version v3.0.0
    {}%
    {\catcode`\$=3}% dollar sign is math shift
}

\appto\endpgfpicture{\end{lateximage}}
```

Ti*k*z is placed inside an SVG image, so use the original meanings of the following:

```
\LetLtxMacro\pgfutil@minipage\LWR@print@minipage
\let\pgfutil@endminipage\endLWR@print@minipage

\let\pgfutil@raggedleft\LWR@print@raggedleft
\let\pgfutil@raggedright\LWR@print@raggedright


\def\pgfutil@font@tiny{\LWR@print@tiny}
\def\pgfutil@font@scriptsize{\LWR@print@scriptsize}
\def\pgfutil@font@footnotesize{\LWR@print@footnotesize}
\def\pgfutil@font@small{\LWR@print@small}
\def\pgfutil@font@normalsize{\LWR@print@normalsize}
\def\pgfutil@font@large{\LWR@print@large}
\def\pgfutil@font@Large{\LWR@print@Large}
\def\pgfutil@font@huge{\LWR@print@huge}
\def\pgfutil@font@Huge{\LWR@print@Huge}

\def\pgfutil@font@itshape{\LWR@print@itshape}
\def\pgfutil@font@bfseries{\LWR@print@bfseries}

```

```
\def\pgfutil@font@normalfont{\LWR@print@normalfont}
```

File 501 **lwarp-tikz-imagelabels.sty**

§ 609 Package tikz-imagelabels

(*Emulates or patches code by* Tobias Plüss.)

Pkg tikz-imagelabels tikz-imagelabels is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{tikz-imagelabels}[2019/06/27]

\BeforeBeginEnvironment{annotationimage}{%
    \begin{lateximage}[-tikz-imagelabels-~\PackageDiagramAltText]%
}

\AfterEndEnvironment{annotationimage}{\end{lateximage}}
```

File 502 **lwarp-titleps.sty**

§ 610 Package titleps

(*Emulates or patches code by* Javier Bezos.)

Pkg titleps titleps is loaded and used by lwarp during HTML output. All user options and macros are ignored and disabled.

Discard all options for lwarp-titleps:

for HTML output:

```
\LWR@ProvidesPackageDrop{titleps}[2016/03/15]
```

\pagestyle and \thispagestyle are already disabled in the lwarp code.

\newpagestyle {⟨*name*⟩} [⟨*style*⟩] {⟨*commands*⟩}

```
\NewDocumentCommand{\newpagestyle}{m o m}{}
```

\renewpagestyle {⟨*name*⟩} [⟨*style*⟩] {⟨*commands*⟩}

```
\NewDocumentCommand{\renewpagestyle}{m o m}{}
```

\sethead [⟨*el*⟩] [⟨*ec*⟩] [⟨*er*⟩] {⟨*ol*⟩} {⟨*oc*⟩} {⟨*or*⟩}

```
\NewDocumentCommand{\sethead}{o o o m m m}{}
```

\setfoot [⟨*el*⟩] [⟨*ec*⟩] [⟨*er*⟩] {⟨*ol*⟩} {⟨*oc*⟩} {⟨*or*⟩}

```
\NewDocumentCommand{\setfoot}{o o o m m m}{}
```

\settitlemarks * {⟨*names*⟩}

```
\NewDocumentCommand{\settitlemarks}{s m}{}
```

\headrule

```
\newcommand*{\headrule}{}
```

\footrule

```
\newcommand*{\footrule}{}
```

\setheadrule {⟨*length*⟩}

```
\newcommand*{\setheadrule}[1]{}
```

\setfootrule {⟨*length*⟩}

```
\newcommand*{\setfootrule}[1]{}
```

\makeheadrule

```
\newcommand*{\makeheadrule}{}
```

\makefootrule

```
\newcommand*{\makefootrule}{}
```

\setmarkboth {⟨*code*⟩}

```
\newcommand{\setmarkboth}[1]{}
```

\widenhead

```
\NewDocumentCommand{\widenhead}{s o o m m}{}
```

\bottitlemarks

```
\newcommand*{\bottitlemarks}{}
```

\toptitlemarks

```
\newcommand*{\toptitlemarks}{}
```

\firsttitlemarks

```
\newcommand*{\firsttitlemarks}{}
```

\nexttitlemarks

```
\newcommand*{\nexttoptitlemarks}{}
```

\outertitlemarks

```
\newcommand*{\outertitlemarks}{}
```

\innertitlemarks

```
\newcommand*{\innertitlemarks}{}
```

\newtitlemark * {⟨*name*⟩}

```
\NewDocumentCommand{\newtitlemark}{s m}{}
```

\pretitlemark * {⟨*section*⟩} {⟨*text*⟩}

```
\NewDocumentCommand{\pretitlemark}{s m m}{}
```

\ifsamemark {⟨*group*⟩} {⟨*command*⟩} {⟨*true*⟩} {⟨*false*⟩}

```
\newcommand{\ifsamemark}[4]{}
```

\setfloathead * [⟨.⟩] [⟨.⟩] [⟨.⟩] {⟨.⟩} {⟨.⟩} {⟨.⟩} {⟨*extra*⟩} [⟨*which*⟩]

```
\NewDocumentCommand{\setfloathead}{s o o o m m m m m}{}
```

\setfloatfoot * [⟨.⟩] [⟨.⟩] [⟨.⟩] {⟨.⟩} {⟨.⟩} {⟨.⟩} {⟨*extra*⟩} [⟨*which*⟩]

```
\NewDocumentCommand{\setfloatfoot}{s o o o m m m m m}{}
```

\nextfloathead * [⟨.⟩] [⟨.⟩] [⟨.⟩] {⟨.⟩} {⟨.⟩} {⟨.⟩} {⟨*extra*⟩} [⟨*which*⟩]

```
\NewDocumentCommand{\nextfloathead}{s o o o m m m m m}{}
```

\nextfloatfoot * [⟨.⟩] [⟨.⟩] [⟨.⟩] {⟨.⟩} {⟨.⟩} {⟨.⟩} {⟨*extra*⟩} [⟨*which*⟩]

```
\NewDocumentCommand{\nextfloatfoot}{s o o o m m m m m}{}
```

\newmarkset {⟨*markset*⟩}

```
\newcommand{\newmarkset}[1]{}
```

\newextramark * {⟨*markset*⟩} {⟨*macro-name*⟩}

```
\NewDocumentCommand{\newextramarkset}{s m m}{}
```

\botextramarks {⟨*markset*⟩}

```
\newcommand{\botextramarks}[1]{}
```

\topextramarks {⟨*markset*⟩}

```
\newcommand{\topextramarks}[1]{}
```

\firstextramarks {⟨*markset*⟩}

```
\newcommand{\firstextramarks}[1]{}
```

\nextextramarks {⟨*markset*⟩}

```
\newcommand{\nexttopextramarks}[1]{}
```

\outerextramarks {⟨*markset*⟩}

```
\newcommand{\outerextramarks}[1]{}
```

\innerextramarks {⟨*markset*⟩}

```
\newcommand{\innerextramarks}[1]{}
```

File 503 **lwarp-titleref.sty**

§ 611 Package

titleref

Pkg titleref titleref is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{titleref}[2001/04/05]

\LetLtxMacro\titleref\nameref

\providecounter{LWR@currenttitle}

\newcommand*{\currenttitle}{%
    \addtocounter{LWR@currenttitle}{1}%
    \label{currenttitle\arabic{LWR@currenttitle}}%
    \nameref{currenttitle\arabic{LWR@currenttitle}}%
}

\newcommand*{\theTitleReference}[2]{}
```

File 504 **lwarp-titlesec.sty**

§ 612 Package

titlesec

(*Emulates or patches code by* Javier Bezos.)

Pkg titlesec titlesec is emulated. All user options and macros are ignored and disabled.

Discard all options for lwarp-titlesec:

for HTML output:

```
\PackageInfo{lwarp}{Using the lwarp version of package ‘titlesec’.}%
\ProvidesPackage{lwarp-titlesec}[2016/03/21]

\newbool{LWR@loadtitleps}
```

```
\boolfalse{LWR@loadtitleps}

\DeclareOption{pagestyles}{
    \booltrue{LWR@loadtitleps}
}

\DeclareOption*{}

\ProcessOptions\relax

\ifbool{LWR@loadtitleps}{
    \RequirePackage{lwarp-titleps}
}{}
```

\titlelabel {⟨*label-format*⟩}

```
\newcommand*{\titlelabel}[1]{}
```

\titleformat* {⟨*command*⟩} {⟨*format*⟩}

\titleformat {⟨*command*⟩} [⟨*shape*⟩] {⟨*format*⟩} {⟨*label*⟩} {⟨*sep*⟩} {⟨*begfore*⟩} [⟨*after*⟩]

```
\newcommand\titleformat{%
  \@ifstar{\ttl@format@s}%
          {\ttl@format@i}}
\newcommand{\ttl@format@s}[1]{}
\NewDocumentCommand{\ttl@format@i}{m o m m m m o}{}
```

\chaptertitlename

```
\@ifundefined{@chapapp}{\let\@chapapp\chaptername}{}
\newcommand\chaptertitlename{\@chapapp}
```

\titlespacing * {⟨*command*⟩} {⟨*left*⟩} {⟨*before*⟩} {⟨*after*⟩} [⟨*right*⟩]

```
\NewDocumentCommand{\titlespacing}{s m m m m o}{}
```

\filright

```
\newcommand*{\filright}{}
```

\filcenter

```
\newcommand*{\filcenter}{}
```

\filleft

```
\newcommand*{\filleft}{}
```

\fillast

```
\newcommand*{\fillast}{}
```

\filinner

```
\newcommand*{\filinner}{}
```

\filouter

```
\newcommand*{\filouter}{}
```

\wordsep

```
\newcommand\wordsep{\fontdimen\tw@\font \@plus
  \fontdimen\thr@@\font \@minus \fontdimen4\font}
```

\titleline * [⟨*align*⟩] {⟨*material*⟩}

```
\NewDocumentCommand{\titleline}{s o m}{}
```

\titlerule [⟨*height*⟩]

```
\providecommand*\titlerule{\@ifstar{\ttl@row}{\ttl@rule}}
\newcommand*{\ttl@rule}[1][]{}
\newcommand*{\ttl@row}[2][]{}
```

\iftitlemeasuring {⟨*true*⟩} {⟨*false*⟩}

```
\newcommand{\iftitlemeasuring}[2]{#2}
```

\assignpagestyle {⟨*command*⟩} {⟨*pagestyle*⟩}

```
\newcommand{\assignpagestyle}[2]{#2}
```

\titleclass {⟨*name*⟩} [⟨*startlevel*⟩] {⟨*class*⟩} [⟨*cmd*⟩]

```
\NewDocumentCommand{\titleclass}{m o m o}{}
```

File 505 **lwarp-titletoc.sty**

§ 613 Package

titletoc

(*Emulates or patches code by* Javier Bezos.)

Pkg titletoc titletoc is emulated. All user options and macros are ignored and disabled.

Discard all options for lwarp-titletoc:

for HTML output:

```
\LWR@ProvidesPackageDrop{titletoc}[2011/12/15]
```

\dottedcontents {⟨*section*⟩} [⟨*left*⟩] {⟨*above*⟩} {⟨*label*⟩} {⟨*leader*⟩}

```
\NewDocumentCommand{\dottedcontents}{m o m m m}{}
```

\titlecontents * {⟨*section*⟩} [⟨*left*⟩] {⟨*above*⟩} {⟨*numbered*⟩} {⟨*numberless*⟩} {⟨*filler*⟩} [⟨*below or begin*⟩] [⟨*separator*⟩] [⟨*end*⟩]

```
\newcommand{\titlecontents}{\@ifstar{\ttl@tcstar}{\ttl@tcnostar}}
\NewDocumentCommand{\ttl@tcstar}{m o m m m m o o o}{}
\NewDocumentCommand{\ttl@tcnostar}{m o m m m m o}{}
```

\contentsmargin [⟨*correction*⟩] {⟨*right*⟩}

```
\newcommand{\contentsmargin}[2][]{}
```

\thecontentslabel

```
\newcommand*{\thecontentslabel}{thecontentslabel}
```

\thecontentspage

```
\newcommand*{\thecontentspage}{thecontentspage}
```

\contentslabel [⟨*format*⟩] {⟨*space*⟩}

```
\newcommand{\contentslabel}[2][]{\thecontentslabel}
```

\contentspage [⟨*format*⟩]

```
\newcommand{\contentspage}[1][]{\thecontentspage}
```

\contentspush {⟨*text*⟩}

```
\newcommand{\contentspush}[1]{}
```

\contentsuse {⟨*name*⟩} {⟨*text*⟩}

```
\newcommand{\contentsuse}[2]{}
```

\startcontents [⟨*name*⟩]

```
\newcommand*{\startcontents}[1][]{}
```

\stopcontents [⟨*name*⟩]

```
\newcommand*{\stopcontents}[1][]{}
```

\resumecontents [⟨*name*⟩]

```
\newcommand*{\resumecontents}[1][]{}
```

\printcontents [⟨*name*⟩] {⟨*prefix*⟩} {⟨*start*⟩} {⟨*code*⟩}

```
\newcommand{\printcontents}[4][]{}
```

\startlist [⟨*name*⟩] {⟨*list*⟩}

```
\newcommand{\startlist}[2][]{}
```

\stoplist [⟨*name*⟩] {⟨*list*⟩}

```
\newcommand{\stoplist}[2][]{}
```

\resumelist [⟨*name*⟩] {⟨*list*⟩}

```
\newcommand{\resumelist}[2][]{}
```

\printlist [⟨*name*⟩] {⟨*list*⟩} {⟨*prefix*⟩} {⟨*code*⟩}

```
\newcommand{\printlist}[4][]{}
```

File 506 **lwarp-titling.sty**

§ 614 Package

titling

(*Emulates or patches code by* Peter Wilson.)

Pkg titling

package support
⚠ load order

lwarp supports the native LaTeX titling commands, and also supports the packages authblk and titling. If both are used, authblk should be loaded before titling.

\published and \subtitle

If using the titling package, additional titlepage fields for \published and \subtitle may be added by using \AddSubtitlePublished in the preamble. See section 69.8.

The various titling footnote restyling commands have no effect.

Pass all options to lwarp-titling:

for HTML output:

```
\LWR@ProvidesPackagePass{titling}[2009/09/04]
```

\@bsmtitlempty Patch \@bsmtitlempty:

```
\let\LWR@orig@bsmtitlempty\@bsmtitlempty
\renewcommand*{\@bsmtitlempty}{%
\LWR@orig@bsmtitlempty%
}
```

\keepthetitle Patch \keepthetitle:

```
\let\LWR@origkeepthetitle\keepthetitle
\renewcommand*{\keepthetitle}{%
\LWR@orig@keepthetitle%
}
```

\killtitle Patch \killtitle:

```
\let\LWR@origkilltitle\killtitle
```

```
\renewcommand*{\killtitle}{%
\LWR@orig@killtitle%
}
```

Env titlingpage

```
\renewenvironment*{titlingpage}
{%
```

Start an HTML titlepage div:

```
\LWR@printpendingfootnotes
\begin{titlepage}
```

Prepare for a custom version of \maketitle inside the titlingpage:

```
\LWR@maketitlesetup
\let\maketitle\LWR@titlingmaketitle
}
{
```

At the end of the environment, end the HTML titlepage div:

```
\end{titlepage}
}
```

Patch the pre/post title/author/date to add HTML tags, then initilize:

```
\AtBeginDocument{
    \pretitle{}
    \posttitle{}

    \preauthor{}
    \postauthor{}

    \predate{}
    \postdate{}
}
```

\LWR@maketitlesetup Patches \thanks macros.

```
\renewcommand*{\LWR@maketitlesetup}{%
```

Redefine the footnote mark:

```
    \def\@makefnmark{\textsuperscript{\@thefnmark}}%
```

\thefootnote ⇒ \nameuse{arabic}{footnote}, or
\thefootnote ⇒ \nameuse{fnsymbol}{footnote}

Redefine the footnote text:

```
    \long\def\@makefntext##1{%
```

Make the footnote mark and some extra horizontal space for the tags:

```
        \makethanksmark~%
```

\makethanksmark ⇒ \thanksfootmark ⇒ \tamark ⇒ \@thefnmark ⇒ \itshape a (or similar)

Print the text:

```
        ##1%
    }% \@makefntext
}
```

\thanksfootmark

```
\renewcommand{\thanksfootmark}{%
%   \hb@xt@\thanksmarkwidth{\hfil\normalfont%
        \thanksscript{%
            \thanksfootpre \tamark \thanksfootpost%
        }%
%   }%
}
```

\maketitle HTML mode. Creates an HTML titlepage div and typesets the title, etc.

Code from the titling package is adapted, simplified, and modified for HTML output.

```
\renewcommand*{\maketitle}{%
```

An HTML titlepage is used for all classes.

```
    \begin{titlepage}
```

Select which kind of footnote marks to use:

```
    \@bsmarkseries
```

Set up special patches:

```
    \LWR@maketitlesetup
```

Typeset the title, etc:

```
    \@maketitle
```

Immediately generate any \thanks footnotes:

```
    \LWR@stoppars\@thanks\LWR@startpars
```

Close the HTML titlepage div:

```
    \end{titlepage}
```

Reset the footnote counter:

```
    \@bscontmark
}
```

`\@maketitle` Typesets the title, etc. Patched for HTML.

```
\DeclareDocumentCommand{\@maketitle}{}{%
    \maketitlehooka
    {
        \LWR@stoppars\LWR@htmltag{\LWR@tagtitle}%
        \@bspretitle \@title \@bsposttitle%
        \LWR@htmltag{\LWR@tagtitleend}\LWR@startpars%
    }
    \maketitlehookb
    {
        \begin{BlockClass}{author}
        \renewcommand{\and}{%
            \end{BlockClass}%
            \begin{BlockClass}{oneauthor}%
        }
        \begin{BlockClass}{oneauthor}%
        \@bspreauthor \@author  \@bspostauthor%
        \end{BlockClass}%
        \end{BlockClass}%
    }
    \maketitlehookc
    {
        \begin{BlockClass}{titledate}%
        \@bspredate \@date \@bspostdate%
        \end{BlockClass}%
    }
    \maketitlehookd
}
```

`\LWR@titlingmaketitle` `\maketitle` for use inside an HTML `titlingpage` environment.

```
\renewcommand*{\LWR@titlingmaketitle}{%
```

Keep pending footnotes out of the title block:

```
\LWR@stoppars\@thanks\LWR@startpars
```

Select which kind of footnote marks to use:

```
\@bsmarkseries
```

Set up special patches:

```
\LWR@maketitlesetup
```

Typeset the title, etc:

```
\@maketitle
```

Immediately generate any \thanks footnotes:

```
\LWR@stoppars\@thanks\LWR@startpars
```

Reset the footnote counter:

```
\@bscontmark
}
```

\thanksmarkseries {⟨*series*⟩}

Sets the type of footnote marks used by \thanks, where type is 'arabic', 'roman', 'fnsymbol', etc.

```
\renewcommand{\thanksmarkseries}[1]{%
\def\@bsmarkseries{\renewcommand{\thefootnote}{\@nameuse{#1}{footnote}}}%
}
```

Set default titlepage thanks footnote marks. See section 69.7.

```
\@ifclassloaded{memoir}{
   \thanksmarkseries{arabic}
}{% not memoir
\if@titlepage
   \thanksmarkseries{arabic}
\else
   \thanksmarkseries{fnsymbol}
\fi
}% not memoir
```

File 507 **lwarp-tocbasic.sty**

§ 615 Package

tocbasic

(*Emulates or patches code by* Markus Kohm.)

Pkg tocbasic tocbasic is nullified for lwarp.

This package may be loaded standalone, but is also loaded automatically if koma-script classes are in use. \DeclareDocumentCommand is used to overwrite the koma-script definitions.

for HTML output:

```
\LWR@ProvidesPackagePass{tocbasic}[2018/12/30]

\DeclareDocumentCommand{\usetocbasicnumberline}{o}{}
\DeclareDocumentCommand{\DeclareTOCStyleEntry}{o m m}{}
\DeclareDocumentCommand{\DeclareTOCStyleEntries}{o m m}{}
\DeclareDocumentCommand{\DeclareTOCEntryStyle}{m o m}{}
\DeclareDocumentCommand{\DefineTOCEntryOption}{m o m}{}
\DeclareDocumentCommand{\DefineTOCEntryBooleanOption}{m o m m m}{}
\DeclareDocumentCommand{\DefineTOCEntryCommandOption}{m o m m m}{}
\DeclareDocumentCommand{\DefineTOCEntryIfOption}{m o m m m}{}
```

```
\DeclareDocumentCommand{\DefineTOCEntryLengthOption}{m o m m m}{}
\DeclareDocumentCommand{\DefineTOCEntryNumberOption}{m o m m m}{}
\DeclareDocumentCommand{\CloneTOCEntryStyle}{m m}{}
\DeclareDocumentCommand{\TOCEntryStyleInitCode}{m m}{}
\DeclareDocumentCommand{\TOCEntryStyleStartInitCode}{m m}{}
```

File 508 **lwarp-tocbibind.sty**

§ 616 Package

tocbibind

(*Emulates or patches code by* Peter Wilson.)

Pkg tocbibind tocbibind is patched for use by lwarp.

placement and TOC options An index may be placed inline with other HTML text, or on its own HTML page:

Pkg makeidx **Inline, with a manual TOC entry:**

A commonly-used method to introduce an index in a LaTeX document:

```
\cleardoublepage
\phantomsection
\addcontentsline{toc}{section}{\indexname}% or chapter
\printindex
```

Pkg makeidx **On its own HTML page, with a manual TOC entry:**

```
\begin{warpprint}
\cleardoublepage
\phantomsection
\addcontentsline{toc}{section}{\indexname}% or chapter
\end{warpprint}
\ForceHTMLPage
\ForceHTMLTOC
\printindex
```

Pkg tocbibind **Inline, with an automatic TOC entry:**

The tocbibind package may be used to automatically place an entry in the TOC.

```
\usepackage[nottoc]{tocbibind}
. . .
\cleardoublepage
\phantomsection % to fix print-version index link
\printindex
```

Pkg tocbibind **On its own HTML page, with an automatic TOC entry:**

```
\usepackage[nottoc]{tocbibind}
. . .
\cleardoublepage
\phantomsection % to fix print-version index link
\ForceHTMLPage
\printindex
```

Opt [tocbibind] numindex
numbered index section

Use the tocbibind numindex option to generate a numbered index. Without this option, the index heading has no number.

Other packages, such as imakeidx, may also have options for including the index in the Table of Contents.

for HTML output:

```
\let\simplechapterdelim\relax

\LWR@ProvidesPackagePass{tocbibind}[2010/10/13]

\renewenvironment{theindex}%
{%
     \if@bibchapter
        \if@donumindex
            \chapter{\indexname}
        \else
          \if@dotocind
            \chapter*{\indexname}
            \addcontentsline{toc}{chapter}{\LWR@isolate{\indexname}}
          \else
            \chapter*{\indexname}
          \fi
        \fi
     \else
        \if@donumindex
            \section{\indexname}
        \else
          \if@dotocind
            \section*{\indexname}
            \addcontentsline{toc}{\@tocextra}{\LWR@isolate{\indexname}}
          \else
            \section*{\indexname}
          \fi
        \fi
     \fi
\let\item\LWR@indexitem%
\let\subitem\LWR@indexsubitem%
\let\subsubitem\LWR@indexsubsubitem%
}{}
```

The following code is shared by anonchap.

```
\DeclareDocumentCommand{\simplechapter}{O{\@empty}}{%
    \def\@chapcntformat##1{%
        #1~\csname the##1\endcsname\simplechapterdelim\quad%
    }%
}

\DeclareDocumentCommand{\restorechapter}{}{%
\let\@chapcntformat\@seccntformat%
}
```

File 509 **lwarp-tocdata.sty**

§ 617 Package

tocdata

(*Emulates or patches code by* Brian Dunn.)

Pkg tocdata tocdata is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{tocdata}[2019/07/06]

\renewcommand*{\LWR@maybetocdata}{%
    \ifdefempty{\TD@thistocdata}{}{%
        \qquad \InlineClass{authorartist}{\tocdataformat{\TD@thistocdata}}%
        \def\TD@thistocdata{}
    }
}

\renewrobustcmd{\tocdatapartprint}[4]
{%
    \InlineClass{authorartist}{%
        \qquad --- %
        \TDoptionalnameprint{#1}\TDoptionalnameprint{#2}#3#4%
    }%
}

\@ifundefined{chapter}{}{
    \let\tocdatachapterprint\tocdatapartprint
}
\let\tocdatasectionprint\tocdatapartprint
\let\tocdatasubsectionprint\tocdatapartprint

\newcommand*{\LWR@TD@settextalign}[1]{%
    \def\LWR@TD@textalign{justify}%
    \ifcsstring{TD@#1align}{\centering}%
        {\def\LWR@TD@textalign{center}}%
        {}%
    \ifcsstring{TD@#1align}{\raggedleft}%
        {\def\LWR@TD@textalign{right}}%
        {}%
    \ifcsstring{TD@#1align}{\raggedright}%
        {\def\LWR@TD@textalign{left}}%
        {}%
}

\renewcommand{\TDartistauthorprint}[5]{%
    \LWR@TD@settextalign{#1}%
    \begin{BlockClass}[text-align:\LWR@TD@textalign]{floatnotes}%
   \InlineClass{authorartist}{\TDoptionalnameprint{#2}\TDoptionalnameprint{#3}#4#5}%
    \end{BlockClass}%
}

\newcommand*{\LWR@TD@setnamealign}[1]{%
    \def\LWR@TD@textalign{justify}%
    \ifcsstring{TD@#1textalign}{\centering}%
        {\def\LWR@TD@textalign{center}}%
        {}%
```

```
    \ifcsstring{TD@#1textalign}{\raggedleft}%
        {\def\LWR@TD@textalign{right}}%
        {}%
    \ifcsstring{TD@#1textalign}{\raggedright}%
        {\def\LWR@TD@textalign{left}}%
        {}%
}

\renewcommand{\TDartistauthortextprint}[2]{%
    \LWR@TD@setnamealign{#1}%
    \begin{BlockClass}[text-align:\LWR@TD@textalign]{floatnotes}%
    #2%
    \end{BlockClass}%
}
```

File 510 **lwarp-tocenter.sty**

§ 618 Package

tocenter

Pkg tocenter

tocenter is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{tocenter}[2004/12/09]

\NewDocumentCommand{\ToCenter}{s o m m}{}
\NewDocumentCommand{\FromMargins}{s o m m m m}{}
```

File 511 **lwarp-tocloft.sty**

§ 619 Package

tocloft

(*Emulates or patches code by* Peter Wilson.)

Pkg tocloft

tocloft is emulated. Most user options and macros are ignored and disabled. `\newlistof` and `\cftchapterprecis` are supported.

Pkg tocloft

⚠ tocloft & other packages

If using tocloft with tocbibind, anonchap, fncychap, or other packages which change chapter title formatting, load tocloft with its `titles` option, which tells tocloft to use standard LaTeX commands to create the titles, allowing other packages to work with it.

Discard all options for lwarp-tocloft:

for HTML output:

```
\LWR@ProvidesPackageDrop{tocloft}[2017/08/31]
```

`\tocloftpagestyle` {⟨*style*⟩}

```
\newcommand{\tocloftpagestyle}[1]{}
```

`\cftmarktoc`

```
\newcommand*{\cftmarktoc}{}
```

\cfttoctitlefont

```
\newcommand*{\cfttoctitlefont}{}
```

\cftaftertoctitle

```
\newcommand*{\cftaftertoctitle}{}

\newlength{\cftbeforetoctitleskip}
\newlength{\cftaftertoctitleskip}
```

\cftmarklof

```
\newcommand*{\cftmarklof}{}
```

\cftloftitlefont

```
\newcommand*{\cftloftitlefont}{}
```

\cftafterloftitle

```
\newcommand*{\cftafterloftitle}{}

\newlength{\cftbeforeloftitleskip}
\newlength{\cftafterloftitleskip}
```

\cftmarklot

```
\newcommand*{\cftmarklot}{}
```

\cftlottitlefont

```
\newcommand*{\cftlottitlefont}{}
```

\cftafterlottitle

```
\newcommand*{\cftafterlottitle}{}

\newlength{\cftbeforelottitleskip}
\newlength{\cftafterlottitleskip}
```

\cftdot

```
\providecommand*{\cftdot}{.}
```

\cftdotsep

```
\providecommand*{\cftdotsep}{1}
```

\cftnodots

```
\providecommand*{\cftnodots}{5000}
```

`\cftdotfill` {⟨*sep*⟩}

```
\providecommand{\cftdotfill}[1]{}
```

`\cftsetpnumwidth` {⟨*length*⟩}

```
\DeclareDocumentCommand{\cftsetpnumwidth}{m}{}
```

`\cftsetrmarg` {⟨*length*⟩}

```
\DeclareDocumentCommand{\cftsetrmarg}{m}{}
```

`\cftpnumalign` {⟨*alignment*⟩}

```
\DeclareDocumentCommand{\cftpnumalign}{m}{}

\LWR@providelength{\cftparskip}
```

The part-related items are also provided by memoir:

```
\LWR@providelength{\cftbeforepartskip}
\LWR@providelength{\cftpartindent}
\LWR@providelength{\cftpartnumwidth}
\providecommand*{\cftpartfont}{}
\providecommand*{\cftpartpresnum}{}
\providecommand*{\cftpartaftersnum}{}
\providecommand*{\cftpartaftersnumb}{}
\providecommand*{\cftpartleader}{}
\providecommand*{\cftpartdotsep}{1}
\providecommand*{\cftpartpagefont}{}
\providecommand*{\cftpartafterpnum}{}
```

memoir uses the full name “chapter” instead of “chap”:

```
\LWR@providelength{\cftbeforechapskip}
\LWR@providelength{\cftchapindent}
\LWR@providelength{\cftchapnumwidth}
\newcommand*{\cftchapfont}{}
\newcommand*{\cftchappresnum}{}
\newcommand*{\cftchapaftersnum}{}
\newcommand*{\cftchapaftersnumb}{}
\newcommand*{\cftchapleader}{}
\newcommand*{\cftchapdotsep}{1}
\newcommand*{\cftchappagefont}{}
\newcommand*{\cftchapafterpnum}{}
```

The following do not appear in memoir:

```
\LWR@providelength{\cftbeforesecskip}
\LWR@providelength{\cftsecindent}
\LWR@providelength{\cftsecnumwidth}
\newcommand*{\cftsecfont}{}
```

```
\newcommand*{\cftsecpresnum}{}
\newcommand*{\cftsecaftersnum}{}
\newcommand*{\cftsecaftersnumb}{}
\newcommand*{\cftsecleader}{}
\newcommand*{\cftsecdotsep}{1}
\newcommand*{\cftsecpagefont}{}
\newcommand*{\cftsecafterpnum}{}

\LWR@providelength{\cftbeforesubsecskip}
\LWR@providelength{\cftsubsecindent}
\LWR@providelength{\cftsubsecnumwidth}
\newcommand*{\cftsubsecfont}{}
\newcommand*{\cftsubsecpresnum}{}
\newcommand*{\cftsubsecaftersnum}{}
\newcommand*{\cftsubsecaftersnumb}{}
\newcommand*{\cftsubsecleader}{}
\newcommand*{\cftsubsecdotsep}{1}
\newcommand*{\cftsubsecpagefont}{}
\newcommand*{\cftsubsecafterpnum}{}

\LWR@providelength{\cftbeforesubsubsecskip}
\LWR@providelength{\cftsubsubsecindent}
\LWR@providelength{\cftsubsubsecnumwidth}
\newcommand*{\cftsubsubsecfont}{}
\newcommand*{\cftsubsubsecpresnum}{}
\newcommand*{\cftsubsubsecaftersnum}{}
\newcommand*{\cftsubsubsecaftersnumb}{}
\newcommand*{\cftsubsubsecleader}{}
\newcommand*{\cftsubsubsecdotsep}{1}
\newcommand*{\cftsubsubsecpagefont}{}
\newcommand*{\cftsubsubsecafterpnum}{}

\LWR@providelength{\cftbeforeparaskip}
\LWR@providelength{\cftparaindent}
\LWR@providelength{\cftparanumwidth}
\newcommand*{\cftparafont}{}
\newcommand*{\cftparapresnum}{}
\newcommand*{\cftparaaftersnum}{}
\newcommand*{\cftparaaftersnumb}{}
\newcommand*{\cftparaleader}{}
\newcommand*{\cftparadotsep}{1}
\newcommand*{\cftparapagefont}{}
\newcommand*{\cftparaafterpnum}{}

\LWR@providelength{\cftbeforesubparaskip}
\LWR@providelength{\cftsubparaindent}
\LWR@providelength{\cftsubparanumwidth}
\newcommand*{\cftsubparafont}{}
\newcommand*{\cftsubparapresnum}{}
\newcommand*{\cftsubparaaftersnum}{}
\newcommand*{\cftsubparaaftersnumb}{}
\newcommand*{\cftsubparaleader}{}
\newcommand*{\cftsubparadotsep}{1}
\newcommand*{\cftsubparapagefont}{}
\newcommand*{\cftsubparaafterpnum}{}
```

```
\LWR@providelength{\cftbeforefigskip}
\LWR@providelength{\cftfigindent}
\LWR@providelength{\cftfignumwidth}
\newcommand*{\cftfigfont}{}
\newcommand*{\cftfigpresnum}{}
\newcommand*{\cftfigaftersnum}{}
\newcommand*{\cftfigaftersnumb}{}
\newcommand*{\cftfigleader}{}
\newcommand*{\cftfigdotsep}{1}
\newcommand*{\cftfigpagefont}{}
\newcommand*{\cftfigafterpnum}{}

\LWR@providelength{\cftbeforesubfigskip}
\LWR@providelength{\cftsubfigindent}
\LWR@providelength{\cftsubfignumwidth}
\newcommand*{\cftsubfigfont}{}
\newcommand*{\cftsubfigpresnum}{}
\newcommand*{\cftsubfigaftersnum}{}
\newcommand*{\cftsubfigaftersnumb}{}
\newcommand*{\cftsubfigleader}{}
\newcommand*{\cftsubfigdotsep}{1}
\newcommand*{\cftsubfigpagefont}{}
\newcommand*{\cftsubfigafterpnum}{}

\LWR@providelength{\cftbeforetabskip}
\LWR@providelength{\cfttabindent}
\LWR@providelength{\cfttabnumwidth}
\newcommand*{\cfttabfont}{}
\newcommand*{\cfttabpresnum}{}
\newcommand*{\cfttabaftersnum}{}
\newcommand*{\cfttabaftersnumb}{}
\newcommand*{\cfttableader}{}
\newcommand*{\cfttabdotsep}{1}
\newcommand*{\cfttabpagefont}{}
\newcommand*{\cfttabafterpnum}{}

\LWR@providelength{\cftbeforesubtabskip}
\LWR@providelength{\cftsubtabindent}
\LWR@providelength{\cftsubtabnumwidth}
\newcommand*{\cftsubtabfont}{}
\newcommand*{\cftsubtabpresnum}{}
\newcommand*{\cftsubtabaftersnum}{}
\newcommand*{\cftsubtabaftersnumb}{}
\newcommand*{\cftsubtableader}{}
\newcommand*{\cftsubtabdotsep}{1}
\newcommand*{\cftsubtabpagefont}{}
\newcommand*{\cftsubtabafterpnum}{}

\DeclareDocumentCommand{\cftsetindents}{m m m}{}

\providecommand{\cftpagenumbersoff}[1]{}
\providecommand{\cftpagenumberson}[1]{}
```

\newlistentry [⟨*within*⟩] {⟨*counter*⟩} {⟨*ext*⟩} {⟨*level-1*⟩}

```
\DeclareDocumentCommand{\newlistentry}{o m m m}
{%
\LWR@traceinfo{newlistentry #2 #3 #4}%
\IfValueTF{#1}%
{%
    \@ifundefined{c@#2}{%
        \newcounter{#2}[#1]%
        \expandafter\edef\csname the#2\endcsname{%
            \expandafter\noexpand\csname the#1\endcsname.\noexpand\arabic{#2}%
        }%
    }{}%
}%
{%
    \@ifundefined{c@#2}{%
        \newcounter{#2}%
    }{}%
}%
\@namedef{l@#2}##1##2{%
    \hypertocfloat{1}{#2}{#3}{##1}{##2}%
    \def\cftwhatismyname{#2}% from memoir
}%
\expandafter\newlength\csname cftbefore#2skip\endcsname%
\expandafter\newlength\csname cft#2indent\endcsname%
\expandafter\newlength\csname cft#2numwidth\endcsname%
\@namedef{cft#2font}{}%
\@namedef{cft#2presnum}{}%
\@namedef{cft#2aftersnum}{}%
\@namedef{cft#2aftersnumb}{}%
\@namedef{cft#2leader}{}%
\@namedef{cft#2dotsep}{1}%
\@namedef{cft#2pagefont}{}%
\@namedef{cft#2afterpnum}{}%
\@namedef{toclevel@#2}{#4}%
\@namedef{cft#2fillnum}##1{}%
\LWR@traceinfo{newlistentry done}%
}
```

\newlistof [⟨*within*⟩] {⟨*type*⟩} {⟨*ext*⟩} {⟨*listofname*⟩}

Emulated through the \newfloat mechanism.

```
\DeclareDocumentCommand{\newlistof}{o m m m}
{%
    \IfValueTF{#1}%
        {\newlistentry[#1]{#2}{#3}{0}}%
        {\newlistentry{#2}{#3}{0}}%
    \@namedef{ext@#2}{#3}%
    \@ifundefined{c@#3depth}{\newcounter{#3depth}}{}%
    \setcounter{#3depth}{1}%
    \@namedef{cftmark#3}{}%
    \@namedef{listof#2}{\LWR@listof{#2}{#4}}%
    \@namedef{@cftmake#3title}{}%
    \expandafter\newlength\csname cftbefore#3titleskip\endcsname%
    \expandafter\newlength\csname cftafter#3titleskip\endcsname%
```

```
    \@namedef{cft#3titlefont}{}%
    \@namedef{cftafter#3title}{}%
    \@namedef{cft#3prehook}{}%
    \@namedef{cft#3posthook}{}%
}
```

`\cftchapterprecis` {⟨*text*⟩}

```
\newcommand{\cftchapterprecis}[1]{%
  \cftchapterprecishere{#1}
  \cftchapterprecistoc{#1}}
\newcommand{\cftchapterprecishere}[1]{%
  \begin{quote}\textit{#1}\end{quote}}
\newcommand{\cftchapterprecistoc}[1]{
  \addtocontents{toc}{%
  {
     \protect\begin{quote}#1\protect\end{quote}}
  }
}
```

File 512 **lwarp-tocstyle.sty**

§ 620 Package

tocstyle

Pkg tocstyle tocstyle is ignored.

⚠ Not fully tested! Please send bug reports!

for HTML output:

```
\LWR@ProvidesPackageDrop{tocstyle}[2017/02/23]
```

```
\newcommand*{\usetocstyle}[2][]{}
\newcommand*{\deactivatetocstyle}[1][]{}
\newcommand*{\reactivatetocstyle}[1][]{}
\NewDocumentCommand{\settocfeature}{o o m m}{}
\NewDocumentCommand{\settocstylefeature}{o m m}{}
\NewDocumentCommand{\newtocstyle}{o o m m}{}
\newcommand*{\aliastoc}[2]{}
\newcommand*{\showtoc}[2][]{}
\newcommand{\iftochasdepth}[4]{}
```

File 513 **lwarp-todo.sty**

§ 621 Package

todo

(*Emulates or patches code by* Federico Garcia.)

Pkg todo todo is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{todo}[2010/03/31]
```

```
\renewcommand\todoitem[2]{%
    \refstepcounter{todo}%
    \item[%
        \HTMLunicode{2610} \quad
        \ref{todopage:\thetodo}
     ] : {\todoformat\ifx#1\todomark\else\textbf{#1} \fi}#2%
    \label{todolbl:\thetodo}%
}%

\renewcommand\doneitem[2]{%
    \stepcounter{todo}%
    \item[%
        \HTMLunicode{2611} \quad
        \ref{todopage:\thetodo}
    ] \@nameuse{@done\the\c@todo}:
        {\todoformat\ifx#1\todomark\else\textbf{#1} \fi}#2%
}

\xpatchcmd{\@displaytodo}
    {\todoformat #1}{\todoformat \textbf{#1}}{}
    {\PackageWarning{lwarp-todo}{Unable to patch @displaytodo.}}

\xpatchcmd{\@displayfulltodo}
    {\todoformat #1}{\todoformat \textbf{#1}}{}
    {\PackageWarning{lwarp-todo}{Unable to patch @displayfulltodo.}}

\patchcmd{\todoenv}{\itshape see text.}{\textit{see text.}}{}
    {\PackageWarning{lwarp-todo}{Unable to patch todoenv.}}

\patchcmd{\astodos}{\todoformat #1}{\todoformat \textbf{#1}}{}
    {\PackageWarning{lwarp-todo}{Unable to patch astodos.}}

\AtBeginDocument{
    \crefname{todo}{todo}{todos}
    \Crefname{todo}{Todo}{Todos}
}
```

File 514 **lwarp-todonotes.sty**

§ 622 Package

todonotes

(*Emulates or patches code by* Henrik Skov Midtiby.)

Pkg todonotes todonotes is emulated.

The documentation for todonotes and luatodonotes have an example with a todo inside a caption. If this example does not work it will be necessary to move the todo outside of the caption.

for HTML output:

```
\LWR@ProvidesPackagePass{todonotes}[2012/07/25]

\if@todonotes@disabled
\else
```

```
4
5 \newcommand{\ext@todo}{tdo}
6
7 \renewcommand{\l@todo}[2]{\hypertocfloat{1}{todo}{ldo}{#1}{#2}}


8 \let\LWRTODONOTES@orig@todototoc\todototoc
9
10 \renewcommand*{\todototoc}{%
11 \LWR@phantomsection%
12 \LWRTODONOTES@orig@todototoc%
13 }
14
15 \renewcommand{\@todonotes@drawMarginNoteWithLine}{
16 \fcolorbox
17     {\@todonotes@currentbordercolor}
18     {\@todonotes@currentbackgroundcolor}
19     {\arabic{@todonotes@numberoftodonotes}}
20 \marginpar{\@todonotes@drawMarginNote}
21 }
22
23 \renewcommand{\@todonotes@drawInlineNote}{%
24 \fcolorboxBlock%
25     {\@todonotes@currentbordercolor}%
26     {\@todonotes@currentbackgroundcolor}%
27     {%
28         \if@todonotes@authorgiven%
29         {\@todonotes@author:\,}%
30         \fi%
31         \@todonotes@text%
32     }%
33 }
34
35 \renewcommand{\@todonotes@drawMarginNote}{%
36     \if@todonotes@authorgiven%
37         \@todonotes@author\par%
38     \fi%
39     \arabic{@todonotes@numberoftodonotes}: %
40     \fcolorbox%
41     {\@todonotes@currentbordercolor}%
42     {\@todonotes@currentbackgroundcolor}%
43     {%
44         \@todonotes@sizecommand%
45         \@todonotes@text %
46     }%
47 }%
48
49 \renewcommand{\@todonotes@drawLineToRightMargin}{}
50
51 \renewcommand{\@todonotes@drawLineToLeftMargin}{}
52
53 \renewcommand{\missingfigure}[2][]{%
54 \setkeys{todonotes}{#1}%
55 \addcontentsline{tdo}{todo}{\@todonotes@MissingFigureText: #2}%
56 \fcolorboxBlock%
57     {\@todonotes@currentbordercolor}%
```

```
    {\@todonotes@currentfigcolor}%
    {%
        \setlength{\fboxrule}{4pt}%
        \fcolorbox{red}{white}{Missing figure} \quad #2%
    }
}

\LetLtxMacro\LWRTODONOTES@orig@todo\@todo

\RenewDocumentCommand{\@todo}{o m}{%
\begingroup%
\renewcommand*{\phantomsection}{}%
\IfValueTF{#1}{%
    \LWRTODONOTES@orig@todo[#1]{#2}%
}{%
    \LWRTODONOTES@orig@todo{#2}%
}
\endgroup%
}

\fi% \if@todonotes@disabled
```

File 515 **lwarp-topcapt.sty**

§ 623 Package topcapt

Pkg topcapt topcapt is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{topcapt}[2004/12/11]

\LetLtxMacro\topcaption\caption
```

File 516 **lwarp-tram.sty**

§ 624 Package tram

Pkg tram tram is emulated.

⚠ block only The HTML emulation uses a , which must not appear inside an HTML or an HTML paragraph. For this reason, the tram environment should only be used to contain paragraphs inside a \parbox or minipage. tram should not be used to mark up inline text.

To disable tram, allowing source compatibility with inline uses:

```
\begin{warpHTML}
\renewenvironment{tram}[1][]{}{}
\end{warpHTML}
```

for HTML output:

```
\LWR@ProvidesPackageDrop{tram}[2013/04/04]
```

```
\newenvironment{tram}[1][]%
    {\BlockClass[background:lightgray]{tram}}
    {\endBlockClass}
```

File 517 **lwarp-transparent.sty**

§ 625 Package

transparent

(*Emulates or patches code by* Heiko Oberdiek.)

Pkg transparent transparent is emulated. `\texttransparent` works for inline objects. `\transparent` only works for `\includegraphics`.

⚠ Not XeLaTeX! Note that transparent does not work with XeLaTeX.

for HTML output:

```
\LWR@ProvidesPackagePass{transparent}[2019/11/29]

\newcommand*{\LWR@HTML@transparent}[1]{\edef\LWR@opacity{#1}}

\LWR@formatted{transparent}


\newcommand*{\LWR@HTML@texttransparent}[2]{%
\begingroup%
\transparent{#1}%
\InlineClass[opacity: #1]{transparent}{#2}%
\endgroup%
}

\LWR@formatted{texttransparent}
```

File 518 **lwarp-trimclip.sty**

§ 626 Package

trimclip

Pkg trimclip trimclip is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{trimclip}[2018/04/08]
```

The third argument, the text, is not touched. This allows `\bgroup` / `\egroup`, and verbatim content.

```
\csdef{trimbox}{\@ifstar\@gobble\@gobble}
\csletcs{trimbox*}{trimbox}
\def\endtrimbox{}
\csletcs{endtrimbox*}{endtrimbox}

\csletcs{clipbox}{trimbox}
\csletcs{clipbox*}{trimbox}
\csletcs{endclipbox}{endtrimbox}
```

```
\csletcs{endclipbox*}{endtrimbox}

\csletcs{marginbox}{trimbox}
\csletcs{marginbox*}{trimbox}
\csletcs{endmarginbox}{endtrimbox}
\csletcs{endmarginbox*}{endtrimbox}
```

File 519 **lwarp-trivfloat.sty**

§ 627 Package

trivfloat

(*Emulates or patches code by* Joseph Wright.)

Pkg trivfloat trivfloat is forced to use the built-in lwarp emulation for floats.

To create a new float type and change its name:

```
\trivfloat{example}
\renewcommand{\examplename}{Example Name}
\crefname{example}{example}{examples}
\Crefname{example}{Example}{Examples}
```

Discard all options for lwarp-trivfloat. This tells trivfloat not to use floatrow or memoir.

```
\LWR@ProvidesPackageDrop{trivfloat}[2009/04/23]
\LWR@origRequirePackage{trivfloat}
```

\tfl@chapter@fix Nullified at the beginning of the document. Is used by trivfloat to correct float chapter numbers, but is not needed for lwarp.

```
\AtBeginDocument{\DeclareDocumentCommand{\tfl@chapter@fix}{m m}{}}
```

§ 627.1 Combining \newfloat, \trivfloat, and algorithmicx

For both print and HTML output:

⚠ When using float, trivfloat, or algorithmicx at the same time, be aware of conflicting file usage. algorithmicx uses .loa. trivfloat by default starts with .loa and goes up for additional floats, skipping .lof and .lot.

⚠ When using \newfloat, be sure to manually assign higher letters to the \newfloat files to avoid .loa used by algorithmicx, and any files used by trivfloat. Also avoid using .lof and .lot.

⚠ When using \trivfloat, you may force it to avoid conflicting with algorithmicx by starting trivfloat's file extensions with .lob:

```
\makeatletter
\setcounter{tfl@float@cnt}{1} % start trivfloats with .lob
\makeatletter
```

File 520 **lwarp-truncate.sty**

§ 628 Package
# truncate

Pkg truncate truncate is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{truncate}[2001/08/20]

\providecommand{\TruncateMarker}{}
\newcommand{\truncate}[3][\TruncateMarker]{#3}
```

File 521 **lwarp-turnthepage.sty**

§ 629 Package
# turnthepage

Pkg turnthepage turnthepage is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{turnthepage}[2011/03/24]

\newcommand{\turnthepage}{}
```

File 522 **lwarp-twoup.sty**

§ 630 Package
# twoup

Pkg twoup twoup is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{twoup}[2007/02/26]

\newcommand{\cleartolastpage}{}
```

File 523 **lwarp-txfonts.sty**

§ 631 Package
# txfonts

(*Emulates or patches code by* Young Ryu.)

Pkg txfonts txfonts is used as-is for SVG math, and is emulated for MathJax.

for HTML output:

```
\LWR@ProvidesPackagePass{txfonts}[2008/01/22]
```

For MathJax:

```
\LWR@origRequirePackage{lwarp-common-mathjax-letters}

\begin{warpMathJax}
\LWR@infoprocessingmathjax{txfonts}

\LWR@mathjax@addgreek@l@up{}{up}
\end{warpMathJax}
```

File 524 **lwarp-txgreeks.sty**

§ 632 Package

txgreeks

(*Emulates or patches code by* Jean-François Burnol.)

Pkg txgreeks txgreeks is used as-is for SVG math, and is emulated for MathJax.

The MathJax emulation honors all package options.

for HTML output:

```
\LWR@ProvidesPackagePass{txgreeks}[2011/03/16]

\LWR@infoprocessingmathjax{txgreeks}

\LWR@origRequirePackage{lwarp-common-mathjax-letters}

\begin{warpMathJax}
\iftgs@uplower% upright lowercase Greek
    \LWR@mathjax@addgreek@l@up{}{}
    \LWR@mathjax@addgreek@l@it{other}{}
\else% italic lowercase Greek
    \LWR@mathjax@addgreek@l@it{}{}
    \LWR@mathjax@addgreek@l@up{other}{}
\fi

\iftgs@itupper % italic uppercase Greek
    \LWR@mathjax@addgreek@u@it*{}{}
    \LWR@mathjax@addgreek@u@up*{other}{}
    \LWR@mathjax@addgreek@u@up*{var}{}
\else% upright uppercase Greek
    \LWR@mathjax@addgreek@u@up*{}{}
    \LWR@mathjax@addgreek@u@it*{other}{}
    \LWR@mathjax@addgreek@u@it*{var}{}
\fi
\end{warpMathJax}
```

File 525 **lwarp-typearea.sty**

§ 633 Package

typearea

(*Emulates or patches code by* Markus Kohm.)

Pkg typearea typearea is emulated.

This package may be loaded standalone, but is also loaded automatically if koma-script classes are in use. \DeclareDocumentCommand is used to overwrite the koma-script definitions.

for HTML output:

```
\LWR@ProvidesPackageDrop{typearea}[2018/03/30]

\DeclareDocumentCommand{\typearea}{o m}{}
\DeclareDocumentCommand{\recalctypearea}{}{}
\@ifundefined{footheight}{\newlength\footheight}{}
\DeclareDocumentCommand{\areaset}{o m m}{}
\DeclareDocumentCommand{\activateareas}{}{}
\DeclareDocumentCommand{\storeareas}{m}{}
\DeclareDocumentCommand{\BeforeRestoreareas}{s m}{}
\DeclareDocumentCommand{\AfterRestoreareas}{s m}{}
\DeclareDocumentCommand{\AfterCalculatingTypearea}{s m}{}
\DeclareDocumentCommand{\AfterSettingArea}{s m}{}
```

File 526 **lwarp-typicons.sty**

§ 634 Package

typicons

(*Emulates or patches code by* Arthur Vigil, Xavier Danaux.)

Pkg typicons typicons is patched for use by lwarp.

If \ticon is used, the name of the icon is used in the alt tag. Otherwise, for each of the individual icon macros, a generic alt tag is used.

for HTML output:

```
\LWR@ProvidesPackagePass{typicons}[2015/05/20]

\LetLtxMacro\LWR@orig@symbol\symbol

\let\LWR@orig@typicon@TI\TI

\newcommand*{\LWR@typicon@symbol}[1]{%
    \begin{lateximage}*[typicon][typicon#1]%
    \begingroup%
    \LWR@orig@typicon@TI%
    \LWR@orig@symbol{#1}%
    \endgroup%
    \end{lateximage}%
}

\renewcommand*{\TI}{%
    \LetLtxMacro\symbol\LWR@typicon@symbol%
}

\renewcommand*{\ticon}[1]
{%
    \begin{lateximage}*[#1 icon][typicon#1]%
    \TI\csname ticon@#1\endcsname%
```

```
    \end{lateximage}%
}
```

File 527 **lwarp-ulem.sty**

§ 635 Package

ulem

(*Emulates or patches code by* Donald Arseneau.)

Pkg ulem Patched for use by lwarp.

for HTML output: Use the original package:

```
\LWR@ProvidesPackagePass{ulem}[2012/05/18]
```

Basic markup commands, using CSS:

```
\NewDocumentCommand{\LWR@HTML@uline}{+m}{%
    \InlineClass%
        (text-decoration:underline; text-decoration-skip: auto)%
        {uline}{\LWR@isolate{#1}}%
}
\LWR@formatted{uline}

\NewDocumentCommand{\LWR@HTML@uuline}{+m}{%
    \InlineClass%
        (%
            text-decoration:underline; text-decoration-skip: auto;%
            text-decoration-style:double%
        )%
        {uuline}{\LWR@isolate{#1}}%
}
\LWR@formatted{uuline}

\NewDocumentCommand{\LWR@HTML@uwave}{+m}{%
    \InlineClass%
        (%
            text-decoration:underline; text-decoration-skip: auto;%
            text-decoration-style:wavy%
        )%
        {uwave}{\LWR@isolate{#1}}%
}
\LWR@formatted{uwave}

\NewDocumentCommand{\LWR@HTML@sout}{+m}{%
    \InlineClass%
        (text-decoration:line-through)%
        {sout}{\LWR@isolate{#1}}%
}
\LWR@formatted{sout}

\NewDocumentCommand{\LWR@HTML@xout}{+m}{%
    \InlineClass%
```

```
        (text-decoration:line-through)%
        {xout}{\LWR@isolate{#1}}%
}
\LWR@formatted{xout}

\NewDocumentCommand{\LWR@HTML@dashuline}{+m}{%
    \InlineClass%
        (%
            text-decoration:underline;%
            text-decoration-skip: auto;%
            text-decoration-style:dashed%
        )%
        {dashuline}{\LWR@isolate{#1}}%
}
\LWR@formatted{dashuline}

\NewDocumentCommand{\LWR@HTML@dotuline}{+m}{%
    \InlineClass%
        (%
            text-decoration:underline;%
            text-decoration-skip: auto;%
            text-decoration-style: dotted%
        )%
        {dotuline}{\LWR@isolate{#1}}%
}
\LWR@formatted{dotuline}
```

Nullified/emulated macros:

```
\NewDocumentCommand{\LWR@HTML@markoverwith}{m}{}
\LWR@formatted{markoverwith}

\NewDocumentCommand{\LWR@HTML@ULon}{+m}{\uline{#1}\egroup}
\LWR@formatted{ULon}
```

File 528 **lwarp-umoline.sty**

§ 636 Package

umoline

(*Emulates or patches code by* Hiroshi Nakashima.)

Pkg umoline umoline is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{umoline}[2000/07/11]

\newcommand*{\LWR@HTML@Underline}[1]{%
    \InlineClass{uline}{#1}%
}
\LWR@formatted{Underline}

\newcommand*{\LWR@HTML@Midline}[1]{%
    \InlineClass{sout}{#1}%
}
```

```
\LWR@formatted{Midline}

\newcommand*{\LWR@HTML@Overline}[1]{%
    \InlineClass{oline}{#1}%
}
\LWR@formatted{Overline}

\newcommand*{\LWR@HTML@UMOline}[2]{%
    \InlineClass{uline}{#2}%
}
\LWR@formatted{UMOline}

\NewDocumentCommand{\LWR@HTML@UMOspace}{s m o}{\hspace*{#2}}
\LWR@formatted{UMOspace}

\NewDocumentCommand{\LWR@HTML@UMOnewline}{s}{\newline}
\LWR@formatted{UMOnewline}
```

File 529 **lwarp-underscore.sty**

§ 637 Package

underscore

Pkg underscore underscore is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{underscore}[2006/09/13]
```

File 530 **lwarp-unicode-math.sty**

§ 638 Package

unicode-math

(*Emulates or patches code by* Will Robertson.)

Pkg unicode-math unicode-math is supported as-is for HTML with SVGmath.

⚠ MathJax If the document source includes embedded Unicode characters, these may not be reproduced correctly for *pdftotext*, and thus not display correctly in MathJax.

Symbol font commands are emulated, but not all combinations are supported by MathJax, especially with the dedicated Greek macros. Symbol macros such as `\symbfsf` may not be sans or bold. For Greek, use the Unicode equivalent, if necessary.

⚠ `\mathversion` The MathJax emulation does not change with the use of `\mathversion`. Whatever emulation is established at the begin of the document will remain.

The option `sans-style` honors `upright` and `italic`, but `italic` will not be sans, in order to support Greek macros.

Greek macros such as `\alpha` respond to the `math-style` option. Latin symbols does not, per MathJax limitations, unless placed inside `\symbit` or similar.

Macros from the categories \mathopen, \mathclose, and \mathfence are emulated. Due to current MathJax limitations, not all stretch to the correct height.

Also emulated are macros from the categories \mathpunct, \mathover, \mathunder, \mathaccent, \mathbotaccent, and \mathop.

The individual unicode-math macros of categories \mathbin, \mathord, and \mathrel are not emulated for MathJax, as there are more than two thousand of them, but they may be added as needed. Place the following in the document preamble after loading unicode-math, including a definition for each macro which is used in the document but undefined in MathJax:

```
\begin{warpMathJax}
\CustomizeMathJax{\newcommand{\uplus}{\mathbin{\unicode{x0228E}}}}
...
\end{warpMathJax}
```

Use \mathrel, \mathbin, etc. depending on the category of each macro. For a list of macro names and symbols, see **texdoc unimath-symbols**.

for HTML output:

```
\LWR@ProvidesPackagePass{unicode-math}[2019/09/26]

\LWR@origRequirePackage{lwarp-common-mathjax-letters}

\begin{warpMathJax}
\LWR@infoprocessingmathjax{unicode-math}

% Not all are possible in MathJax.
\CustomizeMathJax{\let\symnormal\mathit}
\CustomizeMathJax{\let\symliteral\mathrm}
\CustomizeMathJax{\let\symbb\mathbb}
\CustomizeMathJax{\let\symbbit\mathbb}% not italic
\CustomizeMathJax{\let\symcal\mathcal}
\CustomizeMathJax{\let\symscr\mathscr}
\CustomizeMathJax{\let\symfrak\mathfrak}

\CustomizeMathJax{\let\symsfup\mathsf}

\CustomizeMathJax{\let\symsfit\mathit}% not sans
% \CustomizeMathJax{\newcommand{\symsfit}[1]{%
%     \mmlToken{mi}[mathvariant="sans-serif-italic"]{#1}}% not greek
% }

\CustomizeMathJax{\let\symbfsf\mathbf}% not sans
% \CustomizeMathJax{\newcommand{\symbfsf}[1]{%
%     \mmlToken{mi}[mathvariant="bold-sans-serif"]{#1}}% not greek
% }

\CustomizeMathJax{\let\symbfup\mathbf}
\CustomizeMathJax{\newcommand{\symbfit}[1]{\boldsymbol{#1}}}
\CustomizeMathJax{\let\symbfcal\mathcal}% not bold

\CustomizeMathJax{\let\symbfscr\mathscr}% not bold
% \CustomizeMathJax{\newcommand{\symbfscr}[1]{
```

```
%     \mmlToken{mi}[mathvariant="math-bold-script"]{#1}}% not greek
% }

\CustomizeMathJax{\let\symbffrak\mathfrak}% not bold
% \CustomizeMathJax{\newcommand{\symbffrak}[1]{%
%     \mmlToken{mi}[mathvariant="math-bold-fraktur"]{#1}}% not greek
% }

\CustomizeMathJax{\let\symbfsfup\mathbf}% not sans
% \CustomizeMathJax{\newcommand{\symbfsfup}[1]{%
%     \mmlToken{mi}[mathvariant="bold-sans-serif"]{#1}}% not greek
% }

\CustomizeMathJax{\newcommand{\symbfsfit}[1]{\boldsymbol{#1}}}% not sans
% \CustomizeMathJax{\newcommand{\symbfsfit}[1]{%
%     \mmlToken{mi}[mathvariant="sans-serif-bold-italic"]{#1}}% not greek
% }

% Duplicates below are commented out.
\CustomizeMathJax{\let\symup\mathrm}
\CustomizeMathJax{\let\symbf\mathbf}% \symbfup defined above
\CustomizeMathJax{\let\symit\mathit}
% \CustomizeMathJax{\let\symbfit\mathit}% not bold


\ExplSyntaxOn
\AtBeginDocument{
\bool_if:NTF \g__um_sfliteral_bool
    {\CustomizeMathJax{\let\symsf\symsfup}}
    {
        \bool_if:NTF \g__um_upsans_bool
            {\CustomizeMathJax{\let\symsf\symsfup}}
            {\CustomizeMathJax{\let\symsf\symsfit}}
    }
}
\ExplSyntaxOff

% \CustomizeMathJax{\let\symbfsfup\mathbf}% not sans
% \CustomizeMathJax{\let\symsfit\mathit}% not sans
% \CustomizeMathJax{\let\symbfsfit\mathit}% not bold nor sans
\CustomizeMathJax{\let\symtt\mathtt}
% \CustomizeMathJax{\let\symbb\mathbb}
% \CustomizeMathJax{\let\symbbit\mathbb}% not italic
% \CustomizeMathJax{\let\symscr\mathscr}
% \CustomizeMathJax{\let\symbfscr\mathscr}% not bold
% \CustomizeMathJax{\let\symfrak\mathfrak}
\CustomizeMathJax{\let\symbffrac\mathbffrac}
```

Some symbol categories defined by unicode-math, in case they are used inside custom macros:

```
\CustomizeMathJax{\newcommand{\mathfence}[1]{\mathord{#1}}}
\CustomizeMathJax{\newcommand{\mathover}[1]{#1}}
\CustomizeMathJax{\newcommand{\mathunder}[1]{#1}}
\CustomizeMathJax{\newcommand{\mathaccent}[1]{#1}}
\CustomizeMathJax{\newcommand{\mathbotaccent}[1]{#1}}
```

```
\CustomizeMathJax{\newcommand{\mathalpha}[1]{\mathord{#1}}}
```

`math-style` is one of: `ISO`, `TeX`, `french`, `upright`, or `literal`, which set `\g__um_upGreek_bool` and `\g__um_upgreek_bool`.

```
\ExplSyntaxOn

\AtBeginDocument{
\bool_if:NTF \g__um_upGreek_bool
    {\LWR@mathjax@addgreek@u@up*{}{}}
    {\LWR@mathjax@addgreek@u@it*{}{}}

\bool_if:NTF \g__um_upgreek_bool
    {\LWR@mathjax@addgreek@l@up{}{}}
    {\LWR@mathjax@addgreek@l@it{}{}}
}

\LWR@mathjax@addgreek@u@up*{up}{}
\LWR@mathjax@addgreek@u@it*{it}{}
\LWR@mathjax@addgreek@l@up{up}{}
\LWR@mathjax@addgreek@l@it{it}{}

\ExplSyntaxOff

\CustomizeMathJax{\let\lparen(}
\CustomizeMathJax{\let\rparen)}
\CustomizeMathJax{\newcommand{\cuberoot}[1]{\,{}^3\!\!\sqrt{#1}}\,}
\CustomizeMathJax{\newcommand{\fourthroot}[1]{\,{}^4\!\!\sqrt{#1}}\,}
```

Many `\mathopen`/`\mathclose` delimiters are defined in `lwarp_mathjax.txt`, where `\left`/`\right` support is added.

```
\CustomizeMathJax{\newcommand{\longdivision}[1]{\mathord{\unicode{x027CC}#1}}}

\CustomizeMathJax{\newcommand{\mathcomma}{,}}
\CustomizeMathJax{\newcommand{\mathcolon}{:}}
\CustomizeMathJax{\newcommand{\mathsemicolon}{;}}

\CustomizeMathJax{\newcommand{\overbracket}[1]{\mathinner{\overline{\ulcorner{#1}\urcorner}}}}
\CustomizeMathJax{\newcommand{\underbracket}[1]{\mathinner{\underline{\llcorner{#1}\lrcorner}}}}

\CustomizeMathJax{\newcommand{\overbar}[1]{\mathord{#1\unicode{x00305}}}}
\CustomizeMathJax{\newcommand{\ovhook}[1]{\mathord{#1\unicode{x00309}}}}
\CustomizeMathJax{\newcommand{\ocirc}[1]{\mathord{#1\unicode{x0030A}}}}
\CustomizeMathJax{\newcommand{\candra}[1]{\mathord{#1\unicode{x00310}}}}
\CustomizeMathJax{\newcommand{\oturnedcomma}[1]{\mathord{#1\unicode{x00312}}}}
\CustomizeMathJax{\newcommand{\ocommatopright}[1]{\mathord{#1\unicode{x00315}}}}
\CustomizeMathJax{\newcommand{\droang}[1]{\mathord{#1\unicode{x0031A}}}}
\CustomizeMathJax{\newcommand{\leftharpoonaccent}[1]{\mathord{#1\unicode{x020D0}}}}
\CustomizeMathJax{\newcommand{\rightharpoonaccent}[1]{\mathord{#1\unicode{x020D1}}}}
\CustomizeMathJax{\newcommand{\vertoverlay}[1]{\mathord{#1\unicode{x020D2}}}}
\CustomizeMathJax{\newcommand{\leftarrowaccent}[1]{\mathord{#1\unicode{x020D0}}}}
\CustomizeMathJax{\newcommand{\annuity}[1]{\mathord{#1\unicode{x020E7}}}}
\CustomizeMathJax{\newcommand{\widebridgeabove}[1]{\mathord{#1\unicode{x020E9}}}}
\CustomizeMathJax{\newcommand{\asteraccent}[1]{\mathord{#1\unicode{x020F0}}}}
```

```
\CustomizeMathJax{\newcommand{\threeunderdot}[1]{\mathord{#1\unicode{x020E8}}}}

\CustomizeMathJax{\newcommand{\Bbbsum}{\mathop{\unicode{x2140}}\limits}}
\CustomizeMathJax{\newcommand{\oiint}{\mathop{\unicode{x222F}}\limits}}
\CustomizeMathJax{\newcommand{\oiiint}{\mathop{\unicode{x2230}}\limits}}
\CustomizeMathJax{\newcommand{\intclockwise}{\mathop{\unicode{x2231}}\limits}}
\CustomizeMathJax{\newcommand{\ointclockwise}{\mathop{\unicode{x2232}}\limits}}
\CustomizeMathJax{\newcommand{\ointctrclockwise}{\mathop{\unicode{x2233}}\limits}}
\CustomizeMathJax{\newcommand{\varointclockwise}{\mathop{\unicode{x2232}}\limits}}
\CustomizeMathJax{\newcommand{\leftouterjoin}{\mathop{\unicode{x27D5}}\limits}}
\CustomizeMathJax{\newcommand{\rightouterjoin}{\mathop{\unicode{x27D6}}\limits}}
\CustomizeMathJax{\newcommand{\fullouterjoin}{\mathop{\unicode{x27D7}}\limits}}
\CustomizeMathJax{\newcommand{\bigbot}{\mathop{\unicode{x27D8}}\limits}}
\CustomizeMathJax{\newcommand{\bigtop}{\mathop{\unicode{x27D9}}\limits}}
\CustomizeMathJax{\newcommand{\xsol}{\mathop{\unicode{x29F8}}\limits}}
\CustomizeMathJax{\newcommand{\xbsol}{\mathop{\unicode{x29F9}}\limits}}
\CustomizeMathJax{\newcommand{\bigcupdot}{\mathop{\unicode{x2A03}}\limits}}
\CustomizeMathJax{\newcommand{\bigsqcap}{\mathop{\unicode{x2A05}}\limits}}
\CustomizeMathJax{\newcommand{\conjquant}{\mathop{\unicode{x2A07}}\limits}}
\CustomizeMathJax{\newcommand{\disjquant}{\mathop{\unicode{x2A08}}\limits}}
\CustomizeMathJax{\newcommand{\bigtimes}{\mathop{\unicode{x2A09}}\limits}}
\CustomizeMathJax{\newcommand{\modtwosum}{\mathop{\unicode{x2A0A}}\limits}}
\CustomizeMathJax{\newcommand{\sumint}{\mathop{\unicode{x2A0B}}\limits}}
\CustomizeMathJax{\newcommand{\intbar}{\mathop{\unicode{x2A0D}}\limits}}
\CustomizeMathJax{\newcommand{\intBar}{\mathop{\unicode{x2A0E}}\limits}}
\CustomizeMathJax{\newcommand{\fint}{\mathop{\unicode{x2A0F}}\limits}}
\CustomizeMathJax{\newcommand{\cirfnint}{\mathop{\unicode{x2A10}}\limits}}
\CustomizeMathJax{\newcommand{\awint}{\mathop{\unicode{x2A11}}\limits}}
\CustomizeMathJax{\newcommand{\rppolint}{\mathop{\unicode{x2A12}}\limits}}
\CustomizeMathJax{\newcommand{\scpolint}{\mathop{\unicode{x2A13}}\limits}}
\CustomizeMathJax{\newcommand{\npolint}{\mathop{\unicode{x2A14}}\limits}}
\CustomizeMathJax{\newcommand{\pointint}{\mathop{\unicode{x2A15}}\limits}}
\CustomizeMathJax{\newcommand{\sqint}{\mathop{\unicode{x2A16}}\limits}}
\CustomizeMathJax{\newcommand{\intlarhk}{\mathop{\unicode{x2A17}}\limits}}
\CustomizeMathJax{\newcommand{\intx}{\mathop{\unicode{x2A18}}\limits}}
\CustomizeMathJax{\newcommand{\intcap}{\mathop{\unicode{x2A19}}\limits}}
\CustomizeMathJax{\newcommand{\intcup}{\mathop{\unicode{x2A1A}}\limits}}
\CustomizeMathJax{\newcommand{\upint}{\mathop{\unicode{x2A1B}}\limits}}
\CustomizeMathJax{\newcommand{\lowint}{\mathop{\unicode{x2A1C}}\limits}}
\CustomizeMathJax{\newcommand{\bigtriangleleft}{\mathop{\unicode{x2A1E}}\limits}}
\CustomizeMathJax{\newcommand{\zcmp}{\mathop{\unicode{x2A1F}}\limits}}
\CustomizeMathJax{\newcommand{\zpipe}{\mathop{\unicode{x2A20}}\limits}}
\CustomizeMathJax{\newcommand{\zproject}{\mathop{\unicode{x2A21}}\limits}}
\CustomizeMathJax{\newcommand{\biginterleave}{\mathop{\unicode{x2AFC}}\limits}}
\CustomizeMathJax{\newcommand{\bigtalloblong}{\mathop{\unicode{x2AFF}}\limits}}
\CustomizeMathJax{\newcommand{\arabicmaj}{\mathop{\unicode{x1EEF0}}\limits}}
\CustomizeMathJax{\newcommand{\arabichad}{\mathop{\unicode{x1EEF1}}\limits}}

\end{warpMathJax}
```

File 531 **lwarp-units.sty**

§ 639 Package units

(*Emulates or patches code by* Axel Reichert.)

Pkg units units is patched for use by lwarp.

Values are not styled by CSS, and take the style of the surrounding HTML text.

Units are styled according to the print version, so they will be forced to upright roman in HTML if the print version does so. It may be necessary to adjust the document's body CSS to match the print version.

for HTML output:

```
\LWR@ProvidesPackagePass{units}[1998/08/04]

\DeclareRobustCommand*{\LWR@HTML@unit}[2][]{%
\ifblank{#1}%
    {\LWR@textcurrentfont{#2}}%
    {%
        #1%
        \ifthenelse{\boolean{B@UnitsLoose}}{~}{\,}%
        \LWR@textcurrentfont{#2}%
    }%
}
\LWR@formatted{unit}

\DeclareRobustCommand*{\LWR@HTML@unitfrac}[3][]{%
\ifblank{#1}%
    {%
            \nicefrac{#2}{#3}%
    }%
    {%
            #1%
            \ifthenelse{\boolean{B@UnitsLoose}}{~}{\,}%
            \nicefrac{#2}{#3}%
    }%
}

\LWR@formatted{unitfrac}
```

For MathJax:

```
\begin{warpMathJax}
\CustomizeMathJax{\newcommand{\unit}[2][]{#1 \mathinner{#2}}}
\CustomizeMathJax{\newcommand{\unitfrac}[3][]{#1 \mathinner{{}^{#2}\!/\!_{#3}}}}
\end{warpMathJax}
```

File 532 **lwarp-unitsdef.sty**

§ 640 Package unitsdef

(*Emulates or patches code by* Patrick Happel.)

Pkg unitsdef unitsdef is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{unitsdef}[2005/01/04]

\renewcommand{\unitvaluesep}{\,}

\renewcommand{\unittimes}{\@@setunitsepfalse\HTMLunicode{22c5}}% \cdot

\renewunit{\arcmin}{%
    \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
        {\ensuremath{{}^\prime}}%
        {\HTMLunicode{2032}}% prime
}

\renewunit{\arcsec}{%
    \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
        {\ensuremath{{}^{\prime\prime}}}%
        {\HTMLunicode{2033}}% dbl prime
}

\renewrobustcmd{\SI}[2]{%
  \begingroup%
    \let\unit@@xspace\relax%
    \unitSIdef\selectfont%
      \LWR@textcurrentfont{#1#2}% lwarp
  \endgroup%
}
```

File 533 **lwarp-upgreek.sty**

§ 641 Package upgreek

(*Emulates or patches code by* Walter Schmidt.)

Pkg upgreek upgreek is used as-is for SVG math, and is emulated for MathJax.

for HTML output:

```
\LWR@ProvidesPackagePass{upgreek}[2003/02/12]
```

For MathJax:

```
\LWR@origRequirePackage{lwarp-common-mathjax-letters}

\begin{warpMathJax}
\LWR@infoprocessingmathjax{upgreek}

\LWR@mathjax@addgreek@l@up{up}{}
\LWR@mathjax@addgreek@u@up{Up}{}

\end{warpMathJax}
```

File 534 **lwarp-upref.sty**

§ 642 Package upref

Pkg upref upref is ignored.

for HTML output: Discard all options for lwarp-upref:

```
\LWR@ProvidesPackageDrop{upref}[2007/03/14]
```

File 535 **lwarp-url.sty**

§ 643 Package url

(*Emulates or patches code by* Donald Arseneau.)

Pkg url url is patched for use by lwarp.

for HTML output:

```
\LetLtxMacro\LWR@url@orig@url\LWR@url

\LWR@ProvidesPackagePass{url}[2013/09/16]

\newcommand*{\LWR@HTML@Url@FormatString}{%
    \expandafter\LWR@url@orig@url\expandafter{\Url@String}%
}
\LWR@formatted{Url@FormatString}
```

File 536 **lwarp-ushort.sty**

§ 644 Package ushort

(*Emulates or patches code by* Martin Väth.)

Pkg ushort ushort is used as-is, and emulated for MathJax.

for HTML output:

```
\LWR@ProvidesPackagePass{ushort}[2001/06/13]

\begin{warpMathJax}
\CustomizeMathJax{\newcommand{\ushortdline}[1]{%
    \kern{.1em}\underline{\underline{{#1}}}\kern{.1em}%
}}
\CustomizeMathJax{\newcommand{\ushort}[1]{\kern{.1em}\underline{#1}\kern{.1em}}}
\CustomizeMathJax{\newcommand{\ushortd}[1]{\ushortdline{#1}}}
\CustomizeMathJax{\newcommand{\ushortw}[1]{\kern{.1em}\underline{#1}\kern{.1em}}}
\CustomizeMathJax{\newcommand{\ushortdw}[1]{\ushortdline{#1}}}
\end{warpMathJax}
```

File 537 **lwarp-uspace.sty**

§ 645 Package uspace

Pkg uspace uspace is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{uspace}[2016/11/06]
```

File 538 **lwarp-varioref.sty**

§ 646 Package varioref

(*Emulates or patches code by* Frank Mittelbach.)

Pkg varioref varioref is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{varioref}[2020/01/23]
```

Page-related output is not used for HTML output.

```
\def\reftextfaceafter {\unskip}%
\def\reftextfacebefore{\unskip}%
\def\reftextafter     {\unskip}%
\def\reftextbefore    {\unskip}%
\def\reftextcurrent   {\unskip}%
\def\reftextfaraway#1{\unskip}%
\def\reftextpagerange#1#2{\unskip}%
```

File 539 **lwarp-verse.sty**

§ 647 Package verse

(*Emulates or patches code by* Peter Wilson.)

Pkg verse verse is supported and patched by lwarp.

for HTML output: Pass all options for lwarp-verse:

```
\LWR@ProvidesPackagePass{verse}[2009/09/04]
```

When using verse or memoir, always place a \\ after each line.

\attrib The documentation for the verse and memoir packages suggest defining an \attrib command, which may already exist in current documents, but it will only work for print output. lwarp provides \attribution, which works for both print and HTML output. To combine the two so that \attrib is used for print and \attribution is used for HTML:

```
\begin{warpHTML}
\let\attrib\attribution
\end{warpHTML}
```

Len \vleftskip
Len \vleftmargini These lengths are used by verse and memoir to control the left margin, and they

Len \HTMLvleftskip
Len \HTMLleftmargini

may already be set by the user for print output. New lengths \HTMLvleftskip and \HTMLleftmargini are provided to control the margins in HTML output. These new lengths may be set by the user before any verse environment, and persist until they are manually changed again. One reason to change \HTMLleftmargini is if there is a wide \flagverse in use, such as the word "Chorus", in which case the value of \HTMLleftmargini should be set to a wide enough length to contain "Chorus". The default is wide enough for a stanza number.

⚠ spacing

Horizontal spacing relies on *pdftotext*'s ability to discern the layout (-layout option) of the text in the HTML-tagged PDF output. For some settings of \HTMLleftmargini or \HTMLleftskip the horizontal alignment may not work out exactly, in which case a label may be shifted by one space. During translation to HTML, the stanza numbers are kept out of the left margin, which would have caused *pdftotext* to shift everything over.

⚠ verse margin

Env verse

The verse environment will be placed inside a HTML <pre>.

```
\AfterEndPreamble{
\LWR@traceinfo{Patching verse.}
```

At the beginning of the verse environment:

```
\AtBeginEnvironment{verse}
{%
```

Use the original list environment inside a <pre> to attempt to preserve formatting.

```
\LWR@restoreoriglists%
```

Pkg verse
Cls memoir
\flagverse
Len \vleftskip

The verse or memoir packages can place stanza numbers to the left with their \flagverse command. The following does not allow them to go into the left margin, which would cause *pdfcrop* to crop the entire page further to the left.

```
\ifdef{\vleftskip}{%
\setlength{\vleftskip}{\HTMLvleftskip}
\setlength{\leftmargini}{\HTMLleftmargini}
}{}
\LWR@forcenewpage
\LWR@atbeginverbatim{verse}%
}
```

After the end of the verse environment, which places the <pre> tag at the regular left margin:

```
\AtEndEnvironment{verse}{%
\leavevmode%
\LWR@afterendverbatim%
}
```

Patch to place poemtitle inside an HTML of class poemtitle:

```
\ifdef{\poemtitle}{
\DeclareDocumentCommand{\@vstypeptitle}{m}{%
```

```
  \vspace{\beforepoemtitleskip}%
  {\InlineClass{poemtitle}{\poemtitlefont #1}\par}%
  \vspace{\afterpoemtitleskip}%
 }
}{}

\LWR@traceinfo{Finished patching verse.}
}% AfterEndPreamble
```

File 540 **lwarp-versonotes.sty**

§ 648 Package versonotes

(*Emulates or patches code by* Norman Gray.)

Pkg versonotes versonotes is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{versonotes}[2019/07/06]

\newcommand{\versonote}[1]{\marginpar{#1}}
\newdimen\versotextwidth
\newdimen\versoleftmargin
\newcommand*{\versolayout}{}
```

In case the user changed the page number before loading versonotes:

```
\setcounter{page}{1}
```

File 541 **lwarp-vertbars.sty**

§ 649 Package vertbars

(*Emulates or patches code by* Peter Wilson.)

Pkg vertbars vertbars is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{vertbars}[2010/11/27]

\newlength{\barwidth}
\setlength{\barwidth}{0.4pt}
\newlength{\barspace}
\setlength{\barspace}{1em}

\newenvironment{vertbar}{
    \LWR@forcenewpage
    \LWR@forceminwidth{\barwidth}
    \begin{BlockClass}[%
        border-left: \LWR@printlength{\LWR@atleastonept} solid black ; %
        padding-left: \LWR@printlength{\barspace}%
    ]{vertbar}
```

```
}{
    \end{BlockClass}
}
```

File 542 **lwarp-vmargin.sty**

§ 650 Package vmargin

Pkg vmargin vmargin is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{vmargin}[2004/07/15]

\newcommand*{\LWRVM@customsize}[2]{}
\newcommand*{\setpapersize}[2][]{\ifstrequal{#2}{custom}{\LWRVM@customsize}{}}
\newcommand*{\setmargins}[8]{}
\newcommand*{\setmarginsrb}[8]{}
\newcommand*{\setmargnohf}[4]{}
\newcommand*{\setmargnohfrb}[4]{}
\newcommand*{\setmarg}[4]{}
\newcommand*{\setmargrb}[4]{}
\newlength{\PaperWidth}
\setlength{\PaperWidth}{8.5in}
\newlength{\PaperHeight}
\setlength{\PaperHeight}{11in}
\newif\ifLandscape
```

File 543 **lwarp-vowel.sty**

§ 651 Package vowel

(*Emulates or patches code by* FUKUI Rei.)

Pkg vowel vowel is patched for use by lwarp.

This package has been tested with *pdflatex* and the Type 1 TIPA fonts using the following package load sequence:

```
\usepackage[T3,T1]{fontenc}
\usepackage[utf8]{inputenc}
\usepackage[noenc]{tipa}
\usepackage{vowel}
```

for HTML output:

```
\LWR@ProvidesPackagePass{vowel}[2002/08/08]

\renewenvironment{vowel}[1][]
    {%
        \begin{lateximage}[-vowel-~\PackageDiagramAltText]%
        \@vowel[#1]%
    }
    {%
```

```
        \@@vowel%
        \end{lateximage}%
    }
```

File 544 **lwarp-vpe.sty**

§ 652 Package

vpe

Pkg vpe vpe is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{vpe}[2012/04/18]
```

File 545 **lwarp-vwcol.sty**

§ 653 Package

vwcol

(*Emulates or patches code by* Will Robertson.)

Pkg vwcol vwcol is patched for use with lwarp.

The `width` option is ignored. All `vwcol` environments adjust to 1–3 equal-width columns, depening on the width of the browser window.

The remaining options are supported, except for `lines` and `maxrecursion`.

for HTML output:

```
\LWR@ProvidesPackagePass{vwcol}[2015/02/10]
```

Factored from `\vwcol`. Each is given a style tag to append to the final style.

`\LWR@vwcol@addrule` {⟨*style tag*⟩}

```
\newcommand*{\LWR@vwcol@addrule}[1]{%
    \appto{\LWR@vwcolstyle}{%
        #1: %
     \LWR@printlength{\vwcol@rule} solid \LWR@origpound\LWR@vwcol@rulecolor ; %
    }%
}
```

`\LWR@vwcol@addrule` {⟨*style tag*⟩}

```
\newcommand*{\LWR@vwcol@addgap}[1]{%
    \appto{\LWR@vwcolstyle}{%
        #1: %
        \LWR@printlength{\vwcol@sep} ; %
    }%
}
```

Env vwcol {⟨*key/values*⟩}

Redefine the environment to add a HTML style. The style is built depending on the required options.

```
\renewenvironment*{vwcol}[1][]{%
```

New paragraph, and process the options:

```
\LWR@stoppars%
\vwcolsetup{#1}%
```

Begin with no style:

```
\newcommand*{\LWR@vwcolstyle}{}
```

presep and postsep are created with HTML margins:

```
\if@vwcol@presep
    \appto{\LWR@vwcolstyle}{margin-left: 1em ; padding-left: .5em ; }
\fi
\if@vwcol@postsep
    \appto{\LWR@vwcolstyle}{margin-right: 1em ; padding-right: .5em ; }
\fi
```

sep becomes column-gap:

```
\ifdimgreater{\vwcol@sep}{1sp}{
    \LWR@vwcol@addgap{column-gap}
    \LWR@vwcol@addgap{-moz-column-gap}
    \LWR@vwcol@addgap{-webkit-column-gap}
}{}
```

rule become column-rule, while prerule and postrule become HTML borders:

```
\convertcolorspec{named}{\vwcol@rulecol}{HTML}\LWR@vwcol@rulecolor%
\ifdimgreater{\vwcol@rule}{0pt}{
    \ifdimless{\vwcol@rule}{1pt}{
        \setlength{\vwcol@rule}{1pt}
    }{}
    \LWR@vwcol@addrule{column-rule}
    \LWR@vwcol@addrule{-moz-column-rule}
    \LWR@vwcol@addrule{-webkit-column-rule}
    \if@vwcol@prerule\LWR@vwcol@addrule{border-left}\fi
    \if@vwcol@postrule\LWR@vwcol@addrule{border-right}\fi
}{}
```

Each of the justify options becomes a text-align. Indentation is added where appropriate.

```
\ifdefequal{\vwcol@justify}{\RaggedRight}{
    \appto{\LWR@vwcolstyle}{text-align: left ; }
    \ifdimgreater{\vwcol@parindent}{0pt}{
        \appto{\LWR@vwcolstyle}{%
            text-indent: \LWR@printlength{\vwcol@parindent} ; %
        }
    }{}
}{}
```

```
\ifdefequal{\vwcol@justify}{\RaggedLeft}{
    \appto{\LWR@vwcolstyle}{text-align: right ; }
}{}
```

```
\ifdefequal{\vwcol@justify}{\Centering}{
    \appto{\LWR@vwcolstyle}{text-align: center ; }
```

```
}{}
\ifdefequal{\vwcol@justify}{\justifying}{
    \appto{\LWR@vwcolstyle}{text-align: justify ; }
    \ifdimgreater{\vwcol@parindent}{0pt}{
        \appto{\LWR@vwcolstyle}{%
            text-indent: \LWR@printlength{\vwcol@parindent} ; %
        }
    }{}
}{}
```

Create the with the assembled style:

```
\BlockClass[\LWR@vwcolstyle]{multicols}
}
```

When the environment ends:

```
{
\endBlockClass
\LWR@startpars
}
```

File 546 **lwarp-wallpaper.sty**

§ 654 Package

wallpaper

(*Emulates or patches code by* Michael H.F. Wilkinson.)

Pkg wallpaper wallpaper is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{wallpaper}[2005/01/18]

\newcommand*{\CenterWallPaper}[2]{}
\newcommand*{\ThisCenterWallPaper}[2]{}
\newcommand*{\TileWallPaper}[3]{}
\newcommand*{\ThisTileWallPaper}[3]{}
\newcommand*{\TileSquareWallPaper}[2]{}
\newcommand*{\ThisTileSquareWallPaper}[2]{}
\newcommand*{\ULCornerWallPaper}[2]{}
\newcommand*{\ThisULCornerWallPaper}[2]{}
\newcommand*{\LLCornerWallPaper}[2]{}
\newcommand*{\ThisLLCornerWallPaper}[2]{}
\newcommand*{\URCornerWallPaper}[2]{}
\newcommand*{\ThisURCornerWallPaper}[2]{}
\newcommand*{\LRCornerWallPaper}[2]{}
\newcommand*{\ThisLRCornerWallPaper}[2]{}
\newcommand*{\ClearWallPaper}{}
\newlength{\wpXoffset}
\newlength{\wpYoffset}
```

File 547 **lwarp-watermark.sty**

§ 655 Package watermark

(*Emulates or patches code by* Alexander I. Rozhenko.)

Pkg watermark watermark is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{watermark}[2004/12/09]

\newcommand{\watermark}[1]{}
\newcommand{\leftwatermark}[1]{}
\newcommand{\rightwatermark}[1]{}
\newcommand{\thiswatermark}[1]{}
\newcommand{\thispageheading}[1]{}
```

File 548 **lwarp-widetable.sty**

§ 656 Package widetable

(*Emulates or patches code by* Claudio Beccari.)

Pkg widetable widetable is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{widetable}[2019-06-25]

\newenvironment{widetable}{\begin{tabular*}}{\end{tabular*}}
```

File 549 **lwarp-widows-and-orphans.sty**

§ 657 Package widows-and-orphans

Pkg widows-and-orphans widows-and-orphans is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{widows-and-orphans}[2018/09/01]

\NewDocumentCommand\WaOsetup{m}{}
\NewDocumentCommand\WaOparameters{}{}
\NewDocumentCommand\WaOignorenext{}{}
```

File 550 **lwarp-witharrows.sty**

§ 658 Package witharrows

(*Emulates or patches code by* F. Pantigny.)

Pkg witharrows witharrows is patched for use by lwarp. Emulation is provided for MathJax.

for HTML output:

```
\LWR@ProvidesPackagePass{witharrows}[2019/12/27]
```

```
\ifbool{mathjax}{
    % For the hidden print version in the HTML:
    \newcommand{\Arrow}[2][]{}
    \newcommand{\unicode}[1]{}
    \NewDocumentEnvironment { DispWithArrows } { ! d < > ! O { } +b}
        {
            \IfValueTF{#1}{
                \begin{displaymath}
                #1 \left\lbrace
                \begin{align}
                #3
                \end{align}
                \right .
                \end{displaymath}
            }{
                \begin{displaymath}
                \begin{align}
                #3
                \end{align}
                \end{displaymath}
            }
        }
        {}
    \NewDocumentEnvironment { DispWithArrows* } { ! d < > ! O { } +b}
        {
            \IfValueTF{#1}{
                \begin{displaymath}
                #1 \left\lbrace
                \begin{align*}
                #3
                \end{align*}
                \right .
                \end{displaymath}
            }{
                \begin{displaymath}
                \begin{align*}
                #3
                \end{align*}
                \end{displaymath}
            }
        }
        {}
}{
    % If not MathJax, use SVG images.
    \BeforeBeginEnvironment{WithArrows}{\global\booltrue{LWR@unknownmathsize}}
    \BeforeBeginEnvironment{DispWithArrows}{%
        \begin{BlockClass}{displaymathnumbered}%
        \begin{lateximage}%
    }
    \AfterEndEnvironment{DispWithArrows}{\end{lateximage}\end{BlockClass}}
    \BeforeBeginEnvironment{DispWithArrows*}{%
        \begin{BlockClass}{displaymath}%
        \begin{lateximage}%
    }
    \AfterEndEnvironment{DispWithArrows*}{\end{lateximage}\end{BlockClass}}
```

```
}

\begin{warpMathJax}
\CustomizeMathJax{\newenvironment{WithArrows}[1][]{\begin{aligned}}{\end{aligned}}}
% Unable to make a sized box.
\CustomizeMathJax{\newcommand{\Arrow}[2][]{&{\Large\unicode{x2938}}~\textit{#2}}}
\end{warpMathJax}
```

File 551 **lwarp-wrapfig.sty**

§ 659 Package

wrapfig

(*Emulates or patches code by* Donald Arseneau.)

Pkg wrapfig wrapfig is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{wrapfig}[2003/01/31]

\newcommand*{\LWR@wrapposition}{}

\newcommand{\LWR@wrapfig@printHTMLwidth}{width:\LWR@printlength{\LWR@templengthone}}

\AtBeginDocument{
    \@ifpackageloaded{keyfloat}{
        \renewcommand{\LWR@wrapfig@printHTMLwidth}{%
            \ifboolexpr{
                test {\ifnumgreater{\value{KFLT@keyfloatdepth}}{0}} or
                bool {KFLT@inkeysubfloats}
            }%
                {\LWR@printpercentlength{\LWR@templengthone}{\linewidth}\%; }%
                {\LWR@printlength{\LWR@templengthone}}%
        }%
    }{}
}

\newcommand*{\LWR@subwrapfigure}[2]{%
    \renewcommand*{\LWR@wrapposition}{}%
    \ifthenelse{%
        \equal{#1}{r}\OR\equal{#1}{R}\OR%
        \equal{#1}{o}\OR\equal{#1}{O}%
    }%
        {\renewcommand*{\LWR@wrapposition}{float:right}}%
        {\renewcommand*{\LWR@wrapposition}{float:left}}%
    \setlength{\LWR@templengthone}{#2}%
    \LWR@BlockClassWP{%
        width:\LWR@printlength{\LWR@templengthone}; \LWR@wrapposition; %
        margin:10pt%
    }%
    {%
        width:\LWR@wrapfig@printHTMLwidth; %
        \LWR@wrapposition; %
    }%
    (note)%
```

```
    {marginblock}%

    \setlength{\linewidth}{\LWR@templengthone}%
}


\NewDocumentEnvironment{wrapfigure}{o m o m}
{%
    \begin{LWR@setvirtualpage}*%
    \LWR@subwrapfigure{#2}{#4}%
    \renewcommand*{\@captype}{figure}%
}
{%
    \endLWR@BlockClassWP%
    \end{LWR@setvirtualpage}%
}


\NewDocumentEnvironment{wraptable}{o m o m}
{%
    \begin{LWR@setvirtualpage}*%
    \LWR@subwrapfigure{#2}{#4}%
    \renewcommand*{\@captype}{table}%
}
{%
    \endLWR@BlockClassWP%
    \end{LWR@setvirtualpage}%
}


\NewDocumentEnvironment{wrapfloat}{m o m o m}
{%
    \begin{LWR@setvirtualpage}*%
    \LWR@subwrapfigure{#3}{#5}%
    \renewcommand*{\@captype}{#1}%
}
{%
    \endLWR@BlockClassWP%
    \end{LWR@setvirtualpage}%
}

\newlength{\wrapoverhang}
```

File 552 **lwarp-xbmks.sty**

§ 660 Package

xbmks

Pkg xbmks xbmks is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{xbmks}[2018/07/04]

\newcommand{\xbmksetup}[1]{}
```

```
\NewDocumentCommand{\pdfbookmarkx}{o m o m}{}
\NewDocumentCommand{\currentpdfbookmarkx}{m o m}{}
\NewDocumentCommand{\subpdfbookmarkx}{m o m}{}
\NewDocumentCommand{\belowpdfbookmarkx}{m o m}{}
```

File 553 **lwarp-xcolor.sty**

§ 661 Package

xcolor

(*Emulates or patches code by* Dr. Uwe Kern.)

Pkg xcolor xcolor is supported by lwarp.

§ 661.1 Limitations

\colorboxBlock and \fcolorboxBlock

\colorboxBlock and \fcolorboxBlock are provided for increased HTML compatibility, and they are identical to \colorbox and \fcolorbox in print mode. In HTML mode they place their contents into a instead of a . These s are set to display: inline-block so adjacent \colorboxBlocks appear side-by-side in HTML, although text is placed before or after each.

Print-mode definitions for \colorboxBlock and \fcolorboxBlock are created by lwarp's core if xcolor is loaded.

background: none

\fcolorbox and \fcolorboxBlock allow a background color of none, in which case only the frame is drawn, which can be useful for HTML.

color support

Color definitions, models, and mixing are fully supported without any changes required.

colored tables

\rowcolors is supported, except that the optional argument is ignored so far.

colored text and boxes

\textcolor, \colorbox, and \fcolorbox are supported.

\color and \pagecolor

\color and \pagecolor are ignored. Use css or \textcolor where possible.

§ 661.2 xcolor definitions: location and timing

The lwarp core and its lwarp-xcolor package are tightly integrated to allow comparable results for print, HTML, and print inside an HTML lateximage. This requires a number of definitions and redefintions depending on whether each of xcolor and lateximage is being used, and whether print or HTML is being generated. Some of these actions are one-time when xcolor is loaded, and others are temporary as lateximage is used.

When xcolor is loaded in print mode: No special actions are taken at the time that xcolor is loaded in print mode, but see \AtBeginDocument below.

When lwarp-xcolor is loaded in HTML mode: xcolor's original definitions are saved for later restoration. \LWR@restoreorigformatting is appended to restore these definitions for use inside a lateximage. New HTML-mode definitions are created for \textcolor, \pagecolor, \nopagecolor, \colorbox, \colorboxBlock, \fcolorbox, \fcolorboxBlock, and fcolorminipage.

\AtBeginDocument in print or HTML mode: See Section 89. If xcolor has been loaded, the print-mode \fcolorbox is modified to accept a background color of none, and additional definitions are created for lwarp's new macros print-mode macros \colorboxBlock, \fcolorboxBlock, and fcolorminipage. The HTML versions of these macros will already have been created by lwarp-xcolor if it has been loaded.

For use inside an HTML lateximage, \LWR@restoreorigformatting is appended to temporarily set these functions to their print-mode versions.

In a lateximage in HTML mode: \LWR@restoreorigformatting temporarily restores the print-mode definitions of xcolor's functions. See \LWR@restoreorigformatting on page 546.

\color:

Print: Used as-is.

HTML: Ignored by *pdftotext*, and will not appear.

HTML lateximage: Colors will appear in a lateximage.

\textcolor:

Print: Used as-is.

HTML: Redefined by lwarp-xcolor, page 1241.

HTML lateximage: Remembers and reuses the print version.

\pagecolor:

Print: Used as-is.

HTML: Ignored.

HTML lateximage: Colors will be picked up in a lateximage.

\nopagecolor:

Print: Used as-is.

HTML: Ignored.

HTML lateximage: Colors will be picked up in a lateximage.

\colorbox:

Print: Used as-is.

HTML: Redefined by lwarp-xcolor, page 1242.

HTML lateximage: Remembers and reuses the print version.

\colorboxBlock:

Print: Becomes \colorbox.

HTML: Newly defined by lwarp-xcolor to use a , page 1242.

HTML lateximage: Remembers and reuses the print version \colorbox.

\fcolorbox:

Print: Modified to allow a background of none.
\LWR@print@fcolorbox at section 89

HTML: Redefined by lwarp-xcolor, page 1243.

HTML lateximage: Remembers and reuses the print version.

\fcolorboxBlock:

Print: Becomes \fcolorbox. Section 89

HTML: Newly defined by lwarp-xcolor to use a , page 1243.

HTML lateximage: Remembers and reuses the print version \fcolorbox.

fcolorminipage:

Print: Newly defined in the lwarp core.
LWR@print@fcolorminipage at section 89

HTML: Newly defined by lwarp-xcolor, page 1244.

HTML lateximage: Uses the print version.

\boxframe:

Print: Used as-is.

HTML: Redefined by lwarp-xcolor, page 1245.

HTML lateximage: Remembers and reuses the print version.

§ 661.3 Package loading

for HTML output:

```
\LWR@ProvidesPackagePass{xcolor}[2016/05/11]
```

§ 661.4 Remembering and restoring original definitions

Remember the following print-mode actions to be restored when inside a lateximage environment:

```
\LetLtxMacro\LWR@print@pagecolor\pagecolor
\LetLtxMacro\LWR@print@nopagecolor\nopagecolor
```

\LWR@restoreorigformatting

Inside a lateximage the following gets restored to their print-mode actions:

```
\appto\LWR@restoreorigformatting{%
\LetLtxMacro\pagecolor\LWR@print@pagecolor%
\LetLtxMacro\nopagecolor\LWR@print@nopagecolor%
}
```

§ 661.5 \normalcolor

\normalcolor

```
\DeclareRobustCommand{\LWR@HTML@normalcolor}{\color{black}}%

\LWR@formatted{normalcolor}
```

§ 661.6 HTML color style

\LWR@findcurrenttextcolor Sets \LWR@tempcolor to the current color.

```
\renewcommand*{\LWR@findcurrenttextcolor}{%
\LWR@traceinfo{LWR@findcurrenttextcolor}%
\protect\colorlet{LWR@current@color}{.}%
\LWR@traceinfo{LWR@findcurrenttextcolor B}%
\protect\convertcolorspec{named}{LWR@current@color}{HTML}\LWR@tempcolor%
\LWR@traceinfo{LWR@findcurrenttextcolor: done}%
}
```

\LWR@currenttextcolorstyle Prints a color style for the current color.

```
\newcommand*{\LWR@currenttextcolorstyle}{%
\LWR@findcurrenttextcolor%
\ifdefstring{\LWR@tempcolor}{000000}%
{}%
{color: \LWR@origpound\LWR@tempcolor ; }%
}
```

\LWR@textcurrentcolor {⟨*text*⟩} Like \textcolor but uses the current \color instead.

```
\DeclareDocumentCommand{\LWR@textcurrentcolor}{m}{%
\begingroup%
\LWR@hook@processingtags%
\LWR@findcurrenttextcolor%
\InlineClass[color:\LWR@origpound\LWR@tempcolor]{textcolor}{%
    \renewcommand*{\LWR@currenttextcolor}{\LWR@origpound\LWR@tempcolor}%
    #1%
}%
\endgroup%
}
```

\LWR@colorstyle {⟨*1: model*⟩} {⟨*2: color*⟩}

For a color style, prints the color converted to HTML colors.

```
\NewDocumentCommand{\LWR@colorstyle}{m m}{%
\begingroup%
\LWR@hook@processingtags%
```

Use the xcolor package to convert to an HTML color space:

```
\convertcolorspec{#1}{#2}{HTML}\LWR@tempcolor%
```

Print the converted color:

```
\LWR@origpound\LWR@tempcolor%
\endgroup%
}
```

\LWR@backgroundcolor [⟨*model*⟩] {⟨*color*⟩} {⟨*text*⟩}

Similar to \textcolor, but prints black text against a color background.

Converted into an HTML hex color span.

```
\NewDocumentCommand{\LWR@backgroundcolor}{O{named} m m}{%
\begingroup%
\LWR@hook@processingtags%
\InlineClass[background:\LWR@colorstyle{#1}{#2}]{backgroundcolor}{%
#3%
}%
\endgroup%
}
```

§ 661.7 HTML border

`\LWR@borderpadding` {⟨*colorstyle*⟩} {⟨*color*⟩} Prints the HTML attributes for a black border and padding. `\LWR@forceminwidth` must be used first in order to set the border width.

```
\newcommand*{\LWR@borderpadding}[2]{%
border:\LWR@printlength{\LWR@atleastonept} solid \LWR@colorstyle{#1}{#2} ; %
padding:\LWR@printlength{\fboxsep}%
}
```

§ 661.8 High-level macros

`\color` [⟨*model*⟩] {⟨*color*⟩}

⚠ The current `\color` is used by HTML rules and frames, but does not affect the current HTML text output, due to the lack of HTML states and scoping limitations. Use `\textcolor` if possible.

```
\NewDocumentCommand{\LWR@HTML@color}{o m}{%
\IfValueTF{#1}{%
    \LWR@print@color[#1]{#2}%
    \convertcolorspec{#1}{#2}{HTML}\LWR@tempcolor%
}{%
    \LWR@print@color{#2}%
    \convertcolorspec{named}{#2}{HTML}\LWR@tempcolor%
}%
\edef\LWR@currenttextcolor{\LWR@origpound\LWR@tempcolor}%
}

\LWR@formatted{color}
```

`\textcolor` [⟨*model*⟩] {⟨*color*⟩} {⟨*text*⟩}

Converted into an HTML hex color span.

```
\NewDocumentCommand{\LWR@HTML@textcolor}{o m m}{%
\begingroup%
\LWR@hook@processingtags%
\IfValueTF{#1}{%
    \color[#1]{#2}%
}{%
    \color{#2}%
```

```
}%
\InlineClass[color:\LWR@currenttextcolor]{textcolor}{#3}%
\endgroup%
}%

\LWR@formatted{textcolor}
```

\pagecolor [⟨*model*⟩] {⟨*color*⟩}

Ignored. Use CSS instead.

```
\renewcommand*{\pagecolor}[2][named]{}
```

\nopagecolor Ignored.

```
\renewcommand*{\nopagecolor}{}
```

\colorbox [⟨*model*⟩] {⟨*color*⟩} {⟨*text*⟩}

Converted into an HTML hex background color .

```
\NewDocumentCommand{\LWR@HTML@colorbox}{O{named} m +m}{%
\begingroup%
\LWR@hook@processingtags%
\InlineClass[%
background:\LWR@colorstyle{#1}{#2} ; %
padding:\LWR@printlength{\fboxsep}%
]{colorbox}{#3}%
\endgroup%
}

\AtBeginDocument{
    \LWR@formatted{colorbox}
}
```

\colorboxBlock [⟨*model*⟩] {⟨*color*⟩} {⟨*text*⟩}

Converted into an HTML hex background color .

```
\NewDocumentCommand{\LWR@HTML@colorboxBlock}{O{named} m +m}{%
\begingroup%
\LWR@hook@processingtags%


\LWR@stoppars%

\begin{BlockClass}[%
background:\LWR@colorstyle{#1}{#2} ; %
padding:\LWR@printlength{\fboxsep}%
]{colorboxBlock}
#3
\end{BlockClass}%
\endgroup%
```

Prevent paragraph tags around horizontal white space until the start of the next paragraph:

```
\global\booltrue{LWR@minipagethispar}%
}

\AtBeginDocument{
    \LWR@formatted{colorboxBlock}
}
```

\fcolorbox `[`⟨*framemodel*⟩`]` `{`⟨*framecolor*⟩`}` `[`⟨*boxmodel*⟩`]` `{`⟨*boxcolor*⟩`}` `{`⟨*text*⟩`}`

Converted into a framed HTML hex background color span.

A background color of none creates a colored frame without a background color.

```
\NewDocumentCommand{\LWR@HTML@fcolorbox}{O{named} m O{#1} m +m}{%
\LWR@traceinfo{HTML fcolorbox #2 #4}%
\begingroup%
\LWR@hook@processingtags%
\LWR@forceminwidth{\fboxrule}%
\ifthenelse{\equal{#4}{none}}%
    {% no background color
        \InlineClass[%
        \LWR@borderpadding{#1}{#2}%
        ]{fcolorbox}{#5}%
    }%
    {% yes background color
        \InlineClass[%
        \LWR@borderpadding{#1}{#2} ; %
        background:\LWR@colorstyle{#3}{#4}%
        ]{fcolorbox}{#5}%
    }%
\endgroup%
}

\AtBeginDocument{
    \LWR@formatted{fcolorbox}
}
```

\fcolorboxBlock `[`⟨*framemodel*⟩`]` `{`⟨*framecolor*⟩`}` `[`⟨*boxmodel*⟩`]` `{`⟨*boxcolor*⟩`}` `{`⟨*text*⟩`}`

Converted into a framed HTML hex background color span.

A background color of none creates a colored frame without a background color.

```
\NewDocumentCommand{\LWR@HTML@fcolorboxBlock}{O{named} m O{#1} m +m}{%
\LWR@traceinfo{HTML fcolorboxBlock #2 #4}%
\begingroup%
\LWR@hook@processingtags%
\LWR@forceminwidth{\fboxrule}%

\LWR@stoppars%
```

```
\ifthenelse{\equal{#4}{none}}%
    {% no background color
        \begin{BlockClass}[%
            \LWR@borderpadding{#1}{#2}%
        ]{fcolorboxBlock}
        #5
        \end{BlockClass}%
    }%
    {% yes background color
        \convertcolorspec{#3}{#4}{HTML}\LWR@tempcolortwo%
        \begin{BlockClass}[%
            background:\LWR@origpound\LWR@tempcolortwo\ ; %
            \LWR@borderpadding{#1}{#2}%
        ]{fcolorboxBlock}
        #5
        \end{BlockClass}%
    }%
\endgroup%
```

Prevent paragraph tags around horizontal white space until the start of the next paragraph:

```
\global\booltrue{LWR@minipagethispar}%
\LWR@traceinfo{HTML fcolorboxBlock done}%
}

\AtBeginDocument{
    \LWR@formatted{fcolorboxBlock}
}
```

Creates a framed HTML around its contents.

A print-output version is defined in the lwarp core: section 89

`\LWR@subfcolorminipage` {⟨*framemodel*⟩} {⟨*framecolor*⟩} {⟨*background tag*⟩} {⟨*height*⟩}

```
\NewDocumentCommand{\LWR@subfcolorminipage}{m m m m}{%

\LWR@stoppars%

\begin{BlockClass}[%
#3%
\LWR@borderpadding{#1}{#2} ; %
\IfValueT{#4}{height:\LWR@printlength{\LWR@tempheight} ; }%
width:\LWR@printlength{\LWR@tempwidth}%
]{fcolorminipage}%
}
```

Env `fcolorminipage` [⟨*1:framemodel*⟩] {⟨*2:framecolor*⟩} [⟨*3:boxmodel*⟩] {⟨*4:boxcolor*⟩} [⟨*5:align*⟩] [⟨*6:height*⟩] [⟨*7:inner-align*⟩] {⟨*8:width*⟩}

```
\NewDocumentEnvironment{LWR@HTML@fcolorminipage}{O{named} m O{#1} m O{c} o o m}
{%
\LWR@hook@processingtags%
```

```
\setlength{\LWR@tempwidth}{#8}%
\IfValueT{#6}{\setlength{\LWR@tempheight}{#6}}%
\LWR@forceminwidth{\fboxrule}%
\convertcolorspec{#1}{#2}{HTML}\LWR@tempcolor%
\ifthenelse{\equal{#4}{none}}%
    {\LWR@subfcolorminipage{#1}{#2}{}{#6}}%
    {%
        \convertcolorspec{#3}{#4}{HTML}\LWR@tempcolortwo%
        \LWR@subfcolorminipage{#1}{#2}%
            {background:\LWR@origpound\LWR@tempcolortwo\ ; }%
            {#6}%
    }%
}%
{%
    \end{BlockClass}%
```

Prevent paragraph tags around horizontal white space until the start of the next paragraph:

```
    \global\booltrue{LWR@minipagethispar}%
}

\AtBeginDocument{
\LWR@formattedenv{fcolorminipage}
}
```

`\boxframe` {⟨*width*⟩} {⟨*height*⟩} {⟨*depth*⟩}

The depth is added to the height, but the box is not decended below by the depth. `\textcolor` is honored.

```
\newcommand*{\LWR@HTML@boxframe}[3]{%
{%
\setlength{\LWR@tempwidth}{#1}%
\setlength{\LWR@tempheight}{#2}%
\addtolength{\LWR@tempheight}{#3}%
\LWR@forceminwidth{\fboxrule}%
\LWR@findcurrenttextcolor%
\InlineClass[%
display:inline-block ; %
border:\LWR@printlength{\LWR@atleastonept} solid \LWR@currenttextcolor{} ; %
width:\LWR@printlength{\LWR@tempwidth} ; %
height:\LWR@printlength{\LWR@tempheight}%
]{boxframe}{}%
}%
}

\LWR@formatted{boxframe}
```

§ 661.9 Row colors

\rowc@l@rs [⟨*cmds*⟩] {⟨*startrow*⟩} {⟨*odd color*⟩} {⟨*even color*⟩}

```
\newcommand*{\LWR@xcolortempcolor}{}

\def\rowc@l@rs[#1]#2#3#4%
{
\rownum=1%
   \@rowcolorstrue%
   \@ifxempty{#3}%
     {\def\@oddrowcolor{\@norowcolor}}%
     {%
        \convertcolorspec{named}{#3}{HTML}\LWR@xcolortempcolor%
        \edef\@oddrowcolor{%
            \csdef{LWR@xcolorrowHTMLcolor}{\LWR@xcolortempcolor}%
        }%
     }%
   \@ifxempty{#4}%
     {\def\@evenrowcolor{\@norowcolor}}%
     {%
        \convertcolorspec{named}{#4}{HTML}\LWR@xcolortempcolor%
        \edef\@evenrowcolor{%
            \csdef{LWR@xcolorrowHTMLcolor}{\LWR@xcolortempcolor}%
        }%
     }%
   \if@rowcmd
     \def\@rowcolors
     {%
%         #1%
        \if@rowcolors
%         \noalign{%
            \relax\ifnum\rownum<#2\@norowcolor\else
            \ifodd\rownum\@oddrowcolor\else\@evenrowcolor\fi\fi%
%          }%
        \fi%
     }%
   \else
     \def\@rowcolors
     {%
        \if@rowcolors
            \ifnum\rownum<#2%
%            \noalign{%
               \@norowcolor
%             }
            \else
%            #1%
%            \noalign{%
               \ifodd\rownum\@oddrowcolor\else\@evenrowcolor\fi%
%             }%
            \fi
        \fi%
     }%
   \fi
   \ignorespaces%
}
```

\@norowcolor Turns off color for this row.

```
\def\@norowcolor{%
\renewcommand{\LWR@xcolorrowHTMLcolor}{}%
}
```

\@rowc@lors Executed at the end of each row.

```
\def\@rowc@lors{%
%   \noalign{%
        \advance\rownum\@ne%
%   }%
    \@rowcolors%
}
```

File 554 **lwarp-xechangebar.sty**

§ 662 Package xechangebar

Pkg xechangebar xechangebar is ignored

for HTML output:

```
\LWR@ProvidesPackageDrop{xechangebar}[2017/08/03]
\LWR@origRequirePackage{lwarp-changebar}
```

File 555 **lwarp-xellipsis.sty**

§ 663 Package xellipsis

(*Emulates or patches code by* Donald P. Goodman III.)

Pkg xellipsis xellipsis is patched for use by lwarp.

When non-zero, each of the spaces is converted to an HTML thin unbreakable space.

for HTML output:

```
\LWR@ProvidesPackagePass{xellipsis}[2015/11/01]

\newcommand*{\LWR@xellipsespace}[1]{%
\ifdim#1=0pt\else%
    \ifdim#1<\fontdimen2\font%
        \,%
    \else%
        ~%
    \fi%
\fi%
}

\def\xelip{%
\mbox{%
    \LWR@xellipsespace{\xelipprebef}%
    \xelipprechar%
```

```
    \LWR@xellipsespace{\xelippreaft}%
    \LWR@xellipsespace{\xelipbef}%
    \xelipchar%
    \xel@loopi = 1%
    \loop\ifnum\xelipnum>\xel@loopi%
        \advance\xel@loopi by1%
        \LWR@xellipsespace{\xelipgap}%
        \xelipchar%
    \repeat%
    \LWR@xellipsespace{\xelipaft}%
    \LWR@xellipsespace{\xelippostbef}%
    \xelippostchar%
    \LWR@xellipsespace{\xelippostaft}%
}%
}%
```

File 556 **lwarp-xetexko.sty**

§ 664 Package xetexko

(*Emulates or patches code by* Dohyun Kim.)

Pkg xetexko xetexko is patched for use by lwarp.

for HTML output:

```
\LWR@loadbefore{xetexko}

\LWR@ProvidesPackagePass{xetexko}[2021/03/22]

\renewcommand{\verticaltypesetting}{}
\renewenvironment{vertical}[1]{\BlockClass{verticalrl}}{\endBlockClass}
\renewenvironment{horizontal}[1]{\BlockClass{horizontaltb}}{\endBlockClass}
\renewcommand{\vertlatin}[1]{#1}
```

File 557 **lwarp-xevlna.sty**

§ 665 Package xevlna

(*Emulates or patches code by* Zdeněk Wagner.)

Pkg xevlna xevlna is patched for use by lwarp.

Non-breakable spaces are inserted into HTML.

for HTML output:

```
\LWR@ProvidesPackagePass{xevlna}[2016/09/05]

\def\ProcessCSpreposition{\ifx\next\xevlnaXeTeXspace\HTMLentity{nbsp}\fi}

\appto{\LWR@hook@processingtags}{\xevlnaDisable}%
```

File 558 **lwarp-xfakebold.sty**

§ 666 Package

xfakebold

(*Emulates or patches code by* Herbert Voss.)

Pkg xfakebold xfakebold is patched for use by lwarp, and additional underlying support is found in the lwarp core.

⚠ text mode xfakebold is only used in svg math and lateximages. Text mode is not set bold, but \setBold in text will be applied to any following svg math.

for HTML output:

```
\LWR@ProvidesPackagePass{xfakebold}[2020/06/24]

\newcommand*{\LWR@HTML@setBold}{\booltrue{LWR@xfakebold}}
\LWR@formatted{setBold}

\newcommand*{\LWR@HTML@unsetBold}{\boolfalse{LWR@xfakebold}}
\LWR@formatted{unsetBold}

\renewcommand*{\LWR@applyxfakebold}{%
    \ifbool{LWR@xfakebold}{\LWR@print@setBold}{\LWR@print@unsetBold}%
}
```

For MathJax, xfakebold is ignored.

```
\begin{warpMathJax}
\CustomizeMathJax{\newcommand{\setBold}[1][]{}}
\CustomizeMathJax{\newcommand{\unsetBold}{}}
\end{warpMathJax}
```

File 559 **lwarp-xfrac.sty**

§ 667 Package

xfrac

(*Emulates or patches code by* The LaTeX3 Project.)

Pkg xfrac Supported by adding xfrac instances, and emulated for MathJax.

for HTML output:

```
\LWR@ProvidesPackagePass{xfrac}[2018-08-23]
```

⚠ font size In the user's document preamble, lwarp should be loaded after font-related setup. During html conversion, this font is used by lwarp to generate its initial pdf output containing html tags, later to be converted by *pdftotext* to a plain text file. While the text may be in any font which *pdftotext* can read, the math is directly converted into svg images using this same user-selected font. xfrac below is set for the Latin Modern (lmr) font. If another font is used, it may be desirable to redefine \xfracHTMLfontsize with a different em size.

\sfrac [⟨*instance*⟩] {⟨*num*⟩} [⟨*sep*⟩] {⟨*denom*⟩}

A text-mode instance for the default font is provided below. The numerator and denominator formats are adjusted to encase everything in HTML tags. `\scalebox` is made null inside the numerator and denominator, since the HTML tags should not be scaled, and we do not want to introduce additional HTML tags for scaling.

In math mode, which will appear inside a `latexmage`, no adjustments are necessary.

`\xfracHTMLfontsize` User-redefinable macro which controls the font size of the fraction.

```
\newcommand*{\xfracHTMLfontsize}{.6em}
```

instances Instances of xfrac for various font choices:

Produce CSS for a small raised numerator and a small denominator.

Scaling is turned off so that *pdftotext* correctly reads the result.

```
\DeclareInstance{xfrac}{default}{text}{
    numerator-format = {%
        \begingroup%
        \RenewDocumentCommand{\scalebox}{m o m}{##3}%
        \InlineClass{numerator}{#1}\,%
        \endgroup%
    },
    denominator-format = {%
        \begingroup%
        \RenewDocumentCommand{\scalebox}{m o m}{##3}%
        \InlineClass{denominator}{#1}%
        \endgroup%
    },
```

For *pdftotext*, do not scale the text:

```
    scaling = false
}

\DeclareInstance{xfrac}{lmr}{text}{
    numerator-format = {%
        \begingroup%
        \RenewDocumentCommand{\scalebox}{m o m}{##3}%
        \InlineClass{numerator}{#1}\,%
        \endgroup%
    },
    denominator-format = {%
        \begingroup%
        \RenewDocumentCommand{\scalebox}{m o m}{##3}%
        \InlineClass{denominator}{#1}%
        \endgroup%
    },
```

For *pdftotext*, do not scale the text:

```
    scaling = false
}
```

```
\DeclareInstance{xfrac}{lmss}{text}{
    numerator-format = {%
        \begingroup%
        \RenewDocumentCommand{\scalebox}{m o m}{##3}%
        \InlineClass{numerator}{#1}\,%
        \endgroup%
    },
    denominator-format = {%
        \begingroup%
        \RenewDocumentCommand{\scalebox}{m o m}{##3}%
        \InlineClass{denominator}{#1}%
        \endgroup%
    },
```

For *pdftotext*, do not scale the text:

```
    scaling = false
}

\DeclareInstance{xfrac}{lmtt}{text}{
    numerator-format = {%
        \begingroup%
        \RenewDocumentCommand{\scalebox}{m o m}{##3}%
        \InlineClass{numerator}{#1}\,%
        \endgroup%
    },
    denominator-format = {%
        \begingroup%
        \RenewDocumentCommand{\scalebox}{m o m}{##3}%
        \InlineClass{denominator}{#1}%
        \endgroup%
    },
```

For *pdftotext*, do not scale the text:

```
    scaling = false
}
```

For MathJax:

```
\begin{warpMathJax}
\CustomizeMathJax{\newcommand{\LWRsfrac}[2][/]{{}^\LWRsfracnumerator\!#1{}_{#2}}}
\CustomizeMathJax{\newcommand{\sfrac}[2][]{\def\LWRsfracnumerator{#2}\LWRsfrac}}
\end{warpMathJax}
```

File 560 **lwarp-xltabular.sty**

§ 668 Package

xltabular

(*Emulates or patches code by* Rolf Niepraschk, Herbert Voss.)

Pkg xltabular xltabular is emulated by lwarp.

for HTML output: Relies on tabularx.

⚠ table numbering At present, an `xltabular` without a caption or with only a `\caption*` may be misnumbered in HTML, so it may be necessary to place at the end of the table:

```
\warpHTMLonly{\addtocounter{table}{-1}}
```

```
\RequirePackage{tabularx}
\RequirePackage{ltablex}

\LWR@ProvidesPackageDrop{xltabular}[2018/05/23]

\DeclareDocumentEnvironment{xltabular}{o m m}
{\longtable{#3}}
{\endlongtable}
```

File 561 **lwarp-xltxtra.sty**

§ 669 Package xltxtra

(*Emulates or patches code by* Will Robertson, Jonathan Kew.)

Pkg xltxtra xltxtra is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{xltxtra}[2016/01/21]

\RequirePackage{realscripts}
\RequirePackage{metalogo}
\newcommand*\TeX@logo@spacing[6]{}

\newcommand*{\vfrac}[2]{%
\textsuperscript{#1}/\textsubscript{#2}%
}

\newcommand\namedglyph[1]{%
  \@tempcnta=\XeTeXglyphindex "#1"\relax
  \ifnum\@tempcnta>0
    \XeTeXglyph\@tempcnta
  \else
    \xxt@namedglyph@fallback{#1}%
  \fi}

\newcommand\xxt@namedglyph@fallback[1]{[#1]}

\DeclareDocumentCommand{\showhyphens}{m}{}
```

File 562 **lwarp-xmpincl.sty**

§ 670 Package xmpincl

(*Emulates or patches code by* Maarten Sneep.)

Pkg xmpincl xmpincl is ignored.

for HTML output: Discard all options for lwarp-xmpincl:

```
\LWR@ProvidesPackageDrop{xmpincl}[2008/05/10]
\newcommand*{\includexmp}[1]{}
```

File 563 **lwarp-xpiano.sty**

§ 671 Package xpiano

(*Emulates or patches code by* Enrico Gregorio.)

Pkg xpiano xpiano is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{xpiano}

\ExplSyntaxOn
\NewDocumentCommand{\LWR@print@keyboard}{ O{}m }
{
\xpiano_keyboard:nn { #1 } { #2 }
}

\NewDocumentCommand{\LWR@HTML@keyboard}{ O{}m }
{
\begin{lateximage}*
    [%
        -xpiano-~\PackageDiagramAltText{}: \detokenize\expandafter{#2}%
    ]
    [\detokenize\expandafter{#1}]
\xpiano_keyboard:nn { #1 } { #2 }
\end{lateximage}
}
\ExplSyntaxOff

\LWR@formatted{keyboard}
```

File 564 **lwarp-xpinyin.sty**

§ 672 Package xpinyin

(*Emulates or patches code by* Soben Lee.)

Pkg xpinyin xpinyin is supported.

Pinyin is disabled for file names, the sidetoc, and regular footnotes, but is left enabled for minipage footnotes, as per the print mode.

for HTML output:

```
\LWR@ProvidesPackagePass{xpinyin}[2019-04-07]
```

The original's boxes are not used, instead the contents are used with <ruby>, <rb>, and <rt> tags per modern HTML. Color is detected. `ratio` is ignored for ***pdftotext*** to work correctly. Extra spaces are placed inside the tags to allow line breaks in the HTML text.

```
\ExplSyntaxOn
\cs_new_protected_nopar:Npn \LWR@HTML@__xpinyin_make_pinyin_box:nnn #1#2#3
{
    \color_group_begin: \color_ensure_current:
    \l__xpinyin_pinyin_box_hook_tl
    \renewcommand*{\l__xpinyin_ratio_tl}{1}% for pdftotext
    \__xpinyin_select_font:
    \clist_if_exist:cTF { c__xpinyin_multiple_ #1 _clist }
        { \l__xpinyin_multiple_tl \l__xpinyin_format_tl }
        { \l__xpinyin_format_tl }
    \ifdefempty{\l__xpinyin_format_tl}
        {#3}
        {\LWR@textcurrentcolor{#3}}
    \color_group_end:
}
\LWR@formatted{__xpinyin_make_pinyin_box:nnn}

\cs_new_protected_nopar:Npn \LWR@HTML@__xpinyin_CJKsymbol:nn #1#2
  {
    \__xpinyin_leavevmode:
    \LWR@htmltagc{ruby}
    \LWR@htmltagc{rb}
    \__xpinyin_save_CJKsymbol:n {#2}\null% \null removes extra space
    \LWR@htmltagc{/rb\space}
    \LWR@htmltagc{rp}(\LWR@htmltagc{/rp\space}
    \LWR@htmltagc{rt}
    \__xpinyin_make_pinyin_box:nnn {#1} {#2} { \use:c { c__xpinyin_ #1 _tl } }
    \LWR@htmltagc{/rt\space}
    \LWR@htmltagc{rp})\LWR@htmltagc{/rp\space}
    \LWR@htmltagc{/ruby\space}\null
  }
\LWR@formatted{__xpinyin_CJKsymbol:nn}

\cs_new_protected_nopar:Npn \LWR@HTML@__xpinyin_single_CJKsymbol:nn #1#2
  {
    \__xpinyin_leavevmode:
    \LWR@htmltagc{ruby}
    \LWR@htmltagc{rb}
    \__xpinyin_save_CJKsymbol:n {#1}\null% \null removes extra space
    \LWR@htmltagc{/rb\space}
    \LWR@htmltagc{rp}(\LWR@htmltagc{/rp\space}
    \LWR@htmltagc{rt}
    \__xpinyin_make_pinyin_box:xnn
      { \__xpinyin_to_unicode:n {#1} } {#1} { \__xpinyin_pinyin:n {#2} }
    \LWR@htmltagc{/rt\space}
    \LWR@htmltagc{rp})\LWR@htmltagc{/rp\space}
    \LWR@htmltagc{/ruby\space}\null
  }
\LWR@formatted{__xpinyin_single_CJKsymbol:nn}

\ExplSyntaxOff
```

The lwarp core uses the following to disable CJK xpinyin for filenames, sideTOC, and footnotes.

```
\renewcommand*{\LWR@disablepinyin}{\disablepinyin}

\FilenameNullify{\LWR@disablepinyin}
```

File 565 **lwarp-xr.sty**

§ 673 Package xr

(*Emulates or patches code by* Jean-Pierre Drucbert, David Carlisle.)

Pkg xr

xr is patched for use by lwarp. The *_html.aux file is used. \externaldocument is modified to also accept the optional arguments for xr-hyper, which currently uses xr for HTML output.

See section 5.17.

for HTML output:

```
\LWR@ProvidesPackagePass{xr}[2019/07/22]%

\LetLtxMacro\LWR@orig@externaldocument\externaldocument

\RenewDocumentCommand{\externaldocument}{O{} O{} m O{}}{%
    \ifblank{#1}{%
        \LWR@orig@externaldocument{#3_html}%
    }{%
        \LWR@orig@externaldocument[#1]{#3_html}%
    }%
}
```

File 566 **lwarp-xr-hyper.sty**

§ 674 Package xr-hyper

(*Emulates or patches code by* David Carlisle.)

Pkg xr-hyper

xr-hyper is replaced by xr, which is modified to accept the optional arguments for \externaldocument. So far, no hyperlinks are provided for citations.

See section 5.17.

for HTML output:

```
\LWR@ProvidesPackageDrop{xr-hyper}[2019/10/03]%

\LWR@origRequirePackage{lwarp-xr}
```

File 567 **lwarp-xtab.sty**

§ 675 Package xtab

(*Emulates or patches code by* Peter Wilson.)

Pkg xtab xtab is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{xtab}[2011/07/31]
```

⚠ Misplaced alignment tab character &

For `\tablefirsthead`, etc., enclose them as follows:

```
\StartDefiningTabulars
\tablefirsthead
. . .
\StopDefiningTabulars
```

See section 8.10.1.

⚠ lateximage supertabular and xtab are not supported inside a `lateximage`.

```
\newcommand{\LWRXT@firsthead}{}

\newcommand{\tablefirsthead}[1]{%
    \long\gdef\LWRXT@firsthead{#1}%
}

\newcommand{\tablehead}[1]{}

\newcommand{\tablelasthead}[1]{}

\newcommand{\notablelasthead}{}

\newcommand{\tabletail}[1]{}

\newcommand{\LWRXT@lasttail}{}

\newcommand{\tablelasttail}[1]{%
    \long\gdef\LWRXT@lasttail{#1}%
}


\newcommand{\tablecaption}[2][]{%
    \long\gdef\LWRXT@caption{%
        \ifblank{#1}%
            {\caption{#2}}%
            {\caption[#1]{#2}}%
    }%
}

\let\topcaption\tablecaption
\let\bottomcaption\tablecaption


\newcommand*{\LWRXT@caption}{}

\newcommand*{\shrinkheight}[1]{}

\newcommand*{\xentrystretch}[1]{}
```

```
\NewDocumentEnvironment{xtabular}{s o m}
{%
\LWR@traceinfo{xtabular}%
\table%
\LWRXT@caption%
\begin{tabular}{#3}%
\TabularMacro\ifdefvoid{\LWRXT@firsthead}%
{\LWR@getmynexttoken}%
{\expandafter\LWR@getmynexttoken\LWRXT@firsthead}%
}%
{%
\ifdefvoid{\LWRXT@lasttail}%
{}%
{%
\TabularMacro\ResumeTabular%
\LWRXT@lasttail%
}%
\end{tabular}%
\endtable%

\gdef\LWRXT@caption{}%

\LWR@traceinfo{xtabular done}%
}

\NewDocumentEnvironment{mpxtabular}{s o m}
{\minipage{\linewidth}\xtabular{#3}}
{\endxtabular\endminipage}
```

File 568 **lwarp-xunicode.sty**

§ 676 Package

xunicode

Pkg xunicode

Error if xunicode is loaded after lwarp.

Patch lwarp-xunicode, but also verify that is was loaded before lwarp:

for HTML output:

```
\LWR@loadbefore{xunicode}%

\LWR@ProvidesPackagePass{xunicode}[2011/09/09]
```

\textcircled becomes a span with a rounded border. \providecommand is used to avoid conflict with textcomp.

```
\providecommand*{\LWR@HTML@textcircled}[1]{%
    \InlineClass[border: 1px solid \LWR@currenttextcolor]{textcircled}{#1}%
}

\LWR@formatted{textcircled}
```

Nullify xunicode macros when generating filenames:

```
\FilenameNullify{%
    \renewcommand*{\textdegree}{}%
    \renewcommand*{\textcelsius}{}%
    \renewcommand*{\textohm}{}%
    \renewcommand*{\textmu}{}%
    \renewcommand*{\textlquill}{}%
    \renewcommand*{\textrquill}{}%
    \renewcommand*{\textcircledP}{}%
    \renewcommand*{\texttwelveudash}{}%
    \renewcommand*{\textthreequartersemdash}{}%
    \renewcommand*{\textmho}{}%
    \renewcommand*{\textnaira}{}%
    \renewcommand*{\textpeso}{}%
    \renewcommand*{\textrecipe}{}%
    \renewcommand*{\textinterrobang}{}%
    \renewcommand*{\textinterrobangdown}{}%
    \renewcommand*{\textperthousand}{}%
    \renewcommand*{\textpertenthousand}{}%
    \renewcommand*{\textbaht}{}%
    \renewcommand*{\textdiscount}{}%
    \renewcommand*{\textservicemark}{}%
    \renewcommand*{\textcircled}[1]{#1}%
    \renewcommand*{\capitalcedilla}[1]{#1}%
    \renewcommand*{\capitalogonek}[1]{#1}%
    \renewcommand*{\capitalgrave}[1]{#1}%
    \renewcommand*{\capitalacute}[1]{#1}%
    \renewcommand*{\capitalcircumflex}[1]{#1}%
    \renewcommand*{\capitaltilde}[1]{#1}%
    \renewcommand*{\capitaldieresis}[1]{#1}%
    \renewcommand*{\capitalhungarumlaut}[1]{#1}%
    \renewcommand*{\capitalring}[1]{#1}%
    \renewcommand*{\capitalcaron}[1]{#1}%
    \renewcommand*{\capitalbreve}[1]{#1}%
    \renewcommand*{\capitalmacron}[1]{#1}%
    \renewcommand*{\capitaldotaccent}[1]{#1}%
}% FilenameNullify
```

File 569 **lwarp-xurl.sty**

§ 677 Package **xurl**

Pkg xurl xurl is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{xurl}[2020/01/14]

\def\useOriginalUrlSetting{}
```

File 570 **lwarp-xy.sty**

§ 678 Package xy

(*Emulates or patches code by* Kristoffer H. Rose, Ross Moore.)

Pkg xy xy is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{xy}[2013/10/06]
```

After xy modules have been loaded:

```
\AtBeginDocument{
```

The original definitions without a `lateximage`:

```
\LetLtxMacro\LWR@orig@xy\xy
\LetLtxMacro\LWR@orig@endxy\endxy
```

The outer-most `xy` environment is placed in a `lateximage`, but not more than one level deep, which would conflict with xy:

```
\renewcommand*{\xy}{%
    \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
        {\addtocounter{LWR@lateximagedepth}{1}}%
        {\begin{lateximage}[-xy-~\PackageDiagramAltText]}%
    \LWR@orig@xy%
}

\renewcommand*{\endxy}{%
    \LWR@orig@endxy%
    \ifnumcomp{\value{LWR@lateximagedepth}}{>}{1}%
        {\addtocounter{LWR@lateximagedepth}{-1}}%
        {\end{lateximage}}%
}
```

The `\xybox` must use the original definitions of `\xy`, `\endxy`:

```
\def\xybox#1{%
    \LWR@orig@xy#1\LWR@orig@endxy%
    \Edge@c={\rectangleEdge}\computeLeftUpness@%
}
```

If `\xygraph` is used, it is placed inside a `lateximage`:

```
\@ifundefined{xygraph}{}{

\LetLtxMacro\LWR@origxygraph\xygraph

\renewcommand{\xygraph}[1]{%
    \begin{lateximage}[-xy- xygraph \PackageDiagramAltText]
    \LWR@origxygraph{#1}
    \end{lateximage}
}

}% xygraph defined
```

```
33
34 }% AtBeginDocument
```

File 571 **lwarp-zhlineskip.sty**

§ 679 Package zhlineskip

Pkg zhlineskip zhlineskip is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{zhlineskip}[2019/05/15]

2 \newcommand*\SetTextEnvironmentSinglespace[1]{}
3 \newcommand*\RestoreTextEnvironmentLeading[1]{}
4 \newcommand*\SetMathEnvironmentSinglespace[1]{}
5 \newcommand*\RestoreMathEnvironmentLeading[1]{}
```

File 572 **lwarp-zwpagelayout.sty**

§ 680 Package zwpagelayout

(*Emulates or patches code by* Zdeněk Wagner.)

Pkg zwpagelayout zwpagelayout is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{zwpagelayout}[2013/01/13]

2 \def\noBboxes{}
3 \@onlypreamble\noBboxes
4
5 \expandafter\ifx\csname definecolor\endcsname\relax \else
6   \definecolor{cmykblack}{cmyk}{0,0,0,1}
7   \definecolor{grblack}{gray}{0}
8 %   \ifzwpl@redefineblack
9 %     \definecolor{black}{cmyk}{0,0,0,1}\color{black}
10 %   \fi
11   \definecolor{cmykred}{cmyk}{0,1,1,0}
12   \definecolor{cmykgreen}{cmyk}{1,0,1,0}
13   \definecolor{cmykblue}{cmyk}{1,1,0,0}
14   \definecolor{rgbred}{rgb}{1,0,0}
15   \definecolor{rgbgreen}{rgb}{0,1,0}
16   \definecolor{rgbblue}{rgb}{0,0,1}
17 %   \ifzwpl@redefinetocmyk
18 %     \definecolor{red}{cmyk}{0,1,1,0}
19 %     \definecolor{green}{cmyk}{1,0,1,0}
20 %     \definecolor{blue}{cmyk}{1,1,0,0}
21 %   \fi
22 \fi
23
24 \let\OverprintXeTeXExtGState\relax
25
```

```
\DeclareRobustCommand\SetOverprint{\ignorespaces}
\DeclareRobustCommand\SetKnockout{\ignorespaces}
\DeclareRobustCommand\textoverprint[1]{{\SetOverprint#1}}
\DeclareRobustCommand\textknockout[1]{{\SetKnockout#1}}

\def\SetPDFminorversion#1{}
\@onlypreamble\SetPDFminorversion

\newcommand*\Vcorr{}

\DeclareRobustCommand\vb[1][]{}
\NewDocumentCommand{\NewOddPage}{* o}{}
\NewDocumentCommand{\NewEvenPage}{* o}{}
\def\SetOddPageMessage#{\gdef\ZW@oddwarning}
\def\SetEvenPageMessage#{\gdef\Z@@evenwarning}
\def\ZW@oddwarning{Empty page inserted}\let\ZW@evenwarning\ZW@oddwarning

\def\clap#1{#1}

\def\CropFlap{2in}
\def\CropSpine{1in}
\def\CropXSpine{1in}
\def\CropXtrim{.25in}
\def\CropYtrim{.25in}
\def\UserWidth{5in}
\def\UserLeftMargin{1in}
\def\UserRightMargin{1in}
\def\UserTopMargin{1in}
\def\UserBotMargin{1in}
\def\thePageNumber{\LWR@origpound\,\arabic{page}}
\ifXeTeX
\def\ifcaseZWdriver{\ifcase2}
\else
\def\ifcaseZWdriver{\ifcase1}
\fi
\DeclareRobustCommand\ZWifdriver[2]{}
```

File 573 **lwarp-patch-komascript.sty**

§ 681 Package

patch-komascript

Pkg lwarp-patch-komascript

Patches for komascript classes.

lwarp loads this package when scrbook, scrartcl, or scrreprt classes are detected.

Many features are ignored during the HTML conversion. The goal is source-level compatibility.

\captionformat, \figureformat, and \tableformat are not yet emulated.

⚠ Not fully tested! Please send bug reports!

Some features have not yet been tested. Please contact the author with any bug reports.

for HTML output:

```
\ProvidesPackage{lwarp-patch-komascript}
```

typearea is emulated.

```
\RequirePackage{lwarp-typearea}
```

tocbasic is emulated.

```
\RequirePackage{lwarp-tocbasic}
```

scrextend patches most of the new macros.

```
\RequirePackage{lwarp-scrextend}
```

Indexing macros, simplified for lwarp:

```
\AtBeginDocument{

\renewcommand*{\idx@heading}{%
  \idx@@heading{\indexname}%
}

\renewenvironment{theindex}{%
  \idx@heading%
  \index@preamble\par\nobreak
    \let\item\LWR@indexitem%
    \let\subitem\LWR@indexsubitem%
    \let\subsubitem\LWR@indexsubsubitem%
}
{}

\renewcommand*\indexspace{}

}% AtBeginDocument
```

The \minisec is placed inside a of class minisec.

```
\renewcommand*{\minisec}[1]{
    \begin{BlockClass}{minisec}
    #1
    \end{BlockClass}
}
```

The part and chapter preambles are placed as plain text just after each heading.

```
\@ifundefined{setpartpreamble}{}{
\RenewDocumentCommand{\setpartpreamble}{o o +m}{%
    \renewcommand{\part@preamble}{#3}%
}
}

\@ifundefined{setchapterpreamble}{}{
\RenewDocumentCommand{\setchapterpreamble}{o o +m}{%
    \renewcommand{\chapter@preamble}{#3}%
```

```
}
}
```

Do not use \chaptername:

```
\renewcommand*{\LWR@printchaptername}{}
```

Simple captions are used in all cases.

```
\AtBeginDocument{
\AtBeginDocument{
    \LetLtxMacro\captionbelow\caption
    \LetLtxMacro\captionabove\caption

    \LetLtxMacro\captionofbelow\captionof
    \LetLtxMacro\captionofabove\captionof
}
}

\RenewDocumentEnvironment{captionbeside}{o m o o o s}
{}
{%
    \IfValueTF{#1}%
        {\caption[#1]{#2}}%
        {\caption{#2}}%
}

\RenewDocumentEnvironment{captionofbeside}{m o m o o o s}
{}
{%
    \IfValueTF{#2}%
        {\captionof{#1}[#2]{#3}}%
        {\captionof{#1}{#3}}%
}

\RenewDocumentCommand{\setcapindent}{s m}{}
\renewcommand*{\setcaphanging}{}
\renewcommand*{\setcapwidth}[2][]{}
\renewcommand*{\setcapdynwidth}[2][]{}
\RenewDocumentCommand{\setcapmargin}{s o m}{}
```

File 574 **lwarp-patch-memoir.sty**

§ 682 Package

patch-memoir

(*Emulates or patches code by* Peter Wilson.)

Pkg lwarp-patch-memoir Patches for memoir class.

⚠ Not fully tested! Please send bug reports!

lwarp loads this package when the memoir class is detected.

⚠ captions lwarp uses caption, which causes a warning from memoir. This is normal. Adjust captions

via caption, instead of memoir.

⚠ options clash

While emulating memoir, lwarp pre-loads a number of packages (section 682.1). This can cause an options clash when the user's document later loads the same packages with options. To fix this problem, specify the options before loading lwarp:

```
\documentclass{memoir}
. . .
\PassOptionsToPackage{options_list}{package_name}
. . .
\usepackage{lwarp}
. . .
\usepackage{package_name}
```

⚠ version numbers

memoir emulates a number of packages, and declares a version date for each which often does not match the date of the corresponding freestanding package. This can cause warnings about incorrect version numbers. Since lwarp is intended to support the freestanding packages, which are often newer than the date declared by memoir, it is hoped that memoir will update and change its emulated version numbers to match.

\label(bookmark){tag}

\label accepts an optional (bookmark) argument, but this is ignored in HTML.

⚠ comment

The comment environment is from the comment package, and thus requires that the \begin and \end each be on its own line:

```
\begin{comment}
This is a comment.
\end{comment}
```

\newcomment

Comments defined with \newcomment use memoir's defintions, and behave as expected, where the \begin and \end do have to each be on its own line.

⚠ verbatim footnotes

\verbfootnote is not supported.

⚠ \newfootnoteseries

\newfootnoteseries, etc. are not supported.

⚠ page notes

lwarp loads pagenote to perform memoir's pagenote functions, but there are minor differences in \pagenotesubhead and related macros.

page notes with cleveref

To add support for pagenotes with cleveref, add:

```
\crefname{pagenote}{page note}{page notes}
\Crefname{pagenote}{Page note}{Page notes}
```

page note \nameref

Note that for print mode, \nameref print the section name where the page notes are declared in the text, but for HTML it prints the name where the page notes are printed.

⚠ poems

Poem numbering is not supported.

⚠ verbatim

The verbatim environment does not yet support the memoir enhancements. It is currently recommended to load and use fancyvrb instead.

⚠ glossaries

The memoir glossary system is not yet supported by *lwarpmk*. The glossaries package may be used instead, but does require the glossary entries be changed from the memoir syntax to the glossaries syntax.

for HTML output:

```
1 \ProvidesPackage{lwarp-patch-memoir}
```

§ 682.1 Packages

These are pre-loaded to provide emulation for many of memoir's functions. memoir pretends that abstract, etc. are already loaded, via its "emulated" package mechanism, but lwarp is directly loading the "lwarp-" version of each, which happens to avoid memoir's emulation system.

```
\RequirePackage{lwarp-abstract}% req'd
% \RequirePackage{lwarp-array}% no longer req'd
\RequirePackage{lwarp-booktabs}% req'd
% \RequirePackage{lwarp-ccaption}% emualated below
\RequirePackage{lwarp-changepage}% req'd
\RequirePackage{lwarp-crop}
% \RequirePackage{lwarp-dcolumn}% no longer req'd
\RequirePackage{lwarp-enumerate}% req'd
\RequirePackage{lwarp-epigraph}% req'd
\RequirePackage{lwarp-fancyvrb}% req'd
\RequirePackage{lwarp-footmisc}% req'd

\let\framed\relax \let\endframed\relax
\let\shaded\relax \let\endshaded\relax
\let\leftbar\relax \let\endleftbar\relax
\let\snugshade\relax \let\endsnugshade\relax
\RequirePackage{lwarp-framed}% req'd

\RequirePackage{lwarp-hanging}% req'd
\RequirePackage{lwarp-makeidx}% req'd
\DisemulatePackage{moreverb}
\RequirePackage{lwarp-moreverb}
\RequirePackage{lwarp-mparhack}
\RequirePackage{lwarp-needspace}% req'd
\RequirePackage{lwarp-nextpage}% req'd
\RequirePackage{lwarp-pagenote}% req'd
\RequirePackage{lwarp-parskip}
\RequirePackage{lwarp-setspace}% req'd
\RequirePackage{lwarp-showidx}

\makeindex

% \RequirePackage{lwarp-tabularx}% no longer req'd
\RequirePackage{lwarp-titling}% req'd
% \RequirePackage{lwarp-tocbibind}% not emulated by memoir
\RequirePackage{lwarp-tocloft}% req'd
\RequirePackage{lwarp-verse}% req'd
```

§ 682.2 Label handling

Insert the lwarp label mechanism into the memoir package mechanism:

- `\@mem@old@label` is the LaTeX definition of `\label`.
- `\LWR@orig@label` becomes the memoir definition.
- lwarp's `\LWR@new@label` uses `\LWR@orig@label`.
- Want memoir's `\label` to use lwarp's `\label`, which then would use LaTeX's `\label`.
- So:
  - `\@mem@old@label` is set to `\LWR@new@label`.
  - `\LWR@orig@label` is set to `\@mem@old@label`.
- cleveref then encapsulates all the above with `\cref@old@label`.
- For a subcaption, cleveref modifies memoir's `\sf@memsub@label`, but that change is undone by lwarp.

```
\LetLtxMacro\LWR@orig@label\@mem@old@label
\LetLtxMacro\@mem@old@label\LWR@new@label
```

Patches for subfloats to support additional lwarp labels. This is the non-hyperref version from memoir.

```
\AtBeginDocument{
    \renewcommand*{\sf@@memsub@label}[1]{%
        \@bsphack
        \sf@@memsub@label@hook{#1}%
%         \@memoldlabel{#1}%
        \cref@label{#1}%                    lwarp
        \LWR@label@createtag{sub@#1}%           lwarp
        \protected@write\@auxout{}{%
            \string\newlabel{sub@#1}%
            {{\@nameuse{@@thesub\@captype}}%
            {\thepage}}}%
        \LWR@write@lwarplabel{sub@#1}%          lwarp
        \@esphack
    }
}
```

§ 682.3 Page layout

memoir already set the page size to a default, so it must be forced large for lwarp's use, to avoid tag overflows off the page.

```
\setstocksize{190in}{20in}
\setlrmarginsandblock{2in}{2in}{*}
\setulmarginsandblock{1in}{1in}{*}


\renewcommand*{\stockavi}{}
\renewcommand*{\stockav}{}
\renewcommand*{\stockaiv}{}
\renewcommand*{\stockaiii}{}
\renewcommand*{\stockavii}{}
\renewcommand*{\stockbvi}{}
\renewcommand*{\stockbv}{}
\renewcommand*{\stockbiv}{}
\renewcommand*{\stockbiii}{}
\renewcommand*{\stockbvii}{}
% \renewcommand*{\stockmetriccrownvo}{}% in docs but not in the package
\renewcommand*{\stockmlargecrownvo}{}
\renewcommand*{\stockmdemyvo}{}
\renewcommand*{\stockmsmallroyalvo}{}
\renewcommand*{\pageavi}{}
\renewcommand*{\pageavii}{}
\renewcommand*{\pageav}{}
\renewcommand*{\pageaiv}{}
\renewcommand*{\pageaiii}{}
\renewcommand*{\pagebvi}{}
\renewcommand*{\pagebvii}{}
\renewcommand*{\pagebv}{}
\renewcommand*{\pagebiv}{}
\renewcommand*{\pagebiii}{}
% \renewcommand*{\pagemetriccrownvo}{}% in docs but not in the package
\renewcommand*{\pagemlargecrownvo}{}
\renewcommand*{\pagemdemyvo}{}
\renewcommand*{\pagemsmallroyalvo}{}

\renewcommand*{\stockdbill}{}
\renewcommand*{\stockstatement}{}
\renewcommand*{\stockexecutive}{}
\renewcommand*{\stockletter}{}
\renewcommand*{\stockold}{}
\renewcommand*{\stocklegal}{}
\renewcommand*{\stockledger}{}
\renewcommand*{\stockbroadsheet}{}
\renewcommand*{\pagedbill}{}
\renewcommand*{\pagestatement}{}
\renewcommand*{\pageexecutive}{}
\renewcommand*{\pageletter}{}
\renewcommand*{\pageold}{}
\renewcommand*{\pagelegal}{}
\renewcommand*{\pageledger}{}
\renewcommand*{\pagebroadsheet}{}

```

```
\renewcommand*{\stockpottvo}{}
\renewcommand*{\stockfoolscapvo}{}
\renewcommand*{\stockcrownvo}{}
\renewcommand*{\stockpostvo}{}
\renewcommand*{\stocklargecrownvo}{}
\renewcommand*{\stocklargepostvo}{}
\renewcommand*{\stocksmalldemyvo}{}
\renewcommand*{\stockdemyvo}{}
\renewcommand*{\stockmediumvo}{}
\renewcommand*{\stocksmallroyalvo}{}
\renewcommand*{\stockroyalvo}{}
\renewcommand*{\stocksuperroyalvo}{}
\renewcommand*{\stockimperialvo}{}
\renewcommand*{\pagepottvo}{}
\renewcommand*{\pagefoolscapvo}{}
\renewcommand*{\pagecrownvo}{}
\renewcommand*{\pagepostvo}{}
\renewcommand*{\pagelargecrownvo}{}
\renewcommand*{\pagelargepostvo}{}
\renewcommand*{\pagesmalldemyvo}{}
\renewcommand*{\pagedemyvo}{}
\renewcommand*{\pagemediumvo}{}
\renewcommand*{\pagesmallroyalvo}{}
\renewcommand*{\pageroyalvo}{}
\renewcommand*{\pagesuperroyalvo}{}
\renewcommand*{\pageimperialvo}{}

\renewcommand*{\memfontfamily}{}
\renewcommand*{\memfontenc}{}
\renewcommand*{\memfontpack}{}

\renewcommand*{\anyptfilebase}{}
\renewcommand*{\anyptsize}{10}

\renewcommand*{\setstocksize}[2]{}
\renewcommand*{\settrimmedsize}[3]{}
\renewcommand*{\settrims}[2]{}

% \newlength{\lxvchars}
% \setlength{\lxvchars}{305pt}
% \newlength{\xlvchars}
% \setlength{\xlvchars}{190pt}
\renewcommand*{\setxlvchars}[1]{}
\renewcommand*{\setlxvchars}[1]{}

\renewcommand*{\settypeblocksize}[3]{}
\renewcommand*{\setlrmargins}[3]{}
\renewcommand*{\setlrmarginsandblock}[3]{}
\renewcommand*{\setbinding}[1]{}
\renewcommand*{\setulmargins}[3]{}
\renewcommand*{\setulmarginsandblock}[3]{}
\renewcommand*{\setcolsepandrule}[2]{}

\renewcommand*{\setheadfoot}[2]{}
\renewcommand*{\setheaderspaces}[3]{}
```

```
\renewcommand*{\setmarginnotes}[3]{}
\renewcommand*{\setfootins}[2]{}
\renewcommand*{\checkandfixthelayout}[1][]{}
\renewcommand*{\checkthelayout}[1]{}
\renewcommand*{\fixthelayout}{}
%
% \newlength{\stockheight}
% \newlength{\trimtop}
% \newlength{\trimedge}
% \newlength{\stockwidth}
% \newlength{\spinemargin}
% \newlength{\foremargin}
% \newlength{\uppermargin}
% \newlength{\headmargin}
%
\renewcommand*{\typeoutlayout}{}
\renewcommand*{\typeoutstandardlayout}{}
\renewcommand*{\settypeoutlayoutunit}[1]{}
\renewcommand*{\fixpdflayout}{}
\renewcommand*{\fixdvipslayout}{}

\renewcommand*{\medievalpage}[1][]{}
\renewcommand*{\isopage}[1][]{}
\renewcommand*{\semiisopage}[1][]{}

\renewcommand{\setpagebl}[3]{}
\renewcommand{\setpageml}[3]{}
\renewcommand{\setpagetl}[3]{}
\renewcommand{\setpagetm}[3]{}
\renewcommand{\setpagetr}[3]{}
\renewcommand{\setpagemr}[3]{}
\renewcommand{\setpagebr}[3]{}
\renewcommand{\setpagebm}[3]{}
\renewcommand{\setpagecc}[3]{}
```

§ 682.4 Text and fonts

```
\let\miniscule\tiny
\let\HUGE\Huge

\renewcommand*{\abnormalparskip}[1]{}
\renewcommand*{\nonzeroparskip}{}
\renewcommand*{\traditionalparskip}{}

\let\onelineskip\baselineskip

\let\OnehalfSpacing\onehalfspacing
\let\DoubleSpacing\doublespacing
\renewcommand*{\setPagenoteSpacing}[1]{}
\renewcommand*{\setFloatSpacing}[1]{}

\renewcommand{\SingleSpacing}{\@ifstar\singlespacing\singlespacing}

\let\setSingleSpace\SetSinglespace
\let\SingleSpace\singlespace
\let\endSingleSpace\endsinglespace
```

```
\let\Spacing\spacing
\let\endSpacing\endspacing
\let\OnehalfSpace\onehalfspace
\let\endOnehalfSpace\endonehalfspace
\csletcs{OnehalfSpace*}{onehalfspace}
\csletcs{endOnehalfSpace*}{endonehalfspace}
\let\DoubleSpace\doublespace
\let\endDoubleSpace\enddoublespace
\csletcs{DoubleSpace*}{doublespace}
\csletcs{endDoubleSpace*}{enddoublespace}
\renewcommand*{\setDisplayskipStretch}[1]{}
\renewcommand*{\memdskipstretch}{}
\renewcommand*{\noDisplayskipStretch}{}
\renewcommand*{\memdskips}{}

\renewcommand*{\midsloppy}{}
\renewenvironment*{midsloppypar}{}{}

\renewcommand*{\sloppybottom}{}
```

§ 682.5 Titles

```
\csletcs{titlingpage*}{titlingpage}
\csletcs{endtitlingpage*}{endtitlingpage}
\let\titlingpageend\relax
\newcommand{\titlingpageend}[2]{}
\let\andnext\and
\renewcommand*{\thanksmarkstyle}[1]{}

\renewcommand{\thanksfootmark}{%
    \thanksscript{\tamark}%
}

% \newlength{\thanksmarksep}% already provided by memoir

\renewcommand\titlingpageend[2]{}
```

§ 682.6 Abstracts

```
% \newlength{\absindent}
% \newlength{\absparsep}
\renewcommand*{\abstractcol}{}
\renewcommand*{\abstractintoc}{}
\renewcommand*{\abstractnum}{}
\renewcommand*{\abstractrunin}{}
```

§ 682.7 Docment divisions

\book * (⟨*2:PDF name*⟩) [⟨*3:TOC name*⟩] [⟨*4:PDF name*⟩] (⟨*5:PDF name*⟩) {⟨*6:name*⟩}

```
\DeclareDocumentCommand{\book}{s d() o o d() m}{%
    \LWR@section{#1}{#3}{#6}{book}%
}

\def\@apppage{%
```

```
    \part*{\appendixpagename}
}
\renewcommand\mempreaddapppagetotochook{}
\renewcommand\mempostaddapppagetotochook{}

\def\@sapppage{%
    \part*{\appendixpagename}
}


\DeclareDocumentCommand{\mainmatter}{s}{%
    \booltrue{LWR@mainmatter}%
}

\DeclareDocumentCommand{\frontmatter}{s}{%
    \boolfalse{LWR@mainmatter}%
}


\renewcommand*{\raggedbottomsection}{}
\renewcommand*{\normalbottomsection}{}
\renewcommand*{\bottomsectionskip}{}
\renewcommand*{\bottomsectionpenalty}{}
\csletcs{appendixpage*}{appendixpage}
\renewcommand*{\namedsubappendices}{}
\renewcommand*{\unnamedsubappendices}{}
\renewcommand*{\beforebookskip}{}
\renewcommand*{\afterbookskip}{}
\renewcommand*{\beforepartskip}{}
\renewcommand*{\afterpartskip}{}
\renewcommand*{\midbookskip}{}
\renewcommand*{\midpartskip}{}
\renewcommand*{\printbookname}{}
\renewcommand*{\booknamefont}{}
\renewcommand*{\booknamenum}{}
\renewcommand*{\printbooknum}{}
\renewcommand*{\booknumfont}{}
\renewcommand*{\printpartname}{}
\renewcommand*{\partnamefont}{}
\renewcommand*{\partnamenum}{}
\renewcommand*{\printpartnum}{}
\renewcommand*{\partnumfont}{}
\renewcommand*{\printbooktitle}[1]{}
\renewcommand*{\booktitlefont}{}
\renewcommand{\printparttitle}[1]{}
\renewcommand*{\parttitlefont}{}
\renewcommand*{\bookpageend}{}
\renewcommand*{\bookblankpage}{}
\renewcommand*{\nobookblankpage}{}
\renewcommand*{\partpageend}{}
\renewcommand*{\partblankpage}{}
\renewcommand*{\nopartblankpage}{}
\RenewDocumentCommand{\newleadpage}{s o m m}{}% todo
\RenewDocumentCommand{\renewleadpage}{s o m m}{}% todo
\renewcommand*{\leadpagetoclevel}{chapter}

\renewcommand*{\openright}{}
```

```
\renewcommand*{\openleft}{}
\renewcommand*{\openany}{}
\renewcommand*{\clearforchapter}{}
\renewcommand*{\memendofchapterhook}{}
\renewcommand*{\chapterheadstart}{}
% \newlength{\beforechapskip}
\renewcommand*{\afterchapternum}{}
% \newlength{\midchapskip}
\renewcommand*{\afterchaptertitle}{}
% \newlength{\afterchapskip}
\renewcommand*{\printchaptername}{}
\renewcommand*{\chapnamefont}{}
\renewcommand*{\chapternamenum}{}
\renewcommand*{\printchapternum}{}
\renewcommand*{\chapnumfont}{}
\renewcommand{\printchaptertitle}[1]{}
\renewcommand*{\chaptitlefont}{}
\renewcommand*{\printchapternonum}{}
\renewcommand*{\indentafterchapter}{}
\renewcommand*{\noindentafterchapter}{}
\renewcommand*{\insertchapterspace}{}

\renewcommand*{\chapterstyle}[1]{}
\renewcommand{\makechapterstyle}[2]{}
\renewcommand*{\chapindent}{}
\let\chapterprecis\cftchapterprecis
\let\chapterprecishere\cftchapterprecishere
\let\chapterprecistoc\cftchapterprecistoc
\renewcommand*{\precisfont}{}
\renewcommand*{\prechapterprecis}{}
\renewcommand*{\postchapterprecis}{}
\renewcommand{\precistoctext}[1]{}
\renewcommand*{\precistocfont}{}
\renewcommand*{\precistocformat}{}
% \newlength{\prechapterprecisshift}

\renewcommand*{\setbeforesecskip}[1]{}
\renewcommand*{\setaftersecskip}[1]{}
\renewcommand*{\setsecindent}[1]{}
\renewcommand*{\setsecheadstyle}[1]{}
\renewcommand*{\setbeforesubsecskip}[1]{}
\renewcommand*{\setaftersubsecskip}[1]{}
\renewcommand*{\setsubsecindent}[1]{}
\renewcommand*{\setsubsecheadstyle}[1]{}
\renewcommand*{\setbeforesubsubsecskip}[1]{}
\renewcommand*{\setaftersubsubsecskip}[1]{}
\renewcommand*{\setsubsubsecindent}[1]{}
\renewcommand*{\setsubsubsecheadstyle}[1]{}
\renewcommand*{\setbeforeparaskip}[1]{}
\renewcommand*{\setafterparaskip}[1]{}
\renewcommand*{\setparaindent}[1]{}
\renewcommand*{\setparaheadstyle}[1]{}
\renewcommand*{\setbeforesubparaskip}[1]{}
\renewcommand*{\setaftersubparaskip}[1]{}
\renewcommand*{\setsubparaindent}[1]{}
```

```
\renewcommand*{\setsubparaheadstyle}[1]{}
\renewcommand{\@hangfrom}[1]{#1}
\renewcommand{\sethangfrom}[1]{}
\renewcommand{\setsecnumformat}[1]{}

\renewcommand*{\hangsecnum}{}
\renewcommand*{\defaultsecnum}{}

\renewcommand*{\sechook}{}
\renewcommand{\setsechook}[1]{}
\renewcommand*{\subsechook}{}
\renewcommand{\setsubsechook}[1]{}
\renewcommand*{\subsubsechook}{}
\renewcommand{\setsubsubsechook}[1]{}
\renewcommand*{\parahook}{}
\renewcommand{\setparahook}[1]{}
\renewcommand*{\subparahook}{}
\renewcommand{\setsubparahook}[1]{}

\RenewDocumentCommand{\plainbreak}{s m}{\begin{center}~\end{center}}

\RenewDocumentCommand{\fancybreak}{s +m}{%
    \begin{center}#2\end{center}%
}

\RenewDocumentCommand{\plainfancybreak}{s m m +m}{%
    \begin{center}#4\end{center}%
}

\RenewDocumentCommand{\pfbreak}{s}{%
    \begin{center}
    \pfbreakdisplay
    \end{center}
}

% \newlength{\pfbreakskip}
\renewcommand{\pfbreakdisplay}{*\quad*\quad*}

\renewcommand{\makeheadstyles}[2]{}
\renewcommand*{\headstyles}[1]{}
```

§ 682.8 Pagination and headers

```
\renewcommand*{\savepagenumber}{}
\renewcommand*{\restorepagenumber}{}
\renewcommand*{\uppercaseheads}{}
\renewcommand*{\nouppercaseheads}{}

\renewcommand*{\bookpagemark}[1]{}
\renewcommand*{\partmark}[1]{}
\renewcommand*{\bibmark}{}
\renewcommand*{\indexmark}{}
\renewcommand*{\glossarymark}{}

\LWR@origpagestyle{empty}
\renewcommand*{\ps@empty}{}
```

```
\renewcommand*{\makepagestyle}[1]{}
\renewcommand*{\emptypshook}{}%
% \renewcommand*{\empty@oddhead}{}
% \renewcommand*{\empty@oddfoot}{}
% \renewcommand*{\empty@evenhead}{}
% \renewcommand*{\empty@evenfoot}{}
\renewcommand*{\@oddhead}{}
\renewcommand*{\@oddfoot}{}
\renewcommand*{\@evenhead}{}
\renewcommand*{\@evenfoot}{}
\renewcommand*{\aliaspagestyle}[2]{}
\renewcommand*{\copypagestyle}[2]{}

\renewcommand*{\makeevenhead}[4]{}
\renewcommand*{\makeoddhead}[4]{}
\renewcommand*{\makeevenfoot}[4]{}
\renewcommand*{\makeoddfoot}[4]{}
\renewcommand*{\makerunningwidth}[3]{}
% \newlength{\headwidth}
\renewcommand*{\makeheadrule}[3]{}
\renewcommand*{\makefootrule}[3]{}
\renewcommand*{\makeheadfootruleprefix}[3]{}
% \newlength{\normalrulethickness}
% \setlength{\normalrulethickness}{.4pt}
% \newlength{\footruleheight}
% \newlength{\footruleskip}
\renewcommand*{\makeheadposition}[5]{}
\renewcommand{\makepsmarks}[2]{}
\renewcommand*{\makeheadfootstrut}[3]{}

\renewcommand{\createmark}[5]{\csdef{#1mark}[1]{}}
\renewcommand{\createplainmark}[3]{\csdef{#1mark}{}}

\renewcommand{\memUChead}[1]{}
\renewcommand*{\clearplainmark}[1]{}
\renewcommand*{\clearmark}[1]{}
\renewcommand{\addtopsmarks}[3]{}
\renewcommand{\ifonlyfloats}[2]{#2}
\renewcommand*{\mergepagefloatstyle}[3]{}

\renewcommand*{\framepichead}{}
\renewcommand*{\framepictextfoot}{}
\renewcommand*{\framepichook}{}
\renewcommand*{\showheadfootlocoff}{}
\renewcommand*{\showtextblocklocoff}{}
```

§ 682.9 Paragraphs and lists

```
\renewcommand{\hangfrom}[1]{#1}
\let\centerfloat\centering
\renewcommand*{\raggedyright}[1][]{}
% \newlength{\ragrparindent}
\renewcommand{\sourceatright}[2][]{\attribution{#2}}
\let\memorigdbs\LWR@endofline
\let\memorigpar\par
\let\atcentercr\LWR@endofline
```

```
\renewcommand*{\linenottooshort}[1][]{}
\renewcommand*{\russianpar}{}
\renewcommand*{\lastlinerulefill}{}
\renewcommand*{\lastlineparrule}{}
\renewcommand*{\justlastraggedleft}{}
\renewcommand*{\raggedrightthenleft}{}
\renewcommand*{\leftcenterright}{}

\renewcommand{\leftspringright}[4]{%
    \begin{minipage}{#1\linewidth}#3\end{minipage}\qquad%
  \begin{minipage}{#2\linewidth}\begin{flushright}#4\end{flushright}\end{minipage}%
}

\renewenvironment*{blockdescription}
{\LWR@descriptionstart\LWR@origdescription}
{\enddescription}

\renewcommand*{\blockdescriptionlabel}[1]{\textbf{#1}}
\renewenvironment*{labelled}[1]{\begin{description}}{\end{description}}
\renewenvironment*{flexlabelled}[6]{\begin{description}}{\end{description}}
\renewcommand*{\tightlists}{}
\renewcommand*{\defaultlists}{}
\RenewDocumentCommand{\firmlists}{s}{}
\renewcommand*{\firmlist}{}
\renewcommand*{\tightlist}{}
\renewcommand*{\zerotrivseps}{}
\renewcommand*{\savetrivseps}{}
\renewcommand*{\restoretrivseps}{}
```

§ 682.10 Contents lists

```
\csletcs{tableofcontents*}{tableofcontents}
\csletcs{listoffigures*}{listoffigures}
\csletcs{listoftables*}{listoftables}
\renewenvironment{KeepFromToc}{}{}
\renewcommand*{\onecoltocetc}{}
\renewcommand*{\twocoltocetc}{}
\renewcommand*{\ensureonecol}{}
\renewcommand*{\restorefromonecol}{}
\renewcommand*{\doccoltocetc}{}

\renewcommand{\tocheadstart}{}
\renewcommand{\printtoctitle}[1]{}
\renewcommand{\tocmark}{}
\renewcommand{\aftertoctitle}{}
\renewcommand{\lofheadstart}{}
\renewcommand{\printloftitle}[1]{}
\renewcommand{\lofmark}{}
\renewcommand{\afterloftitle}{}
\renewcommand{\lotheadstart}{}
\renewcommand{\printlottitle}[1]{}
\renewcommand{\lotmark}{}
\renewcommand{\afterlottitle}{}

\renewcommand*{\setpnumwidth}[1]{}
```

```
\renewcommand*{\setrmarg}[1]{}
\renewcommand*{\cftbookbreak}{}
\renewcommand*{\cftpartbreak}{}
\renewcommand*{\cftchapterbreak}{}

% \newlength{\cftbeforebookskip}
% \newlength{\cftbookindent}
% \newlength{\cftbooknumwidth}
\renewcommand*{\cftbookfont}{}
\renewcommand*{\cftbookname}{}
\renewcommand*{\cftbookpresnum}{}
\renewcommand*{\cftbookaftersnum}{}
\renewcommand*{\cftbookaftersnumb}{}
\renewcommand*{\cftbookleader}{}
\renewcommand*{\cftbookdotsep}{1}
\renewcommand*{\cftbookpagefont}{}
\renewcommand*{\cftbookafterpnum}{}
\renewcommand*{\cftbookformatpnum}[1]{}
\renewcommand*{\cftbookformatpnumhook}[1]{}
```

Part is already defined by tocloft.

```
% \newlength{\cftbeforechapterskip}
% \newlength{\cftchapterindent}
% \newlength{\cftchapternumwidth}
\renewcommand*{\cftchapterfont}{}
\renewcommand*{\cftchaptername}{}
\renewcommand*{\cftchapterpresnum}{}
\renewcommand*{\cftchapteraftersnum}{}
\renewcommand*{\cftchapteraftersnumb}{}
\renewcommand*{\cftchapterleader}{}
\renewcommand*{\cftchapterdotsep}{1}
\renewcommand*{\cftchapterpagefont}{}
\renewcommand*{\cftchapterafterpnum}{}
\renewcommand*{\cftchapterformatpnum}[1]{}
\renewcommand*{\cftchapterformatpnumhook}[1]{}

% \newlength{\cftbeforesectionskip}
% \newlength{\cftsectionindent}
% \newlength{\cftsectionnumwidth}
\renewcommand*{\cftsectionfont}{}
\renewcommand*{\cftsectionname}{}
\renewcommand*{\cftsectionpresnum}{}
\renewcommand*{\cftsectionaftersnum}{}
\renewcommand*{\cftsectionaftersnumb}{}
\renewcommand*{\cftsectionleader}{}
\renewcommand*{\cftsectiondotsep}{1}
\renewcommand*{\cftsectionpagefont}{}
\renewcommand*{\cftsectionafterpnum}{}
\renewcommand*{\cftsectionformatpnum}[1]{}
\renewcommand*{\cftsectionformatpnumhook}[1]{}

% \newlength{\cftbeforesubsectionskip}
% \newlength{\cftsubsectionindent}
% \newlength{\cftsubsectionnumwidth}
\renewcommand*{\cftsubsectionfont}{}
```

```
\renewcommand*{\cftsubsectionname}{}
\renewcommand*{\cftsubsectionpresnum}{}
\renewcommand*{\cftsubsectionaftersnum}{}
\renewcommand*{\cftsubsectionaftersnumb}{}
\renewcommand*{\cftsubsectionleader}{}
\renewcommand*{\cftsubsectiondotsep}{1}
\renewcommand*{\cftsubsectionpagefont}{}
\renewcommand*{\cftsubsectionafterpnum}{}
\renewcommand*{\cftsubsectionformatpnum}[1]{}
\renewcommand*{\cftsubsectionformatpnumhook}[1]{}

% \newlength{\cftbeforesubsubsectionskip}
% \newlength{\cftsubsubsectionindent}
% \newlength{\cftsubsubsectionnumwidth}
\renewcommand*{\cftsubsubsectionfont}{}
\renewcommand*{\cftsubsubsectionname}{}
\renewcommand*{\cftsubsubsectionpresnum}{}
\renewcommand*{\cftsubsubsectionaftersnum}{}
\renewcommand*{\cftsubsubsectionaftersnumb}{}
\renewcommand*{\cftsubsubsectionleader}{}
\renewcommand*{\cftsubsubsectiondotsep}{1}
\renewcommand*{\cftsubsubsectionpagefont}{}
\renewcommand*{\cftsubsubsectionafterpnum}{}
\renewcommand*{\cftsubsubsectionformatpnum}[1]{}
\renewcommand*{\cftsubsubsectionformatpnumhook}[1]{}

% \newlength{\cftbeforeparagraphskip}
% \newlength{\cftparagraphindent}
% \newlength{\cftparagraphnumwidth}
\renewcommand*{\cftparagraphfont}{}
\renewcommand*{\cftparagraphname}{}
\renewcommand*{\cftparagraphpresnum}{}
\renewcommand*{\cftparagraphaftersnum}{}
\renewcommand*{\cftparagraphaftersnumb}{}
\renewcommand*{\cftparagraphleader}{}
\renewcommand*{\cftparagraphdotsep}{1}
\renewcommand*{\cftparagraphpagefont}{}
\renewcommand*{\cftparagraphafterpnum}{}
\renewcommand*{\cftparagraphformatpnum}[1]{}
\renewcommand*{\cftparagraphformatpnumhook}[1]{}

% \newlength{\cftbeforesubparagraphskip}
% \newlength{\cftsubparagraphindent}
% \newlength{\cftsubparagraphnumwidth}
\renewcommand*{\cftsubparagraphfont}{}
\renewcommand*{\cftsubparagraphname}{}
\renewcommand*{\cftsubparagraphpresnum}{}
\renewcommand*{\cftsubparagraphaftersnum}{}
\renewcommand*{\cftsubparagraphaftersnumb}{}
\renewcommand*{\cftsubparagraphleader}{}
\renewcommand*{\cftsubparagraphdotsep}{1}
\renewcommand*{\cftsubparagraphpagefont}{}
\renewcommand*{\cftsubparagraphafterpnum}{}
\renewcommand*{\cftsubparagraphformatpnum}[1]{}
\renewcommand*{\cftsubparagraphformatpnumhook}[1]{}
```

```
% \newlength{\cftbeforefigureskip}
% \newlength{\cftfigureindent}
% \newlength{\cftfigurenumwidth}
\renewcommand*{\cftfigurefont}{}
\renewcommand*{\cftfigurename}{}
\renewcommand*{\cftfigurepresnum}{}
\renewcommand*{\cftfigureaftersnum}{}
\renewcommand*{\cftfigureaftersnumb}{}
\renewcommand*{\cftfigureleader}{}
\renewcommand*{\cftfiguredotsep}{1}
\renewcommand*{\cftfigurepagefont}{}
\renewcommand*{\cftfigureafterpnum}{}
\renewcommand*{\cftfigureformatpnum}[1]{}
\renewcommand*{\cftfigureformatpnumhook}[1]{}

% \newlength{\cftbeforesubfigureskip}
% \newlength{\cftsubfigureindent}
% \newlength{\cftsubfigurenumwidth}
\newcommand*{\cftsubfigurefont}{}
\newcommand*{\cftsubfigurename}{}
\newcommand*{\cftsubfigurepresnum}{}
\newcommand*{\cftsubfigureaftersnum}{}
\newcommand*{\cftsubfigureaftersnumb}{}
\newcommand*{\cftsubfigureleader}{}
\newcommand*{\cftsubfiguredotsep}{1}
\newcommand*{\cftsubfigurepagefont}{}
\newcommand*{\cftsubfigureafterpnum}{}
\newcommand*{\cftsubfigureformatpnum}[1]{}
\newcommand*{\cftsubfigureformatpnumhook}[1]{}

% \newlength{\cftbeforetableskip}
% \newlength{\cfttableindent}
% \newlength{\cfttablenumwidth}
\renewcommand*{\cfttablefont}{}
\renewcommand*{\cfttablename}{}
\renewcommand*{\cfttablepresnum}{}
\renewcommand*{\cfttableaftersnum}{}
\renewcommand*{\cfttableaftersnumb}{}
\renewcommand*{\cfttableleader}{}
\renewcommand*{\cfttabledotsep}{1}
\renewcommand*{\cfttablepagefont}{}
\renewcommand*{\cfttableafterpnum}{}
\renewcommand*{\cfttableformatpnum}[1]{}
\renewcommand*{\cfttableformatpnumhook}[1]{}

% \newlength{\cftbeforesubtableskip}
% \newlength{\cftsubtableindent}
% \newlength{\cftsubtablenumwidth}
\newcommand*{\cftsubtablefont}{}
\newcommand*{\cftsubtablename}{}
\newcommand*{\cftsubtablepresnum}{}
\newcommand*{\cftsubtableaftersnum}{}
\newcommand*{\cftsubtableaftersnumb}{}
\newcommand*{\cftsubtableleader}{}
\newcommand*{\cftsubtabledotsep}{1}
\newcommand*{\cftsubtablepagefont}{}
```

```
\newcommand*{\cftsubtableafterpnum}{}
\newcommand*{\cftsubtableformatpnum}[1]{}
\newcommand*{\cftsubtableformatpnumhook}[1]{}

\renewcommand*{\booknumberline}[1]{}
\renewcommand*{\partnumberline}[1]{}
\renewcommand*{\chapternumberline}[1]{}
\renewcommand*{\numberlinehook}[1]{}
% \renewcommand*{\cftwhatismyname}{}%
\renewcommand*{\booknumberlinehook}[1]{}
\renewcommand*{\partnumberlinehook}[1]{}
\renewcommand*{\chapternumberlinehook}[1]{}
\renewcommand{\numberlinebox}[2]{}
\renewcommand{\booknumberlinebox}[2]{}
\renewcommand{\partnumberlinebox}[2]{}
\renewcommand{\chapternumberlinebox}[2]{}
%
% \newlength{\cftparfillskip}
\renewcommand*{\cftpagenumbersoff}[1]{}
\renewcommand*{\cftpagenumberson}[1]{}
\renewcommand*{\cftlocalchange}[3]{}
\renewcommand*{\cftaddtitleline}[4]{}
\renewcommand*{\cftaddnumtitleline}[4]{}
\renewcommand{\cftinsertcode}[2]{}
\renewcommand{\cftinserthook}[2]{}
\renewcommand{\settocpreprocessor}[2]{}
\DeclareRobustCommand{\cftpagenumbersoff}[1]{}
\DeclareRobustCommand{\cftpagenumberson}[1]{}
```

§ 682.11 Floats and captions

\@xfloat
\@xdblfloat

Reestablish lwarp's takeover the float handing, which memoir tried to grab:

```
\AtBeginDocument{
\def\@xfloat #1[#2]{%
    \LWR@floatbegin{#1}[#2]
    \normalsize
    \@nameuse{#1adjustment}%
    \LWR@futurenonspacelet\LWR@mynexttoken\LWR@floatalignment%
}
\def\@xdblfloat #1[#2]{%
    \LWR@floatbegin{#1}[#2]
    \normalsize
    \@nameuse{#1adjustment}%
    \LWR@futurenonspacelet\LWR@mynexttoken\LWR@floatalignment%
}
}
```

\newfloat [⟨*1: within*⟩] {⟨*2: type*⟩} {⟨*3: ext*⟩} {⟨*4: capname*⟩}

```
\RenewDocumentCommand{\newfloat}{o m m m}{%
    \def\LWR@tempone{#4}%
    \def\LWR@temptwo{\@nameuse{#2name}}%
    \ifdefequal{\LWR@tempone}{\LWR@temptwo}{% recursive name, already defined
        \IfValueTF{#1}%
```

```
            {\DeclareFloatingEnvironment[fileext=#3,within=#1]{#2}}%
            {\DeclareFloatingEnvironment[fileext=#3]{#2}}%
    }{% not recursive name
        \IfValueTF{#1}%
            {\DeclareFloatingEnvironment[fileext=#3,within=#1,name={#4}]{#2}}%
            {\DeclareFloatingEnvironment[fileext=#3,name={#4}]{#2}}%
    }%
```

newfloat package automatically creates the `\listof` command for new floats, but float does not, so remove `\listof` here in case it is manually created later.

```
    \cslet{listof#2s}\relax%
    \cslet{listof#2es}\relax%
}
```

`\newlistof` `[`⟨*within*⟩`]` {⟨*type*⟩} {⟨*ext*⟩} {⟨*listofname*⟩}

Emulated through the `\newfloat` mechanism. Note that memoir uses a different syntax than tocloft for the name.

```
\RenewDocumentCommand{\newlistof}{o m m m}
{%
    \IfValueTF{#1}%
        {\newlistentry[#1]{#2}{#3}{0}}%
        {\newlistentry{#2}{#3}{0}}%
    \@namedef{ext@#2}{#3}%
    \@ifundefined{c@#3depth}{\newcounter{#3depth}}{}%
    \setcounter{#3depth}{1}%
    \@namedef{#3mark}{}%
    \@namedef{#2}{\LWR@listof{#2}{#4}}%
    \@namedef{@cftmake#3title}{}%
    \@ifundefined{cftbefore#3titleskip}{%
        \expandafter\newlength\csname cftbefore#3titleskip\endcsname%
        \expandafter\newlength\csname cftafter#3titleskip\endcsname%
    }{}%
    \@namedef{cft#3titlefont}{}%
    \@namedef{cftafter#3title}{}%
    \@namedef{cft#3prehook}{}%
    \@namedef{cft#3posthook}{}%
}

\renewcommand{\setfloatadjustment}[2]{}
```

Borrowed from the lwarp version of keyfloat:

```
\NewDocumentEnvironment{KFLTmemoir@marginfloat}{O{-1.2ex} m}
{% start
   \LWR@BlockClassWP{float:right; width:2in; margin:10pt}{}(note){marginblock}%
    \renewcommand*{\@captype}{#2}%
}
{%
    \endLWR@BlockClassWP%
}

\DeclareDocumentEnvironment{marginfigure}{o}
  {\begin{KFLTmemoir@marginfloat}{figure}}
```

```
  {\end{KFLTmemoir@marginfloat}}

\DeclareDocumentEnvironment{margintable}{o}
  {\begin{KFLTmemoir@marginfloat}{table}}
  {\end{KFLTmemoir@marginfloat}}

\renewcommand{\setmarginfloatcaptionadjustment}[2]{}
\renewcommand{\setmpjustification}[2]{}
\renewcommand*{\mpjustification}{}
\renewcommand*{\setfloatlocations}[2]{}
\DeclareDocumentCommand{\suppressfloats}{o}{}
\renewcommand*{\FloatBlock}{}
\renewcommand*{\FloatBlockAllowAbove}{}
\renewcommand*{\FloatBlockAllowBelow}{}
\renewcommand*{\setFloatBlockFor}{}

\renewcommand{\captiontitlefinal}[1]{}
```

`\flegtable`, `\flegfigure`, `\flegtoctable`, `\flegtocfigure` are defined by memoir using `\newfloat`. These are defined with an `@` in ccaption.

```
\renewcommand{\flegtable}{\tablename}
\renewcommand{\flegfigure}{\figurename}
\renewcommand{\flegtoctable}{}
\renewcommand{\flegtocfigure}{}


\renewcommand{\@makesubfloatcaption}[2]{%
    \minipagefullwidth
    \begin{minipage}{\linewidth}%
    #1 \ignorespaces #2 \unskip%
    \end{minipage}
}

\renewcommand*{\tightsubcaptions}{}
\renewcommand*{\loosesubcaptions}{}

\renewcommand*{\subcaptionsize}[1]{}
\renewcommand*{\subcaptionlabelfont}[1]{}
\renewcommand*{\subcaptionfont}[1]{}
\renewcommand*{\subcaptionstyle}[1]{}

\renewcommand*{\hangsubcaption}{}
\renewcommand*{\shortsubcaption}{}
\renewcommand*{\normalsubcaption}{}

\RenewDocumentEnvironment{sidecaption}{o m o}
{}
{%
    \IfValueTF{#1}{\caption[#1]{#2}}{\caption{#2}}%
    \IfValueT{#3}{\label{#3}}%
}

% \newlength{\sidecapwidth}
% \newlength{\sidecapsep}
```

```
\renewcommand*{\setsidecaps}[2]{}
\renewcommand*{\sidecapmargin}[1]{}
% \newif\ifscapmargleft
\scapmargleftfalse
\renewcommand*{\setsidecappos}[1]{}
```

Env sidecontcaption

```
\RenewDocumentEnvironment{sidecontcaption}{m o}
{}
{%
    \ifdef{\ContinuedFloat}%
        {\ContinuedFloat}%
        {\addtocounter{\@captype}{-1}}%
    \caption{#1}%
```

Without \@captype, the section is referred to instead.

```
    \IfValueT{#2}{\label[\@captype]{#2}}%
}
```

\sidenamedlegend does not appear to use the TOC argument.

```
\renewenvironment{sidenamedlegend}[2][]{
    \begin{center}
    \@nameuse{\@captype name}\CaptionSeparator#2
    \end{center}
}
{}

\renewenvironment{sidelegend}[1]
{\begin{center}
    #1

}
{\end{center}}

\renewcommand*{\sidecapstyle}{}
\renewcommand*{\overridescapmargin}[1]{}
% \newlength{\sidecapraise}
\renewcommand*{\sidecapfloatwidth}{\linewidth}

\LetLtxMacro\ctabular\tabular
\LetLtxMacro\endctabular\endtabular

\renewcommand{\autorows}[5][]{%
    #5%
}

\renewcommand{\autocols}[5][]{%
    #5%
}
```

§ 682.12 Footnotes and page notes

```
\renewcommand*{\feetabovefloat}{}
\renewcommand*{\feetbelowfloat}{}
\renewcommand*{\feetatbottom}{}

\renewcommand*{\verbfootnote}[2][]{%
    \PackageError{lwarp,memoir}%
    {Verbatim footnotes are not yet supported by lwarp}%
    {This may be improved some day.}%
}

\renewcommand*{\plainfootnotes}{}
\renewcommand*{\twocolumnfootnotes}{}
\renewcommand*{\threecolumnfootnotes}{}
\renewcommand*{\paragraphfootnotes}{}
\renewcommand*{\footfudgefiddle}{}

\renewcommand*{\newfootnoteseries}[1]{%
    \PackageError{lwarp,memoir}%
    {Memoir footnote series are not yet supported by lwarp}%
    {This may be improved some day.}%
}

\renewcommand*{\plainfootstyle}[1]{}
\renewcommand*{\twocolumnfootstyle}[1]{}
\renewcommand*{\threecolumnfootstyle}[1]{}
\renewcommand*{\paragraphfootstyle}[1]{}

\renewcommand*{\footfootmark}{}
\renewcommand*{\footmarkstyle}[1]{}

% \newlength{\footmarkwidth}
% \newlength{\footmarksep}
% \newlength{\footparindent}

\renewcommand*{\foottextfont}{}

\renewcommand*{\marginparmargin}[1]{}
\renewcommand*{\sideparmargin}[1]{}

\LetLtxMacro\sidepar\marginpar
\renewcommand*{\sideparfont}{}
\renewcommand*{\sideparform}{}
\LWR@providelength{\sideparvshift}

\renewcommand*{\parnopar}{}

\renewcommand{\sidebar}[1]{\begin{quote}#1\end{quote}}
\renewcommand*{\sidebarmargin}[1]{}
\renewcommand*{\sidebarfont}{}
\renewcommand*{\sidebarform}{}
% \newlength{\sidebarhsep}
% \newlength{\sidebarvsep}
% \newlength{\sidebarwidth}
% \newlength{\sidebartopsep}
```

```
\renewcommand{\setsidebarheight}[1]{}
\renewcommand*{\setsidebars}[6]{}
\renewcommand*{\footnotesatfoot}{}
\renewcommand*{\footnotesinmargin}{}

\LetLtxMacro\sidefootnote\footnote
\LetLtxMacro\sidefootnotemark\footnotemark
\LetLtxMacro\sidefootnotetext\footnotetext

\renewcommand*{\sidefootmargin}[1]{}
% \newlength{\sidefoothsep}
% \newlength{\sidefootvsep}
% \newlength{\sidefootwidth}
% \newlength{\sidefootadjust}
% \newlength{\sidefootheight}
\renewcommand*{\setsidefootheight}[1]{}
% \renewcommand*{\sidefootfont}{}% in docs but not in the package
\renewcommand*{\setsidefeet}[6]{}
\renewcommand*{\sidefootmarkstyle}[1]{}
\renewcommand*{\sidefoottextfont}{}
\renewcommand*{\sidefootform}{}

\renewcommand*{\continuousnotenums}{\pncontopttrue}% from pagenote
\renewcommand*{\notepageref}{}
\renewcommand*{\prenotetext}{}
\renewcommand*{\postnotetext}{}
\LetLtxMacro\printpageinnoteshyperref\printpageinnotes
\renewcommand*{\foottopagenote}{}
\renewcommand*{\pagetofootnote}{}
```

\m@m@wrpnote

\startnoteentrystart

To have cleveref work with page note labels, the following patch writes \thepagenote and also adds \arabic{pagenote} to the first argument written to the .ent file:

```
\startnoteentry{{\thepagenote}{\arabic{pagenote}}} . . .
```

The arabic value is required for cleveref. \thepagenote becomes \@firstoftwo#1 and the arabic value becomes \@secondoftwo#1.

⚠ \nameref

Note that for print mode,\nameref print the section name where the page notes are declared in the text, but for HTML it prints the name where the page notes are printed.

```
\xpatchcmd{\m@m@wrpnote}
    {\string\startnoteentry{\thepagenote}}
    {\string\startnoteentry{{\thepagenote}{\arabic{pagenote}}}}
    {}
    {\LWR@patcherror{memoir}{m@m@wrpnote}}

\renewcommand\startnoteentrystart[4]{%
  \prenoteinnotes%
  \noteidinnotes{\@firstoftwo#1}{#2}%
  \@ifmtarg{#2}{%
%         \phantomsection\def\@currentlabel{#1}%            original
        \def\@currentlabel{\@firstoftwo#1}%                 lwarp
        \def\cref@currentlabel{%                            lwarp
            [pagenote][\@secondoftwo#1][]\@firstoftwo#1%    lwarp
```

```
        }%                                                          lwarp
  }{}%
  \pagenoteanchor{#4}%
  \pageinnotes{#3}%
  \prenotetext%
}
```

§ 682.13 Decorative text

```
\renewcommand*{\epigraphposition}[1]{}
\renewcommand*{\epigraphtextposition}[1]{}
\renewcommand*{\epigraphsourceposition}[1]{}
\renewcommand*{\epigraphfontsize}[1]{}
\renewcommand*{\epigraphforheader}[2][]{}
\renewcommand*{\epigraphpicture}{}
```

§ 682.14 Poetry

```
\renewcommand*{\vinphantom}{}
\renewcommand*{\vleftofline}[1]{#1}
% \let\linenumberfrequency\poemlines
% \renewcommand*{\linenumberfont}[1]{}

\DeclareDocumentCommand{\PoemTitle}{s o o m}{%
    \IfValueTF{#2}%
        {\poemtitle[#2]{#4}}%
        {\poemtitle{#4}}%
}

\renewcommand*{\NumberPoemTitle}{}
\renewcommand*{\PlainPoemTitle}{}
\renewcommand*{\poemtitlepstyle}{}
\renewcommand*{\poemtitlestarmark}[1]{}
\renewcommand*{\poemtitlestarpstyle}{}
\renewcommand*{\PoemTitleheadstart}{}
\renewcommand*{\printPoemTitlenonum}{}
\renewcommand*{\printPoemTitlenum}{}
\renewcommand*{\afterPoemTitlenum}{}
\renewcommand*{\printPoemTitletitle}[1]{}
\renewcommand*{\afterPoemTitle}{}
\newlength{\midpoemtitleskip}
\renewcommand*{\PoemTitlenumfont}{}
\renewcommand*{\PoemTitlefont}{}
```

§ 682.15 Boxes, verbatims and files

```
\renewenvironment{qframe}{\framed}{\endframed}
\renewenvironment{qshade}{\shaded}{\endshaded}

\renewcommand*{\setverbatimfont}[1]{}
\renewcommand*{\tabson}[1]{}
\renewcommand*{\tabsoff}{}
\renewcommand*{\wrappingon}{}
\renewcommand*{\wrappingoff}{}
\renewcommand*{\verbatimindent}{}
```

```
\renewcommand*{\verbatimbreakchar}[1]{}

\DefineVerbatimEnvironment{fboxverbatim}{Verbatim}{frame=single}
```

boxedverbatim is already defined by moreverb. boxedverbatim* does not appear to work at all, even in a minimal print memoir document.

```
\renewcommand*{\bvbox}{}
\renewcommand*{\bvtopandtail}{}
\renewcommand*{\bvsides}{}
\renewcommand*{\nobvbox}{}
% \newlength\bvboxsep
\renewcommand*{\bvtoprulehook}{}
\renewcommand*{\bvtopmidhook}{}
\renewcommand*{\bvendrulehook}{}
\renewcommand*{\bvleftsidehook}{}
\renewcommand*{\bvrightsidehook}{}
\renewcommand*{\bvperpagetrue}{}
\renewcommand*{\bvperpagefalse}{}
\renewcommand{\bvtopofpage}[1]{}
\renewcommand{\bvendofpage}[1]{}
\renewcommand*{\linenumberfrequency}[1]{}
\renewcommand*{\resetbvlinenumber}{}
\renewcommand*{\setbvlinenums}[2]{}
\renewcommand*{\linenumberfont}[1]{}
\renewcommand*{\bvnumbersinside}{}
\renewcommand*{\bvnumbersoutside}{}
```

§ 682.16 Cross referencing

```
\renewcommand*{\fref}[1]{\cref{#1}}
\renewcommand*{\tref}[1]{\cref{#1}}
\renewcommand*{\pref}[1]{\cpageref{#1}}
\renewcommand*{\Aref}[1]{\cref{#1}}
\renewcommand*{\Bref}[1]{\cref{#1}}
\renewcommand*{\Pref}[1]{\cref{#1}}
\renewcommand*{\Sref}[1]{\cref{#1}}
\renewcommand*{\figurerefname}{Figure}
\renewcommand*{\tablerefname}{Table}
\renewcommand*{\pagerefname}{page}
\renewcommand*{\bookrefname}{Book~}
\renewcommand*{\partrefname}{Part~}
\renewcommand*{\chapterrefname}{Chapter~}
\renewcommand*{\sectionrefname}{\S}
\renewcommand*{\appendixrefname}{Appendix~}
\LetLtxMacro\titleref\nameref
\renewcommand*{\headnameref}{}
\renewcommand*{\tocnameref}{}

\providecounter{LWR@currenttitle}

\renewcommand*{\currenttitle}{%
    \addtocounter{LWR@currenttitle}{1}%
    \label{currenttitle\arabic{LWR@currenttitle}}%
    \nameref{currenttitle\arabic{LWR@currenttitle}}%
}
```

```
\renewcommand*{\theTitleReference}[2]{}
\renewcommand*{\namerefon}{}
\renewcommand*{\namerefoff}{}
```

§ 682.17 Back matter

\@@wrindexhyp Redefined to write the LWR@autoindex counter instead of page. Note that memoir has two versions, depending on the use of hyperref.

```
\AtBeginDocument{

\def\@@wrindexhyp#1||\\{%
    \addtocounter{LWR@autoindex}{1}%
    \label{LWRindex-\arabic{LWR@autoindex}}%
%     \ifshowindexmark\@showidx{#1}\fi
    \protected@write\@auxout{}%
%         {\string\@@wrindexm@m{\@idxfile}{#1}{\thepage}}%
        {\string\@@wrindexm@m{\@idxfile}{#1}{\arabic{LWR@autoindex}}}%
    \endgroup
    \@esphack}%
```

\@@wrspindexhyp \specialindex behaves like a regular \index, pointing to where \specialindex is used. If \specialindex is used inside a figure or table after the \caption, then the hyperlink will be given the name of that particular figure or table.

```
\def\@@wrspindexhyp#1||\\{%
    \addtocounter{LWR@autoindex}{1}%
    \label{LWRindex-\arabic{LWR@autoindex}}%
%     \ifshowindexmark\@showidx{#1}\fi
    \protected@write\@auxout{}%
%         {\string\@@wrindexm@m{\@idxfile}{#1}{\@nameuse{the\@sptheidx}}}%
        {\string\@@wrindexm@m{\@idxfile}{#1}{\arabic{LWR@autoindex}}}%
    \endgroup
    \@esphack}%

}% \AtBeginDocument
```

\@spindex Patched to append _html to the file:

```
\renewcommand{\@spindex}[2]{%
  \@ifundefined{#1@idxfile}%
  {\ifreportnoidxfile
     \@memwarn{Undefined index file #1}%
    \fi
    \begingroup
    \@sanitize
    \@nowrindex}%
  {\def\@idxfile{#1_html}%
   \def\@sptheidx{#2}%
   \begingroup
   \@sanitize
   \@wrspindex}}
```

\makeindex Patched to use _html filename and \BaseJobname:

```
\catcode`\_=12%
\renewcommand*{\makeindex}[1][\BaseJobname]{%
  \if@filesw
    \def\gindex{\@bsphack%
      \@ifnextchar [{\@index}{\@index[\BaseJobname]}}
    \def\specialindex{\@bsphack\@spindex}%
    \makememindexhook
    \expandafter\newwrite\csname #1@idxfile\endcsname
   \expandafter\immediate\openout \csname #1@idxfile\endcsname #1_html.idx\relax
    \typeout{Writing index file #1_html.idx }%
  \fi}
\catcode`\_=8%
```

\printindex Patched to use _html filename and \BaseJobname. This will later be patched by the lwarp core.

```
\catcode`\_=12%
\renewcommand{\printindex}[1][\BaseJobname]{\@input@{#1_html.ind}}
\catcode`\_=8%
```

```
\DeclareDocumentCommand{\newblock}{}{}
%
\renewcommand*{\showindexmarks}{}
\renewcommand*{\hideindexmarks}{}

\renewcommand*{\xindyindex}{}
```

§ 682.18 Miscellaneous

```
\renewcommand*{\changemarks}{}
\renewcommand*{\nochangemarks}{}
\renewcommand*{\added}[1]{}
\renewcommand*{\deleted}[1]{}
\renewcommand*{\changed}[1]{}

\renewcommand*{\showtrimsoff}{}
\renewcommand*{\showtrimson}{}
\renewcommand*{\trimXmarks}{}
\renewcommand*{\trimLmarks}{}
\renewcommand*{\trimFrame}{}
\renewcommand*{\trimNone}{}
\renewcommand*\trimmarkscolor{}
\renewcommand*{\trimmarks}{}
\renewcommand*{\tmarktl}{}
\renewcommand*{\tmarktr}{}
\renewcommand*{\tmarkbr}{}
\renewcommand*{\tmarkbl}{}
\renewcommand*{\tmarktm}{}
\renewcommand*{\tmarkmr}{}
\renewcommand*{\tmarkbm}{}
\renewcommand*{\tmarkml}{}
\renewcommand*{\trimmark}{}
\renewcommand*{\quarkmarks}{}
\renewcommand*{\registrationColour}[1]{}

```

```
\renewcommand*{\leavespergathering}[1]{}

\renewcommand*{\noprelistbreak}{}

\renewcommand*{\cleartorecto}{}
\renewcommand*{\cleartoverso}{}

\renewenvironment{vplace}[1][]{}{}
```

§ 682.19 ccaption emulation

```
\renewcommand*{\captiondelim}[1]{\renewcommand*{\CaptionSeparator}{#1}}
\renewcommand*{\captionnamefont}[1]{}
\renewcommand*{\captiontitlefont}[1]{}
\renewcommand*{\flushleftright}{}
\renewcommand*{\centerlastline}{}
\renewcommand*{\captionstyle}[2][]{}
\DeclareDocumentCommand{\captionwidth}{m}{}
\renewcommand*{\changecaptionwidth}{}
\renewcommand*{\normalcaptionwidth}{}
\renewcommand*{\hangcaption}{}
\renewcommand*{\indentcaption}[1]{}
\renewcommand*{\normalcaption}{}
\renewcommand{\precaption}[1]{}
\renewcommand{\postcaption}[1]{}
\renewcommand{\midbicaption}[1]{}
\renewcommand{\contcaption}[1]{%
%   \ContinuedFloat%
%   \caption{#1}%
    \begin{LWR@figcaption}% later becomes \caption*
    \LWR@isolate{\@nameuse{\@captype name}}~%
    \thechapter.\the\value{\@captype}\CaptionSeparator\LWR@isolate{#1}%
    \end{LWR@figcaption}%
}

\newlength{\abovelegendskip}
\setlength{\abovelegendskip}{0.5\baselineskip}
\newlength{\belowlegendskip}
\setlength{\belowlegendskip}{\abovelegendskip}
```

The extra \\ here forces a <br> in HTML when \legend is used in a \marginpar.

```
\renewcommand{\legend}[1]{\begin{center}#1\\\end{center}}

\renewcommand{\namedlegend}[2][]{%
    \begin{center}
    \@nameuse{fleg\@captype}\CaptionSeparator#2\\
    \end{center}
    \@nameuse{flegtoc\@captype}{#1}
}
```

\flegtable, \flegfigure, \flegtoctable, \flegtocfigure are defined by memoir using \newfloat. These are defined with an @ in ccaption.

```
\renewcommand{\newfixedcaption}[3][\caption]{%
  \renewcommand{#2}{\def\@captype{#3}#1}}
```

```
\renewcommand{\renewfixedcaption}[3][\caption]{%
  \renewcommand{#2}{\def\@captype{#3}#1}}
\renewcommand{\providefixedcaption}[3][\caption]{%
  \providecommand{#2}{\def\@captype{#3}#1}}

\renewcommand{\bitwonumcaption}[6][]{%
    \ifblank{#2}{\caption{#3}}{\caption[#2]{#3}}%
    \addtocounter{\@captype}{-1}%
    \begingroup%
    \csdef{\@captype name}{#4}%
    \ifblank{#5}{\caption{#6}}{\caption[#5]{#6}}%
    \endgroup%
    \ifblank{#1}{}{\label{#1}}%
}

\LetLtxMacro\bionenumcaption\bitwonumcaption% todo

\renewcommand{\bicaption}[5][]{%
    \ifblank{#2}{\caption{#3}}{\caption[#2]{#3}}%
    \begin{LWR@figcaption}% later becomes \caption*
    \LWR@isolate{#4} % space
    \thechapter.\the\value{\@captype}\CaptionSeparator\LWR@isolate{#5}%
    \end{LWR@figcaption}%
    \ifblank{#1}{}{\label{#1}}%
}

\renewcommand{\bicontcaption}[3]{%
    \contcaption{#1}%
    \begingroup%
    \csdef{\@captype name}{#2}%
    \contcaption{#3}%
    \endgroup%
}
```

Only in ccaption, not in memoir:

```
% \LetLtxMacro\longbitwonumcaption\bitwonumcaption%
% \LetLtxMacro\longbionenumcaption\bitwonumcaption%
% \LetLtxMacro\longbicaption\bicaption%
```

Patches for subfloats to support additional lwarp labels:

```
\renewcommand{\@memsubbody}{%
  \bgroup
  \let\label=\memsub@label
  \ifdonemaincaption\else
    \advance\csname c@\@captype\endcsname\@ne
  \fi
  % \refstepcounter{sub\@captype}\@contkeep%
%   \leavevmode%            lwarp
  \@ifnextchar [%
    {\@memsubfig}%
    {\@memsubfig[\@empty]}}

\renewcommand{\@memcontsubbody}{%
  \bgroup
```

```
  \let\label=\memsub@label
  \@contset
  % \refstepcounter{sub\@captype}\@contkeep%
%   \leavevmode%            lwarp
  \@ifnextchar [%
    {\@memsubfig}%
    {\@memsubfig[\@empty]}}


\long\def\@memsubfloat#1[#2][#3]#4{%
%   \@tempcnta=\@ne
%   \if@tightsubcap
%     \if@minipage
%       \@tempcnta=\z@
%     \else
%       \ifdim\lastskip=\z@
%         \@tempcnta=\@ne
%       \else
%         \@tempcnta=\tw@
%       \fi
%     \fi
%   \fi
%   \if@contbotsub
%     \def\subfig@top{\subfloattopskip}%
%     \def\subfig@bottom{\subfloatbottomskip}%
%   \else
%     \def\subfig@top{\subfloatbottomskip}%
%     \def\subfig@bottom{\subfloattopskip}%
%   \fi
%   \setbox\@tempboxa \hbox{#4}%
%   \@tempdima=\wd\@tempboxa
%   \vbox
  \bgroup%
    \mem@step@subcounter%
%     \vbox
    \LWR@stoppars%
    \minipagefullwidth%                 lwarp
    \begin{minipage}{\linewidth}%       lwarp
    \bgroup
%     \ifcase\@tempcnta
%       \@minipagefalse
%     \or
%       \vspace{\subfig@top}
%     \or
%       \ifdim \lastskip=\z@ \else
%         \@tempskipb\subfig@top\@xaddvskip
%       \fi
%     \fi
    \if@contbotsub
      #4% \box\@tempboxa
      \egroup
      \ifx \@empty#3\relax \else
%         \vskip\subfloatcapskip
        \@memsubcaption{#1}{#2}{#3}%
      \fi
```

```
    \else
      \ifx \@empty#3\relax \else
        \@memsubcaption{#1}{#2}{#3}%
%         \vskip\subfloatcapskip
%         \vskip\subfloatcaptopadj
      \fi\egroup
      #4% \box\@tempboxa
    \fi
%     \vspace{\subfig@bottom}
    \end{minipage}%                     lwarp
    \LWR@startpars%                     lwarp
  \egroup
\egroup
}
```

§ 682.20 Final patchwork

```
\newlistof{tableofcontents}{toc}{\contentsname}
\newlistof{listoffigures}{lof}{\listfigurename}
\newlistof{listoftables}{lot}{\listtablename}
```

File 575 **lwarp-common-multimedia.sty**

§ 683 Package common-multimedia

Pkg lwarp-common-multimedia

Common code for multimedia, movie15, and media9.

The packages multimedia, movie15, and media9 are supported.

HTML5 <audio> and <video> objects are created for .mp3 and .mp4 files.

HTML5 <embed> objects are created for http and ftp links.

\href links are created for other media types. (Unfortunately, there is not much overlap between the file types supported for print output and the file types supported by HTML5.)

For media9, a multimedia object is inserted for each addresource=, as well as each flashvars source= and src=. This may result in duplicate objects.

Undesired objects may be nullified by placing them inside \warpprintonly or the warpprint environment.

Each HTML multimedia object includes the poster text, except for <embed> objects. For movie15, the text option is supported to specify the poster text.

The width, height, and totalheight options are supported. The HTML object is scaled according to the display width, correctly compensating for either tall or wide viewports.

Other options are ignored.

media9 \addmediapath is supported. It is assumed that the same path structure will exist for the HTML document.

HTML5 media controls are always specified for each <audio> and <video> object.

media9 slideshows are not supported.

\hyperlinkmovie, \movieref, and \mediabutton are not supported.

3D objects are not supported.

If using a YouTube™ video, use an "embedded" URL with .../embed/... instead of .../v/...

for HTML output:

```
\ProvidesPackage{lwarp-common-multimedia}[2019/04/22]

\RequirePackage{xkeyval}

\define@key{LWR@multimedia}{width}{\setlength{\LWR@multimedia@width}{#1}}
\define@key{LWR@multimedia}{height}{\setlength{\LWR@multimedia@height}{#1}}
\define@key{LWR@multimedia}{totalheight}{\setlength{\LWR@multimedia@height}{#1}}

\newlength{\LWR@multimedia@width}
\newlength{\LWR@multimedia@height}
\newlength{\LWR@multimedia@maxdimension}
```

\LWR@multimedia@printsize

Proportional to \linewidth and the viewport's smaller dimension. This scales each object such that it will always fit on the screen, even if a tall or wide object inside a tall or wide viewport.

```
\newcommand*{\LWR@multimedia@printsize}{%
    \setlength{\LWR@multimedia@maxdimension}{%
        \maxof%
            {\linewidth}%
            {\maxof{\LWR@multimedia@width}{\LWR@multimedia@height}}%
    }%
    \setlength{\LWR@multimedia@maxdimension}{1.1\LWR@multimedia@maxdimension}%
    \ifdimgreater{\LWR@multimedia@width}{0pt}{%
        width:%
            \LWR@printpercentlength%
                {\LWR@multimedia@width}%
                {\LWR@multimedia@maxdimension}vmin ; % space
    }{}%
    \ifdimgreater{\LWR@multimedia@height}{0pt}{%
        height:%
            \LWR@printpercentlength%
                {\LWR@multimedia@height}%
                {\LWR@multimedia@maxdimension}vmin ; % space
    }{}%
}
```

\LWR@multimedia@fileAV {⟨*poster text*⟩} {⟨*filename*⟩} {⟨*audio/video*⟩} {⟨*mimetype*⟩}

Creates a video or audio from a file. The 2019/10 update of the LaTeX kernel may cause extra quotes to be added in the filenames. They are removed here.

```
\newcommand*{\LWR@multimedia@fileAV}[4]{%
\IfFileExists{#2}{% also sets \@filef@und
\StrSubstitute[100]{\@filef@und}{"}{}[\LWR@parsedfilename]%
```

The container is sized as desired.

```
    \ifstrequal{#3}{audio}{%
        \begin{BlockClass}{AVviewport}
    }{%
        \begin{BlockClass}[\LWR@multimedia@printsize\ margin:auto]{AVviewport}
    }
```

Paragraph tags are unnecessary for the A/V tags.

```
    \LWR@stoppars
```

The A/V element is 100% of the container.

```
    \LWR@htmltag{%
        #3\ % space
        \ifstrequal{#3}{audio}{}{%
            width=\textquotedbl{}100\%\textquotedbl\ % space
            height=\textquotedbl{}100\%\textquotedbl\ % space
        }%
        controls%
    }\LWR@orignewline
```

The file source and type:

```
    \LWR@htmltag{%
        source % space
        src=\textquotedbl%
        \LWR@parsedfilename\unskip\textquotedbl\ % space
        type=\textquotedbl{}#4\textquotedbl}
```

The poster text inside paragraph tags, along with a reference to the file.

```
    \LWR@startpars
    \LWR@href{\LWR@parsedfilename}{#1}
    \LWR@stoppars
```

Finish.

```
    \LWR@htmltag{/#3}\LWR@orignewline
    \end{BlockClass}
}{%
    \PackageError{lwarp-common-multimedia}
        {File '#2' not found}
        {Perhaps an incorrect path?}
}%
}
```

`\LWR@multimedia@httpAV` {⟨*poster text*⟩} {⟨*filename*⟩} {⟨*audio/video*⟩} {⟨*mimetype*⟩}

Creates a video or audio from a URL link.

```
\newcommand*{\LWR@multimedia@httpAV}[4]{%
```

The container is sized as desired.

```
    \ifstrequal{#3}{audio}{%
        \begin{BlockClass}{AVviewport}
    }{%
        \begin{BlockClass}[\LWR@multimedia@printsize\ margin:auto]{AVviewport}
    }
```

Paragraph tags are unnecessary for the A/V tags.

```
    \LWR@stoppars
```

The A/V element is 100% of the container.

```
    \LWR@htmltag{%
        #3\ % space
        \ifstrequal{#3}{audio}{}{%
            width=\textquotedbl{}100\%\textquotedbl\ % space
            height=\textquotedbl{}100\%\textquotedbl\ controls%
        }%
    }\LWR@orignewline
```

The file source and type:

```
    \LWR@htmltag{%
        source % space
        src=\textquotedbl#2\textquotedbl\ % space
        type=\textquotedbl#4\textquotedbl}
```

The poster text inside paragraph tags, along with a reference to the URL.

```
    \LWR@startpars
    \LWR@href{#2}{#1}
    \LWR@stoppars
```

Finish.

```
    \LWR@htmltag{/#3}\LWR@orignewline
    \end{BlockClass}
}
```

`\LWR@multimedia@AV` {⟨*poster text*⟩} {⟨*filename*⟩} {⟨*audio/video*⟩} {⟨*mimetype*⟩}

Creates an audio or video from a file or a URL.

```
\newcommand*{\LWR@multimedia@AV}[4]{%
    \IfBeginWith{#2}{http}%
        {\LWR@multimedia@httpAV{#1}{#2}{#3}{#4}}%
        {%
            \IfBeginWith{#2}{HTTP}%
                {\LWR@multimedia@httpAV{#1}{#2}{#3}{#4}}%
                {\LWR@multimedia@fileAV{#1}{#2}{#3}{#4}}%
        }%
}
```

`\LWR@multimedia@embed` {⟨*poster text*⟩} {⟨*URL or filename*⟩} {⟨*mime type*⟩}

Embeds multimedia of an arbitrary type. The poster text is not used, as it would appear along with the video if the <embed> element is supported.

```
\newcommand*{\LWR@multimedia@embed}[3]{%
    \begin{BlockClass}[width:100\%]{AVviewport}%
    \LWR@stoppars
        \LWR@htmltag{%
            embed % space
            \ifblank{#3}{}{type=\textquotedbl#3\textquotedbl\ }%
        style=\textquotedbl\LWR@multimedia@printsize\ margin:auto\textquotedbl\ % space
            src=\textquotedbl#2\textquotedbl\ % space
        }%
    \LWR@startpars
    \end{BlockClass}
}
```

Error message if the comment character is used among the arguments of \LWR@multimediab.

\LWR@multimedia@percenterror

```
\newcommand*{\LWR@multimedia@percenterror}{%
    \PackageError{lwarp-media9}
    {%
        Do not use a percent comment between\MessageBreak
        \protect\includemedia\space arguments%
    }
    {%
        Percent is changed to a regular character\MessageBreak
        to allow its use inside a URL.%
    }
}
```

\LWR@multimediab [⟨*options*⟩] {⟨*poster text*⟩} {⟨*filename*⟩}

Creates multimedia. Examines the file extension to determine the type. If not a supported type, creates an embedded object if it has a URL. If neither, create a link to the unsupported object.

```
\newcommand*{\LWR@multimediab}[3][]{%
```

Error if the percent character appears among the arguments. This could happen since the comment character has been temporarily disabled, for use in a URL.

```
    \if#1\@percentchar\LWR@multimedia@percenterror\fi%
    \if#2\@percentchar\LWR@multimedia@percenterror\fi%
    \if#3\@percentchar\LWR@multimedia@percenterror\fi%
```

Paragraph handling:

```
    \LWR@stoppars%
```

Record the desired size.

```
    \setlength{\LWR@multimedia@width}{0pt}%
    \setlength{\LWR@multimedia@height}{0pt}%
    \setkeys*{LWR@multimedia}{#1}%
```

If a known A/V type, create an HTML5 <video> or <audio>.

```
    \IfEndWith{#3}{.mp4}{\LWR@multimedia@AV{#2}{#3}{video}{video/mp4}}{%
    \IfEndWith{#3}{.MP4}{\LWR@multimedia@AV{#2}{#3}{video}{video/mp4}}{%
    \IfEndWith{#3}{.mp3}{\LWR@multimedia@AV{#2}{#3}{audio}{audio/mpeg}}{%
    \IfEndWith{#3}{.MP3}{\LWR@multimedia@AV{#2}{#3}{audio}{audio/mpeg}}{%
```

If an arbitrary URL, embed it.

```
    \IfBeginWith{#3}{http}{\LWR@multimedia@embed{#2}{#3}{}}{%
    \IfBeginWith{#3}{HTTP}{\LWR@multimedia@embed{#2}{#3}{}}{%
    \IfBeginWith{#3}{ftp}{\LWR@multimedia@embed{#2}{#3}{}}{%
    \IfBeginWith{#3}{FTP}{\LWR@multimedia@embed{#2}{#3}{}}{%
```

If unknown, create a link to it.

```
        \LWR@href{#3}{#2}% unknown format
    }}}}}}}%
```

Paragraph handling:

```
    \LWR@startpars%
    \endgroup%
}
```

Catcodes which may apper in a URL.

```
\newrobustcmd*{\LWR@multimedia}{%
    \begingroup%
    \LWR@linkmediacatcodes%
    \LWR@multimediab%
}
```

File 576 **lwarp-common-mathjax-letters.sty**

§ 684 Package

common-mathjax-letters

Pkg lwarp-common-mathjax-letters

Common code used by a number of packages to generate Greek math characters for MathJax.

for HTML output:

```
\ProvidesPackage{lwarp-common-mathjax-letters}[2020/08/10]
```

\LWR@mathjax@addletter * {⟨*2: capitalize name?*⟩} {⟨*3: prefix*⟩} {⟨*4: postfix*⟩} {⟨*5: name*⟩} {⟨*6: unicode*⟩}

Star to italicize the result, used when the unicode character does not exist.

```
\begin{warpMathJax}

\NewDocumentCommand{\LWR@mathjax@addletter}{s m m m m m}{
    \IfBooleanTF{#2}%
        {\edef\LWR@tempone{\LWRtexttitlecase{#5}}}%
        {\edef\LWR@tempone{#5}}%
    \xdef\LWR@customizedMathJax{%
        \LWR@customizedMathJax%
        \LWRbackslash(%
        \LWRbackslash def\LWRbackslash%
        #3% prefix
        \LWR@tempone%name
        #4% postfix
        \LWRleftbrace%
    }%
    \IfBooleanTF{#1}{%
        \xdef\LWR@customizedMathJax{%
            \LWR@customizedMathJax%
            \LWRbackslash mathit\LWRleftbrace%
            \LWRbackslash unicode\LWRleftbrace x#6\LWRrightbrace%
            \LWRrightbrace%
        }%
    }{%
        \xdef\LWR@customizedMathJax{%
            \LWR@customizedMathJax%
            \LWRbackslash unicode\LWRleftbrace x#6\LWRrightbrace%
        }%
    }%
```

```
    \xdef\LWR@customizedMathJax{%
        \LWR@customizedMathJax%
        \LWRrightbrace\LWRbackslash)\par%
    }%
}
```

\LWR@mathjax@addgreek@l@up

* {⟨*2: prefix*⟩} {⟨*3: postfix*⟩}

Star to capitalize the macro names.

Adds `\CustomizeMathjax` expressions to define a set of macros for Greek letters, lowercase upright.

```
\NewDocumentCommand{\LWR@mathjax@addgreek@l@up}{s m m}{
    \LWR@mathjax@addletter{#1}{#2}{#3}{alpha}{03B1}
    \LWR@mathjax@addletter{#1}{#2}{#3}{beta}{03B2}
    \LWR@mathjax@addletter{#1}{#2}{#3}{varbeta}{03D0}
    \LWR@mathjax@addletter{#1}{#2}{#3}{gamma}{03B3}
    \LWR@mathjax@addletter{#1}{#2}{#3}{digamma}{03DD}
    \LWR@mathjax@addletter{#1}{#2}{#3}{delta}{03B4}
    \LWR@mathjax@addletter{#1}{#2}{#3}{epsilon}{03F5}
    \LWR@mathjax@addletter{#1}{#2}{#3}{varepsilon}{03B5}
    \LWR@mathjax@addletter{#1}{#2}{#3}{zeta}{03B6}
    \LWR@mathjax@addletter{#1}{#2}{#3}{eta}{03B7}
    \LWR@mathjax@addletter{#1}{#2}{#3}{theta}{03B8}
    \LWR@mathjax@addletter{#1}{#2}{#3}{vartheta}{03D1}
    \LWR@mathjax@addletter{#1}{#2}{#3}{iota}{03B9}
    \LWR@mathjax@addletter{#1}{#2}{#3}{kappa}{03BA}
    \LWR@mathjax@addletter{#1}{#2}{#3}{varkappa}{03F0}
    \LWR@mathjax@addletter{#1}{#2}{#3}{lambda}{03BB}
    \LWR@mathjax@addletter{#1}{#2}{#3}{mu}{03BC}
    \LWR@mathjax@addletter{#1}{#2}{#3}{nu}{03BD}
    \LWR@mathjax@addletter{#1}{#2}{#3}{xi}{03BE}
    \LWR@mathjax@addletter{#1}{#2}{#3}{omicron}{03BF}
    \LWR@mathjax@addletter{#1}{#2}{#3}{pi}{03C0}
    \LWR@mathjax@addletter{#1}{#2}{#3}{varpi}{03D6}
    \LWR@mathjax@addletter{#1}{#2}{#3}{rho}{03C1}
    \LWR@mathjax@addletter{#1}{#2}{#3}{varrho}{03F1}
    \LWR@mathjax@addletter{#1}{#2}{#3}{sigma}{03C3}
    \LWR@mathjax@addletter{#1}{#2}{#3}{varsigma}{03C2}
    \LWR@mathjax@addletter{#1}{#2}{#3}{tau}{03C4}
    \LWR@mathjax@addletter{#1}{#2}{#3}{upsilon}{03C5}
    \LWR@mathjax@addletter{#1}{#2}{#3}{phi}{03D5}
    \LWR@mathjax@addletter{#1}{#2}{#3}{varphi}{03C6}
    \LWR@mathjax@addletter{#1}{#2}{#3}{chi}{03C7}
    \LWR@mathjax@addletter{#1}{#2}{#3}{psi}{03C8}
    \LWR@mathjax@addletter{#1}{#2}{#3}{omega}{03C9}
}
```

\LWR@mathjax@addgreek@u@up

* {⟨*2: prefix*⟩} {⟨*3: postfix*⟩}

Star to capitalize the macro names.

Adds `\CustomizeMathjax` expressions to define a set of macros for Greek letters, uppercase upright.

```
\NewDocumentCommand{\LWR@mathjax@addgreek@u@up}{s m m}{
```

```
    \LWR@mathjax@addletter{#1}{#2}{#3}{alpha}{0391}
    \LWR@mathjax@addletter{#1}{#2}{#3}{beta}{0392}
    \LWR@mathjax@addletter{#1}{#2}{#3}{gamma}{0393}
    \LWR@mathjax@addletter{#1}{#2}{#3}{digamma}{03DC}
    \LWR@mathjax@addletter{#1}{#2}{#3}{delta}{0394}
    \LWR@mathjax@addletter{#1}{#2}{#3}{epsilon}{0395}
    \LWR@mathjax@addletter{#1}{#2}{#3}{zeta}{0396}
    \LWR@mathjax@addletter{#1}{#2}{#3}{eta}{0397}
    \LWR@mathjax@addletter{#1}{#2}{#3}{theta}{0398}
    \LWR@mathjax@addletter{#1}{#2}{#3}{vartheta}{03F4}
    \LWR@mathjax@addletter{#1}{#2}{#3}{iota}{0399}
    \LWR@mathjax@addletter{#1}{#2}{#3}{kappa}{039A}
    \LWR@mathjax@addletter{#1}{#2}{#3}{lambda}{039B}
    \LWR@mathjax@addletter{#1}{#2}{#3}{mu}{039C}
    \LWR@mathjax@addletter{#1}{#2}{#3}{nu}{039D}
    \LWR@mathjax@addletter{#1}{#2}{#3}{xi}{039E}
    \LWR@mathjax@addletter{#1}{#2}{#3}{omicron}{039F}
    \LWR@mathjax@addletter{#1}{#2}{#3}{pi}{03A0}
    \LWR@mathjax@addletter{#1}{#2}{#3}{varpi}{03D6}
    \LWR@mathjax@addletter{#1}{#2}{#3}{rho}{03A1}
    \LWR@mathjax@addletter{#1}{#2}{#3}{sigma}{03A3}
    \LWR@mathjax@addletter{#1}{#2}{#3}{tau}{03A4}
    \LWR@mathjax@addletter{#1}{#2}{#3}{upsilon}{03A5}
    \LWR@mathjax@addletter{#1}{#2}{#3}{phi}{03A6}
    \LWR@mathjax@addletter{#1}{#2}{#3}{chi}{03A7}
    \LWR@mathjax@addletter{#1}{#2}{#3}{psi}{03A8}
    \LWR@mathjax@addletter{#1}{#2}{#3}{omega}{03A9}
}
```

* {⟨*2: prefix*⟩} {⟨*3: postfix*⟩}

\LWR@mathjax@addgreek@l@it

Star to capitalize the macro names.

Adds \CustomizeMathjax expressions to define a set of macros for Greek letters, lowercase italic.

```
\NewDocumentCommand{\LWR@mathjax@addgreek@l@it}{s m m}{
    \LWR@mathjax@addletter{#1}{#2}{#3}{alpha}{1D6FC}
    \LWR@mathjax@addletter{#1}{#2}{#3}{beta}{1D6FD}
    \LWR@mathjax@addletter{#1}{#2}{#3}{varbeta}{03D0}
    \LWR@mathjax@addletter{#1}{#2}{#3}{gamma}{1D6FE}
    \LWR@mathjax@addletter*{#1}{#2}{#3}{digamma}{03DD}
    \LWR@mathjax@addletter{#1}{#2}{#3}{delta}{1D6FF}
    \LWR@mathjax@addletter{#1}{#2}{#3}{epsilon}{1D716}
    \LWR@mathjax@addletter{#1}{#2}{#3}{varepsilon}{1D700}
    \LWR@mathjax@addletter{#1}{#2}{#3}{zeta}{1D701}
    \LWR@mathjax@addletter{#1}{#2}{#3}{eta}{1D702}
    \LWR@mathjax@addletter{#1}{#2}{#3}{theta}{1D703}
    \LWR@mathjax@addletter{#1}{#2}{#3}{vartheta}{1D717}
    \LWR@mathjax@addletter{#1}{#2}{#3}{iota}{1D704}
    \LWR@mathjax@addletter{#1}{#2}{#3}{kappa}{1D705}
    \LWR@mathjax@addletter{#1}{#2}{#3}{varkappa}{1D718}
    \LWR@mathjax@addletter{#1}{#2}{#3}{lambda}{1D706}
    \LWR@mathjax@addletter{#1}{#2}{#3}{mu}{1D707}
    \LWR@mathjax@addletter{#1}{#2}{#3}{nu}{1D708}
    \LWR@mathjax@addletter{#1}{#2}{#3}{xi}{1D709}
```

```
    \LWR@mathjax@addletter{#1}{#2}{#3}{omicron}{1D70A}
    \LWR@mathjax@addletter{#1}{#2}{#3}{pi}{1D70B}
    \LWR@mathjax@addletter{#1}{#2}{#3}{varpi}{1D71B}
    \LWR@mathjax@addletter{#1}{#2}{#3}{rho}{1D70C}
    \LWR@mathjax@addletter{#1}{#2}{#3}{varrho}{1D71A}
    \LWR@mathjax@addletter{#1}{#2}{#3}{sigma}{1D70E}
    \LWR@mathjax@addletter{#1}{#2}{#3}{varsigma}{1D70D}
    \LWR@mathjax@addletter{#1}{#2}{#3}{tau}{1D70F}
    \LWR@mathjax@addletter{#1}{#2}{#3}{upsilon}{1D710}
    \LWR@mathjax@addletter{#1}{#2}{#3}{phi}{1D719}
    \LWR@mathjax@addletter{#1}{#2}{#3}{varphi}{1D711}
    \LWR@mathjax@addletter{#1}{#2}{#3}{chi}{1D712}
    \LWR@mathjax@addletter{#1}{#2}{#3}{psi}{1D713}
    \LWR@mathjax@addletter{#1}{#2}{#3}{omega}{1D714}
}
```

* {⟨*2: prefix*⟩} {⟨*3: postfix*⟩}

\LWR@mathjax@addgreek@u@it

Star to capitalize the macro names.

Adds \CustomizeMathjax expressions to define a set of macros for Greek letters, uppercase italic.

```
\NewDocumentCommand{\LWR@mathjax@addgreek@u@it}{s m m}{
    \LWR@mathjax@addletter{#1}{#2}{#3}{alpha}{1D6E2}
    \LWR@mathjax@addletter{#1}{#2}{#3}{beta}{1D6E3}
    \LWR@mathjax@addletter{#1}{#2}{#3}{gamma}{1D6E4}
    \LWR@mathjax@addletter*{#1}{#2}{#3}{digamma}{03DC}
    \LWR@mathjax@addletter{#1}{#2}{#3}{delta}{1D6E5}
    \LWR@mathjax@addletter{#1}{#2}{#3}{epsilon}{1D6E6}
    \LWR@mathjax@addletter{#1}{#2}{#3}{zeta}{1D6E7}
    \LWR@mathjax@addletter{#1}{#2}{#3}{eta}{1D6E8}
    \LWR@mathjax@addletter{#1}{#2}{#3}{theta}{1D6E9}
    \LWR@mathjax@addletter{#1}{#2}{#3}{vartheta}{1D6F3}
    \LWR@mathjax@addletter{#1}{#2}{#3}{iota}{1D6EA}
    \LWR@mathjax@addletter{#1}{#2}{#3}{kappa}{1D6EB}
    \LWR@mathjax@addletter{#1}{#2}{#3}{lambda}{1D6EC}
    \LWR@mathjax@addletter{#1}{#2}{#3}{mu}{1D6ED}
    \LWR@mathjax@addletter{#1}{#2}{#3}{nu}{1D6EE}
    \LWR@mathjax@addletter{#1}{#2}{#3}{xi}{1D6EF}
    \LWR@mathjax@addletter{#1}{#2}{#3}{omicron}{1D6F0}
    \LWR@mathjax@addletter{#1}{#2}{#3}{pi}{1D6F1}
    \LWR@mathjax@addletter{#1}{#2}{#3}{rho}{1D6F2}
    \LWR@mathjax@addletter{#1}{#2}{#3}{sigma}{1D6F4}
    \LWR@mathjax@addletter{#1}{#2}{#3}{tau}{1D6F5}
    \LWR@mathjax@addletter{#1}{#2}{#3}{upsilon}{1D6F6}
    \LWR@mathjax@addletter{#1}{#2}{#3}{phi}{1D6F7}
    \LWR@mathjax@addletter{#1}{#2}{#3}{chi}{1D6F8}
    \LWR@mathjax@addletter{#1}{#2}{#3}{psi}{1D6F9}
    \LWR@mathjax@addletter{#1}{#2}{#3}{omega}{1D6FA}
}
```

* {⟨*2: prefix*⟩} {⟨*3: postfix*⟩}

\LWR@mathjax@addgreek@l@bfit

Star to capitalize the macro names.

Adds `\CustomizeMathjax` expressions to define a set of macros for Greek letters, lowercase boldface italic.

```
\NewDocumentCommand{\LWR@mathjax@addgreek@l@bfit}{s m m}{
    \LWR@mathjax@addletter{#1}{#2}{#3}{alpha}{1D736}
    \LWR@mathjax@addletter{#1}{#2}{#3}{beta}{1D737}
    \LWR@mathjax@addletter{#1}{#2}{#3}{varbeta}{03D0}
    \LWR@mathjax@addletter{#1}{#2}{#3}{gamma}{1D738}
    \LWR@mathjax@addletter*{#1}{#2}{#3}{digamma}{03DD}
    \LWR@mathjax@addletter{#1}{#2}{#3}{delta}{1D739}
    \LWR@mathjax@addletter{#1}{#2}{#3}{epsilon}{1D750}
    \LWR@mathjax@addletter{#1}{#2}{#3}{varepsilon}{1D73A}
    \LWR@mathjax@addletter{#1}{#2}{#3}{zeta}{1D73B}
    \LWR@mathjax@addletter{#1}{#2}{#3}{eta}{1D73C}
    \LWR@mathjax@addletter{#1}{#2}{#3}{theta}{1D73D}
    \LWR@mathjax@addletter{#1}{#2}{#3}{vartheta}{1D751}
    \LWR@mathjax@addletter{#1}{#2}{#3}{iota}{1D73E}
    \LWR@mathjax@addletter{#1}{#2}{#3}{kappa}{1D73F}
    \LWR@mathjax@addletter{#1}{#2}{#3}{varkappa}{1D752}
    \LWR@mathjax@addletter{#1}{#2}{#3}{lambda}{1D740}
    \LWR@mathjax@addletter{#1}{#2}{#3}{mu}{1D741}
    \LWR@mathjax@addletter{#1}{#2}{#3}{nu}{1D742}
    \LWR@mathjax@addletter{#1}{#2}{#3}{xi}{1D743}
    \LWR@mathjax@addletter{#1}{#2}{#3}{omicron}{1D744}
    \LWR@mathjax@addletter{#1}{#2}{#3}{pi}{1D745}
    \LWR@mathjax@addletter{#1}{#2}{#3}{varpi}{1D755}
    \LWR@mathjax@addletter{#1}{#2}{#3}{rho}{1D746}
    \LWR@mathjax@addletter{#1}{#2}{#3}{varrho}{1D754}
    \LWR@mathjax@addletter{#1}{#2}{#3}{sigma}{1D748}
    \LWR@mathjax@addletter{#1}{#2}{#3}{varsigma}{1D747}
    \LWR@mathjax@addletter{#1}{#2}{#3}{tau}{1D749}
    \LWR@mathjax@addletter{#1}{#2}{#3}{upsilon}{1D74A}
    \LWR@mathjax@addletter{#1}{#2}{#3}{phi}{1D753}
    \LWR@mathjax@addletter{#1}{#2}{#3}{varphi}{1D74B}
    \LWR@mathjax@addletter{#1}{#2}{#3}{chi}{1D74C}
    \LWR@mathjax@addletter{#1}{#2}{#3}{psi}{1D74D}
    \LWR@mathjax@addletter{#1}{#2}{#3}{omega}{1D74E}
}
```

`\LWR@mathjax@addgreek@u@bfit`

`*` `{`⟨*2: prefix*⟩`}` `{`⟨*3: postfix*⟩`}`

Star to capitalize the macro names.

Adds `\CustomizeMathjax` expressions to define a set of macros for Greek letters, uppercase boldface italic.

```
\NewDocumentCommand{\LWR@mathjax@addgreek@u@bfit}{s m m}{
    \LWR@mathjax@addletter{#1}{#2}{#3}{alpha}{1D71C}
    \LWR@mathjax@addletter{#1}{#2}{#3}{beta}{1D71D}
    \LWR@mathjax@addletter{#1}{#2}{#3}{gamma}{1D71E}
    \LWR@mathjax@addletter*{#1}{#2}{#3}{digamma}{03DC}
    \LWR@mathjax@addletter{#1}{#2}{#3}{delta}{1D71F}
    \LWR@mathjax@addletter{#1}{#2}{#3}{epsilon}{1D720}
    \LWR@mathjax@addletter{#1}{#2}{#3}{zeta}{1D721}
    \LWR@mathjax@addletter{#1}{#2}{#3}{eta}{1D722}
    \LWR@mathjax@addletter{#1}{#2}{#3}{theta}{1D723}
    \LWR@mathjax@addletter{#1}{#2}{#3}{vartheta}{1D72D}
```

```
    \LWR@mathjax@addletter{#1}{#2}{#3}{iota}{1D724}
    \LWR@mathjax@addletter{#1}{#2}{#3}{kappa}{1D725}
    \LWR@mathjax@addletter{#1}{#2}{#3}{lambda}{1D726}
    \LWR@mathjax@addletter{#1}{#2}{#3}{mu}{1D727}
    \LWR@mathjax@addletter{#1}{#2}{#3}{nu}{1D728}
    \LWR@mathjax@addletter{#1}{#2}{#3}{xi}{1D729}
    \LWR@mathjax@addletter{#1}{#2}{#3}{omicron}{1D72A}
    \LWR@mathjax@addletter{#1}{#2}{#3}{pi}{1D72B}
    \LWR@mathjax@addletter{#1}{#2}{#3}{rho}{1D72C}
    \LWR@mathjax@addletter{#1}{#2}{#3}{sigma}{1D72E}
    \LWR@mathjax@addletter{#1}{#2}{#3}{tau}{1D72F}
    \LWR@mathjax@addletter{#1}{#2}{#3}{upsilon}{1D730}
    \LWR@mathjax@addletter{#1}{#2}{#3}{phi}{1D731}
    \LWR@mathjax@addletter{#1}{#2}{#3}{chi}{1D732}
    \LWR@mathjax@addletter{#1}{#2}{#3}{psi}{1D733}
    \LWR@mathjax@addletter{#1}{#2}{#3}{omega}{1D734}
}
```

`\LWR@mathjax@addgreek@u@bfup` is not needed.

`\LWR@mathjax@addgreek@u@bfup` * {⟨*2: prefix*⟩} {⟨*3: postfix*⟩}

Star to capitalize the macro names.

Adds `\CustomizeMathjax` expressions to define a set of macros for Greek letters, uppercase boldface upright.

```
\NewDocumentCommand{\LWR@mathjax@addgreek@u@bfup}{s m m}{
    \LWR@mathjax@addletter{#1}{#2}{#3}{alpha}{1D6A8}
    \LWR@mathjax@addletter{#1}{#2}{#3}{beta}{1D6A9}
    \LWR@mathjax@addletter{#1}{#2}{#3}{gamma}{1D6AA}
    \LWR@mathjax@addletter*{#1}{#2}{#3}{digamma}{03DC}
    \LWR@mathjax@addletter{#1}{#2}{#3}{delta}{1D6AB}
    \LWR@mathjax@addletter{#1}{#2}{#3}{epsilon}{1D6AC}
    \LWR@mathjax@addletter{#1}{#2}{#3}{zeta}{1D6AD}
    \LWR@mathjax@addletter{#1}{#2}{#3}{eta}{1D6AE}
    \LWR@mathjax@addletter{#1}{#2}{#3}{theta}{1D6AF}
    \LWR@mathjax@addletter{#1}{#2}{#3}{vartheta}{1D6B9}
    \LWR@mathjax@addletter{#1}{#2}{#3}{iota}{1D6B0}
    \LWR@mathjax@addletter{#1}{#2}{#3}{kappa}{1D6B1}
    \LWR@mathjax@addletter{#1}{#2}{#3}{lambda}{1D6B2}
    \LWR@mathjax@addletter{#1}{#2}{#3}{mu}{1D6B3}
    \LWR@mathjax@addletter{#1}{#2}{#3}{nu}{1D6B4}
    \LWR@mathjax@addletter{#1}{#2}{#3}{xi}{1D6B5}
    \LWR@mathjax@addletter{#1}{#2}{#3}{omicron}{1D6B6}
    \LWR@mathjax@addletter{#1}{#2}{#3}{pi}{1D6B7}
    \LWR@mathjax@addletter{#1}{#2}{#3}{rho}{1D6B8}
    \LWR@mathjax@addletter{#1}{#2}{#3}{sigma}{1D6BA}
    \LWR@mathjax@addletter{#1}{#2}{#3}{tau}{1D6BB}
    \LWR@mathjax@addletter{#1}{#2}{#3}{upsilon}{1D6BC}
    \LWR@mathjax@addletter{#1}{#2}{#3}{phi}{1D6BD}
    \LWR@mathjax@addletter{#1}{#2}{#3}{chi}{1D6BE}
    \LWR@mathjax@addletter{#1}{#2}{#3}{psi}{1D6BF}
    \LWR@mathjax@addletter{#1}{#2}{#3}{omega}{1D6C0}
}
```

{⟨*prefix*⟩}

\LWR@mathjax@addlatin@u@bfit

Adds \CustomizeMathjax expressions to define a set of macros for bold-face italic Latin letters, uppercase and lowercase.

```
\NewDocumentCommand{\LWR@mathjax@addlatin@u@bfit}{m}{
    \LWR@mathjax@addletter{\BooleanFalse}{#1}{}{A}{1D468}
    \LWR@mathjax@addletter{\BooleanFalse}{#1}{}{B}{1D469}
    \LWR@mathjax@addletter{\BooleanFalse}{#1}{}{C}{1D46A}
    \LWR@mathjax@addletter{\BooleanFalse}{#1}{}{D}{1D46B}
    \LWR@mathjax@addletter{\BooleanFalse}{#1}{}{E}{1D46C}
    \LWR@mathjax@addletter{\BooleanFalse}{#1}{}{F}{1D46D}
    \LWR@mathjax@addletter{\BooleanFalse}{#1}{}{G}{1D46E}
    \LWR@mathjax@addletter{\BooleanFalse}{#1}{}{H}{1D46F}
    \LWR@mathjax@addletter{\BooleanFalse}{#1}{}{I}{1D470}
    \LWR@mathjax@addletter{\BooleanFalse}{#1}{}{J}{1D471}
    \LWR@mathjax@addletter{\BooleanFalse}{#1}{}{K}{1D472}
    \LWR@mathjax@addletter{\BooleanFalse}{#1}{}{L}{1D473}
    \LWR@mathjax@addletter{\BooleanFalse}{#1}{}{M}{1D474}
    \LWR@mathjax@addletter{\BooleanFalse}{#1}{}{N}{1D475}
    \LWR@mathjax@addletter{\BooleanFalse}{#1}{}{O}{1D476}
    \LWR@mathjax@addletter{\BooleanFalse}{#1}{}{P}{1D477}
    \LWR@mathjax@addletter{\BooleanFalse}{#1}{}{Q}{1D478}
    \LWR@mathjax@addletter{\BooleanFalse}{#1}{}{R}{1D479}
    \LWR@mathjax@addletter{\BooleanFalse}{#1}{}{S}{1D47A}
    \LWR@mathjax@addletter{\BooleanFalse}{#1}{}{T}{1D47B}
    \LWR@mathjax@addletter{\BooleanFalse}{#1}{}{U}{1D47C}
    \LWR@mathjax@addletter{\BooleanFalse}{#1}{}{V}{1D47D}
    \LWR@mathjax@addletter{\BooleanFalse}{#1}{}{W}{1D47E}
    \LWR@mathjax@addletter{\BooleanFalse}{#1}{}{X}{1D47F}
    \LWR@mathjax@addletter{\BooleanFalse}{#1}{}{Y}{1D480}
    \LWR@mathjax@addletter{\BooleanFalse}{#1}{}{Z}{1D481}
}
```

{⟨*prefix*⟩}

\LWR@mathjax@addlatin@l@bfit

Adds \CustomizeMathjax expressions to define a set of macros for bold-face italic Latin letters, uppercase and lowercase.

```
\NewDocumentCommand{\LWR@mathjax@addlatin@l@bfit}{m}{
    \LWR@mathjax@addletter{\BooleanFalse}{#1}{}{a}{1D482}
    \LWR@mathjax@addletter{\BooleanFalse}{#1}{}{b}{1D483}
    \LWR@mathjax@addletter{\BooleanFalse}{#1}{}{c}{1D484}
    \LWR@mathjax@addletter{\BooleanFalse}{#1}{}{d}{1D485}
    \LWR@mathjax@addletter{\BooleanFalse}{#1}{}{e}{1D486}
    \LWR@mathjax@addletter{\BooleanFalse}{#1}{}{f}{1D487}
    \LWR@mathjax@addletter{\BooleanFalse}{#1}{}{g}{1D488}
    \LWR@mathjax@addletter{\BooleanFalse}{#1}{}{h}{1D489}
    \LWR@mathjax@addletter{\BooleanFalse}{#1}{}{i}{1D48A}
    \LWR@mathjax@addletter{\BooleanFalse}{#1}{}{j}{1D48B}
    \LWR@mathjax@addletter{\BooleanFalse}{#1}{}{k}{1D48C}
    \LWR@mathjax@addletter{\BooleanFalse}{#1}{}{l}{1D48D}
    \LWR@mathjax@addletter{\BooleanFalse}{#1}{}{m}{1D48E}
    \LWR@mathjax@addletter{\BooleanFalse}{#1}{}{n}{1D48F}
    \LWR@mathjax@addletter{\BooleanFalse}{#1}{}{o}{1D490}
    \LWR@mathjax@addletter{\BooleanFalse}{#1}{}{p}{1D491}
    \LWR@mathjax@addletter{\BooleanFalse}{#1}{}{q}{1D492}
```

```
    \LWR@mathjax@addletter{\BooleanFalse}{#1}{}{r}{1D493}
    \LWR@mathjax@addletter{\BooleanFalse}{#1}{}{s}{1D494}
    \LWR@mathjax@addletter{\BooleanFalse}{#1}{}{t}{1D495}
    \LWR@mathjax@addletter{\BooleanFalse}{#1}{}{u}{1D496}
    \LWR@mathjax@addletter{\BooleanFalse}{#1}{}{v}{1D497}
    \LWR@mathjax@addletter{\BooleanFalse}{#1}{}{w}{1D498}
    \LWR@mathjax@addletter{\BooleanFalse}{#1}{}{x}{1D499}
    \LWR@mathjax@addletter{\BooleanFalse}{#1}{}{y}{1D49A}
    \LWR@mathjax@addletter{\BooleanFalse}{#1}{}{z}{1D49B}
}

\end{warpMathJax}
```

File 577 **lwarp-common-mathjax-newpxtxmath.sty**

§ 685 Package

common-mathjax-newpxtxmath

(*Emulates or patches code by* Michael Sharpe.)

Pkg Common code used by newpxmath, newtxmath, and newtxsf for MathJax.

lwarp-common-mathjax-newpxtxmath

for HTML output:

```
\ProvidesPackage{lwarp-common-mathjax-newpxtxmath}[2020/09/20]
```

For MathJax:

```
\LWR@origRequirePackage{lwarp-common-mathjax-nonunicode}
\LWR@origRequirePackage{lwarp-common-mathjax-overlaysymbols}

\begin{warpMathJax}
\CustomizeMathJax{\newcommand{\fAlt}{f}}
\CustomizeMathJax{\newcommand{\rhoAlt}{\rho}}

\CustomizeMathJax{\newcommand{\imathscr}{\mathord{\mathscr{i}}}}
\CustomizeMathJax{\newcommand{\jmathscr}{\mathord{\mathscr{j}}}}
```

`lwarp_mathjax.txt` adds `\left`/`\right` support for delimiters.

```
\CustomizeMathJax{\let\llbracket\lBrack}
\CustomizeMathJax{\let\rrbracket\rBrack}

\CustomizeMathJax{\let\smlbrace\{}
\CustomizeMathJax{\let\smrbrace\}}
\CustomizeMathJax{\newcommand{\Perp}{\mathrel{\unicode{x02AEB}}}}
\CustomizeMathJax{\newcommand{\nPerp}{\mathrel{\not{\!\unicode{x02AEB}}}}}
\CustomizeMathJax{\newcommand{\Zbar}{\mathord{\unicode{x01B5}}}}
\CustomizeMathJax{\newcommand{\Angstrom}{\mathord{\unicode{x212B}}}}
\CustomizeMathJax{\newcommand{\Euler}{\mathord{\unicode{x2107}}}}
\CustomizeMathJax{\newcommand{\transp}{\mathord{\unicode{xFF34}}}}
\CustomizeMathJax{\newcommand{\hermtransp}{\mathord{\unicode{xFF28}}}}
\CustomizeMathJax{\let\htransp=\hermtransp}
\CustomizeMathJax{\newcommand{\circledplus}{\mathbin{\unicode{x2295}}}}
\CustomizeMathJax{\newcommand{\circledminus}{\mathbin{\unicode{x2296}}}}
\CustomizeMathJax{\newcommand{\circledtimes}{\mathbin{\unicode{x2297}}}}
```

```
\CustomizeMathJax{\newcommand{\circledslash}{\mathbin{\unicode{x2298}}}}
%
\CustomizeMathJax{\newcommand{\circleddot}{\mathbin{\unicode{x2299}}}}
\CustomizeMathJax{\let\overgroup\overparen}
\CustomizeMathJax{\let\overgroupra\overrightarrow}
\CustomizeMathJax{\let\undergroup\underparen}
\CustomizeMathJax{\let\undergroupla\underleftarrow}
\CustomizeMathJax{\newcommand{\widering}[1]{\stackrel{\unicode{x2218}}{\overgroup{#1}}}}
\CustomizeMathJax{\let\widearc\overparen}
\CustomizeMathJax{\let\wideOarc\overrightarrow}
\CustomizeMathJax{\newcommand{\LWRvvstar}[2]{{\overrightarrow{#1}_{#2}}}}
\CustomizeMathJax{\newcommand{\vv}{\ifstar\LWRvvstar\overrightarrow}}
%
\CustomizeMathJax{\let\smallintsl\smallint}
\CustomizeMathJax{\newcommand{\smalliintsl}{\mathop{\unicode{x222C}}\limits}}
\CustomizeMathJax{\newcommand{\smalliiintsl}{\mathop{\unicode{x222D}}\limits}}
\CustomizeMathJax{\newcommand{\smalliiiintsl}{\mathop{\unicode{x2A0C}}\limits}}
\CustomizeMathJax{\newcommand{\smallointsl}{\mathop{\unicode{x222E}}\limits}}
\CustomizeMathJax{\newcommand{\smalloiintsl}{\mathop{\unicode{x222F}}\limits}}
\CustomizeMathJax{\newcommand{\smalloiiintsl}{\mathop{\unicode{x2230}}\limits}}
\CustomizeMathJax{\newcommand{\smallvarointclockwisesl}{\mathop{\unicode{x2232}}\limits}}
\CustomizeMathJax{\newcommand{\smallointctrclockwisesl}{\mathop{\unicode{x2233}}\limits}}
\CustomizeMathJax{\newcommand{\smallsumintsl}{\mathop{\unicode{x2A0B}}\limits}}
\CustomizeMathJax{\newcommand{\smallfintsl}{\mathop{\unicode{x2A0F}}\limits}}
\CustomizeMathJax{\newcommand{\smallsqintsl}{\mathop{\unicode{x2A16}}\limits}}
%
\CustomizeMathJax{\let\smallintup\smallint}
\CustomizeMathJax{\newcommand{\smalliintup}{\mathop{\unicode{x222C}}\limits}}
\CustomizeMathJax{\newcommand{\smalliiintup}{\mathop{\unicode{x222D}}\limits}}
\CustomizeMathJax{\newcommand{\smalliiiintup}{\mathop{\unicode{x2A0C}}\limits}}
\CustomizeMathJax{\newcommand{\smallointup}{\mathop{\unicode{x222E}}\limits}}
\CustomizeMathJax{\newcommand{\smalloiintup}{\mathop{\unicode{x222F}}\limits}}
\CustomizeMathJax{\newcommand{\smalloiiintup}{\mathop{\unicode{x2230}}\limits}}
\CustomizeMathJax{\newcommand{\smallvarointclockwiseup}{\mathop{\unicode{x2232}}\limits}}
\CustomizeMathJax{\newcommand{\smallointctrclockwiseup}{\mathop{\unicode{x2233}}\limits}}
\CustomizeMathJax{\newcommand{\smallsumintup}{\mathop{\unicode{x2A0B}}\limits}}
\CustomizeMathJax{\newcommand{\smallfintup}{\mathop{\unicode{x2A0F}}\limits}}
\CustomizeMathJax{\newcommand{\smallsqintup}{\mathop{\unicode{x2A16}}\limits}}
%
\CustomizeMathJax{\newcommand{\iint}{\mathop{\unicode{x222C}}\limits}}
\CustomizeMathJax{\newcommand{\iiint}{\mathop{\unicode{x222D}}\limits}}
\CustomizeMathJax{\newcommand{\iiiint}{\mathop{\unicode{x2A0C}}\limits}}
\CustomizeMathJax{\newcommand{\oiint}{\mathop{\unicode{x222F}}\limits}}
\CustomizeMathJax{\newcommand{\oiiint}{\mathop{\unicode{x2230}}\limits}}
\CustomizeMathJax{\newcommand{\varointclockwise}{\mathop{\unicode{x2232}}\limits}}
\CustomizeMathJax{\newcommand{\ointctrclockwise}{\mathop{\unicode{x2233}}\limits}}
\CustomizeMathJax{\newcommand{\sumint}{\mathop{\unicode{x2A0B}}\limits}}
\CustomizeMathJax{\newcommand{\fint}{\mathop{\unicode{x2A0F}}\limits}}
\CustomizeMathJax{\newcommand{\sqint}{\mathop{\unicode{x2A16}}\limits}}
%
\CustomizeMathJax{\let\intsl\int}
\CustomizeMathJax{\newcommand{\iintsl}{\mathop{\unicode{x222C}}\limits}}
\CustomizeMathJax{\newcommand{\iiintsl}{\mathop{\unicode{x222D}}\limits}}
\CustomizeMathJax{\newcommand{\iiiintsl}{\mathop{\unicode{x2A0C}}\limits}}
\CustomizeMathJax{\let\ointsl\oint}
```

```
\CustomizeMathJax{\newcommand{\oiintsl}{\mathop{\unicode{x222F}}\limits}}
\CustomizeMathJax{\newcommand{\oiiintsl}{\mathop{\unicode{x2230}}\limits}}
\CustomizeMathJax{\newcommand{\varointclockwisesl}{\mathop{\unicode{x2232}}\limits}}
\CustomizeMathJax{\newcommand{\ointctrclockwisesl}{\mathop{\unicode{x2233}}\limits}}
\CustomizeMathJax{\newcommand{\sumintsl}{\mathop{\unicode{x2A0B}}\limits}}
\CustomizeMathJax{\newcommand{\fintsl}{\mathop{\unicode{x2A0F}}\limits}}
\CustomizeMathJax{\newcommand{\sqintsl}{\mathop{\unicode{x2A16}}\limits}}
%
\CustomizeMathJax{\let\intup\int}
\CustomizeMathJax{\newcommand{\iintup}{\mathop{\unicode{x222C}}\limits}}
\CustomizeMathJax{\newcommand{\iiintup}{\mathop{\unicode{x222D}}\limits}}
\CustomizeMathJax{\newcommand{\iiiintup}{\mathop{\unicode{x2A0C}}\limits}}
\CustomizeMathJax{\let\ointup\oint}
\CustomizeMathJax{\newcommand{\oiintup}{\mathop{\unicode{x222F}}\limits}}
\CustomizeMathJax{\newcommand{\oiiintup}{\mathop{\unicode{x2230}}\limits}}
\CustomizeMathJax{\newcommand{\varointclockwiseup}{\mathop{\unicode{x2232}}\limits}}
\CustomizeMathJax{\newcommand{\ointctrclockwiseup}{\mathop{\unicode{x2233}}\limits}}
\CustomizeMathJax{\newcommand{\sumintup}{\mathop{\unicode{x2A0B}}\limits}}
\CustomizeMathJax{\newcommand{\fintup}{\mathop{\unicode{x2A0F}}\limits}}
\CustomizeMathJax{\newcommand{\sqintup}{\mathop{\unicode{x2A16}}\limits}}
%
\CustomizeMathJax{\newcommand{\bigcupdot}{\mathop{\unicode{x2A03}}}}
\CustomizeMathJax{\newcommand{\bigcupplus}{\mathop{\unicode{x2A04}}}}
\CustomizeMathJax{\newcommand{\bigsqcap}{\mathop{\unicode{x2A05}}}}
%


%
\CustomizeMathJax{\newcommand{\bigtimes}{\mathop{\unicode{x2A09}}}}
\CustomizeMathJax{\let\varprod\bigtimes}
%


\CustomizeMathJax{\newcommand{\mappedfrom}{\mathrel{\unicode{x021A4}}}}
\CustomizeMathJax{\let\mappedfromchar\mappedfrom}
\CustomizeMathJax{\newcommand{\mapsfrom}{\mathrel{\unicode{x021A4}}}}
\CustomizeMathJax{\newcommand{\longmappedfrom}{\mathrel{\unicode{x027FB}}}}
%
\CustomizeMathJax{\newcommand{\Mapsto}{\mathrel{\unicode{x02907}}}}
\CustomizeMathJax{\let\Mapstochar\Mapsto}
\CustomizeMathJax{\newcommand{\Longmapsto}{\mathrel{\unicode{x027FE}}}}
\CustomizeMathJax{\newcommand{\Mappedfrom}{\mathrel{\unicode{x02906}}}}
\CustomizeMathJax{\let\Mappedfromchar\Mappedfrom}
\CustomizeMathJax{\newcommand{\Mapsfrom}{\mathrel{\unicode{x02906}}}}
\CustomizeMathJax{\newcommand{\Longmappedfrom}{\mathrel{\unicode{x27FD}}}}
%


\CustomizeMathJax{\newcommand{\medcirc}{\mathbin{\unicode{x025CB}}}}
\CustomizeMathJax{\newcommand{\medbullet}{\mathbin{\unicode{x025CF}}}}
\CustomizeMathJax{\newcommand{\varparallel}{\mathrel{\unicode{x02AFD}}}}
\CustomizeMathJax{\newcommand{\varparallelinv}{\mathrel{\unicode{x244A}}}}
\CustomizeMathJax{\newcommand{\nvarparallel}{\mathrel{\LWRoverlaysymbols{-}{\unicode{x02AFD}}}}}
\CustomizeMathJax{\newcommand{\nvarparallelinv}{\mathrel{\LWRoverlaysymbols{-}{\unicode{x244A}}}}}
%
```

```
\CustomizeMathJax{\newcommand{\coloneq}{\mathrel{\unicode{x02254}}}}
\CustomizeMathJax{\newcommand{\eqcolon}{\mathrel{\unicode{x02255}}}}
%
\CustomizeMathJax{\newcommand{\VDash}{\mathrel{\unicode{x22AB}}}}


%
\CustomizeMathJax{\newcommand{\preceqq}{\mathrel{\unicode{x02AB3}}}}
\CustomizeMathJax{\newcommand{\succeqq}{\mathrel{\unicode{x02AB4}}}}
%

\CustomizeMathJax{\newcommand{\nprecsim}{\mathrel{\LWRoverlaysymbols{/}{\unicode{x0227E}}}}}
\CustomizeMathJax{\newcommand{\nsuccsim}{\mathrel{\LWRoverlaysymbols{/}{\unicode{x0227F}}}}}
\CustomizeMathJax{\newcommand{\nlesssim}{\mathrel{\unicode{x02274}}}}
\CustomizeMathJax{\newcommand{\ngtrsim}{\mathrel{\unicode{x02275}}}}
%


\CustomizeMathJax{\newcommand{\nsubset}{\mathrel{\unicode{x02284}}}}
\CustomizeMathJax{\newcommand{\nsupset}{\mathrel{\unicode{x02285}}}}
\CustomizeMathJax{\newcommand{\notni}{\mathrel{\unicode{x220C}}}}
\CustomizeMathJax{\let\notowns\notni}
%
\CustomizeMathJax{\newcommand{\nlessapprox}{\mathrel{\LWRoverlaysymbols{/}{\unicode{x02A85}}}}}
\CustomizeMathJax{\newcommand{\ngtrapprox}{\mathrel{\LWRoverlaysymbols{/}{\unicode{x02A86}}}}}
%
\CustomizeMathJax{\newcommand{\npreccurlyeq}{\mathrel{\LWRoverlaysymbols{/}{\unicode{x0227C}}}}}
\CustomizeMathJax{\newcommand{\nsucccurlyeq}{\mathrel{\LWRoverlaysymbols{/}{\unicode{x0227D}}}}}
\CustomizeMathJax{\newcommand{\ngtrless}{\mathrel{\unicode{x02279}}}}
\CustomizeMathJax{\newcommand{\nlessgtr}{\mathrel{\unicode{x2278}}}}
\CustomizeMathJax{\newcommand{\nbumpeq}{\mathrel{\LWRoverlaysymbols{/}{\unicode{x0224F}}}}}
\CustomizeMathJax{\newcommand{\nBumpeq}{\mathrel{\LWRoverlaysymbols{/}{\unicode{x0224E}}}}}
%
\CustomizeMathJax{\newcommand{\nbacksim}{\mathrel{\LWRoverlaysymbols{/}{\unicode{x0223D}}}}}
\CustomizeMathJax{\newcommand{\nbacksimeq}{\mathrel{\LWRoverlaysymbols{/}{\unicode{x022CD}}}}}
\CustomizeMathJax{\newcommand{\nasymp}{\mathrel{\unicode{x226D}}}}
\CustomizeMathJax{\newcommand{\nequiv}{\mathrel{\unicode{x2262}}}}
\CustomizeMathJax{\newcommand{\napprox}{\mathrel{\unicode{x2249}}}}
%
\CustomizeMathJax{\newcommand{\nll}{\mathrel{\LWRoverlaysymbols{/}{\unicode{x0226A}}}}}
\CustomizeMathJax{\newcommand{\ngg}{\mathrel{\LWRoverlaysymbols{/}{\unicode{x0226B}}}}}
\CustomizeMathJax{\newcommand{\nthickapprox}{%
    \mathrel{\LWRoverlaysymbols{/}{{\mathbf{\unicode{x02248}}}}}%
}}
\CustomizeMathJax{\newcommand{\napproxeq}{\mathrel{\LWRoverlaysymbols{/}{\unicode{x0224A}}}}}
\CustomizeMathJax{\newcommand{\nprecapprox}{\mathrel{\LWRoverlaysymbols{/}{\unicode{x02AB7}}}}}
\CustomizeMathJax{\newcommand{\nsuccapprox}{\mathrel{\LWRoverlaysymbols{/}{\unicode{x02AB8}}}}}
\CustomizeMathJax{\newcommand{\npreceqq}{\mathrel{\LWRoverlaysymbols{/}{\unicode{x02AB3}}}}}
\CustomizeMathJax{\newcommand{\nsucceqq}{\mathrel{\LWRoverlaysymbols{/}{\unicode{x02AB4}}}}}
\CustomizeMathJax{\newcommand{\nsimeq}{\mathrel{\unicode{x02244}}}}
%
\CustomizeMathJax{\newcommand{\nSubset}{\mathrel{\LWRoverlaysymbols{/}{\unicode{x022D0}}}}}
\CustomizeMathJax{\newcommand{\nSupset}{\mathrel{\LWRoverlaysymbols{/}{\unicode{x022D1}}}}}
\CustomizeMathJax{\newcommand{\nsqsubseteq}{\mathrel{\unicode{x022E2}}}}
\CustomizeMathJax{\newcommand{\nsqsupseteq}{\mathrel{\unicode{x022E3}}}}
%
\CustomizeMathJax{\newcommand{\coloneqq}{\mathrel{\unicode{x02254}}}}
```

```
\CustomizeMathJax{\newcommand{\eqqcolon}{\mathrel{\unicode{x02255}}}}
\CustomizeMathJax{\newcommand{\Coloneqq}{\mathrel{\unicode{x02A74}}}}
\CustomizeMathJax{\newcommand{\Coloneq}{\mathrel{\unicode{x2237}-}}}
\CustomizeMathJax{\newcommand{\Eqcolon}{\mathrel{-\unicode{x2237}}}}
%
\CustomizeMathJax{\newcommand{\lvec}[1]{\mathord{\overset{\unicode{x02190}}{#1}}}}
\CustomizeMathJax{\newcommand{\lrvec}[1]{\mathord{\overset{\unicode{x2194}}{#1}}}}
\CustomizeMathJax{\newcommand{\harpoonacc}[1]{\mathord{\overset{\unicode{x021C0}}{#1}}}}
\CustomizeMathJax{\newcommand{\lharpoonacc}[1]{\mathord{\overset{\unicode{x021BC}}{#1}}}}
\CustomizeMathJax{\newcommand{\lrharpoonacc}[1]{\mathord{\overset{\unicode{x0294E}}{#1}}}}
\CustomizeMathJax{\newcommand{\barbar}[1]{\mathord{\overset{=}{#1}}}}
\CustomizeMathJax{\newcommand{\bartilde}[1]{\mathord{\overset{\simeq}{#1}}}}
\CustomizeMathJax{\newcommand{\barhat}[1]{\mathord{\hat{\bar{#1}}}}}
\CustomizeMathJax{\newcommand{\tildebar}[1]{\mathord{\overset{\eqsim}{#1}}}}
\CustomizeMathJax{\newcommand{\tildetilde}[1]{\mathord{\overset{\approx}{#1}}}}
\CustomizeMathJax{\newcommand{\tildehat}[1]{\mathord{\hat{\tilde{#1}}}}}
\CustomizeMathJax{\newcommand{\hatbar}[1]{\mathord{\bar{\hat{#1}}}}}
\CustomizeMathJax{\newcommand{\hattilde}[1]{\mathord{\tilde{\hat{#1}}}}}
\CustomizeMathJax{\newcommand{\hathat}[1]{\mathord{\hat{\hat{#1}}}}}

\CustomizeMathJax{\newcommand{\cdotB}{\mathord{\boldsymbol{\cdot}}}}
\CustomizeMathJax{\newcommand{\cdotBB}{\mathord{\unicode{x2022}}}}
\CustomizeMathJax{\newcommand{\circS}{\boldsymbol{\circ}}}
\CustomizeMathJax{\newcommand{\bulletSSS}{\bullet}}
\CustomizeMathJax{\newcommand{\bulletSS}{\mathord{\unicode{x025CF}}}}
\CustomizeMathJax{\newcommand{\bulletS}{\mathord{\unicode{x02B24}}}}
\CustomizeMathJax{\newcommand{\primeS}{\prime}}

\CustomizeMathJax{\newcommand{\invamp}{\mathbin{\unicode{x0214B}}}}
```

`lwarp_mathjax.txt` adds `\left`/`\right` support for delimiters.

```
\CustomizeMathJax{\newcommand{\Lbag}{\mathopen{\large\unicode{x027C5}}}}
\CustomizeMathJax{\newcommand{\Rbag}{\mathclose{\large\unicode{x027C6}}}}
\CustomizeMathJax{\newcommand{\circledless}{\mathrel{\unicode{x029C0}}}}
\CustomizeMathJax{\newcommand{\circledgtr}{\mathrel{\unicode{x029C1}}}}
\CustomizeMathJax{\newcommand{\circledbslash}{\mathbin{\unicode{x029B8}}}}


\CustomizeMathJax{\newcommand{\lJoin}{\mathrel{\unicode{x22C9}}}}
\CustomizeMathJax{\newcommand{\rJoin}{\mathrel{\unicode{x22CA}}}}
\CustomizeMathJax{\newcommand{\lrJoin}{\mathrel{\unicode{x2A1D}}}}

\CustomizeMathJax{\newcommand{\lrtimes}{\mathrel{\unicode{x2A1D}}}}
\CustomizeMathJax{\newcommand{\Diamondblack}{\mathord{\unicode{x025C6}}}}
\CustomizeMathJax{\newcommand{\nplus}{\mathrel{\LWRoverlaysymbols{+}{\unicode{x02229}}}}}
\CustomizeMathJax{\newcommand{\nsqsubset}{\mathrel{\LWRoverlaysymbols{/}{\unicode{x0228F}}}}}
\CustomizeMathJax{\newcommand{\nsqsupset}{\mathrel{\LWRoverlaysymbols{/}{\unicode{x02290}}}}}
\CustomizeMathJax{\newcommand{\dasharrow}{\mathrel{\unicode{x021E2}}}}
\CustomizeMathJax{\newcommand{\leftsquigarrow}{\mathrel{\unicode{x021DC}}}}
\CustomizeMathJax{\newcommand{\ntwoheadrightarrow}{\mathrel{\unicode{x02900}}}}
\CustomizeMathJax{\newcommand{\ntwoheadleftarrow}{\mathrel{\unicode{x02B34}}}}
\CustomizeMathJax{\newcommand{\boxast}{\mathbin{\unicode{x029C6}}}}
\CustomizeMathJax{\newcommand{\boxbslash}{\mathbin{\unicode{x29C5}}}}
\CustomizeMathJax{\newcommand{\boxbar}{\mathbin{\unicode{x025EB}}}}
\CustomizeMathJax{\newcommand{\boxslash}{\mathbin{\unicode{x029C4}}}}
```

```
235
236 \CustomizeMathJax{\newcommand{\varclubsuit}{\mathord{\unicode{x02667}}}}
237 \CustomizeMathJax{\newcommand{\vardiamondsuit}{\mathord{\unicode{x02666}}}}
238 \CustomizeMathJax{\newcommand{\varheartsuit}{\mathord{\unicode{x02665}}}}
239 \CustomizeMathJax{\newcommand{\varspadesuit}{\mathord{\unicode{x02664}}}}
240
241 \CustomizeMathJax{\newcommand{\Nearrow}{\mathrel{\unicode{x021D7}}}}
242 \CustomizeMathJax{\newcommand{\Searrow}{\mathrel{\unicode{x021D8}}}}
243 \CustomizeMathJax{\newcommand{\Nwarrow}{\mathrel{\unicode{x021D6}}}}
244 \CustomizeMathJax{\newcommand{\Swarrow}{\mathrel{\unicode{x021D9}}}}
245 \CustomizeMathJax{\newcommand{\Top}{\mathord{\unicode{x02AEA}}}}
246 \CustomizeMathJax{\newcommand{\Bot}{\mathord{\unicode{x02AEB}}}}
247
248 \CustomizeMathJax{\newcommand{\leadstoext}{\mathrel{\unicode{xFF5E}}}}
249
250 \CustomizeMathJax{\newcommand{\sqcupplus}{\mathbin{\LWRoverlaysymbols{+}{\unicode{x02294}}}}}
251 \CustomizeMathJax{\newcommand{\sqcapplus}{\mathbin{\LWRoverlaysymbols{+}{\unicode{x02293}}}}}
252
253 \CustomizeMathJax{\newcommand{\dlb}{\mathopen{\unicode{x027E6}}}}
254 \CustomizeMathJax{\newcommand{\drb}{\mathopen{\unicode{x027E7}}}}
255
256 \CustomizeMathJax{\newcommand{\varg}{g}}
257 \CustomizeMathJax{\newcommand{\vary}{y}}
258 \CustomizeMathJax{\newcommand{\varv}{v}}
259 \CustomizeMathJax{\newcommand{\varw}{w}}
260
261 \CustomizeMathJax{\newcommand{\nexistsAlt}{\mathord{\unicode{x02204}}}}
262 \CustomizeMathJax{\newcommand{\existsAlt}{\mathord{\unicode{x02203}}}}
263 \CustomizeMathJax{\newcommand{\forallAlt}{\mathord{\unicode{x02200}}}}
264 \CustomizeMathJax{\newcommand{\emptysetAlt}{\mathord{\unicode{x02205}}}}
265
266 \CustomizeMathJax{\newcommand{\uppartial}{\mathord{\unicode{x02202}}}}% not upright
267
268 \CustomizeMathJax{\let\varmathbb\mathbb}
269 \CustomizeMathJax{\let\vmathbb\mathbb}
270 \CustomizeMathJax{\let\vvmathbb\mathbb}
271
272 \CustomizeMathJax{\let\smallprod\prod}
273 \CustomizeMathJax{\let\smallsum\sum}
274 \CustomizeMathJax{\let\smallcoprod\coprod}
275
276 \CustomizeMathJax{\newcommand{\openbox}{\mathord{\unicode{x25FD}}}}
277 \CustomizeMathJax{\let\textsquare\openbox}


278 \CustomizeMathJax{\let\varemptyset\emptyset}
279 %
280 % for newpxmath:
281 \CustomizeMathJax{\newcommand{\mathsterling}{\mathord{\unicode{x000A3}}}}
282 \CustomizeMathJax{\newcommand{\mathcent}{\mathord{\unicode{x000A2}}}}
283
284 \end{warpMathJax}
```

File 578 **lwarp-common-mathjax-nonunicode.sty**

§ 686 Package

common-mathjax-nonunicode

(*Emulates or patches code by* Daniel Flipo, Michael Sharpe.)

Pkg lwarp-common-mathjax-nonunicode

Common code used by newpxmath, newtxmath, newtxsf, kpfonts-otf for MathJax. These are symbols not found in Unicode.

Factored from lwarp-common-mathjax-newpxtxmath.

for HTML output:

```
\ProvidesPackage{lwarp-common-mathjax-nonunicode}[2020/09/20]
```

For MathJax:

```
\LWR@origRequirePackage{lwarp-common-mathjax-overlaysymbols}

\begin{warpMathJax}
\CustomizeMathJax{\newcommand{\mmapsto}{\mathrel{\unicode{x021A6}}}}
\CustomizeMathJax{\let\mmapstochar\mmapsto}
\CustomizeMathJax{\newcommand{\longmmapsto}{\mathrel{\unicode{x021A6}}}}
\CustomizeMathJax{\newcommand{\mmappedfrom}{\mathrel{\unicode{x021A4}}}}
\CustomizeMathJax{\let\mmappedfromchar\mmappedfrom}
\CustomizeMathJax{\newcommand{\longmmappedfrom}{\mathrel{\unicode{x021A4}}}}
\CustomizeMathJax{\let\mmapsfrom\mmappedfrom}% from kpfonts-otf
\CustomizeMathJax{\let\longmmapsfrom\longmmappedfrom}% from kpfonts-otf

\CustomizeMathJax{\newcommand{\Mmapsto}{\mathrel{\unicode{x02907}}}}
\CustomizeMathJax{\let\Mmapstochar\Mmapsto}
\CustomizeMathJax{\newcommand{\Longmmapsto}{\mathrel{\unicode{x027FE}}}}
\CustomizeMathJax{\newcommand{\Mmappedfrom}{\mathrel{\unicode{x02906}}}}
\CustomizeMathJax{\let\Mmappedfromchar\Mmappedfrom}
\CustomizeMathJax{\newcommand{\Longmmappedfrom}{\mathrel{\unicode{x027FD}}}}
\CustomizeMathJax{\let\Mmapsfrom\Mmappedfrom}% from kpfonts-otf
\CustomizeMathJax{\let\Longmmapsfrom\Longmmappedfrom}% from kpfonts-otf
%
\CustomizeMathJax{\newcommand{\boxright}{\mathrel{\unicode{x025A1}\!\unicode{x02192}}}}
\CustomizeMathJax{\newcommand{\boxleft}{\mathrel{\unicode{x02190}\!\unicode{x025A1}}}}
\CustomizeMathJax{\newcommand{\boxdotright}{\mathrel{\unicode{x022A1}\!\unicode{x02192}}}}
\CustomizeMathJax{\newcommand{\boxdotleft}{\mathrel{\unicode{x02190}\!\unicode{x022A1}}}}

\CustomizeMathJax{\newcommand{\Diamondright}{\mathrel{\unicode{x025C7}\!\unicode{x02192}}}}
\CustomizeMathJax{\newcommand{\Diamondleft}{\mathrel{\unicode{x02190}\!\unicode{x025C7}}}}
\CustomizeMathJax{\newcommand{\Diamonddotright}{\mathrel{\unicode{x027D0}\!\unicode{x02192}}}}
\CustomizeMathJax{\newcommand{\Diamonddotleft}{\mathrel{\unicode{x02190}\!\unicode{x027D0}}}}

\CustomizeMathJax{\newcommand{\boxRight}{\mathrel{\unicode{x025A1}\!\unicode{x021D2}}}}
\CustomizeMathJax{\newcommand{\boxLeft}{\mathrel{\unicode{x021D0}\!\unicode{x025A1}}}}
\CustomizeMathJax{\newcommand{\boxdotRight}{\mathrel{\unicode{x022A1}\!\unicode{x021D2}}}}
\CustomizeMathJax{\newcommand{\boxdotLeft}{\mathrel{\unicode{x021D0}\!\unicode{x022A1}}}}

\CustomizeMathJax{\newcommand{\DiamondRight}{\mathrel{\unicode{x025C7}\!\unicode{x021D2}}}}
\CustomizeMathJax{\newcommand{\DiamondLeft}{\mathrel{\unicode{x021D0}\!\unicode{x025C7}}}}
\CustomizeMathJax{\newcommand{\DiamonddotRight}{\mathrel{\unicode{x027D0}\!\unicode{x021D2}}}}
\CustomizeMathJax{\newcommand{\DiamonddotLeft}{\mathrel{\unicode{x021D0}\!\unicode{x027D0}}}}
\CustomizeMathJax{\newcommand{\Diamonddot}{\mathrel{\unicode{x027D0}}}}

```

```
\CustomizeMathJax{\newcommand{\circleright}{\mathrel{\unicode{x025CB}\!\unicode{x02192}}}}
\CustomizeMathJax{\newcommand{\circleleft}{\mathrel{\unicode{x02190}\!\unicode{x025CB}}}}
\CustomizeMathJax{\newcommand{\circledotright}{\mathrel{\unicode{x02299}\!\unicode{x02192}}}}
\CustomizeMathJax{\newcommand{\circledotleft}{\mathrel{\unicode{x02190}\!\unicode{x02299}}}}
\CustomizeMathJax{\let\circleddotright\circledotright}
\CustomizeMathJax{\let\circleddotleft\circledotleft}

\CustomizeMathJax{\newcommand{\multimapinv}{\mathrel{\unicode{x027DC}}}}
\CustomizeMathJax{\newcommand{\multimapboth}{\mathrel{\unicode{x029DF}}}}
\CustomizeMathJax{\newcommand{\multimapdot}{{\mathrel{-\!\bullet}}}}
\CustomizeMathJax{\newcommand{\multimapdotinv}{\mathrel{\bullet\!-}}}
\CustomizeMathJax{\newcommand{\multimapdotboth}{\mathrel{{\bullet\!\!-\!\!\bullet}}}}
\CustomizeMathJax{\newcommand{\multimapdotbothA}{\mathrel{\unicode{x022B6}}}}
\CustomizeMathJax{\newcommand{\multimapdotbothB}{\mathrel{\unicode{x22B7}}}}

\CustomizeMathJax{\newcommand{\multimapbothvert}{%
    \mathrel{\overset{\unicode{x025CB}}{\underset{\unicode{x025CB}}{|}}}%
}}
\CustomizeMathJax{\newcommand{\multimapdotbothvert}{%
    \mathrel{\overset{\unicode{x025CF}}{\underset{\unicode{x025CF}}{|}}}%
}}
\CustomizeMathJax{\newcommand{\multimapdotbothBvert}{% bug in kpfonts-otf
    \mathrel{\overset{\unicode{x025CF}}{\underset{\unicode{x025CB}}{|}}}%
}}
\CustomizeMathJax{\newcommand{\multimapdotbothAvert}{% bug in kpfonts-otf
    \mathrel{\overset{\unicode{x025CB}}{\underset{\unicode{x025CF}}{|}}}%
}}

\CustomizeMathJax{\newcommand{\bignplus}{%
    \mathop{\LWRoverlaysymbols{\unicode{xFF0B}}{\unicode{x22C2}}}%
}}
\CustomizeMathJax{\let\bigcapplus\bignplus}
\CustomizeMathJax{\let\capplus\bignplus}% from kpfonts-otf

\CustomizeMathJax{\newcommand{\bigsqcapplus}{%
    \mathop{\LWRoverlaysymbols{\unicode{xFF0B}}{\unicode{x2A05}}}
}}
\CustomizeMathJax{\let\sqcapplus\bigsqcapplus}% from kpfonts-otf

\CustomizeMathJax{\newcommand{\bigsqcupplus}{%
    \mathop{\LWRoverlaysymbols{\unicode{xFF0B}}{\unicode{x2A06}}}
}}
\CustomizeMathJax{\let\sqcupplus\bigsqcupplus}% from kpfonts-otf

\CustomizeMathJax{\newcommand{\parallelslant}{\mathrel{\unicode{x02AFD}}}}
\CustomizeMathJax{\newcommand{\parallelbackslant}{%
    \mathrel{\unicode{x0005C}\!\!\unicode{x0005C}}%
}}

\CustomizeMathJax{\newcommand{\Eqqcolon}{\mathrel{=\!\unicode{x2237}}}}
\CustomizeMathJax{\let\eqqColon\Eqqcolon}% for kpfonts-otf
\CustomizeMathJax{\newcommand{\dashColon}{\mathrel{-\unicode{x2237}}}}
\CustomizeMathJax{\newcommand{\Colondash}{\mathrel{\unicode{x2237}-}}}

\CustomizeMathJax{\newcommand{\colonapprox}{\mathrel{:\approx}}}
```

```
\CustomizeMathJax{\newcommand{\colonsim}{\mathrel{:\sim}}}
\CustomizeMathJax{\newcommand{\Colonapprox}{\mathrel{\unicode{x2237}\!\approx}}}
\CustomizeMathJax{\newcommand{\Colonsim}{\mathrel{\unicode{x2237}\!\sim}}}

\CustomizeMathJax{\newcommand{\strictif}{\mathrel{\unicode{x0297D}}}}% right fish tail
\CustomizeMathJax{\newcommand{\strictfi}{\mathrel{\unicode{x0297C}}}}% left fish tail
\CustomizeMathJax{\newcommand{\strictiff}{%
    \mathrel{\unicode{x0297C}\!\!\unicode{x0297D}}%
}}% left/right fish tails

\CustomizeMathJax{\newcommand{\circledwedge}{%
    \mathbin{\LWRoverlaysymbols{\unicode{x025EF}}{\unicode{x02227}}}%
}}
\CustomizeMathJax{\newcommand{\circledvee}{%
    \mathbin{\LWRoverlaysymbols{\unicode{x025EF}}{\unicode{0x02228}}}%
}}
\CustomizeMathJax{\newcommand{\circledbar}{\mathbin{\unicode{x029B6}}}}

\CustomizeMathJax{\newcommand{\openJoin}{\mathrel{\unicode{x2AA4}}}}% overlapping ><
\CustomizeMathJax{\newcommand{\opentimes}{\mathrel{\unicode{x2AA4}}}}% overlapping ><

\CustomizeMathJax{\newcommand{\VvDash}{\mathrel{\unicode{x22AA}}}}

\CustomizeMathJax{\newcommand{\lambdabar}{%
    \mathord{\LWRoverlaysymbols{\raise{.5ex}{-}}{\lambda}}%
}}

\CustomizeMathJax{\newcommand{\lambdaslash}{\mathord{\unicode{x019B}}}}

\CustomizeMathJax{\newcommand{\Wr}{\mathbin{\unicode{x02240}\!\unicode{x02240}}}}

\CustomizeMathJax{\newcommand{\dashleftrightarrow}{%
    \mathrel{\unicode{x021E0}\!\unicode{x021E2}}%
}}
\CustomizeMathJax{\let\leftrightdasharrow\dashleftrightarrow}% for kpfonts-otf

\end{warpMathJax}
```

File 579 **lwarp-common-mathjax-overlaysymbols.sty**

§ 687 Package

common-mathjax-overlaysymbols

Pkg lwarp-common-mathjax-overlaysymbols

Common code used by a number of packages to overlay two symbols for MathJax.

for HTML output:

```
\ProvidesPackage{lwarp-common-mathjax-overlaysymbols}[2020/08/17]
```

\LWRoverlaysymbols {⟨*symbol*⟩} {⟨*symbol*⟩}

Overlays one symbol over another.

```
\begin{warpMathJax}

\CustomizeMathJax{\newcommand{\LWRoverlaysymbols}[2]{%
```

```
    \mathord{%
        \smash{%
            \mathop{#2\strut}%
            \limits^{\smash{\lower3ex{#1}}}%
        }%
        \strut%
    }%
}}

\end{warpMathJax}
```

Change History

§ 688 ## Chg Hist

For the most recent changes, see page 1352.

v0.0.895
General: maybemath: Added. 958
v0.10
General: 2016/03/08 Initial version 1
v0.11
General: 2016/03/11 1
Added section: Operating-System portability. 229
Added section: Selecting the operating system. 119
Test Suite: MS-Windows in README.txt 1
Test Suite: limages and index in README.txt 1
v0.12
\LWR@newhtmlfile: Bugfix: TOC with numbered files. 397
General: 2016/03/14 1
Global: Uses \p@(type) in float captions. 1
Test Suite: Sub-figures 1
v0.13
\CaptionSeparator: Fix for newer babel package. 524
\LWR@LwarpStart: \up and \fup . . . 416
General: 2016/03/24 1
Fix dollar-redefined bug for newer package. 1185
Removed package: subfig 1
Test Suite: Ordinals, Subcaption 1
v0.14
\LWR@htmlsectionfilename: Fix: Links to home page. 348
General: 2016/03/31 1
floatrow: Added. 818
Docs: Commands for a successful HTML conversion. 123
Docs: Commands into a warpprint environment. 120
Docs: Newclude limitations. 175
Docs: Table: Cross-referencing data structures. 507
Docs: Table: Float data structures. 520
Docs: Trademarks section. 201
Docs: Troubleshooting cross-references. 196
Test Suite: Assigned cleveref name for Test Float. 1
Test Suite: Floatrow 1
v0.15
General: 2016/04/06 1
Added. 822
Ampersand (&): Fixed handling when passed as an argument. 454
Docs: Added warning icons for items needing special attention. 204
Docs: Clarify print/HTML output. . 119
Docs: Moved the supported features table to the introduction. 68
Files: lwarp_formal.css added. 1
Fix: steps counter 822
Fixed & handling. 820
Test Suite: test_suite_formal.css file added. 1
v0.16
General: 2016/04/11 1
\titlingpage: Improved print-output spacing. 425
xfrac: Adjusted for the use of any font: 1250
Added XeLaTeX, LuaLaTeX support. 205
Docs: Font and UTF-8 support. . . 103
Docs: Moved location of \usepackage{lwarp}. 106
Docs: Text not converting. 196
Lwarp no longer selects fonts. 103, 240
Removed package: suffix 1
Test Suite: Improved titlingpage. . 425
Test Suite: Lwarp no longer selects fonts. 1
Test Suite: Supports XeLaTeX, LuaLaTeX. 1
v0.17
\LWR@htmlsectionfilename: Fix: Links when entire doc is one HTML page. 348
General: 2016/04/14 1
mdframed: Added. 958
Test Suite: Fix: Print-version front-matter page numbers. 1
Test Suite: Mdframed 1

v0.18
\LWR@myshorttoc: Reorganize \HomeHTMLFilename logic. 529
\LWR@newhtmlfile: sideTOC after title, improving responsive design. . . . 396
\LWR@requesttoc: Reorganize \HomeHTMLFilename logic. 418
\LWR@subhyperref: Improved HTML output linebreaks. 517
\LWR@subhyperrefclass: Improved HTML output linebreaks. 517
\LWR@subinlineimage: Suppress extra space. 518
\hspace: \hspace supported. 623
General: 2016/05/19 1
graphics: Add: SVG file extension. . 855
graphics: Fix: \linewidth, \textwidth, \textheight inside a minipage. 855
graphics: Improved HTML output linebreaks. 855
graphics: em, ex, %, px dimensions preserved. 855
File: lwarp.css: Improved TOC outline display. 1
Files: lwarp.css and lwarp_formal.css: Improved responsive design. 1
Microtype disabled during HTML generation 241
PDF Unicode input characters. . . . 223
Test Suite: Verse package 1
lateximage: pdfcrop: --hires added. . 581
Reorganize \HomeHTMLFilename logic. 581
Suppress extra space. 581
verse: Supports verse, memoir packages. 1227
minipage: Fix: \linewidth, \textwidth, \textheight inside a minipage. 601
v0.19
\HTMLFilename: Docs: Escape filename underscores. 347
\HomeHTMLFilename: Docs: Escape filename underscores. 347
\LWR@LwarpStart: Enabled \\ equal to \newline. 415
\LWR@doequation: MathJax support. 569
\LWR@doubledollar: MathJax support. 562
\LWR@filestart: lwarp_mathjax.txt loaded. 412
\LWR@minipagestartpars: Suppresses paragraph tags between minipages. 622
\LWR@subsingledollar: MathJax support. 560
\LateximageFontSizeName: Add: User-adjustable math/lateximage font size. 578
\hspace: Fix: \hspace length computations. 623
\minipagefullwidth: Added: No width tag for the next minipage in HTML. 600
\warpHTMLonly: Added. 239
\warpprintonly: Replaces \rowprintedonly. 238
\xfracHTMLfontsize: Added. 1250
General: 2016/06/08 1
CSS for table note item. 1182
MathJax support added. 566, 573, 574
multirow: Added optional args. . . 990
xcolor: Supports colored \rule. . . 1240
Adapts to tikz version. 1185
Avoids MathJax. 553
cleveref: Loaded \AtEndPreamble. 598
Docs: Math options. 106
Docs: Table: Cross-referencing data structures, updated. 507
File: lwarp.css: tnoteitemheader added. 1
File: lwarp_mathjax.txt added. . . . 1
Introduction: MathJax support mentioned. 65
Options: mathsvg and mathjax . . 233
titleps: null \pagestyle and \thispagestyle for HTML. . . . 1186
v0.20
\BlockClassSingle: Renamed from "LWR@htmldivclassline". 364
\HTMLDescription: Added \NewHTMLdescription. (Renamed in v0.30.) 375
\HTMLFilename: No longer escape underscores. 347
\HomeHTMLFilename: No longer escape underscores. 347
\InlineClass: Renamed from "inlineclass". 364
\LWR@closeparagraph: \unskip extra spaces. 368
No break tags in the start/end of a tabular. 368
\LWR@endofline: Fix: \\ 622
\LWR@filestart: Adds meta description. 412
\LWR@htmldivclass: Added optional style. 362

\LWR@htmlelementclass: Added optional style. 362
\LWR@htmlsectionfilename: HTMLFilename: removed additional trailing '-', and may be empty. 348
Sections called "Index" or "index" have an underscore prepended to their filenames if no prefix. 348
\LWR@hyperindexrefsubtwo: Print mode provided in case hyperref not used. 544
\LWR@longtabledatacaptiontag: Fix: Pars in captions. 491
\LWR@section: Combined higher-level sections together into files. 403
\LWR@setOSWindows: Auto-detects operating system. 231
\LWR@subhtmlelementclass: Factored code. 362
\SetHTMLFileNumber: Add: Control file numbers. 348
\cpagerefFor: User-redefinable word for page references. 748
\dotfill: Inserts an ellipsis. 621
\hfill: Inserts a \qquad. 621
\hrulefill: Inserts a short rule. . . . 621
\hspace: Add: Supports HTML thin breakable space. 623
\pageref: Added. 515
\tracinglwarp: Added. 255
General: 2017/02/09 1
afterpage: Added. 651
alltt: Added. 656
bookmark: Added. 696
caption and subcaption supported. . . 1
cleveref and referencing patches: Applied \AfterEndPreamble. . . . 747
draftwatermark: Added. 765
eso-pic: Added. 787
everypage: Added. 791
extramarks: Added. 792
fancyhdr: Added. 798
float: Improved float caption type handling. 815
graphics: Fix: Expands filename. . 855
graphics: Fix: \linewidth in a floatrow. 855
hyperref: Additional user macros. 867
keyfloat: Added. 893
letterspace: User-interface emulated. 907
listings: Added. 917
ltcaption: Added. 929
lwarp-newproject: Added. 267
microtype: User-interface emulated. 975
needspace: Added. 1001
nowidow: Added. 1018
placeins: Added. 1054
ragged2e: Added. 1063
setspace: Improved support. . . . 1089
textpos: Added. 1174
titleps: Added. 1186
titlesec: Added. 1189
titletoc: Added. 1191
titling: Improved compatibility. . . 1193
tocloft: Added. 1201
wallpaper: Added. 1232
wrapfig: Added. 1235
xetexko: Added. 1248
Added @, <, > columns. 447
Added single-expansion data arrays. 344
Code factored into independent lwarp_html files. 639
Docs: Examples for generating HTML file names. 117
Docs: Improved index. 1
Enhanced titling support. 424
File: lwarp.css: Minor fixes for validation. 1
File: lwarpmk used to compile print, HTML, indexes, and lateximages. . . 1
Fix: \linewidth in a floatrow. . . . 821
Moved sidebar and example code to test suite. 1
Page geometry set to 6in wide with large margins. 241
Parallel versions of aux files for print/HTML. 1
Removed reliance on make, grep, gawk. 1
Tabular: \unskip extra spaces. . . 447
Test Suite: HTML meta descriptions. . 1
verbatim: Added. 435
BlockClass: Added optional style. . . 364
Renamed from "blockclass". 364
LWR@nestspan: Fix: Minipages inside a span. 359
v0.21
\LWR@LwarpStart: Changed lateximages to a .txt file. 415
\LWR@filestart: Skip title if not given. 412
\LWR@newhtmlfile: Skip title if not given. 396
\marginpar: Fixed source listing. . . . 382
\marginparBlock: Fixed source listing. 382
General: 2017/02/23 1
fontenc: Added. 828
lwarpmk: Fix: **lwarpmk again** for Windows. 322

lwarpmk: Fix: **`lwarpmk limages`** for Windows. 322
lwarpmk: Fix: *lwarpmk* uses `latexmages` text file instead of shell script. 322
Add: Errors for misplaced packages. 205
Docs: Added internet class. 75
Docs: Added TeX2page, GladTeX. . . 75
Docs: Installing on Windows. 81
File: `lwarp_tutorial.txt` added. . 85
v0.22
`\LWR@parseDcolumn`: Added tabular `D` column. 463
`\LWR@parsebangcolumn`: Added tabular `!` column. 459
`\LWR@parsetablecols`: Unknown table column types become `l`. Added tabular `D`, `!`, `X` columns. 465
`\LWR@printmccoldata`: Added tabular `D`, `!`, and `X` columns. 485
General: 2017/03/02 1
abstract: Added. 641
changepage: Added. 712
dcolumn: Added. 759
ftnright: Added. 837
geometry: Nullified commands. . . 842
layout: Added. 903
lscape: Added. 928
mcaption: Added. 958
nameref: Added. 997
nextpage: Added. 1004
parskip: Added. 1039
showkeys: Added. 1091
sidecap: Added. 1093
tabularx: Added. 1157
varioref: Supported. 132
verse: Added. 1226
v0.23
`\LWR@parsetablecols`: Fix for vert bar column type. 465
`\LWR@printmccoldata`: Fix for vert bar column type. 485
General: 2017/03/02 1
v0.24
`\LWR@htmlfileref`: Fix: Index links while `\tracinglwarp`. 510
`\hspace`: Add: `\hspace \fill` converts to 2em 623
`\hypertocfloat`: List of floats responds to `lofdepth`, `lotdepth`. 535
General: 2017/03/15 1
floatrow: Support for subfig. . . . 818
subfig: Added. 1147
tikz: For tikz v3.0.0 or later, auto-loads tikz babel library if necessary. 1185
Docs: Filename underscore. . . 106, 126
Fix for inline images. 1185
No longer preloads subcaption; conflicted with subfig. 245
`picture`: Fix for inline images. . . . 598
v0.25
`\LWR@loadnever`: Added the ability to prevent conflicting packages. . . . 207
`\addcontentsline`: Handles theorems. 528
General: 2016/03/22 1
amsthm: Added. 661
ellipsis: Added. 770
emptypage: Added. 771
framed: Added. 834
lips: Added. 917
mdframed: Help avoid hyphenation. 960
ntheorem: Added. 1018
showidx: Added. 1091
theorem: Added. 1175
Basic LaTeX theorems: improved css. 436
Docs: Adds credits for patched code. . 1
Docs: Testing lwarp. 192
Fix: Allows XeLaTeX and LuaLaTeX to preload graphics and graphicx. . . 211
v0.26
General: 2017/03/31 1
`lwarp.css`: Improved responsive `marginpar` and `marginblock`. . . . 274
cutwin: Added. 758
endnotes: Added. 773
floatflt: Added. 816
footmisc: Added. 828
footnotehyper: Added. 830
footnote: Added. 829
marginfix: Added. 941
marginnote: Added. 941
mparhack: Added. 985
pagenote: Supported as-is. 1033
sidenotes: Added. 1093
Docs: Improved MiKTeX install instructions. 80, 82
Dollar span avoided in a lateximage. 553
Footnotes now are LaTeX boxes instead of pagenotes. 376
`lateximage`: Labels track page numbers of lateximages. 581
Print mode now uses a `minipage` of `\linewidth`. 581
`picture`: Fix for `\makebox` in `picture`. 598
v0.27
`\LWR@@footnotetext`: Fix for table footnote par tags. 378

General: 2017/04/04 1
lettrine: Added. 907
microtype: Fix with XeLaTeX, LuaLaTeX. 975
soul: Added. 1126
ulem: Added. 1216
Docs: Installing utilities for MacOS. 83
Docs: Limitations of saveboxes. . . 126
Page geometry modified to reduce line overflow. 241
v0.28
\@wrindex: Improved indexing. 539
\HTMLAuthor: Added \HTMLauthor. (Renamed in v0.30.) 375
\LWR@LwarpEnd: If FormatEPUB or FormatWP, no bottom nav. 418
\LWR@LwarpStart: FormatWordProcessor forces single-file output. 415
\LWR@filestart: Adds HTML meta author. 412
\LWR@forcenewpage: Forces new PDF page before major environments. . 354
\LWR@htmlcomment: Breaks ligatures in HTML comments. 361
\LWR@hyperindexrefsubtwo: Improved indexing. 544
\LWR@newhtmlfile: If FormatEPUB or FormatWP: skips headers, footers, nav. 396
\LWR@parsetablecols: Added L, C, R, J column types. 465
\LWR@startref: Removed space. . . . 513
\chapter: If EPUB, prints footnotes before each section. 410
\textup: Fixed span class. 612
General: 2017/04/14 1
glossaries: Added. 846
graphics: Adapts to graphics syntax. 855
graphics: Added. 847
tabularx: Fix for optional pos. . . . 1157
tabulary: Added. 1158
lwarpmk: Add: **printglossary** and **htmlglossary** commands. 322
Added boolean FormatEPUB. 260
Added boolean FormatWP. 261
Added boolean HTMLDebugComments. 255
Added boolean HTMLMarkFloats, changed to WPMarkFloats as of v0.42. 261
Docs: Modfying lwarpmk and index processing. 192
File: lwarp_mathjax.txt: Updated CDN repository. 318
Forced oneside to maintain large right margin. 241
v0.29
General: 2017/04/15 1
*.lwarpmkconf: Add: language option for config files. 274
lwarpmk.conf: Add: language option for config files. 274
graphics: Fix: Error when no optional arguments. 855
lwarpmk: Add: language option for config files. 322
Add: lwarpmklang option for lwarp. 234
Docs: Using a glossary 96
v0.30
\CSSFilename: Renamed from \NewCSS. 373
\HTMLAuthor: Renamed from \HTMLauthor. 375
\HTMLDescription: Renamed from \NewHTMLdescription. 375
\HTMLFirstPageTop: Renamed from \SetFirstPageTop. 373
\HTMLLanguage: Renamed from \MetaLanguage. 411
\HTMLPageBottom: Renamed from \SetPageBottom. 373
\HTMLPageTop: Renamed from \SetPageTop. 373
General: 2017/04/29 1
lwarp-newproject removed, and combined with lwarp. 267
lwarpmk: Add: xdyfile configuration option. 322
lwarpmk: Fix: *xindy* and *texindy* adjusted for *pdflatex*, *xelatex* and *lualatex*. 322
lwarpmk: Fix: *xindy* now used for print index generation with *latexmk*. 322
lwarpmk: language now used for both index and glossary generation. 322
File: lwarp_html.xdy renamed to lwarp.xdy. 316
Fix: *.css files only written in print mode. 274
Fix: lwarp.xdy only written in print mode. 316
Fix: lwarp_mathjax.txt: Only written in print mode. 318
Option lwarpmklang changed to IndexLanguage. 234
Option OSWindows replaces macro \warpOSwindows. 234
Option xdyFilename added. 233

Option *latexmk* replaces macro \UseLatexmk. 236
Options HomeHTMLFilename and HTMLFilename replace macros \HomeHTMLFilename and \HTMLFilename. 234
v0.31
General: 2017/05/15 1
keyfloat: Improved compatibility. . 893
v0.32
\RequirePackage: Fix: Ignores blanks in package list. 249
General: 2016/06/09 1
glossaries: Prevent error with \glo@name not defined. 545
lwarpmk: Fix: **io.lines()** changed to **file:lines()** due to *luatex* changes. 322
v0.33
\HTMLAuthor: Fix: Provides empty default author if none given. . . . 375
\LWR@loadbefore: Fix: No \PackageError if already loaded. 207
\LWR@parseatcolumn: Fix: Column alignment with leftmost @. 458
\LWR@tabledatasinglecolumntag: Fix: Macros in tabular could cause extra data cell. 473
\LWR@vspace: Add: \vspace nullified. 625
\StartDefiningTabulars: Add: Avoids error: Misplaced alignment tab character &. . . 345
General: 2017/07/10 1
amsmath: Removed fleqn option. 657
fancyhdr: Fix: Optional args for \lhead, etc. 798
Add: Tabular at and bang columns now have their own HTML columns. 447
cleveref: Fix: Loaded \AtEndPreamble. 598
Fix: Incorrectly-inline math environments. 574
New handling of & to localize catcode changes. 447
v0.34
\@fnsymbol: Text symbols instead of math. 427
\InlineClass: Moved optional argument in front of mandatory. . 364
\LWR@htmldivclass: Moved optional argument in front of mandatory. . 362
\LWR@htmlelementclass: Moved optional argument in front of mandatory. 362
\LWR@htmlelementclassline: Moved optional argument in front of mandatory. 363
\LWR@htmlspanclass: Moved optional argument in front of mandatory. . 360
\LWR@nullfonts: Improved font control. 548
\LWR@restoreorigformatting: booktabs: Works inside lateximage. 546
Improved font control. 546
\LWR@subhtmlelementclass: Moved optional argument in front of mandatory. 362
\LWR@tabledatacolumntag: booktabs: Works inside lateximage. 497
\fboxBlock: Added. 607
\makebox: Fix: Handles paren arg. . . 605
General: 2017/08/08 1
babel-french: Adds fixed-width HTML spaces to punctuation. . . . 356
balance: Added. 682
booktabs: Works inside lateximage. 500, 696
boxedminipage2e: Added. 699
crop: Added. 755
enumerate: Added. 781
enumitem: Added, no longer required. 781
everyshi: Added. 791
fancybox: Added. 794
fancyvrb: Added, no longer required. 801
figcaps: Added. 810
filecontents: Required. Patched for morewrites. 244
floatpag: Added. 818
flushend: Added. 823
fullpage: Added. 837
hyperxmp: Added. 877
idxlayout: Added. 879
marginfit: Added. 940
mdframed: Improved mdtheorem patch. 965
moreverb: Added. 982
paralist: Added. 1033
pdflscape: Added. 1043
pdfsync: Added. 1046
prelim2e: Added. 1057
rotfloat: Added. 1074
savetrees: Added. 1075
shadow: Added. 1090
syntonly: Added. 1156
titleps: No longer required. 1186
titleref: Prevented. 1189

xcolor: Added \LWR@subfcolorminipage. . . . 1244
xmpincl: Added. 1253
Docs: Horizontal space limitations. . . 1
Docs: Misplaced alignment character. 196
File: lwarp_mathjax.txt: Version change. 318
File: README.txt: updated. 1
Fix: Added the eqnarray environments. 574
Improved font control. 610
Lists refactored to remove enumitem requirement. 438
Verbatim refactored to remove fancyvrb requirement. 433
tabular: booktabs: Works inside lateximage. 502
lateximage: Fix: lateximage with minipage, \parbox, \makebox, \fbox, \framebox, \raisebox, \scalebox, \reflectbox. 581
BlockClass: Moved optional argument in front of mandatory. 364
fminipage: Added. 607
LWR@nestspan: Fix: Minipages, BlocksClass, and lists inside a span. 359
v0.35
General: 2017/08/08 1
Fix: \textbf and related. 610
v0.36
\LWR@@footnotetext: Extra HTML source space after paragraphs. . . 378
Force HTML superscripts. 378
\LWR@HTMLsanitizeexpand: Fix for babel-french. 391
\LWR@closeparagraph: Extra HTML source space after paragraphs. . . 368
\LWR@currenttextcolor: Fix for \rule when xcolor not loaded. . . 619
\LWR@nullfonts: Fix: Filenames while using MathJax. 548
\LWR@restoreorigformatting: siunitx: Improved super/subscripts in a lateximage. 546
\LWR@section: Improved spacing. . . 403
\LWR@stoppars: Extra HTML source space after paragraphs. 371
\LWR@subHTMLsanitize: Fix for babel-french. 390
\fbox: Fix: Uses \fboxrule and \fboxsep. 606
\framebox: Fix: Handles width and horiz position. 606
\makebox: Fix: Handles width and horiz position. 605
General: 2017/08/17 1
babel-french: Adjustements for French variants, load order, footnotes, ellipses. 356
footnote: Extra HTML source space after paragraphs. 829
siunitx: Fix for babel-french. 591
siunitx: Improved symbol support. 1106
transparent: Added. 1211
upref: Added. 1225
xcolor: Added \fcolorboxBlock, \colorboxBlock. 1237
xcolor: Fix: Background none in print mode. 1237
xcolor: Refactored \LWR@colorstyle. 1240
xcolor: Uses \fboxrule and \fboxsep. 1237
xcolor: \fcolorbox etc. now work inside lateximage. 1237
Docs: Reorganized: Special cases and limitations. 123
Source: Improved formatting. 1
tabular: Fix for babel-french. . . . 502
lateximage: Footnotes appear in regular text instead of the lateximage minipage. 581
v0.37
\@include: Maintains independent aux files for HTML. 253
General: 2017/08/19 1
LaTeX accents: Added. 265
babel-french: Adjustment for load order. 356
color: Prevented. 752
siunitx: Improved symbol support. 1106
textcomp: Improved support. . . . 1171
lwarpmk: Removes additional HTML aux files. 322
File handles reorganized. 252
v0.38
\@seccntformat: Added for appendix. 402
\ForceHTMLPage: Added. 400
\ForceHTMLTOC: Added. 400
\LWR@section: \part* starts a new HTML page, for appendix. 403
Modified spacing, uses \numberline. 403
\numberline: Added trailing \quad. . 534
\part: Fix with article class. 409
General: 2017/08/27 1
appendix: Added. 667
arabicfront: Added. 669
chappg: Added. 717
color: Forces xcolor as well. 752

fix2col: Added. 812
fncychap: Added. 824
grffile: Added. 860
metalogo: Added. 971
nonumonpart: Added. 1016
nopageno: Added. 1016
pagenote: Option page disabled. . 1033
realscripts: Added. 1064
relsize: Added. 1068
romanbarpagenumber: Added. . . 1073
romanbar: Added. 1072
scalefnt: Added. 1075
siunitx: Removed from lwarp core. 1106
textcomp: Removed from lwarp core. 1171
tocbibind: Added. 1199
xltxtra: Added. 1252
lwarpmk: Added **print1** and **html1** actions. 322
Added \markboth, \sloppy, etc. . 354
Docs: Enhanced *Supported Features* table. 68
Docs: Index, tocbibind. 138
Docs: Starred sections. 135
v0.39
\@maketitle: titling version. 1196
Native LaTeX version. 428
Removed minipages. 428, 1196
Supports authblk with s of class oneauthor instead of tabular. 428, 1196
\AddSubtitlePublished: Added. . . 429
\LWR@domulticolumn: Add: Optional vpos and # rows. 488
\LWR@restoreorigformatting: Appended with \appto instead of calling various macros. 546
\LWR@tabledatacolumntag: Don't start a data cell if see \TabularMacro. 497
\ResumeTabular: Added. 496
\TabularMacro: Added. 496
\multicolumnrow: Added. . . . 495, 992
\printauthor: Removed minipages. 424
Supports authblk with s of class oneauthor instead of tabular. 424
\thanksmarkseries: Removed minipage footnotes. 1197
General: 2017/09/05 1
a4wide: Added. 641
a4: Added. 640
a5comb: Added. 641
addlines: Added. 650
anysize: Added. 667
authblk: Added. 676
bigdelim: Added. 692
bigstrut: Added. 694
ebook: Added. 767
fullwidth: Added. 838
midpage: Added. 976
multirow: Add: New optional vpos argument. 990
multirow: Add: Supports left/right border for bigdelim. 990
multirow: Fix: Long text argument. 990
supertabular: Added. 1154
textarea: Added. 1170
titling: Improved compatibility. . . 1193
titling: Removed extraneous center environments. 1194
typearea: Added. 1215
xtabular: Added. 1256
zwpagelayout: Added. 1260
Docs: Reorganized tabular discussion. 165
Titlepage \published and \subtitle removed. \AddSubtitlePublished restores. 429
titlepage: Clear pending footnotes. 423
Removed minipages. 423
titlingpage: Clear pending footnotes. 1194
v0.40
\@chapcntformat: Added for tocbibind, anonchap. 403
\LWR@HTMLhline: Added. 501
\LWR@nullfonts: Fix: Long arguments for expandable command. 548
\LWR@restoreorigformatting: Improved LaTeX logos inside a lateximage. 546
Improved symbols inside a lateximage. 546
Nullified \InlineClass, etc. inside a lateximage. 546
\LWR@tabledatacolumntag: Fix for bigdelim: \ldelim, \rdelim. . . . 497
\chapter: Added support for quotchap. 410
\multicolumnrow: Fix: Adapts to older multirow and xparse. 495
\simplechapterdelim: Added for tocbibind, anonchap. 402
\underline: Added. 618
General: 2017/09/25 1
adjmulticol: Added. 649
anonchap: Added. 666
bigdelim: Improved documentation. 692
cuted: Added. 758
dblfnote: Added. 759

fnpos: Added. 825
graphics: Add: Full \graphicspath support. 855
graphics: Moved out of the lwarp core. 847
graphics: Restores \includegraphics and \DeclareGraphicsExtensions in a lateximage. 847
graphicx: Moved out of the lwarp core. 860
grffile: Directly supported. 860
midfloat: Added. 975
multirow: Improved bigdelim borders. 990
pfnote: Added. 1049
quotchap: Added. 1062
sectsty: Added. 1086
stabular: Added. 1131
tabls: Added. 1157
textcomp: Additional symbols, improved XeLaTeX and LuaLaTeX support. 1171
tocbibind: Improved for \simplechapter. 1199
xfrac: No longer preloaded. 246
xltxtra: Fix for \showhyphens with XeLaTeX. 1252

v0.41

\LWR@addcmidruletrim: Add: \cmidrule trims. 478
\LWR@clearmidrules: Add: \cmidrule trims. 476
\LWR@closetabledatacell: Add: Mute > for \bottomrule. 452
Fix: At/bang column with \multirow. 453
Fix: Cancel < for \multicolumn. . 453
\LWR@domulticolumn: Add: \cmidrule trims. 488
Added vertical rules. 489
\LWR@nullifyNoAutoSpacing: babel-french: Fix: \NoAutoSpacing in a tabular. . . 502
\LWR@parsebarcolumn: Added vertical rules. 460
\LWR@printatbang: Add: \cmidrule trims. 472
Add: Mute at and bang columns for \bottomrule. 472
\LWR@printbartag: Added vertical rules. 472
\LWR@subaddcmidruletrim: Added. . 478
\LWR@subcmidrule: Add: \cmidrule trims. 476
\LWR@tabledatasinglecolumntag: Add: \cmidrule trims. 473
Add: Mute < for \bottomrule. . . . 473
\LWR@tabularfinishrow: Unfinished tabular rows automatically filled. . 455
\mcolrowcell: Added for \multicolumrow cells. 500
General: 2017/10/07 1
booktabs: Improved rules. 697
multirow: Add: \cmidrule trims. . 990
Added vertical rules. 990
Fix: < spec. 991
tabular: Fix: \NoAutoSpacing in a tabular with babel-french. 503

v0.42

\@ensuredmath: Improved \ensuremath. 564
\@textsubscript: Added. 618
\@textsuperscript: Added. 618
\LWR@HTMLhline: If FormatWP force explicit border. 501
\LWR@addformatwpalignment: If FormatWP add explicit style for cell alignment. 480
\LWR@addrulewidth: If FormatWP force explicit border. 478
\LWR@amsmathbody: Fix: Numbering and naming AMS math environments. 580
\LWR@amsmathbodynumbered: Fix: Numbering and naming AMS math environments. 580
\LWR@doequation: If FormatWP print LaTeX expression. 569
\LWR@domulticolumn: If FormatWP add cell alignment. 489
\LWR@doubledollar: If FormatWP print LaTeX expression. 562
Improved \ensuremath. 562
Improved line spacing with mathjax. 562
\LWR@floatbegin: If FormatWP add a text frame. 521
\LWR@floatend: If FormatWP add a text frame. 522
\LWR@remembertag: Fix: Numbering and naming AMS math environments. 579
\LWR@restoreorigformatting: Improved \ensuremath. 547
\LWR@subaddcmidruletrim: 0pt if no rule given. 478
\LWR@subsingledollar: If FormatWP print LaTeX expression. 560
\LWR@tabledatasinglecolumntag: If FormatWP add cell alignment. . . 474

\LaTeX: If FormatWP use explicit style. 629
\TeX: If FormatWP use explicit style. . 629
\hspace: If FormatWP add \quads. . . 624
\listoffigures: Added boolean WPMarkLOFT. 531
\listoftables: Added boolean WPMarkLOFT. 531
\marginpar: If FormatWP emulate a wrapfig. 382
\marginparBlock: If FormatWP emulate a wrapfig. 382
\rule: If FormatWP add \quads. 627
\tableofcontents: Added boolean WPMarkTOC. 531
\underline: If FormatWP, use explicit styles for \underline, etc. 618
General: 2017/10/30 1
\textbf and related: If FormatWP, use explicit styles for \textsc, etc. 610
algorithmicx: If FormatWP add \quads. 655
booktabs: If FormatWP force explicit border. 697
epigraph: If FormatWP add HTML styles. 781
fancybox: If FormatWP add HTML styles. 794
floatflt: Added width. 817
graphics: Fix: Class key. 851
graphics: Fix: Filename expansion. 855
graphics: If FormatWP, use explicit size. 852
keyfloat: If FormatWP add explicit HTML style. 898
moreverb: Simplified formatting of listings. 982
multirow: If FormatWP add cell alignment. 990
overpic: Added. 1032
realscripts: Fix for subscripts in a lateximage. 1064
sidenotes: If FormatWP add explicit HTML style. 1094
siunitx: Improved \ensuremath. . . 1106
soul: If FormatWP, add explicit styles. 1126
textcomp: Improved \interrobangdown. 1171
wrapfig: If FormatWP add explicit HTML style. 1235
Added boolean WPMarkLOFT. 261
Added boolean WPMarkMath. 262
Added boolean WPMarkMinipages. 261
Added boolean WPMarkTOC. 261
Added boolean WPTitleHeading. . 262
Docs: Added support page. 2
Docs: Improper \prevdepth. 196
Docs: Reorganized math limitations 152
File: lwarp_mathjax.txt: Updated siunitx script. 318
Fix: Numbering and naming AMS math environments. 579
If FormatWP, shift section headings. 262
tabbing: Added. 435
lateximage: Fix: Numbering and naming AMS math environments. 582
center: If FormatWP use explicit text-align. 587
minipage: Added boolean WPMarkMinipages. 603
If FormatWP add a text frame. 602
eqnarray: Fix: Numbering and naming AMS math environments. 575
If FormatWP print LaTeX expression. 575
LWR@BlockClassWP: Added to factor code. 365
LWR@figcaption: If FormatWP forces italic captions. 526
v0.43
\LWR@domulticolumn: Fix for vertical rules. 489
Fix: Multicolumn trim. 488, 489
\LWR@href: Made robust. 517
\LWR@maybeprintpendingfootnotes: Added FootnoteDepth. 381
\LWR@nolinkurl: Made robust. . . . 518
\LWR@nullfonts: Fix: Nullify dollar inside filesnames. 548
\LWR@parsetablecols: Ignore spaces in col spec. 467
\LWR@printmccoltype: Added vertical rules. 484
\LWR@section: Fix: Expansion in comparison. 404
Fix: Math in section name. . . 405, 407
Fix: Nullify fonts inside HTML comment. 405
\LWR@url: Made robust. 518
\TabularMacro: \newcommand instead of \relax to fix supertabular and xtab. 496
\nameref: Made robust. 515
General: 2017/11/08 1
LWR@currentautosecpage: Added. 383
breakurl: Added. 700
hyperref: Made robust. . . 872, 874, 876
hyperref: \Gauge added. 876
luatodonotes: Added. 933
todonotes: Added. 1208
Added FootnoteDepth. 377

Docs: HTML settings table. 111
Docs: Reorganized HTML customization. 111
v0.44
\@currentlabelname: Adjustment for koma-script. 507
\HTMLTitle: Added. 375
\LWR@addformatwpalignment: Fix for multicolumn alignment if FormatWP. 480
\LWR@backgroundcolor: xcolor: Added \LWR@backgroundcolor. 1241
\LWR@filestart: Add \HTMLTitle. . 414
Fix \HTMLAuthor. 413
\LWR@listitem: Added list and trivlist. 440
\LWR@patchlists: Added list and trivlist. 443
\LWR@strresult: Fix: \providecommand. 450
\LWR@textcurrentcolor: xcolor: Added \LWR@textcurrentcolor. 1240
\addcontentsline: Automatic \LWR@newfloatanchor. 528
\chapter: Add preamble for koma-script. 410
\marginparBlock: Added. 382
\nopagecolor: xcolor: Fix for \nopagecolor. 1242
\part: Add preamble for koma-script. 409
\title: Added \thetitle. 374
General: 2017/11/22 1
algorithmicx: Improved comment symbol. 655
atbegshi: Added. 673
cancel: Added. 703
changepage: Additional options. . 712
easy-todo: Added. 766
fancyref: Added. 800
fixmetodonotes: Added. 814
fixme: Added. 813
fontenc: Allowed after lwarp. . . . 828
hang: Added. 862
ifoddpage: Added. 880
ltxtable: Added. 930
luatodonotes: Improved. 933
lwarp-patch-komascript: Added. . 1261
overpic: Fix: Groups for lateximages. 1032
pdfsync: Fixes. 1046
preview: Added. 1057
scrextend: Added. 1076
scrhack: Added. 1080
scrlayer-notecolumn: Added. . . . 1082
scrlayer-scrpage: Added. 1082
scrlayer: Added. 1080
section: Added. 1085
soulpos: Added. 1128
soulutf8: Added. 1128
supertabular: Fix for caption. . . . 1154
tikz: Fix: Groups for lateximages. . 1185
tocbasic: Added. 1197
tocloft: Added \newlistentry. . . 1206
tocloft: Improved \newlistof. . . 1206
tocstyle: Added. 1207
todonotes: Improved. 1208
todo: Added. 1207
typearea: Added expert commands. 1215
watermark: Added. 1233
xcolor: Added \LWR@currenttextcolorstyle. 1240
xcolor: Added \LWR@findcurrenttextcolor. . 1240
xtab: Fix for caption. 1256
Adjustment for koma-script. 221
AMS environments: Fix: Groups for lateximages. 658
If pdfLaTeX, require T1 and UTF-8 encoding. 223
picture: overpic: Fix: Groups for lateximages. 598
list: Added list and trivlist. . . . 441
LWR@nestspan: Added list and trivlist. 359
v0.45
\@currentHref: Added. 516
\@donoparitem: Modified for HTML. . 438
\@item: Modified for HTML. 438
\@mklab: Modified for HTML. 438
\CSSFilename: Improved filenames with underscores. 373
\LWR@LwarpStart: Fix: Lateximages on incorrect pages with MATHJAX. . . 416
\LWR@label@createtag: Fix: Labels with underscores. 511
\LWR@newautoidanchor: Fix: No anchor if frozen autoid. 523
\LWR@nolinkurl: Fix: Underscore in URL. 518
\LWR@notmemoirloadafter: Added. . 206
\LWR@printpendingmpfootnotes: Added. 382
\LWR@startref: Fix: Labels with underscores. 514
\LWR@subhyperref: Improved URLs with underscores. 517
\LWR@subhyperrefclass: Improved URLs with underscores. 517
\LWR@tabledatacolumntag: Fix: Empty line between rows. 499

\LWR@url: Improved URLs with underscores. 518
\chapter: Add optional heading title for memoir. 410
\newpage: Added. 621
\normalmarginpar: Added. 383
\reversemarginpar: Added. 383
\section: Add optional heading title for memoir. 410
\tableofcontents: Fix: Empty sidetoc. 530
Fix: Patch \AtBeginDocument. . . . 530
General: 2018/01/14 1
array: Added. 669
babel-french: Robust commands. . 356
backref: Added. 682
breakurl: Fix: Underscore in URL. . 700
changebar: Added. 711
cite: Added. 744
continue: Added. 754
endfloat: Added. 772
fancyvrb: Improvements. . . . 801, 802
flafter: Added. 814
fltrace: Added. 823
footnpag: Added. 831
fwlw: Added. 841
graphics: Improved URLs with underscores. 855
hanging: Added. 863
hyperref: Fix: Underscore in URL. 872, 873
lwarp-patch-memoir: Added. . . . 1264
memhfixc: Added. 970
memoir: Added. 633
natbib: Added. 998
pagesel: Added. 1033
prettyref: Added. 1057
subfigure: Added. 1152
subfig: Fix for subcaption end tag. 1150
subfig: Fix: Math in subcaptions. . 1149
textfit: Added. 1174
titleref: Added. 1189
turnthepage: Added. 1213
Allows memoir's preloaded packages. 211
Docs: Fix for double hyphens. . . . 83
Docs: Improved install instructions. 84
Docs: Improved MiKTEX install instructions. 80
Docs: Moved table so doesn't interfere with install docs. 79
File: lwarp_mathjax.txt: Allow MathJax inside tabbing. 318
File: lwarp_mathjax.txt: Allow MathJax inside verse. 318
Fix: Empty sidetoc. 530
Improved: Robust \,, \ , and \textellipsis commands. . . . 620
Separate LWR@thisautoidWP for word processor s. 523
thebibliography: Patched to emphasize titles. 545
minipage: Fix: Improper \prevdepth. 603
v0.46
\LWR@closeparagraph: Fix: Tabular empty lines. 369
\LWR@closeprevious: Fix: Stack unnesting. 354
\LWR@forcenewpage: Fix: Improper \prevdepth. 354
\LWR@lookforpackagename: Fix: Spaces in \usepackage. 249
\LWR@popclose: Fix: Stack unnesting. 343
\LWR@providelength: Added. 225
\LWR@pushclose: Fix: Stack unnesting. 342
\LWRPrintStack: Name changed from \PrintStack. 353
General: 2018/01/23 1
LWR@tabularpardepth added. . . . 450
amsthm: Adapted to trivlist changes. 663
mdframed: Fixes for SVG math or lateximage in title. 962
mdframed: Fixes for footnotes. . . 963
ntheorem: Adapted to trivlist changes. 1018
theorem: Adapt to trivlist changes. 1177, 1178
tabular: Fix: Tabular empty lines. . . 505
list: Fix: Stack unnesting. 441
v0.47
\LWR@HTML@caption@begin: Fix: Argument passed to \LWR@origcaption@begin. . . . 526
\LWR@LwarpStart: Fix for SVG math in \nameref. 417
\LWR@WPcell: Fix: Line wrap at HTML hyphen. 480
\LWR@createautosec: Fix: Line wrap at HTML hyphen. 401
\LWR@domulticolumn: Fix: Line wrap at HTML hyphen. 489
\LWR@floatbegin: Fix: Line wrap at HTML hyphen. 521
\LWR@htmlclosecomment: Add \mbox to prevent line breaks. 360
\LWR@label@createtag: Fix: Line wrap at HTML hyphen. 511
\LWR@newautoidanchor: Fix: Line wrap at HTML hyphen. 523

\LWR@printopenlist: Fix: Line wrap at HTML hyphen. 438
\LWR@startref: Fix: Line wrap at HTML hyphen. 513
\LWR@subsingledollar: Added SVG math image baseline adjust and em sizing. 560
\LWR@subsingledollarsvg: Fix: Line wrap at HTML hyphen. 558
\captionlistentry: Fix: Line wrap at HTML hyphen. 527
\hypertoc: Fix: Line wrap at HTML hyphen. 534
\hypertocfloat: Fix: Line wrap at HTML hyphen. 535
General: 2018/01/30 1
adjmulticol: Fix: Line wrap at HTML hyphen. 650
blowup: Added. 695
caption: Added. 705
changepage: Fix for pagecheck macros. 712
endheads: Added. 772
epigraph: Fix: Line wrap at HTML hyphen. 782
hanging: Fix: Line wrap at HTML hyphen. 863
hang: Fix: Line wrap at HTML hyphen. 862
keyfloat: Fix for SVG math in captions. 894
midpage: Fix: Line wrap at HTML hyphen. 976
multirow: Fix: Line wrap at HTML hyphen. 990
multitoc: Added. 993
ntheorem: Fix: Line wrap at HTML hyphen. 1023
realscripts: Fix: Line wrap at HTML hyphen. 1064
scrextend: Fix: Line wrap at HTML hyphen. 1076
sectionbreak: Added. 1086
sidenotes: Fix for SVG math in captions. 1094
subfig: Fix for SVG math in captions. 1148
subfig: Fix: Support \nameref. . . . 1148
xurl: Added. 1258
lwarpmk: *pdfcrop*: Removed hires option for improved crop accuracy. 322
lateximage: Added CSS style option. 581
Fix: Line wrap at HTML hyphen. . . 586
center: Fix: Line wrap at HTML hyphen. 587
minipage: Fix: Line wrap at HTML hyphen. 602
flushleft: Fix: Line wrap at HTML hyphen. 587
flushright: Fix: Line wrap at HTML hyphen. 587
enumerate: Fix: Line wrap at HTML hyphen. 442
itemize: Fix: Line wrap at HTML hyphen. 441
LWR@BlockClassWP: Fix: Line wrap at HTML hyphen. 365
v0.48
\@@@setcpageref: Fix for new v0.21 of cleveref. 748
\@@@setcref: Fix for new v0.21 of cleveref. 747
\@@@setcrefrange: Fix for new v0.21 of cleveref. 748
\@biblabel: Improved bibliography label. 545
\@item: Honors \makelabel. 438
\@maketitle: Fix: Errors with IEEEtran class. 428
\LWR@LwarpStart: Adjusted space around captions. 416
\LWR@ProvidesPackageDropB: Fix: Options with braces. 252
\LWR@addtabularhrulecolor: colortbl: Added. 481
\LWR@addtabularrulecolors: colortbl: Added. 482
\LWR@closetabledatacell: colortbl: Added. 453, 454
\LWR@lookforpackagename: Fix: Parsing similar package names. . . 248
\LWR@newautopagelabel: Fix: TOC, LOF, LOT links. 384
\LWR@newhtmlfile: Fix: TOC, LOF, LOT links. 398
\LWR@nullfonts: Fix: \newline in title. 548
\LWR@parsedrequirepackagenames: Fix: Parsing similar package names. 247
\LWR@parsetablecols: Fix: Ignore optional tabular column arguments. 468
\LWR@restoreorigformatting: Fix: Spacing in SVG math, lateximage, Ti*k*z. 546
\LWR@section: Fix: TOC, LOF, LOT links. 407
\LWR@tabledatasinglecolumntag: colortbl: Added. 474
\LWR@textcurrentfont: Added. Improves font control. 614
\centerline: Added. 588

\l@part: Adapts to classes without \part. 536
\leftline: Added. 588
\mbox: Nullified for HTML. 604
\rightline: Added. 588
\thempfootnote: Removed \itshape. 381
General: 2018/02/14 1
acronym: Added. 649
acro: Added. 646
chapterbib: Added. 718
colortbl: Added. 469, 480, 752
fancyref: Now directly supported. 800
graphics: Fix: Virtual page size limited to a group. 855, 856
hypcap: Added. 867
hypernat: Added. 867
hyperref: \texorpdfstring now uses the TEX string. 876
luatodonotes: Improved \todototoc. 933
siunitx: Changes fraction to symbol. 1109
siunitx: Improved SVG math. 1106, 1108
siunitx: Improved color output. . . 1107
stfloats: Added. 1146
todonotes: Improved \todototoc. 1209
vmargin: Added. 1229
xfrac: Fix: Added groups around super/subscripts to localize LWR@nestspan changes. 1250
Docs: Converting an existing document. 100
Improved font control. 614
tabular: colortbl: Added. 504
lateximage: Print mode boxed to natural width. 587
abstract: Allow optional name. . . . 430
v0.49
\LWR@addtabularcellcolor: xcolor: Added tabular row colors. 483
\LWR@domulticolumn: xcolor: Added tabular row colors. 490
\LWR@href: Fix: Adapt to classes. . . . 517
\LWR@printlength: Fix: Group printlen changes. 246
\LWR@url: Fix: Adapt to classes. 518
\affiliation: Fix: Adapts to classes which already provide. 423
\noalign: Fix: \noalign inside tabular. 501
General: 2018/02/19 1
amsmath: Fix: Patches for \eqref. 657
eso-pic: Fix for \AddToShipoutPicture. 787
figsize: Added. 811
fnlineno: Added. 825
hypdestopt: Added. 867
hyphenat: Added. 878
lineno: Added. 914
luacolor: Added. 930
pagegrid: Added. 1033
pdfrender: Added. 1046
resizegather: Added. 1071
vertbars: Added. 1228
vwcol: Added. 1230
xcolor: Added tabular row colors. 469, 1246
Fix: Adapt to classes. 620
v0.50
\@ensuredmath: Fix: Use lateximage even if MATHJAX. 564
Improved SVG math alt tags. 564
\LWR@@footnotetext: Robustify macros. 379
\LWR@atbeginverbatim: Improved column alignment. 434
\LWR@doequation: Improved SVG math display. 570
\LWR@doubledollar: Improved SVG math alt tags. 562
Improved SVG math display. 562
\LWR@htmlrefsectionfilename: Fix: SVG math in a section name. . . . 350
\LWR@newhtmlfile: Fix: SVG math in a section name. 398
\LWR@nullfonts: Fix: \underline in sectioning file name. 550
\LWR@overline: Added. 618
\LWR@subsingledollar: Fix: Use lateximage even if MATHJAX. . . 560
Improved SVG math alt tags. 560
\LWR@subsingledollarsvg: MD5 hash avoids duplicate SVG math. 558
\LWR@vspace: Robustify macros. . . . 625
\newline: Robustify macros. 621
\textsubscript: Robustify macros. . 618
\textsuperscript: Robustify macros. 618
General: 2018/03/03 1
lwarp.css: Improved SVG display math centering. 274
lwarp_one_limage.txt: Added. . 317
amsmath: Fix: Upright tags for SVGmath. 657
axodraw2: Added. 681
bytefield: Added. 703
dblfloatfix: Added. 759
diagbox: Added. 760
epstopdf: Added. 783
listings: Force flexible columns. . . 917
morefloats: Added. 982
nonfloat: Added. 1016

ntheorem: Fix: Not standard nor amsthm selected. 1025
pbox: Added. 1040
phfqit: Added. 1049
schemata: Added. 1076
siunitx: Fix: Loads xcolor. 1106
siunitx: Improved SVG math alt tags. 1108
siunitx: Improved units. 591, 1106, 1110
xy: Added. 1259
lwarpmk: Error if lateximages.txt does not exist. 322
lwarpmk: Error if lwarpmk.conf points to lwarp. 322
lwarpmk: Improved error messages. 322
lwarpmk: MD5 hash avoids duplicate SVG math. 322
lwarpmk: Multiprocess support making lateximages. 322
AMS environments: Improved SVG math display. 658
Fix: Load fontspec if necessary. . . 240
Robustify macros. 614
lateximage: Fix: SVG math in a section name. 585
MD5 hash avoids duplicate SVG math. 583, 586
eqnarray: Improved SVG math display. 575, 576

v0.51

\@ensuredmath: Hashes \ensuremath. 564
\@item: Restored list label space. . . . 440
\LWR@HTMLsanitizeexpand: Fix: Escapes double quotes. 391
\LWR@LwarpStart: MathJax: Nullifies \ensuremath. 417
\LWR@addbaselinemarker: Improved SVG math baseline. 554
\LWR@atbeginverbatim: Adds vertical offset. 433
\LWR@doequation: Fix: \addcontentsline inside SVG math. Provides an autoid anchor. . 570
\LWR@doubledollar: Fix: \addcontentsline inside SVG math. Provides an autoid anchor. . 562
\LWR@findcurrenttextcolor: Added \LWR@findcurrenttextcolor when no xcolor. 619
\LWR@newautoidanchor: Fix: No autoid is inside a lateximage. 523
\LWR@singledollarmeasure: Fix: lateximage inside $\mathcal{AMS}$ \text. . 556
Fix: Honors text font around SVG math. 555
Improved SVG math baseline. 556
Typeset SVG math only once during measurement. 556
\LWR@subHTMLsanitize: Fix: Escapes double quotes. 390
\LWR@subsingledollar: Fix: \ensuredmath inside SVG image. . 561
\LWR@subsingledollarsvg: Fix: SVG math with enclosed lateximage. . 557
SVG math baseline improved with invisible rule at corner. 559
\LWR@textcurrentcolor: xcolor: \LWR@textcurrentcolor if xcolor not loaded. 619
\addcontentsline: Add missing support for float mechanism if necessary. 528
No anchor ID if inside SVG image. . 528
\displaymathnormal: Processing for complicated display math. 572
\displaymathother: Processing for complicated display math. 573
General: 2018/03/24 1
MathJax: Nullifies \ensuremath. 393
lwarp_one_limage.txt: *pdftocairo* -noshrink added. 317
afterpackage: No longer required. 244
chemfig: Added. 718
chemformula: Added. 720
chemgreek: Added. 725
chemmacros: Added. 726
chemnum: Added. 743
epstopdf-base: Added. 784
fancybox: Fix: Optional tag for \item in a span. 797
grid: Added. 860
listings: Forces cleared options. . . 918
ltxgrid: Added. 929
mhchem: Added. 973
tikz: Fix for \tikz macro. 1185
tikz: Fix for tikz with optional argument. 1185
titling: Fix for \thanks mark. . . . 1195
lwarpmk: *pdfcrop*: Restored hires option. 322
lwarpmk: *pdftocairo* -noshrink added. 322
AMS environments: Fix: \addcontentsline inside SVG math. Provides an autoid anchor. . 658
Docs: tikz limitations. 161
Docs: Multiple authors and affiliations. 134
Docs: Things to avoid. 123

Docs: Updated Converting an existing document. 100
Fix: Remember original \# in case is redefined. 264
Named HTML entity used for text dollar. 553
lateximage: Added additional hashing option. 581
Fix: lateximage inside $\mathcal{AMS}$ \text. 582
Processing for complicated display math. 585
alignat: amsmath: Fix: Added. . . . 660
eqnarray: Fix: \addcontentsline inside SVG math. Provides an autoid anchor. 575, 576
LWR@displaymathother: Processing for complicated display math. 565
LWR@equationother: Processing for complicated display math. 565
v0.52
\@ensuredmath: Improved hashing expansion. 564
\@mpfootnotetext: Fix: Paragraph handling. 380
\CustomizeMathJax: Added. 393
\LWR@@footnotetext: Fix: Paragraph handling. 379
\LWR@addbaselinemarker: Warnings if lwarp_baseline_marker.png is not present or if graphicx/s not loaded. 554
\LWR@customizedMathJax: Added. . 392
\LWR@doequation: Fix: equation* now based on equation instead of displaymath. 570
Fix: equation* with split. 569
\LWR@filenamenoblanks: Fix: \FileDepth with non-utf8 encoding. 389
\LWR@href: Fix: #, %, &, ~, _ in URL. . . 517
\LWR@nolinkurl: Fix: #, %, &, ~, _ in URL. 518
\LWR@nullfonts: Fix: \texorpdfstring in section names. 551
\LWR@section: Fix: Footnote numbering: Limited HTML comment if starred. 405
Fix: Footnote numbering: Use short TOC entry for HTMLDebug comments. 405
\LWR@singledollarmeasure: Added user-adjustable SVG math font scaling. 556
\LWR@url: Fix: #, %, &, ~, _ in URL. . . 518
\LateximageFontScale: Added user-adjustable SVG math font scaling. 578
\theHTMLTitleSeparator: Fix: \FileDepth with non-utf8 encoding. 411
General: 2018/04/01 1
breakurl: Fix: #, %, &, ~, _ in URL. . . 700
endfloat: Updated for v2.6. 772
fancyvrb: Initial support for \VerbatimFootnotes. 794, 801
graphics: Added defaults. 850
graphics: Updated for v1.1a. . . . 851
graphics: Updated for v1.1b. . . . 851
hyperref: Fix: #, %, &, ~, _ in URL. 872–874
nicefrac: Added. 1011
url: Added. 1225
lwarpmk: Fix: Memory overflow when spawning tasks. 322
lwarpmk: Fix: Skip image generation if from page 0. 322
Changed FootnoteDepth default to \subsbusection. 377
Docs: Improved install instructions. 81
Fix: MathJax script line wraps. Reduced right margin. 241
If pdfLaTeX, allow other input encoding. 223
Restore \kill in a lateximage. . . 927
tabbing: Fix to allow inside lateximage. 435
lateximage: Fix for hash expansion. 583
v0.53
General: 2018/04/01 1
lwarpmk: Added **lwarpmk cleanlimages**. 322
lwarpmk: Added warning for corrupted images. 322
Docs: **lwarpmk cleanlimages**. . . . 97
Docs: **lwarpmk pdftohtml**. 97
v0.54
\@xdlbfloat: Honor \centering, etc. in floats. 522
\LWR@afterendverbatim: Added vspace argument. 434
\LWR@atbeginverbatim: Improved column alignment. 434
\LWR@endfloatalignment: Honor \centering, etc. in floats. 524
\LWR@floatalignment: Honor \centering, etc. in floats. 524
\LWR@floatend: Honor \centering, etc. in floats. 522
\LateximageFontSizeName: Defaults to normalsize. 578

\centering: Added debug comment. 588
\raggedleft: Added debug comment. 588
\raggedright: Added debug comment. 588
General: 2018/04/22 1
*.lwarpmkconf: Option IndexLanguage changed to xindyLanguage. 274
*.lwarpmkconf: Option pdftotextEnc added. 274
*.lwarpmkconf: Option xdyFilename changed to xindyStyle. 274
*.lwarpmkconf: Option xindyCodepage added. 274
lwarp.css: Fix: Text-decoration-skip: auto. 274
lwarpmk.conf: Option IndexLanguage changed to xindyLanguage. 274
lwarpmk.conf: Option pdftotextEnc added. 274
lwarpmk.conf: Option xdyFilename changed to xindyStyle. 274
lwarpmk.conf: Option xindyCodepage added. 274
bibunits: Added. 692
chngpage: Added. 744
forest: Added. 831
glossaries: Fix when not using babel or polyglossia. 846
gridset: Added. 861
hyperref: Fix: \hyperref and \hyperlink with special chars in text. 874
hyperref: Fix: \ref in \hyperref and \hyperlink caused nested link. 874
lwarp-patch-memoir: Update for v3.7g. 1270
magaz: Added. 937
ragged2e: Fix: \centering, etc. . . 1063
textcomp: Fix for \textperthousand. 1171
tikz: Fixes for \pgfpicture, minipages, fit, align, font. 1185
lwarpmk: Added pdftotextenc. . . 322
lwarpmk: Added xindycodepage. . 322
lwarpmk: Changed language to xindylanguage. 322
lwarpmk: Changed xdyfile to xindystyle. 322
lwarpmk: Improved error if configuration file does not exist. . 322
lwarpmk: Increased prominence for error for an unknown command. . 322
lwarpmk: Verifies HTML version exists before lwarpmk limages. . 322
lwarpmk: Verifies image references before lwarpmk limages. 322
Add: pdftotextEnc. 234
Add: xindyCodepage. 234
Added early check for disallowed packages. 209
Docs: BibTeX. 136
Docs: Macros in sectioning names. 123
Never load aecompl. 209
Option IndexLanguage changed to xindyLanguage. 234
Option xdyFilename changed to xindyStyle. 233
verse: Fix: Line spacing. 432
v0.55
\@xdlbfloat: Fix: Float optional args. 522
\LWR@LwarpStart: Fix: Overfull boxes in lateximages. 415
\LWR@nullfonts: Removed extraneous space which appeared in file links. 550
\LWR@phantomsection: Fix: \ForceHTMLTOC with \phantomsection. 628
General: 2018/04/26 1
clrdblpg: Added. 750
Fix: \centering, etc. for koma-script. 521
Fix: QED symbols in lateximage. 665, 1029
v0.56
\LWR@addcdashline: arydshln: Added. 479
\LWR@addmulticolvertrulecolor: Adds support for dashed vertical rules. 487
Adds support for double vertical rules. 487
\LWR@addtabularhrulecolor: Adds support for arydshln dashed rules. 481
Adds support for double \hlines and \midrules. 481
\LWR@addtabularrulecolors: Adds support for dashed vertical rules. . 482
Adds support for double vertical rules. 482
\LWR@closeparagraph: Added support for parnotes. 369
\LWR@domulticolumn: Adds support for dashed vertical rules. 489
Adds support for double vertical rules. 489
\LWR@floatbegin: Adds a <class> per float package style. 521

\LWR@multicolpartext: Fix: \multicolumn parameters. 485
\LWR@openparagraph: Added support for parnotes. 368
\LWR@parsebarcolumn: Adds support for double vertical rules. 460
\LWR@parsecoloncolumn: arydshln: Added. 461
\LWR@parsesemicoloncolumn: arydshln: Added. 461
\LWR@parsetablecols: Added array W column. 469
\LWR@printmccoldata: Added array W column. 486
Fix: \multicolumn parameters. . . 486
\LWR@printmccoltype: Added array W column. 484
Adds support for dashed vertical rules. 484
Adds support for double vertical rules. 484
\LWR@tabledatacolumntag: Fix: \morecmidrules 498
\LWR@textcurrentfont: Added span.textbf, etc. 614
General: 2018/05/12 1
*.lwarpmkconf: Records --shell-escape. 274
lwarp.css: Added div.textbf, etc. 274
lwarp.css: Added span.textbf, etc. 274
lwarpmk.conf: Records --shell-escape. 274
arydshln: Added. 447, 670
lua-check-hyphen: Added. 930
paralist: Fixes for compactenum, compactitem, compactdesc. . . . 1033
parnotes: Added. 1038
quoting: Added. 1063
tocenter: Added. 1201
underscore: Added. 1218
lwarpmk: Added lwarpmk pdftosvg. 322
lwarpmk: Supports --shell-escape. 322
Added \thinspace. 620
Docs: **lwarpmk pdftosvg**. 97
LWR@blocktextcurrentfont: Added div.textbf, etc. 614
v0.57
\BlockClassSingle: Improved print/HTML output selection. . . . 364
\InlineClass: Improved print/HTML output selection. 364
\LWR@href: Fix: Text catcodes. . . . 517
\LWR@listof: Fix: Provide \l@name if not defined. 532
\LWR@singledollarmeasure: Fix: Dynamic inline math expressions. 556
\LWR@subhyperref: Fix: Text catcodes. 517
\LWR@subhyperreftext: Fix: Text catcodes. 517
\LWR@subsingledollar: Fix: Dynamic inline math expressions. 561
\LWR@subsingledollarsvg: Fix: Dynamic inline math expressions. 558
\LWR@vspace: Improved print/HTML output selection. 625
\MathImageAltText: Added. 552
\PackageDiagramAltText: Added. . 552
\StartDefiningMath: Added. 345
\boxframe: xcolor: Fix: Colored \boxframe. 1245
\colorbox: xcolor: New system for switching print and HTML outputs. 1242
\colorboxBlock: xcolor: New system for switching print and HTML outputs. 1242
\fboxBlock: Improved print/HTML output selection. 607
\fcolorbox: xcolor: New system for switching print and HTML outputs. 1243
\framebox: Improved print/HTML output selection. 606
\inlinemathother: Added. 346
\makebox: Improved print/HTML output selection. 605
\mbox: Improved print/HTML output selection. 604
\multicolumnrow: multirow: Improved print/HTML output selection. . . . 992
Improved print/HTML output selection. 495
\newfloat: rotfloat: Added float styles. 1074
rotfloat: Fix for listof sideways floats. 1074
\parbox: Improved print/HTML output selection. 604
\raisebox: Improved print/HTML output selection. 609
\reflectbox: Improved print/HTML output selection. 859
\resizebox: Improved print/HTML output selection. 859
\rotatebox: Improved print/HTML output selection. 857
\rule: Fix: Colored rules. 626
\scalebox: Improved print/HTML output selection. 858

\textcolor: xcolor: New system for switching print and HTML outputs. 1241
General: 2018/06/06 1
MathJax: Supports \footnote, \footnotemark. 393
lwarp.css: Added ruled, boxed, boxruled floats. 274
lwarp.css: Increased float vertical margins. 274
algorithm2e: Added. 651
bigdelim: Improved print/HTML output selection. 692
breakurl: Fix: Text catcodes. . . . 700
colortbl: New system for switching print and HTML outputs. . . . 752, 753
ellipsis: Added \midwordellipsis. 770
errata: Added. 786
float: Added float styles. 815
float: Fix: Do not pre-define \l@name. 816
ltablex: Added. 928
marginnote: Fix: Long optional argument. 941
multirow: Improved print/HTML output selection. 990
register: Added. 1067
subcaption: Fix: \subref. 873
trimclip: Added. 1211
vowel: Added. 1229
xellipsis: Added. 1247
xfrac: Improved print/HTML \scalebox control. 1250
xltabular: Added. 1251
xpiano: Added. 1253
lwarpmk: Improved code factoring. 322
lwarpmk: Improved error handling. 322
Docs: Recompiling *lwarpmk* or CSS files. 192
Docs: Recreating the index for lwarp source. 190
New system for switching print and HTML outputs. 258
minipage: Improved print/HTML output selection. 601
BlockClass: Improved print/HTML output selection. 364
fminipage: Improved print/HTML output selection. 607
LWR@BlockClassWP: Improved print/HTML output selection. . . . 365
v0.58
\LWR@HTML@caption@begin: Improved print/HTML output selection. . . . 526
\LWR@HTML@caption@end: Improved print/HTML output selection. . . . 526
\LWR@HTML@ref: Improved print/HTML output selection. 514
\LWR@doindexentrysubsub: Adds support for \see, \seealso, \emph, \textbf, etc. 542
\LWR@hyperindexrefnullified: Adds support for \see, \seealso, \emph, \textbf, etc. 542
\LWR@hyperindexrefsubtwo: Adds support for \see, \seealso, \emph, \textbf, etc. 544
\LWR@indexitem: Accepts optional arg for repeatindex. 538
\dotfill: Improved print/HTML output selection. 621
\hfill: Improved print/HTML output selection. 621
\hrulefill: Improved print/HTML output selection. 621
\printindex: Fix: Extra \newpage to flush pending \index writes. . . . 938
General: 2018/07/07 1
*.lwarpmkconf: Added option makeindexstyle. 274
*.lwarpmkconf: Added options makeindex and xindy. 274
*.lwarpmkconf: Generated \AtBeginDocument. 274
lwarp.xdy: Requires makeindex.xdy. 316
lwarp.xdy: Supports bold, italic. . 316
lwarp_html.ist: Added. 315
lwarpmk.conf: Added option makeindexstyle. 274
lwarpmk.conf: Added options makeindex and xindy. 274
lwarpmk.conf: Generated \AtBeginDocument. 274
array: Improved print/HTML output selection. 669
attachfile2: Added. 674
attachfile: Added. 673
cases: Added. 709
imakeidx: Added. 880
index: Added. 885
intopdf: Added. 886
lwarp-patch-komascript: Modified indexing. 1262
lwarp-patch-memoir: Fix for \specialindex. 1287
lwarp-patch-memoir: Fix for multiple indexes. 1287, 1288
makeidx: Added. Moved from lwarp core. 938

memoir: Fix for \firsthlline, \lasthline. 496
memoir: Fix for booktabs. 500
pdfpages: Added. 1044
pdfx: Added. 1047
repeatindex: Added. 1070
splitidx: Added. 1130
textcomp: Improved print/HTML output selection. 1171
lwarpmk: Added makeindex and xindy options. 322
lwarpmk: Added -p option for project name. 322
lwarpmk: Added optional list of names for **lwarpmk printindex** and /cmdslwarpmk htmlindex. . . 322
lwarpmk: Glossary generation now uses *makeglossaries*. 322
lwarpmk: **lwarpmk clean** removes all *.ind and *.idx files. 322
Added makeindex option. 235
Added xindy option. 235
Added option makeindexStyle. . 233
Docs: Index, *makeindex*, imakeidx. 138
Docs: Misplaced \omit. 196
Fix: memoir and ccaption. 211
Improved print/HTML output selection. 620
Replaced each \csuse with \@nameuse to force error if undefined. 1
tabbing: Improved print/HTML output selection. 435
v0.59
\LWR@addbaselinemarker: Uses .eps if DVI *latex*. 554
\LWR@latexmkcmd: Fix: --shell-escape with *latexmk*. . . 269
\LWR@writeconf: Compilation commands now preassigned by lwarp instead of being computed by *lwarpmk*. 273
\[: Fix with \displaymathnormal. . 564
General: 2018/09/07 1
Slunits: Added. 1096
accsupp: Added. 645
amsmath: Moved from the lwarp core. 657
asymptote: Added. 672
axessibility: Added. 680
breqn: Added. 700
bxpapersize: Added. 703
canoniclayout: Added. 704
chemformula: Fix for \NMR. 740
draftcopy: Added. 764
epstopdf-base: Improved. 784
epstopdf: Improved. 783
fnbreak: Added. 824
graphics: Fix: Expand filename. . . 856
graphics: Now works with .pdf and .eps filename extensions. 855
nccfancyhdr: Added. 999
pdftricks: Added. 1047
pst-eps: Added. 1059
pstricks: Added. 1060
units: Added support for MathJax. 1223
xunicode: Added. 1257
lwarpmk: Added **lwarpmk epstopdf**. 322
lwarpmk: Consolidated compiling options into printlatexcmd and HTMLlatexcmd. 322
lwarpmk: Double insead of single-dashed --shell-escape option. 322
lwarpmk: Error if lwarpmk.conf format changed. 322
lwarpmk: Warning if operating system changed. 322
Added option dvipdfmx. 236
Added option dvipdfm. 236
Added option dvips. 236
Docs: **lwarpmk epstopdf**. 97
File: lwarp_mathjax.txt: Fix: Removed chapter number from tagged non-numeric MathJax equations. 318
File: lwarp_mathjax.txt: Updated to MathJax v2.7.4. 318
picture: Added an alt tag. 598
v0.60
\LWR@clearmidrules: tabular: Fix for midrules. 476
\LWR@parsenormalcolumn: tabular: Improved memory management: Not using xstring. 462
\LWR@tabledatasinglecolumntag: tabular: Improved memory management: Not using xstring. . 474
\LWR@tabularendofline: Fix: Slowdown for long tables. 457
General: 2018/09/19 1
tabular: Improved memory management: Global boolean. 448, 449
tabular: Improved memory management: Not using xstring. 450, 990
2up: Added. 640
booklet: Added. 696
bophook: Added. 698

diagbox: Fix for par tags. 761
draftfigure: Added. 764
fancytabs: Added. 800
fullminipage: Added. 837
grid-system: Added. 861
layaureo: Added. 903
leading: Added. 906
listings: Fix for HTML entities. . . . 918
listings: Fix if inside a list. . . . 920, 923
thumbs: Added. 1184
thumb: Added. 1184
widows-and-orphans: Added. . . . 1233
v0.61
\DeclareGraphicsExtensions: Fix: EPS for DVI LaTeX. 848
\LWR@HTMLLatexCmd: Added HTMLLatexCmd option. 273
Added PrintLatexCmd option. . . . 273
\LWR@addcompilecmd: Removed spaces. 269
\LWR@closetabledatacell: Fix: Par tags in tabular. 452
\LWR@hyperindexrefnullified: Made robust, ... 542
\LWR@listof: Fix: newfloat lists. . . . 532
\LWRopseq: Added spaces. 231
\RequirePackage: Support up to 20 packages. 249
\inlinemathnormal: Changed name from \StopDynamicMath to \inlinemathnormal. 346
\inlinemathother: Changed name from \StartDynamicMath to \inlinemathother. 346
\lwarpsetup: Added. 232
General: 2018/10/13 1
lwarp.css: Footnotes text align left. 274
lwarp.css: Minipage table and footnotes: tighter margin. 274
chkfloat: Added. 744
cmdtrack: Added. 751
copyrightbox: Added. 754
dprogress: Added. 764
epsfig: Added. 783
graphics: Fix: EPS for DVI LaTeX. . . 852
graphics: Set keys before using filename, for epsfig. 856
lua-visual-debug: Added. 930
pdfprivacy: Added. 1046
psfragx: Added. 1058
psfrag: Added. 1058
pstool: Added. 1059
refcheck: Added. 1067
srcltx: Added. 1131
srctex: Added. 1131
supertabular: Fix for caption w/o opt arg. 1154
thinsp: Added. 1179
threadcol: Added. 1182
uspace: Added. 1226
vpe: Added. 1230
xbmks: Added. 1236
xtab: Fix for caption w/o opt arg. . 1256
Added HTMLLatexCmd option. . . . 235
Added PrintLatexCmd option. . . . 235
Docs: \tracinglwarp 255
Docs: HTML entities. 124
Docs: Compiling using custom shell commands. 178
Docs: Fonts. 103
Docs: HTMLDebugComments 111, 254
Docs: Multiple indexes. 201
Don't write configuration files if processing pstool image. 267
Spaces redefined \AtBeginDocument. 620
v0.62
\@partcntformat: Added for ctex. . 403
\@partnameformat: Added for ctex. . 403
\InlineClass: Added optional word-processing style. Replaces \LWR@HTMLtextstyle. 364
\LWR@PreloadedPackage: Added. . . 589
\LWR@ProvidesPackagePass: Fix: Unknown option error. 251
\LWR@endofline: Extra space if optional arg. 622
\LWR@filestart: Refactored. 414
\LWR@isolate: Added. 226
\LWR@textcurrentfont: Added print version. 619
Tracks depth to avoid nesting repeated font changes. 614
\colorboxBlock: xcolor: Fix: Horiz white space. 1242, 1243
\fcolorbox: Fix: No longer requires xifthen. 595
\fcolorboxBlock: xcolor: Fix: Horiz white space. 1243, 1244
\l@chapter: Don't define if no \chapter. Fix for algorithm2e. . . 536
\slshape: Added. 617
\textup: Fixed WP span class. . . . 612
\theHTMLSection: Added. 412
\theHTMLTitleSection: Added. . . . 411
\theHTMLTitleSeparator: Refactored. 411
General: 2018/11/19 1
\textbf and related: Improved font detection. 610

lwarp.css: Added css for xfrac, nicefrac. 274
lwarp.css: Fixed css for \textup. 274
lwarp.css: Reduced margins in titlepage. 274
lwarp_formal.css: Fix: Font for verse. 311
2in1: Added. 640
CJKutf8: Prevented unless xeCJK. . 746
CJK: Prevented unless xeCJK. 745
asymptote: Improved alt tags. . . 672
bitpattern: Added. 694
calc: Fix: Required for print version. 244
chngpage: Fix: Loads lwarp-chngpage. 744
ctexpatch: Added patch. 634
flippdf: Added. 815
graphics: Fix: Filename expansion. 854
graphics: Fix: FormatWP. 852
musicography: Added. 993
nicefrac: Improved font control and css, honors nice, ugly. 1011
notespages: Added. 1017
octave: Added. 1030
pdfcomment: Added. 1042
pdfmarginpar: Added. 1043
register: Updated to v1.8. 1067
rviewport: Added. 1074
semantic-markup: Added. 1087
textcomp: Fix conflict with xunicode. 1173
tram: Added. 1210
twoup: Added. 1213
ulem: Improved compatibility with CJKulem. 1216
ulem: Now works in a lateximage. 1216
unitsdef: Added. 1223
units: Improved font control and css, honors loose, tight. 1223
xcolor: Fix: Horiz white space. . . . 1244
xechangebar: Added. 1247
xfrac: Improved css. 1250
xunicode: Fix conflict with textcomp. 1257
Added early checks for CJK, CJKutf8. 209
Docs: asymptote. 164
Docs: miktex-poppler-bin-* 84
Docs: *MiKTeX Console* 80
Docs: Improved MiKTeX install instructions. 80
Docs: UTF-8 locale. 181
File: lwarp_mathjax.txt: Removed inoperable siunitx extension. 318
Logos: CSS instead of <sup>, <sub>. 628
Logos: Fix for XeTeX logo if graphics is not loaded. 628
Logos: Improved CSS. 628
Logos: Made robust. 628
fcolorminipage: xcolor: Fix: Horiz white space. 1245
Fix: No longer requires xifthen. . . 596
fminipage: Fix: Horiz white space. . 609
LWR@blocktextcurrentfont: Added print version. 619
v0.63
\LWR@HTMLLatexCmd: ujarticle and related: Compile options. 273
\LWR@LwarpStart: Fixes for xeCJK. . 415
\LWR@atbeginverbatim: Fix for xeCJK. 433
\LWR@checkloadbefore: Added. . . . 207
\LWR@checkloadfilename: Added to reduce number of lwarp-* files. . 247
\LWR@compileuplatex: Added. 270
\LWR@createautosec: Fix for xeCJK. 401
\LWR@earlyclassloadnever: Added. 208
\LWR@filestart: Fix: Break ligature for luatexko. 413
\LWR@firstoffive: Added. 227
\LWR@htmlclosecomment: Fix: Break ligature for luatexko. 360
\LWR@isolate: Fix for xeCJK. 226
\LWR@notltjloadafter: Added more classes. 206
Added. 206
\LWR@subhtmlelementclass: Fix for xeCJK. 362
\LinkHome: Fix: Print version. 350
\linkhomename: Added. 350
General: 2018/12/03 1
lwarp.css: Added css for vertical writing. 274
lwarp.css: Improved css for mdframed. 274
amsthm, mdframed: Fix for enforced load order. 661
emumitem: v3.6: Nullifiy \DrawEnumitemLabel. 781
everyhook: Fix for bxjs* classes. . . 244
geometry: Fix for bxjs* classes. . . 242
mdframed: Avoid thin rules. 960
mdframed: Improved font control. 963–965
stfloats: Adapted to ltj* classes. . . 1146
xpinyin: Added. 1253
zhlineskip: Added. 1260
Added pTeXsupport. 205
Docs: \linkhomename. 111
Docs: \sidetocname. 113
Fix: Default \LWR@mdfive. 222

Improved titles. 963, 964
pTEX: Encoding. 223
pTEX: Load upquote. 224
pTEX: No newunicodechar. 223
LWR@BlockClassWP: Fix for xeCJK. . . 365
v0.64
\LWR@HTMLLatexCmd: utarticle and related: Added. 273
\LWR@checkloadfilename: Prevented bitfield, doublespace, newthm, rplain, si. 247
\LWR@section: Support for ujarticle and related. 406
\enskip: Made robust. 623
\qquad: Made robust. 623
\quad: Made robust. 622
\theHTMLTitleSeparator: Added utarticle and related. 411
General: 2018/12/08 1
addlines: Updated to v0.3. 650
biblatex: Added patch for CTEX. . . 687
bsheaders: Added. 702
gmeometric: Added. 847
marginal: Added. 940
rmpage: Added. 1072
scrlayer-scrpage: Fixes. 1083
scrlayer: Fixes. 1082
scrpage2: Added. 1084
ujarticle and related: Improved \today. 633
Added utarticle and related. 633
v0.65
\LWR@LwarpEnd: Improved css for page layout. 419
\LWR@LwarpStart: Improved css for page layout. 417
\LWR@PreloadedPackage: \AtBeginDocument to avoid option clashes. 589
\LWR@hyperindexrefnullified: Added \textsi. 542
\LWR@newhtmlfile: Error if duplicate file name. 397
Improved css for page layout. 396, 399
\LWR@nullfonts: Added \textsi. . . 548
\LWR@restoreorigformatting: Fix: tabular*. 547
\enskip: Changed to Unicode EN SPACE. 623
\quad: Changed to Unicode EM SPACE. 622
\sishape: Added \sishape. 616
\textsi: Added. 613
General: 2018/12/22 1
lwarp.css: Added \sishape, \textsi. 274
lwarp.css: Improved css for page layout. 274
lwarp.css: Improved css for quotations. 274
lwarp.css: SideTOCto left for improved \marginpars. 274
lwarp_formal.css: SideTOCto left for improved \marginpars. . . . 311
lwarp_sagebrush.css: SideTOCto left for improved \marginpars. . . 306
bounddvi: Added. 699
embrac: Added. 771
footnoterange: Added. 830
gentombow: Added. 842
geometry: Fix for bxjs* classes. . . 242
graphics: Added \includegraphics alt key. . 593, 848, 850, 851, 854, 855
lltjext: Added. 924
multicolrule: Added. 987
multicol: Added \docolaction. . . 987
plarydshln: Added. 1054
plextarydshln: Added. 1056
plextcolortbl: Added. 1056
plext: Added. 1055
pxatbegshi: Added. 1060
pxeveryshi: Added. 1060
pxftnright: Added. 1061
pxjahyper: Added. 1061
tascmac: Added. 1161
versonotes: Added. 1228
Added early checks for jarticle, tarticle, and related. 209
Fix for \rensuji. 633
Fix space between class and id. . . 365
tabular: Added support for plext. . . 502
Fix: tabular*. 502
Fix: Rule color. 504
minipage: Refactored to later allow Japanese <t/y> argument. 601
LWR@figcaption: Uses <figurecaption> instead of <figcaption>. 526
v0.66
\@mpfootnotetext: Improved HTML formatting. 380
\IgnoreMinipageWidths: Added, . . 601
\LWR@@footnotetext: Improved HTML formatting. 379
\LWR@LwarpStart: Fix: TOC, LOF, LOT links. 418
\LWR@checkloadfilename: Prevented colortab, epsf, hyper, picinpar, picins, sistyle, ucs. 247
\LWR@closeparagraph: Fix: Combined span, tabular, and lateximage. . 369

Improved HTML formatting. 369
\LWR@closeparagraph@br: Factored. 368
\LWR@fboxstyle: Use current text color. 606
\LWR@filenamenoblanks: Fix: Section names detokenized. 387
Fix: Section names with macros. . 388
Fix: Section names with percent. . 388
Improved file name generation. . . 387
Limits filename length. 389
\LWR@findcurrenttextcolor: Fix: Color if xcolor not loaded. 619
\LWR@htmlfileref: No longer use zref. 510
\LWR@htmlsectionfilename: Sanitize underscores. 348
\LWR@hyperindexrefsubtwo: Fix: Long index entries. 544
\LWR@indentHTML: Added. 357
\LWR@lateximagedepthref: No longer use zref. 510
\LWR@lateximagenumberref: No longer use zref. 510
\LWR@nameref: No longer use zref. . . 509
\LWR@nullfonts: Logos. 550
\LWR@openparagraph: Improved HTML formatting. 368
\LWR@section: Fix: TOC, LOF, LOT links. 407
Improved HTML formatting. 407
\LWR@setexparray: Fix with \par. . 344
\LWR@setref: No longer use zref. . . 509
\LWR@simplifyname: Added. 386
\LWR@startref: No longer use zref. . 513
\LWR@stoppars: Improved HTML formatting. 371
\LWR@subhtmlelementclass: Improved HTML formatting. . . . 362
\LWR@subhyperrefclass: Improved HTML formatting. 517
\LWR@subinlineimage: Improved HTML formatting. 518
\LWR@write@lwarplabel: No longer use zref. 510
\LWR@writeconf: Added ImagesDirectory and ImagesName. 273
\LinkHome: Fix: Document cross-references. 350
\UseMinipageWidths: Added, ... 601
\fbox: Fix: Removed extra space. . . . 606
\minipagefullwidth: Made \global. 600
\rotatebox: Improved HTML formatting. 858
\rule: Improved HTML formatting. . . 626
\scalebox: Improved HTML formatting. 859
\textgreater: Made robust. 347
\textless: Made robust. 347
General: 2019/02/08 1
LWR@currentautosecpage: Fix for LOF, LOTfloat in home page. . . . 383
lwarp.css: Added niceframe. . . . 274
lwarp.css: Improved CSS for definition lists. 274
lwarp_formal.css: Improved CSS for table notes. 311
lwarp_one_limage.txt: Image directory and prefix. 317
acronym: Fix for acronym in caption. 649
acronym: No longer uses zref. . . . 649
ar: Added. 667
ed: Added. 770
extramarks: Updated to v3.10. . . . 792
fancyhdr: Updated to v3.10. 798
fancyvrb: Improved HTML formatting. 794
graphics: Improved HTML formatting. 855
kotexutf: Patch for references. . . . 635
memoir: Docs re: version numbers. 172
multicolrule: Updated for v1.2. . . . 987
nameauth: Added. 996
register: Verified for v1.9. 1067
subcaption: Added. 1147
tocbasic: Updated to v3.26a. 1197
truncate: Added. 1213
zref: No longer used. 246
lwarpmk: Added ImagesDirectory and ImagesName. 322
lwarpmk: Fix for **cleanlimages**. . 322
Added early checks for colortab, epsf, hyper, picinpar, picins, sistyle, ucs. 209
Added option ImagesDirectory. . 233
Added option ImagesName. 233
Added support for indentfirst. . . . 372
Docs: Updated Converting an existing document. 100
Fix: Minipages inside multicols. . 986
Improved HTML formatting. 802
Package dates added where possible. 640
Sanitize filenames. 237
tabular: Fix: Minipages inside tabular. 505
lateximage: Added \BaseJobname for multiple projects. 581
Improved HTML formatting. 583
minipage: Honor \LWR@forceminipagefullwidth. 602
v0.67
\FilenameNullify: Added. . . . 551, 619

\FilenameSimplify: Added. . . . 386, 395
\LWR@doequation: xfakebold: Added support. 570
\LWR@doubledollar: xfakebold: Added support. 563
\LWR@filenamenoblanks: Improved file name generation. 387
\LWR@lookforpackagename: easyReview: Supported. 248
\LWR@nullfonts: Add'l symbols. . . . 548
\LWR@simplifycustom: Added. 386
\LWR@subsingledollar: xfakebold: Added support. 560
\LWR@subsingledollarsvg: xfakebold: Added support. . . 558, 559
General: 2019/02/23 1
academicons: Added. 643
bbding: Added. 683
changes: Added. 712
color: Fix for version number. . . . 752
dingbat: Added. 762
eurosym: Added. 791
fitbox: Added. 811
fontawesome5: Added. 827
fontawesome: Added. 825
foreign: Added. 831
gloss: Added. 844
karnaugh-map: Added. 890
marvosym: Added. 942
multicap: Added. 985
nomencl: Added. 1016
notes: Added. 1017
pifont: Added. 1053
struktex: Added. 1146
textcomp: Nullify in filenames. . . 1173
typicons: Added. 1215
umoline: Added. 1217
xfakebold: Added support. 552
xfakebold: Added. 1249
xunicode: Nullify in filenames. . . 1257
AMS environments: Added xfakebold support. 658
eqnarray: xfakebold: Added support. 575, 576
v0.68
\LWR@@footnotetext: Factored for multiple foot boxes. 378
\LWR@checkloadfilename: Prevented alg, algorithmic, fncylab, pdfcprot. 247
\LWR@printpendingfootnotes: Factored for multiple footnote boxes. 381
\LWR@tabular@warpprintonly: Added. 501
General: 2019/03/05 1
bigfoot: Added. 693
fnpara: Added. 825
footnotebackref: Added. 830
layouts: Added. 903
listings: Fix for listings v1.7. 923
longtable: Improved error handling. 927
manyfoot: Added. 939
niceframe: Added. 1012
perpage: Added. 1048
showtags: Added. 1091
tablefootnote: Added. 1157
threeparttablex: Added. 1183
threeparttable: Fix for caption type. 1182
lwarpmk: Improved error handling if incomplete compile. 322
Prevented alg, algorithmic, fncylab, pdfcprot. 209
tabular: Fix: \warpprintonly inside tabular. 503
v0.69
\LWR@maybetocdata: Added support for tocdata. 534
\framebox: Fix: Handle paren arg. . . 606
\hypertoc: Added support for tocdata. 534
\hypertocfloat: Added support for tocdata. 536
\makebox: Fix: Handle paren arg. . . . 605
\multicolumnrow: multirow: Error if \multirow without \mrowcell. . . 992
General: 2019/03/21 1
array: Fix for \tabularnewline. 669, 927
ctable: Added. 755
eqlist: Added. 784
eqparbox: Added. 785
ftcap: Added. 837
graphics: Warning if using scale option. 850
keyfloat: Updated for v2.00. 893
listliketab: Added. 923
minitoc: Added. 977
multirow: Error if \multirow without \mrowcell. 990
rotating: Requires graphicx. 1073
supertabular: Fix: Clear caption after use. 1155
tabularx: Require array. 1157
tabulary: Require array. 1158
tocdata: Added. 1200
topcapt: Added. 1210
xtab: Fix: Clear caption after use. . 1257
tabular: Error if \multirow without \mrowcell. 503, 505, 506
lateximage: Fix for *pdftotext* errors from font size change. 586

fminipage: Honors \minipagefullwidth. 608
v0.70
\LWR@closeparagraph: Reduced underfull \hbox warnings. 369
\LWR@lookforpackagename: changes: Updated to v3.1.2. 248
\LWR@mathjaxfilename: Added. . . . 374
\LWR@restoreorigformatting: Fix: \& in a lateximage. 547
\MathJaxFilename: Added. 374
\enddocument: If labels changed, require recompile before making limages. 419
\framebox: Fix: Accept long arg. . . . 606
\makebox: Fix: Accept long arg. . . . 605
Fix: Ignore width of 0pt. 605
Fix: No width given. 605
General: 2019/04/03 1
autonum: Added. 678
changelayout: Added. 711
changes: Updated to v3.1.2. 712
inputtrc: Added. 886
mathtools: Added. 950
metalogox: Added. 971
metalogo: Used in print mode. . . 971
textcomp: Fix for \textinterrobang. 1171
textpos: Added optional arg to textblock. 1174
xunicode: Fix for \textinterrobang. 1257
AMS environments: Refactored. . . 658
Ensure vector font. 224
File: lwarp_mathjax.txt: Loads autoload-all.js extension. . . . 318
File: lwarp_mathjax.txt: Updated to MathJax v2.7.5. 318
Logos: Improved for metalogox, lateximages. 628
LWR@nestspan: Improved minipage, \parbox inside a span. 359
v0.71
\@mpfootnotetext: Improved HTML formatting. 380
Reduced underfull \hbox warnings. 380
\LWR@closeparagraph: Flush left captions. 369
\LWR@closetabledatacell: Fix: Tabular par tags. 452, 453
\LWR@stoppars: Reduced underfull \hbox warnings. 371
\expandcolspec: Added support for tabular '*' column. 464
General: 2019/04/29 1
caption: Reduced underfull \hbox warnings. 706
chemfig: Updated to v1.4. 718
endfloat: Updated for v2.7. 772
lwarp-common-multimedia: Added. 1293
media9: Added. 968
movie15: Added. 984
multimedia: Added. 988
textpos: Updated for v1.9.1. 1174
lwarpmk: If wrong lwarpmk.conf version, or wrong OS, displays the print command to recompile. . . . 322
Docs: Error testing. 194
quotation: Fix: blockquotation tag. 431
v0.72
\LWR@newautopagelabel: Fix: References for xr, xr-hyper. 384
\LWR@printmccoldata: Fix: \multicolumn parameters. 486
\LWR@restoreorigformatting: Use \LWR@formatted for \bfseries, etc. 547
\chapter: Added support for hypbmsec. 410
\ebweight: nfssext-cfr: Added. . . . 615
\hypertoc: Fix: References for xr, xr-hyper. 534
\hypertocfloat: Fix: References for xr, xr-hyper. 535
\lgweight: nfssext-cfr: Added. . . . 615
\paragraph: Added support for hypbmsec. 410
\part: Added support for hypbmsec. 409
\section: Added support for hypbmsec. 410
\subparagraph: Added support for hypbmsec. 410
\subsection: Added support for hypbmsec. 410
\subsubsection: Added support for hypbmsec. 410
\texteb: nfssext-cfr: Added. 611
\textlg: nfssext-cfr: Added. 611
\textulc: fontaxes: Added. 612
\ulcshape: fontaxes: Added. 616
General: 2019/06/08 1
lwarp.css: Added backnaur. 274
lwarp.css: Removed unneeded support for \sishape, \textsi. . 274
backnaur: Added. 681
boxedminipage2e: Added support for lateximages. 699
changes: Fix references for xr, xr-hyper. 712

fontaxes: Added. 614, 827
gloss: Fix references for xr, xr-hyper. 844
hypbmsec: Added. 866
minibox: Added. 976
nfssext-cfr: Added. 1005
nomencl: Fix references for xr, xr-hyper. 1016
pdfcrypt: Added. 1043
shapepar: Added. 1091
slantsc: Added. 1125
soulutf8: Fix: Loads soul. 1128
tabfigures: Added. 1157
xr-hyper: Added. 1255
xr: Added. 1255
zhlineskip: Updated to v1.0e. 1260
Use \LWR@formatted for \bfseries, etc. 264, 614
v0.73
\@include: Fix: \newpage instead of \clearpage. 253
\HTMLTitle: Added default title if none specified. 375
\LWR@LwarpStart: Fix: Empty header/footer. 417
\LWR@addbaselinemarker: Improved warning messages. 554
\LWR@createfooter: Fix: Empty header/footer. 395
\LWR@descitem: Fix: HTML tags. . . . 442
\LWR@forceemptyline: Added. 227
\LWR@gsavebox: Added global save boxes. 228
\LWR@htmlelementclass: Vertical space. 362
\LWR@htmlelementclassline: Vertical space. 363
\LWR@indentHTMLtwo: Added. 358
\LWR@indexitem: Fix: Avoid empty 538
\LWR@indexsubitem: Fix: Avoid empty 538
\LWR@indexsubsubitem: Fix: Avoid empty 538
\LWR@newhtmlfile: Fix: Empty header/footer. 398
\LWR@nullfonts: Fix: \hspace in sectioning file name. 550
\LWR@titlingmaketitle: titling: Fix: Paragraph tags. 428, 1196, 1197
Fix: Paragraph tags. 428
\attribution: Fix: Paragraph tags. . 430
\color: xcolor: Added HTML support. 1241
\fboxBlock: Fix: Paragraph tags. . . . 607
\hspace: Fix: Avoid empty . . 624
\l@book: Added \book for memoir. . 536
\maketitle: titling: Fix: Paragraph tags. 1195
Fix: Paragraph tags. 427
\marginparBlock: Fix: Paragraph tags. 382
\postbookname: Added \book for memoir. 408
\printthanks: Fix: Paragraph tags. . 424
\rule: Fix: Avoid empty 627
General: 2019/07/11 1
lwarp.css: Added \book for memoir. 274
lwarp.css: Improved pkgtocdata formatting. 274
lwarp_formal.css: Added \book for memoir. 306, 311
boxedminipage2e: Fix: Paragraph tags. 699
epigraph: Fix: Paragraph tags. . . . 781
fancyvrb: Fix: Nested /<pre>. 803, 806
fancyvrb: Btrivlist: Fixed paragraph tags. 796
intopdf: Updated to v0.2.1. 886
listings: Fix: Paragraph tags. 922
lwarp-common-multimedia: Fix: No size for audio file. 1293–1295
lwarp-common-multimedia: Fix: Paragraph tags. 1296
lwarp-patch-komascript: Fix for captions. 1263
lwarp-patch-memoir: Added \book. 1270
lwarp-patch-memoir: Fix for \frontmatter* and \mainmatter*. 1271
lyluatex: Added. 936
musicography: Updated to 2019/05/28. Now supports lateximages. 993
quotchap: Fix: Paragraph tags. . . 1062
quotchap: Updated to v1.2. 1062
quoting: Fix: Paragraph tags. 1063
scrextend: Fix: Paragraph tags. . . 1079
stackengine: Added. 1132
threeparttable: Added measuredfigure. 1182
tocdata: Honors \tocdataformat. 1200
tocdata: Improved formatting. . . . 1200
tocdata: Updated to v2.03. 1200
versonotes: Updated to v0.4. 1228
vwcol: Fix: Paragraph tags. 1231
xy: Fix for \xybox. 1259
xy: Improved xy, reverted \xymatrix, for qcicuit. 1259
Added \book for memoir. . . . 340, 356

AMS environments: Fix: alt tags. 658
AMS environments: Fix: Paragraph tags. 658
Numbered HTML entity used for text dollar. 553
tabular: Fix and warning for tabular inside a . 502
LWR@blocktextcurrentfont: Fix: Paragraph tags. 614
LWR@nestspan: Fix: quote, quotation inside a span. 359
v0.74
\@ensuredmath: Add \ThisAltText. 564
\AltTextClose: Added. 551
\AltTextOpen: Added. 551
\ImageAltText: Added. 551
\LWR@ThisAltText: Add \ThisAltText. 552
\LWR@addlinktitle: Added. 513
\LWR@doequation: Add \ThisAltText. 570, 571
\LWR@doubledollar: Add \ThisAltText. 563
\LWR@lateximage@oneimage: Factored from lateximage. 581
\LWR@lateximage@oneimageb: Factored from lateximage. 580
\LWR@setcurrentfont: Factored. 553
\LWR@singledollar: Add \ThisAltText. 563
\LWR@singledollarmeasure: Fix: Font control. 555
\LWR@subinlineimage: Add \ThisAltText. 518
\LWR@subsingledollar: Add \ThisAltText. 561
\LWR@subsingledollarsvg: Adds star argument for lateximage. 558
\LateximageFontScale: Adjusted SVG math font scaling default to 1. 578
\MathImageAltText: Renamed from \mathimage. 552
\PackageDiagramAltText: Renamed from \packagediagramname. 552
\ThisAltText: Add \ThisAltText. 552
\hspace: Ignore negative space. 623
General: 2019/09/02 1
lwarp.css: Added lyluatex. 274
amsmath: Add \ThisAltText. 659
forest: alt text. 831
geometry: Remembers user's geometry. 842
graphics: Add \ThisAltText. 850, 855, 856
lyluatex: Adapts to user's geometry. 936
lyluatex: Preserves left margin. 936
lyluatex: Renamef \lyluateximagename. 936
lyluatex: Split system images, assign class. 936
mhchem: Modified for new lateximage. 973
pdfpages: Adjust to user's paper size. 1045
stackengine: alt tags. 1132
struktex: alt text. 1146
tikz: Added alt text. 1185
lwarpmk: **lwarpmk clean** removes add'l files. 322
lwarpmk: **lwarpmk epstopdf** and **pdftosvg** honor directories. 322
Remembers user's geometry. 241
lateximage: Add \ThisAltText. 586
Added second starred argument. 581, 587
Improved alt text. 583
New syntax for \LWR@subinlineimage. 586
eqnarray: Add \ThisAltText. 576
LWR@displaymathother: Uses \MathImageAltText. 565
LWR@equationother: Uses \MathImageAltText. 565
v0.75
\normalcolor: xcolor: Added for HTML. 1239
General: 2019/09/23 1
lwarp.css: Improved marginblock. 274
keyfloat: Fix: \normalcolor. 893, 894
wrapfig: Fix for \linewidth. 1236
wrapfig: Fix for width. 1235
minipage: Fix: \linewidth. 603
v0.76
General: 2019/10/08 1
lwarp.css: Fix for small caps. 274
acro: Updated for v2.10. 646
xr-hyper: Updated for v6.1. 1255
xr: Updated for v5.05 and xr-hyper v6.1. 1255
Docs expanded: Multiple projects. 97
File: lwarp_mathjax.txt: Updated to MathJax v2.7.6. 318
v0.77
General: 2019/10/15 1
booktabs: Updated to v1.6180339. 697
chemformula: Updated to v4.15. 721
v0.78
\LWR@linkcatcodes: babel-french: Fix: Hyperlinks. 516
Factored. 516

\LWR@linkmediacatcodes:
babel-french: Fix: Hyperlinks. . . 517
Factored. 516
\LWR@nullifyNoAutoSpacing:
babel-french: Fix: Hyperlinks. . . 502
\LWR@subhyperrefclass: Remove extra space. 517
\normalfont: Uses \LWR@formatted. 617
General: 2019/11/07 1
accessibility: Added. 645
babel-french: Fix: Hyperlinks. . . . 356
caption: Added warning regarding passing options. 705
filecontents: Fix to overwrite existing files using new filecontents environment. 244
geometry: Cleaner option handling. 842
graphics: Fix: alt tag expansion. . 855
lwarp-common-multimedia: Fix links with new LaTeX kernel. 1293, 1294
titlesec: Fix for \titleclass. . . . 1191
v0.79
\CustomizeMathJax: Fix: Sanitize for HTML. 393
\LWR@ProvidesPackagePass: Fix: catoptions. 251
\LWR@checkloadfilename: Prevented bxcjkjatype, hangul. 247
\LWR@closetabledatacell: Fix: Nested tabulars. 454
\LWR@customizeMathJax: MathJax: Hide definitions. 395
\LWR@forcenewautoidanchor: Factored. 523
\LWR@mathjaxwarn: Warn if using packages partially supported by MathJax. 637
\LWR@parseaftercolumn: Remove outermost braces. 460
\LWR@parseatcolumn: Remove outermost braces. 458
\LWR@parsebangcolumn: Remove outermost braces. 459
\LWR@parsebeforecolumn: Remove outermost braces. 460
\LWR@setexparray: Fix: Nested tabulars. 344
\LWR@singledollarmeasure: Factored. 555
\LWR@subHTMLsanitize: Fix: \&. Factored. 390
\LWR@subsingledollarsvg: Adjust for unknown size. 558
Factored. 557
\LWR@tabularendofline: Fix: Nested tabulars. 457
\captionlistentry: Fix: Duplicate auto-id. 527
\macrotocsname: Added. 229
\makebox: Fix: Adjust for virtual page size. 605
\multicolumnrow: multirow: Fix: Nested tabulars. 992
\noalign: Fix: Nested tabulars. . . . 501
General: 2020/02/01 1
MathJax: Additional macros. . . . 393
lwarp.css: Fix: Nested tabulars. 274
amsmath: Added MathJax emulation. 660
arydshln: Added MathJax emulation. 671
ar: Added MathJax emulation. . . 669
awesomebox: Added. 679
babel and polyglossia: Added info messages. 636
bigdelim: Added MathJax emulation. 693
bigstrut: Added MathJax emulation. 694
bm: Added. 695
booktabs: Added MathJax emulation. 698
booktabs: Fix for memoir with lateximage. 500, 697
braket: Added. 700
floatflt: Improved width control. . 817
fontawesome5: Supports font size, color. 827
fontawesome: Refactored with fix for \FAthree. 825
fontawesome: Supports font size, color. 825
geometry: Also save \textwidth, \textheight. 243
graphics: Factored from \LWR@includegraphicsb. . . 852, 853
graphics: Fix for negative angles. . 851
ifpdf, ifptex: Provided by iftex. . . 205
keyfloat: Factored to \LWR@setvirtualpage. 898
ltablex: Fix: Require longtable. . . 928
ltxtable: Fix: Required packages. . 930
luatex85: Removed. 205
mathtools: Added MathJax emulation. 951
multirow: Add: MathJax emulation. 992
multirow: Fix: Centered vertical alignment. 991
niceframe: Fix: Adjust for virtual page size. 1012

parallel: Added. 1034
parcolumns: Added. 1036
pdfcolfoot: Added. 1040
pdfcolmk: Added. 1041
pdfcolparallel: Added. 1041
pdfcolparcolumns: Added. 1041
pdfcol: Added. 1040
physics: Added. 1050
siunitx: Fix: \square, \cubed. . . . 1110
siunitx: Improved MathJax. 1108, 1109
slashed: Added. 1126
steinmetz: Added. 1146
svg: Added. 1155
transparent: Supports lateximages. 1211
unicode-math: Added. 1219
widetable: Added. 1233
witharrows: Added. 1233
xcolor: Fix: Nested tabulars. 1246, 1247
xltabular: Fix: Require ltablex. . . . 1251
xurl: Updated to v0.08. 1258
AMS environments: Fix: Nested. . 658
Factored to \LWR@setvirtualpage. 821, 855
Fix: Use newfloat instead of float. 821
Fix: Use full \linewidth. 821
Remember HTML font size. 620
tabular: colortbl: Fix: Nested tabulars. 504
Fix: Nested tabulars. 506
warpMathJax: Added. 240
lateximage: Improved \linewidth. . 584
minipage: Fix: \linewidth frame padding. 603
Fix: Adjust for virtual page size. . . 601
fminipage: Fix: Adjust for virtual page size. 609
LWR@setvirtualpage: Factored. . . . 600
v0.80
\CustomizeMathJax: Fix: Made \@onlypreamble. 393
Warn of slow compile. 393
\LWR@checkloadfilename: Prevented formula, shadethm, slashbox. . . 247
\LWR@infoprocessingmathjax: Add: Info message. 393
\LWR@restoreorigformatting: Improved math, displaymath. . . 547
\fcolorbox: Made robust. 595
\fcolorboxBlock: Made robust. . . . 595
\includegraphics: Made robust. . . 857
General: 2020/02/19 1
\textbf and related: Use HTML series, etc. 610
accessibility: Added MathJax emulation. 645
accsupp: Added MathJax emulation. 646
autobreak: Added. 677
biblatex: Creates hyperlinks. 688
centernot: Added. 710
chemmacros: Updated to v5.10. 732, 739
extarrows: Added. 792
fewerfloatpages: Added. 810
fouridx: Added. 832
gensymb: Added. 841
ghsystem: Added. 843
gmeometric: Requires geometry. 847
hhline: Added. 865
leftidx: Added. 906
mathcomp: Added. 944
mathdots: Added. 946
mathfixs: Added. 946
mismath: Added. 978
nccmath: Added. 1000
noitcrul: Added. 1015
pdfcomment: Added MathJax emulation. 1042
relsize: Added MathJax emulation. 1069
rmathbr: Added. 1072
subsupscripts: Added. 1153
tagpdf: Added. 1158
unicode-math: Improved MathJax. 1219, 1221
url: Creates hyperlinks. 1225
xfrac: Added MathJax emulation. 1251
AMS environments: Fix: Centering starred envs. 658, 659
Improved math, displaymath. . . . 565
Prevented formula, shadethm, slashbox. 209
lateximage: Fix: Rule color in lateximage. 584
fcolorminipage: Made robust. . . . 596
eqnarray: Fix: eqnarray*. 576
v0.81
\LWR@addbaselinemarker: Improved warning messages. 554
\LWR@checkloadfilename: Prevented statex. 247
\LWR@replacestrings: Added. . . . 390
\LWR@subHTMLsanitize: Faster. . . . 390
\textcolor: xcolor: \textcolor: Spurrious space. 1241
General: 2020/03/04 1
lwarp.css: Added nolbreaks. . . . 274
DotArrow: Added. 763

SIunits: Improved \unit. Fixed in math mode. Added MathJax emulation. 1096
axessibility: Added MathJax emulation. 680
axessibility: Updated to 2020/01/08 version. 680
colonequals: Added. 751
decimal: Added. 760
dotlessi: Added. 763
econometrics: Added. 767
engtlc: Added. 774
gridset: Updated to v0.3. 861
hyperref: Added \pdfstringdefDisableCommands. 876
luamplib: Added. 931
multiobjective: Added. 988
nolbreaks: Added. 1015
physunits: Added. 1050
returntogrid: Added. 1071
stackrel: Added. 1134
statex2: Added. 1135
statmath: Added. 1144
lwarpmk: Improved error if in lwarp source directory. 322
Prevented statex. 209

v0.82

\LWR@disablepinyin: Added. 227
\LWR@doequation: MathJax: Improved footnotes. 570
\LWR@syncmathjax: Removed <par> tags. 567
General: 2020/03/25 1
MathJax: Improved footnotes. 394, 571
amsmath: Fixed: \intertext for MathJax. 660
chemfig: Updated to v1.5. 718
draftwatermark: Updated to v2.0. . 765
endnotes: Added MathJax emulation. 773
endnotes: Fix: Mark in print mode. 773
etoc: Added. 788
luatexko: Added. 931
lwarp-patch-memoir: Supports tocvsec2. . . . . 1271, 1275
marginnote: Added MathJax emulation. 942
marginnote: Fix: Neutralize in print mode. 941
nccfoots: Added MathJax emulation. 1000
pagenote: Added MathJax emulation. 1033
parnotes: Added MathJax emulation. 1039
sidenotes: Added MathJax emulation. 1095
soul: Fixed: \<. 1126
syntonly: Added \nopages@. 1156
syntonly: Added to \LWR@loadafter. 211
ulem: Fixed: \dashuline. 1216
xpinyin: Added full pinyin support. 1253

v0.83

General: 2020/03/27 1
lwarp-patch-memoir: Fixed framed. 1265
lwarp-patch-memoir: Fixed: \specialindex. 1287
lwarp-patch-memoir: No longer requires subfigure. 1265
lwarp-patch-memoir: Updated for new sizes. 1267
lwarp-patch-memoir: Updated. 1269, 1270
physunits: Updated to v1.0.4. 1050

v0.84

\@currentHref: backref: Fixed from lwarp v0.72 changes. 516
\@currentlabelname: Default name for previous/next links. 507
\@fnsymbol: \LWR@formatted, fixed double bar. 427
\@makecaption: caption now optional. 524
Warn inside a 525
\@textsubscript: Use \LWR@formatted. No longer \AtBeginDocument. 618
\@textsuperscript: Use \LWR@formatted. 618
\@xdlbfloat: caption now optional. 522
\AddSubtitlePublished: Added \subtitle, \published for koma*. 429
Fixed \subtitle, \printsubtitle if no titling. 429
\HTMLFirstPageBottom: Added \FirstPageBottom. 373
\LWR@LwarpEnd: Added prev/next links. 419
Fix: No footer for epub 419
\LWR@LwarpStart: Added prev/next links. 417
\LWR@createfooter: Added \FirstPageBottom. 395
\LWR@domulticolumn: Fix: Multicolumn style. 489
\LWR@excludecomment: Independent cut files. 239
\LWR@filenamenoblanks: Fix: Dashes in filename. 389

\LWR@filestart: Improved HTML title. 412
\LWR@floatbegin: Warn inside a . 520
\LWR@forcenewautoidanchor: <par> handling. 523
\LWR@htmlsectionfilename: Fix: Sections called "Index" or "index" have -0 appended to their filenames if no prefix. 348
\LWR@new@label: Removed optional args. 512
\LWR@newhtmlfile: Added prev/next links. 397, 399
\LWR@nullfonts: Add'l symbols. 548
Factored out redefinitions. 548
Fix: Accents. 548
Revised \texorpdfstring. 551
\LWR@section: Added prev/next links. 408
Warn inside a . 403
\LWR@startpars: Ignore if in lateximage. 370
\LWR@stoppars: Ignore if in lateximage. 371
\LinkNext: Added prev/next links. 352
\LinkPrevious: Added prev/next links. 352
\attribution: Added print mode. 430
\caption@end: caption now optional. 527
\captionlistentry: caption now optional. 527
\captionof: caption now optional. 528
\end@dlbfloat: caption now optional. 522
\linknextname: Added prev/next links. 351
\linkpreviousname: Added prev/next links. 351
\printthanks: Fix: \printthanks in print mode. 423
\sscshape: Moved to core. 617
\textssc: Moved to core. 613
\textsubscript: Use \LWR@formatted. No longer \AtBeginDocument. 618
\textsuperscript: Use \LWR@formatted. 618
\theHTMLTitleSeparator: Improved spacing for xeCJK. 411
\verbatiminput: Added print mode. 435
General: 2020/04/24 1
LaTeX accents: Add'l symbols. 265
lwarp.css: Added koma-* subject. 274
lwarp.css: Fix: Minipage tex align. 274
lwarp.css: Fix: Top nav if narrow window. 274
lwarp.css: Improved nfssext-cfr. 274
lwarp.css: Improved realscripts. 274
abstract: Updated for memoir. 642
alltt: Added print mode. 656
amsthm: Fix for \nameref. 663
backref: Fixed from lwarp v0.72 changes. 682
biblatex: Fixed: Requires hyperref. 688
boxedminipage: Renamed from boxedminipage2e per author. 699
caption: Improved integration. 706
caption: Non-width \parboxes. 705
caption: Simplified. 705
epigraph: Added print mode. 781
fixme: Added section name. 813
float: Fix: Recursive name. 816
fontaxes: Moved sscshape to core. \FilenameNullify. 827
lwarp-patch-memoir: Creates mark macros. 1274
lwarp-patch-memoir: Fix: \label. 1266
lwarp-patch-memoir: Fixed pagenotes. 1284
lwarp-patch-memoir: Improved cleveref support. 1284
lwarp-patch-memoir: No longer requires subcaption. 1265
lwarp-patch-memoir: No longer uses subcaption. 1281
lwarp-patch-memoir: Use LaTeX captions. 1279
lwarp-patch-memoir: Uses memoir's \newcomment, \commentsoff, \commentson. 1285
lwarp-patch-memoir: \contsubtop, etc. now as-is. 1292
lwarp-patch-memoir: caption now optional, removed dup caption. 1282
mdframed: Warn inside a . 961
memoir: Preloads xcolor. 633
nfssext-cfr: Improved. 1005
nfssext-cfr: \FilenameNullify. 1007, 1010
ntheorem: Warning if thref. 1019
parcolumns: Fixed: Missing \colplacechunks. 1037
realscripts: Added print mode. 1064
realscripts: Fixed starred \textsuperscript, \textsubscript. 1064
realscripts: Improved supersub scripts. 1064
rotfloat: Fix: Requires rotating. 1074
scrextend: Added \titlehead, \subject, \subtitle, \published. 1077
scrextend: Updated to v3.29. 1076

sidenotes: \sidecaption not long arg. 1094
slantsc: \FilenameNullfiy. 1125
titling: \AtBeginDocument. 1194
xpinyin: Disables pinyin when null fonts. 1255
lwarpmk: clean also removes comment_*.cut 322
Added \FirstPageBottom. 373
Added prev/next links. 348
Docs: JetBrain Mono font. 104
Docs: \linkpreviousname. 111
Fix: Multirow style. 991
Fixed: textcomp now in kernel. . . 632
Logos: Only warn about graphics if actually use \Xe. 628
tabbing: Restore spacing. 435
center: Added print mode. 587
verbatim: Added print mode. 435
verse: Added print mode. 432
flushleft: Added print mode. 587
flushright: Added print mode. . . . 587
longtable: caption now optional. . . 926
quotation: Added print mode. 431
quote: Added print mode. 431
LWR@nestspan: Issue warnings inside a span. 359
Nullified minipage, \parbox inside a span. 359
v0.85
\LWR@atbeginverbatim: Fix: Added print macros for fontspec. 434
\LWR@htmlclosecomment: Fix: Added print macros for fontspec. 360
\LWR@htmlcomment: Fix: Added print macros for fontspec. 361
\LWR@htmltagc: Fix: Added print macros for fontspec. 358
General: 2020/05/01 1
idxlayout: Fixed: \AtBeginDocument for load order. 879
mathtools: Fixed: \shortintertext. 953
titlesec: pagestyles option. 1189
url: Fixed print mode. 1225
Fix: Added print macros for fontspec. 614
v0.86
\LWR@filenamenoblanks: Fix: *, (,), . in filename. 388
\LWR@filestart: Error if missing file. 414
\LWR@href: hyperref: Adjusted emulation. 517
\LWR@label@createtag: Fix: Labels in eqnarray. 511
\LWR@label@inmathcomment: Fix: Labels in eqnarray. 511
\LWR@nolinkurl: hyperref: Adjusted emulation. 518
\LWR@phantomsection: hyperref: Adjusted emulation. 628
\LWR@startref: Fixed: \label inside lateximage. 514
\LWR@syncmathjax: Improved MathJax equation numbers. . . . 567
\LWR@url: hyperref: Adjusted emulation. 518
\textcolor: xcolor: \textcolor: Fixed for babel-french. 1241
General: 2020/05/12 1
LWR@insidemathcomment: Added. 552
amsmath: Added support for MathJax. 660
hyperref: Adjusted emulation. . . . 872
mathtools: Added \ArrowBetweenLines*. 952
mathtools: Added \shortvdotswithin*. 953
mathtools: Added starred delimited macros. 953
nccmath: Added \displaybreak. 1001
nccmath: Fixed \nr, added starred. 1001
File: lwarp_mathjax.txt: Added support for starred macros. 318
File: lwarp_mathjax.txt: Improved equation numbering. 318
File: lwarp_mathjax.txt: Updated to MathJax v3 current. 318
v0.87
\LWR@checkloadfilename: Prevented csvtools. 247
\bibliography: Reverted to original. 545
\scshape: Added FixSmallCaps to remove \LWR@print@scshape for erewhon, et. al. 616
\sishape: Added FixSmallCaps to remove \LWR@print@scshape for erewhon, et. al. 616
General: 2020/06/03 1
cancel: Now uses MathJax v3 extension. 703
citeref: Added. 745
drftcite: Added. 765
embrac: Neutralized kerning. . . . 771
ifpdf, ifptex: Restored to work on TL2019 and earlier. 205
jurabib: Added. 889
mathtools: Improved \underbraket, \overbracket. 951
mathtools: Updated starred macros. 951

mhchem: Now uses MathJax v3 extension. 973
multibib: Added. 985
nccmath: Updated starred, improved \underref. 1001
physics: Now uses MathJax v3 extension. 1050
splitbib: Added. 1128
statex2: \pBin exponent. 1135
Added FixSmallCaps to remove \LWR@print@scshape for erewhon, et. al. 610
Docs: Updated docs to compile lwarp documentation. 190
File: lwarp_mathjax.txt: Now provides \ifstar, \ifnextchar. . 318
Prevented csvtools. 209
v0.88
\@wrindex: Added support for *xindex*. 539
\IndexRangeSeparator: Added. . . . 537
\LWR@HTML@ref: Added MathJax. . . 515
Fixed: Starred. 514
\LWR@LetLtxMacrocs: Added. 229
\LWR@absorbstar: Added. 229
\LWR@checkloadfilename: Prevented shadethm. 247
\LWR@doindexentry: Adapts to gindex. 542
\LWR@doindexentrysub: Adapts to gindex. 542
\LWR@doindexentrysubsub: Handles a range, for *xindex*. 542
\LWR@forcenewautoidanchor: Inline handling. 523
\LWR@hyperindexrefsubtwo: Adds support for a range, for *xindex*. . . 544
\LWR@indexnameref: Added IndexRef option, refactored. 541
\LWR@maybe@orignewpage: Added. . 228
\LWR@printchaptername: Conditionally print \chaptername. 403
\LWR@restoreMathJaxformatting: Added. 546
\LWR@restoreorigformatting: Added \vdots. 547
Support for MathJax. 547
\LWR@section: Conditionally print \chaptername. 407
\LWR@xindex@modifyentry: Added support for *xindex*. 538
\hrulefill: Full line if not started paragraph. 621
\hyperindexformat: Added. 544
\hyperindexref: Rewritten to parse commas and ranges. 543
\hyperpage: Added. 544
\nohyperpage: Added. 544
General: 2020/07/19 1
lwarp.css: Added indexheading for gindex. 274
lwarp.css: Added tcolorbox, thmbox. 274
amsmath: Added \dotso text mode. 657
amsthm: Requires amsmath. . . . 661
caption, scrextend: Fixed \caption*. 706
cleveref, varioref: Fix for starred macros. 749
fancyref: Now uses varioref which ignores page-related output. . . . 800
fbox: Added. 808
gindex: Added. 843
hhtensor: Added. 866
mleftright: Added. 982
pdfrender: Restored for xfakebold. 1046
shadethm: Added. 1090
tcolorbox: Added. 1162
termcal: Added. 1169
thm-listof: Added. 1179
thm-restate: Added. 1180
thmbox: Added. 1180
ushort: Added. 1225
varioref: Removed page-related text. 1226
xfakebold: Now works with pdfrender. 1249
Added \vdots. 264, 620
Added LWR@texboxdepth. 227
Added IndexRef option. 235
Added xindex option. 235
Option xindexConfig added. . . . 234
Prevented shadethm. 209
v0.883
General: nfssext-cfr: Fixed \textsw. 1008
v0.89
\@opargbegintheorem: Allow preload of amsmath, amsthm, centernot. 437
\LWR@HTMLsanitizeexpand: Fix: Nested MathJax environments. . 391
\LWR@LwarpStart: MathJax: Improved info message. 417
\LWR@addmathjax: TT font for MathJax. 568
\LWR@amsmathbodynumbered: \textendash for number range. . 580
\LWR@customizeMathJax: Print MathJax customizations with typewriter font. 395
\LWR@doubledollar: TT font for MathJax. 562

\LWR@patcherror: Improved message. 226
\LWR@singledollar: TT font for MathJax. 563
\LWR@subsingledollar: TT font for MathJax. 561
\enddocument: Adapt to LaTeX core changes. 419
General: 2020/09/03 1
accents: Added. 644
atbegshi: Adapt to LaTeXkernel changes. 673
caption3: Split from lwarp-caption. 706
caption: Adapt to v3.5. 705
centernot: Improved. 710
econometrics: Uses lwarp-common-mathjax-letters. 767
everyshi: Adapt to LaTeXkernel changes. 791
everyshi: Included in LaTeX core. . . 632
hepunits: Added. 864
lwarp-common-mathjax-letters: Added. 1297
lwarp-common-mathjax-newpxtxmath: Added. 1304
lwarp-common-mathjax-overlaysymbols: Added. 1312
mathalpha: Added. 942
mathdesign: Added. 944
mathpazo: Added. 947
mathptmx: Added. 947
mathtools: Added \adjustlimits. 951
mathtools: Minor improvements. 951, 955
mismath: Improved math operators. 978
newpxmath: Added. 1002
newtxmath: Added. 1002
newtxsf: Added. 1003
pxfonts: Added. 1061
shuffle: Added. 1092
siunitx: Fix: MathJax for \tothe, \raiseto. 1112
siunitx: Unicode for endash. 1115
statmath: Fixed abcbm, uses lwarp-common-mathjax-letters. 1144
thm-listof: Updated to v0.72. 1179
thm-restate: Updated to v0.72, no changes needed. 1180
thmtools: Added. 1181
txfonts: Added. 1213
upgreek: Added. 1224
lwarpmk: clean also removes *.bbl 322
Allow preload of amsmath, amsthm, centernot. 211, 632
AMS environments: Fix: <ALT> text env name. 658
Foreground/background hooks: Adapt to LaTeX core changes. 420
MathJax: Added \protect, and \mathcode and related. 394
Removed \let of \[, \]. 565
eqnarray: \textendash for number range. 575
v0.891
\LWR@atbeginverbatim: Fix for verbatim, alltt with lists 434
\LWR@checkloadfilename: Prevented libgreek. 247
\LWR@excludecomment: Error if nested comment. 239
\LWR@subHTMLsanitize: Neutralized single quotes. 391
\verb: \verb as \texttt. 433
General: 2020/09/22 1
biblatex: Fixed: Back page references. 689
bussproofs: Added. 702
caption: Improved integration. . . 706
cmbright: Added. 750
colonequals: Uses Unicode and \mathrel. 751
fancyvrb: Fix: BVerbatim with labels. 803
fourier: Added. 832
hyperref: Added backref, pagebackref. 867
hyperref: Fixed \texorpdfstring with babel-french. 876
kpfonts-otf: Added. 902
kpfonts: Added. 900
libertinust1math: Added. 908
listings: Fix for MathJax: Moved \LWR@forcenewpage to start. 918, 920
listings: Improved HTML sanitizing. 918
listings: Improved spacing around ampersand. 918
lwarp-common-mathjax-newpxtxmath: Expanded for kpfonts. 1305–1307, 1309
lwarp-common-mathjax-newpxtxmath: Factored non-Unicode. . . 1306–1308
lwarp-common-mathjax-newpxtxmath: Reverse factored out Greek, non-Unicode. 1304
lwarp-common-mathjax-nonunicode: Added. 1310
mathdesign: Added \mathinner, \mathbin. 945
mathdesign: Added \mathop. . . . 945
mathdesign: Added \mathrel, \mathord. 945

mathdesign: Honors greekuppercase, greeklowercase. 944
mathdots: Added more macros, \mathinner. 946
mathfixs: Added \mathinner. . . . 946
mathpazo: Honors slantedGreek. 947
mathptmx: Honors slantedGreek. 947
mathtools: Improved \underbraket, \overbracket. 951
mathtools: Uses Unicode and \mathrel. 955
multiobjective: Improved. 988
newpxmath: Honors uprightGreek, slantedGreek. 1002, 1003
newtxmath: Honors uprightGreek, slantedGreek. 1002
nicefrac: Added \mathinner, improved fraction. 1012
scalerel: Added. 1075
shuffle: Added \mathbin, improved bar. 1092
txgreeks: Added. 1214
unicode-math: Added sans-style. 1220
units: Added \mathinner, improved fraction. 1223
File: lwarp_mathjax.txt: Renamed tagformat extension. 318
Prevented libgreek. 209
BVerbatim: fancyvrb: Fix: BVerbatim with labels. 807
v0.892
\LWR@subhtmlelementclass: Ignore empty class. 362
\fcolorbox: xcolor: Fixed second optional arg. 1243
\fcolorboxBlock: xcolor: Fixed second optional arg. 1243
General: 2020/10/07 1
fancyvrb: Adapted to fvextra. . . . 807
fancyvrb: Provided \FV@FrameFillLine. 806
fourier: Added \left/\right support in lwarp_mathjax.txt. . 833
fvextra: Added. 838
graphics: Fix path from kernel change. 856
libertinust1math: Added \left/\right support in lwarp_mathjax.txt. 909
lineno: Fix for internallinenumbers*. 914
lwarp-common-mathjax-newpxtxmath: Added \left/\right support in lwarp_mathjax.txt. 1304, 1308
minted: Added. 977
unicode-math: Adeed MathJax support for \left/\right. 1221
File: lwarp_mathjax.txt: Added \left/\right delimiters. 318
fcolorminipage: xcolor: Fixed second optional arg. 1244
v0.893
\LWR@checkloadfilename: Allowed picinpar. 247
\LWR@expandableformatted: Improved error handling. 259
\LWR@expandableformattedenv: Improved error handling. 260
\LWR@formatted: Improved error handling. 259
\LWR@formatted@checkendname: Added. 258
\LWR@formatted@checkname: Added. 258
\LWR@formattedenv: Improved error handling. 259
\LWR@htmlcomment: Disabled in math mode. 361
\LWR@subHTMLsanitize: Optionally neutralized single quotes. 391
General: 2020/11/26 1
MathJax: Added \mathnormal. . . 393
lwarp.css: Added keystroke. . . . 274
braket: Now uses MathJax extension. 700
caption3: Updated date to v2.2e. . 706
caption: Updated date to v3.5g. . . 705
epstopdf-base: Updated date to v2.11. 784
epstopdf: Updated date to v2.11. . 783
esvect: Added. 788
fixmath: Added. 812
graphics: Updated date to v1.4c. . . 847
graphicx: Updated date to v1.2b. . . 860
keystroke: Added. 899
lwarp-common-mathjax-letters: Added \varbeta. 1297
mathastext: Added. 943
mathspec: Added. 948
menukeys: Added. 970
menukeys: Updated to v1.6.1. . . . 970
picinpar: Added. 1052
plimsoll: Added. 1056
pstricks: Fixed pspicture*. 1060
repltext: Added. 1070
schemata: Added <alt> text. . . . 1076
selectp: Added. 1087

seqsplit: Added. 1088
simplebnf: Added. 1095
statistics: Added. 1138
struktex: Removed package date. . 1146
svg: Updated date to v2.02j. 1155
swfigure: Added. 1156
tikz: Fixed font macros. 1185
tocloft: Fix: \cftpagenumbersoff, \cftpagenumberson. 1205
Allowed picinpar. 209
v0.894
\LWR@forceSVGmessage: Improved MathJax warnings. 638
\LWR@mathjaxwarn: Improved MathJax warnings. 638
General: 2020/12/24 1
MathJax: Accept starred \hspace. 394
MathJax: Added \arabic, \number, \noalign. 393
lwarp.css: TeX logos no longer below baseline. 274
booktabs: MathJax: Absorb \cmidrule trim arg. 698
colortbl: Added MathJax emulation. 754
nicematrix: Added. 1012
rmathbr: Updated to v1.1. 1072
v0.895
\LWR@addlinktitle: Improved HTML quotes. 513
\LWR@checkloadfilename: kpfonts load before lwarp. 248
Allowed epsf. 247
\LWR@domulticolumn: Improved HTML quotes. 488, 489
\LWR@floatbegin: Improved HTML quotes. 521
\LWR@forceSVGmessage: Improved MathJax warning. 638
\LWR@forcenewautoidanchor: Improved HTML quotes. 523
\LWR@hook@processingtags: Added. 356
\LWR@label@subcreatetag: Improved HTML quotes. 510
\LWR@mathjaxwarn: Added MathJax warnings for aligned-overset, autoaligne, boldtensors, liberitinust1math, tensind. 638
Improved MathJax warning for unicode-math. 638
\LWR@maybenewtablerow: Improved HTML quotes. 471
\LWR@printatbang: Improved HTML quotes. 472
\LWR@printopenlist: Improved HTML quotes. 438
\LWR@startref: Improved HTML quotes. 513, 514
\LWR@subaddtabularcellcolor: Improved HTML quotes. 483
\LWR@subhyperref: Improved HTML quotes. 517
\LWR@subhyperrefclass: Improved HTML quotes. 517
\LWR@subinlineimage: Improved HTML quotes. 518
\LWR@tabledatasinglecolumntag: Improved HTML quotes. 474
\LWR@tdaddstyle: Improved HTML quotes. 477
\LWR@tdendstyles: Improved HTML quotes. 478
\hspace: Improved HTML quotes. . . . 623
\rotatebox: Improved HTML quotes. 858
\rule: Improved HTML quotes. . 626, 627
\scalebox: Improved HTML quotes. . 859
\verb: Improved HTML quotes. . . . 433
General: 2021/02/18 1
acro: Updated to v3.5. 646
amscdx: Added. 656
amsmath: Added \Hat, etc.. . . . 660
changes: Updated to v4.0.1. 712
epsfig: Supports lateximage. . . . 783
epsf: Added. 782
fancyhdr: Updated to v4.0. 798
impnattypo: Added. 884
isomath: Added. 887
isotope: Added. 887
libertinust1math: MathJax: Fixed for Greek, ignoring sans. 909
lpic: Added. 928
luavlna: Added. 935
mattens: Added. 956
mdwmath: Added. 967
pinlabel: Added. 1054
rlepsf: Added. 1071
rotating: Supports lateximage. . . 1073
siunitx, MathJax: Scientific notation. 1112
siunitx, MathJax: \num sci notation, multiples, +-, decimals, comma. . 1113
siunitx: Fix: MathJax for \ang. . . 1112
siunitx: MathJax: \SI prefix parsing. 1115
skmath: Added. 1120
tensor: Added MathJax. 1168
tikz-imagelabels: Added. 1186
xevlna: Added. 1248
Allow \par. 991
Allowed epsf. 209

File: lwarp_mathjax.txt: Added \ifblank, \ifstrequal macros. . 318
Fixed libertinus-otf \textquotedbl kern. 264
Improved HTML quotes. 262, 356, 655, 803, 853, 854, 862, 872, 873, 920, 961, 990, 1023
Use kpfonts-otf if LuaLaTeX, XeLaTeX. 225
lateximage: Improved HTML quotes. 583
minipage: Improved HTML quotes. . . 602
enumerate: Improved HTML quotes. . 442
itemize: Improved HTML quotes. . . . 441
v0.896
\@begintheorem: Intersperse footnotes. 436
\@currentHref: backref: Improved back refs. 516
\@endtheorem: Intersperse footnotes. 437
\LWR@@footnotetext: Fix: autopage references in footnotes. 378
\LWR@@printpendingfootnotes: Added ARIA role. 381
Fix: Backref to footnote. 381
\LWR@LwarpEnd: Added <main>. . . . 419
Fix: Footnotes at end of document. 418
\LWR@LwarpStart: Added <main>. . . 417
\LWR@currentautosecpageref: Added. 510
\LWR@doequation: Added ARIA role. . 570
\LWR@doubledollar: Added ARIA role. 562
Fix: Displaymath notes with MathJax. 562
\LWR@firstoffive: Changed to firstoffive instead of four. 227
\LWR@htmldivclass: Added ARIA role. 362
\LWR@htmlelementclass: Added ARIA role. 362
\LWR@htmlspanclass: Added ARIA role. 360
\LWR@lateximage@oneimage: Added ARIA role. 581
\LWR@lateximage@oneimageb: Added ARIA role. 580
\LWR@new@label: Revert to a simple \newcommand*. 512
\LWR@newautopagelabel: Fix: Refs if page changed. 384
\LWR@newhtmlfile: Added <main>. 396, 399
\LWR@null@newautopagelabel: Fix: Refs in footnotes. 385
\LWR@nullfonts: Added ARIA role. . 550
Added groups. 550
\LWR@popclose: Stack 19 deep. . . . 343
\LWR@printpendingmpfootnotes: Added ARIA role. 382
\LWR@pushclose: Error if stack overflow. 343
Stack 19 deep. 342
\LWR@refwithsection: Added. . . . 515
\LWR@subhtmlelementclass: Added ARIA role. 362
\LWR@subinlineimage: Added ARIA role. 518
\LWR@subsingledollarsvg: Added ARIA role. 558
\LWR@synconenotename: Fix: MathJax: Footnote names. 571
\LWR@write@lwarplabel: Added \LWR@currentautosecpage. 510
\LWRPrintStack: Stack 19 deep. . . . 353
\RequirePackage: Warn if package option has braces. 250
\marginpar: Added ARIA role. 382
\marginparBlock: Added ARIA role. . 382
\mbox: Added a group. 604
General: 2021/04/08 1
lwarp.css: Added <main>, adjusted <sidetoccontainer> margin. . . . 274 782
amsthm: Fix: Footnotes in opt arg.. 663
amsthm: Improved back refs. 663, 665
amsthm: Intersperse footnotes. 663–666
backref: Improved backrefs. 682
biblatex: Fix: Back references. . . . 689
biblatex: Fix: Citation references. . 689
biblatex: Improved refs: \ref to \LWR@refwithsection. 689
bigdelim: Updated to v2.8. 692
ccicons: Added. 709
chemfig: Updated to v1.6a. 718
citeref: Improved refs: \ref to \LWR@refwithsection. 745
classicthesis: Added. 746
cleveref: Undo memoir changes. . 749
cleveref: Undo subfig changes. . . 750
enotez: Added. 778
floatflt: Added ARIA role. 817
hyperref: Fix: Added *autorefname macros. 875
hyperref: Fix: No \hyperlink in HTML comment. 874
hyperxmp: Added keys. 877
keyfloat: Added ARIA role. 898
listings: Escapes accepted but disabled. 918
listings: Fix: Labels. 919
lwarp-patch-memoir: Added ARIA role. 1280

natbib: Fix: Citation references.. . 998
ntheorem: Intersperse footnotes. 1020, 1021, 1028
orcidlink: Added. 1031
parnotes: Added ARIA role. 1038
pdflscape: Fix: Added landscape. 1043
picinpar: Added ARIA role. 1052
scrlayer-scrpage: Added \automark, \manualmark. 1083
scrlayer-scrpage: Added \headmeark, \pagemark. 1083
theorem: Intersperse footnotes. 1178, 1179
threeparttablex: Fix: \TPTL@tnotex if not referrable. 1183
tocloft: Fix: \cftpagenumbersoff, \cftpagenumberson with memoir. 1205
wrapfig: Added ARIA role. 1235
Docs: Theorem references. 157
Fix: autopage references in footnotes. 794, 802
Stack 19 deep. 341
lateximage: Added ARIA role. . . 581, 586
center: Spurrious space in a . 587
description: Fix: Footnotes inside description label. 442
minipage: Improved back refs. . . . 603
BlockClass: Added ARIA role. 364
flushleft: Spurrious space in a 587
flushright: Spurrious space in a 587
LWR@BlockClassWP: Added ARIA role. 365
LWR@displaymathother: Added ARIA role. 565
LWR@equationother: Added ARIA role. 565
LWR@nestspan: Issue BlockClassWP warning inside a span. 359
v0.897
\LWR@afterloadnever: Refactored. . 208
\LWR@checkloadfilename: Refactored. 247
\LWR@checkloadnever: Refactored. . 211
\LWR@checkloadnevers: Refactored. 209
\LWR@earlyclassloadnever: Replacements now optional. . . . 208
\LWR@earlyloadnever: Refactored. . 208
\LWR@listof: Improved compatibility with newfloat, keyfloat. 532
\LWR@loadnever: Replacements now optional. 207
\RequirePackage: Fixed warning. . . 250
General: 2021/05/24 1
centerlastline: Added. 710
decorule: Added. 760
fancypar: Added. 799
fixme: Modified \AtBeginDocument. 813
float: Improved compatibility with newfloat, keyfloat. 816
froufrou: Added. 836
pbalance: Added. 1039
siunitx-v2: Do not use math mode. 1107
siunitx-v2: Regular group instead of color group. 1107
siunitx-v2: Rollback for v2. 1106
siunitx: Rollback for v2. . . . 591, 1105
v0.898
\LWR@atbeginverbatim: Reduced underfull \hbox warnings. 434
\LWR@beginhideamsmath: Reduced underfull \hbox warnings. 574
\LWR@hidelatexequation: Reduced underfull \hbox warnings. 568
General: 2021/05/29 1
listings: Reduced underfull \hbox warnings. 919
wrapfig: Improved integration with keyfloat. 1235
Reduced underfull \hbox warnings. 855
lateximage: Reduced underfull \hbox warnings. 582
LWR@figcaption: Reduced underfull \hbox warnings. 526
v0.899
\LWR@LwarpStart: Warn if lwarp package not detected. 416
General: 2021/06/29 1
lwarp.css: Improved multicol. . . 274
graphics: Supports keepaspectratio. 849, 856
keyfloat: Fix: lw w/ h. 895
lwarpmk: Warn if lwarp package not detected. 322

Index of Objects

This is an index of macros, environments, booleans, counters, lengths, packages, classes, options, keys, files, and various other programming objects. Each is listed by itself, and also by category. In some cases, they are further subdivided by [class].

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition.

Symbols

\$ *553*
\& *347*, 8701
\(. 11736
*-images.txt (file) *581*
*_html.aux (file) *383*, *507*, *509*, *581*
*_html.lof (file) *525*
*_html.lot (file) *525*
*_html.tex (file) *268*
\, ... *124*
--shell-escape (option) *103*
\@@@setcpageref 39
\@@@setcref 2
\@@@setcrefrange 17
\@author *421*
\@begintheorem 8293
\@biblabel 11182
\@caption 10607
\@captype 10584
\@chapcntformat 7383
\@currentHref 10383
\@currentlabelname 10183
\@date *421*
\@donoparitem 8325
\@endtheorem 8308
\@ensuredmath 11746
\@fnsymbol 8030
\@footnotetext 6743
\@include 1624
\@item 8338
\@makecaption 10607
\@makefnmark 6705
\@makefntext 6704
\@maketitle 57, 8062
\@mklab 8319
\@mpfootnotetext 6745
\@nbitem 8405
\@opargbegintheorem 8300
\@partcntformat 7384
\@partnameformat 7385
\@rowc@lors 9073
\@rowcolors 9072
\@seccntformat 7381
\@starttoc 10748
\@textsubscript 13183
\@textsuperscript 13179
\@title *421*
\@wrglossary 11001
\@wrindex 10973
\@xdlbfloat 10528
\@xfloat 10528
\[. 11736
\\ *621*
$ *562*
$$ *562*
2in1 (package) *640*
2up (package) *640*

A

a4 (package) *640*
a4wide (package) *641*
a5comb (package) *641*
abstract (environment) 8129
abstract (package) *135*, *641*
\abstractname *114*, 8128
academicons (package) *643*
accents (package) *644*
accessibility (package) *645*
accsupp (package) *645*
acro (package) *646*
acronym (package) *648*
\addcontentsline 10696
addlines (package) *650*
\AddSubtitlePublished 8092
adjmulticol (package) *649*
Adobe (program) *76*
\affiliation 7928
afterpage (package) *651*
algorithm2e (package) *651*
algorithmicx (package) *170*, *655*
align (environment) 85
align* (environment) 88
alignat (environment) 97
alignat* (environment) 100
alltt (package) *656*
\AltTextClose *116*, 11398

\AltTextOpen 116, 11397
\AmS 13541
amscdx (package) 656
amsmath (package) 657
amsthm (package) 661
\and 421
anonchap (package) 666
anysize (package) 667
appendix (package) 136, 667
ar (package) 667
arabicfront (package) 669
array (package) 669
\arrayrulecolor 9080
\arrayrulecolornexttoken 9080
arydshln (package) 670
AsciiDoc (program) 76
AsciiDoctor (program) 76
Asciidoctor-LaTeX (program) 76
asymptote (package) 164, 672
atbegshi (package) 673
attachfile (package) 673
attachfile2 (package) 674
\attrib 174, 431, 1226
\attribution 8139
authblk (package) 135, 676
\author 121, 421
autobreak (package) 677
autonum (package) 678
autosec 401
awesomebox (package) 679
axessibility (package) 680
axodraw2 (package) 681

B

babel (package) 175
\backmatter 7359
backnaur (package) 681
backref (package) 682
balance (package) 682
\BaseJobname 5901
BaseJobname (option) 110, 233
bbding (package) 683
\bfseries 13083
biblatex (package) 687
\bibliography 11182
\BibTeX 13534
bibunits (package) 692
bigdelim (package) 170, 692
bigfoot (package) 693
bigstrut (package) 694
bitpattern (package) 694
BlockClass (environment) 119, 6386
\BlockClassSingle 6399
blowup (package) 695
bm (package) 695
booklet (package) 696
bookmark (package) 696
booktabs (package) 696
boolean:
CombineHigherDepths 113, 385
FileSectionNames 113, 348
FixSmallCaps 113, 124, 610
FormatEPUB 182, 260
FormatWP 184, 261
HTMLDebugComments 114, 255
LWR@allowanothergeometry 242
LWR@amsmultline 573
LWR@copiedsidetoc 530
LWR@doingapar 367
LWR@doingcmidrule 449
LWR@doingstartpars 367
LWR@doingtbrule 449
LWR@dynamicmath 346
LWR@emptyatbang 449
LWR@exitingtabular 449
LWR@forceminipagefullwidth 600
LWR@foundmrowcell 449
LWR@freezethisautoid 523
LWR@indisplaymathimage 552
LWR@insidemathcomment 552
LWR@intabularmetadata 449
LWR@isstartingequation 579
LWR@MathJax@silentquotes 390
LWR@mathmacro 345
LWR@minipagefullwidth 600
LWR@minipagethispar 601
LWR@opttablecol 450
LWR@origmathjax 232
LWR@setseqfilelabel 348
LWR@skipatbang 449
LWR@skippingmcolrowcell 449
LWR@skippingmrowcell 449
LWR@starredlongtable 452
LWR@startedrow 448
LWR@tableparcell 449
LWR@tabularcelladded 448
LWR@tabularmutemods 450
LWR@tracinglwarp 255
LWR@unknownmathsize 555
LWR@usedmultirow 449
LWR@validtablecol 450
LWR@verbtags 433
LWR@warnbaselinemarker 555
LWR@warnedcustomizemathjax 392
LWR@xfakebold 552
mathjax 232
usingOSWindows 231
warpingHTML 232
warpingprint 232
WPMarkFloats 185, 261
WPMarkLOFT 186, 261

WPMarkMath 186, 262
WPMarkMinipages 186, 261
WPMarkTOC 186, 261
WPTitleHeading 187, 262
bophook (package) 698
bounddvi (package) 699
boxedminipage (package) 699
boxedminipage2e (package) 699
\boxframe 197
braket (package) 700
breakurl (package) 700
breqn (package) 700
bsheaders (package) 702
bussproofs (package) 702
BVerbatim (environment) 257
bxpapersize (package) 703
bytefield (package) 703

C

calc (package) 244
cancel (package) 703
canoniclayout (package) 704
capt-of (package) 528
caption (package) 171, 528, 705
caption3 (package) 706
\caption@begin 10664
\caption@end 10664
\captionlistentry 10671
\captionof 10712
\CaptionSeparator 10606
cases (package) 709
ccicons (package) 709
center (environment) 12328
\centering 12358
centerlastline (package) 710
\centerline 12377
centernot (package) 710
changebar (package) 711
changelayout (package) 711
changepage (package) 712
changes (package) 712
chappg (package) 717
\chapter 7595
chapterbib (package) 718
chemfig (package) 718
chemformula (package) 720
chemgreek (package) 725
chemmacros (package) 726
chemnum (package) 743
chkfloat (package) 744
chngpage (package) 744
cite (package) 744
citeref (package) 745
CJK (package) 745
CJKutf8 (package) 746
class (key) [Gin] 851
class:
internet 75
komascript 172
memoir 172, 174, 1227
classicthesis (package) 746
\cleardoublepage 13363
\clearpage 13363
cleveref (package) 132, 747
clrdblpg (package) 750
cm-super (package) 103
cmap (package) 104
cmbright (package) 750
cmdtrack (package) 751
colonequals (package) 751
\color 53
color (package) 162, 752
\colorbox 80
\colorboxBlock 93, 12457
colortbl (package) 169, 752
CombineHigherDepths (boolean) . . 113, 385
comment (package) 239
\ConTeXt 13529
continue (package) 754
copyrightbox (package) 754
counter:
FileDepth 113, 385
FootnoteDepth 113, 377
footnoteReset 377
lofdepth 535
lotdepth 535
LWR@cellcolordepth 451
LWR@currentautosecfloatpage . . . 384
LWR@currentautosecpage 383
LWR@externalfilecnt 552
LWR@hdashedlines 448
LWR@hlines 448
LWR@htmlfilenumber 348
LWR@htmlseqfilenumber 348
LWR@lateximagedepth 578
LWR@lateximagenumber 578
LWR@LIpage 578
LWR@midrulecounter 452
LWR@nextautoid 525
LWR@nextautopage 525
LWR@nextequation 566
LWR@prevFileDepth 402
LWR@previousautopagelabel 384
LWR@spandepth 366
LWR@splitstarcopies 464
LWR@splitstarindex 464
LWR@starcount 463
LWR@startingequation 579
LWR@tablecolspecindex 451
LWR@tablecolspecwidth 451
LWR@tableLaTeXcolindex 451

LWR@tabletotalLaTeXcols 451
LWR@tabletotalLaTeXcolsnext . . . 451
LWR@tabularDepth 450
LWR@tabularpardepth 450
LWR@thisautoid 523
LWR@thisautoidWP 523
LWR@virtualpagedepth 600
SideTOCDepth 111, 532
tocdepth 111
\cpagerefFor 38
crop (package) 755
\CSSFilename 114, 117, 6647
ctable (package) 755
\CustomizeMathJax 7120, 7213
cuted (package) 758
cutwin (package) 758

D

\date 121
dblfloatfix (package) 759
dblfnote (package) 759
dcolumn (package) 759
decimal (package) 760
\DeclareGraphicsExtensions 2
decorule (package) 760
\defaddtocounter 930
dejavu (package) 103
description (environment) 8490
diagbox (package) 760
dingbat (package) 762
\displaymathnormal 157, 572, 11992
\displaymathother 157, 572, 12003
ditaa (package) 181
DotArrow (package) 763
\dotfill 13281
dotlessi (package) 763
\doublerulesepcolor 9082
\doublerulesepcolornexttoken 9082
dprogress (package) 764
draftcopy (package) 764
draftfigure (package) 764
draftwatermark (package) 765
drftcite (package) 765
dvipdfm (option) 106, 236
dvipdfmx (option) 106, 236
dvips (option) 106, 236

E

easy-todo (package) 766
ebook (package) 767
\ebweight 13088
econometrics (package) 767
ed (package) 770
ellipsis (package) 770
embrac (package) 771
\emph 12899
emptypage (package) 771
\end@dlbfloat 10553
\end@float 10553
\enddocument 7864
endfloat (package) 772
endheads (package) 772
endnotes (package) 136, 773
engtlc (package) 774
\enlargethispage 13362
enotez (package) 778
\enskip 622, 13307
enumerate (environment) 8463
enumerate (package) 780
enumitem (package) 781
environ (package) 246
environment:
BlockClass 119
fminipage 127
lateximage 577
picture 598
titlepage 121
titlingpage 121
warpall 120
warpHTML 116, 119
warpMathJax 120
warpprint 116, 120
environments:
abstract 8129
align 85
align* 88
alignat 97
alignat* 100
BlockClass 6386
BVerbatim 257
center 12328
description 8490
enumerate 8463
eqnarray 12040
equation 11970
equation* 11978
fcolorminipage 173, 12497
flalign 91
flalign* 94
flushleft 12348
flushright 12338
fminipage 12825
gather 79
gather* 82
itemize 8455
lateximage 12183, 12323
list 8425
longtable 4
LWR@BlockClassWP 6429
LWR@blocktextcurrentfont 13069, 13210
LWR@displaymathnormal 11786

LWR@displaymathother 11789
LWR@equationother 11802
LWR@figcaption 10634
LWR@glrbox 984
LWR@nestspan 6212
LWR@setvirtualpage 12578
LWRcreatelwarpmk 1286
math 11785
minipage 12604
multline 72
multline* 75
picture 12569
quotation 8166
quote 8158
tabbing 8271
tabular 10027
thebibliography 11183
theindex 10924
titlepage 7945
titlingpage 14
verbatim 8253
verse 2, 8176
warpall 1270
warpHTML 1271
warpMathJax 1277
warpprint 1274
epigraph (package) *781*
epsf (package) *782*
epsfig (package) *783*
epstopdf (package) *162*, *783*
epstopdf (program) *160*, *592*
epstopdf-base (package) *783*
eqlist (package) *784*
eqnarray (environment) 12040
eqparbox (package) *785*
equation (environment) 11970
equation* (environment) 11978
errata (package) *786*
eso-pic (package) *787*
esvect (package) *788*
\etalchar *136*
etoc (package) *788*
etoolbox (package) *205*
eurosym (package) *791*
everyhook (package) *244*
everypage (package) *791*
everyshi (package) *791*
\expandcolspec 8958
expl3 (package) *244*
extarrows (package) *792*
extramarks (package) *792*

F

fancybox (package) *129*, *793*
fancyhdr (package) *798*
fancypar (package) *799*
fancyref (package) *800*
fancytabs (package) *800*
fancyvrb (package) *801*
\fbox *127*, 12794
fbox (package) *808*
\fboxBlock *127*, 12805
\fcolorbox 110, 12459
\fcolorboxBlock 133, 12495
fcolorminipage (environment) . . 173, 12497
fewerfloatpages (package) *810*
figcaps (package) *810*
figsize (package) *811*
file:
*-images.txt *581*
*_html.aux *383*, *507*, *509*, *581*
*_html.lof *525*
*_html.lot *525*
*_html.tex *268*
glyphtounicode.tex *104*
lwarp.css *118*, *274*
lwarp.ist *149*, *315*
lwarp.xdy *149*, *316*
lwarp_baseline_marker.eps *553*
lwarp_baseline_marker.png *553*
lwarp_formal.css *311*
lwarp_mathjax.txt *317*
lwarp_one_limage.cmd *317*
lwarp_sagebrush.css *306*
lwarp_tutorial.txt *85*
lwarpmk.conf *274*
lwarpmk.lua *192*
project.css *118*
project.lwarpmkconf *274*
sample_project.css *118*, *315*
tutorial.tex *85*
filecontents (package) *244*
FileDepth (counter) *113*, *385*
\FilenameLimit *113*, 6874
\FilenameNullify *131*, 11392, 13211
\FilenameSimplify *131*, 6895, 7214
FileSectionNames (boolean) *113*, *348*
fitbox (package) *811*
fix2col (package) *812*
fixmath (package) *812*
fixme (package) *176*, *812*
fixmetodonotes (package) *814*
FixSmallCaps (boolean) *113*, *124*, *610*
flafter (package) *814*
\flagverse *1227*
flalign (environment) 91
flalign* (environment) 94
Flare (program) *76*
flippdf (package) *815*
float (package) *170*, *815*
floatflt (package) *816*

floatpag (package) 818
floatrow (package) 171, 818
fltrace (package) 823
\flushbottom 6100
flushend (package) 823
flushleft (environment) 12348
flushright (environment) 12338
fminipage (environment) 127, 12825
fnbreak (package) 824
fncychap (package) 824
fnlineno (package) 825
fnpara (package) 825
fnpos (package) 825
fontawesome (package) 825
fontawesome5 (package) 827
fontaxes (package) 827
fontenc (package) 104, 828
fontspec (package) 103, 240
footmisc (package) 828
footnote (package) 829
footnotebackref (package) 830
FootnoteDepth (counter) 113, 377
footnotehyper (package) 830
footnoterange (package) 830
footnoteReset (counter) 377
footnpag (package) 831
\ForceHTMLPage 135, 7334
\ForceHTMLTOC 135, 7340
foreign (package) 831
forest (package) 831
FormatEPUB (boolean) 182, 260
FormatWP (boolean) 184, 261
fouridx (package) 832
fourier (package) 832
\framebox 12771
framed (package) 834
FrameMaker (program) 76
\frontmatter 7356
froufrou (package) 836
ftcap (package) 837
ftnright (package) 837
fullminipage (package) 837
fullpage (package) 837
fullwidth (package) 838
\fup 13186
\fussy 6102
fvextra (package) 838
fwlw (package) 841

G

gather (environment) 79
gather* (environment) 82
GELLMU (program) 75
gensymb (package) 841
gentombow (package) 842
geometry (package) 241, 842
gettitlestring (package) 244
ghsystem (package) 843
[Gin]:
    class (key) 851
gindex (package) 140, 843
GladTeX (program) 75
gloss (package) 137, 844
glossaries (package) 137, 845
GlossaryCmd (option) 110, 137, 235, 845
glyphtounicode.tex (file) 104
gmeometric (package) 847
graphics (package) 159, 847
graphicx (package) 159, 860
grffile (package) 162, 860
grid (package) 860
grid-system (package) 861
gridset (package) 861

H

hang (package) 862
hanging (package) 863
hepunits (package) 864
Hevea (program) 75
\hfill 13260
hhline (package) 865
hhtensor (package) 866
\HomeHTMLFilename 5903
HomeHTMLFilename (option) 106, 234
\hrule 125
\hrulefill 125, 13262
\hskip 124
\hspace 124, 622, 13315, 13346, 13352
htlatex (program) 75
\HTMLAuthor 115, 122, 6684
HTMLDebugComments (boolean) 114, 255
\HTMLDescription 115, 122, 6689
\HTMLEntity 5885
\HTMLFilename 5902
HTMLFilename (option) 106, 234
\HTMLFirstPageBottom 111, 6635
\HTMLFirstPageTop 111, 6632
htmlglossary (option) [lwarpmk] . . 137, 845
HTMLIndexCmd (option) 109, 235
\HTMLLanguage 114, 7628
HTMLLatexCmd (option) 108, 178, 235
\HTMLleftmargini (length) . . . 174, 432, 1227
\HTMLPageBottom 115, 422, 6641
\HTMLPageTop 115, 6638
\HTMLTitle 114, 122, 6679
\HTMLTitleAfterSection 114, 7651
\HTMLTitleBeforeSection 114, 7646
\HTMLunicode 5893
\HTMLvleftskip (length) 174, 432, 1227
hypbmsec (package) 866
hypcap (package) 867
hypdestopt (package) 867

\hyperindexformat 11171
\hyperindexref 11129
hypernat (package) 867
\hyperpage 11169
hyperref (package) 132, 516, 867
\hypertoc 10857
\hypertocfloat 10880
hyperxmp (package) 877
hyphenat (package) 878

I

idxlayout (package) 879
\if@titlepage 7923
\ifnextchar 155
ifoddpage (package) 880
ifplatform (package) 205
\ifstar 155
\IgnoreMinipageWidths 127, 599, 12594
\ImageAltText 115, 11399
ImagesDirectory (option) 106, 233
ImagesName (option) 106, 233
imakeidx (package) 880
imakeidx (program) 142
impnattypo (package) 884
\includegraphics 324
indentfirst (package) 372
InDesign (program) 76
index (package) 885
index (program) 140
\IndexPageSeparator 114, 10922
\IndexRangeSeparator 114, 10922
IndexRef (option) 109, 235
\InlineClass 119, 6409
\inlinemathnormal 156, 5878
\inlinemathother 156, 5874
inputenc (package) 104
inputenx (package) 104
inputtrc (package) 886
internet (class) 75
intopdf (package) 886
isomath (package) 887
isotope (package) 887
itemize (environment) 8455
\itshape 13118

J

jurabib (package) 889

K

karnaugh-map (package) 890
\kern 124
key:
  [Gin]:
    class 851
keyfloat (package) 172, 893
keystroke (package) 899
komascript (class) 172
kotex (package) 177
kpfonts (package) 900
kpfonts-otf (package) 902
kvoptions (package) 232

L

\l@book 10900
\l@chapter 10902
\l@figure 10913
\l@paragraph 10911
\l@part 10901
\l@section 10908
\l@subparagraph 10912
\l@subsection 10909
\l@subsubsection 10910
\l@table 10914
\LaTeX 13483
LaTeX2HTML (program) 75
\LaTeXe 13483
lateximage (environment) . 577, 12183, 12323
\LateximageFontScale 12113
\LateximageFontSizeName 12112
latexmk (option) 106, 236
latexmk (program) 179
LatexmkIndexCmd (option) 109, 235
LaTeXML (program) 75
layaureo (package) 903
layout (package) 903
layouts (package) 903
leading (package) 906
leftidx (package) 906
\leftline 12376
length:
  \HTMLleftmargini 174, 432, 1227
  \HTMLvleftskip 174, 432, 1227
  \LWR@cmidrulewidth 475
  \LWR@heavyrulewidth 475
  \LWR@lightrulewidth 475
  \LWR@minipageheight 599
  \LWR@minipagewidth 599
  \LWR@tempheight 623
  \LWR@tempraise 623
  \LWR@tempwidth 623
  \LWR@thiscmidrulewidth 475
  \VerbatimHTMLWidth 433
  \vleftmargini 174, 432, 1226
  \vleftskip 174, 432, 1226, 1227
letltxmacro (package) 205
letterspace (package) 907
lettrine (package) 907
\lgweight 13093
libertinust1math (package) 908
LibreOffice (program) 76
\linebreak 13356
lineno (package) 914

\LinkHome 115, 5972, 5977
\linkhomename 111, 5969
\LinkNext 115, 6005, 6018
\linknextname 111, 6001
\LinkPrevious 115, 6004, 6008
\linkpreviousname 111, 6000
Linux (program) 119, 229
lips (package) 917
list (environment) 8425
listings (package) 917
listliketab (package) 923
\listoffigures 10778
\listoftables 10791
lltjext (package) 924
lmodern (package) 103, 104
lofdepth (counter) 535
longtable (environment) 4
longtable (package) 168, 925
lotdepth (counter) 535
lpic (package) 928
lscape (package) 928
ltablex (package) 928
ltcaption (package) 929
ltxgrid (package) 929
ltxtable (package) 929
lua-check-hyphen (package) 930
lua-visual-debug (package) 930
luacolor (package) 930
\LuaLaTeX 13512
LuaLaTeX (program) [requirement] 79
luamplib (package) 931
\LuaTeX 13512
luatexko (package) 931
luatodonotes (package) 176, 933
luavlna (package) 935
lwarp (package) 106
lwarp-common-mathjax-letters (package) 1297
lwarp-common-mathjax-newpxtxmath (package) 1304
lwarp-common-mathjax-nonunicode (package) 1310
lwarp-common-mathjax-overlaysymbols (package) 1312
lwarp-common-multimedia (package) . . 1292
lwarp-patch-komascript (package) . . . 1261
lwarp-patch-memoir (package) 1263
lwarp.css (file) 118, 274
lwarp.ist (file) 149, 315
lwarp.xdy (file) 149, 316
lwarp_baseline_marker.eps (file) 553
lwarp_baseline_marker.png (file) 553
lwarp_formal.css (file) 311
lwarp_mathjax.txt (file) 317
lwarp_one_limage.cmd (file) 317
lwarp_sagebrush.css (file) 306
lwarp_tutorial.txt (file) 85
[lwarpmk]:
htmlglossary (option) 137, 845
printglossary (option) 137, 845
lwarpmk (option) 110, 234, 321
lwarpmk (program) 192, 321
lwarpmk epstopdf (program) 160, 592
lwarpmk pdftosvg (program) 160, 592
lwarpmk.conf (file) 274
lwarpmk.lua (file) 192
\lwarpsetup 1058
\LWR@@footnotetext 6708
\LWR@@makebox@align 12727
\LWR@@makebox@paren 12712
\LWR@@printpendingfootnotes 6779
\LWR@absorbstar 1011
\LWR@addbaselinemarker 11434
\LWR@addcdashline 9348
\LWR@addcmidruletrim 9314
\LWR@addcmidrulewidth 9345
\LWR@addcompilecmd 2042
\LWR@addformatwpalignment 9364
\LWR@addleftmostbartag 9152
\LWR@addlinktitle 10301
\LWR@addmathjax 11882
\LWR@addmulticolvertrulecolor 9618
\LWR@addrulewidth 9319
\LWR@addtabularcellcolor 9493
\LWR@addtabularhrulecolor 9392
\LWR@addtabularrowcolor 9377
\LWR@addtabularrulecolors 9438
\LWR@afterendverbatim 8237
\LWR@afterloadnever 93
LWR@allowanothergeometry (boolean) . 242
\LWR@amsmathbody 12146
\LWR@amsmathbodynumbered 12152
LWR@amsmultline (boolean) 573
\LWR@applyxfakebold 11416
\LWR@atbeginverbatim 8216
\LWR@avoiddupfilenames 6906
\LWR@backgroundcolor 41
\LWR@beginhideamsmath 12022
LWR@BlockClassWP (environment) 6429
LWR@blocktextcurrentfont (environment) 13069, 13210
\LWR@botnavigation 5995
LWR@cdashlines 475
LWR@cellcolordepth (counter) 451
\LWR@cellHTMLcolor 9077
\LWR@checkloadbefore 67
\LWR@checkloadfilename 1452
\LWR@checkloadnever 232, 1451
\LWR@checkloadnevers 124
\LWR@clearmidrules 9233

\LWR@closeparagraph 6532
\LWR@closeparagraph@br 6522
\LWR@closeprevious 6063
\LWR@closetabledatacell 8654
\LWR@cmidrulewidth (length) *475*
LWR@colafterspec *451*
LWR@colatspec *451*
LWR@colbangspec *451*
LWR@colbarspec *451*
LWR@colbeforespec *451*
\LWR@columnHTMLcolor 9075
\LWR@columnspeclookahead 8785
\LWR@compilecmd 2039
\LWR@compileuplatex 2074
\LWR@convertto 925
LWR@copiedsidetoc (boolean) *530*
\LWR@copyfile 1659
\LWR@createautosec 7365
\LWR@createfooter 7217
LWR@currentautosecfloatpage (counter) *384*
LWR@currentautosecpage (counter) . . . *383*
\LWR@currentautosecpageref 10202
\LWR@currentcss 6646
\LWR@currenttextcolor 13197
\LWR@customizedMathJax 7105
\LWR@customizeMathJax 7194
\LWR@descitem 8471
\LWR@disablepinyin 951
LWR@displaymathnormal (environment) 11786
LWR@displaymathother (environment) 11789
\LWR@docdashline 9282
\LWR@docmidrule 9266
\LWR@doequation 11900
\LWR@doindexentry 11110
\LWR@doindexentrysub 11108
\LWR@doindexentrysubsub 11097
LWR@doingapar (boolean) *367*
LWR@doingcmidrule (boolean) *449*
LWR@doingstartpars (boolean) *367*
LWR@doingtbrule (boolean) *449*
\LWR@domulticolumn 9656
\LWR@doubledollar 11677
LWR@dynamicmath (boolean) *346*
\LWR@earlyclassloadnever 103
\LWR@earlyloadnever 98
LWR@emptyatbang (boolean) *449*
\LWR@endfloatalignment 10600
\LWR@endhideamsmath 12032
\LWR@endofline 13288
\LWR@ensuredoingapar 6498
LWR@equationother (environment) . . . 11802
\LWR@equationtag 12132
\LWR@excludecomment 1230
LWR@exitingtabular (boolean) *449*
\LWR@expandableformatted 1740
\LWR@expandableformattedenv 1772
\LWR@expcolspec 8954
LWR@externalfilecnt (counter) *552*
\LWR@fboxstyle 12787
\LWR@fifthoffive 956
LWR@figcaption (environment) 10634
\LWR@filenamenoblanks 6919
\LWR@filestart 7660
\LWR@findcurrenttextcolor 13200
\LWR@findword 1448
\LWR@firstoffive 956
\LWR@floatalignment 10586
\LWR@floatalignmentname 10585
\LWR@floatbegin 10491
\LWR@floatend 10538
\LWR@floatstyle 2
\LWR@footnotebox 6703
\LWR@footnotetext 6742
\LWR@forceemptyline 952
LWR@forceminipagefullwidth (boolean) *600*
\LWR@forceminwidth 12776
\LWR@forcenewautoidanchor 10561
\LWR@forcenewpage 6083
\LWR@forceSVGmessage 13768
\LWR@formatted 1724
\LWR@formatted@checkendname 1715
\LWR@formatted@checkname 1706
\LWR@formattedenv 1756
\LWR@formatting 1705
LWR@foundmrowcell (boolean) *449*
\LWR@fourthoffive 956
LWR@freezethisautoid (boolean) *523*
\LWR@futurenonspacelet 8580
\LWR@FVstyle 56
\LWR@getexparray 5847
\LWR@getmynexttoken 8590
LWR@glrbox (environment) 984
\LWR@gsavebox 970
LWR@hdashedlines (counter) *448*
LWR@heavyrulewidth (length) *475*
\LWR@hidelatexequation 11865
LWR@hlines (counter) *448*
\LWR@hook@processingtags 6126
\LWR@href 10427
\LWR@HTML@caption@begin 10644
\LWR@HTML@caption@end 10655
\LWR@HTML@ref 10344
\LWR@htmlblockcomment 6317
\LWR@htmlblocktag 6319
\LWR@HTMLcline 10008
\LWR@htmlclosecomment 6284
\LWR@htmlcomment 6305
\LWR@htmldivclass 6360
\LWR@htmldivclassend 6365
\LWR@htmlelement 6376

\LWR@htmlelementclass 6344
\LWR@htmlelementclassend 6352
\LWR@htmlelementclassline 6368
\LWR@htmlelementend 6379
LWR@htmlfilenumber (counter) *348*
\LWR@htmlfileref 10205
\LWR@HTMLhline 9989
\LWR@HTMLLatexCmd 2084
\LWR@htmlmulticolumn 9722
\LWR@htmlopencomment 6284
\LWR@htmlrefsectionfilename 5959
\LWR@HTMLsanitize 7075
\LWR@HTMLsanitizeexpand 7083
\LWR@htmlsectionfilename 5919
LWR@htmlseqfilenumber (counter) *348*
\LWR@htmlspan 6259
\LWR@htmlspanclass 6267
\LWR@htmltag 6279
\LWR@htmltagc 6186
\LWR@hyperindexref@@comma 11140
\LWR@hyperindexref@comma 11133
\LWR@hyperindexref@range 11145
\LWR@hyperindexrefnullified 11114
\LWR@hyperindexrefsub 11148
\LWR@hyperindexrefsubtwo 11155
\LWR@includecomment 1230
\LWR@indentHTML 6180
\LWR@indentHTMLtwo 6183
\LWR@indexitem 10939
\LWR@indexnameref 11068
\LWR@indexnameref@anonref 11009
\LWR@indexnameref@cref 11035
\LWR@indexnameref@crefnameref . . . 11052
\LWR@indexnameref@ref 11014
\LWR@indexnameref@refnameref 11023
\LWR@indexsubitem 10943
\LWR@indexsubsubitem 10947
LWR@indisplaymathimage (boolean) . . . *552*
\LWR@infoprocessingmathjax 7140
LWR@insidemathcomment (boolean) *552*
\LWR@instertatbangcols 8646
LWR@intabularmetadata (boolean) *449*
\LWR@isolate 942
LWR@isstartingequation (boolean) . . . *579*
\LWR@itemizeitem 8448
\LWR@label@createtag 10252
\LWR@label@inmathcomment 10238
\LWR@label@subcreatetag 10234
\LWR@lateximage@oneimage 12168
\LWR@lateximage@oneimageb 12159
LWR@lateximagedepth (counter) *578*
\LWR@lateximagedepthref 10208
LWR@lateximagenumber (counter) *578*
\LWR@lateximagenumberref 10211
\LWR@lateximagesfile 1621
\LWR@latexmkcmd 2060
\LWR@latexmkdvipdfm 2065
\LWR@latexmkvar 2054
\LWR@LetLtxMacrocs 1007
\LWR@lightrulewidth (length) *475*
\LWR@linkcatcodes 10386
\LWR@linkmediacatcodes 10394
LWR@LIpage (counter) *578*
\LWR@listitem 8410
\LWR@listof 10804
\LWR@loadafter 20
\LWR@loadbefore 55
\LWR@loadnever 72
\LWR@longtabledatacaptiontag 9731
\LWR@lookforpackagename 1474
\LWR@lwarpconfversion 2033
\LWR@LwarpEnd 7844, 13560
\LWR@LwarpStart 7758, 13560
\LWR@maketitlesetup 34, 8020
LWR@MathJax@silentquotes (boolean) . . *390*
\LWR@mathjaxfilename 6657
\LWR@mathjaxwarn 13725
LWR@mathmacro (boolean) *345*
\LWR@maybe@orignewpage 963
\LWR@maybenewtablerow 9084
\LWR@maybeprintpendingfootnotes . . 6799
\LWR@maybetocdata 10856
LWR@midrulecounter (counter) *452*
LWR@midrules *475*
LWR@minipagefullwidth (boolean) *600*
\LWR@minipageheight (length) *599*
\LWR@minipagestartpars 13295
\LWR@minipagestoppars 13298
LWR@minipagethispar (boolean) *601*
\LWR@minipagewidth (length) *599*
\LWR@multicolother 9558
\LWR@multicolpartext 9552
\LWR@multicolskip 9564
\LWR@multirowborder 3
\LWR@mynexttoken 8579
\LWR@myshorttoc 10724
\LWR@nameref 10199
LWR@nestspan (environment) 6212
\LWR@new@label 10281
\LWR@newautoidanchor 10579
\LWR@newautopagelabel 6857
\LWR@newhtmlfile 7236
LWR@nextautoid (counter) *525*
LWR@nextautopage (counter) *525*
LWR@nextequation (counter) *566*
\LWR@nolinkurl 10439
\LWR@notltjloadafter 42
\LWR@notmemoirloadafter 39
\LWR@null@newautopagelabel 6868
\LWR@nullfonts 11259

\LWR@nullifycomment 1442
\LWR@nullifyNoAutoSpacing 10014
\LWR@nulllistfills 8417
\LWR@openparagraph 6504
LWR@opttablecol (boolean) *450*
\LWR@orig@setBold 11414
\LWR@orig@unsetBold 11415
\LWR@origcolspec 8629
LWR@origmathjax (boolean) *232*
\LWR@overline 13192
\LWR@parseaftercolumn 8863
\LWR@parseatcolumn 8795
\LWR@parsebangcolumn 8825
\LWR@parsebarcolumn 8875
\LWR@parsebeforecolumn 8851
\LWR@parsecoloncolumn 8900
\LWR@parseDcolumn 8949
\LWR@parsedrequirepackagenames . . . 1441
\LWR@parsenormalcolumn 8925
\LWR@parsepcolumn 8937
\LWR@parsesemicoloncolumn 8921
\LWR@parsestarcolumn 8946
\LWR@parsetablecols 8986
\LWR@parsewcolumn 8941
\LWR@patcherror 933
\LWR@patchlists 8527
\LWR@pdfencoding 836
\LWR@phantomsection 13422
\LWR@popclose 5797
\LWR@PreloadedPackage 12381
LWR@prevFileDepth (counter) *402*
LWR@previousautopagelabel (counter) . *384*
\LWR@printatbang 9127
\LWR@printbartag 9117
\LWR@printchaptername 7386
\LWR@printcloselist 8315
\LWR@PrintLatexCmd 2084
\LWR@printlength 1422
\LWR@printmccoldata 9567
\LWR@printmccoltype 9510
\LWR@printopenlist 8316
\LWR@printpendingfootnotes 6796
\LWR@printpendingmpfootnotes 6808
\LWR@printpercentlength 926
\LWR@printthetitle 7972
\LWR@providelength 922
\LWR@ProvidesPackageDrop 1611
\LWR@ProvidesPackageDropA 1596
\LWR@ProvidesPackageDropB 1605
\LWR@ProvidesPackagePass 1565
\LWR@pushclose 5749
\LWR@pushoneclose 7371
\LWR@quickfile 1618
\LWR@refwithsection 10353
\LWR@remembertag 12136
\LWR@replacestrings 7034
\LWR@requesttoc 7837
\LWR@requirepackagenames 1440
\LWR@restoreMathJaxformatting . . . 11207
\LWR@restoreorigaccents 1982
\LWR@restoreorigformatting 11208
\LWR@restoreoriglists 8555
\LWR@rowHTMLcolor 9076
\LWR@ruleHTMLcolor 9078
\LWR@sanitize 1132
\LWR@sanitized 1131
\LWR@secondoffive 956
\LWR@section 7389
\LWR@sectionumber 7362
\LWR@select@html@hspace 13315
\LWR@select@html@nohspace 13346
\LWR@select@print@hspace 13349
\LWR@setcurrentfont 11417
\LWR@setexparray 5838
\LWR@setlatestname 10185
\LWR@setOSWindows 1046
\LWR@setref 10193
LWR@setseqfilelabel (boolean) *348*
LWR@setvirtualpage (environment) . . 12578
\LWR@shellescapecmd 2034
\LWR@sidetoc 10830
\LWR@simplifycustom 6894
\LWR@simplifyname 6883
\LWR@singledollar 11714
\LWR@singledollarmeasure 11489
LWR@skipatbang (boolean) *449*
LWR@skippingmcolrowcell (boolean) . . *449*
LWR@skippingmrowcell (boolean) *449*
LWR@spandepth (counter) *366*
\LWR@spanwarnformat 6196
\LWR@spanwarninvalid 6204
\LWR@splitstarcontents 8957
LWR@splitstarcopies (counter) *464*
LWR@splitstarindex (counter) *464*
LWR@starcount (counter) *463*
LWR@starredlongtable (boolean) *452*
LWR@startedrow (boolean) *448*
LWR@startingequation (counter) *579*
\LWR@startingequationtag 12131
\LWR@startnewdepth 7375
\LWR@startpars 6574
\LWR@startref 10307
\LWR@stoppars 6595
\LWR@stripperiod 10184
\LWR@strresult 8627
\LWR@subaddcmidruletrim 9301
\LWR@subaddtabularcellcolor 9485
\LWR@subcdashline 9269
\LWR@subcmidrule 9251
\LWR@subcustomizedmathjax 7108

\LWR@subhtmlelementclass 6324
\LWR@subHTMLsanitize 7055
\LWR@subhyperref 10402
\LWR@subhyperrefclass 10416
\LWR@subhyperreftext 10411
\LWR@subinlineimage 10465
\LWR@subnewref 10338
\LWR@subsingledollar 11617
\LWR@subsingledollarsvg 11535
\LWR@subtableofcontents 10738
\LWR@subtabularhtmlcolumns 9802
\LWR@syncmathjax 11853
\LWR@syncnotenames 11963
\LWR@syncnotenumbers 11957
\LWR@synconenotename 11958
\LWR@synconenotenumber 11952
LWR@tablecolspec *450*
LWR@tablecolspecindex (counter) *451*
LWR@tablecolspecwidth (counter) *451*
\LWR@tabledatacolumntag 9891
\LWR@tabledatasinglecolumntag 9166
LWR@tableLaTeXcolindex (counter) . . . *451*
LWR@tableparcell (boolean) *449*
LWR@tabletotalLaTeXcols (counter) . . *451*
LWR@tabletotalLaTeXcolsnext (counter) *451*
\LWR@tabular@warpprintonly 10010
LWR@tabularcelladded (boolean) *448*
LWR@tabularDepth (counter) *450*
\LWR@tabularendofline 8764
\LWR@tabularfinishrow 8715
\LWR@tabularhtmlcolumns 9812
\LWR@tabularleftedge 9157
LWR@tabularmutemods (boolean) *450*
LWR@tabularpardepth (counter) *450*
\LWR@tdaddstyle 9288
\LWR@tdendstyles 9294
\LWR@tdstartstyles 9287
\LWR@tempcolor 13198
\LWR@tempcolortwo 13198
\LWR@tempheight (length) *623*
\LWR@tempraise (length) *623*
\LWR@tempwidth (length) *623*
\LWR@textcurrentcolor 24, 13203
\LWR@textcurrentfont 13047, 13209
\LWR@thirdoffive 956
\LWR@ThisAltText 11401
LWR@thisautoid (counter) *523*
LWR@thisautoidWP (counter) *523*
\LWR@thiscmidrulewidth (length) *475*
\LWR@thiscolspec 9165
\LWR@thisfilename 6877
\LWR@thisnewfilename 6882
\LWR@titlingmaketitle 84, 8084
\LWR@topnavigation 5992
\LWR@traceinfo 1687
LWR@tracinglwarp (boolean) *255*
LWR@trimlrules *475*
LWR@trimrrules *475*
\LWR@unknownengine 2046
LWR@unknownmathsize (boolean) *555*
\LWR@url 10452
LWR@usedmultirow (boolean) *449*
LWR@validtablecol (boolean) *450*
LWR@verbtags (boolean) *433*
LWR@virtualpagedepth (counter) *600*
\LWR@vspace 13353
LWR@warnbaselinemarker (boolean) . . . *555*
LWR@warnedcustomizemathjax (boolean) *392*
\LWR@WPcell 9360
\LWR@write@lwarplabel 10214
\LWR@writeconf 2186
\LWR@xcolorrowHTMLcolor 9074
LWR@xfakebold (boolean) *552*
\LWR@xindex@modifyentry 10951
LWRcreatelwarpmk (environment) 1286
\LWRopquote 1041
\LWRopseq 1042
\LWRPrintStack 6038
\LWRsetnextfloat 10630
\LWRtexttitlecase 1002
lyluatex (package) *935*
\LyX 13556

M

Mac OS (program) *119*, *229*
\macrotocsname 996
Madcap (program) *76*
magaz (package) *937*
\mainmatter 7352
make (program) *181*
\makebox 12736
makeidx (package) *151*, *152*, *938*, *1198*
\MakeIndex 13534
makeindex (option) *108*, *235*
makeindex (program) *139*, *149*
makeindexStyle (option) *108*, *149*, *233*
\makelabel *437*
\maketitle 48, *121*, 8043
manyfoot (package) *938*
marginal (package) *940*
marginfit (package) *940*
marginfix (package) *941*
marginnote (package) *941*
\marginpar *126*, *382*, 6820
\marginparBlock *126*, *382*, 6831, 6849
\markboth 6097
\markright 6098
marvosym (package) *942*
math (environment) 11785
mathalpha (package) *942*
mathastext (package) *943*

mathcomp (package) 944
mathdesign (package) 944
mathdots (package) 946
mathfixs (package) 946
\MathImageAltText 116, 11400
MathJax (program) 154, 155
MathJax (program) [requirement] 79
mathjax (boolean) 232
mathjax (option) 106, 233
\MathJaxFilename 114, 6658
mathpazo (package) 947
mathptmx (package) 947
mathspec (package) 948
mathsvg (option) 106, 233
mathtools (package) 158, 950
mattens (package) 956
maybemath (package) 958
\mbox 12709
mcaption (package) 958
\mcolrowcell 9968
mdframed (package) 130, 958
\mdseries 13078
mdwmath (package) 967
media9 (package) 164, 968
memhfixc (package) 970
memoir (class) 172, 174, 1227
menukeys (package) 970
metalogo (package) 971
metalogox (package) 971
mhchem (package) 972
microtype (package) 241, 975
midfloat (package) 975
midpage (package) 976
\MiKTeX 13554
minibox (package) 976
minipage (environment) 12604
\minipagefullwidth 12592
minitoc (package) 977
minted (package) 977
mismath (package) 978
mleftright (package) 982
mmap (package) 104
morefloats (package) 982
moreverb (package) 982
movie15 (package) 164, 983
mparhack (package) 985
\mrowcell 9965
MS-Windows (program) 119, 230
multibib (package) 985
multicap (package) 985
multicol (package) 986
multicolrule (package) 987
\multicolumnrow 45, 9835
multimedia (package) 164, 987
multiobjective (package) 988
\multirow 990
multirow (package) 989
multitoc (package) 993
multline (environment) 72
multline* (environment) 75
musicography (package) 993

N

nameauth (package) 996
\Nameref 10380
\nameref 10371
nameref (package) 997
natbib (package) 998
nccfancyhdr (package) 999
nccfoots (package) 1000
nccmath (package) 1000
needspace (package) 1001
newclude (package) 175
\newfloat 5
newfloat (package) 245
\newline 13286
\newpage 13283
newpxmath (package) 1002
\newtheorem 436
newtxmath (package) 1002
newtxsf (package) 1003
newunicodechar (package) 104
nextpage (package) 1004
nfssext-cfr (package) 1005
nicefrac (package) 159, 1011
niceframe (package) 1012
nicematrix (package) 1012
\noalign 9978
\nohyperpage 11170
noitcrul (package) 1015
nolbreaks (package) 1015
\nolinebreak 13357
nomencl (package) 138, 1015
nonfloat (package) 1016
nonumonpart (package) 1016
\nopagebreak 13361
\nopagecolor 79
nopageno (package) 1016
\normalcolor 8
\normalfont 13156
\normalmarginpar 6846
notes (package) 1017
notespages (package) 1017
nowidow (package) 1018
ntheorem (package) 157, 1018
\numberline 10851
numindex (option) [tocbibind] 152, 1199

O

octave (package) 1030
OpenOffice (program) 76

option:
--shell-escape 103
[lwarpmk]:
htmlglossary 137, 845
printglossary 137, 845
[tocbibind]:
numindex 152, 1199
[tocloft]:
titles 135
BaseJobname 110, 233
dvipdfm 106, 236
dvipdfmx 106, 236
dvips 106, 236
GlossaryCmd 110, 137, 235, 845
HomeHTMLFilename 106, 234
HTMLFilename 106, 234
HTMLIndexCmd 109, 235
HTMLLatexCmd 108, 178, 235
ImagesDirectory 106, 233
ImagesName 106, 233
IndexRef 109, 235
latexmk 106, 236
LatexmkIndexCmd 109, 235
lwarpmk 110, 234, 321
makeindex 108, 235
makeindexStyle 108, 149, 233
mathjax 106, 233
mathsvg 106, 233
OSWindows 110, 119, 230, 234
pdftotextEnc 110, 234
PrintIndexCmd 108, 235
PrintLatexCmd 108, 178, 235
warpHTML 110, 232
warpprint 110, 232
xindex 108, 235
xindexConfig 108, 150, 234
xindy 108, 235
xindyCodepage 108, 234
xindyLanguage 108, 234
xindyStyle 108, 150, 233
orcidlink (package) 1031
\OSPathSymbol 1045
OSWindows (option) 110, 119, 230, 234
overpic (package) 164, 1032

P

package:
2in1 640
2up 640
a4 640
a4wide 641
a5comb 641
abstract 135, 641
academicons 643
accents 644
accessibility 645
accsupp 645
acro 646
acronym 648
addlines 650
adjmulticol 649
afterpage 651
algorithm2e 651
algorithmicx 170, 655
alltt 656
amscdx 656
amsmath 657
amsthm 661
anonchap 666
anysize 667
appendix 136, 667
ar 667
arabicfront 669
array 669
arydshln 670
asymptote 164, 672
atbegshi 673
attachfile 673
attachfile2 674
authblk 135, 676
autobreak 677
autonum 678
awesomebox 679
axessibility 680
axodraw2 681
babel 175
backnaur 681
backref 682
balance 682
bbding 683
biblatex 687
bibunits 692
bigdelim 170, 692
bigfoot 693
bigstrut 694
bitpattern 694
blowup 695
bm 695
booklet 696
bookmark 696
booktabs 696
bophook 698
bounddvi 699
boxedminipage 699
boxedminipage2e 699
braket 700
breakurl 700
breqn 700
bsheaders 702
bussproofs 702
bxpapersize 703

bytefield 703
calc 244
cancel 703
canoniclayout 704
capt-of 528
caption 171, 528, 705
caption3 706
cases 709
ccicons 709
centerlastline 710
centernot 710
changebar 711
changelayout 711
changepage 712
changes 712
chappg 717
chapterbib 718
chemfig 718
chemformula 720
chemgreek 725
chemmacros 726
chemnum 743
chkfloat 744
chngpage 744
cite 744
citeref 745
CJK 745
CJKutf8 746
classicthesis 746
cleveref 132, 747
clrdblpg 750
cm-super 103
cmap 104
cmbright 750
cmdtrack 751
colonequals 751
color 162, 752
colortbl 169, 752
comment 239
continue 754
copyrightbox 754
crop 755
ctable 755
cuted 758
cutwin 758
dblfloatfix 759
dblfnote 759
dcolumn 759
decimal 760
decorule 760
dejavu 103
diagbox 760
dingbat 762
ditaa 181
DotArrow 763
dotlessi 763
dprogress 764
draftcopy 764
draftfigure 764
draftwatermark 765
drftcite 765
easy-todo 766
ebook 767
econometrics 767
ed 770
ellipsis 770
embrac 771
emptypage 771
endfloat 772
endheads 772
endnotes 136, 773
engtlc 774
enotez 778
enumerate 780
enumitem 781
environ 246
epigraph 781
epsf 782
epsfig 783
epstopdf 162, 783
epstopdf-base 783
eqlist 784
eqparbox 785
errata 786
eso-pic 787
esvect 788
etoc 788
etoolbox 205
eurosym 791
everyhook 244
everypage 791
everyshi 791
expl3 244
extarrows 792
extramarks 792
fancybox 129, 793
fancyhdr 798
fancypar 799
fancyref 800
fancytabs 800
fancyvrb 801
fbox 808
fewerfloatpages 810
figcaps 810
figsize 811
filecontents 244
fitbox 811
fix2col 812
fixmath 812
fixme 176, 812

fixmetodonotes 814
flafter 814
flippdf 815
float 170, 815
floatflt 816
floatpag 818
floatrow 171, 818
fltrace 823
flushend 823
fnbreak 824
fncychap 824
fnlineno 825
fnpara 825
fnpos 825
fontawesome 825
fontawesome5 827
fontaxes 827
fontenc 104, 828
fontspec 103, 240
footmisc 828
footnote 829
footnotebackref 830
footnotehyper 830
footnoterange 830
footnpag 831
foreign 831
forest 831
fouridx 832
fourier 832
framed 834
froufrou 836
ftcap 837
ftnright 837
fullminipage 837
fullpage 837
fullwidth 838
fvextra 838
fwlw 841
gensymb 841
gentombow 842
geometry 241, 842
gettitlestring 244
ghsystem 843
gindex 140, 843
gloss 137, 844
glossaries 137, 845
gmeometric 847
graphics 159, 847
graphicx 159, 860
grffile 162, 860
grid 860
grid-system 861
gridset 861
hang 862
hanging 863
hepunits 864
hhline 865
hhtensor 866
hypbmsec 866
hypcap 867
hypdestopt 867
hypernat 867
hyperref 132, 516, 867
hyperxmp 877
hyphenat 878
idxlayout 879
ifoddpage 880
ifplatform 205
imakeidx 880
impnattypo 884
indentfirst 372
index 885
inputenc 104
inputenx 104
inputtrc 886
intopdf 886
isomath 887
isotope 887
jurabib 889
karnaugh-map 890
keyfloat 172, 893
keystroke 899
kotex 177
kpfonts 900
kpfonts-otf 902
kvoptions 232
layaureo 903
layout 903
layouts 903
leading 906
leftidx 906
letltxmacro 205
letterspace 907
lettrine 907
libertinust1math 908
lineno 914
lips 917
listings 917
listliketab 923
lltjext 924
lmodern 103, 104
longtable 168, 925
lpic 928
lscape 928
ltablex 928
ltcaption 929
ltxgrid 929
ltxtable 929
lua-check-hyphen 930
lua-visual-debug 930

luacolor 930
luamplib 931
luatexko 931
luatodonotes 176, 933
luavlna 935
lwarp 106
lwarp-common-mathjax-letters . . 1297
lwarp-common-mathjax-newpxtxmath 1304
lwarp-common-mathjax-nonunicode 1310
lwarp-common-mathjax-overlaysymbols 1312
lwarp-common-multimedia 1292
lwarp-patch-komascript 1261
lwarp-patch-memoir 1263
lyluatex 935
magaz 937
makeidx 151, 152, 938, 1198
manyfoot 938
marginal 940
marginfit 940
marginfix 941
marginnote 941
marvosym 942
mathalpha 942
mathastext 943
mathcomp 944
mathdesign 944
mathdots 946
mathfixs 946
mathpazo 947
mathptmx 947
mathspec 948
mathtools 158, 950
mattens 956
maybemath 958
mcaption 958
mdframed 130, 958
mdwmath 967
media9 . . . . . 164, 968
memhfixc 970
menukeys 970
metalogo 971
metalogox 971
mhchem 972
microtype 241, 975
midfloat 975
midpage 976
minibox 976
minitoc 977
minted 977
mismath 978
mleftright 982
mmap 104
morefloats 982
moreverb 982
movie15 . . . . . 164, 983
mparhack 985
multibib 985
multicap 985
multicol 986
multicolrule 987
multimedia 164, 987
multiobjective 988
multirow 989
multitoc 993
musicography 993
nameauth 996
nameref 997
natbib 998
nccfancyhdr 999
nccfoots 1000
nccmath 1000
needspace 1001
newclude 175
newfloat 245
newpxmath 1002
newtxmath 1002
newtxsf 1003
newunicodechar 104
nextpage 1004
nfssext-cfr 1005
nicefrac 159, 1011
niceframe 1012
nicematrix 1012
noitcrul 1015
nolbreaks 1015
nomencl 138, 1015
nonfloat 1016
nonumonpart 1016
nopageno 1016
notes 1017
notespages 1017
nowidow 1018
ntheorem 157, 1018
octave 1030
orcidlink 1031
overpic 164, 1032
pagegrid 1033
pagenote 136, 1033
pagesel 1033
paralist 1033
parallel 1034
parcolumns 1036
parnotes 1038
parskip 1039
pbalance 1039
pbox 1040
pdfcol 1040
pdfcolfoot 1040

pdfcolmk 1041
pdfcolparallel 1041
pdfcolparcolumns 1041
pdfcomment 1042
pdfcrypt 1043
pdflscape 1043
pdfmarginpar 1043
pdfpages 1043
pdfprivacy 1046
pdfrender 1046
pdfsync 1046
pdftricks 163, 1047
pdfx 1047
perltex 180
perpage 1047
pfnote 1049
phfqit 1049
physics 159, 1049
physunits 1050
picinpar 1052
pifont 1053
pinlabel 1054
placeins 1054
plarydshln 1054
plext 1055
plextarydshln 1056
plextcolortbl 1056
plimsoll 1056
polyglossia 175
prelim2e 1057
prettyref 1057
preview 1057
printlen 246
psfrag 163, 1058
psfragx 1058
pst-eps 1059
pstool 163, 1059
pstricks 162, 1060
pxatbegshi 1060
pxeveryshi 1060
pxfonts 1061
pxftnright 1061
pxjahyper 1061
pythontex 180
quotchap 1062
quoting 1063
ragged2e 1063
realscripts 1064
refcheck 1067
refcount 245
register 1067
relsize 126, 1068
repeatindex 1069
repltext 1070
resizegather 1071
returntogrid 1071
rlepsf 1071
rmathbr 1072
rmpage 1072
romanbar 1072
romanbarpagenumber 1073
rotating 1073
rotfloat 1074
rterface 180
rviewport 1074
sagetex 180
savetrees 1075
scalefnt 1075
scalerel 1075
schemata 1076
scrextend 1076
scrhack 1080
scrlayer 1080
scrlayer-notecolumn 1082
scrlayer-scrpage 1082
scrpage2 1084
section 1085
sectionbreak 1086
sectsty 1086
selectp 1087
semantic-markup 1087
seqsplit 1088
setspace 1089
shadethm 1090
shadow 1090
shapepar 1091
showidx 1091
showkeys 1091
showtags 1091
shuffle 1092
sidecap 1093
sidenotes 1093
simplebnf 1095
SIunits 1096
siunitx 158, 590, 1105
siunitx-v2 1105
skmath 1120
slantsc 1125
slashed 1126
soul 1126
soulpos 1128
soulutf8 1128
splitbib 1128
splitidx 1129
srcltx 1131
srctex 1131
stabular 1131
stackengine 1132
stackrel 1134
statex2 1134

statistics 1138
statmath 1144
steinmetz 1146
stfloats 1146
struktex 1146
subcaption 171, 1147
subfig 171, 1147
subfigure 1152
subsupscripts 1153
supertabular 169, 1154
svg 1155
swfigure 1156
sympytex 180
syntonly 1156
tabfigures 1157
tablefootnote 1157
tabls 1157
tabularx 1157
tabulary 1158
tagpdf 1158
tascmac 1161
tcolorbox 130, 1162
tensor 1168
termcal 1169
textarea 1170
textcomp 104, 125, 1170
textfit 1174
textpos 1174
theorem 1175
thinsp 1179
thm-listof 1179
thm-restate 1180
thmbox 1180
thmtools 1181
threadcol 1182
threeparttable 1182
threeparttablex 169, 1183
thumb 1184
thumbs 1184
tikz 161, 1184
tikz-imagelabels 1186
titleps 1186
titleref 1189
titlesec 1189
titletoc 1191
titling 135, 1193
tocbasic 1197
tocbibind 152, 1198
tocdata 1200
tocenter 1201
tocloft 135, 152, 666, 1201
tocstyle 1207
todo 1207
todonotes 176, 1208
topcapt 1210
tram 1210
transparent 1211
trimclip 1211
trivfloat 170, 1212
truncate 1213
turnthepage 1213
twoup 1213
txfonts 1213
txgreeks 1214
typearea 1215
typicons 1215
ulem 1216
umoline 1217
underscore 1218
unicode-math 1218
units 159, 1223
unitsdef 1223
upgreek 1224
upref 1225
url 132, 1225
ushort 1225
uspace 1226
varioref 132, 1226
varwidth 246
verbatim 245
verse 174, 1226, 1227
versonotes 1228
vertbars 1228
vmargin 1229
vowel 1229
vpe 1230
vwcol 1230
wallpaper 1232
watermark 1233
widetable 1233
widows-and-orphans 1233
witharrows 1233
wrapfig 1235
xbmks 1236
xcolor 162, 594, 1237
xechangebar 1247
xellipsis 1247
xetexko 1248
xevlna 1248
xfakebold 1249
xfrac 1249
xifthen 245
xltabular 1251
xltxtra 1252
xmpincl 1253
xparse 243
xpatch 205
xpiano 1253
xpinyin 1253
xr 1255

xr-hyper 1255
xstring 245
xtab 169, 1256
xunicode 1257
xurl 1258
xy 1259
zhlineskip 1260
zwpagelayout 1260
\PackageDiagramAltText 116, 11405
\pagebreak 13358
\pagecolor 78
pagegrid (package) 1033
pagenote (package) 136, 1033
\pagenumbering 6103
\pageref 10366
\pagerefPageFor 10365
pagesel (package) 1033
\pagestyle 6095
Pandoc (program) 76
\paragraph 7620
paralist (package) 1033
parallel (package) 1034
\parbox 12700
parcolumns (package) 1036
parnotes (package) 1038
\parsemulticolumnalignment 9603
parskip (package) 1039
\part 7587
pbalance (package) 1039
pbox (package) 1040
pdfcol (package) 1040
pdfcolfoot (package) 1040
pdfcolmk (package) 1041
pdfcolparallel (package) 1041
pdfcolparcolumns (package) 1041
pdfcomment (package) 1042
pdfcrop (program) [requirement] 79
pdfcrypt (package) 1043
pdfLaTeX (program) [requirement] 79
pdflscape (package) 1043
pdfmarginpar (package) 1043
pdfpages (package) 1043
pdfprivacy (package) 1046
pdfrender (package) 1046
pdfseparate (program) [requirement] . 79, 84
pdfsync (package) 1046
pdftocairo (program) 160, 592
pdftocairo (program) [requirement] . . 79, 84
pdftotext (program) [requirement] . . 79, 84
pdftotextEnc (option) 110, 234
pdftricks (package) 163, 1047
pdfx (package) 1047
perl (program) [requirement] 84
perltex (package) 180
perpage (package) 1047
pfnote (package) 1049
phfqit (package) 1049
physics (package) 159, 1049
physunits (package) 1050
picinpar (package) 1052
picture (environment) 598, 12569
pifont (package) 1053
pinlabel (package) 1054
placeins (package) 1054
plarydshln (package) 1054
Plastex (program) 75
plext (package) 1055
plextarydshln (package) 1056
plextcolortbl (package) 1056
plimsoll (package) 1056
\PN@parnotes@auto 6503
polyglossia (package) 175
\postbookname 7567
\postchaptername 7571
\postpartname 7569
\postsectionname 7573
\prebookname 7567
\prechaptername 7571
prelim2e (package) 1057
\prepartname 7569
\presectionname 7573
prettyref (package) 1057
preview (package) 1057
\printauthor 422, 7980, 7999
\printdate 422, 7991, 8001
printglossary (option) [lwarpmk] . 137, 845
\printindex 2
PrintIndexCmd (option) 108, 235
PrintLatexCmd (option) 108, 178, 235
printlen (package) 246
\printthanks 421, 7957
\printtitle 422, 7964, 7998
program:
[requirement]:
LuaLaTeX 79
MathJax 79
pdfcrop 79
pdfLaTeX 79
pdfseparate 79, 84
pdftocairo 79, 84
pdftotext 79, 84
perl 84
XeLaTeX 79
Adobe 76
AsciiDoc 76
AsciiDoctor 76
Asciidoctor-LaTeX 76
epstopdf 160, 592
Flare 76
FrameMaker 76

GELLMU 75
GladTeX 75
Hevea 75
htlatex 75
imakeidx 142
InDesign 76
index 140
LaTeX2HTML 75
latexmk 179
LaTeXML 75
LibreOffice 76
Linux 119, 229
lwarpmk 192, 321
lwarpmk epstopdf 160, 592
lwarpmk pdftosvg 160, 592
Mac OS 119, 229
Madcap 76
make 181
makeindex 139, 149
MathJax 154, 155
MS-Windows 119, 230
OpenOffice 76
Pandoc 76
pdftocairo 160, 592
Plastex 75
splitidx 141
TeX2page 75
TeX4ht 75
TeXMaths 186
TtH 75
Unix 119, 229
Windows 119, 230
Word 76
xindex 139, 150
xindy 139, 149
project.css (file) 118
project.lwarpmkconf (file) 274
psfrag (package) 163, 1058
psfragx (package) 1058
pst-eps (package) 1059
pstool (package) 163, 1059
pstricks (package) 162, 1060
pxatbegshi (package) 1060
pxeveryshi (package) 1060
pxfonts (package) 1061
pxftnright (package) 1061
pxjahyper (package) 1061
pythontex (package) 180

Q

\qquad 622, 13306
\quad 622, 13301
quotation (environment) 8166
quotchap (package) 1062
quote (environment) 8158
quoting (package) 1063

R

ragged2e (package) 1063
\raggedbottom 6099
\raggedleft 12364
\raggedright 12370
\raisebox 12888
realscripts (package) 1064
\ref 10344
refcheck (package) 1067
refcount (package) 245
\reflectbox 398
register (package) 1067
relsize (package) 126, 1068
repeatindex (package) 1069
repltext (package) 1070
[requirement]:
LuaLaTeX (program) 79
MathJax (program) 79
pdfcrop (program) 79
pdfLaTeX (program) 79
pdfseparate (program) 79, 84
pdftocairo (program) 79, 84
pdftotext (program) 79, 84
perl (program) 84
XeLaTeX (program) 79
\RequirePackage 1507
\resizebox 407
resizegather (package) 1071
\ResumeTabular 9880
returntogrid (package) 1071
\reversemarginpar 6845
\rightline 12378
rlepsf (package) 1071
rmathbr (package) 1072
\rmfamily 13098
rmpage (package) 1072
romanbar (package) 1072
romanbarpagenumber (package) 1073
\rotatebox 356
rotating (package) 1073
rotfloat (package) 1074
\rowcolor 9079
\rownum 9071
rterface (package) 180
\rule 124, 13365
rviewport (package) 1074

S

sagetex (package) 180
sample_project.css (file) 118, 315
savetrees (package) 1075
\sb 13176
\scalebox 379
scalefnt (package) 1075
scalerel (package) 1075
schemata (package) 1076

scrextend (package) 1076
scrhack (package) 1080
scrlayer (package) 1080
scrlayer-notecolumn (package) 1082
scrlayer-scrpage (package) 1082
scrpage2 (package) 1084
\scshape 13123
\section 7611
section (package) 1085
sectionbreak (package) 1086
sectsty (package) 1086
selectp (package) 1087
semantic-markup (package) 1087
seqsplit (package) 1088
\SetHTMLFileNumber 5904
setspace (package) 1089
\sffamily 13103
\sfrac 1249
shadethm (package) 1090
shadow (package) 1090
shapepar (package) 1091
showidx (package) 1091
showkeys (package) 1091
showtags (package) 1091
shuffle (package) 1092
sidecap (package) 1093
sidenotes (package) 1093
SideTOCDepth (counter) 111, 532
\sidetocname 113, 10827
simplebnf (package) 1095
\simplechapterdelim 7382
\sishape 13138
SIunits (package) 1096
siunitx (package) 158, 590, 1105
siunitx-v2 (package) 1105
skmath (package) 1120
slantsc (package) 1125
slashed (package) 1126
\sloppy 6101
\slshape 13149
soul (package) 1126
soulpos (package) 1128
soulutf8 (package) 1128
\sp 13175
splitbib (package) 1128
splitidx (package) 1129
splitidx (program) 141
srcltx (package) 1131
srctex (package) 1131
\sscshape 13154
stabular (package) 1131
stackengine (package) 1132
stackrel (package) 1134
\StartDefiningMath 5862
\StartDefiningTabulars 5852
statex2 (package) 1134
statistics (package) 1138
statmath (package) 1144
steinmetz (package) 1146
stfloats (package) 1146
\StopDefiningMath 5866
\StopDefiningTabulars 5856
struktex (package) 1146
subcaption (package) 171, 1147
subfig (package) 171, 1147
subfigure (package) 1152
\subparagraph 7623
\subsection 7614
\subsubsection 7617
subsupscripts (package) 1153
supertabular (package) 169, 1154
svg (package) 1155
swfigure (package) 1156
sympytex (package) 180
syntonly (package) 1156

T

tabbing (environment) 8271
tabfigures (package) 1157
tablefootnote (package) 1157
\tableofcontents 115, 10757
tabls (package) 1157
tabular (environment) 10027
\TabularMacro 9878
tabularx (package) 1157
tabulary (package) 1158
tagpdf (package) 1158
tascmac (package) 1161
tcolorbox (package) 130, 1162
tensor (package) 1168
termcal (package) 1169
\TeX 13470
TeX2page (program) 75
TeX4ht (program) 75
TeXMaths (program) 186
textarea (package) 1170
\textbf 12915
\textcolor 65
textcomp (package) 104, 125, 1170
\texteb 12923
textfit (package) 1174
\textgreater 5897
\textit 12971
\textless 5895
\textlg 12931
\textmd 12907
\textnormal 13022
textpos (package) 1174
\textrm 12939
\textsc 12979
\textsf 12947

\textsi 12995
\textsl 13012
\textssc 13020
\textsubscript 13181
\textsuperscript 13177
\texttt 12955
\textulc 12987
\textup 12963
\tfl@chapter@fix *1212*
\thanks *122*
\thanksmarkseries 92
\theauthor *422*
thebibliography (environment) 11183
\thedate *422*
\theHTMLSection 7657
\theHTMLTitleSection 7656
\theHTMLTitleSeparator 7633
theindex (environment) 10924
\thempfootnote 6776
theorem (package) *1175*
\thetitle *422*
thinsp (package) *1179*
\ThisAltText *115*, 11402
\thispagestyle 6096
thm-listof (package) *1179*
thm-restate (package) *1180*
thmbox (package) *1180*
thmtools (package) *1181*
threadcol (package) *1182*
threeparttable (package) *1182*
threeparttablex (package) *169*, *1183*
thumb (package) *1184*
thumbs (package) *1184*
tikz (package) *161*, *1184*
tikz-imagelabels (package) *1186*
\title *121*, 6668
titlepage (environment) *121*, 7945
titleps (package) *1186*
titleref (package) *1189*
titles (option) [tocloft] *135*
titlesec (package) *1189*
titletoc (package) *1191*
titling (package) *135*, *1193*
titlingpage (environment) 14, *121*
tocbasic (package) *1197*
[tocbibind]:
  numindex (option) *152*, *1199*
tocbibind (package) *152*, *1198*
tocdata (package) *1200*
tocdepth (counter) *111*
tocenter (package) *1201*
[tocloft]:
  titles (option) *135*
tocloft (package) *135*, *152*, *666*, *1201*
tocstyle (package) *1207*
todo (package) *1207*
todonotes (package) *176*, *1208*
topcapt (package) *1210*
\tracinglwarp *200*, 1686
tram (package) *1210*
transparent (package) *1211*
trimclip (package) *1211*
trivfloat (package) *170*, *1212*
truncate (package) *1213*
\ttfamily 13108
TtH (program) *75*
turnthepage (package) *1213*
tutorial.tex (file) *85*
twoup (package) *1213*
txfonts (package) *1213*
txgreeks (package) *1214*
typearea (package) *1215*
typicons (package) *1215*

U

\ulcshape 13130
ulem (package) *1216*
umoline (package) *1217*
\underline 13187
underscore (package) *1218*
unicode-math (package) *1218*
units (package) *159*, *1223*
unitsdef (package) *1223*
Unix (program) *119*, *229*
\up 13185
upgreek (package) *1224*
upref (package) *1225*
\upshape 13113
url (package) *132*, *1225*
\UseMinipageWidths *127*, *599*, 12593
ushort (package) *1225*
usingOSWindows (boolean) *231*
uspace (package) *1226*

V

varioref (package) *132*, *1226*
varwidth (package) *246*
\verb 8201
verbatim (environment) 8253
verbatim (package) *245*
\VerbatimHTMLWidth (length) *433*
\verbatiminput 8245
verse (environment) 2, 8176
verse (package) *174*, *1226*, *1227*
versonotes (package) *1228*
vertbars (package) *1228*
\vleftmargini (length) *174*, *432*, *1226*
\vleftskip (length) *174*, *432*, *1226*, *1227*
vmargin (package) *1229*
vowel (package) *1229*
vpe (package) *1230*

\vrule 125
\vspace 124
vwcol (package) 1230

W

wallpaper (package) 1232
warpall (environment) 120, 1270
warpHTML (environment) 116, 119, 1271
warpHTML (option) 110, 232
\warpHTMLonly 117, 120, 1228
warpingHTML (boolean) 232
warpingprint (boolean) 232
warpMathJax (environment) 120, 1277
warpprint (environment) 116, 120, 1274
warpprint (option) 110, 232
\warpprintonly 116, 120, 1227
watermark (package) 1233
widetable (package) 1233
widows-and-orphans (package) 1233
Windows (program) 119, 230
witharrows (package) 1233
Word (program) 76
WPMarkFloats (boolean) 185, 261
WPMarkLOFT (boolean) 186, 261
WPMarkMath (boolean) 186, 262
WPMarkMinipages (boolean) 186, 261
WPMarkTOC (boolean) 186, 261
WPTitleHeading (boolean) 187, 262
wrapfig (package) 1235

X

xbmks (package) 1236
xcolor (package) 162, 594, 1237
xechangebar (package) 1247
\XeLaTeX 13517
XeLaTeX (program) [requirement] 79
xellipsis (package) 1247
\XeTeX 13517
xetexko (package) 1248
xevlna (package) 1248
xfakebold (package) 1249
xfrac (package) 1249
\xfracHTMLfontsize 2
xifthen (package) 245
xindex (option) 108, 235
xindex (program) 139, 150
xindexConfig (option) 108, 150, 234
xindy (option) 108, 235
xindy (program) 139, 149
xindyCodepage (option) 108, 234
xindyLanguage (option) 108, 234
xindyStyle (option) 108, 150, 233
xltabular (package) 1251
xltxtra (package) 1252
xmpincl (package) 1253
xparse (package) 243
xpatch (package) 205
xpiano (package) 1253
xpinyin (package) 1253
xr (package) 1255
xr-hyper (package) 1255
xstring (package) 245
xtab (package) 169, 1256
xunicode (package) 1257
xurl (package) 1258
xy (package) 1259

Z

zhlineskip (package) 1260
zwpagelayout (package) 1260

General Index

This is an index of instructions and concepts. Look here when wondering how to do something, and check the Troubleshooting Index when something goes wrong.

Symbols

\@ifnextchar with MathJax 155
\@ifstar with MathJax 155
\, ... 124
~ 124

A

accents
  in section & file names 400
accessibility 101
adapting
  class 192
  document 100
  package 191
affiliation
  multiple authors 134
algorithmicx
  with newfloat, trivfloat 1212
alt text 101
ARIA 101
array
  mhchem 972
audio 164
author
  HTML meta tag 122, 375
  multiple 134

B

baseline
  tabular 465
bibliography
  HTML page and TOC 135
bitmapped fonts 103
bugs 194

C

Calibre 182
chemistry
  Greek symbols 725
class
  modifying for lwarp 192
code listings 124
compiling
  custom 178
Computer Modern 103
converting
  class 192
  document 100
  package 191
CSS
  class 119
  file selection 118
  lwarp.css 118
  per HTML page 118
  project-specific changes 118
  span 119
ctable 170

D

danger icon 204
debugging 194
  HTML debug comments 254
  tracing log 254
Deja Vu 103
description
  HTML meta tag 122, 375
display math
  complicated objects 157
document
  convert existing 100
documentation
  compile 190
DVI LaTeX 95, 103
dynamic math 156, 157
dynamic math expressions 345

E

endnotes
  HTML page and TOC 135
EPS image
  converting 97
  using 159, 592
EPUB
  conversion software 182
  HTML conversion settings 182, 260
equation numbering
  MathJax 154
error messages 194
export
  to word processor 184

F

FAQ 194

filename
accent in . . . 400
graphics . . . 159, 592
hashed . . . 560, 581
images . . . 159, 592
international languages . . . 174
length . . . 113
simplify . . . 131
underscore in . . . 106, 126
unique . . . 113
font
Computer Modern . . . 103
Deja Vu . . . 103
ligatures . . . 104
packages . . . 104
selection . . . 103
size
lateximage . . . 153, 578
math, SVG . . . 153, 578
xfrac . . . 1250
type 1 vector . . . 103
type 3 bitmapped . . . 103
footnotes . . . 375
MathJax . . . 133
numbering . . . 133
foreign
section names . . . 174
framed objects . . . 127
Frequently Asked Questions . . . 194

G

generator
HTML meta tag . . . 413
GIF images . . . 161, 593
gindex . . . 140
gloss . . . 137
glossaries
HTML page and TOC . . . 135
language . . . 137
options . . . 137
processing . . . 96
graphics
file formats . . . 159, 592
file names . . . 159, 592
Greek
chemistry symbols . . . 725

H

hash
SVG image filename . . . 560, 581
heading, word processor . . . 187
horizontal and vertical space . . . 124
horizontal rule . . . 125
horizontal space
between minipages . . . 622
\hrule . . . 125
HTML
alt text . . . 101
class . . . 119
conversion settings . . . 111
debug comments . . . 254
EPUB . . . 182, 260
word processor . . . 184, 261
conversion suggestions . . . 123
 . . . 119
entities, conversion . . . 124
filename generation . . . 117
headings . . . 203
meta tag
author . . . 122, 375
description . . . 122, 375
generator . . . 413
title . . . 114, 122, 374, 375
viewport . . . 413
selecting print/HTML definitions . . . 255
 . . . 119
style . . . 119
tabular column conversion . . . 466
verbatim, in . . . 124
hyperref
and *xindy* . . . 138
title text . . . 101

I

icon
warning . . . 204
\@ifnextchar with MathJax . . . 155
\@ifnextstar with MathJax . . . 155
image
alt text . . . 101
file formats . . . 159, 592
file names . . . 159, 592
GIF . . . 161, 593
graphicx package . . . 592
hashed filename . . . 560, 581
PDF or EPS
converting . . . 97, 160, 592
using . . . 159, 592
PNG and JPG . . . 161, 592
processing . . . 321
\includegraphics
file names . . . 159, 592
using . . . 159, 592
index
custom display styles . . . 151
formatting . . . 542
gindex
setup . . . 140
HTML page and TOC . . . 135
imakeidx
setup . . . 142

index
setup . . . 140
letter headings . . . 880
makeindex
custom style file . . . 149
setup . . . 139
memoir
setup . . . 146
placement . . . 151
placement and TOC options . . . 151, 1198
processing . . . 89, 90, 138
see, seealso, ranges . . . 138
source code . . . 138
splitidx
setup . . . 141
table of contents . . . 151, 1198
tocbibind . . . 151
UTF-8 . . . 105
xindex
custom configuration file . . . 150
setup . . . 139
xindy
custom style file . . . 149
and hyperref . . . 138
setup . . . 139
inline math
complicated objects . . . 156
international
section names . . . 174
item
empty . . . 437

J

JavaScript
MathJax . . . 152
JPG images . . . 161, 592

L

language
glossaries . . . 137
localization . . . 101
language HTML metadata . . . 411
lateximage
font size . . . 153, 578
processing . . . 321
Latin Modern font . . . 103
LibreOffice
conversion recommendations . . . 187
import into . . . 184
section headings . . . 187
ligatures . . . 104, 241
line numbers . . . 204
link
home/previous/next page . . . 115
`title` text . . . 101
list
empty item . . . 437
filename . . . 126
listings, program code . . . 124
locale . . . 181
localization . . . 101
LuaLaTeX
detection . . . 205
file & section names . . . 400
lwarp
compiling documentation . . . 190
loading . . . 106
options . . . 106
`lwarp.ist`
customizing . . . 149
`lwarp.xdy`
customizing . . . 149
lwarpmk
customizing . . . 192

M

make utility . . . 181
makeindex . . . 139
customizing . . . 149
margin
numbers . . . 204
tags . . . 204
markup languages . . . 76
math
`alt` text . . . 101
display with complicated objects . . . 157
dynamic . . . 156, 157, 345
MathJax . . . 154
font size — SVG . . . 153, 578
inline with complicated objects . . . 156
MathJax custom functions . . . 154
MathJax summary . . . 154
`mathjax` option . . . 233
`mathsvg` option . . . 233
mhchem . . . 972
SVG summary . . . 153
word processor conversion . . . 186
MathJax
`\@ifnextchar` macros . . . 155
`\@ifstar` macros . . . 155
accessibility . . . 101
custom functions . . . 154
custom script . . . 318
equation numbering . . . 154
`mathjax` option . . . 233
starred macros . . . 155
summary . . . 154
`\mcolrowcell` . . . 167
MD5 hash
SVG image filename . . . 560, 581

memoir
framewithtitle, titledframe 173
meta tag, HTML
author 122, 375
description 122, 375
generator 413
title 122, 374, 375
viewport 413
minipage
framed 127
horizontal space between 622
modifying
class 192
document 100
package 191
\mrowcell 167
\multicolumn
with \multirow 167
multimedia 164
multiple projects in a directory 97
\multirow
with \multicolumn 167
multirow
\mrowcell and \mcolrowcell 167

N

navigation
link to home/previous/next page . . . 115
newfloat
with trivfloat, algorithmicx 1212
nomencl 138
numbers
left margin 204

P

package
modifying for lwarp 191
required 240
\par
hooks 370
PDF image
converting 97
using 159, 592
Perl 84
PNG images 161, 592
Poppler 79, 84
print
selecting print/HTML definitions . . . 255
problems 194
program listings 124
programs
utility 78
projects 97
\published 429

R

roles
ARIO 101
rule
horizontal 125

S

section
depths 203
file names 131
heading, word processor 187
international languages 174
settings
accessibility 101
CSS project-specific 118
CSS selection 118
filenames 111
HTML conversion 111
language 101
lwarp package options 106
selecting print/HTML output 119
title page 121
shell escape 103
sidetoc
name 101
sidetoc
depth 111
siunitx
with *TeXMaths* 186
space
horizontal
between minipages 622
horizontal and vertical 124
stack depths 203
starred macros 155
\StartDefiningTabulars 166, 445
\subtitle 429
SVG
converting from PDF or EPS 97
dynamic math 345
image processing 321
math summary 153
mathsvg option 233

T

tabular
baseline 465
HTML columnn conversion 466
in environments, catcode of & . . 166, 445
macros inside 166, 446
\multicolumn with \multirow 167
multirow \mrowcell and \mcolrowcell
. 167
\StartDefiningTabulars 166, 445
tikz
catcodes 1185

dollar redefined 1185
title
HTML meta tag 122, 374, 375
titlepage
\subtitle and \published 429
tracing log 254
trivfloat
with newfloat, algorithmicx 1212
troubleshooting 194
HTML debug comments 254
tracing log 254
type 1 vector fonts 103
type 3 bitmapped fonts 103

U

underscore
filename 106, 126
Unicode
enhanced coverage 103
file & section names 400
input characters 223
selection 103
UTF-8
enhanced coverage 103
file & section names 400
index 105
locale 181
selection 103
utility
programs 78

V

vector fonts 103
verbatim
code and HTML tags 124
vertical space 124
video 164
viewport
HTML meta tag 413

W

warning icon 204
word processor
conversion recommendations 187
HTML conversion settings 184, 261
section headings 187

X

xcite 97
XeLaTeX
detection 205
file & section names 400
xindex 139
customizing 150
xindy 139
and hyperref 138
customizing 149
xr 97
xr-hyper 97

Troubleshooting Index

This index is a sorted reference of problems and solutions. In order to make it easier to locate a solution, the same issue may be addressed by more than one entry.

Entries with higher page numbers are often duplicates of entries with lower page numbers, as the same warning may occur within the user manual and again within the source code for a given package.

A

abstract
- missing TOC . . . 135, 641

accents
- file names . . . 400

acro . . . 176

acronym
- multiply-defined labels . . . 648

\AddSubtitlePublished . . . 429

affiliation . . . 422

alt tags . . . 157, 198

amscdx . . . 656

AMSmath
- ntheorem
  - numbering . . . 157, 1019

appendix
- incorrect TOC link . . . 136, 667

array
- chemformula . . . 176
- MathJax . . . 155

arydshln . . . 670

audio . . . 164

authblk
- \theauthor . . . 421, 422
- titling . . . 135, 421, 676, 1193

author
- affiliation . . . 422
- formatting . . . 121

autonum . . . 678

B

babel
- French . . . 175

backref . . . 682

backref . . . 133

bibliography
- HTML page and TOC . . . 135

bibtex
- \etalchar . . . 136
- Improper \prevdepth . . . 136

bigdelim . . . 170, 692

bigfoot . . . 134, 938

booktabs . . . 696

boxes . . . 126

breqn
- darray . . . 700

bussproofs . . . 702

C

Calibre
- EPUB conversion . . . 182

caption
- numbering . . . 171
- options . . . 123

changes . . . 712

chemfig . . . 176

chemformula
- MathJax . . . 176, 720

chemgreek
- fontspec mapping . . . 725
- text-mode symbols . . . 725

chemmacros
- \makepolymerdelims . . . 726
- redox reactions . . . 726

Chinese
- font . . . 124

CJK
- font . . . 124

cleveref
- cref reference format undefined . . . 157

cmbright . . . 750

colortbl . . . 169, 752

Command \textquoteright invalid in math mode . . . 198

comment . . . 173, 1264

compiling
- slow MathJax . . . 154

cref reference format undefined . . . 157

cross reference
- incorrect link . . . 199
- MathJax . . . 156
- missing . . . 198

CSS . . . 200

ctable . . . 170

D

ditaa . . . 181

documentation
index cross-references . . . 190
dotless j . . . 104
dotlessj . . . 196
duplcate filename . . . 131

E

\endhead, etc. . . . 168
endnotes
HTML page and TOC . . . 135
numbering . . . 136
\ensuremath . . . 197
epstopdf . . . 162, 784
EPUB
encoding . . . 182
page order . . . 182
search order . . . 182
section breaks . . . 183
equation numbering
MathJax . . . 154
error messages . . . 194
\etalchar . . . 136

F

fancybox
\VerbatimFootnotes . . . 134, 794, 801
fancypar . . . 799
fancyvrb
\VerbatimFootnotes . . . 134, 794, 801
figure
macro in name . . . 197
file
inaccessible . . . 113
multiple projects in directory . . . 97
File ended while scanning use of \next . 196
filename
accents . . . 400
corrupted . . . 131, 174
duplicate . . . 131
image extension . . . 159, 592
international, UTF-8 . . . 174
Korean . . . 177
macro in name . . . 131
math in . . . 100, 131, 152
Missing $ inserted . . . 197
fixme . . . 176, 812
float
alignment . . . 125, 170
not seem to be a floating environment 815
numbering . . . 171
out of sequence . . . 199
float . . . 815
floatrow
\FBwidth and \FBheight . . . 172, 818
with subfig . . . 171, 818
floatrow
\ttabbox . . . 165, 445
font
CJK . . . 124
JetBrain Mono . . . 104
ligatures . . . 104
missing symbols . . . 125, 1171
monospace . . . 104
package conflicts . . . 103
selection . . . 103
small caps . . . 124
UTF-8 . . . 103
fontspec
with monospaced fonts . . . 104
with XeLaTeX, LuaLaTeX. . . . 103
footmisc . . . 133, 376
footnote
displaymath . . . 134, 794, 801
in math . . . 134
in sectioning command . . . 133
MathJax . . . 133
memoir . . . 133, 376
numbering . . . 133
paragraph tags . . . 134, 794, 801
sectioning, footmisc . . . 133, 376
sectioning, verbatim . . . 134, 794, 801
title . . . 421
verbatim . . . 134
\VerbatimFootnotes . . . 134, 794, 801
forest . . . 831
formatting
\bfseries etc. . . . 124, 610
fourier . . . 832
frames . . . 127
framewithtitle . . . 173

G

gloss . . . 137
glossaries
HTML page and TOC . . . 135
makeglossaries not found . . . 137, 845
page numbers . . . 137, 846
style . . . 137, 846
graphics
\rotatebox, \scalebox, \reflectbox . . . 161, 593
image format priorities . . . 161, 593
images out of order . . . 91, 199
multimedia . . . 164
optional arguments . . . 161, 593
scale option . . . 100, 161, 593
scaled . . . 848
viewport . . . 161, 593
Greek packages . . . 725
grffile . . . 162, 860

H

\hrule . . . 125
HTML
  &, <, > . . . 124, 610
  alt tags . . . 157
  author . . . 375
  corrupted . . . 104, 121, 126, 196, 200
  entities . . . 124, 610
  image appear as HTML code . . . 91, 199
  inaccessible pages . . . 113, 115
    starred section . . . 135
  invalid . . . 124
  missing pages
    filename not unique . . . 113
    recompile . . . 200
    SideTOCDepth and FileDepth . . . 113
    SideTOCDepth and tocdepth . . . 113
  page did not update . . . 113, 200
  settings
    changed . . . 111
    undefined . . . 196
  validation . . . 124
\HTMLAuthor . . . 375
HTMLIndexCmd
  filenames . . . 109
hyperref
  backref . . . 133
  comments between arguments . . . 132
  incorrect link . . . 199
  Token not allowed in a PDF string . . . 198

I

image
  appears as HTML code . . . 91, 199
  extension case . . . 159, 592
  format priorities . . . 161, 593
  incorrect . . . 91, 199
  not displayed . . . 159, 592
  SVG math size and baseline . . . 153
  viewport . . . 161, 593
Improper \prevdepth
  bibtex . . . 136
  boxes . . . 197
\includegraphics
  optional arguments . . . 161, 593
  scale . . . 100, 161, 593
index
  ?? and non-functional link . . . 110
  documentation references . . . 190
  empty . . . 151
  empty link . . . 132, 198
  formatting . . . 110, 542
  HTML page and TOC . . . 135
  missing entries . . . 138
  numbers, not links . . . 246
  reference ranges . . . 151
  see and seealso . . . 151
  styling references . . . 151
  xindy
    and hyperref . . . 151
  xstring bug . . . 246
isomath . . . 887

J

\j . . . 104
Japanese
  font . . . 124
JetBrain Mono . . . 104

K

keyfloat . . . 172, 893
Korean
  font . . . 124
kpfonts . . . 900
kpfonts-otf . . . 902

L

label
  \nameref empty . . . 132, 198
  characters . . . 132, 198
Label(s) may have changed . . . 197
LaTeX was unable to guess the total... . . . 197
\LateximageFontSizeName . . . 578
Leaders not followed by proper glue . . . 197
LibreOffice
  import . . . 184
ligatures . . . 104
link
  empty . . . 132, 198
Linux . . . 119, 229
list
  empty item . . . 125, 437
listings . . . 199
lists
  label formatting . . . 438
locale . . . 181
longtable
  \endhead, etc. . . . 168
lrbox . . . 126
ltxtable
  numbering . . . 930
luaLaTeX . . . 103
lwarpmk.conf . . . 89, 90
lwarpmk . . . 89, 90
\LWRbackslash . . . 178
\LWRdollar . . . 178
\LWRhash . . . 178
\LWRopquote . . . 178
\LWRopseq . . . 178
\LWRpercent . . . 178

M

Mac OS . . . 119, 229

makeglossaries
not found . . . 137, 845
\makelabel . . . 438
manyfoot . . . 134, 938
\marginpar . . . 126, 382
math
\@ifnextchar macros and MathJax 155
\@ifstar macros and MathJax . . . 155
alt tags . . . 198
appears as HTML code . . . 91, 199
baseline incorrect . . . 153
chemformula . . . 176
Command \textquoteright invalid in math mode . . . 198
custom macros . . . 197
dynamic . . . 345
equation numbering
MathJax . . . 154
ntheorem . . . 157, 1019
file name . . . 100, 131, 152
footnote . . . 134
MathJax . . . 133
in TEX boxes . . . 154
incorrect . . . 91, 199, 345
non-math contents . . . 198
section name . . . 100, 131, 152
size incorrect . . . 153
slow or failed compile . . . 198
MathJax . . . 155
tabbing . . . 165, 435
Tikz . . . 157
mathalpha . . . 942
mathdesign . . . 944
MathJax
\@ifnextchar macros . . . 155
\@ifstar macros . . . 155
arydshln . . . 670
booktabs . . . 696
chemformula . . . 176, 720
custom script . . . 318
equation numbering . . . 154
errors . . . 157, 198, 345
footnotes . . . 133
mathtools . . . 158, 950
mhchem . . . 972
\multicolumn . . . 155
\multirow . . . 155, 168, 989
physics . . . 159
references . . . 156
siunitx . . . 159, 591, 1106
slow compilation . . . 154
starred macros . . . 155
unicode-math . . . 1218
unsupported packages . . . 156, 198
mathpazo . . . 947
mathptmx . . . 947
mathspec . . . 948
mathtools . . . 158, 950
maybemath . . . 958
\mcolrowcell . . . 167
media9 . . . 164
memoir
framewithtitle, titledframe . . . 173
captions . . . 172, 1263
comment . . . 173, 1264
footmisc . . . 133, 376
options clash . . . 172, 1264
page notes . . . 173, 1264
verse
margin . . . 175, 432, 1227
version clash . . . 173, 1264
mhchem
MathJax . . . 972
nested dollar signs . . . 972
minipage
alignment . . . 127, 599
horizontal space between . . . 622
in a span . . . 127, 599
inline . . . 126, 599
multicols, width in . . . 127, 599
size . . . 127, 599
tabular, width in . . . 127, 599
minted . . . 977
Misplaced \noalign . . . 168, 925
tabular
rules . . . 167, 447
Misplaced \omit
tabular . . . 258
Misplaced alignment tab character &
ctable . . . 170, 755
floatrow . . . 171, 818
frames . . . 128
supertabular . . . 169, 1154, 1256
tabular
macros . . . 165, 344, 445
Missing $ inserted
filename or URL . . . 197
Missing \begin{document}
package options . . . 123
morewrites . . . 151, 197
movie15 . . . 164
\mrowcell . . . 167
MS-Windows . . . 119, 230
multicol
\linewidth . . . 127, 599
\multicolumn
MathJax . . . 155
multimedia . . . 164
multiple projects in a directory . . . 97

multiply-defined labels
acronym . . . 648
\multirow and \multicolumn . . . 168, 989
multirow
MathJax . . . 155, 168, 989
\mrowcell and \mcolrowcell . . . 167

N

newclude . . . 175
newpxmath . . . 1002
newtxmath . . . 1002
newtxsf . . . 1003
nicefrac . . . 159
nicematrix . . . 1012
No room for a new \write . . . 197
nomencl . . . 138
ntheorem . . . 1019
cref reference format undefined . . . 157
font . . . 157, 1019
numbering . . . 157, 1019

O

operating system . . . 119, 229
options
clash with memoir . . . 172, 1264
with braces . . . 123
overpic . . . 164, 1032

P

package
MathJax support . . . 156
options with braces . . . 123
version numbers with memoir 173, 1264
page
inacessible . . . 113
page counter
references . . . 132
SVG images . . . 91, 199
page numbers . . . 132, 198, 747
pagenote . . . 136, 1033
pdftricks . . . 163, 1047
perltex . . . 180
pfnote
numbering . . . 134, 1049
physics
MathJax . . . 159
polyglossia
Undefined control seq … begindocument . . . 175, 636
poppler
Syntax Warning (ligature) . . . 825
PrintIndexCmd . . . 108
projects
multiple . . . 97
psfrag . . . 163
pstool . . . 163, 1059
pstricks . . . 162, 1060
pythontex . . . 180

R

reference
% character between arguments . . . 199
empty link . . . 132, 198
incorrect link . . . 199
label characters . . . 132, 198
MathJax . . . 156
missing or incorrect . . . 198
page number . . . 132, 198, 747
undefined
tcolorbox . . . 131
repeatindex . . . 1069
rlepsf . . . 1071
rterface . . . 180
Runaway argument? File ended … . . . 196

S

sample_projects.css
overwritten . . . 118
\savebox . . . 126
\sbox . . . 126
scale (\includegraphics option) 100, 161, 593
sectioning
accents . . . 400
duplicate name . . . 131
international language . . . 174
macro in name . . . 131, 197
math in name . . . 100, 131, 152
missing . . . 113
starred section . . . 135
word processor import . . . 187
seqsplit . . . 1088
sidenotes
numbering . . . 133
siunitx . . . 158, 591, 1106
MathJax . . . 159, 591, 1106
S column . . . 167, 447
tabular S and s columns . . . 158, 591, 1106
v3 . . . 158, 590, 1105
with *TeXMaths* . . . 186
small caps . . . 124
splitidx
\thepage and \AtWriteToIndex 141, 1129
statistics . . . 1138
subcaption
numbering . . . 171
subfig
inline . . . 171, 1148
numbering . . . 171, 1147
options . . . 171, 1148
with floatrow . . . 171, 818

subtable
numbering
subfig . . . 171, 1147
SVG image
appears as HTML code . . . 91, 199
incorrect . . . 91, 199
math incorrect . . . 345
math size and baseline . . . 153
out of order . . . 91, 199
sympytex . . . 180
Syntax Warning (ligature) . . . 825

T

tabbing
math . . . 165, 435
table
macro in name . . . 197
numbering
ltxtable . . . 930
subfig . . . 171, 1147
Table of Contents
missing . . . 115
tabular
baselines . . . 465
corrupt rows . . . 165, 445, 496
\endhead, \endfoot, \endlastfoot . . . 168, 925
inside an environment . . . 165, 445, 496
\kill . . . 168, 925
macro inside . . . 166, 446
Misplaced \noalign . . . 167, 447
Misplaced alignment tab character &
macros . . . 165, 445
rules . . . 344
\multicolumn with \multirow . . . 167
multirow \mrowcell and \mcolrowcell . . . 167
\newcolumntype . . . 166, 446
numbering . . . 1252
row corruption . . . 166, 446
rules . . . 167, 447
S column . . . 167, 447
tcolorbox . . . 130
Temporary page … unable to guess … . . . 197
tensor . . . 1168
TeX capacity exceeded
Text input levels equals 15 . . . 197
TeXMaths . . . 186
text
&, <, > . . . 124, 610
\bfseries etc. . . . 124, 610
corrupted . . . 103
Text input levels equals 15 . . . 197
textcomp
missing symbols . . . 125, 1171
\textquoteright invalid in math mode . 198
\theauthor and authblk . . . 421, 422
theorem
cref reference format undefined . . . 157
threeparttablex . . . 169
tikz
in math . . . 157
matrices, & . . . 161, 1184
title
affiliation . . . 422
newlines . . . 121
\thanks . . . 421
titledframe . . . 173
titling
authblk . . . 135, 421, 676, 1193
hooks . . . 429
tocloft
chapter titles . . . 135, 152, 666, 1201
todonotes . . . 176, 933, 1208
Token not allowed in a PDF string . . . 198
tracing lwarp . . . 200
tram . . . 1210
transparent . . . 1211

U

Undefined control seq … begindocument
polyglossia . . . 175, 636
Unicode
fonts . . . 103
UTF-8 locale . . . 181
unicode-math . . . 1218
units . . . 159
UNIX . . . 119, 229
URL
Missing $ inserted . . . 197
\usebox . . . 126
UTF-8
locale . . . 181

V

varioref . . . 132
verbatim
footnote . . . 134
framed . . . 129, 793
VerbatimFootnotes . . . 134, 794, 801
verse
spacing . . . 174, 432, 1227
verse
margin . . . 175, 432, 1227
version numbers
with memoir . . . 173, 1264
video . . . 164
viewport . . . 161, 593

W

warning messages . . . 194
warpall . . . 120, 196

warpHTML 120, 196
warpMathJax 120, 196
warpprint 120, 196
Windows 119, 230
word processor
  import 184
  sectioning headings 187

X

xcite 97
xeLaTeX 103
xfakebold 1249
xfrac 1249
xindy
  and hyperref 151
  options
    HTMLIndexCmd 109
    LatexmkIndexCmd 109
    PrintIndexCmd 108
xltabular
  numbering 1252
xr 97
xr-hyper 97
xstring 246

Index of Indexes

C

Change History 1314

G

General Index 1377

I

Index of Objects 1353

T

Troubleshooting Index 1382