

More Titlepage Styles with Package `uni-titlepage`*

Markus Kohm[†]

v0.6[‡]2021/08/16

Creation of title pages is something most authors should not have to do. But reality is not perfect, so a lot of authors have to do it. In 2009 KOMA started the title page project at <https://komascript.de/titlepage> to collect real title pages and implement them with a well defined interface. In 2021 the project has been moved to <https://github.com/komascript/uni-titlepage> and renamed.

Now, changing from one title page style to another would be very simple. Nevertheless implementation of a new title page style may be still difficult. But maybe the guys of the title page project would help you. Just ask!

Contents

1	Loading the Package	2
2	The Title Page Styles and their Options	2
2.1	Style DHBW	7
2.2	Style KOMAScript	8
2.3	Style Markus-1	10
2.4	Style Markus-2	12
2.5	Style Spacer	14
2.6	Style TU-DD	16
2.7	Style TU-HH	17
2.8	Style KIT	19
2.9	Style JT-Aufsaetze	20

*This is file version v0.6 of file `uni-titlepage.drv`.

[†]Markus Kohm <komascript@gmx.info>

[‡]**Note:** All version below 0.9 are ALPHA versions. Everything may change. Everything may break. Everything may happen.

2.10 Style JT-Geschichte	21
2.11 Style JT-Typography	22
2.12 Style WWUM	23
3 Additional Commands	24
4 Implementation	25
4.1 The Installation Driver ‘uni-titlepage.ins’	25
4.2 The Package ‘scrbase.sty’	27
4.3 The titlepage Drivers	39
4.4 The Examples and the Manual	56

1 Loading the Package

You may load this package like all the other package, simply using:

```
\usepackage{uni-titlepage}
```

This package declares several options for title page manipulation. We will declare all those options in the following. Most of the options are package options as well, but some are style options only. You may use every package option already as optional argument of `\usepackage` and even of `\documentclass`. But in most cases it would be better to use them as optional argument of `\TitlePageStyle` or `\maketitle`. We show this way below.

2 The Title Page Styles and their Options

TitlePageStyle Several title page styles are supported. You may select a title page style using:

```
\TitlePageStyle[<option>=<value>,...] {<style>}.
```

The available styles are shown at the following sub-sections. Options may be every package option and every style option.

maketitle After loading a style you may generate title pages using:

```
\maketitle[<option>=<value>,...].
```

Again, you may use every package option and every style option as optional argument.

TitleOption Another way to set an option is to use either
TitleOptions

```
\TitleOption{<option>}{<value>}
```

or

`\TitleOptions{⟨option⟩=⟨value⟩,...}`.

You can set every package option and every option of already loaded title page styles.

For every option, that expects a string argument exists a corresponding command with the same name. So you may set, e.g., the title either using `\TitleOptions{title={This is the Title}}` or `\TitleOption{title}{This is the Title}` or `\maketitle[title={This is the Title}]` or `\TitlePageStyle[title={This is the Title}]{...}` or `\title{This is the Title}`. The most robust way is to use the command `\title` instead of the option at one of the other commands! If you use the option you may need to add `\protect` in front of commands inside the option value!

<i>String Option</i>	<i>Styles</i>	<i>Common Meaning</i>
advisor	TU-DD	if your personal advisor differs from the advising professor, this is the name of the advisor
author	<i>every style</i>	the authors, with some styles (currently not with DHBW) you may separate multiple authors by <code>\and</code>
chair	TU-DD, KIT, WWUM	the chair of the faculty of the university where you've made or presented your work
company	DHBW	some works are made not only at a university but in cooperation with a company; at Duale Hochschule Baden-Württemberg this is the default case
course	DHBW	the shortcut for your discipline or course

...

<i>String Option</i>	<i>Styles</i>	<i>Common Meaning</i>
date	DHBW, KIT, KOMAScript, Markus-1, Markus-2, Spacer, TU-HH, TU-DD, JT-Typography, WWUM	the documents main date, this may be, e.g., the release date, the semester of a thesis or any other most valid date
dedication	KOMAScript, Markus-1, Markus-2, Spacer	sometimes it is nice to dedicate the work to someone, e.g., your wife, your children, your grandmother or your first love
academicgrade	DHBW, TU-HH, WUMM	the academic grade or degree you reach with the work
discipline	DHBW, TU-DD, WUMM	the discipline in which you've made your work or reach your academic grade
duration	DHBW	the processing time for your work
faculty	TU-DD, KIT, WUMM	the faculty of the univer- sity where you've made or presented your work
homepage	KIT	the www-address of the homepage
mainlogo	DHBW, KIT	a logo at the main ti- tle (currently used for the DHBW or the KIT logo at the default of <code>titlehead</code>)
matriculationnumber	DHBW, TU-DD	if you were a student while you've made the work, this is your number
oralexaminationdate	TU-HH, WUMM	sometimes the date of the oral examination is not the main date but has to be shown too

...

<i>String Option</i>	<i>Styles</i>	<i>Common Meaning</i>
place	DHBW, TU-HH, JT-Geschichte, JT-Typography, WUMM	the place, in general the city, where you've made the work or where the Duale Hochschule or the publisher resides
professor	TU-DD, WUMM	the name of the professor who advised you during your work
publisher	KOMAScript, Markus-1, Markus-2, Spacer, JT-Aufsätze, JT-Geschichte, JT-Typography	most written works have a publisher
referee	DHBW, TU-HH	every academic work will be referred; with some styles (currently TU-HH, WWUM) multiple referees may be separated with <code>\and</code>
science	WWUM	kind of science, e. g., "Naturwissenschaften"
student	<i>see author</i>	same like author
subject	<i>every style</i>	the kind of work, there are special predefined subjects; if you use one of bachelor , academicgrade , diploma , master , project , seminar , or studentresearch a language dependend replacement will be done; to avoid this, you may set the value in parenthesis
subtitle	KOMAScript, Markus-1, Markus-2, Spacer, TU-HH	the sub-title of the document

...

<i>String Option</i>	<i>Styles</i>	<i>Common Meaning</i>
<code>title</code>	<i>every style</i>	the main title of the document
<code>titlehead</code>	DHBW, KOMAScript, Markus-2, Spacer, KIT	page head over the main title of the document
<code>university</code>	DHBW, TU-DD, TU-HH, KIT, WWUM	the university where you've made or presented your work


Let's have a look at the already defined title page styles. You should find an example L^AT_EX file for each of them at the documentation folder. If not, ask your distributor or administrator for those! But you may find the code of all examples in `docstrip` syntax even at [subsection 4.4](#) starting at [page 56](#). At the shown examples most variable contents was made red.

2.1 Style DHBW

Josef Schmidbauer asked me for a title page usable for bachelor thesis at the “Duale Hochschulen Baden-Württemberg”. This is a only one title page style.

The page (in example `titlepage-DHBW.tex`) is:

1. main title page with `titlehead`, `mainlogo`, `title`, `subject`, `academicgrade`, `discipline`, `place`, `author`, `duration`, `matriculationnumber`, `course`, `company`, `referee`, `university`, and `date`.



The image shows a template for a bachelor thesis title page. It features a red rectangular placeholder for a logo in the top right corner. The text is centered and includes fields for the subject, academic grade, discipline, place, author, duration, matriculation number, course, company, referee, university, and date. The text is in a sans-serif font, with some fields in red and others in black. The layout is clean and professional.

Bachelorarbeitsthema

BACHELORARBEIT

für die Prüfung zum
Bachelor of Engineering

des Studienganges **Studiengang**
an der Dualen Hochschule Baden-Württemberg **Stadt**

von
Vorname Nachname

Abgabedatum

Bearbeitungszeitraum	12 Wochen
Matrikelnummer, Kurs	Matrikelnummer, Kurskürzel
Ausbildungsfirma	Firmenname, Stadt
Betreuer der Ausbildungsfirma	Titel Vorname Nachname
Gutachter der Dualen Hochschule	Titel Vorname Nachname

Note: The upper right corner is the logo placeholder. If you'd download the logo from the DHBW homepage <http://www.dhbw.de> and save it with the name `DHBW_d_MOS_195x95_rgb_300.jpg` it would be used automatically. The logo file is also available from https://de.wikipedia.org/wiki/Datei:DHBW_d_MOS_195x95_rgb_300.jpg. This original logo has a large white border, so it would be much smaller than the red box at the example. The example file also contains comments for an optional company logo at the upper left corner.

2.2 Style KOMAScript

This is a style similar to the title pages of KOMA-Script classes.

The pages (in twoside example `titlepage-KOMAScript.tex`) are:

- 1. defined by `extratitle`, which is not a package option but a style option. You may set it using `\TitleOption` or `\TitleOptions` after loading the style or with the optional argument of `\maketitle` or `\TitlePageStyle`.
- 2. empty and only in twoside mode with `extratitle` used.
- 3. main title page with `titlehead`, `subject`, `title`, `subtitle`, `author`, `date`, `publisher`. You may use `\thanks` at any of these.

Das ist ein Schaustitel im Stil KOMAScript

Den Kopfbereich kann man auf diese Weise füllen.

Eine Klassifizierung der Arbeit

Titel im Stil KOMAScript

Untertitel

Einen Verlag kann man ebenfalls angeben

<p>Oberer Bereich der Rückseite des Haupttitels im Stil KOMAScript.</p> <p>Unterer Bereich der Rückseite des Haupttitels im Stil KOMAScript.</p>	<p>Eine Widmung im Stil KOMAScript</p>
	<ol style="list-style-type: none"> 4. only in twoside mode defined by <code>uppertitleback</code> and <code>lowertitleback</code>, which are not package options but style options. You may set them using <code>\TitleOption</code> or <code>\TitleOptions</code> after loading the style or with the optional argument of <code>\maketitle</code> or <code>\TitlePageStyle</code>. 5. optional post title with <code>dedication</code>. 6. empty and only in twoside mode with <code>dedication</code> used.

2.3 Style Markus-1

This is a style similar to the one of the title of the KOMA-Script book.

The pages (in twoside example `titlepage-Markus-1.tex`) are:

1. defined by `publisher`; may be omitted by `publisher={}`.
2. only in twoside mode with `publisher` defined by `author`.
3. main title page with `subject`, `title`, `subtitle`, and `date`.

	<div>Verlag</div>
<div>Markus Kohn Sonst Jemand</div>	<div>Eine Klassifizierung der Arbeit</div> <div>Titel im Stil Markus-1</div> <div>Untertitel</div>

<p>Oberer Bereich der Rückseite des Haupttitels im Stil <code>Markus-1</code>.</p> <p>Unterer Bereich der Rückseite des Haupttitels im Stil <code>Markus-1</code>.</p>	<p>Eine Widmung im Stil <code>Markus-1</code>.</p>
	<ol style="list-style-type: none"> 4. only in twoside mode defined by <code>uppertitleback</code> and <code>lowertitleback</code>, which are not package options but style options. You may set them using <code>\TitleOption</code> or <code>\TitleOptions</code> after loading the style or with the optional argument of <code>\maketitle</code> or <code>\TitlePageStyle</code>. 5. optional post title with <code>dedication</code>. 6. empty and only in twoside mode with <code>dedication</code> used.

2.4 Style Markus-2

This style is not a real live style, but similar styles are often used:

The pages (in twoside example `titlepage-Markus-2.tex`) are:

1. defined by `extratitle`.
2. empty and only in twoside mode with `extratitle` used.
3. main title page with `titlehead` placed at the page head (if this is to high, it might be put outside the page; if it is to deep, it might overwrite parte of the title), `rulewidth` and `rulesep` for the vertical rule (these aren't package options but style options), `subject`, `title`, `subtitle`, `author`, `date`, and `publisher`.

Das ist ein Schaumtitel im Stil Markus-2

Eine Klassifizierung der Arbeit

Markus Kohn

Titel im Stil Markus-2

Untertitel

Verlag

<p>Oberer Bereich der Rückseite des Haupttitels im Stil <code>Markus-2</code>.</p> <p>Unterer Bereich der Rückseite des Haupttitels im Stil <code>Markus-2</code>.</p>	<p>Eine Widmung im Stil <code>Markus-2</code></p>
	<ol style="list-style-type: none"> 4. only in twoside mode defined by <code>uppertitleback</code> and <code>lowertitleback</code>, which are not package options but style options. You may set them using <code>\TitleOption</code> or <code>\TitleOptions</code> after loading the style or with the optional argument of <code>\maketitle</code> or <code>\TitlePageStyle</code>. 5. optional post title with <code>dedication</code>. 6. empty and only in twoside mode with <code>dedication</code> used.

2.5 Style Spacer

This style is a variant of style Markus-2 from [subsection 2.4](#). It was asked by `spacer2012` at the original `titlepage` project on <https://komascript.de/titlepage>. In difference to Markus-2 the title head will not be placed at the page head but at the body.

The pages (in twoside example `titlepage-Spacer.tex`) are:

1. defined by `extratitle`.
2. empty and only in twoside mode with `extratitle` used.
3. main title page with `titlehead` placed at the page head, `rulewidth` and `rulesep` for the vertical rule (these aren't package options but style options), `subject`, `title`, `subtitle`, `author`, `date`, and `publisher`.

Das ist ein Schautitel im Stil Spacer



Eine Klassifizierung der Arbeit

Markus Köhm

Titel im Stil Spacer

Untertitel

Verlag

<p>Oberer Bereich der Rückseite des Haupttitels im Stil <code>Spacer</code>.</p> <p>Unterer Bereich der Rückseite des Haupttitels im Stil <code>Spacer</code>.</p>	<p>Eine Widmung im Stil <code>Spacer</code></p>
	<ol style="list-style-type: none"> 4. only in twoside mode defined by <code>uppertitleback</code> and <code>lowertitleback</code>, which are not package options but style options. You may set them using <code>\TitleOption</code> or <code>\TitleOptions</code> after loading the style or with the optional argument of <code>\maketitle</code> or <code>\TitlePageStyle</code>. 5. optional post title with <code>dedication</code>. 6. empty and only in twoside mode with <code>dedication</code> used.

2.6 Style TU-DD

This style is used at the “Technische Universität Dresden”. I was asked for this several years ago. Only one title page is defined!

The page (in example `titlepage-TU-DD.tex`) is:

1. main title page with `university`, `faculty`, `chair`, `professor`, `title`, `subject`, `author`, `discipline`, `matriculationnumber`, `advisor`, `place`, and `date`.

Technische Universität Dresden
Fakultät Wirtschaftswissenschaften
SAP-Stiftungslehrstuhl für
Entrepreneurship und Innovation
Prof. Dr. Michael Schefczyk

Titel im Stil TU-DD
Seminararbeit
(bzw. Diplomarbeit)

eingereicht von
Vorname und Name
Studienrichtung
Matrikel-Nr.

Betreuer:
(mit akadem. Grad, Vor- und Zuname)

Dresden, den (Datum der Abgabe)

But there is another variant. If option `blackborder` was set to true, a black border is put around the page:

The page (in example `titlepage-TU-DD.tex` with option `blackborder`) is:

1. main title page with `university`, `faculty`, `chair`, `professor`, `title`, `subject`, `author`, `discipline`, `matriculationnumber`, `advisor`, `place`, and `date`.

Technische Universität Dresden
Fakultät Wirtschaftswissenschaften
SAP-Stiftungslehrstuhl für
Entrepreneurship und Innovation
Prof. Dr. Michael Schefczyk

Titel im Stil TU-DD
Seminararbeit
(bzw. Diplomarbeit)

eingereicht von
Vorname und Name
Studienrichtung
Matrikel-Nr.

Betreuer:
(mit akadem. Grad, Vor- und Zuname)


Dresden, den (Datum der Abgabe)

2.7 Style TU-HH


This style is used at the “Technische Universität Hamburg-Harburg”. I was asked for this several years ago. Only two title pages are defined!

The pages (in twoside example `titlepage-TU-HH.tex`) are:

1. main title page with `title`, `subtitle`, `university`, `academicgrade`, `subject`, `author`, `place`, and `date`. Some additional text depending on the selected language will be used also.



2. only in twoside mode with `referee` and `oralexaminationdate`.



The output of style TU-HH differs, if you use option `final`, which is a style option, not a package option. You may set it using `\TitleOption`

or `\TitleOptions` after loading the style or with the optional argument of `\maketitle` or `\TitlePageStyle`.


2.8 Style KIT

This style is used at the “KIT – University of the State of Baden-Württemberg and National Research Center of the Helmholtz Association”. I’ve made this because of the ugly L^AT_EX class and template made by the KIT itself. Only one title page is defined!

The page (in example `titlepage-KIT.tex`) is:

1. main title page with `titlehead`, `mainlogo`, `title`, `subject`, `author`, `referee`, `advisor`, `university`, `duration`, and `homepage`. Some additional text depending on the selected language will be used also.

If `titlehead` is empty or unused left aligned `mainlogo` will be used. If `mainlogo` is empty or unused, and if you have a logo file `KITLogo_RGB.pdf`, this will be used. As an alternative also `2560px-Logo_KIT.svg.png`, `2000px-Logo_KIT.svg.png`, `1280px-Logo_KIT.svg.png`, `1024px-Logo_KIT.svg.png`, `1000px-Logo_KIT.svg.png`, `800px-Logo_KIT.svg.png`, `640px-Logo_KIT.svg.png`, or `500px-Logo_KIT.svg.png` from https://de.wikipedia.org/wiki/Datei:Logo_KIT.svg would be auto-detected. Several other elements will be set to defaults too, if they are empty. So you don’t need to set all the elements, that has been set at the example file.




2.9 Style JT-Aufsaetze

The style is based on the front cover of “Jan Tschichold: Ausgewählte Aufsätze über Fragen der Gestalt des Buches und der Typographie, Birkhäuser Verlag Basel, 1975, ISBN: 3-7643-1946-1”. I’ve made this, because the book is a major book of classic typography. It seems to be old fashioned and indeed it is. Note, that the front cover of a book and the main title of a book are not the same! Nevertheless, here I’ve made a main title from a front cover. Currently only one title page is defined, but you may also use `extratitle`, `uppertitleback`, and `lowertitleback`.

The page (in example `titlepage-JT-Aufsaetze.tex`) is:

1. main title page with `author`, `title`, `publisher`, `rulewidth` and `rulesep` for width of the horizontal rules and the distance between them (these aren’t package options but style options).




2.10 Style JT-Geschichte

The style is based on “Jan Tschichold: Geschichte der Schrift in Bildern; Holbein-Verlag, 1947”. This is another major book of classic typography. It seems to be old fashioned and indeed it is. Currently only one title page is defined, but you may also use `extratitle`, `uppertitleback`, and `lowertitleback`.

The page (in example `titlepage-JT-Geschichte.tex`) is:

1. main title page with `author`, `title`, `publisher`, `place`, `rulewidth` and `rulesep` for width of the horizontal rules and the distance between them (these aren't package options but style options).

Note, that the default for `titlepagefont` prints everything but the `title` with ad-hoc letterspacing in upper-case letters if `\lsstyle` is available and without letterspacing but in small capitals otherwise. Changing the default of `titlepagefont` will also change this automatism.



2.11 Style JT-Typography

The style is based on “Jan Tschichold: The New Typography; University of California Press, Berkley and Los Angeles, California 1995”. This is the English translation of another major book of classic typography. Some things like missing letterspacing at the upper-case title seems to be wrong. Currently only one title page is defined, but you may also use `extratitle`, `uppertitleback`, and `lowertitleback`.

The page (in example `titlepage-JT-Geschichte.tex`) is:

1. main title page with author, title, subtitle, place, date, publisher.



2.12 Style WWUM

Tobias Südkamp asked me for that title for the Westfälischen Wilhelms-Universität Münster. The `professor` is more likely the `chairman`. Female referees should be prefixed by `[f]`. You can omit the examination date defining an empty `\examinationdate`.

<div>Mein Name Titel der Arbeit 2021</div>	<div>The pages (in example <code>tilepage-WWUM.tex</code>) are:</div> <div><div>1. cover page with <code>author</code>, <code>title</code>, <code>\the\year</code></div><div>2. the backside of the cover page is empty if it exists</div><div>3. main title page with <code>chair</code>, <code>title</code>, <code>subject</code>, <code>academicgrade</code>, <code>science</code>, <code>discipline</code>, <code>faculty</code></div><div>4. main title back side with <code>professor</code>, <code>referee</code>, <code>oralexaminationdate</code> (normally empty)</div></div>
<div>Experimentelle Physik</div> <div>Titel der Arbeit</div> <div>Inaugural-Dissertation zur Erlangung des Doktorgrades der Naturwissenschaften im Fachbereich Physik der Mathematisch-Naturwissenschaftlichen Fakultät der Westfälischen Wilhelms-Universität Münster</div> <div>vorgelegt von Mein Name aus Geburtsort - 2021 -</div>	<div>Dekan/Dekanin: Klaus Naeschenwanz</div> <div>Erster Gutachter: Peter Mustermann</div> <div>Zweite Gutachterin: Petra Musterfrau</div> <div>Datum der mündlichen Prüfung:</div> <div>Tag der Promotion:</div>

3 Additional Commands

`\NowButAfterBeginDocument` Command

```
\NowButAfterBeginDocument{<code>}
```

is something like `\AtBeginDocument`, but if you call it somewhere after `\begin{document}` argument `<code>` will be used immediately. This command is used inside some of the title page styles, because you may load them either at the preamble or even after `\begin{document}`, but some code should not be executed before `\begin{document}`.

`titlepage` In oposite to the `titlepage` environment of the standard classes,

```
\begin{titlepage}[<options>]
```

```
...
```

```
\end{titlepage}
```

knows some options. These are `pagestyle=<style>` and `pagenumber=<number>`. The first one changes the page style of the generated title page to the given `<style>`. If the option is not set, the default `empty` will be used. The second one sets the logical page number of the generated title page to the given `<number>` and sets the counter `pagenumber` to this value. If the option is not used, the value of counter `pagenumber` will be increased by one and the result is used for the logical page number.

`fullsizetitle` Using

```
\begin{fullsizetitle}[<options>]
```

```
...
```

```
\end{fullsizetitle}
```

is almost the same like above. But `fullsizetitle` removes the margins from the generated title page. Nevertheless if binding correction (aka binding offset) of package `typearea` or `geometry` could be recognized, it will not be removed. Some of the title page styles use this environment instead of `titlepage` inside `\maketitle`. With this the margins of the title page do not depend on the type area of the document.

`\usetitleelement` Command

```
\usetitleelement{<element>}
```

gives the content of the corresponding title `<element>`. Each main `<element>` defined by the package may be used. Those are currently: `advisor`, `author`, `chair`, `company`, `course`, `date`, `dedication`, `academicgrade`, `discipline`, `duration`, `faculty`, `homepage`, `mainlogo`, `matriculationnumber`, `oralexaminationdate`, `place`, `professor`, `publisher`, `referee`, `subject`, `subtitle`, `title`, `titlehead`, and `university`. Note: `student` isn't a main `<element>`, because it's only an alias for `author`.

4 Implementation

Note: To generate all files, developers and beta testers should simply use the source from <https://github.com/komascript/uni-titlepage> and call

```
l3build unpack
l3build doc
```

The resulting documentation will be placed in the main folder. The unpacked style file are in `build/unpacked`, You can use

```
l3build install
```

to install them in `TEXMFHOME`. See the manual of `l3build` for more information.

As an alternative you can use the source distribution from CTAN and run:

```
tex uni-titlepage.dtx
```

The documentation is usually part of the source distribution at CTAN. Note, that all the generated `tex` files are example files. Do not copy them to the run-time files but the documentation folder!

4.1 The Installation Driver ‘uni-titlepage.ins’

First of all we produce `uni-titlepage.ins`, the installation driver. It starts very common with loading `docstrip`, preamble declaration and start of generation.

```
1 \def\batchfile{uni-titlepage.dtx}
2 \input docstrip.tex
3 \ifToplevel{%
4   \Msg{*****}
5   \Msg{*}
6   \Msg{* Steps of uni-titlepage generation:}
7   \Msg{* =====}
8   \Msg{*}
9   \Msg{* - Generation of all needed files:}
10  \keepsilent
11  \askforoverwritefalse
12 }
13
14 \preamble
15 Copyright (c) 2009–2021 by Markus Kohm <komascript(at)gmx.info>
16
```

```

17 This file was generated from file(s) of uni-titlepage distribution.
18
19 -----
20
21 This work may be distributed and/or modified under the conditions of
22 the LaTeX Project Public License, version 1.3c of the license.
23 The latest version of this license is in
24 http://www.latex-project.org/lppl.txt
25 and version 1.3c or later is part of all distributions of LaTeX
26 version 2005/12/01 or later.
27
28 This work has the LPPL maintenance status "maintained".
29
30 The Current Maintainer and author of this work is Markus Kohm.
31
32 This file may only be distributed together with
33 the file 'uni-titlepage.dtx'.
34 You may however distribute the file 'uni-titlepage.dtx' without this file.
35
36 \endpreamble
37
38 \generate{%

```

But while the dtx file is the ins file itself, we will never generate this file.

```

39 % \file{uni-titlepage.ins}{\from{uni-titlepage.dtx}{ins}}% not needed
40 \file{uni-titlepage.drv}{\from{uni-titlepage.dtx}{doc,manual}}%
41 \file{uni-titlepage.sty}{\from{uni-titlepage.dtx}{package}}%
42 \file{title-DHBW.def}{\from{uni-titlepage.dtx}{driver,DHBW}}%
43 \file{title-KOMAScript.def}{\from{uni-titlepage.dtx}{driver,KOMAScript}}%
44 \file{title-Markus-1.def}{\from{uni-titlepage.dtx}{driver,Markus,1}}%
45 \file{title-Markus-2.def}{\from{uni-titlepage.dtx}{driver,Markus,2}}%
46 \file{title-Spacer.def}{\from{uni-titlepage.dtx}{driver,Spacer}}%
47 \file{title-TU-DD.def}{\from{uni-titlepage.dtx}{driver,TU-DD}}%
48 \file{title-TU-HH.def}{\from{uni-titlepage.dtx}{driver,TU-HH}}%
49 \file{title-KIT.def}{\from{uni-titlepage.dtx}{driver,KIT}}%
50 \file{title-JT-Aufsaetze.def}{\from{uni-titlepage.dtx}{driver,JT-Aufsaetze}}%
51 \file{title-JT-Geschichte.def}{\from{uni-titlepage.dtx}{driver,JT-Geschichte}}%
52 \file{title-JT-Typography.def}{\from{uni-titlepage.dtx}{driver,JT-Typography}}%
53 \file{title-WWUM.def}{\from{uni-titlepage.dtx}{driver,WWUM}}%
54 \file{titlepage-DHBW.tex}{\from{uni-titlepage.dtx}{doc,example,DHBW}}%
55 \file{titlepage-KOMAScript.tex}{\from{uni-titlepage.dtx}{doc,example,KOMAScript}}%
56 \file{titlepage-Markus-1.tex}{\from{uni-titlepage.dtx}{doc,example,Markus,1}}%
57 \file{titlepage-Markus-2.tex}{\from{uni-titlepage.dtx}{doc,example,Markus,2}}%
58 \file{titlepage-Spacer.tex}{\from{uni-titlepage.dtx}{doc,example,Spacer}}%
59 \file{titlepage-TU-DD.tex}{\from{uni-titlepage.dtx}{doc,example,TU-DD}}%
60 \file{titlepage-TU-HH.tex}{\from{uni-titlepage.dtx}{doc,example,TU-HH}}%
61 \file{titlepage-KIT.tex}{\from{uni-titlepage.dtx}{doc,example,KIT}}%
62 \file{titlepage-JT-Aufsaetze.tex}{\from{uni-titlepage.dtx}{doc,example,JT-Aufsaetze}}%
63 \file{titlepage-JT-Geschichte.tex}{\from{uni-titlepage.dtx}{doc,example,JT-Geschichte}}%
64 \file{titlepage-JT-Typography.tex}{\from{uni-titlepage.dtx}{doc,example,JT-Typography}}%

```

```

65 \file{titlepage-WWUM.tex}{\from{uni-titlepage.dtx}{doc,example,WWUM}}%
66 \nopreamble\nopostamble
67 \file{README.md}{\from{uni-titlepage.dtx}{README}}%
68 }%
69
70 \ifToplevel{%
71 \Msg{* \space\space done.}
72 \Msg{*}
73 \Msg{* You may install all the files now.}
74 \Msg{*}
75 \Msg{*****}
76 }

```

At docstrip run we like to finish the file know:

```
77 \csname endinginput\endcsname
```

4.2 The Package ‘scrbase.sty’

`\TitleOptions` We use the extended option handling of KOMA-Script, so we load package `scrbase` and declare a family, a member and a something like `\KOMAoptions` and `\KOMAoption` but for this package.

```

78 \RequirePackage{scrbase}[2014/12/03]
79 \DefineFamily{title}
80 \DefineFamilyMember{title}
81 \newcommand*{\TitleOptions}{\FamilyOptions{title}}
82 \newcommand*{\TitleOption}{\FamilyOption{title}}

```

`pagenumber`

```

83 \newcounter{titlepage}\setcounter{titlepage}{\@ne}
84 \DefineFamilyKey{title}{pagenumber}{%
85 \setcounter{titlepage}{\the#1}\FamilyKeyStateProcessed
86 }

```

`\titlepagestyle`

`pagestyle`

```

87 \providecommand*{\titlepagestyle}{}
88 \renewcommand*{\titlepagestyle}{empty}
89 \DefineFamilyKey{title}{pagestyle}{%
90 \renewcommand*{\titlepagestyle}{\the#1}\FamilyKeyStateProcessed
91 }

```

`\if@restonecol`

```

92 \ifcsname @restonecolfalse\endcsname
93 \expandafter\@gobble
94 \else
95 \expandafter\@firstofone
96 \fi
97 {\newif\if@restonecol}

```

```

titlepage
    98 \scr@ifundefinedorrelax{titlepage}{\def\tITLEPAGE{}}{}
    99 \scr@ifundefinedorrelax{endtitlepage}{\def\ENDTITLEPAGE{}}{}
    100 \providecommand*\maketitle[1][]{\}

\inittitle Set of commands, that define a title style:
\makeprettitle 101 \newcommand*\tp@undefinedtitle[1]{%
\makeprettitleback 102 \PackageInfo{uni-titlepage}{leaving not defined #1-title page empty}%
\makemainttitle 103 }
\makemainttitleback 104 \newcommand*\inittitle{}
\makeposttitle 105 \newcommand*\makeprettitle{\tp@undefinedtitle{pre}}
\makeposttitleback 106 \newcommand*\makeprettitleback{\tp@undefinedtitle{back of pre}}
\exittitle 107 \newcommand*\makemainttitle{\tp@undefinedtitle{main}}
\tp@undefinedtitle 108 \newcommand*\makemainttitleback{\tp@undefinedtitle{back of main}}
109 \newcommand*\makeposttitle{\tp@undefinedtitle{post}}
110 \newcommand*\makeposttitleback{\tp@undefinedtitle{back of post}}
111 \newcommand*\exittitle{}

\inittitlestyle Will be called before loading a title style:
112 \newcommand*\inittitlestyle{%
113 \renewenvironment{titlepage}[1][]{%
114 \TitleOptions{##1}%
115 \clearpage
116 \if@twocolumn
117 \@restonecoltrue\onecolumn
118 \else
119 \@restonecolfalse
120 \fi
121 \ifx\tITLEPAGEstyle\@empty\else\thispagestyle\tITLEPAGEstyle\fi
122 \if@twoside% im einseitigen Satz ist mir alles egal
123 \ifodd\value{page}% aktuelle Seite ist ungerade

Current page number is odd ...
124 \ifodd\value{titlepage}%
125 \else

... wanted page number is even: put in empty page.
126 \null\newpage
127 \fi
128 \else

Current page number is even ...
129 \ifodd\value{titlepage}%

... wanted page number is off: put in empty page.
130 \null\newpage % Leerseite
131 \fi
132 \fi
133 \fi
134 \setcounter{page}{\value{titlepage}}%

```

```

135 \ifx\titlepagestyle\@empty\else\thispagestyle{\titlepagestyle}\fi
136 }{%
137 \if@restonecol\twocolumn \else \newpage\fi
138 \stepcounter{titlepage}%
139 }%
140
141 \renewcommand*{\maketitle}[1] []{%
142 \begin{group}
143 \TitleOptions{##1}%
144 \inittitle
145 \makeprettitle\if@twoside\makeprettitleback\fi
146 \makemainttitle\if@twoside\makemainttitleback\fi
147 \makeposttitle\if@twoside\makeposttitleback\fi
148 \exittitle
149 \endgroup
150 }%
151
152 \renewcommand*{\inittitle}{}%
153 \renewcommand*{\makeprettitle}{\tp@undefinedtitle{pre}}%
154 \renewcommand*{\makeprettitleback}{\tp@undefinedtitle{back of pre}}%
155 \renewcommand*{\makemainttitle}{\tp@undefinedtitle{main}}%
156 \renewcommand*{\makemainttitleback}{\tp@undefinedtitle{back of main}}%
157 \renewcommand*{\makeposttitle}{\tp@undefinedtitle{post}}%
158 \renewcommand*{\makeposttitleback}{\tp@undefinedtitle{back of post}}%
159 \renewcommand*{\exittitle}{}%
160 }
161 \inittitlestyle

```

`\titlebox` New environment for full page titles (with respect to BCOR or Gm@bindingoffset
`fullsizetitle` if defined)

```

162 \newsavebox\titlebox
163 \newenvironment{fullsizetitle}[1] []{%
164 \TitleOptions{#1}%
165 \begin{lrbox}{\titlebox}
166 \hsize\paperwidth
167 \scr@ifundefinedorrelax{ta@bcor}{%
168 \scr@ifundefinedorrelax{Gm@bindingoffset}}{%
169 \advance\hsize-\Gm@bindingoffset}%
170 }{%
171 \advance\hsize-\ta@bcor
172 \scr@ifundefinedorrelax{Gm@bindingoffset}}{%
173 \ifdim \Gm@bindingoffset=\ta@bcor\else
174 \PackageWarning{uni-titlepage}{Ignoring geometry's binding
175 correction,\MessageBreak
176 using typearea's binding correction.\MessageBreak
177 If you're using geometry and typearea,\MessageBreak
178 you should set both options to the same value,\MessageBreak
179 e.g. \string\KOMAOPTIONS{BCOR=\the\ta@bcor}\MessageBreak
180 \space\space\space\space\space

```

```

181         \string\geometry{bindingoffset=\the\ta@bcor}\MessageBreak
182         to make uni-titlepage use this value%
183     }%
184     \fi
185 }%
186 }%
187 \vsize\paperheight
188 \linewidth\hsize
189 \columnwidth\hsize
190 \textwidth\hsize
191 \textheight\vsize
192 \noindent\minipage{\hsize}
193 }{%
194     \endminipage
195 \end{lrbox}
196 \begin{titlepage}%
197     \vspace*{-1in}\vskip-\topmargin\vskip-\headheight\vskip-\headsep
198     \vskip-\topskip
199     \raggedright
200     \leavevmode
201     \hskip-1in
202     \ifodd\c@page
203         \hskip-\oddsidemargin
204         \scr@ifundefinedorrelax{ta@bcor}{%
205             \scr@ifundefinedorrelax{Gm@bindingoffset}{}%
206             \hskip\Gm@bindingoffset}%
207         }{\hskip\ta@bcor}%
208     \else
209         \hskip-\evensidemargin
210     \fi
211     \vbox to\z@{\hsize\z@
212         \vskip-\baselineskip
213         \makebox[0pt][l]{\usebox\titlebox}%
214     \vss
215 }%
216 \end{titlepage}
217 }

```

\DefineSimpleTitleKey

Define title page “variables”:

\DefineReplaceTitleKey

\tp@replacewarning

\tp@dokeys

```

218 \newcommand*{\tp@replacewarning}[2]{%
219     \PackageWarning{uni-titlepage}{%
220         Using ‘#2’ instead of ‘#1’,\MessageBreak
221         because ‘#1’ not defined%
222     }%
223 }
224 \newcommand*{\tp@dokeys}{}
225 \newcommand*{\DefineSimpleTitleKey}[2][.\@currname.\@currentx]{%
226     \l@addto@macro\tp@dokeys{\do{#2}}%
227     \expandafter\newcommand\expandafter*\csname @#2\endcsname{}}%

```

```

228 \expandafter\newcommand\expandafter*\csname #2\endcsname[1]{%
229   \expandafter\gdef\csname @#2\endcsname{##1}}%
230 \DefineFamilyKey[{#1}]{title}{#2}{%
231   \csname #2\endcsname{##1}%
232   \FamilyKeyStateProcessed
233 }%
234 }
235 \newcommand*\DefineReplaceTitleKey[3][.\@currname.\@current]{%
236   \DefineFamilyKey[{#1}]{title}{#2}{%
237     \tp@replacewarning{#2}{#3}%
238     \FamilyOptions{title}{#3=##1}%
239   }%
240 }

\titlehead
\@titlehead 241 \providecommand*\@titlehead{}
titlehead 242 \providecommand{\titlehead}[1]{\gdef\@titlehead{#1}}
243 \DefineFamilyKey{title}{\titlehead}{\titlehead{#1}\FamilyKeyStateProcessed}

\homepage
\@homepage 244 \providecommand*\@homepage{}
homepage 245 \providecommand{\homepage}[1]{\gdef\@homepage{#1}}
246 \DefineFamilyKey{title}{\homepage}{\homepage{#1}\FamilyKeyStateProcessed}

\title
\@title 247 \let\@title\relax\let\title\relax\DefineSimpleTitleKey{title}
title
\author
\@author 248 \let\@author\relax\let\author\relax\DefineSimpleTitleKey{author}
author
\date
\@date 249 \let\@date\relax\let\date\relax\DefineSimpleTitleKey{date}
date
\duration
\@duration 250 \DefineSimpleTitleKey{duration}
duration
\course
\@course 251 \DefineSimpleTitleKey{course}
course
\company
\@company 252 \DefineSimpleTitleKey{company}
company
\subtitle
\@subtitle 253 \let\@subtitle\relax\let\subtitle\relax\DefineSimpleTitleKey{subtitle}
subtitle
\university
\@university 254 \DefineSimpleTitleKey{university}
university

```

```

\faculty
\@faculty 255 \DefineSimpleTitleKey{faculty}
  faculty
  \chair
  \@chair 256 \DefineSimpleTitleKey{chair}
    chair
\professor
\@professor 257 \DefineSimpleTitleKey{professor}
  professor
  \subject
  \@subject 258 \providecommand*{\@subject}{\{}
    subject 259 \providecommand*{\subject}[1]{\gdef\@subject{#1}}
      260 \l@addto@macro\tp@dokeys{\do{subject}}%
      261 \DefineFamilyKey{title}{subject}{\%
        262 \Ifstr{#1}{project}{\subject{\projectpapername}}{\%
          263 \Ifstr{#1}{seminar}{\subject{\seminarpapername}}{\%
            264 \Ifstr{#1}{studentresearch}{\subject{\studentresearchname}}{\%
              265 \Ifstr{#1}{diploma}{\subject{\diplomathesisname}}{\%
                266 \Ifstr{#1}{degree}{\subject{\degreethesisname}}{\%
                  267 \Ifstr{#1}{master}{\subject{\masterthesisname}}{\%
                    268 \Ifstr{#1}{bachelor}{\subject{\bachelorthesisname}}{\%
                      269 \subject{#1}%
                    270 }%
                  271 }%
                272 }%
              273 }%
            274 }%
          275 }%
        276 }%
      277 \FamilyKeyStateProcessed
    278 }

\Ifstr For compatibility with old versions of scrbase the macro is provided based
on \ifstr if it has not been defined by scrbase.
279 \providecommand*{\Ifstr}{\ifstr}

student
280 \DefineReplaceTitleKey{student}{author}

\sience
\@sience 281 \DefineSimpleTitleKey{sience}
  sience
\discipline
\@discipline 282 \DefineSimpleTitleKey{discipline}
  discipline
\academicgrade
\@academicgrade 283 \DefineSimpleTitleKey{academicgrade}
  academicgrade

```



```

\matriculationnumber
\@matriculationnumber 284 \DefineSimpleTitleKey{matriculationnumber}
  matriculationnumber
    \advisor
      \@advisor 285 \DefineSimpleTitleKey{advisor}
        advisor
        \referee
      \@referee 286 \DefineSimpleTitleKey{referee}
        referee
        \place
      \@place 287 \DefineSimpleTitleKey{place}
        place
    \publisher
  \@publisher 288 \DefineSimpleTitleKey{publisher}
  publisher 289 \renewcommand*{\@publisher}{\csname @publishers\endcsname}

  \mainlogo
  \@mainlogo 290 \DefineSimpleTitleKey{mainlogo}
    mainlogo
\oralexaminationdate
\@oralexaminationdate 291 \DefineSimpleTitleKey{oralexaminationdate}
  oralexaminationdate
  \dedication
  \@dedication 292 \providecommand*{\@dedication}{}
  dedication 293 \providecommand{\dedication}[1]{\gdef\@dedication{#1}}
  294 \DefineFamilyKey{title}{dedication}{dedication{#1}\FamilyKeyStateProcessed}

  \usetitleelement Users cannot simply use, e.g., \@title, \@mainlogo etc. So we need a
\@usetitleelement@error command to get them:
  295 \newcommand*{\@usetitleelement}[1]{%
  296   \scr@ifundefinedorrelax{#1}{%
  297     \@usetitleelement@error{#1}%
  298   }{%
  299     \scr@ifundefinedorrelax{@#1}{%
  300       \@usetitleelement@error{#1}%
  301     }{%
  302       \@nameuse{@#1}%
  303     }%
  304   }%
  305 }
  306 \newcommand*{\@usetitleelement@error}[1]{%
  307   \PackageError{uni-titlepage}{‘#1’ isn’t a title element}{%
  308     You should use \string\usetitleelement\space for title elements
  309     only!\MessageBreak
  310     If you’ll continue, command will be ignored.}%
  311 }

```

Some variables use their own configurable font:

```

titlepagefont
\@titlepagefont 312 \scr@ifundefinedorrelax{newkomafont}{%
313   \newcommand*{\@titlepagefont}{}%
314 }{%
315   \newkomafont{titlepage}{}%
316 }
317 \DefineFamilyKey{title}{titlepagefont}{%
318   \renewcommand*{\@titlepagefont}{#1}%
319   \FamilyKeyStateProcessed
320 }

subjectfont
\subject@font 321 \providecommand*{\subject@font}{\bfseries}
322 \DefineFamilyKey{title}{subjectfont}{%
323   \renewcommand*{\subject@font}{#1}%
324   \FamilyKeyStateProcessed
325 }

titlefont
\title@font 326 \providecommand*{\titlefont}{\bfseries}
327 \DefineFamilyKey{title}{titlefont}{%
328   \renewcommand*{\titlefont}{#1}%
329   \FamilyKeyStateProcessed
330 }

subtitlefont
\@subtitlefont 331 \providecommand*{\@subtitlefont}{\bfseries}
332 \DefineFamilyKey{title}{subtitlefont}{%
333   \renewcommand*{\@subtitlefont}{#1}%
334   \FamilyKeyStateProcessed
335 }

\TitlePageStyle Load a title page style from file
336 \newcommand*{\TitlePageStyle}[2][{}]{%
337   \IfFileExists{title-#2.def}{%
338     \begingroup
339     \edef\@tempa{\endgroup
340       \noexpand\inittitlestyle
341       \noexpand\makeatletter
342       \noexpand\input{title-#2.def}%
343       \noexpand\catcode'\noexpand\@=\the\catcode'\@
344     }%
345     \@tempa
346     \TitleOptions{#1}%
347   }{%
348     \PackageError{uni-titlepage}{No title definition for ‘#2’ found}{%
349       You’ve tried to set title page style ‘#2’, but no title page
350       style definition file\MessageBreak
351       ‘title-#2.def’ may be found%

```

```

352     }%
353   }
354 }

```

\NowButAfterBeginDocument Nice shortcut:

```

355 \newcommand*{\NowButAfterBeginDocument}{%
356   \if@atdocument
357     \expandafter\@firstofone
358   \else
359     \expandafter\AtBeginDocument
360   \fi
361 }

362 \DeclareOption*{\expandafter\TitlePageStyle\expandafter{\CurrentOption}}
363 \FamilyProcessOptions*\relax

```

\chairmanname Language dependent terms:

```

\projectpapername 364 \providecommand*{\chairmanname}{Chairman}
\seminarpapername 365 \providecommand*{\projectpapername}{Project Paper}
\studentreserchname 366 \providecommand*{\seminarpapername}{Seminar Paper}
\diplomathesisname 367 \providecommand*{\studentresearchname}{Student Research Project}
\degreethesisname 368 \providecommand*{\diplomathesisname}{Diploma Thesis}
\masterthesisname 369 \providecommand*{\degreethesisname}{Degree Thesis}
\bachelorthesisname 370 \providecommand*{\masterthesisname}{Master Thesis}
\presentedbyname 371 \providecommand*{\bachelorthesisname}{Bachelor Thesis}
\advisorname 372 \providecommand*{\presentedbyname}{presented by}
\thename 373 \providecommand*{\advisorname}{Advisor}
\ofthename 374 \providecommand*{\thename}{}
\fromname 375 \providecommand*{\ofthename}{of the}
\fromplacename 376 \providecommand*{\fromname}{from}
\malerefereename 377 \providecommand*{\fromplacename}{from}
\refereename 378 \providecommand*{\malerefereename}{Referee}
\oralexaminationdatename 379 \providecommand*{\femalerefereename}{\refereename}
\ordinal 380 \providecommand*{\malerefereename}{\refereename}
\maleordinal 381 \providecommand*{\oralexaminationdatename}{Date of Oral Examination}
\femaleordinal 382 \providecommand*{\atthename}{at}
383 \providecommand*{\durationname}{Processing Time}
384 \providecommand*{\matriculationnumbername}{Matriculationnumber}
385 \providecommand*{\coursename}{Course}
386 \providecommand*{\companyname}{Training Company}
387 \providecommand*{\examinationname}{Examination}
388 \providecommand*{\examinationdatename}{Date of Examination}
389 \newcommand*{\ordinal}{\englishordinal}
390 \newcommand*{\femaleordinal}{\ordinal}
391 \newcommand*{\maleordinal}{\ordinal}
392 \providcaptionname{american,australian,british,canadian,%
393   english,newzealand,UKenglish,USenglish}{\chairmanname}{Chairmain}%
394 \providcaptionname{american,australian,british,canadian,%
395   english,newzealand,UKenglish,USenglish}{\projectpapername}{Project Paper}%

```

396 \providecaptionname{american,australian,british,canadian,%
 397 english,newzealand,UKenglish,USenglish}{\seminarpapername}{Seminar Paper}%
 398 \providecaptionname{american,australian,british,canadian,%
 399 english,newzealand,UKenglish,USenglish}{\studentresearchname}{Student
 400 Research Project}%
 401 \providecaptionname{american,australian,british,canadian,%
 402 english,newzealand,UKenglish,USenglish}{\diplomathesisname}{Diploma Thesis}%
 403 \providecaptionname{american,australian,british,canadian,%
 404 english,newzealand,UKenglish,USenglish}{\degreethesisname}{Degree Thesis}%
 405 \providecaptionname{american,australian,british,canadian,%
 406 english,newzealand,UKenglish,USenglish}{\masterthesisname}{Master Thesis}%
 407 \providecaptionname{american,australian,british,canadian,%
 408 english,newzealand,UKenglish,USenglish}{\bachelorthesisname}{Bachelor
 409 Thesis}%
 410 \providecaptionname{american,australian,british,canadian,%
 411 english,newzealand,UKenglish,USenglish}{\ordinal}{\englishordinal}%
 412 \providecaptionname{american,australian,british,canadian,%
 413 english,newzealand,UKenglish,USenglish}{\presentedbyname}{presented by}%
 414 \providecaptionname{american,australian,british,canadian,%
 415 english,newzealand,UKenglish,USenglish}{\advisorname}{Advisor}%
 416 \providecaptionname{american,australian,british,canadian,%
 417 english,newzealand,UKenglish,USenglish}{\thename}{}%
 418 \providecaptionname{american,australian,british,canadian,%
 419 english,newzealand,UKenglish,USenglish}{\ofthename}{of the}%
 420 \providecaptionname{american,australian,british,canadian,%
 421 english,newzealand,UKenglish,USenglish}{\fromname}{from}%
 422 \providecaptionname{american,australian,british,canadian,%
 423 english,newzealand,UKenglish,USenglish}{\fromplacename}{from}%
 424 \providecaptionname{american,australian,british,canadian,%
 425 english,newzealand,UKenglish,USenglish}{\refereename}{Referee}%
 426 \providecaptionname{american,australian,british,canadian,%
 427 english,newzealand,UKenglish,USenglish}{\oralexaminationdatename}{Date of
 428 Oral Examination}%
 429 \providecaptionname{american,australian,british,canadian,%
 430 english,newzealand,UKenglish,USenglish}{\durationname}{Processing Time}%
 431 \providecaptionname{american,australian,british,canadian,%
 432 english,newzealand,UKenglish,USenglish}{\matriculationnumbername}{Matriculation
 433 \providecaptionname{american,australian,british,canadian,%
 434 english,newzealand,UKenglish,USenglish}{\coursename}{Course}%
 435 \providecaptionname{american,australian,british,canadian,%
 436 english,newzealand,UKenglish,USenglish}{\companynname}{Training Company}%
 437 \providecaptionname{american,australian,british,canadian,%
 438 english,newzealand,UKenglish,USenglish}{\examinationname}{Examination}%
 439 \providecaptionname{american,australian,british,canadian,%
 440 english,newzealand,UKenglish,USenglish}{\examinationdatename}{Date of
 441 Examination}%
 442 \providecaptionname{german,ngerman,austrian,naustrian,%
 443 swissgerman,nswissgerman}{\chairmanname}{Dekan/Dekanin}%
 444 \providecaptionname{german,ngerman,austrian,naustrian,%

```

445 swissgerman,nswissgerman}{\projectpapername}{Projektarbeit}%
446 \providecaptionname{german,ngerman,austrian,naustrian,%
447 swissgerman,nswissgerman}{\seminarpapername}{Seminararbeit}%
448 \providecaptionname{german,ngerman,austrian,naustrian,%
449 swissgerman,nswissgerman}{\studentresearchname}{Studienarbeit}%
450 \providecaptionname{german,ngerman,austrian,naustrian,%
451 swissgerman,nswissgerman}{\diplomathesisname}{Diplomarbeit}%
452 \providecaptionname{german,ngerman,austrian,naustrian,%
453 swissgerman,nswissgerman}{\degreethesisname}{Dissertation}%
454 \providecaptionname{german,ngerman,austrian,naustrian,%
455 swissgerman,nswissgerman}{\masterthesisname}{Master-Arbeit}%
456 \providecaptionname{german,ngerman,austrian,naustrian,%
457 swissgerman,nswissgerman}{\bachelorthesisname}{Bachelor-Arbeit}%
458 \providecaptionname{german,ngerman,austrian,naustrian,%
459 swissgerman,nswissgerman}{\ordinal}{\germanordinal}%
460 \providecaptionname{german,ngerman,austrian,naustrian,%
461 swissgerman,nswissgerman}{\femaleordinal}{\germanfemaleordinal}%
462 \providecaptionname{german,ngerman,austrian,naustrian,%
463 swissgerman,nswissgerman}{\maleordinal}{\germanmaleordinal}%
464 \providecaptionname{german,ngerman,austrian,naustrian,%
465 swissgerman,nswissgerman}{\presentedbyname}{eingereicht von}%
466 \providecaptionname{german,ngerman,austrian,naustrian,%
467 swissgerman,nswissgerman}{\advisorname}{Betreuer}%
468 \providecaptionname{german,ngerman,austrian,naustrian,%
469 swissgerman,nswissgerman}{\thename}{den}%
470 \providecaptionname{german,ngerman,austrian,naustrian,%
471 swissgerman,nswissgerman}{\ofthename}{der}%
472 \providecaptionname{german,ngerman,austrian,naustrian,%
473 swissgerman,nswissgerman}{\fromname}{von}%
474 \providecaptionname{german,ngerman,austrian,naustrian,%
475 swissgerman,nswissgerman}{\fromplacename}{aus}%
476 \providecaptionname{german,ngerman,austrian,naustrian,%
477 swissgerman,nswissgerman}{\refereename}{Gutachter}%
478 \providecaptionname{german,ngerman,austrian,naustrian,%
479 swissgerman,nswissgerman}{\femalerefereename}{Gutachterin}%
480 \providecaptionname{german,ngerman,austrian,naustrian,%
481 swissgerman,nswissgerman}{\oralexaminationdatename}{Datum der m\"undlichen
482 Pr\"ufung}%
483 \providecaptionname{german,ngerman,austrian,naustrian,%
484 swissgerman,nswissgerman}{\durationname}{Bearbeitungszeitraum}%
485 \providecaptionname{german,ngerman,austrian,naustrian,%
486 swissgerman,nswissgerman}{\matriculationnumbername}{Matrikelnummer}%
487 \providecaptionname{german,ngerman,austrian,naustrian,%
488 swissgerman,nswissgerman}{\coursename}{Kurs}%
489 \providecaptionname{german,ngerman,austrian,naustrian,%
490 swissgerman,nswissgerman}{\companyname}{Ausbildungsfirma}%
491 \providecaptionname{german,ngerman,austrian,naustrian,%
492 swissgerman,nswissgerman}{\examinationname}{Pr\"ufung}%
493 \providecaptionname{german,ngerman,austrian,naustrian,%

```

```

494 swissgerman, nswissgerman}{\examinationdatename}{Tag der Pr\"ufung}%

\englishordinal
495 \newcommand*{\englishordinal}[1]{%
496   \ifcsname engordnumber\endcsname
497     \engordnumber{#1}%
498   \else
499     \ifnum #1<\@ne
500       \PackageError{uni-titlepage}{Ordinal of ‘#1’ not defined}{%
501         This package does only define english ordinals from 1}%
502     \else
503       \ifcase #1\or 1st\or 2nd\or 3rd\or 4th\or 5th\or 6th\or 7th\or 8th\or
504         9th\or 10th\else
505         \PackageError{uni-titlepage}{Ordinal of ‘#1’ not defined}{%
506           This package does only define english ordinals from 1 to
507           10.\MessageBreak
508           You may load package ‘engord’ to improve support of english
509           ordinals}%
510       \fi
511     \fi
512   \fi
513 }

\germanordinal
\germanmaleordinal
\germanfemaleordinal
514 \newcommand*{\germanordinal}[1]{%
515   \ifnum #1<\@ne
516     \PackageError{uni-titlepage}{Ordinal of ‘#1’ not defined}{%
517       This package does only define german ordinals from 1}%
518   \else
519     #1.%
520   \fi
521 }
522 \newcommand*{\germanmaleordinal}[1]{%
523   \ifcase #1
524     \PackageError{uni-titlepage}{Male ordinal of ‘#1’ not defined}{%
525       This package does only define german male ordinals from 1}%
526   \or Erster\or Zweiter\or Dritter\or Vierter\or F\"unfter\or Sechster%
527   \or Siebter\or Achter\or Neunter\or Zehnter\else
528     \PackageError{uni-titlepage}{Male ordinal of ‘#1’ not defined}{%
529       This package does only define german male ordinals up to 10}%
530   \fi
531 }
532 \newcommand*{\germanfemaleordinal}[1]{%
533   \ifcase #1
534     \PackageError{uni-titlepage}{Female ordinal of ‘#1’ not defined}{%
535       This package does only define german female ordinals from 1}%
536   \or Erste\or Zweite\or Dritte\or Vierte\or F\"unfte\or Sechste%
537   \or Siebte\or Achte\or Neunte\or Zehnte\else
538     \PackageError{uni-titlepage}{Female ordinal of ‘#1’ not defined}{%

```

```

539      This package does only define german female ordinals up to 10}%
540  \fi
541 }

```

4.3 The titlepage Drivers

```

542 \beginngroup
543   \def\PackageNotLoadedError#1{%
544     \GenericError{%
545       (#1)\@spaces\@spaces\@spaces\@spaces
546     }{%
547       File ‘#1’ Error: package ‘uni-titlepage’ hasn’t been loaded%
548     }{%
549       This definition file was made to be loaded by package
550       ‘uni-titlepage’.\MessageBreak
551       You may not use it without package ‘uni-titlepage’!\MessageBreak
552       See the documentation of package ‘uni-titlepage’ for explanation.%
553     }%
554   }%
555   \ifx\curname uni-titlepage.sty@vers\endcurname\relax
556     \PackageNotLoadedError{%
557 (DHBW)      title-DHBW.def%
558 (KOMAScript) title-KOMAScript.def%
559 (TU-DD)     title-TU-DD.def%
560 (TU-HH)     title-TU-HH.def%
561 (Markus & 1) title-Markus-1.def%
562 (Markus & 2) title-Markus-2.def%
563 (Spacer)    title-Spacer.def%
564 (KIT)       title-KIT.def%
565 (JT-Aufsaetze) title-JT-Aufsaetze.def%
566 (JT-Geschichte) title-JT-Geschichte.def%
567 (JT-Typography) title-JT-Typography.def%
568 (WWUM)      title-WWUM.def%
569     }%
570   \fi
571 \endgroup

```

Each style corresponds with an own member. Nevertheless most styles will not have options in their own, because string options should be global to make change of style very easy.

```

572 \DefineFamilyMember[%
573 (DHBW) DHBW%
574 (KOMAScript) KOMAScript%
575 (TU-DD) TU-DD%
576 (TU-HH) TU-HH%
577 (Markus & 1) Markus-1%
578 (Markus & 2) Markus-2%
579 (Spacer) Spacer%
580 (KIT) KIT%
581 (JT-Aufsaetze) JT-Aufsaetze%

```

```

582 <JT-Geschichte> JT-Geschichte%
583 <JT-Typography> JT-Typography%
584 <WWUM> WWUM%
585 ]{title}

```

Nevertheless some style has their own switches:

blackborder *Trauerrand* at style TU-DD:

```

586 <TU-DD>\FamilyBoolKey[TU-DD]{title}{blackborder}{blackborder}

```

final Style TU-HH distinguishes between drafts and final thesis.

```

587 <TU-HH>\FamilyBoolKey[TU-HH]{title}{final}{final}

```

rulewidth Some styles have some variable rules at the title:

```

\ttitle@rulewidth 588 <*Spacer | JT-Aufsaetze | JT-Geschichte | Markus & 2>
rulesep           589 \providecommand*{\ttitle@rulewidth}{%
\ttitle@rulesep   590 <Spacer | Markus & 2> 0pt%
                  591 <JT-Aufsaetze | JT-Geschichte> .25\textwidth
                  592 }
                  593 \providecommand*{\ttitle@rulesep}{%
                  594 <Spacer | Markus & 2> \ifdim \ttitle@rulewidth>\z@ 10pt\else \z@\fi
                  595 <JT-Aufsaetze | JT-Geschichte> 1.5pt%
                  596 }
                  597 \DefineFamilyKey[%
                  598 <Markus & 2> Markus-2%
                  599 <JT-Aufsaetze> JT-Aufsaetze%
                  600 <JT-Geschichte> JT-Geschichte%
                  601 <Spacer> Spacer%
                  602 ]{title}{rulewidth}{%
                  603 \gdef\ttitle@rulewidth{\dimexpr #1\relax}%
                  604 \FamilyKeyStateProcessed
                  605 }
                  606 \DefineFamilyKey[%
                  607 <Markus & 2> Markus-2%
                  608 <JT-Aufsaetze> JT-Aufsaetze%
                  609 <JT-Geschichte> JT-Geschichte%
                  610 <Spacer> Spacer%
                  611 ]{title}{rulesep}{%
                  612 \gdef\ttitle@rulesep{\dimexpr #1\relax}%
                  613 \FamilyKeyStateProcessed
                  614 }
                  615 </Spacer | JT-Aufsaetze | JT-Geschichte | Markus & 2>

```

An some has their own terms:

```

\presentationinformationWWUM
\presentationinformationTUHH 616 <*DHBW>
\presentationinformationDHBW 617 \providecommand*{\presentationinformationDHBW}{%
\presentationinformationKIT 618 for the \examinationname{} of\[\.5\baselineskip]
                             619 \@academicgrade\[\Opt plus 1fill]

```



```

620 of \@discipline\\[.5\baselineskip]
621 at the \@university{} \@place\\
622 }
623 \providecaptionname{american,australian,british,canadian,%
624 english,newzealand,UKenglish,USenglish}{\presentationinformationDHBW}{%
625 for the \examinationname\\[.5\baselineskip]
626 \@academicgrade\\[0pt plus 1fill]
627 of degree course \@discipline\\[.5\baselineskip]
628 at the \@university\ifx\@place\@empty\else\space\@place\fi
629 }%
630 \providecaptionname{german,ngerman,austrian,naustrian,%
631 swissgerman,nswissgerman}{\presentationinformationDHBW}{%
632 f"ur die \examinationname{} zum\\[.5\baselineskip]
633 \@academicgrade\\[0pt plus 1fill]
634 des Studienganges \@discipline\\[.5\baselineskip]
635 an der \@university{}\ifx\@place\@empty\else\space\@place\fi
636 }%
637 </DHBW>
638 <*TU-HH>
639 \providecommand*{\presentationinformationTUHH}{%
640 \iffinal Of the \else The \fi Graduation Committee of the\\
641 \@university\\[.5ex]
642 to the Acquisition of the Academic Degree\\[.5ex]
643 \@academicgrade\\[.5ex]
644 \iffinal approved \else submitted \fi\@subject}
645 \providecaptionname{american,australian,british,canadian,%
646 english,newzealand,UKenglish,USenglish}{\presentationinformationTUHH}{%
647 \iffinal Of the \else The \fi Graduation Committee of the\\
648 \@university\\[.5ex]
649 to the Acquisition of the Academic Degree\\[.5ex]
650 \@academicgrade\\[.5ex]
651 \iffinal approved \else submitted \fi\@subject}
652 \providecaptionname{german,ngerman,austrian,naustrian,%
653 swissgerman,nswissgerman}{\presentationinformationTUHH}{%
654 \iffinal Vom \else Dem \fi Promotionsausschuss der\\
655 \@university\\[.5ex]
656 zur Erlangung des akademischen Grades\\[.5ex]
657 \@academicgrade\\[.5ex]
658 \iffinal genehmigte \else vorgelegte \fi\@subject}%
659 </TU-HH>
660 <*KIT>
661 \providecommand*{\presentationinformationKIT}{%
662 At the \@faculty\\
663 \strut\ignorespaces\@chair\\
664 }
665 \providecaptionname{american,australian,british,canadian,%
666 english,newzealand,UKenglish,USenglish}{\presentationinformationKIT}{%
667 At the \@faculty\\
668 \strut\ignorespaces\@chair\\

```

```

669 }%
670 \providecaptionname{german,ngerman,austrian,naustrian,%
671   swissgerman,nswissgerman}{\presentationinformationKIT}{%
672   An der \@faculty\\
673   \strut\ignorespaces\@chair\\
674 }%
675 </KIT>
676 <*WWUM>
677 \providecommand*{\presentationinformationWWUM}{%
678   \@subject\\
679   to the Aquisition of the Academic Degree\\
680   \@academicgrade\\
681   of the \@sience{ } of \@discipline\\
682   of the \@faculty{ } faculty\\
683   of the \@university
684 }
685 \providecaptionname{american,australian,british,canadian,%
686   english,newzealand,UKenglish,USenglish}{\presentationinformationWWUM}{%
687   \@subject\\
688   to the Aquisition of the Academic Degree\\
689   \@academicgrade\\
690   of the \@sience{ } of \@discipline\\
691   of the \@faculty{ } faculty\\
692   of the \@university
693 }
694 \providecaptionname{german,ngerman,austrian,naustrian,%
695   swissgerman,nswissgerman}{\presentationinformationWWUM}{%
696   \@subject\\
697   zur Erlangung des \@academicgrade\\
698   der \@sience{ } im Fachbereich \@discipline\\
699   der \@faculty{ } Fakult\ "at\\
700   der \@university
701 }
702 </WWUM>

\KITlongname
\fromname 703 <*KIT>
\refereename 704 \providecaptionname{american,australian,british,canadian,%
\KITurl 705   english,newzealand,UKenglish,USenglish}{\KITlongname}{%
706   University of the State of Baden-W\ "urttemberg and National Research Center
707   of the Helmholtz Association%
708 }%
709 \providecaptionname{german,ngerman,austrian,naustrian,%
710   swissgerman,nswissgerman}{\KITlongname}{%
711   Universit\ "at des Landes Baden-W\ "urttemberg und nationales
712   Forschungszentrum in der Helmholtz-Gemeinschaft
713 }%
714 \scr@ifundefinedorrelax{captionsamerican}{ }{%
715   \renewcaptionname{american}{\fromname}{of}%

```

```

716 \renewcaptionname{american}{\refereename}{Reviewer}%
717 }%
718 \scr@ifundefinedorrelax{captionsaustralian}{}{%
719 \renewcaptionname{australian}{\fromname}{of}%
720 \renewcaptionname{australian}{\refereename}{Reviewer}%
721 }%
722 \scr@ifundefinedorrelax{captionsbritish}{}{%
723 \renewcaptionname{british}{\fromname}{of}%
724 \renewcaptionname{british}{\refereename}{Reviewer}%
725 }%
726 \scr@ifundefinedorrelax{captionscanadian}{}{%
727 \renewcaptionname{canadian}{\fromname}{of}%
728 \renewcaptionname{canadian}{\refereename}{Reviewer}%
729 }%
730 \scr@ifundefinedorrelax{captionsenglish}{}{%
731 \renewcaptionname{english}{\fromname}{of}%
732 \renewcaptionname{english}{\refereename}{Reviewer}%
733 }%
734 \scr@ifundefinedorrelax{captionsnewzealand}{}{%
735 \renewcaptionname{newzealand}{\fromname}{of}%
736 \renewcaptionname{newzealand}{\refereename}{Reviewer}%
737 }%
738 \scr@ifundefinedorrelax{captionsUKenglish}{}{%
739 \renewcaptionname{UKenglish}{\fromname}{of}%
740 \renewcaptionname{UKenglish}{\refereename}{Reviewer}%
741 }%
742 \scr@ifundefinedorrelax{captionsUSenglish}{}{%
743 \renewcaptionname{USenglish}{\fromname}{of}%
744 \renewcaptionname{USenglish}{\refereename}{Reviewer}%
745 }%
746 \newcommand*{\KITurl}{www.kit.edu}
747 </KIT>

```

\presentedbyname

```

748 < *WWUM >
749 \NowButAfterBeginDocument
750 {%
751 \providecaptionname{german,ngerman,austrian,naustrian,
752 swissgerman,nswissgerman}{\presentedbyname}{vorgelegt von}%
753 \scr@ifundefinedorrelax{captionsgerman}{}{%
754 \renewcaptionname{german}{\presentedbyname}{vorgelegt von}%
755 }%
756 \scr@ifundefinedorrelax{captionsgerman}{}{%
757 \renewcaptionname{ngerman}{\presentedbyname}{vorgelegt von}%
758 }%
759 \scr@ifundefinedorrelax{captionsaustrian}{}{%
760 \renewcaptionname{austrian}{\presentedbyname}{vorgelegt von}%
761 }%
762 \scr@ifundefinedorrelax{captionснаustrian}{}{%

```

```

763 \renewcaptionname{naustrian}{\presentedbyname}{vorgelegt von}%
764 }%
765 \scr@ifundefinedorrelax{captionsswissgerman}{}{}%
766 \renewcaptionname{swissgerman}{\presentedbyname}{vorgelegt von}%
767 }%
768 \scr@ifundefinedorrelax{captionsswissgerman}{}{}%
769 \renewcaptionname{nswissgerman}{\presentedbyname}{vorgelegt von}%
770 }%
771 }
772 </WWUM>

```

While style initialization, something may change:

```

773 \renewcommand*{\inittitle}{%

```

style KOMAScript redefines some footnote macros:

```

774 <*KOMAScript>
775 \let\footnotesize\small
776 \let\footnoterule\relax
777 \let\footnote\thanks
778 \renewcommand*\thefootnote{\@fnsymbol\c@footnote}%
779 \let\@oldmakefnmark\@makefnmark
780 \renewcommand*{\@makefnmark}{\rlap\@oldmakefnmark}%
781 </KOMAScript>

```

styles DHBW, TU-DD, TU-HH, and KIT sets some variable if not already done

```

782 <*DHBW | TU-DD | TU-HH | KIT | WWUM>
783 \ifx\@university\@empty
784 \university{%
785 (DHBW) Dualen Hochschule%
786 (TU-DD) Technische\nobreakspace Universit\at\nobreakspace Dresden%
787 (TU-HH) Technische\nobreakspace Universit\at\nobreakspace
788 (TU-HH) Hamburg-Harburg%
789 (KIT) KIT -- \KITlongname
790 (WWUM) Westf\alischen Wilhelms-Universit\at M\unster%
791 }%
792 \fi
793 \ifx\@place\@empty
794 \place{%
795 (DHBW) Baden-W\urttemberg%
796 (TU-DD) Dresden%
797 (TU-HH) Hamburg%
798 (KIT) Karlsruhe%
799 <*WWUM>
800 \PackageWarning{uni-titlepage}{Birth place missing.\MessageBreak
801 Style 'WWUM' needs the birth place of\MessageBreak
802 the student}%
803 </WWUM>
804 }
805 \fi
806 <*DHBW>

```

```

807 \ifx\@mainlogo\@empty
808 \IfFileExists{DHBW_d_MOS_195x95_rgb_300.jpg}{%
809 \scr@ifundefinedorrelax{includegraphics}{%
810 \if@atdocument\else\RequirePackage{graphicx}\fi
811 }{}%
812 \scr@ifundefinedorrelax{includegraphics}{}{%
813 \mainlogo{%
814 \includegraphics[width=57mm,height=27mm]%
815 {DHBW_d_MOS_195x95_rgb_300.jpg}%
816 }%
817 }%
818 }{}%
819 \fi
820 \ifx\@titlehead\@empty
821 \titlehead{\hspace*\fill}\@mainlogo}%
822 \fi
823 \ifx\@titlepagefont\@empty
824 \renewcommand*{\@titlepagefont}{\normalfont\sffamily}%
825 \fi
826 \</DHBW>
827 \<*KIT>
828 \ifx\@homepage\@empty
829 \homepage{\KITurl}%
830 \fi
831 \ifx\@mainlogo\@empty

```

Try to detect one of the suitable PNGs of the KIT logo from https://de.wikipedia.org/wiki/Datei:Logo_KIT.svg.

```

832 \def\KIT@logo{KITLogo_RGB.pdf}\IfFileExists{\KIT@logo}{}{%
833 \def\KIT@logo{2560px-Logo_KIT.svg.png}\IfFileExists{\KIT@logo}{}{%
834 \def\KIT@logo{2000px-Logo_KIT.svg.png}\IfFileExists{\KIT@logo}{}{%
835 \def\KIT@logo{1280px-Logo_KIT.svg.png}\IfFileExists{\KIT@logo}{}{%
836 \def\KIT@logo{1024px-Logo_KIT.svg.png}\IfFileExists{\KIT@logo}{}{%
837 \def\KIT@logo{1000px-Logo_KIT.svg.png}\IfFileExists{\KIT@logo}{}{%
838 \def\KIT@logo{800px-Logo_KIT.svg.png}\IfFileExists{\KIT@logo}{%
839 \def\KIT@logo{640px-Logo_KIT.svg.png}\IfFileExists{\KIT@logo}%
840 \def\KIT@logo{500px-Logo_KIT.svg.png}%
841 }}}}{}%
842 \IfFileExists{\KIT@logo}{%
843 \scr@ifundefinedorrelax{includegraphics}{%
844 \if@atdocument\else\RequirePackage{graphicx}\fi
845 }{}%
846 \scr@ifundefinedorrelax{includegraphics}{}{%
847 \mainlogo{%
848 \includegraphics[width=40mm,height=18.5mm]{\KIT@logo}%
849 }%
850 }%
851 }{}%
852 \fi
853 \ifx\@titlehead\@empty

```

```

854 \titlehead{\@mainlogo\hspace*{\fill}}%
855 \fi
856 \ifx\@titlepagefont\@empty
857 \renewcommand*{\@titlepagefont}{\usefont{T1}{phv}{m}{n}}%
858 \fi
859 \</KIT>
860 \< *WWUM>
861 \ifx\@titlepagefont\@empty
862 \renewcommand*{\@titlepagefont}{\normalfont\large}%
863 \fi
864 \</WWUM>
865 \</DHBW | TU-DD | TU-HH | KIT | WWUM>

```

style Markus-2 uses it's own pagestyle at the first title page

```

866 \< *Markus & 2>
867 \def\ps@maintitle{%
868 \ps@empty
869 \def\@oddhead{%
870 \parbox[b][\headheight][b]{\hspace*{\fill}\@titlepagefont{%
871 \csname @titlehead\endcsname}}%
872 }%
873 \let\@evenhead\@oddhead
874 }%
875 \</Markus & 2>

```

styles JT-Aufsätze and JT-Geschichte set some font defaults:

```

876 \< *JT-Aufsätze | JT-Geschichte>
877 \ifx\@titlepagefont\@empty
878 \JT-Aufsätze \renewcommand*{\@titlepagefont}{\normalfont\Huge\itshape}%
879 \< *JT-Geschichte>
880 \scr@ifundefinedorrelax{lsstyle}{%
881 \renewcommand*{\@titlepagefont}{\normalfont\let\@tpf@extra\scshape}%
882 }{%
883 \renewcommand*{\@titlepagefont}{%
884 \normalfont\def\@tpf@extra{\lsstyle\MakeUppercase}%
885 }%
886 }
887 \</JT-Geschichte>
888 \fi
889 \ifx\titlefont\@empty
890 \renewcommand*{\titlefont}{\normalfont}%
891 \fi
892 \</JT-Aufsätze | JT-Geschichte>
893 \< *JT-Typography>
894 \ifx\@titlepagefont\@empty
895 \renewcommand*{\@titlepagefont}{\normalfont\sffamily\bfseries}%
896 \fi
897 \</JT-Typography>
898 }

```

\publishers KOMA-Script defines this macro. But we use \publisher instead.

```

899 \KOMAScript\providecommand*\publishers{\publisher}

```

\makemaintitle This differs from style to style:

```

900 \renewcommand*\makemaintitle{%
901   \begin{
902     (DHBW | TU-DD | TU-HH | KIT)      fullsizetitle}
903 \KOMAScript | Markus | Spacer | JT-Aufsätze | JT-Geschichte | JT-Typography | WWUM)
904   titlepage}
905 \KOMAScript | Markus | Spacer | JT-Aufsätze | JT-Geschichte | JT-Typography | WWUM)
906   \setlength{\parskip}{\z@}%
907   \setlength{\parindent}{\z@}%
908   \setlength{\parfillskip}{\z@\@plus 1fil}%
909   \linespread{1}\selectfont
910   \@titlepagefont
911 \KOMAScript (DHBW)
912   \vspace*{12mm}%
913   \centering
914   \begin{minipage}[t][\dimexpr\vsiz-36mm\relax][\dimexpr\hsiz-40mm\relax]%
915     \@titlehead\par
916     \centering
917     \Large
918     \vfill
919     {\titlefont{\Large\@title}}\par
920     \vfill
921     {\subjectfont{\Large\@subject}\par}}%
922     \vfill
923     \presentationinformationDHBW\par
924     \vfill
925     \fromname\[\.5\baselineskip]
926     \@author\par
927     \vfill
928     \@date\par
929     \vfill
930     \begin{tabular}{*2{p{.5\dimexpr\linewidth-3\tabcolsep\relax}}@{}}
931       \durationname & \@duration \[\.5ex]
932       \matriculationnumbername, \coursename & \@matriculationnumber,
933       & \@course\[\.5ex]
934       \companynome & \@company \[\.5ex]
935       \advisorname{} \ofthename{} \companynome & \@advisor \[\.5ex]
936       \refereename{} \ofthename{} \@university & \@referee
937     \end{tabular}
938   \end{minipage}
939 \KOMAScript (DHBW)
940 \KOMAScript
941   \ifx\@titlehead\@empty \else
942     \begin{minipage}[t]{\textwidth}%
943       \@titlehead
944     \end{minipage}\par

```

```

945 \fi
946 \null\vfill
947 \begingroup
948 \centering
949 \ifx\@subject\@empty \else
950 {\subject@font{\@subject \par}}%
951 \vskip 3em
952 \fi
953 {\titlefont{\huge \@title\par}}%
954 \vskip 1em
955 {\ifx\@subtitle\@empty\else\@subtitlefont{\@subtitle}\par\fi}%
956 \vskip 2em
957 {\Large \lineskip 0.75em
958 \begin{tabular}[t]{c}
959 \@author
960 \end{tabular}\par
961 }%
962 \vskip 1.5em
963 {\Large \@date \par}%
964 \vskip \z@ \@plus3fill
965 {\Large \@publisher \par}%
966 \vskip 3em
967 \endgroup
968 \@thanks
969 \vfill\null\vskip-\baselineskip
970 

```



```

994      {\bfseries\strut\ignorespaces\@title\unskip\strut\\}
995      \strut\ignorespaces\@subject\unskip\strut\\
996      \vfill
997      \raggedright
998      \hspace*{.25\linewidth}%
999      \strut\ignorespaces\presentedbyname\unskip\strut\\
1000     \hspace*{.25\linewidth}\quad
1001     \begin{tabular}{@{}l@{}}
1002       \strut\ignorespaces\@author\unskip\strut\\
1003       \strut\ignorespaces\@discipline\unskip\strut\\
1004       \strut\ignorespaces\@matriculationnumber\unskip\strut\\
1005     \end{tabular}\\
1006     \vskip\baselineskip
1007     \hspace*{.25\linewidth}%
1008     \strut\ignorespaces\advisorname\unskip:\strut\\
1009     \hspace*{.25\linewidth}\quad
1010     \begin{tabular}{@{}l@{}}
1011       \strut\ignorespaces\@advisor\unskip\strut\\
1012     \end{tabular}
1013     \vskip2\baselineskip
1014     \hspace*{.25\linewidth}%
1015     \strut\ignorespaces\@place,\nobreakspace\thename\nobreakspace\@date
1016     \par}
1017     \vspace*{5mm}
1018   \end{minipage}
1019   }%
1020 \

```

```

1043 \vfill
1044 \presentationinformationWWUM\
1045 \vfill
1046 \presentedbyname\
1047 \@author\
1048 \ifx\@place\@empty\else\fromplacename{} \@place\\\fi
1049 --\, \the\year\,--
1050 </WWUM>
1051 <*Markus & 1>
1052 \raggedright
1053 {\subject@font{%
1054 \large\strut\ignorespaces\@subject\par\vskip 2\baselineskip}}%
1055 {\titlefont{\LARGE\strut\ignorespaces\@title\par}}%
1056 {\@subtitlefont{%
1057 \large\vskip.5\baselineskip\strut\ignorespaces\@subtitle\par}}%
1058 \vfill
1059 {\csname @datefont\endcsname{\large\strut\ignorespaces\@date\par}}%
1060 </Markus & 1>
1061 <*Spacer | Markus & 2>
1062 \raggedright
1063 (Markus & 2) \thispagestyle{maintitle}%
1064 \raisebox{0pt}[\ht\strutbox][\dimexpr\textheight-\ht\strutbox\relax]{%
1065 \rule[\dimexpr-.667\headsep-\textheight\relax]
1066 {\title@rulewidth}
1067 {\dimexpr\textheight+2\headsep\relax}\kern\title@rulesep}%
1068 \parbox[t][\textheight][t]
1069 {\dimexpr \textwidth-\title@rulewidth-\title@rulesep\relax}{%
1070 \raggedright
1071 *Spacer>
1072 \ifx\@titlehead\@empty\else
1073 \raisebox{\dimexpr\ht\strutbox-\totalheight\relax}{%
1074 \parbox[t]{\linewidth}{\@titlehead}%
1075 }\par
1076 \vskip 2\baselineskip
1077 \fi
1078 </Spacer>
1079 {\leavevmode\subject@font{%
1080 \large\strut\ignorespaces\@subject\par\vskip 2\baselineskip}}%
1081 {\def\and{\}\csname @authorfont\endcsname{\large\@author}\par
1082 \vskip .5\baselineskip}%
1083 {\titlefont{\LARGE\strut\ignorespaces\@title\par}}%
1084 {\@subtitlefont{%
1085 \large\vskip.5\baselineskip\strut\ignorespaces\@subtitle\par}}%
1086 \vfill
1087 {\csname @publisherfont\endcsname{\large\@publisher\par}}%
1088 {\csname @datefont\endcsname{\large\strut\ignorespaces\@date\par}}%
1089 }%
1090 </Spacer | Markus & 2>
1091 <*KIT>

```

```

1092 \setlength{\unitlength}{1mm}%
1093 \begin{picture}(0,0)
1094   \put(15,-12){%
1095     \line(1,0){\dimexpr\paperwidth-37mm\relax\@gobble}%
1096   }%
1097   \put(\dimexpr\paperwidth-22mm\@gobble,-19){\oval(14,14)[rt]}%
1098   \put(\dimexpr\paperwidth-15mm\@gobble,-19){%
1099     \line(0,-1){\dimexpr\paperheight-37mm\relax\@gobble}%
1100   }%
1101   \put(22,-\dimexpr\paperheight-18mm\relax\@gobble){%
1102     \line(1,0){\dimexpr\paperwidth-37mm\relax\@gobble}%
1103   }%
1104   \put(22,-\dimexpr\paperheight-25mm\relax\@gobble){\oval(14,14)[lb]}%
1105   \put(15,-\dimexpr\paperheight-25mm\relax\@gobble){%
1106     \line(0,1){\dimexpr\paperheight-37mm\relax\@gobble}%
1107   }%
1108 \end{picture}\par
1109 \vskip\dimexpr -\baselineskip+25mm\relax
1110 \hspace*{27mm}%
1111 \begin{minipage}[t][\dimexpr\paperheight-68mm\relax][t]
1112   {\dimexpr\paperwidth-54mm\relax}
1113   \raggedright\@titlehead\par
1114   \centering
1115   \vskip 25mm
1116   {\@titlepagefont\@title\par}%
1117   \vskip 20mm
1118   {\Large\@subject\\\fromname\par}
1119   \vskip 1cm
1120   {\huge\@author\par}
1121   \vskip 1cm
1122   {\Large\presentationinformationKIT\par}
1123   \vskip 2cm
1124   {\Large
1125     \let\@tempa\refereename
1126     \def\@tempb{1}%
1127     \def\and{%
1128       \\
1129       \xdef\@tempb{\the\numexpr\@tempb+1\relax}%
1130       \expandafter\ordinal\expandafter{\@tempb}~\@tempa: &
1131     }%
1132     \begin{tabular}{@{}lr@{}}
1133       \refereename: & \@referee \\
1134       \global\let\@tempa\advisorname\xdef\@tempb{1}%
1135       \advisorname: & \@advisor \\
1136     \end{tabular}\par
1137   }
1138   \vfill
1139   {\large \durationname: \@duration\par}
1140 \end{minipage}

```

```

1141 \vskip 35mm
1142 \hspace*{27mm}\makebox[\dimexpr\paperwidth-56mm\relax]{%
1143 \tiny\@university\hfill\large\textbf{\@homepage}%
1144 }%
1145 \</KIT>
1146 \<*JT-Aufsätze>
1147 \centering
1148 \@author\
1149 \begin{picture}(\title@rulewidth\@gobble,
1150 \dimexpr .3ex+1pt+\title@rulesep\relax\@gobble)
1151 \put(0,\dimexpr .15ex+.5pt+\title@rulesep\relax\@gobble){%
1152 \linethickness{.3ex}\line(1,0){\title@rulewidth\@gobble}%
1153 }%
1154 \put(0,0){%
1155 \linethickness{1pt}\line(1,0){\title@rulewidth\@gobble}%
1156 }%
1157 \end{picture}\\[\baselineskip]
1158 {\titlefont{\@title\par}}%
1159 \vfill
1160 \@publisher
1161 \</JT-Aufsätze>
1162 \<*JT-Geschichte>
1163 \centering
1164 \large{\@tpf@extra{\@author\unskip\strut}}\\[\dp\strutbox]
1165 {\titlefont{\Huge\@title\par}}
1166 \vfill
1167 \begin{picture}(\title@rulewidth\@gobble,
1168 \dimexpr 4pt+1pt+\title@rulesep\relax\@gobble)
1169 \put(0,\dimexpr 2pt+.5pt+\title@rulesep\relax\@gobble){%
1170 \linethickness{1pt}\line(1,0){\title@rulewidth\@gobble}%
1171 }%
1172 \put(0,0){%
1173 \linethickness{4pt}\line(1,0){\title@rulewidth\@gobble}%
1174 }%
1175 \end{picture}\\[\dp\strutbox]
1176 \@tpf@extra{\@publisher}%
1177 \ifx\@place\@empty\else
1178 \unskip\@tpf@extra{\strut}\\[\dp\strutbox]\@tpf@extra{\@place}%
1179 \fi
1180 \</JT-Geschichte>
1181 \<*JT-Typography>
1182 \raggedright
1183 {\Large\MakeUppercase{\@author}}\\[\baselineskip]}
1184 {\titlefont{\Huge\MakeUppercase{\@title}\unskip\strut\\}}
1185 {\@subtitlefont{\normalsize\MakeUppercase{\@subtitle}\\}}
1186 \vfill
1187 {\normalsize\MakeUppercase{\@place}\ifx\@place\@empty\else\enskip\fi
1188 {\LARGE\MakeUppercase{\@date}}
1189 \ifx\@publisher\@empty\else\unskip\strut\\[1.5\baselineskip]

```

```

1190      \MakeUppercase{\@publisher}%
1191      \fi}
1192 \JT-Typography}
1193 \end{%
1194 \DHBW | TU-DD | TU-HH | KIT} fullsizetitle}
1195 \*KOMAScript | Markus | Spacer | JT-Aufsaetze | JT-Geschichte | JT-Typography | WWUM}
1196 titlepage}
1197 \KOMAScript | Markus | Spacer | JT-Aufsaetze | JT-Geschichte | JT-Typography | WWUM}
1198 }

```

Some of the styles need additional string options for the back of the main title. These are more structural than logical, so we do not define those globally!

```

uppertitleback
\uppertitleback 1199 \*KOMAScript | Markus | Spacer}
\@uppertitleback 1200 \providecommand*\@uppertitleback{}
lowertitleback 1201 \providecommand{\uppertitleback}[1]{\gdef\@uppertitleback{#1}}
\lowertitleback 1202 \DefineFamilyKey[%
\@lowertitleback 1203 \KOMAScript) KOMAScript%
1204 \Markus & 1) Markus-1%
1205 \Markus & 2) Markus-2%
1206 \Spacer) Spacer%
1207 \JT-Aufsaetze) JT-Aufsaetze%
1208 \JT-Geschichte) JT-Geschichte%
1209 \JT-Geschichte) JT-Typography%
1210 ]{title}{uppertitleback}{\uppertitleback{#1}\FamilyKeyStateProcessed}
1211 \providecommand*\@lowertitleback{}
1212 \providecommand{\lowertitleback}[1]{\gdef\@lowertitleback{#1}}
1213 \DefineFamilyKey[%
1214 \KOMAScript) KOMAScript%
1215 \Markus & 1) Markus-1%
1216 \Markus & 2) Markus-2%
1217 \Spacer) Spacer%
1218 \JT-Aufsaetze) JT-Aufsaetze%
1219 \JT-Geschichte) JT-Geschichte%
1220 \JT-Geschichte) JT-Typography%
1221 ]{title}{lowertitleback}{\lowertitleback{#1}\FamilyKeyStateProcessed}
1222 \KOMAScript | Markus | Spacer}

```

\makemaintitleback Only some of the styles define this:

```

1223 \*KOMAScript | Markus | Spacer | JT-Aufsaetze | JT-Geschichte | JT-Typography}
1224 \renewcommand*\makemaintitleback{%
1225 \begin{titlepage}
1226 \begin{minipage}[t]{\textwidth}
1227 \@titlepagefont{\@uppertitleback}%
1228 \end{minipage}\par
1229 \vfill
1230 \begin{minipage}[b]{\textwidth}

```

```

1231      \@titlepagefont{\@lowertitleback}%
1232      \end{minipage}
1233      \end{titlepage}
1234 }
1235 </KOMAScript | Markus | Spacer | JT-Aufsätze | JT-Geschichte | JT-Typography>
1236 <*TU-HH>
1237 \renewcommand*{\makemaintitleback}{%
1238   \begin{titlepage}
1239     \vspace*{\fill}
1240     \iffinal
1241     \@tempcnta\z@
1242     \def\and{%
1243       \par\advance\@tempcnta by\@ne
1244       \@hangfrom{%
1245         \expandafter\ordinal\expandafter{\the\@tempcnta}~\refereename:\enskip
1246       }%
1247     }\and\@referee
1248     \fi
1249     \vskip 1cm
1250     \iffinal
1251     \@hangfrom{\oralexaminationdatename:\enskip}{\@oralexaminationdate}%
1252     \fi
1253   \end{titlepage}
1254 }
1255 </TU-HH>
1256 <*WWUM>
1257 \renewcommand*{\makemaintitleback}{%
1258   \begin{titlepage}
1259     \vspace*{\fill}
1260     \noindent
1261     \@tempcnta\z@
1262     \def\arraystretch{2}%
1263     \newcommand*{\test@malefemale}[1][m]{%
1264       \global\advance\@tempcnta by\@ne
1265       \Ifstr{##1}{f}{\def\fe@male{female}}{\def\fe@male{male}}%
1266       \csname \fe@male ordinal\endcsname{\@tempcnta}\space
1267       \csname \fe@male refereename\endcsname: &
1268       \def\and{\\\test@malefemale}%
1269     }%
1270     \begin{tabular}{@{}ll@{}}
1271       \chairmanname: & \@professor \\
1272       \expandafter\test@malefemale
1273       \@referee \\
1274       \oralexaminationdatename: & \@oralexaminationdate
1275       \ifx\examinationdatename\@empty\else
1276         \\\examinationdatename: &
1277       \fi
1278       \\
1279     \end{tabular}

```

```

1280 \end{titlepage}
1281 }
1282 </WWUM>

```

Some of the styles need additional string options for the pre title. These are more structural than logical, so we do not define those globally!

```

extratitle
\extratitle 1283 <*KOMAScript | Markus & 2 | Spacer | JT-Aufsaetze | JT-Geschichte | JT-Typography>
\@extratitle 1284 \providecommand*{\@extratitle}{%
1285 \providecommand{\extratitle}[1]{\gdef\@extratitle{#1}}
1286 \DefineFamilyKey[%
1287 (KOMAScript) KOMAScript%
1288 (Markus & 2) Markus-2%
1289 (Spacer) Spacer%
1290 (JT-Aufsaetze) JT-Aufsaetze%
1291 (JT-Geschichte) JT-Geschichte%
1292 (JT-Typography) JT-Typography%
1293 ]{title}{extratitle}{\extratitle{#1}\FamilyKeyStateProcessed}
1294 </KOMAScript | Markus & 2 | Spacer | JT-Aufsaetze | JT-Geschichte | JT-Typography>

\makeprettitle Only some styles have pre titles:
\makeprettitleback 1295 <*KOMAScript | Markus & 2 | Spacer | JT-Aufsaetze | JT-Geschichte | JT-Typography>
1296 \renewcommand*{\makeprettitle}{%
1297 \ifx\@extratitle\@empty\else
1298 \begin{titlepage}
1299 \noindent\@extratitle
1300 \end{titlepage}
1301 \fi
1302 }%
1303 </KOMAScript | Markus & 2 | Spacer | JT-Aufsaetze | JT-Geschichte | JT-Typography>
1304 <*Markus & 1>
1305 \renewcommand*{\makeprettitle}{%
1306 \ifx\@publisher\@empty\else
1307 \begin{titlepage}
1308 \raggedleft
1309 {\@titlepagefont%
1310 \large\strut\ignorespaces\@publisher\par}}%
1311 \end{titlepage}
1312 \fi
1313 }
1314 </Markus & 1>
1315 <*WWUM>
1316 \renewcommand*{\makeprettitle}{%
1317 \begin{fullsizetitle}
1318 \@titlepagefont
1319 \vspace*{.33\vsiz}%
1320
1321 \centering

```

```

1322 \author\[\lex]
1323 \title\[\lex]
1324 \the\year
1325 \end{fullsizetitle}
1326 }
1327 </WWUM>

1328 <*KOMAScript | Markus & 2 | Spacer | JT-Aufsätze | JT-Geschichte | JT-Typography>
1329 \renewcommand*{\makepretitlback}{%
1330 \ifx\@extratitle\@empty\else\begin{titlepage}\null\end{titlepage}\fi
1331 }
1332 </KOMAScript | Markus & 2 | Spacer | JT-Aufsätze | JT-Geschichte | JT-Typography>
1333 <*Markus & 1>
1334 \renewcommand*{\makepretitlback}{%
1335 \ifx\@author\@empty\else
1336 \ifx\@publisher\@empty\begin{titlepage}\end{titlepage}\fi
1337 \begin{titlepage}
1338 \raggedleft
1339 {\@titlepagefont{%
1340 \large\null\vskip 2\baselineskip
1341 \LARGE\strut{\def\and{\hspace{1em}}\linebreak[3]}}%
1342 \csname @authorfont\endcsname{\large\ignorespaces\@author}\par}}}%
1343 \end{titlepage}
1344 \fi
1345 }
1346 </Markus & 1>
1347 <*WWUM>
1348 \renewcommand*{\makepretitlback}{%
1349 \if@twoside\begin{titlepage}\null\end{titlepage}\fi
1350 }
1351 </WWUM>

```

\makeposttitle And only some styles provides one more title page with dedication.

\makeposttitlback

```

1352 <*KOMAScript | Markus | Spacer | JT-Aufsätze | JT-Geschichte | JT-Typography>
1353 \renewcommand*{\makeposttitle}{%
1354 \ifx\@dedication\@empty\else
1355 \begin{titlepage}
1356 \null\vfill
1357 {\centering\csname @dedicationfont\endcsname{\@dedication \par}}%
1358 \vskip \z@ \@plus 3fill
1359 \end{titlepage}
1360 \fi
1361 }
1362 \renewcommand*{\makeposttitlback}{%
1363 \ifx\@dedication\@empty\else\begin{titlepage}\null\end{titlepage}\fi
1364 }
1365 </KOMAScript | Markus | Spacer | JT-Aufsätze | JT-Geschichte | JT-Typography>

```

4.4 The Examples and the Manual


```

1366 \documentclass[a4paper,pagesize]{scrbook}
1367 \usepackage[utf8]{inputenc}
1368 \usepackage[ngerman]{babel}
1369 \usepackage[T1]{fontenc}
1370 \usepackage{lmodern}
1371 \JT-Geschichte\usepackage{microtype}
1372 \TU-HH | TU-DD\usepackage{mathpazo}
1373 \TU-HH | TU-DD\usepackage[scaled]{helvet}
1374 \DHBW | Spacer | KIT\usepackage[demo]{graphicx}% remove option demo if you have
1375 \usepackage{xcolor}
1376 \JT-Geschichte | JT-Typography\colorlet{RED}{red}% because of \MakeUppercase{\text
1377 \usepackage{uni-titlepage}
1378 \begin{document}
1379 \*DHBW
1380 \TitlePageStyle{DHBW}
1381 \makeatletter\providecommand*\{@titlepagefont}{\normalfont\sffamily}\makeatother
1382 \setkomafont{subject}{\sffamily\bfseries}
1383 \maketitle[%
1384     titlefont=\sffamily,
1385     mainlogo=\textcolor{red}{\{
1386         % You may add a company logo here!
1387         % NOTE: The original logo has a large white border!
1388         \includegraphics[width=57mm,height=27mm]{
1389             {DHBW_d_MOS_195x95_rgb_300.jpg}%
1390     }},
1391     % You may additionally change titlehead. The original definition of
1392     % titlehead is:
1393     titlehead={\hspace*{\fill}\usetitleelement{mainlogo}},
1394     title=\textcolor{red}{Bachelorarbeitsthema},
1395     subject=\textcolor{red}{BACHELORARBEIT},
1396     academicgrade=\textcolor{red}{Bachelor of Engineering},
1397     discipline=\textcolor{red}{Studiengang},
1398     place={Baden-Württemberg \textcolor{red}{Stadt}},
1399     student=\textcolor{red}{Vorname Nachname},
1400     duration=\textcolor{red}{12 Wochen},
1401     matriculationnumber=\textcolor{red}{Matrikelnummer},
1402     course=\textcolor{red}{Kurskürzel},
1403     company=\textcolor{red}{Firmenname, Stadt},
1404     advisor=\textcolor{red}{Titel Vorname Nachname},
1405     referee=\textcolor{red}{Titel Vorname Nachname},
1406     date=\textcolor{red}{Abgabedatum}
1407 ]
1408 \DHBW
1409 \*TU-DD
1410 \TitlePageStyle{TU-DD}
1411 \maketitle[%
1412     title=\textcolor{red}{Titel im Stil \texttt{TU-DD}},
1413     university=\textcolor{red}{%
1414         Technische\nobreakspace Universit\at\nobreakspace Dresden},%

```

```

1415 faculty=\textcolor{red}{Fakultät Wirtschaftswissenschaften},
1416 chair=\textcolor{red}{SAP-Stiftungslehrstuhl für\
1417     Entrepreneurship und Innovation},
1418 professor=\textcolor{red}{Prof.\,Dr.\,Michael Schefczyk},
1419 % subject=diploma, % one of: project, seminar, studentresearch,
1420 %             % diploma, degree, master, bachelor, or ...
1421 subject=\textcolor{red}{Seminararbeit\,(bzw. Diplomarbeit)},% ... direct value
1422 student=\textcolor{red}{Vorname und Name},
1423 discipline=\textcolor{red}{Studienrichtung},
1424 matriculationnumber=\textcolor{red}{Matrikel-Nr.},
1425 advisor=\textcolor{red}{(mit akadem. Grad, Vor- und Zuname)},
1426 date=\textcolor{red}{(Datum der Abgabe)}
1427 ]
1428
1429 \TitleOptions{pagenumber=1,blackborder}% same with 'Trauerrand'
1430 \maketitle% everything else, like above
1431 \</TU-DD>
1432 \<*KOMAScript>
1433 \TitlePageStyle[pagenumber=1]{KOMAScript}
1434 \maketitle[
1435     extratitle=\textcolor{red}{Das ist ein Schmutztitel im Stil \texttt{KOMAScript}},
1436     titlehead=\textcolor{red}{Den Kopfbereich kann man auf diese Weise füllen.},
1437     subject=\textcolor{red}{Eine Klassifizierung der Arbeit},
1438     title=\textcolor{red}{Titel im Stil \texttt{KOMAScript}},
1439     subtitle=\textcolor{red}{Untertitel},
1440     publisher=\textcolor{red}{Einen Verlag kann man ebenfalls angeben},
1441     uppertitleback=\textcolor{red}{Oberer Bereich der Rückseite des Haupttitels im Stil \texttt{KOMAScript}.},
1442     \texttt{KOMAScript}.},
1443     lowertitleback=\textcolor{red}{Unterer Bereich der Rückseite des Haupttitels im Stil \texttt{KOMAScript}.},
1444     \texttt{KOMAScript}.},
1445     dedication=\textcolor{red}{Eine Widmung im Stil \texttt{KOMAScript}}
1446 ]
1447 \</KOMAScript>
1448 \<*TU-HH>
1449 \TitlePageStyle[pagenumber=1]{TU-HH}
1450 \maketitle[%
1451     final,
1452     title=\textcolor{red}{Titel im Stil \texttt{TU-HH}},
1453     university=\textcolor{red}{Technischen Universität Hamburg-Harburg},
1454     subject=degree,
1455     academicgrade=\textcolor{red}{Doktor der Naturwissenschaften (Dr.\,rer.\,nat)},
1456     place=\textcolor{red}{(Geburtsort)},
1457     date=\textcolor{red}{(aktuelles Jahr)},
1458     referee=\textcolor{red}{Name des ersten Gutachters\protect\and Name des zweiten
1459         Gutachters},
1460     oralexaminationdate=\textcolor{red}{29. Februar 2009}
1461 ]
1462 \</TU-HH>
1463 \<*Markus|Spacer>

```

```

1464 % Maybe we should define one more option for this:
1465 \setkomafont{subject}{\normalfont\sffamily}% because of KOMA-Script class
1466 \setkomafont{title}{\normalfont\sffamily}% because of KOMA-Script class
1467 (*1)
1468 \TitlePageStyle[pagenummer=1]{Markus-1}
1469 \maketitle[%
1470   titlepagefont={\normalfont\sffamily},% to show is without KOMA-Script class
1471   title=\textcolor{red}{Titel im Stil \texttt{Markus-1}},
1472   subject=\textcolor{red}{Eine Klassifizierung der Arbeit},
1473   subtitle=\textcolor{red}{Untertitel},
1474   publisher=\textcolor{red}{Verlag},
1475   uppertitleback=\textcolor{red}{Oberer Bereich der Rückseite des Haupttitels
1476     im Stil \texttt{Markus-1}.},
1477   lowertitleback=\textcolor{red}{Unterer Bereich der Rückseite des Haupttitels
1478     im Stil \texttt{Markus-1}.},
1479   dedication=\textcolor{red}{Eine Widmung im Stil \texttt{Markus-1}},
1480   author=\textcolor{red}{Markus~Kohm\protect\and Sonst~Jemand}
1481 ]
1482 </1>
1483 (*2 | Spacer)
1484 (2)\TitlePageStyle[pagenummer=1]{Markus-2}
1485 (Spacer)\TitlePageStyle[pagenummer=1]{Spacer}
1486 \maketitle[%
1487   rulewidth=2pt,
1488   extratitle=\textcolor{red}{Das ist ein Schmutztitel im Stil \texttt{%
1489 (2)      Markus-2}},
1490 (Spacer)      Spacer}},
1491 (*Spacer)
1492   titlehead=\textcolor{red}{\includegraphics{Logo}},
1493 </Spacer>
1494   title=\textcolor{red}{Titel im Stil \texttt{%
1495 (2)      Markus-2}},
1496 (Spacer)      Spacer}},
1497   subject=\textcolor{red}{Eine Klassifizierung der Arbeit},
1498   subtitle=\textcolor{red}{Untertitel},
1499   publisher=\textcolor{red}{Verlag},
1500   uppertitleback=\textcolor{red}{Oberer Bereich der Rückseite des Haupttitels
1501     im Stil \texttt{%
1502 (2)      Markus-2}.},
1503 (Spacer)      Spacer}.},
1504   lowertitleback=\textcolor{red}{Unterer Bereich der Rückseite des Haupttitels
1505     im Stil \texttt{%
1506 (2)      Markus-2}.},
1507 (Spacer)      Spacer}.},
1508   dedication=\textcolor{red}{Eine Widmung im Stil \texttt{%
1509 (2)      Markus-2}},
1510 (Spacer)      Spacer}},
1511   author=\textcolor{red}{Markus~Kohm}
1512 ]

```

```

1513 </2 | Spacer>
1514 </Markus | Spacer>
1515 <*KIT>
1516 \TitlePageStyle{KIT}
1517 \maketitle[%
1518   mainlogo={\textcolor{red}{%
1519     \includegraphics[width=40mm,height=18.5mm]{KITLogo_RGB}}},%
1520   % You may additionally change titlehead. Original definition of titlehead
1521   % is:
1522   titlehead={\usetitleelement{mainlogo}\hspace*{\fill}},%
1523   title=\textcolor{red}{Titel der Arbeit\im Stil \texttt{KIT}},%
1524   subject=\textcolor{red}{Klassifizierung der Arbeit},%
1525   author=\textcolor{red}{Markus~Kohm},%
1526   faculty=\textcolor{red}{Fakultät für Informatik},%
1527   chair=\textcolor{red}{%
1528     Institute for Program Structures\and Data Organization (IPA)},%
1529   advisor={\textcolor{red}{Titel Vorname Nachname}\and
1530     \textcolor{red}{Titel Vorname Nachname}},%
1531   referee={\textcolor{red}{Titel Vorname Nachname}\and
1532     \textcolor{red}{Titel Vorname Nachname}},%
1533   duration=\textcolor{red}{XX. Monat 20XX -- XX. Monat 20XX},%
1534   university=\textcolor{red}{\KITlongname},%
1535   homepage=\textcolor{red}{\KITurl}}%
1536 ]
1537 </KIT>
1538 <*JT-Aufsätze>
1539 \TitlePageStyle{JT-Aufsätze}
1540 \maketitle[%
1541   % There are only three official elements:
1542   author={\textcolor{red}{Markus Kohm}},%
1543   title={\textcolor{red}{Titel der Arbeit angelehnt an Jan Tschicholds
1544     ausgewählte Aufsätze über Fragen der Gestalt des Buches und der
1545     Typographie}},
1546   titlefont=\normalfont,% You may change the font of the main title
1547   publisher={\textcolor{red}{Der Verlag}}
1548   % Nevertheless, you may use extratitle, lowertitleback and uppertitleback.
1549   % See Markus-2 for more information about those.
1550 ]
1551 </JT-Aufsätze>
1552 <*JT-Geschichte>
1553 \TitlePageStyle{JT-Geschichte}
1554 \maketitle[%
1555   % There are only four official elements:
1556   author={\textcolor{red}{Markus Kohm}},%
1557   title={\textcolor{red}{Titel der Arbeit angelehnt an Jan Tschicholds
1558     Geschichte der Schrift in Bildern}},
1559   titlefont=\itshape,% You may change the font of the main title
1560   publisher={\textcolor{red}{Der Verlag in seiner Langform}},
1561   place={\textcolor{red}{Der Ort}}

```

```

1562 % Nevertheless, you may use extratitle, lowertitleback and uppertitleback.
1563 % See Markus-2 for more information about those.
1564 ]
1565 </JT-Geschichte>
1566 <*JT-Typography>
1567 \TitlePageStyle{JT-Typography}
1568 \maketitle[%
1569 % There are only four official elements:
1570 author={\textcolor{red}{Markus Kohm}},%
1571 title={\textcolor{red}{Titel der Arbeit}},
1572 subtitle={\textcolor{red}{angelehnt an the new Typography}},
1573 publisher={\textcolor{red}{Veröffentlicht für einen Verlag oder auch nicht}},
1574 place={\textcolor{red}{Der Ort}},
1575 date={\textcolor{red}{2012}}
1576 % Nevertheless, you may use extratitle, lowertitleback and uppertitleback.
1577 % See Markus-2 for more information about those.
1578 ]
1579 </JT-Typography>
1580 <*WWUM>
1581 \TitlePageStyle{WWUM}
1582 \renewcaptionname{ngerman}{\examinationdatename}{Tag der Promotion}
1583 %\renewcaptionname{ngerman}{\examinationdatename}{}
1584 %\renewcaptionname{ngerman}{\chairmanname}{Dekan}
1585 %\renewcaptionname{ngerman}{\chairmanname}{Dekanin}
1586 \maketitle[%
1587 title={\textcolor{red}{Titel der Arbeit}},
1588 subject={\textcolor{red}{Inaugural-Dissertation}},
1589 academicgrade={\textcolor{red}{Doktorgrades}},
1590 discipline={\textcolor{red}{Physik}},
1591 sience={\textcolor{red}{Naturwissenschaften}},
1592 chair={\textcolor{red}{Experimentelle Physik}},
1593 faculty={\textcolor{red}{Mathematisch-Naturwissenschaftlichen}},
1594 author={\textcolor{red}{Mein Name}},
1595 place={\textcolor{red}{Geburtsort}},
1596 referee={\textcolor{red}{Peter Mustermann}\and
1597 [f]\textcolor{red}{Petra Musterfrau}},
1598 professor={\textcolor{red}{Klaus Naseschwarz}}
1599 ]
1600 </WWUM>
1601 \end{document}

1602 <!*README>
1603 \documentclass{scrdoc}
1604 \usepackage[utf8]{inputenc}
1605 \usepackage[T1]{fontenc}
1606 \usepackage{lmodern}
1607 \usepackage[english]{babel}
1608 \usepackage{xltabular}
1609 \usepackage{ragged2e}
1610 \usepackage{booktabs}

```

```

1611 \usepackage{graphicx}
1612 \usepackage{hypdoc}
1613 \CodelineIndex
1614 \RecordChanges
1615 \EnableCrossrefs
1616 \GetFileInfo{uni-titlepage.drv}
1617 \begin{document}
1618 \title{More Titlepage Styles with Package \File{uni-titlepage}\footnote{This is
1619     version \fileversion{} of file \File{\filename}.}}
1620 \author{Markus Kohm\footnote{Markus Kohm \textless komascript\textcircled{\tiny
1621     at}gmx.info\textgreater{}}}
1622 \date{\fileversion{}\footnote{\textbf{Note:} All version below 0.9 are ALPHA
1623     versions. Everything may change. Everything may break. Everything may
1624     happen.} \filedate}
1625 \maketitle
1626 \begin{abstract}
1627 \<!/README\>
1628 \<!*README\>
1629 -----
1630
1631 This work may be distributed and/or modified under the conditions of
1632 the LaTeX Project Public License, version 1.3c of the license.
1633 The latest version of this license is in
1634     http://www.latex-project.org/lppl.txt
1635 and version 1.3c or later is part of all distributions of LaTeX
1636 version 2005/12/01 or later.
1637
1638 This work has the LPPL maintenance status "maintained".
1639
1640 The Current Maintainer and author of this work is Markus Kohm.
1641
1642 -----
1643
1644 # ABSTRACT
1645
1646 \<!/README\>
1647 Creation of title pages is something most authors should not have to do.
1648 But reality is not perfect, so a lot of authors have to do it. In 2009
1649 \<!/README\>KOMA started the title page project at \url{https://komascript.de/tit
1650 \<!/README\>KOMA started the title page project at <https://komascript.de/titlepag
1651 to collect real title pages and implement them with a well defined interface.
1652 \<!/README\>In 2021 the project has been moved to \url{https://github.com/komascr
1653 \<!/README\>In 2021 the project has been moved to <https://github.com/komascript/v
1654 and renamed.
1655
1656 Now, changing from one title page style to another would be very
1657 simple. Nevertheless implementation of a new title page style may be still
1658 difficult. But maybe the guys of the title page project would help you. Just
1659 ask!

```

```

1660 (*README)
1661
1662 # Unpacking and Installation for Developers and Distributors
1663
1664 To unpack and install all files, you can download the source from github
1665 and then run:
1666
1667     l3build install
1668
1669 Afterwards you can build the manual and the PDFs of the examples using:
1670
1671     l3build doc
1672
1673 As an alternative you can use the CTAN source distribution. This already
1674 contains the user manual and the PDFs of the example files. So you only have
1675 to run
1676
1677     tex uni-titlepage.dtx
1678
1679 to generate the package file 'uni-titlepage.sty', the title definition files
1680 'title-*.def' and the example titlepages 'titlepage-*.tex'.
1681
1682 Please note, the 'title-*.def' files are run-time files. Together with
1683 'uni-titlepage.sty' they have to be placed in 'tex/latex/uni-titlepage' inside
1684 a TDS tree. All files 'titlepage-*.tex' and 'titlepage-*.pdf' as well as
1685 'uni-titlepage.pdf' are part of the documentation and should be placed in
1686 'doc/latex/uni-titlepage/' of the TDS tree.
1687
1688 # Unpacking and Installation for Users
1689
1690 Users can use the installation described at
1691 [Unpacking and Installation for Developers and Distributors]. However, if
1692 your TeX distributor already distributes a ready for installation package, you
1693 do not need and should not create files and copy them yourself. Just use the
1694 package manager of your TeX distribution to install the package.
1695
1696 # How to Contribute
1697
1698 If you have made a title definition that is not specific for a single project
1699 but could be of interest for other users, you can either
1700
1701 * make your own 'uni-titlepage-F00' package with its own manual and [upload it
1702 to ctan](https://www.ctan.org/upload),
1703 * contribute in adding it to 'uni-titlepage'.
1704
1705 The first option has the advantage, that you are free. There won't be any code
1706 reviews by the 'uni-titlepage' developers. You don't need to use the same
1707 coding style. There is not need to accept the license of 'uni-titlepage'
1708 etc. But in this case you have to take care to keep it compatible with future

```

1709 releases of ‘uni-titlepage’ and it will not be presented in the
 1710 ‘uni-titlepage’ manual.
 1711
 1712 The second option has the advantage, that after accepting your code, the
 1713 ‘uni-titlepage’ developers will try to keep it working even if they change
 1714 ‘uni-titlepage’. But there are several restrictions to your code, before it
 1715 will be accepted. For example, you should always try to use general options,
 1716 if possible. *Static text* (not handled by options) should be configurable via
 1717 ‘\newcaptionname’, ‘\providecaptionname’ and ‘\renewcaptionname’ and should be
 1718 available at least in English and German (but if we can, we help in
 1719 translating them). The coding style and quality is also a criterion.
 1720
 1721 </README>
 1722 <!*README>
 1723 \end{abstract}
 1724 \DocInput{uni-titlepage.dtx}
 1725 \end{document}
 1726 </!README>

Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in *roman* refer to the code lines where the entry is used.

Symbols	
\"	481, 482, 492, 494, 526, 536, 632, 699, 706, 711, 786, 787, 790, 795, 1414
\,	1049, 1418, 1455
\@	343
\@academicgrade	283, 619, 626, 633, 643, 650, 657, 680, 689, 697
\@advisor	285, 935, 1011, 1135
\@author	248, 926, 959, 1002, 1031, 1047, 1081, 1120, 1148, 1164, 1183, 1322, 1335, 1342
\@chair	256, 663, 668, 673, 991, 1040
\@company	252, 934
\@course	251, 933
\@current	225, 235
\@currname	225, 235
\@date	249, 928, 963, 1015, 1036, 1059, 1088, 1188
\@dedication	292, 1354, 1357, 1363
\@discipline	282, 620, 627, 634, 681, 690, 698, 1003
\@duration	250, 931, 1139
\@evenhead	873
\@extratitle	1283, 1297, 1299, 1330
\@faculty	255, 662, 667, 672, 682, 691, 699, 989
\@firstofone	95, 357
\@fnsymbol	778
\@gobble	93, 1095, 1097, 1098, 1099, 1101, 1102, 1104, 1105, 1106, 1149, 1150, 1151, 1152, 1155, 1167, 1168, 1169, 1170, 1173
\@homepage	244, 828, 1143
\@lowertitleback	1199, 1231
\@mainlogo	290, 807, 821, 831, 854
\@makefnmark	779, 780
\@matriculationnumber	284, 932, 1004
\@nameuse	302
\@oddhead	869, 873
\@oldmakefnmark	779, 780
\@oralexaminationdate	291, 1251, 1274
\@place	

287, 621, 628, 635, 793, 1015, 1034, 1048, 1177, 1178, 1187	\arraystretch 1262
\@professor 257, 992, 1271	\askforoverwritefalse 11
\@publisher 288, 965, 1087, 1160, 1176, 1189, 1190, 1306, 1310, 1336	\AtBeginDocument 359
\@referee 286, 936, 1133, 1247, 1273	\atthename 382
\@restonecolfalse 119	\author 248, 1620
\@restonecoltrue 117	author (Option) 248
\@science 281, 681, 690, 698	
\@spaces 545	B
\@subject 258, 644, 651, 658, 678, 687, 696, 921, 949, 950, 995, 1054, 1080, 1118	\bachelorthesisname 268, 364
\@subtitle 253, 955, 1026, 1057, 1085, 1185	\baselineskip 212, 618, 620, 625, 627, 632, 634, 925, 969, 1006, 1013, 1054, 1057, 1076, 1080, 1082, 1085, 1109, 1157, 1183, 1189, 1340
\@subtitlefont 331, 955, 1056, 1084, 1185	\batchfile 1
\@thanks 968	blackborder (Option) 586
\@title 247, 919, 953, 994, 1025, 1042, 1055, 1083, 1116, 1158, 1165, 1184, 1323	
\@titlehead 241, 820, 853, 915, 941, 943, 1072, 1074, 1113	C
\@titlepagefont 312, 823, 824, 856, 857, 861, 862, 870, 877, 878, 881, 883, 894, 895, 910, 1116, 1227, 1231, 1309, 1318, 1339, 1381	\c@footnote 778
\@tpf@extra 881, 884, 1164, 1176, 1178	\catcode 343
\@university 254, 621, 628, 635, 641, 648, 655, 683, 692, 700, 783, 936, 987, 1143	\chair 256
\@uppertitleback . 1200, 1201, 1227	chair (Option) 256
\@uppertitlebacke 1199	\chairmanname 364, 1271, 1584, 1585
\@usetitleelement@error 295	\colorlet 1376
	\columnwidth 189
A	\company 252
\academicgrade 283	company (Option) 252
academicgrade (Option) 283	\companyname 386, 436, 490, 934, 935
\advanve 169	\course 251
\advisor 285	course (Option) 251
advisor (Option) 285	\coursename 385, 434, 488, 932
\advisorname 364, 935, 1008, 1134, 1135	\csname 77, 227, 228, 229, 231, 289, 555, 871, 1059, 1081, 1087, 1088, 1266, 1267, 1342, 1357
\and 1081, 1127, 1242, 1247, 1268, 1341, 1458, 1480, 1529, 1531, 1596	
	D
	\date 249, 1622
	date (Option) 249
	\dedication 292
	dedication (Option) 292
	\DefineFamily 79
	\DefineFamilyKey 84, 89, 230, 236, 243, 246, 261, 294, 317, 322, 327, 332, 597, 606, 1202, 1213, 1286
	\DefineFamilyMember 80, 572
	\DefineReplaceTitleKey . . 218, 280
	\DefineSimpleTitleKey 218, 247, 248, 249, 250, 251, 252, 253, 254,

255, 256, 257, 281, 282, 283, 284, 285, 286, 287, 288, 290, 291	\FamilyOptions 81, 238
\degreethesisname 266, <u>364</u>	\FamilyProcessOptions 363
\dimexpr 603, 612, 914, 930, 981, 982, 1064, 1065, 1067, 1069, 1073, 1095, 1097, 1098, 1099, 1101, 1102, 1104, 1105, 1106, 1109, 1111, 1112, 1142, 1150, 1151, 1168, 1169	\fbox 976
\diplomathesisname 265, <u>364</u>	\fe@male 1265, 1266, 1267
\discipline <u>282</u>	\femaleordinal <u>364</u>
discipline (Option) <u>282</u>	\femalerefereename <u>364</u>
\do 226, 260	\File 1618, 1619
\DocInput 1724	\file 39, 40, 41, 42, 43, 44, 45, 46, 47, 48, 49, 50, 51, 52, 53, 54, 55, 56, 57, 58, 59, 60, 61, 62, 63, 64, 65, 67
\documentclass 1366, 1603	\filedate 1624
\dp 1164, 1175, 1178	\filename 1619
\duration <u>250</u>	\fileversion 1619, 1622
duration (Option) <u>250</u>	\fill 821, 854, 1239, 1259, 1393, 1522
\durationname 383, 430, 484, 931, 1139	final (Option) <u>587</u>
E	\fontsize 986, 988, 990
\edef 339	\footnote 777, 1618, 1620, 1622
\endcsname 77, 92, 227, 228, 229, 231, 289, 496, 555, 871, 1059, 1081, 1087, 1088, 1266, 1267, 1342, 1357	\footnoterule 776
\endminipage 194	\footnotesize 775
\endpreamble 36	\from 39, 40, 41, 42, 43, 44, 45, 46, 47, 48, 49, 50, 51, 52, 53, 54, 55, 56, 57, 58, 59, 60, 61, 62, 63, 64, 65, 67
\englishordinal 389, 411, <u>495</u>	\fromname 364, 703, 925, 1030, 1118
\engordnumber 497	\fromplacename 364, 1033, 1048
\enskip 1187, 1245, 1251	\fullsizetitle <u>162</u>
\evensidemargin 209	fullsizetitle (Umgebung) 24
\examinationdatename 388, 440, 494, 1275, 1276, 1582, 1583	G
\examinationname 387, 438, 492, 618, 625, 632	\generate 38
\exittitle <u>101</u> , 148, 159	\GenericError 544
\extratitle <u>1283</u>	\geometry 181
extratitle (Option) <u>1283</u>	\germanfemaleordinal 461, <u>514</u>
F	\germanmaleordinal 463, <u>514</u>
\faculty <u>255</u>	\germanordinal 459, <u>514</u>
faculty (Option) <u>255</u>	\GetFileInfo 1616
\FamilyBoolKey 586, 587	\Gm@bindingoffset 169, 173, 206
\FamilyKeyStateProcessed 85, 90, 232, 243, 246, 277, 294, 319, 324, 329, 334, 604, 613, 1210, 1221, 1293	H
\FamilyOption 82	\headheight 197, 870
	\headsep 197, 1065, 1067
	\hfill 1143
	\homepage <u>244</u> , 829
	homepage (Option) <u>244</u>
	\ht 1064, 1073
	\Huge 878, 1165, 1184
	\huge 953, 1120

I	
<code>\if@atdocument</code>	356, 810, 844
<code>\if@resonecol</code>	92
<code>\if@restonecol</code>	97, 137
<code>\if@twocolumn</code>	116
<code>\if@twoside</code> 122, 145, 146, 147, 1349	
<code>\ifblackborder</code>	973, 982
<code>\ifcsname</code>	92, 496
<code>\IfFileExists</code> 337, 808, 832, 833, 834, 835, 836, 837, 838, 839, 842	
<code>\iffinal</code>	640, 644, 647, 651, 654, 658, 1240, 1250
<code>\Ifstr</code>	262, 263, 264, 265, 266, 267, 268, 279, 1265
<code>\ifstr</code>	279
<code>\ifToplevel</code>	3, 70
<code>\ignorespaces</code>	663, 668, 673, 987, 989, 991, 992, 994, 995, 999, 1002, 1003, 1004, 1008, 1011, 1015, 1025, 1026, 1030, 1031, 1033, 1034, 1054, 1055, 1057, 1059, 1080, 1083, 1085, 1088, 1310, 1342
<code>\includegraphics</code>	814, 848, 1388, 1492, 1519
<code>\inittitle</code>	101, 144, 152, 773
<code>\inittitlestyle</code>	112, 340
K	
<code>\keepsilent</code>	10
<code>\KIT@logo</code>	832, 833, 834, 835, 836, 837, 838, 839, 840, 842, 848
<code>\KITlongname</code>	703, 789, 1534
<code>\KITurl</code>	703, 829, 1535
<code>\KOMAOPTIONS</code>	179
L	
<code>\l@addto@macro</code>	226, 260
<code>\LARGE</code>	1025, 1055, 1083, 1188, 1341
<code>\Large</code>	917, 919, 921, 957, 963, 965, 1026, 1028, 1030, 1033, 1036, 1118, 1122, 1124, 1183
<code>\large</code> 862, 1054, 1057, 1059, 1080, 1081, 1085, 1087, 1088, 1139, 1143, 1164, 1310, 1340, 1342	
<code>\line</code>	1095, 1099, 1102, 1106, 1152, 1155, 1170, 1173
<code>\linebreak</code>	1341
<code>\linespread</code>	909
<code>\linethickness</code>	1152, 1155, 1170, 1173
<code>\linewidth</code>	188, 930, 982, 998, 1000, 1007, 1009, 1014, 1074
<code>\lowertitleback</code>	1199
<code>lowertitleback (Option)</code>	1199
<code>\lsstyle</code>	884
M	
<code>\mainlogo</code>	290, 813, 847
<code>mainlogo (Option)</code>	290
<code>\makeatletter</code>	341, 1381
<code>\makeatother</code>	1381
<code>\makebox</code>	213, 1142
<code>\makemaintitle</code>	101, 146, 155, 900
<code>\makemaintitleback</code>	101, 146, 156, 1223
<code>\makeposttitle</code>	101, 147, 157, 1352
<code>\makeposttitleback</code>	101, 147, 158, 1352
<code>\makeprettitle</code>	101, 145, 153, 1295
<code>\makeprettitleback</code>	101, 145, 154, 1295, 1329, 1334, 1348
<code>\maketitle</code>	2, 100, 141, 1383, 1411, 1430, 1434, 1450, 1469, 1486, 1517, 1540, 1554, 1568, 1586, 1625
<code>\MakeUppercase</code>	884, 1183, 1184, 1185, 1187, 1188, 1190, 1376
<code>\maleordinal</code>	364
<code>\malerefereename</code>	364
<code>\masterthesisname</code>	267, 364
<code>\matriculationnumber</code>	284
<code>matriculationnumber (Option)</code>	284
<code>\matriculationnumbername</code>	384, 432, 486, 932
<code>\mbox</code>	978
<code>\minipage</code>	192
<code>\Msg</code> 4, 5, 6, 7, 8, 9, 71, 72, 73, 74, 75	
N	
<code>\newcaptionname</code>	1717
<code>\newif</code>	97
<code>\newkomafont</code>	315
<code>\newsavebox</code>	162
<code>\nobreakspace</code>	786, 787, 1015, 1414
<code>\noexpand</code>	340, 341, 342, 343
<code>\nopostamble</code>	66
<code>\nopreamble</code>	66

\NowButAfterBeginDocument . . .	oralexaminationdate (Option) 291
..... 24 , 355 , 749	\oralexaminationdatename . . .
\numexpr 1129 364 , 1251 , 1274
O	\ordinal 364 , 1130 , 1245
\oddsidemargin 203	\oval 1097 , 1104
\ofthename 364 , 935 , 936	P
\onecolumn 117	\PackageNotLoadedError . . 543 , 556
Optionen:	\PackageWarning 174 , 219 , 800
academicgrade 283	pagenumber (Option) 83
advisor 285	pagestyle (Option) 87
author 248	\paperheight 187 , 1099 ,
blackborder 586	1101 , 1104 , 1105 , 1106 , 1111
chair 256	\paperwidth 166 , 1095 ,
company 252	1097 , 1098 , 1102 , 1112 , 1142
course 251	\parfillskip 908
date 249	\parindent 907
dedication 292	\parskip 906
discipline 282	\place 287 , 794
duration 250	place (Option) 287
extratitle 1283	\preamble 14
faculty 255	\presentationinformationDHBW
final 587 616 , 923
homepage 244	\presentationinformationKIT .
lowertitleback 1199 616 , 1122
mainlogo 290	\presentationinformationTUHH
matriculationnumber 284 616 , 1028
oralexaminationdate 291	\presentationinformationWWUM
pagenumber 83 616 , 1044
pagestyle 87	\presentedbyname 364 , 748 , 999 , 1046
place 287	\professor 257
professor 257	professor (Option) 257
publisher 288	\projectpapername 262 , 364
referee 286	\providecaptionname 392 ,
rulesep 588	394 , 396 , 398 , 401 , 403 , 405 ,
rulewidth 588	407 , 410 , 412 , 414 , 416 , 418 ,
sience 281	420 , 422 , 424 , 426 , 429 , 431 ,
student 280	433 , 435 , 437 , 439 , 442 , 444 ,
subjectfont 321	446 , 448 , 450 , 452 , 454 , 456 ,
subject 258	458 , 460 , 462 , 464 , 466 , 468 ,
subtitlefont 331	470 , 472 , 474 , 476 , 478 , 480 ,
subtitle 253	483 , 485 , 487 , 489 , 491 , 493 ,
titlefont 326	623 , 630 , 645 , 652 , 665 , 670 ,
titlehead 241	685 , 694 , 704 , 709 , 751 , 1717
titlepagefont 312	\ps@empty 868
title 247	\ps@maintitle 867
university 254	\publisher 288 , 899
uppertitleback 1199	publisher (Option) 288
\oralexaminationdate 291	\publishers 899

<code>\put</code>	1094, 1097, 1098, 1101, 1104, 1105, 1151, 1154, 1169, 1172	<code>\studentreserchname</code>	364
		<code>\subject</code>	258
		<code>subject (Option)</code>	258
		<code>\subject@font</code>	321, 921, 950, 1053, 1079
Q		<code>subjectfont (Option)</code>	321
<code>\quad</code>	1000, 1009	<code>\subtitle</code>	253
		<code>subtitle (Option)</code>	253
		<code>subtitlefont (Option)</code>	331
R			
<code>\raisebox</code>	1064, 1073	T	
<code>\RecordChanges</code>	1614	<code>\ta@bcor</code>	171, 173, 179, 181, 207
<code>\referee</code>	286	<code>\tabcolsep</code>	930
<code>referee (Option)</code>	286	<code>\test@malefemale</code>	1263, 1268, 1272
<code>\refereename</code>	364, 703, 936, 1125, 1133, 1245	<code>\textbf</code>	1143, 1622
<code>\renewcaptionname</code>	715, 716, 719, 720, 723, 724, 727, 728, 731, 732, 735, 736, 739, 740, 743, 744, 754, 757, 760, 763, 766, 769, 1582, 1583, 1584, 1585, 1717	<code>\textcircled</code>	1620
<code>\renewenvironment</code>	113	<code>\textcolor</code>	1376, 1385, 1394, 1395, 1396, 1397, 1398, 1399, 1400, 1401, 1402, 1403, 1404, 1405, 1406, 1412, 1413, 1415, 1416, 1418, 1421, 1422, 1423, 1424, 1425, 1426, 1435, 1436, 1437, 1438, 1439, 1440, 1441, 1443, 1445, 1452, 1453, 1455, 1456, 1457, 1458, 1460, 1471, 1472, 1473, 1474, 1475, 1477, 1479, 1480, 1488, 1492, 1494, 1497, 1498, 1499, 1500, 1504, 1508, 1511, 1518, 1523, 1524, 1525, 1526, 1527, 1529, 1530, 1531, 1532, 1533, 1534, 1535, 1542, 1543, 1547, 1556, 1557, 1560, 1561, 1570, 1571, 1572, 1573, 1574, 1575, 1587, 1588, 1589, 1590, 1591, 1592, 1593, 1594, 1595, 1596, 1597, 1598
<code>\rlap</code>	780	<code>\textgreater</code>	1621
<code>\rule</code>	972, 1065	<code>\textheight</code>	191, 981, 1064, 1065, 1067, 1068
<code>rulesep (Option)</code>	588	<code>\textless</code>	1620
<code>rulewidth (Option)</code>	588	<code>\texttt</code>	1412, 1435, 1438, 1442, 1444, 1445, 1452, 1471, 1476, 1478, 1479, 1488, 1494, 1501, 1505, 1508, 1523
		<code>\textwidth</code>	190, 591, 942, 1069, 1226, 1230
S		<code>\thanks</code>	777
<code>\scr@ifundefinedorrelax</code>	98, 99, 167, 168, 172, 204, 205, 296, 299, 312, 714, 718, 722, 726, 730, 734, 738, 742, 753, 756, 759, 762, 765, 768, 809, 812, 843, 846, 880	<code>\thefootnote</code>	778
<code>\selectfont</code>	909, 986, 988, 990	<code>\thename</code>	364, 1015
<code>\seminarpapername</code>	263, 364	<code>\tiny</code>	1143, 1620
<code>\setkomafont</code>	1382, 1465, 1466		
<code>\sience</code>	281		
<code>sience (Option)</code>	281		
<code>\small</code>	775		
<code>\stepcounter</code>	138		
<code>\strut</code>	663, 668, 673, 987, 989, 991, 992, 994, 995, 999, 1002, 1003, 1004, 1008, 1011, 1015, 1025, 1026, 1030, 1031, 1033, 1034, 1054, 1055, 1057, 1059, 1080, 1083, 1085, 1088, 1164, 1178, 1184, 1189, 1310, 1341		
<code>\strutbox</code>	1064, 1073, 1164, 1175, 1178		
<code>student (Option)</code>	280		
<code>\studentresearchname</code>	264, 367, 399, 449		

<code>\title</code>	247 , 1618	U	
<code>title</code> (Option)	247	Umgebungen:	
<code>\title@font</code>	326	<code>fullsizetitle</code>	24
<code>\title@rulesep</code>	588 , 1067 , 1069 , 1150 , 1151 , 1168 , 1169	<code>titlepage</code>	24 , 98
<code>\title@rulewidth</code> 588 , 1066 , 1069 , 1149 , 1152 , 1155 , 1167 , 1170 , 1173	<code>\unitlength</code>	1092
<code>\titlebox</code>	162	<code>\university</code>	254 , 784
<code>\titlefont</code>	326 , 328 , 889 , 890 , 919 , 953 , 1055 , 1083 , 1158 , 1165 , 1184	<code>university</code> (Option)	254
<code>titlefont</code> (Option)	326	<code>\unskip</code> 987 , 989 , 991 , 992 , 994 , 995 , 999 , 1002 , 1003 , 1004 , 1008 , 1011 , 1164 , 1178 , 1184 , 1189
<code>\titlehead</code>	241 , 821 , 854	<code>\uppertitleback</code>	1199
<code>titlehead</code> (Option)	241	<code>uppertitleback</code> (Option)	1199
<code>\TitleOption</code>	2 , 78	<code>\url</code>	1649 , 1652
<code>\TitleOptions</code> 2 , 78 , 114 , 143 , 164 , 346 , 1429	<code>\usebox</code>	213
<code>\titlepage</code>	98	<code>\usefont</code>	857
<code>titlepage</code> (Umgebung)	24	<code>\usepackage</code> 1367 , 1368 , 1369 , 1370 , 1371 , 1372 , 1373 , 1374 , 1375 , 1377 , 1604 , 1605 , 1606 , 1607 , 1608 , 1609 , 1610 , 1611 , 1612
<code>titlepage</code> (Umgebung)	98	<code>\usetitleelement</code>	24 , 295 , 1393 , 1522
<code>titlepagefont</code> (Option)	312		
<code>\TitlePageStyle</code> 2 , 336 , 362 , 1380 , 1410 , 1433 , 1449 , 1468 , 1484 , 1485 , 1516 , 1539 , 1553 , 1567 , 1581	V	
<code>\titlepagestyle</code>	87 , 121 , 135	<code>\value</code>	123 , 124 , 129 , 134
<code>\topmargin</code>	197	<code>\vbox</code>	211
<code>\topskip</code>	198	<code>\vsize</code>	187 , 191 , 914 , 1319
<code>\totalheight</code>	1073	<code>\vskip</code>	197 , 198 , 212 , 951 , 954 , 956 , 962 , 964 , 966 , 969 , 985 , 1006 , 1013 , 1054 , 1057 , 1076 , 1080 , 1082 , 1085 , 1109 , 1115 , 1117 , 1119 , 1121 , 1123 , 1141 , 1249 , 1340 , 1358
<code>\tp@dokeys</code>	218 , 260	<code>\vss</code>	214
<code>\tp@replacewarning</code>	218		
<code>\tp@undefinedtitle</code> 101 , 153 , 154 , 155 , 156 , 157 , 158		

Change History

v0.5e	\presentationinformationDHBW: \if replaced by \ifx 40	v0.2a	\makemaintitle: Markus-2: \leavevmode added before \subject@font to avoid line break after \subject@font using package color or xcolor 47
v0.1	General: Start of project 25		
v0.2	General: First version using docstrip 25 new style DHBW 39 new style Spacer 39		\makeprettitle: Markus-1: Usage of \@titlepagefont fixed 55

v0.3		\presentationinformationKIT:	
\@homepage: new internal	31	\NowButAfterBeginDocument	
General: new style KIT	39	not needed any more	40
\homepage: new command . . .	31	provide sevaral English and	
homepage: new option	31	German languages	40
v0.4		\presentationinformationTUHH:	
\@mainlogo: new (internal) . .	33	\NowButAfterBeginDocument	
\@usetitleelement@error:		not needed any more	40
new (internal)	33	provide sevaral English and	
General: new style		German languages	40
JT-Aufsaetze	39	\presentationinformationWWUM:	
new style JT-Geschichte . .	39	new style WWUM	40
new style JT-Typography . .	39	\presentedbyname: changed	
\mainlogo: new	33	value for 'WWUM'	43
mainlogo: new	33	\refereename:	
\usetitleelement: new	33	\NowButAfterBeginDocument	
v0.4a		not needed any more	42
\makemaintitle: fix influence		provide sevaral English and	
of height of titlehead to		German languages	42
vertical alignment of rule . .	50	\sience: new	32
v0.4b		sience: new	32
\makeprettitle: Markus-1:		v0.5a	
publisher page may be		\presentedbyname: fixed	
omitted	55	swissgerman instead of	
v0.4c		swiss	43
subject: typing error fixed		v0.5b	
(mrpiggi)	32	\presentedbyname: changes	
v0.5		have to be delayed	43
\@sience: new	32	v0.5c	
\chairmannname: new	35	\advisorname: not needed	
\femaleordinal: new	35	\AtBeginDocument removed	35
\femalerefereename: new . . .	35	\bachelorthesisname: not	
\fromname:		needed \AtBeginDocument	
\NowButAfterBeginDocument		removed	35
not needed any more	42	\chairmannname: not needed	
provide sevaral English and		\AtBeginDocument removed	35
German languages	42	\degreethesisname: not needed	
\KITlongname:		\AtBeginDocument removed	35
\NowButAfterBeginDocument		\diplomathesisname: not	
not needed any more	42	needed \AtBeginDocument	
provide sevaral English and		removed	35
German languages	42	\femaleordinal: not needed	
\maleordinal: new	35	\AtBeginDocument removed	35
\malerefereename: new	35	\femalerefereename: not	
\presentationinformationDHBW:		needed \AtBeginDocument	
\NowButAfterBeginDocument		removed	35
not needed any more	40	\fromname: not needed	
provide sevaral English and		\AtBeginDocument removed	35
German languages	40		

\fromplacename: not needed		v0.5e	
\AtBeginDocument removed	35	\makemaintitleback: \ifstr	
\malerefereename: not needed		in scrbase renamed to	
\AtBeginDocument removed	35	\Ifstr	53
\masterthesisname: not needed		subject: \ifstr in scrbase	
\AtBeginDocument removed	35	renamed to \Ifstr	32
\ofthename: not needed		v0.5f	
\AtBeginDocument removed	35	General: autodetect several logo	
\oralexaminationdataname:		picture files	45
not needed		usage of l3build	1
\AtBeginDocument removed	35	v0.6	
\ordinal: not needed		\@academicgrade: renamed	
\AtBeginDocument removed	35	“degree” to “academic	
\presentedbyname: not needed		grade” to avoid name clash	
\AtBeginDocument removed	35	with the degree symbol ...	32
\projectpapername: not needed		General: package renamed from	
\AtBeginDocument removed	35	titlepage into	
\refereename: not needed		uni-titlepage	1
\AtBeginDocument removed	35	\academicgrade: renamed	
\seminarpapername: not needed		“degree” to “academic	
\AtBeginDocument removed	35	grade” to avoid name clash	
\studentreserchname: not		with the degree symbol ...	32
needed \AtBeginDocument		academicgrade: renamed	
removed	35	“degree” to “academic	
\thename: not needed		grade” to avoid name clash	
\AtBeginDocument removed	35	with the degree symbol ...	32