

New TX font package

Michael Sharpe

September 1, 2021

1 Introduction

This package is meant to be a replacement for Young Ryu's `txfonts`. It is a complete text (`newtxtext`) and math (`newtxmath`) package with roman text font provided by a Times clone, sans serif based on a Helvetica clone, typewriter faces, plus math symbol fonts whose math italic letters are from a Times Italic clone. As of version 1.4, `newtxtext` no longer depends on `txfonts` but is based on the richer source TeXGyre Termes, but `newtxmath` continues to use the `txfonts` math glyphs with many metric adjustments and some wholesale modifications.

VERY IMPORTANT: The math package changed substantially as of version 1.5, changing a number of glyphs, adding an option to reduce the sizes of large operators, and changing the integral signs to a choice of upright and slanted forms, each available in twelve variants. The new options are `upint` (upright integrals) and `smallerops` (smaller large operators.) Some previously available options may no longer have any effect. The changes are described in detail in the section on math mode options. A summary of the changes in version 1.5 is given in Appendix 1.

Version 1.60 likewise has many additions and changes that are summarized in Appendix 2. Most important is that `newtx` is now able to output a PDF/A-1b compliant pdf using `pdflatex`.

Another important change took place in version 1.65, where `theoremfont` was reimplemented using a new font family, `ntxth` instead of abusing `\textsl`. By default, users of `theoremfont` will see no change in its functionality, including the use of the macro `\textsl` to output italics with upright punctuation. A new option, `truestlanted`, to `newtxtext` has the following effects:

- `\textsl` now outputs slanted text rather than italics with upright punctuation text, but not affecting the usage of the `theoremfont` option to `newtxtext`.
- the former behavior of `\textsl` is now available through the new macro `\textth`, AKA `\textthit`.
- `\pagestyle{headings}` now functions as intended with slanted rather than upright figures in the headers.

This math package works, after possibly replacing its math Roman and Greek letters, with fonts other than Times that are intermediate in weight between Computer Modern and Times. The free font Linux Libertine is one particular target—it is of nearly the same x-height as Computer Modern, but, not being a *modern* font, does not have a high contrast ratio, and so appears denser than Computer Modern but not as much so as Times. It is meant as a replacement for Times, but differs from it in many characteristics, more similar to MinionPro than Times, and provides a better range of variants than Times—three weights (regular, semi-bold

and bold) rather than just two, and has expert features in all weights: old-style figures, more extensive and more interesting ligatures, and small caps. In my opinion, material typeset in Linux Libertine looks better than the corresponding material typeset in Times. This seems especially true on the screen. As of version 1.0, the package also offers support for MinionPro as a math font, but with limitations described in detail below. More recently, an option to provide math support for the garamondx text font package was added. Version 1.55 adds support for the SticksToo text fonts, a reworking of the STIX2 text fonts.

The newtx package differs from txfonts in the following ways:

- the new package is split into separate text and math packages that do not need to be used in conjunction;
- both text and math packages offer options not present in the original package, described below, including the option to use libertine Latin and Greek letters to replace Times, as well as a similar option minion;
- wide accent glyphs have been corrected (they should have zero depth) so that they no longer collide with the underlying glyph;
- for those who do not like the integral in txfonts, an emboldened version of the Computer Modern integral is made available, matching the weight of the txfonts symbols—this is no longer available since the original txfonts integral have been replaced;
- an upright partial derivative symbol has been added, named `\uppartial`;
- there is now an option to get braces more pleasing to older eyes;
- macros have been added to bring the calls to Greek symbols more into conformity with PSNFSS and Mathtime Pro 2;
- problems using AMS macro packages before txfonts are settled;
- `\coloneq` and `\eqcolon` now point to the correct glyphs;
- The problem with the ogonek accent and tabular environments (bad definition of `\k`) is fixed: (the definition of `\k` is removed as of version 1.628, being no longer of use);
- The default encoding for newtxtext is now T1, but support is offered also for OT1 and LY1. As some add-on packages are available only in T1, that seems the best current choice.
- Sans serif is by default taken from TeXGyreHeros, and by default at 90% of the scale factor (set by `scaled`, default value 1). The option `helvratio=.98` will change that to 98%.
- `\varkappa` \varkappa has been moved from AMSb to lettersA, and is now accompanied by an upright form `\upvarkappa` \varkappa which behaves as it should when using the frenchmath option.

2 Text mode options

Beginning with version 1.4, the text font component of newtx is no longer dependent on the txfonts, and is constructed entirely from TeXGyre Termes and some modifications thereof.

The text mode environment invoked by

```
\usepackage{newtxtext}
```

has several options, a number new to version 1.4: you may write

```
\usepackage[scaled=.93]{newtxtext}
```

to load the roman and typewriter text fonts at 93% of normal size, and the sans serif (Helvetica clone) at scale $0.9 * 0.93$. This is not of much utility if the package is used with the math package `newtxmath` to which it is already matched, but may be with other math packages. The options

```
\usepackage[scaled=.95,helvratio=.96]{newtxtext}
```

load roman and typewriter text fonts at 95% of normal size, and the sans serif (Helvetica clone) at scale $0.95 * 0.96$.

The option `osf` instructs the text fonts to use old-style figures 1234567890 rather than the default lining figures 1234567890. As of version 1.23, `newtxtext` loads initially with lining figures so the math package uses lining figures in math mode. The option `osf` changes the default to old-style figures in text at the very end of the preamble, forcing the use of old-style figures in text, but not math. In earlier versions, it was necessary to run `\useosf` after loading `newtxmath`. This is no longer required.

(New in version 1.65.) Slanted text is now provided as part of the `newtxtext` package, but requires that you specify the new option `truestlanted`. Without this option, `\textsl` will continue to behave as in earlier versions, outputting italic text with upright punctuation. If you use the `babel` package, you should load it before `newtxtext`—for example:

```
\usepackage[<babel options>]{babel}  
\usepackage[osf]{newtxtext}
```

More generally, the pattern of the preamble should be:

```
<encoding options>  
[optional] \usepackage{substitutefont} % so you can change babel's fonts  
[optional] \usepackage[<babel options>]{babel}  
\usepackage[p,osf]{newtxtext}% osf in text, lining figures in math  
[optional] redefine the plain theorem style if necessary  
<other font loading commands>  
\usepackage{newtxmath}  
<substitutefont commands>
```

As an example of a `theoremstyle` definition,

```
\usepackage[theoremfont]{newtxtext}  
%% modify the default definition of plain to reduce spacing above and below  
\newtheoremstyle{plain}  
{0pt} % ABOVESPACE, extra space above  
{0pt} % BELOWSPACE, extra space below  
{\slshape} % BODYFONT, italic with upright figures and punctuation  
% Change previous line if using option truestlanted---\thfamily, not \slshape  
{ } % INDENT (empty value is the same as 0pt)  
{\bfseries} % HEADFONT  
{.} % HEADPUNCT  
{5pt plus 1pt minus 1pt} % HEADSPACE  
{ } % CUSTOM-HEAD-SPEC\newtheorem{thm}{Theorem}[section]
```

Here is a specific example following this pattern, but without `theoremfont`.

```
\usepackage[LGR,T1]{fontenc} % spell out all text encodings used
```

```

\usepackage[utf8]{inputenc} %
\usepackage{substitutefont} % so we can use fonts other than those in babel
\usepackage[greek.polutoniko,english]{babel}
\usepackage[largesc,osf]{newtxtext} %
\usepackage[varqu,varl]{zi4}% inconsolata
\usepackage{cabin}% sans serif
\usepackage[vvarbb]{newtxmath}
\useosf % use oldstyle figures except in math
\substitutefont{LGR}{\rmdefault}{Tempora} % use Tempora to render Greek text

```

As of version 1.4, there are four normal figure styles: tabular lining, tabular oldstyle, proportional lining and proportional oldstyle, the default figure alignment being tabular. To make proportional the default, use the option `p` or `proportional`.

Option `defaultsups` (same effect as `defaultsups=true`) forces the package to use the L^AT_EX default footnote markers (or, at least, those in force when the package is loaded) instead of those preferred by the package—Times Roman superior figures instead of spindly ordinary Times lining figures reduced to about 70%. (Footnote markers in minipages use the default lowercase italic alphabetic characters, unless otherwise specified by redefining `\thempfootnote`.) For better control over position and size of footnote markers, use the `superiors` package after loading `newtxtext`. The `\sustyle` font switch and its related `\textsu` macro know not only about figures, but also the lower case letters, including egrave, so that traditional French expressions like 1^{ière} may be typeset correctly.

As of version 1.625, there are now denominator figures (aligned to the text baseline) which may be called either with `\infigures 12345` 12345 or `\textinf{6789}` 6789. (`\textde` has the same effect as `\textinf`.) Currently, these are available only in regular weight, upright shape. There is a new macro `\textfrac` that builds a fraction from superior figures and denominator figures: e.g., `\textlf{5}\, \textfrac{7}{80}` renders as 5/80. The macro was changed starting in version 1.630 to add an optional argument for the integer part, and to allow adjustments to the space before and after the fraction solidus by means of the package options `foresolidus` and `aftsolidus`. Now, for example, `\textfrac[5]{7}{80}` renders as 5/80.

Also, as of version 1.630, there is a custom `\textcircled` macro that gives output very similar to the existing `\textregistered` glyph. E.g., `\textregistered\textcircled{S}\textcircled{2}` renders as ®S②.

Option `largesc` changes the small cap glyphs from the default petite caps defined in TeXGyre Termes (same size as in `txfonts`) to a larger size that, in upright shapes, is metrically compatible with Adobe’s small caps. These are about 10% larger than petite caps. For a comparison, SMALL CAPS, PETITE CAPS, and *ITALIC SMALL CAPS*, *ITALIC PETITE CAPS*.

Option `adobesc` is only for those who own licenses for Adobe Times Small Caps and install them into the `ptmssc` package downloaded from CTAN. This option loads `largesc` and substitutes the Adobe glyphs, where available, including their larger Regular and Bold tabular oldstyle figures.

The `theoremfont` option changes the default font used for the plain theoremstyle of `amsthm`, keeping italic text but substituting upright figures and punctuation, and, provided you have loaded `amsthm` before `newtxtext`, it will redefine the plain theoremstyle. For example, with this option, you get theorem statements like this:

Theorem 2.1. *This is Theorem Italic: text numbers are upright—12345; punctuation is in many cases upright (also, parens, braces {} and brackets []). What about question marks and exclamations? Also upright!*

[These fit better with math mode punctuation and figures, like: for all $x \in [0, 1]$, let $f(x) := \exp(\alpha x)$].

Compare this to traditional plain theoremstyle with the same text:

Theorem 2.1. *This is Theorem Italic: text numbers are upright—12345; punctuation is in many cases upright (also, parens, braces {} and brackets []). What about question marks and exclamations? Also upright! [These fit better with math mode punctuation and figures, like: for all $x \in [0, 1]$, let $f(x) := \exp(\alpha x)$].*

If you are using another theorem package (e.g., ntheorem, theorem) you will have to add your own descriptors as specified in its documentation and set the body font family to `\thfamily`.

3 Spacing issues

This new version of newtxtext has spacing that is a little different, in its default state, from that of the old newtxtext. In small part this is due to the finer kerning of TeXGyre Termes, but mostly because the three parameters that govern inter-word spacing are not the same.

| | txfonts | Termes |
|--------------------------------|---------|--------|
| fontdimen2 (interword space) | .25em | .25em |
| fontdimen3 (interword stretch) | .15em | .2em |
| fontdimen4 (interword shrink) | .06em | .1em |

That is, Termes has the same normal spacing as txfonts but its spacing is more flexible in terms of both stretch and shrink. More frequently than not, a paragraph built with Termes will occupy more space than the same built with txfonts. For this reason, the package offers some ways to change the spacing parameters. This may be important if you are trying to imitate the pagination of a document built using txfonts.

Option `tighter` sets the three fontdimen values to those of txfonts.

Option `looser` sets the three fontdimen values to `{.3em, .2em, .1em}` respectively.

If you want full control, the options `spacing`, `stretch`, `shrink` allow you to modify one or more of the above fontdimens. For example,

```
\usepackage[stretch=.15em,shrink=.095em]{newtxtext}
```

4 Math mode options

The package invoked by

```
\usepackage{newtxmath}
```

loads the math part of the txfonts (with revised metrics and additional glyphs) and should be loaded *after* the text font and its encoding have been specified, as it uses the text font settings to define how operators, numbers, math accents, `\mathrm`, `\mathbf` etc. are rendered. You should also load a Typewriter font so as not to generate mysterious error messages about metafont trying to generate `ectt10`. The package offers a number of options.

- `upint` (new as of version 1.5) selects upright integrals—the default shape is slanted. Each shape/size of integral takes one of twelve form, illustrated below in the case of display size slanted integrals.



named respectively

```
\int \oint \iint \iiint \iiint \oint
\oiint \varointclockwise \ointclockwise \fint \sumint \sqint
```

The three sizes of the upright integrals look like:

| Glyph | Command |
|--------|--------------------------------------|
| \int | <code>\smallint[up]</code> |
| \int | <code>\int[up]</code> |
| \int | <code>\displaystyle{\int[up]}</code> |

Note that the suffix `up` is not required unless the document’s integral style is slanted. You may find the `\smallint` is useful for inline math mode when it is important not to change the line spacing.

- `smallerops` (new as of version 1.5) causes big operators other than integrals to render up to 20% less tall, so that displayed formulas may occupy less vertical space. For example, in the following display, the first operator is the usual `\sum`, the second is what you would get with `smallerops`, the third is `\sum` and the fourth is `\smallsum`, the latter being used mainly with inline math.

$$\sum \sum \sum \Sigma$$

Similarly, there are `\smallprod` and `\smallcoprod` which, along with `\smallsum`, are of class `mathop`, unlike their Greek letter equivalents.

- (New as of version 1.5.) Two macros allow you to change `fontdimen` values in math mode: `\setSYdimens` and `\setEXdimens`, which allow you to change the `fontdimen` parameters for the symbol and extension fonts respectively. They may be used only in your preamble. Their arguments can be any valid \TeX commands to change `fontdimen` values. For example:

```
\def\setSYdimens{\fontdimen16\font=2pt\fontdimen17\font=1.15\fontdimen17\font }
```

Don’t use these unless you know what you’re doing.

- `varg` causes the math italic letters *g*, *v*, *w*, *y* to be replaced by versions which are more distinctive—eg, useful for distinguishing math italic *v* from ν ;
- `varvw` causes the math italic letters *v*, *w* to be replaced by versions which are more distinctive—eg, useful for distinguishing math italic *v* from ν ;
- `libertine` loads different versions of math italic and bold math italic based on Libertine rather than Times—the `varg` and `varvw` options are disabled in this case, as the equivalent variant forms are made available by default;
- (new in version 1.55) `stix2` loads different versions of math italic and bold math italic based on StixTwoMath rather than Times—the `varg` and `varvw` options are disabled in this case. See the documentation to the SticksToo package, which contains more details and some math samples.
- (new in version 1.60) `ebgaramond` loads different versions of math italic and bold math italic based on EBGaramond rather than Times—the `varg` and `varvw` options are disabled in this case. See the end of Appendix 2 for an example of a preamble.
- (new as of version 1.629) `noto`, `notosans` load different versions of math italic and bold math italic based on NotoSerif, NotoSans rather than Times. There are some intricacies involved, for which there

is a separate package, `notomath`, that tries to offer as simple an interface as it was possible for me to devise.

- (new in version 1.62) `nc`, `ncf` load different versions of math italic and bold math italic based on ScholaX (New Century Schoolbook) rather than Times—the `varg` and `varvw` options are disabled in this case. The difference is that option `nc` loads math Greek letters from `newtxmath`, while option `ncf` loads math greek from an adaptation of fourier Greek.
- `minion` loads different versions of math italic and bold math italic based on MinionPro rather than Times—the `varg` and `varvw` options are disabled in this case, as the equivalent variant forms are made available by default—see the extended discussion below;
- `garamondx` loads different versions of math italic and bold math italic based on `garamondx` rather than Times—the `varg` and `varvw` options are disabled in this case, as the equivalent variant forms are made available by default.
- `baskervaldx` (or `Baskervaldx`) loads different versions of math italic and bold math italic based on `Baskervaldx` rather than Times—the `varg` and `varvw` options are disabled in this case, as the equivalent variant forms are made available by default.
- `baskerville` (or `Baskerville`, or `baskervillef` or `BaskervilleF`) loads different versions of math italic and bold math italic based on `BaskervilleF` rather than Times—the `varg` and `varvw` options are disabled in this case, as the equivalent variant forms are made available by default.
- `charter` (or `xcharter`) loads different versions of math italic and bold math italic based on `XCharter` rather than Times—the `varg` and `varvw` options are disabled in this case, as the equivalent variant forms are made available by default. **As of version 1.53, Greek letters in all styles are taken from new alphabets constructed to match the Charter style.**
- `alty` is new as of version 1.611, and applies only when math mode uses Charter alphabets. It causes math italic `y` to be rendered using a rounder shape that is less problematic than the default shape because it lacks the long tail of the `XCharter Italic y`.
- `noxchvw` (or `noXchvw` is new as of version 1.54, and applies only when math mode uses Charter alphabets. It causes math italic `v` and `w` to be rendered using Charter italic glyphs. Use this only if you don't care if math italic `v` is hard to distinguish from Greek `\nu`.
- `cochineal` loads different versions of math italic and bold math italic based on `cochineal` rather than Times—the `varg` and `varvw` options are disabled in this case. There are two additional options specific to `cochineal`.
 - Option `cochf` replaces the default short math italic `f` with the long italic `f` used in text.
 - Option `cochrho` replaces the default short form of `\rho` with the the long form used in text.
- `utopia` (or `heuristica` or `erewhon`) loads different versions of math italic and bold math italic based on `Utopia` rather than Times—the `varg` and `varvw` options are disabled in this case, as the equivalent variant forms are made available by default. The `Heuristica` or `Erewhon` font package must be installed to use this option. (`Erewhon` is based on `Heuristica`, but is 6% smaller and has more complete figures styles and small cap styles, as well as a variety of smaller figures—superior, inferior, numerator, denominator.) For example:

```
\usepackage[osf]{erewhon} %extension of Utopia
\usepackage[varqu,varl]{inconsolata} % sans typewriter
```

```
\usepackage[scaled=.95]{cabin} % sans serif
\usepackage[utopia,vvarbb]{newtxmath}
```

- the `libertine` option also replaces both slanted and upright Greek symbols by the corresponding Libertine glyphs, and similarly for `minion`, `garamondx`, `ebgaramond`, `stix2`, `xcharter` and `cochineal`;
- `cmintegrals` instructs `newtxmath` to load a thicker version of the Computer Modern integral in place of the `newtxmath` default—the `txfonts` integral (identical to the integral in the Wolfram fonts), which is not to everyone’s taste—a consequence is that none of the special forms of `txfonts` integrals are available; **as of version 1.5, this option does nothing, as the new default is slanted integrals.**
- `\usepackage{newtxmath}` requires `amsmath`—there is no need to load it separately.
- If you wish to use `\usepackage{amsthm}`, place it before loading `newtxmath` or the result will be
! LaTeX Error: Command \openbox already defined.
- `uprightGreek` and `slantedGreek` determine the form of Greek alphabet loaded—the default is `uprightGreek`, which loads upright uppercase and slanted lowercase Greek symbols, as is customary in Anglo-American mathematical typesetting. With the option `slantedGreek`, which you might want to use if you cared about ISO standards, all Greek symbols are slanted. No matter which is set, `\Gammaup` (or `\upGamma`) gives you upright Γ , etc, and `\Deltait`, `\zetaait` give you italic (i.e., slanted) versions of those letters. If you are using a text font family with properly constructed OT1–encoded versions, then, no matter what you chose as the default shape for upper case Greek letters, `\mathnormal{\Omega}` etc will always produce the slanted version. (The macro `\mathnormal` means essentially “use the version of the symbol in letters”—i.e., the math italic form. This did not always work as expected in versions prior to 1.45.) Currently, this works as expected with `newtxtext` and `libertine`.
- Option `frenchmath` sets the default style in math mode for rendering uppercase Roman and Greek letters to upright, and lowercase Greek letters to upright. (Introduced in v. 1.28.)
- The option `cmbraces` instructs `newtxmath` to ignore the brace collections from `txfonts`, substituting a collection based on thickened versions of the Computer Modern braces, which I find much easier to distinguish from other delimiters. This works quite well in regular weight but looks a bit clunky in bold. The option `bigdelims`, which superseded `cmbraces`, is now not necessary—it is the default as of version 1.5.
- Option `nonewtxmathopt` (or `scale`, a mistake I cannot now erase) causes `newtxmath` to not make use of the optical math sizes (7pt, 5pt), as preferred by some.
- Option `subscriptcorrection` enables the special spacing of some subscripts. (The default is `nosubscriptcorrection`.)
- The `newtxmath` package contains three different Blackboard Bold alphabets, where the original `txfonts` contained two. The default, triggered by `\mathbb{}`, takes its glyphs from the font which replaces `msbm` and has the same overall appearance of a hollowed-out text font, which I find neither bold nor blackboard-like. The second option, taken from `txfonts`, is triggered by `\varmathbb{}`, is more geometric and, in my opinion, preferable but not optimal. The option `varbb` makes `\mathbb{}` synonymous with `\varmathbb{}`. The third option is the double-struck glyphs from the STIX collection. See the expanded discussion below.
- `noOT1` affects only those text-math combinations where operators is defined by default to OT1 with Greek uppercase letters. It causes operators to keep the same encoding as in `tex`, allowing

operatornames to use accented characters, but losing Greek uppercase.

- `nosymbolsc` causes the package to not load the `symbolsc` fonts, saving a math family. (This font contains mostly exotic symbols, along with some very useful, commonly used symbols like `\coloneq` \coloneqq , `\eqcolon` \eqcolon , `\notin` \notin , `\notni` \notni , `\neq` \neq , `\subset` \subset and `\nsupset` \notsupset , but these have been moved (virtually) to `lettersA` so they may continue to be used even if you use the option `nosymbolsc`.) If this option is selected, then, as of version 1.53, new definitions are made for the missing negated symbols. The package `centernot` is now required.
- `amssymbols` (the default) and `noamssymbols` determine whether the `txfonts` versions of the AMS symbols (AMS \mathcal{M}) are loaded—if so, they override previous settings in `amsmath`. If you use the option `noamssymbols`, then `\mathbb{}` is set to mean the same as `\varmathbb{}`. (One advantage of `noamssymbols` is that you save two of your precious math families for other purposes, such as setting a couple of external math alphabets by means of the `mathalfa` package.) **Important note:** if you load an AMS class, like `amsart`, then some trickery will be involved. The AMS classes have an option, `noamsfonts` which currently (2017) does not work as advertised, but is fixed in `TEXLive` 2018. It is supposed to prevent the loading of AMS \mathcal{A} and AMS \mathcal{B} , which waste two slots. The following workaround seems like a reasonable stopgap until then.

```
\def\symAMSb{5}
\documentclass[noamsfonts]{amsart} %or other AMS classes
\let\symAMSb\@undefined
```

This method of loading the AMS class will save you two slots.

- `libaltvw` has effect only if the `libertine` option is selected—in this case, it substitutes for math italic *v* and *w* hand-crafted versions based on the Libertine epsilon glyphs.
- `bigdelims` loads a different math extension font and redefines most of the small and big math delimiters to have larger sizes so that, for example, there is more of a distinction between `(` and `\big(` in math mode. If this option is specified, `cmbraces` is ignored. (This option is unnecessary, as of version 1.5.)
- `liby` has an effect only if the `libertine` option is selected—with this option, the math italic *y* is chosen to be Libertine’s italic *y* instead of the default one from `txfonts`.
- As of version 1.18 of `newtxmath` (and version 1.07 of `newpxmath`) there are new math accents and macros available.
 - `\widehat` and `\widetilde` have been extended from 3 to 6 sizes, and the smallest is now not as wide as in previous versions. In particular, you can now use, eg, `\widehat{X}^2`, which gives \widehat{X}^2 without the hat colliding with the superscript.
 - The math double bracket delimiters have been moved to another family so their use is less likely to cause a “too many math families” error. The ordinary sizes now have their own macros, `\dlb` and `\drb`, giving, eg, `\llbracket 0, T \rrbracket`, as commonly used in probability theory.
 - The new macros `\overgroup`, `\undergroup`, `\overgroupra`, `\overgroupla`, `\undergroupra` and `\undergroupla` are intended as replacements for the `\wideparen` and related macros from the `yhmath` and `fourier` packages. In fact, `\overgroup` and `\undergroup` are variants of the existing macros `\overbrace` and `\underbrace`, while the suffixes `ra` and `la` signify right arrow and left arrow respectively. The macro `\widering` places a ring centered over an `\overgroup`, not dissimilar from its use in `yhmath`. Example:

```
\[\overgroup{ABC}\quad\overgroupra{ABC}\quad\undergroup{ABC}\quad
```

`\undergroupla{ABC}\quad \widering{ABCD}\]`

gives

$\overline{ABC} \quad \overrightarrow{ABC} \quad \underline{ABC} \quad \underline{ABC} \quad \overline{ABCD}$

- As of version 1.23, the package contains new math accents `\widearc` and `\wideOarc` similar in effect to those from `fourier` and `kpfonts`. Example:

`\[\widearc{BC}\quad\widearc{ABC}\quad\widearc{ABCD}\quad`
`\wideOarc{BC}\quad\wideOarc{ABC}\quad\wideOarc{ABCD}\]`

gives

$\widehat{BC} \quad \widehat{ABC} \quad \widehat{ABCD} \quad \widehat{BC} \quad \widehat{ABC} \quad \widehat{ABCD}$

- The option `timesmathacc` changes the default selection of math accents from the Roman text font, forcing the use of the heavier Times accents. (Libertine has much lighter accents which can seem to almost disappear under some conditions.) If your language uses accented operator names, do not use this option.

4.1 Bold Math Italic macros

It can be a little awkward to specify bold math italic letters without using the `bm` package, which may have some unintended consequences for some users. The option `useBImacros` enables the definitions of macros of the form `\BIA`—`\BIz` that may be used instead, all based on the macro

```
\DeclareRobustCommand{\BI@}[1]{%
\begingroup\text{\mathversion{bold}$#1$}\endgroup}
```

following which, the package conditionally defines, e.g.,

```
\DeclareRobustCommand{\BIA}{\BI@{A}}
```

so that `\BIA` works as expected in all math styles (display, text, script, scriptscript). These macros may be copied with minor changes so that other alphabets may be specified similarly.

IMPORTANT: The Libertine text package is now once again named `libertine`, but requires arguments that are different from the original `libertine` package.

EXAMPLE 1:

```
\usepackage[osf]{newtxtext} % T1, lining figures in math, osf in text
\usepackage{textcomp} % required for special glyphs
%\usepackage{amsmath} % not needed, as it is Required by newtxmath
\usepackage[varvf,vvarbb]{newtxmath}
\usepackage{bm} % load after all math to give access to bold math
%\useosf %no longer required if osf specified
```

EXAMPLE 2:

```
\usepackage[lining,semibold]{libertine} % a bit lighter than Times--no osf in math
\usepackage[T1]{fontenc} % best for Western European languages
\usepackage{textcomp} % required to get special symbols
\usepackage[varqu,varl]{inconsolata}% a typewriter font must be defined
```

```

\usepackage{amsthm}% must be loaded before newtxmath
\usepackage[libertine,vvarbb]{newtxmath}
\usepackage[scr=rsfs]{mathalfa}
\usepackage{bm}% load after all math to give access to bold math
%After loading math package, switch to osf in text.
\useosf % for osf in normal text

```

Caution: If your text font lacks an OT1 encoded version with uppercase Greek, `\mathrm` and `\mathit` applied to Greek letters won't give you what you expect.

5 Usage with Lua \LaTeX and Xe \LaTeX

As far as I can tell, `newtxmath` works with both, but requires a very specific loading order and choice of options. Briefly, except for `libertine` text, the math options must all be loaded prior to loading and using `fontspec`. Be aware that some text packages (eg, `cabin`) may contain a line like

```
\RequirePackage{fontspec}
```

which would prevent (“option clash” error) a subsequent

```
\usepackage[no-math]{fontspec}
```

unless suppressed by an appropriate option. E.g.,

```
\usepackage[type1]{cabin}
```

prevents the problem with the `cabin` package.

The following examples illustrate some general models, the most unintuitive being the first because it loads a small version, `minlibertine`, of `libertine` text for use in math mode as numbers, basic symbols and operators.

EXAMPLE 3:

```

%load text components other than libertine text to be used in math
\usepackage[T1]{fontenc}
\usepackage[scaled=.85]{beramono}% used only by \mathtt
\usepackage[type1]{cabin}% used only by \mathsf
\usepackage{amsthm}% must be loaded before newtxmath
\usepackage[libertine]{newtxmath}
% loads minlibertine because no other Roman text package was specified
% so that \mathrm and \mathbf also use minlibertine
\usepackage[scr=rsfs]{mathalfa}
\usepackage{bm}% load after all math to give access to bold math
%Now load the otf text fonts using fontspec---won't affect math
\usepackage[no-math]{fontspec} % process with XeLaTeX or LuaLaTeX
\usepackage{libertine}
%\usepackage[osf,semibold]{libertine} for osf in text, semibold as bold

```

The next example is similar, but in math mode, numbers, basic symbols, operator names, `\mathrm` and `\mathbf` will render with `fbf-LF`, though math italic and math Greek letters will be from `libertine`. (Note that one specifies the encoding and redefines `\rmdefault`. For reasons I don't yet understand, it may not

work to load the font package—ie, don't substitute `\usepackage{fbb}`, as that will mess up bold in the libertine text package.)

EXAMPLE 4:

```
%load text components other than libertine text to be used in math
\usepackage[T1]{fontenc}
\renewcommand{\rmdefault}{fbb-LF}% Roman font for use in math mode
\usepackage[scaled=.85]{beramono}% used only by \mathtt
\usepackage[type1]{cabin}% used only by \mathsf
\usepackage{amsthm}% load before newtxmath
\usepackage[libertine,vvarbb]{newtxmath}
% does not load minlibertine because another Roman text package was specified
\usepackage[scr=rsfs]{mathalfa}
\usepackage{bm}% load after all math to give access to bold math
%Now load the otf text fonts using fontspec---won't affect math
\usepackage[no-math]{fontspec} % process with XeLaTeX or LuaLaTeX
\usepackage{libertine}
```

6 Alternate forms of glyphs

Prior to version 1.5, several math glyphs had alternate forms:

| Command | Result | Alternate Commands | Alternate Forms |
|------------------------|-------------|--|--------------------------|
| <code>\emptyset</code> | \emptyset | <code>\varnothing</code> , <code>\emptysetAlt</code> | \varnothing, \emptyset |
| <code>\forall</code> | \forall | <code>\forallAlt</code> | \forall |
| <code>\exists</code> | \exists | <code>\existsAlt</code> | \exists |
| <code>\nexists</code> | \nexists | <code>\nexistsAlt</code> | \nexists |

To use an alternate form throughout your document without changing all occurrences of the usual command, insert something like the following in your preamble after loading `newtxmath`:

```
\let\forall\forallAlt
```

As of version 1.5, the old `txfonts` versions of `\forall`, `\exists` and `\nexists` have been removed and the `Alt` versions substituted. Both `\forall` and `\forallAlt` generate \forall , and similarly with `\exists` and `\existsAlt`.

7 Conformity with `amsmath`

The `newtxmath` package now contains a `\RequirePackage{amsmath}`, as it uses a number of the macros defined there. To pass options to `amsmath`, you can pass the options as options to `\documentclass`. For example,

```
\documentclass[11pt,intlimits]{article}
\usepackage{newtxtext}
\usepackage{newtxmath}
```

will load `amsmath` with option `intlimits`. As of version 1.14, `newtxmath` respects the `amsmath` macros for placement of limits on integrals.

8 The minion option

This option allows the use of MinionPro as math letters (Latin and Greek) within the math font, but there are some caveats:

- you must use a recent version of MinionPro (2.00 minimum, 2.12 or higher preferred), such as the version that comes with recent versions of Adobe Reader. The MinionPro package must be generated by FontPro, and the CTAN package `minion2newtx` must be installed separately—it is not in `TeXLive`. The details are spelled out in the documentation for the `minion2newtx` package.

9 The \TeX math font problem

Math font packages in \LaTeX are susceptible to the “Too many math alphabets” error, due to exceeding the limit of just sixteen math font families, or mathgroups, as they are called in \LaTeX . Put in oversimplified terms that do however correctly represent how this all works in `newtxmath`, the following math fonts are always loaded and permanently (if you didn’t prevent loading of some features) occupying slots immediately following `\begin{document}`, and others that may be called for in typesetting a mathematical expression can add to the list as the document grows.

ALWAYS LOADED:

```
0: operators
1: letters
2: symbols
3: largesymbols
4: AMSm (a combination of the old AMSa and AMSb)
5: lettersA
6: symbolsC
7: largesymbolsTXA
8: boldoperators
9: boldletters
10: boldsymbols
11: boldlargesymbols
```

NOTES:

- If using one of the AMS classes (e.g., `amsart`, `amsbook`), you can save two or more math families by adding the option `noamsfonts` in your `\documentclass` call. As of early 2018, This works only with the most recent versions the AMS classes available in both `TeXLive` and `MiKTeX`.
- The operators font is essentially the Roman text font, used for names of operators and as the target for `\mathrm`—its bold version is used as the target for `\mathbf`;
- operators is defined to be the OT1 encoded version of the text font in cases where that version is known to contain upright uppercase Greek letters in its first eleven slots—eg, `newtxtext`, `libertine`.
- if you typeset an expression that, say, calls for a single bold glyph from `symbolsC`, that costs you an entire new slot, leaving only two remaining;
- same with, eg, `\mathit`;
- same with an external Fraktur, Blackboard Bold or Script glyphs;

- if you run out of math alphabets, look first to dropping AMSm as well as symbolsC, which can save you at least two slots;
- if space is tight, do not call bold versions of the fonts listed above where the bold version is not already loaded, to avoid loading a new mathgroup;
- if you absolutely need a letter (not a math symbol) from some math font that would normally cost you another mathgroup, you might consider using as if it were text, with something like

```
\mbox{\usefont{U}{ntxmia}{b}{n} X}}
```

which allows you to use letter X from boldlettersA but without any math features;

- there is a macro \ShowMathFonts in newtxmath which may be called at any point in your document, which will provide you a list of the mathgroups currently in use. This can be helpful in figuring out where problems occur. The output lines take the form

```
(<fam number>: <internal font id> = <tfm name> [newtx name])
```

10 Bold math fonts

Every math font in the txfonts package, and in the newtx package, is accompanied by a bold version. Some usage examples are given below. Generally, one may use either \boldmath to change an entire formula to bold, or \boldsymbol to change one symbol, but the spacing generally works better after loading the bm package and using the \bm macro.

The text glyphs dotlessi (\i) and dotlessj (\j) are rarely needed in actual text—in many fonts, roman dotlessi is very similar to the numeral 1. They are however sometimes needed to build special math glyphs. The following table shows how to generate the mathematical forms of dotlessi and dotlessj. I illustrate with only dotlessi—dotlessj is entirely analogous.

| Type | Weight | Command | Result |
|-------------|---------|----------------------------|--------------------|
| Math Italic | Regular | $\hat{\imath}$ | \hat{i} |
| Math Italic | Bold | $\bm{\hat{\imath}}$ | $\hat{\mathbf{i}}$ |
| Roman | Regular | $\hat{\text{trm}{i}}$ | \hat{i} |
| Roman | Bold | $\bm{\hat{\text{trm}{i}}}$ | $\hat{\mathbf{i}}$ |

In math, bold roman characters are often used to indicate vector quantities, and for this one uses constructions like

- \mathbf{x} produces \mathbf{x} ;
- $\bm{\mathrm{x}}$ produces \mathbf{x} (same as previous but may offer improved spacing);
- \bm{x} produces \mathbf{x} (not roman);
- $\bm{\hat{\mathbf{x}}}$ produces $\hat{\mathbf{x}}$ (with a bold accent);
- $\bm{\dot{\mathbf{x}}}$ produces $\dot{\mathbf{x}}$ (bold but not roman);
- the macro definition

```
\newcommand{\xyvec}[2]{%
\ensuremath{\mkern1.5mu\bm{\textbf{i}}\mkern1.5mu\bm{\textbf{j}}}}
```

allows you to write $\xyvec{x}{y}$ to output $\mathbf{x} + \mathbf{y}$;

- `\bm{\Gamma}` produces **Γ** (bold Gamma);
- `\bm{\hat{\Gamma}}` produces **Γ̂** (bold Gamma with bold accent).

(The last two assume that you have effectively set the option `uprightGreek`—the default.)

11 Blackboard Bold

Much of what is in this section is a repetition of material from other parts of the document, more expanded and with more emphasis on the differences between the available Blackboard Bold alphabets. It also reflects substantive changes in `newtxmath.sty` version 1.640 that have changed for the better the handling of math alphabets such as `\mathbb` and `\mathscr`. The new handlers maintain consistency of the printed output with prior versions, while greatly improving interactions with the `bm` and `hyperref` packages.

When `COST` is mentioned in the following discussion, this is to remind you that you have a total of only sixteen math families available to any document, and it is easy to run out, so I provide the `COST` of an option as the number of math families in regular weight only that this would involve. (If you make also use of a bold symbol from one of those families, the `COST` could double.)

In the \TeX world, Blackboard Bold appeared first in the `amstex` package, with `msam` containing Gothic and `msbm` containing Blackboard Bold. The only weight provided was regular. Those AMS additions, referred to below as `AMSadd`, were designed to blend well with Computer Modern, with geometric symbols vertically centered on its math axis and line widths matching those in Computer Modern. They are not good matches for the math axis and line width in `newtx`. (`COST=2`.)

In the original `txfonts`, the `AMSadd` fonts `msam*` and `msbm*` were replaced by `AMSa` and `AMSb`, with vertical positions and line widths appropriate to Times, each available in regular and bold. (`COST=2`.) In the `newtx` package, these two seven bit fonts are replaced by one eight bit font. (`COST=1`.) In the sequel, this will be called `TXAMSadd`. The Gothic and Blackboard Bold alphabets they contain were not substantially heavier than those in the `AMSadd` fonts, but the shapes were somewhat different. For example, Blackboard Bold A in the original AMS additions and in the original `txfonts` look as followed, scaled up by a factor of five:



In both, there are areas of the glyphs where the narrow gaps between the outlines do not render well at normal text sizes, making for uneven gray blotched areas. In my opinion, neither is good for high quality work. Technically, both work well with respect to `hyperref` and the macros `\bm`, `\boldmath` and `\boldsymbol`.

The following describe a number of common scenarios relative to the AMS font symbols and show how to minimize additional `COST`.

- **I need neither `AMSadd` nor `TXAMSadd`:**
 - Do not load `amssymb`, otherwise `AMSadd` will be loaded.
 - When loading `newtxmath`, include the option `noamssymbols` to prevent `TXAMSadd` from loading.
 - If you use one of the AMS classes (`amsart`, `amsbook`, `amsreport`), the default is for that class to load `amsfonts`, but there is a class option `noamsfonts` to prevent this.
- **I want to use `TXAMSadd`, not `AMSadd`:**

- Do not load `amssymb`, otherwise `AMSadd` will be loaded uselessly, additional `COST=2`.
- When loading `newtxmath`, do not include the option `noamssymbols`, so that `TXAMSadd` will load.
- If you use one of the AMS classes (`amsart`, `amsbook`, `amsreport`), include the class option `noamsfonts` to prevent `AMSadd` from loading.

• **I want to use `AMSadd`, not `TXAMSadd`:**

- If you use one of the AMS classes (`amsart`, `amsbook`, `amsreport`), do not include the class option `noamsfonts` that prevents `AMSadd` from loading. Otherwise, load `amssymb`.
- When loading `newtxmath`, include the option `noamssymbols`, so that `TXAMSadd` will **NOT** load.

`Newtxmath` now has three built-in blackboard bold alphabets, along with package options and macros to call them. In summary:

- In the absence of one of the options `varbb`, `vvarbb`, and assuming you did not block loading of both `AMSadd` and `TXAMSadd`, `\mathbb` will use the alphabet described in the preceding paragraphs, otherwise it will use the alphabet described in the following item.
- The second possible alphabet may be specified by the option `varbb`, looking like `ABCk`. It does cooperate with the bolding macro `\bm` and with `hyperref` but, in my opinion, it has appearance problems. It has all uppercase letters, but in versions of `newtx` up to 1.640, its only lowercase glyph is `lk`. As of version 1.641, there is a full lowercase plus `\imath` and `\jmath`. The bold version is identical to the regular version.
- The third possibility is specified by the option `vvarbb`, looking like `ABCZaz09`. It cooperates with the bolding macro `\bm` and with `hyperref` and, in my opinion, looks better than the other two. It is taken from the original STIX math fonts. There is a slightly heavier bold version.
- No matter which alphabet option you chose, you may use symbols from of of the variant alphabets by means of the macros `\vmathbb`, `\vvmathbb`: e.g., `\vmathbb{N}` gives \mathbb{N} and `\vvmathbb{C}` gives \mathbb{C} . Note that for consistency with earlier usage in `newtxmath`, `\varmathbb` is a synonym for `\vmathbb`.
- In each of the two variant alphabets, there are digits taken from the STIX Blackboard Bold alphabets, as well as `dotlessi` and `dotlessj`.
- **Important note:** Under the option `stix2`, there are still three blackboard fonts but the macro `\vmathbb` now points to glyphs from `DSSerif`, a serified double-struck family that replaces the original variant that is still available under other options. With `stix2`, the `dotlessi` and `dotlessj` glyphs from the `DSSerif` font are available as `\imathbbs` and `\jmathbbs`, no matter which blackboard bold option you chose.

One interesting feature of the third Blackboard Bold alphabet is that it contains blackboard bold numbers, of which 0 and 1 will likely be the most useful, perhaps as operator names. I find `\vvmathbb{1}` useful in specifying an indicator, AKA characteristic function. Here are some examples that hold except with the `stix2` option:

| | Regular | Bold | Remarks |
|-----------|---------------------|-------------------------------|---|
| Default | \mathbb{R} | $\bm{\mathbb{R}}$ | Bold has more interior space |
| | \mathbb{R} | $\{\boldsymbol{\mathbb{R}}\}$ | Also “bold” |
| Variant 1 | \varmathbb{R} | $\bm{\varmathbb{R}}$ | Bold glyphs same as regular |
| ...or | \vmathbb{R} | | |
| | $\varmathbb{2}$ | $\bm{\varmathbb{2}}$ | Bold digits are now bolder |
| Variant 2 | \vvmathbb{R} | $\bm{\vvmathbb{R}}$ | Truly bold! |
| | $\vvmathbb{1}$ | $\bm{\vvmathbb{1}}$ | |
| | $\vvmathbb{\Gamma}$ | $\bm{\vvmathbb{\Gamma}}$ | Also \mathbb{Y} , \mathbb{I} , $\mathbb{\pi}$ |

The macros `\varmathbb` and `\vvmathbb` have been substantially rewritten as of version 1.640. Both accept strings as arguments rather than just single characters, and pass through characters not in the Blackboard Bold alphabet.

Revision 1.640 makes a symbol definition for every Blackboard Bold glyph, like

```
\DeclareMathSymbol{\m@thbbch@rA}{\mathord}{lettersA}{132}
\DeclareMathSymbol{\m@thbbch@rImath}{\mathord}{lettersA}{125}
```

and then parses the argument of, e.g., `\varmathbb`, concatenating the prefix `\m@thbbch@r` with the name of each character in the argument successively. If the resulting macro exists, that definition applies, otherwise the character is passed through to be rendered by the normal means. For example, `\vvmathbb{A\imath\alpha\pi\ c}` renders as $\mathbb{A}\mathbb{\alpha}\mathbb{\pi}\mathbb{c}$.

The prefix `\m@thbbch@r` is a carry-over from the `txfonts`—other alphabets use the simple forms, like `\tx@Bbb` for the `\vvmathbb` letters, `\tx@Scr` for script letters and `\tx@UScr` for upright script letters. So, for example, we have

```
\tx@BbbA % slot 193 in lettersA
...
\tx@BbbZ % slot 218 in lettersA
\tx@Bbba % slot 225 in lettersA
\tx@Bbbz % slot 250 in lettersA
```

The corresponding digits are named

```
\tx@BbbZero % slot 43 in lettersA
...
\tx@BbbNine % slot 52 in lettersA
```

which may be `\let` to more convenient forms just as above: e.g., `\let\BBNine\tx@BbbNine` while in a `\makeatletter` block.

12 Samples from free Times and Libertine packages

TXFONTS:

```
\usepackage{txfonts}
```

A formula from the L^AT_EX Companion, 2nd Edition, p.390:

$$t[u_1, \dots, u_n] = \sum_{k=1}^n \binom{n-1}{k-1} (1-t)^{n-k} t^{k-1} u_k.$$

The ISO would prefer that a formula like

$$\Phi(u) = \frac{1}{\sqrt{2\pi}} \int_{-\infty}^u e^{-t^2/2} dt$$

be typeset instead as

$$\Phi(u) = \frac{1}{\sqrt{2\pi}} \int_{-\infty}^u e^{-t^2/2} dt,$$

with upright π , e and d. I dislike the look of dt when the slope of t is too great.

- Complete match between text and math size and weight;
- first formula much too cramped;
- upper limit of integral much too close to integral sign;
- square on t in integrand comes very close to colliding with it;
- square root in denominator aligned too far right.

NEWTXFONTS:

```
\usepackage{newtxtext}
\usepackage{newtxmath}
```

A formula from the L^AT_EX Companion, 2nd Edition, p.390:

$$t[u_1, \dots, u_n] = \sum_{k=1}^n \binom{n-1}{k-1} (1-t)^{n-k} t^{k-1} u_k.$$

The ISO would prefer that a formula like

$$\Phi(u) = \frac{1}{\sqrt{2\pi}} \int_{-\infty}^u e^{-t^2/2} dt$$

be typeset instead as

$$\Phi(u) = \frac{1}{\sqrt{2\pi}} \int_{-\infty}^u e^{-t^2/2} dt,$$

with upright π , e and d. I dislike the look of dt when the slope of t is too great.

- Complete match between text and math size and weight;
- first formula much less cramped;
- upper limit of integral not too close to integral sign;
- square not too close to t in exponent;
- better alignment of square root in denominator.

MATHTIMEPRO2:

```
\usepackage{newtxtext}
\usepackage[lite]{mtpro2}
```

A formula from the L^AT_EX Companion, 2nd Edition, p.390:

$$t[u_1, \dots, u_n] = \sum_{k=1}^n \binom{n-1}{k-1} (1-t)^{n-k} t^{k-1} u_k.$$

The ISO would prefer that a formula like

$$\Phi(u) = \frac{1}{\sqrt{2\pi}} \int_{-\infty}^u e^{-t^2/2} dt$$

be typeset instead as

$$\Phi(u) = \frac{1}{\sqrt{2\pi}} \int_{-\infty}^u e^{-t^2/2} dt,$$

with upright π , e and d . I dislike the look of dt when the slope of t is too great.

- Complete match between text and math size and weight;
- first formula quite spread out;
- upper limit of integral not too close to integral sign;
- plenty of space between square and t in exponent.

LIBERTINE AND MATHTIMEPRO2:

```
\usepackage{libertine}
\usepackage[T1]{fontenc}
\usepackage[lite]{mtpro2}
```

A formula from the L^AT_EX Companion, 2nd Edition, p.390:

$$t[u_1, \dots, u_n] = \sum_{k=1}^n \binom{n-1}{k-1} (1-t)^{n-k} t^{k-1} u_k.$$

The ISO would prefer that a formula like

$$\Phi(u) = \frac{1}{\sqrt{2\pi}} \int_{-\infty}^u e^{-t^2/2} dt$$

be typeset instead as

$$\Phi(u) = \frac{1}{\sqrt{2\pi}} \int_{-\infty}^u e^{-t^2/2} dt,$$

with upright π , e and d . I dislike the look of dt when the slope of t is too great.

- Mismatch of weight between text and math;

- first formula quite spread out;
- upper limit of integral not too close to integral sign;
- plenty of space between square and t in exponent.

LIBERTINE AND NEWTXMATH:

```
\usepackage{libertine}
\usepackage[T1]{fontenc}
\usepackage[libertine]{newtxmath}
```

A formula from the \LaTeX Companion, 2nd Edition, p.390:

$$t[u_1, \dots, u_n] = \sum_{k=1}^n \binom{n-1}{k-1} (1-t)^{n-k} t^{k-1} u_k.$$

The ISO would prefer that a formula like

$$\Phi(u) = \frac{1}{\sqrt{2\pi}} \int_{-\infty}^u e^{-t^2/2} dt$$

be typeset instead as

$$\Phi(u) = \frac{1}{\sqrt{2\pi}} \int_{-\infty}^u e^{-t^2/2} dt,$$

with upright π , e and d . I dislike the look of dt when the slope of t is too great.

- Very good match between text and math in size and weight;
- first formula not cramped;
- upper limit of integral not too close to integral sign;
- space between square and t in exponent;
- better alignment of square root in denominator.

MATHPTMX:

```
\usepackage{mathptmx}
```

A formula from the L^AT_EX Companion, 2nd Edition, p.390:

$$t[u_1, \dots, u_n] = \sum_{k=1}^n \binom{n-1}{k-1} (1-t)^{n-k} t^{k-1} u_k.$$

The ISO would prefer that a formula like

$$\Phi(u) = \frac{1}{\sqrt{2\pi}} \int_{-\infty}^u e^{-t^2/2} dt$$

be typeset instead as

$$\Phi(u) = \frac{1}{\sqrt{2\pi}} \int_{-\infty}^u e^{-t^2/2} dt,$$

with upright π , e and d. I dislike the look of dt when the slope of t is too great.

- Good match between text and math size and weight, though the summation symbol (from the system symbol font) is too small and too dark;
- first formula well spread;
- upper limit of integral not too close to integral sign;
- space between square and t in exponent;
- there are no upright Greek lowercase letters in this package;
- good alignment of square root in denominator;
- infinity symbol not sufficiently large?
- the package lacks a number of amenities that are present in other packages.

13 Items installed

As well as a collection of PostScript fonts, virtual fonts, font definition files and the central `newtxtext.sty` and `newtxmath.sty` files, the package contains one map file `newtx.map` that must be enabled for the package to function correctly. Its name was changed from `ntx.map` to mirror the package name.) The file `implementation.pdf` in this distribution provides a manifest of all files installed together with a brief indication of the sources. (This file is somewhat outdated. The file `mathnotes.pdf` adds details about the sources for the math fonts, though it is rather cursory.)

The font files `ntxexmods.pfb` and `ntxbexmods.pfb` were derived from `cmex10.pfb` by FontForgery, thickening the Computer Modern braces to match the weight of the `txfonts` braces. The pair `ntxexb.pfb` and `ntxbexb.pfb` were similarly derived from `cmsy7.pfb` and `cmex10.pfb` to produce more braces and matching integral signs based on Computer Modern. The `.tfm` files `rtx[b]mio.tfm` are simply unslanted versions of `rtxmi`, from which we construct upright partial derivative symbols. The last two entries provide us with a way to access custom-encoded versions of `fxlri.pfb` and `fxlbi.map` in order to access some of the unencoded alternate characters—eg, Greek letters, `J.alt` and `v.alt`. The font file `LibertineTheta-Regular.pfb` was created from the Theta symbol in `fxlri.pfb`, which requires some FontForge help to look correct.

This version contains optical versions of the math italic and symbol fonts at 7pt and 5pt, allowing better rendering in `\scriptstyle` and `\scriptscriptstyle`.

14 Appendix 1: Changes made in version 1.5

- The large delimiters have been modified so match the heights in common usage by `cmex10` and other packages. (Those formerly used by `newtxmath` were somewhat shorter, resulting in unexpected behavior of `\Big`, `\bigg`, etc.)
- The integrals used in previous versions have been discarded and replaced by an upright and a slanted form, the latter being the default. The option `upint` switches to the upright form. (The former option `cmintegrals` now has no effect.) Integrals are of three types: `small`, `textstyle` and `displaystyle`. Each size is available in twelve variants. Assuming slanted (the default) is selected, there are 36 regular-weight forms:

| Small | | Text, Display | |
|------------|---------------------------------------|----------------------|----------------------------------|
| \int | <code>\smallint\$</code> | \int, \int | <code>\int\$</code> |
| \iint | <code>\smallliint\$</code> | \iint, \iint | <code>\iint\$</code> |
| \iiint | <code>\smallliiint\$</code> | \iiint, \iiint | <code>\liiint\$</code> |
| \iiiiint | <code>\smallliiiiint\$</code> | \iiiiint, \iiiiint | <code>\liiiiint\$</code> |
| \oint | <code>\smalloint\$</code> | \oint, \oint | <code>\oint\$</code> |
| \oiint | <code>\smalloiint\$</code> | \oiint, \oiint | <code>\oiint\$</code> |
| \oiint | <code>\smalloiint\$</code> | \oiint, \oiint | <code>\oiint\$</code> |
| \oiint | <code>\smalloiint\$</code> | \oiint, \oiint | <code>\oiint\$</code> |
| \oint | <code>\smallfint\$</code> | \oint, \oint | <code>\fint\$</code> |
| \oint | <code>\smallsqint\$</code> | \oint, \oint | <code>\sqint\$</code> |
| \oint | <code>\smallsumint\$</code> | \oint, \oint | <code>\sumint\$</code> |
| \oint | <code>\smallvarointclockwise\$</code> | \oint, \oint | <code>\varointclockwise\$</code> |
| \oint | <code>\smallointctrackwise\$</code> | \oint, \oint | <code>\ointctrackwise\$</code> |

- The overly small delimiters (`{`, `}` in Times) are no longer used in math mode, being replaced by bigger versions. The former option `bigdelims` no longer has any effect.
- There is a new option `smallerops` which chooses smaller renditions (20% smaller in `displaystyle`, 10% smaller in `textstyle`) of the bigoperators:

`\bigscup`
`\bigodot`
`\bigoplus`
`\bigotimes`
`\sum`

\backslash prod
 \backslash bigcup
 \backslash bigcap
 \backslash biguplus
 \backslash bigwedge
 \backslash bigvee
 \backslash bigcupdot
 \backslash bigcapplus
 \backslash bigsqcupplus
 \backslash bigsqcapplus
 \backslash bigsqcap
 \backslash bigtimes
 \backslash coprod

- The dot accents are now taken from a slightly larger series, making available \backslash dot, \backslash ddot, \backslash dddot and \backslash ddddot. For best horizontal alignment with other accents, choose the option `timesmathacc` when loading `newtxmath`.

- New accents have been added and the old vector accent has been replaced. The new accents are:

\backslash vec \rightarrow
 \backslash lvec \leftarrow
 \backslash lrvec \leftrightarrow
 \backslash harpoonacc \rightarrow
 \backslash lharpoonacc \leftarrow
 \backslash lrharpoonacc \leftrightarrow
 \backslash barbar $=$
 \backslash bartilde \approx
 \backslash barhat \wedge
 \backslash tildebar \approx
 \backslash tildedtilde \approx
 \backslash tildehat \wedge
 \backslash hatbar \times
 \backslash hattilde \times
 \backslash hathat \wedge

- New glyphs: (B denotes bigger, S denotes smaller)

\backslash cdotB \cdot (cf. \backslash cdot \cdot)
 \backslash cdotBB \cdot
 \backslash circS \circ (cf. \backslash circ \circ)
 \backslash bulletS \bullet (cf. \backslash bullet \bullet)
 \backslash bulletSS \bullet
 \backslash bulletSSS \bullet
 \backslash primeS \prime (cf. \backslash prime \prime)

- New macros \backslash setSYdimens and \backslash setEXdimens allow experts to modify some math font dimensions.

15 Appendix 2: Changes made in version 1.60

Versions of newtx dated from September, 2019 (1.60 for newtxmath make some quite substantial changes, mostly to math mode.

16 Goals

Spurred by work of Ross Moore to provide means of generating archivable pdf using pdf_latex, the main goal was to change newtx and newpx to meet the requirements for satisfying the PDF/A-1b standards by using an appropriate preamble involving the pdfx package and other unicode mapping files. Making these changes gave me the opportunity to organize the source files to make them more manageable in future revisions.

A further goal whose time seemed ripe was to rework the spacing of math letters, both Roman and Greek, so they behaved better in superscripts and subscripts. This did not turn out to be so easy. The problem is illustrated by math italic j. If you don't give it enough extra space on the left, it will likely collide with the D in rendering D^j . On the other hand, if you do give it enough space on the left, it will look bad as a subscript, appearing too far right.

A final goal was to make better use of the remaining space in some of the math fonts by placing some math alphabets in them, avoiding perhaps a waste of those precious sixteen math families.

17 The important changes

The following changes were made to both newtx and newpx.

17.1 Archivability

Some of the individual font files from which the math fonts are built turned out to have some fairly minor structural issues. These have all been corrected. The more major issue was the lack of unicode mapping for all characters in the fonts. For the symbol and math extension fonts, this issue was largely solved by Ross Moore's glyphtounicode files that are now accessible as part of TeXLive and MiKTeX. The main problem was the math alphabets like math italic, bold math italic, upright Greek and slanted Greek, all of which have now been assigned their own unicode points. For all of these, I constructed new fonts using unicode names for the glyphs, then made fontinst scripts that renamed those unicode values to the original simple names as used in the encoding files so that I could use my old encoding and adjustment files. This exercise has now been carried out for newtxmath, newpxmath, newtxmath/libertine, newtxmath/cochineal, newtxmath/stix2, newtxmath/xcharter and newtxmath/erewhon. Each of these can now be considered to have an "enhanced" status that allows them to share all the new assets described below. The other packages which may be specified as an option to newtxmath (e.g., baskervaldx, baskervillef) must be considered for the moment to be "unenhanced" and able to share only some of the new assets. In particular, only the enhanced items can generate archivable pdf.

Also modified were the sups fonts in newtxtext, where the main issue was unicode mapping. Superior number and some superior letters do have assigned unicode values, but in many cases a more creative approach was needed, and provided once again by Ross Moore. I rebuilt the superior font files using those unicode names, solving that particular problem.

Here is a sample preamble showing the elements you will need to specify to generate a pdf satisfying the PDF/A-1b standards, as verified by Adobe Acrobat Pro. (Other verification processes may yield different outcomes.)

```
\documentclass[noamsfonts]{amsart} % save 2 math families
\pdfcompresslevel=0
\pdfgentounicode=1
\input glyphtounicode.tex
\usepackage{pdfx} % v 1.6.4 or higher
\InputIfFileExists{glyphtounicode-cmr.tex}{}{}
\InputIfFileExists{glyphtounicode-ntx.tex}{}{}
\usepackage{newtxtext} %T1 is default encoding
\usepackage[scaled=0.95]{inconsolata} % typewriter
%\usepackage[leqno]{amsmath}
\usepackage{amsthm}
\usepackage[vvarbb]{newtxmath} % vvarbb gives STIX Bbb
```

Version 1.6.3 of pdfx from February 2019 mishandles math accents. A fix is now available and will become part of the upcoming pdfx v1.6.4.

17.2 Glyph spacing changes

(For enhanced packages only) I reworked the math italics to improve the rendering of some superscripts. This affects (a) parentheses, brackets and braces to inhibit clashes; (b) glyphs like j , f , p , y , ρ , β and μ where a long tail could pose problems intersecting with other glyphs; (c) glyphs like such as D , Q and Φ that are round on the right, where interference is most likely to occur with a superscript. Increasing the left side-bearing of j , etc., helps with superscripts but creates an ugly gap when used as subscripts.

The subscriptcorrection option to newtxmath has been corrected and enhanced so that it now offers a partial solution the subscript spacing problem. I regret that this option is incompatible with xy-pic, both depending on making $_$ an active character. Newtxmath will detect if the xy package is loaded and disable subscriptcorrection if so. You would have to correct such issues by manually inserting a negative \mkern . For example, you might put in your preamble something like

```
\def\jj{\mkern-3mu j}
```

and then use x_{\jj} instead of x_j , turning x_j into x_j .

There are also interactions with pstricks that have to be worked around because subscriptcorrection redefines $_$ as an active character, as do parts of pstricks. In particular, the pstricks short forms for macros like \tput and \nput for attaching labels beneath node connections must be avoided.

If you do enable subscriptcorrection, there is a default correction table in the sty file, but the sty file also looks for a file named, e.g., newtx-substex if you are using the newtx default math letters. There is already such a file located in the newtx distribution in the $/\text{tex}/\text{latex}/$ folder. If you wish to make changes to this file, copy the file to your home TeX folder where it will be found by TeX before the one in the distribution. The entries in the file are lines like

```
{j}{-3}
```

each of which will have the same effect as the above macro if the first item in the subscript is j . You can also specify Greek letters with lines like

`{\beta}{-1.5}`

The complete list of file names recognized for specifying subscript corrections is:

newtx-subs.tex
newtx-libertine-subs.tex
newtx-xcharter-subs.tex
newtx-cochineal-subs.tex
newtx-baskervillef-subs.tex
newtx-stickstoo-subs.tex
newtx-garamond-subs.tex
newtx-ebgaramond-subs.tex
newtx-baskervald-subs.tex
newtx-erewhon-subs.tex
newtx-minion-subs.tex
newtx-nc-subs.tex
newtx-ncf-subs.tex
newtx-noto-subs.tex
newtx-notosans-subs.tex

17.3 New glyphs added

(For enhanced packages only) Math family 1 (letters) has been extended from 128 slots to 256, retaining the OML encoding of the first 128. Most of additional slots have been allocated to a script font from the old STIX collection and an upright modification of that font. By default, \mathscr{F} will produce \mathcal{F} .

- option `uprightscript` changes the output to \mathfrak{F} .

In both cases, there are full upper-case and lower-case and `dotlessi`, `dotlessj`. To insert the latter, you can write either $\mathscr{\imath}$ or \imath , rendered as \imath in the slanted script case.

There are in fact two additional macros, `\mathslscr` (slanted script) and `\mathuscr` (upright script) that may be used. By default, `\mathscr` is `\let` to `\mathslscr`, but, under option `uprightscript`, `\mathscr` is `\let` to `\mathuscr`.

The secondary letters font (lettersA) and math family 2 (symbols) have been rearranged. The first of these continues to have a Fraktur alphabet, but it a modification of its original one, having wider vertical stems and a blacker appearance more in keeping with the weight Times. `dotlessi` and `dotlessj` have been added and can be specified in math mode by \mathfrak{i} and \mathfrak{j} — \mathfrak{i} also works. There are in addition two subsidiary Bbb alphabets in lettersA, specified by the respective options `varbb`, `vvarbb`, and there are corresponding `dotlessi`, `dotlessj` activated by \mathbb{i} , \mathbb{j} no matter the choice of which Blackboard Bold Alphabet. If you select one of the options `varbb`, `vvarbb`, you will have Bbb digits 0..9 using, e.g., $\mathbb{1}$ to get 1. With both options, the arguments `\imath`, `\jmath` will render as expected, as are all upper and lower case letters.

Among the new symbols added are:

- `\hslash`, `\hbar`, `\lambdash`, `\lambdabar`, `\Zbar`, `\Angstrom` are now constructed from the native glyphs, but only in the enhanced families.
- Euler’s constant \mathscr{E} (\mathcal{E}).
- Hermitian transpose `\hermtransp` or `\htransp` is used like \mathbf{A}^{\htransp} (\mathbf{A}^H). This usage is similar to simple transpose \mathbf{A}^{\transp} (\mathbf{A}^T).
- Independence (in the probabilistic sense) can use `\Perp`, \perp , and there is a new `\nPerp`, \nperp for the

negation.

17.4 Adaptive vector accent

The \LaTeX macro `\overrightarrow` provides a right arrow with adaptive width, but not matching the vector head of `newtxmath`. Likewise, the `esvect` provides a similar service with a choice of vector heads, none of which match `newtxmath`. I've added code to provide a matching adaptive vector accent and which uses the same macro name, `\vv`, as `esvect`. For a comparison of these vector accents, `\vec{XY} \vv{XY} \overrightarrow{XY}` renders as

$\vec{XY} \overrightarrow{XY} \overrightarrow{XY}$.

- `\vv{AB}` renders as \overrightarrow{AB} .
- `\vv*{AB}{x}` renders as \overrightarrow{AB}_x . This provides better horizontal spacing of subscripts than `\vv{AB}_{x}`, \overrightarrow{AB}_x .
- You can also do `\vv*{AB}{\vv{CD}}`, which renders as $\overrightarrow{AB}_{\overrightarrow{CD}}$.
- You can change the vertical space between the arrow and the accentee by means of the package option `vecsep`, whose default value is `.25ex`.

17.5 Miscellaneous Changes

- The superior letters fonts in `newtx` have been extended and all glyphs now have appropriate unicode mappings.
- The AMS fonts replacement, `ntxsym` corrects the former misplacement of `\kbbb`, `\daleth`, `\circledR` and `\circledS`.)

18 Changed Font Tables

18.1 letters

| | \acute{o} | \acute{i} | \acute{e} | \acute{a} | \acute{u} | \acute{s} | \acute{c} | \acute{g} | |
|---------------|-------------------|-----------------------|-----------------------|------------------------|------------------------|-------------------------|---------------------------|---------------------------|-----------|
| $\acute{o}ox$ | Γ_0 | Δ_1 | Θ_2 | Λ_3 | Ξ_4 | Π_5 | Σ_6 | Υ_7 | $\sim 0x$ |
| $\acute{o}ix$ | Φ_8 | Ψ_9 | Ω_{10} | α_{11} | β_{12} | γ_{13} | δ_{14} | ϵ_{15} | |
| $\acute{o}2x$ | ζ_{16} | η_{17} | θ_{18} | ι_{19} | κ_{20} | λ_{21} | μ_{22} | ν_{23} | $\sim 1x$ |
| $\acute{o}3x$ | ξ_{24} | π_{25} | ρ_{26} | σ_{27} | τ_{28} | υ_{29} | ϕ_{30} | χ_{31} | |
| $\acute{o}4x$ | ψ_{32} | ω_{33} | ε_{34} | ϑ_{35} | ϖ_{36} | ϱ_{37} | ς_{38} | φ_{39} | $\sim 2x$ |
| $\acute{o}5x$ | \leftarrow_{40} | \leftharpoonup_{41} | \rightarrow_{42} | \rightharpoonup_{43} | \curvearrowleft_{44} | \curvearrowright_{45} | \rhd_{46} | \lhd_{47} | |
| $\acute{o}6x$ | \mathbf{O}_{48} | \mathbf{I}_{49} | \mathbf{Z}_{50} | $\mathbf{3}_{51}$ | $\mathbf{4}_{52}$ | $\mathbf{5}_{53}$ | $\mathbf{6}_{54}$ | $\mathbf{7}_{55}$ | $\sim 3x$ |
| $\acute{o}7x$ | $\mathbf{8}_{56}$ | $\mathbf{9}_{57}$ | $\mathbf{\cdot}_{58}$ | $\mathbf{\cdot}_{59}$ | $\mathbf{<}_{60}$ | $\mathbf{/}_{61}$ | $\mathbf{>}_{62}$ | $\mathbf{\star}_{63}$ | |
| $\acute{o}ox$ | ∂_{64} | A_{65} | B_{66} | C_{67} | D_{68} | E_{69} | F_{70} | G_{71} | $\sim 4x$ |
| $\acute{o}ix$ | H_{72} | I_{73} | J_{74} | K_{75} | L_{76} | M_{77} | N_{78} | O_{79} | |
| $\acute{o}2x$ | P_{80} | Q_{81} | R_{82} | S_{83} | T_{84} | U_{85} | V_{86} | W_{87} | $\sim 5x$ |
| $\acute{o}3x$ | X_{88} | Y_{89} | Z_{90} | \mathfrak{b}_{91} | \mathfrak{d}_{92} | \mathfrak{h}_{93} | \smile_{94} | \frown_{95} | |
| $\acute{o}4x$ | ℓ_{96} | a_{97} | b_{98} | c_{99} | d_{100} | e_{101} | f_{102} | g_{103} | $\sim 6x$ |
| $\acute{o}5x$ | h_{104} | i_{105} | j_{106} | k_{107} | l_{108} | m_{109} | n_{110} | o_{111} | |
| $\acute{o}6x$ | p_{112} | q_{113} | r_{114} | s_{115} | t_{116} | u_{117} | v_{118} | w_{119} | $\sim 7x$ |
| $\acute{o}7x$ | x_{120} | y_{121} | z_{122} | l_{123} | J_{124} | \wp_{125} | $\vec{}_{126}$ | $\hat{}_{127}$ | |

| | | | | | | | | | |
|---------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|-----------------------------|
| $\acute{2}0x$ | $_{128}$ | \mathcal{K}_{129} | $_{130}$ | $_{131}$ | 0_{132} | 1_{133} | 2_{134} | 3_{135} | $\text{~}\acute{8}\text{x}$ |
| $\acute{2}1x$ | 4_{136} | 5_{137} | 6_{138} | 7_{139} | 8_{140} | 9_{141} | \mathcal{A}_{142} | \mathcal{B}_{143} | |
| $\acute{2}2x$ | \mathcal{C}_{144} | \mathcal{D}_{145} | \mathcal{E}_{146} | \mathcal{F}_{147} | \mathcal{G}_{148} | \mathcal{H}_{149} | \mathcal{I}_{150} | \mathcal{J}_{151} | $\text{~}\acute{9}\text{x}$ |
| $\acute{2}3x$ | \mathcal{K}_{152} | \mathcal{L}_{153} | \mathcal{M}_{154} | \mathcal{N}_{155} | \mathcal{O}_{156} | \mathcal{P}_{157} | \mathcal{Q}_{158} | \mathcal{R}_{159} | |
| $\acute{2}4x$ | \mathcal{S}_{160} | \mathcal{T}_{161} | \mathcal{U}_{162} | \mathcal{V}_{163} | \mathcal{W}_{164} | \mathcal{X}_{165} | \mathcal{Y}_{166} | \mathcal{Z}_{167} | $\text{~}\acute{A}\text{x}$ |
| $\acute{2}5x$ | a_{168} | b_{169} | c_{170} | d_{171} | e_{172} | f_{173} | g_{174} | h_{175} | |
| $\acute{2}6x$ | i_{176} | j_{177} | k_{178} | ℓ_{179} | m_{180} | n_{181} | o_{182} | p_{183} | $\text{~}\acute{B}\text{x}$ |
| $\acute{2}7x$ | q_{184} | r_{185} | s_{186} | t_{187} | u_{188} | v_{189} | w_{190} | x_{191} | |
| $\acute{3}0x$ | y_{192} | z_{193} | ι_{194} | \mathcal{I}_{195} | \mathcal{A}_{196} | \mathcal{B}_{197} | \mathcal{C}_{198} | \mathcal{D}_{199} | $\text{~}\acute{C}\text{x}$ |
| $\acute{3}1x$ | \mathcal{E}_{200} | \mathcal{F}_{201} | \mathcal{G}_{202} | \mathcal{H}_{203} | \mathcal{I}_{204} | \mathcal{J}_{205} | \mathcal{K}_{206} | \mathcal{L}_{207} | |
| $\acute{3}2x$ | \mathcal{M}_{208} | \mathcal{N}_{209} | \mathcal{O}_{210} | \mathcal{P}_{211} | \mathcal{Q}_{212} | \mathcal{R}_{213} | \mathcal{S}_{214} | \mathcal{T}_{215} | $\text{~}\acute{D}\text{x}$ |
| $\acute{3}3x$ | \mathcal{U}_{216} | \mathcal{V}_{217} | \mathcal{W}_{218} | \mathcal{X}_{219} | \mathcal{Y}_{220} | \mathcal{Z}_{221} | a_{222} | b_{223} | |
| $\acute{3}4x$ | c_{224} | d_{225} | e_{226} | f_{227} | g_{228} | h_{229} | i_{230} | j_{231} | $\text{~}\acute{E}\text{x}$ |
| $\acute{3}5x$ | k_{232} | ℓ_{233} | m_{234} | n_{235} | o_{236} | p_{237} | q_{238} | r_{239} | |
| $\acute{3}6x$ | s_{240} | t_{241} | u_{242} | v_{243} | w_{244} | x_{245} | y_{246} | z_{247} | $\text{~}\acute{F}\text{x}$ |
| $\acute{3}7x$ | ι_{248} | \mathcal{J}_{249} | $_{250}$ | $_{251}$ | $_{252}$ | $_{253}$ | $_{254}$ | $_{255}$ | |
| | $\text{~}\acute{8}$ | $\text{~}\acute{9}$ | $\text{~}\acute{A}$ | $\text{~}\acute{B}$ | $\text{~}\acute{C}$ | $\text{~}\acute{D}$ | $\text{~}\acute{E}$ | $\text{~}\acute{F}$ | |

18.2 lettersA

| | ´0 | ´1 | ´2 | ´3 | ´4 | ´5 | ´6 | ´7 | |
|------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------------|-----|
| ´00x | Γ_0 | Δ_1 | Θ_2 | Λ_3 | Ξ_4 | Π_5 | Σ_6 | Υ_7 | ´0x |
| ´01x | Φ_8 | Ψ_9 | Ω_{10} | α_{11} | β_{12} | γ_{13} | δ_{14} | ϵ_{15} | |
| ´02x | ζ_{16} | η_{17} | θ_{18} | ι_{19} | κ_{20} | λ_{21} | μ_{22} | ν_{23} | ´1x |
| ´03x | ξ_{24} | π_{25} | ρ_{26} | σ_{27} | τ_{28} | υ_{29} | ϕ_{30} | χ_{31} | |
| ´04x | ψ_{32} | ω_{33} | ϵ_{34} | ϑ_{35} | ϖ_{36} | ϱ_{37} | ς_{38} | φ_{39} | ´2x |
| ´05x | $_{40}$ | $_{41}$ | $_{42}$ | \mathbb{O}_{43} | \mathbb{I}_{44} | \mathbb{Z}_{45} | \mathbb{J}_{46} | \mathbb{A}_{47} | |
| ´06x | \mathbb{S}_{48} | \mathbb{G}_{49} | \mathbb{T}_{50} | \mathbb{B}_{51} | $\mathbb{9}_{52}$ | $_{53}$ | \mathbb{C}_{54} | \mathbb{D}_{55} | ´3x |
| ´07x | \mathbb{E}_{56} | \mathbb{P}_{57} | \mathbb{M}_{58} | \mathbb{N}_{59} | \neq_{60} | $=_{61}$ | $\{_{62}$ | $\}_{63}$ | |
| ´10x | ∂_{64} | \mathfrak{A}_{65} | \mathfrak{B}_{66} | \mathfrak{C}_{67} | \mathfrak{D}_{68} | \mathfrak{E}_{69} | \mathfrak{F}_{70} | \mathfrak{G}_{71} | ´4x |
| ´11x | \mathfrak{H}_{72} | \mathfrak{I}_{73} | \mathfrak{J}_{74} | \mathfrak{K}_{75} | \mathfrak{L}_{76} | \mathfrak{M}_{77} | \mathfrak{N}_{78} | \mathfrak{O}_{79} | |
| ´12x | \mathfrak{P}_{80} | \mathfrak{Q}_{81} | \mathfrak{R}_{82} | \mathfrak{S}_{83} | \mathfrak{T}_{84} | \mathfrak{U}_{85} | \mathfrak{V}_{86} | \mathfrak{W}_{87} | ´5x |
| ´13x | \mathfrak{X}_{88} | \mathfrak{Y}_{89} | \mathfrak{Z}_{90} | \hbar_{91} | \hbar_{92} | λ_{93} | \mathbb{Z}_{94} | \mathbb{A}_{95} | |
| ´14x | \mathbb{E}_{96} | \mathfrak{a}_{97} | \mathfrak{b}_{98} | \mathfrak{c}_{99} | \mathfrak{d}_{100} | \mathfrak{e}_{101} | \mathfrak{f}_{102} | \mathfrak{g}_{103} | ´6x |
| ´15x | \mathfrak{h}_{104} | \mathfrak{i}_{105} | \mathfrak{j}_{106} | \mathfrak{k}_{107} | \mathfrak{l}_{108} | \mathfrak{m}_{109} | \mathfrak{n}_{110} | \mathfrak{o}_{111} | |
| ´16x | \mathfrak{p}_{112} | \mathfrak{q}_{113} | \mathfrak{r}_{114} | \mathfrak{s}_{115} | \mathfrak{t}_{116} | \mathfrak{u}_{117} | \mathfrak{v}_{118} | \mathfrak{w}_{119} | ´7x |
| ´17x | \mathfrak{x}_{120} | \mathfrak{y}_{121} | \mathfrak{z}_{122} | \mathfrak{l}_{123} | \mathfrak{j}_{124} | \mathfrak{l}_{125} | \mathfrak{j}_{126} | $\hat{\mathfrak{i}}_{127}$ | |
| ´20x | $_{128}$ | \mathfrak{K}_{129} | $_{130}$ | $_{131}$ | \mathbb{A}_{132} | \mathbb{B}_{133} | \mathbb{C}_{134} | \mathbb{D}_{135} | ´8x |
| ´21x | \mathbb{E}_{136} | \mathbb{F}_{137} | \mathbb{G}_{138} | \mathbb{H}_{139} | \mathbb{I}_{140} | \mathbb{J}_{141} | \mathbb{K}_{142} | \mathbb{L}_{143} | |
| ´22x | \mathbb{M}_{144} | \mathbb{N}_{145} | \mathbb{O}_{146} | \mathbb{P}_{147} | \mathbb{Q}_{148} | \mathbb{R}_{149} | \mathbb{S}_{150} | \mathbb{T}_{151} | ´9x |
| ´23x | \mathbb{U}_{152} | \mathbb{V}_{153} | \mathbb{W}_{154} | \mathbb{X}_{155} | \mathbb{Y}_{156} | \mathbb{Z}_{157} | \mathfrak{a}_{158} | \mathfrak{b}_{159} | |
| ´24x | \mathfrak{c}_{160} | \mathfrak{d}_{161} | \mathfrak{e}_{162} | \mathfrak{f}_{163} | \mathfrak{g}_{164} | \mathfrak{h}_{165} | \mathfrak{i}_{166} | \mathfrak{j}_{167} | ´Ax |
| ´25x | \mathfrak{k}_{168} | \mathfrak{l}_{169} | \mathfrak{m}_{170} | \mathfrak{n}_{171} | \mathfrak{o}_{172} | \mathfrak{p}_{173} | \mathfrak{q}_{174} | \mathfrak{r}_{175} | |
| ´26x | \mathfrak{s}_{176} | \mathfrak{t}_{177} | \mathfrak{u}_{178} | \mathfrak{v}_{179} | \mathfrak{w}_{180} | \mathfrak{x}_{181} | \mathfrak{y}_{182} | \mathfrak{z}_{183} | ´Bx |
| ´27x | \mathfrak{l}_{184} | \mathfrak{j}_{185} | \mathfrak{l}_{186} | \mathfrak{j}_{187} | \mathfrak{g}_{188} | \mathfrak{y}_{189} | \mathfrak{v}_{190} | \mathfrak{w}_{191} | |
| ´30x | $_{192}$ | \mathbb{A}_{193} | \mathbb{B}_{194} | \mathbb{C}_{195} | \mathbb{D}_{196} | \mathbb{E}_{197} | \mathbb{F}_{198} | \mathbb{G}_{199} | ´Cx |
| ´31x | \mathbb{H}_{200} | \mathbb{I}_{201} | \mathbb{J}_{202} | \mathbb{K}_{203} | \mathbb{L}_{204} | \mathbb{M}_{205} | \mathbb{N}_{206} | \mathbb{O}_{207} | |
| ´32x | \mathbb{P}_{208} | \mathbb{Q}_{209} | \mathbb{R}_{210} | \mathbb{S}_{211} | \mathbb{T}_{212} | \mathbb{U}_{213} | \mathbb{V}_{214} | \mathbb{W}_{215} | ´Dx |
| ´33x | \mathbb{X}_{216} | \mathbb{Y}_{217} | \mathbb{Z}_{218} | \mathbb{F}_{219} | \mathbb{N}_{220} | \mathbb{Y}_{221} | \mathbb{T}_{222} | $_{223}$ | |
| ´34x | $_{224}$ | \mathfrak{a}_{225} | \mathfrak{b}_{226} | \mathfrak{c}_{227} | \mathfrak{d}_{228} | \mathfrak{e}_{229} | \mathfrak{f}_{230} | \mathfrak{g}_{231} | ´Ex |
| ´35x | \mathfrak{h}_{232} | \mathfrak{i}_{233} | \mathfrak{j}_{234} | \mathfrak{k}_{235} | \mathfrak{l}_{236} | \mathfrak{m}_{237} | \mathfrak{n}_{238} | \mathfrak{o}_{239} | |
| ´36x | \mathfrak{p}_{240} | \mathfrak{q}_{241} | \mathfrak{r}_{242} | \mathfrak{s}_{243} | \mathfrak{t}_{244} | \mathfrak{u}_{245} | \mathfrak{v}_{246} | \mathfrak{w}_{247} | ´Fx |
| ´37x | \mathfrak{x}_{248} | \mathfrak{y}_{249} | \mathfrak{z}_{250} | \mathfrak{x}_{251} | $_{252}$ | $_{253}$ | $_{254}$ | $_{255}$ | |
| | ´8 | ´9 | ´A | ´B | ´C | ´D | ´E | ´F | |

18.3 symbols

| | ´0 | ´1 | ´2 | ´3 | ´4 | ´5 | ´6 | ´7 | |
|------|------------------|------------------|------------------|------------------|------------------|------------------|------------------|------------------|-----|
| ´00x | ¬ ₀ | · ₁ | × ₂ | * ₃ | ÷ ₄ | ◇ ₅ | ± ₆ | ∓ ₇ | ~0x |
| ´01x | ⊕ ₈ | ⊖ ₉ | ⊗ ₁₀ | ∅ ₁₁ | ⊙ ₁₂ | ◯ ₁₃ | ○ ₁₄ | ● ₁₅ | |
| ´02x | ≍ ₁₆ | ≡ ₁₇ | ⊆ ₁₈ | ⊇ ₁₉ | ≤ ₂₀ | ≥ ₂₁ | ≤ ₂₂ | ≥ ₂₃ | ~1x |
| ´03x | ~ ₂₄ | ≈ ₂₅ | ⊂ ₂₆ | ⊃ ₂₇ | ≪ ₂₈ | ≫ ₂₉ | < ₃₀ | > ₃₁ | |
| ´04x | ← ₃₂ | → ₃₃ | ↑ ₃₄ | ↓ ₃₅ | ↔ ₃₆ | ↗ ₃₇ | ↘ ₃₈ | ≈ ₃₉ | ~2x |
| ´05x | ⇐ ₄₀ | ⇒ ₄₁ | ⇑ ₄₂ | ⇓ ₄₃ | ⇔ ₄₄ | ↖ ₄₅ | ↙ ₄₆ | ∝ ₄₇ | |
| ´06x | ∕ ₄₈ | ∞ ₄₉ | ∈ ₅₀ | ∃ ₅₁ | Δ ₅₂ | ∇ ₅₃ | ≠ ₅₄ | ≡ ₅₅ | ~3x |
| ´07x | ∀ ₅₆ | ∃ ₅₇ | ¬ ₅₈ | ∅ ₅₉ | ℜ ₆₀ | ℑ ₆₁ | ⊤ ₆₂ | ⊥ ₆₃ | |
| ´10x | ℳ ₆₄ | ℳ ₆₅ | ℳ ₆₆ | ℳ ₆₇ | ℳ ₆₈ | ℳ ₆₉ | ℳ ₇₀ | ℳ ₇₁ | ~4x |
| ´11x | ℳ ₇₂ | ℳ ₇₃ | ℳ ₇₄ | ℳ ₇₅ | ℳ ₇₆ | ℳ ₇₇ | ℳ ₇₈ | ℳ ₇₉ | |
| ´12x | ℳ ₈₀ | ℳ ₈₁ | ℳ ₈₂ | ℳ ₈₃ | ℳ ₈₄ | ℳ ₈₅ | ℳ ₈₆ | ℳ ₈₇ | ~5x |
| ´13x | ℳ ₈₈ | ℳ ₈₉ | ℳ ₉₀ | ℳ ₉₁ | ℳ ₉₂ | ℳ ₉₃ | ℳ ₉₄ | ℳ ₉₅ | |
| ´14x | ⊢ ₉₆ | ⊣ ₉₇ | ⌈ ₉₈ | ⌋ ₉₉ | ⌈ ₁₀₀ | ⌋ ₁₀₁ | { ₁₀₂ | } ₁₀₃ | ~6x |
| ´15x | ⟨ ₁₀₄ | ⟩ ₁₀₅ | ₁₀₆ | ₁₀₇ | ↕ ₁₀₈ | ↕ ₁₀₉ | \ ₁₁₀ | ℓ ₁₁₁ | |
| ´16x | √ ₁₁₂ | Π ₁₁₃ | ∇ ₁₁₄ | ∫ ₁₁₅ | ⊔ ₁₁₆ | ⊓ ₁₁₇ | ⊆ ₁₁₈ | ⊇ ₁₁₉ | ~7x |
| ´17x | § ₁₂₀ | † ₁₂₁ | ‡ ₁₂₂ | ℙ ₁₂₃ | ♣ ₁₂₄ | ◇ ₁₂₅ | ♥ ₁₂₆ | ♠ ₁₂₇ | |
| ´20x | ∫ ₁₂₈ | ∫ ₁₂₉ | ∫ ₁₃₀ | ℳ ₁₃₁ | ℳ ₁₃₂ | ℳ ₁₃₃ | ℳ ₁₃₄ | ℳ ₁₃₅ | ~8x |
| ´21x | ℳ ₁₃₆ | ℳ ₁₃₇ | ℳ ₁₃₈ | ℳ ₁₃₉ | ℳ ₁₄₀ | ℳ ₁₄₁ | ℳ ₁₄₂ | ℳ ₁₄₃ | |
| ´22x | ℳ ₁₄₄ | ℳ ₁₄₅ | ℳ ₁₄₆ | ℳ ₁₄₇ | ℳ ₁₄₈ | ℳ ₁₄₉ | ℳ ₁₅₀ | ℳ ₁₅₁ | ~9x |
| ´23x | Π ₁₅₂ | Σ ₁₅₃ | ≠ ₁₅₄ | ∅ ₁₅₅ | ∅ ₁₅₆ | / ₁₅₇ | ` ₁₅₈ | ´ ₁₅₉ | |
| ´24x | ^ ₁₆₀ | ~ ₁₆₁ | ¯ ₁₆₂ | ˘ ₁₆₃ | · ₁₆₄ | ¨ ₁₆₅ | ° ₁₆₆ | ˇ ₁₆₇ | ~Ax |
| ´25x | … ₁₆₈ | ← ₁₆₉ | → ₁₇₀ | ↔ ₁₇₁ | ↔ ₁₇₂ | ↔ ₁₇₃ | → ₁₇₄ | ↔ ₁₇₅ | |
| ´26x | ↔ ₁₇₆ | ↔ ₁₇₇ | ↔ ₁₇₈ | ↔ ₁₇₉ | ↔ ₁₈₀ | ↔ ₁₈₁ | ↔ ₁₈₂ | ↔ ₁₈₃ | ~Bx |
| ´27x | ↔ ₁₈₄ | (₁₈₅ |) ₁₈₆ | [₁₈₇ |] ₁₈₈ | = ₁₈₉ | ≈ ₁₉₀ | △ ₁₉₁ | |
| ´30x | ≈ ₁₉₂ | ≈ ₁₉₃ | △ ₁₉₄ | ≈ ₁₉₅ | ≈ ₁₉₆ | △ ₁₉₇ | ≈ ₁₉₈ | ≈ ₁₉₉ | ~Cx |
| ´31x | … ₂₀₀ | ₂₀₁ | ₂₀₂ | ⊤ ₂₀₃ | ⊤ ₂₀₄ | ⊤ ₂₀₅ | ⊤ ₂₀₆ | ⊤ ₂₀₇ | |
| ´32x | · ₂₀₈ | · ₂₀₉ | ⊙ ₂₁₀ | · ₂₁₁ | · ₂₁₂ | · ₂₁₃ | ∕ ₂₁₄ | 215 | ~Dx |
| ´33x | 216 | 217 | 218 | 219 | 220 | 221 | 222 | 223 | |
| | ~8 | ~9 | ~A | ~B | ~C | ~D | ~E | ~F | |

18.4 A sample newtx-substex

You may either copy the entire block below, starting with the line `\begin{...}` and ending after the line beginning `\end{}` and pasting it into the top of your document before the `\documentclass{...}` line, which will allow for easy editing and will write the file to the same folder as your document, or make your own file, omitting those outer two lines.

```
\begin{filecontents*}{newtx-substex}
{f}{-3}
{j}{-3}
{p}{-1}
{y}{-1}
{A}{-3}
{B}{-1}
{D}{-1}
{H}{-1}
{I}{-1}
{K}{-1}
{L}{-1}
{M}{-1}
{N}{-0.5}
{P}{-1}
{X}{-1}
{\rho}{-1.5}
{\mu}{-1}
\end{filecontents*}
```

The ebgaramond option to newtxmath

As ebgaramond has an x-height considerably smaller than newtx, some amount of scaling is useful to bridge the gap. In making the replacement letters, I increased the size of the EBGaramond letters by 5%, so make some scaling combination that compensates for this. The weights of ebgaramond used in the substitutions were regular and semibold. This dictates one of the options used for ebgaramond.

EXAMPLE PREAMBLE:

```
\usepackage[lining,semibold,scaled=1.05]{ebgaramond}
% Latex BOLD renders with ebgaramond semibold
\usepackage[T1]{fontenc} % best for Western European languages
\usepackage{textcomp} % required to get special symbols
\usepackage[varqu,varl]{inconsolata}% a typewriter font must be defined
\usepackage{amsthm}% must be loaded before newtxmath
\usepackage[ebgaramond,vvarbb,subscriptcorrection]{newtxmath} % STIX Bbb
\usepackage{bm}% load after all math to give access to bold math
```