

# The `latexrelease` package<sup>\*</sup>

The L<sup>A</sup>T<sub>E</sub>X Project

2021/04/29

This file is maintained by the L<sup>A</sup>T<sub>E</sub>X Project team.  
Bug reports can be opened (category `latex`) at  
<https://latex-project.org/bugs.html>.

## 1 Introduction

Prior to the 2015 release of L<sup>A</sup>T<sub>E</sub>X, essentially no changes had been made to the L<sup>A</sup>T<sub>E</sub>X format code for some years, with all improvements being instead added to the package `fixltx2e`.

While this worked at a technical level it meant that you had to explicitly opt-in to bug fixes and improvements, and the vast majority of documents did not benefit.

As described in L<sup>A</sup>T<sub>E</sub>X News 22, a new policy is being implemented in which improvements will now be added to the format by default, and this `latexrelease` package may be used to ensure stability where needed, either by making a new format use an older definition of some commands, or conversely may be used to supply the new definitions for use with an old format.

The basic use is:

```
\RequirePackage[2015/01/01]{latexrelease}  
\documentclass{article}  
....
```

After such a declaration the document will use definitions current in the January 2015 L<sup>A</sup>T<sub>E</sub>X, whether the actual format being used is older, or newer than that date. In the former case a copy of `latexrelease.sty` would need to be made available for use with the older format. This may be used, for example, to share a document between co-workers using different L<sup>A</sup>T<sub>E</sub>X releases, or to protect a document from being affected by system updates. As well as the definitions within the format itself, individual packages may use the commands defined here to adjust their definitions to the specified date as described below.

Note that the `latexrelease` package is intended for use at the start of a *document*. Package and class code should not include this package as loading a package should not normally globally reset the effective version of L<sup>A</sup>T<sub>E</sub>X that is in force, so affecting all other packages used in the document.

---

<sup>\*</sup>This file has version number v1.0n, last revised 2021/04/29.

The bulk of this package, after some initial setup and option handling consists of a series of `\IncludeInRelease` commands which have been extracted from the main source files of the `LATEX` format. These contain the old and new versions of any commands with modified definitions.

## 2 Package Options

- *yyyy/mm/dd* or *yyyy-nn-dd* The package accepts any possible `LATEX` format date as argument, although dates in the future for which the current release of this package has no information will generate a warning. Dates earlier than 2015 will work but will roll back to some point in 2015 when the method was introduced. The `\requestedLaTeXdate` is set to the normalized date argument so that package rollback defaults to the specified date.
- **current** This is the default behaviour, it does not change the effective date of the format but does ensure that the `\IncludeInRelease` command is defined. The `\requestedLaTeXdate` macro is reset to 0 so that package rollback does not use the implicit date.
- **latest** sets the effective date of the format to the release date of this file, so in an older format applies all patches currently available. The `\requestedLaTeXdate` macro is reset to 0 so that package rollback does not use the implicit date.

In all cases, when the package is loaded, the `\sourceLaTeXdate` is defined to be the numerical representation of `\fmtversion` before the rollback/forward actually happens, so it is possible to test from which was the original `LATEX` version before `latexrelease` was loaded. This is particularly useful when some code in a package has to be redefined differently if rolling backwards in time or forwards.

## 3 Release Specific Code

The `\IncludeInRelease` mechanism allows the kernel developer to associate code with a specific date to choose different versions of definitions depending on the date specified as an option to the `latexrelease` package. Is also available for use by package authors (or even in a document if necessary).

`\IncludeInRelease` `{\code-date}[\format-date]{\label}{\message}\code\EndIncludeInRelease`

`{\code-date}` This date is associated with the `{\code}` argument and will be compared to the requested date in the option to the `latexrelease`.

`[\format-date]` This optional argument can be used to specify a format date with the code in addition to the mandatory `{\code-date}` argument. This can be useful for package developers as described below.

`{\label}` The `{\label}` argument is an identifier (string) that within a given package must be a unique label for each related set of optional definitions. Per package at most one code block from all the `\IncludeInRelease` declarations with the same label will be executed.

`{\message}` The `{\message}` is an informative string that is used in messages. It has no other function.

`<code>` Any  $\text{\TeX}$  code after the `\IncludeInRelease` arguments up until the and the following `\EndIncludeInRelease` is to be conditionally included depending on the date of the format as described below.

The `\IncludeInRelease` declarations with a given label should be in reverse chronological order in the file. The one chosen will depend on this order, the effective format version and the date options, as described below.

If your package `mypackage` defines a `\widget` command but has one definition using the features available in the 2015  $\text{\LaTeX}$  release, and a different definition is required for older formats then you can use:

```
\IncludeInRelease{2015/01/01}{\widget}{Widget Definition}
\def\widget{new version}%
\EndIncludeInRelease

\IncludeInRelease{0000/00/00}{\widget}{Widget Definition}
\def\widget{old version}%
\EndIncludeInRelease
```

If a document using this package is used with a format with effective release date of 2015/01/01 or later the new code will be used, otherwise the old code will be used. Note the *effective release date* might be the original  $\text{\LaTeX}$  release date as shown at the start of every  $\text{\LaTeX}$  job, or it may be set by the `latexrelease` package, so for example a document author who wants to ensure the new version is used could use

```
\RequirePackage[2015/01/01]{latexrelease}
\documentclass{article}
\usepackage{mypackage}
```

If the document is used with a  $\text{\LaTeX}$  format from 2014 or before, then `latexrelease` will not have been part of the original distribution, but it may be obtained from a later  $\text{\LaTeX}$  release or from CTAN and distributed with the document, it will make an older  $\text{\LaTeX}$  release act essentially like the 2015 release.

### 3.1 Intermediate Package Releases

The above example works well for testing against the `latex` format but is not always ideal for controlling code by the release date of the *package*. Suppose  $\text{\LaTeX}$  is not updated but in March you update the `mypackage` package and modify the definition of `\widget`. You could code the package as:

```
\IncludeInRelease{2015/03/01}{\widget}{Widget Definition}
\def\widget{even newer improved March version}%
\EndIncludeInRelease

\IncludeInRelease{2015/01/01}{\widget}{Widget Definition}
\def\widget{new version}%
\EndIncludeInRelease

\IncludeInRelease{0000/00/00}{\widget}{Widget Definition}
```

```
\def\widget{old version}%
\EndIncludeInRelease
```

This would work and allow a document author to choose a date such as

```
\RequirePackage[2015/03/01]{latexrelease}
\documentclass{article}
\usepackage{mypackage}
```

To use the latest version, however it would have disadvantage that until the next release of L<sup>A</sup>T<sub>E</sub>X, by default, if the document does not use `latexrelease` to specify a date, the new improved code will not be selected as the effective date will be 2015/01/01 and so the first code block will be skipped.

For this reason `\IncludeInRelease` has an optional argument that specifies an alternative date to use if a date option has not been specified to `latexrelease`.

```
\IncludeInRelease{2015/03/01}[2015/01/01]{\widget}{Widget Definition}
\def\widget{even newer improved March version}%
\EndIncludeInRelease
```

```
\IncludeInRelease{2015/01/01}{\widget}{Widget Definition}
\def\widget{new version}%
\EndIncludeInRelease
```

```
\IncludeInRelease{0000/00/00}{\widget}{Widget Definition}
\def\widget{old version}%
\EndIncludeInRelease
```

Now, by default on a 2015/01/01 L<sup>A</sup>T<sub>E</sub>X format, the first code block will compare the format date to the optional argument 2015/01/01 and so will execute the *even newer improved* version. The remaining blocks using the `\widget` label argument will all then be skipped.

If on the other hand the document requests an explicit release date using `latexrelease` then this date will be used to decide what code block to include.

## 3.2 Using `\IncludeInRelease` in Packages

If `\IncludeInRelease` is used within a package then all such conditional code needs to be within such declarations, e.g., it is not possible in the above example to have the “current” definition of `\widget` somewhere in the main code and only the two older definitions inside `\IncludeInRelease` declarations. If you would do this then one of those `\IncludeInRelease` declarations would be included overwriting the even newer code in the main part of the package. As a result your package may get fragmented over time with various `\IncludeInRelease` declarations sprinkled throughout your code or you have to interrupt the reading flow by putting those declarations together but not necessarily in the place where they belong.

To avoid this issue you can use the following coding strategy: place the current `\widget` definition in the main code where it correctly belongs.

```
...
\def\widget {even newer improved March version}
\def\@widget{newly added helper command no defined in older releases}
...
```

Then, near the end of your package place the following:

```
\IncludeInRelease{2015/03/01}[2015/01/01]{\widget}{Widget Definition}
\EndIncludeInRelease

\IncludeInRelease{2015/01/01}{\widget}{Widget Definition}
\def\widget{new version}%
\let\@widget\@undefined % this doesn't exist in earlier releases
\EndIncludeInRelease

\IncludeInRelease{0000/00/00}{\widget}{Widget Definition}
\def\widget{old version}%
\EndIncludeInRelease
```

This way the empty code block hides the other `\IncludeInRelease` declarations unless there is an explicit request with a date 2015/01/01 or earlier.

Now if you make a further change to `\widget` in the future you simply copy the current definition into the empty block and add a new empty declaration with today's date and the current format date. This way your main code stays readable and the old versions accumulate at the end of the package.<sup>1</sup>

The only other “extra effort” necessary when using this approach is that it may be advisable to undo new definitions in the code block for the previous release, e.g., in the above example we undefined `\@widget` as that isn't available in the 2015/01/01 release but was defined in the main code. If all your conditional code is within `\IncludeInRelease` declarations that wouldn't been necessary as the new code only gets defined if that release is chosen.

## 4 Declaring entire modules

Sometimes a large chunk of code is added as a module to another larger code base. As example of that in the 2020-10-01 release L<sup>A</sup>T<sub>E</sub>X got a new hook management system, `lthooks`, which was added in one go and, as with all changes to the kernel, it was added to `latexrelease`. However rolling back from a future date to the 2020-10-01 release didn't work because `latexrelease` would try to define again all those commands, which would result in many “already defined” errors and similar issues.

To solve that problem, completely new modules can be defined in `latexrelease` using the commands:

```
\NewModuleRelease{<initial release date>}{<name>}{<message>}
  <module code>
\IncludeInRelease{0000/00/00}{<name>}{<message>}
  <undefine module code>
\EndModuleRelease
```

With that setup, the module `<name>` will be declared to exist only in releases equal or later `<initial release date>`.

---

<sup>1</sup>Of course there may be some cases in which the old code has to be in a specific place within the package as other code depends on it (e.g., if you `\let` something to it). In that case you have to place the code variations in the right place in your package rather than accumulating them at the very end.

If `latexrelease` is rolling backwards or forwards between dates after *⟨initial release date⟩*, then all the *⟨module code⟩* is skipped, except when inside *⟨IncludeInRelease⟩* guards, in which case the code is applied or skipped as discussed above.

If rolling forward from a date before the module’s *⟨initial release date⟩* to a date after that, then all the *⟨module code⟩* is executed to define the module, and `\IncludeInRelease` guards are executed accordingly, depending on the date declared and the target date.

If `latexrelease` is rolling back to a date before *⟨release date⟩*, then the code in the `\IncludeInRelease` guard dated 0000/00/00 is executed instead to undefine the module. This guard *is not* ended by the usual `\EndIncludeInRelease`, but instead by `\EndModuleRelease`.

Finally, if rolling backwards or forwards between dates both before *⟨initial release date⟩*, the entire code between *⟨NewModuleRelease⟩* and *⟨EndModuleRelease⟩* is entirely skipped.

## 4.1 Example

Here is an example usage of the structure described above, as it would be used in the L<sup>A</sup>T<sub>E</sub>X kernel, taking `lthooks` as example:

```
%<*2ekernel|latexrelease>
\ExplSyntaxOn
%<latexrelease>\NewModuleRelease{2020/10/01}{lthooks}%
%<latexrelease>          {The~hook~management~system}
\NewDocumentCommand \NewHook { m }
  { \hook_new:n {#1} }
%<latexrelease>\IncludeInRelease{2021/06/01}{\AddToHook}{Long~argument}
\NewDocumentCommand \AddToHook { m o +m }
  { \hook_gput_code:nnn {#1} {#2} {#3} }
%<latexrelease>\EndIncludeInRelease
%<latexrelease>
%<latexrelease>\IncludeInRelease{2020/10/01}{\AddToHook}{Long~argument}
%<latexrelease>\NewDocumentCommand \AddToHook { m o m }
%<latexrelease> { \hook_gput_code:nnn {#1} {#2} {#3} }
%<latexrelease>\EndIncludeInRelease
%<latexrelease>
%<latexrelease>\IncludeInRelease{0000/00/00}{lthooks}{Undefine~lthooks}
%<latexrelease>\cs_undefine:N \NewHook
%<latexrelease>\cs_undefine:N \AddToHook
%<latexrelease>\EndModuleRelease
\ExplSyntaxOff
%</2ekernel|latexrelease>
```

In the example above, `\NewHook` is declared only once, and unchanged in the next release (2021/06/01 in the example), so it has no `\IncludeInRelease` guards, and will only be defined if needed. `\AddToHook`, on the other hand, changed between the two releases (made up for the example; it didn’t really happen) and has an `\IncludeInRelease` block for the current release (off `docstrip` guards, so it goes into the kernel too), and another for the previous release (in `docstrip` guards so it goes only into `latexrelease`).

Note that in the example above, `\ExplSyntaxOn` and `\ExplSyntaxOff` were added *outside* the module code because, as discussed above, sometimes the code

outside `\IncludeInRelease` guards may be skipped, but not the code inside them, and in that case the catcodes would be wrong when defining the code.

## 5 fixltx2e

As noted above, prior to the 2015 L<sup>A</sup>T<sub>E</sub>X release updates to the L<sup>A</sup>T<sub>E</sub>X kernel were not made in the format source files but were made available in the `fixltx2e` package. That package is no longer needed but we generate a small package from this source that just makes a warning message but otherwise does nothing.

## 6 Implementation

We require at least a somewhat sane version of L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub>. Earlier ones were really quite different from one another.

```
1 (*latexrelease)
2 \NeedsTeXFormat{LaTeX2e}[1996/06/01]
```

### 6.1 Setup

`\sourceLaTeXdate` Store the original L<sup>A</sup>T<sub>E</sub>X format version as a number in the format `YYYYMMDD`. This macro has to be defined conditionally, so that it isn't changed in case `latexrelease.sty` is loaded twice (for tests), but it can't be defined in the kernel only, otherwise `latexrelease.sty` wouldn't work in older L<sup>A</sup>T<sub>E</sub>X due to the missing macro.

```
3 \ifundefined{sourceLaTeXdate}{%
4   \edef\sourceLaTeXdate{%
5     \expandafter\@parse@version\fmtversion//00\@nil}}{}}%
```

`\IncludeInRelease` These are defined in `ltvers.dtx`.  
`\EndIncludeInRelease`

```
6 \DeclareOption*{%
7   \def\@IncludeInRelease#1[#2]{\@IncludeInRelease{#1}}%
8   \let\requestedpatchdate\CurrentOption}
9 \DeclareOption{latest}{%
10  \let\requestedpatchdate\latexreleaseversion
11  \AtEndOfPackage{\def\requestedLaTeXdate{0}}}
12 \DeclareOption{current}{%
13  \let\requestedpatchdate\fmtversion
14  \AtEndOfPackage{\def\requestedLaTeXdate{0}}}
15 \let\requestedpatchdate\fmtversion
16 \ProcessOptions\relax
```

Sanity check options, it allows some non-legal dates but always ensures `requestedLaTeXdate` gets set to a number. Generate an error if there are any non digit tokens remaining after removing the `//`.

```
17 \def\reserved@a{%
18  \edef\requestedLaTeXdate{\the\count@}%
19  \reserved@b}
20 \def\reserved@b#1\\{%
21  \def\reserved@b{#1}%
22  \ifx\reserved@b\@empty\else
```

```

23 \PackageError{latexrelease}%
24         {Unexpected option \requestedpatchdate}%
25         {The option must be of the form yyyy/mm/dd or yyyy-mm-dd}%
26 \fi}
27 \afterassignment\reserved@a
28 \count@\expandafter
29   \@parse@version\expandafter\requestedpatchdate//00\@nil\
    less precautions needed for \fmtversion
30 \edef\currentLaTeXdate{%
31   \expandafter\@parse@version\fmtversion//00\@nil}
32 \ifnum\requestedLaTeXdate=\currentLaTeXdate
33 \PackageWarningNoLine{latexrelease}{%
34   Current format date selected, no patches applied}
35 \expandafter\endinput
36 \fi

```

A newer version of latexrelease should have been distributed with the later format.

```

37 \ifnum\currentLaTeXdate
38   >\expandafter\@parse@version\latexreleaseversion//00\@nil
39 \PackageWarningNoLine{latexrelease}{%
40   The current package is for an older LaTeX format:\MessageBreak
41   LaTeX \latexreleaseversion\space\MessageBreak
42   Obtain a newer version of this package!}
43 \expandafter\endinput
44 \fi

```

can't patch into the future, could make this an error but it has some uses to control package updates so allow for now.

```

45 \ifnum\requestedLaTeXdate
46   >\expandafter\@parse@version\latexreleaseversion//00\@nil
47 \PackageWarningNoLine{latexrelease}{%
48   The current package is for LaTeX \latexreleaseversion:\MessageBreak
49   It has no patches beyond that date\MessageBreak
50   There may be an updated version\MessageBreak
51   of this package available from CTAN}
52 \expandafter\endinput
53 \fi

```

Update the format version to the requested date.

```

54 \let\fmtversion\requestedpatchdate
55 \let\currentLaTeXdate\requestedLaTeXdate

```

## 6.2 Ignoring \_new errors when rolling back

Enforce \ExplSyntaxOn and \ExplSyntaxOff to be \relax in latexrelease if they are not yet defined. They are later restored to be undefined if needed.

```

56 \csname ExplSyntaxOn\endcsname
57 \csname ExplSyntaxOff\endcsname

```

Define a set of changes here, but we'll only use them later to make sure they are applied after expl3 is loaded. If loading from a rather old format, we don't have \ExplSyntaxOn yet.

```

58 \begingroup
59 \endlinechar=-1
60 \catcode95=11 % _
61 \catcode58=11 % :
62 \catcode126=10 % ~
63 \catcode32=09 % <space>
64 \xdef\latexrelease@postexpl{\unexpanded{%
65 (@@=latexrelease)

```

First we'll define a `\declarecommand` that does `\renewcommand` if the command being defined already exists, and `\newcommand` otherwise.

```

66 \cs_gset_protected:Npn \@@_declare_command:w
67 { \@star@or@long \@@_declare_command:Nw }
68 \cs_gset_protected:Npn \@@_declare_command:Nw #1
69 { \cs_if_exist:NTF #1 { \renewcommand } { \newcommand } #1 }

```

Then define a version of `\e@alloc` that checks if the control sequence being defined already exists, and if so, checks if its meaning is the same as the one that would be defined with the call to `\e@alloc`. If both tests pass, nothing is defined to save a register. This version also takes care of setting `\allocationnumber` to the value it would have after the register is allocated.

```

70 \cs_gset_protected:Npn \@@_e@alloc:NnnnnN #1 #2 #3 #4 #5 #6
71 {
72   \cs_if_free:NTF #6
73   { \use:n }
74   {
75     \exp_after:wN \@@_e@alloc:N
76     \token_to_meaning:N #6 \scan_stop: {#2} #6
77   }
78   { \@@_e@alloc #1 {#2} {#3} {#4} {#5} #6 }
79 }

```

Walk through the meaning of the control sequence token by token, looking for the register allocation number.

```

80 \cs_gset_protected:Npn \@@_e@alloc:N #1
81 {
82   \if_int_compare:w 0 < 0
83   \if_int_compare:w 10 < 9#1 ~ 1 \fi:
84   \if_charcode:w " #1 1 \fi: \exp_stop_f:
85   \tex_afterassignment:D \@@_e@alloc:w
86   \@tempcnta #1
87   \use_i:nnn
88   \fi:
89   \use:n
90   {
91     \if_meaning:w \scan_stop: #1
92     \exp_after:wN \use_iv:nnnn
93     \fi:
94     \@@_e@alloc:N
95   }
96 }

```

When found, check if it is the exact same register as it would be allocated, and if it is, set `\allocationnumber` accordingly and exit, otherwise undefine the register and allocate from scratch.

```

97 \cs_gset_protected:Npn \@@_e@alloc:w #1 \scan_stop: #2 #3
98 {
99   #2 \@@_tmp:w = \@tempcnta
100   \token_if_eq_meaning:NNTF #3 \@@_tmp:w
101   { \int_set_eq:NN \allocationnumber \@tempcnta \use_none:n }
102   { \cs_set_eq:NN #3 \tex_undefined:D \use:n }
103 }

```

Now create a token list to hold the list of changed commands, and define a temporary macro that will loop through the command list, store each in `\l_@@_restores_tl`, save a copy, and redefine each.

```

104 \tl_clear_new:N \l_@@_restores_tl
105 \cs_gset:Npn \@@_tmp:w #1 #2
106 {
107   \quark_if_recursion_tail_stop_do:Nn #1
108   { \cs_undefine:N \@@_tmp:w }
109   \tl_put_right:Nn \l_@@_restores_tl {#1}
110   \cs_set_eq:cN { @@_ \cs_to_str:N #1 } #1
111   \cs_set_eq:NN #1 #2
112   \@@_tmp:w
113 }

```

The redefinitions below are needed because:

`\__kernel_chk_if_free_cs:N` This function is used ubiquitously in the `l3kernel` to check if a control sequence is definable, and give an error otherwise (similar to `\@ifdefinable`). Making it a no-op is enough for most cases (except when defining new registers);

`\e@alloc` In the case of new registers, we waste an allocation number if we do `\new\meta {thing}` in a register that's already allocated, so the redefinition of `\e@alloc` checks if the new register is really necessary. This code does not clear the register, which might cause problems in the future, if a register is allocated but not properly cleared before using;

`\__kernel_msg_error:nxx` This command is used to error on already defined scan marks. Just making the error do nothing is enough, as no action is taken in that case;

`\msg_new:nnnn` Used to define new messages. Making it `_gset` is enough. Other `msg` commands like `\msg_new:nnn` and `\__kernel_msg_new:nnn(n)` are defined in terms of `\msg_new:nnnn`, so there is no need to change the other ones;

`\NewDocumentCommand` Used to define user-level commands in the kernel. Making it equal to `\DeclareDocumentCommand` solves the problem;

`\newcommand` Same as above.

And here we go:

```

114 \@@_tmp:w
115 \__kernel_chk_if_free_cs:N \use_none:n
116 \e@alloc \@@_e@alloc:NnnnnN
117 \__kernel_msg_error:nxx \use_none:nnn
118 \msg_new:nnnn \msg_gset:nnnn

```

```

119 \NewDocumentCommand \DeclareDocumentCommand
120 \newcommand \@@_declare_command:w
Temp addition ...
121 \__kernel_msg_error:nnn \use_none:nnn % needed while redirect for kernel msgs doesn't work
122 \q_recursion_tail \q_recursion_tail
123 \q_recursion_stop
Finally, redirect the error thrown by \NewHook to nowhere so it can be safely
reused (the hook isn't redeclared if it already exists).
124 \msg_redirect_name:nnn { hooks } { exists } { none }
125 }%
126 \endgroup
127 \</latexrelease>

```

### 6.3 Undoing the temp modifications

If \ExplSyntaxOn exists (defined and not equal \relax), then use the expl3 restore code, otherwise restore \ExplSyntaxOn and \ExplSyntaxOff to be undefined.

```

128 \</latexrelease-finish>
129 \ifundefined{ExplSyntaxOn}%
130   {\let\ExplSyntaxOn\@undefined
131    \let\ExplSyntaxOff\@undefined
132    \@gobble}%
133   {\ExplSyntaxOn
134    \@firstofone}%
135   {%

```

Now just loop through the list of redefined commands and restore their previous meanings.

```

136 \tl_map_inline:Nn \l_@@_restores_tl
137   {
138     \cs_set_eq:Nc #1 { @@_ \cs_to_str:N #1 }
139     \cs_undefine:c { @@_ \cs_to_str:N #1 }
140   }
141 \tl_clear:N \l_@@_restores_tl

```

And restore the hook error message.

```

142 \msg_redirect_name:nnn { hooks } { exists } { }
143 \@@=
144 \ExplSyntaxOff}%
145 \</latexrelease-finish>

```

### 6.4 Individual Changes

The code for each change will be inserted at this point, extracted from the kernel source files.

### 6.5 fixltx2e

Generate a stub fixltx2e package:

```

146 \<fixltx2e>
147 \IncludeInRelease{2015/01/01}{\fixltxe}{Old fixltx2e package}

```

```

148 \NeedsTeXFormat{LaTeX2e}
149 \PackageWarningNoLine{fixltx2e}{%
150 fixltx2e is not required with releases after 2015\MessageBreak
151 All fixes are now in the LaTeX kernel.\MessageBreak
152 See the latexrelease package for details}
153 \EndIncludeInRelease
154 \IncludeInRelease{0000/00/00}{\fixltxe}{Old fixltx2e package}
155 \def\@outputdblcol{%
156   \if@firstcolumn
157     \global\@firstcolumnfalse
158     \global\setbox\@leftcolumn\copy\@outputbox
159     \splitmaxdepth\maxdimen
160     \vbadness\maxdimen
161     \setbox\@outputbox\vbox{\unvbox\@outputbox\unskip}%
162     \setbox\@outputbox\vsplit\@outputbox to\maxdimen
163     \toks@expandafter{\topmark}%
164     \xdef\@firstcoltopmark{\the\toks@}%
165     \toks@expandafter{\splitfirstmark}%
166     \xdef\@firstcolfirstmark{\the\toks@}%
167     \ifx\@firstcolfirstmark\@empty
168       \global\let\@setmarks\relax
169     \else
170       \gdef\@setmarks{%
171         \let\firstmark\@firstcolfirstmark
172         \let\topmark\@firstcoltopmark}%
173     \fi
174   \else
175     \global\@firstcolumntrue
176     \setbox\@outputbox\vbox{%
177       \hb@xt@\textwidth{%
178         \hb@xt@\columnwidth{\box\@leftcolumn \hss}%
179         \hfil
180         {\normalcolor\vrule \@width\columnseprule}%
181         \hfil
182         \hb@xt@\columnwidth{\box\@outputbox \hss}}}%
183     \@combinedblfloats
184     \@setmarks
185     \@outputpage
186     \beginingroup
187       \@dblfloatplacement
188       \@startdblcolumn
189       \@whilesw\if@fcolmade \fi{\@outputpage\@startdblcolumn}%
190     \endgroup
191   \fi}
192 \def\end@dblfloat{%
193   \if@twocolumn
194     \@endfloatbox
195     \ifnum\@floatpenalty <\z@
196       \@largefloatcheck
197       \global\dp\@currbox1sp %
198       \@cons\@currlist\@currbox
199       \ifnum\@floatpenalty <-\@Mii
200         \penalty -\@Miv
201         \@tempdima\prevdepth

```

```

202         \vbox{}%
203         \prevdepth\@tempdima
204         \penalty\@floatpenalty
205     \else
206         \adjust{\penalty -\@Miv \vbox{}}\penalty\@floatpenalty}\@Esphack
207     \fi
208 \fi
209 \else
210     \end@float
211 \fi
212 }
213 \def\@testwrongwidth #1{%
214     \ifdim\dp#1=f@depth
215     \else
216         \global\@testtrue
217     \fi}
218 \let\f@depth\z@
219 \def\@dblfloatplacement{\global\@dbltopnum\c@dbltopnumber
220     \global\@dbltoproom \dbltopfraction\@colht
221     \textmin \colht
222     \advance \textmin -\@dbltoproom
223     \fpmmin \dblfloatpagefraction\textheight
224     \fptop \dblftop
225     \fpsep \dblfpsep
226     \fpbot \dblfpbot
227     \def\f@depth{1sp}}
228 \def \doclearpage {%
229     \ifvoid\footins
230         \setbox\@tempboxa\vsplit\@cclv to\z@ \unvbox\@tempboxa
231         \setbox\@tempboxa\box\@cclv
232         \xdef\@deferlist{\@toplist\@botlist\@deferlist}%
233         \global \let \@toplist \empty
234         \global \let \@botlist \empty
235         \global \@colroom \colht
236         \ifx \@currlist\empty
237             \else
238                 \@latexerr{Float(s) lost}\@ehb
239                 \global \let \@currlist \empty
240             \fi
241         \@makefcolumn\@deferlist
242         \@whilesw\if@colmade \fi{\@opcol\@makefcolumn\@deferlist}%
243         \if@twocolumn
244             \if@firstcolumn
245                 \xdef\@deferlist{\@dbltoplist\@deferlist}%
246                 \global \let \@dbltoplist \empty
247                 \global \colht \textheight
248                 \begingroup
249                     \dblfloatplacement
250                     \@makefcolumn\@deferlist
251                     \@whilesw\if@colmade \fi{\@outputpage
252                         \@makefcolumn\@deferlist}%
253                 \endgroup
254             \else
255                 \vbox{}\clearpage

```

```

256         \fi
257     \fi
258     \ifx\@deferlist\@empty \else\clearpage \fi
259 \else
260     \setbox\@cclv\vbox{\box\@cclv\vfil}%
261     \@makecol\@opcol
262     \clearpage
263 \fi
264 }
265 \def \@startdblcolumn {%
266     \@tryfcolumn \@deferlist
267     \if@fcolmade
268     \else
269         \begingroup
270             \let \reserved@b \@deferlist
271             \global \let \@deferlist \@empty
272             \let \@elt \@sdblcolelt
273             \reserved@b
274         \endgroup
275     \fi
276 }
277 \def \@addtonextcol{%
278     \begingroup
279     \@insertfalse
280     \@setfloattypecounts
281     \ifnum \@fpstype=8
282     \else
283         \ifnum \@fpstype=24
284         \else
285             \@flsettextmin
286             \@reqcolroom \ht\@currbox
287             \advance \@reqcolroom \@textmin
288             \ifdim \@colroom>\@reqcolroom
289                 \@flsetnum \@colnum
290                 \ifnum \@colnum>\z@
291                     \@bitor\@currtype\@deferlist
292                     \@testwrongwidth\@currbox
293                     \if@test
294                     \else
295                         \@addtotoporbot
296                     \fi
297                 \fi
298             \fi
299         \fi
300     \fi
301     \if@insert
302     \else
303         \@cons\@deferlist\@currbox
304     \fi
305 \endgroup
306 }
307 \def \@addtodblcol{%
308     \begingroup
309     \@insertfalse

```

```

310 \setfloattypecounts
311 \getfpsbit \tw@
312 \ifodd\@tempcnta
313 \flsetnum \dbltopnum
314 \ifnum \dbltopnum>\z@
315 \tempswafalse
316 \ifdim \dbltoproom>\ht\currbox
317 \tempswatrue
318 \else
319 \ifnum \fpstype<\sist@n
320 \advance \dbltoproom \textmin
321 \ifdim \dbltoproom>\ht\currbox
322 \tempswatrue
323 \fi
324 \advance \dbltoproom -\textmin
325 \fi
326 \fi
327 \if@tempswa
328 \bitor \currtype \deferlist
329 \testwrongwidth\currbox
330 \if@test
331 \else
332 \tempdima -\ht\currbox
333 \advance\tempdima
334 -\ifx \dbltoplist\empty \dbltextfloatsep \else
335 \dblfloatsep \fi
336 \global \advance \dbltoproom \tempdima
337 \global \advance \colht \tempdima
338 \global \advance \dbltopnum \m@ne
339 \cons \dbltoplist \currbox
340 \inserttrue
341 \fi
342 \fi
343 \fi
344 \if@insert
345 \else
346 \cons\deferlist\currbox
347 \fi
348 \endgroup
349 }
350 \def \addtocurcol {%
351 \insertfalse
352 \setfloattypecounts
353 \ifnum \fpstype=8
354 \else
355 \ifnum \fpstype=24
356 \else
357 \flsettextmin
358 \advance \textmin \textfloatsheight
359 \reqcolroom \pageht
360 \ifdim \textmin>\reqcolroom
361 \reqcolroom \textmin
362 \fi
363 \fi

```

```

364 \advance \@reqcolroom \ht\@currbox
365 \ifdim \@colroom>\@reqcolroom
366 \@flsetnum \@colnum
367 \ifnum \@colnum>\z@
368 \@bitor\@currtype\@deferlist
369 \@testwrongwidth\@currbox
370 \if@test
371 \else
372 \@bitor\@currtype\@botlist
373 \if@test
374 \@addtobot
375 \else
376 \ifodd \count\@currbox
377 \advance \@reqcolroom \intextsep
378 \ifdim \@colroom>\@reqcolroom
379 \global \advance \@colnum \m@ne
380 \global \advance \@textfloatsheight \ht\@currbox
381 \global \advance \@textfloatsheight 2\intextsep
382 \@cons \@midlist \@currbox
383 \if@nobreak
384 \nobreak
385 \@nobreakfalse
386 \everypar{}%
387 \else
388 \addpenalty \interlinepenalty
389 \fi
390 \vskip \intextsep
391 \box\@currbox
392 \penalty\interlinepenalty
393 \vskip\intextsep
394 \ifnum\outputpenalty <-\@Mii \vskip -\parskip\fi
395 \outputpenalty \z@
396 \@inserttrue
397 \fi
398 \fi
399 \if@insert
400 \else
401 \@addtotoporbot
402 \fi
403 \fi
404 \fi
405 \fi
406 \fi
407 \fi
408 \fi
409 \if@insert
410 \else
411 \@resethfps
412 \@cons\@deferlist\@currbox
413 \fi
414 }
415 \def\@xtryfc #1{%
416 \@next\reserved@a\@trylist{#1}%
417 \@currtype \count #1%

```

```

418 \divide\@currtype\@xxxii
419 \multiply\@currtype\@xxxii
420 \@bitor \@currtype \@failedlist
421 \@testfp #1%
422 \@testwrongwidth #1%
423 \ifdim \ht #1>\@colht
424     \@testtrue
425 \fi
426 \if@test
427     \@cons\@failedlist #1%
428 \else
429     \@ytryfc #1%
430 \fi}
431 \def\@ztryfc #1{%
432     \@tempcnta\count #1%
433     \divide\@tempcnta\@xxxii
434     \multiply\@tempcnta\@xxxii
435     \@bitor \@tempcnta {\@failedlist \@flfail}%
436     \@testfp #1%
437     \@testwrongwidth #1%
438     \@tempdimb\@tempdima
439     \advance\@tempdimb\ht #1%
440     \advance\@tempdimb\@fpsep
441     \ifdim \@tempdimb >\@colht
442         \@testtrue
443     \fi
444     \if@test
445         \@cons\@flfail #1%
446     \else
447         \@cons\@flsucceed #1%
448         \@tempdima\@tempdimb
449     \fi}
450 \def\@{\spacefactor\@m{}}
451 \def\@tempa#1#2{#1#2\relax}
452 \ifx\setlength\@tempa
453     \def\setlength#1#2{#1 #2\relax}
454 \fi
455 \def\addpenalty#1{%
456     \ifvmode
457         \if@minipage
458         \else
459             \if@nobreak
460             \else
461                 \ifdim\lastskip=\z@
462                     \penalty#1\relax
463                 \else
464                     \@tempskipb\lastskip
465                     \begingroup
466                     \advance \@tempskipb
467                         \ifdim\prevdepth>\maxdepth\maxdepth\else
468                             \ifdim \prevdepth = -\@m\p@ \z@ \else \prevdepth \fi
469                     \fi
470                     \vskip -\@tempskipb
471                     \penalty#1%

```

```

472         \vskip \@tempskipb
473     \endgroup
474     \vskip -\@tempskipb
475     \vskip \@tempskipb
476 \fi
477 \fi
478 \fi
479 \else
480     \@noitemerr
481 \fi}
482 \def\@fnsymbol#1{%
483     \ifcase#1\or \TextOrMath\textasteriskcentered *\or
484     \TextOrMath \textdagger \dagger\or
485     \TextOrMath \textdaggerdbl \ddagger \or
486     \TextOrMath \textsection \mathsection\or
487     \TextOrMath \textparagraph \mathparagraph\or
488     \TextOrMath \textbardbl \|\or
489     \TextOrMath {\textasteriskcentered\textasteriskcentered}{**}\or
490     \TextOrMath {\textdagger\textdagger}{\dagger\dagger}\or
491     \TextOrMath {\textdaggerdbl\textdaggerdbl}{\ddagger\ddagger}\else
492     \@ctrerr \fi
493 }
494 \begingroup\expandafter\expandafter\expandafter\endgroup
495 \expandafter\ifx\csname eTeXversion\endcsname\relax
496 \DeclareRobustCommand\TextOrMath{%
497     \ifmmode \expandafter\@secondoftwo
498     \else \expandafter\@firstoftwo \fi}
499 \protected@edef\TextOrMath#1#2{\TextOrMath{#1}{#2}}
500 \else
501 \protected\expandafter\def\csname TextOrMath\space\endcsname{%
502     \ifmmode \expandafter\@secondoftwo
503     \else \expandafter\@firstoftwo \fi}
504 \edef\TextOrMath#1#2{%
505     \expandafter\noexpand\csname TextOrMath\space\endcsname
506     {#1}{#2}}
507 \fi
508 \def\@esphack{%
509     \relax
510     \ifhmode
511         \spacefactor\@savsf
512         \ifdim\@savsk>\z@
513             \nobreak \hskip\z@skip % <-----
514             \ignorespaces
515         \fi
516     \fi}
517 \def\@Esphack{%
518     \relax
519     \ifhmode
520         \spacefactor\@savsf
521         \ifdim\@savsk>\z@
522             \nobreak \hskip\z@skip % <-----
523             \@ignoretrue
524             \ignorespaces
525         \fi

```

```

526 \fi}
527 \DeclareRobustCommand\em
528     {\@nomath\em \ifdim \fontdimen\@ne\font >\z@
529         \eminnershape \else \itshape \fi}
530 \def\eminnershape{\upshape}
531 \DeclareRobustCommand*\textsubscript[1]{%
532     \@textsubscript{\selectfont#1}}
533 \def\@textsubscript#1{%
534     {\m@th\ensuremath_{\mbox{\fontsize\sf@size\z@#1}}}}
535 \def\@DeclareMathSizes #1#2#3#4#5{%
536     \@defaultunits\dimen@ #2pt\relax\@nnil
537     \if $#3$%
538         \expandafter\let\csname S@\strip@pt\dimen@\endcsname\math@fontsfalse
539     \else
540         \@defaultunits\dimen@ii #3pt\relax\@nnil
541         \@defaultunits\@tempdima #4pt\relax\@nnil
542         \@defaultunits\@tempdimb #5pt\relax\@nnil
543         \toks@{#1}%
544         \expandafter\xdef\csname S@\strip@pt\dimen@\endcsname{%
545             \gdef\noexpand\tf@size{\strip@pt\dimen@ii}%
546             \gdef\noexpand\sf@size{\strip@pt\@tempdima}%
547             \gdef\noexpand\ssf@size{\strip@pt\@tempdimb}%
548             \the\toks@
549         }%
550     \fi
551 }
552 \providecommand*\MakeRobust[1]{%
553     \@ifundefined{\expandafter\@gobble\string#1}{%
554         \@latex@error{The control sequence ‘\string#1’ is undefined!%
555             \MessageBreak There is nothing here to make robust}%
556         \@eha
557     }%
558     {%
559         \@ifundefined{\expandafter\@gobble\string#1\space}%
560         {%
561             \expandafter\let\csname
562             \expandafter\@gobble\string#1\space\endcsname=#1%
563             \edef\reserved@a{\string#1}%
564             \def\reserved@b{#1}%
565             \edef\reserved@b{\expandafter\strip@prefix\meaning\reserved@b}%
566             \edef#1{%
567                 \ifx\reserved@a\reserved@b
568                     \noexpand\x@protect\noexpand#1%
569                 \fi
570                 \noexpand\protect\expandafter\noexpand
571                 \csname\expandafter\@gobble\string#1\space\endcsname}%
572             }%
573             {\@latex@info{The control sequence ‘\string#1’ is already robust}}%
574         }%
575 }
576 \MakeRobust\(  

577 \MakeRobust\  

578 \MakeRobust\  

579 \MakeRobust\

```

```

580 \MakeRobust\makebox
581 \MakeRobust\savebox
582 \MakeRobust\framebox
583 \MakeRobust\parbox
584 \MakeRobust\rule
585 \MakeRobust\raisebox
586 \def\@xfloat #1[#2]{%
587   \@nodocument
588   \def \@cuptype {#1}%
589   \def \@fps {#2}%
590   \@onelevel@sanitize \@fps
591   \def \reserved@b {!}%
592   \ifx \reserved@b \@fps
593     \@fpsadddefault
594   \else
595     \ifx \@fps \@empty
596       \@fpsadddefault
597     \fi
598   \fi
599   \ifhmode
600     \@bsphack
601     \@floatpenalty -\@Mii
602   \else
603     \@floatpenalty-\@Miii
604   \fi
605   \ifinner
606     \@parmoderr\@floatpenalty\z@
607   \else
608     \@next\@currbox\@freelist
609     {%
610       \@tempcnta \sixt@@n
611       \expandafter \@tfor \expandafter \reserved@a
612       \expandafter :\expandafter =\@fps
613       \do
614       {%
615         \if \reserved@a h%
616           \ifodd \@tempcnta
617         \else
618           \advance \@tempcnta \@ne
619         \fi
620       \else\if \reserved@a t%
621         \@setfpsbit \tw@
622       \else\if \reserved@a b%
623         \@setfpsbit 4%
624       \else\if \reserved@a p%
625         \@setfpsbit 8%
626       \else\if \reserved@a !%
627         \ifnum \@tempcnta>15
628           \advance\@tempcnta -\sixt@@n\relax
629         \fi
630       \else
631         \@latex@error{Unknown float option ‘\reserved@a’}%
632         {Option ‘\reserved@a’ ignored and ‘p’ used.}%
633         \@setfpsbit 8%

```

```

634         \fi\fi\fi\fi\fi
635     }%
636     \@tempcntb \csname ftype@\@capttype \endcsname
637     \multiply \@tempcntb \xxxii
638     \advance \@tempcnta \@tempcntb
639     \global \count\@currbox \@tempcnta
640 }%
641 \@fltovf
642 \fi
643 \global \setbox\@currbox
644     \color@vbox
645     \normalcolor
646     \vbox \bgroup
647         \hsize\columnwidth
648         \@parboxrestore
649         \@floatboxreset
650 }
651 \def\@stpelt#1{\global\csname c@#1\endcsname \m@ne\stepcounter{#1}}
652 \EndIncludeInRelease
653 /fixltx2e

```