

# The zref package

Heiko Oberdiek\*

2022-03-08 v2.33

## Abstract

Package `zref` tries to get rid of the restriction in  $\text{\LaTeX}$ 's reference system that only two properties are supported. The package implements an extensible referencing system, where properties are handled in a more flexible way. It offers an interface for macro programmers for the access to the system and some applications that uses the new reference scheme.

## Contents

<b>1</b>	<b>Introduction</b>	<b>4</b>
1.1	Standard $\text{\LaTeX}$ behaviour	4
1.2	Basic idea	4
1.3	Interfaces	5
<b>2</b>	<b>Interface for programmers</b>	<b>5</b>
2.1	Entities	5
2.2	Property list	6
2.3	Property	6
2.4	Reference generation	7
2.5	Data extraction	7
2.6	Setup	8
2.7	Declared properties	9
2.8	Wrapper for advanced situations	10
2.9	Counter for unique names	10
<b>3</b>	<b>User interface</b>	<b>10</b>
3.1	Module <code>user</code>	10
3.2	Module <code>abspage</code>	11
3.3	Module <code>lastpage</code>	11
3.3.1	Tests for last page	12
3.3.2	Example	12
3.4	Module <code>thepage</code>	13
3.5	Module <code>nextpage</code>	13
3.5.1	Configuration	14
3.5.2	Example	14
3.6	Module <code>totpages</code>	14
3.7	Module <code>pagelayout</code>	15
3.8	Module <code>marks</code>	15
3.9	Module <code>runs</code>	16
3.10	Module <code>perpage</code>	16
3.11	Module <code>counter</code>	16
3.12	Module <code>titleref</code>	17
3.13	Module <code>savepos</code>	17
3.14	Module <code>abspos</code>	18

---

\*Please report any issues at <https://github.com/ho-tex/zref/issues>

3.15	Module <code>dotfill</code>	18
3.16	Module <code>env</code>	19
3.17	Module <code>xr</code>	19
3.18	Module <code>pageattr</code>	20
<b>4</b>	<b>ToDo</b>	<b>20</b>
<b>5</b>	<b>Example</b>	<b>20</b>
<b>6</b>	<b>Implementation</b>	<b>22</b>
6.1	Package <code>zref</code>	22
6.1.1	Identification	22
6.1.2	Load basic module	23
6.1.3	Process options	23
6.2	Module <code>base</code>	23
6.2.1	Prefixes	23
6.2.2	Identification	24
6.2.3	Utilities	24
6.2.4	Check for $\varepsilon$ -TeX	25
6.2.5	Auxiliary file stuff	25
6.2.6	Property lists	25
6.2.7	Properties	29
6.2.8	Reference generation	32
6.2.9	Reference querying and extracting	35
6.2.10	Compatibility with <code>babel</code>	38
6.2.11	Unique counter support	38
6.2.12	Utilities	39
6.2.13	Setup	39
6.3	Module <code>user</code>	40
6.4	Module <code>abspage</code>	41
6.5	Module <code>counter</code>	42
6.6	Module <code>lastpage</code>	42
6.7	Module <code>thepage</code>	43
6.8	Module <code>nextpage</code>	44
6.9	Module <code>totpages</code>	45
6.10	Module <code>pagelayout</code>	46
6.10.1	Define layout properties	46
6.11	Module <code>pageattr</code>	49
6.12	Module <code>marks</code>	52
6.13	Module <code>runs</code>	54
6.14	Module <code>perpage</code>	54
6.15	Module <code>titleref</code>	57
6.15.1	Implementation	57
6.15.2	User interface	58
6.15.3	Patches for section and caption commands	59
6.15.4	Environment <code>description</code>	60
6.15.5	Class <code>memoir</code>	60
6.15.6	Class <code>beamer</code>	60
6.15.7	Package <code>titlesec</code>	61
6.15.8	Package <code>longtable</code>	61
6.15.9	Package <code>listings</code>	61
6.15.10	Theorems	61
6.16	Module <code>xr</code>	62
6.17	Module <code>hyperref</code>	69
6.18	Module <code>savepos</code>	70
6.18.1	Identification	70
6.18.2	Availability	70
6.18.3	Setup	70

6.18.4	User macros	71
6.19	Module <code>abspos</code>	72
6.19.1	Identification	72
6.19.2	Media	74
6.19.3	Paper	76
6.19.4	Origin	76
6.19.5	Header	77
6.19.6	Body	78
6.19.7	Footer	79
6.19.8	Marginal notes	79
6.19.9	Stock paper	80
6.20	Module <code>dotfill</code>	80
6.21	Module <code>env</code>	81
<b>7</b>	<b>Installation</b>	<b>82</b>
7.1	Download	82
7.2	Bundle installation	82
7.3	Package installation	82
7.4	Refresh file name databases	83
7.5	Some details for the interested	83
<b>8</b>	<b>References</b>	<b>83</b>
<b>9</b>	<b>History</b>	<b>84</b>
[2006/02/20 v1.0]		84
[2006/05/03 v1.1]		84
[2006/05/25 v1.2]		84
[2006/09/08 v1.3]		84
[2007/01/23 v1.4]		84
[2007/02/18 v1.5]		84
[2007/04/06 v1.6]		84
[2007/04/17 v1.7]		84
[2007/04/22 v1.8]		84
[2007/05/02 v1.9]		84
[2007/05/06 v2.0]		84
[2007/05/28 v2.1]		85
[2008/09/21 v2.2]		85
[2008/10/01 v2.3]		85
[2009/08/07 v2.4]		85
[2009/12/06 v2.5]		85
[2009/12/07 v2.6]		85
[2009/12/08 v2.7]		85
[2010/03/26 v2.8]		85
[2010/03/29 v2.9]		85
[2010/04/08 v2.10]		85
[2010/04/15 v2.11]		86
[2010/04/17 v2.12]		86
[2010/04/19 v2.13]		86
[2010/04/22 v2.14]		86
[2010/04/23 v2.15]		86
[2010/04/28 v2.16]		86
[2010/05/01 v2.17]		87
[2010/05/13 v2.18]		87
[2010/10/22 v2.19]		87
[2011/02/12 v2.20]		87
[2011/03/18 v2.21]		87
[2011/10/05 v2.22]		87
[2011/12/05 v2.23]		87

[2012/04/04 v2.24]	87
[2016/05/16 v2.25]	87
[2016/05/21 v2.26]	88
[2018/11/21 v2.27]	88
[2019/11/29 v2.28]	88
[2020-03-03 v2.29]	88
[2020-03-04 v2.30]	88
[2020-05-28 v2.31]	88
[2020-07-03 v2.32]	88
[2022-03-08 v2.33]	88

<b>10 Index</b>	<b>88</b>
-----------------	-----------

## 1 Introduction

Standard L<sup>A</sup>T<sub>E</sub>X’s reference system with `\label`, `\ref`, and `\pageref` supports two properties, the appearance of the counter that is last incremented by `\refstepcounter` and the page with the `\label` command.

Unhappily L<sup>A</sup>T<sub>E</sub>X does not provide an interface for adding another properties. Packages such as `hyperref`, `nameref`, or `titleref` are forced to use ugly hacks to extend the reference system. These ugly hacks are one of the causes for `hyperref`’s difficulty regarding compatibility with other packages.

### 1.1 Standard L<sup>A</sup>T<sub>E</sub>X behaviour

References are created by the `\label` command:

```
\chapter{Second chapter}
\section{First section on page 7} % section 2.1
\label{myref}
```

Now L<sup>A</sup>T<sub>E</sub>X records the section number 2.1 and the page 7 in the reference. Internally the reference is a list with two entries:

```
\r@myref → {2.1}{7}
```

The length of the list is fixed in the L<sup>A</sup>T<sub>E</sub>X kernel. An interface for adding new properties is missing.

There are several tries to add new properties:

**hyperref** uses a list of five properties instead of the standard list with two entries. This causes many compatibility problems with L<sup>A</sup>T<sub>E</sub>X and other packages.

**titleref** stores its title data into the first entry in the list. L<sup>A</sup>T<sub>E</sub>X is happy because it does only see its list with two entries. The situation becomes more difficult, if more properties are added this way. Then the macros form a nested structure inside the first reference argument for the label. Expandable extractions will then become painful.

### 1.2 Basic idea

Some time ago Morten Høgholm sent me an experimental cross referencing mechanism as “expl3” code. His idea is:

```
\g_xref_mylabel_plist →
  \xref_dance_key{salsa}\xref_name_key{Morten}...
```

The entries have the following format:

```
\xref_{your key}_key{(some text)}
```

This approach is much more flexible:

- New properties can easily be added, just use a new key.
- The length of the list is not fixed. A reference can use a subset of the keys.
- The order of the entries does not matter.

Unhappily I am not familiar with the experimental code for L<sup>A</sup>T<sub>E</sub>X3 that will need some time before its first release. Thus I have implemented it as L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> package without disturbing the existing L<sup>A</sup>T<sub>E</sub>X reference system.

### 1.3 Interfaces

The package provides a generic *interface for programmers*. Commands of this interface are prefixed by `\zref@`.

Option `user` enables the *user interface*. Here the commands are prefixed by `\z` to avoid name clashes with existing macros.

Then the packages provides some *modules*. They are applications for the reference system and can also be considered as examples how to use the reference system.

The modules can be loaded as packages. The package name is prefixed with `zref-`, for example:

```
\RequirePackage{zref-abspage}
```

This is the preferred way if the package is loaded from within other packages to avoid option clashes.

As alternative package `zref` can be used and the modules are given as options:

```
\usepackage[perpage,user]{zref}
```

## 2 Interface for programmers

The user interface is described in the next section [3](#).

### 2.1 Entities

**Reference.** Internally a reference is a list of key value pairs:

```
\Z@R@myref → \default{2.1}\page{7}
```

The generic format of a entry is:

```
\Z@R@⟨refname⟩ → \⟨propname⟩{⟨value⟩}
```

`⟨refname⟩` is the name that denoted references (the name used in `\label` and `\ref`). `⟨propname⟩` is the name of the property or key. The property key macro is never executed, it is used in parameter text matching only.

**Property.** Because the name of a property is used in a macro name that must survive the `.aux` file, the name is restricted to letters and ‘@’.

**Property list.** Often references are used for special purposes. Thus it saves memory if just the properties are used in this reference that are necessary for its purpose.

Therefore this package uses the concept of *property lists*. A property list is a set of properties. The set of properties that is used by the default `\label` command is the *main property list*.

## 2.2 Property list

`exp` means that the implementation of the marked macro is expandable. `exp2` goes a step further and marks the macro expandable in exact two expansion steps.

`\zref@newlist {<listname>}`

Declares a new empty property list.

`\zref@addprop {<listname>} {<propname>}`  
`\zref@localaddprop {<listname>} {<propname>}`

Adds the property `<propname>` to the property list `<listname>`. The property and list must exist. The addition is global by `\zref@addprop` and limited to local scope by `\zref@localaddprop`. Between 2010/04/19 v2.13 and 2010/10/22 v2.19 a comma separated list of properties could be used as argument `<propname>`. Since 2010/10/22 v2.19 the addition of several properties at once is supported by `\zref@addprops`.

`\zref@addprops {<listname>} {<propname list>}`  
`\zref@localaddprops {<listname>} {<propname list>}`

These macros add a comma separated list of properties `<propname list>` to list `<listname>`. `\zref@addprops` works globally and `\zref@localaddprops` locally. Since 2010/10/22 v2.19.

`\zref@listexists {<listname>} {<then>}`

Executes `<then>` if the property list `<listname>` exists or raise an error otherwise.

`\zref@iflistundefinedexp {<listname>} {<then>} {<else>}`

Executes `<then>` if the list exists or `<else>` otherwise.

`\zref@iflistcontainsprop {<listname>} {<propname>} {<then>} {<else>}`

Executes `<then>` if the property `<propname>` is part of property list `<listname>` or otherwise it runs the `<else>` part.

## 2.3 Property

`\zref@newprop* {<propname>} [<default>] {<value>}`

This command declares and configures a new property with name `<propname>`.

In case of unknown references or the property does not exist in the reference, the `<default>` is used as value. If it is not specified here, a global default is used, see `\zref@setdefault`.

The correct values of some properties are not known immediately but at page shipout time. Prominent example is the page number. These properties are declared with the star form of the command.

`\zref@setcurrent {<propname>} {<value>}`

This sets the current value of the property `<propname>`. It is a generalization of

setting L<sup>A</sup>T<sub>E</sub>X's `\currentlabel`.

`\zref@getcurrentexp2 {⟨propname⟩}`

This returns the current value of the property `⟨propname⟩`. The value may not be correct, especially if the property is bound to a page (start form of `\zref@newprop`) and the right value is only known at shipout time (e.g. property 'page'). In case of errors (e.g. unknown property) the empty string is returned.

Since version 2010/04/22 v2.14 `\zref@getcurrent` supports `\zref@wrapper@unexpanded`.

`\zref@propexists {⟨propname⟩} {⟨then⟩}`

Calls `⟨then⟩` if the property `⟨propname⟩` is available or generates an error message otherwise.

`\zref@ifpropundefinedexp {⟨propname⟩} {⟨then⟩} {⟨else⟩}`

Calls `⟨then⟩` or `⟨else⟩` depending on the existence of property `⟨propname⟩`.

## 2.4 Reference generation

`\zref@label {⟨refname⟩}`

This works similar to `\label`. The reference `⟨refname⟩` is created and put into the `.aux` file with the properties of the main property list.

`\zref@labelbylist {⟨refname⟩} {⟨listname⟩}`

Same as `\zref@label` except that the properties are taken from the specified property list `⟨listname⟩`.

`\zref@labelbyprops {⟨refname⟩} {⟨propnameA⟩,⟨propnameB⟩,...}`

Same as `\zref@label` except that these properties are used that are given as comma separated list in the second argument.

`\zref@newlabel {⟨refname⟩} {...}`

This is the macro that is used in the `.aux` file. It is basically the same as `\newlabel` apart from the format of the data in the second argument.

## 2.5 Data extraction

`\zref@extractdefaultexp2 {⟨refname⟩} {⟨propname⟩} {⟨default⟩}`

This is the basic command that references the value of a property `⟨propname⟩` for the reference `⟨refname⟩`. In case of errors such as undefined reference the `⟨default⟩` is used instead.

`\zref@extractexp2 {⟨refname⟩} {⟨propname⟩}`

The command is an abbreviation for `\zref@extractdefault`. As default the default of the property is taken, otherwise the global default.

Example for page references:

```

 $\text{\LaTeX:}$   \pageref{foobar}
zref:      \zref@extract{foobar}{page}

```

Both `\zref@extract` and `\zref@extractdefault` are expandable. That means, these macros can directly be used in expandable calculations, see the example file. On the other side, babel's shorthands are not supported, there are no warnings in case of undefined references.

If an user interface doesn't need expandable macros then it can use `\zref@refused` and `\zref@wrapper@babel` for its user macros.

`\zref@refused {<refname>}`

This command is not expandable. It causes the warnings if the reference `<refname>` is not defined. Use the `\zref@extract` commands inside expandable contexts and mark their use outside by `\zref@refused`, see the example file.

`\zref@def@extract {<cmd>} {<refname>} {<propname>}`  
`\zref@def@extractdefault {<cmd>} {<refname>} {<propname>} {<default>}`

Both macros extract the property `<propname>` from the reference `<refname>` the same way as macros `\zref@extract` and `\zref@extractdefault`. The result is stored in macro `<cmd>`. Also `\zref@refused` is called to notify  $\text{\LaTeX}$  that the reference `<refname>` is used. Added in 2011/10/04 v2.22.

`\zref@ifrefundefinedexp {<refname>} {<then>} {<else>}`

Macro `\zref@ifrefundefined` calls arguments `<then>` or `<else>` dependent on the existence of the reference `<refname>`.

`\zifrefundefined {<refname>} {<then>} {<else>}`

Macro `\zifrefundefined` calls `\ref@refused` before executing `\zref@ifrefundefined`. Babel shorthands are supported in `<refname>`.

`\zref@ifrefcontainspropexp {<refname>} {<propname>} {<then>} {<else>}`

Test whether a reference provides a property.

## 2.6 Setup

`\zref@default`

Holds the global default for unknown values.

`\zref@setdefault {<value>}`

Sets the global default for unknown values. The global default is used, if a property does not specify an own default and the value for a property cannot be extracted. This can happen if the reference is unknown or the reference does not have the property.

`\zref@setmainlist {<value>}`

Sets the name of the main property list. The package sets and uses `main`.

## 2.7 Declared properties

Module	Property	Property list	Default
(base)	<code>default</code>	<code>main</code>	<code>&lt;empty&gt;</code>
	<code>page</code>	<code>main</code>	<code>&lt;empty&gt;</code>
<code>abspage</code>	<code>abspage</code>	<code>main</code>	<code>0</code>
<code>counter</code>	<code>counter</code>	<code>main</code>	<code>&lt;empty&gt;</code>
<code>hyperref</code>	<code>anchor</code>	<code>main</code>	<code>&lt;empty&gt;</code>
	<code>url</code>		<code>&lt;empty&gt;</code>
<code>pageattr</code>	<code>pdfpageattr</code>	<code>thepage</code>	<code>...</code>
	<code>pdfpagesattr</code>	<code>LastPage</code>	<code>...</code>
<code>pagelayout</code> <sup>1</sup>	<code>mag</code>	<code>thepage</code>	<code>\number\mag</code>
	<code>paperwidth</code>	<code>thepage</code>	<code>\number\paperwidth</code>
	<code>paperheight</code>	<code>thepage</code>	<code>\number\paperheight</code>
	<code>stockwidth</code>	<code>thepage</code>	<code>\number\stockwidth</code>
	<code>stockheight</code>	<code>thepage</code>	<code>\number\stockheight</code>
	<code>pdfpageheight</code>	<code>thepage</code>	<code>\number\pdfpageheight</code>
	<code>pdfpagewidth</code>	<code>thepage</code>	<code>\number\pdfpagewidth</code>
	<code>pdfhorigin</code>	<code>thepage</code>	<code>\number\pdfhorigin</code>
	<code>pdfvorigin</code>	<code>thepage</code>	<code>\number\pdfvorigin</code>
	<code>hoffset</code>	<code>thepage</code>	<code>\number\hoffset</code>
	<code>voffset</code>	<code>thepage</code>	<code>\number\voffset</code>
	<code>topmargin</code>	<code>thepage</code>	<code>\number\topmargin</code>
	<code>oddsidemargin</code>	<code>thepage</code>	<code>\number\oddsidemargin</code>
	<code>evensidemargin</code>	<code>thepage</code>	<code>\number\evensidemargin</code>
	<code>textwidth</code>	<code>thepage</code>	<code>\number\textwidth</code>
	<code>textheight</code>	<code>thepage</code>	<code>\number\textheight</code>
	<code>headheight</code>	<code>thepage</code>	<code>\number\headheight</code>
	<code>headsep</code>	<code>thepage</code>	<code>\number\headsep</code>
	<code>footskip</code>	<code>thepage</code>	<code>\number\footskip</code>
	<code>marginparwidth</code>	<code>thepage</code>	<code>\number\marginparwidth</code>
	<code>marginparsep</code>	<code>thepage</code>	<code>\number\marginparsep</code>
	<code>columnwidth</code>	<code>thepage</code>	<code>\number\columnwidth</code>
	<code>columnsep</code>	<code>thepage</code>	<code>\number\columnsep</code>
<code>perpage</code>	<code>pagevalue</code>	<code>perpage</code>	<code>0</code>
	<code>page</code>	<code>perpage</code>	<code>&lt;empty&gt;</code>
	<code>abspage</code>	<code>perpage</code>	<code>0</code>
<code>savepos</code>	<code>posx</code>	<code>savepos</code>	<code>0</code>
	<code>posy</code>	<code>savepos</code>	<code>0</code>
<code>titleref</code>	<code>title</code>	<code>main</code>	<code>&lt;empty&gt;</code>
<code>xr</code>	<code>anchor</code>		<code>&lt;empty&gt;</code>
	<code>externaldocument</code>		<code>&lt;empty&gt;</code>
	<code>theotype</code>		<code>&lt;empty&gt;</code>
	<code>title</code>		<code>&lt;empty&gt;</code>
	<code>url</code>		<code>&lt;empty&gt;</code>

<sup>1</sup>Module `pagelayout` only defines properties if the parameter exists.

## 2.8 Wrapper for advanced situations

`\zref@wrapper@babel {...} {\langle name \rangle}`

This macro helps to add shorthand support. The second argument is protected, then the code of the first argument is called with the protected name appended. Examples are in the sources.

`\zref@wrapper@immediate {...}`

There are situations where a label must be written instantly to the `.aux` file, for example after the last page. If the `\zlabel` or `\label` command is put inside this wrapper, immediate writing is enabled. See the implementation for module `lastpage` for an example of its use.

`\zref@wrapper@unexpanded {...}`

Assuming someone wants to extract a value for property `bar` and store the result in a macro `\foo` without traces of the expanding macros and without expanding the value. This (theoretical?) problem can be solved by this wrapper:

```
\zref@wrapper@unexpanded{%  
  \edef\foo{%  
    \zref@extract{someref}{bar}%  
  }%  
}
```

The `\edef` forces the expansion of `\zref@extract`, but the extraction of the value is prevented by the wrapper that uses  $\varepsilon$ -TeX' `\unexpanded` for this purpose. Supported macros are `\zref@extract`, `\zref@extractdefault` and since version 2010/04/22 v2.14 macro `\zref@getcurrent`.

## 2.9 Counter for unique names

Some modules (`titleref` and `dotfillmin`) need unique names for automatically generated label names.

`\zref@require@unique`

This command creates the unique counter `zref@unique` if the counter does not already exist.

`\thezref@unique`

This command is used to generate unique label names.

## 3 User interface

### 3.1 Module user

The user interface for this package and its modules is enabled by `zref`'s package option `user` or package `zref-user`. The names of user commands are prefixed by `z` in order to avoid name clashes with existing macros of the same functionality. Thus the package does not disturb the traditional reference scheme, both can be used together.

The syntax descriptions contain the following markers that are intended as hints for programmers:

<code>babel</code>	Babel shorthands are allowed.
<code>robust</code>	Robust macro.
<code>exp</code>	Expandable version: <ul style="list-style-type: none"> <li>• robust, unless the extracted values are fragile,</li> <li>• no babel shorthand support.</li> </ul>
<code>exp2</code>	Expandable like <code>exp</code> and: <ul style="list-style-type: none"> <li>• expandable in exact two steps.</li> </ul>

The basic user interface of the package without modules are commands that mimic the standard L<sup>A</sup>T<sub>E</sub>X behaviour of `\label`, `\ref`, and `\pageref`:

`\zlabel {⟨refname⟩}^babel`

Similar to `\label`. It generates a label with name `⟨refname⟩` in the new reference scheme.

`\zref [⟨propname⟩] {⟨refname⟩}^babel`

Without optional argument similar to `\ref`, it returns the default reference property. This property is named `default`:

$$\text{\zref}\{x\} \equiv \text{\zref}[\text{default}]\{x\}$$

`\zpageref {⟨refname⟩}^babel`

Convenience macro, similar to `\pageref`.

$$\text{\zpageref}\{x\} \equiv \text{\zref}[\text{page}]\{x\}$$

`\zrefused {⟨refname⟩}^babel`

Some of the user commands in the modules are expandable. The use of such commands do not cause any undefined reference warnings, because inside of expandable contexts this is not possible. However, if there is a place outside of expandable contexts, `\refused` is strongly recommended. The reference `⟨refname⟩` is marked as used, undefined ones will generate warnings.

## 3.2 Module `abspage`

With the help of package `atbegshi` a new counter `abspage` with absolute page numbers is provided. For technical and historical reasons the counter itself is zero based: if you use it directly on the first page, e.g with `\arabic{abspage}` you will get 0 as value. When using `\zref` the first page will be page 1 as expected. Also a new property `abspage` is defined and added to the main property list. Thus you can reference the absolute page number:

```
Section \zref{foo} is on page \zpageref{foo}.
This is page \zref[abspage]{foo}
of \zref[abspage]{LastPage}.
```

The example also makes use of module `lastpage`.

## 3.3 Module `lastpage`

Provides the functionality of package `lastpage` [3] in the new reference scheme. The label `LastPage` is put at the end of the document. You can refer the last page number with:

`\zref@extract{LastPage}{page} (+ \zref@refused{LastPage})`

or

`\zpageref{LastPage}` (module user)

Since version 2008/10/01 v2.3 the module defines the list `LastPage`. In addition to the properties of the main list label `LastPage` also stores the properties of this list `LastPage`. The default of this list is empty. The list can be used by the user to add additional properties for label `LastPage`.

### 3.3.1 Tests for last page

Since version 2010/03/26 v2.8 the macros `\zref@iflastpage` and `\ziflastpage` were added. They test the reference, whether it is a reference of the last page.

`\zref@iflastpageexp {<refname>} {<then>} {<else>}`

Macro `\zref@iflastpage` compares the references `<refname>` with `<LastPage>`. Basis of the comparison is the value of property `abspage`, because the values are different for different pages. This is not ensured by property `page`. Therefore module `abspage` is loaded by module `lastpage`. If both values of property `abspage` are present and match, then `<then>` is executed, otherwise code `<else>` is called. If one or both references are undefined or lack the property `abspage`, then `<else>` is executed.

Macro `\zref@iflastpage` is expandable, therefore `\zref@refused` should be called on `<refname>` and `<LastPage>`.

`\ziflastpage {<refname>} {<then>} {<else>}`

Macro `\ziflastpage` has the same function as `\zref@iflastpage`, but adds support for babel shorthands in `<refname>` and calls `\zref@refused`. However macro `\ziflastpage` is not expandable.

### 3.3.2 Example

```

1 <*example-lastpage>
2 %<<END_EXAMPLE
3 \NeedsTeXFormat{LaTeX2e}
4 \documentclass{report}
5
6 \newcounter{foo}
7 \renewcommand*{\thefoo}{\Alph{foo}}
8
9 \usepackage{zref-lastpage,zref-user}[2019/11/29]
10
11 \makeatletter
12 \zref@newprop{thefoo}{\thefoo}
13 \zref@newprop{valuefoo}{\the\value{foo}}
14 \zref@newprop{chapter}{\thechapter}
15 \zref@addprops{LastPage}{thefoo,valuefoo,chapter}
16 \makeatother
17
18 \newcommand*{\foo}{%
19   \stepcounter{foo}%
20   [Current foo: \thefoo]%
21 }
22
23 \begin{document}
```

```

24 \chapter{First chapter}
25 Last page is \zref{LastPage}.\
26 Last chapter is \zref[chapter]{LastPage}.\
27 Last foo is \zref[thefoo]{LastPage}.\
28 Last value of foo is \zref[valuefoo]{LastPage}.\
29 \foo
30 \chapter{Second chapter}
31 \foo\foo\foo
32 \chapter{Last chapter}
33 \foo
34 \end{document}
35 %END_EXAMPLE
36 \example-lastpage

```

### 3.4 Module thepage

This module `thepage` loads module `abspage`, constructs a reference name using the absolute page number and remembers property `page`. Other properties can be added by adding them to the property list `thepage`.

`\zthepage {⟨absolute page number⟩}`

Macro `\zthepage` is basically a `\zpageref`. The reference name is yield by the `⟨absolute page number⟩`. If the reference is not defined, then the default for property `page` is used.

`\zref@thepage@nameexp {⟨absolute page number⟩}`

Macro `\zref@thepage@name` returns the internal reference name that is constructed using the `⟨absolute page number⟩`. The internal reference name should not be used directly, because it might change in future versions.

`\zref@thepageexp {⟨absolute page number⟩}`  
`\zref@thepage@refused {⟨absolute page number⟩}`

Macro `\zref@thepage` returns the page number (`\thepage`) of `⟨absolute page number⟩`. Because this macro is expandable, `\zref@thepage@refused` is used outside an expandable context to mark the reference as used.

### 3.5 Module nextpage

`\znexpage`

Macro `\znexpage` prints `\thepage` of the following page. It gets the current absolute page number by using a label. There are three cases for the next page:

1. The next page is not known yet because of undefined references. Then `\zunknownnextpagename` is used instead. The default for this macro is the default of property `page`.
2. This page is the last page. Then `\znonextpagename` is used. Its default is empty.
3. The next page is known, then `\thepage` of the next page is used (the value of property `page` of the next page).

### 3.5.1 Configuration

The behaviour can be configured by the following macros.

`\zunknownnextpagename`  
`\znonextpagename`

If the next page is not known or available, then `\znextpage` uses these name macros as default. `\zunknownnextpagename` is used in case of undefined references. Default is the value of property `page` of the next page (`\thepage`). Module `thepage` is used.

Macro `\znonextpagename` is used, if the next page does not exists. That means that the current page is last page. The default is empty.

`\znextpagesetup {<unknown>} {<no next>} {<next>}`

According to the case (see `\znextpage`) macro `\znextpage` calls an internal macro with an argument. The argument is either `\thepage` of the next page or one of `\zunknownnextpagename` or `\znonextpagename`. These internal macro can be changed by `\znextpagesetup`. It expects the definition texts for these three cases of a macro with one argument. The default is

`\znextpagesetup{#1}{#1}{#1}`

### 3.5.2 Example

```
37 <*example-nextpage>
38 %<<END_EXAMPLE
39 \documentclass{book}
40
41 \usepackage{zref-nextpage}[2019/11/29]
42 \znextpagesetup
43   {\thepage}% next page is unknown
44   {\thepage\ (#1)}% this page is last page
45   {\thepage\ $\rightarrow$ #1}% next page is known
46 \renewcommand*{\znonextpagename}{last page}
47
48 \usepackage{fancyhdr}
49 \pagestyle{fancy}
50 \fancyhf{}
51 \fancyhead[LE,RO]{\znextpage}
52 \fancypagestyle{plain}{%
53   \fancyhf{}%
54   \fancyhead[LE,RO]{\znextpage}%
55 }
56
57 \begin{document}
58 \frontmatter
59   \tableofcontents
60 \mainmatter
61   \chapter{Hello World}
62   \clearpage
63   \section{Last section}
64 \end{document}
65 %END_EXAMPLE
66 </example-nextpage>
```

## 3.6 Module `totpages`

For the total number of pages of a document you need to know the absolute page number of the last page. Both modules `abspage` and `lastpage` are necessary and automatically enabled.

`\ztotpagesexp`

Prints the total number of pages or 0 if this number is not yet known. It expands to an explicit number and can also be used even in expandable calculations (`\numexpr`) or counter assignments.

### 3.7 Module `pagelayout`

The module defines additional properties for each parameter of the page layout that is effective during page shipout. The value of length parameters is given in sp without the unit as plain number.

Some parameters are specific for a class (e.g. `stockwidth` and `stockheight` for class `memoir`) or the  $\text{\TeX}$  engine like `pdf $\text{\TeX}$` . If the parameter is not available, then the property will not be defined. The default value of the property is the current setting of the parameter.

The module `thepage` is loaded that generates a label for each page. The properties of module `pagelayout` are added to the property list `thepage` of module `thepage`.

List of properties:

parameter	property	remarks
<code>\mag</code>	<code>mag</code>	
<code>\paperwidth</code>	<code>paperwidth</code>	
<code>\paperheight</code>	<code>paperheight</code>	
<code>\stockwidth</code>	<code>stockwidth</code>	class <code>memoir</code>
<code>\stockheight</code>	<code>stockheight</code>	class <code>memoir</code>
<code>\pdfpagewidth</code>	<code>pdfpagewidth</code>	<code>pdf<math>\text{\TeX}</math></code> , <code>Lua<math>\text{\TeX}</math></code>
<code>\pdfpageheight</code>	<code>pdfpageheight</code>	<code>pdf<math>\text{\TeX}</math></code> , <code>Lua<math>\text{\TeX}</math></code>
<code>\pdfhorigin</code>	<code>pdfhorigin</code>	<code>pdf<math>\text{\TeX}</math></code> , <code>Lua<math>\text{\TeX}</math></code>
<code>\pdfvorigin</code>	<code>pdfvorigin</code>	<code>pdf<math>\text{\TeX}</math></code> , <code>Lua<math>\text{\TeX}</math></code>
<code>\hoffset</code>	<code>hoffset</code>	
<code>\voffset</code>	<code>voffset</code>	
<code>\topmargin</code>	<code>topmargin</code>	
<code>\oddsidemargin</code>	<code>oddsidemargin</code>	
<code>\evensidemargin</code>	<code>evensidemargin</code>	
<code>\textwidth</code>	<code>textwidth</code>	
<code>\textheight</code>	<code>textheight</code>	
<code>\headheight</code>	<code>headheight</code>	
<code>\headsep</code>	<code>headsep</code>	
<code>\footskip</code>	<code>footskip</code>	
<code>\marginparwidth</code>	<code>marginparwidth</code>	
<code>\marginparsep</code>	<code>marginparsep</code>	
<code>\columnwidth</code>	<code>columnwidth</code>	
<code>\columnsep</code>	<code>columnsep</code>	

`\zlistpagelayout`

At the end of document the page layout parameter for each page are printed into the `.log` file if macro `\zlistpagelayout` is called before `\end{document}` (preamble is a good place).

### 3.8 Module `marks`

ToDo.

### 3.9 Module runs

Module `runs` counts the  $\text{\LaTeX}$  runs since last `.aux` file creation and prints the number in the `.log` file.

`\zrunsexp`

Prints the the total number of  $\text{\LaTeX}$  runs including the current one. It expands to an explicit number. Before `\begin{document}` the value is zero meaning the `.aux` file is not read yet. If a previous `.aux` file exists, the value found there increased by one is the new number. Otherwise `\zruns` is set to one.  $\text{\LaTeX}$  runs where the `.aux` files are not rewritten are not counted (see `\nofiles`).

### 3.10 Module perpage

With `\@addtoreset` or `\numberwithin` a counter can be reset if another counter is incremented. This do not work well if the other counter is the page counter. The page counter is incremented in the output routine that is often called asynchronous somewhere on the next page. A reference mechanism costs at least two  $\text{\LaTeX}$  runs, but ensures correct page counter values.

`\zmakeperpage [<reset>] {<counter>}`

At the of a new page counter *<counter>* starts counting with value *<reset>* (default is 1). The macro has the same syntax and semantics as `\MakePerPage` of package `perpage` [5]. Also `perpage` of package `footmisc` [1] can easily be simulated by

```
\zmakeperpage{footnote} % \usepackage[perpage]{footmisc}
```

If footnote symbols are used, some people dislike the first symbol †. It can easily be skipped:

```
\zmakeperpage[2]{footnote}
```

`\thezpage`  
counter `zpage`

If the formatted counter value of the counter that is reset at a new page contains the page value, then you can use `\thezpage`, the page number of the current page. Or counter `zpage` can be used, if the page number should be formatted differently from the current page number. Example:

```
\newcounter{foobar}  
\zmakeperpage{foobar}  
\renewcommand*{\thefoobar}{\thezpage-\arabic{foobar}}  
% or  
\renewcommand*{\thefoobar}{\roman{zpage}-\arabic{foobar}}
```

`\zunmakeperpage {<counter>}`

The reset mechanism for this counter is deactivated.

### 3.11 Module counter

This option just add the property `counter` to the main property list. The property stores the counter name, that was responsible for the reference. This is the property `hyperref`'s `\autoref` feature uses. Thus this property `counter` may be useful for a reimplementaion of the `autoref` feature, see the section 4 with the `todo` list.

### 3.12 Module **titleref**

This option makes section and caption titles available to the reference system similar to packages `titleref` or `nameref`.

`\ztitleref {⟨refname⟩}^babel`

Print the section or caption title of reference `⟨refname⟩`, similar to `\nameref` or `\titleref`.

`\ztitlerefsetup {key1=value1, key2=value2, ...}`

This command allows to configure the behaviour of module `titleref`. The following keys are available:

`title=⟨value⟩`

Sets the current title.

`stripperperiod=true|false`

Follow package `nameref` that removes a last period. Default: `true`.

`expand=true|false`

Package `\titleref` expands the title first. This way garbage and dangerous commands can be removed, e.g. `\label`, `\index...`. See implementation section for more details. Default is `false`.

`cleanup={...}`

Hook to add own cleanup code, if method `expand` is used. See implementation section for more details.

### 3.13 Module **savepos**

This option supports a feature that pdf $\TeX$  provides (and X $\TeX$ ). pdf $\TeX$  is able to tell the current position on the page. The page position is not instantly known. First the page must be constructed by  $\TeX$ 's asynchronous output routine. Thus the time where the position is known is the page shipout time. Thus a reference system where the information is recorded in the first run and made available for use in the second run comes in handy.

`\zsavepos {⟨refname⟩}`

It generates a reference with name `⟨refname⟩`. The reference stores the location where `\zsavepos` is executed in properties `posx` and `posy`.

`\zsaveposx {⟨refname⟩}`  
`\zsaveposy {⟨refname⟩}`

Same as `\zsavepos` except that only the x or y component of the position is stored. Since 2011/12/05 v2.23.

`\zposxexp {⟨refname⟩}`  
`\zposyexp {⟨refname⟩}`

Get the position as number. Unit is sp. Horizontal positions by `\zposx` increase from left to right. Vertical positions by `\zposy` from bottom to top.

Do not rely on absolute page numbers. Because of problems with the origin the numbers may differ in DVI or PDF mode of pdf $\TeX$ . Therefore work with relative values by comparisons.

Both `\zposx` and `\zposy` are expandable and can be used inside calculations (`\setcounter`, `\addtocounter`, package `calc`, `\numexpr`). However this property prevents from notifying L<sup>A</sup>T<sub>E</sub>X that the reference is actually used (the notifying is not expandable). Therefore you should mark the reference as used by `\zrefused`.

This module uses pdfT<sub>E</sub>X's `\pdfsavepos`, `\pdflastxpos`, and `\pdflastypos`. They are available in PDF mode and since version 1.40.0 also in DVI mode.

#### `\zref@savepos`

Macro `\zref@savepos` performs the first part of `\zsavepos` by calling `\pdfsavepos` (if `.aux` files are writable).

Thus `\zsavepos` is basically `\zref@savepos` followed by `\zref@labelbylist{<refname>}{savepos}`. If TeX<sub>E</sub> state is detected and enabled, `\savepos` also adds `\zref@savepos` at the end to support `\beginR` where the whatits are processed in reverse order. The property list `savepos` contains the properties `posx` and `posy`.

### 3.14 Module **abspos**

Module `abspos` allows to get various values of the page layout. There is no user command, only a number of internal commands. For example:

```
\zref@absposx{<label>}{<value>}{<position>}
\zref@absposy{<label>}{<value>}{<position>}
```

The return value is like in the module `savepos` a number representing a length in sp. The length are measured from the bottom left of the page.

`<label>` is a label set with `\zlabel` or `\zsavepos` that allows to retrieve the absolute page number.

`<position>` is for the x-command one of `left`, `right` or `center`. For the y-command it is one of `top`, `bottom`, `center`.

The possible content of `<value>` can be seen in the following table. Be aware that the code makes some assumptions which are perhaps not always true – for example that the left of the head is identical to the left of the body.

value	axis	comments
media	x	left=0, right= <code>\pdfpagewidth</code>
paper	x	left=0, right= <code>\paperwidth</code>
stock	x	derived from paper
media	y	bottom=0, top= <code>\pdfpageheight</code>
paper	y	top= <code>\pdfpageheight</code> , bottom=top- <code>\paperheight</code>
stock	y	top derived from paper
head	x	calculated with <code>hoffset</code> , <code>horigin</code> , etc
head	y	calculated
body	x	= head value
body	y	= head bottom - <code>\headsep</code>
foot	x	= head
foot	y	calculated from body bottom and <code>\footskip</code>
marginpar	x	different on odd/even pages!
marginpar	y	= body

### 3.15 Module **dotfill**

#### `\zdotfill`

This package provides the command `\zdotfill` that works similar to `\dotfill`, but can be configured. Especially it suppresses the dots if a minimum number of dots cannot be set.

`\zdotfillsetup {key1=value1, key2=value2, ...}`

This command allows to configure the behaviour of `\zdotfill`. The following keys are available:

**min**=*<count value>*

If the actual number of dots are smaller than *<count value>*, then the dots are suppressed. Default: 2.

**unit**=*<dimen value>*

The width of a dot unit is given by *<dimen value>*. Default: 0.44em (same as the unit in `\dotfill`).

**dot**=*<value>*

The dot itself is given by *<value>*. Default: . (dot, same as the dot in `\dotfill`).

### 3.16 Module `env`

This module defines two properties `envname` and `envline`. They remember the name of the environment and the line number at the start of the environment.

### 3.17 Module `xr`

This package provides the functionality of package `xr`, see [8]. It also supports the syntax of `xr-hyper`.

`\zexternaldocument * [<prefix>] babel {<external document>} [<url>]`

See `\externaldocument` for a description of this option. The found labels also get a property `externaldocument` that remembers *<external document>*. The standard reference scheme and the scheme of this package use different name spaces for reference names. If the external document uses both systems. Then one import statement would put the names in one namespace and probably causing problems with multiple references of the same name. Thus the star form only looks for `\newlabel` in the `.aux` files, whereas without star only `\zref@newlabels` are used.

In the star form it tries to detect labels from `hyperref`, `titleref`, and `ntheorem`. If such an extended property from the packages before cannot be found or are empty, they are not included in the imported reference.

Warnings are given if a reference name is already in use and the item is ignored. Unknown properties will automatically be declared.

If the external references contain `anchor` properties, then we need also a url to be able to address the external file. As default the filename is taken with a default extension.

`\zxrsetup {key1=value1, key2=value2, ...}`

The following setup options are available:

**ext**: It sets the default extension.

**tozreflabel**: Boolean option. The found references are imported as zref labels. This is enabled by default.

**totxlabel**: Boolean option. The found references are imported as L<sup>A</sup>T<sub>E</sub>X labels. Packages `nameref`, `titleref` and class `memoir` are supported.

**urluse:** Boolean option. If enabled, then a URL is stored in a macro and the macro is put in property ‘urluse’. The URL is not put in property ‘url’. The purpose is to save T<sub>E</sub>X memory.

**verbose:** Boolean option. List the imported labels in the .log file. Default is false.

\zref@xr@ext

If the `\url` is not specified in `\zref@externaldocument`, then the url will be constructed with the file name and this macro as extension. `\XR@ext` is used if `hyperref` is loaded, otherwise `pdf`.

### 3.18 Module `pageattr`

This module allows to recover the content of the register `\pdfpageattr` and `\pdfpagesattr` in `pdftex` and the equivalent register in `luatex`. There is no user command. Programmer commands are

```
\zref@pdfpageattr{<absolute page number>}
\zref@pdfpagesattr{<absolute page number>}
```

## 4 ToDo

Among other things the following issues are left for future work:

- Other applications: `autoref`, `hyperref`, ...

## 5 Example

```
67 <*example>
68 \documentclass{book}
69
70 \usepackage[ngerman]{babel}%
71
72 \usepackage[savepos,totpages,titleref,dotfill,counter,user]{zref}
73
```

Chapters are wrapped inside `\ChapterStart` and `\ChapterStop`. The first argument #1 of `\ChapterStart` is used to form a label id `chap:#1`. At the end of the chapter another label is set by `\zref@wrapper@immediate`, because otherwise at the end of document a deferred write would not be written, because there is no page for shipout.

Also this example shows how chapter titles can be recorded. A new property `chaptitle` is declared and added to the main property list. In `\ChapterStart` the current value of the property is updated.

```
74 \makeatletter
75 \zref@newprop{chaptitle}{}
76 \zref@addprop{main}{chaptitle}
77
78 \newcommand*{\ChapterStart}[2]{%
79   \cleardoublepage
80   \def\current@chapid{#1}%
81   \zref@setcurrent{chaptitle}{#2}%
82   \chapter{#2}%
83   \zlabel{chap:#1}%
84 }
85 \newcommand*{\ChapterStop}{%
```

```

86 \cleardoublepage
87 \zref@wrapper@immediate{%
88   \zref@labelbyprops{chapend:\current@chapid}{abspage}%
89 }%
90 }

```

`\ChapterPages` calculates and returns the number of pages of the referenced chapter.

```

91 \newcommand*{\ChapterPages}[1]{%
92   \zrefused{chap:#1}%
93   \zrefused{chapend:#1}%
94   \number\numexpr
95     \zref@extract{chapend:#1}{abspage}%
96     -\zref@extract{chap:#1}{abspage}%
97     +1\relax
98 }
99 \makeatother
100 \begin{document}

```

As exception we use `\makeatletter` here, because this is just an example file that also should show some of programmer's interface.

```

101 \makeatletter
102
103 \frontmatter
104 \zlabel{documentstart}
105
106 \begin{itemize}
107 \item
108   The frontmatter part has
109   \number\numexpr\zref@extract{chap:first}{abspage}-1\relax
110   ~pages.
111 \item
112   Chapter \zref{chap:first} has \ChapterPages{first} page(s).
113 \item
114   Section \zref{hello} is on the
115   \ifcase\numexpr
116     \zref@extractdefault{hello}{page}{0}%
117     -\zref@extractdefault{chap:first}{page}{0}%
118     +1\relax
119     ??\or first\or second\or third\or forth\fi
120   ~page inside its chapter.
121 \item
122   The document has
123   \zref[abspage]{LastPage} pages.
124   This number is \ifodd\ztotpages odd\else even\fi.
125 \item
126   The last page is labeled with \zpageref{LastPage}.
127 \item
128   The title of chapter \zref{chap:next} %
129   is ‘‘\zref[chaptitle]{chap:next}’’.
130 \end{itemize}
131
132 \tableofcontents
133
134 \mainmatter
135 \ChapterStart{first}{First chapter}
136

```

The user level commands should protect babel shorthands where possible. On the other side, expandable extracting macros are useful in calculations, see above the examples with `\numexpr`.

```

137 \section{Test}
138 \zlabel{a"o}
139 Section \zref{a"o} on page

```

```

140 \zref@wrapper@babel\zref@extract{a"o}{page}.
141
142 Text.
143 \newpage
144
145 \section{Hello World}
146 \zlabel{hello}
147
148 \ChapterStop
149
150 \ChapterStart{next}{Next chapter with \emph{umlauts}: "a"o"u"s}
151

```

Here an example follows that makes use of pdfTeX's "savepos" feature. The position on the page is not known before the page is constructed and shipped out. Therefore the position is stored in references and are available for calculations in the next L<sup>A</sup>T<sub>E</sub>X compile run.

```

152 The width of the first column is
153 \the\dimexpr \zposx{secondcol}sp - \zposx{firstcol}sp\relax,\,
154 the height difference of the two baselines is
155 \the\dimexpr \zposy{firstcol}sp - \zposy{secondline}sp\relax:\,
156 \begin{tabular}{ll}
157 \zsavepos{firstcol}Hello&\zsavepos{secondcol}World\,
158 \zsavepos{secondline}Second line&foobar\,
159 \end{tabular}
160

```

With \zrefused L<sup>A</sup>T<sub>E</sub>X is notified, if the references are not yet available and L<sup>A</sup>T<sub>E</sub>X can generate the rerun hint.

```

161 \zrefused{firstcol}
162 \zrefused{secondcol}
163 \zrefused{secondline}
164
165 \ChapterStop
Test for module \dotfill.
166 \ChapterStart{dotfill}{Test for dotfill feature}
167 \newcommand*{\dfptest}[1]{%
168   #1&
169   [\makebox[#1]]{\dotfill}]&
170   [\makebox[#1]]{\zdotfill}]\,
171 }
172 \begin{tabular}{rll}
173 & [\verb|\dotfill|] & [\verb|\zdotfill|]\,
174 \dfptest{0.43em}
175 \dfptest{0.44em}
176 \dfptest{0.45em}
177 \dfptest{0.87em}
178 \dfptest{0.88em}
179 \dfptest{0.89em}
180 \dfptest{1.31em}
181 \dfptest{1.32em}
182 \dfptest{1.33em}
183 \end{tabular}
184 \ChapterStop
185 \end{document}
186 \example

```

## 6 Implementation

### 6.1 Package zref

#### 6.1.1 Identification

```

187 <*package>
188 \NeedsTeXFormat{LaTeX2e}
189 \ProvidesPackage{zref}
190 [2022-03-08 v2.33 A new reference scheme for LaTeX (H0)]%

```

### 6.1.2 Load basic module

```
191 \RequirePackage{zref-base}[2019/11/29]
```

Abort package loading if zref-base could not be loaded successfully.

```
192 \@ifundefined{ZREF@base@ok}{\endinput}{}%
```

### 6.1.3 Process options

Known modules are loaded and the release date is checked.

```

193 \def\ZREF@temp#1{%
194   \DeclareOption{#1}{%
195     \AtEndOfPackage{%
196       \RequirePackage{zref-#1}[2019/11/29]%
197     }%
198   }%
199 }
200 \ZREF@temp{abspage}
201 \ZREF@temp{counter}
202 \ZREF@temp{dotfill}
203 \ZREF@temp{hyperref}
204 \ZREF@temp{lastpage}
205 \ZREF@temp{marks}
206 \ZREF@temp{nextpage}
207 \ZREF@temp{pageattr}
208 \ZREF@temp{pagelayout}
209 \ZREF@temp{perpage}
210 \ZREF@temp{runs}
211 \ZREF@temp{savepos}
212 \ZREF@temp{thepage}
213 \ZREF@temp{titleref}
214 \ZREF@temp{totpages}
215 \ZREF@temp{user}
216 \ZREF@temp{xr}

217 \ProcessOptions\relax
218 </package>

```

## 6.2 Module base

### 6.2.1 Prefixes

This package uses the following prefixes for macro names:

**\zref@:** Macros of the programmer’s interface.

**\ZREF@:** Internal macros.

**\Z@L@listname:** The properties of the list *<listname>*.

**\Z@D@propname:** The default value for property *<propname>*.

**\Z@E@propname:** Extract function for property *<propname>*.

**\Z@X@propname:** Information whether a property value for property *<propname>* is expanded immediately or at shipout time.

**\Z@C@propname:** Current value of the property *<propname>*.

**\Z@R@labelname:** Data for reference *<labelname>*.

**\ZREF@org@:** Original versions of patched commands.

`\z:` For macros in user land, defined if module `user` is set.

The following family names are used for keys defined according to the `keyval` package:

`ZREF@TR:` Setup for module `titleref`.

### 6.2.2 Identification

```
219 <*base>
220 \NeedsTeXFormat{LaTeX2e}
221 \ProvidesPackage{zref-base}%
222 [2022-03-08 v2.33 Module base for zref (H0)]%
```

### 6.2.3 Utilities

```
223 \providecommand\IfFormatAtLeastTF{\@ifl@t@r\fmtversion}
224 \RequirePackage{ltxcmds}[2010/12/02]
225 \RequirePackage{infwarerr}[2010/04/08]
226 \RequirePackage{kvsetkeys}[2010/03/01]
227 \RequirePackage{kvdefinekeys}[2010/03/01]
228 \RequirePackage{pdftexcmds}[2010/04/01]
```

`\ZREF@name` Several times the package name is used, thus we store it in `\ZREF@name`.

```
229 \def\ZREF@name{zref}

230 \ltx@ifundefined{protected}{%
231   \RequirePackage{makerobust}[2006/03/18]%
```

`\ZREF@Robust`

```
232   \def\ZREF@Robust#1#2{%
233     \def\ZREF@temp{\MakeRobustcommand#2}%
234     \afterassignment\ZREF@temp
235     #1#2%
236   }%
237 }{%
```

`\ZREF@Robust`

```
238   \def\ZREF@Robust#1{%
239     \protected#1%
240   }%
241 }
```

`\ZREF@ifDefinable`

```
242 \def\ZREF@ifDefinable#1#2#3{%
243   \@ifdefinable{#1}{%
244     \ZREF@Robust{#2}#1#3%
245   }%
246 }
```

`\ZREF@UpdatePdfTeX` `\ZREF@UpdatePdfTeX` is used as help message text in error messages.

```
247 \def\ZREF@UpdatePdfTeX{Update pdfTeX.}
```

`\ifZREF@found` The following switch is used in list processing.

```
248 \newif\ifZREF@found
```

`\ZREF@patch` Macro `\ZREF@patch` first checks the existence of the command and safes it.

```
249 \def\ZREF@patch#1{%
250   \ltx@ifundefined{#1}{%
251     \ltx@gobble
252   }{%
253     \expandafter\let\csname ZREF@org@#1\expandafter\endcsname
254     \csname #1\endcsname
255     \ltx@firstofone
256   }%
257 }
```

### 6.2.4 Check for $\varepsilon$ -TeX

The use of  $\varepsilon$ -TeX should be standard nowadays for L<sup>A</sup>T<sub>E</sub>X. We test for  $\varepsilon$ -TeX in order to use its features later.

```

258 \ltx@ifundefined{eTeXversion}{%
259   \PackageError{ZREF@name}{%
260     Missing support for eTeX; package is abandoned%
261   }{%
262     Use a TeX compiler that support eTeX and enable eTeX %
263     in the format.%
264   }%
265   \endinput
266 }{}%

267 \RequirePackage{etexcmds}[2007/09/09]
268 \ifetex@unexpanded
269 \else
270   \PackageError{ZREF@name}{%
271     Missing e-TeX's \string\unexpanded.\MessageBreak
272     Add \string\RequirePackage\string{etexcmds\string} before %
273     \string\documentclass%
274   }{%
275     Probably you are using some package (e.g. ConTeXt) that %
276     redefines \string\unexpanded%
277   }%
278   \expandafter\endinput
279 \fi

```

### 6.2.5 Auxiliary file stuff

We are using some commands in the .aux files. However sometimes these auxiliary files are interpreted by L<sup>A</sup>T<sub>E</sub>X processes that haven't loaded this package (e.g. package xr). Therefore we provide dummy definitions.

```

280 \RequirePackage{auxhook}
281 \AddLineBeginAux{%
282   \string\providecommand\string\zref@newlabel[2]{}%
283 }

```

`\ZREF@RefPrefix`

```

284 \def\ZREF@RefPrefix{Z@R}

```

`\zref@newlabel` For the implementation of `\zref@newlabel` we call the same internal macro `\@newl@bel` that is used in `\newlabel`. Thus we have for free:

- `\Z@R@labelname` is defined.
- L<sup>A</sup>T<sub>E</sub>X's check for multiple references.
- L<sup>A</sup>T<sub>E</sub>X's check for changed references.

```

285 \ZREF@Robust\edef\zref@newlabel{%
286   \noexpand\@newl@bel{\ZREF@RefPrefix}%
287 }

```

### 6.2.6 Property lists

`\zref@newlist` Property lists are stored as list of property names enclosed in curly braces. `\zref@newlist` creates a new list as empty list. Assignments to property lists are global.

```

288 \ZREF@Robust\def\zref@newlist#1{%
289   \zref@iflistundefined{#1}{%
290     \@ifdefinable{Z@L@#1}{%
291       \global\expandafter\let\csname Z@L@#1\endcsname\ltx@empty

```

```

292     \PackageInfo\ZREF@name{New property list: #1}%
293   }%
294 }{%
295   \PackageError\ZREF@name{%
296     Property list ‘#1’ already exists%
297   }\@ehc
298 }%
299 }

```

`\zref@iflistundefined` `\zref@iflistundefined` checks the existence of the property list #1. If the property list is present, then #2 is executed and #3 otherwise.

```

300 \def\zref@iflistundefined#1{%
301   \ltx@ifundefined{Z@L@#1}%
302 }

```

`\zref@listexists` `\zref@listexists` only executes #2 if the property list #1 exists and raises an error message otherwise.

```

303 \ZREF@Robust\def\zref@listexists#1{%
304   \zref@iflistundefined{#1}{%
305     \PackageError\ZREF@name{%
306       Property list ‘#1’ does not exist%
307     }\@ehc
308   }%
309 }

```

`\zref@iflistcontainsprop` `\zref@iflistcontainsprop` checks, whether a property #2 is already present in a property list #1.

```

310 \ZREF@Robust\def\zref@iflistcontainsprop#1#2{%
311   \zref@iflistundefined{#1}{%
312     \ltx@secondoftwo
313   }{%
314     \begingroup\expandafter\endgroup
315     \expandafter\in@
316     \csname#2\expandafter\expandafter\expandafter\endcsname
317     \expandafter\expandafter\expandafter{\csname Z@L@#1\endcsname}%
318     \csname \ltx@ifin@ first\else second\fi oftwo\endcsname
319   }%
320 }

```

`\zref@listforloop`

```

321 \def\zref@listforloop#1#2{%
322   \zref@listexists{#1}{%
323     \expandafter\expandafter\expandafter\@tfor
324     \expandafter\expandafter\expandafter\zref@prop
325     \expandafter\expandafter\expandafter:%
326     \expandafter\expandafter\expandafter=%
327     \csname Z@L@#1\endcsname
328     \do{%
329       \begingroup
330       \escapechar=-1 %
331       \edef\x{\endgroup
332         \def\noexpand\zref@prop{%
333           \expandafter\string\zref@prop
334         }%
335       }%
336       \x
337       #2\zref@prop
338     }%
339   }%
340 }

```

`\zref@addprops` `\zref@addprop` adds the properties #2 to the property list #1, if the property is not already in the list. Otherwise a warning is given.

```

341 \ZREF@Robust\def\zref@addprops#1#2{%
342   \zref@listexists{#1}{%
343     \comma@parse{#2}{%
344       \zref@propexists\comma@entry{%
345         \zref@iflistcontainsprop{#1}\comma@entry{%
346           \PackageWarning\ZREF@name{%
347             Property '\comma@entry' is already in list '#1'%
348           }%
349         }{%
350           \begingroup\expandafter\endgroup
351           \expandafter\g@addto@macro
352           \csname Z@L@#1\expandafter\endcsname
353           \expandafter{\csname\comma@entry\endcsname}%
354         }%
355       }%
356     \ltx@gobble
357   }%
358 }%
359 }
```

`\zref@addprop` `\zref@addprop` adds the property #2 to the property list #1, if the property is not already in the list. Otherwise a warning is given.

```

360 \ZREF@Robust\def\zref@addprop#1#2{%
361   \zref@listexists{#1}{%
362     \zref@propexists{#2}{%
363       \zref@iflistcontainsprop{#1}{#2}{%
364         \PackageWarning\ZREF@name{%
365           Property '#2' is already in list '#1'%
366         }%
367       }{%
368         \begingroup\expandafter\endgroup
369         \expandafter\g@addto@macro
370         \csname Z@L@#1\expandafter\endcsname
371         \expandafter{\csname#2\endcsname}%
372       }%
373     }%
374   }%
375 }
```

`\zref@localaddprops`

```

376 \ZREF@Robust\def\zref@localaddprops#1#2{%
377   \zref@listexists{#1}{%
378     \comma@parse{#2}{%
379       \zref@propexists\comma@entry{%
380         \zref@iflistcontainsprop{#1}\comma@entry{%
381           \PackageWarning\ZREF@name{%
382             Property '\comma@entry' is already in list '#1'%
383           }%
384         }{%
385           \begingroup\expandafter\endgroup
386           \expandafter\ltx@LocalAppendToMacro
387           \csname Z@L@#1\expandafter\endcsname
388           \expandafter{\csname\comma@entry\endcsname}%
389         }%
390       }%
391     \ltx@gobble
392   }%
393 }%
394 }
```

```

\zref@localaddprop
395 \ZREF@Robust\def\zref@localaddprop#1#2{%
396   \zref@listexists{#1}{%
397     \zref@propexists{#2}{%
398       \zref@iflistcontainsprop{#1}{#2}{%
399         \PackageWarning\ZREF@name{%
400           Property ‘#2’ is already in list ‘#1’%
401         }%
402       }%
403     \begingroup\expandafter\endgroup
404     \expandafter\ltx@LocalAppendToMacro
405     \csname Z@L@#1\expandafter\endcsname
406     \expandafter{\csname#2\endcsname}%
407   }%
408 }%
409 }%
410 }

411 \ltx@ifundefined{pdf@strcmp}{%

\zref@delprop
412 \ZREF@Robust\def\zref@delprop{%
413   \ZREF@delprop\gdef
414 }%

\zref@localdelprop
415 \ZREF@Robust\def\zref@localdelprop{%
416   \ZREF@delprop\def
417 }%

\ZREF@delprop
418 \def\ZREF@delprop#1#2#3{%
419   \zref@listexists{#2}{%
420     \begingroup
421     \escapechar=-1 %
422     \def\ZREF@param{#3}%
423     \@onelevel@sanitize\ZREF@param
424     \toks@{%
425       \expandafter\expandafter\expandafter\ZREF@@delprop
426       \csname Z@L@#2\endcsname!%
427     \expandafter\endgroup
428     \expandafter#1\csname Z@L@#2\expandafter\endcsname
429     \expandafter{%
430       \the\toks@
431     }%
432   }%
433 }%

\ZREF@@delprop
434 \def\ZREF@@delprop#1{%
435   \expandafter\ZREF@@@delprop\expandafter{\string#1}#1%
436 }%

\ZREF@@@delprop
437 \def\ZREF@@@delprop#1#2{%
438   \ifx#2!%
439   \else
440     \def\ZREF@temp{#1}%
441     \@onelevel@sanitize\ZREF@temp
442     \ifx\ZREF@param\ZREF@temp
443     \else
444       \toks@\expandafter{%

```

```

445         \the\expandafter\toks@\csname#1\endcsname
446     }%
447     \fi
448     \expandafter\ZREF@@delprop
449     \fi
450 }%

451 }{%

\zref@delprop
452 \ZREF@Robust\def\zref@delprop{%
453     \ZREF@delprop\xdef
454 }%

\zref@localdelprop
455 \ZREF@Robust\def\zref@localdelprop{%
456     \ZREF@delprop\edef
457 }%

\ZREF@delprop
458 \def\ZREF@delprop#1#2#3{%
459     \zref@listexists{#2}{%
460         \def\ZREF@param{#3}%
461         \edef\ZREF@SavedEscapechar{\the\escapechar}%
462         \escapechar=-1 %
463         \expandafter#1\csname Z@L@#2%
464         \expandafter\expandafter\expandafter\endcsname{%
465             \expandafter\expandafter\expandafter\ZREF@@delprop
466             \csname Z@L@#2\endcsname!%
467         }%
468         \escapechar=\ZREF@SavedEscapechar\relax
469     }%
470 }%

```

\ZREF@@delprop Caution: #1 might be an \if or similar token.

```

471 \def\ZREF@@delprop#1{%
472     \expandafter\ZREF@@@delprop\expandafter{\string#1}#1%
473 }%

```

\ZREF@@@delprop

```

474 \def\ZREF@@@delprop#1#2{%
475     \ifx#2!%
476     \else
477         \ifnum\pdf@strcmp{#1}{\ZREF@param}=\ltx@zero
478         \else
479             \expandafter\noexpand\csname#1\endcsname
480         \fi
481         \expandafter\ZREF@@delprop
482     \fi
483 }%

484 }

```

### 6.2.7 Properties

\zref@ifpropundefined \zref@ifpropundefined checks the existence of the property #1. If the property is present, then #2 is executed and #3 otherwise.

```

485 \def\zref@ifpropundefined#1{%
486     \ltx@ifundefined{Z@E@#1}%
487 }

```

`\zref@propexists` Some macros rely on the existence of a property. `\zref@propexists` only executes #2 if the property #1 exists and raises an error message otherwise.

```

488 \ZREF@Robust\def\zref@propexists#1{%
489   \zref@ifpropundefined{#1}{%
490     \PackageError\ZREF@name{%
491       Property ‘#1’ does not exist%
492     }\@ehc
493   }%
494 }

```

`\zref@newprop` A new property is declared by `\zref@newprop`, the property name  $\langle propname \rangle$  is given in #1. The property is created and configured. If the star form is given, then the expansion of the property value is delayed to page shipout time, when the reference is written to the .aux file.

`\Z@D@propname`: Stores the default value for this property.

`\Z@E@propname`: Extract function.

`\Z@X@propname`: Information whether the expansion of the property value is delayed to shipout time.

`\Z@C@propname`: Current value of the property.

```

495 \ZREF@Robust\def\zref@newprop{%
496   \@ifstar{%
497     \let\ZREF@X\noexpand
498     \ZREF@newprop
499   }{%
500     \let\ZREF@X\ltx@empty
501     \ZREF@newprop
502   }%
503 }

```

`\ZREF@newprop`

```

504 \def\ZREF@newprop#1{%
505   \edef\ZREF@P{#1}%
506   \@onelevel@sanitize\ZREF@P
507   \begingroup
508   \ifx\ZREF@P\ZREF@par
509     \PackageError\ZREF@name{%
510       Invalid property name ‘\ZREF@P’%
511     }{%
512       The property name ‘par’ is not allowed %
513       because of internal reasons.%
514       \MessageBreak
515       \@ehc
516     }%
517   \def\ZREF@@newprop[##1]##2{\endgroup}%
518   \else
519     \zref@ifpropundefined\ZREF@P{%
520       \endgroup
521       \PackageInfo\ZREF@name{%
522         New property: \ZREF@P
523       }%
524     }{%
525       \PackageError\ZREF@name{%
526         Property ‘\ZREF@P’ already exists%
527       }\@ehc
528     \def\ZREF@@newprop[##1]##2{\endgroup}%
529     }%
530   \fi
531   \@ifnextchar[\ZREF@@newprop{\ZREF@@newprop[\zref@default]}%
532 }

```

\ZREF@par

```
533 \def\ZREF@par{par}
534 \@onelevel@sanitize\ZREF@par
```

\ZREF@@newprop

```
535 \def\ZREF@@newprop[#1]{%
536   \global\@namedef{Z@D@\ZREF@P}{#1}%
537   \global\expandafter\let\csname Z@X@\ZREF@P\endcsname\ZREF@X
538   \begingroup\expandafter\endgroup
539   \expandafter\ZREF@@@newprop\csname\ZREF@P\endcsname
540   \expandafter\gdef\csname Z@C@\ZREF@P\endcsname{}%
541   \zref@setcurrent\ZREF@P
542 }
543 \def\ZREF@@@newprop#1{%
544   \expandafter
545   \gdef\csname Z@E@\ZREF@P\endcsname##1#1##2##3\ZREF@nil{##2}%
546 }
```

\zref@showprop

```
547 \ZREF@Robust\def\zref@showprop#1{%
548   \zref@ifpropundefined{#1}{%
549     \@PackageInfoNoLine{\ZREF@name}{%
550       Show property ‘#1’: <undefined>%
551     }%
552   }{%
553     \begingroup
554     \toks@\expandafter\expandafter\expandafter{%
555       \csname Z@C@#1\endcsname
556     }%
557     \edef\ZREF@value{\the\toks@}%
558     \ltx@onelevel@sanitize\ZREF@value
559     \toks@\expandafter\expandafter\expandafter{%
560       \csname Z@D@#1\endcsname
561     }%
562     \edef\ZREF@default{\the\toks@}%
563     \ltx@onelevel@sanitize\ZREF@default
564     \@PackageInfoNoLine{\ZREF@name}{%
565       Show property ‘#1’: \MessageBreak
566       \expandafter\ifx\csname Z@X@#1\endcsname\ltx@empty
567         Immediate %
568       \else
569         Delayed %
570       \fi
571       value: [\ZREF@value]\MessageBreak
572       Default: [\ZREF@default]%
573     }%
574     \endgroup
575   }%
576 }
```

\zref@setcurrent    \zref@setcurrent sets the current value for a property.

```
577 \ZREF@Robust\def\zref@setcurrent#1#2{%
578   \zref@propexists{#1}{%
579     \expandafter\def\csname Z@C@#1\endcsname{#2}%
580   }%
581 }
```

\ZREF@getcurrent    \zref@getcurrent gets the current value for a property.

```
582 \def\ZREF@getcurrent#1{%
583   \romannumeral0%
584   \ltx@ifundefined{Z@C@#1}{%
585     \ltx@space
```

```

586 }{%
587   \expandafter\expandafter\expandafter\ltx@space
588   \csname Z@C@#1\endcsname
589 }%
590 }

```

`\ZREF@u@getcurrent`

```

591 \def\ZREF@wu@getcurrent#1{%
592   \etex@unexpanded\expandafter\expandafter\expandafter{%
593     \ZREF@getcurrent{#1}%
594   }%
595 }

```

`\zref@getcurrent`

```

596 \let\zref@getcurrent\ZREF@getcurrent

```

### 6.2.8 Reference generation

`\zref@label` Label macro that uses the main property list.

```

597 \ZREF@Robust\def\zref@label#1{%
598   \zref@labelbylist{#1}\ZREF@mainlist
599 }

```

`\zref@labelbylist` Label macro that stores the properties, specified in the property list #2.

```

600 \ZREF@Robust\def\zref@labelbylist#1#2{%
601   \@bsphack
602   \zref@listexists{#2}{%
603     \expandafter\expandafter\expandafter\ZREF@label
604     \expandafter\expandafter\expandafter{%
605       \csname Z@L@#2\endcsname
606     }{#1}%
607   }%
608   \@esphack
609 }

```

`\zref@labelbyprops` The properties are directly specified in a comma separated list.

```

610 \ZREF@Robust\def\zref@labelbyprops#1#2{%
611   \@bsphack
612   \begingroup
613   \toks@{%
614     \comma@parse{#2}{%
615       \zref@ifpropundefined\comma@entry{%
616         \PackageWarning\ZREF@name{%
617           Property ‘\comma@entry’ is not known%
618         }%
619       }{%
620         \toks@\expandafter{%
621           \the\expandafter\toks@\csname\comma@entry\endcsname
622         }%
623       }%
624       \ltx@gobble
625     }%
626   \expandafter\endgroup
627   \expandafter\ZREF@label\expandafter{\the\toks@}{#1}%
628   \@esphack
629 }

```

`\zref@labelbykv`

```

630 \ZREF@Robust\def\zref@labelbykv#1#2{%
631   \@bsphack
632   \begingroup
633   \let\Z@L@ZREF@temp\ltx@empty

```

```

634     \kvsetkeys{ZREF@LABEL}{#1}%
635     \ifZREF@immediate
636         \expandafter\zref@wrapper@immediate\expandafter{%
637             \expandafter\ZREF@label\expandafter{\Z@L@ZREF@temp}{#2}%
638         }%
639     \else
640         \expandafter\ZREF@label\expandafter{\Z@L@ZREF@temp}{#2}%
641     \fi
642 \endgroup
643 \@esphack
644 }

645 \kv@define@key{ZREF@LABEL}{prop}{%
646     \edef\ZREF@param{#1}%
647     \zref@propexists\ZREF@param{%
648         \zref@iflistcontainsprop{ZREF@temp}\ZREF@param{}{%
649             \begingroup\expandafter\endgroup
650             \expandafter\ltx@LocalAppendToMacro
651             \expandafter\Z@L@ZREF@temp
652             \expandafter{\csname\ZREF@param\endcsname}%
653         }%
654     }%
655 }

656 \kv@define@key{ZREF@LABEL}{list}{%
657     \zref@listforloop{#1}{%
658         \zref@iflistcontainsprop{ZREF@temp}\zref@prop{}{%
659             \begingroup\expandafter\endgroup
660             \expandafter\ltx@LocalAppendToMacro
661             \expandafter\Z@L@ZREF@temp
662             \expandafter{\csname\zref@prop\endcsname}%
663         }%
664         \ltx@gobble
665     }%
666 }

667 \kv@define@key{ZREF@LABEL}{delprop}{%
668     \zref@propexists{#1}{%
669         \zref@localdelprop{ZREF@temp}{#1}%
670     }%
671 }

672 \kv@define@key{ZREF@LABEL}{immediate}[true]{%
673     \edef\ZREF@param{#1}%
674     \ifx\ZREF@param\ZREF@true
675         \ZREF@immediatetrue
676     \else
677         \ifx\ZREF@param\ZREF@false
678             \ZREF@immediatefalse
679         \else
680             \PackageWarning\ZREF@name{%
681                 Option ‘immediate’ expects ‘true’ or ‘false’.\MessageBreak
682                 Ignoring invalid value ‘\ZREF@param’%
683             }%
684         \fi
685     \fi
686 }

\ZREF@false

687 \def\ZREF@false{false}

\ZREF@true

688 \def\ZREF@true{true}

689 \kv@define@key{ZREF@LABEL}{values}[]{%
690     \kv@parse{#1}{%

```

```

691 \ifx\kv@value\relax
692 \PackageWarning\ZREF@name{%
693 Missing value for property ‘\kv@key’%
694 }%
695 \expandafter\ltx@gobbletwo
696 \else
697 \expandafter\zref@setcurrent
698 \fi
699 }%
700 }

```

`\ifZREF@immediate` The switch `\ifZREF@immediate` tells us, whether the label should be written immediately or at page shipout time. `\ZREF@label` need to be notified about this, because it must disable the deferred execution of property values, if the label is written immediately.

```
701 \newif\ifZREF@immediate
```

`\zref@wrapper@immediate` The argument of `\zref@wrapper@immediate` is executed inside a group where `\write` is redefined by adding `\immediate` before its execution. Also `\ZREF@label` is notified via the switch `\ifZREF@immediate`.

```

702 \ZREF@Robust{\long\def}\zref@wrapper@immediate#1{%
703 \begingroup
704 \ZREF@immediatetrue
705 \let\ZREF@org@write\write
706 \def\write{\immediate\ZREF@org@write}%
707 #1%
708 \endgroup
709 }

```

`\ZREF@label` `\ZREF@label` writes the data in the .aux file. #1 contains the list of valid properties, #2 the name of the reference. In case of immediate writing, the deferred execution of property values is disabled. Also `\ZREF@label` is made expandable in this case.

```

710 \def\ZREF@label#1#2{%
711 \if@filesw
712 \begingroup
713 \ifZREF@immediate
714 \let\ZREF@org@thepage\thepage
715 \fi
716 \protected@write\@auxout{%
717 \ifZREF@immediate
718 \let\thepage\ZREF@org@thepage
719 \fi
720 \let\ZREF@temp\ltx@empty
721 \@tfor\ZREF@P:=#1\do{%
722 \begingroup
723 \escapechar=-1 %
724 \edef\x{\endgroup
725 \def\noexpand\ZREF@P{%
726 \expandafter\string\ZREF@P
727 }%
728 }%
729 \x
730 \expandafter\ifx
731 \csname
732 \ifZREF@immediate
733 relax%
734 \else
735 Z@X@\ZREF@P%
736 \fi
737 \endcsname
738 \noexpand
739 \expandafter\let\csname Z@C@\ZREF@P\endcsname\relax

```

```

740      \fi
741      \toks@\expandafter{\ZREF@temp}%
742      \edef\ZREF@temp{%
743        \the\toks@
744        \ltx@backslashchar\ZREF@P{%
745          \expandafter\noexpand\csname Z@C@\ZREF@P\endcsname
746        }%
747      }%
748    }%
749  }{%
750    \string\zref@newlabel{#2}{\ZREF@temp}%
751  }%
752  \endgroup
753  \fi
754 }
755 \def\ZREF@addtoks#1{%
756   \toks@\expandafter\expandafter\expandafter{%
757     \expandafter\the\expandafter\toks@#1%
758   }%
759 }

```

## 6.2.9 Reference querying and extracting

Design goal for the extracting macros is that the extraction process is full expandable. Thus these macros can be used in expandable contexts. But there are problems that cannot be solved by full expandable macros:

- In standard L<sup>A</sup>T<sub>E</sub>X undefined references sets a flag and generate a warning. Both actions are not expandable.
- Babel's support for its shorthand uses commands that use non-expandable assignments. However currently there is hope, that primitives are added to pdfL<sup>A</sup>T<sub>E</sub>X that allows the detection of contexts. Then the shorthand can detect, if they are executed inside `\csname` and protect themselves automatically.

`\zref@ifrefundefined` If a reference #1 is undefined, then macro `\zref@ifrefundefined` calls #2 and #3 otherwise.

```

760 \def\zref@ifrefundefined#1{%
761   \ltx@ifundefined{Z@R@#1}%
762 }

```

`\zifrefundefined` If a reference #1 is undefined, then macro `\zref@ifrefundefined` calls #2 and #3 otherwise. Also the reference is marked used.

```

763 \ZREF@ifDefinable\zifrefundefined\def{%
764   #1{%
765     \zref@wrapper@babel\ZREF@ifrefundefined{#1}%
766   }%
767 }

```

`\ZREF@ifrefundefined`

```

768 \def\ZREF@ifrefundefined#1{%
769   \zref@refused{#1}%
770   \zref@ifrefundefined{#1}%
771 }

```

`\zref@refused` The problem with undefined references is addressed by the macro `\zref@refused`. This can be used outside the expandable context. In case of an undefined reference the flag is set to notify L<sup>A</sup>T<sub>E</sub>X and a warning is given.

```

772 \ZREF@Robust\def\zref@refused#1{%
773   \zref@wrapper@babel\ZREF@refused{#1}%
774 }

```

\ZREF@refused

```
775 \def\ZREF@refused#1{%
776   \zref@ifrefundefined{#1}{%
777     \protect\G@refundefinedtrue
778     \@latex@warning{%
779       Reference ‘#1’ on page \thepage \space undefined%
780     }%
781   }{}%
782 }
```

\zref@ifrefcontainsprop \zref@ifrefcontainsprop looks, if the reference #1 has the property #2 and calls then #3 and #4 otherwise.

```
783 \def\zref@ifrefcontainsprop#1#2{%
784   \zref@ifrefundefined{#1}{%
785     \ltx@secondoftwo
786   }{%
787     \expandafter\ZREF@ifrefcontainsprop
788     \csname Z@E@#2\expandafter\endcsname
789     \csname#2\expandafter\expandafter\expandafter\endcsname
790     \expandafter\expandafter\expandafter{%
791       \csname Z@R@#1\endcsname
792     }%
793   }%
794 }
795 \def\ZREF@ifrefcontainsprop#1#2#3{%
796   \expandafter\ifx\expandafter\ZREF@novalue
797   #1#3#2\ZREF@novalue\ZREF@nil\ltx@empty
798   \expandafter\ltx@secondoftwo
799   \else
800   \expandafter\ltx@firstoftwo
801   \fi
802 }
803 \def\ZREF@novalue{\ZREF@NOVALUE}
```

\zref@extract \zref@extract is an abbreviation for the case that the default of the property is used as default value.

```
804 \def\ZREF@extract#1#2{%
805   \romannumeral0%
806   \ltx@ifundefined{Z@D@#2}{%
807     \expandafter\ltx@space\zref@default
808   }{%
809     \expandafter\expandafter\expandafter\ZREF@@extract
810     \expandafter\expandafter\expandafter{%
811       \csname Z@D@#2\endcsname
812     }{#1}{#2}%
813   }%
814 }
```

\ZREF@@extract

```
815 \def\ZREF@@extract#1#2#3{%
816   \expandafter\expandafter\expandafter\ltx@space
817   \zref@extractdefault{#2}{#3}{#1}%
818 }
```

\ZREF@wu@extract

```
819 \def\ZREF@wu@extract#1#2{%
820   \etex@unexpanded\expandafter\expandafter\expandafter{%
821     \ZREF@extract{#1}{#2}%
822   }%
823 }
```

\zref@extract

```
824 \let\zref@extract\ZREF@extract
```

`\ZREF@extractdefault` The basic extracting macro is `\zref@extractdefault` with the reference name in #1, the property in #2 and the default value in #3 in case for problems.

```

825 \def\ZREF@extractdefault#1#2#3{%
826   \romannumeral0%
827   \zref@ifrefundefined{#1}\ltx@firstoftwo{%
828     \zref@ifpropundefined{#2}\ltx@firstoftwo\ltx@secondoftwo
829   }{%
830     \ltx@space
831     #3%
832   }{%
833     \expandafter\expandafter\expandafter\ltx@space
834     \csname Z@E@#2\expandafter\expandafter\expandafter\endcsname
835     \csname Z@R@#1\expandafter\endcsname
836     \csname#2\endcsname{#3}\ZREF@nil
837   }%
838 }

```

`\ZREF@wu@extractdefault`

```

839 \def\ZREF@wu@extractdefault#1#2#3{%
840   \etex@unexpanded\expandafter\expandafter\expandafter{%
841     \ZREF@extractdefault{#1}{#2}{#3}%
842   }%
843 }

```

`\zref@extractdefault`

```

844 \let\zref@extractdefault\ZREF@extractdefault

```

`\zref@def@extract`

```

845 \ZREF@Robust\def\zref@def@extract#1{%
846   \zref@wrapper@babel{\ZREF@def@extract{#1}}%
847 }

```

`\ZREF@def@extract`

```

848 \def\ZREF@def@extract#1#2#3{%
849   \zref@refused{#2}%
850   \expandafter\expandafter\expandafter\def
851   \expandafter\expandafter\expandafter#1%
852   \expandafter\expandafter\expandafter{%
853     \zref@extract{#2}{#3}%
854   }%
855 }

```

`\zref@def@extractdefault`

```

856 \ZREF@Robust\def\zref@def@extractdefault#1{%
857   \zref@wrapper@babel{\ZREF@def@extractdefault{#1}}%
858 }

```

`\ZREF@def@extractdefault`

```

859 \def\ZREF@def@extractdefault#1#2#3#4{%
860   \zref@refused{#2}%
861   \expandafter\expandafter\expandafter\def
862   \expandafter\expandafter\expandafter#1%
863   \expandafter\expandafter\expandafter{%
864     \zref@extractdefault{#2}{#3}{#4}%
865   }%
866 }

```

`\ZREF@wrapper@unexpanded`

```

867 \ZREF@Robust{\long\def}\ZREF@wrapper@unexpanded#1{%
868   \let\zref@wrapper@unexpanded\ltx@firstofone
869   \let\zref@getcurrent\ZREF@wu@getcurrent

```

```

870 \let\zref@extractdefault\ZREF@wu@extractdefault
871 \let\zref@extract\ZREF@wu@extract
872 #1%
873 \let\zref@wrapper@unexpanded\ZREF@wrapper@unexpanded
874 \let\zref@getcurrent\ZREF@getcurrent
875 \let\zref@extractdefault\ZREF@extractdefault
876 \let\zref@extract\ZREF@extract
877 }

```

\zref@wrapper@unexpanded

```

878 \ltx@ifundefined{etex@unexpanded}{%
879 \let\zref@wrapper@unexpanded\ltx@firstofone
880 }{%
881 \let\zref@wrapper@unexpanded\ZREF@wrapper@unexpanded
882 }

```

### 6.2.10 Compatibility with babel

\zref@wrapper@babel

```

883 \ZREF@Robust{\long\def}\zref@wrapper@babel#1#2{%
884 \ifcsname if@safe@actives\endcsname
885 \expandafter\ltx@firstofone
886 \else
887 \expandafter\ltx@secondoftwo
888 \fi
889 {%
890 \if@safe@actives
891 \expandafter\ltx@secondoftwo
892 \else
893 \expandafter\ltx@firstoftwo
894 \fi
895 {%
896 \begingroup
897 \csname @safe@activestrue\endcsname
898 \edef\x{#2}%
899 \expandafter\endgroup
900 \expandafter\ZREF@wrapper@babel\expandafter{\x}{#1}%
901 }%
902 }{%
903 #1{#2}%
904 }%
905 }
906 \long\def\ZREF@wrapper@babel#1#2{%
907 #2{#1}%
908 }

```

### 6.2.11 Unique counter support

\zref@require@unique Generate the counter `zref@unique` if the counter does not already exist. change 2022-08-03: The counter is no longer removed from the reset, so that the behaviour with `includeonly` is improved, see issue <https://github.com/ho-tex/zref/issues/10>

```

909 \ZREF@Robust\def\zref@require@unique{%
910 \@ifundefined{c@zref@unique}{%
911 \newcounter{zref@unique}%

```

\thezref@unique \thezref@unique is used for automatically generated unique labelnames.

```

912 \renewcommand*\thezref@unique{%
913 zref@number\c@zref@unique
914 }%
915 }{%
916 }

```

To improve the behaviour if `include/includeonly` is used, we round the counter up at every include, see <https://github.com/ho-tex/zref/issues/10>

```

917 \IfFormatAtLeastTF{2020/10/01}
918 {
919   \AddToHook
920     {include/after}
921     {\setcounter{zref@unique}
922       {\csname fp_to_int:n\endcsname{ceil(\c@zref@unique +100,-2)}}}
923 }{}

```

### 6.2.12 Utilities

`\ZREF@number`

```

924 \ltx@ifundefined{numexpr}{%
925   \def\ZREF@number#1{\number#1}%
926 }{%
927   \def\ZREF@number#1{\the\numexpr(#1)\relax}%
928 }

```

### 6.2.13 Setup

`\zref@setdefault` Standard L<sup>A</sup>T<sub>E</sub>X prints “??” in bold face if a reference is not known. `\zref@default` holds the text that is printed in case of unknown references and is used, if the default was not specified during the definition of the new property by `\ref@newprop`. The global default value can be set by `\zref@setdefault`.

```

929 \ZREF@Robust\def\zref@setdefault#1{%
930   \def\zref@default{#1}%
931 }

```

`\zref@default` Now we initialize `\zref@default` with the same value that L<sup>A</sup>T<sub>E</sub>X uses for its undefined references.

```

932 \zref@setdefault{%
933   \nfss@text{\reset@font\bfseries ??}%
934 }

```

### Main property list.

`\zref@setmainlist` The name of the default property list is stored in `\ZREF@mainlist` and can be set by `\zref@setmainlist`.

```

935 \ZREF@Robust\def\zref@setmainlist#1{%
936   \def\ZREF@mainlist{#1}%
937 }
938 \zref@setmainlist{main}

```

Now we create the list.

```

939 \zref@newlist\ZREF@mainlist

```

**Main properties.** The two properties `default` and `page` are created and added to the main property list. They store the data that standard L<sup>A</sup>T<sub>E</sub>X uses in its references created by `\label`.

`default` the apperance of the latest counter that is incremented by `\refstepcounter`

`page` the apperance of the page counter

```

940 \zref@newprop{default}{\@currentlabel}
941 \zref@newprop*{page}{\thepage}
942 \zref@addprops\ZREF@mainlist{default,page}

```

## Properties

`\ZREF@NewPropAnchor`

```
943 \def\ZREF@NewPropAnchor{%
944   \zref@newprop{anchor}{%
945     \ltx@ifundefined{@currentHref}{\@currentHref}%
946   }%
947   \global\let\ZREF@NewPropAnchor\relax
948 }
```

`\zref@titleref@current` Later we will redefine the section and caption macros to catch the current title and remember the value in `\zref@titleref@current`.

`\ZREF@NewPropTitle`

```
949 \def\ZREF@NewPropTitle{%
950   \gdef\zref@titleref@current{%
951     \zref@newprop{title}{\zref@titleref@current}%
952   \global\let\ZREF@NewPropTitle\relax
953 }
```

`\ZREF@NewPropTheotype`

```
954 \def\ZREF@NewPropTheotype{%
955   \zref@newprop{theotype}{}%
956   \global\let\ZREF@NewPropTheotype\relax
957 }
```

`\ZREF@NewPropPageValue`

```
958 \def\ZREF@NewPropPageValue{%
959   \zref@newprop*{pagevalue}[0]{\number\c@page}%
960   \global\let\ZREF@NewPropPageValue\relax
961 }
```

## Mark successful loading

```
962 \let\ZREF@base@ok=Y
963 \</base>
```

## 6.3 Module user

```
964 <*user>
965 \NeedsTeXFormat{LaTeX2e}
966 \ProvidesPackage{zref-user}%
967 [2022-03-08 v2.33 Module user for zref (H0)]%
968 \RequirePackage{zref-base}[2019/11/29]
969 \ifx\ZREF@base@ok Y%
970 \else
971   \expandafter\endinput
972 \fi
```

Module user enables a small user interface. All macros are prefixed by `\z`.

First we define the pendants to the standard  $\text{\LaTeX}$  referencing commands `\label`, `\ref`, and `\pageref`.

`\zlabel` Similar to `\label` the macro `\zlabel` writes a reference entry in the `.aux` file. The main property list is used. Also we add the babel patch. The `\label` command can also be used inside section titles, but it must not go into the table of contents. Therefore we have to check this situation.

```
973 \newcommand*\zlabel{%
974   \ifx\label\ltx@gobble
975     \expandafter\ltx@gobble
976   \else
977     \expandafter\zref@wrapper@babel\expandafter\zref@label
978   \fi
979 }
```

`\zkvlabel`

```

980 \newcommand*{\zkvlabel}[1]{%
981   \ifx\label\ltx@gobble
982     \expandafter\ltx@gobblethree
983   \fi
984   \zref@wrapper@babel{\zref@labelbykv{#1}}%
985 }%
```

`\zref` Macro `\zref` is the corresponding macro for `\ref`. Also it provides an optional argument in order to select another property.

```

986 \newcommand*{\zref}[2][default]{% robust because of optional argument
987   \zref@propexists{#1}{%
988     \zref@wrapper@babel\ZREF@zref{#2}{#1}%
989   }%
990 }%
991 \def\ZREF@zref#1{%
992   \zref@refused{#1}%
993   \zref@extract{#1}%
994 }%
```

`\zpageref` For macro `\zpageref` we just call `\zref` with property `page`.

```

995 \ZREF@ifDefinable\zpageref\def{%
996   {\zref[page]}%
997 }
```

`\zrefused` For the following expandible user macros `\zrefused` should be used to notify L<sup>A</sup>T<sub>E</sub>X in case of undefined references.

```

998 \ZREF@ifDefinable\zrefused\def{%
999   {\zref@refused}%
1000 }
1001 </user>
```

## 6.4 Module `abspage`

```

1002 <*abspage>
1003 \NeedsTeXFormat{LaTeX2e}
1004 \ProvidesPackage{zref-abspage}%
1005   [2022-03-08 v2.33 Module abspage for zref (HO)]%
1006 \RequirePackage{zref-base}[2019/11/29]
1007 \ifx\ZREF@base@ok Y%
1008 \else
1009   \expandafter\endinput
1010 \fi
```

Module `abspage` adds a new property `abspage` to the main property list for absolute page numbers. These are recorded by the help of package `atbegshi`.

```

1011 \RequirePackage{atbegshi}[2011/10/05]%
```

The counter `abspage` must not go in the clear list of `@ckpt` that is used to set counters in `.aux` files of included T<sub>E</sub>X files.

```

1012 \begingroup
1013   \let\@addtoreset\ltx@gobbletwo
1014   \newcounter{abspage}%
1015 \endgroup
1016 \setcounter{abspage}{0}%
1017 \AtBeginShipout{%
1018   \stepcounter{abspage}%
1019 }%
1020 \zref@newprop*{abspage}[0]{\the\c@abspage}%
1021 \zref@addprop\ZREF@mainlist{abspage}%
```

Note that counter `abspage` shows the previous page during page processing. Before shipout the counter is incremented. Thus the property is correctly written with

deferred writing. If the counter is written using `\zref@wrapper@immediate`, then the number is too small by one.

1022 `</abspage>`

## 6.5 Module counter

```
1023 <*counter>
1024 \NeedsTeXFormat{LaTeX2e}
1025 \ProvidesPackage{zref-counter}%
1026 [2022-03-08 v2.33 Module counter for zref (HO)]%
1027 \RequirePackage{zref-base}[2019/11/29]
1028 \ifx\ZREF@base@ok Y%
1029 \else
1030 \expandafter\endinput
1031 \fi
```

For features such as `hyperref`'s `\autoref` we need the name of the counter. The property `counter` is defined and added to the main property list. Starting with `LATEX 2020-10-01` the proper can use `currentcounter`. In older formats `\refstepcounter` has to be patched but this can fail in some cases, see issue #5.

```
1032 \ifl@t@r\fmtversion{2020-10-01}
1033 {
1034 \zref@newprop{counter}{\@currentcounter}
1035 \zref@addprop\ZREF@mainlist{counter}
1036 }
1037 {
1038 \zref@newprop{counter}{}
1039 \zref@addprop\ZREF@mainlist{counter}
1040 \AtBeginDocument{%
1041 \ZREF@patch{refstepcounter}{%
1042 \def\refstepcounter#1{%
1043 \zref@setcurrent{counter}{#1}%
1044 \ZREF@org@refstepcounter{#1}%
1045 }%
1046 }%
1047 }
1048 }
1049 </counter>
```

## 6.6 Module lastpage

```
1050 <*lastpage>
1051 \NeedsTeXFormat{LaTeX2e}
1052 \ProvidesPackage{zref-lastpage}%
1053 [2022-03-08 v2.33 Module lastpage for zref (HO)]%
1054 \RequirePackage{zref-base}[2019/11/29]
1055 \RequirePackage{zref-abspage}[2019/11/29]
1056 \RequirePackage{atveryend}[2009/12/07]
1057 \ifx\ZREF@base@ok Y%
1058 \else
1059 \expandafter\endinput
1060 \fi
```

The module `lastpage` implements the service of package `lastpage` by setting a reference `LastPage` at the end of the document. If module `abspage` is given, also the absolute page number is available, because the properties of the main property list are used.

```
1061 \zref@newlist{LastPage}
1062 \AfterLastShipout{%
1063 \if@filesw
1064 \begingroup
1065 \advance\c@page\m@ne
1066 \toks@{\expandafter\expandafter\expandafter{%
1067 \expandafter\Z@L@main
```

```

1068      \Z@L@LastPage
1069    }%
1070    \expandafter\zref@wrapper@immediate\expandafter{%
1071      \expandafter\ZREF@label\expandafter{\the\toks@}{LastPage}%
1072    }%
1073  \endgroup
1074 \fi
1075 }

\zref@iflastpage
1076 \def\zref@iflastpage#1{%
1077   \ifnum\zref@extractdefault{#1}{abspage}{-1}=%
1078     \zref@extractdefault{LastPage}{abspage}{-2} %
1079   \expandafter\ltx@firstoftwo
1080 \else
1081   \expandafter\ltx@secondoftwo
1082 \fi
1083 }

\ziflastpage
1084 \ZREF@ifDefinable\ziflastpage\def{%
1085   {\zref@wrapper@babel\ZREF@iflastpage}%
1086 }

ZREF@iflastpage
1087 \def\ZREF@iflastpage#1{%
1088   \zref@refused{LastPage}%
1089   \zref@refused{#1}%
1090   \zref@iflastpage{#1}%
1091 }

1092 </lastpage>

```

## 6.7 Module thepage

```

1093 <*thepage>
1094 \NeedsTeXFormat{LaTeX2e}
1095 \ProvidesPackage{zref-thepage}%
1096   [2022-03-08 v2.33 Module thepage for zref (H0)]%
1097 \RequirePackage{zref-base}[2019/11/29]
1098 \ifx\ZREF@base@ok Y%
1099 \else
1100   \expandafter\endinput
1101 \fi

1102 \RequirePackage{atbegshi}[2011/10/05]
1103 \RequirePackage{zref-abspage}[2019/11/29]

1104 \zref@newlist{thepage}
1105 \zref@addprop{thepage}{page}
1106 \ZREF@NewPropPageValue

\zref@thepage@atbegshi@hook
1107 \let\zref@thepage@atbegshi@hook\ltx@empty

1108 \zref@addprop{thepage}{pagevalue}
1109 \AtBeginShipout{%
1110   \AtBeginShipoutAddToBox{%
1111     \zref@thepage@atbegshi@hook
1112     \zref@labelbylist{thepage\the\value{abspage}}{thepage}%
1113   }%
1114 }

```

```

\zref@thepage@name
1115 \ltx@ifundefined{numexpr}{%
1116   \def\zref@thepage@name#1{thepage\number#1}%
1117 }{%
1118   \def\zref@thepage@name#1{thepage\the\numexpr#1}%
1119 }

\zref@thepage
1120 \def\zref@thepage#1{%
1121   \zref@extract{\zref@thepage@name{#1}}{page}%
1122 }%

\zref@thepage@refused
1123 \ZREF@Robust\def\zref@thepage@refused#1{%
1124   \zref@refused{\zref@thepage@name{#1}}%
1125 }%

\zthepage
1126 \ZREF@ifdefinable\zthepage\def{%
1127   #1{%
1128     \zref@thepage@refused{#1}%
1129     \zref@thepage{#1}%
1130   }%
1131 }

1132 </thepage>

```

## 6.8 Module nextpage

```

1133 <*nextpage>
1134 \NeedsTeXFormat{LaTeX2e}
1135 \ProvidesPackage{zref-nextpage}%
1136   [2022-03-08 v2.33 Module nextpage for zref (HO)]%
1137 \RequirePackage{zref-base}[2019/11/29]
1138 \ifx\ZREF@base@ok Y%
1139 \else
1140   \expandafter\endinput
1141 \fi

1142 \RequirePackage{zref-abspage}[2019/11/29]
1143 \RequirePackage{zref-thepage}[2019/11/29]
1144 \RequirePackage{zref-lastpage}[2019/11/29]
1145 \RequirePackage{uniquecounter}[2009/12/18]

1146 \UniqueCounterNew{znnextpage}
1147
1148 \newcommand*{\znnextpagesetup}{%
1149   \afterassignment\ZREF@np@setup@i
1150   \def\ZREF@np@call@unknown##1%
1151 }
1152 \def\ZREF@np@setup@i{%
1153   \afterassignment\ZREF@np@setup@ii
1154   \def\ZREF@np@call@nonext##1%
1155 }
1156 \def\ZREF@np@setup@ii{%
1157   \def\ZREF@np@call@next##1%
1158 }
1159 \def\ZREF@np@call@unknown#1{#1}
1160 \def\ZREF@np@call@nonext#1{#1}
1161 \def\ZREF@np@call@next#1{#1}
1162 \ZREF@ifdefinable\znnextpage\def{%
1163   {\UniqueCounterCall{znnextpage}{\ZREF@nextpage}}%
1164 }%

```

```

1165 \newcommand*{\znonextpagename}{}
1166 \newcommand*{\zunknownnextpagename}{\Z@D@page}
1167 \def\ZREF@nextpage#1{%
1168   \begingroup
1169     \def\ZREF@refname@this{zref@np#1}%
1170     \zref@labelbyprops\ZREF@refname@this{abspage}%
1171     \chardef\ZREF@call=0 % unknown
1172     \ZREF@ifrefundefined\ZREF@refname@this{%
1173       }{%
1174         \edef\ZREF@pagenum@this{%
1175           \zref@extractdefault\ZREF@refname@this{abspage}{0}%
1176         }%
1177         \edef\ZREF@refname@next{%
1178           \zref@thepage@name{%
1179             \the\numexpr\ZREF@pagenum@this+1%
1180           }%
1181         }%
1182         \ifnum\ZREF@pagenum@this>0 %
1183           \ZREF@ifrefundefined{LastPage}{%
1184             \zref@ifrefundefined\ZREF@refname@next{%
1185               }{%
1186                 \chardef\ZREF@call=2 % next page
1187               }%
1188             }{%
1189               \edef\ZREF@pagenum@last{%
1190                 \zref@extractdefault{LastPage}{abspage}{0}%
1191               }%
1192               \ifnum\ZREF@pagenum@this<\ZREF@pagenum@last\ltx@space
1193                 \ZREF@ifrefundefined\ZREF@refname@next{%
1194                   }{%
1195                     \chardef\ZREF@call=2 % next page
1196                   }%
1197                 \else
1198                   \ifnum\ZREF@pagenum@this=\ZREF@pagenum@last\ltx@space
1199                     \chardef\ZREF@call=1 % no next page
1200                   \fi
1201                 \fi
1202               }%
1203             \fi
1204           }%
1205         \edef\x{%
1206           \endgroup
1207           \ifcase\ZREF@call
1208             \noexpand\ZREF@np@call@unknown{%
1209               \noexpand\zunknownnextpagename
1210             }%
1211           \or
1212             \noexpand\ZREF@np@call@nonext{%
1213               \noexpand\znonextpagename
1214             }%
1215           \else
1216             \noexpand\ZREF@np@call@next{%
1217               \noexpand\zref@extract{\ZREF@refname@next}{page}%
1218             }%
1219           \fi
1220         }%
1221       \x
1222     }
1223 \nextpage

```

## 6.9 Module totpages

```

1224 \*totpages

```

```

1225 \NeedsTeXFormat{LaTeX2e}
1226 \ProvidesPackage{zref-totpages}%
1227 [2022-03-08 v2.33 Module totpages for zref (H0)]%
1228 \RequirePackage{zref-base}[2019/11/29]
1229 \ifx\ZREF@base@ok Y%
1230 \else
1231 \expandafter\endinput
1232 \fi

```

The absolute page number of the last page is the total page number.

```

1233 \RequirePackage{zref-abspage}[2019/11/29]
1234 \RequirePackage{zref-lastpage}[2019/11/29]

```

**\ztotpages** Macro `\ztotpages` contains the number of pages. It can be used inside expandable calculations. It expands to zero if the reference is not yet available.

```

1235 \newcommand*{\ztotpages}{%
1236 \zref@extractdefault{LastPage}{abspage}{0}%
1237 }

```

Also we mark the reference `LastPage` as used:

```

1238 \AtBeginDocument{%
1239 \zref@refused{LastPage}%
1240 }
1241 </totpages>

```

## 6.10 Module pagelayout

```

1242 <*pagelayout>
1243 \NeedsTeXFormat{LaTeX2e}
1244 \ProvidesPackage{zref-pagelayout}%
1245 [2022-03-08 v2.33 Module pagelayout for zref (H0)]%
1246 \RequirePackage{zref-base}[2019/11/29]
1247 \ifx\ZREF@base@ok Y%
1248 \else
1249 \expandafter\endinput
1250 \fi

1251 \RequirePackage{zref-thepage}[2019/11/29]
1252 \RequirePackage{iftex}[2019/11/07]%
1253 \RequirePackage{atveryend}[2010/03/24]

```

### 6.10.1 Define layout properties

```

1254 \def\ZREF@temp#1{%
1255 \begingroup
1256 \escapechar=-1 %
1257 \ltx@ifundefined{\string#1}{\endgroup}{%
1258 \edef\x{%
1259 \endgroup
1260 \noexpand\zref@newprop*{\string#1}%
1261 [\noexpand\number\noexpand#1]% hash-ok
1262 {\noexpand\number\noexpand#1}%
1263 \noexpand\zref@addprop{thepage}{\string#1}%
1264 }%
1265 \x
1266 }%
1267 }

1268 \ZREF@temp\mag
1269 \ZREF@temp\paperwidth
1270 \ZREF@temp\paperheight
1271 \ZREF@temp\stockwidth % memoir.cls, crop.sty
1272 \ZREF@temp\stockheight % memoir.cls, crop.sty
1273 \ZREF@temp\mediawidth % VTeX
1274 \ZREF@temp\mediaheight % VTeX

```

```

1275 \ifluatex
1276 \zref@newprop*{pdfvorigin}%
1277             [\number\pdfvariable vorigin]% hash-ok
1278             {\number\pdfvariable vorigin}%
1279 \zref@addprop{thepage}{pdfvorigin}
1280 \zref@newprop*{pdfhorigin}%
1281             [\number\pdfvariable horigin]% hash-ok
1282             {\number\pdfvariable horigin}%
1283 \zref@addprop{thepage}{pdfhorigin}
1284 \zref@newprop*{pdfpageheight}%
1285             [\number\pageheight]% hash-ok
1286             {\number\pageheight}%
1287 \zref@addprop{thepage}{pdfpageheight}
1288 \zref@newprop*{pdfpagewidth}%
1289             [\number\pagewidth]% hash-ok
1290             {\number\pagewidth}%
1291 \zref@addprop{thepage}{pdfpagewidth}
1292 \else
1293 \ZREF@temp\pdfpagewidth
1294 \ZREF@temp\pdfpageheight
1295 \ZREF@temp\pdfhorigin
1296 \ZREF@temp\pdfvorigin
1297 \fi
1298 \ZREF@temp\hoffset
1299 \ZREF@temp\voffset
1300 \ZREF@temp\topmargin
1301 \ZREF@temp\oddsidemargin
1302 \ZREF@temp\evensidemargin
1303 \ZREF@temp\textwidth
1304 \ZREF@temp\textheight
1305 \ZREF@temp\headheight
1306 \ZREF@temp\headsep
1307 \ZREF@temp\footskip
1308 \ZREF@temp\marginparwidth
1309 \ZREF@temp\marginparsep
1310 \ZREF@temp\columnwidth
1311 \ZREF@temp\columnsep
1312 \ZREF@temp\trimedge % memoir.cls
1313 \ZREF@temp\spinemargin % memoir.cls
1314 \ZREF@temp\foremargin % memoir.cls
1315 \ZREF@temp\trintop % memoir.cls
1316 \ZREF@temp\uppermargin % memoir.cls
1317 \ZREF@temp\headmargin % memoir.cls
1318 \IfFormatAtLeastTF{2020/10/01}
1319 {
1320     \zref@newprop*{outputboxwd}[0pt]{\ShipoutBoxWidth}
1321     \zref@newprop*{outputboxht}[0pt]{\ShipoutBoxHeight}
1322     \zref@newprop*{outputboxdp}[0pt]{\ShipoutBoxDepth}
1323 }
1324 {
1325     \zref@newprop*{outputboxwd}[0pt]{\AtBeginShipoutBoxWidth}
1326     \zref@newprop*{outputboxht}[0pt]{\AtBeginShipoutBoxHeight}
1327     \zref@newprop*{outputboxdp}[0pt]{\AtBeginShipoutBoxDepth}
1328 }
1329 \zref@addprops{thepage}{outputboxwd,outputboxht,outputboxdp}

\ifZREF@pl@list
1330 \ltx@newif\ifZREF@pl@list

\zref@listpagelayout
1331 \ZREF@IfDefinable\zlistpagelayout\def{%
1332     {\global\ZREF@pl@listtrue}%

```

1333 }

\ZREF@pl@AfterLastShipout

```
1334 \def\ZREF@pl@AfterLastShipout{%
1335   \ifZREF@pl@list
1336     \edef\ZREF@page@max{\the\value{abspage}}%
1337     \ltx@ifundefined{ZREF@org@testdef}{%
1338       \let\ZREF@org@testdef\@testdef
1339       \def\@testdef##1##2##3{%
1340         \ZREF@org@testdef{##1}{##2}{##3}%
1341         \def\ZREF@temp{##1}%
1342         \ifx\ZREF@temp\ZREF@RefPrefix
1343           \expandafter\gdef\csname##1@##2\endcsname{##3}%
1344         \fi
1345       }%
1346     }{}%
1347     \AtVeryEndDocument{\ZREF@pl@AtVeryEnd}%
1348   \fi
1349 }
```

\ZREF@pl@AtVeryEnd

```
1350 \def\ZREF@pl@AtVeryEnd{%
1351   \begingroup
1352   \toks@{Page layout parameters:\MessageBreak}%
1353   \count@=1 %
1354   \ZREF@pl@ListPage
1355   \edef\x{\endgroup
1356     \noexpand\@PackageInfoNoLine{zref-pagelayout}{\the\toks@}%
1357   }%
1358   \x
1359 }
```

\ZREF@pl@ListPage

```
1360 \def\ZREF@pl@ListPage{%
1361   \edef\x{%
1362     \toks@={%
1363       \the\toks@
1364       Page \the\count@:\noexpand\MessageBreak
1365       \zref@ifrefundefined{thepage\the\count@}{}{%
1366         \ltx@space\ltx@space mag = %
1367         \zref@extract{thepage\the\count@}{mag}%
1368         \noexpand\MessageBreak
1369         \ZREF@pl@ListEntry{paperwidth}%
1370         \ZREF@pl@ListEntry{paperheight}%
1371         \ZREF@pl@ListEntry{stockwidth}%
1372         \ZREF@pl@ListEntry{stockheight}%
1373         \ZREF@pl@ListEntry{mediawidth}%
1374         \ZREF@pl@ListEntry{mediaheight}%
1375         \ZREF@pl@ListEntry{pdfpagewidth}%
1376         \ZREF@pl@ListEntry{pdfpageheight}%
1377         \ZREF@pl@ListEntry{pdfhorigin}%
1378         \ZREF@pl@ListEntry{pdfvorigin}%
1379         \ZREF@pl@ListEntry{hoffset}%
1380         \ZREF@pl@ListEntry{voffset}%
1381         \ZREF@pl@ListEntry{topmargin}%
1382         \ZREF@pl@ListEntry{oddsidemargin}%
1383         \ZREF@pl@ListEntry{evensidemargin}%
1384         \ZREF@pl@ListEntry{textwidth}%
1385         \ZREF@pl@ListEntry{textheight}%
1386         \ZREF@pl@ListEntry{headheight}%
1387         \ZREF@pl@ListEntry{headsep}%
1388         \ZREF@pl@ListEntry{footskip}%

```

```

1389      \ZREF@pl@ListEntry{marginparwidth}%
1390      \ZREF@pl@ListEntry{marginparsep}%
1391      \ZREF@pl@ListEntry{columnwidth}%
1392      \ZREF@pl@ListEntry{columnsep}%
1393      \ZREF@pl@ListEntry{trimedge}%
1394      \ZREF@pl@ListEntry{spinemargin}%
1395      \ZREF@pl@ListEntry{foremargin}%
1396      \ZREF@pl@ListEntry{trimtop}%
1397      \ZREF@pl@ListEntry{uppermargin}%
1398      \ZREF@pl@ListEntry{headmargin}%
1399  }%
1400 }%
1401 }\x
1402 \ifnum\ZREF@page@max>\count@
1403   \advance\count@ by\ltx@one
1404 \else
1405   \expandafter\ltx@gobble
1406 \fi
1407 \ZREF@pl@ListPage
1408 }

```

\ZREF@pl@ListEntry

```

1409 \def\ZREF@pl@ListEntry#1{%
1410   \zref@ifpropundefined{#1}{%
1411     }{%
1412       \zref@ifrefcontainsprop{thepage\the\count@}{#1}{%
1413         \ltx@space\ltx@space#1 = %
1414         \zref@extract{thepage\the\count@}{#1}sp = %
1415         \the\dimexpr\zref@extract{thepage\the\count@}{#1}sp\relax
1416         \noexpand\MessageBreak
1417       }{%
1418       }%
1419 }
1420 \AfterLastShipout{%
1421   \ZREF@pl@AfterLastShipout
1422 }
1423 </pagelayout>

```

## 6.11 Module pageattr

```

1424 <*pageattr>
1425 \NeedsTeXFormat{LaTeX2e}
1426 \ProvidesPackage{zref-pageattr}%
1427 [2022-03-08 v2.33 Module pageattr for zref (HO)]%
1428 \RequirePackage{zref-base}[2019/11/29]
1429 \ifx\ZREF@base@ok Y%
1430 \else
1431   \expandafter\endinput
1432 \fi
1433 \RequirePackage{iftex}[2019/11/07]%
1434 \let\ZREF@temp=N%
1435 \ifluatex
1436   \expandafter\@firstoftwo
1437 \else
1438   \expandafter\@secondoftwo
1439 \fi
1440 {%luatex
1441   \RequirePackage{zref-thepage}[2019/11/29]
1442   \RequirePackage{zref-lastpage}[2019/11/29]%
1443   \zref@newprop*{pdfpageattr}[]{\zref@hex{\the\pdfvariable pageattr}}%

```

```

1444 \zref@addprop{thepage}{pdfpageattr}%
1445 \zref@newprop*{pdfpagesattr}[]{\zref@hex{\the\pdfvariable pagesattr}}%
1446 \zref@addprop{LastPage}{pdfpagesattr}%
1447 \let\ZREF@temp=Y%
1448 }
1449 {%other
1450 \ltx@ifundefined{pdfpageattr}{%
1451 \@PackageInfoNoLine{zref-pageattr}{%
1452 \string\pdfpageattr\space is not available%
1453 }%
1454 \def\zref@pdfpageattr#1{%
1455 \def\zref@pdfpageattr@used#1{%
1456 }{%
1457 \RequirePackage{zref-thepage}[2019/11/29]%
1458 \zref@newprop*{pdfpageattr}[]{\zref@hex{\the\pdfpageattr}}%
1459 \zref@addprop{thepage}{pdfpageattr}%
1460 \let\ZREF@temp=Y%
1461 }
1462 \ltx@ifundefined{pdfpagesattr}{%
1463 \@PackageInfoNoLine{zref-pageattr}{%
1464 \string\pdfpagesattr\space is not available%
1465 }%
1466 \def\zref@pdfpagesattr{%
1467 \def\zref@pdfpagesattr@used{%
1468 }{%
1469 \RequirePackage{zref-lastpage}[2019/11/29]%
1470 \zref@newprop*{pdfpagesattr}[]{\zref@hex{\the\pdfpagesattr}}%
1471 \zref@addprop{LastPage}{pdfpagesattr}%
1472 \let\ZREF@temp=Y%
1473 }%
1474 }%

1475 \ifx\ZREF@temp N%
1476 \expandafter\endinput
1477 \fi

1478 \RequirePackage{zref-abspage}[2019/11/29]
1479 \RequirePackage{atveryend}[2010/03/24]
1480 \RequirePackage{pdfcmds}[2010/04/01]
1481 \let\ZREF@temp=Y%
1482 \ltx@ifundefined{pdf@escapehex}{\let\ZREF@temp=N}{%
1483 \ltx@ifundefined{pdf@unescapehex}{\let\ZREF@temp=N}{%
1484 \ifx\ZREF@temp N%
1485 \let\zref@hex\ltx@firstofone
1486 \let\zref@unhex\ltx@firstofone
1487 \else
1488 \let\zref@hex\pdf@escapehex
1489 \let\zref@unhex\pdf@unescapehex
1490 \fi

\ifZREF@pa@list
1491 \ltx@newif\ifZREF@pa@list

\zref@listpageattr
1492 \ZREF@ifDefinable\zlistpageattr\def{%
1493 {\ZREF@pa@listtrue}%
1494 }

\ZREF@pa@AfterLastShipout
1495 \def\ZREF@pa@AfterLastShipout{%
1496 \ifZREF@pa@list
1497 \edef\ZREF@page@max{\the\value{abspage}}%
1498 \ltx@ifundefined{ZREF@org@testdef}{%
1499 \let\ZREF@org@testdef\@testdef

```

```

1500     \def\@testdef##1##2##3{%
1501         \ZREF@org@testdef{##1}{##2}{##3}%
1502     \def\ZREF@temp{##1}%
1503     \ifx\ZREF@temp\ZREF@RefPrefix
1504         \expandafter\xdef\csname##1@##2\endcsname{##3}%
1505     \fi
1506     }%
1507     }{%
1508     \AtVeryEndDocument{\ZREF@pa@AtVeryEnd}%
1509 \fi
1510 }

```

\ZREF@pa@AtVeryEnd

```

1511 \let\ZREF@temp=Y%
1512 \ltx@ifundefined{pdfpageattr}{\let\ZREF@temp=N}
1513 \ifluatex \let\ZREF@temp=N \fi
1514 \ifx\ZREF@temp Y
1515     \expandafter\@firstoftwo
1516 \else
1517     \expandafter\@secondoftwo
1518 \fi
1519 {%
1520     \def\ZREF@pa@AtVeryEnd{%
1521     }
1522     {%
1523     \def\ZREF@pa@AtVeryEnd{%
1524         \begingroup
1525         \toks@{\List of \ltx@backslashchar
1526             \ifluatex pdfvariable\else pdf\fi
1527             pdfpageattr:\MessageBreak}%
1528         \count@=1 %
1529         \ZREF@pa@ListPage
1530         \edef\x{\endgroup
1531             \noexpand\@PackageInfoNoLine{zref-pageattr}{%
1532                 \the\toks@
1533             }%
1534         }%
1535     \x
1536     }%

```

\zref@pageattr

```

1537 \def\zref@pdfpageattr#1{%
1538     \zref@unhex{%
1539         \zref@extract{thepage\ZREF@number{#1}}{pdfpageattr}%
1540     }%
1541 }
1542 % compability, \zref@pageattr was defined in older versions
1543 \let\zref@pageattr\zref@pdfpageattr

```

\zref@pageattr@used

```

1544 \ZREF@Robust\def\zref@pageattr@used#1{%
1545     \zref@refused{thepage\ZREF@number{#1}}%
1546 }

```

\ZREF@pa@ListPage

```

1547 \def\ZREF@pa@ListPage{%
1548     \edef\x{%
1549         \toks@={%
1550             \the\toks@
1551             Page \the\count@:%
1552             \noexpand\MessageBreak
1553             \zref@ifrefundefined{thepage\the\count@}{-}{%

```

```

1554         <<\zref@pdfpageattr\count@>>%
1555         \noexpand\MessageBreak
1556     }%
1557 }%
1558 }\x
1559 \ifnum\ZREF@page@max>\count@
1560     \advance\count@ by\ltx@one
1561 \else
1562     \expandafter\ltx@gobble
1563 \fi
1564 \ZREF@pa@ListPage
1565 }%
1566 }

1567 \let\ZREF@temp=Y%
1568 \ltx@ifundefined{pdfpagesattr}{\let\ZREF@temp=N}
1569 \ifluatex \let\ZREF@temp=N \fi
1570 \ifx\ZREF@temp N
1571     \expandafter\@firstofone
1572 \fi
1573 {%

```

\zref@pdfpagesattr

```

1574 \def\zref@pdfpagesattr{%
1575     \zref@unhex{%
1576         \zref@extract{LastPage}{pdfpagesattr}%
1577     }%
1578 }%

```

\zref@pdfpagesattr@used

```

1579 \ZREF@Robust\def\zref@pdfpagesattr@used{%
1580     \zref@refused{LastPage}%
1581 }%

1582 \ltx@LocalAppendToMacro\ZREF@pa@AtVeryEnd{%
1583     \@PackageInfoNoLine{zref-pageattr}{%
1584         \ltx@backslashchar
1585         \ifluatex pdfvariable\else pdf\fi
1586         pagesattr:\MessageBreak
1587         <<\zref@pdfpagesattr>>%
1588         \MessageBreak
1589     }%
1590 }%
1591 }

1592 \AfterLastShipout{%
1593     \ZREF@pa@AfterLastShipout
1594 }

1595 </pageattr>

```

## 6.12 Module marks

```

1596 <*marks>
1597 \NeedsTeXFormat{LaTeX2e}
1598 \ProvidesPackage{zref-marks}%
1599 [2022-03-08 v2.33 Module marks for zref (H0)]%
1600 \RequirePackage{zref-base}[2019/11/29]
1601 \ifx\ZREF@base@ok Y%
1602 \else
1603     \expandafter\endinput
1604 \fi

1605 \newcommand*{\zref@marks@register}[3][ ]{%
1606     \edef\ZREF@TempName{#1}%

```

```

1607 \edef\ZREF@TempNum{\ZREF@number{#2}}%
1608 \ifnum\ZREF@TempNum<\ltx@zero %
1609   \PackageError\ZREF@name{%
1610     \string\zref@marks@register\ltx@space is called with invalid%
1611     \MessageBreak
1612     marks register number (\ZREF@TempNum)%
1613   }{%
1614     Use '0' or the command, defined by \string\newmarks.\MessageBreak
1615     \@ehc
1616   }%
1617 \else
1618   \ifx\ZREF@TempName\ltx@empty
1619     \edef\ZREF@TempName{mark\romannumeral\ZREF@TempNum}%
1620   \else
1621     \edef\ZREF@TempName{marks\ZREF@TempName}%
1622   \fi
1623   \ZREF@MARKS@DefineProp{top}%
1624   \ZREF@MARKS@DefineProp{first}%
1625   \ZREF@MARKS@DefineProp{bot}%
1626   \kv@parse{#3}{%
1627     \ifx\kv@value\relax
1628       \def\kv@value{top,first,bot}%
1629     \fi
1630     \edef\ZREF@temp{\expandafter\ltx@car\kv@key X\@nil}%
1631     \ifx\ZREF@temp\ZREF@STAR
1632       \edef\kv@key{\expandafter\ltx@cdr\kv@key\@nil}%
1633       \zref@newlist\kv@key
1634     \fi
1635     \expandafter\comma@parse\expandafter{\kv@value}{%
1636       \ifcase0\ifx\comma@entry\ZREF@NAME@top 1\else
1637         \ifx\comma@entry\ZREF@NAME@first 1\else
1638         \ifx\comma@entry\ZREF@NAME@bot 1\fi\fi\fi\ltx@space
1639       \PackageWarning{zref-marks}{%
1640         Use 'top', 'first' or 'bot' for the list values%
1641         \MessageBreak
1642         in the third argument of \string\zref@marks@register.%
1643         \MessageBreak
1644         Ignoring unkown value '\comma@entry'%
1645       }%
1646     \else
1647       \zref@addprop{\kv@key}{\comma@entry\ZREF@TempName}%
1648     \fi
1649     \ltx@gobble
1650   }%
1651   \ltx@gobbletwo
1652 }%
1653 \fi
1654 }
1655 \def\ZREF@STAR{*}
1656 \def\ZREF@NAME@top{top}
1657 \def\ZREF@NAME@first{first}
1658 \def\ZREF@NAME@bot{bot}
1659 \def\ZREF@MARKS@DefineProp#1{%
1660   \zref@ifpropundefined{#1\ZREF@TempName}{%
1661     \ifnum\ZREF@TempNum=\ltx@zero
1662       \begingroup
1663       \edef\x{\endgroup
1664         \noexpand\zref@newprop*{#1\ZREF@TempName}[] {%
1665           \expandafter\noexpand\csname#1mark\endcsname
1666         }%
1667       }%
1668     \x

```

```

1669     \else
1670     \begingroup
1671     \edef\x{\endgroup
1672     \noexpand\zref@newprop*{#1\ZREF@TempName}[]{%
1673     \expandafter\noexpand\csname#1marks\endcsname
1674     \ZREF@TempNum
1675     }%
1676     }%
1677     \x
1678     \fi
1679 }{%
1680 \PackageWarning{zref-marks}{%
1681 \string\zref@marks@register\ltx@space does not generate the%
1682 \MessageBreak
1683 new property ‘#1\ZREF@TempName’, because\MessageBreak
1684 it is already defined%
1685 }%
1686 }%
1687 }
1688 </marks>

```

### 6.13 Module runs

This module does not use the label-reference-system. The reference changes with each  $\LaTeX$  run and would force a rerun warning always.

```

1689 <*runs>
1690 \NeedsTeXFormat{LaTeX2e}
1691 \ProvidesPackage{zref-runs}%
1692 [2022-03-08 v2.33 Module runs for zref (H0)]%

```

$\backslash$ zruns

```

1693 \providecommand*{\zruns}{0}%
1694 \AtBeginDocument{%
1695 \edef\zruns{\number\numexpr\zruns+1}%
1696 \begingroup
1697 \def\on@line{}%
1698 \PackageInfo{zref-runs}{LaTeX runs: \zruns}%
1699 \if@filesw
1700 \immediate\write\@mainaux{%
1701 \string\gdef\string\zruns{\zruns}%
1702 }%
1703 \fi
1704 \endgroup
1705 }
1706 </runs>

```

### 6.14 Module perpage

```

1707 <*perpage>
1708 \NeedsTeXFormat{LaTeX2e}
1709 \ProvidesPackage{zref-perpage}%
1710 [2022-03-08 v2.33 Module perpage for zref (H0)]%
1711 \RequirePackage{zref-base}[2019/11/29]
1712 \ifx\ZREF@base@ok Y%
1713 \else
1714 \expandafter\endinput
1715 \fi

```

This module resets a counter at page boundaries. Because of the asynchronous output routine page counter properties cannot be asked directly, references are necessary.

For detecting changed pages module `abspage` is loaded.

1716 \RequirePackage{zref-abspage}[2019/11/29]

We group the properties for the needed references in the property list `perpage`. The property `pagevalue` records the correct value of the page counter.

```
1717 \ZREF@NewPropPageValue
1718 \zref@newlist{perpage}
1719 \zref@addprops{perpage}{abspage,page,pagevalue}
```

The page value, known by the reference mechanism, will be stored in counter `zpage`.

```
1720 \newcounter{zpage}
```

Counter `zref@unique` helps in generating unique reference names.

```
1721 \zref@require@unique
```

In order to be able to reset the counter, we hook here into `\stepcounter`. In fact two nested hooks are used to allow other packages to use the first hook at the beginning of `\stepcounter`.

```
1722 \let\ZREF@org@stepcounter\stepcounter
1723 \def\stepcounter#1{%
1724   \ifcsname @stepcounterhook@#1\endcsname
1725     \csname @stepcounterhook@#1\endcsname
1726   \fi
1727   \ZREF@org@stepcounter{#1}%
1728 }
```

If `amstext` is loaded it overwrites the definition (or we overwrite their definition) so we account for this by using a package hook, see <https://github.com/ho-tex/zref/issues/11>.

```
1729 \IfFormatAtLeastTF{2020/10/01}{
1730   {
1731     \AddToHook{package/amstext/after}{
1732       {\def\stepcounter#1{%
1733         \iffirstchoice@
1734         \ifcsname @stepcounterhook@#1\endcsname
1735           \csname @stepcounterhook@#1\endcsname
1736         \fi
1737         \addtocounter{#1}\@ne
1738         \begingroup \let\@elt\@stpelt \csname cl@#1\endcsname \endgroup
1739         \fi
1740       }}
1741   }{}
1742 %   \end{macrocode}
1743 %
1744 %
1745 %   \cs{@stpelt} must be adapted due to the change in latex
1746 %   2015-01, see https://github.com/ho-tex/zref/issues/26
1747 %   \begin{macrocode}
1748 \let\ZREF@org@@stpelt\@stpelt
1749 \def\@stpelt#1{%
1750   \ifcsname ZREF@perpage@#1\endcsname
1751     \begingroup
1752       \let\stepcounter\ZREF@org@stepcounter
1753       \ZREF@org@@stpelt{#1}%
1754     \endgroup
1755     \expandafter\ltx@gobbletwo
1756   \fi
1757   \ZREF@org@@stpelt{#1}%
1758 }
```

`\zmakeperpage` Makro `\zmakeperpage` resets a counter at each page break. It uses the same syntax and semantics as `\MakePerPage` from package `perpage` [5]. The initial start value can be given by the optional argument. Default is one that means after the first `\stepcounter` on a new page the counter starts with one.

```
1759 \ZREF@IfDefinable\zmakeperpage\def{%
```

```

1760 {%
1761   \@ifnextchar[\ZREF@makeperpage@opt{\ZREF@@makeperpage[\ltx@zero]}%
1762 }%
1763 }

```

We hook before the counter is incremented in `\stepcounter`, package `perpage` afterwards. Thus a little calculation is necessary.

```

1764 \def\ZREF@makeperpage@opt[#1]{%
1765   \begingroup
1766     \edef\x{\endgroup
1767       \noexpand\ZREF@@makeperpage[\number\numexpr#1-1\relax]%
1768     }%
1769   \x
1770 }

1771 \def\ZREF@@makeperpage[#1]#2{%
1772   \@ifundefined{@stepcounterhook@#2}{%
1773     \expandafter\gdef\csname @stepcounterhook@#2\endcsname{%
1774   }%
1775   \expandafter\gdef\csname ZREF@perpage@#2\endcsname{%
1776     \ZREF@@perpage@step{#2}{#1}%
1777   }%
1778   \expandafter\g@addto@macro\csname @stepcounterhook@#2\endcsname{%
1779     \ifcsname ZREF@perpage@#2\endcsname
1780       \csname ZREF@perpage@#2\endcsname
1781     \fi
1782   }%
1783 }

```

`\ZREF@@perpage@step` The heart of this module follows.

```

1784 \def\ZREF@@perpage@step#1#2{%

```

First the reference is generated.

```

1785   \global\advance\c@zref@unique\ltx@one
1786   \begingroup
1787     \expandafter
1788     \zref@labelbylist\expandafter{\thezref@unique}{perpage}%

```

The `\expandafter` commands are necessary, because `\ZREF@temp` is also used inside of `\zref@labelbylist`.

The evaluation of the reference follows. If the reference is not yet known, we use the page counter as approximation.

```

1789   \zref@ifrefundefined\thezref@unique{%
1790     \global\c@zpage=\c@page
1791     \global\let\thezpage\thepage
1792     \expandafter\xdef\csname ZREF@abspage@#1\endcsname{%
1793       \number\c@abspage
1794     }%
1795   }%

```

The reference is used to set `\thezpage` and counter `zpage`.

```

1796     \global\c@zpage=\zref@extract\thezref@unique{pagevalue}\relax
1797     \xdef\thezpage{\noexpand\zref@extract{\thezref@unique}{page}}%
1798     \expandafter\xdef\csname ZREF@abspage@#1\endcsname{%
1799       \zref@extractdefault\thezref@unique
1800         {abspage}{\number\c@abspage}%
1801     }%
1802   }%

```

Page changes are detected by a changed absolute page number.

```

1803     \expandafter\ifx\csname ZREF@abspage@#1\endcsname
1804       \csname ZREF@currentabspage@#1\endcsname
1805     \else
1806       \global\csname c@#1\endcsname=#2\relax

```

```

1807     \global\expandafter\let
1808     \csname ZREF@currentabspage@#1\expandafter\endcsname
1809     \csname ZREF@abspage@#1\endcsname
1810     \fi
1811 \endgroup
1812 }

```

`\zunmakeperpage` Macro `\zunmakeperpage` cancels the effect of `\zmakeperpage`.

```

1813 \ZREF@ifDefinable\zunmakeperpage\def{%
1814   #1{%
1815     \global\expandafter
1816     \let\csname ZREF@perpage@#1\endcsname\@undefined
1817   }%
1818 }

1819 </perpage>

```

## 6.15 Module `titleref`

```

1820 <*titleref>
1821 \NeedsTeXFormat{LaTeX2e}
1822 \ProvidesPackage{zref-titleref}%
1823 [2022-03-08 v2.33 Module titleref for zref (HO)]%
1824 \RequirePackage{zref-base}[2019/11/29]
1825 \ifx\ZREF@base@ok Y%
1826 \else
1827   \expandafter\endinput
1828 \fi
1829 \RequirePackage{getttitlestring}[2009/12/08]

```

### 6.15.1 Implementation

```
1830 \RequirePackage{keyval}
```

This module makes section and caption titles available for the reference system. It uses some of the ideas of package `nameref` and `titleref`.

Now we can add the property `title` is added to the main property list.

```

1831 \ZREF@NewPropTitle
1832 \zref@addprop\ZREF@mainlist{title}%

```

The title strings go into the `.aux` file, thus they need some kind of protection. Package `titleref` uses a protected expansion method. The advantage is that this can be used to cleanup the string and to remove `\label`, `\index` and other macros unwanted for referencing. But there is the risk that fragile stuff can break.

Therefore package `nameref` does not expand the string. Thus the entries can safely be written to the `.aux` file. But potentially dangerous macros such as `\label` remain in the string and can cause problems when using the string in references.

`\ifzref@titleref@expand` The switch `\ifzref@titleref@expand` distinguishes between the both methods. Package `nameref`'s behaviour is achieved by setting the switch to false, otherwise `titleref`'s expansion is used. Default is false.

```
1833 \newif\ifzref@titleref@expand
```

`\ZREF@titleref@hook` The hook `\ZREF@titleref@hook` allows to extend the cleanup for the expansion method. Thus unnecessary macros can be removed or dangerous commands removed. The hook is executed before the expansion of `\zref@titleref@current`.

```
1834 \let\ZREF@titleref@hook\ltx@empty
```

`\zref@titleref@cleanup` The hook should not be used directly, instead we provide the macro `\zref@titleref@cleanup` to add stuff to the hook and prevents that a previous non-empty content is not discarded accidentally.

```

1835 \ZREF@Robust\def\zref@titleref@cleanup#1{%
1836   \begingroup
1837   \toks@\expandafter{%

```

```

1838     \ZREF@titleref@hook
1839     #1%
1840 }%
1841 \expandafter\endgroup
1842 \expandafter\def\expandafter\ZREF@titleref@hook\expandafter{%
1843     \the\toks@
1844 }%
1845 }%

```

`\ifzref@titleref@stripperperiod` Sometimes a title contains a period at the end. Package `nameref` removes this. This behaviour is controlled by the switch `\ifzref@titleref@stripperperiod` and works regardless of the setting of option `expand`. Period stripping is the default.

```

1846 \newif\ifzref@titleref@stripperperiod
1847 \zref@titleref@stripperperiodtrue

```

`\zref@titleref@setcurrent` Macro `\zref@titleref@setcurrent` sets a new current title stored in `\zref@titleref@current`. Some cleanup and expansion is performed that can be controlled by the previous switches.

```

1848 \ZREF@Robust\def\zref@titleref@setcurrent#1{%
1849     \ifzref@titleref@expand
1850         \GetTitleStringExpand{#1}%
1851     \else
1852         \GetTitleStringNonExpand{#1}%
1853     \fi
1854     \edef\zref@titleref@current{%
1855         \detokenize\expandafter{\GetTitleStringResult}%
1856     }%
1857     \ifzref@titleref@stripperperiod
1858         \edef\zref@titleref@current{%
1859             \expandafter\ZREF@stripperperiod\zref@titleref@current
1860             \ltx@empty.\ltx@empty\@nil
1861         }%
1862     \fi
1863 }%
1864 \GetTitleStringDisableCommands{%
1865     \ZREF@titleref@hook
1866 }

```

`\ZREF@stripperperiod` If `\ZREF@stripperperiod` is called, the argument consists of space tokens and tokens with catcode 12 (other), because of  $\varepsilon$ -TeX's `\detokenize`.

```

1867 \def\ZREF@stripperperiod#1.\ltx@empty#2\@nil{#1}%

```

### 6.15.2 User interface

`\ztitlerefsetup` The behaviour of module `titleref` is controlled by switches and a hook. They can be set by `\ztitlerefsetup` with a key value interface, provided by package `keyval`. Also the current title can be given explicitly by the key `title`.

```

1868 \define@key{ZREF@TR}{expand}[true]{%
1869     \csname zref@titleref@expand#1\endcsname
1870 }%
1871 \define@key{ZREF@TR}{stripperperiod}[true]{%
1872     \csname zref@titleref@stripperperiod#1\endcsname
1873 }%
1874 \define@key{ZREF@TR}{cleanup}{%
1875     \zref@titleref@cleanup{#1}%
1876 }%
1877 \define@key{ZREF@TR}{title}{%
1878     \def\zref@titleref@current{#1}%
1879 }%
1880 \ZREF@IfDefinable\ztitlerefsetup\def{%
1881     {\kvsetkeys{ZREF@TR}}}%
1882 }%

```

`\ztitleref` The user command `\ztitleref` references the title. For safety `\label` is disabled to prevent multiply defined references.

```

1883 \ZREF@ifDefinable\ztitleref\def{%
1884   {\zref@wrapper@babel\ZREF@titleref}%
1885 }%
1886 \def\ZREF@titleref#1{%
1887   \begingroup
1888     \zref@refused{#1}%
1889     \let\label\ltx@gobble
1890     \zref@extract{#1}{title}%
1891   \endgroup
1892 }%
```

### 6.15.3 Patches for section and caption commands

The section and caption macros are patched to extract the title data.

Captions of figures and tables.

```

1893 \AtBeginDocument{%
1894   \ZREF@patch{@caption}{%
1895     \long\def\@caption#1[#2]{%
1896       \zref@titleref@setcurrent{#2}%
1897       \ZREF@org@@caption{#1}[{#2}]%
1898     }%
1899   }%
```

Section commands without star. The title version for the table of contents is used because it is usually shorter and more robust.

```

1900   \ZREF@patch{@part}{%
1901     \def\@part[#1]{%
1902       \zref@titleref@setcurrent{#1}%
1903       \ZREF@org@@part[{#1}]%
1904     }%
1905   }%
1906   \ZREF@patch{@chapter}{%
1907     \def\@chapter[#1]{%
1908       \zref@titleref@setcurrent{#1}%
1909       \ZREF@org@@chapter[{#1}]%
1910     }%
1911   }%
1912   \ZREF@patch{@sect}{%
1913     \def\@sect#1#2#3#4#5#6[#7]{%
1914       \zref@titleref@setcurrent{#7}%
1915       \ZREF@org@@sect{#1}{#2}{#3}{#4}{#5}{#6}[{#7}]%
1916     }%
1917   }%
```

The star versions of the section commands.

```

1918   \ZREF@patch{@spart}{%
1919     \def\@spart#1{%
1920       \zref@titleref@setcurrent{#1}%
1921       \ZREF@org@@spart{#1}%
1922     }%
1923   }%
1924   \ZREF@patch{@schapter}{%
1925     \def\@schapter#1{%
1926       \zref@titleref@setcurrent{#1}%
1927       \ZREF@org@@schapter{#1}%
1928     }%
1929   }%
1930   \ZREF@patch{@ssect}{%
1931     \def\@ssect#1#2#3#4#5{%
1932       \zref@titleref@setcurrent{#5}%
1933       \ZREF@org@@ssect{#1}{#2}{#3}{#4}{#5}%

```

```

1934 }%
1935 }%

```

#### 6.15.4 Environment description

```

1936 \ZREF@patch{descriptionlabel}{%
1937   \def\descriptionlabel#1{%
1938     \zref@titleref@setcurrent{#1}%
1939     \ZREF@org@descriptionlabel{#1}%
1940   }%
1941 }%

```

#### 6.15.5 Class memoir

```

1942 \@ifclassloaded{memoir}{%
1943   \ltx@ifundefined{ifheadnameref}{}{%
1944     \def\@chapter[#1]#2{%
1945       \ltx@ifundefined{ch@pt@c}{%
1946         \zref@titleref@setcurrent{#1}%
1947       }{%
1948         \ifx\ch@pt@c\ltx@empty
1949           \zref@titleref@setcurrent{#2}%
1950         \else
1951           \def\NR@temp{#1}%
1952           \ifx\NR@temp\ltx@empty
1953             \expandafter\zref@titleref@setcurrent
1954             \expandafter{\ch@pt@c}%
1955           \else
1956             \ifheadnameref
1957               \zref@titleref@setcurrent{#1}%
1958             \else
1959               \expandafter\zref@titleref@setcurrent
1960               \expandafter{\ch@pt@c}%
1961             \fi
1962           \fi
1963         \fi
1964       }%
1965       \ZREF@org@@chapter[{#1}]{#2}%
1966     }%
1967     \ZREF@patch{M@sect}{%
1968       \def\M@sect#1#2#3#4#5#6[#7][#8]{%
1969         \ifheadnameref
1970           \zref@titleref@setcurrent{#8}%
1971         \else
1972           \zref@titleref@setcurrent{#7}%
1973         \fi
1974         \ZREF@org@M@sect{#1}{#2}{#3}{#4}{#5}{#6}[{#7}][{#8}]%
1975       }%
1976     }%
1977   }%
1978 }{}%

```

#### 6.15.6 Class beamer

```

1979 \@ifclassloaded{beamer}{%
1980   \ZREF@patch{beamer@section}{%
1981     \long\def\beamer@section[#1]{%
1982       \zref@titleref@setcurrent{#1}%
1983       \ZREF@org@beamer@section[{#1}]%
1984     }%
1985   }%
1986   \ZREF@patch{beamer@subsection}{%
1987     \long\def\beamer@subsection[#1]{%
1988       \zref@titleref@setcurrent{#1}%
1989       \ZREF@org@beamer@subsection[{#1}]%

```

```

1990     }%
1991 }%
1992 \ZREF@patch{beamer@subsubsection}{%
1993     \long\def\beamer@subsubsection[#1]{%
1994         \zref@titleref@setcurrent{#1}%
1995         \ZREF@org@beamer@subsubsection[#{1}]%
1996     }%
1997 }%
1998 }{}%

```

### 6.15.7 Package titlesec

```

1999 \@ifpackageloaded{titlesec}{%
2000     \ZREF@patch{ttl@sect@i}{%
2001         \def\ttl@sect@i#1#2[#3]#4{%
2002             \zref@titleref@setcurrent{#4}%
2003             \ZREF@org@ttl@sect@i{#1}{#2}[#{3}]{#4}%
2004         }%
2005     }%
2006 \ZREF@patch{ttl@straight@i}{%
2007     \def\ttl@straight@i#1[#2]#3{%
2008         \def\ZREF@temp{#2}%
2009         \ifx\ZREF@temp\ltx@empty
2010             \zref@titleref@setcurrent{#3}%
2011         \else
2012             \zref@titleref@setcurrent{#2}%
2013         \fi
2014         \ZREF@org@ttl@straight@i{#1}[#{2}]{#3}%
2015     }%
2016 }%
2017 }{}%

```

### 6.15.8 Package longtable

Package longtable: some support for its \caption. However \label inside the caption is not supported.

```

2018 \@ifpackageloaded{longtable}{%
2019     \ZREF@patch{LT@c@ption}{%
2020         \def\LT@c@ption#1[#2]#3{%
2021             \ZREF@org@LT@c@ption{#1}[#{2}]{#3}%
2022             \zref@titleref@setcurrent{#2}%
2023         }%
2024     }%
2025 }{}%

```

### 6.15.9 Package listings

Package listings: support for its caption.

```

2026 \@ifpackageloaded{listings}{%
2027     \ZREF@patch{lst@MakeCaption}{%
2028         \def\lst@MakeCaption{%
2029             \ifx\lst@label\ltx@empty
2030             \else
2031                 \expandafter\zref@titleref@setcurrent\expandafter{%
2032                     \lst@caption
2033                 }%
2034             \fi
2035             \ZREF@org@lst@MakeCaption
2036         }%
2037     }%
2038 }{}%

```

### 6.15.10 Theorems

```

2039 \ZREF@patch{@opargbegintheorem}{%
2040   \def\@opargbegintheorem#1#2#3{%
2041     \zref@titleref@setcurrent{#3}%
2042     \ZREF@org@@opargbegintheorem{#1}{#2}{#3}%
2043   }%
2044 }%
2045 \@ifpackageloaded{amsthm}{%
2046   \begingroup
2047     \edef\x{macro:\string#1\string#2[\string#3]}%
2048     \@onelevel@sanitize\x
2049     \def\y#1->#2\@nil{#1}%
2050     \edef\z{\expandafter\y\meaning\@begintheorem->\@nil}%
2051     \@onelevel@sanitize\z
2052     \expandafter\endgroup
2053     \ifx\x\z
2054       \ZREF@patch{@begintheorem}{%
2055         \def\@begintheorem#1#2[#3]{%
2056           \zref@titleref@setcurrent{#3}%
2057           \ZREF@org@@begintheorem{#1}{#2}[%3]}%
2058         }%
2059       }%
2060     \fi
2061   }{}%
2062 }
2063 </titleref>

```

## 6.16 Module xr

```

2064 <*xr>
2065 \NeedsTeXFormat{LaTeX2e}
2066 \ProvidesPackage{zref-xr}%
2067   [2022-03-08 v2.33 Module xr for zref (H0)]%
2068 \RequirePackage{zref-base}[2019/11/29]
2069 \ifx\ZREF@base@ok Y%
2070 \else
2071   \expandafter\endinput
2072 \fi

2073 \RequirePackage{keyval}
2074 \RequirePackage{kvoptions}[2010/02/22]

```

We declare property `url`, because this is added, if a reference is imported and has not already set this field. Or if `hyperref` is used, then this property can be asked.

```

2075 \zref@newprop{url}{}%
2076 \zref@newprop{urluse}{}%
2077 \zref@newprop{externaldocument}{}%

```

Most code, especially the handling of the `.aux` files are taken from David Carlisle's `xr` package. Therefore I drop the documentation for these macros here.

`\zref@xr@ext` If the URL is not specied, then assume processed file with a guessed extension. Use the setting of `hyperref` if available.

```

2078 \providecommand*{\zref@xr@ext}{}%
2079 \ltx@ifundefined{XR@ext}{pdf}{\XR@ext}%
2080 }%

```

`\ifZREF@xr@zreflabel` The use of the star form of `\xexternaldocument` is remembered in the switch `\ifZREF@xr@zreflabel`.

```

2081 \newif\ifZREF@xr@zreflabel

```

```

2082 \SetupKeyvalOptions{%
2083   family=ZREF@XR,%
2084   prefix=ZREF@xr%

```

```

2085 }
2086 \DeclareBoolOption[true]{tozreflabel}
2087 \DeclareBoolOption[false]{toltxlabel}
2088 \DeclareBoolOption{verbose}
2089 \define@key{ZREF@XR}{ext}{%
2090   \def\zref@xr@{#1}%
2091 }
2092 \DeclareBoolOption[false]{urluse}

\zxrsetup
2093 \newcommand*{\zxrsetup}{%
2094   \kvsetkeys{ZREF@XR}%
2095 }%

\ZREF@xr@URL
2096 \newcount\ZREF@xr@URL
2097 \ZREF@xr@URL=\ltx@zero

\ZREF@xr@AddURL
2098 \def\ZREF@xr@AddURL#1{%
2099   \begingroup
2100     \def\ZREF@temp{#1}%
2101     \count@=\ltx@one
2102     \ZREF@xr@@AddUrl
2103   \endgroup
2104 }

\ZREF@xr@@AddUrl
2105 \def\ZREF@xr@@AddUrl{%
2106   \ifnum\count@>\ZREF@xr@URL
2107     \global\advance\ZREF@xr@URL by\ltx@one
2108     \xdef\ZREF@xr@theURL{\romannumeral\ZREF@xr@URL}%
2109     \global\expandafter\let
2110       \csname Z@U@\ZREF@xr@theURL\endcsname\ZREF@temp
2111     \@PackageInfo{zref-xr}{%
2112       \ltx@backslashchar Z@U@\ZREF@xr@theURL:\MessageBreak
2113       \ZREF@temp\MessageBreak
2114     }%
2115   \else
2116     \expandafter
2117       \ifx\csname Z@U@\romannumeral\count@\endcsname\ZREF@temp
2118         \xdef\ZREF@xr@theURL{\romannumeral\count@}%
2119       \else
2120         \expandafter\expandafter\expandafter\ZREF@xr@@AddUrl
2121       \fi
2122   \fi
2123 }

\zexternaldocument In its star form it looks for \newlabel, otherwise for \zref@newlabel. Later we
will read .aux files that expects @ to have catcode 11 (letter).
2124 \ZREF@ifDefinable\zexternaldocument\def{%
2125   {%
2126     \ZREF@NewPropAnchor
2127     \ZREF@NewPropTitle
2128     \begingroup
2129       \csname @safe@actives@true\endcsname
2130       \makeatletter
2131       \@ifstar{%
2132         \ZREF@xr@zreflabelfalse
2133         \@testopt\ZREF@xr@externaldocument{}%
2134       }{%
2135         \ZREF@xr@zreflabeltrue

```

```

2136      \@testopt\ZREF@xr@externaldocument{%
2137      }%
2138  }%
2139 }%

```

If the `\include` featurer was used, there can be several `.aux` files. These files are read one after another, especially they are not recursively read in order to save read registers. Thus it can happen that the read order of the `newlabel` commands differs from L<sup>A</sup>T<sub>E</sub>X's order using `\input`.

`\ZREF@xr@externaldocument` It reads the remaining arguments. `\newcommand` comes in handy for the optional argument.

```

2140 \def\ZREF@xr@externaldocument[#1]#2{%
2141     \def\ZREF@xr@prefix{#1}%
2142     \let\ZREF@xr@filelist\ltx@empty
2143     \edef\ZREF@xr@externalfile{#2}%
2144     \edef\ZREF@xr@file{\ZREF@xr@externalfile.aux}%
2145     \filename@parse{#2}%
2146     \@testopt\ZREF@xr@graburl{#2.\zref@xr@ext}%
2147 }%
2148 \def\ZREF@xr@graburl[#1]{%
2149     \edef\ZREF@xr@url{#1}%
2150     \ifZREF@xr@urluse
2151         \expandafter\ZREF@xr@AddURL\expandafter{\ZREF@xr@url}%
2152     \expandafter\def\expandafter\ZREF@xr@url
2153         \expandafter{\csname Z@U@ZREF@xr@theURL\endcsname}%
2154     \fi
2155     \ZREF@xr@checkfile
2156 \endgroup
2157 }%

```

`\ZREF@xr@processfile` We follow `xr` here, `\IfFileExists` offers a nicer test, but we have to open the file anyway.

```

2158 \def\ZREF@xr@checkfile{%
2159     \openin\@inputcheck\ZREF@xr@file\relax
2160     \ifeof\@inputcheck
2161         \PackageWarning{zref-xr}{%
2162             File ‘\ZREF@xr@file’ not found or empty,\MessageBreak
2163             labels not imported%
2164         }%
2165     \else
2166         \PackageInfo{zref-xr}{%
2167             Label \ifZREF@xr@zreflabel (zref) \fi
2168             import from ‘\ZREF@xr@file’%
2169         }%
2170     \def\ZREF@xr@found{0}%
2171     \def\ZREF@xr@ignored@empty{0}%
2172     \def\ZREF@xr@ignored@zref{0}%
2173     \def\ZREF@xr@ignored@ltx{0}%
2174     \ZREF@xr@processfile
2175     \closein\@inputcheck
2176     \begingroup
2177         \let\on@line\ltx@empty
2178         \PackageInfo{zref-xr}{%
2179             Statistics for ‘\ZREF@xr@file’:\MessageBreak
2180             \ZREF@xr@found\space
2181             \ifZREF@xr@zreflabel zref\else LaTeX\fi\space
2182             label(s) found%
2183             \ifnum\ZREF@xr@ignored@empty>0 %
2184                 ,\MessageBreak
2185                 \ZREF@xr@ignored@empty\space empty label(s) ignored%
2186             \fi

```

```

2187 \ifnum\ZREF@xr@ignored@zref>0 %
2188 ,\MessageBreak
2189 \ZREF@xr@ignored@zref\space
2190 duplicated zref label(s) ignored%
2191 \fi
2192 \ifnum\ZREF@xr@ignored@ltx>0 %
2193 ,\MessageBreak
2194 \ZREF@xr@ignored@ltx\space
2195 duplicated latex label(s) ignored%
2196 \fi
2197 }%
2198 \endgroup
2199 \fi
2200 \ifx\ZREF@xr@filelist\ltx@empty
2201 \else
2202 \edef\ZREF@xr@file{%
2203 \expandafter\ltx@car\ZREF@xr@filelist\@nil
2204 }%
2205 \edef\ZREF@xr@filelist{%
2206 \expandafter\ltx@cdr\ZREF@xr@filelist\ltx@empty\@nil
2207 }%
2208 \expandafter\ZREF@xr@checkfile
2209 \fi
2210 }%

```

\ZREF@xr@processfile

```

2211 \def\ZREF@xr@processfile{%
2212 \read\@inputcheck to\ZREF@xr@line
2213 \expandafter\ZREF@xr@processline\ZREF@xr@line..\ZREF@nil
2214 \ifeof\@inputcheck
2215 \else
2216 \expandafter\ZREF@xr@processfile
2217 \fi
2218 }%

```

\ZREF@xr@processline The most work must be done for analyzing the arguments of \newlabel.

```

2219 \long\def\ZREF@xr@processline#1#2#3\ZREF@nil{%
2220 \def\x{#1}%
2221 \toks@{#2}%
2222 \ifZREF@xr@zreflabel
2223 \ifx\x\ZREF@xr@zref@newlabel
2224 \expandafter
2225 \ZREF@xr@process@zreflabel\ZREF@xr@line...\ZREF@nil
2226 \fi
2227 \else
2228 \ifx\x\ZREF@xr@newlabel
2229 \expandafter
2230 \ZREF@xr@process@label\ZREF@xr@line...[]\ZREF@nil
2231 \fi
2232 \fi
2233 \ifx\x\ZREF@xr@@input
2234 \edef\ZREF@xr@filelist{%
2235 \etex@unexpanded\expandafter{\ZREF@xr@filelist}%
2236 {\filename@area\the\toks@}%
2237 }%
2238 \fi
2239 }%
2240 \def\ZREF@xr@process@zreflabel\zref@newlabel#1#2#3\ZREF@nil{%
2241 \edef\ZREF@xr@refname{Z@R@\ZREF@xr@prefix#1}%
2242 \edef\ZREF@xr@found{\the\numexpr\ZREF@xr@found+1\relax}%
2243 \def\x{#2}%
2244 \edef\ZREF@xr@tempname{$temp$}%
2245 \edef\ZREF@xr@temprefname{Z@R@\ZREF@xr@tempname}%

```

```

2246 \let\ZREF@xr@list\x
2247 \ifx\ZREF@xr@list\ltx@empty
2248   \PackageWarningNoLine{zref-xr}{%
2249     Label '#1' without properties ignored\MessageBreak
2250     in file '\ZREF@xr@file'%
2251   }%
2252   \edef\ZREF@xr@ignored@empty{%
2253     \the\numexpr\ZREF@xr@ignored@empty+1\relax
2254   }%
2255 \else
2256   \expandafter\ZREF@xr@checklist\x\ZREF@nil
2257   \expandafter\let\csname\ZREF@xr@temprefname\endcsname\x
2258   \expandafter\ltx@LocalAppendToMacro
2259   \csname\ZREF@xr@temprefname\expandafter\endcsname
2260   \expandafter{%
2261     \expandafter\externaldocument\expandafter{%
2262       \ZREF@xr@externalfile
2263     }%
2264   }%
2265   \ZREF@xr@urlcheck\ZREF@xr@tempname
2266   \ifZREF@xr@tozreflabel
2267     \@ifundefined{\ZREF@xr@refname}{%
2268       \ifZREF@xr@verbose
2269         \PackageInfo{zref-xr}{%
2270           Import to zref label '\ZREF@xr@tempname#1'%
2271         }%
2272       \fi
2273       \global\expandafter
2274       \let\csname\ZREF@xr@refname\expandafter\endcsname
2275       \csname\ZREF@xr@temprefname\endcsname
2276     }{%
2277       \ZREF@xr@zref@ignorewarning{\ZREF@xr@prefix#1}%
2278     }%
2279   \fi
2280   \ifZREF@xr@toltxlabel
2281     \ZREF@xr@tolabel{\ZREF@xr@tempname}{\ZREF@xr@prefix#1}%
2282   \fi
2283 \fi
2284 }%
2285 \def\ZREF@xr@process@label\newlabel#1#2#3[#4]#5\ZREF@nil{%
2286   \def\ZREF@xr@refname{Z@R@{\ZREF@xr@prefix#1}%
2287   \edef\ZREF@xr@found{\the\numexpr\ZREF@xr@found+1\relax}%
2288   \def\x{#2}%
2289   \edef\ZREF@xr@tempname{$temp$}%
2290   \edef\ZREF@xr@temprefname{Z@R@{\ZREF@xr@tempname}%
2291   \expandafter\ZREF@xr@scanparams
2292     \csname\ZREF@xr@temprefname\expandafter\endcsname
2293     \x{}{}{}{}{}\ZREF@nil
2294   \ifx\\#4\\%
2295   \else
2296     % ntheorem knows an optional argument at the end of \newlabel
2297     \ZREF@NewPropTheotype
2298     \expandafter\ltx@LocalAppendToMacro
2299     \csname\ZREF@xr@temprefname\endcsname{\theotype{#4}}%
2300   \fi
2301   \expandafter\ltx@LocalAppendToMacro
2302   \csname\ZREF@xr@temprefname\expandafter\endcsname\expandafter{%
2303     \expandafter\externaldocument\expandafter{%
2304       \ZREF@xr@externalfile
2305     }%
2306   }%
2307   \ZREF@xr@urlcheck\ZREF@xr@tempname

```

```

2308 \ifZREF@xr@tozreflabel
2309   \@ifundefined{ZREF@xr@refname}{%
2310     \ifZREF@xr@verbose
2311       \PackageInfo{zref-xr}{%
2312         Import to zref label ‘\ZREF@xr@prefix#1’%
2313       }%
2314     \fi
2315     \global\expandafter
2316     \let\csname\ZREF@xr@refname\expandafter\endcsname
2317     \csname\ZREF@xr@temprefname\endcsname
2318   }{%
2319     \ZREF@xr@zref@ignorewarning{\ZREF@xr@prefix#1}%
2320   }%
2321 \fi
2322 \ifZREF@xr@toltxlabel
2323   \ZREF@xr@tolabel{\ZREF@xr@tempname}{\ZREF@xr@prefix#1}%
2324 \fi
2325 }
2326 \def\ZREF@xr@zref@newlabel{\zref@newlabel}%
2327 \def\ZREF@xr@newlabel{\newlabel}%
2328 \def\ZREF@xr@input{\@input}%
2329 \def\ZREF@xr@relax{\relax}%

```

\ZREF@xr@tolabel

```

2330 \def\ZREF@xr@tolabel#1#2{%
2331   \ifZREF@xr@verbose
2332     \PackageInfo{zref-xr}{%
2333       Import to LaTeX label ‘#2’%
2334     }%
2335   \fi
2336   \zref@wrapper@unexpanded{%
2337     \expandafter\xdef\csname r@#2\endcsname{%
2338       {%
2339         \ltx@ifundefined{M@TitleReference}{%
2340           \ltx@ifundefined{TR@TitleReference}{%
2341             \zref@extractdefault{#1}{default}{}}%
2342           {%
2343             \noexpand\TR@TitleReference
2344             {\zref@extractdefault{#1}{default}{}}%
2345             {\zref@extractdefault{#1}{title}{}}%
2346           }%
2347         }{%
2348           \noexpand\M@TitleReference
2349           {\zref@extractdefault{#1}{default}{}}%
2350           {\zref@extractdefault{#1}{title}{}}%
2351         }%
2352       }%
2353     {\zref@extractdefault{#1}{page}{}}%
2354   \ltx@ifpackageloaded{nameref}{%
2355     {\zref@extractdefault{#1}{title}{}}%
2356     {\zref@extractdefault{#1}{anchor}{}}%
2357     \zref@ifrefcontainsprop{#1}{urluse}{%
2358       {\zref@extractdefault{#1}{urluse}{}}%
2359     }{%
2360       {\zref@extractdefault{#1}{url}{}}%
2361     }%
2362   }{}%
2363 }%
2364 }%
2365 }

```

\ZREF@xr@zref@ignorewarning

```

2366 \def\ZREF@xr@zref@ignorewarning#1{%
2367   \PackageWarningNoLine{zref-xr}{%
2368     Zref label ‘#1’ is already in use\MessageBreak
2369     in file ‘\ZREF@xr@file’%
2370   }%
2371   \edef\ZREF@xr@ignored@zref{%
2372     \the\numexpr\ZREF@xr@ignored@zref+1%
2373   }%
2374 }%

```

\ZREF@xr@ltx@ignorewarning

```

2375 \def\ZREF@xr@ltx@ignorewarning#1{%
2376   \PackageWarningNoLine{zref-xr}{%
2377     LaTeX label ‘#1’ is already in use\MessageBreak
2378     in file ‘\ZREF@xr@file’%
2379   }%
2380   \edef\ZREF@xr@ignored@ltx{%
2381     \the\numexpr\ZREF@xr@ignored@ltx+1%
2382   }%
2383 }%

```

\ZREF@xr@checklist

```

2384 \def\ZREF@xr@checklist#1#2#3\ZREF@nil{%
2385   \ifx\@undefined#1\relax
2386     \expandafter\ZREF@xr@checkkey\string#1\@nil
2387   \fi
2388   \ifx\#3\%
2389   \else
2390     \ltx@ReturnAfterFi{%
2391       \ZREF@xr@checklist#3\ZREF@nil
2392     }%
2393   \fi
2394 }%
2395 \def\ZREF@xr@checkkey#1#2\@nil{%
2396   \zref@ifpropundefined{#2}{%
2397     \zref@newprop{#2}{}%
2398   }{%
2399   }%

```

\ZREF@xr@scanparams

```

2400 \def\ZREF@xr@scanparams#1#2#3#4#5#6#7\ZREF@nil{%
2401   \let#1\ltx@empty
2402   \ZREF@foundfalse
2403   \ZREF@xr@scantitleref#1#2\TR@TitleReference{}{}\ZREF@nil
2404   \ifZREF@found
2405   \else
2406     \ltx@LocalAppendToMacro#1{\default{#2}}%
2407   \fi
2408   % page
2409   \ltx@LocalAppendToMacro#1{\page{#3}}%
2410   % nameref title
2411   \ifZREF@found
2412   \else
2413     \ifx\#4\%
2414     \else
2415       \def\ZREF@xr@temp{#4}%
2416       \ifx\ZREF@xr@temp\ZREF@xr@relax
2417       \else
2418         \ltx@LocalAppendToMacro#1{\title{#4}}%
2419       \fi
2420     \fi
2421   \fi

```

```

2422 % anchor
2423 \ifx\\#5\\%
2424 \else
2425   \ltx@LocalAppendToMacro#1{\anchor{#5}}%
2426 \fi
2427 \ifx\\#6\\%
2428 \else
2429   \ifZREF@xr@urluse
2430     \ZREF@xr@AddURL{#6}%
2431     \expandafter\ltx@LocalAppendToMacro\expandafter#1%
2432     \expandafter{%
2433       \expandafter\urluse\expandafter{%
2434         \csname Z@U@\ZREF@xr@theURL\endcsname
2435       }%
2436     }%
2437   \else
2438     \ltx@LocalAppendToMacro#1{\url{#6}}%
2439   \fi
2440 \fi
2441 }%

```

`\ZREF@xr@scantitleref`

```

2442 \def\ZREF@xr@scantitleref#1#2\TR@TitleReference#3#4#5\ZREF@nil{%
2443   \ifx\\#5\\%
2444   \else
2445     \ltx@LocalAppendToMacro#1{%
2446       \default{#3}%
2447       \title{#4}%
2448     }%
2449     \ZREF@foundtrue
2450   \fi
2451 }%

```

`\ZREF@xr@urlcheck`

```

2452 \def\ZREF@xr@urlcheck#1{%
2453   \zref@ifrefcontainsprop{#1}{anchor}{%
2454     \zref@ifrefcontainsprop{#1}{url}{%
2455       }{%
2456         \expandafter
2457         \ltx@LocalAppendToMacro\csname Z@R@#1\expandafter\endcsname
2458         \expandafter{%
2459           \csname url\ifZREF@xr@urluse use\fi
2460           \expandafter\endcsname\expandafter{\ZREF@xr@url}%
2461         }%
2462       }%
2463     }{%
2464     }%
2465   }%
2466 \</xr>

```

## 6.17 Module hyperref

UNFINISHED :-(

```

2467 <*hyperref>
2468 \NeedsTeXFormat{LaTeX2e}
2469 \ProvidesPackage{zref-hyperref}%
2470 [2022-03-08 v2.33 Module hyperref for zref (HO)]%
2471 \RequirePackage{zref-base}[2019/11/29]
2472 \ifx\ZREF@base@ok Y%
2473 \else
2474   \expandafter\endinput
2475 \fi

```

```

2476 \ZREF@NewPropAnchor
2477 \zref@addprop\ZREF@mainlist{anchor}%
2478 </hyperref>

```

## 6.18 Module savepos

Module `savepos` provides an interface for pdfTeX's `\pdfsavepos`, see the manual for pdfTeX.

### 6.18.1 Identification

```

2479 <*savepos>
2480 \NeedsTeXFormat{LaTeX2e}
2481 \ProvidesPackage{zref-savepos}%
2482 [2022-03-08 v2.33 Module savepos for zref (H0)]%
2483 \RequirePackage{zref-base}[2019/11/29]
2484 \ifx\ZREF@base@ok Y%
2485 \else
2486 \expandafter\endinput
2487 \fi

```

### 6.18.2 Availability

First we check, whether the feature is available.

```

2488 \ifx\directlua\@undefined
2489 \ltx@ifundefined{pdfsavepos}{%
2490 \PackageError\ZREF@name{%
2491 \string\pdfsavepos\space is not supported.\MessageBreak
2492 It is provided by pdfTeX (1.40) or XeTeX%
2493 }\ZREF@UpdatePdfTeX
2494 \endinput
2495 }{}%
2496 \fi

```

In PDF mode we are done. However support for DVI mode was added later in version 1.40.0. In earlier versions `\pdfsavepos` is defined, but its execution raises an error. Note that XeTeX also provides `\pdfsavepos`.

```

2497 \ifpdf
2498 \else
2499 \ltx@ifundefined{pdftexversion}{%
2500 }{%
2501 \ifnum\pdftexversion<140 %
2502 \PackageError\ZREF@name{%
2503 \string\pdfsavepos\space is not supported in DVI mode%
2504 \MessageBreak
2505 of this pdfTeX version%
2506 }\ZREF@UpdatePdfTeX
2507 \expandafter\expandafter\expandafter\endinput
2508 \fi
2509 }%
2510 \fi

```

### 6.18.3 Setup

```

2511 \zref@newlist{savepos}
2512 \ifx\directlua\@undefined
2513 \zref@newprop*{posx}[0]{\the\pdflastxpos}
2514 \zref@newprop*{posy}[0]{\the\pdflastypos}
2515 \else
2516 \zref@newprop*{posx}[0]{\the\lastxpos}
2517 \zref@newprop*{posy}[0]{\the\lastypos}
2518 \fi
2519 \zref@addprops{savepos}{posx,posy}

```

### 6.18.4 User macros

`\zref@savepos`

```

2520 \ifx\directlua\@undefined
2521   \def\zref@savepos{%
2522     \if@files
2523       \pdfsavepos
2524     \fi
2525   }
2526 \else
2527   \def\zref@savepos{%
2528     \if@files
2529       \savepos
2530     \fi
2531   }
2532 \fi

```

`\ZREF@zsavepos`

```

2533 \def\ZREF@zsavepos#1#2#3{%
2534   \@bsphack
2535   \if@files
2536     \zref@savepos
2537     #1{#3}{#2}%
2538     \ltx@ifundefined{TeXeTstate}{%
2539   }{%
2540     \ifnum\TeXeTstate=\ltx@zero
2541     \else
2542       \zref@savepos
2543     \fi
2544   }%
2545   \fi
2546   \@esphack
2547 }

```

`\zsavepos` The current location is stored in a reference with the given name.

```

2548 \ZREF@ifDefinable\zsavepos\def{%
2549   {%
2550     \ZREF@zsavepos\zref@labelbylist{savepos}%
2551   }%
2552 }

```

`\zsaveposx`

```

2553 \ZREF@ifDefinable\zsaveposx\def{%
2554   {%
2555     \ZREF@zsavepos\zref@labelbyprops{posx}%
2556   }%
2557 }

```

`\zsaveposy`

```

2558 \ZREF@ifDefinable\zsaveposy\def{%
2559   {%
2560     \ZREF@zsavepos\zref@labelbyprops{posy}%
2561   }%
2562 }

```

`\zposx` `\zposy` The horizontal and vertical position are available by `\zposx` and `\zposy`. Do not rely on absolute positions. They differ in DVI and PDF mode of pdfTeX. Use differences instead. The unit of the position numbers is sp.

```

2563 \newcommand*{\zposx}[1]{%
2564   \zref@extract{#1}{posx}%
2565 }%
2566 \newcommand*{\zposy}[1]{%

```

```

2567 \zref@extract{#1}{posy}%
2568 }%

```

Typically horizontal and vertical positions are used inside calculations. Therefore the extracting macros should be expandable and babel's patch is not applicable.

Also it is in the responsibility of the user to marked used positions by `\zrefused` in order to notify L<sup>A</sup>T<sub>E</sub>X about undefined references.

`\ZREF@savepos@ok`

```

2569 \let\ZREF@savepos@ok=Y
2570 </savepos>

```

## 6.19 Module `abspos`

### 6.19.1 Identification

```

2571 <*abspos>
2572 \NeedsTeXFormat{LaTeX2e}
2573 \ProvidesPackage{zref-abspos}%
2574 [2022-03-08 v2.33 Module abspos for zref (HO)]%
2575 \RequirePackage{zref-base}[2019/11/29]
2576 \ifx\ZREF@base@ok Y%
2577 \else
2578 \expandafter\endinput
2579 \fi

2580 \RequirePackage{zref-savepos}[2019/11/29]
2581 \ifx\ZREF@savepos@ok Y%
2582 \else
2583 \expandafter\endinput
2584 \fi

2585 \RequirePackage{zref-pagelayout}[2019/11/29]
2586 \zref@addprop{savepos}{abspage}
2587 \zref@addprop{savepos}{pagevalue}

```

`\zref@absposx`

```

2588 \newcommand*{\zref@absposx}[3]{%
2589 \number
2590 \expandafter\zref@absposnumx\expandafter{%
2591 \number\zref@extractdefault{#1}{abspage}{0}%
2592 }{#2}{#3}%
2593 \ltx@space
2594 }

```

`\zref@absposy`

```

2595 \newcommand*{\zref@absposy}[3]{%
2596 \number
2597 \expandafter\zref@absposnumy\expandafter{%
2598 \number\zref@extractdefault{#1}{abspage}{0}%
2599 }{#2}{#3}%
2600 \ltx@space
2601 }

```

`\zref@absposnumx`

```

2602 \newcommand*{\zref@absposnumx}[3]{%
2603 \number
2604 % \ifnum#1>\ltx@zero
2605 % \zref@ifrefundefined{thepage#1}{%
2606 % 0%
2607 % }{%
2608 \numexpr\ZREF@absposnum{thepage#1}{#2}{x}{#3}\relax

```

```

2609 % }%
2610 % \else
2611 % 0%
2612 % \fi
2613 }

\zref@absposnumy
2614 \newcommand*\zref@absposnumy}[3]{%
2615 \number
2616 % \ifnum#1>\lt x@zero
2617 % \zref@ifrefundefined{thepage#1}{%
2618 % 0%
2619 % }{%
2620 \numexpr\ZREF@absposnum{thepage#1}{#2}{y}{#3}\relax
2621 % }%
2622 % \else
2623 % 0%
2624 % \fi
2625 }

\ZREF@absposnum
2626 \def\ZREF@absposnum#1#2#3#4{%
2627 \lt x@ifundefined{ZREF@abspos@#2@#3@#4}{%
2628 0%
2629 }{%
2630 \csname ZREF@abspos@#2@#3@#4\endcsname{#1}%
2631 }%
2632 }

\zref@def@absposx
2633 \ZREF@Robust\def\zref@def@absposx#1{%
2634 \zref@wrapper@babel{\ZREF@def@abspos{#1}\zref@absposx}%
2635 }

\zref@def@absposy
2636 \ZREF@Robust\def\zref@def@absposy#1{%
2637 \zref@wrapper@babel{\ZREF@def@abspos{#1}\zref@absposy}%
2638 }

\zref@def@absposnumx
2639 \ZREF@Robust\def\zref@def@absposnumx#1{%
2640 \zref@wrapper@babel{\ZREF@def@abspos{#1}\zref@absposnumx}%
2641 }

\zref@def@absposnumy
2642 \ZREF@Robust\def\zref@def@absposnumy#1{%
2643 \zref@wrapper@babel{\ZREF@def@abspos{#1}\zref@absposnumy}%
2644 }

\ZREF@def@abspos
2645 \def\ZREF@def@absposnumy#1#2#3#4#5{%
2646 \edef#1{#2{#3}{#4}{#5}}%
2647 }

\zref@absposused
2648 \ZREF@Robust\def\zref@absposused{%
2649 \zref@wrapper@babel\ZREF@abspos@used
2650 }

```

\ZREF@abspos@used

```

2651 \def\ZREF@abspos@used#1{%
2652   \zref@refused{#1}%
2653   \zref@ifrefundefined{#1}{%
2654     }{%
2655     \begingroup
2656     \edef\ZREF@temp{%
2657       \zref@extractdefault{#1}{abspage}{0}%
2658     }%
2659     \ifnum\ZREF@temp>\ltx@zero
2660       \zref@refused{thepage\ZREF@temp}%
2661     \else
2662       \@PackageError{zref-abspos}{%
2663         \string\zref@pos@label@used\ltx@space
2664         needs property 'abspage'\MessageBreak
2665         in label '#1'%
2666       }\@ehc
2667     \fi
2668   \endgroup
2669 }%
2670 }

```

\zref@absposnumused

```

2671 \newcommand*{\zref@absposnumused}[1]{%
2672   \ifnum#1>\ltx@zero
2673     \zref@refused{thepage\number#1}%
2674   \else
2675     \@PackageError{zref-abspos}{%
2676       Invalid absolute page number (#1)\MessageBreak
2677       for \string\zref@pos@num@used.\MessageBreak
2678       A positive integer is expected%
2679     }\@ehc
2680   \fi
2681 }

```

\zref@ifabsposundefined

```

2682 \def\zref@ifabsposundefined#1{%
2683   \zref@ifrefundefined{#1}\ltx@firsttwo{%
2684     \expandafter\zref@ifabsposnumundefined\expandafter{%
2685       \number\zref@extractdefault{#1}{abspage}{0}%
2686     }%
2687   }%
2688 }

```

\zref@ifabsposnumundefined

```

2689 \def\zref@ifabsposnumundefined#1{%
2690   \ifnum\ZREF@number{#1}>\ltx@zero
2691     \zref@ifrefundefined{thepage#1}%
2692     \ltx@firstoftwo\ltx@secondoftwo
2693   \else
2694     \expandafter\ltx@firstoftwo
2695   \fi
2696 }

```

## 6.19.2 Media

\ZREF@abspos@media@width

```

2697 \edef\ZREF@abspos@media@width{%
2698   \ltx@ifundefined{pdfpagewidth}{%
2699     \ltx@ifundefined{mediawidth}{%
2700       \ltx@ifundefined{stockwidth}{%
2701         paperwidth%

```

```

2702     }{%
2703         stockwidth%
2704     }%
2705     }{%
2706         mediawidth%
2707     }%
2708     }{%
2709         pdfpagewidth%
2710     }%
2711 }
2712 \ifluatex
2713 \def\ZREF@abspos@media@width{pdfpagewidth}%
2714 \fi

```

\ZREF@abspos@media@height

```

2715 \edef\ZREF@abspos@media@height{%
2716     \ltx@ifundefined{pdfpageheight}{%
2717         \ltx@ifundefined{mediaheight}{%
2718             \ltx@ifundefined{stockheight}{%
2719                 paperheight%
2720             }{%
2721                 stockheight%
2722             }%
2723         }{%
2724             mediaheight%
2725         }%
2726     }{%
2727         \noexpand\ifcase\pdfpageheight
2728             \ltx@ifundefined{stockheight}{%
2729                 paperheight%
2730             }{%
2731                 stockheight%
2732             }%
2733         \noexpand\else
2734             pdfpageheight%
2735         \noexpand\fi
2736     }%
2737 }
2738 \ifluatex
2739 \edef\ZREF@abspos@media@height{%
2740     \noexpand\ifcase\pageheight
2741         \ltx@ifundefined{stockheight}{%
2742             paperheight%
2743         }{%
2744             stockheight%
2745         }%
2746     \noexpand\else
2747         pdfpageheight%
2748     \noexpand\fi}%
2749 \fi

```

\ZREF@abspos@media@x@left

```

2750 \def\ZREF@abspos@media@x@left#1{%
2751     0%
2752 }

```

\ZREF@abspos@media@x@right

```

2753 \def\ZREF@abspos@media@x@right#1{%
2754     \zref@extract{#1}\ZREF@abspos@media@width
2755 }

```

\ZREF@abspos@media@x@center

```

2756 \def\ZREF@abspos@media@x@center#1{%
2757   \ZREF@abspos@media@x@left{#1}%
2758   +\zref@extract{#1}\ZREF@abspos@media@width/2%
2759 }

```

\ZREF@abspos@media@y@top

```

2760 \def\ZREF@abspos@media@y@top#1{%
2761   \zref@extract{#1}\ZREF@abspos@media@height
2762 }

```

\ZREF@abspos@media@y@bottom

```

2763 \def\ZREF@abspos@media@y@bottom#1{%
2764   0%
2765 }

```

\ZREF@abspos@media@y@center

```

2766 \def\ZREF@abspos@media@y@center#1{%
2767   \zref@extract{#1}\ZREF@abspos@media@height/2%
2768 }

```

### 6.19.3 Paper

\ZREF@abspos@paper@x@left

```

2769 \def\ZREF@abspos@paper@x@left#1{%
2770   0%
2771 }

```

\ZREF@abspos@paper@x@right

```

2772 \def\ZREF@abspos@paper@x@right#1{%
2773   \zref@extract{#1}{paperwidth}%
2774 }

```

\ZREF@abspos@paper@x@center

```

2775 \def\ZREF@abspos@paper@x@center#1{%
2776   \zref@extract{#1}{paperwidth}/2%
2777 }

```

\ZREF@abspos@paper@y@top

```

2778 \let\ZREF@abspos@paper@y@top\ZREF@abspos@media@y@top

```

\ZREF@abspos@paper@y@bottom

```

2779 \def\ZREF@abspos@paper@y@bottom#1{%
2780   \ZREF@abspos@paper@y@top{#1}%
2781   -\zref@extract{#1}{paperheight}%
2782 }

```

\ZREF@abspos@paper@y@center

```

2783 \def\ZREF@abspos@paper@y@center#1{%
2784   \ZREF@abspos@paper@y@top{#1}%
2785   -\zref@extract{#1}{paperheight}/2%
2786 }

```

### 6.19.4 Origin

There doesn't seem a good reason to make these tests depend on pdf mode in current engines, so comment out the \ifpdf tests.

\ZREF@abspos@origin@x

```

2787 \let\ZREF@temp\ltx@two
2788 \ltx@ifundefined{pdfhorigin}{-}{%
2789 %   \ifpdf

```

```

2790 \let\ZREF@temp\ltx@zero
2791 % \fi
2792 }
2793 \ifluatex
2794 % \ifpdf
2795 \let\ZREF@temp\ltx@zero
2796 % \fi
2797 \fi
2798
2799 \ifx\ZREF@temp\ltx@two
2800 \ifnum\mag=1000 %
2801 \let\ZREF@temp\ltx@one
2802 \fi
2803 \fi
2804 \ifcase\ZREF@temp
2805 \def\ZREF@abspos@origin@x#1{%
2806 \zref@extract{#1}{pdfhorigin}%
2807 }%
2808 \or
2809 \def\ZREF@abspos@origin@x#1{%
2810 4736286%
2811 }%
2812 \or
2813 \def\ZREF@abspos@origin@x#1{%
2814 \numexpr\mag/1000*\dimexpr 1truein\relax\relax
2815 }%
2816 \fi

```

\ZREF@abspos@origin@y

```

2817 \let\ZREF@temp\ltx@two
2818 \ltx@ifundefined{pdfvorigin}{-}{%
2819 % \ifpdf
2820 \let\ZREF@temp\ltx@zero
2821 % \fi
2822 }
2823 \ifluatex
2824 % \ifpdf
2825 \let\ZREF@temp\ltx@zero
2826 % \fi
2827 \fi
2828 \ifx\ZREF@temp\ltx@two
2829 \ifnum\mag=1000 %
2830 \let\ZREF@temp\ltx@one
2831 \fi
2832 \fi
2833 \ifcase\ZREF@temp
2834 \def\ZREF@abspos@origin@y#1{%
2835 \zref@extract{#1}{pdfvorigin}%
2836 }%
2837 \or
2838 \def\ZREF@abspos@origin@y#1{%
2839 4736286%
2840 }%
2841 \or
2842 \def\ZREF@abspos@origin@y#1{%
2843 \numexpr\mag/1000*\dimexpr 1truein\relax\relax
2844 }%
2845 \fi

```

### 6.19.5 Header

\ZREF@abspos@head@x@left

```

2846 \def\ZREF@abspos@head@x@left#1{%
2847   \ZREF@abspos@paper@x@left{#1}%
2848   +\ZREF@abspos@origin@x{#1}%
2849   +\zref@extract{#1}{\offset}%
2850   +\ifodd\zref@extractdefault{#1}{\pagevalue}{\number\c@page} %
2851     \zref@extract{#1}{\oddsidemargin}%
2852   \else
2853     \zref@extract{#1}{\evensidemargin}%
2854   \fi
2855 }

```

\ZREF@abspos@head@x@right

```

2856 \def\ZREF@abspos@head@x@right#1{%
2857   \ZREF@abspos@head@x@left{#1}%
2858   +\zref@extract{#1}{\textwidth}%
2859 }

```

\ZREF@abspos@head@x@center

```

2860 \def\ZREF@abspos@head@x@center#1{%
2861   \ZREF@abspos@head@x@left{#1}%
2862   +\zref@extract{#1}{\textwidth}/2%
2863 }

```

\ZREF@abspos@head@y@top

```

2864 \def\ZREF@abspos@head@y@top#1{%
2865   \ZREF@abspos@paper@y@top{#1}%
2866   -\ZREF@abspos@origin@y{#1}%
2867   -\zref@extract{#1}{\voffset}%
2868   -\zref@extract{#1}{\topmargin}%
2869 }

```

\ZREF@abspos@head@y@bottom

```

2870 \def\ZREF@abspos@head@y@bottom#1{%
2871   \ZREF@abspos@head@y@top{#1}%
2872   -\zref@extract{#1}{\headheight}%
2873 }

```

\ZREF@abspos@head@y@center

```

2874 \def\ZREF@abspos@head@y@center#1{%
2875   \ZREF@abspos@head@y@top{#1}%
2876   -\zref@extract{#1}{\headheight}/2%
2877 }

```

### 6.19.6 Body

\ZREF@abspos@body@x@left

```

2878 \let\ZREF@abspos@body@x@left\ZREF@abspos@head@x@left

```

\ZREF@abspos@body@x@right

```

2879 \let\ZREF@abspos@body@x@right\ZREF@abspos@head@x@right

```

\ZREF@abspos@body@x@center

```

2880 \let\ZREF@abspos@body@x@center\ZREF@abspos@head@x@center

```

\ZREF@abspos@body@y@top

```

2881 \def\ZREF@abspos@body@y@top#1{%
2882   \ZREF@abspos@head@y@bottom{#1}%
2883   -\zref@extract{#1}{\headsep}%
2884 }

```

\ZREF@abspos@body@y@bottom

```
2885 \def\ZREF@abspos@body@y@bottom#1{%
2886   \ZREF@abspos@body@y@top{#1}%
2887   -\zref@extract{#1}{textheight}%
2888 }
```

\ZREF@abspos@body@y@center

```
2889 \def\ZREF@abspos@body@y@center#1{%
2890   \ZREF@abspos@body@y@top{#1}%
2891   -\zref@extract{#1}{textheight}/2%
2892 }
```

### 6.19.7 Footer

\ZREF@abspos@foot@x@left

```
2893 \let\ZREF@abspos@foot@x@left\ZREF@abspos@head@x@left
```

\ZREF@abspos@foot@x@right

```
2894 \let\ZREF@abspos@foot@x@right\ZREF@abspos@head@x@right
```

\ZREF@abspos@foot@x@center

```
2895 \let\ZREF@abspos@foot@x@center\ZREF@abspos@head@x@center
```

\ZREF@abspos@foot@y@bottom

```
2896 \def\ZREF@abspos@foot@y@bottom#1{%
2897   \ZREF@abspos@body@y@bottom{#1}%
2898   -\zref@extract{#1}{footskip}%
2899 }
```

### 6.19.8 Marginal notes

\ZREF@abspos@marginpar@x@left

```
2900 \def\ZREF@abspos@marginpar@x@left#1{%
2901   \ifodd\zref@extractdefault{#1}{pagevalue}{\number\c@page} %
2902     \ZREF@abspos@body@x@right{#1}%
2903     +\zref@extract{#1}{marginparsep}%
2904   \else
2905     \ZREF@abspos@body@x@left{#1}%
2906     -\zref@extract{#1}{marginparsep}%
2907     -\zref@extract{#1}{marginparwidth}%
2908   \fi
2909 }
```

\ZREF@abspos@marginpar@x@right

```
2910 \def\ZREF@abspos@marginpar@x@right#1{%
2911   \ZREF@abspos@marginpar@x@left{#1}%
2912   +\zref@extract{#1}{marginparwidth}%
2913 }
```

\ZREF@abspos@marginpar@x@center

```
2914 \def\ZREF@abspos@marginpar@x@center#1{%
2915   \ZREF@abspos@marginpar@x@left{#1}%
2916   +\zref@extract{#1}{marginparwidth}/2%
2917 }
```

\ZREF@abspos@marginpar@y@top

```
2918 \let\ZREF@abspos@marginpar@y@top\ZREF@abspos@body@y@top
```

\ZREF@abspos@marginpar@y@bottom

```
2919 \let\ZREF@abspos@marginpar@y@bottom\ZREF@abspos@body@y@bottom
```

\ZREF@abspos@marginpar@y@center

```
2920 \let\ZREF@abspos@marginpar@y@center\ZREF@abspos@body@y@center
```

### 6.19.9 Stock paper

```

\ZREF@abspos@stock@x@left
2921 \let\ZREF@abspos@stock@x@left\ZREF@abspos@paper@x@left

\ZREF@abspos@stock@x@right
2922 \let\ZREF@abspos@stock@x@right\ZREF@abspos@paper@x@right

\ZREF@abspos@stock@x@center
2923 \let\ZREF@abspos@stock@x@center\ZREF@abspos@paper@x@center

\ZREF@abspos@stock@y@top
2924 \let\ZREF@abspos@stock@y@top\ZREF@abspos@paper@y@top

\ZREF@abspos@stock@y@bottom
2925 \let\ZREF@abspos@stock@y@bottom\ZREF@abspos@paper@y@bottom

\ZREF@abspos@stock@y@center
2926 \let\ZREF@abspos@stock@y@center\ZREF@abspos@paper@y@center

2927 </abspos>

```

### 6.20 Module dotfill

```

2928 <*dotfill>
2929 \NeedsTeXFormat{LaTeX2e}
2930 \ProvidesPackage{zref-dotfill}%
2931 [2022-03-08 v2.33 Module dotfill for zref (HO)]%
2932 \RequirePackage{zref-base}[2019/11/29]
2933 \ifx\ZREF@base@ok Y%
2934 \else
2935 \expandafter\endinput
2936 \fi

```

For measuring the width of `\zdotfill` we use the features provided by module `savepos`.

```
2937 \RequirePackage{zref-savepos}[2019/11/29]
```

For automatically generated label names we use the unique counter of module `base`.

```
2938 \zref@require@unique
```

Configuration is done by the key value interface of package `keyval`.

```
2939 \RequirePackage{keyval}
```

The definitions of the keys follow.

```

2940 \define@key{ZREF@DF}{unit}{%
2941   \def\ZREF@df@unit{#1}%
2942 }
2943 \define@key{ZREF@DF}{min}{%
2944   \def\ZREF@df@min{#1}%
2945 }
2946 \define@key{ZREF@DF}{dot}{%
2947   \def\ZREF@df@dot{#1}%
2948 }

```

Defaults are set, see user interface.

```

2949 \providecommand\ZREF@df@min{2}
2950 \providecommand\ZREF@df@unit{.44em}
2951 \providecommand\ZREF@df@dot{.}

```

`\zdotfillsetup` Configuration of `\zdotfill` is done by `\zdotfillsetup`.

```
2952 \newcommand*{\zdotfillsetup}{\kvsetkeys{ZREF@DF}}
```

```

\zdotfill \zdotfill sets labels at the left and the right to get the horizontal position.
\zsavepos is not used, because we do not need the vertical position.
2953 \ZREF@ifDefinable\zdotfill\def{%
2954   {%
2955     \leavevmode
2956     \global\advance\c@zref@unique\ltx@one
2957     \begingroup
2958     \def\ZREF@temp{zref@\number\c@zref@unique}%
2959     \pdfsavepos
2960     \zref@labelbyprops{\thezref@unique L}{posx}%
2961     \setlength{\dimen@}{\ZREF@df@unit}%
2962     \zref@ifrefundefined{\thezref@unique R}{%
2963       \ZREF@dotfill
2964     }{%
2965       \ifnum\numexpr\zposx{\thezref@unique R}%
2966         -\zposx{\thezref@unique L}\relax
2967         <\dimexpr\ZREF@df@min\dimen@\relax
2968         \hfill
2969       \else
2970         \ZREF@dotfill
2971       \fi
2972     }%
2973     \pdfsavepos
2974     \zref@labelbyprops{\thezref@unique R}{posx}%
2975   \endgroup
2976   \kern\z@
2977 }%
2978 }

\ZREF@dotfill Help macro that actually sets the dots.
2979 \def\ZREF@dotfill{%
2980   \cleaders\hb@xt@\dimen@{\hss\ZREF@df@dot\hss}\hfill
2981 }

2982 </dotfill>

6.21 Module env

2983 <*env>
2984 \NeedsTeXFormat{LaTeX2e}
2985 \ProvidesPackage{zref-env}%
2986   [2022-03-08 v2.33 Module env for zref (H0)]%
2987 \RequirePackage{zref-base}[2019/11/29]
2988 \ifx\ZREF@base@ok Y%
2989 \else
2990   \expandafter\endinput
2991 \fi

2992 \zref@newprop{envname}[]{\@currentenv}
2993 \zref@newprop{envline}[]{\zref@env@line}

\zref@env@line Macro \zref@env@line extracts the line number from \@currentline.
2994 \def\zref@env@line{%
2995   \ifx\@currentline\ltx@empty
2996   \else
2997     \expandafter
2998     \ZREF@ENV@line\@currentline\ltx@empty line \ltx@empty\@nil
2999   \fi
3000 }

\ZREF@ENV@line
3001 \def\ZREF@ENV@line#1line #2\ltx@empty#3\@nil{#2}%

3002 </env>

```

## 7 Installation

### 7.1 Download

**Package.** This package is available on CTAN<sup>2</sup>:

[CTAN:macros/latex/contrib/zref/zref.dtx](#) The source file.

[CTAN:macros/latex/contrib/zref/zref.pdf](#) Documentation.

**Bundle.** All the packages of the bundle ‘zref’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

[CTAN:install/macros/latex/contrib/zref.tds.zip](#)

TDS refers to the standard “A Directory Structure for T<sub>E</sub>X Files” ([CTAN:pkg/tds](#)). Directories with `texmf` in their name are usually organized this way.

### 7.2 Bundle installation

**Unpacking.** Unpack the `zref.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip zref.tds.zip -d ~/texmf
```

### 7.3 Package installation

**Unpacking.** The `.dtx` file is a self-extracting docstrip archive. The files are extracted by running the `.dtx` through plain T<sub>E</sub>X:

```
tex zref.dtx
```

**TDS.** Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

<code>zref.sty</code>	→ <code>tex/latex/zref/zref.sty</code>
<code>zref-base.sty</code>	→ <code>tex/latex/zref/zref-base.sty</code>
<code>zref-abspage.sty</code>	→ <code>tex/latex/zref/zref-abspage.sty</code>
<code>zref-abspos.sty</code>	→ <code>tex/latex/zref/zref-abspos.sty</code>
<code>zref-counter.sty</code>	→ <code>tex/latex/zref/zref-counter.sty</code>
<code>zref-dotfill.sty</code>	→ <code>tex/latex/zref/zref-dotfill.sty</code>
<code>zref-env.sty</code>	→ <code>tex/latex/zref/zref-env.sty</code>
<code>zref-hyperref.sty</code>	→ <code>tex/latex/zref/zref-hyperref.sty</code>
<code>zref-lastpage.sty</code>	→ <code>tex/latex/zref/zref-lastpage.sty</code>
<code>zref-marks.sty</code>	→ <code>tex/latex/zref/zref-marks.sty</code>
<code>zref-nextpage.sty</code>	→ <code>tex/latex/zref/zref-nextpage.sty</code>
<code>zref-pageattr.sty</code>	→ <code>tex/latex/zref/zref-pageattr.sty</code>
<code>zref-pagelayout.sty</code>	→ <code>tex/latex/zref/zref-pagelayout.sty</code>
<code>zref-perpage.sty</code>	→ <code>tex/latex/zref/zref-perpage.sty</code>
<code>zref-runs.sty</code>	→ <code>tex/latex/zref/zref-runs.sty</code>
<code>zref-savepos.sty</code>	→ <code>tex/latex/zref/zref-savepos.sty</code>
<code>zref-thepage.sty</code>	→ <code>tex/latex/zref/zref-thepage.sty</code>
<code>zref-titleref.sty</code>	→ <code>tex/latex/zref/zref-titleref.sty</code>
<code>zref-totpages.sty</code>	→ <code>tex/latex/zref/zref-totpages.sty</code>
<code>zref-user.sty</code>	→ <code>tex/latex/zref/zref-user.sty</code>
<code>zref-xr.sty</code>	→ <code>tex/latex/zref/zref-xr.sty</code>
<code>zref.pdf</code>	→ <code>doc/latex/zref/zref.pdf</code>
<code>zref-example.tex</code>	→ <code>doc/latex/zref/zref-example.tex</code>
<code>zref-example-lastpage.tex</code>	→ <code>doc/latex/zref/zref-example-lastpage.tex</code>
<code>zref-example-nextpage.tex</code>	→ <code>doc/latex/zref/zref-example-nextpage.tex</code>
<code>zref.dtx</code>	→ <code>source/latex/zref/zref.dtx</code>

---

<sup>2</sup>[CTAN:pkg/zref](#)

If you have a `docstrip.cfg` that configures and enables `docstrip`'s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

## 7.4 Refresh file name databases

If your  $\text{T}_{\text{E}}\text{X}$  distribution ( $\text{T}_{\text{E}}\text{X}$  Live,  $\text{MiK}_{\text{T}}\text{E}_{\text{X}}$ , ...) relies on file name databases, you must refresh these. For example,  $\text{T}_{\text{E}}\text{X}$  Live users run `texhash` or `mktextlsr`.

## 7.5 Some details for the interested

**Unpacking with  $\text{L}_{\text{A}}\text{T}_{\text{E}}\text{X}$ .** The `.dtx` chooses its action depending on the format:

**plain  $\text{T}_{\text{E}}\text{X}$ :** Run `docstrip` and extract the files.

**$\text{L}_{\text{A}}\text{T}_{\text{E}}\text{X}$ :** Generate the documentation.

If you insist on using  $\text{L}_{\text{A}}\text{T}_{\text{E}}\text{X}$  for `docstrip` (really, `docstrip` does not need  $\text{L}_{\text{A}}\text{T}_{\text{E}}\text{X}$ ), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{zref.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

**Generating the documentation.** You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with `pdf $\text{L}_{\text{A}}\text{T}_{\text{E}}\text{X}$` :

```
pdflatex zref.dtx
makeindex -s gind.ist zref.idx
pdflatex zref.dtx
makeindex -s gind.ist zref.idx
pdflatex zref.dtx
```

## 8 References

- [1] Package `footmisc`, Robin Fairbairns, 2004/01/23 v5.3a. [CTAN:pkg/footmisc](#)
- [2] Package `hyperref`, Sebastian Rahtz, Heiko Oberdiek, 2006/08/16 v6.75c. [CTAN:pkg/hyperref](#)
- [3] Package `lastpage`, Jeff Goldberg, 1994/06/25 v0.1b. [CTAN:pkg/lastpage](#)
- [4] Package `nameref`, Sebastian Rahtz, Heiko Oberdiek, 2006/02/12 v2.24. [CTAN:pkg/nameref](#)
- [5] Package `perpage`, David Kastrup, 2002/12/20 v1.0. [CTAN:pkg/perpage](#)
- [6] Package `titleref`, Donald Arseneau, 2001/04/05 v3.1. [CTAN:pkg/titleref](#)
- [7] Package `totpages`, Wilhelm Müller, 1999/07/14 v1.00. [CTAN:pkg/totpages](#)
- [8] Package `xr`, David Carlisle, 1994/05/28 v5.02. [CTAN:pkg/xr](#)
- [9] Package `xr-hyper`, David Carlisle, 2000/03/22 v6.00beta4. [CTAN:pkg/xr-hyper](#)

## 9 History

[2006/02/20 v1.0]

- First version.

[2006/05/03 v1.1]

- Module `perpage` added.
- Module redesign as packages.

[2006/05/25 v1.2]

- Module `dotfillmin` added.
- Module `base`: macros `\zref@require@unique` and `\thezref@unique` added (used by modules `titleref` and `dotfillmin`).

[2006/09/08 v1.3]

- Typo fixes and English cleanup by Per Starback.

[2007/01/23 v1.4]

- Typo in macro name fixed in documentation.

[2007/02/18 v1.5]

- `\zref@getcurrent` added (suggestion of Igor Akkerman).
- Module `savepos` also supports  $\text{\LaTeX}$ .

[2007/04/06 v1.6]

- Fix in modules `abspage` and `base`: Now counter `abspage` and `zref@unique` are not remembered by `\include`.
- Beamer support for module `titleref`.

[2007/04/17 v1.7]

- Package `atbegshi` replaces `everyshi`.

[2007/04/22 v1.8]

- `\zref@wrapper@babel` and `\zref@refused` are now expandable if `babel` is not used or `\if@safe@actives` is already set to true. (Feature request of Josselin Noirel)

[2007/05/02 v1.9]

- Module `titleref`: Some support for `\caption` of package `longtable`, but only if `\label` is given after `\caption`.

[2007/05/06 v2.0]

- Uses package `etexcmds` for accessing  $\varepsilon\text{-TeX}$ 's `\unexpanded`.

#### [2007/05/28 v2.1]

- Module `titleref` supports caption of package listings.
- Fixes in module `titleref` for support of packages `titlesec` and `longtable`.

#### [2008/09/21 v2.2]

- Module `base`: `\zref@iflistcontainsprop` is documented, but a broken `\zref@listcontainsprop` implemented. Name and implementation fixed (thanks Ohad Kammar).

#### [2008/10/01 v2.3]

- `\zref@localaddprop` added (feature request of Ohad Kammar).
- Module `lastpage`: list ‘LastPage’ added. Label ‘LastPage’ will use the properties of this list (default is empty) along with the properties of the main list.

#### [2009/08/07 v2.4]

- Module `runs` added.

#### [2009/12/06 v2.5]

- Module `lastpage`: Uses package `atveryend`.
- Module `titleref`: Further commands are disabled during string expansion, imported from package `nameref`.

#### [2009/12/07 v2.6]

- Version date added for package `atveryend`.

#### [2009/12/08 v2.7]

- Module `titleref`: Use of package `getttitlestring`.

#### [2010/03/26 v2.8]

- `\zifrefundefined` added.
- Module `lastpage`: Macros `\zref@iflastpage` and `\ziflastpage` added.
- Module `thepage` added.
- Module `nextpage` added.

#### [2010/03/29 v2.9]

- Module `marks` added (without documentation).
- `\zref@addprop` now adds expanded property to list.
- Useless `\ZREF@ErrorNoLine` removed.

#### [2010/04/08 v2.10]

- Module `xr` remembers the external document name in property ‘externaldocument’.

[2010/04/15 v2.11]

- Module `titleref`: Better support of class `memoir`.
- Module `titleref`: Support of theorems.

[2010/04/17 v2.12]

- Module `base`: `\zref@newprop` ensures global empty default.
- Module `xr`: Setup options `tozreflabel` and `toltxlabel` added.

[2010/04/19 v2.13]

- `\zref@setcurrent` throws an error if the property does not exist (Florent Chervet).
- `\zref@getcurrent` the documentation is fixed (Florent Chervet). Also it returns the empty string in case of errors.
- `\zref@addprop` and `\zref@localaddprop` now take a list of property names (feature request of Florent Chervet).
- Example for `\zref@wrapper@unexpanded` corrected (Florent Chervet).

[2010/04/22 v2.14]

- Bug fix for `\zref@getcurrent` second argument wasn't eaten in case of unknown property.
- `\zref@getcurrent` supports `\zref@wrapper@unexpanded`.
- `\zref@wrapper@unexpanded` added for `\ZREF@xr@tolabel`.
- `\zref@extract`, `\zref@extractdefault`, `\zref@getcurrent` are expandable in exact two steps except inside `\zref@wrapper@unexpanded`.

[2010/04/23 v2.15]

- `\zexternaldocument` fixed for property 'url' when importing `\new@label` (bug found by Victor Ivrii).
- Two expansion steps also in `\zref@wrapper@unexpanded`.
- Nested calls of `\zref@wrapper@unexpanded` possible.

[2010/04/28 v2.16]

- More consequent use of package 'ltxcmds' and 'hologo'.
- Module `pagelayout` added.
- Module `pageattr` added.
- Robustness introduced for non-expandable interface macros.
- Internal change of the data format of property lists (suggestion of Florent Chervet).
- Module `titleref`: Support of environment `description`.

[2010/05/01 v2.17]

- `\zref@newprop` throws an error if the property already exists.
- Module `xr`: Bug fix for the case of several `.aux` files (bug found by Victor Ivrii).
- Module `xr`: Property `'urluse'` and option `urluse` added.

[2010/05/13 v2.18]

- Module `env` added.
- Module `savepos`: `\zref@savepos` added.

[2010/10/22 v2.19]

- `\zref@addprop` and `\zref@localaddprop` are limited to one property only (incompatibility to versions v2.13 to v2.18).
- `\zref@addprops` and `\zref@localaddprops` added.
- `\zref@delprop` and `\zref@localdelprop` added.
- `\zref@labelbykv` and `\zkvlabel` (module `user`) with keys `prop`, `list`, `delprop`, `immediate`, `values` added.

[2011/02/12 v2.20]

- Fix for warning in `zref-xr`.

[2011/03/18 v2.21]

- Fix in module `pagelayout` for `\zlistpagelayout`.
- Fix for `\zref@localaddprop` (probably since v2.19).

[2011/10/05 v2.22]

- Documentation fixed for `\zref@(local)addprop(s)`.
- Module `base`: `\zref@def@extract`, `\zref@def@extractdefault` added.
- Fix in module `pagelayout`: Because of missing `\noexpand` commands the values of the `pagelayout` properties on all pages were the values at package loading.
- Module `base`: `\zref@showprop` added.

[2011/12/05 v2.23]

- Module `savepos`: `\zsaveposx` and `\zsaveposy` added.

[2012/04/04 v2.24]

- Module `titleref`, package `titlesec`: some support for class `'straight'` (`\ttl@straight@i`) added.

[2016/05/16 v2.25]

- Documentation updates.

[2016/05/21 v2.26]

- update zref-savepos for new luatex

[2018/11/21 v2.27]

- adapted zref-perpage, see issue <https://github.com/ho-tex/zref/issues/2>

[2019/11/29 v2.28]

- Documentation updates.
- Use iftex directly.

[2020-03-03 v2.29]

- adapted in module zref-pagelayout the properties pdfhorigin, pdfvorigin, pdfpagewidth, pdfpageheight for luatex to the right primitives.
- Removed no longer needed code for older luatex versions.
- added some documentation of the abspos module.
- adapted the abspos module to the new luatex primitives.
- adapted pageattr module to the new luatex primitives.
- added short documentation for pageattr module
- use luatex command names directly in zref-savepos rather than defining pdftex compatibility names.
- allow zref-abspos to use `\pdf[vh]origin` in dvi mode.

[2020-03-04 v2.30]

- add pagevalue property to savepos in the abspos module (issue 1)

[2020-05-28 v2.31]

- Adapted module zref-counter to use `\@currentcounter` in the next  $\text{\LaTeX}$  version (issue 5)

[2020-07-03 v2.32]

- Changed in zref-pagelayout the names of the shipout box dimensions to adapt to the new hook management.

[2022-03-08 v2.33]

- Avoid that amstext undoes the stepcounter patch in zref-perpage, <https://github.com/ho-tex/zref/issues/11>
- Make the unique counter more robust when includeonly is used, <https://github.com/ho-tex/zref/issues/10>

## 10 Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; plain numbers refer to the code lines where the entry is used.

### Symbols

`\@PackageError` . . . [509](#), [525](#), [2662](#), [2675](#)[88](#)

\@PackageInfo	2111	\addtocounter	1737
\@PackageInfoNoLine	549, 564, 1356, 1451, 1463, 1531, 1583	\AddToHook	919, 1731
\@PackageWarning	692	\advance	1065, 1403, 1560, 1785, 2107, 2956
\@addtoreset	1013	\afterassignment	234, 1149, 1153
\@auxout	716	\AfterLastShipout	1062, 1420, 1592
\@begintheorem	2050, 2055	\Alph	7
\@bsphack	601, 611, 631, 2534	\anchor	2425
\@caption	1895	\AtBeginDocument	1040, 1238, 1694, 1893
\@chapter	1907, 1944	\AtBeginShipout	1017, 1109
\@currentHref	945	\AtBeginShipoutAddToBox	1110
\@currentcounter	1034	\AtBeginShipoutBoxDepth	1327
\@currentlabel	940	\AtBeginShipoutBoxHeight	1326
\@currenvir	2992	\AtBeginShipoutBoxWidth	1325
\@currenvline	2995, 2998	\AtEndOfPackage	195
\@ehc	297, 307, 492, 515, 527, 1615, 2666, 2679	\AtVeryEndDocument	1347, 1508
\@elt	1738		
\@esphack	608, 628, 643, 2546	<b>B</b>	
\@firstofone	1571	\beamer@section	1981
\@firstoftwo	1436, 1515	\beamer@subsection	1987
\@ifclassloaded	1942, 1979	\beamer@subsubsection	1993
\@ifdefinable	243, 290	\begin	23, 57, 100, 106, 156, 172, 1747
\@ifl@t@r	223, 1032	\bfseries	933
\@ifnextchar	531, 1761		
\@ifpackageloaded	1999, 2018, 2026, 2045	<b>C</b>	
\@ifstar	496, 2131	\c@abspage	1020, 1793, 1800
\@ifundefined	192, 910, 1772, 2267, 2309	\c@page	959, 1065, 1790, 2850, 2901
\@input	2328	\c@zpage	1790, 1796
\@inputcheck	2159, 2160, 2175, 2212, 2214	\c@zref@unique	913, 922, 1785, 2956, 2958
\@latex@warning	778	\ch@pt@c	1948, 1954, 1960
\@mainaux	1700	\chapter	24, 30, 32, 61, 82
\@namedef	536	\ChapterPages	91, 112
\@ne	1737	\ChapterStart	78, 135, 150, 166
\@newl@bel	286	\ChapterStop	85, 148, 165, 184
\@nil	1630, 1632, 1860, 1867, 2049, 2050, 2203, 2206, 2386, 2395, 2998, 3001	\chardef	1171, 1186, 1195, 1199
\@onelevel@sanitize	423, 441, 506, 534, 2048, 2051	\cleaders	2980
\@opargbegintheorem	2040	\cleardoublepage	79, 86
\@part	1901	\clearpage	62
\@schapter	1925	\closein	2175
\@secondoftwo	1438, 1517	\columnsep	1311
\@sect	1913	\columnwidth	1310
\@spart	1919	\comma@entry	344, 345, 347, 353, 379, 380, 382, 388, 615, 617, 621, 1636, 1637, 1638, 1644, 1647
\@ssect	1931	\comma@parse	343, 378, 614, 1635
\@stpelt	1738, 1748, 1749	\count@	1353, 1364, 1365, 1367, 1402, 1403, 1412, 1414, 1415, 1528, 1551, 1553, 1554, 1559, 1560, 2101, 2106, 2117, 2118
\@testdef	1338, 1339, 1499, 1500	\cs	1745
\@testopt	2133, 2136, 2146	\csname	253, 254, 291, 316, 317, 318, 327, 352, 353, 370, 371, 387, 388, 405, 406, 426, 428, 445, 463, 466, 479, 537, 539, 540, 545, 555, 560, 566, 579, 588, 605, 621, 652, 662, 731, 739, 745, 788, 789, 791, 811, 834, 835, 836, 897, 922, 1343, 1504, 1665, 1673, 1725, 1735, 1738, 1773, 1775, 1778, 1780, 1792, 1798, 1803, 1804, 1806, 1808, 1809,
\@tfor	323, 721		
\@undefined	1816, 2385, 2488, 2512, 2520		
\\	25, 26, 27, 28, 153, 155, 157, 158, 170, 173, 2294, 2388, 2413, 2423, 2427, 2443		
\_	44, 45		
<b>A</b>			
\AddLineBeginAux	281		



<code>\ifzref@titleref@stripperperiod</code> . . .	<code>\ltx@one</code> . . . . .
1846, 1857	1403, 1560,
<code>\ifZREF@xr@toltxlabel</code> . . . 2280, 2322	1785, 2101, 2107, 2801, 2830, 2956
<code>\ifZREF@xr@tozreflabel</code> . . 2266, 2308	<code>\ltx@onelevel@sanitize</code> . . . . 558, 563
<code>\ifZREF@xr@urluse</code> . . 2150, 2429, 2459	<code>\ltx@ReturnAfterFi</code> . . . . . 2390
<code>\ifZREF@xr@verbose</code> . . 2268, 2310, 2331	<code>\ltx@secondoftwo</code> . . . . . 312,
<code>\ifZREF@xr@zreflabel</code> . . . . .	785, 798, 828, 887, 891, 1081, 2692
2081, 2167, 2181, 2222	<code>\ltx@space</code> 585, 587, 807, 816, 830,
<code>\immediate</code> . . . . . 706, 1700	833, 1192, 1198, 1366, 1413,
<code>\in@</code> . . . . . 315	1610, 1638, 1681, 2593, 2600, 2663
<code>\item</code> . . . . . 107, 111, 113, 121, 125, 127	<code>\ltx@two</code> . . . . . 2787, 2799, 2817, 2828
	<code>\ltx@zero</code> . . 477, 1608, 1661, 1761,
	2097, 2540, 2604, 2616, 2659,
	2672, 2690, 2790, 2795, 2820, 2825
<b>K</b>	<b>M</b>
<code>\kern</code> . . . . . 2976	<code>\m@ne</code> . . . . . 1065
<code>\kv@define@key</code> 645, 656, 667, 672, 689	<code>\M@sect</code> . . . . . 1968
<code>\kv@key</code> . . . 693, 1630, 1632, 1633, 1647	<code>\M@TitleReference</code> . . . . . 2348
<code>\kv@parse</code> . . . . . 690, 1626	<code>\mag</code> . . . . . 1268, 2800, 2814, 2829, 2843
<code>\kv@value</code> . . . . 691, 1627, 1628, 1635	<code>\mainmatter</code> . . . . . 60, 134
<code>\kvsetkeys</code> . . . . 634, 1881, 2094, 2952	<code>\makeatletter</code> . . . . . 11, 74, 101, 2130
	<code>\makeatother</code> . . . . . 16, 99
	<code>\makebox</code> . . . . . 169, 170
	<code>\MakeRobustcommand</code> . . . . . 233
	<code>\marginparsep</code> . . . . . 1309
	<code>\marginparwidth</code> . . . . . 1308
	<code>\meaning</code> . . . . . 2050
	<code>\mediaheight</code> . . . . . 1274
	<code>\mediawidth</code> . . . . . 1273
	<code>\MessageBreak</code> . . 271, 514, 565, 571,
	681, 1352, 1364, 1368, 1416,
	1527, 1552, 1555, 1586, 1588,
	1611, 1614, 1641, 1643, 1682,
	1683, 2112, 2113, 2162, 2179,
	2184, 2188, 2193, 2249, 2368,
	2377, 2491, 2504, 2664, 2676, 2677
	<b>N</b>
	<code>\NeedsTeXFormat</code> . . . . .
	. 3, 188, 220, 965, 1003, 1024,
	1051, 1094, 1134, 1225, 1243,
	1425, 1597, 1690, 1708, 1821,
	2065, 2468, 2480, 2572, 2929, 2984
	<code>\newcommand</code> . . . . 18, 78, 85, 91, 167,
	973, 980, 986, 1148, 1165, 1166,
	1235, 1605, 2093, 2563, 2566,
	2588, 2595, 2602, 2614, 2671, 2952
	<code>\newcount</code> . . . . . 2096
	<code>\newcounter</code> . . . . . 6, 911, 1014, 1720
	<code>\newif</code> . . . . . 248, 701, 1833, 1846, 2081
	<code>\newlabel</code> . . . . . 2285, 2296, 2327
	<code>\newmarks</code> . . . . . 1614
	<code>\newpage</code> . . . . . 143
	<code>\nfss@text</code> . . . . . 933
	<code>\NR@temp</code> . . . . . 1951, 1952
	<code>\number</code> . . . . . 94, 109, 913, 925, 959,
	1116, 1261, 1262, 1277, 1278,
	1281, 1282, 1285, 1286, 1289,
	1290, 1695, 1767, 1793, 1800,
	2589, 2591, 2596, 2598, 2603,
	2615, 2673, 2685, 2850, 2901, 2958
	<code>\numexpr</code> . . . . . 94,
	109, 115, 927, 1118, 1179, 1695,
<code>\ifzref@titleref@stripperperiod</code> . . .	
1846, 1857	
<code>\ifZREF@xr@toltxlabel</code> . . . 2280, 2322	
<code>\ifZREF@xr@tozreflabel</code> . . 2266, 2308	
<code>\ifZREF@xr@urluse</code> . . 2150, 2429, 2459	
<code>\ifZREF@xr@verbose</code> . . 2268, 2310, 2331	
<code>\ifZREF@xr@zreflabel</code> . . . . .	
2081, 2167, 2181, 2222	
<code>\immediate</code> . . . . . 706, 1700	
<code>\in@</code> . . . . . 315	
<code>\item</code> . . . . . 107, 111, 113, 121, 125, 127	
<b>K</b>	
<code>\kern</code> . . . . . 2976	
<code>\kv@define@key</code> 645, 656, 667, 672, 689	
<code>\kv@key</code> . . . 693, 1630, 1632, 1633, 1647	
<code>\kv@parse</code> . . . . . 690, 1626	
<code>\kv@value</code> . . . . 691, 1627, 1628, 1635	
<code>\kvsetkeys</code> . . . . 634, 1881, 2094, 2952	
<b>L</b>	
<code>\label</code> . . . . . 974, 981, 1889	
<code>\lastxpos</code> . . . . . 2516	
<code>\lastypos</code> . . . . . 2517	
<code>\leavevmode</code> . . . . . 2955	
<code>\lst@caption</code> . . . . . 2032	
<code>\lst@label</code> . . . . . 2029	
<code>\lst@MakeCaption</code> . . . . . 2028	
<code>\LT@c@ption</code> . . . . . 2020	
<code>\ltx@backslashchar</code> . . . . .	
744, 1525, 1584, 2112	
<code>\ltx@car</code> . . . . . 1630, 2203	
<code>\ltx@cdr</code> . . . . . 1632, 2206	
<code>\ltx@empty</code> . . . . . 291, 500,	
566, 633, 720, 797, 1107, 1618,	
1834, 1860, 1867, 1948, 1952,	
2009, 2029, 2142, 2177, 2200,	
2206, 2247, 2401, 2995, 2998, 3001	
<code>\ltx@firstofone</code> . . . . .	
. . . 255, 868, 879, 885, 1485, 1486	
<code>\ltx@firstoftwo</code> . . . . .	
800, 827, 828, 893, 1079, 2692, 2694	
<code>\ltx@firsttwo</code> . . . . . 2683	
<code>\ltx@gobble</code> . . . . .	
. 251, 356, 391, 624, 664, 974,	
975, 981, 1405, 1562, 1649, 1889	
<code>\ltx@gobblethree</code> . . . . . 982	
<code>\ltx@gobbletwo</code> . 695, 1013, 1651, 1755	
<code>\ltx@ifpackageloaded</code> . . . . . 2354	
<code>\ltx@ifUndefined</code> . . 230, 250, 258,	
411, 878, 924, 1115, 1450, 1462,	
1482, 1483, 1512, 1568, 1943,	
1945, 2489, 2499, 2538, 2788, 2818	
<code>\ltx@ifundefined</code> . . . . .	
. . . . . 301, 486, 584, 761, 806,	
945, 1257, 1337, 1498, 2079,	
2339, 2340, 2627, 2698, 2699,	
2700, 2716, 2717, 2718, 2728, 2741	
<code>\ltx@LocalAppendToMacro</code> . . . . .	
. . . . . 386, 404, 650, 660, 1582,	
2258, 2298, 2301, 2406, 2409,	
2418, 2425, 2431, 2438, 2445, 2457	
<code>\ltx@newif</code> . . . . . 1330, 1491	

1767, 2242, 2253, 2287, 2372, 2381, 2608, 2620, 2814, 2843, 2965	2073, 2074, 2471, 2483, 2575, 2580, 2585, 2932, 2937, 2939, 2987
<b>O</b>	<b>S</b>
\oddsidemargin ..... 1301	\savepos ..... 2529
\on@line ..... 1697, 2177	\section ..... 63, 137, 145
\openin ..... 2159	\setcounter ..... 921, 1016
<b>P</b>	\setlength ..... 2961
\PackageError ..... 259, 270, 295, 305, 490, 1609, 2490, 2502	\SetupKeyvalOptions ..... 2082
\PackageInfo ..... 292, 521, 1698, 2166, 2178, 2269, 2311, 2332	\ShipoutBoxDepth ..... 1322
\PackageWarning ..... 346, 364, 381, 399, 616, 680, 1639, 1680, 2161	\ShipoutBoxHeight ..... 1321
\PackageWarningNoLine 2248, 2367, 2376	\ShipoutBoxWidth ..... 1320
\page ..... 2409	\space ..... 779, 1452, 1464, 2180, 2181, 2185, 2189, 2194, 2491, 2503
\pageheight ..... 1285, 1286, 2740	\spinemargin ..... 1313
\pagestyle ..... 49	\stepcounter .....
\pagewidth ..... 1289, 1290	. 19, 1018, 1722, 1723, 1732, 1752
\paperheight ..... 1270	\stockheight ..... 1272
\paperwidth ..... 1269	\stockwidth ..... 1271
\pdf@escapehex ..... 1488	<b>T</b>
\pdf@strcmp ..... 477	\tableofcontents ..... 59, 132
\pdf@unescapehex ..... 1489	\textheight ..... 1304
\pdfhorigin ..... 1295	\textwidth ..... 1303
\pdflastxpos ..... 2513	\TeXeTstate ..... 2540
\pdflastypos ..... 2514	\the ..... 13, 153, 155, 430, 445, 461, 557, 562, 621, 627, 743, 757, 927, 1020, 1071, 1112, 1118, 1179, 1336, 1356, 1363, 1364, 1365, 1367, 1412, 1414, 1415, 1443, 1445, 1458, 1470, 1497, 1532, 1550, 1551, 1553, 1843, 2236, 2242, 2253, 2287, 2372, 2381, 2513, 2514, 2516, 2517
\pdfpageattr ..... 1452, 1458	\thechapter ..... 14
\pdfpageheight ..... 1294, 2727	\thefoo ..... 7, 12, 20
\pdfpagesattr ..... 1464, 1470	\thetype ..... 2299
\pdfpagewidth ..... 1293	\thepage ..... 43, 44, 45, 714, 718, 779, 941, 1791
\pdfsavepos 2491, 2503, 2523, 2959, 2973	\thezpage ..... 16, 1791, 1797
\pdfTeXversion ..... 2501	\thezref@unique .....
\pdfvariable .....	10, 912, 1788, 1789, 1796, 1797, 1799, 2960, 2962, 2965, 2966, 2974
1277, 1278, 1281, 1282, 1443, 1445	\title ..... 2418, 2447
\pdfvorigin ..... 1296	\toks@ ..... 424, 430, 444, 445, 554, 557, 559, 562, 613, 620, 621, 627, 741, 743, 756, 757, 1066, 1071, 1352, 1356, 1362, 1363, 1525, 1532, 1549, 1550, 1837, 1843, 2221, 2236
\ProcessOptions ..... 217	\topmargin ..... 1300
\protect ..... 777	\TR@TitleReference .. 2343, 2403, 2442
\protected ..... 239	\trimedge ..... 1312
\protected@write ..... 716	\trimtop ..... 1315
\providecommand ..... 223, 282, 1693, 2078, 2949, 2950, 2951	\ttl@sect@i ..... 2001
\ProvidesPackage .....	\ttl@straight@i ..... 2007
... 189, 221, 966, 1004, 1025, 1052, 1095, 1135, 1226, 1244, 1426, 1598, 1691, 1709, 1822, 2066, 2469, 2481, 2573, 2930, 2985	<b>U</b>
<b>R</b>	\unexpanded ..... 271, 276
\read ..... 2212	
\refstepcounter ..... 1042	
\renewcommand ..... 7, 46, 912	
\RequirePackage ..... 191, 196, 224, 225, 226, 227, 228, 231, 267, 272, 280, 968, 1006, 1011, 1027, 1054, 1055, 1056, 1097, 1102, 1103, 1137, 1142, 1143, 1144, 1145, 1228, 1233, 1234, 1246, 1251, 1252, 1253, 1428, 1433, 1441, 1442, 1457, 1469, 1478, 1479, 1480, 1600, 1711, 1716, 1824, 1829, 1830, 2068,	

\UniqueCounterCall	1163	\ZREF@abspos@body@x@right	<u>2879</u> , <u>2902</u>
\UniqueCounterNew	1146	\ZREF@abspos@body@y@bottom	..... <u>2885</u> , <u>2897</u> , <u>2919</u>
\uppermargin	1316	\ZREF@abspos@body@y@center	<u>2889</u> , <u>2920</u>
\url	2438	\ZREF@abspos@body@y@top	..... <u>2881</u> , <u>2886</u> , <u>2890</u> , <u>2918</u>
\urluse	2433	\ZREF@abspos@foot@x@center	..... <u>2895</u>
\usepackage	9, 41, 48, 70, 72	\ZREF@abspos@foot@x@left	..... <u>2893</u>
<b>V</b>			
\value	13, 1112, 1336, 1497	\ZREF@abspos@foot@x@right	..... <u>2894</u>
\verb	173	\ZREF@abspos@foot@y@bottom	..... <u>2896</u>
\voffset	1299	\ZREF@abspos@head@x@center	..... <u>2860</u> , <u>2880</u> , <u>2895</u>
<b>W</b>			
\write	705, 706, 1700	\ZREF@abspos@head@x@left	..... <u>2846</u> , <u>2857</u> , <u>2861</u> , <u>2878</u> , <u>2893</u>
<b>X</b>			
\x	331, 336, 724, 729, 898, 900, 1205, 1221, 1258, 1265, 1355, 1358, 1361, 1401, 1530, 1535, 1548, 1558, 1663, 1668, 1671, 1677, 1766, 1769, 2047, 2048, 2053, 2220, 2223, 2228, 2233, 2243, 2246, 2256, 2257, 2288, 2293	\ZREF@abspos@head@x@right	..... <u>2856</u> , <u>2879</u> , <u>2894</u>
\XR@ext	2079	\ZREF@abspos@head@y@bottom	<u>2870</u> , <u>2882</u>
<b>Y</b>			
\y	2049, 2050	\ZREF@abspos@head@y@center	..... <u>2874</u>
<b>Z</b>			
\z	2050, 2051, 2053	\ZREF@abspos@head@y@top	..... <u>2864</u> , <u>2871</u> , <u>2875</u>
\z@	2976	\ZREF@abspos@marginpar@x@center	<u>2914</u>
\Z@D@page	1166	\ZREF@abspos@marginpar@x@left	..... <u>2900</u> , <u>2911</u> , <u>2915</u>
\Z@L@LastPage	1068	\ZREF@abspos@marginpar@x@right	<u>2910</u>
\Z@L@main	1067	\ZREF@abspos@marginpar@y@bottom	<u>2919</u>
\Z@L@ZREF@temp	633, 637, 640, 651, 661	\ZREF@abspos@marginpar@y@center	<u>2920</u>
\zdotfill	18, 170, 173, <u>2953</u>	\ZREF@abspos@marginpar@y@top	.. <u>2918</u>
\zdotfillsetup	19, <u>2952</u>	\ZREF@abspos@media@height	..... <u>2715</u> , <u>2761</u> , <u>2767</u>
\zexternaldocument	19, <u>2124</u>	\ZREF@abspos@media@width	..... <u>2697</u> , <u>2754</u> , <u>2758</u>
\ziflastpage	12, <u>1084</u>	\ZREF@abspos@media@x@center	... <u>2756</u>
\zifrefundefined	8, <u>763</u>	\ZREF@abspos@media@x@left	<u>2750</u> , <u>2757</u>
\zkvlabel	980	\ZREF@abspos@media@x@right	... <u>2753</u>
\zlabel	11, 83, 104, 138, 146, 973	\ZREF@abspos@media@y@bottom	... <u>2763</u>
\zlistpageattr	1492	\ZREF@abspos@media@y@center	... <u>2766</u>
\zlistpagelayout	15, 1331	\ZREF@abspos@media@y@top	. <u>2760</u> , <u>2778</u>
\zmakeperpage	16, <u>1759</u>	\ZREF@abspos@origin@x	... <u>2787</u> , <u>2848</u>
\znextpage	13, 51, 54, 1162	\ZREF@abspos@origin@y	... <u>2817</u> , <u>2866</u>
\znextpagesetup	14, 42, 1148	\ZREF@abspos@paper@x@center	..... <u>2775</u> , <u>2923</u>
\znonextpagename	46, 1165, 1213	\ZREF@abspos@paper@x@left	..... <u>2769</u> , <u>2847</u> , <u>2921</u>
\zpageref	11, 126, <u>995</u>	\ZREF@abspos@paper@x@right	<u>2772</u> , <u>2922</u>
\zposx	17, 153, <u>2563</u> , 2965, 2966	\ZREF@abspos@paper@y@bottom	..... <u>2779</u> , <u>2925</u>
\zposy	17, 155, <u>2563</u>	\ZREF@abspos@paper@y@center	..... <u>2783</u> , <u>2926</u>
\zref	11, 25, 26, 27, 28, 112, 114, 123, 128, 129, 139, <u>986</u> , 996	\ZREF@abspos@paper@y@top	..... <u>2778</u> , <u>2780</u> , <u>2784</u> , <u>2865</u> , <u>2924</u>
\ZREF@@@delprop	435, <u>437</u> , <u>472</u> , <u>474</u>	\ZREF@abspos@stock@x@center	... <u>2923</u>
\ZREF@@@newprop	539, <u>543</u>	\ZREF@abspos@stock@x@left	..... <u>2921</u>
\ZREF@@@delprop	..... <u>425</u> , <u>434</u> , <u>448</u> , <u>465</u> , <u>471</u> , <u>481</u>	\ZREF@abspos@stock@x@right	... <u>2922</u>
\ZREF@@@extract	809, <u>815</u>	\ZREF@abspos@stock@y@bottom	... <u>2925</u>
\ZREF@@@makeperpage	1761, 1767, 1771	\ZREF@abspos@stock@y@center	... <u>2926</u>
\ZREF@@@newprop	517, 528, 531, <u>535</u>	\ZREF@abspos@stock@y@top	..... <u>2924</u>
\ZREF@@@perpage@step	1776, <u>1784</u>	\ZREF@abspos@used	..... <u>2649</u> , <u>2651</u>
\ZREF@abspos@body@x@center	..... <u>2880</u>	\ZREF@absposnum	... <u>2608</u> , <u>2620</u> , <u>2626</u>
\ZREF@abspos@body@x@left	<u>2878</u> , <u>2905</u>	\zref@absposnumused	..... <u>2671</u>
		\zref@absposnumx	... <u>2590</u> , <u>2602</u> , <u>2640</u>
		\zref@absposnumy	... <u>2597</u> , <u>2614</u> , <u>2643</u>
		\zref@absposused	..... <u>2648</u>

<code>\zref@absposx</code> .....	2588, 2634	<code>\zref@ifabsposnumundefined</code>	2684, 2689
<code>\zref@absposy</code> .....	2595, 2637	<code>\zref@ifabsposundefined</code> .....	2682
<code>\zref@addprop</code> .....		<code>\ZREF@ifDefinable</code> .....	242,
. 6, 76, 360, 1021, 1035, 1039,		763, 995, 998, 1084, 1126, 1162,	
1105, 1108, 1263, 1279, 1283,		1331, 1492, 1759, 1813, 1880,	
1287, 1291, 1444, 1446, 1459,		1883, 2124, 2548, 2553, 2558, 2953	
1471, 1647, 1832, 2477, 2586, 2587		<code>\ZREF@iflastpage</code> ...	1085, 1087, 1087
<code>\zref@addprops</code> .....		<code>\zref@iflastpage</code> .....	12, 1076, 1090
. 6, 15, 341, 942, 1329, 1719, 2519		<code>\zref@iflistcontainsprop</code> .....	6,
<code>\ZREF@addtoks</code> .....	755	310, 345, 363, 380, 398, 648, 658	
<code>\ZREF@base@ok</code> ....	962, 969, 1007,	<code>\zref@iflistundefined</code> .....	
1028, 1057, 1098, 1138, 1229,		..... 6, 289, 300, 304, 311	
1247, 1429, 1601, 1712, 1825,		<code>\zref@ifpropundefined</code> .....	7, 485, 489,
2069, 2472, 2484, 2576, 2933, 2988		519, 548, 615, 828, 1410, 1660, 2396	
<code>\ZREF@call</code> 1171, 1186, 1195, 1199, 1207		<code>\ZREF@ifrefcontainsprop</code> ...	787, 795
<code>\ZREF@def@abspos</code> .....		<code>\zref@ifrefcontainsprop</code> .....	
.... 2634, 2637, 2640, 2643, 2645		... 8, 783, 1412, 2357, 2453, 2454	
<code>\zref@def@absposnumx</code> .....	2639	<code>\ZREF@ifrefundefined</code> .....	
<code>\ZREF@def@absposnumy</code> .....	2645	..... 765, 768, 1172, 1183, 1193	
<code>\zref@def@absposnumy</code> .....	2642	<code>\zref@ifrefundefined</code> .....	
<code>\zref@def@absposx</code> .....	2633	..... 8, 760, 770, 776, 784,	
<code>\zref@def@absposy</code> .....	2636	827, 1184, 1365, 1553, 1789,	
<code>\ZREF@def@extract</code> .....	846, 848	2605, 2617, 2653, 2683, 2691, 2962	
<code>\zref@def@extract</code> .....	8, 845	<code>\ZREF@immediatefalse</code> .....	678
<code>\ZREF@def@extractdefault</code> ...	857, 859	<code>\ZREF@immediatetrue</code> .....	675, 704
<code>\zref@def@extractdefault</code> .....	856	<code>\ZREF@label</code> 603, 627, 637, 640, 710, 1071	
<code>\ZREF@default</code> .....	562, 563, 572	<code>\zref@label</code> .....	7, 597, 977
<code>\zref@default</code> ...	8, 531, 807, 930, 932	<code>\zref@labelbykv</code> .....	630, 984
<code>\ZREF@delprop</code> .....		<code>\zref@labelbylist</code> .....	
..... 413, 416, 418, 453, 456, 458		.... 7, 598, 600, 1112, 1788, 2550	
<code>\zref@delprop</code> .....	412, 452	<code>\zref@labelbyprops</code> .....	7, 88,
<code>\ZREF@df@dot</code> .....	2947, 2951, 2980	610, 1170, 2555, 2560, 2960, 2974	
<code>\ZREF@df@min</code> .....	2944, 2949, 2967	<code>\zref@listexists</code> ....	6, 303, 322,
<code>\ZREF@df@unit</code> .....	2941, 2950, 2961	342, 361, 377, 396, 419, 459, 602	
<code>\ZREF@dotfill</code> .....	2963, 2970, 2979	<code>\zref@listforloop</code> .....	321, 657
<code>\ZREF@ENV@line</code> .....	2998, 3001	<code>\zref@listpageattr</code> .....	1492
<code>\zref@env@line</code> .....	2993, 2994	<code>\zref@listpagelayout</code> .....	1331
<code>\ZREF@extract</code> ....	804, 821, 824, 876	<code>\zref@localaddprop</code> .....	395
<code>\zref@extract</code> ....	7, 95, 96, 109,	<code>\zref@localaddprops</code> .....	376
140, 804, 824, 853, 871, 876,		<code>\zref@localdelprop</code> ....	415, 455, 669
993, 1121, 1217, 1367, 1414,		<code>\ZREF@mainlist</code> ....	598, 936, 939,
1415, 1539, 1576, 1796, 1797,		942, 1021, 1035, 1039, 1832, 2477	
1890, 2564, 2567, 2754, 2758,		<code>\ZREF@makeperpage@opt</code> ...	1761, 1764
2761, 2767, 2773, 2776, 2781,		<code>\ZREF@MARKS@DefineProp</code> .....	
2785, 2806, 2835, 2849, 2851,		..... 1623, 1624, 1625, 1659	
2853, 2858, 2862, 2867, 2868,		<code>\zref@marks@register</code> .....	
2872, 2876, 2883, 2887, 2891,		..... 1605, 1610, 1642, 1681	
2898, 2903, 2906, 2907, 2912, 2916		<code>\ZREF@name</code> .....	229, 259, 270,
<code>\ZREF@extractdefault</code> 825, 841, 844, 875		292, 295, 305, 346, 364, 381,	
<code>\zref@extractdefault</code> . 7, 116, 117,		399, 490, 509, 521, 525, 549,	
817, 844, 864, 870, 875, 1077,		564, 616, 680, 692, 1609, 2490, 2502	
1078, 1175, 1190, 1236, 1799,		<code>\ZREF@NAME@bot</code> .....	1638, 1658
2341, 2344, 2345, 2349, 2350,		<code>\ZREF@NAME@first</code> .....	1637, 1657
2353, 2355, 2356, 2358, 2360,		<code>\ZREF@NAME@top</code> .....	1636, 1656
2591, 2598, 2657, 2685, 2850, 2901		<code>\zref@newlabel</code> .....	
<code>\ZREF@false</code> .....	677, 687	..... 7, 282, 285, 750, 2240, 2326	
<code>\ZREF@foundfalse</code> .....	2402	<code>\zref@newlist</code> .....	6, 288,
<code>\ZREF@foundtrue</code> .....	2449	939, 1061, 1104, 1633, 1718, 2511	
<code>\ZREF@getcurrent</code> ..	582, 593, 596, 874	<code>\ZREF@newprop</code> .....	498, 501, 504
<code>\zref@getcurrent</code> ....	7, 596, 869, 874	<code>\zref@newprop</code> .....	6, 12, 13, 14,
<code>\zref@hex</code> .....		75, 495, 940, 941, 944, 951, 955,	
1443, 1445, 1458, 1470, 1485, 1488		959, 1020, 1034, 1038, 1260,	

1276, 1280, 1284, 1288, 1320,  
 1321, 1322, 1325, 1326, 1327,  
 1443, 1445, 1458, 1470, 1664,  
 1672, 2075, 2076, 2077, 2397,  
 2513, 2514, 2516, 2517, 2992, 2993  
 \ZREF@NewPropAnchor .. 943, 2126, 2476  
 \ZREF@NewPropPageValue 958, 1106, 1717  
 \ZREF@NewPropTheotype .... 954, 2297  
 \ZREF@NewPropTitle ... 949, 1831, 2127  
 \ZREF@nextpage ..... 1163, 1167  
 \ZREF@nil 545, 797, 836, 2213, 2219,  
 2225, 2230, 2240, 2256, 2285,  
 2293, 2384, 2391, 2400, 2403, 2442  
 \ZREF@NOVALUE ..... 803  
 \ZREF@novalue ..... 796, 797, 803  
 \ZREF@np@call@next .. 1157, 1161, 1216  
 \ZREF@np@call@nonext 1154, 1160, 1212  
 \ZREF@np@call@unknown 1150, 1159, 1208  
 \ZREF@np@setup@i ..... 1149, 1152  
 \ZREF@np@setup@ii ..... 1153, 1156  
 \ZREF@number 924, 1539, 1545, 1607, 2690  
 \ZREF@org@@begintheorem ..... 2057  
 \ZREF@org@@caption ..... 1897  
 \ZREF@org@@chapter ..... 1909, 1965  
 \ZREF@org@@opargbegintheorem .. 2042  
 \ZREF@org@@part ..... 1903  
 \ZREF@org@@schapter ..... 1927  
 \ZREF@org@@sect ..... 1915  
 \ZREF@org@@spart ..... 1921  
 \ZREF@org@@ssect ..... 1933  
 \ZREF@org@@stpelt .. 1748, 1753, 1757  
 \ZREF@org@beamer@section ..... 1983  
 \ZREF@org@beamer@subsection ... 1989  
 \ZREF@org@beamer@subsubsection 1995  
 \ZREF@org@descriptionlabel .... 1939  
 \ZREF@org@lst@MakeCaption ..... 2035  
 \ZREF@org@LT@c@ption ..... 2021  
 \ZREF@org@M@sect ..... 1974  
 \ZREF@org@refstepcounter ..... 1044  
 \ZREF@org@stepcounter 1722, 1727, 1752  
 \ZREF@org@testdef .....  
 ..... 1338, 1340, 1499, 1501  
 \ZREF@org@thepage ..... 714, 718  
 \ZREF@org@ttl@sect@i ..... 2003  
 \ZREF@org@ttl@straight@i ..... 2014  
 \ZREF@org@write ..... 705, 706  
 \ZREF@P ..... 505,  
 506, 508, 510, 519, 522, 526,  
 536, 537, 539, 540, 541, 545,  
 721, 725, 726, 735, 739, 744, 745  
 \ZREF@pa@AfterLastShipout 1495, 1593  
 \ZREF@pa@AtVeryEnd .. 1508, 1511, 1582  
 \ZREF@pa@ListPage ..... 1529, 1547  
 \ZREF@pa@listtrue ..... 1493  
 \ZREF@page@max .. 1336, 1402, 1497, 1559  
 \zref@pageattr ..... 1537  
 \zref@pageattr@used ..... 1544  
 \ZREF@pagenum@last ..... 1189, 1192  
 \ZREF@pagenum@this .....  
 ..... 1174, 1179, 1182, 1192, 1198  
 \ZREF@par ..... 508, 533  
 \ZREF@param .....  
 . 422, 423, 442, 460, 477, 646,  
 647, 648, 652, 673, 674, 677, 682  
 \ZREF@patch . 249, 1041, 1894, 1900,  
 1906, 1912, 1918, 1924, 1930,  
 1936, 1967, 1980, 1986, 1992,  
 2000, 2006, 2019, 2027, 2039, 2054  
 \zref@pdfpageattr .....  
 ..... 1454, 1537, 1543, 1554  
 \zref@pdfpageattr@used ..... 1455  
 \zref@pdfpagesattr .. 1466, 1574, 1587  
 \zref@pdfpagesattr@used . 1467, 1579  
 \ZREF@pl@AfterLastShipout 1334, 1421  
 \ZREF@pl@AtVeryEnd ..... 1347, 1350  
 \ZREF@pl@ListEntry .....  
 . 1369, 1370, 1371, 1372, 1373,  
 1374, 1375, 1376, 1377, 1378,  
 1379, 1380, 1381, 1382, 1383,  
 1384, 1385, 1386, 1387, 1388,  
 1389, 1390, 1391, 1392, 1393,  
 1394, 1395, 1396, 1397, 1398, 1409  
 \ZREF@pl@ListPage ..... 1354, 1360  
 \ZREF@pl@listtrue ..... 1332  
 \zref@pos@label@used ..... 2663  
 \zref@pos@num@used ..... 2677  
 \zref@prop 324, 332, 333, 337, 658, 662  
 \zref@propexists .... 7, 344, 362,  
 379, 397, 488, 578, 647, 668, 987  
 \ZREF@refname@next .....  
 ..... 1177, 1184, 1193, 1217  
 \ZREF@refname@this .....  
 ..... 1169, 1170, 1172, 1175  
 \ZREF@RefPrefix . 284, 286, 1342, 1503  
 \ZREF@refused ..... 773, 775  
 \zref@refused .....  
 ... 8, 769, 772, 849, 860, 992,  
 999, 1088, 1089, 1124, 1239,  
 1545, 1580, 1888, 2652, 2660, 2673  
 \zref@require@unique .....  
 ..... 10, 909, 1721, 2938  
 \ZREF@Robust ..... 232,  
 238, 244, 285, 288, 303, 310,  
 341, 360, 376, 395, 412, 415,  
 452, 455, 488, 495, 547, 577,  
 597, 600, 610, 630, 702, 772,  
 845, 856, 867, 883, 909, 929,  
 935, 1123, 1544, 1579, 1835,  
 1848, 2633, 2636, 2639, 2642, 2648  
 \ZREF@SavedEscapechar ..... 461, 468  
 \zref@savepos ... 18, 2520, 2536, 2542  
 \ZREF@savepos@ok ..... 2569, 2581  
 \zref@setcurrent .....  
 ..... 6, 81, 541, 577, 697, 1043  
 \zref@setdefault ..... 8, 929, 932  
 \zref@setmainlist ..... 9, 935  
 \zref@showprop ..... 547  
 \ZREF@STAR ..... 1631, 1655  
 \ZREF@stripperperiod ..... 1859, 1867  
 \ZREF@temp .... 193, 200, 201, 202,  
 203, 204, 205, 206, 207, 208,  
 209, 210, 211, 212, 213, 214,  
 215, 216, 233, 234, 440, 441,

442, 720, 741, 742, 750, 1254,	\ZREF@xr@checkfile .. 2155, 2158, 2208
1268, 1269, 1270, 1271, 1272,	\ZREF@xr@checkkey ..... 2386, 2395
1273, 1274, 1293, 1294, 1295,	\ZREF@xr@checklist ..... 2256, <u>2384</u>
1296, 1298, 1299, 1300, 1301,	\zref@xr@ext ..... 20, <u>2078</u> , 2146
1302, 1303, 1304, 1305, 1306,	\ZREF@xr@externaldocument .....
1307, 1308, 1309, 1310, 1311,	..... 2133, 2136, <u>2140</u>
1312, 1313, 1314, 1315, 1316,	\ZREF@xr@externalfile .....
1317, 1341, 1342, 1434, 1447,	..... 2143, 2144, 2262, 2304
1460, 1472, 1475, 1481, 1482,	\ZREF@xr@file ... 2144, 2159, 2162,
1483, 1484, 1502, 1503, 1511,	2168, 2179, 2202, 2250, 2369, 2378
1512, 1513, 1514, 1567, 1568,	\ZREF@xr@filelist ..... 2142,
1569, 1570, 1630, 1631, 2008,	2200, 2203, 2205, 2206, 2234, 2235
2009, 2100, 2110, 2113, 2117,	\ZREF@xr@found . 2170, 2180, 2242, 2287
2656, 2659, 2660, 2787, 2790,	\ZREF@xr@graburl ..... 2146, 2148
2795, 2799, 2801, 2804, 2817,	\ZREF@xr@ignored@empty .....
2820, 2825, 2828, 2830, 2833, 2958	.... 2171, 2183, 2185, 2252, 2253
\ZREF@TempName .. 1606, 1618, 1619,	\ZREF@xr@ignored@ltx .....
1621, 1647, 1660, 1664, 1672, 1683	.... 2173, 2192, 2194, 2380, 2381
\ZREF@TempNum .....	\ZREF@xr@ignored@zref .....
1607, 1608, 1612, 1619, 1661, 1674	.... 2172, 2187, 2189, 2371, 2372
\zref@thepage ..... 13, <u>1120</u> , 1129	\ZREF@xr@line .. 2212, 2213, 2225, 2230
\zref@thepage@atbegshi@hook ....	\ZREF@xr@list ..... 2246, 2247
..... <u>1107</u> , <u>1111</u>	\ZREF@xr@ltx@ignorewarning .... <u>2375</u>
\zref@thepage@name .....	\ZREF@xr@newlabel ..... 2228, <u>2327</u>
..... 13, <u>1115</u> , 1121, 1124, 1178	\ZREF@xr@prefix ..... 2141, 2241,
\zref@thepage@refused ... <u>1123</u> , 1128	2277, 2281, 2286, 2312, 2319, 2323
\ZREF@titleref ..... 1884, 1886	\ZREF@xr@process@label .. 2230, 2285
\zref@titleref@cleanup .. <u>1835</u> , 1875	\ZREF@xr@process@zreflabel 2225, 2240
\zref@titleref@current .....	\ZREF@xr@processfile .... <u>2158</u> , <u>2211</u>
..... <u>949</u> , 1854, 1858, 1859, 1878	\ZREF@xr@processline .... <u>2213</u> , <u>2219</u>
\ZREF@titleref@hook .....	\ZREF@xr@refname .....
..... <u>1834</u> , 1838, 1842, 1865	2241, 2267, 2274, 2286, 2309, 2316
\zref@titleref@setcurrent .....	\ZREF@xr@relax ..... 2329, 2416
. <u>1848</u> , 1896, 1902, 1908, 1914,	\ZREF@xr@scanparams ..... 2291, <u>2400</u>
1920, 1926, 1932, 1938, 1946,	\ZREF@xr@scantitleref ... 2403, <u>2442</u>
1949, 1953, 1957, 1959, 1970,	\ZREF@xr@temp ..... 2415, 2416
1972, 1982, 1988, 1994, 2002,	\ZREF@xr@tempname 2244, 2245, 2265,
2010, 2012, 2022, 2031, 2041, 2056	2270, 2281, 2289, 2290, 2307, 2323
\zref@titleref@stripperiodtrue 1847	\ZREF@xr@temprefname .....
\ZREF@true ..... 674, <u>688</u>	..... 2245, 2257, 2259,
\ZREF@u@getcurrent ..... <u>591</u>	2275, 2290, 2292, 2299, 2302, 2317
\zref@unhex .... 1486, 1489, 1538, 1575	\ZREF@xr@theURL .....
\ZREF@UpdatePdfTeX ... <u>247</u> , 2493, 2506	2108, 2110, 2112, 2118, 2153, 2434
\ZREF@value ..... 557, 558, 571	\ZREF@xr@tolabel ... 2281, 2323, <u>2330</u>
\ZREF@wrapper@babel ..... 900, 906	\ZREF@xr@URL ... <u>2096</u> , 2106, 2107, 2108
\zref@wrapper@babel .....	\ZREF@xr@url ... 2149, 2151, 2152, 2460
..... 10, 140, 765, 773, 846,	\ZREF@xr@urlcheck .. 2265, 2307, <u>2452</u>
857, <u>883</u> , 977, 984, 988, 1085,	\ZREF@xr@zref@ignorewarning ....
1884, 2634, 2637, 2640, 2643, 2649	..... 2277, 2319, <u>2366</u>
\zref@wrapper@immediate .....	\ZREF@xr@zref@newlabel .. 2223, 2326
..... 10, 87, 636, <u>702</u> , 1070	\ZREF@xr@zreflabelfalse ..... 2132
\ZREF@wrapper@unexpanded ... <u>867</u> , 881	\ZREF@xr@zreflabeltrue ..... 2135
\zref@wrapper@unexpanded .....	\ZREF@zref ..... 988, 991
..... 10, 868, 873, <u>878</u> , 2336	\ZREF@zsavepos . 2533, 2550, 2555, 2560
\ZREF@wu@extract ..... 819, 871	\zrefused 11, 92, 93, 161, 162, 163, 998
\ZREF@wu@extractdefault ... <u>839</u> , 870	\zruns ..... 16, <u>1693</u>
\ZREF@wu@getcurrent ..... 591, 869	\zsavepos ..... 17, 157, 158, <u>2548</u>
\ZREF@X ..... 497, 500, 537	\zsaveposx ..... 17, <u>2553</u>
\zref@xr@ ..... 2090	\zsaveposy ..... <u>2558</u>
\ZREF@xr@@AddUrl ..... 2102, <u>2105</u>	\zthepage ..... 13, <u>1126</u>
\ZREF@xr@@input ..... 2233, <u>2328</u>	\ztitleref ..... 17, <u>1883</u>
\ZREF@xr@AddURL .... <u>2098</u> , 2151, 2430	\ztitlerefsetup ..... 17, <u>1868</u>

<code>\ztotpages</code>	.....	<a href="#">15</a> , <a href="#">124</a> , <a href="#">1235</a>	<code>\zunmakeperpage</code>	.....	<a href="#">16</a> , <a href="#">1813</a>
<code>\zunknownnextpagename</code>	.	<a href="#">14</a> , <a href="#">1166</a> , <a href="#">1209</a>	<code>\zxrsetup</code>	.....	<a href="#">19</a> , <a href="#">2093</a>