

The package `nicematrix`*

F. Pantigny
fpantigny@wanadoo.fr

February 5, 2023

Abstract

The LaTeX package `nicematrix` provides new environments similar to the classical environments `{tabular}`, `{array}` and `{matrix}` of `array` and `amsmath` but with extended features.

$$\begin{array}{c} L_1 \\ L_2 \\ \vdots \\ L_n \end{array} \begin{array}{c} C_1 \\ C_2 \cdots \cdots C_n \end{array} \begin{bmatrix} a_{11} & a_{12} & \cdots & a_{1n} \\ a_{21} & a_{22} & \cdots & a_{2n} \\ \vdots & \vdots & \ddots & \vdots \\ a_{n1} & a_{n2} & \cdots & a_{nn} \end{bmatrix}$$

Product	dimensions (cm)			Price
	L	l	h	
small	3	5.5	1	30
standard	5.5	8	1.5	50.5
premium	8.5	10.5	2	80
extra	8.5	10	1.5	85.5
special	12	12	0.5	70

The package `nicematrix` is entirely contained in the file `nicematrix.sty`. This file may be put in the current directory or in a `texmf` tree. However, the best is to install `nicematrix` with a TeX distribution such as MiKTeX, TeX Live or MacTeX.

Remark: If you use LaTeX via Internet with, for example, Overleaf, you can upload the file `nicematrix.sty` in the repertory of your project in order to take full advantage of the latest version de `nicematrix`.¹

This package can be used with `xelatex`, `lualatex`, `pdflatex` but also by the classical workflow `latex-dvips-ps2pdf` (or Adobe Distiller). However, the file `nicematrix.dtx` of the present documentation should be compiled with XeLaTeX.

This package requires and **loads** the packages `l3keys2e`, `array`, `amsmath`, `pgfcore` and the module `shapes` of PGF (`tikz`, which is a layer over PGF, is *not* loaded). The final user only has to load the package with `\usepackage{nicematrix}`.

The idea of `nicematrix` is to create PGF nodes under the cells and the positions of the rules of the tabular created by `array` and to use these nodes to develop new features. As usual with PGF, the coordinates of these nodes are written in the `aux` to be used on the next compilation and that's why `nicematrix` may need **several compilations**.²

Most features of `nicematrix` may be used without explicit use of PGF or Tikz (which, in fact, is not loaded by default).

A command `\NiceMatrixOptions` is provided to fix the options (the scope of the options fixed by this command is the current TeX group: they are semi-global).

*This document corresponds to the version 6.13f of `nicematrix`, at the date of 2023/02/05.

¹The latest version of the file `nicematrix.sty` may be downloaded from the SVN server of TeXLive:
<https://www.tug.org/svn/texlive/trunk/Master/texmf-dist/tex/latex/nicematrix/nicematrix.sty>

²If you use Overleaf, Overleaf will do automatically the right number of compilations.

1 The environments of this package

The package `nicematrix` defines the following new environments.

<code>{NiceTabular}</code>	<code>{NiceArray}</code>	<code>{NiceMatrix}</code>
<code>{NiceTabular*}</code>	<code>{pNiceArray}</code>	<code>{pNiceMatrix}</code>
<code>{NiceTabularX}</code>	<code>{bNiceArray}</code>	<code>{bNiceMatrix}</code>
	<code>{BNiceArray}</code>	<code>{BNiceMatrix}</code>
	<code>{vNiceArray}</code>	<code>{vNiceMatrix}</code>
	<code>{VNiceArray}</code>	<code>{VNiceMatrix}</code>

The environments `{NiceArray}`, `{NiceTabular}` and `{NiceTabular*}` are similar to the environments `{array}`, `{tabular}` and `{tabular*}` of the package `array` (which is loaded by `nicematrix`).

The environments `{pNiceArray}`, `{bNiceArray}`, etc. have no equivalent in `array`.

The environments `{NiceMatrix}`, `{pNiceMatrix}`, etc. are similar to the corresponding environments of `amsmath` (which is loaded by `nicematrix`): `{matrix}`, `{pmatrix}`, etc.

The environment `{NiceTabularX}` is similar to the environment `{tabularx}` from the eponymous package.³

It's recommended to use primarily the classical environments and to use the environments of `nicematrix` only when some feature provided by these environments is used (this will save memory).

All the environments of the package `nicematrix` accept, between square brackets, an optional list of `key=value` pairs. **There must be no space before the opening bracket (`[`) of this list of options.**

2 The vertical space between the rows

It's well known that some rows of the arrays created by default with LaTeX are, by default, too close to each other. Here is a classical example.

```
\begin{pmatrix}
\frac{1}{2} & -\frac{1}{2} \\
\frac{1}{3} & \frac{1}{4}
\end{pmatrix}
```

Inspired by the package `cellspace` which deals with that problem, the package `nicematrix` provides two keys `cell-space-top-limit` and `cell-space-bottom-limit` similar to the parameters `\cellspacetoplimit` and `\cellspacebottomlimit` of `cellspace`.

There is also a key `cell-space-limits` to set both parameters at once.

The initial value of these parameters is 0 pt in order to have for the environments of `nicematrix` the same behaviour as those of `array` and `amsmath`. However, a value of 1 pt would probably be a good choice and we suggest to set them with `\NiceMatrixOptions`.⁴

```
\NiceMatrixOptions{cell-space-limits = 1pt}

\begin{pNiceMatrix}
\frac12 & -\frac12 \\
\frac13 & \frac14
\end{pNiceMatrix}
```

³In fact, it's possible to use directly the `X` columns in the environment `{NiceTabular}` (and the required width for the tabular is fixed by the key `width`): cf. p. 21

⁴One should remark that these parameters apply also to the columns of type `S` of `siunitx` whereas the package `cellspace` is not able to act on such columns of type `S`.

3 The vertical position of the arrays

The package `nicematrix` provides a option `baseline` for the vertical position of the arrays. This option takes in as value an integer which is the number of the row on which the array will be aligned.

```
$A = \begin{pNiceMatrix}[baseline=2]
\frac{1}{\sqrt{1+p^2}} & p & 1-p \\
1 & 1 & 1 \\
1 & p & 1+p
\end{pNiceMatrix}$
```

$$A = \begin{pmatrix} \frac{1}{\sqrt{1+p^2}} & p & 1-p \\ 1 & 1 & 1 \\ 1 & p & 1+p \end{pmatrix}$$

It's also possible to use the option `baseline` with one of the special values `t`, `c` or `b`. These letters may also be used absolutely like the option of the environments `{tabular}` and `{array}` of `array`. The initial value of `baseline` is `c`.

In the following example, we use the option `t` (equivalent to `baseline=t`) immediately after an `\item` of list. One should remark that the presence of a `\hline` at the beginning of the array doesn't prevent the alignment of the baseline with the baseline of the first row (with `{tabular}` or `{array}` of `array`, one must use `\firsthline`).

```
\begin{enumerate}
\item an item
\smallskip
\item \renewcommand{\arraystretch}{1.2}
$\begin{NiceArray}[t]{lcccccc}
\hline
n & 0 & 1 & 2 & 3 & 4 & 5 \\
u_n & 1 & 2 & 4 & 8 & 16 & 32
\hline
\end{NiceArray}$
\end{enumerate}
```

1. an item

2.	n	0	1	2	3	4	5
	u_n	1	2	4	8	16	32

However, it's also possible to use the tools of `booktabs`⁵: `\toprule`, `\bottomrule`, `\midrule`, etc.

```
\begin{enumerate}
\item an item
\smallskip
\item
$\begin{NiceArray}[t]{lcccccc}
\toprule
n & 0 & 1 & 2 & 3 & 4 & 5 \\
\midrule
u_n & 1 & 2 & 4 & 8 & 16 & 32
\bottomrule
\end{NiceArray}$
\end{enumerate}
```

1. an item

2.	n	0	1	2	3	4	5
	u_n	1	2	4	8	16	32

It's also possible to use the key `baseline` to align a matrix on an horizontal rule (drawn by `\hline`). In this aim, one should give the value `line-i` where *i* is the number of the row *following* the horizontal rule.

```
\NiceMatrixOptions{cell-space-limits=1pt}

$A=\begin{pNiceArray}{cc|cc}[baseline=line-3]
\dfrac{1}{A} & \dfrac{1}{B} & 0 & 0 \\
\dfrac{1}{C} & \dfrac{1}{D} & 0 & 0 \\
\hline
0 & 0 & A & B \\
0 & 0 & D & D
\end{pNiceArray}$
```

$$A = \left(\begin{array}{cc|cc} \frac{1}{A} & \frac{1}{B} & 0 & 0 \\ \frac{1}{C} & \frac{1}{D} & 0 & 0 \\ \hline 0 & 0 & A & B \\ 0 & 0 & D & D \end{array} \right)$$

⁵The extension `booktabs` is *not* loaded by `nicematrix`.

4 The blocks

4.1 General case

In the environments of `nicematrix`, it's possible to use the command `\Block` in order to place an element in the center of a rectangle of merged cells of the array.⁶

The command `\Block` must be used in the upper leftmost cell of the array with two arguments.

- The first argument is the size of the block with the syntax i - j where i is the number of rows of the block and j its number of columns.

If this argument is empty, its default value is 1-1. If the number of rows is not specified, or equal to *, the block extends until the last row (idem for the columns).

- The second argument is the content of the block. It's possible to use `\\` in that content to have a content on several lines. In `{NiceTabular}`, `{NiceTabular*}` and `{NiceTabularX}`, the content of the block is composed in text mode whereas, in the other environments, it is composed in math mode.

Here is an example of utilisation of the command `\Block` in mathematical matrices.

```
$\begin{bNiceArray}{cw{c}{1cm}c|c}[margin]
\Block{3-3}{A} & & 0 \\
& & \Vdots \\
& & 0 \\
\hline
0 & \Cdots & 0 & 0
\end{bNiceArray}$
```

$$\left[\begin{array}{c|c} A & \begin{smallmatrix} 0 \\ \vdots \\ 0 \end{smallmatrix} \\ \hline 0 \cdots \cdots 0 & 0 \end{array} \right]$$

One may wish to raise the size of the “A” placed in the block of the previous example. Since this element is composed in math mode, it's not possible to use directly a command like `\large`, `\Large` and `\LARGE`. That's why the command `\Block` provides an option between angle brackets to specify some TeX code which will be inserted before the beginning of the math mode.⁷

```
$\begin{bNiceArray}{cw{c}{1cm}c|c}[margin]
\Block{3-3}<\Large>{A} & & 0 \\
0 & & \Vdots \\
& & 0 \\
\hline
0 & \Cdots & 0 & 0
\end{bNiceArray}$
```

$$\left[\begin{array}{c|c} A & \begin{smallmatrix} 0 \\ \vdots \\ 0 \end{smallmatrix} \\ \hline 0 \cdots \cdots 0 & 0 \end{array} \right]$$

It's possible to set the horizontal position of the block with one of the keys `l`, `c` and `r`.

```
$\begin{bNiceArray}{cw{c}{1cm}c|c}[margin]
\Block[r]{3-3}<\LARGE>{A} & & 0 \\
& & \Vdots \\
& & 0 \\
\hline
0 & \Cdots & 0 & 0
\end{bNiceArray}$
```

$$\left[\begin{array}{c|c} A & \begin{smallmatrix} 0 \\ \vdots \\ 0 \end{smallmatrix} \\ \hline 0 \cdots \cdots 0 & 0 \end{array} \right]$$

In fact, the command `\Block` accepts as first optional argument (between square brackets) a list of couples `key=value`. The available keys are as follows:

⁶The spaces after a command `\Block` are deleted.

⁷This argument between angular brackets may also be used to insert a command of font such as `\bfseries` when the command `\\` is used in the content of the block.

- the keys `l`, `c` and `r` are used to fix the horizontal position of the content of the block, as explained previously;
- the key `fill` takes in as value a color and fills the block with that color;
- the key `draw` takes in as value a color and strokes the frame of the block with that color (the default value of that key is the current color of the rules of the array);
- the key `color` takes in as value a color and apply that color the content of the block but draws also the frame of the block with that color;
- the keys `hlines`, `vlines` and `hvlines` draw all the corresponding rules in the block;⁸
- the key `line-width` is the width of the rules (this key is meaningful only when one of the keys `draw`, `hvlines`, `vlines` and `hlines` is used);
- the key `rounded-corners` requires rounded corners (for the frame drawn by `draw` and the shape drawn by `fill`) with a radius equal to the value of that key (the default value is 4 pt⁹);
- the keys `t` and `b` fix the base line that will be given to the block when it has a multi-line content (the lines are separated by `\\`);
- when the key `tikz` is used, the Tikz path corresponding of the rectangle which delimits the block is executed with Tikz¹⁰ by using as options the value of that key `tikz` (which must be a list of keys allowed for a Tikz path). For examples, cf. p. 49;
- the key `name` provides a name to the rectangular Tikz node corresponding to the block; it's possible to use that name with Tikz in the `\CodeAfter` of the environment (cf. p. 29);
- the key `respect-arraystretch` prevents the setting of `\arraystretch` to 1 at the beginning of the block (which is the behaviour by default) ;
- the key `borders` provides the ability to draw only some borders of the blocks; the value of that key is a (comma-separated) list of elements covered by `left`, `right`, `top` and `bottom`; it's possible, in fact, in the list which is the value of the key `borders`, to add an entry of the form `tikz={list}` where `list` is a list of couples `key=value` of Tikz specifying the graphical characteristics of the lines that will be drawn (for an example, see p. 52).

One must remark that, by default, the commands `\Blocks` don't create space. There is exception only for the blocks `mono-row` and the blocks `mono-column` as explained just below.

In the following example, we have had to enlarge by hand the columns 2 and 3 (with the construction `wc{...}` of `array`).

```
\begin{NiceTabular}{cwc{2cm}wc{3cm}c}
rose      & tulip & daisy & dahlia \\
violet
& \Block[draw=red,fill=[RGB]{204,204,255},rounded-corners]{2-2}
&          {\LARGE Some beautiful flowers}
& & marigold \\
iris & & & lis \\
arum & periwinkle & forget-me-not & hyacinth
\end{NiceTabular}
```

rose	tulip	daisy	dahlia
violet	Some beautiful flowers		marigold
iris			lis
arum	periwinkle	forget-me-not	hyacinth

⁸However, the rules are not drawn in the sub-blocks of the block, as always with `nicematrix`: the rules are not drawn in the blocks (cf. section 5 p. 7).

⁹This value is the initial value of the *rounded corners* of Tikz.

¹⁰Tikz should be loaded (by default, `nicematrix` only loads PGF) and, if it's not, an error will be raised.

4.2 The mono-column blocks

The mono-column blocks have a special behaviour.

- The natural width of the contents of these blocks is taken into account for the width of the current column.
In the columns with a fixed width (columns `w{...}{...}`, `p{...}`, `b{...}`, `m{...}` and `X`), the content of the block is formatted as a paragraph of that width.
- The specification of the horizontal position provided by the type of column (`c`, `r` or `l`) is taken into account for the blocks.
- The specifications of font specified for the column by a construction `>{...}` in the preamble of the array are taken into account for the mono-column blocks of that column (this behaviour is probably expected).

```
\begin{NiceTabular}{@{}>{\bfseries}lr@{}} \hline
\Block{2-1}{John}    & 12 \\
                    & 13 \\ \hline
Steph               & 8  \\ \hline
\Block{3-1}{Sarah}   & 18 \\
                    & 17 \\
                    & 15 \\ \hline
Ashley              & 20 \\ \hline
Henry               & 14 \\ \hline
\Block{2-1}{Madison} & 15 \\
                    & 19 \\ \hline
\end{NiceTabular}
```

John	12
	13
Steph	8
	18
Sarah	17
	15
Ashley	20
Henry	14
	15
Madison	19

4.3 The mono-row blocks

For the mono-row blocks, the natural height and depth are taken into account for the height and depth of the current row (as does a standard `\multicolumn` of LaTeX).

4.4 The mono-cell blocks

A mono-cell block inherits all the properties of the mono-row blocks and mono-column blocks.

At first sight, one may think that there is no point using a mono-cell block. However, there are some good reasons to use such a block.

- It's possible to use the command `\` in a (mono-cell) block.
- It's possible to use the option of horizontal alignment of the block in derogation of the type of column given in the preamble of the array.
- It's possible to draw a frame around the cell with the key `draw` of the command `\Block` and to fill the background with rounded corners with the keys `fill` and `rounded-corners`.¹¹
- It's possible to draw one or several borders of the cell with the key `borders`.

¹¹If one simply wishes to color the background of a unique cell, there is no point using the command `\Block`: it's possible to use the command `\cellcolor` (when the key `colortbl-like` is used).

```

\begin{NiceTabular}{cc}
\toprule
Writer & \Block[1]{year of birth} \\
\midrule
Hugo & 1802 \\
Balzac & 1799 \\
\bottomrule
\end{NiceTabular}

```

Writer	year of birth
Hugo	1802
Balzac	1799

We recall that if the first mandatory argument of `\Block` is left blank, the block is mono-cell.¹²

4.5 Horizontal position of the content of the block

By default, the horizontal position of the content of a block is computed by using the positions of the *contents* of the columns implied in that block. That's why, in the following example, the header “First group” is correctly centered despite the instruction `!\qquad` in the preamble which has been used to increase the space between the columns (this is not the behaviour of `\multicolumn`).

```

\begin{NiceTabular}{@{}c!\qquad ccc!\qquad ccc@{}}
\toprule
Rank & \Block{1-3}{First group} & & & \Block{1-3}{Second group} \\
& 1A & 1B & 1C & 2A & 2B & 2C \\
\midrule
1 & 0.657 & 0.913 & 0.733 & 0.830 & 0.387 & 0.893 \\
2 & 0.343 & 0.537 & 0.655 & 0.690 & 0.471 & 0.333 \\
3 & 0.783 & 0.885 & 0.015 & 0.306 & 0.643 & 0.263 \\
4 & 0.161 & 0.708 & 0.386 & 0.257 & 0.074 & 0.336 \\
\bottomrule
\end{NiceTabular}

```

Rank	First group			Second group		
	1A	1B	1C	2A	2B	2C
1	0.657	0.913	0.733	0.830	0.387	0.893
2	0.343	0.537	0.655	0.690	0.471	0.333
3	0.783	0.885	0.015	0.306	0.643	0.263
4	0.161	0.708	0.386	0.257	0.074	0.336

In order to have an horizontal positionning of the content of the block computed with the limits of the columns of the LaTeX array (and not with the contents of those columns), one may use the key `L`, `R` and `C` of the command `\Block`.

5 The rules

The usual techniques for the rules may be used in the environments of `nicematrix` (excepted `\vline`). However, there is some small differences with the classical environments.

¹²One may consider that the default value of the first mandatory argument of `\Block` is `1-1`.

5.1 Some differences with the classical environments

5.1.1 The vertical rules

In the environments of `nicematrix`, the vertical rules specified by `|` in the preambles of the environments are never broken, even by an incomplete row or by a double horizontal rule specified by `\hline\hline` (there is no need to use the package `hhline`).

```
\begin{NiceTabular}{|c|c|} \hline
First & Second \\ \hline\hline
Peter & \\ \hline
Mary & George \\ \hline
\end{NiceTabular}
```

First	Second
Peter	
Mary	George

However, the vertical rules are not drawn in the blocks (created by `\Block`: cf. p. 4) nor in the corners (created by the key `corner`: cf. p. 10) nor in the potential exterior rows (created by the keys `first-row` and `last-row`: cf. p. 22).

If you use `booktabs` (which provides `\toprule`, `\midrule`, `\bottomrule`, etc.) and if you really want to add vertical rules (which is not in the spirit of `booktabs`), you should notice that the vertical rules drawn by `nicematrix` are compatible with `booktabs`.

```
$\begin{NiceArray}{|cccc|} \toprule
a & b & c & d \\ \midrule
1 & 2 & 3 & 4 \\
1 & 2 & 3 & 4 \\ \bottomrule
\end{NiceArray}$
```

<i>a</i>	<i>b</i>	<i>c</i>	<i>d</i>
1	2	3	4
1	2	3	4

However, it's still possible to define a specifier (named, for instance, `I`) to draw vertical rules with the standard behaviour of `array`.

```
\newcolumnntype{I}{!{\vrule}}
```

5.1.2 The command `\cline`

The horizontal and vertical rules drawn by `\hline` and the specifier “`|`” make the array larger or wider by a quantity equal to the width of the rule (with `array` and also with `nicematrix`).

For historical reasons, this is not the case with the command `\cline`, as shown by the following example.

```
\setlength{\arrayrulewidth}{2pt}
\begin{tabular}{cccc} \hline
A&B&C&D \\ \cline{2-2}
A&B&C&D \\ \hline
\end{tabular}
```

A	B	C	D
A	<u>B</u>	C	D

In the environments of `nicematrix`, this situation is corrected (it's still possible to go to the standard behaviour of `\cline` with the key `standard-cline`).

```
\setlength{\arrayrulewidth}{2pt}
\begin{NiceTabular}{cccc} \hline
A&B&C&D \\ \cline{2}
A&B&C&D \\ \hline
\end{NiceTabular}
```

A	B	C	D
A	<u>B</u>	C	D

In the environments of `nicematrix`, an instruction `\cline{i}` is equivalent to `\cline{i-i}`.

5.2 The thickness and the color of the rules

The environments of `nicematrix` provide a key `rules/width` to set the width (in fact the thickness) of the rules in the current environment. In fact, this key merely sets the value of the length `\arrayrulewidth`.

It's well known that `colortbl` provides the command `\arrayrulecolor` in order to specify the color of the rules.

With `nicematrix`, it's possible to specify the color of the rules even when `colortbl` is not loaded. For sake of compatibility, the command is also named `\arrayrulecolor`. The environments of `nicematrix` also provide a key `rules/color` to fix the color of the rules in the current environment. This key sets the value locally (whereas `\arrayrulecolor` acts globally).

```
\begin{NiceTabular}{|ccc|}[rules/color=[gray]{0.9},rules/width=1pt]
\hline
rose & tulipe & lys \\
arum & iris & violette \\
muguet & dahlia & souci \\
\hline
\end{NiceTabular}
```

rose	tulipe	lys
arum	iris	violette
muguet	dahlia	souci

5.3 The tools of `nicematrix` for the rules

Here are the tools provided by `nicematrix` for the rules.

- the keys `hlines`, `vlines`, `hvlines` and `hvlines-except-borders`;
- the specifier “|” in the preamble (for the environments with preamble);
- the command `\Hline`.

All these tools don't draw the rules in the blocks nor in the empty corners (when the key `corners` is used), nor in the exterior rows and columns.

- These blocks are:
 - the blocks created by the command `\Block`¹³ presented p. 4;
 - the blocks implicitly delimited by the continuous dotted lines created by `\Cdots`, `\Vdots`, etc. (cf. p. 23).
- The corners are created by the key `corners` explained below (see p. 10).
- For the exterior rows and columns, see p. 22.

In particular, this remark explains the difference between the standard command `\hline` and the command `\Hline` provided by `nicematrix`.

New 6.13 The key `\Hline` takes in an optional argument (between square brackets) which is a list of `key=value` pairs. For the description of those keys, see `custom-line` on p. 11.

5.3.1 The keys `hlines` and `vlines`

The keys `hlines` and `vlines` (which draw, of course, horizontal and vertical rules) take in as value a list of numbers which are the numbers of the rules to draw.¹⁴

In fact, for the environments with delimiters (such as `{pNiceMatrix}` or `{bNiceArray}`), the key `vlines` don't draw the exterior rules (this is certainly the expected behaviour).

```
$\begin{pNiceMatrix}[vlines,rules/width=0.2pt]
1 & 2 & 3 & 4 & 5 & 6 \\
1 & 2 & 3 & 4 & 5 & 6 \\
1 & 2 & 3 & 4 & 5 & 6 \\
\end{pNiceMatrix}$
```

1	2	3	4	5	6
1	2	3	4	5	6
1	2	3	4	5	6

¹³And also the command `\multicolumn` but it's recommended to use instead `\Block` in the environments of `nicematrix`.

¹⁴It's possible to put in that list some intervals of integers with the syntax `i-j`.

5.3.2 The keys hvlines and hvlines-except-borders

The key `hvlines` (no value) is the conjunction of the keys `hlines` and `vlines`.

```
\setlength{\arrayrulewidth}{1pt}
\begin{NiceTabular}{cccc}[hvlines,rules/color=blue]
rose          & tulipe & marguerite & dahlia \\
violette     & \Block[draw=red]{2-2}{\LARGE fleurs} & & & souci \\
pervenche   & & & lys \\
arum        & iris & jacinthe & muguet
\end{NiceTabular}
```

rose	tulipe	marguerite	dahlia
violette	fleurs		souci
pervenche			lys
arum	iris	jacinthe	muguet

The key `hvlines-except-borders` is similar to the key `hvlines` but does not draw the rules on the horizontal and vertical borders of the array.

5.3.3 The (empty) corners

The four **corners** of an array will be designed by NW, SW, NE and SE (*north west, south west, north east and south east*).

For each of these corners, we will call *empty corner* (or simply *corner*) the reunion of all the empty rectangles starting from the cell actually in the corner of the array.¹⁵

However, it's possible, for a cell without content, to require `nicemarix` to consider that cell as not empty with the key `\NotEmpty`.

In the example on the right (where B is in the center of a block of size 2×2), we have colored in blue the four (empty) corners of the array.

When the key `corners` is used, `nicematrix` computes the (empty) corners and these corners will be taken into account by the tools for drawing the rules (the rules won't be drawn in the corners).

```
\NiceMatrixOptions{cell-space-top-limit=3pt}
\begin{NiceTabular}{*{6}{c}}[corners,hvlines]
& & & & A & \\
& & A & A & A & \\
& & & A & & \\
& & A & A & A & A & \\
A & A & A & A & A & A & A & \\
A & A & A & A & A & A & A & \\
& A & A & A & & & \\
& \Block{2-2}{B} & & A & & \\
& & & A & & \\
\end{NiceTabular}
```

				A	
		A	A	A	
			A		
		A	A	A	A
A	A	A	A	A	A
A	A	A	A	A	A
	A	A	A		
	B		A		
			A		

¹⁵For sake of completeness, we should also say that a cell contained in a block (even an empty cell) is not taken into account for the determination of the corners. That behaviour is natural. The precise definition of a “non-empty cell” is given below (cf. p. 47).

It's also possible to provide to the key `corners` a (comma-separated) list of corners (designed by NW, SW, NE and SE).

```
\NiceMatrixOptions{cell-space-top-limit=3pt}
\begin{NiceTabular}{*{6}{c}}[corners=NE,hvlines]
1\\
1&1\\
1&2&1\\
1&3&3&1\\
1&4&6&4&1\\
&&&&&1
\end{NiceTabular}
```

1					
1	1				
1	2	1			
1	3	3	1		
1	4	6	4	1	
					1

▷ The corners are also taken into account by the tools provided by `nicematrix` to color cells, rows and columns. These tools don't color the cells which are in the corners (cf. p. 14).

5.4 The command `\diagbox`

The command `\diagbox` (inspired by the package `diagbox`), allows, when it is used in a cell, to slash that cell diagonally downwards.

```
$\begin{NiceArray}{*{5}{c}}[hvlines]
\diagbox{x}{y} & e & a & b & c \\
e & e & a & b & c \\
a & a & e & c & b \\
b & b & c & e & a \\
c & c & b & a & e
\end{NiceArray}$
```

$\begin{smallmatrix} y \\ x \end{smallmatrix}$	<i>e</i>	<i>a</i>	<i>b</i>	<i>c</i>
<i>e</i>	<i>e</i>	<i>a</i>	<i>b</i>	<i>c</i>
<i>a</i>	<i>a</i>	<i>e</i>	<i>c</i>	<i>b</i>
<i>b</i>	<i>b</i>	<i>c</i>	<i>e</i>	<i>a</i>
<i>c</i>	<i>c</i>	<i>b</i>	<i>a</i>	<i>e</i>

It's possible to use the command `\diagbox` in a `\Block`.

5.5 Commands for customized rules

It's also possible to define commands and letters for customized rules with the key `custom-line` available in `\NiceMatrixOptions` and in the options of individual environments. That key takes in as argument a list of `key=value` pairs. First, there is three keys to define the tools which will be used to use that new type of rule.

- the key `command` is the name (without the backslash) of a command that will be created by `nicematrix` and that will be available for the final user in order to draw horizontal rules (similarly to `\hline`);
- New 6.11** the key `ccommand` is the name (without the backslash) of a command that will be created by `nicematrix` and that will be available for the final user to order to draw partial horizontal rules (similarly to `\cline`, hence the name `ccommand`): the argument of that command is a list of intervals of columns specified by the syntax *i* or *i-j*.¹⁶
- the key `letter` takes in as argument a letter¹⁷ that the user will use in the preamble of an environment with preamble (such as `\NiceTabular`) in order to specify a vertical rule.

We will now speak of the keys which describe the rule itself. Those keys may also be used in the (optional) argument of an individual command `\Hline`.

There is three possibilities.

- First possibility*

It's possible to specify composite rules, with a color and a color for the inter-rule space (as possible with `colortbl` for instance).

¹⁶It's recommended to use such commands only once in a row because each use will create space between the rows corresponding to the total width of the rule.

¹⁷The following letters are forbidden: `lcrpmbVX|()[]!@<>`

- the key `multiplicity` is the number of consecutive rules that will be drawn: for instance, a value of 2 will create double rules such those created by `\hline\hline` or `||` in the preamble of an environment;
- the key `color` sets the color of the rules ;
- the key `sep-color` sets the color between two successive rules (should be used only in conjunction with `multiplicity`).

That system may be used, in particular, for the definition of commands and letters to draw rules with a specific color (and those rules will respect the blocks and corners as do all the rules of `nicematrix`).

```
\begin{NiceTabular}{lcIcIc}[custom-line = {letter=I, color=blue}]
\hline
      & \Block{1-3}{dimensions} \\
      & L & l & h \\
\hline
Product A & 3 & 1 & 2 \\
Product B & 1 & 3 & 4 \\
Product C & 5 & 4 & 1 \\
\hline
\end{NiceTabular}
```

- *Second possibility*

It's possible to use the key `tikz` (if Tikz is loaded). In that case, the rule is drawn directly with Tikz by using as parameters the value of the key `tikz` which must be a list of *key=value* pairs which may be applied to a Tikz path.

By default, no space is reserved for the rule that will be drawn with Tikz. It is possible to specify a reservation (horizontal for a vertical rule and vertical for an horizontal one) with the key `total-width`. That value of that key, is, in some ways, the width of the rule that will be drawn (`nicematrix` does not compute that width from the characteristics of the rule specified in `tikz`).

	dimensions		
	L	l	H
Product A	3	1	2
Product B	1	3	4
Product C	5	4	1

Here is an example with the key `dotted` of Tikz.

```
\NiceMatrixOptions
{
  custom-line =
  {
    letter = I ,
    tikz = dotted ,
    total-width = \pgflinewidth
  }
}

\begin{NiceTabular}{cIcIc}
one & two & three \\
four & five & six \\
seven & eight & nine
\end{NiceTabular}
```

one	two	three
four	five	six
seven	eight	nine

- *Third possibility* : the key `dotted`

As one can see, the dots of a dotted line of Tikz have the shape of a square, and not a circle. That's why the extension `nicematrix` provides in the key `custom-line` a key `dotted` which will draw rounded dots. The initial value of the key `total-width` is, in this case, equal to the diameter of the dots (but the user may change the value with the key `total-width` if needed). Those dotted rules are also used by `nicematrix` to draw continuous dotted rules between cells of the matrix with `\Cdots`, `\Vdots`, etc. (cf. p. 23).

In fact, `nicematrix` defines by default the commands `\hdottedline` and `\cdottedline` and the letter “:” for those dotted rules.¹⁸

```
\NiceMatrixOptions % present in nicematrix.sty
{
  custom-line =
  {
    letter = : ,
    command = hdottedline ,
    ccommand = cdottedline ,
    dotted
  }
}
```

Thus, it's possible to use the commands `\hdottedline` and `\cdottedline` to draw horizontal dotted rules.

```
\begin{pNiceMatrix}
1 & 2 & 3 & 4 & 5 \\
\hdottedline
6 & 7 & 8 & 9 & 10 \\
\cdottedline{1,4-5}
11 & 12 & 13 & 14 & 15
\end{pNiceMatrix}
```

$$\begin{pmatrix} 1 & 2 & 3 & 4 & 5 \\ \hdottedline 6 & 7 & 8 & 9 & 10 \\ \cdottedline{1,4-5} 11 & 12 & 13 & 14 & 15 \end{pmatrix}$$

In the environments with an explicit preamble (like `{NiceTabular}`, `{NiceArray}`, etc.), it's possible to draw a vertical dotted line with the specifier “:”.

```
\left(\begin{NiceArray}{cccc:c}
1 & 2 & 3 & 4 & 5 \\
6 & 7 & 8 & 9 & 10 \\
11 & 12 & 13 & 14 & 15
\end{NiceArray}\right)
```

$$\left(\begin{array}{cccc:c} 1 & 2 & 3 & 4 & 5 \\ 6 & 7 & 8 & 9 & 10 \\ 11 & 12 & 13 & 14 & 15 \end{array}\right)$$

6 The color of the rows and columns

6.1 Use of `colortbl`

We recall that the package `colortbl` can be loaded directly with `\usepackage{colortbl}` or by loading `xcolor` with the key `table`: `\usepackage[table]{xcolor}`.

Since the package `nicematrix` is based on `array`, it's possible to use `colortbl` with `nicematrix`.

However, there is two drawbacks:

- The package `colortbl` patches `array`, leading to some incompatibilities (for instance with the command `\hdotsfor`).

¹⁸However, it's possible to overwrite those definitions with a `custom-line` (in order, for example, to switch to dashed lines).

- The package `colortbl` constructs the array row by row, alternating colored rectangles, rules and contents of the cells. The resulting PDF is difficult to interpret by some PDF viewers and may lead to artefacts on the screen.
 - Some rules seem to disappear. This is because many PDF viewers give priority to graphical element drawn posteriorly (which is in the spirit of the “painting model” of PostScript and PDF). Concerning this problem, MuPDF (which is used, for instance, by SumatraPDF) gives better results than Adobe Reader).
 - A thin white line may appear between two cells of the same color. This phenomenon occurs when each cell is colored with its own instruction `fill` (the PostScript operator `fill` noted `f` in PDF). This is the case with `colortbl`: each cell is colored on its own, even when `\columncolor` or `\rowcolor` is used.
- As for this phenomenon, Adobe Reader gives better results than MuPDF.

The package `nicematrix` provides tools to avoid those problems.

6.2 The tools of `nicematrix` in the `\CodeBefore`

The package `nicematrix` provides some tools (independent of `colortbl`) to draw the colored panels first, and, then, the content of the cells and the rules. This strategy is more conform to the “painting model” of the formats PostScript and PDF and is more suitable for the PDF viewers. However, it requires several compilations.¹⁹

The extension `nicematrix` provides a key `code-before` for some code that will be executed before the drawing of the tabular.

An alternative syntax is provided: it’s possible to put the content of that `code-before` between the keywords `\CodeBefore` and `\Body` at the beginning of the environment.

```
\begin{pNiceArray}{preamble}
\CodeBefore
  instructions of the code-before
\Body
  contents of the environment
\end{pNiceArray}
```

New commands are available in that `\CodeBefore`: `\cellcolor`, `\rectanglecolor`, `\rowcolor`, `\columncolor`, `\rowcolors`, `\rowlistcolors`, `\chessboardcolors` and `\arraycolor`.²⁰

All these commands accept an optional argument (between square brackets and in first position) which is the color model for the specification of the colors.

These commands don’t color the cells which are in the “corners” if the key `corners` is used. This key has been described p. 10.

- The command `\cellcolor` takes its name from the command `\cellcolor` of `colortbl`.
This command takes in as mandatory arguments a color and a list of cells, each of which with the format i - j where i is the number of the row and j the number of the column of the cell. In fact, despite its name, this command may be used to color a whole row (with the syntax i -) or a whole column (with the syntax $-j$).

```
\begin{NiceTabular}{ccc}[hvlines]
\CodeBefore
  \cellcolor[HTML]{FFFF88}{3-1,2-2,-3}
\Body
a & b & c \\
e & f & g \\
h & i & j \\
\end{NiceTabular}
```

a	b	c
e	f	g
h	i	j

¹⁹If you use Overleaf, Overleaf will do automatically the right number of compilations.

²⁰Remark that, in the `\CodeBefore`, PGF/Tikz nodes of the form “(i-lj)” are also available to indicate the position to the potential rules: cf. p. 44.

- The command `\rectanglecolor` takes three mandatory arguments. The first is the color. The second is the upper-left cell of the rectangle and the third is the lower-right cell of the rectangle.

```
\begin{NiceTabular}{ccc}[hvlines]
\CodeBefore
  \rectanglecolor{blue!15}{2-2}{3-3}
\Body
a & b & c \\
e & f & g \\
h & i & j \\
\end{NiceTabular}
```

a	b	c
e	f	g
h	i	j

- The command `\arraycolor` takes in as mandatory argument a color and color the whole tabular with that color (excepted the potential exterior rows and columns: cf. p. 22). It's only a particular case of `\rectanglecolor`.
- The command `\chessboardcolors` takes in as mandatory arguments two colors and it colors the cells of the tabular in quincunx with these colors.

```
$$\begin{pNiceMatrix}[r,margin]
\CodeBefore
  \chessboardcolors{red!15}{blue!15}
\Body
1 & -1 & 1 \\
-1 & 1 & -1 \\
1 & -1 & 1 \\
\end{pNiceMatrix}$$
```

$$\begin{pmatrix} 1 & -1 & 1 \\ -1 & 1 & -1 \\ 1 & -1 & 1 \end{pmatrix}$$

We have used the key `r` which aligns all the columns rightwards (cf. p. 38).

- The command `\rowcolor` takes its name from the command `\rowcolor` of `colortbl`. Its first mandatory argument is the color and the second is a comma-separated list of rows or interval of rows with the form *a-b* (an interval of the form *a-* represent all the rows from the row *a* until the end).

```
$$\begin{NiceArray}{l1l1}[hvlines]
\CodeBefore
  \rowcolor{red!15}{1,3-5,8-}
\Body
a_1 & b_1 & c_1 \\
a_2 & b_2 & c_2 \\
a_3 & b_3 & c_3 \\
a_4 & b_4 & c_4 \\
a_5 & b_5 & c_5 \\
a_6 & b_6 & c_6 \\
a_7 & b_7 & c_7 \\
a_8 & b_8 & c_8 \\
a_9 & b_9 & c_9 \\
a_{10} & b_{10} & c_{10} \\
\end{NiceArray}$$
```

a_1	b_1	c_1
a_2	b_2	c_2
a_3	b_3	c_3
a_4	b_4	c_4
a_5	b_5	c_5
a_6	b_6	c_6
a_7	b_7	c_7
a_8	b_8	c_8
a_9	b_9	c_9
a_{10}	b_{10}	c_{10}

- The command `\columncolor` takes its name from the command `\columncolor` of `colortbl`. Its syntax is similar to the syntax of `\rowcolor`.
- The command `\rowcolors` (with a *s*) takes its name from the command `\rowcolors` of `colortbl`. The *s* emphasizes the fact that there is *two* colors. This command colors alternately the rows

of the tabular with the row colors (provided in second and third argument), beginning with the row whose number is given in first (mandatory) argument.

In fact, the first (mandatory) argument is, more generally, a comma separated list of intervals describing the rows involved in the action of `\rowcolors` (an interval of the form $i-j$ describes in fact the interval of all the rows of the tabular, beginning with the row i).

The last argument of `\rowcolors` is an optional list of pairs $key=value$ (the optional argument in the first position corresponds to the colorimetric space). The available keys are `cols`, `restart` and `respect-blocks`.

- The key `cols` describes a set of columns. The command `\rowcolors` will color only the cells of these columns. The value is a comma-separated list of intervals of the form $i-j$ (where i or j may be replaced by $*$).
- With the key `restart`, each interval of rows (specified by the first mandatory argument) begins with the same color.²¹
- With the key `respect-blocks` the “rows” alternately colored may extend over several rows if they have to incorporate blocks (created with the command `\Block`: cf. p. 4).

```
\begin{NiceTabular}{clr}[hvlines]
\CodeBefore
  \rowcolors[gray]{2}{0.8}{}[cols=2-3,restart]
\Body
\Block{1-*}{Results} \
John & 12 \
Stephen & 8 \
Sarah & 18 \
Ashley & 20 \
Henry & 14 \
Madison & 15
\end{NiceTabular}
```

Results		
A	John	12
	Stephen	8
B	Sarah	18
	Ashley	20
	Henry	14
	Madison	15

```
\begin{NiceTabular}{lr}[hvlines]
\CodeBefore
  \rowcolors{1}{blue!10}{}[respect-blocks]
\Body
\Block{2-1}{John} & 12 \
& 13 \
Steph & 8 \
\Block{3-1}{Sarah} & 18 \
& 17 \
& 15 \
Ashley & 20 \
Henry & 14 \
\Block{2-1}{Madison} & 15 \
& 19
\end{NiceTabular}
```

John	12
	13
Steph	8
Sarah	18
	17
	15
Ashley	20
Henry	14
Madison	15
	19

- The extension `nicematrix` provides also a command `\rowlistcolors`. This command generalises the command `\rowcolors`: instead of two successive arguments for the colors, this command takes in an argument which is a (comma-separated) list of colors. In that list, the symbol `=` represent a color identical to the previous one.

²¹Otherwise, the color of a given row relies only upon the parity of its absolute number.


```

\begin{NiceTabular}{c}
\CodeBefore
  \rowlistcolors{1}{red!15,blue!15,green!15}
\Body
Peter \\
James \\
Abigail \\
Elisabeth \\
Claudius \\
Jane \\
Alexandra \\
\end{NiceTabular}

```

Peter
James
Abigail
Elisabeth
Claudius
Jane
Alexandra

It's also possible to use in the command `\rowlistcolors` a color series defined by the command `\definecolorseries` of `xcolor` (and initialized with the command `\resetcolorseries`²²).

```

\begin{NiceTabular}{c}
\CodeBefore
  \definecolorseries{BlueWhite}{rgb}{last}{blue}{white}
  \resetcolorseries{\value{iRow}}{BlueWhite}
  \rowlistcolors{1}{BlueWhite!+}
\Body
Peter \\
James \\
Abigail \\
Elisabeth \\
Claudius \\
Jane \\
Alexandra \\
\end{NiceTabular}

```

Peter
James
Abigail
Elisabeth
Claudius
Jane
Alexandra

We recall that all the color commands we have described don't color the cells which are in the "corners". In the following example, we use the key `corners=NE` to require the determination of the corner *north east* (NE).

```

\begin{NiceTabular}{cccccc}[corners=NE,margin,hvlines,first-row,first-col]
\CodeBefore
  \rowlistcolors{1}{blue!15, }
\Body
  & 0 & 1 & 2 & 3 & 4 & 5 & 6 \\
0 & 1 & \\
1 & 1 & 1 & \\
2 & 1 & 2 & 1 & \\
3 & 1 & 3 & 3 & 1 & \\
4 & 1 & 4 & 6 & 4 & 1 & \\
5 & 1 & 5 & 10 & 10 & 5 & 1 & \\
6 & 1 & 6 & 15 & 20 & 15 & 6 & 1 \\
\end{NiceTabular}

```

	0	1	2	3	4	5	6
0	1						
1	1	1					
2	1	2	1				
3	1	3	3	1			
4	1	4	6	4	1		
5	1	5	10	10	5	1	
6	1	6	15	20	15	6	1

One should remark that all the previous commands are compatible with the commands of `booktabs` (`\toprule`, `\midrule`, `\bottomrule`, etc). However, `booktabs` is *not* loaded by `nicematrix`.

²²For the initialization, in the following example, you have used the counter `iRow` which, when used in the `\CodeBefore` (and in the `\CodeAfter`) corresponds to the number of rows of the array: cf. p 39. That leads to an ajustement of the gradation of the colors to the size of the tabular.

```

\begin{NiceTabular}[c]{lSSSS}
\CodeBefore
  \rowcolor{red!15}{1-2}
  \rowcolors{3}{blue!15}{}
\Body
\toprule
\Block{2-1}{Product} &
\Block{1-3}{dimensions (cm)} & & &
\Block{2-1}{\rotate{Price}} \\
\cmidrule{rl}{2-4}
& L & l & h & \\
\midrule
small & 3 & 5.5 & 1 & 30 \\
standard & 5.5 & 8 & 1.5 & 50.5 \\
premium & 8.5 & 10.5 & 2 & 80 \\
extra & 8.5 & 10 & 1.5 & 85.5 \\
special & 12 & 12 & 0.5 & 70 \\
\bottomrule
\end{NiceTabular}

```

Product	dimensions (cm)			Price
	L	l	h	
small	3	5.5	1	30
standard	5.5	8	1.5	50.5
premium	8.5	10.5	2	80
extra	8.5	10	1.5	85.5
special	12	12	0.5	70

We have used the type of column S of siunitx.

6.3 Color tools with the syntax of colortbl

It's possible to access the preceding tools with a syntax close to the syntax of `colortbl`. For that, one must use the key `colortbl-like` in the current environment.²³

There are three commands available (they are inspired by `colortbl` but are *independent* of `colortbl`):

- `\cellcolor` which colorizes a cell;²⁴
- `\rowcolor` which must be used in a cell and which colorizes the end of the row;
- `\columncolor` which must be used in the preamble of the environment with the same syntax as the corresponding command of `colortbl` (however, unlike the command `\columncolor` of `colortbl`, this command `\columncolor` can appear within another command, itself used in the preamble of the array).

```

\NewDocumentCommand { \Blue } { } { } { \columncolor{blue!15} }
\begin{NiceTabular}[colortbl-like]{>{\Blue}c>{\Blue}cc}
\toprule
\rowcolor{red!15}
Last name & First name & Birth day \\
\midrule
Achard & Jacques & 5 juin 1962 \\
Lefebvre & Mathilde & 23 mai 1988 \\
Vanesse & Stephany & 30 octobre 1994 \\
Dupont & Chantal & 15 janvier 1998 \\
\bottomrule
\end{NiceTabular}

```

Last name	First name	Birth day
Achard	Jacques	5 juin 1962
Lefebvre	Mathilde	23 mai 1988
Vanesse	Stephany	30 octobre 1994
Dupont	Chantal	15 janvier 1998

²³Up to now, this key is *not* available in `\NiceMatrixOptions`.

²⁴However, this command `\cellcolor` will delete the following spaces, which does not the command `\cellcolor` of `colortbl`.

7 The command `\RowStyle`

The command `\RowStyle` takes in as argument some formatting instructions that will be applied to each cell on the rest of the current row.

That command also takes in as optional argument (between square brackets) a list of *key=value* pairs.

- The key `nb-rows` sets the number of rows to which the specifications of the current command will apply (with the special value `*`, it will apply to all the following rows).
- The keys `cell-space-top-limit`, `cell-space-bottom-limit` and `cell-space-limits` are available with the same meaning that the corresponding global keys (cf. p. 2).
- The key `rowcolor` sets the color of the background and the key `color` sets the color of the text.²⁵
- The key `bold` enforces bold characters for the cells of the row, both in math and text mode.

```
\begin{NiceTabular}{cccc}
\hline
\RowStyle[cell-space-limits=3pt]{\rotate}
first & second & third & fourth \\
\RowStyle[nb-rows=2,rowcolor=blue!50,color=white]{\sffamily}
1 & 2 & 3 & 4 \\
I & II & III & IV
\end{NiceTabular}
```

first	second	third	fourth
1	2	3	4
I	II	III	IV

The command `\rotate` is described p. 38.

8 The width of the columns

8.1 Basic tools

In the environments with an explicit preamble (like `{NiceTabular}`, `{NiceArray}`, etc.), it's possible to fix the width of a given column with the standard letters `w`, `W`, `p`, `b` and `m` of the package `array`.

```
\begin{NiceTabular}{Wc{2cm}cc}[hvlines]
Paris & New York & Madrid \\
Berlin & London & Roma \\
Rio & Tokyo & Oslo
\end{NiceTabular}
```

Paris	New York	Madrid
Berlin	London	Roma
Rio	Tokyo	Oslo

In the environments of `nicematrix`, it's also possible to fix the *minimal* width of all the columns (excepted the potential exterior columns: cf. p. 22) directly with the key `columns-width`.

```
$\begin{pNiceMatrix}[columns-width = 1cm]
1 & 12 & -123 \\
12 & 0 & 0 \\
4 & 1 & 2
\end{pNiceMatrix}$
```

$$\begin{pmatrix} 1 & 12 & -123 \\ 12 & 0 & 0 \\ 4 & 1 & 2 \end{pmatrix}$$

Note that the space inserted between two columns (equal to `2 \tabcolsep` in `{NiceTabular}` and to `2 \arraycolsep` in the other environments) is not suppressed (of course, it's possible to suppress this space by setting `\tabcolsep` or `\arraycolsep` equal to 0 pt before the environment).

²⁵The key `color` uses the command `\color` but inserts also an instruction `\leavevmode` before. This instruction prevents a extra vertical space in the cells which belong to columns of type `p`, `b`, `m` and `X` (which start in vertical mode).

It's possible to give the special value `auto` to the option `columns-width`: all the columns of the array will have a width equal to the widest cell of the array.²⁶

```
\begin{pNiceMatrix}[columns-width = auto]
1 & 12 & -123 \\
12 & 0 & 0 \\
4 & 1 & 2
\end{pNiceMatrix}
```

$$\begin{pmatrix} 1 & 12 & -123 \\ 12 & 0 & 0 \\ 4 & 1 & 2 \end{pmatrix}$$

Without surprise, it's possible to fix the minimal width of the columns of all the arrays of a current scope with the command `\NiceMatrixOptions`.

```
\NiceMatrixOptions{columns-width=10mm}
\begin{pNiceMatrix}
a & b \\ c & d
\end{pNiceMatrix}
=
\begin{pNiceMatrix}
1 & 1245 \\ 345 & 2
\end{pNiceMatrix}
```

$$\begin{pmatrix} a & b \\ c & d \end{pmatrix} = \begin{pmatrix} 1 & 1245 \\ 345 & 2 \end{pmatrix}$$

But it's also possible to fix a zone where all the matrices will have their columns of the same width, equal to the widest cell of all the matrices. This construction uses the environment `{NiceMatrixBlock}` with the option `auto-columns-width`²⁷. The environment `{NiceMatrixBlock}` has no direct link with the command `\Block` presented previously in this document (cf. p. 4).

```
\begin{NiceMatrixBlock}[auto-columns-width]
\begin{array}{c}
\begin{bNiceMatrix}
9 & 17 \\ -2 & 5
\end{bNiceMatrix} \\
\begin{bNiceMatrix}
1 & 1245345 \\ 345 & 2
\end{bNiceMatrix}
\end{array}
\end{NiceMatrixBlock}
```

$$\begin{bmatrix} 9 & 17 \\ -2 & 5 \end{bmatrix}$$

$$\begin{bmatrix} 1 & 1245345 \\ 345 & 2 \end{bmatrix}$$

8.2 The columns V of varwidth

Let's recall first the behaviour of the environment `{varwidth}` of the eponymous package `varwidth`. That environment is similar to the classical environment `{minipage}` but the width provided in the argument is only the *maximal* width of the created box. In the general case, the width of the box constructed by an environment `{varwidth}` is the natural width of its contents.

That point is illustrated on the following examples.

```
\fbox{%
\begin{varwidth}{8cm}
\begin{itemize}
\item first item
\item second item
\end{itemize}
\end{varwidth}}
```

- first item
- second item

²⁶The result is achieved with only one compilation (but PGF/Tikz will have written informations in the `aux` file and a message requiring a second compilation will appear).

²⁷At this time, this is the only usage of the environment `{NiceMatrixBlock}` but it may have other usages in the future.

```

\fbbox{%
\begin{minipage}{8cm}
\begin{itemize}
\item first item
\item second item
\end{itemize}
\end{minipage}}

```

- first item
- second item

The package `varwidth` provides also the column type `V`. A column of type `V{<dim>}` encapsulates all its cells in a `{varwidth}` with the argument `<dim>` (and does also some tuning).

When the package `varwidth` is loaded, the columns `V` of `varwidth` are supported by `nicematrix`.

```

\begin{NiceTabular}[corners=NW,hvlines]{V{3cm}V{3cm}V{3cm}}
& some text & some very very very long text \\
some very very very long text & \\
some very very very long text & \\
\end{NiceTabular}

```

	some text	some very very very long text
some very very very long text		
some very very very long text		

Concerning `nicematrix`, one of the interests of this type of columns is that, for a cell of a column of type `V`, the PGF/Tikz node created by `nicematrix` for the content of that cell has a width adjusted to the content of the cell : cf. p. 42.

One should remark that the extension `varwidth` (at least in its version 0.92) has some problems: for instance, with LuaLaTeX, it does not work when the content begins with `\color`.

8.3 The columns X

The environment `{NiceTabular}` provides `X` columns similar to those provided by the environment `{tabularx}` of the eponymous package.

The required width of the tabular may be specified with the key `width` (in `{NiceTabular}` or in `\NiceMatrixOptions`). The initial value of this parameter is `\linewidth` (and not `\textwidth`).

For sake of similarity with the environment `{tabularx}`, `nicematrix` also provides an environment `{NiceTabularX}` with a syntax similar to the syntax of `{tabularx}`, that is to say with a first mandatory argument which is the width of the tabular.²⁸

As with the packages `tabu`²⁹ and `tabularray`, the specifier `X` takes in an optional argument (between square brackets) which is a list of keys.

- It's possible to give a weight for the column by providing a positive integer directly as argument of the specifier `X`. For example, a column `X[2]` will have a width double of the width of a column `X` (which has a weight equal to 1).³⁰
- It's possible to specify an horizontal alignment with one of the letters `l`, `c` and `r` (which insert respectively `\raggedright`, `\centering` and `\raggedleft` followed by `\arraybackslash`).

²⁸If `tabularx` is loaded, one must use `{NiceTabularX}` (and not `{NiceTabular}`) in order to use the columns `X` (this point comes from a conflict in the definitions of the specifier `X`).

²⁹The extension `tabu` is now considered as deprecated.

³⁰The negative values of the weight, as provided by `tabu` (which is now obsolete), are *not* supported by `nicematrix`. If such a value is used, an error will be raised.

- It's possible to specify a vertical alignment with one of the keys `t` (alias `p`), `m` and `b` (which construct respectively columns of type `p`, `m` and `b`). The default value is `t`.

```
\begin{NiceTabular}[width=9cm]{X[2,1]X[1]}[hvlines]
a rather long text which fits on several lines
& a rather long text which fits on several lines \\
a shorter text & a shorter text
\end{NiceTabular}
```

a rather long text which fits on several lines	a rather long text which fits on several lines
a shorter text	a shorter text

9 The exterior rows and columns

The options `first-row`, `last-row`, `first-col` and `last-col` allow the composition of exterior rows and columns in the environments of `nicematrix`. It's particularly interesting for the (mathematical) matrices.

A potential “first row” (exterior) has the number 0 (and not 1). Idem for the potential “first column”.

```
$\begin{pNiceMatrix}[first-row,last-row,first-col,last-col,nullify-dots]
& C_1 & & \Cdots & & & C_4 & & \\
L_1 & & a_{11} & & a_{12} & & a_{13} & & a_{14} & & L_1 \\
\Vdots & & a_{21} & & a_{22} & & a_{23} & & a_{24} & & \Vdots \\
& & a_{31} & & a_{32} & & a_{33} & & a_{34} & & \\
L_4 & & a_{41} & & a_{42} & & a_{43} & & a_{44} & & L_4 \\
& & C_1 & & \Cdots & & & & C_4 & & \\
\end{pNiceMatrix}$
```

$$\begin{array}{c}
C_1 \dots\dots\dots C_4 \\
L_1 \left(\begin{array}{cccc} a_{11} & a_{12} & a_{13} & a_{14} \\ a_{21} & a_{22} & a_{23} & a_{24} \\ a_{31} & a_{32} & a_{33} & a_{34} \\ a_{41} & a_{42} & a_{43} & a_{44} \end{array} \right) L_1 \\
\vdots \\
\vdots \\
L_4 \left(\begin{array}{cccc} a_{41} & a_{42} & a_{43} & a_{44} \end{array} \right) L_4 \\
C_1 \dots\dots\dots C_4
\end{array}$$

The dotted lines have been drawn with the tools presented p. 23.

We have several remarks to do.

- For the environments with an explicit preamble (i.e. `{NiceTabular}`, `{NiceArray}` and its variants), no letter must be given in that preamble for the potential first column and the potential last column: they will automatically (and necessarily) be of type `r` for the first column and `l` for the last one.³¹
- One may wonder how `nicematrix` determines the number of rows and columns which are needed for the composition of the “last row” and “last column”.
 - For the environments with explicit preamble, like `{NiceTabular}` and `{pNiceArray}`, the number of columns can obviously be computed from the preamble.

³¹The users wishing exterior columns with another type of alignment should consider the command `\SubMatrix` available in the `\CodeAfter` (cf. p. 30).

- When the option `light-syntax` (cf. p. 40) is used, `nicematrix` has, in any case, to load the whole body of the environment (and that’s why it’s not possible to put verbatim material in the array with the option `light-syntax`). The analysis of this whole body gives the number of rows and the number of columns.
- In the other cases, `nicematrix` compute the number of rows and columns during the first compilation and write the result in the `aux` file for the next run.

However, it’s possible to provide the number of the last row and the number of the last column as values of the options `last-row` and `last-col`, tending to an acceleration of the whole compilation of the document. That’s what we will do throughout the rest of the document.

It’s possible to control the appearance of these rows and columns with options `code-for-first-row`, `code-for-last-row`, `code-for-first-col` and `code-for-last-col`. These options specify tokens that will be inserted before each cell of the corresponding row or column.

```
\NiceMatrixOptions{code-for-first-row = \color{red},
                  code-for-first-col = \color{blue},
                  code-for-last-row = \color{green},
                  code-for-last-col = \color{magenta}}
$\begin{pNiceArray}{cc|cc}[first-row,last-row=5,first-col,last-col,nullify-dots]
    & C_1 & & \Cdots & & C_4 & & \\
L_1 & a_{11} & a_{12} & a_{13} & a_{14} & L_1 & & \\
\vdots & a_{21} & a_{22} & a_{23} & a_{24} & \vdots & & \\
\hline
& a_{31} & a_{32} & a_{33} & a_{34} & & & \\
L_4 & a_{41} & a_{42} & a_{43} & a_{44} & L_4 & & \\
& C_1 & & \Cdots & & C_4 & & \\
\end{pNiceArray}$
```

$$\begin{array}{c}
 \textcolor{red}{C_1} \dots \dots \dots \textcolor{red}{C_4} \\
 \textcolor{blue}{L_1} \left(\begin{array}{cc|cc} a_{11} & a_{12} & a_{13} & a_{14} \\ a_{21} & a_{22} & a_{23} & a_{24} \\ a_{31} & a_{32} & a_{33} & a_{34} \\ a_{41} & a_{42} & a_{43} & a_{44} \end{array} \right) \textcolor{magenta}{L_1} \\
 \vdots \quad \quad \quad \vdots \\
 \textcolor{blue}{L_4} \quad \quad \quad \textcolor{magenta}{L_4} \\
 \textcolor{green}{C_1} \dots \dots \dots \textcolor{green}{C_4}
 \end{array}$$

Remarks

- As shown in the previous example, the horizontal and vertical rules don’t extend in the exterior rows and columns. This remark also applies to the customized rules created by the key `custom-line` (cf. p. 11).
- A specification of color present in `code-for-first-row` also applies to a dotted line drawn in that exterior “first row” (excepted if a value has been given to `xdots/color`). Idem for the other exterior rows and columns.
- Logically, the potential option `columns-width` (described p. 19) doesn’t apply to the “first column” and “last column”.
- For technical reasons, it’s not possible to use the option of the command `\` after the “first row” or before the “last row”. The placement of the delimiters would be wrong. If you are looking for a workaround, consider the command `\SubMatrix` in the `\CodeAfter` described p. 30.

10 The continuous dotted lines

Inside the environments of the package `nicematrix`, new commands are defined: `\Ldots`, `\Cdots`, `\Vdots`, `\Ddots`, and `\Iddots`. These commands are intended to be used in place of `\dots`, `\cdots`,

`\vdots`, `\ddots` and `\iddots`.³²

Each of them must be used alone in the cell of the array and it draws a dotted line between the first non-empty cells³³ on both sides of the current cell. Of course, for `\Ldots` and `\Cdots`, it's an horizontal line; for `\Vdots`, it's a vertical line and for `\Ddots` and `\Iddots` diagonal ones. It's possible to change the color of these lines with the option `color`.³⁴

```
\begin{bNiceMatrix}
a_1      & \Cdots &      & & a_1      & \\
\Vdots   & a_2    & \Cdots & & a_2      & \\
        & \Vdots & \Ddots[color=red] & & & \\
\\
a_1      & a_2    &      & & a_n      & \\
\end{bNiceMatrix}
```

$$\begin{bmatrix} a_1 & \cdots & \cdots & \cdots & a_1 \\ \vdots & & & & \vdots \\ & a_2 & \cdots & \cdots & a_2 \\ \vdots & \vdots & & & \vdots \\ a_1 & a_2 & & & a_n \end{bmatrix}$$

In order to represent the null matrix, one can use the following code:

```
\begin{bNiceMatrix}
0      & \Cdots & 0      & \\
\Vdots &      & \Vdots & \\
0      & \Cdots & 0      & \\
\end{bNiceMatrix}
```

$$\begin{bmatrix} 0 & \cdots & \cdots & 0 \\ \vdots & & & \vdots \\ 0 & \cdots & \cdots & 0 \end{bmatrix}$$

However, one may want a larger matrix. Usually, in such a case, the users of LaTeX add a new row and a new column. It's possible to use the same method with `nicematrix`:

```
\begin{bNiceMatrix}
0      & \Cdots & \Cdots & 0      & \\
\Vdots &      &      & \Vdots & \\
\Vdots &      &      & \Vdots & \\
0      & \Cdots & \Cdots & 0      & \\
\end{bNiceMatrix}
```

$$\begin{bmatrix} 0 & \cdots & \cdots & \cdots & 0 \\ \vdots & & & & \vdots \\ \vdots & & & & \vdots \\ 0 & \cdots & \cdots & \cdots & 0 \end{bmatrix}$$

In the first column of this exemple, there are two instructions `\Vdots` but, of course, only one dotted line is drawn.

In fact, in this example, it would be possible to draw the same matrix more easily with the following code:

```
\begin{bNiceMatrix}
0      & \Cdots &      & & 0      & \\
\Vdots &      &      & &      & \\
        &      &      & & \Vdots & \\
0      &      &      & & \Cdots & 0 \\
\end{bNiceMatrix}
```

$$\begin{bmatrix} 0 & \cdots & \cdots & \cdots & 0 \\ \vdots & & & & \vdots \\ & & & & \vdots \\ 0 & \cdots & \cdots & \cdots & 0 \end{bmatrix}$$

There are also other means to change the size of the matrix. Someone might want to use the optional argument of the command `\` for the vertical dimension and a command `\hspace*` in a cell for the horizontal dimension.³⁵

³²The command `\iddots`, defined in `nicematrix`, is a variant of `\ddots` with dots going forward. If `mathdots` is loaded, the version of `mathdots` is used. It corresponds to the command `\adots` of `unicode-math`.

³³The precise definition of a “non-empty cell” is given below (cf. p. 47).

³⁴It's also possible to change the color of all these dotted lines with the option `xdots/color` (`xdots` to remind that it works for `\Cdots`, `\Ldots`, `\Vdots`, etc.): cf. p. 27.

³⁵In `nicematrix`, one should use `\hspace*` and not `\hspace` for such an usage because `nicematrix` loads `array`. One may also remark that it's possible to fix the width of a column by using the environment `{NiceArray}` (or one of its variants) with a column of type `w` or `W`: see p. 19

However, a command `\hspace*` might interfere with the construction of the dotted lines. That's why the package `nicematrix` provides a command `\Hspace` which is a variant of `\hspace` transparent for the dotted lines of `nicematrix`.

```
\begin{bNiceMatrix}
0 & & \Cdots & & \Hspace*{1cm} & 0 & \\
\Vdots & & & & & & \Vdots \\
0 & & \Cdots & & & 0 & \\
\end{bNiceMatrix}
```

$$\begin{bmatrix} 0 & \cdots & \cdots & 0 \\ \vdots & & & \vdots \\ \vdots & & & \vdots \\ \vdots & & & \vdots \\ 0 & \cdots & \cdots & 0 \end{bmatrix}$$

10.1 The option `nullify-dots`

Consider the following matrix composed classically with the environment `{pmatrix}` of `amsmath`.

```
$A = \begin{pmatrix}
h & i & j & k & l & m \\
x & & & & & x
\end{pmatrix}
\end{pmatrix}$
```

$$A = \begin{pmatrix} h & i & j & k & l & m \\ x & & & & & x \end{pmatrix}$$

If we add `\ldots` instructions in the second row, the geometry of the matrix is modified.

```
$B = \begin{pmatrix}
h & i & j & k & l & m \\
x & \ldots & \ldots & \ldots & \ldots & x
\end{pmatrix}
\end{pmatrix}$
```

$$B = \begin{pmatrix} h & i & j & k & l & m \\ x & \dots & \dots & \dots & \dots & x \end{pmatrix}$$

By default, with `nicematrix`, if we replace `{pmatrix}` by `{pNiceMatrix}` and `\ldots` by `\Ldots`, the geometry of the matrix is not changed.

```
$C = \begin{pNiceMatrix}
h & i & j & k & l & m \\
x & \Ldots & \Ldots & \Ldots & \Ldots & x
\end{pNiceMatrix}$
```

$$C = \begin{pmatrix} h & i & j & k & l & m \\ x & \dots & \dots & \dots & \dots & x \end{pmatrix}$$

However, one may prefer the geometry of the first matrix A and would like to have such a geometry with a dotted line in the second row. It's possible by using the option `nullify-dots` (and only one instruction `\Ldots` is necessary).

```
$D = \begin{pNiceMatrix}[nullify-dots]
h & i & j & k & l & m \\
x & \Ldots & & & & x
\end{pNiceMatrix}$
```

$$D = \begin{pmatrix} h & i & j & k & l & m \\ x & \dots & & & & x \end{pmatrix}$$

The option `nullify-dots` smashes the instructions `\Ldots` (and the variants) horizontally but also vertically.

10.2 The commands `\Hdotsfor` and `\Vdotsfor`

Some people commonly use the command `\hdotsfor` of `amsmath` in order to draw horizontal dotted lines in a matrix. In the environments of `nicematrix`, one should use instead `\Hdotsfor` in order to draw dotted lines similar to the other dotted lines drawn by the package `nicematrix`.

As with the other commands of `nicematrix` (like `\Cdots`, `\Ldots`, `\Vdots`, etc.), the dotted line drawn with `\Hdotsfor` extends until the contents of the cells on both sides.

```
$\begin{pNiceMatrix}
1 & 2 & 3 & 4 & 5 \\
1 & \Hdotsfor{3} & & & 5 \\
1 & 2 & 3 & 4 & 5 \\
1 & 2 & 3 & 4 & 5
\end{pNiceMatrix}$
```

$$\begin{pmatrix} 1 & 2 & 3 & 4 & 5 \\ 1 & \dots & \dots & \dots & 5 \\ 1 & 2 & 3 & 4 & 5 \\ 1 & 2 & 3 & 4 & 5 \end{pmatrix}$$

However, if these cells are empty, the dotted line extends only in the cells specified by the argument of `\Hdotsfor` (by design).

```


$$\begin{pmatrix} 1 & 2 & 3 & 4 & 5 \\ & \cdots & \cdots & \cdots & \cdots \\ 1 & 2 & 3 & 4 & 5 \\ 1 & 2 & 3 & 4 & 5 \end{pmatrix}$$


```

Remark: Unlike the command `\hdotsfor` of `amsmath`, the command `\Hdotsfor` may be used even when the package `colortbl`³⁶ is loaded (but you might have problem if you use `\rowcolor` on the same row as `\Hdotsfor`).

The package `nicematrix` also provides a command `\Vdotsfor` similar to `\Hdotsfor` but for the vertical dotted lines. The following example uses both `\Hdotsfor` and `\Vdotsfor`:

```

\begin{bNiceMatrix}
C[a_1,a_1] & \Cdots & C[a_1,a_n]
& \hspace*{20mm} & C[a_1,a_1^{(p)}] & \Cdots & C[a_1,a_n^{(p)}] \\
\Vdots & \Ddots & \Vdots
& \Hdotsfor{1} & \Vdots & \Ddots & \Vdots \\
C[a_n,a_1] & \Cdots & C[a_n,a_n]
& & C[a_n,a_1^{(p)}] & \Cdots & C[a_n,a_n^{(p)}] \\
\rule{0pt}{15mm}\NotEmpty & \Vdotsfor{1} & & \Ddots & & \Vdotsfor{1} \\
C[a_1^{(p)},a_1] & \Cdots & C[a_1^{(p)},a_n]
& & C[a_1^{(p)},a_1^{(p)}] & \Cdots & C[a_1^{(p)},a_n^{(p)}] \\
& & C[a_1^{(p)},a_1^{(p)}] & \Cdots & C[a_1^{(p)},a_n^{(p)}] \\
\Vdots & \Ddots & \Vdots
& \Hdotsfor{1} & \Vdots & \Ddots & \Vdots \\
C[a_n^{(p)},a_1] & \Cdots & C[a_n^{(p)},a_n]
& & C[a_n^{(p)},a_1^{(p)}] & \Cdots & C[a_n^{(p)},a_n^{(p)}] \\
\end{bNiceMatrix}

```

$$\left[\begin{array}{ccc} C[a_1, a_1] \cdots \cdots C[a_1, a_n] & & C[a_1, a_1^{(p)}] \cdots \cdots C[a_1, a_n^{(p)}] \\ \vdots & \ddots & \vdots \\ C[a_n, a_1] \cdots \cdots C[a_n, a_n] & \cdots \cdots & C[a_n, a_1^{(p)}] \cdots \cdots C[a_n, a_n^{(p)}] \\ & \ddots & \vdots \\ C[a_1^{(p)}, a_1] \cdots \cdots C[a_1^{(p)}, a_n] & & C[a_1^{(p)}, a_1^{(p)}] \cdots \cdots C[a_1^{(p)}, a_n^{(p)}] \\ \vdots & \ddots & \vdots \\ C[a_n^{(p)}, a_1] \cdots \cdots C[a_n^{(p)}, a_n] & \cdots \cdots & C[a_n^{(p)}, a_1^{(p)}] \cdots \cdots C[a_n^{(p)}, a_n^{(p)}] \end{array} \right]$$

10.3 How to generate the continuous dotted lines transparently

Imagine you have a document with a great number of mathematical matrices with ellipsis. You may wish to use the dotted lines of `nicematrix` without having to modify the code of each matrix. It's possible with the keys. `renew-dots` and `renew-matrix`.³⁷

- The option `renew-dots`

With this option, the commands `\ldots`, `\cdots`, `\vdots`, `\ddots`, `\iddots`³² and `\hdotsfor` are redefined within the environments provided by `nicematrix` and behave like `\Ldots`, `\Cdots`,

³⁶We recall that when `xcolor` is loaded with the option `table`, the package `colortbl` is loaded.

³⁷The options `renew-dots`, `renew-matrix` can be fixed with the command `\NiceMatrixOptions` like the other options. However, they can also be fixed as options of the command `\usepackage`.

`\Vdots`, `\Ddots`, `\Iddots` and `\Hdotsfor`; the command `\dots` (“automatic dots” of `amsmath`) is also redefined to behave like `\Ldots`.

- The option `renew-matrix`

With this option, the environment `{matrix}` is redefined and behave like `{NiceMatrix}`, and so on for the five variants.

Therefore, with the keys `renew-dots` and `renew-matrix`, a classical code gives directly the output of `nicematrix`.

```
\NiceMatrixOptions{renew-dots,renew-matrix}
\begin{pmatrix}
1 & \cdots & \cdots & 1 & \\
0 & \ddots & & & \vdots \\
\vdots & \ddots & \ddots & \vdots & \\
0 & \cdots & 0 & & 1
\end{pmatrix}
\end{pmatrix}
```

$$\begin{pmatrix} 1 & \cdots & \cdots & 1 & \\ 0 & \ddots & & & \vdots \\ \vdots & \ddots & \ddots & \vdots & \\ 0 & \cdots & 0 & & 1 \end{pmatrix}$$

10.4 The labels of the dotted lines

The commands `\Ldots`, `\Cdots`, `\Vdots`, `\Ddots`, `\Iddots` and `\Hdotsfor` (and the command `\line` in the `\CodeAfter` which is described p. 29) accept two optional arguments specified by the tokens `_` and `^` for labels positionned below and above the line. The arguments are composed in math mode with `\scriptstyle`.

```
$\begin{bNiceMatrix}
1 & \hspace*{1cm} & & 0 \\
& \Ddots^{n \text{ times}} & & \\
0 & & & 1
\end{bNiceMatrix}$
```

$$\begin{bmatrix} 1 & & & 0 \\ & \ddots^{n \text{ times}} & & \\ 0 & & & 1 \end{bmatrix}$$

10.5 Customisation of the dotted lines

The dotted lines drawn by `\Ldots`, `\Cdots`, `\Vdots`, `\Ddots`, `\Iddots`, `\Hdotsfor` and `\Vdotsfor` (and by the command `\line` in the `\CodeAfter` which is described p. 29) may be customized by the following options (specified between square brackets after the command):

- `color`;
- `radius`;
- `shorten-start`, `shorten-end` and `shorten`;
- `inter`;
- `line-style`.

These options may also be fixed with `\NiceMatrixOptions`, as options of `\CodeAfter` or at the level of a given environment but, in those cases, they must be prefixed by `xdots` (`xdots` to remind that it works for `\Cdots`, `\Ldots`, `\Vdots`, etc.), and, thus have for names:

- `xdots/color`;
- `xdots/radius`;
- `xdots/shorten-start`, `xdots/shorten-end` and `xdots/shorten`;
- `xdots/inter`;
- `xdots/line-style`.

For the clarity of the explanations, we will use those names.

The option `xdots/color`

The option `xdots/color` fixes the color of the dotted line. However, one should remark that the dotted lines drawn in the exterior rows and columns have a special treatment: cf. p. 22.

The option `xdots/radius`

The option `radius` fixes the radius of the dots. The initial value is 0.53 pt.

The option `xdots/shorten`

The keys `xdots/shorten-start` and `xdots/shorten-end` fix the margin at the extremities of the line. The key `xdots/shorten` fixes both parameters. The initial value is 0.3 em (it is recommended to use a unit of length dependent of the current font).

New 6.10 The keys `xdots/shorten-start` and `xdots/shorten-end` have been introduced in version 6.10. In the previous versions, there was only `xdots/shorten`.

The option `xdots/inter`

The option `xdots/inter` fixes the length between the dots. The initial value is 0.45 em (it is recommended to use a unit of length dependent of the current font).

The option `xdots/line-style`

It should be pointed that, by default, the lines drawn by Tikz with the parameter `dotted` are composed of square dots (and not rounded ones).³⁸

```
\tikz \draw [dotted] (0,0) -- (5,0) ;
```

In order to provide lines with rounded dots in the style of those provided by `\ldots` (at least with the *Computer Modern* fonts), the package `nicematrix` embeds its own system to draw a dotted line (and this system uses PGF and not Tikz). This style is called `standard` and that's the initial value of the parameter `xdots/line-style`.

However (when Tikz is loaded) it's possible to use for `xdots/line-style` any style provided by Tikz, that is to say any sequence of options provided by Tikz for the Tikz paths (with the exception of “color”, “shorten >” and “shorten <”).

Here is for example a tridiagonal matrix with the style `loosely dotted`:

```
\begin{pNiceMatrix}[nullify-dots,xdots/line-style=loosely dotted]
a      & b      & 0      & & & \Cdots & 0      & \\
b      & a      & b      & & \Ddots & & \Vdots & \\
0      & b      & a      & & \Ddots & & & \\
      & & \Ddots & & \Ddots & & \Ddots & \\
\Vdots & & & & & & 0      & \\
0      & & \Cdots & & & & b      & \\
      & & & & 0      & & b      & a
\end{pNiceMatrix}
```

$$\begin{pmatrix} a & b & 0 & \cdots & 0 \\ b & a & b & \ddots & \\ 0 & b & a & \ddots & \\ \vdots & & \ddots & \ddots & \vdots \\ 0 & \cdots & 0 & b & a \end{pmatrix}$$

³⁸The first reason of this behaviour is that the PDF format includes a description for dashed lines. The lines specified with this descriptor are displayed very efficiently by the PDF readers. It's easy, starting from these dashed lines, to create a line composed by square dots whereas a line of rounded dots needs a specification of each dot in the PDF file. Nevertheless, you can have a look at the following page to see how to have dotted rules with rounded dots in Tikz: <https://tex.stackexchange.com/questions/52848/tikz-line-with-large-dots>

10.6 The dotted lines and the rules

The dotted lines determine virtual blocks which have the same behaviour regarding the rules (the rules specified by the specifier `|` in the preamble, by the command `\Hline`, by the keys `hlines`, `vlines`, `hvlines` and `hvlines-except-borders` and by the tools created by `custom-line` are not drawn within the blocks).³⁹

```
\begin{bNiceMatrix}[margin,hvlines]
\Block{3-3}<\LARGE>\{A\} & & 0 \\
& \hspace*{1cm} & & \Vdots \\
& & 0 \\
0 & \Cdots & 0 & 0
\end{bNiceMatrix}
```

$$\left[\begin{array}{ccc|c} & & & 0 \\ & & & \vdots \\ & & & 0 \\ \hline 0 & \cdots & 0 & 0 \end{array} \right]$$

11 The `\CodeAfter`

The option `code-after` may be used to give some code that will be executed *after* the construction of the matrix.⁴⁰

For the legibility of the code, an alternative syntax is provided: it's possible to give the instructions of the `code-after` at the end of the environment, after the keyword `\CodeAfter`. Although `\CodeAfter` is a keyword, it takes in an optional argument (between square brackets).⁴¹

The experienced users may, for instance, use the PGF/Tikz nodes created by `nicematrix` in the `\CodeAfter`. These nodes are described further beginning on p. 41.

Moreover, several special commands are available in the `\CodeAfter`: `line`, `\SubMatrix`, `\OverBrace` and `\UnderBrace`. We will now present these commands.

11.1 The command `\line` in the `\CodeAfter`

The command `\line` draws directly dotted lines between cells or blocks. It takes in two arguments for the cells or blocks to link. Both argument may be:

- a specification of cell of the form i - j where i is the number of the row and j is the number of the column;
- **New 6.10** the name of a block (created by the command `\Block` with the key `name` of that command).

The options available for the customisation of the dotted lines created by `\Cdots`, `\Vdots`, etc. are also available for this command (cf. p. 27).

This command may be used, for example, to draw a dotted line between two adjacent cells.

```
\NiceMatrixOptions{xdots/shorten = 0.6 em}
\begin{pNiceMatrix}
I & 0 & & \Cdots & 0 & \\
0 & & I & & \Ddots & \Vdots \\
\Vdots & & \Ddots & I & 0 & \\
0 & & \Cdots & 0 & & I
\CodeAfter \line{2-2}{3-3}
\end{pNiceMatrix}
```

$$\begin{pmatrix} I & 0 & \cdots & 0 \\ 0 & I & & \vdots \\ \vdots & & I & 0 \\ 0 & \cdots & 0 & I \end{pmatrix}$$

³⁹On the other side, the command `\line` in the `\CodeAfter` (cf. p. 29) does *not* create block.

⁴⁰There is also a key `code-before` described p. 14.

⁴¹Here are the keys accepted in that argument: `delimiters/color`, `rules` and its sub-keys and `sub-matrix` (linked to the command `\SubMatrix`) and its sub-keys.

It can also be used to draw a diagonal line not parallel to the other diagonal lines (by default, the dotted lines drawn by `\Ddots` are “parallelized”: cf. p. 47).

```
\begin{bNiceMatrix}
1      & \Cdots & & 1      & 2      & \Cdots & & 2      & \\
0      & \Ddots & & \Vdots & \Vdots & \hspace*{2.5cm} & & \Vdots & \\
\Vdots & \Ddots & & & & & & & \\
0      & \Cdots & 0 & 1      & 2      & \Cdots & & 2      & \\
\CodeAfter \line[shorten=6pt]{1-5}{4-7}
\end{bNiceMatrix}
```

$$\left[\begin{array}{cccccc} 1 & \cdots & 1 & 2 & \cdots & 2 \\ 0 & \ddots & & \vdots & \vdots & \hspace*{2.5cm} & \vdots \\ \vdots & \ddots & & & & & \\ 0 & \cdots & 0 & 1 & 2 & \cdots & 2 \end{array} \right]$$

11.2 The command `\SubMatrix` in the `\CodeAfter`

The command `\SubMatrix` provides a way to put delimiters on a portion of the array considered as a submatrix. The command `\SubMatrix` takes in five arguments:

- the first argument is the left delimiter, which may be any extensible delimiter provided by LaTeX : `(`, `[`, `\{`, `\langle`, `\lggroup`, `\lfloor`, etc. but also the null delimiter `.`;
- the second argument is the upper-left corner of the submatrix with the syntax $i-j$ where i the number of row and j the number of column;
- the third argument is the lower-right corner with the same syntax;
- the fourth argument is the right delimiter;
- the last argument, which is optional, is a list of *key=value* pairs.⁴²

One should remark that the command `\SubMatrix` draws the delimiters after the construction of the array: no space is inserted by the command `\SubMatrix` itself. That’s why, in the following example, we have used the key `margin` and you have added by hand some space between the third and fourth column with `@{\hspace{1.5em}}` in the preamble of the array.

```
\[ \begin{NiceArray}{ccc@{\hspace{1.5em}}c}[cell-space-limits=2pt,margin]
1      & 1      & 1      & x \\
\dfrac{1}{4} & \dfrac{1}{2} & \dfrac{1}{4} & y \\
1      & 2      & 3      & z \\
\CodeAfter
  \SubMatrix({1-1}{3-3})
  \SubMatrix({1-4}{3-4})
\end{NiceArray} \]
```

$$\begin{pmatrix} 1 & 1 & 1 \\ \frac{1}{4} & \frac{1}{2} & \frac{1}{4} \\ 1 & 2 & 3 \end{pmatrix} \begin{pmatrix} x \\ y \\ z \end{pmatrix}$$

In fact, the command `\SubMatrix` also takes in two optional arguments specified by the traditional symbols `^` and `_` for material in superscript and subscript.

```
\begin{bNiceMatrix}[right-margin=1em]
1 & 1 & 1 \\
1 & a & b \\
1 & c & d \\
\CodeAfter
  \SubMatrix[{2-2}{3-3}]^T
\end{bNiceMatrix}
```

$$\begin{bmatrix} 1 & 1 & 1 \\ 1 & a & b \\ 1 & c & d \end{bmatrix}^T$$

The options of the command `\SubMatrix` are as follows:

⁴²There is no optional argument between square brackets in first position because a square bracket just after `\SubMatrix` must be interpreted as the first (mandatory) argument of the command `\SubMatrix`: that bracket is the left delimiter of the sub-matrix to construct (eg.: `\SubMatrix[{2-2}{4-7}]`).

- `left-xshift` and `right-xshift` shift horizontally the delimiters (there exists also the key `xshift` which fixes both parameters);
- `extra-height` adds a quantity to the total height of the delimiters (`height \ht + depth \dp`);
- `delimiters/color` fixes the color of the delimiters (also available in `\NiceMatrixOptions`, in the environments with delimiters and as option of the keyword `\CodeAfter`);
- `slim` is a boolean key: when that key is in force, the horizontal position of the delimiters is computed by using only the contents of the cells of the submatrix whereas, in the general case, the position is computed by taking into account the cells of the whole columns implied in the submatrix (see example below). ;
- `vlines` contents a list of numbers of vertical rules that will be drawn in the sub-matrix (if this key is used without value, all the vertical rules of the sub-matrix are drawn);
- `hlines` is similar to `vlines` but for the horizontal rules;
- `hvlines`, which must be used without value, draws all the vertical and horizontal rules.

One should remark that these keys add their rules after the construction of the main matrix: no space is added between the rows and the columns of the array for these rules.

All these keys are also available in `\NiceMatrixOptions`, at the level of the environments of `nicematrix` or as option of the command `\CodeAfter` with the prefix `sub-matrix` which means that their names are therefore `sub-matrix/left-xshift`, `sub-matrix/right-xshift`, `sub-matrix/xshift`, etc.

```

\begin{NiceArray}{cc@{\hspace{5mm}}l}[cell-space-limits=2pt]
  & & \frac{1}{2} \\
  & & \frac{1}{4} \\
a & b & \frac{1}{2}a + \frac{1}{4}b \\
c & d & \frac{1}{2}c + \frac{1}{4}d \\
\CodeAfter
  \SubMatrix{1-3}{2-3}
  \SubMatrix{3-1}{4-2}
  \SubMatrix{3-3}{4-3}
\end{NiceArray}$

```

Here is the same example with the key `slim` used for one of the submatrices.

$$\begin{array}{cc} & \frac{1}{2} \\ a & b \\ c & d \end{array} \begin{pmatrix} \frac{1}{2}a + \frac{1}{4}b \\ \frac{1}{2}c + \frac{1}{4}d \end{pmatrix}$$

There is also a key `name` which gives a name to the submatrix created by `\SubMatrix`. That name is used to create PGF/Tikz nodes: cf p. 45.

It's also possible to specify some delimiters⁴³ by placing them in the preamble of the environment (for the environments with a preamble: `{NiceArray}`, `{pNiceArray}`, etc.). This syntax is inspired by the extension `blkarray`.

When there are two successive delimiters (necessarily a closing one following by an opening one for another submatrix), a space equal to `\enskip` is automatically inserted.

⁴³Those delimiters are `(`, `[`, `\{` and the closing ones. Of course, it's also possible to put `|` and `||` in the preamble of the environment.

```

 $\begin{pNiceArray}{(c)(c)(c)}
a_{11} & a_{12} & & a_{13} \\
a_{21} & \displaystyle \int_0^1 \frac{1}{x^2+1} dx & a_{23} \\
a_{31} & a_{32} & a_{33}
\end{pNiceArray}$ 

```

$$\begin{pmatrix} a_{11} \\ a_{21} \\ a_{31} \end{pmatrix} \begin{pmatrix} a_{12} \\ \int_0^1 \frac{1}{x^2+1} dx \\ a_{32} \end{pmatrix} \begin{pmatrix} a_{13} \\ a_{23} \\ a_{33} \end{pmatrix}$$

The command `\SubMatrix` is, in fact, also available in the `\CodeBefore`. By using `\SubMatrix` in the `\CodeBefore`, the delimiters drawn by those commands `\SubMatrix` are taken into account to limit the continuous dotted lines (drawn by `\Cdots`, `\Vdots`, etc.) which have an open extremity. For an example, see voir [18.8](#) p. [58](#).

11.3 The commands `\OverBrace` and `\UnderBrace` in the `\CodeAfter`

The commands `\OverBrace` and `\UnderBrace` provide a way to put horizontal braces on a part of the array. These commands take in three arguments:

- the first argument is the upper-left corner of the submatrix with the syntax i - j where i the number of row and j the number of column;
- the second argument is the lower-right corner with the same syntax;
- the third argument is the label of the brace that will be put by `nicematrix` (with PGF) above the brace (for the command `\OverBrace`) or under the brace (for `\UnderBrace`).

```

\begin{pNiceMatrix}
1 & 2 & 3 & 4 & 5 & 6 \\
11 & 12 & 13 & 14 & 15 & 16 \\
\CodeAfter
\OverBrace{1-1}{2-3}{A}
\OverBrace{1-4}{2-6}{B}
\end{pNiceMatrix}

```

$$\begin{pmatrix} \overbrace{1 \quad 2 \quad 3}^A & \overbrace{4 \quad 5 \quad 6}^B \\ 11 & 12 & 13 & 14 & 15 & 16 \end{pmatrix}$$

In fact, the commands `\OverBrace` and `\UnderBrace` take in an optional argument (in first position and between square brackets) for a list of `key=value` pairs. The available keys are:

- `left-shorten` and `right-shorten` which do not take in value; when the key `left-shorten` is used, the abscissa of the left extremity of the brace is computed with the contents of the cells of the involved sub-array, otherwise, the position of the potential vertical rule is used (idem for `right-shorten`).
- `shorten`, which is the conjunction of the keys `left-shorten` and `right-shorten`;
- `yshift`, which shifts vertically the brace (and its label) ;
- `color`, which sets the color of the brace (and its label).

```

\begin{pNiceMatrix}
1 & 2 & 3 & 4 & 5 & 6 \\
11 & 12 & 13 & 14 & 15 & 16 \\
\CodeAfter
\OverBrace[shorten,yshift=3pt]{1-1}{2-3}{A}
\OverBrace[shorten,yshift=3pt]{1-4}{2-6}{B}
\end{pNiceMatrix}

```

$$\begin{pmatrix} \overbrace{1 \quad 2 \quad 3}^A & \overbrace{4 \quad 5 \quad 6}^B \\ 11 & 12 & 13 & 14 & 15 & 16 \end{pmatrix}$$

12 Captions and notes in the tabulars

12.1 Caption of a tabular

New 6.12 The environment `{NiceTabular}` provides the keys `caption`, `short-caption` and `label` which may be used when the tabular is inserted in a floating environment (typically the environment `{table}`).

With the key `caption`, the caption, when it is long, is wrapped at the width of the tabular (excepted the potential exterior columns specified by `first-col` and `last-col`), without the use of the package `threeparttable` or the package `floatrow`.

By default, the caption is composed below the tabular. With the key `caption-above`, available in `\NiceMatrixOptions`, the caption will be composed above the tabular.

The key `short-caption` corresponds to the optional argument of the classical command `\caption` and the key `label` corresponds, of course, to the command `\label`.

See table 1, p. 35 for an example of use the keys `caption` and `label`.

12.2 The footnotes

The package `nicematrix` allows, by using `footnote` or `footnotehyper`, the extraction of the notes inserted by `\footnote` in the environments of `nicematrix` and their composition in the footpage with the other notes of the document.

If `nicematrix` is loaded with the option `footnote` (with `\usepackage[footnote]{nicematrix}` or with `\PassOptionsToPackage`), the package `footnote` is loaded (if it is not yet loaded) and it is used to extract the footnotes.

If `nicematrix` is loaded with the option `footnotehyper`, the package `footnotehyper` is loaded (if it is not yet loaded) and it is used to extract footnotes.

Caution: The packages `footnote` and `footnotehyper` are incompatible. The package `footnotehyper` is the successor of the package `footnote` and should be used preferently. The package `footnote` has some drawbacks, in particular: it must be loaded after the package `xcolor` and it is not perfectly compatible with `hyperref`.

12.3 The notes of tabular

The package `nicematrix` also provides a command `\tabularnote` which gives the ability to specify notes that will be composed at the end of the array with a width of line equal to the width of the array (excepted the potential exterior columns specified by `first-col` and `last-col`). With no surprise, that command is available only in the environments `{NiceTabular}`, `{NiceTabular*}` and `{NiceTabularX}`.

In fact, this command is available only if the extension `enumitem` has been loaded (before or after `nicematrix`). Indeed, the notes are composed at the end of the array with a type of list provided by the package `enumitem`.

```
\begin{NiceTabular}{@{}llr@{}}
\toprule \RowStyle{\bfseries}
Last name & First name & Birth day \\
\midrule
Achard\tabularnote{Achard is an old family of the Poitou.}
& Jacques & 5 juin 1962 \\
Lefebvre\tabularnote{The name Lefebvre is an alteration of the name Lefebure.}
& Mathilde & 23 mai 1988 \\
Vanesse & Stephany & 30 octobre 1994 \\
Dupont & Chantal & 15 janvier 1998 \\
\bottomrule
\end{NiceTabular}
```

Last name	First name	Birth day
Achard ^a	Jacques	June 5, 2005
Lefebvre ^b	Mathilde	January 23, 1975
Vanesse	Stephany	October 30, 1994
Dupont	Chantal	January 15, 1998

^a Achard is an old family of the Poitou.

^b The name Lefebvre is an alteration of the name Lefebure.

- If you have several successive commands `\tabularnote{...}` with no space at all between them, the labels of the corresponding notes are composed together, separated by commas (this is similar to the option `multiple` of `footmisc` for the footnotes).
- If a command `\tabularnote{...}` is exactly at the end of a cell (with no space at all after), the label of the note is composed in an overlapping position (towards the right). This structure may provide a better alignment of the cells of a given column.
- If the key `notes/para` is used, the notes are composed at the end of the array in a single paragraph (as with the key `para` of `threeparttable`).
- There is a key `tabularnote` which provides a way to insert some text in the zone of the notes before the numbered tabular notes.

New 6.13 An alternative syntaxe is available with the environment `{TabularNote}`. That environment should be used at the end of the environment `{NiceTabular}` (but *before* a potential instruction `\CodeAfter`).

- If the package `booktabs` has been loaded (before or after `nicematrix`), the key `notes/bottomrule` draws a `\bottomrule` of `booktabs` *after* the notes.
- The command `\tabularnote` may be used *before* the environment of `nicematrix`. Thus, it's possible to use it on the title inserted by `\caption` in an environment `{table}` of LaTeX (or in a command `\captionof` of the package `caption`). It's also possible, as expected, to use the command `\tabularnote` in the caption provided by the *key* `caption` of the environment `{NiceTabular}`.

If several commands `\tabularnote` are used in a tabular with the same argument, only one note is inserted at the end of the tabular (but all the labels are composed, of course). It's possible to control that feature with the key `notes/detect-duplicates`.⁴⁴

- It's possible to create a reference to a tabular note created by `\tabularnote` (with the usual command `\label` used after the `\tabularnote`).

For an illustration of some of those remarks, see table 1, p. 35. This table has been composed with the following code (the package `caption` has been loaded in this document).

```
\begin{table}
\centering
\NiceMatrixOptions{caption-above}
\begin{NiceTabular}{@{}llc@{}}
[
caption = A tabular whose caption has been specified by the key
\texttt{caption}\tabularnote{It's possible to put a tabular note in the caption} ,
label = t:tabularnote ,
tabularnote = Some text before the notes. ,
notes/bottomrule
]
```

⁴⁴For technical reasons, the final user is not allowed to put several commands `\tabularnote` with exactly the same argument in the caption of the tabular.

```

\toprule
Last name & First name & Length of life \\
\midrule
Churchill & Wiston & 91\\
Nightingale\-tabularnote{Considered as the first nurse of history}
\-tabularnote{Nicknamed ``the Lady with the Lamp''.}
& Florence\-tabularnote{This note is shared by two references.} & 90 \\
Schoelcher & Victor & 89\-tabularnote{The label of the note is overlapping.}\\
Touchet & Marie\-tabularnote{This note is shared by two references.} & 89 \\
Wallis & John & 87 \\
\bottomrule
\end{NiceTabular}
\end{table}

```

Table 1: A tabular whose caption has been specified by the key `caption`^a

Last name	First name	Length of life
Churchill	Wiston	91
Nightingale ^{b,c}	Florence ^d	90
Schoelcher	Victor	89 ^e
Touchet	Marie ^d	89
Wallis	John	87

Some text before the notes.

^a It's possible to put a tabular note in the caption

^b Considered as the first nurse of history.

^c Nicknamed “the Lady with the Lamp”.

^d This note is shared by two references.

^e The label of the note is overlapping.

12.4 Customisation of the tabular notes

The tabular notes can be customized with a set of keys available in `\NiceMatrixOptions`. The name of these keys is prefixed by `notes`.

- `notes/para`
- `notes/bottomrule`
- `notes/style`
- `notes/label-in-tabular`
- `notes/label-in-list`
- `notes/enumitem-keys`
- `notes/enumitem-keys-para`
- `notes/code-before`

For sake of commodity, it is also possible to set these keys in `\NiceMatrixOptions` via a key `notes` which takes in as value a list of pairs `key=value` where the name of the keys need no longer be prefixed by `notes`:

```

\NiceMatrixOptions
{
  notes =
  {
    bottomrule ,
    style = ... ,
    label-in-tabular = ... ,
    enumitem-keys =
    {
      labelsep = ... ,
      align = ... ,
      ...
    }
  }
}

```

We detail these keys.

- The key `notes/para` requires the composition of the notes (at the end of the tabular) in a single paragraph.

Initial value: `false`

That key is also available within a given environment.

- The key `notes/bottomrule` adds a `\bottomrule` of `booktabs` *after* the notes. Of course, that rule is drawn only if there is really notes in the tabular. The package `booktabs` must have been loaded (before or after the package `nicematrix`). If it is not, an error is raised.

Initial value: `false`

That key is also available within a given environment.

- The key `notes/style` is a command whose argument is specified by `#1` and which gives the style of numerotation of the notes. That style will be used by `\ref` when referencing a tabular note marked with a command `\label`. The labels formatted by that style are used, separated by commas, when the user puts several consecutive commands `\tabularnote`. The marker `#1` is meant to be the name of a LaTeX counter.

Initial value: `\textit{\alph{#1}}`

Another possible value should be a mere `\arabic{#1}`

- The key `notes/label-in-tabular` is a command whose argument is specified by `#1` which is used when formatting the label of a note in the tabular. Internally, this number of note has already been formatted by `notes/style` before sent to that command.

Initial value: `#1`

In French, it's a tradition of putting a small space before the label of note. That tuning could be achieved by the following code:

```
\NiceMatrixOptions{notes/label-in-tabular = \,\textsuperscript{#1}}
```

- The key `notes/label-in-list` is a command whose argument is specified by `#1` which is used when formatting the label in the list of notes at the end of the tabular. Internally, this number of note has already been formatted by `notes/style` before sent to that command.

Initial value: `#1`

In French, the labels of notes are not composed in upper position when composing the notes. Such behaviour could be achieved by:

```
\NiceMatrixOptions{notes/label-in-list = #1.\nobreak\hspace{0.25em}}
```

The command `\nobreak` is for the event that the option `para` is used.

- The notes are composed at the end of the tabular by using internally a style of list of `enumitem`. This style of list is defined as follows (with, of course, keys of `enumitem`):

```
noitemsep , leftmargin = * , align = left , labelsep = Opt
```

The specification `align = left` in that style requires a composition of the label leftwards in the box affected to that label. With that tuning, the notes are composed flush left, which is pleasant when composing tabulars in the spirit of `booktabs` (see for example the table 1, p. 35).

The key `notes/enumitem-keys` specifies a list of pairs `key=value` (following the specifications of `enumitem`) to customize that style of list (it uses internally the command `\setlist*` of `enumitem`).

- The key `notes/enumitem-keys-para` is similar to the previous one but corresponds to the type of list used when the option `para` is in force. Of course, when the option `para` is used, a list of type `inline` (as called by `enumitem`) is used and the pairs `key=value` should correspond to such a list of type `inline`.

Initially, the style of list is defined by: `afterlabel = \nobreak, itemjoin = \quad`

- The key `notes/code-before` is a token list inserted by `nicematrix` just before the composition of the notes at the end of the tabular.

Initial value: *empty*

For example, if one wishes to compose all the notes in gray and `\footnotesize`, he should use that key:

```
\NiceMatrixOptions{notes/code-before = \footnotesize \color{gray}}
```

It's also possible to add `\raggedright` or `\RaggedRight` in that key (`\RaggedRight` is a command of `ragged2e`).

- The key `notes/detect-duplicates` activates the detection of the commands `\tabularnotes` with the same argument.

Initial value : `true`

For an example of customisation of the tabular notes, see p. 49.

12.5 Use of `{NiceTabular}` with `threeparttable`

If you wish to use the environment `{NiceTabular}`, `{NiceTabular*}` `{NiceTabularX}` in an environment `{threeparttable}` of the eponymous package, you have to patch the environment `{threeparttable}` with the following code (with a version of LaTeX at least 2020/10/01).

```
\makeatletter
\AddToHook{env/threeparttable/begin}
{ \TPT@hookin{NiceTabular} \TPT@hookin{NiceTabular*} \TPT@hookin{NiceTabularX} }
\makeatother
```

13 Other features

14 Autres fonctionnalités

14.1 Command `\ShowCellNames`

The command `\ShowCellNames`, which may be used in the `\CodeBefore` and in the `\CodeAfter` display the name (with the form *i-j*) of each cell. When used in the `\CodeAfter`, that command

applies a semi-transparent white rectangle to fade the array (caution: some PDF readers don't support transparency).

```
\begin{NiceTabular}{ccc}[hvlines,cell-space-limits=3pt]
  \Block{2-2}{} & & & test \\
  & & & blabla \\
  & & & some text & nothing \\
\CodeAfter \ShowCellNames
\end{NiceTabular}
```

1-1	1-2	1-3
2-1	2-2	2-3
3-1	3-2	3-3

14.2 Use of the column type S of siunitx

If the package siunitx is loaded (before or after nicematrix), it's possible to use the S column type of siunitx in the environments of nicematrix. The implementation doesn't use explicitly any private macro of siunitx.

```
$\begin{pNiceArray}{ScW{c}{1cm}c}[nullify-dots,first-row]
{C_1} & \Cdots & & C_n \\
2.3 & 0 & \Cdots & 0 \\
12.4 & \Vdots & & \Vdots \\
1.45 & \\
7.2 & 0 & \Cdots & 0 \\
\end{pNiceArray}$
```

$$\begin{pmatrix} C_1 & \dots & \dots & C_n \\ 2.3 & 0 & \dots & 0 \\ 12.4 & \vdots & & \vdots \\ 1.45 & \vdots & & \vdots \\ 7.2 & 0 & \dots & 0 \end{pmatrix}$$

On the other hand, the d columns of the package dcolumn are not supported by nicematrix.

14.3 Default column type in {NiceMatrix}

New 6.11 The environments without preamble ({NiceMatrix}, {pNiceMatrix}, {bNiceMatrix}, etc.) and the commande \pAutoNiceMatrix (and its variants) provide an option columns-type to specify the type of column which will be used (the initial value is, of course, c).

The keys l and r are shortcuts for columns-type=l and columns-type=r.

```
$\begin{bNiceMatrix}[r]
\cos x & - \sin x \\
\sin x & \cos x
\end{bNiceMatrix}$
```

$$\begin{bmatrix} \cos x & -\sin x \\ \sin x & \cos x \end{bmatrix}$$

The key columns-type is available in \NiceMatrixOptions but with the prefix matrix, which means that its name is, within \NiceMatrixOptions : matrix/columns-type.

14.4 The command \rotate

The package nicematrix provides a command \rotate. When used in the beginning of a cell, this command composes the contents of the cell after a rotation of 90° in the direct sens.

In the following command, we use that command in the code-for-first-row.⁴⁵

```
\NiceMatrixOptions%
{code-for-first-row = \scriptstyle \rotate \text{image of },
code-for-last-col = \scriptstyle }
$A = \begin{pNiceMatrix}[first-row,last-col=4]
e_1 & e_2 & e_3 & \\
1 & 2 & 3 & e_1 \\
4 & 5 & 6 & e_2 \\
7 & 8 & 9 & e_3
\end{pNiceMatrix}$
```

$$A = \begin{pmatrix} \text{image of } e_1 & \text{image of } e_2 & \text{image of } e_3 \\ 1 & 2 & 3 \\ 4 & 5 & 6 \\ 7 & 8 & 9 \end{pmatrix} \begin{matrix} e_1 \\ e_2 \\ e_3 \end{matrix}$$

If the command \rotate is used in the “last row” (exterior to the matrix), the corresponding elements are aligned upwards as shown below.

⁴⁵It can also be used in \RowStyle (cf. p. 19).

```

\NiceMatrixOptions%
{code-for-last-row = \scriptstyle \rotate ,
 code-for-last-col = \scriptstyle }
$A = \begin{pNiceMatrix}[last-row=4,last-col=4]
1 & 2 & 3 & e_1 \\
4 & 5 & 6 & e_2 \\
7 & 8 & 9 & e_3 \\
\text{image of } & e_1 & e_2 & e_3
\end{pNiceMatrix}$

```

$$A = \begin{pmatrix} 1 & 2 & 3 \\ 4 & 5 & 6 \\ 7 & 8 & 9 \end{pmatrix} \begin{matrix} e_1 \\ e_2 \\ e_3 \end{matrix}$$

image of e_1 e_2 e_3

14.5 The option `small`

With the option `small`, the environments of the package `nicematrix` are composed in a way similar to the environment `{smallmatrix}` of the package `amsmath` (and the environments `{psmallmatrix}`, `{bsmallmatrix}`, etc. of the package `mathtools`).

```

$\begin{bNiceArray}{cccc|c}[small,
                        last-col,
                        code-for-last-col = \scriptscriptstyle,
                        columns-width = 3mm ]
1 & -2 & 3 & 4 & 5 \\
0 & 3 & 2 & 1 & 2 & L_2 \text{ gets } 2 L_1 - L_2 \\
0 & 1 & 1 & 2 & 3 & L_3 \text{ gets } L_1 + L_3
\end{bNiceArray}$

```

$$\left[\begin{array}{cccc|c} 1 & -2 & 3 & 4 & 5 \\ 0 & 3 & 2 & 1 & 2 \\ 0 & 1 & 1 & 2 & 3 \end{array} \right] \begin{matrix} \\ L_2 \leftarrow 2L_1 - L_2 \\ L_3 \leftarrow L_1 + L_3 \end{matrix}$$

One should note that the environment `{NiceMatrix}` with the option `small` is not composed *exactly* as the environment `{smallmatrix}`. Indeed, all the environments of `nicematrix` are constructed upon `{array}` (of the package `array`) whereas the environment `{smallmatrix}` is constructed directly with an `\halign` of TeX.

In fact, the option `small` corresponds to the following tuning:

- the cells of the array are composed with `\scriptstyle`;
- `\arraystretch` is set to 0.47;
- `\arraycolsep` is set to 1.45 pt;
- the characteristics of the dotted lines are also modified.

14.6 The counters `iRow` and `jCol`

In the cells of the array, it's possible to use the LaTeX counters `iRow` and `jCol` which represent the number of the current row and the number of the current column⁴⁶. Of course, the user must not change the value of these counters which are used internally by `nicematrix`.

In the `\CodeBefore` (cf. p. 14) and in the `\CodeAfter` (cf. p. 29), `iRow` represents the total number of rows (excepted the potential exterior rows) and `jCol` represents the total number of columns (excepted the potential exterior columns).

⁴⁶We recall that the exterior “first row” (if it exists) has the number 0 and that the exterior “first column” (if it exists) has also the number 0.

```

 $\begin{pNiceMatrix}$ % don't forget the %
[first-row,
first-col,
code-for-first-row = \mathbf{\alpha{jCol}} ,
code-for-first-col = \mathbf{\arabic{iRow}} ]
& & & & \\
& 1 & 2 & 3 & 4 \\
& 5 & 6 & 7 & 8 \\
& 9 & 10 & 11 & 12
\end{pNiceMatrix}

```

$$\begin{matrix} & \mathbf{a} & \mathbf{b} & \mathbf{c} & \mathbf{d} \\ \mathbf{1} & 1 & 2 & 3 & 4 \\ \mathbf{2} & 5 & 6 & 7 & 8 \\ \mathbf{3} & 9 & 10 & 11 & 12 \end{matrix}$$

If LaTeX counters called `iRow` and `jCol` are defined in the document by packages other than `nicematrix` (or by the final user), they are shadowed in the environments of `nicematrix`.

The package `nicematrix` also provides commands in order to compose automatically matrices from a general pattern. These commands are `\AutoNiceMatrix`, `\pAutoNiceMatrix`, `\bAutoNiceMatrix`, `\vAutoNiceMatrix`, `\VAutoNiceMatrix` and `\BAutoNiceMatrix`.

These commands take in two mandatory arguments. The first is the format of the matrix, with the syntax $n-p$ where n is the number of rows and p the number of columns. The second argument is the pattern (it's a list of tokens which are inserted in each cell of the constructed matrix).

```

 $C = \pAutoNiceMatrix{3-3}{C_{\arabic{iRow},\arabic{jCol}}}$ 

```

$$C = \begin{pmatrix} C_{1,1} & C_{1,2} & C_{1,3} \\ C_{2,1} & C_{2,2} & C_{2,3} \\ C_{3,1} & C_{3,2} & C_{3,3} \end{pmatrix}$$

14.7 The key `light-syntax`

The option `light-syntax` (inpired by the package `spalign`) allows the user to compose the arrays with a lighter syntax, which gives a better legibility of the TeX source.

When this option is used, one should use the semicolon for the end of a row and spaces or tabulations to separate the columns. However, as usual in the TeX world, the spaces after a control sequence are discarded and the elements between curly braces are considered as a whole.

```

 $\begin{bNiceMatrix}[light-syntax,first-row,first-col]$ 
{} a          b          ;
a 2\cos a     {\cos a + \cos b} ;
b \cos a+\cos b { 2 \cos b }
\end{bNiceMatrix}

```

$$\begin{matrix} & a & b \\ a & \begin{bmatrix} 2 \cos a & \cos a + \cos b \end{bmatrix} \\ b & \begin{bmatrix} \cos a + \cos b & 2 \cos b \end{bmatrix} \end{matrix}$$

It's possible to change the character used to mark the end of rows with the option `end-of-row`. As said before, the initial value is a semicolon.

When the option `light-syntax` is used, it is not possible to put verbatim material (for example with the command `\verb`) in the cells of the array.⁴⁷

14.8 Color of the delimiters

For the environments with delimiters (`\pNiceArray`, `\pNiceMatrix`, etc.), it's possible to change the color of the delimiters with the key `delimiters/color`.

```

 $\begin{bNiceMatrix}[delimiters/color=red]$ 
1 & 2 \\
3 & 4
\end{bNiceMatrix}

```

$$\begin{bmatrix} 1 & 2 \\ 3 & 4 \end{bmatrix}$$

This colour also applies to the delimiters drawn by the command `\SubMatrix` (cf. p. 30).

⁴⁷The reason is that, when the option `light-syntax` is used, the whole content of the environment is loaded as a TeX argument to be analyzed. The environment doesn't behave in that case as a standard environment of LaTeX which only put TeX commands before and after the content.

14.9 The environment `{NiceArrayWithDelims}`

In fact, the environment `{pNiceArray}` and its variants are based upon a more general environment, called `{NiceArrayWithDelims}`. The first two mandatory arguments of this environment are the left and right delimiters used in the construction of the matrix. It's possible to use `{NiceArrayWithDelims}` if we want to use atypical or asymmetrical delimiters.

```

$\begin{NiceArrayWithDelims}
  {\downarrow}{\uparrow}{ccc}[margin]
1 & 2 & 3 \\
4 & 5 & 6 \\
7 & 8 & 9
\end{NiceArrayWithDelims}
```

$$\begin{array}{ccc} 1 & 2 & 3 \\ 4 & 5 & 6 \\ 7 & 8 & 9 \end{array}$$

14.10 The command `\OnlyMainNiceMatrix`

The command `\OnlyMainNiceMatrix` executes its argument only when it is in the main part of the array, that is to say it is not in one of the exterior rows. If it is used outside an environment of `nicematrix`, that command is no-op.

For an example of utilisation, see tex.stackexchange.com/questions/488566

15 Use of Tikz with `nicematrix`

15.1 The nodes corresponding to the contents of the cells

The package `nicematrix` creates a PGF/Tikz node for each (non-empty) cell of the considered array. These nodes are used to draw the dotted lines between the cells of the matrix (inter alia).

Caution : By default, no node is created in a empty cell.

However, it's possible to impose the creation of a node with the command `\NotEmpty`. ⁴⁸

The nodes of a document must have distinct names. That's why the names of the nodes created by `nicematrix` contains the number of the current environment. Indeed, the environments of `nicematrix` are numbered by a internal global counter.

In the environment with the number n , the node of the row i and column j has for name `nm-n-i-j`.

The command `\NiceMatrixLastEnv` provides the number of the last environment of `nicematrix` (for LaTeX, it's a “fully expandable” command and not a counter).

However, it's advisable to use instead the key `name`. This key gives a name to the current environment. When the environment has a name, the nodes are accessible with the name “*name-i-j*” where *name* is the name given to the array and i and j the numbers of row and column. It's possible to use these nodes with PGF but the final user will probably prefer to use Tikz (which is a convenient layer upon PGF). However, one should remind that `nicematrix` doesn't load Tikz by default. In the following examples, we assume that Tikz has been loaded.

```

$\begin{pNiceMatrix}[name=mymatrix]
1 & 2 & 3 \\
4 & 5 & 6 \\
7 & 8 & 9
\end{pNiceMatrix}
\tikz[remember picture,overlay]
  \draw (mymatrix-2-2) circle (2mm) ;
```

$$\begin{pmatrix} 1 & 2 & 3 \\ 4 & \textcircled{5} & 6 \\ 7 & 8 & 9 \end{pmatrix}$$

Don't forget the options `remember picture` and `overlay`.

⁴⁸One should note that, with that command, the cell is considered as non-empty, which has consequences for the continuous dotted lines (cf. p. 23) and the computation of the “corners” (cf. p. 10).

In the `\CodeAfter`, the things are easier : one must refer to the nodes with the form $i-j$ (we don't have to indicate the environment which is of course the current environment).

```

 $\begin{pNiceMatrix}$ 
1 & 2 & 3 \\
4 & 5 & 6 \\
7 & 8 & 9
 $\CodeAfter$ 
\tikz \draw (2-2) circle (2mm) ;
 $\end{pNiceMatrix}$ 

```

$$\begin{pmatrix} 1 & 2 & 3 \\ 4 & \textcircled{5} & 6 \\ 7 & 8 & 9 \end{pmatrix}$$

In the following example, we have underlined all the nodes of the matrix (we explain below the technic used : cf. p. 56).

$$\begin{pmatrix} a & a+b & a+b+c \\ a & a & a+b \\ a & a & a \end{pmatrix}$$

The nodes of the last column (excepted the potential «last column» specified by `last-col`) may also be indicated by i -last. Similarly, the nodes of the last row may be indicated by last- j .

15.1.1 The columns V of varwidth

When the extension `varwidth` is loaded, the columns of the type `V` defined by `varwidth` are supported by `nicematrix`. It may be interessant to notice that, for a cell of a column of type `V`, the PGF/Tikz node created by `nicematrix` for the content of that cell has a width adjusted to the content of the cell. This is in contrast to the case of the columns of type `p`, `m` or `b` for which the nodes have always a width equal to the width of the column. In the following example, the command `\lipsum` is provided by the eponymous package.

```

\begin{NiceTabular}{V{10cm}}
\bfseries \large
Titre \\
\lipsum[1][1-4]
\CodeAfter
\tikz \draw [rounded corners] (1-1) -| (last-|2) -- (last-|1) |- (1-1) ;
\end{NiceTabular}

```

Titre

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna.

We have used the nodes corresponding to the position of the potential rules, which are described below (cf. p. 44).

15.2 The “medium nodes” and the “large nodes”

In fact, the package `nicematrix` can create “extra nodes”: the “medium nodes” and the “large nodes”. The first ones are created with the option `create-medium-nodes` and the second ones with the option `create-large-nodes`.⁴⁹

These nodes are not used by `nicematrix` by default, and that's why they are not created by default.

⁴⁹There is also an option `create-extra-nodes` which is an alias for the conjunction of `create-medium-nodes` and `create-large-nodes`.

The names of the “medium nodes” are constructed by adding the suffix “-medium” to the names of the “normal nodes”. In the following example, we have underlined the “medium nodes”. We consider that this example is self-explanatory.

$$\begin{pmatrix} a & a+b & a+b+c \\ a & a & a+b \\ a & a & a \end{pmatrix}$$

The names of the “large nodes” are constructed by adding the suffix “-large” to the names of the “normal nodes”. In the following example, we have underlined the “large nodes”. We consider that this example is self-explanatory.⁵⁰

$$\begin{pmatrix} a & a+b & a+b+c \\ a & a & a+b \\ a & a & a \end{pmatrix}$$

The “large nodes” of the first column and last column may appear too small for some usage. That’s why it’s possible to use the options `left-margin` and `right-margin` to add space on both sides of the array and also space in the “large nodes” of the first column and last column. In the following example, we have used the options `left-margin` and `right-margin`.⁵¹

$$\begin{pmatrix} a & a+b & a+b+c \\ a & a & a+b \\ a & a & a \end{pmatrix}$$

It’s also possible to add more space on both side of the array with the options `extra-left-margin` and `extra-right-margin`. These margins are not incorporated in the “large nodes”. It’s possible to fix both values with the option `extra-margin` and, in the following example, we use `extra-margin` with the value 3 pt.

$$\begin{pmatrix} a & a+b & a+b+c \\ a & a & a+b \\ a & a & a \end{pmatrix}$$

Be careful : These nodes are reconstructed from the contents of the contents cells of the array. Usually, they do not correspond to the cells delimited by the rules (if we consider that these rules are drawn).

Here is an array composed with the following code:

```
\large
\begin{NiceTabular}{wl{2cm}ll}[hvlines]
fraise & amande & abricot \\
prune & pêche & poire \\[1ex]
noix & noisette & brugnon
\end{NiceTabular}
```

fraise	amande	abricot
prune	pêche	poire
noix	noisette	brugnon

Here, we have colored all the cells of the array with `\chessboardcolors`.

fraise	amande	abricot
prune	pêche	poire
noix	noisette	brugnon

⁵⁰There is no “large nodes” created in the exterior rows and columns (for these rows and columns, cf. p. 22).

⁵¹The options `left-margin` and `right-margin` take dimensions as values but, if no value is given, the default value is used, which is `\arraycolsep` (by default: 5 pt). There is also an option `margin` to fix both `left-margin` and `right-margin` to the same value.

Here are the “large nodes” of this array (without use of `margin` nor `extra-margin`).

fraise	amande	abricot
prune	pêche	poire
noix	noisette	brugnon

The nodes we have described are not available by default in the `\CodeBefore` (described p. 14). It’s possible to have these nodes available in the `\CodeBefore` by using the key `create-cell-nodes` of the keyword `\CodeBefore` (in that case, the nodes are created first before the construction of the array by using informations written on the `aux` file and created a second time during the construction of the array itself).

Here is an example which uses these nodes in the `\CodeAfter`.

```
\begin{NiceArray}{c@{\;}c@{\;}c@{\;}c}[create-medium-nodes]
  u_1 & - & u_0 & = & r & \\
  u_2 & - & u_1 & = & r & \\
  u_3 & - & u_2 & = & r & \\
  u_4 & - & u_3 & = & r & \\
  \phantom{u_5} & & \phantom{u_4} & & \smash{\vdots} & \\
  u_n & - & u_{n-1} & = & r & \\
\hline
  u_n & - & u_0 & = & nr & \\
\CodeAfter
  \tikz[very thick, red, opacity=0.4,name suffix = -medium]
  \draw (1-1.north west) -- (2-3.south east)
  (2-1.north west) -- (3-3.south east)
  (3-1.north west) -- (4-3.south east)
  (4-1.north west) -- (5-3.south east)
  (5-1.north west) -- (6-3.south east) ;
\end{NiceArray}
```

$$\begin{array}{rclcl}
 u_1 & - & u_0 & = & r \\
 u_2 & - & u_1 & = & r \\
 u_3 & - & u_2 & = & r \\
 u_4 & - & u_3 & = & r \\
 & & \vdots & & \\
 u_n & - & u_{n-1} & = & r \\
 \hline
 u_n & - & u_0 & = & nr
 \end{array}$$

15.3 The nodes which indicate the position of the rules

The package `nicematrix` creates a PGF/Tikz node merely called i (with the classical prefix) at the intersection of the horizontal rule of number i and the vertical rule of number i (more specifically the potential position of those rules because maybe there are not actually drawn). The last node has also an alias called `last`. There is also a node called $i.5$ midway between the node i and the node $i + 1$. These nodes are available in the `\CodeBefore` and the `\CodeAfter`.

	$\bullet^{1.5}$	tulipe	lys
arum		$\bullet^{2.5}$	violette mauve
muguet	dahlia		$\bullet^{3.5}$

If we use Tikz (we remind that `nicematrix` does not load Tikz by default, by only PGF, which is a sub-layer of Tikz), we can access, in the `\CodeAfter` but also in the `\CodeBefore`, to the intersection of the (potential) horizontal rule i and the (potential) vertical rule j with the syntax $(i-j)$.

```

\begin{NiceMatrix}
\CodeBefore
\tikz \draw [fill=red!15] (7-|4) |- (8-|5) |- (9-|6) |- cycle ;
\Body
1 \\\
1 & 1 \\\
1 & 2 & 1 \\\
1 & 3 & 3 & 1 \\\
1 & 4 & 6 & 4 & 1 \\\
1 & 5 & 10 & 10 & 5 & 1 \\\
1 & 6 & 15 & 20 & 15 & 6 & 1 \\\
1 & 7 & 21 & 35 & 35 & 21 & 7 & 1 \\\
1 & 8 & 28 & 56 & 70 & 56 & 28 & 8 & 1
\end{NiceMatrix}

```

```

1
1 1
1 2 1
1 3 3 1
1 4 6 4 1
1 5 10 10 5 1
1 6 15 20 15 6 1
1 7 21 35 35 21 7 1
1 8 28 56 70 56 28 8 1

```

The nodes of the form $i.5$ may be used, for example to cross a row of a matrix (if Tikz is loaded).

```

$\begin{pNiceArray}{ccc|c}
2 & 1 & 3 & 0 \\\
3 & 3 & 1 & 0 \\\
3 & 3 & 1 & 0
\CodeAfter
\tikz \draw [red] (3.5-|1) -- (3.5-|last) ;
\end{pNiceArray}$

```

$$\left(\begin{array}{ccc|c} 2 & 1 & 3 & 0 \\ 3 & 3 & 1 & 0 \\ \hline 3 & 3 & 1 & 0 \end{array}\right)$$

15.4 The nodes corresponding to the command `\SubMatrix`

The command `\SubMatrix` available in the `\CodeAfter` has been described p. 30.

If a command `\SubMatrix` has been used with the key `name` with an expression such as `name=MyName` three PGF/Tikz nodes are created with the names `MyName-left`, `MyName` and `MyName-right`.

The nodes `MyName-left` and `MyName-right` correspond to the delimiters left and right and the node `MyName` correspond to the submatrix itself.

In the following example, we have highlighted these nodes (the submatrix itself has been created with `\SubMatrix\{{2-2}\{3-3}\}`).

$$\left(\begin{array}{cccc} 121 & 23 & 345 & 345 \\ 45 & \left\{ \begin{array}{cc} 346 & 863 \\ 38458 & 34 \end{array} \right\} & 444 & \\ 3462 & & 294 & \\ 34 & 7 & 78 & 309 \end{array}\right)$$

16 API for the developpers

The package `nicematrix` provides two variables which are internal but public⁵²:

- `\g_nicematrix_code_before_tl` ;
- `\g_nicematrix_code_after_tl`.

These variables contain the code of what we have called the “code-before” (usually specified at the beginning of the environment with the syntax using the keywords `\CodeBefore` and `\Body`) and the “code-after” (usually specified at the end of the environment after the keyword `\CodeAfter`). The developer can use them to add code from a cell of the array (the affectation must be global, allowing to exit the cell, which is a TeX group).

One should remark that the use of `\g_nicematrix_code_before_tl` needs one compilation more (because the instructions are written on the `aux` file to be used during the next run).

Example : We want to write a command `\crossbox` to draw a cross in the current cell. This command will take in an optional argument between square brackets for a list of pairs *key-value* which will be given to Tikz before the drawing.


It’s possible to program such command `\crossbox` as follows, explicitly using the public variable `\g_nicematrix_code_before_tl`.

```
\ExplSyntaxOn
\cs_new_protected:Nn \__pantigny_crossbox:nnn
{
  \tikz \draw [ #3 ]
    ( #1 -| \int_eval:n { #2 + 1 } ) -- ( \int_eval:n { #1 + 1 } -| #2 )
    ( #1 -| #2 ) -- ( \int_eval:n { #1 + 1 } -| \int_eval:n { #2 + 1 } ) ;
}

\NewDocumentCommand \crossbox { ! 0 { } }
{
  \tl_gput_right:Nx \g_nicematrix_code_before_tl
  {
    \__pantigny_crossbox:nnn
    { \int_use:c { c@iRow } }
    { \int_use:c { c@jCol } }
    { \exp_not:n { #1 } }
  }
}
\ExplSyntaxOff
```

Here is an example of utilisation:

```
\begin{NiceTabular}{ccc}[hvlines]
\CodeBefore
  \arraycolor{gray!10}
\Body
merlan & requin & cabillaud \\
baleine & \crossbox[red] & morue \\
mante & raie & poule
\end{NiceTabular}
```

merlan	requin	cabillaud
baleine		morue
mante	raie	poule

⁵²According to the LaTeX3 conventions, each variable with name beginning with `\g_nicematrix` ou `\l_nicematrix` is public and each variable with name beginning with `\g__nicematrix` or `\l__nicematrix` is private.

17 Technical remarks

First remark: the package `underscore` must be loaded before `nicematrix`.

17.1 Diagonal lines

By default, all the diagonal lines⁵³ of a same array are “parallelized”. That means that the first diagonal line is drawn and, then, the other lines are drawn parallel to the first one (by rotation around the left-most extremity of the line). That’s why the position of the instructions `\Ddots` in the array can have a marked effect on the final result.

In the following examples, the first `\Ddots` instruction is written in color:

Example with parallelization (default):

```
$A = \begin{pNiceMatrix}
1      & \Cdots &      & 1      & \\
a+b    & \Ddots &      & \Vdots & \\
\Vdots & \Ddots &      &        & \\
a+b    & \Cdots & a+b  & 1      & \\
\end{pNiceMatrix}$
```

$$A = \begin{pmatrix} 1 & \cdots & \cdots & \cdots & 1 \\ a+b & \ddots & & & \\ \vdots & \ddots & & & \\ \vdots & & & & \\ a+b & \cdots & \cdots & a+b & 1 \end{pmatrix}$$

```
$A = \begin{pNiceMatrix}
1      & \Cdots &      & 1      & \\
a+b    &        &      & \Vdots & \\
\Vdots & \Ddots & \Ddots &        & \\
a+b    & \Cdots & a+b  & 1      & \\
\end{pNiceMatrix}$
```

$$A = \begin{pmatrix} 1 & \cdots & \cdots & \cdots & 1 \\ a+b & & & & \\ \vdots & \ddots & & & \\ \vdots & & & & \\ a+b & \cdots & \cdots & a+b & 1 \end{pmatrix}$$

It’s possible to turn off the parallelization with the option `parallelize-diags` set to `false`:

The same example without parallelization:

$$A = \begin{pmatrix} 1 & \cdots & \cdots & \cdots & 1 \\ a+b & & & & \\ \vdots & \ddots & & & \\ \vdots & & & & \\ a+b & \cdots & \cdots & a+b & 1 \end{pmatrix}$$

It’s possible to specify the instruction `\Ddots` which will be drawn first (and which will be used to draw the other diagonal dotted lines when the parallelization is in force) with the key `draw-first`: `\Ddots[draw-first]`.

17.2 The “empty” cells

An instruction like `\Ldots`, `\Cdots`, etc. tries to determine the first non-empty cell on both sides. When the key `corners` is used (cf. p. 10), `nicematrix` computes corners consisting of empty cells. However, an “empty cell” is not necessarily a cell with no TeX content (that is to say a cell with no token between the two ampersands `&`). The precise rules are as follow.

- An implicit cell is empty. For example, in the following matrix:

```
\begin{pmatrix}
a & b \\
c & \\
\end{pmatrix}
```

the last cell (second row and second column) is empty.

⁵³We speak of the lines created by `\Ddots` and not the lines created by a command `\line` in the `\CodeAfter`.

- For the columns of type `p`, `m`, `b`, `V`⁵⁴ and `X`⁵⁵, the cell is empty if (and only if) its content in the TeX code is empty (there is only spaces between the ampersands `&`).
- For the columns of type `c`, `l`, `r` and `w{\dots}{\dots}`, the cell is empty if (and only if) its TeX output has a width equal to zero.
- A cell containing the command `\NotEmpty` is not empty (and a PGF/Tikz node is created in that cell).
- A cell with only a command `\Hspace` (or `\Hspace*`) is empty. This command `\Hspace` is a command defined by the package `nicematrix` with the same meaning as `\hspace` except that the cell where it is used is considered as empty. This command can be used to fix the width of some columns of the matrix without interfering with `nicematrix`.

17.3 The option `exterior-arraycolsep`

The environment `{array}` inserts an horizontal space equal to `\arraycolsep` before and after each column. In particular, there is a space equal to `\arraycolsep` before and after the array. This feature of the environment `{array}` was probably not a good idea⁵⁶. The environment `{matrix}` of `amsmath` and its variants (`{pmatrix}`, `{vmatrix}`, etc.) of `amsmath` prefer to delete these spaces with explicit instructions `\hskip -\arraycolsep`⁵⁷. The package `nicematrix` does the same in all its environments, `{NiceArray}` included. However, if the user wants the environment `{NiceArray}` behaving by default like the environment `{array}` of `array` (for example, when adapting an existing document) it's possible to control this behaviour with the option `exterior-arraycolsep`, set by the command `\NiceMatrixOptions`. With this option, exterior spaces of length `\arraycolsep` will be inserted in the environments `{NiceArray}` (the other environments of `nicematrix` are not affected).

17.4 Incompatibilities

The package `nicematrix` is not compatible with the class `ieeeaccess` (because that class is not compatible with PGF/Tikz).⁵⁸

In order to use `nicematrix` with the class `aastex631`, you have to add the following lines in the preamble of your document :

```
\BeforeBegin{NiceTabular}{\let\begin\BeginEnvironment\let\end\EndEnvironment}
\BeforeBegin{NiceArray}{\let\begin\BeginEnvironment}
\BeforeBegin{NiceMatrix}{\let\begin\BeginEnvironment}
```

In order to use `nicematrix` with the class `sn-jnl`, `pgf` must be loaded before the `\documentclass`:

```
\RequirePackage{pgf}
\documentclass{sn-jnl}
```

The package `nicematrix` is not fully compatible with the packages and classes of LuaTeX-ja: the detection of the empty corners (cf. p. 10) may be wrong in some circumstances.

The package `nicematrix` is not fully compatible with the package `arydshln` (because this package redefines many internals of `array`). By any means, in the context of `nicematrix`, it's recommended to draw dashed rules with the tools provided by `nicematrix`, by creating a customized line style with `custom-line`: cf. p. 11.

⁵⁴The columns of type `V` are provided by `varwidth`: cf. p. 20.

⁵⁵See p. 21

⁵⁶In the documentation of `{amsmath}`, we can read: *The extra space of `\arraycolsep` that `array` adds on each side is a waste so we remove it [in `{matrix}`] (perhaps we should instead remove it from `array` in general, but that's a harder task).*

⁵⁷And not by inserting `@{}` on both sides of the preamble of the array. As a consequence, the length of the `\hline` is not modified and may appear too long, in particular when using square brackets.

⁵⁸See <https://tex.stackexchange.com/questions/528975/error-loading-tikz-in-ieeeaccess-class>

18 Examples

18.1 Utilisation of the key “tikz” of the command `\Block`

The key `tikz` of the command `\Block` is available only when Tikz is loaded.⁵⁹ For the following example, we also need the Tikz library `patterns`.

```
\usetikzlibrary{patterns}

\ttfamily \small
\begin{NiceTabular}{X[m]X[m]X[m]}[hvlines,cell-space-limits=3pt]
  \Block[tikz={pattern=grid,pattern color=lightgray}]{}
    {pattern = grid,\ \ pattern color = lightgray}
& \Block[tikz={pattern = north west lines,pattern color=blue}]{}
  {pattern = north west lines,\ \ pattern color = blue}
& \Block[tikz={outer color = red!50, inner color=white }]{2-1}
  {outer color = red!50,\ \ inner color = white} \ \
  \Block[tikz={pattern = sixpointed stars, pattern color = blue!15}]{}
  {pattern = sixpointed stars,\ \ pattern color = blue!15}
& \Block[tikz={left color = blue!50}]{}
  {left color = blue!50} \ \
\end{NiceTabular}
```

<pre>pattern = grid, pattern color = lightgray</pre>	<pre>pattern = north west lines, pattern color = blue</pre>	<pre>outer color = red!50, inner color = white</pre>
<pre>pattern = sixpointed stars, pattern color = blue!15</pre>	<pre>left color = blue!50</pre>	

18.2 Notes in the tabulars

The tools provided by `nicematrix` for the composition of the tabular notes have been presented in the section 12 p. 33.

Let’s consider that we wish to number the notes of a tabular with stars.⁶⁰

First, we write a command `\stars` similar the well-known commands `\arabic`, `\alph`, `\Alph`, etc. which produces a number of stars equal to its argument⁶¹.

```
\ExplSyntaxOn
\NewDocumentCommand \stars { m }
  { \prg_replicate:nn { \value { #1 } } { $ \star $ } }
\ExplSyntaxOff
```

Of course, we change the style of the labels with the key `notes/style`. However, it would be interesting to change also some parameters in the type of list used to compose the notes at the end of the tabular. First, we required a composition flush right for the labels with the setting `align=right`. Moreover, we want the labels to be composed on a width equal to the width of the widest label. The widest label is, of course, the label with the greatest number of stars. We know that number: it is equal to `\value{tabularnote}` (because `tabularnote` is the LaTeX counter used by `\tabularnote` and, therefore, at the end of the tabular, its value is equal to the total number of tabular notes). We use the key `widest*` of `enumitem` in order to require a width equal to that value: `widest*=\value{tabularnote}`.

⁵⁹By default, `nicematrix` only loads PGF, which is a sub-layer of Tikz.

⁶⁰Of course, it’s realistic only when there is very few notes in the tabular.

⁶¹In fact: the value of its argument.

```

\NiceMatrixOptions
{
  notes =
  {
    style = \stars{#1} ,
    enumitem-keys =
    {
      widest* = \value{tabularnote} ,
      align = right
    }
  }
}

\begin{NiceTabular}{\llr{}}
\toprule \RowStyle{\bfseries}
Last name & First name & Birth day \\
\midrule
Achard\tabularnote{Achard is an old family of the Poitou.}
& Jacques & 5 juin 1962 \\
Lefebvre\tabularnote{The name Lefebvre is an alteration of the name Lefebure.}
& Mathilde & 23 mai 1988 \\
Vanesse & Stephany & 30 octobre 1994 \\
Dupont & Chantal & 15 janvier 1998 \\
\bottomrule
\end{NiceTabular}

```

Last name	First name	Birth day
Achard*	Jacques	June 5, 2005
Lefebvre**	Mathilde	January 23, 1975
Vanesse	Stephany	October 30, 1994
Dupont	Chantal	January 15, 1998

*Achard is an old family of the Poitou.

**The name Lefebvre is an alteration of the name Lefebure.

18.3 Dotted lines

An example with the resultant of two polynoms:

```

\setlength{\extrarowheight}{1mm}
\[\begin{vNiceArray}{cccc:ccc}[columns-width=6mm]
a_0 & & & & b_0 & & & \\
a_1 & & \Ddots & & b_1 & & \Ddots & \\
\vdots & & \Ddots & & \vdots & & \Ddots & b_0 \\
a_p & & & a_0 & & & b_1 & \\
& & \Ddots & & a_1 & & b_q & & \Ddots \\
& & & \Ddots & & & & \Ddots & \\
& & & a_p & & & & & b_q
\end{vNiceArray}\]

```

$$\left| \begin{array}{ccc} a_0 & & \\ a_1 & \ddots & \\ \vdots & & \\ a_p & & \end{array} \right. \begin{array}{ccc} & a_0 & \\ & a_1 & \\ & \vdots & \\ & a_p & \end{array} \left| \begin{array}{ccc} b_0 & & \\ b_1 & \ddots & \\ \vdots & & \\ b_q & & \end{array} \right. \begin{array}{ccc} & b_0 & \\ & b_1 & \\ & \vdots & \\ & b_q & \end{array} \right|$$

An example for a linear system:

```

 $\begin{pmatrix} 1 & 1 & 1 & \cdots & 1 & 0 & \backslash \\ 0 & 1 & 0 & \cdots & 0 & & L_2 \text{ gets } L_2 - L_1 \\ 0 & 0 & 1 & \ddots & \vdots & & L_3 \text{ gets } L_3 - L_1 \\ & & & \ddots & \vdots & \vdots & \\ \vdots & & & \ddots & 0 & \backslash \\ 0 & & & \cdots & 0 & 1 & L_n \text{ gets } L_n - L_1 \end{pmatrix}$ 

```

$$\left(\begin{array}{cccccc|c} 1 & 1 & 1 & \cdots & 1 & 0 \\ 0 & 1 & 0 & \cdots & 0 & L_2 \leftarrow L_2 - L_1 \\ 0 & 0 & 1 & \ddots & \vdots & L_3 \leftarrow L_3 - L_1 \\ \vdots & & & \ddots & \vdots & \vdots \\ \vdots & & & & 0 & \vdots \\ 0 & \cdots & \cdots & 0 & 1 & L_n \leftarrow L_n - L_1 \end{array} \right)$$

18.4 Dotted lines which are no longer dotted

The option `line-style` controls the style of the lines drawn by `\Ldots`, `\Cdots`, etc. Thus, it's possible with these commands to draw lines which are no longer dotted.

```

\NiceMatrixOptions{code-for-first-row = \scriptstyle,code-for-first-col = \scriptstyle }
\setcounter{MaxMatrixCols}{12}
\newcommand{\blue}{\color{blue}}
\begin{pmatrix} 1 & \vdots & \vdots & \vdots \\ & \ddots & & \\ & & 1 & \\ & & & \ddots \\ & & & & 0 \\ 0 & \cdots & 0 & 1 \end{pmatrix} \begin{array}{l} 0 \\ L_2 \leftarrow L_2 - L_1 \\ L_3 \leftarrow L_3 - L_1 \\ \vdots \\ L_n \leftarrow L_n - L_1 \end{array}

```

$$\begin{pmatrix} 1 & & & \\ & \ddots & & \\ & & 1 & \\ & & & 1 \end{pmatrix} \begin{pmatrix} & & & \\ & & & \\ & & 1 & \\ & & & 1 \end{pmatrix} \begin{pmatrix} & & & \\ & & & \\ & & 1 & \\ & & & 1 \end{pmatrix} \begin{pmatrix} & & & \\ & & & \\ & & 1 & \\ & & & 1 \end{pmatrix}$$

In fact, it's even possible to draw solid lines with the commands `\Cdots`, `\Vdots`, etc.⁶²

```
\NiceMatrixOptions
  {nullify-dots,code-for-first-col = \color{blue},code-for-first-row=\color{blue}}
$\begin{pNiceMatrix}[first-row,first-col]
    & & \Ldots[line-style={solid,<->},shorten=0pt]^{n \text{ columns}} \\
    & 1 & 1 & 1 & \Ldots & 1 \\
    & 1 & 1 & 1 & & 1 \\
\Vdots[line-style={solid,<->}]_{n \text{ rows}} & 1 & 1 & 1 & & 1 \\
    & 1 & 1 & 1 & & 1 \\
    & 1 & 1 & 1 & \Ldots & 1 \\
\end{pNiceMatrix}$
```

$$\begin{pmatrix} 1 & 1 & 1 & \dots & 1 \\ 1 & 1 & 1 & & 1 \\ 1 & 1 & 1 & & 1 \\ 1 & 1 & 1 & & 1 \\ 1 & 1 & 1 & \dots & 1 \end{pmatrix}$$

18.5 Dashed rules

In the following example, we use the command `\Block` to draw dashed rules. For that example, Tikz should be loaded (by `\usepackage{tikz}`).

```
\begin{pNiceMatrix}
\Block[borders={bottom,right,tikz=dashed}]{2-2}{
1 & 2 & 0 & 0 & 0 & 0 \\
4 & 5 & 0 & 0 & 0 & 0 \\
0 & 0 & \Block[borders={bottom,top,right,left,tikz=dashed}]{2-2}{
7 & 1 & 0 & 0 \\
0 & 0 & -1 & 2 & 0 & 0 \\
0 & 0 & 0 & 0 & \Block[borders={left,top,tikz=dashed}]{2-2}{
3 & 4 \\
0 & 0 & 0 & 0 & 1 & 4
}
}
\end{pNiceMatrix}
```

⁶²In this document, the Tikz library `arrows.meta` has been loaded, which impacts the shape of the arrow tips.

$$\left(\begin{array}{cc|ccc} 1 & 2 & 0 & 0 & 0 & 0 \\ 4 & 5 & 0 & 0 & 0 & 0 \\ \hline 0 & 0 & 7 & 1 & 0 & 0 \\ 0 & 0 & -1 & 2 & 0 & 0 \\ \hline 0 & 0 & 0 & 0 & 3 & 4 \\ 0 & 0 & 0 & 0 & 1 & 4 \end{array}\right)$$

18.6 Stacks of matrices

We often need to compose mathematical matrices on top on each other (for example for the resolution of linear systems).

In order to have the columns aligned one above the other, it's possible to fix a width for all the columns. That's what is done in the following example with the environment `{NiceMatrixBlock}` and its option `auto-columns-width`.

```
\begin{NiceMatrixBlock}[auto-columns-width]
\NiceMatrixOptions
{
  light-syntax,
  last-col, code-for-last-col = \color{blue} \scriptstyle,
}
\setlength{\extrarowheight}{1mm}

$\begin{pNiceArray}{rrrr|r}
12 -8 7 5 3 {} ;
3 -18 12 1 4 ;
-3 -46 29 -2 -15 ;
9 10 -5 4 7
\end{pNiceArray}$

\smallskip
$\begin{pNiceArray}{rrrr|r}
12 -8 7 5 3 ;
0 64 -41 1 19 { L_2 \gets L_1-4L_2 } ;
0 -192 123 -3 -57 { L_3 \gets L_1+4L_3 } ;
0 -64 41 -1 -19 { L_4 \gets 3L_1-4L_4 } ;
\end{pNiceArray}$

\smallskip
$\begin{pNiceArray}{rrrr|r}
12 -8 7 5 3 ;
0 64 -41 1 19 ;
0 0 0 0 0 { L_3 \gets 3 L_2 + L_3 }
\end{pNiceArray}$

\smallskip
$\begin{pNiceArray}{rrrr|r}
12 -8 7 5 3 {} ;
0 64 -41 1 19 ;
\end{pNiceArray}$

\end{NiceMatrixBlock}
```

$$\left(\begin{array}{cccc|c} 12 & -8 & 7 & 5 & 3 \\ 3 & -18 & 12 & 1 & 4 \\ -3 & -46 & 29 & -2 & -15 \\ 9 & 10 & -5 & 4 & 7 \end{array}\right)$$

$$\begin{pmatrix} 12 & -8 & 7 & 5 & 3 \\ 0 & 64 & -41 & 1 & 19 \\ 0 & -192 & 123 & -3 & -57 \\ 0 & -64 & 41 & -1 & -19 \end{pmatrix} \begin{matrix} L_2 \leftarrow L_1 - 4L_2 \\ L_3 \leftarrow L_1 + 4L_3 \\ L_4 \leftarrow 3L_1 - 4L_4 \end{matrix}$$

$$\begin{pmatrix} 12 & -8 & 7 & 5 & 3 \\ 0 & 64 & -41 & 1 & 19 \\ 0 & 0 & 0 & 0 & 0 \end{pmatrix} L_3 \leftarrow 3L_2 + L_3$$

$$\begin{pmatrix} 12 & -8 & 7 & 5 & 3 \\ 0 & 64 & -41 & 1 & 19 \end{pmatrix}$$

However, one can see that the last matrix is not perfectly aligned with others. That's why, in LaTeX, the parenthesis have not exactly the same width (smaller parenthesis are a bit slimer).

In order to solve that problem, it's possible to require the delimiters to be composed with the maximal width, thanks to the boolean key `delimiters/max-width`.

```

\begin{NiceMatrixBlock}[auto-columns-width]
\NiceMatrixOptions
{
  delimiters/max-width,
  light-syntax,
  last-col, code-for-last-col = \color{blue}\scriptstyle,
}
\setlength{\extrarowheight}{1mm}

$\begin{pNiceArray}{rrrr|r}
12 -8 7 5 3 {} ;
3 -18 12 1 4 ;
-3 -46 29 -2 -15 ;
9 10 -5 4 7
\end{pNiceArray}$

...
\end{NiceMatrixBlock}

```

$$\begin{pmatrix} 12 & -8 & 7 & 5 & 3 \\ 3 & -18 & 12 & 1 & 4 \\ -3 & -46 & 29 & -2 & -15 \\ 9 & 10 & -5 & 4 & 7 \end{pmatrix}$$

$$\begin{pmatrix} 12 & -8 & 7 & 5 & 3 \\ 0 & 64 & -41 & 1 & 19 \\ 0 & -192 & 123 & -3 & -57 \\ 0 & -64 & 41 & -1 & -19 \end{pmatrix} \begin{matrix} L_2 \leftarrow L_1 - 4L_2 \\ L_3 \leftarrow L_1 + 4L_3 \\ L_4 \leftarrow 3L_1 - 4L_4 \end{matrix}$$

$$\begin{pmatrix} 12 & -8 & 7 & 5 & 3 \\ 0 & 64 & -41 & 1 & 19 \\ 0 & 0 & 0 & 0 & 0 \end{pmatrix} L_3 \leftarrow 3L_2 + L_3$$

$$\begin{pmatrix} 12 & -8 & 7 & 5 & 3 \\ 0 & 64 & -41 & 1 & 19 \end{pmatrix}$$

If you wish an alignment of the different matrices without the same width for all the columns, you can construct a unique array and place the parenthesis with commands `\SubMatrix` in the `\CodeAfter`. Of course, that array can't be broken by a page break.

```

\setlength{\extrarowheight}{1mm}
\[\begin{NiceMatrix}[ r, last-col=6, code-for-last-col = \scriptstyle \color{blue} ]
12 & -8 & 7 & 5 & 3 & \\
3 & -18 & 12 & 1 & 4 & \\
-3 & -46 & 29 & -2 & -15 & \\
9 & 10 & -5 & 4 & 7 & \\[1mm]
12 & -8 & 7 & 5 & 3 & \\
0 & 64 & -41 & 1 & 19 & L_2 \gets L_1-4L_2 \\
0 & -192 & 123 & -3 & -57 & L_3 \gets L_1+4L_3 \\
0 & -64 & 41 & -1 & -19 & L_4 \gets 3L_1-4L_4 \\[1mm]
12 & -8 & 7 & 5 & 3 & \\
0 & 64 & -41 & 1 & 19 & \\
0 & 0 & 0 & 0 & 0 & L_3 \gets 3L_2+L_3 \\[1mm]
12 & -8 & 7 & 5 & 3 & \\
0 & 64 & -41 & 1 & 19 & \\
\CodeAfter [sub-matrix/vlines=4]
\SubMatrix({1-1}{4-5})
\SubMatrix({5-1}{8-5})
\SubMatrix({9-1}{11-5})
\SubMatrix({12-1}{13-5})
\end{NiceMatrix}\]

```

$$\begin{pmatrix} 12 & -8 & 7 & 5 & 3 \\ 3 & -18 & 12 & 1 & 4 \\ -3 & -46 & 29 & -2 & -15 \\ 9 & 10 & -5 & 4 & 7 \end{pmatrix}$$

$$\begin{pmatrix} 12 & -8 & 7 & 5 & 3 \\ 0 & 64 & -41 & 1 & 19 \\ 0 & -192 & 123 & -3 & -57 \\ 0 & -64 & 41 & -1 & -19 \end{pmatrix}
\begin{array}{l} L_2 \leftarrow L_1 - 4L_2 \\ L_3 \leftarrow L_1 + 4L_3 \\ L_4 \leftarrow 3L_1 - 4L_4 \end{array}$$

$$\begin{pmatrix} 12 & -8 & 7 & 5 & 3 \\ 0 & 64 & -41 & 1 & 19 \\ 0 & 0 & 0 & 0 & 0 \end{pmatrix}
\begin{array}{l} L_3 \leftarrow 3L_2 + L_3 \end{array}$$

$$\begin{pmatrix} 12 & -8 & 7 & 5 & 3 \\ 0 & 64 & -41 & 1 & 19 \end{pmatrix}$$

In this tabular, the instructions `\SubMatrix` are executed after the composition of the tabular and, thus, the vertical rules are drawn without adding space between the columns.

In fact, it's possible, with the key `vlines-in-sub-matrix`, to choose a letter in the preamble of the array to specify vertical rules which will be drawn in the `\SubMatrix` only (by adding space between the columns).

```

\setlength{\extrarowheight}{1mm}
\[\begin{NiceArray}
[
vlines-in-sub-matrix=I,
last-col,
code-for-last-col = \scriptstyle \color{blue}
]
{rrrrIr}
12 & -8 & 7 & 5 & 3 & \\
3 & -18 & 12 & 1 & 4 & \\

```

```

-3 & -46 & 29 & -2 & -15 \\
 9 & 10 & & -5 & 4 & 7 \\[1mm]
12 & -8 & & 7 & 5 & 3 \\
0 & 64 & & -41 & 1 & 19 & L_2 \gets L_1-4L_2 \\
0 & & -192 & 123 & -3 & -57 & L_3 \gets L_1+4L_3 \\
0 & & -64 & 41 & -1 & -19 & L_4 \gets 3L_1-4L_4 \\
12 & -8 & & 7 & 5 & 3 \\
0 & 64 & & -41 & 1 & 19 \\
0 & & 0 & 0 & 0 & 0 & L_3 \gets 3L_2+L_3 \\
12 & -8 & & 7 & 5 & 3 \\
0 & 64 & & -41 & 1 & 19 \\
\CodeAfter
\SubMatrix({1-1}{4-5})
\SubMatrix({5-1}{8-5})
\SubMatrix({9-1}{11-5})
\SubMatrix({12-1}{13-5})
\end{NiceArray}\]

```

$$\begin{pmatrix} 12 & -8 & 7 & 5 & 3 \\ 3 & -18 & 12 & 1 & 4 \\ -3 & -46 & 29 & -2 & -15 \\ 9 & 10 & -5 & 4 & 7 \end{pmatrix}$$

$$\begin{pmatrix} 12 & -8 & 7 & 5 & 3 \\ 0 & 64 & -41 & 1 & 19 \\ 0 & -192 & 123 & -3 & -57 \\ 0 & -64 & 41 & -1 & -19 \end{pmatrix}
\begin{array}{l} L_2 \leftarrow L_1 - 4L_2 \\ L_3 \leftarrow L_1 + 4L_3 \\ L_4 \leftarrow 3L_1 - 4L_4 \end{array}$$

$$\begin{pmatrix} 12 & -8 & 7 & 5 & 3 \\ 0 & 64 & -41 & 1 & 19 \\ 0 & 0 & 0 & 0 & 0 \end{pmatrix}
\begin{array}{l} L_3 \leftarrow 3L_2 + L_3 \end{array}$$

$$\begin{pmatrix} 12 & -8 & 7 & 5 & 3 \\ 0 & 64 & -41 & 1 & 19 \end{pmatrix}$$

18.7 How to highlight cells of a matrix

In order to highlight a cell of a matrix, it's possible to “draw” that cell with the key `draw` of the command `\Block` (this is one of the uses of a mono-cell block⁶³).

```

$\begin{pNiceArray}{>{\strut}cccc}[margin,rules/color=blue]
\Block[draw]{a_{11}} & a_{12} & a_{13} & a_{14} \\
a_{21} & \Block[draw]{a_{22}} & a_{23} & a_{24} \\
a_{31} & a_{32} & \Block[draw]{a_{33}} & a_{34} \\
a_{41} & a_{42} & a_{43} & \Block[draw]{a_{44}} \\
\end{pNiceArray}$

```

$$\begin{pmatrix} a_{11} & a_{12} & a_{13} & a_{14} \\ a_{21} & a_{22} & a_{23} & a_{24} \\ a_{31} & a_{32} & a_{33} & a_{34} \\ a_{41} & a_{42} & a_{43} & a_{44} \end{pmatrix}$$

We should remark that the rules we have drawn are drawn *after* the construction of the array and thus, they don't spread the cells of the array. We recall that, on the other side, the commands `\hline` and

⁶³We recall that, if the first mandatory argument of the command `\Block` is left empty, that means that the block is a mono-cell block

`\Hline`, the specifier “|” and the options `hlines`, `vlines`, `hvlines` and `hvlines-except-borders` spread the cells.⁶⁴

It’s possible to color a row with `\rowcolor` in the `code-before` (or with `\rowcolor` in the first cell of the row if the key `colortbl-like` is used—even when `colortbl` is not loaded).

```
\begin{pNiceArray}{>{\strut}cccc}[margin, extra-margin=2pt,colortbl-like]
  \rowcolor{red!15}A_{11} & A_{12} & A_{13} & A_{14} \\
  A_{21} & \rowcolor{red!15}A_{22} & A_{23} & A_{24} \\
  A_{31} & A_{32} & \rowcolor{red!15}A_{33} & A_{34} \\
  A_{41} & A_{42} & A_{43} & \rowcolor{red!15}A_{44}
\end{pNiceArray}
```

$$\begin{pmatrix} A_{11} & A_{12} & A_{13} & A_{14} \\ A_{21} & A_{22} & A_{23} & A_{24} \\ A_{31} & A_{32} & A_{33} & A_{34} \\ A_{41} & A_{42} & A_{43} & A_{44} \end{pmatrix}$$

However, it’s not possible to do a fine tuning. That’s why we describe now a method to highlight a row of the matrix.

That example and the following ones require Tikz (by default, `nicematrix` only loads PGF, which is a sub-layer of Tikz) and the Tikz library `fit`. The following lines in the preamble of your document do the job:

```
\usepackage{tikz}
\usetikzlibrary{fit}
```

We create a rectangular Tikz node which encompasses the nodes of the second row by using the tools of the Tikz library `fit`. Those nodes are not available by default in the `\CodeBefore` (for efficiency). We have to require their creation with the key `create-cell-nodes` of the keyword `\CodeBefore`.

```
\tikzset{highlight/.style={rectangle,
                           fill=red!15,
                           rounded corners = 0.5 mm,
                           inner sep=1pt,
                           fit=#1}}
```

```
$\begin{bNiceMatrix}
\CodeBefore [create-cell-nodes]
  \tikz \node [highlight = (2-1) (2-3)] {} ;
\Body
0 & \Cdots & 0 \\
1 & \Cdots & 1 \\
0 & \Cdots & 0 \\
\end{bNiceMatrix}$
```

$$\begin{bmatrix} 0 & \cdots & 0 \\ 1 & \cdots & 1 \\ 0 & \cdots & 0 \end{bmatrix}$$

We consider now the following matrix. If we want to highlight each row of this matrix, we can use the previous technique three times.

⁶⁴For the command `\cline`, see the remark p. 8.

```

\[\begin{pNiceArray}{ccc}[last-col]
\CodeBefore [create-cell-nodes]
\begin{tikzpicture}
\node [highlight = (1-1) (1-3)] {} ;
\node [highlight = (2-1) (2-3)] {} ;
\node [highlight = (3-1) (3-3)] {} ;
\end{tikzpicture}
\Body
a & a + b & a + b + c & L_1 \\
a & a & a + b & L_2 \\
a & a & a & L_3
\end{pNiceArray}\]

```

$$\begin{pmatrix} a & a+b & a+b+c \\ a & a & a+b \\ a & a & a \end{pmatrix} \begin{matrix} L_1 \\ L_2 \\ L_3 \end{matrix}$$

The result may seem disappointing. We can improve it by using the “medium nodes” instead of the “normal nodes”.

```

\[\begin{pNiceArray}{ccc}[last-col,create-medium-nodes]
\CodeBefore [create-cell-nodes]
\begin{tikzpicture} [name suffix = -medium]
\node [highlight = (1-1) (1-3)] {} ;
\node [highlight = (2-1) (2-3)] {} ;
\node [highlight = (3-1) (3-3)] {} ;
\end{tikzpicture}
\Body
a & a + b & a + b + c & L_1 \\
a & a & a + b & L_2 \\
a & a & a & L_3
\end{pNiceArray}\]

```

$$\begin{pmatrix} a & a+b & a+b+c \\ a & a & a+b \\ a & a & a \end{pmatrix} \begin{matrix} L_1 \\ L_2 \\ L_3 \end{matrix}$$

18.8 Utilisation of \SubMatrix in the \CodeBefore

In the following example, we illustrate the mathematical product of two matrices.

The whole figure is an environment `{NiceArray}` and the three pairs of parenthesis have been added with `\SubMatrix` in the `\CodeBefore`.

$$\begin{matrix} & & C_j & \\ & & \begin{pmatrix} b_{11} & \cdots & b_{1j} & \cdots & b_{1n} \\ \vdots & & \vdots & & \vdots \\ b_{k1} & \cdots & b_{kj} & \cdots & b_{kn} \\ \vdots & & \vdots & & \vdots \\ b_{n1} & \cdots & b_{nj} & \cdots & b_{nn} \end{pmatrix} & \\ & & \vdots & \\ L_i & \begin{pmatrix} a_{11} & \cdots & a_{1n} \\ \vdots & & \vdots \\ a_{i1} & \cdots & a_{ik} & \cdots & a_{in} \\ \vdots & & \vdots & & \vdots \\ a_{n1} & \cdots & \cdots & \cdots & a_{nn} \end{pmatrix} & \begin{pmatrix} \vdots \\ \vdots \\ \cdots c_{ij} \\ \vdots \end{pmatrix} \end{matrix}$$

```

\tikzset{highlight/.style={rectangle,
    fill=red!15,
    rounded corners = 0.5 mm,
    inner sep=1pt,
    fit=#1}}

\[\begin{NiceArray}{*{6}{c}@{\hspace{6mm}}*{5}{c}}[nullify-dots]
\CodeBefore [create-cell-nodes]
    \SubMatrix({2-7}{6-last})
    \SubMatrix({7-2}{last-6})
    \SubMatrix({7-7}{last-last})
    \begin{tikzpicture}
        \node [highlight = (9-2) (9-6)] { } ;
        \node [highlight = (2-9) (6-9)] { } ;
    \end{tikzpicture}
\Body
    & & & & & & & \color{blue}\scriptstyle C_j \\
    & & & & & & b_{11} & \Cdots & b_{1j} & \Cdots & b_{1n} \\
    & & & & & & \Vdots & & \Vdots & & \Vdots \\
    & & & & & & & & b_{kj} \\
    & & & & & & & & \Vdots \\
    & & & & & & b_{n1} & \Cdots & b_{nj} & \Cdots & b_{nn} \\
    & a_{11} & \Cdots & & & a_{1n} \\
    & \Vdots & & & & \Vdots & & & \Vdots \\
\color{blue}\scriptstyle L_i
    & a_{i1} & \Cdots & a_{ik} & \Cdots & a_{in} & \Cdots & & c_{ij} \\
    & \Vdots & & & & \Vdots \\
    & a_{n1} & \Cdots & & & a_{nn} \\
\CodeAfter
\tikz \draw [gray,shorten > = 1mm, shorten < = 1mm] (9-4.north) to [bend left] (4-9.west) ;
\end{NiceArray}\]

```

19 Implementation

By default, the package `nicematrix` doesn't patch any existing code.

However, when the option `renew-dots` is used, the commands `\cdots`, `\ldots`, `\dots`, `\vdots`, `\ddots` and `\iddots` are redefined in the environments provided by `nicematrix` as explained previously. In the same way, if the option `renew-matrix` is used, the environment `{matrix}` of `amsmath` is redefined.

On the other hand, the environment `{array}` is never redefined.

Of course, the package `nicematrix` uses the features of the package `array`. It tries to be independent of its implementation. Unfortunately, it was not possible to be strictly independent. For example, the package `nicematrix` relies upon the fact that the package `{array}` uses `\ialign` to begin the `\halign`.

Declaration of the package and packages loaded

The prefix `nicematrix` has been registered for this package.

See: <http://mirrors.ctan.org/macros/latex/contrib/l3kernel/l3prefixes.pdf>

<@@=nicematrix>

First, we load `pgfcore` and the module `shapes`. We do so because it's not possible to use `\usepgfmodule` in `\ExplSyntaxOn`.

```

1 \RequirePackage{pgfcore}
2 \usepgfmodule{shapes}

```

We give the traditional declaration of a package written with the L3 programming layer.

```

3 \RequirePackage{l3keys2e}
4 \ProvidesExplPackage
5   {nicematrix}
6   {\myfiledate}
7   {\myfileversion}
8   {Enhanced arrays with the help of PGF/TikZ}

```

The command for the treatment of the options of `\usepackage` is at the end of this package for technical reasons.

We load some packages.

```

9 \RequirePackage { array }
10 \RequirePackage { amsmath }

11 \cs_new_protected:Npn \@@_error:n { \msg_error:nn { nicematrix } }
12 \cs_new_protected:Npn \@@_warning:n { \msg_warning:nn { nicematrix } }
13 \cs_new_protected:Npn \@@_error:nn { \msg_error:nnn { nicematrix } }
14 \cs_generate_variant:Nn \@@_error:nn { n x }
15 \cs_new_protected:Npn \@@_error:nnn { \msg_error:nnnn { nicematrix } }
16 \cs_new_protected:Npn \@@_fatal:n { \msg_fatal:nn { nicematrix } }
17 \cs_new_protected:Npn \@@_fatal:nn { \msg_fatal:nnn { nicematrix } }
18 \cs_new_protected:Npn \@@_msg_new:nn { \msg_new:nnn { nicematrix } }

```

With Overleaf, a document is compiled in non-stop mode. When there is an error, there is no way to the user to use the key H in order to have more information. That's why we decide to put that piece of information (for the messages with such information) in the main part of the message when the key `messages-for-Overleaf` is used (at load-time).

```

19 \cs_new_protected:Npn \@@_msg_new:nnn #1 #2 #3
20   {
21     \bool_if:NTF \c_@@_messages_for_Overleaf_bool
22       { \msg_new:nnn { nicematrix } { #1 } { #2 \\\ #3 } }
23       { \msg_new:nnnn { nicematrix } { #1 } { #2 } { #3 } }
24   }

```

We also create a command which will generate usually an error but only a warning on Overleaf. The argument is given by curriification.

```

25 \cs_new_protected:Npn \@@_error_or_warning:n
26   { \bool_if:NTF \c_@@_messages_for_Overleaf_bool \@@_warning:n \@@_error:n }

```

We try to detect whether the compilation is done on Overleaf. We use `\c_sys_jobname_str` because, with Overleaf, the value of `\c_sys_jobname_str` is always “output”.

```

27 \bool_set:Nn \c_@@_messages_for_Overleaf_bool
28   {
29     \str_if_eq_p:Vn \c_sys_jobname_str { _region_ } % for Emacs
30     || \str_if_eq_p:Vn \c_sys_jobname_str { output } % for Overleaf
31   }

32 \cs_new_protected:Npn \@@_msg_redirect_name:nn
33   { \msg_redirect_name:nnn { nicematrix } }
34 \cs_new_protected:Npn \@@_gredirect_none:n #1
35   {
36     \group_begin:
37     \globaldefs = 1
38     \@@_msg_redirect_name:nn { #1 } { none }
39     \group_end:
40   }
41 \cs_new_protected:Npn \@@_err_gredirect_none:n #1
42   {
43     \@@_error:n { #1 }

```

```

44 \@@_gredirect_none:n { #1 }
45 }
46 \cs_new_protected:Npn \@@_warning_gredirect_none:n #1
47 {
48 \@@_warning:n { #1 }
49 \@@_gredirect_none:n { #1 }
50 }

```

Security test

Within the package `nicematrix`, we will have to test whether a cell of a `{NiceTabular}` is empty. For the cells of the columns of type `p`, `b`, `m`, `X` and `V`, we will test whether the cell is syntactically empty (that is to say that there is only spaces between the ampersands `&`). That test will be done with the command `\@@_test_if_empty:` by testing if the two first tokens in the cells are (during the TeX process) are `\ignorespaces` and `\unskip`.

However, if, one day, there is a changement in the implementation of `array`, maybe that this test will be broken (and `nicematrix` also).

That's why, by security, we will take a test in a small `{tabular}` composed in the box `\l_tmpa_box` used as sandbox.

```

51 \@@_msg_new:nn { Internal~error }
52 {
53 Potential~problem~when~using~nicematrix.\\
54 The~package~nicematrix~have~detected~a~modification~of~the~
55 standard~environment~{array}~(of~the~package~array).~Maybe~you~will~encounter~
56 some~slight~problems~when~using~nicematrix.~If~you~don't~want~to~see~
57 this~message~again,~load~nicematrix~with:~\token_to_str:N
58 \usepackage[no-test-for-array]{nicematrix}.
59 }

60 \@@_msg_new:nn { mdwtab~loaded }
61 {
62 The~packages~'mdwtab'~and~'nicematrix'~are~incompatible.~
63 This~error~is~fatal.
64 }

65 \cs_new_protected:Npn \@@_security_test:n #1
66 {
67 \peek_meaning:NTF \ignorespaces
68 { \@@_security_test_i:w }
69 { \@@_error:n { Internal~error } }
70 #1
71 }

72 \cs_new_protected:Npn \@@_security_test_i:w \ignorespaces #1
73 {
74 \peek_meaning:NF \unskip { \@@_error:n { Internal~error } }
75 #1
76 }

```

Here, the box `\l_tmpa_box` will be used as sandbox to take our security test.

```

77 \hook_gput_code:nnn { begindocument } { . }
78 {
79 \@ifpackageloaded { mdwtab }
80 { \@@_fatal:n { mdwtab~loaded } }
81 {
82 \@ifpackageloaded { fontspec }
83 { }

```

```

84     {
85         \bool_if:NF \c_@@_no_test_for_array_bool
86         {
87             \group_begin:
88             \hbox_set:Nn \l_tmpa_box
89             {
90                 \begin { tabular } { c > { \@@_security_test:n } c c }
91                 text & & text
92                 \end { tabular }
93             }
94             \group_end:
95         }
96     }
97 }
98 }

```

Technical definitions

```

99 \tl_new:N \l_@@_argspec_tl
100 \cs_generate_variant:Nn \seq_set_split:Nnn { N V n }
101 \cs_generate_variant:Nn \keys_define:nn { n x }
102 \cs_generate_variant:Nn \str_lowercase:n { V }

103 \hook_gput_code:nnn { begindocument } { . }
104 {
105     \@ifpackageloaded { varwidth }
106     { \bool_const:Nn \c_@@_varwidth_loaded_bool { \c_true_bool } }
107     { \bool_const:Nn \c_@@_varwidth_loaded_bool { \c_false_bool } }
108     \@ifpackageloaded { booktabs }
109     { \bool_const:Nn \c_@@_booktabs_loaded_bool { \c_true_bool } }
110     { \bool_const:Nn \c_@@_booktabs_loaded_bool { \c_false_bool } }
111     \@ifpackageloaded { enumitem }
112     { \bool_const:Nn \c_@@_enumitem_loaded_bool { \c_true_bool } }
113     { \bool_const:Nn \c_@@_enumitem_loaded_bool { \c_false_bool } }
114     \@ifpackageloaded { tabularx }
115     { \bool_const:Nn \c_@@_tabularx_loaded_bool { \c_true_bool } }
116     { \bool_const:Nn \c_@@_tabularx_loaded_bool { \c_false_bool } }
117     \@ifpackageloaded { floatrow }
118     { \bool_const:Nn \c_@@_floatrow_loaded_bool { \c_true_bool } }
119     { \bool_const:Nn \c_@@_floatrow_loaded_bool { \c_false_bool } }
120     \@ifpackageloaded { tikz }
121     {

```

In some constructions, we will have to use a `{pgfpicture}` which *must* be replaced by a `{tikzpicture}` if Tikz is loaded. However, this switch between `{pgfpicture}` and `{tikzpicture}` can't be done dynamically with a conditional because, when the Tikz library `external` is loaded by the user, the pair `\tikzpicture-\endtikzpicture` (or `\begin{tikzpicture}-\end{tikzpicture}`) must be statically “visible” (even when externalization is not activated).

That's why we create `\c_@@_pgfortikzpicture_tl` and `\c_@@_endpgfortikzpicture_tl` which will be used to construct in a `\AtBeginDocument` the correct version of some commands. The tokens `\exp_not:N` are mandatory.

```

122     \bool_const:Nn \c_@@_tikz_loaded_bool \c_true_bool
123     \tl_const:Nn \c_@@_pgfortikzpicture_tl { \exp_not:N \tikzpicture }
124     \tl_const:Nn \c_@@_endpgfortikzpicture_tl { \exp_not:N \endtikzpicture }
125 }
126 {
127     \bool_const:Nn \c_@@_tikz_loaded_bool \c_false_bool
128     \tl_const:Nn \c_@@_pgfortikzpicture_tl { \exp_not:N \pgfpicture }
129     \tl_const:Nn \c_@@_endpgfortikzpicture_tl { \exp_not:N \endpgfpicture }
130 }
131 }

```

We test whether the current class is `revtex4-1` (deprecated) or `revtex4-2` because these classes redefines `\array` (of `array`) in a way incompatible with our programming. At the date January 2022, the current version `revtex4-2` is 4.2e (compatible with `booktabs`).

```

132 \@ifclassloaded { revtex4-1 }
133   { \bool_const:Nn \c_@@_revtex_bool \c_true_bool }
134   {
135     \@ifclassloaded { revtex4-2 }
136     { \bool_const:Nn \c_@@_revtex_bool \c_true_bool }
137     {

```

Maybe one of the previous classes will be loaded inside another class... We try to detect that situation.

```

138     \cs_if_exist:NT \rvtx@ifformat@geq
139     { \bool_const:Nn \c_@@_revtex_bool \c_true_bool }
140     { \bool_const:Nn \c_@@_revtex_bool \c_false_bool }
141   }
142 }

```

```

143 \cs_generate_variant:Nn \tl_if_single_token_p:n { V }

```

The following regex will be used to modify the preamble of the array when the key `colortbl-like` is used.

```

144 \regex_const:Nn \c_@@_columncolor_regex { \c { columncolor } }

```

If the final user uses `nicematrix`, PGF/Tikz will write instruction `\pgfsyspdfmark` in the `aux` file. If he changes its mind and no longer loads `nicematrix`, an error may occur at the next compilation because of remanent instructions `\pgfsyspdfmark` in the `aux` file. With the following code, we try to avoid that situation.

```

145 \cs_new_protected:Npn \@@_provide_pgfsyspdfmark:
146   {
147     \iow_now:Nn \@mainaux
148     {
149       \ExplSyntaxOn
150       \cs_if_free:NT \pgfsyspdfmark
151       { \cs_set_eq:NN \pgfsyspdfmark \@gobblethree }
152       \ExplSyntaxOff
153     }
154     \cs_gset_eq:NN \@@_provide_pgfsyspdfmark: \prg_do_nothing:
155   }

```

We define a command `\iddots` similar to `\ddots` (`\ddots`) but with dots going forward (`\iddots`). We use `\ProvideDocumentCommand` and so, if the command `\iddots` has already been defined (for example by the package `mathdots`), we don't define it again.

```

156 \ProvideDocumentCommand \iddots { }
157   {
158     \mathinner
159     {
160       \tex_mkern:D 1 mu
161       \box_move_up:nn { 1 pt } { \hbox:n { . } }
162       \tex_mkern:D 2 mu
163       \box_move_up:nn { 4 pt } { \hbox:n { . } }
164       \tex_mkern:D 2 mu
165       \box_move_up:nn { 7 pt }
166       { \vbox:n { \kern 7 pt \hbox:n { . } } }
167       \tex_mkern:D 1 mu
168     }
169   }

```

This definition is a variant of the standard definition of `\ddots`.

In the `aux` file, we will have the references of the PGF/Tikz nodes created by `nicematrix`. However, when `booktabs` is used, some nodes (more precisely, some `row` nodes) will be defined twice because

their position will be modified. In order to avoid an error message in this case, we will redefine `\pgfutil@check@rerun` in the aux file.

```

170 \hook_gput_code:nnn { begindocument } { . }
171 {
172   \@ifpackageloaded { booktabs }
173     { \iow_now:Nn \@mainaux \nicematrix@redefine@check@rerun }
174     { }
175 }
176 \cs_set_protected:Npn \nicematrix@redefine@check@rerun
177 {
178   \cs_set_eq:NN \@_old_pgfutil@check@rerun \pgfutil@check@rerun

```

The new version of `\pgfutil@check@rerun` will not check the PGF nodes whose names start with `nm-` (which is the prefix for the nodes created by `nicematrix`).

```

179   \cs_set_protected:Npn \pgfutil@check@rerun ##1 ##2
180   {
181     \str_if_eq:eeF { nm- } { \tl_range:nnn { ##1 } 1 3 }
182     { \@_old_pgfutil@check@rerun { ##1 } { ##2 } }
183   }
184 }

```

We have to know whether `colortbl` is loaded in particular for the redefinition of `\everycr`.

```

185 \bool_new:N \l_@@_colortbl_loaded_bool
186 \hook_gput_code:nnn { begindocument } { . }
187 {
188   \@ifpackageloaded { colortbl }
189     { \bool_set_true:N \l_@@_colortbl_loaded_bool }
190     {

```

The command `\CT@arc@` is a command of `colortbl` which sets the color of the rules in the array. We will use it to store the instruction of color for the rules even if `colortbl` is not loaded.

```

191   \cs_set_protected:Npn \CT@arc@ { }
192   \cs_set:Npn \arrayrulecolor #1 # { \CT@arc@ { #1 } }
193   \cs_set:Npn \CT@arc@ #1 #2
194   {
195     \dim_compare:nNnT \baselineskip = \c_zero_dim \noalign
196       { \cs_gset:Npn \CT@arc@ { \color #1 { #2 } } }
197   }

```

Idem for `\CT@drs@`.

```

198   \cs_set:Npn \doublerulesepcolor #1 # { \CT@drs@ { #1 } }
199   \cs_set:Npn \CT@drs@ #1 #2
200   {
201     \dim_compare:nNnT \baselineskip = \c_zero_dim \noalign
202       { \cs_gset:Npn \CT@drsc@ { \color #1 { #2 } } }
203   }
204   \cs_set:Npn \hline
205   {
206     \noalign { \ifnum 0 = ` } \fi
207     \cs_set_eq:NN \hskip \vskip
208     \cs_set_eq:NN \vrule \hrule
209     \cs_set_eq:NN \@width \@height
210     { \CT@arc@ \vline }
211     \futurelet \reserved@a
212     \@xhline
213   }
214 }
215 }

```

We have to redefine `\cline` for several reasons. The command `\@@_cline` will be linked to `\cline` in the beginning of `{NiceArrayWithDelims}`. The following commands must *not* be protected.

```

216 \cs_set:Npn \@@_standard_cline #1 { \@@_standard_cline:w #1 \q_stop }
217 \cs_set:Npn \@@_standard_cline:w #1-#2 \q_stop
218 {

```



```

219 \int_compare:nNnT \l_@@_first_col_int = 0 { \omit & }
220 \int_compare:nNnT { #1 } > 1 { \multispan { \int_eval:n { #1 - 1 } } & }
221 \multispan { \int_eval:n { #2 - #1 + 1 } }
222 {
223   \CT@arc@
224   \leaders \hrule \@height \arrayrulewidth \hfill

```

The following `\skip_horizontal:N \c_zero_dim` is to prevent a potential `\unskip` to delete the `\leaders`⁶⁵

```

225   \skip_horizontal:N \c_zero_dim
226 }

```

Our `\everycr` has been modified. In particular, the creation of the `row` node is in the `\everycr` (maybe we should put it with the incrementation of `\c@iRow`). Since the following `\cr` correspond to a “false row”, we have to nullify `\everycr`.

```

227 \everycr { }
228 \cr
229 \noalign { \skip_vertical:N -\arrayrulewidth }
230 }

```

The following version of `\cline` spreads the array of a quantity equal to `\arrayrulewidth` as does `\hline`. It will be loaded excepted if the key `standard-cline` has been used.

```

231 \cs_set:Npn \@@_cline

```

We have to act in a fully expandable way since there may be `\noalign` (in the `\multispan`) to detect. That’s why we use `\@@_cline_i:en`.

```

232 { \@@_cline_i:en \l_@@_first_col_int }

```

The command `\cline_i:nn` has two arguments. The first is the number of the current column (it *must* be used in that column). The second is a standard argument of `\cline` of the form *i-j* or the form *i*.

```

233 \cs_set:Npn \@@_cline_i:nn #1 #2 { \@@_cline_i:w #1|#2- \q_stop }
234 \cs_set:Npn \@@_cline_i:w #1|#2-#3 \q_stop
235 {
236   \tl_if_empty:nTF { #3 }
237   { \@@_cline_iii:w #1|#2-#2 \q_stop }
238   { \@@_cline_ii:w #1|#2-#3 \q_stop }
239 }
240 \cs_set:Npn \@@_cline_ii:w #1|#2-#3-\q_stop
241 { \@@_cline_iii:w #1|#2-#3 \q_stop }
242 \cs_set:Npn \@@_cline_iii:w #1|#2-#3 \q_stop
243 {

```

Now, `#1` is the number of the current column and we have to draw a line from the column `#2` to the column `#3` (both included).

```

244 \int_compare:nNnT { #1 } < { #2 }
245 { \multispan { \int_eval:n { #2 - #1 } } & }
246 \multispan { \int_eval:n { #3 - #2 + 1 } }
247 {
248   \CT@arc@
249   \leaders \hrule \@height \arrayrulewidth \hfill
250   \skip_horizontal:N \c_zero_dim
251 }

```

You look whether there is another `\cline` to draw (the final user may put several `\cline`).

```

252 \peek_meaning_remove_ignore_spaces:NTF \cline
253 { & \@@_cline_i:en { \int_eval:n { #3 + 1 } } }
254 { \everycr { } \cr }
255 }
256 \cs_generate_variant:Nn \@@_cline_i:nn { e n }

```

The following command is a small shortcut.

```

257 \cs_new:Npn \@@_math_toggle_token:

```

⁶⁵See question 99041 on TeX StackExchange.

```

258 { \bool_if:NF \l_@@_NiceTabular_bool \c_math_toggle_token }

259 \cs_new_protected:Npn \@@_set_CT@arc@:n #1
260 {
261   \tl_if_blank:NF { #1 }
262   {
263     \tl_if_head_eq_meaning:nNTF { #1 } [
264       { \cs_set:Npn \CT@arc@ { \color #1 } }
265       { \cs_set:Npn \CT@arc@ { \color { #1 } } }
266     ]
267   }
268 \cs_generate_variant:Nn \@@_set_CT@arc@:n { V }

269 \cs_new_protected:Npn \@@_set_CT@drsc@:n #1
270 {
271   \tl_if_head_eq_meaning:nNTF { #1 } [
272     { \cs_set:Npn \CT@drsc@ { \color #1 } }
273     { \cs_set:Npn \CT@drsc@ { \color { #1 } } }
274   ]
275 \cs_generate_variant:Nn \@@_set_CT@drsc@:n { V }

```

The following command must *not* be protected since it will be used to write instructions in the (internal) `\CodeBefore`.

```

276 \cs_new:Npn \@@_exp_color_arg:Nn #1 #2
277 {
278   \tl_if_head_eq_meaning:nNTF { #2 } [
279     { #1 #2 }
280     { #1 { #2 } }
281   ]
282 \cs_generate_variant:Nn \@@_exp_color_arg:Nn { N V }

```

The following command must be protected because of its use of the command `\color`.

```

283 \cs_new_protected:Npn \@@_color:n #1
284 {
285   \tl_if_blank:NF { #1 }
286   { \@@_exp_color_arg:Nn \color { #1 } }
287 }
288 \cs_generate_variant:Nn \@@_color:n { V }

289 \cs_set_eq:NN \@@_old_pgfpointanchor \pgfpointanchor

```

The column S of siunitx

We want to know whether the package `siunitx` is loaded and, if it is loaded, we redefine the S columns of `siunitx`.

```

290 \bool_new:N \l_@@_siunitx_loaded_bool
291 \hook_gput_code:nnn { begindocument } { . }
292 {
293   \ifpackageloaded { siunitx }
294   { \bool_set_true:N \l_@@_siunitx_loaded_bool }
295   { }
296 }

```

The command `\@@_renew_NC@rewrite@S:` will be used in each environment of `nicematrix` in order to “rewrite” the S column in each environment.

```

297 \hook_gput_code:nnn { begindocument } { . }
298 {
299   \bool_if:nTF { ! \l_@@_siunitx_loaded_bool }
300   { \cs_set_eq:NN \@@_renew_NC@rewrite@S: \prg_do_nothing: }
301   {
302     \cs_new_protected:Npn \@@_renew_NC@rewrite@S:
303     {

```

```

304         \renewcommand*{\NC@rewrite@S}[1] []
305         {
\@temptokena is a toks (not supported by the L3 programming layer).
306         \tl_if_empty:nTF { ##1 }
307         {
308             \@temptokena \exp_after:wN
309             { \tex_the:D \@temptokena \@@_S: }
310         }
311         {
312             \@temptokena \exp_after:wN
313             { \tex_the:D \@temptokena \@@_S: [ ##1 ] }
314         }
315         \NC@find
316     }
317 }
318 }
319 }

320 \cs_new_protected:Npn \@@_rescan_for_spanish:N #1
321 {
322     \tl_set_rescan:Nno
323     #1
324     {
325         \char_set_catcode_other:N >
326         \char_set_catcode_other:N <
327     }
328     #1
329 }

```

Parameters

The following counter will count the environments `{NiceArray}`. The value of this counter will be used to prefix the names of the Tikz nodes created in the array.

```
330 \int_new:N \g_@@_env_int
```

The following command is only a syntactic shortcut. It must *not* be protected (it will be used in names of PGF nodes).

```
331 \cs_new:Npn \@@_env: { nm - \int_use:N \g_@@_env_int }
```

The command `\NiceMatrixLastEnv` is not used by the package `nicematrix`. It's only a facility given to the final user. It gives the number of the last environment (in fact the number of the current environment but it's meant to be used after the environment in order to refer to that environment — and its nodes — without having to give it a name). This command *must* be expandable since it will be used in pgf nodes.

```

332 \NewExpandableDocumentCommand \NiceMatrixLastEnv { }
333 { \int_use:N \g_@@_env_int }

```

The following command is only a syntactic shortcut. The `q` in `qpoint` means *quick*.

```

334 \cs_new_protected:Npn \@@_qpoint:n #1
335 { \pgfpointanchor { \@@_env: - #1 } { center } }

```

The following counter will count the environments `{NiceMatrixBlock}`.

```
336 \int_new:N \g_@@_NiceMatrixBlock_int
```

If, in a tabular, there is a tabular note in a caption that must be composed *above* the tabular, we will store in `\l_@@_note_in_caption_int` the number of notes in that caption. It will be stored in the `aux` file.

```
337 \int_new:N \l_@@_note_in_caption_int
```

The dimension `\l_@@_columns_width_dim` will be used when the options specify that all the columns must have the same width (but, if the key `columns-width` is used with the special value `auto`, the boolean `\l_@@_auto_columns_width_bool` also will be raised).

```
338 \dim_new:N \l_@@_columns_width_dim
```

The dimension `\l_@@_col_width_dim` will be available in each cell which belongs to a column of fixed width: `w{...}{...}`, `W{...}{...}`, `p{}`, `m{}`, `b{}` but also `X` (when the actual width of that column is known, that is to say after the first compilation). It's the width of that column. It will be used by some commands `\Block`. A non positive value means that the column has no fixed width (it's a column of type `c`, `r`, `l`, etc.).

```
339 \dim_new:N \l_@@_col_width_dim
340 \dim_set:Nn \l_@@_col_width_dim { -1 cm }
```

The following counters will be used to count the numbers of rows and columns of the array.

```
341 \int_new:N \g_@@_row_total_int
342 \int_new:N \g_@@_col_total_int
```

The following parameter will be used by `\@@_create_row_node`: to avoid to create the same row-node twice (at the end of the array).

```
343 \int_new:N \g_@@_last_row_node_int
```

The following counter corresponds to the key `nb-rows` of the command `\RowStyle`.

```
344 \int_new:N \l_@@_key_nb_rows_int
```

The following token list will contain the type of horizontal alignment of the current cell as provided by the corresponding column. The possible values are `r`, `l`, `c`. For example, a column `p[1]{3cm}` will provide the value `l` for all the cells of the column.

```
345 \str_new:N \l_@@_hpos_cell_str
346 \str_set:Nn \l_@@_hpos_cell_str { c }
```

When there is a mono-column block (created by the command `\Block`), we want to take into account the width of that block for the width of the column. That's why we compute the width of that block in the `\g_@@_blocks_wd_dim` and, after the construction of the box `\l_@@_cell_box`, we change the width of that box to take into account the length `\g_@@_blocks_wd_dim`.

```
347 \dim_new:N \g_@@_blocks_wd_dim
```

Idem for the mono-row blocks.

```
348 \dim_new:N \g_@@_blocks_ht_dim
349 \dim_new:N \g_@@_blocks_dp_dim
```

The following dimension correspond to the key `width` (which may be fixed in `\NiceMatrixOptions` but also in an environment `{NiceTabular}`).

```
350 \dim_new:N \l_@@_width_dim
```

The sequence `\g_@@_names_seq` will be the list of all the names of environments used (via the option `name`) in the document: two environments must not have the same name. However, it's possible to use the option `allow-duplicate-names`.

```
351 \seq_new:N \g_@@_names_seq
```

We want to know whether we are in an environment of `nicematrix` because we will raise an error if the user tries to use nested environments.

```
352 \bool_new:N \l_@@_in_env_bool
```

The following key corresponds to the key `notes/detect_duplicates`.

```
353 \bool_new:N \l_@@_notes_detect_duplicates_bool
354 \bool_set_true:N \l_@@_notes_detect_duplicates_bool
```

If the user uses `{NiceArray}` or `{NiceTabular}` the flag `\g_@@_NiceArray_bool` will be raised.

```
355 \bool_new:N \g_@@_NiceArray_bool
```

In fact, if there is delimiters in the preamble of `{NiceArray}` (eg: `[cccc]`), this boolean will be set to false.

If the user uses `{NiceTabular}`, `{NiceTabular*}` or `{NiceTabularX}`, we will raise the following flag.

```
356 \bool_new:N \l_@@_NiceTabular_bool
```

If the user uses `{NiceTabular*}`, the width of the tabular (in the first argument of the environment `{NiceTabular*}`) will be stored in the following dimension.

```
357 \dim_new:N \l_@@_tabular_width_dim
```

The following dimension will be used for the total width of composite rules (*total* means that the spaces on both sides are included).

```
358 \dim_new:N \l_@@_rule_width_dim
```

If the user uses an environment without preamble, we will raise the following flag.

```
359 \bool_new:N \l_@@_Matrix_bool
```

The following boolean will be raised when the command `\rotate` is used.

```
360 \bool_new:N \g_@@_rotate_bool
```

In a cell, it will be possible to know whether we are in a cell of a column of type `X` thanks to that flag.

```
361 \bool_new:N \l_@@_X_column_bool
```

```
362 \bool_new:N \g_@@_caption_finished_bool
```

We will write in `\g_@@_aux_tl` all the instructions that we have to write on the `aux` file for the current environment. The content of that token list will be written on the `aux` file at the end of the environment (in an instruction `\tl_gset:cn { c_@@_ \int_use:N \g_@@_env_int _ tl }`).

```
363 \tl_new:N \g_@@_aux_tl
```

The following parameter corresponds to the key `columns-type` of the environments `{NiceMatrix}`, `{pNiceMatrix}`, etc. and also the key `matrix / columns-type` of `\NiceMatrixOptions`. However, it does *not* contain the value provided by the final user. Indeed, a transformation is done in order to have a preamble (for the package `array`) which is `nicematrix`-aware. That transformation is done with the command `\@@_set_preamble:Nn`.

```
364 \tl_new:N \l_@@_columns_type_tl
365 \hook_gput_code:nnn { begindocument } { . }
366 { \@@_set_preamble:Nn \l_@@_columns_type_tl { c } }
```

```
367 \cs_new_protected:Npn \@@_test_if_math_mode:
368 {
369   \if_mode_math: \else:
370     \@@_fatal:n { Outside-math-mode }
371   \fi:
372 }
```

The letter used for the `vlines` which will be drawn only in the sub-matrices. `vlism` stands for *vertical lines in sub-matrices*.

```
373 \tl_new:N \l_@@_letter_vlism_tl
```

The list of the columns where vertical lines in sub-matrices (`vlism`) must be drawn. Of course, the actual value of this sequence will be known after the analyse of the preamble of the array.

```
374 \seq_new:N \g_@@_cols_vlism_seq
```

The following colors will be used to memorize the color of the potential “first col” and the potential “first row”.

```
375 \colorlet { nicematrix-last-col } { . }
376 \colorlet { nicematrix-last-row } { . }
```

The following string is the name of the current environment or the current command of `nicematrix` (despite its name which contains `env`).

```
377 \str_new:N \g_@@_name_env_str
```

The following string will contain the word *command* or *environment* whether we are in a command of `nicematrix` or in an environment of `nicematrix`. The default value is *environment*.

```
378 \tl_new:N \g_@@_com_or_env_str
379 \tl_gset:Nn \g_@@_com_or_env_str { environment }
```

The following command will be able to reconstruct the full name of the current command or environment (despite its name which contains `env`). This command must *not* be protected since it will be used in error messages and we have to use `\str_if_eq:VnTF` and not `\tl_if_eq:NnTF` because we need to be fully expandable).

```
380 \cs_new:Npn \@@_full_name_env:
381 {
382   \str_if_eq:VnTF \g_@@_com_or_env_str { command }
383   { command \space \c_backslash_str \g_@@_name_env_str }
384   { environment \space \{ \g_@@_name_env_str \} }
385 }
```

The following token list corresponds to the option `code-after` (it’s also possible to set the value of that parameter with the keyword `\CodeAfter`). That parameter is *public*.

```
386 \tl_new:N \g_nicematrix_code_after_tl
387 \bool_new:N \l_@@_in_code_after_bool
```

For the key code of the command `\SubMatrix` (itself in the main `\CodeAfter`), we will use the following token list.

```
388 \tl_new:N \l_@@_code_tl
```

The following token list has a function similar to `\g_nicematrix_code_after_tl` but it is used internally by `nicematrix`. In fact, we have to distinguish between `\g_nicematrix_code_after_tl` and `\g_@@_pre_code_after_tl` because we must take care of the order in which instructions stored in that parameters are executed.

```
389 \tl_new:N \g_@@_pre_code_after_tl
```

```
390 \tl_new:N \g_nicematrix_code_before_tl
391 \tl_new:N \g_@@_pre_code_before_tl
```

The counters `\l_@@_old_iRow_int` and `\l_@@_old_jCol_int` will be used to save the values of the potential LaTeX counters `iRow` and `jCol`. These LaTeX counters will be restored at the end of the environment.

```
392 \int_new:N \l_@@_old_iRow_int
393 \int_new:N \l_@@_old_jCol_int
```

The TeX counters `\c@iRow` and `\c@jCol` will be created in the beginning of `{NiceArrayWithDelims}` (if they don’t exist previously).

The following sequence will contain the names (without backslash) of the commands created by `custom-line` by the key `command` or `ccommand` (commands used by the final user in order to draw horizontal rules).

```
394 \seq_new:N \l_@@_custom_line_commands_seq
```

The following token list corresponds to the key `rules/color` available in the environments.

```
395 \tl_new:N \l_@@_rules_color_tl
```

The sum of the weights of all the X-columns in the preamble. The weight of a X-column is given as an optional argument between square brackets. The default value, of course, is 1.

```
396 \int_new:N \g_@@_total_X_weight_int
```

If there is at least one X-column in the preamble of the array, the following flag will be raised via the `aux` file. The length `l_@@_x_columns_dim` will be the width of X-columns of weight 1 (the width of a column of weight n will be that dimension multiplied by n). That value is computed after the construction of the array during the first compilation in order to be used in the following run.

```
397 \bool_new:N \l_@@_X_columns_aux_bool
398 \dim_new:N \l_@@_X_columns_dim
```

This boolean will be used only to detect in an expandable way whether we are at the beginning of the (potential) column zero, in order to raise an error if `\Hdotsfor` is used in that column.

```
399 \bool_new:N \g_@@_after_col_zero_bool
```

A kind of false row will be inserted at the end of the array for the construction of the `col` nodes (and also to fix the width of the columns when `columns-width` is used). When this special row will be created, we will raise the flag `\g_@@_row_of_col_done_bool` in order to avoid some actions set in the redefinition of `\everycr` when the last `\cr` of the `\halign` will occur (after that row of `col` nodes).

```
400 \bool_new:N \g_@@_row_of_col_done_bool
```

It's possible to use the command `\NotEmpty` to specify explicitly that a cell must be considered as non empty by `nicematrix` (the Tikz nodes are constructed only in the non empty cells).

```
401 \bool_new:N \g_@@_not_empty_cell_bool
```

`\l_@@_code_before_tl` may contain two types of informations:

- A `code-before` written in the `aux` file by a previous run. When the `aux` file is read, this `code-before` is stored in `\g_@@_code_before_i_tl` (where i is the number of the environment) and, at the beginning of the environment, it will be put in `\l_@@_code_before_tl`.
- The final user can explicitly add material in `\l_@@_code_before_tl` by using the key `code-before` or the keyword `\CodeBefore` (with the keyword `\Body`).

```
402 \tl_new:N \l_@@_code_before_tl
403 \bool_new:N \l_@@_code_before_bool
```

The following token list will contain the code inserted in each cell of the current row (this token list will be cleared at the beginning of each row).

```
404 \tl_new:N \g_@@_row_style_tl
```

The following dimensions will be used when drawing the dotted lines.

```
405 \dim_new:N \l_@@_x_initial_dim
406 \dim_new:N \l_@@_y_initial_dim
407 \dim_new:N \l_@@_x_final_dim
408 \dim_new:N \l_@@_y_final_dim
```

The L3 programming layer provides scratch dimensions `\l_tmpa_dim` and `\l_tmpb_dim`. We creates two more in the same spirit.

```
409 \dim_zero_new:N \l_@@_tmpc_dim
410 \dim_zero_new:N \l_@@_tmpd_dim
```

Some cells will be declared as “empty” (for example a cell with an instruction `\Cdots`).

```
411 \bool_new:N \g_@@_empty_cell_bool
```

The following boolean will be used to deal with the commands `\tabularnote` in the caption (command `\caption` or key `caption`).

```
412 \bool_new:N \g_@@_second_composition_bool
```

The following dimensions will be used internally to compute the width of the potential “first column” and “last column”.

```
413 \dim_new:N \g_@@_width_last_col_dim
414 \dim_new:N \g_@@_width_first_col_dim
```

The following sequence will contain the characteristics of the blocks of the array, specified by the command `\Block`. Each block is represented by 6 components surrounded by curly braces:

`{imin}{jmin}{imax}{jmax}{options}{contents}`.

The variable is global because it will be modified in the cells of the array.

```
415 \seq_new:N \g_@@_blocks_seq
```

We also manage a sequence of the *positions* of the blocks. In that sequence, each block is represented by only five components: `{imin}{jmin}{imax}{jmax}{ name}`. A block with the key `hvlines` won’t appear in that sequence (otherwise, the lines in that block would not be drawn!).

```
416 \seq_new:N \g_@@_pos_of_blocks_seq
```

In fact, this sequence will also contain the positions of the cells with a `\diagbox`. The sequence `\g_@@_pos_of_blocks_seq` will be used when we will draw the rules (which respect the blocks).

We will also manage a sequence for the positions of the dotted lines. These dotted lines are created in the array by `\Cdots`, `\Vdots`, `\Ddots`, etc. However, their positions, that is to say, their extremities, will be determined only after the construction of the array. In this sequence, each item contains five components: `{imin}{jmin}{imax}{jmax}{ name}`.

```
417 \seq_new:N \g_@@_pos_of_xdots_seq
```

The sequence `\g_@@_pos_of_xdots_seq` will be used when we will draw the rules required by the key `hvlines` (these rules won’t be drawn within the virtual blocks corresponding to the dotted lines).

The final user may decide to “stroke” a block (using, for example, the key `draw=red!15` when using the command `\Block`). In that case, the rules specified, for instance, by `hvlines` must not be drawn around the block. That’s why we keep the information of all that stroken blocks in the following sequence.

```
418 \seq_new:N \g_@@_pos_of_stroken_blocks_seq
```

If the user has used the key `corners`, all the cells which are in an (empty) corner will be stored in the following sequence.

```
419 \seq_new:N \l_@@_corners_cells_seq
```

The list of the names of the potential `\SubMatrix` in the `\CodeAfter` of an environment. Unfortunately, that list has to be global (we have to use it inside the group for the options of a given `\SubMatrix`).

```
420 \seq_new:N \g_@@_submatrix_names_seq
```

The following flag will be raised if the key `width` is used in an environment `{NiceTabular}` (not in a command `\NiceMatrixOptions`). You use it to raise an error when this key is used while no column `X` is used.

```
421 \bool_new:N \l_@@_width_used_bool
```

The sequence `\g_@@_multicolumn_cells_seq` will contain the list of the cells of the array where a command `\multicolumn{n}{...}{...}` with $n > 1$ is issued. In `\g_@@_multicolumn_sizes_seq`, the “sizes” (that is to say the values of n) correspondent will be stored. These lists will be used for the creation of the “medium nodes” (if they are created).

```
422 \seq_new:N \g_@@_multicolumn_cells_seq
423 \seq_new:N \g_@@_multicolumn_sizes_seq
```


The following counters will be used when searching the extremities of a dotted line (we need these counters because of the potential “open” lines in the `\SubMatrix`—the `\SubMatrix` in the code-before).

```
424 \int_new:N \l_@@_row_min_int
425 \int_new:N \l_@@_row_max_int
426 \int_new:N \l_@@_col_min_int
427 \int_new:N \l_@@_col_max_int
```

The following sequence will be used when the command `\SubMatrix` is used in the `\CodeBefore` (and not in the `\CodeAfter`). It will contain the position of all the sub-matrices specified in the `\CodeBefore`. Each sub-matrix is represented by an “object” of the forme $\{i\}\{j\}\{k\}\{l\}$ where i and j are the number of row and column of the upper-left cell and k and l the number of row and column of the lower-right cell.

```
428 \seq_new:N \g_@@_submatrix_seq
```

We are able to determine the number of columns specified in the preamble (for the environments with explicit preamble of course and without the potential exterior columns).

```
429 \int_new:N \g_@@_static_num_of_col_int
```

The following parameters correspond to the keys `fill`, `draw`, `tikz`, `borders`, and `rounded-corners` of the command `\Block`.

```
430 \tl_new:N \l_@@_fill_tl
431 \tl_new:N \l_@@_draw_tl
432 \seq_new:N \l_@@_tikz_seq
433 \clist_new:N \l_@@_borders_clist
434 \dim_new:N \l_@@_rounded_corners_dim
```

The last parameter has no direct link with the [empty] corners of the array (which are computed and taken into account by `nicematrix` when the key `corners` is used).

The following token list correspond to the key `color` of the command `\Block` and also the key `color` of the command `\RowStyle`.

```
435 \tl_new:N \l_@@_color_tl
```

Here is the dimension for the width of the rule when a block (created by `\Block`) is stroked.

```
436 \dim_new:N \l_@@_line_width_dim
```

The parameters of the horizontal position of the label of a block. If the user uses the key `c` or `C`, the value is `c`. If the user uses the key `l` or `L`, the value is `l`. If the user uses the key `r` or `R`, the value is `r`. If the user has used a capital letter, the boolean `\l_@@_hpos_of_block_cap_bool` will be raised (in the second pass of the analyze of the keys of the command `\Block`).

```
437 \str_new:N \l_@@_hpos_block_str
438 \str_set:Nn \l_@@_hpos_block_str { c }
439 \bool_new:N \l_@@_hpos_of_block_cap_bool
```

For the vertical position, the possible values are `c`, `t` and `b`. Of course, it would be interesting to program a key `T` and a key `B`.

```
440 \tl_new:N \l_@@_vpos_of_block_tl
441 \tl_set:Nn \l_@@_vpos_of_block_tl { c }
```

Used when the key `draw-first` is used for `\Ddots` or `\Iddots`.

```
442 \bool_new:N \l_@@_draw_first_bool
```

The following flag corresponds to the keys `vlines` and `hlines` of the command `\Block` (the key `hvlines` is the conjunction of both).

```
443 \bool_new:N \l_@@_vlines_block_bool
444 \bool_new:N \l_@@_hlines_block_bool
```

The blocks which use the key `-` will store their content in a box. These boxes are numbered with the following counter.

```
445 \int_new:N \g_@@_block_box_int
```

```

446 \dim_new:N \l_@@_submatrix_extra_height_dim
447 \dim_new:N \l_@@_submatrix_left_xshift_dim
448 \dim_new:N \l_@@_submatrix_right_xshift_dim
449 \clist_new:N \l_@@_hlines_clist
450 \clist_new:N \l_@@_vlines_clist
451 \clist_new:N \l_@@_submatrix_hlines_clist
452 \clist_new:N \l_@@_submatrix_vlines_clist

```

The following flag will be used by (for instance) `\@@_vline_ii:`. When `\l_@@_dotted_bool` is true, a dotted line (with our system) will be drawn.

```

453 \bool_new:N \l_@@_dotted_bool

```

The following flag will be set to true during the composition of a caption specified (by the key `caption`).

```

454 \bool_new:N \l_@@_in_caption_bool

```

Variables for the exterior rows and columns

The keys for the exterior rows and columns are `first-row`, `first-col`, `last-row` and `last-col`. However, internally, these keys are not coded in a similar way.

• First row

The integer `\l_@@_first_row_int` is the number of the first row of the array. The default value is 1, but, if the option `first-row` is used, the value will be 0.

```

455 \int_new:N \l_@@_first_row_int
456 \int_set:Nn \l_@@_first_row_int 1

```

• First column

The integer `\l_@@_first_col_int` is the number of the first column of the array. The default value is 1, but, if the option `first-col` is used, the value will be 0.

```

457 \int_new:N \l_@@_first_col_int
458 \int_set:Nn \l_@@_first_col_int 1

```

• Last row

The counter `\l_@@_last_row_int` is the number of the potential “last row”, as specified by the key `last-row`. A value of `-2` means that there is no “last row”. A value of `-1` means that there is a “last row” but we don’t know the number of that row (the key `last-row` has been used without value and the actual value has not still been read in the `aux` file).

```

459 \int_new:N \l_@@_last_row_int
460 \int_set:Nn \l_@@_last_row_int { -2 }

```

If, in an environment like `{pNiceArray}`, the option `last-row` is used without value, we will globally raise the following flag. It will be used to know if we have, after the construction of the array, to write in the `aux` file the number of the “last row”.⁶⁶

```

461 \bool_new:N \l_@@_last_row_without_value_bool

```

Idem for `\l_@@_last_col_without_value_bool`

```

462 \bool_new:N \l_@@_last_col_without_value_bool

```

⁶⁶We can’t use `\l_@@_last_row_int` for this usage because, if `nicematrix` has read its value from the `aux` file, the value of the counter won’t be `-1` any longer.

- **Last column**

For the potential “last column”, we use an integer. A value of -2 means that there is no last column. A value of -1 means that we are in an environment without preamble (e.g. `{bNiceMatrix}`) and there is a last column but we don’t know its value because the user has used the option `last-col` without value. A value of 0 means that the option `last-col` has been used in an environment with preamble (like `{pNiceArray}`): in this case, the key was necessary without argument.

```
463 \int_new:N \l_@@_last_col_int
464 \int_set:Nn \l_@@_last_col_int { -2 }
```

However, we have also a boolean. Consider the following code:

```
\begin{pNiceArray}{cc}[last-col]
1 & 2 \\
3 & 4
\end{pNiceArray}
```

In such a code, the “last column” specified by the key `last-col` is not used. We want to be able to detect such a situation and we create a boolean for that job.

```
465 \bool_new:N \g_@@_last_col_found_bool
```

This boolean is set to `false` at the end of `\@@_pre_array_ii:`.

Some utilities

```
466 \cs_set_protected:Npn \@@_cut_on_hyphen:w #1-#2\q_stop
467 {
468   \tl_set:Nn \l_tmpa_tl { #1 }
469   \tl_set:Nn \l_tmpb_tl { #2 }
470 }
```

The following takes as argument the name of a `clist` and which should be a list of intervals of integers. It *expands* that list, that is to say, it replaces (by a sort of `mapcan` or `flat_map`) the interval by the explicit list of the integers.

```
471 \cs_new_protected:Npn \@@_expand_clist:N #1
472 {
473   \clist_if_in:NnF #1 { all }
474   {
475     \clist_clear:N \l_tmpa_clist
476     \clist_map_inline:Nn #1
477     {
478       \tl_if_in:nnTF { ##1 } { - }
479       { \@@_cut_on_hyphen:w ##1 \q_stop }
480       {
481         \tl_set:Nn \l_tmpa_tl { ##1 }
482         \tl_set:Nn \l_tmpb_tl { ##1 }
483       }
484       \int_step_inline:nnn { \l_tmpa_tl } { \l_tmpb_tl }
485       { \clist_put_right:Nn \l_tmpa_clist { ###1 } }
486     }
487     \tl_set_eq:NN #1 \l_tmpa_clist
488   }
489 }
```

The command `\tabularnote`

Of course, it's possible to use `\tabularnote` in the main tabular. But there is also the possibility to use that command in the caption of the tabular. And the caption may be specified by two means:

- The caption may of course be provided by the command `\caption` in a floating environment. Of course, a command `\tabularnote` in that `\caption` makes sens only if the `\caption` is *before* the `{tabular}`.
- It's also possible to use `\tabularnote` in the value of the key `caption` of the `{NiceTabular}` when the key `caption-above` is in force. However, in that case, one must remind that the caption is composed *after* the composition of the box which contains the main tabular (that's mandatory since that caption must be wrapped with a line width equal to the width of the tabular). However, we want the labels of the successive tabular notes in the logical order. That's why:
 - The number of tabular notes present in the caption will be written on the `aux` file and available in `\l_@@_note_in_caption_int`.
 - During the composition of the main tabular, the tabular notes will be numbered from `\l_@@_note_in_caption_int+1` and the notes will be stored in `\g_@@_notes_seq`.
 - During the composition of the caption (value of `\l_@@_caption_tl`), the tabular notes will be numbered from 1 to `\l_@@_note_in_caption_int` and the notes themselves will be stored in `\g_@@_notes_in_caption_seq`.
 - After the composition of the main tabular and after the composition of the caption, the sequences `\g_@@_notes_in_caption_seq` and `\g_@@_notes_seq` will be merged (in that order) and the notes will be composed.

The LaTeX counter `tabularnote` will be used to count the tabular notes during the construction of the array (this counter won't be used during the composition of the notes at the end of the array). You use a LaTeX counter because we will use `\refstepcounter` in order to have the tabular notes referenceable.

```
490 \newcounter { tabularnote }
491 \seq_new:N \g_@@_notes_seq
492 \seq_new:N \g_@@_notes_in_caption_seq
```

Before the actual tabular notes, it's possible to put a text specified by the key `tabularnote` of the environment. The token list `\l_@@_tabularnote_tl` corresponds to the value of that key.

```
493 \tl_new:N \g_@@_tabularnote_tl
```

We prepare the tools for the formatting of the references of the footnotes (in the tabular itself). There may have several references of footnote at the same point and we have to take into account that point.

```
494 \seq_new:N \l_@@_notes_labels_seq
495 \newcounter{nicematrix_draft}
496 \cs_new_protected:Npn \@@_notes_format:n #1
497 {
498   \setcounter { nicematrix_draft } { #1 }
499   \@@_notes_style:n { nicematrix_draft }
500 }
```

The following function can be redefined by using the key `notes/style`.

```
501 \cs_new:Npn \@@_notes_style:n #1 { \textit { \alph { #1 } } }
```

The following fonction can be redefined by using the key `notes/label-in-tabular`.

```
502 \cs_new:Npn \@@_notes_label_in_tabular:n #1 { \textsuperscript { #1 } }
```

The following function can be redefined by using the key `notes/label-in-list`.

```
503 \cs_new:Npn \@@_notes_label_in_list:n #1 { \textsuperscript { #1 } }
```

We define `\thetabulernote` because it will be used by LaTeX if the user want to reference a tabular which has been marked by a `\label`. The TeX group is for the case where the user has put an instruction such as `\color{red}` in `\@@_notes_style:n`.

```
504 \cs_set:Npn \thetabulernote { { \@@_notes_style:n { tabulernote } } }
```

The tabular notes will be available for the final user only when `enumitem` is loaded. Indeed, the tabular notes will be composed at the end of the array with a list customized by `enumitem` (a list `tabularnotes` in the general case and a list `tabularnotes*` if the key `para` is in force). However, we can test whether `enumitem` has been loaded only at the beginning of the document (we want to allow the user to load `enumitem` after `nicematrix`).

```
505 \hook_gput_code:nnn { begindocument } { . }
506 {
507   \bool_if:nTF { ! \c_@@_enumitem_loaded_bool }
508   {
509     \NewDocumentCommand \tabulernote { m }
510     {
511       \@@_error_or_warning:n { enumitem-not-loaded }
512       \@@_gredirect_none:n { enumitem-not-loaded }
513     }
514   }
515 }
```

The type of list `tabularnotes` will be used to format the tabular notes at the end of the array in the general case and `tabularnotes*` will be used if the key `para` is in force.

```
516 \newlist { tabularnotes } { enumerate } { 1 }
517 \setlist [ tabularnotes ]
518 {
519   topsep = 0pt ,
520   noitemsep ,
521   leftmargin = * ,
522   align = left ,
523   labelsep = 0pt ,
524   label =
525     \@@_notes_label_in_list:n { \@@_notes_style:n { tabularnotesi } } ,
526 }
527 \newlist { tabularnotes* } { enumerate* } { 1 }
528 \setlist [ tabularnotes* ]
529 {
530   afterlabel = \nobreak ,
531   itemjoin = \quad ,
532   label =
533     \@@_notes_label_in_list:n { \@@_notes_style:n { tabularnotes*i } }
534 }
```

One must remind that we have allowed a `\tabular` in the caption and that caption may also be found in the list of tables (`\listoftables`). We want the command `\tabulernote` be no-op during the composition of that list. That's why we program `\tabulernote` to be no-op excepted in a floating environment or in an environment of `nicematrix`.

```
535 \NewDocumentCommand \tabulernote { m }
536 {
537   \bool_if:nT { \cs_if_exist_p:N \c@type || \l_@@_in_env_bool }
538   {
539     \bool_if:nTF { ! \l_@@_NiceTabular_bool && \l_@@_in_env_bool }
540     { \@@_error:n { tabulernote-forbidden } }
541     {
542       \bool_if:NTF \l_@@_in_caption_bool
543       { \@@_tabulernote_ii:n { #1 } }
544       { \@@_tabulernote_i:n { #1 } }
545     }
546   }
547 }
```

```

545     }
546   }
547 }

```

For the version in normal conditions, that is to say not in the key `caption`.

```

548   \cs_new_protected:Npn \l_@@_tabularnote_i:n #1
549   {

```

You have to see whether the argument of `\tabularnote` has yet been used as argument of another `\tabularnote` in the same tabular. In that case, there will be only one note (for both commands `\tabularnote`) at the end of the tabular. We search the argument of our command `\tabularnote` in the `\g_@@_notes_seq`. The position in the sequence will be stored in `\l_tmpa_int` (0 if the text is not in the sequence yet).

```

550     \int_zero:N \l_tmpa_int
551     \bool_if:NT \l_@@_notes_detect_duplicates_bool
552     {
553       \seq_map_indexed_inline:Nn \g_@@_notes_seq
554       {
555         \tl_if_eq:nnT { #1 } { ##2 }
556         { \int_set:Nn \l_tmpa_int { ##1 } \seq_map_break: }
557       }
558       \int_compare:nNnF \l_tmpa_int = 0
559       { \int_add:Nn \l_tmpa_int \l_@@_note_in_caption_int }
560     }
561     \int_compare:nNnTF \l_tmpa_int = 0
562     {
563       \int_gincr:N \c@tabularnote
564       \seq_put_right:Nx \l_@@_notes_labels_seq
565       { \@@_notes_format:n { \int_use:c { c @ tabularnote } } }
566       \seq_gput_right:Nn \g_@@_notes_seq { #1 }
567     }
568     {
569       \seq_put_right:Nx \l_@@_notes_labels_seq
570       { \@@_notes_format:n { \int_use:N \l_tmpa_int } }
571     }
572     \peek_meaning:NF \tabularnote
573     {

```

If the following token is *not* a `\tabularnote`, we have finished the sequence of successive commands `\tabularnote` and we have to format the labels of these tabular notes (in the array). We compose those labels in a box `\l_tmpa_box` because we will do a special construction in order to have this box in an overlapping position if we are at the end of a cell.

```

574       \hbox_set:Nn \l_tmpa_box
575       {

```

We remind that it is the command `\@@_notes_label_in_tabular:n` that will put the labels in a `\textsuperscript`.

```

576         \@@_notes_label_in_tabular:n
577         {
578           \seq_use:Nnnn
579           \l_@@_notes_labels_seq { , } { , } { , }
580         }
581       }

```

We want the (last) tabular note referenceable (with the standard command `\label`).

```

582     \int_gsub:Nn \c@tabularnote { 1 }
583     \int_set_eq:NN \l_tmpa_int \c@tabularnote
584     \refstepcounter { tabularnote }
585     \int_compare:nNnT \l_tmpa_int = \c@tabularnote
586     { \int_gincr:N \c@tabularnote }
587     \seq_clear:N \l_@@_notes_labels_seq
588     \hbox_overlap_right:n { \box_use:N \l_tmpa_box }

```

If the command `\tabularnote` is used exactly at the end of the cell, the `\unskip` (inserted by `array`?) will delete the skip we insert now and the label of the footnote will be composed in an overlapping position (by design).

```

589         \skip_horizontal:n { \box_wd:N \l_tmpa_box }
590     }
591 }

```

Now the version when the command is used in the key `caption`. The main difficulty is that the argument of the command `\caption` is composed several times. In order to know the number of commands `\tabularnote` in the caption, we will consider that there should not be the same tabular note twice in the caption (in the main tabular, it's possible). Once we have found a tabular note which has yet been encountered, we consider that you are in a new composition of the argument of `\caption`. At that time, we store in `\g_@@_nb_of_notes_int` the number of notes in the `\caption`.

```

592     \cs_new_protected:Npn \@@_tabularnote_ii:n #1
593     {
594         \int_gincr:N \c@tabularnote
595         \bool_if:NTF \g_@@_caption_finished_bool
596         {
597             \int_compare:nNnTF
598             \c@tabularnote > { \tl_count:N \g_@@_notes_in_caption_seq }
599             { \int_gset:Nn \c@tabularnote { 1 } }
600             \seq_if_in:NnF \g_@@_notes_in_caption_seq { #1 }
601             { \@@_fatal:n { Identical-notes-in-caption } }
602         }
603         {
604             \seq_if_in:NnTF \g_@@_notes_in_caption_seq { #1 }
605             {
606                 \bool_gset_true:N \g_@@_caption_finished_bool
607                 \int_gset:Nn \c@tabularnote { 1 }
608             }
609             { \seq_gput_right:Nn \g_@@_notes_in_caption_seq { #1 } }
610         }
611         \seq_put_right:Nx \l_@@_notes_labels_seq
612         { \@@_notes_format:n { \int_use:N \c@tabularnote } }
613         \peek_meaning:NF \tabularnote
614         {
615             \hbox_set:Nn \l_tmpa_box
616             {
617                 \@@_notes_label_in_tabular:n
618                 {
619                     \seq_use:Nnnn
620                     \l_@@_notes_labels_seq { , } { , } { , } { , }
621                 }
622             }
623             \seq_clear:N \l_@@_notes_labels_seq
624             \hbox_overlap_right:n { \box_use:N \l_tmpa_box }
625             \skip_horizontal:n { \box_wd:N \l_tmpa_box }
626         }
627     }
628 }
629 }

```

Command for creation of rectangle nodes

The following command should be used in a `{pgfpicture}`. It creates a rectangle (empty but with a name).

#1 is the name of the node which will be created; **#2** and **#3** are the coordinates of one of the corner of the rectangle; **#4** and **#5** are the coordinates of the opposite corner.

```

630 \cs_new_protected:Npn \@@_pgf_rect_node:nnnnn #1 #2 #3 #4 #5
631 {
632     \begin { pgfscope }

```

```

633 \pgfset
634 {
635     outer~sep = \c_zero_dim ,
636     inner~sep = \c_zero_dim ,
637     minimum~size = \c_zero_dim
638 }
639 \pgftransformshift { \pgfpoint { 0.5 * ( #2 + #4 ) } { 0.5 * ( #3 + #5 ) } }
640 \pgfnode
641 { rectangle }
642 { center }
643 {
644     \vbox_to_ht:nn
645     { \dim_abs:n { #5 - #3 } }
646     {
647         \vfill
648         \hbox_to_wd:nn { \dim_abs:n { #4 - #2 } } { }
649     }
650 }
651 { #1 }
652 { }
653 \end { pgfscope }
654 }

```

The command `\@@_pgf_rect_node:nnn` is a variant of `\@@_pgf_rect_node:nnnnn`: it takes two PGF points as arguments instead of the four dimensions which are the coordinates.

```

655 \cs_new_protected:Npn \@@_pgf_rect_node:nnn #1 #2 #3
656 {
657     \begin { pgfscope }
658     \pgfset
659     {
660         outer~sep = \c_zero_dim ,
661         inner~sep = \c_zero_dim ,
662         minimum~size = \c_zero_dim
663     }
664     \pgftransformshift { \pgfpointscale { 0.5 } { \pgfpointadd { #2 } { #3 } } }
665     \pgfpointdiff { #3 } { #2 }
666     \pgfgetlastxy \l_tmpa_dim \l_tmpb_dim
667     \pgfnode
668     { rectangle }
669     { center }
670     {
671         \vbox_to_ht:nn
672         { \dim_abs:n \l_tmpb_dim }
673         { \vfill \hbox_to_wd:nn { \dim_abs:n \l_tmpa_dim } { } }
674     }
675     { #1 }
676     { }
677     \end { pgfscope }
678 }

```

The options

The following parameter corresponds to the keys `caption`, `short-caption` and `label` of the environment `{NiceTabular}`.

```

679 \tl_new:N \l_@@_caption_tl
680 \tl_new:N \l_@@_short_caption_tl
681 \tl_new:N \l_@@_label_tl

```

The following parameter corresponds to the key `caption-above` of `\NiceMatrixOptions`. When this parameter is `true`, the captions of the environments `{NiceTabular}`, specified with the key `caption` are put above the tabular (and below elsewhere).


```
682 \bool_new:N \l_@@_caption_above_bool
```

By default, the commands `\cellcolor` and `\rowcolor` are available for the user in the cells of the tabular (the user may use the commands provided by `\colortbl`). However, if the key `colortbl-like` is used, these commands are available.

```
683 \bool_new:N \l_@@_colortbl_like_bool
```

By default, the behaviour of `\cline` is changed in the environments of `nicematrix`: a `\cline` spreads the array by an amount equal to `\arrayrulewidth`. It's possible to disable this feature with the key `\l_@@_standard_line_bool`.

```
684 \bool_new:N \l_@@_standard_cline_bool
```

The following dimensions correspond to the options `cell-space-top-limit` and `co` (these parameters are inspired by the package `cellspace`).

```
685 \dim_new:N \l_@@_cell_space_top_limit_dim
686 \dim_new:N \l_@@_cell_space_bottom_limit_dim
```

The following dimension is the distance between two dots for the dotted lines (when `line-style` is equal to `standard`, which is the initial value). The initial value is 0.45 em but it will be changed if the option `small` is used.

```
687 \dim_new:N \l_@@_xdots_inter_dim
688 \hook_gput_code:nnn { begindocument } { . }
689 { \dim_set:Nn \l_@@_xdots_inter_dim { 0.45 em } }
```

We use a hook only by security in case `revtex4-1` is used (even though it is obsolete).

The following dimension is the minimal distance between a node (in fact an anchor of that node) and a dotted line (we say “minimal” because, by definition, a dotted line is not a continuous line and, therefore, this distance may vary a little).

```
690 \dim_new:N \l_@@_xdots_shorten_start_dim
691 \dim_new:N \l_@@_xdots_shorten_end_dim
692 \hook_gput_code:nnn { begindocument } { . }
693 {
694   \dim_set:Nn \l_@@_xdots_shorten_start_dim { 0.3 em }
695   \dim_set:Nn \l_@@_xdots_shorten_end_dim { 0.3 em }
696 }
```

We use a hook only by security in case `revtex4-1` is used (even though it is obsolete).

The following dimension is the radius of the dots for the dotted lines (when `line-style` is equal to `standard`, which is the initial value). The initial value is 0.53 pt but it will be changed if the option `small` is used.

```
697 \dim_new:N \l_@@_xdots_radius_dim
698 \hook_gput_code:nnn { begindocument } { . }
699 { \dim_set:Nn \l_@@_xdots_radius_dim { 0.53 pt } }
```

We use a hook only by security in case `revtex4-1` is used (even though it is obsolete).

The token list `\l_@@_xdots_line_style_tl` corresponds to the option `tikz` of the commands `\Cdots`, `\Ldots`, etc. and of the options `line-style` for the environments and `\NiceMatrixOptions`. The constant `\c_@@_standard_tl` will be used in some tests.

```
700 \tl_new:N \l_@@_xdots_line_style_tl
701 \tl_const:Nn \c_@@_standard_tl { standard }
702 \tl_set_eq:NN \l_@@_xdots_line_style_tl \c_@@_standard_tl
```

The boolean `\l_@@_light_syntax_bool` corresponds to the option `light-syntax`.

```
703 \bool_new:N \l_@@_light_syntax_bool
```

The string `\l_@@_baseline_tl` may contain one of the three values `t`, `c` or `b` as in the option of the environment `{array}`. However, it may also contain an integer (which represents the number of the row to which align the array).

```
704 \tl_new:N \l_@@_baseline_tl
705 \tl_set:Nn \l_@@_baseline_tl c
```

The flag `\l_@@_exterior_arraycolsep_bool` corresponds to the option `exterior-arraycolsep`. If this option is set, a space equal to `\arraycolsep` will be put on both sides of an environment `{NiceArray}` (as it is done in `{array}` of `array`).

```
706 \bool_new:N \l_@@_exterior_arraycolsep_bool
```

The flag `\l_@@_parallelize_diags_bool` controls whether the diagonals are parallelized. The initial value is `true`.

```
707 \bool_new:N \l_@@_parallelize_diags_bool
708 \bool_set_true:N \l_@@_parallelize_diags_bool
```

The following parameter correspond to the key `corners`. The elements of that `clist` must be in NW, SW, NE and SE.

```
709 \clist_new:N \l_@@_corners_clist
```

```
710 \dim_new:N \l_@@_notes_above_space_dim
711 \hook_gput_code:nnn { begindocument } { . }
712 { \dim_set:Nn \l_@@_notes_above_space_dim { 1 mm } }
```

We use a hook only by security in case `revtex4-1` is used (even though it is obsolete).

The flag `\l_@@_nullify_dots_bool` corresponds to the option `nullify-dots`. When the flag is down, the instructions like `\vdots` are inserted within a `\hphantom` (and so the constructed matrix has exactly the same size as a matrix constructed with the classical `{matrix}` and `\ldots`, `\vdots`, etc.).

```
713 \bool_new:N \l_@@_nullify_dots_bool
```

The following flag corresponds to the key `respect-arraystretch` (that key has an effect on the blocks).

```
714 \bool_new:N \l_@@_respect_arraystretch_bool
```

The following flag will be used when the current options specify that all the columns of the array must have the same width equal to the largest width of a cell of the array (except the cells of the potential exterior columns).

```
715 \bool_new:N \l_@@_auto_columns_width_bool
```

The following boolean corresponds to the key `create-cell-nodes` of the keyword `\CodeBefore`.

```
716 \bool_new:N \g_@@_recreate_cell_nodes_bool
```

The string `\l_@@_name_str` will contain the optional name of the environment: this name can be used to access to the Tikz nodes created in the array from outside the environment.

```
717 \str_new:N \l_@@_name_str
```

The boolean `\l_@@_medium_nodes_bool` will be used to indicate whether the “medium nodes” are created in the array. Idem for the “large nodes”.

```
718 \bool_new:N \l_@@_medium_nodes_bool
719 \bool_new:N \l_@@_large_nodes_bool
```

The boolean `\l_@@_except_borders_bool` will be raised when the key `hvlines-except-borders` will be used (but that key has also other effects).

```
720 \bool_new:N \l_@@_except_borders_bool
```

The dimension `\l_@@_left_margin_dim` correspond to the option `left-margin`. Idem for the right margin. These parameters are involved in the creation of the “medium nodes” but also in the placement of the delimiters and the drawing of the horizontal dotted lines (`\hdottedline`).

```
721 \dim_new:N \l_@@_left_margin_dim
722 \dim_new:N \l_@@_right_margin_dim
```

The dimensions `\l_@@_extra_left_margin_dim` and `\l_@@_extra_right_margin_dim` correspond to the options `extra-left-margin` and `extra-right-margin`.

```
723 \dim_new:N \l_@@_extra_left_margin_dim
724 \dim_new:N \l_@@_extra_right_margin_dim
```

The token list `\l_@@_end_of_row_tl` corresponds to the option `end-of-row`. It specifies the symbol used to mark the ends of rows when the light syntax is used.

```
725 \tl_new:N \l_@@_end_of_row_tl
726 \tl_set:Nn \l_@@_end_of_row_tl { ; }
```

The following parameter is for the color the dotted lines drawn by `\Cdots`, `\Ldots`, `\Vdots`, `\Ddots`, `\Iddots` and `\Hdotsfor` but *not* the dotted lines drawn by `\hdottedline` and “:”.

```
727 \tl_new:N \l_@@_xdots_color_tl
```

The following token list corresponds to the key `delimiters/color`.

```
728 \tl_new:N \l_@@_delimiters_color_tl
```

Sometimes, we want to have several arrays vertically juxtaposed in order to have an alignment of the columns of these arrays. To achieve this goal, one may wish to use the same width for all the columns (for example with the option `columns-width` or the option `auto-columns-width` of the environment `{NiceMatrixBlock}`). However, even if we use the same type of delimiters, the width of the delimiters may be different from an array to another because the width of the delimiter is function of its size. That’s why we create an option called `delimiters/max-width` which will give to the delimiters the width of a delimiter (of the same type) of big size. The following boolean corresponds to this option.

```
729 \bool_new:N \l_@@_delimiters_max_width_bool
```

```
730 \keys_define:nn { NiceMatrix / xdots }
731 {
732   line-style .code:n =
733   {
734     \bool_lazy_or:nnTF
```

We can’t use `\c_@@_tikz_loaded_bool` to test whether `tikz` is loaded because `\NiceMatrixOptions` may be used in the preamble of the document.

```
735     { \cs_if_exist_p:N \tikzpicture }
736     { \str_if_eq_p:nn { #1 } { standard } }
737     { \tl_set:Nn \l_@@_xdots_line_style_tl { #1 } }
738     { \@@_error:n { bad-option-for-line-style } }
739   } ,
740   line-style .value_required:n = true ,
741   color .tl_set:N = \l_@@_xdots_color_tl ,
742   color .value_required:n = true ,
743   shorten .code:n =
744     \hook_gput_code:nnn { begindocument } { . }
745     {
746       \dim_set:Nn \l_@@_xdots_shorten_start_dim { #1 }
747       \dim_set:Nn \l_@@_xdots_shorten_end_dim { #1 }
748     } ,
749   shorten-start .code:n =
750     \hook_gput_code:nnn { begindocument } { . }
751     { \dim_set:Nn \l_@@_xdots_shorten_start_dim { #1 } } ,
752   shorten-end .code:n =
753     \hook_gput_code:nnn { begindocument } { . }
754     { \dim_set:Nn \l_@@_xdots_shorten_end_dim { #1 } } ,
```

We use a hook only by security in case `revtex4-1` is used (even though it is obsolete). Idem for the following keys.

```

755 shorten .value_required:n = true ,
756 shorten-start .value_required:n = true ,
757 shorten-end .value_required:n = true ,
758 radius .code:n =
759   \hook_gput_code:nnn { begindocument } { . }
760   { \dim_set:Nn \l_@@_xdots_radius_dim { #1 } } ,
761 radius .value_required:n = true ,
762 inter .code:n =
763   \hook_gput_code:nnn { begindocument } { . }
764   { \dim_set:Nn \l_@@_xdots_inter_dim { #1 } } ,
765 radius .value_required:n = true ,

```

The options `down` and `up` are not documented for the final user because he should use the syntax with `^` and `_`.

```

766 down .tl_set:N = \l_@@_xdots_down_tl ,
767 up .tl_set:N = \l_@@_xdots_up_tl ,

```

The key `draw-first`, which is meant to be used only with `\Ddots` and `\Iddots`, which be caught when `\Ddots` or `\Iddots` is used (during the construction of the array and not when we draw the dotted lines).

```

768 draw-first .code:n = \prg_do_nothing: ,
769 unknown .code:n = \@@_error:n { Unknown-key-for-xdots }
770 }

```

```

771 \keys_define:nn { NiceMatrix / rules }
772 {
773   color .tl_set:N = \l_@@_rules_color_tl ,
774   color .value_required:n = true ,
775   width .dim_set:N = \arrayrulewidth ,
776   width .value_required:n = true ,
777   unknown .code:n = \@@_error:n { Unknown-key-for-rules }
778 }

```

First, we define a set of keys “NiceMatrix / Global” which will be used (with the mechanism of `.inherit:n`) by other sets of keys.

```

779 \keys_define:nn { NiceMatrix / Global }
780 {
781   custom-line .code:n = \@@_custom_line:n { #1 } ,
782   rules .code:n = \keys_set:nn { NiceMatrix / rules } { #1 } ,
783   rules .value_required:n = true ,
784   standard-cline .bool_set:N = \l_@@_standard_cline_bool ,
785   standard-cline .default:n = true ,
786   cell-space-top-limit .dim_set:N = \l_@@_cell_space_top_limit_dim ,
787   cell-space-top-limit .value_required:n = true ,
788   cell-space-bottom-limit .dim_set:N = \l_@@_cell_space_bottom_limit_dim ,
789   cell-space-bottom-limit .value_required:n = true ,
790   cell-space-limits .meta:n =
791   {
792     cell-space-top-limit = #1 ,
793     cell-space-bottom-limit = #1 ,
794   } ,
795   cell-space-limits .value_required:n = true ,
796   xdots .code:n = \keys_set:nn { NiceMatrix / xdots } { #1 } ,
797   light-syntax .bool_set:N = \l_@@_light_syntax_bool ,
798   light-syntax .default:n = true ,
799   end-of-row .tl_set:N = \l_@@_end_of_row_tl ,
800   end-of-row .value_required:n = true ,
801   first-col .code:n = \int_zero:N \l_@@_first_col_int ,
802   first-row .code:n = \int_zero:N \l_@@_first_row_int ,
803   last-row .int_set:N = \l_@@_last_row_int ,

```

```

804 last-row .default:n = -1 ,
805 code-for-first-col .tl_set:N = \l_@@_code_for_first_col_tl ,
806 code-for-first-col .value_required:n = true ,
807 code-for-last-col .tl_set:N = \l_@@_code_for_last_col_tl ,
808 code-for-last-col .value_required:n = true ,
809 code-for-first-row .tl_set:N = \l_@@_code_for_first_row_tl ,
810 code-for-first-row .value_required:n = true ,
811 code-for-last-row .tl_set:N = \l_@@_code_for_last_row_tl ,
812 code-for-last-row .value_required:n = true ,
813 hlines .clist_set:N = \l_@@_hlines_clist ,
814 vlines .clist_set:N = \l_@@_vlines_clist ,
815 hlines .default:n = all ,
816 vlines .default:n = all ,
817 vlines-in-sub-matrix .code:n =
818 {
819   \tl_if_single_token:nTF { #1 }
820   { \tl_set:Nn \l_@@_letter_vlism_tl { #1 } }
821   { \@@_error:n { One-letter~allowed } }
822 },
823 vlines-in-sub-matrix .value_required:n = true ,
824 hvlines .code:n =
825 {
826   \clist_set:Nn \l_@@_vlines_clist { all }
827   \clist_set:Nn \l_@@_hlines_clist { all }
828 },
829 hvlines-except-borders .code:n =
830 {
831   \clist_set:Nn \l_@@_vlines_clist { all }
832   \clist_set:Nn \l_@@_hlines_clist { all }
833   \bool_set_true:N \l_@@_except_borders_bool
834 },
835 parallelize-diags .bool_set:N = \l_@@_parallelize_diags_bool ,

```

With the option `renew-dots`, the command `\cdots`, `\ldots`, `\vdots`, `\ddots`, etc. are redefined and behave like the commands `\Cdots`, `\Ldots`, `\Vdots`, `\Ddots`, etc.

```

836 renew-dots .bool_set:N = \l_@@_renew_dots_bool ,
837 renew-dots .value_forbidden:n = true ,
838 nullify-dots .bool_set:N = \l_@@_nullify_dots_bool ,
839 create-medium-nodes .bool_set:N = \l_@@_medium_nodes_bool ,
840 create-large-nodes .bool_set:N = \l_@@_large_nodes_bool ,
841 create-extra-nodes .meta:n =
842 { create-medium-nodes , create-large-nodes } ,
843 left-margin .dim_set:N = \l_@@_left_margin_dim ,
844 left-margin .default:n = \arraycolsep ,
845 right-margin .dim_set:N = \l_@@_right_margin_dim ,
846 right-margin .default:n = \arraycolsep ,
847 margin .meta:n = { left-margin = #1 , right-margin = #1 } ,
848 margin .default:n = \arraycolsep ,
849 extra-left-margin .dim_set:N = \l_@@_extra_left_margin_dim ,
850 extra-right-margin .dim_set:N = \l_@@_extra_right_margin_dim ,
851 extra-margin .meta:n =
852 { extra-left-margin = #1 , extra-right-margin = #1 } ,
853 extra-margin .value_required:n = true ,
854 respect-arraystretch .bool_set:N = \l_@@_respect_arraystretch_bool ,
855 respect-arraystretch .default:n = true
856 }

```

We define a set of keys used by the environments of `nicematrix` (but not by the command `\NiceMatrixOptions`).

```

857 \keys_define:nn { NiceMatrix / Env }
858 {
859   corners .clist_set:N = \l_@@_corners_clist ,

```

```

860   corners .default:n = { NW , SW , NE , SE } ,
861   code-before .code:n =
862   {
863     \tl_if_empty:nF { #1 }
864     {
865       \tl_gput_left:Nn \g_@@_pre_code_before_tl { #1 }
866       \bool_set_true:N \l_@@_code_before_bool
867     }
868   } ,
869   code-before .value_required:n = true ,

```

The options `c`, `t` and `b` of the environment `{NiceArray}` have the same meaning as the option of the classical environment `{array}`.

```

870   c .code:n = \tl_set:Nn \l_@@_baseline_tl c ,
871   t .code:n = \tl_set:Nn \l_@@_baseline_tl t ,
872   b .code:n = \tl_set:Nn \l_@@_baseline_tl b ,
873   baseline .tl_set:N = \l_@@_baseline_tl ,
874   baseline .value_required:n = true ,
875   columns-width .code:n =
876   { \tl_if_eq:nnTF { #1 } { auto }
877     { \bool_set_true:N \l_@@_auto_columns_width_bool }
878     { \dim_set:Nn \l_@@_columns_width_dim { #1 } } ,
879   columns-width .value_required:n = true ,
880   name .code:n =

```

We test whether we are in the measuring phase of an environment of `amsmath` (always loaded by `nicematrix`) because we want to avoid a fallacious message of duplicate name in this case.

```

881   \legacy_if:nF { measuring@ }
882   {
883     \str_set:Nn \l_tmpa_str { #1 }
884     \seq_if_in:NVTF \g_@@_names_seq \l_tmpa_str
885     { \@@_error:nn { Duplicate~name } { #1 } }
886     { \seq_gput_left:NV \g_@@_names_seq \l_tmpa_str }
887     \str_set_eq:NN \l_@@_name_str \l_tmpa_str
888   } ,
889   name .value_required:n = true ,
890   code-after .tl_gset:N = \g_nicematrix_code_after_tl ,
891   code-after .value_required:n = true ,
892   colortbl-like .code:n =
893   { \bool_set_true:N \l_@@_colortbl_like_bool
894     \bool_set_true:N \l_@@_code_before_bool ,
895   colortbl-like .value_forbidden:n = true
896   }
897   \keys_define:nn { NiceMatrix / notes }
898   {
899     para .bool_set:N = \l_@@_notes_para_bool ,
900     para .default:n = true ,
901     code-before .tl_set:N = \l_@@_notes_code_before_tl ,
902     code-before .value_required:n = true ,
903     code-after .tl_set:N = \l_@@_notes_code_after_tl ,
904     code-after .value_required:n = true ,
905     bottomrule .bool_set:N = \l_@@_notes_bottomrule_bool ,
906     bottomrule .default:n = true ,
907     style .code:n = \cs_set:Nn \@@_notes_style:n { #1 } ,
908     style .value_required:n = true ,
909     label-in-tabular .code:n =
910     { \cs_set:Nn \@@_notes_label_in_tabular:n { #1 } ,
911     label-in-tabular .value_required:n = true ,
912     label-in-list .code:n =
913     { \cs_set:Nn \@@_notes_label_in_list:n { #1 } ,
914     label-in-list .value_required:n = true ,
915     enumitem-keys .code:n =
916     {

```

```

917     \hook_gput_code:nnn { begindocument } { . }
918     {
919         \bool_if:NT \c_@@_enumitem_loaded_bool
920         { \setlist* [ tabularnotes ] { #1 } }
921     }
922 },
923 enumitem-keys .value_required:n = true ,
924 enumitem-keys-para .code:n =
925 {
926     \hook_gput_code:nnn { begindocument } { . }
927     {
928         \bool_if:NT \c_@@_enumitem_loaded_bool
929         { \setlist* [ tabularnotes* ] { #1 } }
930     }
931 },
932 enumitem-keys-para .value_required:n = true ,
933 detect-duplicates .bool_set:N = \l_@@_notes_detect_duplicates_bool ,
934 detect-duplicates .default:n = true ,
935 unknown .code:n = \@@_error:n { Unknown~key~for~notes }
936 }
937 \keys_define:nn { NiceMatrix / delimiters }
938 {
939     max-width .bool_set:N = \l_@@_delimiters_max_width_bool ,
940     max-width .default:n = true ,
941     color .tl_set:N = \l_@@_delimiters_color_tl ,
942     color .value_required:n = true ,
943 }

```

We begin the construction of the major sets of keys (used by the different user commands and environments).

```

944 \keys_define:nn { NiceMatrix }
945 {
946     NiceMatrixOptions .inherit:n =
947     { NiceMatrix / Global } ,
948     NiceMatrixOptions / xdots .inherit:n = NiceMatrix / xdots ,
949     NiceMatrixOptions / rules .inherit:n = NiceMatrix / rules ,
950     NiceMatrixOptions / notes .inherit:n = NiceMatrix / notes ,
951     NiceMatrixOptions / sub-matrix .inherit:n = NiceMatrix / sub-matrix ,
952     SubMatrix / rules .inherit:n = NiceMatrix / rules ,
953     CodeAfter / xdots .inherit:n = NiceMatrix / xdots ,
954     CodeBefore / sub-matrix .inherit:n = NiceMatrix / sub-matrix ,
955     NiceMatrix .inherit:n =
956     {
957         NiceMatrix / Global ,
958         NiceMatrix / Env ,
959     } ,
960     NiceMatrix / xdots .inherit:n = NiceMatrix / xdots ,
961     NiceMatrix / rules .inherit:n = NiceMatrix / rules ,
962     NiceTabular .inherit:n =
963     {
964         NiceMatrix / Global ,
965         NiceMatrix / Env
966     } ,
967     NiceTabular / xdots .inherit:n = NiceMatrix / xdots ,
968     NiceTabular / rules .inherit:n = NiceMatrix / rules ,
969     NiceTabular / notes .inherit:n = NiceMatrix / notes ,
970     NiceArray .inherit:n =
971     {
972         NiceMatrix / Global ,
973         NiceMatrix / Env ,
974     } ,
975     NiceArray / xdots .inherit:n = NiceMatrix / xdots ,

```

```

976 NiceArray / rules .inherit:n = NiceMatrix / rules ,
977 pNiceArray .inherit:n =
978 {
979     NiceMatrix / Global ,
980     NiceMatrix / Env ,
981 } ,
982 pNiceArray / xdots .inherit:n = NiceMatrix / xdots ,
983 pNiceArray / rules .inherit:n = NiceMatrix / rules ,
984 }

```

We finalise the definition of the set of keys “NiceMatrix / NiceMatrixOptions” with the options specific to \NiceMatrixOptions.

```

985 \keys_define:nn { NiceMatrix / NiceMatrixOptions }
986 {
987     delimiters / color .tl_set:N = \l_@@_delimiters_color_tl ,
988     delimiters / color .value_required:n = true ,
989     delimiters / max-width .bool_set:N = \l_@@_delimiters_max_width_bool ,
990     delimiters / max-width .default:n = true ,
991     delimiters .code:n = \keys_set:nn { NiceMatrix / delimiters } { #1 } ,
992     delimiters .value_required:n = true ,
993     width .code:n = \dim_set:Nn \l_@@_width_dim { #1 } ,
994     width .value_required:n = true ,
995     last-col .code:n =
996         \tl_if_empty:nF { #1 }
997         { \@@_error:n { last-col-non-empty-for-NiceMatrixOptions } }
998         \int_zero:N \l_@@_last_col_int ,
999     small .bool_set:N = \l_@@_small_bool ,
1000     small .value_forbidden:n = true ,

```

With the option `renew-matrix`, the environment `{matrix}` of `amsmath` and its variants are redefined to behave like the environment `{NiceMatrix}` and its variants.

```

1001     renew-matrix .code:n = \@@_renew_matrix: ,
1002     renew-matrix .value_forbidden:n = true ,

```

The option `exterior-arraycolsep` will have effect only in `{NiceArray}` for those who want to have for `{NiceArray}` the same behaviour as `{array}`.

```

1003     exterior-arraycolsep .bool_set:N = \l_@@_exterior_arraycolsep_bool ,

```

If the option `columns-width` is used, all the columns will have the same width.

In `\NiceMatrixOptions`, the special value `auto` is not available.

```

1004     columns-width .code:n =
1005         \tl_if_eq:nnTF { #1 } { auto }
1006         { \@@_error:n { Option-auto-for-columns-width } }
1007         { \dim_set:Nn \l_@@_columns_width_dim { #1 } } ,

```

Usually, an error is raised when the user tries to give the same name to two distinct environments of `nicematrix` (these names are global and not local to the current TeX scope). However, the option `allow-duplicate-names` disables this feature.

```

1008     allow-duplicate-names .code:n =
1009         \@@_msg_redirect_name:nn { Duplicate-name } { none } ,
1010     allow-duplicate-names .value_forbidden:n = true ,
1011     notes .code:n = \keys_set:nn { NiceMatrix / notes } { #1 } ,
1012     notes .value_required:n = true ,
1013     sub-matrix .code:n = \keys_set:nn { NiceMatrix / sub-matrix } { #1 } ,
1014     sub-matrix .value_required:n = true ,
1015     matrix / columns-type .code:n =
1016         \@@_set_preamble:Nn \l_@@_columns_type_tl { #1 } ,
1017     matrix / columns-type .value_required:n = true ,
1018     caption-above .bool_set:N = \l_@@_caption_above_bool ,
1019     caption-above .default:n = true ,
1020     unknown .code:n = \@@_error:n { Unknown-key-for-NiceMatrixOptions }
1021 }

```


`\NiceMatrixOptions` is the command of the `nicematrix` package to fix options at the document level. The scope of these specifications is the current TeX group.

```
1022 \NewDocumentCommand \NiceMatrixOptions { m }
1023   { \keys_set:nn { NiceMatrix / NiceMatrixOptions } { #1 } }
```

We finalise the definition of the set of keys “NiceMatrix / NiceMatrix”. That set of keys will be used by `{NiceMatrix}`, `{pNiceMatrix}`, `{bNiceMatrix}`, etc.

```
1024 \keys_define:nn { NiceMatrix / NiceMatrix }
1025   {
1026     last-col .code:n = \tl_if_empty:nTF {#1}
1027       {
1028         \bool_set_true:N \l_@@_last_col_without_value_bool
1029         \int_set:Nn \l_@@_last_col_int { -1 }
1030       }
1031       { \int_set:Nn \l_@@_last_col_int { #1 } } ,
1032     columns-type .code:n = \@@_set_preamble:Nn \l_@@_columns_type_tl { #1 } ,
1033     columns-type .value_required:n = true ,
1034     l .meta:n = { columns-type = l } ,
1035     r .meta:n = { columns-type = r } ,
1036     delimiters / color .tl_set:N = \l_@@_delimiters_color_tl ,
1037     delimiters / color .value_required:n = true ,
1038     delimiters / max-width .bool_set:N = \l_@@_delimiters_max_width_bool ,
1039     delimiters / max-width .default:n = true ,
1040     delimiters .code:n = \keys_set:nn { NiceMatrix / delimiters } { #1 } ,
1041     delimiters .value_required:n = true ,
1042     small .bool_set:N = \l_@@_small_bool ,
1043     small .value_forbidden:n = true ,
1044     unknown .code:n = \@@_error:n { Unknown-key-for-NiceMatrix }
1045   }
```

We finalise the definition of the set of keys “NiceMatrix / NiceArray” with the options specific to `{NiceArray}`.

```
1046 \keys_define:nn { NiceMatrix / NiceArray }
1047   {
```

In the environments `{NiceArray}` and its variants, the option `last-col` must be used without value because the number of columns of the array is read from the preamble of the array.

```
1048     small .bool_set:N = \l_@@_small_bool ,
1049     small .value_forbidden:n = true ,
1050     last-col .code:n = \tl_if_empty:nF { #1 }
1051       { \@@_error:n { last-col-non-empty-for-NiceArray } }
1052       \int_zero:N \l_@@_last_col_int ,
1053     r .code:n = \@@_error:n { r-or-l-with-preamble } ,
1054     l .code:n = \@@_error:n { r-or-l-with-preamble } ,
1055     unknown .code:n = \@@_error:n { Unknown-key-for-NiceArray }
1056   }
1057 \keys_define:nn { NiceMatrix / pNiceArray }
1058   {
1059     first-col .code:n = \int_zero:N \l_@@_first_col_int ,
1060     last-col .code:n = \tl_if_empty:nF {#1}
1061       { \@@_error:n { last-col-non-empty-for-NiceArray } }
1062       \int_zero:N \l_@@_last_col_int ,
1063     first-row .code:n = \int_zero:N \l_@@_first_row_int ,
1064     delimiters / color .tl_set:N = \l_@@_delimiters_color_tl ,
1065     delimiters / color .value_required:n = true ,
1066     delimiters / max-width .bool_set:N = \l_@@_delimiters_max_width_bool ,
1067     delimiters / max-width .default:n = true ,
1068     delimiters .code:n = \keys_set:nn { NiceMatrix / delimiters } { #1 } ,
1069     delimiters .value_required:n = true ,
1070     small .bool_set:N = \l_@@_small_bool ,
1071     small .value_forbidden:n = true ,
```

```

1072   r .code:n = \@@_error:n { r-or-l-with-preamble } ,
1073   l .code:n = \@@_error:n { r-or-l-with-preamble } ,
1074   unknown .code:n = \@@_error:n { Unknown-key-for-NiceMatrix }
1075 }

```

We finalise the definition of the set of keys “NiceMatrix / NiceTabular” with the options specific to {NiceTabular}.

```

1076 \keys_define:nn { NiceMatrix / NiceTabular }
1077 {

```

The dimension width will be used if at least a column of type X is used. If there is no column of type X, an error will be raised.

```

1078   width .code:n = \dim_set:Nn \l_@@_width_dim { #1 }
1079   \bool_set_true:N \l_@@_width_used_bool ,
1080   width .value_required:n = true ,
1081   notes .code:n = \keys_set:nn { NiceMatrix / notes } { #1 } ,
1082   tabularnote .tl_gset:N = \g_@@_tabularnote_tl ,
1083   tabularnote .value_required:n = true ,
1084   caption .tl_set:N = \l_@@_caption_tl ,
1085   caption .value_required:n = true ,
1086   short-caption .tl_set:N = \l_@@_short_caption_tl ,
1087   short-caption .value_required:n = true ,
1088   label .tl_set:N = \l_@@_label_tl ,
1089   label .value_required:n = true ,
1090   last-col .code:n = \tl_if_empty:nF {#1}
1091   { \@@_error:n { last-col-non-empty-for-NiceArray } }
1092   \int_zero:N \l_@@_last_col_int ,
1093   r .code:n = \@@_error:n { r-or-l-with-preamble } ,
1094   l .code:n = \@@_error:n { r-or-l-with-preamble } ,
1095   unknown .code:n = \@@_error:n { Unknown-key-for-NiceTabular }
1096 }

```

Important code used by {NiceArrayWithDelims}

The pseudo-environment \@@_cell_begin:w–\@@_cell_end: will be used to format the cells of the array. In the code, the affectations are global because this pseudo-environment will be used in the cells of a \halign (via an environment {array}).

```

1097 \cs_new_protected:Npn \@@_cell_begin:w
1098 {

```

\g_@@_cell_after_hook_tl will be set during the composition of the box \l_@@_cell_box and will be used *after* the composition in order to modify that box.

```

1099   \tl_gclear:N \g_@@_cell_after_hook_tl

```

At the beginning of the cell, we link \CodeAfter to a command which do begin with \ (whereas the standard version of \CodeAfter does not).

```

1100   \cs_set_eq:NN \CodeAfter \@@_CodeAfter_i:

```

We increment \c@jCol, which is the counter of the columns.

```

1101   \int_gincr:N \c@jCol

```

Now, we increment the counter of the rows. We don’t do this incrementation in the \everycr because some packages, like arydshln, create special rows in the \halign that we don’t want to take into account.

```

1102   \int_compare:nNnT \c@jCol = 1
1103   { \int_compare:nNnT \l_@@_first_col_int = 1 \@@_begin_of_row: }

```

The content of the cell is composed in the box `\l_@@_cell_box`. The `\hbox_set_end:` corresponding to this `\hbox_set:Nw` will be in the `\@@_cell_end:` (and the potential `\c_math_toggle_token` also).

```

1104 \hbox_set:Nw \l_@@_cell_box
1105 \bool_if:NF \l_@@_NiceTabular_bool
1106 {
1107     \c_math_toggle_token
1108     \bool_if:NT \l_@@_small_bool \scriptstyle
1109 }
1110 \g_@@_row_style_tl

```

We will call *corners* of the matrix the cases which are at the intersection of the exterior rows and exterior columns (of course, the four corners doesn't always exist simultaneously).

The codes `\l_@@_code_for_first_row_tl` and *al* don't apply in the corners of the matrix.

```

1111 \int_compare:nNnTF \c@iRow = 0
1112 {
1113     \int_compare:nNnT \c@jCol > 0
1114     {
1115         \l_@@_code_for_first_row_tl
1116         \xglobal \colorlet { nicematrix-first-row } { . }
1117     }
1118 }
1119 {
1120     \int_compare:nNnT \c@iRow = \l_@@_last_row_int
1121     {
1122         \l_@@_code_for_last_row_tl
1123         \xglobal \colorlet { nicematrix-last-row } { . }
1124     }
1125 }
1126 }

```

The following macro `\@@_begin_of_row` is usually used in the cell number 1 of the row. However, when the key `first-col` is used, `\@@_begin_of_row` is executed in the cell number 0 of the row.

```

1127 \cs_new_protected:Npn \@@_begin_of_row:
1128 {
1129     \int_gincr:N \c@iRow
1130     \dim_gset_eq:NN \g_@@_dp_ante_last_row_dim \g_@@_dp_last_row_dim
1131     \dim_gset:Nn \g_@@_dp_last_row_dim { \box_dp:N \@arstrutbox }
1132     \dim_gset:Nn \g_@@_ht_last_row_dim { \box_ht:N \@arstrutbox }
1133     \pgfpicture
1134     \pgfrememberpicturepositiononpagetrue
1135     \pgfcoordinate
1136     { \@@_env: - row - \int_use:N \c@iRow - base }
1137     { \pgfpoint \c_zero_dim { 0.5 \arrayrulewidth } }
1138     \str_if_empty:NF \l_@@_name_str
1139     {
1140         \pgfnodealias
1141         { \l_@@_name_str - row - \int_use:N \c@iRow - base }
1142         { \@@_env: - row - \int_use:N \c@iRow - base }
1143     }
1144     \endpgfpicture
1145 }

```

Remark: If the key `recreate-cell-nodes` of the `\CodeBefore` is used, then we will add some lines to that command.

The following code is used in each cell of the array. It actualises quantities that, at the end of the array, will give informations about the vertical dimension of the two first rows and the two last rows. If the user uses the `last-row`, some lines of code will be dynamically added to this command.

```

1146 \cs_new_protected:Npn \@@_update_for_first_and_last_row:
1147 {
1148     \int_compare:nNnTF \c@iRow = 0

```

```

1149 {
1150   \dim_gset:Nn \g_@@_dp_row_zero_dim
1151   { \dim_max:nn \g_@@_dp_row_zero_dim { \box_dp:N \l_@@_cell_box } }
1152   \dim_gset:Nn \g_@@_ht_row_zero_dim
1153   { \dim_max:nn \g_@@_ht_row_zero_dim { \box_ht:N \l_@@_cell_box } }
1154 }
1155 {
1156   \int_compare:nNnT \c@iRow = 1
1157   {
1158     \dim_gset:Nn \g_@@_ht_row_one_dim
1159     { \dim_max:nn \g_@@_ht_row_one_dim { \box_ht:N \l_@@_cell_box } }
1160   }
1161 }
1162 }
1163 \cs_new_protected:Npn \@@_rotate_cell_box:
1164 {
1165   \box_rotate:Nn \l_@@_cell_box { 90 }
1166   \int_compare:nNnT \c@iRow = \l_@@_last_row_int
1167   {
1168     \vbox_set_top:Nn \l_@@_cell_box
1169     {
1170       \vbox_to_zero:n { }
1171       \skip_vertical:n { - \box_ht:N \@arstrutbox + 0.8 ex }
1172       \box_use:N \l_@@_cell_box
1173     }
1174   }
1175   \bool_gset_false:N \g_@@_rotate_bool
1176 }
1177 \cs_new_protected:Npn \@@_adjust_size_box:
1178 {
1179   \dim_compare:nNnT \g_@@_blocks_wd_dim > \c_zero_dim
1180   {
1181     \box_set_wd:Nn \l_@@_cell_box
1182     { \dim_max:nn { \box_wd:N \l_@@_cell_box } \g_@@_blocks_wd_dim }
1183     \dim_gzero:N \g_@@_blocks_wd_dim
1184   }
1185   \dim_compare:nNnT \g_@@_blocks_dp_dim > \c_zero_dim
1186   {
1187     \box_set_dp:Nn \l_@@_cell_box
1188     { \dim_max:nn { \box_dp:N \l_@@_cell_box } \g_@@_blocks_dp_dim }
1189     \dim_gzero:N \g_@@_blocks_dp_dim
1190   }
1191   \dim_compare:nNnT \g_@@_blocks_ht_dim > \c_zero_dim
1192   {
1193     \box_set_ht:Nn \l_@@_cell_box
1194     { \dim_max:nn { \box_ht:N \l_@@_cell_box } \g_@@_blocks_ht_dim }
1195     \dim_gzero:N \g_@@_blocks_ht_dim
1196   }
1197 }
1198 \cs_new_protected:Npn \@@_cell_end:
1199 {
1200   \@@_math_toggle_token:
1201   \hbox_set_end:

```

The token list `\g_@@_cell_after_hook_tl` is (potentially) set during the composition of the box `\l_@@_cell_box` and is used now *after* the composition in order to modify that box.

```

1202   \g_@@_cell_after_hook_tl
1203   \bool_if:NT \g_@@_rotate_bool \@@_rotate_cell_box:
1204   \@@_adjust_size_box:
1205   \box_set_ht:Nn \l_@@_cell_box
1206   { \box_ht:N \l_@@_cell_box + \l_@@_cell_space_top_limit_dim }
1207   \box_set_dp:Nn \l_@@_cell_box
1208   { \box_dp:N \l_@@_cell_box + \l_@@_cell_space_bottom_limit_dim }

```

We want to compute in `\g_@@_max_cell_width_dim` the width of the widest cell of the array (except the cells of the “first column” and the “last column”).

```
1209 \dim_gset:Nn \g_@@_max_cell_width_dim
1210 { \dim_max:nn \g_@@_max_cell_width_dim { \box_wd:N \l_@@_cell_box } }
```

The following computations are for the “first row” and the “last row”.

```
1211 \@@_update_for_first_and_last_row:
```

If the cell is empty, or may be considered as if, we must not create the PGF node, for two reasons:

- it’s a waste of time since such a node would be rather pointless;
- we test the existence of these nodes in order to determine whether a cell is empty when we search the extremities of a dotted line.

However, it’s very difficult to determine whether a cell is empty. Up to now we use the following technic:

- for the columns of type p, m, b, V (of `varwidth`) or X, we test whether the cell is syntactically empty with `\@@_test_if_empty:` and `\@@_test_if_empty_for_S:`
- if the width of the box `\l_@@_cell_box` (created with the content of the cell) is equal to zero, we consider the cell as empty (however, this is not perfect since the user may have used a `\rlap`, `\llap`, `\clap` or a `\mathclap` of `mathtools`).
- the cells with a command `\Ldots` or `\Cdots`, `\Vdots`, etc., should also be considered as empty; if `nullify-dots` is in force, there would be nothing to do (in this case the previous commands only write an instruction in a kind of `\CodeAfter`); however, if `nullify-dots` is not in force, a phantom of `\ldots`, `\cdots`, `\vdots` is inserted and its width is not equal to zero; that’s why these commands raise a boolean `\g_@@_empty_cell_bool` and we begin by testing this boolean.

```
1212 \bool_if:NTF \g_@@_empty_cell_bool
1213 { \box_use_drop:N \l_@@_cell_box }
1214 {
1215   \bool_lazy_or:nnTF
1216     \g_@@_not_empty_cell_bool
1217     { \dim_compare_p:nNn { \box_wd:N \l_@@_cell_box } > \c_zero_dim }
1218     \@@_node_for_cell:
1219     { \box_use_drop:N \l_@@_cell_box }
1220 }
1221 \int_gset:Nn \g_@@_col_total_int { \int_max:nn \g_@@_col_total_int \c@jCol }
1222 \bool_gset_false:N \g_@@_empty_cell_bool
1223 \bool_gset_false:N \g_@@_not_empty_cell_bool
1224 }
```

The following command creates the PGF name of the node with, of course, `\l_@@_cell_box` as the content.

```
1225 \cs_new_protected:Npn \@@_node_for_cell:
1226 {
1227   \pgfpicture
1228   \pgfsetbaseline \c_zero_dim
1229   \pgfrememberpicturepositiononpagetrue
1230   \pgfset
1231   {
1232     inner~sep = \c_zero_dim ,
1233     minimum~width = \c_zero_dim
1234   }
1235   \pgfnode
1236   { rectangle }
1237   { base }
1238   {
```

The following instruction `\set@color` has been added on 2022/10/06. It's necessary only with XeLaTeX and not with the other engines (we don't know why).

```

1239     \set@color
1240     \box_use_drop:N \l_@@_cell_box
1241   }
1242   { \@@_env: - \int_use:N \c@iRow - \int_use:N \c@jCol }
1243   { }
1244   \str_if_empty:NF \l_@@_name_str
1245   {
1246     \pgfnodealias
1247     { \l_@@_name_str - \int_use:N \c@iRow - \int_use:N \c@jCol }
1248     { \@@_env: - \int_use:N \c@iRow - \int_use:N \c@jCol }
1249   }
1250   \endpgfpicture
1251 }

```

As its name says, the following command is a patch for the command `\@@_node_for_cell:`. This patch will be appended on the left of `\@@_node_for_the_cell:` when the construction of the cell nodes (of the form (i-j)) in the `\CodeBefore` is required.

```

1252 \cs_new_protected:Npn \@@_patch_node_for_cell:n #1
1253 {
1254   \cs_new_protected:Npn \@@_patch_node_for_cell:
1255   {
1256     \hbox_set:Nn \l_@@_cell_box
1257     {
1258       \box_move_up:nn { \box_ht:N \l_@@_cell_box}
1259       \hbox_overlap_left:n
1260       {
1261         \pgfsys@markposition
1262         { \@@_env: - \int_use:N \c@iRow - \int_use:N \c@jCol - NW }

```

I don't know why the following adjustment is needed when the compilation is done with XeLaTeX or with the classical way `latex`, `divps`, `ps2pdf` (or Adobe Distiller). However, it seems to work.

```

1263         #1
1264       }
1265       \box_use:N \l_@@_cell_box
1266       \box_move_down:nn { \box_dp:N \l_@@_cell_box }
1267       \hbox_overlap_left:n
1268       {
1269         \pgfsys@markposition
1270         { \@@_env: - \int_use:N \c@iRow - \int_use:N \c@jCol - SE }
1271       }
1272     }
1273   }
1274 }
1275 }

```

We have no explanation for the different behaviour between the TeX engines...

```

1276 \bool_lazy_or:nnTF \sys_if_engine_xetex_p: \sys_if_output_dvi_p:
1277 {
1278   \@@_patch_node_for_cell:n
1279   { \skip_horizontal:n { 0.5 \box_wd:N \l_@@_cell_box } }
1280 }
1281 { \@@_patch_node_for_cell:n { } }

```

The second argument of the following command `\@@_instruction_of_type:nnn` defined below is the type of the instruction (`Cdots`, `Vdots`, `Ddots`, etc.). The third argument is the list of options. This command writes in the corresponding `\g_@@_type_lines_tl` the instruction which will actually draw the line after the construction of the matrix.

For example, for the following matrix,

```

\begin{pNiceMatrix}
1 & 2 & 3 & 4 \\
5 & \Cdots & & 6 \\
7 & \Cdots & [color=red]
\end{pNiceMatrix}

```

$$\begin{pmatrix} 1 & 2 & 3 & 4 \\ 5 & \cdots & & 6 \\ 7 & \cdots & & \end{pmatrix}$$

the content of `\g_@@_Cdots_lines_tl` will be:

```

\@@_draw_Cdots:nnn {2}{2}{}
\@@_draw_Cdots:nnn {3}{2}{color=red}

```

The first argument is a boolean which indicates whether you must put the instruction on the left or on the right on the list of instructions.

```

1282 \cs_new_protected:Npn \@@_instruction_of_type:nnn #1 #2 #3
1283 {
1284   \bool_if:nTF { #1 } \tl_gput_left:cx \tl_gput_right:cx
1285     { \g_@@_ #2 _ lines _ tl }
1286     {
1287       \use:c { @@ _ draw _ #2 : nnn }
1288       { \int_use:N \c_iRow }
1289       { \int_use:N \c_jCol }
1290       { \exp_not:n { #3 } }
1291     }
1292 }
1293 \cs_new_protected:Npn \@@_array:n
1294 {
1295   \bool_if:NTF \l_@@_NiceTabular_bool
1296     { \dim_set_eq:NN \col@sep \tabcolsep }
1297     { \dim_set_eq:NN \col@sep \arraycolsep }
1298   \dim_compare:nNnTF \l_@@_tabular_width_dim = \c_zero_dim
1299     { \cs_set_nopar:Npn \@halignto { } }
1300     { \cs_set_nopar:Npx \@halignto { to \dim_use:N \l_@@_tabular_width_dim } }

```

If `colortbl` is loaded, `\@tabarray` has been redefined to incorporate `\CT@start`.

```

1301   \@tabarray
\l_@@_baseline_tl may have the value t, c or b. However, if the value is b, we compose the
\array (of array) with the option t and the right translation will be done further. Remark that
\str_if_eq:VnTF is fully expandable and you need something fully expandable here.
1302   [ \str_if_eq:VnTF \l_@@_baseline_tl c c t ]
1303 }
1304 \cs_generate_variant:Nn \@@_array:n { V }

```

We keep in memory the standard version of `\ialign` because we will redefine `\ialign` in the environment `{NiceArrayWithDelims}` but restore the standard version for use in the cells of the array.

```

1305 \cs_set_eq:NN \@@_old_ialign: \ialign

```

The following command creates a row node (and not a row of nodes!).

```

1306 \cs_new_protected:Npn \@@_create_row_node:
1307 {
1308   \int_compare:nNnT \c_iRow > \g_@@_last_row_node_int
1309     {
1310       \int_gset_eq:NN \g_@@_last_row_node_int \c_iRow
1311       \@@_create_row_node_i:
1312     }
1313 }
1314 \cs_new_protected:Npn \@@_create_row_node_i:
1315 {

```

The `\hbox:n` (or `\hbox`) is mandatory.

```

1316   \hbox
1317   {
1318     \bool_if:NT \l_@@_code_before_bool
1319     {

```

```

1320         \vtop
1321         {
1322             \skip_vertical:N 0.5\arrayrulewidth
1323             \pgfsys@markposition
1324             { \@@_env: - row - \int_eval:n { \c@iRow + 1 } }
1325             \skip_vertical:N -0.5\arrayrulewidth
1326         }
1327     }
1328     \pgfpicture
1329     \pgfrememberpicturepositiononpagetrue
1330     \pgfcoordinate { \@@_env: - row - \int_eval:n { \c@iRow + 1 } }
1331     { \pgfpoint \c_zero_dim { - 0.5 \arrayrulewidth } }
1332     \str_if_empty:NF \l_@@_name_str
1333     {
1334         \pgfnodealias
1335         { \l_@@_name_str - row - \int_eval:n { \c@iRow + 1 } }
1336         { \@@_env: - row - \int_eval:n { \c@iRow + 1 } }
1337     }
1338     \endpgfpicture
1339 }
1340 }

```

The following must *not* be protected because it begins with `\noalign`.

```

1341 \cs_new:Npn \@@_everycr: { \noalign { \@@_everycr_i: } }
1342 \cs_new_protected:Npn \@@_everycr_i:
1343 {
1344     \int_gzero:N \c@jCol
1345     \bool_gset_false:N \g_@@_after_col_zero_bool
1346     \bool_if:NF \g_@@_row_of_col_done_bool
1347     {
1348         \@@_create_row_node:

```

We don't draw now the rules of the key `hlines` (or `hvlines`) but we reserve the vertical space for theses rules (the rules will be drawn by PGF).

```

1349     \tl_if_empty:NF \l_@@_hlines_clist
1350     {
1351         \tl_if_eq:NnF \l_@@_hlines_clist { all }
1352         {
1353             \exp_args:NNx
1354             \clist_if_in:NnT
1355             \l_@@_hlines_clist
1356             { \int_eval:n { \c@iRow + 1 } }
1357         }
1358     }

```

The counter `\c@iRow` has the value `-1` only if there is a “first row” and that we are before that “first row”, i.e. just before the beginning of the array.

```

1359     \int_compare:nNnT \c@iRow > { -1 }
1360     {
1361         \int_compare:nNnF \c@iRow = \l_@@_last_row_int

```

The command `\CT@arc@` is a command of `colortbl` which sets the color of the rules in the array. The package `nicematrix` uses it even if `colortbl` is not loaded. We use a TeX group in order to limit the scope of `\CT@arc@`.

```

1362         { \hrule height \arrayrulewidth width \c_zero_dim }
1363     }
1364 }
1365 }
1366 }
1367 }

```

The command `\@@_newcolumntype` is the command `\newcolumntype` of `array` without the warnings for redefinitions of columns types (we will use it to redefine the columns types `w` and `W`).


```

1368 \cs_set_protected:Npn \@@_newcolumnntype #1
1369 {
1370   \cs_set:cpn { NC @ find @ #1 } ##1 #1 { \NC@ { ##1 } }
1371   \peek_meaning:NTF [
1372     { \newcol@ #1 }
1373     { \newcol@ #1 [ 0 ] }
1374   }

```

When the key `renew-dots` is used, the following code will be executed.

```

1375 \cs_set_protected:Npn \@@_renew_dots:
1376 {
1377   \cs_set_eq:NN \ldots \@@_Ldots
1378   \cs_set_eq:NN \cdots \@@_Cdots
1379   \cs_set_eq:NN \vdots \@@_Vdots
1380   \cs_set_eq:NN \ddots \@@_Ddots
1381   \cs_set_eq:NN \iddots \@@_Iddots
1382   \cs_set_eq:NN \dots \@@_Ldots
1383   \cs_set_eq:NN \hdotsfor \@@_Hdotsfor:
1384 }

```

When the key `colortbl-like` is used, the following code will be executed.

```

1385 \cs_new_protected:Npn \@@_colortbl_like:
1386 {
1387   \cs_set_eq:NN \cellcolor \@@_cellcolor_tabular
1388   \cs_set_eq:NN \rowcolor \@@_rowcolor_tabular
1389   \cs_set_eq:NN \columncolor \@@_columncolor_preamble
1390 }

```

The following code `\@@_pre_array_ii:` is used in `{NiceArrayWithDelims}`. It exists as a standalone macro only for legibility.

```

1391 \cs_new_protected:Npn \@@_pre_array_ii:
1392 {

```

The number of letters `X` in the preamble of the array.

```

1393   \int_gzero:N \g_@@_total_X_weight_int
1394   \@@_expand_clist:N \l_@@_hlines_clist
1395   \@@_expand_clist:N \l_@@_vlines_clist

```

If `booktabs` is loaded, we have to patch the macro `\@BTnormal` which is a macro of `booktabs`. The macro `\@BTnormal` draws an horizontal rule but it occurs after a vertical skip done by a low level TeX command. When this macro `\@BTnormal` occurs, the `row` node has yet been inserted by `nicematrix` *before* the vertical skip (and thus, at a wrong place). That why we decide to create a new `row` node (for the same row). We patch the macro `\@BTnormal` to create this `row` node. This new `row` node will overwrite the previous definition of that `row` node and we have managed to avoid the error messages of that redefinition ⁶⁷.

```

1396   \bool_if:NT \c_@@_booktabs_loaded_bool
1397   { \tl_put_left:Nn \@BTnormal \@@_create_row_node_i: }
1398   \box_clear_new:N \l_@@_cell_box
1399   \normalbaselines

```

If the option `small` is used, we have to do some tuning. In particular, we change the value of `\arraystretch` (this parameter is used in the construction of `\@arstrutbox` in the beginning of `{array}`).

```

1400   \bool_if:NT \l_@@_small_bool
1401   {
1402     \cs_set_nopar:Npn \arraystretch { 0.47 }
1403     \dim_set:Nn \arraycolsep { 1.45 pt }
1404   }

```

⁶⁷cf. `\nicematrix@redefine@check@rerun`

```

1405 \bool_if:NT \g_@@_recreate_cell_nodes_bool
1406 {
1407     \tl_put_right:Nn \@@_begin_of_row:
1408     {
1409         \pgfsys@markposition
1410         { \@@_env: - row - \int_use:N \c@iRow - base }
1411     }
1412 }

```

The environment `{array}` uses internally the command `\ialign`. We change the definition of `\ialign` for several reasons. In particular, `\ialign` sets `\everycr` to `{ }` and we *need* to have to change the value of `\everycr`.

```

1413 \cs_set_nopar:Npn \ialign
1414 {
1415     \bool_if:NTF \l_@@_colortbl_loaded_bool
1416     {
1417         \CT@everycr
1418         {
1419             \noalign { \cs_gset_eq:NN \CT@row@color \prg_do_nothing: }
1420             \@@_everycr:
1421         }
1422     }
1423     { \everycr { \@@_everycr: } }
1424     \tabskip = \c_zero_skip

```

The box `\@arstrutbox` is a box constructed in the beginning of the environment `{array}`. The construction of that box takes into account the current value of `\arraystretch`⁶⁸ and `\extrarowheight` (of `array`). That box is inserted (via `\@arstrut`) in the beginning of each row of the array. That's why we use the dimensions of that box to initialize the variables which will be the dimensions of the potential first and last row of the environment. This initialization must be done after the creation of `\@arstrutbox` and that's why we do it in the `\ialign`.

```

1425 \dim_gzero_new:N \g_@@_dp_row_zero_dim
1426 \dim_gset:Nn \g_@@_dp_row_zero_dim { \box_dp:N \@arstrutbox }
1427 \dim_gzero_new:N \g_@@_ht_row_zero_dim
1428 \dim_gset:Nn \g_@@_ht_row_zero_dim { \box_ht:N \@arstrutbox }
1429 \dim_gzero_new:N \g_@@_ht_row_one_dim
1430 \dim_gset:Nn \g_@@_ht_row_one_dim { \box_ht:N \@arstrutbox }
1431 \dim_gzero_new:N \g_@@_dp_ante_last_row_dim
1432 \dim_gzero_new:N \g_@@_ht_last_row_dim
1433 \dim_gset:Nn \g_@@_ht_last_row_dim { \box_ht:N \@arstrutbox }
1434 \dim_gzero_new:N \g_@@_dp_last_row_dim
1435 \dim_gset:Nn \g_@@_dp_last_row_dim { \box_dp:N \@arstrutbox }

```

After its first use, the definition of `\ialign` will revert automatically to its default definition. With this programming, we will have, in the cells of the array, a clean version of `\ialign`.

```

1436 \cs_set_eq:NN \ialign \@@_old_ialign:
1437 \halign
1438 }

```

We keep in memory the old versions of `\ldots`, `\cdots`, etc. only because we use them inside `\phantom` commands in order that the new commands `\Ldots`, `\Cdots`, etc. give the same spacing (except when the option `nullify-dots` is used).

```

1439 \cs_set_eq:NN \@@_old_ldots \ldots
1440 \cs_set_eq:NN \@@_old_cdots \cdots
1441 \cs_set_eq:NN \@@_old_vdots \vdots
1442 \cs_set_eq:NN \@@_old_ddots \ddots
1443 \cs_set_eq:NN \@@_old_iddots \iddots
1444 \bool_if:NTF \l_@@_standard_cline_bool
1445 { \cs_set_eq:NN \cline \@@_standard_cline }

```

⁶⁸The option `small` of `nicematrix` changes (among others) the value of `\arraystretch`. This is done, of course, before the call of `{array}`.

```

1446 { \cs_set_eq:NN \cline \@@_cline }
1447 \cs_set_eq:NN \ldots \@@_ldots
1448 \cs_set_eq:NN \cdots \@@_cdots
1449 \cs_set_eq:NN \vdots \@@_vdots
1450 \cs_set_eq:NN \ddots \@@_ddots
1451 \cs_set_eq:NN \iddots \@@_iddots
1452 \cs_set_eq:NN \hline \@@_hline:
1453 \cs_set_eq:NN \hspace \@@_hspace:
1454 \cs_set_eq:NN \hdotsfor \@@_hdotsfor:
1455 \cs_set_eq:NN \vdotsfor \@@_vdotsfor:
1456 \cs_set_eq:NN \Block \@@_Block:
1457 \cs_set_eq:NN \rotate \@@_rotate:
1458 \cs_set_eq:NN \OnlyMainNiceMatrix \@@_OnlyMainNiceMatrix:n
1459 \cs_set_eq:NN \dotfill \@@_old_dotfill:
1460 \cs_set_eq:NN \CodeAfter \@@_CodeAfter:
1461 \cs_set_eq:NN \diagbox \@@_diagbox:nn
1462 \cs_set_eq:NN \NotEmpty \@@_NotEmpty:
1463 \cs_set_eq:NN \RowStyle \@@_RowStyle:n
1464 \seq_map_inline:Nn \l_@@_custom_line_commands_seq
1465 { \cs_set_eq:cc { ##1 } { nicematrix - ##1 } }
1466 \bool_if:NT \l_@@_colortbl_like_bool \@@_colortbl_like:
1467 \bool_if:NT \l_@@_renew_dots_bool \@@_renew_dots:

```

We redefine `\multicolumn` and, since we want `\multicolumn` to be available in the potential environments `{tabular}` nested in the environments of `nicematrix`, we patch `{tabular}` to go back to the original definition.

```

1468 \cs_set_eq:NN \multicolumn \@@_multicolumn:nnn
1469 \hook_gput_code:nnn { env / tabular / begin } { . }
1470 { \cs_set_eq:NN \multicolumn \@@_old_multicolumn }

```

If there is one or several commands `\tablarnote` in the caption specified by the key `caption` and if that caption has to be composed above the tabular, we have now that information because it has been written in the aux file at a previous run. We use that information to start counting the tabular notes in the main array at the right value (that remember that the caption will be composed *after* the array!).

```

1471 \tl_if_exist:NT \l_@@_note_in_caption_tl
1472 {
1473   \tl_if_empty:NF \l_@@_note_in_caption_tl
1474   {
1475     \int_set_eq:NN \l_@@_note_in_caption_int
1476     { \l_@@_note_in_caption_tl }
1477     \int_gset:Nn \c@tablarnote { \l_@@_note_in_caption_tl }
1478   }
1479 }

```

The sequence `\g_@@_multicolumn_cells_seq` will contain the list of the cells of the array where a command `\multicolumn{n}{...}{...}` with $n > 1$ is issued. In `\g_@@_multicolumn_sizes_seq`, the “sizes” (that is to say the values of n) correspondent will be stored. These lists will be used for the creation of the “medium nodes” (if they are created).

```

1480 \seq_gclear:N \g_@@_multicolumn_cells_seq
1481 \seq_gclear:N \g_@@_multicolumn_sizes_seq

```

The counter `\c@iRow` will be used to count the rows of the array (its incrementation will be in the first cell of the row).

```

1482 \int_gset:Nn \c@iRow { \l_@@_first_row_int - 1 }

```

At the end of the environment `{array}`, `\c@iRow` will be the total number de rows.

`\g_@@_row_total_int` will be the number or rows excepted the last row (if `\l_@@_last_row_bool` has been raised with the option `last-row`).

```

1483 \int_gzero_new:N \g_@@_row_total_int

```

The counter `\c@jCol` will be used to count the columns of the array. Since we want to know the total number of columns of the matrix, we also create a counter `\g_@@_col_total_int`. These counters are updated in the command `\@@_cell_begin:w` executed at the beginning of each cell.

```

1484 \int_gzero_new:N \g_@@_col_total_int

```

```

1485 \cs_set_eq:NN \@ifnextchar \new@ifnextchar
1486 \@_renew_NC@rewrite@S:
1487 \bool_gset_false:N \g_@@_last_col_found_bool

```

During the construction of the array, the instructions `\Cdots`, `\Ldots`, etc. will be written in token lists `\g_@@_Cdots_lines_tl`, etc. which will be executed after the construction of the array.

```

1488 \tl_gclear_new:N \g_@@_Cdots_lines_tl
1489 \tl_gclear_new:N \g_@@_Ldots_lines_tl
1490 \tl_gclear_new:N \g_@@_Vdots_lines_tl
1491 \tl_gclear_new:N \g_@@_Ddots_lines_tl
1492 \tl_gclear_new:N \g_@@_Iddots_lines_tl
1493 \tl_gclear_new:N \g_@@_HVDotsfor_lines_tl

1494 \tl_gclear:N \g_nicematrix_code_before_tl
1495 \tl_gclear:N \g_@@_pre_code_before_tl
1496 }

```

This is the end of `\@@_pre_array_ii:`.

The command `\@@_pre_array:` will be executed after analyse of the keys of the environment.

```

1497 \cs_new_protected:Npn \@_pre_array:
1498 {
1499 \cs_if_exist:NT \theiRow { \int_set_eq:NN \l_@@_old_iRow_int \c@iRow }
1500 \int_gzero_new:N \c@iRow
1501 \cs_if_exist:NT \thejCol { \int_set_eq:NN \l_@@_old_jCol_int \c@jCol }
1502 \int_gzero_new:N \c@jCol

```

We recall that `\l_@@_last_row_int` and `\l_@@_last_column_int` are *not* the numbers of the last row and last column of the array. There are only the values of the keys `last-row` and `last-column` (maybe the user has provided erroneous values). The meaning of that counters does not change during the environment of `nicematrix`. There is only a slight adjustment: if the user have used one of those keys without value, we provide now the right value as read on the `aux` file (of course, it's possible only after the first compilation).

```

1503 \int_compare:nNnT \l_@@_last_row_int = { -1 }
1504 {
1505 \bool_set_true:N \l_@@_last_row_without_value_bool
1506 \bool_if:NT \g_@@_aux_found_bool
1507 { \int_set:Nn \l_@@_last_row_int { \seq_item:Nn \g_@@_size_seq 3 } }
1508 }
1509 \int_compare:nNnT \l_@@_last_col_int = { -1 }
1510 {
1511 \bool_if:NT \g_@@_aux_found_bool
1512 { \int_set:Nn \l_@@_last_col_int { \seq_item:Nn \g_@@_size_seq 6 } }
1513 }

```

If there is an exterior row, we patch a command used in `\@@_cell_begin:w` in order to keep track of some dimensions needed to the construction of that “last row”.

```

1514 \int_compare:nNnT \l_@@_last_row_int > { -2 }
1515 {
1516 \tl_put_right:Nn \@_update_for_first_and_last_row:
1517 {
1518 \dim_gset:Nn \g_@@_ht_last_row_dim
1519 { \dim_max:nn \g_@@_ht_last_row_dim { \box_ht:N \l_@@_cell_box } }
1520 \dim_gset:Nn \g_@@_dp_last_row_dim
1521 { \dim_max:nn \g_@@_dp_last_row_dim { \box_dp:N \l_@@_cell_box } }
1522 }
1523 }

1524 \seq_gclear:N \g_@@_cols_vlism_seq
1525 \seq_gclear:N \g_@@_submatrix_seq

```

Now the `\CodeBefore`.

```
1526 \bool_if:NT \l_@@_code_before_bool \@@_exec_code_before:
```

The value of `\g_@@_pos_of_blocks_seq` has been written on the `aux` file and loaded before the (potential) execution of the `\CodeBefore`. Now, we clear that variable because it will be reconstructed during the creation of the array.

```
1527 \seq_gclear:N \g_@@_pos_of_blocks_seq
```

Idem for other sequences written on the `aux` file.

```
1528 \seq_gclear_new:N \g_@@_multicolumn_cells_seq
```

```
1529 \seq_gclear_new:N \g_@@_multicolumn_sizes_seq
```

The command `\create_row_node:` will create a row-node (and not a row of nodes!). However, at the end of the array we construct a “false row” (for the col-nodes) and it interferes with the construction of the last row-node of the array. We don’t want to create such row-node twice (to avoid warnings or, maybe, errors). That’s why the command `\@@_create_row_node:` will use the following counter to avoid such construction.

```
1530 \int_gset:Nn \g_@@_last_row_node_int { -2 }
```

The value `-2` is important.

The code in `\@@_pre_array_ii:` is used only here.

```
1531 \@@_pre_array_ii:
```

The array will be composed in a box (named `\l_@@_the_array_box`) because we have to do manipulations concerning the potential exterior rows.

```
1532 \box_clear_new:N \l_@@_the_array_box
```

We compute the width of both delimiters. We remind that, when the environment `{NiceArray}` is used, it’s possible to specify the delimiters in the preamble (eg `[ccc]`).

```
1533 \dim_zero_new:N \l_@@_left_delim_dim
1534 \dim_zero_new:N \l_@@_right_delim_dim
1535 \bool_if:NTF \g_@@_NiceArray_bool
1536 {
1537   \dim_gset:Nn \l_@@_left_delim_dim { 2 \arraycolsep }
1538   \dim_gset:Nn \l_@@_right_delim_dim { 2 \arraycolsep }
1539 }
1540 {
```

The command `\bBigg@` is a command of `amsmath`.

```
1541 \hbox_set:Nn \l_tmpa_box { $ \bBigg@ 5 \g_@@_left_delim_tl $ }
1542 \dim_set:Nn \l_@@_left_delim_dim { \box_wd:N \l_tmpa_box }
1543 \hbox_set:Nn \l_tmpa_box { $ \bBigg@ 5 \g_@@_right_delim_tl $ }
1544 \dim_set:Nn \l_@@_right_delim_dim { \box_wd:N \l_tmpa_box }
1545 }
```

Here is the beginning of the box which will contain the array. The `\hbox_set_end:` corresponding to this `\hbox_set:Nw` will be in the second part of the environment (and the closing `\c_math_toggle_token` also).

```
1546 \hbox_set:Nw \l_@@_the_array_box
1547 \skip_horizontal:N \l_@@_left_margin_dim
1548 \skip_horizontal:N \l_@@_extra_left_margin_dim
1549 \c_math_toggle_token
1550 \bool_if:NTF \l_@@_light_syntax_bool
1551 { \use:c { @@-light-syntax } }
1552 { \use:c { @@-normal-syntax } }
1553 }
```

The following command `\@@_CodeBefore_Body:w` will be used when the keyword `\CodeBefore` is present at the beginning of the environment.

```
1554 \cs_new_protected_nopar:Npn \@@_CodeBefore_Body:w #1 \Body
1555 {
1556   \tl_gput_left:Nn \g_@@_pre_code_before_tl { #1 }
1557   \bool_set_true:N \l_@@_code_before_bool
```

We go on with `\@@_pre_array:` which will (among other) execute the `\CodeBefore` (specified in the key `code-before` or after the keyword `\CodeBefore`). By definition, the `\CodeBefore` must be executed before the body of the array...

```
1558   \@@_pre_array:
1559 }
```

The `\CodeBefore`

The following command will be executed if the `\CodeBefore` has to be actually executed.

```
1560 \cs_new_protected:Npn \@@_pre_code_before:
1561 {
```

First, we give values to the LaTeX counters `iRow` and `jCol`. We remind that, in the `\CodeBefore` (and in the `\CodeAfter`) they represent the numbers of rows and columns of the array (without the potential last row and last column). The value of `\g_@@_row_total_int` is the number of the last row (with potentially a last exterior row) and `\g_@@_col_total_int` is the number of the last column (with potentially a last exterior column).

```
1562   \int_set:Nn \c@iRow { \seq_item:Nn \g_@@_size_seq 2 }
1563   \int_set:Nn \c@jCol { \seq_item:Nn \g_@@_size_seq 5 }
1564   \int_set_eq:NN \g_@@_row_total_int { \seq_item:Nn \g_@@_size_seq 3 }
1565   \int_set_eq:NN \g_@@_col_total_int { \seq_item:Nn \g_@@_size_seq 6 }
```

Now, we will create all the `col` nodes and `row` nodes with the informations written in the `aux` file. You use the technique described in the page 1229 of `pgfmanual.pdf`, version 3.1.4b.

```
1566   \pgfsys@markposition { \@@_env: - position }
1567   \pgfsys@getposition { \@@_env: - position } \@@_picture_position:
1568   \pgfpicture
1569   \pgf@relevantforpicturesizefalse
```

First, the recreation of the `row` nodes.

```
1570   \int_step_inline:nnn \l_@@_first_row_int { \g_@@_row_total_int + 1 }
1571   {
1572     \pgfsys@getposition { \@@_env: - row - ##1 } \@@_node_position:
1573     \pgfcoordinate { \@@_env: - row - ##1 }
1574     { \pgfpointdiff \@@_picture_position: \@@_node_position: }
1575   }
```

Now, the recreation of the `col` nodes.

```
1576   \int_step_inline:nnn \l_@@_first_col_int { \g_@@_col_total_int + 1 }
1577   {
1578     \pgfsys@getposition { \@@_env: - col - ##1 } \@@_node_position:
1579     \pgfcoordinate { \@@_env: - col - ##1 }
1580     { \pgfpointdiff \@@_picture_position: \@@_node_position: }
1581   }
```

Now, you recreate the diagonal nodes by using the `row` nodes and the `col` nodes.

```
1582   \@@_create_diag_nodes:
```

Now, the creation of the cell nodes (`i-j`), and, maybe also the “medium nodes” and the “large nodes”.

```
1583   \bool_if:NT \g_@@_recreate_cell_nodes_bool \@@_recreate_cell_nodes:
1584   \endpgfpicture
```

Now, the recreation of the nodes of the blocks *which have a name*.

```
1585   \@@_create_blocks_nodes:
```

```

1586 \bool_if:NT \c_@@_tikz_loaded_bool
1587 {
1588   \tikzset
1589   {
1590     every-picture / .style =
1591     { overlay , name-prefix = \@@_env: - }
1592   }
1593 }
1594 \cs_set_eq:NN \cellcolor \@@_cellcolor
1595 \cs_set_eq:NN \rectanglecolor \@@_rectanglecolor
1596 \cs_set_eq:NN \roundedrectanglecolor \@@_roundedrectanglecolor
1597 \cs_set_eq:NN \rowcolor \@@_rowcolor
1598 \cs_set_eq:NN \rowcolors \@@_rowcolors
1599 \cs_set_eq:NN \rowlistcolors \@@_rowlistcolors
1600 \cs_set_eq:NN \arraycolor \@@_arraycolor
1601 \cs_set_eq:NN \columncolor \@@_columncolor
1602 \cs_set_eq:NN \chessboardcolors \@@_chessboardcolors
1603 \cs_set_eq:NN \SubMatrix \@@_SubMatrix_in_code_before
1604 \cs_set_eq:NN \ShowCellNames \@@_ShowCellNames
1605 }

```

```

1606 \cs_new_protected:Npn \@@_exec_code_before:
1607 {
1608   \seq_gclear_new:N \g_@@_colors_seq
1609   \bool_gset_false:N \g_@@_recreate_cell_nodes_bool
1610   \group_begin:

```

We compose the `\CodeBefore` in math mode in order to nullify the spaces put by the user between instructions in the `\CodeBefore`.

```

1611 \bool_if:NT \l_@@_NiceTabular_bool \c_math_toggle_token

```

The following code is a security for the case the user has used `babel` with the option `spanish`: in that case, the characters `<` (de code ASCII 60) and `>` are activated and Tikz is not able to solve the problem (even with the Tikz library `babel`).

```

1612 \int_compare:nNtT { \char_value_catcode:n { 60 } } = { 13 }
1613 {
1614   \@@_rescan_for_spanish:N \g_@@_pre_code_before_tl
1615   \@@_rescan_for_spanish:N \l_@@_code_before_tl
1616 }

```

Here is the `\CodeBefore`. The construction is a bit complicated because `\g_@@_pre_code_before_tl` may begin with keys between square brackets. Moreover, after the analyze of those keys, we sometimes have to decide to do *not* execute the rest of `\g_@@_pre_code_before_tl` (when it is asked for the creation of cell nodes in the `\CodeBefore`). That's why we use a `\q_stop`: it will be used to discard the rest of `\g_@@_pre_code_before_tl`.

```

1617 \exp_last_unbraced:NV \@@_CodeBefore_keys:
1618 \g_@@_pre_code_before_tl

```

Now, all the cells which are specified to be colored by instructions in the `\CodeBefore` will actually be colored. It's a two-stages mechanism because we want to draw all the cells with the same color at the same time to absolutely avoid thin white lines in some PDF viewers.

```

1619 \@@_actually_color:
1620 \l_@@_code_before_tl
1621 \q_stop
1622 \bool_if:NT \l_@@_NiceTabular_bool \c_math_toggle_token
1623 \group_end:
1624 \bool_if:NT \g_@@_recreate_cell_nodes_bool
1625 { \tl_put_left:Nn \@@_node_for_cell: \@@_patch_node_for_cell: }
1626 }

```

```

1627 \keys_define:nn { NiceMatrix / CodeBefore }
1628 {
1629     create-cell-nodes .bool_gset:N = \g_@@_recreate_cell_nodes_bool ,
1630     create-cell-nodes .default:n = true ,
1631     sub-matrix .code:n = \keys_set:nn { NiceMatrix / sub-matrix } { #1 } ,
1632     sub-matrix .value_required:n = true ,
1633     delimiters / color .tl_set:N = \l_@@_delimiters_color_tl ,
1634     delimiters / color .value_required:n = true ,
1635     unknown .code:n = \@@_error:n { Unknown-key-for-CodeBefore }
1636 }
1637 \NewDocumentCommand \@@_CodeBefore_keys: { 0 { } }
1638 {
1639     \keys_set:nn { NiceMatrix / CodeBefore } { #1 }
1640     \@@_CodeBefore:w
1641 }

```

We have extracted the options of the keyword `\CodeBefore` in order to see whether the key `create-cell-nodes` has been used. Now, you can execute the rest of the `\CodeAfter`, excepted, of course, if we are in the first compilation.

```

1642 \cs_new_protected:Npn \@@_CodeBefore:w #1 \q_stop
1643 {
1644     \bool_if:NT \g_@@_aux_found_bool
1645     {
1646         \@@_pre_code_before:
1647         #1
1648     }
1649 }

```

By default, if the user uses the `\CodeBefore`, only the `col` nodes, `row` nodes and `diag` nodes are available in that `\CodeBefore`. With the key `create-cell-nodes`, the cell nodes, that is to say the nodes of the form $(i-j)$ (but not the extra nodes) are also available because those nodes also are recreated and that recreation is done by the following command.

```

1650 \cs_new_protected:Npn \@@_recreate_cell_nodes:
1651 {
1652     \int_step_inline:nnn \l_@@_first_row_int \g_@@_row_total_int
1653     {
1654         \pgfsys@getposition { \@@_env: - ##1 - base } \@@_node_position:
1655         \pgfcoordinate { \@@_env: - row - ##1 - base }
1656         { \pgfpointdiff \@@_picture_position: \@@_node_position: }
1657         \int_step_inline:nnn \l_@@_first_col_int \g_@@_col_total_int
1658         {
1659             \cs_if_exist:cT
1660             { pgf @ sys @ pdf @ mark @ pos @ \@@_env: - ##1 - #####1 - NW }
1661             {
1662                 \pgfsys@getposition
1663                 { \@@_env: - ##1 - #####1 - NW }
1664                 \@@_node_position:
1665                 \pgfsys@getposition
1666                 { \@@_env: - ##1 - #####1 - SE }
1667                 \@@_node_position_i:
1668                 \@@_pgf_rect_node:nnn
1669                 { \@@_env: - ##1 - #####1 }
1670                 { \pgfpointdiff \@@_picture_position: \@@_node_position: }
1671                 { \pgfpointdiff \@@_picture_position: \@@_node_position_i: }
1672             }
1673         }
1674     }
1675     \int_step_inline:nn \c@iRow
1676     {
1677         \pgfnodealias
1678         { \@@_env: - ##1 - last }

```



```

1679     { \@@_env: - ##1 - \int_use:N \c@jCol }
1680   }
1681   \int_step_inline:nn \c@jCol
1682   {
1683     \pgfnodealias
1684     { \@@_env: - last - ##1 }
1685     { \@@_env: - \int_use:N \c@iRow - ##1 }
1686   }
1687   \@@_create_extra_nodes:
1688 }

```

```

1689 \cs_new_protected:Npn \@@_create_blocks_nodes:
1690 {
1691   \pgfpicture
1692   \pgf@relevantforpicturesizefalse
1693   \pgfrememberpicturepositiononpagetrue
1694   \seq_map_inline:Nn \g_@@_pos_of_blocks_seq
1695   { \@@_create_one_block_node:nnnnn ##1 }
1696   \endpgfpicture
1697 }

```

The following command is called `\@@_create_one_block_node:nnnnn` but, in fact, it creates a node only if the last argument (#5) which is the name of the block, is not empty.⁶⁹

```

1698 \cs_new_protected:Npn \@@_create_one_block_node:nnnnn #1 #2 #3 #4 #5
1699 {
1700   \tl_if_empty:nF { #5 }
1701   {
1702     \@@_qpoint:n { col - #2 }
1703     \dim_set_eq:NN \l_tmpa_dim \pgf@x
1704     \@@_qpoint:n { #1 }
1705     \dim_set_eq:NN \l_tmpb_dim \pgf@y
1706     \@@_qpoint:n { col - \int_eval:n { #4 + 1 } }
1707     \dim_set_eq:NN \l_@@_tmpc_dim \pgf@x
1708     \@@_qpoint:n { \int_eval:n { #3 + 1 } }
1709     \dim_set_eq:NN \l_@@_tmpd_dim \pgf@y
1710     \@@_pgf_rect_node:nnnnn
1711     { \@@_env: - #5 }
1712     { \dim_use:N \l_tmpa_dim }
1713     { \dim_use:N \l_tmpb_dim }
1714     { \dim_use:N \l_@@_tmpc_dim }
1715     { \dim_use:N \l_@@_tmpd_dim }
1716   }
1717 }

```

```

1718 \cs_new_protected:Npn \@@_patch_for_revtext:
1719 {
1720   \cs_set_eq:NN \@addamp \@addamp@LaTeX
1721   \cs_set_eq:NN \insert@column \insert@column@array
1722   \cs_set_eq:NN \@classx \@classx@array
1723   \cs_set_eq:NN \@xarraycr \@xarraycr@array
1724   \cs_set_eq:NN \@arraycr \@arraycr@array
1725   \cs_set_eq:NN \@xargarraycr \@xargarraycr@array
1726   \cs_set_eq:NN \array \array@array
1727   \cs_set_eq:NN \@array \@array@array
1728   \cs_set_eq:NN \@tabular \@tabular@array
1729   \cs_set_eq:NN \@mkpream \@mkpream@array
1730   \cs_set_eq:NN \endarray \endarray@array
1731   \cs_set:Npn \@tabarray { \ifnextchar [ { \@array } { \@array [ c ] } }

```

⁶⁹Moreover, there is also in the list `\g_@@_pos_of_blocks_seq` the positions of the dotted lines (created by `\Cdots`, etc.) and, for these entries, there is, of course, no name (the fifth component is empty).

```

1732 \cs_set:Npn \endtabular { \endarray $\egroup} % $
1733 }

```

The environment {NiceArrayWithDelims}

```

1734 \NewDocumentEnvironment { NiceArrayWithDelims }
1735 { m m O { } m ! O { } t \CodeBefore }
1736 {
1737 \bool_if:NT \c_@@_revtex_bool \@@_patch_for_revtex:
1738 \@@_provide_pgfsyspdfmark:
1739 \bool_if:NT \c_@@_footnote_bool \savenotes

```

The aim of the following `\bgroup` (the corresponding `\egroup` is, of course, at the end of the environment) is to be able to put an exposant to a matrix in a mathematical formula.

```

1740 \bgroup

1741 \tl_gset:Nn \g_@@_left_delim_tl { #1 }
1742 \tl_gset:Nn \g_@@_right_delim_tl { #2 }
1743 \tl_gset:Nn \g_@@_preamble_tl { #4 }

1744 \int_gzero:N \g_@@_block_box_int
1745 \dim_zero:N \g_@@_width_last_col_dim
1746 \dim_zero:N \g_@@_width_first_col_dim
1747 \bool_gset_false:N \g_@@_row_of_col_done_bool
1748 \str_if_empty:NT \g_@@_name_env_str
1749 { \str_gset:Nn \g_@@_name_env_str { NiceArrayWithDelims } }
1750 \bool_if:NTF \l_@@_NiceTabular_bool
1751 \mode_leave_vertical:
1752 \@@_test_if_math_mode:
1753 \bool_if:NT \l_@@_in_env_bool { \@@_fatal:n { Yet~in~env } }
1754 \bool_set_true:N \l_@@_in_env_bool

```

The command `\CT@arc@` contains the instruction of color for the rules of the array⁷⁰. This command is used by `\CT@arc@` but we use it also for compatibility with `colortbl`. But we want also to be able to use color for the rules of the array when `colortbl` is *not* loaded. That's why we do the following instruction which is in the patch of the beginning of arrays done by `colortbl`. Of course, we restore the value of `\CT@arc@` at the end of our environment.

```

1755 \cs_gset_eq:NN \@@_old_CT@arc@ \CT@arc@

```

We deactivate Tikz externalization because we will use PGF pictures with the options `overlay` and `remember picture` (or equivalent forms). We deactivate with `\tikzexternaldisable` and not with `\tikzset{external/export=false}` which is *not* equivalent.

```

1756 \cs_if_exist:NT \tikz@library@external@loaded
1757 {
1758 \tikzexternaldisable
1759 \cs_if_exist:NT \ifstandalone
1760 { \tikzset { external / optimize = false } }
1761 }

```

We increment the counter `\g_@@_env_int` which counts the environments of the package.

```

1762 \int_gincr:N \g_@@_env_int
1763 \bool_if:NF \l_@@_block_auto_columns_width_bool
1764 { \dim_gzero_new:N \g_@@_max_cell_width_dim }

```

The sequence `\g_@@_blocks_seq` will contain the carateristics of the blocks (specified by `\Block`) of the array. The sequence `\g_@@_pos_of_blocks_seq` will contain only the position of the blocks (except the blocks with the key `hvlines`).

```

1765 \seq_gclear:N \g_@@_blocks_seq
1766 \seq_gclear:N \g_@@_pos_of_blocks_seq

```

⁷⁰e.g. `\color[rgb]{0.5,0.5,0}`

In fact, the sequence `\g_@@_pos_of_blocks_seq` will also contain the positions of the cells with a `\diagbox`.

```

1767 \seq_gclear:N \g_@@_pos_of_stroken_blocks_seq
1768 \seq_gclear:N \g_@@_pos_of_xdots_seq
1769 \tl_gclear_new:N \g_@@_code_before_tl
1770 \tl_gclear:N \g_@@_row_style_tl

```

We load all the informations written in the aux file during previous compilations corresponding to the current environment.

```

1771 \bool_gset_false:N \g_@@_aux_found_bool
1772 \tl_if_exist:cT { c_@@ _ \int_use:N \g_@@_env_int _ tl }
1773 {
1774   \bool_gset_true:N \g_@@_aux_found_bool
1775   \use:c { c_@@ _ \int_use:N \g_@@_env_int _ tl }
1776 }

```

Now, we prepare the token list for the instructions that we will have to write on the aux file at the end of the environment.

```

1777 \tl_gclear:N \g_@@_aux_tl
1778 \tl_if_empty:NF \g_@@_code_before_tl
1779 {
1780   \bool_set_true:N \l_@@_code_before_bool
1781   \tl_put_right:NV \l_@@_code_before_tl \g_@@_code_before_tl
1782 }
1783 \tl_if_empty:NF \g_@@_pre_code_before_tl
1784 { \bool_set_true:N \l_@@_code_before_bool }

```

The set of keys is not exactly the same for `{NiceArray}` and for the variants of `{NiceArray}` (`{pNiceArray}`, `{bNiceArray}`, etc.) because, for `{NiceArray}`, we have the options `t`, `c`, `b` and `baseline`.

```

1785 \bool_if:NTF \g_@@_NiceArray_bool
1786 { \keys_set:nn { NiceMatrix / NiceArray } }
1787 { \keys_set:nn { NiceMatrix / pNiceArray } }
1788 { #3 , #5 }

1789 \@@_set_CT@arc@:V \l_@@_rules_color_tl

```

The argument `#6` is the last argument of `{NiceArrayWithDelims}`. With that argument of type “`t \CodeBefore`”, we test whether there is the keyword `\CodeBefore` at the beginning of the body of the environment. If that keyword is present, we have now to extract all the content between that keyword `\CodeBefore` and the (other) keyword `\Body`. It's the job that will do the command `\@@_CodeBefore_Body:w`. After that job, the command `\@@_CodeBefore_Body:w` will go on with `\@@_pre_array:`.

```

1790 \IfBooleanTF { #6 } \@@_CodeBefore_Body:w \@@_pre_array:
1791 }

```

Now, the second part of the environment `{NiceArrayWithDelims}`.

```

1792 {
1793   \bool_if:NTF \l_@@_light_syntax_bool
1794   { \use:c { end @@-light-syntax } }
1795   { \use:c { end @@-normal-syntax } }
1796   \c_math_toggle_token
1797   \skip_horizontal:N \l_@@_right_margin_dim
1798   \skip_horizontal:N \l_@@_extra_right_margin_dim
1799   \hbox_set_end:

```

End of the construction of the array (in the box `\l_@@_the_array_box`).

If the user has used the key `width` without any column `X`, we raise an error.

```

1800 \bool_if:NT \l_@@_width_used_bool
1801 {
1802   \int_compare:nNnT \g_@@_total_X_weight_int = 0
1803   { \@@_error_or_warning:n { width-without-X-columns } }

```

```
1804 }
```

Now, if there is at least one X-column in the environment, we compute the width that those columns will have (in the next compilation). In fact, `l_@@_X_columns_dim` will be the width of a column of weight 1. For a X-column of weight n , the width will be `l_@@_X_columns_dim` multiplied by n .

```
1805 \int_compare:nNnT \g_@@_total_X_weight_int > 0
1806 {
1807   \tl_gput_right:Nx \g_@@_aux_tl
1808   {
1809     \bool_set_true:N \l_@@_X_columns_aux_bool
1810     \dim_set:Nn \l_@@_X_columns_dim
1811     {
1812       \dim_compare:nNnTF
1813       {
1814         \dim_abs:n
1815         { \l_@@_width_dim - \box_wd:N \l_@@_the_array_box }
1816       }
1817       <
1818       { 0.001 pt }
1819       { \dim_use:N \l_@@_X_columns_dim }
1820       {
1821         \dim_eval:n
1822         {
1823           ( \l_@@_width_dim - \box_wd:N \l_@@_the_array_box )
1824           / \int_use:N \g_@@_total_X_weight_int
1825           + \l_@@_X_columns_dim
1826         }
1827       }
1828     }
1829   }
1830 }
```

It the user has used the key `last-row` with a value, we control that the given value is correct (since we have just constructed the array, we know the actual number of rows of the array).

```
1831 \int_compare:nNnT \l_@@_last_row_int > { -2 }
1832 {
1833   \bool_if:NF \l_@@_last_row_without_value_bool
1834   {
1835     \int_compare:nNnF \l_@@_last_row_int = \c@iRow
1836     {
1837       \@@_error:n { Wrong~last~row }
1838       \int_gset_eq:NN \l_@@_last_row_int \c@iRow
1839     }
1840   }
1841 }
```

Now, the definition of `\c@jCol` and `\g_@@_col_total_int` change: `\c@jCol` will be the number of columns without the “last column”; `\g_@@_col_total_int` will be the number of columns with this “last column”.⁷¹

```
1842 \int_gset_eq:NN \c@jCol \g_@@_col_total_int
1843 \bool_if:nTF \g_@@_last_col_found_bool
1844 { \int_gdecr:N \c@jCol }
1845 {
1846   \int_compare:nNnT \l_@@_last_col_int > { -1 }
1847   { \@@_error:n { last~col~not~used } }
1848 }
```

We fix also the value of `\c@iRow` and `\g_@@_row_total_int` with the same principle.

```
1849 \int_gset_eq:NN \g_@@_row_total_int \c@iRow
1850 \int_compare:nNnT \l_@@_last_row_int > { -1 } { \int_gdecr:N \c@iRow }
```

⁷¹We remind that the potential “first column” (exterior) has the number 0.

Now, we begin the real construction in the output flow of TeX. First, we take into account a potential “first column” (we remind that this “first column” has been constructed in an overlapping position and that we have computed its width in `\g_@@_width_first_col_dim`: see p. 139).

```

1851 \int_compare:nNnT \l_@@_first_col_int = 0
1852 {
1853   \skip_horizontal:N \col@sep
1854   \skip_horizontal:N \g_@@_width_first_col_dim
1855 }

```

The construction of the real box is different when `\g_@@_NiceArray_bool` is true (`{NiceArray}` or `{NiceTabular}`) and in the other environments because, in `{NiceArray}` or `{NiceTabular}`, we have no delimiter to put (but we have tabular notes to put). We begin with this case.

```

1856 \bool_if:NTF \g_@@_NiceArray_bool
1857 {
1858   \str_case:VnF \l_@@_baseline_tl
1859   {
1860     b \@@_use_arraybox_with_notes_b:
1861     c \@@_use_arraybox_with_notes_c:
1862   }
1863   \@@_use_arraybox_with_notes:
1864 }

```

Now, in the case of an environment `{pNiceArray}`, `{bNiceArray}`, etc. We compute `\l_tmpa_dim` which is the total height of the “first row” above the array (when the key `first-row` is used).

```

1865 {
1866   \int_compare:nNnTF \l_@@_first_row_int = 0
1867   {
1868     \dim_set_eq:NN \l_tmpa_dim \g_@@_dp_row_zero_dim
1869     \dim_add:Nn \l_tmpa_dim \g_@@_ht_row_zero_dim
1870   }
1871   { \dim_zero:N \l_tmpa_dim }

```

We compute `\l_tmpb_dim` which is the total height of the “last row” below the array (when the key `last-row` is used). A value of `-2` for `\l_@@_last_row_int` means that there is no “last row”.⁷²

```

1872 \int_compare:nNnTF \l_@@_last_row_int > { -2 }
1873 {
1874   \dim_set_eq:NN \l_tmpb_dim \g_@@_ht_last_row_dim
1875   \dim_add:Nn \l_tmpb_dim \g_@@_dp_last_row_dim
1876 }
1877 { \dim_zero:N \l_tmpb_dim }
1878 \hbox_set:Nn \l_tmpa_box
1879 {
1880   \c_math_toggle_token
1881   \@@_color:V \l_@@_delimiters_color_tl
1882   \exp_after:wN \left \g_@@_left_delim_tl
1883   \vcenter
1884   {

```

We take into account the “first row” (we have previously computed its total height in `\l_tmpa_dim`). The `\hbox:n` (or `\hbox`) is necessary here.

```

1885   \skip_vertical:n { -\l_tmpa_dim - \arrayrulewidth }
1886   \hbox
1887   {
1888     \bool_if:NTF \l_@@_NiceTabular_bool
1889     { \skip_horizontal:N -\tabcolsep }
1890     { \skip_horizontal:N -\arraycolsep }
1891     \@@_use_arraybox_with_notes_c:
1892     \bool_if:NTF \l_@@_NiceTabular_bool
1893     { \skip_horizontal:N -\tabcolsep }
1894     { \skip_horizontal:N -\arraycolsep }
1895   }

```

⁷²A value of `-1` for `\l_@@_last_row_int` means that there is a “last row” but the user have not set the value with the option `last row` (and we are in the first compilation).

We take into account the “last row” (we have previously computed its total height in `\l_tmpb_dim`).

```
1896         \skip_vertical:n { -\l_tmpb_dim + \arrayrulewidth }
1897     }
```

Curiously, we have to put again the following specification of color. Otherwise, with XeLaTeX (and not with the other engines), the closing delimiter is not colored.

```
1898         @@_color:V \l_@@_delimiters_color_tl
1899         \exp_after:wN \right \g_@@_right_delim_tl
1900         \c_math_toggle_token
1901     }
```

Now, the box `\l_tmpa_box` is created with the correct delimiters.

We will put the box in the TeX flow. However, we have a small work to do when the option `delimiters/max-width` is used.

```
1902     \bool_if:NTF \l_@@_delimiters_max_width_bool
1903     {
1904         @@_put_box_in_flow_bis:nn
1905         \g_@@_left_delim_tl \g_@@_right_delim_tl
1906     }
1907     @@_put_box_in_flow:
1908 }
```

We take into account a potential “last column” (this “last column” has been constructed in an overlapping position and we have computed its width in `\g_@@_width_last_col_dim`: see p. 140).

```
1909     \bool_if:NT \g_@@_last_col_found_bool
1910     {
1911         \skip_horizontal:N \g_@@_width_last_col_dim
1912         \skip_horizontal:N \col@sep
1913     }
1914     \bool_if:NF \l_@@_Matrix_bool
1915     {
1916         \int_compare:nNnT \c@jCol < \g_@@_static_num_of_col_int
1917         { @@_warning_gredirect_none:n { columns-not-used } }
1918     }
1919     @@_after_array:
```

The aim of the following `\egroup` (the corresponding `\bgroup` is, of course, at the beginning of the environment) is to be able to put an exposant to a matrix in a mathematical formula.

```
1920     \egroup
```

We write on the aux file all the informations corresponding to the current environment.

```
1921     \iow_now:Nn \@mainaux { \ExplSyntaxOn }
1922     \iow_now:Nn \@mainaux { \char_set_catcode_space:n { 32 } }
1923     \iow_now:Nx \@mainaux
1924     {
1925         \tl_gset:cn { c_@@_ \int_use:N \g_@@_env_int _ tl }
1926         { \exp_not:V \g_@@_aux_tl }
1927     }
1928     \iow_now:Nn \@mainaux { \ExplSyntaxOff }

1929     \bool_if:NT \c_@@_footnote_bool \endsavenotes
1930 }
```

This is the end of the environment `{NiceArrayWithDelims}`.

We construct the preamble of the array

The transformation of the preamble is an operation in several steps.⁷³

⁷³Be careful: the transformation of the preamble may also have by-side effects, for example, the boolean `\g_@@_NiceArray_bool` will be set to `false` if we detect in the preamble a delimiter at the beginning or at the end.

The preamble given by the final user is in `\g_@@_preamble_tl` and the modified version will be stored in `\g_@@_preamble_tl` also.

```
1931 \cs_new_protected:Npn \@@_transform_preamble:
1932 {
```

First, we will do an “expansion” of the preamble with the tools of the package `array` itself. This “expansion” will expand all the constructions with `*` and all column types (defined by the user or by various packages using `\newcolumntype`).

Since we use the tools of `array` to do this expansion, we will have a programming which is not in the style of the L3 programming layer.

We redefine the column types `w` and `W`. We use `\@@_newcolumntype` instead of `\newcolumntype` because we don’t want warnings for column types already defined. These redefinitions are in fact *protections* of the letters `w` and `W`. We don’t want these columns type expanded because we will do the patch ourselves after. We want to be able to use the standard column types `w` and `W` in potential `{tabular}` of `array` in some cells of our array. That’s why we do those redefinitions in a TeX group.

```
1933 \group_begin:
```

If we are in an environment without explicit preamble, we have nothing to do (excepted the treatment on both sides of the preamble which will be done at the end).

```
1934 \bool_if:NF \l_@@_Matrix_bool
1935 {
1936   \@@_newcolumntype w [ 2 ] { \@@_w: { ##1 } { ##2 } }
1937   \@@_newcolumntype W [ 2 ] { \@@_W: { ##1 } { ##2 } }
```

If the package `varwidth` has defined the column type `V`, we protect from expansion by redefining it to `\@@_V:` (which will be caught by our system).

```
1938 \cs_if_exist:NT \NC@find@V { \@@_newcolumntype V { \@@_V: } }
```

First, we have to store our preamble in the token register `\@temptokena` (those “token registers” are *not* supported by the L3 programming layer).

```
1939 \exp_args:NV \@temptokena \g_@@_preamble_tl
```

Initialisation of a flag used by `array` to detect the end of the expansion.

```
1940 \@tempswatru
```

The following line actually does the expansion (it’s has been copied from `array.sty`). The expanded version is still in `\@temptokena`.

```
1941 \@whilesw \if@tempswa \fi { \@tempswafalse \the \NC@list }
```

Now, we have to “patch” that preamble by transforming some columns. We will insert in the TeX flow the preamble in its actual form (that is to say after the “expansion”) following by a marker `\q_stop` and we will consume these tokens constructing the (new form of the) preamble in `\g_@@_preamble_tl`. This is done recursively with the command `\@@_patch_preamble:n`. In the same time, we will count the columns with the counter `\c@jCol`.

```
1942 \int_gzero:N \c@jCol
1943 \tl_gclear:N \g_@@_preamble_tl
```

`\g_tmpb_bool` will be raised if you have a `|` at the end of the preamble.

```
1944 \bool_gset_false:N \g_tmpb_bool
1945 \tl_if_eq:NnTF \l_@@_vlines_clist { all }
1946 {
1947   \tl_gset:Nn \g_@@_preamble_tl
1948   { ! { \skip_horizontal:N \arrayrulewidth } }
1949 }
1950 {
1951   \clist_if_in:NnT \l_@@_vlines_clist 1
1952   {
1953     \tl_gset:Nn \g_@@_preamble_tl
1954     { ! { \skip_horizontal:N \arrayrulewidth } }
1955   }
1956 }
```

The sequence `\g_@@_cols_vlism_seq` will contain the numbers of the columns where you will to have to draw vertical lines in the potential sub-matrices (hence the name `vlism`).

```
1957 \seq_clear:N \g_@@_cols_vlism_seq
```

The following sequence will store the arguments of the successive `>` in the preamble.

```
1958 \tl_gclear_new:N \g_@@_pre_cell_tl
```

The counter `\l_tmpa_int` will count the number of consecutive occurrences of the symbol `|`.

```
1959 \int_zero:N \l_tmpa_int
```

Now, we actually patch the preamble (and it is constructed in `\g_@@_preamble_tl`).

```
1960 \exp_after:wN \@@_patch_preamble:n \the \@temptokena \q_stop
1961 \int_gset_eq:NN \g_@@_static_num_of_col_int \c_jCol
1962 }
```

Now, we replace `\columncolor` by `\@@_columncolor_preamble`.

```
1963 \bool_if:NT \l_@@_colortbl_like_bool
1964 {
1965   \regex_replace_all:NnN
1966     \c_@@_columncolor_regex
1967     { \c { @@_columncolor_preamble } }
1968     \g_@@_preamble_tl
1969 }
```

Now, we can close the TeX group which was opened for the redefinition of the columns of type `w` and `W`.

```
1970 \group_end:
```

If there was delimiters at the beginning or at the end of the preamble, the environment `{NiceArray}` is transformed into an environment `{xNiceMatrix}`.

```
1971 \bool_lazy_or:nnT
1972   { ! \str_if_eq_p:Vn \g_@@_left_delim_tl { . } }
1973   { ! \str_if_eq_p:Vn \g_@@_right_delim_tl { . } }
1974   { \bool_gset_false:N \g_@@_NiceArray_bool }
```

We want to remind whether there is a specifier `|` at the end of the preamble.

```
1975 \bool_if:NT \g_tmpb_bool { \bool_set_true:N \l_@@_bar_at_end_of_pream_bool }
```

We complete the preamble with the potential “exterior columns” (on both sides).

```
1976 \int_compare:nNnTF \l_@@_first_col_int = 0
1977   { \tl_gput_left:NV \g_@@_preamble_tl \c_@@_preamble_first_col_tl }
1978   {
1979     \bool_lazy_all:nT
1980       {
1981         \g_@@_NiceArray_bool
1982         { \bool_not_p:n \l_@@_NiceTabular_bool }
1983         { \tl_if_empty_p:N \l_@@_vlines_clist }
1984         { \bool_not_p:n \l_@@_exterior_arraycolsep_bool }
1985       }
1986       { \tl_gput_left:Nn \g_@@_preamble_tl { @ { } } }
1987   }
1988 \int_compare:nNnTF \l_@@_last_col_int > { -1 }
1989   { \tl_gput_right:NV \g_@@_preamble_tl \c_@@_preamble_last_col_tl }
1990   {
1991     \bool_lazy_all:nT
1992       {
1993         \g_@@_NiceArray_bool
1994         { \bool_not_p:n \l_@@_NiceTabular_bool }
1995         { \tl_if_empty_p:N \l_@@_vlines_clist }
1996         { \bool_not_p:n \l_@@_exterior_arraycolsep_bool }
1997       }
1998       { \tl_gput_right:Nn \g_@@_preamble_tl { @ { } } }
1999   }
```


We add a last column to raise a good error message when the user puts more columns than allowed by its preamble. However, for technical reasons, it's not possible to do that in `{NiceTabular*}` (`\l_@@_tabular_width_dim=0pt`).

```

2000   \dim_compare:nNnT \l_@@_tabular_width_dim = \c_zero_dim
2001   {
2002     \tl_gput_right:Nn \g_@@_preamble_tl
2003     { > { \@@_error_too_much_cols: } 1 }
2004   }
2005 }
```

The command `\@@_patch_preamble:n` is the main function for the transformation of the preamble. It is recursive.

```

2006 \cs_new_protected:Npn \@@_patch_preamble:n #1
2007 {
2008   \str_case:nnF { #1 }
2009   {
2010     c { \@@_patch_preamble_i:n #1 }
2011     l { \@@_patch_preamble_i:n #1 }
2012     r { \@@_patch_preamble_i:n #1 }
2013     > { \@@_patch_preamble_xiv:n }
2014     ! { \@@_patch_preamble_ii:nn #1 }
2015     @ { \@@_patch_preamble_ii:nn #1 }
2016     | { \@@_patch_preamble_iii:n #1 }
2017     p { \@@_patch_preamble_iv:n #1 }
2018     b { \@@_patch_preamble_iv:n #1 }
2019     m { \@@_patch_preamble_iv:n #1 }
2020     \@@_V: { \@@_patch_preamble_v:n }
2021     V { \@@_patch_preamble_v:n }
2022     \@@_w: { \@@_patch_preamble_vi:nnnn { } #1 }
2023     \@@_W: { \@@_patch_preamble_vi:nnnn { \@@_special_W: } #1 }
2024     \@@_S: { \@@_patch_preamble_vii:n }
2025     ( { \@@_patch_preamble_viii:nn #1 }
2026     [ { \@@_patch_preamble_viii:nn #1 }
2027     \{ { \@@_patch_preamble_viii:nn #1 }
2028     ) { \@@_patch_preamble_ix:nn #1 }
2029     ] { \@@_patch_preamble_ix:nn #1 }
2030     \} { \@@_patch_preamble_ix:nn #1 }
2031     X { \@@_patch_preamble_x:n }
```

When `tabularx` is loaded, a local redefinition of the specifier `X` is done to replace `X` by `\@@_X`. Thus, our column type `X` will be used in the `{NiceTabularX}`.

```

2032   \@@_X { \@@_patch_preamble_x:n }
2033   \q_stop { }
2034 }
2035 {
2036   \str_if_eq:nVTF { #1 } \l_@@_letter_vlism_tl
2037   {
2038     \seq_gput_right:Nx \g_@@_cols_vlism_seq
2039     { \int_eval:n { \c@jCol + 1 } }
2040     \tl_gput_right:Nx \g_@@_preamble_tl
2041     { \exp_not:N ! { \skip_horizontal:N \arrayrulewidth } }
2042     \@@_patch_preamble:n
2043   }
2044 }
```

Now the case of a letter set by the final user for a customized rule. Such customized rule is defined by using the key `custom-line` in `\NiceMatrixOptions`. That key takes in as value a list of *key=value* pairs. Among the keys available in that list, there is the key `letter`. All the letters defined by this way by the final user for such customized rules are added in the set of keys `{NiceMatrix/ColumnTypes}`. That set of keys is used to store the characteristics of those types of rules for convenience: the keys of that set of keys won't never be used as keys by the final user (he will use, instead, letters in the preamble of its array).

```

2044   {
2045     \keys_if_exist:nnTF { NiceMatrix / ColumnTypes } { #1 }
```

```

2046         {
2047             \keys_set:nn { NiceMatrix / ColumnTypes } { #1 }
2048             \@@_patch_preamble:n
2049         }
2050         { \@@_fatal:nn { unknown~column~type } { #1 } }
2051     }
2052 }
2053 }

```

Now, we will list all the auxiliary functions for the different types of entries in the preamble of the array.

For c, l and r

```

2054 \cs_new_protected:Npn \@@_patch_preamble_i:n #1
2055 {
2056     \tl_gput_right:NV \g_@@_preamble_tl \g_@@_pre_cell_tl
2057     \tl_gclear:N \g_@@_pre_cell_tl
2058     \tl_gput_right:Nn \g_@@_preamble_tl
2059     {
2060         > { \@@_cell_begin:w \str_set:Nn \l_@@_hpos_cell_str { #1 } }
2061         #1
2062         < \@@_cell_end:
2063     }

```

We increment the counter of columns and then we test for the presence of a <.

```

2064     \int_gincr:N \c@jCol
2065     \@@_patch_preamble_xi:n
2066 }

```

For >, ! and @

```

2067 \cs_new_protected:Npn \@@_patch_preamble_ii:nn #1 #2
2068 {
2069     \tl_gput_right:Nn \g_@@_preamble_tl { #1 { #2 } }
2070     \@@_patch_preamble:n
2071 }

```

For |

```

2072 \cs_new_protected:Npn \@@_patch_preamble_iii:n #1
2073 {
2074     \int_incr:N \l_tmpa_int
2075     \@@_patch_preamble_iii_i:n
2076 }

```

\l_tmpa_int is the number of successive occurrences of |

```

2074     \int_incr:N \l_tmpa_int
2075     \@@_patch_preamble_iii_i:n
2076 }
2077 \cs_new_protected:Npn \@@_patch_preamble_iii_i:n #1
2078 {
2079     \str_if_eq:nnTF { #1 } |
2080     { \@@_patch_preamble_iii:n | }
2081     {
2082         \dim_set:Nn \l_tmpa_dim
2083         {
2084             \arrayrulewidth * \l_tmpa_int
2085             + \doublerulesep * ( \l_tmpa_int - 1 )
2086         }
2087         \tl_gput_right:Nx \g_@@_preamble_tl
2088         {

```

Here, the command \dim_eval:n is mandatory.

```

2089         \exp_not:N ! { \skip_horizontal:n { \dim_eval:n { \l_tmpa_dim } } }
2090     }
2091     \tl_gput_right:Nx \g_@@_pre_code_after_tl
2092     {
2093         \@@_vline:n
2094         {

```

```

2095         position = \int_eval:n { \c@jCol + 1 } ,
2096         multiplicity = \int_use:N \l_tmpa_int ,
2097         total-width = \dim_use:N \l_tmpa_dim % added 2022-08-06
2098     }

```

We don't have provided value for `start` nor for `end`, which means that the rule will cover (potentially) all the rows of the array.

```

2099     }
2100     \int_zero:N \l_tmpa_int
2101     \str_if_eq:nnT { #1 } { \q_stop } { \bool_gset_true:N \g_tmpb_bool }
2102     \@@_patch_preamble:n #1
2103 }
2104 }
2105 \cs_new_protected:Npn \@@_patch_preamble_xiv:n #1
2106 {
2107     \tl_gput_right:Nn \g_@@_pre_cell_tl { > { #1 } }
2108     \@@_patch_preamble:n
2109 }
2110 \bool_new:N \l_@@_bar_at_end_of_pream_bool

```

The specifier `p` (and also the specifiers `m`, `b`, `V` and `X`) have an optional argument between square brackets for a list of *key-value* pairs. Here are the corresponding keys.

```

2111 \keys_define:nn { WithArrows / p-column }
2112 {
2113     r .code:n = \str_set:Nn \l_@@_hpos_col_str { r } ,
2114     r .value_forbidden:n = true ,
2115     c .code:n = \str_set:Nn \l_@@_hpos_col_str { c } ,
2116     c .value_forbidden:n = true ,
2117     l .code:n = \str_set:Nn \l_@@_hpos_col_str { l } ,
2118     l .value_forbidden:n = true ,
2119     R .code:n =
2120         \IfPackageLoadedTF { ragged2e }
2121         { \str_set:Nn \l_@@_hpos_col_str { R } }
2122         {
2123             \@@_error_or_warning:n { ragged2e~not~loaded }
2124             \str_set:Nn \l_@@_hpos_col_str { r }
2125         } ,
2126     R .value_forbidden:n = true ,
2127     L .code:n =
2128         \IfPackageLoadedTF { ragged2e }
2129         { \str_set:Nn \l_@@_hpos_col_str { L } }
2130         {
2131             \@@_error_or_warning:n { ragged2e~not~loaded }
2132             \str_set:Nn \l_@@_hpos_col_str { l }
2133         } ,
2134     L .value_forbidden:n = true ,
2135     C .code:n =
2136         \IfPackageLoadedTF { ragged2e }
2137         { \str_set:Nn \l_@@_hpos_col_str { C } }
2138         {
2139             \@@_error_or_warning:n { ragged2e~not~loaded }
2140             \str_set:Nn \l_@@_hpos_col_str { c }
2141         } ,
2142     C .value_forbidden:n = true ,
2143     S .code:n = \str_set:Nn \l_@@_hpos_col_str { si } ,
2144     S .value_forbidden:n = true ,
2145     p .code:n = \str_set:Nn \l_@@_vpos_col_str { p } ,
2146     p .value_forbidden:n = true ,
2147     t .meta:n = p ,
2148     m .code:n = \str_set:Nn \l_@@_vpos_col_str { m } ,
2149     m .value_forbidden:n = true ,
2150     b .code:n = \str_set:Nn \l_@@_vpos_col_str { b } ,

```

```

2151     b .value_forbidden:n = true ,
2152 }

```

For p, b and m. The argument #1 is that value : p, b or m.

```

2153 \cs_new_protected:Npn \@@_patch_preamble_iv:n #1
2154 {
2155     \str_set:Nn \l_@@_vpos_col_str { #1 }

```

Now, you look for a potential character [after the letter of the specifier (for the options).

```

2156     \@@_patch_preamble_iv_i:n
2157 }

2158 \cs_new_protected:Npn \@@_patch_preamble_iv_ii:n #1
2159 {
2160     \str_if_eq:nnTF { #1 } { [ ]
2161         { \@@_patch_preamble_iv_iii:w [ ]
2162           { \@@_patch_preamble_iv_iii:w [ ] { #1 } }
2163         }
2164     \cs_new_protected:Npn \@@_patch_preamble_iv_iii:w [ #1 ]
2165     { \@@_patch_preamble_iv_iii:nn { #1 } }

```

#1 is the optional argument of the specifier (a list of *key-value* pairs).

#2 is the mandatory argument of the specifier: the width of the column.

```

2166 \cs_new_protected:Npn \@@_patch_preamble_iv_iii:nn #1 #2
2167 {

```

The possible values of \l_@@_hpos_col_str are j (for *justified* which is the initial value), l, c, r, L, C and R (when the user has used the corresponding key in the optional argument of the specifier).

```

2168     \str_set:Nn \l_@@_hpos_col_str { j }
2169     \tl_set:Nn \l_tmpa_tl { #1 }
2170     \tl_replace_all:Nnn \l_tmpa_tl { \@@_S: } { S }
2171     \@@_keys_p_column:V \l_tmpa_tl
2172     \@@_patch_preamble_iv_iv:nn { #2 } { minipage }
2173 }

2174 \cs_new_protected:Npn \@@_keys_p_column:n #1
2175 { \keys_set_known:nnN { WithArrows / p-column } { #1 } \l_tmpa_tl }
2176 \cs_generate_variant:Nn \@@_keys_p_column:n { V }

```

The first argument is the width of the column. The second is the type of environment: `minipage` or `varwidth`.

```

2177 \cs_new_protected:Npn \@@_patch_preamble_iv_iv:nn #1 #2
2178 {
2179     \use:x
2180     {
2181         \@@_patch_preamble_iv_v:nnnnnnnn
2182         { \str_if_eq:VnTF \l_@@_vpos_col_str { p } { t } { b } }
2183         { \dim_eval:n { #1 } }
2184     }

```

The parameter \l_@@_hpos_col_str (as \l_@@_vpos_col_str) exists only during the construction of the preamble. During the composition of the array itself, you will have, in each cell, the parameter \l_@@_hpos_cell_str which will provide the horizontal alignment of the column to which belongs the cell.

```

2185         \str_if_eq:VnTF \l_@@_hpos_col_str j
2186         { \str_set:Nn \exp_not:N \l_@@_hpos_cell_str { c } }
2187         {
2188             \str_set:Nn \exp_not:N \l_@@_hpos_cell_str
2189             { \str_lowercase:V \l_@@_hpos_col_str }
2190         }
2191         \str_case:Vn \l_@@_hpos_col_str
2192         {
2193             c { \exp_not:N \centering }
2194             l { \exp_not:N \raggedright }

```

```

2195         r { \exp_not:N \raggedleft }
2196         C { \exp_not:N \Centering }
2197         L { \exp_not:N \RaggedRight }
2198         R { \exp_not:N \RaggedLeft }
2199     }
2200 }
2201 { \str_if_eq:VnT \l_@@_vpos_col_str { m } \@@_center_cell_box: }
2202 { \str_if_eq:VnT \l_@@_hpos_col_str { si } \siunitx_cell_begin:w }
2203 { \str_if_eq:VnT \l_@@_hpos_col_str { si } \siunitx_cell_end: }
2204 { #2 }
2205 {
2206     \str_case:VnF \l_@@_hpos_col_str
2207     {
2208         { j } { c }
2209         { si } { c }
2210     }

```

We use `\str_lowercase:n` to convert `R` to `r`, etc.

```

2211     { \str_lowercase:V \l_@@_hpos_col_str }
2212 }
2213 }

```

We increment the counter of columns, and then we test for the presence of a `<`.

```

2214     \int_gincr:N \c@jCol
2215     \@@_patch_preamble_xi:n
2216 }

```

#1 is the optional argument of `{minipage}` (or `{varwidth}`): `t` or `b`. Indeed, for the columns of type `m`, we use the value `b` here because there is a special post-action in order to center vertically the box (see **#4**).

#2 is the width of the `{minipage}` (or `{varwidth}`), that is to say also the width of the column.

#3 is the coding for the horizontal position of the content of the cell (`\centering`, `\raggedright`, `\raggedleft` or nothing). It's also possible to put in that **#3** some code to fix the value of `\l_@@_hpos_cell_str` which will be available in each cell of the column.

#4 is an extra-code which contains `\@@_center_cell_box:` (when the column is a `m` column) or nothing (in the other cases).

#5 is a code put just before the `c` (or `r` or `l`: see **#8**).

#6 is a code put just after the `c` (or `r` or `l`: see **#8**).

#7 is the type of environment: `minipage` or `varwidth`.

#8 is the letter `c` or `r` or `l` which is the basic specifier of column which is used *in fine*.

```

2217 \cs_new_protected:Npn \@@_patch_preamble_iv_v:nnnnnnnn #1 #2 #3 #4 #5 #6 #7 #8
2218 {
2219     \str_if_eq:VnTF \l_@@_hpos_col_str { si }
2220     { \tl_gput_right:Nn \g_@@_preamble_tl { > { \@@_test_if_empty_for_S: } } }
2221     { \tl_gput_right:Nn \g_@@_preamble_tl { > { \@@_test_if_empty: } } }
2222     \tl_gput_right:N \g_@@_preamble_tl \g_@@_pre_cell_tl
2223     \tl_gclear:N \g_@@_pre_cell_tl
2224     \tl_gput_right:Nn \g_@@_preamble_tl
2225     {
2226         > {

```

The parameter `\l_@@_col_width_dim`, which is the width of the current column, will be available in each cell of the column. It will be used by the mono-column blocks.

```

2227         \dim_set:Nn \l_@@_col_width_dim { #2 }
2228         \@@_cell_begin:w
2229         \begin { #7 } [ #1 ] { #2 }

```

The following lines have been taken from `array.sty`.

```

2230     \everypar
2231     {
2232         \vrule height \box_ht:N \@arstrutbox width \c_zero_dim
2233         \everypar { }
2234     }

```

Now, the potential code for the horizontal position of the content of the cell (`\centering`, `\raggedright`, `\RaggedRight`, etc.).

```
2235         #3
```

The following code is to allow something like `\centering` in `\RowStyle`.

```
2236         \g_@@_row_style_tl
2237         \arraybackslash
2238         #5
2239     }
2240     #8
2241     < {
2242         #6
```

The following line has been taken from `array.sty`.

```
2243         \@finalstrut \@arstrutbox
2244         % \bool_if:NT \g_@@_rotate_bool { \raggedright \hspace = 3 cm }
2245         \end { #7 }
```

If the letter in the preamble is `m`, `#4` will be equal to `\@@_center_cell_box`: (see just below).

```
2246         #4
2247         \@@_cell_end:
2248     }
2249 }
2250 }
```

```
2251 \cs_new_protected:Npn \@@_test_if_empty: \ignorespaces #1
2252 {
2253     \peek_meaning:NT \unskip
2254     {
2255         \tl_gput_right:Nn \g_@@_cell_after_hook_tl
2256         {
2257             \box_set_wd:Nn \l_@@_cell_box \c_zero_dim
```

We put the following code in order to have a column with the correct width even when all the cells of the column are empty.

```
2258         \skip_horizontal:N \l_@@_col_width_dim
2259     }
2260 }
2261 #1
2262 }
2263 \cs_new_protected:Npn \@@_test_if_empty_for_S: #1
2264 {
2265     \peek_meaning:NT \__siunitx_table_skip:n
2266     {
2267         \tl_gput_right:Nn \g_@@_cell_after_hook_tl
2268         { \box_set_wd:Nn \l_@@_cell_box \c_zero_dim }
2269     }
2270     #1
2271 }
```

The following command will be used in `m`-columns in order to center vertically the box. In fact, despite its name, the command does not always center the cell. Indeed, if there is only one row in the cell, it should not be centered vertically. It's not possible to know the number of rows of the cell. However, we consider (as in `array`) that if the height of the cell is no more that the height of `\@arstrutbox`, there is only one row.

```
2272 \cs_new_protected:Npn \@@_center_cell_box:
2273 {
```

By putting instructions in `\g_@@_cell_after_hook_tl`, we require a post-action of the box `\l_@@_cell_box`.

```
2274     \tl_gput_right:Nn \g_@@_cell_after_hook_tl
2275     {
```

```

2276 \int_compare:nNnT
2277 { \box_ht:N \l_@@_cell_box }
2278 >

```

Previously, we had `\@arstrutbox` and not `\strutbox` in the following line but the code in `array` has changed in v 2.5g and we follow the change (see *array: Correctly identify single-line m-cells* in LaTeX News 36).

```

2279 { \box_ht:N \strutbox }
2280 {
2281   \hbox_set:Nn \l_@@_cell_box
2282   {
2283     \box_move_down:nn
2284     {
2285       ( \box_ht:N \l_@@_cell_box - \box_ht:N \@arstrutbox
2286       + \baselineskip ) / 2
2287     }
2288     { \box_use:N \l_@@_cell_box }
2289   }
2290 }
2291 }
2292 }

```

For V (similar to the V of `varwidth`).

```

2293 \cs_new_protected:Npn \@@_patch_preamble_v:n #1
2294 {
2295   \str_if_eq:nnTF { #1 } { [ ] }
2296   { \@@_patch_preamble_v_i:w [ ] }
2297   { \@@_patch_preamble_v_i:w [ ] { #1 } }
2298 }
2299 \cs_new_protected:Npn \@@_patch_preamble_v_i:w [ #1 ]
2300 { \@@_patch_preamble_v_ii:nn { #1 } }
2301 \cs_new_protected:Npn \@@_patch_preamble_v_ii:nn #1 #2
2302 {
2303   \str_set:Nn \l_@@_vpos_col_str { p }
2304   \str_set:Nn \l_@@_hpos_col_str { j }
2305   \tl_set:Nn \l_tmpa_tl { #1 }
2306   \tl_replace_all:Nnn \l_tmpa_tl { \@@_S: } { S }
2307   \@@_keys_p_column:V \l_tmpa_tl
2308   \bool_if:NTF \c_@@_varwidth_loaded_bool
2309   { \@@_patch_preamble_iv_iv:nn { #2 } { varwidth } }
2310   {
2311     \@@_error_or_warning:n { varwidth~not~loaded }
2312     \@@_patch_preamble_iv_iv:nn { #2 } { minipage }
2313   }
2314 }

```

For w and W

```

2315 \cs_new_protected:Npn \@@_patch_preamble_vi:nnnn #1 #2 #3 #4
2316 {
2317   \tl_gput_right:NV \g_@@_preamble_tl \g_@@_pre_cell_tl
2318   \tl_gclear:N \g_@@_pre_cell_tl
2319   \tl_gput_right:Nn \g_@@_preamble_tl
2320   {
2321     > {

```

The parameter `\l_@@_col_width_dim`, which is the width of the current column, will be available in each cell of the column. It will be used by the mono-column blocks.

```

2322 \dim_set:Nn \l_@@_col_width_dim { #4 }
2323 \hbox_set:Nw \l_@@_cell_box
2324 \@@_cell_begin:w
2325 \str_set:Nn \l_@@_hpos_cell_str { #3 }
2326 }
2327 c
2328 < {

```

```

2329         \@@_cell_end:
2330         \hbox_set_end:
2331         \bool_if:NT \g_@@_rotate_bool \@@_rotate_cell_box:
2332         #1
2333         \@@_adjust_size_box:
2334         \makebox [ #4 ] [ #3 ] { \box_use_drop:N \l_@@_cell_box }
2335     }
2336 }

```

We increment the counter of columns and then we test for the presence of a <.

```

2337     \int_gincr:N \c@jCol
2338     \@@_patch_preamble_xi:n
2339 }

```

```

2340 \cs_new_protected:Npn \@@_special_W:
2341 {
2342     \dim_compare:nNnT
2343     { \box_wd:N \l_@@_cell_box }
2344     >
2345     \l_@@_col_width_dim
2346     { \@@_warning:n { W~warning } }
2347 }

```

For \@@_S:. If the user has used S[...], S has been replaced by \@@_S: during the first expansion of the preamble (done with the tools of standard LaTeX and array).

```

2348 \cs_new_protected:Npn \@@_patch_preamble_vii:n #1
2349 {
2350     \str_if_eq:nnTF { #1 } { [ ]
2351     { \@@_patch_preamble_vii_i:w [ ]
2352     { \@@_patch_preamble_vii_i:w [ ] { #1 } }
2353 }
2354 \cs_new_protected:Npn \@@_patch_preamble_vii_i:w [ #1 ]
2355 { \@@_patch_preamble_vii_ii:n { #1 } }
2356 \cs_new_protected:Npn \@@_patch_preamble_vii_ii:n #1
2357 {

```

We test whether the version of nicematrix is at least 3.0. We will change the programming of the test further with something like \@ifpackagelater.

```

2358     \cs_if_exist:NTF \siunitx_cell_begin:w
2359     {
2360         \tl_gput_right:NV \g_@@_preamble_tl \g_@@_pre_cell_tl
2361         \tl_gclear:N \g_@@_pre_cell_tl
2362         \tl_gput_right:Nn \g_@@_preamble_tl
2363         {
2364             > {
2365                 \@@_cell_begin:w
2366                 \keys_set:nn { siunitx } { #1 }
2367                 \siunitx_cell_begin:w
2368             }
2369             c
2370             < { \siunitx_cell_end: \@@_cell_end: }
2371         }

```

We increment the counter of columns and then we test for the presence of a <.

```

2372     \int_gincr:N \c@jCol
2373     \@@_patch_preamble_xi:n
2374 }
2375 { \@@_fatal:n { Version-of-siunitx-too-old } }
2376 }

```


For (, [and \{.

```

2377 \cs_new_protected:Npn \@@_patch_preamble_viii:nn #1 #2
2378 {
2379   \bool_if:NT \l_@@_small_bool { \@@_fatal:n { Delimiter~with~small } }

```

If we are before the column 1 and not in {NiceArray}, we reserve space for the left delimiter.

```

2380   \int_compare:nNnTF \c@jCol = \c_zero_int
2381   {
2382     \str_if_eq:VnTF \g_@@_left_delim_tl { . }
2383     {

```

In that case, in fact, the first letter of the preamble must be considered as the left delimiter of the array.

```

2384       \tl_gset:Nn \g_@@_left_delim_tl { #1 }
2385       \tl_gset:Nn \g_@@_right_delim_tl { . }
2386       \@@_patch_preamble:n #2
2387     }
2388     {
2389       \tl_gput_right:Nn \g_@@_preamble_tl { ! { \enskip } }
2390       \@@_patch_preamble_viii_i:nn { #1 } { #2 }
2391     }
2392   }
2393   { \@@_patch_preamble_viii_i:nn { #1 } { #2 } }
2394 }
2395 \cs_new_protected:Npn \@@_patch_preamble_viii_i:nn #1 #2
2396 {
2397   \tl_gput_right:Nx \g_@@_pre_code_after_tl
2398   { \@@_delimiter:nnn #1 { \int_eval:n { \c@jCol + 1 } } } \c_true_bool }
2399   \tl_if_in:nnTF { ( [ \{ ) ] \} } { #2 }
2400   {
2401     \@@_error:nn { delimiter~after~opening } { #2 }
2402     \@@_patch_preamble:n
2403   }
2404   { \@@_patch_preamble:n #2 }
2405 }

```

For),] and \}. We have two arguments for the following command because we directly read the following letter in the preamble (we have to see whether we have a opening delimiter following and we also have to see whether we are at the end of the preamble because, in that case, our letter must be considered as the right delimiter of the environment if the environment is {NiceArray}).

```

2406 \cs_new_protected:Npn \@@_patch_preamble_ix:nn #1 #2
2407 {
2408   \bool_if:NT \l_@@_small_bool { \@@_fatal:n { Delimiter~with~small } }
2409   \tl_if_in:nnTF { ) ] \} } { #2 }
2410   { \@@_patch_preamble_ix_i:nnn #1 #2 }
2411   {
2412     \tl_if_eq:nnTF { \q_stop } { #2 }
2413     {
2414       \str_if_eq:VnTF \g_@@_right_delim_tl { . }
2415       { \tl_gset:Nn \g_@@_right_delim_tl { #1 } }
2416       {
2417         \tl_gput_right:Nn \g_@@_preamble_tl { ! { \enskip } }
2418         \tl_gput_right:Nx \g_@@_pre_code_after_tl
2419         { \@@_delimiter:nnn #1 { \int_use:N \c@jCol } } \c_false_bool }
2420         \@@_patch_preamble:n #2
2421       }
2422     }
2423     {
2424       \tl_if_in:nnT { ( [ \{ } { #2 }
2425       { \tl_gput_right:Nn \g_@@_preamble_tl { ! { \enskip } } }
2426       \tl_gput_right:Nx \g_@@_pre_code_after_tl
2427       { \@@_delimiter:nnn #1 { \int_use:N \c@jCol } } \c_false_bool }
2428       \@@_patch_preamble:n #2

```

```

2429     }
2430   }
2431 }
2432 \cs_new_protected:Npn \@@_patch_preamble_ix_i:nnn #1 #2 #3
2433 {
2434   \tl_if_eq:nnTF { \q_stop } { #3 }
2435   {
2436     \str_if_eq:VnTF \g_@@_right_delim_tl { . }
2437     {
2438       \tl_gput_right:Nn \g_@@_preamble_tl { ! { \enskip } }
2439       \tl_gput_right:Nx \g_@@_pre_code_after_tl
2440       { \@@_delimiter:nnn #1 { \int_use:N \c@jCol } \c_false_bool }
2441       \tl_gset:Nn \g_@@_right_delim_tl { #2 }
2442     }
2443     {
2444       \tl_gput_right:Nn \g_@@_preamble_tl { ! { \enskip } }
2445       \tl_gput_right:Nx \g_@@_pre_code_after_tl
2446       { \@@_delimiter:nnn #1 { \int_use:N \c@jCol } \c_false_bool }
2447       \@@_error:nn { double~closing~delimiter } { #2 }
2448     }
2449   }
2450   {
2451     \tl_gput_right:Nx \g_@@_pre_code_after_tl
2452     { \@@_delimiter:nnn #1 { \int_use:N \c@jCol } \c_false_bool }
2453     \@@_error:nn { double~closing~delimiter } { #2 }
2454     \@@_patch_preamble:n #3
2455   }
2456 }

```

For the case of a letter X. This specifier may take in an optional argument (between square brackets). That's why we test whether there is a [after the letter X.

```

2457 \cs_new_protected:Npn \@@_patch_preamble_x:n #1
2458 {
2459   \str_if_eq:nnTF { #1 } { [ ]
2460     { \@@_patch_preamble_x_i:w [ ]
2461       { \@@_patch_preamble_x_i:w [ ] #1 }
2462     }
2463   \cs_new_protected:Npn \@@_patch_preamble_x_i:w [ #1 ]
2464     { \@@_patch_preamble_x_ii:n { #1 } }

```

#1 is the optional argument of the X specifier (a list of *key-value* pairs).

The following set of keys is for the specifier X in the preamble of the array. Such specifier may have as keys all the keys of { WithArrows / p-column } but also a key as 1, 2, 3, etc. The following set of keys will be used to retrieve that value (in the counter \l_@@_weight_int).

```

2465 \keys_define:nn { WithArrows / X-column }
2466 { unknown .code:n = \int_set:Nn \l_@@_weight_int { \l_keys_key_str } }

```

In the following command, #1 is the list of the options of the specifier X.

```

2467 \cs_new_protected:Npn \@@_patch_preamble_x_ii:n #1
2468 {

```

The possible values of \l_@@_hpos_col_str are j (for *justified* which is the initial value), l, c and r (when the user has used the corresponding key in the optional argument of the specifier X).

```

2469   \str_set:Nn \l_@@_hpos_col_str { j }

```

The possible values of \l_@@_vpos_col_str are p (the initial value), m and b (when the user has used the corresponding key in the optional argument of the specifier X).

```

2470   \tl_set:Nn \l_@@_vpos_col_str { p }

```

The integer `\l_@@_weight_int` will be the weight of the X column (the initial value is 1). The user may specify a different value (such as 2, 3, etc.) by putting that value in the optional argument of the specifier. The weights of the X columns are used in the computation of the actual width of those columns as in `tabu` of `tabularray`.

```

2471 \int_zero_new:N \l_@@_weight_int
2472 \int_set:Nn \l_@@_weight_int { 1 }
2473 \tl_set:Nn \l_tmpa_tl { #1 }
2474 \tl_replace_all:Nnn \l_tmpa_tl { \@@_S: } { S }
2475 \@@_keys_p_column:V \l_tmpa_tl
2476 % \keys_set_known:nnN { WithArrows / p-column } { #1 } \l_tmpa_tl
2477 \keys_set:nV { WithArrows / X-column } \l_tmpa_tl
2478 \int_compare:nNnT \l_@@_weight_int < 0
2479 {
2480   \@@_error_or_warning:n { negative-weight }
2481   \int_set:Nn \l_@@_weight_int { - \l_@@_weight_int }
2482 }
2483 \int_gadd:Nn \g_@@_total_X_weight_int \l_@@_weight_int

```

We test whether we know the width of the X-columns by reading the aux file (after the first compilation, the width of the X-columns is computed and written in the aux file).

```

2484 \bool_if:NTF \l_@@_X_columns_aux_bool
2485 {
2486   \@@_patch_preamble_iv_iv:nn
2487   { \l_@@_weight_int \l_@@_X_columns_dim }
2488   { minipage }
2489 }
2490 {
2491   \tl_gput_right:Nn \g_@@_preamble_tl
2492   {
2493     > {
2494       \@@_cell_begin:w
2495       \bool_set_true:N \l_@@_X_column_bool

```

The following code will nullify the box of the cell.

```

2496 \tl_gput_right:Nn \g_@@_cell_after_hook_tl
2497 { \hbox_set:Nn \l_@@_cell_box { } }

```

We put a `{minipage}` to give to the user the ability to put a command such as `\centering` in the `\RowStyle`.

```

2498 \begin { minipage } { 5 cm } \arraybackslash
2499 }
2500 c
2501 < {
2502   \end { minipage }
2503   \@@_cell_end:
2504 }
2505 }
2506 \int_gincr:N \c@jCol
2507 \@@_patch_preamble_xi:n
2508 }
2509 }

```

After a specifier of column, we have to test whether there is one or several `<{...}` because, after those potential `<{...}`, we have to insert `!\skip_horizontal:N ...` when the key `vlines` is used. In fact, we have also to test whether there is, after the `<{...}`, a `@{...}`.

```

2510 \cs_new_protected:Npn \@@_patch_preamble_xi:n #1
2511 {
2512   \str_if_eq:nnTF { #1 } { < }
2513   \@@_patch_preamble_xiii:n
2514   {
2515     \str_if_eq:nnTF { #1 } { @ }
2516     \@@_patch_preamble_xv:n
2517     {

```

```

2518 \tl_if_eq:NnTF \l_@@_vlines_clist { all }
2519 {
2520   \tl_gput_right:Nn \g_@@_preamble_tl
2521   { ! { \skip_horizontal:N \arrayrulewidth } }
2522 }
2523 {
2524   \exp_args:NNx
2525   \clist_if_in:NnT \l_@@_vlines_clist { \int_eval:n { \c@jCol + 1 } }
2526   {
2527     \tl_gput_right:Nn \g_@@_preamble_tl
2528     { ! { \skip_horizontal:N \arrayrulewidth } }
2529   }
2530 }
2531 \@@_patch_preamble:n { #1 }
2532 }
2533 }
2534 }
2535 \cs_new_protected:Npn \@@_patch_preamble_xiii:n #1
2536 {
2537   \tl_gput_right:Nn \g_@@_preamble_tl { < { #1 } }
2538   \@@_patch_preamble_xi:n
2539 }

```

We have to catch a @{...} after a specifier of column because, if we have to draw a vertical rule, we have to add in that @{...} a \hskip corresponding to the width of the vertical rule.

```

2540 \cs_new_protected:Npn \@@_patch_preamble_xv:n #1
2541 {
2542   \tl_if_eq:NnTF \l_@@_vlines_clist { all }
2543   {
2544     \tl_gput_right:Nn \g_@@_preamble_tl
2545     { @ { #1 \skip_horizontal:N \arrayrulewidth } }
2546   }
2547   {
2548     \exp_args:NNx
2549     \clist_if_in:NnT \l_@@_vlines_clist { \int_eval:n { \c@jCol + 1 } }
2550     {
2551       \tl_gput_right:Nn \g_@@_preamble_tl
2552       { @ { #1 \skip_horizontal:N \arrayrulewidth } }
2553     }
2554   }
2555   \@@_patch_preamble:n
2556 }
2557 % \end{macrocode}
2558 %
2559 % \bigskip
2560 % \begin{macrocode}
2561 \cs_new_protected:Npn \@@_set_preamble:Nn #1 #2
2562 {
2563   \group_begin:
2564   \@@_newcolumntype w [ 2 ] { \@@_w: { ##1 } { ##2 } }
2565   \@@_newcolumntype W [ 2 ] { \@@_W: { ##1 } { ##2 } }
2566   \@temptokena { #2 }
2567   \@tempswatrue
2568   \@whilesw \if@tempswa \fi { \@tempswafalse \the \NC@list }
2569   \tl_gclear:N \g_@@_preamble_tl
2570   \exp_after:wN \@@_patch_m_preamble:n \the \@temptokena \q_stop
2571   \group_end:
2572   \tl_set_eq:NN #1 \g_@@_preamble_tl
2573   % \group_end:
2574 }

```

The redefinition of `\multicolumn`

The following command must *not* be protected since it begins with `\multispan` (a TeX primitive).

```
2575 \cs_new:Npn \@@_multicolumn:nnn #1 #2 #3
2576 {
```

The following lines are from the definition of `\multicolumn` in `array` (and *not* in standard LaTeX). The first line aims to raise an error if the user has put more than one column specifier in the preamble of `\multicolumn`.

```
2577 \multispan { #1 }
2578 \begingroup
2579 \cs_set:Npn \@addamp { \if@firstamp \@firstampfalse \else \@preamerr 5 \fi }

2580 \@@_newcolumnntype w [ 2 ] { \@@_w: { ##1 } { ##2 } }
2581 \@@_newcolumnntype W [ 2 ] { \@@_W: { ##1 } { ##2 } }
```

You do the expansion of the (small) preamble with the tools of `array`.

```
2582 \@temptokena = { #2 }
2583 \@tempswatrue
2584 \@whilesw \if@tempswa \fi { \@tempswafalse \the \NC@list }
```

Now, we patch the (small) preamble as we have done with the main preamble of the `array`.

```
2585 \tl_gclear:N \g_@@_preamble_tl
2586 \exp_after:wN \@@_patch_m_preamble:n \the \@temptokena \q_stop
```

The following lines are an adaptation of the definition of `\multicolumn` in `array`.

```
2587 \exp_args:NV \@mkpream \g_@@_preamble_tl
2588 \@addtopreamble \@empty
2589 \endgroup
```

Now, you do a treatment specific to `nicematrix` which has no equivalent in the original definition of `\multicolumn`.

```
2590 \int_compare:nNnT { #1 } > 1
2591 {
2592   \seq_gput_left:Nx \g_@@_multicolumn_cells_seq
2593   { \int_use:N \c@iRow - \int_eval:n { \c@jCol + 1 } }
2594   \seq_gput_left:Nn \g_@@_multicolumn_sizes_seq { #1 }
2595   \seq_gput_right:Nx \g_@@_pos_of_blocks_seq
2596   {
2597     {
2598       \int_compare:nNnTF \c@jCol = 0
2599       { \int_eval:n { \c@iRow + 1 } }
2600       { \int_use:N \c@iRow }
2601     }
2602     { \int_eval:n { \c@jCol + 1 } }
2603     {
2604       \int_compare:nNnTF \c@jCol = 0
2605       { \int_eval:n { \c@iRow + 1 } }
2606       { \int_use:N \c@iRow }
2607     }
2608     { \int_eval:n { \c@jCol + #1 } }
2609     { } % for the name of the block
2610   }
2611 }
```

The following lines were in the original definition of `\multicolumn`.

```
2612 \cs_set:Npn \@sharp { #3 }
2613 \@arstrut
2614 \@preamble
2615 \null
```

We add some lines.

```

2616 \int_gadd:Nn \c@jCol { #1 - 1 }
2617 \int_compare:nNnT \c@jCol > \g_@@_col_total_int
2618 { \int_gset_eq:NN \g_@@_col_total_int \c@jCol }
2619 \ignorespaces
2620 }

```

The following commands will patch the (small) preamble of the `\multicolumn`. All those commands have a `m` in their name to recall that they deal with the redefinition of `\multicolumn`.

```

2621 \cs_new_protected:Npn \@@_patch_m_preamble:n #1
2622 {
2623   \str_case:nnF { #1 }
2624   {
2625     c { \@@_patch_m_preamble_i:n #1 }
2626     l { \@@_patch_m_preamble_i:n #1 }
2627     r { \@@_patch_m_preamble_i:n #1 }
2628     > { \@@_patch_m_preamble_ii:nn #1 }
2629     ! { \@@_patch_m_preamble_ii:nn #1 }
2630     @ { \@@_patch_m_preamble_ii:nn #1 }
2631     | { \@@_patch_m_preamble_iii:n #1 }
2632     p { \@@_patch_m_preamble_iv:nnn t #1 }
2633     m { \@@_patch_m_preamble_iv:nnn c #1 }
2634     b { \@@_patch_m_preamble_iv:nnn b #1 }
2635     \@@_w: { \@@_patch_m_preamble_v:nnnn { } #1 }
2636     \@@_W: { \@@_patch_m_preamble_v:nnnn { \@@_special_W: } #1 }
2637     \q_stop { }
2638   }
2639   { \@@_fatal:nn { unknown~column~type } { #1 } }
2640 }

```

For `c`, `l` and `r`

```

2641 \cs_new_protected:Npn \@@_patch_m_preamble_i:n #1
2642 {
2643   \tl_gput_right:Nn \g_@@_preamble_tl
2644   {
2645     > { \@@_cell_begin:w \str_set:Nn \l_@@_hpos_cell_str { #1 } }
2646     #1
2647     < \@@_cell_end:
2648   }

```

We test for the presence of a `<`.

```

2649 \@@_patch_m_preamble_x:n
2650 }

```

For `>`, `!` and `@`

```

2651 \cs_new_protected:Npn \@@_patch_m_preamble_ii:nn #1 #2
2652 {
2653   \tl_gput_right:Nn \g_@@_preamble_tl { #1 { #2 } }
2654   \@@_patch_m_preamble:n
2655 }

```

For `|`

```

2656 \cs_new_protected:Npn \@@_patch_m_preamble_iii:n #1
2657 {
2658   \tl_gput_right:Nn \g_@@_preamble_tl { #1 }
2659   \@@_patch_m_preamble:n
2660 }

```

For `p`, `m` and `b`

```

2661 \cs_new_protected:Npn \@@_patch_m_preamble_iv:nnn #1 #2 #3
2662 {
2663   \tl_gput_right:Nn \g_@@_preamble_tl

```

```

2664 {
2665   > {
2666     \@@_cell_begin:w
2667     \begin { minipage } [ #1 ] { \dim_eval:n { #3 } }
2668     \mode_leave_vertical:
2669     \arraybackslash
2670     \vrule height \box_ht:N \@arstrutbox depth 0 pt width 0 pt
2671   }
2672   c
2673   < {
2674     \vrule height 0 pt depth \box_dp:N \@arstrutbox width 0 pt
2675     \end { minipage }
2676     \@@_cell_end:
2677   }
2678 }

```

We test for the presence of a <.

```

2679 \@@_patch_m_preamble_x:n
2680 }

```

For w and W

```

2681 \cs_new_protected:Npn \@@_patch_m_preamble_v:nnnn #1 #2 #3 #4
2682 {
2683   \tl_gput_right:Nn \g_@@_preamble_tl
2684   {
2685     > {
2686       \dim_set:Nn \l_@@_col_width_dim { #4 }
2687       \hbox_set:Nw \l_@@_cell_box
2688       \@@_cell_begin:w
2689       \str_set:Nn \l_@@_hpos_cell_str { #3 }
2690     }
2691     c
2692     < {
2693       \@@_cell_end:
2694       \hbox_set_end:
2695       \bool_if:NT \g_@@_rotate_bool \@@_rotate_cell_box:
2696       #1
2697       \@@_adjust_size_box:
2698       \makebox [ #4 ] [ #3 ] { \box_use_drop:N \l_@@_cell_box }
2699     }
2700   }

```

We test for the presence of a <.

```

2701 \@@_patch_m_preamble_x:n
2702 }

```

After a specifier of column, we have to test whether there is one or several <{...}.

```

2703 \cs_new_protected:Npn \@@_patch_m_preamble_x:n #1
2704 {
2705   \str_if_eq:nnTF { #1 } { < }
2706   \@@_patch_m_preamble_ix:n
2707   { \@@_patch_m_preamble:n { #1 } }
2708 }
2709 \cs_new_protected:Npn \@@_patch_m_preamble_ix:n #1
2710 {
2711   \tl_gput_right:Nn \g_@@_preamble_tl { < { #1 } }
2712   \@@_patch_m_preamble_x:n
2713 }

```

The command `\@@_put_box_in_flow:` puts the box `\l_tmpa_box` (which contains the array) in the flow. It is used for the environments with delimiters. First, we have to modify the height and the depth to take back into account the potential exterior rows (the total height of the first row has been computed in `\l_tmpa_dim` and the total height of the potential last row in `\l_tmpb_dim`).

```

2714 \cs_new_protected:Npn \@@_put_box_in_flow:
2715 {
2716   \box_set_ht:Nn \l_tmpa_box { \box_ht:N \l_tmpa_box + \l_tmpa_dim }
2717   \box_set_dp:Nn \l_tmpa_box { \box_dp:N \l_tmpa_box + \l_tmpb_dim }
2718   \tl_if_eq:NnTF \l_@@_baseline_tl { c }
2719   { \box_use_drop:N \l_tmpa_box }
2720   \@@_put_box_in_flow_i:
2721 }

```

The command `\@@_put_box_in_flow_i:` is used when the value of `\l_@@_baseline_tl` is different of `c` (which is the initial value and the most used).

```

2722 \cs_new_protected:Npn \@@_put_box_in_flow_i:
2723 {
2724   \pgfpicture
2725     \@@_qpoint:n { row - 1 }
2726     \dim_gset_eq:NN \g_tmpa_dim \pgf@y
2727     \@@_qpoint:n { row - \int_eval:n { \c@iRow + 1 } }
2728     \dim_gadd:Nn \g_tmpa_dim \pgf@y
2729     \dim_gset:Nn \g_tmpa_dim { 0.5 \g_tmpa_dim }

```

Now, `\g_tmpa_dim` contains the y -value of the center of the array (the delimiters are centered in relation with this value).

```

2730   \str_if_in:NnTF \l_@@_baseline_tl { line- }
2731   {
2732     \int_set:Nn \l_tmpa_int
2733     {
2734       \str_range:Nnn
2735       \l_@@_baseline_tl
2736       6
2737       { \tl_count:V \l_@@_baseline_tl }
2738     }
2739     \@@_qpoint:n { row - \int_use:N \l_tmpa_int }
2740   }
2741   {
2742     \str_case:VnF \l_@@_baseline_tl
2743     {
2744       { t } { \int_set:Nn \l_tmpa_int 1 }
2745       { b } { \int_set_eq:NN \l_tmpa_int \c@iRow }
2746     }
2747     { \int_set:Nn \l_tmpa_int \l_@@_baseline_tl }
2748     \bool_lazy_or:nnT
2749     { \int_compare_p:nNn \l_tmpa_int < \l_@@_first_row_int }
2750     { \int_compare_p:nNn \l_tmpa_int > \g_@@_row_total_int }
2751     {
2752       \@@_error:n { bad~value~for~baseline }
2753       \int_set:Nn \l_tmpa_int 1
2754     }
2755     \@@_qpoint:n { row - \int_use:N \l_tmpa_int - base }

```

We take into account the position of the mathematical axis.

```

2756     \dim_gsub:Nn \g_tmpa_dim { \fontdimen22 \textfont2 }
2757   }
2758   \dim_gsub:Nn \g_tmpa_dim \pgf@y

```

Now, `\g_tmpa_dim` contains the value of the y translation we have to to.

```

2759   \endpgfpicture
2760   \box_move_up:nn \g_tmpa_dim { \box_use_drop:N \l_tmpa_box }
2761   \box_use_drop:N \l_tmpa_box
2762 }

```

The following command is *always* used by `{NiceArrayWithDelims}` (even if, in fact, there is no tabular notes: in fact, it's not possible to know whether there is tabular notes or not before the composition of the blocks).

```

2763 \cs_new_protected:Npn \@@_use_arraybox_with_notes_c:

```



```
2764 {
```

With an environment `{Matrix}`, you want to remove the exterior `\arraycolsep` but we don't know the number of columns (since there is no preamble) and that's why we can't put `@{}` at the end of the preamble. That's why we remove a `\arraycolsep` now.

```
2765 \bool_lazy_and:nNT \l_@@_Matrix_bool \g_@@_NiceArray_bool
2766 {
2767   \box_set_wd:Nn \l_@@_the_array_box
2768   { \box_wd:N \l_@@_the_array_box - \arraycolsep }
2769 }
```

We need a `{minipage}` because we will insert a LaTeX list for the tabular notes (that means that a `\vtop{\hsize=...}` is not enough).

```
2770 \begin { minipage } [ t ] { \box_wd:N \l_@@_the_array_box }
2771 \bool_if:NT \l_@@_caption_above_bool
2772 {
2773   \tl_if_empty:NF \l_@@_caption_tl
2774   {
2775     \bool_set_false:N \g_@@_caption_finished_bool
2776     \int_gzero:N \c@tabularnote
2777     \@@_insert_caption:
```

If there is one or several commands `\tabularnote` in the caption, we will write in the aux file the number of such tabular notes.

```
2778     \int_gset:Nn \c@tabularnote
2779     { \seq_count:N \g_@@_notes_in_caption_seq }
2780     \int_compare:nNnF \c@tabularnote = 0
2781     {
2782       \tl_gput_right:Nx \g_@@_aux_tl
2783       {
2784         \tl_set:Nn \exp_not:N \l_@@_note_in_caption_tl
2785         { \int_eval:n { \c@tabularnote } }
2786       }
2787     }
2788   }
2789 }
```

The `\hbox` avoids that the `pgfpicture` inside `\@@_draw_blocks` adds a extra vertical space before the notes.

```
2790 \hbox
2791 {
2792   \box_use_drop:N \l_@@_the_array_box
```

We have to draw the blocks right now because there may be tabular notes in some blocks (which are not mono-column: the blocks which are mono-column have been composed in boxes yet)... and we have to create (potentially) the extra nodes before creating the blocks since there are `medium` nodes to create for the blocks.

```
2793 \@@_create_extra_nodes:
2794 \seq_if_empty:NF \g_@@_blocks_seq \@@_draw_blocks:
2795 }
```

We don't do the following test with `\c@tabularnote` because the value of that counter is not reliable when the command `\ttabbox` of `floatrow` is used (because `\ttabbox` de-activate `\stepcounter` because if compiles several twice its tabular).

```
2796 \bool_lazy_any:nT
2797 {
2798   { ! \seq_if_empty_p:N \g_@@_notes_seq }
2799   { ! \seq_if_empty_p:N \g_@@_notes_in_caption_seq }
2800   { ! \tl_if_empty_p:V \g_@@_tabularnote_tl }
2801 }
2802 \@@_insert_tabularnotes:
2803 \cs_set_eq:NN \tabularnote \@@_tabularnote_error:n
2804 \bool_if:NF \l_@@_caption_above_bool \@@_insert_caption:
2805 \end { minipage }
2806 }
```

```

2807 \cs_new_protected:Npn \@@_insert_caption:
2808 {
2809   \tl_if_empty:NF \l_@@_caption_tl
2810   {
2811     \cs_if_exist:NTF \@capytype
2812     { \@@_insert_caption_i: }
2813     { \@@_error:n { caption~outside~float } }
2814   }
2815 }

```

```

2816 \cs_new_protected:Npn \@@_insert_caption_i:
2817 {
2818   \group_begin:

```

The flag `\l_@@_in_caption_bool` affects only the behaviour of the command `\tabularnote` when used in the caption.

```

2819   \bool_set_true:N \l_@@_in_caption_bool

```

The package `floatrow` does a redefinition of `\@makecaption` which will extract the caption from the tabular. However, the old version of `\@makecaption` has been stored by `floatrow` in `\FR@makecaption`. That's why we restore the old version.

```

2820   \bool_if:NT \c_@@_floatrow_loaded_bool
2821   { \cs_set_eq:NN \@makecaption \FR@makecaption }
2822   \tl_if_empty:NTF \l_@@_short_caption_tl
2823   { \caption { \l_@@_caption_tl } }
2824   { \caption [ \l_@@_short_caption_tl ] { \l_@@_caption_tl } }
2825   \tl_if_empty:NF \l_@@_label_tl { \label { \l_@@_label_tl } }
2826   \group_end:
2827 }

```

```

2828 \cs_new_protected:Npn \@@_tabularnote_error:n #1
2829 {
2830   \@@_error_or_warning:n { tabularnote~below~the~tabular }
2831   \@@_gredirect_none:n { tabularnote~below~the~tabular }
2832 }

```

```

2833 \cs_new_protected:Npn \@@_insert_tabularnotes:
2834 {
2835   \seq_concat:NNN \g_@@_notes_seq \g_@@_notes_in_caption_seq \g_@@_notes_seq
2836   \int_set:Nn \c@tabularnote { \seq_count:N \g_@@_notes_seq }
2837   \skip_vertical:N 0.65ex

```

The TeX group is for potential specifications in the `\l_@@_notes_code_before_tl`.

```

2838   \group_begin:
2839   \l_@@_notes_code_before_tl
2840   \tl_if_empty:NF \g_@@_tabularnote_tl
2841   {
2842     \g_@@_tabularnote_tl \par
2843     \tl_gclear:N \g_@@_tabularnote_tl
2844   }

```

We compose the tabular notes with a list of `enumitem`. The `\strut` and the `\unskip` are designed to give the ability to put a `\bottomrule` at the end of the notes with a good vertical space.

```

2845   \int_compare:nNnT \c@tabularnote > 0
2846   {
2847     \bool_if:NTF \l_@@_notes_para_bool
2848     {
2849       \begin { tabularnotes* }
2850       \seq_map_inline:Nn \g_@@_notes_seq { \item ##1 } \strut
2851       \end { tabularnotes* }

```

The following `\par` is mandatory for the event that the user has put `\footnotesize` (for example) in the `notes/code-before`.

```

2852     \par
2853   }

```

```

2854     {
2855         \tabularnotes
2856         \seq_map_inline:Nn \g_@@_notes_seq { \item ##1 } \strut
2857     \endtabularnotes
2858     }
2859 }
2860 \unskip
2861 \group_end:
2862 \bool_if:NT \l_@@_notes_bottomrule_bool
2863 {
2864     \bool_if:NTF \c_@@_booktabs_loaded_bool
2865     {

```

The two dimensions `\aboverulesep` et `\heavyrulewidth` are parameters defined by `booktabs`.

```

2866         \skip_vertical:N \aboverulesep
\CT@arc@ is the specification of color defined by colortbl but you use it even if colortbl is not loaded.
2867     { \CT@arc@ \hrule height \heavyrulewidth }
2868 }
2869 { \@@_error_or_warning:n { bottomrule~without~booktabs } }
2870 }
2871 \l_@@_notes_code_after_tl
2872 \seq_gclear:N \g_@@_notes_seq
2873 \seq_gclear:N \g_@@_notes_in_caption_seq
2874 \int_gzero:N \c@tabularnote
2875 }

```

The case of `baseline` equal to `b`. Remember that, when the key `b` is used, the `{array}` (of `array`) is constructed with the option `t` (and not `b`). Now, we do the translation to take into account the option `b`.

```

2876 \cs_new_protected:Npn \@@_use_arraybox_with_notes_b:
2877 {
2878     \pgfpicture
2879     \@@_qpoint:n { row - 1 }
2880     \dim_gset_eq:NN \g_tmpa_dim \pgf@y
2881     \@@_qpoint:n { row - \int_use:N \c@iRow - base }
2882     \dim_gsub:Nn \g_tmpa_dim \pgf@y
2883     \endpgfpicture
2884     \dim_gadd:Nn \g_tmpa_dim \arrayrulewidth
2885     \int_compare:nNnT \l_@@_first_row_int = 0
2886     {
2887         \dim_gadd:Nn \g_tmpa_dim \g_@@_ht_row_zero_dim
2888         \dim_gadd:Nn \g_tmpa_dim \g_@@_dp_row_zero_dim
2889     }
2890     \box_move_up:nn \g_tmpa_dim { \hbox { \@@_use_arraybox_with_notes_c: } }
2891 }

```

Now, the general case.

```

2892 \cs_new_protected:Npn \@@_use_arraybox_with_notes:
2893 {

```

We convert a value of `t` to a value of 1.

```

2894     \tl_if_eq:NnT \l_@@_baseline_tl { t }
2895     { \tl_set:Nn \l_@@_baseline_tl { 1 } }

```

Now, we convert the value of `\l_@@_baseline_tl` (which should represent an integer) to an integer stored in `\l_tmpa_int`.

```

2896     \pgfpicture
2897     \@@_qpoint:n { row - 1 }
2898     \dim_gset_eq:NN \g_tmpa_dim \pgf@y
2899     \str_if_in:NnTF \l_@@_baseline_tl { line- }
2900     {
2901         \int_set:Nn \l_tmpa_int
2902         {
2903             \str_range:Nnn

```

```

2904         \l_@@_baseline_tl
2905         6
2906         { \tl_count:V \l_@@_baseline_tl }
2907     }
2908     \@@_qpoint:n { row - \int_use:N \l_tmpa_int }
2909 }
2910 {
2911     \int_set:Nn \l_tmpa_int \l_@@_baseline_tl
2912     \bool_lazy_or:nnT
2913     { \int_compare_p:nNn \l_tmpa_int < \l_@@_first_row_int }
2914     { \int_compare_p:nNn \l_tmpa_int > \g_@@_row_total_int }
2915     {
2916         \@@_error:n { bad-value-for-baseline }
2917         \int_set:Nn \l_tmpa_int 1
2918     }
2919     \@@_qpoint:n { row - \int_use:N \l_tmpa_int - base }
2920 }
2921 \dim_gsub:Nn \g_tmpa_dim \pgf@y
2922 \endpgfpicture
2923 \dim_gadd:Nn \g_tmpa_dim \arrayrulewidth
2924 \int_compare:nNnT \l_@@_first_row_int = 0
2925 {
2926     \dim_gadd:Nn \g_tmpa_dim \g_@@_ht_row_zero_dim
2927     \dim_gadd:Nn \g_tmpa_dim \g_@@_dp_row_zero_dim
2928 }
2929 \box_move_up:nn \g_tmpa_dim { \hbox { \@@_use_arraybox_with_notes_c: } }
2930 }

```

The command `\@@_put_box_in_flow_bis:` is used when the option `delimiters/max-width` is used because, in this case, we have to adjust the widths of the delimiters. The arguments `#1` and `#2` are the delimiters specified by the user.

```

2931 \cs_new_protected:Npn \@@_put_box_in_flow_bis:nn #1 #2
2932 {

```

We will compute the real width of both delimiters used.

```

2933     \dim_zero_new:N \l_@@_real_left_delim_dim
2934     \dim_zero_new:N \l_@@_real_right_delim_dim
2935     \hbox_set:Nn \l_tmpb_box
2936     {
2937         \c_math_toggle_token
2938         \left #1
2939         \vcenter
2940         {
2941             \vbox_to_ht:nn
2942             { \box_ht_plus_dp:N \l_tmpa_box }
2943             { }
2944         }
2945         \right .
2946         \c_math_toggle_token
2947     }
2948     \dim_set:Nn \l_@@_real_left_delim_dim
2949     { \box_wd:N \l_tmpb_box - \nulldelimiterspace }
2950     \hbox_set:Nn \l_tmpb_box
2951     {
2952         \c_math_toggle_token
2953         \left .
2954         \vbox_to_ht:nn
2955         { \box_ht_plus_dp:N \l_tmpa_box }
2956         { }
2957         \right #2
2958         \c_math_toggle_token
2959     }
2960     \dim_set:Nn \l_@@_real_right_delim_dim
2961     { \box_wd:N \l_tmpb_box - \nulldelimiterspace }

```

Now, we can put the box in the TeX flow with the horizontal adjustments on both sides.

```

2962 \skip_horizontal:N \l_@@_left_delim_dim
2963 \skip_horizontal:N -\l_@@_real_left_delim_dim
2964 @@_put_box_in_flow:
2965 \skip_horizontal:N \l_@@_right_delim_dim
2966 \skip_horizontal:N -\l_@@_real_right_delim_dim
2967 }

```

The construction of the array in the environment `{NiceArrayWithDelims}` is, in fact, done by the environment `{@@-light-syntax}` or by the environment `{@@-normal-syntax}` (whether the option `light-syntax` is in force or not). When the key `light-syntax` is not used, the construction is a standard environment (and, thus, it's possible to use verbatim in the array).

```

2968 \NewDocumentEnvironment { @@-normal-syntax } { }

```

First, we test whether the environment is empty. If it is empty, we raise a fatal error (it's only a security). In order to detect whether it is empty, we test whether the next token is `\end` and, if it's the case, we test if this is the end of the environment (if it is not, an standard error will be raised by LaTeX for incorrect nested environments).

```

2969 {
2970   \peek_remove_spaces:n
2971   {
2972     \peek_meaning:NTF \end
2973     \@@_analyze_end:Nn
2974     {
2975       \@@_transform_preamble:

```

Here is the call to `\array` (we have a dedicated macro `\@@_array:n` because of compatibility with the classes `revtex4-1` and `revtex4-2`).

```

2976       \@@_array:V \g_@@_preamble_tl
2977     }
2978   }
2979 }
2980 {
2981   \@@_create_col_nodes:
2982   \endarray
2983 }

```

When the key `light-syntax` is in force, we use an environment which takes its whole body as an argument (with the specifier `b`).

```

2984 \NewDocumentEnvironment { @@-light-syntax } { b }
2985 {

```

First, we test whether the environment is empty. It's only a security. Of course, this test is more easy than the similar test for the “normal syntax” because we have the whole body of the environment in `#1`.

```

2986   \tl_if_empty:nT { #1 } { \@@_fatal:n { empty~environment } }
2987   \tl_map_inline:nn { #1 }
2988   {
2989     \str_if_eq:nnT { ##1 } { & }
2990     { \@@_fatal:n { ampersand~in~light-syntax } }
2991     \str_if_eq:nnT { ##1 } { \ }
2992     { \@@_fatal:n { double-backslash~in~light-syntax } }
2993   }

```

Now, you extract the `\CodeAfter` of the body of the environment. Maybe, there is no command `\CodeAfter` in the body. That's why you put a marker `\CodeAfter` after `#1`. If there is yet a `\CodeAfter` in `#1`, this second (or third...) `\CodeAfter` will be caught in the value of `\g_nicematrix_code_after_tl`. That doesn't matter because `\CodeAfter` will be set to *no-op* before the execution of `\g_nicematrix_code_after_tl`.

```

2994   \@@_light_syntax_i:w #1 \CodeAfter \q_stop

```

The command `\array` is hidden somewhere in `\@@_light_syntax_i:w`.

```
2995 }

```

Now, the second part of the environment. We must leave these lines in the second part (and not put them in the first part even though we caught the whole body of the environment with an argument of type `b`) in order to have the columns `S` of `siunitx` working fine.

```
2996 {
2997   \@@_create_col_nodes:
2998   \endarray
2999 }

3000 \cs_new_protected:Npn \@@_light_syntax_i:w #1\CodeAfter #2\q_stop
3001 {
3002   \tl_gput_right:Nn \g_nicematrix_code_after_tl { #2 }

```

The body of the array, which is stored in the argument `#1`, is now splitted into items (and *not* tokens).

```
3003   \seq_clear_new:N \l_@@_rows_seq

```

We rescan the character of end of line in order to have the correct catcode.

```
3004   \tl_set_rescan:Nno \l_@@_end_of_row_tl { } \l_@@_end_of_row_tl
3005   \seq_set_split:Nvn \l_@@_rows_seq \l_@@_end_of_row_tl { #1 }

```

We delete the last row if it is empty.

```
3006   \seq_pop_right:NN \l_@@_rows_seq \l_tmpa_tl
3007   \tl_if_empty:NF \l_tmpa_tl
3008   { \seq_put_right:Nv \l_@@_rows_seq \l_tmpa_tl }

```

If the environment uses the option `last-row` without value (i.e. without saying the number of the rows), we have now the opportunity to compute that value. We do it, and so, if the token list `\l_@@_code_for_last_row_tl` is not empty, we will use directly where it should be.

```
3009   \int_compare:nNnT \l_@@_last_row_int = { -1 }
3010   { \int_set:Nn \l_@@_last_row_int { \seq_count:N \l_@@_rows_seq } }

```

The new value of the body (that is to say after replacement of the separators of rows and columns by `\\` and `&`) of the environment will be stored in `\l_@@_new_body_tl` (that part of the implementation has been changed in the version 6.11 of `nicematrix` in order to allow the use of commands such as `\hline` or `\hdottedline` with the key `light-syntax`).

```
3011   \tl_clear_new:N \l_@@_new_body_tl
3012   \int_zero_new:N \l_@@_nb_cols_int

```

First, we treat the first row.

```
3013   \seq_pop_left:NN \l_@@_rows_seq \l_tmpa_tl
3014   \@@_line_with_light_syntax:V \l_tmpa_tl

```

Now, the other rows (with the same treatment, excepted that we have to insert `\\` between the rows).

```
3015   \seq_map_inline:Nn \l_@@_rows_seq
3016   {
3017     \tl_put_right:Nn \l_@@_new_body_tl { \\ }
3018     \@@_line_with_light_syntax:n { ##1 }
3019   }

3020   \int_compare:nNnT \l_@@_last_col_int = { -1 }
3021   {
3022     \int_set:Nn \l_@@_last_col_int
3023     { \l_@@_nb_cols_int - 1 + \l_@@_first_col_int }
3024   }

```

Now, we can construct the preamble: if the user has used the key `last-col`, we have the correct number of columns even though the user has used `last-col` without value.

```
3025   \@@_transform_preamble:

```

The call to `\array` is in the following command (we have a dedicated macro `\@@_array:n` because of compatibility with the classes `revtex4-1` and `revtex4-2`).

```
3026   \@@_array:V \g_@@_preamble_tl \l_@@_new_body_tl
3027 }

```

```

3028 \cs_new_protected:Npn \@@_line_with_light_syntax:n #1
3029 {
3030   \seq_clear_new:N \l_@@_cells_seq
3031   \seq_set_split:Nnn \l_@@_cells_seq { ~ } { #1 }
3032   \int_set:Nn \l_@@_nb_cols_int
3033   {
3034     \int_max:nn
3035     \l_@@_nb_cols_int
3036     { \seq_count:N \l_@@_cells_seq }
3037   }
3038   \seq_pop_left:NN \l_@@_cells_seq \l_tmpa_tl
3039   \tl_put_right:NV \l_@@_new_body_tl \l_tmpa_tl
3040   \seq_map_inline:Nn \l_@@_cells_seq
3041   { \tl_put_right:Nn \l_@@_new_body_tl { & ##1 } }
3042 }
3043 \cs_generate_variant:Nn \@@_line_with_light_syntax:n { V }

```

The following command is used by the code which detects whether the environment is empty (we raise a fatal error in this case: it's only a security). When this command is used, #1 is, in fact, always \end.

```

3044 \cs_new_protected:Npn \@@_analyze_end:Nn #1 #2
3045 {
3046   \str_if_eq:VnT \g_@@_name_env_str { #2 }
3047   { \@@_fatal:n { empty~environment } }

```

We repeat in the stream the \end{...} we have extracted and the user will have an error for incorrect nested environments.

```

3048   \end { #2 }
3049 }

```

The command \@@_create_col_nodes: will construct a special last row. That last row is a false row used to create the col nodes and to fix the width of the columns (when the array is constructed with an option which specifies the width of the columns).

```

3050 \cs_new:Npn \@@_create_col_nodes:
3051 {
3052   \crcr
3053   \int_compare:nNnT \l_@@_first_col_int = 0
3054   {
3055     \omit
3056     \hbox_overlap_left:n
3057     {
3058       \bool_if:NT \l_@@_code_before_bool
3059       { \pgfsys@markposition { \@@_env: - col - 0 } }
3060       \pgfpicture
3061       \pgfrememberpicturepositiononpagetrue
3062       \pgfcoordinate { \@@_env: - col - 0 } \pgfpointorigin
3063       \str_if_empty:NF \l_@@_name_str
3064       { \pgfnodealias { \l_@@_name_str - col - 0 } { \@@_env: - col - 0 } }
3065       \endpgfpicture
3066       \skip_horizontal:N 2\col@sep
3067       \skip_horizontal:N \g_@@_width_first_col_dim
3068     }
3069     &
3070   }
3071   \omit

```

The following instruction must be put after the instruction \omit.

```

3072   \bool_gset_true:N \g_@@_row_of_col_done_bool

```

First, we put a col node on the left of the first column (of course, we have to do that *after* the \omit).

```

3073   \int_compare:nNnTF \l_@@_first_col_int = 0
3074   {

```

```

3075 \bool_if:NT \l_@@_code_before_bool
3076 {
3077     \hbox
3078     {
3079         \skip_horizontal:N -0.5\arrayrulewidth
3080         \pgfsys@markposition { \@@_env: - col - 1 }
3081         \skip_horizontal:N 0.5\arrayrulewidth
3082     }
3083 }
3084 \pgfpicture
3085 \pgfrememberpicturepositiononpagetrue
3086 \pgfcoordinate { \@@_env: - col - 1 }
3087 { \pgfpoint { - 0.5 \arrayrulewidth } \c_zero_dim }
3088 \str_if_empty:NF \l_@@_name_str
3089 { \pgfnodealias { \l_@@_name_str - col - 1 } { \@@_env: - col - 1 } }
3090 \endpgfpicture
3091 }
3092 {
3093     \bool_if:NT \l_@@_code_before_bool
3094     {
3095         \hbox
3096         {
3097             \skip_horizontal:N 0.5\arrayrulewidth
3098             \pgfsys@markposition { \@@_env: - col - 1 }
3099             \skip_horizontal:N -0.5\arrayrulewidth
3100         }
3101     }
3102     \pgfpicture
3103     \pgfrememberpicturepositiononpagetrue
3104     \pgfcoordinate { \@@_env: - col - 1 }
3105     { \pgfpoint { 0.5 \arrayrulewidth } \c_zero_dim }
3106     \str_if_empty:NF \l_@@_name_str
3107     { \pgfnodealias { \l_@@_name_str - col - 1 } { \@@_env: - col - 1 } }
3108     \endpgfpicture
3109 }

```

We compute in `\g_tmpa_skip` the common width of the columns (it's a skip and not a dimension). We use a global variable because we are in a cell of an `\halign` and because we have to use this variable in other cells (of the same row). The affectation of `\g_tmpa_skip`, like all the affectations, must be done after the `\omit` of the cell.

We give a default value for `\g_tmpa_skip` (0 pt plus 1 fill) but it will just after be erased by a fixed value in the concerned cases.

```

3110 \skip_gset:Nn \g_tmpa_skip { 0 pt+plus 1 fill }
3111 \bool_if:NF \l_@@_auto_columns_width_bool
3112 { \dim_compare:nNnT \l_@@_columns_width_dim > \c_zero_dim }
3113 {
3114     \bool_lazy_and:nnTF
3115     \l_@@_auto_columns_width_bool
3116     { \bool_not_p:n \l_@@_block_auto_columns_width_bool }
3117     { \skip_gset_eq:NN \g_tmpa_skip \g_@@_max_cell_width_dim }
3118     { \skip_gset_eq:NN \g_tmpa_skip \l_@@_columns_width_dim }
3119     \skip_gadd:Nn \g_tmpa_skip { 2 \col@sep }
3120 }
3121 \skip_horizontal:N \g_tmpa_skip
3122 \hbox
3123 {
3124     \bool_if:NT \l_@@_code_before_bool
3125     {
3126         \hbox
3127         {
3128             \skip_horizontal:N -0.5\arrayrulewidth
3129             \pgfsys@markposition { \@@_env: - col - 2 }
3130             \skip_horizontal:N 0.5\arrayrulewidth

```



```

3131     }
3132   }
3133   \pgfpicture
3134   \pgfrememberpicturepositiononpagetrue
3135   \pgfcoordinate { \@@_env: - col - 2 }
3136   { \pgfpoint { - 0.5 \arrayrulewidth } \c_zero_dim }
3137   \str_if_empty:NF \l_@@_name_str
3138   { \pgfnodealias { \l_@@_name_str - col - 2 } { \@@_env: - col - 2 } }
3139   \endpgfpicture
3140 }

```

We begin a loop over the columns. The integer `\g_tmpa_int` will be the number of the current column. This integer is used for the Tikz nodes.

```

3141   \int_gset:Nn \g_tmpa_int 1
3142   \bool_if:NTF \g_@@_last_col_found_bool
3143   { \prg_replicate:nn { \int_max:nn { \g_@@_col_total_int - 3 } 0 } }
3144   { \prg_replicate:nn { \int_max:nn { \g_@@_col_total_int - 2 } 0 } }
3145   {
3146     &
3147     \omit
3148     \int_gincr:N \g_tmpa_int

```

The incrementation of the counter `\g_tmpa_int` must be done after the `\omit` of the cell.

```

3149     \skip_horizontal:N \g_tmpa_skip
3150     \bool_if:NT \l_@@_code_before_bool
3151     {
3152       \hbox
3153       {
3154         \skip_horizontal:N -0.5\arrayrulewidth
3155         \pgfsys@markposition
3156         { \@@_env: - col - \int_eval:n { \g_tmpa_int + 1 } }
3157         \skip_horizontal:N 0.5\arrayrulewidth
3158       }
3159     }

```

We create the col node on the right of the current column.

```

3160     \pgfpicture
3161     \pgfrememberpicturepositiononpagetrue
3162     \pgfcoordinate { \@@_env: - col - \int_eval:n { \g_tmpa_int + 1 } }
3163     { \pgfpoint { - 0.5 \arrayrulewidth } \c_zero_dim }
3164     \str_if_empty:NF \l_@@_name_str
3165     {
3166       \pgfnodealias
3167       { \l_@@_name_str - col - \int_eval:n { \g_tmpa_int + 1 } }
3168       { \@@_env: - col - \int_eval:n { \g_tmpa_int + 1 } }
3169     }
3170     \endpgfpicture
3171   }

```

```

3172   &
3173   \omit

```

The two following lines have been added on 2021-12-15 to solve a bug mentionned by Joao Luis Soares by mail.

```

3174   \int_compare:nNnT \g_@@_col_total_int = 1
3175   { \skip_gset:Nn \g_tmpa_skip { 0 pt~plus 1 fill } }
3176   \skip_horizontal:N \g_tmpa_skip
3177   \int_gincr:N \g_tmpa_int
3178   \bool_lazy_all:nT
3179   {
3180     \g_@@_NiceArray_bool
3181     { \bool_not_p:n \l_@@_NiceTabular_bool }
3182     { \clist_if_empty_p:N \l_@@_vlines_clist }
3183     { \bool_not_p:n \l_@@_exterior_arraycolsep_bool }

```

```

3184         { ! \l_@@_bar_at_end_of_pream_bool }
3185     }
3186     { \skip_horizontal:N -\col@sep }
3187     \bool_if:NT \l_@@_code_before_bool
3188     {
3189         \hbox
3190         {
3191             \skip_horizontal:N -0.5\arrayrulewidth

```

With an environment `{Matrix}`, you want to remove the exterior `\arraycolsep` but we don't know the number of columns (since there is no preamble) and that's why we can't put `@{}` at the end of the preamble. That's why we remove a `\arraycolsep` now.

```

3192         \bool_lazy_and:nnT \l_@@_Matrix_bool \g_@@_NiceArray_bool
3193         { \skip_horizontal:N -\arraycolsep }
3194         \pgfsys@markposition
3195         { \@@_env: - col - \int_eval:n { \g_tmpa_int + 1 } }
3196         \g_tmpa_int + 1 } }
3197         \skip_horizontal:N 0.5\arrayrulewidth
3198         \bool_lazy_and:nnT \l_@@_Matrix_bool \g_@@_NiceArray_bool
3199         { \skip_horizontal:N \arraycolsep }
3200     }
3201 }
3202 \pgfpicture
3203 \pgfrememberpicturepositiononpagetrue
3204 \pgfcoordinate { \@@_env: - col - \int_eval:n { \g_tmpa_int + 1 } }
3205 {
3206     \bool_lazy_and:nnTF \l_@@_Matrix_bool \g_@@_NiceArray_bool
3207     {
3208         \pgfpoint
3209         { - 0.5 \arrayrulewidth - \arraycolsep }
3210         \c_zero_dim
3211     }
3212     { \pgfpoint { - 0.5 \arrayrulewidth } \c_zero_dim }
3213 }
3214 \str_if_empty:NF \l_@@_name_str
3215 {
3216     \pgfnodealias
3217     { \l_@@_name_str - col - \int_eval:n { \g_tmpa_int + 1 } }
3218     { \@@_env: - col - \int_eval:n { \g_tmpa_int + 1 } }
3219 }
3220 \endpgfpicture

3221 \bool_if:NT \g_@@_last_col_found_bool
3222 {
3223     \hbox_overlap_right:n
3224     {
3225         \skip_horizontal:N \g_@@_width_last_col_dim
3226         \bool_if:NT \l_@@_code_before_bool
3227         {
3228             \pgfsys@markposition
3229             { \@@_env: - col - \int_eval:n { \g_@@_col_total_int + 1 } }
3230         }
3231         \pgfpicture
3232         \pgfrememberpicturepositiononpagetrue
3233         \pgfcoordinate
3234         { \@@_env: - col - \int_eval:n { \g_@@_col_total_int + 1 } }
3235         \pgfpointorigin
3236         \str_if_empty:NF \l_@@_name_str
3237         {
3238             \pgfnodealias
3239             {
3240                 \l_@@_name_str - col
3241                 - \int_eval:n { \g_@@_col_total_int + 1 }

```

```

3242         }
3243         { \@@_env: - col - \int_eval:n { \g_@@_col_total_int + 1 } }
3244     }
3245     \endpgfpicture
3246 }
3247 }
3248 \cr
3249 }

```

Here is the preamble for the “first column” (if the user uses the key `first-col`)

```

3250 \tl_const:Nn \c_@@_preamble_first_col_tl
3251 {
3252     >
3253     {

```

At the beginning of the cell, we link `\CodeAfter` to a command which do begins with `\` (whereas the standard version of `\CodeAfter` begins does not).

```

3254         \cs_set_eq:NN \CodeAfter \@@_CodeAfter_i:
3255         \bool_gset_true:N \g_@@_after_col_zero_bool
3256         \@@_begin_of_row:

```

The contents of the cell is constructed in the box `\l_@@_cell_box` because we have to compute some dimensions of this box.

```

3257         \hbox_set:Nw \l_@@_cell_box
3258         \@@_math_toggle_token:
3259         \bool_if:NT \l_@@_small_bool \scriptstyle

```

We insert `\l_@@_code_for_first_col_tl...` but we don’t insert it in the potential “first row” and in the potential “last row”.

```

3260         \bool_lazy_and:nnT
3261         { \int_compare_p:nNn \c@iRow > 0 }
3262         {
3263             \bool_lazy_or_p:nn
3264             { \int_compare_p:nNn \l_@@_last_row_int < 0 }
3265             { \int_compare_p:nNn \c@iRow < \l_@@_last_row_int }
3266         }
3267         {
3268             \l_@@_code_for_first_col_tl
3269             \xglobal \colorlet { nicematrix-first-col } { . }
3270         }
3271     }

```

Be careful: despite this letter `l` the cells of the “first column” are composed in a `R` manner since they are composed in a `\hbox_overlap_left:n`.

```

3272     l
3273     <
3274     {
3275         \@@_math_toggle_token:
3276         \hbox_set_end:
3277         \bool_if:NT \g_@@_rotate_bool \@@_rotate_cell_box:
3278         \@@_adjust_size_box:
3279         \@@_update_for_first_and_last_row:

```

We actualise the width of the “first column” because we will use this width after the construction of the array.

```

3280         \dim_gset:Nn \g_@@_width_first_col_dim
3281         { \dim_max:nn \g_@@_width_first_col_dim { \box_wd:N \l_@@_cell_box } }

```

The content of the cell is inserted in an overlapping position.

```

3282         \hbox_overlap_left:n
3283         {
3284             \dim_compare:nNnTF { \box_wd:N \l_@@_cell_box } > \c_zero_dim
3285             \@@_node_for_cell:
3286             { \box_use_drop:N \l_@@_cell_box }

```

```

3287         \skip_horizontal:N \l_@@_left_delim_dim
3288         \skip_horizontal:N \l_@@_left_margin_dim
3289         \skip_horizontal:N \l_@@_extra_left_margin_dim
3290     }
3291     \bool_gset_false:N \g_@@_empty_cell_bool
3292     \skip_horizontal:N -2\col@sep
3293 }
3294 }

```

Here is the preamble for the “last column” (if the user uses the key `last-col`).

```

3295 \tl_const:Nn \c_@@_preamble_last_col_tl
3296 {
3297     >
3298     {

```

At the beginning of the cell, we link `\CodeAfter` to a command which do begins with `\` (whereas the standard version of `\CodeAfter` begins does not).

```

3299         \cs_set_eq:NN \CodeAfter \@@_CodeAfter_i:

```

With the flag `\g_@@_last_col_found_bool`, we will know that the “last column” is really used.

```

3300         \bool_gset_true:N \g_@@_last_col_found_bool
3301         \int_gincr:N \c@jCol
3302         \int_gset_eq:NN \g_@@_col_total_int \c@jCol

```

The contents of the cell is constructed in the box `\l_tmpa_box` because we have to compute some dimensions of this box.

```

3303         \hbox_set:Nw \l_@@_cell_box
3304         \@@_math_toggle_token:
3305         \bool_if:NT \l_@@_small_bool \scriptstyle

```

We insert `\l_@@_code_for_last_col_tl...` but we don’t insert it in the potential “first row” and in the potential “last row”.

```

3306         \int_compare:nNnT \c@iRow > 0
3307         {
3308             \bool_lazy_or:nnT
3309             { \int_compare_p:nNn \l_@@_last_row_int < 0 }
3310             { \int_compare_p:nNn \c@iRow < \l_@@_last_row_int }
3311             {
3312                 \l_@@_code_for_last_col_tl
3313                 \xglobal \colorlet { nicematrix-last-col } { . }
3314             }
3315         }
3316     }
3317     1
3318     <
3319     {
3320         \@@_math_toggle_token:
3321         \hbox_set_end:
3322         \bool_if:NT \g_@@_rotate_bool \@@_rotate_cell_box:
3323         \@@_adjust_size_box:
3324         \@@_update_for_first_and_last_row:

```

We actualise the width of the “last column” because we will use this width after the construction of the array.

```

3325         \dim_gset:Nn \g_@@_width_last_col_dim
3326         { \dim_max:nn \g_@@_width_last_col_dim { \box_wd:N \l_@@_cell_box } }
3327         \skip_horizontal:N -2\col@sep

```

The content of the cell is inserted in an overlapping position.

```

3328         \hbox_overlap_right:n
3329         {
3330             \dim_compare:nNnT { \box_wd:N \l_@@_cell_box } > \c_zero_dim
3331             {
3332                 \skip_horizontal:N \l_@@_right_delim_dim
3333                 \skip_horizontal:N \l_@@_right_margin_dim
3334                 \skip_horizontal:N \l_@@_extra_right_margin_dim

```

```

3335         \@@_node_for_cell:
3336     }
3337 }
3338 \bool_gset_false:N \g_@@_empty_cell_bool
3339 }
3340 }

```

The environment `{NiceArray}` is constructed upon the environment `{NiceArrayWithDelims}` but, in fact, there is a flag `\g_@@_NiceArray_bool`. In `{NiceArrayWithDelims}`, some special code will be executed if this flag is raised.

```

3341 \NewDocumentEnvironment { NiceArray } { }
3342 {
3343     \bool_gset_true:N \g_@@_NiceArray_bool
3344     \str_if_empty:NT \g_@@_name_env_str
3345         { \str_gset:Nn \g_@@_name_env_str { NiceArray } }

```

We put `.` and `.` for the delimiters but, in fact, that doesn't matter because these arguments won't be used in `{NiceArrayWithDelims}` (because the flag `\g_@@_NiceArray_bool` is raised).

```

3346     \NiceArrayWithDelims . .
3347 }
3348 { \endNiceArrayWithDelims }

```

We create the variants of the environment `{NiceArrayWithDelims}`.

```

3349 \cs_new_protected:Npn \@@_def_env:nnn #1 #2 #3
3350 {
3351     \NewDocumentEnvironment { #1 NiceArray } { }
3352     {
3353         \bool_gset_false:N \g_@@_NiceArray_bool
3354         \str_if_empty:NT \g_@@_name_env_str
3355             { \str_gset:Nn \g_@@_name_env_str { #1 NiceArray } }
3356         \@@_test_if_math_mode:
3357         \NiceArrayWithDelims #2 #3
3358     }
3359     { \endNiceArrayWithDelims }
3360 }
3361 \@@_def_env:nnn p ( )
3362 \@@_def_env:nnn b [ ]
3363 \@@_def_env:nnn B \{ \}
3364 \@@_def_env:nnn v | |
3365 \@@_def_env:nnn V \| \|

```

The environment `{NiceMatrix}` and its variants

```

3366 \cs_new_protected:Npn \@@_begin_of_NiceMatrix:nn #1 #2
3367 {
3368     \bool_set_true:N \l_@@_Matrix_bool
3369     \use:c { #1 NiceArray }
3370     {
3371         *
3372         {
3373             \int_compare:nNnTF \l_@@_last_col_int < 0
3374                 \c@MaxMatrixCols
3375                 { \int_eval:n { \l_@@_last_col_int - 1 } }
3376         }
3377         { #2 }
3378     }
3379 }
3380 \cs_generate_variant:Nn \@@_begin_of_NiceMatrix:nn { n V }

```

```

3381 \clist_map_inline:nn { p , b , B , v , V }
3382 {
3383   \NewDocumentEnvironment { #1 NiceMatrix } { ! O { } }
3384   {
3385     \bool_gset_false:N \g_@@_NiceArray_bool
3386     \str_gset:Nn \g_@@_name_env_str { #1 NiceMatrix }
3387     \keys_set:nn { NiceMatrix / NiceMatrix } { ##1 }
3388     \@@_begin_of_NiceMatrix:nV { #1 } \l_@@_columns_type_tl
3389   }
3390   { \use:c { end #1 NiceArray } }
3391 }

```

We define also an environment {NiceMatrix}

```

3392 \NewDocumentEnvironment { NiceMatrix } { ! O { } }
3393 {
3394   \bool_gset_false:N \g_@@_NiceArray_bool
3395   \str_gset:Nn \g_@@_name_env_str { NiceMatrix }
3396   \keys_set:nn { NiceMatrix / NiceMatrix } { #1 }
3397   \@@_begin_of_NiceMatrix:nV { } \l_@@_columns_type_tl
3398 }
3399 { \endNiceArray }

```

The following command will be linked to \NotEmpty in the environments of nicematrix.

```

3400 \cs_new_protected:Npn \@@_NotEmpty:
3401 { \bool_gset_true:N \g_@@_not_empty_cell_bool }

```

{NiceTabular}, {NiceTabularX} and {NiceTabular*}

```

3402 \NewDocumentEnvironment { NiceTabular } { O { } m ! O { } }
3403 {

```

If the dimension \l_@@_width_dim is equal to 0 pt, that means that it has not be set by a previous use of \NiceMatrixOptions.

```

3404   \dim_compare:nNnT \l_@@_width_dim = \c_zero_dim
3405     { \dim_set_eq:NN \l_@@_width_dim \linewidth }
3406   \str_gset:Nn \g_@@_name_env_str { NiceTabular }
3407   \keys_set:nn { NiceMatrix / NiceTabular } { #1 , #3 }
3408   \tl_if_empty:NF \l_@@_short_caption_tl
3409   {
3410     \tl_if_empty:NT \l_@@_caption_tl
3411     {
3412       \@@_error_or_warning:n { short-caption~without~caption }
3413       \tl_set_eq:NN \l_@@_caption_tl \l_@@_short_caption_tl
3414     }
3415   }
3416   \tl_if_empty:NF \l_@@_label_tl
3417   {
3418     \tl_if_empty:NT \l_@@_caption_tl
3419     { \@@_error_or_warning:n { label~without~caption } }
3420   }
3421   \NewDocumentEnvironment { TabularNote } { b }
3422   {
3423     \bool_if:NTF \l_@@_in_code_after_bool
3424     { \@@_error_or_warning:n { TabularNote~in~CodeAfter } }
3425     {
3426       \tl_if_empty:NF \g_@@_tabularnote_tl
3427       { \tl_gput_right:Nn \g_@@_tabularnote_tl { \par } }
3428       \tl_gput_right:Nn \g_@@_tabularnote_tl { ##1 }
3429     }
3430   }
3431   { }
3432   \bool_set_true:N \l_@@_NiceTabular_bool
3433   \NiceArray { #2 }

```

```

3434 }
3435 { \endNiceArray }

3436 \cs_set_protected:Npn \@@_newcolumnntype #1
3437 {
3438   \cs_if_free:cT { NC @ find @ #1 }
3439   { \NC@list \expandafter { \the \NC@list \NC@do #1 } }
3440   \cs_set:cpn {NC @ find @ #1 } ##1 #1 { \NC@ { ##1 } }
3441   \peek_meaning:NTF [
3442     { \newcol@ #1 }
3443     { \newcol@ #1 [ 0 ] }
3444   }

3445 \NewDocumentEnvironment { NiceTabularX } { m O { } m ! O { } }
3446 {

```

The following code prevents the expansion of the ‘X’ columns with the definition of that columns in `tabularx` (this would result in an error in `{NiceTabularX}`).

```

3447   \bool_if:NT \c_@@_tabularx_loaded_bool { \newcolumnntype { X } { \@@_X } }
3448   \str_gset:Nn \g_@@_name_env_str { NiceTabularX }
3449   \dim_zero_new:N \l_@@_width_dim
3450   \dim_set:Nn \l_@@_width_dim { #1 }
3451   \keys_set:nn { NiceMatrix / NiceTabular } { #2 , #4 }
3452   \bool_set_true:N \l_@@_NiceTabular_bool
3453   \NiceArray { #3 }
3454 }
3455 { \endNiceArray }

3456 \NewDocumentEnvironment { NiceTabular* } { m O { } m ! O { } }
3457 {
3458   \str_gset:Nn \g_@@_name_env_str { NiceTabular* }
3459   \dim_set:Nn \l_@@_tabular_width_dim { #1 }
3460   \keys_set:nn { NiceMatrix / NiceTabular } { #2 , #4 }
3461   \bool_set_true:N \l_@@_NiceTabular_bool
3462   \NiceArray { #3 }
3463 }
3464 { \endNiceArray }

```

After the construction of the array

```

3465 \cs_new_protected:Npn \@@_after_array:
3466 {
3467   \group_begin:

```

When the option `last-col` is used in the environments with explicit preambles (like `{NiceArray}`, `{pNiceArray}`, etc.) a special type of column is used at the end of the preamble in order to compose the cells in an overlapping position (with `\hbox_overlap_right:n`) but (if `last-col` has been used), we don’t have the number of that last column. However, we have to know that number for the color of the potential `\Vdots` drawn in that last column. That’s why we fix the correct value of `\l_@@_last_col_int` in that case.

```

3468   \bool_if:NT \g_@@_last_col_found_bool
3469   { \int_set_eq:NN \l_@@_last_col_int \g_@@_col_total_int }

```

If we are in an environment without preamble (like `{NiceMatrix}` or `{pNiceMatrix}`) and if the option `last-col` has been used without value we also fix the real value of `\l_@@_last_col_int`.

```

3470   \bool_if:NT \l_@@_last_col_without_value_bool
3471   { \int_set_eq:NN \l_@@_last_col_int \g_@@_col_total_int }

```

It’s also time to give to `\l_@@_last_row_int` its real value.

```

3472   \bool_if:NT \l_@@_last_row_without_value_bool
3473   { \int_set_eq:NN \l_@@_last_row_int \g_@@_row_total_int }

3474   \tl_gput_right:Nx \g_@@_aux_tl

```

```

3475 {
3476   \seq_gset_from_clist:Nn \exp_not:N \g_@@_size_seq
3477   {
3478     \int_use:N \l_@@_first_row_int ,
3479     \int_use:N \c@iRow ,
3480     \int_use:N \g_@@_row_total_int ,
3481     \int_use:N \l_@@_first_col_int ,
3482     \int_use:N \c@jCol ,
3483     \int_use:N \g_@@_col_total_int
3484   }
3485 }

```

We write also the potential content of `\g_@@_pos_of_blocks_seq`. It will be used to recreate the blocks with a name in the `\CodeBefore` and also if the command `\rowcolors` is used with the key `respect-blocks`).

```

3486 \seq_if_empty:NF \g_@@_pos_of_blocks_seq
3487 {
3488   \tl_gput_right:Nx \g_@@_aux_tl
3489   {
3490     \seq_gset_from_clist:Nn \exp_not:N \g_@@_pos_of_blocks_seq
3491     { \seq_use:Nnnn \g_@@_pos_of_blocks_seq , , , }
3492   }
3493 }
3494 \seq_if_empty:NF \g_@@_multicolumn_cells_seq
3495 {
3496   \tl_gput_right:Nx \g_@@_aux_tl
3497   {
3498     \seq_gset_from_clist:Nn \exp_not:N \g_@@_multicolumn_cells_seq
3499     { \seq_use:Nnnn \g_@@_multicolumn_cells_seq , , , }
3500     \seq_gset_from_clist:Nn \exp_not:N \g_@@_multicolumn_sizes_seq
3501     { \seq_use:Nnnn \g_@@_multicolumn_sizes_seq , , , }
3502   }
3503 }

```

Now, you create the diagonal nodes by using the `row` nodes and the `col` nodes.

```

3504 \@@_create_diag_nodes:

```

We create the aliases using `last` for the nodes of the cells in the last row and the last column.

```

3505 \pgfpicture
3506 \int_step_inline:nn \c@iRow
3507 {
3508   \pgfnodealias
3509   { \@@_env: - ##1 - last }
3510   { \@@_env: - ##1 - \int_use:N \c@jCol }
3511 }
3512 \int_step_inline:nn \c@jCol
3513 {
3514   \pgfnodealias
3515   { \@@_env: - last - ##1 }
3516   { \@@_env: - \int_use:N \c@iRow - ##1 }
3517 }
3518 \str_if_empty:NF \l_@@_name_str
3519 {
3520   \int_step_inline:nn \c@iRow
3521   {
3522     \pgfnodealias
3523     { \l_@@_name_str - ##1 - last }
3524     { \@@_env: - ##1 - \int_use:N \c@jCol }
3525   }
3526   \int_step_inline:nn \c@jCol
3527   {
3528     \pgfnodealias
3529     { \l_@@_name_str - last - ##1 }
3530     { \@@_env: - \int_use:N \c@iRow - ##1 }

```



```

3531     }
3532   }
3533   \endpgfpicture

```

By default, the diagonal lines will be parallelized⁷⁴. There are two types of diagonals lines: the `\Ddots` diagonals and the `\Iddots` diagonals. We have to count both types in order to know whether a diagonal is the first of its type in the current `{NiceArray}` environment.

```

3534   \bool_if:NT \l_@@_parallelize_diags_bool
3535   {
3536     \int_gzero_new:N \g_@@_ddots_int
3537     \int_gzero_new:N \g_@@_iddots_int

```

The dimensions `\g_@@_delta_x_one_dim` and `\g_@@_delta_y_one_dim` will contain the Δ_x and Δ_y of the first `\Ddots` diagonal. We have to store these values in order to draw the others `\Ddots` diagonals parallel to the first one. Similarly `\g_@@_delta_x_two_dim` and `\g_@@_delta_y_two_dim` are the Δ_x and Δ_y of the first `\Iddots` diagonal.

```

3538     \dim_gzero_new:N \g_@@_delta_x_one_dim
3539     \dim_gzero_new:N \g_@@_delta_y_one_dim
3540     \dim_gzero_new:N \g_@@_delta_x_two_dim
3541     \dim_gzero_new:N \g_@@_delta_y_two_dim
3542   }
3543   \int_zero_new:N \l_@@_initial_i_int
3544   \int_zero_new:N \l_@@_initial_j_int
3545   \int_zero_new:N \l_@@_final_i_int
3546   \int_zero_new:N \l_@@_final_j_int
3547   \bool_set_false:N \l_@@_initial_open_bool
3548   \bool_set_false:N \l_@@_final_open_bool

```

If the option `small` is used, the values `\l_@@_xdots_radius_dim` and `\l_@@_xdots_inter_dim` (used to draw the dotted lines created by `\hdottedline` and `\vdottedline` and also for all the other dotted lines when `line-style` is equal to `standard`, which is the initial value) are changed.

```

3549   \bool_if:NT \l_@@_small_bool
3550   {
3551     \dim_set:Nn \l_@@_xdots_radius_dim { 0.7 \l_@@_xdots_radius_dim }
3552     \dim_set:Nn \l_@@_xdots_inter_dim { 0.55 \l_@@_xdots_inter_dim }

```

The dimensions `\l_@@_xdots_shorten_start_dim` and `\l_@@_xdots_shorten_end_dim` correspond to the options `xdots/shorten-start` and `xdots/shorten-end` available to the user.

```

3553     \dim_set:Nn \l_@@_xdots_shorten_start_dim
3554     { 0.6 \l_@@_xdots_shorten_start_dim }
3555     \dim_set:Nn \l_@@_xdots_shorten_end_dim
3556     { 0.6 \l_@@_xdots_shorten_end_dim }
3557   }

```

Now, we actually draw the dotted lines (specified by `\Cdots`, `\Vdots`, etc.).

```

3558   \@@_draw_dotted_lines:

```

The following computes the “corners” (made up of empty cells) but if there is no corner to compute, it won’t do anything. The corners are computed in `\l_@@_corners_cells_seq` which will contain all the cells which are empty (and not in a block) considered in the corners of the array.

```

3559   \@@_compute_corners:

```

The sequence `\g_@@_pos_of_blocks_seq` must be “adjusted” (for the case where the user have written something like `\Block{1-*}`).

```

3560   \@@_adjust_pos_of_blocks_seq:
3561   \tl_if_empty:NF \l_@@_hlines_clist \@@_draw_hlines:
3562   \tl_if_empty:NF \l_@@_vlines_clist \@@_draw_vlines:

```

Now, the pre-code-after and then, the `\CodeAfter`.

```

3563   \bool_if:NT \c_@@_tikz_loaded_bool

```

⁷⁴It’s possible to use the option `parallelize-diags` to disable this parallelization.

```

3564 {
3565   \tikzset
3566   {
3567     every~picture / .style =
3568     {
3569       overlay ,
3570       remember~picture ,
3571       name~prefix = \@@_env: -
3572     }
3573   }
3574 }
3575 \cs_set_eq:NN \ialign \@@_old_ialign:
3576 \cs_set_eq:NN \SubMatrix \@@_SubMatrix
3577 \cs_set_eq:NN \UnderBrace \@@_UnderBrace
3578 \cs_set_eq:NN \OverBrace \@@_OverBrace
3579 \cs_set_eq:NN \ShowCellNames \@@_ShowCellNames
3580 \cs_set_eq:NN \line \@@_line
3581 \g_@@_pre_code_after_tl
3582 \tl_gclear:N \g_@@_pre_code_after_tl

```

When `light-syntax` is used, we insert systematically a `\CodeAfter` in the flow. Thus, it's possible to have two instructions `\CodeAfter` and the second may be in `\g_nicematrix_code_after_tl`. That's why we set `\Code-after` to be *no-op* now.

```

3583 \cs_set_eq:NN \CodeAfter \prg_do_nothing:

```

We clear the list of the names of the potential `\SubMatrix` that will appear in the `\CodeAfter` (unfortunately, that list has to be global).

```

3584 \seq_gclear:N \g_@@_submatrix_names_seq

```

The following code is a security for the case the user has used `babel` with the option `spanish`: in that case, the characters `>` and `<` are activated and Tikz is not able to solve the problem (even with the Tikz library `babel`).

```

3585 \int_compare:nNnT { \char_value_catcode:n { 60 } } = { 13 }
3586 { \@@_rescan_for_spanish:N \g_nicematrix_code_after_tl }

```

And here's the `\CodeAfter`. Since the `\CodeAfter` may begin with an “argument” between square brackets of the options, we extract and treat that potential “argument” with the command `\@@_CodeAfter_keys:`.

```

3587 \bool_set_true:N \l_@@_in_code_after_bool
3588 \exp_last_unbraced:N \@@_CodeAfter_keys: \g_nicematrix_code_after_tl
3589 \scan_stop:
3590 \tl_gclear:N \g_nicematrix_code_after_tl
3591 \group_end:

```

`\g_@@_pre_code_before_tl` is for instructions in the cells of the array such as `\rowcolor` and `\cellcolor` (when the key `colortbl-like` is in force). These instructions will be written on the aux file to be added to the `code-before` in the next run.

```

3592 \tl_if_empty:NF \g_@@_pre_code_before_tl
3593 {
3594   \tl_gput_right:Nx \g_@@_aux_tl
3595   {
3596     \tl_gset:Nn \exp_not:N \g_@@_pre_code_before_tl
3597     { \exp_not:V \g_@@_pre_code_before_tl }
3598   }
3599   \tl_gclear:N \g_@@_pre_code_before_tl
3600 }
3601 \tl_if_empty:NF \g_nicematrix_code_before_tl
3602 {
3603   \tl_gput_right:Nx \g_@@_aux_tl
3604   {
3605     \tl_gset:Nn \exp_not:N \g_@@_code_before_tl
3606     { \exp_not:V \g_nicematrix_code_before_tl }
3607   }
3608   \tl_gclear:N \g_nicematrix_code_before_tl

```

```

3609     }

3610     \str_gclear:N \g_@@_name_env_str
3611     \@@_restore_iRow_jCol:

```

The command `\CT@arc@` contains the instruction of color for the rules of the array⁷⁵. This command is used by `\CT@arc@` but we use it also for compatibility with `colortbl`. But we want also to be able to use color for the rules of the array when `colortbl` is *not* loaded. That’s why we do the following instruction which is in the patch of the end of arrays done by `colortbl`.

```

3612     \cs_gset_eq:NN \CT@arc@ \@@_old_CT@arc@
3613 }

```

The following command will extract the potential options (between square brackets) at the beginning of the `\CodeAfter` (that is to say, when `\CodeAfter` is used, the options of that “command” `\CodeAfter`). Idem for the `\CodeBefore`.

```

3614 \NewDocumentCommand \@@_CodeAfter_keys: { 0 { } }
3615 { \keys_set:nn { NiceMatrix / CodeAfter } { #1 } }

```

We remind that the first mandatory argument of the command `\Block` is the size of the block with the special format $i-j$. However, the user is allowed to omit i or j (or both). This will be interpreted as: the last row (resp. column) of the block will be the last row (resp. column) of the block (without the potential exterior row—resp. column—of the array). By convention, this is stored in `\g_@@_pos_of_blocks_seq` (and `\g_@@_blocks_seq`) as a number of rows (resp. columns) for the block equal to 100. It’s possible, after the construction of the array, to replace these values by the correct ones (since we know the number of rows and columns of the array).

```

3616 \cs_new_protected:Npn \@@_adjust_pos_of_blocks_seq:
3617 {
3618     \seq_gset_map_x:NNn \g_@@_pos_of_blocks_seq \g_@@_pos_of_blocks_seq
3619     { \@@_adjust_pos_of_blocks_seq_i:nnnnn #1 }
3620 }

```

The following command must *not* be protected.

```

3621 \cs_new:Npn \@@_adjust_pos_of_blocks_seq_i:nnnnn #1 #2 #3 #4 #5
3622 {
3623     { #1 }
3624     { #2 }
3625     {
3626         \int_compare:nNnTF { #3 } > { 99 }
3627         { \int_use:N \c@iRow }
3628         { #3 }
3629     }
3630     {
3631         \int_compare:nNnTF { #4 } > { 99 }
3632         { \int_use:N \c@jCol }
3633         { #4 }
3634     }
3635     { #5 }
3636 }

```

We recall that, when externalization is used, `\tikzpicture` and `\endtikzpicture` (or `\pgfpicture` and `\endpgfpicture`) must be directly “visible”. That’s why we have to define the adequate version of `\@@_draw_dotted_lines`: whether Tikz is loaded or not (in that case, only PGF is loaded).

```

3637 \hook_gput_code:nnn { begindocument } { . }
3638 {
3639     \cs_new_protected:Npx \@@_draw_dotted_lines:
3640     {
3641         \c_@@_pgfortikzpicture_tl
3642         \@@_draw_dotted_lines_i:
3643         \c_@@_endpgfortikzpicture_tl

```

⁷⁵e.g. `\color[rgb]{0.5,0.5,0}`

```

3644 }
3645 }

```

The following command *must* be protected because it will appear in the construction of the command `\@@_draw_dotted_lines:`.

```

3646 \cs_new_protected:Npn \@@_draw_dotted_lines_i:
3647 {
3648   \pgfrememberpicturepositiononpagetrue
3649   \pgf@relevantforpicturesizefalse
3650   \g_@@_HVdotsfor_lines_tl
3651   \g_@@_Vdots_lines_tl
3652   \g_@@_Ddots_lines_tl
3653   \g_@@_Iddots_lines_tl
3654   \g_@@_Cdots_lines_tl
3655   \g_@@_Ldots_lines_tl
3656 }

3657 \cs_new_protected:Npn \@@_restore_iRow_jCol:
3658 {
3659   \cs_if_exist:NT \theiRow { \int_gset_eq:NN \c@iRow \l_@@_old_iRow_int }
3660   \cs_if_exist:NT \thejCol { \int_gset_eq:NN \c@jCol \l_@@_old_jCol_int }
3661 }

```

We define a new PGF shape for the diag nodes because we want to provide a anchor called `.5` for those nodes.

```

3662 \pgfdeclareshape { @@_diag_node }
3663 {
3664   \savedanchor { \five }
3665   {
3666     \dim_gset_eq:NN \pgf@x \l_tmpa_dim
3667     \dim_gset_eq:NN \pgf@y \l_tmpb_dim
3668   }
3669   \anchor { 5 } { \five }
3670   \anchor { center } { \pgfpointorigin }
3671 }

```

The following command creates the diagonal nodes (in fact, if the matrix is not a square matrix, not all the nodes are on the diagonal).

```

3672 \cs_new_protected:Npn \@@_create_diag_nodes:
3673 {
3674   \pgfpicture
3675   \pgfrememberpicturepositiononpagetrue
3676   \int_step_inline:nn { \int_max:nn \c@iRow \c@jCol }
3677   {
3678     \@@_qpoint:n { col - \int_min:nn { ##1 } { \c@jCol + 1 } }
3679     \dim_set_eq:NN \l_tmpa_dim \pgf@x
3680     \@@_qpoint:n { row - \int_min:nn { ##1 } { \c@iRow + 1 } }
3681     \dim_set_eq:NN \l_tmpb_dim \pgf@y
3682     \@@_qpoint:n { col - \int_min:nn { ##1 + 1 } { \c@jCol + 1 } }
3683     \dim_set_eq:NN \l_@@_tmpc_dim \pgf@x
3684     \@@_qpoint:n { row - \int_min:nn { ##1 + 1 } { \c@iRow + 1 } }
3685     \dim_set_eq:NN \l_@@_tmpd_dim \pgf@y
3686     \pgftransformshift { \pgfpoint \l_tmpa_dim \l_tmpb_dim }

```

Now, `\l_tmpa_dim` and `\l_tmpb_dim` become the width and the height of the node (of shape `@_diag_node`) that we will construct.

```

3687     \dim_set:Nn \l_tmpa_dim { ( \l_@@_tmpc_dim - \l_tmpa_dim ) / 2 }
3688     \dim_set:Nn \l_tmpb_dim { ( \l_@@_tmpd_dim - \l_tmpb_dim ) / 2 }
3689     \pgfnode { @@_diag_node } { center } { } { \@@_env: - ##1 } { }
3690     \str_if_empty:NF \l_@@_name_str
3691     { \pgfnodealias { \l_@@_name_str - ##1 } { \@@_env: - ##1 } }
3692   }

```

```

3693 \int_set:Nn \l_tmpa_int { \int_max:nn \c@iRow \c@jCol + 1 }
3694 @@_qpoint:n { row - \int_min:nn { \l_tmpa_int } { \c@iRow + 1 } }
3695 \dim_set_eq:NN \l_tmpa_dim \pgf@y
3696 @@_qpoint:n { col - \int_min:nn { \l_tmpa_int } { \c@jCol + 1 } }
3697 \pgfcoordinate
3698 { @@_env: - \int_use:N \l_tmpa_int } { \pgfpoint \pgf@x \l_tmpa_dim }
3699 \pgfnodealias
3700 { @@_env: - last }
3701 { @@_env: - \int_eval:n { \int_max:nn \c@iRow \c@jCol + 1 } }
3702 \str_if_empty:NF \l_@@_name_str
3703 {
3704   \pgfnodealias
3705   { \l_@@_name_str - \int_use:N \l_tmpa_int }
3706   { @@_env: - \int_use:N \l_tmpa_int }
3707   \pgfnodealias
3708   { \l_@@_name_str - last }
3709   { @@_env: - last }
3710 }
3711 \endpgfpicture
3712 }

```

A dotted line will be said *open* in one of its extremities when it stops on the edge of the matrix and *closed* otherwise. In the following matrix, the dotted line is closed on its left extremity and open on its right.

$$\begin{pmatrix} a+b+c & a+b & a \\ a & \dots\dots\dots & \\ a & a+b & a+b+c \end{pmatrix}$$

- the first argument is the row of the cell where the command was issued;
- the second argument is the column of the cell where the command was issued;
- the third argument is the x -value of the orientation vector of the line;
- the fourth argument is the y -value of the orientation vector of the line.

- `\l_@@_initial_i_int` and `\l_@@_initial_j_int` which are the coordinates of one extremity of the line;
- `\l_@@_final_i_int` and `\l_@@_final_j_int` which are the coordinates of the other extremity of the line;
- `\l_@@_initial_open_bool` and `\l_@@_final_open_bool` to indicate whether the extremities are open or not.

```
3715 \cs_set:cpn { @@ _ dotted _ #1 - #2 } { }
```

```

3716 \int_set:Nn \l_@@_initial_i_int { #1 }
3717 \int_set:Nn \l_@@_initial_j_int { #2 }
3718 \int_set:Nn \l_@@_final_i_int { #1 }
3719 \int_set:Nn \l_@@_final_j_int { #2 }

```

We will do two loops: one when determinating the initial cell and the other when determinating the final cell. The boolean `\l_@@_stop_loop_bool` will be used to control these loops. In the first loop, we search the “final” extremity of the line.

```

3720   \bool_set_false:N \l_@@_stop_loop_bool
3721   \bool_do_until:Nn \l_@@_stop_loop_bool
3722   {
3723     \int_add:Nn \l_@@_final_i_int { #3 }
3724     \int_add:Nn \l_@@_final_j_int { #4 }

```

We test if we are still in the matrix.

```

3725   \bool_set_false:N \l_@@_final_open_bool
3726   \int_compare:nNnTF \l_@@_final_i_int > \l_@@_row_max_int
3727   {
3728     \int_compare:nNnTF { #3 } = 1
3729     { \bool_set_true:N \l_@@_final_open_bool }
3730     {
3731       \int_compare:nNnT \l_@@_final_j_int > \l_@@_col_max_int
3732       { \bool_set_true:N \l_@@_final_open_bool }
3733     }
3734   }
3735   {
3736     \int_compare:nNnTF \l_@@_final_j_int < \l_@@_col_min_int
3737     {
3738       \int_compare:nNnT { #4 } = { -1 }
3739       { \bool_set_true:N \l_@@_final_open_bool }
3740     }
3741     {
3742       \int_compare:nNnT \l_@@_final_j_int > \l_@@_col_max_int
3743       {
3744         \int_compare:nNnT { #4 } = 1
3745         { \bool_set_true:N \l_@@_final_open_bool }
3746       }
3747     }
3748   }
3749   \bool_if:NTF \l_@@_final_open_bool

```

If we are outside the matrix, we have found the extremity of the dotted line and it’s an *open* extremity.

```

3750   {

```

We do a step backwards.

```

3751     \int_sub:Nn \l_@@_final_i_int { #3 }
3752     \int_sub:Nn \l_@@_final_j_int { #4 }
3753     \bool_set_true:N \l_@@_stop_loop_bool
3754   }

```

If we are in the matrix, we test whether the cell is empty. If it’s not the case, we stop the loop because we have found the correct values for `\l_@@_final_i_int` and `\l_@@_final_j_int`.

```

3755   {
3756     \cs_if_exist:cTF
3757     {
3758       @@ _ dotted _
3759       \int_use:N \l_@@_final_i_int -
3760       \int_use:N \l_@@_final_j_int
3761     }
3762     {
3763       \int_sub:Nn \l_@@_final_i_int { #3 }
3764       \int_sub:Nn \l_@@_final_j_int { #4 }
3765       \bool_set_true:N \l_@@_final_open_bool
3766       \bool_set_true:N \l_@@_stop_loop_bool
3767     }
3768     {
3769       \cs_if_exist:cTF
3770       {
3771         pgf @ sh @ ns @ \@@_env:
3772         - \int_use:N \l_@@_final_i_int

```

```

3773         - \int_use:N \l_@@_final_j_int
3774     }
3775     { \bool_set_true:N \l_@@_stop_loop_bool }

```

If the case is empty, we declare that the cell as non-empty. Indeed, we will draw a dotted line and the cell will be on that dotted line. All the cells of a dotted line have to be marked as “dotted” because we don’t want intersections between dotted lines. We recall that the research of the extremities of the lines are all done in the same TeX group (the group of the environment), even though, when the extremities are found, each line is drawn in a TeX group that we will open for the options of the line.

```

3776     {
3777         \cs_set:cpn
3778         {
3779             @@ _ dotted _
3780             \int_use:N \l_@@_final_i_int -
3781             \int_use:N \l_@@_final_j_int
3782         }
3783         { }
3784     }
3785 }
3786 }
3787 }

```

For `\l_@@_initial_i_int` and `\l_@@_initial_j_int` the programming is similar to the previous one.

```

3788 \bool_set_false:N \l_@@_stop_loop_bool
3789 \bool_do_until:Nn \l_@@_stop_loop_bool
3790 {
3791     \int_sub:Nn \l_@@_initial_i_int { #3 }
3792     \int_sub:Nn \l_@@_initial_j_int { #4 }
3793     \bool_set_false:N \l_@@_initial_open_bool
3794     \int_compare:nNnTF \l_@@_initial_i_int < \l_@@_row_min_int
3795     {
3796         \int_compare:nNnTF { #3 } = 1
3797         { \bool_set_true:N \l_@@_initial_open_bool }
3798         {
3799             \int_compare:nNnT \l_@@_initial_j_int = { \l_@@_col_min_int -1 }
3800             { \bool_set_true:N \l_@@_initial_open_bool }
3801         }
3802     }
3803     {
3804         \int_compare:nNnTF \l_@@_initial_j_int < \l_@@_col_min_int
3805         {
3806             \int_compare:nNnT { #4 } = 1
3807             { \bool_set_true:N \l_@@_initial_open_bool }
3808         }
3809         {
3810             \int_compare:nNnT \l_@@_initial_j_int > \l_@@_col_max_int
3811             {
3812                 \int_compare:nNnT { #4 } = { -1 }
3813                 { \bool_set_true:N \l_@@_initial_open_bool }
3814             }
3815         }
3816     }
3817     \bool_if:NnTF \l_@@_initial_open_bool
3818     {
3819         \int_add:Nn \l_@@_initial_i_int { #3 }
3820         \int_add:Nn \l_@@_initial_j_int { #4 }
3821         \bool_set_true:N \l_@@_stop_loop_bool
3822     }
3823     {
3824         \cs_if_exist:cTF
3825         {

```

```

3826         @@ _ dotted _
3827         \int_use:N \l_@@_initial_i_int -
3828         \int_use:N \l_@@_initial_j_int
3829     }
3830     {
3831         \int_add:Nn \l_@@_initial_i_int { #3 }
3832         \int_add:Nn \l_@@_initial_j_int { #4 }
3833         \bool_set_true:N \l_@@_initial_open_bool
3834         \bool_set_true:N \l_@@_stop_loop_bool
3835     }
3836     {
3837         \cs_if_exist:cTF
3838         {
3839             pgf @ sh @ ns @ \@@_env:
3840             - \int_use:N \l_@@_initial_i_int
3841             - \int_use:N \l_@@_initial_j_int
3842         }
3843         { \bool_set_true:N \l_@@_stop_loop_bool }
3844         {
3845             \cs_set:cpn
3846             {
3847                 @@ _ dotted _
3848                 \int_use:N \l_@@_initial_i_int -
3849                 \int_use:N \l_@@_initial_j_int
3850             }
3851             { }
3852         }
3853     }
3854 }
3855 }

```

We remind the rectangle described by all the dotted lines in order to respect the corresponding virtual “block” when drawing the horizontal and vertical rules.

```

3856     \seq_gput_right:Nx \g_@@_pos_of_xdots_seq
3857     {
3858         { \int_use:N \l_@@_initial_i_int }

```

Be careful: with `\Iddots`, `\l_@@_final_j_int` is inferior to `\l_@@_initial_j_int`. That’s why we use `\int_min:nn` and `\int_max:nn`.

```

3859         { \int_min:nn \l_@@_initial_j_int \l_@@_final_j_int }
3860         { \int_use:N \l_@@_final_i_int }
3861         { \int_max:nn \l_@@_initial_j_int \l_@@_final_j_int }
3862         { } % for the name of the block
3863     }
3864 }

```

The following command (*when it will be written*) will set the four counters `\l_@@_row_min_int`, `\l_@@_row_max_int`, `\l_@@_col_min_int` and `\l_@@_col_max_int` to the intersections of the submatrices which contains the cell of row #1 and column #2. As of now, it’s only the whole array (excepted exterior rows and columns).

```

3865 \cs_new_protected:Npn \@@_adjust_to_submatrix:nn #1 #2
3866 {
3867     \int_set:Nn \l_@@_row_min_int 1
3868     \int_set:Nn \l_@@_col_min_int 1
3869     \int_set_eq:NN \l_@@_row_max_int \c@iRow
3870     \int_set_eq:NN \l_@@_col_max_int \c@jCol

```

We do a loop over all the submatrices specified in the code-before. We have stored the position of all those submatrices in `\g_@@_submatrix_seq`.

```

3871     \seq_map_inline:Nn \g_@@_submatrix_seq
3872     { \@@_adjust_to_submatrix:nnnnn { #1 } { #2 } ##1 }
3873 }

```


#1 and #2 are the numbers of row and columns of the cell where the command of dotted line (ex.: \Vdots) has been issued. #3, #4, #5 and #6 are the specification (in i and j) of the submatrix we are analyzing.

```

3874 \cs_set_protected:Npn \@@_adjust_to_submatrix:nnnnnn #1 #2 #3 #4 #5 #6
3875 {
3876   \bool_if:nT
3877   {
3878     \int_compare_p:n { #3 <= #1 }
3879     && \int_compare_p:n { #1 <= #5 }
3880     && \int_compare_p:n { #4 <= #2 }
3881     && \int_compare_p:n { #2 <= #6 }
3882   }
3883   {
3884     \int_set:Nn \l_@@_row_min_int { \int_max:nn \l_@@_row_min_int { #3 } }
3885     \int_set:Nn \l_@@_col_min_int { \int_max:nn \l_@@_col_min_int { #4 } }
3886     \int_set:Nn \l_@@_row_max_int { \int_min:nn \l_@@_row_max_int { #5 } }
3887     \int_set:Nn \l_@@_col_max_int { \int_min:nn \l_@@_col_max_int { #6 } }
3888   }
3889 }

3890 \cs_new_protected:Npn \@@_set_initial_coords:
3891 {
3892   \dim_set_eq:NN \l_@@_x_initial_dim \pgf@x
3893   \dim_set_eq:NN \l_@@_y_initial_dim \pgf@y
3894 }
3895 \cs_new_protected:Npn \@@_set_final_coords:
3896 {
3897   \dim_set_eq:NN \l_@@_x_final_dim \pgf@x
3898   \dim_set_eq:NN \l_@@_y_final_dim \pgf@y
3899 }
3900 \cs_new_protected:Npn \@@_set_initial_coords_from_anchor:n #1
3901 {
3902   \pgfpointanchor
3903   {
3904     \@@_env:
3905     - \int_use:N \l_@@_initial_i_int
3906     - \int_use:N \l_@@_initial_j_int
3907   }
3908   { #1 }
3909   \@@_set_initial_coords:
3910 }
3911 \cs_new_protected:Npn \@@_set_final_coords_from_anchor:n #1
3912 {
3913   \pgfpointanchor
3914   {
3915     \@@_env:
3916     - \int_use:N \l_@@_final_i_int
3917     - \int_use:N \l_@@_final_j_int
3918   }
3919   { #1 }
3920   \@@_set_final_coords:
3921 }

3922 \cs_new_protected:Npn \@@_open_x_initial_dim:
3923 {
3924   \dim_set_eq:NN \l_@@_x_initial_dim \c_max_dim
3925   \int_step_inline:nnn \l_@@_first_row_int \g_@@_row_total_int
3926   {
3927     \cs_if_exist:cT
3928     { pgf @ sh @ ns @ \@@_env: - ##1 - \int_use:N \l_@@_initial_j_int }
3929     {
3930       \pgfpointanchor
3931       { \@@_env: - ##1 - \int_use:N \l_@@_initial_j_int }
3932       { west }

```

```

3933         \dim_set:Nn \l_@@_x_initial_dim
3934         { \dim_min:nn \l_@@_x_initial_dim \pgf@x }
3935     }
3936 }

```

If, in fact, all the cells of the columns are empty (no PGF/Tikz nodes in those cells).

```

3937 \dim_compare:nNnT \l_@@_x_initial_dim = \c_max_dim
3938 {
3939     \@@_qpoint:n { col - \int_use:N \l_@@_initial_j_int }
3940     \dim_set_eq:NN \l_@@_x_initial_dim \pgf@x
3941     \dim_add:Nn \l_@@_x_initial_dim \col@sep
3942 }
3943 }
3944 \cs_new_protected:Npn \@@_open_x_final_dim:
3945 {
3946     \dim_set:Nn \l_@@_x_final_dim { - \c_max_dim }
3947     \int_step_inline:nnn \l_@@_first_row_int \g_@@_row_total_int
3948     {
3949         \cs_if_exist:cT
3950         { \pgf @ sh @ ns @ \@@_env: - ##1 - \int_use:N \l_@@_final_j_int }
3951         {
3952             \pgfpointanchor
3953             { \@@_env: - ##1 - \int_use:N \l_@@_final_j_int }
3954             { east }
3955             \dim_set:Nn \l_@@_x_final_dim
3956             { \dim_max:nn \l_@@_x_final_dim \pgf@x }
3957         }
3958     }

```

If, in fact, all the cells of the columns are empty (no PGF/Tikz nodes in those cells).

```

3959 \dim_compare:nNnT \l_@@_x_final_dim = { - \c_max_dim }
3960 {
3961     \@@_qpoint:n { col - \int_eval:n { \l_@@_final_j_int + 1 } }
3962     \dim_set_eq:NN \l_@@_x_final_dim \pgf@x
3963     \dim_sub:Nn \l_@@_x_final_dim \col@sep
3964 }
3965 }

```

The first and the second arguments are the coordinates of the cell where the command has been issued. The third argument is the list of the options.

```

3966 \cs_new_protected:Npn \@@_draw_Ldots:nnn #1 #2 #3
3967 {
3968     \@@_adjust_to_submatrix:nn { #1 } { #2 }
3969     \cs_if_free:cT { @@ _ dotted _ #1 - #2 }
3970     {
3971         \@@_find_extremities_of_line:nnnn { #1 } { #2 } 0 1

```

The previous command may have changed the current environment by marking some cells as “dotted”, but, fortunately, it is outside the group for the options of the line.

```

3972 \group_begin:
3973     \int_compare:nNnTF { #1 } = 0
3974     { \color { nicematrix-first-row } }
3975     {

```

We remind that, when there is a “last row” `\l_@@_last_row_int` will always be (after the construction of the array) the number of that “last row” even if the option `last-row` has been used without value.

```

3976         \int_compare:nNnT { #1 } = \l_@@_last_row_int
3977         { \color { nicematrix-last-row } }
3978     }
3979     \keys_set:nn { NiceMatrix / xdots } { #3 }
3980     \tl_if_empty:VF \l_@@_xdots_color_tl { \color { \l_@@_xdots_color_tl } }
3981     \@@_actually_draw_Ldots:
3982 \group_end:

```

```

3983     }
3984 }

```

The command `\@@_actually_draw_Ldots:` has the following implicit arguments:

- `\l_@@_initial_i_int`
- `\l_@@_initial_j_int`
- `\l_@@_initial_open_bool`
- `\l_@@_final_i_int`
- `\l_@@_final_j_int`
- `\l_@@_final_open_bool.`

The following function is also used by `\Hdotsfor`.

```

3985 \cs_new_protected:Npn \@@_actually_draw_Ldots:
3986 {
3987   \bool_if:NTF \l_@@_initial_open_bool
3988   {
3989     \@@_open_x_initial_dim:
3990     \@@_qpoint:n { row - \int_use:N \l_@@_initial_i_int - base }
3991     \dim_set_eq:NN \l_@@_y_initial_dim \pgf@y
3992   }
3993   { \@@_set_initial_coords_from_anchor:n { base-east } }
3994   \bool_if:NTF \l_@@_final_open_bool
3995   {
3996     \@@_open_x_final_dim:
3997     \@@_qpoint:n { row - \int_use:N \l_@@_final_i_int - base }
3998     \dim_set_eq:NN \l_@@_y_final_dim \pgf@y
3999   }
4000   { \@@_set_final_coords_from_anchor:n { base-west } }

```

We raise the line of a quantity equal to the radius of the dots because we want the dots really “on” the line of text. Of course, maybe we should not do that when the option `line-style` is used (?).

```

4001   \dim_add:Nn \l_@@_y_initial_dim \l_@@_xdots_radius_dim
4002   \dim_add:Nn \l_@@_y_final_dim \l_@@_xdots_radius_dim
4003   \@@_draw_line:
4004 }

```

The first and the second arguments are the coordinates of the cell where the command has been issued. The third argument is the list of the options.

```

4005 \cs_new_protected:Npn \@@_draw_Cdots:nnn #1 #2 #3
4006 {
4007   \@@_adjust_to_submatrix:nn { #1 } { #2 }
4008   \cs_if_free:cT { @@ _ dotted _ #1 - #2 }
4009   {
4010     \@@_find_extremities_of_line:nnnn { #1 } { #2 } 0 1

```

The previous command may have changed the current environment by marking some cells as “dotted”, but, fortunately, it is outside the group for the options of the line.

```

4011   \group_begin:
4012   \int_compare:nNnTF { #1 } = 0
4013   { \color { nicematrix-first-row } }
4014   {

```

We remind that, when there is a “last row” `\l_@@_last_row_int` will always be (after the construction of the array) the number of that “last row” even if the option `last-row` has been used without value.

```

4015       \int_compare:nNnT { #1 } = \l_@@_last_row_int
4016       { \color { nicematrix-last-row } }
4017   }
4018   \keys_set:nn { NiceMatrix / xdots } { #3 }

```

```

4019         \tl_if_empty:VF \l_@@_xdots_color_tl { \color { \l_@@_xdots_color_tl } }
4020         \@@_actually_draw_Cdots:
4021     \group_end:
4022 }
4023 }

```

The command `\@@_actually_draw_Cdots:` has the following implicit arguments:

- `\l_@@_initial_i_int`
- `\l_@@_initial_j_int`
- `\l_@@_initial_open_bool`
- `\l_@@_final_i_int`
- `\l_@@_final_j_int`
- `\l_@@_final_open_bool.`

```

4024 \cs_new_protected:Npn \@@_actually_draw_Cdots:
4025 {
4026     \bool_if:NTF \l_@@_initial_open_bool
4027     { \@@_open_x_initial_dim: }
4028     { \@@_set_initial_coords_from_anchor:n { mid-east } }
4029     \bool_if:NTF \l_@@_final_open_bool
4030     { \@@_open_x_final_dim: }
4031     { \@@_set_final_coords_from_anchor:n { mid-west } }
4032     \bool_lazy_and:nnTF
4033         \l_@@_initial_open_bool
4034         \l_@@_final_open_bool
4035     {
4036         \@@_qpoint:n { row - \int_use:N \l_@@_initial_i_int }
4037         \dim_set_eq:NN \l_tmpa_dim \pgf@y
4038         \@@_qpoint:n { row - \int_eval:n { \l_@@_initial_i_int + 1 } }
4039         \dim_set:Nn \l_@@_y_initial_dim { ( \l_tmpa_dim + \pgf@y ) / 2 }
4040         \dim_set_eq:NN \l_@@_y_final_dim \l_@@_y_initial_dim
4041     }
4042     {
4043         \bool_if:NT \l_@@_initial_open_bool
4044         { \dim_set_eq:NN \l_@@_y_initial_dim \l_@@_y_final_dim }
4045         \bool_if:NT \l_@@_final_open_bool
4046         { \dim_set_eq:NN \l_@@_y_final_dim \l_@@_y_initial_dim }
4047     }
4048     \@@_draw_line:
4049 }
4050 \cs_new_protected:Npn \@@_open_y_initial_dim:
4051 {
4052     \@@_qpoint:n { row - \int_use:N \l_@@_initial_i_int - base }
4053     \dim_set:Nn \l_@@_y_initial_dim
4054     {
4055         \fp_to_dim:n
4056         {
4057             \pgf@y
4058             + ( \box_ht:N \strutbox + \extrarowheight ) * \arraystretch
4059         }
4060     } % modified 6.13c
4061     \int_step_inline:nnn \l_@@_first_col_int \g_@@_col_total_int
4062     {
4063         \cs_if_exist:cT
4064         { \pgf @ sh @ ns @ \@@_env: - \int_use:N \l_@@_initial_i_int - ##1 }
4065         {
4066             \pgfpointanchor
4067             { \@@_env: - \int_use:N \l_@@_initial_i_int - ##1 }
4068             { north }

```

```

4069         \dim_set:Nn \l_@@_y_initial_dim
4070         { \dim_max:nn \l_@@_y_initial_dim \pgf@y }
4071     }
4072 }
4073 }
4074 \cs_new_protected:Npn \@@_open_y_final_dim:
4075 {
4076     \@@_qpoint:n { row - \int_use:N \l_@@_final_i_int - base }
4077     \dim_set:Nn \l_@@_y_final_dim
4078     { \fp_to_dim:n { \pgf@y - ( \box_dp:N \strutbox ) * \arraystretch } }
4079     % modified 6.13c
4080     \int_step_inline:nnn \l_@@_first_col_int \g_@@_col_total_int
4081     {
4082         \cs_if_exist:cT
4083         { \pgf @ sh @ ns @ \@@_env: - \int_use:N \l_@@_final_i_int - ##1 }
4084         {
4085             \pgfpointanchor
4086             { \@@_env: - \int_use:N \l_@@_final_i_int - ##1 }
4087             { south }
4088             \dim_set:Nn \l_@@_y_final_dim
4089             { \dim_min:nn \l_@@_y_final_dim \pgf@y }
4090         }
4091     }
4092 }

```

The first and the second arguments are the coordinates of the cell where the command has been issued. The third argument is the list of the options.

```

4093 \cs_new_protected:Npn \@@_draw_Vdots:nnn #1 #2 #3
4094 {
4095     \@@_adjust_to_submatrix:nn { #1 } { #2 }
4096     \cs_if_free:cT { @@ _ dotted _ #1 - #2 }
4097     {
4098         \@@_find_extremities_of_line:nnnn { #1 } { #2 } 1 0

```

The previous command may have changed the current environment by marking some cells as “dotted”, but, fortunately, it is outside the group for the options of the line.

```

4099     \group_begin:
4100     \int_compare:nNnTF { #2 } = 0
4101     { \color { nicematrix-first-col } }
4102     {
4103         \int_compare:nNnT { #2 } = \l_@@_last_col_int
4104         { \color { nicematrix-last-col } }
4105     }
4106     \keys_set:nn { NiceMatrix / xdots } { #3 }
4107     \tl_if_empty:VF \l_@@_xdots_color_tl
4108     { \color { \l_@@_xdots_color_tl } }
4109     \@@_actually_draw_Vdots:
4110 \group_end:
4111 }
4112 }

```

The command `\@@_actually_draw_Vdots:` has the following implicit arguments:

- `\l_@@_initial_i_int`
- `\l_@@_initial_j_int`
- `\l_@@_initial_open_bool`
- `\l_@@_final_i_int`
- `\l_@@_final_j_int`
- `\l_@@_final_open_bool`.

The following function is also used by `\Vdotsfor`.

```
4113 \cs_new_protected:Npn \@@_actually_draw_Vdots:
4114 {
```

The boolean `\l_tmpa_bool` indicates whether the column is of type `l` or may be considered as if.

```
4115 \bool_set_false:N \l_tmpa_bool
```

First the case when the line is closed on both ends.

```
4116 \bool_lazy_or:nnF \l_@@_initial_open_bool \l_@@_final_open_bool
4117 {
4118   \@@_set_initial_coords_from_anchor:n { south-west }
4119   \@@_set_final_coords_from_anchor:n { north-west }
4120   \bool_set:Nn \l_tmpa_bool
4121   { \dim_compare_p:nNn \l_@@_x_initial_dim = \l_@@_x_final_dim }
4122 }
```

Now, we try to determine whether the column is of type `c` or may be considered as if.

```
4123 \bool_if:NTF \l_@@_initial_open_bool
4124 \@@_open_y_initial_dim:
4125 { \@@_set_initial_coords_from_anchor:n { south } }
4126 \bool_if:NTF \l_@@_final_open_bool
4127 \@@_open_y_final_dim:
4128 { \@@_set_final_coords_from_anchor:n { north } }
4129 \bool_if:NTF \l_@@_initial_open_bool
4130 {
4131   \bool_if:NTF \l_@@_final_open_bool
4132   {
4133     \@@_qpoint:n { col - \int_use:N \l_@@_initial_j_int }
4134     \dim_set_eq:NN \l_tmpa_dim \pgf@x
4135     \@@_qpoint:n { col - \int_eval:n { \l_@@_initial_j_int + 1 } }
4136     \dim_set:Nn \l_@@_x_initial_dim { ( \pgf@x + \l_tmpa_dim ) / 2 }
4137     \dim_set_eq:NN \l_@@_x_final_dim \l_@@_x_initial_dim
```

We may think that the final user won't use a "last column" which contains only a command `\Vdots`. However, if the `\Vdots` is in fact used to draw, not a dotted line, but an arrow (to indicate the number of rows of the matrix), it may be really encountered.

```
4138 \int_compare:nNnT \l_@@_last_col_int > { -2 }
4139 {
4140   \int_compare:nNnT \l_@@_initial_j_int = \g_@@_col_total_int
4141   {
4142     \dim_set_eq:NN \l_tmpa_dim \l_@@_right_margin_dim
4143     \dim_add:Nn \l_tmpa_dim \l_@@_extra_right_margin_dim
4144     \dim_add:Nn \l_@@_x_initial_dim \l_tmpa_dim
4145     \dim_add:Nn \l_@@_x_final_dim \l_tmpa_dim
4146   }
4147 }
4148 }
4149 { \dim_set_eq:NN \l_@@_x_initial_dim \l_@@_x_final_dim }
4150 }
4151 {
4152   \bool_if:NTF \l_@@_final_open_bool
4153   { \dim_set_eq:NN \l_@@_x_final_dim \l_@@_x_initial_dim }
4154 }
```

Now the case where both extremities are closed. The first conditional tests whether the column is of type `c` or may be considered as if.

```
4155 \dim_compare:nNnF \l_@@_x_initial_dim = \l_@@_x_final_dim
4156 {
4157   \dim_set:Nn \l_@@_x_initial_dim
4158   {
4159     \bool_if:NTF \l_tmpa_bool \dim_min:nn \dim_max:nn
4160     \l_@@_x_initial_dim \l_@@_x_final_dim
4161   }
4162   \dim_set_eq:NN \l_@@_x_final_dim \l_@@_x_initial_dim
4163 }
```

```

4164     }
4165   }
4166   \@@_draw_line:
4167 }

```

For the diagonal lines, the situation is a bit more complicated because, by default, we parallelize the diagonals lines. The first diagonal line is drawn and then, all the other diagonal lines are drawn parallel to the first one.

The first and the second arguments are the coordinates of the cell where the command has been issued. The third argument is the list of the options.

```

4168 \cs_new_protected:Npn \@@_draw_Ddots:nnn #1 #2 #3
4169 {
4170   \@@_adjust_to_submatrix:nn { #1 } { #2 }
4171   \cs_if_free:cT { @@ _ dotted _ #1 - #2 }
4172   {
4173     \@@_find_extremities_of_line:nnnn { #1 } { #2 } 1 1

```

The previous command may have changed the current environment by marking some cells as “dotted”, but, fortunately, it is outside the group for the options of the line.

```

4174     \group_begin:
4175     \keys_set:nn { NiceMatrix / xdots } { #3 }
4176     \tl_if_empty:VF \l_@@_xdots_color_tl { \color { \l_@@_xdots_color_tl } }
4177     \@@_actually_draw_Ddots:
4178     \group_end:
4179   }
4180 }

```

The command `\@@_actually_draw_Ddots:` has the following implicit arguments:

- `\l_@@_initial_i_int`
- `\l_@@_initial_j_int`
- `\l_@@_initial_open_bool`
- `\l_@@_final_i_int`
- `\l_@@_final_j_int`
- `\l_@@_final_open_bool`.

```

4181 \cs_new_protected:Npn \@@_actually_draw_Ddots:
4182 {
4183   \bool_if:NTF \l_@@_initial_open_bool
4184   {
4185     \@@_open_y_initial_dim:
4186     \@@_open_x_initial_dim:
4187   }
4188   { \@@_set_initial_coords_from_anchor:n { south-east } }
4189   \bool_if:NTF \l_@@_final_open_bool
4190   {
4191     \@@_open_x_final_dim:
4192     \dim_set_eq:NN \l_@@_x_final_dim \pgf@x
4193   }
4194   { \@@_set_final_coords_from_anchor:n { north-west } }

```

We have retrieved the coordinates in the usual way (they are stored in `\l_@@_x_initial_dim`, etc.). If the parallelization of the diagonals is set, we will have (maybe) to adjust the fourth coordinate.

```

4195   \bool_if:NT \l_@@_parallelize_diags_bool
4196   {
4197     \int_gincr:N \g_@@_ddots_int

```

We test if the diagonal line is the first one (the counter `\g_@@_ddots_int` is created for this usage).

```

4198     \int_compare:nNnTF \g_@@_ddots_int = 1

```

If the diagonal line is the first one, we have no adjustment of the line to do but we store the Δ_x and the Δ_y of the line because these values will be used to draw the others diagonal lines parallels to the first one.

```

4199     {
4200         \dim_gset:Nn \g_@@_delta_x_one_dim
4201         { \l_@@_x_final_dim - \l_@@_x_initial_dim }
4202         \dim_gset:Nn \g_@@_delta_y_one_dim
4203         { \l_@@_y_final_dim - \l_@@_y_initial_dim }
4204     }

```

If the diagonal line is not the first one, we have to adjust the second extremity of the line by modifying the coordinate `\l_@@_x_initial_dim`.

```

4205     {
4206         \dim_set:Nn \l_@@_y_final_dim
4207         {
4208             \l_@@_y_initial_dim +
4209             ( \l_@@_x_final_dim - \l_@@_x_initial_dim ) *
4210             \dim_ratio:nn \g_@@_delta_y_one_dim \g_@@_delta_x_one_dim
4211         }
4212     }
4213 }
4214 \@@_draw_line:
4215 }

```

We draw the `\Iddots` diagonals in the same way.

The first and the second arguments are the coordinates of the cell where the command has been issued. The third argument is the list of the options.

```

4216 \cs_new_protected:Npn \@@_draw_Iddots:nnn #1 #2 #3
4217 {
4218     \@@_adjust_to_submatrix:nn { #1 } { #2 }
4219     \cs_if_free:cT { @@ _ dotted _ #1 - #2 }
4220     {
4221         \@@_find_extremities_of_line:nnnn { #1 } { #2 } 1 { -1 }

```

The previous command may have changed the current environment by marking some cells as “dotted”, but, fortunately, it is outside the group for the options of the line.

```

4222     \group_begin:
4223     \keys_set:nn { NiceMatrix / xdots } { #3 }
4224     \tl_if_empty:VF \l_@@_xdots_color_tl { \color { \l_@@_xdots_color_tl } }
4225     \@@_actually_draw_Iddots:
4226     \group_end:
4227 }
4228 }

```

The command `\@@_actually_draw_Iddots:` has the following implicit arguments:

- `\l_@@_initial_i_int`
- `\l_@@_initial_j_int`
- `\l_@@_initial_open_bool`
- `\l_@@_final_i_int`
- `\l_@@_final_j_int`
- `\l_@@_final_open_bool`.

```

4229 \cs_new_protected:Npn \@@_actually_draw_Iddots:
4230 {
4231     \bool_if:NTF \l_@@_initial_open_bool
4232     {
4233         \@@_open_y_initial_dim:
4234         \@@_open_x_initial_dim:

```



```

4235     }
4236     { \@@_set_initial_coords_from_anchor:n { south-west } }
4237     \bool_if:NTF \l_@@_final_open_bool
4238     {
4239         \@@_open_y_final_dim:
4240         \@@_open_x_final_dim:
4241     }
4242     { \@@_set_final_coords_from_anchor:n { north-east } }
4243     \bool_if:NT \l_@@_parallelize_diags_bool
4244     {
4245         \int_gincr:N \g_@@_iddots_int
4246         \int_compare:nNnTF \g_@@_iddots_int = 1
4247         {
4248             \dim_gset:Nn \g_@@_delta_x_two_dim
4249             { \l_@@_x_final_dim - \l_@@_x_initial_dim }
4250             \dim_gset:Nn \g_@@_delta_y_two_dim
4251             { \l_@@_y_final_dim - \l_@@_y_initial_dim }
4252         }
4253         {
4254             \dim_set:Nn \l_@@_y_final_dim
4255             {
4256                 \l_@@_y_initial_dim +
4257                 ( \l_@@_x_final_dim - \l_@@_x_initial_dim ) *
4258                 \dim_ratio:nn \g_@@_delta_y_two_dim \g_@@_delta_x_two_dim
4259             }
4260         }
4261     }
4262     \@@_draw_line:
4263 }

```

The actual instructions for drawing the dotted lines with Tikz

The command `\@@_draw_line:` should be used in a `{pgfpicture}`. It has six implicit arguments:

- `\l_@@_x_initial_dim`
- `\l_@@_y_initial_dim`
- `\l_@@_x_final_dim`
- `\l_@@_y_final_dim`
- `\l_@@_initial_open_bool`
- `\l_@@_final_open_bool`

```

4264 \cs_new_protected:Npn \@@_draw_line:
4265 {
4266     \pgfrememberpicturepositiononpagetrue
4267     \pgf@relevantforpicturesizefalse
4268     \bool_lazy_or:nnTF
4269     { \tl_if_eq_p:NN \l_@@_xdots_line_style_tl \c_@@_standard_tl }
4270     \l_@@_dotted_bool
4271     \@@_draw_standard_dotted_line:
4272     \@@_draw_unstandard_dotted_line:
4273 }

```

We have to do a special construction with `\exp_args:NV` to be able to put in the list of options in the correct place in the Tikz instruction.

```

4274 \cs_new_protected:Npn \@@_draw_unstandard_dotted_line:
4275 {
4276     \begin { scope }

```

```

4277 \@@_draw_unstandard_dotted_line:o
4278 { \l_@@_xdots_line_style_tl , \l_@@_xdots_color_tl }
4279 }

```

We have used the fact that, in PGF, un color name can be put directly in a list of options (that's why we have put directly `\l_@@_xdots_color_tl`).

The argument of `\@@_draw_unstandard_dotted_line:n` is, in fact, the list of options.

```

4280 \cs_new_protected:Npn \@@_draw_unstandard_dotted_line:n #1
4281 {
4282   \@@_draw_unstandard_dotted_line:nVV
4283   { #1 }
4284   \l_@@_xdots_up_tl
4285   \l_@@_xdots_down_tl
4286 }
4287 \cs_generate_variant:Nn \@@_draw_unstandard_dotted_line:n { o }
4288 \cs_new_protected:Npn \@@_draw_unstandard_dotted_line:nnn #1 #2 #3
4289 {
4290   \draw
4291   [
4292     #1 ,
4293     shorten-> = \l_@@_xdots_shorten_end_dim ,
4294     shorten-< = \l_@@_xdots_shorten_start_dim ,
4295   ]
4296   ( \l_@@_x_initial_dim , \l_@@_y_initial_dim )

```

Be careful: We can't put `\c_math_toggle_token` instead of `$` in the following lines because we are in the contents of Tikz nodes (and they will be *rescanned* if the Tikz library `babel` is loaded).

```

4297   -- node [ sloped , above ] { $ \scriptstyle #2 $ }
4298   node [ sloped , below ] { $ \scriptstyle #3 $ }
4299   ( \l_@@_x_final_dim , \l_@@_y_final_dim ) ;
4300 \end { scope }
4301 }
4302 \cs_generate_variant:Nn \@@_draw_unstandard_dotted_line:nnn { n V V }

```

The command `\@@_draw_standard_dotted_line:` draws the line with our system of dots (which gives a dotted line with real round dots).

```

4303 \cs_new_protected:Npn \@@_draw_standard_dotted_line:
4304 {
4305   \bool_lazy_and:nnF
4306   { \tl_if_empty_p:N \l_@@_xdots_up_tl }
4307   { \tl_if_empty_p:N \l_@@_xdots_down_tl }
4308   {
4309     \pgfscope
4310     \pgftransformshift
4311     {
4312       \pgfpointlineattime { 0.5 }
4313       { \pgfpoint \l_@@_x_initial_dim \l_@@_y_initial_dim }
4314       { \pgfpoint \l_@@_x_final_dim \l_@@_y_final_dim }
4315     }
4316     \pgftransformrotate
4317     {
4318       \fp_eval:n
4319       {
4320         atand
4321         (
4322           \l_@@_y_final_dim - \l_@@_y_initial_dim ,
4323           \l_@@_x_final_dim - \l_@@_x_initial_dim
4324         )
4325       }
4326     }
4327     \pgfnode
4328     { rectangle }
4329     { south }

```

```

4330     {
4331         \c_math_toggle_token
4332         \scriptstyle \l_@@_xdots_up_tl
4333         \c_math_toggle_token
4334     }
4335     { }
4336     { \pgfusepath { } }
4337     \pgfnode
4338     { rectangle }
4339     { north }
4340     {
4341         \c_math_toggle_token
4342         \scriptstyle \l_@@_xdots_down_tl
4343         \c_math_toggle_token
4344     }
4345     { }
4346     { \pgfusepath { } }
4347     \endpgfscope
4348 }
4349 \group_begin:

```

The dimension `\l_@@_l_dim` is the length ℓ of the line to draw. We use the floating point reals of the L3 programming layer to compute this length.

```

4350     \dim_zero_new:N \l_@@_l_dim
4351     \dim_set:Nn \l_@@_l_dim
4352     {
4353         \fp_to_dim:n
4354         {
4355             sqrt
4356             (
4357                 ( \l_@@_x_final_dim - \l_@@_x_initial_dim ) ^ 2
4358                 +
4359                 ( \l_@@_y_final_dim - \l_@@_y_initial_dim ) ^ 2
4360             )
4361         }
4362     }

```

It seems that, during the first compilations, the value of `\l_@@_l_dim` may be erroneous (equal to zero or very large). We must detect these cases because they would cause errors during the drawing of the dotted line. Maybe we should also write something in the `aux` file to say that one more compilation should be done.

```

4363     \bool_lazy_or:nnF
4364     { \dim_compare_p:nNn { \dim_abs:n \l_@@_l_dim } > \c_@@_max_l_dim }
4365     { \dim_compare_p:nNn \l_@@_l_dim = \c_zero_dim }
4366     \@@_draw_standard_dotted_line_i:
4367 \group_end:
4368 }
4369 \dim_const:Nn \c_@@_max_l_dim { 50 cm }
4370 \cs_new_protected:Npn \@@_draw_standard_dotted_line_i:
4371 {

```

The number of dots will be `\l_tmpa_int + 1`.

```

4372     \bool_if:NTF \l_@@_initial_open_bool
4373     {
4374         \bool_if:NTF \l_@@_final_open_bool
4375         {
4376             \int_set:Nn \l_tmpa_int
4377             { \dim_ratio:nn \l_@@_l_dim \l_@@_xdots_inter_dim }
4378         }
4379         {
4380             \int_set:Nn \l_tmpa_int
4381             {
4382                 \dim_ratio:nn

```

```

4383         { \l_@@_l_dim - \l_@@_xdots_shorten_start_dim }
4384         \l_@@_xdots_inter_dim
4385     }
4386 }
4387 }
4388 {
4389     \bool_if:NTF \l_@@_final_open_bool
4390     {
4391         \int_set:Nn \l_tmpa_int
4392         {
4393             \dim_ratio:nn
4394             { \l_@@_l_dim - \l_@@_xdots_shorten_end_dim }
4395             \l_@@_xdots_inter_dim
4396         }
4397     }
4398     {
4399         \int_set:Nn \l_tmpa_int
4400         {
4401             \dim_ratio:nn
4402             {
4403                 \l_@@_l_dim
4404                 - \l_@@_xdots_shorten_start_dim - \l_@@_xdots_shorten_end_dim
4405             }
4406             \l_@@_xdots_inter_dim
4407         }
4408     }
4409 }

```

The dimensions `\l_tmpa_dim` and `\l_tmpb_dim` are the coordinates of the vector between two dots in the dotted line.

```

4410 \dim_set:Nn \l_tmpa_dim
4411 {
4412     ( \l_@@_x_final_dim - \l_@@_x_initial_dim ) *
4413     \dim_ratio:nn \l_@@_xdots_inter_dim \l_@@_l_dim
4414 }
4415 \dim_set:Nn \l_tmpb_dim
4416 {
4417     ( \l_@@_y_final_dim - \l_@@_y_initial_dim ) *
4418     \dim_ratio:nn \l_@@_xdots_inter_dim \l_@@_l_dim
4419 }

```

In the loop over the dots, the dimensions `\l_@@_x_initial_dim` and `\l_@@_y_initial_dim` will be used for the coordinates of the dots. But, before the loop, we must move until the first dot.

```

4420 \dim_gadd:Nn \l_@@_x_initial_dim
4421 {
4422     ( \l_@@_x_final_dim - \l_@@_x_initial_dim ) *
4423     \dim_ratio:nn
4424     {
4425         \l_@@_l_dim - \l_@@_xdots_inter_dim * \l_tmpa_int
4426         + \l_@@_xdots_shorten_start_dim - \l_@@_xdots_shorten_end_dim
4427     }
4428     { 2 \l_@@_l_dim }
4429 }
4430 \dim_gadd:Nn \l_@@_y_initial_dim
4431 {
4432     ( \l_@@_y_final_dim - \l_@@_y_initial_dim ) *
4433     \dim_ratio:nn
4434     {
4435         \l_@@_l_dim - \l_@@_xdots_inter_dim * \l_tmpa_int
4436         + \l_@@_xdots_shorten_start_dim - \l_@@_xdots_shorten_end_dim
4437     }
4438     { 2 \l_@@_l_dim }
4439 }
4440 \pgf@relevantforpicturesizefalse

```

```

4441 \int_step_inline:nnn 0 \l_tmpa_int
4442 {
4443   \pgfpathcircle
4444   { \pgfpoint \l_@@_x_initial_dim \l_@@_y_initial_dim }
4445   { \l_@@_xdots_radius_dim }
4446   \dim_add:Nn \l_@@_x_initial_dim \l_tmpa_dim
4447   \dim_add:Nn \l_@@_y_initial_dim \l_tmpb_dim
4448 }
4449 \pgfusepathqfill
4450 }

```

User commands available in the new environments

The commands `\@@_Ldots`, `\@@_Cdots`, `\@@_Vdots`, `\@@_Ddots` and `\@@_Iddots` will be linked to `\Ldots`, `\Cdots`, `\Vdots`, `\Ddots` and `\Iddots` in the environments `{NiceArray}` (the other environments of `nicematrix` rely upon `{NiceArray}`).

The syntax of these commands uses the character `_` as embellishment and that's why we have to insert a character `_` in the *arg spec* of these commands. However, we don't know the future catcode of `_` in the main document (maybe the user will use `underscore`, and, in that case, the catcode is 13 because `underscore` activates `_`). That's why these commands will be defined in a `\hook_gput_code:nnn { begindocument } { . }` and the *arg spec* will be rescanned.

```

4451 \hook_gput_code:nnn { begindocument } { . }
4452 {
4453   \tl_set:Nn \l_@@_argspec_tl { 0 { } E { _ ^ } { { } { } } }
4454   \tl_set_rescan:Nno \l_@@_argspec_tl { } \l_@@_argspec_tl
4455   \exp_args:NNV \NewDocumentCommand \@@_Ldots \l_@@_argspec_tl
4456   {
4457     \int_compare:nNnTF \c@jCol = 0
4458     { \@@_error:nn { in~first~col } \Ldots }
4459     {
4460       \int_compare:nNnTF \c@jCol = \l_@@_last_col_int
4461       { \@@_error:nn { in~last~col } \Ldots }
4462       {
4463         \@@_instruction_of_type:nnn \c_false_bool { \Ldots }
4464         { #1 , down = #2 , up = #3 }
4465       }
4466     }
4467     \bool_if:NF \l_@@_nullify_dots_bool
4468     { \phantom { \ensuremath { \@@_old_ldots } } }
4469     \bool_gset_true:N \g_@@_empty_cell_bool
4470   }

4471   \exp_args:NNV \NewDocumentCommand \@@_Cdots \l_@@_argspec_tl
4472   {
4473     \int_compare:nNnTF \c@jCol = 0
4474     { \@@_error:nn { in~first~col } \Cdots }
4475     {
4476       \int_compare:nNnTF \c@jCol = \l_@@_last_col_int
4477       { \@@_error:nn { in~last~col } \Cdots }
4478       {
4479         \@@_instruction_of_type:nnn \c_false_bool { \Cdots }
4480         { #1 , down = #2 , up = #3 }
4481       }
4482     }
4483     \bool_if:NF \l_@@_nullify_dots_bool
4484     { \phantom { \ensuremath { \@@_old_cdots } } }
4485     \bool_gset_true:N \g_@@_empty_cell_bool
4486   }

```

```

4487 \exp_args:NNV \NewDocumentCommand \@@_Vdots \l_@@_argspec_tl
4488 {
4489   \int_compare:nNnTF \c@iRow = 0
4490   { \@@_error:nn { in~first~row } \Vdots }
4491   {
4492     \int_compare:nNnTF \c@iRow = \l_@@_last_row_int
4493     { \@@_error:nn { in~last~row } \Vdots }
4494     {
4495       \@@_instruction_of_type:nnn \c_false_bool { \Vdots }
4496       { #1 , down = #2 , up = #3 }
4497     }
4498   }
4499   \bool_if:NF \l_@@_nullify_dots_bool
4500   { \phantom { \ensuremath { \@@_old_vdots } } }
4501   \bool_gset_true:N \g_@@_empty_cell_bool
4502 }

4503 \exp_args:NNV \NewDocumentCommand \@@_Ddots \l_@@_argspec_tl
4504 {
4505   \int_case:nnF \c@iRow
4506   {
4507     0 { \@@_error:nn { in~first~row } \Ddots }
4508     \l_@@_last_row_int { \@@_error:nn { in~last~row } \Ddots }
4509   }
4510   {
4511     \int_case:nnF \c@jCol
4512     {
4513       0 { \@@_error:nn { in~first~col } \Ddots }
4514       \l_@@_last_col_int { \@@_error:nn { in~last~col } \Ddots }
4515     }
4516     {
4517       \keys_set_known:nn { NiceMatrix / Ddots } { #1 }
4518       \@@_instruction_of_type:nnn \l_@@_draw_first_bool { \Ddots }
4519       { #1 , down = #2 , up = #3 }
4520     }
4521   }
4522 }
4523 \bool_if:NF \l_@@_nullify_dots_bool
4524 { \phantom { \ensuremath { \@@_old_ddots } } }
4525 \bool_gset_true:N \g_@@_empty_cell_bool
4526 }

4527 \exp_args:NNV \NewDocumentCommand \@@_Iddots \l_@@_argspec_tl
4528 {
4529   \int_case:nnF \c@iRow
4530   {
4531     0 { \@@_error:nn { in~first~row } \Iddots }
4532     \l_@@_last_row_int { \@@_error:nn { in~last~row } \Iddots }
4533   }
4534   {
4535     \int_case:nnF \c@jCol
4536     {
4537       0 { \@@_error:nn { in~first~col } \Iddots }
4538       \l_@@_last_col_int { \@@_error:nn { in~last~col } \Iddots }
4539     }
4540     {
4541       \keys_set_known:nn { NiceMatrix / Ddots } { #1 }
4542       \@@_instruction_of_type:nnn \l_@@_draw_first_bool { \Iddots }
4543       { #1 , down = #2 , up = #3 }
4544     }
4545   }
4546   \bool_if:NF \l_@@_nullify_dots_bool

```

```

4547         { \phantom { \ensuremath { \@@_old_iddots } } }
4548     \bool_gset_true:N \g_@@_empty_cell_bool
4549 }
4550 }

```

End of the \AddToHook.

Despite its name, the following set of keys will be used for \Ddots but also for \Iddots.

```

4551 \keys_define:nn { NiceMatrix / Ddots }
4552 {
4553     draw-first .bool_set:N = \l_@@_draw_first_bool ,
4554     draw-first .default:n = true ,
4555     draw-first .value_forbidden:n = true
4556 }

```

The command \@@_Hspace: will be linked to \hspace in {NiceArray}.

```

4557 \cs_new_protected:Npn \@@_Hspace:
4558 {
4559     \bool_gset_true:N \g_@@_empty_cell_bool
4560     \hspace
4561 }

```

In the environments of nicematrix, the command \multicolumn is redefined. We will patch the environment {tabular} to go back to the previous value of \multicolumn.

```

4562 \cs_set_eq:NN \@@_old_multicolumn \multicolumn

```

The command \@@_Hdotsfor will be linked to \Hdotsfor in {NiceArrayWithDelims}. Tikz nodes are created also in the implicit cells of the \Hdotsfor (maybe we should modify that point).

This command must *not* be protected since it begins with \multicolumn.

```

4563 \cs_new:Npn \@@_Hdotsfor:
4564 {
4565     \bool_lazy_and:nnTF
4566     { \int_compare_p:nNn \c@jCol = 0 }
4567     { \int_compare_p:nNn \l_@@_first_col_int = 0 }
4568     {
4569         \bool_if:NTF \g_@@_after_col_zero_bool
4570         {
4571             \multicolumn { 1 } { c } { }
4572             \@@_Hdotsfor_i
4573         }
4574         { \@@_fatal:n { Hdotsfor~in~col~0 } }
4575     }
4576     {
4577         \multicolumn { 1 } { c } { }
4578         \@@_Hdotsfor_i
4579     }
4580 }

```

The command \@@_Hdotsfor_i is defined with \NewDocumentCommand because it has an optional argument. Note that such a command defined by \NewDocumentCommand is protected and that's why we have put the \multicolumn before (in the definition of \@@_Hdotsfor:).

```

4581 \hook_gput_code:nnn { begindocument } { . }
4582 {
4583     \tl_set:Nn \l_@@_argspec_tl { 0 { } m 0 { } E { _ ^ } { { } { } } }
4584     \tl_set_rescan:Nno \l_@@_argspec_tl { } \l_@@_argspec_tl

```

We don't put ! before the last optionnal argument for homogeneity with \Cdots, etc. which have only one optional argument.

```

4585     \exp_args:NNV \NewDocumentCommand \@@_Hdotsfor_i \l_@@_argspec_tl
4586     {
4587         \tl_gput_right:Nx \g_@@_Hvdotsfor_lines_tl

```

```

4588     {
4589         \@@_Hdotsfor:nnnn
4590         { \int_use:N \c@iRow }
4591         { \int_use:N \c@jCol }
4592         { #2 }
4593         {
4594             #1 , #3 ,
4595             down = \exp_not:n { #4 } ,
4596             up = \exp_not:n { #5 }
4597         }
4598     }
4599     \prg_replicate:nn { #2 - 1 } { & \multicolumn { 1 } { c } { } }
4600 }
4601 }

```

```

4602 \cs_new_protected:Npn \@@_Hdotsfor:nnnn #1 #2 #3 #4
4603 {
4604     \bool_set_false:N \l_@@_initial_open_bool
4605     \bool_set_false:N \l_@@_final_open_bool

```

For the row, it's easy.

```

4606     \int_set:Nn \l_@@_initial_i_int { #1 }
4607     \int_set_eq:NN \l_@@_final_i_int \l_@@_initial_i_int

```

For the column, it's a bit more complicated.

```

4608     \int_compare:nNnTF { #2 } = 1
4609     {
4610         \int_set:Nn \l_@@_initial_j_int 1
4611         \bool_set_true:N \l_@@_initial_open_bool
4612     }
4613     {
4614         \cs_if_exist:cTF
4615         {
4616             pgf @ sh @ ns @ \@@_env:
4617             - \int_use:N \l_@@_initial_i_int
4618             - \int_eval:n { #2 - 1 }
4619         }
4620         { \int_set:Nn \l_@@_initial_j_int { #2 - 1 } }
4621         {
4622             \int_set:Nn \l_@@_initial_j_int { #2 }
4623             \bool_set_true:N \l_@@_initial_open_bool
4624         }
4625     }
4626     \int_compare:nNnTF { #2 + #3 - 1 } = \c@jCol
4627     {
4628         \int_set:Nn \l_@@_final_j_int { #2 + #3 - 1 }
4629         \bool_set_true:N \l_@@_final_open_bool
4630     }
4631     {
4632         \cs_if_exist:cTF
4633         {
4634             pgf @ sh @ ns @ \@@_env:
4635             - \int_use:N \l_@@_final_i_int
4636             - \int_eval:n { #2 + #3 }
4637         }
4638         { \int_set:Nn \l_@@_final_j_int { #2 + #3 } }
4639         {
4640             \int_set:Nn \l_@@_final_j_int { #2 + #3 - 1 }
4641             \bool_set_true:N \l_@@_final_open_bool
4642         }
4643     }
4644     \group_begin:
4645     \int_compare:nNnTF { #1 } = 0
4646     { \color { nicematrix-first-row } }

```



```

4647 {
4648   \int_compare:nNnT { #1 } = \g_@@_row_total_int
4649     { \color { nicematrix-last-row } }
4650 }
4651 \keys_set:nn { NiceMatrix / xdots } { #4 }
4652 \tl_if_empty:VF \l_@@_xdots_color_tl { \color { \l_@@_xdots_color_tl } }
4653 \@@_actually_draw_Ldots:
4654 \group_end:

```

We declare all the cells concerned by the `\Hdotsfor` as “dotted” (for the dotted lines created by `\Cdots`, `\Ldots`, etc., this job is done by `\@@_find_extremities_of_line:nnnn`). This declaration is done by defining a special control sequence (to nil).

```

4655   \int_step_inline:nnn { #2 } { #2 + #3 - 1 }
4656     { \cs_set:cpn { @@ _ dotted _ #1 - ##1 } { } }
4657 }

4658 \hook_gput_code:nnn { begindocument } { . }
4659 {
4660   \tl_set:Nn \l_@@_argspec_tl { 0 { } m 0 { } E { _ ^ } { { } { } } }
4661   \tl_set_rescan:Nno \l_@@_argspec_tl { } \l_@@_argspec_tl
4662   \exp_args:NNV \NewDocumentCommand \@@_Vdotsfor: \l_@@_argspec_tl
4663     {
4664       \tl_gput_right:Nx \g_@@_HVdotsfor_lines_tl
4665         {
4666           \@@_Vdotsfor:nnnn
4667             { \int_use:N \c@iRow }
4668             { \int_use:N \c@jCol }
4669             { #2 }
4670             {
4671               #1 , #3 ,
4672               down = \exp_not:n { #4 } , up = \exp_not:n { #5 }
4673             }
4674         }
4675     }
4676 }

```

Enf of `\AddToHook`.

```

4677 \cs_new_protected:Npn \@@_Vdotsfor:nnnn #1 #2 #3 #4
4678 {
4679   \bool_set_false:N \l_@@_initial_open_bool
4680   \bool_set_false:N \l_@@_final_open_bool

```

For the column, it’s easy.

```

4681   \int_set:Nn \l_@@_initial_j_int { #2 }
4682   \int_set_eq:NN \l_@@_final_j_int \l_@@_initial_j_int

```

For the row, it’s a bit more complicated.

```

4683   \int_compare:nNnTF #1 = 1
4684     {
4685     \int_set:Nn \l_@@_initial_i_int 1
4686     \bool_set_true:N \l_@@_initial_open_bool
4687   }
4688   {
4689     \cs_if_exist:cTF
4690       {
4691         pgf @ sh @ ns @ \@@_env:
4692         - \int_eval:n { #1 - 1 }
4693         - \int_use:N \l_@@_initial_j_int
4694       }
4695     { \int_set:Nn \l_@@_initial_i_int { #1 - 1 } }
4696     {
4697       \int_set:Nn \l_@@_initial_i_int { #1 }
4698       \bool_set_true:N \l_@@_initial_open_bool

```

```

4699     }
4700   }
4701   \int_compare:nNnTF { #1 + #3 - 1 } = \c@iRow
4702   {
4703     \int_set:Nn \l_@@_final_i_int { #1 + #3 - 1 }
4704     \bool_set_true:N \l_@@_final_open_bool
4705   }
4706   {
4707     \cs_if_exist:cTF
4708     {
4709       pgf @ sh @ ns @ \@@_env:
4710       - \int_eval:n { #1 + #3 }
4711       - \int_use:N \l_@@_final_j_int
4712     }
4713     { \int_set:Nn \l_@@_final_i_int { #1 + #3 } }
4714     {
4715       \int_set:Nn \l_@@_final_i_int { #1 + #3 - 1 }
4716       \bool_set_true:N \l_@@_final_open_bool
4717     }
4718   }
4719   \group_begin:
4720   \int_compare:nNnTF { #2 } = 0
4721   { \color { nicematrix-first-col } }
4722   {
4723     \int_compare:nNnT { #2 } = \g_@@_col_total_int
4724     { \color { nicematrix-last-col } }
4725   }
4726   \keys_set:nn { NiceMatrix / xdots } { #4 }
4727   \tl_if_empty:VF \l_@@_xdots_color_tl { \color { \l_@@_xdots_color_tl } }
4728   \@@_actually_draw_Vdots:
4729   \group_end:

```

We declare all the cells concerned by the `\Vdotsfor` as “dotted” (for the dotted lines created by `\Cdots`, `\Ldots`, etc., this job is done by `\@@_find_extremities_of_line:nnnn`). This declaration is done by defining a special control sequence (to nil).

```

4730   \int_step_inline:nnn { #1 } { #1 + #3 - 1 }
4731   { \cs_set:cpn { @@ _ dotted _ ##1 - #2 } { } }
4732 }

```

The command `\@@_rotate:` will be linked to `\rotate` in `{NiceArrayWithDelims}`.

```

4733 \cs_new_protected:Npn \@@_rotate: { \bool_gset_true:N \g_@@_rotate_bool }

```

The command `\line` accessible in code-after

In the `\CodeAfter`, the command `\@@_line:nn` will be linked to `\line`. This command takes two arguments which are the specifications of two cells in the array (in the format i - j) and draws a dotted line between these cells.

First, we write a command with the following behaviour:

- If the argument is of the format i - j , our command applies the command `\int_eval:n` to i and j ;
- If not (that is to say, when it’s a name of a `\Block`), the argument is left unchanged.

This must *not* be protected (and is, of course fully expandable).⁷⁶

⁷⁶Indeed, we want that the user may use the command `\line` in `\CodeAfter` with LaTeX counters in the arguments — with the command `\value`.

```

4734 \cs_new:Npn \@@_double_int_eval:n #1-#2 \q_stop
4735 {
4736   \tl_if_empty:nTF { #2 }
4737     { #1 }
4738     { \@@_double_int_eval_i:n #1-#2 \q_stop }
4739 }
4740 \cs_new:Npn \@@_double_int_eval_i:n #1-#2- \q_stop
4741 { \int_eval:n { #1 } - \int_eval:n { #2 } }

```

With the following construction, the command `\@@_double_int_eval:n` is applied to both arguments before the application of `\@@_line_i:nn` (the construction uses the fact the `\@@_line_i:nn` is protected and that `\@@_double_int_eval:n` is fully expandable).

```

4742 \hook_gput_code:nnn { begindocument } { . }
4743 {
4744   \tl_set:Nn \l_@@_argspec_tl { 0 { } m m ! 0 { } E { _ ^ } { { } { } } }
4745   \tl_set_rescan:Nno \l_@@_argspec_tl { } \l_@@_argspec_tl
4746   \exp_args:NNV \NewDocumentCommand \@@_line \l_@@_argspec_tl
4747     {
4748       \group_begin:
4749       \keys_set:nn { NiceMatrix / xdots } { #1 , #4 , down = #5 , up = #6 }
4750       \tl_if_empty:VF \l_@@_xdots_color_tl { \color { \l_@@_xdots_color_tl } }
4751       \use:e
4752       {
4753         \@@_line_i:nn
4754         { \@@_double_int_eval:n #2 - \q_stop }
4755         { \@@_double_int_eval:n #3 - \q_stop }
4756       }
4757       \group_end:
4758     }
4759 }
4760 \cs_new_protected:Npn \@@_line_i:nn #1 #2
4761 {
4762   \bool_set_false:N \l_@@_initial_open_bool
4763   \bool_set_false:N \l_@@_final_open_bool
4764   \bool_if:nTF
4765     {
4766       \cs_if_free_p:c { pgf @ sh @ ns @ \@@_env: - #1 }
4767       ||
4768       \cs_if_free_p:c { pgf @ sh @ ns @ \@@_env: - #2 }
4769     }
4770     {
4771       \@@_error:nnn { unknown~cell~for~line~in~CodeAfter } { #1 } { #2 }
4772     }
4773     { \@@_draw_line_ii:nn { #1 } { #2 } }
4774 }
4775 \hook_gput_code:nnn { begindocument } { . }
4776 {
4777   \cs_new_protected:Npx \@@_draw_line_ii:nn #1 #2
4778   {

```

We recall that, when externalization is used, `\tikzpicture` and `\endtikzpicture` (or `\pgfpicture` and `\endpgfpicture`) must be directly “visible” and that why we do this static construction of the command `\@@_draw_line_ii:.`

```

4779   \c_@@_pgfortikzpicture_tl
4780   \@@_draw_line_iii:nn { #1 } { #2 }
4781   \c_@@_endpgfortikzpicture_tl
4782 }
4783 }

```

The following command *must* be protected (it’s used in the construction of `\@@_draw_line_ii:nn`).

```

4784 \cs_new_protected:Npn \@@_draw_line_iii:nn #1 #2
4785 {

```

```

4786 \pgfrememberpicturepositiononpagetrue
4787 \pgfpointshapeborder { \@@_env: - #1 } { \@@_qpoint:n { #2 } }
4788 \dim_set_eq:NN \l_@@_x_initial_dim \pgf@x
4789 \dim_set_eq:NN \l_@@_y_initial_dim \pgf@y
4790 \pgfpointshapeborder { \@@_env: - #2 } { \@@_qpoint:n { #1 } }
4791 \dim_set_eq:NN \l_@@_x_final_dim \pgf@x
4792 \dim_set_eq:NN \l_@@_y_final_dim \pgf@y
4793 \@@_draw_line:
4794 }

```

The commands `\Ldots`, `\Cdots`, `\Vdots`, `\Ddots`, and `\Iddots` don't use this command because they have to do other settings (for example, the diagonal lines must be parallelized).

The command `\RowStyle`

```

4795 \keys_define:nn { NiceMatrix / RowStyle }
4796 {
4797   cell-space-top-limit .dim_set:N = \l_tmpa_dim ,
4798   cell-space-top-limit .initial:n = \c_zero_dim ,
4799   cell-space-top-limit .value_required:n = true ,
4800   cell-space-bottom-limit .dim_set:N = \l_tmpb_dim ,
4801   cell-space-bottom-limit .initial:n = \c_zero_dim ,
4802   cell-space-bottom-limit .value_required:n = true ,
4803   cell-space-limits .meta:n =
4804   {
4805     cell-space-top-limit = #1 ,
4806     cell-space-bottom-limit = #1 ,
4807   } ,
4808   color .tl_set:N = \l_@@_color_tl ,
4809   color .value_required:n = true ,
4810   bold .bool_set:N = \l_tmpa_bool ,
4811   bold .default:n = true ,
4812   bold .initial:n = false ,
4813   nb-rows .code:n =
4814     \str_if_eq:nnTF { #1 } { * }
4815     { \int_set:Nn \l_@@_key_nb_rows_int { 500 } }
4816     { \int_set:Nn \l_@@_key_nb_rows_int { #1 } } ,
4817   nb-rows .value_required:n = true ,
4818   rowcolor .tl_set:N = \l_tmpa_tl ,
4819   rowcolor .value_required:n = true ,
4820   rowcolor .initial:n = ,
4821   unknown .code:n = \@@_error:n { Unknown-key-for-RowStyle }
4822 }

```

```

4823 \NewDocumentCommand \@@_RowStyle:n { 0 { } m }
4824 {
4825   \group_begin:
4826   \tl_clear:N \l_tmpa_tl % value of \rowcolor
4827   \tl_clear:N \l_@@_color_tl
4828   \int_set:Nn \l_@@_key_nb_rows_int 1
4829   \keys_set:nn { NiceMatrix / RowStyle } { #1 }

```

If the key `rowcolor` has been used.

```

4830   \tl_if_empty:NF \l_tmpa_tl
4831   {

```

First, the end of the current row (we remind that `\RowStyle` applies to the *end* of the current row).

```

4832     \tl_gput_right:Nx \g_@@_pre_code_before_tl
4833     {

```

The command `\@@_exp_color_arg:N` is *fully expandable*.

```

4834     \@@_exp_color_arg:N \@@_rectanglecolor \l_tmpa_tl
4835     { \int_use:N \c@iRow - \int_use:N \c@jCol }

```

```

4836         { \int_use:N \c@iRow - * }
4837     }

```

Then, the other rows (if there is several rows).

```

4838     \int_compare:nNnT \l_@@_key_nb_rows_int > 1
4839     {
4840         \tl_gput_right:Nx \g_@@_pre_code_before_tl
4841         {
4842             \@@_exp_color_arg:NV \@@_rowcolor \l_tmpa_tl
4843             {
4844                 \int_eval:n { \c@iRow + 1 }
4845                 - \int_eval:n { \c@iRow + \l_@@_key_nb_rows_int - 1 }
4846             }
4847         }
4848     }
4849 }

```

```

4850 \tl_gput_right:Nn \g_@@_row_style_tl { \ifnum \c@iRow < }
4851 \tl_gput_right:Nx \g_@@_row_style_tl
4852 { \int_eval:n { \c@iRow + \l_@@_key_nb_rows_int } }
4853 \tl_gput_right:Nn \g_@@_row_style_tl { #2 }

```

$\backslash\l_tmpa_dim$ is the value of the key `cell-space-top-limit` of `\RowStyle`.

```

4854 \dim_compare:nNnT \l_tmpa_dim > \c_zero_dim
4855 {
4856     \tl_gput_right:Nx \g_@@_row_style_tl
4857     {
4858         \tl_gput_right:Nn \exp_not:N \g_@@_cell_after_hook_tl
4859         {
4860             \dim_set:Nn \l_@@_cell_space_top_limit_dim
4861             { \dim_use:N \l_tmpa_dim }
4862         }
4863     }
4864 }

```

$\backslash\l_tmpb_dim$ is the value of the key `cell-space-bottom-limit` of `\RowStyle`.

```

4865 \dim_compare:nNnT \l_tmpb_dim > \c_zero_dim
4866 {
4867     \tl_gput_right:Nx \g_@@_row_style_tl
4868     {
4869         \tl_gput_right:Nn \exp_not:N \g_@@_cell_after_hook_tl
4870         {
4871             \dim_set:Nn \l_@@_cell_space_bottom_limit_dim
4872             { \dim_use:N \l_tmpb_dim }
4873         }
4874     }
4875 }

```

$\backslash\l_@@_color_tl$ is the value of the key `color` of `\RowStyle`.

```

4876 \tl_if_empty:NF \l_@@_color_tl
4877 {
4878     \tl_gput_right:Nx \g_@@_row_style_tl
4879     {
4880         \mode_leave_vertical:
4881         \@@_color:n { \l_@@_color_tl }
4882     }
4883 }

```

$\backslash\l_tmpa_bool$ is the value of the key `bold`.

```

4884 \bool_if:NT \l_tmpa_bool
4885 {
4886     \tl_gput_right:Nn \g_@@_row_style_tl
4887     {
4888         \if_mode_math:
4889             \c_math_toggle_token
4890             \bfseries \boldmath
4891             \c_math_toggle_token
4892         \else:

```

```

4893         \bfseries \boldmath
4894     \fi:
4895 }
4896 }
4897 \tl_gput_right:Nn \g_@@_row_style_tl { \fi }
4898 \group_end:
4899 \g_@@_row_style_tl
4900 \ignorespaces
4901 }

```

Colors of cells, rows and columns

We want to avoid the thin white lines that are shown in some PDF viewers (eg: with the engine MuPDF used by SumatraPDF). That's why we try to draw rectangles of the same color in the same instruction `\pgfusepath { fill }` (and they will be in the same instruction `fill`—coded `f`—in the resulting PDF).

The commands `\@@_rowcolor`, `\@@_columncolor`, `\@@_rectanglecolor` and `\@@_rowlistcolors` don't directly draw the corresponding rectangles. Instead, they store their instructions color by color:

- A sequence `\g_@@_colors_seq` will be built containing all the colors used by at least one of these instructions. Each *color* may be prefixed by its color model (eg: `[gray]{0.5}`).
- For the color whose index in `\g_@@_colors_seq` is equal to *i*, a list of instructions which use that color will be constructed in the token list `\g_@@_color_i_tl`. In that token list, the instructions will be written using `\@@_cartesian_color:nn` and `\@@_rectanglecolor:nn`.

`#1` is the color and `#2` is an instruction using that color. Despite its name, the command `\@@_add_to_colors_seq:nn` doesn't only add a color to `\g_@@_colors_seq`: it also updates the corresponding token list `\g_@@_color_i_tl`. We add in a global way because the final user may use the instructions such as `\cellcolor` in a loop of `pgffor` in the `\CodeBefore` (and we recall that a loop of `pgffor` is encapsulated in a group).

```

4902 \cs_new_protected:Npn \@@_add_to_colors_seq:nn #1 #2
4903 {

```

First, we look for the number of the color and, if it's found, we store it in `\l_tmpa_int`. If the color is not present in `\l_@@_colors_seq`, `\l_tmpa_int` will remain equal to 0.

```

4904     \int_zero:N \l_tmpa_int

```

We don't take into account the colors like `myserie!!+` because those colors are special color from a `\definecolorseries` of `xcolor`.

```

4905     \str_if_in:nnF { #1 } { !! }
4906     {
4907         \seq_map_indexed_inline:Nn \g_@@_colors_seq
4908         { \tl_if_eq:nnT { #1 } { ##2 } { \int_set:Nn \l_tmpa_int { ##1 } } }
4909     }
4910     \int_compare:nNnTF \l_tmpa_int = \c_zero_int

```

First, the case where the color is a *new* color (not in the sequence).

```

4911     {
4912         \seq_gput_right:Nn \g_@@_colors_seq { #1 }
4913         \tl_gset:cx { g_@@_color _ \seq_count:N \g_@@_colors_seq _ tl } { #2 }
4914     }

```

Now, the case where the color is *not* a new color (the color is in the sequence at the position `\l_tmpa_int`).

```

4915     { \tl_gput_right:cx { g_@@_color _ \int_use:N \l_tmpa_int _ tl } { #2 } }
4916 }

```

```

4917 \cs_generate_variant:Nn \@@_add_to_colors_seq:nn { x n }
4918 \cs_generate_variant:Nn \@@_add_to_colors_seq:nn { x x }

```

The macro `\@@_actually_color:` will actually fill all the rectangles, color by color (using the sequence `\l_@@_colors_seq` and all the token lists of the form `\l_@@_color_i_tl`).

```

4919 \cs_new_protected:Npn \@@_actually_color:
4920 {
4921   \pgfpicture
4922   \pgf@relevantforpicturesizefalse
4923   \seq_map_indexed_inline:Nn \g_@@_colors_seq
4924   {
4925     \color ##2
4926     \use:c { g_@@_color _ ##1 _tl }
4927     \tl_gclear:c { g_@@_color _ ##1 _tl }
4928     \pgfusepath { fill }
4929   }
4930   \endpgfpicture
4931 }
4932 \cs_new_protected:Npn \@@_cartesian_color:nn #1 #2
4933 {
4934   \tl_set:Nn \l_@@_rows_tl { #1 }
4935   \tl_set:Nn \l_@@_cols_tl { #2 }
4936   \@@_cartesian_path:
4937 }

```

Here is an example : `\@@_rowcolor {red!15} {1,3,5-7,10-}`

```

4938 \NewDocumentCommand \@@_rowcolor { 0 { } m m }
4939 {
4940   \tl_if_blank:nF { #2 }
4941   {
4942     \@@_add_to_colors_seq:xn
4943     { \tl_if_blank:nF { #1 } { [ #1 ] } { #2 } }
4944     { \@@_cartesian_color:nn { #3 } { - } }
4945   }
4946 }

```

Here an example : `\@@_columncolor:nn {red!15} {1,3,5-7,10-}`

```

4947 \NewDocumentCommand \@@_columncolor { 0 { } m m }
4948 {
4949   \tl_if_blank:nF { #2 }
4950   {
4951     \@@_add_to_colors_seq:xn
4952     { \tl_if_blank:nF { #1 } { [ #1 ] } { #2 } }
4953     { \@@_cartesian_color:nn { - } { #3 } }
4954   }
4955 }

```

Here is an example : `\@@_rectanglecolor{red!15}{2-3}{5-6}`

```

4956 \NewDocumentCommand \@@_rectanglecolor { 0 { } m m m }
4957 {
4958   \tl_if_blank:nF { #2 }
4959   {
4960     \@@_add_to_colors_seq:xn
4961     { \tl_if_blank:nF { #1 } { [ #1 ] } { #2 } }
4962     { \@@_rectanglecolor:nnn { #3 } { #4 } { 0 pt } }
4963   }
4964 }

```

The last argument is the radius of the corners of the rectangle.

```

4965 \NewDocumentCommand \@@_roundedrectanglecolor { 0 { } m m m m }
4966 {
4967   \tl_if_blank:nF { #2 }
4968   {

```

```

4969     \@@_add_to_colors_seq:xn
4970     { \tl_if_blank:nF { #1 } { [ #1 ] } { #2 } }
4971     { \@@_rectanglecolor:nnn { #3 } { #4 } { #5 } }
4972   }
4973 }

```

The last argument is the radius of the corners of the rectangle.

```

4974 \cs_new_protected:Npn \@@_rectanglecolor:nnn #1 #2 #3
4975 {
4976   \@@_cut_on_hyphen:w #1 \q_stop
4977   \tl_clear_new:N \l_@@_tmpc_tl
4978   \tl_clear_new:N \l_@@_tmpd_tl
4979   \tl_set_eq:NN \l_@@_tmpc_tl \l_tmpa_tl
4980   \tl_set_eq:NN \l_@@_tmpd_tl \l_tmpb_tl
4981   \@@_cut_on_hyphen:w #2 \q_stop
4982   \tl_set:Nx \l_@@_rows_tl { \l_@@_tmpc_tl - \l_tmpa_tl }
4983   \tl_set:Nx \l_@@_cols_tl { \l_@@_tmpd_tl - \l_tmpb_tl }

```

The command `\@@_cartesian_path:n` takes in two implicit arguments: `\l_@@_cols_tl` and `\l_@@_rows_tl`.

```

4984   \@@_cartesian_path:n { #3 }
4985 }

```

Here is an example : `\@@_cellcolor[rgb]{0.5,0.5,0}{2-3,3-4,4-5,5-6}`

```

4986 \NewDocumentCommand \@@_cellcolor { 0 { } m m }
4987 {
4988   \clist_map_inline:nn { #3 }
4989   { \@@_rectanglecolor [ #1 ] { #2 } { ##1 } { ##1 } }
4990 }

```

```

4991 \NewDocumentCommand \@@_chessboardcolors { 0 { } m m }
4992 {
4993   \int_step_inline:nn { \int_use:N \c@iRow }
4994   {
4995     \int_step_inline:nn { \int_use:N \c@jCol }
4996     {
4997       \int_if_even:nTF { ####1 + ##1 }
4998       { \@@_cellcolor [ #1 ] { #2 } }
4999       { \@@_cellcolor [ #1 ] { #3 } }
5000       { ##1 - ####1 }
5001     }
5002   }
5003 }

```

The command `\@@_arraycolor` (linked to `\arraycolor` at the beginning of the `\CodeBefore`) will color the whole tabular (excepted the potential exterior rows and columns) and the cells in the “corners”.

```

5004 \NewDocumentCommand \@@_arraycolor { 0 { } m }
5005 {
5006   \@@_rectanglecolor [ #1 ] { #2 }
5007   { 1 - 1 }
5008   { \int_use:N \c@iRow - \int_use:N \c@jCol }
5009 }

5010 \keys_define:nn { NiceMatrix / rowcolors }
5011 {
5012   respect-blocks .bool_set:N = \l_@@_respect_blocks_bool ,
5013   respect-blocks .default:n = true ,
5014   cols .tl_set:N = \l_@@_cols_tl ,
5015   restart .bool_set:N = \l_@@_rowcolors_restart_bool ,

```



```

5016     restart .default:n = true ,
5017     unknown .code:n = \@@_error:n { Unknown-key-for-rowcolors }
5018 }

```

The command `\rowcolors` (accessible in the `code-before`) is inspired by the command `\rowcolors` of the package `xcolor` (with the option `table`). However, the command `\rowcolors` of `nicematrix` has *not* the optional argument of the command `\rowcolors` of `xcolor`. Here is an example: `\rowcolors{1}{blue!10}{}[respect-blocks]`.

#1 (optional) is the color space ; #2 is a list of intervals of rows ; #3 is the list of colors ; #4 is for the optional list of pairs *key=value*.

```

5019 \NewDocumentCommand \@@_rowlistcolors { 0 { } m m 0 { } }
5020 {

```

The group is for the options. `\l_@@_colors_seq` will be the list of colors.

```

5021   \group_begin:
5022   \seq_clear_new:N \l_@@_colors_seq
5023   \seq_set_split:Nnn \l_@@_colors_seq { , } { #3 }
5024   \tl_clear_new:N \l_@@_cols_tl
5025   \tl_set:Nn \l_@@_cols_tl { - }
5026   \keys_set:nn { NiceMatrix / rowcolors } { #4 }

```

The counter `\l_@@_color_int` will be the rank of the current color in the list of colors (modulo the length of the list).

```

5027   \int_zero_new:N \l_@@_color_int
5028   \int_set:Nn \l_@@_color_int 1
5029   \bool_if:NT \l_@@_respect_blocks_bool
5030   {

```

We don't want to take into account a block which is completely in the “first column” of (number 0) or in the “last column” and that's why we filter the sequence of the blocks (in a the sequence `\l_tmpa_seq`).

```

5031     \seq_set_eq:NN \l_tmpb_seq \g_@@_pos_of_blocks_seq
5032     \seq_set_filter:Nnn \l_tmpa_seq \l_tmpb_seq
5033     { \@@_not_in_exterior_p:nnnnn ##1 }
5034   }
5035   \pgfpicture
5036   \pgf@relevantforpicturesizefalse

```

#2 is the list of intervals of rows.

```

5037   \clist_map_inline:nn { #2 }
5038   {
5039     \tl_set:Nn \l_tmpa_tl { ##1 }
5040     \tl_if_in:NnTF \l_tmpa_tl { - }
5041     { \@@_cut_on_hyphen:w ##1 \q_stop }
5042     { \tl_set:Nx \l_tmpb_tl { \int_use:N \c@iRow } }

```

Now, `\l_tmpa_tl` and `\l_tmpb_tl` are the first row and the last row of the interval of rows that we have to treat. The counter `\l_tmpa_int` will be the index of the loop over the rows.

```

5043     \int_set:Nn \l_tmpa_int \l_tmpa_tl
5044     \bool_if:NTF \l_@@_rowcolors_restart_bool
5045     { \int_set:Nn \l_@@_color_int 1 }
5046     { \int_set:Nn \l_@@_color_int \l_tmpa_tl }
5047     \int_zero_new:N \l_@@_tmpc_int
5048     \int_set:Nn \l_@@_tmpc_int \l_tmpb_tl
5049     \int_do_until:nNnn \l_tmpa_int > \l_@@_tmpc_int
5050     {

```

We will compute in `\l_tmpb_int` the last row of the “block”.

```

5051     \int_set_eq:NN \l_tmpb_int \l_tmpa_int

```

If the key `respect-blocks` is in force, we have to adjust that value (of course).

```

5052     \bool_if:NT \l_@@_respect_blocks_bool
5053     {
5054       \seq_set_filter:Nnn \l_tmpb_seq \l_tmpa_seq
5055       { \@@_intersect_our_row_p:nnnnn #####1 }
5056       \seq_map_inline:Nn \l_tmpb_seq { \@@_rowcolors_i:nnnnn #####1 }

```

Now, the last row of the block is computed in `\l_tmpb_int`.

```

5057     }
5058     \tl_set:Nx \l_@@_rows_tl
5059     { \int_use:N \l_tmpa_int - \int_use:N \l_tmpb_int }
\l_@@_tmpc_tl will be the color that we will use.
5060     \tl_clear_new:N \l_@@_color_tl
5061     \tl_set:Nx \l_@@_color_tl
5062     {
5063       \@@_color_index:n
5064       {
5065         \int_mod:nn
5066         { \l_@@_color_int - 1 }
5067         { \seq_count:N \l_@@_colors_seq }
5068         + 1
5069       }
5070     }
5071     \tl_if_empty:NF \l_@@_color_tl
5072     {
5073       \@@_add_to_colors_seq:xx
5074       { \tl_if_blank:nF { #1 } { [ #1 ] } { \l_@@_color_tl } }
5075       { \@@_cartesian_color:nn { \l_@@_rows_tl } { \l_@@_cols_tl } }
5076     }
5077     \int_incr:N \l_@@_color_int
5078     \int_set:Nn \l_tmpa_int { \l_tmpb_int + 1 }
5079   }
5080 }
5081 \endpgfpicture
5082 \group_end:
5083 }

```

The command `\@@_color_index:n` peeks in `\l_@@_colors_seq` the color at the index #1. However, if that color is the symbol `=`, the previous one is poken. This macro is recursive.

```

5084 \cs_new:Npn \@@_color_index:n #1
5085 {
5086   \str_if_eq:eeTF { \seq_item:Nn \l_@@_colors_seq { #1 } } { = }
5087   { \@@_color_index:n { #1 - 1 } }
5088   { \seq_item:Nn \l_@@_colors_seq { #1 } }
5089 }

```

The command `\rowcolors` (available in the `\CodeBefore`) is a specialisation of the most general command `\rowlistcolors`.

```

5090 \NewDocumentCommand \@@_rowcolors { 0 { } m m m 0 { } }
5091 { \@@_rowlistcolors [ #1 ] { #2 } { { #3 } , { #4 } } [ #5 ] }

5092 \cs_new_protected:Npn \@@_rowcolors_i:nnnnn #1 #2 #3 #4 #5
5093 {
5094   \int_compare:nNnT { #3 } > \l_tmpb_int
5095   { \int_set:Nn \l_tmpb_int { #3 } }
5096 }

5097 \prg_new_conditional:Nnn \@@_not_in_exterior:nnnnn p
5098 {
5099   \bool_lazy_or:nnTF
5100   { \int_compare_p:nNn { #4 } = \c_zero_int }
5101   { \int_compare_p:nNn { #2 } = { \int_eval:n { \c@jCol + 1 } } }
5102   \prg_return_false:
5103   \prg_return_true:
5104 }

```

The following command return true when the block intersects the row \l_tmpa_int.

```

5105 \prg_new_conditional:Nnn \@@_intersect_our_row:nnnnn p
5106 {
5107   \bool_if:nTF
5108   {
5109     \int_compare_p:n { #1 <= \l_tmpa_int }
5110     &&
5111     \int_compare_p:n { \l_tmpa_int <= #3 }
5112   }
5113   \prg_return_true:
5114   \prg_return_false:
5115 }

```

The following command uses two implicit arguments: \l_@@_rows_tl and \l_@@_cols_tl which are specifications for a set of rows and a set of columns. It creates a path but does *not* fill it. It must be filled by another command after. The argument is the radius of the corners. We define below a command \@@_cartesian_path: which corresponds to a value 0 pt for the radius of the corners. This command is in particular used in \@@_rectanglecolor:nnn (used in \@@_rectanglecolor, itself used in \@@_cellcolor).

```

5116 \cs_new_protected:Npn \@@_cartesian_path:n #1
5117 {
5118   \bool_lazy_and:nnT
5119   { ! \seq_if_empty_p:N \l_@@_corners_cells_seq }
5120   { \dim_compare_p:nNn { #1 } = \c_zero_dim }
5121   {
5122     \@@_expand_clist:NN \l_@@_cols_tl \c_jCol
5123     \@@_expand_clist:NN \l_@@_rows_tl \c_iRow
5124   }

```

We begin the loop over the columns.

```

5125 \clist_map_inline:Nn \l_@@_cols_tl
5126 {
5127   \tl_set:Nn \l_tmpa_tl { ##1 }
5128   \tl_if_in:NnTF \l_tmpa_tl { - }
5129   { \@@_cut_on_hyphen:w ##1 \q_stop }
5130   { \@@_cut_on_hyphen:w ##1 - ##1 \q_stop }
5131   \bool_lazy_or:nnT
5132   { \tl_if_blank_p:V \l_tmpa_tl }
5133   { \str_if_eq_p:Vn \l_tmpa_tl { * } }
5134   { \tl_set:Nn \l_tmpa_tl { 1 } }
5135   \bool_lazy_or:nnT
5136   { \tl_if_blank_p:V \l_tmpb_tl }
5137   { \str_if_eq_p:Vn \l_tmpb_tl { * } }
5138   { \tl_set:Nx \l_tmpb_tl { \int_use:N \c_jCol } }
5139   \int_compare:nNnT \l_tmpb_tl > \c_jCol
5140   { \tl_set:Nx \l_tmpb_tl { \int_use:N \c_jCol } }

```

\l_@@_tmpc_tl will contain the number of column.

```

5141 \tl_set_eq:NN \l_@@_tmpc_tl \l_tmpa_tl

```

If we decide to provide the commands \cellcolor, \rectanglecolor, \rowcolor, \columncolor, \rowcolors and \chessboardcolors in the code-before of a \SubMatrix, we will have to modify the following line, by adding a kind of offset. We will have also some other lines to modify.

```

5142 \@@_qpoint:n { col - \l_tmpa_tl }
5143 \int_compare:nNnTF \l_@@_first_col_int = \l_tmpa_tl
5144 { \dim_set:Nn \l_@@_tmpc_dim { \pgf@x - 0.5 \arrayrulewidth } }
5145 { \dim_set:Nn \l_@@_tmpc_dim { \pgf@x + 0.5 \arrayrulewidth } }
5146 \@@_qpoint:n { col - \int_eval:n { \l_tmpb_tl + 1 } }
5147 \dim_set:Nn \l_tmpa_dim { \pgf@x + 0.5 \arrayrulewidth }

```

We begin the loop over the rows.

```

5148 \clist_map_inline:Nn \l_@@_rows_tl
5149 {
5150   \tl_set:Nn \l_tmpa_tl { ####1 }

```

```

5151 \tl_if_in:NnTF \l_tmpa_tl { - }
5152 { \@@_cut_on_hyphen:w #####1 \q_stop }
5153 { \@@_cut_on_hyphen:w #####1 - #####1 \q_stop }
5154 \tl_if_empty:NT \l_tmpa_tl { \tl_set:Nn \l_tmpa_tl { 1 } }
5155 \tl_if_empty:NT \l_tmpb_tl
5156 { \tl_set:Nx \l_tmpb_tl { \int_use:N \c@iRow } }
5157 \int_compare:nNnT \l_tmpb_tl > \c@iRow
5158 { \tl_set:Nx \l_tmpb_tl { \int_use:N \c@iRow } }

```

Now, the numbers of both rows are in `\l_tmpa_tl` and `\l_tmpb_tl`.

```

5159 \seq_if_in:NxF \l_@@_corners_cells_seq
5160 { \l_tmpa_tl - \l_@@_tmpc_tl }
5161 {
5162   \@@_qpoint:n { row - \int_eval:n { \l_tmpb_tl + 1 } }
5163   \dim_set:Nn \l_tmpb_dim { \pgf@y + 0.5 \arrayrulewidth }
5164   \@@_qpoint:n { row - \l_tmpa_tl }
5165   \dim_set:Nn \l_@@_tmpd_dim { \pgf@y + 0.5 \arrayrulewidth }
5166   \pgfsetcornersarced { \pgfpoint { #1 } { #1 } }
5167   \pgfpathrectanglecorners
5168   { \pgfpoint \l_@@_tmpc_dim \l_@@_tmpd_dim }
5169   { \pgfpoint \l_tmpa_dim \l_tmpb_dim }
5170 }
5171 }
5172 }
5173 }

```

The following command corresponds to a radius of the corners equal to 0 pt. This command is used by the commands `\@@_rowcolors`, `\@@_columncolor` and `\@@_rowcolor:n` (used in `\@@_rowcolor`).

```

5174 \cs_new_protected:Npn \@@_cartesian_path: { \@@_cartesian_path:n { 0 pt } }

```

The following command will be used only with `\l_@@_cols_tl` and `\c@jCol` (first case) or with `\l_@@_rows_tl` and `\c@iRow` (second case). For instance, with `\l_@@_cols_tl` equal to 2,4-6,8-* and `\c@jCol` equal to 10, the clist `\l_@@_cols_tl` will be replaced by 2,4,5,6,8,9,10.

```

5175 \cs_new_protected:Npn \@@_expand_clist:NN #1 #2
5176 {
5177   \clist_set_eq:NN \l_tmpa_clist #1
5178   \clist_clear:N #1
5179   \clist_map_inline:Nn \l_tmpa_clist
5180   {
5181     \tl_set:Nn \l_tmpa_tl { ##1 }
5182     \tl_if_in:NnTF \l_tmpa_tl { - }
5183     { \@@_cut_on_hyphen:w ##1 \q_stop }
5184     { \@@_cut_on_hyphen:w ##1 - ##1 \q_stop }
5185     \bool_lazy_or:nnT
5186     { \tl_if_blank_p:V \l_tmpa_tl }
5187     { \str_if_eq_p:Vn \l_tmpa_tl { * } }
5188     { \tl_set:Nn \l_tmpa_tl { 1 } }
5189     \bool_lazy_or:nnT
5190     { \tl_if_blank_p:V \l_tmpb_tl }
5191     { \str_if_eq_p:Vn \l_tmpb_tl { * } }
5192     { \tl_set:Nx \l_tmpb_tl { \int_use:N #2 } }
5193     \int_compare:nNnT \l_tmpb_tl > #2
5194     { \tl_set:Nx \l_tmpb_tl { \int_use:N #2 } }
5195     \int_step_inline:nnn \l_tmpa_tl \l_tmpb_tl
5196     { \clist_put_right:Nn #1 { #####1 } }
5197   }
5198 }

```

When the user uses the key `colortbl-like`, the following command will be linked to `\cellcolor` in the tabular.

```

5199 \NewDocumentCommand \@@_cellcolor_tabular { 0 { } m }
5200 {

```

```

5201 \tl_gput_right:Nx \g_@@_pre_code_before_tl
5202 {

```

We must not expand the color (#2) because the color may contain the token ! which may be activated by some packages (ex.: babel with the option french on latex and pdflatex).

```

5203 \@@_cellcolor [ #1 ] { \exp_not:n { #2 } }
5204 { \int_use:N \c@iRow - \int_use:N \c@jCol }
5205 }
5206 \ignorespaces
5207 }

```

When the user uses the key colortbl-like, the following command will be linked to \rowcolor in the tabular.

```

5208 \NewDocumentCommand \@@_rowcolor_tabular { 0 { } m }
5209 {
5210 \tl_gput_right:Nx \g_@@_pre_code_before_tl
5211 {
5212 \@@_rectanglecolor [ #1 ] { \exp_not:n { #2 } }
5213 { \int_use:N \c@iRow - \int_use:N \c@jCol }
5214 { \int_use:N \c@iRow - \exp_not:n { \int_use:N \c@jCol } }
5215 }
5216 \ignorespaces
5217 }

```

```

5218 \NewDocumentCommand \@@_columncolor_preamble { 0 { } m }
5219 {

```

With the following line, we test whether the cell is the first one we encounter in its column (don't forget that some rows may be incomplete).

```

5220 \int_compare:nNnT \c@jCol > \g_@@_col_total_int
5221 {

```

You use gput_left because we want the specification of colors for the columns drawn before the specifications of color for the rows (and the cells). Be careful: maybe this is not effective since we have an analyze of the instructions in the \CodeBefore in order to fill color by color (to avoid the thin white lines).

```

5222 \tl_gput_left:Nx \g_@@_pre_code_before_tl
5223 {
5224 \exp_not:N \columncolor [ #1 ]
5225 { \exp_not:n { #2 } } { \int_use:N \c@jCol }
5226 }
5227 }
5228 }

```

The vertical and horizontal rules

OnlyMainNiceMatrix

We give to the user the possibility to define new types of columns (with \newcolumnntype of array) for special vertical rules (*e.g.* rules thicker than the standard ones) which will not extend in the potential exterior rows of the array.

We provide the command \OnlyMainNiceMatrix in that goal. However, that command must be no-op outside the environments of nicematrix (and so the user will be allowed to use the same new type of column in the environments of nicematrix and in the standard environments of array).

That's why we provide first a global definition of \OnlyMainNiceMatrix.

```

5229 \cs_set_eq:NN \OnlyMainNiceMatrix \use:n

```

Another definition of `\OnlyMainNiceMatrix` will be linked to the command in the environments of `nicematrix`. Here is that definition, called `\@@_OnlyMainNiceMatrix:n`.

```

5230 \cs_new_protected:Npn \@@_OnlyMainNiceMatrix:n #1
5231 {
5232   \int_compare:nNnTF \l_@@_first_col_int = 0
5233   { \@@_OnlyMainNiceMatrix_i:n { #1 } }
5234   {
5235     \int_compare:nNnTF \c@jCol = 0
5236     {
5237       \int_compare:nNnF \c@iRow = { -1 }
5238       { \int_compare:nNnF \c@iRow = { \l_@@_last_row_int - 1 } { #1 } }
5239     }
5240     { \@@_OnlyMainNiceMatrix_i:n { #1 } }
5241   }
5242 }

```

This definition may seem complicated but we must remind that the number of row `\c@iRow` is incremented in the first cell of the row, *after* a potential vertical rule on the left side of the first cell. The command `\@@_OnlyMainNiceMatrix_i:n` is only a short-cut which is used twice in the above command. This command must *not* be protected.

```

5243 \cs_new_protected:Npn \@@_OnlyMainNiceMatrix_i:n #1
5244 {
5245   \int_compare:nNnF \c@iRow = 0
5246   { \int_compare:nNnF \c@iRow = \l_@@_last_row_int { #1 } }
5247 }

```

Remember that `\c@iRow` is not always inferior to `\l_@@_last_row_int` because `\l_@@_last_row_int` may be equal to -2 or -1 (we can't write `\int_compare:nNnT \c@iRow < \l_@@_last_row_int`).

General system for drawing rules

When a command, environment or “subsystem” of `nicematrix` wants to draw a rule, it will write in the internal `\CodeAfter` a command `\@@_vline:n` or `\@@_hline:n`. Both commands take in as argument a list of *key=value* pairs. That list will first be analyzed with the following set of keys. However, unknown keys will be analyzed further with another set of keys.

```

5248 \keys_define:nn { NiceMatrix / Rules }
5249 {
5250   position .int_set:N = \l_@@_position_int ,
5251   position .value_required:n = true ,
5252   start .int_set:N = \l_@@_start_int ,
5253   start .initial:n = 1 ,
5254   end .code:n =
5255     \bool_lazy_or:nnTF
5256     { \tl_if_empty_p:n { #1 } }
5257     { \str_if_eq_p:nn { #1 } { last } }
5258     { \int_set_eq:NN \l_@@_end_int \c@jCol }
5259     { \int_set:Nn \l_@@_end_int { #1 } }
5260 }

```

It's possible that the rule won't be drawn continuously from `start` to `end` because of the blocks (created with the command `\Block`), the virtual blocks (created by `\Cdots`, etc.), etc. That's why an analyse is done and the rule is cut in small rules which will actually be drawn. The small continuous rules will be drawn by `\@@_vline_ii:` and `\@@_hline_ii:`. Those commands use the following set of keys.

```

5261 \keys_define:nn { NiceMatrix / RulesBis }
5262 {
5263   multiplicity .int_set:N = \l_@@_multiplicity_int ,
5264   multiplicity .initial:n = 1 ,
5265   dotted .bool_set:N = \l_@@_dotted_bool ,
5266   dotted .initial:n = false ,

```

```

5267 dotted .default:n = true ,
5268 color .code:n = \@@_set_CT@arc@:n { #1 } ,
5269 color .value_required:n = true ,
5270 sep-color .code:n = \@@_set_CT@drsc@:n { #1 } ,
5271 sep-color .value_required:n = true ,

```

If the user uses the key `tikz`, the rule (or more precisely: the different sub-rules since a rule may be broken by blocks or others) will be drawn with Tikz.

```

5272 tikz .tl_set:N = \l_@@_tikz_rule_tl ,
5273 tikz .value_required:n = true ,
5274 tikz .initial:n = ,
5275 total-width .dim_set:N = \l_@@_rule_width_dim ,
5276 total-width .value_required:n = true ,
5277 width .meta:n = { total-width = #1 } ,
5278 unknown .code:n = \@@_error:n { Unknow-key-for-RulesBis }
5279 }

```

The vertical rules

The following command will be executed in the internal `\CodeAfter`. The argument `#1` is a list of `key=value` pairs.

```

5280 \cs_new_protected:Npn \@@_vline:n #1
5281 {

```

The group is for the options.

```

5282 \group_begin:
5283 \int_zero_new:N \l_@@_end_int
5284 \int_set_eq:NN \l_@@_end_int \c@iRow
5285 \keys_set_known:nnN { NiceMatrix / Rules } { #1 } \l_@@_other_keys_tl

```

The following test is for the case where the user does not use all the columns specified in the preamble of the environment (for instance, a preamble of `|c|c|c|` but only two columns used).

```

5286 \int_compare:nNnT \l_@@_position_int < { \c@jCol + 2 }
5287 \@@_vline_i:
5288 \group_end:
5289 }

```

```

5290 \cs_new_protected:Npn \@@_vline_i:
5291 {
5292 \int_zero_new:N \l_@@_local_start_int
5293 \int_zero_new:N \l_@@_local_end_int

```

`\l_tmpa_tl` is the number of row and `\l_tmpb_tl` the number of column. When we have found a row corresponding to a rule to draw, we note its number in `\l_@@_tmpc_tl`.

```

5294 \tl_set:Nx \l_tmpb_tl { \int_eval:n \l_@@_position_int }
5295 \int_step_variable:nnNn \l_@@_start_int \l_@@_end_int
5296 \l_tmpa_tl
5297 {

```

The boolean `\g_tmpa_bool` indicates whether the small vertical rule will be drawn. If we find that it is in a block (a real block, created by `\Block` or a virtual block corresponding to a dotted line, created by `\Cdots`, `\Vdots`, etc.), we will set `\g_tmpa_bool` to `false` and the small vertical rule won't be drawn.

```

5298 \bool_gset_true:N \g_tmpa_bool
5299 \seq_map_inline:Nn \g_@@_pos_of_blocks_seq
5300 { \@@_test_vline_in_block:nnnnn ##1 }
5301 \seq_map_inline:Nn \g_@@_pos_of_xdots_seq
5302 { \@@_test_vline_in_block:nnnnn ##1 }
5303 \seq_map_inline:Nn \g_@@_pos_of_stroken_blocks_seq
5304 { \@@_test_vline_in_stroken_block:nnnn ##1 }
5305 \clist_if_empty:NF \l_@@_corners_clist \@@_test_in_corner_v:
5306 \bool_if:NTF \g_tmpa_bool
5307 {
5308 \int_compare:nNnT \l_@@_local_start_int = 0

```

We keep in memory that we have a rule to draw. `\l_@@_local_start_int` will be the starting row of the rule that we will have to draw.

```

5309         { \int_set:Nn \l_@@_local_start_int \l_tmpa_tl }
5310     }
5311     {
5312         \int_compare:nNnT \l_@@_local_start_int > 0
5313         {
5314             \int_set:Nn \l_@@_local_end_int { \l_tmpa_tl - 1 }
5315             \@@_vline_ii:
5316             \int_zero:N \l_@@_local_start_int
5317         }
5318     }
5319 }
5320 \int_compare:nNnT \l_@@_local_start_int > 0
5321 {
5322     \int_set_eq:NN \l_@@_local_end_int \l_@@_end_int
5323     \@@_vline_ii:
5324 }
5325 }

5326 \cs_new_protected:Npn \@@_test_in_corner_v:
5327 {
5328     \int_compare:nNnTF \l_tmpb_tl = { \int_eval:n { \c@jCol + 1 } }
5329     {
5330         \seq_if_in:NxT
5331         \l_@@_corners_cells_seq
5332         { \l_tmpa_tl - \int_eval:n { \l_tmpb_tl - 1 } }
5333         { \bool_set_false:N \g_tmpa_bool }
5334     }
5335     {
5336         \seq_if_in:NxT
5337         \l_@@_corners_cells_seq
5338         { \l_tmpa_tl - \l_tmpb_tl }
5339         {
5340             \int_compare:nNnTF \l_tmpb_tl = 1
5341             { \bool_set_false:N \g_tmpa_bool }
5342             {
5343                 \seq_if_in:NxT
5344                 \l_@@_corners_cells_seq
5345                 { \l_tmpa_tl - \int_eval:n { \l_tmpb_tl - 1 } }
5346                 { \bool_set_false:N \g_tmpa_bool }
5347             }
5348         }
5349     }
5350 }

5351 \cs_new_protected:Npn \@@_vline_ii:
5352 {
5353     \keys_set:nV { NiceMatrix / RulesBis } \l_@@_other_keys_tl
5354     \bool_if:NTF \l_@@_dotted_bool
5355     \@@_vline_iv:
5356     {
5357         \tl_if_empty:NTF \l_@@_tikz_rule_tl
5358         \@@_vline_iii:
5359         \@@_vline_v:
5360     }
5361 }

```

First the case of a standard rule: the user has not used the key `dotted` nor the key `tikz`.

```

5362 \cs_new_protected:Npn \@@_vline_iii:
5363 {

```



```

5364 \pgfpicture
5365 \pgfrememberpicturepositiononpagetrue
5366 \pgf@relevantforpicturesizefalse
5367 \@@_qpoint:n { row - \int_use:N \l_@@_local_start_int }
5368 \dim_set_eq:NN \l_tmpa_dim \pgf@y
5369 \@@_qpoint:n { col - \int_use:N \l_@@_position_int }
5370 \dim_set:Nn \l_tmpb_dim
5371 {
5372   \pgf@x
5373   - 0.5 \l_@@_rule_width_dim
5374   +
5375   ( \arrayrulewidth * \l_@@_multiplicity_int
5376     + \doublerulesep * ( \l_@@_multiplicity_int - 1 ) ) / 2
5377 }
5378 \@@_qpoint:n { row - \int_eval:n { \l_@@_local_end_int + 1 } }
5379 \dim_set_eq:NN \l_@@_tmpc_dim \pgf@y
5380 \bool_lazy_all:nT
5381 {
5382   { \int_compare_p:nNn \l_@@_multiplicity_int > 1 }
5383   { \cs_if_exist_p:N \CT@drsc@ }
5384   { ! \tl_if_blank_p:V \CT@drsc@ }
5385 }
5386 {
5387   \group_begin:
5388   \CT@drsc@
5389   \dim_add:Nn \l_tmpa_dim { 0.5 \arrayrulewidth }
5390   \dim_sub:Nn \l_@@_tmpc_dim { 0.5 \arrayrulewidth }
5391   \dim_set:Nn \l_@@_tmpd_dim
5392   {
5393     \l_tmpb_dim - ( \doublerulesep + \arrayrulewidth )
5394     * ( \l_@@_multiplicity_int - 1 )
5395   }
5396   \pgfpathrectanglecorners
5397   { \pgfpoint \l_tmpb_dim \l_tmpa_dim }
5398   { \pgfpoint \l_@@_tmpd_dim \l_@@_tmpc_dim }
5399   \pgfusepath { fill }
5400   \group_end:
5401 }
5402 \pgfpathmoveto { \pgfpoint \l_tmpb_dim \l_tmpa_dim }
5403 \pgfpathlineto { \pgfpoint \l_tmpb_dim \l_@@_tmpc_dim }
5404 \prg_replicate:nn { \l_@@_multiplicity_int - 1 }
5405 {
5406   \dim_sub:Nn \l_tmpb_dim \arrayrulewidth
5407   \dim_sub:Nn \l_tmpb_dim \doublerulesep
5408   \pgfpathmoveto { \pgfpoint \l_tmpb_dim \l_tmpa_dim }
5409   \pgfpathlineto { \pgfpoint \l_tmpb_dim \l_@@_tmpc_dim }
5410 }
5411 \CT@arc@
5412 \pgfsetlinewidth { 1.1 \arrayrulewidth }
5413 \pgfsetrectcap
5414 \pgfusepathqstroke
5415 \endpgfpicture
5416 }

```

The following code is for the case of a dotted rule (with our system of rounded dots).

```

5417 \cs_new_protected:Npn \@@_vline_iv:
5418 {
5419   \pgfpicture
5420   \pgfrememberpicturepositiononpagetrue
5421   \pgf@relevantforpicturesizefalse
5422   \@@_qpoint:n { col - \int_use:N \l_@@_position_int }
5423   \dim_set:Nn \l_@@_x_initial_dim { \pgf@x - 0.5 \l_@@_rule_width_dim }
5424   \dim_set_eq:NN \l_@@_x_final_dim \l_@@_x_initial_dim

```

```

5425 \@@_qpoint:n { row - \int_use:N \l_@@_local_start_int }
5426 \dim_set_eq:NN \l_@@_y_initial_dim \pgf@y
5427 \@@_qpoint:n { row - \int_eval:n { \l_@@_local_end_int + 1 } }
5428 \dim_set_eq:NN \l_@@_y_final_dim \pgf@y
5429 \CT@arc@
5430 \@@_draw_line:
5431 \endpgfpicture
5432 }

```

The following code is for the case when the user uses the key `tikz` (in the definition of a customized rule by using the key `custom-line`).

```

5433 \cs_new_protected:Npn \@@_vline_v:
5434 {
5435   \begin {tikzpicture }
5436   \pgfrememberpicturepositiononpagetrue
5437   \pgf@relevantforpicturesizefalse
5438   \@@_qpoint:n { row - \int_use:N \l_@@_local_start_int }
5439   \dim_set_eq:NN \l_tmpa_dim \pgf@y
5440   \@@_qpoint:n { col - \int_use:N \l_@@_position_int }
5441   \dim_set:Nn \l_tmpb_dim { \pgf@x - 0.5 \l_@@_rule_width_dim }
5442   \@@_qpoint:n { row - \int_eval:n { \l_@@_local_end_int + 1 } }
5443   \dim_set_eq:NN \l_@@_tmpc_dim \pgf@y
5444   \exp_args:NV \tikzset \l_@@_tikz_rule_tl
5445   \use:x { \exp_not:N \draw [ \l_@@_tikz_rule_tl ] }
5446     ( \l_tmpb_dim , \l_tmpa_dim ) --
5447     ( \l_tmpb_dim , \l_@@_tmpc_dim ) ;
5448   \end { tikzpicture }
5449 }

```

The command `\@@_draw_vlines:` draws all the vertical rules excepted in the blocks, in the virtual blocks (determined by a command such as `\Cdots`) and in the corners (if the key `corners` is used).

```

5450 \cs_new_protected:Npn \@@_draw_vlines:
5451 {
5452   \int_step_inline:nnn
5453   {
5454     \bool_if:nTF { \g_@@_NiceArray_bool && ! \l_@@_except_borders_bool }
5455     1 2
5456   }
5457   {
5458     \bool_if:nTF { \g_@@_NiceArray_bool && ! \l_@@_except_borders_bool }
5459     { \int_eval:n { \c@jCol + 1 } }
5460     \c@jCol
5461   }
5462   {
5463     \tl_if_eq:NnF \l_@@_vlines_clist { all }
5464     { \clist_if_in:NnT \l_@@_vlines_clist { ##1 } }
5465     { \@@_vline:n { position = ##1 , total-width = \arrayrulewidth } }
5466   }
5467 }

```

The horizontal rules

The following command will be executed in the internal `\CodeAfter`. The argument `#1` is a list of `key=value` pairs of the form `{NiceMatrix/Rules}`.

```

5468 \cs_new_protected:Npn \@@_hline:n #1
5469 {

```

The group is for the options.

```

5470   \group_begin:
5471   \int_zero_new:N \l_@@_end_int
5472   \int_set_eq:NN \l_@@_end_int \c@jCol

```

```

5473 \keys_set_known:nnN { NiceMatrix / Rules } { #1 } \l_@@_other_keys_tl
5474 \@@_hline_i:
5475 \group_end:
5476 }

5477 \cs_new_protected:Npn \@@_hline_i:
5478 {
5479   \int_zero_new:N \l_@@_local_start_int
5480   \int_zero_new:N \l_@@_local_end_int

```

\l_tmpa_tl is the number of row and \l_tmpb_tl the number of column. When we have found a column corresponding to a rule to draw, we note its number in \l_@@_tmpc_tl.

```

5481 \tl_set:Nx \l_tmpa_tl { \int_use:N \l_@@_position_int }
5482 \int_step_variable:nnNn \l_@@_start_int \l_@@_end_int
5483   \l_tmpb_tl
5484   {

```

The boolean \g_tmpa_bool indicates whether the small horizontal rule will be drawn. If we find that it is in a block (a real block, created by \Block or a virtual block corresponding to a dotted line, created by \Cdots, \Vdots, etc.), we will set \g_tmpa_bool to false and the small horizontal rule won't be drawn.

```

5485   \bool_gset_true:N \g_tmpa_bool
5486   \seq_map_inline:Nn \g_@@_pos_of_blocks_seq
5487     { \@@_test_hline_in_block:nnnnn ##1 }
5488   \seq_map_inline:Nn \g_@@_pos_of_xdots_seq
5489     { \@@_test_hline_in_block:nnnnn ##1 }
5490   \seq_map_inline:Nn \g_@@_pos_of_stroken_blocks_seq
5491     { \@@_test_hline_in_stroken_block:nnnn ##1 }
5492   \clist_if_empty:NF \l_@@_corners_clist \@@_test_in_corner_h:
5493   \bool_if:NTF \g_tmpa_bool
5494   {
5495     \int_compare:nNnT \l_@@_local_start_int = 0

```

We keep in memory that we have a rule to draw. \l_@@_local_start_int will be the starting row of the rule that we will have to draw.

```

5496     { \int_set:Nn \l_@@_local_start_int \l_tmpb_tl }
5497   }
5498   {
5499     \int_compare:nNnT \l_@@_local_start_int > 0
5500     {
5501       \int_set:Nn \l_@@_local_end_int { \l_tmpb_tl - 1 }
5502       \@@_hline_ii:
5503       \int_zero:N \l_@@_local_start_int
5504     }
5505   }
5506 }
5507 \int_compare:nNnT \l_@@_local_start_int > 0
5508 {
5509   \int_set_eq:NN \l_@@_local_end_int \l_@@_end_int
5510   \@@_hline_ii:
5511 }
5512 }

```

```

5513 \cs_new_protected:Npn \@@_test_in_corner_h:
5514 {
5515   \int_compare:nNnTF \l_tmpa_tl = { \int_eval:n { \c@iRow + 1 } }
5516   {
5517     \seq_if_in:NxT
5518       \l_@@_corners_cells_seq
5519       { \int_eval:n { \l_tmpa_tl - 1 } - \l_tmpb_tl }
5520     { \bool_set_false:N \g_tmpa_bool }
5521   }
5522   {
5523     \seq_if_in:NxT

```

```

5524     \l_@@_corners_cells_seq
5525     { \l_tmpa_tl - \l_tmpb_tl }
5526     {
5527         \int_compare:nNnTF \l_tmpa_tl = 1
5528         { \bool_set_false:N \g_tmpa_bool }
5529         {
5530             \seq_if_in:NxT
5531             \l_@@_corners_cells_seq
5532             { \int_eval:n { \l_tmpa_tl - 1 } - \l_tmpb_tl }
5533             { \bool_set_false:N \g_tmpa_bool }
5534         }
5535     }
5536 }
5537 }

5538 \cs_new_protected:Npn \@@_hline_ii:
5539 {
5540     % \bool_set_false:N \l_@@_dotted_bool
5541     \keys_set:nV { NiceMatrix / RulesBis } \l_@@_other_keys_tl
5542     \bool_if:NTF \l_@@_dotted_bool
5543     \@@_hline_iv:
5544     {
5545         \tl_if_empty:NTF \l_@@_tikz_rule_tl
5546         \@@_hline_iii:
5547         \@@_hline_v:
5548     }
5549 }

```

First the case of a standard rule (without the keys dotted and tikz).

```

5550 \cs_new_protected:Npn \@@_hline_iii:
5551 {
5552     \pgfpicture
5553     \pgfrememberpicturepositiononpagetrue
5554     \pgf@relevantforpicturesizefalse
5555     \@@_qpoint:n { col - \int_use:N \l_@@_local_start_int }
5556     \dim_set_eq:NN \l_tmpa_dim \pgf@x
5557     \@@_qpoint:n { row - \int_use:N \l_@@_position_int }
5558     \dim_set:Nn \l_tmpb_dim
5559     {
5560         \pgf@y
5561         - 0.5 \l_@@_rule_width_dim
5562         +
5563         ( \arrayrulewidth * \l_@@_multiplicity_int
5564           + \doublerulesep * ( \l_@@_multiplicity_int - 1 ) ) / 2
5565     }
5566     \@@_qpoint:n { col - \int_eval:n { \l_@@_local_end_int + 1 } }
5567     \dim_set_eq:NN \l_@@_tmpc_dim \pgf@x
5568     \bool_lazy_all:nT
5569     {
5570         { \int_compare_p:nNn \l_@@_multiplicity_int > 1 }
5571         { \cs_if_exist_p:N \CT@drsc@ }
5572         { ! \tl_if_blank_p:V \CT@drsc@ }
5573     }
5574     {
5575         \group_begin:
5576         \CT@drsc@
5577         \dim_set:Nn \l_@@_tmpd_dim
5578         {
5579             \l_tmpb_dim - ( \doublerulesep + \arrayrulewidth )
5580             * ( \l_@@_multiplicity_int - 1 )
5581         }
5582         \pgfpathrectanglecorners

```

```

5583         { \pgfpoint \l_tmpa_dim \l_tmpb_dim }
5584         { \pgfpoint \l_@@_tmpc_dim \l_@@_tmpd_dim }
5585         \pgfusepathqfill
5586         \group_end:
5587     }
5588     \pgfpathmoveto { \pgfpoint \l_tmpa_dim \l_tmpb_dim }
5589     \pgfpathlineto { \pgfpoint \l_@@_tmpc_dim \l_tmpb_dim }
5590     \prg_replicate:nn { \l_@@_multiplicity_int - 1 }
5591     {
5592         \dim_sub:Nn \l_tmpb_dim \arrayrulewidth
5593         \dim_sub:Nn \l_tmpb_dim \doublerulesep
5594         \pgfpathmoveto { \pgfpoint \l_tmpa_dim \l_tmpb_dim }
5595         \pgfpathlineto { \pgfpoint \l_@@_tmpc_dim \l_tmpb_dim }
5596     }
5597     \CT@arc@
5598     \pgfsetlinewidth { 1.1 \arrayrulewidth }
5599     \pgfsetrectcap
5600     \pgfusepathqstroke
5601     \endpgfpicture
5602 }

```

The following code is for the case of a dotted rule (with our system of rounded dots). The aim is that, by standard the dotted line fits between square brackets (`\hline` doesn't).

```
\begin{bNiceMatrix}
```

```
1 & 2 & 3 & 4 \\
```

```
\hline
```

```
1 & 2 & 3 & 4 \\
```

```
\hdottedline
```

```
1 & 2 & 3 & 4
```

```
\end{bNiceMatrix}
```

$$\begin{bmatrix} 1 & 2 & 3 & 4 \\ 1 & 2 & 3 & 4 \\ 1 & 2 & 3 & 4 \end{bmatrix}$$

But, if the user uses `margin`, the dotted line extends to have the same width as a `\hline`.

```
\begin{bNiceMatrix}[margin]
```

```
1 & 2 & 3 & 4 \\
```

```
\hline
```

```
1 & 2 & 3 & 4 \\
```

```
\hdottedline
```

```
1 & 2 & 3 & 4
```

```
\end{bNiceMatrix}
```

$$\begin{bmatrix} 1 & 2 & 3 & 4 \\ 1 & 2 & 3 & 4 \\ \dots & \dots & \dots & \dots \\ 1 & 2 & 3 & 4 \end{bmatrix}$$

```
5603 \cs_new_protected:Npn \l_@@_hline_iv:
```

```
5604 {
```

```
5605     \pgfpicture
```

```
5606     \pgfrememberpicturepositiononpagetrue
```

```
5607     \pgf@relevantforpicturesizefalse
```

```
5608     \l_@@_qpoint:n { row - \int_use:N \l_@@_position_int }
```

```
5609     \dim_set:Nn \l_@@_y_initial_dim { \pgf@y - 0.5 \l_@@_rule_width_dim }
```

```
5610     \dim_set_eq:NN \l_@@_y_final_dim \l_@@_y_initial_dim
```

```
5611     \l_@@_qpoint:n { col - \int_use:N \l_@@_local_start_int }
```

```
5612     \dim_set_eq:NN \l_@@_x_initial_dim \pgf@x
```

```
5613     \int_compare:nNnT \l_@@_local_start_int = 1
```

```
5614     {
```

```
5615         \dim_sub:Nn \l_@@_x_initial_dim \l_@@_left_margin_dim
```

```
5616         \bool_if:NT \g_@@_NiceArray_bool
```

```
5617         { \dim_sub:Nn \l_@@_x_initial_dim \arraycolsep }
```

For reasons purely aesthetic, we do an adjustment in the case of a rounded bracket. The correction by `0.5 \l_@@_xdots_inter_dim` is *ad hoc* for a better result.

```
5618     \tl_if_eq:NnF \g_@@_left_delim_tl (
```

```
5619         { \dim_add:Nn \l_@@_x_initial_dim { 0.5 \l_@@_xdots_inter_dim } }
```

```
5620     )
```

```
5621     \l_@@_qpoint:n { col - \int_eval:n { \l_@@_local_end_int + 1 } }
```

```
5622     \dim_set_eq:NN \l_@@_x_final_dim \pgf@x
```

```
5623     \int_compare:nNnT \l_@@_local_end_int = \c@jCol
```

```

5624 {
5625   \dim_add:Nn \l_@@_x_final_dim \l_@@_right_margin_dim
5626   \bool_if:NT \g_@@_NiceArray_bool
5627   { \dim_add:Nn \l_@@_x_final_dim \arraycolsep }
5628   \tl_if_eq:NnF \g_@@_right_delim_tl )
5629   { \dim_gsub:Nn \l_@@_x_final_dim { 0.5 \l_@@_xdots_inter_dim } }
5630 }
5631 \CT@arc@
5632 \@@_draw_line:
5633 \endpgfpicture
5634 }

```

The following code is for the case when the user uses the key `tikz` (in the definition of a customized rule by using the key `custom-line`).

```

5635 \cs_new_protected:Npn \@@_hline_v:
5636 {
5637   \begin { tikzpicture }
5638   \pgfrememberpicturepositiononpagetrue
5639   \pgf@relevantforpicturesizefalse
5640   \@@_qpoint:n { col - \int_use:N \l_@@_local_start_int }
5641   \dim_set_eq:NN \l_tmpa_dim \pgf@x
5642   \@@_qpoint:n { row - \int_use:N \l_@@_position_int }
5643   \dim_set:Nn \l_tmpb_dim { \pgf@y - 0.5 \l_@@_rule_width_dim }
5644   \@@_qpoint:n { col - \int_eval:n { \l_@@_local_end_int + 1 } }
5645   \dim_set_eq:NN \l_@@_tmpc_dim \pgf@x
5646   \exp_args:NV \tikzset \l_@@_tikz_rule_tl
5647   \use:x { \exp_not:N \draw [ \l_@@_tikz_rule_tl ] }
5648   ( \l_tmpa_dim , \l_tmpb_dim ) --
5649   ( \l_@@_tmpc_dim , \l_tmpb_dim ) ;
5650   \end { tikzpicture }
5651 }

```

The command `\@@_draw_hlines:` draws all the horizontal rules excepted in the blocks (even the virtual blocks determined by commands such as `\Cdots` and in the corners (if the key `corners` is used)).

```

5652 \cs_new_protected:Npn \@@_draw_hlines:
5653 {
5654   \int_step_inline:nnn
5655   {
5656     \bool_if:nTF { \g_@@_NiceArray_bool && ! \l_@@_except_borders_bool }
5657     1 2
5658   }
5659   {
5660     \bool_if:nTF { \g_@@_NiceArray_bool && ! \l_@@_except_borders_bool }
5661     { \int_eval:n { \c@iRow + 1 } }
5662     \c@iRow
5663   }
5664   {
5665     \tl_if_eq:NnF \l_@@_hlines_clist { all }
5666     { \clist_if_in:NnT \l_@@_hlines_clist { ##1 } }
5667     { \@@_hline:n { position = ##1 , total-width = \arrayrulewidth } }
5668   }
5669 }

```

The command `\@@_Hline:` will be linked to `\Hline` in the environments of `nicematrix`.

```

5670 \cs_set:Npn \@@_Hline: { \noalign \bgroup \@@_Hline_i:n { 1 } }

```

The argument of the command `\@@_Hline_i:n` is the number of successive `\Hline` found.

```

5671 \cs_set:Npn \@@_Hline_i:n #1
5672 {
5673   \peek_remove_spaces:n
5674   {

```

```

5675     \peek_meaning:NTF \Hline
5676     { \@@_Hline_ii:nn { #1 + 1 } }
5677     { \@@_Hline_iii:n { #1 } }
5678   }
5679 }
5680 \cs_set:Npn \@@_Hline_ii:nn #1 #2 { \@@_Hline_i:n { #1 } }
5681 \cs_set:Npn \@@_Hline_iii:n #1
5682 {
5683   \peek_meaning:NTF [
5684     { \@@_Hline_iv:nw { #1 } }
5685     { \@@_Hline_iv:nw { #1 } [ ] }
5686   ]
5687 \cs_set:Npn \@@_Hline_iv:nw #1 [ #2 ]
5688 {
5689   \@@_compute_rule_width:n { multiplicity = #1 , #2 }
5690   \skip_vertical:n { \l_@@_rule_width_dim }
5691   \tl_gput_right:Nx \g_@@_pre_code_after_tl
5692   {
5693     \@@_hline:n
5694     {
5695       multiplicity = #1 ,
5696       position = \int_eval:n { \c@iRow + 1 } ,
5697       total-width = \dim_use:N \l_@@_rule_width_dim ,
5698       #2
5699     }
5700   }
5701   \egroup
5702 }

```

Customized rules defined by the final user

The final user can define a customized rule by using the key `custom-line` in `\NiceMatrixOptions`. That key takes in as value a list of `key=value` pairs.

Among the keys available in that list, there is the key `letter` to specify a letter that the final user will use in the preamble of the array. All the letters defined by this way by the final user for such customized rules are added in the set of keys `{NiceMatrix / ColumnTypes}`. That set of keys is used to store the characteristics of those types of rules for convenience: the keys of that set of keys won't never be used as keys by the final user (he will use, instead, letters in the preamble of its array).

```

5703 \keys_define:nn { NiceMatrix / ColumnTypes } { }

```

The following command will create the customized rule (it is executed when the final user uses the key `custom-line`, for example in `\NiceMatrixOptions`).

```

5704 \cs_new_protected:Npn \@@_custom_line:n #1
5705 {
5706   \str_clear_new:N \l_@@_command_str
5707   \str_clear_new:N \l_@@_ccommand_str
5708   \str_clear_new:N \l_@@_letter_str
5709   \keys_set_known:nnN { NiceMatrix / custom-line } { #1 } \l_@@_other_keys_tl

```

If the final user only wants to draw horizontal rules, he does not need to specify a letter (for the vertical rules in the preamble of the array). On the other hand, if he only wants to draw vertical rules, he does not need to define a command (which is the tool to draw horizontal rules in the array). Of course, a definition of custom lines with no letter and no command would be point-less.

```

5710   \bool_lazy_all:nTF
5711   {
5712     { \str_if_empty_p:N \l_@@_letter_str }
5713     { \str_if_empty_p:N \l_@@_command_str }
5714     { \str_if_empty_p:N \l_@@_ccommand_str }
5715   }
5716   { \@@_error:n { No-letter~and~no-command } }

```

```

5717     { \exp_args:NV \@@_custom_line_i:n \l_@@_other_keys_tl }
5718   }
5719 \keys_define:nn { NiceMatrix / custom-line }
5720 {
5721   % here, we will use change in the future to use .str_set:N
5722   letter .code:n = \str_set:Nn \l_@@_letter_str { #1 } ,
5723   letter .value_required:n = true ,
5724   command .code:n = \str_set:Nn \l_@@_command_str { #1 } ,
5725   command .value_required:n = true ,
5726   ccommand .code:n = \str_set:Nn \l_@@_ccommand_str { #1 } ,
5727   ccommand .value_required:n = true ,
5728 }

```

```

5729 \cs_new_protected:Npn \@@_custom_line_i:n #1
5730 {

```

The following flags will be raised when the keys `tikz`, `dotted` and `color` are used (in the `custom-line`).

```

5731   \bool_set_false:N \l_@@_tikz_rule_bool
5732   \bool_set_false:N \l_@@_dotted_rule_bool
5733   \bool_set_false:N \l_@@_color_bool
5734   \keys_set:nn { NiceMatrix / custom-line-bis } { #1 }
5735   \bool_if:NT \l_@@_tikz_rule_bool
5736   {

```

We can't use `\c_@@_tikz_loaded_bool` to test whether `tikz` is loaded because `\NiceMatrixOptions` may be used in the preamble of the document.

```

5737     \cs_if_exist:NF \tikzpicture
5738     { \@@_error:n { tikz~in~custom-line~without~tikz } }
5739     \bool_if:NT \l_@@_color_bool
5740     { \@@_error:n { color~in~custom-line~with~tikz } }
5741   }
5742   \bool_if:nT
5743   {
5744     \int_compare_p:nNn \l_@@_multiplicity_int > 1
5745     && \l_@@_dotted_rule_bool
5746   }
5747   { \@@_error:n { key~multiplicity~with~dotted } }
5748   \str_if_empty:NF \l_@@_letter_str
5749   {
5750     \int_compare:nTF { \str_count:N \l_@@_letter_str != 1 }
5751     { \@@_error:n { Several~letters } }
5752     {
5753       \exp_args:NnV \tl_if_in:NnTF
5754       \c_@@_forbidden_letters_str \l_@@_letter_str
5755       { \@@_error:n { Forbidden~letter } }
5756     }

```

The final user can, locally, redefine a letter of column type. That's compatible with the use of `\keys_define:nn`: the definition is local and may overwrite a previous definition.

```

5757     \keys_define:nx { NiceMatrix / ColumnTypes }
5758     {
5759       \l_@@_letter_str .code:n =
5760       { \@@_v_custom_line:n { \exp_not:n { #1 } } }
5761     }
5762   }
5763 }
5764 }
5765 \str_if_empty:NF \l_@@_command_str { \@@_h_custom_line:n { #1 } }
5766 \str_if_empty:NF \l_@@_ccommand_str { \@@_c_custom_line:n { #1 } }
5767 }
5768 \str_const:Nn \c_@@_forbidden_letters_str { lcrpmbVX|()!@<> }

```


The previous command `\@@_custom_line_i:n` uses the following set of keys. However, the whole definition of the customized lines (as provided by the final user as argument of `custom-line`) will also be used further with other sets of keys (for instance `{NiceMatrix/Rules}`). That's why the following set of keys has some keys which are no-op.

```

5769 \keys_define:nn { NiceMatrix / custom-line-bis }
5770 {
5771     multiplicity .int_set:N = \l_@@_multiplicity_int ,
5772     multiplicity .initial:n = 1 ,
5773     multiplicity .value_required:n = true ,
5774     color .code:n = \bool_set_true:N \l_@@_color_bool ,
5775     color .value_required:n = true ,
5776     tikz .code:n = \bool_set_true:N \l_@@_tikz_rule_bool ,
5777     tikz .value_required:n = true ,
5778     dotted .code:n = \bool_set_true:N \l_@@_dotted_rule_bool ,
5779     dotted .value_forbidden:n = true ,
5780     total-width .code:n = { } ,
5781     total-width .value_required:n = true ,
5782     width .code:n = { } ,
5783     width .value_required:n = true ,
5784     sep-color .code:n = { } ,
5785     sep-color .value_required:n = true ,
5786     unknown .code:n = \@@_error:n { Unknown~key~for~custom-line }
5787 }

```

The following keys will indicate whether the keys `dotted`, `tikz` and `color` are used in the use of a `custom-line`.

```

5788 \bool_new:N \l_@@_dotted_rule_bool
5789 \bool_new:N \l_@@_tikz_rule_bool
5790 \bool_new:N \l_@@_color_bool

```

The following keys are used to determine the total width of the line (including the spaces on both sides of the line). The key `width` is deprecated and has been replaced by the key `total-width`.

```

5791 \keys_define:nn { NiceMatrix / custom-line-width }
5792 {
5793     multiplicity .int_set:N = \l_@@_multiplicity_int ,
5794     multiplicity .initial:n = 1 ,
5795     multiplicity .value_required:n = true ,
5796     tikz .code:n = \bool_set_true:N \l_@@_tikz_rule_bool ,
5797     total-width .code:n = \dim_set:Nn \l_@@_rule_width_dim { #1 }
5798     \bool_set_true:N \l_@@_total_width_bool ,
5799     total-width .value_required:n = true ,
5800     width .meta:n = { total-width = #1 } ,
5801     dotted .code:n = \bool_set_true:N \l_@@_dotted_rule_bool ,
5802 }

```

The following command will create the command that the final user will use in its array to draw an horizontal rule (hence the ‘h’ in the name) with the full width of the array. `#1` is the whole set of keys to pass to the command `\@@_hline:n` (which is in the internal `\CodeAfter`).

```

5803 \cs_new_protected:Npn \@@_h_custom_line:n #1
5804 {

```

We use `\cs_set:cpn` and not `\cs_new:cpn` because we want a local definition. Moreover, the command must *not* be protected since it begins with `\noalign`.

```

5805     \cs_set:cpn { nicematrix - \l_@@_command_str }
5806     {
5807         \noalign
5808         {
5809             \@@_compute_rule_width:n { #1 }
5810             \skip_vertical:n { \l_@@_rule_width_dim }
5811             \tl_gput_right:Nx \g_@@_pre_code_after_tl
5812             {
5813                 \@@_hline:n

```

```

5814         {
5815             #1 ,
5816             position = \int_eval:n { \c@iRow + 1 } ,
5817             total-width = \dim_use:N \l_@@_rule_width_dim
5818         }
5819     }
5820 }
5821 }
5822 \seq_put_left:NV \l_@@_custom_line_commands_seq \l_@@_command_str
5823 }
5824 \cs_generate_variant:Nn \@@_h_custom_line:nn { n V }

```

The following command will create the command that the final user will use in its array to draw an horizontal rule on only some of the columns of the array (hence the letter c as in `\cline`). #1 is the whole set of keys to pass to the command `\@@_hline:n` (which is in the internal `\CodeAfter`).

```

5825 \cs_new_protected:Npn \@@_c_custom_line:n #1
5826 {

```

Here, we need an expandable command since it begins with an `\noalign`.

```

5827     \exp_args:Nc \NewExpandableDocumentCommand
5828     { nicematrix - \l_@@_ccommand_str }
5829     { 0 { } m }
5830     {
5831         \noalign
5832         {
5833             \@@_compute_rule_width:n { #1 , ##1 }
5834             \skip_vertical:n { \l_@@_rule_width_dim }
5835             \clist_map_inline:nn
5836             { ##2 }
5837             { \@@_c_custom_line_i:nn { #1 , ##1 } { ####1 } }
5838         }
5839     }
5840     \seq_put_left:NV \l_@@_custom_line_commands_seq \l_@@_ccommand_str
5841 }

```

The first argument is the list of key-value pairs characteristic of the line. The second argument is the specification of columns for the `\cline` with the syntax *a-b*.

```

5842 \cs_new_protected:Npn \@@_c_custom_line_i:nn #1 #2
5843 {
5844     \str_if_in:nnTF { #2 } { - }
5845     { \@@_cut_on_hyphen:w #2 \q_stop }
5846     { \@@_cut_on_hyphen:w #2 - #2 \q_stop }
5847     \tl_gput_right:Nx \g_@@_pre_code_after_tl
5848     {
5849         \@@_hline:n
5850         {
5851             #1 ,
5852             start = \l_tmpa_tl ,
5853             end = \l_tmpb_tl ,
5854             position = \int_eval:n { \c@iRow + 1 } ,
5855             total-width = \dim_use:N \l_@@_rule_width_dim
5856         }
5857     }
5858 }
5859 \cs_generate_variant:Nn \@@_c_custom_line:nn { n V }
5860 \cs_new_protected:Npn \@@_compute_rule_width:n #1
5861 {
5862     \bool_set_false:N \l_@@_tikz_rule_bool
5863     \bool_set_false:N \l_@@_total_width_bool
5864     \bool_set_false:N \l_@@_dotted_rule_bool
5865     \keys_set_known:nn { NiceMatrix / custom-line-width } { #1 }
5866     \bool_if:NF \l_@@_total_width_bool

```

```

5867 {
5868   \bool_if:NTF \l_@@_dotted_rule_bool
5869   { \dim_set:Nn \l_@@_rule_width_dim { 2 \l_@@_xdots_radius_dim } }
5870   {
5871     \bool_if:NF \l_@@_tikz_rule_bool
5872     {
5873       \dim_set:Nn \l_@@_rule_width_dim
5874       {
5875         \arrayrulewidth * \l_@@_multiplicity_int
5876         + \doublerulesep * ( \l_@@_multiplicity_int - 1 )
5877       }
5878     }
5879   }
5880 }
5881 }

```

```

5882 \cs_new_protected:Npn \@@_v_custom_line:n #1
5883 {
5884   \@@_compute_rule_width:n { #1 }

```

In the following line, the `\dim_use:N` is mandatory since we do an expansion.

```

5885 \tl_gput_right:Nx \g_@@_preamble_tl
5886 { \exp_not:N ! { \skip_horizontal:n { \dim_use:N \l_@@_rule_width_dim } } }
5887 \tl_gput_right:Nx \g_@@_pre_code_after_tl
5888 {
5889   \@@_vline:n
5890   {
5891     #1 ,
5892     position = \int_eval:n { \c@jCol + 1 } ,
5893     total-width = \dim_use:N \l_@@_rule_width_dim
5894   }
5895 }
5896 }
5897 \@@_custom_line:n
5898 { letter = : , command = hdottedline , ccommand = cdottedline, dotted }

```

The key hvlines

The following command tests whether the current position in the array (given by `\l_tmpa_tl` for the row and `\l_tmpb_tl` for the column) would provide an horizontal rule towards the right in the block delimited by the four arguments #1, #2, #3 and #4. If this rule would be in the block (it must not be drawn), the boolean `\l_tmpa_bool` is set to false.

```

5899 \cs_new_protected:Npn \@@_test_hline_in_block:nnnnn #1 #2 #3 #4 #5
5900 {
5901   \bool_lazy_all:nT
5902   {
5903     { \int_compare_p:nNn \l_tmpa_tl > { #1 } }
5904     { \int_compare_p:nNn \l_tmpa_tl < { #3 + 1 } }
5905     { \int_compare_p:nNn \l_tmpb_tl > { #2 - 1 } }
5906     { \int_compare_p:nNn \l_tmpb_tl < { #4 + 1 } }
5907   }
5908   { \bool_gset_false:N \g_tmpa_bool }
5909 }

```

The same for vertical rules.

```

5910 \cs_new_protected:Npn \@@_test_vline_in_block:nnnnn #1 #2 #3 #4 #5
5911 {
5912   \bool_lazy_all:nT
5913   {
5914     { \int_compare_p:nNn \l_tmpa_tl > { #1 - 1 } }
5915     { \int_compare_p:nNn \l_tmpa_tl < { #3 + 1 } }
5916     { \int_compare_p:nNn \l_tmpb_tl > { #2 } }
5917     { \int_compare_p:nNn \l_tmpb_tl < { #4 + 1 } }
5918   }

```

```

5919     { \bool_gset_false:N \g_tmpa_bool }
5920   }
5921 \cs_new_protected:Npn \@@_test_hline_in_stroken_block:nnnn #1 #2 #3 #4
5922 {
5923   \bool_lazy_all:nT
5924   {
5925     {
5926       ( \int_compare_p:nNn \l_tmpa_tl = { #1 } )
5927       || ( \int_compare_p:nNn \l_tmpa_tl = { #3 + 1 } )
5928     }
5929     { \int_compare_p:nNn \l_tmpb_tl > { #2 - 1 } }
5930     { \int_compare_p:nNn \l_tmpb_tl < { #4 + 1 } }
5931   }
5932   { \bool_gset_false:N \g_tmpa_bool }
5933 }
5934 \cs_new_protected:Npn \@@_test_vline_in_stroken_block:nnnn #1 #2 #3 #4
5935 {
5936   \bool_lazy_all:nT
5937   {
5938     { \int_compare_p:nNn \l_tmpa_tl > { #1 - 1 } }
5939     { \int_compare_p:nNn \l_tmpa_tl < { #3 + 1 } }
5940     {
5941       ( \int_compare_p:nNn \l_tmpb_tl = { #2 } )
5942       || ( \int_compare_p:nNn \l_tmpb_tl = { #4 + 1 } )
5943     }
5944   }
5945   { \bool_gset_false:N \g_tmpa_bool }
5946 }

```

The key corners

When the key `corners` is raised, the rules are not drawn in the corners. Of course, we have to compute the corners before we begin to draw the rules.

```

5947 \cs_new_protected:Npn \@@_compute_corners:
5948 {

```

The sequence `\l_@@_corners_cells_seq` will be the sequence of all the empty cells (and not in a block) considered in the corners of the array.

```

5949   \seq_clear_new:N \l_@@_corners_cells_seq
5950   \clist_map_inline:Nn \l_@@_corners_clist
5951   {
5952     \str_case:nnF { ##1 }
5953     {
5954       { NW }
5955       { \@@_compute_a_corner:nnnnnn 1 1 1 1 \c@iRow \c@jCol }
5956       { NE }
5957       { \@@_compute_a_corner:nnnnnn 1 \c@jCol 1 { -1 } \c@iRow 1 }
5958       { SW }
5959       { \@@_compute_a_corner:nnnnnn \c@iRow 1 { -1 } 1 1 \c@jCol }
5960       { SE }
5961       { \@@_compute_a_corner:nnnnnn \c@iRow \c@jCol { -1 } { -1 } 1 1 }
5962     }
5963     { \@@_error:nn { bad~corner } { ##1 } }
5964   }

```

Even if the user has used the key `corners` the list of cells in the corners may be empty.

```

5965   \seq_if_empty:NF \l_@@_corners_cells_seq
5966   {

```

You write on the `aux` file the list of the cells which are in the (empty) corners because you need that information in the `\CodeBefore` since the commands which color the `rows`, `columns` and `cells` must not color the cells in the corners.

```

5967 \tl_gput_right:Nx \g_@@_aux_tl
5968 {
5969   \seq_set_from_clist:Nn \exp_not:N \l_@@_corners_cells_seq
5970   { \seq_use:Nnnn \l_@@_corners_cells_seq , , , }
5971 }
5972 }
5973 }

```

“Computing a corner” is determining all the empty cells (which are not in a block) that belong to that corner. These cells will be added to the sequence `\l_@@_corners_cells_seq`.

The six arguments of `\@@_compute_a_corner:nnnnnn` are as follow:

- #1 and #2 are the number of row and column of the cell which is actually in the corner;
- #3 and #4 are the steps in rows and the step in columns when moving from the corner;
- #5 is the number of the final row when scanning the rows from the corner;
- #6 is the number of the final column when scanning the columns from the corner.

```

5974 \cs_new_protected:Npn \@@_compute_a_corner:nnnnnn #1 #2 #3 #4 #5 #6
5975 {

```

For the explanations and the name of the variables, we consider that we are computing the left-upper corner.

First, we try to determine which is the last empty cell (and not in a block: we won’t add that precision any longer) in the column of number 1. The flag `\l_tmpa_bool` will be raised when a non-empty cell is found.

```

5976 \bool_set_false:N \l_tmpa_bool
5977 \int_zero_new:N \l_@@_last_empty_row_int
5978 \int_set:Nn \l_@@_last_empty_row_int { #1 }
5979 \int_step_inline:nnnn { #1 } { #3 } { #5 }
5980 {
5981   \@@_test_if_cell_in_a_block:nn { ##1 } { \int_eval:n { #2 } }
5982   \bool_lazy_or:nnTF
5983   {
5984     \cs_if_exist_p:c
5985     { pgf @ sh @ ns @ \@@_env: - ##1 - \int_eval:n { #2 } }
5986   }
5987   \l_tmpb_bool
5988   { \bool_set_true:N \l_tmpa_bool }
5989   {
5990     \bool_if:NF \l_tmpa_bool
5991     { \int_set:Nn \l_@@_last_empty_row_int { ##1 } }
5992   }
5993 }

```

Now, you determine the last empty cell in the row of number 1.

```

5994 \bool_set_false:N \l_tmpa_bool
5995 \int_zero_new:N \l_@@_last_empty_column_int
5996 \int_set:Nn \l_@@_last_empty_column_int { #2 }
5997 \int_step_inline:nnnn { #2 } { #4 } { #6 }
5998 {
5999   \@@_test_if_cell_in_a_block:nn { \int_eval:n { #1 } } { ##1 }
6000   \bool_lazy_or:nnTF
6001   \l_tmpb_bool
6002   {
6003     \cs_if_exist_p:c
6004     { pgf @ sh @ ns @ \@@_env: - \int_eval:n { #1 } - ##1 }
6005   }

```

```

6006     { \bool_set_true:N \l_tmpa_bool }
6007     {
6008         \bool_if:NF \l_tmpa_bool
6009         { \int_set:Nn \l_@@_last_empty_column_int { ##1 } }
6010     }
6011 }

```

Now, we loop over the rows.

```

6012     \int_step_inline:nnnn { #1 } { #3 } \l_@@_last_empty_row_int
6013     {

```

We treat the row number ##1 with another loop.

```

6014         \bool_set_false:N \l_tmpa_bool
6015         \int_step_inline:nnnn { #2 } { #4 } \l_@@_last_empty_column_int
6016         {
6017             \@@_test_if_cell_in_a_block:nn { ##1 } { ####1 }
6018             \bool_lazy_or:nnTF
6019             \l_tmpb_bool
6020             {
6021                 \cs_if_exist_p:c
6022                 { pgf @ sh @ ns @ \@@_env: - ##1 - ####1 }
6023             }
6024             { \bool_set_true:N \l_tmpa_bool }
6025             {
6026                 \bool_if:NF \l_tmpa_bool
6027                 {
6028                     \int_set:Nn \l_@@_last_empty_column_int { ####1 }
6029                     \seq_put_right:Nn
6030                     \l_@@_corners_cells_seq
6031                     { ##1 - ####1 }
6032                 }
6033             }
6034         }
6035     }
6036 }

```

The following macro tests whether a cell is in (at least) one of the blocks of the array (or in a cell with a `\diagbox`).

The flag `\l_tmpb_bool` will be raised if the cell #1-#2 is in a block (or in a cell with a `\diagbox`).

```

6037 \cs_new_protected:Npn \@@_test_if_cell_in_a_block:nn #1 #2
6038 {
6039     \int_set:Nn \l_tmpa_int { #1 }
6040     \int_set:Nn \l_tmpb_int { #2 }
6041     \bool_set_false:N \l_tmpb_bool
6042     \seq_map_inline:Nn \g_@@_pos_of_blocks_seq
6043     { \@@_test_if_cell_in_block:nnnnnnn \l_tmpa_int \l_tmpb_int ##1 }
6044 }
6045 \cs_new_protected:Npn \@@_test_if_cell_in_block:nnnnnnn #1 #2 #3 #4 #5 #6 #7
6046 {
6047     \int_compare:nNnT { #3 } < { \int_eval:n { #1 + 1 } }
6048     {
6049         \int_compare:nNnT { #1 } < { \int_eval:n { #5 + 1 } }
6050         {
6051             \int_compare:nNnT { #4 } < { \int_eval:n { #2 + 1 } }
6052             {
6053                 \int_compare:nNnT { #2 } < { \int_eval:n { #6 + 1 } }
6054                 { \bool_set_true:N \l_tmpb_bool }
6055             }
6056         }
6057     }
6058 }

```

The environment {NiceMatrixBlock}

The following flag will be raised when all the columns of the environments of the block must have the same width in “auto” mode.

```
6059 \bool_new:N \l_@@_block_auto_columns_width_bool
```

Up to now, there is only one option available for the environment {NiceMatrixBlock}.

```
6060 \keys_define:nn { NiceMatrix / NiceMatrixBlock }
6061 {
6062   auto-columns-width .code:n =
6063   {
6064     \bool_set_true:N \l_@@_block_auto_columns_width_bool
6065     \dim_gzero_new:N \g_@@_max_cell_width_dim
6066     \bool_set_true:N \l_@@_auto_columns_width_bool
6067   }
6068 }

6069 \NewDocumentEnvironment { NiceMatrixBlock } { ! 0 { } }
6070 {
6071   \int_gincr:N \g_@@_NiceMatrixBlock_int
6072   \dim_zero:N \l_@@_columns_width_dim
6073   \keys_set:nn { NiceMatrix / NiceMatrixBlock } { #1 }
6074   \bool_if:NT \l_@@_block_auto_columns_width_bool
6075   {
6076     \cs_if_exist:cT { @@_max_cell_width_ \int_use:N \g_@@_NiceMatrixBlock_int }
6077     {
6078       \exp_args:Nnc \dim_set:Nn \l_@@_columns_width_dim
6079       { @@_max_cell_width_ \int_use:N \g_@@_NiceMatrixBlock_int }
6080     }
6081   }
6082 }
```

At the end of the environment {NiceMatrixBlock}, we write in the main aux file instructions for the column width of all the environments of the block (that’s why we have stored the number of the first environment of the block in the counter \l_@@_first_env_block_int).

```
6083 {
6084   \bool_if:NT \l_@@_block_auto_columns_width_bool
6085   {
6086     \iow_shipout:Nn \@mainaux \ExplSyntaxOn
6087     \iow_shipout:Nx \@mainaux
6088     {
6089       \cs_gset:cpn
6090       { @@_max _ cell _ width _ \int_use:N \g_@@_NiceMatrixBlock_int }
```

For technical reasons, we have to include the width of a potential rule on the right side of the cells.

```
6091       { \dim_eval:n { \g_@@_max_cell_width_dim + \arrayrulewidth } }
6092     }
6093     \iow_shipout:Nn \@mainaux \ExplSyntaxOff
6094   }
6095 }
```

The extra nodes

First, two variants of the functions \dim_min:nn and \dim_max:nn.

```
6096 \cs_generate_variant:Nn \dim_min:nn { v n }
6097 \cs_generate_variant:Nn \dim_max:nn { v n }
```

The following command is called in \@@_use_arraybox_with_notes_c: just before the construction of the blocks (if the creation of medium nodes is required, medium nodes are also created for the blocks and that construction uses the standard medium nodes).

```

6098 \cs_new_protected:Npn \@@_create_extra_nodes:
6099 {
6100   \bool_if:NTF \l_@@_medium_nodes_bool
6101   {
6102     \bool_if:NTF \l_@@_large_nodes_bool
6103     \@@_create_medium_and_large_nodes:
6104     \@@_create_medium_nodes:
6105   }
6106   { \bool_if:NT \l_@@_large_nodes_bool \@@_create_large_nodes: }
6107 }

```

We have three macros of creation of nodes: `\@@_create_medium_nodes:`, `\@@_create_large_nodes:` and `\@@_create_medium_and_large_nodes:`.

We have to compute the mathematical coordinates of the “medium nodes”. These mathematical coordinates are also used to compute the mathematical coordinates of the “large nodes”. That’s why we write a command `\@@_computations_for_medium_nodes:` to do these computations.

The command `\@@_computations_for_medium_nodes:` must be used in a `{pgfpicture}`.

For each row i , we compute two dimensions `l_@@_row_i_min_dim` and `l_@@_row_i_max_dim`. The dimension `l_@@_row_i_min_dim` is the minimal y -value of all the cells of the row i . The dimension `l_@@_row_i_max_dim` is the maximal y -value of all the cells of the row i .

Similarly, for each column j , we compute two dimensions `l_@@_column_j_min_dim` and `l_@@_column_j_max_dim`. The dimension `l_@@_column_j_min_dim` is the minimal x -value of all the cells of the column j . The dimension `l_@@_column_j_max_dim` is the maximal x -value of all the cells of the column j .

Since these dimensions will be computed as maximum or minimum, we initialize them to `\c_max_dim` or `-\c_max_dim`.

```

6108 \cs_new_protected:Npn \@@_computations_for_medium_nodes:
6109 {
6110   \int_step_variable:nnNn \l_@@_first_row_int \g_@@_row_total_int \@@_i:
6111   {
6112     \dim_zero_new:c { l_@@_row\_@@_i: _min_dim }
6113     \dim_set_eq:cN { l_@@_row\_@@_i: _min_dim } \c_max_dim
6114     \dim_zero_new:c { l_@@_row\_@@_i: _max_dim }
6115     \dim_set:cn { l_@@_row\_@@_i: _max_dim } { - \c_max_dim }
6116   }
6117   \int_step_variable:nnNn \l_@@_first_col_int \g_@@_col_total_int \@@_j:
6118   {
6119     \dim_zero_new:c { l_@@_column\_@@_j: _min_dim }
6120     \dim_set_eq:cN { l_@@_column\_@@_j: _min_dim } \c_max_dim
6121     \dim_zero_new:c { l_@@_column\_@@_j: _max_dim }
6122     \dim_set:cn { l_@@_column\_@@_j: _max_dim } { - \c_max_dim }
6123   }

```

We begin the two nested loops over the rows and the columns of the array.

```

6124   \int_step_variable:nnNn \l_@@_first_row_int \g_@@_row_total_int \@@_i:
6125   {
6126     \int_step_variable:nnNn
6127     \l_@@_first_col_int \g_@@_col_total_int \@@_j:

```

If the cell $(i-j)$ is empty or an implicit cell (that is to say a cell after implicit ampersands `&`) we don’t update the dimensions we want to compute.

```

6128     {
6129       \cs_if_exist:cT
6130       { pgf @ sh @ ns @ \@@_env: - \@@_i: - \@@_j: }

```

We retrieve the coordinates of the anchor south west of the (normal) node of the cell $(i-j)$. They will be stored in `\pgf@x` and `\pgf@y`.

```

6131     {
6132       \pgfpointanchor { \@@_env: - \@@_i: - \@@_j: } { south-west }
6133       \dim_set:cn { l_@@_row\_@@_i: _min_dim }

```



```

6134         { \dim_min:vn { l_@@_row _ @@_i: _min_dim } \pgf@y }
6135     \seq_if_in:NxF \g_@@_multicolumn_cells_seq { @@_i: - @@_j: }
6136     {
6137         \dim_set:cn { l_@@_column _ @@_j: _min_dim}
6138         { \dim_min:vn { l_@@_column _ @@_j: _min_dim } \pgf@x }
6139     }

```

We retrieve the coordinates of the anchor north east of the (normal) node of the cell (i - j). They will be stored in `\pgf@x` and `\pgf@y`.

```

6140     \pgfpointanchor { @@_env: - @@_i: - @@_j: } { north-east }
6141     \dim_set:cn { l_@@_row _ @@_i: _ max_dim }
6142     { \dim_max:vn { l_@@_row _ @@_i: _ max_dim } \pgf@y }
6143     \seq_if_in:NxF \g_@@_multicolumn_cells_seq { @@_i: - @@_j: }
6144     {
6145         \dim_set:cn { l_@@_column _ @@_j: _ max_dim }
6146         { \dim_max:vn { l_@@_column _ @@_j: _ max_dim } \pgf@x }
6147     }
6148 }
6149 }
6150 }

```

Now, we have to deal with empty rows or empty columns since we don't have created nodes in such rows and columns.

```

6151     \int_step_variable:nnNn \l_@@_first_row_int \g_@@_row_total_int @@_i:
6152     {
6153         \dim_compare:nNnT
6154         { \dim_use:c { l_@@_row _ @@_i: _ min _ dim } } = \c_max_dim
6155         {
6156             @@_qpoint:n { row - @@_i: - base }
6157             \dim_set:cn { l_@@_row _ @@_i: _ max _ dim } \pgf@y
6158             \dim_set:cn { l_@@_row _ @@_i: _ min _ dim } \pgf@y
6159         }
6160     }
6161     \int_step_variable:nnNn \l_@@_first_col_int \g_@@_col_total_int @@_j:
6162     {
6163         \dim_compare:nNnT
6164         { \dim_use:c { l_@@_column _ @@_j: _ min _ dim } } = \c_max_dim
6165         {
6166             @@_qpoint:n { col - @@_j: }
6167             \dim_set:cn { l_@@_column _ @@_j: _ max _ dim } \pgf@y
6168             \dim_set:cn { l_@@_column _ @@_j: _ min _ dim } \pgf@y
6169         }
6170     }
6171 }

```

Here is the command `\@@_create_medium_nodes:`. When this command is used, the “medium nodes” are created.

```

6172 \cs_new_protected:Npn \@@_create_medium_nodes:
6173 {
6174     \pgfpicture
6175     \pgfrememberpicturepositiononpagetrue
6176     \pgf@relevantforpicturesizefalse
6177     \@@_computations_for_medium_nodes:

```

Now, we can create the “medium nodes”. We use a command `\@@_create_nodes:` because this command will also be used for the creation of the “large nodes”.

```

6178     \tl_set:Nn \l_@@_suffix_tl { -medium }
6179     \@@_create_nodes:
6180     \endpgfpicture
6181 }

```

The command `\@@_create_large_nodes:` must be used when we want to create only the “large nodes” and not the medium ones⁷⁷. However, the computation of the mathematical coordinates of the “large nodes” needs the computation of the mathematical coordinates of the “medium nodes”. Hence, we use first `\@@_computations_for_medium_nodes:` and then the command `\@@_computations_for_large_nodes:`.

```

6182 \cs_new_protected:Npn \@@_create_large_nodes:
6183 {
6184   \pgfpicture
6185     \pgfrememberpicturepositiononpagetrue
6186     \pgf@relevantforpicturesizefalse
6187     \@@_computations_for_medium_nodes:
6188     \@@_computations_for_large_nodes:
6189     \tl_set:Nn \l_@@_suffix_tl { - large }
6190     \@@_create_nodes:
6191   \endpgfpicture
6192 }

6193 \cs_new_protected:Npn \@@_create_medium_and_large_nodes:
6194 {
6195   \pgfpicture
6196     \pgfrememberpicturepositiononpagetrue
6197     \pgf@relevantforpicturesizefalse
6198     \@@_computations_for_medium_nodes:

```

Now, we can create the “medium nodes”. We use a command `\@@_create_nodes:` because this command will also be used for the creation of the “large nodes”.

```

6199   \tl_set:Nn \l_@@_suffix_tl { - medium }
6200   \@@_create_nodes:
6201   \@@_computations_for_large_nodes:
6202   \tl_set:Nn \l_@@_suffix_tl { - large }
6203   \@@_create_nodes:
6204 \endpgfpicture
6205 }

```

For “large nodes”, the exterior rows and columns don’t interfere. That’s why the loop over the columns will start at 1 and stop at `\c@jCol` (and not `\g_@@_col_total_int`). Idem for the rows.

```

6206 \cs_new_protected:Npn \@@_computations_for_large_nodes:
6207 {
6208   \int_set:Nn \l_@@_first_row_int 1
6209   \int_set:Nn \l_@@_first_col_int 1

```

We have to change the values of all the dimensions `l_@@_row_i_min_dim`, `l_@@_row_i_max_dim`, `l_@@_column_j_min_dim` and `l_@@_column_j_max_dim`.

```

6210   \int_step_variable:nNn { \c@iRow - 1 } \@@_i:
6211   {
6212     \dim_set:cn { l_@@_row _ \@@_i: _ min _ dim }
6213     {
6214       (
6215         \dim_use:c { l_@@_row _ \@@_i: _ min _ dim } +
6216         \dim_use:c { l_@@_row _ \int_eval:n { \@@_i: + 1 } _ max _ dim }
6217       )
6218       / 2
6219     }
6220     \dim_set_eq:cc { l_@@_row _ \int_eval:n { \@@_i: + 1 } _ max _ dim }
6221     { l_@@_row _ \@@_i: _ min _ dim }
6222   }
6223   \int_step_variable:nNn { \c@jCol - 1 } \@@_j:
6224   {
6225     \dim_set:cn { l_@@_column _ \@@_j: _ max _ dim }
6226     {

```

⁷⁷If we want to create both, we have to use `\@@_create_medium_and_large_nodes:`

```

6227      (
6228      \dim_use:c { l_@@_column _ \@@_j: _ max _ dim } +
6229      \dim_use:c
6230      { l_@@_column _ \int_eval:n { \@@_j: + 1 } _ min _ dim }
6231      )
6232      / 2
6233      }
6234      \dim_set_eq:cc { l_@@_column _ \int_eval:n { \@@_j: + 1 } _ min _ dim }
6235      { l_@@_column _ \@@_j: _ max _ dim }
6236      }

```

Here, we have to use `\dim_sub:cn` because of the number 1 in the name.

```

6237      \dim_sub:cn
6238      { l_@@_column _ 1 _ min _ dim }
6239      \l_@@_left_margin_dim
6240      \dim_add:cn
6241      { l_@@_column _ \int_use:N \c@jCol _ max _ dim }
6242      \l_@@_right_margin_dim
6243      }

```

The command `\@@_create_nodes:` is used twice: for the construction of the “medium nodes” and for the construction of the “large nodes”. The nodes are constructed with the value of all the dimensions `l_@@_row_i_min_dim`, `l_@@_row_i_max_dim`, `l_@@_column_j_min_dim` and `l_@@_column_j_max_dim`. Between the construction of the “medium nodes” and the “large nodes”, the values of these dimensions are changed.

The function also uses `\l_@@_suffix_tl` (-medium or -large).

```

6244 \cs_new_protected:Npn \@@_create_nodes:
6245 {
6246   \int_step_variable:nnNn \l_@@_first_row_int \g_@@_row_total_int \@@_i:
6247   {
6248     \int_step_variable:nnNn \l_@@_first_col_int \g_@@_col_total_int \@@_j:
6249     {

```

We draw the rectangular node for the cell (`\@@_i-\@@_j`).

```

6250       \@@_pgf_rect_node:nnnnn
6251       { \@@_env: - \@@_i: - \@@_j: \l_@@_suffix_tl }
6252       { \dim_use:c { l_@@_column _ \@@_j: _ min_dim } }
6253       { \dim_use:c { l_@@_row _ \@@_i: _ min_dim } }
6254       { \dim_use:c { l_@@_column _ \@@_j: _ max_dim } }
6255       { \dim_use:c { l_@@_row _ \@@_i: _ max_dim } }
6256       \str_if_empty:NF \l_@@_name_str
6257       {
6258         \pgfnodealias
6259         { \l_@@_name_str - \@@_i: - \@@_j: \l_@@_suffix_tl }
6260         { \@@_env: - \@@_i: - \@@_j: \l_@@_suffix_tl }
6261       }
6262     }
6263   }

```

Now, we create the nodes for the cells of the `\multicolumn`. We recall that we have stored in `\g_@@_multicolumn_cells_seq` the list of the cells where a `\multicolumn{n}{...}{...}` with $n > 1$ was issued and in `\g_@@_multicolumn_sizes_seq` the correspondent values of n .

```

6264   \seq_mapthread_function:NNN
6265   \g_@@_multicolumn_cells_seq
6266   \g_@@_multicolumn_sizes_seq
6267   \@@_node_for_multicolumn:nn
6268   }

```

```

6269 \cs_new_protected:Npn \@@_extract_coords_values: #1 - #2 \q_stop
6270 {
6271   \cs_set_nopar:Npn \@@_i: { #1 }
6272   \cs_set_nopar:Npn \@@_j: { #2 }
6273 }

```

The command `\@@_node_for_multicolumn:nn` takes two arguments. The first is the position of the cell where the command `\multicolumn{n}{...}{...}` was issued in the format *i-j* and the second is the value of *n* (the length of the “multi-cell”).

```

6274 \cs_new_protected:Npn \@@_node_for_multicolumn:nn #1 #2
6275 {
6276   \@@_extract_coords_values: #1 \q_stop
6277   \@@_pgf_rect_node:nnnnn
6278     { \@@_env: - \@@_i: - \@@_j: \l_@@_suffix_tl }
6279     { \dim_use:c { \l_@@_column _ \@@_j: _ min _ dim } }
6280     { \dim_use:c { \l_@@_row _ \@@_i: _ min _ dim } }
6281     { \dim_use:c { \l_@@_column _ \int_eval:n { \@@_j: +#2-1 } _ max _ dim } }
6282     { \dim_use:c { \l_@@_row _ \@@_i: _ max _ dim } }
6283   \str_if_empty:NF \l_@@_name_str
6284   {
6285     \pgfnodealias
6286       { \l_@@_name_str - \@@_i: - \@@_j: \l_@@_suffix_tl }
6287       { \int_use:N \g_@@_env_int - \@@_i: - \@@_j: \l_@@_suffix_tl }
6288   }
6289 }

```

The blocks

The code deals with the command `\Block`. This command has no direct link with the environment `{NiceMatrixBlock}`.

The options of the command `\Block` will be analyzed first in the cell of the array (and once again when the block will be put in the array). Here is the set of keys for the first pass.

```

6290 \keys_define:nn { NiceMatrix / Block / FirstPass }
6291 {
6292   l .code:n = \str_set:Nn \l_@@_hpos_block_str l ,
6293   l .value_forbidden:n = true ,
6294   r .code:n = \str_set:Nn \l_@@_hpos_block_str r ,
6295   r .value_forbidden:n = true ,
6296   c .code:n = \str_set:Nn \l_@@_hpos_block_str c ,
6297   c .value_forbidden:n = true ,
6298   L .code:n = \str_set:Nn \l_@@_hpos_block_str l ,
6299   L .value_forbidden:n = true ,
6300   R .code:n = \str_set:Nn \l_@@_hpos_block_str r ,
6301   R .value_forbidden:n = true ,
6302   C .code:n = \str_set:Nn \l_@@_hpos_block_str c ,
6303   C .value_forbidden:n = true ,
6304   t .code:n = \str_set:Nn \l_@@_vpos_of_block_tl t ,
6305   t .value_forbidden:n = true ,
6306   b .code:n = \str_set:Nn \l_@@_vpos_of_block_tl b ,
6307   b .value_forbidden:n = true ,
6308   color .tl_set:N = \l_@@_color_tl ,
6309   color .value_required:n = true ,
6310   respect-arraystretch .bool_set:N = \l_@@_respect_arraystretch_bool ,
6311   respect-arraystretch .default:n = true ,
6312 }

```

The following command `\@@_Block:` will be linked to `\Block` in the environments of `nicematrix`. We define it with `\NewExpandableDocumentCommand` because it has an optional argument between `<` and `>`. It's mandatory to use an expandable command.

```

6313 \NewExpandableDocumentCommand \@@_Block: { 0 { } m D < > { } +m }
6314 {

```

If the first mandatory argument of the command (which is the size of the block with the syntax *i-j*) has not been provided by the user, you use 1-1 (that is to say a block of only one cell).

```

6315   \peek_remove_spaces:n

```

```

6316 {
6317   \tl_if_blank:nTF { #2 }
6318   { \@@_Block_i 1-1 \q_stop }
6319   {
6320     \int_compare:nNnTF { \char_value_catcode:n { 45 } } = { 13 }
6321     \@@_Block_i_czech \@@_Block_i
6322     #2 \q_stop
6323   }
6324   { #1 } { #3 } { #4 }
6325 }
6326 }

```

With the following construction, we extract the values of i and j in the first mandatory argument of the command.

```

6327 \cs_new:Npn \@@_Block_i #1-#2 \q_stop { \@@_Block_ii:nnnnn { #1 } { #2 } }

```

With `babel` with the key `czech`, the character `-` (hyphen) is active. That's why we need a special version. Remark that we could not use a preprocessor in the command `\@@_Block:` to do the job because the command `\@@_Block:` is defined with the command `\NewExpandableDocumentCommand`.

```

6328 {
6329   \char_set_catcode_active:N -
6330   \cs_new:Npn \@@_Block_i_czech #1-#2 \q_stop { \@@_Block_ii:nnnnn { #1 } { #2 } }
6331 }

```

Now, the arguments have been extracted: `#1` is i (the number of rows of the block), `#2` is j (the number of columns of the block), `#3` is the list of *key=values* pairs, `#4` are the tokens to put before the math mode and the beginning of the small array of the block and `#5` is the label of the block.

```

6332 \cs_new_protected:Npn \@@_Block_ii:nnnnn #1 #2 #3 #4 #5
6333 {

```

We recall that `#1` and `#2` have been extracted from the first mandatory argument of `\Block` (which is of the syntax $i-j$). However, the user is allowed to omit i or j (or both). We detect that situation by replacing a missing value by 100 (it's a convention: when the block will actually be drawn these values will be detected and interpreted as *maximal possible value* according to the actual size of the array).

```

6334   \bool_lazy_or:nnTF
6335   { \tl_if_blank_p:n { #1 } }
6336   { \str_if_eq_p:nn { #1 } { * } }
6337   { \int_set:Nn \l_tmpa_int { 100 } }
6338   { \int_set:Nn \l_tmpa_int { #1 } }
6339   \bool_lazy_or:nnTF
6340   { \tl_if_blank_p:n { #2 } }
6341   { \str_if_eq_p:nn { #2 } { * } }
6342   { \int_set:Nn \l_tmpb_int { 100 } }
6343   { \int_set:Nn \l_tmpb_int { #2 } }

```

If the block is mono-column.

```

6344   \int_compare:nNnTF \l_tmpb_int = 1
6345   {
6346     \str_if_empty:NTF \l_@@_hpos_cell_str
6347     { \str_set:Nn \l_@@_hpos_block_str c }
6348     { \str_set_eq:NN \l_@@_hpos_block_str \l_@@_hpos_cell_str }
6349   }
6350   { \str_set:Nn \l_@@_hpos_block_str c }

```

The value of `\l_@@_hpos_block_str` may be modified by the keys of the command `\Block` that we will analyze now.

```

6351   \keys_set_known:nn { NiceMatrix / Block / FirstPass } { #3 }

```

```

6352 \tl_set:Nx \l_tmpa_tl
6353 {
6354   { \int_use:N \c@iRow }
6355   { \int_use:N \c@jCol }
6356   { \int_eval:n { \c@iRow + \l_tmpa_int - 1 } }
6357   { \int_eval:n { \c@jCol + \l_tmpb_int - 1 } }
6358 }

```

Now, `\l_tmpa_tl` contains an “object” corresponding to the position of the block with four components, each of them surrounded by curly brackets:

`{imin}-{jmin}-{imax}-{jmax}`.

If the block is mono-column or mono-row, we have a special treatment. That’s why we have two macros: `\@@_Block_iv:nnnnn` and `\@@_Block_v:nnnnn` (the five arguments of those macros are provided by curryfication).

```

6359 \bool_if:nTF
6360 {
6361   (
6362     \int_compare_p:nNn { \l_tmpa_int } = 1
6363     ||
6364     \int_compare_p:nNn { \l_tmpb_int } = 1
6365   )
6366   && ! \tl_if_empty_p:n { #5 }

```

For the blocks mono-column, we will compose right now in a box in order to compute its width and take that width into account for the width of the column. However, if the column is a X column, we should not do that since the width is determined by another way. This should be the same for the p, m and b columns and we should modify that point. However, for the X column, it’s imperative. Otherwise, the process for the determination of the widths of the columns will be wrong.

```

6367   && ! \l_@@_X_column_bool
6368 }
6369 { \exp_args:Nxx \@@_Block_iv:nnnnn }
6370 { \exp_args:Nxx \@@_Block_v:nnnnn }
6371 { \l_tmpa_int } { \l_tmpb_int } { #3 } { #4 } { #5 }
6372 }

```

The following macro is for the case of a `\Block` which is mono-row or mono-column (or both). In that case, the content of the block is composed right now in a box (because we have to take into account the dimensions of that box for the width of the current column or the height and the depth of the current row). However, that box will be put in the array *after the construction of the array* (by using PGF).

```

6373 \cs_new_protected:Npn \@@_Block_iv:nnnnn #1 #2 #3 #4 #5
6374 {
6375   \int_gincr:N \g_@@_block_box_int
6376   \cs_set_protected_nopar:Npn \diagbox ##1 ##2
6377   {
6378     \tl_gput_right:Nx \g_@@_pre_code_after_tl
6379     {
6380       \@@_actually_diagbox:nnnnnn
6381       { \int_use:N \c@iRow }
6382       { \int_use:N \c@jCol }
6383       { \int_eval:n { \c@iRow + #1 - 1 } }
6384       { \int_eval:n { \c@jCol + #2 - 1 } }
6385       { \exp_not:n { ##1 } } { \exp_not:n { ##2 } }
6386     }
6387   }
6388   \box_gclear_new:c
6389   { g_@@_block_box_int \int_use:N \g_@@_block_box_int _ box }
6390   \hbox_gset:cn
6391   { g_@@_block_box_int \int_use:N \g_@@_block_box_int _ box }
6392   {

```

For a mono-column block, if the user has specified a color for the column in the preamble of the array, we want to fix that color in the box we construct. We do that with `\set@color` and not `\color_ensure_current:` (in order to use `\color_ensure_current:` safely, you should load `l3backend` before the `\documentclass` with `\RequirePackage{expl3}`).

```
6393 \tl_if_empty:NTF \l_@@_color_tl
6394 { \int_compare:nNnT { #2 } = 1 \set@color }
6395 { \@@_color:V \l_@@_color_tl }
```

If the block is mono-row, we use `\g_@@_row_style_tl` even if it has yet been used in the beginning of the cell where the command `\Block` has been issued because we want to be able to take into account a potential instruction of color of the font in `\g_@@_row_style_tl`.

```
6396 \int_compare:nNnT { #1 } = 1 \g_@@_row_style_tl
6397 \group_begin:
6398 \bool_if:NF \l_@@_respect_arraystretch_bool
6399 { \cs_set:Npn \arraystretch { 1 } }
6400 \dim_zero:N \extrarowheight
6401 #4
```

If the box is rotated (the key `\rotate` may be in the previous #4), the tabular used for the content of the cell will be constructed with a format `c`. In the other cases, the tabular will be constructed with a format equal to the key of position of the box. In other words: the alignment internal to the tabular is the same as the external alignment of the tabular (that is to say the position of the block in its zone of merged cells).

```
6402 \bool_if:NT \g_@@_rotate_bool { \str_set:Nn \l_@@_hpos_block_str c }
6403 \bool_if:NTF \l_@@_NiceTabular_bool
6404 {
6405   \bool_lazy_all:nTF
6406   {
6407     { \int_compare_p:nNn { #2 } = 1 }
6408     { \dim_compare_p:n { \l_@@_col_width_dim >= \c_zero_dim } }
6409     { ! \g_@@_rotate_bool } % added 2022/09/16
6410   }
6411 }
```

When the block is mono-column in a column with a fixed width (eg `p{3cm}`).

```
6411 {
6412   \begin { minipage } [ \l_@@_vpos_of_block_tl ]
6413   { \l_@@_col_width_dim }
6414   \str_case:Nn \l_@@_hpos_block_str
6415   {
6416     c \centering
6417     r \raggedleft
6418     l \raggedright
6419   }
6420   #5
6421   \end { minipage }
6422 }
6423 {
6424   \use:x
6425   {
6426     \exp_not:N \begin { tabular } [ \l_@@_vpos_of_block_tl ]
6427     { @ { } \l_@@_hpos_block_str @ { } }
6428   }
6429   #5
6430   \end { tabular }
6431 }
6432 }
6433 {
6434   \c_math_toggle_token
6435   \use:x
6436   {
6437     \exp_not:N \begin { array } [ \l_@@_vpos_of_block_tl ]
6438     { @ { } \l_@@_hpos_block_str @ { } }
6439   }
6440   #5
6441 }
```

```

6441         \end { array }
6442         \c_math_toggle_token
6443     }
6444     \group_end:
6445 }
6446 \bool_if:NT \g_@@_rotate_bool
6447 {
6448     \box_grotate:cn
6449     { g_@@_ block _ box _ \int_use:N \g_@@_block_box_int _ box }
6450     { 90 }
6451     \bool_gset_false:N \g_@@_rotate_bool
6452 }

```

If we are in a mono-column block, we take into account the width of that block for the width of the column.

```

6453 \int_compare:nNnT { #2 } = 1
6454 {
6455     \dim_gset:Nn \g_@@_blocks_wd_dim
6456     {
6457         \dim_max:nn
6458         \g_@@_blocks_wd_dim
6459         {
6460             \box_wd:c
6461             { g_@@_ block _ box _ \int_use:N \g_@@_block_box_int _ box }
6462         }
6463     }
6464 }

```

If we are in a mono-row block, we take into account the height and the depth of that block for the height and the depth of the row.

```

6465 \int_compare:nNnT { #1 } = 1
6466 {
6467     \dim_gset:Nn \g_@@_blocks_ht_dim
6468     {
6469         \dim_max:nn
6470         \g_@@_blocks_ht_dim
6471         {
6472             \box_ht:c
6473             { g_@@_ block _ box _ \int_use:N \g_@@_block_box_int _ box }
6474         }
6475     }
6476     \dim_gset:Nn \g_@@_blocks_dp_dim
6477     {
6478         \dim_max:nn
6479         \g_@@_blocks_dp_dim
6480         {
6481             \box_dp:c
6482             { g_@@_ block _ box _ \int_use:N \g_@@_block_box_int _ box }
6483         }
6484     }
6485 }
6486 \seq_gput_right:Nx \g_@@_blocks_seq
6487 {
6488     \l_tmpa_tl

```

In the list of options #3, maybe there is a key for the horizontal alignment (l, r or c). In that case, that key has been read and stored in `\l_@@_hpos_block_str`. However, maybe there were no key of the horizontal alignment and that's why we put a key corresponding to the value of `\l_@@_hpos_block_str`, which is fixed by the type of current column.

```

6489 { \exp_not:n { #3 } , \l_@@_hpos_block_str }
6490 {
6491     \box_use_drop:c
6492     { g_@@_ block _ box _ \int_use:N \g_@@_block_box_int _ box }
6493 }

```



```

6494     }
6495 }

```

The following macro is for the standard case, where the block is not mono-row and not mono-column. In that case, the content of the block is *not* composed right now in a box. The composition in a box will be done further, just after the construction of the array.

```

6496 \cs_new_protected:Npn \l_@@_Block_v:nnnnn #1 #2 #3 #4 #5
6497 {
6498   \seq_gput_right:Nx \l_@@_blocks_seq
6499   {
6500     \l_tmpa_tl
6501     { \exp_not:n { #3 } }
6502     {
6503       \bool_if:NTF \l_@@_NiceTabular_bool
6504       {
6505         \group_begin:
6506         \bool_if:NF \l_@@_respect_arraystretch_bool
6507         { \cs_set:Npn \exp_not:N \arraystretch { 1 } }
6508         \exp_not:n
6509         {
6510           \dim_zero:N \extrarowheight
6511           #4

```

If the box is rotated (the key `\rotate` may be in the previous #4), the tabular used for the content of the cell will be constructed with a format `c`. In the other cases, the tabular will be constructed with a format equal to the key of position of the box. In other words: the alignment internal to the tabular is the same as the external alignment of the tabular (that is to say the position of the block in its zone of merged cells).

```

6512       \bool_if:NT \l_@@_rotate_bool
6513       { \str_set:Nn \l_@@_hpos_block_str c }
6514       \use:x
6515       {
6516         \exp_not:N \begin { tabular } [ \l_@@_vpos_of_block_tl ]
6517         { @ { } \l_@@_hpos_block_str @ { } }
6518       }
6519       #5
6520       \end { tabular }
6521     }
6522   \group_end:
6523 }
6524 {
6525   \group_begin:
6526   \bool_if:NF \l_@@_respect_arraystretch_bool
6527   { \cs_set:Npn \exp_not:N \arraystretch { 1 } }
6528   \exp_not:n
6529   {
6530     \dim_zero:N \extrarowheight
6531     #4
6532     \bool_if:NT \l_@@_rotate_bool
6533     { \str_set:Nn \l_@@_hpos_block_str c }
6534     \c_math_toggle_token
6535     \use:x
6536     {
6537       \exp_not:N \begin { array } [ \l_@@_vpos_of_block_tl ]
6538       { @ { } \l_@@_hpos_block_str @ { } }
6539     }
6540     #5
6541     \end { array }
6542     \c_math_toggle_token
6543   }
6544   \group_end:
6545 }
6546 }

```

```

6547     }
6548 }

```

We recall that the options of the command `\Block` are analyzed twice: first in the cell of the array and once again when the block will be put in the array *after the construction of the array* (by using PGF).

```

6549 \keys_define:nn { NiceMatrix / Block / SecondPass }
6550 {
6551     tikz .code:n =
6552         \bool_if:NTF \c_@@tikz_loaded_bool
6553         { \seq_put_right:Nn \l_@@tikz_seq { { #1 } } }
6554         { \@@_error:n { tikz-key-without-tikz } } ,
6555     tikz .value_required:n = true ,
6556     fill .code:n =
6557         \tl_set_rescan:Nnn
6558         \l_@@fill_tl
6559         { \char_set_catcode_other:N ! }
6560         { #1 } ,
6561     fill .value_required:n = true ,
6562     draw .code:n =
6563         \tl_set_rescan:Nnn
6564         \l_@@draw_tl
6565         { \char_set_catcode_other:N ! }
6566         { #1 } ,
6567     draw .default:n = default ,
6568     rounded-corners .dim_set:N = \l_@@rounded_corners_dim ,
6569     rounded-corners .default:n = 4 pt ,
6570     color .code:n =
6571         \@@_color:n { #1 }
6572         \tl_set_rescan:Nnn
6573         \l_@@draw_tl
6574         { \char_set_catcode_other:N ! }
6575         { #1 } ,
6576     color .value_required:n = true ,
6577     borders .clist_set:N = \l_@@borders_clist ,
6578     borders .value_required:n = true ,
6579     hvlines .meta:n = { vlines , hlines } ,
6580     vlines .bool_set:N = \l_@@vlines_block_bool ,
6581     vlines .default:n = true ,
6582     hlines .bool_set:N = \l_@@hlines_block_bool ,
6583     hlines .default:n = true ,
6584     line-width .dim_set:N = \l_@@line_width_dim ,
6585     line-width .value_required:n = true ,
6586     l .code:n = \str_set:Nn \l_@@hpos_block_str l ,
6587     l .value_forbidden:n = true ,
6588     r .code:n = \str_set:Nn \l_@@hpos_block_str r ,
6589     r .value_forbidden:n = true ,
6590     c .code:n = \str_set:Nn \l_@@hpos_block_str c ,
6591     c .value_forbidden:n = true ,
6592     L .code:n = \str_set:Nn \l_@@hpos_block_str l
6593         \bool_set_true:N \l_@@hpos_of_block_cap_bool ,
6594     L .value_forbidden:n = true ,
6595     R .code:n = \str_set:Nn \l_@@hpos_block_str r
6596         \bool_set_true:N \l_@@hpos_of_block_cap_bool ,
6597     R .value_forbidden:n = true ,
6598     C .code:n = \str_set:Nn \l_@@hpos_block_str c
6599         \bool_set_true:N \l_@@hpos_of_block_cap_bool ,
6600     C .value_forbidden:n = true ,
6601     t .code:n = \str_set:Nn \l_@@vpos_of_block_tl t ,
6602     t .value_forbidden:n = true ,
6603     b .code:n = \str_set:Nn \l_@@vpos_of_block_tl b ,
6604     b .value_forbidden:n = true ,

```

```

6605     name .tl_set:N = \l_@@_block_name_str ,
6606     name .value_required:n = true ,
6607     name .initial:n = ,
6608     respect-arraystretch .bool_set:N = \l_@@_respect_arraystretch_bool ,
6609     respect-arraystretch .default:n = true ,
6610     v-center .bool_set:N = \l_@@_v_center_bool ,
6611     v-center .default:n = true ,
6612     v-center .initial:n = false ,
6613     transparent .bool_set:N = \l_@@_transparent_bool ,
6614     transparent .default:n = true ,
6615     transparent .initial:n = false ,
6616     unknown .code:n = \@@_error:n { Unknown-key-for-Block }
6617 }

```

The command `\@@_draw_blocks:` will draw all the blocks. This command is used after the construction of the array. We have to revert to a clean version of `\ialign` because there may be tabulars in the `\Block` instructions that will be composed now.

```

6618 \cs_new_protected:Npn \@@_draw_blocks:
6619 {
6620     \cs_set_eq:NN \ialign \@@_old_ialign:
6621     \seq_map_inline:Nn \g_@@_blocks_seq { \@@_Block_iv:nnnnnn ##1 }
6622 }
6623 \cs_new_protected:Npn \@@_Block_iv:nnnnnn #1 #2 #3 #4 #5 #6
6624 {

```

The integer `\l_@@_last_row_int` will be the last row of the block and `\l_@@_last_col_int` its last column.

```

6625     \int_zero_new:N \l_@@_last_row_int
6626     \int_zero_new:N \l_@@_last_col_int

```

We remind that the first mandatory argument of the command `\Block` is the size of the block with the special format *i-j*. However, the user is allowed to omit *i* or *j* (or both). This will be interpreted as: the last row (resp. column) of the block will be the last row (resp. column) of the block (without the potential exterior row—resp. column—of the array). By convention, this is stored in `\g_@@_blocks_seq` as a number of rows (resp. columns) for the block equal to 100. That's what we detect now.

```

6627     \int_compare:nNnTF { #3 } > { 99 }
6628     { \int_set_eq:NN \l_@@_last_row_int \c{iRow} }
6629     { \int_set:Nn \l_@@_last_row_int { #3 } }
6630     \int_compare:nNnTF { #4 } > { 99 }
6631     { \int_set_eq:NN \l_@@_last_col_int \c{jCol} }
6632     { \int_set:Nn \l_@@_last_col_int { #4 } }
6633     \int_compare:nNnTF \l_@@_last_col_int > \g_@@_col_total_int
6634     {
6635         \int_compare:nTF
6636         { \l_@@_last_col_int <= \g_@@_static_num_of_col_int }
6637         {
6638             \msg_error:nnnn { nicematrix } { Block-too-large~2 } { #1 } { #2 }
6639             \@@_msg_redirect_name:nn { Block-too-large~2 } { none }
6640             \@@_msg_redirect_name:nn { columns-not-used } { none }
6641         }
6642         { \msg_error:nnnn { nicematrix } { Block-too-large~1 } { #1 } { #2 } }
6643     }
6644     {
6645         \int_compare:nNnTF \l_@@_last_row_int > \g_@@_row_total_int
6646         { \msg_error:nnnn { nicematrix } { Block-too-large~1 } { #1 } { #2 } }
6647         { \@@_Block_v:nnnnnn { #1 } { #2 } { #3 } { #4 } { #5 } { #6 } }
6648     }
6649 }
6650 \cs_new_protected:Npn \@@_Block_v:nnnnnn #1 #2 #3 #4 #5 #6
6651 {

```

The group is for the keys.

```
6652 \group_begin:
6653 \keys_set:nn { NiceMatrix / Block / SecondPass } { #5 }
```

We restrict the use of the key v-center to the case of a mono-row block.

```
6654 \bool_if:NT \l_@@_v_center_bool
6655 {
6656   \int_compare:nNnF { #1 } = { #3 }
6657   {
6658     \@@_error:n { Wrong-use-of-v-center }
6659     \bool_set_false:N \l_@@_v_center_bool
6660   }
6661 }
6662 \bool_if:NT \l_@@_vlines_block_bool
6663 {
6664   \tl_gput_right:Nx \g_nicematrix_code_after_tl
6665   {
6666     \@@_vlines_block:nnn
6667     { \exp_not:n { #5 } }
6668     { #1 - #2 }
6669     { \int_use:N \l_@@_last_row_int - \int_use:N \l_@@_last_col_int }
6670   }
6671 }
6672 \bool_if:NT \l_@@_hlines_block_bool
6673 {
6674   \tl_gput_right:Nx \g_nicematrix_code_after_tl
6675   {
6676     \@@_hlines_block:nnn
6677     { \exp_not:n { #5 } }
6678     { #1 - #2 }
6679     { \int_use:N \l_@@_last_row_int - \int_use:N \l_@@_last_col_int }
6680   }
6681 }
6682 \bool_if:nF
6683 {
6684   \l_@@_transparent_bool
6685   || ( \l_@@_vlines_block_bool && \l_@@_hlines_block_bool )
6686 }
6687 {
```

The sequence of the positions of the blocks (excepted the blocks with the key hvlines) will be used when drawing the rules (in fact, there is also the \multicolumn and the \diagbox in that sequence).

```
6688 \seq_gput_left:Nx \g_@@_pos_of_blocks_seq
6689 { { #1 } { #2 } { #3 } { #4 } { \l_@@_block_name_str } }
6690 }
6691 \bool_lazy_and:nnT
6692 { ! (\tl_if_empty_p:N \l_@@_draw_tl) }
6693 { \l_@@_hlines_block_bool || \l_@@_vlines_block_bool }
6694 { \@@_error:n { hlines-with-color } }
6695 \tl_if_empty:NF \l_@@_draw_tl
6696 {
6697   \tl_gput_right:Nx \g_nicematrix_code_after_tl
6698   {
6699     \@@_stroke_block:nnn
6700     { \exp_not:n { #5 } }
6701     { #1 - #2 }
6702     { \int_use:N \l_@@_last_row_int - \int_use:N \l_@@_last_col_int }
6703   }
6704   \seq_gput_right:Nn \g_@@_pos_of_stroken_blocks_seq
6705   { { #1 } { #2 } { #3 } { #4 } }
6706 }
```

```

6707 \clist_if_empty:NF \l_@@_borders_clist
6708 {
6709   \tl_gput_right:Nx \g_nicematrix_code_after_tl
6710   {
6711     \@@_stroke_borders_block:nnn
6712     { \exp_not:n { #5 } }
6713     { #1 - #2 }
6714     { \int_use:N \l_@@_last_row_int - \int_use:N \l_@@_last_col_int }
6715   }
6716 }
6717 \tl_if_empty:NF \l_@@_fill_tl
6718 {
6719   \tl_gput_right:Nx \g_@@_pre_code_before_tl
6720   {
6721     \exp_not:N \roundedrectanglecolor
6722     \exp_args:NV \tl_if_head_eq_meaning:nNTF \l_@@_fill_tl [
6723       { \l_@@_fill_tl }
6724       { { \l_@@_fill_tl } }
6725       { #1 - #2 }
6726       { \int_use:N \l_@@_last_row_int - \int_use:N \l_@@_last_col_int }
6727       { \dim_use:N \l_@@_rounded_corners_dim }
6728     ]
6729   }
6730 \seq_if_empty:NF \l_@@_tikz_seq
6731 {
6732   \tl_gput_right:Nx \g_nicematrix_code_before_tl
6733   {
6734     \@@_block_tikz:nnnnn
6735     { #1 }
6736     { #2 }
6737     { \int_use:N \l_@@_last_row_int }
6738     { \int_use:N \l_@@_last_col_int }
6739     { \seq_use:Nn \l_@@_tikz_seq { , } }
6740   }
6741 }
6742 \cs_set_protected_nopar:Npn \diagbox ##1 ##2
6743 {
6744   \tl_gput_right:Nx \g_@@_pre_code_after_tl
6745   {
6746     \@@_actually_diagbox:nnnnnn
6747     { #1 }
6748     { #2 }
6749     { \int_use:N \l_@@_last_row_int }
6750     { \int_use:N \l_@@_last_col_int }
6751     { \exp_not:n { ##1 } } { \exp_not:n { ##2 } }
6752   }
6753 }
6754 \hbox_set:Nn \l_@@_cell_box { \set@color #6 }
6755 \bool_if:NT \g_@@_rotate_bool \@@_rotate_cell_box:

```

Let's consider the following `{NiceTabular}`. Because of the instruction `!\hspace{1cm}` in the preamble which increases the space between the columns (by adding, in fact, that space to the previous column, that is to say the second column of the tabular), we will create *two* nodes relative to the block: the node `1-1-block` and the node `1-1-block-short`.

```

\begin{NiceTabular}{cc!\hspace{1cm}}c}
\Block{2-2}{our block} & & one & \\\
& & two & \\\
three & & four & five & \\\

```

```
six          & seven & eight \\
\end{NiceTabular}
```

We highlight the node 1-1-block

our block		one
		two
three	four	five
six	seven	eight

We highlight the node 1-1-block-short

our block		one
		two
three	four	five
six	seven	eight

The construction of the node corresponding to the merged cells.

```
6756 \pgfpicture
6757 \pgfrememberpicturepositiononpagetrue
6758 \pgf@relevantforpicturesizefalse
6759 \@@_qpoint:n { row - #1 }
6760 \dim_set_eq:NN \l_tmpa_dim \pgf@y
6761 \@@_qpoint:n { col - #2 }
6762 \dim_set_eq:NN \l_tmpb_dim \pgf@x
6763 \@@_qpoint:n { row - \int_eval:n { \l_@@_last_row_int + 1 } }
6764 \dim_set_eq:NN \l_@@_tmpc_dim \pgf@y
6765 \@@_qpoint:n { col - \int_eval:n { \l_@@_last_col_int + 1 } }
6766 \dim_set_eq:NN \l_@@_tmpd_dim \pgf@x
```

We construct the node for the block with the name (#1-#2-block).

The function `\@@_pgf_rect_node:nnnnn` takes in as arguments the name of the node and the four coordinates of two opposite corner points of the rectangle.

```
6767 \@@_pgf_rect_node:nnnnn
6768 { \@@_env: - #1 - #2 - block }
6769 \l_tmpb_dim \l_tmpa_dim \l_@@_tmpd_dim \l_@@_tmpc_dim
6770 \str_if_empty:NF \l_@@_block_name_str
6771 {
6772 \pgfnodealias
6773 { \@@_env: - \l_@@_block_name_str }
6774 { \@@_env: - #1 - #2 - block }
6775 \str_if_empty:NF \l_@@_name_str
6776 {
6777 \pgfnodealias
6778 { \l_@@_name_str - \l_@@_block_name_str }
6779 { \@@_env: - #1 - #2 - block }
6780 }
6781 }
```

Now, we create the “short node” which, in general, will be used to put the label (that is to say the content of the node). However, if one the keys L, C or R is used (that information is provided by the boolean `\l_@@_hpos_of_block_cap_bool`), we don’t need to create that node since the normal node is used to put the label.

```
6782 \bool_if:NF \l_@@_hpos_of_block_cap_bool
6783 {
6784 \dim_set_eq:NN \l_tmpb_dim \c_max_dim
```

The short node is constructed by taking into account the *contents* of the columns involved in at least one cell of the block. That’s why we have to do a loop over the rows of the array.

```
6785 \int_step_inline:nnn \l_@@_first_row_int \g_@@_row_total_int
6786 {
```

We recall that, when a cell is empty, no (normal) node is created in that cell. That’s why we test the existence of the node before using it.

```
6787 \cs_if_exist:cT
6788 { pgf @ sh @ ns @ \@@_env: - ##1 - #2 }
6789 {
6790 \seq_if_in:NnF \g_@@_multicolumn_cells_seq { ##1 - #2 }
6791 {
6792 \pgfpointanchor { \@@_env: - ##1 - #2 } { west }
```

```

6793         \dim_set:Nn \l_tmpb_dim { \dim_min:nn \l_tmpb_dim \pgf@x }
6794     }
6795 }
6796

```

If all the cells of the column were empty, `\l_tmpb_dim` has still the same value `\c_max_dim`. In that case, you use for `\l_tmpb_dim` the value of the position of the vertical rule.

```

6797     \dim_compare:nNnT \l_tmpb_dim = \c_max_dim
6798     {
6799         \@@_qpoint:n { col - #2 }
6800         \dim_set_eq:NN \l_tmpb_dim \pgf@x
6801     }
6802     \dim_set:Nn \l_@@_tmpd_dim { - \c_max_dim }
6803     \int_step_inline:nnn \l_@@_first_row_int \g_@@_row_total_int
6804     {
6805         \cs_if_exist:cT
6806         { \pgf @ sh @ ns @ \@@_env: - #1 - \int_use:N \l_@@_last_col_int }
6807         {
6808             \seq_if_in:NnF \g_@@_multicolumn_cells_seq { #1 - #2 }
6809             {
6810                 \pgfpointanchor
6811                 { \@@_env: - #1 - \int_use:N \l_@@_last_col_int }
6812                 { east }
6813                 \dim_set:Nn \l_@@_tmpd_dim { \dim_max:nn \l_@@_tmpd_dim \pgf@x }
6814             }
6815         }
6816     }
6817     \dim_compare:nNnT \l_@@_tmpd_dim = { - \c_max_dim }
6818     {
6819         \@@_qpoint:n { col - \int_eval:n { \l_@@_last_col_int + 1 } }
6820         \dim_set_eq:NN \l_@@_tmpd_dim \pgf@x
6821     }
6822     \@@_pgf_rect_node:nnnnn
6823     { \@@_env: - #1 - #2 - block - short }
6824     \l_tmpb_dim \l_tmpa_dim \l_@@_tmpd_dim \l_@@_tmpc_dim
6825 }

```

If the creation of the “medium nodes” is required, we create a “medium node” for the block. The function `\@@_pgf_rect_node:nnn` takes in as arguments the name of the node and two PGF points.

```

6826     \bool_if:NT \l_@@_medium_nodes_bool
6827     {
6828         \@@_pgf_rect_node:nnn
6829         { \@@_env: - #1 - #2 - block - medium }
6830         { \pgfpointanchor { \@@_env: - #1 - #2 - medium } { north-west } }
6831         {
6832             \pgfpointanchor
6833             { \@@_env:
6834               - \int_use:N \l_@@_last_row_int
6835               - \int_use:N \l_@@_last_col_int - medium
6836             }
6837             { south-east }
6838         }
6839     }

```

Now, we will put the label of the block beginning with the case of a `\Block` of one row.

```

6840     \bool_if:nTF
6841     { \int_compare_p:nNn { #1 } = { #3 } && ! \l_@@_v_center_bool }
6842     {

```

We take into account the case of a block of one row in the “first row” or the “last row”.

```

6843         \int_compare:nNnTF { #1 } = 0
6844         { \l_@@_code_for_first_row_tl }
6845         {
6846             \int_compare:nNnT { #1 } = \l_@@_last_row_int

```

```

6847         \l_@@_code_for_last_row_tl
6848     }

```

If the block has only one row, we want the label of the block perfectly aligned on the baseline of the row. That's why we have constructed a `\pgfcoordinate` on the baseline of the row, in the first column of the array. Now, we retrieve the y -value of that node and we store it in `\l_tmpa_dim`.

```

6849         \pgfextracty \l_tmpa_dim { \@@_qpoint:n { row - #1 - base } }

```

We retrieve (in `\pgf@x`) the x -value of the center of the block.

```

6850     \pgfpointanchor
6851     {
6852         \@@_env: - #1 - #2 - block
6853         \bool_if:NF \l_@@_hpos_of_block_cap_bool { - short }
6854     }
6855     {
6856         \str_case:Vn \l_@@_hpos_block_str
6857         {
6858             c { center }
6859             l { west }
6860             r { east }
6861         }
6862     }

```

We put the label of the block which has been composed in `\l_@@_cell_box`.

```

6863     \pgftransformshift { \pgfpoint \pgf@x \l_tmpa_dim }
6864     \pgfset { inner~sep = \c_zero_dim }
6865     \pgfnode
6866     { rectangle }
6867     {
6868         \str_case:Vn \l_@@_hpos_block_str
6869         {
6870             c { base }
6871             l { base~west }
6872             r { base~east }
6873         }
6874     }
6875     { \box_use_drop:N \l_@@_cell_box } { } { }
6876 }

```

If the number of rows is different of 1, we will put the label of the block by using the short node (the label of the block has been composed in `\l_@@_cell_box`).

```

6877     {

```

If we are in the first column, we must put the block as if it was with the key `r`.

```

6878         \int_compare:nNnT { #2 } = 0
6879         { \str_set:Nn \l_@@_hpos_block_str r }
6880         \bool_if:nT \g_@@_last_col_found_bool
6881         {
6882             \int_compare:nNnT { #2 } = \g_@@_col_total_int
6883             { \str_set:Nn \l_@@_hpos_block_str l }
6884         }
6885     \pgftransformshift
6886     {
6887         \pgfpointanchor
6888         {
6889             \@@_env: - #1 - #2 - block
6890             \bool_if:NF \l_@@_hpos_of_block_cap_bool { - short }
6891         }
6892         {
6893             \str_case:Vn \l_@@_hpos_block_str
6894             {
6895                 c { center }
6896                 l { west }
6897                 r { east }
6898             }

```



```

6899     }
6900   }
6901   \pgfset { inner-sep = \c_zero_dim }
6902   \pgfnode
6903     { rectangle }
6904     {
6905       \str_case:Vn \l_@@_hpos_block_str
6906       {
6907         c { center }
6908         l { west }
6909         r { east }
6910       }
6911     }
6912     { \box_use_drop:N \l_@@_cell_box } { } { }
6913   }
6914   \endpgfpicture
6915   \group_end:
6916 }

```

The first argument of `\@@_stroke_block:nnn` is a list of options for the rectangle that you will stroke. The second argument is the upper-left cell of the block (with, as usual, the syntax *i-j*) and the third is the last cell of the block (with the same syntax).

```

6917 \cs_new_protected:Npn \@@_stroke_block:nnn #1 #2 #3
6918 {
6919   \group_begin:
6920   \tl_clear:N \l_@@_draw_tl
6921   \dim_set_eq:NN \l_@@_line_width_dim \arrayrulewidth
6922   \keys_set_known:nn { NiceMatrix / BlockStroke } { #1 }
6923   \pgfpicture
6924   \pgfrememberpicturepositiononpagetrue
6925   \pgf@relevantforpicturesizefalse
6926   \tl_if_empty:NF \l_@@_draw_tl
6927   {

```

If the user has used the key `color` of the command `\Block` without value, the color fixed by `\arrayrulecolor` is used.

```

6928     \str_if_eq:VnTF \l_@@_draw_tl { default }
6929     { \CT@arc@ }
6930     { \@@_color:V \l_@@_draw_tl }
6931   }
6932   \pgfsetcornersarced
6933   {
6934     \pgfpoint
6935     { \dim_use:N \l_@@_rounded_corners_dim }
6936     { \dim_use:N \l_@@_rounded_corners_dim }
6937   }
6938   \@@_cut_on_hyphen:w #2 \q_stop
6939   \bool_lazy_and:nnT
6940     { \int_compare_p:n { \l_tmpa_tl <= \c@iRow } }
6941     { \int_compare_p:n { \l_tmpb_tl <= \c@jCol } }
6942   {
6943     \@@_qpoint:n { row - \l_tmpa_tl }
6944     \dim_set:Nn \l_tmpb_dim { \pgf@y }
6945     \@@_qpoint:n { col - \l_tmpb_tl }
6946     \dim_set:Nn \l_@@_tmpc_dim { \pgf@x }
6947     \@@_cut_on_hyphen:w #3 \q_stop
6948     \int_compare:nNnT \l_tmpa_tl > \c@iRow
6949     { \tl_set:Nx \l_tmpa_tl { \int_use:N \c@iRow } }
6950     \int_compare:nNnT \l_tmpb_tl > \c@jCol
6951     { \tl_set:Nx \l_tmpb_tl { \int_use:N \c@jCol } }
6952     \@@_qpoint:n { row - \int_eval:n { \l_tmpa_tl + 1 } }
6953     \dim_set:Nn \l_tmpa_dim { \pgf@y }
6954     \@@_qpoint:n { col - \int_eval:n { \l_tmpb_tl + 1 } }

```

```

6955     \dim_set:Nn \l_@@_tmpd_dim { \pgf@x }
6956     \pgfpathrectanglecorners
6957     { \pgfpoint \l_@@_tmpc_dim \l_tmpb_dim }
6958     { \pgfpoint \l_@@_tmpd_dim \l_tmpa_dim }
6959     \pgfsetlinewidth { 1.1 \l_@@_line_width_dim }
6960     \dim_compare:nNnTF \l_@@_rounded_corners_dim = \c_zero_dim
6961     { \pgfusepathqstroke }
6962     { \pgfusepath { stroke } }
6963   }
6964   \endpgfpicture
6965   \group_end:
6966 }

```

Here is the set of keys for the command `\@@_stroke_block:nnn`.

```

6967 \keys_define:nn { NiceMatrix / BlockStroke }
6968 {
6969   color .tl_set:N = \l_@@_draw_tl ,
6970   draw .tl_set:N = \l_@@_draw_tl ,
6971   draw .default:n = default ,
6972   line-width .dim_set:N = \l_@@_line_width_dim ,
6973   rounded-corners .dim_set:N = \l_@@_rounded_corners_dim ,
6974   rounded-corners .default:n = 4 pt
6975 }

```

The first argument of `\@@_vlines_block:nnn` is a list of options for the rules that we will draw. The second argument is the upper-left cell of the block (with, as usual, the syntax $i-j$) and the third is the last cell of the block (with the same syntax).

```

6976 \cs_new_protected:Npn \@@_vlines_block:nnn #1 #2 #3
6977 {
6978   \dim_set_eq:NN \l_@@_line_width_dim \arrayrulewidth
6979   \keys_set_known:nn { NiceMatrix / BlockBorders } { #1 }
6980   \@@_cut_on_hyphen:w #2 \q_stop
6981   \tl_set_eq:NN \l_@@_tmpc_tl \l_tmpa_tl
6982   \tl_set_eq:NN \l_@@_tmpd_tl \l_tmpb_tl
6983   \@@_cut_on_hyphen:w #3 \q_stop
6984   \tl_set:Nx \l_tmpa_tl { \int_eval:n { \l_tmpa_tl + 1 } }
6985   \tl_set:Nx \l_tmpb_tl { \int_eval:n { \l_tmpb_tl + 1 } }
6986   \int_step_inline:nnn \l_@@_tmpd_tl \l_tmpb_tl
6987   {
6988     \use:x
6989     {
6990       \@@_vline:n
6991       {
6992         position = ##1 ,
6993         start = \l_@@_tmpc_tl ,
6994         end = \int_eval:n { \l_tmpa_tl - 1 } ,
6995         total-width = \dim_use:N \l_@@_line_width_dim % added 2022-08-06
6996       }
6997     }
6998   }
6999 }
7000 \cs_new_protected:Npn \@@_hlines_block:nnn #1 #2 #3
7001 {
7002   \dim_set_eq:NN \l_@@_line_width_dim \arrayrulewidth
7003   \keys_set_known:nn { NiceMatrix / BlockBorders } { #1 }
7004   \@@_cut_on_hyphen:w #2 \q_stop
7005   \tl_set_eq:NN \l_@@_tmpc_tl \l_tmpa_tl
7006   \tl_set_eq:NN \l_@@_tmpd_tl \l_tmpb_tl
7007   \@@_cut_on_hyphen:w #3 \q_stop
7008   \tl_set:Nx \l_tmpa_tl { \int_eval:n { \l_tmpa_tl + 1 } }
7009   \tl_set:Nx \l_tmpb_tl { \int_eval:n { \l_tmpb_tl + 1 } }
7010   \int_step_inline:nnn \l_@@_tmpc_tl \l_tmpa_tl
7011   {

```

```

7012 \use:x
7013 {
7014   \@@_hline:n
7015   {
7016     position = ##1 ,
7017     start = \l_@@_tmpd_tl ,
7018     end = \int_eval:n { \l_tmpb_tl - 1 } ,
7019     total-width = \dim_use:N \l_@@_line_width_dim % added 2022-08-06
7020   }
7021 }
7022 }
7023 }

```

The first argument of `\@@_stroke_borders_block:nnn` is a list of options for the borders that you will stroke. The second argument is the upper-left cell of the block (with, as usual, the syntax $i-j$) and the third is the last cell of the block (with the same syntax).

```

7024 \cs_new_protected:Npn \@@_stroke_borders_block:nnn #1 #2 #3
7025 {
7026   \dim_set_eq:NN \l_@@_line_width_dim \arrayrulewidth
7027   \keys_set_known:nn { NiceMatrix / BlockBorders } { #1 }
7028   \dim_compare:nNnTF \l_@@_rounded_corners_dim > \c_zero_dim
7029   { \@@_error:n { borders~forbidden } }
7030   {
7031     \tl_clear_new:N \l_@@_borders_tikz_tl
7032     \keys_set:nV
7033     { NiceMatrix / OnlyForTikzInBorders }
7034     \l_@@_borders_clist
7035     \@@_cut_on_hyphen:w #2 \q_stop
7036     \tl_set_eq:NN \l_@@_tmpc_tl \l_tmpa_tl
7037     \tl_set_eq:NN \l_@@_tmpd_tl \l_tmpb_tl
7038     \@@_cut_on_hyphen:w #3 \q_stop
7039     \tl_set:Nx \l_tmpa_tl { \int_eval:n { \l_tmpa_tl + 1 } }
7040     \tl_set:Nx \l_tmpb_tl { \int_eval:n { \l_tmpb_tl + 1 } }
7041     \@@_stroke_borders_block_i:
7042   }
7043 }
7044 \hook_gput_code:nnn { begindocument } { . }
7045 {
7046   \cs_new_protected:Npx \@@_stroke_borders_block_i:
7047   {
7048     \c_@@_pgfortikzpicture_tl
7049     \@@_stroke_borders_block_ii:
7050     \c_@@_endpgfortikzpicture_tl
7051   }
7052 }
7053 \cs_new_protected:Npn \@@_stroke_borders_block_ii:
7054 {
7055   \pgfrememberpicturerepositiononpagetrue
7056   \pgf@relevantforpicturesizefalse
7057   \CT@arc@
7058   \pgfsetlinewidth { 1.1 \l_@@_line_width_dim }
7059   \clist_if_in:NnT \l_@@_borders_clist { right }
7060   { \@@_stroke_vertical:n \l_tmpb_tl }
7061   \clist_if_in:NnT \l_@@_borders_clist { left }
7062   { \@@_stroke_vertical:n \l_@@_tmpd_tl }
7063   \clist_if_in:NnT \l_@@_borders_clist { bottom }
7064   { \@@_stroke_horizontal:n \l_tmpa_tl }
7065   \clist_if_in:NnT \l_@@_borders_clist { top }
7066   { \@@_stroke_horizontal:n \l_@@_tmpc_tl }
7067 }
7068 \keys_define:nn { NiceMatrix / OnlyForTikzInBorders }
7069 {

```

```

7070 tikz .code:n =
7071     \cs_if_exist:NTF \tikzpicture
7072     { \tl_set:Nn \l_@@_borders_tikz_tl { #1 } }
7073     { \@@_error:n { tikz-in~borders~without~tikz } } ,
7074 tikz .value_required:n = true ,
7075 top .code:n = ,
7076 bottom .code:n = ,
7077 left .code:n = ,
7078 right .code:n = ,
7079 unknown .code:n = \@@_error:n { bad~border }
7080 }

```

The following command is used to stroke the left border and the right border. The argument #1 is the number of column (in the sense of the `col` node).

```

7081 \cs_new_protected:Npn \@@_stroke_vertical:n #1
7082 {
7083     \@@_qpoint:n \l_@@_tmpc_tl
7084     \dim_set:Nn \l_tmpb_dim { \pgf@y + 0.5 \l_@@_line_width_dim }
7085     \@@_qpoint:n \l_tmpa_tl
7086     \dim_set:Nn \l_@@_tmpc_dim { \pgf@y + 0.5 \l_@@_line_width_dim }
7087     \@@_qpoint:n { #1 }
7088     \tl_if_empty:NTF \l_@@_borders_tikz_tl
7089     {
7090         \pgfpathmoveto { \pgfpoint \pgf@x \l_tmpb_dim }
7091         \pgfpathlineto { \pgfpoint \pgf@x \l_@@_tmpc_dim }
7092         \pgfusepathqstroke
7093     }
7094     {
7095         \use:x { \exp_not:N \draw [ \l_@@_borders_tikz_tl ] }
7096         ( \pgf@x , \l_tmpb_dim ) -- ( \pgf@x , \l_@@_tmpc_dim ) ;
7097     }
7098 }

```

The following command is used to stroke the top border and the bottom border. The argument #1 is the number of row (in the sense of the `row` node).

```

7099 \cs_new_protected:Npn \@@_stroke_horizontal:n #1
7100 {
7101     \@@_qpoint:n \l_@@_tmpd_tl
7102     \clist_if_in:NnTF \l_@@_borders_clist { left }
7103     { \dim_set:Nn \l_tmpa_dim { \pgf@x - 0.5 \l_@@_line_width_dim } }
7104     { \dim_set:Nn \l_tmpa_dim { \pgf@x + 0.5 \l_@@_line_width_dim } }
7105     \@@_qpoint:n \l_tmpb_tl
7106     \dim_set:Nn \l_tmpb_dim { \pgf@x + 0.5 \l_@@_line_width_dim }
7107     \@@_qpoint:n { #1 }
7108     \tl_if_empty:NTF \l_@@_borders_tikz_tl
7109     {
7110         \pgfpathmoveto { \pgfpoint \l_tmpa_dim \pgf@y }
7111         \pgfpathlineto { \pgfpoint \l_tmpb_dim \pgf@y }
7112         \pgfusepathqstroke
7113     }
7114     {
7115         \use:x { \exp_not:N \draw [ \l_@@_borders_tikz_tl ] }
7116         ( \l_tmpa_dim , \pgf@y ) -- ( \l_tmpb_dim , \pgf@y ) ;
7117     }
7118 }

```

Here is the set of keys for the command `\@@_stroke_borders_block:nnn`.

```

7119 \keys_define:nn { NiceMatrix / BlockBorders }
7120 {
7121     borders .clist_set:N = \l_@@_borders_clist ,
7122     rounded-corners .dim_set:N = \l_@@_rounded_corners_dim ,
7123     rounded-corners .default:n = 4 pt ,

```

```

7124     line-width .dim_set:N = \l_@@_line_width_dim ,
7125 }

```

The following command will be used if the key `tikz` has been used for the command `\Block`. The arguments `#1` and `#2` are the coordinates of the first cell and `#3` and `#4` the coordinates of the last cell of the block. `#5` is a comma-separated list of the Tikz keys used with the path.

```

7126 \cs_new_protected:Npn \@@_block_tikz:nnnnn #1 #2 #3 #4 #5
7127 {
7128   \begin { tikzpicture }
7129   \clist_map_inline:nn { #5 }
7130   {
7131     \path [ ##1 ]
7132       ( #1 -| #2 )
7133       rectangle
7134       ( \int_eval:n { #3 + 1 } -| \int_eval:n { #4 + 1 } ) ;
7135   }
7136   \end { tikzpicture }
7137 }

```

How to draw the dotted lines transparently

```

7138 \cs_set_protected:Npn \@@_renew_matrix:
7139 {
7140   \RenewDocumentEnvironment { pmatrix } { } {
7141     { \pNiceMatrix }
7142     { \endpNiceMatrix }
7143   \RenewDocumentEnvironment { vmatrix } { } {
7144     { \vNiceMatrix }
7145     { \endvNiceMatrix }
7146   \RenewDocumentEnvironment { Vmatrix } { } {
7147     { \VNiceMatrix }
7148     { \endVNiceMatrix }
7149   \RenewDocumentEnvironment { bmatrix } { } {
7150     { \bNiceMatrix }
7151     { \endbNiceMatrix }
7152   \RenewDocumentEnvironment { Bmatrix } { } {
7153     { \BNiceMatrix }
7154     { \endBNiceMatrix }
7155   }

```

Automatic arrays

We will extract the potential keys `columns-type`, `l`, `c`, `r` and pass the other keys to the environment `{NiceArrayWithDelims}`.

```

7156 \keys_define:nn { NiceMatrix / Auto }
7157 {
7158   columns-type .code:n = \@@_set_preamble:Nn \l_@@_columns_type_tl { #1 } ,
7159   columns-type .value_required:n = true ,
7160   l .meta:n = { columns-type = l } ,
7161   r .meta:n = { columns-type = r } ,
7162   c .meta:n = { columns-type = c } ,
7163   delimiters / color .tl_set:N = \l_@@_delimiters_color_tl ,
7164   delimiters / color .value_required:n = true ,
7165   delimiters / max-width .bool_set:N = \l_@@_delimiters_max_width_bool ,
7166   delimiters / max-width .default:n = true ,
7167   delimiters .code:n = \keys_set:nn { NiceMatrix / delimiters } { #1 } ,
7168   delimiters .value_required:n = true ,
7169 }
7170 \NewDocumentCommand \AutoNiceMatrixWithDelims
7171 { m m O { } > { \SplitArgument { 1 } { - } } m O { } m ! O { } }
7172 { \@@_auto_nice_matrix:nnnnnn { #1 } { #2 } #4 { #6 } { #3 , #5 , #7 } }

```

```

7173 \cs_new_protected:Npn \@@_auto_nice_matrix:nnnnnn #1 #2 #3 #4 #5 #6
7174 {

```

The group is for the protection of the keys.

```

7175 \group_begin:
7176 \bool_set_true:N \l_@@_Matrix_bool
7177 \keys_set_known:nnN { NiceMatrix / Auto } { #6 } \l_tmpa_tl

```

We nullify the command \@@_transform_preamble: because we will provide a preamble which is yet transformed (by using \l_@@_columns_type_tl which is yet nicematrix-ready).

```

7178 \cs_set_eq:NN \@@_transform_preamble: \prg_do_nothing:
7179 \use:x
7180 {
7181 \exp_not:N \begin { NiceArrayWithDelims } { #1 } { #2 }
7182 { * { #4 } { \exp_not:V \l_@@_columns_type_tl } }
7183 [ \exp_not:V \l_tmpa_tl ]
7184 }
7185 \int_compare:nNnT \l_@@_first_row_int = 0
7186 {
7187 \int_compare:nNnT \l_@@_first_col_int = 0 { & }
7188 \prg_replicate:nn { #4 - 1 } { & }
7189 \int_compare:nNnT \l_@@_last_col_int > { -1 } { & } \\\
7190 }
7191 \prg_replicate:nn { #3 }
7192 {
7193 \int_compare:nNnT \l_@@_first_col_int = 0 { & }

```

We put { } before #6 to avoid a hasty expansion of a potential \arabic{iRow} at the beginning of the row which would result in an incorrect value of that iRow (since iRow is incremented in the first cell of the row of the \halign).

```

7194 \prg_replicate:nn { #4 - 1 } { { } #5 & } #5
7195 \int_compare:nNnT \l_@@_last_col_int > { -1 } { & } \\\
7196 }
7197 \int_compare:nNnT \l_@@_last_row_int > { -2 }
7198 {
7199 \int_compare:nNnT \l_@@_first_col_int = 0 { & }
7200 \prg_replicate:nn { #4 - 1 } { & }
7201 \int_compare:nNnT \l_@@_last_col_int > { -1 } { & } \\\
7202 }
7203 \end { NiceArrayWithDelims }
7204 \group_end:
7205 }

7206 \cs_set_protected:Npn \@@_define_com:nnn #1 #2 #3
7207 {
7208 \cs_set_protected:cpn { #1 AutoNiceMatrix }
7209 {
7210 \bool_gset_false:N \g_@@_NiceArray_bool
7211 \str_gset:Nx \g_@@_name_env_str { #1 AutoNiceMatrix }
7212 \AutoNiceMatrixWithDelims { #2 } { #3 }
7213 }
7214 }

7215 \@@_define_com:nnn p ( )
7216 \@@_define_com:nnn b [ ]
7217 \@@_define_com:nnn v | |
7218 \@@_define_com:nnn V \ | \ |
7219 \@@_define_com:nnn B \{ \}

```

We define also a command \AutoNiceMatrix similar to the environment {NiceMatrix}.

```

7220 \NewDocumentCommand \AutoNiceMatrix { 0 { } m 0 { } m ! 0 { } }
7221 {
7222 \group_begin:
7223 \bool_gset_true:N \g_@@_NiceArray_bool

```

```

7224 \AutoNiceMatrixWithDelims . . { #2 } { #4 } [ #1 , #3 , #5 ]
7225 \group_end:
7226 }

```

The redefinition of the command `\dotfill`

```

7227 \cs_set_eq:NN \@@_old_dotfill \dotfill
7228 \cs_new_protected:Npn \@@_dotfill:
7229 {

```

First, we insert `\@@_dotfill` (which is the saved version of `\dotfill`) in case of use of `\dotfill` “internally” in the cell (e.g. `\hbox to 1cm {\dotfill}`).

```

7230 \@@_old_dotfill
7231 \bool_if:NT \l_@@_NiceTabular_bool
7232 { \group_insert_after:N \@@_dotfill_ii: }
7233 { \group_insert_after:N \@@_dotfill_i: }
7234 }
7235 \cs_new_protected:Npn \@@_dotfill_i: { \group_insert_after:N \@@_dotfill_ii: }
7236 \cs_new_protected:Npn \@@_dotfill_ii: { \group_insert_after:N \@@_dotfill_iii: }

```

Now, if the box is not empty (unfortunately, we can’t actually test whether the box is empty and that’s why we only consider it’s width), we insert `\@@_dotfill` (which is the saved version of `\dotfill`) in the cell of the array, and it will extend, since it is no longer in `\l_@@_cell_box`.

```

7237 \cs_new_protected:Npn \@@_dotfill_iii:
7238 { \dim_compare:nNnT { \box_wd:N \l_@@_cell_box } = \c_zero_dim \@@_old_dotfill }

```

The command `\diagbox`

The command `\diagbox` will be linked to `\diagbox:nn` in the environments of `nicematrix`. However, there are also redefinitions of `\diagbox` in other circumstances.

```

7239 \cs_new_protected:Npn \@@_diagbox:nn #1 #2
7240 {
7241 \tl_gput_right:Nx \g_@@_pre_code_after_tl
7242 {
7243 \@@_actually_diagbox:nnnnnn
7244 { \int_use:N \c@iRow }
7245 { \int_use:N \c@jCol }
7246 { \int_use:N \c@iRow }
7247 { \int_use:N \c@jCol }
7248 { \exp_not:n { #1 } }
7249 { \exp_not:n { #2 } }
7250 }

```

We put the cell with `\diagbox` in the sequence `\g_@@_pos_of_blocks_seq` because a cell with `\diagbox` must be considered as non empty by the key `corners`.

```

7251 \seq_gput_right:Nx \g_@@_pos_of_blocks_seq
7252 {
7253 { \int_use:N \c@iRow }
7254 { \int_use:N \c@jCol }
7255 { \int_use:N \c@iRow }
7256 { \int_use:N \c@jCol }

```

The last argument is for the name of the block.

```

7257 { }
7258 }
7259 }

```

The command `\diagbox` is also redefined locally when we draw a block.

The first four arguments of `\@@_actually_diagbox:nnnnnn` correspond to the rectangle (=block) to slash (we recall that it’s possible to use `\diagbox` in a `\Block`). The other two are the elements to draw below and above the diagonal line.

```

7260 \cs_new_protected:Npn \@@_actually_diagbox:nnnnnn #1 #2 #3 #4 #5 #6
7261 {
7262   \pgfpicture
7263   \pgf@relevantforpicturesizefalse
7264   \pgfrememberpicturepositiononpagetrue
7265   \@@_qpoint:n { row - #1 }
7266   \dim_set_eq:NN \l_tmpa_dim \pgf@y
7267   \@@_qpoint:n { col - #2 }
7268   \dim_set_eq:NN \l_tmpb_dim \pgf@x
7269   \pgfpathmoveto { \pgfpoint \l_tmpb_dim \l_tmpa_dim }
7270   \@@_qpoint:n { row - \int_eval:n { #3 + 1 } }
7271   \dim_set_eq:NN \l_@@_tmpc_dim \pgf@y
7272   \@@_qpoint:n { col - \int_eval:n { #4 + 1 } }
7273   \dim_set_eq:NN \l_@@_tmpd_dim \pgf@x
7274   \pgfpathlineto { \pgfpoint \l_@@_tmpd_dim \l_@@_tmpc_dim }
7275   {

```

The command `\CT@arc@` is a command of `colortbl` which sets the color of the rules in the array. The package `nicematrix` uses it even if `colortbl` is not loaded.

```

7276   \CT@arc@
7277   \pgfsetroundcap
7278   \pgfusepathqstroke
7279 }
7280 \pgfset { inner~sep = 1 pt }
7281 \pgfscope
7282 \pgftransformshift { \pgfpoint \l_tmpb_dim \l_@@_tmpc_dim }
7283 \pgfnode { rectangle } { south-west }
7284 {
7285   \begin { minipage } { 20 cm }
7286   \@@_math_toggle_token: #5 \@@_math_toggle_token:
7287   \end { minipage }
7288 }
7289 { }
7290 { }
7291 \endpgfscope
7292 \pgftransformshift { \pgfpoint \l_@@_tmpd_dim \l_tmpa_dim }
7293 \pgfnode { rectangle } { north-east }
7294 {
7295   \begin { minipage } { 20 cm }
7296   \raggedleft
7297   \@@_math_toggle_token: #6 \@@_math_toggle_token:
7298   \end { minipage }
7299 }
7300 { }
7301 { }
7302 \endpgfpicture
7303 }

```

The keyword `\CodeAfter`

The `\CodeAfter` (inserted with the key `code-after` or after the keyword `\CodeAfter`) may always begin with a list of pairs `key=value` between square brackets. Here is the corresponding set of keys.

```

7304 \keys_define:nn { NiceMatrix }
7305 {
7306   CodeAfter / rules .inherit:n = NiceMatrix / rules ,
7307   CodeAfter / sub-matrix .inherit:n = NiceMatrix / sub-matrix
7308 }
7309 \keys_define:nn { NiceMatrix / CodeAfter }
7310 {
7311   sub-matrix .code:n = \keys_set:nn { NiceMatrix / sub-matrix } { #1 } ,
7312   sub-matrix .value_required:n = true ,

```



```

7313   delimiters / color .tl_set:N = \l_@@_delimiters_color_tl ,
7314   delimiters / color .value_required:n = true ,
7315   rules .code:n = \keys_set:nn { NiceMatrix / rules } { #1 } ,
7316   rules .value_required:n = true ,
7317   unknown .code:n = \@@_error:n { Unknown-key-for-CodeAfter }
7318 }

```

In fact, in this subsection, we define the user command `\CodeAfter` for the case of the “normal syntax”. For the case of “light-syntax”, see the definition of the environment `{@@-light-syntax}` on p. 133.

In the environments of `nicematrix`, `\CodeAfter` will be linked to `\@@_CodeAfter:`. That macro must *not* be protected since it begins with `\omit`.

```

7319 \cs_new:Npn \@@_CodeAfter: { \omit \@@_CodeAfter_ii:n }

```

However, in each cell of the environment, the command `\CodeAfter` will be linked to the following command `\@@_CodeAfter_ii:n` which begins with `\`.

```

7320 \cs_new_protected:Npn \@@_CodeAfter_i: { \ \omit \@@_CodeAfter_ii:n }

```

We have to catch everything until the end of the current environment (of `nicematrix`). First, we go until the next command `\end`.

```

7321 \cs_new_protected:Npn \@@_CodeAfter_ii:n #1 \end
7322 {
7323   \tl_gput_right:Nn \g_nicematrix_code_after_tl { #1 }
7324   \@@_CodeAfter_iv:n
7325 }

```

We catch the argument of the command `\end` (in `#1`).

```

7326 \cs_new_protected:Npn \@@_CodeAfter_iv:n #1
7327 {

```

If this is really the end of the current environment (of `nicematrix`), we put back the command `\end` and its argument in the TeX flow.

```

7328   \str_if_eq:eeTF \@currentenv { #1 }
7329   { \end { #1 } }

```

If this is not the `\end` we are looking for, we put those tokens in `\g_nicematrix_code_after_tl` and we go on searching for the next command `\end` with a recursive call to the command `\@@_CodeAfter:n`.

```

7330   {
7331     \tl_gput_right:Nn \g_nicematrix_code_after_tl { \end { #1 } }
7332     \@@_CodeAfter_ii:n
7333   }
7334 }

```

The delimiters in the preamble

The command `\@@_delimiter:nnn` will be used to draw delimiters inside the matrix when delimiters are specified in the preamble of the array. It does *not* concern the exterior delimiters added by `{NiceArrayWithDelims}` (and `{pNiceArray}`, `{pNiceMatrix}`, etc.).

A delimiter in the preamble of the array will write an instruction `\@@_delimiter:nnn` in the `\g_@@_pre_code_after_tl` (and also potentially add instructions in the preamble provided to `\array` in order to add space between columns).

The first argument is the type of delimiter (`(`, `[`, `\{`, `)`, `]` or `\}`). The second argument is the number of column. The third argument is a boolean equal to `\c_true_bool` (resp. `\c_false_true`) when the delimiter must be put on the left (resp. right) side.

```

7335 \cs_new_protected:Npn \@@_delimiter:nnn #1 #2 #3
7336 {
7337   \pgfpicture
7338   \pgfrememberpicturepositiononpagetrue
7339   \pgf@relevantforpicturesizefalse

```

`\l_@@_y_initial_dim` and `\l_@@_y_final_dim` will be the y -values of the extremities of the delimiter we will have to construct.

```

7340 \@@_qpoint:n { row - 1 }
7341 \dim_set_eq:NN \l_@@_y_initial_dim \pgf@y
7342 \@@_qpoint:n { row - \int_eval:n { \c@iRow + 1 } }
7343 \dim_set_eq:NN \l_@@_y_final_dim \pgf@y

```

We will compute in `\l_tmpa_dim` the x -value where we will have to put our delimiter (on the left side or on the right side).

```

7344 \bool_if:nTF { #3 }
7345 { \dim_set_eq:NN \l_tmpa_dim \c_max_dim }
7346 { \dim_set:Nn \l_tmpa_dim { - \c_max_dim } }
7347 \int_step_inline:nnn \l_@@_first_row_int \g_@@_row_total_int
7348 {
7349   \cs_if_exist:cT
7350   { pgf @ sh @ ns @ \@@_env: - ##1 - #2 }
7351   {
7352     \pgfpointanchor
7353     { \@@_env: - ##1 - #2 }
7354     { \bool_if:nTF { #3 } { west } { east } }
7355     \dim_set:Nn \l_tmpa_dim
7356     { \bool_if:nTF { #3 } \dim_min:nn \dim_max:nn \l_tmpa_dim \pgf@x }
7357   }
7358 }

```

Now we can put the delimiter with a node of PGF.

```

7359 \pgfset { inner~sep = \c_zero_dim }
7360 \dim_zero:N \nulldelimiterspace
7361 \pgftransformshift
7362 {
7363   \pgfpoint
7364   { \l_tmpa_dim }
7365   { ( \l_@@_y_initial_dim + \l_@@_y_final_dim + \arrayrulewidth ) / 2 }
7366 }
7367 \pgfnode
7368 { rectangle }
7369 { \bool_if:nTF { #3 } { east } { west } }
7370 {

```

Here is the content of the PGF node, that is to say the delimiter, constructed with its right size.

```

7371 \nullfont
7372 \c_math_toggle_token
7373 \@@_color:V \l_@@_delimiters_color_tl
7374 \bool_if:nTF { #3 } { \left #1 } { \left . }
7375 \vcenter
7376 {
7377   \nullfont
7378   \hrule \@height
7379   \dim_eval:n { \l_@@_y_initial_dim - \l_@@_y_final_dim }
7380   \@depth \c_zero_dim
7381   \@width \c_zero_dim
7382 }
7383 \bool_if:nTF { #3 } { \right . } { \right #1 }
7384 \c_math_toggle_token
7385 }
7386 { }
7387 { }
7388 \endpgfpicture
7389 }

```

The command `\SubMatrix`

```

7390 \keys_define:nn { NiceMatrix / sub-matrix }

```

```

7391 {
7392   extra-height .dim_set:N = \l_@@_submatrix_extra_height_dim ,
7393   extra-height .value_required:n = true ,
7394   left-xshift .dim_set:N = \l_@@_submatrix_left_xshift_dim ,
7395   left-xshift .value_required:n = true ,
7396   right-xshift .dim_set:N = \l_@@_submatrix_right_xshift_dim ,
7397   right-xshift .value_required:n = true ,
7398   xshift .meta:n = { left-xshift = #1, right-xshift = #1 } ,
7399   xshift .value_required:n = true ,
7400   delimiters / color .tl_set:N = \l_@@_delimiters_color_tl ,
7401   delimiters / color .value_required:n = true ,
7402   slim .bool_set:N = \l_@@_submatrix_slim_bool ,
7403   slim .default:n = true ,
7404   hlines .clist_set:N = \l_@@_submatrix_hlines_clist ,
7405   hlines .default:n = all ,
7406   vlines .clist_set:N = \l_@@_submatrix_vlines_clist ,
7407   vlines .default:n = all ,
7408   hvlines .meta:n = { hlines, vlines } ,
7409   hvlines .value_forbidden:n = true ,
7410 }
7411 \keys_define:nn { NiceMatrix }
7412 {
7413   SubMatrix .inherit:n = NiceMatrix / sub-matrix ,
7414   CodeAfter / sub-matrix .inherit:n = NiceMatrix / sub-matrix ,
7415   NiceMatrix / sub-matrix .inherit:n = NiceMatrix / sub-matrix ,
7416   NiceArray / sub-matrix .inherit:n = NiceMatrix / sub-matrix ,
7417   pNiceArray / sub-matrix .inherit:n = NiceMatrix / sub-matrix ,
7418   NiceMatrixOptions / sub-matrix .inherit:n = NiceMatrix / sub-matrix ,
7419 }

```

The following keys set is for the command `\SubMatrix` itself (not the tuning of `\SubMatrix` that can be done elsewhere).

```

7420 \keys_define:nn { NiceMatrix / SubMatrix }
7421 {
7422   delimiters / color .tl_set:N = \l_@@_delimiters_color_tl ,
7423   delimiters / color .value_required:n = true ,
7424   hlines .clist_set:N = \l_@@_submatrix_hlines_clist ,
7425   hlines .default:n = all ,
7426   vlines .clist_set:N = \l_@@_submatrix_vlines_clist ,
7427   vlines .default:n = all ,
7428   hvlines .meta:n = { hlines, vlines } ,
7429   hvlines .value_forbidden:n = true ,
7430   name .code:n =
7431     \tl_if_empty:nTF { #1 }
7432     { \@@_error:n { Invalid-name } }
7433     {
7434       \regex_match:nnTF { \A[A-Za-z][A-Za-z0-9]*\Z } { #1 }
7435       {
7436         \seq_if_in:NnTF \g_@@_submatrix_names_seq { #1 }
7437         { \@@_error:nn { Duplicate-name-for-SubMatrix } { #1 } }
7438         {
7439           \str_set:Nn \l_@@_submatrix_name_str { #1 }
7440           \seq_gput_right:Nn \g_@@_submatrix_names_seq { #1 }
7441         }
7442       }
7443       { \@@_error:n { Invalid-name } }
7444     } ,
7445   name .value_required:n = true ,
7446   rules .code:n = \keys_set:nn { NiceMatrix / rules } { #1 } ,
7447   rules .value_required:n = true ,
7448   code .tl_set:N = \l_@@_code_tl ,
7449   code .value_required:n = true ,
7450   unknown .code:n = \@@_error:n { Unknown-key-for-SubMatrix }
7451 }

```

```

7452 \NewDocumentCommand \@@_SubMatrix_in_code_before { m m m m ! 0 { } }
7453 {
7454   \peek_remove_spaces:n
7455   {
7456     \tl_gput_right:Nx \g_@@_pre_code_after_tl
7457     {
7458       \SubMatrix { #1 } { #2 } { #3 } { #4 }
7459       [
7460         delimiters / color = \l_@@_delimiters_color_tl ,
7461         hlines = \l_@@_submatrix_hlines_clist ,
7462         vlines = \l_@@_submatrix_vlines_clist ,
7463         extra-height = \dim_use:N \l_@@_submatrix_extra_height_dim ,
7464         left-xshift = \dim_use:N \l_@@_submatrix_left_xshift_dim ,
7465         right-xshift = \dim_use:N \l_@@_submatrix_right_xshift_dim ,
7466         slim = \bool_to_str:N \l_@@_submatrix_slim_bool ,
7467         #5
7468       ]
7469     }
7470     \@@_SubMatrix_in_code_before_i { #2 } { #3 }
7471   }
7472 }

7473 \NewDocumentCommand \@@_SubMatrix_in_code_before_i
7474 { > { \SplitArgument { 1 } { - } } m > { \SplitArgument { 1 } { - } } m }
7475 { \@@_SubMatrix_in_code_before_i:nnnn #1 #2 }

7476 \cs_new_protected:Npn \@@_SubMatrix_in_code_before_i:nnnn #1 #2 #3 #4
7477 {
7478   \seq_gput_right:Nx \g_@@_submatrix_seq
7479   {

We use \str_if_eq:nnTF because it is fully expandable.
7480     { \str_if_eq:nnTF { #1 } { last } { \int_use:N \c@iRow } { #1 } }
7481     { \str_if_eq:nnTF { #2 } { last } { \int_use:N \c@jCol } { #2 } }
7482     { \str_if_eq:nnTF { #3 } { last } { \int_use:N \c@iRow } { #3 } }
7483     { \str_if_eq:nnTF { #4 } { last } { \int_use:N \c@jCol } { #4 } }
7484   }
7485 }

```

In the pre-code-after and in the `\CodeAfter` the following command `\@@_SubMatrix` will be linked to `\SubMatrix`.

- #1 is the left delimiter;
- #2 is the upper-left cell of the matrix with the format $i-j$;
- #3 is the lower-right cell of the matrix with the format $i-j$;
- #4 is the right delimiter;
- #5 is the list of options of the command;
- #6 is the potential subscript;
- #7 is the potential superscript.

For explanations about the construction with rescanning of the preamble, see the documentation for the user command `\Cdots`.

```

7486 \hook_gput_code:nnn { begindocument } { . }
7487 {
7488   \tl_set:Nn \l_@@_argspec_tl { m m m m 0 { } E { _ ^ } { { } { } } }
7489   \tl_set_rescan:Nno \l_@@_argspec_tl { } \l_@@_argspec_tl
7490   \exp_args:NNV \NewDocumentCommand \@@_SubMatrix \l_@@_argspec_tl
7491   {
7492     \peek_remove_spaces:n
7493     {
7494       \@@_sub_matrix:nnnnnnn

```

```

7495         { #1 } { #2 } { #3 } { #4 } { #5 } { #6 } { #7 }
7496     }
7497 }
7498 }

```

The following macro will compute `\l_@@_first_i_tl`, `\l_@@_first_j_tl`, `\l_@@_last_i_tl` and `\l_@@_last_j_tl` from the arguments of the command as provided by the user (for example 2-3 and 5-last).

```

7499 \NewDocumentCommand \@@_compute_i_j:nn
7500 { > { \SplitArgument { 1 } { - } } m > { \SplitArgument { 1 } { - } } m }
7501 { \@@_compute_i_j:nnnn #1 #2 }

7502 \cs_new_protected:Npn \@@_compute_i_j:nnnn #1 #2 #3 #4
7503 {
7504     \tl_set:Nn \l_@@_first_i_tl { #1 }
7505     \tl_set:Nn \l_@@_first_j_tl { #2 }
7506     \tl_set:Nn \l_@@_last_i_tl { #3 }
7507     \tl_set:Nn \l_@@_last_j_tl { #4 }
7508     \tl_if_eq:NnT \l_@@_first_i_tl { last }
7509     { \tl_set:NV \l_@@_first_i_tl \c@iRow }
7510     \tl_if_eq:NnT \l_@@_first_j_tl { last }
7511     { \tl_set:NV \l_@@_first_j_tl \c@jCol }
7512     \tl_if_eq:NnT \l_@@_last_i_tl { last }
7513     { \tl_set:NV \l_@@_last_i_tl \c@iRow }
7514     \tl_if_eq:NnT \l_@@_last_j_tl { last }
7515     { \tl_set:NV \l_@@_last_j_tl \c@jCol }
7516 }

7517 \cs_new_protected:Npn \@@_sub_matrix:nnnnnn #1 #2 #3 #4 #5 #6 #7
7518 {
7519     \group_begin:

```

The four following token lists correspond to the position of the `\SubMatrix`.

```

7520 \@@_compute_i_j:nn { #2 } { #3 }
7521 \bool_lazy_or:nnTF
7522 { \int_compare_p:nNn \l_@@_last_i_tl > \g_@@_row_total_int }
7523 { \int_compare_p:nNn \l_@@_last_j_tl > \g_@@_col_total_int }
7524 { \@@_error:nn { Construct-too-large } { \SubMatrix } }
7525 {
7526     \str_clear_new:N \l_@@_submatrix_name_str
7527     \keys_set:nn { NiceMatrix / SubMatrix } { #5 }
7528     \pgfpicture
7529     \pgfrememberpicturepositiononpagetrue
7530     \pgf@relevantforpicturesizefalse
7531     \pgfset { inner-sep = \c_zero_dim }
7532     \dim_set_eq:NN \l_@@_x_initial_dim \c_max_dim
7533     \dim_set:Nn \l_@@_x_final_dim { - \c_max_dim }

```

The last value of `\int_step_inline:nnn` is provided by currying.

```

7534 \bool_if:NTF \l_@@_submatrix_slim_bool
7535 { \int_step_inline:nnn \l_@@_first_i_tl \l_@@_last_i_tl }
7536 { \int_step_inline:nnn \l_@@_first_row_int \g_@@_row_total_int }
7537 {
7538     \cs_if_exist:cT
7539     { pgf @ sh @ ns @ \@@_env: - ##1 - \l_@@_first_j_tl }
7540     {
7541         \pgfpointanchor { \@@_env: - ##1 - \l_@@_first_j_tl } { west }
7542         \dim_set:Nn \l_@@_x_initial_dim
7543         { \dim_min:nn \l_@@_x_initial_dim \pgf@x }
7544     }
7545     \cs_if_exist:cT
7546     { pgf @ sh @ ns @ \@@_env: - ##1 - \l_@@_last_j_tl }
7547     {
7548         \pgfpointanchor { \@@_env: - ##1 - \l_@@_last_j_tl } { east }
7549         \dim_set:Nn \l_@@_x_final_dim

```

```

7550         { \dim_max:nn \l_@@_x_final_dim \pgf@x }
7551     }
7552 }
7553 \dim_compare:nNnTF \l_@@_x_initial_dim = \c_max_dim
7554 { \@@_error:nn { Impossible~delimiter } { left } }
7555 {
7556     \dim_compare:nNnTF \l_@@_x_final_dim = { - \c_max_dim }
7557     { \@@_error:nn { Impossible~delimiter } { right } }
7558     { \@@_sub_matrix_i:nnnn { #1 } { #4 } { #6 } { #7 } }
7559 }
7560 \endpgfpicture
7561 }
7562 \group_end:
7563 }

```

#1 is the left delimiter, #2 is the right one, #3 is the subscript and #4 is the superscript.

```

7564 \cs_new_protected:Npn \@@_sub_matrix_i:nnnn #1 #2 #3 #4
7565 {
7566     \@@_qpoint:n { row - \l_@@_first_i_tl - base }
7567     \dim_set:Nn \l_@@_y_initial_dim
7568     {
7569         \fp_to_dim:n
7570         {
7571             \pgf@y
7572             + ( \box_ht:N \strutbox + \extrarowheight ) * \arraystretch
7573         }
7574         % modified 6.13c
7575     }
7576     \@@_qpoint:n { row - \l_@@_last_i_tl - base }
7577     \dim_set:Nn \l_@@_y_final_dim
7578     { \fp_to_dim:n { \pgf@y - ( \box_dp:N \strutbox ) * \arraystretch } }
7579     % modified 6.13c
7580     \int_step_inline:nnn \l_@@_first_col_int \g_@@_col_total_int
7581     {
7582         \cs_if_exist:cT
7583         { pgf @ sh @ ns @ \@@_env: - \l_@@_first_i_tl - ##1 }
7584         {
7585             \pgfpointanchor { \@@_env: - \l_@@_first_i_tl - ##1 } { north }
7586             \dim_set:Nn \l_@@_y_initial_dim
7587             { \dim_max:nn \l_@@_y_initial_dim \pgf@y }
7588         }
7589         \cs_if_exist:cT
7590         { pgf @ sh @ ns @ \@@_env: - \l_@@_last_i_tl - ##1 }
7591         {
7592             \pgfpointanchor { \@@_env: - \l_@@_last_i_tl - ##1 } { south }
7593             \dim_set:Nn \l_@@_y_final_dim
7594             { \dim_min:nn \l_@@_y_final_dim \pgf@y }
7595         }
7596     }
7597     \dim_set:Nn \l_tmpa_dim
7598     {
7599         \l_@@_y_initial_dim - \l_@@_y_final_dim +
7600         \l_@@_submatrix_extra_height_dim - \arrayrulewidth
7601     }
7602     \dim_zero:N \nulldelimiterspace

```

We will draw the rules in the \SubMatrix.

```

7602 \group_begin:
7603 \pgfsetlinewidth { 1.1 \arrayrulewidth }
7604 \@@_set_CT@arc@:V \l_@@_rules_color_tl
7605 \CT@arc@

```

Now, we draw the potential vertical rules specified in the preamble of the environments with the letter fixed with the key `vlines-in-sub-matrix`. The list of the columns where there is such rule to draw is in `\g_@@_cols_vlism_seq`.

```

7606   \seq_map_inline:Nn \g_@@_cols_vlism_seq
7607   {
7608     \int_compare:nNnT \l_@@_first_j_tl < { ##1 }
7609     {
7610       \int_compare:nNnT
7611       { ##1 } < { \int_eval:n { \l_@@_last_j_tl + 1 } }
7612       {

```

First, we extract the value of the abscissa of the rule we have to draw.

```

7613         \@@_qpoint:n { col - ##1 }
7614         \pgfpathmoveto { \pgfpoint \pgf@x \l_@@_y_initial_dim }
7615         \pgfpathlineto { \pgfpoint \pgf@x \l_@@_y_final_dim }
7616         \pgfusepathqstroke
7617       }
7618     }
7619   }

```

Now, we draw the vertical rules specified in the key `vlines` of `\SubMatrix`. The last argument of `\int_step_inline:nn` or `\clist_map_inline:Nn` is given by curryfication.

```

7620   \tl_if_eq:NnTF \l_@@_submatrix_vlines_clist { all }
7621   { \int_step_inline:nn { \l_@@_last_j_tl - \l_@@_first_j_tl } }
7622   { \clist_map_inline:Nn \l_@@_submatrix_vlines_clist }
7623   {
7624     \bool_lazy_and:nnTF
7625     { \int_compare_p:nNn { ##1 } > 0 }
7626     {
7627       \int_compare_p:nNn
7628       { ##1 } < { \l_@@_last_j_tl - \l_@@_first_j_tl + 1 } }
7629     {
7630       \@@_qpoint:n { col - \int_eval:n { ##1 + \l_@@_first_j_tl } }
7631       \pgfpathmoveto { \pgfpoint \pgf@x \l_@@_y_initial_dim }
7632       \pgfpathlineto { \pgfpoint \pgf@x \l_@@_y_final_dim }
7633       \pgfusepathqstroke
7634     }
7635     { \@@_error:nnn { Wrong-line-in-SubMatrix } { vertical } { ##1 } }
7636   }

```

Now, we draw the horizontal rules specified in the key `hlines` of `\SubMatrix`. The last argument of `\int_step_inline:nn` or `\clist_map_inline:Nn` is given by curryfication.

```

7637   \tl_if_eq:NnTF \l_@@_submatrix_hlines_clist { all }
7638   { \int_step_inline:nn { \l_@@_last_i_tl - \l_@@_first_i_tl } }
7639   { \clist_map_inline:Nn \l_@@_submatrix_hlines_clist }
7640   {
7641     \bool_lazy_and:nnTF
7642     { \int_compare_p:nNn { ##1 } > 0 }
7643     {
7644       \int_compare_p:nNn
7645       { ##1 } < { \l_@@_last_i_tl - \l_@@_first_i_tl + 1 } }
7646     {
7647       \@@_qpoint:n { row - \int_eval:n { ##1 + \l_@@_first_i_tl } }

```

We use a group to protect `\l_tmpa_dim` and `\l_tmpb_dim`.

```

7648   \group_begin:

```

We compute in `\l_tmpa_dim` the x -value of the left end of the rule.

```

7649       \dim_set:Nn \l_tmpa_dim
7650       { \l_@@_x_initial_dim - \l_@@_submatrix_left_xshift_dim }
7651       \str_case:nn { #1 }
7652       {
7653         ( { \dim_sub:Nn \l_tmpa_dim { 0.9 mm } }
7654         [ { \dim_sub:Nn \l_tmpa_dim { 0.2 mm } }

```

```

7655         \{ { \dim_sub:Nn \l_tmpa_dim { 0.9 mm } }
7656     }
7657     \pgfpathmoveto { \pgfpoint \l_tmpa_dim \pgf@y }
We compute in \l_tmpb_dim the  $x$ -value of the right end of the rule.
7658     \dim_set:Nn \l_tmpb_dim
7659     { \l_@@_x_final_dim + \l_@@_submatrix_right_xshift_dim }
7660     \str_case:nn { #2 }
7661     {
7662         ) { \dim_add:Nn \l_tmpb_dim { 0.9 mm } }
7663         ] { \dim_add:Nn \l_tmpb_dim { 0.2 mm } }
7664         \} { \dim_add:Nn \l_tmpb_dim { 0.9 mm } }
7665     }
7666     \pgfpathlineto { \pgfpoint \l_tmpb_dim \pgf@y }
7667     \pgfusepathqstroke
7668     \group_end:
7669 }
7670 { \@@_error:nnn { Wrong~line~in~SubMatrix } { horizontal } { ##1 } }
7671 }

```

If the key name has been used for the command `\SubMatrix`, we create a PGF node with that name for the submatrix (this node does not encompass the delimiters that we will put after).

```

7672     \str_if_empty:NF \l_@@_submatrix_name_str
7673     {
7674         \@@_pgf_rect_node:nnnn \l_@@_submatrix_name_str
7675         \l_@@_x_initial_dim \l_@@_y_initial_dim
7676         \l_@@_x_final_dim \l_@@_y_final_dim
7677     }
7678     \group_end:

```

The group was for `\CT@arc@` (the color of the rules).

Now, we deal with the left delimiter. Of course, the environment `{pgfscope}` is for the `\pgftransformshift`.

```

7679     \begin { pgfscope }
7680     \pgftransformshift
7681     {
7682         \pgfpoint
7683         { \l_@@_x_initial_dim - \l_@@_submatrix_left_xshift_dim }
7684         { ( \l_@@_y_initial_dim + \l_@@_y_final_dim ) / 2 }
7685     }
7686     \str_if_empty:NTF \l_@@_submatrix_name_str
7687     { \@@_node_left:nn #1 { } }
7688     { \@@_node_left:nn #1 { \@@_env: - \l_@@_submatrix_name_str - left } }
7689     \end { pgfscope }

```

Now, we deal with the right delimiter.

```

7690     \pgftransformshift
7691     {
7692         \pgfpoint
7693         { \l_@@_x_final_dim + \l_@@_submatrix_right_xshift_dim }
7694         { ( \l_@@_y_initial_dim + \l_@@_y_final_dim ) / 2 }
7695     }
7696     \str_if_empty:NTF \l_@@_submatrix_name_str
7697     { \@@_node_right:nnnn #2 { } { #3 } { #4 } }
7698     {
7699         \@@_node_right:nnnn #2
7700         { \@@_env: - \l_@@_submatrix_name_str - right } { #3 } { #4 }
7701     }
7702     \cs_set_eq:NN \pgfpointanchor \@@_pgfpointanchor:n
7703     \flag_clear_new:n { nicematrix }
7704     \l_@@_code_tl
7705 }

```


In the key code of the command `\SubMatrix` there may be Tikz instructions. We want that, in these instructions, the i and j in specifications of nodes of the forms $i-j$, $\text{row-}i$, $\text{col-}j$ and $i-|j$ refer to the number of row and column *relative* of the current `\SubMatrix`. That's why we will patch (locally in the `\SubMatrix`) the command `\pgfpointanchor`.

```
7706 \cs_set_eq:NN \@@_old_pgfpntanchor \pgfpntanchor
```

The following command will be linked to `\pgfpointanchor` just before the execution of the option code of the command `\SubMatrix`. In this command, we catch the argument #1 of `\pgfpointanchor` and we apply to it the command `\@@_pgfpntanchor_i:nn` before passing it to the original `\pgfpointanchor`. We have to act in an expandable way because the command `\pgfpointanchor` is used in names of Tikz nodes which are computed in an expandable way.

```
7707 \cs_new_protected:Npn \@@_pgfpntanchor:n #1
7708 {
7709   \use:e
7710   { \exp_not:N \@@_old_pgfpntanchor { \@@_pgfpntanchor_i:nn #1 } }
7711 }
```

In fact, the argument of `\pgfpointanchor` is always of the form `\a_command { name_of_node }` where “name_of_node” is the name of the Tikz node without the potential prefix and suffix. That's why we catch two arguments and work only on the second by trying (first) to extract an hyphen -.

```
7712 \cs_new:Npn \@@_pgfpntanchor_i:nn #1 #2
7713 { #1 { \@@_pgfpntanchor_ii:w #2 - \q_stop } }
```

Since `\seq_if_in:NnTF` and `\clist_if_in:NnTF` are not expandable, we will use the following token list and `\str_case:nVTF` to test whether we have an integer or not.

```
7714 \tl_const:Nn \c_@@_integers_alist_tl
7715 {
7716   { 1 } { } { 2 } { } { 3 } { } { 4 } { } { 5 } { }
7717   { 6 } { } { 7 } { } { 8 } { } { 9 } { } { 10 } { }
7718   { 11 } { } { 12 } { } { 13 } { } { 14 } { } { 15 } { }
7719   { 16 } { } { 17 } { } { 18 } { } { 19 } { } { 20 } { }
7720 }
```

```
7721 \cs_new:Npn \@@_pgfpntanchor_ii:w #1-#2\q_stop
7722 {
```

If there is no hyphen, that means that the node is of the form of a single number (ex.: 5 or 11). In that case, we are in an analysis which result from a specification of node of the form $i-|j$. In that case, the i of the number of row arrives first (and alone) in a `\pgfpointanchor` and, the, the j arrives (alone) in the following `\pgfpointanchor`. In order to know whether we have a number of row or a number of column, we keep track of the number of such treatments by the expandable flag called `nicematrix`.

```
7723   \tl_if_empty:nTF { #2 }
7724   {
7725     \str_case:nVTF { #1 } \c_@@_integers_alist_tl
7726     {
7727       \flag_raise:n { nicematrix }
7728       \int_if_even:nTF { \flag_height:n { nicematrix } }
7729       { \int_eval:n { #1 + \l_@@_first_i_tl - 1 } }
7730       { \int_eval:n { #1 + \l_@@_first_j_tl - 1 } }
7731     }
7732     { #1 }
7733   }
```

If there is an hyphen, we have to see whether we have a node of the form $i-j$, $\text{row-}i$ or $\text{col-}j$.

```
7734   { \@@_pgfpntanchor_iii:w { #1 } #2 }
7735 }
```

There was an hyphen in the name of the node and that's why we have to retrieve the extra hyphen we have put (cf. `\@@_pgfpointanchor_i:nn`).

```

7736 \cs_new:Npn \@@_pgfpointanchor_iii:w #1 #2 -
7737 {
7738   \str_case:nnF { #1 }
7739   {
7740     { row } { row - \int_eval:n { #2 + \l_@@_first_i_tl - 1 } }
7741     { col } { col - \int_eval:n { #2 + \l_@@_first_j_tl - 1 } }
7742   }

```

Now the case of a node of the form $i-j$.

```

7743 {
7744   \int_eval:n { #1 + \l_@@_first_i_tl - 1 }
7745   - \int_eval:n { #2 + \l_@@_first_j_tl - 1 }
7746 }
7747 }

```

The command `\@@_node_left:nn` puts the left delimiter with the correct size. The argument `#1` is the delimiter to put. The argument `#2` is the name we will give to this PGF node (if the key `name` has been used in `\SubMatrix`).

```

7748 \cs_new_protected:Npn \@@_node_left:nn #1 #2
7749 {
7750   \pgfnode
7751   { rectangle }
7752   { east }
7753   {
7754     \nullfont
7755     \c_math_toggle_token
7756     \@@_color:V \l_@@_delimiters_color_tl
7757     \left #1
7758     \vcenter
7759     {
7760       \nullfont
7761       \hrule \@height \l_tmpa_dim
7762       \@depth \c_zero_dim
7763       \@width \c_zero_dim
7764     }
7765     \right .
7766     \c_math_toggle_token
7767   }
7768   { #2 }
7769   { }
7770 }

```

The command `\@@_node_right:nn` puts the right delimiter with the correct size. The argument `#1` is the delimiter to put. The argument `#2` is the name we will give to this PGF node (if the key `name` has been used in `\SubMatrix`). The argument `#3` is the subscript and `#4` is the superscript.

```

7771 \cs_new_protected:Npn \@@_node_right:nnnn #1 #2 #3 #4
7772 {
7773   \pgfnode
7774   { rectangle }
7775   { west }
7776   {
7777     \nullfont
7778     \c_math_toggle_token
7779     \@@_color:V \l_@@_delimiters_color_tl
7780     \left .
7781     \vcenter
7782     {
7783       \nullfont
7784       \hrule \@height \l_tmpa_dim
7785       \@depth \c_zero_dim
7786       \@width \c_zero_dim

```

```

7787     }
7788     \right #1
7789     \tl_if_empty:nF { #3 } { _ { \smash { #3 } } }
7790     ^ { \smash { #4 } }
7791     \c_math_toggle_token
7792   }
7793   { #2 }
7794   { }
7795 }

```

Les commandes \UnderBrace et \OverBrace

The following commands will be linked to \UnderBrace and \OverBrace in the \CodeAfter.

```

7796 \NewDocumentCommand \@@_UnderBrace { 0 { } m m m 0 { } }
7797 {
7798   \peek_remove_spaces:n
7799   { \@@_brace:nnnnn { #2 } { #3 } { #4 } { #1 , #5 } { under } }
7800 }

7801 \NewDocumentCommand \@@_OverBrace { 0 { } m m m 0 { } }
7802 {
7803   \peek_remove_spaces:n
7804   { \@@_brace:nnnnn { #2 } { #3 } { #4 } { #1 , #5 } { over } }
7805 }

7806 \keys_define:nn { NiceMatrix / Brace }
7807 {
7808   left-shorten .bool_set:N = \l_@@_brace_left_shorten_bool ,
7809   left-shorten .default:n = true ,
7810   right-shorten .bool_set:N = \l_@@_brace_right_shorten_bool ,
7811   shorten .meta:n = { left-shorten , right-shorten } ,
7812   right-shorten .default:n = true ,
7813   yshift .dim_set:N = \l_@@_brace_yshift_dim ,
7814   yshift .value_required:n = true ,
7815   yshift .initial:n = \c_zero_dim ,
7816   color .tl_set:N = \l_tmpa_tl ,
7817   color .value_required:n = true ,
7818   unknown .code:n = \@@_error:n { Unknown~key~for~Brace }
7819 }

```

#1 is the first cell of the rectangle (with the syntax $i-j$; #2 is the last cell of the rectangle; #3 is the label of the text; #4 is the optional argument (a list of *key-value* pairs); #5 is equal to *under* or *over*.

```

7820 \cs_new_protected:Npn \@@_brace:nnnnn #1 #2 #3 #4 #5
7821 {
7822   \group_begin:

```

The four following token lists correspond to the position of the sub-matrix to which a brace will be attached.

```

7823 \@@_compute_i_j:nn { #1 } { #2 }
7824 \bool_lazy_or:nnTF
7825 { \int_compare_p:nNn \l_@@_last_i_tl > \g_@@_row_total_int }
7826 { \int_compare_p:nNn \l_@@_last_j_tl > \g_@@_col_total_int }
7827 {
7828   \str_if_eq:nnTF { #5 } { under }
7829   { \@@_error:nn { Construct~too~large } { \UnderBrace } }
7830   { \@@_error:nn { Construct~too~large } { \OverBrace } }
7831 }
7832 {
7833   \tl_clear:N \l_tmpa_tl
7834   \keys_set:nn { NiceMatrix / Brace } { #4 }
7835   \tl_if_empty:NF \l_tmpa_tl { \color { \l_tmpa_tl } }

```

```

7836 \pgfpicture
7837 \pgfrememberpicturerepositiononpagetrue
7838 \pgf@relevantforpicturesizefalse
7839 \bool_if:NT \l_@@_brace_left_shorten_bool
7840 {
7841   \dim_set_eq:NN \l_@@_x_initial_dim \c_max_dim
7842   \int_step_inline:nnn \l_@@_first_i_tl \l_@@_last_i_tl
7843   {
7844     \cs_if_exist:cT
7845     { pgf @ sh @ ns @ \@@_env: - ##1 - \l_@@_first_j_tl }
7846     {
7847       \pgfpointanchor { \@@_env: - ##1 - \l_@@_first_j_tl } { west }
7848       \dim_set:Nn \l_@@_x_initial_dim
7849       { \dim_min:nn \l_@@_x_initial_dim \pgf@x }
7850     }
7851   }
7852 }
7853 \bool_lazy_or:nnT
7854 { \bool_not_p:n \l_@@_brace_left_shorten_bool }
7855 { \dim_compare_p:nNn \l_@@_x_initial_dim = \c_max_dim }
7856 {
7857   \@@_qpoint:n { col - \l_@@_first_j_tl }
7858   \dim_set_eq:NN \l_@@_x_initial_dim \pgf@x
7859 }
7860 \bool_if:NT \l_@@_brace_right_shorten_bool
7861 {
7862   \dim_set:Nn \l_@@_x_final_dim { - \c_max_dim }
7863   \int_step_inline:nnn \l_@@_first_i_tl \l_@@_last_i_tl
7864   {
7865     \cs_if_exist:cT
7866     { pgf @ sh @ ns @ \@@_env: - ##1 - \l_@@_last_j_tl }
7867     {
7868       \pgfpointanchor { \@@_env: - ##1 - \l_@@_last_j_tl } { east }
7869       \dim_set:Nn \l_@@_x_final_dim
7870       { \dim_max:nn \l_@@_x_final_dim \pgf@x }
7871     }
7872   }
7873 }
7874 \bool_lazy_or:nnT
7875 { \bool_not_p:n \l_@@_brace_right_shorten_bool }
7876 { \dim_compare_p:nNn \l_@@_x_final_dim = { - \c_max_dim } }
7877 {
7878   \@@_qpoint:n { col - \int_eval:n { \l_@@_last_j_tl + 1 } }
7879   \dim_set_eq:NN \l_@@_x_final_dim \pgf@x
7880 }
7881 \pgfset { inner~sep = \c_zero_dim }
7882 \str_if_eq:nnTF { #5 } { under }
7883 { \@@_underbrace_i:n { #3 } }
7884 { \@@_overbrace_i:n { #3 } }
7885 \endpgfpicture
7886 }
7887 \group_end:
7888 }

```

The argument is the text to put above the brace.

```

7889 \cs_new_protected:Npn \@@_overbrace_i:n #1
7890 {
7891   \@@_qpoint:n { row - \l_@@_first_i_tl }
7892   \pgftransformshift
7893   {
7894     \pgfpoint
7895     { ( \l_@@_x_initial_dim + \l_@@_x_final_dim ) / 2 }
7896     { \pgf@y + \l_@@_brace_yshift_dim - 3 pt }
7897   }

```

```

7898 \pgfnode
7899 { rectangle }
7900 { south }
7901 {
7902   \vbox_top:n
7903   {
7904     \group_begin:
7905     \everycr { }
7906     \halign
7907     {
7908       \hfil ## \hfil \crrcr
7909       \@@_math_toggle_token: #1 \@@_math_toggle_token: \cr
7910       \noalign { \skip_vertical:n { 3 pt } \nointerlineskip }
7911       \c_math_toggle_token
7912       \overbrace
7913       {
7914         \hbox_to_wd:nn
7915         { \l_@@_x_final_dim - \l_@@_x_initial_dim }
7916         { }
7917       }
7918       \c_math_toggle_token
7919       \cr
7920     }
7921     \group_end:
7922   }
7923 }
7924 { }
7925 { }
7926 }

```

The argument is the text to put under the brace.

```

7927 \cs_new_protected:Npn \@@_underbrace_i:n #1
7928 {
7929   \@@_qpoint:n { row - \int_eval:n { \l_@@_last_i_tl + 1 } }
7930   \pgftransformshift
7931   {
7932     \pgfpoint
7933     { ( \l_@@_x_initial_dim + \l_@@_x_final_dim ) / 2 }
7934     { \pgf@y - \l_@@_brace_yshift_dim + 3 pt }
7935   }
7936   \pgfnode
7937   { rectangle }
7938   { north }
7939   {
7940     \group_begin:
7941     \everycr { }
7942     \vbox:n
7943     {
7944       \halign
7945       {
7946         \hfil ## \hfil \crrcr
7947         \c_math_toggle_token
7948         \underbrace
7949         {
7950           \hbox_to_wd:nn
7951           { \l_@@_x_final_dim - \l_@@_x_initial_dim }
7952           { }
7953         }
7954         \c_math_toggle_token
7955         \cr
7956         \noalign { \skip_vertical:n { 3 pt } \nointerlineskip }
7957         \@@_math_toggle_token: #1 \@@_math_toggle_token: \cr
7958       }
7959     }

```

```

7960     \group_end:
7961 }
7962 { }
7963 { }
7964 }

```

The command \ShowCellNames

```

7965 \NewDocumentCommand \@@_ShowCellNames_CodeBefore { }
7966 {
7967   \dim_zero_new:N \g_@@_tmpc_dim
7968   \dim_zero_new:N \g_@@_tmpd_dim
7969   \dim_zero_new:N \g_@@_tmpe_dim
7970   \int_step_inline:nn \c@iRow
7971   {
7972     \begin { pgfpicture }
7973     \@@_qpoint:n { row - ##1 }
7974     \dim_set_eq:NN \l_tmpa_dim \pgf@y
7975     \@@_qpoint:n { row - \int_eval:n { ##1 + 1 } }
7976     \dim_gset:Nn \g_tmpa_dim { ( \l_tmpa_dim + \pgf@y ) / 2 }
7977     \dim_gset:Nn \g_tmpb_dim { \l_tmpa_dim - \pgf@y }
7978     \bool_if:NTF \l_@@_in_code_after_bool
7979     \end { pgfpicture }
7980     \int_step_inline:nn \c@jCol
7981     {
7982       \hbox_set:Nn \l_tmpa_box
7983       { \normalfont \Large \color { red ! 50 } ##1 - ####1 }
7984       \begin { pgfpicture }
7985       \@@_qpoint:n { col - ####1 }
7986       \dim_gset_eq:NN \g_@@_tmpc_dim \pgf@x
7987       \@@_qpoint:n { col - \int_eval:n { ####1 + 1 } }
7988       \dim_gset:Nn \g_@@_tmpd_dim { \pgf@x - \g_@@_tmpc_dim }
7989       \dim_gset_eq:NN \g_@@_tmpe_dim \pgf@x
7990       \endpgfpicture
7991       \end { pgfpicture }
7992       \fp_set:Nn \l_tmpa_fp
7993       {
7994         \fp_min:nn
7995         {
7996           \fp_min:nn
7997           { \dim_ratio:nn { \g_@@_tmpd_dim } { \box_wd:N \l_tmpa_box } }
7998           { \dim_ratio:nn { \g_tmpb_dim } { \box_ht_plus_dp:N \l_tmpa_box } }
7999         }
8000         { 1.0 }
8001       }
8002       \box_scale:Nnn \l_tmpa_box { \fp_use:N \l_tmpa_fp } { \fp_use:N \l_tmpa_fp }
8003       \pgfpicture
8004       \pgfrememberpicturepositiononpagetrue
8005       \pgf@relevantforpicturesizefalse
8006       \pgftransformshift
8007       {
8008         \pgfpoint
8009         { 0.5 * ( \g_@@_tmpc_dim + \g_@@_tmpe_dim ) }
8010         { \dim_use:N \g_tmpa_dim }
8011       }
8012       \pgfnode
8013       { rectangle }
8014       { center }
8015       { \box_use:N \l_tmpa_box }
8016       { }
8017       { }
8018       \endpgfpicture

```

```

8019     }
8020   }
8021 }

8022 \NewDocumentCommand \@@_ShowCellNames { }
8023 {
8024   \bool_if:NT \l_@@_in_code_after_bool
8025   {
8026     \pgfpicture
8027     \pgfrememberpicturepositiononpagetrue
8028     \pgf@relevantforpicturesizefalse
8029     \pgfpathrectanglecorners
8030     { \@@_qpoint:n { 1 } }
8031     { \@@_qpoint:n { \int_eval:n { \c@iRow + 1 } } }
8032     \pgfsetfillopacity { 0.75 }
8033     \pgfsetfillcolor { white }
8034     \pgfusepathqfill
8035     \endpgfpicture
8036   }
8037   \dim_zero_new:N \g_@@_tmpc_dim
8038   \dim_zero_new:N \g_@@_tmpd_dim
8039   \dim_zero_new:N \g_@@_tmpe_dim
8040   \int_step_inline:nn \c@iRow
8041   {
8042     \bool_if:NTF \l_@@_in_code_after_bool
8043     {
8044       \pgfpicture
8045       \pgfrememberpicturepositiononpagetrue
8046       \pgf@relevantforpicturesizefalse
8047     }
8048     { \begin { pgfpicture } }
8049     \@@_qpoint:n { row - ##1 }
8050     \dim_set_eq:NN \l_tmpa_dim \pgf@y
8051     \@@_qpoint:n { row - \int_eval:n { ##1 + 1 } }
8052     \dim_gset:Nn \g_tmpa_dim { ( \l_tmpa_dim + \pgf@y ) / 2 }
8053     \dim_gset:Nn \g_tmpb_dim { \l_tmpa_dim - \pgf@y }
8054     \bool_if:NTF \l_@@_in_code_after_bool
8055     { \endpgfpicture }
8056     { \end { pgfpicture } }
8057     \int_step_inline:nn \c@jCol
8058     {
8059       \hbox_set:Nn \l_tmpa_box
8060       {
8061         \normalfont \Large \sffamily \bfseries
8062         \bool_if:NTF \l_@@_in_code_after_bool
8063         { \color { red } }
8064         { \color { red ! 50 } }
8065         ##1 - ####1
8066       }
8067       \bool_if:NTF \l_@@_in_code_after_bool
8068       {
8069         \pgfpicture
8070         \pgfrememberpicturepositiononpagetrue
8071         \pgf@relevantforpicturesizefalse
8072       }
8073       { \begin { pgfpicture } }
8074       \@@_qpoint:n { col - ####1 }
8075       \dim_gset_eq:NN \g_@@_tmpc_dim \pgf@x
8076       \@@_qpoint:n { col - \int_eval:n { ####1 + 1 } }
8077       \dim_gset:Nn \g_@@_tmpd_dim { \pgf@x - \g_@@_tmpc_dim }
8078       \dim_gset_eq:NN \g_@@_tmpe_dim \pgf@x
8079       \bool_if:NTF \l_@@_in_code_after_bool
8080       { \endpgfpicture }
8081       { \end { pgfpicture } }

```

```

8082 \fp_set:Nn \l_tmpa_fp
8083 {
8084   \fp_min:nn
8085   {
8086     \fp_min:nn
8087     { \dim_ratio:nn { \g_@@_tmpd_dim } { \box_wd:N \l_tmpa_box } }
8088     { \dim_ratio:nn { \g_tmpe_dim } { \box_ht_plus_dp:N \l_tmpa_box } }
8089   }
8090   { 1.0 }
8091 }
8092 \box_scale:Nnn \l_tmpa_box { \fp_use:N \l_tmpa_fp } { \fp_use:N \l_tmpa_fp }
8093 \pgfpicture
8094 \pgfrememberpicturepositiononpagetrue
8095 \pgf@relevantforpicturesizefalse
8096 \pgftransformshift
8097 {
8098   \pgfpoint
8099   { 0.5 * ( \g_@@_tmpc_dim + \g_@@_tmpe_dim ) }
8100   { \dim_use:N \g_tmpa_dim }
8101 }
8102 \pgfnode
8103 { rectangle }
8104 { center }
8105 { \box_use:N \l_tmpa_box }
8106 { }
8107 { }
8108 \endpgfpicture
8109 }
8110 }
8111 }

```

We process the options at package loading

We process the options when the package is loaded (with `\usepackage`) but we recommend to use `\NiceMatrixOptions` instead.

We must process these options after the definition of the environment `{NiceMatrix}` because the option `renew-matrix` executes the code `\cs_set_eq:NN \env@matrix \NiceMatrix`.

Of course, the command `\NiceMatrix` must be defined before such an instruction is executed.

The boolean `\g_@@_footnotehyper_bool` will indicate if the option `footnotehyper` is used.

```

8112 \bool_new:N \c_@@_footnotehyper_bool

```

The boolean `\c_@@_footnote_bool` will indicate if the option `footnote` is used, but quickly, it will also be set to true if the option `footnotehyper` is used.

```

8113 \bool_new:N \c_@@_footnote_bool

8114 \msg_new:nnnn { nicematrix } { Unknown-key-for-package }
8115 {
8116   The~key~'\l_keys_key_str'~is~unknown. \\
8117   That~key~will~be~ignored. \\
8118   For~a~list~of~the~available~keys,~type~H~<return>.
8119 }
8120 {
8121   The~available~keys~are~(in~alphabetic~order):~
8122   footnote,~
8123   footnotehyper,~
8124   messages-for-Overleaf,~
8125   no-test-for-array,~
8126   renew-dots,~and
8127   renew-matrix.
8128 }

```



```

8129 \keys_define:nn { NiceMatrix / Package }
8130 {
8131   renew-dots .bool_set:N = \l_@@_renew_dots_bool ,
8132   renew-dots .value_forbidden:n = true ,
8133   renew-matrix .code:n = \@@_renew_matrix: ,
8134   renew-matrix .value_forbidden:n = true ,
8135   messages-for-Overleaf .bool_set:N = \c_@@_messages_for_Overleaf_bool ,
8136   footnote .bool_set:N = \c_@@_footnote_bool ,
8137   footnotehyper .bool_set:N = \c_@@_footnotehyper_bool ,
8138   no-test-for-array .bool_set:N = \c_@@_no_test_for_array_bool ,
8139   no-test-for-array .default:n = true ,
8140   unknown .code:n = \@@_error:n { Unknown-key-for-package }
8141 }
8142 \ProcessKeysOptions { NiceMatrix / Package }

8143 \@@_msg_new:nn { footnote-with-footnotehyper-package }
8144 {
8145   You~can't~use~the~option~'footnote'~because~the~package~
8146   footnotehyper~has~already~been~loaded.~
8147   If~you~want,~you~can~use~the~option~'footnotehyper'~and~the~footnotes~
8148   within~the~environments~of~nicematrix~will~be~extracted~with~the~tools~
8149   of~the~package~footnotehyper.\\
8150   The~package~footnote~won't~be~loaded.
8151 }

8152 \@@_msg_new:nn { footnotehyper-with-footnote-package }
8153 {
8154   You~can't~use~the~option~'footnotehyper'~because~the~package~
8155   footnote~has~already~been~loaded.~
8156   If~you~want,~you~can~use~the~option~'footnote'~and~the~footnotes~
8157   within~the~environments~of~nicematrix~will~be~extracted~with~the~tools~
8158   of~the~package~footnote.\\
8159   The~package~footnotehyper~won't~be~loaded.
8160 }

8161 \bool_if:NT \c_@@_footnote_bool
8162 {

```

The class beamer has its own system to extract footnotes and that's why we have nothing to do if beamer is used.

```

8163   \@ifclassloaded { beamer }
8164   { \bool_set_false:N \c_@@_footnote_bool }
8165   {
8166     \@ifpackageloaded { footnotehyper }
8167     { \@@_error:n { footnote-with-footnotehyper-package } }
8168     { \usepackage { footnote } }
8169   }
8170 }

8171 \bool_if:NT \c_@@_footnotehyper_bool
8172 {

```

The class beamer has its own system to extract footnotes and that's why we have nothing to do if beamer is used.

```

8173   \@ifclassloaded { beamer }
8174   { \bool_set_false:N \c_@@_footnote_bool }
8175   {
8176     \@ifpackageloaded { footnote }
8177     { \@@_error:n { footnotehyper-with-footnote-package } }
8178     { \usepackage { footnotehyper } }
8179   }
8180   \bool_set_true:N \c_@@_footnote_bool
8181 }

```

The flag `\c_@@_footnote_bool` is raised and so, we will only have to test `\c_@@_footnote_bool` in order to know if we have to insert an environment `{savenotes}`.

About the package underscore

```

8182 \bool_new:N \l_@@_underscore_loaded_bool
8183 \ifpackageloaded { underscore }
8184 { \bool_set_true:N \l_@@_underscore_loaded_bool }
8185 { }

8186 \hook_gput_code:nnn { begindocument } { . }
8187 {
8188   \bool_if:NF \l_@@_underscore_loaded_bool
8189   {
8190     \ifpackageloaded { underscore }
8191     { \@@_error:n { underscore~after~nicematrix } }
8192   }
8193 }

```

Error messages of the package

```

8194 \bool_if:NTF \c_@@_messages_for_Overleaf_bool
8195 { \str_const:Nn \c_@@_available_keys_str { } }
8196 {
8197   \str_const:Nn \c_@@_available_keys_str
8198   { For~a~list~of~the~available~keys,~type~H~<return>. }
8199 }

8200 \seq_new:N \g_@@_types_of_matrix_seq
8201 \seq_gset_from_clist:Nn \g_@@_types_of_matrix_seq
8202 {
8203   NiceMatrix ,
8204   pNiceMatrix , bNiceMatrix , vNiceMatrix, BNiceMatrix, VNiceMatrix
8205 }
8206 \seq_gset_map_x:NNn \g_@@_types_of_matrix_seq \g_@@_types_of_matrix_seq
8207 { \tl_to_str:n { #1 } }

```

If the user uses too much columns, the command `\@@_error_too_much_cols:` is triggered. This command raises an error but also tries to give the best information to the user in the error message. The command `\seq_if_in:NVTF` is not expandable and that's why we can't put it in the error message itself. We have to do the test before the `\@@_fatal:n`.

```

8208 \cs_new_protected:Npn \@@_error_too_much_cols:
8209 {
8210   \seq_if_in:NVTF \g_@@_types_of_matrix_seq \g_@@_name_env_str
8211   {
8212     \int_compare:nNnTF \l_@@_last_col_int = { -2 }
8213     { \@@_fatal:n { too~much~cols~for~matrix } }
8214     {
8215       \bool_if:NF \l_@@_last_col_without_value_bool
8216       { \@@_fatal:n { too~much~cols~for~matrix~with~last~col } }
8217     }
8218   }
8219   { \@@_fatal:n { too~much~cols~for~array } }
8220 }

```

The following command must *not* be protected since it's used in an error message.

```

8221 \cs_new:Npn \@@_message_hdotsfor:
8222 {
8223   \tl_if_empty:VF \g_@@_HVdotsfor_lines_tl
8224   { ~Maybe~your~use~of~\token_to_str:N \Hdotsfor\ is~incorrect.}
8225 }
8226 \@@_msg_new:nn { negative~weight }

```

```

8227 {
8228   Negative-weight.\
8229   The~weight~of~the~'X'~columns~must~be~positive~and~you~have~used~
8230   the~value~'\int_use:N \l_@@_weight_int'.\
8231   The~absolute~value~will~be~used.
8232 }
8233 \@@_msg_new:nn { last~col~not~used }
8234 {
8235   Column~not~used.\
8236   The~key~'last-col'~is~in~force~but~you~have~not~used~that~last~column~
8237   in~your~\@@_full_name_env:~.~However,~you~can~go~on.
8238 }
8239 \@@_msg_new:nn { too~much~cols~for~matrix~with~last~col }
8240 {
8241   Too~much~columns.\
8242   In~the~row~\int_eval:n { \c@iRow - 1 },~
8243   you~try~to~use~more~columns~
8244   than~allowed~by~your~\@@_full_name_env:~.\@@_message_hdotsfor:\
8245   The~maximal~number~of~columns~is~\int_eval:n { \l_@@_last_col_int - 1 }~
8246   (plus~the~exterior~columns).~This~error~is~fatal.
8247 }
8248 \@@_msg_new:nn { too~much~cols~for~matrix }
8249 {
8250   Too~much~columns.\
8251   In~the~row~\int_eval:n { \c@jCol - 1 },~
8252   you~try~to~use~more~columns~than~allowed~by~your~
8253   \@@_full_name_env:~.\@@_message_hdotsfor:\ Recall~that~the~maximal~
8254   number~of~columns~for~a~matrix~is~fixed~by~the~LaTeX~counter~
8255   'MaxMatrixCols'.~Its~current~value~is~\int_use:N \c@MaxMatrixCols.~
8256   This~error~is~fatal.
8257 }

```

For the following message, remind that the test is not done after the construction of the array but in each row. That's why we have to put `\c@jCol-1` and not `\c@jCol`.

```

8258 \@@_msg_new:nn { too~much~cols~for~array }
8259 {
8260   Too~much~columns.\
8261   In~the~row~\int_eval:n { \c@jCol - 1 },~
8262   ~you~try~to~use~more~columns~than~allowed~by~your~
8263   \@@_full_name_env:~.\@@_message_hdotsfor:\ The~maximal~number~of~columns~is~
8264   \int_use:N \g_@@_static_num_of_col_int\
8265   ~(plus~the~potential~exterior~ones).~
8266   This~error~is~fatal.
8267 }
8268 \@@_msg_new:nn { columns~not~used }
8269 {
8270   Columns~not~used.\
8271   The~preamble~of~your~\@@_full_name_env:\ announces~\int_use:N
8272   \g_@@_static_num_of_col_int\ columns~but~you~use~only~\int_use:N \c@jCol.\
8273   The~columns~you~did~not~used~won't~be~created.\
8274   We~won't~have~similar~error~till~the~end~of~the~document.
8275 }
8276 \@@_msg_new:nn { in~first~col }
8277 {
8278   Erroneous~use.\
8279   You~can't~use~the~command~#1 in~the~first~column~(number~0)~of~the~array.\
8280   That~command~will~be~ignored.
8281 }
8282 \@@_msg_new:nn { in~last~col }
8283 {
8284   Erroneous~use.\

```

```

8285     You~can't~use~the~command~#1~in~the~last~column~(exterior)~of~the~array.\\
8286     That~command~will~be~ignored.
8287 }
8288 \@@_msg_new:nn { in~first~row }
8289 {
8290     Erroneous~use.\\
8291     You~can't~use~the~command~#1~in~the~first~row~(number~0)~of~the~array.\\
8292     That~command~will~be~ignored.
8293 }
8294 \@@_msg_new:nn { in~last~row }
8295 {
8296     You~can't~use~the~command~#1~in~the~last~row~(exterior)~of~the~array.\\
8297     That~command~will~be~ignored.
8298 }
8299 \@@_msg_new:nn { caption~outside~float }
8300 {
8301     Key~caption~forbidden.\\
8302     You~can't~use~the~key~'caption'~because~you~are~not~in~a~floating~
8303     environment.~This~key~will~be~ignored.
8304 }
8305 \@@_msg_new:nn { short~caption~without~caption }
8306 {
8307     You~should~not~use~the~key~'short~caption'~without~'caption'.~
8308     However,~your~'short~caption'~will~be~used~as~'caption'.
8309 }
8310 \@@_msg_new:nn { double~closing~delimiter }
8311 {
8312     Double~delimiter.\\
8313     You~can't~put~a~second~closing~delimiter~"#1"~just~after~a~first~closing~
8314     delimiter.~This~delimiter~will~be~ignored.
8315 }
8316 \@@_msg_new:nn { delimiter~after~opening }
8317 {
8318     Double~delimiter.\\
8319     You~can't~put~a~second~delimiter~"#1"~just~after~a~first~opening~
8320     delimiter.~That~delimiter~will~be~ignored.
8321 }
8322 \@@_msg_new:nn { bad~option~for~line~style }
8323 {
8324     Bad~line~style.\\
8325     Since~you~haven't~loaded~Tikz,~the~only~value~you~can~give~to~'line~style'~
8326     is~'standard'.~That~key~will~be~ignored.
8327 }
8328 \@@_msg_new:nn { Identical~notes~in~caption }
8329 {
8330     Identical~tabular~notes.\\
8331     You~can't~put~several~notes~with~the~same~content~in~
8332     \token_to_str:N \caption\ (but~you~can~in~the~main~tabular).\\
8333     If~you~go~on,~the~output~will~probably~be~erroneous.
8334 }
8335 \@@_msg_new:nn { tabularnote~below~the~tabular }
8336 {
8337     \token_to_str:N \tabularnote\ forbidden\\
8338     You~can't~use~\token_to_str:N \tabularnote\ in~the~caption~
8339     of~your~tabular~because~the~caption~will~be~composed~below~
8340     the~tabular.~If~you~want~the~caption~above~the~tabular~use~the~
8341     key~'caption~above'~in~\token_to_str:N \NiceMatrixOptions.\\
8342     Your~\token_to_str:N \tabularnote\ will~be~discarded~and~
8343     no~similar~error~will~raised~in~this~document.
8344 }

```

```

8345 \@@_msg_new:nn { Unknown-key-for-rules }
8346 {
8347   Unknown~key.\\
8348   There-is-only-two-keys-available-here:~width~and~color.\\
8349   You-key~'\l_keys_key_str'~will~be~ignored.
8350 }
8351 \@@_msg_new:nnn { Unknown-key-for-custom-line }
8352 {
8353   Unknown~key.\\
8354   The-key~'\l_keys_key_str'~is-unknown-in-a~'custom-line'.~
8355   It-you-go-on,~you-will-probably-have-other-errors. \\
8356   \c_@@_available_keys_str
8357 }
8358 {
8359   The~available-keys-are~(in~alphabetic~order):~
8360   ccommand,~
8361   color,~
8362   command,~
8363   dotted,~
8364   letter,~
8365   multiplicity,~
8366   sep-color,~
8367   tikz,~and~total-width.
8368 }
8369 \@@_msg_new:nnn { Unknown-key-for~xdots }
8370 {
8371   Unknown~key.\\
8372   The-key~'\l_keys_key_str'~is-unknown-for~a~command~for~drawing~dotted~rules.\\
8373   \c_@@_available_keys_str
8374 }
8375 {
8376   The~available-keys-are~(in~alphabetic~order):~
8377   'color',~
8378   'inter',~
8379   'line-style',~
8380   'radius',~
8381   'shorten',~
8382   'shorten-end'~and~'shorten-start'.
8383 }
8384 \@@_msg_new:nn { Unknown-key-for-rowcolors }
8385 {
8386   Unknown~key.\\
8387   As~for~now,~there-is-only-two-keys-available-here:~'cols'~and~'respect-blocks'~
8388   (and~you~try~to~use~'\l_keys_key_str')\\
8389   That~key~will~be~ignored.
8390 }
8391 \@@_msg_new:nn { label-without-caption }
8392 {
8393   You-can't-use-the-key~'label'~in~your~'{NiceTabular}'~because~
8394   you~have~not~used~the-key~'caption'.~The-key~'label'~will~be~ignored.
8395 }
8396 \@@_msg_new:nn { W-warning }
8397 {
8398   Line~\msg_line_number:~The-cell-is-too-wide-for-your-column~'W'~
8399   (row~\int_use:N \c@iRow).
8400 }
8401 \@@_msg_new:nn { Construct-too-large }
8402 {
8403   Construct-too-large.\\
8404   Your~command~\token_to_str:N #1
8405   can't-be-drawn-because~your~matrix~is~too~small.\\

```

```

8406     That~command~will~be~ignored.
8407 }

8408 \@@_msg_new:nn { underscore~after~nicematrix }
8409 {
8410     Problem~with~'underscore'.\\
8411     The~package~'underscore'~should~be~loaded~before~'nicematrix'.~
8412     You~can~go~on~but~you~won't~be~able~to~write~something~such~as:\\
8413     '\token_to_str:N \Cdots\token_to_str:N _{n~\token_to_str:N \text{~times}}'.
8414 }

8415 \@@_msg_new:nn { ampersand~in~light~syntax }
8416 {
8417     Ampersand~forbidden.\\
8418     You~can't~use~an~ampersand~(\token_to_str:N &)~to~separate~columns~because~
8419     ~the~key~'light~syntax'~is~in~force.~This~error~is~fatal.
8420 }

8421 \@@_msg_new:nn { double~backslash~in~light~syntax }
8422 {
8423     Double~backslash~forbidden.\\
8424     You~can't~use~\token_to_str:N
8425     \\~to~separate~rows~because~the~key~'light~syntax'~
8426     is~in~force.~You~must~use~the~character~'\l_@@_end_of_row_tl'~
8427     (set~by~the~key~'end-of-row').~This~error~is~fatal.
8428 }

8429 \@@_msg_new:nn { hlines~with~color }
8430 {
8431     Incompatible~keys.\\
8432     You~can't~use~the~keys~'hlines',~'vlines'~or~'hvlines'~for~a~
8433     '\token_to_str:N \Block'~when~the~key~'color'~or~'draw'~is~used.\\
8434     Maybe~it~will~possible~in~future~version.\\
8435     Your~key~will~be~discarded.
8436 }

8437 \@@_msg_new:nn { bad~value~for~baseline }
8438 {
8439     Bad~value~for~baseline.\\
8440     The~value~given~to~'baseline'~(\int_use:N \l_tmpa_int)~is~not~
8441     valid.~The~value~must~be~between~\int_use:N \l_@@_first_row_int\ and~
8442     \int_use:N \g_@@_row_total_int\ or~equal~to~'t',~'c'~or~'b'~or~of~
8443     the~form~'line-i'.\\
8444     A~value~of~1~will~be~used.
8445 }

8446 \@@_msg_new:nn { ragged2e~not~loaded }
8447 {
8448     You~have~to~load~'ragged2e'~in~order~to~use~the~key~'\l_keys_key_str'~in~
8449     your~column~'\l_@@_vpos_col_str'~(or~'X').~The~key~'\str_lowercase:V
8450     \l_keys_key_str'~will~be~used~instead.
8451 }

8452 \@@_msg_new:nn { Invalid~name }
8453 {
8454     Invalid~name.\\
8455     You~can't~give~the~name~'\l_keys_value_tl'~to~a~\token_to_str:N
8456     \SubMatrix\ of~your~\@@_full_name_env:.\\
8457     A~name~must~be~accepted~by~the~regular~expression~[A-Za-z][A-Za-z0-9]*.\\
8458     This~key~will~be~ignored.
8459 }

8460 \@@_msg_new:nn { Wrong~line~in~SubMatrix }
8461 {
8462     Wrong~line.\\
8463     You~try~to~draw~a~#1~line~of~number~'#2'~in~a~
8464     \token_to_str:N \SubMatrix\ of~your~\@@_full_name_env:\ but~that~
8465     number~is~not~valid.~It~will~be~ignored.

```

```

8466     }
8467 \@@_msg_new:nn { Impossible-delimiter }
8468 {
8469     Impossible-delimiter.\\
8470     It's-impossible-to-draw-the-#1-delimiter-of-your-
8471     \token_to_str:N \SubMatrix\ because-all-the-cells-are-empty-
8472     in-that-column.
8473     \bool_if:NT \l_@@_submatrix_slim_bool
8474     { ~Maybe-you-should-try-without-the-key-'slim'. } \\
8475     This-\token_to_str:N \SubMatrix\ will-be-ignored.
8476 }
8477 \@@_msg_new:nn { width-without-X-columns }
8478 {
8479     You-have-used-the-key-'width'~but-you-have-put-no-'X'~column.~
8480     That-key-will-be-ignored.
8481 }
8482 \@@_msg_new:nn { key-multiplicity-with-dotted }
8483 {
8484     Incompatible-keys. \\
8485     You-have-used-the-key-'multiplicity'~with-the-key-'dotted'~
8486     in-a-'custom-line'.~They-are-incompatible. \\
8487     The-key-'multiplicity'~will-be-discarded.
8488 }
8489 \@@_msg_new:nn { empty-environment }
8490 {
8491     Empty-environment.\\
8492     Your-\@@_full_name_env:\ is-empty.~This-error-is-fatal.
8493 }
8494 \@@_msg_new:nn { Wrong-use-of-v-center }
8495 {
8496     Wrong-use-of-v-center.\\
8497     You-should-not-use-the-key-'v-center'~here-because-your-block-is-not~
8498     mono-row.~However,~you-can-go-on.
8499 }
8500 \@@_msg_new:nn { No-letter-and-no-command }
8501 {
8502     Erroneous-use.\\
8503     Your-use-of-'custom-line'~is-no-op-since-you-don't-have-used-the~
8504     key-'letter'~(for-a-letter-for-vertical-rules)~nor-the-keys-'command'~or~
8505     ~'ccommand'~(to-draw-horizontal-rules).\\
8506     However,~you-can-go-on.
8507 }
8508 \@@_msg_new:nn { Forbidden-letter }
8509 {
8510     Forbidden-letter.\\
8511     You-can't-use-the-letter~'\l_@@_letter_str'~for-a-customized-line.\\
8512     It-will-be-ignored.
8513 }
8514 \@@_msg_new:nn { Several-letters }
8515 {
8516     Wrong-name.\\
8517     You-must-use-only-one-letter-as-value-for-the-key-'letter'~(and-you-
8518     have-used~'\l_@@_letter_str').\\
8519     It-will-be-ignored.
8520 }
8521 \@@_msg_new:nn { Delimiter-with-small }
8522 {
8523     Delimiter-forbidden.\\
8524     You-can't-put-a-delimiter-in-the-preamble-of-your-\@@_full_name_env:\
8525     because-the-key-'small'~is-in-force.\\

```

```

8526     This-error-is-fatal.
8527 }

8528 \@@_msg_new:nn { unknown-cell-for-line-in-CodeAfter }
8529 {
8530     Unknown-cell.\\
8531     Your-command~\token_to_str:N\line\{#1\}\{#2\}~in~
8532     the~\token_to_str:N \CodeAfter\ of~your~\@@_full_name_env:\
8533     can't-be-executed-because-a-cell~doesn't-exist.\\
8534     This-command~\token_to_str:N \line\ will-be-ignored.
8535 }

8536 \@@_msg_new:nnn { Duplicate-name-for-SubMatrix }
8537 {
8538     Duplicate-name.\\
8539     The-name~'#1'~is~already-used-for-a~\token_to_str:N \SubMatrix\
8540     in~this~\@@_full_name_env:.\
8541     This-key~will-be-ignored.\\
8542     \bool_if:NF \c_@@_messages_for_Overleaf_bool
8543     { For~a-list-of~the~names~already-used,~type~H~<return>. }
8544 }
8545 {
8546     The~names~already-defined-in~this~\@@_full_name_env:\ are:~
8547     \seq_use:Nnnn \g_@@_submatrix_names_seq { ~and~ } { ,~ } { ~and~ }.
8548 }

8549 \@@_msg_new:nn { r-or-l-with-preamble }
8550 {
8551     Erroneous-use.\\
8552     You-can't-use-the-key~'\l_keys_key_str'~in~your~\@@_full_name_env:~
8553     You-must-specify-the~alignment~of~your~columns~with~the~preamble~of~
8554     your~\@@_full_name_env:.\
8555     This-key~will-be-ignored.
8556 }

8557 \@@_msg_new:nn { Hdotsfor-in-col-0 }
8558 {
8559     Erroneous-use.\\
8560     You-can't-use~\token_to_str:N \Hdotsfor\ in~an~exterior~column~of~
8561     the~array.~This-error-is-fatal.
8562 }

8563 \@@_msg_new:nn { bad-corner }
8564 {
8565     Bad-corner.\\
8566     #1~is~an~incorrect~specification~for~a~corner~(in~the~key~
8567     'corners').~The~available~values~are:~NW,~SW,~NE~and~SE.\\
8568     This~specification~of~corner~will-be-ignored.
8569 }

8570 \@@_msg_new:nn { bad-border }
8571 {
8572     Bad-border.\\
8573     \l_keys_key_str\space~is~an~incorrect~specification~for~a~border~
8574     (in~the~key~'borders'~of~the~command~\token_to_str:N \Block).~
8575     The~available~values~are:~left,~right,~top~and~bottom~(and~you~can~
8576     also~use~the~key~'tikz'
8577     \bool_if:nF \c_@@_tikz_loaded_bool
8578     {~if~you~load~the~LaTeX~package~'tikz'}).\\
8579     This~specification~of~border~will-be-ignored.
8580 }

8581 \@@_msg_new:nn { tikz-key-without-tikz }
8582 {
8583     Tikz-not-loaded.\\
8584     You-can't-use-the-key~'tikz'~for~the~command~'\token_to_str:N
8585     \Block'~because~you~have~not~loaded~tikz.~
8586     This-key~will-be-ignored.

```



```

8587 }
8588 \@@_msg_new:nn { last-col~non-empty~for~NiceArray }
8589 {
8590   Erroneous-use.\
8591   In~the~\@@_full_name_env:,~you~must~use~the~key~
8592   'last-col'~without~value.\
8593   However,~you~can~go~on~for~this~time~
8594   (the~value~'\l_keys_value_tl'~will~be~ignored).
8595 }
8596 \@@_msg_new:nn { last-col~non-empty~for~NiceMatrixOptions }
8597 {
8598   Erroneous-use.\
8599   In~\NiceMatrixoptions,~you~must~use~the~key~
8600   'last-col'~without~value.\
8601   However,~you~can~go~on~for~this~time~
8602   (the~value~'\l_keys_value_tl'~will~be~ignored).
8603 }
8604 \@@_msg_new:nn { Block~too~large-1 }
8605 {
8606   Block~too~large.\
8607   You~try~to~draw~a~block~in~the~cell~#1-#2~of~your~matrix~but~the~matrix~is~
8608   too~small~for~that~block. \
8609 }
8610 \@@_msg_new:nn { Block~too~large-2 }
8611 {
8612   Block~too~large.\
8613   The~preamble~of~your~\@@_full_name_env:\ announces~\int_use:N
8614   \g_@@_static_num_of_col_int\
8615   columns~but~you~use~only~\int_use:N \c@jCol\ and~that's~why~a~block~
8616   specified~in~the~cell~#1-#2~can't~be~drawn.~You~should~add~some~ampersands~
8617   (&)~at~the~end~of~the~first~row~of~your~
8618   \@@_full_name_env:.\
8619   This~block~and~maybe~others~will~be~ignored.
8620 }
8621 \@@_msg_new:nn { unknown~column~type }
8622 {
8623   Bad~column~type.\
8624   The~column~type~'#1'~in~your~\@@_full_name_env:\
8625   is~unknown. \
8626   This~error~is~fatal.
8627 }
8628 \@@_msg_new:nn { tabularnote~forbidden }
8629 {
8630   Forbidden~command.\
8631   You~can't~use~the~command~\token_to_str:N\ tabularnote\
8632   ~here.~This~command~is~available~only~in~
8633   \{NiceTabular\},~\{NiceTabular*\}~and~\{NiceTabularX\}~or~in~
8634   the~argument~of~a~command~\token_to_str:N \caption\ included~
8635   in~an~environment~{table}. \
8636   This~command~will~be~ignored.
8637 }
8638 \@@_msg_new:nn { borders~forbidden }
8639 {
8640   Forbidden~key.\
8641   You~can't~use~the~key~'borders'~of~the~command~\token_to_str:N \Block\
8642   because~the~option~'rounded-corners'~
8643   is~in~force~with~a~non-zero~value.\
8644   This~key~will~be~ignored.
8645 }
8646 \@@_msg_new:nn { bottomrule~without~booktabs }

```

```

8647 {
8648   booktabs~not~loaded.\\
8649   You~can't~use~the~key~'tabular/bottomrule'~because~you~haven't~
8650   loaded~'booktabs'.\\
8651   This~key~will~be~ignored.
8652 }

8653 \@@_msg_new:nn { enumitem~not~loaded }
8654 {
8655   enumitem~not~loaded.\\
8656   You~can't~use~the~command~\token_to_str:N\tabularnote\
8657   ~because~you~haven't~loaded~'enumitem'.\\
8658   All~the~commands~\token_to_str:N\tabularnote\ will~be~
8659   ignored~in~the~document.
8660 }

8661 \@@_msg_new:nn { tikz~in~custom~line~without~tikz }
8662 {
8663   Tikz~not~loaded.\\
8664   You~have~used~the~key~'tikz'~in~the~definition~of~a~
8665   customized~line~(with~'custom~line')~but~tikz~is~not~loaded.~
8666   You~can~go~on~but~you~will~have~another~error~if~you~actually~
8667   use~that~custom~line.
8668 }

8669 \@@_msg_new:nn { tikz~in~borders~without~tikz }
8670 {
8671   Tikz~not~loaded.\\
8672   You~have~used~the~key~'tikz'~in~a~key~'borders'~(of~a~
8673   command~\token_to_str:N\Block')~but~tikz~is~not~loaded.~
8674   That~key~will~be~ignored.
8675 }

8676 \@@_msg_new:nn { color~in~custom~line~with~tikz }
8677 {
8678   Erroneous~use.\\
8679   In~a~'custom~line',~you~have~used~both~'tikz'~and~'color',~
8680   which~is~forbidden~(you~should~use~'color'~inside~the~key~'tikz').~
8681   The~key~'color'~will~be~discarded.
8682 }

8683 \@@_msg_new:nn { Wrong~last~row }
8684 {
8685   Wrong~number.\\
8686   You~have~used~'last~row=\int_use:N \l_@@_last_row_int'~but~your~
8687   \@@_full_name_env:\ seems~to~have~\int_use:N \c@iRow \ rows.~
8688   If~you~go~on,~the~value~of~\int_use:N \c@iRow \ will~be~used~for~
8689   last~row.~You~can~avoid~this~problem~by~using~'last~row'~
8690   without~value~(more~compilations~might~be~necessary).
8691 }

8692 \@@_msg_new:nn { Yet~in~env }
8693 {
8694   Nested~environments.\\
8695   Environments~of~nicematrix~can't~be~nested.\\
8696   This~error~is~fatal.
8697 }

8698 \@@_msg_new:nn { Outside~math~mode }
8699 {
8700   Outside~math~mode.\\
8701   The~\@@_full_name_env:\ can~be~used~only~in~math~mode~
8702   (and~not~in~\token_to_str:N \vcenter).\\
8703   This~error~is~fatal.
8704 }

8705 \@@_msg_new:nn { One~letter~allowed }
8706 {

```

```

8707     Bad~name.\\
8708     The~value~of~key~'\l_keys_key_str'~must~be~of~length~1.\\
8709     It~will~be~ignored.
8710 }

8711 \@@_msg_new:nn { TabularNote~in~CodeAfter }
8712 {
8713     Environment~{TabularNote}~forbidden.\\
8714     You~must~use~{TabularNote}~at~the~end~of~your~{NiceTabular}~
8715     but~*before*~the~\token_to_str:N \CodeAfter.\\
8716     This~environment~{TabularNote}~will~be~ignored.
8717 }

8718 \@@_msg_new:nn { varwidth~not~loaded }
8719 {
8720     varwidth~not~loaded.\\
8721     You~can't~use~the~column~type~'V'~because~'varwidth'~is~not~
8722     loaded.\\
8723     Your~column~will~behave~like~'p'.
8724 }

8725 \@@_msg_new:nnn { Unknow~key~for~RulesBis }
8726 {
8727     Unknow~key.\\
8728     Your~key~'\l_keys_key_str'~is~unknown~for~a~rule.\\
8729     \c_@@_available_keys_str
8730 }
8731 {
8732     The~available~keys~are~(in~alphabetic~order):~
8733     color,~
8734     dotted,~
8735     multiplicity,~
8736     sep-color,~
8737     tikz,~and~total~width.
8738 }
8739

8740 \@@_msg_new:nnn { Unknown~key~for~Block }
8741 {
8742     Unknown~key.\\
8743     The~key~'\l_keys_key_str'~is~unknown~for~the~command~\token_to_str:N
8744     \Block.\\ It~will~be~ignored. \\
8745     \c_@@_available_keys_str
8746 }
8747 {
8748     The~available~keys~are~(in~alphabetic~order):~b,~borders,~c,~draw,~fill,~
8749     hlines,~hvlines,~l,~line-width,~name,~rounded-corners,~r,~respect-arraystretch,
8750     ~t,~tikz,~transparent~and~vlines.
8751 }

8752 \@@_msg_new:nn { Version~of~siunitx~too~old }
8753 {
8754     siunitx~too~old.\\
8755     You~can't~use~'S'~columns~because~your~version~of~'siunitx'~
8756     is~too~old.~You~need~at~least~v~3.0~and~your~log~file~says:~"siunitx,~
8757     \use:c { ver @ siunitx.sty }". \\
8758     This~error~is~fatal.
8759 }

8760 \@@_msg_new:nnn { Unknown~key~for~Brace }
8761 {
8762     Unknown~key.\\
8763     The~key~'\l_keys_key_str'~is~unknown~for~the~commands~\token_to_str:N
8764     \UnderBrace\ and~\token_to_str:N \OverBrace.\\
8765     It~will~be~ignored. \\
8766     \c_@@_available_keys_str
8767 }

```

```

8768 {
8769     The~available~keys~are~(in~alphabetic~order):~color,~left~shorten,~
8770     right~shorten,~shorten~(which~fixes~both~left~shorten~and~
8771     right~shorten)~and~yshift.
8772 }
8773 \@@_msg_new:nnn { Unknown~key~for~CodeAfter }
8774 {
8775     Unknown~key.\\
8776     The~key~'\l_keys_key_str'~is~unknown.\\
8777     It~will~be~ignored. \\
8778     \c_@@_available_keys_str
8779 }
8780 {
8781     The~available~keys~are~(in~alphabetic~order):~
8782     delimiters/color,~
8783     rules~(with~the~subkeys~'color'~and~'width'),~
8784     sub-matrix~(several~subkeys)~
8785     and~xdots~(several~subkeys).~
8786     The~latter~is~for~the~command~\token_to_str:N \line.
8787 }
8788 \@@_msg_new:nnn { Unknown~key~for~CodeBefore }
8789 {
8790     Unknown~key.\\
8791     The~key~'\l_keys_key_str'~is~unknown.\\
8792     It~will~be~ignored. \\
8793     \c_@@_available_keys_str
8794 }
8795 {
8796     The~available~keys~are~(in~alphabetic~order):~
8797     create-cell-nodes,~
8798     delimiters/color~and~
8799     sub-matrix~(several~subkeys).
8800 }
8801 \@@_msg_new:nnn { Unknown~key~for~SubMatrix }
8802 {
8803     Unknown~key.\\
8804     The~key~'\l_keys_key_str'~is~unknown.\\
8805     That~key~will~be~ignored. \\
8806     \c_@@_available_keys_str
8807 }
8808 {
8809     The~available~keys~are~(in~alphabetic~order):~
8810     'delimiters/color',~
8811     'extra-height',~
8812     'hlines',~
8813     'hvlines',~
8814     'left-xshift',~
8815     'name',~
8816     'right-xshift',~
8817     'rules'~(with~the~subkeys~'color'~and~'width'),~
8818     'slim',~
8819     'vlines'~and~'xshift'~(which~sets~both~'left-xshift'~
8820     and~'right-xshift').\\
8821 }
8822 \@@_msg_new:nnn { Unknown~key~for~notes }
8823 {
8824     Unknown~key.\\
8825     The~key~'\l_keys_key_str'~is~unknown.\\
8826     That~key~will~be~ignored. \\
8827     \c_@@_available_keys_str
8828 }
8829 {

```

```

8830 The~available~keys~are~(in~alphabetic~order):~
8831 bottomrule,~
8832 code-after,~
8833 code-before,~
8834 detect-duplicates,~
8835 enumitem-keys,~
8836 enumitem-keys-para,~
8837 para,~
8838 label-in-list,~
8839 label-in-tabular~and~
8840 style.
8841 }

8842 \@@_msg_new:nnn { Unknown~key~for~RowStyle }
8843 {
8844   Unknown~key.\\
8845   The~key~'\l_keys_key_str'~is~unknown~for~the~command~
8846   \token_to_str:N \RowStyle. \\
8847   That~key~will~be~ignored. \\
8848   \c_@@_available_keys_str
8849 }
8850 {
8851   The~available~keys~are~(in~alphabetic~order):~
8852   'bold',~
8853   'cell-space-top-limit',~
8854   'cell-space-bottom-limit',~
8855   'cell-space-limits',~
8856   'color',~
8857   'nb-rows'~and~
8858   'rowcolor'.
8859 }

8860 \@@_msg_new:nnn { Unknown~key~for~NiceMatrixOptions }
8861 {
8862   Unknown~key.\\
8863   The~key~'\l_keys_key_str'~is~unknown~for~the~command~
8864   \token_to_str:N \NiceMatrixOptions. \\
8865   That~key~will~be~ignored. \\
8866   \c_@@_available_keys_str
8867 }
8868 {
8869   The~available~keys~are~(in~alphabetic~order):~
8870   allow-duplicate-names,~
8871   caption-above,~
8872   cell-space-bottom-limit,~
8873   cell-space-limits,~
8874   cell-space-top-limit,~
8875   code-for-first-col,~
8876   code-for-first-row,~
8877   code-for-last-col,~
8878   code-for-last-row,~
8879   corners,~
8880   custom-key,~
8881   create-extra-nodes,~
8882   create-medium-nodes,~
8883   create-large-nodes,~
8884   delimiters~(several~subkeys),~
8885   end-of-row,~
8886   first-col,~
8887   first-row,~
8888   hlines,~
8889   hvlines,~
8890   last-col,~
8891   last-row,~
8892   left-margin,~

```

```

8893 light-syntax,~
8894 matrix/columns-type,~
8895 notes~(several~subkeys),~
8896 nullify-dots,~
8897 renew-dots,~
8898 renew-matrix,~
8899 respect-arraystretch,~
8900 right-margin,~
8901 rules~(with~the~subkeys~'color'~and~'width'),~
8902 small,~
8903 sub-matrix~(several~subkeys),~
8904 vl原因,~
8905 xdots~(several~subkeys).
8906 }

```

For '{NiceArray}', the set of keys is the same as for {NiceMatrix} excepted that there is no l and r.

```

8907 \@@_msg_new:nnn { Unknown~key~for~NiceArray }
8908 {
8909   Unknown~key.\\
8910   The~key~'\l_keys_key_str'~is~unknown~for~the~environment~
8911   \{NiceArray\}. \\
8912   That~key~will~be~ignored. \\
8913   \c_@@_available_keys_str
8914 }
8915 {
8916   The~available~keys~are~(in~alphabetic~order):~
8917   b,~
8918   baseline,~
8919   c,~
8920   cell-space-bottom-limit,~
8921   cell-space-limits,~
8922   cell-space-top-limit,~
8923   code-after,~
8924   code-for-first-col,~
8925   code-for-first-row,~
8926   code-for-last-col,~
8927   code-for-last-row,~
8928   colortbl-like,~
8929   columns-width,~
8930   corners,~
8931   create-extra-nodes,~
8932   create-medium-nodes,~
8933   create-large-nodes,~
8934   extra-left-margin,~
8935   extra-right-margin,~
8936   first-col,~
8937   first-row,~
8938   hlines,~
8939   hvlines,~
8940   last-col,~
8941   last-row,~
8942   left-margin,~
8943   light-syntax,~
8944   name,~
8945   nullify-dots,~
8946   renew-dots,~
8947   respect-arraystretch,~
8948   right-margin,~
8949   rules~(with~the~subkeys~'color'~and~'width'),~
8950   small,~
8951   t,~
8952   tabularnote,~
8953   vl原因,~

```

```

8954     xdots/color,~
8955     xdots/shorten-start,~
8956     xdots/shorten-end,~
8957     xdots/shorten-and~
8958     xdots/line-style.
8959 }

```

This error message is used for the set of keys NiceMatrix/NiceMatrix and NiceMatrix/pNiceArray (but not by NiceMatrix/NiceArray because, for this set of keys, there is no l and r).

```

8960 \@@_msg_new:nnn { Unknown~key~for~NiceMatrix }
8961 {
8962   Unknown~key.\\
8963   The~key~'\l_keys_key_str'~is~unknown~for~the~
8964   \@@_full_name_env:. \\
8965   That~key~will~be~ignored. \\
8966   \c_@@_available_keys_str
8967 }
8968 {
8969   The~available~keys~are~(in~alphabetic~order):~
8970   b,~
8971   baseline,~
8972   c,~
8973   cell-space-bottom-limit,~
8974   cell-space-limits,~
8975   cell-space-top-limit,~
8976   code-after,~
8977   code-for-first-col,~
8978   code-for-first-row,~
8979   code-for-last-col,~
8980   code-for-last-row,~
8981   colortbl-like,~
8982   columns-type,~
8983   columns-width,~
8984   corners,~
8985   create-extra-nodes,~
8986   create-medium-nodes,~
8987   create-large-nodes,~
8988   extra-left-margin,~
8989   extra-right-margin,~
8990   first-col,~
8991   first-row,~
8992   hlines,~
8993   hvlines,~
8994   l,~
8995   last-col,~
8996   last-row,~
8997   left-margin,~
8998   light-syntax,~
8999   name,~
9000   nullify-dots,~
9001   r,~
9002   renew-dots,~
9003   respect-arraystretch,~
9004   right-margin,~
9005   rules~(with~the~subkeys~'color'~and~'width'),~
9006   small,~
9007   t,~
9008   vlines,~
9009   xdots/color,~
9010   xdots/shorten-start,~
9011   xdots/shorten-end,~
9012   xdots/shorten-and~
9013   xdots/line-style.
9014 }

```

```

9015 \@@_msg_new:nnn { Unknown~key~for~NiceTabular }
9016 {
9017   Unknown~key.\\
9018   The~key~'\l_keys_key_str'~is~unknown~for~the~environment~
9019   \{NiceTabular\}. \\
9020   That~key~will~be~ignored. \\
9021   \c_@@_available_keys_str
9022 }
9023 {
9024   The~available~keys~are~(in~alphabetic~order):~
9025   b,~
9026   baseline,~
9027   c,~
9028   caption,~
9029   cell-space-bottom-limit,~
9030   cell-space-limits,~
9031   cell-space-top-limit,~
9032   code-after,~
9033   code-for-first-col,~
9034   code-for-first-row,~
9035   code-for-last-col,~
9036   code-for-last-row,~
9037   colortbl-like,~
9038   columns-width,~
9039   corners,~
9040   custom-line,~
9041   create-extra-nodes,~
9042   create-medium-nodes,~
9043   create-large-nodes,~
9044   extra-left-margin,~
9045   extra-right-margin,~
9046   first-col,~
9047   first-row,~
9048   hlines,~
9049   hvlines,~
9050   label,~
9051   last-col,~
9052   last-row,~
9053   left-margin,~
9054   light-syntax,~
9055   name,~
9056   notes~(several~subkeys),~
9057   nullify-dots,~
9058   renew-dots,~
9059   respect-arraystretch,~
9060   right-margin,~
9061   rules~(with~the~subkeys~'color'~and~'width'),~
9062   short-caption,~
9063   t,~
9064   tabularnote,~
9065   vlines,~
9066   xdots/color,~
9067   xdots/shorten-start,~
9068   xdots/shorten-end,~
9069   xdots/shorten~and~
9070   xdots/line-style.
9071 }
9072 \@@_msg_new:nnn { Duplicate~name }
9073 {
9074   Duplicate~name.\\
9075   The~name~'\l_keys_value_tl'~is~already~used~and~you~shouldn't~use~
9076   the~same~environment~name~twice.~You~can~go~on,~but,~
9077   maybe,~you~will~have~incorrect~results~especially~

```



```

9078   if~you~use~'columns-width=auto'~.~If~you~don't~want~to~see~this~
9079   message~again,~use~the~key~'allow-duplicate-names'~in~
9080   '\token_to_str:N \NiceMatrixOptions'.\\
9081   \c_@@_available_keys_str
9082   }
9083   {
9084     The~names~already~defined~in~this~document~are:~
9085     \seq_use:Nnnn \g_@@_names_seq { ~and~ } { ,~ } { ~and~ }.
9086   }
9087   \@@_msg_new:nn { Option-auto-for-columns-width }
9088   {
9089     Erroneous~use.\\
9090     You~can't~give~the~value~'auto'~to~the~key~'columns-width'~here.~
9091     That~key~will~be~ignored.
9092   }

```

20 History

The successive versions of the file `nicematrix.sty` provided by TeXLive are available on the SVN server of TeXLive:

<https://www.tug.org/svn/texlive/trunk/Master/texmf-dist/tex/latex/nicematrix/nicematrix.sty>

Changes between version 6.12 and 6.13

New environment `{TabularNote}` in `{NiceTabular}` with the same semantic as the key `tabularnote` (for legibility).

The command `\Hline` nows accepts options (between square brackets).

Changes between version 6.11 and 6.12

New keys `caption`, `short-caption` and `label` in the environment `{NiceTabular}`.

In `{NiceTabular}`, a caption specified by the key `caption` is wrapped to the width of the tabular.

Correction of a bug: it's now possible to use `\OverBrace` and `\UnderBrace` with `unicode-math` (with XeLaTeX or LuaLaTeX).

Changes between version 6.10 and 6.11

New key `matrix/columns-type` to specify the type of columns of the matrices.

New key `ccommand` in `custom-line` and new command `\cdottedline`.

Changes between version 6.9 and 6.10

New keys `xdots/shorten-start` and `xdots/shorten-end`.

It's possible to use `\line` in the `\CodeAfter` between two blocks (and not only two cells).

Changes between version 6.8 and 6.9

New keys `xdots/radius` and `xdots/inter` for customisation of the continuous dotted lines.

New command `\ShowCellNames` available in the `\CodeBefore` and in the `\CodeAfter`.

Changes between version 6.7 and 6.8

In the notes of a tabular (with the command `\tabularnote`), the duplicates are now detected: when several commands `\tabularnote` are used with the same argument, only one note is created at the end of the tabular (but all the labels are present, of course).

Changes between version 6.6 and 6.7

Key `color` for `\OverBrace` and `\UnderBrace` in the `\CodeAfter`
Key `tikz` in the key borders of a command `\Block`

Changes between version 6.5 and 6.6

Keys `tikz` and `width` in `custom-line`.

Changes between versions 6.4 and 6.5

Key `custom-line` in `\NiceMatrixOptions`.
Key `respect-arraystretch`.

Changes between versions 6.3 and 6.4

New commands `\UnderBrace` and `\OverBrace` in the `\CodeAfter`.
Correction of a bug of the key `baseline` (cf. question 623258 on TeX StackExchange).
Correction of a bug with the columns `V` of `varwidth`.
Correction of a bug: the use of `\hdottedline` and `:` in the preamble of the array (of another letter specified by `letter-for-dotted-lines`) was incompatible with the key `xdots/line-style`.

Changes between versions 6.2 and 6.3

Keys `nb-rows`, `rowcolor` and `bold` for the command `\RowStyle`
Key `name` for the command `\Block`.
Support for the columns `V` of `varwidth`.

Changes between versions 6.1 and 6.2

Better compatibility with the classes `revtex4-1` and `revtex4-2`.
Key `vlines-in-sub-matrix`.

Changes between versions 6.0 and 6.1

Better computation of the widths of the `X` columns.
Key `color` for the command `\RowStyle`.

Changes between versions 5.19 and 6.0

Columns `X` and environment `{NiceTabularX}`.
Command `\rowlistcolors` available in the `\CodeBefore`.
In columns with fixed width, the blocks are composed as paragraphs (wrapping of the lines).
The key `define-L-C-R` has been deleted.

Changes between versions 5.18 and 5.19

New key `tikz` for the command `\Block`.

Changes between versions 5.17 and 5.18

New command `\RowStyle`

Changes between versions 5.16 and 5.17

The key `define-L-C-R` (only available at load-time) now raises a (non fatal) error.

Keys `L`, `C` and `R` for the command `\Block`.

Key `hvlines-except-borders`.

It's now possible to use a key `l`, `r` or `c` with the command `\pAutoNiceMatrix` (and the similar ones).

Changes between versions 5.15 and 5.16

It's now possible to use the cells corresponding to the contents of the nodes (of the form `i-j`) in the `\CodeBefore` when the key `create-cell-nodes` of that `\CodeBefore` is used. The medium and the large nodes are also available if the corresponding keys are used.

Changes between versions 5.14 and 5.15

Key `hvlines` for the command `\Block`.

The commands provided by `nicematrix` to color cells, rows and columns don't color the cells which are in the "corners" (when the key `corner` is used).

It's now possible to specify delimiters for submatrices in the preamble of an environment.

The version 5.15b is compatible with the version 3.0+ of `siunitx` (previous versions were not).

Changes between versions 5.13 and 5.14

Nodes of the form `(1.5)`, `(2.5)`, `(3.5)`, etc.

Keys `t` and `b` for the command `\Block`.

Key `corners`.

Changes between versions 5.12 and 5.13

New command `\arraycolor` in the `\CodeBefore` (with its key `except-corners`).

New key `borders` for the command `\Block`.

New command `\Hline` (for horizontal rules not drawn in the blocks).

The keys `vlines` and `hlines` takes in as value a (comma-separated) list of numbers (for the rules to draw).

Changes between versions 5.11 and 5.12

Keywords `\CodeBefore` and `\Body` (alternative syntax to the key `code-before`).

New key `delimiters/max-width`.

New keys `hlines`, `vlines` and `hvlines` for the command `\SubMatrix` in the `\CodeAfter`.

New key `rounded-corners` for the command `\Block`.

Changes between versions 5.10 and 5.11

It's now possible, in the `code-before` and in the `\CodeAfter`, to use the syntax `|i-j|` for the Tikz node at the intersection of the (potential) horizontal rule number i and the (potential) vertical rule number j .

Changes between versions 5.9 and 5.10

New command `\SubMatrix` available in the `\CodeAfter`.

It's possible to provide options (between brackets) to the keyword `\CodeAfter`.

Changes between versions 5.8 and 5.9

Correction of a bug: in the previous versions, it was not possible to use the key `line-style` for the continuous dotted lines when the Tikz library `babel` was loaded.

New key `cell-space-limits`.

Changes between versions 5.7 and 5.8

Keys `cols` and `restart` of the command `\rowcolors` in the `code-before`.

Modification of the behaviour of `\` in the columns of type `p`, `m` or `b` (for a behaviour similar to the environments of `array`).

Better error messages for the command `\Block`.

Changes between versions 5.6 and 5.7

New key `delimiters-color`

Keys `fill`, `draw` and `line-width` for the command `\Block`.

Changes between versions 5.5 and 5.6

Different behaviour for the mono-row blocks.

New command `\NotEmpty`.

Changes between versions 5.4 and 5.5

The user must never put `\omit` before `\CodeAfter`.

Correction of a bug: the tabular notes `\tabularnotes` were not composed when present in a block (except a mono-column block).

Changes between versions 5.3 and 5.4

Key `tabularnote`.

Different behaviour for the mono-column blocks.

Changes between versions 5.2 and 5.3

Keys `c`, `r` and `l` for the command `\Block`.

It's possible to use the key `draw-first` with `\Ddots` and `\Iddots` to specify which dotted line will be drawn first (the other lines will be drawn parallel to that one if parallelization is activated).

Changes between versions 5.1 and 5.2

The vertical rules specified by `|` or `||` in the preamble respect the blocks.

Key `respect-blocks` for `\rowcolors` (with a `s`) in the `code-before`.

The variable `\g_nicematrix_code_before_tl` is now public.

The key `baseline` may take in as value an expression of the form `line-i` to align the `\hline` in the row `i`.

The key `hvlines-except-corners` may take in as value a list of corners (eg: `NW,SE`).

Changes between versions 5.0 and 5.1

The vertical rules specified by `|` in the preamble are not broken by `\hline\hline` (and other).

Environment `{NiceTabular*}`

Command `\Vdotsfor` similar to `\Hdotsfor`

The variable `\g_nicematrix_code_after_tl` is now public.

Changes between versions 4.4 and 5.0

Use of the standard column types `l`, `c` and `r` instead of `L`, `C` and `R`.

It's now possible to use the command `\diagbox` in a `\Block`.

Command `\tabularnote`

Changes between versions 4.3 and 4.4

New key `hvlines-except-corners` (now deprecated).

Changes between versions 4.2 and 4.3

The horizontal centering of the content of a `\Block` is correct even when an instruction such as `!\{quad}` is used in the preamble of the array.

It's now possible to use the command `\Block` in the “last row”.

Changes between versions 4.1 and 4.2

It's now possible to write `\begin{pNiceMatrix}a&b\\c&d\end{pNiceMatrix}^2` with the expected result.

Changes between versions 4.0 and 4.1

New keys `cell-space-top-limit` and `cell-space-bottom-limit`

New command `\diagbox`

The key `hvlime` don't draw rules in the blocks (commands `\Block`) and in the virtual blocks corresponding to the dotted lines.

Changes between versions 3.15 and 4.0

New environment `{NiceTabular}`

Commands to color cells, rows and columns with a perfect result in the PDF.

Changes between versions 3.14 and 3.15

It's possible to put labels on the dotted lines drawn by `\Ldots`, `\Cdots`, `\Vdots`, `\Ddots`, `\Iddots`, `\Hdotsfor` and the command `\line` in the `code-after` with the tokens `_` and `^`.

The option `baseline` is now available in all the environments of `nicematrix`. Before, it was available only in `{NiceArray}`.

New keyword `\CodeAfter` (in the environments of `nicematrix`).

Changes between versions 3.13 and 3.14

Correction of a bug (question 60761504 on [stackoverflow](https://stackoverflow.com)).

Better error messages when the user uses `&` or `\\` when `light-syntax` is in force.

Changes between versions 3.12 and 3.13

The behaviour of the command `\rotate` is improved when used in the “last row”.

The option `dotted-lines-margin` has been renamed in `xdots/shorten` and the options `xdots/color` and `xdots/line-style` have been added for a complete customisation of the dotted lines.

In the environments without preamble (`{NiceMatrix}`, `{pNiceMatrix}`, etc.), it’s possible to use the options `l` (`=L`) or `r` (`=R`) to specify the type of the columns.

The starred versions of the commands `\Cdots`, `\Ldots`, `\Vdots`, `\Ddots` and `\Iddots` are deprecated since the version 3.1 of `nicematrix`. Now, one should load `nicematrix` with the option `starred-commands` to avoid an error at the compilation.

The code of `nicematrix` no longer uses Tikz but only PGF. By default, Tikz is *not* loaded by `nicematrix`.

Changes between versions 3.11 and 3.12

Command `\rotate` in the cells of the array.

Options `vlines`, `hlines` and `hvlines`.

Option `baseline` pour `{NiceArray}` (not for the other environments).

The name of the Tikz nodes created by the command `\Block` has changed: when the command has been issued in the cell $i-j$, the name is `i-j-block` and, if the creation of the “medium nodes” is required, a node `i-j-block-medium` is created.

If the user tries to use more columns than allowed by its environment, an error is raised by `nicematrix` (instead of a low-level error).

The package must be loaded with the option `obsolete-environments` if we want to use the deprecated environments.

Changes between versions 3.10 and 3.11

Correction of a bug linked to `first-row` and `last-row`.

Changes between version 3.9 and 3.10

New option `light-syntax` (and `end-of-row`).

New option `dotted-lines-margin` for fine tuning of the dotted lines.

Changes between version 3.8 and 3.9

New commands `\NiceMatrixLastEnv` and `\OnlyMainNiceMatrix`.

New options `create-medium-nodes` and `create-large-nodes`.

Changes between version 3.7 and 3.8

New programming for the command `\Block` when the block has only one row. With this programming, the vertical rules drawn by the specifier “|” at the end of the block is actually drawn. In previous versions, they were not because the block of one row was constructed with `\multicolumn`. An error is raised when an obsolete environment is used.

Changes between version 3.6 and 3.7

The four “corners” of the matrix are correctly protected against the four codes: `code-for-first-col`, `code-for-last-col`, `code-for-first-row` and `code-for-last-row`.

New command `\pAutoNiceMatrix` and its variants (suggestion of Christophe Bal).

Changes between version 3.5 and 3.6

LaTeX counters `iRow` and `jCol` available in the cells of the array.

Addition of `\normalbaselines` before the construction of the array: in environments like `{align}` of `amsmath` the value of `\baselineskip` is changed and if the options `first-row` and `last-row` were used in an environment of `nicematrix`, the position of the delimiters was wrong.

A warning is written in the `.log` file if an obsolete environment is used.

There is no longer artificial errors `Duplicate~name` in the environments of `amsmath`.

Changes between version 3.4 and 3.5

Correction on a bug on the two previous versions where the `code-after` was not executed.

Changes between version 3.3 and 3.4

Following a discussion on TeX StackExchange⁷⁸, optimization of Tikz externalization is disabled in the environments of `nicematrix` when the class `standalone` or the package `standalone` is used.

Changes between version 3.2 and 3.3

The options `first-row`, `last-row`, `first-col` and `last-col` are now available in the environments `{NiceMatrix}`, `{pNiceMatrix}`, `{bNiceMatrix}`, etc.

The option `columns-width=auto` doesn't need any more a second compilation.

The previous version of `nicematrix` was incompatible with a recent version of `expl3` (released 2019/09/30). This version is compatible.

Changes between version 3.1 and 3.2 (and 3.2a)

Option `small`.

Changes between version 3.0 and 3.1

Command `\Block` to draw block matrices.

Error message when the user gives an incorrect value for `last-row`.

A dotted line can no longer cross another dotted line (excepted the dotted lines drawn by `\cdottedline`, the symbol “:” (in the preamble of the array) and `\line` in `code-after`).

The starred versions of `\Cdots`, `\Ldots`, etc. are now deprecated because, with the new implementation, they become pointless. These starred versions are no longer documented.

The vertical rules in the matrices (drawn by “|”) are now compatible with the color fixed by `colortbl`.

Correction of a bug: it was not possible to use the colon “:” in the preamble of an array when `pdflatex` was used with `french-babel` (because `french-babel` activates the colon in the beginning of the document).

Changes between version 2.3 and 3.0

Modification of `\Hdotsfor`. Now `\Hdotsfor` erases the `\vlines` (of “|”) as `\hdotsfor` does.

Composition of exterior rows and columns on the four sides of the matrix (and not only on two sides) with the options `first-row`, `last-row`, `first-col` and `last-col`.

⁷⁸cf. tex.stackexchange.com/questions/510841/nicematrix-and-tikz-external-optimize

Changes between version 2.2.1 and 2.3

Compatibility with the column type S of siunitx.
Option `hlines`.

Changes between version 2.2 and 2.2.1

Improvement of the vertical dotted lines drawn by the specifier “:” in the preamble.
Modification of the position of the dotted lines drawn by `\hdottedline`.

Changes between version 2.1.5 and 2.2

Possibility to draw horizontal dotted lines to separate rows with the command `\hdottedline` (similar to the classical command `\hline` and the command `\hdashline` of `arydshln`).
Possibility to draw vertical dotted lines to separate columns with the specifier “:” in the preamble (similar to the classical specifier “|” and the specifier “:” of `arydshln`).

Changes between version 2.1.4 and 2.1.5

Compatibility with the classes `revtex4-1` and `revtex4-2`.
Option `allow-duplicate-names`.

Changes between version 2.1.3 and 2.1.4

Replacement of some options `0 { }` in commands and environments defined with `xparse` by `! 0 { }` (because a recent version of `xparse` introduced the specifier `!` and modified the default behaviour of the last optional arguments).
See www.texdev.net/2018/04/21/xparse-optional-arguments-at-the-end

Changes between version 2.1.2 and 2.1.3

When searching the end of a dotted line from a command like `\Cdots` issued in the “main matrix” (not in the exterior column), the cells in the exterior column are considered as outside the matrix. That means that it’s possible to do the following matrix with only a `\Cdots` command (and a single `\Vdots`).

$$\begin{pmatrix} & C_j & \\ 0 & \vdots & 0 \\ & \ddots & \dots \\ 0 & & 0 \end{pmatrix} L_i$$

Changes between version 2.1 and 2.1.1

Small corrections: for example, the option `code-for-first-row` is now available in the command `\NiceMatrixOptions`.

Following a discussion on TeX StackExchange⁷⁹, Tikz externalization is now deactivated in the environments of the package `nicematrix`.⁸⁰

⁷⁹cf. tex.stackexchange.com/questions/450841/tikz-externalize-and-nicematrix-package

⁸⁰Before this version, there was an error when using `nicematrix` with Tikz externalization. In any case, it’s not possible to externalize the Tikz elements constructed by `nicematrix` because they use the options `overlay` and `remember picture`.

Changes between version 2.0 and 2.1

New implementation of the environment `{pNiceArrayRC}`. With this new implementation, there is no restriction on the width of the columns.

The package `nicematrix` no longer loads `mathtools` but only `amsmath`.

Creation of “medium nodes” and “large nodes”.

Changes between version 1.4 and 2.0

The versions 1.0 to 1.4 of `nicematrix` were focused on the continuous dotted lines whereas the version 2.0 of `nicematrix` provides different features to improve the typesetting of mathematical matrices.

Changes between version 1.3 and 1.4

The column types `w` and `W` can now be used in the environments `{NiceArray}`, `{pNiceArrayC}` and its variants with the same meaning as in the package `array`.

New option `columns-width` to fix the same width for all the columns of the array.

Changes between version 1.2 and 1.3

New environment `{pNiceArrayC}` and its variants.

Correction of a bug in the definition of `{BNiceMatrix}`, `{vNiceMatrix}` and `{VNiceMatrix}` (in fact, it was a typo).

Options are now available locally in `{pNiceMatrix}` and its variants.

The names of the options are changed. The old names were names in “camel style”.

Changes between versions 1.1 and 1.2

New environment `{NiceArray}` with column types `L`, `C` and `R`.

Changes between versions 1.0 and 1.1

The dotted lines are no longer drawn with Tikz nodes but with Tikz circles (for efficiency).

Modification of the code which is now twice faster.

Contents

1	The environments of this package	2
2	The vertical space between the rows	2
3	The vertical position of the arrays	3
4	The blocks	4
4.1	General case	4
4.2	The mono-column blocks	6
4.3	The mono-row blocks	6
4.4	The mono-cell blocks	6
4.5	Horizontal position of the content of the block	7
5	The rules	7
5.1	Some differences with the classical environments	8
5.1.1	The vertical rules	8
5.1.2	The command <code>\cline</code>	8
5.2	The thickness and the color of the rules	9
5.3	The tools of nicematrix for the rules	9
5.3.1	The keys <code>hlines</code> and <code>vlines</code>	9
5.3.2	The keys <code>hvlines</code> and <code>hvlines-except-borders</code>	10
5.3.3	The (empty) corners	10
5.4	The command <code>\diagbox</code>	11
5.5	Commands for customized rules	11
6	The color of the rows and columns	13
6.1	Use of <code>colortbl</code>	13
6.2	The tools of nicematrix in the <code>\CodeBefore</code>	14
6.3	Color tools with the syntax of <code>colortbl</code>	18
7	The command <code>\RowStyle</code>	19
8	The width of the columns	19
8.1	Basic tools	19
8.2	The columns <code>V</code> of <code>varwidth</code>	20
8.3	The columns <code>X</code>	21
9	The exterior rows and columns	22
10	The continuous dotted lines	23
10.1	The option <code>nullify-dots</code>	25
10.2	The commands <code>\Hdotsfor</code> and <code>\Vdotsfor</code>	25
10.3	How to generate the continuous dotted lines transparently	26
10.4	The labels of the dotted lines	27
10.5	Customisation of the dotted lines	27
10.6	The dotted lines and the rules	29
11	The <code>\CodeAfter</code>	29
11.1	The command <code>\line</code> in the <code>\CodeAfter</code>	29
11.2	The command <code>\SubMatrix</code> in the <code>\CodeAfter</code>	30
11.3	The commands <code>\OverBrace</code> and <code>\UnderBrace</code> in the <code>\CodeAfter</code>	32

12	Captions and notes in the tabulars	33
12.1	Caption of a tabular	33
12.2	The footnotes	33
12.3	The notes of tabular	33
12.4	Customisation of the tabular notes	35
12.5	Use of <code>{NiceTabular}</code> with <code>threeparttable</code>	37
13	Other features	37
14	Autres fonctionnalités	37
14.1	Command <code>\ShowCellNames</code>	37
14.2	Use of the column type <code>S</code> of <code>siunitx</code>	38
14.3	Default column type in <code>{NiceMatrix}</code>	38
14.4	The command <code>\rotate</code>	38
14.5	The option <code>small</code>	39
14.6	The counters <code>iRow</code> and <code>jCol</code>	39
14.7	The key <code>light-syntax</code>	40
14.8	Color of the delimiters	40
14.9	The environment <code>{NiceArrayWithDelims}</code>	41
14.10	The command <code>\OnlyMainNiceMatrix</code>	41
15	Use of Tikz with <code>nicematrix</code>	41
15.1	The nodes corresponding to the contents of the cells	41
15.1.1	The columns <code>V</code> of <code>varwidth</code>	42
15.2	The medium nodes and the large nodes	42
15.3	The nodes which indicate the position of the rules	44
15.4	The nodes corresponding to the command <code>\SubMatrix</code>	45
16	API for the developers	46
17	Technical remarks	47
17.1	Diagonal lines	47
17.2	The empty cells	47
17.3	The option <code>exterior-arraycolsep</code>	48
17.4	Incompatibilities	48
18	Examples	49
18.1	Utilisation of the key <code>'tikz'</code> of the command <code>\Block</code>	49
18.2	Notes in the tabulars	49
18.3	Dotted lines	50
18.4	Dotted lines which are no longer dotted	51
18.5	Dashed rules	52
18.6	Stacks of matrices	53
18.7	How to highlight cells of a matrix	56
18.8	Utilisation of <code>\SubMatrix</code> in the <code>\CodeBefore</code>	58
19	Implementation	59
20	History	257