

The `postnotes` package^{*}

Code documentation

Gustavo Barros[†]

2023-06-16

Contents

1	Initial setup	2
2	Data	2
3	Options	5
4	<code>\postnote</code>	10
5	<code>\postnoteref</code>	16
6	<code>\postnotesection</code>	16
7	<code>\printpostnotes</code>	17
8	Headers	24
9	Compatibility	30
10	Languages	38
	Index	41

^{*}This file describes v0.2.5, released 2023-06-16.

[†]<https://github.com/gusbrs/postnotes>

1 Initial setup

Start the DocStrip guards.

```
1 <*package>
```

Identify the internal prefix (L^AT_EX3 DocStrip convention).

```
2 <@@=postnotes>
```

The new syntax for file/package hooks, which the package assumes, requires kernel 2021-11-15 (ltnnews34, ltfilehook). Furthermore, the kernel of 2022-06-01 introduced a couple of very nice features which simplifies the relation with hyperref (ltnnews35, hyperref-linktarget): the provision of \MakeLinkTarget and the definition by the kernel of the starred version of \ref, which we can use regardless of hyperref being loaded. So we require the 2022-06-01 kernel or newer.

```
3 \NeedsTeXFormat{LaTeX2e}
4 \providecommand\IfFormatAtLeastTF{\@ifl@t@r\fmtversion}
5 \IfFormatAtLeastTF{2022-06-01}
6 {}
7 {%
8   \PackageError{postnotes}{LaTeX kernel too old}
9   {%
10     'postnotes' requires a LaTeX kernel 2022-06-01 or newer.%
11     \MessageBreak Loading will abort!%
12   }%
13   \endinput
14 }%

15 \ProvidesExplPackage {postnotes} {2023-06-16} {0.2.5}
16 {Endnotes for LaTeX}
```

2 Data

`__postnotes_data_name:n` Returns the name of the property list variable which stores the data of the \postnote with $\langle note\ id \rangle$ number.

```
\__postnotes_data_name:n {\langle note id \rangle}

17 \cs_new:Npn \__postnotes_data_name:n #1
18 { g__postnotes_ #1 _data_prop }
19 \cs_generate_variant:Nn \__postnotes_data_name:n { e }
```

(End of definition for __postnotes_data_name:n.)

postnotes provides a number of hooks from the new hook system to grant some points of access in key places of the package. Note that hooks created with \NewHook are meant to be public interfaces (see <https://chat.stackexchange.com/transcript/message/62955941#62955941>, and following discussion).

`__postnotes_store:nn` Stores the metadata and $\langle note\ content \rangle$ of \postnote with ID $\langle note\ id \rangle$, from where it is called. The postnotes/note/store hook is intended to add further data to the note, when required to support packages with specific needs.

```
\__postnotes_store:nn {\langle note id \rangle} {\langle note content \rangle}
```

```

20 \NewHook { postnotes/note/store }
21 \cs_new_protected:Npn \__postnotes_store:nn #1#2
22 {
23   \prop_new:c { \__postnotes_data_name:e {#1} }
24   \prop_gput:cnn { \__postnotes_data_name:e {#1} } { type } { note }
25   \prop_gput:cnx { \__postnotes_data_name:e {#1} } { mark }
26     { \l__postnotes_mark_tl }
27   \prop_gput:cnx { \__postnotes_data_name:e {#1} } { counter }
28     { \int_use:N \c@postnote }
29   \prop_gput:cnx { \__postnotes_data_name:e {#1} } { sortnum }
30     {
31       \bool_if:NTF \l__postnotes_manual_sortnum_bool
32         { \fp_use:N \l__postnotes_sort_num_fp }
33         { \int_use:N \c@postnote }
34     }
35   \cs_if_exist:cT { chapter }
36     {
37       \prop_gput:cnx { \__postnotes_data_name:e {#1} }
38         { thechapter } { \thechapter }
39     }
40   \prop_gput:cnx { \__postnotes_data_name:e {#1} } { thesection }
41     { \thesection }
42   \prop_gput:cnx { \__postnotes_data_name:e {#1} } { pnsectname }
43     { \g__postnotes_section_name_tl }
44   \prop_gput:cnx { \__postnotes_data_name:e {#1} } { pnsectid }
45     { \int_use:N \g__postnotes_sectid_int }
46   \prop_gput:cnx { \__postnotes_data_name:e {#1} } { multibool }
47     { \bool_to_str:N \l__postnotes_maybe_multi_bool }
48   \prop_gput:cnn { \__postnotes_data_name:e {#1} } { content } {#2}
49   \UseHook { postnotes/note/store }
50 }

```

(End of definition for __postnotes_store:nn.)

__postnotes_store_section:nn Stores the metadata and $\langle \text{note content} \rangle$ of \postnotessection with ID $\langle \text{note id} \rangle$, from where it is called.

```

\__postnotes_store_section:nn {\langle \text{note id} \rangle} {\langle \text{note content} \rangle}
51 \cs_new_protected:Npn \__postnotes_store_section:nn #1#2
52 {
53   \prop_new:c { \__postnotes_data_name:e {#1} }
54   \prop_gput:cnn { \__postnotes_data_name:e {#1} } { type } { section }
55   \cs_if_exist:cT { chapter }
56     {
57       \prop_gput:cnx { \__postnotes_data_name:e {#1} }
58         { thechapter } { \thechapter }
59     }
60   \prop_gput:cnx { \__postnotes_data_name:e {#1} } { thesection }
61     { \thesection }
62   \prop_gput:cnn { \__postnotes_data_name:e {#1} } { content } {#2}
63 }
64 \cs_generate_variant:Nn \__postnotes_store_section:nn { nx }

```

(End of definition for __postnotes_store_section:nn.)

`__postnotes_prop_get:nnN` Convenience functions to retrieve and clear data from a note based on the ID number.
`__postnotes_prop_item:nn`
`__postnotes_prop_gclear:n`

```

\__postnotes_prop_get:nnN {<note id>} {<property>} {<tl var to set>}
\__postnotes_prop_item:nn {<note id>} {<property>}
\__postnotes_prop_gclear:n {<note id>}

65 \cs_new_protected:Npn \__postnotes_prop_get:nnN #1#2#3
66 {
67   \prop_get:cnNF { \__postnotes_data_name:e {#1} } {#2} #3
68   { \tl_clear:N #3 }
69 }
70 \cs_new:Npn \__postnotes_prop_item:nn #1#2
71 { \prop_item:cn { \__postnotes_data_name:e {#1} } {#2} }
72 \cs_new_protected:Npn \__postnotes_prop_gclear:n #1
73 { \prop_gclear:c { \__postnotes_data_name:e {#1} } }

(End of definition for \__postnotes_prop_get:nnN, \__postnotes_prop_item:nn, and \__postnotes_prop_gclear:n.)

```

`\post@note` The `\newlabel` equivalent for postnotes. Based on the kernel's `\@newl@bel` so that we get L^AT_EX checks for multiple and changed references for free (procedure learnt from `zref`). `\post@note`, when the `.aux` file is read, defines macros named `\postnote@r@<label name>`, according to the prefix set by `\c__postnotes_ref_prefix_tl`.

```

\post@note {<label name>} {<label content>}

74 \tl_const:Nn \c__postnotes_ref_prefix_tl { postnote@r }
75 \cs_new_protected:Npx \post@note #1#2
76 { \exp_not:N \@newl@bel { \c__postnotes_ref_prefix_tl } {#1} {#2} }

(End of definition for \post@note.)

```

`__postnotes_set_mark_page_label:n` Label setting functions for each pertinent context. They must use `\iow_shipout_x:Nn`, since the main information we are interested in is the page.
`__postnotes_set_text_page_label:n`
`__postnotes_set_print_page_label:n`

```

\__postnotes_set_mark_page_label:n {<label name>}
\__postnotes_set_text_page_label:n {<label name>}
\__postnotes_set_print_page_label:n {<label name>}

77 \cs_new_protected:Npn \__postnotes_set_mark_page_label:n #1
78 {
79   \iow_shipout_x:Nn \@auxout
80   { \token_to_str:N \post@note { mark@ #1 } { \thepage } }
81 }
82 \cs_generate_variant:Nn \__postnotes_set_mark_page_label:n { x }
83 \cs_new_protected:Npn \__postnotes_set_text_page_label:n #1
84 {
85   \iow_shipout_x:Nn \@auxout
86   { \token_to_str:N \post@note { text@ #1 } { \int_use:N \c@page } }
87 }
88 \cs_generate_variant:Nn \__postnotes_set_text_page_label:n { x }
89 \cs_new_protected:Npn \__postnotes_set_print_page_label:n #1
90 {
91   \iow_shipout_x:Nn \@auxout
92   { \token_to_str:N \post@note { print@ #1 } { \int_use:N \c@page } }
93 }
94 \cs_generate_variant:Nn \__postnotes_set_print_page_label:n { x }

```

(End of definition for `_postnotes_set_mark_page_label:n`, `_postnotes_set_text_page_label:n`,
and `_postnotes_set_print_page_label:n`.)

`_postnotes_get_pageref:Nn`
`_postnotes_extract_pageref:n`

Reference data extraction functions.

```

\__postnotes_get_pageref:Nn {\tl var to set} {\label name}
\__postnotes_extract_pageref:n {\label name}

95 \cs_new_protected:Npn \__postnotes_get_pageref:Nn #1#2
96 {
97   \cs_if_exist:cTF { \c__postnotes_ref_prefix_tl @ #2 }
98   { \tl_set:Nv #1 { \c__postnotes_ref_prefix_tl @ #2 } }
99   { \tl_clear:N #1 }
100 }
101 \cs_generate_variant:Nn \__postnotes_get_pageref:Nn { Nx }
102 \cs_new:Npn \__postnotes_extract_pageref:n #1
103 {
104   \cs_if_exist:cTF { \c__postnotes_ref_prefix_tl @ #1 }
105   { \exp_not:v { \c__postnotes_ref_prefix_tl @ #1 } }
106   { \c_empty_tl }
107 }
108 \cs_generate_variant:Nn \__postnotes_extract_pageref:n { e }

```

(End of definition for `_postnotes_get_pageref:Nn` and `_postnotes_extract_pageref:n`.)

3 Options

heading option

```

109 \keys_define:nn { postnotes/setup }
110 {
111   heading .cs_set_protected:Np = \pnheading ,
112   heading .value_required:n = true ,
113 }

```

`\pnheading` Provide default value for `\pnheading`.

```

114 \cs_if_exist:cTF { chapter }
115 {
116   \cs_new_protected:Npn \pnheading
117   {
118     \chapter*{\pntitle}
119     \@mkboth{\pnheaderdefault}{\pnheaderdefault}
120   }
121 }
122 {
123   \cs_new_protected:Npn \pnheading
124   {
125     \section*{\pntitle}
126     \@mkboth{\pnheaderdefault}{\pnheaderdefault}
127   }
128 }

```

(End of definition for `\pnheading`.)

format option

```
129 \tl_new:N \l__postnotes_print_format_tl
130 \keys_define:nn { postnotes/setup }
131 {
132     format .tl_set:N = \l__postnotes_print_format_tl ,
133     format .initial:n = { \small } ,
134     format .value_required:n = true ,
135 }
```

listenv option

```
136 \tl_new:N \l__postnotes_print_env_tl
137 \bool_new:N \l__postnotes_print_as_list_bool
138 \keys_define:nn { postnotes/setup }
139 {
140     listenv .code:n =
141     {
142         \tl_if_eq:nnTF {#1} { none }
143         {
144             \bool_set_false:N \l__postnotes_print_as_list_bool
145             \tl_set:Nn \l__postnotes_post_printnote_tl { \par }

```

A sensible default just in case. It should not get to be used though.

```
146         \tl_set:Nn \l__postnotes_print_env_tl { itemize }
147     }
148     {
149         \bool_set_true:N \l__postnotes_print_as_list_bool
150         \tl_set:Nn \l__postnotes_print_env_tl {#1}
151     }
152 },
153 listenv .initial:n = { postnoteslist } ,
154 listenv .value_required:n = true ,
155 }
```

A couple of built-in list environments provided for convenience, and `postnoteslist` as default. The horizontal setup of the label in these lists is based on the description environment of the standard classes (see the *The L^AT_EX Companion*).

```
156 \NewDocumentEnvironment { postnoteslist } { }
157 {
158     \list { }
159     {
160         \setlength { \leftmargin } { Opt }
161         \setlength { \labelwidth } { Opt }
162         \setlength { \itemindent } { .5\parindent }
163         \cs_set_eq:NN \makelabel \l__postnotes_list_makelabel:n
164         \setlength { \rightmargin } { Opt }
165         \setlength { \listparindent } { \parindent }
166         \setlength { \parsep } { \parskip }
167         \setlength { \itemsep } { Opt }
168         \setlength { \topsep } { .5\topsep }
169         \setlength { \partopsep } { .5\partopsep }
170     }
171 }
172 { \endlist }
173 \NewDocumentEnvironment { postnoteslisthang } { }
```

```

174 {
175   \list { }
176   {
177     \setlength { \leftmargin } { 1em }
178     \setlength { \labelwidth } { -\leftmargin }
179     \setlength { \itemindent } { -2\leftmargin }
180     \cs_set_eq:NN \makelabel \__postnotes_list_makelabel:n
181     \setlength { \rightmargin } { 0pt }
182     \setlength { \listparindent } { \parindent }
183     \setlength { \parsep } { \parskip }
184     \setlength { \itemsep } { 0pt }
185     \setlength { \topsep } { .5\topsep }
186     \setlength { \partopsep } { .5\partopsep }
187   }
188 }
189 { \endlist }
190 \cs_new:Npn \__postnotes_list_makelabel:n #1
191 { \hspace { \labelsep } \normalfont ~ #1 }

```

makemark and maketextmark options

The arguments are: #1 is the mark, #2 and #3 are, respectively, the start and the end of the backlink.

```

192 \keys_define:nn { postnotes/setup }
193 {
194   makemark .cs_set:Np = \__postnotes_make_mark:nnn #1#2#3 ,
195   makemark .value_required:n = true ,

```

From the default kernel definition of \@makefnmark.

```

196   makemark .initial:n =
197     { #2 \hbox { \@textsuperscript { \normalfont #1 } } #3 } ,
198   maketextmark .cs_set:Np = \__postnotes_make_text_mark:nnn #1#2#3 ,
199   maketextmark .value_required:n = true ,
200   maketextmark .initial:n = { #2 #1 . #3 } ,
201 }

```

pretextmark, posttextmark, postprintnote options

```

202 \tl_new:N \l__postnotes_pre_textmark_tl
203 \tl_new:N \l__postnotes_post_textmark_tl
204 \tl_new:N \l__postnotes_post_printnote_tl
205 \keys_define:nn { postnotes/setup }
206 {
207   pretextmark .tl_set:N = \l__postnotes_pre_textmark_tl ,
208   pretextmark .value_required:n = true ,
209   posttextmark .tl_set:N = \l__postnotes_post_textmark_tl ,
210   posttextmark .value_required:n = true ,
211   postprintnote .tl_set:N = \l__postnotes_post_printnote_tl ,
212   postprintnote .value_required:n = true ,
213 }

```

hyperref and backlink options

```

214 \bool_new:N \l__postnotes_hyperlink_bool
215 \bool_new:N \l__postnotes_hyperref_warn_bool

```

```

216 \bool_new:N \l__postnotes_backlink_bool
217 \keys_define:nn { postnotes/setup }
218 {
219   hyperref .choice: ,
220   hyperref / auto .code:n =
221   {
222     \bool_set_true:N \l__postnotes_hyperlink_bool
223     \bool_set_false:N \l__postnotes_hyperref_warn_bool
224   } ,
225   hyperref / true .code:n =
226   {
227     \bool_set_true:N \l__postnotes_hyperlink_bool
228     \bool_set_true:N \l__postnotes_hyperref_warn_bool
229   } ,
230   hyperref / false .code:n =
231   {
232     \bool_set_false:N \l__postnotes_hyperlink_bool
233     \bool_set_false:N \l__postnotes_hyperref_warn_bool
234   } ,
235   hyperref .initial:n = auto ,
236   hyperref .default:n = true ,
237   backlink .bool_set:N = \l__postnotes_backlink_bool ,
238   backlink .initial:n = true ,
239   backlink .default:n = true ,
240 }
241 \AddToHook { begindocument }
242 {
243   \IfPackageLoadedTF { hyperref }
244   { }
245   {
246     \bool_if:NT \l__postnotes_hyperref_warn_bool
247     { \msg_warning:nn { postnotes } { missing-hyperref } }
248     \bool_set_false:N \l__postnotes_hyperlink_bool
249   }
250   \keys_define:nn { postnotes/setup }
251   {
252     hyperref .code:n =
253     {
254       \msg_warning:nnn { postnotes }
255       { option-preamble-only } { hyperref }
256     } ,
257     backlink .code:n =
258     {
259       \msg_warning:nnn { postnotes }
260       { option-preamble-only } { backlink }
261     } ,
262   }
263 }
264 \msg_new:nnn { postnotes } { option-preamble-only }
265 { Option~'#1'~only~available~in~the~preamble~\msg_line_context:. }
266 \msg_new:nnn { postnotes } { missing-hyperref }
267 { Missing~'hyperref'~package.~Setting~'hyperref=false'. }

```


sort option

```
268 \bool_new:N \l__postnotes_sort_bool
269 \keys_define:nn { postnotes/setup }
270 {
271   sort .bool_set:N = \l__postnotes_sort_bool ,
272   sort .initial:n = true ,
273   sort .default:n = true ,
274 }
```

style option

```
275 \keys_define:nn { postnotes/setup }
276 {
277   style .choice: ,
278   style / endnotes .meta:n =
279   {
280     listenv = none ,
281     format =
282     {
283       \footnotesize
284       \setlength { \rightskip } { 0pt }
285       \setlength { \leftskip } { 0pt }
286       \setlength { \parindent } { 1.8em }
287     } ,
288     pretextmark = { \par } ,
```

endnotes uses a zero width box to get the desired alignment to the right, but that does not play well with the backlinks, so we have a little more work to do to get this right.

```
289     maketextmark =
290     {
291       \hbox_set:Nn \l_tmpa_box { \@textsuperscript { \normalfont ##1 } }
292       \skip_horizontal:n { - \box_wd:N \l_tmpa_box }
293       ##2 \box_use:N \l_tmpa_box ##3
294     } ,
295   } ,
296   style / pagenote .meta:n =
297   {
298     listenv = none ,
299     format = { } ,
300     pretextmark = { \par\noindent } ,
301     maketextmark = { { \normalfont ##2 ##1 . ##3 } } ,
302     posttextmark = { ~ } ,
303   } ,
304 }
```

\postnotesetup

\postnotesetup Provide \postnotesetup.

\postnotesetup{<options>}

```
305 \NewDocumentCommand \postnotesetup { m }
306 { \keys_set:nn { postnotes/setup } {#1} }
```

(End of definition for \postnotesetup.)

4 `\postnote`

Different from the traditional `\footnotemark` / `\footnotetext` system, in the context of end notes, the functionality which corresponds to `\footnotetext` is simply to store the data to be typeset later. Hence, some of the problems that afflict footnotes do not apply to end notes. Namely, and as far as I can tell, they can be used in “inner horizontal mode” (`\mbox` etc.), and in math mode, and if the “text” will be typeset in the same page as the “mark” is of little concern.

However, the separation between “mark” and “text” is still useful in other contexts: floats and contexts where multiple typesetting passes are performed. David Carlisle and Ulrike Fischer shared some thoughts on the matter at the TeX.SX chat: <https://chat.stackexchange.com/transcript/message/60754383#60754383>.

The interesting questions here are: if they are replaceable in their roles in these contexts and how much would we lose by providing them. In analyzing this, we have to distinguish two situations: when `\footnotemark` is called with no argument (and thus steps the counter), and when it is called with the optional argument (and thus refrains from stepping the counter).

For floats, the problem they pose is that they may disturb the *ordering* of the notes. This particular issue can be solved by using `\footnotemark` without argument, and manually adjusting the counter on subsequent calls to `\footnotetext`. A good example of the technique is <https://tex.stackexchange.com/a/43694>. True, a user may wish to specify the mark explicitly, but doesn’t necessarily need to do it to solve the ordering issue.

Multiple typesetting passes of content are much harder. And they abound: the standard classes’ `\caption` typesets the caption once, if it is short, but twice if it is longer than a line; `amsmath`’s math environments perform a measuring pass before actually typesetting the equations; `amsmath`’s `\text` macro runs the contents through `\mathchoice` (which typesets the contents four times) when in math mode; `tabularx` and `tabularray` also perform measuring passes of their tables; so does `csquotes`’ blockquotes; and certainly more that I’m unaware. A number of these places offer some one or another way to mitigate the issue: `amsmath`, `tabularx`, `csquotes` and (optionally) `tabularray` restore counter values after measuring steps; `amsmath` offers a boolean to indicate when it is a measuring pass; `csquotes` offers further handles. But the standard `\caption` offers none, and neither does `amsmath`’s `\text` macro. Well, the `pkgcaption` package can disable the multiple passes for `\caption` with the option `singlelinecheck`, but it is not reasonable to require it for our purposes, so we must assume the worst case.

Enrico Gregorio is categorical in stating that `\endnotemark` and `\endnotetext` are required for `enotez` to handle `\caption`, which apparently it didn’t offer originally: “The package should implement `\endnotemark` and `\endnotetext` for this case. According to the documentation, the author deems them to not be needed: he’s wrong.” (<https://tex.stackexchange.com/a/314937>). See also <https://tex.stackexchange.com/a/43794> and <https://tex.stackexchange.com/a/358207>.

In this scenario, when there’s no way around the multiple passes, `\footnotemark` can only handle the general case if used with an argument, precisely because it inhibits the stepping of the counter. Otherwise the counter is stepped multiple times, and we’d get the wrong number (and mark). In some circumstances, if we know the number of passes is deterministic, we might get away by adjusting the counter manually (`\caption` may be dealt with this way: if we know it to be two lines, we can decrement the counter before it and get correct results, even hyperlinked). But in cases which adjusting the counter is sufficient, end notes can be dealt with in the same way, and doesn’t need the

separation between “mark” and “text”. So, what is distinctive of the kernel’s footnote apparatus, which allows it as much flexibility as one would like, is receiving an arbitrary number as argument and not stepping the counter. And as far as `\footnotemark` and `\footnotetext` are concerned, the main point of the optional argument is really to “manually establish the relation” between the two of them. So, if *not stepping the counter* is what is needed to handle the general case, is it viable to do so? What would we lose in so doing?

When receiving an arbitrary number as argument, as the kernel functionality for footnotes and other endnotes packages do, this value is expected to be printed as such, hence it must correspond to the `postnote` counter (in our case). But this counter is in the hands of the user, and can be reset along the document, thus its uniqueness cannot be ensured. But not stepping `postnote` is perfectly viable, as it just aims at storing how the mark is to be typeset. However, not stepping the ID counter would complicate things considerably. Not doing so implies we’d lose the connection we have between the “mark” and the corresponding “text”. We might add the “text” to the queue, but all the metadata would be lost, including the `hyperref` anchor, but really the set of data without which the kind of functionality offered would be nonviable, or severely hampered. Not stepping `postnote` but stepping the ID counter also is not sufficient, because we’d get a note in duplicity. We could naively think that a gap in the ID is not a problem, and just not add the duplicate to the queue. But how could we tell the difference between a legitimate and an illegitimate step of the ID counter?

I have not been able to devise a way to “reconnect” “text” and “mark” in the absence of the unique ID counter. The most promising idea was to have mandatory arguments to `\postnotemark` and `\postnotetext` receiving a *label* which we could use to identify their counterparts, but I was not able to go through with this, and the attempts all increased complexity considerably. It is not just a label/ref system, there’s got to be a one-to-one correspondence between the sets, uniqueness has to be ensured on both sides, and there cannot be “lone” marks or texts (a bijection). Besides, this label based system of identification would have to live side-by-side with the one based on the counter. So, even if we’d have unique IDs, we wouldn’t know beforehand in what form it comes. Considering the ID is used to build the variable name in which we store the note’s information, this would also complicate things.

Besides, there are ways to get things working with multiple passes without the “mark”/“text” partition. As mentioned, there are a number of cases which offer some kind of “handle” or way to identify the multiple passes. `csquotes` has a dedicated hook that can be used. `amsmath` sets the `measuring@` boolean (which `hyperref` also defines). So, not all cases are as tricky as `\caption` or `\text`, and even that can be decently dealt with without a separation between “mark” and “text”. Besides, in difficult cases, the package offers a `nomark` option to `\postnote` to place a note, but typeset no mark. Then we can typeset a mark with `\postnoteref` referring to a `\label` in the note of interest. This would result in a correct mark without duplicity, and in a correct link from there to the note’s text at `\printpostnotes`. The drawback is that the placement of `\postnote` would be important, and results sensitive to it. All the metadata is collected at the point of `\postnote`, anchor included, not at the point of `\postnoteref`. So the consequences are a slightly off backlink, possibly imprecise metadata, etc. Considering `hyperref` itself shies away completely from linking `\footnotemark` with an argument, I’d say there’s some gain.

The truth is there are some trade-offs, there’s no “ideal” solution. Still, all in all, my judgment is that the unique ID counter is worth more than the inconveniences of an occasional `\postnote[nomark]` referenced with `\postnoteref`, and even that should not

be needed much. So, for the time being, until something else shakes this balance, I won't be offering `\postnotemark` and `\postnotetext`.

For the `hyperref` support for cross-references in `\postnote`, I've moved back and forth quite a lot. One of the ideas I fancied was using `\refstepcounter` and let `hyperref` do its job. But, since I want to have control of the anchor/destination name on both “sides”, I'd have to set `\theHpostnote` locally before calling `\refstepcounter`, otherwise results might be sensitive to user calls to `\counterwithin` (see <https://github.com/latex3/hyperref/issues/230>, thanks Ulrike Fischer). However, even if that worked well for the default case, we still had to setup things manually, in case of a manually supplied mark. All in all, I'm just calling `\stepcounter`, setting the relevant cross-reference variables once and setting the anchor manually.

`postnote` is the public, user facing, counter for `\postnote`. It determines how the note's mark gets to be typeset. It can be reset, set, and have its printed representation changed. Of course, whether those are meaningful is up to the user.

```
307 \newcounter { postnote }
```

`\g__postnotes_note_id_int` `\g__postnotes_note_id_int` is the internal, unique counter which provides the ID number of each note. It ties “mark” and “text” together, is also the connection between each note and its data, including the content, which is stored in a property list named according to `__postnotes_data_name:n` and the ID number. `\l_postnotes_note_id_tl` is a convenience variable storing the counter's value. `\g__postnotes_queue_seq` stores the sequence of notes' IDs to be processed by the next call of `\printpostnotes`.

```
308 \int_new:N \g__postnotes_note_id_int
309 \tl_new:N \l_postnotes_note_id_tl
310 \tl_set:Nn \l_postnotes_note_id_tl { \int_use:N \g__postnotes_note_id_int }
311 \seq_new:N \g__postnotes_queue_seq
```

(End of definition for `\g__postnotes_note_id_int`, `\l_postnotes_note_id_tl`, and `\g__postnotes_queue_seq`. This function is documented on page ??.)

`\postnote` Provide `\postnote`.

```
\postnote [<options>] {\<note text>}
```

```
312 \NewDocumentCommand \postnote { 0 { } +m }
313 { \__postnotes_note:nn {#1} {#2} }
```

(End of definition for `\postnote`.)

`__postnotes_note:nn` The internal version of `\postnote`. The `postnotes/note/begin` hook is meant to provide a place from where some additional setup for the note can be performed. This is being used for adding support for some features/packages, but can also be used, for example, to add an extra local property for `zref`.

```
\__postnotes_note:nn [<options>] {\<note content>}
```

```

314 \NewHook { postnotes/note/begin }
315 \cs_new_protected:Npn \__postnotes_note:nn #1#2
316 {
317   \group_begin:
318   \keys_set:nn { postnotes/note } {#1}
319   \__postnotes_inhibit_note:F
320   {
321     \int_gincr:N \g__postnotes_note_id_int
322     \tl_if_empty:NT \l__postnotes_mark_tl
323     {
324       \stepcounter { postnote }
325       \tl_set:Nx \l__postnotes_mark_tl { \thepostnote }
326     }
327     \seq_gput_right:Nx \g__postnotes_queue_seq
328     { \l_postnotes_note_id_tl }
329     \UseHook { postnotes/note/begin }
330     \cs_set:Npn \@currentcounter { postnote }
331     \cs_set:Npx \@currentlabel { \p@postnote \l__postnotes_mark_tl }
332     \MakeLinkTarget* { postnote. \l_postnotes_note_id_tl .mark }
333     \__postnotes_set_mark_page_label:x { \l_postnotes_note_id_tl }
334     \__postnotes_set_user_labels:
335     \bool_if:NF \l__postnotes_nomark_bool
336     {
337       \__postnotes_typeset_mark:xV
338       { \l_postnotes_note_id_tl } \l__postnotes_mark_tl
339     }
340     \__postnotes_store:nn { \l_postnotes_note_id_tl } {#2}
341   }
342   \group_end:
343 }

```

(End of definition for __postnotes_note:nn.)

Options for \postnote.

```

344 \tl_new:N \l__postnotes_mark_tl
345 \bool_new:N \l__postnotes_nomark_bool
346 \fp_new:N \l__postnotes_sort_num_fp
347 \tl_new:N \l__postnotes_note_label_tl
348 \bool_new:N \l__postnotes_manual_sortnum_bool
349 \bool_new:N \l__postnotes_maybe_multi_bool
350 \keys_define:nn { postnotes/note }
351 {
352   markstr .tl_set:N = \l__postnotes_mark_tl ,
353   markstr .value_required:n = true ,
354   sortnum .code:n =
355   {
356     \fp_set:Nn \l__postnotes_sort_num_fp {#1}
357     \bool_set_true:N \l__postnotes_manual_sortnum_bool
358   } ,
359   sortnum .value_required:n = true ,
360   mark .meta:n =
361   {
362     markstr = {#1} ,
363     sortnum = {#1} ,

```

```

364     } ,
365     mark .value_required:n = true ,
366     nomark .bool_set:N = \l__postnotes_nomark_bool ,
367     nomark .default:n = true ,
368     label .tl_set:N = \l__postnotes_note_label_tl ,
369     label .value_required:n = true ,
370 }

```

`__postnotes_inhibit_note:TF` In contexts of multiple passes of content, it may be needed, or preferred, to inhibit the note altogether to avoid side effects and duplicity. This conditional, obviously, will always return the true branch unless something is done in the `postnotes/note/inhibit` hook. This hook is meant to handle support for packages or features which may justify note inhibition, and the code there should set `\l__postnotes_inhibit_note_bool`, `\l__postnotes_print_plain_mark_bool` and `\l__postnotes_print_plain_mark_stepcounter_bool` as appropriate to the case.

```

371 \bool_new:N \l__postnotes_inhibit_note_bool
372 \bool_new:N \l__postnotes_print_plain_mark_bool
373 \bool_new:N \l__postnotes_print_plain_mark_stepcounter_bool
374 \NewHook { postnotes/note/inhibit }
375 \prg_new_protected_conditional:Npnn \__postnotes_inhibit_note: { F }
376 {
377     \bool_set_false:N \l__postnotes_inhibit_note_bool
378     \bool_set_false:N \l__postnotes_print_plain_mark_bool
379     \bool_set_false:N \l__postnotes_print_plain_mark_stepcounter_bool
380     \UseHook { postnotes/note/inhibit }

```

Printing a plain mark here may be needed because, if we are inhibiting the note in a “measuring context” and omit it completely, the measuring being performed will be off by the size of the mark. So, to ensure the measuring can be done correctly, we place the mark. What to do with the counter itself, depends on the situation. In places that are known to restore the counter values after the measuring pass, we can let the counter be stepped. And, actually we should do so, for example, in a `tabularx` with multiple postnotes, if we don’t step the counter, all the measuring will be done with the number of the first note. Otherwise, we don’t actually step the counter but, to typeset correctly the mark that would be printed if the counter had been stepped, we increment `\c@postnote` locally and grouped, and smuggle `\thepostnote` out of the group.

```

381 \bool_if:NT \l__postnotes_print_plain_mark_bool
382 {
383     \tl_if_empty:NT \l__postnotes_mark_tl
384     {
385         \bool_if:NTF \l__postnotes_print_plain_mark_stepcounter_bool
386         {
387             \stepcounter { postnote }
388             \tl_set:Nx \l__postnotes_mark_tl { \thepostnote }
389         }
390         {
391             \group_begin:
392             \int_incr:N \c@postnote
393             \exp_args:NNNx
394             \group_end:
395             \tl_set:Nn \l__postnotes_mark_tl { \thepostnote }
396         }
397     }

```

```

398     \_postnotes_typeset_mark_wrapper:n
399     { \_postnotes_make_mark:nnn { \l__postnotes_mark_tl } { } { } }
400   }
401   \bool_if:NTF \l__postnotes_inhibit_note_bool
402   { \prg_return_true:  }
403   { \prg_return_false: }
404 }

```

(End of definition for _postnotes_inhibit_note:TF.)

_postnotes_typeset_mark:nn Auxiliary functions for mark typesetting in _postnotes_note:nn. _postnotes_typeset_mark_wrapper:n is based on the definition of \@footnotemark in the kernel.

```

    \_postnotes_typeset_mark:nn {<note id>} {<mark>}
    \_postnotes_typeset_mark_wrapper:n {<mark>}

405 \cs_new_protected:Npn \_postnotes_typeset_mark:nn #1#2
406 {
407   \_postnotes_typeset_mark_wrapper:n
408   {
409     \bool_if:NTF \l__postnotes_hyperlink_bool
410     {
411       \_postnotes_make_mark:nnn {#2}
412       { \hyper@linkstart { link } { postnote. #1 .text } }
413       { \hyper@linkend }
414     }
415     { \_postnotes_make_mark:nnn {#2} { } { } }
416   }
417 }
418 \cs_generate_variant:Nn \_postnotes_typeset_mark:nn { xV }
419 \tl_new:N \l__postnotes_saved_spacefactor_tl
420 \cs_new_protected:Npn \_postnotes_typeset_mark_wrapper:n #1
421 {
422   \mode_leave_vertical:
423   \mode_if_horizontal:T
424   {
425     \tl_set:Nx \l__postnotes_saved_spacefactor_tl { \the\spacefactor }
426     \nobreak
427   }
428   #1
429   \mode_if_horizontal:T
430   { \spacefactor \l__postnotes_saved_spacefactor_tl }
431   \scan_stop:
432 }

```

(End of definition for _postnotes_typeset_mark:nn and _postnotes_typeset_mark_wrapper:n.)

_postnotes_set_user_labels: Auxiliary function for user label setting in _postnotes_note:nn. Supports the label and zlabel options of \postnote.

```

433 \cs_new_protected:Npn \_postnotes_set_user_labels:
434 {
435   \tl_if_empty:NF \l__postnotes_note_label_tl
436   { \exp_args:NV \label \l__postnotes_note_label_tl }
437   \tl_if_empty:NF \l__postnotes_note_zlabel_tl

```

```

438     { \exp_args:NV \zlabel \l__postnotes_note_zlabel_tl }
439   }

```

(End of definition for `__postnotes_set_user_labels:.`)

5 `\postnoteref`

`\postnoteref` Provide `\postnoteref`.

```

\postnoteref<*>{\<label>}

440 \NewDocumentCommand \postnoteref { s m }
441   { \__postnotes_note_ref:nn {#1} {#2} }

```

(End of definition for `\postnoteref`.)

`__postnotes_note_ref:nn` The internal version of `\postnoteref`.

```

\__postnotes_note_ref:nn {\<star bool>} {\<label>}

442 \cs_new_protected:Npn \__postnotes_note_ref:nn #1#2
443   {
444     \group_begin:
445     \__postnotes_typeset_mark_wrapper:n
446       {
447         \bool_lazy_and:nnTF
448           { ! #1 }
449           { \l__postnotes_hyperlink_bool }
450           {
451             \hyperref [ #2 ]
452               { \__postnotes_make_mark:nnn { \ref*{#2} } { } { } }
453           }
454           { \__postnotes_make_mark:nnn { \ref*{#2} } { } { } }
455       }
456     \group_end:
457   }

```

(End of definition for `__postnotes_note_ref:nn`.)

6 `\postnotesection`

`\postnotesection` Provide `\postnotesection` and `\postnotesectionx`.
`\postnotesectionx`

```

\postnotesection[\<options>]{\<section content>}
\postnotesectionx[\<options>]{\<section content>}

458 \NewDocumentCommand \postnotesection { 0 { } +m }
459   { \__postnotes_section:nn {#1} {#2} }
460 \NewDocumentCommand \postnotesectionx { 0 { } +m }
461   {
462     % NOTE Command deprecated in 2022-12-27 for v0.2.0.
463     \msg_warning:nn { postnotes } { postnotesectionx-deprecated }
464     \postnotesection [ #1 , exp ] {#2}

```



```

465 }
466 \msg_new:nnn { postnotes } { postnotessectionx-deprecated }
467 {
468   '\iow_char:N\postnotessectionx'~is~deprecated~\msg_line_context:~
469   Use~the~'exp'~option~of~'\iow_char:N\postnotessection'~instead.
470 }

```

(End of definition for \postnotessection and \postnotessectionx.)

__postnotes_section:nn The internal version of \postnotessection.

```

      \__postnotes_section:nn {<options>} {<content>}
471 \int_new:N \g__postnotes_sectid_int
472 \cs_new_protected:Npn \__postnotes_section:nn #1#2
473 {
474   \group_begin:
475   \int_gincr:N \g__postnotes_sectid_int
476   \int_gincr:N \g__postnotes_note_id_int
477   \seq_gput_right:Nx \g__postnotes_queue_seq { \l_postnotes_note_id_tl }
478   \tl_gclear:N \g__postnotes_section_name_tl
479   \keys_set:nn { postnotes/section } {#1}
480   \bool_if:NTF \l__postnotes_section_exp_bool
481     { \__postnotes_store_section:nx { \l_postnotes_note_id_tl } {#2} }
482     { \__postnotes_store_section:nn { \l_postnotes_note_id_tl } {#2} }
483   \group_end:
484 }

```

(End of definition for __postnotes_section:nn.)

Options for \postnotessection. Actually, I would have preferred to use “label” for the name option, but I feared I might need it further down the road for the traditional meaning.

```

485 \tl_new:N \g__postnotes_section_name_tl
486 \bool_new:N \l__postnotes_section_exp_bool
487 \keys_define:nn { postnotes/section }
488 {
489   name .tl_gset:N = \g__postnotes_section_name_tl ,
490   name .value_required:n = true ,
491   exp .bool_set:N = \l__postnotes_section_exp_bool ,
492   exp .initial:n = false ,
493   exp .default:n = true ,
494 }

```

7 \printpostnotes

\printpostnotes Provide \printpostnotes.

```

      \printpostnotes
495 \NewDocumentCommand \printpostnotes { }
496 { \__postnotes_print_notes: }

```

(End of definition for \printpostnotes.)

<code>\pnthechapter</code>	User facing variables, aimed at making available some of the notes' and sections' metadata
<code>\pnthesection</code>	for the user at specific contexts.
<code>\pnthechapternextnote</code>	497 <code>\tl_new:N \pnthechapter</code>
<code>\pnthesectionnextnote</code>	498 <code>\tl_new:N \pnthesection</code>
<code>\pnthepage</code>	499 <code>\tl_new:N \pnthechapternextnote</code>
	500 <code>\tl_new:N \pnthesectionnextnote</code>
	501 <code>\tl_new:N \pnthepage</code>

(End of definition for `\pnthechapter` and others.)

<code>\g__postnotes_print_postnotes_int</code>	Auxiliary variables for <code>__postnotes_print_notes:</code>
<code>\l__postnotes_print_note_id_tl</code>	502 <code>\int_new:N \g__postnotes_print_postnotes_int</code>
<code>\l__postnotes_print_note_id_next_tl</code>	503 <code>\tl_new:N \l__postnotes_print_note_id_tl</code>
<code>\l__postnotes_print_counter_tl</code>	504 <code>\tl_new:N \l__postnotes_print_note_id_next_tl</code>
<code>\l__postnotes_print_mark_tl</code>	505 <code>\tl_new:N \l__postnotes_print_counter_tl</code>
<code>\l__postnotes_print_type_curr_tl</code>	506 <code>\tl_new:N \l__postnotes_print_mark_tl</code>
<code>\l__postnotes_print_type_next_tl</code>	507 <code>\tl_new:N \l__postnotes_print_type_curr_tl</code>
<code>\l__postnotes_print_type_prev_tl</code>	508 <code>\tl_new:N \l__postnotes_print_type_next_tl</code>
<code>\l__postnotes_print_content_tl</code>	509 <code>\tl_new:N \l__postnotes_print_type_prev_tl</code>
<code>\l__postnotes_clear_queue_seq</code>	510 <code>\tl_new:N \l__postnotes_print_content_tl</code>
	511 <code>\seq_new:N \l__postnotes_clear_queue_seq</code>

(End of definition for `\g__postnotes_print_postnotes_int` and others. This function is documented on page ??.)

`__postnotes_print_notes:` hooks. Both meant at providing points of entry for additional setup, specially to add support to packages and features which require it. The `postnotes/print/begin` hook is run early in `__postnotes_print_notes:` and only once per call, after the user options have been processed. The `postnotes/print/note/begin` hook is run once for each note, at the point where environment variables are being set or restored, before the typesetting of either the mark or the text, but within a group of its own of each note.

```

512 \NewHook { postnotes/print/begin }
513 \NewHook { postnotes/print/note/begin }

```

The `postnotetext` is a counter used to restore the original value of `postnote` at the time of printing, for the purposes of cross-referencing, it should be different from `postnote` if a note may occur inside `\printpostnotes`. The `postnotessection` is a counter which is stepped for every postnote section which gets to be actually typeset. It's aim is to provide a valid "enclosing counter" to `postnote` in the context of `\printpostnotes`. Since we don't know where `postnote` may have been reset along the document, in the general case, we can't rely on any other preexisting counter. This means that the particular value of `postnotessection` is of little practical meaning, it really is just meant to provide recognizable "bounds" for `postnote` along the printing of the notes. Indeed, it is initialized to a very high value (larger than the conceivable number of postnote sections in a document), so that "marks" and "texts" don't mix in the same reference list, which would occur if the enclosing counters of both belonged to the same range, and with somewhat arbitrary results, since we cannot ensure the step of the enclosing counter along the document matches `postnotessection`. This is actually a tricky problem from the cross-referencing standpoint: two different things, which should be of the same type, are reset along the document, but shouldn't really be mixed together. They are both L^AT_EX 2_ε counters, since they may be required externally. Their

main intended use case is to support zref-clever, but in principle they can be of general use.

```

514 \newcounter { postnotetext }
515 \newcounter { postnotessection }
516 \setcounter { postnotessection } { 10000 }

```

`__postnotes_print_notes:` The internal version of `\printpostnotes`.

```

\__postnotes_print_notes:

517 \cs_new_protected:Npn \__postnotes_print_notes:
518 {
519   \group_begin:
520   \int_gincr:N \g__postnotes_print_postnotes_int
521   \seq_if_empty:NTF \g__postnotes_queue_seq
522     { \msg_warning:nn { postnotes } { empty-printpostnotes } }
523     {
524       \pnheading
525       \UseHook { postnotes/print/begin }
526       \tl_set:Nn \l__postnotes_print_type_prev_tl { open }
527       \seq_set_eq:NN \l__postnotes_clear_queue_seq \g__postnotes_queue_seq
528       \__postnotes_verify_multipass:N \g__postnotes_queue_seq
529       \bool_if:NT \l__postnotes_sort_bool
530         { \__postnotes_sort_queue:N \g__postnotes_queue_seq }
531       \bool_gset_true:N \g__postnotes_header_vars_next_bool
532       \__postnotes_get_headers_data:N \g__postnotes_queue_seq
533       \__postnotes_set_headers_vars_first:

```

Ensure the first note after a heading has paragraph indentation when `listenv` is `none`. `endnotes` uses a workaroundsish solution in `\enoteheading`, setting a box and then skipping back a line. Enrico Gregorio is correct, though, in criticizing it at https://tex.stackexchange.com/q/575905#comment1450213_575915, and suggests the use of `\@afterindenttrue`, which is what `indentfirst` does (we do the same, just locally).

```

534   \bool_if:NF \l__postnotes_print_as_list_bool
535   {
536     \cs_set_eq:NN \@afterindentfalse \@afterindenttrue
537     \@afterindenttrue
538   }
539   \bool_until_do:nn { \seq_if_empty_p:N \g__postnotes_queue_seq }
540   {
541     \seq_gpop_left:NN \g__postnotes_queue_seq
542     \l_postnotes_print_note_id_tl
543     \__postnotes_prop_get:nnN { \l_postnotes_print_note_id_tl }
544       { type } \l__postnotes_print_type_curr_tl
545     \tl_if_eq:NnTF \l__postnotes_print_type_curr_tl { section }
546       { % type_curr = 'section'
547         \seq_if_empty:NTF \g__postnotes_queue_seq
548           {
549             \tl_set:Nn \l__postnotes_print_note_id_next_tl { noid }
550             \tl_set:Nn \l__postnotes_print_type_next_tl { close }
551           }
552           {
553             \seq_get_left:NN \g__postnotes_queue_seq
554             \l__postnotes_print_note_id_next_tl

```

```

555         \__postnotes_prop_get:nnN
556         { \l__postnotes_print_note_id_next_tl }
557         { type } \l__postnotes_print_type_next_tl
558     }

```

We only process the entry if type_next is note: here are skipped empty sections.

```

559     \tl_if_eq:NnT \l__postnotes_print_type_next_tl { note }
560     {
561         \stepcounter { postnotessection }
562         \group_begin:
563         \__postnotes_prop_get:nnN
564         { \l__postnotes_print_note_id_tl }
565         { thechapter } \pnthechapter
566         \__postnotes_prop_get:nnN
567         { \l__postnotes_print_note_id_tl }
568         { thesection } \pnthesection
569         \__postnotes_prop_get:nnN
570         { \l__postnotes_print_note_id_next_tl }
571         { thechapter } \pnthechapternextnote
572         \__postnotes_prop_get:nnN
573         { \l__postnotes_print_note_id_next_tl }
574         { thesection } \pnthesectionnextnote
575         \__postnotes_prop_get:nnN
576         { \l__postnotes_print_note_id_tl }
577         { content } \l__postnotes_print_content_tl
578         \l__postnotes_print_content_tl
579         \group_end:

```

Set type_prev for the next iteration.

```

580         \tl_set:NV \l__postnotes_print_type_prev_tl
581         \l__postnotes_print_type_curr_tl
582     }
583 }
584 { % type_curr = 'note'
585     \tl_if_eq:NnF \l__postnotes_print_type_prev_tl { note }
586     {
587         \bool_if:NTF \l__postnotes_print_as_list_bool
588         { \exp_args:Nx \begin { \l__postnotes_print_env_tl } }
589         { \group_begin: }
590         \l__postnotes_print_format_tl
591     }
592     \group_begin:
593     \UseHook { postnotes/print/note/begin }
594     \__postnotes_get_pageref:Nx \pnthechapter
595     { mark@ \l__postnotes_print_note_id_tl }
596     \__postnotes_prop_get:nnN
597     { \l__postnotes_print_note_id_tl }
598     { mark } \l__postnotes_print_mark_tl
599     \__postnotes_prop_get:nnN
600     { \l__postnotes_print_note_id_tl }
601     { counter } \l__postnotes_print_counter_tl
602     \__postnotes_prop_get:nnN
603     { \l__postnotes_print_note_id_tl }
604     { content } \l__postnotes_print_content_tl
605     \cs_set:Npn \@currentcounter { postnotetext }

```

```

606 \int_set:Nn \c@postnotetext
607 { \l__postnotes_print_counter_tl }
608 \cs_set:Npx \@currentlabel
609 { \p@postnote \l__postnotes_print_mark_tl }
610 \__postnotes_text_mark_wrapper:n
611 {
612   \MakeLinkTarget*
613   { postnote. \l__postnotes_print_note_id_tl .text }
614   \__postnotes_set_text_page_label:x
615   { \l__postnotes_print_note_id_tl }
616   \__postnotes_typeset_text_mark:eV
617   { \l__postnotes_print_note_id_tl }
618   \l__postnotes_print_mark_tl
619 }
620 \l__postnotes_print_content_tl
621 \l__postnotes_post_printnote_tl
622 \group_end:

```

For notes, query for next note’s type *after* the current note was typeset, to handle possible nesting. Even if nesting is not a feature, this should avoid hard crashes related to “lonely \item” or “extra \endgroup” errors, in case it occurs.

```

623 \seq_if_empty:NTF \g__postnotes_queue_seq
624 {
625   \tl_set:Nn \l__postnotes_print_note_id_next_tl { noid }
626   \tl_set:Nn \l__postnotes_print_type_next_tl { close }
627 }
628 {
629   \seq_get_left:NN \g__postnotes_queue_seq
630   \l__postnotes_print_note_id_next_tl
631   \__postnotes_prop_get:nnN
632   { \l__postnotes_print_note_id_next_tl }
633   { type } \l__postnotes_print_type_next_tl
634 }
635 \tl_if_eq:NnF \l__postnotes_print_type_next_tl { note }
636 {
637   \bool_if:NTF \l__postnotes_print_as_list_bool
638   { \exp_args:Nx \end { \l__postnotes_print_env_tl } }
639   { \group_end: }

```

Ensure \par at the end of \printopostnotes (see <https://github.com/u-fischer/tagpdf/issues/68#issuecomment-1587343876>, thanks Ulrike Fischer).

```

640 \par
641 }

```

Set type_prev for the next iteration.

```

642 \tl_set:NV \l__postnotes_print_type_prev_tl
643 \l__postnotes_print_type_curr_tl
644 }
645 }
646 \AddToHookNext { shipout/after }
647 { \bool_gset_false:N \g__postnotes_header_vars_next_bool }

```

We won’t use the variables anymore, clear them to reduce memory usage. Given how we populated \l__postnotes_clear_queue_seq, this won’t catch nested notes. But it’s

not worth to conditionally add new items along the way (testing it every iteration) for this. Again, not a feature.

```

648         \seq_map_inline:Nn \l__postnotes_clear_queue_seq
649         { \l__postnotes_prop_gclear:n { ##1 } }
650     }
651     \group_end:
652 }

```

(End of definition for `__postnotes_print_notes:.`)

```

653 \msg_new:nnn { postnotes } { empty-printpostnotes }
654 { Empty~'\iow_char:N\printpostnotes'\msg_line_context:. }

```

`__postnotes_typeset_text_mark:nn` Auxiliary functions for mark typesetting in `__postnotes_print_notes:.`
`__postnotes_text_mark_wrapper:n`

```

        \__postnotes_typeset_text_mark:nn {<note id>} {<mark>}
        \__postnotes_text_mark_wrapper:n {<mark>}

655 \cs_new_protected:Npn \__postnotes_typeset_text_mark:nn #1#2
656 {
657     \bool_lazy_and:nnTF
658     { \l__postnotes_hyperlink_bool }
659     { \l__postnotes_backlink_bool }
660     {
661         \__postnotes_make_text_mark:nnn {#2}
662         { \hyper@linkstart { link } { postnote. #1 .mark } }
663         { \hyper@linkend }
664     }
665     { \__postnotes_make_text_mark:nnn {#2} { } { } }
666 }
667 \cs_generate_variant:Nn \__postnotes_typeset_text_mark:nn { eV }
668 \cs_new_protected:Npn \__postnotes_text_mark_wrapper:n #1
669 {
670     \bool_if:NTF \l__postnotes_print_as_list_bool
671     {
672         \item [ \l__postnotes_pre_textmark_tl #1 \l__postnotes_post_textmark_tl ]

```

Leave vertical mode to avoid “perhaps a missing `\item`” error for empty notes.

```

673         \mode_leave_vertical:
674     }
675     { \l__postnotes_pre_textmark_tl #1 \l__postnotes_post_textmark_tl }
676 }

```

(End of definition for `__postnotes_typeset_text_mark:nn` and `__postnotes_text_mark_wrapper:n`.)

Print auxiliary

`__postnotes_verify_multipass:N` provides a general procedure for handling cases of multiple passes of content. Ideally, the job should be done at `__postnotes_inhibit_note:F`, if at all possible. But, failing that, we can rely on the fact that `\postnotes` of measuring/trial passes don’t end up being output and hence don’t generate labels in the `.aux` file. This is the equivalent for `postnotes` to the effect of write restrictions for the packages based on external files, which is how they actually handle these cases. However, despite this being a general test, and a reasonable one, I’d like to restrain it’s

use to the minimum possible. First, using this criterion across the board would result in large swings on the content of `\printpostnotes` and spurious warnings in an initial compilation since the labels are not available on the first run. Second, I'd prefer not to interfere with the queue, unless we really need to. Hence, we only apply this check for “eligible” items. For signaling this eligibility, the note must have been stored with the `\l__postnotes_maybe_multi_bool` set to `true`, which is then saved in the `multibool` property. One implication of this procedure is that, if there are any new notes marked as `multibool`, three rounds of compilation will be needed, since the labels of the printed notes will be written only on the second run and the document will thus require a third one to stabilize.

```
\__postnotes_verify_multipass:N \__postnotes_verify_multipass:N (\g__postnotes_queue_seq)
677 \cs_new_protected:Npn \__postnotes_verify_multipass:N #1
678 {
679   \group_begin:
680   \seq_clear:N \l_tmpa_seq
681   \seq_map_inline:Nn #1
682   {
683     \__postnotes_prop_get:nnN {##1} { multibool } \l_tmpa_tl
684     \tl_if_eq:NnTF \l_tmpa_tl { true }
685     {
686       \cs_if_exist:cT
687       { \c__postnotes_ref_prefix_tl @ mark@ ##1 }
688       { \seq_put_right:Nn \l_tmpa_seq {##1} }
689     }
690     { \seq_put_right:Nn \l_tmpa_seq {##1} }
691   }
692   \seq_gset_eq:NN #1 \l_tmpa_seq
693   \group_end:
694 }
```

(End of definition for `__postnotes_verify_multipass:N`.)

`__postnotes_sort_queue:N` Sorting function for `__postnotes_print_notes:.`

```
\__postnotes_sort_queue:N (\g__postnotes_queue_seq)
695 \cs_new_protected:Npn \__postnotes_sort_queue:N #1
696 {
697   \group_begin:
698   \seq_gsort:Nn #1
699   {
700     \__postnotes_prop_get:nnN {##1} { pnsectid } \l_tmpa_tl
701     \__postnotes_prop_get:nnN {##2} { pnsectid } \l_tmpb_tl
702     \tl_if_eq:NNTF \l_tmpa_tl \l_tmpb_tl
703     {
704       \__postnotes_prop_get:nnN {##1} { type } \l_tmpa_tl
705       \__postnotes_prop_get:nnN {##2} { type } \l_tmpb_tl
706       \bool_lazy_and:nnTF
707       { \str_if_eq_p:Vn \l_tmpa_tl { note } }
708       { \str_if_eq_p:Vn \l_tmpb_tl { note } }
709       {
710         \__postnotes_prop_get:nnN {##1} { sortnum } \l_tmpa_tl
```

```

711         \_postnotes_prop_get:nnN {##2} { sortnum } \l_tmpb_tl
712         \fp_compare:nNnTF { \l_tmpa_tl } > { \l_tmpb_tl }
713         { \sort_return_swapped: }
714         { \sort_return_same: }
715     }
716     { \sort_return_same: }
717 }
718 { \sort_return_same: }
719 }
720 \group_end:
721 }

```

(End of definition for `_postnotes_sort_queue:N`.)

8 Headers

The headers infrastructure of `postnotes` is comprised of three basic parts:

1. For each `\postnote`, labels are set storing the `page` where the note occurs. Each note actually generates a pair of such labels, once when `\postnote` is called (with the mark), and another where the note is printed (in `\printpostnotes`). The former ones store `\thepage`, since we want the printed representation of it for typesetting purposes, the latter ones store the value of the `page` counter, since we don't need to typeset it, but do need to perform algebraic operations with it. These labels are set by `_postnotes_set_mark_page_label:n`, `_postnotes_set_text_page_label:n`, and `_postnotes_set_print_page_label:n` at the appropriate places. The set of these labels provides a mapping from each note's "mark" and "text" to the page where it occurs.
2. This information set is processed by `_postnotes_get_headers_data:N` at the beginning of `_postnotes_print_notes:` to identify the first and last note of each page in `\printpostnotes`, and to generate a mapping from these first and last notes on each page to the pages where their corresponding marks occur. We also take the opportunity to enrich this mapping with other metadata of each note. So we get also mappings from the first and last note on each page to `\thechapter`, `\thesection`, and the `name` of the section in which they occur. These mappings are stored in property lists `\g__postnotes_header_⟨info⟩_first_prop` and `\g__postnotes_header_⟨info⟩_last_prop` where the `key` is the page in `\printpostnotes` where their note's content is typeset (or rather where it starts to be typeset, it is the page where the text's mark is printed).
3. Based on these mappings, along the span of notes section we run `_postnotes_set_headers_vars_next:` at each `shipout/before` hook to set user facing variables for the *next* page, which will be available when their heading gets typeset. Given that at `shipout` we can rely on a correct value of the `page` counter, we use it as `key` to query the property lists generated in the previous step. These user facing variables are called `\pnhd⟨info⟩first` and `\pnhd⟨info⟩last`. Since we cannot rely on the shipout hook for the first page of `\printpostnotes`, `_postnotes_set_headers_vars_first:` is run at its beginning to ensure correct values are in place on the first page of the notes section.

These `\pnhd<info>first` and `\pnhd<info>last` variables can then be used to build simple functions which can be passed to mark commands to achieve rich contextual running headers.

<code>\pnhdpagefirst</code>	User facing variables, aimed at making available header data for the user. Setting these
<code>\pnhdpagelast</code>	variables with correct values at the moment the header gets typeset is <i>the</i> objective of
<code>\pnhdchapfirst</code>	the whole headers infrastructure of the package.
<code>\pnhdchaplast</code>	
<code>\pnhdsectfirst</code>	722 <code>\tl_new:N \pnhdpagefirst</code>
<code>\pnhdsectlast</code>	723 <code>\tl_new:N \pnhdpagelast</code>
<code>\pnhdnamefirst</code>	724 <code>\tl_new:N \pnhdchapfirst</code>
<code>\pnhdnamelast</code>	725 <code>\tl_new:N \pnhdchaplast</code>
	726 <code>\tl_new:N \pnhdsectfirst</code>
	727 <code>\tl_new:N \pnhdsectlast</code>
	728 <code>\tl_new:N \pnhdnamefirst</code>
	729 <code>\tl_new:N \pnhdnamelast</code>

(End of definition for `\pnhdpagefirst` and others.)

<code>\g__postnotes_header_page_first_prop</code>	Auxiliary variables for the headers infrastructure.
<code>\g__postnotes_header_page_last_prop</code>	730 <code>\prop_new:N \g__postnotes_header_page_first_prop</code>
<code>\g__postnotes_header_chap_first_prop</code>	731 <code>\prop_new:N \g__postnotes_header_page_last_prop</code>
<code>\g__postnotes_header_chap_last_prop</code>	732 <code>\prop_new:N \g__postnotes_header_chap_first_prop</code>
<code>\g__postnotes_header_sect_first_prop</code>	733 <code>\prop_new:N \g__postnotes_header_chap_last_prop</code>
<code>\g__postnotes_header_sect_last_prop</code>	734 <code>\prop_new:N \g__postnotes_header_sect_first_prop</code>
<code>\g__postnotes_header_name_first_prop</code>	735 <code>\prop_new:N \g__postnotes_header_sect_last_prop</code>
<code>\g__postnotes_header_name_last_prop</code>	736 <code>\prop_new:N \g__postnotes_header_name_first_prop</code>
<code>\g__postnotes_header_prev_last_page_tl</code>	737 <code>\prop_new:N \g__postnotes_header_name_last_prop</code>
<code>\g__postnotes_header_prev_last_chap_tl</code>	738 <code>\tl_new:N \g__postnotes_header_prev_last_page_tl</code>
<code>\g__postnotes_header_prev_last_sect_tl</code>	739 <code>\tl_new:N \g__postnotes_header_prev_last_chap_tl</code>
<code>\g__postnotes_header_prev_last_name_tl</code>	740 <code>\tl_new:N \g__postnotes_header_prev_last_sect_tl</code>
<code>\l__postnotes_prev_text_page_tl</code>	741 <code>\tl_new:N \g__postnotes_header_prev_last_name_tl</code>
<code>\l__postnotes_curr_text_page_tl</code>	742 <code>\tl_new:N \l__postnotes_prev_text_page_tl</code>
<code>\l__postnotes_prev_mark_page_tl</code>	743 <code>\tl_new:N \l__postnotes_curr_text_page_tl</code>
<code>\l__postnotes_prev_mark_chap_tl</code>	744 <code>\tl_new:N \l__postnotes_prev_mark_page_tl</code>
<code>\l__postnotes_prev_mark_sect_tl</code>	745 <code>\tl_new:N \l__postnotes_prev_mark_chap_tl</code>
<code>\l__postnotes_prev_mark_name_tl</code>	746 <code>\tl_new:N \l__postnotes_prev_mark_sect_tl</code>
	747 <code>\tl_new:N \l__postnotes_prev_mark_name_tl</code>

(End of definition for `\g__postnotes_header_page_first_prop` and others.)

<code>__postnotes_get_headers_data:N</code>	Process header data for <code>__postnotes_set_headers_vars:n</code> .
--	--

```

\__postnotes_get_headers_data:N <\g__postnotes_queue_seq>
748 \cs_new_protected:Npn \__postnotes_get_headers_data:N #1
749 {
750   \group_begin:
751   \tl_gclear:N \pnhdpagefirst
752   \tl_gclear:N \pnhdpagelast
753   \tl_gclear:N \pnhdchapfirst
754   \tl_gclear:N \pnhdchaplast
755   \tl_gclear:N \pnhdsectfirst
756   \tl_gclear:N \pnhdsectlast

```

```

757 \tl_gclear:N \pnhdnamefirst
758 \tl_gclear:N \pnhdnamelast
759 \prop_gclear:N \g__postnotes_header_page_first_prop
760 \prop_gclear:N \g__postnotes_header_page_last_prop
761 \prop_gclear:N \g__postnotes_header_chap_first_prop
762 \prop_gclear:N \g__postnotes_header_chap_last_prop
763 \prop_gclear:N \g__postnotes_header_sect_first_prop
764 \prop_gclear:N \g__postnotes_header_sect_last_prop
765 \prop_gclear:N \g__postnotes_header_name_first_prop
766 \prop_gclear:N \g__postnotes_header_name_last_prop
767 \tl_gclear:N \g__postnotes_header_prev_last_page_tl
768 \tl_gclear:N \g__postnotes_header_prev_last_chap_tl
769 \tl_gclear:N \g__postnotes_header_prev_last_sect_tl
770 \tl_gclear:N \g__postnotes_header_prev_last_name_tl
771 \tl_clear:N \l__postnotes_prev_text_page_tl
772 \tl_clear:N \l__postnotes_curr_text_page_tl
773 \tl_clear:N \l__postnotes_prev_mark_page_tl
774 \tl_clear:N \l__postnotes_prev_mark_chap_tl
775 \tl_clear:N \l__postnotes_prev_mark_sect_tl
776 \tl_clear:N \l__postnotes_prev_mark_name_tl
777 \seq_map_inline:Nn #1
778 {
779   \exp_args:Nx \tl_if_eq:nnT
780   { \__postnotes_prop_item:nn {##1} { type } }
781   { note }
782   {
783     \__postnotes_get_pageref:Nn
784     \l__postnotes_curr_text_page_tl { text@ ##1 }
785     \tl_if_empty:NF \l__postnotes_curr_text_page_tl
786     {
787       \tl_if_eq:NNTF
788       \l__postnotes_prev_text_page_tl
789       \l__postnotes_curr_text_page_tl
790       {

```

We are on the same page as the previous note, just update the `prev_mark` data.

```

791     \__postnotes_get_pageref:Nn
792     \l__postnotes_prev_mark_page_tl { mark@ ##1 }
793     \__postnotes_prop_get:nnN {##1} { thechapter }
794     \l__postnotes_prev_mark_chap_tl
795     \__postnotes_prop_get:nnN {##1} { thesection }
796     \l__postnotes_prev_mark_sect_tl
797     \__postnotes_prop_get:nnN {##1} { pnsectname }
798     \l__postnotes_prev_mark_name_tl
799   }
800 {

```

We are on the transition between two pages, current ID is the first note of the new page (or on the very first note of `\printpostnotes`, given `\l__postnotes_prev_text_page_tl` is initialized to empty).

Set ‘last’ values for previous page, based on the last valid `prev_mark` stored ones. There is no previous page to the first one of `\printpostnotes`, so we don’t set ‘last’ values for it (conditioning on `\l__postnotes_prev_text_page_tl` being empty, which only occurs on the first note).

```

801 \tl_if_empty:NF \l__postnotes_prev_text_page_tl
802 {
803   \prop_gput:Nxx \g__postnotes_header_page_last_prop
804     { \l__postnotes_prev_text_page_tl }
805     { \l__postnotes_prev_mark_page_tl }
806   \prop_gput:Nxx \g__postnotes_header_chap_last_prop
807     { \l__postnotes_prev_text_page_tl }
808     { \l__postnotes_prev_mark_chap_tl }
809   \prop_gput:Nxx \g__postnotes_header_sect_last_prop
810     { \l__postnotes_prev_text_page_tl }
811     { \l__postnotes_prev_mark_sect_tl }
812   \prop_gput:Nxx \g__postnotes_header_name_last_prop
813     { \l__postnotes_prev_text_page_tl }
814     { \l__postnotes_prev_mark_name_tl }
815 }

```

Set ‘first’ values for current page, based on the current note ID.

```

816 \prop_gput:Nxx \g__postnotes_header_page_first_prop
817   { \l__postnotes_curr_text_page_tl }
818   { \__postnotes_extract_pageref:n { mark@ ##1 } }
819 \prop_gput:Nxx \g__postnotes_header_chap_first_prop
820   { \l__postnotes_curr_text_page_tl }
821   { \__postnotes_prop_item:nn {##1} { thechapter } }
822 \prop_gput:Nxx \g__postnotes_header_sect_first_prop
823   { \l__postnotes_curr_text_page_tl }
824   { \__postnotes_prop_item:nn {##1} { thesection } }
825 \prop_gput:Nxx \g__postnotes_header_name_first_prop
826   { \l__postnotes_curr_text_page_tl }
827   { \__postnotes_prop_item:nn {##1} { pnsectname } }

```

Store `prev_mark` data for the first note on the page.

```

828 \__postnotes_get_pageref:Nn
829   \l__postnotes_prev_mark_page_tl { mark@ ##1 }
830 \__postnotes_prop_get:nnN {##1} { thechapter }
831   \l__postnotes_prev_mark_chap_tl
832 \__postnotes_prop_get:nnN {##1} { thesection }
833   \l__postnotes_prev_mark_sect_tl
834 \__postnotes_prop_get:nnN {##1} { pnsectname }
835   \l__postnotes_prev_mark_name_tl

```

Set `\l__postnotes_prev_text_page_tl` for the next page (`\l__postnotes_curr_text_page_tl` is never empty at this point, since we conditioned to it).

```

836 \tl_set:NV \l__postnotes_prev_text_page_tl
837   \l__postnotes_curr_text_page_tl
838 }
839 }
840 }
841 }

```

We can’t catch the transition from the last page of `\printpostnotes` to the following one through the mapping above, but the `prev_mark` values of the last note in the loop are the ones we want, so we set ‘last’ values for the last page based on them.

```

842 \tl_if_empty:NF \l__postnotes_prev_text_page_tl
843 {
844   \prop_gput:Nxx \g__postnotes_header_page_last_prop

```

```

845         { \l__postnotes_prev_text_page_tl }
846         { \l__postnotes_prev_mark_page_tl }
847     \prop_gput:Nxx \g__postnotes_header_chap_last_prop
848     { \l__postnotes_prev_text_page_tl }
849     { \l__postnotes_prev_mark_chap_tl }
850     \prop_gput:Nxx \g__postnotes_header_sect_last_prop
851     { \l__postnotes_prev_text_page_tl }
852     { \l__postnotes_prev_mark_sect_tl }
853     \prop_gput:Nxx \g__postnotes_header_name_last_prop
854     { \l__postnotes_prev_text_page_tl }
855     { \l__postnotes_prev_mark_name_tl }
856 }
857 \group_end:
858 }

```

(End of definition for __postnotes_get_headers_data:N.)

The sequence of pages processed in __postnotes_get_headers_data:N is not ensured to be continuous, since not every page of \printpostnotes starts a note. There may be notes that fill whole pages, or the last page of the notes may end with a note that started on the penultimate page. We must handle this case at __postnotes_set_headers_vars:n. For every page for which there is information provided by __postnotes_get_headers_data:N we store a header_prev_last (the last value of the previous header) for each of the variables of interest. If the next page is skipped in the sequence (no notes starting on it), we can use these stored values to set both ‘first’ and ‘last’ variables based on them for that page.

__postnotes_set_headers_vars:n Set user facing variables based on data generated by __postnotes_get_headers_data:N.

```

\__postnotes_set_headers_vars:n {(page number)}

859 \cs_new_protected:Npn \__postnotes_set_headers_vars:n #1
860 {
861     \group_begin:
862     \prop_get:NnNTF \g__postnotes_header_page_first_prop
863     {#1} \l_tmpa_tl
864     { \tl_gset:NV \pnhdpagefirst \l_tmpa_tl }
865     { \tl_gset:NV \pnhdpagefirst \g__postnotes_header_prev_last_page_tl }
866     \prop_get:NnNTF \g__postnotes_header_page_last_prop
867     {#1} \l_tmpa_tl
868     {
869         \tl_gset:NV \pnhdpagelast \l_tmpa_tl
870         \tl_gset:NV \g__postnotes_header_prev_last_page_tl \l_tmpa_tl
871     }
872     { \tl_gset:NV \pnhdpagelast \g__postnotes_header_prev_last_page_tl }
873     \prop_get:NnNTF \g__postnotes_header_chap_first_prop
874     {#1} \l_tmpa_tl
875     { \tl_gset:NV \pnhdchapfirst \l_tmpa_tl }
876     { \tl_gset:NV \pnhdchapfirst \g__postnotes_header_prev_last_chap_tl }
877     \prop_get:NnNTF \g__postnotes_header_chap_last_prop
878     {#1} \l_tmpa_tl
879     {
880         \tl_gset:NV \pnhdchaplast \l_tmpa_tl
881         \tl_gset:NV \g__postnotes_header_prev_last_chap_tl \l_tmpa_tl

```

```

882     }
883     { \tl_gset:NV \pnhdchaplast \g__postnotes_header_prev_last_chap_tl }
884     \prop_get:NnNTF \g__postnotes_header_sect_first_prop
885     {#1} \l_tmpa_tl
886     { \tl_gset:NV \pnhdsectfirst \l_tmpa_tl }
887     { \tl_gset:NV \pnhdsectfirst \g__postnotes_header_prev_last_sect_tl }
888     \prop_get:NnNTF \g__postnotes_header_sect_last_prop
889     {#1} \l_tmpa_tl
890     {
891       \tl_gset:NV \pnhdsectlast \l_tmpa_tl
892       \tl_gset:NV \g__postnotes_header_prev_last_sect_tl \l_tmpa_tl
893     }
894     { \tl_gset:NV \pnhdsectlast \g__postnotes_header_prev_last_sect_tl }
895     \prop_get:NnNTF \g__postnotes_header_name_first_prop
896     {#1} \l_tmpa_tl
897     { \tl_gset:NV \pnhdnamefirst \l_tmpa_tl }
898     { \tl_gset:NV \pnhdnamefirst \g__postnotes_header_prev_last_name_tl }
899     \prop_get:NnNTF \g__postnotes_header_name_last_prop
900     {#1} \l_tmpa_tl
901     {
902       \tl_gset:NV \pnhdnamelast \l_tmpa_tl
903       \tl_gset:NV \g__postnotes_header_prev_last_name_tl \l_tmpa_tl
904     }
905     { \tl_gset:NV \pnhdnamelast \g__postnotes_header_prev_last_name_tl }
906     \group_end:
907   }
908   \cs_generate_variant:Nn \__postnotes_set_headers_vars:n { x }

```

(End of definition for `__postnotes_set_headers_vars:n`.)

`__postnotes_set_headers_vars_next:`
`__postnotes_set_headers_vars_first:`

The functions that actually call `__postnotes_set_headers_vars:n` at the appropriate contexts with appropriate page values. Though we set `__postnotes_set_headers_vars_next:` to run at every shipout/before hook of the document, it is made no-op by `\g__postnotes_header_vars_next_bool` which only has a true value inside `\printpostnotes`. `__postnotes_set_headers_vars_first:` must set a label and retrieve its value to be able to have a reliable value of its own page.

```

909 \AddToHook { shipout/before } [ postnotes/header ]
910 { \__postnotes_set_headers_vars_next: }
911 \bool_new:N \g__postnotes_header_vars_next_bool
912 \cs_new_protected:Npn \__postnotes_set_headers_vars_next:
913 {
914   \bool_if:NT \g__postnotes_header_vars_next_bool
915   { \__postnotes_set_headers_vars:x { \int_eval:n { \c@page + 1 } } }
916 }
917 \cs_new_protected:Npn \__postnotes_set_headers_vars_first:
918 {
919   \__postnotes_set_print_page_label:x
920   { \int_use:N \g__postnotes_print_postnotes_int }
921   \__postnotes_set_headers_vars:x
922   {
923     \__postnotes_extract_pageref:e
924     { print@ \int_use:N \g__postnotes_print_postnotes_int }
925   }
926 }

```

(End of definition for `_postnotes_set_headers_vars_next:` and `_postnotes_set_headers_vars_first:`.)

`\pnheaderdefault` A basic header function to be used as default in the `heading` option. It produces a header in the form “Notes to pages N–M”, with a text which can be localized (see Section 10).

```

\pnheaderdefault

927 \NewDocumentCommand \pnheaderdefault {}
928 {
929   \tl_if_eq:NNTF \pnhdpagefirst \pnhdpagelast
930     { \pnhdnotes{} ~ \pnhdtopage{} ~ \pnhdpagefirst }
931     { \pnhdnotes{} ~ \pnhdtopages{} ~ \pnhdpagefirst -- \pnhdpagelast }
932 }

```

(End of definition for `\pnheaderdefault`.)

9 Compatibility

A dedicated temp variable for restoring data.

```

933 \tl_new:N \l__postnotes_restore_tmp_tl

```

`\caption`

For `\caption`’s possible two passes. This catches more than just captions, of course, but is not overkill.

From the user’s perspective, one-line captions will just work. For two-line captions, there are two alternatives: i) decrement the counter by 1 `\addtocounter{postnote}{-1}` before the caption, then call `\postnote` inside the caption; or ii) right before the caption, call `\postnote[nomark]{\label{mynote}...}`, then use `\postnoteref{mynote}` inside the caption.

```

934 \AddToHook { postnotes/note/begin } [ postnotes ]
935 {
936   \cs_if_exist:NT \@captype
937   { \bool_set_true:N \l__postnotes_maybe_multi_bool }
938 }

```

biblatex

Thanks Moritz Wemheuer: https://tex.stackexchange.com/q/597359#comment1594585_597389.

```

939 \AddToHook { package/biblatex/after }
940 {

```

Let `biblatex` know we are in a “notes” context. See <https://tex.stackexchange.com/a/304464>, including comments.

```

941   \AddToHook { postnotes/print/begin } [ postnotes ]
942   { \toggletrue { blx@footnote } }

```

Make biblatex’s `\mkbibendnote` use `\postnote`. This is very likely desired in most cases, but may occasionally not be, so we add it to an individually labeled hook, which can be disabled with `\RemoveFromHook{begindocument/before}[postnotes/mkbibendnote]` in the preamble.

```

943 \AddToHook { begindocument/before } [ postnotes/mkbibendnote ]
944 {
945   \cs_set:Npn \blx@theendnote { \postnote }
946   \cs_set:Npn \blx@theendnotetext
947     { \blx@err@endnote \footnotetext }
948 }
949 }
950 <*gobble>

```

I had made an initial experimental attempt to support biblatex’s `refsegments`, `refcontexts` and `refsections`. However, this attempt was rash. Even if I could get many example files to work for `refsegments` and `refcontexts`, I could not do so for `refsections`. More importantly, with this partial implementation, I could also generate documents which confused biblatex more than it helped. Things I couldn’t understand well, or fix. All in all, I don’t think this partial implementation is tenable, and I could not take it further. Hence, `postnotes` support for this feature set of biblatex will depend, as it should, on proper upstream support for “saving” and “restoring” citation “context” information.

I have made a feature request at biblatex for this (<https://github.com/plk/biblatex/issues/1226>), which was (understandably) classified as “long term, no promises”.

The attempt was the following (currently “gobbled” from the package):

```

951 \AddToHook { package/biblatex/after }
952 {

```

Store biblatex variables for each note.

```

953 \AddToHook { postnotes/note/store } [ postnotes ]
954 {
955   \prop_gput:cnx { \__postnotes_data_name:e { \l_postnotes_note_id_tl } }
956     { biblatex@refsection } { \int_use:N \c@refsection }
957   \prop_gput:cnx { \__postnotes_data_name:e { \l_postnotes_note_id_tl } }
958     { biblatex@refsegment } { \int_use:N \c@refsegment }
959   \prop_gput:cnx { \__postnotes_data_name:e { \l_postnotes_note_id_tl } }
960     { biblatex@refcontextbool }
961     { \iftoggle { blx@refcontext } { true } { false } }
962   \prop_gput:cnV { \__postnotes_data_name:e { \l_postnotes_note_id_tl } }
963     { biblatex@refcontext } \blx@refcontext@context
964 }

```

biblatex setup, once for `\printpostnotes` call.

```

965 \AddToHook { postnotes/print/begin } [ postnotes ]
966 {
967   \__postnotes_biblatex_endrefcontext_local:
968   \__postnotes_biblatex_citereset_local:
969 }

```

Restore biblatex variables for each note.

```

970 \AddToHook { postnotes/print/note/begin } [ postnotes ]
971 {

```

```

972     \__postnotes_prop_get:nnN { \l_postnotes_print_note_id_tl }
973     { biblatex@refsection } \l__postnotes_restore_tmp_tl
974     \int_set:Nn \c@refsection { \l__postnotes_restore_tmp_tl }
975     \__postnotes_prop_get:nnN { \l_postnotes_print_note_id_tl }
976     { biblatex@refsegment } \l__postnotes_restore_tmp_tl
977     \int_set:Nn \c@refsegment { \l__postnotes_restore_tmp_tl }
978     \__postnotes_prop_get:nnN { \l_postnotes_print_note_id_tl }
979     { biblatex@refcontextbool } \l__postnotes_restore_tmp_tl
980     \use:c { toggle \l__postnotes_restore_tmp_tl } { blx@refcontext }
981     \__postnotes_prop_get:nnN { \l_postnotes_print_note_id_tl }
982     { biblatex@refcontext } \l__postnotes_restore_tmp_tl
983     \blx@edef@refcontext { \l__postnotes_restore_tmp_tl }
984 }

```

Auxiliary functions.

`__postnotes_biblatex_endrefcontext_local:` Replicate the job of `\endrefcontext`, but with local effects, restrained to the group of `\printpostnotes`.

```

985     \cs_new_protected:Npn \__postnotes_biblatex_endrefcontext_local:
986     {
987         \togglefalse { blx@refcontext }
988         \tl_clear:N \blx@refcontext@labelprefix
989         \tl_clear:N \blx@refcontext@labelprefix@real
990         \tl_set:Nx \blx@refcontext@sortingtemplatename { \blx@sorting }
991         \tl_set:Nn \blx@refcontext@sortingnamekeytemplatename { global }
992         \tl_set:Nn \blx@refcontext@uniquenametemplatename { global }
993         \tl_set:Nn \blx@refcontext@labelalphanametemplatename { global }
994         \blx@edef@refcontext
995         {
996             \blx@refcontext@sortingtemplatename /
997             \blx@refcontext@sortingnamekeytemplatename /
998             /
999             \blx@refcontext@uniquenametemplatename /
1000             \blx@refcontext@labelalphanametemplatename
1001         }
1002     }

```

(End of definition for `__postnotes_biblatex_endrefcontext_local:.`)

`__postnotes_biblatex_citereset_local:` Replicate the job of `\citereset`, but with local effects, restrained to the group of `\printpostnotes`.

```

1003     \cs_new_protected:Npn \__postnotes_biblatex_citereset_local:
1004     {
1005         \global\cslet{blx@bsee@the\c@refsection}\@empty
1006         \global\cslet{blx@fsee@the\c@refsection}\@empty
1007         \tl_clear:c { blx@bsee@ \int_use:N \c@refsection }
1008         \tl_clear:c { blx@fsee@ \int_use:N \c@refsection }
1009         \blx@ibidreset@force
1010         \undef \blx@lastkey@text
1011         \undef \blx@lastkey@foot
1012         \blx@idemreset@force
1013         \undef \blx@lasthash@text
1014         \undef \blx@lasthash@foot

```



```

\blx@opcitreset@force

1011      \clist_map_inline:Nn \blx@trackhash@text
1012      { \csundef { blx@lastkey@text@ ##1 } }
1013      \tl_clear:N \blx@trackhash@text
1014      \clist_map_inline:Nn \blx@trackhash@foot
1015      { \csundef { blx@lastkey@foot@ ##1 } }
1016      \tl_clear:N \blx@trackhash@foot

\blx@loccitreset@force

1017      \clist_map_inline:Nn \blx@trackkeys@text
1018      { \csundef { blx@lastnote@text@ ##1 } }
1019      \tl_clear:N \blx@trackkeys@text
1020      \clist_map_inline:Nn \blx@trackkeys@foot
1021      { \csundef { blx@lastnote@foot@ ##1 } }
1022      \tl_clear:N \blx@trackkeys@foot

and all of them do:

1023      \cs_set_eq:NN \blx@lastmpfn \z@
1024      }

(End of definition for \__postnotes_biblatex_citereset_local:.)

1025 }

```

biblatex’s `refsections`, contrary to `refsegments` and `refcontexts` which are handled in the L^AT_EX side of things (as far as I can tell), need to go through `biber`, and must have correct corresponding citation data written to the `.bcf` file. And the way `\refsection` is implemented presumes each section is only ever begun once (fair...), thus making it difficult to “reopen” it, or append new citations to it later on, when the notes are printed. The start of a `refsection` must be registered on the `.bcf` file, and this is done by `\refsection` (and its auxiliary functions). However, a number of its characteristics make things particularly difficult for the purpose at hand: i) it unconditionally sets a label for the section which, of course, cannot be done twice; and, critically, ii) the optional argument of the environment (which receives the $\langle resources \rangle$) is used to set a local assignment to `\blx@bibfiles`, based on which the relevant information is written to the `.bcf` file, and when the group closes the information is gone. My best attempt is below but it is not good. It feels a wrong approach to “go around” the intended use of `\refsection` so much, and it can’t handle at all its optional argument, for the reasons above. It’s also incomplete, since it does not handle restoring `\l__postnotes_biblatex_orig_refsection_tl`.

```

1026 \AddToHook { package/biblatex/after }
1027 {
1028   \tl_new:N \l__postnotes_biblatex_orig_refsection_tl
1029   \tl_new:N \g__postnotes_biblatex_prev_refsection_tl
1030   \AddToHook { postnotes/print/begin } [ postnotes ]
1031   {
1032     \tl_set:Nx \l__postnotes_biblatex_orig_refsection_tl
1033     { \int_use:N \c@refsection }
1034     \tl_gset:Nx \g__postnotes_biblatex_prev_refsection_tl
1035     \l__postnotes_biblatex_orig_refsection_tl
1036   }
1037   \AddToHook { postnotes/print/note/begin } [ postnotes ]
1038   {
1039     \__postnotes_prop_get:nnN { \l__postnotes_print_note_id_tl }

```

```

1040         { biblatex@refsection } \l__postnotes_restore_tmp_tl
1041     \tl_if_eq:NNF
1042         \l__postnotes_restore_tmp_tl
1043         \g__postnotes_biblatex_prev_refsection_tl
1044     {
1045         \int_set:Nn \c@blx@maxsection
1046             { \l__postnotes_restore_tmp_tl - 1 }
1047         \tl_gset_eq:NN \g__postnotes_biblatex_prev_refsection_tl
1048             \l__postnotes_restore_tmp_tl
1049         \group_begin:
1050         \cs_set_eq:NN \label \use_none:n
1051         \cs_set_eq:NN \blx@info \use_none:n
1052         \blx@endrefsection
1053         \refsection
1054         \group_end:
1055     }
1056 }
1057 }
1058 </gobble>

```

zref-user

`\l__postnotes_note_zlabel_tl` Even though the `zlabel` option is provided only when `zref-user` is loaded, `\l__postnotes_note_zlabel_tl` must be unconditionally defined, since it is presumed to exist by `__postnotes_set_user_labels:`.

```

1059 \tl_new:N \l__postnotes_note_zlabel_tl

```

(End of definition for `\l__postnotes_note_zlabel_tl`.)

```

1060 \AddToHook { package/zref-user/after }
1061 {

```

Provide `zlabel` option.

```

1062     \keys_define:nn { postnotes/note }
1063     {
1064         zlabel .tl_set:N = \l__postnotes_note_zlabel_tl ,
1065         zlabel .value_required:n = true ,
1066     }

```

`\postnotezref` Provide `\postnotezref`.

```

\postnotezref(*){<label>}

```

```

1067 \NewDocumentCommand \postnotezref { s m }
1068 { \__postnotes_note_zref:nn {#1} {#2} }

```

(End of definition for `\postnotezref`.)

`__postnotes_note_zref:nn` The internal version of `\postnotezref`.

```

\__postnotes_note_zref:nn {<star bool>} {<label>}

```

```

1069 \cs_new_protected:Npn \__postnotes_note_zref:nn #1#2
1070 {
1071   \group_begin:
1072   \__postnotes_typeset_mark_wrapper:n
1073   {
1074     \bool_lazy_all:nTF
1075     {
1076       { ! #1 }
1077       { \l__postnotes_hyperlink_bool }
1078       { \l__postnotes_zrefhyperref_bool }
1079     }
1080     {
1081       \hyperlink
1082       { \zref@extractdefault {#2} { anchor } { } }
1083       { \__postnotes_make_mark:nnn { \zref{#2} } { } { } }
1084     }
1085     { \__postnotes_make_mark:nnn { \zref{#2} } { } { } }
1086   }
1087   \group_end:
1088 }

```

(End of definition for __postnotes_note_zref:nn.)

```

1089 }
1090 \bool_new:N \l__postnotes_zrefhyperref_bool
1091 \AddToHook { package/zref-hyperref/after }
1092 { \bool_set_true:N \l__postnotes_zrefhyperref_bool }

```

zref-clever

```

1093 \AddToHook { package/zref-clever/after }
1094 {
1095   \zcsetup
1096   {
1097     countertype = { postnote = endnote } ,
1098     countertype = { postnotetext = endnote } ,
1099   }
1100   \AddToHook { postnotes/print/begin } [ postnotes ]
1101   { \zcsetup { counterresetby = { postnotetext = postnotesection } } }
1102 }

```

zref-check

```

1103 \AddToHook { package/zref-check/after }
1104 {
1105   \IfPackageAtLeastTF { zref-check } { 2022-07-05 }
1106   {
1107     \AddToHook { postnotes/note/store } [ postnotes ]
1108     {
1109       \prop_gput:cnx { \__postnotes_data_name:e { \l__postnotes_note_id_tl } }
1110       { zref-check@abschap } { \int_use:N \c@zc@abschap }
1111       \prop_gput:cnx { \__postnotes_data_name:e { \l__postnotes_note_id_tl } }
1112       { zref-check@abssec } { \int_use:N \c@zc@abssec }
1113     }
1114     \AddToHook { postnotes/print/note/begin } [ postnotes ]

```

```

1115         {
1116             \__postnotes_prop_get:nnN { \l_postnotes_print_note_id_tl }
1117             { zref-check@abschap } \l__postnotes_restore_tmp_tl
1118             \int_set:Nn \c@zc@abschap { \l__postnotes_restore_tmp_tl }
1119             \__postnotes_prop_get:nnN { \l_postnotes_print_note_id_tl }
1120             { zref-check@abssec } \l__postnotes_restore_tmp_tl
1121             \int_set:Nn \c@zc@abssec { \l__postnotes_restore_tmp_tl }
1122         }
1123     }
1124     { }
1125 }

```

amsmath

```

1126 \AddToHook { package/amsmath/after }
1127 {

```

Testing for `\ifmeasuring@` is sufficient to get things right for the measuring passes in math environments.

```

1128     \AddToHook { postnotes/note/inhibit } [ postnotes ]
1129     {
1130         \legacy_if:nT { measuring@ }
1131         {
1132             \bool_set_true:N \l__postnotes_inhibit_note_bool
1133             \bool_set_true:N \l__postnotes_print_plain_mark_bool
1134             \bool_set_true:N \l__postnotes_print_plain_mark_stepcounter_bool
1135         }
1136     }

```

However, the `\text` macro, defined by `amstext` (required by `amsmath`), poses problems if its own. Despite my best efforts, I could not salvage things from the use of `\mathchoice` and the redefinitions of `\setcounter` and `\addtocounter` performed by `amstext`. Setting `\l__postnotes_maybe_multi_bool` when `firstchoice@` is false grants us a working situation for display style. But the use of `\postnote` inside `\text` (and, if `amsmath` is loaded, `\textnormal`, `\textup`, etc.) in inline math environments is not supported. If a note really needs to be there, one can use the `nomark` option and `\postnoteref`. Things should work in text mode and in display style. For some related discussion with regard to footnotes, see <https://tex.stackexchange.com/a/82820> and, in particular, Barbara Beeton’s comment: “This is certainly bravura code. I do hope it doesn’t result in a request to add `\footnote` capabilities to `amsmath`’s multi-line display facilities. (The answer will almost certainly be no. We agree with Kopka & Daly.)”

```

1137     \AddToHook { postnotes/note/begin } [ postnotes ]
1138     {
1139         \legacy_if:nF { firstchoice@ }
1140         { \bool_set_true:N \l__postnotes_maybe_multi_bool }
1141     }
1142 }

```

csquotes

```

1143 \AddToHook { package/csquotes/after }
1144 {
1145     \bool_new:N \l__postnotes_csquotes_measuring_bool
1146     \BlockquoteDisable
1147     { \bool_set_true:N \l__postnotes_csquotes_measuring_bool }
1148     \AddToHook { postnotes/note/inhibit } [ postnotes ]

```

```

1149     {
1150       \bool_if:NT \l__postnotes_csquotes_measuring_bool
1151       {
1152         \bool_set_true:N \l__postnotes_inhibit_note_bool
1153         \bool_set_true:N \l__postnotes_print_plain_mark_bool
1154         \bool_set_true:N \l__postnotes_print_plain_mark_stepcounter_bool
1155       }
1156     }
1157   }

```

tabularx

For the identification of the trial passes in `tabularx`, see <https://tex.stackexchange.com/a/640035> (including discussion in the comments, thanks David Carlisle), and also <https://tex.stackexchange.com/a/227155> and <https://tex.stackexchange.com/a/352134>.

```

1158 \AddToHook { package/tabularx/after }
1159 {
1160   \bool_new:N \l__postnotes_tabularx_inside_env_bool
1161   \AddToHook { env/tabularx/begin } [ postnotes ]
1162   {
1163     \bool_set_true:N \l__postnotes_tabularx_inside_env_bool
1164     \cs_set_eq:NN \__postnotes_tabularx_saved_write:Nn \write
1165   }
1166   \AddToHook { postnotes/note/inhibit } [ postnotes ]
1167   {
1168     \bool_lazy_and:nnT
1169     { \l__postnotes_tabularx_inside_env_bool }
1170     { ! \cs_if_eq_p:NN \write \__postnotes_tabularx_saved_write:Nn }
1171     {
1172       \bool_set_true:N \l__postnotes_inhibit_note_bool
1173       \bool_set_true:N \l__postnotes_print_plain_mark_bool
1174       \bool_set_true:N \l__postnotes_print_plain_mark_stepcounter_bool
1175     }
1176   }
1177 }

```

tabularray

```

1178 \AddToHook { package/tabularray/after }
1179 {

```

Since version 2023A, from 2023-03-01, `tabularray` offers the `\lTblrMeasuringBool` which is true when measuring and false otherwise. See <https://tex.stackexchange.com/q/675818> and <https://github.com/lvjrr/tabularray/issues/179> (thanks Ulrike Fischer).

```

1180   \bool_if_exist:NTF \lTblrMeasuringBool
1181   {

```

I’d be inclined to restrict the inhibition effect to known `tabularray` environments to “keep things under control”. However this is a dedicated and public boolean, and users can create arbitrary new `tabularray` environments with `\NewTblrEnviron`, which we either wouldn’t catch or have to provide an user interface for. So, for the time being, let’s trust this boolean won’t be misused by third-parties or users. Note that

setting `\l__postnotes_print_plain_mark_stepcounter_bool` to true presumes `tabularray`'s `counter` module is enabled. But, since this is the only way to get the measuring right in this context if there is more than one `\postnote` inside a given table, `pkgpostnotes` expects and requires the `counter` module.

```

1182     \AddToHook { postnotes/note/inhibit } [ postnotes ]
1183     {
1184         \bool_if:NT \lTblrMeasuringBool
1185         {
1186             \bool_set_true:N \l__postnotes_inhibit_note_bool
1187             \bool_set_true:N \l__postnotes_print_plain_mark_bool
1188             \bool_set_true:N \l__postnotes_print_plain_mark_stepcounter_bool
1189         }
1190     }
1191 }
1192 {

```

If the new boolean is not yet available, we use `__postnotes_verify_multipass:N` to distinguish a trial/measure pass from the final one.

```

1193     \clist_map_inline:nn
1194     {
1195         tblr , longtblr , talltblr , booktabs ,
1196         longtabs , talltabs , +array
1197     }
1198     {
1199         \AddToHook { env/#1/begin } [ postnotes ]
1200         { \bool_set_true:N \l__postnotes_maybe_multi_bool }
1201     }
1202 }
1203 }

```

10 Languages

<code>\pntitle</code> <code>\pnhdnotes</code> <code>\pnhdtopage</code> <code>\pnhdtopages</code>	<p>Set of language specific user variables. They are used in the default value of the <code>heading</code> option and in <code>\pnheaderdefault</code> which, ultimately, is also used in the same place.</p> <pre> 1204 \tl_new:N \pntitle 1205 \tl_new:N \pnhdnotes 1206 \tl_new:N \pnhdtopage 1207 \tl_new:N \pnhdtopages 1208 \tl_set:Nn \pntitle { Notes } 1209 \tl_set:Nn \pnhdnotes { Notes } 1210 \tl_set:Nn \pnhdtopage { to~page } 1211 \tl_set:Nn \pnhdtopages { to~pages } </pre>
---	---

(End of definition for `\pntitle` and others.)

<code>__postnotes_define_language:nn</code>	<p>Defines language specific values for <i>⟨postnote language⟩</i> by storing a set of assignments for the language specific variables in <i>⟨setup⟩</i>. <i>⟨postnote language⟩</i> is an internal name, typically the “main” name of the language, based on which we can set specific <code>babel</code> or <code>polyglossia</code> languages or variants.</p>
--	---

```

        \__postnotes_define_language:nn {⟨postnote language⟩} {⟨setup⟩}

1212 \cs_new_protected:Npn \__postnotes_define_language:nn #1#2
1213 {

```

```

1214 \tl_new:c { g__postnotes_language_ #1 _tl }
1215 \tl_gset:cn { g__postnotes_language_ #1 _tl } {#2}
1216 }

```

(End of definition for `__postnotes_define_language:nn`.)

For `babel` we use the new hook system, it's clean, and avoids the `\addto` pitfalls. The appropriate hook to use is `babel/<language>/beforeextras` so that users can override it with a traditional `\addto\extras<language>`.

Note that, for `babel`, the captions are currently handled in two different ways – the “old way” and the “new way” – and which of them is used depends on the language. Most still use the “old way”, but the problem is that it is not universal. And the “new way” uses a different naming scheme – `\<language><caption>`, which is meant to be set with `\setlocalecaption`, and not suitable for our needs. The `\extras<language>` macros are meant for “arbitrary” code to be run when the language is selected, which is what we want. The captions used to work in the same way, but no longer for languages which use the “new way”.

Note also that there seems to exist some qualms about `babel`'s `\addto`. A number of packages define their own versions of it. Do so at least `varioref` (probably the original), `backref`, and `cleveref`. The latter comments that `\addto` is “flawed”. `babel` itself comments the definition recognizing that there is an “inconsistency”: depending on the case, the operation will be either local or global. This is documented in the manual, which explains this inconsistent behavior is preserved for backward compatibility, and recommends `etoolbox`'s facilities if available. `polyglossia` also recommends `etoolbox`'s `\gappto`. All in all, if there's need to use the traditional way instead of the new hooks, just rely on `expl3` and use `\tl_gput_right:Nn`.

`__postnotes_set_babel_language:nn` Sets `<babel language>` to execute the setup defined by `__postnotes_define_language:nn` for `<postnote language>` at the `babel/<language>/beforeextras` hook.

```

\__postnotes_set_babel_language:nn {<babel language>} {<postnote language>}

1217 \cs_new_protected:Npn \__postnotes_set_babel_language:nn #1#2
1218 {
1219   \ActivateGenericHook { babel/#1/beforeextras }
1220   \exp_args:Nnv \AddToHook { babel/#1/beforeextras }
1221     { g__postnotes_language_ #2 _tl }
1222 }

```

(End of definition for `__postnotes_set_babel_language:nn`.)

`polyglossia` uses a similar set of macros for setting up languages as `babel` does. However, the `\blockextras@<language>` macros are unfortunately internal (despite what the manual says, that's what the code does), thus requiring `\makeatletter/\makeatother` for user configuration, which would be an inconvenience. On the other hand, `polyglossia`'s `\captions<language>` works as in `babel`'s “old way”, meaning it is just a “hook” to which we can append some code. So we use `\captions<language>` for `polyglossia`. Things may complicate here if there's need to set up different values for different language variants, since the hooks available are all necessarily internal, but I doubt we'll ever need variants for these simple strings.

`__postnotes_set_polyglossia_language:nn` Sets `<polyglossia language>` to execute the setup defined by `__postnotes_define_language:nn` for `<postnote language>` at the `polyglossia \captions<language>` hook.

```

1223 \__postnotes_set_polyglossia_language:nn {(<polyglossia language>)}
1224   {(<postnote language>)}
1225 \cs_new_protected:Npn \__postnotes_set_polyglossia_language:nn #1#2
1226 {
1227   \AddToHook { package/polyglossia/after }
1228   {
1229     \exp_args:Nnv \csgappto { captions #1 }
1230     { g__postnotes_language_ #2 _tl }
1231   }
1232 }

```

(End of definition for __postnotes_set_polyglossia_language:nn.)

English

```

1231 \__postnotes_define_language:nn { english }
1232 {
1233   \tl_set:Nn \pntitle { Notes }
1234   \tl_set:Nn \pnhdnotes { Notes }
1235   \tl_set:Nn \pnhdtopage { to~page }
1236   \tl_set:Nn \pnhdtopages { to~pages }
1237 }
1238 \__postnotes_set_babel_language:nn { english } { english }
1239 \__postnotes_set_babel_language:nn { british } { english }
1240 \__postnotes_set_babel_language:nn { american } { english }
1241 \__postnotes_set_babel_language:nn { canadian } { english }
1242 \__postnotes_set_babel_language:nn { australian } { english }
1243 \__postnotes_set_babel_language:nn { newzealand } { english }
1244 \__postnotes_set_babel_language:nn { UKenglish } { english }
1245 \__postnotes_set_babel_language:nn { USenglish } { english }
1246 \__postnotes_set_polyglossia_language:nn { english } { english }

```

Portuguese

```

1247 \__postnotes_define_language:nn { portuguese }
1248 {
1249   \tl_set:Nn \pntitle { Notas }
1250   \tl_set:Nn \pnhdnotes { Notas }
1251   \tl_set:Nn \pnhdtopage { da~página }
1252   \tl_set:Nn \pnhdtopages { das~páginas }
1253 }
1254 \__postnotes_set_babel_language:nn { portuguese } { portuguese }
1255 \__postnotes_set_babel_language:nn { brazilian } { portuguese }
1256 \__postnotes_set_babel_language:nn { portuges } { portuguese }
1257 \__postnotes_set_babel_language:nn { brazil } { portuguese }
1258 \__postnotes_set_polyglossia_language:nn { portuguese } { portuguese }

```

French

French localization validated by ‘Pika78’ at issue [#1](#).

babel-french also has .ldfs for `francais`, `frenchb`, and `canadien`, but they are deprecated as options and, if used, they fall back to either `french` or `acadian`.

```

1259 \__postnotes_define_language:nn { french }
1260 {

```



```

1261 \tl_set:Nn \pntitle { Notes }
1262 \tl_set:Nn \pnhdnotes { Notes }
1263 \tl_set:Nn \pnhdtopage { de~la~page }
1264 \tl_set:Nn \pnhdtopages { des~pages }
1265 }
1266 \__postnotes_set_babel_language:nn { french } { french }
1267 \__postnotes_set_babel_language:nn { acadian } { french }
1268 \__postnotes_set_polyglossia_language:nn { french } { french }

```

German

German localization provided by Herbert Voß at issue [#2](#).

`babel-german` also has `.ldfs` for `germanb` and `ngermanb`, but they are deprecated as options and, if used, they fall back respectively to `german` and `ngerman`.

```

1269 \__postnotes_define_language:nn { german }
1270 {
1271   \tl_set:Nn \pntitle { Endnoten }
1272   \tl_set:Nn \pnhdnotes { Endnoten }
1273   \tl_set:Nn \pnhdtopage { zu~Seite }
1274   \tl_set:Nn \pnhdtopages { zu~Seiten }
1275 }
1276 \__postnotes_set_babel_language:nn { german } { german }
1277 \__postnotes_set_babel_language:nn { ngerman } { german }
1278 \__postnotes_set_babel_language:nn { austrian } { german }
1279 \__postnotes_set_babel_language:nn { naustrian } { german }
1280 \__postnotes_set_babel_language:nn { swissgerman } { german }
1281 \__postnotes_set_babel_language:nn { nswissgerman } { german }
1282 \__postnotes_set_polyglossia_language:nn { german } { german }
1283 </package>

```

Index

The italic numbers denote the pages where the corresponding entry is described, numbers underlined point to the definition, all others indicate the places where it is used.

A		bool commands:	
<code>\ActivateGenericHook</code>	1219	<code>\bool_gset_false:N</code>	647
<code>\addto</code>	39	<code>\bool_gset_true:N</code>	531
<code>\addtocounter</code>	36	<code>\bool_if:NTF</code>	31, 246, 335, 381, 385, 401, 409, 480, 529, 534, 587, 637, 670, 914, 1150, 1184
<code>\AddToHook</code>	241, 909, 934, 939, 941, 943, 951, 953, 965, 970, 1026, 1030, 1037, 1060, 1091, 1093, 1100, 1103, 1107, 1114, 1126, 1128, 1137, 1143, 1148, 1158, 1161, 1166, 1178, 1182, 1199, 1220, 1225	<code>\bool_if_exist:NTF</code>	1180
<code>\AddToHookNext</code>	646	<code>\bool_lazy_all:nTF</code>	1074
		<code>\bool_lazy_and:nnTF</code>	447, 657, 706, 1168
		<code>\bool_new:N</code>	137, 214, 215, 216, 268, 345, 348, 349, 371, 372, 373, 486, 911, 1090, 1145, 1160
		<code>\bool_set_false:N</code>	144, 223, 232, 233, 248, 377, 378, 379
B		<code>\bool_set_true:N</code>	149, 222, 227, 228, 357,
<code>\begin</code>	588		
<code>\BlockquoteDisable</code>	1146		

937, 1092, 1132, 1133, 1134, 1140, 1147, 1152, 1153, 1154, 1163, 1172, 1173, 1174, 1186, 1187, 1188, 1200	\exp_not:n 105
\bool_to_str:N 47	F
\bool_until_do:nn 539	\fmtversion 4
box commands:	\footnote 36
\box_use:N 293	\footnotemark 10, 11
\box_wd:N 292	\footnotesize 283
\l_tmpa_box 291, 292, 293	\footnotetext 10, 11, 947
C	fp commands:
\caption 10, 11, 30	\fp_compare:nNnTF 712
\chapter 118	\fp_new:N 346
\citereset 32	\fp_set:Nn 356
clist commands:	\fp_use:N 32
\clist_map_inline:Nn	G
. 1011, 1014, 1017, 1020	\gappto 39
\clist_map_inline:nn 1193	group commands:
\counterwithin 12	\group_begin:
cs commands: 317, 391, 444, 474, 519, 562,
\cs_generate_variant:Nn 19,	589, 592, 679, 697, 750, 861, 1049, 1071
64, 82, 88, 94, 101, 108, 418, 667, 908	\group_end:
\cs_if_eq_p:NN 1170 342, 394, 456, 483, 579, 622,
\cs_if_exist:NTF	639, 651, 693, 720, 857, 906, 1054, 1087
. 35, 55, 97, 104, 114, 686, 936	H
\cs_new:Npn 17, 70, 102, 190	\hbox 197
\cs_new_protected:Npn 21,	hbox commands:
51, 65, 72, 77, 83, 89, 95, 116, 123,	\hbox_set:Nn 291
315, 405, 420, 433, 442, 472, 517,	\hspace 191
655, 668, 677, 695, 748, 859, 912,	\hyperlink 1081
917, 985, 1003, 1069, 1212, 1217, 1223	\hyperref 451
\cs_new_protected:Npx 75	I
\cs_set:Npn 330, 605, 945, 946	\IfFormatAtLeastTF 4, 5
\cs_set:Npx 331, 608	\IfPackageAtLeastTF 1105
\cs_set_eq:NN	\IfPackageLoadedTF 243
163, 180, 536, 1023, 1050, 1051, 1164	\iftoggle 961
\csgappto 1227	int commands:
\csundef 1012, 1015, 1018, 1021	\int_eval:n 915
E	\int_gincr:N 321, 475, 476, 520
\end 638	\int_incr:N 392
\endgroup 21	\int_new:N 308, 471, 502
\endinput 13	\int_set:Nn
\endlist 172, 189 606, 974, 977, 1045, 1118, 1121
\endnotemark 10	\int_use:N
\endnotetext 10 28, 33, 45, 86, 92, 310, 920, 924,
\endrefcontext 32	956, 958, 1005, 1006, 1033, 1110, 1112
\noteheading 19	iow commands:
exp commands:	\iow_char:N 468, 469, 654
\exp_args:NNNx 393	\iow_shipout_x:Nn 4, 79, 85, 91
\exp_args:Nnv 1220, 1227	\item 21, 22, 672
\exp_args:NV 436, 438	\itemindent 162, 179
\exp_args:Nx 588, 638, 779	\itemsep 167, 184
\exp_not:N 76	

K	
keys commands:	
\keys_define:nn	109, 130, 138, 192, 205, 217, 250, 269, 275, 350, 487, 1062
\keys_set:nn	306, 318, 479
L	
\label	11, 436, 1050
\labelsep	191
\labelwidth	161, 178
\leftmargin	160, 177, 178, 179
\leftskip	285
legacy commands:	
\legacy_if:nTF	1130, 1139
\list	158, 175
\listparindent	165, 182
\lTblrMeasuringBool	37, 1180, 1184
M	
\makeatletter	39
\makeatother	39
\makelabel	163, 180
\MakeLinkTarget	2, 332, 612
\mathchoice	10, 36
\mbox	10
\MessageBreak	11
\mkbibendnote	31
mode commands:	
\mode_if_horizontal:TF	423, 429
\mode_leave_vertical:	422, 673
msg commands:	
\msg_line_context:	265, 468, 654
\msg_new:nnn	264, 266, 466, 653
\msg_warning:nn	247, 463, 522
\msg_warning:nnn	254, 259
N	
\NeedsTeXFormat	3
\newcounter	307, 514, 515
\NewDocumentCommand	305, 312, 440, 458, 460, 495, 927, 1067
\NewDocumentEnvironment	156, 173
\NewHook	2, 20, 314, 374, 512, 513
\newlabel	4
\NewTblrEnviron	37
\nobreak	426
\noindent	300
\normalfont	191, 197, 291, 301
P	
\PackageError	8
\par	21, 145, 288, 300, 640
\parindent	162, 165, 182, 286
\parsep	166, 183
\parskip	166, 183
\partopsep	169, 186
\pnhdchapfirst	722, 753, 875, 876
\pnhdchaplast	722, 754, 880, 883
\pnhdnamefirst	722, 757, 897, 898
\pnhdnamelast	722, 758, 902, 905
\pnhdnotes	930, 931, 1204, 1234, 1250, 1262, 1272
\pnhdpagefirst	722, 751, 864, 865, 929, 930, 931
\pnhdpagelast	722, 752, 869, 872, 929, 931
\pnhdsectfirst	722, 755, 886, 887
\pnhdsectlast	722, 756, 891, 894
\pnhdtopage	930, 1204, 1235, 1251, 1263, 1273
\pnhdtopages	931, 1204, 1236, 1252, 1264, 1274
\pnheaderdefault	30, 38, 119, 126, 927
\pnheading	5, 111, 114, 524
\pnthechapter	497, 565
\pnthechapternextnote	497, 571
\pnthepage	497, 594
\pnthesection	497, 568
\pnthesectionnextnote	497, 574
\pntitle	118, 125, 1204, 1233, 1249, 1261, 1271
\postnote	2, 10–13, 15, 22, 24, 30, 31, 36, 38, 312, 945
\postnotemark	11, 12
\postnoteref	11, 16, 36, 440
postnotes commands:	
\l_postnotes_note_id_tl	12, 308, 328, 332, 333, 338, 340, 477, 481, 482, 955, 957, 959, 962, 1109, 1111
\l_postnotes_print_note_id_tl	502, 542, 543, 564, 567, 576, 595, 597, 600, 603, 613, 615, 617, 972, 975, 978, 981, 1039, 1116, 1119
postnotes internal commands:	
\l__postnotes_backlink_bool	216, 237, 659
__postnotes_biblatex_citereset_local:	968, 1003, 1003
__postnotes_biblatex_endrefcontext_local:	967, 985, 985
\l__postnotes_biblatex_orig_refsection_tl	33, 1028, 1032, 1035
\g__postnotes_biblatex_prev_refsection_tl	1029, 1034, 1043, 1047
\l__postnotes_clear_queue_seq	21, 502, 527, 648
\l__postnotes_csquotes_measuring_bool	1145, 1147, 1150
\l__postnotes_curr_text_page_tl	27, 730, 772, 784, 785, 789, 817, 820, 823, 826, 837

__postnotes_data_name:n . . .	2, 12, 17, 17, 19, 23, 24, 25, 27, 29, 37, 40, 42, 44, 46, 48, 53, 54, 57, 60, 62, 67, 71, 73, 955, 957, 959, 962, 1109, 1111
__postnotes_define_language:nn .	38, 39, 1212, 1212, 1231, 1247, 1259, 1269
__postnotes_extract_pageref:n . .	5, 95, 102, 108, 818, 923
__postnotes_get_headers_data:N .	24, 25, 28, 532, 748, 748
__postnotes_get_pageref:Nn	5, 95, 95, 101, 594, 783, 791, 828
\g__postnotes_header_chap_first_-prop	730, 761, 819, 873
\g__postnotes_header_chap_last_-prop	730, 762, 806, 847, 877
\g__postnotes_header_name_first_-prop	730, 765, 825, 895
\g__postnotes_header_name_last_-prop	730, 766, 812, 853, 899
\g__postnotes_header_page_first_-prop	730, 759, 816, 862
\g__postnotes_header_page_last_-prop	730, 760, 803, 844, 866
\g__postnotes_header_prev_last_-chap_tl	730, 768, 876, 881, 883
\g__postnotes_header_prev_last_-name_tl	730, 770, 898, 903, 905
\g__postnotes_header_prev_last_-page_tl	730, 767, 865, 870, 872
\g__postnotes_header_prev_last_-sect_tl	730, 769, 887, 892, 894
\g__postnotes_header_sect_first_-prop	730, 763, 822, 884
\g__postnotes_header_sect_last_-prop	730, 764, 809, 850, 888
\g__postnotes_header_vars_next_-bool	29, 531, 647, 911, 914
\l__postnotes_hyperlink_bool	222, 227, 232, 248, 409, 449, 658, 1077
\l__postnotes_hyperref_warn_bool	215, 223, 228, 233, 246
__postnotes_inhibit_note:	375
__postnotes_inhibit_note:TF	22, 319, 371
\l__postnotes_inhibit_note_bool	14, 371, 377, 401, 1132, 1152, 1172, 1186
__postnotes_list_makelabel:n	163, 180, 190
__postnotes_make_mark:nnn	194, 399, 411, 415, 452, 454, 1083, 1085
__postnotes_make_text_mark:nnn	198, 661, 665
\l__postnotes_manual_sortnum_-bool	31, 348, 357
\l__postnotes_mark_tl	26, 322, 325, 331, 338, 344, 352, 383, 388, 395, 399
\l__postnotes_maybe_multi_bool	23, 36, 47, 349, 937, 1140, 1200
\l__postnotes_nomark_bool	335, 345, 366
__postnotes_note:nn	12, 15, 313, 314, 315
\g__postnotes_note_id_int	12, 308, 321, 476
\l__postnotes_note_label_tl	347, 368, 435, 436
__postnotes_note_ref:nn	16, 441, 442, 442
\l__postnotes_note_zlabel_tl	34, 437, 438, 1059, 1064
__postnotes_note_zref:nn	34, 1068, 1069, 1069
\l__postnotes_post_printnote_tl	145, 204, 211, 621
\l__postnotes_post_textmark_tl	203, 209, 672, 675
\l__postnotes_pre_textmark_tl	202, 207, 672, 675
\l__postnotes_prev_mark_chap_tl	730, 774, 794, 808, 831, 849
\l__postnotes_prev_mark_name_tl	730, 776, 798, 814, 835, 855
\l__postnotes_prev_mark_page_tl	730, 773, 792, 805, 829, 846
\l__postnotes_prev_mark_sect_tl	730, 775, 796, 811, 833, 852
\l__postnotes_prev_text_page_tl	26, 27, 730, 771, 788, 801, 804, 807, 810, 813, 836, 842, 845, 848, 851, 854
\l__postnotes_print_as_list_bool	137, 144, 149, 534, 587, 637, 670
\l__postnotes_print_content_tl	502, 577, 578, 604, 620
\l__postnotes_print_counter_tl	502, 601, 607
\l__postnotes_print_env_tl	136, 146, 150, 588, 638
\l__postnotes_print_format_tl	129, 132, 590
\l__postnotes_print_mark_tl	502, 598, 609, 618
\l__postnotes_print_note_id_-next_tl	502, 549, 554, 556, 570, 573, 625, 630, 632

_postnotes_print_notes:	_postnotes_set_headers_vars_-
. 18, 19, 22-24, 496, 517, 517	next: 24, 29, 909, 910, 912
\l_postnotes_print_plain_mark_-	_postnotes_set_mark_page_-
bool 14,	label:n 4, 24, 77, 77, 82, 333
372, 378, 381, 1133, 1153, 1173, 1187	_postnotes_set_polyglossia_-
\l_postnotes_print_plain_mark_-	language:nn 40,
stepcounter_bool 14, 38,	1223, 1223, 1246, 1258, 1268, 1282
373, 379, 385, 1134, 1154, 1174, 1188	_postnotes_set_print_page_-
\g_postnotes_print_postnotes_-	label:n 4, 24, 77, 89, 94, 919
int 502, 520, 920, 924	_postnotes_set_text_page_-
\l_postnotes_print_type_curr_tl	label:n 4, 24, 77, 83, 88, 614
. 502, 544, 545, 581, 643	_postnotes_set_user_labels: . . .
\l_postnotes_print_type_next_tl 34, 334, 433, 433
. . . . 502, 550, 557, 559, 626, 633, 635	\l_postnotes_sort_bool 268, 271, 529
\l_postnotes_print_type_prev_tl	\l_postnotes_sort_num_fp 32, 346, 356
. 502, 526, 580, 585, 642	_postnotes_sort_queue:N
_postnotes_prop_gclear:n 23, 530, 695, 695
. 4, 65, 72, 649	_postnotes_store:nn . 2, 20, 21, 340
_postnotes_prop_get:nnN	_postnotes_store_section:nn . . .
. 4, 65, 65, 543, 555, 563, 3, 51, 51, 64, 481, 482
566, 569, 572, 575, 596, 599, 602,	\l_postnotes_tabularx_inside_-
631, 683, 700, 701, 704, 705, 710,	env_bool 1160, 1163, 1169
711, 793, 795, 797, 830, 832, 834,	_postnotes_tabularx_saved_-
972, 975, 978, 981, 1039, 1116, 1119	write:Nn 1164, 1170
_postnotes_prop_item:nn	_postnotes_text_mark_wrapper:n
. 4, 65, 70, 780, 821, 824, 827 22, 610, 655, 668
\g_postnotes_queue_seq 12,	_postnotes_typeset_mark:nn . . .
23, 25, 308, 327, 477, 521, 527, 528, 15, 337, 405, 405, 418
530, 532, 539, 541, 547, 553, 623, 629	_postnotes_typeset_mark_-
\c_postnotes_ref_prefix_tl	wrapper:n
. 4, 74, 76, 97, 98, 104, 105, 687 15, 398, 405, 407, 420, 445, 1072
\l_postnotes_restore_tmp_tl	_postnotes_typeset_text_-
. 933, 973, 974, 976,	mark:nn 22, 616, 655, 655, 667
977, 979, 980, 982, 983, 1040, 1042,	_postnotes_verify_multipass:N .
1046, 1048, 1117, 1118, 1120, 1121 22, 23, 38, 528, 677, 677
\l_postnotes_saved_spacefactor_-	\l_postnotes_zrefhyperref_bool .
tl 419, 425, 430 1078, 1090, 1092
\g_postnotes_sectid_int 45, 471, 475	\postnotessection 3, 16, 17, 458
_postnotes_section:nn	\postnotessectionx 16, 458
. 17, 459, 471, 472	\postnotesetup 9, 305
\l_postnotes_section_exp_bool	\postnotetext 11, 12
. 480, 486, 491	\postnotezref 34, 1067
\g_postnotes_section_name_tl	prg commands:
. 43, 478, 485, 489	\prg_new_protected_conditional:Npnn
_postnotes_set_babel_language:nn 375
. 39, 1217, 1217, 1238, 1239,	\prg_return_false: 403
1240, 1241, 1242, 1243, 1244, 1245,	\prg_return_true: 402
1254, 1255, 1256, 1257, 1266, 1267,	\printopstnotes 21
1276, 1277, 1278, 1279, 1280, 1281	\printopstnotes 11,
_postnotes_set_headers_vars:n .	12, 17-19, 23, 24, 26-29, 31, 32, 495
. . . 25, 28, 29, 859, 859, 908, 915, 921	prop commands:
_postnotes_set_headers_vars_-	\prop_gclear:N 73,
first: 24, 29, 533, 909, 917	759, 760, 761, 762, 763, 764, 765, 766

`\prop_get:NnNTF` 67,
 862, 866, 873, 877, 884, 888, 895, 899
`\prop_gput:Nnn` 24,
 25, 27, 29, 37, 40, 42, 44, 46, 48,
 54, 57, 60, 62, 803, 806, 809, 812,
 816, 819, 822, 825, 844, 847, 850,
 853, 955, 957, 959, 962, 1109, 1111
`\prop_item:Nn` 71
`\prop_new:N` 23, 53,
 730, 731, 732, 733, 734, 735, 736, 737
`\providecommand` 4
`\ProvidesExplPackage` 15

R

`\ref` 2, 452, 454
`\refsection` 33, 1053
`\refstepcounter` 12
`\rightmargin` 164, 181
`\rightskip` 284

S

scan commands:
 `\scan_stop:` 431
`\section` 125
 seq commands:
 `\seq_clear:N` 680
 `\seq_get_left:NN` 553, 629
 `\seq_gpop_left:NN` 541
 `\seq_gput_right:Nn` 327, 477
 `\seq_gset_eq:NN` 692
 `\seq_gsort:Nn` 698
 `\seq_if_empty:NTF` 521, 547, 623
 `\seq_if_empty_p:N` 539
 `\seq_map_inline:Nn` 648, 681, 777
 `\seq_new:N` 311, 511
 `\seq_put_right:Nn` 688, 690
 `\seq_set_eq:NN` 527
 `\l_tmpa_seq` 680, 688, 690, 692
`\setcounter` 36, 516
`\setlength` 160, 161, 162, 164, 165, 166,
 167, 168, 169, 177, 178, 179, 181,
 182, 183, 184, 185, 186, 284, 285, 286
`\setlocalecaption` 39
 skip commands:
 `\skip_horizontal:n` 292
`\small` 133
 sort commands:
 `\sort_return_same:` 714, 716, 718
 `\sort_return_swapped:` 713
`\spacefactor` 425, 430
`\stepcounter` 12, 324, 387, 561
 str commands:
 `\str_if_eq_p:nn` 707, 708

T

TeX and L^AT_EX 2_ε commands:

`\@afterindentfalse` 536
`\@afterindenttrue` 19, 536, 537
`\@auxout` 79, 85, 91
`\@capttype` 936
`\@currentcounter` 330, 605
`\@currentlabel` 331, 608
`\@footnotemark` 15
`\@ifl@t@r` 4
`\@makefnmark` 7
`\@mkboth` 119, 126
`\@newl@bel` 4, 76
`\@textsuperscript` 197, 291
`\blx@bibfiles` 33
`\blx@edef@refcontext` 983, 994
`\blx@endrefsection` 1052
`\blx@err@endnote` 947
`\blx@info` 1051
`\blx@lasthash@foot` 1010
`\blx@lasthash@text` 1009
`\blx@lastkey@foot` 1008
`\blx@lastkey@text` 1007
`\blx@lastmpfn` 1023
`\blx@refcontext@context` 963
`\blx@refcontext@labelalphanametemplatenam`
 993, 1000
`\blx@refcontext@labelprefix` ... 988
`\blx@refcontext@labelprefix@real` 989
`\blx@refcontext@sortingnamekeytemplatenam`
 991, 997
`\blx@refcontext@sortingtemplatenam`
 990, 996
`\blx@refcontext@uniquenametemplatenam`
 992, 999
`\blx@sorting` 990
`\blx@theendnote` 945
`\blx@theendnotetext` 946
`\blx@trackhash@foot` 1014, 1016
`\blx@trackhash@text` 1011, 1013
`\blx@trackkeys@foot` 1020, 1022
`\blx@trackkeys@text` 1017, 1019
`\c@blx@maxsection` 1045
`\c@page` 86, 92, 915
`\c@postnote` 14, 28, 33, 392
`\c@postnotetext` 606
`\c@refsection` 956, 974, 1005, 1006, 1033
`\c@refsegment` 958, 977
`\c@zcc@abschap` 1110, 1118
`\c@zcc@abssec` 1112, 1121
`\hyper@linkend` 413, 663
`\hyper@linkstart` 412, 662
`\ifmeasuring@` 36
`\p@postnote` 331, 609

<code>\post@note</code>	4, 74, 80, 86, 92	729, 738, 739, 740, 741, 742, 743,
<code>\z@</code>	1023	744, 745, 746, 747, 933, 1028, 1029,
<code>\zref@extractdefault</code>	1082	1059, 1204, 1205, 1206, 1207, 1214
<code>\text</code>	10, 11, 36	<code>\tl_set:Nn</code> 98, 145, 146, 150,
<code>\textnormal</code>	36	310, 325, 388, 395, 425, 526, 549,
<code>\textup</code>	36	550, 580, 625, 626, 642, 836, 990,
<code>\the</code>	425	991, 992, 993, 1032, 1208, 1209,
<code>\thechapter</code>	24, 38, 58	1210, 1211, 1233, 1234, 1235, 1236,
<code>\theHpostnote</code>	12	1249, 1250, 1251, 1252, 1261, 1262,
<code>\thepage</code>	24, 80	1263, 1264, 1271, 1272, 1273, 1274
<code>\thepostnote</code>	14, 325, 388, 395	<code>\l_tmpa_tl</code>
<code>\thesection</code>	24, 41, 61 683, 684, 700, 702, 704, 707,
tl commands:		710, 712, 863, 864, 867, 869, 870,
<code>\c_empty_tl</code>	106	874, 875, 878, 880, 881, 885, 886,
<code>\tl_clear:N</code>	68, 99,	889, 891, 892, 896, 897, 900, 902, 903
	771, 772, 773, 774, 775, 776, 988,	<code>\l_tmpb_tl</code> . 701, 702, 705, 708, 711, 712
	989, 1005, 1006, 1013, 1016, 1019, 1022	<code>\togglefalse</code>
<code>\tl_const:Nn</code>	74	987
<code>\tl_gclear:N</code> 478, 751, 752, 753, 754,		<code>\toggletrue</code>
755, 756, 757, 758, 767, 768, 769, 770		942
<code>\tl_gput_right:Nn</code>	39	token commands:
<code>\tl_gset:Nn</code>	864,	<code>\token_to_str:N</code>
865, 869, 870, 872, 875, 876, 880,		80, 86, 92
881, 883, 886, 887, 891, 892, 894,		<code>\topsep</code>
897, 898, 902, 903, 905, 1034, 1215		168, 185
<code>\tl_gset_eq:NN</code>	1047	
<code>\tl_if_empty:NTF</code>		
.... 322, 383, 435, 437, 785, 801, 842		
<code>\tl_if_eq:NNTF</code> ... 702, 787, 929, 1041		
<code>\tl_if_eq:NnTF</code> 545, 559, 585, 635, 684		
<code>\tl_if_eq:nnTF</code>	142, 779	
<code>\tl_new:N</code>	129, 136,	
202, 203, 204, 309, 344, 347, 419,		
485, 497, 498, 499, 500, 501, 503,		
504, 505, 506, 507, 508, 509, 510,		
722, 723, 724, 725, 726, 727, 728,		

		U
<code>\undef</code>	1007, 1008, 1009, 1010	
use commands:		
<code>\use:N</code>	980	
<code>\use_none:n</code>	1050, 1051	
<code>\UseHook</code>	49, 329, 380, 525, 593	

		W
<code>\write</code>	1164, 1170	

		Z
<code>\zcsetup</code>	1095, 1101	
<code>\zlabel</code>	438	
<code>\zref</code>	1083, 1085	