

Program and package xindex

—

0.49 (July 6, 2023)

Herbert Voß

hvoss@tug.org

Contents

1. Introduction	3
1.1. Syntax	3
1.2. How it works	4
1.3. The .idx file	4
2. Language	7
3. Sorting	10
3.1. Default sorting by a character table	10
3.2. Sorting by using UCA (Unicode Collation Algorithm)	14
3.3. Case sensitive index entries	15
3.4. Ignore space for sorting	16
4. Pagenumbers	17
4.1. Compressing pagenumbers series	17
4.2. Modify Pagenumber	17
4.3. Suppress Pagenumber	18
5. The config file	20
6. hyperref	23
7. Including L^AT_EX commands into the .idx file	23
8. Headings	24
9. Automatic index creation	26
10. Labels	26
11. Demerits	27
A. Examples	27

Contents

Thanks to:

Mark Baudoin; Denis Bitouzé; Andreas Deininger; Brian Dunn; Gonzalo Pesquero Serrano; Michal Hoflich; Mykel Kochenderfer; Alexey Kuznetzov; Frank Mittelbach; Peter Müller; Heiko Oberdiek; Matteo Paolini; Stefan Pinnow; Florent Rougon; Martin Sievers; Simon Spiegel; Jürgen Spitzmüller;

1. Introduction

The Lua program xindex is a unicode aware program for creating an index file from an .idx source file. It is completely compatible to the current makeindex program, but can handle UTF-8, 16, 32, and 64. The \LaTeX package xindex is a package which provides a \LaTeX command which writes additional text into the index file. This text (comments and/or macros) will be accepted by the program xindex.

The general structure of a data element in the Lua table is:

```
data = { Entry = <text>, -- like the input line without command \indexentry
  pages = {
    { number = <roman/arabic number or text>,
      special = <macro> }, -- the part after | in the input
    [...]
    { number = <roman/arabic number or text>,
      special = <macro> }
  },
  sortChar = <unicode codepoint>, -- of the first character of Entry
  Macro = <TeX macro> -- only useful with LaTeX package xindex
}
```

After reading the input file the Lua table pages has only one element for the number and the so-called special command. When the pages are compressed the table will collect all pages which refer to the same entry name.

1.1. Syntax

The syntax is xindex [...] <file(s)> where [...] are optional arguments, either in short or long form which, of course, can be mixed:

```
xindex
[-q,--quiet ]
[-h,--help ]
[-v ] verbose
[-c,--config ] default is cfg
[-e,--escapechar ] default is "
[-a, --no_casesensitive ] default is false
[-b,--no_labels ] default is false
[-n,--noheadings ] default is false
[-i,--ignoreSpace ] default is false
[-o,--output ] default is <input>.ind
[-k,--checklang ] default ist false
[-l,--language ] default is en
[-g,--no_pagenumber] default is false
[-p,--prefix] default L
[-u,--use_UCA ] default is false
[-s,--use_stdin ] default is false
```

1. Introduction

```
[-V,--version ]  
<files...> (default stdin) file(s)[.idx]    one or more files
```

For example:

```
xindex -q -l fr -b myDoc  
xindex -l de -c DIN2 demo1 demo2 demo3  
xindex -c norsk -o index.ind demo1 demo2.bdx demo3.adx
```

1. -q: quiet; -l fr: french language setting; -b: no labels; myDoc: input data myDoc or myDoc.idx)
output data will be myDoc.ind and logfile myDoc.ilg
2. -l de: German language setting; -c DIN2: config file xindex-DIN2.lua; demo1 demo2 demo3: input
data files with or without extension .idx
output data will be demo1.ind and logfile xindex.ilg
3. -c norsk: config file xindex-norsk.lua; -o index.ind: output file; demo1 demo2.bdx demo3.adx: in-
put data files with or without extension .idx
output data will be xindex.ind and logfile xindex.ilg

It is also possible to use standard input for the index data, which needs the -s parameter:

```
cat myDoc.idx | xindex -q -l fr -b -s  
xindex -l de -c DIN2 < myDoc.idx
```

The language has to be chosen as an international abbreviation in lower- or uppercase letters, see https://en.wikipedia.org/wiki/ISO_3166-2

1.2. How it works

xindex creates by default an output file <input>.ind which can be read by the \LaTeX document with the default command `\printindex`. One can use another output filename, which makes only sense if one doesn't use the `\printindex` command for typesetting the index. The default sorting is given by the configuration file, which defines replacements for accented characters, like `ö→o`.

1.3. The .idx file

There are four characters which must be escaped if used in the command `\index`: `!`, `@`, `"`, or `|`. These characters have a special meaning for the index. The default escape character is the double quote `"`:

xindex-1.tex

```
\usepackage{makeidx}\makeindex  
\usepackage{xindex}% for |left||rightParen  
  
\section{Escaping characters}  
\begin{itemize}  
\item Exclamation mark ! \index{Exclamation ("!)}\index{"!}  
\item Vertical bar | \index{Vertical bar ("|)}\index{"|}  
\item Doublequote \verb|"| \index{""}  
\end{itemize}
```

```

\item Double doublequote \verb|""| \index{""""}
\item At character @ \index{At ("@)}\index{"@}
\item Left parenthesis \{ \index{\parenLeft}
\item Right parenthesis \} \index{\parenRight}
\end{itemize}
run \texttt{xindex -u <file.idx>}\index{file.idx@\texttt{<file.idx>}|textit}\index{123}
\index{Etagé} \index{Ètagé}
\newpage
\printindex

```

1 Escaping characters

- Exclamation mark !
- Vertical bar |
- Doublequote "
- Double doublequote ""
- At character @
- Left parenthesis {
- Right parenthesis }

```
run xindex -u <file.idx>
```

Index

Symbols

!, 1
 "", 1
 ", 1
 {, 1
 }, 1
 @, 1
 |, 1

Numbers

123, 1

A

At (@), 1

E

Ètagé, 1
 Etagé, 1
 Exclamation (!), 1

F

<file.idx>, 1

V

Vertical bar (|), 1

It is by design that the parentheses { and } cannot be used as index entry. The *package* xindex defines the two commands \parenLeft and \parenRight which can be used instead (see examples above and and below).

The same example without using unicode sorting (no option -u):

```

\usepackage{makeidx}\makeindex
\usepackage{xindex}% for \left|\rightParen

\section{Escaping characters}
\begin{itemize}
\item Exclamation mark ! \index{Exclamation ("!")}\index{"!}
\item Vertical bar | \index{Vertical bar ("|")}\index{"|}
\item Doublequote \verb|"| \index{"}
\item Double doublequote \verb|""| \index{""""}

```

xindex-2.tex

```

\item At character @ \index{At ("@)\index{"@}
\item Left paranthesis \{ \index{\parenLeft}
\item Right paranthesis \} \index{\parenRight}
\end{itemize}
run \texttt{xindex -u <file.idx>}\index{file.idx@\texttt{<file.idx>}|textit}\index{123}
\index{Etagé} \index{Ètagé}
\newpage
\printindex

```

1 Escaping characters

- Exclamation mark !
- Vertical bar |
- Doublequote "
- Double doublequote ""
- At character @
- Left paranthesis {
- Right paranthesis }

```
run xindex -u <file.idx>
```

Index

Symbols

!, 1
 ””, 1
 ”, 1
 @, 1
 {, 1
 |, 1
 }, 1

Numbers

123, 1

A

At (@), 1

E

Ètagé, 1
 Etagé, 1
 Exclamation (!), 1

F

<file.idx>, 1

V

Vertical bar (|), 1

For the German language the double quote is an active character and it makes life easier if one chooses another character. The escape character can be changed easily by the optional argument `-e "<char>"` or `--escapechar "<char>"`. The following example shows how it works for the escape character `>` (greater). Internally the escape sequences are now defined as:

```

escape_chars = { -- by default " is the escape char
  {esc_char..'""', '//escapedquote//',      '""' },
  {esc_char..'@', '//escapedat//',          '@' },
  {esc_char..'|"', '//escapedvert//',       '| ' },
  {esc_char..'!', '//scapedexcl//',         '!' }
}

```

which is, of course, not of interest for the user. With the beginning the escaped chars are converted into the internal strings and later back to the origin meaning. The two characters `{}` cannot be used as `\{}` inside the argument of `\index`. The package `xindex` defines the two helper macros

```
\providecommand\parenLeft{\{}  
\providecommand\parenRight{\}}
```

The following example shows how to use it:

```
\usepackage{xindex}  
\usepackage{makeidx}\makeindex  
  
\section{Escaping characters with >}  
\begin{itemize}  
\item Exclamation mark ! \index{exclaim (>!)}  
\item Vertical bar| \index{Vertical bar (>|)}  
\item Doublequote \verb|"| \index{>}  
\item Double doublequote \verb|" "| \index{>">}  
\item At character @ \index{At (>@)}  
\item Group start \{ \index{\parenLeft}  
\item Group end \} \index{\parenRight}  
\end{itemize}  
Run \texttt{xindex} with \texttt{xindex -e ">"}\index{<file.idx>}\index{123}  
\newpage  
\printindex
```

xindex-3.tex

1 Escaping characters with >

- Exclamation mark !
- Vertical bar|
- Doublequote "
- Double doublequote ""
- At character @
- Group start {
- Group end }

Run xindex with xindex -e ">"

Index

Symbols

””, 1
”, 1
<file.idx>, 1
{, 1
}, 1

Numbers

123, 1

A

At (@), 1

E

exclaim (!), 1

V

Vertical bar (|), 1

2. Language

The language is only important for the first two headers in the output of the index data. They are by default *Symbols* followed by *Numbers*. In a new version of xindex it will be customizable. The predefined language is »en« and currently the following languages which its alias are possible:

2. Language

```
indexheader = {
  cs = {"Symboly", "Čísla", "czech"},
  da = {"Symboler", "Tal", "danish"},
  de = {"Symbole", "Zahlen", "austrian", "german", "germanb", "ngerman", "naustrian"},
  en = {"Symbols", "Numbers", "english", "USenglish", "american", "UKenglish", "british", "canadian", "aust"},
  es = {"Símbolos", "Números", "spanish"},
  fr = {"Symboles", "Nombres", "french", "français", "canadien", "acadien"},
  it = {"Simboli", "Numeri", "italian"},
  jp = {"シンボル", "番号", "japanese"},
  nl = {"Symbolen", "Nummers", "dutch"},
  no = {"Symboler", "Tall", "norsk", "nynorsk"},
  ru = {"Символы", "Числа", "russian"},
}
```

The following example was run with `xindex -l it <file>.idx`:

xindex-4.tex

```
\usepackage{makeidx}\makeindex
```

```
\section{Escaping characters with >}
```

```
\begin{itemize}
```

```
\item Exclamation mark ! \index{exclaim (!)}
```

```
\item Vertical bar| \index{Vertical bar (>|)}
```

```
\item Doublequote \verb|"| \index{>}"
```

```
\item Double doublequote \verb|" "| \index{>">"}
```

```
\item At character @ \index{At (>@)}
```

```
\end{itemize}
```

```
Run \texttt{xindex} with \texttt{xindex -l it -e ">"}\index{123}
```

```
\newpage
```

```
\printindex
```

1 Escaping characters with >

- Exclamation mark !
- Vertical bar|
- Doublequote "
- Double doublequote ""
- At character @

Run xindex with `xindex -l it -e ">"`

Indice analitico

Simboli

", 1

""", 1

Numeri

123, 1

A

At (@), 1

E

exclaim (!), 1

V

Vertical bar (|), 1

The following example was run with `xindex -k <file>.idx`. In this case `xindex` tries to detect the language from the aux file(s). This is only possible if package `babel` or `polyglossia` are used.


```

\usepackage[dutch]{babel}
\usepackage{makeidx}\makeindex

\section{Escaping characters with ?}
\begin{itemize}
\item Exclamation mark ! \index{exclaim (!)}
\item Vertical bar| \index{Vertical bar (|)}
\item Doublequote \verb|"| \index{"}
\item Double doublequote \verb|" "| \index{"?"}
\item At character @ \index{At (@)}
\end{itemize}
Run \texttt{xindex} with \texttt{xindex -k -e "?"}\index{123}
\newpage
\printindex

```

1 Escaping characters with ?

- Exclamation mark !
- Vertical bar|
- Doublequote "
- Double doublequote ""
- At character @

Run xindex with xindex -k -e "?"

Index

Symbolen

", 1
, 1

Nummers

123, 1

A

At (@), 1

E

exclaim (!), 1

V

Vertical bar (|), 1

For the russian language you have to choose the language and the config file. This allows to have different indexes with different language.

```

\usepackage[russian]{babel}
\usepackage{fontspec}
\usepackage[regular]{newcomputermodern}
\defaultfontfeatures{Ligatures=TeX}
\usepackage{xindex}\makeindex % run with xindex -u -l RU -c RU <file>

```

```

\begin{tabular}{ll}
Хвойные: & \verb|\index{Хвойные} |\index{Хвойные}\\
\quad торрея, & \\
\quad & \verb|\index{Хвойные!тисовые!торрея (Torreya)}| %
\quad & \index{Хвойные!тисовые!торрея (Torreya)} \\
\quad тис ягодный, & \\
\quad & \verb|\index{Хвойные!тисовые!тис!ягодный (Táxus baccata)}| %
\quad & \index{Хвойные!тисовые!тис!ягодный (Táxus baccata)} \\
\quad ливанский кедр, & \\
\quad & \verb|\index{Хвойные!сосновые!кедр!ливанский (Cedrus libani)}| %
\quad & \index{Хвойные!сосновые!кедр!ливанский (Cedrus libani)}

```

3. Sorting

```
\quad ель обыкновенная. &
\verb|\index{Хвойные!сосновые!ель!обыкновенная (Picea abies)}|{%
\index{Хвойные!сосновые!ель!обыкновенная (Picea abies)}\}[2ex]
Под колючей ежевикой & \verb|\index{Ежевика (Rúbus) }|{%
\index{Ежевика (Rúbus)}\}
жил ушастый ёж. &
\verb|\index{Ёж!ушастый (Hemiechinus auritus)}|{%
\index{Ёж!ушастый (Hemiechinus auritus)}
\end{tabular}
\printindex % xindex -u -l RU -c RU <file>
```

Хвойные:	<code>\index{Хвойные}</code>
торрея,	<code>\index{Хвойные!тисовые!торрея (Torreya)}</code>
тис ягодный,	<code>\index{Хвойные!тисовые!тис!ягодный (Taxus baccata)}</code>
ливанский кедр,	<code>\index{Хвойные!сосновые!кедр!ливанский (Cedrus libani)}</code>
ель обыкновенная.	<code>\index{Хвойные!сосновые!ель!обыкновенная (Picea abies)}</code>
Под колючей ежевикой	<code>\index{Ежевика (Rúbus) }</code>
жил ушастый ёж.	<code>\index{Ёж!ушастый (Hemiechinus auritus)}</code>

Предметный указатель

Е

Ёж

— ушастый (*Hemiechinus auritus*), 1

Ежевика (*Rúbus*), 1

Х

Хвойные, 1

— сосновые

— — ель

— — — обыкновенная (*Picea abies*), 1

— — кедр

— — — ливанский (*Cedrus libani*), 1

— тисовые

— — тис

— — — ягодный (*Taxus baccata*) , 1

— — торрея (*Torreya*) , 1

3. Sorting

3.1. Default sorting by a character table

The default sorting is unicode aware and uses a translation table for accented characters:

```
alphabet_lower = { -- for sorting
```

```

{ ' ' }, -- only for internal tests
{ 'a', 'á', 'à', 'ä' },
{ 'b' },
{ 'c' },
{ 'd' },
{ 'e', 'é', 'è', 'ë' },
{ 'f' },
{ 'g' },
{ 'h' },
{ 'i', 'í', 'ì', 'ï' },
{ 'j' },
{ 'k' },
{ 'l' },
{ 'm' },
{ 'n', 'ñ' },
{ 'o', 'ó', 'ò', 'ö' },
{ 'p' },
{ 'q' },
{ 'r' },
{ 's' },
{ 't' },
{ 'u', 'ú', 'ù', 'ü' },
{ 'v' },
{ 'w' },
{ 'x' },
{ 'y' },
{ 'z' }
}

```

There is also a table for the uppercase letters. If it should be edited or extended then copy first the base configuration file `xindex-cfg.lua` and modify that new file. It can be used by `xindex` with the optional argument `-c newfile` if it is named as `xindex-newfile.lua`. For German there already exists a configuration file `xindex-DIN2.lua` which uses the so-called »Telefonbuchsortierung« which converts the umlauts like `ö→oe`:

```

alphabet_upper = { -- for sorting
  { ' ' },
  { 'A', 'Á', 'À', 'Ä' },
  { 'B' },
  { 'C' },
  { 'D' },
  { 'E', 'È', 'Ê', 'ë' },
  { 'F' },
  { 'G' },
  { 'H' },
  { 'I', 'Í', 'Î', 'ï' },
  { 'J' },
  { 'K' },
  { 'L' },

```

3. Sorting

```
{ 'M' },
{ 'N', 'Ñ' },
{ 'O', 'Ó', 'Ò', 'Ö' },
{ 'P' },
{ 'Q' },
{ 'R' },
{ 'S' },
{ 'T' },
{ 'U', 'Ú', 'Ù', 'Ü' },
{ 'V' },
{ 'W' },
{ 'X' },
{ 'Y' },
{ 'Z' }
}
```

xindex-7.tex

```
\usepackage{makeidx}\makeindex
\newcommand\Index[1]{\index{#1}#1}
```

Sorted with `\verb|-l DE|`

```
\Index{Österreich} \Index{Öresund}
\Index{Ostern} \Index{Ober}
\Index{Oberin} \Index{Österreich}
\Index{Öresund} \Index{Ostern}
\Index{Ober} \Index{Oberin}
\Index{Obstler} \Index{Öl}
\Index{ölen} \Index{Ödem}
\Index{Oligarch} \Index{Oder}
\Index{oder} \index{Fluss!Oder}
\index{Oder|seealso{Fluss}}
\Index{Göbel} \Index{Goethe}
\Index{Göthe} \Index{Götz}
\Index{Goldmann}
```

```
\printindex
```

Index

F

Fluss
- Oder, 1

G

Göbel, 1
Goethe, 1
Goldmann, 1
Göthe, 1
Götz, 1

O

Ober, 1

Oberin, 1
Obstler, 1
Ödem, 1
Oder, 1
oder, 1
Oder, *siehe auch* Fluss
Öl, 1
ölen, 1
Oligarch, 1
Öresund, 1
Ostern, 1
Österreich, 1

The same sorted with the German DIN variant 2 with `--config DIN2`, which is part of the \TeX distribution. In this case a letter \ddot{O} is converted to Oe before sorting the word beginning with the letter \ddot{O} :

```
\usepackage{makeidx}\makeindex
\newcommand\Index[1]{\index{#1}#1}
```

Sorted with

```
\verb|--config DIN2 -l DE|
```

```
\Index{Österreich} \Index{Öresund}
\Index{Ostern} \Index{Ober}
\Index{Oberin} \Index{Österreich}
\Index{Öresund} \Index{Ostern}
\Index{Ober} \Index{Oberin}
\Index{Obstler} \Index{Öl}
```

```
\Index{ölen} \Index{Ödem}
\Index{Oligarch} \Index{Oder}
\Index{oder} \index{Fluss!Oder}
\index{Oder|seealso{Fluss}}
\Index{Göbel} \Index{Goethe}
\Index{Göthe} \Index{Götz}
\Index{Goldmann}
```

```
\printindex
```

Index

F	Öl, 1
Fluss	ölen, 1
- Oder, 1	Öresund, 1
G	Österreich, 1
Göbel, 1	Ober, 1
Göthe, 1	Oberin, 1
Goethe, 1	Obstler, 1
Götz, 1	oder, 1
Goldmann, 1	Oder, 1, <i>siehe auch</i> Fluss
O	Oligarch, 1
Ödem, 1	Ostern, 1

The following runs with `xindex -l jp <file>`:

```
\usepackage{fontspec}
\setmainfont{SourceHanSans}
\usepackage[japanese]{babel}
\addto\captionsjapanese{%
  \def\indexname{指数}}
\usepackage{hvinde}% for \Index
\usepackage{makeidx}\makeindex
```

```
\Index{車} \Index{車道}
日本\index{日本|fbox} \Index{病院} \Index{コンピュータ}
\Index{プリンタ} \Index{印刷} \Index{スイミングプール} \Index{天王}
\Index{広島} \Index{ドイツ} \Index{日本} \Index{ワープロ}
\Index{foo} und \Index{bar} \Index{/} \Index{4711}
\newpage\printindex
```

指数	
シンボル	ワ
//, 1	ワープロ, 1
番号	印
4711, 1	印刷, 1
B	天
bar, 1	天王, 1
F	広
foo, 1	広島, 1
コ	日
コンピュータ, 1	日本, 1, 1
ス	病
スイミングプール, 1	病院, 1
ド	車
ドイツ, 1	車, 1
プ	車道, 1
プリンタ, 1	

xindex-9.tex

3.2. Sorting by using UCA (Unicode Collation Algorithm)

With the optional argument `-u` or alternatively `--use_UCA` the sorting will be done by Michal Hoftich's Lua package `LUA-UCA`, which should be part of any TeX installation.

The sorting order can be easily modified. Read the documentation of the package `LUA-UCA` on how to do it and what languages are supported so far. Any additional code setting for UCA should be don't in the file `xindex-cfg-uca.lua`, which will automatically be read by `xindex`.

```
\usepackage{multicol}
\usepackage{makeidx}\makeindex
\def\Index#1{#1\index{#1}}
```

```
Sorted with \verb|-u -l cs|
\Index{ahoj} \Index{crha}, \Index{čaj}, \Index{chachar},
\Index{rak}, \Index{řeka}, \Index{srp}, \Index{šutr},
\Index{hudba}, \Index{linux}, \Index{zebra},
\Index{žába}, \Index{7 dubů}
\begin{multicols}{2} \printindex \end{multicols}
```

Sorted with `-u -l cs` ahoj crha, čaj, chachar, rak, řeka, srp, šutr, hudba, linux, zebra, žába, 7 dubů

Index	
A	L
ahoj, 1	linux, 1
C	R
crha, 1	rak, 1
Č	Ř
čaj, 1	řeka, 1
H	S
hudba, 1	srp, 1
Ch	šutr, 1
chachar, 1	Z
	žába, 1
	zebra, 1
	Čísla
	7 dubů, 1

xindex-10.tex

3.3. Case sensitive index entries

By default `foo` and `Foo` are two different entries and will be handled differently by `xindex`: `Foo` will be as an own entry before `foo`. Let's see a more complex example. In the index the entry `xindex-DIN2.lua` is the first one of the `xindex-???` series because uppercase letters are sorted before lowercase letters.

```
\usepackage{makeidx}
\usepackage{hyperref}
```

```
foo\newpage
\printindex
```

Index

X
xindex package, 2, 15
xindex program, 4, 13f
xindex-DIN2.lua file, 6
xindex-HAdW-eKO.lua file, 10
xindex-cfg-common.cfg file, 9
xindex-cfg-common.lua file, 14
xindex-cfg.lua file, 6, 10
xindex-dtk.lua file, 12
xindex-newfile.lua file, 6

xindex-11.tex

3. Sorting

The same example sorted with the `-a` or `--no_casesensitive` has another output: now `xindex-cfg-common.lua` is the first one of the `xindex-???` series.

xindex-12.tex

```
\usepackage{makeidx}  
\usepackage{hyperref}
```

```
foo\newpage  
\printindex
```

Index

X

xindex package, 2, 15
xindex program, 4, 13f
xindex-cfg-common.cfg file, 9
xindex-cfg-common.lua file, 14
xindex-cfg.lua file, 6, 10
xindex-DIN2.lua file, 6
xindex-dtk.lua file, 12
xindex-HAdW-eKO.lua file, 10
xindex-newfile.lua file, 6

3.4. Ignore space for sorting

By default »alpha sort« will be sorted before »alphaA«:

xindex-13.tex

```
\usepackage{makeidx}\makeindex  
% default sorting
```

```
Test  
\index{alpha sort}\index{alphaA}  
\newpage  
\printindex
```

Index

A

alpha sort, 1
alphaA, 1

This can be changed with the optional argument `-i` or `--ignoreSpace`:

xindex-14.tex

```
\usepackage{makeidx}\makeindex  
% sort with xindex -i <file>
```

```
Test  
\index{alpha sort}\index{alphaA}  
\newpage  
\printindex
```

Index

A

alphaA, 1
alpha sort, 1

4. Pagenumbers

4.1. Compressing pagenumber series

By default page sequences of an entry are compressed to

8f page 8 and 9

8ff page 8, 9, and 10

8-12 page 8, 9, ..., 12

The so-called folio abbreviation is language dependent and defined in the file `xindex-cfg-common.cfg`:

```
\usepackage{makeidx}\makeindex
```

```
Sorted with \verb|-l fr|
```

```
foobar\index{foobar|{}  
foo\index{foo}\index{bar}\index{baz}\newpage  
foo\index{foo}\index{bar}\index{baz}\newpage  
foo\index{bar}\index{baz}\newpage  
foo\index{baz}\newpage  
foo\index{foo}foobar\index{foobar|})  
\newpage  
\printindex
```

Index

B

bar, 1 sqq.

baz, 1–4

F

foo, 1 sq., 5

foobar, 1–5

xindex-15.tex

4.2. Modify Pagenumber

Every page can be combined with an additional macro, like `\index{foo|fbox}`, the page number will be set into a framebox. If we have on the same page the two commands:

```
foo\index{foo} and foo\index{foo|bar}
```

then we have two different index entries which will not be compressed to one entry. In the following example we have four different entries for `foo` which is the reason that we do not get an output like `foo, 1--4`. Only the first two entries are of the same type, so we get `1f` in the output.

```
\usepackage{makeidx}\makeindex
```

```
Ein foo\index{foo} \newpage und \index{foo}  
ein foo\index{foo|textit} \newpage  
und foo\index{foo|textbf} \newpage  
und foo\index{foo|fbox}
```

```
\newpage  
\printindex
```

Index

F

foo, 1f, 2, 3, 4

xindex-16.tex

4.3. Suppress Pagenumber

Instead of printing an index in the default way, one can also print a glossary without the pagenumbers. This is possible with the optional argument `-g` which is equivalent to the long form `--no_pagenumber`. The following example uses an own config file for the definition of the description environment:

```
itemPageDelimiter = ""
compressPages     = true
fCompress         = false
minCompress       = 2
rangeSymbol       = "--"
numericPage       = true
sublabels         = {"", "\\item", "\\item", "\\item"}
pageNoPrefixDel   = ""
idxnewletter      = "\\textbf"
envStart          = "\\begin{description}"
indexOpening      = "\\makeatletter\\z
                  \\def\\subitem{\\@idxitem} \\def\\subsubitem{\\@idxitem}\\z
                  \\def\\subsubsubitem{\\@idxitem}\\z
                  \\makeatother\\z
                  \\itemsep 0.1ex" -- commands after envStart
envStop           = "\\end{description}"
```

```
\usepackage[english]{babel}
\usepackage[imakeidx]{xindex}% run xindex internally
\makeindex
\makeindex[name=gls, options= -c description -n --no pagenumber]
Abbreviations:

XAS,\index{XAS --- X-ray absorption spectroscopy.}
XAFS,\index{XAFS --- Extended x-ray absorption fine structure.}
EXAFS,\index{EXAFS --- Extended x-ray absorption fine structure.}
XANES,\index{XANES --- X-ray absorption near edge structure.}
PES,\index{PES --- Photo emission spectroscopy.}
ARPES,\index{ARPES --- Angle resolved photo electron spectroscopy.}
SCES,\index{SCES --- Strongly correlated electron systems.}
HTSC,\index{HTSC --- High temperature superconductivity.}
MOCVD,\index{MOCVD --- Metalorganic chemical vapour deposition.}
PLD.\index{PLD --- Pulsed laser deposition.}

\smallskip Terms.

Fermions:
\index[gls]{Fermions@[Fermions]}%
\index[gls]{Fermions@[Fermions]!\[sf Fermion] --- a particle with a
half-odd-integer spin  $S$ .}electron,
\index[gls]{Fermions@[Fermions]!\[sf Electron] --- a subatomic particle
with a negative elementary electric charge:  $S=1/2$ .}proton,
```

```
\index[gls]{Fermions@[Fermions]![\sf Proton] --- a subatomic particle with a
positive elementary electric charge:  $S=1/2$ .}positron,
\index[gls]{Fermions@[Fermions]![\sf Positron] --- a particle with a positive
elementary electric charge, and the same mass as an electron:  $S=1/2$ .}neutron,
\index[gls]{Fermions@[Fermions]![\sf Neutron] --- a subatomic electrically
neutral particle:  $S=1/2$ .}neutrino.
\index[gls]{Fermions@[Fermions]![\sf Neutrino] --- an elementary electrically
neutral particle with very small rest mass:  $S=1/2$ .}
```

Bosons:

```
\index[gls]{Bosons@[Bosons]}%
\index[gls]{Bosons@[Bosons]![\sf Boson] --- a particle with an
integer spin  $S$ .}photon,
\index[gls]{Bosons@[Bosons]![\sf Photon] --- a quantum of the
electromagnetic field:  $S=1$ .}meson,
\index[gls]{Bosons@[Bosons]![\sf Meson] --- a hadronic subatomic particle
composed of an equal number of quarks and antiquarks:  $S=0$ .}pion.
\index[gls]{Bosons@[Bosons]![\sf Pion] --- any of  $\pi^0$ -,  $\pi^+$ -,  $\pi^-$ -
 $\pi^0$ -,  $\pi^+$ -,  $\pi^-$ - mesons consisting of quark and antiquark:  $S=0$ .}
```

```
\printindex
\printindex[gls]
```

Index

A

ARPES — Angle resolved photo
electron
spectroscopy., 1

E

EXAFS — Extended x-ray
absorption fine
structure., 1

H

HTSC — High temperature
superconductivity., 1

M

MOCVD — Metalorganic
chemical vapour
deposition., 1

P

PES — Photo emission
spectroscopy., 1
PLD — Pulsed laser deposition.,
1

S

SCES — Strongly correlated
electron systems., 1

X

XAFS — Extended x-ray
absorption fine
structure., 1
XANES — X-ray absorption
near edge structure., 1
XAS — X-ray absorption
spectroscopy., 1

Bosons

Boson — a particle with an integer spin S .

Meson — a hadronic subatomic particle composed of an equal number
of quarks and antiquarks: $S = 0$.

Photon — a quantum of the electromagnetic field: $S = 1$.

Pion — any of π^0 -, π^+ -, π^- - mesons consisting of quark and antiquark:
 $S = 0$.

Fermions

Electron — a subatomic particle with a negative elementary electric charge:
 $S = 1/2$.

Fermion — a particle with a half-odd-integer spin S .

Neutrino — an elementary electrically neutral particle with very small
rest mass: $S = 1/2$.

Neutron — a subatomic electrically neutral particle: $S = 1/2$.

Positron — a particle with a positive elementary electric charge, and the
same mass as an electron: $S = 1/2$.

Proton — a subatomic particle with a positive elementary electric charge:
 $S = 1/2$.

5. The config file

The main config file `xindex-cfg.lua` is used by default and loading it by the optional parameter `-c` makes no sense. A new config file must have the prefix `xindex-` and the file extension `.lua`, for example: `xindex-HAdW-eK0.lua` which can be used with `--config HAdW-eK0`. The file must be saved in the documents directory or in one which is known to `kpsewhich`, for example¹ `$TEXMFLOCAL/tex/lualatex/xindex/` Do not forget to update the filename database.

A new config file must declare at least the variables which are part of the default config file: the translation tables and

```
itemPageDelimiter = ","      -- Hello, 14
compressPages      = true
  -- something like 12--15, instead of 12,13,14,15. the |( ... |) syntax is still valid
fCompress         = true    -- 3f -> page 3, 4 and 3ff -> page 3, 4, 5
minCompress        = 3      -- 14--17 or
rangeSymbol       = "--"
numericPage        = true   -- for non numerical pagenumbers, like "VI-17"
sublabels          = {"", "-\\-", "--\\-", "---\\-"}
  -- for the sub(sub(sub-items, first one is empty
pageNoPrefixDel    = ""     -- a delimiter for page numbers like "VI-17" -- not used !!!
indexOpening       = ""     -- commands/text after \begin{theindex}
```

The new config file can define own functions for compressing the pagelist for a given entry and for the formatting of the output. They must be called `specialCompressPageList` and `specialGetPageList`.

For example:

```
function specialCompressPageList(pages)
  if (pages[1]["number"] == "") then pages[1]["number"] = " " end
  if (#pages <= 1) then
    pages[1]["number"] = pages[1]["number"]:gsub('-',':~')-- replace "-" with ":~"
    return pages
  end -- only one pageno
  local sortPages = {}
  local roman
  local volume
  local page
  local i
  for i=1,#pages do
    roman = string.gsub(pages[i]["number"],'%U*', '') -- only uppercase to catch VII/1-123f and VII/3-123ff (folium pages)
    if romanToNumber(roman) then
      roman = string.format("%05d",tonumber(romanToNumber(roman))) -- only roman part VII
    else
      roman = ""
    end
    volume = string.gsub(pages[i]["number"],'%a*', '') -- only the number /2 123 or /2-123
```

¹The directory `xindex` must be created before saving the file.

```

if volume then volume = volume:gsub('-%d*','') end -- delete - char to get /2
page = string.gsub(pages[i]["number"],'.*-', '')
page = string.format("%5s",page)
sortPages[#sortPages+1] = {
  origin = pages[i],
  sort = roman..volume.." "..page } -- no minus between Roman/Volume and first page
end
table.sort(sortPages, function(a,b) return a["sort"] < b["sort"] end )

[...]

return pages
end
end

```

is a special function which can handle page numbers like VII-17, VIII/2/1-186. Internally exists a function `compressPageList` which is used if no `specialCompressPageList` is defined.

```
\usepackage{makeidx}
```

```
\mbox{}}\printindex
```

index-18.tex

Personenverzeichnis

A		K	
Aachen, Johannes von	VII/1 : 215	Karl	
Aarones	VII/2/1 : 1003, 1012	- II., Kaiser	VII/1 : 147
Abrahamson	VII/2/1 : 864, 991, 1048, 1067, 1156	- III., Kaiser	VII/1 : 149
Adamson	VII/2/1 : 1223, IX/1 : 1228	- IV., Kaiser	VI/1 : 12, VII/1 : 34, 147
Adrian		- V., Kaiser	VI/1 : 84, 284, 654, VI/2 : 708, 1014, 1043, 1131, 1210, VII/1 : 34
- Hauster	VII/1 : 514, XI/1 : 515	- VI., Kaiser	VII/1 : 296
Alting		- IX., Kaiser	VII/1 : 296
- Mensa	VII/1 : 426, 434, 453, 455, 466f.	- X., Kaiser	VII/1 : 149
B		- der Große, Kaiser	VI/2 : 987, 989, 1028
Braunschweig-Wolfenbüttel		O	
- Karl Viktor von, Herzog	VI/1 : 83	Osnabrück	
Bremen		- Heinz von, Bischof	see Sachsen-Lauenburg
- Heinz von, Erzbischof	see Sachsen-Lauenburg	S	
J		Schleswig-Holstein	
Julian		- Rudolf von, Herzog	VII/2/1 : 758-761, 765
- Apostata, römischer Kaiser	VII/2/1 : 904	Z	
Justinian I., byzantinischer Kaiser	VII/1 : 326, 734, VII/2/1 : 1011	Zwingl, Haldrich	IX : 479, 692

The config file `xindex-dtk.lua` defines a special page output:

```
function specialGetPageList(v,hyperpage) -- Entry table, boolean
```

5. The config file

```

local Pages = {}
[.]
  if (Pages[1]["special"] == nil) or (Pages[1]["number"] == nil) then return "" end
  if #Pages == 1 then
    return "\\relax"..Pages[1]["number"].."\\@nil"
  else
    pageNo = "\\relax"..Pages[1]["number"]
    for i=2,#Pages do
      if Pages[i]["number"] then
        pageNo = pageNo..", "..Pages[i]["number"].."\\@nil"
        Pages[i] = {}
      end
    end
  end
[.]
end

```

The following example runs `xindex -c dtk -l de -n <input>`

xindex-19.tex

```
\usepackage{makeidx}
```

```
\mbox{}\label{president}
\printindex
```

Autorenliste

Elke Bährendtsen
elke@xyz.de

Horst Fannt
Friedrichallee 74
13233 Neu-Isenburg
horst.fannt@gmxnet.de

Jonasson Jared Jazek
mail@jones.net

Martin Koon
Freiherr-Links-Weg 16
15525 Neckar
koo@xyz.org

[14] **Eike Schulten** [40]
Haussteig 15
36396 Stuttgart
eike.schulten@kabel.de

[48] **Markus Severs** [4]
siehe Seite 1

[20] **Herbert Voß** [3, 5]
Wasgensteig 12
10127 Potsdam
herbert@xyz.de

[24, 31] **Michael Ziegenda** [9]
Lokostr. 19
20713 Kallin
ziegenda@mail.com

There are three predefined sublabels for `\subitems`. The program itself can handle more, there is no limit for `xindex`.

xindex-20.tex

```

\makeatletter
\g@addto@macro{\theindex}{%
  \def\subsubsubitem{\@idxitem\hspace*{35\p@}}
  \def\subsubsubsubitem{\@idxitem\hspace*{40\p@}}
}
\makeatother
\usepackage{makeidx}\makeindex

```

```

foo\index{foo} bar\index{foo!bar}
baz\index{foo!bar!baz} foobar%
\index{foo!bar!baz!foobar} Kuba
\index{foo!bar!baz!foobar!Kuba}
\newpage \printindex

```

Index

F
foo, 1
 - bar, 1
 - baz, 1
 — foobar, 1
 — Kuba, 1

6. hyperref

Using the package hyperref is no problem:

```
\usepackage{makeidx}\makeindex
\usepackage{hvinde}% for \Index
\usepackage{colorlinks}{hyperref}
```

```
Sorted with \verb|-l DE|
\Index{Österreich} \Index{Öresund}
\Index{Ostern} \Index{Ober} \Index{Oberin}
\Index{Österreich} \index{Öresund|textbf}
\Index{Ostern} \Index{Ober} \Index{Oberin}
\Index{Obstler} \Index{Öl} \Index{ölen}
\Index{Ödem} \Index{Oligarch} \Index{Oder}
\Index{oder} \index{Fluss!Oder|textit}
\Index{Oder|seealso{Fluss}} \Index{Göbel}
\Index{Goethe} \Index{Göthe} \Index{Götz}
\newpage\Index{Goldmann} \Index{Goethe}
\newpage \printindex
```

Index

F	
Fluss	Oberin, 1
- Oder, 1	Obstler, 1
	Ödem, 1
G	Oder, 1
Göbel, 1	oder, 1
Goethe, 1f	Oder, <i>see also</i> Fluss
Goldmann, 2	Öl, 1
Göthe, 1	ölen, 1
Götz, 1	Oligarch, 1
	Öresund, 1, 1
O	Ostern, 1
Ober, 1	Österreich, 1

xindex-21.tex

7. Including L^AT_EX commands into the .idx file

The command `\addtocontents` doesn't work for the index file. With the L^AT_EX package `xindex` (same name as the Lua program `xindex`) defines a macro `\writeidx` which writes its argument into the .idx file. This can be useful to insert a pagebreak/""columnbreak before a new letter in the output of the index file:

```
\documentclass{article}
\usepackage{makeidx}
\makeindex
\usepackage{xindex}
\begin{document}

\index{foo}foo and
\writeidx{\clearpage}
\index{bar}bar

\printindex
\end{document}
```

Such commands are then taken into account by the program `xindex`. With the often used program `makeindex` such commands are ignored. In the following example we put an horizontal line after the first entry:

xindex-22.tex

```
\usepackage{xindex}
\makeindex

\index{foo}foo and
\writeidx{\item\protect\hrulefill}
\index{bar}bar
\index{gex}gex

\printindex
```

Index

B
bar, 1

F
foo, 1

G
gex, 1

8. Headings

By default the output uses the English headings: Symbols, Numbers, and A ... There are three predefined languages `en`, `de`, and `fr`. The definition is in the file `xindex-cfg-common.lua` (see also section 2 on page 7). It can easily be extended for other languages. Sometimes the headers are not needed, for example in a name list. With the optional argument `-n` or `--noheadings` the created `.ind` file has only the vertical space between different first letters:

xindex-23.tex

```
\usepackage{makeidx}\makeindex

Ein foo\index{foo}\index{bar|{}
  \newpage und \index{foo}
ein foo\index{foo|textit} \newpage
und foo\index{foo|textbf} \newpage
und foo\index{foo|fbox}
\index{bar|)}
\newpage
\verb|xindex -n <file>|
\printindex
```

```
xindex -n <file>
```

Index

bar, 1–4

foo, 1f, 2, 3, 4

The headings are printed by default as `\textbf`. This can be changed in the config file by setting the variable `idxnewletter`, for example: `idxnewletter = "\\textit"`. If you need some more code here then define an own macro for it, which can be seen in the following example. It has an own config file `xindex-header.lua` which has the line

```
idxnewletter = "\\idxnewletter"
```

In the documents preamble there is the definition:

```
\newcommand\idxnewletter[1]{\textbf{\textit{#1}}}
```



```

æšžŒŠŸŽ
\usepackage{makeidx}\makeindex
\newcommand\idxnewletter[1]{\textbf{\textit{#1}}}

```

```

æšžŒŠŸŽ
\section{Escaping characters}
\begin{itemize}
\item Exclamation mark ! \index{exclaim (!)}
\item Vertical bar| \index{Vertical bar (|)}
\item Doublequote \verb|"| \index{""}
\item Double doublequote \verb|" "| \index{" """}
\item At character @ \index{At (@)}
\end{itemize}
run \verb|xindex -c header <file.idx>|
\index{<file.idx>@\texttt{<file.idx>}}
\index{123}
\newpage
\printindex

```

Index

Symbols

””, 1
 ”, 1
 <file.idx>, 1

Numbers

123, 1

A

At (@), 1

E

exclaim (!), 1

V

Vertical bar (|), 1

xindex-24.tex

9. Automatic index creation

With package `xindex` one can define several different index files, e. g. an index of names. With the optional argument `imakeidx` the package itself loads `imakeidx` and adds the program `xindex` as the default program to `imakeidx`.

xindex-25.tex

```
\usepackage[imakeidx]{xindex}
\makeindex[name=persons,title=Index of names,
  columns=1,options= --noheadings]
\def\ThanhVN{Hàn Thê\protect\llap{%
  \raise 0.5ex\hbox{\'{}}}}

foo\index[persons]{Niepraschk,~ Rolf}
foo\index[persons]{Lamport,~ Leslie}
foo\index[persons]{Knuth,~ Donald}
foo\index[persons]{Knuth,~ Donald}
\newpage
foo\index[persons]{Lamport,~ Leslie}
foo\index[persons]{Thành,~ \ThanhVN}
foo\index[persons]{Kew,~ Jonathan}
foo\index[persons]{Kohm,~ Markus}
foo\index[persons]{Preining,~ Norbert}
\newpage
foo\index[persons]{Schenk,~ Christian}
foo\index[persons]{Feuerstack,~ Thomas}
foo\index[persons]{Tobin,~ Geoffrey}
foo\index[persons]{Wilson,~ Peter}
\newpage
foo\index[persons]{Kohm,~ Markus}
foo\index[persons]{Theiling,~ Henrik}
foo\index[persons]{Pégourié-Gonnard,~ Manuel}
foo\index[persons]{Roux,~ Élie}
\newpage
foo\index[persons]{Mittelbach,~ Frank}
foo\index[persons]{Fairbairns,~ Robin}
foo\index[persons]{Lemberg,~ Werner}
foo\index[persons]{Volovich,~ Vladimir}

\printindex[persons]
```

Index of names

Fairbairns, Robin,
Feuerstack, Thomas,

Kew, Jonathan,
Knuth, Donald,
Kohm, Markus,

Lamport, Leslie,
Lemberg, Werner,

Mittelbach, Frank,

Niepraschk, Rolf,

Pégourié-Gonnard, Manuel,
Preining, Norbert,

Roux, Élie,

Schenk, Christian,

Thành, Hàn Thê,
Theiling, Henrik,
Tobin, Geoffrey,

Volovich, Vladimir,

Wilson, Peter,

You have to run \LaTeX with the `--shell-escape` option to run `xindex` from within the \LaTeX document.

10. Labels

By default `xindex` creates labels in the index for the symbols, numbers, and other parts (letters) to which one can refer. with `\ref{label}`. The labels are named `L-xindex-<name>`. The prefix `L` can be changed by the config file. `<name>` maybe symbols, numbers, or `A` (a letter). For example

```
\begin{theindex}
\par\textbf{Symbols}\label{L-xindex-symbols}
```

```
\nopagebreak[4]
\item @, \hyperpage{3}
\item (, \hyperpage{3}
\item !, \hyperpage{3}

\indexspace
\textbf{A}\label{L-xindex-A}
[...]
```

The labels can be used to create a reference to a specific part in the index, for example the letter X is in the index on page 30 (`\pageref{L-xindex-X}`).

With the optional argument `-b` for the run of `xindex` one can suppress the creation of the labels, e.g. `xindex -b -l fr ...`.

11. Demerits

- For more than 5000 entries in the `.idx` file the internal Lua function for sorting may take some time.
- The `.idx` file is not checked for \LaTeX errors in the argument of `\indexentry`.

A. Examples

```
\usepackage[imakeidx]{xindex}
\makeindex
% Brian Dunn
```

```
First level.\index{first level}

First level second level.\index{first level!second level}

Duplicate.\index{first level!second level}

Alpha.\index{alpha}

Alpha beta.\index{alpha!beta}

Alpha beta gamma.\index{alpha!beta!gamma}

Duplicate alpha beta.\index{alpha!beta}

Duplicate alpha beta gamma.\index{alpha!beta!gamma}

\newpage
\printindex
```

Index

```
A
alpha, 1
  - beta, 1
    - gamma, 1

F
first level, 1
  - second level, 1
```

xindex-26.tex

xindex-27.tex

```
\usepackage[imakeidx]{xindex}
\makeindex[options=-l de]

% Martin Sievers

Test \index{A!Test} oder auch \index{B!Test}
\newpage
\printindex
```

Index	
A	B
A	B
- Test, 1	- Test, 1

```
%% Denis Bitouzé
\usepackage{makeidx}\makeindex
```

```
Foo\index{foo!bar1!baz1}
Foo\index{foo!bar1!baz2}
Foo\index{foo!bar2!baz1}
Foo\index{foo!bar2!baz2}
\printindex
```

Index

F

foo

- bar1
 - baz1, 1
 - baz2, 1
- bar2
 - baz1, 1
 - baz2, 1

xindex-28.tex

Index

Symbols

, 4

-u package option, 5

@, 4

!, 4

A

accented characters, 4

\addtocontents, 23

argument, 3

aux file, 8

B

babel package, 8

C

columnbreak, 23

config file, 21

D

data element, 3

description environment, 18

E

entry name, 3

escape character, 4, 6

H

hyperref package, 23

I

.idx file extension, 3, 23, 27

imakeidx package option, 26

imakeidx package, 26

.ind file extension, 24

\index, 4, 6

index of names, 26

\indexentry, 27

K

kpsewhich program, 20

L

label, 26

language, 4, 7, 24

L^AT_EX errors, 27

.lua file extension, 20

M

makeindex program, 3, 23

N

numbers, 26

O

output, 4

P

page number, 3, 21

pagebreak, 23

\pageref, 27

\parenLeft, 5

\parenRight, 5

polyglossia package, 8

\printindex, 4

R

\ref, 26

S

Shell escape, 26

sorting, 4, 27

\subitems, 22

symbols, 26

syntax, 3

T

\textbf, 24

U

unicode, 3

UTF-8, 3

W

\writeidx, 23

X

xindex package, 3, 6, 23, 26

xindex program, 7, 14f, 22f, 26

xindex-cfg-common.cfg file, 17

xindex-cfg-common.lua file, 24

xindex-cfg-uca.lua file, 14

xindex-cfg.lua file, 11, 20

xindex-DIN2.lua file, 11

xindex-dtk.lua file, 21

xindex-HAdW-eKO.lua file, 20

xindex-header.lua file, 24

xindex-newfile.lua file, 11