

# docshots: L<sup>A</sup>T<sub>E</sub>X Package that Renders T<sub>E</sub>X Samples Next to Their PDF Snapshots\*

Yegor Bugayenko  
yegor256@gmail.com

2024-01-09, 0.4.1

**NB!** This package doesn't work on Windows! Also, you must run T<sub>E</sub>X processor with `--shell-escape` option. Also, you must have `pdlafter`, [Perl](#), [Ghostscript](#), and [pdfcrop](#) installed.


## 1 Introduction

When you want to demonstrate to the readers of your documentation how to use certain T<sub>E</sub>X commands, the best way would be to show exactly how the entire document will be rendered in PDF, using a subprocess that would render it (via `pdflatex`, for example). To [my best](#) knowledge, there were no packages that would allow you do exactly this. That's why I created this simple package.

For example, this code:

```
\begin{docshot}
\documentclass{article}
\usepackage{xcolor}
\pagestyle{empty}
\begin{document}
  Hello, {\color{orange}\LaTeX}!
\end{document}
\end{docshot}
```


is rendered as such:

	<pre>1 \documentclass{article} 2 \usepackage{xcolor} 3 \pagestyle{empty} 4 \begin{document} 5   Hello, {\color{orange}\LaTeX}! 6 \end{document}</pre>
---	---

Here is a more complex example:

---

\*The sources are in GitHub at [yegor256/docshots](https://github.com/yegor256/docshots)



```


1 \documentclass{article}
2 \usepackage{tikz}
3 \pagestyle{empty}
4 \begin{document}
5 \begin{tikzpicture}
6 \node [circle,draw] (v0) {$v_0$};
7 \node [circle,draw=orange,thick,
8   below right of=v0] (v1) {$v_1$};
9 \draw [->] (v0) -- (v1);
10 \end{tikzpicture}
11 \end{document}

```

The picture you see on the left side is rendered by a subprocess executing `pdflatex` with the `.tex` content taken from the source file. After a successful processing of  $\text{\TeX}$  sources, we use [pdfcrop](#) to trim the document.

We execute `pdflatex` with `-interaction=batchmode` and `-halt-on-error` options. This means that  $\text{\TeX}$  processing will stop at the first error. Check your  $\text{\TeX}$  log to understand what went wrong.

When you render a text instead of a single picture, it's recommended to use [geometry](#) package to change the size of the page:



```

1 \documentclass{article}
2 \usepackage[paperwidth=2in,
3   paperheight=2.3in]{geometry}
4 \begin{document}
5 ‘‘There is no sadder thing than
6 a young pessimist, except an old
7 pessimist’’ --- \emph{Mark Twain}
8 \end{document}

```

You can also use `\pagestyle{empty}` as was done in previous docshots.

## 2 Package Options

`pdflatex` The default command line tool for turning `.tex` into `.pdf` is `pdflatex`. However, you can change that by using `pdflatex` package option, for example:

```

\documentclass{article}
\usepackage[pdflatex=/usr/local/bin/pdflatex]{docshot}
\begin{document}
\begin{docshot}
Hello, world!
\end{docshot}
\end{document}

```

`gs` The default location of Ghostscript is just `gs`. You can change that by using `gs` package

option, for example:

```
\usepackage[gs=/usr/bin/ghostscript]{docshot}
```

**pdfcrop** The default location of pdfcrop is just pdfcrop. You can change that by using pdfcrop package option, for example:

```
\usepackage[pdfcrop=/bin/pdfcrop]{docshot}
```

**margin** When we crop the PDF rendered, we leave a margin around the content. The default value may be changed by the package option margin:

```
\usepackage[margin=10]{docshot}
```

**nocrop** You may disable cropping with the help of nocrop option:

```
\usepackage[nocrop]{docshot}
```

**hspace** The horizontal distance between the image and its verbatim T<sub>E</sub>X source may be configured via hspace package option:

```
\usepackage[hspace=1em]{docshot}
```

**left** The default width of the image may be changed by left option, while the width of  
**right** the verbatim T<sub>E</sub>X source may be modified by right option:

```
\usepackage[left=2in,right=.5\linewidth]{docshot}
```

**dtx** If you use this package inside .dtx documentation, add dtx package option. Thanks to this option all comment symbols will be removed from line starts:

```
\usepackage[dtx]{docshot}
```

**tmpdir** The default location of temp files is \_docshots. You can change this using tmpdir option:

```
\usepackage[tmpdir=/tmp/foo]{docshot}
```

**runs** By default, we run pdf<sub>l</sub>atex just once for each docshot. You can change this number using the package option runs. This may be helpful if you need BibT<sub>E</sub>X processing, for example:

```
\usepackage[runs=3]{docshot}
```

**small** You don't have too much freedom in formatting of verbatim texts, but you can make  
**tiny** their font a bit smaller using small package option. You can also make it very small using tiny option:

```
\usepackage[small]{docshot}
```

**log** With log option you can make us print all possible logs to the main T<sub>E</sub>X log. By default, we don't do this and you won't see the output of pdf<sub>l</sub>atex compilation, for example. Just use it like this:

```
\usepackage[log]{docshot}
```

**inputminted** By default, we render the verbatim text using \VerbatimInput command. You can change that and make us use \inputminted from [minted](#) package instead, for example:

```
\usepackage{minted}  
\setminted[java]{frame=lines,framesep=2mm}  
\usepackage[inputminted=java]{docshot}
```

`\lstinputlisting` By default, we render the verbatim text using `\VerbatimInput` command. You can change that and make us use `\lstinputlisting` from [listings](#) package instead, for example:

```
\usepackage{listings}
\lstset{basicstyle=\small}
\usepackage[lstinputlisting]{docshot}
```

### 3 Fine-tuning Options

`\docshotOptions` By default, we render the verbatim text using `\VerbatimInput` command with no options. You can add your options using `\docshotOptions` command:

```
\docshotOptions{firstline=4}
\begin{docshot}
...
\end{docshot}
```

The options will be cleaned up by the first render of a docshot.

### 4 Prerequisites

`\docshotPrerequisite` If you need some files to be present next to the `.tex` snippet while it's rendered by `pdflatex`, you can use `\docshotPrerequisite` with a single mandatory argument. The argument is the name of a file you need to be copied from current directory to the temporary directory, where all snippets are rendered. The command can be used either in the body of the document or in the preamble — it doesn't matter, as long as it shows up before the docshot that needs the prerequisite. For example:

```
\documentclass{article}
\usepackage{docshot}
\docshotPrerequisite{duck.jpg}
\begin{document}
\begin{docshot}
  \documentclass{article}
  \usepackage{graphicx}
  \pagestyle{empty}
  \begin{document}
    This is my favorite picture of a duck:
    \includegraphics[width=2in]{duck.jpg}
  \end{document}
\end{docshot}
\end{document}
```

`\docshotAfter` If you need something to happen after each `pdflatex` run of a docshot, you may use `\docshotAfter` command right before docshot environment. For example, you have a bibliography file that you want to be visible for all snippets and you want all of them to run [biber](#) in order to process citations:

```
\documentclass{article}
\usepackage{docshot}
\docshotPrerequisite{main.bib}
\begin{document}
```

```

\docshotAfter{biber $2}
\begin{docshot}
  \documentclass{acmart}
  \usepackage[natbib=true]{biblatex}
  \addbibresource{main.bib}
  \pagestyle{empty}
  \begin{document}
    You must read the book of \citet{knuth1984}.
    \printbibliography
  \end{document}
\end{docshot}
\end{document}

```

The script you specify in the first argument of `\docshotAfter` will get three arguments when it runs:

- \$1 the cycle of pdf<sub>l</sub>atex processing (1, 2, ...),
- \$2 the hash of the snippet,
- \$3 the name of the .tex file.

\$2 is basically equals to \$1 with an attached .tex suffix. `\docshotAfter` applies only to the first docshot environment that goes after it! You must specify `\docshotAfter` before each docshot where you want such post-processing to happen.

## 5 Implementation

First, we include a few packages:

```

1 \RequirePackage{iexec}
2 \RequirePackage{fancyvrb}
3 \RequirePackage{xcolor}
4 \RequirePackage{graphicx}
5 \RequirePackage{tikz}

```

Then, we process package options:

```

6 \RequirePackage{pgfopts}
7 \RequirePackage{ifluatex}
8 \RequirePackage{ifxetex}
9 \def\docshots@log{}
10 \pgfkeys{
11   /docshots/.cd,
12   dtx/.store in=\docshots@dtx,
13   log/.code=\def\docshots@log{log},
14   nocrop/.code=\def\docshots@nocrop{},
15   lstinputlisting/.store in=\docshots@lstinputlisting,
16   inputminted/.store in=\docshots@inputminted,
17   tmpdir/.store in=\docshots@tmpdir,
18   tmpdir/.default=_docshots\ifxetex-xe\else\ifluatex-lua\fi\fi,
19   small/.store in=\docshots@small,
20   tiny/.store in=\docshots@tiny,
21   runs/.store in=\docshots@runs,
22   runs/.default=1,
23   pdflatex/.store in=\docshots@pdflatex,
24   pdflatex/.default=pdflatex,

```

```

25 gs/.store in=\docshots@gs,
26 gs/.default=gs,
27 pdfcrop/.store in=\docshots@pdfcrop,
28 pdfcrop/.default=pdfcrop,
29 margin/.store in=\docshots@margin,
30 margin/.default=5,
31 hspace/.store in=\docshots@hspace,
32 hspace/.default=.05\linewidth,
33 left/.store in=\docshots@left,
34 left/.default=.3\linewidth,
35 right/.store in=\docshots@right,
36 right/.default=.55\linewidth,
37 tmpdir,pdflatex,gs,pdfcrop,margin,hspace,left,right,runs
38 }
39 \ProcessPgfoptions{/docshots}

```

Then, we print the version of pdflatex to T<sub>E</sub>X log:

```
40 \iexec[\docshots@log,quiet]{"\docshots@pdflatex" --version}%
```

Then, we print the version of pdfcrop to T<sub>E</sub>X log:

```

41 \ifdefined\docshots@nocrop\else%
42 \iexec[\docshots@log,quiet]{"\docshots@pdfcrop" --version}%
43 \fi%

```

Then, we print the version of ghostscript to T<sub>E</sub>X log:

```
44 \iexec[\docshots@log,quiet]{"\docshots@gs" --version}%
```

Then, we make a directory where all temporary files will be kept:

```
45 \iexec[null]{mkdir -p "\docshots@tmpdir/\jobname"}%
```

\docshots@mdfive Then, we define a command for MD5 hash calculating of a file:

```

46 \RequirePackage{pdftexcmds}
47 \makeatletter\newcommand\docshots@mdfive[1]{\pdf@filemdfivesum{#1}}\makeatother

```

docshot Then, we define docshot environment:

```

48 \makeatletter\newenvironment{docshot}
49 {\VerbatimEnvironment\begin{VerbatimOut}
50 {\docshots@tmpdir/\jobname/verbatim.tex}}
51 {\end{VerbatimOut}}%

```

If we are in dtx mode, leading percent characters must be removed:

```

52 \ifdefined\docshots@dtx%
53 \iexec[null]{perl -i -0777pe "s/(\n|^)\x{25}\\s?/\1/g"
54 \docshots@tmpdir/\jobname/verbatim.tex}%
55 \fi%

```

We calculate MD5 hashsum of the file content:

```
56 \def\hash{\docshots@mdfive{\docshots@tmpdir/\jobname/verbatim.tex}}%
```

If the PDF with the required name already exists, we ignore this step. Otherwise, we copy verbatim.tex into new file and run pdflatex:

```

57 \IfFileExists{\docshots@tmpdir/\jobname/\hash.pdf}
58 {\message{docshots: Won't render,
59 the PDF '\docshots@tmpdir/\jobname/\hash.pdf' already exists^^J}}
60 {\iexec[\docshots@log,quiet]{cp "\docshots@tmpdir/\jobname/verbatim.tex"
61 "\docshots@tmpdir/\jobname/\hash.tex"}}%

```

```

62 \message{docshots: rendering at line no. \the\inputlineno^^J}%
63 \foreach \n in {1,...,\docshots@runs}{%
64   \iexec[\docshots@log,
65     stdout=\docshots@tmpdir/\jobname/\hash.stdout,
66     exit=\docshots@tmpdir/\jobname/\hash.ret,
67     quiet,trace]{cd "\docshots@tmpdir/\jobname" &&
68       "\docshots@pdflatex"
69       -interaction=errorstopmode
70       -halt-on-error
71       -shell-escape
72       \hash.tex}%
73   \ifnum\n=1\else%
74     \message{docshots: pdflatex run no.\n^^J}%
75   \fi%
76   \IfFileExists{\docshots@tmpdir/\jobname/after.sh}
77     {\iexec[\docshots@log,quiet]{chmod a+x
78       "\docshots@tmpdir/\jobname/after.sh"}
79     \iexec[\docshots@log,quiet]{cd "\docshots@tmpdir/\jobname" &&
80       ./after.sh \n\space \hash\space \hash.tex}}
81   {}}}%

```

Here we delete after.sh which may exist here after the last compilation of pdflatex:

```

82 \iexec[\docshots@log,quiet]{rm -f "\docshots@tmpdir/\jobname/after.sh"}

```

If a cropped version of the PDF with the required name already exists, we ignore this step. Otherwise, we ask pdfcrop to crop the PDF:

```

83 \IfFileExists{\docshots@tmpdir/\jobname/\hash.crop.pdf}
84   {\message{docshots: Won't pdfcrop,
85     the PDF '\docshots@tmpdir/\jobname/\hash.crop.pdf'
86     already exists^^J}}
87   {\ifdefined\docshots@nocrop
88     \iexec[\docshots@log,quiet]{cp
89       "\docshots@tmpdir/\jobname/\hash.pdf"
90       "\docshots@tmpdir/\jobname/\hash.crop.pdf"}%
91     \else%
92       \iexec[\docshots@log,quiet]{"\docshots@pdfcrop"
93         --margins 0
94         "\docshots@tmpdir/\jobname/\hash.pdf"
95         "\docshots@tmpdir/\jobname/\hash.crop.pdf"}%
96     \fi}%

```

We configure fancyvrb:

```

97 \def\docshots@xopts{
98   numbers=left,numbersep=3pt,
99   frame=leftline,framerule=.2pt,rulecolor=\color{gray},
100   samepage=true,
101   commandchars=none,
102   baselinestretch=1
103 }%
104 \ifdefined\docshots@small%
105   \edef\docshots@xopts{\unexpanded\expandafter{\docshots@xopts},fontsize=\small}%
106 \fi%
107 \ifdefined\docshots@tiny%
108   \edef\docshots@xopts{\unexpanded\expandafter{\docshots@xopts},fontsize=\scriptsize}%
109 \fi%

```

```

110 \ifdefined\docshots@opts
111 \edef\docshots@xopts{\unexpanded\expandafter{\docshots@xopts},\docshots@opts}
112 \fi

Finally, we render the two-column content:

113 \begin{group}%
114 \par%
115 \tikz[baseline=(a.north)]
116 \node (a) [draw=gray,inner sep=\docshots@margin,
117 line width=.2pt]
118 {\includegraphics[width=\docshots@left]
119 {\docshots@tmpdir/\jobname/\hash.crop.pdf}};%
120 \hspace{\docshots@hspace}%
121 \begin{minipage}[t]{\docshots@right}%
122 \vspace{0pt}%
123 \ifdefined\docshots@lstinputlisting%
124 \expandafter\lstinputlisting\expandafter[\docshots@opts]
125 {\docshots@tmpdir/\jobname/\hash.tex}%
126 \else\ifdefined\docshots@inputminted%
127 \expandafter\inputminted\expandafter[\docshots@opts]
128 {\docshots@inputminted}
129 {\docshots@tmpdir/\jobname/\hash.tex}%
130 \else%
131 \expandafter\VerbatimInput\expandafter[\docshots@xopts]
132 {\docshots@tmpdir/\jobname/\hash.tex}%
133 \fi\fi%
134 \vspace{0pt}%
135 \end{minipage}%
136 \par%
137 \end{group}%
138 \docshotOptions{}%
139 }\makeatother

```

`\docshotPrerequisite` Then, we define `\docshotPrerequisite` command:

```

140 \makeatletter\newcommand\docshotPrerequisite[1]{
141 \iexec[\docshots@log,quiet]{cp #1 "\docshots@tmpdir/\jobname"}%
142 \message{docshots: File '#1' copied to
143 '\docshots@tmpdir/\jobname/#1'^^J}%
144 }\makeatother

```

`\docshotAfter` Then, we define `\docshotAfter` command:

```

145 \makeatletter\newcommand\docshotAfter[1]{
146 \iexec[\docshots@log,quiet]{/bin/echo -n '\detokenize{#1}'
147 > "\docshots@tmpdir/\jobname/after.sh"}%
148 \message{docshots: File
149 '\docshots@tmpdir/\jobname/after.sh' created^^J}%
150 }\makeatother

```

`\docshotOptions` Finally, we define `\docshotOptions` command:

```

151 \makeatletter
152 \gdef\docshots@opts{}
153 \newcommand\docshotOptions[1]{%
154 \gdef\docshots@opts{#1}%
155 }\makeatother

```



## Change History

0.0.1	General: Initial version . . . . .	5	0.1.1	\docshots@mdfive: New supplementary command added to calculate MD5 sum of a file. . . . .	6
0.0.3	General: The command is added to enable copying of supplementary files into docshots snippets processing directory. . . . .	4	0.2.0	General: New package option "nocrop" added to allow disabling of "pdfcrop" execution. . . . .	5
0.0.4	General: Package options "lstinputlisting" and "inputminted" introduced to enable printing of verbatim text either via listings or minted packages. . . . .	5	0.3.0	\docshotOptions: New command introduced to help specify custom options for verbatim environments. . . . .	8
0.0.5	General: Package option "log" added, which enables detailed logging via exec. By default, there is no logging at all. . . . .	5	0.3.1	docshot: A bug fixed, now handling of leading percentage symbols is done right. . . . .	6
0.1.0	docshot: The output is saved to a hash-named file, for better uniqueness of temporary files. . . . .	6	0.4.0	docshot: Now, $\TeX$ output has a log message with the number of the line in the source file, which we render. . . . .	6

# Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in *roman* refer to the code lines where the entry is used.

<b>B</b>		95, 119, 125, 129,	<b>L</b>			
<code>\begin</code> .....	49, 121	132, 141, 143, 147, 149	<code>\linewidth</code> .....	32, 34, 36		
<b>C</b>		<code>\docshots@xopts</code> ...	<code>\lstinputlisting</code> ..	124		
<code>\color</code> .....	99	97, 105, 108, 111, 131				
<b>D</b>		<b>E</b>	<b>M</b>			
<code>\def</code> .....	9, 13, 14, 56, 97	<code>\edef</code> .....	105, 108, 111	<code>\makeatletter</code> .....	47, 48, 140, 145, 151	
<code>\detokenize</code> .....	146	<code>\end</code> .....	51, 135	<code>\makeatother</code> .....	47, 139, 144, 150, 155	
<code>\docshot</code> .....	48	<code>\expandafter</code> ...	105,	<code>\message</code> .....	58, 62, 74, 84, 142, 148	
<code>\docshotAfter</code> .....	145	108, 111, 124, 127, 131				
<code>\docshotOptions</code>	138, 151	<b>F</b>				
<code>\docshotPrerequisite</code>	140	<code>\foreach</code> .....	63	<b>N</b>		
<code>\docshots@dtx</code> ....	12, 52	<b>G</b>				
<code>\docshots@gs</code> .....	25, 44	<code>\gdef</code> .....	152, 154	<code>\newcommand</code>	47, 140, 145, 153	
<code>\docshots@hspace</code>	31, 120	<b>H</b>		<code>\newenvironment</code> ....	48	
<code>\docshots@inputminted</code>	16, 126, 128	<code>\hash</code> .....	56, 57, 59,	<code>\node</code> .....	116	
<code>\docshots@left</code> ..	33, 118	61, 65, 66, 72, 80,	<b>P</b>			
<code>\docshots@log</code>	9, 13, 40,	83, 85, 89, 90, 94,	<code>\par</code> .....	114, 136		
42, 44, 60, 64, 77,		95, 119, 125, 129, 132	<code>\pdf@filemdfivesum</code> ..	47		
79, 82, 88, 92, 141, 146		<code>\hspace</code> .....	120	<code>\pgfkeys</code> .....	10	
<code>\docshots@lstinputlisting</code>	15, 123	<b>I</b>		<code>\ProcessPgfOptions</code> ..	39	
<code>\docshots@margin</code>	29, 116	<code>\iexec</code> .....	40, 42, 44,	<b>R</b>		
<code>\docshots@mdfive</code> ..	46, 56	45, 53, 60, 64, 77,	<code>\RequirePackage</code> ..			1,
<code>\docshots@nocrop</code> ..	14, 41, 87	79, 82, 88, 92, 141, 146	2, 3, 4, 5, 6, 7, 8, 46			
<code>\docshots@opts</code> ..	110,	<code>\ifdefined</code> ..	41, 52, 87,	<b>S</b>		
111, 124, 127, 152, 154		104, 107, 110, 123, 126	<code>\scriptsize</code> .....			108
<code>\docshots@pdfcrop</code> ..	27, 42, 92	<code>\IfFileExists</code> ..	57, 76, 83	<code>\small</code> .....	105	
<code>\docshots@pdflatex</code> ..	23, 40, 68	<code>\ifluatex</code> .....	18	<code>\space</code> .....	80	
<code>\docshots@right</code> ..	35, 121	<code>\ifnum</code> .....	73	<b>T</b>		
<code>\docshots@runs</code> ...	21, 63	<code>\ifxetex</code> .....	18	<code>\the</code> .....	62	
<code>\docshots@small</code> ..	19, 104	<code>\includegraphics</code> ..	118	<code>\tikz</code> .....	115	
<code>\docshots@tiny</code> ..	20, 107	<code>\inputlineno</code> .....	62	<b>U</b>		
<code>\docshots@tmpdir</code> ..	17,	<code>\inputminted</code> .....	127	<code>\unexpanded</code> ..	105, 108, 111	
45, 50, 54, 56, 57,		<b>J</b>		<b>V</b>		
59, 60, 61, 65, 66,		<code>\jobname</code>	45, 50, 54, 56, 57,	<code>\VerbatimEnvironment</code>	49	
67, 76, 78, 79, 82,		59, 60, 61, 65, 66,	67, 76, 78, 79, 82,	<code>\VerbatimInput</code> ....	131	
83, 85, 89, 90, 94,		67, 76, 78, 79, 82,	83, 85, 89, 90, 94,	<code>\vspace</code> .....	122, 134	
95, 119, 125, 129,		83, 85, 89, 90, 94,	95, 119, 125, 129,			
132, 141, 143, 147, 149		95, 119, 125, 129,	132, 141, 143, 147, 149			